

DIRECTIONAL EXIT BLADE

Product Features

- Maintained emergency exit blade with easy access to change legend direction on site
- LiFePO4 battery with self-test functionality as standard
- Ceiling or wall mounted mounting options as standard with accessories for recessed and suspending
- Polycarbonate body with double sided acrylic legend



INCLUDING BATTERY

CAT NO.	TYPE	WATTAGE	FINISH
LEBLDW	Self-Test	2.5W	White
LEBLDB	Self-Test	2.5W	Black

Product Accessories

CAT NO.	DESCRIPTION
LEBLDWRC	Recessing Kit (White only)
LEBLDWSA	Side Arm Bracket (White only)
LEBLDSUS	1 metre Suspension Kit

CAT NO.	WEIGHT(Kg)	CRI	FREQUENCY (Hz)	IK RATING	BATTERY TYPE	BATTERY CAPACITY	TEMP RANGE (°C)	AMBIENT TEMP RATED LIFE (°C)
LEBLDW	0.52	≥80	50-60hz	IK04	LiFePO4 3.2V	1000mAh	-5 to +25	25
LEBLDB	0.52	≥80	50-60hz	IK04	LiFePO4 3.2V	1000mAh	-5 to +25	25

STANDARD	DESCRIPTION
60598-1	Luminaires – General requirements
60598-2-22	Luminaires – Emergency
61000-3-2	Electromagnetic compatibility (EMC) - Part 3-2: Limits – for harmonic current emissions
61000-3-3	Lamp controlgear – Part 1: General and safety requirements
61547	Equipment for general lighting purposes – EMC immunity requirements
55015	Limits and methods of measurement of radio disturbance characteristics of electrical lighting and similar equipment



Product Drawing

