

Product Information VG.20.02

13-03-2018

VatOil A.T.F. Type III

Description

ATF Type III is a modern automatic transmission fluid, which meets the latest GM Dexron III specifications. ATF Type III is based on special mineral base oils and selected additives to give the product the following properties:

- Very low viscosity at low temperatures
- Extremely high and stable viscosity index
- Excellent stability against oxidation at high temperatures
- Good anti-wear, anti-corrosion and anti-foaming qualities
- Specific friction properties
- Does not affect seals and non-ferrous metals

Application

ATF Type III can be used for automatic transmissions, power-steering units, torque converters and other applications, for which a GM Dexron III or any of the following specifications is recommended.

Specifications

Meets the requirements of

Dexron IID/IIE/IIIF/IIIG/IIIH

MB 236.1/236.5/236.6/236.7/236.9

Ford Mercon/M2C138-CJ/166-H

MAN 339 Typ Z1/V1

Allison C4/TES-389

Cat TO-2

Voith 55.6335 (G607)

Volvo 97341

ZF TE-ML 02F/03D/04D/09A/09B/11A/11B/14A/17C

Typicals

Density at 15 °C, kg/l 0,853

Viscosity 40 °C, mm²/s 37,70

Viscosity 100 °C, mm²/s 7,60

Viscosity Index 175

Flash Point COC, °C 210

Pour Point, °C -51

Total Base Number, mgKOH/g 1,9

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Available packagings



50088
1 L bottle



50495
4 L can



50089
20 L can



50090
60 L drum



50128
210 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.