

- Type: Digital AF/AE single-lens reflex camera with built-in flash
- Recording Media: SD card, SDHC card, SDXC memory card
- Compatible with Ultra High Speed (UHS-I) memory cards and Eye-Fi cards.
- Image Format: Approx. 22.3mm x 14.9mm (APS-C)
- Compatible Lenses: Canon EF lenses (including EF-S lenses)
- Lens Mount: Canon EF mount

Image Sensor

- Type: CMOS Sensor
 - Pixels: Effective pixels: Approx. 24.20 megapixels
Total pixels: Approx. 24.70 megapixels
 - Pixel Unit: 3.72 μ m square
 - Aspect Ratio: 3:2 (Horizontal : Vertical)
 - Color Filter System: RGB primary color filters
 - Low Pass Filter: Fixed position in front of the image sensor
 - Dust Deletion Feature: (1) Self Cleaning Sensor Unit
Removes dust adhering to the low-pass filter.
Self-cleaning executed automatically (taking approx. 2 sec.) when power is turned on or off. Manual execution also possible (taking approx. 5 sec.).
- (2) Dust Delete Data acquisition and appending
The coordinates of the dust adhering to the low-pass filter are detected by a test shot and appended to subsequent images.
The dust coordinate data appended to the image is used by the provided software to automatically erase the dust spots.
- (3) Manual cleaning

Recording System

- Recording Format: Complies with Design rule for Camera File system 2.0 and Exif 2.30

- File Size: 3:2

1. Large: Approx. 24.00 Megapixels (6000 x 4000)
2. Medium: Approx. 10.60 Megapixels (3984 x 2656)
3. Small 1: Approx. 5.90 Megapixels (2976 x 1984)
4. Small 2: Approx. 2.50 Megapixels (1920 x 1280)
5. Small 3: Approx. 0.35 Megapixels (720 x 480)
6. RAW: Approx. 24.00 Megapixels (6000 x 4000)

4:3

1. Large: Approx. 21.30 Megapixels (5328 x 4000)
2. Medium: Approx. 9.50 Megapixels (3552 x 2664)
3. Small 1: Approx. 5.30 Megapixels (2656 x 1992)
4. Small 2: Approx. 2.20 Megapixels (1696 x 1280)
5. Small 3: Approx. 0.31 Megapixels (640 x 480)
6. RAW: Approx. 24.00 Megapixels (6000 x 4000)

16:9

1. Large: Approx. 20.20 Megapixels (6000 x 3368)
2. Medium: Approx. 8.90 Megapixels (3984 x 2240)
3. Small 1: Approx. 5.00 Megapixels (2976 x 1680)
4. Small 2: Approx. 2.10 Megapixels (1920 x 1080)
5. Small 3: Approx. 0.29 Megapixels (720 x 408)
6. RAW: Approx. 24.00 Megapixels (6000 x 4000)

1:1

1. Large: Approx. 16.00 Megapixels (4000 x 4000)
2. Medium: Approx. 7.10 Megapixels (2656 x 2656)
3. Small 1: Approx. 3.90 Megapixels (1984 x 1984)
4. Small 2: Approx. 1.60 Megapixels (1280 x 1280)
5. Small 3: Approx. 0.23 Megapixels (480 x 480)
6. RAW: Approx. 24.00 Megapixels (6000 x 4000)

- Backup Recording: N/A

- File Numbering: The following three types of file numbering method can be set:

(1) Continuous numbering

- The numbering of captured images will continue even after you replace the camera's card.

(2) Auto reset

- When you replace the camera's card, the numbering will be reset to start from 0001. If the new card already contains images, the numbering will continue from the last recorded image in the card.

(3) Manual reset

- Resets the file number to 0001, and creates a new folder automatically.
- RAW + JPEG Simultaneous Recording: Yes
- Color Space: sRGB, Adobe RGB
- Picture Style: Auto, Standard, Portrait, Landscape, Neutral, Faithful, Monochrome, User Defined 1-3
- In Basic Zone modes, "Auto" is set automatically.
- In Creative Zone modes, you can select or set the Picture Style.
- Default settings for [User Defined 1-3] are [Auto].

White Balance

- Settings: Auto, Preset (Daylight; Shade; Cloudy, Twilight, Sunset; Tungsten light; White Fluorescent Light; Flash), Custom (Approx. 2,000° - 10,000°K), White Balance Correction, and White Balance Bracketing
- Auto White Balance: Auto white balance with the image sensor
- Color Temperature Compensation: White balance correction:
 - Blue/amber bias: ± 9 levels
 - Magenta/green bias: ± 9 levels
- Correction based on the current WB mode's color temperature.
- Color Temperature Information Transmission: Provided

Viewfinder

- Type: Eye-level SLR (with fixed pentamirror)
- Coverage: Approx. 95% vertically and horizontally (with Eye point approx. 19mm)
- Coverage is approx. 93% when aspect ratio is set to 16:9.
- Magnification: Approx. $0.82x / 23.2^\circ$ (50mm lens ∞ , -1 m^{-1})
- Eye Point: Approx. 19 mm (At -1m^{-1} from the eyepiece lens center)
- Dioptric Adjustment Correction: Adjustable from approx. -3.0 to $+1.0 \text{ m}^{-1}$ (dpt)
- Focusing Screen: Fixed
- Mirror: Quick-return half mirror (transmission: reflection ratio of 40:60)
- Viewfinder Information:
 - AF information
AF points and focus confirmation
 - Exposure information
Shutter speed, aperture, ISO speed (always displayed), AE lock, exposure level, spot metering circle, exposure warning, flicker detection indicator
 - Flash information
Flash ready, flash exposure compensation, high-speed sync, FE lock, red-eye reduction light
 - Image information
Highlight tone priority (D+), maximum burst (1-digit display), white balance correction, SD card information
- Depth Of Field Preview: Enabled with depth-of-field preview button

Autofocus

- Type: TTL secondary image-forming, phase-difference detection
- AF Points: 19 points
All AF points are cross-type at f/5.6
Center AF point is diagonal cross-type at f/2.8
- AF Working Range: EV -0.5 - 18 (at room temperature and ISO 100, based on Canon's testing standards)
- Focusing Modes: (1) Autofocus
 - One-Shot AF
 - Predictive AI Servo AF

- AI Focus AF (*Switches between One-Shot AF and AI Servo AF)
*Switches between One-Shot AF and AI Servo AF

(2) Manual focus (MF)

- AF Point Selection: (1) Manual selection

(2) Auto selection

- Automatically set in Basic Zone modes.
- Selected AF Point Display: Indicated by superimposed display in the viewfinder and on the LCD monitor.
- AF Assist Beam: Intermittent firing of built-in flash
Effective range: Approx. 13.1 ft. / 4m at center, approx. 11.5 ft. / 3.5m at periphery
- With an EOS-dedicated Speedlite attached, the Speedlite's AF-assist beam is emitted instead.
- Compatible with AF assist-beam (intermittent firing) of 320EX, 270EX II, and 270EX flashes.

Exposure Control

- Metering Modes: 7560-pixel RGB+IR metering sensor
Metering with the area divided into 63 segments (9x7)
 - 1) Evaluative metering (linked to all AF points)
 - 2) Partial metering (center, approx. 6.0% of viewfinder)
 - 3) Spot metering (center, approx. 3.5% of viewfinder)
 - 4) Center-weighted average metering
- Metering Range: EV 1 - 20 (at 23°C / 73°F with 50mm f/1.8 II lens at ISO 100)
- Exposure Control Systems: **Creative Zone**

(1) Program AE (shiftable)

(2) Shutter-priority AE

(3) Aperture-priority AE

(4) Manual exposure (including bulb)

Basic zone

(1) Scene Intelligent Auto (Program AE / non-shiftable)

(2) Flash Off

(3) Creative Auto

- When background blurring is set, shooting with flash is disabled. When the flash is raised, background blurring cannot be set.

(4) Portrait

(5) Landscape

(6) Close-up

(7) Sports

(8) Special Scene

- • Kids
 - • Food
 - • Candlelight
 - • Night Portrait
 - • Handheld Night Scene
 - • HDR Backlight Control mode
- ISO Speed Range: **For Stills:**
Manual setting range of ISO 100-12800, expansion to IS 25600 equivalent.

Shooting Mode		ISO Settings	
		Without Flash	With Flash
Auto, Flash OFF, Creative Auto, Portrait, Macro, Sports		ISO 100–6400	ISO 400 ²³ (excluding Auto, Children, Night Portrait, Handheld Night Scene)
Landscape		ISO 100–1600	
Scene	Children, Food, Candlelight, Night Portrait, HDR, Backlight Control	ISO 100–6400	
	Handheld Night Scene	ISO 100–12800	
P, TV, Av, M ²		ISO 100–6400 ³	
With flash		ISO 400	

¹: Depends on the maximum ISO speed that has been set.

²: If fill-flash will result in overexposure, the ISO speed can be set to ISO 100 at the maximum.

³: If you use bounce flash with an external Speedlite in the Creative Auto, Portrait, Landscape, Macro, Sports, Food, or P mode, the ISO speed is set automatically within ISO 400–ISO 1600 (or up to the maximum limit) to match the brightness.

- Exposure Compensation: (1) Manual: ± 5 stops in 1/3- or 1/2-stop increments
- (2) AEB : ± 2 stops in 1/3- or 1/2-stop increments
- If the exposure compensation exceeds ± 2 stops, the left or right icon appears in the viewfinder.
- Manual exposure compensation and AEB can be set in combination.
- AEB is set in the following sequence: Standard exposure, decreased exposure, and increased exposure.
- If AEB is used with the self-timer, the three bracketed shots will be taken in succession after the 10-sec. or 2-sec. delay.

- AE Lock: (1) Auto AE lock
- In the One-Shot AF mode with evaluative metering, AE lock takes effect when focus is achieved.

(2) Manual AE lock

- In the P, Tv, Av, and M modes, enabled with the AE lock button. (Press again to update.)
- Enabled in all metering modes.

Shutter

- Type: Vertical-travel, mechanical, focal-plane shutter with all speeds electronically-controlled
- Electronic 1st curtain and mechanical 2nd curtain
- Shutter Speeds: 1/4000 to 30 sec., Bulb (total shutter speed range)
X-sync at 1/200 sec.
- Shutter Release: Soft-touch electromagnetic release
- Self Timer: 10-sec. or 2-sec. Delay
- Shutter Lag Time:
 1. During SW-1 ON, time lag between SW-2 ON and start of exposure: approx. 0.075 sec.
*Approx. 0.100 sec. for Silent Shooting: approx. 0.250 sec. with flash
 2. Time lag between simultaneous SW-1/SW-2 ON and start of exposure: Approx. 0.240 sec.
*Time lag with the aperture stopped down by 3 stops or less (Excludes AF operation time).
*Approx. 0.265 sec. for Silent Shooting

External Speedlite

- Flash Metering: E-TTL II autoflash (evaluative flash metering and average flash metering), FE Lock
- Flash Exposure Compensation: ± 2 stops in 1/3-stop or 1/2-stop increments
- FE Lock: Provided
- External Flash Settings: (1) External flash function setting
- Flash firing, E-TTL II auto flash system, flash mode, wireless sender, zoom, sync setting, flash exposure compensation, FEB, and clear setting.
- With the 600EX-RT, radio wireless transmission control is possible.

(2) External flash C.Fn setting

- The actual setting options for (1) and (2) will differ depending on the Speedlite used.
- PC Terminal: Not Provided

Drive System

- Drive Modes:
 1. Single shooting
 2. Continuous shooting
Max. approx. 5.0 fps
 3. At 1/500 sec. or faster shutter speed, and at the maximum aperture (varies depending on the lens).
 4. Silent single shooting
 5. Silent continuous shooting
Max. approx. 3.0 fps
 6. 10-sec. self timer/remote control
 7. 2-sec. self-timer
 8. Continuous shooting after 10-sec. self-timer (2 to 10 shots)
- Continuous Shooting Speed: High-speed continuous shooting: Max. approx. 5.0 fps
- Maximum Burst: **Number of Shots Based on 8GB memory Card:**
 - JPEG Large/Fine: Approx. 180
 - JPEG Large/Normal: Approx. 1810 (Full)
 - Medium/Fine: Approx. 1770 (Full)
 - Medium/Normal: Approx. 3500 (Full)
 - S1/Fine: Approx. 2830 (Full)
 - S1/Normal: Approx. 5320 (Full)
 - S2: Approx. 5320 (Full)
 - S3: Approx. 20180 (Full)
 - RAW: Approx. 7 Shots
 - RAW+JPEG Large/Fine: 6 Shots

Number of Shots Based on 8GB UHS-I memory card:

- JPEG Large/Fine: Approx. 940 (Full)
- JPEG Large/Normal: Approx. 1810 (Full)
- Medium/Fine: Approx. 1770 (Full)
- Medium/Normal: Approx. 3500 (Full)
- S1/Fine: Approx. 2830 (Full)

S1/Normal: Approx. 5320 (Full)

S2: Approx. 5320 (Full)

S3: Approx. 20180 (Full)

RAW: Approx. 8 Shots

RAW+JPEG Large/Fine: 6 Shots

- The number of possible shots and maximum burst are those obtained with the 8 GB card of Canon's testing standards.
- The file size, number of possible shots, and maximum burst differ depending on shooting conditions (aspect ratio of 3:2, subject, memory card brand, ISO speed, Picture Style, etc.).
- Figures appended with an "Full" indicate that continuous shooting is possible until the card becomes full.

Live View Functions

- Shooting Modes: Still photo shooting and video shooting
- Focusing: (1) Hybrid CMOS AF III
- Covers approx. 80% (width) x 80% (height) of the screen area.

(2) Manual focus

*Manual focusing by enlarging images by approx. five to ten times

- Metering Modes: Real-time evaluative metering with image sensor.
 - (1) Evaluative metering (315 zones)
 - (2) Partial metering (approx. 10.0% of Live View screen)
 - (3) Spot metering (approx. 2.7% of Live View screen)
 - (4) Center-weighted average metering
- AE lock possible. The active metering time can be changed.
- Metering Range: EV 0 - 20 (at 73°F/23°C at ISO 100); EV 0 - 18 (with Hybrid CMOS AF III at 73°F/23°C at ISO 100)
- Grid Display: (1) 3x3
 - (2) 6x4
- Exposure Simulation: Provided
- Silent Shooting: Not provided

Video Shooting

- File Format: MP4:
Movie: MPEG-4 AVC / H.264
- Variable (average) bit rate
Audio: AAC
MOV: MOV format movie cannot be shot. (playback is possible)
- File Size: Recording Size:
[Full HD]
Standard: 1920 x 1080 (30 fps/25 fps/24 fps): 216 MB/min.
Lightweight: 1920 x 1080 (30 fps/25 fps): 87 MB/min.

[HD]
Standard: 1280 x 720 (60 fps/50 fps): 187 MB/min.
Lightweight: 1280 x 720 (30 fps/25 fps): 30 MB/min.

[SD]
Standard: 640 x 480 (30 fps/ 25 fps): 66 MB/min.
Lightweight: 640 x 480 (30 fps/ 25 fps): 23 MB/min.
- If the recording time reaches 29 min. 59 sec., the movie shooting stops automatically.
- The file size is 4 GB, and shooting does not stop automatically.
- Frame Rates: 1920 x 1080 (Full HD): 30p (29.97) / 24p (23.976) / 25p

1280 x 720 (HD): 60p (59.94) / 50p

640 x 480 (SD): 30p (29.97) / 25p
- Continuous Shooting Time:

MP4 Format						
Video Recording Size			Total Recording Time			File Size
			4GB	8GB	16GB	
1920 x 1080	30fps 25fps 24fps	Standard	17 min.	35 min	1 hr. 10 min.	216
	30fps 25fps 24fps	Lightweight	43 min.	1 hr. 26 min.	2 hr. 53 min.	87
1280 x 720	60fps 50fps	Standard	20 min.	40 min.	1 hr. 21 min.	187
	60fps 50fps	Lightweight	2 hr. 5 min.	4 hr. 10 min.	8 hr. 20 min.	30
640 x 480	30fps 25fps	Standard	57 min.	1 hr. 55 min.	3 hr. 50 min.	66
	30fps 25fps	Lightweight	2 hr. 43 min.	5 hr. 26 min.	10 hr. 53 min.	23

If recording time reaches 29 min. 59 sec., movie shooting stops automatically.

See Frame Rates section for actual frame rates

- Focusing: (1) Hybrid CMOS AF III
- Covers approx. 80% (width) x 80% (height) of the screen area.
- (2) Manual focus
- Magnify the image by approx. 5x or approx. 10x and focus manually.
- Range: 8 bit, 0 - 255
- Exposure Control: (1) Program AE for movie shooting
- In Basic Zone modes, P, Av, and Tv modes
- Shutter speed 1/30 - 1/4000 sec. (Signal accumulation time), aperture, and ISO speed automatically set.
- (2) Manual exposure
- Shutter speed (signal accumulation time), aperture, and ISO speed (auto/manual) manually set. The shutter speed (signal accumulation time) is limited to 1/4000 sec. at the maximum and to 1/30 sec. at the

minimum for 24/25/30 fps or 1/60 sec. or higher for 50/60 fps.

- Exposure Compensation: Provided (± 3 stops in 1/3-stop increments)
- For video, exposure compensation will not be applied beyond ± 3 stops even if the exposure compensation has been set beyond ± 3 stops.
- For still photo shooting, the exposure compensation can be set and applied up to ± 5 stops.

LCD Monitor

- Type: TFT color, liquid-crystal monitor with Touch Panel LCD (capacitive type)
- Monitor Size: Wide 3.0-inch (Screen aspect ratio of 3:2)
7.7cm diagonal (6.37cm wide, 4.25cm high)
- Pixels: Approx. 1,040,000 dots
- Coverage: Approx. 100%
- Brightness Control: Adjustable to one of seven levels
- Coating: Anti-smudge coating
- Interface Languages: 25 (English, German, French, Dutch, Danish, Portuguese, Finnish, Italian, Norwegian, Swedish, Spanish, Greek, Russian, Polish, Czech, Hungarian, Romanian, Ukrainian, Turkish, Arabic, Thai, Simplified/Traditional Chinese, Korean, Japanese)

Playback

- Display Format:
 1. Single image display
 - Single image, basic information, detailed information, histogram display
 2. Index display
 - 4/9/36/100 images
 3. Jump display (Image jump w/ Main Dial)
 - 1/10/100 images, shooting date, by folder, movies only, stills only, by rating
- Highlight Alert: On the detailed information and histogram displays, highlight areas with no image data will blink.
- Histogram: Brightness / RGB

Quick Control Function

- Items: When you press the Quick Control function button under the following conditions, you can set the functions below:
 1. During still photo playback:
Image protect, image rotate, rating, Creative Filters, resize, Cropping, and image jump with Main Dial
 2. During movie playback:
Image protect, rating, and image jump with Main Dial

Image Protection and Erase

- Protection: Erase protection can be applied/canceled for a single image, all images in a folder, or all images on the card
- Erase: Erase single image, erase selected images, erase all images in folder, erase all images on a card, or erase only unprotected images

Direct Printing

- Compatible Printers: PictBridge-compatible printers
- Printable Images: RAW, JPEG, and RAW+JPEG images complying to Design rule for Camera File System
- Movies cannot be printed.

DPOF: Digital Print Order Format

- DPOF: Complies to DPOF Version 1.1

Direct Image Transfer

- Compatible Images: Not Provided

Customization

- Custom Functions: 13 Custom Functions with 41 settings settable with the camera
- Custom Controls: Not Provided
- My Menu Registration: Up to six top-tier menu options and Custom Function settings can be registered

Interface

- USB Terminal:
 - For personal computer communication and PictBridge (Hi-Speed USB)
 - Audio (stereo)/video (NTSC/PAL) output
 - To connect a GP-E2 GPS Receiver
- Video Out Terminal: Type C (Switches automatically to suit the resolution)
Video output: 1080/60i, 1080/50i, 480/60p, 576/50p
- Switches automatically to 1, 2, 3, or 4 to suit the TV
- Extension System Terminal: 3.5mm diameter stereo mini-jack

Power Source

- Battery: One Battery Pack LP-E17
- With the AC Adapter Kit ACK-E18, AC power is possible.
- With Battery Grip BG-E18, it is possible to use two Battery Pack LP-E17 units.
- Battery Life: 1) Camera body only, LP-E17 x1

Shooting Method	Temperature	Possible Shots	
		AE 100%	AE 50%, FA 50%
Viewfinder Shooting	73°F / 23°C	550	440
	32°F / 0°C	470	400
Live View Shooting	73°F / 23°C	200	180
	32°F / 0°C	170	150

2) Using Battery Grip BG-E18

Shooting Method	Power Source	Temperature	Possible Shots	
			AE 100%	AE 50%, FA 50%
Viewfinder Shooting	LP-E17 x2	73°F / 23°C	1,100	880
		32°F / 0°C	940	800
Live View Shooting	LP-E17 x2	73°F / 23°C	400	360
		32°F / 0°C	340	300

- Battery Check: Automatic battery level check when power is turned ON.

Battery level indicated in one of four levels on LCD monitor.

- Power Saving: Power turns off after the set time of non-operation elapses
- [Auto power off] settable to 30 sec., 1 min., 2 min., 4 min., 8 min., 15 min. or disable
- Date/Time Battery: Built-in secondary battery
It is not replaceable by the user. It recharges when the batter pack is loaded or when the AC adapter is connected. Without any recharging, the backup battery can maintain the date/time for approx. 3 months. The backup battery takes approx. 8 hours to be fully recharged.
- Start-up Time: Approx. 0.18 sec. (based on CIPA testing standards)

Dimensions and Weight

- Dimensions (W x H x D): Approx. 5.20 x 3.98 x 3.07 in.
Approx. 131.9 x 100.9 x 77.8mm
- Weight: Approx. 19.58 oz. / 555g (CIPA standard)
Approx. 17.99 oz. / 510g (Body only)

Operating Environment

- Working Temperature Range: 32-104°F/0-40°C
- Working Humidity Range: 85% or less

All data are based on Canon's Standard Test Method. Subject to change without notice.

