




SAND STONE

STONE TALES
COMPACT



COLLECTION CATALOGUE

unicomstarker®

SAND STONE
60 x 90_60 x 60_30 x 60 - 24" x 36" _ 24" x 24" _ 12" x 24"



SIZES & DECORS



60 X 120
 24" X 48"
 RETTIFICATO **66**

60 X 90
 24" X 36"
 RETTIFICATO **69**

60 X 60
 24" X 24"
 RETTIFICATO **54**

30 X 60
 12" X 24"
 RETTIFICATO **51**

30 X 60
 12" X 24"
 PLANK **29**

30 X 30
 12" X 12"
 MOSAICO **115**

PEZZI SPECIALI | SPECIAL ITEMS | PIÉCES ESPECIALES | FORMTEILE

GRADINO RETTIFICATO	GRADONE COSTA RETTA RETTIFICATO	GRADONE ANG. COSTA RETTA DX SX RETTIFICATO	ELEMENTO A L RETTIFICATO	BATTISCOPA SMALTATO RETTIFICATO
30 x 60 12" x 24" 33	30 x 60 x 3.2 12" x 24" x 1.26" 115	30 x 30 x 3.2 12" x 12" x 1.26" 118	30 x 60 x 5 12" x 24" x 2" 49	7 x 60 2 3/4" x 24" 15

SAND STONE		spessore thickness	pezzi/sc pcs/box	mq/sc sqm/box	kg/sc kgs/box	sc/pl box/pal	mq/pl sqm/pal	kq/pl kgs/pal
60x120 24"x48"	rettificato	10	2	1.44	14.75	32	46.08	944.00
60x90 24"x36"	rettificato	10	2	1.08	22.05	48	51.84	1058.40
60x60 24"x24"	rettificato	10	3	1.08	21.35	40	43.20	854.00
30x60 12"x24"	rettificato	10	6	1.08	21.28	40	43.20	851.20
30x30 12"x12"	mosaico		11	0.99	18.00	36	35.64	648.00
30x60 12"x24"	plank		5		20.00			
7x60 3"x24"	battiscopa smalt. rett.		12		11.40			
30x60 12"x24"	gradino rettificato		8		31.60			
30x60 12"x24"	gradone costa retta rett.		4		19.40			
30x30 12"x12"	gradone ang. costa retta rett.		2		4.40			
30x60 12"x24"	elemento a L		4		17.20			

CARATTERISTICHE TECNICHE | TECHNICAL FEATURES | CARACTERISTIQUES TECHNIQUES | TECHNISCHE EIGENSCHAFTEN

	ISO 10545-3 assorbimento d'acqua / water absorption	< 0.5%	NATURALE DIN5 1097 / DIN5 1130 coefficiente d'attrito (scivolosità) / dynamic coefficient of friction (slipperiness)	A / R10	
	ISO 10545-4 resistenza alla flessione / breaking strength	35 N/mm²	ANSI A 137.1 / DCOF BOT 3000 E	> 0.42	
	ISO 10545-13 resistenza agli acidi / resistance to acid	GLA		V3 var. moderata / V3 moderate var.	
	ISO 10545-12 resistenza al gelo / frost resistance	resiste / frost proof		ISO 10545-2 planarità / surface flatness	± 0.5%
	ISO 10545-14 resistenza alle macchie / stain resistance	4		ortogonalità / orthogonality	± 0.6%
	spessore / thickness	10 mm			

SAND STONE
60 x 120 - 24" x 48"