

HT RESIDENTIAL SMARTSERIES® PROGRAMMABLE WALL HEATER



IDEAL SPACES

- Bedrooms
- Living/Family Rooms
- Kitchens
- Bathrooms
- Basements
- Offices
- Conference Rooms
- Hallways
- Lobbies
- Waiting Rooms
- Entrance Ways
- Vestibules

COLORS

- White
- Gray

DIMENSIONS

- Grille: 19-9/16"H x 13-11/16"W x 1"D
- Back Box: 17-7/16"H x 12"W x 3-3/4"D

TEMP RANGE

- 40°– 99°F

CFM

- 100



- Heater automatically adjusts wattage output and blower speed for whisper-quiet operation and optimum comfort
- Heating element is heavy-duty, non-glowing steel fins brazed to steel sheathed tubular elements placed in grid pattern that covers the entire discharge area
- Automatic fan delay eliminates cold drafts on start-up and discharges residual heat from the heater body during shut down
- SmartSeries® Digital Thermostat: 5/2-day programming with four periods per day
- Contemporary, clean design with easy to use LED touch screen
- Easy installation - heater is mounted prior to wiring. Both hands are free to make field connections in spacious compartment

HT RESIDENTIAL SMARTSERIES® PROGRAMMABLE WALL HEATER

MODELS & SPECIFICATIONS							
CATALOG NO.	UPC	VOLTS	WATTS	AMPS	PHASES	BTU/HR.	SHIP WT. (LBS.)
HT2024SS	6 85360 15351 3	240	250/2000	1.0/8.3	1	853/6826	20
HT1502SS	6 85360 15350 6	120	200/1500	1.6/12.5	1	682/5120	20
HT2024SSNW	6 85360 15854 9	240	250/2000	1.0/8.3	1	853/6826	27
HT1502SSNW	6 85360 15852 5	120	200/1500	1.6/12.5	1	682/5120	27

SURFACE MOUNTING FRAME ACCESSORIES			
CATALOG NO.	UPC	DESCRIPTION	SHIP WT. (LBS)
SMHTSSW	6 85360 15631 6	Northern White Surface Mounting Frame, 14-5/8"W x 20-1/4"H x 3-3/4"D	2.6
SMHTSSBL	6 85360 15630 9	Black Surface Mounting Frame, 14-5/8"W x 20-1/4"H x 3-3/4"D	2.6

NOTE: Mounting Limitations: Do not install heater closer than 12 in. to the floor, 12 in. to an adjacent wall, 36 in. to the ceiling. Do not install heater behind towel rack or door, upside down or sideways, in the floor, in the ceiling, or in closets.

