



TRYGG

A product by Nøsted &



TRACKS

PRODUCT CATALOG

2021

TRYGG TRACKS



DRIVA FLOAT



FRIGG ALLROUND



TYR GRIP



BALDER

Nosted & has developed four models of TRYGG forestry tracks to improve the performance of today's modern harvesters, forwarders and skidders.

TRYGG tracks are engineered to provide reliable traction, reduced ground pressure, improved fuel economy, tire protection and very long service life.

- Increased load capacity
- Increased pulling power
- Climbing and grip on steep slopes
- Ground protection, minimized rutting
- Tire protection, extended tire life
- Snow, mud, ice, wetlands
- Improved fuel economy
- Machine balance, safety

Having been through a two year development and test period all of us at Nosted & are now proud to present the finished products that perfectly represent the TRYGG quality our customers have come to expect and rely on.



- **Mountain climber**
- Grip and traction on the steepest slopes
- Thick cross bars spaced out maximize ground pressure for penetration into hard and frozen terrain
- Large cleats grip and pull through snow, ice, mud and rugged terrain
- Made of boron alloy steel milled in Germany
- Not intended for use on soft wet land



Crossbar

48 mm x 48 mm
2" x 2"



Linksystem

26 mm
1"



Crossbar cleats

50 mm x 30 mm x 50 mm
2" x 1¼" x 2"
*Single or double option

TRYGG TYR - GRIP TRACK

Stock no.	Tire size	Tire fitment	Boggie CC	Cross bar length	Kg	Lb	Unit
670100	600 - 22,5 Single Cleat			740	1210	2662	Pair
670160	600 - 26,5 Single Cleat			740	1210	2662	Pair
670161	600 - 26,5 Double Cleat			740	1210	2662	Pair
670230	710 - 24,5 Single Cleat	FKF, FKF2, A343	1430	850	1395	3069	Pair
670231	710 - 24,5 Double Cleat	FKF, FKF2, A343	1430	850	1395	3069	Pair
670261	710 - 26,5 Single Cleat	FKF2, TRS2, A331, A342, A343, A344	1500	850	1491	3280	Pair
670262	710 - 26,5 Double Cleat	FKF2, TRS2, A331, A342, A343, A344	1500	850	1491	3280	Pair
670263	710 - 26,5 Single Cleat	TRS, TRS2, T440, TiGF	1500	850	1491	3280	Pair
670264	710 - 26,5 Double Cleat	TRS, TRS2, T440, TiGF	1500	850	1491	3280	Pair
670360	750 - 26,5 Single Cleat			915	1550	3410	Pair
670361	750 - 26,5 Double Cleat			915	1550	3410	Pair



Track lock

16 locks included allow the operator to keep the "tightness" adjusted properly as the tires and tracks wear over time.

- 8 - short 105 mm / 4"
- 4 - medium 155 mm / 6"
- 4 - long 205 mm / 8"

* Installation tool and setup clamps sold separately (page 7)

* Performance comparison chart (page 7)



- **Wet land floater**
- Load bearing and machine balance on soggy wet terrain
- Wide cross bars set close together maximize footprint and minimize ground pressure
- Gentle on the forest floor and root systems
- Made of boron alloy steel milled in Germany
- Not intended for use on snow or steep slopes



Crossbar

150 mm x 16 mm
6" x 5/8"



Linksystem

26 mm
1"



Crossbar cleats

50 mm x 30 mm x 50 mm
2" x 1 1/4" x 2"
*Single or double option

TRYGG DRIVA - FLOAT TRACK

Stock no.	Tire size	Tire fitment	Boggie CC	Cross bar length	Kg	Lb	Unit
670861	710 - 26,5 Single Cleat	FKF2, TRS2, A331, A342, A343, A344	1500	850	1460	3212	Pair
670862	710 - 26,5 Double Cleat	FKF2, TRS2, A331, A342, A343, A344	1500	850	1460	3212	Pair
670863	710 - 26,5 Single Cleat	TRS, TRS2, T440, TiGF	1500	850	1460	3212	Pair
670864	710 - 26,5 Double Cleat	TRS, TRS2, T440, TiGF	1500	850	1460	3212	Pair



Track lock

16 locks included allow the operator to keep the "tightness" adjusted properly as the tires and tracks wear over time.

- 8 - short 105 mm / 4"
- 4 - medium 155 mm / 6"
- 4 - long 205 mm / 8"

* Installation tool and setup clamps sold separately (page 7)

* Performance comparison chart (page 7)



- **Foothills dozer**
- Balanced "Float" and "Grip" for a wide variety of climate and ground conditions
- Mid width cross bars are wide enough apart to provide good traction, and close enough together to provide good flotation
- Climbing, pulling, load bearing and balance
- Made of boron alloy steel milled in Germany



Crossbar

80 mm x 20 mm
3 1/8" x 3/4"



Linksystem

26 mm
1"



Crossbar cleats

50 mm x 30 mm x 50 mm
2" x 1 1/4" x 2"
* Single or double option

TRYGG FRIGG - ALLROUND TRACK

Stock no.	Tire size	Tire fitment	Boggie CC	Cross bar length	Kg	Lb	Unit
670400	600 - 22,5 Single Cleat			1290	1290	2838	Pair
670460	600 - 26,5 Single Cleat	FKF, FKF2, T428, A343		740	1326	2917	Pair
670461	600 - 26,5 Double Cleat	FKF, FKF2, T428, A343		740	1326	2917	Pair
670530	710 - 24,5 Single Cleat	FKF, FKF2, A343	1430	850	1316	2895	Pair
670531	710 - 24,5 Double Cleat	FKF, FKF2, A343	1430	850	1316	2895	Pair
670561	710 - 26,5 Single Cleat	FKF2, TRS2, A331, A342, A343, A344	1500	850	1407	3095	Pair
670562	710 - 26,5 Double Cleat	FKF2, TRS2, A331, A342, A343, A344	1500	850	1407	3095	Pair
670563	710 - 26,5 Single Cleat	TRS, TRS2, T440, TiGF	1500	850	1407	3095	Pair
670564	710 - 26,5 Double Cleat	TRS, TRS2, T440, TiGF	1500	850	1407	3095	Pair
670660	750 - 26,5 Single Cleat			1520	1520	3344	Pair
670661	750 - 26,5 Double Cleat			1520	1520	3344	Pair



Track lock

16 locks included allow the operator to keep the "tightness" adjusted properly as the tires and tracks wear over time.

- 8 - short 105 mm / 4"
- 4 - medium 155 mm / 6"
- 4 - long 205 mm / 8"

* Installation tool and setup clamps sold separately (page 7)

* Performance comparison chart (page 7)



- **Steep slope runner**
- Climbing grip and stability on rugged mountains
- Powers through snow, mud and ice
- Extends tire life and turns well worn tires into traction monsters
- Out lasts chains by up to double the hours
- Made of boron alloy steel milled in Germany
- Rough ride, increased fuel consumption compared to chains



**Crossbar
with raised ridge**



Linksystem

26 mm
1"



**Single or double
crossbar cleats**

45 mm x 20 mm x 35 mm
1 3/4" x 7/8" x 1 3/8"



TRYGG BALDER - SINGLE WHEEL TRACK						
Stock no.	Product	Spec	Cross pad length	Kg	Lb	Unit
670071	30.5X32, Single Cleat	26 mm	960	1337	2941	Pair
670072	30.5X32, Double Cleat	26 mm	961	1337	2941	Pair
670082	35.5X32, Single Cleat	26 mm	1120	1473	3240	Pair
670083	35.5X32, Double Cleat	26 mm	1121	1473	3240	Pair
670060	700/55X34, Single Cleat	22 mm l.s.	866	1592	3502	Pair
670064	710/55X34, Single Cleat	22 mm l.s.	866	1592	3502	Pair



Track lock

Three removable cross bars allow the operator to keep the "tightness" adjusted properly as the tires and tracks wear over time.

* Installation tool sold separately (page 7)

* 8 track locks included for installation



TRYGG TRACK LOCK						
Stock no.	Product	Spec	Lenght	Kg	Lb	Unit
671110	Track lock 105 4"	26 mm	105 mm	2.75	6	Each
671120	Track lock 155 6"	26 mm	155 mm	3.9	9	Each
671130	Track lock 205 8"	26 mm	205 mm	4.7	10	Each
671150	Track lock extension	50x45	120 mm	2.15	5	Each
671151	Track lock bolt	N/A	N/A	0.1	0.02	Each
671152	Track lock nut	N/A	N/A	0.03	0.06	Each



TRYGG SET UP CLAMPS				
Stock no.	Product	Kg	Lb	Unit
671450	Installation clamps	7	15.4	Pair



TRYGG INSTALLATION TOOL				
Stock no.	Product	Kg	Lb	Unit
671410	Tightening tool - TYR	6	13	Each
671415	Tightening tool - FRIGG	6	13	Each
671420	Tightening tool - DRIVA	6	13	Each
671425	Tightening tool - BALDER	6	13	Each

PERFORMANCE COMPARISON

	TYR GRIP	FRIGG ALLROUND	DRIVA FLOAT	BALDER
Grip on steep slopes	***	**	*	***
Floatation on soft ground	*	**	***	*
Stability on snow	***	**	*	***
Tire protection	*	**	***	*

WARRANTY

TRYGG Tracks are warranted to be free from defects in materials and workmanship for a period of 90 days from the date of first use. No warranty is expressed or implied as to the fitness for a particular purpose, wear ability or merchantability. Nosted & will not pay any claim for labor on any of its products or for delays or damages caused by their use. In no event shall Nosted & be held liable for any incidental or consequential damages related to use of their products. Defects should be reported to the dealer where TRYGG products were originally purchased. Repair or replacement or refund will be the options to correct products deemed to be defective.





TRYGG


TRYGG is a recognized world leader in the field of chain production. Our products, made in Norway, are especially developed for users operating in extreme environments where reliability and safety is paramount.


Nøsted & AS
4515 Grønviksveien 8
Mandal, Norway
Tel: +47 38 27 25 50
Fax: +47 38 27 25 51
E-mail: post@trygg.no
www.trygg.no

Nosted & Inc.
5495 Rue Saint-Roch
Drummondville, Quebec
Canada J2B 6V4
Tel: 888-478-2426
Fax: 819-478-1187
E-post: christian.tracy@nosted.com
www.nosted.com

 Tryggkjetting

 @trygg_chains

 Nøsted&

 @nosted_and

Thank you for choosing TRYGG! Share your photos with us! #tryggchains #tryggkjetting

DEALER: