



IDV26

DIRECT VENT GAS FIREPLACE INSERT



THE ULTIMATE IN DESIGN, ENGINEERING & QUALITY

Model IDV26N Direct Vent Insert (Natural Gas), LOGF27 Log Set, I26CV3BL Clean View (Black), IDV26RL Brick Liner.



IDV26

DIRECT VENT GAS FIREPLACE INSERT



THE ULTIMATE IN DESIGN, ENGINEERING & QUALITY

Model IDV26N Vent Insert (Natural Gas), I26CVPF1BL Clean View Picture Frame (Black), LOGF27 Log Set, IDV26RL Refractory Brick Liner.

Model	IDV26N	IDV26NE2 / NE	IDV26LP	IDV26LPE2 / LPE
Fuel	Natural	Natural	Propane	Propane
Input Max.	30,000 BTU	30,000 BTU	30,000 BTU	30,000 BTU
Input Min.	21,000 BTU	21,000 BTU	25,000 BTU	25,000 BTU
FE (P.4.1-15)	65.25%	67.37%	66.30%	68.30%

STANDARD FEATURES

- Dual Burner with glowing embers
- Millivolt valve system allows operation during power failure with adjustable flame control
- Matchless Piezo Ignition
- Ceramic Glass (Heat Radiating)
- On/Off Rocker switch
- Heat activated blower with variable speed control
- Safety Screen Barrier
- Proflame II Models include Remote Control – Features flame, fan, thermostat, smart thermostat (WiFi Compatibility*): IDV26NE2, IDV26LPE2 Models only

*Smartphone (local WiFi only)

OPTIONAL FEATURES

Log Set

Fibre Split Oak

Glass Tray with Bronze Glass

Clean View Kit

Black

Surrounds for Clean View

Black

Surround Picture Frame for Clean View

Black

Liners

Porcelain Reflective Liner or Traditional Brick

Wall Mount Thermostat

Standard On/Off or Programmable

Remote Control

On/Off, Thermostat
On/Off, Thermostat
On/Off modulating



PF1 or MV



PF2

CLEAN VIEW AND SURROUND SIZES (IN.)

IDV26	Width	Height	Depth
I26CV1	35 ⁵ / ₈ "	22 ³ / ₄ "	1 ³ / ₄ "
I26CV2	44 ⁵ / ₈ "	26 ⁵ / ₈ "	1 ³ / ₄ "
I26CVPF1	35 ⁵ / ₈ "	25 ⁷ / ₈ "	1 ³ / ₄ "
I26CVPF2	44 ⁷ / ₈ "	33 ¹ / ₂ "	1 ³ / ₄ "
I26S1	42"	27 ¹ / ₂ "	
I26SU	47 ¹ / ₂ "	35 ⁵ / ₈ " / 28 ⁵ / ₈ "*	
I26SU	39 ³ / ₈ "	29 ³ / ₄ "	
I26CV3	35 ⁵ / ₈ "	22 ³ / ₄ "	3 ¹ / ₂ "

*Dimension as a three sided surround

MINIMUM FIREPLACE OPENING (IN.)


IDV26	Width	Height	Depth
IDV26	33" / 28"*	19 ¹ / ₂ "	14 ¹ / ₄ "

*Components In (CV1) 33", Components Out (CV2) 28"


MINIMUM UNIT COVERAGE – CLEAN VIEW

IDV26	Width	Height
I26CV1*	34 ¹ / ₂ "	22"
I26CV2*	41 ¹ / ₂ "	25 ¹ / ₂ "
I26CV3*	34"	22"
I26CVPF1*	34 ¹ / ₂ "	25"
I26CVPF2*	41 ¹ / ₂ "	32 ³ / ₈ "
I26CV1DS*	34 ¹ / ₂ "	22"

*Back Frame Dimension of Clean View Kit



IDV26RL Traditional Brick Liner



LOGF27 Fibre Split Oak Logo Set

1. IDV26N Direct Vent Insert (Natural Gas), LOGF27 Log Set, I26CVPF2BL Clean View Picture Frame (Black), IDV26RL Refractory Brick Liner.
2. IDV26N Direct Vent Insert (Natural Gas), I26CV2BL Clean View Kit (Black), LOGF27 Log Set, IDV26RL Refractory Brick Liner.
3. IDV26N Direct Vent Insert (Natural Gas), I26CVPF1BL Clean View Picture Frame (Black), LOGF27 Log Set, IDV26PRL Porcelain Reflective Liner.
4. IDV26N Direct Vent Insert (Natural Gas), I26CV1BL Clean View Kit (Black), I26S1BL Surround (Black), LOGF27 Log Set, IDV26RL Refractory Brick Liner.





Find all detailed IDV26 manuals.

2340 Logan Avenue
Winnipeg, Manitoba, Canada R2R 2V3
Phone: (204) 632-1962 Fax: (204) 632-1960
www.kingsmanfireplaces.com

IDV26

DIRECT VENT GAS FIREPLACE INSERT



FOR CALIFORNIA RESIDENTS ONLY:

WARNING! This product can expose you to chemicals including Carbon Monoxide, that is an externally vented by-product of fuel consumption, which is [are] known to the State of California to cause birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov.



Model IDV26N Direct Vent Insert (Natural Gas), RSP10 Glass Tray Support with Bronze Glass, IDV26PRL Porcelain Reflective Liner, I26CV1BL Clean View (Black), I26S1BL Surround (Black).



*Components may have to be ordered separately to create a complete unit. Discuss with your local Kingsman dealer for clarification. Kingsman Fireplaces maintains a program of continuous testing, refinement and improvements of all its products. Some aspect of units shown here may be changed at any time without notice or obligation. Certification: Certified for Canada/USA as a Vented Gas Fireplace Heater ANSI Z21.88-2014, CSA 2.33-2014, CGA 2.17-M91 (R2009).

Canada

ENERGUIDE

Look for the **EnerGuide** Gas Fireplace Energy Efficiency Rating in this brochure

Based on CSA P.4.1-15



CRAFTED ENTIRELY IN CANADA, EACH KINGSMAN FIREPLACE IS BUILT TO THE HIGHEST STANDARDS AND MADE TO LAST.

Printed in Canada
08/23 - B076