

SOLACE ZERO CLEARANCE DIRECT VENT GAS FIREPLACE

Unit Illustrated: Solace HBZDV4736N Direct Vent Fireplace, LOGF36 Log Set (Fiber Split Oak), VLBIT4 Log Bits, HB47CVCK Circulating Kit (Designer Clean View), HB47RRH Liner (Red Herringbone Brick).



SOLACE.

Imagine lively gatherings or times of quiet reflection in front of the beautiful Solace. Available in two sizes, the Solace allows you to transform your fireplace into something truly unique.

With so much style and attention to detail, the Solace is available in a range of sizes and styles. You can choose from our mid-efficient rated fireplace for ambiance and taking the chill out of the room, or our higher-efficient version for additional warmth.

- · Millivolt or IPI valve system allows operation during a power failure with Hi/Low heat and flame adjustment
- Dual burner with Realistic Flame Pattern
- Safety Screen Barrier

Designer Clean View Circulating Kit: No Louvers Required

Louvers: Grills available in Black

Fan Kit: Heat activated with variable speed control


Accessories: Log sets or rock sets required

Liners: Porcelain Reflective Liner or Brick Liners

Thermostat: Wall Mount or Programmable

Remote:

Thermostat On/Off, Thermostat On/Off modulating, Thermostat On/Off modulating and fan control



MQHBZDV3636LP / LPE	Тор	Propane	29,000 BTU	22,200 BTU	67.63% / 69.25%	LOGF36
MQHBZDV4236LP / LPE	Тор	Propane	29,000 BTU	22,200 BTU	67.63% / 69.25%	LOGF36
HBZDV4736N / NE	Тор	Natural Gas	40,000 BTU	27,000 BTU	60.39% / 61.88%	LOGF36
HBZDV4736LP / LPE	Тор	Propane	36,000 BTU	30,000 BTU	53.79% / 54.90%	LOGF36
SOLACE II	Flue	Fuel	Input Max.	Input Min.	FE (P.4.1-15)	Log Sets
HBZDV3624N / NE	Тор	Natural Gas	24,000 BTU	14,000 BTU	50.48% / 52.30%	MQLOGC45, MQLOGF36BW, LOGC44
HBZDV3624LP / LPE	Тор	Natural Gas	22,000 BTU	15,000 BTU	52.59% / 54.24%	MQLOGC45, MQLOGF36BW, LOGC44
HBZDV3628N / NE	Тор	Propane	28,000 BTU	20,000 BTU	60.61% / 62.69%	MQLOGC45, MQLOGF36BW, LOGC44
HBZDV3628LP /LPE	Тор	Propane	26,000 BTU	19,000 BTU	62.48% / 64.16%	MQLOGC45, MQLOGF36BW, LOGC44
HBZDV4224N / NE	Тор	Natural Gas	24,000 BTU	14,000 BTU	55.69% / 57.81%	MQLOGC45, MQLOGF36BW, LOGC44
HBZDV4224LP / LPE	Тор	Natural Gas	22,000 BTU	15,000 BTU	57.03% / 59.09%	MQLOGC45, MQLOGF36BW, LOGC44
HBZDV4228N / NE	Тор	Propane	28,000 BTU	20,000 BTU	68.04% / 70.16%	MQLOGC45, MQLOGF36BW, LOGC44
HBZDV4228LP / LPE	Тор	Propane	26,000 BTU	19,000 BTU	65.29% / 67.66%	MQLOGC45, MQLOGF36BW, LOGC44

Input

Min.

29,000 BTU

29,000 BTU

22 200 DTU

FE

(P.4.1-15)

61.98% / 63.92%

61.98% / 63.92%

CT CON / CO OF0/

Log


Sets

LOGF36

LOGF36

100500

TOP FLUE	Hei	Height		Front Width		Depth	
MODEL	Actual	Framing	Actual	Framing	Actual	Framing	
LOUVERS							
HBZDV36	34 ¹³ ⁄16"	35"	36"	36 ¾"	16 7⁄16"	17"	
HBZDV42	37"	37 ¾"	41 1/8"	42 ³ /8"	16 7⁄16"	17"	
HBZDV47	43 1⁄16"	43 1⁄8"	47 1⁄16"	47 ³ /8"	19 7⁄16"	19 ½"	
CLEAN VIEW	CIRCULATI	NG KIT					
HBZDV36	34 ¹¹ ⁄16"	41"	38 1⁄16"	38 7⁄16"	18 1/8"	19 ½"	
HBZDV42	36 ¹³ ⁄16"	43"	42 ½16"	42 1/16"	18 ¹⁵ ⁄16"	19 ½"	
HBZDV47	49"	49 ½"	48 1/16"	48 ¾"	21 ¹⁵ /16"	22"	



TOP FLUE MODEL VIEWING AREA					
Width Height					
HBZDV36	29 ¾"	18 5⁄8"			
HBZDV42	33 ¾"	20 3⁄8"			
HBZDV47	39 ½"	26 ¾"			

SPECIFICATIONS

Flue

Тор

Top

Ton

Fuel

Natural Gas

Natural Gas

D......

Input Max.

30,500 BTU

30,500 BTU

20 000 0711

SOLACE

MQHBZDV3636N / NE

MQHBZDV4236N / NE

CORNER FRAMING DIMENSIONS (INCHES): LOUVERED UNITS

HBZDV36		HB	SZDV42	HB	HBZDV47		
Α	54 ¹³ /16"	Α	58 ¹³ /16"	Α	65 ¼"		
В	36 ¾"	В	42 3⁄8"	В	47 ¾"		
С	36"	С	41 1/8"	С	47 1⁄16"		
D	9 ³ ⁄16"	D	8 ¼"	D	8 ¹⁵ /16"		
Е	38 ¾"	Е	41 5⁄8"	E	46 1⁄8"		
F	12 3⁄8"	F	13 ³ ⁄4"	F	13 15/16		
G	17 %16"	G	19 ½"	G	19 11/16'		
н	27 ¾"	н	29 7⁄16"	н	32 5⁄8"		

CORNER FRAMING DIMENSIONS (INCHES): CLEAN VIEW CIRCULATING KIT (CVK)

HE	SZDV36	HE	SZDV42	HE	HBZDV47		
Α	59 %"	Α	63 ¹³ ⁄16"	Α	70 ³ ⁄16"		
В	38 7⁄16"	В	42 1/16"	В	48 ¾"		
С	38 1⁄6"	С	42 1⁄16"	С	48 1⁄16"		
D	10 ¹¹ /16"	D	10 ¹¹ /16"	D	10 1⁄8"		
Е	42 5⁄16"	Е	45 1⁄8"	E	49 ⁵ /8"		
F	12 3⁄8"	F	13 ¾"	F	13 ¹⁵ /16"		
G	17 %16"	G	19 ½"	G	19 ¹¹ /16"		
н	29 5/16"	н	31 1/8"	н	35 1⁄16"		

	Width	Height			
DV36	29 ¾"	18 5/8"			
DV42	33 ¾"	20 3/8"			
DV47	39 ½"	26 3⁄8"			

marquis	S





ACCESSORIES

LOG SETS

SOLACE



MEDIA OPTIONS*





MQLOGC45 Burnt Oak SOLACE II

SOLACE II

REMOTE

THERMOSTAT

SOLACE II



MQROCK2 Natural Rock Set

MQROCK2 Multi-Colored Rock Set PF1 IPI/MV

Z80PT Wall Mount

LINERS




RLH Herringbone Brick



RRH Red Herringbone Brick



RLT Traditional Brick



PL Porcelain Reflective



Unit Illustrated: Solace II HBZDV3624N Direct Vent Fireplace MQLOGC45 Log Set (Oak), HB36CVCK Circulating Kit (Designer Clean View), HB36RLH Liner (Herringbone Brick).

*Requires Support Platform (Solace II only)









FOR CALIFORNIA RESIDENTS ONLY: WARNING! This product can expose you to chemicals including Carbon Monoxide, that is an externally vented by-product of fuel consumption, which is [are] known to the State of California to cause birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov.

Unit Illustrated: Solace MOHBZDV4236N Direct Vent Fireplace, LOGF36 Log Set (Fiber Split Oak), HB42GBL Black Grills, HB42RLT Liner (Traditional Brick).



HOME

Marquis Fireplaces maintains a program of continuous testing, refinement and improvements of all its products. Some aspect of units shown here may be changed at any time without notice or obligation.

Certified to: ANSI Z21.88-2017 • CSA 2.33-2017 Vented Gas Fireplace Heaters, CSA 2.17-2017

Note: Components may have to be ordered separately to create a complete unit. Discuss with your local Marquis Dealer for clarification.

Canadä



Look for the **EnerGuide** Gas Fireplace Energy Efficiency Rating in this brochure

Based on CSA P.4.1-15

Crafted entirely in Canada, each Marquis fireplace is built to the highest standards and made to last.



2340 Logan Avenue Winnipeg, Manitoba, CAN R2R 2V3 Phone: 204.632.1962 Fax: 204.632.1960 marquisfireplaces.net

LIMITED LIFETIME WARRANTY

Printed in Canada **B057 – 04/2024**