

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : Nelfapox STL Premium Coat (Base)
Product code : F.0653.A
Product group : Recipe

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Main use category : Professional use, Industrial use
Use of the substance/mixture : Surface tolerant epoxy coating
Function or use category : Coatings and paints, thinners, paint removers

1.3. Details of the supplier of the safety data sheet

Manufacturer

Nelf Marine Paints B.V.
Nieuweweg 5
NL 9073 GN Marrum, Fryslân
Nederland
T +31 (0)518 - 418 000
info@nelfmarine.nl, www.nelfmarine.nl

1.4. Emergency telephone number

Country/Area	Organisation/Company	Address	Emergency number	Comment
Netherlands	Nationaal Vergiftigingen Informatie Centrum (NVIC)	Huispostnummer Q03.2.315 Postbus 85500 3508 GA Utrecht	+31 88 755 80 00	Only for the purpose of informing medical personnel in cases of acute intoxications (24 hours a day, 7 days a week)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 3 H226
Skin corrosion/irritation, Category 2 H315
Serious eye damage/eye irritation, Category 2 H319
Skin sensitisation, Category 1 H317
Hazardous to the aquatic environment – Chronic Hazard, Category 3 H412
Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Flammable liquid and vapour. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful to aquatic life with long lasting effects.

Nelfapox STL Premium Coat (Base)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS02

GHS07

CLP Signal word

: Warning

Contains

: reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700); Phenol, methylstyrenated

Hazard statements (CLP)

: H226 - Flammable liquid and vapour.
H315 - Causes skin irritation.
H317 - May cause an allergic skin reaction.
H319 - Causes serious eye irritation.
H412 - Harmful to aquatic life with long lasting effects.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 - Avoid breathing vapours.
P264 - Wash hands thoroughly after handling.
P280 - Wear eye protection, protective gloves.
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.

Precautionary statements (CLP)

2.3. Other hazards

PBT: not yet assessed

vPvB: not yet assessed

Contains vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

Component	
Substance(s) meeting the vPvB criteria of REACH regulation, in accordance with Annex XIII	Phenol, methylstyrenated (68512-30-1)
Substance(s) not meeting the PBT criteria of REACH regulation, in accordance with Annex XIII	Phenol, methylstyrenated (68512-30-1)

The mixture contains substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

Component	
Substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605	Phenol, methylstyrenated (68512-30-1)
Substance(s) not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605	reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (1675-54-3)

Nelfapox STL Premium Coat (Base)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Barium sulphate substance with national workplace exposure limit(s) (DE, GB, SK)	CAS-No.: 7727-43-7 EC-No.: 231-784-4	25 – 50	Not classified
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight $\leq$ 700)	CAS-No.: 1675-54-3 EC-No.: 216-823-5 EC Index-No.: 603-073-00-2 REACH-no: 01-2119456619-26	10 – 25	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411
Talc substance with national workplace exposure limit(s) (GB, NL, PL, RO)	CAS-No.: 14807-96-6 EC-No.: 238-877-9	10 – 25	Not classified
Phenol, methylstyrenated substance listed on REACH Candidate List vPvB substance; substance identified as having endocrine disrupting properties	CAS-No.: 68512-30-1 EC-No.: 270-966-8 REACH-no: 01-2119555274-38	5 – 10	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 3, H412
Reaction mass of ethylbenzene and xylene substance with national workplace exposure limit(s) (DE, FR, GB, NL, PL); substance with a Community workplace exposure limit	EC-No.: 905-588-0 REACH-no: 01-2119488216-32	5 – 10	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 (ATE=1100 mg/kg bodyweight) Acute Tox. 4 (Inhalation), H332 (ATE=11 mg/l/4h) Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 3, H412
CI Pigment White 6 substance with national workplace exposure limit(s) (DE, FR, GB, PL, RO, SK)	CAS-No.: 13463-67-7 EC-No.: 236-675-5 EC Index-No.: 022-006-00-2 REACH-no: 01-2119489379-17	5 – 10	Not classified
2-methylpropan-1-ol; iso-butanol substance with national workplace exposure limit(s) (CZ, DE, FR, GB, PL, RO, SK)	CAS-No.: 78-83-1 EC-No.: 201-148-0 EC Index-No.: 603-108-00-1 REACH-no: 01-2119484609-23	1 – 2.5	Flam. Liq. 3, H226 STOT SE 3, H335 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H336
Hydrocarbons, C9, aromatics substance with national workplace exposure limit(s) (NL)	CAS-No.: 128601-23-0 EC-No.: 918-668-5 REACH-no: 01-2119455851-35	1 – 2.5	Flam. Liq. 3, H226 STOT SE 3, H336 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 EUH066
Quartz, respirable fraction substance with national workplace exposure limit(s) (FR, GB, NL)	CAS-No.: 14808-60-7 EC-No.: 238-878-4	0.1 – 0.3	STOT RE 1, H372
Formaldehyde, polymer with 2-(chloromethyl)oxirane and phenol	CAS-No.: 9003-36-5 EC-No.: 500-006-8 REACH-no: 01-2119454392-40	0.1 – 0.3	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1A, H317 Aquatic Chronic 2, H411

Nelfapox STL Premium Coat (Base)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
1,6-bis (2,3-epoxypropoxy) hexane	CAS-No.: 933999-84-9 EC-No.: 618-939-5 REACH-no: 01-2119463471-41	0.1 – 0.3	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 3, H412

Specific concentration limits:		
Name	Product identifier	Specific concentration limits (%)
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)	CAS-No.: 1675-54-3 EC-No.: 216-823-5 EC Index-No.: 603-073-00-2 REACH-no: 01-2119456619-26	($5 \leq C \leq 100$) Skin Irrit. 2; H315 ($5 \leq C \leq 100$) Eye Irrit. 2; H319

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: If you feel unwell, seek medical advice.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.
Self protection of the first-aider	: First aid workers will be equipped with suitable personal protective equipment.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: None under normal conditions.
Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction. Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after eye contact	: Eye irritation.
Symptoms/effects after ingestion	: None under normal conditions.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Flammable liquid and vapour.
Explosion hazard	: No direct explosion hazard.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

5.3. Advice for firefighters

Firefighting instructions	: Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.
---------------------------	---

Nelfapox STL Premium Coat (Base)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.

For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray.

For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.

Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray.

Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed.

Packaging materials : Always store product in container of same material as original container.

7.3. Specific end use(s)

No additional information available

Nelfapox STL Premium Coat (Base)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

National occupational exposure and biological limit values

Nelfapox STL Premium Coat (Base)	
Netherlands - Occupational Exposure Limits	
TGG-8u (OEL TWA)	50 ppm
Hydrocarbons, C9, aromatics (128601-23-0)	
Netherlands - Occupational Exposure Limits	
TGG-8u (OEL TWA)	100 mg/m ³
	19 ppm
Reaction mass of ethylbenzene and xylene	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	221 mg/m ³
IOEL STEL	442 mg/m ³
Netherlands - Occupational Exposure Limits	
TGG-8u (OEL TWA)	210 mg/m ³
TGG-15min (OEL STEL)	442 mg/m ³
Talc (14807-96-6)	
Netherlands - Occupational Exposure Limits	
Local name	Talk
TGG-8u (OEL TWA)	0.25 mg/m ³ (respirabel)
Regulatory reference	Arbeidsomstandighedenregeling 2024
CI Pigment White 6 (13463-67-7)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Titanium dioxide
Remark	SCOEL Recommendations (Ongoing)
Quartz, respirable fraction (14808-60-7)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Silica crystalline (Quartz)
Remark	SCOEL Recommendations (2003)
Netherlands - Occupational Exposure Limits	
Local name	Silicium(di)oxide – kwarts
TGG-8u (OEL TWA)	0.075 mg/m ³ (Voor respirabel stof)

8.2. Exposure controls

Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Nelfapox STL Premium Coat (Base)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Personal protection equipment

Personal protective equipment:

Wear recommended personal protective equipment.

Personal protective equipment symbol(s):



Eye and face protection

Eye protection:

Safety glasses

Eye protection			
Type	Field of application	Characteristics	Standard
Safety glasses			

Skin protection

Skin and body protection:

Wear suitable protective clothing

Skin and body protection	
Type	Standard
Tyvek® Gown/Coveralls	

Hand protection:

Protective gloves

Hand protection					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Reusable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	> 0,1 mm	2 (< 1.5)	EN ISO 374

Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Respiratory protection			
Device	Filter type	Condition	Standard
Reusable half mask	Type P2	Dust protection	EN 143
Reusable half mask	Filter A2/B2	Vapour protection	EN 143

Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Blue. brown. Yellow. Grey. Green. Purple. red. white. Violet. Silver. Black.
Odour	: characteristic.
Odour threshold	: Not available
Melting point	: Not applicable

Nelfapox STL Premium Coat (Base)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Freezing point	: Not available
Boiling point	: ≥ 100 °C
Flammability	: Flammable liquid and vapour.
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: 24 (≥ 24) °C
Auto-ignition temperature	: > 200 °C
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: 604.23 – 725.076 mm ² /s
Viscosity, dynamic	: 1000 – 1200 mPa·s
Solubility	: Not miscible.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: 1.655 kg/l
Relative density	: Not available
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

Other safety characteristics

VOC content : 215 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable liquid and vapour.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified
Additional information	: Epoxy resin (M.V. 700). May produce an allergic reaction

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (1675-54-3)

LD50 oral rat	11400 mg/kg
---------------	-------------

Nelfapox STL Premium Coat (Base)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (1675-54-3)	
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal))
LD50 dermal rabbit	> 22800 mg/kg
Phenol, methylstyrenated (68512-30-1)	
LD50 oral rat	> 2000 mg/kg
LD50 dermal rat	> 2000 mg/kg
LC50 Inhalation - Rat	> 5 mg/l/4h
Hydrocarbons, C9, aromatics (128601-23-0)	
LD50 oral rat	3492 (2000 – 5000) mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 Inhalation - Rat	> 6193 mg/l
Reaction mass of ethylbenzene and xylene	
LD50 dermal rabbit	12126 mg/kg bodyweight Animal: rabbit, Animal sex: male
LC50 Inhalation - Rat	29000 mg/l
Talc (14807-96-6)	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method)
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	> 2.1 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Guideline: EU Method B.2 (Acute Toxicity (Inhalation)), Guideline: EPA OPPTS 870.1300 (Acute inhalation toxicity)
CI Pigment White 6 (13463-67-7)	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure), Guideline: EPA OPPTS 870.1100 (Acute Oral Toxicity)
Barium sulphate (7727-43-7)	
LD50 oral rat	> 5000 mg/kg
Formaldehyde, polymer with 2-(chloromethyl)oxirane and phenol (9003-36-5)	
LD50 oral rat	> 2000 mg/kg
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
Skin corrosion/irritation	: The product contains low molecular weight epoxy constituents which are irritating to eyes, mucous membrane and skin. Based on the properties of the epoxy constituent(s) and considering toxicological data on similar preparations, this product may be a skin sensitiser and an irritant.
Additional information	: Causes skin irritation.
Phenol, methylstyrenated (68512-30-1)	
pH	7
Talc (14807-96-6)	
pH	8 – 10

Nelfapox STL Premium Coat (Base)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

CI Pigment White 6 (13463-67-7)	
pH	7 (6 – 9)
Barium sulphate (7727-43-7)	
pH	9
Serious eye damage/irritation	: May cause irritation to the eyes
Phenol, methylstyrenated (68512-30-1)	
pH	7
Talc (14807-96-6)	
pH	8 – 10
CI Pigment White 6 (13463-67-7)	
pH	7 (6 – 9)
Barium sulphate (7727-43-7)	
pH	9
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (1675-54-3)	
NOAEL (chronic, oral, animal/male, 2 years)	15 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies), Guideline: EPA OPPTS 870.4300 (Combined Chronic Toxicity / Carcinogenicity), Guideline: other:
NOAEL (chronic, oral, animal/female, 2 years)	100 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies), Guideline: EPA OPPTS 870.4300 (Combined Chronic Toxicity / Carcinogenicity), Guideline: other:
Barium sulphate (7727-43-7)	
NOAEL (chronic, oral, animal/male, 2 years)	60 mg/kg bodyweight Animal: rat, Animal sex: male
NOAEL (chronic, oral, animal/female, 2 years)	75 mg/kg bodyweight Animal: rat, Animal sex: female
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
2-methylpropan-1-ol; iso-butanol (78-83-1)	
STOT-single exposure	May cause respiratory irritation. May cause drowsiness or dizziness.
Hydrocarbons, C9, aromatics (128601-23-0)	
STOT-single exposure	May cause drowsiness or dizziness. May cause respiratory irritation.
Reaction mass of ethylbenzene and xylene	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: Not classified
2-methylpropan-1-ol; iso-butanol (78-83-1)	
NOAEL (oral, rat, 90 days)	> 1450 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (1675-54-3)	
NOAEL (oral, rat, 90 days)	50 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents), Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: other:

Nelfapox STL Premium Coat (Base)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hydrocarbons, C9, aromatics (128601-23-0)	
NOAEL (oral, rat, 90 days)	600 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
Reaction mass of ethylbenzene and xylene	
LOAEL (oral, rat, 90 days)	150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Talc (14807-96-6)	
NOAEL (oral, rat, 90 days)	100 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 452 (Chronic Toxicity Studies)
Quartz, respirable fraction (14808-60-7)	
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.
Formaldehyde, polymer with 2-(chloromethyl)oxirane and phenol (9003-36-5)	
NOAEL (oral, rat, 90 days)	≈ 250 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
Aspiration hazard : Not classified	
Nelfapox STL Premium Coat (Base)	
Viscosity, kinematic	604.23 – 725.076 mm ² /s
2-methylpropan-1-ol; iso-butanol (78-83-1)	
Viscosity, kinematic	3.879 mm ² /s
reaction product: bisphenol-A(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (1675-54-3)	
Viscosity, kinematic	6896.552 mm ² /s
Phenol, methylstyrenated (68512-30-1)	
Viscosity, kinematic	294 mm ² /s calculated
Hydrocarbons, C9, aromatics (128601-23-0)	
Viscosity, kinematic	81.52 mm ² /s
Reaction mass of ethylbenzene and xylene	
Viscosity, kinematic	< 0.9 mm ² /s
Quartz, respirable fraction (14808-60-7)	
Viscosity, kinematic	practically insoluble
1,6-bis (2,3-epoxypropoxy) hexane (933999-84-9)	
Viscosity, kinematic	10.3 mm ² /s
11.2. Information on other hazards	
Endocrine disrupting properties	
Component	
Phenol, methylstyrenated (68512-30-1)	The substance is identified for having endocrine disrupting properties but there is no additional data available (see section 2.3)

Nelfapox STL Premium Coat (Base)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Harmful to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute) : Not classified
Hazardous to the aquatic environment, long-term (chronic) : Harmful to aquatic life with long lasting effects.

2-methylpropan-1-ol; iso-butanol (78-83-1)

LC50 - Fish [1]	1430 mg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	1100 mg/l Test organisms (species): Daphnia pulex
NOEC (chronic)	20 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

reaction product: bisphenol-A(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (1675-54-3)

LC50 - Fish [1]	1.5 mg/l
EC50 - Other aquatic organisms [1]	1.7 mg/l
EC50 72h - Algae [1]	9.4 mg/l
EC50 72h - Algae [2]	> 11 mg/l Test organisms (species): Scenedesmus capricornutum
LOEC (chronic)	1 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	0.3 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic algae	4.2 mg/l

Hydrocarbons, C9, aromatics (128601-23-0)

EC50 - Crustacea [1]	3.2 mg/l
EC50 72h - Algae [1]	0.42 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	0.29 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)

Reaction mass of ethylbenzene and xylene

LC50 - Fish [1]	2.6 mg/l
EC50 - Crustacea [1]	> 3.4 mg/l Test organisms (species): Ceriodaphnia dubia
EC50 72h - Algae [1]	2.2 mg/l
LOEC (chronic)	3.16 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	> 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d'

Talc (14807-96-6)

LC50 - Fish [1]	89581.02 mg/l Test organisms (species): other:
LC50 - Fish [2]	110000 mg/l Test organisms (species): other:
EC50 96h - Algae [1]	7202.7 mg/l Test organisms (species): other:
NOEC (chronic)	1459.798 mg/l Test organisms (species): other: Duration: '30 d'

CI Pigment White 6 (13463-67-7)

EC50 - Other aquatic organisms [1]	> 100 mg/l Test organisms (species):
EC50 72h - Algae [1]	> 100 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)

Nelfapox STL Premium Coat (Base)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

CI Pigment White 6 (13463-67-7)	
LOEC (chronic)	5 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
Barium sulphate (7727-43-7)	
EC50 - Crustacea [1]	> 58.8 mg/l Test organisms (species): Daphnia magna
Formaldehyde, polymer with 2-(chloromethyl)oxirane and phenol (9003-36-5)	
LC50 - Fish [1]	> 1000 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
LC50 - Fish [2]	5.7 mg/l Test organisms (species): Leuciscus idus
EC50 - Crustacea [1]	3.5 mg/l Test organisms (species): Daphnia magna
LOEC (chronic)	1 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	0.3 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
1,6-bis (2,3-epoxypropoxy) hexane (933999-84-9)	
LC50 - Fish [1]	≈ 30 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	39 – 57 mg/l Test organisms (species): Daphnia magna
12.2. Persistence and degradability	
Nelfapox STL Premium Coat (Base)	
Persistence and degradability	Not established.
2-methylpropan-1-ol; iso-butanol (78-83-1)	
Persistence and degradability	Rapidly degradable
reaction product: bisphenol-A(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (1675-54-3)	
Persistence and degradability	Rapidly degradable
Phenol, methylstyrenated (68512-30-1)	
Persistence and degradability	Rapidly degradable
Hydrocarbons, C9, aromatics (128601-23-0)	
Persistence and degradability	Rapidly degradable
Reaction mass of ethylbenzene and xylene	
Persistence and degradability	Rapidly degradable
Talc (14807-96-6)	
Persistence and degradability	Rapidly degradable
CI Pigment White 6 (13463-67-7)	
Persistence and degradability	Rapidly degradable
Barium sulphate (7727-43-7)	
Persistence and degradability	Rapidly degradable
Quartz, respirable fraction (14808-60-7)	
Persistence and degradability	Rapidly degradable
Micronized amide wax	
Persistence and degradability	Rapidly degradable

Nelfapox STL Premium Coat (Base)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Formaldehyde, polymer with 2-(chloromethyl)oxirane and phenol (9003-36-5)

Persistence and degradability	Rapidly degradable
-------------------------------	--------------------

1,6-bis (2,3-epoxypropoxy) hexane (933999-84-9)

Persistence and degradability	Rapidly degradable
-------------------------------	--------------------

12.3. Bioaccumulative potential

2-methylpropan-1-ol; iso-butanol (78-83-1)

Partition coefficient n-octanol/water (Log Pow)	0.76
---	------

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (1675-54-3)

Partition coefficient n-octanol/water (Log Pow)	3.242
---	-------

Hydrocarbons, C9, aromatics (128601-23-0)

Partition coefficient n-octanol/water (Log Pow)	< 4
---	-----

Reaction mass of ethylbenzene and xylene

Partition coefficient n-octanol/water (Log Pow)	3.1
---	-----

Micronized amide wax

Partition coefficient n-octanol/water (Log Pow)	> 6
---	-----

1,6-bis (2,3-epoxypropoxy) hexane (933999-84-9)

Partition coefficient n-octanol/water (Log Pow)	0.822
---	-------

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

Nelfapox STL Premium Coat (Base)

PBT: not yet assessed

vPvB: not yet assessed

Component

Substance(s) meeting the vPvB criteria of REACH regulation, in accordance with Annex XIII	Phenol, methylstyrenated (68512-30-1)
---	---------------------------------------

Substance(s) not meeting the PBT criteria of REACH regulation, in accordance with Annex XIII	Phenol, methylstyrenated (68512-30-1)
--	---------------------------------------

12.6. Endocrine disrupting properties

Component

Phenol, methylstyrenated (68512-30-1)	The substance is identified for having endocrine disrupting properties but there is no additional data available (see section 2.3)
---------------------------------------	--

12.7. Other adverse effects

No additional information available

Nelfapox STL Premium Coat (Base)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional waste regulation	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Disposal must be done according to official regulations.
Additional information	: Flammable vapours may accumulate in the container. Do not re-use empty containers.
European List of Waste (LoW, EC 2000/532)	: 08 01 11* - waste paint and varnish containing organic solvents or other dangerous substances 08 01 12 - waste paint and varnish other than those mentioned in 08 01 11

SECTION 14: Transport information

In accordance with ADR / RID

ADR	RID
14.1. UN number or ID number	
UN 1263	UN 1263
14.2. UN proper shipping name	
PAINT	PAINT
Transport document description	
UN 1263 PAINT, 3, III, (D/E)	UN 1263 PAINT, 3, III
14.3. Transport hazard class(es)	
3	3
	
14.4. Packing group	
III	III
14.5. Environmental hazards	
Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available	

14.6. Special precautions for user

Special transport precautions	: In package sizes smaller than 450 L, under the conditions of 2.2.3.1.5.1, this product is ADR exempt.
-------------------------------	---

Overland transport

Classification code (ADR)	: F1
Special provisions (ADR)	: 163, 367, 650
Limited quantities (ADR)	: 5I
Excepted quantities (ADR)	: E1
Packing instructions (ADR)	: P001, IBC03, LP01, R001
Special packing provisions (ADR)	: PP1
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T2
Portable tank and bulk container special provisions (ADR)	: TP1, TP29
Tank code (ADR)	: LGBF
Vehicle for tank carriage	: FL

Nelfapox STL Premium Coat (Base)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Transport category (ADR) : 3
Special provisions for carriage - Packages (ADR) : V12
Special provisions for carriage - Operation (ADR) : S2
Hazard identification number (Kemler No.) : 30
Orange plates :



Tunnel restriction code (ADR) : D/E

Rail transport

Classification code (RID) : F1
Special provisions (RID) : 163, 367, 650
Limited quantities (RID) : 5L
Excepted quantities (RID) : E1
Packing instructions (RID) : P001, IBC03, LP01, R001
Special packing provisions (RID) : PP1
Mixed packing provisions (RID) : MP19
Portable tank and bulk container instructions (RID) : T2
Portable tank and bulk container special provisions (RID) : TP1, TP29
Tank codes for RID tanks (RID) : LGBF
Transport category (RID) : 3
Special provisions for carriage – Packages (RID) : W12
Colis express (express parcels) (RID) : CE4
Hazard identification number (RID) : 30

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)	
Reference code	Applicable on
3(b)	Nelfapox STL Premium Coat (Base) ; reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) ; Phenol, methylstyrenated ; Hydrocarbons, C9, aromatics ; Reaction mass of ethylbenzene and xylene ; Formaldehyde, polymer with 2-(chloromethyl)oxirane and phenol ; 1,6-bis (2,3-epoxypropoxy) hexane
3(c)	Nelfapox STL Premium Coat (Base) ; reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) ; Phenol, methylstyrenated ; Hydrocarbons, C9, aromatics ; Formaldehyde, polymer with 2-(chloromethyl)oxirane and phenol ; 1,6-bis (2,3-epoxypropoxy) hexane
3(a)	Nelfapox STL Premium Coat (Base) ; Hydrocarbons, C9, aromatics ; Reaction mass of ethylbenzene and xylene

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains substance(s) listed on the REACH Candidate List in concentrations ≥ 0.1 % or SCL: Phenol, methylstyrenated (EC 270-966-8, CAS 68512-30-1)

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Nelfapox STL Premium Coat (Base)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Ozone Regulation (2024/590)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 2024/590 on substances that deplete the ozone layer)

Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

VOC Directive (2004/42)

VOC content : 215 g/l
Decopaint Directive (2004/42/EC) - Annex II : A/j (Paints and Varnishes - Two-pack reactive performance coatings for specific end use such as floors)
Maximum allowed concentration : 500 g/l VOC
Maximum content of VOC : 215.00 g/l VOC

Explosives Precursors Regulation (EU 2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (EC 273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

National regulations

Netherlands

ABM category : Z(2) - biodegradable substances with hazardous properties for humans and the environment (carcinogenicity/ mutagenicity/reprotoxicity/bioacumulative potential or toxicity)
SZW-lijst van kankerverwekkende stoffen : Phenol, methylstyrenated, Quartz, respirable fraction are listed
SZW-lijst van mutagene stoffen : Phenol, methylstyrenated is listed
SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed
SZW-lijst van reprotoxische stoffen – Vruchtbaarheid : None of the components are listed
SZW-lijst van reprotoxische stoffen – Ontwikkeling : None of the components are listed

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes:

The information supplied has been based upon the current level of information available, for the purpose of specifying the requirements regarding environment, health and safety in conjunction with the product. They are not to be interpreted as a warranty. This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

Indication of changes		
Section	Changed item	Comments
	Revision date	Modified
2.1	Contains	Removed
2.2	EUH-statements	Removed
3	Composition/information on ingredients	Modified

Abbreviations and acronyms:

	CLP
DPD	Dangerous Preparations Directive 1999/45/EC
DSD	Dangerous Substances Directive 67/548/EEC
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006

Nelfapox STL Premium Coat (Base)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:	
ACGIH	American Conference of Governmental Industrial Hygienists
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
CAS-No.	Chemical Abstracts Service number
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
COD	Chemical oxygen demand (COD)
CSA	Chemical safety assessment
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
ED	Endocrine disruptor
EN	European Standard
EWC	European waste catalogue
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
Log Kow	Partition coefficient n-octanol/water (Log Kow)
Log Pow	Partition coefficient n-octanol/water (Log Pow)
MAK	maximum workplace concentration
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
N.O.S.	Not Otherwise Specified
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
OSHA	Occupational Safety Health Administration
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
PPE	Personal protection equipment
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet

Nelfapox STL Premium Coat (Base)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:

STP	Sewage treatment plant
TF	Technical function
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
TWA	Time Weighted Average
VOC	Volatile Organic Compounds
vPvB	Very Persistent and Very Bioaccumulative
UFI	Unique Formula Identifier

Data sources	: REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.
Training advice	: Normal use of this product shall imply use in accordance with the instructions on the packaging.
Other information	: None.

Full text of H- and EUH-statements:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1A	Skin sensitisation, category 1A
STOT RE 1	Specific target organ toxicity – Repeated exposure, Category 1
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.

Nelfapox STL Premium Coat (Base)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:

H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Flam. Liq. 3	H226	On basis of test data
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
Skin Sens. 1	H317	Calculation method
Aquatic Chronic 3	H412	Calculation method

Safety Data Sheet applicable for regions : NL - Netherlands

The classification complies with : ATP 8

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.