

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : Nelfapox Universal Primer 2800 (Base)
Product code : F.0667.A
Product group : Recipe

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Main use category : Professional use, Industrial use
Use of the substance/mixture : Corrosion resistant 2-component primer based on epoxy resin
Function or use category : Coatings and paints, thinners, paint removers

1.3. Details of the supplier of the safety data sheet

Manufacturer

Nelf Marine Paints B.V.
Nieuweweg 5
NL 9073 GN Marrum, Fryslân
Nederland
T +31 (0)518 - 418 000
info@nelfmarine.nl, www.nelfmarine.nl

1.4. Emergency telephone number

Country/Area	Organisation/Company	Address	Emergency number	Comment
Netherlands	Nationaal Vergiftigingen Informatie Centrum (NVIC)	Huispostnummer Q03.2.315 Postbus 85500 3508 GA Utrecht	+31 88 755 80 00	Only for the purpose of informing medical personnel in cases of acute intoxications (24 hours a day, 7 days a week)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 3 H226
Skin corrosion/irritation, Category 2 H315
Serious eye damage/eye irritation, Category 2 H319
Skin sensitisation, Category 1 H317
Specific target organ toxicity – Single exposure, Category 3, H335
Respiratory tract irritation
Specific target organ toxicity – Repeated exposure, Category 2 H373
Hazardous to the aquatic environment – Chronic Hazard, Category 3 H412
Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Flammable liquid and vapour. May cause damage to organs through prolonged or repeated exposure. May cause respiratory irritation. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful to aquatic life with long lasting effects.

Nelfapox Universal Primer 2800 (Base)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



CLP Signal word

Contains

Hazard statements (CLP)

Precautionary statements (CLP)

- : Warning
- : reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700); Phenol, methylstyrenated; Reaction mass of ethylbenzene and xylene
- : H226 - Flammable liquid and vapour.
H315 - Causes skin irritation.
H317 - May cause an allergic skin reaction.
H319 - Causes serious eye irritation.
H335 - May cause respiratory irritation.
H373 - May cause damage to organs through prolonged or repeated exposure.
H412 - Harmful to aquatic life with long lasting effects.
- : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
No smoking.
P261 - Avoid breathing spray, vapours.
P264 - Wash hands thoroughly after handling.
P280 - Wear eye protection, protective gloves.
P312 - Call doctor if you feel unwell.
P314 - Get medical advice/attention if you feel unwell.

2.3. Other hazards

Contains vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

Component	
Substance(s) meeting the vPvB criteria of REACH regulation, in accordance with Annex XIII	Phenol, methylstyrenated (68512-30-1)
Substance(s) not meeting the PBT criteria of REACH regulation, in accordance with Annex XIII	Phenol, methylstyrenated (68512-30-1)
PBT: not relevant – no registration required	butan-1-ol; n-butanol (71-36-3)(¹)
vPvB: not relevant – no registration required	butan-1-ol; n-butanol (71-36-3)(¹)

(¹) Substance(s) in concentration below 0.1 % and displayed on a voluntary basis

The mixture contains substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

Component	
Substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605	Phenol, methylstyrenated (68512-30-1)

Nelfapox Universal Primer 2800 (Base)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Talc substance with national workplace exposure limit(s) (GB, NL, PL, RO)	CAS-No.: 14807-96-6 EC-No.: 238-877-9	10 – 25	Not classified
Reaction mass of ethylbenzene and xylene substance with national workplace exposure limit(s) (DE, FR, GB, NL, PL); substance with a Community workplace exposure limit	EC-No.: 905-588-0 REACH-no: 01-2119488216-32	10 – 25	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 (ATE=1100 mg/kg bodyweight) Acute Tox. 4 (Inhalation), H332 (ATE=11 mg/l/4h) Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 3, H412
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)	CAS-No.: 25068-38-6 EC-No.: 500-033-5 EC Index-No.: 603-074-00-8 REACH-no: 01-2119456619-26	10 – 25	Eye Irrit. 2, H319 Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411
CI Pigment White 6 substance with national workplace exposure limit(s) (DE, FR, GB, PL, RO, SK)	CAS-No.: 13463-67-7 EC-No.: 236-675-5 EC Index-No.: 022-006-00-2 REACH-no: 01-2119489379-17	10 – 25	Not classified
Reaction mass of ethylbenzene and m-xylene and p-xylene substance with national workplace exposure limit(s) (DE, FR, GB, NL, PL); substance with a Community workplace exposure limit	EC-No.: 905-562-9 REACH-no: 01-2119555267-33	3 – 5	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 (ATE=1100 mg/kg bodyweight) Acute Tox. 4 (Inhalation), H332 (ATE=1.5 mg/l/4h) Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304
substance with national workplace exposure limit(s) (CZ, DE, FR, GB, PL, SI, SK)	CAS-No.: 7429-90-5 EC-No.: 231-072-3 EC Index-No.: 013-002-00-1 REACH-no: 01-2119529243-45	3 – 5	Water-react. 2, H261 Flam. Sol. 1, H228
Phenol, methylstyrenated substance listed on REACH Candidate List vPvB substance; substance identified as having endocrine disrupting properties	CAS-No.: 68512-30-1 EC-No.: 270-966-8 REACH-no: 01-2119555274-38	3 – 5	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 3, H412
2-methoxy-1-methylethyl acetate substance with national workplace exposure limit(s) (AT, BE, BG, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, LT, LU, LV, MT, NL, PL, RO, SE, SI, SK, IS, NO, RS, CH); substance with a Community workplace exposure limit	CAS-No.: 108-65-6 EC-No.: 203-603-9 EC Index-No.: 607-195-00-7 REACH-no: 01-2119475791-29	2.5 – 3	Flam. Liq. 3, H226 STOT SE 3, H336

Nelfapox Universal Primer 2800 (Base)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics substance with national workplace exposure limit(s) (PL); substance with a Community workplace exposure limit	CAS-No.: 64742-48-9 EC-No.: 919-857-5 EC Index-No.: 649-327-00-6 REACH-no: 01-2119463258-33	1 – 2.5	Flam. Liq. 3, H226 STOT SE 3, H336 Asp. Tox. 1, H304 EUH066
1-methoxy-2-propanol; monopropylene glycol methyl ether substance with national workplace exposure limit(s) (BE, CZ, DE, FR, GB, NL, PL, RO, SK, RS); substance with a Community workplace exposure limit	CAS-No.: 107-98-2 EC-No.: 203-539-1 EC Index-No.: 603-064-00-3 REACH-no: 01-2119457435-35	1 – 2.5	Flam. Liq. 3, H226 STOT SE 3, H336
Fatty acids, tall-oil, esters with polyethylene glycol mono(hydrogen maleate), compounds with amides from diethylenetriamine and tall-oil fatty acids	CAS-No.: 222716-38-3	0.1 – 0.3	Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) Skin Irrit. 2, H315 Skin Sens. 1, H317 STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
n-butyl acetate substance with national workplace exposure limit(s) (CZ, DE, FR, GB, NL, PL, RO, SK, RS); substance with a Community workplace exposure limit	CAS-No.: 123-86-4 EC-No.: 204-658-1 EC Index-No.: 607-025-00-1 REACH-no: 01-2119485493-29	0.1 – 0.3	Flam. Liq. 3, H226 STOT SE 3, H336 EUH066
Trimethylol propane	CAS-No.: 77-99-6 EC-No.: 201-074-9 REACH-no: 01-2119486799-10	0.1 – 0.3	Repr. 2, H361fd
Quartz, inhalable fraction substance with national workplace exposure limit(s) (GB, NL); substance with a Community workplace exposure limit	CAS-No.: 14808-60-7 EC-No.: 238-878-4	0.036 – 0.05	Not classified
butan-1-ol; n-butanol substance with national workplace exposure limit(s) (BE, CZ, DE, FR, GB, NL, RO, SK)	CAS-No.: 71-36-3 EC-No.: 200-751-6 EC Index-No.: 603-004-00-6 REACH-no: 01-2119484630-38	0.01 – 0.036	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 (ATE=780 mg/kg bodyweight) STOT SE 3, H335 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H336
2-methoxypropanol substance with national workplace exposure limit(s) (DE)	CAS-No.: 1589-47-5 EC-No.: 216-455-5 EC Index-No.: 603-106-00-0	0.0015 – 0.01	Flam. Liq. 3, H226 Repr. 1B, H360D STOT SE 3, H335 Skin Irrit. 2, H315 Eye Dam. 1, H318
2-methoxypropyl acetate substance with national workplace exposure limit(s) (CZ, DE, PL, SK)	CAS-No.: 70657-70-4 EC-No.: 274-724-2 EC Index-No.: 607-251-00-0	0.0015 – 0.01	Flam. Liq. 3, H226 Repr. 1B, H360D STOT SE 3, H335
toluene substance with national workplace exposure limit(s) (CZ, DE, FR, GB, NL, PL, RO, SI, SK, RS); substance with a Community workplace exposure limit	CAS-No.: 108-88-3 EC-No.: 203-625-9 EC Index-No.: 601-021-00-3 REACH-no: 01-2119471310-51	0.0015 – 0.01	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Repr. 2, H361d STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 3, H412

Nelfapox Universal Primer 2800 (Base)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
2,2'-iminodiethylamine; diethylenetriamine substance with national workplace exposure limit(s) (CZ, FR, GB, RO)	CAS-No.: 111-40-0 EC-No.: 203-865-4 EC Index-No.: 612-058-00-X REACH-no: 01-2119473793-27	0.001 – 0.0015	Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) Acute Tox. 4 (Dermal), H312 (ATE=1100 mg/kg bodyweight) Acute Tox. 2 (Inhalation), H330 (ATE=0.5 mg/l/4h) Skin Corr. 1B, H314 Skin Sens. 1, H317 STOT SE 3, H335

Specific concentration limits:

Name	Product identifier	Specific concentration limits (%)
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)	CAS-No.: 25068-38-6 EC-No.: 500-033-5 EC Index-No.: 603-074-00-8 REACH-no: 01-2119456619-26	(5 ≤ C ≤ 100) Skin Irrit. 2; H315 (5 ≤ C ≤ 100) Eye Irrit. 2; H319

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.
First-aid measures after skin contact	: Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.
Self protection of the first-aiders	: First aid workers will be equipped with suitable personal protective equipment.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: May cause respiratory irritation.
Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction. Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after eye contact	: Eye irritation.
Symptoms/effects after ingestion	: None under normal conditions.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Flammable liquid and vapour.
Explosion hazard	: No direct explosion hazard.

Nelfapox Universal Primer 2800 (Base)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Firefighting instructions : Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.

For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Do not breathe dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes.

Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

Packaging materials : Always store product in container of same material as original container.

Nelfapox Universal Primer 2800 (Base)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

National occupational exposure and biological limit values

Reaction mass of ethylbenzene and m-xylene and p-xylene	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	221 mg/m ³
IOEL STEL	442 mg/m ³
Netherlands - Occupational Exposure Limits	
TGG-8u (OEL TWA)	210 mg/m ³
TGG-15min (OEL STEL)	442 mg/m ³
Reaction mass of ethylbenzene and xylene	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	221 mg/m ³
IOEL STEL	442 mg/m ³
Netherlands - Occupational Exposure Limits	
TGG-8u (OEL TWA)	210 mg/m ³
TGG-15min (OEL STEL)	442 mg/m ³
1-methoxy-2-propanol; monopropylene glycol methyl ether (107-98-2)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	1-Methoxypropanol-2
IOEL TWA	375 mg/m ³
	100 ppm
IOEL STEL	568 mg/m ³
	150 ppm
Remark	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
Netherlands - Occupational Exposure Limits	
Local name	1-Methoxy-2-propanol
TGG-8u (OEL TWA)	375 mg/m ³
	100 ppm
TGG-15min (OEL STEL)	563 mg/m ³
	150 ppm
Remark	H (Huidopname) Stoffen die relatief gemakkelijk door de huid kunnen worden opgenomen, hetgeen een substantiële bijdrage kan betekenen aan de totale inwendige blootstelling, hebben in de lijst een Haanduiding. Bij deze stoffen moeten naast maatregelen tegen inademing ook adequate maatregelen ter voorkoming van huidcontact worden genomen.
Regulatory reference	Arbidsomstandighedenregeling 2024

Nelfapox Universal Primer 2800 (Base)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2-methoxy-1-methylethyl acetate (108-65-6)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	2-Methoxy-1-methylethylacetate
IOEL TWA	275 mg/m ³
	50 ppm
IOEL STEL	550 mg/m ³
	100 ppm
Remark	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
Netherlands - Occupational Exposure Limits	
Local name	1-Methoxy-2-propylacetaat
TGG-8u (OEL TWA)	550 mg/m ³
	100 ppm
Regulatory reference	Arbeidsomstandighedenregeling 2024
Talc (14807-96-6)	
Netherlands - Occupational Exposure Limits	
Local name	Talk
TGG-8u (OEL TWA)	0.25 mg/m ³ (respirabel)
Regulatory reference	Arbeidsomstandighedenregeling 2024
Quartz, inhalable fraction (14808-60-7)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Silica crystalline (Quartz)
IOEL TWA	0.05 mg/m ³ (respirable dust)
Remark	SCOEL Recommendations (2003)
Regulatory reference	SCOEL Recommendations
Netherlands - Occupational Exposure Limits	
Local name	Silicium(di)oxide – kwarts
TGG-8u (OEL TWA)	0.075 mg/m ³ (Voor respirabel stof)
Remark	Kankerverwekkende stof
Regulatory reference	Arbeidsomstandighedenregeling 2024
CI Pigment White 6 (13463-67-7)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Titanium dioxide
Remark	SCOEL Recommendations (Ongoing)
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-48-9)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	White spirit Type 3
IOEL TWA	116 mg/m ³
	20 ppm

Nelfapox Universal Primer 2800 (Base)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-48-9)	
IOEL STEL	290 mg/m ³
	50 ppm
Remark	skin. SCOEL Recommendations (2007)
Regulatory reference	SCOEL Recommendations
butan-1-ol; n-butanol (71-36-3)	
Netherlands - Occupational Exposure Limits	
Local name	n-butanol
TGG-8u (OEL TWA)	62 mg/m ³
	20 ppm
toluene (108-88-3)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Toluene
IOEL TWA	192 mg/m ³
	50 ppm
IOEL STEL	384 mg/m ³
	100 ppm
Remark	Skin
Regulatory reference	COMMISSION DIRECTIVE 2006/15/EC
Netherlands - Occupational Exposure Limits	
Local name	Tolueen
TGG-8u (OEL TWA)	150 mg/m ³
	39 ppm
TGG-15min (OEL STEL)	384 mg/m ³
	100 ppm
Regulatory reference	Arbeidsomstandighedenregeling 2024
n-butyl acetate (123-86-4)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	n-butyl acetate
IOEL TWA	241 mg/m ³
	50 ppm
IOEL STEL	723 mg/m ³
	150 ppm
Remark	SCOEL Recommendations (Ongoing)
Regulatory reference	COMMISSION DIRECTIVE (EU) 2019/1831
Netherlands - Occupational Exposure Limits	
Local name	n-Butylacetaat
TGG-8u (OEL TWA)	241 mg/m ³
	50 ppm

Nelfapox Universal Primer 2800 (Base)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

n-butyl acetate (123-86-4)

TGG-15min (OEL STEL)

723 mg/m³

150 ppm

Regulatory reference

Arbeidsomstandighedenregeling 2026

8.2. Exposure controls

Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Personal protection equipment

Personal protective equipment:

Wear recommended personal protective equipment.

Personal protective equipment symbol(s):



Eye and face protection

Eye protection:

Safety glasses

Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves

Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: brown. Yellow. Green. Grey. red.
Odour	: Aromatic.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: ≥ 100 °C
Flammability	: Flammable liquid and vapour.
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: 23 (≥ 23) °C
Auto-ignition temperature	: > 200 °C
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: 851.596 (821.596 – 997.653) mm ² /s
Viscosity, dynamic	: 1100 (1100 – 1300) mPa·s
Solubility	: Immiscible.

Nelfapox Universal Primer 2800 (Base)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: 1.41 kg/l
Relative density	: Not available
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

Other safety characteristics

VOC content : 370 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable liquid and vapour.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (25068-38-6)	
LD50 oral rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method)
Reaction mass of ethylbenzene and m-xylene and p-xylene	
LD50 dermal rabbit	12126 mg/kg bodyweight Animal: rabbit, Animal sex: male
Phenol, methylstyrenated (68512-30-1)	
LD50 oral rat	> 2000 mg/kg
LD50 dermal rat	> 2000 mg/kg
LC50 Inhalation - Rat	> 5 mg/l/4h
Reaction mass of ethylbenzene and xylene	
LD50 dermal rabbit	12126 mg/kg bodyweight Animal: rabbit, Animal sex: male

Nelfapox Universal Primer 2800 (Base)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Reaction mass of ethylbenzene and xylene	
LC50 Inhalation - Rat	29000 mg/l
1-methoxy-2-propanol; monopropylene glycol methyl ether (107-98-2)	
LD50 oral rat	4016 (2000 – 5000) mg/kg
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: EU Method B.3 (Acute Toxicity (Dermal))
LD50 dermal rabbit	> 2000 mg/kg
LC50 Inhalation - Rat (Vapours)	> 25.8 mg/l/4h
2-methoxy-1-methylethyl acetate (108-65-6)	
LD50 oral	8532 mg/kg
LD50 dermal rat	> 5000 mg/kg
LC50 Inhalation - Rat	35.7 mg/l
Talc (14807-96-6)	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method)
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	> 2.1 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Guideline: EU Method B.2 (Acute Toxicity (Inhalation)), Guideline: EPA OPPTS 870.1300 (Acute inhalation toxicity)
CI Pigment White 6 (13463-67-7)	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure), Guideline: EPA OPPTS 870.1100 (Acute Oral Toxicity)
Trimethylol propane (77-99-6)	
LD50 oral rat	≈ 14700 mg/kg bodyweight Animal: rat, Animal sex: male
LD50 dermal rabbit	> 10000 mg/kg bodyweight Animal: rabbit
LC50 Inhalation - Rat	> 0.85 mg/l air Animal: rat, Animal sex: male
(7429-90-5)	
LD50 oral rat	> 15900 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LC50 Inhalation - Rat	> 0.888 mg/l air Animal: rat, Animal sex: male, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-48-9)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 5000 mg/kg
LC50 Inhalation - Rat	> 4951 mg/l/4h Maximum attainable vapor concentration
2,2'-iminodiethylamine; diethylenetriamine (111-40-0)	
LD50 oral	1553 mg/kg
LD50 dermal	1045 mg/kg
LC50 Inhalation - Rat	0.07 mg/l

Nelfapox Universal Primer 2800 (Base)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

butan-1-ol; n-butanol (71-36-3)	
LD50 oral rat	780 mg/kg
LD50 dermal rabbit	3400 mg/kg
LC50 Inhalation - Rat	24.3 mg/l/4h
toluene (108-88-3)	
LD50 oral rat	5580 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: EU Method B.1 (Acute Toxicity (Oral)), 95% CL: 5300 - 5910
LD50 dermal rabbit	> 5000 mg/kg bodyweight Animal: rabbit, Animal sex: male, 95% CL: 9,63 - 20,77
n-butyl acetate (123-86-4)	
LD50 oral rat	> 10000 mg/kg
LD50 dermal rabbit	> 14000 mg/kg
LC50 Inhalation - Rat (Vapours)	> 21 mg/l/4h
Skin corrosion/irritation : Causes skin irritation.	
Phenol, methylstyrenated (68512-30-1)	
pH	7
1-methoxy-2-propanol; monopropylene glycol methyl ether (107-98-2)	
pH	4 – 7
2-methoxy-1-methylethyl acetate (108-65-6)	
pH	4
Talc (14807-96-6)	
pH	8 – 10
CI Pigment White 6 (13463-67-7)	
pH	7 (6 – 9)
2,2'-iminodiethylamine; diethylenetriamine (111-40-0)	
pH	> 12
butan-1-ol; n-butanol (71-36-3)	
pH	7
n-butyl acetate (123-86-4)	
pH	6.2
Serious eye damage/irritation : Causes serious eye irritation.	
Phenol, methylstyrenated (68512-30-1)	
pH	7
1-methoxy-2-propanol; monopropylene glycol methyl ether (107-98-2)	
pH	4 – 7
2-methoxy-1-methylethyl acetate (108-65-6)	
pH	4
Talc (14807-96-6)	
pH	8 – 10

Nelfapox Universal Primer 2800 (Base)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

CI Pigment White 6 (13463-67-7)	
pH	7 (6 – 9)
2,2'-iminodiethylamine; diethylenetriamine (111-40-0)	
pH	> 12
butan-1-ol; n-butanol (71-36-3)	
pH	7
n-butyl acetate (123-86-4)	
pH	6.2
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
(7429-90-5)	
NOAEL (animal/male, F0/P)	1000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
STOT-single exposure	: May cause respiratory irritation.
Reaction mass of ethylbenzene and m-xylene and p-xylene	
STOT-single exposure	May cause respiratory irritation.
Reaction mass of ethylbenzene and xylene	
STOT-single exposure	May cause respiratory irritation.
2-methoxypropanol (1589-47-5)	
STOT-single exposure	May cause respiratory irritation.
1-methoxy-2-propanol; monopropylene glycol methyl ether (107-98-2)	
STOT-single exposure	May cause drowsiness or dizziness.
2-methoxy-1-methylethyl acetate (108-65-6)	
STOT-single exposure	May cause drowsiness or dizziness.
2-methoxypropyl acetate (70657-70-4)	
STOT-single exposure	May cause respiratory irritation.
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-48-9)	
STOT-single exposure	May cause drowsiness or dizziness.
2,2'-iminodiethylamine; diethylenetriamine (111-40-0)	
STOT-single exposure	May cause respiratory irritation.
butan-1-ol; n-butanol (71-36-3)	
STOT-single exposure	May cause respiratory irritation. May cause drowsiness or dizziness.
toluene (108-88-3)	
STOT-single exposure	May cause drowsiness or dizziness.
n-butyl acetate (123-86-4)	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: May cause damage to organs through prolonged or repeated exposure.

Nelfapox Universal Primer 2800 (Base)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Reaction mass of ethylbenzene and m-xylene and p-xylene	
LOAEL (oral, rat, 90 days)	150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Reaction mass of ethylbenzene and xylene	
LOAEL (oral, rat, 90 days)	150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
1-methoxy-2-propanol; monopropylene glycol methyl ether (107-98-2)	
LOAEL (oral, rat, 90 days)	2757 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)
NOAEL (oral, rat, 90 days)	919 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)
NOAEL (dermal, rat/rabbit, 90 days)	> 1000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)
2-methoxy-1-methylethyl acetate (108-65-6)	
NOAEL (dermal, rat/rabbit, 90 days)	> 1000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)
Talc (14807-96-6)	
NOAEL (oral, rat, 90 days)	100 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 452 (Chronic Toxicity Studies)
Trimethylol propane (77-99-6)	
NOAEL (oral, rat, 90 days)	200 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
NOAEC (inhalation, rat, gas, 90 days)	≈ 3.5 ppm Animal: rat
(7429-90-5)	
LOAEC (inhalation, rat, dust/mist/fume, 90 days)	0.05 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
NOAEL (subchronic, oral, animal/male, 90 days)	1034 mg/kg bodyweight Animal: dog, Animal sex: male, Guideline: OECD Guideline 409 (Repeated Dose 90-Day Oral Toxicity Study in Non-Rodents)
NOAEL (subchronic, oral, animal/female, 90 days)	1087 mg/kg bodyweight Animal: dog, Animal sex: female, Guideline: OECD Guideline 409 (Repeated Dose 90-Day Oral Toxicity Study in Non-Rodents)
2,2'-iminodiethylamine; diethylenetriamine (111-40-0)	
LOAEL (oral, rat, 90 days)	530 – 620 mg/kg bodyweight Animal: rat, Guideline: other:
NOAEL (oral, rat, 90 days)	70 – 80 mg/kg bodyweight Animal: rat, Guideline: other:
Fatty acids, tall-oil, esters with polyethylene glycol mono(hydrogen maleate), compounds with amides from diethylenetriamine and tall-oil fatty acids (222716-38-3)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
toluene (108-88-3)	
LOAEL (oral, rat, 90 days)	1250 mg/kg bodyweight Animal: rat, Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents)

Nelfapox Universal Primer 2800 (Base)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

toluene (108-88-3)	
NOAEL (oral, rat, 90 days)	625 mg/kg bodyweight Animal: rat, Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation, rat, vapour, 90 days)	2.355 mg/l air Animal: rat, Guideline: EU Method B.29 (Sub-Chronic Inhalation Toxicity:90-Day Study)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
n-butyl acetate (123-86-4)	
LOAEL (oral, rat, 90 days)	500 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 798.2650 (90-Day Oral Toxicity in Rodents)
NOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 798.2650 (90-Day Oral Toxicity in Rodents)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	2.4 mg/l/6h/day
Aspiration hazard : Not classified	
Nelfapox Universal Primer 2800 (Base)	
Viscosity, kinematic	851.596 (821.596 – 997.653) mm²/s
Reaction mass of ethylbenzene and m-xylene and p-xylene	
Viscosity, kinematic	< 20.5 mm²/s
Phenol, methylstyrenated (68512-30-1)	
Viscosity, kinematic	294 mm²/s calculated
Reaction mass of ethylbenzene and xylene	
Viscosity, kinematic	< 0.9 mm²/s
1-methoxy-2-propanol; monopropylene glycol methyl ether (107-98-2)	
Viscosity, kinematic	1.848 mm²/s
2-methoxypropyl acetate (70657-70-4)	
Viscosity, kinematic	≤ 20.5 mm²/s
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-48-9)	
Viscosity, kinematic	1.02 mm²/s
Human evidence for classification	Yes
Hydrocarbon	Yes
Aliphatic, alicyclic or aromatic hydrocarbon	Yes
2,2'-iminodiethylamine; diethylenetriamine (111-40-0)	
Viscosity, kinematic	5.26 mm²/s
butan-1-ol; n-butanol (71-36-3)	
Viscosity, kinematic	3.7 mm²/s calculated
toluene (108-88-3)	
Viscosity, kinematic	0.647 mm²/s
n-butyl acetate (123-86-4)	
Viscosity, kinematic	0.83 mm²/s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm²/s)'

Nelfapox Universal Primer 2800 (Base)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

11.2. Information on other hazards

Endocrine disrupting properties

Component	
Phenol, methylstyrenated (68512-30-1)	The substance is identified for having endocrine disrupting properties but there is no additional data available (see section 2.3)

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: Harmful to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Harmful to aquatic life with long lasting effects.

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (25068-38-6)

EC50 - Crustacea [1]	≈ 2 mg/l Test organisms (species): Daphnia magna
----------------------	--

Reaction mass of ethylbenzene and m-xylene and p-xylene

EC50 - Crustacea [1]	> 3.4 mg/l Test organisms (species): Ceriodaphnia dubia
LOEC (chronic)	3.16 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	> 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d'

Reaction mass of ethylbenzene and xylene

LC50 - Fish [1]	2.6 mg/l
EC50 - Crustacea [1]	> 3.4 mg/l Test organisms (species): Ceriodaphnia dubia
EC50 72h - Algae [1]	2.2 mg/l
LOEC (chronic)	3.16 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	> 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d'

1-methoxy-2-propanol; monopropylene glycol methyl ether (107-98-2)

LC50 - Fish [1]	6812 mg/l
EC50 - Crustacea [1]	23300 mg/l
EC50 - Other aquatic organisms [1]	2954 mg/l Test organisms (species): other aquatic crustacea:

2-methoxy-1-methylethyl acetate (108-65-6)

LC50 - Fish [1]	> 100 mg/l
EC50 - Crustacea [1]	373 mg/l
EC50 72h - Algae [1]	> 1000 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
NOEC (chronic)	≥ 100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	47.5 mg/l Test organisms (species): Oryzias latipes Duration: '14 d'

Talc (14807-96-6)

LC50 - Fish [1]	89581.02 mg/l Test organisms (species): other:
LC50 - Fish [2]	110000 mg/l Test organisms (species): other:

Nelfapox Universal Primer 2800 (Base)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Talc (14807-96-6)	
EC50 96h - Algae [1]	7202.7 mg/l Test organisms (species): other:
NOEC (chronic)	1459.798 mg/l Test organisms (species): other: Duration: '30 d'
CI Pigment White 6 (13463-67-7)	
EC50 - Other aquatic organisms [1]	> 100 mg/l Test organisms (species):
EC50 72h - Algae [1]	> 100 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
LOEC (chronic)	5 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
Trimethylol propane (77-99-6)	
LC50 - Fish [1]	> 1000 mg/l Test organisms (species): Alburnus alburnus
LC50 - Fish [2]	> 10 g/l Test organisms (species): Alburnus alburnus
EC50 - Crustacea [1]	13000 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	> 1000 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
NOEC (chronic)	> 1000 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
(7429-90-5)	
EC50 72h - Algae [1]	1.05 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	0.2 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
2,2'-iminodiethylamine; diethylenetriamine (111-40-0)	
LC50 - Fish [1]	0.43 g/l Test organisms (species): Poecilia reticulata
EC50 - Crustacea [1]	64.6 mg/l Test organisms (species): Daphnia magna
EC50 - Crustacea [2]	16 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	1164 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	187 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
LOEC (chronic)	11.3 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	5.6 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	> 10 mg/l Test organisms (species): Gasterosteus aculeatus Duration: '28 d'
butan-1-ol; n-butanol (71-36-3)	
LC50 - Fish [1]	1910 (100 – 2300) mg/l
toluene (108-88-3)	
LC50 - Fish [1]	5.5 mg/l Test organisms (species): Oncorhynchus kisutch
LOEC (chronic)	2.76 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
NOEC (chronic)	0.74 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
NOEC chronic fish	1.39 mg/l Test organisms (species): Oncorhynchus kisutch Duration: '40 d'
n-butyl acetate (123-86-4)	
LC50 - Fish [1]	81 (18 – 185) mg/l
LC50 - Fish [2]	18 mg/l

Nelfapox Universal Primer 2800 (Base)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

n-butyl acetate (123-86-4)	
EC50 - Crustacea [1]	44 mg/l
EC50 72h - Algae [1]	200 mg/l
EC50 72h - Algae [2]	246 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
LOEC (chronic)	47.6 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	23.2 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

12.2. Persistence and degradability

Nelfapox Universal Primer 2800 (Base)	
Persistence and degradability	Rapidly degradable
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (25068-38-6)	
Persistence and degradability	Rapidly degradable
Reaction mass of ethylbenzene and m-xylene and p-xylene	
Persistence and degradability	Rapidly degradable
Phenol, methylstyrenated (68512-30-1)	
Persistence and degradability	Rapidly degradable
Reaction mass of ethylbenzene and xylene	
Persistence and degradability	Rapidly degradable
2-methoxypropanol (1589-47-5)	
Persistence and degradability	Rapidly degradable
1-methoxy-2-propanol; monopropylene glycol methyl ether (107-98-2)	
Persistence and degradability	Rapidly degradable
2-methoxy-1-methylethyl acetate (108-65-6)	
Persistence and degradability	Rapidly degradable
2-methoxypropyl acetate (70657-70-4)	
Persistence and degradability	Rapidly degradable
Talc (14807-96-6)	
Persistence and degradability	Rapidly degradable
Nefelinsyenit (37244-96-5)	
Persistence and degradability	Rapidly degradable
Quartz, inhalable fraction (14808-60-7)	
Persistence and degradability	Rapidly degradable
CI Pigment White 6 (13463-67-7)	
Persistence and degradability	Rapidly degradable
Trimethylol propane (77-99-6)	
Persistence and degradability	Rapidly degradable

Nelfapox Universal Primer 2800 (Base)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

(7429-90-5)	
Persistence and degradability	Rapidly degradable
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-48-9)	
Persistence and degradability	Rapidly degradable
2,2'-iminodiethylamine; diethylenetriamine (111-40-0)	
Persistence and degradability	Rapidly degradable
butan-1-ol; n-butanol (71-36-3)	
Persistence and degradability	Rapidly degradable
Fatty acids, tall-oil, esters with polyethylene glycol mono(hydrogen maleate), compounds with amides from diethylenetriamine and tall-oil fatty acids (222716-38-3)	
Persistence and degradability	Rapidly degradable
toluene (108-88-3)	
Persistence and degradability	Rapidly degradable
n-butyl acetate (123-86-4)	
Persistence and degradability	Rapidly degradable
12.3. Bioaccumulative potential	
reaction product: bisphenol-A(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (25068-38-6)	
Partition coefficient n-octanol/water (Log Pow)	3.242
Reaction mass of ethylbenzene and xylene	
Partition coefficient n-octanol/water (Log Pow)	3.1
1-methoxy-2-propanol; monopropylene glycol methyl ether (107-98-2)	
Partition coefficient n-octanol/water (Log Pow)	-0.44
2-methoxy-1-methylethyl acetate (108-65-6)	
Partition coefficient n-octanol/water (Log Pow)	1.2
2-methoxypropyl acetate (70657-70-4)	
Partition coefficient n-octanol/water (Log Pow)	1.2
Trimethylol propane (77-99-6)	
Partition coefficient n-octanol/water (Log Pow)	-0.47
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-48-9)	
Partition coefficient n-octanol/water (Log Pow)	> 4
butan-1-ol; n-butanol (71-36-3)	
Partition coefficient n-octanol/water (Log Pow)	0.88
toluene (108-88-3)	
Partition coefficient n-octanol/water (Log Pow)	2.73
n-butyl acetate (123-86-4)	
Partition coefficient n-octanol/water (Log Pow)	2.3

Nelfapox Universal Primer 2800 (Base)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

Component	
Substance(s) meeting the vPvB criteria of REACH regulation, in accordance with Annex XIII	Phenol, methylstyrenated (68512-30-1)
Substance(s) not meeting the PBT criteria of REACH regulation, in accordance with Annex XIII	Phenol, methylstyrenated (68512-30-1)
PBT: not relevant – no registration required	butan-1-ol; n-butanol (71-36-3)(¹)
vPvB: not relevant – no registration required	butan-1-ol; n-butanol (71-36-3)(¹)

(¹) Substance(s) in concentration below 0.1 % and displayed on a voluntary basis

12.6. Endocrine disrupting properties

Component	
Phenol, methylstyrenated (68512-30-1)	The substance is identified for having endocrine disrupting properties but there is no additional data available (see section 2.3)

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional waste regulation	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Disposal must be done according to official regulations.
Additional information	: Flammable vapours may accumulate in the container. Do not re-use empty containers.
European List of Waste (LoW, EC 2000/532)	: 08 01 11* - waste paint and varnish containing organic solvents or other dangerous substances 08 01 12 - waste paint and varnish other than those mentioned in 08 01 11

SECTION 14: Transport information

In accordance with ADR / RID

ADR	RID
14.1. UN number or ID number	
UN 1263	UN 1263
14.2. UN proper shipping name	
PAINT	PAINT
Transport document description	
UN 1263 PAINT, 3, III, (D/E)	UN 1263 PAINT, 3, III
14.3. Transport hazard class(es)	
3	3

Nelfapox Universal Primer 2800 (Base)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878


ADR	RID
	
14.4. Packing group	
III	III
14.5. Environmental hazards	
Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available	

14.6. Special precautions for user

Special transport precautions : In package sizes smaller than 450 L, under the conditions of 2.2.3.1.5.1, this product is ADR exempt.

Overland transport

Classification code (ADR) : F1
Special provisions (ADR) : 163, 367, 650
Limited quantities (ADR) : 5L
Excepted quantities (ADR) : E1
Packing instructions (ADR) : P001, IBC03, LP01, R001
Special packing provisions (ADR) : PP1
Mixed packing provisions (ADR) : MP19
Portable tank and bulk container instructions (ADR) : T2
Portable tank and bulk container special provisions (ADR) : TP1, TP29
Tank code (ADR) : LGBF
Vehicle for tank carriage : FL
Transport category (ADR) : 3
Special provisions for carriage - Packages (ADR) : V12
Special provisions for carriage - Operation (ADR) : S2
Hazard identification number (Kemler No.) : 30
Orange plates :



Tunnel restriction code (ADR) : D/E

Rail transport

Classification code (RID) : F1
Special provisions (RID) : 163, 367, 650
Limited quantities (RID) : 5L
Excepted quantities (RID) : E1
Packing instructions (RID) : P001, R001
Special packing provisions (RID) : PP1
Mixed packing provisions (RID) : MP19
Transport category (RID) : 3
Colis express (express parcels) (RID) : CE4
Hazard identification number (RID) : 33

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

Nelfapox Universal Primer 2800 (Base)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)	
Reference code	Applicable on
3(b)	Nelfapox Universal Primer 2800 (Base) ; Phenol, methylstyrenated ; Reaction mass of ethylbenzene and xylene ; 2-methoxypropanol ; 1-methoxy-2-propanol; monopropylene glycol methyl ether ; 2-methoxy-1-methylethyl acetate ; 2-methoxypropyl acetate ; Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics ; 2,2'-iminodiethylamine; diethylenetriamine ; butan-1-ol; n-butanol ; Fatty acids, tall-oil, esters with polyethylene glycol mono(hydrogen maleate), compounds with amides from diethylenetriamine and tall-oil fatty acids ; toluene
3(a)	Nelfapox Universal Primer 2800 (Base) ; Reaction mass of ethylbenzene and xylene ; 2-methoxypropanol ; 1-methoxy-2-propanol; monopropylene glycol methyl ether ; 2-methoxy-1-methylethyl acetate ; 2-methoxypropyl acetate ; Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics ; butan-1-ol; n-butanol ; toluene
3(c)	Nelfapox Universal Primer 2800 (Base) ; Phenol, methylstyrenated ; Fatty acids, tall-oil, esters with polyethylene glycol mono(hydrogen maleate), compounds with amides from diethylenetriamine and tall-oil fatty acids ; toluene

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains substance(s) listed on the REACH Candidate List in concentrations ≥ 0.1 % or SCL: Phenol, methylstyrenated (EC 270-966-8, CAS 68512-30-1)

PIC Regulation (Prior Informed Consent)

Contains substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals): Naphtha (petroleum), hydrotreated heavy (64742-48-9)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (2024/590)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 2024/590 on substances that deplete the ozone layer)

Council Regulation (EC) for the control of dual-use items

Contains substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items: Aluminium powder (7429-90-5).

VOC Directive (2004/42)

Contains organic solvents (≥ 1%)	
VOC content	: 370 g/l
Decopaint Directive (2004/42/EC) - Annex II	: A/j (Paints and Varnishes - Two-pack reactive performance coatings for specific end use such as floors)
Maximum allowed concentration	: 500 g/l VOC
Maximum content of VOC	: 437.00 g/l VOC

Explosives Precursors Regulation (EU 2019/1148)

Contains substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (EC 273/2004)

Contains substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

Name	CN designation	CAS-No.	CN code	Category, Subcategory	Threshold	Annex
Toluene		108-88-3	2902 30 00	Category 3		Annex I

National regulations

Nelfapox Universal Primer 2800 (Base)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Netherlands

ABM category	: Z(2) - biodegradable substances with hazardous properties for humans and the environment (carcinogenicity/ mutagenicity/reprotoxicity/bioaccumulative potential or toxicity)
SZW List of Carcinogenic Substances	: Phenol, methylstyrenated,2-methoxypropyl acetate,Nefelinsyenit,Quartz, inhalable fraction are listed
SZW List of Mutagenic Substances	: Phenol, methylstyrenated,2-methoxypropyl acetate,Nefelinsyenit are listed
SZW List of Reprotoxic Substances – Breastfeeding	: None of the components are listed
SZW List of Reprotoxic Substances – Fertility	: None of the components are listed
SZW List of Reprotoxic Substances – Development	: 2-methoxypropanol,2-methoxypropyl acetate,toluene are listed

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes		
Section	Changed item	Comments
	Revision date	Modified
2.1	Contains	Modified
2.2	EUH-statements	Removed

Abbreviations and acronyms:	
ACGIH	American Conference of Governmental Industrial Hygienists
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
CAS-No.	Chemical Abstracts Service number
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
COD	Chemical oxygen demand (COD)
CSA	Chemical safety assessment
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
ED	Endocrine disruptor
EN	European Standard
EWC	European waste catalogue
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration

Nelfapox Universal Primer 2800 (Base)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:	
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
Log Kow	Partition coefficient n-octanol/water (Log Kow)
Log Pow	Partition coefficient n-octanol/water (Log Pow)
MAK	maximum workplace concentration
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
N.O.S.	Not Otherwise Specified
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
OSHA	Occupational Safety Health Administration
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
PPE	Personal protection equipment
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
TF	Technical function
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
TWA	Time Weighted Average
VOC	Volatile Organic Compounds
vPvB	Very Persistent and Very Bioaccumulative
UFI	Unique Formula Identifier

Full text of H- and EUH-statements:	
Acute Tox. 2 (Inhalation)	Acute toxicity (inhal.), Category 2
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2

Nelfapox Universal Primer 2800 (Base)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
Flam. Liq. 3	Flammable liquids, Category 3
Flam. Sol. 1	Flammable solids, Category 1
Repr. 1B	Reproductive toxicity, Category 1B
Repr. 2	Reproductive toxicity, Category 2
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation
Water-react. 2	Substances and Mixtures which, in contact with water, emit flammable gases, Category 2
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H228	Flammable solid.
H261	In contact with water releases flammable gases.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H360D	May damage the unborn child.
H361d	Suspected of damaging the unborn child.
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:		
Flam. Liq. 3	H226	On basis of test data
Skin Irrit. 2	H315	Calculation method

Nelfapox Universal Primer 2800 (Base)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:		
Eye Irrit. 2	H319	Calculation method
Skin Sens. 1	H317	Calculation method
STOT SE 3	H335	Calculation method
STOT RE 2	H373	Calculation method
Aquatic Chronic 3	H412	Calculation method

Safety Data Sheet applicable for regions : NL - Netherlands
The classification complies with : ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.