

PRIMER VT PLUS

Primer/vapour barrier for floors and walls in wet rooms



PRODUCT IDENTITY

Primer VT Plus is a latex-based, thixotropic primer/vapour barrier for wet rooms. It is part of a technically approved wet-room system and of the VT system, together with **Mapegum WPS**.

WHERE TO USE

Primer VT Plus can be applied to concrete, render, anhydrite screed, plasterboard and cementitious fillers, as well as approved construction boards. It can be applied in wet rooms where there is a requirement of an S_D value of over 10 m.

RECOMMENDATIONS

Primer VT Plus should not be diluted with water.

DIRECTIONS FOR USE

Substrate

The substrate must be clean and dry.

Application

Apply **Primer VT Plus** with a roller/brush in two coats, with a total consumption of 0.3 kg per m². The coats should be applied at right angles to each other.

Mapegum WPS can be applied once the **Primer VT Plus** is dry (approx. 30 minutes at +20°C).

CLEANING

All equipment used should be cleaned immediately after use with water.

CONSUMPTION

0.3 kg/m².

PACKAGING

Primer VT Plus is supplied in 6 and 14 kg tubs.

STORAGE

Primer VT Plus can be stored for 12 months unopened in its original packaging.

Primer VT Plus must be stored in a frost-free environment.

SAFETY INSTRUCTIONS FOR PREPARATION AND INSTALLATION

Instructions for the safe use of our products can be found on the latest version of the SDS available from our website www.mapei.no

PRODUCT FOR PROFESSIONAL USE.

TECHNICAL DATA (typical values)

PRODUCT IDENTITY

Colour:	blue
Consistency:	liquid
Density:	approx. 1.28 g/cm ³
pH:	2 - 3
Dry solid content:	55 %
Viscosity:	tixotropic
EMICODE:	EC1 Plus – very low emission

PRODUCT APPLICATION DATA (at +20°C, 50 % RH)

Application temperature range:	from +10°C to +40°C
--------------------------------	---------------------

FINAL PROPERTIES

Ready for coating:	when primer is dry, after approx. 30 minutes
--------------------	--

WARNING

Although the technical details and recommendations contained in this product data sheet correspond to the best of our knowledge and experience, all the above - information must, in every case, be taken as merely indicative and subject to confirmation after long-term practical application: for this reason, anyone who intends to use the product must ensure beforehand that it is suitable for the envisaged application: in every case, the user alone is fully responsible for any consequences deriving from the use of the product.

Please refer to the current version of the technical data sheet, available from our web site www.mapei.no

LEGAL NOTICE

The contents of this Technical Data Sheet ("TDS") may be copied into another project-related document, but the resulting document shall not supplement or replace requirements per the TDS in effect at the time of the MAPEI product installation. For the most up-to-date TDS and warranty information, please visit our website at www.mapei.no

ANY ALTERATIONS TO THE WORDING OR REQUIREMENTS CONTAINED IN OR DERIVED FROM THIS TDS SHALL VOID ALL RELATED MAPEI WARRANTIES.

Mapei AS

Vallsetvegen 6, 2120 Sagstua, Norge



+47 62 97 20 00



www.mapei.no



post@mapei.no

10205-5-2021-gbxno

Any reproduction of texts, photos and illustrations published here is prohibited and subject to prosecution.

