

A BRAND AT-1 Advanced Performance One Pass Thread Mill The World's Only Single Pass Thread Mill!

PRIMARY TARGETS

Thread Milling Customers Looking to Reduce Cycle Time by 50%!

SOLUTIONS

- A Single Pass Option to Cut Cycle Time!
- Working in Tandem with the Trifecta (The AT-1 along with OSG's thread milling software Thread Pro and the DCT a Diameter Correction Tool for easy and consistent setups)

WHAT OUR CUSTOMERS SEE

- Three Passes to a Single Pass! What a Difference!
- Setup Time *Reduced by 50%!*

HOW DOES IT WORK?

Unique Helix Geometry

• Eliminates Cutting Deflection for Straight Threads

Variable Geometry

Reduces Chatter and Increases Tool Life

EgiAs Coating

For Exceptional Wear Resistance

OSG's Trifecta

AT-1 + Thread Pro + DCT = Low Setup Times

A The A Brand

osgtool.com OSG USA, Inc. : 800-837-2223

OSG Canada, Ltd. : 905-632-8032 • OSG Royco (Mexico) : +52 (722) 279-36-08 to 11

A Brand AT-1 Advanced Performance One Pass Thread Mill

A Brand AT-1



OSG's newest thread mill, the A Brand AT-1, is designed with a left-hand helix and starts cutting from the shank side, reducing deflection, preventing bending, thus allowing for 1-pass cutting and reducing overall cutting time. Along with OSG's patented EgiAs coating, it also has unequal spacing/variable lead flute which reduces vibration for better thread quality.



Features & Benefits

- OSG's EgiAs coating for exceptional wear resistance and longer tool life.
- Right-hand cut and left-hand helix geometry to prevent bending/deflection.
- · Unequal spacing/variable lead flute for reduced vibration.

List Numbers

16620 - A Brand AT-1 (Inch) 16625 - A Brand AT-1 (Metric) 16630 - A Brand AT-1 (NPT) 16631 - A Brand AT-1 (NPTF)


Size Range

1/4"-1" M6-M24 1/16"-1" 1/16"-1"


1-Pass Cutting

Left Hand Helix Reduces Deflection for 1-Pass Cutting

The AT-1 is designed with a left hand helix and starts cutting from the shank side, reducing deflection, preventing bending, thus allowing for 1-pass cutting and reducing overall cutting time.



Starts cutting from the shank side Result: Reduced deflection Note: Climb milling recommended



Starts cutting from the tip Result: Big deflection

ТооІ	AT-1 (List 16620)	Conventional
Size	Ø19.7mm • 54mm Length of Cut	
Thread Size	M24 x 3	
Work Material	304 Stainless Steel	
Tapping Depth	45mm (full depth)	
Cutting Speed	131 SFM (646 RPM)	
Feed	5.9 IPM (0.0016 IPT)	
Number of Passes	1	2
Coolant	Water-Soluble	
Machine	Horizontal Machining Center	





For more information use your phone to scan the QR code to the right and visit: osgtool.com/at-1



EDP#800334CA

osgtool.com OSG USA, Inc.: 800-837-2223 OSG Canada, Ltd.: 905-632-8032 • OSG Royco (Mexico): +52 (722) 279-36-08 to 11