



CLEAN OIL
BRIGHT IDEAS

A 15/25

CJC™ Off-line Filter Insert

CJC™ Product Sheet

APPLICATION

The CJC™ A 15/25 Filter Insert is ideal for the fine filtration of mineral and synthetic based

- engine lube oils
- turbine lube oils
- hydraulic oils
- gear oils
- honing oils
- quenching oils

FILTRATION CAPABILITY

- **Particle Removal**

All CJC™ Filter Inserts have the following filtration degree:

- particles $> 3 \mu\text{m}$ (micron) absolute
= 98.7% of all solid particles
- particles $> 0.8 \mu\text{m}$ (micron) nominal
= 50% of all solid particles

are retained in each pass.

The dirt holding capacity of an A 15/25 Insert is 1.5 litres of evenly distributed solids.

- **Degradation Products**

Oxidation by-products, resin / sludge, and varnish are retained by the cellulose material. The cellulose will retain **appr. 1 kg** of degradation products.

- **Water Removal**

The water absorption potential is up to 50% (i.e. 750 mL H₂O) of the total contaminant holding capacity.

DIMENSIONS

The figures below are nominal:

Diameter: 15 cm
Height: 25 cm

COMPONENT

CJC™ Filter Inserts type A consist of bonded discs. Main ingredient is wood cellulose.

IDENTIFICATION

To order the A 15/25 Filter Insert, please use:
Article No: PA5600322



CJC™ A 15/25 Filter Insert