

Make / Model SUBARU/IMPREZA SDN/WGN

Other

Year 3/93 – 8/07

Part number T2S013

Maximum towing capacity 750 kg

Maximum ball load 60 kg

Bar weight 12 kg

Fit with wiring harness part No. EL5804

Fitting Instructions

Warning:

Safety First: Always use correct safety equipment.

This towbar is NOT to be drilled, cut, welded or modified in any way.

Check the surrounding area before drilling into chassis or body panels for fuel lines, wiring harnesses and other components that may be a hazard.

General:

Before fitting this towbar read fitting instructions and check installation hardware is correct.

Check that the towbar is suitable for the vehicle and be wary of any changes to the vehicle design that may conflict with the fitting of this towbar.

After drilling, blow any filings clear, remove any swarf and treat exposed metal with a rust inhibitor.

If this vehicle requires a bumper cut out, please check to make sure that you measure twice and check twice before cutting any panels as some bumper profiles can change.

If you are not sure then ask your towbar supplier.

Tighten all bolts as specified on the last page.

1. REMOVE BOLTS AND FITTING KIT FROM TOWBAR/PACKER PLATE IN KIT PROVIDED TO BE USED ON MODELS WITH AIR BOX INSTALLED.
 - 1.1. UNDO EXHAUST FROM REAR HANGER.
 - 1.2. REMOVE PASSENGER SIDE SHIPPING HOOK/KEEP M12 BOLTS ONLY.
 - 1.3. REMOVE DRIVERS SIDE SHIPPING HOOK/KEEP M12 BOLTS ONLY.
 - 1.4. REMOVE CENTRE BUMPER SUPPORT TAB SCRIVET.
2. INSTALL TOW BAR USING ORIGINAL M12 BOLTS AND TIGHTEN TO SPECIFIED RATINGS.
 - 2.1. IF VEHICLE HAS AIR BOX INSTALLED/PLATE TO BE FITTED BETWEEN TOW BAR AND SUB FRAME OF VEHICLE USING REAR TWO BOLTS ON DRIVERS SIDE/FRONT HOLE FOR AIR BOX.
 - 2.2. REMOUNT EXHAUST USING LONG M10 BOLT AND WASHERS PROVIDED.
 - 2.3. REATTACH CENTRE BUMPER SUPPORT.

INSTALL BALLMOUNT /ATTACH RATINGS STICKERS TO DRIVERS SIDE DOOR PILLAR.

Torque table for bolt tightening

Metric GRADE 8.8	UNC GRADE 8
M6 – 12.5 Nm	3/8 – 50 Nm
M8 – 30 Nm	1/2 - 125 Nm
M10 – 60 Nm	5/8 – 245 Nm
M12 – 103 Nm	
M14 – 167 Nm	
M16 – 270 Nm	