

Max Towing Capacity: 2000kg	Towbar Weight: 22kg
Max Ball Load: 200kg	Wiring Harness Part #: UNT337



Tools Required: - Spanners, Sockets, Torque Wrench

Kit Contents					
Item No.	Description	Qty	Item No.	Description	Qty
1.	Towbar – T4D519	1	6.	Plate – 40 x 40	4
2.	Ball Mount – L4120	1	7.	M8 x 1.25 x 30 Bolt & Nut	8
3.	M12 x 1.25 x 35 Bolt	4	8.	M8 Shake proof washer	8
4.	M12 Shake proof washer	4	9.	M8 Flat washer	8
5.	M12 Flat Washer	4	10.	Class 4 Pin	1



## Warning:

- This product is for towing purposes only and must only be loaded as shown in your vehicle Owners Manual.
- This towbar is NOT to be drilled, cut, welded or modified in any way.
- Check behind chassis rail and body panels before drilling to ensure no hazards are present

## General:

- Before fitting this towbar read fitting instructions and check installation hardware is correct.
- Check that the towbar is suitable for the vehicle and be wary of any changes to the vehicle design that may conflict with the fitting of this towbar.
- After drilling, blow any filings clear, remove any swarf and treat exposed metal with a rust inhibitor.
- If this vehicle requires a bumper cut out, please check to make sure that you measure twice and check twice before cutting any panels as some bumper profiles can change. If you are not sure, then please ask your towbar supplier

Nissan X-Trail T31 Wagon– T4D519



#### Step 1 **Remove Rear Bumper** Instructions Tools **Torque Spec** a. Remove 2 x scrivets from bottom centre of **Torque Keys** bumper/disconnect reverse lamps. **Trim Removal Tool** b. Open tailgate /2 x plastic caps to be removed revealing top bumper fixture. c. Remove torque screws from wheel arches then carefully pull flare from guard to reveal 10mm head bolt to be removed. d. Remove bumper pulling out at sides then rearwards from centre/place bumper onto a stand.

Step 2	Remove Impact Beam		
Instructio	ons	Tools	Torque Spec
a. Remove impact beam and discard/remove		Spanners Sockets	90Nm

## Step 3 **Towbar Fitment** Tools **Torque Spec** Instructions a. Remove all bolts from tow bar taking note of Sockets bolt locations and assembly. Spanners b. Install tow bar into subframe and secure using M8 bolts and washers into existing captive nuts on back panel of vehicle.[leave loose] c. 4 x M12 bolts, plates and washers to be installed into side arms of towbar through existing holes under vehicle. [previously drilled for clearance]



Nissan X-Trail T31 Wagon– T4D519

Ste	ep 4	Bumper Cut		
Inst	ructior	15	Tools	Torque Spec
b.	been in on veh down t transfe of bum 85mm measu [CHEC	er cut out to be done after towbar has installed /using bumper retaining strip nicle as a reference point, measure to the top of hitch box of towbar and er this measurement to the back centre inper. Section to be removed will be wide x 120mm down from point red. K MEASUREMENTS TO BE CORRECT E CUTTING BUMPER]	Air Saw	

St	ep 5	Finishing Up		
Ins	tructior	IS	Tools	Torque Spec
a. b. c. d.	Refit e reverse Fit ball	n all bolts to specified ratings. xhaust/refit bumper/reconnect e lamps. mount with pin and clip provided. ratings sticker to drivers side door	Torque Wrench	M12-103Nm M8-30Nm
		Facturer of TAG branded products, war following conditions:	RRANTY STA	
	• Yo	u can show proof of purchase.		
	• Th	e towbar has been correctly installed I	by a suitably qualified instal	ler.
		e towbar has not been modified or ab rpose intended.	used in any way and has on	ly been used for the



Nissan X-Trail T31 Wagon- T4D519

• The towbar was not fitted second hand to your vehicle.

The extent of this warranty includes materials and workmanship used in the manufacture of the towbar and is to the equivalent value of current, full replacement cost.

Nothing stated or implied in this warranty limits in any way, the statutory rights that you may have.

To make a claim visit the original installer in the first instance or, if you are unable to or are not satisfied with their help, then contact us directly by email at warranty@tagtowing.com