

Fitting Instructions



SKU

PRODUCT

T4D569

TAG Heavy Duty Towbar to suit Nissan Patrol (04/1992 - 02/2017)



Scan for latest
version of these
instructions


SPECIFICATIONS

- Towbar Class: Heavy Duty
- Towing Capacity: 2500kg

IN THIS GUIDE

- Fitment Instructions
- Torque Settings
- Warranty Info

Towbar Fitting Instructions



<i>Item Number</i>	<i>Item</i>	<i>Quantity</i>
1	Towbar – T4D569	1
2	Ball Mount– L4180	1
3	M14 x 1.5 x 40 Bolt	4
4	M14 Shake proof washer	4
5	M14 Flat Washer	4
6	M14 x 1.5 Nut	4
7	½" x 1 ½" UNC Bolt	4
8	M12 Shake proof washer	10
9	½" Flat washer	10
10	½" UNC Nut	10
11	Plate with bend– Left & Right	1 of ea
12	Plate rectangular	2
13	½" x 2" Bolt with wire & plate	6
14	Class 4 Pin & Clip	1

Tools Required: Spanners, Screwdriver, Sockets, Torque wrench

Step-By-Step Instructions

Warning:

- This product is for towing purposes only and must only be loaded as shown in your vehicle Owner's Manual.
- This towbar is NOT to be drilled, cut, welded, or modified in any way.
- Check behind chassis rail and body panels before drilling to ensure no hazards are present
- All load ratings shown are under the assumption your trailer has a functional braking system installed
- When installed in positions other than the one depicted in these instructions the Tow Ball Mount may interfere or obstruct certain features of your vehicle (tailgate opening, Chassis clearance, etc.)

General:

- Before fitting this towbar read fitting instructions and check installation hardware is correct.
- Check that the towbar is suitable for the vehicle and be wary of any changes to the vehicle design that may conflict with the fitting of this towbar. (Tray, Canopy, Suspension etc.)
- After drilling, blow any filings clear, remove any swarf and treat exposed metal with a rust inhibitor.
- The high tensile fasteners supplied with this product are an integral feature to achieving the specified rating, if replacement is required ensure that fasteners of the same grade (8.8) & quality are used. Contact an authorised TAG distributor or the TAG fitment centre - (07) 3208 3022 - if further information is required.

Towbar Maintenance and Care:

It is recommended, when not in use, the Tow Ball Mount assembly and class 4 Pin and Clip is stored inside the car away from moisture to prevent standing water from forming rust. Inspect to ensure, on regular basis, fasteners are torqued to the specifications below and in good condition.

**Ensure that the fitting instructions are read and understood prior to fitment
Place these instructions in the vehicle's glovebox after installation is completed**

Towbar Fitting Instructions



Step 1. Fit Towbar

- a. Remove centre towing bracket from crossmember.
- b. Lift towbar up to the outside of the chassis rails. Insert 2x 1½"x ½" bolts each side into chassis & secure loosely.
- c. Bolt angle plates to towbar sidearms using 2x M14 x40 bolts, washers & nuts per side and clamp to underside of chassis rail.
- d. Use holes in angle brackets as a guide and drill 13mm holes in bottom face of chassis.
- e. Insert 2"x ½" bolts on wire into chassis and down through drilled holes.
- f. Secure with ½" nuts & washers.
- g. Tighten all bolts to torque specification on back page.

Step 2. Fit Ball Mount and Apply Door Sticker

- a. Attach plastic hitch surround to receiver.
- b. Insert ball mount into hitch receiver and secure with the pull pin and R-clip.
- c. Apply one of the compliance labels to the pillar of the driver's door.
- d. Leave the remaining label & the fitting instructions in the vehicle handbook



Torque table for bolt tightening

Diameter	Pitch	Grade	Torque	Unit
M8	1.25	8.8	29	Nm
M10	1.25	8.8	57	Nm
M10	1.50	8.8	44	Nm
M12	1.25	8.8	101	Nm
M12	1.50	8.8	97	Nm
M12	1.75	8.8	77	Nm
M14	2.00	8.8	122	Nm
M16	2.00	8.8	190	Nm
Imperial Bolt Torque Settings				
3/8"	UNC	8	44.75	Nm
1/2"	UNC	8	108.5	Nm

TAG Warranty Statement

SWD warrants your TAG Towbar for its full product life under the following conditions:

- You can show proof of purchase.
- The towbar has been correctly installed by a suitably qualified installer.
- The towbar has not been modified or abused in any way and has only been used for the purpose intended.
- The towbar was not fitted second hand to your vehicle.

The extent of this warranty includes materials and workmanship used in the manufacture of the towbar and is to the equivalent value of current, full replacement cost.

Nothing stated or implied in this warranty limits in any way, the statutory rights that you may have.

To make a claim visit the original installer in the first instance or, if you are unable to or are not satisfied with their help, then contact us direct by phone on 1300 669122 or visit www.swd.com.au