Hyundai Getz 3&5 DR – (10/03 - ON) – T2Z506



Max Towing Capacity: 700kg		Towbar Weight: 12kg	
Max Ba	all Load: 70kg	Wiring Harness Part #:	
	Tools Required:		
Spanners, Sockets, Screwdriver, Torque wrench		wrench	



ITEM	DESCRIPTION	QTY.	ITEM	DESCRIPTION	QTY.
NO.			NO.		
1	Towbar – T2Z506	1	5	1/2" Flat Washer	4
not Shown	Ball Mount – L201	1	6	M16 x 2 x 40	2
3	M12 x 1.25 x 40 Bolt	4	7	M16 Spring Washer	2
4	M12 Shake proof washer	4			

Hyundai Getz 3&5 DR – (10/03 - ON) – T2Z506

ENSURE THAT THE FITTING INSTRUCTIONS ARE READ AND UNDERSTOOD PRIOR TO FITMENT PLACE THESE INSTRUCTIONS IN THE VEHICLE'S GLOVEBOX AFTER INSTALLATION IS COMPLETED Warning:

TOWBA

- This product is for towing purposes only and must only be loaded as shown in your vehicle Owner's Manual.
- This towbar is NOT to be drilled, cut, welded, or modified in any way.
- All load ratings shown are under the assumption your trailer has a functional braking system installed
- When installed in positions other than the one depicted in these instructions the Tow Ball Mount may interfere or obstruct certain features of your vehicle (tailgate opening, Chassis clearance, etc.)

General:

- Before fitting this towbar check installation hardware is included and correct.
- Check that the towbar is suitable for the vehicle make, model and year then make sure any changes to the vehicle design do not conflict with the fitting of this towbar. (Tray, Canopy, Suspension etc.)
- After drilling, blow any filings clear, remove any swarf and treat exposed metal with a rust inhibitor.
- Check behind chassis rail and body panels before drilling to ensure no hazards are present (fuel lines, electrical wires etc.)
- If this vehicle requires a bumper cut out, please check to make sure that your measurements are correct and clear before cutting any panels as some bumper profiles can change. If you are not sure, then please ask your towbar supplier
- The high tensile fasteners supplied with this product are an integral feature to achieving the specified rating, if replacement is required ensure that fasteners of the same grade (8.8) & quality are used. Contact an authorised TAG distributer or the TAG fitment centre (07) 3208 3022 if further information is required.

Towbar Maintenance and Care:

It is recommended, when not in use, the Tow Ball Mount assembly and class 4 Pin and Clip is stored inside the car away from moisture to prevent standing water from forming rust. Inspect to ensure, on regular basis, fasteners are torqued to the specifications below and in good condition.

Metric Bolt Torque Settings										
Diameter	Pitch	Grade	Torque	Unit		Diameter	Pitch	Grade	Torque	Unit
M8	1.25	8.8	29	Nm		M12	1.50	8.8	97	Nm
M10	1.25	8.8	57	Nm		M12	1.75	8.8	77	Nm
M10	1.50	8.8	44	Nm		M14	2.00	8.8	122	Nm
M12	1.25	8.8	101	Nm		M16	2.00	8.8	190	Nm
Imperial Bolt Torque Settings										
3/8"	UNC	8	44.75	Nm		1/2''	UNC	8	108.5	Nm

Hyundai Getz 3&5 DR – (10/03 - ON) – T2Z506



Step 1	Remove Exhaust & Fit Towba	•				
	Instructions					
b. Fit tow up first a washers plate bet c. Fit pas washers specified	ve exhaust from rear hanger of vehicle. vbar onto vehicle placing drivers' side and securing with M12 bolts and supplied making sure to place spacer tween towbar and subframe. senger side with M12 bolts and supplied and tighten all bolts to I ratings (Pg.2). xhaust onto rear hanger.					

Step 2	Fit Ball Mount and Apply Door	· Sticker
	Instruct	ions
b. Secure c. Apply pillar of d. Leave	a plastic hitch surround to receiver. e Ball Mount to the towbar one of the compliance labels to the the driver's door. the remaining label & the fitting ons in the vehicle handbook.	



Hyundai Getz 3&5 DR - (10/03 - ON) - T2Z506



WARRANTY STATEMENT

The manufacturer of TAG branded products, warrants your TAG Towbar for its full product life under the following conditions:

- You can show proof of purchase.
- The towbar has been correctly installed by a suitably qualified installer.
- The towbar has not been modified or abused in any way and has only been used for the purpose intended.
- The towbar was not fitted second hand to your vehicle.

The extent of this warranty includes materials and workmanship used in the manufacture of the towbar and is to the equivalent value of current, full replacement cost. Nothing stated or implied in this warranty limits in any way, the statutory rights that you may have.

To make a claim visit the original installer in the first instance or, if you are unable to or are not satisfied with their help, then contact us directly by email at warranty@tagtowing.com