

ZU607T

High brightness professional laser projector









- Bright WUXGA laser projector 6500 lumens
- 30,000 hours maintenance-free laser light source
- Control with HDBaseT 3.0, RS232 and OMSL
- 4K, HDR and HLG Compatibility



The high brightness ZU607T features 6500 lumens, 4K and HDR compatibility and a dust resistant IP6X certified optical engine for 24/7 operational capabilities and low maintenance. This projector boasts an extremely long-life laser technology, manual horizontal and vertical lens shift and built-in 15W speakers.

Specifications

EAN: 5055387668515, Colour: White

Display/image Display technology DLP

Resolution WUXGA (1920x1200) Brightness 6,500 lumens 5.200 **ANSI** brightness 300.000:1 Contrast ratio Native aspect ratio 16:10 4:3,16:9,16:10 Aspect ratio - compatible +-30° Keystone correction -

horizontal

Keystone correction - vertical +-30°

Has vertical auto keystone Yes correction

Displayable colours (millions) 1073.4 Horizontal scan rate 5k~140kHzKhz Vertical scan rate 24~120HzHz Uniformity 85%

0.8m ~ 7.67m (31.5" ~ 301.8") diagonal Screen size

Lamp info Light source type Laser 30,000 hours LASER life

Optical 1.2:1 ~ 1.92:1 Throw ratio Projection distance (m) 1.3m - 7.8m Zoom 1.6 Zoom type Manual

Focal length (mm) 17.63 ~ 27.9 Lens shift Vertical -100 ~ 120%, Horizontal: +/-10%

Native offset 120%

Lens shift Yes - {{downloads_link}}

Connectivity

Connections Inputs 2 x HDMI 2.0, 2 x VGA, 1 x Composite video, 2 x

Audio 3.5mm, 1 x USB-A power 1.5A

Outputs 1 x HDMI 2.0, 1 x Audio 3.5mm, 1 x 3D sync, 1 x

Control 1 x HDBaseT 4K, 1 x RJ45, 1 x RS232

LAN - wireless networking

General Noise level (min) 33dB Noise level (max) 36dB Full 3D 3D

Security Security bar, Kensington Lock, Password protected interface

IP rating IP6X

OSD / display languages 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi,

Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional),

Turkish, Vietnamese

24/7 operation Yes 360° operation Yes

Backlit ProAV remote Remote control 883BTU/hour Heat dissipation Speaker count

Watts per speaker 15W In the box AC power cord

Remote control 2x AAA batteries

Basic user manual

Networking LAN - control

Yes LAN - wireless networking No LAN

Power

Universal AC 100--240V± 10%~ 50 / 60 Hz with PEC input Power supply

<0.5W Power consumption (standby) Power consumption (min) 300W 366W Power consumption (max)

Weight and dimensions

374 x 302 x 117 Dimensions (W x D x H) mm Gross weight 8.6 kg Net weight 6.3 kg





