

ZH462

Eco-friendly compact high brightness Full HD laser projector









- Bright Full HD 1080p DuraCore laser projector -5000 lumens and IP6X certified
- Compact for easy installation 1.3x zoom, 360-degree and portrait projection
- Reduced power consumption for a long life span -DuraCore laser technology delivers 30,000 hours maintenance free laser light source
- External power supply More reliability, portability and energy efficiency



The ZH462 is one of Optoma's most compact and hassle-free Full HD 1080p DuraCore laser projectors to date. Designed for maintenance-free continuous operation, it delivers powerful image performance with flexible installation features and extensive connectivity options in a sleek, compact form factor, up to 34% smaller than previous Optoma models.¹

An added benefit, the ZH462 features an external power supply offering more reliability, portability and energy efficiency.

Specifications

Focal length (mm) Native offset

Connectivity

3D compatibility

EAN: 5055387667860, Colour: White

UPC: 796435447106, Colour: White Display/image DLP™ Display technology 1080p Full HD (1920x1080) Resolution **Brightness** 5.000 lumens Contrast ratio 3,000,000:1 Native aspect ratio 4:3,16:9,16:10 Aspect ratio - compatible 309 Keystone correction horizontal 30° Keystone correction - vertical Displayable colours (millions) 1073.4 Uniformity 75% Lamp info Light source type Laser LASER life 30,000 hours Optical Throw ratio 1.13:1 ~ 1.47:1 Projection distance (m) 1m - 8m Zoom 1.3 Zoom type Manual

16.90 ~ 21.61

116%

Connections Inputs 2 x HDMI 2.0

Outputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A

Control 1 x RS232, 1 x RJ45

General Noise level (typical) 29dB Noise level (max) 31dB

PC compatibility FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 2D compatibility NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz

SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Yes (DLP 3D; PC frame sequential 120Hz 3D, Blu-r

Security Security bar, Kensington Lock, Password protected interface IP6X

IP rating

OSD / display languages 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi,

Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional),

Turkish, Vietnamese Yes

24/7 operation 360° operation Yes

Operating conditions 0°C ~ 40°C, Max. Humidity 80%, Max. Altitude 2,500m

Card style Remote control Speaker count Watts per speaker 15W In the box AC power cord Remote control

1x CR2025 battery Basic user manual UHDCast Pro

Optional wireless models Power

External power supply, 100V ~ 240V, 50-60Hz Power supply

Power consumption (standby) <0.5W Power consumption (min) 128W 205W Power consumption (max)

Weight and dimensions

274 x 216 x 108 Dimensions (W x D x H) mm Gross weight 4.6 kg 3.4 kg Net weight



