Key **Features**

- True 4K HDR immersive visual experience
- Advanced LED technology with 30,000 hours
 lifes nan
- 2,900 Lumens for bright and clear images in any environment
- Easy Setup: 0.69-0.83 short throw ratio with H/V keystone & 4 corner adjustment
- Designed for Xbox for ultimate gaming
 experience



Product **Description**

Experience gaming like never before with the world's first "Designed for Xbox" projector series. Boasting a 1440p resolution delivered with an ultra-smooth 120Hz refresh rate on a 100+" screen, the ViewSonic X2-4K transforms gaming sessions into a larger-than-life experience. The projector combines crisp visuals rendered in 4K HDR with cinematic audio produced by Harman Kardon speakers to deliver a truly enthralling audiovisual experience. Immerse yourself in brilliant image quality powered by advanced 3rd generation LED technology that offers a 60,000-hour lifespan without the need for lamp replacement, a high brightness of 2,900 Lumens, and vibrant colours covering 125% Rec.709. The ViewSonic X2-4K has a 0.69-0.83 short throw ratio, allowing for a 100" display from just 1.5 meters away, and its H/V keystone and 4 corner adjustment features make creating the ultimate gaming hub a breeze. Screen mirroring via Wi-Fi also enables seamless content streaming, while Bluetooth connectivity provides additional audio options, offering an intuitive and cinematic audiovisual experience.

Visit Us

www.viewsonic.com



SPECIFICATION	
Native Resolution:	3840x2160
Brightness:	2900 (Lumens)
Contrast Ratio:	3000000:1
Display Color:	1.07 Billion Colors
Light Source Type:	LED
Light Source Life (hours) with Normal Mode:	60000
Lens:	F=2.53-2.73, f=10.20-12.25mm
Projection Offset:	105%+/-5%
Throw Ratio:	0.69-0.83
Optical Zoom:	1.2X
Digital Zoom:	0.8x-2.0x
Image Size:	60"-120"
Throw Distance:	0.92m-2.2m (100"@1.53m)
Keystone:	H:+/-40° , V:+/-40°
Audible Noise (Normal):	33dB
Audible Noise (Eco):	29dB
Local Storage:	Total 16GB (12GB available storage)
Input Lag:	4.2ms
Resolution Support:	VGA(640 x 480) to 4K(3840 x 2160)
HDTV Compatibility:	480i, 480p, 576i, 576p, 720p, 1080i, 1080p, 2160p
Horizontal Frequency:	15K-135KHz
Vertical Scan Rate:	23-240Hz
INPUT	
HDMI:	2
USB Type C:	(HDMI 2.0, HDCP 1.4/2.2) 1 (5V/1A)
Audio-in (Bluetooth):	1 (BT4.2)
	1
USB Type A:	(USB2.0 Reader)
Wifi Input:	1 (5Gn)
OUTPUT Audio-out (3.5mm):	1
Audio-out (Bluetooth):	1 (BT4.2)
	6W Cube x2
Speaker:	(Full range x2)
USB Type A (Power):	(USB2.0 - 5V/1A x1,
	(USB2.0 - 5V/1A x1, share with USB A Input)
CONTROL	
	share with USB A Input)
CONTROL RS232 (DB 9-pin male):	share with USB A Input)
CONTROL RS232 (DB 9-pin male): USB Type A (Services):	share with USB A Input) 1 1 100-240V+/- 10%, 50/60Hz
CONTROL RS232 (DB 9-pin male): USB Type A (Services): OTHERS Power Supply Voltage:	1 1 100-240V+/- 10%, 50/60Hz (AC in)
CONTROL RS232 (DB 9-pin male): USB Type A (Services): OTHERS Power Supply Voltage: Power Consumption:	share with USB A Input) 1 1 100-240V+/- 10%, 50/60Hz
CONTROL RS232 (DB 9-pin male): USB Type A (Services): OTHERS Power Supply Voltage: Power Consumption: Operating Temperature:	1 1 100-240V+/- 10%, 50/60Hz (AC in) Normal: 236W Standby: <0.5W 0~40°C
CONTROL RS232 (DB 9-pin male): USB Type A (Services): OTHERS Power Supply Voltage: Power Consumption: Operating Temperature: Carton:	1 1 100-240V+/- 10%, 50/60Hz (AC in) Normal: 236W Standby: <0.5W 0~40°C Color
CONTROL RS232 (DB 9-pin male): USB Type A (Services): OTHERS Power Supply Voltage: Power Consumption: Operating Temperature: Carton: Net Weight:	1 1 100-240V+/- 10%, 50/60Hz (AC in) Normal: 236W Standby: <0.5W 0~40°C Color 3.6kg
CONTROL RS232 (DB 9-pin male): USB Type A (Services): OTHERS Power Supply Voltage: Power Consumption: Operating Temperature: Carton: Net Weight: Gross Weight:	1 1 1 100-240V+/- 10%, 50/60Hz (AC in) Normal: 236W Standby: <0.5W 0~40°C Color 3.6kg 5.5kg
CONTROL RS232 (DB 9-pin male): USB Type A (Services): OTHERS Power Supply Voltage: Power Consumption: Operating Temperature: Carton: Net Weight:	1 1 100-240V+/- 10%, 50/60Hz (AC in) Normal: 236W Standby: <0.5W 0~40°C Color 3.6kg
CONTROL RS232 (DB 9-pin male): USB Type A (Services): OTHERS Power Supply Voltage: Power Consumption: Operating Temperature: Carton: Net Weight: Gross Weight: Dimensions (WxDxH) with	1 1 1 100-240V+/- 10%, 50/60Hz (AC in) Normal: 236W Standby: <0.5W 0~40°C Color 3.6kg 5.5kg
CONTROL RS232 (DB 9-pin male): USB Type A (Services): OTHERS Power Supply Voltage: Power Consumption: Operating Temperature: Carton: Net Weight: Gross Weight: Dimensions (WxDxH) with Adjustment Foot:	\$\text{share with USB A Input}\$ 1 1 100-240V+/- 10%, 50/60Hz (AC in) Normal: 236W Standby: <0.5W 0~40°C Color 3.6kg 5.5kg 355x251x121mm 490x376x313mm English, French, Spanish, Thai,
CONTROL RS232 (DB 9-pin male): USB Type A (Services): OTHERS Power Supply Voltage: Power Consumption: Operating Temperature: Carton: Net Weight: Gross Weight: Dimensions (WxDxH) with Adjustment Foot: Packing Dimensions:	1 1 100-240V+/- 10%, 50/60Hz (AC in) Normal: 236W Standby: <0.5W 0~40°C Color 3.6kg 5.5kg 355x251x121mm 490x376x313mm English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-
CONTROL RS232 (DB 9-pin male): USB Type A (Services): OTHERS Power Supply Voltage: Power Consumption: Operating Temperature: Carton: Net Weight: Gross Weight: Dimensions (WxDxH) with Adjustment Foot:	share with USB A Input) 1 1 100-240V+/- 10%, 50/60Hz (AC in) Normal: 236W Standby: <0.5W 0~40°C Color 3.6kg 5.5kg 355x251x121mm 490x376x313mm English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish,
CONTROL RS232 (DB 9-pin male): USB Type A (Services): OTHERS Power Supply Voltage: Power Consumption: Operating Temperature: Carton: Net Weight: Gross Weight: Dimensions (WxDxH) with Adjustment Foot: Packing Dimensions:	share with USB A Input) 1 1 100-240V+/- 10%, 50/60Hz (AC in) Normal: 236W Standby: <0.5W 0~40°C Color 3.6kg 5.5kg 355x251x121mm 490x376x313mm English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, India, Arabic, Vietnamese, Greek, Hungarian Total
CONTROL RS232 (DB 9-pin male): USB Type A (Services): OTHERS Power Supply Voltage: Power Consumption: Operating Temperature: Carton: Net Weight: Gross Weight: Dimensions (WxDxH) with Adjustment Foot: Packing Dimensions:	share with USB A Input) 1 1 100-240V+/- 10%, 50/60Hz (AC in) Normal: 236W Standby: <0.5W 0~40°C Color 3.6kg 5.5kg 355x251x121mm 490x376x313mm English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, India, Arabic, Vietnamese, Greek, Hungarian Total 24 languages English, S-Chinese, T-Chinese,
CONTROL RS232 (DB 9-pin male): USB Type A (Services): OTHERS Power Supply Voltage: Power Consumption: Operating Temperature: Carton: Net Weight: Gross Weight: Dimensions (WxDxH) with Adjustment Foot: Packing Dimensions: OSD Language:	share with USB A Input) 1 1 100-240V+/- 10%, 50/60Hz (AC in) Normal: 236W Standby: <0.5W 0~40°C Color 3.6kg 5.5kg 355x251x121mm 490x376x313mm English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, India, Arabic, Vietnamese, Greek, Hungarian Total 24 languages English, S-Chinese, T-Chinese, Indonesian, Finish, French, German, Italian, Japanese, Korean, Polish, Italian, Japanese, Korean, Polish
CONTROL RS232 (DB 9-pin male): USB Type A (Services): OTHERS Power Supply Voltage: Power Consumption: Operating Temperature: Carton: Net Weight: Gross Weight: Dimensions (WxDxH) with Adjustment Foot: Packing Dimensions:	share with USB A Input) 1 1 100-240V+/- 10%, 50/60Hz (AC in) Normal: 236W Standby: <0.5W 0~40°C Color 3.6kg 5.5kg 355x251x121mm 490x376x313mm English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, India, Arabic, Vietnamese, Greek, Hungarian Total 24 languages English, S-Chinese, T-Chinese, Indonesian, Finish, French, German, Italian, Japanese, Korean, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Arabic, Czech,
CONTROL RS232 (DB 9-pin male): USB Type A (Services): OTHERS Power Supply Voltage: Power Consumption: Operating Temperature: Carton: Net Weight: Gross Weight: Dimensions (WxDxH) with Adjustment Foot: Packing Dimensions: OSD Language: User Guide Language:	share with USB A Input) 1 1 100-240V+/- 10%, 50/60Hz (AC in) Normal: 236W Standby: <0.5W 0-40°C Color 3.6kg 5.5kg 355x251x121mm 490x376x313mm English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, India, Arabic, Vietnamese, Greek, Hungarian Total 24 languages English, S-Chinese, T-Chinese, Indonesian, Finish, French, German, Italian, Japanese, Korean, Polish, Portuguese, Russian, Spanish,
CONTROL RS232 (DB 9-pin male): USB Type A (Services): OTHERS Power Supply Voltage: Power Consumption: Operating Temperature: Carton: Net Weight: Gross Weight: Dimensions (WxDxH) with Adjustment Foot: Packing Dimensions: OSD Language: User Guide Language:	share with USB A Input) 1 1 100-240V+/- 10%, 50/60Hz (AC in) Normal: 236W Standby: <0.5W 0~40°C Color 3.6kg 5.5kg 355x251x121mm 490x376x313mm English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, India, Arabic, Vietnamese, Greek, Hungarian Total 24 languages English, S-Chinese, T-Chinese, Indonesian, Finish, French, German, Italian, Japanese, Korean, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Arabic, Czech, Thai, Vietnamese, total 20 languages
CONTROL RS232 (DB 9-pin male): USB Type A (Services): OTHERS Power Supply Voltage: Power Consumption: Operating Temperature: Carton: Net Weight: Gross Weight: Dimensions (WxDxH) with Adjustment Foot: Packing Dimensions: OSD Language: User Guide Language: STANDARD ACCESSORY Power Cord:	share with USB A Input) 1 1 100-240V+/- 10%, 50/60Hz (AC in) Normal: 236W Standby: <0.5W 0~40°C Color 3.6kg 5.5kg 355x251x121mm 490x376x313mm English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Ozech, T-Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, India, Arabic, Vietnamese, Greek, Hungarian Total 24 languages English, S-Chinese, T-Chinese, Indonesian, Finish, French, German, Italian, Japanese, Korean, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Arabic, Czech, Thai, Vietnamese, total 20 languages
CONTROL RS232 (DB 9-pin male): USB Type A (Services): OTHERS Power Supply Voltage: Power Consumption: Operating Temperature: Carton: Net Weight: Gross Weight: Dimensions (WxDxH) with Adjustment Foot: Packing Dimensions: OSD Language: User Guide Language: STANDARD ACCESSORY Power Cord: USB-C Cable:	share with USB A Input) 1 1 100-240V+/- 10%, 50/60Hz (AC in) Normal: 236W Standby: <0.5W 0~40°C Color 3.6kg 5.5kg 355x251x121mm 490x376x313mm English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, India, Arabic, Vietnamese, Greek, Hungarian Total 24 languages English, S-Chinese, T-Chinese, Indonesian, Finish, French, German, Italian, Japanese, Korean, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Arabic, Czech, Thai, Vietnamese, total 20 languages
CONTROL RS232 (DB 9-pin male): USB Type A (Services): OTHERS Power Supply Voltage: Power Consumption: Operating Temperature: Carton: Net Weight: Gross Weight: Dimensions (WxDxH) with Adjustment Foot: Packing Dimensions: OSD Language: User Guide Language: STANDARD ACCESSORY Power Cord: USB-C Cable: Remote Control:	share with USB A Input) 1 1 1 100-240V+/- 10%, 50/60Hz (AC in) Normal: 236W Standby: <0.5W 0~40°C Color 3.6kg 5.5kg 355x251x121mm 490x376x313mm English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, India, Arabic, Vietnamese, Greek, Hungarian Total 24 languages English, S-Chinese, T-Chinese, Indonesian, Finish, French, German, Italian, Japanese, Korean, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Arabic, Czech, Thai, Vietnamese, total 20 languages 1 1 (1m) 1 (BT w/ backlit)
CONTROL RS232 (DB 9-pin male): USB Type A (Services): OTHERS Power Supply Voltage: Power Consumption: Operating Temperature: Carton: Net Weight: Gross Weight: Dimensions (WxDxH) with Adjustment Foot: Packing Dimensions: OSD Language: User Guide Language: STANDARD ACCESSORY Power Cord: USB-C Cable: Remote Control: OSG:	share with USB A Input) 1 1 1 100-240V+/- 10%, 50/60Hz (AC in) Normal: 236W Standby: <0.5W 0~40°C Color 3.6kg 5.5kg 355x251x121mm 490x376x313mm English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, India, Arabic, Vietnamese, Greek, Hungarian Total 24 languages English, S-Chinese, T-Chinese, Indonesian, Finish, French, German, Italian, Japanese, Korean, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Arabic, Czech, Thai, Vietnamese, total 20 languages 1 1 (1m) 1 (BT w/ backlit)
CONTROL RS232 (DB 9-pin male): USB Type A (Services): OTHERS Power Supply Voltage: Power Consumption: Operating Temperature: Carton: Net Weight: Gross Weight: Dimensions (WxDxH) with Adjustment Foot: Packing Dimensions: OSD Language: User Guide Language: STANDARD ACCESSORY Power Cord: USB-C Cable: Remote Control: OSG: Warranty Card:	share with USB A Input) 1 1 1 100-240V+/- 10%, 50/60Hz (AC in) Normal: 236W Standby: <0.5W 0~40°C Color 3.6kg 5.5kg 355x251x121mm 490x376x313mm English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, India, Arabic, Vietnamese, Greek, Hungarian Total 24 languages English, S-Chinese, T-Chinese, Indonesian, Finish, French, German, Italian, Japanese, Korean, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Arabic, Czech, Thai, Vietnamese, total 20 languages 1 1 (1m) 1 (BT w/ backlit)
CONTROL RS232 (DB 9-pin male): USB Type A (Services): OTHERS Power Supply Voltage: Power Consumption: Operating Temperature: Carton: Net Weight: Gross Weight: Dimensions (WxDxH) with Adjustment Foot: Packing Dimensions: OSD Language: STANDARD ACCESSORY Power Cord: USB-C Cable: Remote Control: OSG: Warranty Card: OPTIONAL ACCESSORY	share with USB A Input) 1 1 100-240V+/- 10%, 50/60Hz (AC in) Normal: 236W Standby: <0.5W 0-40°C Color 3.6kg 5.5kg 355x251x121mm 490x376x313mm English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, India, Arabic, Vietnamese, Greek, Hungarian Total 24 languages Indonesian, Finish, French, German, Italian, Japanese, Korean, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Arabic, Czech, Thai, Vietnamese, total 20 languages 1 1 (1m) 1 (BT w/ backlit) Yes Yes (CN Only)
CONTROL RS232 (DB 9-pin male): USB Type A (Services): OTHERS Power Supply Voltage: Power Consumption: Operating Temperature: Carton: Net Weight: Gross Weight: Dimensions (WxDxH) with Adjustment Foot: Packing Dimensions: OSD Language: User Guide Language: STANDARD ACCESSORY Power Cord: USB-C Cable: Remote Control: OSG: Warranty Card:	share with USB A Input) 1 1 1 100-240V+/- 10%, 50/60Hz (AC in) Normal: 236W Standby: <0.5W 0~40°C Color 3.6kg 5.5kg 355x251x121mm 490x376x313mm English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, India, Arabic, Vietnamese, Greek, Hungarian Total 24 languages English, S-Chinese, T-Chinese, Indonesian, Finish, French, German, Italian, Japanese, Korean, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Arabic, Czech, Thai, Vietnamese, total 20 languages 1 1 (1m) 1 (BT w/ backlit)