## **Key Features**

- 4K HDR professional-quality visuals
- 6,000 ANSI Lumens offering bright images in any environment
- Up to a 300" ultra-large screen with a lower cost-per-inch
- Supports a 21:9 aspect ratio, ideal for Microsoft Teams Rooms
- Installation flexibility: H/V lens shift, 1.6x optical zoom, and H/V keystone correction



## Product **Description**

The LSC601-4K is a lamp-free, high-brightness projector designed for commercial, educational, and public spaces. Equipped with 4K resolution and HDR/HLG support, it delivers professional-quality presentations and stunning visuals. Utilising 2nd generation laser phosphor technology, this projector offers 6,000 ANSI Lumens of brightness for up to 30,000 hours and can project an ultra-large screen up to 300". Ideal for modern workplaces, its 21:9 aspect ratio is optimised for Microsoft Teams Rooms applications, enhancing collaborative environments. Equipped with features like H/V lens shift, 1.6x optical zoom, H/V keystone correction, and 360° projection capabilities, the LSC601-4K offers flexible setup possibilities. Additionally, its comprehensive LAN control ensures seamless integration into existing device management networks.

- 1. Zoom Ring
- 2. Focus Ring
- 3. Front IR
- 4. S/PDIF
- 5. USB-A (5V/2A)
- 6. HDMI 2.0/HDCP 2.2
- 7. USB-A (5V/2A)
- 8. RS232
- 9. Audio Out
- 10. Rear IR
- 11. RI45 12. HDBaseT
- 13. AC In
- 14. LED Indicator
- 15. Keypad
- 16. Lens Shift Control Knob x2
- 17. Power Button

Visit Us

www.viewsonic.com



SPECIFICATION		OTHERS
Native Resolution:	WUXGA with 4K Enhancement	Power Supply Voltag
Brightness:	6000 (ANSI Lumens)	. one: eapp.y ronag
Brightness (Center Lumens):	6500	Power Consumption:
Contrast Ratio:	500:1	Operating Temperatu
Display Color:	1.07 Billion Colors	Carton:
Light Source Type:	Laser Phosphor	Net Weight:
Light Source Life (hours) with Normal Mode:	20000	Gross Weight:
Light Source Life (hours) with SuperEco Mode:	30000 (Eco)	Dimensions (WxDxH Adjustment Foot:
Lens:	F=1.5-2.08, f=17.2-27.7mm	Packing Dimensions:
Projection Offset:	0%+/-5%	OSD Language:
Throw Ratio:	1.2-2.01	
Optical Zoom:	1.6X	
Digital Zoom:	1.0x-2.0x	
Image Size:	30"-300"	
Throw Distance:	0.80-13.35m (100"@2.66m)	User Guide Languag
Keystone:	H:+/-25° , V:+/-30°	
Lens Shift V. Range:	+66%, 0%	
Lens Shift H. Range:	+29%, -29%	STANDARD ACCES
Audible Noise (Normal):	37dB	Power Cord:
Audible Noise (Eco):	26dB	Remote Control:
Input Lag:	32ms	QSG:
Resolution Support:	VGA(640 x 480) to 4K(3840 x 2160)	Air Filter:
HDTV Compatibility:	480i, 480p, 576i, 576p, 720p, 1080i, 1080p, 2160p	Warranty Card: OPTIONAL ACCESS
Horizontal Frequency:	15K-135KHz	Air Filter:
Vertical Scan Rate:	24-85Hz	Wall/Ceiling Mount:
NPUT		wall/Celling Mount.
HDMI:	2 (HDMI 2.0, HDCP 1.4/2.2)	
Audio-in (3.5mm):	1	
USB Type A:	2 (5V/2A)	
HDBaseT:	1	
RJ45 Input (Internet):	Yes	
OUTPUT		
Audio-out (3.5mm):	1	
Audio-out (HDMI ARC):	1 (Share with HDMI Input)	
S/PDIF:	1	
Speaker:	16W	
USB Type A (Power):	2 (USB2.0 - 5V/2A, share with USB A Input)	
CONTROL	. ,	
RS232 (DB 9-pin male):	1	
RJ45 (LAN control):	1 (share with RJ45 Internet)	
USB Type A (Services):	1 (share with USB A Output)	

**THERS** 100-240V+/- 10%, 50/60Hz ower Supply Voltage: (AC in) Normal: 325W ower Consumption: Standby: <0.5W 0~40°C perating Temperature: arton: Brown let Weight: 7.9kg aross Weight: 10.93kg imensions (WxDxH) with 405x358x137mm djustment Foot: acking Dimensions: 510x498x260mm

Hungarian, Czech, Vietnamese, Thai, total 23 languages English, S-Chinese, T-Chinese, Indonesian, Finish, French, German, Italian, Japanese, Korean, Polish, lser Guide Language: Portuguese, Russian, Spanish, Swedish, Turkish, Arabic, Czech, Thai, Vietnamese, total 20 languages

English, German, French, Italian, Spanish, Polish, Swedish, Dutch Portugese, Japanese, Simplified Chinese, Traditional Chinese,

Korean, Russian, Turkish, Finnish, Norwegian, Danish, Indonesian,

## **FANDARD ACCESSORY**

ower Cord: 1 Remote Control: 1 QSG: Yes ir Filter: Yes Varranty Card: Yes (CN Only)

## PTIONAL ACCESSORY

ir Filter: Yes PJ-WMK-007