Key Features

- 7,100 ANSI Lumens with a high native contrast ratio ensure vibrant images in large venues
- True 4K HDR delivers exceptional image clarity and detail
- Supports 21:9 aspect ratio, ideal for Microsoft Teams Rooms
- Installation flexibility: motorized focus, 1.6x optical zoom, lens shift , H/V keystone correction, and 360° projection
- Centralized LAN control for efficient management



Product **Description**

Introducing the LS950-4K from ViewSonic's Luminous Superior Series, tailored for expansive venue displays. Featuring a robust 7,100 ANSI Lumens brightness and high native contrast through DLP technology, it delivers stunning 4K UHD visuals on screens exceeding 100 inches. Perfect for museums and educational institutions, the LS950-4K's ultra-high resolution with HDR/HLG support ensures every detail is vivid and clear, enhancing viewer engagement. With 21:9 aspect ratio support, the LS950-4K is also an ideal choice for Microsoft Teams Rooms. Its 1.6x optical zoom allows for a flexible setup to suit various installation needs, and the motorized focus, lens shift, and H/V keystone adjustment make the process a breeze. Additionally, portrait mode and 360° projection capabilities cater to more advanced requirements. Comprehensive LAN control ensures seamless integration into corporate networks. Employing advanced 3rd generation laser phosphor technology, the LS950-4K boasts a remarkable 30,000-hour lifespan, reducing maintenance costs for both business and educational institutions.

Visit Us

www.viewsonic.com



SPECIFICATION		OTHERS
Native Resolution:	3840x2160	Power Supply Voltage:
Brightness:	7100 (ANSI Lumens)	
Brightness (Center Lumens):	7300	Power Consumption:
Contrast Ratio:	3000000:1	Operating Temperature:
Display Color:	1.07 Billion Colors	Carton:
Light Source Type:	Laser Phosphor	Net Weight:
Light Source Life (hours) with Normal Mode:	20000	Gross Weight: Dimensions (WxDxH) with
Light Source Life (hours) with SuperEco Mode:	30000	Adjustment Foot: Packing Dimensions:
Lens:	F=2.0-2.1, f=18.72-29.59mm	OSD Language:
Projection Offset:	0%±10%	
Throw Ratio:	1.25-2.00	
Optical Zoom:	1.6X	
Digital Zoom:	0.8x-1.8x	
Image Size:	50"- 300"	
Throw Distance:	1.36-13.42m (100"@2.78m)	User Guide Language:
Keystone:	H:+/-30° , V:+/-30°	
Lens Shift V. Range:	+55%, -55%	
Lens Shift H. Range:	+25%, -25%	STANDARD ACCESSORY
Audible Noise (Normal):	34dB	Power Cord:
Audible Noise (Eco):	32dB	Remote Control:
Input Lag:	16ms	000
Resolution Support:	VGA(640 x 480) to 4K(3840 x 2160)	QSG:
HDTV Compatibility:	576i, 576p, 720p, 1080i, 1080p, 2160p	Warranty Card:
Horizontal Frequency:	15K- 135KHz	
Vertical Scan Rate:	23- 240Hz	
NPUT		
HDMI:	2 (HDMI 2.0/ HDCP 1.4/2.2)	
3D VESA (Sync):	1 (BNC)	
HDBaseT:	1	
IR In:	1	
DUTPUT		
HDMI out:	1	
Audio-out (3.5mm):	1	
Speaker:	10W x2	
USB Type A (Power):	1 (5V/1.5A)	
12V Trigger (3.5mm):	1	
3D SYNC Out:	1	
CONTROL		
RS232 (DB 9-pin male):	1	
RJ45 (LAN control):	1	
USB Type B (Services):	1	

1 (share with IR in)

Wired Remote Control - In:

100-240V+/- 10%, 50/60Hz

(AC in)

5~40°C Brown 14.1kg 18.8kg

Normal: 450W Standby: <0.5W

486X433X186mm

654x563x373mm

languages

(w/ backlit)

Yes (CN Only)

Yes

English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, Hindi, Vietnamese, Greek, Hungarian, Danish, Norwegian. Total 25 languages

English, S-Chinese, T-Chinese, Indonesian, Finish, French, German, Italian, Japanese, Korean, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Arabic, Czech, Thai, Vietnamese, total 20