

VISION Techconnect Faceplate Control Module - LIFETIME WARRANTY(TC3-CTL/2)

8 buttons - learns ir remote control codes from other remotes - supports rs-232, 12v trigger, scheduling - multiple commands per button - double-space module - 1-gang uk surround and backbox included - white



The Vision Techconnect TC3-CTL/2 control module is designed by Vision Audio Visual. This product stands out with its 8 backlit buttons, simplifying control in any lighting condition. It's built for versatility, featuring both serial (RS-232) and infrared interfaces, allowing for seamless integration with various devices. Compliance with standards such as C-Tick, EMC, ISO 9001:2015, RoHS, UKCA, and WEEE, assures users of its quality and environmental responsibility. Furthermore, its power system is adaptable to global standards, accepting AC 100-240 V, making it an ideal choice for international applications. Whether for professional or personal use, the TC3-CTL/2 offers reliability and efficiency in managing your technological environment.

Key Selling Points

- 8 backlit buttons for easy control
- Dual serial (RS-232) and infrared interfaces for versatile device connectivity
- Compliant with multiple standards including C-Tick and ISO 9001:2015
- Supports a wide voltage range (AC 100-240 V) for global use

Product Features

- Efficient control**
With 8 backlit buttons, the Vision Techconnect TC3-CTL/2 control module offers an intuitive interface for managing integrated systems and automation effortlessly. The backlit feature ensures easy operation in low-light conditions.
- Versatile connectivity**
Equipped with serial (RS-232) and infrared interfaces, this control module provides flexible options for connecting and controlling a wide range of devices, making it a versatile addition to any setup.
- Reliable performance**
Designed to meet various compliance standards including C-Tick, EMC, ISO 9001:2015, RoHS, UKCA, and WEEE, the TC3-CTL/2 ensures reliable performance and adherence to quality and environmental guidelines.
- Adaptable power compatibility**
The control module's power system is designed for global use, accepting AC 100-240 V input and operating efficiently with a nominal voltage of AC 120/230 V, making it suitable for a wide range of power supply standards.

Main Specifications

Product Description	Vision Techconnect TC3-CTL/2 - control module - white
Product Type	Control module
Gangs Qty	1
Power Source	Power adapter
Input Type	8 buttons
Colour	White
Manufacturer Warranty	Limited lifetime warranty
Dimensions (WxDxH)	6.4 cm x 4.2 cm x 4.8 cm

Extended Specification

General

Product Type	Control module
Gangs Qty	1
Power Source	Power adapter
Interfaces Details	2 x serial (RS-232) 2 x infrared
Features	Schedule function, backlit buttons

Miscellaneous

Included Accessories	IR Blaster with cable (20 m), IR Blaster with cable (0.15 m), serial cable, 48 buttons, power plug adapter (EU), power plug adapter (UK), power plug adapter (AU)
Product Material	Plastic
Colour	White
Voltage Required	AC 100-240 V
Rated Current	0.5 A
Warranty	Limited lifetime warranty
Compliant Standards	ISO 9001:2015, RoHS, WEEE, EMC, C-Tick, UKCA

Dimensions & Weight

Width	6.4 cm
Depth	4.2 cm
Height	4.8 cm
Weight	63 g
Dimensions & Weight Details	Surround: 8.6 cm x 0.8 cm x 8.6 cm Back box: 8.6 cm x 4.5 cm x 8.6 cm Transformer: 6.6 cm x 4.3 cm x 3 cm

Dimensions & Weight (Shipping)

Shipping Width	18 cm
Shipping Depth	15 cm
Shipping Height	6.3 cm
Shipping Weight	500 g

Control Unit

Buttons Qty	8
-------------	---

Product data is provided by CNET, we do not warrant the accuracy and completeness of the material contained in this data sheet