

Key Features

- 3rd generation laser phosphor technology with up to a 20,000-hour lifespan
- Immersive true 4K HDR offering up to 300" screen
- Vibrant and clear visuals with 4,000 ANSI Lumens of brightness
- Powerful 10W cube speaker for immersive sound
- Installation flexibility: 1.3x optical zoom, H/V keystone, 4 corners adjustment



Product **Description**

Transform your home into a cinematic experience with the LX750-4K smart laser projector. Equipped with 3rd-generationlaser phosphor technology, it delivers 4,000 ANSI Lumens of brightness and up to 20,000 hours of lamp-free use, ensuring vivid visuals day or night. Enjoy immersive 4K HDR picture quality on screens up to 300 inches, paired with a built-in 10W cube speaker for rich, room-filling sound. With features like 1.3x optical zoom, H/V keystonecorrection, and four-corner adjustment, setup is simple and flexible. Plus, with Google TV and a native Netflix app, the LX750-4K brings effortless streaming and premium entertainment into any room.





- 1. Zoom/Focus Ring
- 2. Keypad
- 3. Adjustment Foot
- 4. Lens
- 5. Front IR
- 6. Audio Out 7. RS-232

- 8. USB-A (5V/1.5A)
- 9. HDMI 2.0 / HDCP 2.2 (ARC)
- 10. HDMI 2.0 / HDCP 2.2

Visit Us

www.viewsonic.com

PECIFICATION		OTHERS
Projection System:	0.47" 4K-UHD	Power Supp
Native Resolution:	3840x2160	
Brightness:	4000 (ANSI Lumens)	Power Cons
Contrast Ratio:	1200:1	Operating To
Display Color:	1.07 Billion Colors	Carton:
Light Source Type:	Laser Phosphor	Net Weight:
Light Source Life (hours) with Normal Mode:	20000	Gross Weigl
Lens:	F=1.94~2.12,f=11.9-15.5mm	Dimensions Adjustment
Projection Offset:	110%+/-6%	Packing Dim
Throw Ratio:	1.127~1.465	OSD Langua
Optical Zoom:	1.3X	
Image Size:	60"-300"	
Throw Distance:	1.49-9.72m (150"@3.74m)	
Keystone:	H:+/-40° , V:+/-40°	
Audible Noise (Normal):	33dB (TBD)	User Guide
Audible Noise (Eco):	27dB (TBD)	
Local Storage:	Total 8GB (4GB available storage)	STANDARD
Input Lag:	1ms	Power Cord
Resolution Support:	VGA(640 x 480) to 4K(3840 x 2160)	Remote Cor
HDTV Compatibility:	480i, 480p, 576i, 576p, 720p, 1080i, 1080p, 2160p	QSG:
Horizontal Frequency:	15K-135KHz	OPTIONAL
Vertical Scan Rate:	23-240Hz	Wall/Ceiling
NPUT		Carry Bag:
HDMI:	2 (HDMI 2.0, HDCP 2.2)	
Wifi Input:	1 (5Gn)	
OUTPUT		
Audio-out (3.5mm):	1	

1 (BT5.0)

10W Cube

1(5V/1.5A)

1 (share with HDMI Input)

(share with USB A Output)

Audio-out (Bluetooth):

Audio-out (HDMI ARC):

USB Type A (Power):

RS232 (DB 9-pin male):

USB Type A (Services):

Speaker:

CONTROL

OTHERS	
Power Supply Voltage:	100-240V+/- 10%, 50/60Hz (AC in)
Power Consumption:	Normal: TBD Standby: <0.5W
Operating Temperature:	0~40°C
Carton:	Brown
Net Weight:	3.5kg
Gross Weight:	4.6kg
Dimensions (WxDxH) with Adjustment Foot:	312x234x104mm
Packing Dimensions:	415x168x297mm
OSD Language:	English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T- Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, Hindi, Arabic, Vietnamese, Greek, Hungarian Total 24 languages
User Guide Language:	English, S-Chinese, T-Chinese, Indonesian, Finish, French, German, Italian, Japanese, Korean, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Arabic, Czech, Thai, Vietnamese, total 20 languages
STANDARD ACCESSORY	
Power Cord:	1
Remote Control:	1 (BT w/ backlit)
QSG:	Yes
OPTIONAL ACCESSORY	
Wall/Ceiling Mount:	PJ-WMK-007

PJ-CASE-008