

FEATURES

- 71-1/2" x 36-3/16" x 24-1/16"
- Luxuriously deep bathing well
- Cast-acrylic construction provides high durability
- Slip-resistant surface
- 1hp ultra-quiet blower
- 300 watt heated air injection system
- Final purge/drying cycle to clean each air jet
- Drain with various finishes
- LED lighting
- Multi-functional Remote
 - Normal Mode: Fully adjustable massage level for just the right amount of comfort
 - Pulsating Mode: Powerful, penetrating massage
 - Oscillation Mode: Wave-like, soothing massage
- 2 Pillows

MODELS

- ABA626T
Acrylic bathtub. Slip-resistant surface.
Remote Control with light.
Left Blower
- ABA626S
Acrylic bathtub. Slip-resistant surface.
Remote Control with light.
Right Blower

COLORS/FINISHES

- Shell Color
 - #01 Cotton
 - #12 Sedona Beige
- Drain
 - #CP Polished Chrome
 - #BN Brushed Nickel
 - #PN Polished Nickel
- Jet Trim
 - Color matched caps
- Pillows
 - Neutral White

CODES/STANDARDS

- Meets and exceeds ASME A112.19.7M, CSA B45.10, UL 1795, CSA C22.2 #218.2
- Certifications: IAPMO(cUSPC), Intertek/ETL, State of Massachusetts, City of Los Angeles and others
- Code Compliance: USPC, IPC, NSPC, NPC Canada, and others



PRODUCT SPECIFICATION

The TOTO® Aimes® Airbath™ shall have a luxuriously deep bathing well. The Airbath shall have a cast-acrylic construction that provides high durability with a slip-resistant surface. The Airbath shall have a 1hp ultra-quiet blower, a 300 watt heated air injection system and a final purge/drying cycle to clean each air jet. The Airbath shall have a drain with various finishes, LED lighting and a multi-functional remote. Airbath shall be TOTO Model ABA626____.

SPECIFICATIONS

- Size 71-1/2" L x 36-3/16" W x 24-1/16" H
- Depth 19"
- Warranty 1 Year Limited Warranty on acrylic tub
1 Year Limited Warranty on components and parts
- Material Cast Acrylic construction
- Electrical Requirements 15 AMP; 120V w/ GFCI
- Shipping Weight 199 lbs.
- Shipping Dimensions 74-1/2" L x 45" W x 27-1/2" H
- Gallons 88 to overflow

INSTALLATION NOTES

Floor support under bath must provide a minimum of 75 lbs/square foot (366 kg/square meter) loading.

