

BC 04

inch 62x30x24 mm 1575x762x610

■ interior dimensions

rim: inch 58x26 mm 1473x660 base: inch 48x25 mm 1219x635 height: inch 20 mm 508

■ capacity to overflow gal (us) - 82 liters - 310

■ weight
lb - 255 kg - 116

■ installation

freestanding, 1 wall, 2 walls or 3 walls

■ accessory

oak bridge wenge shade


■ material


WETMAR BiO™, True High Gloss™ or matte finish

■ color white

■ codes/standards applicable IAPMO-ANSI Z124.1 IAPMO-ANSI Z124.3 CSA B 45.0 - CSA B45.4







front view




WETSTYLE Plug & Bathe™ overflow and drain connection system includes:

Soft-touch pop-up drain, for built-in overflow. Fits both 1-1/2" ABS drain waste and 1-1/2" tubular brass

1-1/2" ABS Direct vertical drain waste fitting (copper/brass option also available)

1-1/2" ABS 90° Elbow drain waste fitting (copper/brass option also available)



WETSTYLE cannot be held responsible for any technical errors and reserves the right to make revisions without notice.

Approximate measurement.

The manufacturer accept ¼" (6.35mm) variance.





inch 62x30x24 mm 1575x762x610

■ overflow and drain connection WETSTYLE Plug & Bathe™ system (ABS or copper/brass)

■ overflow

built-in slot design polished chrome or brushed nickel


■ drain

soft toe touch polished chrome or brushed nickel

■ faucet area recommended wall-mounted or floor-mounted

■ option

columns for wall or deck-mounted faucets (refer to the Column collection)



Bathtub installation supplies

A tile flange will be supplied to comply with the requested position. Installed at the factory to prevent water leakage, this must be placed directly on the partition framing prior to the installation of drywall.

Plumbing installation restriction

BC 0401, freestanding bathtub requires a vertical plumbing connection rising from the floor.

A horizontal connection is not an option.

WETSTYLE cannot be held responsible for any technical errors and reserves the right to make revisions without notice.

Approximate measurement. The manufacturer accept $\mbox{14}$ " (6.35mm) variance.

