

CHESTERFIELD

Features

Bridge Style Kitchen Faucet with Sidespray

- · Solid brass construction
- · Bridge-style brass valve bodies
- · Quarter-turn washerless ceramic disc valve cartridges
- ADA compliant traditional lever handles
- Swivel spout assembly with integral diverter assembly
- Solid brass pull-out sidespray assembly
- 6-9/16" (16.7 cm) spout height at outlet
- 8-1/2" (21.6 cm) min. to 10-3/8" (26.4 cm) max. spout reach (c-c)
- For 8" (20.3 cm) centers Maximum 9-3/4" (24.9 cm)
- 1.8 gallons (6.8 liters) per minute maximum flow rate



Meets or exceeds the following at date of manufacture:


- ASME A112.18.1/CSA B125.1
- IAPMO/cUPC
- TPC
- NSF 61
- ADA
- ICC/ANSI A117.1
- Energy Policy Act of 1992
- All applicable US Federal and State material regulations





9453-1







Colors / Finishes

• 10B: Oil Rubbed Bronze 15: Polished Nickel • 15S: Satin Nickel 26: Polished Chrome

• Other: Refer to the Newport Brass catalog for additional color/finish options.

Specified Model Colors / Finishes Model **Description** 9453-1 Bridge Style Kitchen Faucet with Sidespray □ 10B □ 15 □ 15S □ 26 Other

Product Specification:

Add "Color / Finish" suffix to Model number, below.

The Bridge Style Kitchen Faucet with Sidespray shall be made of solid brass construction. Faucet shall incorporate a swivel spout assembly with integral side-spray diverter assembly and feature bridge-style brass valve bodies with quarter-turn washerless ceramic disc valve cartridges. Faucet shall have a 1.8 gallons (6.8 liters) per minute maximum flow rate. Product shall be for 8" (20.3 cm) centers - Maximum 9-3/4" (24.8 cm). Product shall incorporate a 6-9/16" (16.7 cm) spout height at outlet and an 8-1/2" (21.6 cm) min. to 10-3/8" (26.4 cm) max. spout reach (c-c). Faucet shall incorporate ADA compliant traditional lever handles. Bridge-Style Kitchen Faucet with Sidespray shall be Newport Brass Model 9453-1/_

9453-1

Product Dimensions (units are in inches)

