


Always check the website for the most updated specifications: www.americh.com



All bathtub dimensions are  $\pm 1/2$ ".

# Airbath System II



#### LEGEND:



**BLOWER** 

20



ON/OFF CONTROL



ACCESS PANEL (PROVIDED BY FACTORY)

## **STANDARD EQUIPMENT:**

Integral Waste & Overflow with Polished Chrome trim
 Available with polished brass, polished nickel, satin
 nickel or oil rubbed bronze trim at no additional charge
 if specified at the time of order. Requests after order is
 shipped are subject to a \$75 list charge for trim

· Lift bag is provided

## **INSTALLATION TIPS**

- Install according to Owner's Manual and local codes.
- Access panel for Airbath® systems included with the Contura series.
- Hot water supply should be 65-75% of tub capacity or greater.
- Always consult your local plumber for recommendations as installations will vary.

#### **DIMENSIONS:**

Dia

 $66" \times 32" \times 24"$  ( $1676 \times 813 \times 610$  mm) Gallon to Overflow = 68 (Liters = 257) Factory installed integral drain.

MATERIAL: Acrylic (White and Biscuit Only)

TUB FLOOR: Non-Textured

**Undermount:** No

# **ELECTRICAL REQUIREMENTS**

Americh recommends one 20 amp ground fault circuit interrupter (GFCI) for each power supply provided with the bathtub.

#### **OPTIONAL ACCESSORIES**

- Chromatherapy
- Linear Overflow
- Remote Control Upgrade

# **CODES AND COMPLIANCE**

Americh products meet or exceed the following standards:

- Underwriters Laboratories (UL)
- Underwriters Laboratories Canada (cUL)
- Canadian Standards Association (CSA)
- ANSI Z124.1 ANSI A112-19.7 ANSI A112.19.8

Contact Americh for additional approvals.