

TECHNICAL SPECIFICATIONS

Serenity Series • Fax on Demand #1264


SERENITY 6

59 1/4 x 59 1/4 x 24 (1505 x 1505 x 610)
inches (mm)



Note: Serenity tub only models feature a Pre-leveled ABS Support Base.

Tub-mounted Faucetry
- Suggested locations



FEATURES lbs (kg) Dimensional Tolerance ± 3/8". Dimensions needed for site preparation should be measured from the unit. Aquatic assumes no responsibility for preparatory work.

Type and Model #	Material	System	Powered By	Heater	Controls	Drain	Pkg. Wt.
Soaker #A16AIR606OTO	Acrylic	-	-	-	-	Center Front	206 (93)
HotSoak #A16AIR606OHS	Acrylic	Water circulation	Pump	1.5 kW Inline maintenance	Electronic	Center Front	236 (107)
Air Bath #A16AIR606O	Acrylic	Air channel	Variable speed blower	Integrated	Electronic	Center Front	236 (107)
DriftBath #A16AIR606ODB	Acrylic	Water circulation	Pump	Integrated	Electronic	Center Front	247 (112)

DIMENSIONS inches (mm)

Width Overall / Net	Depth Overall / Net	Height Overall / Net	Skirt Height
59 1/4 (1505)	59 1/4 (1505)	24 (610)	-

SUMP DATA inches (mm)

Capacity to Overflow gal (ltr)	Min. Operating Capacity gal (ltr)	WIDTH @ centerline		DEPTH @ centerline	
		Top	Bottom	Top	Bottom
90 (341)	-	51 (1295)	41 3/4 (1060)	45 (1145)	37 (940)

PLUMBING DIMENSIONS inches (mm)

A	B	Drain Diameter / Clearance
5 1/2 (140)	14 1/4 (360)	

NOTES:

1) Where applicable, utilize cut-out templates packed with unit for deck cutouts.

2) 16 x 16 (405 x 405) minimum access required at pump/blower location(s).

3) For Low Profile Deck, framing height will need to be increased by an additional 1".

ELECTRICAL DATA

Component	Specification	Requirement
Heated Blower (Air Bath)	10.5 AMP; 120V	15 AMP; 120V, separate circuit; Class A GFCI
Pump (HotSoak)	1/15 HP; 1.3 AMP; 120V	20 AMP; 120V, separate circuit; Class A GFCI
Heater (HotSoak)	1.5 kW; 12 AMP; 120V	
Pump (DriftBath)	3/4 HP; 8.8 AMP; 120V	15 AMP; 120V, separate circuit; Class A GFCI

Each Serenity air bath is equipped with an air heating system to raise the temperature of the air entering the bath. This air temperature will be lower than the bathing temperature of the water, but will help reduce rapid decrease in water temperature. In addition, the air coming from the air jets will feel cool against the skin. This system does not heat the water.