



## Always check the website for the most updated specifications: www.americh.com









Tub pictured with optional waste &

All bathtub dimensions are ± 1/2".

## Builder Series

# **Luxury Series**







## Platinum Series


## Combination


(pump and blower location only)






# 







## INSTALLATION TIPS

Install according to Owner's Manual and local codes.

Airbath III units may be 1½" - 2½" higher than stated.

Any whirlpool or Airbath® unit requires an access panel.

Hot water supply should be 65-75% of tub capacity or greater.

Always consult your local plumber for recommendations as

installations will vary.

Cut-out dimension: 82" x 40"

### DIMENSIONS

84" x 42" x 21" (2134 x 1067 x 533 mm) Whirlpool Operating Gallons = 70 (Liters = 265)

Gallon to Overflow = 85 (Liters = 322)

MATERIAL: Acrylic (All Americh Standard Colors)

TUB FLOOR: Textured

UNDERMOUNT: Yes

Advise Americh when ordering to ensure there are no issues

with deck mounted controls.

Always take dimensions directly from the unit.

### ELECTRICAL REQUIREMENTS

Americh recommends one 20 amp ground fault circuit interrupter (GFCI) for each power supply provided with the bathtub.

## OPTIONAL ACCESSORIES

Apron

Chromatherapy\*

Grab Bars: 9" \* - 14" - 16"

High Density Insulation\*

iBath Sound System

Inline Heater (whirlpool only)

Jets: Additional or Rotary\*

Lo Profile Tub Edge

Ozone System (whirlpool and/or Airbath only)

Pillows: 13"

Angle - Full Back

Remote Control Upgrade (select series only)

Serenity Soak (tub only)

Syllent Pump with Heated Air\*

Tile Flange Kit

Trim Kit Upgrade\*

Waste & Overflow

Cable Drive Overflow\*

Linear Overflow

\* Standard on Platinum Series

### CODES AND COMPLIANCE

Americh products meet or exceed the following standards:

Underwriters Laboratories (UL)

Underwriters Laboratories - Canada (cUL)

Canadian Standards Association - (CSA)

ANSI Z124.1 • ANSI A112-19.7

ANSI A112.19.8 • ASTM F462-79

Contact Americh for additional approvals.