



BARRINGTON® 7236

Always check the website for the most updated specifications: www.americh.com









Tub pictured with optional waste & overflow.

All bathtub dimensions are $\pm 1/2$ ".

Builder Series



Luxury Series



DIMENSIONS

72" x 36" x 22" deep (1829 x 914 x 559 mm) Whirlpool Operating Gallons = 55 (Liters = 208) Gallon to Overflow = 90 (Liters = 341)

MATERIAL: Acrylic (All Americh Standard Colors)

TUB FLOOR: Textured

Undermount: Yes

 Advise Americh when ordering to ensure there are no issues with deck mounted controls.


Americh recommends one 20 amp ground fault circuit interrupter


· Always take dimensions directly from the unit.

Platinum Series









(GFCI) for each power supply provided with the bathtub. OPTIONAL ACCESSORIES

ELECTRICAL REQUIREMENTS

- Apron
- Chromatherapy*
- Grab Bars: 9" * 14" 16"
- High Density Insulation*
- iBath Sound System
- Inline Heater (whirlpool only)
- Jets: Additional or Rotary*
- Lo Profile Tub Edge
- Ozone System (whirlpool and/or Airbath only)
- Pillow: 13" *
- Remote Control Upgrade (select series only)
- Serenity Soak (tub only)
- Syllent Pump with Heated Air*
- Tile Flange Kit
- Trim Kit Upgrade*
- Waste & Overflow
 - Cable Drive Overflow*
 - Linear Overflow

INSTALLATION TIPS

- Install according to Owner's Manual and local codes.
- Airbath III units may be 11/2" 21/2" higher than stated.
- Any whirlpool or Airbath® unit requires an access panel.
- $\bullet\,$ Hot water supply should be 65-75% of tub capacity or greater.

ON/OFF CONTROL

- ACCESS PANEL (MINIMUM 16" X 20")

- Always consult your local plumber for recommendations as installations will vary.
- Cut-out dimension: 70" x 34"

*Standard on Platinum Series

CODES AND COMPLIANCE

Americh products meet or exceed the following standards:

- Underwriters Laboratories (UL)
- Underwriters Laboratories Canada (cUL)
- Canadian Standards Association (CSA)
- ANSI Z124.1 ANSI A112-19.7
- ANSI A112.19.8 ASTM F462-79

Contact Americh for additional approvals.