




Always check the website for the most updated specifications: www.americh.com





42 28 - 101/2







All bathtub dimensions are ± 1/2".

DIMENSIONS

Builder Series







MATERIAL: Acrylic (All Americh Standard Colors)

66" x 42" x 22" (1676 x 1067 x 559 mm) Whirlpool Operating Gallons = 55 (Liters = 208) Gallon to Overflow = 75 (Liters = 284)




UNDERMOUNT: Yes


Advise Americh when ordering to ensure there are no issues with deck mounted controls.

Always take dimensions directly from the unit.


Platinum Series

















INSTALLATION TIPS

Install according to Owner's Manual and local codes. Airbath III units may be 11/2" - 21/2" higher than stated. Any whirlpool or Airbath® unit requires an access panel. Hot water supply should be 65-75% of tub capacity or greater. Always consult your local plumber for recommendations as installations will vary. Cut-out dimension: 64" x 40"

ELECTRI CAL REQUIREMENTS

Americh recommends one 20 amp ground fault circuit interrupter (GFCI) for each power supply provided with the bathtub.

OPTIONAL ACCESSORIES

Apron

Chromatherapy*

Grab Bars: 9" * - 14" - 16"

High Density Insulation*

iBath Sound System

Inline Heater (whirlpool only)

Jets: Additional or Rotary*

Lo Profile Tub Edge

Ozone System (whirlpool and/or Airbath only)

Pillows: 13" *

Angle - Full Back

Remote Control Upgrade (select series only)

Serenity Soak (tub only)

Syllent Pump with Heated Air*

Tile Flange Kit

Trim Kit Upgrade*

Waste & Overflow

Cable Drive Overflow*

Linear Overflow

CODES AND COMPLIANCE

Americh products meet or exceed the following standards:

Underwriters Laboratories (UL)

Underwriters Laboratories - Canada (cUL)

Canadian Standards Association - (CSA)

ANSI Z124.1 • ANSI A112-19.7

ANSI A112.19.8 • ASTM F462-79

Contact Americh for additional approvals.

^{*} Standard on Platinum Series