

# U-Box,2210,empty,bk

R451736



The universal distributor box with 2 x 2 width unit (WU) and 1 height unit (HU) can be equipped with a large number of different screens. This creates a modular construction for almost unlimited combinations. All manner of configurations are possible, from simple power boxes for power distribution through data boxes with copper or optical fiber technology to mixed hybrid boxes (consolidation points). Keystone faceplates also make it easy to install multimedia applications.

Ideal for installation in raised floors, dropped ceilings, in cable runs, in riser zones, in distribution cabinets and as a surface-mounted solution on ceilings and walls out of and within reach. From halogen-free plastic for installation of devices up to 16 A/ 400 VAC / 50 Hz.

Empty without equipment.

For correct installation according to the standard, 2 safety screws are included which effectively prevent access without tools.

Optional accessories: Connectors, separating hoods and a terminal strip, among others.

## TECHNICAL DATA

### MATERIAL & COLOR

Material:	PC+ABS,FR(40),Bayblend®,FR3010
Surface:	Sandstrahloptik
Color:	RAL 9005

### DIMENSIONS

Width:	144 mm
Height:	61 mm
Depth:	144 mm
Weight:	210 g

### LEGAL

Conformity:	CE
Approval:	VDE beantragt
Protection:	IP20
Combustability:	UL 94 V-0
Inflammability:	850 °C
Flammability:	960 °C
Halogen Free:	Ja
Recycling Regulations:	RoHS/Weee/Reach
Customs Tariff Number:	8536.50

### ELECTRICAL CHARACTERISTICS

Rated voltage:	400 VAC
Rated current:	16 A

### OPERATING CONDITIONS

Storage Temperature:	min. -15 °C
Operating Temperature:	-5 °C bis +60 °C

### MECHANICAL CHARACTERISTICS

Impact Energy:	5 J
Static Load:	120 kg
Static Load Dome:	200 kg

## TENDER TEXT

---

### **U-Box,2210,empty,bk**

The universal distributor box with 2 x 2 width unit (WU) and 1 height unit (HU) can be equipped with a large number of different screens. This creates a modular construction for almost unlimited combinations. All manner of configurations are possible, from simple power boxes for power distribution through data boxes with copper or optical fiber technology to mixed hybrid boxes (consolidation points). Keystone faceplates also make it easy to install multimedia applications.

Ideal for installation in raised floors, dropped ceilings, in cable runs, in riser zones, in distribution cabinets and as a surface-mounted solution on ceilings and walls out of and within reach. From halogen-free plastic for installation of devices up to 16 A/ 400 VAC / 50 Hz. Empty without equipment.

For correct installation according to the standard, 2 safety screws are included which effectively prevent access without tools.

Optional accessories: Connectors, separating hoods and a terminal strip, among others.

### **Characteristics:**

Material: PC+ABS,FR(40),Bayblend®,FR3010

Surface: Sandstrahloptik

Color: RAL 9005

Width: 144 mm

Height: 61 mm

Depth: 144 mm

Weight: 210 g

Conformity: CE

Approval: VDE beantragt

Protection: IP20

Combustability: UL 94 V-0

Inflammability: 850 °C

Flammability: 960 °C

Halogen Free: Ja

Recycling Regulations: RoHS/WEEE/Reach

Ratedvoltage: 400 VAC

Ratedcurrent: 16 A

Storage Temperature: min. -15 °C

Operating Temperature: -5 °C bis +60 °C

Impact Energy: 5 J

Static Load: 120 kg

Static Load Dome: 200 kg

Article Number: R451736

ENo: 154 763 629

Customs Tariff Number: 8536.50

Manufacturer: Reichle & De-Massari AG