

§

Technical Datasheets



R&M Mounting Plate 45x45 mm

The mounting plate 45x45 mm are designed for screw-less flush installation in cover frames and duct cut outs. They can be mounted to walls or ducts in wall installations, as well as Deskbox and floor box.

Recommended depth for backboxes and floorboxes > 70 mm.

Features:

- 2x1 Port with Smart Holes and 1 Port as well
- Can be installed into plastic or metal duct with horizontal or vertical distribution
- Angle and Flat versions
- Labelling window is available
- Two colour with RAL9010 and RAL9005 (White and Black)
- Material: PC+ ABS



Characteristics		Requirement	Standard
			IEC 60603-7
Mechanical Data			
Press out Force		≥ 100 [N]	IEC 61753 – 11 - 1
Press holding Force		60N	IEC 61753 – 11 - 1
Climatic Data			
		Temperature of operational area	
Cold	Temperature	- 10 °C	IEC 60068 – 2 - 1
Dry heat	Temperature	+ 60 °C	IEC 60068 -2 - 2
		Temperature at storage in dry heat	
Dry heat	Temperature	+ 60 °C	IEC 60068 -2 - 2
Relative Humidity		90% to 96% non- condensing	IEC 60068- 2- 30

Ordering Information

Description	Part Number	Color	Packing
Mounting plate 45x45, 1 Port, angled	R506663	RAL9010	10
Mounting plate 45x45, 2x1, flat	R313330	RAL9010	10
Mounting plate 45x45, 2x1, angled	R313332	RAL9010	10
Mounting plate 45x45, 2x1, flat	R313333	RAL9005	10
Mounting plate 45x45, 2x1, angled	R313331	RAL9005	10

Labeling Sheet

R313397



Matching Modules

RJ45 Module

Cat.5e s / u	R925370	R925371	
	R304325	R304326	
Cat.6 s / u	R302372	R302373	
	R304327	R304328	




FO Module

SC-RJ	R308459	R308461	
E-2000TM	R306882	R306878	R308889
LC			



Matching Accessories

R&M Security System (Level 1 and Level 3)



Warning:

R&M Security system Level 2 can only be used every second port, as well as Fiber Guard!
R506663 works with all 3 levels security products

Drawing

