

PRIME-FSU-right-ANT-empty



030.6161

GENERAL DESCRIPTION

3/4U PRIME FSU is a pure splice unit. The basic fiber inlay is suitable for 24 crimp splice protectors. Up to three additional MCM splice cassettes with 24 crimp splice protectors each can be retrofitted. The fiber feed is from the right side and up to 8x5mm transport tubes with a tool-less connection. Suitable for PRIME-3U rack ETSI and 19 „rack with rear mounting
Max capacity: 96 fiber optic terminations

PRODUCT-NO	PRODUCT DESCRIPTION
R849844	PRIME-FSU-right-ANT-empty

SCOPE OF SUPPLY

3/4U FSU-Unit with Fiber inlay
4 pcs. Cable ties, small
1 pcs. Laser sign, small
Installation manual

TECHNICAL DATA

DESCRIPTION	VALUE / VALUE RANGE
Mounting	PRIME-3U-Sub-rack, ETSI/19“BM
Assembly	fully populated
Mounting frame type	slid-in unit

MECHANICAL DATA

DESCRIPTION	VALUE / VALUE RANGE
Color	metal sheet (Black-RAL 9005), front and fiber management (light gray-RAL 7035)
Material	metal sheet and plastic
Weight (Kg)	2.36

PRIME-FSU-right-ANT-empty

CLIMATICAL DATA

DESCRIPTION	VALUE / VALUE RANGE
Temperature range - in service	-25 °C to +70 °C / -13 °F to +158 °F
Temperature range - in storage & transport	-40 °C to +85 °C / -40 °F to +185 °F

FIRE PROPERTIES

DESCRIPTION	VALUE / VALUE RANGE
Halogen free, acid gases	Pass
RoHS	Pass

TECHNICAL DRAWING

