

PRIME-FOU-right-empty



030.6168

GENERAL DESCRIPTION

3/4U PRIME FOU is a fiber overlength unit. Inside the unit can store up to 32m Fiber overlength of loose tube or patch cord fibers. With the two Velcro tape the cable can be fixed in a safe way. The fiber feed is from the back side. Suitable for PRIME-3U sub-rack for 19" rack with front mounting. .

PRODUCT-NO	PRODUCT DESCRIPTION
R850806	PRIME-FOU-right-empty

SCOPE OF SUPPLY

3/4U FOU-Unit
2 pcs. Velcro-tape
1 pcs. Cable mounting bracket
2 pcs. Screws and Washer M3
1 pcs. Laser sign, small
Installation manual

TECHNICAL DATA

DESCRIPTION	VALUE / VALUE RANGE
Mounting	PRIME-3U-Sub-rack, ETSI/19"BM
Assembly	fully populated
Mounting frame type	slid-in unit

MECHANICAL DATA

DESCRIPTION	VALUE / VALUE RANGE
Color	metal sheet (Black-RAL 9005), front and fiber management (light gray-RAL 7035)
Material	metal sheet and plastic
Weight (Kg)	2.15

PRIME-FOU-right-empty

CLIMATICAL DATA

DESCRIPTION	VALUE / VALUE RANGE
Temperature range - in service	-25 °C to +70 °C / -13 °F to +158 °F
Temperature range - in storage & transport	-40 °C to +85 °C / -40 °F to +185 °F

FIRE PROPERTIES

DESCRIPTION	VALUE / VALUE RANGE
Halogen free, acid gases	Pass
RoHS	Pass

TECHNICAL DRAWING

