

PRIME-FBU-24xLC-D-APC8-C



030.6152

GENERAL DESCRIPTION

3/4U PRIME FBU is a breakout unit. Simple connection of pre-assembled cables. Feeding and connecting of the cables from the front and back side. Attaching the fan-out cable with safety strap. Suitable for PRIME-3U rack ETSI and 19" rack mounting.

PRODUCT-NO	PRODUCT DESCRIPTION
R858604	PRIME-FBU-24xLC-D-APC8-C

SCOPE OF SUPPLY

3/4U FBU-Unit fully assembled
1 pcs. Cable mounting plate, back fixation
1 pcs. Velcro tape
1 pcs. Laser sign, small
Installation manual

TECHNICAL DATA

DESCRIPTION	VALUE / VALUE RANGE
Fiber count	24
Number of connectors A	24
Connector type FO A	LC-Duplex
Protection class IP A	IP 20
Polishing plug A	APC
Attenuation grade IL A	C
Connector color A	green
Sleeve material	ceramic
Standards / norms	Adapter in acc. with IEC 61754-20
Mounting	PRIME-3U-Sub-rack, ETSI/19"

PRIME-FBU-24xLC-D-APC8-C

DESCRIPTION	VALUE / VALUE RANGE
Assembly	fully populated
Mounting frame type	slid-in unit

MECHANICAL DATA

DESCRIPTION	VALUE / VALUE RANGE
Color	metal sheet (Black-RAL 9005), front and fiber management (light gray-RAL 7035)
Material	metal sheet and plastic

CLIMATICAL DATA

DESCRIPTION	VALUE / VALUE RANGE
Temperature range - in service	-25 °C to 70 °C / -13 °F to +158 °F
Temperature range - in storage & transport	-40 °C to 85 °C / -40 °F to +185 °F

FIRE PROPERTIES

DESCRIPTION	VALUE / VALUE RANGE
Halogen free, acid gases	Pass
RoHS	Pass

TECHNICAL DRAWING

