






















RS PRO Range Guide

Your Smart Choice for

ELECTRICAL

	p.2 Cable Accs		p.109 Cable Mgt & Elec Acc
	p.132 Contactors /Breakers		p.133 Current, Position & movement sensors
	p.134 DIN Rail Terminal Blocks		p.150 Drives & Motors
	p.162 Elec & Data Cable		p.188 Electrical T&M
	p.198 Enclosures		p.260 Machine Safety
	p.261 Photoelectric & proximity Sensors		p.281 PLC, HMI & IPC
	p.282 Power Management		p.289 Pressure , level and flow
	p.295 Push But & Swit		p.306 Pwr & Ind Cable
	p.307 Relays		p.319 Sounders /Beacons
	p.325 Structural Systems		p.332 Temp Sensors & Control
			p.425 Timers, Counters



FAST FITTING FEET,TYPE 1 20MM DIAx10MM H

- ขนาดบรรจุภัณฑ์: **50 x EA**
- Anti Vibration Mount Type: Rubber Foot
 - Diameter: 20 mm
 - Foot Height: 10 mm
 - Overall Height: 10 mm
 - Foot Shape: Round



1720855 Rubber Foot

FAST FITTING FEET,TYPE 1 24MM DIAx14MM H

- ขนาดบรรจุภัณฑ์: **50 x EA**
- Anti Vibration Mount Type: Rubber Foot
 - Diameter: 24 mm
 - Foot Height: 14 mm
 - Overall Height: 14 mm
 - Foot Shape: Round



1720856 Rubber Foot

RS PRO ROUND ANTI VIBRATION MOUNT, RUBBER FOOT

- ขนาดบรรจุภัณฑ์: **50 x EA**
- Anti Vibration Mount Type: Rubber Foot
 - Diameter: 21 mm
 - Foot Height: 4.2 mm
 - Overall Height: 4.2 mm
 - Foot Shape: Round



1720858 Rubber Foot

RS PRO ROUND ANTI VIBRATION MOUNT, RUBBER FOOT

- ขนาดบรรจุภัณฑ์: **40 x EA**
- Anti Vibration Mount Type: Rubber Foot
 - Diameter: 40 mm
 - Foot Height: 10 mm
 - Overall Height: 10 mm
 - Foot Shape: Round



1720859 Rubber Foot

PUSH ON FEET

- ขนาดบรรจุภัณฑ์: **40 x EA**
- Anti Vibration Mount Type: Rubber Foot
 - Diameter: 13.4 mm
 - Foot Height: 15.2 mm
 - Overall Height: 15.2 mm
 - Material: Rubber
 - Foot Shape: Round



1720860 Rubber Foot

RS PRO ROUND ANTI VIBRATION MOUNT, RUBBER FOOT

- ขนาดบรรจุภัณฑ์: **40 x EA**
- Anti Vibration Mount Type: Rubber Foot
 - Diameter: 15 mm
 - Foot Height: 6 mm
 - Overall Height: 6 mm
 - Foot Shape: Round



1720866 Rubber Foot

RS PRO ROUND ANTI VIBRATION MOUNT, RUBBER FOOT

- ขนาดบรรจุภัณฑ์: **40 x EA**
- Anti Vibration Mount Type: Rubber Foot
 - Diameter: 14.2 mm
 - Foot Height: 5.5 mm
 - Overall Height: 5.5 mm
 - Foot Shape: Round



1720870 Rubber Foot

RS PRO ROUND ANTI VIBRATION MOUNT, RUBBER FOOT

- ขนาดบรรจุภัณฑ์: **40 x EA**
- Anti Vibration Mount Type: Rubber Foot
 - Diameter: 15 mm
 - Foot Height: 9 mm
 - Overall Height: 9 mm
 - Foot Shape: Round



1720871 Rubber Foot

RS PRO ROUND ANTI VIBRATION MOUNT, RUBBER FOOT

- ขนาดบรรจุภัณฑ์: **40 x EA**
- Anti Vibration Mount Type: Rubber Foot
 - Diameter: 21 mm
 - Foot Height: 6 mm
 - Overall Height: 6 mm
 - Foot Shape: Round



1720875 Rubber Foot

RS PRO ROUND ANTI VIBRATION MOUNT, RUBBER FOOT

- ขนาดบรรจุภัณฑ์: **40 x EA**
- Anti Vibration Mount Type: Rubber Foot
 - Diameter: 15 mm
 - Foot Height: 6 mm
 - Overall Height: 6 mm
 - Foot Shape: Round



1720876 Rubber Foot

RS PRO ROUND ANTI VIBRATION MOUNT, RUBBER FOOT

- ขนาดบรรจุภัณฑ์: **40 x EA**
- Anti Vibration Mount Type: Rubber Foot
 - Diameter: 15 mm
 - Foot Height: 6 mm
 - Overall Height: 6 mm
 - Foot Shape: Round



1720877 Rubber Foot

RS PRO ROUND ANTI VIBRATION MOUNT, RUBBER FOOT

- ขนาดบรรจุภัณฑ์: **40 x EA**
- Anti Vibration Mount Type: Rubber Foot
 - Diameter: 21 mm
 - Foot Height: 8 mm
 - Overall Height: 8 mm
 - Foot Shape: Round



1720878 Rubber Foot

CABLE,CLAMP,RIBBON,SELF ADHESIVE,PVC,25.4MM,13MM

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Cable Clip/Clamp Style: Flat Cable Clamp
 - Affixing Method: Self Adhesive
 - Material: PVC
 - Colour: Grey
 - Length: 13 mm
 - Width: 25 mm
 - Depth: 6 mm
 - Self Adhesive: Yes



233180 Flat Cable

CABLE,CLAMP,RIBBON,SELF ADHESIVE,PVC,25.4MM,25MM

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Cable Clip/Clamp Style: Flat Cable Clamp
 - Affixing Method: Self Adhesive
 - Material: PVC
 - Colour: Grey
 - Length: 24 mm
 - Width: 25 mm
 - Depth: 9 mm
 - Self Adhesive: Yes



233190 Flat Cable

CABLE,CLIP,CIRCULAR,TV,BLACK POLYPROPYLENE,DIA 5/6MM

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Cable Clip/Clamp Style: TV Cable Clip
 - Maximum Bundle Diameter: 6 mm
 - Affixing Method: Nail
 - Material: PE
 - Colour: Black
 - Width: 4.69 mm
 - Depth: 7.18 mm
 - Dimensions [L x W (x D)]: 4.69 x 7.18 mm



233415 TV Cable Clip

CABLE,CLIP,CIRCULAR,TV,BLACK POLYPROPYLENE,DIA 7/8MM

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Cable Clip/Clamp Style: TV Cable Clip
 - Maximum Bundle Diameter: 8 mm
 - Affixing Method: Nail
 - Material: PE
 - Colour: Black
 - Length: 9.9 mm
 - Width: 5.6 mm
 - Depth: 10.9 mm



233433 TV Cable Clip

RS PRO WHITE PE RECTANGULAR CABLE CLIP

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Cable Clip/Clamp Style: Rectangular Cable Clip
 - Affixing Method: Nail
 - Material: PE
 - Colour: White
 - Length: 9.9 mm
 - Width: 18 mm
 - Depth: 12.9 mm
 - Dimensions [L x W (x D)]: 9.9 x 18 x 12.9 mm



233443 Rectangular

RS PRO GREY PE RECTANGULAR CABLE CLIP

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Cable Clip/Clamp Style: Rectangular Cable Clip
 - Affixing Method: Nail
 - Material: PE
 - Colour: Grey
 - Length: 9.9 mm
 - Width: 26.6 mm
 - Depth: 12.9 mm
 - Dimensions [L x W (x D)]: 9.9 x 26.6 x 12.9 mm



233459 Rectangular

RS PRO WHITE PE ROUND CLIP, 5MM MAX. BUNDLE

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Cable Clip/Clamp Style: Round Clip
 - Maximum Bundle Diameter: 5 mm
 - Affixing Method: Nail
 - Material: PE
 - Colour: White
 - Width: 5 mm
 - Depth: 7.6 mm
 - Dimensions [L x W (x D)]: 5 x 7.4 mm



233512 Round Clip

RS PRO WHITE PE ROUND CLIP, 3.5MM MAX. BUNDLE

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Cable Clip/Clamp Style: Round Clip
 - Maximum Bundle Diameter: 3.5 mm
 - Affixing Method: Nail
 - Material: PE
 - Colour: White
 - Width: 3.5 mm
 - Depth: 5.9 mm
 - Dimensions [L x W (x D)]: 3.5 x 6.4 mm



233516 Round Clip

CABLE,CLIP,ROUND,PLASTIC,WHITE,7.0MM DIA

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Cable Clip/Clamp Style: Round Clip
 - Maximum Bundle Diameter: 7 mm
 - Affixing Method: Nail
 - Material: PE
 - Colour: White
 - Length: 7 mm
 - Width: 11 mm
 - Depth: 11 mm
 - Dimensions [L x W (x D)]: 7 x 11 mm



233522 Round Clip

RS PRO WHITE PE RECTANGULAR CABLE CLIP

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Cable Clip/Clamp Style: Rectangular Cable Clip
 - Affixing Method: Nail
 - Material: PE
 - Colour: White
 - Length: 10 mm
 - Width: 11.6 mm
 - Depth: 9.7 mm
 - Dimensions [L x W (x D)]: 10 x 11.6 x 9.7 mm



233556 Rectangular

RS PRO WHITE PE RECTANGULAR CABLE CLIP

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Cable Clip/Clamp Style: Rectangular Cable Clip
 - Affixing Method: Nail
 - Material: PE
 - Colour: White
 - Length: 9.3 mm
 - Width: 8 mm
 - Depth: 8 mm
 - Dimensions [L x W (x D)]: 9.3 x 8 x 8 mm



233562 Rectangular

RS PRO WHITE PE RECTANGULAR CABLE CLIP

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Cable Clip/Clamp Style: Rectangular Cable Clip
 - Affixing Method: Nail
 - Material: PE
 - Colour: White
 - Length: 9.9 mm
 - Width: 8.5 mm
 - Depth: 8 mm
 - Dimensions [L x W (x D)]: 9.9 x 8.5 x 8 mm



233578 Rectangular

RS PRO WHITE PE RECTANGULAR CABLE CLIP

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Cable Clip/Clamp Style: Rectangular Cable Clip
 - Affixing Method: Nail
 - Material: PE
 - Colour: White
 - Length: 9.8 mm
 - Width: 10 mm
 - Depth: 10 mm
 - Dimensions [L x W (x D)]: 9.8 x 10 x 10 mm



233584 Rectangular

RS PRO GREY PE RECTANGULAR CABLE CLIP, 1.5MM MAX. BUNDLE

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Cable Clip/Clamp Style: Rectangular Cable Clip
 - Maximum Bundle Diameter: 1.5 mm
 - Affixing Method: Nail
 - Material: PE
 - Colour: Grey
 - Length: 9.9 mm
 - Width: 8.5 mm
 - Depth: 8 mm



233629 Rectangular

RS PRO GREY PE RECTANGULAR CABLE CLIP, 6MM MAX. BUNDLE

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Cable Clip/Clamp Style: Rectangular Cable Clip
 - Maximum Bundle Diameter: 6 mm
 - Affixing Method: Nail
 - Material: PE
 - Colour: Grey
 - Length: 9.4 mm
 - Width: 13.5 mm
 - Depth: 11.6 mm



233657 Rectangular

CABLE,CLIP,NYLON,SELF-ADHESIVE,15.7MM,BUNDLE

- ขนาดบรรจุภัณฑ์: **50 x EA**
- Cable Clip/Clamp Style: Cable Clip
 - Maximum Bundle Diameter: 15.75 mm
 - Affixing Method: Self Adhesive
 - Material: Nylon 66
 - Colour: Natural
 - Length: 32.5 mm
 - Width: 28.3 mm
 - Depth: 15.2 mm



404427 Cable Clip

CABLE,CLIP,NYLON,SELF-ADHESIVE,7MM,BUNDLE

- ขนาดบรรจุภัณฑ์: **50 x EA**
- Cable Clip/Clamp Style: Cable Clip
 - Maximum Bundle Diameter: 7.11 mm
 - Affixing Method: Self Adhesive
 - Material: Nylon 66
 - Colour: Natural
 - Length: 26.8 mm
 - Width: 26.5 mm
 - Depth: 11.7 mm



404433 Cable Clip

CABLE,CLIP,NYLON,SELF-ADHESIVE,13.5MM,BUNDLE

- ขนาดบรรจุภัณฑ์: **50 x EA**
- Cable Clip/Clamp Style: Cable Clip
 - Maximum Bundle Diameter: 13.51 mm
 - Affixing Method: Self Adhesive
 - Material: Nylon 66
 - Colour: Natural
 - Length: 25.6 mm
 - Width: 25.5 mm
 - Depth: 17.2 mm



404437 Cable Clip

CABLE,CLAMP,NYLON,SELF-ADHESIVE,ADJUSTABLE,25MM

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Cable Clip/Clamp Style: Adjustable Clamp
 - Maximum Bundle Diameter: 26 mm
 - Affixing Method: Self Adhesive
 - Material: Nylon 66
 - Colour: Grey
 - Length: 30.5 mm
 - Width: 21 mm
 - Depth: 108 mm



404443 Adjustable

RS PRO GREY NYLON ADJUSTABLE CLAMP, 22MM MAX. BUNDLE

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Cable Clip/Clamp Style: Adjustable Clamp
 - Maximum Bundle Diameter: 22 mm
 - Affixing Method: Self Adhesive
 - Material: Nylon 66
 - Colour: Grey
 - Length: 30.5 mm
 - Width: 21 mm
 - Depth: 90 mm



404449 Adjustable

CABLE, CLAMP, NYLON, SELF-ADHESIVE, ADJUSTABLE, 18MM

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Cable Clip/Clamp Style: Adjustable Clamp
 - Maximum Bundle Diameter: 17 mm
 - Affixing Method: Self Adhesive
 - Material: Nylon 66
 - Colour: Grey
 - Length: 25 mm
 - Width: 18 mm
 - Depth: 70 mm



404455 Adjustable

CABLE, CLIP, NYLON, SELF-ADHESIVE, 4MM, BUNDLE

- ขนาดบรรจุภัณฑ์: **50 x EA**
- Cable Clip/Clamp Style: Round Clip
 - Maximum Bundle Diameter: 4.06 mm
 - Affixing Method: Self Adhesive
 - Material: Nylon 66
 - Colour: Natural
 - Length: 19 mm
 - Width: 19 mm
 - Depth: 7.2 mm



404459 Round Clip

CABLE, CLIP, HOOK, SELF-ADHESIVE, WHITE, PLASTICISED, AL

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Cable Clip/Clamp Style: Hook Clip
 - Affixing Method: Self Adhesive
 - Material: Aluminium
 - Colour: White
 - Length: 69.8 mm
 - Width: 25.4 mm
 - Depth: 7.9 mm
 - Self Adhesive: Yes



475142 Hook Clip

RS PRO NATURAL ALUMINIUM BUCKLE CLIP, 13MM MAX. BUNDLE

- ขนาดบรรจุภัณฑ์: **250 x EA**
- Cable Clip/Clamp Style: Buckle Clip
 - Maximum Bundle Diameter: 13 mm
 - Affixing Method: Self Adhesive
 - Material: Aluminium
 - Colour: Natural
 - Length: 63.5 mm
 - Width: 25.4 mm
 - Depth: 6.4 mm



475148 Buckle Clip

CABLE, CLIP, RIBBON, ALUMINIUM, SELF-ADHESIVE, 13MM, 10

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Cable Clip/Clamp Style: Open Arm Clip
 - Maximum Bundle Diameter: 12.7 mm
 - Affixing Method: Self Adhesive
 - Material: Aluminium
 - Colour: Natural
 - Length: 12.9 mm
 - Width: 9.8 mm
 - Depth: 6.3 mm



475154 Open Arm Clip

RS PRO NATURAL ALUMINIUM BUCKLE CLIP, 19.3MM MAX. BUNDLE

- ขนาดบรรจุภัณฑ์: **250 x EA**
- Cable Clip/Clamp Style: Buckle Clip
 - Maximum Bundle Diameter: 19.3 mm
 - Affixing Method: Self Adhesive
 - Material: Aluminium
 - Colour: Natural
 - Length: 89 mm
 - Width: 25.4 mm
 - Depth: 8 mm



475158 Buckle Clip

CABLE, CLIP, METAL, ALUMINIUM, SELF-ADHESIVE, MAX DIA 9

- ขนาดบรรจุภัณฑ์: **250 x EA**
- Cable Clip/Clamp Style: Open Arm Clip
 - Maximum Bundle Diameter: 9.5 mm
 - Affixing Method: Self Adhesive
 - Material: Aluminium
 - Colour: Natural
 - Length: 19 mm
 - Width: 16 mm
 - Depth: 14.9 mm



475160 Open Arm Clip

CABLE, CLIP, RIBBON, ALUMINIUM, SELF-ADHESIVE, 19.3MM, 1

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Cable Clip/Clamp Style: Open Arm Clip
 - Maximum Bundle Diameter: 18 mm
 - Affixing Method: Self Adhesive
 - Material: Aluminium
 - Colour: Natural
 - Length: 19.3 mm
 - Width: 9.8 mm
 - Depth: 6.3 mm



475164 Open Arm Clip

CABLE, CLIP, RIBBON, ALUMINIUM, SELF-ADHESIVE, 25.7MM, 2

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Cable Clip/Clamp Style: Open Arm Clip
 - Maximum Bundle Diameter: 10 mm
 - Affixing Method: Self Adhesive
 - Material: Aluminium
 - Colour: Natural
 - Length: 25.6 mm
 - Width: 9.8 mm
 - Depth: 7.6 mm



475170 Open Arm Clip

RS PRO NATURAL ALUMINIUM OPEN ARM CLIP

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Cable Clip/Clamp Style: Open Arm Clip
 - Affixing Method: Self Adhesive
 - Material: Aluminium
 - Colour: Natural
 - Length: 33 mm
 - Width: 9.8 mm
 - Depth: 9.8 mm
 - Self Adhesive: Yes



475182 Open Arm Clip

RS PRO NATURAL ALUMINIUM OPEN ARM CLIP, 10MM MAX. BUNDLE

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Cable Clip/Clamp Style: Open Arm Clip
 - Maximum Bundle Diameter: 10 mm
 - Affixing Method: Self Adhesive
 - Material: Aluminium
 - Colour: Natural
 - Length: 44 mm
 - Width: 9.8 mm
 - Depth: 12.2 mm



475186 Open Arm Clip

RS PRO NATURAL ALUMINIUM OPEN ARM CLIP

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Cable Clip/Clamp Style: Open Arm Clip
 - Affixing Method: Self Adhesive
 - Material: Aluminium
 - Colour: Natural
 - Length: 63.7 mm
 - Width: 9.8 mm
 - Depth: 17.5 mm
 - Self Adhesive: Yes



475192 Open Arm Clip

CABLE, CLIP, METAL, ALUMINIUM, SELF-ADHESIVE, MAX DIA 6

- ขนาดบรรจุภัณฑ์: **250 x EA**
- Cable Clip/Clamp Style: Open Arm Clip
 - Maximum Bundle Diameter: 6 mm
 - Affixing Method: Self Adhesive
 - Material: Aluminium
 - Colour: Natural
 - Length: 16 mm
 - Width: 10.6 mm
 - Depth: 9.4 mm



475198 Open Arm Clip

RS PRO 6.4MM NATURAL NYLON P CLIP

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Closed Inside Diameter: 6.4 mm
 - Width: 10 mm
 - Fixing Hole Diameter: 4.6 mm
 - Material: Nylon
 - Coating/Lining: None
 - Colour: Natural



479544 6.4 mm

CABLE, CLAMP, P CLIPS, NATURAL, 12.7MM DIA

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Cable Clip/Clamp Style: Cable Clip



479548 Cable Clip

RS PRO NATURAL NYLON SADDLE CLIP

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Cable Clip/Clamp Style: Saddle Clip
 - Affixing Method: Push In
 - Material: Nylon 66
 - Colour: Natural
 - Length: 5.5 mm
 - Width: 15.9 mm
 - Depth: 9 mm
 - Fire Behaviour: Flame Retardant



479550 Saddle Clip

RS PRO NATURAL NYLON SADDLE CLIP

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Cable Clip/Clamp Style: Saddle Clip
 - Affixing Method: Push In
 - Material: Nylon 66
 - Colour: Natural
 - Length: 5.5 mm
 - Width: 15.9 mm
 - Depth: 14.2 mm
 - Dimensions [L x W (x D)]: 5.5 x 15.9 x 14.2 mm



479560 Saddle Clip

RS PRO NATURAL NYLON SADDLE CLIP

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Cable Clip/Clamp Style: Saddle Clip
 - Affixing Method: Push In
 - Material: Nylon 66
 - Colour: Natural
 - Length: 5.5 mm
 - Width: 15.9 mm
 - Depth: 23 mm
 - Dimensions [L x W (x D)]: 5.5 x 15.9 x 23 mm



479572 Saddle Clip

RS PRO NATURAL NYLON SADDLE CLIP

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Cable Clip/Clamp Style: Saddle Clip
 - Affixing Method: Push In
 - Material: Nylon 66
 - Colour: Natural
 - Length: 5.5 mm
 - Width: 15.9 mm
 - Depth: 31.1 mm
 - Dimensions [L x W (x D)]: 5.5 x 15.9 x 31.1 mm



479576 Saddle Clip

RS PRO WHITE NYLON SADDLE CLIP, 10.2MM MAX. BUNDLE

- ขนาดบรรจุภัณฑ์: **25 x EA**
- Cable Clip/Clamp Style: Saddle Clip
 - Maximum Bundle Diameter: 10.2 mm
 - Material: Nylon 66
 - Colour: White
 - Width: 15.9 mm
 - Depth: 5.6 mm
 - Dimensions [L x W (x D)]: 15.9 x 5.6 mm



479582 Saddle Clip

CABLE,CLIP,BUNNY,ADHESIVE BASE,BUNDLE DIA 12.7MM

- ขนาดบรรจุภัณฑ์: **20 x EA**
- Cable Clip/Clamp Style: Bunny Clip
 - Maximum Bundle Diameter: 14.8 mm
 - Affixing Method: Self Adhesive
 - Material: Nylon 66
 - Colour: Natural
 - Length: 35.2 mm
 - Width: 22 mm
 - Dimensions [L x W (x D)]: 35.2 x 22 mm



479601 Bunny Clip

CABLE,CLIP,BUNNY,ADHESIVE BASE,BUNDLE DIA 10MM

- ขนาดบรรจุภัณฑ์: **20 x EA**
- Cable Clip/Clamp Style: Bunny Clip
 - Maximum Bundle Diameter: 7.9 mm
 - Affixing Method: Self Adhesive
 - Material: Nylon 66
 - Colour: Natural
 - Length: 27.5 mm
 - Width: 17.4 mm
 - Dimensions [L x W (x D)]: 27.5 x 17.4 mm



479605 Bunny Clip

RS PRO GREY PVC DUCT CLIP, 9.5MM MAX. BUNDLE

- ขนาดบรรจุภัณฑ์: **25 x EA**
- Cable Clip/Clamp Style: Duct Clip
 - Maximum Bundle Diameter: 9.5 mm
 - Affixing Method: Self Adhesive
 - Material: PVC
 - Colour: Grey
 - Length: 28.5 mm
 - Width: 25.4 mm
 - Depth: 13.8 mm



479611 Duct Clip

RS PRO NATURAL NYLON TWISTER CLIP, 7MM MAX. BUNDLE

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Cable Clip/Clamp Style: Twister Clip
 - Maximum Bundle Diameter: 7 mm
 - Affixing Method: Twist
 - Material: Nylon 66
 - Colour: Natural
 - Length: 25 mm
 - Width: 2 mm
 - Dimensions [L x W (x D)]: 25 x 2 mm



819832 Twister Clip

RS PRO NATURAL NYLON TWISTER CLIP, 15MM MAX. BUNDLE

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Cable Clip/Clamp Style: Twister Clip
 - Maximum Bundle Diameter: 15 mm
 - Affixing Method: Twist
 - Material: Nylon 66
 - Colour: Natural
 - Length: 33.8 mm
 - Width: 1.9 mm
 - Dimensions [L x W (x D)]: 33.8 x 1.9 mm



819848 Twister Clip

RS PRO NATURAL NYLON TWISTER CLIP, 23.6MM MAX. BUNDLE

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Cable Clip/Clamp Style: Twister Clip
 - Maximum Bundle Diameter: 23.6 mm
 - Affixing Method: Twist
 - Material: Nylon 66
 - Colour: Natural
 - Length: 45 mm
 - Width: 2 mm
 - Dimensions [L x W (x D)]: 45 x 2 mm



821239 Twister Clip

RS PRO NATURAL NYLON CABLE CLAMP, 4.3MM MAX. BUNDLE

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Cable Clip/Clamp Style: Cable Clamp
 - Maximum Bundle Diameter: 4.3 mm
 - Affixing Method: Adhesive
 - Material: Nylon
 - Colour: Natural
 - Width: 9.5 mm
 - Depth: 6.5 mm



1720839 Cable Clamp

RS PRO NATURAL STEEL CABLE CLIP, 8MM MAX. BUNDLE

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Cable Clip/Clamp Style: Cable Clip
 - Maximum Bundle Diameter: 8 mm
 - Affixing Method: Screw
 - Material: Steel
 - Colour: Natural
 - Length: 56 mm
 - Width: 20 mm
 - Depth: 8 mm



1823854 Cable Clip

RS PRO NATURAL STEEL CABLE CLIP, 20MM MAX. BUNDLE

- ขนาดบรรจุภัณฑ์: **50 x EA**
- Cable Clip/Clamp Style: Cable Clip
 - Maximum Bundle Diameter: 20 mm
 - Affixing Method: Screw
 - Material: Steel
 - Colour: Natural
 - Length: 110.5 mm
 - Width: 20 mm
 - Depth: 20 mm



1823855 Cable Clip

CABLE,CLEAT,LDPE,BLACK,SIZE 5,12.7MM,QTY 50

- ขนาดบรรจุภัณฑ์: **50 x EA**
- Cable Clip/Clamp Style: Cable Clip
 - Maximum Bundle Diameter: 12.7 mm
 - Affixing Method: Screw
 - Material: PE
 - Colour: Black
 - Width: 17.5 mm
 - Depth: 28 mm
 - Dimensions [L x W (x D)]: 17.5 x 28 mm



1845214 Cable Clip

RS PRO BLACK NYLON C CLAMP, 17MM MAX. BUNDLE

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Cable Clip/Clamp Style: C Clamp
 - Maximum Bundle Diameter: 17 mm
 - Affixing Method: Adhesive
 - Material: Nylon
 - Colour: Black
 - Length: 41.3 mm
 - Width: 15.6 mm
 - Fire Behaviour: Flame Retardant



2138532 C Clamp

RS PRO BLACK NYLON C CLAMP, 12MM MAX. BUNDLE

- ขนาดบรรจุภัณฑ์: **50 x EA**
- Cable Clip/Clamp Style: C Clamp
 - Maximum Bundle Diameter: 12 mm
 - Affixing Method: Adhesive
 - Material: Nylon
 - Colour: Black
 - Length: 34.8 mm
 - Width: 16.5 mm
 - Fire Behaviour: Flame Retardant



2138533 C Clamp

RS PRO NATURAL NYLON CABLE CLIP, 2.8MM MAX. BUNDLE

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Cable Clip/Clamp Style: Cable Clip
 - Maximum Bundle Diameter: 2.8 mm
 - Affixing Method: Adhesive
 - Material: Nylon
 - Colour: Natural
 - Length: 13 mm
 - Width: 9.5 mm
 - Fire Behaviour: Flame Retardant



2138534 Cable Clip

RS PRO NATURAL NYLON CABLE CLIP, 7MM MAX. BUNDLE

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Cable Clip/Clamp Style: Cable Clip
 - Maximum Bundle Diameter: 7 mm
 - Affixing Method: Adhesive
 - Material: Nylon
 - Colour: Natural
 - Length: 25 mm
 - Width: 25 mm
 - Fire Behaviour: Flame Retardant



2138535 Cable Clip

RS PRO NATURAL NYLON CABLE CLIP, 12.8MM MAX. BUNDLE

- ขนาดบรรจุภัณฑ์: **50 x EA**
- Cable Clip/Clamp Style: Cable Clip
 - Maximum Bundle Diameter: 12.8 mm
 - Affixing Method: Adhesive
 - Material: Nylon
 - Colour: Natural
 - Length: 33.7 mm
 - Width: 27.5 mm
 - Fire Behaviour: Flame Retardant



2138536 Cable Clip

RS PRO NATURAL NYLON CABLE CLIP, 5.5MM MAX. BUNDLE

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Cable Clip/Clamp Style: Cable Clip
 - Maximum Bundle Diameter: 5.5 mm
 - Affixing Method: Adhesive
 - Material: Nylon
 - Colour: Natural
 - Length: 27 mm
 - Width: 17 mm
 - Fire Behaviour: Flame Retardant



2138537 Cable Clip

RS PRO BLACK NYLON FLAT CABLE CLAMP

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Cable Clip/Clamp Style: Flat Cable Clamp
 - Affixing Method: Adhesive
 - Material: Nylon
 - Colour: Black
 - Length: 52.2 mm
 - Width: 56.8 mm
 - Fire Behaviour: Flame Retardant
 - Dimensions [L x W (x D)]: 52.2 x 56.8 x 26.2 mm



2138538 Flat Cable

RS PRO NATURAL NYLON ROUND CLIP, 4.9MM MAX. BUNDLE

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Cable Clip/Clamp Style: Round Clip
 - Maximum Bundle Diameter: 4.9 mm
 - Affixing Method: Adhesive
 - Material: Nylon 66
 - Colour: Natural
 - Length: 52.2 mm
 - Width: 56.8 mm
 - Fire Behaviour: Flame Retardant



2163629 Round Clip

RS PRO NATURAL NYLON CABLE CLAMP

- ขนาดบรรจุภัณฑ์: **50 x EA**
- Cable Clip/Clamp Style: Cable Clamp
 - Affixing Method: Adhesive
 - Material: Nylon 66
 - Colour: Natural
 - Length: 4.1 mm
 - Width: 9.4 mm
 - Fire Behaviour: Self-extinguishing
 - Self Adhesive: Yes



2144760 Cable Clamp

RS PRO NATURAL NYLON CABLE CLAMP

- ขนาดบรรจุภัณฑ์: **50 x EA**
- Cable Clip/Clamp Style: Cable Clamp
 - Affixing Method: Adhesive
 - Material: Nylon 66
 - Colour: Natural
 - Length: 6.1 mm
 - Width: 9.4 mm
 - Fire Behaviour: Self-extinguishing
 - Self Adhesive: Yes



2144776 Cable Clamp

RS PRO NATURAL NYLON CABLE CLAMP

- ขนาดบรรจุภัณฑ์: **50 x EA**
- Cable Clip/Clamp Style: Cable Clamp
 - Affixing Method: Adhesive
 - Material: Nylon 66
 - Colour: Natural
 - Length: 7.4 mm
 - Width: 12.7 mm
 - Fire Behaviour: Self-extinguishing
 - Self Adhesive: Yes



2144782 Cable Clamp

RS PRO NATURAL NYLON CABLE CLAMP

- ขนาดบรรจุภัณฑ์: **50 x EA**
- Cable Clip/Clamp Style: Cable Clamp
 - Affixing Method: Adhesive
 - Material: Nylon 66
 - Colour: Natural
 - Length: 9.1 mm
 - Width: 12.7 mm
 - Fire Behaviour: Self-extinguishing
 - Self Adhesive: Yes



2144798 Cable Clamp

RS PRO NATURAL NYLON CABLE CLAMP

- ขนาดบรรจุภัณฑ์: **50 x EA**
- Cable Clip/Clamp Style: Cable Clamp
 - Affixing Method: Adhesive
 - Material: Nylon 66
 - Colour: Natural
 - Length: 11.2 mm
 - Width: 12.7 mm
 - Fire Behaviour: Self-extinguishing
 - Self Adhesive: Yes



2144805 Cable Clamp

RS PRO NATURAL NYLON CABLE CLAMP

- ขนาดบรรจุภัณฑ์: **50 x EA**
- Cable Clip/Clamp Style: Cable Clamp
 - Affixing Method: Adhesive
 - Material: Nylon 66
 - Colour: Natural
 - Length: 13 mm
 - Width: 12.7 mm
 - Fire Behaviour: Self-extinguishing
 - Self Adhesive: Yes



2144827 Cable Clamp

RS PRO NATURAL PE CABLE CLIP

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Cable Clip/Clamp Style: Cable Clip
 - Affixing Method: Nail
 - Material: PE
 - Colour: Natural
 - Length: 5.2 mm
 - Width: 4.6 mm
 - Depth: 5.2 mm
 - Dimensions [L x W (x D)]: 4.6 x 5.2 mm



7389363 Cable Clip

WIRE SADDLE, 7.9X3.8X9.7MM

- ขนาดบรรจุภัณฑ์: **50 x EA**
- Cable Clip/Clamp Style: Wire Saddle
 - Maximum Bundle Diameter: 6.4 mm
 - Affixing Method: Push In
 - Material: Nylon 66
 - Colour: White
 - Length: 7.9 mm
 - Width: 3.8 mm
 - Depth: 9.7 mm



8178895 Wire Saddle

RS PRO WHITE NYLON WIRE SADDLE, 3.5MM MAX. BUNDLE

- ขนาดบรรจุภัณฑ์: **50 x EA**
- Cable Clip/Clamp Style: Wire Saddle
 - Maximum Bundle Diameter: 3.5 mm
 - Affixing Method: Push In
 - Material: Nylon 66
 - Colour: White
 - Length: 6.6 mm
 - Width: 3.8 mm
 - Depth: 7.8 mm



8178899 Wire Saddle

RS PRO NATURAL NYLON WIRE SADDLE, 10.7MM MAX. BUNDLE

- ขนาดบรรจุภัณฑ์: **50 x EA**
- Cable Clip/Clamp Style: Wire Saddle
 - Maximum Bundle Diameter: 10.7 mm
 - Affixing Method: Push In
 - Material: Nylon 66
 - Colour: Natural
 - Length: 9.3 mm
 - Width: 4 mm
 - Depth: 13.4 mm



8178902 Wire Saddle

MOUNTING TWIST TIE, 15~20MM BUNDLE DIA

- ขนาดบรรจุภัณฑ์: **20 x EA**
- Cable Clip/Clamp Style: Cable Clip
 - Maximum Bundle Diameter: 20 mm
 - Affixing Method: Twist
 - Material: Nylon 66
 - Colour: Natural
 - Length: 40 mm
 - Width: 25.5 mm
 - Dimensions [L x W (x D)]: 40 x 25.5 mm



8178906 Cable Clip

STANDOFF TWIST TIE, 10.4MM DIA

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Cable Clip/Clamp Style: Twister Clip
 - Maximum Bundle Diameter: 10.4 mm
 - Affixing Method: Push In
 - Material: Nylon 66
 - Colour: Natural
 - Length: 27.3 mm
 - Dimensions [L x W (x D)]: 27.3 x 10.4 mm



8178909 Twister Clip

TWIST TIE, 10.1MM BUNDLE DIA

- ขนาดบรรจุภัณฑ์: **50 x EA**
- Cable Clip/Clamp Style: Twister Clip
 - Maximum Bundle Diameter: 10.1 mm
 - Affixing Method: Twist
 - Material: Nylon 66
 - Colour: Natural
 - Length: 29.8 mm
 - Width: 1.7 mm
 - Depth: 11.6 mm



8178915 Twister Clip

TWIST TIE, 13.4MM BUNDLE DIA

- ขนาดบรรจุภัณฑ์: **50 x EA**
- Cable Clip/Clamp Style: Twister Clip
 - Maximum Bundle Diameter: 13.4 mm
 - Affixing Method: Twist
 - Material: Nylon 66
 - Colour: Natural
 - Length: 33.8 mm
 - Width: 1.9 mm
 - Depth: 15 mm



8178918 Twister Clip

RS PRO WHITE METAL CABLE CLIP

- ขนาดบรรจุภัณฑ์: **50 x EA**
- Cable Clip/Clamp Style: Cable Clip
 - Affixing Method: Self Adhesive
 - Material: Metal
 - Colour: White
 - Length: 19.4 mm
 - Width: 10 mm
 - Depth: 0.5 mm
 - Self Adhesive: Yes



8178921 Cable Clip

RS PRO NATURAL NYLON TWISTER CLIP, 7MM MAX. BUNDLE

- ขนาดบรรจุภัณฑ์: **50 x EA**
- Cable Clip/Clamp Style: Twister Clip
 - Maximum Bundle Diameter: 7 mm
 - Affixing Method: Twist
 - Material: Nylon 66
 - Colour: Natural
 - Length: 25 mm
 - Width: 2 mm
 - Depth: 7 mm



8178924 Twister Clip

TWIST TIE, 21.3MM BUNDLE DIA

- ขนาดบรรจุภัณฑ์: **50 x EA**
- Cable Clip/Clamp Style: Twister Clip
 - Maximum Bundle Diameter: 21.3 mm
 - Affixing Method: Twist
 - Material: Nylon 66
 - Colour: Natural
 - Length: 45 mm
 - Width: 2 mm
 - Depth: 23.6 mm



8178928 Twister Clip

RS PRO WHITE NYLON CABLE CLAMP, 15.4MM MAX. BUNDLE

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Cable Clip/Clamp Style: Cable Clamp
 - Maximum Bundle Diameter: 15.4 mm
 - Affixing Method: Push In
 - Material: Nylon 66
 - Colour: White
 - Length: 37 mm
 - Width: 18.4 mm
 - Depth: 31.8 mm



8178937 Cable Clamp

RS PRO NATURAL NYLON CABLE CLAMP

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Cable Clip/Clamp Style: Cable Clamp
 - Affixing Method: Snap In
 - Material: Nylon 66
 - Colour: Natural
 - Length: 67 mm
 - Width: 15.7 mm
 - Depth: 16.3 mm
 - Fire Behaviour: Self-extinguishing



8178943 Cable Clamp

RS PRO NATURAL NYLON CABLE CLAMP

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Cable Clip/Clamp Style: Cable Clamp
 - Affixing Method: Snap In
 - Material: Nylon 66
 - Colour: Natural
 - Length: 45.1 mm
 - Width: 18.5 mm
 - Depth: 16.3 mm
 - Fire Behaviour: Self-extinguishing



8178946 Cable Clamp

CABLE CLAMP, 5MM BUNDLE DIA

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Cable Clip/Clamp Style: Cable Clamp
 - Maximum Bundle Diameter: 5 mm
 - Affixing Method: Screw
 - Material: Nylon 66
 - Colour: Natural
 - Length: 18.6 mm
 - Width: 9.6 mm
 - Depth: 1.2 mm



8178952 Cable Clamp

CABLE CLAMP, 3.1MM BUNDLE DIA

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Cable Clip/Clamp Style: Cable Clamp
 - Maximum Bundle Diameter: 3.1 mm
 - Affixing Method: Screw
 - Material: Nylon 66
 - Colour: Natural
 - Length: 17 mm
 - Width: 9.6 mm
 - Depth: 1.2 mm



8178956 Cable Clamp

CABLE CLAMP, 12.7MM BUNDLE DIA

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Cable Clip/Clamp Style: P Clamp
 - Maximum Bundle Diameter: 12.7 mm
 - Affixing Method: Screw
 - Material: Nylon 66
 - Colour: Natural
 - Length: 31 mm
 - Width: 12 mm
 - Depth: 1.5 mm



8178959 P Clamp

RS PRO GREY NYLON CABLE CLAMP, 14MM MAX. BUNDLE

- ขนาดบรรจุภัณฑ์: **50 x EA**
- Cable Clip/Clamp Style: Cable Clamp
 - Maximum Bundle Diameter: 14 mm
 - Affixing Method: Self Adhesive
 - Material: Nylon 66
 - Colour: Grey
 - Length: 30 mm
 - Width: 24.5 mm
 - Dimensions [L x W (x D)]: 30 x 24.5 mm



8178962 Cable Clamp

CABLE CLAMP, 6.35MM BUNDLE DIA


- ขนาดบรรจุภัณฑ์: **100 x EA**
- Cable Clip/Clamp Style: Cable Clamp
 - Maximum Bundle Diameter: 6.4 mm
 - Affixing Method: Screw
 - Material: Nylon 66
 - Colour: Natural
 - Length: 20 mm
 - Width: 10 mm
 - Depth: 1.4 mm



8178968 Cable Clamp

CABLE CLAMP, 16~18MM BUNDLE DIA


- ขนาดบรรจุภัณฑ์: **50 x EA**
- Cable Clip/Clamp Style: Cable Clamp
 - Maximum Bundle Diameter: 18 mm
 - Affixing Method: Self Adhesive
 - Material: Nylon 66
 - Colour: Grey
 - Length: 30 mm
 - Width: 24.5 mm
 - Dimensions [L x W (x D)]: 30 x 24.5 mm



8178971 Cable Clamp

CABLE CLAMP, 6~7MM BUNDLE DIA

- ขนาดบรรจุภัณฑ์: **50 x EA**
- Cable Clip/Clamp Style: Cable Clamp
 - Maximum Bundle Diameter: 7 mm
 - Affixing Method: Self Adhesive
 - Material: Nylon 66
 - Colour: Grey
 - Length: 25 mm
 - Width: 20 mm
 - Dimensions [L x W (x D)]: 25 x 20 mm



8178974 Cable Clamp

CABLE CLAMP, 9~10MM BUNDLE DIA


- ขนาดบรรจุภัณฑ์: **50 x EA**
- Cable Clip/Clamp Style: Cable Clamp
 - Maximum Bundle Diameter: 10 mm
 - Affixing Method: Self Adhesive
 - Material: Nylon 66
 - Colour: Grey
 - Length: 30 mm
 - Width: 24.5 mm
 - Dimensions [L x W (x D)]: 30 x 24.5 mm



8178978 Cable Clamp

CABLEMAT CARPET TOP

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 1200 mm
 - Internal Dimensions: 400 x 1200 mm
 - Width: 400 mm
 - Colour: Black
 - Material: Rubber
 - Standards Met: EN 13501-1, EN 14041



1757246 1200 mm

RS PRO 1.2M BLACK CABLE COVER IN RUBBER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 1.2 m
 - Internal Dimensions: 400 x 1200 mm
 - Width: 400 mm
 - Colour: Black
 - Material: Rubber
 - Standards Met: EN 13501-1



1757247 1.2 m

RS PRO 1M BLACK, RED CABLE COVER IN RUBBER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 1 m
 - Width: 24.9 mm
 - Colour: Black, Red
 - Material: Rubber
 - Number of Channels: 2



2184305 1 m

RS PRO 1M BLACK, RED CABLE COVER IN RUBBER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 1 m
 - Width: 50.0 mm
 - Colour: Black, Red
 - Material: Rubber
 - Number of Channels: 3



2184306 1 m

RS PRO 1.83M GREY CABLE COVER IN PVC, 7.4MM INSIDE DIA.

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inside Diameter: 7.4 mm
 - Length: 1.83 m
 - Width: 25.4 mm
 - Internal Dimensions: 7.4 x 3.8 mm
 - Colour: Grey
 - Material: PVC



8659492 7.4 mm

RS PRO 1.83M BROWN CABLE COVER IN PVC, 7.4MM INSIDE DIA.

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inside Diameter: 7.4 mm
 - Length: 1.83 m
 - Width: 25.4 mm
 - Internal Dimensions: 7.4 x 3.8 mm
 - Colour: Brown
 - Material: PVC



8659495 7.4 mm

RS PRO 1.83M WHITE CABLE COVER IN PVC, 7.4MM INSIDE DIA.

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inside Diameter: 7.4 mm
 - Length: 1.83 m
 - Width: 25.4 mm
 - Internal Dimensions: 7.4 x 3.8 mm
 - Colour: White
 - Material: PVC



8659499 7.4 mm

RS PRO 1.83M GREY CABLE COVER IN PVC, 14.8MM INSIDE DIA.

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inside Diameter: 14.8 mm
 - Length: 1.83 m
 - Width: 50.8 mm
 - Internal Dimensions: 14.8 x 7.4 mm
 - Colour: Grey
 - Material: PVC



8659502 14.8 mm

RS PRO 1.83M BROWN CABLE COVER IN PVC, 14.8MM INSIDE DIA.

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inside Diameter: 14.8 mm
 - Length: 1.83 m
 - Width: 50.8 mm
 - Internal Dimensions: 14.8 x 7.4 mm
 - Colour: Brown
 - Material: PVC



8659506 14.8 mm

RS PRO 1.83M BLACK CABLE COVER IN PVC, 7.4MM INSIDE DIA.

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inside Diameter: 7.4 mm
 - Length: 1.83 m
 - Width: 25.4 mm
 - Internal Dimensions: 7.4 x 3.8 mm
 - Colour: Black
 - Material: PVC



8659509 7.4 mm

RS PRO 1.83M BLACK CABLE COVER IN PVC, 14.8MM INSIDE DIA.

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inside Diameter: 14.8 mm
 - Length: 1.83 m
 - Width: 50.8 mm
 - Internal Dimensions: 14.8 x 7.8 mm
 - Colour: Black
 - Material: PVC



8659518 14.8 mm

RS PRO 1.83M GREY CABLE COVER IN PVC, 19MM INSIDE DIA.

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inside Diameter: 19 mm
 - Length: 1.83 m
 - Width: 66 mm
 - Internal Dimensions: 19 x 10.9 mm
 - Colour: Grey
 - Material: PVC



8659512 19 mm

RS PRO 1.83M WHITE CABLE COVER IN PVC, 14.8MM INSIDE DIA.

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inside Diameter: 14.8 mm
 - Length: 1.83 m
 - Width: 50.8 mm
 - Internal Dimensions: 14.8 x 7.8 mm
 - Colour: White
 - Material: PVC



8659515 14.8 mm

RS PRO 1.83M BROWN CABLE COVER IN PVC, 19MM INSIDE DIA.

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inside Diameter: 19 mm
 - Length: 1.83 m
 - Width: 66 mm
 - Internal Dimensions: 19 x 10.9 mm
 - Colour: Brown
 - Material: PVC



8659521 19 mm

RS PRO 1.83M WHITE CABLE COVER IN PVC, 19MM INSIDE DIA.

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inside Diameter: 19 mm
 - Length: 1.83 m
 - Width: 66 mm
 - Internal Dimensions: 19 x 10.9 mm
 - Colour: White
 - Material: PVC



8659524 19 mm

RS PRO 1.83M BLACK CABLE COVER IN PVC, 19MM INSIDE DIA.

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inside Diameter: 19 mm
 - Length: 1.83 m
 - Width: 66 mm
 - Internal Dimensions: 19 x 10.9 mm
 - Colour: Black
 - Material: PVC



8659528 19 mm

RS PRO 1.83M GREY CABLE COVER IN PVC, 22MM INSIDE DIA.

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inside Diameter: 22 mm
 - Length: 1.83 m
 - Width: 76.2 mm
 - Internal Dimensions: 22 x 11.6 mm
 - Colour: Grey
 - Material: PVC



8659537 22 mm

RS PRO 1.83M BLACK CABLE COVER IN PVC, 22MM INSIDE DIA.

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inside Diameter: 22 mm
 - Length: 1.83 m
 - Width: 76.2 mm
 - Internal Dimensions: 22 x 11.6 mm
 - Colour: Black
 - Material: PVC



8659543 22 mm

RS PRO 1.83M GREY CABLE COVER IN PVC, 29.4MM INSIDE DIA.

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inside Diameter: 29.4 mm
 - Length: 1.83 m
 - Width: 101.6 mm
 - Internal Dimensions: 29.4 x 15.4 mm
 - Colour: Grey
 - Material: PVC



8659546 29.4 mm

RS PRO 1.83M BLACK CABLE COVER IN PVC, 29.4MM INSIDE DIA.

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inside Diameter: 29.4 mm
 - Length: 1.83 m
 - Width: 101.6 mm
 - Internal Dimensions: 29.4 x 15.4 mm
 - Colour: Black
 - Material: PVC



8659552 29.4 mm

RS PRO 1M GREY CABLE COVER IN PVC, 7.4MM INSIDE DIA.

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inside Diameter: 7.4 mm
 - Length: 1 m
 - Width: 25.4 mm
 - Internal Dimensions: 7.4 x 3.8 mm
 - Colour: Grey
 - Material: PVC



8659556 7.4 mm

RS PRO 1.83M WHITE CABLE COVER IN PVC, 29.4MM INSIDE DIA.

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inside Diameter: 29.4 mm
 - Length: 1.83 m
 - Width: 101.6 mm
 - Internal Dimensions: 29.4 x 15.4 mm
 - Colour: White
 - Material: PVC



8659559 29.4 mm

RS PRO 1M WHITE CABLE COVER IN PVC, 7.4MM INSIDE DIA.

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inside Diameter: 7.4 mm
 - Length: 1 m
 - Width: 25.4 mm
 - Internal Dimensions: 7.4 x 3.8 mm
 - Colour: White
 - Material: PVC



8659568 7.4 mm

RS PRO 1M WHITE CABLE COVER IN PVC, 14.8 X 7.8MM INSIDE DIA.

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inside Diameter: 14.8 x 7.8 mm
 - Length: 1 m
 - Width: 50.8 mm
 - Internal Dimensions: 14.8 x 7.8 mm
 - Colour: White
 - Material: PVC



8659578 14.8 x 7.8 mm

RS PRO 1M BLACK CABLE COVER IN PVC, 7.4MM INSIDE DIA.

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inside Diameter: 7.4 mm
 - Length: 1 m
 - Width: 25.4 mm
 - Internal Dimensions: 7.4 x 3.8 mm
 - Colour: Black
 - Material: PVC



8659562 7.4 mm

RS PRO 1M BLACK CABLE COVER IN PVC, 14.8 X 7.8MM INSIDE DIA.

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inside Diameter: 14.8 x 7.8 mm
 - Length: 1 m
 - Width: 50.8 mm
 - Internal Dimensions: 14.8 x 7.8 mm
 - Colour: Black
 - Material: PVC



8659587 14.8 x 7.8 mm

RS PRO 1M BROWN CABLE COVER IN PVC, 7.4MM INSIDE DIA.

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inside Diameter: 7.4 mm
 - Length: 1 m
 - Width: 25.4 mm
 - Internal Dimensions: 7.4 x 3.8 mm
 - Colour: Brown
 - Material: PVC



8659565 7.4 mm

RS PRO 1M BROWN CABLE COVER IN PVC, 14.8MM INSIDE DIA.

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inside Diameter: 14.8 mm
 - Length: 1 m
 - Width: 50.8 mm
 - Internal Dimensions: 14.8 mm x 7.8 mm
 - Colour: Brown
 - Material: PVC



8659574 14.8 mm

RS PRO 1M BROWN CABLE COVER IN PVC, 19 X 10.9MM INSIDE DIA.

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inside Diameter: 19 x 10.9 mm
 - Length: 1 m
 - Width: 66 mm
 - Internal Dimensions: 19 x 10.9 mm
 - Colour: Brown
 - Material: PVC



8659584 19 x 10.9 mm

RS PRO 1M GREY CABLE COVER IN PVC, 14.8MM INSIDE DIA.

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inside Diameter: 14.8 mm
 - Length: 1 m
 - Width: 50.8 mm
 - Internal Dimensions: 14.8 mm x 7.8 mm
 - Colour: Grey
 - Material: PVC



8659571 14.8 mm

RS PRO 1M GREY CABLE COVER IN PVC, 19 X 10.9MM INSIDE DIA.

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inside Diameter: 19 x 10.9 mm
 - Length: 1 m
 - Width: 66 mm
 - Internal Dimensions: 19 x 10.9 mm
 - Colour: Grey
 - Material: PVC



8659580 19 x 10.9 mm

RS PRO 1M GREY CABLE COVER IN PVC, 22MM INSIDE DIA.

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inside Diameter: 22 mm
 - Length: 1 m
 - Width: 76.2 mm
 - Internal Dimensions: 22 x 11.6 mm
 - Colour: Grey
 - Material: PVC



8659590 22 mm

RS PRO 1M GREY CABLE COVER IN PVC, 29.4MM INSIDE DIA.

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inside Diameter: 29.4 mm
 - Length: 1 m
 - Width: 101.6 mm
 - Internal Dimensions: 29.4 x 15.4 mm
 - Colour: Grey
 - Material: PVC



8659616 29.4 mm

RS PRO 1M WHITE CABLE COVER IN PVC, 19 X 10.9MM INSIDE DIA.

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inside Diameter: 19 x 10.9 mm
 - Length: 1 m
 - Width: 66 mm
 - Internal Dimensions: 19 x 10.9 mm
 - Colour: White
 - Material: PVC



8659593 19 x 10.9 mm

RS PRO 1M WHITE CABLE COVER IN PVC, 22 X 11.6MM INSIDE DIA.

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inside Diameter: 22 x 11.6 mm
 - Length: 1 m
 - Width: 76.2 mm
 - Internal Dimensions: 22 x 11.6 mm
 - Colour: White
 - Material: PVC



8659603 22 x 11.6 mm

RS PRO 1M BLACK CABLE COVER IN PVC, 19 X 10.9MM INSIDE DIA.

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inside Diameter: 19 x 10.9 mm
 - Length: 1 m
 - Internal Dimensions: 19 x 10.9 mm
 - Width: 66 mm
 - Colour: Black
 - Material: PVC



8659596 19 x 10.9 mm

RS PRO 1M BLACK CABLE COVER IN PVC, 22MM INSIDE DIA.

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inside Diameter: 22 mm
 - Length: 1 m
 - Width: 76.2 mm
 - Internal Dimensions: 22 x 11.6 mm
 - Colour: Black
 - Material: PVC



8659607 22 mm

RS PRO 1M BROWN CABLE COVER IN PVC, 29.4MM INSIDE DIA.

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inside Diameter: 29.4 mm
 - Length: 1 m
 - Width: 101.6 mm
 - Internal Dimensions: 29.4 x 15.4 mm
 - Colour: Brown
 - Material: PVC



8659619 29.4 mm

RS PRO 1M BLACK CABLE COVER IN PVC, 29.4MM INSIDE DIA.

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inside Diameter: 29.4 mm
 - Length: 1 m
 - Width: 101.6 mm
 - Internal Dimensions: 29.4 x 15.4 mm
 - Colour: Black
 - Material: PVC



8659622 29.4 mm

ABB CABLE GLAND ADAPTOR, PG16 EXTERIOR THREAD, M16 INTERIOR

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Exterior Thread Size: PG16
 - Interior Thread Size: M16
 - Material: Nylon 66
 - Type: Adaptor
 - Thread Size: PG16 → M16
 - Colour: Grey
 - Standards Met: UL 94V-2
 - Minimum Operating Temperature: -20 °C



2813296 PG16

RS PRO CABLE GLAND ADAPTOR, PG13 EXTERIOR THREAD, M16

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Exterior Thread Size: PG13
 - Interior Thread Size: M16
 - Material: Nylon 66
 - Type: Adaptor
 - Thread Size: PG13 → M16
 - Colour: Grey
 - Standards Met: UL 94V-2



8178883 PG13

RS PRO CABLE GLAND ADAPTOR, PG9 EXTERIOR THREAD, M16

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Exterior Thread Size: PG9
 - Interior Thread Size: M16
 - Material: Nylon 66
 - Type: Adaptor
 - Thread Size: PG9 → M16
 - Colour: Grey
 - Standards Met: UL 94V-2



8178886 PG9

RS PRO CABLE GLAND ADAPTOR, PG11 EXTERIOR THREAD, M16

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Exterior Thread Size: PG11
 - Interior Thread Size: M16
 - Material: Nylon 66
 - Type: Adaptor
 - Thread Size: PG11 → M16
 - Colour: Grey
 - Standards Met: UL 94V-2



8178889 PG11

RS PRO CABLE GLAND ADAPTOR, M25 X 1.5 EXTERIOR THREAD, M32 X

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Exterior Thread Size: M25 x 1.5
 - Interior Thread Size: M32 x 1.5
 - Material: Nylon 66
 - Type: Enlarger
 - Thread Size: M25 → M32
 - Colour: Grey
 - Standards Met: UL 94V-2



8229852 M25 x 1.5

RS PRO CABLE GLAND ADAPTOR, M16 X 1.5 EXTERIOR THREAD, M20 X 1.5

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Exterior Thread Size: M16 x 1.5
 - Interior Thread Size: M20 x 1.5
 - Material: Nylon 66
 - Type: Enlarger
 - Thread Size: M16 → M20
 - Colour: Grey
 - Standards Met: UL 94V-2



8229855 M16 x 1.5

RS PRO CABLE GLAND ADAPTOR, M20 X 1.5 EXTERIOR THREAD, M25 X

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Exterior Thread Size: M20 x 1.5
 - Interior Thread Size: M25 x 1.5
 - Material: Nylon 66
 - Type: Enlarger
 - Thread Size: M20 → M25
 - Colour: Grey
 - Standards Met: UL 94V-2



8229858 M20 x 1.5

RS PRO CABLE GLAND ADAPTOR, M12 X 1.5 EXTERIOR THREAD, M16 X 1.5

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Exterior Thread Size: M12 x 1.5
 - Interior Thread Size: M16 x 1.5
 - Material: Nylon 66
 - Type: Enlarger
 - Thread Size: M12 → M16
 - Colour: Black
 - Standards Met: UL 94V-2



8229861 M12 x 1.5

RS PRO CABLE GLAND ADAPTOR, M16 X 1.5 EXTERIOR THREAD, M20 X 1.5

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Exterior Thread Size: M16 x 1.5
 - Interior Thread Size: M20 x 1.5
 - Material: Nylon 66
 - Type: Enlarger
 - Thread Size: M16 → M20
 - Colour: Black
 - Standards Met: UL 94V-2



8229864 M16 x 1.5

RS PRO CABLE GLAND ADAPTOR, M25 X 1.5 EXTERIOR THREAD, M20 X 1.5

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Exterior Thread Size: M25 x 1.5
 - Interior Thread Size: M20 x 1.5
 - Material: Nylon 66
 - Type: Enlarger
 - Thread Size: M25 → M20
 - Colour: Black
 - Standards Met: UL 94V-2



8229868 M25 x 1.5

RS PRO CABLE GLAND ADAPTOR, M16 X 1.5 EXTERIOR THREAD, M12 X 1.5

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Exterior Thread Size: M16 x 1.5
 - Interior Thread Size: M12 x 1.5
 - Material: Nylon 66
 - Type: Reducer
 - Thread Size: M16 → M12
 - Colour: Black
 - Standards Met: UL 94V-2



8229870 M16 x 1.5

RS PRO CABLE GLAND ADAPTOR, M20 X 1.5 EXTERIOR THREAD, M16 X 1.5

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Exterior Thread Size: M20 x 1.5
 - Interior Thread Size: M16 x 1.5
 - Material: Nylon 66
 - Type: Reducer
 - Thread Size: M20 → M16
 - Colour: Black
 - Standards Met: UL 94V-2



8229874 M20 x 1.5

RS PRO CABLE GLAND ADAPTOR, M25 X 1.5 EXTERIOR THREAD, M32 X 1.5

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Exterior Thread Size: M25 x 1.5
 - Interior Thread Size: M32 x 1.5
 - Material: Nylon 66
 - Type: Enlarger
 - Thread Size: M25 → M32
 - Colour: Black
 - Standards Met: UL 94V-2



8229877 M25 x 1.5

RS PRO CABLE GLAND ADAPTOR, M16 X 1.5 EXTERIOR THREAD, M12 X 1.5

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Exterior Thread Size: M16 x 1.5
 - Interior Thread Size: M12 x 1.5
 - Material: Nylon 66
 - Type: Reducer
 - Thread Size: M16 → M12
 - Colour: Grey
 - Standards Met: UL 94V-2



8229880 M16 x 1.5

RS PRO CABLE GLAND ADAPTOR, M25 X 1.5 EXTERIOR THREAD, M20 X 1.5

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Exterior Thread Size: M25 x 1.5
 - Interior Thread Size: M20 x 1.5
 - Material: Nylon 66
 - Type: Reducer
 - Thread Size: M25 → M20
 - Colour: Black
 - Standards Met: UL 94V-2



8229883 M25 x 1.5

RS PRO CABLE GLAND ADAPTOR, M32 X 1.5 EXTERIOR THREAD, M25 X 1.5

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Exterior Thread Size: M32 x 1.5
 - Interior Thread Size: M25 x 1.5
 - Material: Nylon 66
 - Type: Reducer
 - Thread Size: M32 → M25
 - Colour: Black
 - Standards Met: UL 94V-2



8229886 M32 x 1.5

RS PRO CABLE GLAND ADAPTOR, M25 X 1.5 EXTERIOR THREAD, M20 X 1.5

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Exterior Thread Size: M25 x 1.5
 - Interior Thread Size: M20 x 1.5
 - Material: Nylon 66
 - Type: Reducer
 - Thread Size: M25 → M20
 - Colour: Grey
 - Standards Met: UL 94V-2



8229892 M25 x 1.5

RS PRO CABLE GLAND ADAPTOR, M32 X 1.5 EXTERIOR THREAD, M25 X 1.5

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Exterior Thread Size: M32 x 1.5
 - Interior Thread Size: M25 x 1.5
 - Material: Nylon 66
 - Type: Reducer
 - Thread Size: M32 → M25
 - Colour: Grey
 - Standards Met: UL 94V-2



8229896 M32 x 1.5

RS PRO CABLE GLAND ADAPTOR, M20 X 1.5 EXTERIOR THREAD, M16 X 1.5

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Exterior Thread Size: M20 x 1.5
 - Interior Thread Size: M16 x 1.5
 - Material: Nylon 66
 - Type: Reducer
 - Thread Size: M20 → M16
 - Colour: Grey
 - Standards Met: UL 94V-2



8229899 M20 x 1.5

RS PRO GREY NYLON 66 CABLE GLAND LOCKNUT, PG13.5 THREAD,

- ขนาดบรรจุภัณฑ์: **25 x EA**
- Material: Nylon 66
 - Thread Size: PG13.5
 - Colour: Grey
 - IP Rating: IP68



8229704 Nylon 66

RS PRO BLACK NYLON 66 CABLE GLAND LOCKNUT, PG9 THREAD, IP68

- ขนาดบรรจุภัณฑ์: **25 x EA**
- Material: Nylon 66
 - Thread Size: PG9
 - Colour: Black
 - IP Rating: IP68



8229717 Nylon 66

RS PRO BLACK NYLON 66 CABLE GLAND LOCKNUT, PG13.5 THREAD,

- ขนาดบรรจุภัณฑ์: **25 x EA**
- Material: Nylon 66
 - Thread Size: PG13.5
 - Colour: Black
 - IP Rating: IP68



8229729 Nylon 66

RS PRO BLACK NYLON 66 CABLE GLAND LOCKNUT, PG21 THREAD, IP68

- ขนาดบรรจุภัณฑ์: **25 x EA**
- Material: Nylon 66
 - Thread Size: PG21
 - Colour: Black
 - IP Rating: IP68



8229732 Nylon 66

RS PRO BLACK NYLON 66 CABLE GLAND LOCKNUT, PG29 THREAD,

- ขนาดบรรจุภัณฑ์: 25 x EA
- Material: Nylon 66
 - Thread Size: PG29
 - Colour: Black
 - IP Rating: IP68



8229735 Nylon 66

M12 X 1.5 GREY LOCKNUT IP68

- ขนาดบรรจุภัณฑ์: 25 x EA
- Material: Nylon 66
 - Thread Size: M12
 - Colour: Grey
 - IP Rating: IP68



8229791 Nylon 66

M16 X 1.5 GREY LOCKNUT IP68

- ขนาดบรรจุภัณฑ์: 25 x EA
- Material: Nylon 66
 - Thread Size: M16
 - Colour: Grey
 - IP Rating: IP68



8229795 Nylon 66

M32 X 1.5 GREY LOCKNUT IP68

- ขนาดบรรจุภัณฑ์: 25 x EA
- Material: Nylon 66
 - Thread Size: M32
 - Colour: Grey
 - IP Rating: IP68



8229802 Nylon 66

M20 X 1.5 GREY LOCKNUT IP68

- ขนาดบรรจุภัณฑ์: 25 x EA
- Material: Nylon 66
 - Thread Size: M20
 - Colour: Grey
 - IP Rating: IP68



8229805 Nylon 66

M25 X 1.5 GREY LOCKNUT IP68

- ขนาดบรรจุภัณฑ์: 25 x EA
- Material: Nylon 66
 - Thread Size: M25
 - Colour: Grey
 - IP Rating: IP68



8229808 Nylon 66

M16 X 1.5 WHITE LOCKNUT IP68

- ขนาดบรรจุภัณฑ์: 25 x EA
- Material: Nylon 66
 - Thread Size: M16
 - Colour: White
 - IP Rating: IP68



8229811 Nylon 66

M20 X 1.5 WHITE LOCKNUT IP68

- ขนาดบรรจุภัณฑ์: 25 x EA
- Material: Nylon 66
 - Thread Size: M20
 - Colour: White
 - IP Rating: IP68



8229814 Nylon 66

RS PRO WHITE NYLON 66 CABLE GLAND LOCKNUT, M25 THREAD, IP68

- ขนาดบรรจุภัณฑ์: 25 x EA
- Material: Nylon 66
 - Thread Size: M25
 - Colour: White
 - IP Rating: IP68



8229818 Nylon 66

RS PRO RED NYLON 66 CABLE GLAND LOCKNUT, M20 THREAD, IP68

- ขนาดบรรจุภัณฑ์: 25 x EA
- Material: Nylon 66
 - Thread Size: M20
 - Colour: Red
 - IP Rating: IP68



8229820 Nylon 66

RS PRO RED NYLON 66 CABLE GLAND LOCKNUT, M25 THREAD, IP68

- ขนาดบรรจุภัณฑ์: 25 x EA
- Material: Nylon 66
 - Thread Size: M25
 - Colour: Red
 - IP Rating: IP68



8229824 Nylon 66

M20 X 1.5 BLACK LOCKNUT IP68

- ขนาดบรรจุภัณฑ์: 25 x EA
- Material: Nylon 66
 - Thread Size: M20
 - Colour: Black
 - IP Rating: IP68



8229830 Nylon 66

M12 X 1.5 BLACK LOCKNUT IP68

- ขนาดบรรจุภัณฑ์: 25 x EA
- Material: Nylon 66
 - Thread Size: M12
 - Colour: Black
 - IP Rating: IP68



8229833 Nylon 66

RS PRO BLACK NYLON 66 CABLE GLAND LOCKNUT, M16 THREAD, IP68

- ขนาดบรรจุภัณฑ์: 25 x EA
- Material: Nylon 66
 - Thread Size: M16
 - Colour: Black
 - IP Rating: IP68



8229836 Nylon 66

RS PRO BLACK NYLON 66 CABLE GLAND LOCKNUT, M32 THREAD, IP68

- ขนาดบรรจุภัณฑ์: 25 x EA
- Material: Nylon 66
 - Thread Size: M32
 - Colour: Black
 - IP Rating: IP68



8229842 Nylon 66

M25 X 1.5 BLACK LOCKNUT IP68

- ขนาดบรรจุภัณฑ์: 25 x EA
- Material: Nylon 66
 - Thread Size: M25
 - Colour: Black
 - IP Rating: IP68



8229849 Nylon 66

**RS PRO BLANKING PLUG, M12,
12.2MM HOLE DIAMETER, NICKEL**

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Thread Size: M12
 - Hole Diameter: 12.2 mm
 - Material: Nickel Plated Brass
 - Plug Type: Blanking
 - Threaded/Unthreaded: Threaded
 - Hazardous Area Certification: ATEX
 - IP Rating: IP68
 - Series: Ex-HSPM



2116788 M12

**RS PRO BLANKING PLUG, M16,
16.2MM HOLE DIAMETER, NICKEL**

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Thread Size: M16
 - Hole Diameter: 16.2 mm
 - Material: Nickel Plated Brass
 - Plug Type: Blanking
 - Threaded/Unthreaded: Threaded
 - Hazardous Area Certification: ATEX
 - IP Rating: IP68
 - Series: Ex-HSPM



2116789 M16

**RS PRO BLANKING PLUG, M20,
20.2MM HOLE DIAMETER, NICKEL**

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Thread Size: M20
 - Hole Diameter: 20.2 mm
 - Material: Nickel Plated Brass
 - Plug Type: Blanking
 - Threaded/Unthreaded: Threaded
 - Hazardous Area Certification: ATEX
 - IP Rating: IP68
 - Series: Ex-HSPM



2116790 M20

**RS PRO BLANKING PLUG, M25,
25.2MM HOLE DIAMETER, NICKEL**

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Thread Size: M25
 - Hole Diameter: 25.2 mm
 - Material: Nickel Plated Brass
 - Plug Type: Blanking
 - Threaded/Unthreaded: Threaded
 - Hazardous Area Certification: ATEX
 - IP Rating: IP68
 - Series: Ex-HSPM



2116791 M25

**RS PRO BLANKING PLUG, M32,
32.2MM HOLE DIAMETER, NICKEL**

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Thread Size: M32
 - Hole Diameter: 32.2 mm
 - Material: Nickel Plated Brass
 - Plug Type: Blanking
 - Threaded/Unthreaded: Threaded
 - Hazardous Area Certification: ATEX
 - IP Rating: IP68
 - Series: Ex-HSPM



2116792 M32

**RS PRO STOPPING PLUG, M20,
20.2MM HOLE DIAMETER, THREADED**

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Thread Size: M20
 - Hole Diameter: 20.2 mm
 - Plug Type: Stopping
 - Threaded/Unthreaded: Threaded
 - Hazardous Area Certification: ATEX
 - IP Rating: IP68
 - Series: Ex-SPM



2116793 M20

**RS PRO STOPPING PLUG, M25,
25.2MM HOLE DIAMETER, THREADED**

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Thread Size: M25
 - Hole Diameter: 25.2 mm
 - Plug Type: Stopping
 - Threaded/Unthreaded: Threaded
 - Hazardous Area Certification: ATEX
 - IP Rating: IP68
 - Series: Ex-SPM



2116794 M25

**RS PRO STOPPING PLUG, M40,
40.2MM HOLE DIAMETER, THREADED**

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Thread Size: M40
 - Hole Diameter: 40.2 mm
 - Plug Type: Stopping
 - Threaded/Unthreaded: Threaded
 - Hazardous Area Certification: ATEX
 - IP Rating: IP68
 - Series: Ex-SPM



2116795 M40

**RS PRO BLANKING PLUG, 19.1MM
HOLE DIAMETER, NYLON 66, 22.9MM**

- ขนาดบรรจุภัณฑ์: **25 x EA**
- Hole Diameter: 19.1 mm
 - Material: Nylon 66
 - Plug Type: Blanking
 - Diameter: 22.9 mm
 - Threaded/Unthreaded: Unthreaded
 - Colour: Black
 - Series: 81788
 - Standards Met: UL 94V-2



8178845 19.1 mm

**RS PRO BLANKING PLUG, 5MM HOLE
DIAMETER, NYLON 66, 6.3MM**

- ขนาดบรรจุภัณฑ์: **25 x EA**
- Hole Diameter: 5 mm
 - Material: Nylon 66
 - Plug Type: Blanking
 - Diameter: 6.3 mm
 - Threaded/Unthreaded: Unthreaded
 - Colour: Black
 - Series: 81788
 - Standards Met: UL 94V-2



8178849 5 mm

**RS PRO BLANKING PLUG, 9.5MM
HOLE DIAMETER, NYLON 66, 13MM**

- ขนาดบรรจุภัณฑ์: **25 x EA**
- Hole Diameter: 9.5 mm
 - Material: Nylon 66
 - Plug Type: Blanking
 - Diameter: 13 mm
 - Threaded/Unthreaded: Unthreaded
 - Colour: Black
 - Series: 81788
 - Standards Met: UL 94V-2



8178851 9.5 mm

**RS PRO BLANKING PLUG, 12.7MM
HOLE DIAMETER, NYLON 66, 14.5MM**

- ขนาดบรรจุภัณฑ์: **25 x EA**
- Hole Diameter: 12.7 mm
 - Material: Nylon 66
 - Plug Type: Blanking
 - Diameter: 14.5 mm
 - Threaded/Unthreaded: Unthreaded
 - Colour: Black
 - Series: 81788
 - Standards Met: UL 94V-2



8178855 12.7 mm

**RS PRO BLANKING PLUG, 6MM HOLE
DIAMETER, NYLON 66, 7.8MM**

- ขนาดบรรจุภัณฑ์: **25 x EA**
- Hole Diameter: 6 mm
 - Material: Nylon 66
 - Plug Type: Blanking
 - Diameter: 7.8 mm
 - Threaded/Unthreaded: Unthreaded
 - Colour: Black
 - Series: 81788
 - Standards Met: UL 94V-2



8178858 6 mm

**RS PRO BLANKING PLUG, 15.9MM
HOLE DIAMETER, NYLON 66, 19.5MM**

- ขนาดบรรจุภัณฑ์: **25 x EA**
- Hole Diameter: 15.9 mm
 - Material: Nylon 66
 - Plug Type: Blanking
 - Diameter: 19.5 mm
 - Threaded/Unthreaded: Unthreaded
 - Colour: Black
 - Series: 81788
 - Standards Met: UL 94V-2



8178864 15.9 mm

**RS PRO BLANKING PLUG, 25.4MM
HOLE DIAMETER, NYLON 66, 29MM**

- ขนาดบรรจุภัณฑ์: **25 x EA**
- Hole Diameter: 25.4 mm
 - Material: Nylon 66
 - Plug Type: Blanking
 - Diameter: 29 mm
 - Threaded/Unthreaded: Unthreaded
 - Colour: Black
 - Series: 81788
 - Standards Met: UL 94V-2



8178867 25.4 mm

**RS PRO BLANKING PLUG, M20 X 1.5,
19.9MM HOLE DIAMETER,**

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Thread Size: M20 x 1.5
 - Hole Diameter: 19.9 mm
 - Material: Nylon 66
 - Plug Type: Blanking
 - Diameter: 24 mm
 - Threaded/Unthreaded: Threaded
 - Colour: Black
 - Series: 86597



8659742 M20 x 1.5

RS PRO BLANKING BLANKING PLUG, M12 X 1.5, 11.7MM HOLE DIAMETER,

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Thread Size: M12 x 1.5
 - Hole Diameter: 11.7 mm
 - Material: Nylon 66
 - Plug Type: Blanking
 - Diameter: 15 mm
 - Threaded/Unthreaded: Threaded
 - Colour: Black
 - Series: 86597



8659745 M12 x 1.5

RS PRO BLANKING BLANKING PLUG, M16 X 1.5, 15.7MM HOLE DIAMETER,

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Thread Size: M16 x 1.5
 - Hole Diameter: 15.7 mm
 - Material: Nylon 66
 - Plug Type: Blanking
 - Diameter: 20 mm
 - Threaded/Unthreaded: Threaded
 - Colour: Black
 - Series: 86597



8659748 M16 x 1.5

RS PRO BLANKING BLANKING PLUG, M25 X 1.5, 24.7MM HOLE DIAMETER,

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Thread Size: M25 x 1.5
 - Hole Diameter: 24.7 mm
 - Material: Nylon 66
 - Plug Type: Blanking
 - Diameter: 29.7 mm
 - Threaded/Unthreaded: Threaded
 - Colour: Black
 - Series: 86597



8659751 M25 x 1.5

RS PRO BLANKING BLANKING PLUG, M32 X 1.5, 31.7MM HOLE DIAMETER,

- ขนาดบรรจุภัณฑ์: **50 x EA**
- Thread Size: M32 x 1.5
 - Hole Diameter: 31.7 mm
 - Material: Nylon 66
 - Plug Type: Blanking
 - Diameter: 36.6 mm
 - Threaded/Unthreaded: Threaded
 - Colour: Black
 - Series: 86597



8659754 M32 x 1.5

RS PRO BLANKING BLANKING PLUG, M40 X 1.5, 39.9MM HOLE DIAMETER,

- ขนาดบรรจุภัณฑ์: **50 x EA**
- Thread Size: M40 x 1.5
 - Hole Diameter: 39.9 mm
 - Material: Nylon 66
 - Plug Type: Blanking
 - Diameter: 45.8 mm
 - Threaded/Unthreaded: Threaded
 - Colour: Black
 - Series: 86597



8659758 M40 x 1.5

RS PRO BLANKING BLANKING PLUG, M63 X 1.5, 62.4MM HOLE DIAMETER,

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Thread Size: M63 x 1.5
 - Hole Diameter: 62.4 mm
 - Material: Nylon 66
 - Plug Type: Blanking
 - Diameter: 69.3 mm
 - Threaded/Unthreaded: Threaded
 - Colour: Black
 - Series: 86597



8659760 M63 x 1.5

RS PRO BLANKING BLANKING PLUG, M12 X 1.5, 11.7MM HOLE DIAMETER,

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Thread Size: M12 x 1.5
 - Hole Diameter: 11.7 mm
 - Material: Nylon 66
 - Plug Type: Blanking
 - Diameter: 15 mm
 - Threaded/Unthreaded: Threaded
 - Colour: Grey
 - Series: 86597



8659764 M12 x 1.5

RS PRO BLANKING BLANKING PLUG, M50 X 1.5, 49.9MM HOLE DIAMETER,

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Thread Size: M50 x 1.5
 - Hole Diameter: 49.9 mm
 - Material: Nylon 66
 - Plug Type: Blanking
 - Diameter: 55.5 mm
 - Threaded/Unthreaded: Threaded
 - Colour: Black
 - Series: 86597



8659767 M50 x 1.5

RS PRO BLANKING BLANKING PLUG, M25 X 1.5, 24.7MM HOLE DIAMETER,

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Thread Size: M25 x 1.5
 - Hole Diameter: 24.7 mm
 - Material: Nylon 66
 - Plug Type: Blanking
 - Diameter: 29.7 mm
 - Threaded/Unthreaded: Threaded
 - Colour: Grey
 - Series: 86597



8659770 M25 x 1.5

RS PRO BLANKING BLANKING PLUG, M16 X 1.5, 15.7MM HOLE DIAMETER,

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Thread Size: M16 x 1.5
 - Hole Diameter: 15.7 mm
 - Material: Nylon 66
 - Plug Type: Blanking
 - Diameter: 20 mm
 - Threaded/Unthreaded: Threaded
 - Colour: Grey
 - Series: 86597



8659773 M16 x 1.5

RS PRO BLANKING BLANKING PLUG, M20 X 1.5, 19.9MM HOLE DIAMETER,

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Thread Size: M20 x 1.5
 - Hole Diameter: 19.9 mm
 - Material: Nylon 66
 - Plug Type: Blanking
 - Diameter: 24 mm
 - Threaded/Unthreaded: Threaded
 - Colour: Grey
 - Series: 86597



8659776 M20 x 1.5

RS PRO BLANKING BLANKING PLUG, M40 X 1.5, 39.9MM HOLE DIAMETER,

- ขนาดบรรจุภัณฑ์: **50 x EA**
- Thread Size: M40 x 1.5
 - Hole Diameter: 39.9 mm
 - Material: Nylon 66
 - Plug Type: Blanking
 - Diameter: 45.8 mm
 - Threaded/Unthreaded: Threaded
 - Colour: Grey
 - Series: 86597



8659782 M40 x 1.5

RS PRO BLANKING BLANKING PLUG, M50 X 1.5, 49.9MM HOLE DIAMETER,

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Thread Size: M50 x 1.5
 - Hole Diameter: 49.9 mm
 - Material: Nylon 66
 - Plug Type: Blanking
 - Diameter: 55.5 mm
 - Threaded/Unthreaded: Threaded
 - Colour: Grey
 - Series: 86597



8659786 M50 x 1.5

RS PRO BLANKING BLANKING PLUG, M32 X 1.5, 31.7MM HOLE DIAMETER,

- ขนาดบรรจุภัณฑ์: **50 x EA**
- Thread Size: M32 x 1.5
 - Hole Diameter: 31.7 mm
 - Material: Nylon 66
 - Plug Type: Blanking
 - Diameter: 36.6 mm
 - Threaded/Unthreaded: Threaded
 - Colour: Grey
 - Series: 86597



8659789 M32 x 1.5

RS PRO BLANKING BLANKING PLUG, 12.7MM HOLE DIAMETER, NYLON 66,

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Hole Diameter: 12.7 mm
 - Material: Nylon 66
 - Plug Type: Blanking
 - Diameter: 16.5 mm
 - Threaded/Unthreaded: Unthreaded
 - Colour: Black
 - For Use With: Chassis Thickness Under 3.2 mm
 - Series: 86597



8659792 12.7 mm

RS PRO BLANKING BLANKING PLUG, M63 X 1.5, 62.4MM HOLE DIAMETER,

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Thread Size: M63 x 1.5
 - Hole Diameter: 62.4 mm
 - Material: Nylon 66
 - Plug Type: Blanking
 - Diameter: 69.3 mm
 - Threaded/Unthreaded: Threaded
 - Colour: Grey
 - Series: 86597



8659795 M63 x 1.5

RS PRO BLANKING BLANKING PLUG, 7.9MM HOLE DIAMETER, NYLON 66,

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Hole Diameter: 7.9 mm
 - Material: Nylon 66
 - Plug Type: Blanking
 - Diameter: 10.3 mm
 - Threaded/Unthreaded: Unthreaded
 - Colour: Black
 - For Use With: Chassis Thickness Under 3.2 mm
 - Series: 86597



8659798 7.9 mm

RS PRO BLANKING BLANKING PLUG, 14.3MM HOLE DIAMETER, NYLON 66,

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Hole Diameter: 14.3 mm
 - Material: Nylon 66
 - Plug Type: Blanking
 - Diameter: 16.7 mm
 - Threaded/Unthreaded: Unthreaded
 - Colour: Black
 - For Use With: Chassis Thickness Under 3.2 mm
 - Series: 86598



8659802 14.3 mm

RS PRO BLANKING BLANKING PLUG, 22.2MM HOLE DIAMETER, NYLON 66,

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Hole Diameter: 22.2 mm
 - Material: Nylon 66
 - Plug Type: Blanking
 - Diameter: 25.8 mm
 - Threaded/Unthreaded: Unthreaded
 - Colour: Black
 - For Use With: Chassis Thickness Under 3.2 mm
 - Series: 86598



8659805 22.2 mm

RS PRO BLANKING BLANKING PLUG, 30.1MM HOLE DIAMETER, NYLON 66,

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Hole Diameter: 30.1 mm
 - Material: Nylon 66
 - Plug Type: Blanking
 - Diameter: 34.2 mm
 - Threaded/Unthreaded: Unthreaded
 - Colour: Black
 - For Use With: Chassis Thickness Under 3.2 mm
 - Series: 86598



8659809 30.1 mm

RS PRO BLANKING BLANKING PLUG, 44.5MM HOLE DIAMETER, NYLON 66,

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Hole Diameter: 44.5 mm
 - Material: Nylon 66
 - Plug Type: Blanking
 - Diameter: 49.7 mm
 - Threaded/Unthreaded: Unthreaded
 - Colour: Black
 - For Use With: Chassis Thickness Under 3.2 mm
 - Series: 86598



8659811 44.5 mm

RS PRO BLACK PLASTIC CABLE GLAND, M20 THREAD, 4MM MIN, 7MM

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Hole Diameter: 38.1 mm
 - Material: Nylon 66
 - Plug Type: Blanking
 - Diameter: 42.1 mm
 - Threaded/Unthreaded: Unthreaded
 - Colour: Black
 - For Use With: Chassis Thickness Under 3.2 mm
 - Series: 86598



8659818 38.1 mm

RS PRO BLACK PLASTIC CABLE GLAND, M20 THREAD, 4MM MIN, 7MM

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Thread Size: M20
 - Maximum Cable Diameter: 7 mm
 - Minimum Cable Diameter: 4 mm
 - Material: Plastic
 - Colour: Black
 - IP Rating: IP55
 - Locknut Included: Yes
 - Fire Behaviour: Low Smoke & Fume (LSF)



127170 M20

RS PRO BLACK PLASTIC CABLE GLAND, M16 THREAD, 7MM MIN,

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Thread Size: M16
 - Maximum Cable Diameter: 10.5 mm
 - Minimum Cable Diameter: 7 mm
 - Material: Plastic
 - Colour: Black
 - IP Rating: IP55
 - Locknut Included: Yes
 - Fire Behaviour: Low Smoke & Fume (LSF)



127209 M16

RS PRO BLACK PLASTIC CABLE GLAND, M20 THREAD, 8MM MIN,

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Thread Size: M20
 - Maximum Cable Diameter: 13 mm
 - Minimum Cable Diameter: 8 mm
 - Material: Plastic
 - Colour: Black
 - IP Rating: IP55
 - Locknut Included: Yes
 - Fire Behaviour: Low Smoke & Fume (LSF)



127215 M20

RS PRO BLACK PLASTIC CABLE GLAND, M20 THREAD, 8MM MIN,

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Thread Size: M20
 - Maximum Cable Diameter: 13 mm
 - Minimum Cable Diameter: 8 mm
 - Material: Plastic
 - Colour: Black
 - IP Rating: IP55
 - Locknut Included: Yes
 - Fire Behaviour: Low Smoke & Fume (LSF)



127221 M20

RS PRO WHITE PLASTIC CABLE GLAND, M20 THREAD, 4MM MIN, 7MM

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Thread Size: M20
 - Maximum Cable Diameter: 7 mm
 - Minimum Cable Diameter: 4 mm
 - Material: Plastic
 - Colour: White
 - IP Rating: IP55
 - Locknut Included: Yes
 - Minimum Operating Temperature: -20 °C



127338 M20

HEX,HEAD,NYLON,CABLE,GLAND,IP55,WHITE,M16,7-10.5MM

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Thread Size: M16
 - Maximum Cable Diameter: 10.5 mm
 - Minimum Cable Diameter: 7 mm
 - Material: Plastic
 - Colour: White
 - IP Rating: IP55
 - Locknut Included: Yes
 - Minimum Operating Temperature: -20 °C



127344 M16

RS PRO WHITE PLASTIC CABLE GLAND, M20 THREAD, 4MM MIN, 7MM

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Thread Size: M20
 - Maximum Cable Diameter: 7 mm
 - Minimum Cable Diameter: 4 mm
 - Material: Plastic
 - Colour: White
 - IP Rating: IP55
 - Locknut Included: Yes
 - Fire Behaviour: Low Smoke & Fume (LSF)



127372 M20

RS PRO WHITE PLASTIC CABLE GLAND, M20 THREAD, 8MM MIN,

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Thread Size: M20
 - Maximum Cable Diameter: 13 mm
 - Minimum Cable Diameter: 8 mm
 - Material: Plastic
 - Colour: White
 - IP Rating: IP55
 - Locknut Included: Yes
 - Minimum Operating Temperature: -20 °C



127401 M20

RS PRO BLACK PLASTIC CABLE GLAND, M20 THREAD, 7MM MIN,

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Thread Size: M20
 - Maximum Cable Diameter: 10.5 mm
 - Minimum Cable Diameter: 7 mm
 - Material: Plastic
 - Colour: Black
 - IP Rating: IP55
 - Locknut Included: Yes
 - Fire Behaviour: Low Smoke & Fume (LSF)



127619 M20

RS PRO BLACK PLASTIC CABLE GLAND, M20 THREAD, 7MM MIN,

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Thread Size: M20
 - Maximum Cable Diameter: 10.5 mm
 - Minimum Cable Diameter: 7 mm
 - Material: Plastic
 - Colour: Black
 - IP Rating: IP55
 - Locknut Included: Yes
 - Fire Behaviour: Low Smoke & Fume (LSF)



127631 M20

RS PRO BLACK PLASTIC CABLE GLAND, M20 THREAD, 4MM MIN, 7MM

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Thread Size: M20
 - Maximum Cable Diameter: 7 mm
 - Minimum Cable Diameter: 4 mm
 - Material: Plastic
 - Colour: Black
 - IP Rating: IP55
 - Locknut Included: Yes
 - Fire Behaviour: Low Smoke & Fume (LSF)



127647 M20

RS PRO BLACK NYLON CABLE GLAND KIT, M5 THREAD, IP66

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thread Size: M5
 - Material: Nylon 66
 - Colour: Black
 - IP Rating: IP66
 - Locknut Included: No
 - Fire Behaviour: Halogen Free
 - Maximum Operating Temperature: +120 °C
 - Minimum Operating Temperature: -40 °C



1856068 M5

RS PRO BLACK NYLON CABLE GLAND KIT, M5 THREAD, IP66


- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thread Size: M5
 - Material: Nylon 66
 - Colour: Black
 - IP Rating: IP66
 - Locknut Included: No
 - Fire Behaviour: Halogen Free, Self-extinguishing
 - Maximum Operating Temperature: +120 °C
 - Minimum Operating Temperature: -40 °C



1856069 M5

RS PRO BLACK NYLON CABLE GLAND KIT, M5 THREAD, IP66

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thread Size: M5
 - Material: Nylon 66
 - Colour: Black
 - IP Rating: IP66
 - Locknut Included: No
 - Fire Behaviour: Halogen Free, Self-extinguishing
 - Maximum Operating Temperature: +120 °C
 - Minimum Operating Temperature: -40 °C



1856070 M5

RS PRO BLACK NYLON CABLE GLAND KIT, M5 THREAD, IP66

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thread Size: M5
 - Material: Nylon 66
 - Colour: Black
 - IP Rating: IP66
 - Locknut Included: No
 - Fire Behaviour: Halogen Free, Self-extinguishing
 - Maximum Operating Temperature: +120 °C
 - Minimum Operating Temperature: -40 °C



1856071 M5

RS PRO GREY CABLE GLAND KIT, IP66

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Colour: Grey
 - IP Rating: IP66
 - Locknut Included: No
 - Number of Pieces: 10
 - Standards Met: RoHS Compliant
 - Kit Includes: Seal Dummy



1856072 Grey

RS PRO GREY CABLE GLAND KIT, 2MM MAX, IP66

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Maximum Cable Diameter: 2 mm
 - Colour: Grey
 - IP Rating: IP66
 - Locknut Included: No
 - Number of Pieces: 10
 - Standards Met: RoHS Compliant
 - Kit Includes: Seal



1856073 2 mm

RS PRO GREY CABLE GLAND KIT, 4MM MAX, IP66

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Maximum Cable Diameter: 4 mm
 - Colour: Grey
 - IP Rating: IP66
 - Locknut Included: No
 - Number of Pieces: 10
 - Standards Met: RoHS Compliant
 - Kit Includes: Seal



1856074 4 mm

RS PRO GREY CABLE GLAND KIT, 6MM MAX, IP66

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Maximum Cable Diameter: 6 mm
 - Colour: Grey
 - IP Rating: IP66
 - Locknut Included: No
 - Number of Pieces: 10
 - Standards Met: RoHS Compliant
 - Kit Includes: Seal



1856075 6 mm

RS PRO GREY TPE CABLE GLAND KIT, 7MM MIN, 8MM MAX, IP66

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Maximum Cable Diameter: 8 mm
 - Minimum Cable Diameter: 7 mm
 - Material: TPE
 - Colour: Grey
 - IP Rating: IP66
 - Locknut Included: No
 - Maximum Operating Temperature: +90 °C
 - Minimum Operating Temperature: -40 °C



1856076 8 mm

RS PRO GREY TPE CABLE GLAND KIT, 9MM MIN, 10MM MAX, IP66

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Maximum Cable Diameter: 10 mm
 - Minimum Cable Diameter: 9 mm
 - Material: TPE
 - Colour: Grey
 - IP Rating: IP66
 - Locknut Included: No
 - Maximum Operating Temperature: +90 °C
 - Minimum Operating Temperature: -40 °C



1856077 10 mm

RS PRO GREY CABLE GLAND KIT, 12MM MAX, IP66

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Maximum Cable Diameter: 12 mm
 - Colour: Grey
 - IP Rating: IP66
 - Locknut Included: No
 - Number of Pieces: 10
 - Standards Met: RoHS Compliant
 - Kit Includes: Seal



1856079 12 mm

RS PRO GREY CABLE GLAND KIT, 14MM MAX, IP66

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Maximum Cable Diameter: 14 mm
 - Colour: Grey
 - IP Rating: IP66
 - Locknut Included: No
 - Number of Pieces: 10
 - Standards Met: RoHS Compliant
 - Kit Includes: Seal



1856080 14 mm

RS PRO GREY CABLE GLAND KIT, 5MM MAX, IP66

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Maximum Cable Diameter: 5 mm
 - Colour: Grey
 - IP Rating: IP66
 - Locknut Included: No
 - Number of Pieces: 10
 - Standards Met: RoHS Compliant
 - Kit Includes: Seal



1856082 5 mm

RS PRO GREY CABLE GLAND KIT, 6MM MAX, IP66

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Maximum Cable Diameter: 6 mm
 - Colour: Grey
 - IP Rating: IP66
 - Locknut Included: No
 - Number of Pieces: 10
 - Standards Met: RoHS Compliant
 - Kit Includes: Seal



1856083 6 mm

RS PRO GREY CABLE GLAND KIT, 3MM MAX, IP66

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Maximum Cable Diameter: 3 mm
 - Colour: Grey
 - IP Rating: IP66
 - Locknut Included: No
 - Number of Pieces: 10
 - Standards Met: RoHS Compliant
 - Kit Includes: Seal



1856085 3 mm

RS PRO GREY CABLE GLAND KIT, 4MM MAX, IP66

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Maximum Cable Diameter: 4 mm
 - Colour: Grey
 - IP Rating: IP66
 - Locknut Included: No
 - Number of Pieces: 10
 - Standards Met: RoHS Compliant
 - Kit Includes: Seal



1856086 4 mm

RS PRO GREY CABLE GLAND KIT, 4.5MM MAX, IP66

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Maximum Cable Diameter: 4.5 mm
 - Colour: Grey
 - IP Rating: IP66
 - Locknut Included: No
 - Number of Pieces: 10
 - Standards Met: RoHS Compliant
 - Kit Includes: Seal



1856087 4.5 mm

RS PRO GREY CABLE GLAND KIT, 6.5MM MAX, IP66

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Maximum Cable Diameter: 6.5 mm
 - Colour: Grey
 - IP Rating: IP66
 - Locknut Included: No
 - Number of Pieces: 10
 - Standards Met: RoHS Compliant
 - Kit Includes: Seal



1856088 6.5 mm

RS PRO GREY CABLE GLAND KIT, IP66

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Colour: Grey
 - IP Rating: IP66
 - Locknut Included: No
 - Number of Pieces: 10
 - Standards Met: RoHS Compliant
 - Kit Includes: Seal Dummy



1856089 Grey

RS PRO GREY CABLE GLAND KIT, 16MM MAX, IP66

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Maximum Cable Diameter: 16 mm
 - Colour: Grey
 - IP Rating: IP66
 - Locknut Included: No
 - Number of Pieces: 10
 - Standards Met: RoHS Compliant
 - Kit Includes: Seal



1856091 16 mm

RS PRO BLACK NYLON CABLE GLAND KIT, M20 THREAD, IP66

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Thread Size: M20
 - Material: Nylon 66
 - Colour: Black
 - IP Rating: IP66
 - Locknut Included: Yes
 - Fire Behaviour: Halogen Free, Self-extinguishing
 - Maximum Operating Temperature: +120 °C
 - Minimum Operating Temperature: -40 °C



1856101 M20

RS PRO BLACK NYLON CABLE GLAND KIT, M25 THREAD, IP66

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Thread Size: M25
 - Material: Nylon 66
 - Colour: Black
 - IP Rating: IP66
 - Locknut Included: No
 - Fire Behaviour: Halogen Free, Self-extinguishing
 - Maximum Operating Temperature: +120 °C
 - Minimum Operating Temperature: -40 °C



1856102 M25

RS PRO BLACK NYLON CABLE GLAND KIT, M32 THREAD, IP66

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Thread Size: M32
 - Material: Nylon 66
 - Colour: Black
 - IP Rating: IP66
 - Locknut Included: No
 - Fire Behaviour: Halogen Free, Self-extinguishing
 - Maximum Operating Temperature: +120 °C
 - Minimum Operating Temperature: -40 °C



1856103 M32

RS PRO BLACK NYLON CABLE GLAND KIT, M50 THREAD, IP66

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Thread Size: M50
 - Material: Nylon 66
 - Colour: Black
 - IP Rating: IP66
 - Locknut Included: No
 - Fire Behaviour: Halogen Free, Self-extinguishing
 - Maximum Operating Temperature: +120 °C
 - Minimum Operating Temperature: -40 °C



1856105 M50

RS PRO METALLIC BRASS CABLE GLAND, PG9 THREAD, 4MM MIN, 8MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thread Size: PG9
 - Maximum Cable Diameter: 8 mm
 - Minimum Cable Diameter: 4 mm
 - Material: Brass
 - Colour: Metallic
 - Series: RS Pro
 - IP Rating: IP68
 - Locknut Included: No



2084378 PG9

RS PRO METALLIC BRASS CABLE GLAND, PG11 THREAD, 5MM MIN, 10MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thread Size: PG11
 - Maximum Cable Diameter: 10 mm
 - Minimum Cable Diameter: 5 mm
 - Material: Brass
 - Colour: Metallic
 - Series: RS Pro
 - IP Rating: IP68
 - Locknut Included: No



2084379 PG11

RS PRO METALLIC BRASS CABLE GLAND, PG21 THREAD, 13MM MIN, 18MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thread Size: PG21
 - Maximum Cable Diameter: 18 mm
 - Minimum Cable Diameter: 13 mm
 - Material: Brass
 - Colour: Metallic
 - Series: RS Pro
 - IP Rating: IP68
 - Locknut Included: No



2084383 PG21

RS PRO METALLIC BRASS CABLE GLAND, PG29 THREAD, 18MM MIN, 25MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thread Size: PG29
 - Maximum Cable Diameter: 25 mm
 - Minimum Cable Diameter: 18 mm
 - Material: Brass
 - Colour: Metallic
 - Series: RS Pro
 - IP Rating: IP68
 - Locknut Included: No



2084384 PG29

RS PRO METALLIC NICKEL PLATED BRASS CABLE GLAND, M12 X 1.5

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Thread Size: M12 x 1.5
 - Maximum Cable Diameter: 6.5 mm
 - Minimum Cable Diameter: 3 mm
 - Material: Nickel Plated Brass
 - Colour: Metallic
 - IP Rating: IP68
 - Locknut Included: Yes
 - Maximum Operating Temperature: +100 °C



2100592 M12 x 1.5

RS PRO METALLIC NICKEL PLATED BRASS CABLE GLAND, M16 X 1.5

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thread Size: M16 x 1.5
 - Maximum Cable Diameter: 8 mm
 - Minimum Cable Diameter: 4 mm
 - Material: Nickel Plated Brass
 - Colour: Metallic
 - IP Rating: IP68
 - Locknut Included: Yes
 - Maximum Operating Temperature: +100 °C



2100594 M16 x 1.5

RS PRO METALLIC NICKEL PLATED BRASS CABLE GLAND, M16 X 1.5

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thread Size: M16 x 1.5
 - Maximum Cable Diameter: 8 mm
 - Minimum Cable Diameter: 4 mm
 - Material: Nickel Plated Brass
 - Colour: Metallic
 - IP Rating: IP68
 - Locknut Included: No
 - Maximum Operating Temperature: +100 °C



2100595 M16 x 1.5

RS PRO METALLIC NICKEL PLATED BRASS CABLE GLAND, PG13.5

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Thread Size: PG13.5
 - Maximum Cable Diameter: 12 mm
 - Minimum Cable Diameter: 6 mm
 - Material: Nickel Plated Brass
 - Colour: Metallic
 - IP Rating: IP68
 - Locknut Included: Yes
 - Maximum Operating Temperature: +100 °C



2100621 PG13.5

RS PRO METALLIC NICKEL PLATED BRASS CABLE GLAND, PG16 THREAD,

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Thread Size: PG16
 - Maximum Cable Diameter: 14 mm
 - Minimum Cable Diameter: 10 mm
 - Material: Nickel Plated Brass
 - Colour: Metallic
 - IP Rating: IP68
 - Locknut Included: Yes
 - Maximum Operating Temperature: +100 °C



2100624 PG16

RS PRO METALLIC NICKEL PLATED BRASS CABLE GLAND, PG16 THREAD,


- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thread Size: PG16
 - Maximum Cable Diameter: 14 mm
 - Minimum Cable Diameter: 10 mm
 - Material: Nickel Plated Brass
 - Colour: Metallic
 - IP Rating: IP68
 - Locknut Included: No
 - Maximum Operating Temperature: +100 °C



2100626 PG16

RS PRO METALLIC NICKEL PLATED BRASS CABLE GLAND, PG21 THREAD,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thread Size: PG21
 - Maximum Cable Diameter: 16 mm
 - Minimum Cable Diameter: 9 mm
 - Material: Nickel Plated Brass
 - Colour: Metallic
 - IP Rating: IP68
 - Locknut Included: No
 - Maximum Operating Temperature: +100 °C



2100628 PG21

RS PRO BLACK NYLON CABLE GLAND, M12 X 1.5 THREAD, 3MM MIN, 6.5MM

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Thread Size: M12 x 1.5
 - Maximum Cable Diameter: 6.5 mm
 - Minimum Cable Diameter: 3 mm
 - Material: Nylon 66
 - Colour: Black
 - Series: KSS METRIC THREAD
 - IP Rating: IP68
 - Locknut Included: No



2101317 M12 x 1.5

RS PRO BLACK NYLON CABLE GLAND, M12 X 1.5 THREAD, 3MM MIN, 6.5MM

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Thread Size: M12 x 1.5
 - Maximum Cable Diameter: 6.5 mm
 - Minimum Cable Diameter: 3 mm
 - Material: Nylon 66
 - Colour: Black
 - Series: KSS METRIC THREAD
 - IP Rating: IP68
 - Locknut Included: No



2101318 M12 x 1.5

RS PRO GREY NYLON CABLE GLAND, M12 X 1.5 THREAD, 3MM MIN, 6.5MM

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Thread Size: M12 x 1.5
 - Maximum Cable Diameter: 6.5 mm
 - Minimum Cable Diameter: 3 mm
 - Material: Nylon 66
 - Colour: Grey
 - Series: KSS METRIC THREAD
 - IP Rating: IP68
 - Locknut Included: Yes



2101319 M12 x 1.5

RS PRO BLACK NYLON CABLE GLAND, M12 X 1.25 THREAD, 3MM MIN, 6.5MM

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Thread Size: M12 x 1.25
 - Maximum Cable Diameter: 6.5 mm
 - Minimum Cable Diameter: 3 mm
 - Material: Nylon 66
 - Colour: Black
 - Series: KSS METRIC THREAD (Strain Relief type)
 - IP Rating: IP68
 - Locknut Included: Yes



2101320 M12 x 1.25

RS PRO GREY NYLON CABLE GLAND, M12 X 1.25 THREAD, 3MM MIN, 6.5MM

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Thread Size: M12 x 1.25
 - Maximum Cable Diameter: 6.5 mm
 - Minimum Cable Diameter: 3 mm
 - Material: Nylon 66
 - Colour: Grey
 - Series: KSS METRIC THREAD (Strain Relief type)
 - IP Rating: IP68
 - Locknut Included: Yes



2101321 M12 x 1.25

RS PRO BLACK NYLON CABLE GLAND, M16 X 1.5 THREAD, 5MM MIN, 10MM

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Thread Size: M16 x 1.5
 - Maximum Cable Diameter: 10 mm
 - Minimum Cable Diameter: 5 mm
 - Material: Nylon 66
 - Colour: Black
 - Series: KSS METRIC THREAD
 - IP Rating: IP68
 - Locknut Included: Yes



2101322 M16 x 1.5

RS PRO GREY NYLON CABLE GLAND, M16 X 1.5 THREAD, 5MM MIN, 10MM

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Thread Size: M16 x 1.5
 - Maximum Cable Diameter: 10 mm
 - Minimum Cable Diameter: 5 mm
 - Material: Nylon 66
 - Colour: Grey
 - Series: KSS METRIC THREAD
 - IP Rating: IP68
 - Locknut Included: Yes



2101323 M16 x 1.5

RS PRO BLACK NYLON CABLE GLAND, M16 X 1.5 THREAD, 5MM MIN, 10MM

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Thread Size: M16 x 1.5
 - Maximum Cable Diameter: 10 mm
 - Minimum Cable Diameter: 5 mm
 - Material: Nylon 66
 - Colour: Black
 - Series: KSS METRIC THREAD (Strain Relief type)
 - IP Rating: IP68
 - Locknut Included: Yes



2101324 M16 x 1.5

RS PRO GREY NYLON CABLE GLAND, M16 X 1.5 THREAD, 5MM MIN, 10MM

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Thread Size: M16 x 1.5
 - Maximum Cable Diameter: 10 mm
 - Minimum Cable Diameter: 5 mm
 - Material: Nylon 66
 - Colour: Grey
 - Series: KSS METRIC THREAD (Strain Relief type)
 - IP Rating: IP68
 - Locknut Included: Yes



2101325 M16 x 1.5

RS PRO BLACK NYLON CABLE GLAND, M20 X 1.5 THREAD, 8MM MIN, 12MM

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Thread Size: M20 x 1.5
 - Maximum Cable Diameter: 12 mm
 - Minimum Cable Diameter: 8 mm
 - Material: Nylon 66
 - Colour: Black
 - Series: KSS METRIC THREAD
 - IP Rating: IP68
 - Locknut Included: Yes



2101326 M20 x 1.5

RS PRO GREY NYLON CABLE GLAND, M20 X 1.5 THREAD, 8MM MIN, 12MM

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Thread Size: M20 x 1.5
 - Maximum Cable Diameter: 12 mm
 - Minimum Cable Diameter: 8 mm
 - Material: Nylon 66
 - Colour: Grey
 - Series: KSS METRIC THREAD
 - IP Rating: IP68
 - Locknut Included: Yes



2101327 M20 x 1.5

RS PRO BLACK NYLON CABLE GLAND, M20 X 1.5 THREAD, 10MM MIN, 14MM

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Thread Size: M20 x 1.5
 - Maximum Cable Diameter: 14 mm
 - Minimum Cable Diameter: 10 mm
 - Material: Nylon 66
 - Colour: Black
 - Series: KSS METRIC THREAD (Strain Relief type)
 - IP Rating: IP68
 - Locknut Included: Yes



2101328 M20 x 1.5

RS PRO BLACK NYLON CABLE GLAND, M25 X 1.5 THREAD, 11MM MIN, 17MM

- ขนาดบรรจุภัณฑ์: 5 x EA
- Thread Size: M25 x 1.5
 - Maximum Cable Diameter: 17 mm
 - Minimum Cable Diameter: 11 mm
 - Material: Nylon 66
 - Colour: Black
 - Series: KSS METRIC THREAD
 - IP Rating: IP68
 - Locknut Included: Yes



2101331 M25 x 1.5

RS PRO GREY NYLON CABLE GLAND, M25 X 1.5 THREAD, 11MM MIN, 17MM

- ขนาดบรรจุภัณฑ์: 5 x EA
- Thread Size: M25 x 1.5
 - Maximum Cable Diameter: 17 mm
 - Minimum Cable Diameter: 11 mm
 - Material: Nylon 66
 - Colour: Grey
 - Series: KSS METRIC THREAD
 - IP Rating: IP68
 - Locknut Included: Yes



2101332 M25 x 1.5

RS PRO BLACK NYLON CABLE GLAND, M25 X 1.5 THREAD, 13MM MIN, 18MM

- ขนาดบรรจุภัณฑ์: 5 x EA
- Thread Size: M25 x 1.5
 - Maximum Cable Diameter: 18 mm
 - Minimum Cable Diameter: 13 mm
 - Material: Nylon 66
 - Colour: Black
 - Series: KSS METRIC THREAD (Strain Relief type)
 - IP Rating: IP68
 - Locknut Included: Yes



2101333 M25 x 1.5

RS PRO GREY NYLON CABLE GLAND, M25 X 1.5 THREAD, 13MM MIN, 18MM

- ขนาดบรรจุภัณฑ์: 5 x EA
- Thread Size: M25 x 1.5
 - Maximum Cable Diameter: 18 mm
 - Minimum Cable Diameter: 13 mm
 - Material: Nylon 66
 - Colour: Grey
 - Series: KSS METRIC THREAD (Strain Relief type)
 - IP Rating: IP68
 - Locknut Included: Yes



2101334 M25 x 1.5

RS PRO BLACK NYLON CABLE GLAND, M32 X 1.5 THREAD, 15MM MIN, 21MM

- ขนาดบรรจุภัณฑ์: 5 x EA
- Thread Size: M32 x 1.5
 - Maximum Cable Diameter: 21 mm
 - Minimum Cable Diameter: 15 mm
 - Material: Nylon 66
 - Colour: Black
 - Series: KSS METRIC THREAD
 - IP Rating: IP68
 - Locknut Included: Yes



2101336 M32 x 1.5

RS PRO GREY NYLON CABLE GLAND, M32 X 1.5 THREAD, 15MM MIN, 21MM

- ขนาดบรรจุภัณฑ์: 5 x EA
- Thread Size: M32 x 1.5
 - Maximum Cable Diameter: 21 mm
 - Minimum Cable Diameter: 15 mm
 - Material: Nylon 66
 - Colour: Grey
 - Series: KSS METRIC THREAD
 - IP Rating: IP68
 - Locknut Included: Yes



2101337 M32 x 1.5

RS PRO GREY NYLON CABLE GLAND, M12 X 1.5 THREAD, 3MM MIN, 6.5MM

- ขนาดบรรจุภัณฑ์: 5 x EA
- Thread Size: M12 x 1.5
 - Maximum Cable Diameter: 6.5 mm
 - Minimum Cable Diameter: 3 mm
 - Material: Nylon 66
 - Colour: Grey
 - Series: KSS METRIC THREAD
 - IP Rating: IP68
 - Locknut Included: No



2101339 M12 x 1.5

RS PRO BLACK NYLON CABLE GLAND, M16 X 1.5 THREAD, 5MM MIN, 10MM

- ขนาดบรรจุภัณฑ์: 5 x EA
- Thread Size: M16 x 1.5
 - Maximum Cable Diameter: 10 mm
 - Minimum Cable Diameter: 5 mm
 - Material: Nylon 66
 - Colour: Black
 - Series: KSS METRIC THREAD
 - IP Rating: IP68
 - Locknut Included: No



2101340 M16 x 1.5

RS PRO GREY NYLON CABLE GLAND, M16 X 1.5 THREAD, 5MM MIN, 10MM

- ขนาดบรรจุภัณฑ์: 5 x EA
- Thread Size: M16 x 1.5
 - Maximum Cable Diameter: 10 mm
 - Minimum Cable Diameter: 5 mm
 - Material: Nylon 66
 - Colour: Grey
 - Series: KSS METRIC THREAD
 - IP Rating: IP68
 - Locknut Included: No



2101341 M16 x 1.5

RS PRO BLACK NYLON CABLE GLAND, M20 X 1.5 THREAD, 8MM MIN, 12MM

- ขนาดบรรจุภัณฑ์: 5 x EA
- Thread Size: M20 x 1.5
 - Maximum Cable Diameter: 12 mm
 - Minimum Cable Diameter: 8 mm
 - Material: Nylon 66
 - Colour: Black
 - Series: KSS METRIC THREAD
 - IP Rating: IP68
 - Locknut Included: No



2101342 M20 x 1.5

RS PRO GREY NYLON CABLE GLAND, M20 X 1.5 THREAD, 8MM MIN, 12MM

- ขนาดบรรจุภัณฑ์: 5 x EA
- Thread Size: M20 x 1.5
 - Maximum Cable Diameter: 12 mm
 - Minimum Cable Diameter: 8 mm
 - Material: Nylon 66
 - Colour: Grey
 - Series: KSS METRIC THREAD
 - IP Rating: IP68
 - Locknut Included: No



2101343 M20 x 1.5

RS PRO BLACK NYLON CABLE GLAND, M25 X 1.5 THREAD, 11MM MIN, 17MM

- ขนาดบรรจุภัณฑ์: 5 x EA
- Thread Size: M25 x 1.5
 - Maximum Cable Diameter: 17 mm
 - Minimum Cable Diameter: 11 mm
 - Material: Nylon 66
 - Colour: Black
 - Series: KSS METRIC THREAD
 - IP Rating: IP68
 - Locknut Included: No



2101344 M25 x 1.5

RS PRO GREY NYLON CABLE GLAND, M25 X 1.5 THREAD, 11MM MIN, 17MM

- ขนาดบรรจุภัณฑ์: 5 x EA
- Thread Size: M25 x 1.5
 - Maximum Cable Diameter: 17 mm
 - Minimum Cable Diameter: 11 mm
 - Material: Nylon 66
 - Colour: Grey
 - Series: KSS METRIC THREAD
 - IP Rating: IP68
 - Locknut Included: No



2101345 M25 x 1.5

RS PRO BLACK NYLON CABLE GLAND, M32 X 1.5 THREAD, 15MM MIN, 21MM

- ขนาดบรรจุภัณฑ์: 5 x EA
- Thread Size: M32 x 1.5
 - Maximum Cable Diameter: 21 mm
 - Minimum Cable Diameter: 15 mm
 - Material: Nylon 66
 - Colour: Black
 - Series: KSS METRIC THREAD
 - IP Rating: IP68
 - Locknut Included: No



2101346 M32 x 1.5

RS PRO GREY NYLON CABLE GLAND, PG13.5 THREAD, 6MM MIN, 12MM

- ขนาดบรรจุภัณฑ์: 5 x EA
- Thread Size: PG13.5
 - Maximum Cable Diameter: 12 mm
 - Minimum Cable Diameter: 6 mm
 - Material: Nylon 66
 - Colour: Grey
 - Series: KSS PG THREAD (DIN STANDARD)
 - IP Rating: IP68
 - Locknut Included: No



2101348 PG13.5

RS PRO GREY NYLON CABLE GLAND, PG7 THREAD, 3MM MIN, 6.5MM MAX,

- ขนาดบรรจุภัณฑ์: 5 x EA
- Thread Size: PG7
 - Maximum Cable Diameter: 6.5 mm
 - Minimum Cable Diameter: 3 mm
 - Material: Nylon 66
 - Colour: Grey
 - Series: KSS PG THREAD (DIN STANDARD)
 - IP Rating: IP68
 - Locknut Included: No



2101349 PG7

RS PRO BLACK NYLON CABLE GLAND, PG11 THREAD, 5MM MIN, 10MM MAX,

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Thread Size: PG11
 - Maximum Cable Diameter: 10 mm
 - Minimum Cable Diameter: 5 mm
 - Material: Nylon 66
 - Colour: Black
 - Series: KSS PG THREAD (DIN STANDARD)
 - IP Rating: IP68
 - Locknut Included: No



2101350 PG11

RS PRO GREY NYLON CABLE GLAND, PG11 THREAD, 5MM MIN, 10MM MAX,

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Thread Size: PG11
 - Maximum Cable Diameter: 10 mm
 - Minimum Cable Diameter: 5 mm
 - Material: Nylon 66
 - Colour: Grey
 - Series: KSS PG THREAD (DIN STANDARD)
 - IP Rating: IP68
 - Locknut Included: No



2101351 PG11

RS PRO BLACK NYLON CABLE GLAND, PG13.5 THREAD, 6MM MIN, 12MM

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Thread Size: PG13.5
 - Maximum Cable Diameter: 12 mm
 - Minimum Cable Diameter: 6 mm
 - Material: Nylon 66
 - Colour: Black
 - Series: KSS PG THREAD (DIN STANDARD)
 - IP Rating: IP68
 - Locknut Included: No



2101352 PG13.5

RS PRO BLACK NYLON CABLE GLAND, PG16 THREAD, 10MM MIN, 14MM MAX,

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Thread Size: PG16
 - Maximum Cable Diameter: 14 mm
 - Minimum Cable Diameter: 10 mm
 - Material: Nylon 66
 - Colour: Black
 - Series: KSS PG THREAD (DIN STANDARD)
 - IP Rating: IP68
 - Locknut Included: No



2101353 PG16

RS PRO BLACK NYLON CABLE GLAND, PG21 THREAD, 13MM MIN, 18MM MAX,

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Thread Size: PG21
 - Maximum Cable Diameter: 18 mm
 - Minimum Cable Diameter: 13 mm
 - Material: Nylon 66
 - Colour: Black
 - Series: KSS PG THREAD (DIN STANDARD)
 - IP Rating: IP68
 - Locknut Included: No



2101355 PG21

RS PRO GREY NYLON CABLE GLAND, PG21 THREAD, 13MM MIN, 18MM MAX,

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Thread Size: PG21
 - Maximum Cable Diameter: 18 mm
 - Minimum Cable Diameter: 13 mm
 - Material: Nylon 66
 - Colour: Grey
 - Series: KSS PG THREAD (DIN STANDARD)
 - IP Rating: IP68
 - Locknut Included: No



2101356 PG21

RS PRO BLACK NYLON CABLE GLAND, PG29 THREAD, 18MM MIN, 25MM

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Thread Size: PG29
 - Maximum Cable Diameter: 25 mm
 - Minimum Cable Diameter: 18 mm
 - Material: Nylon 66
 - Colour: Black
 - Series: KSS PG THREAD (DIN STANDARD)
 - IP Rating: IP68
 - Locknut Included: No



2101358 PG29

RS PRO GREY NYLON CABLE GLAND, PG29 THREAD, 18MM MIN, 25MM

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Thread Size: PG29
 - Maximum Cable Diameter: 25 mm
 - Minimum Cable Diameter: 18 mm
 - Material: Nylon 66
 - Colour: Grey
 - Series: KSS PG THREAD (DIN STANDARD)
 - IP Rating: IP68
 - Locknut Included: No



2101359 PG29

RS PRO BLACK NYLON CABLE GLAND, PG7 THREAD, 3MM MIN, 6.5MM MAX,

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Thread Size: PG7
 - Maximum Cable Diameter: 6.5 mm
 - Minimum Cable Diameter: 3 mm
 - Material: Nylon 66
 - Colour: Black
 - Series: KSS PG THREAD (DIN STANDARD)
 - IP Rating: IP68
 - Locknut Included: No



2101360 PG7

RS PRO BLACK NYLON CABLE GLAND, PG9 THREAD, 4MM MIN, 8MM MAX,

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Thread Size: PG9
 - Maximum Cable Diameter: 8 mm
 - Minimum Cable Diameter: 4 mm
 - Material: Nylon 66
 - Colour: Black
 - Series: KSS PG THREAD (DIN STANDARD)
 - IP Rating: IP68
 - Locknut Included: No



2101361 PG9

RS PRO GREY NYLON CABLE GLAND, PG9 THREAD, 4MM MIN, 8MM MAX,

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Thread Size: PG9
 - Maximum Cable Diameter: 8 mm
 - Minimum Cable Diameter: 4 mm
 - Material: Nylon 66
 - Colour: Grey
 - Series: KSS PG THREAD (DIN STANDARD)
 - IP Rating: IP68
 - Locknut Included: No



2101362 PG9

RS PRO GREY NYLON CABLE GLAND, PG11 THREAD, 5MM MIN, 10MM MAX,

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Thread Size: PG9
 - Maximum Cable Diameter: 10 mm
 - Minimum Cable Diameter: 5 mm
 - Material: Nylon 66
 - Colour: Grey
 - Series: KSS PG THREAD (DIN STANDARD) (Strain Relief type)
 - IP Rating: IP68
 - Locknut Included: Yes



2101365 PG11

RS PRO GREY NYLON CABLE GLAND, PG13.5 THREAD, 6MM MIN, 12MM

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Thread Size: PG13.5
 - Maximum Cable Diameter: 12 mm
 - Minimum Cable Diameter: 6 mm
 - Material: Nylon 66
 - Colour: Grey
 - Series: KSS PG THREAD (DIN STANDARD)
 - IP Rating: IP68
 - Locknut Included: Yes



2101366 PG13.5

RS PRO GREY NYLON CABLE GLAND, PG16 THREAD, 10MM MIN, 14MM MAX,

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Thread Size: PG16
 - Maximum Cable Diameter: 14 mm
 - Minimum Cable Diameter: 10 mm
 - Material: Nylon 66
 - Colour: Grey
 - Series: KSS PG THREAD (DIN STANDARD)
 - IP Rating: IP68
 - Locknut Included: Yes



2101367 PG16

RS PRO GREY NYLON CABLE GLAND, PG16 THREAD, 10MM MIN, 14MM MAX,

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Thread Size: PG16
 - Maximum Cable Diameter: 14 mm
 - Minimum Cable Diameter: 10 mm
 - Material: Nylon 66
 - Colour: Grey
 - Series: KSS PG THREAD (DIN STANDARD) (Strain Relief type)
 - IP Rating: IP68
 - Locknut Included: Yes



2101368 PG16

RS PRO GREY NYLON CABLE GLAND, PG21 THREAD, 13MM MIN, 18MM MAX,

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Thread Size: PG21
 - Maximum Cable Diameter: 18 mm
 - Minimum Cable Diameter: 13 mm
 - Material: Nylon 66
 - Colour: Grey
 - Series: KSS PG THREAD (DIN STANDARD)
 - IP Rating: IP68
 - Locknut Included: Yes



2101369 PG21

RS PRO GREY NYLON CABLE GLAND, PG29 THREAD, 18MM MIN, 25MM

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Thread Size: PG29
 - Maximum Cable Diameter: 25 mm
 - Minimum Cable Diameter: 18 mm
 - Material: Nylon 66
 - Colour: Grey
 - Series: KSS PG THREAD (DIN STANDARD)
 - IP Rating: IP68
 - Locknut Included: Yes



2101371 PG29

RS PRO BLACK NYLON CABLE GLAND, PG7 THREAD, 3MM MIN, 6.5MM MAX,

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Thread Size: PG7
 - Maximum Cable Diameter: 6.5 mm
 - Minimum Cable Diameter: 3 mm
 - Material: Nylon 66
 - Colour: Black
 - Series: KSS PG THREAD (DIN STANDARD)
 - IP Rating: IP68
 - Locknut Included: Yes



2101372 PG7

RS PRO GREY NYLON CABLE GLAND, PG7 THREAD, 3MM MIN, 6.5MM MAX,

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Thread Size: PG7
 - Maximum Cable Diameter: 6.5 mm
 - Minimum Cable Diameter: 3 mm
 - Material: Nylon 66
 - Colour: Grey
 - Series: KSS PG THREAD (DIN STANDARD) (Strain Relief type)
 - IP Rating: IP68
 - Locknut Included: Yes



2101374 PG7

RS PRO GREY NYLON CABLE GLAND, PG9 THREAD, 4MM MIN, 8MM MAX,

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Thread Size: PG9
 - Maximum Cable Diameter: 8 mm
 - Minimum Cable Diameter: 4 mm
 - Material: Nylon 66
 - Colour: Grey
 - Series: KSS PG THREAD (DIN STANDARD)
 - IP Rating: IP68
 - Locknut Included: Yes



2101375 PG9

RS PRO GREY NYLON CABLE GLAND, PG9 THREAD, 4MM MIN, 8MM MAX,

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Thread Size: PG9
 - Maximum Cable Diameter: 8 mm
 - Minimum Cable Diameter: 4 mm
 - Material: Nylon 66
 - Colour: Grey
 - Series: KSS PG THREAD (DIN STANDARD) (Strain Relief type)
 - IP Rating: IP68
 - Locknut Included: Yes



2101376 PG9

RS PRO NICKEL PLATED BRASS CABLE GLAND, M20 X 1.5 THREAD, 5MM MIN,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thread Size: M20 x 1.5
 - Maximum Cable Diameter: 9 mm
 - Minimum Cable Diameter: 5 mm
 - Material: Nickel Plated Brass
 - Series: Han CGM-M
 - IP Rating: IP68
 - Locknut Included: No
 - Minimum Operating Temperature: -40 °C



2116796 M20 x 1.5

RS PRO NICKEL PLATED BRASS CABLE GLAND, M20 X 1.5 THREAD, 10MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thread Size: M20 x 1.5
 - Maximum Cable Diameter: 14 mm
 - Minimum Cable Diameter: 10 mm
 - Material: Nickel Plated Brass
 - Series: Han CGM-M
 - IP Rating: IP68
 - Locknut Included: No
 - Minimum Operating Temperature: -40 °C



2116798 M20 x 1.5

RS PRO NICKEL PLATED BRASS CABLE GLAND, M32 X 1.5 THREAD, 13MM

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Thread Size: M32 x 1.5
 - Maximum Cable Diameter: 20 mm
 - Minimum Cable Diameter: 13 mm
 - Material: Nickel Plated Brass
 - Series: SKINTOP MS-M Brush
 - IP Rating: IP68
 - Locknut Included: No
 - Minimum Operating Temperature: -40 °C



2116800 M32 x 1.5

RS PRO GREY NYLON CABLE GLAND, M12X1.5 THREAD, 3MM MIN, 6.5MM

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Thread Size: M12X1.5
 - Maximum Cable Diameter: 6.5 mm
 - Minimum Cable Diameter: 3 mm
 - Material: Nylon 66
 - Colour: Grey
 - IP Rating: IP68
 - Locknut Included: Yes
 - Fire Behaviour: Fire Resistant



2141063 M12X1.5

RS PRO BLACK NYLON CABLE GLAND, M16X1.5 THREAD, 5MM MIN, 10MM

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Thread Size: M16X1.5
 - Maximum Cable Diameter: 10 mm
 - Minimum Cable Diameter: 5 mm
 - Material: Nylon 66
 - Colour: Black
 - IP Rating: IP68
 - Locknut Included: Yes
 - Fire Behaviour: Fire Resistant



2141064 M16X1.5

RS PRO GREY NYLON CABLE GLAND, M20X1.5 THREAD, 8MM MIN, 12MM

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Thread Size: M20X1.5
 - Maximum Cable Diameter: 12 mm
 - Minimum Cable Diameter: 8 mm
 - Material: Nylon 66
 - Colour: Grey
 - IP Rating: IP68
 - Locknut Included: Yes
 - Fire Behaviour: Fire Resistant



2141065 M20X1.5

RS PRO WHITE NYLON CABLE GLAND, M20X1.5 THREAD, 8MM MIN, 12MM

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Thread Size: M20X1.5
 - Maximum Cable Diameter: 12 mm
 - Minimum Cable Diameter: 8 mm
 - Material: Nylon 66
 - Colour: White
 - IP Rating: IP68
 - Locknut Included: Yes
 - Fire Behaviour: Fire Resistant



2141066 M20X1.5

RS PRO WHITE NYLON CABLE GLAND, M40X1.5 THREAD, 22MM MIN, 32MM

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Thread Size: M40X1.5
 - Maximum Cable Diameter: 32 mm
 - Minimum Cable Diameter: 22 mm
 - Material: Nylon 66
 - Colour: White
 - IP Rating: IP68
 - Locknut Included: Yes
 - Fire Behaviour: Fire Resistant



2141070 M40X1.5

RS PRO BLACK NYLON CABLE GLAND, M40X1.5 THREAD, 20MM MIN, 28MM

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Thread Size: M40X1.5
 - Maximum Cable Diameter: 28 mm
 - Minimum Cable Diameter: 20 mm
 - Material: Nylon 66
 - Colour: Black
 - IP Rating: IP68
 - Locknut Included: Yes
 - Fire Behaviour: Fire Resistant



2141071 M40X1.5

RS PRO GREY NYLON CABLE GLAND, M40X1.5 THREAD, 20MM MIN, 28MM

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Thread Size: M40X1.5
 - Maximum Cable Diameter: 28 mm
 - Minimum Cable Diameter: 20 mm
 - Material: Nylon 66
 - Colour: Grey
 - IP Rating: IP68
 - Locknut Included: Yes
 - Fire Behaviour: Fire Resistant



2141072 M40X1.5

RS PRO GREY NYLON CABLE GLAND, M20X1.5 THREAD, 10MM MIN, 14MM

- ขนาดบรรจุภัณฑ์: **50 x EA**
- Thread Size: M20X1.5
 - Maximum Cable Diameter: 14 mm
 - Minimum Cable Diameter: 10 mm
 - Material: Nylon 66
 - Colour: Grey
 - Locknut Included: No
 - Fire Behaviour: Fire Resistant
 - Minimum Operating Temperature: -40 °C



2141076 M20X1.5

RS PRO GREY NYLON CABLE GLAND, M25X1.5 THREAD, 11MM MIN, 17MM

- ขนาดบรรจุภัณฑ์: 5 x EA
- Thread Size: M25x1.5
 - Maximum Cable Diameter: 17 mm
 - Minimum Cable Diameter: 11 mm
 - Material: Nylon 66
 - Colour: Grey
 - Locknut Included: No
 - Fire Behaviour: Fire Resistant
 - Minimum Operating Temperature: -40 °C



2141077 M25x1.5

RS PRO GREY NYLON CABLE GLAND, M32X1.5 THREAD, 15MM MIN, 21MM

- ขนาดบรรจุภัณฑ์: 5 x EA
- Thread Size: M32X1.5
 - Maximum Cable Diameter: 21 mm
 - Minimum Cable Diameter: 15 mm
 - Material: Nylon 66
 - Colour: Grey
 - Locknut Included: No
 - Fire Behaviour: Fire Resistant
 - Minimum Operating Temperature: -40 °C



2141078 M32X1.5

RS PRO GREY NYLON CABLE GLAND, PG11 THREAD, 5MM MIN, 10MM MAX,

- ขนาดบรรจุภัณฑ์: 5 x EA
- Thread Size: PG11
 - Maximum Cable Diameter: 10 mm
 - Minimum Cable Diameter: 5 mm
 - Material: Nylon 66
 - Colour: Grey
 - IP Rating: IP68
 - Locknut Included: Yes
 - Fire Behaviour: Fire Resistant



2141082 PG11

RS PRO GREY NYLON CABLE GLAND, PG36 THREAD, 22MM MIN, 32MM

- ขนาดบรรจุภัณฑ์: 5 x EA
- Thread Size: PG36
 - Maximum Cable Diameter: 32 mm
 - Minimum Cable Diameter: 22 mm
 - Material: Nylon 66
 - Colour: Grey
 - IP Rating: IP68
 - Locknut Included: Yes
 - Fire Behaviour: Fire Resistant



2141083 PG36

RS PRO GREY NYLON CABLE GLAND, PG9 THREAD, 4MM MIN, 8MM MAX,

- ขนาดบรรจุภัณฑ์: 5 x EA
- Thread Size: PG9
 - Maximum Cable Diameter: 8 mm
 - Minimum Cable Diameter: 4 mm
 - Material: Nylon 66
 - Colour: Grey
 - IP Rating: IP68
 - Locknut Included: Yes
 - Fire Behaviour: Fire Resistant



2141084 PG9

ABB METALLIC NICKEL PLATED BRASS CABLE GLAND, M16 THREAD, 6MM

- ขนาดบรรจุภัณฑ์: 5 x EA
- Thread Size: M16
 - Maximum Cable Diameter: 9 mm
 - Minimum Cable Diameter: 6 mm
 - Material: Nickel Plated Brass
 - Colour: Metallic
 - IP Rating: IP68
 - Locknut Included: No
 - Minimum Operating Temperature: -40 °C



2647308 M16

ABB METALLIC NICKEL PLATED BRASS CABLE GLAND, M25 THREAD, 6MM

- ขนาดบรรจุภัณฑ์: 5 x EA
- Thread Size: M25
 - Maximum Cable Diameter: 11 mm
 - Minimum Cable Diameter: 6 mm
 - Material: Nickel Plated Brass
 - Colour: Metallic
 - IP Rating: IP68
 - Locknut Included: No
 - Minimum Operating Temperature: -40 °C



2647364 M25

ABB METALLIC NICKEL PLATED BRASS CABLE GLAND, M25 THREAD, 17MM

- ขนาดบรรจุภัณฑ์: 5 x EA
- Thread Size: M25
 - Maximum Cable Diameter: 20 mm
 - Minimum Cable Diameter: 17 mm
 - Material: Nickel Plated Brass
 - Colour: Metallic
 - IP Rating: IP68
 - Locknut Included: No
 - Minimum Operating Temperature: -40 °C



2647415 M25

ABB METALLIC NICKEL PLATED BRASS CABLE GLAND, M16 THREAD, 7MM

- ขนาดบรรจุภัณฑ์: 5 x EA
- Thread Size: M16
 - Maximum Cable Diameter: 11 mm
 - Minimum Cable Diameter: 7 mm
 - Material: Nickel Plated Brass
 - Colour: Metallic
 - IP Rating: IP68
 - Locknut Included: No
 - Minimum Operating Temperature: -40 °C



2650269 M16

RS PRO GREY EPDM CABLE GLAND, M16 THREAD, 5MM MIN, 9MM MAX,

- ขนาดบรรจุภัณฑ์: 10 x EA
- Thread Size: M16
 - Maximum Cable Diameter: 9 mm
 - Minimum Cable Diameter: 5 mm
 - Material: EPDM
 - Colour: Grey
 - IP Rating: IP67
 - Fire Behaviour: Halogen Free
 - Maximum Operating Temperature: +110 °C



2797009 M16

CABLE, GLAND, RUBBER, HALOGEN FREE, IP67, CABLE DIA 14-20MM

- ขนาดบรรจุภัณฑ์: 10 x EA
- Thread Size: M32
 - Maximum Cable Diameter: 20 mm
 - Minimum Cable Diameter: 15 mm
 - Material: EPDM
 - Colour: Grey
 - IP Rating: IP67
 - Maximum Operating Temperature: +110 °C
 - Minimum Operating Temperature: -40 °C



2797065 M32

WHT NYLON ROUNDTOP IP68 CABLE GLAND, M12

- ขนาดบรรจุภัณฑ์: 5 x EA
- Thread Size: M12
 - Maximum Cable Diameter: 6.5 mm
 - Minimum Cable Diameter: 3 mm
 - Material: Nylon 66
 - Colour: White
 - IP Rating: IP68
 - Locknut Included: Yes
 - Maximum Operating Temperature: +85 °C



6694642 M12

RS PRO WHITE NYLON CABLE GLAND, M12 THREAD, 3MM MIN, 6.5MM MAX,

- ขนาดบรรจุภัณฑ์: 100 x EA
- Thread Size: M12
 - Maximum Cable Diameter: 6.5 mm
 - Minimum Cable Diameter: 3 mm
 - Material: Nylon 66
 - Colour: White
 - IP Rating: IP68
 - Locknut Included: Yes
 - Maximum Operating Temperature: +85 °C



6694651 M12

IP68 BLACK NYLON GLAND, M12, 3-6.5MM

- ขนาดบรรจุภัณฑ์: 5 x EA
- Thread Size: M12
 - Maximum Cable Diameter: 6.5 mm
 - Minimum Cable Diameter: 3 mm
 - Material: Nylon 66
 - Colour: Black
 - IP Rating: IP68
 - Locknut Included: Yes
 - Maximum Operating Temperature: +85 °C



6694654 M12

RS PRO BLACK NYLON CABLE GLAND, M12 THREAD, 3MM MIN, 6.5MM MAX,

- ขนาดบรรจุภัณฑ์: 100 x EA
- Thread Size: M12
 - Maximum Cable Diameter: 6.5 mm
 - Minimum Cable Diameter: 3 mm
 - Material: Nylon 66
 - Colour: Black
 - IP Rating: IP68
 - Locknut Included: Yes
 - Maximum Operating Temperature: +85 °C



6694658 M12

RS PRO BLACK NYLON CABLE GLAND, M20 THREAD, 4MM MIN, 9MM MAX,

- ขนาดบรรจุภัณฑ์: 5 x EA
- Thread Size: M20
 - Maximum Cable Diameter: 9 mm
 - Minimum Cable Diameter: 4 mm
 - Material: Nylon
 - Colour: Black
 - IP Rating: IP68
 - Locknut Included: Yes
 - Maximum Operating Temperature: +85 °C



6694660 M20

IP68 BLACK NYLON GLAND, M20, 6-12MM

- ขนาดบรรจุภัณฑ์: 5 x EA
- Thread Size: M20
 - Maximum Cable Diameter: 12 mm
 - Minimum Cable Diameter: 6 mm
 - Material: Nylon
 - Colour: Black
 - IP Rating: IP68
 - Locknut Included: Yes
 - Maximum Operating Temperature: +85 °C



6694664 M20

BLACK ROUND TOP IP68 CABLE GLAND, M16

- ขนาดบรรจุภัณฑ์: 5 x EA
- Thread Size: M16
 - Maximum Cable Diameter: 7 mm
 - Minimum Cable Diameter: 3 mm
 - Material: Nylon
 - Colour: Black
 - IP Rating: IP68
 - Locknut Included: Yes
 - Maximum Operating Temperature: +85 °C



6694667 M16

BLACK ROUNDTOP IP68 CABLE GLAND, M32

- ขนาดบรรจุภัณฑ์: 5 x EA
- Thread Size: M32
 - Maximum Cable Diameter: 25 mm
 - Minimum Cable Diameter: 18 mm
 - Material: Nylon 66
 - Colour: Black
 - IP Rating: IP68
 - Locknut Included: Yes
 - Maximum Operating Temperature: +85 °C



6694670 M32

IP68 BLACK NYLON GLAND, M20, 10-14MM

- ขนาดบรรจุภัณฑ์: 5 x EA
- Thread Size: M20
 - Maximum Cable Diameter: 14 mm
 - Minimum Cable Diameter: 10 mm
 - Material: Nylon 66
 - Colour: Black
 - IP Rating: IP68
 - Locknut Included: Yes
 - Maximum Operating Temperature: +85 °C



6694673 M20

BLACK ROUNDTOP IP68 CABLE GLAND, M25

- ขนาดบรรจุภัณฑ์: 5 x EA
- Thread Size: M25
 - Maximum Cable Diameter: 18 mm
 - Minimum Cable Diameter: 13 mm
 - Material: Nylon 66
 - Colour: Black
 - IP Rating: IP68
 - Locknut Included: Yes
 - Maximum Operating Temperature: +85 °C



6694676 M25

RS PRO BLACK NYLON CABLE GLAND, M50 THREAD, 30MM MIN, 38MM

- ขนาดบรรจุภัณฑ์: 5 x EA
- Thread Size: M50
 - Maximum Cable Diameter: 38 mm
 - Minimum Cable Diameter: 30 mm
 - Material: Nylon 66
 - Colour: Black
 - IP Rating: IP68
 - Locknut Included: Yes
 - Minimum Operating Temperature: -60 °C



6694682 M50

RS PRO BLACK NYLON CABLE GLAND, M63 THREAD, 34MM MIN, 44MM MAX,

- ขนาดบรรจุภัณฑ์: 5 x EA
- Thread Size: M63
 - Maximum Cable Diameter: 44 mm
 - Minimum Cable Diameter: 34 mm
 - Material: Nylon 66
 - Colour: Black
 - IP Rating: IP68
 - Locknut Included: Yes
 - Maximum Operating Temperature: +85 °C



6694686 M63

BLACK ROUNDTOP IP68 CABLE GLAND, M40

- ขนาดบรรจุภัณฑ์: 5 x EA
- Thread Size: M40
 - Maximum Cable Diameter: 32 mm
 - Minimum Cable Diameter: 22 mm
 - Material: Nylon 66
 - Colour: Black
 - IP Rating: IP68
 - Locknut Included: Yes
 - Maximum Operating Temperature: +85 °C



6694689 M40

RS PRO GREY NYLON CABLE GLAND, PG7 THREAD, 3.5MM MIN, 6MM MAX,

- ขนาดบรรจุภัณฑ์: 10 x EA
- Thread Size: PG7
 - Maximum Cable Diameter: 6 mm
 - Minimum Cable Diameter: 3.5 mm
 - Material: Nylon 66
 - Colour: Grey
 - IP Rating: IP68
 - Locknut Included: Yes
 - Standards Met: UL 94 V-2



8229571 PG7

RS PRO GREY NYLON CABLE GLAND, PG9 THREAD, 4MM MIN, 8MM MAX,

- ขนาดบรรจุภัณฑ์: 10 x EA
- Thread Size: PG9
 - Maximum Cable Diameter: 8 mm
 - Minimum Cable Diameter: 4 mm
 - Material: Nylon 66
 - Colour: Grey
 - IP Rating: IP68
 - Locknut Included: Yes
 - Standards Met: UL 94 V-2



8229580 PG9

RS PRO GREY NYLON CABLE GLAND, PG13.5 THREAD, 6MM MIN, 12MM

- ขนาดบรรจุภัณฑ์: 10 x EA
- Thread Size: PG13.5
 - Maximum Cable Diameter: 12 mm
 - Minimum Cable Diameter: 6 mm
 - Material: Nylon 66
 - Colour: Grey
 - IP Rating: IP68
 - Locknut Included: Yes
 - Standards Met: UL 94 V-2



8229587 PG13.5

RS PRO BLACK NYLON CABLE GLAND, PG7 THREAD, 3.5MM MIN, 6MM MAX,

- ขนาดบรรจุภัณฑ์: 10 x EA
- Thread Size: PG7
 - Maximum Cable Diameter: 6 mm
 - Minimum Cable Diameter: 3.5 mm
 - Material: Nylon 66
 - Colour: Black
 - IP Rating: IP68
 - Locknut Included: Yes
 - Standards Met: UL 94 V-2



8229593 PG7

RS PRO GREY NYLON CABLE GLAND, PG21 THREAD, 13MM MIN, 18MM MAX,

- ขนาดบรรจุภัณฑ์: 10 x EA
- Thread Size: PG21
 - Maximum Cable Diameter: 18 mm
 - Minimum Cable Diameter: 13 mm
 - Material: Nylon 66
 - Colour: Grey
 - IP Rating: IP68
 - Locknut Included: Yes
 - Standards Met: UL 94 V-2



8229599 PG21

RS PRO BLACK NYLON CABLE GLAND, PG13.5 THREAD, 6MM MIN, 12MM

- ขนาดบรรจุภัณฑ์: 10 x EA
- Thread Size: PG13.5
 - Maximum Cable Diameter: 12 mm
 - Minimum Cable Diameter: 6 mm
 - Material: Nylon 66
 - Colour: Black
 - IP Rating: IP68
 - Locknut Included: Yes
 - Standards Met: UL 94 V-2



8229600 PG13.5

RS PRO BLACK NYLON CABLE GLAND, PG9 THREAD, 4MM MIN, 8MM MAX,

- ขนาดบรรจุภัณฑ์: 10 x EA
- Thread Size: PG9
 - Maximum Cable Diameter: 8 mm
 - Minimum Cable Diameter: 4 mm
 - Material: Nylon 66
 - Colour: Black
 - IP Rating: IP68
 - Locknut Included: Yes
 - Standards Met: UL 94 V-2



8229603 PG9

CABLE GLAND PG11 BLACK IP68

- ขนาดบรรจุภัณฑ์: 10 x EA
- Thread Size: PG11
 - Maximum Cable Diameter: 10 mm
 - Minimum Cable Diameter: 5 mm
 - Material: Nylon 66
 - Colour: Black
 - IP Rating: IP68
 - Locknut Included: Yes
 - Standards Met: UL 94 V-2



8229606 PG11

RS PRO BLACK NYLON CABLE GLAND, PG21 THREAD, 13MM MIN, 18MM MAX,

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Thread Size: PG21
 - Maximum Cable Diameter: 18 mm
 - Minimum Cable Diameter: 13 mm
 - Material: Nylon 66
 - Colour: Black
 - IP Rating: IP68
 - Locknut Included: Yes
 - Standards Met: UL 94 V-2



8229612 PG21

RS PRO GREY NYLON CABLE GLAND, M12 THREAD, 3MM MIN, 6.5MM MAX,

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Thread Size: M12
 - Maximum Cable Diameter: 6.5 mm
 - Minimum Cable Diameter: 3 mm
 - Material: Nylon 66
 - Colour: Grey
 - IP Rating: IP68
 - Locknut Included: Yes
 - Standards Met: UL 94 V-2



8229616 M12

RS PRO GREY NYLON CABLE GLAND, M25 THREAD, 13MM MIN, 18MM MAX,

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Thread Size: M25
 - Maximum Cable Diameter: 18 mm
 - Minimum Cable Diameter: 13 mm
 - Material: Nylon 66
 - Colour: Grey
 - IP Rating: IP68
 - Locknut Included: Yes
 - Standards Met: UL 94 V-2



8229622 M25

CABLE GLANDM16 X 1.5 GREY IP68

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Thread Size: M16
 - Maximum Cable Diameter: 10 mm
 - Minimum Cable Diameter: 5 mm
 - Material: Nylon 66
 - Colour: Grey
 - IP Rating: IP68
 - Locknut Included: Yes
 - Standards Met: UL 94 V-2



8229625 M16

CABLE GLANDM12 X 1.5 BLACK IP68

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Thread Size: M12
 - Maximum Cable Diameter: 6.5 mm
 - Minimum Cable Diameter: 3 mm
 - Material: Nylon 66
 - Colour: Black
 - IP Rating: IP68
 - Locknut Included: Yes
 - Standards Met: UL 94 V-2



8229631 M12

RS PRO BLACK NYLON CABLE GLAND, M16 THREAD, 5MM MIN, 10MM MAX,

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Thread Size: M16
 - Maximum Cable Diameter: 10 mm
 - Minimum Cable Diameter: 5 mm
 - Material: Nylon 66
 - Colour: Black
 - IP Rating: IP68
 - Locknut Included: Yes
 - Standards Met: UL 94 V-2



8229634 M16

CABLE GLANDM20 X 1.5 BLACK IP68

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Thread Size: M20
 - Maximum Cable Diameter: 14 mm
 - Minimum Cable Diameter: 5 mm
 - Material: Nylon 66
 - Colour: Black
 - IP Rating: IP68
 - Locknut Included: Yes
 - Standards Met: UL 94 V-2



8229638 M20

ROUND TOP CABLE GLAND PG7 GREY IP68

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Thread Size: PG7
 - Maximum Cable Diameter: 6 mm
 - Minimum Cable Diameter: 3.5 mm
 - Material: Nylon 66
 - Colour: Grey
 - IP Rating: IP68
 - Locknut Included: Yes
 - Standards Met: UL 94 V-2



8229640 PG7

RS PRO GREY NYLON CABLE GLAND, PG9 THREAD, 4MM MIN, 8MM MAX,

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Thread Size: PG9
 - Maximum Cable Diameter: 8 mm
 - Minimum Cable Diameter: 4 mm
 - Material: Nylon 66
 - Colour: Grey
 - IP Rating: IP68
 - Locknut Included: Yes
 - Standards Met: UL 94 V-2



8229644 PG9

RS PRO BLACK NYLON CABLE GLAND, M25 THREAD, 13MM MIN, 18MM MAX,

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Thread Size: M25
 - Maximum Cable Diameter: 18 mm
 - Minimum Cable Diameter: 13 mm
 - Material: Nylon 66
 - Colour: Black
 - IP Rating: IP68
 - Locknut Included: Yes
 - Standards Met: UL 94 V-2



8229647 M25

ROUND TOP CABLE GLAND PG16 GREY IP68

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Thread Size: PG16
 - Maximum Cable Diameter: 14 mm
 - Minimum Cable Diameter: 10 mm
 - Material: Nylon 66
 - Colour: Grey
 - IP Rating: IP68
 - Locknut Included: Yes
 - Standards Met: UL 94 V-2



8229650 PG16

ROUND TOP CABLE GLAND PG11 GREY IP68

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Thread Size: PG11
 - Maximum Cable Diameter: 10 mm
 - Minimum Cable Diameter: 5 mm
 - Material: Nylon 66
 - Colour: Grey
 - IP Rating: IP68
 - Locknut Included: Yes
 - Standards Met: UL 94 V-2



8229653 PG11

ROUND TOP CABLE GLAND PG13.5 GREY IP68

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Thread Size: PG13.5
 - Maximum Cable Diameter: 12 mm
 - Minimum Cable Diameter: 6 mm
 - Material: Nylon 66
 - Colour: Grey
 - IP Rating: IP68
 - Locknut Included: Yes
 - Standards Met: UL 94 V-2



8229656 PG13.5

ROUND TOP CABLE GLAND PG29 GREY IP68

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Thread Size: PG29
 - Maximum Cable Diameter: 25 mm
 - Minimum Cable Diameter: 18 mm
 - Material: Nylon 66
 - Colour: Grey
 - IP Rating: IP68
 - Locknut Included: Yes
 - Standards Met: UL 94 V-2



8229662 PG29

ROUND TOP CABLE GLAND PG7 BLACK IP68

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Thread Size: PG7
 - Maximum Cable Diameter: 6 mm
 - Minimum Cable Diameter: 3.5 mm
 - Material: Nylon 66
 - Colour: Black
 - IP Rating: IP68
 - Locknut Included: Yes
 - Standards Met: UL 94 V-2



8229666 PG7

ROUND TOP CABLE GLAND PG21 GREY IP68

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Thread Size: PG21
 - Maximum Cable Diameter: 18 mm
 - Minimum Cable Diameter: 13 mm
 - Material: Nylon 66
 - Colour: Grey
 - IP Rating: IP68
 - Locknut Included: Yes
 - Standards Met: UL 94 V-2



8229669 PG21

ROUND TOP CABLE GLAND PG13.5 BLACK IP68

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Thread Size: PG13.5
 - Maximum Cable Diameter: 12 mm
 - Minimum Cable Diameter: 6 mm
 - Material: Nylon 66
 - Colour: Black
 - IP Rating: IP68
 - Locknut Included: Yes
 - Standards Met: UL 94 V-2



8229672 PG13.5

ROUND TOP CABLE GLAND PG9 BLACK IP68

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Thread Size: PG9
 - Maximum Cable Diameter: 8 mm
 - Minimum Cable Diameter: 4 mm
 - Material: Nylon 66
 - Colour: Black
 - IP Rating: IP68
 - Locknut Included: Yes
 - Standards Met: UL 94 V-2



8229675 PG9

ROUND TOP CABLE GLAND PG11 BLACK IP68

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Thread Size: PG11
 - Maximum Cable Diameter: 10 mm
 - Minimum Cable Diameter: 5 mm
 - Material: Nylon 66
 - Colour: Black
 - IP Rating: IP68
 - Locknut Included: Yes
 - Standards Met: UL 94 V-2



8229678 PG11

ROUND TOP CABLE GLAND PG16 BLACK IP68

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Thread Size: PG16
 - Maximum Cable Diameter: 14 mm
 - Minimum Cable Diameter: 10 mm
 - Material: Nylon 66
 - Colour: Black
 - IP Rating: IP68
 - Locknut Included: Yes
 - Standards Met: UL 94 V-2



8229681 PG16

ROUND TOP CABLE GLAND PG21 BLACK IP68

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Thread Size: PG21
 - Maximum Cable Diameter: 18 mm
 - Minimum Cable Diameter: 13 mm
 - Material: Nylon 66
 - Colour: Black
 - IP Rating: IP68
 - Locknut Included: Yes
 - Standards Met: UL 94 V-2



8229684 PG21

RS PRO BLACK NYLON CABLE GLAND, PG29 THREAD, 18MM MIN, 25MM

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Thread Size: PG29
 - Maximum Cable Diameter: 25 mm
 - Minimum Cable Diameter: 18 mm
 - Material: Nylon 66
 - Colour: Black
 - IP Rating: IP68
 - Locknut Included: Yes
 - Standards Met: UL 94 V-2



8229688 PG29

ROUND TOPCABLE GLANDM12 X 1.5 GREY IP68

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Thread Size: M12
 - Maximum Cable Diameter: 6.5 mm
 - Minimum Cable Diameter: 3 mm
 - Material: Nylon 66
 - Colour: Grey
 - IP Rating: IP68
 - Locknut Included: Yes
 - Standards Met: UL 94 V-2



8229739 M12

ROUND TOPCABLE GLANDM20 X 1.5 GREY IP68

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Thread Size: M20
 - Maximum Cable Diameter: 14 mm
 - Minimum Cable Diameter: 10 mm
 - Material: Nylon 66
 - Colour: Grey
 - IP Rating: IP68
 - Locknut Included: Yes
 - Standards Met: UL 94 V-2



8229741 M20

ROUND TOPCABLE GLANDM25 X 1.5 GREY IP68

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Thread Size: M25
 - Maximum Cable Diameter: 18 mm
 - Minimum Cable Diameter: 13 mm
 - Material: Nylon 66
 - Colour: Grey
 - IP Rating: IP68
 - Locknut Included: Yes
 - Standards Met: UL 94 V-2



8229745 M25

ROUND TOPCABLE GLANDM16 X 1.5 GREY IP68

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Thread Size: M16
 - Maximum Cable Diameter: 10 mm
 - Minimum Cable Diameter: 5 mm
 - Material: Nylon 66
 - Colour: Grey
 - IP Rating: IP68
 - Locknut Included: Yes
 - Standards Met: UL 94 V-2



8229748 M16

ROUND TOPCABLE GLANDM25S X 1.5 GREY IP68

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Thread Size: M25
 - Maximum Cable Diameter: 18 mm
 - Minimum Cable Diameter: 13 mm
 - Material: Nylon 66
 - Colour: Grey
 - IP Rating: IP68
 - Locknut Included: Yes
 - Standards Met: UL 94 V-2



8229751 M25

ROUND TOPCABLE GLANDM32 X 1.5 GREY IP68

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Thread Size: M32
 - Maximum Cable Diameter: 25 mm
 - Minimum Cable Diameter: 18 mm
 - Material: Nylon 66
 - Colour: Grey
 - IP Rating: IP68
 - Locknut Included: Yes
 - Standards Met: UL 94 V-2



8229754 M32

ROUND TOPCABLE GLANDM20S X 1.5 GREY/IP68

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Thread Size: M20
 - Maximum Cable Diameter: 14 mm
 - Minimum Cable Diameter: 10 mm
 - Material: Nylon 66
 - Colour: Grey
 - IP Rating: IP68
 - Locknut Included: Yes
 - Standards Met: UL 94 V-2



8229757 M20

RS PRO BLACK NYLON CABLE GLAND, M25 THREAD, 13MM MIN, 18MM MAX,

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Thread Size: M25
 - Maximum Cable Diameter: 18 mm
 - Minimum Cable Diameter: 13 mm
 - Material: Nylon 66
 - Colour: Black
 - IP Rating: IP68
 - Locknut Included: Yes
 - Standards Met: UL 94 V-2



8229763 M25

RS PRO WHITE NYLON CABLE GLAND, M16 THREAD, 5MM MIN, 10MM MAX,

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Thread Size: M16
 - Maximum Cable Diameter: 10 mm
 - Minimum Cable Diameter: 5 mm
 - Material: Nylon 66
 - Colour: White
 - IP Rating: IP68
 - Locknut Included: Yes
 - Standards Met: UL 94 V-2



8229767 M16

ROUND TOPCABLE GLANDM32 X 1.5 WHITE IP68

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Thread Size: M32
 - Maximum Cable Diameter: 25 mm
 - Minimum Cable Diameter: 18 mm
 - Material: Nylon 66
 - Colour: White
 - IP Rating: IP68
 - Locknut Included: Yes
 - Standards Met: UL 94 V-2



8229773 M32

RS PRO WHITE NYLON CABLE GLAND, M20 THREAD, 10MM MIN, 14MM MAX,

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Thread Size: M20
 - Maximum Cable Diameter: 14 mm
 - Minimum Cable Diameter: 10 mm
 - Material: Nylon 66
 - Colour: White
 - IP Rating: IP68
 - Locknut Included: Yes
 - Standards Met: UL 94 V-2



8229776 M20

ROUND TOPCABLE GLANDM25 X 1.5 WHITE IP68

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Thread Size: M25
 - Maximum Cable Diameter: 18 mm
 - Minimum Cable Diameter: 13 mm
 - Material: Nylon 66
 - Colour: White
 - IP Rating: IP68
 - Locknut Included: Yes
 - Standards Met: UL 94 V-2



8229779 M25

ROUND TOPCABLE GLANDM20S X 1.5 WHITEIP68

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Thread Size: M20
 - Maximum Cable Diameter: 14 mm
 - Minimum Cable Diameter: 10 mm
 - Material: Nylon 66
 - Colour: White
 - IP Rating: IP68
 - Locknut Included: Yes
 - Standards Met: UL 94 V-2



8229782 M20

RS PRO WHITE NYLON CABLE GLAND, M25 THREAD, 13MM MIN, 18MM MAX,

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Thread Size: M25
 - Maximum Cable Diameter: 18 mm
 - Minimum Cable Diameter: 13 mm
 - Material: Nylon 66
 - Colour: White
 - IP Rating: IP68
 - Locknut Included: Yes
 - Standards Met: UL 94 V-2



8229785 M25

RS PRO RED NYLON CABLE GLAND, M20 THREAD, 10MM MIN, 14MM MAX,

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Thread Size: M20
 - Maximum Cable Diameter: 14 mm
 - Minimum Cable Diameter: 10 mm
 - Material: Nylon 66
 - Colour: Red
 - IP Rating: IP68
 - Locknut Included: Yes
 - Standards Met: UL 94 V-2



8229789 M20

RS PRO RED NYLON CABLE GLAND, M25 THREAD, 13MM MIN, 18MM MAX,

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Thread Size: M25
 - Maximum Cable Diameter: 18 mm
 - Minimum Cable Diameter: 13 mm
 - Material: Nylon 66
 - Colour: Red
 - IP Rating: IP68
 - Locknut Included: Yes
 - Standards Met: UL 94 V-2



8229798 M25

M12 BRASS CABLE GLAND + LOCKNUT,3-6.5MM

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Thread Size: M12
 - Maximum Cable Diameter: 6.5 mm
 - Minimum Cable Diameter: 3 mm
 - Material: Nickel Plated Brass
 - Colour: Metallic
 - IP Rating: IP68
 - Locknut Included: Yes
 - Minimum Operating Temperature: -40 °C



8319012 M12

M16 BRASS CABLE GLAND + LOCKNUT,5-10MM

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Thread Size: M16 x 1.5
 - Maximum Cable Diameter: 10 mm
 - Minimum Cable Diameter: 5 mm
 - Material: Nickel Plated Brass
 - Colour: Metallic
 - IP Rating: IP68
 - Locknut Included: Yes
 - Minimum Operating Temperature: -40 °C



8319021 M16 x 1.5

M20 BRASS CABLE GLAND + LOCKNUT,8-14MM

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Thread Size: M20
 - Maximum Cable Diameter: 14 mm
 - Minimum Cable Diameter: 8 mm
 - Material: Nickel Plated Brass
 - Colour: Metallic
 - IP Rating: IP68
 - Locknut Included: Yes
 - Minimum Operating Temperature: -40 °C



8319024 M20

M25 BRASS CABLE GLAND + LOCKNUT,9-16MM

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Thread Size: M25
 - Maximum Cable Diameter: 16 mm
 - Minimum Cable Diameter: 9 mm
 - Material: Nickel Plated Brass
 - Colour: Metallic
 - IP Rating: IP68
 - Locknut Included: Yes
 - Minimum Operating Temperature: -40 °C



8319028 M25

M40 BRASS CABLE GLAND + LOCKNUT,22-32MM

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Thread Size: M40
 - Maximum Cable Diameter: 32 mm
 - Minimum Cable Diameter: 22 mm
 - Material: Nickel Plated Brass
 - Colour: Metallic
 - IP Rating: IP68
 - Locknut Included: Yes
 - Minimum Operating Temperature: -40 °C



8319030 M40

M50 BRASS CABLE GLAND + LOCKNUT,31-38MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thread Size: M50 x 1.5
 - Maximum Cable Diameter: 38 mm
 - Minimum Cable Diameter: 31 mm
 - Material: Nickel Plated Brass
 - Colour: Metallic
 - IP Rating: IP68
 - Locknut Included: Yes
 - Minimum Operating Temperature: -40 °C



8319034 M50 x 1.5

M32 BRASS CABLE GLAND + LOCKNUT,15-22MM

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Thread Size: M32
 - Maximum Cable Diameter: 22 mm
 - Minimum Cable Diameter: 15 mm
 - Material: Nickel Plated Brass
 - Colour: Metallic
 - IP Rating: IP68
 - Locknut Included: Yes
 - Minimum Operating Temperature: -40 °C



8319037 M32

PG9 BRASS CABLE GLAND + LOCKNUT,4-8MM

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Thread Size: PG9
 - Maximum Cable Diameter: 8 mm
 - Minimum Cable Diameter: 4 mm
 - Material: Nickel Plated Brass
 - Colour: Metallic
 - IP Rating: IP68
 - Locknut Included: Yes
 - Minimum Operating Temperature: -40 °C



8319040 PG9

RS PRO METALLIC NICKEL PLATED BRASS CABLE GLAND, M63 THREAD,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thread Size: M63
 - Maximum Cable Diameter: 44 mm
 - Minimum Cable Diameter: 37 mm
 - Material: Nickel Plated Brass
 - Colour: Metallic
 - IP Rating: IP68
 - Locknut Included: Yes
 - Minimum Operating Temperature: -40 °C



8319043 M63

PG7 BRASS CABLE GLAND + LOCKNUT,3-6.5MM

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Thread Size: PG7
 - Maximum Cable Diameter: 6.5 mm
 - Minimum Cable Diameter: 3 mm
 - Material: Nickel Plated Brass
 - Colour: Metallic
 - IP Rating: IP68
 - Locknut Included: Yes
 - Minimum Operating Temperature: -40 °C



8319046 PG7

PG13.5 BRASS CABLEGLAND + LOCKNUT,6-12MM

- ขนาดบรรจุภัณฑ์: 5 x EA
- Thread Size: PG13.5
 - Maximum Cable Diameter: 12 mm
 - Minimum Cable Diameter: 6 mm
 - Material: Nickel Plated Brass
 - Colour: Metallic
 - IP Rating: IP68
 - Locknut Included: Yes
 - Minimum Operating Temperature: -40 °C



8319052 PG13.5

RS PRO METALLIC NICKEL PLATED BRASS CABLE GLAND, PG16 THREAD,

- ขนาดบรรจุภัณฑ์: 5 x EA
- Thread Size: PG16
 - Maximum Cable Diameter: 14 mm
 - Minimum Cable Diameter: 8 mm
 - Material: Nickel Plated Brass
 - Colour: Metallic
 - IP Rating: IP68
 - Locknut Included: Yes
 - Minimum Operating Temperature: -40 °C



8319056 PG16

PG11 BRASS CABLE GLAND + LOCKNUT,5-10MM

- ขนาดบรรจุภัณฑ์: 5 x EA
- Thread Size: PG11
 - Maximum Cable Diameter: 10 mm
 - Minimum Cable Diameter: 5 mm
 - Material: Nickel Plated Brass
 - Colour: Metallic
 - IP Rating: IP68
 - Locknut Included: Yes
 - Minimum Operating Temperature: -40 °C



8319059 PG11

PG21 BRASS CABLE GLAND + LOCKNUT,13-18MM

- ขนาดบรรจุภัณฑ์: 5 x EA
- Thread Size: PG21
 - Maximum Cable Diameter: 18 mm
 - Minimum Cable Diameter: 13 mm
 - Material: Nickel Plated Brass
 - Colour: Metallic
 - IP Rating: IP68
 - Locknut Included: Yes
 - Minimum Operating Temperature: -40 °C



8319065 PG21

RS PRO METALLIC NICKEL PLATED BRASS CABLE GLAND, PG29 THREAD,

- ขนาดบรรจุภัณฑ์: 5 x EA
- Thread Size: PG29
 - Maximum Cable Diameter: 25 mm
 - Minimum Cable Diameter: 18 mm
 - Material: Nickel Plated Brass
 - Colour: Metallic
 - IP Rating: IP68
 - Locknut Included: Yes
 - Minimum Operating Temperature: -40 °C



8319068 PG29

EMC CABLE GLAND C/W LOCKNUT,PG9,4-8 MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thread Size: PG9
 - Maximum Cable Diameter: 8 mm
 - Minimum Cable Diameter: 4 mm
 - Material: Nickel Plated Brass
 - Colour: Metallic
 - IP Rating: IP68
 - Locknut Included: Yes
 - Minimum Operating Temperature: -40 °C



8354087 PG9

EMC CABLE GLAND C/W LOCKNUT,PG16, 8-14MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thread Size: PG16
 - Maximum Cable Diameter: 14 mm
 - Minimum Cable Diameter: 8 mm
 - Material: Nickel Plated Brass
 - Colour: Metallic
 - IP Rating: IP68
 - Locknut Included: Yes
 - Minimum Operating Temperature: -40 °C



8354093 PG16

RS PRO METALLIC NICKEL PLATED BRASS CABLE GLAND, PG11 THREAD,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thread Size: PG11
 - Maximum Cable Diameter: 10 mm
 - Minimum Cable Diameter: 5 mm
 - Material: Nickel Plated Brass
 - Colour: Metallic
 - IP Rating: IP68
 - Locknut Included: Yes
 - Maximum Operating Temperature: +110 °C



8354096 PG11

EMC CABLE GLAND C/W LOCKNUT,PG13.5 6-12MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thread Size: PG13.5
 - Maximum Cable Diameter: 12 mm
 - Minimum Cable Diameter: 6 mm
 - Material: Nickel Plated Brass
 - Colour: Metallic
 - IP Rating: IP68
 - Locknut Included: Yes
 - Minimum Operating Temperature: -40 °C



8354099 PG13.5

RS PRO METALLIC NICKEL PLATED BRASS CABLE GLAND, PG36 THREAD,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thread Size: PG36
 - Maximum Cable Diameter: 32 mm
 - Minimum Cable Diameter: 22 mm
 - Material: Nickel Plated Brass
 - Colour: Metallic
 - IP Rating: IP68
 - Locknut Included: Yes
 - Minimum Operating Temperature: -40 °C



8354100 PG36

RS PRO METALLIC NICKEL PLATED BRASS CABLE GLAND, PG29 THREAD,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thread Size: PG29
 - Maximum Cable Diameter: 25 mm
 - Minimum Cable Diameter: 18 mm
 - Material: Nickel Plated Brass
 - Colour: Metallic
 - IP Rating: IP68
 - Locknut Included: Yes
 - Minimum Operating Temperature: -40 °C



8354106 PG29

RS PRO METALLIC NICKEL PLATED BRASS CABLE GLAND, M20 THREAD,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thread Size: M20
 - Maximum Cable Diameter: 18 mm
 - Minimum Cable Diameter: 6 mm
 - Material: Nickel Plated Brass
 - Colour: Metallic
 - IP Rating: IP68
 - Locknut Included: Yes
 - Minimum Operating Temperature: -40 °C



8354112 M20

EMC CABLE GLAND C/W LOCKNUT,M25S 10-16MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thread Size: M25
 - Maximum Cable Diameter: 16 mm
 - Minimum Cable Diameter: 10 mm
 - Material: Nickel Plated Brass
 - Colour: Metallic
 - IP Rating: IP68
 - Locknut Included: Yes
 - Minimum Operating Temperature: -40 °C



8354116 M25

EMC CABLE GLAND C/W LOCKNUT,M16, 4-8 MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thread Size: M16
 - Maximum Cable Diameter: 8 mm
 - Minimum Cable Diameter: 4 mm
 - Material: Nickel Plated Brass
 - Colour: Metallic
 - IP Rating: IP68
 - Locknut Included: Yes
 - Minimum Operating Temperature: -40 °C



8354119 M16

EMC CABLE GLAND C/W LOCKNUT,M50 30-38MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thread Size: M50
 - Maximum Cable Diameter: 38 mm
 - Minimum Cable Diameter: 30 mm
 - Material: Nickel Plated Brass
 - Colour: Metallic
 - IP Rating: IP68
 - Locknut Included: Yes
 - Maximum Operating Temperature: +110 °C



8354122 M50

EMC CABLE GLAND C/W LOCKNUT,M32S 15-22MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thread Size: M32
 - Maximum Cable Diameter: 22 mm
 - Minimum Cable Diameter: 15 mm
 - Material: Nickel Plated Brass
 - Colour: Metallic
 - IP Rating: IP68
 - Locknut Included: Yes
 - Minimum Operating Temperature: -40 °C



8354125 M32

EMC CABLE GLAND C/W LOCKNUT, M40S21-30MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thread Size: M40
 - Maximum Cable Diameter: 30 mm
 - Minimum Cable Diameter: 21 mm
 - Material: Nickel Plated Brass
 - Colour: Metallic
 - IP Rating: IP68
 - Locknut Included: Yes
 - Minimum Operating Temperature: -40 °C



8354128 M40

RS PRO BLACK PVC 6.4MM CABLE GROMMET FOR MAXIMUM OF 4MM

- ขนาดบรรจุภัณฑ์: 100 x EA
- Grommet Type: Cable Grommet
 - Maximum Cable Diameter: 4 mm
 - Panel Hole Diameter: 6.4 mm
 - Material: PVC
 - Colour: Black
 - Maximum Panel Thickness: 1.6 mm



543197 Cable Grommet

RS PRO BLACK PVC 9.5MM CABLE GROMMET FOR MAXIMUM OF 6.4MM

- ขนาดบรรจุภัณฑ์: 100 x EA
- Grommet Type: Cable Grommet
 - Maximum Cable Diameter: 6.4 mm
 - Panel Hole Diameter: 9.5 mm
 - Material: PVC
 - Colour: Black
 - Maximum Panel Thickness: 1.6 mm



543204 Cable Grommet

RS PRO BLACK PVC 12.5MM CABLE GROMMET FOR MAXIMUM OF 9.5MM

- ขนาดบรรจุภัณฑ์: 100 x EA
- Grommet Type: Cable Grommet
 - Maximum Cable Diameter: 9.5 mm
 - Panel Hole Diameter: 12.5 mm
 - Material: PVC
 - Colour: Black
 - Maximum Panel Thickness: 1.6 mm



543210 Cable Grommet

RS PRO BLACK PVC 9.52MM CABLE GROMMET FOR MAXIMUM OF

- ขนาดบรรจุภัณฑ์: 50 x EA
- Grommet Type: Cable Grommet
 - Maximum Cable Diameter: 6.35 mm
 - Panel Hole Diameter: 9.52 mm
 - Material: PVC
 - Colour: Black
 - Maximum Panel Thickness: 2.4 mm



543282 Cable Grommet

RS PRO BLACK PVC 20MM CABLE GROMMET FOR MAXIMUM OF 16MM

- ขนาดบรรจุภัณฑ์: 100 x EA
- Grommet Type: Cable Grommet
 - Maximum Cable Diameter: 16 mm
 - Panel Hole Diameter: 20 mm
 - Material: PVC
 - Colour: Black
 - Maximum Panel Thickness: 1.6 mm



605649 Cable Grommet

RS PRO BLACK PVC 25MM CABLE GROMMET FOR MAXIMUM OF 18.5MM

- ขนาดบรรจุภัณฑ์: 100 x EA
- Grommet Type: Cable Grommet
 - Maximum Cable Diameter: 18.5 mm
 - Panel Hole Diameter: 25 mm
 - Material: PVC
 - Colour: Black
 - Maximum Panel Thickness: 1.6 mm



605655 Cable Grommet

RS PRO BLACK PVC 20MM CABLE GROMMET FOR MAXIMUM OF 16MM

- ขนาดบรรจุภัณฑ์: 100 x EA
- Grommet Type: Cable Grommet
 - Maximum Cable Diameter: 16 mm
 - Panel Hole Diameter: 20 mm
 - Material: PVC
 - Colour: Black
 - Maximum Panel Thickness: 1.5 mm



605661 Cable Grommet

RS PRO BLACK PVC 25MM CABLE GROMMET FOR MAXIMUM OF

- ขนาดบรรจุภัณฑ์: 100 x EA
- Grommet Type: Cable Grommet
 - Maximum Cable Diameter: 20.5 mm
 - Panel Hole Diameter: 25 mm
 - Material: PVC
 - Colour: Black
 - Maximum Panel Thickness: 1.5 mm



605677 Cable Grommet

GROMMET DA 80/110/ 10

- ขนาดบรรจุภัณฑ์: 100 x EA
- Grommet Type: Cable Grommet
 - Maximum Cable Diameter: 8 mm
 - Panel Hole Diameter: 11 mm
 - Material: Polychloroprene
 - Colour: Black
 - Series: HELAVIA
 - Maximum Panel Thickness: 1 mm



136604 Cable Grommet

GROMMET DA 90/160/15

- ขนาดบรรจุภัณฑ์: 100 x EA
- Grommet Type: Cable Grommet
 - Maximum Cable Diameter: 9 mm
 - Panel Hole Diameter: 20 mm
 - Material: Polychloroprene
 - Colour: Black
 - Series: HELAVIA
 - Maximum Panel Thickness: 1.5 mm



1366402 Cable Grommet

MEMBRANE GROMMET DG 53

- ขนาดบรรจุภัณฑ์: 50 x EA
- Grommet Type: Cable Grommet
 - Minimum Cable Diameter: 1 mm
 - Maximum Cable Diameter: 53 mm
 - Panel Hole Diameter: 64 mm
 - Material: Polychloroprene
 - Colour: Black
 - Series: DG



1366705 Cable Grommet

PVC GROMMET DK 3/5/8-2

- ขนาดบรรจุภัณฑ์: 100 x EA
- Grommet Type: Cable Grommet
 - Maximum Cable Diameter: 3 mm
 - Panel Hole Diameter: 5 mm
 - Material: PVC
 - Colour: Black
 - Series: PLIO
 - Maximum Panel Thickness: 2 mm



1366812 Cable Grommet

PVC GROMMET DK 5.5/8/12-1.5

- ขนาดบรรจุภัณฑ์: 100 x EA
- Grommet Type: Cable Grommet
 - Maximum Cable Diameter: 5.5 mm
 - Panel Hole Diameter: 8 mm
 - Material: PVC
 - Colour: Black
 - Series: PLIO
 - Maximum Panel Thickness: 1.5 mm



1366890 Cable Grommet

PVC GROMMET DK 6/9/12-1.5

- ขนาดบรรจุภัณฑ์: 100 x EA
- Grommet Type: Cable Grommet
 - Maximum Cable Diameter: 6 mm
 - Panel Hole Diameter: 9 mm
 - Material: PVC
 - Colour: Black
 - Series: PLIO
 - Maximum Panel Thickness: 1.5 mm



1366963 Cable Grommet

PVC GROMMET DK 7/14/18-1

- ขนาดบรรจุภัณฑ์: 100 x EA
- Grommet Type: Cable Grommet
 - Maximum Cable Diameter: 7 mm
 - Panel Hole Diameter: 14 mm
 - Material: PVC
 - Colour: Black
 - Series: PLIO
 - Maximum Panel Thickness: 1 mm



1367023 Cable Grommet

RS PRO BLACK PVC 18MM CABLE GROMMET FOR MAXIMUM OF 10MM

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Grommet Type: Cable Grommet
 - Maximum Cable Diameter: 10 mm
 - Panel Hole Diameter: 18 mm
 - Material: PVC
 - Colour: Black
 - Series: PLIO
 - Maximum Panel Thickness: 1 mm



1367130 Cable Grommet

RS PRO BLACK PVC 22MM CABLE GROMMET FOR MAXIMUM OF 14MM

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Grommet Type: Cable Grommet
 - Maximum Cable Diameter: 14 mm
 - Panel Hole Diameter: 22 mm
 - Material: PVC
 - Colour: Black
 - Series: PLIO
 - Maximum Panel Thickness: 3 mm



1367297 Cable Grommet

PVC GROMMET DK 16/22/27-2

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Grommet Type: Cable Grommet
 - Maximum Cable Diameter: 16 mm
 - Panel Hole Diameter: 22 mm
 - Material: PVC
 - Colour: Black
 - Series: PLIO
 - Maximum Panel Thickness: 2 mm



1367348 Cable Grommet

PVC GROMMET DK 18/22/27-3

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Grommet Type: Cable Grommet
 - Maximum Cable Diameter: 18 mm
 - Panel Hole Diameter: 22 mm
 - Material: PVC
 - Colour: Black
 - Series: PLIO
 - Maximum Panel Thickness: 3 mm



1367405 Cable Grommet

RS PRO BLACK POLYETHYLENE GROMMET STRIP

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Grommet Type: Grommet Strip
 - Minimum Panel Thickness: 1.6 mm
 - Material: Polyethylene
 - Colour: Black
 - Grommet Strip Length: 1.2 m



2133609 Grommet Strip

RS PRO GREY POLYETHYLENE GROMMET STRIP

- ขนาดบรรจุภัณฑ์: **30 x MTR**
- Grommet Type: Grommet Strip
 - Minimum Panel Thickness: 2 mm
 - Material: Polyethylene
 - Colour: Grey
 - Grommet Strip Length: 30 m



2133611 Grommet Strip

RS PRO BLACK PVC 31.7MM CABLE GROMMET FOR MAXIMUM OF 25MM

- ขนาดบรรจุภัณฑ์: **50 x EA**
- Minimum Panel Thickness: 1.5 mm
 - Grommet Type: Cable Grommet
 - Panel Hole Diameter: 31.7 mm
 - Maximum Cable Diameter: 25 mm
 - Material: PVC
 - Colour: Black



2133616 1.5 mm

RS PRO BLACK PVC 10.9MM CABLE GROMMET FOR MAXIMUM OF 7.8MM

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Minimum Panel Thickness: 2.3 mm
 - Grommet Type: Cable Grommet
 - Panel Hole Diameter: 10.9 mm
 - Maximum Cable Diameter: 7.8 mm
 - Material: PVC
 - Colour: Black



2133617 2.3 mm

RS PRO GREY POLYETHYLENE CABLE GROMMET

- ขนาดบรรจุภัณฑ์: **25 x MTR**
- Grommet Type: Cable Grommet
 - Minimum Panel Thickness: 1.2 mm
 - Material: Polyethylene
 - Colour: Grey
 - Grommet Strip Length: 25 m



2133618 Cable Grommet

RS PRO GREY POLYETHYLENE CABLE GROMMET

- ขนาดบรรจุภัณฑ์: **25 x MTR**
- Grommet Type: Cable Grommet
 - Minimum Panel Thickness: 2 mm
 - Material: Polyethylene
 - Colour: Grey
 - Grommet Strip Length: 25 m



2133619 Cable Grommet

RS PRO GREY NYLON 66 CABLE GROMMET

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Grommet Type: Cable Grommet
 - Minimum Panel Thickness: 2.4 mm
 - Material: Nylon 66
 - Colour: Grey



2133621 Cable Grommet

RS PRO GREY POLYETHYLENE CABLE GROMMET

- ขนาดบรรจุภัณฑ์: **25 x MTR**
- Grommet Type: Cable Grommet
 - Minimum Panel Thickness: 3.2 mm
 - Material: Polyethylene
 - Colour: Grey
 - Grommet Strip Length: 25 m



2133622 Cable Grommet

RS PRO BLACK PVC 12MM CABLE GROMMET FOR MAXIMUM OF 8MM

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Grommet Type: Cable Grommet
 - Maximum Cable Diameter: 8 mm
 - Panel Hole Diameter: 12 mm
 - Material: PVC
 - Colour: Black
 - Maximum Panel Thickness: 3 mm



2414580 Cable Grommet

RS PRO BLACK PVC 16MM CABLE GROMMET FOR MAXIMUM OF 12MM

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Grommet Type: Cable Grommet
 - Maximum Cable Diameter: 12 mm
 - Panel Hole Diameter: 16 mm
 - Material: PVC
 - Colour: Black
 - Maximum Panel Thickness: 3 mm



2414596 Cable Grommet

RS PRO BLACK PVC 22MM CABLE GROMMET FOR MAXIMUM OF 18MM

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Grommet Type: Cable Grommet
 - Maximum Cable Diameter: 18 mm
 - Panel Hole Diameter: 22 mm
 - Material: PVC
 - Colour: Black
 - Maximum Panel Thickness: 3 mm



2414603 Cable Grommet

437 PIECE PVC BLACK GROMMET KIT

- ขนาดบรรจุภัณฑ์: **1 x KT**
- Grommet Type: Cable Grommet Kit
 - Minimum Cable Diameter: 3 mm
 - Maximum Cable Diameter: 19 mm
 - Material: PVC
 - Colour: Black



6664584 Cable Grommet

PVC BLACK GROMMET 13.3MM BAG 100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Grommet Type: Cable Grommet
 - Maximum Cable Diameter: 6.4 mm
 - Panel Hole Diameter: 10 mm
 - Material: PVC
 - Colour: Black
 - Maximum Panel Thickness: 1.7 mm



6664590 Cable Grommet

PVC BLACK GROMMET 8.5MM BAG 100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Grommet Type: Cable Grommet
 - Maximum Cable Diameter: 3 mm
 - Panel Hole Diameter: 6 mm
 - Material: PVC
 - Colour: Black
 - Maximum Panel Thickness: 1.7 mm



6664593 Cable Grommet

PVC BLACK GROMMET 10.2MM BAG 100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Grommet Type: Cable Grommet
 - Maximum Cable Diameter: 5 mm
 - Panel Hole Diameter: 7.2 mm
 - Material: PVC
 - Colour: Black
 - Maximum Panel Thickness: 1.7 mm



6664596 Cable Grommet

PVC BLACK GROMMET 15.5MM BAG 100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Grommet Type: Cable Grommet
 - Maximum Cable Diameter: 7.8 mm
 - Panel Hole Diameter: 11 mm
 - Material: PVC
 - Colour: Black
 - Maximum Panel Thickness: 3 mm



6664600 Cable Grommet

PVC BLACK GROMMET 19.5MM BAG 100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Grommet Type: Cable Grommet
 - Maximum Cable Diameter: 10.5 mm
 - Panel Hole Diameter: 13.9 mm
 - Material: PVC
 - Colour: Black
 - Maximum Panel Thickness: 3.4 mm



6664603 Cable Grommet

PVC BLACK GROMMET 23.7MM BAG 100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Grommet Type: Cable Grommet
 - Maximum Cable Diameter: 15.5 mm
 - Panel Hole Diameter: 20.1 mm
 - Material: PVC
 - Colour: Black
 - Maximum Panel Thickness: 1.7 mm



6664607 Cable Grommet

PVC BLACK GROMMET 23.9MM BAG 100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Grommet Type: Cable Grommet
 - Maximum Cable Diameter: 15.5 mm
 - Panel Hole Diameter: 19.6 mm
 - Material: PVC
 - Colour: Black
 - Maximum Panel Thickness: 2 mm



6664613 Cable Grommet

PVC BLACK GROMMET 29.9MM BAG 100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Grommet Type: Cable Grommet
 - Maximum Cable Diameter: 18.9 mm
 - Panel Hole Diameter: 25.1 mm
 - Material: PVC
 - Colour: Black
 - Maximum Panel Thickness: 1.5 mm



6664616 Cable Grommet

PVC BLACK GROMMET 38.1MM BAG 100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Grommet Type: Cable Grommet
 - Maximum Cable Diameter: 25 mm
 - Panel Hole Diameter: 31.7 mm
 - Material: PVC
 - Colour: Black
 - Maximum Panel Thickness: 1.5 mm



6664619 Cable Grommet

PVC BLACK GROMMET 30MM BAG 100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Grommet Type: Cable Grommet
 - Maximum Cable Diameter: 20.8 mm
 - Panel Hole Diameter: 26 mm
 - Material: PVC
 - Colour: Black
 - Maximum Panel Thickness: 2.4 mm



6664622 Cable Grommet

EDGING GROMMET PE NATURAL 1.0MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Grommet Type: Grommet Strip
 - Minimum Panel Thickness: 0.5 mm
 - Minimum Cable Diameter: 0.5 mm
 - Maximum Cable Diameter: 1 mm
 - Material: PE
 - Colour: Natural
 - Grommet Strip Length: 10 m
 - Maximum Panel Thickness: 1 mm



8659714 Grommet Strip

RS PRO NATURAL PE GROMMET STRIP FOR 1.1 → 2MM CABLE DIA.

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Grommet Type: Grommet Strip
 - Minimum Panel Thickness: 1.6 mm
 - Minimum Cable Diameter: 1.1 mm
 - Maximum Cable Diameter: 2 mm
 - Material: PE
 - Colour: Natural
 - Grommet Strip Length: 10 m
 - Maximum Panel Thickness: 2 mm



8659720 Grommet Strip

RS PRO NATURAL PE GROMMET STRIP FOR 0.6 → 1.2MM CABLE DIA.

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Grommet Type: Grommet Strip
 - Minimum Panel Thickness: 1 mm
 - Minimum Cable Diameter: 0.6 mm
 - Maximum Cable Diameter: 1.2 mm
 - Material: PE
 - Colour: Natural
 - Grommet Strip Length: 10 m
 - Maximum Panel Thickness: 2 mm



8659723 Grommet Strip

RS PRO NATURAL PE GROMMET STRIP FOR 0.9 → 1.6MM CABLE DIA.

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Grommet Type: Grommet Strip
 - Minimum Panel Thickness: 1.2 mm
 - Minimum Cable Diameter: 0.9 mm
 - Maximum Cable Diameter: 1.6 mm
 - Material: PE
 - Colour: Natural
 - Grommet Strip Length: 10 m
 - Maximum Panel Thickness: 1.6 mm



8659726 Grommet Strip

RS PRO NATURAL PE GROMMET STRIP FOR 1.5 → 3.2MM CABLE DIA.

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Grommet Type: Grommet Strip
 - Minimum Panel Thickness: 2.4 mm
 - Minimum Cable Diameter: 1.5 mm
 - Maximum Cable Diameter: 3.2 mm
 - Material: PE
 - Colour: Natural
 - Grommet Strip Length: 10 m
 - Maximum Panel Thickness: 3.2 mm



8659732 Grommet Strip

EDGING GROMMET PE NATURAL 4.5-5.5MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Grommet Type: Grommet Strip
 - Minimum Panel Thickness: 4.5 mm
 - Minimum Cable Diameter: 4.5 mm
 - Maximum Cable Diameter: 5.5 mm
 - Material: PE
 - Colour: Natural
 - Grommet Strip Length: 10 m
 - Maximum Panel Thickness: 5.5 mm



8659736 Grommet Strip

RS PRO NATURAL PE GROMMET STRIP FOR 1.2 → 2.4MM CABLE DIA.

ขนาดบรรจุภัณฑ์: **1 x EA**

- Grommet Type: Grommet Strip
- Minimum Panel Thickness: 2 mm
- Minimum Cable Diameter: 1.2 mm
- Maximum Cable Diameter: 2.4 mm
- Material: PE
- Colour: Natural
- Grommet Strip Length: 10 m
- Maximum Panel Thickness: 2.4 mm



8659739 Grommet Strip

TOOL,APPLICATION,CABLE MARKER,0.7/4MM SQ

ขนาดบรรจุภัณฑ์: **1 x EA**

- Accessory Type: Cable Marker Application Tool
- For Use With: Helagrip Cable Markers Size B



404405 Cable Marker

TOOL,APPLICATION,CABLE MARKER,4/16MM SQ

ขนาดบรรจุภัณฑ์: **1 x EA**

- Accessory Type: Cable Marker Application Tool
- For Use With: Helagrip Cable Markers Size C



404409 Cable Marker

TOOL,APPLICATION,CABLE MARKER,0.5/0.78MM SQ

ขนาดบรรจุภัณฑ์: **1 x EA**

- Accessory Type: Cable Marker Application Tool
- For Use With: Helagrip Cable Markers Size A



404415 Cable Marker

RS PRO MARKER STRIP FOR OVAL SHAPE CABLE MARKER 9MM

ขนาดบรรจุภัณฑ์: **100 x EA**

- Accessory Type: Marker Strip
- For Use With: Oval shape cable marker
- Carrier Width: 9 mm
- Material: Nylon 66



2153048 Marker Strip

RS PRO MARKER STRIP FOR OVAL SHAPE CABLE MARKER 9MM

ขนาดบรรจุภัณฑ์: **100 x EA**

- Accessory Type: Marker Strip
- For Use With: Oval shape cable marker
- Carrier Width: 9 mm
- Material: Nylon 66



2153050 Marker Strip

RS PRO CABLE TIE CABLE MARKERS, WHITE

ขนาดบรรจุภัณฑ์: **100 x EA**

- Affixing Method: Cable Tie
- Maximum Cable Diameter: 4.8 mm
- Colour: White
- Length: 38.5 mm
- Width: 19 mm
- Quantity: 100
- Printable: No
- Material: Nylon 66



492291 Cable Tie

RS PRO CABLE TIE CABLE MARKERS, WHITE

ขนาดบรรจุภัณฑ์: **100 x EA**

- Affixing Method: Cable Tie
- Maximum Cable Diameter: 4.8 mm
- Colour: White
- Length: 45.3 mm
- Width: 19 mm
- Quantity: 100
- Printable: No
- Material: Nylon 66



492308 Cable Tie

CABLE,MARKER,PLATE,NYLON,19.1X5 0.8MM

ขนาดบรรจุภัณฑ์: **100 x EA**

- Affixing Method: Cable Tie
- Maximum Cable Diameter: 4.8 mm
- Colour: White
- Length: 50.5 mm
- Width: 19 mm
- Quantity: 100
- Printable: No
- Material: Nylon 66



492314 Cable Tie

RS PRO CABLE TIE CABLE MARKERS, WHITE

ขนาดบรรจุภัณฑ์: **100 x EA**

- Affixing Method: Cable Tie
- Maximum Cable Diameter: 4.8 mm
- Colour: White
- Length: 65 mm
- Width: 19 mm
- Quantity: 100
- Printable: No
- Material: Nylon 66



492320 Cable Tie

RS PRO SLIDE ON CABLE MARKER, WHITE ON BLACK, PRE-PRINTED "0"

ขนาดบรรจุภัณฑ์: **250 x EA**

- Affixing Method: Slide On
- Legend: 0
- Minimum Cable Diameter: 1.3 mm
- Maximum Cable Diameter: 3 mm
- Colour: White on Black
- Material: PVC
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: 60 °C



2153019 Slide On

RS PRO SLIDE ON CABLE MARKER, WHITE ON BROWN, PRE-PRINTED "1"

ขนาดบรรจุภัณฑ์: **250 x EA**

- Affixing Method: Slide On
- Legend: 1
- Minimum Cable Diameter: 1.3 mm
- Maximum Cable Diameter: 3 mm
- Colour: White on Brown
- Material: PVC
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: 60 °C



2153021 Slide On

RS PRO SLIDE ON CABLE MARKER, BLACK ON RED, PRE-PRINTED "2"

ขนาดบรรจุภัณฑ์: **250 x EA**

- Affixing Method: Slide On
- Legend: 2
- Minimum Cable Diameter: 1.3 mm
- Maximum Cable Diameter: 3 mm
- Colour: Black on Red
- Material: PVC
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: 60 °C



2153022 Slide On

RS PRO SLIDE ON CABLE MARKER, BLACK ON ORANGE, PRE-PRINTED "3"

ขนาดบรรจุภัณฑ์: **250 x EA**

- Affixing Method: Slide On
- Legend: 3
- Minimum Cable Diameter: 1.3 mm
- Maximum Cable Diameter: 3 mm
- Colour: Black on Orange
- Material: PVC
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: 60 °C



2153023 Slide On

RS PRO SLIDE ON CABLE MARKER, BLACK ON YELLOW, PRE-PRINTED "4"

ขนาดบรรจุภัณฑ์: **250 x EA**

- Affixing Method: Slide On
- Legend: 4
- Minimum Cable Diameter: 1.3 mm
- Maximum Cable Diameter: 3 mm
- Colour: Black on Yellow
- Material: PVC
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: 60 °C



2153024 Slide On

RS PRO SLIDE ON CABLE MARKER, BLACK ON GREEN, PRE-PRINTED "5"

ขนาดบรรจุภัณฑ์: **250 x EA**

- Affixing Method: Slide On
- Legend: 5
- Minimum Cable Diameter: 1.3 mm
- Maximum Cable Diameter: 3 mm
- Colour: Black on Green
- Material: PVC
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: 60 °C



2153025 Slide On

RS PRO SLIDE ON CABLE MARKER, BLACK ON WHITE, PRE-PRINTED "9"

- ขนาดบรรจุภัณฑ์: **250 x EA**
- Affixing Method: Slide On
 - Legend: 9
 - Minimum Cable Diameter: 2.5 mm
 - Maximum Cable Diameter: 5.1 mm
 - Colour: Black on White
 - Material: PVC
 - Minimum Operating Temperature: 0 °C
 - Maximum Operating Temperature: 60 °C



2153044 Slide On

RS PRO TIE CABLE MARKER, NATURAL

- ขนาดบรรจุภัณฑ์: **50 x EA**
- Affixing Method: Tie
 - Colour: Natural
 - Length: 30 mm
 - Width: 9.5 mm
 - Material: PE
 - Minimum Operating Temperature: 0 °C
 - Maximum Operating Temperature: 70 °C
 - Operating Temperature Range: 0°C→+70°C



2153046 Tie

RS PRO TIE CABLE MARKER, NATURAL

- ขนาดบรรจุภัณฑ์: **50 x EA**
- Affixing Method: Tie
 - Colour: Natural
 - Length: 40 mm
 - Width: 17 mm
 - Material: PE
 - Minimum Operating Temperature: 0 °C
 - Maximum Operating Temperature: 70 °C
 - Operating Temperature Range: 0°C→+70°C



2153047 Tie

RS PRO CLIP ON CABLE MARKER, WHITE ON BLACK, PRE-PRINTED "0"

- ขนาดบรรจุภัณฑ์: **1200 x EA**
- Affixing Method: Clip On
 - Legend: 0
 - Minimum Cable Diameter: 2.2 mm
 - Maximum Cable Diameter: 2.8 mm
 - Colour: White on Black
 - Material: Nylon 66
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: 85 °C



2153051 Clip On

RS PRO CLIP ON CABLE MARKER, WHITE ON BROWN, PRE-PRINTED "1"

- ขนาดบรรจุภัณฑ์: **1200 x EA**
- Affixing Method: Clip On
 - Legend: 1
 - Minimum Cable Diameter: 3 mm
 - Maximum Cable Diameter: 3.6 mm
 - Colour: White on Brown
 - Material: Nylon 66
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: 85 °C



2153056 Clip On

RS PRO SLIDE ON CABLE MARKER, BLACK ON WHITE, 3 → 4.2MM CABLE

- ขนาดบรรจุภัณฑ์: **250 x EA**
- Affixing Method: Slide On
 - Minimum Cable Diameter: 3 mm
 - Maximum Cable Diameter: 4.2 mm
 - Colour: Black on White
 - Printable: No
 - Material: PVC
 - Minimum Operating Temperature: 0 °C
 - Maximum Operating Temperature: +70 °C



2252169 Slide On

RS PRO SLIDE ON CABLE MARKER, BLACK ON WHITE, PRE-PRINTED "+", 3

- ขนาดบรรจุภัณฑ์: **250 x EA**
- Affixing Method: Slide On
 - Legend: +
 - Minimum Cable Diameter: 3 mm
 - Maximum Cable Diameter: 4.2 mm
 - Colour: Black on White
 - Printable: No
 - Material: PVC
 - Minimum Operating Temperature: 0 °C



2252170 Slide On

RS PRO SLIDE ON CABLE MARKER, BLACK ON WHITE, PRE-PRINTED

- ขนาดบรรจุภัณฑ์: **250 x EA**
- Affixing Method: Slide On
 - Legend: Earth
 - Minimum Cable Diameter: 3 mm
 - Maximum Cable Diameter: 4.2 mm
 - Colour: Black on White
 - Printable: No
 - Material: PVC
 - Minimum Operating Temperature: 0 °C



2252177 Slide On

RS PRO SLIDE ON CABLE MARKERS, BLACK ON YELLOW, PRE-PRINTED "1",

- ขนาดบรรจุภัณฑ์: **1000 x EA**
- Affixing Method: Slide On
 - Legend: 1
 - Minimum Cable Diameter: 3 mm
 - Maximum Cable Diameter: 4.2 mm
 - Colour: Black on Yellow
 - Length: 4 mm
 - Quantity: 1000
 - Printable: No



8120802 Slide On

RS PRO SLIDE ON CABLE MARKERS, BLACK ON YELLOW, PRE-PRINTED "2",

- ขนาดบรรจุภัณฑ์: **1000 x EA**
- Affixing Method: Slide On
 - Legend: 2
 - Minimum Cable Diameter: 3 mm
 - Maximum Cable Diameter: 4.2 mm
 - Colour: Black on Yellow
 - Length: 4 mm
 - Quantity: 1000
 - Printable: No



8120806 Slide On

RS PRO SLIDE ON CABLE MARKERS, BLACK ON YELLOW, PRE-PRINTED "0",

- ขนาดบรรจุภัณฑ์: **1000 x EA**
- Affixing Method: Slide On
 - Legend: 0
 - Minimum Cable Diameter: 3 mm
 - Maximum Cable Diameter: 4.2 mm
 - Colour: Black on Yellow
 - Length: 4 mm
 - Quantity: 1000
 - Printable: No



8120809 Slide On

RS PRO SLIDE ON CABLE MARKERS, BLACK ON YELLOW, PRE-PRINTED "5",

- ขนาดบรรจุภัณฑ์: **1000 x EA**
- Affixing Method: Slide On
 - Legend: 5
 - Minimum Cable Diameter: 3 mm
 - Maximum Cable Diameter: 4.2 mm
 - Colour: Black on Yellow
 - Length: 4 mm
 - Quantity: 1000
 - Printable: No



8120812 Slide On

RS PRO SLIDE ON CABLE MARKERS, BLACK ON YELLOW, PRE-PRINTED "3",

- ขนาดบรรจุภัณฑ์: **1000 x EA**
- Affixing Method: Slide On
 - Legend: 3
 - Minimum Cable Diameter: 3 mm
 - Maximum Cable Diameter: 4.2 mm
 - Colour: Black on Yellow
 - Length: 4 mm
 - Quantity: 1000
 - Printable: No



8120815 Slide On

RS PRO SLIDE ON CABLE MARKERS, BLACK ON YELLOW, PRE-PRINTED "4",

- ขนาดบรรจุภัณฑ์: **1000 x EA**
- Affixing Method: Slide On
 - Legend: 4
 - Minimum Cable Diameter: 3 mm
 - Maximum Cable Diameter: 4.2 mm
 - Colour: Black on Yellow
 - Length: 4 mm
 - Quantity: 1000
 - Printable: No



8120818 Slide On

RS PRO SLIDE ON CABLE MARKERS, BLACK ON YELLOW, PRE-PRINTED "6",

- ขนาดบรรจุภัณฑ์: **1000 x EA**
- Affixing Method: Slide On
 - Legend: 6
 - Minimum Cable Diameter: 3 mm
 - Maximum Cable Diameter: 4.2 mm
 - Colour: Black on Yellow
 - Length: 4 mm
 - Quantity: 1000
 - Printable: No



8120821 Slide On

RS PRO SLIDE ON CABLE MARKERS, BLACK ON YELLOW, PRE-PRINTED "7",

- ขนาดบรรจุภัณฑ์: **1000 x EA**
- Affixing Method: Slide On
 - Legend: 7
 - Minimum Cable Diameter: 3 mm
 - Maximum Cable Diameter: 4.2 mm
 - Colour: Black on Yellow
 - Length: 4 mm
 - Quantity: 1000
 - Printable: No



8120824 Slide On

RS PRO SLIDE ON CABLE MARKERS, BLACK ON YELLOW, PRE-PRINTED "T",

- ขนาดบรรจุภัณฑ์: **500 x EA**
- Affixing Method: Slide On
 - Legend: T
 - Minimum Cable Diameter: 3.5 mm
 - Maximum Cable Diameter: 7 mm
 - Colour: Black on Yellow
 - Length: 5 mm
 - Quantity: 500
 - Printable: No



8121168 Slide On

RS PRO SLIDE ON CABLE MARKERS, BLACK ON YELLOW, PRE-PRINTED "V",

- ขนาดบรรจุภัณฑ์: **500 x EA**
- Affixing Method: Slide On
 - Legend: V
 - Minimum Cable Diameter: 3.5 mm
 - Maximum Cable Diameter: 7 mm
 - Colour: Black on Yellow
 - Length: 5 mm
 - Quantity: 500
 - Printable: No



8121170 Slide On

RS PRO SLIDE ON CABLE MARKERS, BLACK ON YELLOW, PRE-PRINTED

- ขนาดบรรจุภัณฑ์: **500 x EA**
- Affixing Method: Slide On
 - Legend: W
 - Minimum Cable Diameter: 3.5 mm
 - Maximum Cable Diameter: 7 mm
 - Colour: Black on Yellow
 - Length: 5 mm
 - Quantity: 500
 - Printable: No



8121174 Slide On

RS PRO SLIDE ON CABLE MARKERS, BLACK ON YELLOW, PRE-PRINTED "U",

- ขนาดบรรจุภัณฑ์: **500 x EA**
- Affixing Method: Slide On
 - Legend: U
 - Minimum Cable Diameter: 3.5 mm
 - Maximum Cable Diameter: 7 mm
 - Colour: Black on Yellow
 - Length: 5 mm
 - Quantity: 500
 - Printable: No



8121177 Slide On

RS PRO SLIDE ON CABLE MARKERS, BLACK ON YELLOW, PRE-PRINTED "I",

- ขนาดบรรจุภัณฑ์: **500 x EA**
- Affixing Method: Slide On
 - Legend: -
 - Minimum Cable Diameter: 3.5 mm
 - Maximum Cable Diameter: 7 mm
 - Colour: Black on Yellow
 - Length: 5 mm
 - Quantity: 500
 - Printable: No



8121196 Slide On

RS PRO SLIDE ON CABLE MARKERS, BLACK ON YELLOW, PRE-PRINTED

- ขนาดบรรจุภัณฑ์: **500 x EA**
- Affixing Method: Slide On
 - Legend: O
 - Minimum Cable Diameter: 3.5 mm
 - Maximum Cable Diameter: 7 mm
 - Colour: Black on Yellow
 - Length: 5 mm
 - Quantity: 500
 - Printable: No



8121155 Slide On

RS PRO SLIDE ON CABLE MARKERS, BLACK ON YELLOW, PRE-PRINTED " / ",


- ขนาดบรรจุภัณฑ์: **500 x EA**
- Affixing Method: Slide On
 - Legend: /
 - Minimum Cable Diameter: 3.5 mm
 - Maximum Cable Diameter: 7 mm
 - Colour: Black on Yellow
 - Length: 5 mm
 - Quantity: 500
 - Printable: No



8121199 Slide On

RS PRO CLIP ON CABLE MARKERS, YELLOW, PRE-PRINTED "0 → 9"

- ขนาดบรรจุภัณฑ์: **150 x EA**
- Affixing Method: Clip On
 - Legend: 0 → 9
 - Colour: Yellow
 - Length: 2.9 mm
 - Quantity: 150
 - Printable: No
 - Material: Nylon 66
 - Standards Met: RoHS Compliant, UL, UL 94 V-2



8121203 Clip On

RS PRO CLIP ON CABLE MARKERS, BLACK ON YELLOW, PRE-PRINTED "A"

- ขนาดบรรจุภัณฑ์: **195 x EA**
- Affixing Method: Clip On
 - Legend: A → M
 - Colour: Black on Yellow
 - Length: 2.9 mm
 - Quantity: 195
 - Printable: No
 - Material: Nylon 66
 - Standards Met: RoHS Compliant, UL, UL 94 V-2



8121212 Clip On

RS PRO CLIP ON CABLE MARKERS, BLACK, BROWN, GREEN, GREY,

- ขนาดบรรจุภัณฑ์: **150 x EA**
- Affixing Method: Clip On
 - Legend: 0 → 9
 - Colour: Black, Brown, Green, Grey, Orange, Red, Violet, White, Yellow
 - Length: 2.8 mm
 - Quantity: 150
 - Printable: No
 - Material: Nylon 66
 - Standards Met: RoHS Compliant, UL, UL 94 V-2



8121219 Clip On

RS PRO CLIP ON CABLE MARKERS, BLACK, BROWN, GREEN, GREY,

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Affixing Method: Clip On
 - Legend: 0 → 9
 - Colour: Black, Brown, Green, Grey, Orange, Red, Violet, White, Yellow
 - Length: 2.9 mm
 - Quantity: 100
 - Printable: No
 - Material: Nylon 66
 - Standards Met: RoHS Compliant, UL, UL 94 V-2



8121225 Clip On

RS PRO CLIP ON CABLE MARKERS, BLACK, BROWN, GREEN, GREY,

- ขนาดบรรจุภัณฑ์: **250 x EA**
- Affixing Method: Clip On
 - Legend: 0 → 9
 - Colour: Black, Brown, Green, Grey, Orange, Red, Violet, White, Yellow
 - Length: 2.3 mm
 - Quantity: 250
 - Printable: No
 - Material: Nylon 66
 - Standards Met: RoHS Compliant, UL, UL 94 V-2



8121231 Clip On

RS PRO CLIP ON CABLE MARKERS, BLACK ON YELLOW, PRE-PRINTED "A"

- ขนาดบรรจุภัณฑ์: **130 x EA**
- Affixing Method: Clip On
 - Legend: A → M
 - Colour: Black on Yellow
 - Length: 2.9 mm
 - Quantity: 130
 - Printable: No
 - Material: Nylon 66
 - Standards Met: RoHS Compliant, UL, UL 94 V-2



8121234 Clip On

RS PRO CLIP ON CABLE MARKERS, BLACK ON YELLOW, PRE-PRINTED "N"

- ขนาดบรรจุภัณฑ์: **130 x EA**
- Affixing Method: Clip On
 - Legend: N → Z
 - Colour: Black on Yellow
 - Length: 2.9 mm
 - Quantity: 130
 - Printable: No
 - Material: Nylon 66
 - Standards Met: RoHS Compliant, UL, UL 94 V-2



8121237 Clip On

RS PRO CLIP ON CABLE MARKERS, BLACK ON YELLOW, PRE-PRINTED "A"

- ขนาดบรรจุภัณฑ์: **325 x EA**
- Affixing Method: Clip On
 - Legend: A → M
 - Colour: Black on Yellow
 - Length: 2.3 mm
 - Quantity: 325
 - Printable: No
 - Material: Nylon 66
 - Standards Met: RoHS Compliant, UL, UL 94 V-2



8121240 Clip On

RS PRO CLIP ON CABLE MARKERS, BLACK ON YELLOW, PRE-PRINTED "N"

- ขนาดบรรจุภัณฑ์: **325 x EA**
- Affixing Method: Clip On
 - Legend: N → Z
 - Colour: Black on Yellow
 - Length: 2.3 mm
 - Quantity: 325
 - Printable: No
 - Material: Nylon 66
 - Standards Met: RoHS Compliant, UL, UL 94 V-2



8121243 Clip On

RS PRO SNAP ON CABLE MARKERS, BLACK ON ORANGE, PRE-PRINTED

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Affixing Method: Snap On
 - Legend: 6
 - Minimum Cable Diameter: 4 mm
 - Maximum Cable Diameter: 5 mm
 - Colour: Black on Orange
 - Length: 4 mm
 - Quantity: 100
 - Printable: No



8121414 Snap On

RS PRO SNAP ON CABLE MARKERS, BLACK ON ORANGE, PRE-PRINTED

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Affixing Method: Snap On
 - Legend: 7
 - Minimum Cable Diameter: 4 mm
 - Maximum Cable Diameter: 5 mm
 - Colour: Black on Orange
 - Length: 4 mm
 - Quantity: 100
 - Printable: No



8121417 Snap On

RS PRO SNAP ON CABLE MARKERS, BLACK ON ORANGE, PRE-PRINTED

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Affixing Method: Snap On
 - Legend: 9
 - Minimum Cable Diameter: 4 mm
 - Maximum Cable Diameter: 5 mm
 - Colour: Black on Orange
 - Length: 4 mm
 - Quantity: 100
 - Printable: No



8121420 Snap On

RS PRO SNAP ON CABLE MARKERS, BLACK ON ORANGE, PRE-PRINTED

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Affixing Method: Snap On
 - Legend: A
 - Minimum Cable Diameter: 4 mm
 - Maximum Cable Diameter: 5 mm
 - Colour: Black on Orange
 - Length: 4 mm
 - Quantity: 100
 - Printable: No



8121423 Snap On

RS PRO SNAP ON CABLE MARKERS, BLACK ON ORANGE, PRE-PRINTED

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Affixing Method: Snap On
 - Legend: B
 - Minimum Cable Diameter: 4 mm
 - Maximum Cable Diameter: 5 mm
 - Colour: Black on Orange
 - Length: 4 mm
 - Quantity: 100
 - Printable: No



8121427 Snap On

RS PRO SNAP ON CABLE MARKERS, BLACK ON ORANGE, PRE-PRINTED

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Affixing Method: Snap On
 - Legend: C
 - Minimum Cable Diameter: 4 mm
 - Maximum Cable Diameter: 5 mm
 - Colour: Black on Orange
 - Length: 4 mm
 - Quantity: 100
 - Printable: No



8121436 Snap On

RS PRO SNAP ON CABLE MARKERS, BLACK ON ORANGE, PRE-PRINTED

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Affixing Method: Snap On
 - Legend: D
 - Minimum Cable Diameter: 4 mm
 - Maximum Cable Diameter: 5 mm
 - Colour: Black on Orange
 - Length: 4 mm
 - Quantity: 100
 - Printable: No



8121439 Snap On

RS PRO SNAP ON CABLE MARKERS, BLACK ON ORANGE, PRE-PRINTED

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Affixing Method: Snap On
 - Legend: M
 - Minimum Cable Diameter: 4 mm
 - Maximum Cable Diameter: 5 mm
 - Colour: Black on Orange
 - Length: 4 mm
 - Quantity: 100
 - Printable: No



8121467 Snap On

RS PRO SNAP ON CABLE MARKERS, BLACK ON ORANGE, PRE-PRINTED

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Affixing Method: Snap On
 - Legend: P
 - Minimum Cable Diameter: 4 mm
 - Maximum Cable Diameter: 5 mm
 - Colour: Black on Orange
 - Length: 4 mm
 - Quantity: 100
 - Printable: No



8121473 Snap On

RS PRO SNAP ON CABLE MARKERS, BLACK ON ORANGE, PRE-PRINTED

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Affixing Method: Snap On
 - Legend: R
 - Minimum Cable Diameter: 4 mm
 - Maximum Cable Diameter: 5 mm
 - Colour: Black on Orange
 - Length: 4 mm
 - Quantity: 100
 - Printable: No



8121486 Snap On

RS PRO SNAP ON CABLE MARKERS, BLACK ON ORANGE, PRE-PRINTED

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Affixing Method: Snap On
 - Legend: U
 - Minimum Cable Diameter: 4 mm
 - Maximum Cable Diameter: 5 mm
 - Colour: Black on Orange
 - Length: 4 mm
 - Quantity: 100
 - Printable: No



8121492 Snap On

RS PRO ADHESIVE CABLE MARKERS, BLACK ON WHITE, PRE-PRINTED "0" →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Affixing Method: Adhesive
 - Legend: 0 → 9
 - Colour: Black on White
 - Length: 33 mm
 - Width: 5.6 mm
 - Quantity: 10
 - Printable: No
 - Material: Vinyl Coated Cloth



8121528 Adhesive

RS PRO ADHESIVE CABLE MARKERS, BLACK ON WHITE, PRE-PRINTED "1" →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Affixing Method: Adhesive
 - Legend: 1 → 45
 - Colour: Black on White
 - Length: 33 mm
 - Width: 5.6 mm
 - Quantity: 10
 - Printable: No
 - Material: Vinyl Coated Cloth



8121530 Adhesive

RS PRO ADHESIVE CABLE MARKERS, BLACK ON WHITE, PRE-PRINTED "46" →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Affixing Method: Adhesive
 - Legend: 46 → 90
 - Colour: Black on White
 - Length: 33 mm
 - Width: 5.6 mm
 - Quantity: 10
 - Printable: No
 - Material: Vinyl Coated Cloth



8121534 Adhesive

RS PRO ADHESIVE CABLE MARKERS, BLACK ON WHITE, PRE-PRINTED "0" →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Affixing Method: Adhesive
 - Legend: 0 → 15; - / ; +; A → Z
 - Colour: Black on White
 - Length: 33 mm
 - Width: 5.6 mm
 - Quantity: 10
 - Printable: No
 - Material: Vinyl Coated Cloth



8121537 Adhesive

RS PRO CABLE TIE CABLE MARKERS, NATURAL

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Affixing Method: Cable Tie
 - Colour: Natural
 - Length: 130 mm
 - Width: 2.5 mm
 - Quantity: 100
 - Printable: No
 - Material: Nylon 66
 - Standards Met: cULus E97527, RoHS Compliant, UL, 94 V-2



8121540 Cable Tie

RS PRO CABLE TIE CABLE MARKERS, NATURAL

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Affixing Method: Cable Tie
 - Colour: Natural
 - Length: 270 mm
 - Width: 4.6 mm
 - Quantity: 100
 - Printable: No
 - Material: Nylon 66
 - Standards Met: cULus E97527, RoHS Compliant, UL, UL 94 V-2



8121543 Cable Tie

RS PRO CABLE TIE CABLE MARKERS, NATURAL

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Affixing Method: Cable Tie
 - Colour: Natural
 - Length: 200 mm
 - Width: 4.6 mm
 - Quantity: 100
 - Printable: No
 - Material: Nylon 66
 - Standards Met: cULus E97527, RoHS Compliant, UL, UL 94 V-2



8121546 Cable Tie

RS PRO CABLE TIE CABLE MARKERS, NATURAL

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Affixing Method: Cable Tie
 - Colour: Natural
 - Length: 300 mm
 - Width: 4.8 mm
 - Quantity: 100
 - Printable: No
 - Material: Nylon 66
 - Standards Met: cULus E97527, RoHS Compliant, UL, UL 94 V-2



8121552 Cable Tie

RS PRO CABLE TIE CABLE MARKERS, NATURAL

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Affixing Method: Cable Tie
 - Colour: Natural
 - Length: 110 mm
 - Width: 2.5 mm
 - Quantity: 100
 - Printable: No
 - Material: Nylon 66
 - Standards Met: cULus E97527, RoHS Compliant, UL, UL 94 V-2



8121559 Cable Tie

RS PRO HEAT SHRINK CABLE MARKER, WHITE, 1.1 → 2.7MM CABLE

- ขนาดบรรจุภัณฑ์: **250 x EA**
- Affixing Method: Heat Shrink
 - Minimum Cable Diameter: 1.1 mm
 - Maximum Cable Diameter: 2.7 mm
 - Colour: White
 - Width: 3.2 mm
 - Quantity: 250
 - Material: Polyolefin
 - Minimum Operating Temperature: -55 °C



8726202 Heat Shrink

RS PRO HEAT SHRINK CABLE MARKER, WHITE, 2.3 → 5.5MM CABLE

- ขนาดบรรจุภัณฑ์: **1000 x EA**
- Affixing Method: Heat Shrink
 - Minimum Cable Diameter: 2.3 mm
 - Maximum Cable Diameter: 5.5 mm
 - Colour: White
 - Width: 6.4 mm
 - Quantity: 1000
 - Material: Polyolefin
 - Minimum Operating Temperature: -55 °C



8726242 Heat Shrink

RS PRO HEAT SHRINK CABLE MARKER, WHITE, 2.3 → 5.5MM CABLE

- ขนาดบรรจุภัณฑ์: **250 x EA**
- Affixing Method: Heat Shrink
 - Minimum Cable Diameter: 2.3 mm
 - Maximum Cable Diameter: 5.5 mm
 - Colour: White
 - Width: 6.4 mm
 - Quantity: 250
 - Material: Polyolefin
 - Minimum Operating Temperature: -55 °C



8726249 Heat Shrink

RS PRO HEAT SHRINK CABLE MARKER, WHITE, 4.7 → 10.8MM CABLE

- ขนาดบรรจุภัณฑ์: **250 x EA**
- Affixing Method: Heat Shrink
 - Minimum Cable Diameter: 4.7 mm
 - Maximum Cable Diameter: 10.8 mm
 - Colour: White
 - Width: 12.7 mm
 - Quantity: 250
 - Material: Polyolefin
 - Minimum Operating Temperature: -55 °C



8726261 Heat Shrink

RS PRO SLIDE ON CABLE MARKER KIT, BLACK, BLUE, BROWN, GREEN, GREY,

- ขนาดบรรจุภัณฑ์: **1 x KT**
- Affixing Method: Slide On
 - Legend: -, +, 0 → 9, Earth, L, N, Plain, R, S, T
 - Minimum Cable Diameter: 2 mm
 - Maximum Cable Diameter: 8 mm
 - Colour: Black, Blue, Brown, Green, Grey, Orange, Red, Violet, White, Yellow
 - Quantity: 3600
 - Printable: No
 - Material: PVC



9140592 Slide On

RS PRO SLIDE ON CABLE MARKER KIT, BLACK, BLUE, BROWN, GREEN, GREY,

- ขนาดบรรจุภัณฑ์: **1 x KT**
- Affixing Method: Slide On
 - Legend: -, +, 0 → 9, Earth, L, N, Plain, R, S, T
 - Minimum Cable Diameter: 0.75 mm
 - Maximum Cable Diameter: 3.5 mm
 - Colour: Black, Blue, Brown, Green, Grey, Orange, Red, Violet, White, Yellow
 - Quantity: 4500
 - Printable: No
 - Material: PVC



9140602 Slide On

RS PRO SLIDE ON CABLE MARKER KIT, BLACK, BLUE, BROWN, GREEN, GREY,

- ขนาดบรรจุภัณฑ์: **1 x KT**
- Affixing Method: Slide On
 - Legend: -, +, 0 → 9, Earth, L, N, Plain, R, S, T
 - Minimum Cable Diameter: 0.75 mm
 - Maximum Cable Diameter: 8 mm
 - Colour: Black, Blue, Brown, Green, Grey, Orange, Red, Violet, White, Yellow
 - Quantity: 2700
 - Printable: No
 - Material: PVC



9140605 Slide On

CABLE, SLEEVE, HEAT RESISTING, GLASS FIBRE, BORE

- ขนาดบรรจุภัณฑ์: **3 x EA**
- Sleeve Diameter: 2 mm
 - Colour: Red
 - Material: Acrylic Fibreglass
 - Sleeve Length: 5 m
 - Braided: Yes
 - Expandable: No
 - Minimum Operating Temperature: -25 °C
 - Maximum Operating Temperature: +155 °C



398745 2 mm

CABLE, SLEEVE, HEAT RESISTING, GLASS FIBRE, BORE

- ขนาดบรรจุภัณฑ์: **3 x EA**
- Sleeve Diameter: 2 mm
 - Colour: Black
 - Material: Acrylic Fibreglass
 - Sleeve Length: 5 m
 - Braided: Yes
 - Expandable: No
 - Minimum Cable Diameter: 2 mm
 - Minimum Operating Temperature: -25 °C



398751 2 mm

CABLE, SLEEVE, HEAT RESISTING, GLASS FIBRE, BORE

- ขนาดบรรจุภัณฑ์: **3 x EA**
- Sleeve Diameter: 4 mm
 - Colour: Red
 - Material: Acrylic Fibreglass
 - Sleeve Length: 5 m
 - Braided: Yes
 - Expandable: No
 - Minimum Cable Diameter: 4 mm
 - Minimum Operating Temperature: -25 °C



398846 4 mm

RS PRO BRAIDED ACRYLIC FIBREGLASS BLACK CABLE SLEEVE,

- ขนาดบรรจุภัณฑ์: **3 x EA**
- Sleeve Diameter: 4 mm
 - Colour: Black
 - Material: Acrylic Fibreglass
 - Sleeve Length: 5 m
 - Braided: Yes
 - Expandable: No
 - Minimum Cable Diameter: 4 mm
 - Maximum Cable Diameter: 4 mm



398852 4 mm

RS PRO BRAIDED ACRYLIC FIBREGLASS GREEN CABLE SLEEVE,

- ขนาดบรรจุภัณฑ์: **3 x EA**
- Sleeve Diameter: 4 mm
 - Colour: Green
 - Material: Acrylic Fibreglass
 - Sleeve Length: 5 m
 - Braided: Yes
 - Expandable: No
 - Minimum Cable Diameter: 4 mm
 - Minimum Operating Temperature: -25 °C



398874 4 mm

CABLE,SLEEVE,HEAT RESISTING,GLASS FIBRE,BORE

- ขนาดบรรจุภัณฑ์: **3 x EA**
- Sleeve Diameter: 4 mm
 - Colour: Blue
 - Material: Acrylic Fibreglass
 - Sleeve Length: 5 m
 - Braided: Yes
 - Expandable: No
 - Minimum Cable Diameter: 4 mm
 - Minimum Operating Temperature: -25 °C



398880 4 mm

CABLE,SLEEVE,HEAT RESISTING,GLASS FIBRE,BORE

- ขนาดบรรจุภัณฑ์: **2 x EA**
- Sleeve Diameter: 6 mm
 - Colour: Red
 - Material: Acrylic Fibreglass
 - Sleeve Length: 5 m
 - Braided: Yes
 - Expandable: No
 - Minimum Cable Diameter: 6 mm
 - Minimum Operating Temperature: -25 °C



398896 6 mm

CABLE,SLEEVE,HEAT RESISTING,GLASS FIBRE,BORE

- ขนาดบรรจุภัณฑ์: **2 x EA**
- Sleeve Diameter: 6 mm
 - Colour: Black
 - Material: Acrylic Fibreglass
 - Sleeve Length: 5 m
 - Braided: Yes
 - Expandable: No
 - Minimum Cable Diameter: 6 mm
 - Minimum Operating Temperature: -25 °C



398903 6 mm

RS PRO SILICONE RUBBER GREEN CABLE SLEEVE, 1MM DIAMETER, 15M

- ขนาดบรรจุภัณฑ์: **15 x MTR**
- Sleeve Diameter: 1 mm
 - Colour: Green
 - Material: Silicone Rubber
 - Sleeve Length: 15 m
 - Braided: No
 - Minimum Operating Temperature: -60 °C
 - Maximum Operating Temperature: +180 °C
 - Standards Met: RoHS Compliant, UL E345553



399401 1 mm

RS PRO SILICONE RUBBER RED CABLE SLEEVE, 1MM DIAMETER, 15M LENGTH

- ขนาดบรรจุภัณฑ์: **15 x MTR**
- Sleeve Diameter: 1 mm
 - Colour: Red
 - Material: Silicone Rubber
 - Sleeve Length: 15 m
 - Braided: No
 - Minimum Operating Temperature: -60 °C
 - Maximum Operating Temperature: +180 °C
 - Dielectric Strength: 20 kV/mm



399417 1 mm

CABLE,SLEEVE,HEAT RESISTANT,SILICONE RUBBER,BORE

- ขนาดบรรจุภัณฑ์: **10 x MTR**
- Sleeve Diameter: 2 mm
 - Colour: Green
 - Material: Silicone Rubber
 - Sleeve Length: 10 m
 - Braided: No
 - Minimum Operating Temperature: -60 °C
 - Maximum Operating Temperature: +180 °C
 - Dielectric Strength: 20 kV/mm



399439 2 mm

CABLE,SLEEVE,HEAT RESISTANT,SILICONE RUBBER,BORE

- ขนาดบรรจุภัณฑ์: **10 x MTR**
- Sleeve Diameter: 2 mm
 - Colour: Red
 - Material: Silicone Rubber
 - Sleeve Length: 10 m
 - Braided: No
 - Minimum Operating Temperature: -60 °C
 - Maximum Operating Temperature: +180 °C
 - Dielectric Strength: 20 kV/mm



399445 2 mm

RS PRO BRAIDED ACRYLIC FIBREGLASS BROWN CABLE SLEEVE,

- ขนาดบรรจุภัณฑ์: **3 x EA**
- Sleeve Diameter: 2 mm
 - Colour: Brown
 - Material: Acrylic Fibreglass
 - Sleeve Length: 5 m
 - Braided: Yes
 - Expandable: No
 - Minimum Cable Diameter: 4 mm
 - Minimum Operating Temperature: -25 °C



399568 4 mm

CABLE,SLEEVE,PVC,3MM BORE, GREEN/YELLOW, 40M

- ขนาดบรรจุภัณฑ์: **40 x MTR**
- Sleeve Diameter: 3 mm
 - Colour: Green, Yellow
 - Material: PVC
 - Sleeve Length: 40 m
 - Braided: No
 - Minimum Cable Diameter: 3 mm
 - Minimum Operating Temperature: -20 °C
 - Maximum Operating Temperature: +85 °C



404130 3 mm

RS PRO PVC BLUE CABLE SLEEVE, 3MM DIAMETER, 40M LENGTH

- ขนาดบรรจุภัณฑ์: **40 x MTR**
- Sleeve Diameter: 3 mm
 - Colour: Blue
 - Material: PVC
 - Sleeve Length: 40 m
 - Braided: No
 - Minimum Cable Diameter: 3 mm
 - Minimum Operating Temperature: -20 °C
 - Maximum Operating Temperature: +85 °C



404134 3 mm

CABLE,SLEEVE,PVC,3MM BORE, BLACK, 40M

- ขนาดบรรจุภัณฑ์: **40 x MTR**
- Sleeve Diameter: 3 mm
 - Colour: Black
 - Material: PVC
 - Sleeve Length: 40 m
 - Braided: No
 - Minimum Cable Diameter: 3 mm
 - Minimum Operating Temperature: -20 °C
 - Maximum Operating Temperature: +85 °C



404140 3 mm

RS PRO PVC RED CABLE SLEEVE, 4MM DIAMETER, 30M LENGTH

- ขนาดบรรจุภัณฑ์: **30 x MTR**
- Sleeve Diameter: 4 mm
 - Colour: Red
 - Material: PVC
 - Sleeve Length: 30 m
 - Braided: No
 - Minimum Cable Diameter: 4 mm
 - Minimum Operating Temperature: -20 °C
 - Maximum Operating Temperature: +85 °C



404146 4 mm

RS PRO PVC GREEN, YELLOW CABLE SLEEVE, 4MM DIAMETER, 30M LENGTH

- ขนาดบรรจุภัณฑ์: **30 x MTR**
- Sleeve Diameter: 4 mm
 - Colour: Green, Yellow
 - Material: PVC
 - Sleeve Length: 30 m
 - Braided: No
 - Minimum Cable Diameter: 4 mm
 - Minimum Operating Temperature: -20 °C
 - Maximum Operating Temperature: +85 °C



404162 4 mm

RS PRO PVC BLUE CABLE SLEEVE, 4MM DIAMETER, 30M LENGTH

- ขนาดบรรจุภัณฑ์: **30 x MTR**
- Sleeve Diameter: 4 mm
 - Colour: Blue
 - Material: PVC
 - Sleeve Length: 30 m
 - Braided: No
 - Minimum Cable Diameter: 4 mm
 - Minimum Operating Temperature: -20 °C
 - Maximum Operating Temperature: +85 °C



404168 4 mm

RS PRO PVC GREEN CABLE SLEEVE, 4MM DIAMETER, 30M LENGTH

- ขนาดบรรจุภัณฑ์: **30 x MTR**
- Sleeve Diameter: 4 mm
 - Colour: Green
 - Material: PVC
 - Sleeve Length: 30 m
 - Braided: No
 - Minimum Cable Diameter: 4 mm
 - Minimum Operating Temperature: -20 °C
 - Maximum Operating Temperature: +85 °C



404174 4 mm

RS PRO PVC BROWN CABLE SLEEVE, 4MM DIAMETER, 30M LENGTH

- ขนาดบรรจุภัณฑ์: **30 x MTR**
- Sleeve Diameter: 4 mm
 - Colour: Brown
 - Material: PVC
 - Sleeve Length: 30 m
 - Braided: No
 - Minimum Cable Diameter: 4 mm
 - Minimum Operating Temperature: -20 °C
 - Maximum Operating Temperature: +85 °C



404178 4 mm

CABLE,SLEEVE,PVC,4MM BORE,BLACK,30M

ขนาดบรรจุภัณฑ์: 30 x MTR

- Sleeve Diameter: 4 mm
- Colour: Black
- Material: PVC
- Sleeve Length: 30 m
- Braided: No
- Minimum Cable Diameter: 4 mm
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +85 °C



404180 4 mm

RS PRO PVC GREY CABLE SLEEVE, 4MM DIAMETER, 30M LENGTH

ขนาดบรรจุภัณฑ์: 30 x MTR

- Sleeve Diameter: 4 mm
- Colour: Grey
- Material: PVC
- Sleeve Length: 30 m
- Braided: No
- Minimum Cable Diameter: 4 mm
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +85 °C



404184 4 mm

RS PRO PVC RED CABLE SLEEVE, 2MM DIAMETER, 50M LENGTH

ขนาดบรรจุภัณฑ์: 50 x MTR

- Sleeve Diameter: 2 mm
- Colour: Red
- Material: PVC
- Sleeve Length: 50 m
- Braided: No
- Minimum Cable Diameter: 2 mm
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +85 °C



404190 2 mm

CABLE,SLEEVE,PVC,6MM BORE,BLACK,10M

ขนาดบรรจุภัณฑ์: 10 x MTR

- Sleeve Diameter: 6 mm
- Colour: Black
- Material: PVC
- Sleeve Length: 10 m
- Braided: No
- Minimum Cable Diameter: 6 mm
- Maximum Cable Diameter: 6 mm
- Minimum Operating Temperature: -20 °C



404196 6 mm

CABLE,SLEEVE,PVC,6MM BORE,BLUE,10M

ขนาดบรรจุภัณฑ์: 10 x MTR

- Sleeve Diameter: 6 mm
- Colour: Blue
- Material: PVC
- Sleeve Length: 10 m
- Braided: No
- Minimum Cable Diameter: 6 mm
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +85 °C



404203 6 mm

RS PRO PVC BROWN CABLE SLEEVE, 6MM DIAMETER, 10M LENGTH

ขนาดบรรจุภัณฑ์: 10 x MTR

- Sleeve Diameter: 6 mm
- Colour: Brown
- Material: PVC
- Sleeve Length: 10 m
- Braided: No
- Minimum Cable Diameter: 6 mm
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +85 °C



404207 6 mm

CABLE,SLEEVE,PVC,6MM BORE,GREY,10M

ขนาดบรรจุภัณฑ์: 10 x MTR

- Sleeve Diameter: 6 mm
- Colour: Grey
- Material: PVC
- Sleeve Length: 10 m
- Braided: No
- Minimum Cable Diameter: 6 mm
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +85 °C



404213 6 mm

CABLE,SLEEVE,PVC,6MM BORE,GREEN/YELLOW,10M

ขนาดบรรจุภัณฑ์: 10 x MTR

- Sleeve Diameter: 6 mm
- Colour: Green, Yellow
- Material: PVC
- Sleeve Length: 10 m
- Braided: No
- Minimum Cable Diameter: 6 mm
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +85 °C



404219 6 mm

RS PRO PVC GREEN CABLE SLEEVE, 2MM DIAMETER, 50M LENGTH

ขนาดบรรจุภัณฑ์: 50 x MTR

- Sleeve Diameter: 2 mm
- Colour: Green
- Material: PVC
- Sleeve Length: 50 m
- Braided: No
- Minimum Cable Diameter: 2 mm
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +85 °C



404225 2 mm

CABLE,SLEEVE,PVC,10MM BORE,BLACK,10M

ขนาดบรรจุภัณฑ์: 10 x MTR

- Sleeve Diameter: 10 mm
- Colour: Black
- Material: PVC
- Sleeve Length: 10 m
- Braided: No
- Minimum Cable Diameter: 10 mm
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +85 °C



404229 10 mm

CABLE,SLEEVE,PVC,2MM BORE,GREEN/YELLOW,50M

ขนาดบรรจุภัณฑ์: 50 x MTR

- Sleeve Diameter: 2 mm
- Colour: Green, Yellow
- Material: PVC
- Sleeve Length: 50 m
- Braided: No
- Minimum Cable Diameter: 2 mm
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +85 °C



404231 2 mm

CABLE,SLEEVE,PVC,2MM BORE,BLACK,50M

ขนาดบรรจุภัณฑ์: 50 x MTR

- Sleeve Diameter: 2 mm
- Colour: Black
- Material: PVC
- Sleeve Length: 50 m
- Braided: No
- Minimum Cable Diameter: 2 mm
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +85 °C



404235 2 mm

RS PRO PVC GREY CABLE SLEEVE, 2MM DIAMETER, 50M LENGTH

ขนาดบรรจุภัณฑ์: 50 x MTR

- Sleeve Diameter: 2 mm
- Colour: Grey
- Material: PVC
- Sleeve Length: 50 m
- Braided: No
- Minimum Cable Diameter: 2 mm
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +85 °C



404247 2 mm

RS PRO PVC BROWN CABLE SLEEVE, 10MM DIAMETER, 10M LENGTH

ขนาดบรรจุภัณฑ์: 10 x MTR

- Sleeve Diameter: 10 mm
- Colour: Brown
- Material: PVC
- Sleeve Length: 10 m
- Braided: No
- Minimum Cable Diameter: 10 mm
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +85 °C



404499 10 mm

RS PRO PVC BLUE CABLE SLEEVE, 10MM DIAMETER, 10M LENGTH

ขนาดบรรจุภัณฑ์: 10 x MTR

- Sleeve Diameter: 10 mm
- Colour: Blue
- Material: PVC
- Sleeve Length: 10 m
- Braided: No
- Minimum Cable Diameter: 10 mm
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +85 °C



404506 10 mm

CABLE,SLEEVE,PVC,10MM BORE,GREEN/YELLOW,10M

ขนาดบรรจุภัณฑ์: 10 x MTR

- Sleeve Diameter: 10 mm
- Colour: Green, Yellow
- Material: PVC
- Sleeve Length: 10 m
- Braided: No
- Minimum Cable Diameter: 10 mm
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +85 °C



404528 10 mm

CABLE,SLEEVE,EXPANDABLE,BRAIDED ,FLEXIBLE,GREY,DIA.

- ขนาดบรรจุภัณฑ์: **5 x MTR**
- Sleeve Diameter: 30 mm
 - Colour: Grey
 - Material: PET
 - Sleeve Length: 5 m
 - Braided: Yes
 - Expandable: Yes
 - Minimum Cable Diameter: 25 mm
 - Maximum Cable Diameter: 45 mm



408192 30 mm

CABLE,SLEEVE,EXPANDABLE,BRAIDED ,FLEXIBLE,BLACK,DIA

- ขนาดบรรจุภัณฑ์: **5 x MTR**
- Sleeve Diameter: 5 mm
 - Colour: Black
 - Material: PET
 - Sleeve Length: 5 m
 - Braided: Yes
 - Expandable: Yes
 - Minimum Cable Diameter: 3 mm
 - Maximum Cable Diameter: 10 mm



408198 5 mm

CABLE,SLEEVE,EXPANDABLE,BRAIDED ,FLEXIBLE,BLACK,DIA

- ขนาดบรรจุภัณฑ์: **5 x MTR**
- Sleeve Diameter: 15 mm
 - Colour: Black
 - Material: PET
 - Sleeve Length: 5 m
 - Braided: Yes
 - Expandable: Yes
 - Minimum Cable Diameter: 10 mm
 - Maximum Cable Diameter: 25 mm



408205 15 mm

CABLE,SLEEVE,EXPANDABLE,BRAIDED ,FLEXIBLE,BLACK,DIA

- ขนาดบรรจุภัณฑ์: **5 x MTR**
- Sleeve Diameter: 10 mm
 - Colour: Black
 - Material: PET
 - Sleeve Length: 5 m
 - Braided: Yes
 - Expandable: Yes
 - Minimum Cable Diameter: 6 mm
 - Maximum Cable Diameter: 18 mm



408209 10 mm

CABLE,SLEEVE,EXPANDABLE,BRAIDED ,FLEXIBLE,BLACK,DIA

- ขนาดบรรจุภัณฑ์: **5 x MTR**
- Sleeve Diameter: 30 mm
 - Colour: Black
 - Material: PET
 - Sleeve Length: 5 m
 - Braided: Yes
 - Expandable: Yes
 - Minimum Cable Diameter: 25 mm
 - Maximum Cable Diameter: 45 mm



408211 30 mm

CABLE,SLEEVE,EXPANDABLE,BRAIDED ,FLEXIBLE,BLACK,DIA

- ขนาดบรรจุภัณฑ์: **5 x MTR**
- Sleeve Diameter: 20 mm
 - Colour: Black
 - Material: PET
 - Sleeve Length: 5 m
 - Braided: Yes
 - Expandable: Yes
 - Minimum Cable Diameter: 12 mm
 - Maximum Cable Diameter: 30 mm



408215 20 mm

CABLE,SLEEVE,EXPANDABLE,BRAIDED ,FLEXIBLE,BLACK,DIA

- ขนาดบรรจุภัณฑ์: **5 x MTR**
- Sleeve Diameter: 40 mm
 - Colour: Black
 - Material: PET
 - Sleeve Length: 5 m
 - Braided: Yes
 - Expandable: Yes
 - Minimum Cable Diameter: 35 mm
 - Maximum Cable Diameter: 60 mm



408221 40 mm

CABLE,SLEEVE,EXPANDABLE,BRAIDED ,FLEXIBLE,BLACK,DIA

- ขนาดบรรจุภัณฑ์: **5 x MTR**
- Sleeve Diameter: 50 mm
 - Colour: Black
 - Material: PET
 - Sleeve Length: 5 m
 - Braided: Yes
 - Expandable: Yes
 - Minimum Cable Diameter: 45 mm
 - Maximum Cable Diameter: 73 mm



408227 50 mm

CABLE,SLEEVE,EXPANDABLE,BRAIDED ,FLEXIBLE,GREY,DIA.

- ขนาดบรรจุภัณฑ์: **5 x MTR**
- Sleeve Diameter: 20 mm
 - Colour: Grey
 - Material: PET
 - Sleeve Length: 5 m
 - Braided: Yes
 - Expandable: Yes
 - Minimum Cable Diameter: 12 mm
 - Maximum Cable Diameter: 30 mm



408233 20 mm

CABLE,SLEEVE,EXPANDABLE,BRAIDED ,FLEXIBLE,GREY,DIA.

- ขนาดบรรจุภัณฑ์: **5 x MTR**
- Sleeve Diameter: 10 mm
 - Colour: Grey
 - Material: PET
 - Sleeve Length: 5 m
 - Braided: Yes
 - Expandable: Yes
 - Minimum Cable Diameter: 6 mm
 - Maximum Cable Diameter: 18 mm



408237 10 mm

CABLE,SLEEVE,EXPANDABLE,BRAIDED ,FLEXIBLE,GREY,DIA.

- ขนาดบรรจุภัณฑ์: **5 x MTR**
- Sleeve Diameter: 5 mm
 - Colour: Grey
 - Material: PET
 - Sleeve Length: 5 m
 - Braided: Yes
 - Expandable: Yes
 - Minimum Cable Diameter: 3 mm
 - Maximum Cable Diameter: 10 mm



408243 5 mm

RS PRO EXPANDABLE BRAIDED PET GREY CABLE SLEEVE, 15MM

- ขนาดบรรจุภัณฑ์: **5 x MTR**
- Sleeve Diameter: 15 mm
 - Colour: Grey
 - Material: PET
 - Sleeve Length: 5 m
 - Braided: Yes
 - Expandable: Yes
 - Minimum Cable Diameter: 10 mm
 - Maximum Cable Diameter: 25 mm



408249 15 mm

RS PRO EXPANDABLE BRAIDED PET GREY CABLE SLEEVE, 50MM

- ขนาดบรรจุภัณฑ์: **5 x MTR**
- Sleeve Diameter: 50 mm
 - Colour: Grey
 - Material: PET
 - Sleeve Length: 5 m
 - Braided: Yes
 - Expandable: Yes
 - Minimum Cable Diameter: 45 mm
 - Maximum Cable Diameter: 73 mm



408255 50 mm

RS PRO EXPANDABLE BRAIDED PET GREY CABLE SLEEVE, 40MM

- ขนาดบรรจุภัณฑ์: **5 x MTR**
- Sleeve Diameter: 40 mm
 - Colour: Grey
 - Material: PET
 - Sleeve Length: 5 m
 - Braided: Yes
 - Expandable: Yes
 - Minimum Cable Diameter: 35 mm
 - Maximum Cable Diameter: 60 mm



408259 40 mm

CABLE,SLEEVING,BRAIDED,EXPANDABLE,POLYESTER,25MM,1

- ขนาดบรรจุภัณฑ์: **10 x MTR**
- Sleeve Diameter: 25 mm
 - Colour: Black
 - Material: PET
 - Sleeve Length: 10 m
 - Braided: Yes
 - Expandable: Yes
 - Minimum Cable Diameter: 10 mm
 - Maximum Cable Diameter: 30 mm



408271 25 mm

CABLE,SLEEVING,BRAIDED,EXPANDABLE,POLYESTER,15MM,1

- ขนาดบรรจุภัณฑ์: **10 x MTR**
- Sleeve Diameter: 10 mm
 - Colour: Black
 - Material: PET
 - Sleeve Length: 10 m
 - Braided: Yes
 - Expandable: Yes
 - Minimum Cable Diameter: 5 mm
 - Maximum Cable Diameter: 21 mm



408277 10 mm

CABLE, SLEEVING, BRAIDED, EXPANDABLE, POLYESTER, 12MM, 3

ขนาดบรรจุภัณฑ์: **30 x MTR**

- Sleeve Diameter: 12 mm
- Colour: Black
- Material: PET
- Sleeve Length: 30 m
- Braided: Yes
- Expandable: Yes
- Minimum Cable Diameter: 6.35 mm
- Maximum Cable Diameter: 19 mm



408283 12 mm

CABLE, SLEEVING, BRAIDED, EXPANDABLE, POLYESTER, 40MM, 1

ขนาดบรรจุภัณฑ์: **10 x MTR**

- Sleeve Diameter: 40 mm
- Colour: Black
- Material: PET
- Sleeve Length: 10 m
- Braided: Yes
- Expandable: Yes
- Minimum Cable Diameter: 18 mm
- Maximum Cable Diameter: 54 mm



408287 40 mm

CABLE, SLEEVING, BRAIDED, EXPANDABLE, POLYESTER, 3MM, 30

ขนาดบรรจุภัณฑ์: **30 x MTR**

- Sleeve Diameter: 3 mm
- Colour: Black
- Material: PET
- Sleeve Length: 30 m
- Braided: Yes
- Expandable: Yes
- Minimum Cable Diameter: 2.36 mm
- Maximum Cable Diameter: 6.35 mm



408293 3 mm

CABLE, SLEEVING, BRAIDED, EXPANDABLE, POLYESTER, 19MM, 3

ขนาดบรรจุภัณฑ์: **30 x MTR**

- Sleeve Diameter: 19 mm
- Colour: Black
- Material: PET
- Sleeve Length: 30 m
- Braided: Yes
- Expandable: Yes
- Minimum Cable Diameter: 12.7 mm
- Maximum Cable Diameter: 31.7 mm



408299 19 mm

RS PRO PTFE CLEAR CABLE SLEEVE, 1.91MM DIAMETER

ขนาดบรรจุภัณฑ์: **5 x MTR**

- Sleeve Diameter: 1.91 mm
- Colour: Clear
- Material: PTFE
- Braided: No
- Minimum Operating Temperature: -65 °C
- Maximum Operating Temperature: +260 °C
- Fire Behaviour: Flame Retardant
- Dielectric Strength: 45 kV/mm



1789504 1.91 mm

CLEAR PTFE 5M SLEEVE, 1.27MM BORE

ขนาดบรรจุภัณฑ์: **5 x MTR**

- Sleeve Diameter: 1.27 mm
- Colour: Clear
- Material: PTFE
- Braided: No
- Minimum Operating Temperature: -65 °C
- Maximum Operating Temperature: +260 °C
- Fire Behaviour: Flame Retardant
- Dielectric Strength: 45 kV/mm



1789505 1.27 mm

CLEAR PTFE 5M SLEEVE, 3.05MM BORE

ขนาดบรรจุภัณฑ์: **5 x MTR**

- Sleeve Diameter: 3.05 mm
- Colour: Clear
- Material: PTFE
- Braided: No
- Minimum Operating Temperature: -65 °C
- Maximum Operating Temperature: +260 °C
- Fire Behaviour: Flame Retardant
- Dielectric Strength: 45 kV/mm



1789506 3.05 mm

RS PRO PTFE CLEAR CABLE SLEEVE, 1.01MM DIAMETER

ขนาดบรรจุภัณฑ์: **5 x MTR**

- Sleeve Diameter: 1.01 mm
- Colour: Clear
- Material: PTFE
- Braided: No
- Minimum Operating Temperature: -65 °C
- Maximum Operating Temperature: +260 °C
- Fire Behaviour: Flame Retardant
- Dielectric Strength: 45 kV/mm



1789507 1.01 mm

CLEAR PTFE 5M SLEEVE, 0.71MM BORE

ขนาดบรรจุภัณฑ์: **5 x MTR**

- Sleeve Diameter: 0.71 mm
- Colour: Clear
- Material: PTFE
- Sleeve Length: 5 m
- Braided: No
- Minimum Operating Temperature: -65 °C
- Maximum Operating Temperature: +260 °C
- Fire Behaviour: Flame Retardant



1789508 0.71 mm

RS PRO PTFE CLEAR CABLE SLEEVE, 0.89MM DIAMETER

ขนาดบรรจุภัณฑ์: **5 x MTR**

- Sleeve Diameter: 0.89 mm
- Colour: Clear
- Material: PTFE
- Braided: No
- Minimum Operating Temperature: -65 °C
- Maximum Operating Temperature: +260 °C
- Fire Behaviour: Flame Retardant
- Dielectric Strength: 45 kV/mm



1789509 0.89 mm

BLACK EXPANDABLE BRAIDED SLEEVING 3-9MM

ขนาดบรรจุภัณฑ์: **25 x MTR**

- Sleeve Diameter: 5 mm
- Colour: Black
- Material: PET
- Sleeve Length: 25 m
- Braided: Yes
- Expandable: Yes
- Minimum Cable Diameter: 3 mm
- Maximum Cable Diameter: 9 mm



1797007 5 mm

RS PRO EXPANDABLE BRAIDED PET GREY CABLE SLEEVE, 5MM DIAMETER,

ขนาดบรรจุภัณฑ์: **25 x MTR**

- Sleeve Diameter: 5 mm
- Colour: Grey
- Material: PET
- Sleeve Length: 25 m
- Braided: Yes
- Expandable: Yes
- Minimum Cable Diameter: 3 mm
- Maximum Cable Diameter: 9 mm



1797008 5 mm

RS PRO EXPANDABLE BRAIDED PET BLACK CABLE SLEEVE, 6MM

ขนาดบรรจุภัณฑ์: **25 x MTR**

- Sleeve Diameter: 6 mm
- Colour: Black
- Material: PET
- Sleeve Length: 25 m
- Braided: Yes
- Expandable: Yes
- Minimum Cable Diameter: 4 mm
- Maximum Cable Diameter: 11 mm



1797009 6 mm

RS PRO EXPANDABLE BRAIDED PET GREY CABLE SLEEVE, 6MM DIAMETER,

ขนาดบรรจุภัณฑ์: **25 x MTR**

- Sleeve Diameter: 6 mm
- Colour: Grey
- Material: PET
- Sleeve Length: 25 m
- Braided: Yes
- Expandable: Yes
- Minimum Cable Diameter: 4 mm
- Maximum Cable Diameter: 11 mm



1797010 6 mm

BLACK EXPANDABLE BRAIDED SLEEVING 5-12MM

ขนาดบรรจุภัณฑ์: **15 x MTR**

- Sleeve Diameter: 8 mm
- Colour: Black
- Material: PET
- Sleeve Length: 15 m
- Braided: Yes
- Expandable: Yes
- Minimum Cable Diameter: 5 mm
- Maximum Cable Diameter: 12 mm



1797011 8 mm

RS PRO EXPANDABLE BRAIDED PET GREY CABLE SLEEVE, 8MM DIAMETER,

ขนาดบรรจุภัณฑ์: **15 x MTR**

- Sleeve Diameter: 8 mm
- Colour: Grey
- Material: PET
- Sleeve Length: 15 m
- Braided: Yes
- Expandable: Yes
- Minimum Cable Diameter: 5 mm
- Maximum Cable Diameter: 12 mm



1797012 8 mm

BLACK EXPANDABLE BRAIDED SLEEVING 7-15MM

- ขนาดบรรจุภัณฑ์: **15 x MTR**
- Sleeve Diameter: 10 mm
 - Colour: Black
 - Material: PET
 - Sleeve Length: 15 m
 - Braided: Yes
 - Expandable: Yes
 - Minimum Cable Diameter: 7 mm
 - Maximum Cable Diameter: 15 mm



1797013 10 mm

RS PRO EXPANDABLE BRAIDED PET GREY CABLE SLEEVE, 10MM

- ขนาดบรรจุภัณฑ์: **15 x MTR**
- Sleeve Diameter: 10 mm
 - Colour: Grey
 - Material: PET
 - Sleeve Length: 15 m
 - Braided: Yes
 - Expandable: Yes
 - Minimum Cable Diameter: 7 mm
 - Maximum Cable Diameter: 15 mm



1797014 10 mm

RS PRO EXPANDABLE BRAIDED PET BLACK CABLE SLEEVE, 12MM

- ขนาดบรรจุภัณฑ์: **15 x MTR**
- Sleeve Diameter: 12 mm
 - Colour: Black
 - Material: PET
 - Sleeve Length: 15 m
 - Braided: Yes
 - Expandable: Yes
 - Minimum Cable Diameter: 8 mm
 - Maximum Cable Diameter: 17 mm



1797015 12 mm

RS PRO EXPANDABLE BRAIDED PET BLACK CABLE SLEEVE, 15MM

- ขนาดบรรจุภัณฑ์: **15 x MTR**
- Sleeve Diameter: 15 mm
 - Colour: Black
 - Material: PET
 - Sleeve Length: 15 m
 - Braided: Yes
 - Expandable: Yes
 - Minimum Cable Diameter: 10 mm
 - Maximum Cable Diameter: 21 mm



1797017 15 mm

RS PRO EXPANDABLE BRAIDED PET BLACK CABLE SLEEVE, 20MM

- ขนาดบรรจุภัณฑ์: **10 x MTR**
- Sleeve Diameter: 20 mm
 - Colour: Black
 - Material: PET
 - Sleeve Length: 10 m
 - Braided: Yes
 - Expandable: Yes
 - Minimum Cable Diameter: 14 mm
 - Maximum Cable Diameter: 27 mm



1797019 20 mm

RS PRO EXPANDABLE BRAIDED PET BLACK CABLE SLEEVE, 25MM

- ขนาดบรรจุภัณฑ์: **10 x MTR**
- Sleeve Diameter: 25 mm
 - Colour: Black
 - Material: PET
 - Sleeve Length: 10 m
 - Braided: Yes
 - Expandable: Yes
 - Minimum Cable Diameter: 18 mm
 - Maximum Cable Diameter: 34 mm



1797021 25 mm

RS PRO EXPANDABLE BRAIDED PET GREY CABLE SLEEVE, 25MM

- ขนาดบรรจุภัณฑ์: **10 x MTR**
- Sleeve Diameter: 25 mm
 - Colour: Grey
 - Material: PET
 - Sleeve Length: 10 m
 - Braided: Yes
 - Expandable: Yes
 - Minimum Cable Diameter: 18 mm
 - Maximum Cable Diameter: 34 mm



1797022 25 mm

BLACK EXPANDABLE BRAIDED SLEEVING 28-47M

- ขนาดบรรจุภัณฑ์: **10 x MTR**
- Sleeve Diameter: 30 mm
 - Colour: Black
 - Material: PET
 - Sleeve Length: 10 m
 - Braided: Yes
 - Expandable: Yes
 - Minimum Cable Diameter: 28 mm
 - Maximum Cable Diameter: 47 mm



1797023 30 mm

RS PRO EXPANDABLE BRAIDED PET GREY CABLE SLEEVE, 30MM

- ขนาดบรรจุภัณฑ์: **10 x MTR**
- Sleeve Diameter: 30 mm
 - Colour: Grey
 - Material: PET
 - Sleeve Length: 10 m
 - Braided: Yes
 - Expandable: Yes
 - Minimum Cable Diameter: 28 mm
 - Maximum Cable Diameter: 47 mm



1797024 30 mm

METAL SCREENING BRAID

- ขนาดบรรจุภัณฑ์: **10 x MTR**
- Sleeve Diameter: 3 mm
 - Material: Tin Plated Copper
 - Sleeve Length: 10 m
 - Braided: Yes
 - Expandable: Yes
 - Minimum Cable Diameter: 2.5 mm
 - Maximum Cable Diameter: 5 mm
 - Minimum Operating Temperature: -65 °C



1811979 3 mm

RS PRO EXPANDABLE BRAIDED TIN PLATED COPPER CABLE SLEEVE, 6MM

- ขนาดบรรจุภัณฑ์: **10 x MTR**
- Sleeve Diameter: 6 mm
 - Material: Tin Plated Copper
 - Sleeve Length: 10 m
 - Braided: Yes
 - Expandable: Yes
 - Minimum Cable Diameter: 4.5 mm
 - Maximum Cable Diameter: 9.5 mm
 - Minimum Operating Temperature: -65 °C



1811982 6 mm

RS PRO EXPANDABLE BRAIDED TIN PLATED COPPER CABLE SLEEVE,

- ขนาดบรรจุภัณฑ์: **10 x MTR**
- Sleeve Diameter: 7.5 mm
 - Material: Tin Plated Copper
 - Sleeve Length: 10 m
 - Braided: Yes
 - Expandable: Yes
 - Minimum Cable Diameter: 7 mm
 - Maximum Cable Diameter: 14 mm
 - Minimum Operating Temperature: -65 °C



1811983 7.5 mm

RS PRO EXPANDABLE BRAIDED TIN PLATED COPPER CABLE SLEEVE,

- ขนาดบรรจุภัณฑ์: **10 x MTR**
- Sleeve Diameter: 10 mm
 - Material: Tin Plated Copper
 - Sleeve Length: 10 m
 - Braided: Yes
 - Expandable: Yes
 - Minimum Cable Diameter: 8 mm
 - Maximum Cable Diameter: 22 mm
 - Minimum Operating Temperature: -65 °C



1811984 10 mm

RS PRO EXPANDABLE BRAIDED TIN PLATED COPPER CABLE SLEEVE,

- ขนาดบรรจุภัณฑ์: **10 x MTR**
- Sleeve Diameter: 12.5 mm
 - Material: Tin Plated Copper
 - Sleeve Length: 10 m
 - Braided: Yes
 - Expandable: Yes
 - Minimum Cable Diameter: 11 mm
 - Maximum Cable Diameter: 24 mm
 - Minimum Operating Temperature: -65 °C



1811985 12.5 mm

RS PRO EXPANDABLE BRAIDED TIN PLATED COPPER CABLE SLEEVE,

- ขนาดบรรจุภัณฑ์: **10 x MTR**
- Sleeve Diameter: 20 mm
 - Material: Tin Plated Copper
 - Sleeve Length: 10 m
 - Braided: Yes
 - Expandable: Yes
 - Minimum Cable Diameter: 3.5 mm
 - Maximum Cable Diameter: 7.5 mm
 - Minimum Operating Temperature: -65 °C



1811986 20 mm

RS PRO EXPANDABLE BRAIDED NICKEL PLATED COPPER CABLE

- ขนาดบรรจุภัณฑ์: **10 x MTR**
- Sleeve Diameter: 4 mm
 - Material: Nickel Plated Copper
 - Sleeve Length: 10 m
 - Braided: Yes
 - Expandable: Yes
 - Minimum Cable Diameter: 3.5 mm
 - Maximum Cable Diameter: 7.5 mm
 - Minimum Operating Temperature: -65 °C



1811988 4 mm

RS PRO EXPANDABLE BRAIDED NICKEL PLATED COPPER CABLE

- ขนาดบรรจุภัณฑ์: **10 x MTR**
- Sleeve Diameter: 6 mm
 - Material: Nickel Plated Copper
 - Sleeve Length: 10 m
 - Braided: Yes
 - Expandable: Yes
 - Minimum Cable Diameter: 4.5 mm
 - Maximum Cable Diameter: 9.5 mm
 - Minimum Operating Temperature: -65 °C



1811989 6 mm

RS PRO EXPANDABLE BRAIDED NICKEL PLATED COPPER CABLE

- ขนาดบรรจุภัณฑ์: **10 x MTR**
- Sleeve Diameter: 7.5 mm
 - Material: Nickel Plated Copper
 - Sleeve Length: 10 m
 - Braided: Yes
 - Expandable: Yes
 - Minimum Cable Diameter: 7 mm
 - Maximum Cable Diameter: 14 mm
 - Minimum Operating Temperature: -65 °C



1811990 7.5 mm

RS PRO EXPANDABLE BRAIDED NICKEL PLATED COPPER CABLE

- ขนาดบรรจุภัณฑ์: **10 x MTR**
- Sleeve Diameter: 10 mm
 - Material: Nickel Plated Copper
 - Sleeve Length: 10 m
 - Braided: Yes
 - Expandable: Yes
 - Minimum Cable Diameter: 8 mm
 - Maximum Cable Diameter: 22 mm
 - Minimum Operating Temperature: -65 °C



1811991 10 mm

RS PRO EXPANDABLE BRAIDED NICKEL PLATED COPPER CABLE

- ขนาดบรรจุภัณฑ์: **10 x MTR**
- Sleeve Diameter: 12.5 mm
 - Material: Nickel Plated Copper
 - Sleeve Length: 10 m
 - Braided: Yes
 - Expandable: Yes
 - Minimum Cable Diameter: 11 mm
 - Maximum Cable Diameter: 24 mm
 - Minimum Operating Temperature: -65 °C



1811992 12.5 mm

RS PRO EXPANDABLE BRAIDED TIN PLATED COPPER CABLE SLEEVE, 3MM

- ขนาดบรรจุภัณฑ์: **10 x MTR**
- Sleeve Diameter: 3 mm
 - Material: Tin Plated Copper
 - Sleeve Length: 10 m
 - Braided: Yes
 - Expandable: Yes
 - Minimum Cable Diameter: 2.5 mm
 - Maximum Cable Diameter: 5 mm
 - Minimum Operating Temperature: -65 °C



1811994 3 mm

RS PRO EXPANDABLE BRAIDED TIN PLATED COPPER CABLE SLEEVE, 4MM

- ขนาดบรรจุภัณฑ์: **10 x MTR**
- Sleeve Diameter: 4 mm
 - Material: Tin Plated Copper
 - Sleeve Length: 10 m
 - Braided: Yes
 - Expandable: Yes
 - Minimum Cable Diameter: 3.5 mm
 - Maximum Cable Diameter: 7.5 mm
 - Minimum Operating Temperature: -65 °C



1811995 4 mm

RS PRO EXPANDABLE BRAIDED TIN PLATED COPPER CABLE SLEEVE, 6MM

- ขนาดบรรจุภัณฑ์: **10 x MTR**
- Sleeve Diameter: 6 mm
 - Material: Tin Plated Copper
 - Sleeve Length: 10 m
 - Braided: Yes
 - Expandable: Yes
 - Minimum Cable Diameter: 4.5 mm
 - Maximum Cable Diameter: 9.5 mm
 - Minimum Operating Temperature: -65 °C



1811997 6 mm

RS PRO EXPANDABLE BRAIDED TIN PLATED COPPER CABLE SLEEVE, 7.5MM

- ขนาดบรรจุภัณฑ์: **10 x MTR**
- Sleeve Diameter: 7.5 mm
 - Material: Tin Plated Copper
 - Sleeve Length: 10 m
 - Braided: Yes
 - Expandable: Yes
 - Minimum Cable Diameter: 7 mm
 - Maximum Cable Diameter: 14 mm
 - Minimum Operating Temperature: -65 °C



1811998 7.5 mm

RS PRO EXPANDABLE BRAIDED TIN PLATED COPPER CABLE SLEEVE, 12.5MM

- ขนาดบรรจุภัณฑ์: **10 x MTR**
- Sleeve Diameter: 12.5 mm
 - Material: Tin Plated Copper
 - Sleeve Length: 10 m
 - Braided: Yes
 - Expandable: Yes
 - Minimum Cable Diameter: 11 mm
 - Maximum Cable Diameter: 24 mm
 - Minimum Operating Temperature: -65 °C



1812000 12.5 mm

RS PRO EXPANDABLE BRAIDED TIN PLATED COPPER CABLE SLEEVE, 15MM

- ขนาดบรรจุภัณฑ์: **10 x MTR**
- Sleeve Diameter: 15 mm
 - Material: Tin Plated Copper
 - Sleeve Length: 10 m
 - Braided: Yes
 - Expandable: Yes
 - Minimum Cable Diameter: 14.5 mm
 - Maximum Cable Diameter: 30 mm
 - Minimum Operating Temperature: -65 °C



1812001 15 mm

RS PRO EXPANDABLE BRAIDED TIN PLATED COPPER CABLE SLEEVE, 20MM

- ขนาดบรรจุภัณฑ์: **10 x MTR**
- Sleeve Diameter: 20 mm
 - Material: Tin Plated Copper
 - Sleeve Length: 10 m
 - Braided: Yes
 - Expandable: Yes
 - Minimum Cable Diameter: 16 mm
 - Maximum Cable Diameter: 38 mm
 - Minimum Operating Temperature: -65 °C



1812002 20 mm

RS PRO EXPANDABLE BRAIDED TIN PLATED COPPER CABLE SLEEVE, 4MM BORE

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Sleeve Diameter: 4 mm
 - Material: Tin Plated Copper
 - Sleeve Length: 100 m
 - Braided: Yes
 - Expandable: Yes
 - Minimum Cable Diameter: 3.5 mm
 - Maximum Cable Diameter: 7.5 mm
 - Minimum Operating Temperature: -65 °C



1812004 4 mm

RS PRO EXPANDABLE BRAIDED TIN PLATED COPPER CABLE SLEEVE, 3MM BORE

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Sleeve Diameter: 3 mm
 - Material: Tin Plated Copper
 - Sleeve Length: 100 m
 - Braided: Yes
 - Expandable: Yes
 - Minimum Cable Diameter: 2.5 mm
 - Maximum Cable Diameter: 5 mm
 - Minimum Operating Temperature: -65 °C



1812019 3 mm

BLACK SILICONE RUBBER SLEEVE, 1MM BORE

- ขนาดบรรจุภัณฑ์: **15 x MTR**
- Sleeve Diameter: 1 mm
 - Colour: Black
 - Material: Silicone
 - Sleeve Length: 15 m
 - Braided: No
 - Expandable: No
 - Minimum Operating Temperature: -60 °C
 - Maximum Operating Temperature: +180 °C



1874820 1 mm

BLACK SILICONE RUBBER SLEEVE, 2MM BORE

- ขนาดบรรจุภัณฑ์: **10 x MTR**
- Sleeve Diameter: 2 mm
 - Colour: Black
 - Material: Silicone
 - Sleeve Length: 10 m
 - Braided: No
 - Expandable: No
 - Minimum Operating Temperature: -60 °C
 - Maximum Operating Temperature: +180 °C



1874821 2 mm

RS PRO PVC BLACK CABLE SLEEVE, 3 MM±0.25 DIAMETER, 30.48M LENGTH

- ขนาดบรรจุภัณฑ์: **30 x MTR**
- Sleeve Diameter: 3 mm±0.25
 - Colour: Black
 - Material: PVC
 - Sleeve Length: 30.48 m
 - Braided: No
 - Expandable: No
 - Minimum Operating Temperature: -20 °C
 - Maximum Operating Temperature: +105 °C



1893170 3 mm±0.25

RS PRO PVC BLACK CABLE SLEEVE

- ขนาดบรรจุภัณฑ์: **30 x MTR**
- Colour: Black
 - Material: PVC
 - Braided: No
 - Expandable: No
 - Fire Behaviour: Flame Retardant
 - Dielectric Strength: 2500 V/m
 - Standards Met: RoHS Compliant
 - Wall Thickness: 0.47 mm



1893171 Black

RS PRO CABLE SLEEVE

- ขนาดบรรจุภัณฑ์: **30 x MTR**
- Wall Thickness: 0.47 mm



1893172 0.47 mm

RS PRO PVC BLACK CABLE SLEEVE

- ขนาดบรรจุภัณฑ์: **30 x MTR**
- Colour: Black
 - Material: PVC
 - Braided: No
 - Expandable: No
 - Fire Behaviour: Flame Retardant
 - Dielectric Strength: 2500 V/m
 - Standards Met: RoHS Compliant
 - Wall Thickness: 0.47 mm



1893173 Black

RS PRO PVC BLACK CABLE SLEEVE

- ขนาดบรรจุภัณฑ์: **30 x MTR**
- Colour: Black
 - Material: PVC
 - Braided: No
 - Expandable: No
 - Fire Behaviour: Flame Retardant
 - Dielectric Strength: 2500 V/m
 - Standards Met: RoHS Compliant
 - Wall Thickness: 0.47 mm



1893174 Black

RS PRO PVC BLACK CABLE SLEEVE

- ขนาดบรรจุภัณฑ์: **30 x MTR**
- Colour: Black
 - Material: PVC
 - Braided: No
 - Expandable: No
 - Fire Behaviour: Flame Retardant
 - Dielectric Strength: 2500 V/m
 - Standards Met: RoHS Compliant
 - Wall Thickness: 0.47 mm



1893175 Black

RS PRO PVC BLACK CABLE SLEEVE

- ขนาดบรรจุภัณฑ์: **30 x MTR**
- Colour: Black
 - Material: PVC
 - Braided: No
 - Expandable: No
 - Fire Behaviour: Flame Retardant
 - Dielectric Strength: 2500 V/m
 - Standards Met: RoHS Compliant
 - Wall Thickness: 0.60 mm



1893176 Black

RS PRO PVC BLACK CABLE SLEEVE, 30.48M LENGTH

- ขนาดบรรจุภัณฑ์: **30 x MTR**
- Colour: Black
 - Material: PVC
 - Sleeve Length: 30.48 m
 - Braided: No
 - Expandable: No
 - Maximum Cable Diameter: 12.70 mm ±0.35
 - Minimum Operating Temperature: -20 °C
 - Maximum Operating Temperature: +105 °C



1893179 Black

CABLE,SLEEVE,SILICON RUBBER,1.2MM,BLACK

- ขนาดบรรจุภัณฑ์: **15 x MTR**
- Sleeve Diameter: 1.2 mm
 - Colour: Black
 - Material: Silicone Rubber
 - Sleeve Length: 15 m
 - Braided: No
 - Minimum Operating Temperature: -60 °C
 - Maximum Operating Temperature: +180 °C
 - Standards Met: RoHS Compliant



2521688 1.2 mm

RS PRO SILICONE RUBBER GREEN CABLE SLEEVE, 1.2MM DIAMETER, 15M

- ขนาดบรรจุภัณฑ์: **15 x MTR**
- Sleeve Diameter: 1.2 mm
 - Colour: Green
 - Material: Silicone Rubber
 - Sleeve Length: 15 m
 - Braided: No
 - Minimum Operating Temperature: -60 °C
 - Maximum Operating Temperature: +180 °C
 - Standards Met: RoHS Compliant



2521694 1.2 mm

CABLE,SLEEVE,SILICON RUBBER,1.5MM,BLACK

- ขนาดบรรจุภัณฑ์: **15 x MTR**
- Sleeve Diameter: 1.5 mm
 - Colour: Black
 - Material: Silicone Rubber
 - Sleeve Length: 15 m
 - Braided: No
 - Minimum Operating Temperature: -60 °C
 - Maximum Operating Temperature: +180 °C
 - Standards Met: RoHS Compliant



2521717 1.5 mm

CABLE,SLEEVE,SILICON RUBBER,1.5MM,GREEN

- ขนาดบรรจุภัณฑ์: **15 x MTR**
- Sleeve Diameter: 1.5 mm
 - Colour: Green
 - Material: Silicone Rubber
 - Sleeve Length: 15 m
 - Braided: No
 - Maximum Cable Diameter: 1.5 mm
 - Minimum Operating Temperature: -60 °C
 - Maximum Operating Temperature: +180 °C



2521739 1.5 mm

CABLE,SLEEVE,SILICON RUBBER,1.5MM,RED

- ขนาดบรรจุภัณฑ์: **15 x MTR**
- Sleeve Diameter: 1.5 mm
 - Colour: Red
 - Material: Silicone Rubber
 - Sleeve Length: 15 m
 - Braided: No
 - Maximum Cable Diameter: 1.5 mm
 - Minimum Operating Temperature: -60 °C
 - Maximum Operating Temperature: +180 °C



2521745 1.5 mm

RS PRO EXPANDABLE BRAIDED SILICONE RUBBER GLASS BLACK

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 2 mm
 - Colour: Black
 - Material: Silicone Rubber Glass
 - Sleeve Length: 1 m
 - Braided: Yes
 - Expandable: Yes
 - Minimum Cable Diameter: 2 mm
 - Maximum Cable Diameter: 3.2 mm



6681223 2 mm

CONFORM EXP SILICONE/GLASS SLEEVING 4MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 4 mm
 - Colour: Black
 - Material: Silicone Rubber Glass
 - Sleeve Length: 1 m
 - Braided: Yes
 - Expandable: Yes
 - Minimum Cable Diameter: 4 mm
 - Maximum Cable Diameter: 6.4 mm



6681226 4 mm

RS PRO EXPANDABLE BRAIDED SILICONE RUBBER GLASS BLACK

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 12 mm
 - Colour: Black
 - Material: Silicone Rubber Glass
 - Sleeve Length: 1 m
 - Braided: Yes
 - Expandable: Yes
 - Minimum Cable Diameter: 12 mm
 - Maximum Cable Diameter: 19.2 mm



6681232 12 mm

RS PRO EXPANDABLE BRAIDED SILICONE RUBBER GLASS BLACK

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 16 mm
 - Colour: Black
 - Material: Silicone Rubber Glass
 - Sleeve Length: 1 m
 - Braided: Yes
 - Expandable: Yes
 - Minimum Cable Diameter: 16 mm
 - Maximum Cable Diameter: 25.6 mm



6681236 16 mm

RS PRO EXPANDABLE BRAIDED SILICONE RUBBER GLASS BLACK

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sleeve Diameter: 8 mm
 - Colour: Black
 - Material: Silicone Rubber Glass
 - Sleeve Length: 1 m
 - Braided: Yes
 - Expandable: Yes
 - Minimum Cable Diameter: 8 mm
 - Maximum Cable Diameter: 12.8 mm



6681239 8 mm

VSR10 HGH TEMP GLASS SLEEVING 10MM

- ขนาดบรรจุภัณฑ์: 5 x MTR
- Sleeve Diameter: 10 mm
 - Colour: Natural
 - Material: Fibreglass
 - Sleeve Length: 5 m
 - Braided: Yes
 - Expandable: No
 - Minimum Cable Diameter: 10 mm
 - Minimum Operating Temperature: -40 °C



6681242 10 mm

VSR10 HGH TEMP GLASS SLEEVING 6MM

- ขนาดบรรจุภัณฑ์: 5 x MTR
- Sleeve Diameter: 6 mm
 - Colour: Natural
 - Material: Fibreglass
 - Sleeve Length: 5 m
 - Braided: Yes
 - Expandable: No
 - Minimum Cable Diameter: 6 mm
 - Minimum Operating Temperature: -40 °C



6681245 6 mm

VSR10 HGH TEMP GLASS SLEEVING 8MM

- ขนาดบรรจุภัณฑ์: 5 x MTR
- Sleeve Diameter: 8 mm
 - Colour: Natural
 - Material: Fibreglass
 - Sleeve Length: 5 m
 - Braided: Yes
 - Expandable: No
 - Minimum Cable Diameter: 8 mm
 - Minimum Operating Temperature: -40 °C



6681248 8 mm

VSR10 HGH TEMP GLASS SLEEVING 12MM

- ขนาดบรรจุภัณฑ์: 5 x MTR
- Sleeve Diameter: 12 mm
 - Colour: Natural
 - Material: Fibreglass
 - Sleeve Length: 5 m
 - Braided: Yes
 - Expandable: No
 - Minimum Cable Diameter: 12 mm
 - Minimum Operating Temperature: -40 °C



6681251 12 mm

VSR10 HGH TEMP GLASS SLEEVING 16MM

- ขนาดบรรจุภัณฑ์: 5 x MTR
- Sleeve Diameter: 16 mm
 - Colour: Natural
 - Material: Fibreglass
 - Sleeve Length: 5 m
 - Braided: Yes
 - Expandable: No
 - Minimum Cable Diameter: 16 mm
 - Minimum Operating Temperature: -40 °C



6681254 16 mm

VSR10 HGH TEMP GLASS SLEEVING 20MM

- ขนาดบรรจุภัณฑ์: 5 x MTR
- Sleeve Diameter: 20 mm
 - Colour: Natural
 - Material: Fibreglass
 - Sleeve Length: 5 m
 - Braided: Yes
 - Expandable: No
 - Minimum Cable Diameter: 20 mm
 - Minimum Operating Temperature: -40 °C



6681258 20 mm

PLAS 7 SELF CLOSING SLEEVE 4MM

- ขนาดบรรจุภัณฑ์: 3 x MTR
- Sleeve Diameter: 4 mm
 - Colour: Black
 - Material: PET
 - Sleeve Length: 3 m
 - Braided: Yes
 - Expandable: No
 - Minimum Cable Diameter: 4 mm
 - Maximum Cable Diameter: 8 mm



6681260 4 mm

PLAS 7 SELF CLOSING SLEEVE 7MM

- ขนาดบรรจุภัณฑ์: 3 x MTR
- Sleeve Diameter: 7 mm
 - Colour: Black
 - Material: PET
 - Sleeve Length: 3 m
 - Braided: Yes
 - Expandable: No
 - Minimum Cable Diameter: 7 mm
 - Maximum Cable Diameter: 12 mm



6681264 7 mm

VSR10 HGH TEMP GLASS SLEEVING 25MM

- ขนาดบรรจุภัณฑ์: 5 x MTR
- Sleeve Diameter: 25 mm
 - Colour: Natural
 - Material: Fibreglass
 - Sleeve Length: 5 m
 - Braided: Yes
 - Expandable: No
 - Minimum Cable Diameter: 25 mm
 - Minimum Operating Temperature: -40 °C



6681267 25 mm

PLAS 7 SELF CLOSING SLEEVE 20MM

- ขนาดบรรจุภัณฑ์: 3 x MTR
- Sleeve Diameter: 20 mm
 - Colour: Black
 - Material: PET
 - Sleeve Length: 3 m
 - Braided: Yes
 - Expandable: No
 - Minimum Cable Diameter: 20 mm
 - Maximum Cable Diameter: 28 mm



6681270 20 mm

PLAS 7 SELF CLOSING SLEEVE 10MM

- ขนาดบรรจุภัณฑ์: 3 x MTR
- Sleeve Diameter: 10 mm
 - Colour: Black
 - Material: PET
 - Sleeve Length: 3 m
 - Braided: Yes
 - Expandable: No
 - Minimum Cable Diameter: 10 mm
 - Maximum Cable Diameter: 15 mm



6681273 10 mm

PLAS 7 SELF CLOSING SLEEVE 14MM

- ขนาดบรรจุภัณฑ์: 3 x MTR
- Sleeve Diameter: 14 mm
 - Colour: Black
 - Material: PET
 - Sleeve Length: 3 m
 - Braided: Yes
 - Expandable: No
 - Minimum Cable Diameter: 14 mm
 - Maximum Cable Diameter: 21 mm



6681276 14 mm

PLAS 7 SELF CLOSING SLEEVE 32MM

- ขนาดบรรจุภัณฑ์: 3 x MTR
- Sleeve Diameter: 32 mm
 - Colour: Black
 - Material: PET
 - Sleeve Length: 3 m
 - Braided: Yes
 - Expandable: No
 - Minimum Cable Diameter: 32 mm
 - Maximum Cable Diameter: 44 mm



6681282 32 mm

RS PRO BRAIDED PET BLACK CABLE SLEEVE, 44MM DIAMETER, 3M LENGTH

- ขนาดบรรจุภัณฑ์: 3 x MTR
- Sleeve Diameter: 44 mm
 - Colour: Black
 - Material: PET
 - Sleeve Length: 3 m
 - Braided: Yes
 - Expandable: No
 - Minimum Cable Diameter: 44 mm
 - Minimum Operating Temperature: -50 °C



6681286 44 mm

RS PRO BRAIDED PET BLACK CABLE SLEEVE, 26MM DIAMETER, 3M LENGTH

- ขนาดบรรจุภัณฑ์: 3 x MTR
- Sleeve Diameter: 26 mm
 - Colour: Black
 - Material: PET
 - Sleeve Length: 3 m
 - Braided: Yes
 - Expandable: No
 - Minimum Cable Diameter: 26 mm
 - Maximum Cable Diameter: 34 mm



6681289 26 mm

VSR10 EXPANDABLE GLASS SLEEVING 10MM

- ขนาดบรรจุภัณฑ์: **5 x MTR**
- Sleeve Diameter: 10 mm
 - Colour: Natural
 - Material: Fibreglass
 - Sleeve Length: 5 m
 - Braided: Yes
 - Expandable: Yes
 - Minimum Cable Diameter: 10 mm
 - Maximum Cable Diameter: 22 mm



6681295 10 mm

VSR10 EXPANDABLE GLASS SLEEVING 20MM

- ขนาดบรรจุภัณฑ์: **5 x MTR**
- Sleeve Diameter: 20 mm
 - Colour: Natural
 - Material: Fibreglass
 - Sleeve Length: 5 m
 - Braided: Yes
 - Expandable: Yes
 - Minimum Cable Diameter: 20 mm
 - Maximum Cable Diameter: 55 mm



6681298 20 mm

CABLE SLEEVE TOOL INSTALLATION, FOR USE WITH KS, KL SERIES SPIRAL

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Tool Type: Sleeve Installation
 - For Use With: KS, KL Series Spiral Wraps
 - Series: KT



2044433 Sleeve

CABLE SLEEVE TOOL INSTALLATION, FOR USE WITH KS, KL SERIES SPIRAL

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Tool Type: Sleeve Installation
 - For Use With: KS, KL Series Spiral Wraps
 - Series: KT



2044435 Sleeve

CABLE SLEEVE TOOL INSTALLATION, FOR USE WITH KS, KL SERIES SPIRAL

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Tool Type: Sleeve Installation
 - For Use With: KS, KL Series Spiral Wraps
 - Series: KT



2044436 Sleeve

CABLE SLEEVE TOOL INSTALLATION, FOR USE WITH KS, KL SERIES SPIRAL

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Tool Type: Sleeve Installation
 - For Use With: KS, KL Series Spiral Wraps
 - Series: KT



2044437 Sleeve

CABLE SLEEVE TOOL INSTALLATION, FOR USE WITH KS, KL SERIES SPIRAL

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Tool Type: Sleeve Installation
 - For Use With: KS, KL Series Spiral Wraps
 - Series: KT



2044438 Sleeve

HARNESS WRAP APPLICATOR TOOL 20/25MM DIA

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Material: PP



687679 PP

CABLE, RETENTION, SPIRAL WRAP, POLYTHENE, DIA 3.2/12.7MM

- ขนาดบรรจุภัณฑ์: **5 x MTR**
- Minimum Cable Diameter: 1.5 mm
 - Maximum Cable Diameter: 3 mm
 - Colour: Natural
 - Internal Diameter: 1.5 mm
 - Material: Polyethylene
 - Maximum Bundle Diameter: 10 mm
 - Minimum Operating Temperature: -50 °C
 - Maximum Operating Temperature: +50 °C



227968 1.5 mm

CABLE, RETENTION, SPIRAL WRAP, POLYTHENE, DIA 6.4/50MM

- ขนาดบรรจุภัณฑ์: **5 x MTR**
- Minimum Cable Diameter: 4 mm
 - Maximum Cable Diameter: 6 mm
 - Colour: Natural
 - Internal Diameter: 4 mm
 - Material: Polyethylene
 - Maximum Bundle Diameter: 25 mm
 - Minimum Operating Temperature: -50 °C
 - Maximum Operating Temperature: +50 °C



227974 4 mm

CABLE, RETENTION, SPIRAL WRAP, POLYTHENE, DIA 13/80MM

- ขนาดบรรจุภัณฑ์: **3 x MTR**
- Minimum Cable Diameter: 9 mm
 - Maximum Cable Diameter: 12 mm
 - Colour: Natural
 - Internal Diameter: 9 mm
 - Material: Polyethylene
 - Maximum Bundle Diameter: 32 mm
 - Minimum Operating Temperature: -50 °C
 - Maximum Operating Temperature: +50 °C



227980 9 mm

RS PRO SPIRAL WRAP, I.D 32MM 35MM POLYPROPYLENE

- ขนาดบรรจุภัณฑ์: **25 x MTR**
- Minimum Cable Diameter: 9 mm
 - Maximum Cable Diameter: 35 mm
 - Colour: Black
 - Internal Diameter: 32 mm
 - Material: Polypropylene
 - Maximum Bundle Diameter: 35 mm
 - Fire Behaviour: Halogen Free
 - Wall Thickness: 1.3 mm



2044414 35 mm

RS PRO SPIRAL WRAP, I.D 8MM 10MM POLYPROPYLENE

- ขนาดบรรจุภัณฑ์: **25 x MTR**
- Minimum Cable Diameter: 8 mm
 - Maximum Cable Diameter: 10 mm
 - Colour: Black
 - Internal Diameter: 8 mm
 - Material: Polypropylene
 - Maximum Bundle Diameter: 10 mm
 - Fire Behaviour: Halogen Free
 - Wall Thickness: 0.8 mm



2044415 8 mm

RS PRO SPIRAL WRAP, I.D 12MM POLYETHYLENE

- ขนาดบรรจุภัณฑ์: **5 x MTR**
- Minimum Cable Diameter: 12 mm
 - Maximum Cable Diameter: 32 mm
 - Colour: Natural
 - Internal Diameter: 12 mm
 - Material: Polyethylene
 - Fire Behaviour: Halogen Free
 - Wall Thickness: 0.85 mm
 - Length: 5 m



2044416 12 mm

RS PRO SPIRAL WRAP, I.D 19MM POLYETHYLENE

- ขนาดบรรจุภัณฑ์: **30 x MTR**
- Minimum Cable Diameter: 19 mm
 - Maximum Cable Diameter: 50 mm
 - Colour: Natural
 - Internal Diameter: 19 mm
 - Material: Polyethylene
 - Fire Behaviour: Halogen Free
 - Wall Thickness: 1.2 mm
 - Length: 30.5 m



2044417 19 mm

RS PRO SPIRAL WRAP, I.D 15MM 16MM POLYPROPYLENE

- ขนาดบรรจุภัณฑ์: **25 x MTR**
- Minimum Cable Diameter: 15 mm
 - Maximum Cable Diameter: 16 mm
 - Colour: Black
 - Internal Diameter: 15 mm
 - Material: Polypropylene
 - Maximum Bundle Diameter: 16 mm
 - Fire Behaviour: Halogen Free
 - Wall Thickness: 0.8 mm



2044418 15 mm

RS PRO SPIRAL WRAP, I.D 15MM 16MM POLYPROPYLENE

ขนาดบรรจุภัณฑ์: 2 x MTR

- Minimum Cable Diameter: 15 mm
- Maximum Cable Diameter: 16 mm
- Colour: Grey
- Internal Diameter: 15 mm
- Material: Polypropylene
- Maximum Bundle Diameter: 16 mm
- Fire Behaviour: Halogen Free
- Wall Thickness: 0.8 mm



2044419 15 mm

RS PRO SPIRAL WRAP, I.D 20MM 22MM POLYPROPYLENE

ขนาดบรรจุภัณฑ์: 25 x MTR

- Minimum Cable Diameter: 20 mm
- Maximum Cable Diameter: 22 mm
- Colour: Black
- Internal Diameter: 20 mm
- Material: Polypropylene
- Maximum Bundle Diameter: 22 mm
- Fire Behaviour: Halogen Free
- Wall Thickness: 0.9 mm



2044420 20 mm

RS PRO SPIRAL WRAP, I.D 25MM 27MM POLYPROPYLENE

ขนาดบรรจุภัณฑ์: 2 x MTR

- Minimum Cable Diameter: 25 mm
- Maximum Cable Diameter: 27 mm
- Colour: Black
- Internal Diameter: 25 mm
- Material: Polypropylene
- Maximum Bundle Diameter: 27 mm
- Fire Behaviour: Halogen Free
- Wall Thickness: 1.3 mm



2044421 25 mm

RS PRO SPIRAL WRAP, I.D 25MM 27MM POLYPROPYLENE

ขนาดบรรจุภัณฑ์: 25 x MTR

- Minimum Cable Diameter: 25 mm
- Maximum Cable Diameter: 27 mm
- Colour: Black
- Internal Diameter: 25 mm
- Material: Polypropylene
- Maximum Bundle Diameter: 27 mm
- Fire Behaviour: Halogen Free
- Wall Thickness: 1.3 mm



2044422 25 mm

RS PRO SPIRAL WRAP, I.D 25MM 27MM POLYPROPYLENE

ขนาดบรรจุภัณฑ์: 2 x MTR

- Minimum Cable Diameter: 25 mm
- Maximum Cable Diameter: 27 mm
- Colour: Grey
- Internal Diameter: 25 mm
- Material: Polypropylene
- Maximum Bundle Diameter: 27 mm
- Fire Behaviour: Halogen Free
- Wall Thickness: 1.3 mm



2044423 25 mm

RS PRO SPIRAL WRAP, I.D 6MM POLYETHYLENE

ขนาดบรรจุภัณฑ์: 30 x MTR

- Minimum Cable Diameter: 6 mm
- Maximum Cable Diameter: 25 mm
- Colour: Natural
- Internal Diameter: 6 mm
- Material: Polyethylene
- Fire Behaviour: Halogen Free
- Wall Thickness: 0.6 mm
- Length: 30.5 m



2044424 6 mm

RS PRO SPIRAL WRAP, I.D 19MM POLYETHYLENE

ขนาดบรรจุภัณฑ์: 30 x MTR

- Minimum Cable Diameter: 19 mm
- Maximum Cable Diameter: 50 mm
- Colour: Black
- Internal Diameter: 19 mm
- Material: Polyethylene
- Fire Behaviour: Halogen Free
- Wall Thickness: 1.2 mm
- Length: 30.5 m



2044425 19 mm

RS PRO SPIRAL WRAP, I.D 6MM POLYETHYLENE

ขนาดบรรจุภัณฑ์: 30 x MTR

- Minimum Cable Diameter: 6 mm
- Maximum Cable Diameter: 25 mm
- Colour: Black
- Internal Diameter: 6 mm
- Material: Polyethylene
- Fire Behaviour: Halogen Free
- Wall Thickness: 0.6 mm
- Length: 30.5 m



2044426 6 mm

RS PRO SPIRAL WRAP, I.D 12MM POLYETHYLENE

ขนาดบรรจุภัณฑ์: 5 x MTR

- Minimum Cable Diameter: 12 mm
- Maximum Cable Diameter: 32 mm
- Colour: Black
- Internal Diameter: 12 mm
- Material: Polyethylene
- Fire Behaviour: Halogen Free
- Wall Thickness: 0.85 mm
- Length: 5 m



2044427 12 mm

RS PRO SPIRAL WRAP, I.D 12MM POLYETHYLENE

ขนาดบรรจุภัณฑ์: 5 x MTR

- Minimum Cable Diameter: 12 mm
- Maximum Cable Diameter: 32 mm
- Colour: Grey
- Internal Diameter: 12 mm
- Material: Polyethylene
- Fire Behaviour: Halogen Free
- Wall Thickness: 0.85 mm
- Length: 5 m



2044429 12 mm

RS PRO SPIRAL WRAP, I.D 6MM POLYETHYLENE

ขนาดบรรจุภัณฑ์: 5 x MTR

- Minimum Cable Diameter: 6 mm
- Maximum Cable Diameter: 25 mm
- Colour: Grey
- Internal Diameter: 6 mm
- Material: Polyethylene
- Fire Behaviour: Halogen Free
- Wall Thickness: 0.85 mm
- Length: 5 m



2044430 6 mm

RS PRO SPIRAL WRAP, I.D 15MM 16MM POLYPROPYLENE

ขนาดบรรจุภัณฑ์: 2 x MTR

- Minimum Cable Diameter: 15 mm
- Maximum Cable Diameter: 16 mm
- Colour: Black
- Internal Diameter: 15 mm
- Material: Polypropylene
- Maximum Bundle Diameter: 16 mm
- Fire Behaviour: Halogen Free
- Wall Thickness: 0.8 mm



2044431 15 mm

RS PRO SPIRAL WRAP, I.D 6MM POLYETHYLENE

ขนาดบรรจุภัณฑ์: 5 x MTR

- Minimum Cable Diameter: 6 mm
- Colour: Natural
- Internal Diameter: 6 mm
- Material: Polyethylene
- Length: 30.5 m
- Series: KS



2044432 6 mm

RS PRO SPIRAL WRAP, I.D 8MM 10MM PA 6 NYLON

ขนาดบรรจุภัณฑ์: 5 x MTR

- Minimum Cable Diameter: 8 mm
- Maximum Cable Diameter: 10 mm
- Colour: Black
- Internal Diameter: 8 mm
- Material: PA 6
- Maximum Bundle Diameter: 10 mm
- Wall Thickness: 0.8 mm
- Length: 5 m



2108572 8 mm

RS PRO SPIRAL WRAP, I.D 13.4MM 16MM NYLON 6

ขนาดบรรจุภัณฑ์: 5 x MTR

- Minimum Cable Diameter: 15 mm
- Maximum Cable Diameter: 15 mm
- Colour: Black
- Internal Diameter: 13.4 mm
- Material: Nylon 6
- Maximum Bundle Diameter: 16 mm
- Wall Thickness: 0.8 mm
- Length: 5 m



2108588 15 mm

RS PRO SPIRAL WRAP, I.D 25MM 25MM PA 6 NYLON

ขนาดบรรจุภัณฑ์: 5 x MTR

- Maximum Cable Diameter: 25 mm
- Colour: Black
- Internal Diameter: 25 mm
- Material: PA 6
- Maximum Bundle Diameter: 25 mm
- Wall Thickness: 1 mm
- Length: 5 m



2108594 25 mm

**RS PRO SPIRAL WRAP, I.D 15MM
16MM PP**

ขนาดบรรจุภัณฑ์: **25 x MTR**

- Minimum Cable Diameter: 15 mm
- Maximum Cable Diameter: 16 mm
- Colour: White
- Internal Diameter: 15 mm
- Material: PP
- Maximum Bundle Diameter: 16 mm
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: +70 °C



2144061 15 mm

**RS PRO SPIRAL WRAP, I.D 25MM
27MM PP**

ขนาดบรรจุภัณฑ์: **25 x MTR**

- Minimum Cable Diameter: 25 mm
- Maximum Cable Diameter: 27 mm
- Colour: White
- Internal Diameter: 25 mm
- Material: PP
- Maximum Bundle Diameter: 27 mm
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: +70 °C



2144063 25 mm

**RS PRO SPIRAL WRAP, I.D 9MM 32MM
POLYETHYLENE**

ขนาดบรรจุภัณฑ์: **25 x MTR**

- Minimum Cable Diameter: 9 mm
- Maximum Cable Diameter: 32 mm
- Colour: Natural
- Internal Diameter: 9 mm
- Material: Polyethylene
- Maximum Bundle Diameter: 32 mm
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: 70 °C



2144065 9 mm

**RS PRO SPIRAL WRAP, I.D 4MM
25MM POLYETHYLENE**

ขนาดบรรจุภัณฑ์: **25 x MTR**

- Minimum Cable Diameter: 4 mm
- Maximum Cable Diameter: 6 mm
- Colour: Natural
- Internal Diameter: 4 mm
- Material: Polyethylene
- Maximum Bundle Diameter: 25 mm
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: 70 °C



2144066 4 mm

**RS PRO SPIRAL WRAP, I.D 9MM 32MM
POLYETHYLENE**

ขนาดบรรจุภัณฑ์: **31 x MTR**

- Minimum Cable Diameter: 9 mm
- Maximum Cable Diameter: 32 mm
- Colour: Grey
- Internal Diameter: 9 mm
- Material: Polyethylene
- Maximum Bundle Diameter: 32 mm
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: 70 °C



2144068 9 mm

**RS PRO SPIRAL WRAP, I.D 4MM
25MM POLYETHYLENE**

ขนาดบรรจุภัณฑ์: **31 x MTR**

- Minimum Cable Diameter: 4 mm
- Maximum Cable Diameter: 25 mm
- Colour: White
- Internal Diameter: 4 mm
- Material: Polyethylene
- Maximum Bundle Diameter: 25 mm
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: 70 °C



2144071 4 mm

**RS PRO SPIRAL WRAP, I.D 20MM
23MM PA 6 NYLON**

ขนาดบรรจุภัณฑ์: **5 x MTR**

- Minimum Cable Diameter: 20 mm
- Maximum Cable Diameter: 23 mm
- Colour: Black
- Internal Diameter: 20 mm
- Material: PA 6
- Maximum Bundle Diameter: 23 mm
- Wall Thickness: 0.9 mm
- Length: 5 m



2884923 20 mm

**RS PRO SPIRAL WRAP, I.D 9MM 32MM
POLYETHYLENE**

ขนาดบรรจุภัณฑ์: **3 x MTR**

- Minimum Cable Diameter: 9 mm
- Maximum Cable Diameter: 12 mm
- Colour: Black
- Internal Diameter: 9 mm
- Material: Polyethylene
- Maximum Bundle Diameter: 32 mm
- Wall Thickness: 0.85 mm
- Length: 3 m



8117620 9 mm

PE SPIRAL WRAP 3MM BLACK 5M

ขนาดบรรจุภัณฑ์: **5 x MTR**

- Minimum Cable Diameter: 1.5 mm
- Maximum Cable Diameter: 3 mm
- Colour: Black
- Internal Diameter: 1.5 mm
- Material: Polyethylene
- Maximum Bundle Diameter: 10 mm
- Minimum Operating Temperature: -50 °C
- Maximum Operating Temperature: +50 °C



8117632 1.5 mm

**RS PRO SPIRAL WRAP, I.D 10.3MM
32MM POLYETHYLENE**

ขนาดบรรจุภัณฑ์: **30 x MTR**

- Minimum Cable Diameter: 9 mm
- Maximum Cable Diameter: 12 mm
- Colour: Natural
- Internal Diameter: 10.3 mm
- Material: Polyethylene
- Maximum Bundle Diameter: 32 mm
- Wall Thickness: 0.85 mm
- Length: 30.5 m



8117636 9 mm

**PE SPIRAL WRAPPING, 6MM BLACK
5M**

ขนาดบรรจุภัณฑ์: **5 x MTR**

- Minimum Cable Diameter: 4 mm
- Maximum Cable Diameter: 6 mm
- Colour: Black
- Internal Diameter: 4 mm
- Material: Polyethylene
- Maximum Bundle Diameter: 25 mm
- Minimum Operating Temperature: -50 °C
- Maximum Operating Temperature: +50 °C



8117639 4 mm

PE SPIRAL WRAP 12MM BLACK 30.5M

ขนาดบรรจุภัณฑ์: **30 x MTR**

- Minimum Cable Diameter: 4 mm
- Maximum Cable Diameter: 12 mm
- Colour: Black
- Internal Diameter: 10.3 mm
- Material: Polyethylene
- Maximum Bundle Diameter: 32 mm
- Wall Thickness: 0.85 mm
- Length: 30.5 m



8117642 9 mm

**PE SPIRAL WRAP 6MM NATURAL
30.5M**

ขนาดบรรจุภัณฑ์: **30 x MTR**

- Minimum Cable Diameter: 4 mm
- Maximum Cable Diameter: 4.5 mm
- Colour: Natural
- Internal Diameter: 4 mm
- Material: Polyethylene
- Maximum Bundle Diameter: 15 mm
- Wall Thickness: 0.6 mm
- Length: 30.5 m



8117645 4 mm

**PE SPIRAL WRAP 3MM NATURAL
30.5M**

ขนาดบรรจุภัณฑ์: **30 x MTR**

- Minimum Cable Diameter: 1.5 mm
- Maximum Cable Diameter: 3 mm
- Colour: Natural
- Internal Diameter: 1.5 mm
- Material: Polyethylene
- Maximum Bundle Diameter: 10 mm
- Minimum Operating Temperature: -50 °C
- Maximum Operating Temperature: +50 °C



8117648 1.5 mm

**RS PRO SPIRAL WRAP, I.D 4MM 15MM
POLYETHYLENE**

ขนาดบรรจุภัณฑ์: **30 x MTR**

- Minimum Cable Diameter: 4 mm
- Maximum Cable Diameter: 4.5 mm
- Colour: Black
- Internal Diameter: 4 mm
- Material: Polyethylene
- Maximum Bundle Diameter: 15 mm
- Wall Thickness: 0.6 mm
- Length: 30.5 m



8117651 4 mm

**RS PRO SPIRAL WRAP, I.D 1.5MM
10MM POLYETHYLENE**

ขนาดบรรจุภัณฑ์: **30 x MTR**

- Minimum Cable Diameter: 1.5 mm
- Maximum Cable Diameter: 3 mm
- Colour: Black
- Internal Diameter: 1.5 mm
- Material: Polyethylene
- Maximum Bundle Diameter: 10 mm
- Minimum Operating Temperature: -50 °C
- Maximum Operating Temperature: +50 °C



8117654 1.5 mm

PE SPIRAL CABLE WRAP 8MM BLACK 3M

- ขนาดบรรจุภัณฑ์: **3 x MTR**
- Minimum Cable Diameter: 6 mm
 - Maximum Cable Diameter: 8 mm
 - Colour: Black
 - Internal Diameter: 6 mm
 - Material: Polyethylene
 - Maximum Bundle Diameter: 30 mm
 - Wall Thickness: 0.75 mm
 - Length: 3 m



8117658 6 mm

PE SPIRAL CABLE WRAP 8MM BLACK 30.5M

- ขนาดบรรจุภัณฑ์: **30 x MTR**
- Minimum Cable Diameter: 6 mm
 - Maximum Cable Diameter: 8 mm
 - Colour: Black
 - Internal Diameter: 6 mm
 - Material: Polyethylene
 - Maximum Bundle Diameter: 30 mm
 - Wall Thickness: 0.75 mm
 - Length: 30.5 m



8117660 6 mm

RS PRO SPIRAL WRAP, I.D 6MM 30MM POLYETHYLENE

- ขนาดบรรจุภัณฑ์: **30 x MTR**
- Minimum Cable Diameter: 6 mm
 - Maximum Cable Diameter: 8 mm
 - Colour: Natural
 - Internal Diameter: 6 mm
 - Material: Polyethylene
 - Maximum Bundle Diameter: 30 mm
 - Wall Thickness: 0.75 mm
 - Length: 30 m



8117664 6 mm

PE SPIRAL CABLE WRAP 8 MM NATURAL 3M

- ขนาดบรรจุภัณฑ์: **3 x MTR**
- Minimum Cable Diameter: 6 mm
 - Maximum Cable Diameter: 8 mm
 - Colour: Natural
 - Internal Diameter: 6 mm
 - Material: Polyethylene
 - Maximum Bundle Diameter: 30 mm
 - Wall Thickness: 0.75 mm
 - Length: 3 m



8117667 6 mm

PE SPIRAL WRAP 12MM BLACK 10M

- ขนาดบรรจุภัณฑ์: **10 x MTR**
- Minimum Cable Diameter: 9 mm
 - Maximum Cable Diameter: 12 mm
 - Colour: Black
 - Internal Diameter: 9 mm
 - Material: Polyethylene
 - Maximum Bundle Diameter: 32 mm
 - Wall Thickness: 0.85 mm
 - Length: 10 m



8117670 9 mm

PE SPIRAL WRAP 6MM BLACK 10M

- ขนาดบรรจุภัณฑ์: **10 x MTR**
- Minimum Cable Diameter: 4 mm
 - Maximum Cable Diameter: 4.5 mm
 - Colour: Black
 - Internal Diameter: 4 mm
 - Material: Polyethylene
 - Maximum Bundle Diameter: 15 mm
 - Wall Thickness: 0.6 mm
 - Length: 10 m



8117673 4 mm

PE SPIRAL WRAP 8MM BLACK 10M

- ขนาดบรรจุภัณฑ์: **10 x MTR**
- Minimum Cable Diameter: 6 mm
 - Maximum Cable Diameter: 8 mm
 - Colour: Black
 - Internal Diameter: 6 mm
 - Material: Polyethylene
 - Maximum Bundle Diameter: 30 mm
 - Wall Thickness: 0.75 mm
 - Length: 10 m



8117676 6 mm

PE SPIRAL WRAP 6MM NATURAL 10M

- ขนาดบรรจุภัณฑ์: **10 x MTR**
- Minimum Cable Diameter: 4 mm
 - Maximum Cable Diameter: 4.5 mm
 - Colour: Natural
 - Internal Diameter: 4 mm
 - Material: Polyethylene
 - Maximum Bundle Diameter: 15 mm
 - Wall Thickness: 0.6 mm
 - Length: 10 m



8117682 4 mm

PE SPIRAL WRAP 8MM NATURAL 10M

- ขนาดบรรจุภัณฑ์: **10 x MTR**
- Minimum Cable Diameter: 6 mm
 - Maximum Cable Diameter: 8 mm
 - Colour: Natural
 - Internal Diameter: 6 mm
 - Material: Polyethylene
 - Maximum Bundle Diameter: 30 mm
 - Wall Thickness: 0.75 mm
 - Length: 10 m



8117686 6 mm

PE SPIRAL WRAP 15MM BLACK 10M

- ขนาดบรรจุภัณฑ์: **10 x MTR**
- Minimum Cable Diameter: 12 mm
 - Maximum Cable Diameter: 15 mm
 - Colour: Black
 - Internal Diameter: 15 mm
 - Material: Polyethylene
 - Maximum Bundle Diameter: 35 mm
 - Wall Thickness: 1 mm
 - Length: 10 m



8117689 12 mm

RS PRO SPIRAL WRAP, I.D 4MM 25MM NYLON

- ขนาดบรรจุภัณฑ์: **10 x MTR**
- Minimum Cable Diameter: 4 mm
 - Maximum Cable Diameter: 4.5 mm
 - Colour: Black
 - Internal Diameter: 4 mm
 - Material: Nylon
 - Maximum Bundle Diameter: 25 mm
 - Wall Thickness: 0.45 mm
 - Length: 10 m



8117692 4 mm

PE SPIRAL WRAP 12MM NATURAL 10M

- ขนาดบรรจุภัณฑ์: **10 x MTR**
- Minimum Cable Diameter: 9 mm
 - Maximum Cable Diameter: 12 mm
 - Colour: Natural
 - Internal Diameter: 10.3 mm
 - Material: Polyethylene
 - Maximum Bundle Diameter: 32 mm
 - Minimum Operating Temperature: -50 °C
 - Maximum Operating Temperature: +50 °C



8117695 9 mm

RS PRO SPIRAL WRAP, I.D 12MM 35MM POLYETHYLENE

- ขนาดบรรจุภัณฑ์: **10 x MTR**
- Minimum Cable Diameter: 12 mm
 - Maximum Cable Diameter: 15 mm
 - Colour: Natural
 - Internal Diameter: 12 mm
 - Material: Polyethylene
 - Maximum Bundle Diameter: 35 mm
 - Wall Thickness: 1 mm
 - Length: 10 m



8117698 12 mm

NYLON SPIRAL WRAP 8MM BLACK 10M

- ขนาดบรรจุภัณฑ์: **10 x MTR**
- Minimum Cable Diameter: 6 mm
 - Maximum Cable Diameter: 8 mm
 - Colour: Black
 - Internal Diameter: 6 mm
 - Material: Nylon
 - Maximum Bundle Diameter: 30 mm
 - Wall Thickness: 0.7 mm
 - Length: 10 m



8117702 6 mm

NYLON SPIRAL WRAP 12MM BLACK 10M

- ขนาดบรรจุภัณฑ์: **10 x MTR**
- Minimum Cable Diameter: 9 mm
 - Maximum Cable Diameter: 12 mm
 - Colour: Black
 - Internal Diameter: 10.6 mm
 - Material: Nylon
 - Maximum Bundle Diameter: 32 mm
 - Wall Thickness: 0.7 mm
 - Length: 10 m



8117705 9 mm

RS PRO SPIRAL WRAP, I.D 12MM 35MM NYLON

- ขนาดบรรจุภัณฑ์: **10 x MTR**
- Minimum Cable Diameter: 12 mm
 - Maximum Cable Diameter: 15 mm
 - Colour: Black
 - Internal Diameter: 12 mm
 - Material: Nylon
 - Maximum Bundle Diameter: 35 mm
 - Wall Thickness: 0.8 mm
 - Length: 10 m



8117709 12 mm

NYLON SPIRAL WRAP 8MM NATURAL 10M

- ขนาดบรรจุภัณฑ์: **10 x MTR**
- Minimum Cable Diameter: 6 mm
 - Maximum Cable Diameter: 8 mm
 - Colour: Natural
 - Internal Diameter: 6 mm
 - Material: Nylon
 - Maximum Bundle Diameter: 30 mm
 - Wall Thickness: 0.7 mm
 - Length: 10 m



8117711 6 mm

RS PRO SPIRAL WRAP, I.D 10.6MM 32MM NYLON

- ขนาดบรรจุภัณฑ์: **10 x MTR**
- Minimum Cable Diameter: 9 mm
 - Maximum Cable Diameter: 12 mm
 - Colour: Natural
 - Internal Diameter: 10.6 mm
 - Material: Nylon
 - Maximum Bundle Diameter: 32 mm
 - Wall Thickness: 0.7 mm
 - Length: 10 m



8117715 9 mm

NYLON SPIRAL WRAP 6MM NATURAL 10M

- ขนาดบรรจุภัณฑ์: **10 x MTR**
- Minimum Cable Diameter: 4 mm
 - Maximum Cable Diameter: 4.5 mm
 - Colour: Natural
 - Internal Diameter: 4 mm
 - Material: Nylon
 - Maximum Bundle Diameter: 25 mm
 - Wall Thickness: 0.45 mm
 - Length: 10 m



8117718 4 mm

RS PRO SPIRAL WRAP, I.D 12MM 35MM POLYETHYLENE

- ขนาดบรรจุภัณฑ์: **10 x MTR**
- Minimum Cable Diameter: 12 mm
 - Maximum Cable Diameter: 15 mm
 - Colour: Natural
 - Internal Diameter: 12 mm
 - Material: Polyethylene
 - Maximum Bundle Diameter: 35 mm
 - Wall Thickness: 0.8 mm
 - Length: 10 m



8117724 12 mm

RS PRO CABLE DRUM ROLLER, 1 SHELF

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Type: Cable Drum Roller
 - Number of Shelves: 1
 - Height: 128 mm
 - Width: 568 mm
 - Length: 565 mm
 - Diameter: 120 mm → 1200 mm
 - Material: Aluminium, Steel



666688 Cable Drum

RS PRO EMPTY CABLE REEL 30M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Type: Empty Cable Reel
 - Maximum Cable Length Capacity: 30 m
 - Cable Diameter Capacity: 12 mm
 - Height: 367 mm
 - Diameter: 310 mm
 - Material: Rubber
 - Series: V DGT



1245323 Empty Cable

RS PRO EMPTY CABLE REEL 55M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Type: Empty Cable Reel
 - Maximum Cable Length Capacity: 55 m, 65 m, 215 m
 - Cable Diameter Capacity: 6.5 mm, 12 mm, 14 mm
 - Height: 40 mm
 - Width: 120 mm
 - Diameter: 380 mm
 - Material: Steel



3793705 Empty Cable

RS PRO EMPTY CABLE REEL 20M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Type: Empty Cable Reel
 - Maximum Cable Length Capacity: 20 m, 25 m, 60 m
 - Cable Diameter Capacity: 6.5 mm, 12 mm, 14 mm
 - Height: 30 mm
 - Width: 100 mm
 - Diameter: 240 mm
 - Material: Plastic



3793727 Empty Cable

RS PRO EMPTY CABLE REEL 30M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Type: Empty Cable Reel
 - Maximum Cable Length Capacity: 30 m, 33 m, 115 m
 - Cable Diameter Capacity: 6.5 mm, 12 mm, 14 mm
 - Height: 30 mm
 - Width: 100 mm
 - Diameter: 300 mm
 - Material: Plastic



3793733 Empty Cable

RS PRO EMPTY CABLE REEL 90M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Type: Empty Cable Reel
 - Maximum Cable Length Capacity: 90 m, 110 m, 350 m
 - Cable Diameter Capacity: 6.5 mm, 12 mm, 14 mm
 - Height: 40 mm
 - Width: 120 mm
 - Diameter: 460 mm
 - Material: Steel



3793755 Empty Cable

PLIERS,CABLE TIE,MAX 5MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Tool Type: Cable Tie Plier



549909 Cable Tie Plier

RS PRO CABLE TIE GUN, 2.2 → 4.8MM CAPACITY

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Series: RS PRO
 - Cable Tie Capacity: 2.2 → 4.8 mm
 - Height Safe: No



2061753 RS PRO

TOOL,CABLE TIE,STAINLESS STEEL,CT3

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Cable Tie Capacity: 0.3 → 12 mm
 - Material: Steel



4931958 0.3 → 12 mm

CABLE TIE TOOL FOR 1.8 -4.8 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Cable Tie Capacity: 2.2 → 4.8 mm



8117732 2.2 → 4.8 mm

CABLE TIE TOOL FOR 2.5-10.0 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Cable Tie Capacity: 2.5 → 10 mm



8117735 2.5 → 10 mm

RS PRO SELF ADHESIVE CABLE TIE MOUNT 19.5 MM X 19.5MM, 4.6MM

- ขนาดบรรจุภัณฑ์: **50 x EA**
- Cable Tie Width Acceptance: 4.6 mm
 - Length: 19.5 mm
 - Width: 19.5 mm
 - Fixing Hole Diameter: 3.2 mm
 - Self Adhesive: Yes
 - Material: Nylon 66
 - Series: HC
 - Minimum Operating Temperature: -28 °C



227996 4.6 mm

RS PRO SELF ADHESIVE NATURAL CABLE TIE MOUNT 29 MM X 29MM,

- ขนาดบรรจุภัณฑ์: **50 x EA**
- Colour: Natural
 - Cable Tie Width Acceptance: 5 mm
 - Length: 29 mm
 - Width: 29 mm
 - Fixing Hole Diameter: 5 mm
 - Self Adhesive: Yes
 - Material: Nylon 66
 - Series: HC



229560 Natural

RS PRO BLACK CABLE TIE MOUNT 10 MM X 15MM, 4.8MM MAX. CABLE TIE

- ขนาดบรรจุภัณฑ์: **250 x EA**
- Colour: Black
 - Cable Tie Width Acceptance: 4.8 mm
 - Length: 15 mm
 - Width: 10 mm
 - Fixing Hole Diameter: 3.5 mm
 - Self Adhesive: No
 - Material: Nylon 66
 - Series: HC



233663 Black

CABLE,TIE,CLAMP,NYLON,BLACK,M6

- ขนาดบรรจุภัณฑ์: **250 x EA**
- Colour: Black
 - Cable Tie Width Acceptance: 8 mm
 - Length: 23 mm
 - Width: 16 mm
 - Fixing Hole Diameter: 6.3 mm
 - Material: Nylon 66
 - Series: HC
 - Minimum Operating Temperature: -45 °C



233685 Black

CABLE,TIE,CLAMP,NYLON,WHITE,M3

- ขนาดบรรจุภัณฑ์: **250 x EA**
- Colour: White
 - Cable Tie Width Acceptance: 5 mm
 - Length: 15 mm
 - Width: 10 mm
 - Fixing Hole Diameter: 3 mm
 - Material: Nylon 66
 - Series: SM
 - Minimum Operating Temperature: -45 °C



666717 White

CABLE,TIE,CLAMP,NYLON,WHITE,M6

- ขนาดบรรจุภัณฑ์: **250 x EA**
- Colour: White
 - Cable Tie Width Acceptance: 9 mm
 - Length: 23 mm
 - Width: 16 mm
 - Fixing Hole Diameter: 6 mm
 - Material: Nylon 66
 - Series: SM
 - Minimum Operating Temperature: -45 °C



666739 White

CABLE,TIE,BASE,NYLON,SELF ADHESIVE,12.7X12.7X2.5MM

- ขนาดบรรจุภัณฑ์: **50 x EA**
- Colour: Natural
 - Cable Tie Width Acceptance: 2.5 mm
 - Length: 13 mm
 - Width: 13 mm
 - Self Adhesive: Yes
 - Material: Nylon 66
 - Series: HC
 - Minimum Operating Temperature: -28 °C



666751 Natural

RS PRO SELF ADHESIVE NATURAL CABLE TIE MOUNT 12.5 MM X 12.5MM,

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Colour: Natural
 - Cable Tie Width Acceptance: 3.2 mm
 - Length: 12.5 mm
 - Width: 12.5 mm
 - Fixing Hole Diameter: 3.2 mm
 - Self Adhesive: Yes
 - Material: Nylon 66
 - Minimum Operating Temperature: -40 °C



2040240 Natural

RS PRO SELF ADHESIVE BLACK CABLE TIE MOUNT 19.5 MM X 19.5MM, 4.6MM

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Colour: Black
 - Cable Tie Width Acceptance: 4.6 mm
 - Length: 19.5 mm
 - Width: 19.5 mm
 - Fixing Hole Diameter: 3.9 mm
 - Self Adhesive: Yes
 - Material: Nylon 66
 - Minimum Operating Temperature: -40 °C



2040241 Black

RS PRO SELF ADHESIVE BLACK CABLE TIE MOUNT 19.5 MM X 19.5MM, 4.6MM

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Colour: Black
 - Cable Tie Width Acceptance: 4.6 mm
 - Length: 19.5 mm
 - Width: 19.5 mm
 - Fixing Hole Diameter: 3.9 mm
 - Self Adhesive: Yes
 - Material: Nylon 66
 - Minimum Operating Temperature: -40 °C



2040242 Black

RS PRO SELF ADHESIVE NATURAL CABLE TIE MOUNT 19.5 MM X 19.5MM,

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Colour: Natural
 - Cable Tie Width Acceptance: 4.6 mm
 - Length: 19.5 mm
 - Width: 19.5 mm
 - Fixing Hole Diameter: 3.9 mm
 - Self Adhesive: Yes
 - Material: Nylon 66
 - Minimum Operating Temperature: -40 °C



2040243 Natural

RS PRO SELF ADHESIVE BLACK CABLE TIE MOUNT 28.6 MM X 28.6MM,

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Colour: Black
 - Cable Tie Width Acceptance: 5.5 mm
 - Length: 28.6 mm
 - Width: 28.6 mm
 - Fixing Hole Diameter: 5.3 mm
 - Self Adhesive: Yes
 - Material: Nylon 66
 - Minimum Operating Temperature: -40 °C



2040244 Black

RS PRO SELF ADHESIVE BLACK CABLE TIE MOUNT 28.6 MM X 28.6MM,

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Colour: Black
 - Cable Tie Width Acceptance: 5.5 mm
 - Length: 28.6 mm
 - Width: 28.6 mm
 - Fixing Hole Diameter: 5.3 mm
 - Self Adhesive: Yes
 - Material: Nylon 66
 - Minimum Operating Temperature: -40 °C



2040245 Black

RS PRO SELF ADHESIVE NATURAL CABLE TIE MOUNT 28.6 MM X

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Colour: Natural
 - Cable Tie Width Acceptance: 5.5 mm
 - Length: 28.6 mm
 - Width: 28.6 mm
 - Fixing Hole Diameter: 5.3 mm
 - Self Adhesive: Yes
 - Material: Nylon 66
 - Minimum Operating Temperature: -40 °C



2040247 Natural

RS PRO SELF ADHESIVE NATURAL CABLE TIE MOUNT 38.5 MM X

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Colour: Natural
 - Cable Tie Width Acceptance: 10.2 mm
 - Length: 38.5 mm
 - Width: 38.5 mm
 - Fixing Hole Diameter: 7.6 mm
 - Self Adhesive: Yes
 - Material: Nylon 66
 - Minimum Operating Temperature: -40 °C



2040248 Natural

RS PRO SELF ADHESIVE BLACK CABLE TIE MOUNT 12.5 MM X 12.5MM, 3.2MM

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Colour: Black
 - Cable Tie Width Acceptance: 3.2 mm
 - Length: 12.5 mm
 - Width: 12.5 mm
 - Fixing Hole Diameter: 3.2 mm
 - Self Adhesive: Yes
 - Material: Nylon 66
 - Minimum Operating Temperature: -40 °C



2040249 Black

RS PRO SELF ADHESIVE BLACK CABLE TIE MOUNT 38.5 MM X 38.5MM,

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Colour: Black
 - Cable Tie Width Acceptance: 10.2 mm
 - Length: 38.5 mm
 - Width: 38.5 mm
 - Fixing Hole Diameter: 7.6 mm
 - Self Adhesive: Yes
 - Material: Nylon 66
 - Minimum Operating Temperature: -40 °C



2040250 Black

RS PRO BLACK CABLE TIE MOUNT 14.9 MM X 40.2MM, 10MM MAX. CABLE TIE

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Colour: Black
 - Cable Tie Width Acceptance: 10 mm
 - Length: 40.2 mm
 - Width: 14.9 mm
 - Fixing Hole Diameter: 8 mm
 - Self Adhesive: No
 - Material: Nylon 66
 - Minimum Operating Temperature: -40 °C



2138519 Black

RS PRO NATURAL CABLE TIE MOUNT 9.5 MM X 19MM, 5MM MAX. CABLE TIE

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Colour: Natural
 - Cable Tie Width Acceptance: 5 mm
 - Length: 19 mm
 - Width: 9.5 mm
 - Fixing Hole Diameter: 5.2 mm
 - Self Adhesive: No
 - Material: Nylon 66
 - Minimum Operating Temperature: -40 °C



2138520 Natural

RS PRO NATURAL CABLE TIE MOUNT 9.5 MM X 19MM, 5MM MAX. CABLE TIE

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Colour: Natural
 - Cable Tie Width Acceptance: 5 mm
 - Length: 19 mm
 - Width: 9.5 mm
 - Fixing Hole Diameter: 4.3 mm
 - Self Adhesive: No
 - Material: Nylon 66
 - Minimum Operating Temperature: -40 °C



2138521 Natural

NATURAL CABLE TIE MOUNT 10 MM X 15MM, 5.1MM MAX. CABLE TIE WIDTH

- ขนาดบรรจุภัณฑ์: **500 x EA**
- Colour: Natural
 - Cable Tie Width Acceptance: 5.1 mm
 - Length: 15 mm
 - Width: 10 mm
 - Fixing Hole Diameter: 3.5 mm
 - Self Adhesive: No
 - Material: Nylon 66
 - Minimum Operating Temperature: -40 °C



2138522 Natural

SELF ADHESIVE WHITE CABLE TIE MOUNT 28.6 MM X 28.6MM, 5.5MM

- ขนาดบรรจุภัณฑ์: **50 x EA**
- Colour: White
 - Cable Tie Width Acceptance: 5.5 mm
 - Length: 28.6 mm
 - Width: 28.6 mm
 - Fixing Hole Diameter: 5 mm
 - Self Adhesive: Yes
 - Material: Nylon 66
 - Minimum Operating Temperature: -40 °C



2138523 White

SELF ADHESIVE BLACK CABLE TIE MOUNT 29.2 MM X 29.2MM, 5.5MM

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Colour: Black
 - Cable Tie Width Acceptance: 5.5 mm
 - Length: 29.2 mm
 - Width: 29.2 mm
 - Fixing Hole Diameter: 5 mm
 - Self Adhesive: Yes
 - Material: Nylon 66
 - Minimum Operating Temperature: -40 °C



2138524 Black

NATURAL CABLE TIE MOUNT 16 MM X 23MM, 9MM MAX. CABLE TIE WIDTH

- ขนาดบรรจุภัณฑ์: **500 x EA**
- Colour: Natural
 - Cable Tie Width Acceptance: 9 mm
 - Length: 23 mm
 - Width: 16 mm
 - Fixing Hole Diameter: 6.3 mm
 - Self Adhesive: No
 - Material: Nylon 66
 - Minimum Operating Temperature: -40 °C



2138525 Natural

SELF ADHESIVE NATURAL CABLE TIE MOUNT 26.1 MM X 26.1MM, 8MM MAX.

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Colour: Natural
 - Cable Tie Width Acceptance: 8 mm
 - Length: 26.1 mm
 - Width: 26.1 mm
 - Fixing Hole Diameter: 4.3 mm
 - Self Adhesive: Yes
 - Material: Nylon 66
 - Minimum Operating Temperature: -40 °C



2138526 Natural

SELF ADHESIVE BLACK CABLE TIE MOUNT 26.1 MM X 26.1MM, 8MM MAX.

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Colour: Black
 - Cable Tie Width Acceptance: 8 mm
 - Length: 26.1 mm
 - Width: 26.1 mm
 - Fixing Hole Diameter: 4.3 mm
 - Self Adhesive: Yes
 - Material: Nylon 66
 - Minimum Operating Temperature: -40 °C



2138527 Black

BLACK CABLE TIE MOUNT 13.8 MM X 23MM, 9.5MM MAX. CABLE TIE WIDTH

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Colour: Black
 - Cable Tie Width Acceptance: 9.5 mm
 - Length: 23 mm
 - Width: 13.8 mm
 - Fixing Hole Diameter: 5.3 mm
 - Self Adhesive: No
 - Material: Nylon 66
 - Minimum Operating Temperature: -40 °C



2138528 Black

RS PRO SELF ADHESIVE BLACK CABLE TIE MOUNT 38.5 MM X 38.5MM,

- ขนาดบรรจุภัณฑ์: **50 x EA**
- Colour: Black
 - Cable Tie Width Acceptance: 10.2 mm
 - Length: 38.5 mm
 - Width: 38.5 mm
 - Fixing Hole Diameter: 5 mm
 - Self Adhesive: Yes
 - Material: Nylon 66
 - Minimum Operating Temperature: -40 °C



2138529 Black

RS PRO BLACK CABLE TIE MOUNT 9.6 MM X 18.5MM, 8.1MM MAX. CABLE TIE

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Colour: Black
 - Cable Tie Width Acceptance: 8.1 mm
 - Length: 18.5 mm
 - Width: 9.6 mm
 - Fixing Hole Diameter: 6.2 mm
 - Self Adhesive: No
 - Material: Nylon 66
 - Minimum Operating Temperature: -40 °C



2138531 Black

RS PRO SELF ADHESIVE NATURAL CABLE TIE MOUNT 28 MM X 28MM,

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Colour: Natural
 - Cable Tie Width Acceptance: 5.3 mm
 - Length: 28 mm
 - Width: 28 mm
 - Fixing Hole Diameter: 5.6 mm
 - Self Adhesive: Yes
 - Material: Nylon 66
 - Minimum Operating Temperature: -40 °C



2138539 Natural

RS PRO SELF ADHESIVE NATURAL CABLE TIE MOUNT 16 MM X 23MM,

- ขนาดบรรจุภัณฑ์: **50 x EA**
- Colour: Natural
 - Cable Tie Width Acceptance: 9 mm
 - Length: 23 mm
 - Width: 16 mm
 - Fixing Hole Diameter: 5 mm
 - Self Adhesive: Yes
 - Material: Nylon 66
 - Minimum Operating Temperature: -40 °C



2138540 Natural

RS PRO NATURAL CABLE TIE MOUNT 10 MM X 15MM, 5.1MM MAX. CABLE

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Colour: Natural
 - Cable Tie Width Acceptance: 5.1 mm
 - Length: 15 mm
 - Width: 10 mm
 - Fixing Hole Diameter: 3.5 mm
 - Self Adhesive: No
 - Material: Nylon 66
 - Minimum Operating Temperature: -40 °C



2163630 Natural

CABLE, TIE, BASE, NYLON, SELF ADHESIVE, 38X38X10.2, WITH

- ขนาดบรรจุภัณฑ์: **50 x EA**
- Colour: Natural
 - Cable Tie Width Acceptance: 10.2 mm
 - Length: 38.5 mm
 - Width: 38.5 mm
 - Fixing Hole Diameter: 5 mm
 - Self Adhesive: Yes
 - Material: Nylon 66
 - Series: HC



6292514 Natural

BLACK S/ADHESIVE C/TIE BASE, 38X38MM

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Colour: Black
 - Cable Tie Width Acceptance: 10.2 mm
 - Length: 38 mm
 - Width: 38 mm
 - Fixing Hole Diameter: 5 mm
 - Self Adhesive: Yes
 - Material: Nylon 66
 - Series: HC



7300335 Black

RS PRO SELF ADHESIVE NATURAL CABLE TIE MOUNT 19.5 MM X 19.5MM,

- ขนาดบรรจุภัณฑ์: **250 x EA**
- Colour: Natural
 - Cable Tie Width Acceptance: 4.6 mm
 - Length: 19.5 mm
 - Width: 19.5 mm
 - Fixing Hole Diameter: 3.2 mm
 - Self Adhesive: Yes
 - Material: Nylon 66
 - Series: HC



8111713 Natural

CABLE TIE MOUNT 12.5X12.5 BLACK NYLON 66

- ขนาดบรรจุภัณฑ์: **50 x EA**
- Colour: Black
 - Cable Tie Width Acceptance: 3.2 mm
 - Length: 12.5 mm
 - Width: 12.5 mm
 - Fixing Hole Diameter: 3.2 mm
 - Self Adhesive: Yes
 - Material: Nylon 66
 - Series: HC



8111723 Black

CABLE TIE MOUNT 19.5X19.5 BLACK NYLON 66

- ขนาดบรรจุภัณฑ์: **50 x EA**
- Colour: Black
 - Cable Tie Width Acceptance: 4.6 mm
 - Length: 19.5 mm
 - Width: 19.5 mm
 - Fixing Hole Diameter: 3.2 mm
 - Self Adhesive: Yes
 - Material: Nylon 66
 - Series: HC



8111726 Black

CABLE TIE MOUNT 29.2X29.2 BLACK NYLON 66

- ขนาดบรรจุภัณฑ์: **50 x EA**
- Colour: Black
 - Cable Tie Width Acceptance: 5.5 mm
 - Length: 29.2 mm
 - Width: 29.2 mm
 - Fixing Hole Diameter: 5 mm
 - Self Adhesive: Yes
 - Material: Nylon 66
 - Series: HC



8111729 Black

PUSH TIE MOUNT NYLON 9+V-2 NATURAL 3.8MM

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Colour: Natural
 - Cable Tie Width Acceptance: 3.8 mm
 - Length: 15 mm
 - Width: 6.5 mm
 - Fixing Hole Diameter: 4.8 mm
 - Material: Nylon 66
 - Series: PHC
 - Quantity: 100



8659675 Natural

RS PRO NATURAL CABLE TIE MOUNT 16.1MM, 5MM MAX. CABLE TIE WIDTH

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Colour: Natural
 - Cable Tie Width Acceptance: 5 mm
 - Length: 16.1 mm
 - Fixing Hole Diameter: 7 mm
 - Material: Nylon 66
 - Series: PHC
 - Quantity: 100



8659679 Natural

RS PRO NATURAL CABLE TIE MOUNT 12.1 MM X 17.6MM, 6.5MM MAX.

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Colour: Natural
 - Cable Tie Width Acceptance: 6.5 mm
 - Length: 17.6 mm
 - Width: 12.1 mm
 - Fixing Hole Diameter: 9 x 8 mm
 - Material: Nylon 66
 - Series: PHC
 - Quantity: 100



8659681 Natural

RS PRO NATURAL CABLE TIE MOUNT 16.1MM, 5MM MAX. CABLE TIE WIDTH

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Colour: Natural
 - Cable Tie Width Acceptance: 5 mm
 - Length: 16.1 mm
 - Fixing Hole Diameter: 7 mm
 - Material: Nylon 66
 - Series: PHC
 - Quantity: 100



8659688 Natural

SELF ADH TIE MOUNT NYLON NATURAL 19X19MM

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Colour: Natural
 - Cable Tie Width Acceptance: 4.1 mm
 - Length: 19 mm
 - Width: 19 mm
 - Fixing Hole Diameter: 4.4 mm
 - Self Adhesive: Yes
 - Material: Nylon 66
 - Series: HC



8659701 Natural

SELF ADH TIE MOUNT NYLON NATURAL 26.5MM

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Colour: Natural
 - Cable Tie Width Acceptance: 5.6 mm
 - Length: 26.3 mm
 - Width: 26.3 mm
 - Fixing Hole Diameter: 5 mm
 - Self Adhesive: Yes
 - Material: Nylon 66
 - Series: HC



8659704 Natural

RS PRO NATURAL CABLE TIE MOUNT 13.8 MM X 23MM, 9.5MM MAX. CABLE

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Colour: Natural
 - Cable Tie Width Acceptance: 9.5 mm
 - Length: 23 mm
 - Width: 13.8 mm
 - Fixing Hole Diameter: 5.3 mm
 - Material: Nylon 66
 - Series: HC
 - Quantity: 100



8659708 Natural

RS PRO NATURAL CABLE TIE MOUNT 14.7 MM X 30MM, 9.3MM MAX. CABLE


- ขนาดบรรจุภัณฑ์: **100 x EA**
- Colour: Natural
 - Cable Tie Width Acceptance: 9.3 mm
 - Length: 30 mm
 - Width: 14.7 mm
 - Fixing Hole Diameter: 5 mm
 - Material: Nylon 66
 - Series: HC
 - Quantity: 100



8659717 Natural

RS PRO CABLE TIE, LADDER, 225MM X 7 MM, METALLIC 316 STAINLESS STEEL,

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 225 mm
 - Width: 7 mm
 - Colour: Metallic
 - Material: 316 Stainless Steel
 - Type: Ladder
 - Quantity: 100
 - Minimum Operating Temperature: -80 °C
 - Maximum Operating Temperature: +539 °C



121618 225 mm

RS PRO CABLE TIE, LADDER, 300MM X 7 MM, METALLIC 316 STAINLESS STEEL,

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 300 mm
 - Width: 7 mm
 - Colour: Metallic
 - Material: 316 Stainless Steel
 - Type: Ladder
 - Quantity: 100
 - Minimum Operating Temperature: -80 °C
 - Maximum Operating Temperature: +539 °C



121624 300 mm

RS PRO CABLE TIE, LADDER, 610MM X 12 MM, METALLIC 316 STAINLESS


- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 610 mm
 - Width: 12 mm
 - Colour: Metallic
 - Material: 316 Stainless Steel
 - Type: Ladder
 - Quantity: 100
 - Minimum Operating Temperature: -80 °C
 - Maximum Operating Temperature: +539 °C



121646 610 mm

RS PRO CABLE TIE, LADDER, 225MM X 7 MM, BLACK POLYESTER COATED

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 225 mm
 - Width: 7 mm
 - Colour: Black
 - Material: Polyester Coated Stainless Steel
 - Type: Ladder
 - Quantity: 100
 - Minimum Operating Temperature: -80 °C
 - Maximum Operating Temperature: +150 °C



121652 225 mm

RS PRO CABLE TIE, LADDER, 300MM X 7 MM, BLACK POLYESTER COATED


- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 300 mm
 - Width: 7 mm
 - Colour: Black
 - Material: Polyester Coated Stainless Steel
 - Type: Ladder
 - Quantity: 100
 - Minimum Operating Temperature: -80 °C
 - Maximum Operating Temperature: +150 °C



121668 300 mm

RS PRO CABLE TIE, LADDER, 610MM X 7 MM, BLACK POLYESTER COATED

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 610 mm
 - Width: 7 mm
 - Colour: Black
 - Material: Polyester Coated Stainless Steel
 - Type: Ladder
 - Quantity: 100
 - Minimum Operating Temperature: -80 °C
 - Maximum Operating Temperature: +150 °C



121674 610 mm

RS PRO CABLE TIE, 150MM X 3.6 MM, NATURAL NYLON, PK-100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 150 mm
 - Width: 3.6 mm
 - Colour: Natural
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 100
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



178478 150 mm

RS PRO CABLE TIE, 190MM X 4.8 MM, NATURAL NYLON, PK-100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 190 mm
 - Width: 4.8 mm
 - Colour: Natural
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 100
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



178484 190 mm

RS PRO CABLE TIE, 292MM X 3.6 MM, NATURAL NYLON, PK-100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 292 mm
 - Width: 3.6 mm
 - Colour: Natural
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 100
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



178490 292 mm

RS PRO CABLE TIE, 368MM X 4.8 MM, NATURAL NYLON, PK-100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 368 mm
 - Width: 4.8 mm
 - Colour: Natural
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 100
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



178507 368 mm

RS PRO CABLE TIE, 380MM X 7.6 MM, NATURAL NYLON, PK-100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 380 mm
 - Width: 7.6 mm
 - Colour: Natural
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 100
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



178513 380 mm

RS PRO CABLE TIE, 100MM X 2.5 MM, ASSORTED NYLON, PK-1000

- ขนาดบรรจุภัณฑ์: **1000 x EA**
- Length: 100 mm
 - Width: 2.5 mm
 - Colour: Assorted
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 1000
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



233118 100 mm

RS PRO CABLE TIE, 100MM X 2.5 MM, 4.6 MM, 4.8 MM, ASSORTED NYLON,

- ขนาดบรรจุภัณฑ์: **650 x EA**
- Length: 100 mm, 203 mm, 280 mm
 - Width: 2.5 mm, 4.6 mm, 4.8 mm
 - Colour: Assorted
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 650
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



233124 100 mm, 203 mm,

RS PRO CABLE TIE, 100MM X 2.5 MM, 4.6 MM, 4.8 MM, ASSORTED NYLON,

- ขนาดบรรจุภัณฑ์: **850 x EA**
- Length: 100 mm, 203 mm, 280 mm
 - Width: 2.5 mm, 4.6 mm, 4.8 mm
 - Colour: Assorted
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 850
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



233130 100 mm, 203 mm,

RS PRO CABLE TIE, 100MM X 2.5 MM, BLUE NYLON, PK-100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 100 mm
 - Width: 2.5 mm
 - Colour: Blue
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 100
 - Minimum Operating Temperature: -50 °C
 - Maximum Operating Temperature: +85 °C



233203 100 mm

RS PRO CABLE TIE, 100MM X 2.5 MM, RED NYLON, PK-100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 100 mm
 - Width: 2.5 mm
 - Colour: Red
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 100
 - Minimum Operating Temperature: -50 °C
 - Maximum Operating Temperature: +85 °C



233207 100 mm

RS PRO CABLE TIE, 100MM X 2.5 MM, GREEN NYLON, PK-100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 100 mm
 - Width: 2.5 mm
 - Colour: Green
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 100
 - Minimum Operating Temperature: -50 °C
 - Maximum Operating Temperature: +85 °C



233225 100 mm

RS PRO CABLE TIE, 100MM X 2.5 MM, YELLOW NYLON, PK-100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 100 mm
 - Width: 2.5 mm
 - Colour: Yellow
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 100
 - Minimum Operating Temperature: -50 °C
 - Maximum Operating Temperature: +85 °C



233229 100 mm

RS PRO CABLE TIE, 165MM X 2.5 MM, RED NYLON, PK-100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 165 mm
 - Width: 2.5 mm
 - Colour: Red
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 100
 - Minimum Operating Temperature: -50 °C
 - Maximum Operating Temperature: +85 °C



233231 165 mm

RS PRO CABLE TIE, 100MM X 2.5 MM, ORANGE NYLON, PK-100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 100 mm
 - Width: 2.5 mm
 - Colour: Orange
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 100
 - Minimum Operating Temperature: -50 °C
 - Maximum Operating Temperature: +85 °C



233235 100 mm

RS PRO CABLE TIE, 165MM X 2.5 MM, BLUE NYLON, PK-100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 165 mm
 - Width: 2.5 mm
 - Colour: Blue
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 100
 - Minimum Operating Temperature: -50 °C
 - Maximum Operating Temperature: +85 °C



233241 165 mm

RS PRO CABLE TIE, 165MM X 2.5 MM, YELLOW NYLON, PK-100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 165 mm
 - Width: 2.5 mm
 - Colour: Yellow
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 100
 - Minimum Operating Temperature: -50 °C
 - Maximum Operating Temperature: +85 °C



233269 165 mm

RS PRO CABLE TIE, 165MM X 2.5 MM, GREEN NYLON, PK-100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 165 mm
 - Width: 2.5 mm
 - Colour: Green
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 100
 - Minimum Operating Temperature: -50 °C
 - Maximum Operating Temperature: +85 °C



233275 165 mm

RS PRO CABLE TIE, 165MM X 2.5 MM, ORANGE NYLON, PK-100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 165 mm
 - Width: 2.5 mm
 - Colour: Orange
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 100
 - Minimum Operating Temperature: -50 °C
 - Maximum Operating Temperature: +85 °C



233281 165 mm

RS PRO CABLE TIE, 203MM X 2.5 MM, RED NYLON, PK-100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 203 mm
 - Width: 2.5 mm
 - Colour: Red
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 100
 - Minimum Operating Temperature: -50 °C
 - Maximum Operating Temperature: +85 °C



233297 203 mm

RS PRO CABLE TIE, 203MM X 2.5 MM, BLUE NYLON, PK-100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 203 mm
 - Width: 2.5 mm
 - Colour: Blue
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 100
 - Minimum Operating Temperature: -50 °C
 - Maximum Operating Temperature: +85 °C



233304 203 mm

RS PRO CABLE TIE, 203MM X 2.5 MM, YELLOW NYLON, PK-100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 203 mm
 - Width: 2.5 mm
 - Colour: Yellow
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 100
 - Minimum Operating Temperature: -50 °C
 - Maximum Operating Temperature: +85 °C



233310 203 mm

RS PRO CABLE TIE, 203MM X 2.5 MM, GREEN NYLON, PK-100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 203 mm
 - Width: 2.5 mm
 - Colour: Green
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 100
 - Minimum Operating Temperature: -50 °C
 - Maximum Operating Temperature: +85 °C



233354 203 mm

RS PRO CABLE TIE, 203MM X 2.5 MM, ORANGE NYLON, PK-100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 203 mm
 - Width: 2.5 mm
 - Colour: Orange
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 100
 - Minimum Operating Temperature: -50 °C
 - Maximum Operating Temperature: +85 °C



233386 203 mm

RS PRO CABLE TIE, 100MM X 2.5 MM, BLACK NYLON, PK-100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 100 mm
 - Width: 2.5 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 100
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



233455 100 mm

RS PRO CABLE TIE, 190MM X 4.8 MM, BLACK NYLON, PK-100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 190 mm
 - Width: 4.8 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 100
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



233461 190 mm

RS PRO CABLE TIE, 150MM X 3.6 MM, BLACK NYLON, PK-100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 150 mm
 - Width: 3.6 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 100
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



233465 150 mm

RS PRO CABLE TIE, 203MM X 4.6 MM, BLACK NYLON, PK-100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 203 mm
 - Width: 4.6 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 100
 - UV Resistant: Yes
 - Minimum Operating Temperature: -40 °C



233471 203 mm

RS PRO CABLE TIE, 292MM X 3.6 MM, BLACK NYLON, PK-100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 292 mm
 - Width: 3.6 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 100
 - UV Resistant: Yes
 - Minimum Operating Temperature: -40 °C



233477 292 mm

RS PRO CABLE TIE, 368MM X 4.8 MM, BLACK NYLON, PK-100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 368 mm
 - Width: 4.8 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 100
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



233483 368 mm

RS PRO CABLE TIE, 300MM X 4.8 MM, BLACK NYLON, PK-100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 300 mm
 - Width: 4.8 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 100
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



233487 300 mm

RS PRO CABLE TIE, 380MM X 7.6 MM, BLACK NYLON, PK-100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 380 mm
 - Width: 7.6 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 100
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



233493 380 mm

RS PRO CABLE TIE, 100MM X 2.5 MM, BLACK NYLON, PK-1000

- ขนาดบรรจุภัณฑ์: **1000 x EA**
- Length: 100 mm
 - Width: 2.5 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 1000
 - UV Resistant: No
 - Minimum Operating Temperature: -40 °C



233499 100 mm

RS PRO CABLE TIE, 150MM X 3.6 MM, BLACK NYLON, PK-1000

- ขนาดบรรจุภัณฑ์: **1000 x EA**
- Length: 150 mm
 - Width: 3.6 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 1000
 - UV Resistant: No
 - Minimum Operating Temperature: -40 °C



233500 150 mm

RS PRO CABLE TIE, 190MM X 4.8 MM, BLACK NYLON, PK-1000

- ขนาดบรรจุภัณฑ์: **1000 x EA**
- Length: 190 mm
 - Width: 4.8 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 1000
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



233506 190 mm

RS PRO CABLE TIE, 100MM X 2.5 MM, ASSORTED NYLON, PK-250

- ขนาดบรรจุภัณฑ์: **250 x EA**
- Length: 100 mm
 - Width: 2.5 mm
 - Colour: Assorted
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 250
 - Minimum Operating Temperature: -50 °C
 - Maximum Operating Temperature: +85 °C



233528 100 mm

RS PRO CABLE TIE, 165MM X 2.5 MM, ASSORTED NYLON, PK-250

- ขนาดบรรจุภัณฑ์: **250 x EA**
- Length: 165 mm
 - Width: 2.5 mm
 - Colour: Assorted
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 250
 - Minimum Operating Temperature: -50 °C
 - Maximum Operating Temperature: +85 °C



233534 165 mm

RS PRO CABLE TIE, 203MM X 2.5 MM, ASSORTED NYLON, PK-250

- ขนาดบรรจุภัณฑ์: **250 x EA**
- Length: 203 mm
 - Width: 2.5 mm
 - Colour: Assorted
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 250
 - Minimum Operating Temperature: -50 °C
 - Maximum Operating Temperature: +85 °C



233540 203 mm

RS PRO CABLE TIE, 150MM X 3.6 MM, ASSORTED NYLON, PK-250

- ขนาดบรรจุภัณฑ์: **250 x EA**
- Length: 150 mm
 - Width: 3.6 mm
 - Colour: Assorted
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 250
 - Minimum Operating Temperature: -50 °C
 - Maximum Operating Temperature: +85 °C



233691 150 mm

RS PRO CABLE TIE, 203MM X 4.6 MM, ASSORTED NYLON, PK-250

- ขนาดบรรจุภัณฑ์: **250 x EA**
- Length: 203 mm
 - Width: 4.6 mm
 - Colour: Assorted
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 250
 - Minimum Operating Temperature: -50 °C
 - Maximum Operating Temperature: +85 °C



233708 203 mm

RS PRO CABLE TIE, 300MM X 4.8 MM, ASSORTED NYLON, PK-250

- ขนาดบรรจุภัณฑ์: **250 x EA**
- Length: 300 mm
 - Width: 4.8 mm
 - Colour: Assorted
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 250
 - Minimum Operating Temperature: -50 °C
 - Maximum Operating Temperature: +85 °C



233714 300 mm

RS PRO CABLE TIE, 385MM X 4.8 MM, ASSORTED NYLON, PK-250

- ขนาดบรรจุภัณฑ์: **250 x EA**
- Length: 385 mm
 - Width: 4.8 mm
 - Colour: Assorted
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 250
 - Minimum Operating Temperature: -50 °C
 - Maximum Operating Temperature: +85 °C



233792 385 mm

RS PRO CABLE TIE, 100MM X 2.5 MM, WHITE NYLON, PK-100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 100 mm
 - Width: 2.5 mm
 - Colour: White
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 100
 - Minimum Operating Temperature: -50 °C
 - Maximum Operating Temperature: +85 °C



389864 100 mm

RS PRO CABLE TIE, 190MM X 4.8 MM, WHITE NYLON, PK-100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 190 mm
 - Width: 4.8 mm
 - Colour: White
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 100
 - Minimum Operating Temperature: -10 °C
 - Maximum Operating Temperature: +85 °C



389870 190 mm

RS PRO CABLE TIE, 100MM X 2.5 MM, WHITE NYLON, PK-100


- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 100 mm
 - Width: 2.5 mm
 - Colour: White
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 100
 - Minimum Operating Temperature: -50 °C
 - Maximum Operating Temperature: +85 °C



390274 100 mm

RS PRO CABLE TIE, 200MM X 3.6 MM, BLUE NYLON, PK-100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 200 mm
 - Width: 3.6 mm
 - Colour: Blue
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 100
 - Tensile Strength: 176.4 N



404534 200 mm

RS PRO CABLE TIE, 203MM X 3.6 MM, PINK NYLON, PK-100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 203 mm
 - Width: 3.6 mm
 - Colour: Pink
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 100
 - Tensile Strength: 176.4 N
 - Maximum Bundle Diameter: 52 mm



404538 203 mm

RS PRO CABLE TIE, 203MM X 3.6 MM, YELLOW NYLON, PK-100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 203 mm
 - Width: 3.6 mm
 - Colour: Yellow
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 100
 - Tensile Strength: 176.4 N
 - Maximum Bundle Diameter: 52 mm



404540 203 mm

RS PRO CABLE TIE, 203MM X 3.6 MM, GREEN NYLON, PK-100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 203 mm
 - Width: 3.6 mm
 - Colour: Green
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 100
 - Tensile Strength: 176.4 N
 - Maximum Bundle Diameter: 52 mm



404544 203 mm

RS PRO CABLE TIE, 203MM X 3.6 MM, ORANGE NYLON, PK-100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 203 mm
 - Width: 3.6 mm
 - Colour: Orange
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 100
 - Tensile Strength: 176.4 N
 - Maximum Bundle Diameter: 52 mm



404550 203 mm

RS PRO CABLE TIE, 143MM X 1.8 MM, NATURAL NYLON, PK-100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 143 mm
 - Width: 1.8 mm
 - Colour: Natural
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 100
 - Fire Behaviour: Flame Retardant
 - Tensile Strength: 49 N



479588 143 mm

RS PRO CABLE TIE, 143MM X 1.8 MM, WHITE NYLON, PK-1000

- ขนาดบรรจุภัณฑ์: **1000 x EA**
- Length: 143 mm
 - Width: 1.8 mm
 - Colour: White
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 1000
 - Fire Behaviour: Flame Retardant
 - Tensile Strength: 49 N



479594 143 mm

RS PRO CABLE TIE, SCREW MOUNT, 113MM X 2.5 MM, NATURAL NYLON,

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 113 mm
 - Width: 2.5 mm
 - Colour: Natural
 - Material: Nylon 66
 - Type: Screw Mount
 - Quantity: 100
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



601079 113 mm

RS PRO CABLE TIE, SCREW MOUNT, 171.5MM X 3.7 MM, NATURAL NYLON,

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 171.5 mm
 - Width: 3.7 mm
 - Colour: Natural
 - Material: Nylon 66
 - Type: Screw Mount
 - Quantity: 100
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



601085 171.5 mm

RS PRO CABLE TIE, SCREW MOUNT, 221.3MM X 4.2 MM, NATURAL NYLON,

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 221.3 mm
 - Width: 4.2 mm
 - Colour: Natural
 - Material: Nylon 66
 - Type: Screw Mount
 - Quantity: 100
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



601091 221.3 mm

RS PRO CABLE TIE, SCREW MOUNT, 317.2MM X 7.8 MM, NATURAL NYLON,

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 317.2 mm
 - Width: 7.8 mm
 - Colour: Natural
 - Material: Nylon 66
 - Type: Screw Mount
 - Quantity: 100
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



601108 317.2 mm

RS PRO CABLE TIE, ROLLER BALL, 840MM X 12 MM, STEEL STAINLESS

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 840 mm
 - Width: 12 mm
 - Colour: Steel
 - Material: Stainless Steel
 - Type: Roller Ball
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +300 °C
 - Fire Behaviour: Halogen Free



1235028 840 mm

RS PRO CABLE TIE, ROLLER BALL, 360MM X 12 MM, STEEL STAINLESS

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 360 mm
 - Width: 12 mm
 - Colour: Steel
 - Material: Stainless Steel
 - Type: Roller Ball
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +300 °C
 - Fire Behaviour: Halogen Free



1235029 360 mm

RS PRO CABLE TIE, ROLLER BALL, 520MM X 12 MM, STEEL STAINLESS

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 520 mm
 - Width: 12 mm
 - Colour: Steel
 - Material: Stainless Steel
 - Type: Roller Ball
 - Minimum Operating Temperature: -80 °C
 - Maximum Operating Temperature: +538 °C
 - Tensile Strength: 2225 N



1235030 520 mm

RS PRO CABLE TIE, ROLLER BALL, 680MM X 12 MM, STEEL STAINLESS

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 680 mm
 - Width: 12 mm
 - Colour: Steel
 - Material: Stainless Steel
 - Type: Roller Ball
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +300 °C
 - Fire Behaviour: Halogen Free



1235033 680 mm

RS PRO CABLE TIE, ROLLER BALL, 200MM X 4.6 MM, STEEL STAINLESS

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 200 mm
 - Width: 4.6 mm
 - Colour: Steel
 - Material: Stainless Steel
 - Type: Roller Ball
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +300 °C
 - Fire Behaviour: Halogen Free



1235034 200 mm

RS PRO CABLE TIE, ROLLER BALL, 360MM X 7.9 MM, STEEL STAINLESS

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 360 mm
 - Width: 7.9 mm
 - Colour: Steel
 - Material: Stainless Steel
 - Type: Roller Ball
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +300 °C
 - Fire Behaviour: Halogen Free



1235035 360 mm

RS PRO CABLE TIE, ROLLER BALL, 125MM X 4.6 MM, STEEL STAINLESS

- ขนาดบรรจุภัณฑ์: 100 x EA
- Length: 125 mm
 - Width: 4.6 mm
 - Colour: Steel
 - Material: Stainless Steel
 - Type: Roller Ball
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +300 °C
 - Fire Behaviour: Halogen Free



1235036 125 mm

RS PRO CABLE TIE, ROLLER BALL, 360MM X 4.6 MM, STEEL STAINLESS

- ขนาดบรรจุภัณฑ์: 100 x EA
- Length: 360 mm
 - Width: 4.6 mm
 - Colour: Steel
 - Material: Stainless Steel
 - Type: Roller Ball
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +300 °C
 - Fire Behaviour: Halogen Free



1235037 360 mm

RS PRO CABLE TIE, ROLLER BALL, 200MM X 7.9 MM, METALLIC 316

- ขนาดบรรจุภัณฑ์: 100 x EA
- Length: 200 mm
 - Width: 7.9 mm
 - Colour: Metallic
 - Material: 316 Stainless Steel
 - Type: Roller Ball
 - Quantity: 100
 - Minimum Operating Temperature: -80 °C
 - Maximum Operating Temperature: +538 °C



1595313 200 mm

RS PRO CABLE TIE, ROLLER BALL, 360MM X 4.6 MM, METALLIC 316

- ขนาดบรรจุภัณฑ์: 100 x EA
- Length: 360 mm
 - Width: 4.6 mm
 - Colour: Metallic
 - Material: 316 Stainless Steel
 - Type: Roller Ball
 - Quantity: 100
 - Minimum Operating Temperature: -80 °C
 - Maximum Operating Temperature: +538 °C



1595329 360 mm

RS PRO CABLE TIE, ROLLER BALL, 360MM X 7.9 MM, METALLIC 316

- ขนาดบรรจุภัณฑ์: 100 x EA
- Length: 360 mm
 - Width: 7.9 mm
 - Colour: Metallic
 - Material: 316 Stainless Steel
 - Type: Roller Ball
 - Quantity: 100
 - Minimum Operating Temperature: -80 °C
 - Maximum Operating Temperature: +538 °C



1595335 360 mm

RS PRO CABLE TIE, BALL LOCK, 200MM X 4.6 MM, METALLIC 316

- ขนาดบรรจุภัณฑ์: 100 x EA
- Length: 200 mm
 - Width: 4.6 mm
 - Colour: Metallic
 - Material: 316 Stainless Steel
 - Type: Ball Lock
 - Quantity: 100
 - Minimum Operating Temperature: -80 °C
 - Maximum Operating Temperature: +538 °C



1595357 200 mm

RS PRO CABLE TIE, METAL DETECTABLE, 203MM X 4.6 MM, BLUE

- ขนาดบรรจุภัณฑ์: 100 x EA
- Length: 203 mm
 - Width: 4.6 mm
 - Colour: Blue
 - Material: Metal Detectable Nylon
 - Type: Metal Detectable
 - Quantity: 100
 - Maximum Bundle Diameter: 52 mm



1721765 203 mm

RS PRO CABLE TIE, METAL DETECTABLE, 150MM X 3.6 MM, BLUE

- ขนาดบรรจุภัณฑ์: 100 x EA
- Length: 150 mm
 - Width: 3.6 mm
 - Colour: Blue
 - Material: Metal Detectable Nylon
 - Type: Metal Detectable
 - Quantity: 100
 - Maximum Bundle Diameter: 36 mm



1721766 150 mm

RS PRO CABLE TIE, METAL DETECTABLE, 400MM X 4.6 MM, BLUE

- ขนาดบรรจุภัณฑ์: 100 x EA
- Length: 400 mm
 - Width: 4.6 mm
 - Colour: Blue
 - Material: Metal Detectable Nylon
 - Type: Metal Detectable
 - Quantity: 100
 - Maximum Bundle Diameter: 116 mm



1721767 400 mm

RS PRO CABLE TIE, METAL DETECTABLE, 380MM X 7.6 MM, BLUE

- ขนาดบรรจุภัณฑ์: 100 x EA
- Length: 380 mm
 - Width: 7.6 mm
 - Colour: Blue
 - Material: Metal Detectable Nylon
 - Type: Metal Detectable
 - Quantity: 100
 - Maximum Bundle Diameter: 105 mm



1721768 380 mm

RS PRO CABLE TIE, METAL DETECTABLE, 250MM X 4.5 MM, BLUE

- ขนาดบรรจุภัณฑ์: 100 x EA
- Length: 250 mm
 - Width: 4.5 mm
 - Colour: Blue
 - Material: Metal Detectable Nylon
 - Type: Metal Detectable
 - Quantity: 100
 - Maximum Bundle Diameter: 65 mm



1721769 250 mm

RS PRO CABLE TIE, 200MM X 4.6 MM, BLACK PP, PK-100

- ขนาดบรรจุภัณฑ์: 100 x EA
- Length: 200 mm
 - Width: 4.6 mm
 - Colour: Black
 - Material: PP
 - Quantity: 100
 - Tensile Strength: 10 kg
 - Maximum Bundle Diameter: 52 mm



1789487 200 mm

RS PRO CABLE TIE, 300MM X 7.6 MM, BLACK PP, PK-100

- ขนาดบรรจุภัณฑ์: 100 x EA
- Length: 300 mm
 - Width: 7.6 mm
 - Colour: Black
 - Material: PP
 - Quantity: 100
 - Tensile Strength: 23 kg
 - Maximum Bundle Diameter: 80 mm



1789488 300 mm

RS PRO CABLE TIE, DOUBLE HEAD KNOT, 150MM X 3.6 MM, NATURAL PE

- ขนาดบรรจุภัณฑ์: 100 x EA
- Length: 150 mm
 - Width: 3.6 mm
 - Colour: Natural
 - Material: PE
 - Type: Double Head Knot
 - Quantity: 100
 - Maximum Bundle Diameter: 38 mm



1789498 150 mm

RS PRO CABLE TIE, HOOK AND LOOP, 150MM X 17 MM, BLACK NYLON

- ขนาดบรรจุภัณฑ์: 10 x EA
- Length: 150 mm
 - Width: 17 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Hook and Loop



1797165 150 mm

RS PRO CABLE TIE, HOOK AND LOOP, 225MM X 25 MM, BLACK NYLON

- ขนาดบรรจุภัณฑ์: 10 x EA
- Length: 225 mm
 - Width: 25 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Hook and Loop



1797166 225 mm

RS PRO CABLE TIE, HOOK AND LOOP, 225MM X 25 MM, RED NYLON

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Length: 225 mm
 - Width: 25 mm
 - Colour: Red
 - Material: Nylon 66
 - Type: Hook and Loop



1797167 225 mm

RS PRO CABLE TIE, HOOK AND LOOP, 225MM X 25 MM, YELLOW NYLON

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Length: 225 mm
 - Width: 25 mm
 - Colour: Yellow
 - Material: Nylon 66
 - Type: Hook and Loop



1797168 225 mm

RS PRO CABLE TIE, HOOK AND LOOP, 225MM X 25 MM, GREEN NYLON


- ขนาดบรรจุภัณฑ์: **10 x EA**
- Length: 225 mm
 - Width: 25 mm
 - Colour: Green
 - Material: Nylon 66
 - Type: Hook and Loop



1797169 225 mm

RS PRO CABLE TIE, HOOK AND LOOP, 225MM X 25 MM, BLUE NYLON

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Length: 225 mm
 - Width: 25 mm
 - Colour: Blue
 - Material: Nylon 66
 - Type: Hook and Loop



1797170 225 mm

RS PRO CABLE TIE, HOOK AND LOOP, 225MM X 25 MM, WHITE NYLON

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Length: 225 mm
 - Width: 25 mm
 - Colour: White
 - Material: Nylon 66
 - Type: Hook and Loop



1797171 225 mm

RS PRO CABLE TIE, HOOK AND LOOP, 325MM X 25 MM, BLACK NYLON

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Length: 325 mm
 - Width: 25 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Hook and Loop



1797172 325 mm

RS PRO CABLE TIE, HOOK AND LOOP, 325MM X 25 MM, RED NYLON

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Length: 325 mm
 - Width: 25 mm
 - Colour: Red
 - Material: Nylon 66
 - Type: Hook and Loop



1797173 325 mm

RS PRO CABLE TIE, HOOK AND LOOP, 325MM X 25 MM, YELLOW NYLON

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Length: 325 mm
 - Width: 25 mm
 - Colour: Yellow
 - Material: Nylon 66
 - Type: Hook and Loop



1797174 325 mm

RS PRO CABLE TIE, HOOK AND LOOP, 325MM X 25 MM, GREEN NYLON

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Length: 325 mm
 - Width: 25 mm
 - Colour: Green
 - Material: Nylon 66
 - Type: Hook and Loop



1797175 325 mm

RS PRO CABLE TIE, HOOK AND LOOP, 325MM X 25 MM, BLUE NYLON

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Length: 325 mm
 - Width: 25 mm
 - Colour: Blue
 - Material: Nylon 66
 - Type: Hook and Loop



1797176 325 mm

RS PRO CABLE TIE, HOOK AND LOOP, 5M X 16 MM, BLACK NYLON

- ขนาดบรรจุภัณฑ์: **5 x MTR**
- Length: 5 m
 - Width: 16 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Hook and Loop



1797177 5 m

RS PRO CABLE TIE, HOOK AND LOOP, 5M X 16 MM, RED NYLON

- ขนาดบรรจุภัณฑ์: **5 x MTR**
- Length: 5 m
 - Width: 16 mm
 - Colour: Red
 - Material: Nylon 66
 - Type: Hook and Loop



1797178 5 m

RS PRO CABLE TIE, HOOK AND LOOP, 5M X 16 MM, YELLOW NYLON

- ขนาดบรรจุภัณฑ์: **5 x MTR**
- Length: 5 m
 - Width: 16 mm
 - Colour: Yellow
 - Material: Nylon 66
 - Type: Hook and Loop



1797179 5 m

RS PRO CABLE TIE, HOOK AND LOOP, 5M X 16 MM, BLUE NYLON

- ขนาดบรรจุภัณฑ์: **5 x MTR**
- Length: 5 m
 - Width: 16 mm
 - Colour: Blue
 - Material: Nylon 66
 - Type: Hook and Loop



1797180 5 m

RS PRO CABLE TIE, HOOK AND LOOP, 5M X 16 MM, WHITE NYLON

- ขนาดบรรจุภัณฑ์: **5 x MTR**
- Length: 5 m
 - Width: 16 mm
 - Colour: White
 - Material: Nylon 66
 - Type: Hook and Loop



1797181 5 m

RS PRO CABLE TIE, HOOK AND LOOP, 310MM X 20 MM, BLACK NYLON, PK-

- ขนาดบรรจุภัณฑ์: **5 x MTR**
- Length: 310 mm
 - Width: 20 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Hook and Loop
 - Quantity: 10



1797182 310 mm

RS PRO CABLE TIE, HOOK AND LOOP, 310MM X 20 MM, RED NYLON, PK-10

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Length: 310 mm
 - Width: 20 mm
 - Colour: Red
 - Material: Nylon 66
 - Type: Hook and Loop
 - Quantity: 10



1797183 310 mm

RS PRO CABLE TIE, HOOK AND LOOP, 300MM X 20 MM, YELLOW NYLON,

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Length: 300 mm
 - Width: 20 mm
 - Colour: Yellow
 - Material: Nylon 66
 - Type: Hook and Loop
 - Quantity: 10



1797184 300 mm

RS PRO CABLE TIE, HOOK AND LOOP, 300MM X 20 MM, GREEN NYLON, PK-

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Length: 300 mm
 - Width: 20 mm
 - Colour: Green
 - Material: Nylon 66
 - Type: Hook and Loop
 - Quantity: 10



1797185 300 mm

RS PRO CABLE TIE, HOOK AND LOOP, 300MM X 20 MM, BLUE NYLON, PK-10

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Length: 300 mm
 - Width: 20 mm
 - Colour: Blue
 - Material: Nylon 66
 - Type: Hook and Loop
 - Quantity: 10



1797186 300 mm

RS PRO CABLE TIE, HOOK AND LOOP, 310MM X 20 MM, WHITE NYLON, PK-

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Length: 310 mm
 - Width: 20 mm
 - Colour: White
 - Material: Nylon 66
 - Type: Hook and Loop
 - Quantity: 10



1797187 310 mm

RS PRO CABLE TIE, HOOK AND LOOP, 50MM X 20 MM, BLACK NYLON, PK-10

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Length: 50 mm
 - Width: 20 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Hook and Loop
 - Quantity: 10



1797188 50 mm

RS PRO CABLE TIE, 100MM X 4.6 MM, BLACK 316 STAINLESS STEEL

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 100 mm
 - Width: 4.6 mm
 - Colour: Black
 - Material: 316 Stainless Steel
 - UV Resistant: Yes
 - Minimum Operating Temperature: -80 °C
 - Maximum Operating Temperature: +150 °C
 - Fire Behaviour: Halogen Free



1834158 100 mm

RS PRO CABLE TIE, 360MM X 4.6 MM, BLACK 316 STAINLESS STEEL

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 360 mm
 - Width: 4.6 mm
 - Colour: Black
 - Material: 316 Stainless Steel
 - UV Resistant: Yes
 - Minimum Operating Temperature: -80 °C
 - Maximum Operating Temperature: +150 °C
 - Fire Behaviour: Halogen Free



1834160 360 mm

RS PRO CABLE TIE, ZIG ZAG, 100MM X 4.6 MM 316 STAINLESS STEEL

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 100 mm
 - Width: 4.6 mm
 - Material: 316 Stainless Steel
 - Type: Zig Zag
 - UV Resistant: Yes
 - Minimum Operating Temperature: -80 °C
 - Maximum Operating Temperature: +500 °C
 - Fire Behaviour: Fire Resistant



1834162 100 mm

RS PRO CABLE TIE, ZIG ZAG, 150MM X 4.6 MM 316 STAINLESS STEEL

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 150 mm
 - Width: 4.6 mm
 - Material: 316 Stainless Steel
 - Type: Zig Zag
 - UV Resistant: Yes
 - Minimum Operating Temperature: -80 °C
 - Maximum Operating Temperature: +500 °C
 - Fire Behaviour: Fire Resistant



1834165 150 mm

RS PRO CABLE TIE, LADDER SINGLE LOCK, 300MM X 7 MM, BLACK 316

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 300 mm
 - Width: 7 mm
 - Colour: Black
 - Material: 316 Stainless Steel
 - Type: Ladder Single Lock
 - Quantity: 100
 - UV Resistant: Yes
 - Minimum Operating Temperature: -80 °C



1834173 300 mm

RS PRO CABLE TIE, LADDER SINGLE LOCK, 225MM X 7 MM 316 STAINLESS

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 225 mm
 - Width: 7 mm
 - Material: 316 Stainless Steel
 - Type: Ladder Single Lock
 - Quantity: 100
 - UV Resistant: Yes
 - Minimum Operating Temperature: -80 °C
 - Maximum Operating Temperature: +500 °C



1834175 225 mm

RS PRO CABLE TIE, LADDER SINGLE LOCK, 610MM X 7 MM 316 STAINLESS

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 610 mm
 - Width: 7 mm
 - Material: 316 Stainless Steel
 - Type: Ladder Single Lock
 - Quantity: 100
 - UV Resistant: Yes
 - Minimum Operating Temperature: -80 °C
 - Maximum Operating Temperature: +500 °C



1834177 610 mm

RS PRO CABLE TIE, LADDER SINGLE LOCK, 610MM X 12 MM 316 STAINLESS

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 610 mm
 - Width: 12 mm
 - Material: 316 Stainless Steel
 - Type: Ladder Single Lock
 - Quantity: 100
 - UV Resistant: Yes
 - Minimum Operating Temperature: -80 °C
 - Maximum Operating Temperature: +500 °C



1834178 610 mm

RS PRO CABLE TIE, RELEASABLE, 330MM X 10 MM, BLACK 316

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 330 mm
 - Width: 10 mm
 - Colour: Black
 - Material: 316 Stainless Steel
 - Type: Releasable
 - UV Resistant: Yes
 - Minimum Operating Temperature: -80 °C
 - Maximum Operating Temperature: +150 °C



1834183 330 mm

RS PRO CABLE TIE, BALL LOCK, 360MM X 4.6 MM 304 STAINLESS

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 360 mm
 - Width: 4.6 mm
 - Material: 304 Stainless Steel
 - Type: Ball Lock
 - UV Resistant: Yes
 - Minimum Operating Temperature: -80 °C
 - Maximum Operating Temperature: +500 °C
 - Tensile Strength: 1100 N



1834225 360 mm

RS PRO CABLE TIE, BALL LOCK, 200MM X 4.6 MM, BLACK 316

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 200 mm
 - Width: 4.6 mm
 - Colour: Black
 - Material: 316 Stainless Steel
 - Type: Ball Lock
 - UV Resistant: Yes
 - Minimum Operating Temperature: -80 °C
 - Maximum Operating Temperature: +150 °C



1834254 200 mm

RS PRO CABLE TIE, BALL LOCK, 520MM X 4.6 MM, BLACK 316

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 520 mm
 - Width: 4.6 mm
 - Colour: Black
 - Material: 316 Stainless Steel
 - Type: Ball Lock
 - UV Resistant: Yes
 - Minimum Operating Temperature: -80 °C
 - Maximum Operating Temperature: +150 °C



1834256 520 mm

RS PRO CABLE TIE, BALL LOCK, 360MM X 7.9 MM, BLACK 316


- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 360 mm
 - Width: 7.9 mm
 - Colour: Black
 - Material: 316 Stainless Steel
 - Type: Ball Lock
 - UV Resistant: Yes
 - Minimum Operating Temperature: -80 °C
 - Maximum Operating Temperature: +150 °C



1834261 360 mm

RS PRO CABLE TIE, BALL LOCK, 1.2M X 12 MM, BLACK 316 STAINLESS STEEL

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 1.2 m
 - Width: 12 mm
 - Colour: Black
 - Material: 316 Stainless Steel
 - Type: Ball Lock
 - UV Resistant: Yes
 - Minimum Operating Temperature: -80 °C
 - Maximum Operating Temperature: +150 °C



1834269 1.2 m

RS PRO CABLE TIE, RELEASABLE, 230MM X 5 MM, BLACK POLYESTER

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 230 mm
 - Width: 5 mm
 - Colour: Black
 - Material: Polyester Coated Stainless Steel
 - Type: Releasable
 - Quantity: 100
 - Minimum Operating Temperature: -80 °C
 - Maximum Operating Temperature: +150 °C



1858670 230 mm

RS PRO CABLE TIE, RELEASABLE, 330MM X 10 MM, BLACK 316

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 330 mm
 - Width: 10 mm
 - Colour: Black
 - Material: 316 Stainless Steel
 - Type: Releasable
 - Quantity: 100
 - UV Resistant: Yes
 - Minimum Operating Temperature: -80 °C



1859364 330 mm

RS PRO CABLE TIE, 368MM X 4.8 MM, BLACK NYLON, PK-100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 368 mm
 - Width: 4.8 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Non-Releasable
 - Quantity: 100
 - UV Resistant: Yes
 - Minimum Operating Temperature: -40 °C



2012389 368 mm

RS PRO CABLE TIE KIT, 203MM X 3.6 MM, BLACK NYLON, PK-100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 203 mm
 - Width: 3.6 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Non-Releasable
 - Quantity: 100
 - UV Resistant: Yes
 - Minimum Operating Temperature: -40 °C



2012390 203 mm

RS PRO CABLE TIE KIT, BLACK PA66MP

- ขนาดบรรจุภัณฑ์: **1 x KT**
- Colour: Black
 - Material: PA66MP
 - Fire Behaviour: Self-extinguishing



2013590 Black

RS PRO CABLE TIE, HEAT RESISTANT, NON-RELEASABLE, 100MM X 2.5 MM,

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 100 mm
 - Width: 2.5 mm
 - Colour: Natural
 - Material: PA 4.6
 - Type: Heat Resistant, Non-Releasable
 - Maximum Operating Temperature: +150 °C
 - Fire Behaviour: Halogen Free
 - Tensile Strength: 18 lb



2066625 100 mm

RS PRO CABLE TIE, HEAT RESISTANT, NON-RELEASABLE, 203MM X 4.6 MM,

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 203 mm
 - Width: 4.6 mm
 - Colour: Natural
 - Material: PA 4.6
 - Type: Heat Resistant, Non-Releasable
 - Maximum Operating Temperature: +150 °C
 - Fire Behaviour: Halogen Free
 - Tensile Strength: 50 lb



2066627 203 mm

RS PRO CABLE TIE, HEAT RESISTANT, NON-RELEASABLE, 385MM X 4.8 MM,

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 385 mm
 - Width: 4.8 mm
 - Colour: Natural
 - Material: PA 4.6
 - Type: Heat Resistant, Non-Releasable
 - Maximum Operating Temperature: +150 °C
 - Fire Behaviour: Halogen Free
 - Tensile Strength: 50 lb



2066628 385 mm

RS PRO CABLE TIE, 102MM X 2.4 MM, BLACK NYLON, PK-100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 102 mm
 - Width: 2.4 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Non-Releasable
 - Quantity: 100
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



2098130 102 mm

RS PRO CABLE TIE, 155MM X 3.6 MM, BLACK NYLON, PK-100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 155 mm
 - Width: 3.6 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Non-Releasable
 - Quantity: 100
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



2098131 155 mm

RS PRO CABLE TIE, 186MM X 4.8 MM, BLACK NYLON, PK-100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 186 mm
 - Width: 4.8 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Non-Releasable
 - Quantity: 100
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



2098132 186 mm

RS PRO CABLE TIE, 284MM X 3.6 MM, BLACK NYLON, PK-100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 284 mm
 - Width: 3.6 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Non-Releasable
 - Quantity: 100
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



2098133 284 mm

RS PRO CABLE TIE, 284MM X 3.6 MM, BLACK NYLON, PK-100

- ขนาดบรรจุภัณฑ์: **1000 x EA**
- Length: 284 mm
 - Width: 3.6 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 100
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



2098134 284 mm

RS PRO CABLE TIE, 350MM X 8 MM, BLACK NYLON, PK-100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 350 mm
 - Width: 8 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 100
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



2098135 350 mm

RS PRO CABLE TIE, 350MM X 8 MM, BLACK NYLON, PK-100

- ขนาดบรรจุภัณฑ์: **500 x EA**
- Length: 350 mm
 - Width: 8 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 100
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



2098136 350 mm

RS PRO CABLE TIE, 361MM X 4.8 MM, BLACK NYLON, PK-100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 361 mm
 - Width: 4.8 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 100
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



2098137 361 mm

RS PRO CABLE TIE, 203MM X 3.6 MM, NATURAL NYLON

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 203 mm
 - Width: 3.6 mm
 - Colour: Natural
 - Material: Nylon 66
 - Type: Non-Releaseable
 - UV Resistant: No
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



2132982 203 mm

RS PRO CABLE TIE, 203MM X 3.6 MM, NATURAL NYLON

- ขนาดบรรจุภัณฑ์: **1000 x EA**
- Length: 203 mm
 - Width: 3.6 mm
 - Colour: Natural
 - Material: Nylon 66
 - Type: Non-Releaseable
 - UV Resistant: No
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



2132983 203 mm

RS PRO CABLE TIE, 203MM X 3.5 MM, NATURAL NYLON

- ขนาดบรรจุภัณฑ์: **1000 x EA**
- Length: 203 mm
 - Width: 3.5 mm
 - Colour: Natural
 - Material: Nylon 66
 - Type: Non-Releaseable
 - UV Resistant: No
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



2132984 203 mm

RS PRO CABLE TIE, 250MM X 4.8 MM, NATURAL NYLON

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 250 mm
 - Width: 4.8 mm
 - Colour: Natural
 - Material: Nylon 66
 - Type: Non-Releaseable
 - UV Resistant: No
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



2132986 250 mm

RS PRO CABLE TIE, 250MM X 4.8 MM, NATURAL NYLON

- ขนาดบรรจุภัณฑ์: **1000 x EA**
- Length: 250 mm
 - Width: 4.8 mm
 - Colour: Natural
 - Material: Nylon 66
 - Type: Non-Releaseable
 - UV Resistant: No
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



2132987 250 mm

RS PRO CABLE TIE, 368MM X 3.6 MM, NATURAL NYLON

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 368 mm
 - Width: 3.6 mm
 - Colour: Natural
 - Material: Nylon 66
 - Type: Non-Releaseable
 - UV Resistant: No
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



2132989 368 mm

RS PRO CABLE TIE, 450MM X 8 MM, BLACK NYLON

- ขนาดบรรจุภัณฑ์: **50 x EA**
- Length: 450 mm
 - Width: 8 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Non-Releaseable
 - UV Resistant: No
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



2132990 450 mm

RS PRO CABLE TIE, 142MM X 3.2 MM, BLACK NYLON

- ขนาดบรรจุภัณฑ์: **1000 x EA**
- Length: 142 mm
 - Width: 3.2 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Non-Releaseable
 - UV Resistant: Yes
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



2132992 142 mm

RS PRO CABLE TIE, 165MM X 2.5 MM, BLACK NYLON

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 165 mm
 - Width: 2.5 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Non-Releaseable
 - UV Resistant: Yes
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



2132993 165 mm

RS PRO CABLE TIE, 190MM X 4.8 MM, BLACK NYLON

- ขนาดบรรจุภัณฑ์: **1000 x EA**
- Length: 190 mm
 - Width: 4.8 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Non-Releaseable
 - UV Resistant: Yes
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



2132994 190 mm

RS PRO CABLE TIE, 230MM X 2.5 MM, BLACK NYLON

- ขนาดบรรจุภัณฑ์: **1000 x EA**
- Length: 230 mm
 - Width: 2.5 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Non-Releaseable
 - UV Resistant: Yes
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



2132995 230 mm

RS PRO CABLE TIE, 230MM X 2.5 MM, BLACK NYLON

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 230 mm
 - Width: 2.5 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Non-Releaseable
 - UV Resistant: Yes
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



2132996 230 mm

RS PRO CABLE TIE, 250MM X 4.8 MM, BLACK NYLON

- ขนาดบรรจุภัณฑ์: **1000 x EA**
- Length: 250 mm
 - Width: 4.8 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Non-Releaseable
 - UV Resistant: Yes
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



2132997 250 mm

RS PRO CABLE TIE, 292MM X 3.6 MM, BLACK NYLON

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 292 mm
 - Width: 3.6 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Non-Releaseable
 - UV Resistant: Yes
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



2132999 292 mm

RS PRO CABLE TIE, 368MM X 3.6 MM, BLACK NYLON

- ขนาดบรรจุภัณฑ์: **1000 x EA**
- Length: 368 mm
 - Width: 3.6 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Non-Releaseable
 - UV Resistant: Yes
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



2133000 368 mm

RS PRO CABLE TIE, 450MM X 8 MM, BLACK NYLON

- ขนาดบรรจุภัณฑ์: **50 x EA**
- Length: 450 mm
 - Width: 8 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Non-Releaseable
 - UV Resistant: Yes
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



2133002 450 mm

RS PRO CABLE TIE, DOUBLE HEADED, 500MM X 12.7 MM, BLACK NYLON

- ขนาดบรรจุภัณฑ์: **50 x EA**
- Length: 500 mm
 - Width: 12.7 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Double Headed
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C
 - Fire Behaviour: Self-extinguishing



2133018 500 mm

RS PRO CABLE TIE, DOUBLE HEADED, 900MM X 8 MM, BLUE NYLON, PK-50

- ขนาดบรรจุภัณฑ์: **50 x EA**
- Length: 900 mm
 - Width: 8 mm
 - Colour: Blue
 - Material: Nylon 66
 - Type: Double Headed
 - Quantity: 50
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +80 °C



2133019 900 mm

RS PRO CABLE TIE, 100MM X 2.5 MM→4.8 MM, NATURAL NYLON, PK-

- ขนาดบรรจุภัณฑ์: **1 x KT**
- Length: 100 mm→385 mm
 - Width: 2.5 mm→4.8 mm
 - Colour: Natural
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 2500
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



2206253 100 mm→385 mm

RS PRO CABLE TIE, 100MM X 2.5 MM→4.8 MM, BLACK NYLON, PK-2500

- ขนาดบรรจุภัณฑ์: **1 x KT**
- Length: 100 mm→385 mm
 - Width: 2.5 mm→4.8 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 2500
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



2206254 100 mm→385 mm

RS PRO CABLE TIE, 350MM X 12 MM, BLACK 316 STAINLESS STEEL, PK-100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 350 mm
 - Width: 12 mm
 - Colour: Black
 - Material: 316 Stainless Steel
 - Type: Non-Releaseable
 - Quantity: 100
 - UV Resistant: Yes
 - Minimum Operating Temperature: -40 °C



2242227 350 mm

RS PRO CABLE TIE, 450MM X 12 MM, BLACK 316 STAINLESS STEEL, PK-100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 450 mm
 - Width: 12 mm
 - Colour: Black
 - Material: 316 Stainless Steel
 - Type: Non-Releaseable
 - Quantity: 100
 - UV Resistant: Yes
 - Minimum Operating Temperature: -40 °C



2242229 450 mm

RS PRO CABLE TIE, 550MM X 12 MM, BLACK 316 STAINLESS STEEL, PK-100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 550 mm
 - Width: 12 mm
 - Colour: Black
 - Material: 316 Stainless Steel
 - Type: Non-Releaseable
 - Quantity: 100
 - UV Resistant: Yes
 - Minimum Operating Temperature: -40 °C



2242230 550 mm

RS PRO CABLE TIE, 150MM X 4.6 MM, BLACK 316 STAINLESS STEEL, PK-100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 150 mm
 - Width: 4.6 mm
 - Colour: Black
 - Material: 316 Stainless Steel
 - Type: Non-Releaseable
 - Quantity: 100
 - UV Resistant: Yes
 - Minimum Operating Temperature: -40 °C



2242232 150 mm

RS PRO CABLE TIE, 200MM X 4.6 MM, BLACK 316 STAINLESS STEEL, PK-100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 200 mm
 - Width: 4.6 mm
 - Colour: Black
 - Material: 316 Stainless Steel
 - Type: Non-Releaseable
 - Quantity: 100
 - UV Resistant: Yes
 - Minimum Operating Temperature: -40 °C



2242233 200 mm

RS PRO CABLE TIE, 350MM X 4.6 MM, BLACK 316 STAINLESS STEEL, PK-100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 350 mm
 - Width: 4.6 mm
 - Colour: Black
 - Material: 316 Stainless Steel
 - Type: Non-Releaseable
 - Quantity: 100
 - UV Resistant: Yes
 - Minimum Operating Temperature: -40 °C



2242235 350 mm

RS PRO CABLE TIE, 450MM X 4.6 MM, BLACK 316 STAINLESS STEEL, PK-100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 450 mm
 - Width: 4.6 mm
 - Colour: Black
 - Material: 316 Stainless Steel
 - Type: Non-Releaseable
 - Quantity: 100
 - UV Resistant: Yes
 - Minimum Operating Temperature: -40 °C



2242236 450 mm

RS PRO CABLE TIE, 650MM X 4.6 MM, BLACK 316 STAINLESS STEEL, PK-100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 650 mm
 - Width: 4.6 mm
 - Colour: Black
 - Material: 316 Stainless Steel
 - Type: Non-Releaseable
 - Quantity: 100
 - UV Resistant: Yes
 - Minimum Operating Temperature: -40 °C



2242238 650 mm

RS PRO CABLE TIE, 1M X 8 MM, BLACK 316 STAINLESS STEEL, PK-100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 1 m
 - Width: 8 mm
 - Colour: Black
 - Material: 316 Stainless Steel
 - Type: Non-Releaseable
 - Quantity: 100
 - UV Resistant: Yes
 - Minimum Operating Temperature: -40 °C



2242241 1 m

RS PRO CABLE TIE, 350MM X 8 MM, BLACK 316 STAINLESS STEEL, PK-100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 350 mm
 - Width: 8 mm
 - Colour: Black
 - Material: 316 Stainless Steel
 - Type: Non-Releaseable
 - Quantity: 100
 - UV Resistant: Yes
 - Minimum Operating Temperature: -40 °C



2242243 350 mm

RS PRO CABLE TIE, 450MM X 8 MM, BLACK 316 STAINLESS STEEL, PK-100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 450 mm
 - Width: 8 mm
 - Colour: Black
 - Material: 316 Stainless Steel
 - Type: Non-Releaseable
 - Quantity: 100
 - UV Resistant: Yes
 - Minimum Operating Temperature: -40 °C



2242244 450 mm

RS PRO CABLE TIE, 650MM X 8 MM, BLACK 316 STAINLESS STEEL, PK-100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 650 mm
 - Width: 8 mm
 - Colour: Black
 - Material: 316 Stainless Steel
 - Type: Non-Releaseable
 - Quantity: 100
 - UV Resistant: Yes
 - Minimum Operating Temperature: -40 °C



2242246 650 mm

RS PRO CABLE TIE, 100 MM, 150 MM, 203 MM X 2.5 MM, 3.6 MM, 4.6 MM,

- ขนาดบรรจุภัณฑ์: **500 x EA**
- Length: 100 mm, 150 mm, 203 mm
 - Width: 2.5 mm, 3.6 mm, 4.6 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Non-Releaseable
 - UV Resistant: No
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



2243112 100 mm, 150 mm,

RS PRO CABLE TIE, 1.168M X 9 MM, NATURAL NYLON

- ขนาดบรรจุภัณฑ์: **50 x EA**
- Length: 1.168 m
 - Width: 9 mm
 - Colour: Natural
 - Material: Nylon 66
 - Type: Non-Releaseable
 - UV Resistant: No
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



2243117 1.168 m

RS PRO CABLE TIE, 1.168M X 9 MM, BLACK NYLON

- ขนาดบรรจุภัณฑ์: **50 x EA**
- Length: 1.168 m
 - Width: 9 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Non-Releaseable
 - UV Resistant: No
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



2243119 1.168 m

RS PRO CABLE TIE, 150MM X 3.6 MM, GREEN NYLON

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 150 mm
 - Width: 3.6 mm
 - Colour: Green
 - Material: Nylon 66
 - Type: Non-Releaseable
 - UV Resistant: No
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



2243122 150 mm

RS PRO CABLE TIE, 150MM X 3.6 MM, RED NYLON

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 150 mm
 - Width: 3.6 mm
 - Colour: Red
 - Material: Nylon 66
 - Type: Non-Releaseable
 - UV Resistant: No
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



2243123 150 mm

RS PRO CABLE TIE, 150MM X 3.6 MM, BLACK NYLON

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 150 mm
 - Width: 3.6 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Non-Releaseable
 - UV Resistant: Yes
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



2243124 150 mm

RS PRO CABLE TIE, 203MM X 4.6 MM, NATURAL NYLON

- ขนาดบรรจุภัณฑ์: **500 x EA**
- Length: 203 mm
 - Width: 4.6 mm
 - Colour: Natural
 - Material: Nylon 66
 - Type: Non-Releaseable
 - UV Resistant: No
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



2243126 203 mm

RS PRO CABLE TIE, 203MM X 4.6 MM, BLUE NYLON

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 203 mm
 - Width: 4.6 mm
 - Colour: Blue
 - Material: Nylon 66
 - Type: Non-Releaseable
 - UV Resistant: No
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



2243127 203 mm

RS PRO CABLE TIE, 203MM X 4.6 MM, GREEN NYLON

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 203 mm
 - Width: 4.6 mm
 - Colour: Green
 - Material: Nylon 66
 - Type: Non-Releaseable
 - UV Resistant: No
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



2243128 203 mm

RS PRO CABLE TIE, 203MM X 4.6 MM, ORANGE NYLON

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 203 mm
 - Width: 4.6 mm
 - Colour: Orange
 - Material: Nylon 66
 - Type: Non-Releaseable
 - UV Resistant: No
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



2243130 203 mm

RS PRO CABLE TIE, 203MM X 4.6 MM, RED NYLON

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 203 mm
 - Width: 4.6 mm
 - Colour: Red
 - Material: Nylon 66
 - Type: Non-Releaseable
 - UV Resistant: No
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



2243131 203 mm

RS PRO CABLE TIE, 203MM X 4.6 MM, YELLOW NYLON

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 203 mm
 - Width: 4.6 mm
 - Colour: Yellow
 - Material: Nylon 66
 - Type: Non-Releaseable
 - UV Resistant: No
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



2243133 203 mm

RS PRO CABLE TIE, 250MM X 2.5 MM, NATURAL NYLON

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 250 mm
 - Width: 2.5 mm
 - Colour: Natural
 - Material: Nylon 66
 - Type: Non-Releaseable
 - UV Resistant: No
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



2243134 250 mm

RS PRO CABLE TIE, 280MM X 4.8 MM, BLUE NYLON

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 280 mm
 - Width: 4.8 mm
 - Colour: Blue
 - Material: Nylon 66
 - Type: Non-Releaseable
 - UV Resistant: No
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



2243138 280 mm

RS PRO CABLE TIE, 280MM X 4.8 MM, BLACK NYLON

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 280 mm
 - Width: 4.8 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Non-Releaseable
 - UV Resistant: No
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



2243139 280 mm

RS PRO CABLE TIE, 280MM X 4.8 MM, BLACK NYLON

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 280 mm
 - Width: 4.8 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Non-Releaseable
 - UV Resistant: Yes
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



2243141 280 mm

RS PRO CABLE TIE, 280MM X 4.8 MM, YELLOW NYLON

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 280 mm
 - Width: 4.8 mm
 - Colour: Yellow
 - Material: Nylon 66
 - Type: Non-Releaseable
 - UV Resistant: No
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



2243143 280 mm

RS PRO CABLE TIE, 300MM X 4.8 MM, NATURAL

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 300 mm
 - Width: 4.8 mm
 - Colour: Natural
 - Type: Non-Releaseable
 - UV Resistant: No
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +150 °C
 - Fire Behaviour: Self-extinguishing



2243146 300 mm

RS PRO CABLE TIE, 360MM X 7.6 MM, BLACK NYLON

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 360 mm
 - Width: 7.6 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Non-Releaseable
 - UV Resistant: Yes
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



2243147 360 mm

RS PRO CABLE TIE, 368MM X 4.8 MM NYLON

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 368 mm
 - Width: 4.8 mm
 - Material: Nylon 66
 - Type: Non-Releaseable
 - UV Resistant: No
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +105 °C
 - Fire Behaviour: Self-extinguishing



2243148 368 mm

RS PRO CABLE TIE, 368MM X 4.8 MM, WHITE NYLON

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 368 mm
 - Width: 4.8 mm
 - Colour: White
 - Material: Nylon 66
 - Type: Non-Releaseable
 - UV Resistant: No
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



2243149 368 mm

RS PRO CABLE TIE, 380MM X 7.6 MM, BLUE NYLON

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 380 mm
 - Width: 7.6 mm
 - Colour: Blue
 - Material: Nylon 66
 - Type: Non-Releaseable
 - UV Resistant: No
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



2243151 380 mm

RS PRO CABLE TIE, 380MM X 7.6 MM, NATURAL NYLON

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 380 mm
 - Width: 7.6 mm
 - Colour: Natural
 - Material: Nylon 66
 - Type: Non-Releaseable
 - UV Resistant: No
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +150 °C



2243154 380 mm

RS PRO CABLE TIE, 380MM X 7.6 MM, RED NYLON

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 380 mm
 - Width: 7.6 mm
 - Colour: Red
 - Material: Nylon 66
 - Type: Non-Releaseable
 - UV Resistant: No
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



2243155 380 mm

RS PRO CABLE TIE, 385MM X 4.8 MM, BLACK NYLON

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 385 mm
 - Width: 4.8 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Non-Releaseable
 - UV Resistant: No
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



2243161 385 mm

RS PRO CABLE TIE, 385MM X 4.8 MM, RED NYLON

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 385 mm
 - Width: 4.8 mm
 - Colour: Red
 - Material: Nylon 66
 - Type: Non-Releaseable
 - UV Resistant: No
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



2243166 385 mm

RS PRO CABLE TIE, 450MM X 8 MM, BLACK NYLON

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 450 mm
 - Width: 8 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Non-Releaseable
 - UV Resistant: No
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +105 °C



2243168 450 mm

RS PRO CABLE TIE, 450MM X 4.8 MM, BLACK NYLON

- ขนาดบรรจุภัณฑ์: **500 x EA**
- Length: 450 mm
 - Width: 4.8 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Non-Releaseable
 - UV Resistant: No
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



2243169 450 mm

RS PRO CABLE TIE, 610MM X 7.6 MM, NATURAL NYLON

- ขนาดบรรจุภัณฑ์: **50 x EA**
- Length: 610 mm
 - Width: 7.6 mm
 - Colour: Natural
 - Material: Nylon 66
 - Type: Non-Releasable
 - UV Resistant: No
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



2243171 610 mm

RS PRO CABLE TIE, 610MM X 7.6 MM, BLACK NYLON

- ขนาดบรรจุภัณฑ์: **50 x EA**
- Length: 610 mm
 - Width: 7.6 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Non-Releasable
 - UV Resistant: No
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



2243172 610 mm

RS PRO CABLE TIE, 610MM X 7.6 MM, BLACK NYLON

- ขนาดบรรจุภัณฑ์: **50 x EA**
- Length: 610 mm
 - Width: 7.6 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Non-Releasable
 - UV Resistant: No
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



2243173 610 mm

RS PRO CABLE TIE, 940MM X 9 MM, BLACK NYLON

- ขนาดบรรจุภัณฑ์: **25 x EA**
- Length: 940 mm
 - Width: 9 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Non-Releasable
 - UV Resistant: No
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



2243174 940 mm

RS PRO CABLE TIE, 370MM X 4.8 MM, BLACK NYLON

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 370 mm
 - Width: 4.8 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Non-Releasable
 - UV Resistant: No
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



2243175 370 mm

RS PRO CABLE TIE, RELEASABLE, 200MM X 7.6 MM, BLACK NYLON

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 200 mm
 - Width: 7.6 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Releasable
 - UV Resistant: No
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



2243180 200 mm

RS PRO CABLE TIE, 250MM X 7.6 MM, BLACK NYLON

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 250 mm
 - Width: 7.6 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Non-Releasable
 - UV Resistant: Yes
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



2243181 250 mm

RS PRO CABLE TIE, 112MM X 2.5 MM, NATURAL NYLON

- ขนาดบรรจุภัณฑ์: **25 x EA**
- Length: 112 mm
 - Width: 2.5 mm
 - Colour: Natural
 - Material: Nylon 66
 - Type: Non-Releasable
 - UV Resistant: No
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



2243189 112 mm

RS PRO CABLE TIE, 200MM X 4.6 MM, RED NYLON

- ขนาดบรรจุภัณฑ์: **25 x EA**
- Length: 200 mm
 - Width: 4.6 mm
 - Colour: Red
 - Material: Nylon 66
 - Type: Non-Releasable
 - UV Resistant: No
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



2243194 200 mm

RS PRO CABLE TIE, 200MM X 4.6 MM, YELLOW NYLON

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 200 mm
 - Width: 4.6 mm
 - Colour: Yellow
 - Material: Nylon 66
 - Type: Non-Releasable
 - UV Resistant: No
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



2243195 200 mm

RS PRO CABLE TIE, 300MM X 4.8 MM, NATURAL NYLON

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 300 mm
 - Width: 4.8 mm
 - Colour: Natural
 - Material: Nylon 66
 - Type: Non-Releasable
 - UV Resistant: No
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



2243196 300 mm

RS PRO CABLE TIE, 370MM X 4.8 MM, NATURAL NYLON

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 370 mm
 - Width: 4.8 mm
 - Colour: Natural
 - Material: Nylon 66
 - Type: Non-Releasable
 - UV Resistant: No
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



2243197 370 mm

RS PRO CABLE TIE, 150MM X 2.9 MM, NATURAL NYLON

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 150 mm
 - Width: 2.9 mm
 - Colour: Natural
 - Material: Nylon 66
 - Type: Non-Releasable
 - UV Resistant: No
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



2243199 150 mm

RS PRO CABLE TIE, HOOK AND LOOP, 150MM X 20 MM, BLACK FABRIC

- ขนาดบรรจุภัณฑ์: **25 x EA**
- Length: 150 mm
 - Width: 20 mm
 - Colour: Black
 - Material: Fabric
 - Type: Hook and Loop



2854562 150 mm

RS PRO CABLE TIE, HOOK AND LOOP, 203.5MM X 12 MM, BLACK FABRIC

- ขนาดบรรจุภัณฑ์: **25 x EA**
- Length: 203.5 mm
 - Width: 12 mm
 - Colour: Black
 - Material: Fabric
 - Type: Hook and Loop



2854578 203.5 mm

RS PRO CABLE TIE, HOOK AND LOOP, 305MM X 12 MM, BLACK FABRIC

- ขนาดบรรจุภัณฑ์: **25 x EA**
- Length: 305 mm
 - Width: 12 mm
 - Colour: Black
 - Material: Fabric
 - Type: Hook and Loop



2854584 305 mm

RICHCO CABLE TIE, STANDARD, 150MM X 3.6 MM, NATURAL NYLON,

- ขนาดบรรจุภัณฑ์: 100 x EA
- Length: 150 mm
 - Width: 3.6 mm
 - Colour: Natural
 - Material: Nylon 66
 - Type: Standard
 - Quantity: 100
 - Minimum Operating Temperature: -50 °C
 - Maximum Operating Temperature: +120 °C



3210092 150 mm

RICHCO CABLE TIE, RELEASABLE, 152.4MM X 2.4 MM, BLUE

- ขนาดบรรจุภัณฑ์: 100 x EA
- Length: 152.4 mm
 - Width: 2.4 mm
 - Colour: Blue
 - Material: Polypropylene
 - Type: Releasable
 - Quantity: 100
 - Series: BT
 - Maximum Bundle Diameter: 44.5 mm



3212543 152.4 mm

RS PRO CABLE TIE, 203MM X 4.6 MM, NATURAL NYLON, PK-100

- ขนาดบรรจุภัณฑ์: 100 x EA
- Length: 203 mm
 - Width: 4.6 mm
 - Colour: Natural
 - Material: Nylon 66
 - Type: Non-Releasable
 - Quantity: 100
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



4892140 203 mm

RS PRO CABLE TIE, 300MM X 4.8 MM, NATURAL NYLON, PK-100

- ขนาดบรรจุภัณฑ์: 100 x EA
- Length: 300 mm
 - Width: 4.8 mm
 - Colour: Natural
 - Material: Nylon 66
 - Type: Non-Releasable
 - Quantity: 100
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



4892156 300 mm

RS PRO CABLE TIE, 100MM X 2.5 MM, NATURAL NYLON, PK-1000

- ขนาดบรรจุภัณฑ์: 1000 x EA
- Length: 100 mm
 - Width: 2.5 mm
 - Colour: Natural
 - Material: Nylon 66
 - Type: Non-Releasable
 - Quantity: 1000
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



4920447 100 mm

RS PRO CABLE TIE, 150MM X 3.6 MM, NATURAL NYLON, PK-1000

- ขนาดบรรจุภัณฑ์: 1000 x EA
- Length: 150 mm
 - Width: 3.6 mm
 - Colour: Natural
 - Material: Nylon 66
 - Type: Non-Releasable
 - Quantity: 1000
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



4920453 150 mm

RS PRO CABLE TIE, 190MM X 4.8 MM, NATURAL NYLON, PK-1000

- ขนาดบรรจุภัณฑ์: 1000 x EA
- Length: 190 mm
 - Width: 4.8 mm
 - Colour: Natural
 - Material: Nylon 66
 - Type: Non-Releasable
 - Quantity: 1000
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



4920469 190 mm

RS PRO CABLE TIE, ROLLER BALL, 520MM X 4.6 MM, METALLIC 316

- ขนาดบรรจุภัณฑ์: 100 x EA
- Length: 520 mm
 - Width: 4.6 mm
 - Colour: Metallic
 - Material: 316 Stainless Steel
 - Type: Roller Ball
 - Quantity: 100
 - Minimum Operating Temperature: -80 °C
 - Maximum Operating Temperature: +538 °C



5474305 520 mm

RS PRO CABLE TIE, ROLLER BALL, 520MM X 7.9 MM, METALLIC 316

- ขนาดบรรจุภัณฑ์: 100 x EA
- Length: 520 mm
 - Width: 7.9 mm
 - Colour: Metallic
 - Material: 316 Stainless Steel
 - Type: Roller Ball
 - Quantity: 100
 - Minimum Operating Temperature: -80 °C
 - Maximum Operating Temperature: +538 °C



5474311 520 mm

RS PRO CABLE TIE, ROLLER BALL, 200MM X 4.6 MM, BLACK POLYESTER

- ขนาดบรรจุภัณฑ์: 100 x EA
- Length: 200 mm
 - Width: 4.6 mm
 - Colour: Black
 - Material: Polyester Coated Stainless Steel
 - Type: Roller Ball
 - Quantity: 100
 - Minimum Operating Temperature: -80 °C
 - Maximum Operating Temperature: +150 °C



5474327 200 mm

RS PRO CABLE TIE, ROLLER BALL, 360MM X 4.6 MM, BLACK POLYESTER

- ขนาดบรรจุภัณฑ์: 100 x EA
- Length: 360 mm
 - Width: 4.6 mm
 - Colour: Black
 - Material: Polyester Coated Stainless Steel
 - Type: Roller Ball
 - Quantity: 100
 - Minimum Operating Temperature: -80 °C
 - Maximum Operating Temperature: +150 °C



5474333 360 mm

RS PRO CABLE TIE, ROLLER BALL, 200MM X 7.9 MM, METALLIC

- ขนาดบรรจุภัณฑ์: 100 x EA
- Length: 200 mm
 - Width: 7.9 mm
 - Colour: Metallic
 - Material: Polyester Coated Stainless Steel
 - Type: Roller Ball
 - Quantity: 100
 - Minimum Operating Temperature: -80 °C
 - Maximum Operating Temperature: +150 °C



5474355 200 mm

RS PRO CABLE TIE, ROLLER BALL, 360MM X 7.9 MM, METALLIC

- ขนาดบรรจุภัณฑ์: 100 x EA
- Length: 360 mm
 - Width: 7.9 mm
 - Colour: Metallic
 - Material: Polyester Coated Stainless Steel
 - Type: Roller Ball
 - Quantity: 100
 - Minimum Operating Temperature: -80 °C
 - Maximum Operating Temperature: +150 °C



5474377 360 mm

RS PRO CABLE TIE, RELEASABLE, 230MM X 10 MM, METALLIC 316

- ขนาดบรรจุภัณฑ์: 100 x EA
- Length: 230 mm
 - Width: 10 mm
 - Colour: Metallic
 - Material: 316 Stainless Steel
 - Type: Releasable
 - Quantity: 100
 - UV Resistant: Yes
 - Minimum Operating Temperature: -80 °C



5474399 230 mm

RS PRO CABLE TIE, RELEASABLE, 450MM X 10 MM, METALLIC 316

- ขนาดบรรจุภัณฑ์: 100 x EA
- Length: 450 mm
 - Width: 10 mm
 - Colour: Metallic
 - Material: 316 Stainless Steel
 - Type: Releasable
 - Quantity: 100
 - Minimum Operating Temperature: -80 °C
 - Maximum Operating Temperature: +150 °C



5474406 450 mm

RS PRO CABLE TIE, ROLLER BALL, 125MM X 4.6 MM, METALLIC 316

- ขนาดบรรจุภัณฑ์: 100 x EA
- Length: 125 mm
 - Width: 4.6 mm
 - Colour: Metallic
 - Material: 316 Stainless Steel
 - Type: Roller Ball
 - Quantity: 100
 - Minimum Operating Temperature: -80 °C
 - Maximum Operating Temperature: +538 °C



5474434 125 mm

RS PRO CABLE TIE, SUB MINIATURE, 71MM X 1.6 MM, WHITE NYLON, PK-

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 71 mm
 - Width: 1.6 mm
 - Colour: White
 - Material: Nylon 66
 - Type: Sub Miniature
 - Quantity: 100
 - Fire Behaviour: Flame Retardant
 - Tensile Strength: 78,4 N



6642883 71 mm

RS PRO CABLE TIE, SUB MINIATURE, 71MM X 1.6 MM, BLACK NYLON, PK-

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 71 mm
 - Width: 1.6 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Sub Miniature
 - Quantity: 100
 - UV Resistant: Yes
 - Fire Behaviour: Flame Retardant



6642887 71 mm

RS PRO CABLE TIE, DOUBLE LOCKING, 132MM X 9 MM, BLACK NYLON, PK-

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 132 mm
 - Width: 9 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Double Locking
 - Quantity: 100
 - Fire Behaviour: Flame Retardant
 - Tensile Strength: 343 N



6664672 132 mm

RS PRO CABLE TIE, DOUBLE LOCKING, 180MM X 9 MM, BLACK NYLON, PK-

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 180 mm
 - Width: 9 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Double Locking
 - Quantity: 100
 - Fire Behaviour: Flame Retardant
 - Tensile Strength: 343 N



6664675 180 mm

RS PRO CABLE TIE, DOUBLE LOCKING, 235MM X 9 MM, BLACK NYLON, PK-

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 235 mm
 - Width: 9 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Double Locking
 - Quantity: 100
 - Fire Behaviour: Flame Retardant
 - Tensile Strength: 539 N



6664679 235 mm

RS PRO CABLE TIE, DOUBLE LOCKING, 300MM X 9 MM, BLACK NYLON, PK-

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 300 mm
 - Width: 9 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Double Locking
 - Quantity: 100
 - Fire Behaviour: Flame Retardant
 - Tensile Strength: 539 N



6664681 300 mm

RS PRO CABLE TIE, DOUBLE LOCKING, 360MM X 9 MM, BLACK NYLON, PK-

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 360 mm
 - Width: 9 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Double Locking
 - Quantity: 100
 - Fire Behaviour: Flame Retardant
 - Tensile Strength: 539 N



6664685 360 mm

RS PRO CABLE TIE, DOUBLE LOCKING, 265MM X 9 MM, BLACK NYLON, PK-

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 265 mm
 - Width: 9 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Double Locking
 - Quantity: 100
 - Fire Behaviour: Flame Retardant
 - Tensile Strength: 539 N



6664688 265 mm

RS PRO CABLE TIE, DOUBLE LOCKING, 760MM X 9 MM, BLACK NYLON, PK-

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 760 mm
 - Width: 9 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Double Locking
 - Quantity: 100
 - Fire Behaviour: Flame Retardant
 - Tensile Strength: 539 N



6664691 760 mm

RS PRO CABLE TIE, DOUBLE LOCKING, 510MM X 9 MM, BLACK NYLON, PK-

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 510 mm
 - Width: 9 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Double Locking
 - Quantity: 100
 - Fire Behaviour: Flame Retardant
 - Tensile Strength: 539 N



6664694 510 mm

RS PRO CABLE TIE, DOUBLE LOCKING, 610MM X 9 MM, BLACK NYLON, PK-

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 610 mm
 - Width: 9 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Double Locking
 - Quantity: 100
 - Fire Behaviour: Flame Retardant
 - Tensile Strength: 539 N



6664697 610 mm

RS PRO CABLE TIE, DOUBLE LOCKING, 300MM X 9 MM, NATURAL NYLON, PK-

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 300 mm
 - Width: 9 mm
 - Colour: Natural
 - Material: Nylon 66
 - Type: Double Locking
 - Quantity: 100
 - Fire Behaviour: Flame Retardant
 - Tensile Strength: 539 N



6664710 300 mm

RS PRO CABLE TIE, DOUBLE LOCKING, 760MM X 9 MM, NATURAL NYLON, PK-

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 760 mm
 - Width: 9 mm
 - Colour: Natural
 - Material: Nylon 66
 - Type: Double Locking
 - Quantity: 100
 - Fire Behaviour: Flame Retardant
 - Tensile Strength: 539 N



6664720 760 mm

RS PRO CABLE TIE, DOUBLE LOCKING, 510MM X 9 MM, NATURAL NYLON, PK-

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 510 mm
 - Width: 9 mm
 - Colour: Natural
 - Material: Nylon 66
 - Type: Double Locking
 - Quantity: 100
 - Fire Behaviour: Flame Retardant
 - Tensile Strength: 539 N



6664723 510 mm

RS PRO CABLE TIE, ROLLER BALL, 680MM X 7.9 MM, METALLIC 316

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 680 mm
 - Width: 7.9 mm
 - Colour: Metallic
 - Material: 316 Stainless Steel
 - Type: Roller Ball
 - Quantity: 100
 - Minimum Operating Temperature: -80 °C
 - Maximum Operating Temperature: +538 °C



7436166 680 mm

RS PRO CABLE TIE, ROLLER BALL, 150MM X 4.6 MM, METALLIC 316

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 150 mm
 - Width: 4.6 mm
 - Colour: Metallic
 - Material: 316 Stainless Steel
 - Type: Roller Ball
 - Quantity: 100
 - Minimum Operating Temperature: -80 °C
 - Maximum Operating Temperature: +538 °C



7436169 150 mm

RS PRO CABLE TIE, ROLLER BALL, 1M X 4.6 MM, METALLIC 316 STAINLESS

- ขนาดบรรจุภัณฑ์: 100 x EA
- Length: 1 m
 - Width: 4.6 mm
 - Colour: Metallic
 - Material: 316 Stainless Steel
 - Type: Roller Ball
 - Quantity: 100
 - Minimum Operating Temperature: -80 °C
 - Maximum Operating Temperature: +538 °C



7436172 1 m

RS PRO CABLE TIE, ROLLER BALL, 840MM X 4.6 MM, METALLIC 316

- ขนาดบรรจุภัณฑ์: 100 x EA
- Length: 840 mm
 - Width: 4.6 mm
 - Colour: Metallic
 - Material: 316 Stainless Steel
 - Type: Roller Ball
 - Quantity: 100
 - Minimum Operating Temperature: -80 °C
 - Maximum Operating Temperature: +538 °C



7436175 840 mm

RS PRO CABLE TIE, ROLLER BALL, 840MM X 7.9 MM, METALLIC 316

- ขนาดบรรจุภัณฑ์: 100 x EA
- Length: 840 mm
 - Width: 7.9 mm
 - Colour: Metallic
 - Material: 316 Stainless Steel
 - Type: Roller Ball
 - Quantity: 100
 - Minimum Operating Temperature: -80 °C
 - Maximum Operating Temperature: +538 °C



7436178 840 mm

RS PRO CABLE TIE, ROLLER BALL, 100MM X 4.6 MM, BLACK POLYESTER

- ขนาดบรรจุภัณฑ์: 100 x EA
- Length: 100 mm
 - Width: 4.6 mm
 - Colour: Black
 - Material: Polyester Coated Stainless Steel
 - Type: Roller Ball
 - Quantity: 100
 - Minimum Operating Temperature: -80 °C
 - Maximum Operating Temperature: +150 °C



7436184 100 mm

RS PRO CABLE TIE, ROLLER BALL, 680MM X 4.6 MM, BLACK POLYESTER

- ขนาดบรรจุภัณฑ์: 100 x EA
- Length: 680 mm
 - Width: 4.6 mm
 - Colour: Black
 - Material: Polyester Coated Stainless Steel
 - Type: Roller Ball
 - Quantity: 100
 - Minimum Operating Temperature: -80 °C
 - Maximum Operating Temperature: +150 °C



7436190 680 mm

RS PRO CABLE TIE, ROLLER BALL, 680MM X 7.9 MM, BLACK POLYESTER

- ขนาดบรรจุภัณฑ์: 100 x EA
- Length: 680 mm
 - Width: 7.9 mm
 - Colour: Black
 - Material: Polyester Coated Stainless Steel
 - Type: Roller Ball
 - Quantity: 100
 - Minimum Operating Temperature: -80 °C
 - Maximum Operating Temperature: +150 °C



7436194 680 mm

RS PRO CABLE TIE, ROLLER BALL, 150MM X 4.6 MM, BLACK POLYESTER

- ขนาดบรรจุภัณฑ์: 100 x EA
- Length: 150 mm
 - Width: 4.6 mm
 - Colour: Black
 - Material: Polyester Coated Stainless Steel
 - Type: Roller Ball
 - Quantity: 100
 - Minimum Operating Temperature: -80 °C
 - Maximum Operating Temperature: +150 °C



7436197 150 mm

RS PRO CABLE TIE, ROLLER BALL, 100MM X 4.6 MM, YELLOW

- ขนาดบรรจุภัณฑ์: 100 x EA
- Length: 100 mm
 - Width: 4.6 mm
 - Colour: Yellow
 - Material: Polyester Coated Stainless Steel
 - Type: Roller Ball
 - Quantity: 100
 - Minimum Operating Temperature: -80 °C
 - Maximum Operating Temperature: +150 °C



7436239 100 mm

RS PRO CABLE TIE, ROLLER BALL, 150MM X 4.6 MM, YELLOW

- ขนาดบรรจุภัณฑ์: 100 x EA
- Length: 150 mm
 - Width: 4.6 mm
 - Colour: Yellow
 - Material: Polyester Coated Stainless Steel
 - Type: Roller Ball
 - Quantity: 100
 - Minimum Operating Temperature: -80 °C
 - Maximum Operating Temperature: +150 °C



7436241 150 mm

RS PRO CABLE TIE, ROLLER BALL, 360MM X 4.6 MM, GREEN POLYESTER

- ขนาดบรรจุภัณฑ์: 100 x EA
- Length: 360 mm
 - Width: 4.6 mm
 - Colour: Green
 - Material: Polyester Coated Stainless Steel
 - Type: Roller Ball
 - Quantity: 100
 - Minimum Operating Temperature: -80 °C
 - Maximum Operating Temperature: +150 °C



7436273 360 mm

RS PRO CABLE TIE, ROLLER BALL, 150MM X 4.6 MM, BLUE POLYESTER

- ขนาดบรรจุภัณฑ์: 100 x EA
- Length: 150 mm
 - Width: 4.6 mm
 - Colour: Blue
 - Material: Polyester Coated Stainless Steel
 - Type: Roller Ball
 - Quantity: 100
 - Minimum Operating Temperature: -80 °C
 - Maximum Operating Temperature: +150 °C



7436298 150 mm

RS PRO CABLE TIE, ZIG ZAG, 125MM X 4.6 MM, METALLIC 316 STAINLESS

- ขนาดบรรจุภัณฑ์: 100 x EA
- Length: 125 mm
 - Width: 4.6 mm
 - Colour: Metallic
 - Material: 316 Stainless Steel
 - Type: Zig Zag
 - Quantity: 100
 - Minimum Operating Temperature: -80 °C
 - Maximum Operating Temperature: +540 °C



7436336 125 mm

RS PRO CABLE TIE, ZIG ZAG, 360MM X 4.6 MM, METALLIC 316 STAINLESS

- ขนาดบรรจุภัณฑ์: 100 x EA
- Length: 360 mm
 - Width: 4.6 mm
 - Colour: Metallic
 - Material: 316 Stainless Steel
 - Type: Zig Zag
 - Quantity: 100
 - Minimum Operating Temperature: -80 °C
 - Maximum Operating Temperature: +540 °C



7436346 360 mm

RS PRO CABLE TIE, ZIG ZAG, 520MM X 7.9 MM, METALLIC 316 STAINLESS

- ขนาดบรรจุภัณฑ์: 100 x EA
- Length: 520 mm
 - Width: 7.9 mm
 - Colour: Metallic
 - Material: 316 Stainless Steel
 - Type: Zig Zag
 - Quantity: 100
 - Minimum Operating Temperature: -80 °C
 - Maximum Operating Temperature: +540 °C



7436352 520 mm

RS PRO CABLE TIE, ZIG ZAG, 360MM X 7.9 MM, METALLIC 316 STAINLESS

- ขนาดบรรจุภัณฑ์: 100 x EA
- Length: 360 mm
 - Width: 7.9 mm
 - Colour: Metallic
 - Material: 316 Stainless Steel
 - Type: Zig Zag
 - Quantity: 100
 - Minimum Operating Temperature: -80 °C
 - Maximum Operating Temperature: +540 °C



7436355 360 mm

RS PRO CABLE TIE, ZIG ZAG, 520MM X 4.6 MM, METALLIC 316 STAINLESS

- ขนาดบรรจุภัณฑ์: 100 x EA
- Length: 520 mm
 - Width: 4.6 mm
 - Colour: Metallic
 - Material: 316 Stainless Steel
 - Type: Zig Zag
 - Quantity: 100
 - Minimum Operating Temperature: -80 °C
 - Maximum Operating Temperature: +540 °C



7436358 520 mm

RS PRO CABLE TIE, 100MM X 4.6 MM, BLACK STAINLESS STEEL

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 100 mm
 - Width: 4.6 mm
 - Colour: Black
 - Material: Stainless Steel



7436361 100 mm

RS PRO CABLE TIE, ROLLER BALL, 4x40MM X 12 MM, METALLIC 316

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 440 mm
 - Width: 12 mm
 - Colour: Metallic
 - Material: 316 Stainless Steel
 - Type: Roller Ball
 - Quantity: 100
 - Minimum Operating Temperature: -80 °C
 - Maximum Operating Temperature: +540 °C



7436399 440 mm

RS PRO CABLE TIE, ROLLER BALL, 4x40MM X 12 MM, METALLIC

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 440 mm
 - Width: 12 mm
 - Colour: Metallic
 - Material: Polyester Coated Stainless Steel
 - Type: Roller Ball
 - Quantity: 100
 - UV Resistant: Yes
 - Minimum Operating Temperature: -80 °C



7436409 440 mm

RS PRO CABLE TIE, 100MM X 2.5 MM, BLACK NYLON, PK-100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 100 mm
 - Width: 2.5 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 100
 - UV Resistant: Yes
 - Fire Behaviour: Flame Retardant



8111482 100 mm

RS PRO CABLE TIE, 142MM X 3.2 MM, BLACK NYLON, PK-100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 142 mm
 - Width: 3.2 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 100
 - UV Resistant: Yes
 - Fire Behaviour: Flame Retardant



8111486 142 mm

RS PRO CABLE TIE, 385MM X 4.8 MM, BLACK NYLON, PK-100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 385 mm
 - Width: 4.8 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 100
 - UV Resistant: Yes
 - Fire Behaviour: Flame Retardant



8111492 385 mm

RS PRO CABLE TIE, 190MM X 4.8 MM, BLACK NYLON, PK-100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 190 mm
 - Width: 4.8 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 100
 - UV Resistant: Yes
 - Fire Behaviour: Flame Retardant



8111495 190 mm

RS PRO CABLE TIE, 203MM X 4.6 MM, BLACK NYLON, PK-100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 203 mm
 - Width: 4.6 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 100
 - UV Resistant: Yes
 - Fire Behaviour: Flame Retardant



8111498 203 mm

RS PRO CABLE TIE, 450MM X 4.8 MM, BLACK NYLON, PK-100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 450 mm
 - Width: 4.8 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 100
 - UV Resistant: Yes
 - Fire Behaviour: Flame Retardant



8111502 450 mm

RS PRO CABLE TIE, 380MM X 7.6 MM, BLACK NYLON, PK-100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 380 mm
 - Width: 7.6 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 100
 - UV Resistant: Yes
 - Fire Behaviour: Flame Retardant



8111509 380 mm

RS PRO CABLE TIE, 300MM X 7.6 MM, BLACK NYLON, PK-100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 300 mm
 - Width: 7.6 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 100
 - UV Resistant: Yes
 - Fire Behaviour: Flame Retardant



8111511 300 mm

RS PRO CABLE TIE, 450MM X 8 MM, BLACK NYLON, PK-100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 450 mm
 - Width: 8 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 100
 - UV Resistant: Yes
 - Fire Behaviour: Flame Retardant



8111515 450 mm

RS PRO CABLE TIE, 240MM X 7.6 MM, BLACK NYLON, PK-100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 240 mm
 - Width: 7.6 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 100
 - UV Resistant: Yes
 - Fire Behaviour: Flame Retardant



8111518 240 mm

RS PRO CABLE TIE, 203MM X 4.6 MM, NATURAL NYLON, PK-100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 203 mm
 - Width: 4.6 mm
 - Colour: Natural
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 100
 - UV Resistant: Yes
 - Fire Behaviour: Flame Retardant



8111521 203 mm

RS PRO CABLE TIE, 610MM X 9 MM, BLACK NYLON, PK-100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 610 mm
 - Width: 9 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 100
 - UV Resistant: Yes
 - Fire Behaviour: Flame Retardant



8111524 610 mm

RS PRO CABLE TIE, 385MM X 4.8 MM, NATURAL NYLON, PK-100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 385 mm
 - Width: 4.8 mm
 - Colour: Natural
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 100
 - UV Resistant: Yes
 - Fire Behaviour: Flame Retardant



8111530 385 mm

RS PRO CABLE TIE, 450MM X 4.8 MM, NATURAL NYLON, PK-100

- ขนาดบรรจุภัณฑ์: 100 x EA
- Length: 450 mm
 - Width: 4.8 mm
 - Colour: Natural
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 100
 - UV Resistant: Yes
 - Fire Behaviour: Flame Retardant



8111533 450 mm

RS PRO CABLE TIE, 300MM X 4.8 MM, NATURAL NYLON, PK-100

- ขนาดบรรจุภัณฑ์: 100 x EA
- Length: 300 mm
 - Width: 4.8 mm
 - Colour: Natural
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 100
 - UV Resistant: Yes
 - Fire Behaviour: Flame Retardant



8111537 300 mm

RS PRO CABLE TIE, 300MM X 7.6 MM, NATURAL NYLON, PK-100

- ขนาดบรรจุภัณฑ์: 100 x EA
- Length: 300 mm
 - Width: 7.6 mm
 - Colour: Natural
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 100
 - UV Resistant: Yes
 - Fire Behaviour: Flame Retardant



8111543 300 mm

RS PRO CABLE TIE, 380MM X 7.6 MM, NATURAL NYLON, PK-100

- ขนาดบรรจุภัณฑ์: 100 x EA
- Length: 380 mm
 - Width: 7.6 mm
 - Colour: Natural
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 100
 - UV Resistant: Yes
 - Fire Behaviour: Flame Retardant



8111546 380 mm

RS PRO CABLE TIE, 240MM X 7.6 MM, NATURAL NYLON, PK-100

- ขนาดบรรจุภัณฑ์: 100 x EA
- Length: 240 mm
 - Width: 7.6 mm
 - Colour: Natural
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 100
 - UV Resistant: Yes
 - Fire Behaviour: Flame Retardant



8111549 240 mm

RS PRO CABLE TIE, 450MM X 8 MM, NATURAL NYLON, PK-100

- ขนาดบรรจุภัณฑ์: 100 x EA
- Length: 450 mm
 - Width: 8 mm
 - Colour: Natural
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 100
 - UV Resistant: Yes
 - Fire Behaviour: Flame Retardant



8111552 450 mm

RS PRO CABLE TIE, 610MM X 9 MM, NATURAL NYLON, PK-100

- ขนาดบรรจุภัณฑ์: 100 x EA
- Length: 610 mm
 - Width: 9 mm
 - Colour: Natural
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 100
 - UV Resistant: Yes
 - Fire Behaviour: Flame Retardant



8111555 610 mm

RS PRO CABLE TIE, 750MM X 7.5 MM, NATURAL NYLON, PK-100

- ขนาดบรรจุภัณฑ์: 100 x EA
- Length: 750 mm
 - Width: 7.5 mm
 - Colour: Natural
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 100
 - UV Resistant: Yes
 - Fire Behaviour: Flame Retardant



8111559 750 mm

RS PRO CABLE TIE, 142MM X 3.2 MM, NATURAL NYLON, PK-100

- ขนาดบรรจุภัณฑ์: 100 x EA
- Length: 142 mm
 - Width: 3.2 mm
 - Colour: Natural
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 100
 - UV Resistant: Yes
 - Fire Behaviour: Flame Retardant



8111561 142 mm

RS PRO CABLE TIE, 190MM X 4.8 MM, NATURAL NYLON, PK-100

- ขนาดบรรจุภัณฑ์: 100 x EA
- Length: 190 mm
 - Width: 4.8 mm
 - Colour: Natural
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 100
 - UV Resistant: Yes
 - Fire Behaviour: Flame Retardant



8111565 190 mm

RS PRO CABLE TIE, 100MM X 2.5 MM, NATURAL NYLON, PK-100

- ขนาดบรรจุภัณฑ์: 100 x EA
- Length: 100 mm
 - Width: 2.5 mm
 - Colour: Natural
 - Material: Nylon 66
 - Type: Non-Releaseable
 - Quantity: 100
 - UV Resistant: Yes
 - Fire Behaviour: Flame Retardant



8111568 100 mm

RS PRO CABLE TIE, HEAT STABILISED, 203MM X 2.5 MM, BLACK NYLON, PK-

- ขนาดบรรจุภัณฑ์: 100 x EA
- Length: 203 mm
 - Width: 2.5 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Heat Stabilised
 - Quantity: 100
 - Maximum Operating Temperature: +105 °C
 - Fire Behaviour: Flame Retardant



8111571 203 mm

RS PRO CABLE TIE, HEAT STABILISED, 142MM X 2.5 MM, BLACK NYLON, PK-

- ขนาดบรรจุภัณฑ์: 100 x EA
- Length: 142 mm
 - Width: 2.5 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Heat Stabilised
 - Quantity: 100
 - Maximum Operating Temperature: +105 °C
 - Fire Behaviour: Flame Retardant



8111574 142 mm

RS PRO CABLE TIE, HEAT STABILISED, 100MM X 2.5 MM, BLACK NYLON, PK-

- ขนาดบรรจุภัณฑ์: 100 x EA
- Length: 100 mm
 - Width: 2.5 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Heat Stabilised
 - Quantity: 100
 - Maximum Operating Temperature: +105 °C
 - Fire Behaviour: Flame Retardant



8111577 100 mm

RS PRO CABLE TIE, HEAT STABILISED, 150MM X 3.6 MM, BLACK NYLON, PK-

- ขนาดบรรจุภัณฑ์: 100 x EA
- Length: 150 mm
 - Width: 3.6 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Heat Stabilised
 - Quantity: 100
 - Maximum Operating Temperature: +105 °C
 - Fire Behaviour: Flame Retardant



8111580 150 mm

RS PRO CABLE TIE, HEAT STABILISED, 160MM X 4.8 MM, BLACK NYLON, PK-

- ขนาดบรรจุภัณฑ์: 100 x EA
- Length: 160 mm
 - Width: 4.8 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Heat Stabilised
 - Quantity: 100
 - Maximum Operating Temperature: +105 °C
 - Fire Behaviour: Flame Retardant



8111583 160 mm

RS PRO CABLE TIE, HEAT STABILISED, 180MM X 3.6 MM, BLACK NYLON, PK-

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 180 mm
 - Width: 3.6 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Heat Stabilised
 - Quantity: 100
 - Maximum Operating Temperature: +105 °C
 - Fire Behaviour: Flame Retardant



8111587 180 mm

RS PRO CABLE TIE, HEAT STABILISED, 265MM X 3.6 MM, BLACK NYLON, PK-

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 265 mm
 - Width: 3.6 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Heat Stabilised
 - Quantity: 100
 - Maximum Operating Temperature: +105 °C
 - Fire Behaviour: Flame Retardant



8111593 265 mm

RS PRO CABLE TIE, HEAT STABILISED, 203MM X 3.6 MM, BLACK NYLON, PK-

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 203 mm
 - Width: 3.6 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Heat Stabilised
 - Quantity: 100
 - Maximum Operating Temperature: +105 °C
 - Fire Behaviour: Flame Retardant



8111596 203 mm

RS PRO CABLE TIE, HEAT STABILISED, 292MM X 3.6 MM, BLACK NYLON, PK-

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 292 mm
 - Width: 3.6 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Heat Stabilised
 - Quantity: 100
 - Maximum Operating Temperature: +105 °C
 - Fire Behaviour: Flame Retardant



8111599 292 mm

RS PRO CABLE TIE, RELEASABLE, 150MM X 7.6 MM, BLACK NYLON, PK-

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 150 mm
 - Width: 7.6 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Releasable
 - Quantity: 100
 - Fire Behaviour: Flame Retardant
 - Tensile Strength: 215.6 N



8111600 150 mm

RS PRO CABLE TIE, HEAT STABILISED, 203MM X 4.6 MM, BLACK NYLON, PK-

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 203 mm
 - Width: 4.6 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Heat Stabilised
 - Quantity: 100
 - Maximum Operating Temperature: +105 °C
 - Fire Behaviour: Flame Retardant



8111603 203 mm

RS PRO CABLE TIE, HEAT STABILISED, 550MM X 12.7 MM, BLACK NYLON, PK-

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 550 mm
 - Width: 12.7 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Heat Stabilised
 - Quantity: 100
 - Maximum Operating Temperature: +105 °C
 - Fire Behaviour: Self-extinguishing



8111606 550 mm

RS PRO CABLE TIE, RELEASABLE, 150MM X 7.6 MM, NATURAL NYLON,

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 150 mm
 - Width: 7.6 mm
 - Colour: Natural
 - Material: Nylon 66
 - Type: Releasable
 - Quantity: 100
 - Fire Behaviour: Flame Retardant
 - Tensile Strength: 215.6 N



8111612 150 mm

RS PRO CABLE TIE, RELEASABLE, 250MM X 7.6 MM, NATURAL NYLON,

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 250 mm
 - Width: 7.6 mm
 - Colour: Natural
 - Material: Nylon 66
 - Type: Releasable
 - Quantity: 100
 - Fire Behaviour: Flame Retardant
 - Tensile Strength: 215.6 N



8111616 250 mm

RS PRO CABLE TIE, RELEASABLE, 250MM X 7.6 MM, BLACK NYLON, PK-

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 250 mm
 - Width: 7.6 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Releasable
 - Quantity: 100
 - Fire Behaviour: Flame Retardant
 - Tensile Strength: 215.6 N



8111619 250 mm

RS PRO CABLE TIE, HEAT STABILISED, 203MM X 2.5 MM, NATURAL NYLON,

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 203 mm
 - Width: 2.5 mm
 - Colour: Natural
 - Material: Nylon 66
 - Type: Heat Stabilised
 - Quantity: 100
 - Maximum Operating Temperature: +105 °C
 - Fire Behaviour: Flame Retardant



8111622 203 mm

RS PRO CABLE TIE, HEAT STABILISED, 142MM X 2.5 MM, NATURAL NYLON,

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 142 mm
 - Width: 2.5 mm
 - Colour: Natural
 - Material: Nylon 66
 - Type: Heat Stabilised
 - Quantity: 100
 - Maximum Operating Temperature: +105 °C
 - Fire Behaviour: Flame Retardant



8111625 142 mm

RS PRO CABLE TIE, HEAT STABILISED, 150MM X 3.6 MM, NATURAL NYLON,

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 150 mm
 - Width: 3.6 mm
 - Colour: Natural
 - Material: Nylon 66
 - Type: Heat Stabilised
 - Quantity: 100
 - Maximum Operating Temperature: +105 °C
 - Fire Behaviour: Flame Retardant



8111631 150 mm

RS PRO CABLE TIE, HEAT STABILISED, 160MM X 4.8 MM, NATURAL NYLON,

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 160 mm
 - Width: 4.8 mm
 - Colour: Natural
 - Material: Nylon 66
 - Type: Heat Stabilised
 - Quantity: 100
 - Maximum Operating Temperature: +105 °C
 - Fire Behaviour: Flame Retardant



8111634 160 mm

RS PRO CABLE TIE, HEAT STABILISED, 180MM X 3.6 MM, NATURAL NYLON,

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 180 mm
 - Width: 3.6 mm
 - Colour: Natural
 - Material: Nylon 66
 - Type: Heat Stabilised
 - Quantity: 100
 - Maximum Operating Temperature: +105 °C
 - Fire Behaviour: Flame Retardant



8111638 180 mm

RS PRO CABLE TIE, HEAT STABILISED, 292MM X 3.6 MM, NATURAL NYLON,

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 292 mm
 - Width: 3.6 mm
 - Colour: Natural
 - Material: Nylon 66
 - Type: Heat Stabilised
 - Quantity: 100
 - Maximum Operating Temperature: +105 °C
 - Fire Behaviour: Flame Retardant



8111640 292 mm

RS PRO CABLE TIE, HEAT STABILISED, 265MM X 3.6 MM, NATURAL NYLON,

ขนาดบรรจุภัณฑ์: 100 x EA

- Length: 265 mm
- Width: 3.6 mm
- Colour: Natural
- Material: Nylon 66
- Type: Heat Stabilised
- Quantity: 100
- Maximum Operating Temperature: +105 °C
- Fire Behaviour: Flame Retardant



8111644 265 mm

RS PRO CABLE TIE, HEAT STABILISED, 203MM X 3.6 MM, NATURAL NYLON,

ขนาดบรรจุภัณฑ์: 100 x EA

- Length: 203 mm
- Width: 3.6 mm
- Colour: Natural
- Material: Nylon 66
- Type: Heat Stabilised
- Quantity: 100
- Maximum Operating Temperature: +105 °C
- Fire Behaviour: Flame Retardant



8111647 203 mm

RS PRO CABLE TIE, 300MM X 4.8 MM, BLACK NYLON, PK-1000

ขนาดบรรจุภัณฑ์: 1000 x EA

- Length: 300 mm
- Width: 4.8 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releaseable
- Quantity: 1000
- Fire Behaviour: Flame Retardant
- Maximum Bundle Diameter: 83 mm



8111650 300 mm

RS PRO CABLE TIE, HEAT STABILISED, 203MM X 4.6 MM, NATURAL NYLON,

ขนาดบรรจุภัณฑ์: 100 x EA

- Length: 203 mm
- Width: 4.6 mm
- Colour: Natural
- Material: Nylon 66
- Type: Heat Stabilised
- Quantity: 100
- Maximum Operating Temperature: +105 °C
- Fire Behaviour: Flame Retardant



8111653 203 mm

RS PRO CABLE TIE, 368MM X 4.8 MM, BLACK NYLON, PK-1000

ขนาดบรรจุภัณฑ์: 1000 x EA

- Length: 368 mm
- Width: 4.8 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releaseable
- Quantity: 1000
- Fire Behaviour: Flame Retardant
- Maximum Bundle Diameter: 105 mm



8111662 368 mm

RS PRO CABLE TIE, 203MM X 4.6 MM, BLACK NYLON, PK-1000

ขนาดบรรจุภัณฑ์: 1000 x EA

- Length: 203 mm
- Width: 4.6 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releaseable
- Quantity: 1000
- Fire Behaviour: Flame Retardant
- Tensile Strength: 215.6 N



8111666 203 mm

RS PRO CABLE TIE, 380MM X 7.6 MM, BLACK NYLON, PK-1000

ขนาดบรรจุภัณฑ์: 1000 x EA

- Length: 380 mm
- Width: 7.6 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releaseable
- Quantity: 1000
- Fire Behaviour: Flame Retardant
- Maximum Bundle Diameter: 105 mm



8111669 380 mm

RS PRO CABLE TIE, 610MM X 9 MM, BLACK NYLON, PK-100

ขนาดบรรจุภัณฑ์: 100 x EA

- Length: 610 mm
- Width: 9 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releaseable
- Quantity: 100
- Fire Behaviour: Flame Retardant
- Tensile Strength: 784 N



8111672 610 mm

RS PRO CABLE TIE, 550MM X 12.7 MM, BLACK NYLON, PK-100

ขนาดบรรจุภัณฑ์: 100 x EA

- Length: 550 mm
- Width: 12.7 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releaseable
- Quantity: 100
- Fire Behaviour: Flame Retardant
- Tensile Strength: 1117.2 N



8111675 550 mm

RS PRO CABLE TIE, 450MM X 8 MM, BLACK NYLON, PK-100

ขนาดบรรจุภัณฑ์: 100 x EA

- Length: 450 mm
- Width: 8 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releaseable
- Quantity: 100
- Fire Behaviour: Flame Retardant
- Tensile Strength: 588 N



8111678 450 mm

RS PRO CABLE TIE, 762MM X 9 MM, BLACK NYLON, PK-100

ขนาดบรรจุภัณฑ์: 100 x EA

- Length: 762 mm
- Width: 9 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releaseable
- Quantity: 100
- Fire Behaviour: Flame Retardant
- Tensile Strength: 784 N



8111681 762 mm

RS PRO CABLE TIE, 340MM X 7.6 MM, BLACK NYLON, PK-100

ขนาดบรรจุภัณฑ์: 100 x EA

- Length: 340 mm
- Width: 7.6 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releaseable
- Quantity: 100
- Fire Behaviour: Flame Retardant
- Tensile Strength: 539 N



8111684 340 mm

RS PRO CABLE TIE, 300MM X 7.6 MM, BLACK NYLON, PK-1000

ขนาดบรรจุภัณฑ์: 100 x EA

- Length: 300 mm
- Width: 7.6 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releaseable
- Quantity: 100
- Fire Behaviour: Flame Retardant
- Tensile Strength: 539 N



8111688 300 mm

RS PRO CABLE TIE, 100MM X 2.5 MM, NATURAL NYLON, PK-1000

ขนาดบรรจุภัณฑ์: 1000 x EA

- Length: 100 mm
- Width: 2.5 mm
- Colour: Natural
- Material: Nylon 66
- Type: Non-Releaseable
- Quantity: 1000
- Fire Behaviour: Flame Retardant
- Tensile Strength: 78.4 N



8111690 100 mm

RS PRO CABLE TIE, 203MM X 2.5 MM, NATURAL NYLON, PK-100

ขนาดบรรจุภัณฑ์: 100 x EA

- Length: 203 mm
- Width: 2.5 mm
- Colour: Natural
- Material: Nylon 66
- Type: Non-Releaseable
- Quantity: 100
- Fire Behaviour: Flame Retardant
- Tensile Strength: 78.4 N



8111694 203 mm

RS PRO CABLE TIE, 250MM X 4.8 MM, BLACK NYLON, PK-100

ขนาดบรรจุภัณฑ์: 100 x EA

- Length: 250 mm
- Width: 4.8 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releaseable
- Quantity: 100
- Fire Behaviour: Flame Retardant
- Tensile Strength: 215.6 N



8111697 250 mm

RS PRO CABLE TIE, 550MM X 12.7 MM, NATURAL NYLON, PK-100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 550 mm
 - Width: 12.7 mm
 - Colour: Natural
 - Material: Nylon 66
 - Type: Non-Releasable
 - Quantity: 100
 - Fire Behaviour: Flame Retardant
 - Tensile Strength: 1117.2 N



8111701 550 mm

RS PRO CABLE TIE, 142MM X 2.5 MM, NATURAL NYLON, PK-100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 142 mm
 - Width: 2.5 mm
 - Colour: Natural
 - Material: Nylon 66
 - Type: Non-Releasable
 - Quantity: 100
 - Fire Behaviour: Flame Retardant
 - Tensile Strength: 78.4 N



8111704 142 mm

RS PRO CABLE TIE, 385MM X 4.8 MM, NATURAL NYLON, PK-100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 385 mm
 - Width: 4.8 mm
 - Colour: Natural
 - Material: Nylon 66
 - Type: Non-Releasable
 - Quantity: 100
 - Fire Behaviour: Flame Retardant
 - Tensile Strength: 215.6 N



8111707 385 mm

RS PRO CABLE TIE, 160MM X 4.8 MM, NATURAL NYLON, PK-100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 160 mm
 - Width: 4.8 mm
 - Colour: Natural
 - Material: Nylon 66
 - Type: Non-Releasable
 - Quantity: 100
 - Fire Behaviour: Flame Retardant
 - Tensile Strength: 215.6 N



8111710 160 mm

RS PRO CABLE TIE, FLAME RETARDANT, 380MM X 12.7 MM,

- ขนาดบรรจุภัณฑ์: **50 x EA**
- Length: 380 mm
 - Width: 12.7 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Flame Retardant
 - Quantity: 100
 - Fire Behaviour: Flame Retardant
 - Tensile Strength: 1117.2 N



8111741 380 mm

RS PRO CABLE TIE, FLAME RETARDANT, 480MM X 12.7 MM,

- ขนาดบรรจุภัณฑ์: **50 x EA**
- Length: 480 mm
 - Width: 12.7 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Flame Retardant
 - Quantity: 100
 - Fire Behaviour: Flame Retardant
 - Tensile Strength: 1117.2 N



8111745 480 mm

RS PRO CABLE TIE, FLAME RETARDANT, 280MM X 12.7 MM,

- ขนาดบรรจุภัณฑ์: **50 x EA**
- Length: 280 mm
 - Width: 12.7 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Flame Retardant
 - Quantity: 100
 - Fire Behaviour: Flame Retardant
 - Tensile Strength: 1117.2 N



8111748 280 mm

RS PRO CABLE TIE, FLAME RETARDANT, 550MM X 12.7 MM,

- ขนาดบรรจุภัณฑ์: **50 x EA**
- Length: 550 mm
 - Width: 12.7 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Flame Retardant
 - Quantity: 100
 - Fire Behaviour: Flame Retardant
 - Tensile Strength: 1117.2 N



8111754 550 mm

RS PRO CABLE TIE, FLAME RETARDANT, 100MM X 2.5 MM, BLACK

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 100 mm
 - Width: 2.5 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Flame Retardant
 - Quantity: 100
 - Fire Behaviour: Flame Retardant
 - Tensile Strength: 78.4 N



8111773 100 mm

RS PRO CABLE TIE, FLAME RETARDANT, 150MM X 3.6 MM, BLACK

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 150 mm
 - Width: 3.6 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Flame Retardant
 - Quantity: 100
 - Fire Behaviour: Flame Retardant
 - Tensile Strength: 176.4 N



8111776 150 mm

RS PRO CABLE TIE, FLAME RETARDANT, 203MM X 4.8 MM,

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 203 mm
 - Width: 4.8 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Flame Retardant
 - Quantity: 100
 - Fire Behaviour: Flame Retardant
 - Tensile Strength: 215.6 N



8111779 203 mm

RS PRO CABLE TIE, FLAME RETARDANT, 380MM X 7.6 MM,

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 380 mm
 - Width: 7.6 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Flame Retardant
 - Quantity: 100
 - Fire Behaviour: Flame Retardant
 - Tensile Strength: 539 N



8111782 380 mm

RS PRO CABLE TIE, 111MM X 2.6 MM, NATURAL NYLON, PK-100

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 111 mm
 - Width: 2.6 mm
 - Colour: Natural
 - Material: Nylon 66
 - Type: Non-Releasable
 - Quantity: 100
 - Fire Behaviour: Flame Retardant
 - Maximum Bundle Diameter: 20 mm



8111785 111 mm

RS PRO CABLE TIE, RELEASABLE, 125MM X 4.5 MM, BLACK NYLON, PK-

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 125 mm
 - Width: 4.5 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Releasable
 - Quantity: 100
 - Fire Behaviour: Flame Retardant
 - Tensile Strength: 215.6 N



8111795 125 mm

RS PRO CABLE TIE, RELEASABLE, 250MM X 4.5 MM, BLACK NYLON, PK-

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 250 mm
 - Width: 4.5 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Releasable
 - Quantity: 100
 - Fire Behaviour: Flame Retardant
 - Tensile Strength: 215.6 N



8111802 250 mm

RS PRO CABLE TIE, RELEASABLE, 150MM X 4.5 MM, BLACK NYLON, PK-

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Length: 150 mm
 - Width: 4.5 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Releasable
 - Quantity: 100
 - Fire Behaviour: Flame Retardant
 - Tensile Strength: 215.6 N



8111805 150 mm

RS PRO CABLE TIE, RELEASABLE, 200MM X 4.5 MM, BLACK NYLON, PK-

- ขนาดบรรจุภัณฑ์: 100 x EA
- Length: 200 mm
 - Width: 4.5 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Releasable
 - Quantity: 100
 - Fire Behaviour: Flame Retardant
 - Tensile Strength: 215.6 N



8111808 200 mm

RS PRO CABLE TIE, RELEASABLE, 300MM X 4.5 MM, BLACK NYLON, PK-

- ขนาดบรรจุภัณฑ์: 100 x EA
- Length: 300 mm
 - Width: 4.5 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Releasable
 - Quantity: 100
 - Fire Behaviour: Flame Retardant
 - Tensile Strength: 215.6 N



8111811 300 mm

RS PRO CABLE TIE, DOUBLE LOCKING, 132MM X 6 MM, BLACK NYLON, PK-

- ขนาดบรรจุภัณฑ์: 100 x EA
- Length: 132 mm
 - Width: 6 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Double Locking
 - Quantity: 100
 - Fire Behaviour: Flame Retardant
 - Tensile Strength: 22 kg



8659625 132 mm

RS PRO CABLE TIE, DOUBLE LOCKING, 180MM X 6 MM, BLACK NYLON, PK-

- ขนาดบรรจุภัณฑ์: 100 x EA
- Length: 180 mm
 - Width: 6 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Double Locking
 - Quantity: 100
 - Fire Behaviour: Flame Retardant
 - Tensile Strength: 22 kg



8659629 180 mm

RS PRO CABLE TIE, DOUBLE LOCKING, 382MM X 9 MM, BLACK NYLON, PK-

- ขนาดบรรจุภัณฑ์: 100 x EA
- Length: 382 mm
 - Width: 9 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Double Locking
 - Quantity: 100
 - Fire Behaviour: Flame Retardant
 - Tensile Strength: 55 kg



8659641 382 mm

RS PRO CABLE TIE, DOUBLE LOCKING, 292MM X 9 MM, BLACK NYLON, PK-

- ขนาดบรรจุภัณฑ์: 100 x EA
- Length: 292 mm
 - Width: 9 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Double Locking
 - Quantity: 100
 - Fire Behaviour: Flame Retardant
 - Tensile Strength: 55 kg



8659644 292 mm

RS PRO CABLE TIE, DOUBLE LOCKING, 760MM X 9 MM, BLACK NYLON, PK-

- ขนาดบรรจุภัณฑ์: 100 x EA
- Length: 760 mm
 - Width: 9 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Double Locking
 - Quantity: 100
 - Fire Behaviour: Flame Retardant
 - Tensile Strength: 55 kg



8659657 760 mm

RS PRO CRIMPING TOOL

- ขนาดบรรจุภัณฑ์: 1 x EA
- Crimp Tool Type: Crimping Tool
 - For Use With: Cable Bushings
 - Overall Length: 174 mm



392012 Crimping Tool

STRAIN RELIEF BUSH, 5.6-6.22MM CABLE DIA

- ขนาดบรรจุภัณฑ์: 25 x EA
- Material: Nylon 66
 - Colour: Black



8178861 Nylon 66

STRAIN RELIEF BUSH, 6.37-7.37MM CABLE DIA

- ขนาดบรรจุภัณฑ์: 25 x EA
- Material: Nylon 66
 - Colour: Black



8178870 Nylon 66

STRAIN RELIEF BUSH, 7.6MM CABLE DIA

- ขนาดบรรจุภัณฑ์: 25 x EA
- Material: Nylon 66
 - Colour: Black



8178873 Nylon 66

STRAIN RELIEF BUSH, 8.25-9.14MM CABLE DIA

- ขนาดบรรจุภัณฑ์: 25 x EA
- Material: Nylon 66
 - Colour: Black



8178877 Nylon 66

BREAK-AWAY FAN MOUNT 83,5MM

- ขนาดบรรจุภัณฑ์: 50 x EA
- Mount Type: Rivet



1720861 Rivet

FAN MOUNT RIVET 22,2MM 40 SHORE A

- ขนาดบรรจุภัณฑ์: 50 x EA
- Mount Type: Rivet



1720862 Rivet

CABLE, HEATSHRINK, SLEEVE, LOW TEMPERATURE, BORE 1.6MM

- ขนาดบรรจุภัณฑ์: **25 x MTR**
- Sleeve Diameter: 1.6 mm
 - Shrink Diameter: 0.8 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 25 m
 - Material: Polyolefin



389628 1.6 mm

CABLE, HEATSHRINK, SLEEVE, LOW TEMPERATURE, BORE 2.4MM

- ขนาดบรรจุภัณฑ์: **25 x MTR**
- Sleeve Diameter: 2.4 mm
 - Shrink Diameter: 1.2 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 25 m
 - Material: Polyolefin



389634 2.4 mm

RS PRO HEAT SHRINK TUBING, BLACK 3.2MM SLEEVE DIA. X 20M LENGTH 2:1

- ขนาดบรรจุภัณฑ์: **20 x MTR**
- Sleeve Diameter: 3.2 mm
 - Shrink Diameter: 1.6 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 20 m
 - Material: Polyolefin



389640 3.2 mm

RS PRO HEAT SHRINK TUBING, BLACK 4.8MM SLEEVE DIA. X 20M LENGTH 2:1

- ขนาดบรรจุภัณฑ์: **20 x MTR**
- Sleeve Diameter: 4.8 mm
 - Shrink Diameter: 2.4 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 20 m
 - Material: Polyolefin



389656 4.8 mm

CABLE, HEATSHRINK, SLEEVE, LOW TEMPERATURE, BORE 6.4MM

- ขนาดบรรจุภัณฑ์: **15 x MTR**
- Sleeve Diameter: 6.4 mm
 - Shrink Diameter: 3.2 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 15 m
 - Material: Polyolefin



389662 6.4 mm

RS PRO HEAT SHRINK TUBING, BLACK 9.5MM SLEEVE DIA. X 12M LENGTH 2:1

- ขนาดบรรจุภัณฑ์: **12 x MTR**
- Sleeve Diameter: 9.5 mm
 - Shrink Diameter: 4.7 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 12 m
 - Material: Polyolefin



389678 9.5 mm

CABLE, HEATSHRINK, SLEEVE, LOW TEMPERATURE, BORE 12.7MM

- ขนาดบรรจุภัณฑ์: **10 x MTR**
- Sleeve Diameter: 12.7 mm
 - Shrink Diameter: 6.3 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 10 m
 - Material: Polyolefin



389684 12.7 mm

RS PRO HEAT SHRINK TUBING, BLACK 19MM SLEEVE DIA. X 6M LENGTH 2:1

- ขนาดบรรจุภัณฑ์: **6 x MTR**
- Sleeve Diameter: 19 mm
 - Shrink Diameter: 9.5 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 6 m
 - Material: Polyolefin



389690 19 mm

CABLE, HEATSHRINK, SLEEVE, LOW TEMPERATURE, BORE 25.4MM

- ขนาดบรรจุภัณฑ์: **3 x MTR**
- Sleeve Diameter: 25.4 mm
 - Shrink Diameter: 12.7 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 3 m
 - Material: Polyolefin



389707 25.4 mm

CABLE, HEATSHRINK, SLEEVE, WHITE, POLYOLEFIN, 1.2, BORE 1.6MM

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Sleeve Diameter: 1.6 mm
 - Shrink Diameter: 0.8 mm
 - Colour: White
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



392220 1.6 mm

CABLE, HEATSHRINK, SLEEVE, WHITE, POLYOLEFIN, 1.2, BORE 2.4MM

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Sleeve Diameter: 2.4 mm
 - Shrink Diameter: 1.2 mm
 - Colour: White
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



392236 2.4 mm

RS PRO HEAT SHRINK TUBING, WHITE 3.2MM SLEEVE DIA. X 1.2M LENGTH 2:1

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Sleeve Diameter: 3.2 mm
 - Shrink Diameter: 1.6 mm
 - Colour: White
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



392242 3.2 mm

RS PRO HEAT SHRINK TUBING, WHITE 4.8MM SLEEVE DIA. X 1.2M LENGTH 2:1

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Sleeve Diameter: 4.8 mm
 - Shrink Diameter: 2.4 mm
 - Colour: White
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



392258 4.8 mm

CABLE, HEATSHRINK, SLEEVE, WHITE, POLYOLEFIN, 1.2, BORE 6.4MM

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Sleeve Diameter: 6.4 mm
 - Shrink Diameter: 3.2 mm
 - Colour: White
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



392264 6.4 mm

CABLE, HEATSHRINK, SLEEVE, WHITE, POLYOLEFIN, 1.2, BORE 9.5MM

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Sleeve Diameter: 9.5 mm
 - Shrink Diameter: 4.8 mm
 - Colour: White
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



392270 9.5 mm

CABLE, HEATSHRINK, SLEEVE, WHITE, POLYOLEFIN, 1.2, BORE 12.7MM

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Sleeve Diameter: 12.7 mm
 - Shrink Diameter: 6.4 mm
 - Colour: White
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



392286 12.7 mm

**RS PRO HEAT SHRINK TUBING, WHITE
19.1MM SLEEVE DIA. X 1.2M LENGTH**

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Sleeve Diameter: 19.1 mm
 - Shrunk Diameter: 9.5 mm
 - Colour: White
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



392292 19.1 mm

**RS PRO HEAT SHRINK TUBING, WHITE
25.4MM SLEEVE DIA. X 1.2M LENGTH**

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Sleeve Diameter: 25.4 mm
 - Shrunk Diameter: 12.7 mm
 - Colour: White
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



392309 25.4 mm

**RS PRO HEAT SHRINK TUBING, WHITE
38.1MM SLEEVE DIA. X 1.2M LENGTH**

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Sleeve Diameter: 38.1 mm
 - Shrunk Diameter: 19.1 mm
 - Colour: White
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



392315 38.1 mm

**RS PRO HEAT SHRINK TUBING, WHITE
50.8MM SLEEVE DIA. X 1.2M LENGTH**

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Sleeve Diameter: 50.8 mm
 - Shrunk Diameter: 25.4 mm
 - Colour: White
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



392321 50.8 mm

CABLE, HEATSHRINK, SLEEVE, KIT, 1.0-6.4MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 2.4 mm, 3 mm, 3.2 mm, 4.8 mm, 6.4 mm, 9.5 mm, 12.7 mm
 - Shrunk Diameter: Assortment
 - Colour: Black, Blue, Brown, Green/Yellow, Red, White, Yellow
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: Yes
 - Shrink Ratio: 2:1, 3:1
 - Material: Polyolefin
 - Flame Retardant: Yes



397679 2.4 mm, 3 mm,

**CABLE, HEATSHRINK, SLEEVE, BLUE
POLYOLEFIN, 1.2, BORE 1.6MM**

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Sleeve Diameter: 1.6 mm
 - Shrunk Diameter: 0.8 mm
 - Colour: Blue
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



397871 1.6 mm

**CABLE, HEATSHRINK, SLEEVE, BLUE
POLYOLEFIN, 1.2, BORE 2.4MM**

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Sleeve Diameter: 2.4 mm
 - Shrunk Diameter: 1.2 mm
 - Colour: Blue
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



397887 2.4 mm

**CABLE, HEATSHRINK, SLEEVE, BLUE
POLYOLEFIN, 1.2, BORE 3.2MM**

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Sleeve Diameter: 3.2 mm
 - Shrunk Diameter: 1.6 mm
 - Colour: Blue
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



397893 3.2 mm

**RS PRO HEAT SHRINK TUBING, BLUE
4.8MM SLEEVE DIA. X 1.2M LENGTH 2:1**

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Sleeve Diameter: 4.8 mm
 - Shrunk Diameter: 2.4 mm
 - Colour: Blue
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



397900 4.8 mm

**CABLE, HEATSHRINK, SLEEVE, BLUE
POLYOLEFIN, 1.2, BORE 9.5MM**

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Sleeve Diameter: 9.5 mm
 - Shrunk Diameter: 4.8 mm
 - Colour: Blue
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



397922 9.5 mm

**CABLE, HEATSHRINK, SLEEVE, BLUE
POLYOLEFIN, 1.2, BORE 6.4MM**

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Sleeve Diameter: 6.4 mm
 - Shrunk Diameter: 3.2 mm
 - Colour: Blue
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



397916 6.4 mm

**CABLE, HEATSHRINK, SLEEVE, BLUE
POLYOLEFIN, 1.2, BORE 12.7MM**

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Sleeve Diameter: 12.7 mm
 - Shrunk Diameter: 6.4 mm
 - Colour: Blue
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



397938 12.7 mm

**RS PRO HEAT SHRINK TUBING, BLUE
19.1MM SLEEVE DIA. X 1.2M LENGTH**

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Sleeve Diameter: 19.1 mm
 - Shrunk Diameter: 9.5 mm
 - Colour: Blue
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



397944 19.1 mm

**CABLE, HEATSHRINK, SLEEVE, BLUE
POLYOLEFIN, 1.2, BORE 25.4MM**


- ขนาดบรรจุภัณฑ์: **5 x EA**
- Sleeve Diameter: 25.4 mm
 - Shrunk Diameter: 12.7 mm
 - Colour: Blue
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



397950 25.4 mm

**CABLE, HEATSHRINK, SLEEVE, BLUE
POLYOLEFIN, 1.2, BORE 38.0MM**

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Sleeve Diameter: 38.1 mm
 - Shrunk Diameter: 19.1 mm
 - Colour: Blue
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



397966 38.1 mm

**RS PRO HEAT SHRINK TUBING, BLUE
50.8MM SLEEVE DIA. X 1.2M LENGTH**

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Sleeve Diameter: 50.8 mm
 - Shrunk Diameter: 25.4 mm
 - Colour: Blue
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



397972 50.8 mm

CABLE, HEATSHRINK, SLEEVE, RED, POLYOLEFIN, 1.2, BORE 1.6MM

- ขนาดบรรจุภัณฑ์: 5 x EA
- Sleeve Diameter: 1.6 mm
 - Shrink Diameter: 0.8 mm
 - Colour: Red
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



397988 1.6 mm

CABLE, HEATSHRINK, SLEEVE, RED, POLYOLEFIN, 1.2, BORE 2.4MM

- ขนาดบรรจุภัณฑ์: 5 x EA
- Sleeve Diameter: 2.4 mm
 - Shrink Diameter: 1.2 mm
 - Colour: Red
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



397994 2.4 mm

CABLE, HEATSHRINK, SLEEVE, GREEN/YELLOW, POLYOLEFIN, 1.2, BORE

- ขนาดบรรจุภัณฑ์: 5 x EA
- Sleeve Diameter: 25.4 mm
 - Shrink Diameter: 12.7 mm
 - Colour: Green
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



398032 25.4 mm

CABLE, HEATSHRINK, SLEEVE, GREEN/YELLOW, POLYOLEFIN, 1.2, BORE 19.0MM

- ขนาดบรรจุภัณฑ์: 5 x EA
- Sleeve Diameter: 19.1 mm
 - Shrink Diameter: 9.5 mm
 - Colour: Green
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



398048 19.1 mm

CABLE, HEATSHRINK, SLEEVE, GREEN/YELLOW, POLYOLEFIN, 1.2, BORE 12.7MM

- ขนาดบรรจุภัณฑ์: 5 x EA
- Sleeve Diameter: 12.7 mm
 - Shrink Diameter: 6.4 mm
 - Colour: Green
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



398054 12.7 mm

CABLE, HEATSHRINK, SLEEVE, GREEN/YELLOW, POLYOLEFIN, 1.2, BORE 9.5MM

- ขนาดบรรจุภัณฑ์: 5 x EA
- Sleeve Diameter: 9.5 mm
 - Shrink Diameter: 4.8 mm
 - Colour: Green
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



398060 9.5 mm

CABLE, HEATSHRINK, SLEEVE, GREEN/YELLOW, POLYOLEFIN, 1.2, BORE 6.4MM

- ขนาดบรรจุภัณฑ์: 5 x EA
- Sleeve Diameter: 6.4 mm
 - Shrink Diameter: 3.2 mm
 - Colour: Green
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



398076 6.4 mm

CABLE, HEATSHRINK, SLEEVE, GREEN/YELLOW, POLYOLEFIN, 1.2, BORE 4.8MM


- ขนาดบรรจุภัณฑ์: 5 x EA
- Sleeve Diameter: 4.8 mm
 - Shrink Diameter: 2.4 mm
 - Colour: Green, Yellow
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



398082 4.8 mm

CABLE, HEATSHRINK, SLEEVE, GREEN/YELLOW, POLYOLEFIN, 1.2, BORE 1.6MM

- ขนาดบรรจุภัณฑ์: 5 x EA
- Sleeve Diameter: 3.2 mm
 - Shrink Diameter: 1.6 mm
 - Colour: Green
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



398098 3.2 mm

CABLE, HEATSHRINK, SLEEVE, BLACK, POLYOLEFIN, 1.2, BORE 50.8MM

- ขนาดบรรจุภัณฑ์: 5 x EA
- Sleeve Diameter: 50.8 mm
 - Shrink Diameter: 25.4 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



398127 50.8 mm

CABLE, HEATSHRINK, SLEEVE, BLACK, POLYOLEFIN, 1.2, BORE 38.0MM

- ขนาดบรรจุภัณฑ์: 5 x EA
- Sleeve Diameter: 38.1 mm
 - Shrink Diameter: 19.1 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



398133 38.1 mm

CABLE, HEATSHRINK, SLEEVE, BLACK, POLYOLEFIN, 1.2, BORE 25.4MM

- ขนาดบรรจุภัณฑ์: 5 x EA
- Sleeve Diameter: 25.4 mm
 - Shrink Diameter: 12.7 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



398149 25.4 mm

CABLE, HEATSHRINK, SLEEVE, BLACK, POLYOLEFIN, 1.2, BORE 19.9MM

- ขนาดบรรจุภัณฑ์: 5 x EA
- Sleeve Diameter: 19.1 mm
 - Shrink Diameter: 9.5 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



398155 19.1 mm

CABLE, HEATSHRINK, SLEEVE, BLACK, POLYOLEFIN, 1.2, BORE 12.7MM

- ขนาดบรรจุภัณฑ์: 5 x EA
- Sleeve Diameter: 12.7 mm
 - Shrink Diameter: 6.4 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



398161 12.7 mm

CABLE, HEATSHRINK, SLEEVE, BLACK, POLYOLEFIN, 1.2, BORE 9.5MM

- ขนาดบรรจุภัณฑ์: 5 x EA
- Sleeve Diameter: 9.5 mm
 - Shrink Diameter: 4.8 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



398177 9.5 mm

CABLE, HEATSHRINK, SLEEVE, BLACK, POLYOLEFIN, 1.2, BORE 6.4MM

- ขนาดบรรจุภัณฑ์: 5 x EA
- Sleeve Diameter: 6.4 mm
 - Shrink Diameter: 3.2 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



398183 6.4 mm

CABLE, HEATSHRINK, SLEEVE, BLACK, POLYOLEFIN, 1.2, BORE 4.8MM

- ขนาดบรรจุภัณฑ์: 5 x EA
- Sleeve Diameter: 4.8 mm
 - Shrink Diameter: 2.4 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



398199 4.8 mm

CABLE, HEATSHRINK, SLEEVE, BLACK, POLYOLEFIN, 1.2, BORE 3.2MM

- ขนาดบรรจุภัณฑ์: 5 x EA
- Sleeve Diameter: 3.2 mm
 - Shrink Diameter: 1.6 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



398206 3.2 mm

CABLE, HEATSHRINK, SLEEVE, BLACK, POLYOLEFIN, 1.2, BORE 2.4MM

- ขนาดบรรจุภัณฑ์: 5 x EA
- Sleeve Diameter: 2.4 mm
 - Shrink Diameter: 1.2 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



398212 2.4 mm

CABLE, HEATSHRINK, SLEEVE, BLACK, POLYOLEFIN, 1.2, BORE 1.6MM

- ขนาดบรรจุภัณฑ์: 5 x EA
- Sleeve Diameter: 1.6 mm
 - Shrink Diameter: 0.8 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



398228 1.6 mm

CABLE, HEATSHRINK, SLEEVE, RED, POLYOLEFIN, 1.2, BORE 50.8MM

- ขนาดบรรจุภัณฑ์: 5 x EA
- Sleeve Diameter: 50.8 mm
 - Shrink Diameter: 25.4 mm
 - Colour: Red
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



398234 50.8 mm

CABLE, HEATSHRINK, SLEEVE, RED, POLYOLEFIN, 1.2, BORE 38.4MM

- ขนาดบรรจุภัณฑ์: 5 x EA
- Sleeve Diameter: 38.1 mm
 - Shrink Diameter: 19.1 mm
 - Colour: Red
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



398240 38.1 mm

CABLE, HEATSHRINK, SLEEVE, RED, POLYOLEFIN, 1.2, BORE 25.4MM

- ขนาดบรรจุภัณฑ์: 5 x EA
- Sleeve Diameter: 25.4 mm
 - Shrink Diameter: 12.7 mm
 - Colour: Red
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



398256 25.4 mm

CABLE, HEATSHRINK, SLEEVE, RED, POLYOLEFIN, 1.2, BORE 19.0MM

- ขนาดบรรจุภัณฑ์: 5 x EA
- Sleeve Diameter: 19.1 mm
 - Shrink Diameter: 9.5 mm
 - Colour: Red
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



398262 19.1 mm

CABLE, HEATSHRINK, SLEEVE, RED, POLYOLEFIN, 1.2, BORE 12.7MM

- ขนาดบรรจุภัณฑ์: 5 x EA
- Sleeve Diameter: 12.7 mm
 - Shrink Diameter: 6.4 mm
 - Colour: Red
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



398278 12.7 mm

CABLE, HEATSHRINK, SLEEVE, RED, POLYOLEFIN, 1.2, BORE 9.5MM

- ขนาดบรรจุภัณฑ์: 5 x EA
- Sleeve Diameter: 9.5 mm
 - Shrink Diameter: 4.8 mm
 - Colour: Red
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



398284 9.5 mm

CABLE, HEATSHRINK, SLEEVE, RED, POLYOLEFIN, 1.2, BORE 6.4MM

- ขนาดบรรจุภัณฑ์: 5 x EA
- Sleeve Diameter: 6.4 mm
 - Shrink Diameter: 3.2 mm
 - Colour: Red
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



398290 6.4 mm

CABLE, HEATSHRINK, SLEEVE, RED, POLYOLEFIN, 1.2, BORE 4.8MM

- ขนาดบรรจุภัณฑ์: 5 x EA
- Sleeve Diameter: 4.8 mm
 - Shrink Diameter: 2.4 mm
 - Colour: Red
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



398307 4.8 mm

RS PRO HEAT SHRINK TUBING, RED 3.2MM SLEEVE DIA. X 1.2M LENGTH 2:1

- ขนาดบรรจุภัณฑ์: 5 x EA
- Sleeve Diameter: 3.2 mm
 - Shrink Diameter: 1.6 mm
 - Colour: Red
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



398313 3.2 mm

CABLE, HEATSHRINK, SLEEVE, HIGH TEMP, POLYVINYLIDENE, BORE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sleeve Diameter: 25.4 mm
 - Shrink Diameter: 12.7 mm
 - Colour: Clear
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Fluoropolymer



398385 25.4 mm

CABLE, HEATSHRINK, SLEEVE, HIGH TEMP, POLYVINYLIDENE, BORE 19.0MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sleeve Diameter: 19.1 mm
 - Shrink Diameter: 9.5 mm
 - Colour: Clear
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Fluoropolymer



398391 19.1 mm

CABLE, HEATSHRINK, SLEEVE, HIGH TEMP, POLYVINYLIDENE, BORE 12.7MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sleeve Diameter: 12.7 mm
 - Shrink Diameter: 6.4 mm
 - Colour: Clear
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Fluoropolymer



398408 12.7 mm

CABLE, HEATSHRINK, SLEEVE, HIGH TEMP, POLYVINYLIDENE, BORE 9.5MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sleeve Diameter: 9.5 mm
 - Shrink Diameter: 4.8 mm
 - Colour: Clear
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Fluoropolymer



398414 9.5 mm

CABLE, HEATSHRINK, SLEEVE, HIGH TEMP, POLYVINYLIDENE, BORE 6.4MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sleeve Diameter: 6.4 mm
 - Shrink Diameter: 3.2 mm
 - Colour: Clear
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Fluoropolymer



398420 6.4 mm

CABLE, HEATSHRINK, SLEEVE, HIGH TEMP, POLYVINYLIDENE, BORE 4.8MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sleeve Diameter: 4.8 mm
 - Shrink Diameter: 2.4 mm
 - Colour: Clear
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Fluoropolymer



398436 4.8 mm

CABLE, HEATSHRINK, SLEEVE, HIGH TEMP, POLYVINYLIDENE, BORE 3.2MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sleeve Diameter: 3.2 mm
 - Shrink Diameter: 1.6 mm
 - Colour: Clear
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Fluoropolymer



398442 3.2 mm

CABLE, HEATSHRINK, SLEEVE, HIGH TEMP, POLYVINYLIDENE, BORE 2.4MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sleeve Diameter: 2.4 mm
 - Shrink Diameter: 1.2 mm
 - Colour: Clear
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Fluoropolymer



398458 2.4 mm

CABLE, HEATSHRINK, SLEEVE, HIGH TEMP, POLYVINYLIDENE, BORE 1.6MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sleeve Diameter: 1.6 mm
 - Shrink Diameter: 0.8 mm
 - Colour: Clear
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Fluoropolymer



398464 1.6 mm

CABLE, HEATSHRINK, SLEEVE, YELLOW POLYOLEFIN, 1.2, BORE 1.6MM

- ขนาดบรรจุภัณฑ์: 5 x EA
- Sleeve Diameter: 1.6 mm
 - Shrink Diameter: 0.8 mm
 - Colour: Yellow
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



399489 1.6 mm

CABLE, HEATSHRINK, SLEEVE, YELLOW POLYOLEFIN, 1.2, BORE 2.4MM

- ขนาดบรรจุภัณฑ์: 5 x EA
- Sleeve Diameter: 2.4 mm
 - Shrink Diameter: 1.2 mm
 - Colour: Yellow
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



399495 2.4 mm

CABLE, HEATSHRINK, SLEEVE, YELLOW POLYOLEFIN, 1.2, BORE 3.2MM

- ขนาดบรรจุภัณฑ์: 5 x EA
- Sleeve Diameter: 3.2 mm
 - Shrink Diameter: 1.6 mm
 - Colour: Yellow
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



399502 3.2 mm

RS PRO HEAT SHRINK TUBING, YELLOW 4.8MM SLEEVE DIA. X 1.2M

- ขนาดบรรจุภัณฑ์: 5 x EA
- Sleeve Diameter: 4.8 mm
 - Shrink Diameter: 2.4 mm
 - Colour: Yellow
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



399518 4.8 mm

RS PRO HEAT SHRINK TUBING, YELLOW 6.4MM SLEEVE DIA. X 1.2M

- ขนาดบรรจุภัณฑ์: 5 x EA
- Sleeve Diameter: 6.4 mm
 - Shrink Diameter: 3.2 mm
 - Colour: Yellow
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



399524 6.4 mm

RS PRO HEAT SHRINK TUBING, YELLOW 9.5MM SLEEVE DIA. X 1.2M

- ขนาดบรรจุภัณฑ์: 5 x EA
- Sleeve Diameter: 9.5 mm
 - Shrink Diameter: 4.8 mm
 - Colour: Yellow
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



399619 9.5 mm

CABLE, HEATSHRINK, SLEEVE, YELLOW POLYOLEFIN, 1.2, BORE 12.7MM

- ขนาดบรรจุภัณฑ์: 5 x EA
- Sleeve Diameter: 12.7 mm
 - Shrink Diameter: 6.4 mm
 - Colour: Yellow
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



399625 12.7 mm

RS PRO HEAT SHRINK TUBING, YELLOW 19.1MM SLEEVE DIA. X 1.2M

- ขนาดบรรจุภัณฑ์: 5 x EA
- Sleeve Diameter: 19.1 mm
 - Shrink Diameter: 9.5 mm
 - Colour: Yellow
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



399631 19.1 mm

RS PRO HEAT SHRINK TUBING, YELLOW 25.4MM SLEEVE DIA. X 1.2M

- ขนาดบรรจุภัณฑ์: 5 x EA
- Sleeve Diameter: 25.4 mm
 - Shrink Diameter: 12.7 mm
 - Colour: Yellow
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



399647 25.4 mm

RS PRO HEAT SHRINK TUBING, YELLOW 38.1MM SLEEVE DIA. X 1.2M

- ขนาดบรรจุภัณฑ์: 5 x EA
- Sleeve Diameter: 38.1 mm
 - Shrink Diameter: 19.1 mm
 - Colour: Yellow
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



399653 38.1 mm

RS PRO HEAT SHRINK TUBING, YELLOW 50.8MM SLEEVE DIA. X 1.2M

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Sleeve Diameter: 50.8 mm
 - Shrink Diameter: 25.4 mm
 - Colour: Yellow
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



399669 50.8 mm

CABLE, HEATSHRINK, SLEEVE, CLEAR, P OLYOLEFIN, 1.2M BORE 1.6MM

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Sleeve Diameter: 1.6 mm
 - Shrink Diameter: 0.8 mm
 - Colour: Clear
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



399899 1.6 mm

CABLE, HEATSHRINK, SLEEVE, CLEAR, P OLYOLEFIN, 1.2M BORE 2.4MM

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Sleeve Diameter: 2.4 mm
 - Shrink Diameter: 1.2 mm
 - Colour: Clear
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



399906 2.4 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, CLEAR 3.2MM SLEEVE DIA. X

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Sleeve Diameter: 3.2 mm
 - Shrink Diameter: 1.6 mm
 - Colour: Clear
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



399912 3.2 mm

CABLE, HEATSHRINK, SLEEVE, CLEAR, P OLYOLEFIN, 1.2M BORE 4.8MM

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Sleeve Diameter: 4.8 mm
 - Shrink Diameter: 2.4 mm
 - Colour: Clear
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



399928 4.8 mm

CABLE, HEATSHRINK, SLEEVE, CLEAR, P OLYOLEFIN, 1.2M BORE 6.4MM

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Sleeve Diameter: 6.4 mm
 - Shrink Diameter: 3.2 mm
 - Colour: Clear
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



399934 6.4 mm

CABLE, HEATSHRINK, SLEEVE, CLEAR, P OLYOLEFIN, 1.2M BORE 9.5MM

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Sleeve Diameter: 9.5 mm
 - Shrink Diameter: 4.8 mm
 - Colour: Clear
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



399940 9.5 mm

CABLE, HEATSHRINK, SLEEVE, CLEAR, P OLYOLEFIN, 1.2M BORE 12.7MM

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Sleeve Diameter: 12.7 mm
 - Shrink Diameter: 6.4 mm
 - Colour: Clear
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



399956 12.7 mm

CABLE, HEATSHRINK, SLEEVE, CLEAR, P OLYOLEFIN, 1.2M BORE 19.0MM

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Sleeve Diameter: 19.1 mm
 - Shrink Diameter: 9.5 mm
 - Colour: Clear
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



399962 19.1 mm

CABLE, HEATSHRINK, SLEEVE, CLEAR, P OLYOLEFIN, 1.2M BORE 25.4MM

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Sleeve Diameter: 25.4 mm
 - Shrink Diameter: 12.7 mm
 - Colour: Clear
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



399978 25.4 mm

CABLE, HEATSHRINK, SLEEVE, CLEAR, P OLYOLEFIN, 1.2M BORE 38.0MM

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Sleeve Diameter: 38.1 mm
 - Shrink Diameter: 19.1 mm
 - Colour: Clear
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



399984 38.1 mm

CABLE, HEATSHRINK, SLEEVE, CLEAR, P OLYOLEFIN, 1.2M BORE 50.8MM

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Sleeve Diameter: 50.8 mm
 - Shrink Diameter: 25.4 mm
 - Colour: Clear
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



399990 50.8 mm

RS PRO ADHESIVE LINED HEAT SHRINK TUBING, BLUE, RED, WHITE,

- ขนาดบรรจุภัณฑ์: **1 x KT**
- Sleeve Diameter: 12.7 mm, 19.1 mm, 25.4 mm, 38.1 mm
 - Shrink Diameter: Set
 - Colour: Blue, Red, White, Yellow
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: Yes
 - Shrink Ratio: 2:1, 3:1
 - Sleeve Length: Set
 - Material: Polyolefin



562640 12.7 mm, 19.1 mm,

TERMINATION KIT

- ขนาดบรรจุภัณฑ์: **1 x KT**
- Sleeve Diameter: 3.2 mm, 4.8 mm, 6.4 mm, 9.5 mm
 - Shrink Diameter: Assortment
 - Colour: Black, Blue, Green/Yellow, Red, White
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: Yes
 - Shrink Ratio: 2:1
 - Sleeve Length: 110 mm
 - Material: Polyolefin



562646 3.2 mm, 4.8 mm,

RS PRO HEAT SHRINK TUBING, BLACK, BLUE, GREEN/YELLOW, RED,

- ขนาดบรรจุภัณฑ์: **1 x KT**
- Sleeve Diameter: 6.4 mm, 9.5 mm, 12.7 mm, 19.1 mm, 25.4 mm
 - Shrink Diameter: Assortment
 - Colour: Black, Blue, Green/Yellow, Red, White
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: Longueurs assorties
 - Material: Polyolefin



562652 6.4 mm, 9.5 mm,

DUAL WALL, HEATSHRINK W3NH BLACK 40/13

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 40 mm
 - Shrink Diameter: 13 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: Yes
 - Shrink Ratio: 3:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



562656 40 mm

DUAL WALL, HEATSHRINK W3NH BLACK 19/6

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 19.1 mm
 - Shrunk Diameter: 6 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: Yes
 - Shrink Ratio: 3:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



562662 19.1 mm

DUAL WALL, HEATSHRINK W3NH BLACK 12/4

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 12.7 mm
 - Shrunk Diameter: 4 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: Yes
 - Shrink Ratio: 3:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



562668 12.7 mm

DUAL WALL, HEATSHRINK W3NH BLACK 9/3

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 9 mm
 - Shrunk Diameter: 3 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: Yes
 - Shrink Ratio: 3:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



562678 9 mm

DUAL WALL, HEATSHRINK W3NH BLACK 6/2

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 6.4 mm
 - Shrunk Diameter: 2 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: Yes
 - Shrink Ratio: 3:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



562684 6.4 mm

CABLE, HEATSHRINK, SLEEVE, BLACK, POLYOLEFIN, 1.6MM

- ขนาดบรรจุภัณฑ์: **25 x EA**
- Sleeve Diameter: 1.6 mm
 - Shrunk Diameter: 0.8 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 25 m
 - Material: Polyolefin



666852 1.6 mm

RS PRO HEAT SHRINK TUBING, BLACK 2.4MM SLEEVE DIA. X 25M LENGTH 2:1

- ขนาดบรรจุภัณฑ์: **25 x EA**
- Sleeve Diameter: 2.4 mm
 - Shrunk Diameter: 1.2 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 25 m
 - Material: Polyolefin



666868 2.4 mm

CABLE, HEATSHRINK, SLEEVE, BLACK, POLYOLEFIN, 3.2MM

- ขนาดบรรจุภัณฑ์: **20 x EA**
- Sleeve Diameter: 3.2 mm
 - Shrunk Diameter: 1.6 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 20 m
 - Material: Polyolefin



666874 3.2 mm

CABLE, HEATSHRINK, SLEEVE, BLACK, POLYOLEFIN, 4.8MM

- ขนาดบรรจุภัณฑ์: **20 x EA**
- Sleeve Diameter: 4.8 mm
 - Shrunk Diameter: 2.4 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 20 m
 - Material: Polyolefin



666880 4.8 mm

RS PRO HEAT SHRINK TUBING, BLACK 6.4MM SLEEVE DIA. X 15M LENGTH 2:1

- ขนาดบรรจุภัณฑ์: **15 x EA**
- Sleeve Diameter: 6.4 mm
 - Shrunk Diameter: 3.2 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 15 m
 - Material: Polyolefin



666896 6.4 mm

CABLE, HEATSHRINK, SLEEVE, BLACK, POLYOLEFIN, 9.5MM

- ขนาดบรรจุภัณฑ์: **12 x EA**
- Sleeve Diameter: 9.5 mm
 - Shrunk Diameter: 4.8 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 12 m
 - Material: Polyolefin



666903 9.5 mm

CABLE, HEATSHRINK, SLEEVE, BLACK, POLYOLEFIN, 12.7MM

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Sleeve Diameter: 12.7 mm
 - Shrunk Diameter: 6.4 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 10 m
 - Material: Polyolefin



666919 12.7 mm

CABLE, HEATSHRINK, SLEEVE, BLACK, POLYOLEFIN, 19.0MM

- ขนาดบรรจุภัณฑ์: **6 x MTR**
- Sleeve Diameter: 19.1 mm
 - Shrunk Diameter: 9.5 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 6 m
 - Material: Polyolefin



666925 19.1 mm

CABLE, HEATSHRINK, SLEEVE, BLACK, POLYOLEFIN, 25.4MM

- ขนาดบรรจุภัณฑ์: **3 x EA**
- Sleeve Diameter: 25.4 mm
 - Shrunk Diameter: 12.7 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 3 m
 - Material: Polyolefin



666931 25.4 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, BLACK 1.6MM SLEEVE DIA. X

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Sleeve Diameter: 1.6 mm
 - Shrunk Diameter: 0.8 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



2116191 1.6 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, BLACK 2.4MM SLEEVE DIA. X

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Sleeve Diameter: 2.4 mm
 - Shrunk Diameter: 1.2 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



2116208 2.4 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, BLACK 3.2MM SLEEVE DIA. X

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Sleeve Diameter: 3.2 mm
 - Shrunk Diameter: 1.6 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



2116214 3.2 mm

CABLE, HEATSHRINK, LSF, ZERO HALOGEN 2:1, 4.8MM DIA

- ขนาดบรรจุภัณฑ์: 5 x EA
- Sleeve Diameter: 4.8 mm
 - Shrink Diameter: 2.4 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



2116220 4.8 mm

CABLE, HEATSHRINK, LSF, ZERO HALOGEN 2:1, 6.4MM DIA

- ขนาดบรรจุภัณฑ์: 5 x EA
- Sleeve Diameter: 6.4 mm
 - Shrink Diameter: 3.2 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



2116236 6.4 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, BLACK 9.5MM SLEEVE DIA. X

- ขนาดบรรจุภัณฑ์: 5 x EA
- Sleeve Diameter: 9.5 mm
 - Shrink Diameter: 4.8 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



2116242 9.5 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, BLACK 12.7MM SLEEVE DIA. X

- ขนาดบรรจุภัณฑ์: 5 x EA
- Sleeve Diameter: 12.7 mm
 - Shrink Diameter: 6.4 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



2116258 12.7 mm

CABLE, HEATSHRINK, LSF, ZERO HALOGEN 2:1, 19.1MM DIA

- ขนาดบรรจุภัณฑ์: 5 x EA
- Sleeve Diameter: 19.1 mm
 - Shrink Diameter: 9.5 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



2116270 19.1 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, BLACK 38.1MM SLEEVE DIA. X

- ขนาดบรรจุภัณฑ์: 5 x EA
- Sleeve Diameter: 38.1 mm
 - Shrink Diameter: 19.1 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



2116292 38.1 mm

RS PRO HEAVY WALL ADHESIVE LINED HEAT SH

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sleeve Diameter: 13 mm
 - Shrink Diameter: 4 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: Yes
 - Shrink Ratio: 3:1
 - Sleeve Length: 1.22 m



2269083 13 mm

RS PRO HEAVY WALL ADHESIVE LINED HEAT SH

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sleeve Diameter: 22 mm
 - Shrink Diameter: 6 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: Yes
 - Shrink Ratio: 3:1
 - Sleeve Length: 1.22 m



2269084 22 mm

RS PRO HIGH RATIO HEAVY WALL HEAT SHRINK

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sleeve Diameter: 19 mm
 - Shrink Diameter: 3.2 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: Yes
 - Shrink Ratio: 6:1
 - Sleeve Length: 1.22 m



2269089 19 mm

RS PRO HIGH RATIO HEAVY WALL HEAT SHRINK

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sleeve Diameter: 33 mm
 - Shrink Diameter: 5.5 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: Yes
 - Shrink Ratio: 6:1
 - Sleeve Length: 1.22 m



2269090 33 mm

RS PRO HIGH RATIO HEAVY WALL HEAT SHRINK

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sleeve Diameter: 33 mm
 - Shrink Diameter: 5.5 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: Yes
 - Shrink Ratio: 6:1
 - Sleeve Length: 254 mm



2269091 33 mm

RS PRO HIGH RATIO HEAVY WALL HEAT SHRINK

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sleeve Diameter: 45 mm
 - Shrink Diameter: 7.4 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: Yes
 - Shrink Ratio: 6:1
 - Sleeve Length: 254 mm



2269092 45 mm

RS PRO HIGH RATIO HEAVY WALL HEAT SHRINK

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sleeve Diameter: 45 mm
 - Shrink Diameter: 7.4 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: Yes
 - Shrink Ratio: 6:1
 - Sleeve Length: 1.22 m



2269093 45 mm

RS PRO HIGH RATIO HEAVY WALL HEAT SHRINK

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sleeve Diameter: 51 mm
 - Shrink Diameter: 8.3 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: Yes
 - Shrink Ratio: 6:1
 - Sleeve Length: 1.22 m



2269095 51 mm

RS PRO HIGH RATIO HEAVY WALL HEAT SHRINK

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sleeve Diameter: 70 mm
 - Shrink Diameter: 11.7 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: Yes
 - Shrink Ratio: 6:1
 - Sleeve Length: 254 mm



2269097 70 mm

RS PRO MEDIUM WALL ADHESIVE LINED HEAT S

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sleeve Diameter: 12 mm
 - Shrink Diameter: 3 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: Yes
 - Shrink Ratio: 3:1
 - Sleeve Length: 1.22 m



2269098 12 mm

RS PRO MEDIUM WALL ADHESIVE LINED HEAT S

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 16 mm
 - Shrink Diameter: 5 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: Yes
 - Shrink Ratio: 3:1
 - Sleeve Length: 1.22 m



2269099 16 mm

RS PRO MEDIUM WALL ADHESIVE LINED HEAT S

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 19 mm
 - Shrink Diameter: 5 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: Yes
 - Shrink Ratio: 3:1
 - Sleeve Length: 1.22 m



2269101 19 mm

RS PRO MEDIUM WALL ADHESIVE LINED HEAT S

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 33 mm
 - Shrink Diameter: 8 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: Yes
 - Shrink Ratio: 3:1
 - Sleeve Length: 1.22 m



2269102 33 mm

RS PRO MEDIUM WALL ADHESIVE LINED HEAT S

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 115 mm
 - Shrink Diameter: 34 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: Yes
 - Shrink Ratio: 3:1
 - Sleeve Length: 1.22 m



2269106 115 mm

RS PRO HEAT SHRINK TUBING, BLACK 1.6MM S

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 2 mm
 - Shrink Diameter: 0.8 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 12 m
 - Material: Polyolefin



2269107 2 mm

RS PRO HEAT SHRINK TUBING, BLACK 3MM SLE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 3.5 mm
 - Shrink Diameter: 1.5 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 10 m
 - Material: Polyolefin



2269108 3.5 mm

RS PRO HEAT SHRINK TUBING, BLACK 6MM SLE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 6.5 mm
 - Shrink Diameter: 3 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 7.5 m
 - Material: Polyolefin



2269111 6.5 mm

RS PRO HEAT SHRINK TUBING, BLACK 9MM SLE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 9.6 mm
 - Shrink Diameter: 4.5 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 5 m
 - Material: Polyolefin



2269112 9.6 mm

RS PRO HEAT SHRINK TUBING, BLACK 12.7MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 12.7 mm
 - Shrink Diameter: 6 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 5 m
 - Material: Polyolefin



2269113 12.7 mm

RS PRO HEAT SHRINK TUBING, BLACK 18MM SL

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 19 mm
 - Shrink Diameter: 9 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 5 m
 - Material: Polyolefin



2269114 19 mm

RS PRO HEAT SHRINK TUBING, BLACK 12MM SLEEVE DIA. X 5M LENGTH 3:1

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 12 mm
 - Shrink Diameter: 4 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 3:1
 - Sleeve Length: 5 m
 - Material: Polyolefin



2269118 12 mm

RS PRO ADHESIVE LINED HEAT SHRINK TUBING, BLACK 3.2MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 3.2 mm
 - Shrink Diameter: 1 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: Yes
 - Shrink Ratio: 3:1
 - Sleeve Length: 3 m



2269139 3.2 mm

RS PRO ADHESIVE LINED HEAT SHRINK TUBING

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 25 mm
 - Shrink Diameter: 8 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: Yes
 - Shrink Ratio: 3:1
 - Sleeve Length: 3 m



2269140 25 mm

RS PRO ADHESIVE LINED HEAT SHRINK TUBING

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 25 mm
 - Shrink Diameter: 8 mm
 - Colour: Clear
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: Yes
 - Shrink Ratio: 3:1
 - Sleeve Length: 3 m



2269141 25 mm

BLACK ADHESIVE LINED TUBING, 6-2MM I/D

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 6.4 mm
 - Shrink Diameter: 2 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink Tubing
 - Adhesive Lined: Yes
 - Shrink Ratio: 3:1
 - Sleeve Length: 1.22 m
 - Material: Polyolefin



2345886 6.4 mm

RS PRO ADHESIVE LINED HEAT SHRINK TUBING, BLACK 12.7MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 12.7 mm
 - Shrink Diameter: 4 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink Tubing
 - Adhesive Lined: Yes
 - Shrink Ratio: 3:1
 - Sleeve Length: 1.22 m
 - Material: Polyolefin



2345887 12.7 mm

RS PRO ADHESIVE LINED HEAT SHRINK TUBING, BLACK 19.1MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 19.1 mm
 - Shrunk Diameter: 6 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink Tubing
 - Adhesive Lined: Yes
 - Shrink Ratio: 3:1
 - Sleeve Length: 1.22 m
 - Material: Polyolefin



2345889 19.1 mm

RS PRO ADHESIVE LINED HEAT SHRINK TUBING, BLACK 4.8MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 4.8 mm
 - Shrunk Diameter: 1.6 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink Tubing
 - Adhesive Lined: Yes
 - Shrink Ratio: 3:1
 - Sleeve Length: 1.22 m
 - Material: Polyolefin



2345892 4.8 mm

BLACK ADHESIVE LINED TUBING, 4-1MM I/D

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 4 mm
 - Shrunk Diameter: 1 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink Tubing
 - Adhesive Lined: Yes
 - Shrink Ratio: 4:1
 - Sleeve Length: 1.22 m
 - Material: Polyolefin



2345893 4 mm

RS PRO ADHESIVE LINED HEAT SHRINK TUBING, BLACK 8MM SLEEVE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 8 mm
 - Shrunk Diameter: 2 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink Tubing
 - Adhesive Lined: Yes
 - Shrink Ratio: 4:1
 - Sleeve Length: 1.22 m
 - Material: Polyolefin



2345895 8 mm

RS PRO ADHESIVE LINED HEAT SHRINK TUBING, BLACK 12MM SLEEVE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 12 mm
 - Shrunk Diameter: 3 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink Tubing
 - Adhesive Lined: Yes
 - Shrink Ratio: 4:1
 - Sleeve Length: 1.22 m
 - Material: Polyolefin



2345896 12 mm

BLACK ADHESIVE LINED TUBING, 16-4MM I/D

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 16 mm
 - Shrunk Diameter: 4 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink Tubing
 - Adhesive Lined: Yes
 - Shrink Ratio: 4:1
 - Sleeve Length: 1.22 m
 - Material: Polyolefin



2345897 16 mm

BLACK ADHESIVE LINED TUBING, 24-6MM I/D

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 24 mm
 - Shrunk Diameter: 6 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink Tubing
 - Adhesive Lined: Yes
 - Shrink Ratio: 4:1
 - Sleeve Length: 1.22 m
 - Material: Polyolefin



2345898 24 mm

BLACK ADHESIVE LINED TUBING, 32-8MM I/D

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 32 mm
 - Shrunk Diameter: 8 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink Tubing
 - Adhesive Lined: Yes
 - Shrink Ratio: 4:1
 - Sleeve Length: 1.22 m
 - Material: Polyolefin



2345899 32 mm

ADHESIVE LINED HEATSHRINK TUBING, 3MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 3.2 mm
 - Shrunk Diameter: 1 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink Tubing
 - Adhesive Lined: Yes
 - Shrink Ratio: 3:1
 - Sleeve Length: 1.22 m
 - Material: Polyolefin



2345901 3.2 mm

ADHESIVE LINED HEATSHRINK TUBING, 6MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 6.4 mm
 - Shrunk Diameter: 2 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink Tubing
 - Adhesive Lined: Yes
 - Shrink Ratio: 3:1
 - Sleeve Length: 1.22 m
 - Material: Polyolefin



2345902 6.4 mm

BLACK HEATSHRINK TUBING, 1.2MM BORE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 1.2 mm
 - Shrunk Diameter: 0.6 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink Tubing
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.22 m
 - Material: Polyolefin



2345906 1.2 mm

RS PRO HEAT SHRINK TUBE, CLEAR 1.2MM SLEEVE DIA. X 1.22M LENGTH

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 1.2 mm
 - Shrunk Diameter: 0.6 mm
 - Colour: Clear
 - Sleeve Type: Heat Shrink Tubing
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.22 m
 - Material: Polyolefin



2345907 1.2 mm

BLACK HEATSHRINK TUBING, 1.6MM BORE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 1.6 mm
 - Shrunk Diameter: 0.8 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink Tubing
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.22 m
 - Material: Polyolefin



2345908 1.6 mm

BLACK HEATSHRINK TUBING, 2.4MM BORE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 2.4 mm
 - Shrunk Diameter: 1.2 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink Tubing
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.22 m
 - Material: Polyolefin



2345909 2.4 mm

RS PRO HEAT SHRINK TUBE, CLEAR 3.2MM SLEEVE DIA. X 1.22M LENGTH

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 3.2 mm
 - Shrunk Diameter: 1.6 mm
 - Colour: Clear
 - Sleeve Type: Heat Shrink Tubing
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.22 m
 - Material: Polyolefin



2345911 3.2 mm

BLACK HEATSHRINK TUBING, 4.8MM BORE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 4.8 mm
 - Shrunk Diameter: 2.4 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink Tubing
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.22 m
 - Material: Polyolefin



2345912 4.8 mm

RS PRO HEAT SHRINK TUBE, CLEAR 4.8MM SLEEVE DIA. X 1.22M LENGTH

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sleeve Diameter: 4.8 mm
 - Shrink Diameter: 2.4 mm
 - Colour: Clear
 - Sleeve Type: Heat Shrink Tubing
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.22 m
 - Material: Polyolefin



2345913 4.8 mm

RS PRO HEAT SHRINK TUBE, BLACK 6.4MM SLEEVE DIA. X 1.22M LENGTH

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sleeve Diameter: 6.4 mm
 - Shrink Diameter: 3.2 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink Tubing
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.22 m
 - Material: Polyolefin



2345914 6.4 mm

RS PRO HEAT SHRINK TUBE, BLACK 9.5MM SLEEVE DIA. X 1.22M LENGTH

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sleeve Diameter: 9.5 mm
 - Shrink Diameter: 4.8 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink Tubing
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.22 m
 - Material: Polyolefin



2345916 9.5 mm

RS PRO HEAT SHRINK TUBE, BLACK 12.7MM SLEEVE DIA. X 1.22M LENGTH

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sleeve Diameter: 12.7 mm
 - Shrink Diameter: 6.4 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink Tubing
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.22 m
 - Material: Polyolefin



2345919 12.7 mm

BLACK HEATSHRINK TUBING,19MM BORE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sleeve Diameter: 19.1 mm
 - Shrink Diameter: 9.5 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink Tubing
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.22 m
 - Material: Polyolefin



2345921 19.1 mm

RS PRO HEAT SHRINK TUBE, CLEAR 19.1MM SLEEVE DIA. X 1.22M LENGTH

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sleeve Diameter: 19.1 mm
 - Shrink Diameter: 9.5 mm
 - Colour: Clear
 - Sleeve Type: Heat Shrink Tubing
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.22 m
 - Material: Polyolefin



2345922 19.1 mm

BLACK HEATSHRINK TUBING,25.4MM BORE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sleeve Diameter: 25.4 mm
 - Shrink Diameter: 12.7 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink Tubing
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.22 m
 - Material: Polyolefin



2345924 25.4 mm

RS PRO HEAT SHRINK TUBE, CLEAR 25.4MM SLEEVE DIA. X 1.22M LENGTH

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sleeve Diameter: 25.4 mm
 - Shrink Diameter: 12.7 mm
 - Colour: Clear
 - Sleeve Type: Heat Shrink Tubing
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.22 m
 - Material: Polyolefin



2345925 25.4 mm

BLACK HEATSHRINK TUBING,51MM BORE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sleeve Diameter: 50.8 mm
 - Shrink Diameter: 25.4 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink Tubing
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.22 m
 - Material: Polyolefin



2345928 50.8 mm

RS PRO HEAT SHRINK TUBE, CLEAR 50.8MM SLEEVE DIA. X 1.22M LENGTH

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sleeve Diameter: 50.8 mm
 - Shrink Diameter: 25.4 mm
 - Colour: Clear
 - Sleeve Type: Heat Shrink Tubing
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.22 m
 - Material: Polyolefin



2345929 50.8 mm

RS PRO HEAT SHRINK TUBE, BLACK 76.2MM SLEEVE DIA. X 1.22M LENGTH

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sleeve Diameter: 76.2 mm
 - Shrink Diameter: 38.1 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink Tubing
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.22 m
 - Material: Polyolefin



2345930 76.2 mm

BLACK HEATSHRINK TUBING,101.6MM BORE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sleeve Diameter: 101.6 mm
 - Shrink Diameter: 50.8 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink Tubing
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.22 m
 - Material: Polyolefin



2345931 101.6 mm

RNF 3000 HEATSHRINK

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sleeve Diameter: 3 mm
 - Shrink Diameter: 1 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink Tubing
 - Adhesive Lined: No
 - Shrink Ratio: 3:1
 - Sleeve Length: 1.22 m
 - Material: Polyolefin



2345932 3 mm

RS PRO HEAT SHRINK TUBE, BLACK 9.1MM SLEEVE DIA. X 1.22M LENGTH

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sleeve Diameter: 9.1 mm
 - Shrink Diameter: 3 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink Tubing
 - Adhesive Lined: No
 - Shrink Ratio: 3:1
 - Sleeve Length: 1.22 m
 - Material: Polyolefin



2345933 9.1 mm

RS PRO HEAT SHRINK TUBE, BLACK 25MM SLEEVE DIA. X 1.22M LENGTH

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sleeve Diameter: 25 mm
 - Shrink Diameter: 8 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink Tubing
 - Adhesive Lined: No
 - Shrink Ratio: 3:1
 - Sleeve Length: 1.22 m
 - Material: Polyolefin



2345935 25 mm

RS PRO HEAT SHRINK TUBE, CLEAR 1.2MM SLEEVE DIA. X 1.2M LENGTH 2:1

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sleeve Diameter: 1.2 mm
 - Shrink Diameter: 0.6 mm
 - Colour: Clear
 - Sleeve Type: Heat Shrink Tubing
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyvinylidene Fluoride



2345936 1.2 mm

CLEAR HEATSHRINK TUBING,2.4MM I/D

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 2.4 mm
 - Shrink Diameter: 1.2 mm
 - Colour: Clear
 - Sleeve Type: Heat Shrink Tubing
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyvinylidene Fluoride



2345937 2.4 mm

RS PRO HEAT SHRINK TUBE, CLEAR 6.4MM SLEEVE DIA. X 1.2M LENGTH 2:1

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 6.4 mm
 - Shrink Diameter: 3.2 mm
 - Colour: Clear
 - Sleeve Type: Heat Shrink Tubing
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyvinylidene Fluoride



2345938 6.4 mm

RS PRO HEAT SHRINK TUBE, CLEAR 9.5MM SLEEVE DIA. X 1.2M LENGTH 2:1

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 9.5 mm
 - Shrink Diameter: 4.8 mm
 - Colour: Clear
 - Sleeve Type: Heat Shrink Tubing
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyvinylidene Fluoride



2345940 9.5 mm

RS PRO HEAT SHRINK TUBE, CLEAR 12.7MM SLEEVE DIA. X 1.2M LENGTH

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 12.7 mm
 - Shrink Diameter: 6.4 mm
 - Colour: Clear
 - Sleeve Type: Heat Shrink Tubing
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyvinylidene Fluoride



2345941 12.7 mm

CLEAR HEATSHRINK TUBING,19.0MM I/D

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 19.1 mm
 - Shrink Diameter: 9.5 mm
 - Colour: Clear
 - Sleeve Type: Heat Shrink Tubing
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyvinylidene Fluoride



2345942 19.1 mm

CLEAR HEATSHRINK TUBING,4.8MM I/D

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 4.8 mm
 - Shrink Diameter: 2.4 mm
 - Colour: Clear
 - Sleeve Type: Heat Shrink Tubing
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyvinylidene Fluoride



2345944 4.8 mm

RS PRO HEAT SHRINK TUBING, TRANSPARENT 1.2MM SLEEVE DIA. X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 1.2 mm
 - Shrink Diameter: 0.6 mm
 - Colour: Transparent
 - Sleeve Type: Heat Shrink Tubing
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyvinylidene Fluoride



2345946 1.2 mm

RS PRO HEAT SHRINK TUBING, CLEAR 2MM SLEEVE DIA. X 1.22M LENGTH 4:1

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 2 mm
 - Shrink Diameter: 0.5 mm
 - Colour: Clear
 - Sleeve Type: Heat Shrink Tubing
 - Adhesive Lined: No
 - Shrink Ratio: 4:1
 - Sleeve Length: 1.22 m
 - Material: PTFE



2345955 2 mm

RS PRO HEAT SHRINK TUBING, CLEAR 3.5MM SLEEVE DIA. X 1.22M LENGTH

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 3.5 mm
 - Shrink Diameter: 0.85 mm
 - Colour: Clear
 - Sleeve Type: Heat Shrink Tubing
 - Adhesive Lined: No
 - Shrink Ratio: 4:1
 - Sleeve Length: 1.22 m
 - Material: PTFE



2345956 3.5 mm

HIGH TEMP HEATSHRINK TUBING,6.4MM I/D

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 6 mm
 - Shrink Diameter: 1.5 mm
 - Colour: Clear
 - Sleeve Type: Heat Shrink Tubing
 - Adhesive Lined: No
 - Shrink Ratio: 4:1
 - Sleeve Length: 1.22 m
 - Material: PTFE



2345957 6 mm

RS PRO HEAT SHRINK TUBING, CLEAR 9.5MM SLEEVE DIA. X 1.22M LENGTH

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 9.5 mm
 - Shrink Diameter: 2.8 mm
 - Colour: Clear
 - Sleeve Type: Heat Shrink Tubing
 - Adhesive Lined: No
 - Shrink Ratio: 4:1
 - Sleeve Length: 1.22 m
 - Material: PTFE



2345958 9.5 mm

CABLE,HEATSHRINK,ADHESIVE LINED,40/13 RED

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 40 mm
 - Shrink Diameter: 13 mm
 - Colour: Red
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: Yes
 - Shrink Ratio: 3:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



2417602 40 mm

CABLE,HEATSHRINK,ADHESIVE LINED,40/13 WHITE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 40 mm
 - Shrink Diameter: 13 mm
 - Colour: White
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: Yes
 - Shrink Ratio: 3:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



2417618 40 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, YELLOW 38.1MM SLEEVE DIA.

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 38.1 mm
 - Shrink Diameter: 19.1 mm
 - Colour: Yellow
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



2672051 38.1 mm

CABLE,HEATSHRINK,MEDIUM WALL,LFH,2:1,BLUE,3.2MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 3.2 mm
 - Shrink Diameter: 1.6 mm
 - Colour: Blue
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



2672089 3.2 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, BLUE 4.8MM SLEEVE DIA. X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 4.8 mm
 - Shrink Diameter: 2.4 mm
 - Colour: Blue
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



2672095 4.8 mm

CABLE, HEATSHRINK, MEDIUM WALL, LFH, 2:1, BLUE, 6.4MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sleeve Diameter: 6.4 mm
 - Shrink Diameter: 3.2 mm
 - Colour: Blue
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



2672102 6.4 mm

CABLE, HEATSHRINK, MEDIUM WALL, LFH, 2:1, BLUE, 9.5MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sleeve Diameter: 9.5 mm
 - Shrink Diameter: 4.8 mm
 - Colour: Blue
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



2672118 9.5 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, BLUE 12.7MM SLEEVE DIA. X

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sleeve Diameter: 12.7 mm
 - Shrink Diameter: 6.4 mm
 - Colour: Blue
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



2672124 12.7 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, BLUE 19.1MM SLEEVE DIA. X

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sleeve Diameter: 19.1 mm
 - Shrink Diameter: 9.5 mm
 - Colour: Blue
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



2672130 19.1 mm

CABLE, HEATSHRINK, MEDIUM WALL, LFH, 2:1, BLUE, 25.4MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sleeve Diameter: 25.4 mm
 - Shrink Diameter: 12.7 mm
 - Colour: Blue
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



2672146 25.4 mm

CABLE, HEATSHRINK, MEDIUM WALL, LFH, 2:1, BLUE, 38MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sleeve Diameter: 38.1 mm
 - Shrink Diameter: 19.1 mm
 - Colour: Blue
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



2672152 38.1 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, RED 1.6MM SLEEVE DIA. X

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sleeve Diameter: 1.6 mm
 - Shrink Diameter: 0.8 mm
 - Colour: Red
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



2672168 1.6 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, RED 2.4MM SLEEVE DIA. X

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sleeve Diameter: 2.4 mm
 - Shrink Diameter: 1.2 mm
 - Colour: Red
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



2672174 2.4 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, RED 3.2MM SLEEVE DIA. X

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sleeve Diameter: 3.2 mm
 - Shrink Diameter: 1.6 mm
 - Colour: Red
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



2672180 3.2 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, RED 4.8MM SLEEVE DIA. X

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sleeve Diameter: 4.8 mm
 - Shrink Diameter: 2.4 mm
 - Colour: Red
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



2672203 4.8 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, RED 6.4MM SLEEVE DIA. X

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sleeve Diameter: 6.4 mm
 - Shrink Diameter: 3.2 mm
 - Colour: Red
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



2672219 6.4 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, RED 9.5MM SLEEVE DIA. X

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sleeve Diameter: 9.5 mm
 - Shrink Diameter: 4.8 mm
 - Colour: Red
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



2672225 9.5 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, RED 12.7MM SLEEVE DIA. X

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sleeve Diameter: 12.7 mm
 - Shrink Diameter: 6.4 mm
 - Colour: Red
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



2672231 12.7 mm

CABLE, HEATSHRINK, MEDIUM WALL, LFH, 2:1, RED, 19MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sleeve Diameter: 19.1 mm
 - Shrink Diameter: 9.5 mm
 - Colour: Red
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



2672247 19.1 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, RED 25.4MM SLEEVE DIA. X

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sleeve Diameter: 25.4 mm
 - Shrink Diameter: 12.7 mm
 - Colour: Red
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



2672269 25.4 mm

CABLE, HEATSHRINK, MEDIUM WALL, LFH, 2:1, RED, 38MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sleeve Diameter: 38.1 mm
 - Shrink Diameter: 19.1 mm
 - Colour: Red
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



2672275 38.1 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, WHITE 4.8MM SLEEVE DIA. X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 4.8 mm
 - Shrink Diameter: 2.4 mm
 - Colour: White
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



2672326 4.8 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, WHITE 9.5MM SLEEVE DIA. X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 9.5 mm
 - Shrink Diameter: 4.8 mm
 - Colour: White
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



2672348 9.5 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, WHITE 12.7MM SLEEVE DIA. X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 12.7 mm
 - Shrink Diameter: 6.4 mm
 - Colour: White
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



2672354 12.7 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, WHITE 19.1MM SLEEVE DIA. X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 19.1 mm
 - Shrink Diameter: 9.5 mm
 - Colour: White
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



2672360 19.1 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, WHITE 38.1MM SLEEVE DIA. X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 38.1 mm
 - Shrink Diameter: 19.1 mm
 - Colour: White
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



2672382 38.1 mm

CABLE, HEATSHRINK, MEDIUM WALL, LFH, 2:1, GREEN/YELLOW, 1.6MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 1.6 mm
 - Shrink Diameter: 0.8 mm
 - Colour: Green
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



2684969 1.6 mm

CABLE, HEATSHRINK, MEDIUM WALL, LFH, 2:1, GREEN/YELLOW, 2.4MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 2.4 mm
 - Shrink Diameter: 1.2 mm
 - Colour: Green
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



2684975 2.4 mm

CABLE, HEATSHRINK, MEDIUM WALL, LFH, 2:1, GREEN/YELLOW, 3.2MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 3.2 mm
 - Shrink Diameter: 1.6 mm
 - Colour: Green
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



2684981 3.2 mm

CABLE, HEATSHRINK, MEDIUM WALL, LFH, 2:1, GREEN/YELLOW, 4.8MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 4.8 mm
 - Shrink Diameter: 2.4 mm
 - Colour: Green, Yellow
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



2684997 4.8 mm

CABLE, HEATSHRINK, MEDIUM WALL, LFH, 2:1, GREEN/YELLOW, 6.4MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 6.4 mm
 - Shrink Diameter: 3.2 mm
 - Colour: Green
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



2685007 6.4 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, GREEN 9.5MM SLEEVE DIA. X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 9.5 mm
 - Shrink Diameter: 4.8 mm
 - Colour: Green
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



2685013 9.5 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, GREEN 12.7MM SLEEVE DIA. X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 12.7 mm
 - Shrink Diameter: 6.4 mm
 - Colour: Green
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



2685029 12.7 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, GREEN 19.1MM SLEEVE DIA. X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 19.1 mm
 - Shrink Diameter: 9.5 mm
 - Colour: Green
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



2685035 19.1 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, GREEN 25.4MM SLEEVE DIA.

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 25.4 mm
 - Shrink Diameter: 12.7 mm
 - Colour: Green
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



2685041 25.4 mm

CABLE, HEATSHRINK, MEDIUM WALL, LFH, 2:1, GREEN/YELLOW, 38MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 38.1 mm
 - Shrink Diameter: 19.1 mm
 - Colour: Green
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



2685057 38.1 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, BLACK 3MM SLEEVE DIA. X

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Sleeve Diameter: 3 mm
 - Shrink Diameter: 1 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 3:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



2812811 3 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, BLACK 9MM SLEEVE DIA. X

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Sleeve Diameter: 9 mm
 - Shrunk Diameter: 3 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 3:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



2812833 9 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, BLACK 18MM SLEEVE DIA. X

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Sleeve Diameter: 18 mm
 - Shrunk Diameter: 6 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 3:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



2812855 18 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, BLACK 40MM SLEEVE DIA. X

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Sleeve Diameter: 40 mm
 - Shrunk Diameter: 13 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 3:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



2812883 40 mm

CABLE, HEATSHRINK, KIT, ZERO HALOGEN, FLAME RETARDANT, 2:1

- ขนาดบรรจุภัณฑ์: **1 x KT**
- Sleeve Diameter: 2.4 mm, 3.2 mm, 4.8 mm, 6.4 mm, 9.5 mm, 12.7 mm
 - Shrunk Diameter: Assortment
 - Colour: Black, Blue, Green/Yellow, Red, White
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: Yes
 - Shrink Ratio: 2:1
 - Sleeve Length: 10 cm, 14 cm, 18 cm, 20 cm, 25 cm
 - Material: Polyolefin



3974263 2.4 mm, 3.2 mm,

CABLE, HEATSHRINK, SLEEVE, BLACK, POLYOLEFIN, 30CM, 201.6MM

- ขนาดบรรจุภัณฑ์: **20 x EA**
- Sleeve Diameter: 1.6 mm
 - Shrunk Diameter: 0.8 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 300 mm
 - Material: Polyolefin



4177211 1.6 mm

CABLE, HEATSHRINK, SLEEVE, BLACK, POLYOLEFIN, 30CM, 202.4MM

- ขนาดบรรจุภัณฑ์: **20 x EA**
- Sleeve Diameter: 2.4 mm
 - Shrunk Diameter: 1.2 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 300 mm
 - Material: Polyolefin



4177227 2.4 mm

CABLE, HEATSHRINK, SLEEVE, BLACK, POLYOLEFIN, 30CM, 203.2MM

- ขนาดบรรจุภัณฑ์: **20 x EA**
- Sleeve Diameter: 3.2 mm
 - Shrunk Diameter: 1.6 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 300 mm
 - Material: Polyolefin



4177249 3.2 mm

CABLE, HEATSHRINK, SLEEVE, BLACK, POLYOLEFIN, 30CM, 204.8MM

- ขนาดบรรจุภัณฑ์: **20 x EA**
- Sleeve Diameter: 4.8 mm
 - Shrunk Diameter: 2.4 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 300 mm
 - Material: Polyolefin



4177255 4.8 mm

CABLE, HEATSHRINK, SLEEVE, BLACK, POLYOLEFIN, 30CM, 206.4MM

- ขนาดบรรจุภัณฑ์: **20 x EA**
- Sleeve Diameter: 6.4 mm
 - Shrunk Diameter: 3.2 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 300 mm
 - Material: Polyolefin



4177261 6.4 mm

CABLE, HEATSHRINK, SLEEVE, BLACK, POLYOLEFIN, 30CM, 209.5MM

- ขนาดบรรจุภัณฑ์: **20 x EA**
- Sleeve Diameter: 9.5 mm
 - Shrunk Diameter: 4.8 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 300 mm
 - Material: Polyolefin



4177277 9.5 mm

CABLE, HEATSHRINK, SLEEVE, BLACK, POLYOLEFIN, 30CM, 2012.7MM

- ขนาดบรรจุภัณฑ์: **20 x EA**
- Sleeve Diameter: 12.7 mm
 - Shrunk Diameter: 6.4 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 300 mm
 - Material: Polyolefin



4177283 12.7 mm

RS PRO HEAT SHRINK TUBING, BLACK 19.1MM SLEEVE DIA. X 300MM LENGTH

- ขนาดบรรจุภัณฑ์: **20 x EA**
- Sleeve Diameter: 19.1 mm
 - Shrunk Diameter: 9.5 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 300 mm
 - Material: Polyolefin



4177299 19.1 mm

RS PRO HEAT SHRINK TUBING, BLACK 38MM SLEEVE DIA. X 300MM LENGTH

- ขนาดบรรจุภัณฑ์: **20 x EA**
- Sleeve Diameter: 38 mm
 - Shrunk Diameter: 19 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 300 mm
 - Material: Polyolefin



4177312 38 mm

RS PRO HEAT SHRINK TUBING, BLACK 50.8MM SLEEVE DIA. X 300MM

- ขนาดบรรจุภัณฑ์: **20 x EA**
- Sleeve Diameter: 50.8 mm
 - Shrunk Diameter: 25.4 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 300 mm
 - Material: Polyolefin



4177328 50.8 mm

CABLE, HEATSHRINK, LAME RETARDANT, KIT, ADHESIVE

- ขนาดบรรจุภัณฑ์: **1 x KT**
- Sleeve Diameter: 3 mm
 - Shrunk Diameter: 1.5 mm
 - Colour: Blue, Red, White, Yellow
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: Yes
 - Shrink Ratio: 3:1
 - Sleeve Length: Assortment
 - Material: Polyolefin



4179087 3 mm

CABLE, HEATSHRINK, SLEEVE, POLYOLEFIN, 30CM, 20 PIECES, 1.6MM, CLEAR

- ขนาดบรรจุภัณฑ์: **20 x EA**
- Sleeve Diameter: 1.6 mm
 - Shrunk Diameter: 0.8 mm
 - Colour: Clear
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 300 mm
 - Material: Polyolefin



4434889 1.6 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, CLEAR 2.4MM SLEEVE DIA. X

- ขนาดบรรจุภัณฑ์: **20 x EA**
- Sleeve Diameter: 2.4 mm
 - Shrunk Diameter: 1.2 mm
 - Colour: Clear
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 300 mm
 - Material: Polyolefin



4434895 2.4 mm

CABLE,HEATSHRINK,SLEEVE,POLYOLE FIN,30CM,20 PIECES,3.2MM,CLEAR

- ขนาดบรรจุภัณฑ์: **20 x EA**
- Sleeve Diameter: 3.2 mm
 - Shrunk Diameter: 1.6 mm
 - Colour: Clear
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 300 mm
 - Material: Polyolefin



4434902 3.2 mm

CABLE,HEATSHRINK,SLEEVE,POLYOLE FIN,30CM,20 PIECES,4.8MM,CLEAR

- ขนาดบรรจุภัณฑ์: **20 x EA**
- Sleeve Diameter: 4.8 mm
 - Shrunk Diameter: 2.4 mm
 - Colour: Clear
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 300 mm
 - Material: Polyolefin



4434924 4.8 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, CLEAR 6.4MM SLEEVE DIA. X

- ขนาดบรรจุภัณฑ์: **20 x EA**
- Sleeve Diameter: 6.4 mm
 - Shrunk Diameter: 3.2 mm
 - Colour: Clear
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 300 mm
 - Material: Polyolefin



4434930 6.4 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, CLEAR 9.5MM SLEEVE DIA. X

- ขนาดบรรจุภัณฑ์: **20 x EA**
- Sleeve Diameter: 9.5 mm
 - Shrunk Diameter: 4.8 mm
 - Colour: Clear
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 300 mm
 - Material: Polyolefin



4434946 9.5 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, CLEAR 12.7MM SLEEVE DIA. X

- ขนาดบรรจุภัณฑ์: **20 x EA**
- Sleeve Diameter: 12.7 mm
 - Shrunk Diameter: 6.4 mm
 - Colour: Clear
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 300 mm
 - Material: Polyolefin



4434952 12.7 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, CLEAR 19.1MM SLEEVE DIA. X

- ขนาดบรรจุภัณฑ์: **20 x EA**
- Sleeve Diameter: 19.1 mm
 - Shrunk Diameter: 9.5 mm
 - Colour: Clear
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 300 mm
 - Material: Polyolefin



4434968 19.1 mm

CABLE,HEATSHRINK,SLEEVE,POLYOLE FIN,30CM,20 PIECES,25.4MM,CLEAR

- ขนาดบรรจุภัณฑ์: **20 x EA**
- Sleeve Diameter: 25.4 mm
 - Shrunk Diameter: 12.7 mm
 - Colour: Clear
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 300 mm
 - Material: Polyolefin



4434974 25.4 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, CLEAR 38.1MM SLEEVE DIA. X

- ขนาดบรรจุภัณฑ์: **20 x EA**
- Sleeve Diameter: 38.1 mm
 - Shrunk Diameter: 19.1 mm
 - Colour: Clear
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 300 mm
 - Material: Polyolefin



4434980 38.1 mm

CABLE,HEATSHRINK,SLEEVE,POLYOLE FIN,30CM,20 PIECES,50.8MM,CLEAR

- ขนาดบรรจุภัณฑ์: **20 x EA**
- Sleeve Diameter: 50.8 mm
 - Shrunk Diameter: 25.4 mm
 - Colour: Clear
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 300 mm
 - Material: Polyolefin



4434996 50.8 mm

HEATSHRINK,CABLE,SLEEVE,KIT,2:1,3:1,CLEAR

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 3 mm, 3.2 mm, 6.4 mm, 9 mm
 - Shrunk Diameter: Assortment
 - Colour: Clear
 - Sleeve Type: Heat Shrink
 - Shrink Ratio: 2:1
 - Sleeve Length: 100 mm
 - Material: Fluoropolymer, Polyolefin, PVDF
 - Flame Retardant: Yes



4580639 3 mm, 3.2 mm,

RS PRO HEAT SHRINK TUBING, ASSORTED 3.2MM SLEEVE DIA. X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 3.2 mm, 6.4 mm, 9.5 mm, 12.7 mm
 - Shrunk Diameter: Assortment
 - Colour: Assorted
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 3.6 cm, 4.1 cm, 6 cm, 9 cm, 12 cm, 15 cm, 20 cm, 25 cm
 - Material: Polyolefin



4580645 3.2 mm, 6.4 mm,

HEATSHRINK,CABLE,SLEEVE,HIGH TEMPERATURE,FLAME

- ขนาดบรรจุภัณฑ์: **4 x EA**
- Sleeve Diameter: 6.4 mm
 - Shrunk Diameter: 3.2 mm
 - Colour: Clear
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 300 mm
 - Material: Fluoropolymer



4580651 6.4 mm

HEATSHRINK,CABLE,SLEEVE,HIGH TEMPERATURE,FLAME

- ขนาดบรรจุภัณฑ์: **4 x EA**
- Sleeve Diameter: 3.2 mm
 - Shrunk Diameter: 1.6 mm
 - Colour: Clear
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 300 mm
 - Material: Fluoropolymer



4580667 3.2 mm

HEATSHRINK,CABLE,SLEEVE,POLYOLE FIN,3/1X30CM,X20

- ขนาดบรรจุภัณฑ์: **20 x EA**
- Sleeve Diameter: 3.2 mm
 - Shrunk Diameter: 0.6 mm
 - Colour: Clear
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: Yes
 - Shrink Ratio: 3:1
 - Sleeve Length: 300 mm
 - Material: Polyolefin



4580673 3.2 mm

HEATSHRINK,CABLE,SLEEVE,POLYOLE FIN,9/3X30CM,X20

- ขนาดบรรจุภัณฑ์: **20 x EA**
- Sleeve Diameter: 9.5 mm
 - Shrunk Diameter: 3 mm
 - Colour: Clear
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: Yes
 - Shrink Ratio: 3:1
 - Sleeve Length: 300 mm
 - Material: Polyolefin



4580689 9.5 mm

HEATSHRINK, CABLE, SLEEVE, POLYOLEFIN, 12/1/4X30CM, X20

- ขนาดบรรจุภัณฑ์: 20 x EA
- Sleeve Diameter: 12.7 mm
 - Shrunk Diameter: 4 mm
 - Colour: Clear
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: Yes
 - Shrink Ratio: 3:1
 - Sleeve Length: 300 mm
 - Material: Polyolefin



4580695 12.7 mm

HEATSHRINK, ADHESIVE LINED, FLAME RETARDANT, BLACK, 3/1, 1.2M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sleeve Diameter: 3 mm
 - Shrunk Diameter: 1 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: Yes
 - Shrink Ratio: 3:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



4811775 3 mm

HEATSHRINK, ADHESIVE LINED, FLAME RETARDANT, BLACK, 6/2, 1.2M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sleeve Diameter: 6.4 mm
 - Shrunk Diameter: 2 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: Yes
 - Shrink Ratio: 3:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



4811797 6.4 mm

HEATSHRINK, ADHESIVE LINED, FLAME RETARDANT, BLACK, 9/3, 1.2M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sleeve Diameter: 9.5 mm
 - Shrunk Diameter: 3 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: Yes
 - Shrink Ratio: 3:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



4811804 9.5 mm

RS PRO ADHESIVE LINED HEAT SHRINK TUBING, BLACK 12.7MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sleeve Diameter: 12.7 mm
 - Shrunk Diameter: 4 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: Yes
 - Shrink Ratio: 3:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



4811810 12.7 mm

HEATSHRINK, ADHESIVE LINED, FLAME RETARDANT, BLACK, 19/6, 1.2M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sleeve Diameter: 19 mm
 - Shrunk Diameter: 6 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: Yes
 - Shrink Ratio: 3:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



4811826 19 mm

HEATSHRINK, ADHESIVE LINED, FLAME RETARDANT, BLACK, 24/8, 1.2M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sleeve Diameter: 24 mm
 - Shrunk Diameter: 8 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: Yes
 - Shrink Ratio: 3:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



4811832 24 mm

HEATSHRINK, ADHESIVE LINED, FLAME RETARDANT, BLACK, 40/13, 1.2M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sleeve Diameter: 40 mm
 - Shrunk Diameter: 13 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: Yes
 - Shrink Ratio: 3:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



4811854 40 mm

CABLE, HEATSHRINK, SLEEVE, GREY, POLYOLEFIN, 1.2, BORE 1.6MM

- ขนาดบรรจุภัณฑ์: 5 x EA
- Sleeve Diameter: 1.6 mm
 - Shrunk Diameter: 0.8 mm
 - Colour: Grey
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



4834100 1.6 mm

RS PRO HEAT SHRINK TUBING, GREY 2.4MM SLEEVE DIA. X 1.2M LENGTH 2:1

- ขนาดบรรจุภัณฑ์: 5 x EA
- Sleeve Diameter: 2.4 mm
 - Shrunk Diameter: 1.2 mm
 - Colour: Grey
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



4834122 2.4 mm

CABLE, HEATSHRINK, SLEEVE, GREY, POLYOLEFIN, 1.2, BORE 3.2MM

- ขนาดบรรจุภัณฑ์: 5 x EA
- Sleeve Diameter: 3.2 mm
 - Shrunk Diameter: 1.6 mm
 - Colour: Grey
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



4834138 3.2 mm

CABLE, HEATSHRINK, SLEEVE, GREY, POLYOLEFIN, 1.2, BORE 4.8MM

- ขนาดบรรจุภัณฑ์: 5 x EA
- Sleeve Diameter: 4.8 mm
 - Shrunk Diameter: 2.4 mm
 - Colour: Grey
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



4834144 4.8 mm

CABLE, HEATSHRINK, SLEEVE, GREY, POLYOLEFIN, 1.2, BORE 6.4MM

- ขนาดบรรจุภัณฑ์: 5 x EA
- Sleeve Diameter: 6.4 mm
 - Shrunk Diameter: 3.2 mm
 - Colour: Grey
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



4834150 6.4 mm

RS PRO HEAT SHRINK TUBING, GREY 9.5MM SLEEVE DIA. X 1.2M LENGTH 2:1

- ขนาดบรรจุภัณฑ์: 5 x EA
- Sleeve Diameter: 9.5 mm
 - Shrunk Diameter: 4.8 mm
 - Colour: Grey
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



4834166 9.5 mm

CABLE, HEATSHRINK, SLEEVE, GREY, POLYOLEFIN, 1.2, BORE 12.7MM

- ขนาดบรรจุภัณฑ์: 5 x EA
- Sleeve Diameter: 12.7 mm
 - Shrunk Diameter: 6.4 mm
 - Colour: Grey
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



4834172 12.7 mm

CABLE, HEATSHRINK, SLEEVE, GREY, POLYOLEFIN, 1.2, BORE 19.1MM

- ขนาดบรรจุภัณฑ์: 5 x EA
- Sleeve Diameter: 19 mm
 - Shrunk Diameter: 9.5 mm
 - Colour: Grey
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



4834188 19 mm

RS PRO HEAT SHRINK TUBING, GREY 25.4MM SLEEVE DIA. X 1.2M LENGTH

- ขนาดบรรจุภัณฑ์: 5 x EA
- Sleeve Diameter: 25.4 mm
 - Shrink Diameter: 12.7 mm
 - Colour: Grey
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



4834194 25.4 mm

RS PRO HEAT SHRINK TUBING, GREY 38MM SLEEVE DIA. X 1.2M LENGTH 2:1

- ขนาดบรรจุภัณฑ์: 5 x EA
- Sleeve Diameter: 38 mm
 - Shrink Diameter: 19 mm
 - Colour: Grey
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



4834201 38 mm

RS PRO HEAT SHRINK TUBING, GREY 50.8MM SLEEVE DIA. X 1.2M LENGTH

- ขนาดบรรจุภัณฑ์: 5 x EA
- Sleeve Diameter: 50.8 mm
 - Shrink Diameter: 25.4 mm
 - Colour: Grey
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



4834217 50.8 mm

RS PRO HEAT SHRINK TUBING, BROWN 3.2MM SLEEVE DIA. X 1.2M

- ขนาดบรรจุภัณฑ์: 5 x EA
- Sleeve Diameter: 3.2 mm
 - Shrink Diameter: 1.6 mm
 - Colour: Brown
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



4834245 3.2 mm

RS PRO HEAT SHRINK TUBING, BROWN 4.8MM SLEEVE DIA. X 1.2M

- ขนาดบรรจุภัณฑ์: 5 x EA
- Sleeve Diameter: 4.8 mm
 - Shrink Diameter: 2.4 mm
 - Colour: Brown
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



4834251 4.8 mm

CABLE, HEATSHRINK, SLEEVE, BROWN, POLYOLEFIN, 1.2, BORE 6.4MM

- ขนาดบรรจุภัณฑ์: 5 x EA
- Sleeve Diameter: 6.4 mm
 - Shrink Diameter: 3.2 mm
 - Colour: Brown
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



4834267 6.4 mm

RS PRO HEAT SHRINK TUBING, BROWN 9.5MM SLEEVE DIA. X 1.2M

- ขนาดบรรจุภัณฑ์: 5 x EA
- Sleeve Diameter: 9.5 mm
 - Shrink Diameter: 4.8 mm
 - Colour: Brown
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



4834289 9.5 mm

CABLE, HEATSHRINK, SLEEVE, BROWN, POLYOLEFIN, 1.2, BORE 12.7MM

- ขนาดบรรจุภัณฑ์: 5 x EA
- Sleeve Diameter: 12.7 mm
 - Shrink Diameter: 6.4 mm
 - Colour: Brown
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



4834295 12.7 mm

RS PRO HEAT SHRINK TUBING, BROWN 19MM SLEEVE DIA. X 1.2M

- ขนาดบรรจุภัณฑ์: 5 x EA
- Sleeve Diameter: 19 mm
 - Shrink Diameter: 9.5 mm
 - Colour: Brown
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



4834302 19 mm

RS PRO HEAT SHRINK TUBING, BROWN 25.4MM SLEEVE DIA. X 1.2M

- ขนาดบรรจุภัณฑ์: 5 x EA
- Sleeve Diameter: 25.4 mm
 - Shrink Diameter: 12.7 mm
 - Colour: Brown
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



4834318 25.4 mm

RS PRO HEAT SHRINK TUBING, BROWN 38MM SLEEVE DIA. X 1.2M

- ขนาดบรรจุภัณฑ์: 5 x EA
- Sleeve Diameter: 38 mm
 - Shrink Diameter: 19 mm
 - Colour: Brown
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



4834324 38 mm

RS PRO HEAT SHRINK TUBING, BROWN 50.8MM SLEEVE DIA. X 1.2M

- ขนาดบรรจุภัณฑ์: 5 x EA
- Sleeve Diameter: 50.8 mm
 - Shrink Diameter: 25.4 mm
 - Colour: Brown
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



4834346 50.8 mm

TUBES, HEAT SHRINK, PORTABLE STACKABLE KIT, 21, 12M TUBES, 30

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sleeve Diameter: Set
 - Shrink Diameter: Set
 - Colour: Assorted
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: Yes
 - Shrink Ratio: 2:1, 3:1
 - Sleeve Length: Set
 - Material: Polyolefin



4873852 Set

RS PRO HALOGEN FREE HEAT SHRINK TUBING, BROWN 1.6MM SLEEVE DIA. X

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sleeve Diameter: 1.6 mm
 - Shrink Diameter: 0.8 mm
 - Colour: Brown
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



5377945 1.6 mm

CABLE, HEATSHRINK, MEDIUM WALL, LFH, 2:1, BROWN, 2.4MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sleeve Diameter: 2.4 mm
 - Shrink Diameter: 1.2 mm
 - Colour: Brown
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



5377967 2.4 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, BROWN 3.2MM SLEEVE DIA.

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sleeve Diameter: 3.2 mm
 - Shrink Diameter: 1.6 mm
 - Colour: Brown
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



5377995 3.2 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, GREY 4.8MM SLEEVE DIA. X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 4.8 mm
 - Shrink Diameter: 2.4 mm
 - Colour: Grey
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



5378005 4.8 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, BROWN 4.8MM SLEEVE DIA.

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 4.8 mm
 - Shrink Diameter: 2.4 mm
 - Colour: Brown
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



5378011 4.8 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, GREY 6.4MM SLEEVE DIA. X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 6.4 mm
 - Shrink Diameter: 3.2 mm
 - Colour: Grey
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



5378027 6.4 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, BROWN 6.4MM SLEEVE DIA.

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 6.4 mm
 - Shrink Diameter: 3.2 mm
 - Colour: Brown
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



5378033 6.4 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, GREY 9.5MM SLEEVE DIA. X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 9.5 mm
 - Shrink Diameter: 4.8 mm
 - Colour: Grey
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



5378049 9.5 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, BROWN 9.5MM SLEEVE DIA.

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 9.5 mm
 - Shrink Diameter: 4.8 mm
 - Colour: Brown
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



5378061 9.5 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, GREY 12.7MM SLEEVE DIA. X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 12.7 mm
 - Shrink Diameter: 6.4 mm
 - Colour: Grey
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



5378077 12.7 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, BROWN 12.7MM SLEEVE DIA.

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 12.7 mm
 - Shrink Diameter: 6.4 mm
 - Colour: Brown
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



5378083 12.7 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, GREY 19.1MM SLEEVE DIA. X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 19.1 mm
 - Shrink Diameter: 9.5 mm
 - Colour: Grey
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



5378099 19.1 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, BROWN 19.1MM SLEEVE DIA.

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 19.1 mm
 - Shrink Diameter: 9.5 mm
 - Colour: Brown
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



5378106 19.1 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, GREY 25.4MM SLEEVE DIA. X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 25.4 mm
 - Shrink Diameter: 12.7 mm
 - Colour: Grey
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



5378128 25.4 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, BROWN 25.4MM SLEEVE DIA.

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 25.4 mm
 - Shrink Diameter: 12.7 mm
 - Colour: Brown
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



5378134 25.4 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, GREY 38.1MM SLEEVE DIA. X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 38.1 mm
 - Shrink Diameter: 19.1 mm
 - Colour: Grey
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



5378140 38.1 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, BROWN 38.1MM SLEEVE DIA.

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sleeve Diameter: 38.1 mm
 - Shrink Diameter: 19.1 mm
 - Colour: Brown
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



5378156 38.1 mm

CLEAR HEATSHRINK TUBE 9/3MM I/D

- ขนาดบรรจุภัณฑ์: **5 x MTR**
- Sleeve Diameter: 9 mm
 - Shrink Diameter: 3 mm
 - Colour: Clear
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 3:1
 - Sleeve Length: 5 m
 - Material: Polyolefin



7004450 9 mm

CLEAR HEATSHRINK TUBE 3/1MM I/D

- ขนาดบรรจุภัณฑ์: **10 x MTR**
- Sleeve Diameter: 3 mm
 - Shrink Diameter: 1 mm
 - Colour: Clear
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 3:1
 - Sleeve Length: 10 m
 - Material: Polyolefin



7004453 3 mm

CLEAR HEATSHRINK TUBE 6/2MM I/D

- ขนาดบรรจุภัณฑ์: **7 x MTR**
- Sleeve Diameter: 6 mm
 - Shrunk Diameter: 2 mm
 - Colour: Clear
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 3:1
 - Sleeve Length: 7 m
 - Material: Polyolefin



7004456 6 mm

CLEAR HEATSHRINK TUBE 18/6MM I/D

- ขนาดบรรจุภัณฑ์: **3 x MTR**
- Sleeve Diameter: 18 mm
 - Shrunk Diameter: 6 mm
 - Colour: Clear
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 3:1
 - Sleeve Length: 3 m
 - Material: Polyolefin



7004462 18 mm

CLEAR HEATSHRINK TUBE 24/8MM I/D

- ขนาดบรรจุภัณฑ์: **3 x MTR**
- Sleeve Diameter: 24 mm
 - Shrunk Diameter: 8 mm
 - Colour: Clear
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 3:1
 - Sleeve Length: 3 m
 - Material: Polyolefin



7004466 24 mm

CLEAR HEATSHRINK TUBE 12/4MM I/D

- ขนาดบรรจุภัณฑ์: **4 x MTR**
- Sleeve Diameter: 12 mm
 - Shrunk Diameter: 4 mm
 - Colour: Clear
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 3:1
 - Sleeve Length: 4 m
 - Material: Polyolefin



7004469 12 mm

YELLOW HEATSHRINK TUBE 9/3MM I/D

- ขนาดบรรจุภัณฑ์: **5 x MTR**
- Sleeve Diameter: 9 mm
 - Shrunk Diameter: 3 mm
 - Colour: Yellow
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 3:1
 - Sleeve Length: 5 m
 - Material: Polyolefin



7004472 9 mm

YELLOW HEATSHRINK TUBE 3/1MM I/D

- ขนาดบรรจุภัณฑ์: **10 x MTR**
- Sleeve Diameter: 3 mm
 - Shrunk Diameter: 1 mm
 - Colour: Yellow
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 3:1
 - Sleeve Length: 10 m
 - Material: Polyolefin



7004475 3 mm

YELLOW HEATSHRINK TUBE 6/2MM I/D

- ขนาดบรรจุภัณฑ์: **7 x MTR**
- Sleeve Diameter: 6 mm
 - Shrunk Diameter: 2 mm
 - Colour: Yellow
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 3:1
 - Sleeve Length: 7 m
 - Material: Polyolefin



7004478 6 mm

RS PRO HEAT SHRINK TUBING, YELLOW 12MM SLEEVE DIA. X 4M

- ขนาดบรรจุภัณฑ์: **4 x MTR**
- Sleeve Diameter: 12 mm
 - Shrunk Diameter: 4 mm
 - Colour: Yellow
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 3:1
 - Sleeve Length: 4 m
 - Material: Polyolefin



7004481 12 mm

YELLOW HEATSHRINK TUBE 18/6MM I/D

- ขนาดบรรจุภัณฑ์: **3 x MTR**
- Sleeve Diameter: 18 mm
 - Shrunk Diameter: 6 mm
 - Colour: Yellow
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 3:1
 - Sleeve Length: 3 m
 - Material: Polyolefin



7004484 18 mm

YELLOW HEATSHRINK TUBE 24/8MM I/D

- ขนาดบรรจุภัณฑ์: **3 x MTR**
- Sleeve Diameter: 24 mm
 - Shrunk Diameter: 8 mm
 - Colour: Yellow
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 3:1
 - Sleeve Length: 3 m
 - Material: Polyolefin



7004488 24 mm

BLUE HEATSHRINK TUBE 6/2MM I/D

- ขนาดบรรจุภัณฑ์: **7 x MTR**
- Sleeve Diameter: 6 mm
 - Shrunk Diameter: 2 mm
 - Colour: Blue
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 3:1
 - Sleeve Length: 7 m
 - Material: Polyolefin



7004490 6 mm

BLUE HEATSHRINK TUBE 9/3MM I/D

- ขนาดบรรจุภัณฑ์: **5 x MTR**
- Sleeve Diameter: 9 mm
 - Shrunk Diameter: 3 mm
 - Colour: Blue
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 3:1
 - Sleeve Length: 5 m
 - Material: Polyolefin



7004494 9 mm

BLUE HEATSHRINK TUBE 3/1MM I/D

- ขนาดบรรจุภัณฑ์: **10 x MTR**
- Sleeve Diameter: 3 mm
 - Shrunk Diameter: 1 mm
 - Colour: Blue
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 3:1
 - Sleeve Length: 10 m
 - Material: Polyolefin



7004497 3 mm

BLUE HEATSHRINK TUBE 24/8MM I/D

- ขนาดบรรจุภัณฑ์: **3 x MTR**
- Sleeve Diameter: 24 mm
 - Shrunk Diameter: 8 mm
 - Colour: Blue
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 3:1
 - Sleeve Length: 3 m
 - Material: Polyolefin



7004501 24 mm

BLUE HEATSHRINK TUBE 12/4MM I/D

- ขนาดบรรจุภัณฑ์: **4 x MTR**
- Sleeve Diameter: 12 mm
 - Shrunk Diameter: 4 mm
 - Colour: Blue
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 3:1
 - Sleeve Length: 4 m
 - Material: Polyolefin



7004504 12 mm

BLUE HEATSHRINK TUBE 18/6MM I/D

- ขนาดบรรจุภัณฑ์: **3 x MTR**
- Sleeve Diameter: 18 mm
 - Shrunk Diameter: 6 mm
 - Colour: Blue
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 3:1
 - Sleeve Length: 3 m
 - Material: Polyolefin



7004507 18 mm

RED HEATSHRINK TUBE 3/1MM I/D

- ขนาดบรรจุภัณฑ์: **10 x MTR**
- Sleeve Diameter: 3 mm
 - Shrink Diameter: 1 mm
 - Colour: Red
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 3:1
 - Sleeve Length: 10 m
 - Material: Polyolefin



7004510 3 mm

RED HEATSHRINK TUBE 6/2MM I/D

- ขนาดบรรจุภัณฑ์: **7 x MTR**
- Sleeve Diameter: 6 mm
 - Shrink Diameter: 2 mm
 - Colour: Red
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 3:1
 - Sleeve Length: 7 m
 - Material: Polyolefin



7004513 6 mm

RED HEATSHRINK TUBE 9/3MM I/D

- ขนาดบรรจุภัณฑ์: **5 x MTR**
- Sleeve Diameter: 9 mm
 - Shrink Diameter: 3 mm
 - Colour: Red
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 3:1
 - Sleeve Length: 5 m
 - Material: Polyolefin



7004517 9 mm

RED HEATSHRINK TUBE 24/8MM I/D

- ขนาดบรรจุภัณฑ์: **3 x MTR**
- Sleeve Diameter: 24 mm
 - Shrink Diameter: 8 mm
 - Colour: Red
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 3:1
 - Sleeve Length: 3 m
 - Material: Polyolefin



7004523 24 mm

RED HEATSHRINK TUBE 12/4MM I/D

- ขนาดบรรจุภัณฑ์: **4 x MTR**
- Sleeve Diameter: 12 mm
 - Shrink Diameter: 4 mm
 - Colour: Red
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 3:1
 - Sleeve Length: 4 m
 - Material: Polyolefin



7004526 12 mm

RED HEATSHRINK TUBE 18/6MM I/D

- ขนาดบรรจุภัณฑ์: **3 x MTR**
- Sleeve Diameter: 18 mm
 - Shrink Diameter: 6 mm
 - Colour: Red
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 3:1
 - Sleeve Length: 3 m
 - Material: Polyolefin



7004529 18 mm

BLACK HEATSHRINK TUBE 3/1MM I/D

- ขนาดบรรจุภัณฑ์: **10 x MTR**
- Sleeve Diameter: 3 mm
 - Shrink Diameter: 1 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 3:1
 - Sleeve Length: 10 m
 - Material: Polyolefin



7004532 3 mm

BLACK HEATSHRINK TUBE 6/2MM I/D

- ขนาดบรรจุภัณฑ์: **7 x MTR**
- Sleeve Diameter: 6 mm
 - Shrink Diameter: 2 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 3:1
 - Sleeve Length: 7 m
 - Material: Polyolefin



7004535 6 mm

BLACK HEATSHRINK TUBE 9/3MM I/D

- ขนาดบรรจุภัณฑ์: **5 x MTR**
- Sleeve Diameter: 9 mm
 - Shrink Diameter: 3 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 3:1
 - Sleeve Length: 5 m
 - Material: Polyolefin



7004539 9 mm

BLACK HEATSHRINK TUBE 18/6MM I/D

- ขนาดบรรจุภัณฑ์: **3 x MTR**
- Sleeve Diameter: 18 mm
 - Shrink Diameter: 6 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 3:1
 - Sleeve Length: 3 m
 - Material: Polyolefin



7004541 18 mm

BLACK HEATSHRINK TUBE 24/8MM I/D

- ขนาดบรรจุภัณฑ์: **3 x MTR**
- Sleeve Diameter: 24 mm
 - Shrink Diameter: 8 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 3:1
 - Sleeve Length: 3 m
 - Material: Polyolefin



7004545 24 mm

BLACK HEATSHRINK TUBE 12/4MM I/D

- ขนาดบรรจุภัณฑ์: **4 x MTR**
- Sleeve Diameter: 12 mm
 - Shrink Diameter: 4 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 3:1
 - Sleeve Length: 4 m
 - Material: Polyolefin



7004548 12 mm

WHITE HEATSHRINK TUBE 9/3MM I/D

- ขนาดบรรจุภัณฑ์: **5 x MTR**
- Sleeve Diameter: 9 mm
 - Shrink Diameter: 3 mm
 - Colour: White
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 3:1
 - Sleeve Length: 5 m
 - Material: Polyolefin



7004551 9 mm

WHITE HEATSHRINK TUBE 3/1MM I/D

- ขนาดบรรจุภัณฑ์: **10 x MTR**
- Sleeve Diameter: 3 mm
 - Shrink Diameter: 1 mm
 - Colour: White
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 3:1
 - Sleeve Length: 10 m
 - Material: Polyolefin



7004554 3 mm

WHITE HEATSHRINK TUBE 6/2MM I/D

- ขนาดบรรจุภัณฑ์: **7 x MTR**
- Sleeve Diameter: 6 mm
 - Shrink Diameter: 2 mm
 - Colour: White
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 3:1
 - Sleeve Length: 7 m
 - Material: Polyolefin



7004557 6 mm

WHITE HEATSHRINK TUBE 12/4MM I/D

- ขนาดบรรจุภัณฑ์: **4 x MTR**
- Sleeve Diameter: 12 mm
 - Shrink Diameter: 4 mm
 - Colour: White
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 3:1
 - Sleeve Length: 4 m
 - Material: Polyolefin



7004560 12 mm

WHITE HEATSHRINK TUBE 18/6MM I/D

- ขนาดบรรจุภัณฑ์: **3 x MTR**
- Sleeve Diameter: 18 mm
 - Shrink Diameter: 6 mm
 - Colour: White
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 3:1
 - Sleeve Length: 3 m
 - Material: Polyolefin



7004567 18 mm

WHITE HEATSHRINK TUBE 24/8MM I/D

- ขนาดบรรจุภัณฑ์: **3 x MTR**
- Sleeve Diameter: 24 mm
 - Shrink Diameter: 8 mm
 - Colour: White
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 3:1
 - Sleeve Length: 3 m
 - Material: Polyolefin



7004573 24 mm

GREEN/YELLOW HEATSHRINK TUBE 3/1MM I/D

- ขนาดบรรจุภัณฑ์: **10 x MTR**
- Sleeve Diameter: 3 mm
 - Shrink Diameter: 1 mm
 - Colour: Green, Yellow
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 3:1
 - Material: Polyolefin
 - Flame Retardant: Yes



7004582 3 mm

GREEN/YELLOW HEATSHRINK TUBE 6/2MM I/D

- ขนาดบรรจุภัณฑ์: **7 x MTR**
- Sleeve Diameter: 6 mm
 - Shrink Diameter: 2 mm
 - Colour: Green, Yellow
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 3:1
 - Sleeve Length: 7 m
 - Material: Polyolefin



7004589 6 mm

GREEN/YELLOW HEATSHRINK TUBE 9/3MM I/D

- ขนาดบรรจุภัณฑ์: **5 x MTR**
- Sleeve Diameter: 9 mm
 - Shrink Diameter: 3 mm
 - Colour: Green, Yellow
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 3:1
 - Sleeve Length: 5 m
 - Material: Polyolefin



7004595 9 mm

GREEN/YELLOW HEATSHRINK TUBE 12/4MM I/D

- ขนาดบรรจุภัณฑ์: **4 x MTR**
- Sleeve Diameter: 12 mm
 - Shrink Diameter: 4 mm
 - Colour: Green, Yellow
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 3:1
 - Sleeve Length: 4 m
 - Material: Polyolefin



7004608 12 mm

GREEN/YELLOW HEATSHRINK TUBE 18/6MM I/D

- ขนาดบรรจุภัณฑ์: **3 x MTR**
- Sleeve Diameter: 18 mm
 - Shrink Diameter: 6 mm
 - Colour: Green, Yellow
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 3:1
 - Sleeve Length: 3 m
 - Material: Polyolefin



7004611 18 mm

GREEN/YELLOW HEATSHRINK TUBE 24/8MM I/D

- ขนาดบรรจุภัณฑ์: **3 x MTR**
- Sleeve Diameter: 24 mm
 - Shrink Diameter: 8 mm
 - Colour: Green, Yellow
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 3:1
 - Sleeve Length: 3 m
 - Material: Polyolefin



7004618 24 mm

BLACK LOW SHRINK TEMP TUBE 1.6MM I/D

- ขนาดบรรจุภัณฑ์: **10 x MTR**
- Sleeve Diameter: 1.6 mm
 - Shrink Diameter: 0.8 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 10 m
 - Material: Polyolefin



7004620 1.6 mm

BLACK LOW SHRINK TEMP TUBE 2.4MM I/D

- ขนาดบรรจุภัณฑ์: **10 x MTR**
- Sleeve Diameter: 2.4 mm
 - Shrink Diameter: 1.2 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 10 m
 - Material: Polyolefin



7004624 2.4 mm

BLACK LOW SHRINK TEMP TUBE 3.2MM I/D

- ขนาดบรรจุภัณฑ์: **10 x MTR**
- Sleeve Diameter: 3.2 mm
 - Shrink Diameter: 1.6 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 10 m
 - Material: Polyolefin



7004630 3.2 mm

BLACK LOW SHRINK TEMP TUBE 6.4MM I/D

- ขนาดบรรจุภัณฑ์: **8 x MTR**
- Sleeve Diameter: 6.4 mm
 - Shrink Diameter: 3.2 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 8 m
 - Material: Polyolefin



7004646 6.4 mm

BLACK LOW SHRINK TEMP TUBE 4.8MM I/D

- ขนาดบรรจุภัณฑ์: **9 x MTR**
- Sleeve Diameter: 4.8 mm
 - Shrink Diameter: 2.4 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 9 m
 - Material: Polyolefin



7004649 4.8 mm

BLACK LOW SHRINK TEMP TUBE 9.5MM I/D

- ขนาดบรรจุภัณฑ์: **6 x MTR**
- Sleeve Diameter: 9.5 mm
 - Shrink Diameter: 4.8 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 6 m
 - Material: Polyolefin



7004658 9.5 mm

BLACK LOWSHRINK TEMP TUBE 12.7MM I/D

- ขนาดบรรจุภัณฑ์: **6 x MTR**
- Sleeve Diameter: 12.7 mm
 - Shrink Diameter: 6.4 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 6 m
 - Material: Polyolefin



7004661 12.7 mm

BLACK LOWSHRINK TEMP TUBE 19.0MM I/D

- ขนาดบรรจุภัณฑ์: **5 x MTR**
- Sleeve Diameter: 19 mm
 - Shrink Diameter: 9.5 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 5 m
 - Material: Polyolefin



7004664 19 mm

BLACK LOWSHRINK TEMP TUBE 25.4MM I/D

- ขนาดบรรจุภัณฑ์: 3 x MTR
- Sleeve Diameter: 25.4 mm
 - Shrunk Diameter: 12.7 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 3 m
 - Material: Polyolefin



7004668 25.4 mm

RED LOW SHRINK TEMP TUBE 2.4MM I/D

- ขนาดบรรจุภัณฑ์: 10 x MTR
- Sleeve Diameter: 2.4 mm
 - Shrunk Diameter: 1.2 mm
 - Colour: Red
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 10 m
 - Material: Polyolefin



7004670 2.4 mm

RED LOW SHRINK TEMP TUBE 3.2MM I/D

- ขนาดบรรจุภัณฑ์: 10 x MTR
- Sleeve Diameter: 3.2 mm
 - Shrunk Diameter: 1.6 mm
 - Colour: Red
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 10 m
 - Material: Polyolefin



7004674 3.2 mm

RED LOW SHRINK TEMP TUBE 1.6MM I/D

- ขนาดบรรจุภัณฑ์: 10 x MTR
- Sleeve Diameter: 1.6 mm
 - Shrunk Diameter: 0.8 mm
 - Colour: Red
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 10 m
 - Material: Polyolefin



7004677 1.6 mm

RED LOW SHRINK TEMP TUBE 9.5MM I/D

- ขนาดบรรจุภัณฑ์: 6 x MTR
- Sleeve Diameter: 9.5 mm
 - Shrunk Diameter: 4.8 mm
 - Colour: Red
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 6 m
 - Material: Polyolefin



7004680 9.5 mm

RED LOW SHRINK TEMP TUBE 4.8MM I/D

- ขนาดบรรจุภัณฑ์: 9 x MTR
- Sleeve Diameter: 4.8 mm
 - Shrunk Diameter: 2.4 mm
 - Colour: Red
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 9 m
 - Material: Polyolefin



7004683 4.8 mm

RED LOW SHRINK TEMP TUBE 6.4MM I/D

- ขนาดบรรจุภัณฑ์: 8 x MTR
- Sleeve Diameter: 6.4 mm
 - Shrunk Diameter: 3.2 mm
 - Colour: Red
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 8 m
 - Material: Polyolefin



7004686 6.4 mm

RED LOW SHRINK TEMP TUBE 19.0MM I/D

- ขนาดบรรจุภัณฑ์: 5 x MTR
- Sleeve Diameter: 19 mm
 - Shrunk Diameter: 9.5 mm
 - Colour: Red
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 5 m
 - Material: Polyolefin



7004692 19 mm

RED LOW SHRINK TEMP TUBE 25.4MM I/D

- ขนาดบรรจุภัณฑ์: 3 x MTR
- Sleeve Diameter: 25.4 mm
 - Shrunk Diameter: 12.7 mm
 - Colour: Red
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 3 m
 - Material: Polyolefin



7004696 25.4 mm

RED LOW SHRINK TEMP TUBE 12.7MM I/D

- ขนาดบรรจุภัณฑ์: 6 x MTR
- Sleeve Diameter: 12.7 mm
 - Shrunk Diameter: 6.4 mm
 - Colour: Red
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 6 m
 - Material: Polyolefin



7004699 12.7 mm

RS PRO HEAT SHRINK TUBING, YELLOW 3.2MM SLEEVE DIA. X 10M

- ขนาดบรรจุภัณฑ์: 10 x MTR
- Sleeve Diameter: 3.2 mm
 - Shrunk Diameter: 1.6 mm
 - Colour: Yellow
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 10 m
 - Material: Polyolefin



7004703 3.2 mm

RS PRO HEAT SHRINK TUBING, YELLOW 1.6MM SLEEVE DIA. X 10M

- ขนาดบรรจุภัณฑ์: 10 x MTR
- Sleeve Diameter: 1.6 mm
 - Shrunk Diameter: 0.8 mm
 - Colour: Yellow
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 10 m
 - Material: Polyolefin



7004706 1.6 mm

YELLOW LOW SHRINK TEMP TUBE 2.4MM I/D

- ขนาดบรรจุภัณฑ์: 10 x MTR
- Sleeve Diameter: 2.4 mm
 - Shrunk Diameter: 1.2 mm
 - Colour: Yellow
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 10 m
 - Material: Polyolefin



7004709 2.4 mm

RS PRO HEAT SHRINK TUBING, YELLOW 4.8MM SLEEVE DIA. X 9M

- ขนาดบรรจุภัณฑ์: 9 x MTR
- Sleeve Diameter: 4.8 mm
 - Shrunk Diameter: 2.4 mm
 - Colour: Yellow
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 9 m
 - Material: Polyolefin



7004712 4.8 mm

RS PRO HEAT SHRINK TUBING, YELLOW 6.4MM SLEEVE DIA. X 8M

- ขนาดบรรจุภัณฑ์: 8 x MTR
- Sleeve Diameter: 6.4 mm
 - Shrunk Diameter: 3.2 mm
 - Colour: Yellow
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 8 m
 - Material: Polyolefin



7004715 6.4 mm

YELLOW LOW SHRINK TEMP TUBE 9.5MM I/D

- ขนาดบรรจุภัณฑ์: 6 x MTR
- Sleeve Diameter: 9.5 mm
 - Shrunk Diameter: 4.8 mm
 - Colour: Yellow
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 6 m
 - Material: Polyolefin



7004719 9.5 mm

RS PRO HEAT SHRINK TUBING, YELLOW 19MM SLEEVE DIA. X 5M

- ขนาดบรรจุภัณฑ์: **5 x MTR**
- Sleeve Diameter: 19 mm
 - Shrunk Diameter: 9.5 mm
 - Colour: Yellow
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 5 m
 - Material: Polyolefin



7004721 19 mm

RS PRO HEAT SHRINK TUBING, YELLOW 25.4MM SLEEVE DIA. X 3M

- ขนาดบรรจุภัณฑ์: **3 x MTR**
- Sleeve Diameter: 25.4 mm
 - Shrunk Diameter: 12.7 mm
 - Colour: Yellow
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 3 m
 - Material: Polyolefin



7004725 25.4 mm

YELLOW LOW SHRINK TEMP TUBE 12.7MM I/D

- ขนาดบรรจุภัณฑ์: **6 x MTR**
- Sleeve Diameter: 12.7 mm
 - Shrunk Diameter: 6.4 mm
 - Colour: Yellow
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 6 m
 - Material: Polyolefin



7004728 12.7 mm

BLUE LOW SHRINK TEMP TUBE 3.2MM I/D

- ขนาดบรรจุภัณฑ์: **10 x MTR**
- Sleeve Diameter: 3.2 mm
 - Shrunk Diameter: 1.6 mm
 - Colour: Blue
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 10 m
 - Material: Polyolefin



7004731 3.2 mm

BLUE LOW SHRINK TEMP TUBE 1.6MM I/D

- ขนาดบรรจุภัณฑ์: **10 x MTR**
- Sleeve Diameter: 1.6 mm
 - Shrunk Diameter: 0.8 mm
 - Colour: Blue
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 10 m
 - Material: Polyolefin



7004734 1.6 mm

BLUE LOW SHRINK TEMP TUBE 2.4MM I/D

- ขนาดบรรจุภัณฑ์: **10 x MTR**
- Sleeve Diameter: 2.4 mm
 - Shrunk Diameter: 1.2 mm
 - Colour: Blue
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 10 m
 - Material: Polyolefin



7004737 2.4 mm

BLUE LOW SHRINK TEMP TUBE 4.8MM I/D

- ขนาดบรรจุภัณฑ์: **9 x MTR**
- Sleeve Diameter: 4.8 mm
 - Shrunk Diameter: 2.4 mm
 - Colour: Blue
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 9 m
 - Material: Polyolefin



7004740 4.8 mm

RS PRO HEAT SHRINK TUBING, BLUE 6.4MM SLEEVE DIA. X 8M LENGTH 2:1

- ขนาดบรรจุภัณฑ์: **8 x MTR**
- Sleeve Diameter: 6.4 mm
 - Shrunk Diameter: 3.2 mm
 - Colour: Blue
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 8 m
 - Material: Polyolefin



7004743 6.4 mm

RS PRO HEAT SHRINK TUBING, BLUE 9.5MM SLEEVE DIA. X 6M LENGTH 2:1

- ขนาดบรรจุภัณฑ์: **6 x MTR**
- Sleeve Diameter: 9.5 mm
 - Shrunk Diameter: 4.8 mm
 - Colour: Blue
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 6 m
 - Material: Polyolefin



7004747 9.5 mm

BLUE LOW SHRINK TEMP TUBE 25.4MM I/D

- ขนาดบรรจุภัณฑ์: **3 x MTR**
- Sleeve Diameter: 25.4 mm
 - Shrunk Diameter: 12.7 mm
 - Colour: Blue
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 3 m
 - Material: Polyolefin



7004753 25.4 mm

BLUE LOW SHRINK TEMP TUBE 12.7MM I/D

- ขนาดบรรจุภัณฑ์: **6 x MTR**
- Sleeve Diameter: 12.7 mm
 - Shrunk Diameter: 6.4 mm
 - Colour: Blue
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 6 m
 - Material: Polyolefin



7004756 12.7 mm

BLUE LOW SHRINK TEMP TUBE 19.0MM I/D

- ขนาดบรรจุภัณฑ์: **5 x MTR**
- Sleeve Diameter: 19 mm
 - Shrunk Diameter: 9.5 mm
 - Colour: Blue
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 5 m
 - Material: Polyolefin



7004759 19 mm

RS PRO HEAT SHRINK TUBING, WHITE 1.6MM SLEEVE DIA. X 10M LENGTH 2:1

- ขนาดบรรจุภัณฑ์: **10 x MTR**
- Sleeve Diameter: 1.6 mm
 - Shrunk Diameter: 0.8 mm
 - Colour: White
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 10 m
 - Material: Polyolefin



7004762 1.6 mm

WHITE LOW SHRINK TEMP TUBE 2.4MM I/D

- ขนาดบรรจุภัณฑ์: **10 x MTR**
- Sleeve Diameter: 2.4 mm
 - Shrunk Diameter: 1.2 mm
 - Colour: White
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 10 m
 - Material: Polyolefin



7004765 2.4 mm

WHITE LOW SHRINK TEMP TUBE 3.2MM I/D

- ขนาดบรรจุภัณฑ์: **10 x MTR**
- Sleeve Diameter: 3.2 mm
 - Shrunk Diameter: 1.6 mm
 - Colour: White
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 10 m
 - Material: Polyolefin



7004769 3.2 mm

WHITE LOW SHRINK TEMP TUBE 6.4MM I/D

- ขนาดบรรจุภัณฑ์: **8 x MTR**
- Sleeve Diameter: 6.4 mm
 - Shrunk Diameter: 3.2 mm
 - Colour: White
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 8 m
 - Material: Polyolefin



7004771 6.4 mm

WHITE LOW SHRINK TEMP TUBE 9.5MM I/D

- ขนาดบรรจุภัณฑ์: 6 x MTR
- Sleeve Diameter: 9.5 mm
 - Shrunk Diameter: 4.8 mm
 - Colour: White
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 6 m
 - Material: Polyolefin



7004775 9.5 mm

WHITE LOW SHRINK TEMP TUBE 4.8MM I/D

- ขนาดบรรจุภัณฑ์: 9 x MTR
- Sleeve Diameter: 4.8 mm
 - Shrunk Diameter: 2.4 mm
 - Colour: White
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 9 m
 - Material: Polyolefin



7004778 4.8 mm

RS PRO HEAT SHRINK TUBING, WHITE 25.4MM SLEEVE DIA. X 3M LENGTH 2:1

- ขนาดบรรจุภัณฑ์: 3 x MTR
- Sleeve Diameter: 25.4 mm
 - Shrunk Diameter: 12.7 mm
 - Colour: White
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 3 m
 - Material: Polyolefin



7004781 25.4 mm

WHITE LOW SHRINK TEMP TUBE 12.7MM I/D

- ขนาดบรรจุภัณฑ์: 6 x MTR
- Sleeve Diameter: 12.7 mm
 - Shrunk Diameter: 6.4 mm
 - Colour: White
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 6 m
 - Material: Polyolefin



7004784 12.7 mm

WHITE LOW SHRINK TEMP TUBE 19.0MM I/D

- ขนาดบรรจุภัณฑ์: 5 x MTR
- Sleeve Diameter: 19 mm
 - Shrunk Diameter: 9.5 mm
 - Colour: White
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 5 m
 - Material: Polyolefin



7004787 19 mm

CABLE TIES, ONE WRAP, HOOK/LOOP, 50 PCS, 200MML

- ขนาดบรรจุภัณฑ์: 1 x EA
- Width: 20 mm
 - Length: 200 mm
 - Hook Type: Hook & Loop
 - Pre-cut Width: 20 x 200 mm



4499189 20 mm

CABLE CLAMP, P CLIPS, NATURAL, 9.5MM DIA

- ขนาดบรรจุภัณฑ์: 100 x EA
- Closed Inside Diameter: 9.5 mm
 - Width: 12 mm
 - Fixing Hole Diameter: 5 mm
 - Material: Nylon
 - Coating/Lining: None
 - Colour: Natural



479538 9.5 mm

RS PRO 25.4MM NATURAL NYLON P CLIP

- ขนาดบรรจุภัณฑ์: 100 x EA
- Closed Inside Diameter: 25.4 mm
 - Width: 12 mm
 - Fixing Hole Diameter: 4.6 mm
 - Material: Nylon
 - Coating/Lining: None
 - Colour: Natural



479554 25.4 mm

RS PRO 7.9MM NATURAL NYLON 66 P CLIP

- ขนาดบรรจุภัณฑ์: 100 x EA
- Closed Inside Diameter: 7.9 mm
 - Width: 10 mm
 - Fixing Hole Diameter: 5 mm
 - Material: Nylon 66
 - Colour: Natural



2209397 7.9 mm

RS PRO 15.8MM NATURAL NYLON 66 P CLIP

- ขนาดบรรจุภัณฑ์: 100 x EA
- Closed Inside Diameter: 15.8 mm
 - Width: 14.4 mm
 - Fixing Hole Diameter: 5 mm
 - Material: Nylon 66
 - Colour: Natural



2209398 15.8 mm

RS PRO 5MM BLACK NYLON 66 P CLIP

- ขนาดบรรจุภัณฑ์: 100 x EA
- Closed Inside Diameter: 5 mm
 - Width: 9.6 mm
 - Fixing Hole Diameter: 4.8 mm
 - Material: Nylon 66
 - Colour: Black



2209399 5 mm

RS PRO CABLE CLAMP, BLACK NYLON 66, 9.4V-

- ขนาดบรรจุภัณฑ์: 100 x EA
- Closed Inside Diameter: 6.4 mm
 - Width: 10.1 mm
 - Fixing Hole Diameter: 4.6 mm
 - Material: Nylon 66
 - Colour: Black



2209400 6.4 mm

RS PRO 7.9MM BLACK NYLON 66 P CLIP

- ขนาดบรรจุภัณฑ์: 100 x EA
- Closed Inside Diameter: 7.9 mm
 - Width: 10 mm
 - Fixing Hole Diameter: 5 mm
 - Material: Nylon 66
 - Colour: Black



2209402 7.9 mm

RS PRO 9.5MM BLACK NYLON 66 P CLIP

- ขนาดบรรจุภัณฑ์: 100 x EA
- Closed Inside Diameter: 9.5 mm
 - Width: 12.3 mm
 - Fixing Hole Diameter: 5 mm
 - Material: Nylon 66
 - Colour: Black



2209403 9.5 mm

RS PRO 12.7MM BLACK NYLON 66 P CLIP

- ขนาดบรรจุภัณฑ์: 100 x EA
- Closed Inside Diameter: 12.7 mm
 - Width: 12.2 mm
 - Fixing Hole Diameter: 5 mm
 - Material: Nylon 66
 - Colour: Black



2209404 12.7 mm

RS PRO 15.8MM BLACK NYLON 66 P CLIP

- ขนาดบรรจุภัณฑ์: 100 x EA
- Closed Inside Diameter: 15.8 mm
 - Width: 14.4 mm
 - Fixing Hole Diameter: 5 mm
 - Material: Nylon 66
 - Colour: Black



2209405 15.8 mm

CABLE,P CLIP,NYLON,4.8/6.4MM DIA

- ขนาดบรรจุภัณฑ์: **25 x EA**
- Closed Inside Diameter: 6.4 mm
 - Width: 13 mm
 - Fixing Hole Diameter: 5 x 10.4 mm, 5.5 mm
 - Material: Nylon
 - Coating/Lining: None
 - Colour: Natural



4726396 6.4 mm

CABLE,P CLIP,NYLON 6.4/9.5MM DIA

- ขนาดบรรจุภัณฑ์: **25 x EA**
- Closed Inside Diameter: 9.5 mm
 - Width: 13 mm
 - Fixing Hole Diameter: 5 x 16.1 mm, 5.5 mm
 - Material: Nylon
 - Coating/Lining: None
 - Colour: Natural



4726403 9.5 mm

CABLE,P CLIP,NYLON,9.5/14.3,MM DIA

- ขนาดบรรจุภัณฑ์: **25 x EA**
- Closed Inside Diameter: 14.3 mm
 - Width: 13 mm
 - Fixing Hole Diameter: 5 x 20.7 mm, 5.5 mm
 - Material: Nylon
 - Coating/Lining: None
 - Colour: Natural



4726425 14.3 mm

RS PRO BLUE LOW-DENSITY POLYETHYLENE SOLDER SLEEVE

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Minimum Cable Diameter: 3.7 mm
 - Maximum Cable Diameter: 8 mm
 - Sleeve Length: 32.5 mm
 - Material: Low-Density Polyethylene
 - Dielectric Strength: 1 kV
 - Minimum Operating Temperature: -55 °C
 - Maximum Operating Temperature: +125 °C
 - Quantity: 1



8726280 3.7 mm

SOLDER SLEEVE SIZE 1

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Minimum Cable Diameter: 1.4 mm
 - Maximum Cable Diameter: 2.7 mm
 - Sleeve Length: 24.5 mm
 - Material: Low-Density Polyethylene
 - Dielectric Strength: 1 kV
 - Minimum Operating Temperature: -55 °C
 - Maximum Operating Temperature: +125 °C
 - Quantity: 1



8726283 1.4 mm

RS PRO BLUE LOW-DENSITY POLYETHYLENE SOLDER SLEEVE

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Minimum Cable Diameter: 2.3 mm
 - Maximum Cable Diameter: 4.5 mm
 - Sleeve Length: 29.3 mm
 - Material: Low-Density Polyethylene
 - Dielectric Strength: 1 kV
 - Minimum Operating Temperature: -55 °C
 - Maximum Operating Temperature: +125 °C
 - Quantity: 1



8726286 2.3 mm

SOLDER SLEEVE ASSORTMENT KIT

- ขนาดบรรจุภัณฑ์: **25 x EA**
- Minimum Cable Diameter: 1.4 mm
 - Maximum Cable Diameter: 13 mm
 - Material: Low-Density Polyethylene
 - Minimum Operating Temperature: -55 °C
 - Maximum Operating Temperature: +125 °C
 - Quantity: 25
 - Colour: Transparent
 - Standards Met: RoHS Compliant



8726296 1.4 mm

RS PRO BLUE LOW-DENSITY POLYETHYLENE SOLDER SLEEVE

- ขนาดบรรจุภัณฑ์: **25 x EA**
- Minimum Cable Diameter: 5.8 mm
 - Maximum Cable Diameter: 11.5 mm
 - Sleeve Length: 35.5 mm
 - Material: Low-Density Polyethylene
 - Dielectric Strength: 1 kV
 - Minimum Operating Temperature: -55 °C
 - Maximum Operating Temperature: +125 °C
 - Quantity: 1



8726299 5.8 mm

HEATSHRINK,CABLE,SLEEVE,CRIMP SPLICE TERMINAL,RED,X10

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Insulation: Insulated



4580702 Insulated

HEATSHRINK,CABLE,SLEEVE,CRIMP SPLICE TERMINAL,BLUE,X10

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Insulation: Insulated



4580718 Insulated

HEATSHRINK,CABLE,SLEEVE,CRIMP SPLICE TERMINAL,YELLOW,X10

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Insulation: Insulated



4580724 Insulated

HEAT SHRINK BUTT, RED 0.5-1.5MM

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Sleeve Length: 35 mm
 - Material: Copper
 - Voltage Rating: 600 V
 - Minimum Operating Temperature: -55 °C
 - Maximum Operating Temperature: +125 °C
 - Shrink Temperature: +150 °C
 - Colour: Red



8199870 35 mm

HEAT SHRINK BUTT BLUE 1.5-2.5MM

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Sleeve Length: 35 mm
 - Material: Copper
 - Voltage Rating: 600 V
 - Minimum Operating Temperature: -55 °C
 - Maximum Operating Temperature: +125 °C
 - Shrink Temperature: +150 °C
 - Colour: Blue



8199874 35 mm

RS PRO WIRE SPLICE CONNECTOR

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Sleeve Length: 41 mm
 - Material: Copper
 - Voltage Rating: 600 V
 - Minimum Operating Temperature: -55 °C
 - Maximum Operating Temperature: +125 °C
 - Shrink Temperature: +150 °C
 - Colour: Yellow



8199883 41 mm

RS PRO WIRE STRIPPER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Cable Stripper
 - For Use With: Smart Meter Cable



1749107 Cable Stripper

RS PRO WIRE STRIPPER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Cable Stripper
 - For Use With: Smart Meter Cable



1749108 Cable Stripper

RS PRO STEEL GALVANISED ADAPTABLE BOX, 75MM X 75MM X

- ขนาดบรรจุภัณฑ์: 1 x EA
- Material: Steel
 - Finish: Galvanised
 - Length: 75 mm
 - Width: 75 mm
 - Depth: 50 mm
 - Height: 75 mm
 - Knockout Size: 20/25 mm



563898 Steel

CONDUIT, STEEL, ADAPTABLE BOX, GALVANISED, 100X100X50MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Material: Steel
 - Finish: Galvanised
 - Number of Knockouts: 8
 - Length: 100 mm
 - Width: 100 mm
 - Depth: 50 mm
 - Height: 100 mm
 - Knockout Size: 20/25 mm



563905 Steel

RS PRO 304 STAINLESS STEEL SATIN ADAPTABLE ENCLOSURE BOX, 100MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Material: 304 Stainless Steel
 - Finish: Satin
 - Length: 100 mm
 - Width: 100 mm
 - Depth: 50 mm
 - Height: 100 mm



1219691 304 Stainless

RS PRO 304 STAINLESS STEEL SATIN ADAPTABLE ENCLOSURE BOX, 100MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Material: 304 Stainless Steel
 - Finish: Satin
 - Length: 100 mm
 - Width: 100 mm
 - Depth: 50 mm
 - Height: 160 mm



1219692 304 Stainless

RS PRO 304 STAINLESS STEEL SATIN ADAPTABLE ENCLOSURE BOX, 100MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Material: 304 Stainless Steel
 - Finish: Satin
 - Length: 100 mm
 - Width: 100 mm
 - Depth: 85 mm
 - Height: 100 mm



1219693 304 Stainless

RS PRO 304 STAINLESS STEEL SATIN ADAPTABLE ENCLOSURE BOX, 160MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Material: 304 Stainless Steel
 - Finish: Satin
 - Length: 160 mm
 - Width: 100 mm
 - Depth: 85 mm
 - Height: 160 mm



1219694 304 Stainless

RS PRO 304 STAINLESS STEEL SATIN ADAPTABLE ENCLOSURE BOX, 220MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Material: 304 Stainless Steel
 - Finish: Satin
 - Length: 220 mm
 - Width: 100 mm
 - Depth: 85 mm
 - Height: 220 mm



1219695 304 Stainless

RS PRO 304 STAINLESS STEEL SATIN ADAPTABLE ENCLOSURE BOX, 220MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Material: 304 Stainless Steel
 - Finish: Satin
 - Length: 220 mm
 - Width: 160 mm
 - Depth: 85 mm
 - Height: 220 mm



1219697 304 Stainless

RS PRO 304 STAINLESS STEEL SATIN ADAPTABLE ENCLOSURE BOX, 280MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Material: 304 Stainless Steel
 - Finish: Satin
 - Length: 280 mm
 - Width: 220 mm
 - Depth: 85 mm
 - Height: 280 mm



1219699 304 Stainless

RS PRO 304 STAINLESS STEEL SATIN ADAPTABLE BOX, 75MM X 75MM X

- ขนาดบรรจุภัณฑ์: 1 x EA
- Material: 304 Stainless Steel
 - Finish: Satin
 - Length: 75 mm
 - Width: 75 mm
 - Depth: 50 mm
 - Height: 75 mm



1466772 304 Stainless

RS PRO 316 STAINLESS STEEL SATIN ADAPTABLE ENCLOSURE BOX, 104MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Material: 316 Stainless Steel
 - Finish: Satin
 - Length: 104 mm
 - Width: 104 mm
 - Depth: 50 mm
 - Height: 104 mm



4711580 316 Stainless

RS PRO 316 STAINLESS STEEL SATIN ADAPTABLE ENCLOSURE BOX, 160MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Material: 316 Stainless Steel
 - Finish: Satin
 - Length: 160 mm
 - Width: 160 mm
 - Depth: 85 mm
 - Height: 160 mm



4711625 316 Stainless

RS PRO 316 STAINLESS STEEL SATIN ADAPTABLE ENCLOSURE BOX, 220MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Material: 316 Stainless Steel
 - Finish: Satin
 - Length: 220 mm
 - Width: 220 mm
 - Depth: 85 mm
 - Height: 220 mm



4711631 316 Stainless

RS PRO STEEL ADAPTABLE BOX, 75MM X 75MM X 50MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Material: Steel
 - Length: 75 mm
 - Width: 75 mm
 - Depth: 50 mm
 - Height: 75 mm



7639201 Steel

RS PRO STEEL ADAPTABLE BOX, 100MM X 100MM X 50MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Material: Steel
 - Length: 100 mm
 - Width: 100 mm
 - Depth: 50 mm
 - Height: 100 mm



7639204 Steel

RS PRO ADAPTABLE BOX, 150MM X 150MM X 50MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 150 mm
 - Width: 150 mm
 - Depth: 50 mm
 - Height: 150 mm



7639208 150 mm

RS PRO STEEL GALVANISED ADAPTABLE BOX, 150MM X 150MM X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Material: Steel
 - Finish: Galvanised
 - Length: 150 mm
 - Width: 150 mm
 - Depth: 50 mm
 - Height: 150 mm



7639242 Steel

RS PRO STEEL GALVANISED ADAPTABLE BOX, 100MM X 100MM X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Material: Steel
 - Finish: Galvanised
 - Length: 100 mm
 - Width: 100 mm
 - Depth: 50 mm
 - Height: 100 mm



7639248 Steel

RS PRO STEEL GALVANISED ADAPTABLE BOX, 75MM X 75MM X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Material: Steel
 - Finish: Galvanised
 - Length: 75 mm
 - Width: 75 mm
 - Depth: 50 mm
 - Height: 75 mm



7639251 Steel

RS PRO GREY BACK BOX, BS, IP20, 1 GANGS

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Number of Gangs: 1
 - Depth: 42 mm
 - Series: RS Metalclad
 - Earth Terminal: Yes
 - Width: 86 mm
 - Colour Shade: Grey
 - Colour: Grey
 - IP Rating: IP20



3611962 1

RS PRO GREY BACK BOX, BS, IP20, 2 GANGS

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Number of Gangs: 2
 - Depth: 42 mm
 - Series: RS Metalclad
 - Earth Terminal: Yes
 - Width: 147 mm
 - Colour Shade: Grey
 - Colour: Grey
 - IP Rating: IP20



3611984 2

RS PRO WHITE PVC ELECTRICAL ENCLOSURE, BS, 2 GANGS, 147 X 86 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Number of Gangs: 2
 - Depth: 32 mm
 - Series: Mini
 - Material: PVC
 - Earth Terminal: No
 - Width: 147 mm
 - Colour: White
 - Dimensions: 147 x 86 x 32 mm



9171615 2

RS PRO WHITE PVC BACK BOX, BS, 2 GANGS

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Number of Gangs: 2
 - Depth: 32 mm
 - Material: PVC
 - Series: Mini
 - Earth Terminal: No
 - Width: 147 mm
 - Colour: White
 - Fixing Standard: BS



9171637 2

CONNECTOR, TERMINAL, SCREW, SINGLE POLE, INTERLOCKING, TAB/TAB

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Number of Contacts: 1
 - Contact Material: Steel
 - Contact Plating: Zinc
 - Screw Size: M4
 - Wire Size: 22 → 12 AWG
 - Material: Polyamide
 - Fixing Centre: 11.2 mm
 - Current Rating: 20 A



425415 1

RS PRO BARRIER STRIP, 1 CONTACT, 20A, 600 V

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Number of Contacts: 1
 - Contact Material: Steel
 - Contact Plating: Zinc
 - Screw Size: M4
 - Wire Size: 22 → 12 AWG
 - Material: Polyamide
 - Fixing Centre: 11.2 mm
 - Current Rating: 20 A



425421 1

CONNECTOR, TERMINAL, GROUP PANEL, MIN

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Number of Contacts: 36
 - Pitch: 6.35 mm
 - Number of Rows: 2
 - Dimensions: 117 x 38 x 7.5 mm
 - Depth: 38 mm
 - Length: 117 mm
 - Width: 38 mm



433703 36

CONNECTOR, TERMINAL, TAG STRIP, STD

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Number of Contacts: 28
 - Pitch: 9.5 mm
 - Fixing Centre: 28.6 mm
 - Dimensions: 266.7 x 17.9 x 10.6 mm
 - Depth: 10.6 mm
 - Width: 17.9 mm
 - Length: 266.7 mm



433775 28

RS PRO BARRIER STRIP, 28 CONTACT, 6.3MM PITCH

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Number of Contacts: 28
 - Pitch: 6.3 mm
 - Fixing Centre: 28.6 mm
 - Dimensions: 194 x 16.7 x 4 mm
 - Depth: 4 mm
 - Width: 16.7 mm
 - Length: 194 mm



433781 28

RS PRO BARRIER STRIP, 9.5MM PITCH, 20A, 750 V, SCREW

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Pitch: 9.5 mm
 - Contact Material: Brass
 - Contact Plating: Tin
 - Wire Size: 12 AWG
 - Material: Polyamide
 - Current Rating: 20 A
 - Voltage Rating: 750 V
 - Minimum Operating Temperature: -40 °C



7638110 9.5 mm

RS PRO NATURAL STEEL SADDLE CLAMP, 20MM MAX. BUNDLE

- ขนาดบรรจุภัณฑ์: **50 x EA**
- Cable Clip/Clamp Style: Saddle Clamp
 - Maximum Bundle Diameter: 20 mm
 - Affixing Method: Screw
 - Material: Steel
 - Colour: Natural



605100 Saddle Clamp

RS PRO NATURAL GALVANISED STEEL SADDLE CLAMP, 20MM MAX. BUNDLE

- ขนาดบรรจุภัณฑ์: **25 x EA**
- Cable Clip/Clamp Style: Saddle Clamp
 - Maximum Bundle Diameter: 20 mm
 - Affixing Method: Screw
 - Material: Galvanised Steel
 - Colour: Natural



606002 Saddle Clamp

RS PRO NATURAL STEEL SADDLE CLAMP, 25MM MAX. BUNDLE

- ขนาดบรรจุภัณฑ์: **25 x EA**
- Cable Clip/Clamp Style: Saddle Clamp
 - Maximum Bundle Diameter: 25 mm
 - Affixing Method: Screw
 - Material: Steel
 - Colour: Natural



606018 Saddle Clamp

RS PRO BLACK STEEL SADDLE CLAMP, 20MM MAX. BUNDLE

- ขนาดบรรจุภัณฑ์: **50 x EA**
- Cable Clip/Clamp Style: Saddle Clamp
 - Maximum Bundle Diameter: 20 mm
 - Affixing Method: Screw
 - Material: Steel
 - Colour: Black



608121 Saddle Clamp

RS PRO BLACK STEEL SADDLE CLAMP, 20MM MAX. BUNDLE

- ขนาดบรรจุภัณฑ์: **25 x EA**
- Cable Clip/Clamp Style: Saddle Clamp
 - Maximum Bundle Diameter: 20 mm
 - Affixing Method: Screw
 - Material: Steel
 - Colour: Black



608143 Saddle Clamp

RS PRO BLACK NYLON P CLAMP, 20MM MAX. BUNDLE

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Cable Clip/Clamp Style: P Clamp
 - Maximum Bundle Diameter: 20 mm
 - Affixing Method: Screw
 - Material: Nylon
 - Colour: Black



614019 P Clamp

RS PRO STEEL SADDLE CLAMP, 25MM MAX. BUNDLE

- ขนาดบรรจุภัณฑ์: **50 x EA**
- Cable Clip/Clamp Style: Saddle Clamp
 - Maximum Bundle Diameter: 25 mm
 - Affixing Method: Screw
 - Material: Steel



651513 Saddle Clamp

CONDUIT, P CLIP, PLATED STEEL, PVC INSERT, 10MM, 5MM FIXING

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Cable Clip/Clamp Style: P Clamp
 - Maximum Bundle Diameter: 10 mm
 - Affixing Method: Screw
 - Material: Plated Steel
 - Colour: Black
 - Width: 12.7 mm
 - Depth: 1.4 mm
 - Dimensions [L x W (x D)]: 12.7 x 1.4 mm



1865353 P Clamp

CONDUIT, P CLIP, PLATED STEEL, PVC INSERT, 12MM, 5MM FIXING

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Cable Clip/Clamp Style: P Clamp
 - Maximum Bundle Diameter: 14 mm
 - Affixing Method: Screw
 - Material: Plated Steel
 - Colour: Black
 - Width: 12.7 mm
 - Depth: 1.4 mm
 - Dimensions [L x W (x D)]: 12.7 x 1.4 mm



1865375 P Clamp

CONDUIT, P CLIP, PLATED STEEL, PVC INSERT, 16MM, 5MM FIXING

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Cable Clip/Clamp Style: P Clamp
 - Maximum Bundle Diameter: 16 mm
 - Affixing Method: Screw
 - Material: Plated Steel
 - Colour: Black
 - Width: 12.7 mm
 - Depth: 1.4 mm
 - Dimensions [L x W (x D)]: 12.7 x 1.4 mm



1865381 P Clamp

CONDUIT, P CLIP, PLATED STEEL, PVC INSERT, 20MM, 5MM FIXING

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Cable Clip/Clamp Style: P Clamp
 - Maximum Bundle Diameter: 20 mm
 - Affixing Method: Screw
 - Material: Plated Steel
 - Colour: Black
 - Width: 12.7 mm
 - Depth: 1.4 mm
 - Dimensions [L x W (x D)]: 12.7 x 1.4 mm



1865397 P Clamp

CONDUIT, P CLIP, PLATED STEEL, PVC INSERT, 25MM, 5MM FIXING

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Cable Clip/Clamp Style: P Clamp
 - Maximum Bundle Diameter: 25 mm
 - Affixing Method: Screw
 - Material: Plated Steel
 - Colour: Black
 - Width: 12.7 mm
 - Depth: 1.4 mm
 - Dimensions [L x W (x D)]: 12.7 x 1.4 mm



1865404 P Clamp

CONDUIT, P CLIP, PLATED STEEL, PVC INSERT, 32MM, 5MM FIXING

- ขนาดบรรจุภัณฑ์: **2 x EA**
- Cable Clip/Clamp Style: P Clamp
 - Maximum Bundle Diameter: 32 mm
 - Affixing Method: Screw
 - Material: Plated Steel
 - Colour: Black
 - Width: 12.7 mm
 - Depth: 1.4 mm
 - Dimensions [L x W (x D)]: 12.7 x 1.4 mm



1865410 P Clamp

RS PRO BLACK PLATED STEEL P CLAMP, 40MM MAX. BUNDLE

- ขนาดบรรจุภัณฑ์: **2 x EA**
- Cable Clip/Clamp Style: P Clamp
 - Maximum Bundle Diameter: 40 mm
 - Affixing Method: Screw
 - Material: Plated Steel
 - Colour: Black
 - Width: 19.1 mm
 - Depth: 2.4 mm
 - Dimensions [L x W (x D)]: 19.1 x 2.4 mm



2875581 P Clamp

RS PRO BLACK PLATED STEEL P CLAMP, 50MM MAX. BUNDLE

- ขนาดบรรจุภัณฑ์: **2 x EA**
- Cable Clip/Clamp Style: P Clamp
 - Maximum Bundle Diameter: 50 mm
 - Affixing Method: Screw
 - Material: Plated Steel
 - Colour: Black
 - Width: 25.4 mm
 - Depth: 2.4 mm
 - Dimensions [L x W (x D)]: 25.4 x 2.4 mm



2875597 P Clamp

RS PRO SILVER 316 STAINLESS STEEL SADDLE CLAMP, 20MM MAX. BUNDLE

- ขนาดบรรจุภัณฑ์: **4 x EA**
- Cable Clip/Clamp Style: Saddle Clamp
 - Maximum Bundle Diameter: 20 mm
 - Affixing Method: Screw
 - Material: 316 Stainless Steel
 - Colour: Silver
 - Dimensions [L x W (x D)]: 19.3 x 18.2 mm



4711300 Saddle Clamp

RS PRO SILVER 316 STAINLESS STEEL SADDLE CLAMP, 25MM MAX. BUNDLE

- ขนาดบรรจุภัณฑ์: **4 x EA**
- Cable Clip/Clamp Style: Saddle Clamp
 - Maximum Bundle Diameter: 25 mm
 - Affixing Method: Screw
 - Material: 316 Stainless Steel
 - Colour: Silver
 - Dimensions [L x W (x D)]: 56 x 19.3 x 19.5 mm



4711316 Saddle Clamp

LOCKNUT, BRASS, NICKEL PLATED, M16

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Material: Brass
 - Thread Size: M16



127164 Brass

CONDUIT, LOCKNUTS, NYLON, BLACK, METRIC, M16, 6.7MM THICK, 19MM A/F

- ขนาดบรรจุภัณฑ์: **25 x EA**
- Material: PA 6
 - Thread Size: M16
 - Colour: Black
 - Minimum Operating Temperature: -20 °C
 - Maximum Operating Temperature: +80 °C



127259 PA 6

LOCKNUT,BRASS,NICKEL PLATED,M40

ขนาดบรรจุภัณฑ์: **10 x EA**
 • Material: Brass
 • Thread Size: M40
 • Colour: Nickel



127388 Brass

CONDUIT,LOCKNUTS,NYLON,BLACK, METRIC,M20,8MM THICK,23MM A/F

ขนาดบรรจุภัณฑ์: **25 x EA**
 • Material: PA 6
 • Thread Size: M20
 • Colour: Black
 • Minimum Operating Temperature: -20 °C
 • Maximum Operating Temperature: +80 °C



127417 PA 6

RS PRO BLACK NYLON CABLE GLAND LOCKNUT, PG13.5 THREAD

ขนาดบรรจุภัณฑ์: **25 x EA**
 • Material: Nylon
 • Thread Size: PG13.5
 • Colour: Black
 • Minimum Operating Temperature: -20 °C
 • Maximum Operating Temperature: +80 °C



127423 Nylon

LOCKNUT,BRASS,NICKEL PLATED,M20

ขนาดบรรจุภัณฑ์: **10 x EA**
 • Material: Nickel Plated Brass
 • Thread Size: M20
 • Colour: Nickel



127473 Nickel Plated

LOCKNUT,BRASS,NICKEL PLATED,M25

ขนาดบรรจุภัณฑ์: **10 x EA**
 • Material: Brass
 • Thread Size: M25



127489 Brass

LOCKNUT,BRASS,NICKEL PLATED,M32

ขนาดบรรจุภัณฑ์: **10 x EA**
 • Material: Brass
 • Thread Size: M32



127495 Brass

LOCKNUT,BRASS,NICKEL PLATED,M50

ขนาดบรรจุภัณฑ์: **10 x EA**
 • Material: Brass
 • Thread Size: M50



127502 Brass

CONDUIT,LOCKNUTS,NYLON,BLACK, METRIC,M32,9MM THICK,37MM A/F

ขนาดบรรจุภัณฑ์: **5 x EA**
 • Material: PA 6
 • Thread Size: M32
 • Colour: Black
 • Minimum Operating Temperature: -20 °C
 • Maximum Operating Temperature: +80 °C



127524 PA 6

CONDUIT,LOCKNUTS,NYLON,BLACK, METRIC,M50,10MM THICK,60MM A/F

ขนาดบรรจุภัณฑ์: **5 x EA**
 • Material: PA 6
 • Thread Size: M50
 • Colour: Black
 • Minimum Operating Temperature: -20 °C
 • Maximum Operating Temperature: +80 °C



127530 PA 6

CONDUIT,LOCKNUTS,NYLON,BLACK, METRIC,M40,10MM THICK,50MM A/F

ขนาดบรรจุภัณฑ์: **5 x EA**
 • Material: PA 6
 • Thread Size: M40
 • Colour: Black
 • Minimum Operating Temperature: -20 °C
 • Maximum Operating Temperature: +80 °C



127546 PA 6

CONDUIT,LOCKNUTS,NYLON,BLACK, METRIC,M25,9MM THICK,28MM A/F

ขนาดบรรจุภัณฑ์: **25 x EA**
 • Material: PA 6
 • Thread Size: M25
 • Colour: Black
 • Minimum Operating Temperature: -20 °C
 • Maximum Operating Temperature: +80 °C



127653 PA 6

RS PRO BLACK STEEL CABLE GLAND LOCKNUT, M16 THREAD

ขนาดบรรจุภัณฑ์: **10 x EA**
 • Material: Steel
 • Thread Size: M16
 • Colour: Black



608806 Steel

CONDUIT,LOCKNUT,STEEL,BLACK ENAMELLED,20MM,27AF

ขนาดบรรจุภัณฑ์: **10 x EA**
 • Material: Steel
 • Thread Size: M20
 • Colour: Black



608812 Steel

RS PRO BLACK STEEL CABLE GLAND LOCKNUT, M25 THREAD

ขนาดบรรจุภัณฑ์: **10 x EA**
 • Material: Steel
 • Thread Size: M25
 • Colour: Black



608828 Steel

RS PRO BLACK STEEL CABLE GLAND LOCKNUT, M32 THREAD

ขนาดบรรจุภัณฑ์: **10 x EA**
 • Material: Steel
 • Thread Size: M32
 • Colour: Black



608834 Steel

CONDUIT,LOCKNUTS,STEEL,GALVANI SED,16MM,22 AF

ขนาดบรรจุภัณฑ์: **10 x EA**
 • Material: Steel
 • Thread Size: M16
 • Colour: Silver
 • For Use With: All ISO Threaded Conduit Fittings & Accessories



621102 Steel

RS PRO SILVER STEEL CABLE GLAND LOCKNUT, M20 THREAD

ขนาดบรรจุภัณฑ์: 10 x EA

- Material: Steel
- Thread Size: M20
- Colour: Silver
- For Use With: All ISO Threaded Conduit Fittings & Accessories



621118 Steel

CONDUIT, LOCKNUTS, STEEL, GALVANI SED, 25MM, 35 AF

ขนาดบรรจุภัณฑ์: 10 x EA

- Material: Steel
- Thread Size: M25
- Colour: Silver
- For Use With: All ISO Threaded Conduit Fittings & Accessories



621124 Steel

RS PRO SILVER STEEL CABLE GLAND LOCKNUT, M32 THREAD

ขนาดบรรจุภัณฑ์: 10 x EA

- Material: Steel
- Thread Size: M32
- Colour: Silver
- For Use With: All ISO Threaded Conduit Fittings & Accessories



621130 Steel

RS PRO SILVER 316 STAINLESS STEEL CABLE GLAND LOCKNUT, M20

ขนาดบรรจุภัณฑ์: 10 x EA

- Material: 316 Stainless Steel
- Thread Size: M20
- Colour: Silver
- IP Rating: IP66, IP67



4711394 316 Stainless

RS PRO SILVER 316 STAINLESS STEEL CABLE GLAND LOCKNUT, M25

ขนาดบรรจุภัณฑ์: 10 x EA

- Material: 316 Stainless Steel
- Thread Size: M25
- Colour: Silver



4711401 316 Stainless

TAPE, WIREMAN, COILED SPRING STEEL, 10M

ขนาดบรรจุภัณฑ์: 1 x EA

- Routing Tool Type: Draw Wire
- Maximum Length: 10 m
- Material: Spring Steel
- Kit Includes: Tape



2902560 Draw Wire

RS PRO SPRING STEEL CABLE ROD DRAW WIRE

ขนาดบรรจุภัณฑ์: 1 x EA

- Routing Tool Type: Draw Wire
- Maximum Length: 20 m
- Material: Spring Steel
- Kit Includes: Tape



2902576 Draw Wire

TAPE, WIREMAN, PLAIN TAPE AND WINDER

ขนาดบรรจุภัณฑ์: 1 x EA

- Routing Tool Type: Draw Wire
- Maximum Length: 15 m
- Material: Spring Steel
- Kit Includes: Tape



2902605 Draw Wire

RS PRO GLASS FIBRE REINFORCED PLASTIC (GRP) CABLE ROD DRAW

ขนาดบรรจุภัณฑ์: 1 x EA

- Routing Tool Type: Draw Wire
- Maximum Length: 15 m
- Material: Glass Fibre Reinforced Plastic (GRP)
- Kit Includes: Tape



2902627 Draw Wire

ROUND NYLON WIREMANS TAPE 10M

ขนาดบรรจุภัณฑ์: 1 x EA

- Routing Tool Type: Draw Wire
- Maximum Length: 10 m
- Material: Nylon
- Kit Includes: Nylon Cable Rod With Cable Grip



9184970 Draw Wire

ROUND NYLON WIREMANS TAPE 20M

ขนาดบรรจุภัณฑ์: 1 x EA

- Routing Tool Type: Draw Wire
- Maximum Length: 20 m
- Material: Nylon
- Kit Includes: Nylon Cable Rod With Cable Grip



9184977 Draw Wire

WIRE, 304 STAINLESS STEEL 3M X 100 MM X 30 MM WING

ขนาดบรรจุภัณฑ์: 8 x EA

- Tray/Basket Type: Wire Tray
- Length: 3 m
- Width: 100 mm
- Depth: 30 mm wing
- Material: 304 Stainless Steel



2216323 Wire Tray

TRUNKING, FLEXIBLE, SLOTTED, SELF ADHESIVE, 9X11X500MM

ขนาดบรรจุภัณฑ์: 10 x EA

- Width: 9 mm
- Depth: 11 mm
- Trunking/Chain Type: Slotted Flexible Panel Trunking
- Colour: White
- Material: Polypropylene
- Length: 0.5 m
- Slot Type: Flexible
- Fire Behaviour: Flame Retardant, Halogen Free, Low Smoke Density, Self-extinguishing



598591 9 mm

TRUNKING, FLEXIBLE, SLOTTED, SELF ADHESIVE, 20X500MM

ขนาดบรรจุภัณฑ์: 10 x EA

- Width: 20 mm
- Depth: 20 mm
- Trunking/Chain Type: Slotted Flexible Panel Trunking
- Colour: White
- Material: Polypropylene
- Length: 0.5 m
- Slot Type: Flexible
- Fire Behaviour: Flame Retardant, Halogen Free, Low Smoke Density, Self-extinguishing



598608 20 mm

TRUNKING, FLEXIBLE, SLOTTED, SELF ADHESIVE, 30X500MM

ขนาดบรรจุภัณฑ์: 10 x EA

- Width: 30 mm
- Depth: 30 mm
- Trunking/Chain Type: Slotted Flexible Panel Trunking
- Colour: White
- Material: Polypropylene
- Length: 0.5 m
- Slot Type: Flexible
- Fire Behaviour: Flame Retardant, Halogen Free, Low Smoke Density, Self-extinguishing



598614 30 mm

TRUNKING, FLEXIBLE, SLOTTED, SELF ADHESIVE, 40X500MM

ขนาดบรรจุภัณฑ์: 5 x EA

- Width: 40 mm
- Depth: 40 mm
- Trunking/Chain Type: Slotted Flexible Panel Trunking
- Colour: White
- Material: Polypropylene
- Length: 0.5 m
- Slot Type: Flexible
- Fire Behaviour: Flame Retardant, Halogen Free, Low Smoke Density, Self-extinguishing



598620 40 mm

RS PRO GREY SLOTTED PANEL TRUNKING - OPEN SLOT, W100 MM X

- ขนาดบรรจุภัณฑ์: **12 x EA**
- Width: 100 mm
 - Depth: 80 mm
 - Trunking/Chain Type: Slotted Panel Trunking
 - Colour: Grey
 - Material: PVC
 - Length: 2 m
 - Slot Type: Open
 - Fire Behaviour: Self-extinguishing



1548103 100 mm

RS PRO WHITE PARAPET TRUNKING, W130 MM X D70MM, L2M, PVC

- ขนาดบรรจุภัณฑ์: **6 x EA**
- Width: 130 mm
 - Depth: 70 mm
 - Trunking/Chain Type: Parapet Trunking
 - Colour: White
 - Material: PVC
 - Length: 2 m



2215295 130 mm

RS PRO BLACK SLOTTED PANEL TRUNKING - OPEN SLOT, W25 MM X

- ขนาดบรรจุภัณฑ์: **12 x EA**
- Width: 25 mm
 - Depth: 50 mm
 - Trunking/Chain Type: Slotted Panel Trunking
 - Colour: Black
 - Material: PVC
 - Length: 2 m
 - Slot Type: Open
 - Series: Wiring Duct



2339167 25 mm

RS PRO BLACK SLOTTED PANEL TRUNKING - OPEN SLOT, W25 MM X

- ขนาดบรรจุภัณฑ์: **4 x EA**
- Width: 25 mm
 - Depth: 50 mm
 - Trunking/Chain Type: Slotted Panel Trunking
 - Colour: Black
 - Material: PVC
 - Length: 1 m
 - Slot Type: Open
 - Series: Wiring Duct



2339168 25 mm

RS PRO OPEN SLOT 8MM WIRING DUCT, GREY P

- ขนาดบรรจุภัณฑ์: **4 x EA**
- Width: 25 mm
 - Depth: 50 mm
 - Trunking/Chain Type: Slotted Panel Trunking
 - Colour: Grey
 - Material: PVC
 - Length: 1 m
 - Slot Type: Open
 - Series: Wiring Duct



2339169 25 mm

RS PRO GREY SLOTTED PANEL TRUNKING - OPEN SLOT, W25 MM X

- ขนาดบรรจุภัณฑ์: **4 x EA**
- Width: 25 mm
 - Depth: 75 mm
 - Trunking/Chain Type: Slotted Panel Trunking
 - Colour: Grey
 - Material: PVC
 - Length: 1 m
 - Slot Type: Open
 - Series: Wiring Duct



2339172 25 mm

RS PRO GREY SLOTTED PANEL TRUNKING - OPEN SLOT, W50 MM X

- ขนาดบรรจุภัณฑ์: **4 x EA**
- Width: 50 mm
 - Depth: 25 mm
 - Trunking/Chain Type: Slotted Panel Trunking
 - Colour: Grey
 - Material: PVC
 - Length: 1 m
 - Slot Type: Open
 - Series: Wiring Duct



2339175 50 mm

RS PRO BLACK SLOTTED PANEL TRUNKING - OPEN SLOT, W50 MM X

- ขนาดบรรจุภัณฑ์: **4 x EA**
- Width: 50 mm
 - Depth: 50 mm
 - Trunking/Chain Type: Slotted Panel Trunking
 - Colour: Black
 - Material: PVC
 - Length: 1 m
 - Slot Type: Open
 - Series: Wiring Duct



2339176 50 mm

RS PRO GREY SLOTTED PANEL TRUNKING - OPEN SLOT, W50 MM X

- ขนาดบรรจุภัณฑ์: **4 x EA**
- Width: 50 mm
 - Depth: 50 mm
 - Trunking/Chain Type: Slotted Panel Trunking
 - Colour: Grey
 - Material: PVC
 - Length: 1 m
 - Slot Type: Open
 - Series: Wiring Duct



2339177 50 mm

RS PRO BLACK SLOTTED PANEL TRUNKING - CLOSED SLOT, W25 MM X

- ขนาดบรรจุภัณฑ์: **4 x EA**
- Width: 25 mm
 - Depth: 30 mm
 - Trunking/Chain Type: Slotted Panel Trunking
 - Colour: Black
 - Material: PVC
 - Length: 1 m
 - Slot Type: Closed
 - Series: Wiring Duct



2339187 25 mm

RS PRO GREY SLOTTED PANEL TRUNKING - CLOSED SLOT, W40 MM

- ขนาดบรรจุภัณฑ์: **12 x EA**
- Width: 25 mm
 - Depth: 40 mm
 - Trunking/Chain Type: Slotted Panel Trunking
 - Colour: Grey
 - Material: PVC
 - Length: 2 m
 - Slot Type: Closed
 - Series: Wiring Duct



2339188 40 mm

RS PRO BLACK SLOTTED PANEL TRUNKING - OPEN SLOT, W25 MM X

- ขนาดบรรจุภัณฑ์: **4 x EA**
- Width: 25 mm
 - Depth: 40 mm
 - Trunking/Chain Type: Slotted Panel Trunking
 - Colour: Black
 - Material: PVC
 - Length: 1 m
 - Slot Type: Open
 - Series: Wiring Duct



2339191 25 mm

RS PRO WHITE MINI TRUNKING, W18 MM X D18MM, L2M, PVC

- ขนาดบรรจุภัณฑ์: **8 x EA**
- Width: 18 mm
 - Depth: 18 mm
 - Trunking/Chain Type: Mini Trunking
 - Colour: White
 - Material: PVC
 - Length: 2 m



2374041 18 mm

RS PRO WHITE MINI TRUNKING, W30 MM X D30MM, L2M, PVC

- ขนาดบรรจุภัณฑ์: **25 x EA**
- Width: 30 mm
 - Depth: 30 mm
 - Trunking/Chain Type: Mini Trunking
 - Colour: White
 - Material: PVC
 - Length: 2 m



2374042 30 mm

RS PRO WHITE MINI TRUNKING, W30 MM X D30MM, L2M, PVC

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Width: 30 mm
 - Depth: 30 mm
 - Trunking/Chain Type: Mini Trunking
 - Colour: White
 - Material: PVC
 - Length: 2 m



2374043 30 mm

RS PRO WHITE MINI TRUNKING, W40 MM X D40MM, L2M, PVC

- ขนาดบรรจุภัณฑ์: **16 x EA**
- Width: 40 mm
 - Depth: 40 mm
 - Trunking/Chain Type: Mini Trunking
 - Colour: White
 - Material: PVC
 - Length: 2 m



2374046 40 mm

RS PRO WHITE MINI TRUNKING, W40 MM X D40MM, L2M, PVC

- ขนาดบรรจุภัณฑ์: 4 x EA
- Width: 40 mm
 - Depth: 40 mm
 - Trunking/Chain Type: Mini Trunking
 - Colour: White
 - Material: PVC
 - Length: 2 m



2374047 40 mm

RS PRO WHITE MINI TRUNKING, W60 MM X D40MM, L2M, PVC

- ขนาดบรรจุภัณฑ์: 14 x EA
- Width: 60 mm
 - Depth: 40 mm
 - Trunking/Chain Type: Mini Trunking
 - Colour: White
 - Material: PVC
 - Length: 2 m



2374048 60 mm

RS PRO WHITE MINI TRUNKING, W60 MM X D60MM, L2M, PVC

- ขนาดบรรจุภัณฑ์: 12 x EA
- Width: 60 mm
 - Depth: 60 mm
 - Trunking/Chain Type: Mini Trunking
 - Colour: White
 - Material: PVC
 - Length: 2 m



2374051 60 mm

RS PRO WHITE MINI TRUNKING, W60 MM X D60MM, L2M, PVC

- ขนาดบรรจุภัณฑ์: 4 x EA
- Width: 60 mm
 - Depth: 60 mm
 - Trunking/Chain Type: Mini Trunking
 - Colour: White
 - Material: PVC
 - Length: 2 m



2374052 60 mm

RS PRO GREY SLOTTED PANEL TRUNKING - OPEN SLOT, W25 MM X

- ขนาดบรรจุภัณฑ์: 8 x EA
- Width: 25 mm
 - Depth: 25 mm
 - Trunking/Chain Type: Slotted Panel Trunking
 - Colour: Grey
 - Material: PVC
 - Length: 2 m
 - Slot Type: Open
 - Fire Behaviour: Self-extinguishing



3011924 25 mm

RS PRO GREY SLOTTED PANEL TRUNKING - OPEN SLOT, W50 MM X

- ขนาดบรรจุภัณฑ์: 8 x EA
- Width: 50 mm
 - Depth: 50 mm
 - Trunking/Chain Type: Slotted Panel Trunking
 - Colour: Grey
 - Material: PVC
 - Length: 2 m
 - Slot Type: Open
 - Fire Behaviour: Self-extinguishing



3011974 50 mm

RS PRO GREY SLOTTED PANEL TRUNKING - OPEN SLOT, W25 MM X

- ขนาดบรรจุภัณฑ์: 4 x EA
- Width: 25 mm
 - Depth: 25 mm
 - Trunking/Chain Type: Slotted Panel Trunking
 - Colour: Grey
 - Material: PVC
 - Length: 1 m
 - Slot Type: Open
 - Fire Behaviour: Self-extinguishing



8793713 25 mm

RS PRO GREY SLOTTED PANEL TRUNKING - OPEN SLOT, W60 MM X

- ขนาดบรรจุภัณฑ์: 4 x EA
- Width: 60 mm
 - Depth: 60 mm
 - Trunking/Chain Type: Slotted Panel Trunking
 - Colour: Grey
 - Material: PVC
 - Length: 1 m
 - Slot Type: Open
 - Fire Behaviour: Self-extinguishing



8793722 60 mm

RS PRO GREY SLOTTED PANEL TRUNKING - NARROW SLOT, W40 MM X

- ขนาดบรรจุภัณฑ์: 4 x EA
- Width: 40 mm
 - Depth: 40 mm
 - Trunking/Chain Type: Slotted Panel Trunking
 - Colour: Grey
 - Material: PVC
 - Length: 1 m
 - Slot Type: Narrow
 - Fire Behaviour: Self-extinguishing



8793725 40 mm

RS PRO GREY SLOTTED PANEL TRUNKING - OPEN SLOT, W100 MM X

- ขนาดบรรจุภัณฑ์: 4 x EA
- Width: 100 mm
 - Depth: 100 mm
 - Trunking/Chain Type: Slotted Panel Trunking
 - Colour: Grey
 - Material: PVC
 - Length: 1 m
 - Slot Type: Open
 - Fire Behaviour: Self-extinguishing



8793729 100 mm

RS PRO GREY SLOTTED PANEL TRUNKING - OPEN SLOT, W40 MM X

- ขนาดบรรจุภัณฑ์: 4 x EA
- Width: 40 mm
 - Depth: 60 mm
 - Trunking/Chain Type: Slotted Panel Trunking
 - Colour: Grey
 - Material: PVC
 - Length: 1 m
 - Slot Type: Open
 - Fire Behaviour: Self-extinguishing



8793731 40 mm

RS PRO GREY SLOTTED PANEL TRUNKING - OPEN SLOT, W80 MM X

- ขนาดบรรจุภัณฑ์: 4 x EA
- Width: 80 mm
 - Depth: 80 mm
 - Trunking/Chain Type: Slotted Panel Trunking
 - Colour: Grey
 - Material: PVC
 - Length: 1 m
 - Slot Type: Open
 - Fire Behaviour: Self-extinguishing



8793735 80 mm

RS PRO GREY SLOTTED PANEL TRUNKING - OPEN SLOT, W40 MM X

- ขนาดบรรจุภัณฑ์: 4 x EA
- Width: 40 mm
 - Depth: 80 mm
 - Trunking/Chain Type: Slotted Panel Trunking
 - Colour: Grey
 - Material: PVC
 - Length: 1 m
 - Slot Type: Open
 - Fire Behaviour: Self-extinguishing



8793738 40 mm

RS PRO GREY SLOTTED PANEL TRUNKING - NARROW SLOT, W40 MM X

- ขนาดบรรจุภัณฑ์: 4 x EA
- Width: 40 mm
 - Depth: 60 mm
 - Trunking/Chain Type: Slotted Panel Trunking
 - Colour: Grey
 - Material: PVC
 - Length: 1 m
 - Slot Type: Narrow
 - Fire Behaviour: Self-extinguishing



8793741 40 mm

RS PRO GREY SLOTTED PANEL TRUNKING - OPEN SLOT, W60 MM X

- ขนาดบรรจุภัณฑ์: 4 x EA
- Width: 60 mm
 - Depth: 80 mm
 - Trunking/Chain Type: Slotted Panel Trunking
 - Colour: Grey
 - Material: PVC
 - Length: 1 m
 - Slot Type: Open
 - Fire Behaviour: Self-extinguishing



8793744 60 mm

RS PRO GREY SLOTTED PANEL TRUNKING - NARROW SLOT, W40 MM X

- ขนาดบรรจุภัณฑ์: 4 x EA
- Width: 40 mm
 - Depth: 80 mm
 - Trunking/Chain Type: Slotted Panel Trunking
 - Colour: Grey
 - Material: PVC
 - Length: 1 m
 - Slot Type: Narrow
 - Fire Behaviour: Self-extinguishing



8793747 40 mm

RS PRO GREY SLOTTED PANEL TRUNKING - NARROW SLOT, W60 MM

- ขนาดบรรจุภัณฑ์: 4 x EA
- Width: 60 mm
 - Depth: 80 mm
 - Trunking/Chain Type: Slotted Panel Trunking
 - Colour: Grey
 - Material: PVC
 - Length: 1 m
 - Slot Type: Narrow
 - Fire Behaviour: Self-extinguishing



8793750 60 mm

RS PRO GREY SLOTTED PANEL TRUNKING - OPEN SLOT, W80 MM X

- ขนาดบรรจุภัณฑ์: 4 x EA
- Width: 80 mm
 - Depth: 80 mm
 - Trunking/Chain Type: Slotted Panel Trunking
 - Colour: Grey
 - Material: PVC
 - Length: 1 m
 - Slot Type: Open
 - Fire Behaviour: Self-extinguishing



8793753 80 mm

RS PRO GALVANISED STEEL CABLE TRUNKING ACCESSORY, 50 X 50MM

- ขนาดบรรจุภัณฑ์: 2 x EA
- Trunking Accessory Type: Flanged Coupler
 - Material: Galvanised Steel
 - Width: 50 mm
 - Height: 50 mm
 - Dimensions: 50 x 50 mm
 - Series: Galvanised Steel



562930 Flanged Coupler

RS PRO GALVANISED STEEL CABLE TRUNKING ACCESSORY, 75 X 75MM

- ขนาดบรรจุภัณฑ์: 2 x EA
- Trunking Accessory Type: Flanged Coupler
 - Material: Galvanised Steel
 - Width: 75 mm
 - Height: 75 mm
 - Dimensions: 75 x 75 mm
 - Series: Galvanised Steel



562946 Flanged Coupler

RS PRO PVC CABLE TRUNKING END CAP, 110 X 70MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Trunking Accessory Type: End Cap
 - Material: PVC
 - Dimensions: 110 x 70 mm



2215304 End Cap

RS PRO PVC CABLE TRUNKING, 110 X 70MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Trunking Accessory Type: Flat Angle
 - Material: PVC
 - Dimensions: 110 x 70 mm



2215306 Flat Angle

RS PRO PVC CABLE TRUNKING FLAT CORNER

- ขนาดบรรจุภัณฑ์: 1 x EA
- Trunking Accessory Type: Mounting Box
 - Material: PVC
 - Height: 45 mm



2215308 Mounting Box

RS PRO PVC CABLE TRUNKING SOCKET BOX

- ขนาดบรรจุภัณฑ์: 1 x EA
- Trunking Accessory Type: Mounting Box
 - Material: PVC
 - Height: 45 mm



2215309 Mounting Box

RS PRO 304 STAINLESS STEEL CABLE TRUNKING ACCESSORY, 75 X 75MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Trunking Accessory Type: 90° Bend Front Lid
 - Material: 304 Stainless Steel
 - Width: 75 mm
 - Height: 75 mm
 - Dimensions: 75 x 75 mm
 - Series: Stainless Steel
 - Standards Met: UL



4711451 90° Bend Front

RS PRO 304 STAINLESS STEEL CABLE TRUNKING ACCESSORY, 75 X 75MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Trunking Accessory Type: Coupling
 - Material: 304 Stainless Steel
 - Width: 75 mm
 - Height: 75 mm
 - Dimensions: 75 x 75 mm
 - Series: Stainless Steel
 - Standards Met: UL



4711530 Coupling

RS PRO 304 STAINLESS STEEL CABLE TRUNKING ACCESSORY, 75 X 75MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Trunking Accessory Type: Flanged Coupler
 - Material: 304 Stainless Steel
 - Width: 75 mm
 - Height: 75 mm
 - Dimensions: 75 x 75 mm
 - Series: Stainless Steel
 - Standards Met: UL



4711552 Flanged Coupler

RS PRO 304 STAINLESS STEEL CABLE TRUNKING ACCESSORY, 75 X 75MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Trunking Accessory Type: End Cap
 - Material: 304 Stainless Steel
 - Width: 75 mm
 - Height: 75 mm
 - Dimensions: 75 x 75 mm
 - Series: Stainless Steel
 - Standards Met: UL



4711574 End Cap

RS PRO PVC CABLE TRUNKING ACCESSORY, 16 X 16MM

- ขนาดบรรจุภัณฑ์: 2 x EA
- Trunking Accessory Type: Coupling
 - Material: PVC
 - Width: 16 mm
 - Height: 16 mm
 - Dimensions: 16 x 16 mm
 - Series: Mini



9171546 Coupling

RS PRO PVC CABLE TRUNKING ACCESSORY, 38 X 25MM

- ขนาดบรรจุภัณฑ์: 2 x EA
- Trunking Accessory Type: Coupling
 - Material: PVC
 - Width: 38 mm
 - Height: 25 mm
 - Dimensions: 38 x 25 mm
 - Series: Mini



9171552 Coupling

RS PRO PVC CABLE TRUNKING ACCESSORY, 25 X 16MM

- ขนาดบรรจุภัณฑ์: 2 x EA
- Trunking Accessory Type: Coupling
 - Material: PVC
 - Width: 25 mm
 - Height: 16 mm
 - Dimensions: 25 x 16 mm
 - Series: Mini



9171555 Coupling

RS PRO PVC CABLE TRUNKING ACCESSORY, 16 X 16MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Trunking Accessory Type: Flat Tee
 - Material: PVC
 - Width: 16 mm
 - Height: 16 mm
 - Dimensions: 16 x 16 mm
 - Series: Mini



9171561 Flat Tee

RS PRO PVC CABLE TRUNKING ACCESSORY, 38 X 25MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Trunking Accessory Type: Flat Tee
 - Material: PVC
 - Width: 38 mm
 - Height: 25 mm
 - Dimensions: 38 x 25 mm
 - Series: Mini



9171568 Flat Tee

RS PRO PVC CABLE TRUNKING ACCESSORY, 25 X 16MM

- ขนาดบรรจุภัณฑ์: **2 x EA**
- Trunking Accessory Type: Flat Angle
 - Material: PVC
 - Width: 25 mm
 - Height: 16 mm
 - Dimensions: 25 x 16 mm
 - Series: Mini



9171570 Flat Angle

RS PRO PVC CABLE TRUNKING ACCESSORY, 16 X 16MM

- ขนาดบรรจุภัณฑ์: **2 x EA**
- Trunking Accessory Type: Flat Angle
 - Material: PVC
 - Width: 16 mm
 - Height: 16 mm
 - Dimensions: 16 x 16 mm
 - Series: Mini



9171577 Flat Angle

RS PRO PVC CABLE TRUNKING ACCESSORY, 25 X 16MM

- ขนาดบรรจุภัณฑ์: **2 x EA**
- Trunking Accessory Type: External Angle
 - Material: PVC
 - Width: 25 mm
 - Height: 16 mm
 - Dimensions: 25 x 16 mm
 - Series: Mini



9171580 External Angle

RS PRO PVC CABLE TRUNKING ACCESSORY, 16 X 16MM


- ขนาดบรรจุภัณฑ์: **2 x EA**
- Trunking Accessory Type: External Angle
 - Material: PVC
 - Width: 16 mm
 - Height: 16 mm
 - Dimensions: 16 x 16 mm
 - Series: Mini



9171586 External Angle

RS PRO PVC CABLE TRUNKING ACCESSORY, 16 X 16MM

- ขนาดบรรจุภัณฑ์: **2 x EA**
- Trunking Accessory Type: Internal Angle
 - Material: PVC
 - Width: 16 mm
 - Height: 16 mm
 - Dimensions: 16 x 16 mm
 - Series: Mini



9171596 Internal Angle

RS PRO PVC CABLE TRUNKING ACCESSORY, 16 X 16MM

- ขนาดบรรจุภัณฑ์: **2 x EA**
- Trunking Accessory Type: Internal Angle
 - Material: PVC
 - Width: 25 mm
 - Height: 16 mm
 - Dimensions: 25 x 16 mm
 - Series: Mini



9171606 Internal Angle

RS PRO PVC CABLE TRUNKING ACCESSORY, 25 X 16MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Trunking Accessory Type: Flat Tee
 - Material: PVC
 - Width: 25 mm
 - Height: 16 mm
 - Dimensions: 25 x 16 mm
 - Series: Mini



9171631 Flat Tee

RS PRO FLEXIBLE CONDUIT, 25MM NOMINAL DIAMETER, PLASTIC, GREY

- ขนาดบรรจุภัณฑ์: **5 x MTR**
- Nominal Diameter: 25 mm
 - Material: Plastic
 - Conduit Type: Flexible
 - Outer Diameter: 25.8 mm
 - Colour: Grey
 - Interior Diameter: 21.2 mm
 - Length: 5 m
 - IP Rating: IP55



429666 25 mm

RS PRO FLEXIBLE CONDUIT, 20MM NOMINAL DIAMETER, PLASTIC, GREY

- ขนาดบรรจุภัณฑ์: **5 x MTR**
- Nominal Diameter: 20 mm
 - Material: Plastic
 - Conduit Type: Flexible
 - Outer Diameter: 20 mm
 - Colour: Grey
 - Interior Diameter: 14.1 mm
 - Length: 5 m
 - IP Rating: IP55



429672 20 mm

RS PRO FLEXIBLE CONDUIT, 16MM NOMINAL DIAMETER, PLASTIC, GREY

- ขนาดบรรจุภัณฑ์: **5 x MTR**
- Nominal Diameter: 16 mm
 - Material: Plastic
 - Conduit Type: Flexible
 - Outer Diameter: 16 mm
 - Colour: Grey
 - Interior Diameter: 10.7 mm
 - Length: 5 m
 - IP Rating: IP55



429678 16 mm

RS PRO FLEXIBLE CONDUIT, 10MM NOMINAL DIAMETER, PLASTIC, GREY

- ขนาดบรรจุภัณฑ์: **5 x MTR**
- Nominal Diameter: 10 mm
 - Material: Plastic
 - Conduit Type: Flexible
 - Outer Diameter: 10.2 mm
 - Colour: Grey
 - Interior Diameter: 7.4 mm
 - Length: 5 m
 - IP Rating: IP55



429688 10 mm

RS PRO FLEXIBLE CONTRACTOR PACK CONDUIT, 20MM NOMINAL

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Nominal Diameter: 20 mm
 - Material: Plastic
 - Conduit Type: Flexible Contractor Pack
 - Colour: Black
 - Length: 10 m
 - IP Rating: IP66
 - Maximum Operating Temperature: +105 °C
 - Standards Met: EN 50086, UL Listed



5132376 20 mm

RS PRO FLEXIBLE CONDUIT, 25MM NOMINAL DIAMETER, PLASTIC, BLACK

- ขนาดบรรจุภัณฑ์: **10 x MTR**
- Nominal Diameter: 25 mm
 - Material: Plastic
 - Conduit Type: Flexible
 - Outer Diameter: 28.5 mm
 - Colour: Black
 - Interior Diameter: 23 mm
 - Length: 10 m
 - Coating Material: Uncoated



7559001 25 mm

RS PRO FLEXIBLE CONDUIT, 16MM NOMINAL DIAMETER, PLASTIC, BLACK

- ขนาดบรรจุภัณฑ์: **25 x MTR**
- Nominal Diameter: 16 mm
 - Material: Plastic
 - Conduit Type: Flexible
 - Outer Diameter: 15.8 mm
 - Colour: Black
 - Interior Diameter: 12.2 mm
 - Length: 25 m
 - Coating Material: Uncoated



7559004 16 mm

RS PRO FLEXIBLE CONDUIT, 20MM NOMINAL DIAMETER, PLASTIC, BLACK

- ขนาดบรรจุภัณฑ์: **25 x MTR**
- Nominal Diameter: 20 mm
 - Material: Plastic
 - Conduit Type: Flexible
 - Outer Diameter: 21.7 mm
 - Colour: Black
 - Interior Diameter: 16.8 mm
 - Length: 25 m
 - Coating Material: Uncoated



7559007 20 mm

RS PRO FLEXIBLE CONDUIT, 32MM NOMINAL DIAMETER, PLASTIC, BLACK

- ขนาดบรรจุภัณฑ์: **10 x MTR**
- Nominal Diameter: 32 mm
 - Material: Plastic
 - Conduit Type: Flexible
 - Outer Diameter: 34.4 mm
 - Colour: Black
 - Interior Diameter: 28.6 mm
 - Length: 10 m
 - Coating Material: Uncoated



7559010 32 mm

RS PRO FLEXIBLE, SPLIT CONDUIT, 16MM NOMINAL DIAMETER, PLASTIC,

- ขนาดบรรจุภัณฑ์: **25 x MTR**
- Nominal Diameter: 16 mm
 - Material: Plastic
 - Conduit Type: Flexible, Split
 - Outer Diameter: 16 mm
 - Colour: Black
 - Interior Diameter: 10.7 mm
 - Length: 25 m
 - Coating Material: Uncoated



7559013 16 mm

RS PRO FLEXIBLE, SPLIT CONDUIT, 20MM NOMINAL DIAMETER, PLASTIC,

- ขนาดบรรจุภัณฑ์: **25 x MTR**
- Nominal Diameter: 20 mm
 - Material: Plastic
 - Conduit Type: Flexible, Split
 - Outer Diameter: 19.5 mm
 - Colour: Black
 - Interior Diameter: 15 mm
 - Length: 25 m
 - Coating Material: Uncoated



7559017 20 mm

RS PRO FLEXIBLE CONDUIT, 16MM NOMINAL DIAMETER, PLASTIC, BLACK

- ขนาดบรรจุภัณฑ์: **25 x MTR**
- Nominal Diameter: 16 mm
 - Material: Plastic
 - Conduit Type: Flexible
 - Outer Diameter: 16 mm
 - Colour: Black
 - Interior Diameter: 10.7 mm
 - Length: 25 m
 - Coating Material: Uncoated



7559023 16 mm

RS PRO FLEXIBLE, SPLIT CONDUIT, 25MM NOMINAL DIAMETER, PLASTIC,

- ขนาดบรรจุภัณฑ์: **10 x MTR**
- Nominal Diameter: 25 mm
 - Material: Plastic
 - Conduit Type: Flexible, Split
 - Outer Diameter: 25.8 mm
 - Colour: Black
 - Interior Diameter: 21.2 mm
 - Length: 10 m
 - Coating Material: Uncoated



7559026 25 mm

RS PRO FLEXIBLE, SPLIT CONDUIT, 32MM NOMINAL DIAMETER, PLASTIC,

- ขนาดบรรจุภัณฑ์: **10 x MTR**
- Nominal Diameter: 32 mm
 - Material: Plastic
 - Conduit Type: Flexible, Split
 - Outer Diameter: 32 mm
 - Colour: Black
 - Interior Diameter: 24.3 mm
 - Length: 10 m
 - Coating Material: Uncoated



7559029 32 mm

RS PRO FLEXIBLE CONDUIT, 20MM NOMINAL DIAMETER, PLASTIC, BLACK

- ขนาดบรรจุภัณฑ์: **25 x MTR**
- Nominal Diameter: 20 mm
 - Material: Plastic
 - Conduit Type: Flexible
 - Outer Diameter: 19.5 mm
 - Colour: Black
 - Interior Diameter: 15 mm
 - Length: 25 m
 - Coating Material: Uncoated



7559032 20 mm

RS PRO FLEXIBLE CONDUIT, 25MM NOMINAL DIAMETER, PLASTIC, BLACK

- ขนาดบรรจุภัณฑ์: **10 x MTR**
- Nominal Diameter: 25 mm
 - Material: Plastic
 - Conduit Type: Flexible
 - Outer Diameter: 25.8 mm
 - Colour: Black
 - Interior Diameter: 21.2 mm
 - Length: 10 m
 - Coating Material: Uncoated



7559035 25 mm

RS PRO FLEXIBLE CONDUIT, 32MM NOMINAL DIAMETER, PLASTIC, BLACK

- ขนาดบรรจุภัณฑ์: **10 x MTR**
- Nominal Diameter: 32 mm
 - Material: Plastic
 - Conduit Type: Flexible
 - Outer Diameter: 32 mm
 - Colour: Black
 - Interior Diameter: 24.3 mm
 - Length: 10 m
 - Coating Material: Uncoated



7559039 32 mm

RS PRO FLEXIBLE CONDUIT, 12MM NOMINAL DIAMETER, GALVANISED

- ขนาดบรรจุภัณฑ์: **25 x MTR**
- Nominal Diameter: 12 mm
 - Material: Galvanised Steel
 - Conduit Type: Flexible
 - Outer Diameter: 11 mm
 - Colour: Black
 - Interior Diameter: 8.2 mm
 - Length: 25 m
 - Coating Material: PVC



7840094 12 mm

RS PRO TERMINAL BOX, CONDUIT FITTING, 20MM NOMINAL SIZE, STEEL,

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Nominal Size: 20 mm
 - Fitting Type: Terminal Box
 - Material: Steel
 - Colour: Black
 - Finish: Black Enamel
 - Standards Met: BS EN 50086



228722 20 mm

RS PRO ANGLE BOX, CONDUIT FITTING, 25MM NOMINAL SIZE, STEEL

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Nominal Size: 25 mm
 - Fitting Type: Angle Box
 - Material: Steel
 - Finish: Galvanised
 - Standards Met: BS EN 50086



228772 25 mm

RS PRO T PIECE, CONDUIT FITTING, 25MM NOMINAL SIZE, STEEL

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Nominal Size: 25 mm
 - Fitting Type: T Piece
 - Material: Steel
 - Finish: Galvanised
 - Standards Met: BS EN 50086



228788 25 mm

RS PRO THROUGH BOX, CONDUIT FITTING, 25MM NOMINAL SIZE, STEEL

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Nominal Size: 25 mm
 - Fitting Type: Through Box
 - Material: Steel
 - Finish: Galvanised
 - Standards Met: BS EN 50086



228794 25 mm

RS PRO TERMINAL BOX, CONDUIT FITTING, 25MM NOMINAL SIZE, STEEL

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Nominal Size: 25 mm
 - Fitting Type: Terminal Box
 - Material: Steel
 - Finish: Galvanised
 - Standards Met: BS EN 50086



228851 25 mm

RS PRO M20-M16 REDUCER CABLE CONDUIT FITTING, 20MM NOMINAL

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Fitting Type: Reducer
 - Nominal Size: 20 mm
 - Material: Brass
 - Thread Size: M20-M16
 - Finish: Nickel Plated



127467 Reducer

RS PRO T PIECE, CONDUIT FITTING, 20MM NOMINAL SIZE, STEEL

- ขนาดบรรจุภัณฑ์: 5 x EA
- Nominal Size: 20 mm
 - Fitting Type: T Piece
 - Material: Steel
 - Finish: Galvanised
 - Standards Met: BS EN 50086



228873 20 mm

RS PRO TERMINAL BOX, CONDUIT FITTING, 20MM NOMINAL SIZE, M4,

- ขนาดบรรจุภัณฑ์: 5 x EA
- Nominal Size: 20 mm
 - Fitting Type: Terminal Box
 - Thread Size: M4
 - Material: Steel
 - Finish: Galvanised



228889 20 mm

RS PRO THROUGH BOX, CONDUIT FITTING, 20MM NOMINAL SIZE, STEEL

- ขนาดบรรจุภัณฑ์: 5 x EA
- Nominal Size: 20 mm
 - Fitting Type: Through Box
 - Material: Steel
 - Finish: Galvanised
 - Standards Met: BS EN 50086



228895 20 mm

CONDUIT,FLEXIBLE,POLYETHYLENE,M 25,STRAIGHT ADAPTOR

- ขนาดบรรจุภัณฑ์: 5 x EA
- Fitting Type: Straight
 - Nominal Size: 25 mm
 - Material: Nylon 66
 - Thread Size: M25
 - Colour: Grey
 - Finish: Grey
 - IP Rating: IP55



429640 Straight

RS PRO STRAIGHT, CONDUIT FITTING, 20MM NOMINAL SIZE, NYLON 66,

- ขนาดบรรจุภัณฑ์: 5 x EA
- Nominal Size: 20 mm
 - Fitting Type: Straight
 - Material: Nylon 66
 - Colour: Grey
 - IP Rating: IP55
 - Finish: Grey
 - Standards Met: UL 94 V-0



429650 20 mm

RS PRO STRAIGHT, CONDUIT FITTING, 16MM NOMINAL SIZE, NYLON 66,

- ขนาดบรรจุภัณฑ์: 5 x EA
- Nominal Size: 16 mm
 - Fitting Type: Straight
 - Material: Nylon 66
 - Colour: Grey
 - IP Rating: IP55
 - Finish: Grey
 - Standards Met: UL 94 V-0



429656 16 mm

RS PRO STRAIGHT, CONDUIT FITTING, 10MM NOMINAL SIZE, M12, NYLON 66,

- ขนาดบรรจุภัณฑ์: 5 x EA
- Nominal Size: 10 mm
 - Fitting Type: Straight
 - Thread Size: M12
 - Material: Nylon 66
 - Colour: Grey
 - IP Rating: IP55
 - Finish: Grey



429662 10 mm

RS PRO M20 DOME COVER CONDUIT FITTING, 20MM NOMINAL SIZE

- ขนาดบรรจุภัณฑ์: 10 x EA
- Fitting Type: Dome Cover
 - Nominal Size: 20 mm
 - Material: Steel
 - Thread Size: M20
 - Finish: Galvanised
 - Standards Met: BS EN 50086



606024 Dome Cover

RS PRO COUPLER CABLE CONDUIT FITTING, 20MM NOMINAL SIZE

- ขนาดบรรจุภัณฑ์: 25 x EA
- Fitting Type: Coupler
 - Nominal Size: 20 mm
 - Material: Steel
 - Finish: Galvanised
 - Standards Met: BS EN 50086



606030 Coupler

RS PRO COUPLER, CONDUIT FITTING, 25MM NOMINAL SIZE, STEEL

- ขนาดบรรจุภัณฑ์: 25 x EA
- Nominal Size: 25 mm
 - Fitting Type: Coupler
 - Material: Steel
 - Finish: Galvanised
 - Standards Met: BS EN 50086



606046 25 mm

RS PRO M20 LOCK RING CABLE CONDUIT FITTING, 20MM NOMINAL

- ขนาดบรรจุภัณฑ์: 50 x EA
- Fitting Type: Lock Ring
 - Nominal Size: 20 mm
 - Material: Steel
 - Thread Size: M20
 - Standards Met: BS EN 50086



607982 Lock Ring

RS PRO LOCK RING, CONDUIT FITTING, 25MM NOMINAL SIZE, M25,

- ขนาดบรรจุภัณฑ์: 50 x EA
- Fitting Type: Lock Ring
 - Nominal Size: 25 mm
 - Material: Steel
 - Thread Size: M25
 - Standards Met: BS EN 50086



607998 25 mm

RS PRO DOME COVER, CONDUIT FITTING, 20MM NOMINAL SIZE, M20,

- ขนาดบรรจุภัณฑ์: 10 x EA
- Nominal Size: 20 mm
 - Fitting Type: Dome Cover
 - Thread Size: M20
 - Material: Steel
 - Colour: Black
 - Finish: Black
 - Standards Met: BS EN 50086



608165 20 mm

RS PRO COUPLER, CONDUIT FITTING, 20MM NOMINAL SIZE, STEEL, BLACK

- ขนาดบรรจุภัณฑ์: 25 x EA
- Nominal Size: 20 mm
 - Fitting Type: Coupler
 - Material: Steel
 - Colour: Black
 - Finish: Black Enamel
 - Standards Met: BS EN 50086



608171 20 mm

RS PRO COUPLER, CONDUIT FITTING, 25MM NOMINAL SIZE, STEEL, BLACK

- ขนาดบรรจุภัณฑ์: 25 x EA
- Nominal Size: 25 mm
 - Fitting Type: Coupler
 - Material: Steel
 - Colour: Black
 - Finish: Black Enamel
 - Standards Met: BS EN 50086



608187 25 mm

RS PRO REDUCER CABLE CONDUIT FITTING, 25MM NOMINAL SIZE

- ขนาดบรรจุภัณฑ์: 10 x EA
- Fitting Type: Reducer
 - Nominal Size: 25 mm
 - Material: Steel
 - Finish: Enamelled
 - Standards Met: BS EN 50086



608216 Reducer

RS PRO M20 MALE BUSH CABLE CONDUIT FITTING, 20MM NOMINAL

- ขนาดบรรจุภัณฑ์: **25 x EA**
- Fitting Type: Male Bush
 - Nominal Size: 20 mm
 - Material: Brass
 - Thread Size: M20
 - Standards Met: BS EN 50086



608222 Male Bush

RS PRO MALE BUSH, CONDUIT FITTING, 25MM NOMINAL SIZE,

- ขนาดบรรจุภัณฑ์: **25 x EA**
- Nominal Size: 25 mm
 - Fitting Type: Male Bush
 - Material: Brass
 - Standards Met: BS EN 50086



608238 25 mm

RS PRO M20 MALE BUSH CABLE CONDUIT FITTING, 20MM NOMINAL

- ขนาดบรรจุภัณฑ์: **25 x EA**
- Fitting Type: Male Bush
 - Nominal Size: 20 mm
 - Material: Brass
 - Thread Size: M20
 - Standards Met: BS EN 50086



608244 Male Bush

RS PRO FEMALE BUSH, CONDUIT FITTING, 20MM NOMINAL SIZE, BRASS

- ขนาดบรรจุภัณฑ์: **25 x EA**
- Nominal Size: 20 mm
 - Fitting Type: Female Bush
 - Material: Brass
 - Standards Met: BS EN 50086



608250 20 mm

RS PRO MALE HOOK CONDUIT FITTING, BLACK 20MM NOMINAL SIZE

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Fitting Type: Male Hook
 - Nominal Size: 20 mm
 - Material: Steel
 - Colour: Black
 - Finish: Enamelled
 - Standards Met: BS EN 50086



608266 Male Hook

RS PRO FLANGE COUPLER CABLE CONDUIT FITTING, 20MM NOMINAL

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Fitting Type: Flange Coupler
 - Nominal Size: 20 mm
 - Material: Steel
 - Finish: Galvanised
 - Standards Met: BS EN 50086



619957 Flange Coupler

RS PRO FLANGE COUPLER, CONDUIT FITTING, 25MM NOMINAL SIZE, STEEL

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Nominal Size: 25 mm
 - Fitting Type: Flange Coupler
 - Material: Steel
 - Finish: Galvanised
 - Standards Met: BS EN 50086



619963 25 mm

RS PRO REDUCER, CONDUIT FITTING, 20MM NOMINAL SIZE, STEEL

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Nominal Size: 20 mm
 - Fitting Type: Reducer
 - Material: Steel
 - Finish: Enamelled
 - Standards Met: BS EN 50086



619979 20 mm

RS PRO MALE BUSH, CONDUIT FITTING, 25MM NOMINAL SIZE,

- ขนาดบรรจุภัณฑ์: **25 x EA**
- Nominal Size: 25 mm
 - Fitting Type: Male Bush
 - Material: Brass
 - Standards Met: BS EN 50086



619985 25 mm

RS PRO JACK CHAIN CONDUIT FITTING, BLACK #8 NOMINAL SIZE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Fitting Type: Jack Chain
 - Nominal Size: 8 mm
 - Material: Steel
 - Colour: Black
 - Finish: Black
 - Standards Met: BS EN 50086



621089 Jack Chain

RS PRO JACK CHAIN, CONDUIT FITTING, 8MM NOMINAL SIZE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Nominal Size: 8 mm
 - Fitting Type: Jack Chain
 - Material: Galvanised Steel
 - Finish: Galvanised
 - Standards Met: BS EN 50086



621095 8 mm

RS PRO THREAD CONVERTER, CONDUIT FITTING, 9MM NOMINAL

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Nominal Size: 9 mm
 - Fitting Type: Thread Converter
 - Thread Size: PG9 → M16
 - Material: Brass
 - Finish: Nickel Plated



623899 9 mm

RS PRO THREAD CONVERTER, CONDUIT FITTING, 9MM NOMINAL

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Nominal Size: 9 mm
 - Fitting Type: Thread Converter
 - Thread Size: PG9 → M20
 - Material: Brass
 - Finish: Nickel Plated



623906 9 mm

RS PRO THREAD CONVERTER, CONDUIT FITTING, 16MM NOMINAL

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Nominal Size: 16 mm
 - Fitting Type: Thread Converter
 - Thread Size: PG11 → M16
 - Material: Brass
 - Finish: Nickel Plated



623912 16 mm

RS PRO THREAD CONVERTER, CONDUIT FITTING, 13MM NOMINAL

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Nominal Size: 13 mm
 - Fitting Type: Thread Converter
 - Thread Size: PG13.5 → M20
 - Material: Brass
 - Finish: Nickel Plated



623934 13 mm

RS PRO THREAD CONVERTER, CONDUIT FITTING, 16MM NOMINAL

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Nominal Size: 16 mm
 - Fitting Type: Thread Converter
 - Thread Size: PG16 → M20
 - Material: Brass
 - Colour: Black
 - IP Rating: IP66
 - Finish: Nickel Plated



623940 16 mm

RS PRO THREAD CONVERTER, CONDUIT FITTING, 21MM NOMINAL

- ขนาดบรรจุภัณฑ์: 5 x EA
- Nominal Size: 21 mm
 - Fitting Type: Thread Converter
 - Thread Size: PG21 → M25
 - Material: Brass
 - Finish: Nickel Plated



623956 21 mm

RS PRO THROUGH BOX, CONDUIT FITTING, 20MM NOMINAL SIZE, 316

- ขนาดบรรจุภัณฑ์: 1 x EA
- Nominal Size: 20 mm
 - Fitting Type: Through Box
 - Material: 316 Stainless Steel
 - Colour: Silver
 - IP Rating: IP67
 - Finish: Satin
 - Standards Met: BS EN 60529:1992 - IEC 529:1989, UL



4711243 20 mm

RS PRO ANGLE BOX, CONDUIT FITTING, 25MM NOMINAL SIZE, 316

- ขนาดบรรจุภัณฑ์: 1 x EA
- Nominal Size: 25 mm
 - Fitting Type: Angle Box
 - Material: 316 Stainless Steel
 - Colour: Silver
 - IP Rating: IP67
 - Finish: Satin
 - Standards Met: BS EN 60529:1992 - IEC 529:1989, UL



4711271 25 mm

RS PRO 3 WAY TEE BOX, CONDUIT FITTING, 20MM NOMINAL SIZE, 316

- ขนาดบรรจุภัณฑ์: 1 x EA
- Nominal Size: 20 mm
 - Fitting Type: 3 Way Tee Box
 - Material: 316 Stainless Steel
 - Colour: Silver
 - IP Rating: IP67
 - Finish: Satin
 - Standards Met: BS EN 60529:1992 - IEC 529:1989, UL



4711287 20 mm

RS PRO 3 WAY TEE BOX, CONDUIT FITTING, 25MM NOMINAL SIZE, 316

- ขนาดบรรจุภัณฑ์: 1 x EA
- Nominal Size: 25 mm
 - Fitting Type: 3 Way Tee Box
 - Material: 316 Stainless Steel
 - Colour: Silver
 - IP Rating: IP67
 - Finish: Satin
 - Standards Met: BS EN 60529:1992 - IEC 529:1989, UL



4711293 25 mm

RS PRO FLANGE COUPLER, CONDUIT FITTING, 20MM NOMINAL SIZE, 316

- ขนาดบรรจุภัณฑ์: 4 x EA
- Nominal Size: 20 mm
 - Fitting Type: Flange Coupler
 - Material: 316 Stainless Steel
 - Colour: Silver
 - Finish: Satin
 - Standards Met: BS EN 60529:1992 - IEC 529:1989, UL



4711322 20 mm

RS PRO COUPLER, CONDUIT FITTING, 20MM NOMINAL SIZE, 316 STAINLESS

- ขนาดบรรจุภัณฑ์: 4 x EA
- Nominal Size: 20 mm
 - Fitting Type: Coupler
 - Material: 316 Stainless Steel
 - Colour: Silver
 - Finish: Satin
 - Standards Met: BS EN 60529:1992 - IEC 529:1989, UL



4711344 20 mm

RS PRO COUPLER, CONDUIT FITTING, 25MM NOMINAL SIZE, 316 STAINLESS

- ขนาดบรรจุภัณฑ์: 4 x EA
- Nominal Size: 25 mm
 - Fitting Type: Coupler
 - Material: 316 Stainless Steel
 - Colour: Silver
 - Finish: Satin
 - Standards Met: BS EN 60529:1992 - IEC 529:1989, UL



4711350 25 mm

RS PRO MALE BUSH, CONDUIT FITTING, 20MM NOMINAL SIZE, 316

- ขนาดบรรจุภัณฑ์: 4 x EA
- Nominal Size: 20 mm
 - Fitting Type: Male Bush
 - Material: 316 Stainless Steel
 - Colour: Silver
 - IP Rating: IP67
 - Finish: Satin
 - Standards Met: BS EN 60529:1992 - IEC 529:1989, UL



4711366 20 mm

RS PRO SHORT NIPPLE, CONDUIT FITTING, 20MM NOMINAL SIZE, 316

- ขนาดบรรจุภัณฑ์: 4 x EA
- Nominal Size: 20 mm
 - Fitting Type: Short Nipple
 - Material: 316 Stainless Steel
 - Colour: Silver
 - Finish: Satin
 - Standards Met: BS EN 60529:1992 - IEC 529:1989, UL



4711417 20 mm

RS PRO SHORT NIPPLE, CONDUIT FITTING, 25MM NOMINAL SIZE, 316

- ขนาดบรรจุภัณฑ์: 4 x EA
- Nominal Size: 25 mm
 - Fitting Type: Short Nipple
 - Material: 316 Stainless Steel
 - Colour: Silver
 - Finish: Satin
 - Standards Met: BS EN 60529:1992 - IEC 529:1989, UL



4711423 25 mm

RS PRO ADAPTER, CONDUIT FITTING, 20MM NOMINAL SIZE, PG21, NYLON

- ขนาดบรรจุภัณฑ์: 10 x EA
- Nominal Size: 20 mm
 - Fitting Type: Adapter
 - Thread Size: PG21
 - Material: Nylon 66



7559051 20 mm

RS PRO ADAPTER, CONDUIT FITTING, 16MM NOMINAL SIZE, PG9, NYLON 66

- ขนาดบรรจุภัณฑ์: 10 x EA
- Nominal Size: 16 mm
 - Fitting Type: Adapter
 - Thread Size: PG9
 - Material: Nylon 66



7559057 16 mm

RS PRO ADAPTER, CONDUIT FITTING, 32MM NOMINAL SIZE, PG29, NYLON

- ขนาดบรรจุภัณฑ์: 10 x EA
- Nominal Size: 32 mm
 - Fitting Type: Adapter
 - Thread Size: PG29
 - Material: Nylon 66



7559063 32 mm

RS PRO ADAPTER, CONDUIT FITTING, 16MM NOMINAL SIZE, NYLON 66

- ขนาดบรรจุภัณฑ์: 10 x EA
- Nominal Size: 16 mm
 - Fitting Type: Adapter
 - Material: Nylon 66



7559067 16 mm

RS PRO ADAPTER, CONDUIT FITTING, 32MM NOMINAL SIZE, NYLON 66

- ขนาดบรรจุภัณฑ์: 10 x EA
- Nominal Size: 32 mm
 - Fitting Type: Adapter
 - Material: Nylon 66



7559073 32 mm

RS PRO ADAPTER, CONDUIT FITTING, 20MM NOMINAL SIZE, NYLON 66

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Nominal Size: 20 mm
 - Fitting Type: Adapter
 - Material: Nylon 66



7559076 20 mm

RS PRO ADAPTER, CONDUIT FITTING, 25MM NOMINAL SIZE, NYLON 66

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Nominal Size: 25 mm
 - Fitting Type: Adapter
 - Material: Nylon 66



7559079 25 mm

RS PRO INSPECTION BEND, CONDUIT FITTING, 20MM NOMINAL SIZE, STEEL

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Nominal Size: 20 mm
 - Fitting Type: Inspection Bend
 - Material: Steel
 - Colour: Silver
 - Finish: Galvanised
 - Standards Met: BS EN 50086



7639181 20 mm

RS PRO INSPECTION BEND, CONDUIT FITTING, 25MM NOMINAL SIZE, STEEL

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Nominal Size: 25 mm
 - Fitting Type: Inspection Bend
 - Material: Steel
 - Colour: Silver
 - Finish: Galvanised
 - Standards Met: BS EN 50086



7639188 25 mm

RS PRO Y BOX, CONDUIT FITTING, 25MM NOMINAL SIZE, STEEL

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Nominal Size: 25 mm
 - Fitting Type: Y Box
 - Material: Steel
 - Finish: Galvanised
 - Standards Met: BS EN 50086



7639191 25 mm

RS PRO Y BOX, CONDUIT FITTING, 20MM NOMINAL SIZE, M4, STEEL

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Nominal Size: 20 mm
 - Fitting Type: Y Box
 - Thread Size: M4
 - Material: Steel
 - Colour: Silver
 - Finish: Galvanised
 - Standards Met: BS EN 50086



7639194 20 mm

RS PRO INSPECTION ELBOW, CONDUIT FITTING, 20MM NOMINAL

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Nominal Size: 20 mm
 - Fitting Type: Inspection Elbow
 - Material: Steel
 - Colour: Silver
 - Finish: Galvanised
 - Standards Met: BS EN 50086



7639210 20 mm

RS PRO INSPECTION ELBOW, CONDUIT FITTING, 25MM NOMINAL

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Nominal Size: 25 mm
 - Fitting Type: Inspection Elbow
 - Material: Steel
 - Colour: Silver
 - Finish: Galvanised
 - Standards Met: BS EN 50086



7639214 25 mm

RS PRO RECESSED COVER, CONDUIT FITTING, 20MM NOMINAL SIZE, STEEL

- ขนาดบรรจุภัณฑ์: **25 x EA**
- Nominal Size: 20 mm, 25 mm
 - Fitting Type: Recessed Cover
 - Material: Steel
 - Finish: Galvanised
 - Standards Met: BS EN 50086



7639217 20 mm, 25 mm

RS PRO GASKET, CONDUIT FITTING, 20MM NOMINAL SIZE, RUBBER

- ขนาดบรรจุภัณฑ์: **25 x EA**
- Nominal Size: 20 mm, 25 mm
 - Fitting Type: Gasket
 - Material: Rubber
 - Colour: Black
 - Standards Met: BS EN 50086



7639220 20 mm, 25 mm

RS PRO INSPECTION TEE, CONDUIT FITTING, 20MM NOMINAL SIZE, STEEL

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Nominal Size: 20 mm
 - Fitting Type: Inspection Tee
 - Material: Steel
 - Colour: Silver
 - Finish: Galvanised
 - Standards Met: BS EN 50086



7639223 20 mm

RS PRO INSPECTION TEE, CONDUIT FITTING, 25MM NOMINAL SIZE, STEEL

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Nominal Size: 25 mm
 - Fitting Type: Inspection Tee
 - Material: Steel
 - Colour: Silver
 - Finish: Galvanised
 - Standards Met: BS EN 50086



7639226 25 mm

RS PRO RECESSED COVER, CONDUIT FITTING, 20MM NOMINAL SIZE, STEEL

- ขนาดบรรจุภัณฑ์: **25 x EA**
- Nominal Size: 20 mm, 25 mm
 - Fitting Type: Recessed Cover
 - Material: Steel
 - Colour: Black
 - Finish: Black Enamel
 - Standards Met: BS EN 50086



7639232 20 mm, 25 mm

RS PRO NIPPLE, CONDUIT FITTING, 20MM NOMINAL SIZE, STEEL, SILVER

- ขนาดบรรจุภัณฑ์: **25 x EA**
- Nominal Size: 20 mm
 - Fitting Type: Nipple
 - Material: Steel
 - Colour: Silver
 - Finish: Zinc
 - Standards Met: BS EN 50086



7639236 20 mm

RS PRO NIPPLE, CONDUIT FITTING, 25MM NOMINAL SIZE, STEEL, SILVER

- ขนาดบรรจุภัณฑ์: **25 x EA**
- Nominal Size: 25 mm
 - Fitting Type: Nipple
 - Material: Steel
 - Colour: Silver
 - Finish: Zinc
 - Standards Met: BS EN 50086



7639245 25 mm

RS PRO ADAPTER, CONDUIT FITTING, 6.35MM NOMINAL SIZE, M16, ZINC

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Nominal Size: 6.35 mm
 - Fitting Type: Adapter
 - Thread Size: M16
 - Material: Zinc Alloy



7840114 6.35 mm

RS PRO, CONDUIT FITTING, PLASTIC, BLACK

- ขนาดบรรจุภัณฑ์: 5 x EA
 • Material: Plastic
 • Colour: Black



9172000 Plastic

RS PRO, CONDUIT FITTING, PLASTIC, WHITE

- ขนาดบรรจุภัณฑ์: 5 x EA
 • Material: Plastic
 • Colour: White



9172006 Plastic

RS PRO COUPLER, CONDUIT FITTING, (DIA) 20MM NOMINAL SIZE, PVC,

- ขนาดบรรจุภัณฑ์: 4 x EA
 • Nominal Size: (Dia) 20 mm
 • Fitting Type: Coupler
 • Material: PVC
 • Colour: White



9172044 (Dia) 20 mm

RS PRO T PIECE, CONDUIT FITTING, (DIA) 20MM NOMINAL SIZE, 20MM,

- ขนาดบรรจุภัณฑ์: 1 x EA
 • Nominal Size: (Dia) 20 mm
 • Fitting Type: T Piece
 • Thread Size: 20 mm
 • Material: PVC
 • Colour: White



9172066 (Dia) 20 mm

RS PRO THROUGH BOX, CONDUIT FITTING, (DIA) 20MM NOMINAL SIZE,

- ขนาดบรรจุภัณฑ์: 1 x EA
 • Nominal Size: (Dia) 20 mm
 • Fitting Type: Through Box
 • Material: PVC
 • Colour: White



9172069 (Dia) 20 mm

RS PRO INSPECTION ELBOW, CONDUIT FITTING, 20MM NOMINAL

- ขนาดบรรจุภัณฑ์: 1 x EA
 • Nominal Size: 20 mm
 • Fitting Type: Inspection Elbow
 • Material: PVC
 • Colour: Black



9172072 20 mm

RS PRO INSPECTION ELBOW, CONDUIT FITTING, 20MM NOMINAL

- ขนาดบรรจุภัณฑ์: 1 x EA
 • Nominal Size: 20 mm
 • Fitting Type: Inspection Elbow
 • Material: PVC
 • Colour: White



9172078 20 mm

RS PRO COUPLER, CONDUIT FITTING, (DIA) 20MM NOMINAL SIZE, PVC,

- ขนาดบรรจุภัณฑ์: 4 x EA
 • Nominal Size: (Dia) 20 mm
 • Fitting Type: Coupler
 • Material: PVC
 • Colour: Black



9172088 (Dia) 20 mm

RS PRO THROUGH BOX, CONDUIT FITTING, (DIA) 20MM NOMINAL SIZE,

- ขนาดบรรจุภัณฑ์: 1 x EA
 • Nominal Size: (Dia) 20 mm
 • Fitting Type: Through Box
 • Material: PVC
 • Colour: Black



9172094 (Dia) 20 mm

RS PRO ANGLE BOX, CONDUIT FITTING, (DIA) 20MM NOMINAL SIZE,

- ขนาดบรรจุภัณฑ์: 1 x EA
 • Nominal Size: (Dia) 20 mm
 • Fitting Type: Angle Box
 • Material: PVC
 • Colour: Black



9172104 (Dia) 20 mm

RS PRO 3 WAY TEE BOX, CONDUIT FITTING, (DIA) 20MM NOMINAL SIZE,

- ขนาดบรรจุภัณฑ์: 1 x EA
 • Nominal Size: (Dia) 20 mm
 • Fitting Type: 3 Way Tee Box
 • Material: PVC
 • Colour: Black



9172107 (Dia) 20 mm

RS PRO INSPECTION BEND, CONDUIT FITTING, (DIA) 25MM NOMINAL SIZE,

- ขนาดบรรจุภัณฑ์: 1 x EA
 • Nominal Size: (Dia) 25 mm
 • Fitting Type: Inspection Bend
 • Material: PVC
 • Colour: Black



9172126 (Dia) 25 mm

RS PRO CLEAR DIN RAIL TERMINAL BLOCK, 16MM², 450 V

- ขนาดบรรจุภัณฑ์: 3 x EA
 • Colour: Clear
 • American Wire Gauge: 10 → 5 AWG
 • Termination Method: Screw
 • Cable CSA: 16 mm², 6 mm²
 • Voltage Rating: 450 V
 • Current Rating: 100 A
 • Maximum Operating Temperature: +85 °C



3882833 Clear

RS PRO CLEAR NON-FUSED DIN RAIL TERMINAL, 16MM², 450 V

- ขนาดบรรจุภัณฑ์: 3 x EA
 • Colour: Clear
 • American Wire Gauge: 10 → 5 AWG
 • Termination Method: Screw
 • Cable CSA: 16 mm², 6 mm²
 • Voltage Rating: 450 V
 • Current Rating: 100 A
 • Maximum Operating Temperature: +85 °C



3882855 Clear

RS PRO CLEAR TERMINAL BLOCK, 35MM², 450 V, 450 V

- ขนาดบรรจุภัณฑ์: 3 x EA
 • Colour: Clear
 • American Wire Gauge: 10 → 2 AWG, 10 → 2 AWG
 • Termination Method: Screw
 • Cable CSA: 35 mm², 35 mm²
 • Voltage Rating: 450 V
 • Current Rating: 170 A, 170 A
 • Maximum Operating Temperature: +85 °C



3882861 Clear

RS PRO COMMONING BLOCK, 11 WAY, 750 V

- ขนาดบรรจุภัณฑ์: 1 x EA
 • Number of Ways: 11
 • Termination Method: Screw
 • Wire Size: 6 mm²
 • Voltage Rating: 750 V
 • Maximum Operating Temperature: +85 °C



8680752 11

RS PRO COMMONING BLOCK, 4 WAY, 450 V

- ขนาดบรรจุภัณฑ์: 5 x EA
- Number of Ways: 4
 - Termination Method: Screw
 - Wire Size: 16 mm²
 - Voltage Rating: 450 V
 - Maximum Operating Temperature: +85 °C



8680755 4

RS PRO COMMONING BLOCK, 5 WAY, 450 V

- ขนาดบรรจุภัณฑ์: 5 x EA
- Number of Ways: 5
 - Termination Method: Screw
 - Wire Size: 6 mm²
 - Voltage Rating: 450 V
 - Maximum Operating Temperature: +85 °C



8680774 5

RS PRO COMMONING BLOCK, 3 WAY, 450 V

- ขนาดบรรจุภัณฑ์: 5 x EA
- Number of Ways: 3
 - Termination Method: Screw
 - Wire Size: 6 mm²
 - Voltage Rating: 450 V
 - Maximum Operating Temperature: +85 °C



8680786 3

DERIVATIO TERMINAL BLOCK 6-16 6P

- ขนาดบรรจุภัณฑ์: 1 x EA
- Number of Ways: 6
 - Termination Method: Screw
 - Wire Size: 6 mm²
 - Voltage Rating: 750 V
 - Maximum Operating Temperature: +85 °C



8680792 6

RS PRO COMMONING BLOCK, 6 WAY, 750 V

- ขนาดบรรจุภัณฑ์: 1 x EA
- Number of Ways: 6
 - Termination Method: Screw
 - Wire Size: 16 mm²
 - Voltage Rating: 750 V
 - Maximum Operating Temperature: +85 °C



8680799 6

RS PRO COMMONING BLOCK, 3 WAY, 750 V

- ขนาดบรรจุภัณฑ์: 1 x EA
- Number of Ways: 3
 - Termination Method: Screw
 - Wire Size: 35 mm²
 - Voltage Rating: 750 V
 - Maximum Operating Temperature: +85 °C



8680806 3

RS PRO 4-WAY DOUBLE SCREW EARTH TERMINAL BLOCK, 0 TO

- ขนาดบรรจุภัณฑ์: 5 x EA
- Earth Block Type: Double Screw
 - Wire Size: 0 → 16 mm²
 - Cable CSA: 0 to 16 mm²
 - Colour: Grey
 - Number of Ways: 4
 - Termination Method: Screw Down
 - Housing Material: Brass
 - Length: 51.4 mm



425544 Double Screw

RS PRO 8-WAY DOUBLE SCREW EARTH TERMINAL BLOCK, 0 → 16 AWG

- ขนาดบรรจุภัณฑ์: 5 x EA
- Earth Block Type: Double Screw
 - Wire Size: 0 → 16 mm²
 - Colour: Grey
 - Number of Ways: 8
 - Termination Method: Screw Down
 - Housing Material: Brass
 - Length: 86 mm
 - Width: 18.5 mm



425550 Double Screw

RS PRO 3-WAY DOUBLE SCREW EARTH TERMINAL BLOCK, 0 TO

- ขนาดบรรจุภัณฑ์: 5 x EA
- Earth Block Type: Double Screw
 - Wire Size: 0 → 16 mm²
 - Cable CSA: 0 to 16 mm²
 - Colour: Grey
 - Number of Ways: 3
 - Termination Method: Screw Down
 - Housing Material: Brass
 - Length: 42.6 mm



2830730 Double Screw

RS PRO 5-WAY DOUBLE SCREW EARTH TERMINAL BLOCK, 0 TO

- ขนาดบรรจุภัณฑ์: 5 x EA
- Earth Block Type: Double Screw
 - Wire Size: 0 → 16 mm²
 - Cable CSA: 0 to 16 mm²
 - Colour: Grey
 - Number of Ways: 5
 - Termination Method: Screw Down
 - Housing Material: Brass
 - Length: 60 mm



2830746 Double Screw

RS PRO 6-WAY DOUBLE SCREW EARTH TERMINAL BLOCK, 0 TO

- ขนาดบรรจุภัณฑ์: 5 x EA
- Earth Block Type: Double Screw
 - Wire Size: 0 → 16 mm²
 - Cable CSA: 0 to 16 mm²
 - Colour: Grey
 - Number of Ways: 6
 - Termination Method: Screw Down
 - Housing Material: Brass
 - Length: 69 mm



2830768 Double Screw

RS PRO 7-WAY DOUBLE SCREW EARTH TERMINAL BLOCK, 0 TO

- ขนาดบรรจุภัณฑ์: 5 x EA
- Earth Block Type: Double Screw
 - Wire Size: 0 → 16 mm²
 - Cable CSA: 0 to 16 mm²
 - Colour: Grey
 - Number of Ways: 7
 - Termination Method: Screw Down
 - Housing Material: Brass
 - Length: 77.2 mm



2830774 Double Screw

RS PRO 3-WAY CE (BS EN 60998) EARTH BLOCK, 0 → 16 AWG WIRE,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Earth Block Type: CE (BS EN 60998)
 - Wire Size: 0 → 16 AWG
 - Number of Ways: 3
 - Termination Method: Screw Down
 - Housing Material: Brass
 - Length: 42.3 mm
 - Width: 18 mm
 - Height: 12 mm



8670991 CE (BS EN

RS PRO 5-WAY CE (BS EN 60998) EARTH BLOCK, 0 → 16 AWG WIRE,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Earth Block Type: CE (BS EN 60998)
 - Wire Size: 0 → 16 AWG
 - Number of Ways: 5
 - Termination Method: Screw Down
 - Housing Material: Brass
 - Length: 59.7 mm
 - Width: 18 mm
 - Height: 12 mm



8671004 CE (BS EN

RS PRO 8-WAY CE (BS EN 60998) EARTH BLOCK, 0 → 16 AWG WIRE,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Earth Block Type: CE (BS EN 60998)
 - Wire Size: 0 → 16 AWG
 - Number of Ways: 8
 - Termination Method: Screw Down
 - Housing Material: Brass
 - Length: 86 mm
 - Width: 18 mm
 - Height: 12 mm



8671007 CE (BS EN

CONNECTOR, TERMINAL BLOCK, TEETUBE, 3 POLE, BLACK

- ขนาดบรรจุภัณฑ์: 1 x EA
- Material: Nylon
 - Length: 115 mm
 - Height: 26.5 mm
 - IP Rating: IP68
 - Number of Terminals: 3
 - Colour: Black
 - Number of Ways: 3
 - Cable Entry: 2



4691795 Nylon

CONNECTOR, TERMINAL BLOCK, TEE TUBE, 5 POLE, BLACK

- ขนาดบรรจุภัณฑ์: 1 x EA
- Material: Nylon
 - Length: 130 mm
 - Height: 32 mm
 - IP Rating: IP68
 - Number of Terminals: 5
 - Colour: Black
 - Number of Ways: 5
 - Cable Entry: 2



4691818 Nylon

RS PRO BLACK JUNCTION BOX, 4 TERMINALS

- ขนาดบรรจุภัณฑ์: 5 x EA
- Number of Terminals: 4
 - Colour: Black
 - Number of Ways: 4
 - Current Rating: 20 A
 - Diameter: 76 mm



7767640 4

RS PRO BLACK JUNCTION BOX, 4 TERMINALS

- ขนาดบรรจุภัณฑ์: 5 x EA
- Number of Terminals: 4
 - Colour: Black
 - Number of Ways: 4
 - Current Rating: 5 A
 - Diameter: 62 mm



7767646 4

RS PRO BLACK JUNCTION BOX, 3 TERMINALS

- ขนาดบรรจุภัณฑ์: 5 x EA
- Number of Terminals: 3
 - Colour: Black
 - Number of Ways: 4
 - Current Rating: 30 A
 - Diameter: 76 mm



7767659 3

RS PRO GREY 1 BLANKING PLATE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Colour: Grey
 - Material: Metal
 - Number of Gangs: 1
 - Series: RS Metalclad



3611940 Grey

RS PRO GREY 2 BLANKING PLATE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Colour: Grey
 - Material: Steel
 - Number of Gangs: 2
 - Series: RS Metalclad



3611956 Grey

RS PRO 1 WAY BRUSH PLATE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Brush Plate
 - Number of Outlets: 1
 - Number of Ways: 1
 - Length: 86 mm
 - Width: 86 mm
 - Depth: 10 mm



8781091 Brush Plate

RS PRO 2 WAY BRUSH PLATE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Brush Plate
 - Number of Outlets: 2
 - Number of Ways: 2
 - Length: 86 mm
 - Width: 121 mm
 - Depth: 10 mm



8781101 Brush Plate

CONNECTOR, TERMINAL, SOLDER TAG, M6/0BA

- ขนาดบรรจุภัณฑ์: 250 x EA
- Inner Diameter: 6.4 mm
 - Contact Material: Brass
 - Contact Plating: Tin



1867826 6.4 mm

CONNECTOR, TERMINAL, SOLDER TAG, M5/2BA

- ขนาดบรรจุภัณฑ์: 250 x EA
- Inner Diameter: 5.3 mm
 - Contact Material: Brass
 - Contact Plating: Tin



1867832 5.3 mm

CONNECTOR, TERMINAL, SOLDER TAG, M4/3BA

- ขนาดบรรจุภัณฑ์: 250 x EA
- Inner Diameter: 4.3 mm
 - Contact Material: Brass
 - Contact Plating: Tin



1867848 4.3 mm

RS PRO SOLDER TAG, BRASS CONTACTS, TIN

- ขนาดบรรจุภัณฑ์: 250 x EA
- Inner Diameter: 3.5 mm
 - Contact Material: Brass
 - Contact Plating: Tin



1867854 3.5 mm

CONNECTOR, TERMINAL, SOLDER TAG, M3/6BA

- ขนาดบรรจุภัณฑ์: 250 x EA
- Inner Diameter: 3.2 mm
 - Contact Material: Brass
 - Contact Plating: Tin



1867860 3.2 mm

CONNECTOR, TERMINAL, SOLDER TAG, M2/8BA

- ขนาดบรรจุภัณฑ์: 250 x EA
- Inner Diameter: 2.2 mm
 - Contact Material: Brass
 - Contact Plating: Tin



1867876 2.2 mm

RS PRO 3-WAY NON-FUSED TERMINAL BLOCK, 40A, SCREW DOWN

- ขนาดบรรจุภัณฑ์: 5 x EA
- Number of Ways: 3
 - Current Rating: 40 A
 - Wire Size: 22 → 8 AWG
 - Termination Method: Screw Down
 - Mounting Type: Screw Down
 - Fused: No
 - Material: Nylon
 - Pitch: 17.7 mm



465637 3

RS PRO 3-WAY FUSED TERMINAL BLOCK, 6.3A, SCREW TERMINALS

- ขนาดบรรจุภัณฑ์: 10 x EA
- Number of Ways: 3
 - Current Rating: 6.3 A
 - Termination Method: Screw
 - Mounting Type: Panel Mount
 - Fused: Yes
 - Material: Nylon 66
 - Pitch: 9 mm
 - Voltage Rating: 450 V



1225193 3

CONNECTOR, TERMINAL BLOCK, NYLON, 6, 6, 41A, 12 WAY

- ขนาดบรรจุภัณฑ์: 5 x EA
- Number of Ways: 12
 - Current Rating: 50 A
 - Wire Size: 10 mm²
 - Termination Method: Screw Down
 - Fused: No
 - Material: Nylon
 - Voltage Rating: 400 V
 - Pitch: 15 mm



4649700 12

CONNECTOR, TERMINAL BLOCK, NYLON, 6, 6, 32A, 12 WAY

- ขนาดบรรจุภัณฑ์: 5 x EA
- Number of Ways: 12
 - Current Rating: 41 A
 - Wire Size: 4 mm²
 - Termination Method: Screw Down
 - Mounting Type: Through Hole
 - Fused: No
 - Material: Nylon
 - Pitch: 12 mm



4649722 12

CONNECTOR, TERMINAL BLOCK, NYLON, 6, 6, 24A, 12 WAY

- ขนาดบรรจุภัณฑ์: 5 x EA
- Number of Ways: 12
 - Current Rating: 24 A
 - Wire Size: 2.5 mm²
 - Termination Method: Screw Down
 - Mounting Type: Through Hole
 - Fused: No
 - Material: Nylon
 - Voltage Rating: 400 V



4649738 12

CONNECTOR, TERMINAL BLOCK, NYLON, 6, 6, 17.5A, 12 WAY

- ขนาดบรรจุภัณฑ์: 5 x EA
- Number of Ways: 12
 - Current Rating: 24 A
 - Wire Size: 2.5 mm²
 - Termination Method: Screw Down
 - Mounting Type: Free Hanging
 - Fused: No
 - Material: Nylon
 - Pitch: 8 mm



4649744 12

RS PRO 12-WAY NON-FUSED TERMINAL BLOCK, 57A, SCREW

- ขนาดบรรจุภัณฑ์: 5 x EA
- Number of Ways: 12
 - Current Rating: 57 A
 - Wire Size: 6 mm²
 - Termination Method: Screw Down
 - Mounting Type: Through Hole
 - Fused: No
 - Material: Glass Fibre Reinforced Nylon
 - Voltage Rating: 400 V



4649750 12

CONNECTOR, TERMINAL BLOCK, HIGH TEMP, 32A, 12 WAY

- ขนาดบรรจุภัณฑ์: 5 x EA
- Number of Ways: 12
 - Current Rating: 41 A
 - Wire Size: 4 mm²
 - Termination Method: Screw Down
 - Mounting Type: Through Hole
 - Fused: No
 - Material: Nylon
 - Pitch: 12 mm



4649766 12

CONNECTOR, TERMINAL BLOCK, HIGH TEMP, 17.5A, 12 WAY

- ขนาดบรรจุภัณฑ์: 5 x EA
- Number of Ways: 12
 - Current Rating: 24 A
 - Wire Size: 2.5 mm²
 - Termination Method: Screw Down
 - Mounting Type: Through Hole
 - Fused: No
 - Material: Nylon
 - Pitch: 8 mm



4649772 12

CONNECTOR, TERMINAL BLOCK, HIGH TEMP, 24A, 12 WAY

- ขนาดบรรจุภัณฑ์: 5 x EA
- Number of Ways: 12
 - Current Rating: 24 A
 - Wire Size: 2.5 mm²
 - Termination Method: Screw Down
 - Mounting Type: Through Hole
 - Fused: No
 - Material: Nylon
 - Voltage Rating: 400 V



4649788 12

CONNECTOR, TERMINAL BLOCK, 12 WAY, 1.5MM2, NYLON, 250-

- ขนาดบรรจุภัณฑ์: 5 x EA
- Number of Ways: 12
 - Current Rating: 24 A
 - Wire Size: 2.5 mm²
 - Termination Method: Screw Down
 - Mounting Type: Through Hole
 - Fused: No
 - Material: Nylon
 - Pitch: 8 mm



4928687 12

CONNECTOR, TERMINAL BLOCK, 12 WAY, 2.5MM2, NYLON, 400V, NATURAL

- ขนาดบรรจุภัณฑ์: 5 x EA
- Number of Ways: 12
 - Current Rating: 32 A
 - Wire Size: 4 mm²
 - Termination Method: Screw Down
 - Mounting Type: Through Hole
 - Fused: No
 - Material: Nylon
 - Voltage Rating: 400 V



4928700 12

RS PRO 12-WAY NON-FUSED TERMINAL BLOCK, 41A, SCREW

- ขนาดบรรจุภัณฑ์: 5 x EA
- Number of Ways: 12
 - Current Rating: 41 A
 - Wire Size: 6 mm²
 - Termination Method: Screw Down
 - Mounting Type: Through Hole
 - Fused: No
 - Material: Nylon
 - Voltage Rating: 400 V



4928716 12

CONNECTOR, TERMINAL BLOCK, 12 WAY, 6MM2, NYLON, 400V, NATURAL

- ขนาดบรรจุภัณฑ์: 5 x EA
- Number of Ways: 12
 - Current Rating: 57 A
 - Wire Size: 10 mm²
 - Termination Method: Screw Down
 - Mounting Type: Through Hole
 - Fused: No
 - Material: Nylon
 - Voltage Rating: 400 V



4928722 12

RS PRO 2-WAY NON-FUSED TERMINAL BLOCK, 16A, SCREW DOWN

- ขนาดบรรจุภัณฑ์: 5 x EA
- Number of Ways: 2
 - Current Rating: 16 A
 - Wire Size: 2.5 mm²
 - Termination Method: Screw Down
 - Mounting Type: Cable Mount
 - Fused: No
 - Material: Nylon
 - Voltage Rating: 400 V



4956187 2

CONNECTOR, TERMINAL BLOCK, 2 WAY, 2.5MM2, NYLON, 400V, BROWN

- ขนาดบรรจุภัณฑ์: 5 x EA
- Number of Ways: 2
 - Current Rating: 16 A
 - Wire Size: 2.5 mm²
 - Termination Method: Screw Down
 - Mounting Type: Cable Mount
 - Fused: No
 - Material: Nylon
 - Voltage Rating: 400 V



4956193 2

RS PRO 2-WAY NON-FUSED TERMINAL BLOCK, 16A, SCREW DOWN

- ขนาดบรรจุภัณฑ์: 5 x EA
- Number of Ways: 2
 - Current Rating: 16 A
 - Wire Size: 2.5 mm²
 - Termination Method: Screw Down
 - Mounting Type: Cable Mount
 - Fused: No
 - Material: Nylon
 - Voltage Rating: 400 V



4956200 2

RS PRO 2-WAY NON-FUSED TERMINAL BLOCK, 16A, SCREW DOWN

- ขนาดบรรจุภัณฑ์: 5 x EA
- Number of Ways: 2
 - Current Rating: 16 A
 - Wire Size: 2.5 mm²
 - Termination Method: Screw Down
 - Mounting Type: Cable Mount
 - Fused: No
 - Material: Nylon
 - Voltage Rating: 400 V



4956216 2

RS PRO 3-WAY NON-FUSED TERMINAL BLOCK, 16A, SCREW DOWN

- ขนาดบรรจุภัณฑ์: 5 x EA
- Number of Ways: 3
 - Current Rating: 16 A
 - Wire Size: 2.5 mm²
 - Termination Method: Screw Down
 - Mounting Type: Cable Mount
 - Fused: No
 - Material: Nylon
 - Voltage Rating: 400 V



4956238 3

RS PRO 3-WAY NON-FUSED TERMINAL BLOCK, 16A, SCREW DOWN

- ขนาดบรรจุภัณฑ์: 5 x EA
- Number of Ways: 3
 - Current Rating: 16 A
 - Wire Size: 2.5 mm²
 - Termination Method: Screw Down
 - Mounting Type: Cable Mount
 - Fused: No
 - Material: Nylon
 - Voltage Rating: 400 V



4956250 3

RS PRO 3-WAY NON-FUSED TERMINAL BLOCK, 16A, SCREW DOWN

- ขนาดบรรจุภัณฑ์: 5 x EA
- Number of Ways: 3
 - Current Rating: 16 A
 - Wire Size: 2.5 mm²
 - Termination Method: Screw Down
 - Mounting Type: Cable Mount
 - Fused: No
 - Material: Nylon
 - Voltage Rating: 400 V



4956266 3

RS PRO 3-WAY NON-FUSED TERMINAL BLOCK, 16A, SCREW DOWN

- ขนาดบรรจุภัณฑ์: 5 x EA
- Number of Ways: 3
 - Current Rating: 16 A
 - Wire Size: 2.5 mm²
 - Termination Method: Screw Down
 - Mounting Type: Cable Mount
 - Fused: No
 - Material: Nylon
 - Voltage Rating: 400 V



4956272 3

RS PRO 3-WAY NON-FUSED TERMINAL BLOCK, 16A, SCREW DOWN

- ขนาดบรรจุภัณฑ์: 5 x EA
- Number of Ways: 3
 - Current Rating: 16 A
 - Wire Size: 2.5 mm²
 - Termination Method: Screw Down
 - Mounting Type: Cable Mount
 - Fused: No
 - Material: Nylon
 - Voltage Rating: 400 V



4956288 3

RS PRO 3-WAY NON-FUSED TERMINAL BLOCK, 16A, SCREW DOWN

- ขนาดบรรจุภัณฑ์: 5 x EA
- Number of Ways: 3
 - Current Rating: 16 A
 - Wire Size: 2.5 mm²
 - Termination Method: Screw Down
 - Mounting Type: Cable Mount
 - Fused: No
 - Material: Nylon
 - Voltage Rating: 400 V



4956294 3

RS PRO 3-WAY NON-FUSED TERMINAL BLOCK, 16A, SCREW DOWN

- ขนาดบรรจุภัณฑ์: 5 x EA
- Number of Ways: 3
 - Current Rating: 16 A
 - Wire Size: 2.5 mm²
 - Termination Method: Screw Down
 - Mounting Type: Cable Mount
 - Fused: No
 - Material: Nylon
 - Voltage Rating: 400 V



4956301 3

12 WAY POLYPROPYLENE 6A TERMINAL BLOCK

- ขนาดบรรจุภัณฑ์: 5 x EA
- Number of Ways: 12
 - Current Rating: 6 A
 - Wire Size: 14 AWG
 - Termination Method: Screw Down
 - Fused: No
 - Material: PP
 - Pitch: 8 mm
 - Voltage Rating: 400 V



7033814 12

12 WAY POLYPROPYLENE 10A TERMINAL BLOCK

- ขนาดบรรจุภัณฑ์: 5 x EA
- Number of Ways: 12
 - Current Rating: 24 A
 - Wire Size: 12 AWG
 - Termination Method: Screw Down
 - Fused: No
 - Material: PP
 - Pitch: 10 mm
 - Voltage Rating: 380 V



7033818 12

RS PRO 12-WAY NON-FUSED TERMINAL BLOCK, 76A, SCREW

- ขนาดบรรจุภัณฑ์: 5 x EA
- Number of Ways: 12
 - Current Rating: 76 A
 - Wire Size: 6 AWG
 - Termination Method: Screw Down
 - Fused: No
 - Material: PP
 - Pitch: 15 mm
 - Voltage Rating: 400 V



7033820 12

RS PRO 12-WAY NON-FUSED TERMINAL BLOCK, 101A, SCREW

- ขนาดบรรจุภัณฑ์: 5 x EA
- Number of Ways: 12
 - Current Rating: 101 A
 - Wire Size: 4 AWG
 - Termination Method: Screw Down
 - Fused: No
 - Material: PP
 - Pitch: 19.5 mm
 - Voltage Rating: 400 V



7033824 12

RS PRO 12-WAY NON-FUSED TERMINAL BLOCK, 20A, SCREW

- ขนาดบรรจุภัณฑ์: 5 x EA
- Number of Ways: 12
 - Current Rating: 20 A
 - Wire Size: 10 AWG
 - Termination Method: Screw Down
 - Fused: No
 - Material: PP
 - Pitch: 12 mm
 - Voltage Rating: 380 V



7033827 12

BLACK 6MMSQ. TERMINAL STRIP 450V

- ขนาดบรรจุภัณฑ์: 5 x EA
- Number of Ways: 12
 - Current Rating: 32 A
 - Wire Size: 6 mm²
 - Termination Method: Screw
 - Fused: No
 - Material: POLYPROPYLENE
 - Pitch: 12 mm
 - Voltage Rating: 380 V



7033830 12

BLACK 2.5MMSQ. TERMINAL STRIP 250V

- ขนาดบรรจุภัณฑ์: 5 x EA
- Number of Ways: 12
 - Current Rating: 24 A
 - Wire Size: 2.5 mm²
 - Termination Method: Screw
 - Fused: No
 - Material: POLYPROPYLENE
 - Pitch: 8 mm
 - Voltage Rating: 400 V



7033833 12

BLACK 4MMSQ. TERMINAL STRIP 450V

- ขนาดบรรจุภัณฑ์: 5 x EA
- Number of Ways: 12
 - Current Rating: 24 A
 - Wire Size: 4 mm²
 - Termination Method: Screw
 - Fused: No
 - Material: POLYPROPYLENE
 - Pitch: 10 mm
 - Voltage Rating: 380 V



7033836 12

BLACK 16MMSQ. TERMINAL STRIP 450V

- ขนาดบรรจุภัณฑ์: 5 x EA
- Number of Ways: 12
 - Current Rating: 76 A
 - Wire Size: 16 mm²
 - Termination Method: Screw
 - Fused: No
 - Material: POLYPROPYLENE
 - Pitch: 15 mm
 - Voltage Rating: 400 V



7033842 12

2 WAY 10A CERAMIC TERMINAL BLOCK 230V

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Number of Ways: 2
 - Current Rating: 32 A
 - Wire Size: 12 AWG
 - Termination Method: Screw Down
 - Fused: No
 - Material: Ceramic
 - Voltage Rating: 450 V
 - Minimum Operating Temperature: -40 °C


7033846 2

BLACK 10MMSQ. TERMINAL STRIP 450V

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Number of Ways: 12
 - Current Rating: 57 A
 - Wire Size: 10 mm²
 - Termination Method: Screw
 - Fused: No
 - Material: POLYPROPYLENE
 - Pitch: 11 mm
 - Voltage Rating: 400 V


7033849 12

3 WAY 15A TERMINAL BLOCK

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Number of Ways: 3
 - Current Rating: 57 A
 - Wire Size: 8 AWG
 - Termination Method: Screw Down
 - Fused: No
 - Material: Ceramic
 - Voltage Rating: 450 V
 - Minimum Operating Temperature: -40 °C


7033852 3

RS PRO 3-WAY NON-FUSED TERMINAL BLOCK, 32A, SCREW DOWN

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Number of Ways: 3
 - Current Rating: 32 A
 - Wire Size: 12 AWG
 - Termination Method: Screw Down
 - Fused: No
 - Material: Ceramic
 - Voltage Rating: 450 V
 - Minimum Operating Temperature: -40 °C


7033855 3

2 WAY 15A CERAMIC TERMINAL BLOCK 450V

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Number of Ways: 2
 - Current Rating: 57 A
 - Wire Size: 8 AWG
 - Termination Method: Screw Down
 - Fused: No
 - Material: Ceramic
 - Voltage Rating: 450 V
 - Minimum Operating Temperature: -40 °C


7033858 2

2 WAY 30A CERAMIC TERMINAL BLOCK 450V

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Number of Ways: 2
 - Current Rating: 76 A
 - Wire Size: 6 AWG
 - Termination Method: Screw Down
 - Fused: No
 - Material: Ceramic
 - Voltage Rating: 450 V
 - Minimum Operating Temperature: -40 °C


7033861 2

3 WAY 30A CERAMIC TERMINAL BLOCK 450V

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Number of Ways: 3
 - Current Rating: 76 A
 - Wire Size: 6 AWG
 - Termination Method: Screw Down
 - Fused: No
 - Material: Ceramic
 - Voltage Rating: 450 V
 - Minimum Operating Temperature: -40 °C


7033864 3

12 WAY POLYETHYLENE TERMINAL BLOCK, 3A

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Number of Ways: 12
 - Current Rating: 3 → 24 A
 - Wire Size: 12 AWG
 - Termination Method: Screw
 - Mounting Type: Free Hanging, Panel Mount
 - Fused: No
 - Material: PE
 - Pitch: 8 mm


7638113 12

12 WAY POLYETHYLENE TERMINAL BLOCK, 5A

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Number of Ways: 12
 - Current Rating: 5 → 32 A
 - Wire Size: 10 AWG
 - Termination Method: Screw
 - Mounting Type: Free Hanging, Panel Mount
 - Fused: No
 - Material: PE
 - Pitch: 10 mm


7638116 12

12 WAY MOULDED BARRIER STRIP, 15A

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Number of Ways: 12
 - Current Rating: 30 A
 - Wire Size: 12 AWG
 - Termination Method: Screw
 - Mounting Type: Free Hanging, Panel Mount
 - Fused: No
 - Material: Polyamide
 - Voltage Rating: 750 V


7638122 12

3 WAY MOULDED BARRIER STRIP, 15A

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Number of Ways: 3
 - Current Rating: 20 A
 - Wire Size: 12 AWG
 - Termination Method: Screw
 - Mounting Type: Free Hanging, Panel Mount
 - Fused: No
 - Material: Polyamide
 - Voltage Rating: 750 V


7638129 3

RS PRO 10-WAY NON-FUSED TERMINAL BLOCK, 24A, SCREW

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Number of Ways: 10
 - Current Rating: 24 A
 - Wire Size: 1.5 mm²
 - Termination Method: Screw
 - Fused: No
 - Material: PC
 - Pitch: 9.4 mm
 - Voltage Rating: 450 V


7869196 10

RS PRO 10-WAY NON-FUSED TERMINAL BLOCK, 57A, SCREW

- ขนาดบรรจุภัณฑ์: **6 x EA**
- Number of Ways: 10
 - Current Rating: 57 A
 - Wire Size: 10 mm²
 - Termination Method: Screw
 - Fused: No
 - Material: PC
 - Voltage Rating: 500 V
 - Pitch: 16.5 mm


7869207 10

RS PRO 1-WAY NON-FUSED TERMINAL BLOCK, 125A, SCREW TERMINALS, 35

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Number of Ways: 1
 - Current Rating: 125 A
 - Wire Size: 35 mm²
 - Termination Method: Screw
 - Fused: No
 - Material: PC
 - Voltage Rating: 500 V
 - Minimum Operating Temperature: +85 °C


7869213 1

CERAMIC TERMINAL BLOCKS, 4 MM2, 4 POLES

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Number of Ways: 4
 - Current Rating: 5 → 32 A
 - Wire Size: 12 AWG
 - Termination Method: Screw Down
 - Mounting Type: Screw
 - Fused: No
 - Material: Ceramic
 - Voltage Rating: 450 V


8133098 4

RS PRO 4-WAY NON-FUSED TERMINAL BLOCK, 30 → 76A, SCREW DOWN

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Number of Ways: 4
 - Current Rating: 30 → 76 A
 - Wire Size: 6 AWG
 - Termination Method: Screw Down
 - Mounting Type: Screw
 - Fused: No
 - Material: Ceramic
 - Voltage Rating: 450 V


8133101 4

CERAMIC TERMINAL BLOCKS, 4 MM2,3 POLES

- ขนาดบรรจุภัณฑ์: 5 x EA
- Number of Ways: 3
 - Current Rating: 5 → 32 A
 - Wire Size: 12 AWG
 - Termination Method: Screw Down
 - Mounting Type: Screw
 - Fused: No
 - Material: Ceramic
 - Voltage Rating: 250 V



8133105 3

RS PRO 4-WAY NON-FUSED TERMINAL BLOCK, 15 → 57A, SCREW DOWN

- ขนาดบรรจุภัณฑ์: 5 x EA
- Number of Ways: 4
 - Current Rating: 15 → 57 A
 - Wire Size: 8 AWG
 - Termination Method: Screw Down
 - Mounting Type: Screw
 - Fused: No
 - Material: Ceramic
 - Voltage Rating: 450 V



8133108 4

RS PRO 1-WAY NON-FUSED TERMINAL BLOCK, 30 → 76A, SCREW DOWN

- ขนาดบรรจุภัณฑ์: 10 x EA
- Number of Ways: 1
 - Current Rating: 30 → 76 A
 - Wire Size: 6 AWG
 - Termination Method: Screw Down
 - Mounting Type: Screw
 - Fused: No
 - Material: Ceramic
 - Voltage Rating: 450 V



8133111 1

CERAMIC TERMINAL BLOCKS, 4 MM2, 1 POLE

- ขนาดบรรจุภัณฑ์: 10 x EA
- Number of Ways: 1
 - Current Rating: 5 → 32 A
 - Wire Size: 12 AWG
 - Termination Method: Screw Down
 - Mounting Type: Screw
 - Fused: No
 - Material: Ceramic
 - Voltage Rating: 450 V



8133114 1

CERAMIC TERMINAL BLOCKS, 10 MM2, 1 POLE

- ขนาดบรรจุภัณฑ์: 10 x EA
- Number of Ways: 1
 - Current Rating: 15 → 57 A
 - Wire Size: 8 AWG
 - Termination Method: Screw Down
 - Mounting Type: Screw
 - Fused: No
 - Material: Ceramic
 - Voltage Rating: 450 V



8133117 1

PA TERMINAL BLOCKS, 4MM2

- ขนาดบรรจุภัณฑ์: 5 x EA
- Number of Ways: 12
 - Current Rating: 3 → 24 A
 - Wire Size: 12 AWG
 - Termination Method: Screw Down
 - Mounting Type: Screw
 - Fused: No
 - Material: Polyamide
 - Voltage Rating: 380 V



8133120 12

PA TERMINAL BLOCKS, 6 MM2

- ขนาดบรรจุภัณฑ์: 5 x EA
- Number of Ways: 12
 - Current Rating: 5 → 32 A
 - Wire Size: 10 AWG
 - Termination Method: Screw Down
 - Mounting Type: Screw
 - Fused: No
 - Material: Polyamide
 - Voltage Rating: 380 V



8133123 12

RS PRO 12-WAY NON-FUSED TERMINAL BLOCK, 10 → 57A, SCREW

- ขนาดบรรจุภัณฑ์: 5 x EA
- Number of Ways: 12
 - Current Rating: 10 → 57 A
 - Wire Size: 8 AWG
 - Termination Method: Screw Down
 - Mounting Type: Screw
 - Fused: No
 - Material: Polyamide
 - Voltage Rating: 400 V



8133127 12

RS PRO 12-WAY NON-FUSED TERMINAL BLOCK, 15 → 61A, SCREW

- ขนาดบรรจุภัณฑ์: 5 x EA
- Number of Ways: 12
 - Current Rating: 15 → 61 A
 - Wire Size: 7 AWG
 - Termination Method: Screw Down
 - Mounting Type: Screw
 - Fused: No
 - Material: Polyamide
 - Voltage Rating: 400 V



8133136 12

RS PRO 12-WAY NON-FUSED TERMINAL BLOCK, 30 → 76A, SCREW

- ขนาดบรรจุภัณฑ์: 5 x EA
- Number of Ways: 12
 - Current Rating: 30 → 76 A
 - Wire Size: 6 AWG
 - Termination Method: Screw Down
 - Mounting Type: Screw
 - Fused: No
 - Material: Polyamide
 - Voltage Rating: 400 V



8133139 12

RS PRO 12-WAY NON-FUSED TERMINAL BLOCK, 10 → 57A, SCREW

- ขนาดบรรจุภัณฑ์: 5 x EA
- Number of Ways: 12
 - Current Rating: 10 → 57 A
 - Wire Size: 8 AWG
 - Termination Method: Screw
 - Mounting Type: Cable Mount
 - Fused: No
 - Material: Polyamide
 - Voltage Rating: 450 V



8407923 12

PA TERMINAL BLOCK 2.5MM2

- ขนาดบรรจุภัณฑ์: 5 x EA
- Number of Ways: 12
 - Current Rating: 2.5 → 20 A
 - Wire Size: 14 AWG
 - Termination Method: Screw
 - Mounting Type: Cable Mount
 - Fused: No
 - Material: Polyamide
 - Voltage Rating: 450 V



8407929 12

RS PRO 12-WAY NON-FUSED TERMINAL BLOCK, 5 → 32A, SCREW

- ขนาดบรรจุภัณฑ์: 5 x EA
- Number of Ways: 12
 - Current Rating: 5 → 32 A
 - Wire Size: 10 AWG
 - Termination Method: Screw
 - Mounting Type: Cable Mount
 - Fused: No
 - Material: Polyamide
 - Voltage Rating: 450 V



8407932 12

RS PRO 12-WAY NON-FUSED TERMINAL BLOCK, 3 → 24A, SCREW

- ขนาดบรรจุภัณฑ์: 5 x EA
- Number of Ways: 12
 - Current Rating: 3 → 24 A
 - Wire Size: 12 AWG
 - Termination Method: Screw
 - Mounting Type: Cable Mount
 - Fused: No
 - Material: Polyamide
 - Voltage Rating: 450 V



8407935 12

RS PRO 12-WAY NON-FUSED TERMINAL BLOCK, 17.5A, SCREW

- ขนาดบรรจุภัณฑ์: 5 x EA
- Number of Ways: 12
 - Current Rating: 17.5 A
 - Wire Size: 16 AWG
 - Termination Method: Screw
 - Mounting Type: Cable Mount
 - Fused: No
 - Material: Polyamide
 - Voltage Rating: 450 V



8407939 12

RS PRO 12-WAY NON-FUSED TERMINAL BLOCK, 32A, SCREW

- ขนาดบรรจุภัณฑ์: 5 x EA
- Number of Ways: 12
 - Current Rating: 32 A
 - Wire Size: 12 AWG
 - Termination Method: Screw
 - Mounting Type: Cable Mount
 - Fused: No
 - Material: Polyamide
 - Voltage Rating: 450 V



8407941 12

RS PRO 12-WAY NON-FUSED TERMINAL BLOCK, 32A, SCREW

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Number of Ways: 12
 - Current Rating: 32 A
 - Wire Size: 12 AWG
 - Termination Method: Screw
 - Mounting Type: Cable Mount
 - Fused: No
 - Material: Polyamide
 - Voltage Rating: 450 V



8407951 12

PA TERMINAL BLOCK 2.5MM2

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Number of Ways: 12
 - Current Rating: 17.5 A
 - Wire Size: 16 AWG
 - Termination Method: Screw
 - Mounting Type: Cable Mount
 - Fused: No
 - Material: Polyamide
 - Voltage Rating: 450 V



8407954 12

RS PRO 12-WAY NON-FUSED TERMINAL BLOCK, 24A, SCREW

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Number of Ways: 12
 - Current Rating: 24 A
 - Wire Size: 14 AWG
 - Termination Method: Screw
 - Mounting Type: Cable Mount
 - Fused: No
 - Material: Polyamide
 - Voltage Rating: 450 V



8407957 12

RS PRO 12-WAY NON-FUSED TERMINAL BLOCK, 41A, SCREW

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Number of Ways: 12
 - Current Rating: 41 A
 - Wire Size: 10 AWG
 - Termination Method: Screw
 - Mounting Type: Cable Mount
 - Fused: No
 - Material: Polyamide
 - Voltage Rating: 450 V



8407960 12

RS PRO 12-WAY NON-FUSED TERMINAL BLOCK, 2.5 → 20A, SCREW

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Number of Ways: 12
 - Current Rating: 2.5 → 20 A
 - Wire Size: 14 AWG
 - Termination Method: Screw
 - Fused: No
 - Material: Polyamide
 - Voltage Rating: 450 V
 - Pitch: 7.2 mm



8659821 12

PA TERM BLOCKS HORIZONTAL PLUG 4MM2

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Number of Ways: 12
 - Current Rating: 3 → 24 A
 - Wire Size: 12 AWG
 - Termination Method: Screw
 - Fused: No
 - Material: Polyamide
 - Voltage Rating: 450 V
 - Minimum Operating Temperature: -40 °C



8659830 12

RS PRO 12-WAY NON-FUSED TERMINAL BLOCK, 5 → 32A, SCREW

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Number of Ways: 12
 - Current Rating: 5 → 32 A
 - Wire Size: 10 AWG
 - Termination Method: Screw
 - Fused: No
 - Material: Polyamide
 - Voltage Rating: 450 V
 - Minimum Operating Temperature: -40 °C



8659833 12

RS PRO 12-WAY NON-FUSED TERMINAL BLOCK, 10 → 57A, SCREW

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Number of Ways: 12
 - Current Rating: 10 → 57 A
 - Wire Size: 8 AWG
 - Termination Method: Screw Down
 - Mounting Type: Cable Mount
 - Fused: No
 - Material: PE
 - Voltage Rating: 400 V



8670963 12

RS PRO 12-WAY NON-FUSED TERMINAL BLOCK, 15 → 61A, SCREW

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Number of Ways: 12
 - Current Rating: 15 → 61 A
 - Wire Size: 7 AWG
 - Termination Method: Screw Down
 - Mounting Type: Cable Mount
 - Fused: No
 - Material: PE
 - Voltage Rating: 400 V



8670972 12

RS PRO 12-WAY NON-FUSED TERMINAL BLOCK, 30 → 76A, SCREW

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Number of Ways: 12
 - Current Rating: 30 → 76 A
 - Wire Size: 6 AWG
 - Termination Method: Screw Down
 - Mounting Type: Cable Mount
 - Fused: No
 - Material: PE
 - Voltage Rating: 400 V



8670975 12

RS PRO 12-WAY NON-FUSED TERMINAL BLOCK, 60 → 101A, SCREW

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Number of Ways: 12
 - Current Rating: 60 → 101 A
 - Wire Size: 4 AWG
 - Termination Method: Screw Down
 - Mounting Type: Cable Mount
 - Fused: No
 - Material: PE
 - Voltage Rating: 400 V



8670979 12

RS PRO 12-WAY NON-FUSED TERMINAL BLOCK, 60 → 101A, SCREW


- ขนาดบรรจุภัณฑ์: **5 x EA**
- Number of Ways: 12
 - Current Rating: 60 → 101 A
 - Wire Size: 4 AWG
 - Termination Method: Screw Down
 - Mounting Type: Cable Mount
 - Fused: No
 - Material: PA 66
 - Voltage Rating: 400 V



8670988 12

RS PRO 10-WAY NON-FUSED TERMINAL BLOCK, SCREW

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Number of Ways: 10
 - Wire Size: 2.5 mm²
 - Termination Method: Screw
 - Mounting Type: Panel Mount
 - Fused: No
 - Material: PC
 - Voltage Rating: 450 V
 - Maximum Operating Temperature: +85 °C



8680733 10

RS PRO 12-WAY NON-FUSED TERMINAL BLOCK, SCREW

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Number of Ways: 12
 - Wire Size: 25 mm²
 - Termination Method: Screw
 - Mounting Type: Panel Mount
 - Fused: No
 - Material: PP
 - Pitch: 19.5 mm
 - Voltage Rating: 500 V



8680742 12

RS PRO 10-WAY NON-FUSED TERMINAL BLOCK, SCREW

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Number of Ways: 10
 - Wire Size: 10 mm²
 - Termination Method: Screw
 - Mounting Type: Panel Mount
 - Fused: No
 - Material: PC
 - Voltage Rating: 450 V
 - Maximum Operating Temperature: +85 °C



8680758 10

RS PRO 10-WAY NON-FUSED TERMINAL BLOCK, SCREW

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Number of Ways: 10
 - Wire Size: 1.5 mm²
 - Termination Method: Screw
 - Mounting Type: Panel Mount
 - Fused: No
 - Material: PC
 - Voltage Rating: 450 V
 - Maximum Operating Temperature: +85 °C



8680768 10

RS PRO 3-WAY NON-FUSED TERMINAL BLOCK, SCREW TERMINALS, 2.5 MM²,

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Number of Ways: 3
 - Wire Size: 2.5 mm²
 - Termination Method: Screw
 - Mounting Type: Panel Mount
 - Fused: No
 - Material: Polyamide
 - Voltage Rating: 400 V
 - Maximum Operating Temperature: +100 °C



8680777 3

RS PRO 10-WAY NON-FUSED TERMINAL BLOCK, SCREW

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Number of Ways: 10
 - Wire Size: 4 mm²
 - Termination Method: Screw
 - Mounting Type: Panel Mount
 - Fused: No
 - Material: PC
 - Voltage Rating: 450 V
 - Maximum Operating Temperature: +85 °C



8680796 10

RS PRO 12-WAY NON-FUSED TERMINAL BLOCK, SCREW

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Number of Ways: 12
 - Wire Size: 16 mm²
 - Termination Method: Screw
 - Mounting Type: Panel Mount
 - Fused: No
 - Material: PP
 - Pitch: 15 mm
 - Voltage Rating: 450 V



8680803 12

TERM.BLOCK 1WAY 2.5-TR

- ขนาดบรรจุภัณฑ์: **50 x EA**
- Number of Ways: 1
 - Wire Size: 2.5 mm²
 - Termination Method: Screw
 - Fused: No
 - Material: PC
 - Voltage Rating: 450 V
 - Maximum Operating Temperature: +85 °C
 - Enclosed: Yes



8680809 1

RS PRO 3-WAY NON-FUSED TERMINAL BLOCK, SCREW TERMINALS, 2.5 MM²,

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Number of Ways: 3
 - Wire Size: 2.5 mm²
 - Termination Method: Screw
 - Mounting Type: Panel Mount
 - Fused: No
 - Material: Polyamide
 - Pitch: 21.5 mm
 - Voltage Rating: 450 V



8680812 3

RS PRO 12-WAY NON-FUSED TERMINAL BLOCK, SCREW

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Number of Ways: 12
 - Wire Size: 4 mm²
 - Termination Method: Screw
 - Mounting Type: Panel Mount
 - Fused: No
 - Material: Polyamide
 - Pitch: 12 mm
 - Voltage Rating: 400 V



8680815 12

RS PRO 12-WAY DISCONNECT TERMINAL BLOCK, 76A, SCREW

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Number of Ways: 12
 - Current Rating: 76 A
 - Wire Size: 16 mm²
 - Termination Method: Screw
 - Mounting Type: Surface Mount
 - Fused: No
 - Material: Glass Fibre Reinforced, Polyamide
 - Voltage Rating: 450 V



9106788 12

RS PRO END COVER FOR USE WITH FOR USE WITH TERMINAL BLOCKS

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Accessory Type: End Cover
 - For Use With: Terminal Block
 - Series: Polyamide



425437 End Cover

RS PRO TERMINAL BLOCK COVER FOR USE WITH TERMINAL BLOCKS

- ขนาดบรรจุภัณฑ์: **4 x EA**
- Accessory Type: Terminal Block Cover
 - For Use With: Terminal Block



4649794 Terminal Block

RS PRO SHROUD KIT FOR USE WITH TERMINAL BLOCKS

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Accessory Type: Shroud Kit
 - For Use With: Terminal Block



4649801 Shroud Kit

NYLON TERMINAL BLOCK HOUSING IP44, CABLE MOUNT

- ขนาดบรรจุภัณฑ์: **5 x EA**
- IP Rating: IP44
 - Series: TH110
 - Material: Nylon
 - Mounting Type: Cable Mount
 - Number of Contacts: 3
 - Maximum Operating Temperature: 125.0 °C
 - Minimum Operating Temperature: -20.0 °C



4561060 IP44

NYLON TERMINAL BLOCK HOUSING IP67, CABLE MOUNT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- IP Rating: IP67
 - Series: TH200
 - Material: Nylon
 - Mounting Type: Cable Mount
 - Number of Contacts: 3
 - Maximum Operating Temperature: 125.0 °C
 - Minimum Operating Temperature: -20.0 °C



4924641 IP67

NYLON TERMINAL BLOCK HOUSING IP68, CABLE MOUNT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- IP Rating: IP68
 - Series: TH387
 - Material: Nylon
 - Mounting Type: Cable Mount
 - Number of Contacts: 4
 - Maximum Operating Temperature: 125.0 °C
 - Minimum Operating Temperature: -20.0 °C



9106772 IP68

NYLON TERMINAL BLOCK HOUSING IP68, CABLE MOUNT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- IP Rating: IP68
 - Series: TH387
 - Material: Nylon
 - Mounting Type: Cable Mount
 - Number of Contacts: 4
 - Maximum Operating Temperature: 125.0 °C
 - Minimum Operating Temperature: -20.0 °C



9106781 IP68

CONTACT,AUXILIARY,240V

ขนาดบรรจุภัณฑ์: 1 x EA

- Number of Contacts: 2
- Normal State Configuration: NO/NC
- Mounting Style: DIN Rail Mount
- Contact Voltage Rating: 240 V ac
- Pole and Throw Configuration: DP



3313696 2

RS PRO SPLIT CORE CURRENT TRANSDUCER, 50A INPUT, 24 V

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Transformer Type: Split Core
 - Supply Voltage: 24 V
 - Input Current: 50 A
 - Overall Height: 51 mm
 - Overall Depth: 26.5 mm
 - Minimum Temperature: -25 °C
 - Maximum Temperature: +65 °C
 - Series: CVH500IP01



2100642 Split Core

RS PRO SPLIT CORE CURRENT TRANSDUCER, 5A INPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Transformer Type: Split Core
 - Input Current: 5 A
 - Overall Height: 51 mm
 - Overall Depth: 26.5 mm
 - Minimum Temperature: -20 °C
 - Maximum Temperature: +65 °C
 - Series: CVH5R0VP01
 - Mounting Type: Panel Mount



2100645 Split Core

RS PRO MAGNETIC PICKUP

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 10 V
 - Overall Height: 22 mm
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +100 °C



304166 10 V

RS PRO MAGNETIC PICKUP

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 5 → 15 V dc
 - Overall Height: 28.6 mm
 - Minimum Operating Temperature: -25 °C
 - Maximum Operating Temperature: +85 °C



304172 5 → 15 V dc

RS PRO INCREMENTAL INCREMENTAL ENCODER, 1024 PPR, HTL INVERTED

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Encoder Technology: Incremental
 - Pulses Per Revolution: 1024
 - Maximum Revolutions: 10000 rpm
 - Output Signal Type: HTL Inverted
 - Shaft Type: Solid
 - Supply Voltage: 5 → 30 V dc
 - Shaft Diameter: 6 mm
 - Resolution: 2500 ppr



7951028 Incremental

RS PRO INCREMENTAL INCREMENTAL ENCODER, 50 PPR, HTL INVERTED

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Encoder Technology: Incremental
 - Pulses Per Revolution: 50
 - Maximum Revolutions: 8000 rpm
 - Output Signal Type: HTL Inverted
 - Shaft Type: Solid
 - Supply Voltage: 5 → 30 V dc
 - Shaft Diameter: 10 mm
 - Resolution: 50 ppr



7951031 Incremental

RS PRO INCREMENTAL INCREMENTAL ENCODER, 200 PPR, HTL INVERTED

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Encoder Technology: Incremental
 - Pulses Per Revolution: 200
 - Maximum Revolutions: 8000 rpm
 - Output Signal Type: HTL Inverted
 - Shaft Type: Solid
 - Supply Voltage: 5 → 30 V dc
 - Shaft Diameter: 10 mm
 - Resolution: 2500 ppr



7951040 Incremental

RS PRO INCREMENTAL INCREMENTAL ENCODER, 4096 PPR, HTL INVERTED

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Encoder Technology: Incremental
 - Pulses Per Revolution: 4096
 - Maximum Revolutions: 6000 rpm
 - Output Signal Type: HTL Inverted
 - Shaft Type: Hollow
 - Supply Voltage: 10 → 30 V dc
 - Shaft Diameter: 12 mm
 - Resolution: 5000 ppr



7951141 Incremental

RS PRO LINEAR MEASURING LINEAR TRANSDUCER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Encoder Technology: Linear Measuring
 - Stroke: 25 mm
 - IP Rating: IP65
 - Overall Height: 8.6 mm
 - Overall Width: 28.1 mm
 - Overall Depth: 52 mm
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



9094196 Linear Measuring

RS PRO LINEAR MEASURING LINEAR TRANSDUCER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Encoder Technology: Linear Measuring
 - Stroke: 100 mm
 - IP Rating: IP65
 - Overall Height: 8.6 mm
 - Overall Width: 28.1 mm
 - Overall Depth: 127 mm
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



9094203 Linear Measuring

RS PRO LINEAR MEASURING LINEAR TRANSDUCER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Encoder Technology: Linear Measuring
 - Stroke: 50 mm
 - IP Rating: IP65
 - Overall Height: 8.6 mm
 - Overall Width: 28.1 mm
 - Overall Depth: 77 mm
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



9094209 Linear Measuring

RS PRO LINEAR MEASURING LINEAR TRANSDUCER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Encoder Technology: Linear Measuring
 - Stroke: 200 mm
 - IP Rating: IP65
 - Overall Height: 8.6 mm
 - Overall Width: 28.1 mm
 - Overall Depth: 227 mm
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +85 °C



9094212 Linear Measuring

RS PRO WHITE DIN RAIL TERMINAL BLOCK, SINGLE LEVEL, 0.2 → 2.5MM²,

ขนาดบรรจุภัณฑ์: 10 x EA

- Colour: White
- Number of Levels: Single
- Cable CSA: 0.2 → 2.5 mm²
- Current Rating: 24 A
- Voltage Rating: 800 V
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +105 °C



501613 White

RS PRO BROWN FEED THROUGH TERMINAL BLOCK, SINGLE LEVEL, 0,2

ขนาดบรรจุภัณฑ์: 10 x EA

- Colour: Brown
- Number of Levels: Single
- Cable CSA: 0.2 → 2.5 mm²
- Current Rating: 24 A
- Voltage Rating: 800 V
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +105 °C



501635 Brown

RS PRO GREY FEED THROUGH TERMINAL BLOCK, SINGLE LEVEL, 0,2

ขนาดบรรจุภัณฑ์: 10 x EA

- Colour: Grey
- Number of Levels: Single
- Cable CSA: 0.2 → 2.5 mm²
- Current Rating: 24 A
- Voltage Rating: 800 V
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +105 °C



501639 Grey

RS PRO YELLOW DIN RAIL TERMINAL BLOCK, SINGLE LEVEL, 0.2 → 2.5MM²,

ขนาดบรรจุภัณฑ์: 10 x EA

- Colour: Yellow
- Number of Levels: Single
- Cable CSA: 0.2 → 2.5 mm²
- Current Rating: 24 A
- Voltage Rating: 800 V
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +105 °C



501641 Yellow

RS PRO BLACK DIN RAIL TERMINAL BLOCK, SINGLE LEVEL, 0.2 → 4MM²,

ขนาดบรรจุภัณฑ์: 10 x EA

- Colour: Black
- Number of Levels: Single
- Cable CSA: 0.2 → 4 mm²
- Current Rating: 32 A
- Voltage Rating: 800 V
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +105 °C



501645 Black

RS PRO ORANGE DIN RAIL TERMINAL BLOCK, SINGLE LEVEL, 0.2 → 4MM²,

ขนาดบรรจุภัณฑ์: 10 x EA

- Colour: Orange
- Number of Levels: Single
- Cable CSA: 0.2 → 4 mm²
- Current Rating: 32 A
- Voltage Rating: 800 V
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +105 °C



501651 Orange

RS PRO YELLOW DIN RAIL TERMINAL BLOCK, 0.2 → 4MM²

ขนาดบรรจุภัณฑ์: 10 x EA

- Colour: Yellow
- Cable CSA: 0.2 → 4 mm²
- Current Rating: 32 A



501663 Yellow

RS PRO RED DIN RAIL TERMINAL BLOCK, SINGLE LEVEL, 0.2 → 4MM²,

ขนาดบรรจุภัณฑ์: 10 x EA

- Colour: Red
- Number of Levels: Single
- Cable CSA: 0.2 → 4 mm²
- Current Rating: 32 A
- Voltage Rating: 800 V
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +105 °C



501673 Red

RS PRO BROWN DIN RAIL TERMINAL BLOCK, 16 → 50MM², 1 KV

ขนาดบรรจุภัณฑ์: 1 x EA

- Colour: Brown
- Series: RK
- American Wire Gauge: 6 → 0 AWG
- Cable CSA: 16 → 50 mm²
- Voltage Rating: 1 kV
- Current Rating: 150 A



501714 Brown

RS PRO BROWN DIN RAIL TERMINAL BLOCK, 35 → 95MM², 1 KV

ขนาดบรรจุภัณฑ์: 1 x EA

- Colour: Brown
- Series: RK
- American Wire Gauge: 2 → 0000 AWG
- Cable CSA: 35 → 95 mm²
- Voltage Rating: 1 kV
- Current Rating: 232 A



501718 Brown

RS PRO BROWN DIN RAIL TERMINAL BLOCK, SINGLE LEVEL, 0.2 → 4MM²,

ขนาดบรรจุภัณฑ์: 10 x EA

- Colour: Brown
- Number of Levels: Single
- Cable CSA: 0.2 → 4 mm²
- Current Rating: 32 A
- Voltage Rating: 800 V
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +105 °C



501720 Brown

RS PRO BROWN DIN RAIL TERMINAL BLOCK, 2.5 → 35MM², 800 V

ขนาดบรรจุภัณฑ์: 10 x EA

- Colour: Brown
- Series: RK
- American Wire Gauge: 12 → 2 AWG
- Cable CSA: 2.5 → 35 mm²
- Voltage Rating: 800 V
- Current Rating: 125 A



501724 Brown

RS PRO ORANGE DIN RAIL TERMINAL BLOCK, SINGLE LEVEL, 0.2 → 2.5MM²,

ขนาดบรรจุภัณฑ์: 10 x EA

- Colour: Orange
- Number of Levels: Single
- Cable CSA: 0.2 → 2.5 mm²
- Current Rating: 24 A
- Voltage Rating: 800 V
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +105 °C



501730 Orange

RS PRO BROWN DIN RAIL TERMINAL BLOCK, 2.5 → 16MM², 800 V

ขนาดบรรจุภัณฑ์: 10 x EA

- Colour: Brown
- American Wire Gauge: 10 → 4 AWG
- Series: RK
- Termination Method: Screw
- Cable CSA: 2.5 → 16 mm²
- Voltage Rating: 800 V
- Current Rating: 85 A



501770 Brown

RS PRO GREY DIN RAIL TERMINAL BLOCK, SINGLE LEVEL, 0.2 → 4MM²,

ขนาดบรรจุภัณฑ์: 10 x EA

- Colour: Grey
- Number of Levels: Single
- Cable CSA: 0.2 → 4 mm²
- Current Rating: 32 A
- Voltage Rating: 800 V
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +105 °C



501803 Grey

RS PRO BLUE DIN RAIL TERMINAL BLOCK, 0.2 → 10MM², 800 V

ขนาดบรรจุภัณฑ์: 10 x EA

- Colour: Blue
- Series: RK
- American Wire Gauge: 22 → 6 AWG
- Cable CSA: 0.2 → 10 mm²
- Voltage Rating: 800 V
- Current Rating: 65 A



501819 Blue

RS PRO RED DIN RAIL TERMINAL BLOCK, SINGLE LEVEL, 0.2 → 2.5MM²,

ขนาดบรรจุภัณฑ์: **10 x EA**

- Colour: Red
- Number of Levels: Single
- Cable CSA: 0.2 → 2.5 mm²
- Current Rating: 24 A
- Voltage Rating: 800 V
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +105 °C



501821 Red

RS PRO BLUE DIN RAIL TERMINAL BLOCK, 0.2 → 4MM², 500 V

ขนาดบรรจุภัณฑ์: **10 x EA**

- Colour: Blue
- Series: RK
- American Wire Gauge: 22 → 10 AWG
- Cable CSA: 0.2 → 4 mm²
- Voltage Rating: 500 V
- Current Rating: 40 A
- Pitch: 6 mm



501831 Blue

RS PRO BLACK FUSED DIN RAIL TERMINAL, 0.5 → 10MM², 400 V

ขนาดบรรจุภัณฑ์: **10 x EA**

- Colour: Black
- Series: SK
- Termination Method: Screw
- Cable CSA: 0.5 → 10 mm²
- Fused: Yes
- Voltage Rating: 400 V
- Current Rating: 10 A
- Pitch: 6 mm



501837 Black

RS PRO BEIGE FEED THROUGH TERMINAL BLOCK, 500 V

ขนาดบรรจุภัณฑ์: **1 x EA**

- Colour: Beige
- American Wire Gauge: 22 → 12 AWG
- Series: STKD 1
- Termination Method: Screw
- Voltage Rating: 500 V
- Current Rating: 6.3 A



501843 Beige

RS PRO BLACK FUSED DIN RAIL TERMINAL, 0.5 → 10MM², 400 V

ขนาดบรรจุภัณฑ์: **10 x EA**

- Colour: Black
- American Wire Gauge: 22 → 8 AWG
- Series: SK
- Termination Method: Screw
- Cable CSA: 0.5 → 10 mm²
- Fused: Yes
- Voltage Rating: 400 V
- Current Rating: 10 A



501875 Black

CONNECTOR, TERMINAL, DIN RAIL, THREE TIER, 3 IN 1 OUT,

ขนาดบรรจุภัณฑ์: **1 x EA**

- Colour: Red
- Number of Levels: Triple
- Series: IK
- Cable CSA: 0.2 → 2.5 mm²
- Current Rating: 24 A
- Voltage Rating: 24 V dc
- Pitch: 5 mm



501893 Red

RS PRO BEIGE STUD TERMINAL, SINGLE LEVEL, 1 KV

ขนาดบรรจุภัณฑ์: **1 x EA**

- Colour: Beige
- Number of Levels: Single
- American Wire Gauge: 10 AWG
- Series: HSK
- Current Rating: 269 A
- Voltage Rating: 1 kV
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +120 °C



501910 Beige

RS PRO WHITE DIN RAIL TERMINAL BLOCK, SINGLE LEVEL, 0.2 → 4MM²,

ขนาดบรรจุภัณฑ์: **10 x EA**

- Colour: White
- Number of Levels: Single
- Cable CSA: 0.2 → 4 mm²
- Current Rating: 32 A
- Voltage Rating: 800 V
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +105 °C



501932 White

RS PRO BLACK DIN RAIL TERMINAL BLOCK, SINGLE LEVEL, 0.2 → 2.5MM²,

ขนาดบรรจุภัณฑ์: **10 x EA**

- Colour: Black
- Number of Levels: Single
- Cable CSA: 0.2 → 2.5 mm²
- Current Rating: 24 A
- Voltage Rating: 800 V
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +105 °C



501976 Black

RS PRO BEIGE STUD TERMINAL, SINGLE LEVEL, 1 KV

ขนาดบรรจุภัณฑ์: **1 x EA**

- Colour: Beige
- Number of Levels: Single
- American Wire Gauge: 14 → 2 AWG
- Series: HSK
- Current Rating: 125 A
- Voltage Rating: 1 kV
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +120 °C



501982 Beige

RS PRO STUD TERMINAL, 1 KV

ขนาดบรรจุภัณฑ์: **1 x EA**

- Series: HSK
- American Wire Gauge: 14 → 0 AWG
- Voltage Rating: 1 kV
- Current Rating: 150 A



501988 HSK

RS PRO BROWN DIN RAIL TERMINAL BLOCK, DOUBLE LEVEL, 0.2 → 2.5MM²,

ขนาดบรรจุภัณฑ์: **5 x EA**

- Colour: Brown
- Number of Levels: Double
- American Wire Gauge: 22 → 12 AWG
- Series: RKD
- Termination Method: Screw
- Cable CSA: 0.2 → 2.5 mm²
- Current Rating: 24 A
- Voltage Rating: 500 V



501994 Brown

RS PRO BROWN DIN RAIL TERMINAL BLOCK, DOUBLE LEVEL, 0.2 → 4MM²,

ขนาดบรรจุภัณฑ์: **5 x EA**

- Colour: Brown
- Number of Levels: Double
- American Wire Gauge: 22 → 10 AWG
- Series: RKD
- Termination Method: Screw
- Cable CSA: 0.2 → 4 mm²
- Voltage Rating: 500 V
- Current Rating: 32 A



501998 Brown

RS PRO BLUE DIN RAIL TERMINAL BLOCK, 0.2 → 2.5MM², 800 V

ขนาดบรรจุภัณฑ์: **10 x EA**

- Colour: Blue
- American Wire Gauge: 22 → 12 AWG
- Series: RK
- Termination Method: Screw
- Cable CSA: 0.2 → 2.5 mm²
- Current Rating: 24 A
- Voltage Rating: 800 V
- Minimum Operating Temperature: -40 °C



802783 Blue

RS PRO BLUE DIN RAIL TERMINAL BLOCK, 0.2 → 4MM², 500 V

ขนาดบรรจุภัณฑ์: **10 x EA**

- Colour: Blue
- American Wire Gauge: 22 → 10 AWG
- Series: RK
- Termination Method: Screw
- Cable CSA: 0.2 → 4 mm²
- Current Rating: 40 A
- Voltage Rating: 500 V
- Minimum Operating Temperature: -40 °C



815644 Blue

RS PRO BEIGE DIN RAIL TERMINAL BLOCK, 0.2 → 4MM², 800 V

ขนาดบรรจุภัณฑ์: **10 x EA**

- Colour: Beige
- American Wire Gauge: 22 → 11 AWG
- Series: RK
- Termination Method: Screw
- Cable CSA: 0.2 → 4 mm²
- Current Rating: 40 A
- Voltage Rating: 800 V
- Minimum Operating Temperature: -40 °C



815666 Beige

RS PRO BLUE FEED THROUGH TERMINAL BLOCK, 0.2 → 4MM², 800 V

- ขนาดบรรจุภัณฑ์: 10 x EA
- Colour: Blue
 - American Wire Gauge: 22 → 11 AWG
 - Series: RK
 - Termination Method: Screw
 - Cable CSA: 0.2 → 4 mm²
 - Current Rating: 40 A
 - Voltage Rating: 800 V
 - Minimum Operating Temperature: -40 °C



815672 Blue

RS PRO BROWN DIN RAIL TERMINAL BLOCK, 0.2 → 10MM², 800 V

- ขนาดบรรจุภัณฑ์: 10 x EA
- Colour: Brown
 - American Wire Gauge: 22 → 8 AWG
 - Series: RK
 - Termination Method: Screw
 - Cable CSA: 0.2 → 10 mm²
 - Current Rating: 65 A
 - Voltage Rating: 800 V
 - Minimum Operating Temperature: -40 °C



815694 Brown

RS PRO BROWN DOUBLE LEVEL TERMINAL BLOCK, DOUBLE LEVEL, 0.5

- ขนาดบรรจุภัณฑ์: 10 x EA
- Colour: Brown
 - Number of Levels: Double
 - American Wire Gauge: 22 → 12 AWG
 - Series: RKD
 - Termination Method: Screw
 - Cable CSA: 0.5 → 4 mm²
 - Current Rating: 32 A
 - Voltage Rating: 500 V



815701 Brown

RS PRO BROWN DIN RAIL TERMINAL BLOCK, 0.5 → 5MM², 600 V

- ขนาดบรรจุภัณฑ์: 5 x EA
- Colour: Brown
 - American Wire Gauge: 22 → 12 AWG
 - Series: TRK
 - Termination Method: Screw
 - Cable CSA: 0.5 → 5 mm²
 - Current Rating: 15 A
 - Voltage Rating: 600 V
 - Minimum Operating Temperature: -40 °C



815723 Brown

RS PRO GREY FEED THROUGH TERMINAL BLOCK, SINGLE LEVEL,

- ขนาดบรรจุภัณฑ์: 5 x EA
- Colour: Grey
 - Number of Levels: Single
 - American Wire Gauge: 22 → 8 AWG
 - Series: WK
 - Termination Method: Screw
 - Cable CSA: 6 mm²
 - Voltage Rating: 1 kV
 - Current Rating: 41 A



3846972 Grey

RS PRO GREY FEED THROUGH TERMINAL BLOCK, SINGLE LEVEL,

- ขนาดบรรจุภัณฑ์: 5 x EA
- Colour: Grey
 - Number of Levels: Single
 - American Wire Gauge: 16 → 6 AWG
 - Series: WKN
 - Termination Method: Screw
 - Cable CSA: 10 mm²
 - Voltage Rating: 1 kV
 - Current Rating: 57 A



3846988 Grey

RS PRO GREY FEED THROUGH TERMINAL BLOCK, 12 → 4 AWG,

- ขนาดบรรจุภัณฑ์: 5 x EA
- Colour: Grey
 - Wire Size: 12 → 4 AWG
 - Number of Levels: Single
 - Series: WKN
 - Termination Method: Screw
 - Cable CSA: 16 mm²
 - Voltage Rating: 1 kV
 - Current Rating: 71 A



3846994 Grey

RS PRO GREY FEED THROUGH TERMINAL BLOCK, 0.5 → 2.5MM², 300

- ขนาดบรรจุภัณฑ์: 1 x EA
- Colour: Grey
 - Series: WS
 - Termination Method: Screw
 - Cable CSA: 0.5 → 2.5 mm²
 - Voltage Rating: 300 V
 - Current Rating: 10 A



4709593 Grey

RS PRO BLUE FEED THROUGH TERMINAL BLOCK, SINGLE LEVEL,

- ขนาดบรรจุภัณฑ์: 10 x EA
- Colour: Blue
 - Number of Levels: Single
 - American Wire Gauge: 22 → 12 AWG
 - Series: SRK
 - Termination Method: Screw
 - Cable CSA: 2.5 mm²
 - Voltage Rating: 1 kV
 - Current Rating: 24 A



7622503 Blue

RS PRO BEIGE FEED THROUGH TERMINAL BLOCK, SINGLE LEVEL,

- ขนาดบรรจุภัณฑ์: 10 x EA
- Colour: Beige
 - Number of Levels: Single
 - American Wire Gauge: 22 → 12 AWG
 - Series: SRK
 - Termination Method: Screw
 - Cable CSA: 2.5 mm²
 - Voltage Rating: 1 kV
 - Current Rating: 24 A



7622509 Beige

RS PRO BEIGE DIN RAIL TERMINAL BLOCK, SINGLE LEVEL, 4MM², 1 KV

- ขนาดบรรจุภัณฑ์: 10 x EA
- Colour: Beige
 - Number of Levels: Single
 - American Wire Gauge: 22 → 11 AWG
 - Series: SRK
 - Termination Method: Screw
 - Cable CSA: 4 mm²
 - Voltage Rating: 1 kV
 - Current Rating: 40 A



7622512 Beige

RS PRO BLUE DIN RAIL TERMINAL BLOCK, DOUBLE LEVEL, 4MM², 1 KV

- ขนาดบรรจุภัณฑ์: 10 x EA
- Colour: Blue
 - Number of Levels: Double
 - American Wire Gauge: 22 → 11 AWG
 - Series: SRK
 - Termination Method: Screw
 - Cable CSA: 4 mm²
 - Voltage Rating: 1 kV
 - Current Rating: 40 A



7622515 Blue

RS PRO BEIGE DIN RAIL TERMINAL BLOCK, DOUBLE LEVEL, 6MM², 1 KV

- ขนาดบรรจุภัณฑ์: 10 x EA
- Colour: Beige
 - Number of Levels: Double
 - American Wire Gauge: 22 → 8 AWG
 - Series: SRK
 - Termination Method: Screw
 - Cable CSA: 6 mm²
 - Voltage Rating: 1 kV
 - Current Rating: 65 A



7622519 Beige

RS PRO BEIGE DIN RAIL TERMINAL BLOCK, DOUBLE LEVEL, 10MM², 1 KV

- ขนาดบรรจุภัณฑ์: 10 x EA
- Colour: Beige
 - Number of Levels: Double
 - American Wire Gauge: 10 → 6 AWG
 - Series: SRK
 - Termination Method: Screw
 - Cable CSA: 10 mm²
 - Voltage Rating: 1 kV
 - Current Rating: 85 A



7622521 Beige

RS PRO BLUE DIN RAIL TERMINAL BLOCK, DOUBLE LEVEL, 10MM², 1 KV

- ขนาดบรรจุภัณฑ์: 10 x EA
- Colour: Blue
 - Number of Levels: Double
 - American Wire Gauge: 10 → 6 AWG
 - Series: SRK
 - Termination Method: Screw
 - Cable CSA: 10 mm²
 - Voltage Rating: 1 kV
 - Current Rating: 85 A



7622525 Blue

RS PRO BLUE DIN RAIL TERMINAL BLOCK, DOUBLE LEVEL, 6MM², 1 KV

- ขนาดบรรจุภัณฑ์: 10 x EA
- Colour: Blue
 - Number of Levels: Double
 - American Wire Gauge: 22 → 8 AWG
 - Series: SRK
 - Termination Method: Screw
 - Cable CSA: 6 mm²
 - Voltage Rating: 1 kV
 - Current Rating: 65 A



7622528 Blue

RS PRO GREEN/YELLOW EARTH TERMINAL BLOCK, SINGLE LEVEL,

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Colour: Green/Yellow
 - Number of Levels: Single
 - American Wire Gauge: 22 → 12 AWG
 - Series: SSL
 - Termination Method: Screw
 - Cable CSA: 2.5 mm²
 - Pitch: 5.1 mm
 - Minimum Operating Temperature: -40 °C


7622534 Green/Yellow

RS PRO GREEN/YELLOW EARTH TERMINAL BLOCK, SINGLE LEVEL,

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Colour: Green/Yellow
 - Number of Levels: Single
 - American Wire Gauge: 22 → 11 AWG
 - Series: SSL
 - Termination Method: Screw
 - Cable CSA: 4 mm²
 - Pitch: 6.1 mm
 - Minimum Operating Temperature: -40 °C


7622537 Green/Yellow

RS PRO GREEN/YELLOW EARTH TERMINAL BLOCK, SINGLE LEVEL,

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Colour: Green/Yellow
 - Number of Levels: Single
 - American Wire Gauge: 10 → 6 AWG
 - Series: SSL
 - Termination Method: Screw
 - Cable CSA: 10 mm²
 - Pitch: 10.1 mm
 - Minimum Operating Temperature: -40 °C


7622540 Green/Yellow

RS PRO GREY DIN RAIL TERMINAL BLOCK, SINGLE LEVEL, 2.5MM², 600 V

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Colour: Grey
 - Number of Levels: Single
 - American Wire Gauge: 20 → 12 AWG
 - Series: ZRK
 - Termination Method: Spring Clamp
 - Cable CSA: 2.5 mm²
 - Current Rating: 27 A
 - Voltage Rating: 600 V


7637404 Grey

RS PRO BLUE DIN RAIL TERMINAL BLOCK, DOUBLE LEVEL, 2.5MM², 600

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Colour: Blue
 - Number of Levels: Double
 - American Wire Gauge: 20 → 12 AWG
 - Series: ZRK
 - Termination Method: Spring Clamp
 - Cable CSA: 2.5 mm²
 - Current Rating: 27 A
 - Voltage Rating: 600 V


7637413 Blue

RS PRO BLUE DIN RAIL TERMINAL BLOCK, DOUBLE LEVEL, 2.5MM², 600

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Colour: Blue
 - Number of Levels: Double
 - American Wire Gauge: 20 → 12 AWG
 - Series: ZRK
 - Termination Method: Spring Clamp
 - Cable CSA: 2.5 mm²
 - Current Rating: 27 A
 - Voltage Rating: 600 V


7637422 Blue

RS PRO GREEN/YELLOW EARTH TERMINAL BLOCK, SINGLE LEVEL,

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Colour: Green/Yellow
 - Number of Levels: Single
 - American Wire Gauge: 20 → 12 AWG
 - Series: ZSL
 - Termination Method: Spring Clamp
 - Cable CSA: 2.5 mm²
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +120 °C


7637426 Green/Yellow

RS PRO GREY DIN RAIL TERMINAL BLOCK, DOUBLE LEVEL, 2.5MM², 600

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Colour: Grey
 - Number of Levels: Double
 - American Wire Gauge: 20 → 12 AWG
 - Series: ZRK
 - Termination Method: Spring Clamp
 - Cable CSA: 2.5 mm²
 - Current Rating: 27 A
 - Voltage Rating: 600 V


7637429 Grey

RS PRO GREY DOUBLE LEVEL TERMINAL BLOCK, DOUBLE LEVEL,

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Colour: Grey
 - Number of Levels: Double
 - American Wire Gauge: 20 → 12 AWG
 - Series: ZRKD
 - Termination Method: Spring Clamp
 - Cable CSA: 2.5 mm²
 - Current Rating: 24 A
 - Voltage Rating: 500 V


7637438 Grey

RS PRO GREY MULTI LEVEL TERMINAL BLOCK, TRIPLE LEVEL, 2.5MM², 500 V

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Colour: Grey
 - Number of Levels: Triple
 - American Wire Gauge: 20 → 12 AWG
 - Series: ZIKD
 - Termination Method: Spring Clamp
 - Cable CSA: 2.5 mm²
 - Current Rating: 24 A
 - Voltage Rating: 500 V


7637444 Grey

RS PRO GREY DIN RAIL TERMINAL BLOCK, DOUBLE LEVEL, 4MM², 600 V

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Colour: Grey
 - Number of Levels: Double
 - American Wire Gauge: 20 → 10 AWG
 - Series: ZRK
 - Termination Method: Spring Clamp
 - Cable CSA: 4 mm²
 - Current Rating: 35 A
 - Voltage Rating: 600 V


7637460 Grey

RS PRO GREEN/YELLOW EARTH TERMINAL BLOCK, SINGLE LEVEL,

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Colour: Green/Yellow
 - Number of Levels: Single
 - American Wire Gauge: 20 → 10 AWG
 - Series: ZSL
 - Termination Method: Spring Clamp
 - Cable CSA: 4 mm²
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +120 °C


7637472 Green/Yellow

RS PRO BLUE DIN RAIL TERMINAL BLOCK, DOUBLE LEVEL, 4MM², 600 V

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Colour: Blue
 - Number of Levels: Double
 - American Wire Gauge: 20 → 10 AWG
 - Series: ZRK
 - Termination Method: Spring Clamp
 - Cable CSA: 4 mm²
 - Current Rating: 35 A
 - Voltage Rating: 600 V


7637479 Blue

RS PRO GREY DIN RAIL TERMINAL BLOCK, DOUBLE LEVEL, 4MM², 600 V

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Colour: Grey
 - Number of Levels: Double
 - American Wire Gauge: 20 → 10 AWG
 - Series: ZRK
 - Termination Method: Spring Clamp
 - Cable CSA: 4 mm²
 - Current Rating: 35 A
 - Voltage Rating: 600 V


7637485 Grey

RS PRO GREEN/YELLOW EARTH TERMINAL BLOCK, SINGLE LEVEL,

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Colour: Green/Yellow
 - Number of Levels: Single
 - American Wire Gauge: 22 → 8 AWG
 - Series: ZSL
 - Termination Method: Spring Clamp
 - Cable CSA: 6 mm²
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +120 °C


7637514 Green/Yellow

RS PRO BEIGE FEED THROUGH TERMINAL BLOCK, SINGLE LEVEL, 1 KV

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Colour: Beige
 - Number of Levels: Single
 - American Wire Gauge: 16 → 4 AWG
 - Series: 17124.2
 - Termination Method: Screw
 - Current Rating: 101 (IEC) A, 85 (CSA) A, 85 (UL) A
 - Voltage Rating: 1 kV
 - Minimum Operating Temperature: -40 °C


8724688 Beige

RS PRO GREEN, YELLOW EARTH TERMINAL BLOCK, SINGLE LEVEL

- ขนาดบรรจุภัณฑ์: 1 x EA
- Colour: Green, Yellow
 - Number of Levels: Single
 - American Wire Gauge: 16 → 4 AWG
 - Series: 17130.2
 - Termination Method: Screw
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +120 °C



8724690 Green, Yellow

RS PRO BEIGE FEED THROUGH TERMINAL BLOCK, SINGLE LEVEL, 1 kV

- ขนาดบรรจุภัณฑ์: 1 x EA
- Colour: Beige
 - Number of Levels: Single
 - American Wire Gauge: 16 → 1/0 AWG
 - Series: 17140.2
 - Termination Method: Screw
 - Current Rating: 150 (CSA) A, 150 (IEC) A, 150 (UL) A
 - Voltage Rating: 1 kV
 - Minimum Operating Temperature: -40 °C



8724694 Beige

RS PRO BLUE FEED THROUGH TERMINAL BLOCK, SINGLE LEVEL, 1 kV

- ขนาดบรรจุภัณฑ์: 5 x EA
- Colour: Blue
 - Number of Levels: Single
 - American Wire Gauge: 16 → 4 AWG
 - Series: 17124.5
 - Termination Method: Screw
 - Current Rating: 101 (IEC) A, 85 (CSA) A, 85 (UL) A
 - Voltage Rating: 1 kV
 - Minimum Operating Temperature: -40 °C



8724697 Blue

RS PRO GREEN, YELLOW EARTH TERMINAL BLOCK, DOUBLE LEVEL

- ขนาดบรรจุภัณฑ์: 1 x EA
- Colour: Green, Yellow
 - Number of Levels: Double
 - American Wire Gauge: 8 → 0 AWG
 - Series: 17158.2
 - Termination Method: Screw
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +120 °C



8724701 Green, Yellow

RS PRO GREEN, YELLOW EARTH TERMINAL BLOCK, SINGLE LEVEL

- ขนาดบรรจุภัณฑ์: 1 x EA
- Colour: Green, Yellow
 - Number of Levels: Single
 - American Wire Gauge: 16 → 1/0 AWG
 - Series: 17145.2
 - Termination Method: Screw
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +120 °C



8724704 Green, Yellow

RS PRO BEIGE FEED THROUGH TERMINAL BLOCK, DOUBLE LEVEL, 1

- ขนาดบรรจุภัณฑ์: 1 x EA
- Colour: Beige
 - Number of Levels: Double
 - American Wire Gauge: 4 → 0 AWG
 - Series: 17165.2
 - Termination Method: Screw
 - Current Rating: 220 (CSA) A, 228 (UL) A, 290 (IEC) A
 - Voltage Rating: 1 kV
 - Minimum Operating Temperature: -40 °C



8724717 Beige

RS PRO GREEN, YELLOW EARTH TERMINAL BLOCK, DOUBLE LEVEL

- ขนาดบรรจุภัณฑ์: 1 x EA
- Colour: Green, Yellow
 - Number of Levels: Double
 - American Wire Gauge: 30 → 12 AWG
 - Series: 17182.2
 - Termination Method: Screw
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +120 °C



8724791 Green, Yellow

RS PRO BEIGE FEED THROUGH TERMINAL BLOCK, DOUBLE LEVEL, 1

- ขนาดบรรจุภัณฑ์: 5 x EA
- Colour: Beige
 - Number of Levels: Double
 - American Wire Gauge: 30 → 12 AWG
 - Series: 17180.2
 - Termination Method: Screw
 - Current Rating: 20 (CSA) A, 20 (UL) A, 32 (IEC) A
 - Voltage Rating: 1 kV
 - Minimum Operating Temperature: -40 °C



8724798 Beige

RS PRO BEIGE STUD TERMINAL, DOUBLE LEVEL, 1 kV

- ขนาดบรรจุภัณฑ์: 1 x EA
- Colour: Beige
 - Number of Levels: Double
 - American Wire Gauge: 14 → 2 AWG
 - Series: 17170.2
 - Termination Method: Bolt
 - Current Rating: 115 (UL) A, 125 (IEC) A, 130 (CSA) A
 - Voltage Rating: 1 kV
 - Minimum Operating Temperature: -40 °C



8724824 Beige

RS PRO BLACK DISCONNECT TERMINAL BLOCK, SINGLE LEVEL, 600

- ขนาดบรรจุภัณฑ์: 1 x EA
- Colour: Black
 - Number of Levels: Single
 - American Wire Gauge: 22 → 11 AWG
 - Series: 17150.4
 - Termination Method: Screw
 - Current Rating: 10 (IEC) A, 16 (cUL) A, 16 (UL) A
 - Voltage Rating: 600 V
 - Minimum Operating Temperature: -40 °C



8724827 Black

RS PRO BEIGE STUD TERMINAL, DOUBLE LEVEL, 1 kV

- ขนาดบรรจุภัณฑ์: 1 x EA
- Colour: Beige
 - Number of Levels: Double
 - American Wire Gauge: 10 AWG
 - Series: 17024.2
 - Termination Method: Bolt
 - Current Rating: 353 (IEC) A, 360 (CSA) A, 380 (UL) A
 - Voltage Rating: 1 kV
 - Minimum Operating Temperature: -40 °C



8724830 Beige

RS PRO BEIGE STUD TERMINAL, DOUBLE LEVEL, 1 kV

- ขนาดบรรจุภัณฑ์: 1 x EA
- Colour: Beige
 - Number of Levels: Double
 - American Wire Gauge: 14 → 0 AWG
 - Series: 17035.2
 - Termination Method: Bolt
 - Current Rating: 20 (CSA) A, 175 (UL) A, 192 (IEC) A
 - Voltage Rating: 1 kV
 - Minimum Operating Temperature: -40 °C



8724833 Beige

RS PRO BEIGE STUD TERMINAL, DOUBLE LEVEL, 1 kV

- ขนาดบรรจุภัณฑ์: 1 x EA
- Colour: Beige
 - Number of Levels: Double
 - American Wire Gauge: 10 AWG
 - Series: 17023.2
 - Termination Method: Bolt
 - Current Rating: 269 (IEC) A, 310 (CSA) A, 310 (UL) A
 - Voltage Rating: 1 kV
 - Minimum Operating Temperature: -40 °C



8724836 Beige

RS PRO GREY FEED THROUGH TERMINAL BLOCK, SINGLE LEVEL, 800

- ขนาดบรรจุภัณฑ์: 10 x EA
- Colour: Grey
 - Number of Levels: Single
 - American Wire Gauge: 22 → 12 AWG
 - Series: 1296.2
 - Termination Method: Screw
 - Current Rating: 20 (cUL) A, 20 (UL) A, 24 (IEC) A
 - Voltage Rating: 800 V
 - Minimum Operating Temperature: -40 °C



8725603 Grey

RS PRO BEIGE DOUBLE LEVEL TERMINAL BLOCK, DOUBLE LEVEL, 500

- ขนาดบรรจุภัณฑ์: 5 x EA
- Colour: Beige
 - Number of Levels: Double
 - American Wire Gauge: 22 → 14 AWG
 - Series: 1206.2
 - Termination Method: Screw
 - Current Rating: 20 (cUL) A, 20 (UL) A, 24 (IEC) A
 - Voltage Rating: 500 V
 - Minimum Operating Temperature: -40 °C



8725609 Beige

RS PRO BEIGE FEED THROUGH TERMINAL BLOCK, SINGLE LEVEL, 500

- ขนาดบรรจุภัณฑ์: 5 x EA
- Colour: Beige
 - Number of Levels: Single
 - American Wire Gauge: 22 → 10 AWG
 - Series: 1015.2
 - Termination Method: Screw
 - Current Rating: 30 (UL) A, 32 (IEC) A, 40 (CSA) A
 - Voltage Rating: 500 V
 - Minimum Operating Temperature: -40 °C



8725612 Beige

RS PRO BEIGE DISCONNECT TERMINAL BLOCK, SINGLE LEVEL,

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Colour: Beige
 - Number of Levels: Single
 - American Wire Gauge: 22 → 12 AWG
 - Series: 2190.2
 - Termination Method: Screw
 - Cable CSA: 4 mm²
 - Current Rating: 16 (UL) A, 6.3 (CSA) A, 6.3 (IEC) A
 - Voltage Rating: 600 V



8725615 Beige

RS PRO BEIGE FEED THROUGH TERMINAL BLOCK, TRIPLE LEVEL, 300

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Colour: Beige
 - Number of Levels: Triple
 - American Wire Gauge: 22 → 14 AWG
 - Series: 2268.2
 - Termination Method: Screw
 - Current Rating: 20 (CSA) A, 20 (CSAus) A, 24 (IEC) A
 - Voltage Rating: 300 V
 - Minimum Operating Temperature: -40 °C



8725619 Beige

RS PRO GREEN, YELLOW EARTH TERMINAL BLOCK, SINGLE LEVEL

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Colour: Green, Yellow
 - Number of Levels: Single
 - American Wire Gauge: 20 → 6 AWG
 - Series: 1213.2
 - Termination Method: Screw
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +105 °C



8725621 Green, Yellow

RS PRO BEIGE STUD TERMINAL, SINGLE LEVEL, 1 kV

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Colour: Beige
 - Number of Levels: Single
 - American Wire Gauge: 14 → 2 AWG
 - Series: 17001.2
 - Termination Method: Bolt
 - Current Rating: 115 (CSA) A, 115 (CSAus) A, 125 (IEC) A
 - Voltage Rating: 1 kV
 - Minimum Operating Temperature: -40 °C



8725625 Beige

RS PRO GREEN, YELLOW EARTH TERMINAL BLOCK, SINGLE LEVEL

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Colour: Green, Yellow
 - Number of Levels: Single
 - American Wire Gauge: 22 → 12 AWG
 - Series: 1056.2
 - Termination Method: Screw
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +105 °C



8725628 Green, Yellow

RS PRO DOUBLE LEVEL TERMINAL BLOCK, DOUBLE LEVEL, 2.5MM², 800

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Number of Levels: Double
 - Series: CDK 2.5
 - American Wire Gauge: 22 → 12 AWG
 - Termination Method: Screw
 - Cable CSA: 2.5 mm²
 - Current Rating: 20 (UL/CSA) A, 24 (IEC) A
 - Voltage Rating: 800 V



8787471 Double

RS PRO DOUBLE LEVEL TERMINAL BLOCK, DOUBLE LEVEL, 2.5MM², 800

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Number of Levels: Double
 - Series: CDK 2.5
 - American Wire Gauge: 22 → 12 AWG
 - Termination Method: Screw
 - Cable CSA: 2.5 mm²
 - Current Rating: 20 (UL/CSA) A, 24 (IEC) A
 - Voltage Rating: 800 V



8787480 Double

RS PRO DOUBLE LEVEL TERMINAL BLOCK, DOUBLE LEVEL, 4MM², 800 V

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Number of Levels: Double
 - Series: CDK 4
 - American Wire Gauge: 22 → 10 AWG
 - Termination Method: Screw
 - Cable CSA: 4 mm²
 - Current Rating: 30 (UL/CSA) A, 32 (IEC) A
 - Voltage Rating: 800 V



8787483 Double

RS PRO DIN RAIL TERMINAL BLOCK, SINGLE LEVEL, 2.5MM², 800 V

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Number of Levels: Single
 - Series: CDU 2.5
 - American Wire Gauge: 22 → 10 AWG
 - Termination Method: Screw
 - Cable CSA: 2.5 mm²
 - Current Rating: 24 A
 - Voltage Rating: 800 V



8787487 Single

RS PRO DIN RAIL TERMINAL BLOCK, SINGLE LEVEL, 2.5MM², 400 V

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Number of Levels: Single
 - Series: CDU 2.5
 - American Wire Gauge: 22 → 12 AWG
 - Termination Method: Screw
 - Cable CSA: 2.5 mm²
 - Current Rating: 20 (UL/CSA) A, 24 (IEC) A
 - Voltage Rating: 400 V



8787493 Single

RS PRO BLACK DIN RAIL TERMINAL BLOCK, SINGLE LEVEL, 2.5MM², 800 V

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Colour: Black
 - Number of Levels: Single
 - American Wire Gauge: 22 → 10 AWG
 - Series: CDU 2.5
 - Termination Method: Screw
 - Cable CSA: 2.5 mm²
 - Voltage Rating: 800 V
 - Current Rating: 24 A



8787496 Black

RS PRO BLUE DIN RAIL TERMINAL BLOCK, SINGLE LEVEL, 2.5MM², 800 V

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Colour: Blue
 - Number of Levels: Single
 - American Wire Gauge: 22 → 10 AWG
 - Series: CDU 2.5
 - Termination Method: Screw
 - Cable CSA: 2.5 mm²
 - Voltage Rating: 800 V
 - Current Rating: 24 A



8787499 Blue

RS PRO DIN RAIL TERMINAL BLOCK, SINGLE LEVEL, 3.5MM², 1 kV

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Number of Levels: Single
 - Series: CDU 35
 - American Wire Gauge: 10 → 2 AWG
 - Termination Method: Screw
 - Cable CSA: 3.5 mm²
 - Current Rating: 114 (UL/CSA) A, 125 (IEC) A
 - Voltage Rating: 1 kV



8787500 Single

RS PRO DIN RAIL TERMINAL BLOCK, SINGLE LEVEL, 2.5MM², 800 V

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Number of Levels: Single
 - Series: CDU 2.5
 - American Wire Gauge: 28 → 12 AWG
 - Termination Method: Screw
 - Cable CSA: 2.5 mm²
 - Current Rating: 20 (UL/CSA) A, 24 (IEC) A
 - Voltage Rating: 800 V



8787503 Single

RS PRO DIN RAIL TERMINAL BLOCK, SINGLE LEVEL, 2.5MM², 800 V

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Number of Levels: Single
 - Series: CDU 2.5
 - American Wire Gauge: 28 → 12 AWG
 - Termination Method: Screw
 - Cable CSA: 2.5 mm²
 - Current Rating: 20 (UL/CSA) A, 24 (IEC) A
 - Voltage Rating: 800 V



8787506 Single

RS PRO DIN RAIL TERMINAL BLOCK, SINGLE LEVEL, 4MM², 400 V

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Number of Levels: Single
 - Series: CDU 4
 - American Wire Gauge: 22 → 10 AWG
 - Termination Method: Screw
 - Cable CSA: 4 mm²
 - Current Rating: 30 A
 - Voltage Rating: 400 V



8787512 Single

RS PRO DIN RAIL TERMINAL BLOCK, SINGLE LEVEL, 4MM², 800 V

- ขนาดบรรจุภัณฑ์: 10 x EA
- Number of Levels: Single
 - Series: CDU 4
 - American Wire Gauge: 22 → 10 AWG
 - Termination Method: Screw
 - Cable CSA: 4 mm²
 - Current Rating: 30 (UL/CSA) A, 32 (IEC) A
 - Voltage Rating: 800 V



8787516 Single

RS PRO DIN RAIL TERMINAL BLOCK, SINGLE LEVEL, 4MM², 800 V

- ขนาดบรรจุภัณฑ์: 10 x EA
- Number of Levels: Single
 - Series: CDU 4
 - American Wire Gauge: 22 → 8 AWG
 - Termination Method: Screw
 - Cable CSA: 4 mm²
 - Current Rating: 32 (IEC) A, 35 (UL/CSA) A
 - Voltage Rating: 800 V



8787519 Single

RS PRO DIN RAIL TERMINAL BLOCK, SINGLE LEVEL, 4MM², 800 V

- ขนาดบรรจุภัณฑ์: 10 x EA
- Number of Levels: Single
 - Series: CDU 4
 - American Wire Gauge: 22 → 10 AWG
 - Termination Method: Screw
 - Cable CSA: 4 mm²
 - Current Rating: 30 (UL/CSA) A, 32 (IEC) A
 - Voltage Rating: 800 V



8787522 Single

RS PRO DIN RAIL TERMINAL BLOCK, SINGLE LEVEL, 4MM², 800 V

- ขนาดบรรจุภัณฑ์: 10 x EA
- Number of Levels: Single
 - Series: CDU 4
 - American Wire Gauge: 22 → 10 AWG
 - Termination Method: Screw
 - Cable CSA: 4 mm²
 - Current Rating: 30 (UL/CSA) A, 32 (IEC) A
 - Voltage Rating: 800 V



8787525 Single

RS PRO DIN RAIL TERMINAL BLOCK, SINGLE LEVEL, 4MM², 800 V

- ขนาดบรรจุภัณฑ์: 10 x EA
- Number of Levels: Single
 - Series: CDU 4
 - American Wire Gauge: 22 → 10 AWG
 - Termination Method: Screw
 - Cable CSA: 4 mm²
 - Current Rating: 30 (UL/CSA) A, 32 (IEC) A
 - Voltage Rating: 800 V



8787528 Single

RS PRO DIN RAIL TERMINAL BLOCK, SINGLE LEVEL, 4MM², 600 V

- ขนาดบรรจุภัณฑ์: 10 x EA
- Number of Levels: Single
 - Series: CDU 4
 - American Wire Gauge: 22 → 8 AWG
 - Termination Method: Screw
 - Cable CSA: 4 mm²
 - Current Rating: 32 (IEC) A, 35 (UL/CSA) A
 - Voltage Rating: 600 V



8787531 Single

RS PRO DIN RAIL TERMINAL BLOCK, SINGLE LEVEL, 6MM², 800 V

- ขนาดบรรจุภัณฑ์: 10 x EA
- Number of Levels: Single
 - Series: CDU 6
 - American Wire Gauge: 20 → 8 AWG
 - Termination Method: Screw
 - Cable CSA: 6 mm²
 - Current Rating: 41 (IEC) A, 50 (UL/CSA) A
 - Voltage Rating: 800 V



8787534 Single

RS PRO DIN RAIL TERMINAL BLOCK, SINGLE LEVEL, 6MM², 800 V

- ขนาดบรรจุภัณฑ์: 10 x EA
- Number of Levels: Single
 - Series: CDU 6
 - American Wire Gauge: 26 → 8 AWG
 - Termination Method: Screw
 - Cable CSA: 6 mm²
 - Current Rating: 50 (UL/CSA) A, 57 (IEC) A
 - Voltage Rating: 800 V



8787538 Single

RS PRO DIN RAIL TERMINAL BLOCK, SINGLE LEVEL, 800 V

- ขนาดบรรจุภัณฑ์: 10 x EA
- Number of Levels: Single
 - Series: CDU 6
 - American Wire Gauge: 26 → 8 AWG
 - Termination Method: Screw
 - Current Rating: 50 (UL/CSA) A, 57 (IEC) A
 - Voltage Rating: 800 V



8787547 Single

RS PRO DISCONNECT TERMINAL BLOCK, SINGLE LEVEL, 2.5MM², 600 V

- ขนาดบรรจุภัณฑ์: 10 x EA
- Number of Levels: Single
 - Series: CTR 2.5
 - American Wire Gauge: 22 → 12 AWG
 - Termination Method: Screw
 - Cable CSA: 2.5 mm²
 - Current Rating: 12 (UL/CSA) A, 15 (IEC) A
 - Voltage Rating: 600 V



8787584 Single

RS PRO DISCONNECT TERMINAL BLOCK, SINGLE LEVEL, 4MM², 800 V

- ขนาดบรรจุภัณฑ์: 5 x EA
- Number of Levels: Single
 - Series: CTR 4
 - American Wire Gauge: 22 → 10 AWG
 - Termination Method: Screw
 - Cable CSA: 4 mm²
 - Current Rating: 22 A
 - Voltage Rating: 800 V



8787588 Single

RS PRO DISCONNECT TERMINAL BLOCK, SINGLE LEVEL, 4MM², 400 V

- ขนาดบรรจุภัณฑ์: 5 x EA
- Number of Levels: Single
 - Series: CTR 4
 - American Wire Gauge: 22 → 14 AWG
 - Termination Method: Screw
 - Cable CSA: 4 mm²
 - Current Rating: 15 A
 - Voltage Rating: 400 V



8787597 Single

RS PRO GREY FUSED DIN RAIL TERMINAL, SINGLE LEVEL, 24 → 240 V

- ขนาดบรรจุภัณฑ์: 5 x EA
- Colour: Grey
 - Number of Levels: Single
 - Series: ENYA
 - Termination Method: Screw
 - Fused: Yes
 - Current Rating: 8 A
 - Voltage Rating: 24 → 240 V ac/dc
 - Minimum Operating Temperature: -25 °C



9064595 Grey

RS PRO RED DIN RAIL TERMINAL BLOCK, 2.5MM², 800 V

- ขนาดบรรจุภัณฑ์: 1 x EA
- Colour: Red
 - American Wire Gauge: 22 → 10 AWG
 - Termination Method: Screw
 - Cable CSA: 2.5 mm²
 - Voltage Rating: 800 V
 - Current Rating: 24 A



9131201 Red

RS PRO ORANGE DIN RAIL TERMINAL BLOCK, 2.5MM², 800 V

- ขนาดบรรจุภัณฑ์: 10 x EA
- Colour: Orange
 - American Wire Gauge: 22 → 10 AWG
 - Termination Method: Screw
 - Cable CSA: 2.5 mm²
 - Voltage Rating: 800 V
 - Current Rating: 24 A



9131207 Orange

RS PRO BLUE DIN RAIL TERMINAL BLOCK, 4MM², 800 V

- ขนาดบรรจุภัณฑ์: 1 x EA
- Colour: Blue
 - American Wire Gauge: 22 → 8 AWG
 - Termination Method: Screw
 - Cable CSA: 4 mm²
 - Voltage Rating: 800 V
 - Current Rating: 32 (IEC) A, 35 (CSA) A, 35 (UL) A



9131210 Blue

RS PRO BEIGE DIN RAIL TERMINAL BLOCK, 10MM², 1 KV

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Colour: Beige
 - American Wire Gauge: 16 → 6 AWG
 - Termination Method: Screw
 - Cable CSA: 10 mm²
 - Voltage Rating: 1 kV
 - Current Rating: 57 (IEC) A, 65 (CSA) A, 65 (UL) A



9131213 Beige

RS PRO BEIGE DIN RAIL TERMINAL BLOCK, 16MM², 1 KV

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Colour: Beige
 - American Wire Gauge: 14 → 4 AWG
 - Termination Method: Screw
 - Cable CSA: 16 mm²
 - Voltage Rating: 1 kV
 - Current Rating: 76 (IEC) A, 78 (CSA) A, 78 (UL) A



9131217 Beige

RS PRO BLUE DIN RAIL TERMINAL BLOCK, 2.5MM², 800 V

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Colour: Blue
 - American Wire Gauge: 28 → 12 AWG
 - Termination Method: Screw
 - Cable CSA: 2.5 mm²
 - Voltage Rating: 800 V
 - Current Rating: 20 (CSA) A, 20 (UL) A, 24 (IEC) A



9131223 Blue

RS PRO BEIGE DIN RAIL TERMINAL BLOCK, 6MM², 800 V

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Colour: Beige
 - American Wire Gauge: 20 → 8 AWG
 - Termination Method: Screw
 - Cable CSA: 6 mm²
 - Voltage Rating: 800 V
 - Current Rating: 41 (IEC) A, 50 (CSA) A, 50 (UL) A



9131226 Beige

RS PRO DIN RAIL TERMINAL BLOCK, 2.5MM², 800 V

- ขนาดบรรจุภัณฑ์: **1 x EA**
- American Wire Gauge: 22 → 10 AWG
 - Termination Method: Screw
 - Cable CSA: 2.5 mm²
 - Voltage Rating: 800 V
 - Current Rating: 24 A



9131229 22 → 10 AWG

RS PRO BEIGE DIN RAIL TERMINAL BLOCK, 2.5MM², 800 V

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Colour: Beige
 - American Wire Gauge: 24 → 4 AWG
 - Termination Method: Screw
 - Cable CSA: 2.5 mm²
 - Voltage Rating: 800 V
 - Current Rating: 65 (CSA) A, 65 (UL) A, 76 (IEC) A



9131232 Beige

RS PRO BEIGE DIN RAIL TERMINAL BLOCK, 2.5MM², 800 V

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Colour: Beige
 - American Wire Gauge: 28 → 12 AWG
 - Termination Method: Spring Clamp
 - Cable CSA: 2.5 mm²
 - Voltage Rating: 800 V
 - Current Rating: 20 (CSA) A, 20 (UL) A, 32 (IEC) A



9131235 Beige

RS PRO BEIGE DIN RAIL TERMINAL BLOCK, 2.5MM², 800 V

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Colour: Beige
 - American Wire Gauge: 28 → 12 AWG
 - Termination Method: Spring Clamp
 - Cable CSA: 2.5 mm²
 - Voltage Rating: 800 V
 - Current Rating: 18 (CSA) A, 18 (UL) A, 24 (IEC) A



9131239 Beige

RS PRO BEIGE DOUBLE LEVEL TERMINAL BLOCK, DOUBLE LEVEL,

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Colour: Beige
 - Number of Levels: Double
 - American Wire Gauge: 28 → 12 AWG
 - Termination Method: Spring Clamp
 - Cable CSA: 2.5 mm²
 - Voltage Rating: 800 V
 - Current Rating: 20 (CSA) A, 20 (UL) A, 24 (IEC) A



9131241 Beige

RS PRO BEIGE DISCONNECT TERMINAL BLOCK, 4MM², 800 V

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Colour: Beige
 - American Wire Gauge: 22 → 14 AWG
 - Termination Method: Screw
 - Cable CSA: 4 mm²
 - Voltage Rating: 800 V
 - Current Rating: 10 (IEC) A, 15 (CSA) A, 15 (UL) A



9131248 Beige

RS PRO GREY DIN RAIL TERMINAL BLOCK, 2.5MM², 800 V

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Colour: Grey
 - American Wire Gauge: 28 → 12 AWG
 - Cable CSA: 2.5 mm²
 - Voltage Rating: 800 V
 - Current Rating: 20 A (CSA), 20 A (UL), 24 A (IEC)



9131257 Grey

RS PRO BLACK FEED THROUGH TERMINAL BLOCK, 4MM², 600 V

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Colour: Black
 - American Wire Gauge: 28 → 10 AWG
 - Cable CSA: 4 mm²
 - Voltage Rating: 600 V
 - Current Rating: 10 (IEC) A, 6.3 (CSA) A, 6.3 (UL) A



9131263 Black

RS PRO GREEN/YELLOW FEED THROUGH TERMINAL BLOCK, 4MM²

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Colour: Green/Yellow
 - American Wire Gauge: 28 → 10 AWG
 - Cable CSA: 4 mm²



9131267 Green/Yellow

RS PRO GREY DOUBLE LEVEL TERMINAL BLOCK, DOUBLE LEVEL,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Colour: Grey
 - Number of Levels: Double
 - American Wire Gauge: 28 → 12 AWG
 - Cable CSA: 2.5 mm²
 - Current Rating: 20 A (IEC), 20 A (UL), 22 A (CSA)
 - Voltage Rating: 600 V



9131276 Grey

RS PRO JUMPER BAR FOR USE WITH DIN RAIL TERMINAL BLOCKS

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Accessory Type: Cross Connector
 - Series: O
 - For Use With: Terminal Block



399105 Cross Connector

RS PRO PARTITION PLATE FOR USE WITH DIN RAIL TERMINAL BLOCKS

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Accessory Type: Partition Plate
 - For Use With: DIN Rail Terminal



501746 Partition Plate

RS PRO END COVER FOR USE WITH DIN RAIL TERMINAL BLOCKS

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Accessory Type: End Plate
 - For Use With: DIN Rail Terminal



501764 End Plate

RS PRO END COVER FOR USE WITH DIN RAIL TERMINAL BLOCKS

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Accessory Type: End Plate
 - For Use With: DIN Rail Terminal



501774 End Plate

RS PRO GROUP MARKER FOR USE WITH DIN RAIL TERMINAL BLOCKS

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Accessory Type: Group Marker
 - For Use With: DIN Rail Terminal



501786 Group Marker

RS PRO JUMPER BAR FOR USE WITH DIN RAIL TERMINAL BLOCKS

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Accessory Type: Cross Connector
 - Series: Q
 - For Use With: DIN Rail Terminal



501792 Cross Connector

RS PRO END COVER FOR USE WITH DIN RAIL TERMINAL BLOCKS

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Accessory Type: End Plate
 - For Use With: DIN Rail Terminal



501796 End Plate

RS PRO END STOP FOR USE WITH DIN RAIL TERMINAL BLOCKS

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Accessory Type: End Stop
 - For Use With: DIN Rail Terminal



501847 End Stop

RS PRO END COVER FOR USE WITH FUSED TERMINAL BLOCK

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Accessory Type: End Plate
 - For Use With: Fused Terminal Block



501865 End Plate

RS PRO END STOP FOR USE WITH DIN RAIL TERMINAL BLOCKS

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Accessory Type: End Stop
 - For Use With: DIN Rail Terminal



501938 End Stop

RS PRO END STOP FOR USE WITH TOP HAT DIN RAIL

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Accessory Type: End Stop
 - For Use With: TS 35 DIN Rail



501972 End Stop

RS PRO END COVER FOR USE WITH DIN RAIL TERMINAL BLOCKS

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Accessory Type: End Plate
 - Series: AP
 - For Use With: Terminal Block



815717 End Plate

RS PRO END COVER FOR USE WITH DIN RAIL TERMINAL BLOCKS

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Accessory Type: End Plate
 - Series: AP SI
 - For Use With: Terminal Block



815745 End Plate

RS PRO JUMPER BAR FOR USE WITH DIN RAIL TERMINAL BLOCKS

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Accessory Type: 10-Pole Jumper Bar
 - Series: Q
 - For Use With: Terminal Block



815789 10-Pole Jumper

RS PRO JUMPER BAR FOR USE WITH DIN RAIL TERMINAL BLOCKS

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Accessory Type: 10-Pole Jumper Bar
 - Series: Q
 - For Use With: Terminal Block



815795 10-Pole Jumper

RS PRO JUMPER BAR FOR USE WITH DIN RAIL TERMINAL BLOCKS


- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Cross Connector
 - Series: Q
 - For Use With: Terminal Block



815802 Cross Connector

RS PRO END COVER FOR USE WITH DIN RAIL TERMINAL BLOCKS

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Accessory Type: End Plate
 - Series: AP
 - For Use With: Terminal Block



3847054 End Plate

RS PRO END COVER FOR USE WITH DIN RAIL TERMINAL BLOCKS

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Accessory Type: End Plate
 - Series: APN
 - For Use With: Terminal Block



3847060 End Plate

RS PRO END COVER FOR USE WITH DIN RAIL TERMINAL BLOCKS

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Accessory Type: End Plate
 - Series: APN
 - For Use With: Terminal Block



3847076 End Plate

RS PRO JUMPER BAR FOR USE WITH DIN RAIL TERMINAL BLOCKS

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Accessory Type: 2-Pole Jumper Bar
 - Series: SQI
 - For Use With: Terminal Block



7622543 2-Pole Jumper

RS PRO JUMPER BAR FOR USE WITH DIN RAIL TERMINAL BLOCKS

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Accessory Type: 2-Pole Jumper Bar
 - Series: SQI
 - For Use With: Terminal Block



7622587 2-Pole Jumper

RS PRO SHIELD CONNECTOR FOR USE WITH CABLE

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Accessory Type: Shield Connector
 - Series: SAB
 - For Use With: Cable



7637369 Shield Connector

RS PRO SHIELD CONNECTOR FOR USE WITH CABLE

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Accessory Type: Shield Connector
 - Series: SAB
 - For Use With: Cable



7637375 Shield Connector

RS PRO SHIELD CONNECTOR FOR USE WITH CABLE

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Accessory Type: Shield Connector
 - Series: SAB
 - For Use With: Cable



7637384 Shield Connector

RS PRO SHIELD CONNECTOR FOR USE WITH CABLE

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Accessory Type: Shield Connector
 - Series: SAB
 - For Use With: Cable



7637387 Shield Connector

RS PRO BUSBAR SUPPORT FOR USE WITH SHIELD-CONNECTION CLIP

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Accessory Type: Busbar Support
 - Series: SH
 - For Use With: Shield-Connection Clip



7637390 Busbar Support

RS PRO BUSBAR SUPPORT FOR USE WITH SHIELD-CONNECTION CLIP

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Busbar Support
 - Series: Ssch
 - For Use With: Shield-Connection Clip



7637397 Busbar Support

RS PRO CLAMPING YOKE FOR USE WITH BUSBAR

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Accessory Type: Clamping Yoke
 - Series: ZB
 - For Use With: Busbar



7637407 Clamping Yoke

RS PRO END COVER FOR USE WITH ZRK SERIES TERMINAL BLOCK, ZSL

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Accessory Type: End Plate
 - Series: ZAP
 - For Use With: ZRK Series Terminal Block, ZSL Series Terminal Block



7637435 End Plate

RS PRO JUMPER BAR FOR USE WITH ZRK TENSION SPRING CONNECTION

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Accessory Type: Cross Connector
 - Series: ZOI
 - For Use With: ZRK Tension Spring Connection System
 - Number of Poles: 2
 - Contact Dimensions: 2.5mm²



7637457 Cross Connector

RS PRO END COVER FOR USE WITH ZRK SERIES TERMINAL BLOCK, ZSL

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Accessory Type: End Plate
 - Series: ZAP
 - For Use With: ZRK Series Terminal Block, ZSL Series Terminal Block



7637491 End Plate

RS PRO JUMPER BAR FOR USE WITH ZRK TENSION SPRING CONNECTION

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Accessory Type: Cross Connector
 - Series: ZOI
 - For Use With: ZRK Tension Spring Connection System
 - Number of Poles: 2
 - Contact Dimensions: 4mm²



7637494 Cross Connector

RS PRO END STOP FOR USE WITH DIN RAIL

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Accessory Type: End Stop
 - Series: TS35
 - For Use With: DIN Rail



7637567 End Stop

RS PRO END COVER FOR USE WITH FF SERIES, RK SERIES, SERIES, SF SERIES,

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Accessory Type: End Cover
 - Series: 2001.5
 - For Use With: FF Series, RK Series, Series, SF Series, SRK Series, TSK



8724723 End Cover

RS PRO END COVER FOR USE WITH SRK SERIES

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Accessory Type: End Cover
 - Series: 2001.2
 - For Use With: SRK Series



8724726 End Cover

RS PRO END COVER FOR USE WITH SSL SERIES

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Accessory Type: End Cover
 - Series: 2001.1
 - For Use With: SSL Series



8724729 End Cover

RS PRO END COVER FOR USE WITH SRK SERIES

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Accessory Type: End Cover
 - Series: 17254.2
 - For Use With: SRK Series



8724735 End Cover

RS PRO END COVER FOR USE WITH SRK SERIES, SRKD SERIES, SSL

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Accessory Type: End Cover
 - Series: 17200.8
 - For Use With: SRK Series, SRKD Series, SSL Series, SSLD Series



8724739 End Cover

RS PRO 5 WAY PLUG IN CROSS CONNECTOR FOR USE WITH SRK

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Accessory Type: 5 Way Plug in Cross Connector
 - Series: 17204.8
 - For Use With: SRK Series, SRKD Series, SSL Series, SSLD Series



8724741 5 Way Plug in

RS PRO 10 WAY PLUG IN CROSS CONNECTOR FOR USE WITH SRK

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: 10 Way Plug in Cross Connector
 - Series: 17209.8
 - For Use With: SRK Series, SRKD Series, SSL Series, SSLD Series



8724745 10 Way Plug in

RS PRO 4 WAY PLUG IN CROSS CONNECTOR FOR USE WITH SRK

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Accessory Type: 4 Way Plug in Cross Connector
 - Series: 17213.8
 - For Use With: SRK Series, SRKD Series, SSIK Series, SSL Series, SSLD Series



8724751 4 Way Plug in

RS PRO 2 WAY PLUG IN CROSS CONNECTOR FOR USE WITH SRK

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Accessory Type: 2 Way Plug in Cross Connector
 - Series: 17211.8
 - For Use With: SRK Series, SRKD Series, SSIK Series, SSL Series, SSLD Series



8724754 2 Way Plug in

RS PRO 3 WAY PLUG IN CROSS CONNECTOR FOR USE WITH SRK

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Accessory Type: 3 Way Plug in Cross Connector
 - Series: 17212.8
 - For Use With: SRK Series, SRKD Series, SSIK Series, SSL Series, SSLD Series



8724757 3 Way Plug in

RS PRO 10 WAY PLUG IN CROSS CONNECTOR FOR USE WITH SRK

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: 10 Way Plug in Cross Connector
 - Series: 17219.8
 - For Use With: SRK Series, SRKD Series, SSIK Series, SSL Series, SSLD Series



8724760 10 Way Plug in

RS PRO 2 WAY PLUG IN CROSS CONNECTOR FOR USE WITH SRK

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Accessory Type: 2 Way Plug in Cross Connector
 - Series: 17247.8
 - For Use With: SRK Series, SSL Series



8724785 2 Way Plug in

RS PRO END COVER FOR USE WITH SRKD SERIES

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Accessory Type: End Cover
 - Series: 17292.2
 - For Use With: SRKD Series



8724814 End Cover

RS PRO TERMINAL COVER FOR USE WITH HSKG SERIES

- ขนาดบรรจุภัณฑ์: **4 x EA**
- Accessory Type: Terminal Cover
 - Series: 17268.8
 - For Use With: HSKG Series



8724846 Terminal Cover

RS PRO TERMINAL COVER FOR USE WITH HSKG SERIES

- ขนาดบรรจุภัณฑ์: **2 x EA**
- Accessory Type: Terminal Cover
 - Series: 17025.8
 - For Use With: HSKG Series



8724855 Terminal Cover

RS PRO TERMINAL COVER FOR USE WITH HSKG SERIES

- ขนาดบรรจุภัณฑ์: **2 x EA**
- Accessory Type: Terminal Cover
 - Series: 17123.8
 - For Use With: HSKG Series



8724858 Terminal Cover

RS PRO END STOP FOR USE WITH ES SERIES, RK SERIES, SRK SERIES

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Accessory Type: End Stop
 - Series: 2005.2
 - For Use With: ES Series, RK Series, SRK Series



8725637 End Stop

END PLATE FOR MINI 2.5/4/6/10MM SQ.MM


- ขนาดบรรจุภัณฑ์: **5 x EA**
- Accessory Type: End Cover
 - Series: CEP
 - For Use With: CDU



8787544 End Cover

END BRACKET FOR 2.5/4/6/10MM SQ.MM

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Accessory Type: End Stop
 - Series: CEW
 - For Use With: CDK, CDU, CPE, CTR



8787553 End Stop

SCREW END BLACKET 2.5/4/6/10MM SQ.MM

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Accessory Type: End Stop
 - Series: CEW
 - For Use With: CDK, CDU, CPE, CTR



8787556 End Stop

RS PRO JUMPER BAR FOR USE WITH SCREW CLAMP TERMINAL BLOCK

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Accessory Type: Jumper Bar
 - Series: COV
 - For Use With: Screw Clamp Terminal Block



8787572 Jumper Bar

RS PRO JUMPER BAR FOR USE WITH SCREW CLAMP TERMINAL BLOCK

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Accessory Type: Jumper Bar
 - Series: COV
 - For Use With: Screw Clamp Terminal Block



8787581 Jumper Bar

RS PRO MOUNTING FOOT

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Accessory Type: Mounting Foot



8806796 Mounting Foot

RS PRO MOUNTING FOOT

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Accessory Type: Mounting Foot



8806806 Mounting Foot

RS PRO MOUNTING FOOT

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Accessory Type: Mounting Foot



8806809 Mounting Foot

RS PRO END COVER FOR USE WITH 4 MM TERMINAL ZAP 4/3A

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Accessory Type: End Cover
 - For Use With: 4 mm Terminal ZAP 4/3A



8997810 End Cover

RS PRO END COVER FOR USE WITH 2.5 MM TERMINAL ZAP 2.5/3A

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Accessory Type: End Cover
 - For Use With: 2.5 mm Terminal ZAP 2.5/3A



8997817 End Cover

RS PRO 2 WAY PLUG IN CROSS CONNECTOR FOR USE WITH 2.5 MM

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Accessory Type: 2 Way Plug in Cross Connector
 - For Use With: 2.5 mm Spring Terminals



8997832 2 Way Plug in

RS PRO 3 WAY PLUG IN CROSS CONNECTOR FOR USE WITH 2.5 MM

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Accessory Type: 3 Way Plug in Cross Connector
 - For Use With: 2.5 mm Spring Terminals



8997836 3 Way Plug in

RS PRO END COVER FOR USE WITH 2.5 MM TRIPLE DECK TERMINAL

- ขนาดบรรจุภัณฑ์: **20 x EA**
- Accessory Type: End Cover
 - For Use With: 2.5 mm Triple Deck Terminal



8997839 End Cover

RS PRO JUMPER BAR FOR USE WITH 2.5 MM SPRING TERMINALS

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Accessory Type: Jumper Bar
 - For Use With: 2.5 mm Spring Terminals



8997845 Jumper Bar

RS PRO JUMPER BAR FOR USE WITH 4 MM SPRING TERMINAL

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Accessory Type: Jumper Bar
 - For Use With: 4 mm Spring Terminal



8997851 Jumper Bar

RS PRO END COVER FOR USE WITH RK 1.5-4 TERMINALS, RK 1.5-4/15

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Accessory Type: End Cover
 - For Use With: RK 1.5-4 Terminals, RK 1.5-4/15



9064592 End Cover

RS PRO END COVER FOR USE WITH DIN RAIL TERMINAL BLOCKS

- ขนาดบรรจุภัณฑ์: 5 x EA
 • Accessory Type: End Cover
 • For Use With: DIN Rail Terminal Blocks



9131285 End Cover

RS PRO JUMPER BAR FOR USE WITH DIN RAIL TERMINAL BLOCKS

- ขนาดบรรจุภัณฑ์: 5 x EA
 • Accessory Type: Jumper Bar
 • For Use With: DIN Rail Terminal Blocks



9131289 Jumper Bar

RS PRO END STOP FOR USE WITH DIN RAIL TERMINAL BLOCKS

- ขนาดบรรจุภัณฑ์: 5 x EA
 • Accessory Type: End Stop
 • For Use With: DIN Rail Terminal Blocks



9131291 End Stop

RS PRO END COVER FOR USE WITH DIN RAIL TERMINAL BLOCKS


- ขนาดบรรจุภัณฑ์: 5 x EA
 • Accessory Type: End Cover
 • For Use With: DIN Rail Terminal Blocks



9131295 End Cover

RS PRO END COVER FOR USE WITH DIN RAIL TERMINAL BLOCKS

- ขนาดบรรจุภัณฑ์: 5 x EA
 • Accessory Type: End Cover
 • For Use With: DIN Rail Terminal Blocks



9131298 End Cover

RS PRO COMB LINK FOR USE WITH CDK 4 TERMINAL BLOCK, CDU 4

- ขนาดบรรจุภัณฑ์: 5 x EA
 • Accessory Type: Comb Link
 • For Use With: CDK 4 Terminal Block, CDU 4 Terminal Block, CDU 4SL Terminal Block, CPE 4 Terminal Block, CTR 4 Terminal Block, CTR 4D Terminal Block



9131302 Comb Link

RS PRO COMB LINK FOR USE WITH CDK 2.5 TERMINAL BLOCK, CDU 2.5

- ขนาดบรรจุภัณฑ์: 5 x EA
 • Accessory Type: Comb Link
 • For Use With: CDK 2.5 Terminal Block, CDU 2.5 Terminal Block, CDU 2.5SL Terminal Block, CPE 2.5 Terminal Block, CTR 2.5 Terminal Block, CTR 2.5D Terminal Block



9131305 Comb Link

RS PRO JUMPER BAR FOR USE WITH DIN RAIL TERMINAL BLOCKS

- ขนาดบรรจุภัณฑ์: 5 x EA
 • Accessory Type: Jumper Bar
 • For Use With: DIN Rail Terminal Blocks



9131308 Jumper Bar

RS PRO JUMPER BAR FOR USE WITH CDK 6 TERMINAL BLOCK, CDU 6

- ขนาดบรรจุภัณฑ์: 5 x EA
 • Accessory Type: Jumper Bar
 • For Use With: CDK 6 Terminal Block, CDU 6 Terminal Block, CDU6SL Terminal Block



9131311 Jumper Bar

RS PRO JUMPER BAR FOR USE WITH CDU 35 TERMINAL BLOCK

- ขนาดบรรจุภัณฑ์: 5 x EA
 • Accessory Type: Jumper Bar
 • For Use With: CDU 35 Terminal Block



9131320 Jumper Bar

RS PRO 2-WAY EARTH TERMINAL BLOCK, 4MM², 0.2 → 4 AWG WIRE,

- ขนาดบรรจุภัณฑ์: 10 x EA
 • Wire Size: 0.2 → 4 mm²
 • Cable CSA: 4 mm²
 • Colour: Green/Yellow
 • Number of Ways: 2
 • Termination Method: Screw Down
 • Housing Material: Nylon
 • Length: 32 mm
 • Width: 7 mm



501815 0.2 → 4 mm²

RS PRO 2-WAY TOP HAT EARTH TERMINAL BLOCK, 2.5 → 25 MM² WIRE, SCREW

- ขนาดบรรจุภัณฑ์: 5 x EA
 • Earth Block Type: Top Hat
 • Wire Size: 2.5 → 25 mm²
 • Colour: Green/Yellow
 • Number of Ways: 2
 • Termination Method: Screw Down
 • Housing Material: Nylon
 • Length: 50 mm
 • Width: 12 mm



501960 Top Hat

RS PRO 2-WAY TOP HAT EARTH TERMINAL BLOCK, 4MM², 22 → 11

- ขนาดบรรจุภัณฑ์: 5 x EA
 • Earth Block Type: Top Hat
 • Wire Size: 22 → 11 AWG
 • Cable CSA: 4 mm²
 • Colour: Green/Yellow
 • Number of Ways: 2
 • Termination Method: Screw Down
 • Housing Material: Nylon
 • Length: 56 mm



815773 Top Hat

RS PRO 2-WAY EARTH TERMINAL BLOCK, 6MM², 20 → 8 AWG WIRE,

- ขนาดบรรจุภัณฑ์: 1 x EA
 • Wire Size: 20 → 8 AWG
 • Cable CSA: 6 mm²
 • Colour: Green/Yellow
 • Number of Ways: 2
 • Termination Method: Screw Down
 • Housing Material: Nylon
 • Current Rating: 41 A
 • Voltage Rating: 800 V



3847004 20 → 8 AWG

RS PRO 2-WAY EARTH TERMINAL BLOCK, 10MM², 16 → 6 AWG WIRE,

- ขนาดบรรจุภัณฑ์: 1 x EA
 • Wire Size: 16 → 6 AWG
 • Cable CSA: 10 mm²
 • Colour: Green/Yellow
 • Number of Ways: 2
 • Termination Method: Screw Down
 • Housing Material: Nylon
 • Current Rating: 57 A
 • Voltage Rating: 800 V



3847010 16 → 6 AWG

RS PRO 2-WAY EARTH TERMINAL BLOCK, 16MM², 14 → 4 AWG WIRE,

- ขนาดบรรจุภัณฑ์: 1 x EA
 • Wire Size: 14 → 4 AWG
 • Cable CSA: 16 mm²
 • Colour: Green/Yellow
 • Number of Ways: 2
 • Termination Method: Screw Down
 • Housing Material: Nylon
 • Current Rating: 76 A
 • Voltage Rating: 800 V



3847032 14 → 4 AWG

RS PRO 2-WAY EARTH TERMINAL BLOCK, 35MM², 10 → 2 AWG WIRE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Wire Size: 10 → 2 AWG
 - Cable CSA: 35 mm²
 - Colour: Green/Yellow
 - Number of Ways: 2
 - Termination Method: Screw Down
 - Housing Material: Nylon
 - Current Rating: 125 A
 - Voltage Rating: 800 V



3847048 10 → 2 AWG

RS PRO DIN RAIL EARTH BLOCK, 6MM², 22 → 8 AWG WIRE, SCREW

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Earth Block Type: DIN Rail
 - Wire Size: 22 → 8 AWG
 - Cable CSA: 6 mm²
 - Colour: Green/Yellow
 - Termination Method: Screw Down
 - Maximum Operating Temperature: +120 °C
 - Minimum Operating Temperature: -40 °C



7622531 DIN Rail

RS PRO 2-WAY DIN RAIL EARTH BLOCK, 1.5 TO 10MM², 16 → 6 AWG

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Earth Block Type: DIN Rail
 - Wire Size: 16 → 6 AWG
 - Cable CSA: 1.5 to 10 mm²
 - Colour: Green/Yellow
 - Number of Ways: 2
 - Termination Method: Screw
 - Length: 56.7 mm
 - Width: 46 mm



8787550 DIN Rail

RS PRO 2-WAY DIN RAIL EARTH BLOCK, 0.2 TO 2.5MM², 26 → 12 AWG

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Earth Block Type: DIN Rail
 - Wire Size: 26 → 12 AWG
 - Cable CSA: 0.2 to 2.5 mm²
 - Colour: Green/Yellow
 - Number of Ways: 2
 - Termination Method: Screw
 - Voltage Rating: 600 V
 - Length: 42.8 mm



8787562 DIN Rail

RS PRO 2-WAY DIN RAIL EARTH BLOCK, 0.5 TO 4MM², 26 → 10 AWG

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Earth Block Type: DIN Rail
 - Wire Size: 26 → 10 AWG
 - Cable CSA: 0.5 to 4 mm²
 - Colour: Green/Yellow
 - Number of Ways: 2
 - Termination Method: Screw
 - Length: 56.7 mm
 - Width: 46 mm



8787566 DIN Rail

RS PRO 2-WAY DIN RAIL EARTH BLOCK, 0.5 TO 2.5MM², 26 → 12 AWG

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Earth Block Type: DIN Rail
 - Wire Size: 26 → 12 AWG
 - Cable CSA: 0.5 to 2.5 mm²
 - Colour: Green/Yellow
 - Number of Ways: 2
 - Termination Method: Screw
 - Length: 56.7 mm
 - Width: 46 mm



8787569 DIN Rail

RS PRO 2-WAY DIN RAIL EARTH BLOCK, 0.2 TO 4MM², 26 → 10 AWG

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Earth Block Type: DIN Rail
 - Wire Size: 26 → 10 AWG
 - Cable CSA: 0.2 to 4 mm²
 - Colour: Green/Yellow
 - Number of Ways: 2
 - Termination Method: Screw
 - Length: 42.8 mm
 - Width: 46.3 mm



8787575 DIN Rail

RS PRO 2-WAY DIN RAIL EARTH BLOCK, 0.5 TO 6MM², 26 → 8 AWG

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Earth Block Type: DIN Rail
 - Wire Size: 26 → 8 AWG
 - Cable CSA: 0.5 to 6 mm²
 - Colour: Green/Yellow
 - Number of Ways: 2
 - Termination Method: Screw
 - Length: 57 mm
 - Width: 46 mm



8787578 DIN Rail

TERMINAL, MINIATURE, FUSE HOLDER, 15MM, SYMMETRICAL RAI

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Fuse Holder Type: Rail Mount
 - Current Rating: 16 A
 - Voltage Rating: 600 V ac
 - Rail Type: DIN 15 mm
 - Compatible Fuse Length: 20 mm
 - Compatible Fuse Sizes: 5 x 20 mm
 - Series: STK
 - Terminal Type: Screw



501809 Rail Mount

RS PRO 10-CONTACT INTERFACE MODULE, IDC CONNECTOR, DIN RAIL


- ขนาดบรรจุภัณฑ์: **1 x EA**
- Number of Contacts: 10
 - Connector Type: IDC
 - Mounting Type: DIN Rail Mount
 - Voltage Rating: 50 V
 - Current Rating: 1 A
 - Cable CSA: 4 mm²
 - Dimensions: 45 x 70 x 62 mm
 - Depth: 62 mm



403308 10

RS PRO, 20 POLE IDC CONNECTOR INTERFACE MODULE, DIN RAIL MOUNT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Number of Contacts: 20
 - Connector Type: IDC
 - Mounting Type: DIN Rail Mount
 - Voltage Rating: 50 V
 - Current Rating: 1 A
 - Cable CSA: 4 mm²
 - Dimensions: 70 x 70 x 62 mm
 - Depth: 62 mm



403314 20

RS PRO 26-CONTACT INTERFACE MODULE, IDC CONNECTOR, DIN RAIL

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Number of Contacts: 26
 - Connector Type: IDC
 - Mounting Type: DIN Rail Mount
 - Voltage Rating: 50 V
 - Current Rating: 1 A
 - Cable CSA: 4 mm²
 - Dimensions: 90 x 70 x 62 mm
 - Depth: 62 mm



403320 26

RS PRO 40-CONTACT INTERFACE MODULE, IDC CONNECTOR, DIN RAIL

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Number of Contacts: 40
 - Connector Type: IDC
 - Mounting Type: DIN Rail Mount
 - Voltage Rating: 50 V
 - Current Rating: 1 A
 - Cable CSA: 4 mm²
 - Dimensions: 115 x 70 x 62 mm
 - Depth: 62 mm



403336 40

RS PRO 50-CONTACT INTERFACE MODULE, IDC CONNECTOR, DIN RAIL

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Number of Contacts: 50
 - Connector Type: IDC
 - Mounting Type: DIN Rail Mount
 - Voltage Rating: 50 V
 - Current Rating: 1 A
 - Cable CSA: 4 mm²
 - Dimensions: 145 x 70 x 62 mm
 - Depth: 62 mm



403342 50

CONNECTOR, TERMINAL, DIN RAIL, D PLUG, 9 WAY

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Gender: Male
 - Number of Contacts: 9
 - Connector Type: D-sub
 - Mounting Type: DIN Rail Mount
 - Voltage Rating: 50 V
 - Current Rating: 1 A
 - Cable CSA: 4 mm²
 - Dimensions: 45 x 70 x 62 mm



403364 Male

RS PRO 9-CONTACT FEMALE INTERFACE MODULE, D-SUB

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Gender: Female
 - Number of Contacts: 9
 - Connector Type: D-sub
 - Mounting Type: DIN Rail Mount
 - Voltage Rating: 50 V
 - Current Rating: 1 A
 - Cable CSA: 4 mm²
 - Dimensions: 45 x 70 x 62 mm



403370 Female

RS PRO 15-CONTACT FEMALE INTERFACE MODULE, D-SUB

- ขนาดบรรจุภัณฑ์: 1 x EA
- Gender: Female
 - Number of Contacts: 15
 - Connector Type: D-sub
 - Mounting Type: DIN Rail Mount
 - Voltage Rating: 50 V
 - Current Rating: 1 A
 - Cable CSA: 4 mm²
 - Dimensions: 65 x 70 x 62 mm



403392 Female

RS PRO 37-CONTACT MALE INTERFACE MODULE, D-SUB

- ขนาดบรรจุภัณฑ์: 1 x EA
- Gender: Male
 - Number of Contacts: 37
 - Connector Type: D-sub
 - Mounting Type: DIN Rail Mount
 - Voltage Rating: 50 V
 - Current Rating: 1 A
 - Cable CSA: 4 mm²
 - Dimensions: 110 x 70 x 62 mm



403409 Male

RS PRO 37-CONTACT FEMALE INTERFACE MODULE, D-SUB

- ขนาดบรรจุภัณฑ์: 1 x EA
- Gender: Female
 - Number of Contacts: 37
 - Connector Type: D-sub
 - Mounting Type: DIN Rail Mount
 - Voltage Rating: 50 V
 - Current Rating: 1 A
 - Cable CSA: 4 mm²
 - Dimensions: 110 x 70 x 62 mm



403415 Female

RS PRO 25-CONTACT MALE INTERFACE MODULE, D-SUB

- ขนาดบรรจุภัณฑ์: 1 x EA
- Gender: Male
 - Number of Contacts: 25
 - Connector Type: D-sub
 - Mounting Type: DIN Rail Mount
 - Voltage Rating: 50 V
 - Current Rating: 1 A
 - Cable CSA: 4 mm²
 - Dimensions: 90 x 70 x 62 mm



425106 Male

RS PRO 25-CONTACT FEMALE INTERFACE MODULE, D-SUB

- ขนาดบรรจุภัณฑ์: 1 x EA
- Gender: Female
 - Number of Contacts: 25
 - Connector Type: D-sub
 - Mounting Type: DIN Rail Mount
 - Voltage Rating: 50 V
 - Current Rating: 1 A
 - Cable CSA: 4 mm²
 - Dimensions: 90 x 70 x 62 mm



425112 Female

RS PRO 14-CONTACT MALE INTERFACE MODULE, FLAT RIBBON

- ขนาดบรรจุภัณฑ์: 1 x EA
- Gender: Male
 - Wire Size: 22 → 14 AWG
 - Number of Contacts: 14
 - Connector Type: Flat Ribbon Cable
 - Mounting Type: DIN Rail Mount
 - Test Proof Voltage: 0.67 kV ac
 - Voltage Rating: 125 V ac/dc
 - Current Rating: 1 A



6659651 Male

RS PRO 16-CONTACT MALE INTERFACE MODULE, FLAT RIBBON

- ขนาดบรรจุภัณฑ์: 1 x EA
- Gender: Male
 - Wire Size: 22 → 14 AWG
 - Number of Contacts: 16
 - Connector Type: Flat Ribbon Cable
 - Mounting Type: DIN Rail Mount
 - Test Proof Voltage: 0.67 kV ac
 - Voltage Rating: 125 V ac/dc
 - Current Rating: 1 A



6659655 Male

RS PRO 10-CONTACT MALE INTERFACE MODULE, FLAT RIBBON

- ขนาดบรรจุภัณฑ์: 1 x EA
- Gender: Male
 - Wire Size: 22 → 14 AWG
 - Number of Contacts: 10
 - Connector Type: Flat Ribbon Cable
 - Mounting Type: DIN Rail Mount
 - Test Proof Voltage: 0.67 kV ac
 - Voltage Rating: 125 V ac/dc
 - Current Rating: 1 A



6659658 Male

RS PRO 34-CONTACT MALE INTERFACE MODULE, FLAT RIBBON

- ขนาดบรรจุภัณฑ์: 1 x EA
- Gender: Male
 - Wire Size: 22 → 14 AWG
 - Number of Contacts: 20
 - Connector Type: Flat Ribbon Cable
 - Mounting Type: DIN Rail Mount
 - Test Proof Voltage: 0.67 kV ac
 - Voltage Rating: 125 V ac/dc
 - Current Rating: 1 A



6659661 Male

RS PRO 20-CONTACT MALE INTERFACE MODULE, FLAT RIBBON

- ขนาดบรรจุภัณฑ์: 1 x EA
- Gender: Male
 - Wire Size: 22 → 14 AWG
 - Number of Contacts: 20
 - Connector Type: Flat Ribbon Cable
 - Mounting Type: DIN Rail Mount
 - Test Proof Voltage: 0.67 kV ac
 - Voltage Rating: 125 V ac/dc
 - Current Rating: 1 A



6659664 Male

RS PRO 50-CONTACT MALE INTERFACE MODULE, FLAT RIBBON

- ขนาดบรรจุภัณฑ์: 1 x EA
- Gender: Male
 - Wire Size: 22 → 14 AWG
 - Number of Contacts: 50
 - Connector Type: Flat Ribbon Cable
 - Mounting Type: DIN Rail Mount
 - Test Proof Voltage: 0.67 kV ac
 - Voltage Rating: 125 V ac/dc
 - Current Rating: 1 A



6659673 Male

RS PRO 15-CONTACT FEMALE INTERFACE MODULE, D-SUB

- ขนาดบรรจุภัณฑ์: 1 x EA
- Gender: Female
 - Wire Size: 22 → 14 AWG
 - Number of Contacts: 15
 - Connector Type: D-sub
 - Mounting Type: DIN Rail Mount
 - Test Proof Voltage: 0.6 kV
 - Voltage Rating: 125 V ac/dc
 - Current Rating: 1.5 A



6659683 Female

RS PRO 25-CONTACT FEMALE INTERFACE MODULE, D-SUB

- ขนาดบรรจุภัณฑ์: 1 x EA
- Gender: Female
 - Wire Size: 22 → 14 AWG
 - Number of Contacts: 25
 - Connector Type: D-sub
 - Mounting Type: DIN Rail Mount
 - Test Proof Voltage: 0.6 kV
 - Voltage Rating: 125 V ac/dc
 - Current Rating: 1.5 A



6659692 Female

RS PRO 37-CONTACT FEMALE INTERFACE MODULE, D-SUB

- ขนาดบรรจุภัณฑ์: 1 x EA
- Gender: Female
 - Wire Size: 22 → 14 AWG
 - Number of Contacts: 37
 - Connector Type: D-sub
 - Mounting Type: DIN Rail Mount
 - Test Proof Voltage: 0.6 kV
 - Voltage Rating: 125 V ac/dc
 - Current Rating: 1.5 A



6659695 Female

RS PRO 9-CONTACT MALE INTERFACE MODULE, D-SUB CONNECTOR, DIN

- ขนาดบรรจุภัณฑ์: 1 x EA
- Gender: Male
 - Wire Size: 22 → 14 AWG
 - Number of Contacts: 9
 - Connector Type: D-sub
 - Mounting Type: DIN Rail Mount
 - Test Proof Voltage: 0.6 kV
 - Voltage Rating: 125 V ac/dc
 - Current Rating: 1.5 A



6659699 Male

RS PRO 25-CONTACT MALE INTERFACE MODULE, D-SUB

- ขนาดบรรจุภัณฑ์: 1 x EA
- Gender: Male
 - Wire Size: 22 → 14 AWG
 - Number of Contacts: 25
 - Connector Type: D-sub
 - Mounting Type: DIN Rail Mount
 - Test Proof Voltage: 0.6 kV
 - Voltage Rating: 125 V ac/dc
 - Current Rating: 1.5 A



6659702 Male

RS PRO 37-CONTACT MALE INTERFACE MODULE, D-SUB

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Gender: Male
 - Wire Size: 22 → 14 AWG
 - Number of Contacts: 37
 - Connector Type: D-sub
 - Mounting Type: DIN Rail Mount
 - Test Proof Voltage: 0.6 kV
 - Voltage Rating: 125 V ac/dc
 - Current Rating: 1.5 A



6659706 Male

RS PRO 15-CONTACT MALE INTERFACE MODULE, D-SUB

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Gender: Male
 - Wire Size: 22 → 14 AWG
 - Number of Contacts: 15
 - Connector Type: D-sub
 - Mounting Type: DIN Rail Mount
 - Test Proof Voltage: 0.6 kV
 - Voltage Rating: 125 V ac/dc
 - Current Rating: 1.5 A



6659709 Male

TERMINALS,DIN RAIL,ACCESSORIES,LABELS,6MM,BLA

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Accessory Type: Marker Card
 - For Use With: DIN Rail Terminal



501623 Marker Card

RS PRO MARKER CARD FOR USE WITH DIN RAIL TERMINAL

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Accessory Type: Marker Card
 - For Use With: DIN Rail Terminal



501629 Marker Card

RS PRO MARKER CARD FOR USE WITH DIN RAIL TERMINAL

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Accessory Type: Marker Card
 - For Use With: DIN Rail Terminal



501679 Marker Card

RS PRO MARKER CARD FOR USE WITH DIN RAIL TERMINAL

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Accessory Type: Marker Card
 - For Use With: DIN Rail Terminal



501685 Marker Card

RS PRO MARKER CARD FOR USE WITH DIN RAIL TERMINAL

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Accessory Type: Marker Card
 - For Use With: DIN Rail Terminal



501689 Marker Card

RS PRO MARKER CARD FOR USE WITH DIN RAIL TERMINAL

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Accessory Type: Marker Card
 - For Use With: DIN Rail Terminal



501695 Marker Card

RS PRO MARKING TAG FOR USE WITH SCREW CLAMP TERMINAL BLOCK

- ขนาดบรรจุภัณฑ์: **2 x EA**
- Accessory Type: Marking Tag
 - For Use With: Screw Clamp Terminal Block
 - Series: W5



8787590 Marking Tag

RS PRO MARKING TAG FOR USE WITH DIN RAIL TERMINAL BLOCK

- ขนาดบรรจุภัณฑ์: **2 x EA**
- Accessory Type: Marking Tag
 - For Use With: DIN Rail Terminal Block
 - Series: W6



9131282 Marking Tag

RS PRO MARKING TAG FOR USE WITH DIN RAIL TERMINAL BLOCK

- ขนาดบรรจุภัณฑ์: **2 x EA**
- Accessory Type: Marking Tag
 - For Use With: DIN Rail Terminal Block
 - Series: W8



9131318 Marking Tag

RS PRO BRUSHED GEARED, 7.9 W, 6 → 15 V, 9 NCM, 617 RPM, 6MM SHAFT

ขนาดบรรจุภัณฑ์: 1 x EA

- Supply Voltage: 6 → 15 V dc
- DC Motor Type: Brushed Geared
- Power Rating: 7.9 W
- Output Speed: 617 rpm
- Shaft Diameter: 6 mm
- Maximum Output Torque: 915 gcm
- Gearhead Type: Spur
- Current Rating: 990 mA



420564 6 → 15 V dc

RS PRO BRUSHED GEARED, 7.9 W, 6 → 15 V, 29 NCM, 210 RPM, 6MM SHAFT

ขนาดบรรจุภัณฑ์: 1 x EA

- Supply Voltage: 6 → 15 V
- DC Motor Type: Brushed Geared
- Power Rating: 7.9 W
- Output Speed: 210 rpm
- Shaft Diameter: 6 mm
- Maximum Output Torque: 3000 gcm
- Gearhead Type: Spur
- Current Rating: 990 mA



420568 6 → 15 V

RS PRO BRUSHED GEARED, 19.35 W, 6 → 15 V, 59 NCM, 4 RPM, 6MM SHAFT

ขนาดบรรจุภัณฑ์: 1 x EA

- Supply Voltage: 6 → 15 V
- DC Motor Type: Brushed Geared
- Power Rating: 19.35 W
- Output Speed: 4 rpm
- Shaft Diameter: 6 mm
- Maximum Output Torque: 6000 gcm
- Gearhead Type: Spur
- Current Rating: 2.75 A



420570 6 → 15 V

RS PRO BRUSHED GEARED, 7.9 W, 6 → 15 V, 4 NCM, 1644 RPM, 6MM SHAFT

ขนาดบรรจุภัณฑ์: 1 x EA

- Supply Voltage: 6 → 15 V
- DC Motor Type: Brushed Geared
- Power Rating: 7.9 W
- Output Speed: 1644 rpm
- Shaft Diameter: 6 mm
- Maximum Output Torque: 381 gcm
- Gearhead Type: Spur
- Current Rating: 990 mA



420574 6 → 15 V

RS PRO BRUSHED GEARED, 19.8 W, 12 V, 59 NCM, 29 RPM, 6MM SHAFT

ขนาดบรรจุภัณฑ์: 1 x EA

- Supply Voltage: 12 V dc
- DC Motor Type: Brushed Geared
- Power Rating: 19.8 W
- Output Speed: 29 rpm
- Shaft Diameter: 6 mm
- Maximum Output Torque: 6000 gcm
- Gearhead Type: Spur
- Current Rating: 2.81 A



420586 12 V dc

RS PRO BRUSHED GEARED, 7.98 W, 12 V, 59 NCM, 116 RPM, 6MM SHAFT

ขนาดบรรจุภัณฑ์: 1 x EA

- Supply Voltage: 12 V dc
- DC Motor Type: Brushed Geared
- Power Rating: 7.98 W
- Output Speed: 116 rpm
- Shaft Diameter: 6 mm
- Maximum Output Torque: 6000 gcm
- Gearhead Type: Spur
- Current Rating: 990 mA



420596 12 V dc

RS PRO BRUSHED GEARED, 38.7 W, 12 V, 98 NCM, 43 RPM, 12MM SHAFT

ขนาดบรรจุภัณฑ์: 1 x EA

- Supply Voltage: 12 V dc
- DC Motor Type: Brushed Geared
- Power Rating: 38.7 W
- Output Speed: 43 rpm
- Shaft Diameter: 12 mm
- Maximum Output Torque: 100000 gcm
- Gearhead Type: Planetary
- Current Rating: 4.61 A



420609 12 V dc

RS PRO BRUSHED GEARED, 36.88 W, 12 V, 98 NCM, 9 RPM, 12MM SHAFT

ขนาดบรรจุภัณฑ์: 1 x EA

- Supply Voltage: 12 V dc
- DC Motor Type: Brushed Geared
- Power Rating: 36.88 W
- Output Speed: 9 rpm
- Shaft Diameter: 12 mm
- Maximum Output Torque: 100000 gcm
- Gearhead Type: Planetary
- Current Rating: 4.61 A



420615 12 V dc

RS PRO BRUSHED GEARED, 41.3 W, 12 V, 2.9 NM, 11 RPM, 8MM SHAFT

ขนาดบรรจุภัณฑ์: 1 x EA

- Supply Voltage: 12 V dc
- DC Motor Type: Brushed Geared
- Power Rating: 41.3 W
- Output Speed: 11 rpm
- Shaft Diameter: 8 mm
- Maximum Output Torque: 30000 gcm
- Gearhead Type: Planetary
- Current Rating: 5.5 A



420619 12 V dc

RS PRO BRUSHED GEARED, 41.3 W, 12 V, 2 NM, 55 RPM, 8MM SHAFT

ขนาดบรรจุภัณฑ์: 1 x EA

- Supply Voltage: 12 V dc
- DC Motor Type: Brushed Geared
- Power Rating: 41.3 W
- Output Speed: 55 rpm
- Shaft Diameter: 8 mm
- Maximum Output Torque: 20000 gcm
- Gearhead Type: Planetary
- Current Rating: 5.5 A



420621 12 V dc

RS PRO BRUSHED GEARED, 38.7 W, 12 V, 95 NCM, 1085 RPM, 12MM SHAFT

ขนาดบรรจุภัณฑ์: 1 x EA

- Supply Voltage: 12 V dc
- DC Motor Type: Brushed Geared
- Power Rating: 38.7 W
- Output Speed: 1085 rpm
- Shaft Diameter: 12 mm
- Maximum Output Torque: 9734 gcm
- Gearhead Type: Planetary
- Current Rating: 5.5 A



420625 12 V dc

RS PRO BRUSHED GEARED, 41.3 W, 12 V, 29 NCM, 1425 RPM, 8MM SHAFT

ขนาดบรรจุภัณฑ์: 1 x EA

- Supply Voltage: 12 V dc
- DC Motor Type: Brushed Geared
- Power Rating: 41.3 W
- Output Speed: 1425 rpm
- Shaft Diameter: 8 mm
- Maximum Output Torque: 3000 gcm
- Gearhead Type: Planetary
- Current Rating: 5.28 A



420631 12 V dc

RS PRO BRUSHED GEARED, 1.5 W, 12 V, 25 NCM, 29 RPM, 4MM SHAFT

ขนาดบรรจุภัณฑ์: 1 x EA

- Supply Voltage: 12 V dc
- DC Motor Type: Brushed Geared
- Power Rating: 1.5 W
- Output Speed: 29 rpm
- Shaft Diameter: 4 mm
- Maximum Output Torque: 2500 gcm
- Gearhead Type: Planetary
- Current Rating: 200 mA



420637 12 V dc

RS PRO BRUSHED GEARED, 1.31 W, 12 V, 15 NCM, 6 RPM, 4MM SHAFT

ขนาดบรรจุภัณฑ์: 1 x EA

- Supply Voltage: 12 V, 12 → 24 V dc
- DC Motor Type: Brushed Geared
- Power Rating: 1.31 W
- Output Speed: 6 rpm
- Shaft Diameter: 4 mm
- Maximum Output Torque: 1500 gcm
- Gearhead Type: Spur
- Current Rating: 190 mA



420647 12 V, 12 → 24 V dc

RS PRO BRUSHED GEARED, 19.8 W, 12 V, 20 NCM, 753 RPM, 6MM SHAFT

ขนาดบรรจุภัณฑ์: 1 x EA

- Supply Voltage: 12 V dc
- DC Motor Type: Brushed Geared
- Power Rating: 19.8 W
- Output Speed: 753 rpm
- Shaft Diameter: 6 mm
- Maximum Output Torque: 2000 gcm
- Gearhead Type: Spur
- Current Rating: 2.81 A



420665 12 V dc

RS PRO BRUSHED GEARED, 19.8 W, 12 V, 29 NCM, 256 RPM, 6MM SHAFT

ขนาดบรรจุภัณฑ์: 1 x EA

- Supply Voltage: 12 V dc
- DC Motor Type: Brushed Geared
- Power Rating: 19.8 W
- Output Speed: 256 rpm
- Shaft Diameter: 6 mm
- Maximum Output Torque: 3000 gcm
- Gearhead Type: Spur
- Current Rating: 2.81 A



420669 12 V dc

RS PRO BRUSHED GEARED, 7.92 W, 12 V, 59 NCM, 20 RPM, 6MM SHAFT


- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 12 V dc
 - DC Motor Type: Brushed Geared
 - Power Rating: 7.92 W
 - Output Speed: 20 rpm
 - Shaft Diameter: 6 mm
 - Maximum Output Torque: 6000 gcm
 - Gearhead Type: Spur
 - Current Rating: 990 mA



420671 12 V dc

RS PRO BRUSHED GEARED, 19.8 W, 12 V, 10 NCM, 2008 RPM, 6MM SHAFT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 12 V dc
 - DC Motor Type: Brushed Geared
 - Power Rating: 19.8 W
 - Output Speed: 2008 rpm
 - Shaft Diameter: 6 mm
 - Maximum Output Torque: 1000 gcm
 - Gearhead Type: Spur
 - Current Rating: 2.81 A



420675 12 V dc

RS PRO BRUSHED GEARED, 1.71 W, 3 V, 15 NCM, 7 RPM, 4MM SHAFT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 3 V dc
 - DC Motor Type: Brushed Geared
 - Power Rating: 1.71 W
 - Output Speed: 7 rpm
 - Shaft Diameter: 4 mm
 - Maximum Output Torque: 1500 gcm
 - Gearhead Type: Spur
 - Current Rating: 1.06 A



420681 3 V dc

RS PRO BRUSHED GEARED, 1.3 W, 12 V, 12 NCM, 27 RPM, 4MM SHAFT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 12 V dc
 - DC Motor Type: Brushed Geared
 - Power Rating: 1.3 W
 - Output Speed: 27 rpm
 - Shaft Diameter: 4 mm
 - Maximum Output Torque: 1200 gcm
 - Gearhead Type: Spur
 - Current Rating: 194 mA



420693 12 V dc

RS PRO BRUSHED GEARED, 19.8 W, 4.5 → 15 V, 59 NCM, 120 RPM, 6MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 4.5 V
 - DC Motor Type: Brushed Geared
 - Power Rating: 19.8 W
 - Output Speed: 120 rpm
 - Shaft Diameter: 6 mm
 - Maximum Output Torque: 6000 gcm
 - Gearhead Type: Spur
 - Current Rating: 2.81 A



420697 4.5 V

RS PRO BRUSHED GEARED, 1.5 W, 12 V, 24 MNM, 1675 RPM, 4MM SHAFT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 12 V dc
 - DC Motor Type: Brushed Geared
 - Power Rating: 1.5 W
 - Output Speed: 1675 rpm
 - Shaft Diameter: 4 mm
 - Maximum Output Torque: 246 gcm
 - Gearhead Type: Planetary
 - Current Rating: 200 mA



420700 12 V dc

RS PRO BRUSHED GEARED, 1.5 W, 12 V, 20 NCM, 76 RPM, 4MM SHAFT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 12 V dc
 - DC Motor Type: Brushed Geared
 - Power Rating: 1.5 W
 - Output Speed: 76 rpm
 - Shaft Diameter: 4 mm
 - Maximum Output Torque: 2000 gcm
 - Gearhead Type: Planetary
 - Current Rating: 200 mA



420704 12 V dc

RS PRO BRUSHED GEARED, 0.39 W, 12 V, 24 NCM, 6 RPM, 3MM SHAFT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 12 V dc
 - DC Motor Type: Brushed Geared
 - Power Rating: 0.39 W
 - Output Speed: 6 rpm
 - Shaft Diameter: 3 mm
 - Maximum Output Torque: 2400 gcm
 - Gearhead Type: Planetary
 - Current Rating: 60 mA



420710 12 V dc

RS PRO BRUSHED GEARED, 1.5 W, 12 V, 20 NCM, 108 RPM, 4MM SHAFT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 12 V dc
 - DC Motor Type: Brushed Geared
 - Power Rating: 1.5 W
 - Output Speed: 108 rpm
 - Shaft Diameter: 4 mm
 - Maximum Output Torque: 2000 gcm
 - Gearhead Type: Planetary
 - Current Rating: 200 mA



420716 12 V dc

RS PRO BRUSHED GEARED, 24 V, 40 NCM, 86 RPM, 5.5MM SHAFT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 24 V
 - DC Motor Type: Brushed Geared
 - Output Speed: 86 rpm
 - Shaft Diameter: 5.5 mm
 - Maximum Output Torque: 40 Ncm
 - Gearhead Type: Spur
 - Gear Ratio: 60:1
 - Dimensions: 40 x 40 x 68.5 mm



440536 24 V

RS PRO BRUSHLESS, 12 V, 0.019 NM, 5170 RPM, 20MM SHAFT DIAMETER

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 12 V
 - DC Motor Type: Brushless
 - Output Speed: 5170 rpm
 - Shaft Diameter: 20 mm
 - Maximum Output Torque: 0.019 Nm
 - Current Rating: 0.63A
 - Length: 14 mm



2163784 12 V

RS PRO BRUSHLESS, 12 V, 0.075 NM, 2800 RPM, 20MM SHAFT DIAMETER

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 12 V
 - DC Motor Type: Brushless
 - Output Speed: 2800 rpm
 - Shaft Diameter: 20 mm
 - Maximum Output Torque: 0.075 Nm
 - Length: 17.9 mm



2163787 12 V

RS PRO BRUSHLESS, 24 V, 0.05 NM, 4800 RPM, 25MM SHAFT DIAMETER

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 24 V
 - DC Motor Type: Brushless
 - Output Speed: 4800 rpm
 - Shaft Diameter: 25 mm
 - Maximum Output Torque: 0.05 Nm
 - Length: 20 mm



2163788 24 V

RS PRO BRUSHLESS, 24 V, 0.11 NM, 4800 RPM, 25MM SHAFT DIAMETER

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 24 V
 - DC Motor Type: Brushless
 - Output Speed: 4800 rpm
 - Shaft Diameter: 25 mm
 - Maximum Output Torque: 0.11 Nm
 - Length: 40 mm



2163789 24 V

RS PRO BRUSHLESS, 24 V, 0.21 NM, 4500 RPM, 25MM SHAFT DIAMETER

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 24 V
 - DC Motor Type: Brushless
 - Output Speed: 4500 rpm
 - Shaft Diameter: 25 mm
 - Maximum Output Torque: 0.21 Nm
 - Length: 57 mm



2163790 24 V

RS PRO BRUSHLESS, 24 V, 0.24 NM, 4800 RPM, 25MM SHAFT DIAMETER

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 24 V
 - DC Motor Type: Brushless
 - Output Speed: 4800 rpm
 - Shaft Diameter: 25 mm
 - Maximum Output Torque: 0.24 Nm
 - Length: 60 mm



2163791 24 V

RS PRO BRUSHLESS, 48 V, 0.9 NM, 3700 RPM, 20MM SHAFT DIAMETER

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 48 V
 - DC Motor Type: Brushless
 - Output Speed: 3700 rpm
 - Shaft Diameter: 20 mm
 - Maximum Output Torque: 0.9 Nm
 - Length: 38 mm



2163797 48 V

RS PRO BRUSHED, 41 W, 14.5 V, 13 NCM, 3000 RPM, 6MM SHAFT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 14.5 V dc
 - DC Motor Type: Brushed
 - Power Rating: 41 W
 - Output Speed: 3000 rpm
 - Shaft Diameter: 6 mm
 - Maximum Output Torque: 13 Ncm
 - Dimensions: 120 (Dia.) x 37.7 mm
 - Current Rating: 6.9 A



2259541 14.5 V dc

RS PRO BRUSHED, 110 W, 23.5 V, 35 NCM, 3000 RPM, 10MM SHAFT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 23.5 V dc
 - DC Motor Type: Brushed
 - Power Rating: 110 W
 - Output Speed: 3000 rpm
 - Shaft Diameter: 10 mm
 - Maximum Output Torque: 35 Ncm
 - Dimensions: 152 (Dia.) x 60 mm
 - Current Rating: 6.9 A



2259579 23.5 V dc

RS PRO BRUSHED GEARED, 2.51 W, 3 V, 5 MNM, 2 → 3700 RPM, 2MM SHAFT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 3 V, 1.5 → 3 V dc
 - DC Motor Type: Brushed Geared
 - Power Rating: 2.51 W
 - Output Speed: 4 - 3825 rpm
 - Shaft Diameter: 2 mm
 - Maximum Output Torque: 50 gcm
 - Gearhead Type: Spur
 - Current Rating: 260 mA



2389642 3 V, 1.5 → 3 V dc

RS PRO BRUSHED GEARED, 19.8 W, 12 V, 10 NCM, 1095 RPM, 6MM SHAFT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 12 V dc
 - DC Motor Type: Brushed Geared
 - Power Rating: 19.8 W
 - Output Speed: 1095 rpm
 - Shaft Diameter: 6 mm
 - Maximum Output Torque: 1000 gcm
 - Gearhead Type: Spur
 - Current Rating: 2.81 A



2389664 12 V dc

RS PRO BRUSHED GEARED, 19.8 W, 12 V, 59 NCM, 84 RPM, 6MM SHAFT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 12 V, 4.5 → 15 V dc
 - DC Motor Type: Brushed Geared
 - Power Rating: 19.8 W
 - Output Speed: 84 rpm
 - Shaft Diameter: 6 mm
 - Maximum Output Torque: 6000 gcm
 - Gearhead Type: Spur
 - Current Rating: 2.75 A



2389670 12 V, 4.5 → 15 V dc

RS PRO BRUSHED, 1.21 W, 1.5 → 3 V, 10.4 GCM, 8200 → 14000 RPM, 2MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 1.5 → 3 V dc
 - DC Motor Type: Brushed
 - Power Rating: 1.21 W
 - Output Speed: 8200 → 14000 rpm
 - Shaft Diameter: 2 mm
 - Maximum Output Torque: 10.4 gcm
 - Dimensions: 21 (Dia.) x 38 mm
 - Current Rating: 960 mA



2389692 1.5 → 3 V dc

RS PRO GEARED, 5.75 W, 6 → 15 V, 58.8 GCM, 10668 RPM, 2.31MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 6 → 15 V dc
 - DC Motor Type: Geared
 - Power Rating: 5.75 W
 - Output Speed: 10668 rpm
 - Shaft Diameter: 2.31 mm
 - Maximum Output Torque: 58.8 gcm
 - Dimensions: 27.63 (Dia.) x 32.5 mm
 - Current Rating: 770 mA



2389715 6 → 15 V dc

RS PRO GEARED, 7.98 W, 6 → 15 V, 78.4 GCM, 9869 RPM, 2.31MM SHAFT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 6 → 15 V dc
 - DC Motor Type: Geared
 - Power Rating: 7.98 W
 - Output Speed: 9869 rpm
 - Shaft Diameter: 2.31 mm
 - Maximum Output Torque: 78.4 gcm
 - Dimensions: 27.7 (Dia.) x 38 mm
 - Current Rating: 990 mA



2389737 6 → 15 V dc

RS PRO GEARED, 21.2 W, 4.5 → 15 V, 154.4 GCM, 13360 RPM, 3.18MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 4.5 → 15 V dc
 - DC Motor Type: Geared
 - Power Rating: 21.2 W
 - Output Speed: 13360 rpm
 - Shaft Diameter: 3.18 mm
 - Maximum Output Torque: 154.4 gcm
 - Dimensions: 35.8 (Dia.) x 50 mm
 - Current Rating: 2.85 A



2389759 4.5 → 15 V dc

RS PRO BRUSHED GEARED, 1.62 W, 12 → 24 V, 5 MNM, 2 → 4199 RPM, 2MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 12 → 24 V dc
 - DC Motor Type: Brushed Geared
 - Power Rating: 1.62 W
 - Output Speed: 2 - 2100 rpm
 - Shaft Diameter: 2 mm
 - Maximum Output Torque: 50 gcm
 - Gearhead Type: Spur
 - Current Rating: 300 mA



2389822 12 → 24 V dc

RS PRO BRUSHED GEARED, 1.6 W, 3 V, 5 MNM, 1 → 2300 RPM, 2MM SHAFT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 3 V dc
 - DC Motor Type: Brushed Geared
 - Power Rating: 1.6 W
 - Output Speed: 2 - 2300 rpm
 - Shaft Diameter: 2 mm
 - Maximum Output Torque: 50 gcm
 - Gearhead Type: Spur
 - Current Rating: 850 mA



2389844 3 V dc

RS PRO GEARED, 12 V, 10 NCM, 180 RPM, 5MM SHAFT DIAMETER

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 12 V dc
 - DC Motor Type: Geared
 - Output Speed: 180 rpm
 - Shaft Diameter: 5 mm
 - Maximum Output Torque: 100 mNm
 - Gearhead Type: Spur
 - Length: 57.8 mm
 - Width: 27.7 mm



2588287 12 V dc

RS PRO GEARED, 24 V, 10 NCM, 190 RPM, 5MM SHAFT DIAMETER

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 24 V dc
 - DC Motor Type: Geared
 - Output Speed: 190 rpm
 - Shaft Diameter: 5 mm
 - Maximum Output Torque: 100 mNm
 - Gearhead Type: Spur
 - Length: 57.8 mm
 - Width: 27.7 mm



2588293 24 V dc

RS PRO GEARED, 12 V, 20 NCM, 70 RPM, 5MM SHAFT DIAMETER

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 12 V dc
 - DC Motor Type: Geared
 - Output Speed: 70 rpm
 - Shaft Diameter: 5 mm
 - Maximum Output Torque: 200 mNm
 - Gearhead Type: Spur
 - Length: 57.8 mm
 - Width: 27.7 mm



2588300 12 V dc

RS PRO GEARED, 24 V, 20 NCM, 75 RPM, 5MM SHAFT DIAMETER

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 24 V dc
 - DC Motor Type: Geared
 - Output Speed: 75 rpm
 - Shaft Diameter: 5 mm
 - Maximum Output Torque: 200 mNm
 - Gearhead Type: Spur
 - Length: 57.8 mm
 - Width: 27.7 mm



2588316 24 V dc

RS PRO GEARED, 12 V, 30 NCM, 29 RPM, 5MM SHAFT DIAMETER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 12 V dc
 - DC Motor Type: Geared
 - Output Speed: 29 rpm
 - Shaft Diameter: 5 mm
 - Maximum Output Torque: 300 mNm
 - Gearhead Type: Spur
 - Length: 62.3 mm
 - Width: 27.7 mm



2588322 12 V dc

RS PRO GEARED, 24 V, 30 NCM, 30 RPM, 5MM SHAFT DIAMETER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 24 V dc
 - DC Motor Type: Geared
 - Output Speed: 30 rpm
 - Shaft Diameter: 5 mm
 - Maximum Output Torque: 300 mNm
 - Gearhead Type: Spur
 - Length: 62.3 mm
 - Width: 27.7 mm



2588344 24 V dc

RS PRO GEARED, 12 V, 30 NCM, 11 RPM, 5MM SHAFT DIAMETER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 12 V dc
 - DC Motor Type: Geared
 - Output Speed: 11 rpm
 - Shaft Diameter: 5 mm
 - Maximum Output Torque: 300 mNm
 - Gearhead Type: Spur
 - Length: 62.3 mm
 - Width: 27.7 mm



2588350 12 V dc

RS PRO GEARED, 24 V, 30 NCM, 12 RPM, 5MM SHAFT DIAMETER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 24 V dc
 - DC Motor Type: Geared
 - Output Speed: 12 rpm
 - Shaft Diameter: 5 mm
 - Maximum Output Torque: 300 mNm
 - Gearhead Type: Spur
 - Length: 62.3 mm
 - Width: 27.7 mm



2588366 24 V dc

RS PRO GEARED, 12 V, 30 NCM, 5 RPM, 5MM SHAFT DIAMETER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 12 V dc
 - DC Motor Type: Geared
 - Output Speed: 5 rpm
 - Shaft Diameter: 5 mm
 - Maximum Output Torque: 300 mNm
 - Gearhead Type: Spur
 - Length: 66.8 mm
 - Width: 27.7 mm



2588372 12 V dc

RS PRO GEARED, 24 V, 30 NCM, 5 RPM, 5MM SHAFT DIAMETER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 24 V dc
 - DC Motor Type: Geared
 - Output Speed: 5 rpm
 - Shaft Diameter: 5 mm
 - Maximum Output Torque: 300 mNm
 - Gearhead Type: Spur
 - Length: 66.8 mm
 - Width: 27.7 mm



2588388 24 V dc

RS PRO BRUSHED GEARED, 19.8 W, 12 V, 29 NCM, 241 RPM, 6MM SHAFT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 12 V dc
 - DC Motor Type: Brushed Geared
 - Power Rating: 19.8 W
 - Output Speed: 241 rpm
 - Shaft Diameter: 6 mm
 - Maximum Output Torque: 3000 gcm
 - Current Rating: 2.75 A



3213164 12 V dc

RS PRO BRUSHED GEARED, 19.8 W, 12 V, 59 NCM, 15 RPM, 6MM SHAFT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 12 V dc
 - DC Motor Type: Brushed Geared
 - Power Rating: 19.8 W
 - Output Speed: 15 rpm
 - Shaft Diameter: 6 mm
 - Maximum Output Torque: 6000 gcm
 - Gearhead Type: Spur
 - Current Rating: 2.75 A



3213170 12 V dc

RS PRO, 36.88 W, 12 V, 82.08 GCM, 4289 RPM, 6.35MM SHAFT DIAMETER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 12 V dc
 - Power Rating: 36.88 W
 - Output Speed: 4289 rpm
 - Shaft Diameter: 6.35 mm
 - Maximum Output Torque: 82.08 gcm
 - Dimensions: 51.8 (Dia.) x 69 mm
 - Current Rating: 5.28 A
 - Length: 69 mm



3213186 12 V dc

RS PRO BRUSHED GEARED, 13.2 W, 24 V, 75 NCM, 1260 RPM, 6MM SHAFT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 24 V dc
 - DC Motor Type: Brushed Geared
 - Power Rating: 13.2 W
 - Output Speed: 1260 rpm
 - Shaft Diameter: 6 mm
 - Maximum Output Torque: 0.75 Nm
 - Gearhead Type: Planetary
 - Current Rating: 850 mA



3989776 24 V dc

RS PRO BRUSHED GEARED, 13.2 W, 24 V, 13 NCM, 450 RPM, 6MM SHAFT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 24 V dc
 - DC Motor Type: Brushed Geared
 - Power Rating: 13.2 W
 - Output Speed: 450 rpm
 - Shaft Diameter: 6 mm
 - Maximum Output Torque: 134 mNm
 - Gearhead Type: Planetary
 - Current Rating: 850 mA



3989782 24 V dc

RS PRO BRUSHED GEARED, 13.2 W, 24 V, 4.5 NM, 63 RPM, 6MM SHAFT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 24 V dc
 - DC Motor Type: Brushed Geared
 - Power Rating: 13.2 W
 - Output Speed: 63 rpm
 - Shaft Diameter: 6 mm
 - Maximum Output Torque: 4.5 Nm
 - Gearhead Type: Planetary
 - Current Rating: 850 mA



3989833 24 V dc

RS PRO BRUSHED GEARED, 13.2 W, 24 V, 4.5 NM, 27 RPM, 6MM SHAFT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 24 V dc
 - DC Motor Type: Brushed Geared
 - Power Rating: 13.2 W
 - Output Speed: 27 rpm
 - Shaft Diameter: 6 mm
 - Maximum Output Torque: 4.5 Nm
 - Gearhead Type: Planetary
 - Current Rating: 850 mA



3989849 24 V dc

RS PRO BRUSHED GEARED, 1.71 W, 3 V, 4 NCM, 604 RPM, 4MM SHAFT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 3 V dc
 - DC Motor Type: Brushed Geared
 - Power Rating: 1.71 W
 - Output Speed: 604 rpm
 - Shaft Diameter: 4 mm
 - Maximum Output Torque: 400 gcm
 - Gearhead Type: Spur
 - Current Rating: 1.06 A



4130587 3 V dc

RS PRO BRUSHED GEARED, 1.71 W, 3 V, 6 NCM, 240 RPM, 4MM SHAFT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 3 V dc
 - DC Motor Type: Brushed Geared
 - Power Rating: 1.71 W
 - Output Speed: 240 rpm
 - Shaft Diameter: 4 mm
 - Maximum Output Torque: 600 gcm
 - Gearhead Type: Spur
 - Current Rating: 1.06 A



4130593 3 V dc

RS PRO BRUSHED GEARED, 1.71 W, 3 V, 10 NCM, 72 RPM, 4MM SHAFT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 3 V dc
 - DC Motor Type: Brushed Geared
 - Power Rating: 1.71 W
 - Output Speed: 72 rpm
 - Shaft Diameter: 4 mm
 - Maximum Output Torque: 1000 gcm
 - Gearhead Type: Spur
 - Current Rating: 1.06 A



4130600 3 V dc

RS PRO BRUSHED GEARED, 1.31 W, 12 V, 4 NCM, 442 RPM, 4MM SHAFT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 12 V dc
 - DC Motor Type: Brushed Geared
 - Power Rating: 1.31 W
 - Output Speed: 442 rpm
 - Shaft Diameter: 4 mm
 - Maximum Output Torque: 400 gcm
 - Gearhead Type: Spur
 - Current Rating: 190 mA



4130616 12 V dc

RS PRO BRUSHED GEARED, 1.31 W, 12 V, 10 NCM, 66 RPM, 4MM SHAFT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 12 V, 12 → 24 V dc
 - DC Motor Type: Brushed Geared
 - Power Rating: 1.31 W
 - Output Speed: 66 rpm
 - Shaft Diameter: 4 mm
 - Maximum Output Torque: 1000 gcm
 - Gearhead Type: Spur
 - Current Rating: 190 mA



4130622 12 V, 12 → 24 V dc

RS PRO BRUSHED GEARED, 1.31 W, 12 V, 59 MNM, 221 RPM, 4MM SHAFT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 12 V dc
 - DC Motor Type: Brushed Geared
 - Power Rating: 1.31 W
 - Output Speed: 221 rpm
 - Shaft Diameter: 4 mm
 - Maximum Output Torque: 600 gcm
 - Gearhead Type: Spur
 - Current Rating: 190 mA



4130638 12 V dc

RS PRO BRUSHED GEARED, 19.8 W, 12 V, 5 NCM, 4819 RPM, 6MM SHAFT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 12 V dc
 - DC Motor Type: Brushed Geared
 - Power Rating: 19.8 W
 - Output Speed: 4819 rpm
 - Shaft Diameter: 6 mm
 - Maximum Output Torque: 500 gcm
 - Gearhead Type: Spur
 - Current Rating: 2.85 A



4179633 12 V dc

RS PRO BRUSHED GEARED, 19.8 W, 12 V, 59 NCM, 4 RPM, 6MM SHAFT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 12 V dc
 - DC Motor Type: Brushed Geared
 - Power Rating: 19.8 W
 - Output Speed: 4 rpm
 - Shaft Diameter: 6 mm
 - Maximum Output Torque: 6000 gcm
 - Gearhead Type: Spur
 - Current Rating: 2.8 A



4179649 12 V dc

RS PRO BRUSHED GEARED, 7.92 W, 12 V, 13 NCM, 1974 RPM, 6MM SHAFT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 12 V dc
 - DC Motor Type: Brushed Geared
 - Power Rating: 7.92 W
 - Output Speed: 1974 rpm
 - Shaft Diameter: 6 mm
 - Maximum Output Torque: 1284 gcm
 - Gearhead Type: Planetary
 - Current Rating: 990 mA



4179655 12 V dc

RS PRO BRUSHED GEARED, 7.92 W, 12 V, 98 NCM, 99 RPM, 6MM SHAFT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 12 V dc
 - DC Motor Type: Brushed Geared
 - Power Rating: 7.92 W
 - Output Speed: 99 rpm
 - Shaft Diameter: 6 mm
 - Maximum Output Torque: 10000 gcm
 - Gearhead Type: Planetary
 - Current Rating: 990 mA



4179661 12 V dc

RS PRO BRUSHED GEARED, 7.92 W, 12 V, 98 NCM, 19 RPM, 6MM SHAFT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 12 V dc
 - DC Motor Type: Brushed Geared
 - Power Rating: 7.92 W
 - Output Speed: 19 rpm
 - Shaft Diameter: 6 mm
 - Maximum Output Torque: 10000 gcm
 - Gearhead Type: Planetary
 - Current Rating: 990 mA



4179677 12 V dc

RS PRO BRUSHED GEARED, 0.394 W, 12 V, 7 MNM, 1550 RPM, 3MM SHAFT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 12 V dc
 - DC Motor Type: Brushed Geared
 - Power Rating: 0.394 W
 - Output Speed: 1550 rpm
 - Shaft Diameter: 3 mm
 - Maximum Output Torque: 68 gcm
 - Gearhead Type: Planetary
 - Current Rating: 85 mA



4179683 12 V dc

RS PRO BRUSHED GEARED, 0.394 W, 12 V, 8 NCM, 100 RPM, 3MM SHAFT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 12 V dc
 - DC Motor Type: Brushed Geared
 - Power Rating: 0.394 W
 - Output Speed: 100 rpm
 - Shaft Diameter: 3 mm
 - Maximum Output Torque: 794 gcm
 - Gearhead Type: Planetary
 - Current Rating: 85 mA



4179706 12 V dc

RS PRO BRUSHED GEARED, 0.394 W, 12 V, 20 NCM, 27 RPM, 3MM SHAFT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 12 V dc
 - DC Motor Type: Brushed Geared
 - Power Rating: 0.394 W
 - Output Speed: 27 rpm
 - Shaft Diameter: 3 mm
 - Maximum Output Torque: 2000 gcm
 - Gearhead Type: Planetary
 - Current Rating: 85 mA



4179712 12 V dc

RS PRO BRUSHED GEARED, 7.92 W, 12 V, 5 NCM, 3948 RPM, 6MM SHAFT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 12 V dc
 - DC Motor Type: Brushed Geared
 - Power Rating: 7.92 W
 - Output Speed: 3948 rpm
 - Shaft Diameter: 6 mm
 - Maximum Output Torque: 520 gcm
 - Gearhead Type: Spur
 - Current Rating: 990 mA



4540798 12 V dc

RS PRO BRUSHED GEARED, 7.92 W, 12 V, 10 NCM, 1645 RPM, 6MM SHAFT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 12 V dc
 - DC Motor Type: Brushed Geared
 - Power Rating: 7.92 W
 - Output Speed: 1645 rpm
 - Shaft Diameter: 6 mm
 - Maximum Output Torque: 1000 gcm
 - Gearhead Type: Spur
 - Current Rating: 990 mA



4540805 12 V dc

RS PRO BRUSHED GEARED, 7.92 W, 12 V, 10 NCM, 897 RPM, 6MM SHAFT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 12 V dc
 - DC Motor Type: Brushed Geared
 - Power Rating: 7.92 W
 - Output Speed: 897 rpm
 - Shaft Diameter: 6 mm
 - Maximum Output Torque: 1000 gcm
 - Gearhead Type: Spur
 - Current Rating: 990 mA



4540827 12 V dc

RS PRO BRUSHED GEARED, 7.92 W, 12 V, 29 NCM, 197 RPM, 6MM SHAFT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 12 V dc
 - DC Motor Type: Brushed Geared
 - Power Rating: 7.92 W
 - Output Speed: 197 rpm
 - Shaft Diameter: 6 mm
 - Maximum Output Torque: 3000 gcm
 - Gearhead Type: Spur
 - Current Rating: 990 mA



4540833 12 V dc

RS PRO BRUSHED GEARED, 7.92 W, 12 V, 59 NCM, 67 RPM, 6MM SHAFT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 12 V dc
 - DC Motor Type: Brushed Geared
 - Power Rating: 7.92 W
 - Output Speed: 67 rpm
 - Shaft Diameter: 6 mm
 - Maximum Output Torque: 6000 gcm
 - Gearhead Type: Spur
 - Current Rating: 990 mA



4540849 12 V dc

RS PRO BRUSHED GEARED, 7.92 W, 12 V, 59 NCM, 12 RPM, 6MM SHAFT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 12 V dc
 - DC Motor Type: Brushed Geared
 - Power Rating: 7.92 W
 - Output Speed: 12 rpm
 - Shaft Diameter: 6 mm
 - Maximum Output Torque: 6000 gcm
 - Gearhead Type: Spur
 - Current Rating: 990 mA



4540855 12 V dc

RS PRO BRUSHED GEARED, 7.92 W, 12 V, 59 NCM, 3 RPM, 6MM SHAFT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 12 V dc
 - DC Motor Type: Brushed Geared
 - Power Rating: 7.92 W
 - Output Speed: 3 rpm
 - Shaft Diameter: 6 mm
 - Maximum Output Torque: 6000 gcm
 - Gearhead Type: Spur
 - Current Rating: 990 mA



4540861 12 V dc

RS PRO BRUSHED GEARED, 19.8 W, 12 V, 20 NCM, 3090 RPM, 6MM SHAFT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 12 V dc
 - DC Motor Type: Brushed Geared
 - Power Rating: 19.8 W
 - Output Speed: 3090 rpm
 - Shaft Diameter: 6 mm
 - Maximum Output Torque: 2000 gcm
 - Gearhead Type: Planetary
 - Current Rating: 2.8 A



4540877 12 V dc

MOTOR,GEARED,4.5-15VDC,PLANETARY,EPICYCLIC,GEARHE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 12 V dc
 - DC Motor Type: Brushed Geared
 - Power Rating: 19.8 W
 - Output Speed: 120 rpm
 - Shaft Diameter: 6 mm
 - Maximum Output Torque: 10000 gcm
 - Gearhead Type: Planetary
 - Current Rating: 2.75 A



4540883 12 V dc

RS PRO BRUSHED GEARED, 19.8 W, 12 V, 1.2 NM, 24 RPM, 6MM SHAFT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 12 V dc
 - DC Motor Type: Brushed Geared
 - Power Rating: 19.8 W
 - Output Speed: 24 rpm
 - Shaft Diameter: 6 mm
 - Maximum Output Torque: 12000 gcm
 - Gearhead Type: Spur
 - Current Rating: 2.81 A



4540899 12 V dc

RS PRO BRUSHLESS, 24 V, 0.19 NM, 4000 RPM, 5MM SHAFT DIAMETER

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 24 V dc
 - DC Motor Type: Brushless
 - Output Speed: 4000 rpm
 - Shaft Diameter: 5 mm
 - Maximum Output Torque: 0.19 Nm
 - Dimensions: 41 x 42 x 42 mm
 - Current Rating: 5.4 A
 - Length: 41 mm



5366024 24 V dc

RS PRO BRUSHLESS, 24 V, 0.75 NM, 4000 RPM, 5MM SHAFT DIAMETER

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 24 V dc
 - DC Motor Type: Brushless
 - Output Speed: 4000 rpm
 - Shaft Diameter: 5 mm
 - Maximum Output Torque: 0.75 Nm
 - Dimensions: 100 x 42 x 42 mm
 - Current Rating: 20 A
 - Length: 100 mm



5366030 24 V dc

RS PRO BRUSHLESS, 36 V, 0.68 NM, 4000 RPM, 8MM SHAFT DIAMETER

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 36 V dc
 - DC Motor Type: Brushless
 - Output Speed: 4000 rpm
 - Shaft Diameter: 8 mm
 - Maximum Output Torque: 0.68 Nm
 - Dimensions: 57 (Dia.) x 74 mm
 - Current Rating: 9.8 A
 - Length: 74 mm



5366046 36 V dc

RS PRO GEARED, 11 W, 4.5 → 15 V, 206 GCM, 5216 RPM, 6MM SHAFT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 4.5 → 15 V
 - DC Motor Type: Geared
 - Power Rating: 11 W
 - Output Speed: 5216 rpm
 - Shaft Diameter: 6 mm
 - Maximum Output Torque: 206 gcm
 - Dimensions: 37 (Dia.) x 84.1 mm
 - Current Rating: 1.26 A



7521949 4.5 → 15 V

RS PRO GEARED, 11 W, 4.5 → 15 V, 6000 GCM, 12 RPM, 6MM SHAFT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 4.5 → 15 V
 - DC Motor Type: Geared
 - Power Rating: 11 W
 - Output Speed: 12 rpm
 - Shaft Diameter: 6 mm
 - Maximum Output Torque: 6000 gcm
 - Dimensions: 37 (Dia.) x 86.6 mm
 - Current Rating: 1.26 A



7521958 4.5 → 15 V

RS PRO GEARED, 7.98 W, 6 → 15 V, 78.4 GCM, 112 RPM, 6MM SHAFT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 6 → 15 V
 - DC Motor Type: Geared
 - Power Rating: 7.98 W
 - Output Speed: 112 rpm
 - Shaft Diameter: 6 mm
 - Maximum Output Torque: 78.4 gcm
 - Dimensions: 32 (Dia.) x 73.9 mm
 - Current Rating: 990 mA



7521964 6 → 15 V

RS PRO GEARED, 7.98 W, 6 → 15 V, 78.4 GCM, 41 RPM, 6MM SHAFT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 6 → 15 V
 - DC Motor Type: Geared
 - Power Rating: 7.98 W
 - Output Speed: 41 rpm
 - Shaft Diameter: 6 mm
 - Maximum Output Torque: 78.4 gcm
 - Dimensions: 32 (Dia.) x 80.5 mm
 - Current Rating: 990 mA



7521967 6 → 15 V

RS PRO BRUSHED GEARED, 0.394 W, 12 V, 16 NCM, 60 RPM, 3MM SHAFT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 12 V dc
 - DC Motor Type: Brushed Geared
 - Power Rating: 0.394 W
 - Output Speed: 60 rpm
 - Shaft Diameter: 3 mm
 - Maximum Output Torque: 1600 gcm
 - Gearhead Type: Planetary
 - Dimensions: 16 (Dia.) x 49 mm



7521970 12 V dc

RS PRO GEARED, 7 W, 4.5 → 15 V, 114 GCM, 7300 RPM, 6MM SHAFT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 4.5 → 15 V
 - DC Motor Type: Geared
 - Power Rating: 7 W
 - Output Speed: 7300 rpm
 - Shaft Diameter: 6 mm
 - Maximum Output Torque: 114 gcm
 - Dimensions: 37 (Dia.) x 76.1 mm
 - Current Rating: 840 mA



7521983 4.5 → 15 V

RS PRO GEARED, 7 W, 4.5 → 15 V, 114 GCM, 7300 RPM, 6MM SHAFT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 4.5 → 15 V
 - DC Motor Type: Geared
 - Power Rating: 7 W
 - Output Speed: 7300 rpm
 - Shaft Diameter: 6 mm
 - Maximum Output Torque: 114 gcm
 - Dimensions: 37 (Dia.) x 73.6 mm
 - Current Rating: 840 mA



7521989 4.5 → 15 V

RS PRO BRUSHED GEARED, 0.46 W, 6 V, 17 MNM, 230 RPM, 3MM SHAFT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 6 V dc
 - DC Motor Type: Brushed Geared
 - Power Rating: 0.46 W
 - Output Speed: 230 rpm
 - Shaft Diameter: 3 mm
 - Maximum Output Torque: 173 gcm
 - Gearhead Type: Spur
 - Dimensions: 29.25 x 12 x 10 mm



7521999 6 V dc

RS PRO BRUSHED GEARED, 0.46 W, 6 V, 202 G.CM, 145 RPM, 3MM SHAFT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 6 V
 - DC Motor Type: Brushed Geared
 - Power Rating: 0.46 W
 - Output Speed: 145 rpm
 - Shaft Diameter: 3 mm
 - Maximum Output Torque: 700 gcm
 - Gearhead Type: Spur
 - Dimensions: 15.1 x 12 x 10 mm



7522002 6 V

RS PRO BRUSHED, 0.58 W, 6 V, 3.9 GCM, 13500 RPM, 2.5MM SHAFT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 6 V
 - DC Motor Type: Brushed
 - Power Rating: 0.58 W
 - Output Speed: 13500 rpm
 - Shaft Diameter: 2.5 mm
 - Maximum Output Torque: 3.9 gcm
 - Dimensions: 15.1 x 12 x 10 mm
 - Current Rating: 320 mA



7522005 6 V

RS PRO BRUSHED GEARED, 19.8 W, 12 V, 29 NCM, 12048 RPM, 6MM SHAFT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 12 V
 - DC Motor Type: Brushed Geared
 - Power Rating: 19.8 W
 - Output Speed: 12048 rpm
 - Shaft Diameter: 6 mm
 - Maximum Output Torque: 29 Ncm
 - Gearhead Type: Spur
 - Current Rating: 2.85 A



8347593 12 V

RS PRO BRUSHED GEARED, 7 W, 12 V, 10 NCM, 822 RPM, 6MM SHAFT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 12 V
 - DC Motor Type: Brushed Geared
 - Power Rating: 7 W
 - Output Speed: 822 rpm
 - Shaft Diameter: 6 mm
 - Maximum Output Torque: 10 Ncm
 - Gearhead Type: Spur
 - Dimensions: 32 (Dia.) x 89.4 mm



8347603 12 V

RS PRO BRUSHED GEARED, 12.8 W, 12 V, 20 NCM, 1354 RPM, 6MM SHAFT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 12 V
 - DC Motor Type: Brushed Geared
 - Power Rating: 12.8 W
 - Output Speed: 1354 rpm
 - Shaft Diameter: 6 mm
 - Maximum Output Torque: 20 Ncm
 - Gearhead Type: Planetary
 - Dimensions: 37 (Dia.) x 112.5 mm



8347613 12 V

RS PRO BRUSHED GEARED, 7 W, 12 V, 1.2 NM, 8 RPM, 6MM SHAFT DIAMETER

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 12 V
 - DC Motor Type: Brushed Geared
 - Power Rating: 7 W
 - Output Speed: 8 rpm
 - Shaft Diameter: 6 mm
 - Maximum Output Torque: 1.2 Nm
 - Gearhead Type: Planetary
 - Dimensions: 32 (Dia.) x 108.6 mm



8347616 12 V

RS PRO BRUSHED GEARED, 0.39 W, 12 V, 20 NCM, 14 RPM, 3MM SHAFT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 12 V
 - DC Motor Type: Brushed Geared
 - Power Rating: 0.39 W
 - Output Speed: 14 rpm
 - Shaft Diameter: 3 mm
 - Maximum Output Torque: 20 Ncm
 - Gearhead Type: Planetary
 - Current Rating: 85 mA



8347619 12 V

RS PRO BRUSHED GEARED, 12.8 W, 12 V, 1.2 NM, 14 RPM, 6MM SHAFT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 12 V
 - DC Motor Type: Brushed Geared
 - Power Rating: 12.8 W
 - Output Speed: 14 rpm
 - Shaft Diameter: 6 mm
 - Maximum Output Torque: 1.2 Nm
 - Gearhead Type: Planetary
 - Dimensions: 37 (Dia.) x 120 mm



8347625 12 V

RS PRO BRUSHED GEARED, 7 W, 12 V, 10 NCM, 992 RPM, 6MM SHAFT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 12 V
 - DC Motor Type: Brushed Geared
 - Power Rating: 7 W
 - Output Speed: 992 rpm
 - Shaft Diameter: 6 mm
 - Maximum Output Torque: 10 Ncm
 - Gearhead Type: Spur
 - Dimensions: 27.9 (Dia.) x 87.1 mm



8347629 12 V

RS PRO BRUSHED GEARED, 7 W, 12 V, 59 NCM, 60 RPM, 6MM SHAFT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 12 V
 - DC Motor Type: Brushed Geared
 - Power Rating: 7 W
 - Output Speed: 60 rpm
 - Shaft Diameter: 6 mm
 - Maximum Output Torque: 59 Ncm
 - Gearhead Type: Spur
 - Dimensions: 27.9 (Dia.) x 92.1 mm



8347631 12 V

RS PRO BRUSHED GEARED, 0.58 W, 3 V, 4 MNM, 1350 RPM, 3MM SHAFT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 3 V
 - DC Motor Type: Brushed Geared
 - Power Rating: 0.58 W
 - Output Speed: 1350 rpm
 - Shaft Diameter: 3 mm
 - Maximum Output Torque: 4 mNm
 - Gearhead Type: Spur
 - Dimensions: 29.25 x 10 x 12 mm



8347635 3 V

RS PRO BRUSHED GEARED, 41.3 W, 12 V, 1.8 NM, 116 RPM, 8MM SHAFT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 12 V
 - DC Motor Type: Brushed Geared
 - Power Rating: 41.3 W
 - Output Speed: 116 rpm
 - Shaft Diameter: 8 mm
 - Maximum Output Torque: 1.8 Nm
 - Gearhead Type: Planetary
 - Dimensions: 44.6 (Dia.) x 133.9 mm



8347641 12 V

RS PRO BRUSHED GEARED, 0.58 W, 3 V, 3 NCM, 137 RPM, 3MM SHAFT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 3 V
 - DC Motor Type: Brushed Geared
 - Power Rating: 0.58 W
 - Output Speed: 137 rpm
 - Shaft Diameter: 3 mm
 - Maximum Output Torque: 3 Ncm
 - Gearhead Type: Spur
 - Dimensions: 29.25 x 10 x 12 mm



8347644 3 V

RS PRO BRUSHED GEARED, 0.58 W, 3 V, 9 NCM, 45 RPM, 3MM SHAFT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 3 V
 - DC Motor Type: Brushed Geared
 - Power Rating: 0.58 W
 - Output Speed: 45 rpm
 - Shaft Diameter: 3 mm
 - Maximum Output Torque: 9 Ncm
 - Gearhead Type: Spur
 - Dimensions: 29.25 x 10 x 12 mm



8347647 3 V

RS PRO BRUSHED GEARED, 41.3 W, 12 V, 2.5 NM, 27 RPM, 8MM SHAFT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 12 V
 - DC Motor Type: Brushed Geared
 - Power Rating: 41.3 W
 - Output Speed: 27 rpm
 - Shaft Diameter: 8 mm
 - Maximum Output Torque: 2.5 Nm
 - Gearhead Type: Planetary
 - Dimensions: 44.6 (Dia.) x 140.6 mm



8347650 12 V

RS PRO BRUSHED GEARED, 7.85 W, 12 V, 1482 GCM, 431 RPM, 6MM SHAFT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 12 V
 - DC Motor Type: Brushed Geared
 - Power Rating: 7.85 W
 - Output Speed: 431 rpm
 - Shaft Diameter: 6 mm
 - Maximum Output Torque: 1482 gcm
 - Gearhead Type: Planetary
 - Dimensions: 32 (Dia.) x 67.5 mm



8347663 12 V

RS PRO BRUSHED GEARED, 7 W, 12 V, 59 NCM, 2.6RPM, 6MM SHAFT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 12 V
 - DC Motor Type: Brushed Geared
 - Power Rating: 7 W
 - Output Speed: 2.6rpm
 - Shaft Diameter: 6 mm
 - Maximum Output Torque: 59 Ncm
 - Gearhead Type: Spur
 - Dimensions: 37 (Dia.) x 83.6mm



8347666 12 V

RS PRO BRUSHED GEARED, 7.85 W, 12 V, 2399 GCM, 228 RPM, 6MM SHAFT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 12 V
 - DC Motor Type: Brushed Geared
 - Power Rating: 7.85 W
 - Output Speed: 228 rpm
 - Shaft Diameter: 6 mm
 - Maximum Output Torque: 2399 gcm
 - Gearhead Type: Planetary
 - Dimensions: 32 (Dia.) x 73.9mm



8347669 12 V

RS PRO BRUSHED GEARED, 19.8 W, 12 V, 3024 GCM, 537 RPM, 6MM SHAFT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 12 V
 - DC Motor Type: Brushed Geared
 - Power Rating: 19.8 W
 - Output Speed: 537 rpm
 - Shaft Diameter: 6 mm
 - Maximum Output Torque: 3024 gcm
 - Gearhead Type: Planetary
 - Dimensions: 35.8 (Dia.) x 82.9mm



8347672 12 V

RS PRO BRUSHED GEARED, 0.46 W, 6 V, 24 GCM, 1800 RPM, 3MM SHAFT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 6 V
 - DC Motor Type: Brushed Geared
 - Power Rating: 0.46 W
 - Output Speed: 1800 rpm
 - Shaft Diameter: 3 mm
 - Maximum Output Torque: 24 gcm
 - Gearhead Type: Spur
 - Dimensions: 24.25 x 10 x 12mm



8347675 6 V

RS PRO BRUSHED GEARED, 12.8 W, 12 V, 223 GCM, 5258 RPM, 3.175MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 12 V
 - DC Motor Type: Brushed Geared
 - Power Rating: 12.8 W
 - Output Speed: 5258 rpm
 - Shaft Diameter: 3.175 mm
 - Maximum Output Torque: 223 gcm
 - Dimensions: 37 (Dia.) x 57.1mm
 - Current Rating: 1.42 A



8347679 12 V

RS PRO BRUSHLESS, 24 V, 0.021 NM, 4600 RPM, 6.2MM SHAFT DIAMETER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 24 V
 - DC Motor Type: Brushless
 - Output Speed: 4600 rpm
 - Shaft Diameter: 6.2 mm
 - Maximum Output Torque: 0.021 Nm
 - Dimensions: 22 (Dia.) x 55.7 mm
 - Current Rating: 1.1 A
 - Length: 55.7 mm



8928757 24 V

RS PRO BRUSHLESS, 24 V, 0.25 NM, 5260 RPM, 4MM SHAFT DIAMETER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 24 V
 - DC Motor Type: Brushless
 - Output Speed: 5260 rpm
 - Shaft Diameter: 4 mm
 - Maximum Output Torque: 0.25 Nm
 - Dimensions: 42.8 (Dia.) x 42.2 mm
 - Current Rating: 7 A
 - Length: 42.2 mm



8928767 24 V

RS PRO BRUSHED GEARED, 12 V, 10 NCM, 155 RPM, 6MM SHAFT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 12 V
 - DC Motor Type: Brushed Geared
 - Output Speed: 155 rpm
 - Shaft Diameter: 6 mm
 - Maximum Output Torque: 10 Ncm
 - Gearhead Type: Spur
 - Gear Ratio: 30:1
 - Dimensions: 38 x 38 x 40 mm



9013282 12 V

RS PRO BRUSHED GEARED, 12 V, 20 MNM, 260 RPM, 6MM SHAFT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 12 V
 - DC Motor Type: Brushed Geared
 - Output Speed: 260 rpm
 - Shaft Diameter: 6 mm
 - Maximum Output Torque: 20 mNm
 - Gearhead Type: Spur
 - Gear Ratio: 18:1
 - Dimensions: 71.2 x 38 x 38 mm



9013288 12 V

RS PRO BRUSHED GEARED, 12 V, 20 NCM, 80 RPM, 6MM SHAFT DIAMETER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 12 V
 - DC Motor Type: Brushed Geared
 - Output Speed: 80 rpm
 - Shaft Diameter: 6 mm
 - Maximum Output Torque: 20 Ncm
 - Gearhead Type: Spur
 - Gear Ratio: 60:1
 - Dimensions: 73.7 x 38 x 38 mm



9013291 12 V

RS PRO BRUSHED GEARED, 12 V, 30 NCM, 47 RPM, 6MM SHAFT DIAMETER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 12 V
 - DC Motor Type: Brushed Geared
 - Output Speed: 47 rpm
 - Shaft Diameter: 6 mm
 - Maximum Output Torque: 30 Ncm
 - Gearhead Type: Spur
 - Gear Ratio: 100:1
 - Dimensions: 73.7 x 38 x 38 mm



9013294 12 V

RS PRO BRUSHED GEARED, 12 V, 600 MNM, 23 RPM, 6MM SHAFT DIAMETER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 12 V
 - DC Motor Type: Brushed Geared
 - Output Speed: 23 rpm
 - Shaft Diameter: 6 mm
 - Maximum Output Torque: 600 mNm
 - Gearhead Type: Spur
 - Gear Ratio: 200:1
 - Dimensions: 76.5 x 38 x 38 mm



9013298 12 V

RS PRO BRUSHED GEARED, 12 V, 600 MNM, 5 RPM, 6MM SHAFT DIAMETER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 12 V
 - DC Motor Type: Brushed Geared
 - Output Speed: 5 rpm
 - Shaft Diameter: 6 mm
 - Maximum Output Torque: 600 mNm
 - Gearhead Type: Spur
 - Gear Ratio: 900:1
 - Dimensions: 38 x 38 x 47.5 mm



9013301 12 V

RS PRO BRUSHED GEARED, 24 V, 70 MNM, 260 RPM, 6MM SHAFT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 24 V
 - DC Motor Type: Brushed Geared
 - Output Speed: 260 rpm
 - Shaft Diameter: 6 mm
 - Maximum Output Torque: 70 mNm
 - Gearhead Type: Spur
 - Gear Ratio: 18:1
 - Dimensions: 71.2 x 38 x 38 mm



9013305 24 V

RS PRO BRUSHED GEARED, 12 V, 600 MNM, 9 RPM, 6MM SHAFT DIAMETER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 12 V
 - DC Motor Type: Brushed Geared
 - Output Speed: 9 rpm
 - Shaft Diameter: 6 mm
 - Maximum Output Torque: 600 mNm
 - Gearhead Type: Spur
 - Gear Ratio: 500:1
 - Dimensions: 79 x 38 x 38 mm



9013308 12 V

RS PRO BRUSHED GEARED, 24 V, 30 NCM, 47 RPM, 6MM SHAFT DIAMETER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 24 V
 - DC Motor Type: Brushed Geared
 - Output Speed: 47 rpm
 - Shaft Diameter: 6 mm
 - Maximum Output Torque: 30 Ncm
 - Gearhead Type: Spur
 - Gear Ratio: 100:1
 - Dimensions: 73.7 x 38 x 38 mm



9013311 24 V

RS PRO BRUSHED GEARED, 24 V, 10 NCM, 155 RPM, 6MM SHAFT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 24 V
 - DC Motor Type: Brushed Geared
 - Output Speed: 155 rpm
 - Shaft Diameter: 6 mm
 - Maximum Output Torque: 10 Ncm
 - Gearhead Type: Spur
 - Gear Ratio: 30:1
 - Dimensions: 38 x 38 x 40 mm



9013314 24 V

RS PRO BRUSHED GEARED, 24 V, 20 NCM, 80 RPM, 6MM SHAFT DIAMETER

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 24 V
 - DC Motor Type: Brushed Geared
 - Output Speed: 80 rpm
 - Shaft Diameter: 6 mm
 - Maximum Output Torque: 20 Ncm
 - Gearhead Type: Spur
 - Gear Ratio: 60:1
 - Dimensions: 73.7 x 38 x 38 mm



9013317 24 V

RS PRO BRUSHED GEARED, 24 V, 600 MNM, 23 RPM, 6MM SHAFT DIAMETER

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 24 V
 - DC Motor Type: Brushed Geared
 - Output Speed: 23 rpm
 - Shaft Diameter: 6 mm
 - Maximum Output Torque: 600 mNm
 - Gearhead Type: Spur
 - Gear Ratio: 200:1
 - Dimensions: 107.6 x 38 x 38 mm



9013320 24 V

RS PRO BRUSHED GEARED, 24 V, 600 MNM, 9 RPM, 6MM SHAFT DIAMETER

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 24 V
 - DC Motor Type: Brushed Geared
 - Output Speed: 9 rpm
 - Shaft Diameter: 6 mm
 - Maximum Output Torque: 600 mNm
 - Gearhead Type: Spur
 - Gear Ratio: 500:1
 - Dimensions: 79 x 38 x 38 mm



9013323 24 V

RS PRO BRUSHED GEARED, 24 V, 600 MNM, 5 RPM, 6MM SHAFT DIAMETER

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 24 V
 - DC Motor Type: Brushed Geared
 - Output Speed: 5 rpm
 - Shaft Diameter: 6 mm
 - Maximum Output Torque: 600 mNm
 - Gearhead Type: Spur
 - Gear Ratio: 900:1
 - Dimensions: 38 x 38 x 47.5 mm



9013327 24 V

GEARBOX, SPUR, OVOID, PRECISION DC MOTOR, 160:1

- ขนาดบรรจุภัณฑ์: 1 x EA
- Gear Ratio: 160:1
 - Gearbox Type: Ovoid
 - Shaft Diameter: 4 mm
 - Overall Width: 50 mm



336258 160:1

GEARBOX, SPUR, OVOID, PRECISION DC MOTOR, 640:1

- ขนาดบรรจุภัณฑ์: 1 x EA
- Gear Ratio: 640:1
 - Gearbox Type: Ovoid
 - Shaft Diameter: 4 mm
 - Overall Width: 50 mm



336264 640:1

GEARBOX, SPUR, OVOID, PRECISION DC MOTOR, 1250:1

- ขนาดบรรจุภัณฑ์: 1 x EA
- Gear Ratio: 1250:1
 - Gearbox Type: Ovoid
 - Shaft Diameter: 4 mm
 - Overall Width: 50 mm



336270 1250:1

RS PRO INVERTER DRIVE, 1-PHASE IN, 0.4 KW, 230 V AC, 7.2 A

- ขนาดบรรจุภัณฑ์: 1 x EA
- Power Rating: 0.4 kW
 - Phase: 1
 - Supply Voltage: 230 V ac
 - Current Rating: 7.2 A
 - Output Frequency: 0.01 → 599 Hz
 - For Use With: AC Motors
 - Series: RS510
 - IP Rating: IP20



1223410 0.4 kW

RS PRO INVERTER DRIVE, 1-PHASE IN, 0.75 KW, 230 V AC, 11 A

- ขนาดบรรจุภัณฑ์: 1 x EA
- Power Rating: 0.75 kW
 - Phase: 1
 - Supply Voltage: 230 V ac
 - Current Rating: 11 A
 - Output Frequency: 0.01 → 599 Hz
 - For Use With: AC Motors
 - Series: RS510
 - IP Rating: IP20



1223411 0.75 kW

RS PRO INVERTER DRIVE, 1-PHASE IN, 1.5 KW, 230 V AC, 15.5 A

- ขนาดบรรจุภัณฑ์: 1 x EA
- Power Rating: 1.5 kW
 - Phase: 1
 - Supply Voltage: 230 V ac
 - Current Rating: 15.5 A
 - Output Frequency: 0.01 → 599 Hz
 - For Use With: AC Motors
 - Series: RS510
 - IP Rating: IP20



1223413 1.5 kW

RS PRO INVERTER DRIVE, 1-PHASE IN, 2.2 KW, 230 V AC, 21 A

- ขนาดบรรจุภัณฑ์: 1 x EA
- Power Rating: 2.2 kW
 - Phase: 1
 - Supply Voltage: 230 V ac
 - Current Rating: 21 A
 - Output Frequency: 0.01 → 599 Hz
 - For Use With: AC Motors
 - Series: RS510
 - IP Rating: IP20



1223414 2.2 kW

RS PRO INVERTER DRIVE, 3-PHASE IN, 0.75 KW, 380 → 480 V AC, 4.2 A

- ขนาดบรรจุภัณฑ์: 1 x EA
- Power Rating: 0.75 kW
 - Phase: 3
 - Supply Voltage: 380 → 480 V ac
 - Current Rating: 4.2 A
 - Output Frequency: 599 Hz
 - For Use With: Wide Range of Drive Applications
 - IP Rating: IP20
 - Field Bus Communication Type: BACnet, Modbus, RS485



1748216 0.75 kW

RS PRO INVERTER DRIVE, 3-PHASE IN, 1.5 KW, 380 → 480 V AC, 5.6 A

- ขนาดบรรจุภัณฑ์: 1 x EA
- Power Rating: 1.5 kW
 - Phase: 3
 - Supply Voltage: 380 → 480 V ac
 - Current Rating: 5.6 A
 - Output Frequency: 599 Hz
 - For Use With: Wide Range of Drive Applications
 - IP Rating: IP20
 - Field Bus Communication Type: BACnet, Modbus, RS485



1748217 1.5 kW

RS PRO INVERTER DRIVE, 3-PHASE IN, 2.2 KW, 380 → 480 V AC, 7.3 A

- ขนาดบรรจุภัณฑ์: 1 x EA
- Power Rating: 2.2 kW
 - Phase: 3
 - Supply Voltage: 380 → 480 V ac
 - Current Rating: 7.3 A
 - Output Frequency: 599 Hz
 - For Use With: Wide Range of Drive Applications
 - IP Rating: IP20
 - Field Bus Communication Type: BACnet, Modbus, RS485



1748218 2.2 kW

RS PRO INVERTER DRIVE, 3-PHASE IN, 3.7 KW, 380 → 480 V AC, 10.1 A

- ขนาดบรรจุภัณฑ์: 1 x EA
- Power Rating: 3.7 kW
 - Phase: 3
 - Supply Voltage: 380 → 480 V ac
 - Current Rating: 10.1 A
 - Output Frequency: 599 Hz
 - For Use With: Wide Range of Drive Applications
 - IP Rating: IP20
 - Field Bus Communication Type: BACnet, Modbus, RS485



1748219 3.7 kW

RS PRO INVERTER DRIVE, 3-PHASE IN, 5.5 KW, 380 → 480 V AC, 14.3 A

- ขนาดบรรจุภัณฑ์: 1 x EA
- Power Rating: 5.5 kW
 - Phase: 3
 - Supply Voltage: 380 → 480 V ac
 - Current Rating: 14.3 A
 - Output Frequency: 599 Hz
 - For Use With: Wide Range of Drive Applications
 - IP Rating: IP20
 - Field Bus Communication Type: BACnet, Modbus, RS485



1748220 5.5 kW

REGULATOR, VOLTAGE, 15V, 3A, C/W SPEED CONTROL, DC MOTORS

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 6 → 15 V dc
 - Current Rating: 3 A
 - Voltage Rating: 6 → 15 V dc



2389816 6 → 15 V dc

CONTROL, SERVO MOTOR, PRECISION DC, 4 QUADRANT, 2A

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 10 → 35 V
 - Current Rating: 2.2 A
 - Voltage Rating: 27.5 V



3132122 10 → 35 V

MOTOR, SPEED, REGULATOR, PANEL MOUNT, PWM, 3A

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 6 → 15 V dc
 - Current Rating: 3 A
 - Voltage Rating: 6 → 15 V dc



4179728 6 → 15 V dc

BI DIRECTIONAL SPEED REGULATOR

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 6 → 15 V dc
 - Current Rating: 3 A
 - Voltage Rating: 6 → 15 V dc



7522009 6 → 15 V dc

RS PRO STEPPER MOTOR CONTROLLER, 4.4 A, 48 V

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Rating: 4.4 A
 - Voltage Rating: 48 V
 - Overall Length: 92 mm
 - Overall Width: 85 mm
 - Overall Depth: 23 mm



9058780 4.4 A

RS PRO STEPPER MOTOR CONTROLLER 2.2 A, 24 → 48V, 78 X 68

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Rating: 2.2 A
 - Voltage Rating: 48 V
 - Overall Length: 78 mm
 - Overall Width: 68 mm
 - Overall Depth: 21 mm



9058786 2.2 A

RS PRO MOUNTING KIT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Mounting Kit
 - For Use With: Motor



336214 Mounting Kit

MCLENNAN ADAPTER

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Adapter
 - For Use With: Motor



718947 Adapter

RS PRO 2.2 KW SOFT STARTER, 230 V AC, 1 PHASE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Power Rating: 2.2 kW
 - Motor Starter Type: Soft Start
 - Voltage Rating: 230 V ac
 - Phase: 1
 - Current Rating: 12 A
 - Overall Length: 120 mm
 - Overall Width: 45 mm
 - Overall Depth: 70 mm



2096340 2.2 kW

RS PRO 2.2 KW SOFT STARTER, 400 V AC, 3 PHASE, IP20

- ขนาดบรรจุภัณฑ์: 1 x EA
- Power Rating: 2.2 kW
 - Motor Starter Type: Soft Start
 - Voltage Rating: 460 V ac
 - Phase: 3
 - Current Rating: 5.5 A
 - IP Rating: IP20
 - Overall Length: 120 mm
 - Overall Width: 45 mm



2096356 2.2 kW

RS PRO 2.2 KW SOFT STARTER, 400 V AC, 3 PHASE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Power Rating: 2.2 kW
 - Motor Starter Type: Soft Start
 - Voltage Rating: 460 V ac
 - Phase: 3
 - Current Rating: 5.5 A
 - Overall Length: 120 mm
 - Overall Width: 45 mm
 - Overall Depth: 75 mm



2128683 2.2 kW

MOTOR, SERVO, 24VDC, C/W DUAL SHAFT, RATED SPEED 1600RPM, RATED

- ขนาดบรรจุภัณฑ์: 1 x EA
- Maximum Output Torque: 27 Ncm
 - Supply Voltage: 24 V dc
 - Output Speed: 1600 rpm
 - Power Rating: 30 W
 - Stall Torque: 12 Nm
 - Shaft Diameter: 6 mm
 - Length: 64 mm
 - Width: 66 mm



2635995 27 Ncm

MOTOR, SERVO, 24VDC, 9NCM, C/W TACHO ASSEMBLY

- ขนาดบรรจุภัณฑ์: 1 x EA
- Maximum Output Torque: 36 Ncm
 - Supply Voltage: 24 → 30 V dc
 - Output Speed: 1600 rpm
 - Power Rating: 30 W
 - Stall Torque: 14 Ncm
 - Shaft Diameter: 6 mm
 - Length: 134 mm
 - Width: 66 mm



2636005 36 Ncm

MOTOR, SERVO, 24VDC, 9NCM, C/W ENCODER

- ขนาดบรรจุภัณฑ์: 1 x EA
- Maximum Output Torque: 36 Ncm
 - Supply Voltage: 24 → 30 V dc
 - Output Speed: 1600 rpm
 - Power Rating: 30 W
 - Stall Torque: 12 Ncm
 - Shaft Diameter: 6 mm
 - Length: 88 mm
 - Width: 66 mm



2636011 36 Ncm

RS PRO HYBRID STEPPER MOTOR, 9.6 V, UNIPOLAR, 1.8°, 5MM SHAFT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Stepper Motor Type: Hybrid
 - Step Angle: 1.8°
 - Number Of Wires: 6
 - Supply Voltage: 9.6 V
 - Frame Size: 42.3 x 42.3 mm
 - Shaft Diameter: 5 mm
 - Current Rating: 400 mA
 - Winding Arrangement: Unipolar



1805278 Hybrid

RS PRO HYBRID STEPPER MOTOR, 12 V, UNIPOLAR, 1.8°, 5MM SHAFT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Stepper Motor Type: Hybrid
 - Step Angle: 1.8°
 - Number Of Wires: 6
 - Supply Voltage: 12 V
 - Frame Size: 42.3 x 42.3 mm
 - Shaft Diameter: 5 mm
 - Current Rating: 310 mA
 - Winding Arrangement: Unipolar



1805279 Hybrid

RS PRO HYBRID STEPPER MOTOR, 12 V, UNIPOLAR, 1.8°, 6.35MM SHAFT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Stepper Motor Type: Hybrid
 - Step Angle: 1.8°
 - Number Of Wires: 6
 - Supply Voltage: 12 V
 - Frame Size: 56.4 x 56.4 mm
 - Shaft Diameter: 6.35 mm
 - Current Rating: 400 mA
 - Winding Arrangement: Unipolar



1805281 Hybrid

RS PRO HYBRID STEPPER MOTOR, 6 V, UNIPOLAR, 1.8°, 6.35MM SHAFT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Stepper Motor Type: Hybrid
 - Step Angle: 1.8°
 - Number Of Wires: 6
 - Supply Voltage: 6 V
 - Frame Size: 56.4 x 56.4 mm
 - Shaft Diameter: 6.35 mm
 - Current Rating: 850 mA
 - Winding Arrangement: Unipolar



1805282 Hybrid

RS PRO HYBRID STEPPER MOTOR, 12 V, UNIPOLAR, 1.8°, 6.35MM SHAFT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Stepper Motor Type: Hybrid
 - Step Angle: 1.8°
 - Number Of Wires: 6
 - Supply Voltage: 12 V
 - Frame Size: 56.4 x 56.4 mm
 - Shaft Diameter: 6.35 mm
 - Current Rating: 420 mA
 - Winding Arrangement: Unipolar



1805283 Hybrid

RS PRO HYBRID STEPPER MOTOR, 1.65 V, 2.39 V, 3.42 V, PARALLEL,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Stepper Motor Type: Hybrid
 - Step Angle: 1.8°
 - Holding Torque: 2.6 (Unipolar) nm, 3.4 (Parallel) nm, 3.4 (Series) nm
 - Number Of Wires: 8
 - Supply Voltage: 1.65 V, 2.39 V, 3.42 V
 - Frame Size: 85.85 x 85.85 mm
 - Shaft Diameter: 12 mm
 - Current Rating: 3 A, 4.2 A, 5.9 A



1805293 Hybrid

RS PRO HYBRID, PERMANENT MAGNET STEPPER MOTOR, 3.96 V,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Stepper Motor Type: Hybrid, Permanent Magnet
 - Step Angle: 1.8°
 - Holding Torque: 17.5 mNm
 - Number Of Wires: 4
 - Supply Voltage: 3.96 V
 - Frame Size: 20.2 x 20.2 mm
 - Shaft Diameter: 4 mm
 - Current Rating: 600 mA



5350338 Hybrid,

RS PRO HYBRID, PERMANENT MAGNET STEPPER MOTOR, 3.8 V,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Stepper Motor Type: Hybrid, Permanent Magnet
 - Step Angle: 1.8°
 - Holding Torque: 60 mNm
 - Number Of Wires: 4
 - Supply Voltage: 3.8 V
 - Frame Size: 28 x 28 mm
 - Shaft Diameter: 4 mm
 - Current Rating: 670 mA



5350344 Hybrid,

RS PRO HYBRID, PERMANENT MAGNET STEPPER MOTOR, 2.8 V,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Stepper Motor Type: Hybrid, Permanent Magnet
 - Step Angle: 0.9°
 - Holding Torque: 2.2 mNm
 - Number Of Wires: 4
 - Supply Voltage: 2.8 V
 - Frame Size: 42.3 x 42.3 mm
 - Shaft Diameter: 5 mm
 - Current Rating: 1.33 A



5350372 Hybrid,

RS PRO HYBRID STEPPER MOTOR, 2.8 V, 0.44NM TORQUE, 0.9°, 5MM SHAFT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Stepper Motor Type: Hybrid
 - Step Angle: 0.9°
 - Holding Torque: 0.44 Nm
 - Number Of Wires: 4
 - Supply Voltage: 2.8 V
 - Frame Size: 42.3 x 42.3 mm
 - Shaft Diameter: 5 mm
 - Current Rating: 1.68 A



5350401 Hybrid

RS PRO HYBRID, PERMANENT MAGNET STEPPER MOTOR, 2.3 V,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Stepper Motor Type: Hybrid, Permanent Magnet
 - Step Angle: 1.8°
 - Holding Torque: 1.0 Nm
 - Number Of Wires: 4
 - Supply Voltage: 2.3 V
 - Frame Size: 56.4 x 56.4 mm
 - Shaft Diameter: 6.35 mm
 - Current Rating: 2.8 A



5350423 Hybrid,

RS PRO HYBRID, PERMANENT MAGNET STEPPER MOTOR, 3.2 V,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Stepper Motor Type: Hybrid, Permanent Magnet
 - Step Angle: 1.8°
 - Holding Torque: 1.89 Nm
 - Number Of Wires: 4
 - Supply Voltage: 3.2 V
 - Frame Size: 56.4 x 56.4 mm
 - Shaft Diameter: 6.35 mm
 - Current Rating: 2.8 A



5350445 Hybrid,

RS PRO HYBRID, PERMANENT MAGNET STEPPER MOTOR, 2.8 V,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Stepper Motor Type: Hybrid, Permanent Magnet
 - Step Angle: 1.8°
 - Holding Torque: 0.22 Nm
 - Number Of Wires: 4
 - Supply Voltage: 2.8 V
 - Frame Size: 42.3 x 42.3 mm
 - Shaft Diameter: 5 mm
 - Current Rating: 1.33 A



5350467 Hybrid,

RS PRO HYBRID, PERMANENT MAGNET STEPPER MOTOR, 2.8 V,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Stepper Motor Type: Hybrid, Permanent Magnet
 - Step Angle: 1.8°
 - Holding Torque: 0.44 Nm
 - Number Of Wires: 4
 - Supply Voltage: 2.8 V
 - Frame Size: 42.3 x 42.3 mm
 - Shaft Diameter: 5 mm
 - Current Rating: 1.68 A



5350489 Hybrid,

RS PRO HYBRID, PERMANENT MAGNET STEPPER MOTOR, 2.5 V,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Stepper Motor Type: Hybrid, Permanent Magnet
 - Step Angle: 0.9°
 - Holding Torque: 1.26 Nm
 - Number Of Wires: 4
 - Supply Voltage: 2.5 V
 - Frame Size: 56.4 x 56.4 mm
 - Shaft Diameter: 6.35 mm
 - Current Rating: 3.8 A



5350502 Hybrid,

RS PRO HYBRID, PERMANENT MAGNET STEPPER MOTOR, 9 V,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Stepper Motor Type: Hybrid, Permanent Magnet
 - Step Angle: 1.8°
 - Holding Torque: 0.21 Nm
 - Number Of Wires: 4
 - Supply Voltage: 9 V
 - Frame Size: 39.2 x 39.2 mm
 - Shaft Diameter: 5 mm
 - Current Rating: 600 mA



8928723 Hybrid,

RS PRO HYBRID, PERMANENT MAGNET STEPPER MOTOR, 2.64 V,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Stepper Motor Type: Hybrid, Permanent Magnet
 - Step Angle: 1.8°
 - Holding Torque: 65 mNm
 - Number Of Wires: 4
 - Supply Voltage: 2.64 V
 - Frame Size: 39.2 x 39.2 mm
 - Shaft Diameter: 5 mm
 - Current Rating: 400 mA



8928729 Hybrid,

**HYBRID STEPPER MOTOR 1.8 DEGREE,
4 WIRES**

ขนาดบรรจุภัณฑ์: 1 x EA

- Stepper Motor Type: Hybrid, Permanent Magnet
- Step Angle: 1.8 °
- Holding Torque: 0.36 Nm
- Number Of Wires: 4
- Supply Voltage: 2.8 V
- Frame Size: 42.3 x 42.3 mm
- Shaft Diameter: 5 mm
- Current Rating: 1.68 A



8928732 Hybrid,

RS PRO SCREENED 1 CORE MICROPHONE CABLE, 0.22 MM² CSA,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Audio Cable Type: Microphone Cable
 - Number of Cores: 1
 - Cross Sectional Area: 0.22 mm²
 - Screened/Unscreened: Screened
 - Insulation Material: PE
 - Outer Diameter: 3.1 mm
 - Length: 100 m
 - Fire Behaviour: Self-extinguishing



2075312 Microphone

RS PRO SCREENED 2 CORE MICROPHONE CABLE, 0.22 MM² CSA,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Audio Cable Type: Microphone Cable
 - Number of Cores: 2
 - Cross Sectional Area: 0.22 mm²
 - Screened/Unscreened: Screened
 - Insulation Material: PE
 - Outer Diameter: 3.7 mm
 - Length: 100 m
 - Minimum Operating Temperature: -20 °C



2075319 Microphone

RS PRO SCREENED 3 CORE MICROPHONE CABLE, 0.22 MM² CSA,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Audio Cable Type: Microphone Cable
 - Number of Cores: 3
 - Cross Sectional Area: 0.22 mm²
 - Screened/Unscreened: Screened
 - Insulation Material: PE
 - Outer Diameter: 4 mm
 - Length: 100 m
 - Fire Behaviour: Self-extinguishing



2075320 Microphone

RS PRO SCREENED 4 CORE MICROPHONE CABLE, 0.16 MM² CSA,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Audio Cable Type: Microphone Cable
 - Number of Cores: 4
 - Cross Sectional Area: 0.16 mm²
 - Screened/Unscreened: Screened
 - Insulation Material: PVC
 - Outer Diameter: 4.4 mm
 - Length: 100 m
 - Fire Behaviour: Self-extinguishing



2075321 Microphone

RS PRO SCREENED 4 CORE MICROPHONE CABLE, 0.15 MM² CSA,

- ขนาดบรรจุภัณฑ์: **50 x MTR**
- Audio Cable Type: Microphone Cable
 - Number of Cores: 4
 - Cross Sectional Area: 0.15 mm²
 - Screened/Unscreened: Screened
 - Insulation Material: PVC
 - Outer Diameter: 4.7 mm
 - Length: 50 m
 - Fire Behaviour: Self-extinguishing



2075323 Microphone

RS PRO SCREENED 4 CORE MICROPHONE CABLE, 0.22 MM² CSA,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Audio Cable Type: Microphone Cable
 - Number of Cores: 4
 - Cross Sectional Area: 0.22 mm²
 - Screened/Unscreened: Screened
 - Insulation Material: PE
 - Outer Diameter: 4.4 mm
 - Length: 100 m
 - Fire Behaviour: Self-extinguishing



2075324 Microphone

RS PRO SCREENED 6 CORE MICROPHONE CABLE, 0.22 MM² CSA,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Audio Cable Type: Microphone Cable
 - Number of Cores: 6
 - Cross Sectional Area: 0.22 mm²
 - Screened/Unscreened: Screened
 - Insulation Material: PE
 - Outer Diameter: 5.2 mm
 - Length: 100 m
 - Fire Behaviour: Self-extinguishing



2075325 Microphone

RS PRO SCREENED 1 CORE MICROPHONE CABLE, 0.22 MM² CSA,

- ขนาดบรรจุภัณฑ์: **25 x MTR**
- Audio Cable Type: Microphone Cable
 - Number of Cores: 1
 - Cross Sectional Area: 0.22 mm²
 - Screened/Unscreened: Screened
 - Insulation Material: PE
 - Outer Diameter: 4.5 mm
 - Length: 25 m
 - Fire Behaviour: Self-extinguishing



2075329 Microphone

RS PRO MALE FEMALE TV AERIAL CABLE, RG59/U, 75 Ω, 1.5M

- ขนาดบรรจุภัณฑ์: **1 x MTR**
- Terminated/Unterminated: Terminated
 - Coaxial Type: RG59/U
 - Connector A Gender: Male
 - Connector B Gender: Female
 - Characteristic Impedance: 75 Ω
 - Length: 1.5 m
 - Sheath Colour: Grey
 - Insulation Material: PVC



1115462 Terminated

RS PRO MALE FEMALE TV AERIAL CABLE, 75 Ω, 3.5M

- ขนาดบรรจุภัณฑ์: **3 x MTR**
- Terminated/Unterminated: Terminated
 - Connector A Gender: Male
 - Connector B Gender: Female
 - Characteristic Impedance: 75 Ω
 - Length: 3.5 m
 - Sheath Colour: Grey
 - Shielding: Shielded
 - Conductor Material: Copper



1115478 Terminated

RS PRO COAXIAL CABLE, RG58, 50 Ω, 100M

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Terminated/Unterminated: Unterminated
 - Coaxial Type: RG58
 - Outer Diameter: 4.95 mm
 - Characteristic Impedance: 50 Ω
 - Length: 100 m
 - Sheath Colour: Black
 - Sheath Material: PVC
 - Operating Temperature Range: -10 °C→+70 °C



2163678 Unterminated

RS PRO COAXIAL CABLE, RG59, 75 Ω, 100M

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Terminated/Unterminated: Unterminated
 - Coaxial Type: RG59
 - Outer Diameter: 6.1 mm
 - Characteristic Impedance: 75 Ω
 - Length: 100 m
 - Sheath Colour: Black
 - Sheath Material: PVC
 - Operating Temperature Range: -10 °C→+70 °C



2163679 Unterminated

COAX CABLE RG174 A/U

- ขนาดบรรจุภัณฑ์: **20 x MTR**
- Terminated/Unterminated: Unterminated
 - Coaxial Type: RG174A/U
 - Outer Diameter: 2.79 mm
 - Characteristic Impedance: 50 Ω
 - Attenuation: 220 dB/100m @ 3GHz, 42 dB/100m @ 200MHz, 60 dB/100m @ 400MHz
 - Length: 20 m
 - Sheath Colour: Black
 - Conductor Strand Type: Stranded



2228610 Unterminated

RS PRO COAXIAL CABLE, RG58, 50 Ω, 500M

- ขนาดบรรจุภัณฑ์: **500 x MTR**
- Terminated/Unterminated: Unterminated
 - Coaxial Type: RG58
 - Outer Diameter: 4.95 mm
 - Characteristic Impedance: 50 Ω
 - Attenuation: 4.7 dB/100m
 - Length: 500 m
 - Sheath Colour: White
 - Conductor Strand Type: Stranded



5217916 Unterminated

RS PRO COAXIAL CABLE, RG179, 75 Ω, 50M

- ขนาดบรรจุภัณฑ์: **50 x MTR**
- Terminated/Unterminated: Unterminated
 - Coaxial Type: RG179
 - Outer Diameter: 2.8 mm
 - Characteristic Impedance: 75 Ω
 - Attenuation: 52.5 dB/100m @ 400MHz, 64.6 dB/100m @ 700MHz, 73.2 dB/100m @ 900MHz, 78.7 dB/100m @ 1GHz
 - Length: 50 m
 - Sheath Colour: Black
 - Conductor Strand Type: Stranded



5217950 Unterminated

RS PRO COAXIAL CABLE, RG62A/U, 93 Ω, 100M

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Terminated/Unterminated: Unterminated
 - Coaxial Type: RG62A/U
 - Outer Diameter: 6.07 mm
 - Characteristic Impedance: 93 Ω
 - Attenuation: 17.4 dB/100m @ 400MHz, 23.9 dB/100m @ 700MHz, 26.9 dB/100m @ 900MHz, 28.5 dB/100m @ 1GHz
 - Length: 100 m
 - Sheath Colour: Black
 - Conductor Strand Type: Solid



5218010 Unterminated

RS PRO COAXIAL CABLE, RG62A/U, 93 Ω, 100M

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Terminated/Unterminated: Unterminated
 - Coaxial Type: RG62A/U
 - Outer Diameter: 6.15 mm
 - Characteristic Impedance: 93 Ω
 - Attenuation: 0.125 dB/m
 - Length: 100 m
 - Sheath Colour: Black
 - Fire Behaviour: Flame Retardant



5218032 Unterminated

RS PRO COAXIAL CABLE, RG178B/U, 50 Ω


- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Terminated/Unterminated: Unterminated
 - Coaxial Type: RG178B/U
 - Outer Diameter: 1.85 mm
 - Characteristic Impedance: 50 Ω
 - Attenuation: 151 dB @ 1GHz
 - Sheath Colour: Brown
 - Conductor Strand Type: Stranded
 - Sheath Material: FEP



9060635 Unterminated

RS PRO DATA CABLE, 0.14 MM², SCREENED, GREY, 26 AWG

- ขนาดบรรจุภัณฑ์: **50 x MTR**
- Cross Sectional Area: 0.14 mm²
 - Screened/Unscreened: Screened
 - Sheath Colour: Grey
 - American Wire Gauge: 26 AWG
 - Outer Diameter: 7.50 mm
 - Voltage Rating: 250 V
 - Shielded/Unshielded: Shielded



1959503 0.14 mm²

WIRE, ANNEALED COPPER, TINNED, 16 SWG, BS4109, 200G, FUSEWIRE 70A

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Cross Sectional Area: 1.3 mm²
 - American Wire Gauge: 16 AWG
 - Core Strands: 1/1.63 mm
 - Outer Diameter: 1.63 mm
 - Length: 11.4 m
 - Finish: Tinned
 - Wire Style: BS EN13602
 - Shield Type: Unshielded



355041 1.3 mm²

WIRE, ANNEALED COPPER, TINNED, 18 SWG, BS4109, 200G, FUSEWIRE 45A

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Cross Sectional Area: 1.1 mm²
 - American Wire Gauge: 17 AWG
 - Core Strands: 1/1.22 mm
 - Outer Diameter: 1.22 mm
 - Length: 20.2 m
 - Finish: Tinned
 - Wire Style: BS EN13602
 - Shield Type: Unshielded



355057 1.1 mm²

WIRE, ANNEALED COPPER, TINNED, 20 SWG, BS4109, 200G, FUSEWIRE 33A

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Cross Sectional Area: 0.7 mm²
 - American Wire Gauge: 19 AWG
 - Core Strands: 1/0.91 mm
 - Outer Diameter: 0.91 mm
 - Length: 34.6 m
 - Finish: Tinned
 - Wire Style: BS EN13602
 - Shield Type: Unshielded



355063 0.7 mm²

WIRE, ANNEALED COPPER, TINNED, 22 SWG, BS4109, 200G, FUSEWIRE 25A

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Cross Sectional Area: 0.4 mm²
 - American Wire Gauge: 21 AWG
 - Core Strands: 1/0.71 mm
 - Outer Diameter: 0.71 mm
 - Length: 50.9 m
 - Finish: Tinned
 - Wire Style: BS EN13602
 - Shield Type: Unshielded



355079 0.4 mm²

WIRE, ANNEALED COPPER, TINNED, 24 SWG, BS4109, 200G, FUSEWIRE 17A

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Cross Sectional Area: 0.2 mm²
 - American Wire Gauge: 24 AWG
 - Core Strands: 1/0.56 mm
 - Outer Diameter: 0.56 mm
 - Length: 91.3 m
 - Finish: Tinned
 - Wire Style: BS EN13602
 - Shield Type: Unshielded



355085 0.2 mm²

WIRE, COPPER, SOLID, POLYURETHANE INSULATED, BS4520, 500G, 0.25MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Cross Sectional Area: 0.05 mm²
 - American Wire Gauge: 30 AWG
 - Core Strands: 1/0.25 mm
 - Insulation Material: PUR
 - Outer Diameter: 0.25 mm
 - Length: 1100 m
 - Finish: Enamelled
 - Wire Style: EN 60317/20



357716 0.05 mm²

WIRE, COPPER, SOLID, POLYURETHANE INSULATED, BS4520, 500G, 0.315MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Cross Sectional Area: 0.08 mm²
 - American Wire Gauge: 28 AWG
 - Core Strands: 1/0.31 mm
 - Insulation Material: PUR
 - Outer Diameter: 0.37 mm
 - Length: 700 m
 - Finish: Enamelled
 - Wire Style: EN 60317/20



357722 0.08 mm²

WIRE, COPPER, SOLID, POLYURETHANE INSULATED, BS4520, 500G, 0.4MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Cross Sectional Area: 0.13 mm²
 - American Wire Gauge: 26 AWG
 - Core Strands: 1/0.4 mm
 - Insulation Material: PUR
 - Outer Diameter: 0.45 mm
 - Length: 400 m
 - Finish: Enamelled
 - Wire Style: EN 60317/20



357738 0.13 mm²

WIRE, COPPER, SOLID, POLYURETHANE INSULATED, BS4520, 500G, 0.5MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Cross Sectional Area: 0.2 mm²
 - American Wire Gauge: 24 AWG
 - Core Strands: 1/0.5 mm
 - Insulation Material: PUR
 - Outer Diameter: 0.5 mm
 - Length: 286 m
 - Finish: Enamelled
 - Wire Style: EN 60317/20



357744 0.2 mm²

WIRE, COPPER, SOLID, POLYURETHANE INSULATED, BS4520, 500G, 0.56MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Cross Sectional Area: 0.26 mm²
 - American Wire Gauge: 23 AWG
 - Core Strands: 1/0.56 mm
 - Insulation Material: PUR
 - Outer Diameter: 0.62 mm
 - Length: 200 m
 - Finish: Enamelled
 - Wire Style: EN 60317/20



357750 0.26 mm²

WIRE, COPPER, SOLID, POLYURETHANE INSULATED, BS4520, 500G, 0.71MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Cross Sectional Area: 0.4 mm²
 - American Wire Gauge: 21 AWG
 - Core Strands: 1/0.71 mm
 - Insulation Material: PUR
 - Outer Diameter: 0.78 mm
 - Length: 120 m
 - Finish: Enamelled
 - Wire Style: EN 60317/20



357766 0.4 mm²

WIRE, COPPER, SOLID, POLYURETHANE INSULATED, BS4520, 500G, 0.81MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Cross Sectional Area: 0.52 mm²
 - American Wire Gauge: 20 AWG
 - Core Strands: 1/0.8 mm
 - Insulation Material: PUR
 - Outer Diameter: 0.87 mm
 - Length: 100 m
 - Finish: Enamelled
 - Wire Style: EN 60317/20



357772 0.52 mm²

WIRE, COPPER, SOLID, POLYURETHANE INSULATED, BS4520, 500G, 1.0MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Cross Sectional Area: 0.82 mm²
 - American Wire Gauge: 18 AWG
 - Core Strands: 1/1.0 mm
 - Insulation Material: PUR
 - Outer Diameter: 1.08 mm
 - Length: 80 m
 - Finish: Enamelled
 - Wire Style: EN 60317/20



357788 0.82 mm²

WIRE, COPPER, SOLID, POLYURETHANE INSULATED, BS4520, 500G, 1.25MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Cross Sectional Area: 1.3 mm²
 - American Wire Gauge: 16 AWG
 - Core Strands: 1/1.25 mm
 - Insulation Material: PUR
 - Outer Diameter: 1.33 mm
 - Length: 40 m
 - Finish: Enamelled
 - Wire Style: EN 60317/20



357794 1.3 mm²

WIRE, COPPER, SOLID, POLYURETHANE INSULATED, BS4520, 500G, 0.2MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Cross Sectional Area: 0.03 mm²
 - American Wire Gauge: 32 AWG
 - Core Strands: 1/0.2 mm
 - Insulation Material: PUR
 - Outer Diameter: 0.23 mm
 - Length: 1600 m
 - Finish: Enamelled
 - Wire Style: EN 60317/20



357918 0.03 mm²

WIRE, COPPER, SOLID, POLYURETHANE INSULATED, BS4520, 500G, 0.244MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Cross Sectional Area: 0.04 mm²
 - American Wire Gauge: 31 AWG
 - Core Strands: 1/0.22 mm
 - Insulation Material: PUR
 - Outer Diameter: 0.26 mm
 - Length: 1300 m
 - Finish: Enamelled
 - Wire Style: EN 60317/20



357924 0.04 mm²

WIRE, COPPER, SOLID, POLYURETHANE INSULATED, BS4520, 500G, 1.5MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Cross Sectional Area: 1.5 mm²
 - American Wire Gauge: 15 AWG
 - Core Strands: 1/1.5 mm
 - Insulation Material: PUR
 - Outer Diameter: 1.59 mm
 - Length: 30 m
 - Finish: Enamelled
 - Wire Style: EN 60317/20



357930 1.5 mm²

WIRE, ANNEALED COPPER, TINNED, 14-SWG, BS4109, 200

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Cross Sectional Area: 3.3 mm²
 - American Wire Gauge: 12 AWG
 - Core Strands: 1/2.03 mm
 - Outer Diameter: 2.03 mm
 - Length: 7.1 m
 - Finish: Tinned
 - Wire Style: BS EN13602
 - Shield Type: Unshielded



390527 3.3 mm²

WIRE, ANNEALED COPPER, TINNED, 25-SWG, BS4109, 200

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Cross Sectional Area: 0.2 mm²
 - American Wire Gauge: 24 AWG
 - Core Strands: 1/0.51 mm
 - Outer Diameter: 0.51 mm
 - Length: 114 m
 - Finish: Tinned
 - Wire Style: BS EN13602
 - Shield Type: Unshielded



390549 0.2 mm²

WIRE, ANNEALED COPPER, TINNED, 29-SWG, BS4109, 200

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Cross Sectional Area: 0.08 mm²
 - American Wire Gauge: 28 AWG
 - Core Strands: 1/0.35 mm
 - Outer Diameter: 0.35 mm
 - Length: 256 m
 - Finish: Tinned
 - Wire Style: BS EN13602
 - Shield Type: Unshielded



390555 0.08 mm²

WIRE, ANNEALED COPPER, TINNED, 35-SWG, BS4109, 200

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Cross Sectional Area: 0.03 mm²
 - American Wire Gauge: 32 AWG
 - Core Strands: 1/0.20 mm
 - Outer Diameter: 0.21 mm
 - Length: 717 m
 - Finish: Tinned
 - Wire Style: BS EN13602
 - Shield Type: Unshielded



390561 0.03 mm²

RS PRO CAT5E ETHERNET CABLE, F/UTP SHIELD, GREY PVC SHEATH,

- ขนาดบรรจุภัณฑ์: **305 x MTR**
- LAN Category: Cat5e
 - Terminated/Unterminated: Unterminated
 - Length: 305 m
 - Outer Sheath Material: PVC
 - Shield Type: F/UTP
 - Sheath Colour: Grey
 - American Wire Gauge: 24 AWG
 - Outer Diameter: 5 mm



556865 Cat5e

RS PRO CAT5E ETHERNET CABLE, F/UTP SHIELD, PURPLE PVC SHEATH,

- ขนาดบรรจุภัณฑ์: **305 x MTR**
- LAN Category: Cat5e
 - Terminated/Unterminated: Unterminated
 - Length: 305 m
 - Core Strands: 1/24
 - Shield Type: F/UTP
 - Outer Sheath Material: PVC
 - Sheath Colour: Purple
 - Fire Behaviour: Low Smoke Zero Halogen (LSZH)



556869 Cat5e

RS PRO CAT6 ETHERNET CABLE, F/UTP SHIELD, PURPLE LSZH SHEATH,

- ขนาดบรรจุภัณฑ์: **305 x MTR**
- LAN Category: Cat6
 - Terminated/Unterminated: Unterminated
 - Length: 305 m
 - Core Strands: 1/23
 - Shield Type: F/UTP
 - Outer Sheath Material: LSZH
 - Sheath Colour: Purple
 - Fire Behaviour: Low Smoke Zero Halogen (LSZH)



556875 Cat6

RS PRO CAT5E ETHERNET CABLE, U/UTP SHIELD, PURPLE LSZH SHEATH,

- ขนาดบรรจุภัณฑ์: **305 x MTR**
- LAN Category: Cat5e
 - Terminated/Unterminated: Unterminated
 - Length: 305 m
 - Core Strands: 1/24
 - Shield Type: U/UTP
 - Outer Sheath Material: LSZH
 - Sheath Colour: Purple
 - Fire Behaviour: Low Smoke Zero Halogen (LSZH)



557193 Cat5e

RS PRO CAT5E ETHERNET CABLE, F/UTP SHIELD, GREY PVC SHEATH,

- ขนาดบรรจุภัณฑ์: **305 x MTR**
- LAN Category: Cat5e
 - Terminated/Unterminated: Unterminated
 - Length: 305 m
 - Core Strands: 1/24
 - Shield Type: F/UTP
 - Outer Sheath Material: PVC
 - Sheath Colour: Grey
 - Conductor Strand Type: Solid



557212 Cat5e

RS PRO CAT5E ETHERNET CABLE, U/UTP SHIELD, GREY PVC SHEATH,

- ขนาดบรรจุภัณฑ์: **305 x MTR**
- LAN Category: Cat5e
 - Terminated/Unterminated: Unterminated
 - Length: 305 m
 - Core Strands: 1/24
 - Shield Type: U/UTP
 - Outer Sheath Material: PVC
 - Sheath Colour: Grey
 - Attenuation: ≥40 dB



557470 Cat5e

RS PRO CAT6A ETHERNET CABLE, U/FTP SHIELD, GREY PVC SHEATH,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- LAN Category: Cat6a
 - Terminated/Unterminated: Unterminated
 - Length: 100 m
 - Shield Type: U/FTP
 - Outer Sheath Material: PVC
 - Sheath Colour: Grey
 - Attenuation: 45.3 dB/100m
 - Standards Met: Euroclass Eca



1135901 Cat6a

RS PRO CAT6A ETHERNET CABLE, SF/FTP SHIELD, GREY PVC SHEATH,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- LAN Category: Cat6a
 - Terminated/Unterminated: Unterminated
 - Length: 100 m
 - Shield Type: SF/FTP
 - Outer Sheath Material: PVC
 - Sheath Colour: Grey
 - Attenuation: 45.3 dB/100m
 - Standards Met: Euroclass Eca



1135902 Cat6a

RS PRO CAT7 ETHERNET CABLE, U/FTP SHIELD, BLACK PVC SHEATH,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- LAN Category: Cat7
 - Terminated/Unterminated: Unterminated
 - Length: 100 m
 - Shield Type: U/FTP
 - Outer Sheath Material: PVC
 - Sheath Colour: Black
 - Attenuation: 50.1 dB/100m
 - Standards Met: Euroclass Eca



1135903 Cat7

RS PRO CAT7 ETHERNET CABLE, U/FTP SHIELD, BLACK LSZH SHEATH,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- LAN Category: Cat7
 - Terminated/Unterminated: Unterminated
 - Length: 100 m
 - Outer Sheath Material: LSZH
 - Shield Type: U/FTP
 - Sheath Colour: Black
 - Fire Behaviour: Low Smoke Zero Halogen (LSZH)
 - Attenuation: 61.9 dB/100m



1135904 Cat7

RS PRO CAT7 ETHERNET CABLE, SF/FTP SHIELD, BLACK PVC SHEATH,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- LAN Category: Cat7
 - Terminated/Unterminated: Unterminated
 - Length: 100 m
 - Outer Sheath Material: PVC
 - Shield Type: SF/FTP
 - Sheath Colour: Black
 - Attenuation: 50.1 dB/100m
 - American Wire Gauge: 23 AWG



1135905 Cat7

RS PRO CAT7 ETHERNET CABLE, U/FTP SHIELD, GREY PVC SHEATH,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- LAN Category: Cat7
 - Terminated/Unterminated: Unterminated
 - Length: 100 m
 - Shield Type: U/FTP
 - Outer Sheath Material: PVC
 - Sheath Colour: Grey
 - Attenuation: 50.1 dB/100m
 - Standards Met: Euroclass Eca



1135906 Cat7

RS PRO CAT7 ETHERNET CABLE, SF/FTP SHIELD, GREY PVC SHEATH,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- LAN Category: Cat7
 - Terminated/Unterminated: Unterminated
 - Length: 100 m
 - Outer Sheath Material: PVC
 - Shield Type: SF/FTP
 - Sheath Colour: Grey
 - Attenuation: 50.1 dB/100m
 - American Wire Gauge: 23 AWG



1135908 Cat7

RS PRO CAT7A ETHERNET CABLE, U/FTP SHIELD, BLACK PVC SHEATH,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- LAN Category: Cat7a
 - Terminated/Unterminated: Unterminated
 - Length: 100 m
 - Shield Type: U/FTP
 - Outer Sheath Material: PVC
 - Sheath Colour: Black
 - Attenuation: 61.9 dB/100m
 - Standards Met: Euroclass Eca



1135909 Cat7a

RS PRO CAT7A ETHERNET CABLE, U/FTP SHIELD, BLACK LSZH SHEATH,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- LAN Category: Cat7a
 - Terminated/Unterminated: Unterminated
 - Length: 100 m
 - Shield Type: U/FTP
 - Outer Sheath Material: LSZH
 - Sheath Colour: Black
 - Fire Behaviour: Low Smoke Zero Halogen (LSZH)
 - Attenuation: 61.9 dB/100m



1135910 Cat7a

CORDON CAT6 F/UTP 1M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- LAN Category: Cat6
 - Terminated/Unterminated: Terminated
 - Connector A: RJ45
 - Connector A Gender: Male
 - Connector B: RJ45
 - Connector B Gender: Male
 - Length: 1 m
 - Outer Sheath Material: PVC



2010530 Cat6

RS PRO CAT6 ETHERNET CABLE, RJ45 TO RJ45, F/UTP SHIELD, GREY PVC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- LAN Category: Cat6
 - Terminated/Unterminated: Terminated
 - Connector A: RJ45
 - Connector A Gender: Male
 - Connector B: RJ45
 - Connector B Gender: Male
 - Length: 2 m
 - Outer Sheath Material: PVC



2010531 Cat6

RS PRO CAT6 ETHERNET CABLE, RJ45 TO RJ45, F/UTP SHIELD, GREY PVC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- LAN Category: Cat6
 - Terminated/Unterminated: Terminated
 - Connector A: RJ45
 - Connector A Gender: Male
 - Connector B: RJ45
 - Connector B Gender: Male
 - Length: 5 m
 - Outer Sheath Material: PVC



2010533 Cat6

RS PRO CAT6A ETHERNET CABLE, RJ45 TO RJ45, U/FTP SHIELD, GREY

- ขนาดบรรจุภัณฑ์: **1 x EA**
- LAN Category: Cat6a
 - Terminated/Unterminated: Terminated
 - Connector A: RJ45
 - Connector A Gender: Male
 - Connector B: RJ45
 - Connector B Gender: Male
 - Length: 1 m
 - Outer Sheath Material: LSZH



2010534 Cat6a

RS PRO CAT6A ETHERNET CABLE, RJ45 TO RJ45, U/FTP SHIELD, GREY

- ขนาดบรรจุภัณฑ์: **1 x EA**
- LAN Category: Cat6a
 - Terminated/Unterminated: Terminated
 - Connector A: RJ45
 - Connector A Gender: Male
 - Connector B: RJ45
 - Connector B Gender: Male
 - Length: 2 m
 - Outer Sheath Material: LSZH



2010535 Cat6a

RS PRO CAT6 ETHERNET CABLE, U/UTP SHIELD, WHITE LSZH SHEATH,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- LAN Category: Cat6
 - Terminated/Unterminated: Unterminated
 - Length: 100 m
 - Outer Sheath Material: LSZH
 - Shield Type: U/UTP
 - Sheath Colour: White
 - Fire Behaviour: Low Smoke Zero Halogen (LSZH)



2097614 Cat6

BLUE CAT5 PLUS UTP PATCH CABLE, 50M

- ขนาดบรรจุภัณฑ์: **50 x MTR**
- LAN Category: Cat5
 - Terminated/Unterminated: Unterminated
 - Length: 50 m
 - Core Strands: 7/0.16
 - Shield Type: U/UTP
 - Outer Sheath Material: PVC
 - Sheath Colour: Blue
 - Attenuation: 37.4 dB



8124781 Cat5

RS PRO CAT5 ETHERNET CABLE, U/UTP SHIELD, YELLOW PVC SHEATH,

- ขนาดบรรจุภัณฑ์: **50 x MTR**
- LAN Category: Cat5
 - Terminated/Unterminated: Unterminated
 - Length: 50 m
 - Core Strands: 7/0.16
 - Shield Type: U/UTP
 - Outer Sheath Material: PVC
 - Sheath Colour: Yellow
 - Attenuation: 37.4 dB



8124785 Cat5

RS PRO CAT5 ETHERNET CABLE, U/UTP SHIELD, RED PVC SHEATH, 50M

- ขนาดบรรจุภัณฑ์: **50 x MTR**
- LAN Category: Cat5
 - Terminated/Unterminated: Unterminated
 - Length: 50 m
 - Core Strands: 7/0.16
 - Shield Type: U/UTP
 - Outer Sheath Material: PVC
 - Sheath Colour: Red
 - Attenuation: 37.4 dB



8124788 Cat5

RS PRO CAT5E ETHERNET CABLE, S/UTP SHIELD, GREY PVC SHEATH,

- ขนาดบรรจุภัณฑ์: **305 x MTR**
- LAN Category: Cat5e
 - Terminated/Unterminated: Unterminated
 - Length: 305 m
 - Core Strands: 7/0.16
 - Shield Type: S/UTP
 - Outer Sheath Material: PVC
 - Sheath Colour: Grey
 - Attenuation: 37.4 dB



8124791 Cat5e

RS PRO CAT5 ETHERNET CABLE, U/UTP SHIELD, GREEN PVC SHEATH,

- ขนาดบรรจุภัณฑ์: **50 x MTR**
- LAN Category: Cat5
 - Terminated/Unterminated: Unterminated
 - Length: 50 m
 - Core Strands: 7/0.16
 - Shield Type: U/UTP
 - Outer Sheath Material: PVC
 - Sheath Colour: Green
 - Attenuation: 37.4 dB



8124794 Cat5

RS PRO CAT5E ETHERNET CABLE, U/UTP SHIELD, GREY PVC SHEATH,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- LAN Category: Cat5e
 - Terminated/Unterminated: Unterminated
 - Length: 100 m
 - Core Strands: 7/0.16
 - Shield Type: U/UTP
 - Outer Sheath Material: PVC
 - Sheath Colour: Grey
 - Attenuation: 37.4 dB



8124797 Cat5e

4 PAIR SHIELDED CAT5E FTP PATCH 100M

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- LAN Category: Cat5e
 - Terminated/Unterminated: Unterminated
 - Length: 100 m
 - Core Strands: 7/0.16
 - Shield Type: F/UTP
 - Outer Sheath Material: PVC
 - Sheath Colour: Grey
 - Attenuation: 37.4 dB



8124801 Cat5e

RS PRO CAT5E ETHERNET CABLE, U/UTP SHIELD, PURPLE PVC SHEATH,

- ขนาดบรรจุภัณฑ์: **305 x MTR**
- LAN Category: Cat5e
 - Terminated/Unterminated: Unterminated
 - Length: 305 m
 - Core Strands: 8/0.5
 - Shield Type: U/UTP
 - Outer Sheath Material: PVC
 - Sheath Colour: Purple
 - Fire Behaviour: Low Smoke Zero Halogen (LSZH)



9164080 Cat5e

RS PRO CAT6 ETHERNET CABLE, U/UTP SHIELD, GREY PVC SHEATH,

- ขนาดบรรจุภัณฑ์: **305 x MTR**
- LAN Category: Cat6
 - Terminated/Unterminated: Unterminated
 - Length: 305 m
 - Core Strands: 8/0.57
 - Shield Type: U/UTP
 - Outer Sheath Material: PVC
 - Sheath Colour: Grey
 - Standards Met: RoHS Compliant



9164087 Cat6

RS PRO CAT6 ETHERNET CABLE, U/UTP SHIELD, YELLOW PVC SHEATH,

- ขนาดบรรจุภัณฑ์: **305 x MTR**
- LAN Category: Cat6
 - Terminated/Unterminated: Unterminated
 - Length: 305 m
 - Core Strands: 8/0.57
 - Shield Type: U/UTP
 - Outer Sheath Material: PVC
 - Sheath Colour: Yellow
 - Fire Behaviour: Low Smoke Zero Halogen (LSZH)



9164093 Cat6

RS PRO CAT6 ETHERNET CABLE, U/UTP SHIELD, PURPLE PVC SHEATH,

- ขนาดบรรจุภัณฑ์: **305 x MTR**
- LAN Category: Cat6
 - Terminated/Unterminated: Unterminated
 - Length: 305 m
 - Core Strands: 8/0.57
 - Shield Type: U/UTP
 - Outer Sheath Material: PVC
 - Sheath Colour: Purple
 - Fire Behaviour: Low Smoke Zero Halogen (LSZH)



9164096 Cat6

RS PRO CAT6 ETHERNET CABLE, U/UTP SHIELD, BLUE PVC SHEATH,

- ขนาดบรรจุภัณฑ์: **305 x MTR**
- LAN Category: Cat6
 - Terminated/Unterminated: Unterminated
 - Length: 305 m
 - Core Strands: 8/0.57
 - Shield Type: U/UTP
 - Outer Sheath Material: PVC
 - Sheath Colour: Blue
 - Fire Behaviour: Low Smoke Zero Halogen (LSZH)



9164099 Cat6

RS PRO CAT6 ETHERNET CABLE, U/UTP SHIELD, BLACK PE SHEATH,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- LAN Category: Cat6
 - Terminated/Unterminated: Unterminated
 - Length: 100 m
 - Core Strands: 8/0.57
 - Shield Type: U/UTP
 - Outer Sheath Material: PE
 - Sheath Colour: Black
 - Standards Met: RoHS Compliant



9164103 Cat6

RS PRO FEMALE CAT6A RJ45 CONNECTOR

- ขนาดบรรจุภัณฑ์: **8 x EA**
- Gender: Female
 - Ethernet Connector Type: RJ45 Connector
 - LAN Category: Cat6a
 - Mounting Type: Tool-Less Cable Mounting
 - Number of Parts: 1
 - Number of Ways: 1
 - Shield Type: 360° Shielded
 - Contact Material: Bronze



2010529 Female

RS PRO DUPLEX MULTI MODE OM3 FIBRE OPTIC CABLE, 6.5MM, BLACK,

- ขนาดบรรจุภัณฑ์: **250 x MTR**
- Length: 250 m
 - Propagation Mode: Multi Mode
 - Terminated/Unterminated: Unterminated
 - Core Diameter: 6.5 mm
 - Number of Cores: 8
 - Sheath Colour: Black
 - Cable Construction: Duplex
 - Fibre Type: OM3



1235717 250 m

RS PRO SIMPLEX FIBRE OPTIC CABLE, 980MM, BLACK, 20M

- ขนาดบรรจุภัณฑ์: **20 x MTR**
- Length: 20 m
 - Terminated/Unterminated: Unterminated
 - Core Diameter: 980 µm
 - Number of Cores: 1
 - Sheath Colour: Black
 - Cable Construction: Simplex
 - Maximum Operating Temperature: +85 °C
 - Minimum Operating Temperature: -45 °C



1644254 20 m

RS PRO SIMPLEX FIBRE OPTIC CABLE, 980MM, BLACK, 20M

- ขนาดบรรจุภัณฑ์: **20 x MTR**
- Length: 20 m
 - Terminated/Unterminated: Unterminated
 - Core Diameter: 980 µm
 - Number of Cores: 2
 - Sheath Colour: Black
 - Cable Construction: Simplex
 - Maximum Operating Temperature: +85 °C
 - Minimum Operating Temperature: -45 °C



1644255 20 m

RS PRO MULTI MODE FIBRE OPTIC CABLE, 0.0625MM, BLACK, 500M

- ขนาดบรรจุภัณฑ์: **500 x MTR**
- Length: 500 m
 - Propagation Mode: Multi Mode
 - Terminated/Unterminated: Unterminated
 - Core Diameter: 0.0625 mm
 - Number of Cores: 4
 - Sheath Colour: Black
 - Fire Behaviour: Low Smoke Zero Halogen (LSZH)
 - Sheath Material: Low Smoke Zero Halogen (LSZH)



2908861 500 m

RS PRO RED 0.13 MM² EQUIPMENT WIRE, 26 AWG, 1/0.4 MM, 100M, ETFE


- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.13 mm²
 - Sheath Colour: Red
 - American Wire Gauge: 26 AWG
 - Core Strands: 1/0.4 mm
 - Length: 100 m
 - Insulation Material: ETFE
 - Voltage Rating: 375 V
 - Outer Diameter: 0.71 mm



354054 0.13 mm²

RS PRO BLUE 0.13 MM² EQUIPMENT WIRE, 26 AWG, 1/0.4 MM, 100M, ETFE

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.13 mm²
 - Sheath Colour: Blue
 - American Wire Gauge: 26 AWG
 - Core Strands: 1/0.4 mm
 - Length: 100 m
 - Insulation Material: ETFE
 - Outer Diameter: 0.71 mm
 - Voltage Rating: 375 V



354060 0.13 mm²

RS PRO BLACK 0.13 MM² EQUIPMENT WIRE, 26 AWG, 1/0.4 MM, 100M, ETFE

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.13 mm²
 - Sheath Colour: Black
 - American Wire Gauge: 26 AWG
 - Core Strands: 1/0.4 mm
 - Length: 100 m
 - Insulation Material: ETFE
 - Voltage Rating: 375 V
 - Outer Diameter: 0.71 mm



354076 0.13 mm²

RS PRO WHITE 0.13 MM² EQUIPMENT WIRE, 26 AWG, 1/0.4 MM, 100M, ETFE

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.13 mm²
 - Sheath Colour: White
 - American Wire Gauge: 26 AWG
 - Core Strands: 1/0.4 mm
 - Length: 100 m
 - Insulation Material: ETFE
 - Voltage Rating: 375 V
 - Outer Diameter: 0.71 mm



354098 0.13 mm²

RS PRO RED 0.05 MM² EQUIPMENT WIRE, 30 AWG, 1/0.25 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.05 mm²
 - Sheath Colour: Red
 - American Wire Gauge: 30 AWG
 - Core Strands: 1/0.25 mm
 - Length: 100 m
 - Insulation Material: ETFE
 - Voltage Rating: 375 V
 - Outer Diameter: 0.56 mm



359835 0.05 mm²

RS PRO BLUE 0.05 MM² EQUIPMENT WIRE, 30 AWG, 1/0.25 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.05 mm²
 - Sheath Colour: Blue
 - American Wire Gauge: 30 AWG
 - Core Strands: 1/0.25 mm
 - Length: 100 m
 - Insulation Material: ETFE
 - Outer Diameter: 0.56 mm
 - Voltage Rating: 375 V



359841 0.05 mm²

RS PRO BLACK 0.05 MM² EQUIPMENT WIRE, 30 AWG, 1/0.25 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.05 mm²
 - Sheath Colour: Black
 - American Wire Gauge: 30 AWG
 - Core Strands: 1/0.25 mm
 - Length: 100 m
 - Insulation Material: ETFE
 - Voltage Rating: 375 V
 - Outer Diameter: 0.56 mm



359857 0.05 mm²

RS PRO GREEN 0.05 MM² EQUIPMENT WIRE, 30 AWG, 1/0.25 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.05 mm²
 - Sheath Colour: Green
 - American Wire Gauge: 30 AWG
 - Core Strands: 1/0.25 mm
 - Length: 100 m
 - Insulation Material: ETFE
 - Voltage Rating: 375 V
 - Outer Diameter: 0.56 mm



359885 0.05 mm²

RS PRO PURPLE 0.05 MM² EQUIPMENT WIRE, 30 AWG, 1/0.25

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.05 mm²
 - Sheath Colour: Purple
 - American Wire Gauge: 30 AWG
 - Core Strands: 1/0.25 mm
 - Length: 100 m
 - Insulation Material: ETFE
 - Outer Diameter: 0.56 mm
 - Voltage Rating: 375 V



359891 0.05 mm²

RS PRO WHITE 0.05 MM² EQUIPMENT WIRE, 30 AWG, 1/0.25 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.05 mm²
 - Sheath Colour: White
 - American Wire Gauge: 30 AWG
 - Core Strands: 1/0.25 mm
 - Length: 100 m
 - Insulation Material: ETFE
 - Voltage Rating: 375 V
 - Outer Diameter: 0.56 mm



359908 0.05 mm²

RS PRO WHITE 0.2 MM² HOOKUP & EQUIPMENT WIRE, 24 AWG, 19/0.12

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.2 mm²
 - Sheath Colour: White
 - American Wire Gauge: 24 AWG
 - Core Strands: 19/0.12 mm
 - Length: 100 m
 - Insulation Material: Polyamide
 - Voltage Rating: 600 V ac
 - Outer Diameter: 0.96 mm



1113142 0.2 mm²

RS PRO GREEN 0.33 MM² EQUIPMENT WIRE, 22 AWG, 19/0.15 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.33 mm²
 - Sheath Colour: Green
 - American Wire Gauge: 22 AWG
 - Core Strands: 19/0.15 mm
 - Length: 100 m
 - Insulation Material: Polyamide
 - Voltage Rating: 600 V ac
 - Outer Diameter: 1.1 mm



1113143 0.33 mm²

RS PRO BLUE 1 MM² AUTOMOTIVE WIRE, 57/0.15 MM, 30M

- ขนาดบรรจุภัณฑ์: **30 x MTR**
- Cross Sectional Area: 1 mm²
 - Sheath Colour: Blue
 - Core Strands: 57/0.15 mm
 - Length: 30 m
 - Outer Diameter: 2.7 mm
 - Voltage Rating: 600 V
 - Maximum Operating Temperature: +100 °C
 - Minimum Operating Temperature: -40 °C



1225857 1 mm²

RS PRO BROWN 1 MM² AUTOMOTIVE WIRE, 57/0.15 MM, 30M

- ขนาดบรรจุภัณฑ์: **30 x MTR**
- Cross Sectional Area: 1 mm²
 - Sheath Colour: Brown
 - Core Strands: 57/0.15 mm
 - Length: 30 m
 - Outer Diameter: 2.7 mm
 - Voltage Rating: 600 V
 - Maximum Operating Temperature: +100 °C
 - Minimum Operating Temperature: -40 °C



1225858 1 mm²

RS PRO GREEN 1 MM² AUTOMOTIVE WIRE, 57/0.15 MM, 30M

- ขนาดบรรจุภัณฑ์: **30 x MTR**
- Cross Sectional Area: 1 mm²
 - Sheath Colour: Green
 - Core Strands: 57/0.15 mm
 - Length: 30 m
 - Outer Diameter: 2.7 mm
 - Voltage Rating: 600 V
 - Maximum Operating Temperature: +100 °C
 - Minimum Operating Temperature: -40 °C



1225859 1 mm²

RS PRO WHITE 1 MM² AUTOMOTIVE WIRE, 57/0.15 MM, 30M

- ขนาดบรรจุภัณฑ์: **30 x MTR**
- Cross Sectional Area: 1 mm²
 - Sheath Colour: White
 - Core Strands: 57/0.15 mm
 - Length: 30 m
 - Outer Diameter: 2.7 mm
 - Voltage Rating: 600 V
 - Maximum Operating Temperature: +100 °C
 - Minimum Operating Temperature: -40 °C



1225860 1 mm²

RS PRO PINK 1 MM² AUTOMOTIVE WIRE, 57/0.15 MM, 30M

- ขนาดบรรจุภัณฑ์: **30 x MTR**
- Cross Sectional Area: 1 mm²
 - Sheath Colour: Pink
 - Core Strands: 57/0.15 mm
 - Length: 30 m
 - Outer Diameter: 2.7 mm
 - Voltage Rating: 600 V
 - Maximum Operating Temperature: +100 °C
 - Minimum Operating Temperature: -40 °C



1225864 1 mm²

RS PRO YELLOW 3 MM² AUTOMOTIVE WIRE, 175/0.15 MM, 30M

- ขนาดบรรจุภัณฑ์: **30 x MTR**
- Cross Sectional Area: 3 mm²
 - Sheath Colour: Yellow
 - Core Strands: 175/0.15 mm
 - Length: 30 m
 - Outer Diameter: 4.1 mm
 - Voltage Rating: 600 V
 - Maximum Operating Temperature: +100 °C
 - Minimum Operating Temperature: -40 °C



1225890 3 mm²

RS PRO GREEN 0.2 MM² EQUIPMENT WIRE, 24 AWG, 1/0.51 MM, 50M, ETFE

- ขนาดบรรจุภัณฑ์: **50 x MTR**
- Cross Sectional Area: 0.2 mm²
 - Sheath Colour: Green
 - American Wire Gauge: 24 AWG
 - Core Strands: 1/0.51 mm
 - Length: 50 m
 - Insulation Material: ETFE
 - Voltage Rating: 300 V
 - Maximum Operating Temperature: +160 °C



2077122 0.2 mm²

RS PRO YELLOW 0.2 MM² EQUIPMENT WIRE, 24 AWG, 1/0.51 MM, 50M, ETFE

- ขนาดบรรจุภัณฑ์: **50 x MTR**
- Cross Sectional Area: 0.2 mm²
 - Sheath Colour: Yellow
 - American Wire Gauge: 24 AWG
 - Core Strands: 1/0.51 mm
 - Length: 50 m
 - Insulation Material: ETFE
 - Voltage Rating: 300 V
 - Maximum Operating Temperature: +160 °C



2077123 0.2 mm²

RS PRO ORANGE 0.2 MM² EQUIPMENT WIRE, 24 AWG, 1/0.51

- ขนาดบรรจุภัณฑ์: **50 x MTR**
- Cross Sectional Area: 0.2 mm²
 - Sheath Colour: Orange
 - American Wire Gauge: 24 AWG
 - Core Strands: 1/0.51 mm
 - Length: 50 m
 - Insulation Material: ETFE
 - Voltage Rating: 300 V
 - Maximum Operating Temperature: +160 °C



2077124 0.2 mm²

RS PRO BLUE 0.2 MM² EQUIPMENT WIRE, 24 AWG, 1/0.51 MM, 50M, ETFE

- ขนาดบรรจุภัณฑ์: **50 x MTR**
- Cross Sectional Area: 0.2 mm²
 - Sheath Colour: Blue
 - American Wire Gauge: 24 AWG
 - Core Strands: 1/0.51 mm
 - Length: 50 m
 - Insulation Material: ETFE
 - Voltage Rating: 300 V
 - Maximum Operating Temperature: +160 °C



2077125 0.2 mm²

RS PRO BROWN 0.2 MM² EQUIPMENT WIRE, 24 AWG, 1/0.51 MM, 50M, ETFE

- ขนาดบรรจุภัณฑ์: **50 x MTR**
- Cross Sectional Area: 0.2 mm²
 - Sheath Colour: Brown
 - American Wire Gauge: 24 AWG
 - Core Strands: 1/0.51 mm
 - Length: 50 m
 - Insulation Material: ETFE
 - Voltage Rating: 300 V
 - Maximum Operating Temperature: +160 °C



2077126 0.2 mm²

RS PRO GREY 0.2 MM² EQUIPMENT WIRE, 24 AWG, 1/0.51 MM, 50M, ETFE

- ขนาดบรรจุภัณฑ์: **50 x MTR**
- Cross Sectional Area: 0.2 mm²
 - Sheath Colour: Grey
 - American Wire Gauge: 24 AWG
 - Core Strands: 1/0.51 mm
 - Length: 50 m
 - Insulation Material: ETFE
 - Voltage Rating: 300 V
 - Maximum Operating Temperature: +160 °C



2077127 0.2 mm²

RS PRO PURPLE 0.2 MM² EQUIPMENT WIRE, 24 AWG, 1/0.51 MM, 50M, ETFE

- ขนาดบรรจุภัณฑ์: **50 x MTR**
- Cross Sectional Area: 0.2 mm²
 - Sheath Colour: Purple
 - American Wire Gauge: 24 AWG
 - Core Strands: 1/0.51 mm
 - Length: 50 m
 - Insulation Material: ETFE
 - Voltage Rating: 300 V
 - Maximum Operating Temperature: +160 °C



2077128 0.2 mm²

RS PRO WHITE 0.12 MM² EQUIPMENT WIRE, 26 AWG, 1/0.40 MM, 50M, ETFE

- ขนาดบรรจุภัณฑ์: **50 x MTR**
- Cross Sectional Area: 0.12 mm²
 - Sheath Colour: White
 - American Wire Gauge: 26 AWG
 - Core Strands: 1/0.40 mm
 - Length: 50 m
 - Insulation Material: ETFE
 - Voltage Rating: 300 V
 - Series: RS PRO



2077129 0.12 mm²

RS PRO RED 0.12 MM² EQUIPMENT WIRE, 26 AWG, 1/0.40 MM, 50M, ETFE

- ขนาดบรรจุภัณฑ์: **50 x MTR**
- Cross Sectional Area: 0.12 mm²
 - Sheath Colour: Red
 - American Wire Gauge: 26 AWG
 - Core Strands: 1/0.40 mm
 - Length: 50 m
 - Insulation Material: ETFE
 - Voltage Rating: 300 V
 - Series: RS PRO



2077130 0.12 mm²

RS PRO GREEN 0.12 MM² EQUIPMENT WIRE, 26 AWG, 1/0.40 MM, 50M, ETFE

- ขนาดบรรจุภัณฑ์: **50 x MTR**
- Cross Sectional Area: 0.12 mm²
 - Sheath Colour: Green
 - American Wire Gauge: 26 AWG
 - Core Strands: 1/0.40 mm
 - Length: 50 m
 - Insulation Material: ETFE
 - Voltage Rating: 300 V
 - Maximum Operating Temperature: 160 °C



2077132 0.12 mm²

RS PRO BLACK 0.12 MM² EQUIPMENT WIRE, 26 AWG, 1/0.40 MM, 50M, ETFE

- ขนาดบรรจุภัณฑ์: **50 x MTR**
- Cross Sectional Area: 0.12 mm²
 - Sheath Colour: Black
 - American Wire Gauge: 26 AWG
 - Core Strands: 1/0.40 mm
 - Length: 50 m
 - Insulation Material: ETFE
 - Voltage Rating: 300 V
 - Series: RS PRO



2077133 0.12 mm²

RS PRO YELLOW 0.12 MM² EQUIPMENT WIRE, 26 AWG, 1/0.40

- ขนาดบรรจุภัณฑ์: **50 x MTR**
- Cross Sectional Area: 0.12 mm²
 - Sheath Colour: Yellow
 - American Wire Gauge: 26 AWG
 - Core Strands: 1/0.40 mm
 - Length: 50 m
 - Insulation Material: ETFE
 - Voltage Rating: 300 V
 - Maximum Operating Temperature: 160 °C



2077134 0.12 mm²

RS PRO BLUE 0.12 MM² EQUIPMENT WIRE, 26 AWG, 1/0.40 MM, 50M, ETFE

- ขนาดบรรจุภัณฑ์: **50 x MTR**
- Cross Sectional Area: 0.12 mm²
 - Sheath Colour: Blue
 - American Wire Gauge: 26 AWG
 - Core Strands: 1/0.40 mm
 - Length: 50 m
 - Insulation Material: ETFE
 - Voltage Rating: 300 V
 - Series: RS PRO



2077135 0.12 mm²

RS PRO WHITE 0.08 MM² EQUIPMENT WIRE, 28 AWG, 1/0.32 MM, 50M, ETFE

- ขนาดบรรจุภัณฑ์: **50 x MTR**
- Cross Sectional Area: 0.08 mm²
 - Sheath Colour: White
 - American Wire Gauge: 28 AWG
 - Core Strands: 1/0.32 mm
 - Length: 50 m
 - Insulation Material: ETFE
 - Voltage Rating: 300 V
 - Series: RS PRO



2077136 0.08 mm²

RS PRO BLACK 0.08 MM² EQUIPMENT WIRE, 28 AWG, 1/0.32 MM, 50M, ETFE

- ขนาดบรรจุภัณฑ์: **50 x MTR**
- Cross Sectional Area: 0.08 mm²
 - Sheath Colour: Black
 - American Wire Gauge: 28 AWG
 - Core Strands: 1/0.32 mm
 - Length: 50 m
 - Insulation Material: ETFE
 - Voltage Rating: 300 V
 - Maximum Operating Temperature: 160 °C



2077137 0.08 mm²

RS PRO RED 0.08 MM² EQUIPMENT WIRE, 28 AWG, 1/0.32 MM, 50M, ETFE

- ขนาดบรรจุภัณฑ์: **50 x MTR**
- Cross Sectional Area: 0.08 mm²
 - Sheath Colour: Red
 - American Wire Gauge: 28 AWG
 - Core Strands: 1/0.32 mm
 - Length: 50 m
 - Insulation Material: ETFE
 - Voltage Rating: 300 V
 - Series: RS PRO



2077138 0.08 mm²

RS PRO BLUE 0.08 MM² EQUIPMENT WIRE, 28 AWG, 1/0.32 MM, 50M, ETFE

- ขนาดบรรจุภัณฑ์: **50 x MTR**
- Cross Sectional Area: 0.08 mm²
 - Sheath Colour: Blue
 - American Wire Gauge: 28 AWG
 - Core Strands: 1/0.32 mm
 - Length: 50 m
 - Insulation Material: ETFE
 - Voltage Rating: 300 V
 - Series: RS PRO



2077139 0.08 mm²

RS PRO GREEN 0.08 MM² EQUIPMENT WIRE, 28 AWG, 1/0.32 MM, 50M, ETFE

- ขนาดบรรจุภัณฑ์: **50 x MTR**
- Cross Sectional Area: 0.08 mm²
 - Sheath Colour: Green
 - American Wire Gauge: 28 AWG
 - Core Strands: 1/0.32 mm
 - Length: 50 m
 - Insulation Material: ETFE
 - Voltage Rating: 300 V
 - Maximum Operating Temperature: 160 °C



2077140 0.08 mm²

RS PRO WHITE 0.05 MM² EQUIPMENT WIRE, 30 AWG, 1/0.25 MM, 50M,

- ขนาดบรรจุภัณฑ์: **50 x MTR**
- Cross Sectional Area: 0.05 mm²
 - Sheath Colour: White
 - American Wire Gauge: 30 AWG
 - Core Strands: 1/0.25 mm
 - Length: 50 m
 - Insulation Material: ETFE
 - Voltage Rating: 300 V
 - Series: RS PRO



2077141 0.05 mm²

RS PRO BLACK 0.05 MM² EQUIPMENT WIRE, 30 AWG, 1/0.25 MM, 50M,

- ขนาดบรรจุภัณฑ์: **50 x MTR**
- Cross Sectional Area: 0.05 mm²
 - Sheath Colour: Black
 - American Wire Gauge: 30 AWG
 - Core Strands: 1/0.25 mm
 - Length: 50 m
 - Insulation Material: ETFE
 - Voltage Rating: 300 V
 - Series: RS PRO



2077142 0.05 mm²

RS PRO YELLOW 0.05 MM² EQUIPMENT WIRE, 30 AWG, 1/0.25

- ขนาดบรรจุภัณฑ์: **50 x MTR**
- Cross Sectional Area: 0.05 mm²
 - Sheath Colour: Yellow
 - American Wire Gauge: 30 AWG
 - Core Strands: 1/0.25 mm
 - Length: 50 m
 - Insulation Material: ETFE
 - Voltage Rating: 300 V
 - Series: RS PRO



2077143 0.05 mm²

RS PRO RED 0.05 MM² EQUIPMENT WIRE, 30 AWG, 1/0.25 MM, 50M,

- ขนาดบรรจุภัณฑ์: **50 x MTR**
- Cross Sectional Area: 0.05 mm²
 - Sheath Colour: Red
 - American Wire Gauge: 30 AWG
 - Core Strands: 1/0.25 mm
 - Length: 50 m
 - Insulation Material: ETFE
 - Voltage Rating: 300 V
 - Series: RS PRO



2077144 0.05 mm²

RS PRO GREEN 0.05 MM² EQUIPMENT WIRE, 30 AWG, 1/0.25 MM, 50M,

- ขนาดบรรจุภัณฑ์: **50 x MTR**
- Cross Sectional Area: 0.05 mm²
 - Sheath Colour: Green
 - American Wire Gauge: 30 AWG
 - Core Strands: 1/0.25 mm
 - Length: 50 m
 - Insulation Material: ETFE
 - Voltage Rating: 300 V
 - Series: RS PRO



2077145 0.05 mm²

RS PRO BLUE 0.05 MM² EQUIPMENT WIRE, 30 AWG, 1/0.25 MM, 50M,

- ขนาดบรรจุภัณฑ์: **50 x MTR**
- Cross Sectional Area: 0.05 mm²
 - Sheath Colour: Blue
 - American Wire Gauge: 30 AWG
 - Core Strands: 1/0.25 mm
 - Length: 50 m
 - Insulation Material: ETFE
 - Voltage Rating: 300 V
 - Series: RS PRO



2077146 0.05 mm²

RS PRO BROWN 0.05 MM² EQUIPMENT WIRE, 30 AWG, 1/0.25

- ขนาดบรรจุภัณฑ์: **50 x MTR**
- Cross Sectional Area: 0.05 mm²
 - Sheath Colour: Brown
 - American Wire Gauge: 30 AWG
 - Core Strands: 1/0.25 mm
 - Length: 50 m
 - Insulation Material: ETFE
 - Voltage Rating: 300 V
 - Series: RS PRO



2077148 0.05 mm²

RS PRO ORANGE 0.05 MM² EQUIPMENT WIRE, 30 AWG, 1/0.25

- ขนาดบรรจุภัณฑ์: **50 x MTR**
- Cross Sectional Area: 0.05 mm²
 - Sheath Colour: Orange
 - American Wire Gauge: 30 AWG
 - Core Strands: 1/0.25 mm
 - Length: 50 m
 - Insulation Material: ETFE
 - Voltage Rating: 300 V
 - Maximum Operating Temperature: 160 °C



2077149 0.05 mm²

RS PRO WHITE 0.2 MM² EQUIPMENT WIRE, 24 AWG, 1/0.51 MM, 50M, ETFE

- ขนาดบรรจุภัณฑ์: **50 x MTR**
- Cross Sectional Area: 0.2 mm²
 - Sheath Colour: White
 - American Wire Gauge: 24 AWG
 - Core Strands: 1/0.51 mm
 - Length: 50 m
 - Insulation Material: ETFE
 - Voltage Rating: 300 V
 - Maximum Operating Temperature: +160 °C



2077150 0.2 mm²

RS PRO GREY 0.05 MM² EQUIPMENT WIRE, 30 AWG, 1/0.25 MM, 50M,

- ขนาดบรรจุภัณฑ์: **50 x MTR**
- Cross Sectional Area: 0.05 mm²
 - Sheath Colour: Grey
 - American Wire Gauge: 30 AWG
 - Core Strands: 1/0.25 mm
 - Length: 50 m
 - Insulation Material: ETFE
 - Voltage Rating: 300 V
 - Maximum Operating Temperature: 160 °C



2077151 0.05 mm²

RS PRO PURPLE 0.05 MM² EQUIPMENT WIRE, 30 AWG, 1/0.25

- ขนาดบรรจุภัณฑ์: **50 x MTR**
- Cross Sectional Area: 0.05 mm²
 - Sheath Colour: Purple
 - American Wire Gauge: 30 AWG
 - Core Strands: 1/0.25 mm
 - Length: 50 m
 - Insulation Material: ETFE
 - Voltage Rating: 300 V
 - Maximum Operating Temperature: 160 °C



2077152 0.05 mm²

RS PRO RED 0.2 MM² EQUIPMENT WIRE, 24 AWG, 1/0.51 MM, 50M, ETFE

- ขนาดบรรจุภัณฑ์: **50 x MTR**
- Cross Sectional Area: 0.2 mm²
 - Sheath Colour: Red
 - American Wire Gauge: 24 AWG
 - Core Strands: 1/0.51 mm
 - Length: 50 m
 - Insulation Material: ETFE
 - Voltage Rating: 300 V
 - Minimum Operating Temperature: -65 °C



2077155 0.2 mm²

RS PRO BLACK 0.05 MM² EQUIPMENT WIRE, 30 AWG, 1/0.25 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.05 mm²
 - Sheath Colour: Black
 - American Wire Gauge: 30 AWG
 - Core Strands: 1/0.25 mm
 - Length: 100 m
 - Insulation Material: ETFE
 - Voltage Rating: 300 V
 - Series: RS PRO



2077156 0.05 mm²

RS PRO GREEN 0.05 MM² EQUIPMENT WIRE, 30 AWG, 1/0.25 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.05 mm²
 - Sheath Colour: Green
 - American Wire Gauge: 30 AWG
 - Core Strands: 1/0.25 mm
 - Length: 100 m
 - Insulation Material: ETFE
 - Voltage Rating: 300 V
 - Series: RS PRO



2077157 0.05 mm²

RS PRO WHITE 0.05 MM² EQUIPMENT WIRE, 30 AWG, 1/0.25 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.05 mm²
 - Sheath Colour: White
 - American Wire Gauge: 30 AWG
 - Core Strands: 1/0.25 mm
 - Length: 100 m
 - Insulation Material: ETFE
 - Voltage Rating: 300 V
 - Series: RS PRO



2077158 0.05 mm²

RS PRO RED 0.05 MM² EQUIPMENT WIRE, 30 AWG, 1/0.25 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.05 mm²
 - Sheath Colour: Red
 - American Wire Gauge: 30 AWG
 - Core Strands: 1/0.25 mm
 - Length: 100 m
 - Insulation Material: ETFE
 - Voltage Rating: 300 V
 - Series: RS PRO



2077159 0.05 mm²

RS PRO YELLOW 0.05 MM² EQUIPMENT WIRE, 30 AWG, 1/0.25

- ขนาดบรรจุภัณฑ์: **50 x MTR**
- Cross Sectional Area: 0.05 mm²
 - Sheath Colour: Yellow
 - American Wire Gauge: 30 AWG
 - Core Strands: 1/0.25 mm
 - Length: 50 m
 - Insulation Material: Kynar
 - Voltage Rating: 300 V
 - Outer Diameter: 0.5 mm



2094798 0.05 mm²

RS PRO RED 0.05 MM² HOOK UP WIRE, 30 AWG, 1/0.25 MM, 50M,

- ขนาดบรรจุภัณฑ์: **50 x MTR**
- Cross Sectional Area: 0.05 mm²
 - Sheath Colour: Red
 - American Wire Gauge: 30 AWG
 - Core Strands: 1/0.25 mm
 - Length: 50 m
 - Insulation Material: Kynar
 - Voltage Rating: 300 V
 - Outer Diameter: 0.5 mm



2094811 0.05 mm²

RS PRO WHITE 0.05 MM² EQUIPMENT WIRE, 30 AWG, 1/0.25 MM, 50M,

- ขนาดบรรจุภัณฑ์: **50 x MTR**
- Cross Sectional Area: 0.05 mm²
 - Sheath Colour: White
 - American Wire Gauge: 30 AWG
 - Core Strands: 1/0.25 mm
 - Length: 50 m
 - Insulation Material: Kynar
 - Voltage Rating: 300 V
 - Outer Diameter: 0.5 mm



2094827 0.05 mm²

RS PRO BLACK 0.05 MM² EQUIPMENT WIRE, 30 AWG, 1/0.25 MM, 50M,

- ขนาดบรรจุภัณฑ์: **50 x MTR**
- Cross Sectional Area: 0.05 mm²
 - Sheath Colour: Black
 - American Wire Gauge: 30 AWG
 - Core Strands: 1/0.25 mm
 - Length: 50 m
 - Insulation Material: Kynar
 - Outer Diameter: 0.5 mm
 - Voltage Rating: 300 V



2094849 0.05 mm²

RS PRO RESISTANCE WIRE, 7M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 7 m
 - Outer Diameter: 2.03 mm
 - Maximum Operating Temperature: +1150 °C
 - Conductor Material: Nickel Chrome Alloy



7141717 7 m

RS PRO RESISTANCE WIRE, 36M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 36 m
 - Outer Diameter: 0.91 mm
 - Maximum Operating Temperature: +1150 °C
 - Conductor Material: Nickel Chrome Alloy



7141723 36 m

RS PRO RESISTANCE WIRE, 11.5M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 11.5 m
 - Outer Diameter: 1.63 mm
 - Maximum Operating Temperature: +1150 °C
 - Conductor Material: Nickel Chrome Alloy



7141726 11.5 m

RS PRO RESISTANCE WIRE, 20.5M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 20.5 m
 - Outer Diameter: 1.22 mm
 - Maximum Operating Temperature: +1150 °C
 - Conductor Material: Nickel Chrome Alloy



7141729 20.5 m

RS PRO RESISTANCE WIRE, 60M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 60 m
 - Outer Diameter: 0.71 mm
 - Maximum Operating Temperature: +1150 °C
 - Conductor Material: Nickel Chrome Alloy



7141732 60 m

RS PRO RESISTANCE WIRE, 98M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 98 m
 - Outer Diameter: 0.56 mm
 - Maximum Operating Temperature: +1150 °C
 - Conductor Material: Nickel Chrome Alloy



7141735 98 m

RS PRO RESISTANCE WIRE, 118M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 118 m
 - Outer Diameter: 0.51 mm
 - Maximum Operating Temperature: +1150 °C
 - Conductor Material: Nickel Chrome Alloy



7141739 118 m

RS PRO EQUIPMENT WIRE, 623M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 623 m
 - Outer Diameter: 0.21 mm
 - Maximum Operating Temperature: +1150 °C
 - Conductor Material: Nickel Chrome Alloy



7141741 623 m

RS PRO RESISTANCE WIRE, 237M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 237 m
 - Outer Diameter: 0.35 mm
 - Maximum Operating Temperature: +1150 °C
 - Conductor Material: Nickel Chrome Alloy



7141748 237 m

RS PRO BLACK 0.08 MM² PTFE EQUIPMENT WIRE, 28 AWG, 7/0.12

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.08 mm²
 - Sheath Colour: Black
 - American Wire Gauge: 28 AWG
 - Core Strands: 7/0.12 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Voltage Rating: 300 V
 - Outer Diameter: 0.71 mm



8417131 0.08 mm²

RS PRO PINK 0.08 MM² PTFE EQUIPMENT WIRE, 28 AWG, 7/0.12

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.08 mm²
 - Sheath Colour: Pink
 - American Wire Gauge: 28 AWG
 - Core Strands: 7/0.12 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Voltage Rating: 300 V
 - Outer Diameter: 0.71 mm



8417134 0.08 mm²

RS PRO RED 0.08 MM² PTFE EQUIPMENT WIRE, 28 AWG, 7/0.12

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.08 mm²
 - Sheath Colour: Red
 - American Wire Gauge: 28 AWG
 - Core Strands: 7/0.12 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Voltage Rating: 300 V
 - Outer Diameter: 0.71 mm



8417138 0.08 mm²

RS PRO YELLOW 0.08 MM² PTFE EQUIPMENT WIRE, 28 AWG, 7/0.12

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.08 mm²
 - Sheath Colour: Yellow
 - American Wire Gauge: 28 AWG
 - Core Strands: 7/0.12 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Voltage Rating: 300 V
 - Outer Diameter: 0.71 mm



8417140 0.08 mm²

RS PRO BLUE 0.08 MM² PTFE EQUIPMENT WIRE, 28 AWG, 7/0.12

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.08 mm²
 - Sheath Colour: Blue
 - American Wire Gauge: 28 AWG
 - Core Strands: 7/0.12 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Voltage Rating: 300 V
 - Outer Diameter: 0.71 mm



8417144 0.08 mm²

RS PRO WHITE 0.08 MM² PTFE EQUIPMENT WIRE, 28 AWG, 7/0.12

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.08 mm²
 - Sheath Colour: White
 - American Wire Gauge: 28 AWG
 - Core Strands: 7/0.12 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Voltage Rating: 300 V
 - Outer Diameter: 0.71 mm



8417147 0.08 mm²

RS PRO BROWN 0.08 MM² PTFE EQUIPMENT WIRE, 28 AWG, 7/0.12

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.08 mm²
 - Sheath Colour: Brown
 - American Wire Gauge: 28 AWG
 - Core Strands: 7/0.12 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Voltage Rating: 300 V
 - Outer Diameter: 0.71 mm



8417150 0.08 mm²

RS PRO ORANGE 0.08 MM² PTFE EQUIPMENT WIRE, 28 AWG, 7/0.12

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.08 mm²
 - Sheath Colour: Orange
 - American Wire Gauge: 28 AWG
 - Core Strands: 7/0.12 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Voltage Rating: 300 V
 - Outer Diameter: 0.71 mm



8417153 0.08 mm²

RS PRO GREEN 0.08 MM² PTFE EQUIPMENT WIRE, 28 AWG, 7/0.12

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.08 mm²
 - Sheath Colour: Green
 - American Wire Gauge: 28 AWG
 - Core Strands: 7/0.12 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Outer Diameter: 0.71 mm
 - Voltage Rating: 300 V



8417156 0.08 mm²

RS PRO GREY 0.08 MM² PTFE EQUIPMENT WIRE, 28 AWG, 7/0.12

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.08 mm²
 - Sheath Colour: Grey
 - American Wire Gauge: 28 AWG
 - Core Strands: 7/0.12 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Voltage Rating: 300 V
 - Outer Diameter: 0.71 mm



8417162 0.08 mm²

RS PRO BLACK 0.12 MM² PTFE EQUIPMENT WIRE, 26 AWG, 7/0.15

- ขนาดบรรจุภัณฑ์: **25 x MTR**
- Cross Sectional Area: 0.12 mm²
 - Sheath Colour: Black
 - American Wire Gauge: 26 AWG
 - Core Strands: 7/0.15 mm
 - Length: 25 m
 - Insulation Material: PTFE
 - Voltage Rating: 300 V
 - Outer Diameter: 0.8 mm



8417166 0.12 mm²

RS PRO PURPLE 0.08 MM² PTFE EQUIPMENT WIRE, 28 AWG, 7/0.12

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.08 mm²
 - Sheath Colour: Purple
 - American Wire Gauge: 28 AWG
 - Core Strands: 7/0.12 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Voltage Rating: 300 V
 - Outer Diameter: 0.71 mm



8417169 0.08 mm²

RS PRO WHITE 0.12 MM² PTFE EQUIPMENT WIRE, 26 AWG, 7/0.15

- ขนาดบรรจุภัณฑ์: **25 x MTR**
- Cross Sectional Area: 0.12 mm²
 - Sheath Colour: White
 - American Wire Gauge: 26 AWG
 - Core Strands: 7/0.15 mm
 - Length: 25 m
 - Insulation Material: PTFE
 - Voltage Rating: 300 V
 - Outer Diameter: 0.8 mm



8417172 0.12 mm²

RS PRO RED 0.12 MM² PTFE EQUIPMENT WIRE, 26 AWG, 7/0.15

- ขนาดบรรจุภัณฑ์: **25 x MTR**
- Cross Sectional Area: 0.12 mm²
 - Sheath Colour: Red
 - American Wire Gauge: 26 AWG
 - Core Strands: 7/0.15 mm
 - Length: 25 m
 - Insulation Material: PTFE
 - Voltage Rating: 300 V
 - Outer Diameter: 0.8 mm



8417178 0.12 mm²

RS PRO BLACK 0.12 MM² PTFE EQUIPMENT WIRE, 26 AWG, 7/0.15

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.12 mm²
 - Sheath Colour: Black
 - American Wire Gauge: 26 AWG
 - Core Strands: 7/0.15 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Voltage Rating: 300 V
 - Outer Diameter: 0.8 mm



8417181 0.12 mm²

RS PRO PINK 0.12 MM² PTFE EQUIPMENT WIRE, 26 AWG, 7/0.15

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.12 mm²
 - Sheath Colour: Pink
 - American Wire Gauge: 26 AWG
 - Core Strands: 7/0.15 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Outer Diameter: 0.8 mm
 - Voltage Rating: 300 V



8417184 0.12 mm²

RS PRO RED 0.12 MM² PTFE EQUIPMENT WIRE, 26 AWG, 7/0.15

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.12 mm²
 - Sheath Colour: Red
 - American Wire Gauge: 26 AWG
 - Core Strands: 7/0.15 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Voltage Rating: 300 V
 - Outer Diameter: 0.8 mm



8417188 0.12 mm²

RS PRO BLUE 0.12 MM² PTFE EQUIPMENT WIRE, 26 AWG, 7/0.15

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.12 mm²
 - Sheath Colour: Blue
 - American Wire Gauge: 26 AWG
 - Core Strands: 7/0.15 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Voltage Rating: 300 V
 - Outer Diameter: 0.8 mm



8417190 0.12 mm²

RS PRO GREEN 0.12 MM² PTFE EQUIPMENT WIRE, 26 AWG, 7/0.15

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.12 mm²
 - Sheath Colour: Green
 - American Wire Gauge: 26 AWG
 - Core Strands: 7/0.15 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Voltage Rating: 300 V
 - Outer Diameter: 0.8 mm



8417194 0.12 mm²

RS PRO WHITE 0.12 MM² PTFE EQUIPMENT WIRE, 26 AWG, 7/0.15

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.12 mm²
 - Sheath Colour: White
 - American Wire Gauge: 26 AWG
 - Core Strands: 7/0.15 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Voltage Rating: 300 V
 - Outer Diameter: 0.8 mm



8417197 0.12 mm²

RS PRO PURPLE 0.12 MM² PTFE EQUIPMENT WIRE, 26 AWG, 7/0.15

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.12 mm²
 - Sheath Colour: Purple
 - American Wire Gauge: 26 AWG
 - Core Strands: 7/0.15 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Voltage Rating: 300 V
 - Outer Diameter: 0.8 mm



8417201 0.12 mm²

RS PRO YELLOW 0.12 MM² PTFE EQUIPMENT WIRE, 26 AWG, 7/0.15

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.12 mm²
 - Sheath Colour: Yellow
 - American Wire Gauge: 26 AWG
 - Core Strands: 7/0.15 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Voltage Rating: 300 V
 - Outer Diameter: 0.8 mm



8417204 0.12 mm²

RS PRO BROWN 0.12 MM² PTFE EQUIPMENT WIRE, 26 AWG, 7/0.15

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.12 mm²
 - Sheath Colour: Brown
 - American Wire Gauge: 26 AWG
 - Core Strands: 7/0.15 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Voltage Rating: 300 V
 - Outer Diameter: 0.8 mm



8417207 0.12 mm²

RS PRO ORANGE 0.12 MM² PTFE EQUIPMENT WIRE, 26 AWG, 7/0.15

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.12 mm²
 - Sheath Colour: Orange
 - American Wire Gauge: 26 AWG
 - Core Strands: 7/0.15 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Outer Diameter: 0.8 mm
 - Voltage Rating: 300 V



8417210 0.12 mm²

RS PRO BLACK 0.22 MM² PTFE EQUIPMENT WIRE, 24 AWG, 7/0.2

- ขนาดบรรจุภัณฑ์: **25 x MTR**
- Cross Sectional Area: 0.22 mm²
 - Sheath Colour: Black
 - American Wire Gauge: 24 AWG
 - Core Strands: 7/0.2 mm
 - Length: 25 m
 - Insulation Material: PTFE
 - Outer Diameter: 0.95 mm
 - Voltage Rating: 300 V



8417213 0.22 mm²

RS PRO BLACK 0.22 MM² PTFE EQUIPMENT WIRE, 24 AWG, 7/0.2

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.22 mm²
 - Sheath Colour: Black
 - American Wire Gauge: 24 AWG
 - Core Strands: 7/0.2 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Voltage Rating: 300 V
 - Outer Diameter: 0.95 mm



8417223 0.22 mm²

RS PRO RED 0.22 MM² PTFE EQUIPMENT WIRE, 24 AWG, 7/0.2

- ขนาดบรรจุภัณฑ์: **25 x MTR**
- Cross Sectional Area: 0.22 mm²
 - Sheath Colour: Red
 - American Wire Gauge: 24 AWG
 - Core Strands: 7/0.2 mm
 - Length: 25 m
 - Insulation Material: PTFE
 - Voltage Rating: 300 V
 - Outer Diameter: 0.95 mm



8417226 0.22 mm²

RS PRO WHITE 0.22 MM² PTFE EQUIPMENT WIRE, 24 AWG, 7/0.2

- ขนาดบรรจุภัณฑ์: **25 x MTR**
- Cross Sectional Area: 0.22 mm²
 - Sheath Colour: White
 - American Wire Gauge: 24 AWG
 - Core Strands: 7/0.2 mm
 - Length: 25 m
 - Insulation Material: PTFE
 - Voltage Rating: 300 V
 - Outer Diameter: 0.95 mm



8417229 0.22 mm²

RS PRO PINK 0.22 MM² PTFE EQUIPMENT WIRE, 24 AWG, 7/0.2

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.22 mm²
 - Sheath Colour: Pink
 - American Wire Gauge: 24 AWG
 - Core Strands: 7/0.2 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Voltage Rating: 300 V
 - Outer Diameter: 0.95 mm



8417232 0.22 mm²

RS PRO RED 0.22 MM² PTFE EQUIPMENT WIRE, 24 AWG, 7/0.2

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.22 mm²
 - Sheath Colour: Red
 - American Wire Gauge: 24 AWG
 - Core Strands: 7/0.2 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Voltage Rating: 300 V
 - Outer Diameter: 0.95 mm



8417235 0.22 mm²

RS PRO BLUE 0.22 MM² PTFE EQUIPMENT WIRE, 24 AWG, 7/0.2

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.22 mm²
 - Sheath Colour: Blue
 - American Wire Gauge: 24 AWG
 - Core Strands: 7/0.2 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Outer Diameter: 0.95 mm
 - Voltage Rating: 300 V



8417241 0.22 mm²

RS PRO ORANGE 0.22 MM² PTFE EQUIPMENT WIRE, 24 AWG, 7/0.2

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.22 mm²
 - Sheath Colour: Orange
 - American Wire Gauge: 24 AWG
 - Core Strands: 7/0.2 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Voltage Rating: 300 V
 - Outer Diameter: 0.95 mm



8417245 0.22 mm²

RS PRO YELLOW 0.22 MM² PTFE EQUIPMENT WIRE, 24 AWG, 7/0.2

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.22 mm²
 - Sheath Colour: Yellow
 - American Wire Gauge: 24 AWG
 - Core Strands: 7/0.2 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Voltage Rating: 300 V
 - Outer Diameter: 0.95 mm



8417248 0.22 mm²

RS PRO PURPLE 0.22 MM² PTFE EQUIPMENT WIRE, 24 AWG, 7/0.2

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.22 mm²
 - Sheath Colour: Purple
 - American Wire Gauge: 24 AWG
 - Core Strands: 7/0.2 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Voltage Rating: 300 V
 - Outer Diameter: 0.95 mm



8417251 0.22 mm²

RS PRO GREEN 0.22 MM² PTFE EQUIPMENT WIRE, 24 AWG, 7/0.2

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.22 mm²
 - Sheath Colour: Green
 - American Wire Gauge: 24 AWG
 - Core Strands: 7/0.2 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Voltage Rating: 300 V
 - Outer Diameter: 0.95 mm



8417254 0.22 mm²

RS PRO BROWN 0.22 MM² PTFE EQUIPMENT WIRE, 24 AWG, 7/0.2

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.22 mm²
 - Sheath Colour: Brown
 - American Wire Gauge: 24 AWG
 - Core Strands: 7/0.2 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Voltage Rating: 300 V
 - Outer Diameter: 0.95 mm



8417257 0.22 mm²

RS PRO GREY 0.22 MM² PTFE EQUIPMENT WIRE, 24 AWG, 7/0.2

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.22 mm²
 - Sheath Colour: Grey
 - American Wire Gauge: 24 AWG
 - Core Strands: 7/0.2 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Voltage Rating: 300 V
 - Outer Diameter: 0.95 mm



8417260 0.22 mm²

RS PRO BLACK 0.34 MM² PTFE EQUIPMENT WIRE, 22 AWG, 19/0.15

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.34 mm²
 - Sheath Colour: Black
 - American Wire Gauge: 22 AWG
 - Core Strands: 19/0.15 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Voltage Rating: 300 V
 - Outer Diameter: 1.1 mm



8417263 0.34 mm²

RS PRO PINK 0.34 MM² PTFE EQUIPMENT WIRE, 22 AWG, 19/0.15

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.34 mm²
 - Sheath Colour: Pink
 - American Wire Gauge: 22 AWG
 - Core Strands: 19/0.15 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Voltage Rating: 300 V
 - Outer Diameter: 1.1 mm



8417267 0.34 mm²

RS PRO YELLOW 0.34 MM² PTFE EQUIPMENT WIRE, 22 AWG, 19/0.15

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.34 mm²
 - Sheath Colour: Yellow
 - American Wire Gauge: 22 AWG
 - Core Strands: 19/0.15 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Voltage Rating: 300 V
 - Outer Diameter: 1.1 mm



8417273 0.34 mm²

RS PRO RED 0.34 MM² PTFE EQUIPMENT WIRE, 22 AWG, 19/0.15

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.34 mm²
 - Sheath Colour: Red
 - American Wire Gauge: 22 AWG
 - Core Strands: 19/0.15 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Outer Diameter: 1.1 mm
 - Voltage Rating: 300 V



8417276 0.34 mm²

RS PRO WHITE 0.34 MM² PTFE EQUIPMENT WIRE, 22 AWG, 19/0.15

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.34 mm²
 - Sheath Colour: White
 - American Wire Gauge: 22 AWG
 - Core Strands: 19/0.15 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Voltage Rating: 300 V
 - Outer Diameter: 1.1 mm



8417279 0.34 mm²

RS PRO BLUE 0.34 MM² PTFE EQUIPMENT WIRE, 22 AWG, 19/0.15

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.34 mm²
 - Sheath Colour: Blue
 - American Wire Gauge: 22 AWG
 - Core Strands: 19/0.15 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Voltage Rating: 300 V
 - Outer Diameter: 1.1 mm



8417282 0.34 mm²

RS PRO ORANGE 0.34 MM² PTFE EQUIPMENT WIRE, 22 AWG, 19/0.15

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.34 mm²
 - Sheath Colour: Orange
 - American Wire Gauge: 22 AWG
 - Core Strands: 19/0.15 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Voltage Rating: 300 V
 - Outer Diameter: 1.1 mm



8417285 0.34 mm²

RS PRO GREEN 0.34 MM² PTFE EQUIPMENT WIRE, 22 AWG, 19/0.15

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.34 mm²
 - Sheath Colour: Green
 - American Wire Gauge: 22 AWG
 - Core Strands: 19/0.15 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Voltage Rating: 300 V
 - Outer Diameter: 1.1 mm



8417289 0.34 mm²

RS PRO PURPLE 0.34 MM² PTFE EQUIPMENT WIRE, 22 AWG, 19/0.15

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.34 mm²
 - Sheath Colour: Purple
 - American Wire Gauge: 22 AWG
 - Core Strands: 19/0.15 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Voltage Rating: 300 V
 - Outer Diameter: 1.1 mm



8417291 0.34 mm²

RS PRO BROWN 0.34 MM² PTFE EQUIPMENT WIRE, 22 AWG, 19/0.15

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.34 mm²
 - Sheath Colour: Brown
 - American Wire Gauge: 22 AWG
 - Core Strands: 19/0.15 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Voltage Rating: 300 V
 - Outer Diameter: 1.1 mm



8417298 0.34 mm²

RS PRO RED 0.6 MM² PTFE EQUIPMENT WIRE, 20 AWG, 19/0.2

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.6 mm²
 - Sheath Colour: Red
 - American Wire Gauge: 20 AWG
 - Core Strands: 19/0.2 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Voltage Rating: 300 V
 - Outer Diameter: 1.35 mm



8417302 0.6 mm²

RS PRO BLACK 0.6 MM² PTFE EQUIPMENT WIRE, 20 AWG, 19/0.2

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.6 mm²
 - Sheath Colour: Black
 - American Wire Gauge: 20 AWG
 - Core Strands: 19/0.2 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Voltage Rating: 300 V
 - Outer Diameter: 1.35 mm



8417305 0.6 mm²

RS PRO PINK 0.6 MM² PTFE EQUIPMENT WIRE, 20 AWG, 19/0.2

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.6 mm²
 - Sheath Colour: Pink
 - American Wire Gauge: 20 AWG
 - Core Strands: 19/0.2 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Voltage Rating: 300 V
 - Outer Diameter: 1.35 mm



8417308 0.6 mm²

RS PRO WHITE 0.6 MM² PTFE EQUIPMENT WIRE, 20 AWG, 19/0.2

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.6 mm²
 - Sheath Colour: White
 - American Wire Gauge: 20 AWG
 - Core Strands: 19/0.2 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Voltage Rating: 300 V
 - Outer Diameter: 1.35 mm



8417311 0.6 mm²

RS PRO YELLOW 0.6 MM² PTFE EQUIPMENT WIRE, 20 AWG, 19/0.2

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.6 mm²
 - Sheath Colour: Yellow
 - American Wire Gauge: 20 AWG
 - Core Strands: 19/0.2 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Voltage Rating: 300 V
 - Outer Diameter: 1.35 mm



8417314 0.6 mm²

RS PRO BLUE 0.6 MM² PTFE EQUIPMENT WIRE, 20 AWG, 19/0.2

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.6 mm²
 - Sheath Colour: Blue
 - American Wire Gauge: 20 AWG
 - Core Strands: 19/0.2 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Outer Diameter: 1.35 mm
 - Voltage Rating: 300 V



8417318 0.6 mm²

RS PRO GREEN 0.6 MM² PTFE EQUIPMENT WIRE, 20 AWG, 19/0.2

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.6 mm²
 - Sheath Colour: Green
 - American Wire Gauge: 20 AWG
 - Core Strands: 19/0.2 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Voltage Rating: 300 V
 - Outer Diameter: 1.35 mm



8417320 0.6 mm²

RS PRO BROWN 0.6 MM² PTFE EQUIPMENT WIRE, 20 AWG, 19/0.2

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.6 mm²
 - Sheath Colour: Brown
 - American Wire Gauge: 20 AWG
 - Core Strands: 19/0.2 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Voltage Rating: 300 V
 - Outer Diameter: 1.35 mm



8417324 0.6 mm²

RS PRO ORANGE 0.6 MM² PTFE EQUIPMENT WIRE, 20 AWG, 19/0.2

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.6 mm²
 - Sheath Colour: Orange
 - American Wire Gauge: 20 AWG
 - Core Strands: 19/0.2 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Voltage Rating: 300 V
 - Outer Diameter: 1.35 mm



8417327 0.6 mm²

RS PRO BLACK 0.22 MM² PTFE EQUIPMENT WIRE, 24 AWG, 7/0.2

- ขนาดบรรจุภัณฑ์: **25 x MTR**
- Cross Sectional Area: 0.22 mm²
 - Sheath Colour: Black
 - American Wire Gauge: 24 AWG
 - Core Strands: 7/0.2 mm
 - Length: 25 m
 - Insulation Material: PTFE
 - Voltage Rating: 600 V
 - Outer Diameter: 1.2 mm



8417330 0.22 mm²

RS PRO PURPLE 0.6 MM² PTFE EQUIPMENT WIRE, 20 AWG, 19/0.2

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.6 mm²
 - Sheath Colour: Purple
 - American Wire Gauge: 20 AWG
 - Core Strands: 19/0.2 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Voltage Rating: 300 V
 - Outer Diameter: 1.35 mm



8417333 0.6 mm²

RS PRO GREY 0.6 MM² PTFE EQUIPMENT WIRE, 20 AWG, 19/0.2

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.6 mm²
 - Sheath Colour: Grey
 - American Wire Gauge: 20 AWG
 - Core Strands: 19/0.2 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Voltage Rating: 300 V
 - Outer Diameter: 1.35 mm



8417336 0.6 mm²

RS PRO RED 0.22 MM² PTFE EQUIPMENT WIRE, 24 AWG, 7/0.2

- ขนาดบรรจุภัณฑ์: **25 x MTR**
- Cross Sectional Area: 0.22 mm²
 - Sheath Colour: Red
 - American Wire Gauge: 24 AWG
 - Core Strands: 7/0.2 mm
 - Length: 25 m
 - Insulation Material: PTFE
 - Voltage Rating: 600 V
 - Outer Diameter: 1.2 mm



8417342 0.22 mm²

RS PRO YELLOW 0.22 MM² PTFE EQUIPMENT WIRE, 24 AWG, 7/0.2

- ขนาดบรรจุภัณฑ์: **25 x MTR**
- Cross Sectional Area: 0.22 mm²
 - Sheath Colour: Yellow
 - American Wire Gauge: 24 AWG
 - Core Strands: 7/0.2 mm
 - Length: 25 m
 - Insulation Material: PTFE
 - Voltage Rating: 600 V
 - Outer Diameter: 1.2 mm



8417346 0.22 mm²

RS PRO PINK 0.22 MM² PTFE EQUIPMENT WIRE, 24 AWG, 7/0.2

- ขนาดบรรจุภัณฑ์: **25 x MTR**
- Cross Sectional Area: 0.22 mm²
 - Sheath Colour: Pink
 - American Wire Gauge: 24 AWG
 - Core Strands: 7/0.2 mm
 - Length: 25 m
 - Insulation Material: PTFE
 - Voltage Rating: 600 V
 - Outer Diameter: 1.2 mm



8417349 0.22 mm²

RS PRO RED 0.22 MM² PTFE EQUIPMENT WIRE, 24 AWG, 7/0.2

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.22 mm²
 - Sheath Colour: Red
 - American Wire Gauge: 24 AWG
 - Core Strands: 7/0.2 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Voltage Rating: 600 V
 - Outer Diameter: 1.2 mm



8417352 0.22 mm²

RS PRO BLACK 0.22 MM² PTFE EQUIPMENT WIRE, 24 AWG, 7/0.2

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.22 mm²
 - Sheath Colour: Black
 - American Wire Gauge: 24 AWG
 - Core Strands: 7/0.2 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Voltage Rating: 600 V
 - Outer Diameter: 1.2 mm



8417355 0.22 mm²

RS PRO PINK 0.22 MM² PTFE EQUIPMENT WIRE, 24 AWG, 7/0.2

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.22 mm²
 - Sheath Colour: Pink
 - American Wire Gauge: 24 AWG
 - Core Strands: 7/0.2 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Voltage Rating: 600 V
 - Outer Diameter: 1.2 mm



8417358 0.22 mm²

RS PRO WHITE 0.22 MM² PTFE EQUIPMENT WIRE, 24 AWG, 7/0.2

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.22 mm²
 - Sheath Colour: White
 - American Wire Gauge: 24 AWG
 - Core Strands: 7/0.2 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Voltage Rating: 600 V
 - Outer Diameter: 1.2 mm



8417361 0.22 mm²

RS PRO YELLOW 0.22 MM² PTFE EQUIPMENT WIRE, 24 AWG, 7/0.2

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.22 mm²
 - Sheath Colour: Yellow
 - American Wire Gauge: 24 AWG
 - Core Strands: 7/0.2 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Voltage Rating: 600 V
 - Outer Diameter: 1.2 mm



8417364 0.22 mm²

RS PRO BLUE 0.22 MM² PTFE EQUIPMENT WIRE, 24 AWG, 7/0.2

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.22 mm²
 - Sheath Colour: Blue
 - American Wire Gauge: 24 AWG
 - Core Strands: 7/0.2 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Voltage Rating: 600 V
 - Outer Diameter: 1.2 mm



8417370 0.22 mm²

RS PRO GREEN 0.22 MM² PTFE EQUIPMENT WIRE, 24 AWG, 7/0.2

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.22 mm²
 - Sheath Colour: Green
 - American Wire Gauge: 24 AWG
 - Core Strands: 7/0.2 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Voltage Rating: 600 V
 - Outer Diameter: 1.2 mm



8417374 0.22 mm²

RS PRO ORANGE 0.22 MM² PTFE EQUIPMENT WIRE, 24 AWG, 7/0.2

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.22 mm²
 - Sheath Colour: Orange
 - American Wire Gauge: 24 AWG
 - Core Strands: 7/0.2 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Voltage Rating: 600 V
 - Outer Diameter: 1.2 mm



8417377 0.22 mm²

RS PRO GREY 0.22 MM² PTFE EQUIPMENT WIRE, 24 AWG, 7/0.2

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.22 mm²
 - Sheath Colour: Grey
 - American Wire Gauge: 24 AWG
 - Core Strands: 7/0.2 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Voltage Rating: 600 V
 - Outer Diameter: 1.2 mm



8417380 0.22 mm²

RS PRO BROWN 0.22 MM² PTFE EQUIPMENT WIRE, 24 AWG, 7/0.2

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.22 mm²
 - Sheath Colour: Brown
 - American Wire Gauge: 24 AWG
 - Core Strands: 7/0.2 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Voltage Rating: 600 V
 - Outer Diameter: 1.2 mm



8417383 0.22 mm²

RS PRO PURPLE 0.22 MM² PTFE EQUIPMENT WIRE, 24 AWG, 7/0.2

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.22 mm²
 - Sheath Colour: Purple
 - American Wire Gauge: 24 AWG
 - Core Strands: 7/0.2 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Voltage Rating: 600 V
 - Outer Diameter: 1.2 mm



8417386 0.22 mm²

RS PRO PINK 0.34 MM² PTFE EQUIPMENT WIRE, 22 AWG, 19/0.15

- ขนาดบรรจุภัณฑ์: **25 x MTR**
- Cross Sectional Area: 0.34 mm²
 - Sheath Colour: Pink
 - American Wire Gauge: 22 AWG
 - Core Strands: 19/0.15 mm
 - Length: 25 m
 - Insulation Material: PTFE
 - Voltage Rating: 600 V
 - Outer Diameter: 1.35 mm



8417392 0.34 mm²

RS PRO RED 0.34 MM² PTFE EQUIPMENT WIRE, 22 AWG, 19/0.15

- ขนาดบรรจุภัณฑ์: **25 x MTR**
- Cross Sectional Area: 0.34 mm²
 - Sheath Colour: Red
 - American Wire Gauge: 22 AWG
 - Core Strands: 19/0.15 mm
 - Length: 25 m
 - Insulation Material: PTFE
 - Voltage Rating: 600 V
 - Outer Diameter: 1.35 mm



8417396 0.34 mm²

RS PRO BLACK 0.34 MM² PTFE EQUIPMENT WIRE, 22 AWG, 19/0.15

- ขนาดบรรจุภัณฑ์: **25 x MTR**
- Cross Sectional Area: 0.34 mm²
 - Sheath Colour: Black
 - American Wire Gauge: 22 AWG
 - Core Strands: 19/0.15 mm
 - Length: 25 m
 - Insulation Material: PTFE
 - Voltage Rating: 600 V
 - Outer Diameter: 1.35 mm



8417399 0.34 mm²

RS PRO YELLOW 0.34 MM² PTFE EQUIPMENT WIRE, 22 AWG, 19/0.15

- ขนาดบรรจุภัณฑ์: **25 x MTR**
- Cross Sectional Area: 0.34 mm²
 - Sheath Colour: Yellow
 - American Wire Gauge: 22 AWG
 - Core Strands: 19/0.15 mm
 - Length: 25 m
 - Insulation Material: PTFE
 - Voltage Rating: 600 V
 - Outer Diameter: 1.35 mm



8417406 0.34 mm²

RS PRO BLACK 0.34 MM² PTFE EQUIPMENT WIRE, 22 AWG, 19/0.15

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.34 mm²
 - Sheath Colour: Black
 - American Wire Gauge: 22 AWG
 - Core Strands: 19/0.15 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Outer Diameter: 1.35 mm
 - Voltage Rating: 600 V



8417409 0.34 mm²

RS PRO RED 0.34 MM² PTFE EQUIPMENT WIRE, 22 AWG, 19/0.15

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.34 mm²
 - Sheath Colour: Red
 - American Wire Gauge: 22 AWG
 - Core Strands: 19/0.15 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Voltage Rating: 600 V
 - Outer Diameter: 1.35 mm



8417412 0.34 mm²

RS PRO WHITE 0.34 MM² PTFE EQUIPMENT WIRE, 22 AWG, 19/0.15

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.34 mm²
 - Sheath Colour: White
 - American Wire Gauge: 22 AWG
 - Core Strands: 19/0.15 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Voltage Rating: 600 V
 - Outer Diameter: 1.35 mm



8417415 0.34 mm²

RS PRO YELLOW 0.34 MM² PTFE EQUIPMENT WIRE, 22 AWG, 19/0.15

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.34 mm²
 - Sheath Colour: Yellow
 - American Wire Gauge: 22 AWG
 - Core Strands: 19/0.15 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Voltage Rating: 600 V
 - Outer Diameter: 1.35 mm



8417419 0.34 mm²

RS PRO BLUE 0.34 MM² PTFE EQUIPMENT WIRE, 22 AWG, 19/0.15

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.34 mm²
 - Sheath Colour: Blue
 - American Wire Gauge: 22 AWG
 - Core Strands: 19/0.15 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Voltage Rating: 600 V
 - Outer Diameter: 1.35 mm



8417421 0.34 mm²

RS PRO GREEN 0.34 MM² PTFE EQUIPMENT WIRE, 22 AWG, 19/0.15

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.34 mm²
 - Sheath Colour: Green
 - American Wire Gauge: 22 AWG
 - Core Strands: 19/0.15 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Outer Diameter: 1.35 mm
 - Voltage Rating: 600 V



8417425 0.34 mm²

RS PRO ORANGE 0.34 MM² PTFE EQUIPMENT WIRE, 22 AWG, 19/0.15

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.34 mm²
 - Sheath Colour: Orange
 - American Wire Gauge: 22 AWG
 - Core Strands: 19/0.15 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Voltage Rating: 600 V
 - Outer Diameter: 1.35 mm



8417428 0.34 mm²

RS PRO BLACK 0.6 MM² PTFE EQUIPMENT WIRE, 20 AWG, 19/0.2

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.6 mm²
 - Sheath Colour: Black
 - American Wire Gauge: 20 AWG
 - Core Strands: 19/0.2 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Voltage Rating: 600 V
 - Outer Diameter: 1.6 mm



8417431 0.6 mm²

RS PRO BROWN 0.34 MM² PTFE EQUIPMENT WIRE, 22 AWG, 19/0.15

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.34 mm²
 - Sheath Colour: Brown
 - American Wire Gauge: 22 AWG
 - Core Strands: 19/0.15 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Voltage Rating: 600 V
 - Outer Diameter: 1.35 mm



8417434 0.34 mm²

RS PRO GREY 0.34 MM² PTFE EQUIPMENT WIRE, 22 AWG, 19/0.15

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.34 mm²
 - Sheath Colour: Grey
 - American Wire Gauge: 22 AWG
 - Core Strands: 19/0.15 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Voltage Rating: 600 V
 - Outer Diameter: 1.35 mm



8417437 0.34 mm²

RS PRO RED 0.6 MM² PTFE EQUIPMENT WIRE, 20 AWG, 19/0.2

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.6 mm²
 - Sheath Colour: Red
 - American Wire Gauge: 20 AWG
 - Core Strands: 19/0.2 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Voltage Rating: 600 V
 - Outer Diameter: 1.6 mm



8417443 0.6 mm²

RS PRO WHITE 0.6 MM² PTFE EQUIPMENT WIRE, 20 AWG, 19/0.2

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.6 mm²
 - Sheath Colour: White
 - American Wire Gauge: 20 AWG
 - Core Strands: 19/0.2 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Voltage Rating: 600 V
 - Outer Diameter: 1.6 mm



8417447 0.6 mm²

RS PRO BLUE 0.6 MM² PTFE EQUIPMENT WIRE, 20 AWG, 19/0.2

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.6 mm²
 - Sheath Colour: Blue
 - American Wire Gauge: 20 AWG
 - Core Strands: 19/0.2 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Outer Diameter: 1.6 mm
 - Voltage Rating: 600 V



8417453 0.6 mm²

RS PRO ORANGE 0.6 MM² PTFE EQUIPMENT WIRE, 20 AWG, 19/0.2

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.6 mm²
 - Sheath Colour: Orange
 - American Wire Gauge: 20 AWG
 - Core Strands: 19/0.2 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Voltage Rating: 600 V
 - Outer Diameter: 1.6 mm



8417459 0.6 mm²

RS PRO GREEN 0.6 MM² PTFE EQUIPMENT WIRE, 20 AWG, 19/0.2

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.6 mm²
 - Sheath Colour: Green
 - American Wire Gauge: 20 AWG
 - Core Strands: 19/0.2 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Voltage Rating: 600 V
 - Outer Diameter: 1.6 mm



8417462 0.6 mm²

RS PRO BROWN 0.6 MM² HARSH ENVIRONMENT WIRE, 20 AWG, 19/0.2

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.6 mm²
 - Sheath Colour: Brown
 - American Wire Gauge: 20 AWG
 - Core Strands: 19/0.2 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Voltage Rating: 600 V
 - Outer Diameter: 1.6 mm



8417465 0.6 mm²

RS PRO PURPLE 0.6 MM² HARSH ENVIRONMENT WIRE, 20 AWG, 19/0.2

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.6 mm²
 - Sheath Colour: Purple
 - American Wire Gauge: 20 AWG
 - Core Strands: 19/0.2 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Voltage Rating: 600 V
 - Outer Diameter: 1.6 mm



8417469 0.6 mm²

RS PRO PINK 3 MM² HARSH ENVIRONMENT WIRE, 12 AWG,

- ขนาดบรรจุภัณฑ์: **25 x MTR**
- Cross Sectional Area: 3 mm²
 - Sheath Colour: Pink
 - American Wire Gauge: 12 AWG
 - Core Strands: 19/0.45 mm
 - Length: 25 m
 - Insulation Material: PTFE
 - Voltage Rating: 1 kV
 - Outer Diameter: 3.31 mm



8417471 3 mm²

RS PRO GREY 0.6 MM² HARSH ENVIRONMENT WIRE, 20 AWG, 19/0.2

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.6 mm²
 - Sheath Colour: Grey
 - American Wire Gauge: 20 AWG
 - Core Strands: 19/0.2 mm
 - Length: 100 m
 - Insulation Material: PTFE
 - Outer Diameter: 1.6 mm
 - Voltage Rating: 600 V



8417478 0.6 mm²

RS PRO YELLOW 0.2 MM² HOOK UP WIRE, 24 AWG, 17/0.16 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Cross Sectional Area: 0.2 mm²
 - Sheath Colour: Yellow
 - American Wire Gauge: 24 AWG
 - Core Strands: 17/0.16 mm
 - Length: 100 m
 - Insulation Material: XLPE
 - Voltage Rating: 600 V
 - Outer Diameter: 2.2 mm



8724379 0.2 mm²

RS PRO RED 0.33 MM² HOOK UP WIRE, 22 AWG, 17/0.16 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Cross Sectional Area: 0.33 mm²
 - Sheath Colour: Red
 - American Wire Gauge: 22 AWG
 - Core Strands: 17/0.16 mm
 - Length: 100 m
 - Insulation Material: XLPE
 - Voltage Rating: 600 V
 - Outer Diameter: 2.4 mm



8724391 0.33 mm²

RS PRO BLACK 0.33 MM² HOOK UP WIRE, 22 AWG, 17/0.16 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Cross Sectional Area: 0.33 mm²
 - Sheath Colour: Black
 - American Wire Gauge: 22 AWG
 - Core Strands: 17/0.16 mm
 - Length: 100 m
 - Insulation Material: XLPE
 - Voltage Rating: 600 V
 - Outer Diameter: 2.4 mm



8724394 0.33 mm²

RS PRO WHITE 0.33 MM² HOOK UP WIRE, 22 AWG, 17/0.16 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Cross Sectional Area: 0.33 mm²
 - Sheath Colour: White
 - American Wire Gauge: 22 AWG
 - Core Strands: 17/0.16 mm
 - Length: 100 m
 - Insulation Material: XLPE
 - Voltage Rating: 600 V
 - Outer Diameter: 2.4 mm



8724404 0.33 mm²

RS PRO BROWN 0.08 MM² HOOK UP WIRE, 28 AWG, 7/0.12 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.08 mm²
 - Sheath Colour: Brown
 - American Wire Gauge: 28 AWG
 - Core Strands: 7/0.12 mm
 - Length: 100 m
 - Insulation Material: MPPE
 - Voltage Rating: 600 V
 - Outer Diameter: 0.9 mm



8724420 0.08 mm²

RS PRO BLACK 0.08 MM² HOOK UP WIRE, 28 AWG, 7/0.12 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.08 mm²
 - Sheath Colour: Black
 - American Wire Gauge: 28 AWG
 - Core Strands: 7/0.12 mm
 - Length: 100 m
 - Insulation Material: MPPE
 - Voltage Rating: 600 V
 - Outer Diameter: 0.9 mm



8724426 0.08 mm²

RS PRO BLUE 0.08 MM² HOOK UP WIRE, 28 AWG, 7/0.12 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.08 mm²
 - Sheath Colour: Blue
 - American Wire Gauge: 28 AWG
 - Core Strands: 7/0.12 mm
 - Length: 100 m
 - Insulation Material: MPPE
 - Voltage Rating: 600 V
 - Outer Diameter: 0.9 mm



8724432 0.08 mm²

RS PRO WHITE 0.08 MM² HOOK UP WIRE, 28 AWG, 7/0.12 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.08 mm²
 - Sheath Colour: White
 - American Wire Gauge: 28 AWG
 - Core Strands: 7/0.12 mm
 - Length: 100 m
 - Insulation Material: MPPE
 - Voltage Rating: 600 V
 - Outer Diameter: 0.9 mm



8724436 0.08 mm²

RS PRO RED 0.08 MM² HOOK UP WIRE, 28 AWG, 7/0.12 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.08 mm²
 - Sheath Colour: Red
 - American Wire Gauge: 28 AWG
 - Core Strands: 7/0.12 mm
 - Length: 100 m
 - Insulation Material: MPPE
 - Voltage Rating: 600 V
 - Outer Diameter: 0.9 mm



8724439 0.08 mm²

RS PRO ORANGE 0.08 MM² HOOK UP WIRE, 28 AWG, 7/0.12 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.08 mm²
 - Sheath Colour: Orange
 - American Wire Gauge: 28 AWG
 - Core Strands: 7/0.12 mm
 - Length: 100 m
 - Insulation Material: MPPE
 - Voltage Rating: 600 V
 - Outer Diameter: 0.9 mm



8724442 0.08 mm²

RS PRO GREEN 0.08 MM² HOOK UP WIRE, 28 AWG, 7/0.12 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.08 mm²
 - Sheath Colour: Green
 - American Wire Gauge: 28 AWG
 - Core Strands: 7/0.12 mm
 - Length: 100 m
 - Insulation Material: MPPE
 - Voltage Rating: 600 V
 - Outer Diameter: 0.9 mm



8724445 0.08 mm²

RS PRO YELLOW 0.08 MM² HOOK UP WIRE, 28 AWG, 7/0.12 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.08 mm²
 - Sheath Colour: Yellow
 - American Wire Gauge: 28 AWG
 - Core Strands: 7/0.12 mm
 - Length: 100 m
 - Insulation Material: MPPE
 - Voltage Rating: 600 V
 - Outer Diameter: 0.9 mm



8724448 0.08 mm²

RS PRO BLACK 0.13 MM² HOOK UP WIRE, 26 AWG, 7/0.16 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.13 mm²
 - Sheath Colour: Black
 - American Wire Gauge: 26 AWG
 - Core Strands: 7/0.16 mm
 - Length: 100 m
 - Insulation Material: MPPE
 - Voltage Rating: 600 V
 - Outer Diameter: 1 mm



8724458 0.13 mm²

RS PRO RED 0.13 MM² HOOK UP WIRE, 26 AWG, 7/0.16 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.13 mm²
 - Sheath Colour: Red
 - American Wire Gauge: 26 AWG
 - Core Strands: 7/0.16 mm
 - Length: 100 m
 - Insulation Material: MPPE
 - Voltage Rating: 600 V
 - Outer Diameter: 1 mm



8724460 0.13 mm²

RS PRO BLUE 0.13 MM² HOOK UP WIRE, 26 AWG, 7/0.16 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.13 mm²
 - Sheath Colour: Blue
 - American Wire Gauge: 26 AWG
 - Core Strands: 7/0.16 mm
 - Length: 100 m
 - Insulation Material: MPPE
 - Voltage Rating: 600 V
 - Outer Diameter: 1 mm



8724464 0.13 mm²

RS PRO BROWN 0.13 MM² HOOK UP WIRE, 26 AWG, 7/0.16 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.13 mm²
 - Sheath Colour: Brown
 - American Wire Gauge: 26 AWG
 - Core Strands: 7/0.16 mm
 - Length: 100 m
 - Insulation Material: MPPE
 - Voltage Rating: 600 V
 - Outer Diameter: 1 mm



8724467 0.13 mm²

RS PRO WHITE 0.13 MM² HOOK UP WIRE, 26 AWG, 7/0.16 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.13 mm²
 - Sheath Colour: White
 - American Wire Gauge: 26 AWG
 - Core Strands: 7/0.16 mm
 - Length: 100 m
 - Insulation Material: MPPE
 - Voltage Rating: 600 V
 - Outer Diameter: 1 mm



8724473 0.13 mm²

RS PRO GREEN 0.13 MM² HOOK UP WIRE, 26 AWG, 7/0.16 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.13 mm²
 - Sheath Colour: Green
 - American Wire Gauge: 26 AWG
 - Core Strands: 7/0.16 mm
 - Length: 100 m
 - Insulation Material: MPPE
 - Voltage Rating: 600 V
 - Outer Diameter: 1 mm



8724476 0.13 mm²

RS PRO RED 0.2 MM² HOOK UP WIRE, 24 AWG, 11/0.16 MM, 100M, MPPE

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.2 mm²
 - Sheath Colour: Red
 - American Wire Gauge: 24 AWG
 - Core Strands: 11/0.16 mm
 - Length: 100 m
 - Insulation Material: MPPE
 - Voltage Rating: 600 V
 - Outer Diameter: 1.12 mm



8724492 0.2 mm²

RS PRO BLACK 0.2 MM² HOOK UP WIRE, 24 AWG, 11/0.16 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.2 mm²
 - Sheath Colour: Black
 - American Wire Gauge: 24 AWG
 - Core Strands: 11/0.16 mm
 - Length: 100 m
 - Insulation Material: MPPE
 - Voltage Rating: 600 V
 - Outer Diameter: 1.12 mm



8724495 0.2 mm²

RS PRO BLUE 0.2 MM² HOOK UP WIRE, 24 AWG, 11/0.16 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.2 mm²
 - Sheath Colour: Blue
 - American Wire Gauge: 24 AWG
 - Core Strands: 11/0.16 mm
 - Length: 100 m
 - Insulation Material: MPPE
 - Voltage Rating: 600 V
 - Outer Diameter: 1.12 mm



8724502 0.2 mm²

RS PRO WHITE 0.2 MM² HOOK UP WIRE, 24 AWG, 11/0.16 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.2 mm²
 - Sheath Colour: White
 - American Wire Gauge: 24 AWG
 - Core Strands: 11/0.16 mm
 - Length: 100 m
 - Insulation Material: MPPE
 - Voltage Rating: 600 V
 - Outer Diameter: 1.12 mm



8724505 0.2 mm²

RS PRO GREEN 0.2 MM² HOOK UP WIRE, 24 AWG, 11/0.16 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.2 mm²
 - Sheath Colour: Green
 - American Wire Gauge: 24 AWG
 - Core Strands: 11/0.16 mm
 - Length: 100 m
 - Insulation Material: MPPE
 - Voltage Rating: 600 V
 - Outer Diameter: 1.12 mm



8724509 0.2 mm²

RS PRO GREY 0.2 MM² HOOK UP WIRE, 24 AWG, 11/0.16 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.2 mm²
 - Sheath Colour: Grey
 - American Wire Gauge: 24 AWG
 - Core Strands: 11/0.16 mm
 - Length: 100 m
 - Insulation Material: MPPE
 - Voltage Rating: 600 V
 - Outer Diameter: 1.12 mm



8724515 0.2 mm²

RS PRO YELLOW 0.2 MM² HOOK UP WIRE, 24 AWG, 11/0.16 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.2 mm²
 - Sheath Colour: Yellow
 - American Wire Gauge: 24 AWG
 - Core Strands: 11/0.16 mm
 - Length: 100 m
 - Insulation Material: MPPE
 - Voltage Rating: 600 V
 - Outer Diameter: 1.12 mm



8724518 0.2 mm²

RS PRO BROWN 0.33 MM² HOOK UP WIRE, 22 AWG, 7/0.12 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.33 mm²
 - Sheath Colour: Brown
 - American Wire Gauge: 22 AWG
 - Core Strands: 7/0.12 mm
 - Length: 100 m
 - Insulation Material: MPPE
 - Voltage Rating: 600 V
 - Outer Diameter: 1.3 mm



8724521 0.33 mm²

RS PRO BLACK 0.33 MM² HOOK UP WIRE, 22 AWG, 7/0.12 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.33 mm²
 - Sheath Colour: Black
 - American Wire Gauge: 22 AWG
 - Core Strands: 7/0.12 mm
 - Length: 100 m
 - Insulation Material: MPPE
 - Voltage Rating: 600 V
 - Outer Diameter: 1.3 mm



8724527 0.33 mm²

RS PRO RED 0.33 MM² HOOK UP WIRE, 22 AWG, 7/0.12 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.33 mm²
 - Sheath Colour: Red
 - American Wire Gauge: 22 AWG
 - Core Strands: 7/0.12 mm
 - Length: 100 m
 - Insulation Material: MPPE
 - Voltage Rating: 600 V
 - Outer Diameter: 1.3 mm



8724530 0.33 mm²

RS PRO BLUE 0.33 MM² HOOK UP WIRE, 22 AWG, 7/0.12 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.33 mm²
 - Sheath Colour: Blue
 - American Wire Gauge: 22 AWG
 - Core Strands: 7/0.12 mm
 - Length: 100 m
 - Insulation Material: MPPE
 - Voltage Rating: 600 V
 - Outer Diameter: 1.3 mm



8724533 0.33 mm²

RS PRO WHITE 0.33 MM² HOOK UP WIRE, 22 AWG, 7/0.12 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.33 mm²
 - Sheath Colour: White
 - American Wire Gauge: 22 AWG
 - Core Strands: 7/0.12 mm
 - Length: 100 m
 - Insulation Material: MPPE
 - Voltage Rating: 600 V
 - Outer Diameter: 1.3 mm



8724537 0.33 mm²

RS PRO ORANGE 0.33 MM² HOOK UP WIRE, 22 AWG, 7/0.12 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.33 mm²
 - Sheath Colour: Orange
 - American Wire Gauge: 22 AWG
 - Core Strands: 7/0.12 mm
 - Length: 100 m
 - Insulation Material: MPPE
 - Voltage Rating: 600 V
 - Outer Diameter: 1.3 mm



8724543 0.33 mm²

RS PRO GREEN 0.33 MM² HOOK UP WIRE, 22 AWG, 7/0.12 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.33 mm²
 - Sheath Colour: Green
 - American Wire Gauge: 22 AWG
 - Core Strands: 7/0.12 mm
 - Length: 100 m
 - Insulation Material: MPPE
 - Voltage Rating: 600 V
 - Outer Diameter: 1.3 mm



8724546 0.33 mm²

RS PRO YELLOW 0.33 MM² HOOK UP WIRE, 22 AWG, 7/0.12 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.33 mm²
 - Sheath Colour: Yellow
 - American Wire Gauge: 22 AWG
 - Core Strands: 7/0.12 mm
 - Length: 100 m
 - Insulation Material: MPPE
 - Voltage Rating: 600 V
 - Outer Diameter: 1.3 mm



8724549 0.33 mm²

RS PRO RED 0.13 MM² HOOK UP WIRE, 26 AWG, 7/0.16 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.13 mm²
 - Sheath Colour: Red
 - American Wire Gauge: 26 AWG
 - Core Strands: 7/0.16 mm
 - Length: 100 m
 - Insulation Material: PVC
 - Voltage Rating: 600 V
 - Outer Diameter: 2.1 mm



8724593 0.13 mm²

RS PRO YELLOW 0.2 MM² HOOK UP WIRE, 24 AWG, 11/0.16 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.2 mm²
 - Sheath Colour: Yellow
 - American Wire Gauge: 24 AWG
 - Core Strands: 11/0.16 mm
 - Length: 100 m
 - Insulation Material: PVC
 - Voltage Rating: 600 V
 - Outer Diameter: 2.2 mm



8724622 0.2 mm²

RS PRO YELLOW 0.33 MM² HOOK UP WIRE, 22 AWG, 17/0.16 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.33 mm²
 - Sheath Colour: Yellow
 - American Wire Gauge: 22 AWG
 - Core Strands: 17/0.16 mm
 - Length: 100 m
 - Insulation Material: PVC
 - Voltage Rating: 600 V
 - Outer Diameter: 2.4 mm



8724640 0.33 mm²

RS PRO BLACK 0.13 MM² HOOK UP WIRE, 26 AWG, 7/0.16 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.13 mm²
 - Sheath Colour: Black
 - American Wire Gauge: 26 AWG
 - Core Strands: 7/0.16 mm
 - Length: 100 m
 - Insulation Material: XLPE
 - Voltage Rating: 300 V
 - Outer Diameter: 1.3 mm



8725136 0.13 mm²

RS PRO RED 0.13 MM² HOOK UP WIRE, 26 AWG, 7/0.16 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.13 mm²
 - Sheath Colour: Red
 - American Wire Gauge: 26 AWG
 - Core Strands: 7/0.16 mm
 - Length: 100 m
 - Insulation Material: XLPE
 - Voltage Rating: 300 V
 - Outer Diameter: 1.3 mm



8725151 0.13 mm²

RS PRO BLUE 0.13 MM² HOOK UP WIRE, 26 AWG, 7/0.16 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.13 mm²
 - Sheath Colour: Blue
 - American Wire Gauge: 26 AWG
 - Core Strands: 7/0.16 mm
 - Length: 100 m
 - Insulation Material: XLPE
 - Voltage Rating: 300 V
 - Outer Diameter: 1.3 mm



8725167 0.13 mm²

RS PRO BLACK 0.2 MM² HOOK UP WIRE, 24 AWG, 11/0.16 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.2 mm²
 - Sheath Colour: Black
 - American Wire Gauge: 24 AWG
 - Core Strands: 11/0.16 mm
 - Length: 100 m
 - Insulation Material: XLPE
 - Voltage Rating: 300 V
 - Outer Diameter: 1.43 mm



8725205 0.2 mm²

RS PRO RED 0.2 MM² HOOK UP WIRE, 24 AWG, 11/0.16 MM, 100M, XLPE

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.2 mm²
 - Sheath Colour: Red
 - American Wire Gauge: 24 AWG
 - Core Strands: 11/0.16 mm
 - Length: 100 m
 - Insulation Material: XLPE
 - Voltage Rating: 300 V
 - Outer Diameter: 1.43 mm



8725215 0.2 mm²

RS PRO BROWN 0.2 MM² HOOK UP WIRE, 24 AWG, 11/0.16 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.2 mm²
 - Sheath Colour: Brown
 - American Wire Gauge: 24 AWG
 - Core Strands: 11/0.16 mm
 - Length: 100 m
 - Insulation Material: XLPE
 - Voltage Rating: 300 V
 - Outer Diameter: 1.43 mm



8725218 0.2 mm²

RS PRO BLUE 0.2 MM² HOOK UP WIRE, 24 AWG, 11/0.16 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.2 mm²
 - Sheath Colour: Blue
 - American Wire Gauge: 24 AWG
 - Core Strands: 11/0.16 mm
 - Length: 100 m
 - Insulation Material: XLPE
 - Voltage Rating: 300 V
 - Outer Diameter: 1.43 mm



8725221 0.2 mm²

RS PRO WHITE 0.2 MM² HOOK UP WIRE, 24 AWG, 11/0.16 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.2 mm²
 - Sheath Colour: White
 - American Wire Gauge: 24 AWG
 - Core Strands: 11/0.16 mm
 - Length: 100 m
 - Insulation Material: XLPE
 - Voltage Rating: 300 V
 - Outer Diameter: 1.43 mm



8725233 0.2 mm²

RS PRO YELLOW 0.2 MM² HOOK UP WIRE, 24 AWG, 11/0.16 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.2 mm²
 - Sheath Colour: Yellow
 - American Wire Gauge: 24 AWG
 - Core Strands: 11/0.16 mm
 - Length: 100 m
 - Insulation Material: XLPE
 - Voltage Rating: 300 V
 - Outer Diameter: 1.43 mm



8725243 0.2 mm²

RS PRO GREEN 0.2 MM² HOOK UP WIRE, 24 AWG, 11/0.16 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.2 mm²
 - Sheath Colour: Green
 - American Wire Gauge: 24 AWG
 - Core Strands: 11/0.16 mm
 - Length: 100 m
 - Insulation Material: XLPE
 - Voltage Rating: 300 V
 - Outer Diameter: 1.43 mm



8725246 0.2 mm²

RS PRO BLACK 0.33 MM² HOOK UP WIRE, 22 AWG, 17/0.16 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.33 mm²
 - Sheath Colour: Black
 - American Wire Gauge: 22 AWG
 - Core Strands: 17/0.16 mm
 - Length: 100 m
 - Insulation Material: XLPE
 - Voltage Rating: 300 V
 - Outer Diameter: 1.58 mm



8725274 0.33 mm²

RS PRO BROWN 0.33 MM² HOOK UP WIRE, 22 AWG, 17/0.16 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.33 mm²
 - Sheath Colour: Brown
 - American Wire Gauge: 22 AWG
 - Core Strands: 17/0.16 mm
 - Length: 100 m
 - Insulation Material: XLPE
 - Voltage Rating: 300 V
 - Outer Diameter: 1.58 mm



8725277 0.33 mm²

RS PRO RED 0.33 MM² HOOK UP WIRE, 22 AWG, 17/0.16 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.33 mm²
 - Sheath Colour: Red
 - American Wire Gauge: 22 AWG
 - Core Strands: 17/0.16 mm
 - Length: 100 m
 - Insulation Material: XLPE
 - Voltage Rating: 300 V
 - Outer Diameter: 1.58 mm



8725280 0.33 mm²

RS PRO WHITE 0.33 MM² HOOK UP WIRE, 22 AWG, 17/0.16 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.33 mm²
 - Sheath Colour: White
 - American Wire Gauge: 22 AWG
 - Core Strands: 17/0.16 mm
 - Length: 100 m
 - Insulation Material: XLPE
 - Voltage Rating: 300 V
 - Outer Diameter: 1.58 mm



8725293 0.33 mm²

RS PRO BLUE 0.33 MM² HOOK UP WIRE, 22 AWG, 17/0.16 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.33 mm²
 - Sheath Colour: Blue
 - American Wire Gauge: 22 AWG
 - Core Strands: 17/0.16 mm
 - Length: 100 m
 - Insulation Material: XLPE
 - Voltage Rating: 300 V
 - Outer Diameter: 1.58 mm



8725296 0.33 mm²

RS PRO YELLOW 0.33 MM² HOOK UP WIRE, 22 AWG, 17/0.16 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.33 mm²
 - Sheath Colour: Yellow
 - American Wire Gauge: 22 AWG
 - Core Strands: 17/0.16 mm
 - Length: 100 m
 - Insulation Material: XLPE
 - Voltage Rating: 300 V
 - Outer Diameter: 1.58 mm



8725300 0.33 mm²

RS PRO GREEN 0.33 MM² HOOK UP WIRE, 22 AWG, 17/0.16 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.33 mm²
 - Sheath Colour: Green
 - American Wire Gauge: 22 AWG
 - Core Strands: 17/0.16 mm
 - Length: 100 m
 - Insulation Material: XLPE
 - Outer Diameter: 1.58 mm
 - Voltage Rating: 300 V



8725303 0.33 mm²

RS PRO ORANGE 0.33 MM² HOOK UP WIRE, 22 AWG, 17/0.16 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.33 mm²
 - Sheath Colour: Orange
 - American Wire Gauge: 22 AWG
 - Core Strands: 17/0.16 mm
 - Length: 100 m
 - Insulation Material: XLPE
 - Voltage Rating: 300 V
 - Outer Diameter: 1.58 mm



8725312 0.33 mm²

RS PRO PURPLE 0.33 MM² HOOK UP WIRE, 22 AWG, 17/0.16 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.33 mm²
 - Sheath Colour: Purple
 - American Wire Gauge: 22 AWG
 - Core Strands: 17/0.16 mm
 - Length: 100 m
 - Insulation Material: XLPE
 - Voltage Rating: 300 V
 - Outer Diameter: 1.58 mm



8725322 0.33 mm²

RS PRO GREY 0.33 MM² HOOK UP WIRE, 22 AWG, 17/0.16 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.33 mm²
 - Sheath Colour: Grey
 - American Wire Gauge: 22 AWG
 - Core Strands: 17/0.16 mm
 - Length: 100 m
 - Insulation Material: XLPE
 - Voltage Rating: 300 V
 - Outer Diameter: 1.58 mm



8725325 0.33 mm²

RS PRO RED 0.26 MM² EQUIPMENT WIRE, 23 AWG, 3/0.07 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.26 mm²
 - Sheath Colour: Red
 - American Wire Gauge: 23 AWG
 - Core Strands: 3/0.07 mm
 - Length: 100 m
 - Insulation Material: PVC
 - Outer Diameter: 1.7 mm
 - Voltage Rating: 250 V



8738863 0.26 mm²

RS PRO BLACK 0.08 MM² HOOK UP WIRE, 28 AWG, 7/0.12 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.08 mm²
 - Sheath Colour: Black
 - American Wire Gauge: 28 AWG
 - Core Strands: 7/0.12 mm
 - Length: 100 m
 - Insulation Material: XLPE
 - Voltage Rating: 6 kV dc
 - Outer Diameter: 1.2 mm



8738876 0.08 mm²

RS PRO RED 0.13 MM² HOOK UP WIRE, 26 AWG, 7/0.16 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.13 mm²
 - Sheath Colour: Red
 - American Wire Gauge: 26 AWG
 - Core Strands: 7/0.16 mm
 - Length: 100 m
 - Insulation Material: XLPE
 - Voltage Rating: 6 kV dc
 - Outer Diameter: 1.4 mm



8738911 0.13 mm²

RS PRO BLUE 0.13 MM² HOOK UP WIRE, 26 AWG, 7/0.16 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.13 mm²
 - Sheath Colour: Blue
 - American Wire Gauge: 26 AWG
 - Core Strands: 7/0.16 mm
 - Length: 100 m
 - Insulation Material: XLPE
 - Voltage Rating: 6 kV dc
 - Outer Diameter: 1.4 mm



8738914 0.13 mm²

RS PRO BLACK 0.2 MM² HOOK UP WIRE, 24 AWG, 11/0.16 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.2 mm²
 - Sheath Colour: Black
 - American Wire Gauge: 24 AWG
 - Core Strands: 11/0.16 mm
 - Length: 100 m
 - Insulation Material: XLPE
 - Voltage Rating: 6 kV dc
 - Outer Diameter: 1.5 mm



8738930 0.2 mm²

RS PRO RED 0.2 MM² HOOK UP WIRE, 24 AWG, 11/0.16 MM, 100M, XLPE

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.2 mm²
 - Sheath Colour: Red
 - American Wire Gauge: 24 AWG
 - Core Strands: 11/0.16 mm
 - Length: 100 m
 - Insulation Material: XLPE
 - Voltage Rating: 6 kV dc
 - Outer Diameter: 1.5 mm



8738942 0.2 mm²

RS PRO BLUE 0.2 MM² HOOK UP WIRE, 24 AWG, 11/0.16 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.2 mm²
 - Sheath Colour: Blue
 - American Wire Gauge: 24 AWG
 - Core Strands: 11/0.16 mm
 - Length: 100 m
 - Insulation Material: XLPE
 - Voltage Rating: 6 kV dc
 - Outer Diameter: 1.5 mm



8738946 0.2 mm²

RS PRO BROWN 0.2 MM² HOOK UP WIRE, 24 AWG, 11/0.16 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.2 mm²
 - Sheath Colour: Brown
 - American Wire Gauge: 24 AWG
 - Core Strands: 11/0.16 mm
 - Length: 100 m
 - Insulation Material: XLPE
 - Voltage Rating: 6 kV dc
 - Outer Diameter: 1.5 mm



8738949 0.2 mm²

RS PRO YELLOW 0.2 MM² HOOK UP WIRE, 24 AWG, 11/0.16 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.2 mm²
 - Sheath Colour: Yellow
 - American Wire Gauge: 24 AWG
 - Core Strands: 11/0.16 mm
 - Length: 100 m
 - Insulation Material: XLPE
 - Voltage Rating: 6 kV dc
 - Outer Diameter: 1.5 mm



8738952 0.2 mm²

RS PRO WHITE 0.2 MM² HOOK UP WIRE, 24 AWG, 11/0.16 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.2 mm²
 - Sheath Colour: White
 - American Wire Gauge: 24 AWG
 - Core Strands: 11/0.16 mm
 - Length: 100 m
 - Insulation Material: XLPE
 - Voltage Rating: 6 kV dc
 - Outer Diameter: 1.5 mm



8738955 0.2 mm²

RS PRO GREEN 0.2 MM² HOOK UP WIRE, 24 AWG, 11/0.16 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.2 mm²
 - Sheath Colour: Green
 - American Wire Gauge: 24 AWG
 - Core Strands: 11/0.16 mm
 - Length: 100 m
 - Insulation Material: XLPE
 - Voltage Rating: 6 kV dc
 - Outer Diameter: 1.5 mm



8738958 0.2 mm²

RS PRO ORANGE 0.2 MM² HOOK UP WIRE, 24 AWG, 11/0.16 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.2 mm²
 - Sheath Colour: Orange
 - American Wire Gauge: 24 AWG
 - Core Strands: 11/0.16 mm
 - Length: 100 m
 - Insulation Material: XLPE
 - Voltage Rating: 6 kV dc
 - Outer Diameter: 1.5 mm



8738961 0.2 mm²

RS PRO GREY 0.2 MM² HOOK UP WIRE, 24 AWG, 11/0.16 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.2 mm²
 - Sheath Colour: Grey
 - American Wire Gauge: 24 AWG
 - Core Strands: 11/0.16 mm
 - Length: 100 m
 - Insulation Material: XLPE
 - Voltage Rating: 6 kV dc
 - Outer Diameter: 1.5 mm



8738964 0.2 mm²

RS PRO PURPLE 0.2 MM² HOOK UP WIRE, 24 AWG, 11/0.16 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.2 mm²
 - Sheath Colour: Purple
 - American Wire Gauge: 24 AWG
 - Core Strands: 11/0.16 mm
 - Length: 100 m
 - Insulation Material: XLPE
 - Voltage Rating: 6 kV dc
 - Outer Diameter: 1.5 mm



8738968 0.2 mm²

RS PRO RED 0.33 MM² HOOK UP WIRE, 22 AWG, 17/0.16 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.33 mm²
 - Sheath Colour: Red
 - American Wire Gauge: 22 AWG
 - Core Strands: 17/0.16 mm
 - Length: 100 m
 - Insulation Material: XLPE
 - Voltage Rating: 6 kV dc
 - Outer Diameter: 1.58 mm



8738974 0.33 mm²

RS PRO BLACK 0.33 MM² HOOK UP WIRE, 22 AWG, 17/0.16 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.33 mm²
 - Sheath Colour: Black
 - American Wire Gauge: 22 AWG
 - Core Strands: 17/0.16 mm
 - Length: 100 m
 - Insulation Material: XLPE
 - Voltage Rating: 6 kV dc
 - Outer Diameter: 1.58 mm



8738977 0.33 mm²

RS PRO BLUE 0.33 MM² HOOK UP WIRE, 22 AWG, 17/0.16 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.33 mm²
 - Sheath Colour: Blue
 - American Wire Gauge: 22 AWG
 - Core Strands: 17/0.16 mm
 - Length: 100 m
 - Insulation Material: XLPE
 - Voltage Rating: 6 kV dc
 - Outer Diameter: 1.58 mm



8738983 0.33 mm²

RS PRO WHITE 0.33 MM² HOOK UP WIRE, 22 AWG, 17/0.16 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.33 mm²
 - Sheath Colour: White
 - American Wire Gauge: 22 AWG
 - Core Strands: 17/0.16 mm
 - Length: 100 m
 - Insulation Material: XLPE
 - Voltage Rating: 6 kV dc
 - Outer Diameter: 1.58 mm



8738986 0.33 mm²

RS PRO ORANGE 0.33 MM² HOOK UP WIRE, 22 AWG, 17/0.16 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.33 mm²
 - Sheath Colour: Orange
 - American Wire Gauge: 22 AWG
 - Core Strands: 17/0.16 mm
 - Length: 100 m
 - Insulation Material: XLPE
 - Voltage Rating: 6 kV dc
 - Outer Diameter: 1.58 mm



8738992 0.33 mm²

RS PRO GREY 0.33 MM² HOOK UP WIRE, 22 AWG, 17/0.16 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.33 mm²
 - Sheath Colour: Grey
 - American Wire Gauge: 22 AWG
 - Core Strands: 17/0.16 mm
 - Length: 100 m
 - Insulation Material: XLPE
 - Voltage Rating: 6 kV dc
 - Outer Diameter: 1.58 mm



8738996 0.33 mm²

RS PRO YELLOW 0.33 MM² HOOK UP WIRE, 22 AWG, 17/0.16 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.33 mm²
 - Sheath Colour: Yellow
 - American Wire Gauge: 22 AWG
 - Core Strands: 17/0.16 mm
 - Length: 100 m
 - Insulation Material: XLPE
 - Outer Diameter: 1.58 mm
 - Voltage Rating: 6 kV dc



8738999 0.33 mm²

RS PRO RED 0.2 MM² HOOK UP WIRE, 24 AWG, 11/0.16 MM, 100M, PVC

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.2 mm²
 - Sheath Colour: Red
 - American Wire Gauge: 24 AWG
 - Core Strands: 11/0.16 mm
 - Length: 100 m
 - Insulation Material: PVC
 - Voltage Rating: 300 V
 - Outer Diameter: 1.4 mm



8739933 0.2 mm²

RS PRO BLACK 0.2 MM² HOOK UP WIRE, 24 AWG, 11/0.16 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.2 mm²
 - Sheath Colour: Black
 - American Wire Gauge: 24 AWG
 - Core Strands: 11/0.16 mm
 - Length: 100 m
 - Insulation Material: PVC
 - Voltage Rating: 300 V
 - Outer Diameter: 1.4 mm



8739936 0.2 mm²

RS PRO WHITE 0.2 MM² HOOK UP WIRE, 24 AWG, 11/0.16 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.2 mm²
 - Sheath Colour: White
 - American Wire Gauge: 24 AWG
 - Core Strands: 11/0.16 mm
 - Length: 100 m
 - Insulation Material: PVC
 - Voltage Rating: 300 V
 - Outer Diameter: 1.4 mm



8739945 0.2 mm²

RS PRO RED 0.33 MM² HOOK UP WIRE, 22 AWG, 7/0.25 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.33 mm²
 - Sheath Colour: Red
 - American Wire Gauge: 22 AWG
 - Core Strands: 7/0.25 mm
 - Length: 100 m
 - Insulation Material: PVC
 - Voltage Rating: 300 V
 - Outer Diameter: 1.6 mm



8739970 0.33 mm²

RS PRO BLUE 0.33 MM² HOOK UP WIRE, 22 AWG, 7/0.25 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.33 mm²
 - Sheath Colour: Blue
 - American Wire Gauge: 22 AWG
 - Core Strands: 7/0.25 mm
 - Length: 100 m
 - Insulation Material: PVC
 - Voltage Rating: 300 V
 - Outer Diameter: 1.6 mm



8739973 0.33 mm²

RS PRO WHITE 0.33 MM² HOOK UP WIRE, 22 AWG, 7/0.25 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.33 mm²
 - Sheath Colour: White
 - American Wire Gauge: 22 AWG
 - Core Strands: 7/0.25 mm
 - Length: 100 m
 - Insulation Material: PVC
 - Voltage Rating: 300 V
 - Outer Diameter: 1.6 mm



8739977 0.33 mm²

RS PRO YELLOW 0.33 MM² HOOK UP WIRE, 22 AWG, 17/0.16 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.33 mm²
 - Sheath Colour: Yellow
 - American Wire Gauge: 22 AWG
 - Core Strands: 17/0.16 mm
 - Length: 100 m
 - Insulation Material: XLPE
 - Outer Diameter: 2.4 mm
 - Voltage Rating: 600 V



8740352 0.33 mm²

RS PRO BLACK 0.08 MM² HOOK UP WIRE, 28 AWG, 7/0.12 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.08 mm²
 - Sheath Colour: Black
 - American Wire Gauge: 28 AWG
 - Core Strands: 7/0.12 mm
 - Length: 100 m
 - Insulation Material: PVC
 - Outer Diameter: 1.2 mm
 - Voltage Rating: 300 V



8740361 0.08 mm²

RS PRO PURPLE 0.33 MM² HOOK UP WIRE, 22 AWG, 17/0.16 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.33 mm²
 - Sheath Colour: Purple
 - American Wire Gauge: 22 AWG
 - Core Strands: 17/0.16 mm
 - Length: 100 m
 - Insulation Material: XLPE
 - Outer Diameter: 2.4 mm
 - Voltage Rating: 600 V



8740368 0.33 mm²

RS PRO WHITE 0.08 MM² HOOK UP WIRE, 28 AWG, 7/0.12 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.08 mm²
 - Sheath Colour: White
 - American Wire Gauge: 28 AWG
 - Core Strands: 7/0.12 mm
 - Length: 100 m
 - Insulation Material: PVC
 - Outer Diameter: 1.2 mm
 - Voltage Rating: 300 V



8740371 0.08 mm²

RS PRO RED 0.08 MM² HOOK UP WIRE, 28 AWG, 7/0.12 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.08 mm²
 - Sheath Colour: Red
 - American Wire Gauge: 28 AWG
 - Core Strands: 7/0.12 mm
 - Length: 100 m
 - Insulation Material: PVC
 - Outer Diameter: 1.2 mm
 - Voltage Rating: 300 V



8740374 0.08 mm²

RS PRO BLUE 0.08 MM² HOOK UP WIRE, 28 AWG, 7/0.12 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.08 mm²
 - Sheath Colour: Blue
 - American Wire Gauge: 28 AWG
 - Core Strands: 7/0.12 mm
 - Length: 100 m
 - Insulation Material: PVC
 - Outer Diameter: 1.2 mm
 - Voltage Rating: 300 V



8740377 0.08 mm²

RS PRO GREEN 0.08 MM² HOOK UP WIRE, 28 AWG, 7/0.12 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.08 mm²
 - Sheath Colour: Green
 - American Wire Gauge: 28 AWG
 - Core Strands: 7/0.12 mm
 - Length: 100 m
 - Insulation Material: PVC
 - Outer Diameter: 1.2 mm
 - Voltage Rating: 300 V



8740380 0.08 mm²

RS PRO BLACK 0.13 MM² HOOK UP WIRE, 26 AWG, 7/0.16 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.13 mm²
 - Sheath Colour: Black
 - American Wire Gauge: 26 AWG
 - Core Strands: 7/0.16 mm
 - Length: 100 m
 - Insulation Material: PVC
 - Outer Diameter: 1.3 mm
 - Voltage Rating: 300 V



8740393 0.13 mm²

RS PRO BLUE 0.13 MM² HOOK UP WIRE, 26 AWG, 7/0.16 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.13 mm²
 - Sheath Colour: Blue
 - American Wire Gauge: 26 AWG
 - Core Strands: 7/0.16 mm
 - Length: 100 m
 - Insulation Material: PVC
 - Outer Diameter: 1.3 mm
 - Voltage Rating: 300 V



8740400 0.13 mm²

RS PRO RED 0.13 MM² HOOK UP WIRE, 26 AWG, 7/0.16 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.13 mm²
 - Sheath Colour: Red
 - American Wire Gauge: 26 AWG
 - Core Strands: 7/0.16 mm
 - Length: 100 m
 - Insulation Material: PVC
 - Outer Diameter: 1.3 mm
 - Voltage Rating: 300 V



8740406 0.13 mm²

RS PRO YELLOW 0.13 MM² HOOK UP WIRE, 26 AWG, 7/0.16 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.13 mm²
 - Sheath Colour: Yellow
 - American Wire Gauge: 26 AWG
 - Core Strands: 7/0.16 mm
 - Length: 100 m
 - Insulation Material: PVC
 - Voltage Rating: 300 V
 - Outer Diameter: 1.3 mm



8740416 0.13 mm²

RS PRO WHITE 0.13 MM² HOOK UP WIRE, 26 AWG, 7/0.16 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.13 mm²
 - Sheath Colour: White
 - American Wire Gauge: 26 AWG
 - Core Strands: 7/0.16 mm
 - Length: 100 m
 - Insulation Material: PVC
 - Outer Diameter: 1.3 mm
 - Voltage Rating: 300 V



8740419 0.13 mm²

RS PRO GREY 0.33 MM² HOOK UP WIRE, 22 AWG, 17/0.16 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.33 mm²
 - Sheath Colour: Grey
 - American Wire Gauge: 22 AWG
 - Core Strands: 17/0.16 mm
 - Length: 100 m
 - Insulation Material: PVC
 - Outer Diameter: 1.58 mm
 - Voltage Rating: 300 V



8740450 0.33 mm²

RS PRO YELLOW 0.33 MM² HOOK UP WIRE, 22 AWG, 17/0.16 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.33 mm²
 - Sheath Colour: Yellow
 - American Wire Gauge: 22 AWG
 - Core Strands: 17/0.16 mm
 - Length: 100 m
 - Insulation Material: PVC
 - Outer Diameter: 1.58 mm
 - Voltage Rating: 300 V



8740453 0.33 mm²

RS PRO BLACK 0.08 MM² HOOK UP WIRE, 28 AWG, 7/0.12 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.08 mm²
 - Sheath Colour: Black
 - American Wire Gauge: 28 AWG
 - Core Strands: 7/0.12 mm
 - Length: 100 m
 - Insulation Material: XLPVC
 - Outer Diameter: 0.9 mm
 - Voltage Rating: 150 V



8775257 0.08 mm²

RS PRO RED 0.13 MM² HOOK UP WIRE, 26 AWG, 7/0.16 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.13 mm²
 - Sheath Colour: Red
 - American Wire Gauge: 26 AWG
 - Core Strands: 7/0.16 mm
 - Length: 100 m
 - Insulation Material: XLPVC
 - Voltage Rating: 150 V
 - Outer Diameter: 1 mm



8775291 0.13 mm²

RS PRO BLACK 0.33 MM² HOOK UP WIRE, 22 AWG, 7/0.25 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.33 mm²
 - Sheath Colour: Black
 - American Wire Gauge: 22 AWG
 - Core Strands: 7/0.25 mm
 - Length: 100 m
 - Insulation Material: XLPVC
 - Outer Diameter: 1.58 mm
 - Voltage Rating: 150 V



8775358 0.33 mm²

RS PRO BLACK 0.08 MM² HOOK UP WIRE, 28 AWG, 7/0.12 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.08 mm²
 - Sheath Colour: Black
 - American Wire Gauge: 28 AWG
 - Core Strands: 7/0.12 mm
 - Length: 100 m
 - Insulation Material: PVC
 - Outer Diameter: 1.2 mm
 - Voltage Rating: 300 V



8840837 0.08 mm²

RS PRO RED 0.08 MM² HOOK UP WIRE, 28 AWG, 7/0.12 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.08 mm²
 - Sheath Colour: Red
 - American Wire Gauge: 28 AWG
 - Core Strands: 7/0.12 mm
 - Length: 100 m
 - Insulation Material: PVC
 - Outer Diameter: 1.2 mm
 - Voltage Rating: 300 V



8840840 0.08 mm²

RS PRO BLUE 0.08 MM² HOOK UP WIRE, 28 AWG, 7/0.12 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.08 mm²
 - Sheath Colour: Blue
 - American Wire Gauge: 28 AWG
 - Core Strands: 7/0.12 mm
 - Length: 100 m
 - Insulation Material: PVC
 - Outer Diameter: 1.2 mm
 - Voltage Rating: 300 V



8840843 0.08 mm²

RS PRO BLACK 0.13 MM² HOOK UP WIRE, 26 AWG, 7/0.16 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.13 mm²
 - Sheath Colour: Black
 - American Wire Gauge: 26 AWG
 - Core Strands: 7/0.16 mm
 - Length: 100 m
 - Insulation Material: PVC
 - Outer Diameter: 1.3 mm
 - Voltage Rating: 300 V



8840869 0.13 mm²

RS PRO RED 0.13 MM² HOOK UP WIRE, 26 AWG, 7/0.16 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.13 mm²
 - Sheath Colour: Red
 - American Wire Gauge: 26 AWG
 - Core Strands: 7/0.16 mm
 - Length: 100 m
 - Insulation Material: PVC
 - Outer Diameter: 1.3 mm
 - Voltage Rating: 300 V



8840871 0.13 mm²

RS PRO BROWN 0.13 MM² HOOK UP WIRE, 26 AWG, 7/0.16 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.13 mm²
 - Sheath Colour: Brown
 - American Wire Gauge: 26 AWG
 - Core Strands: 7/0.16 mm
 - Length: 100 m
 - Insulation Material: PVC
 - Outer Diameter: 1.3 mm
 - Voltage Rating: 300 V



8840878 0.13 mm²

RS PRO ORANGE 0.13 MM² HOOK UP WIRE, 26 AWG, 7/0.16 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.13 mm²
 - Sheath Colour: Orange
 - American Wire Gauge: 26 AWG
 - Core Strands: 7/0.16 mm
 - Length: 100 m
 - Insulation Material: PVC
 - Outer Diameter: 1.3 mm
 - Voltage Rating: 300 V



8840890 0.13 mm²

RS PRO GREY 0.33 MM² HOOK UP WIRE, 22 AWG, 17/0.16 MM, 100M,

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Cross Sectional Area: 0.33 mm²
 - Sheath Colour: Grey
 - American Wire Gauge: 22 AWG
 - Core Strands: 17/0.16 mm
 - Length: 100 m
 - Insulation Material: PVC
 - Outer Diameter: 1.58 mm
 - Voltage Rating: 300 V



8840926 0.33 mm²

RS PRO 1.27MM 10 WAY FLAT RIBBON CABLE, GREY SHEATH, 12.7 MM

- ขนาดบรรจุภัณฑ์: **30 x MTR**
- Ribbon Cable Type: Flat
 - Pitch: 1.27 mm
 - Terminated/Unterminated: Unterminated
 - Number of Ways: 10
 - Screened/Unscreened: Unscreened
 - American Wire Gauge: 28 AWG
 - Length: 30 m
 - Width: 12.7 mm



360093 Flat

RS PRO 1.27MM 16 WAY FLAT RIBBON CABLE, GREY SHEATH, 20.3 MM

- ขนาดบรรจุภัณฑ์: **30 x MTR**
- Ribbon Cable Type: Flat
 - Pitch: 1.27 mm
 - Terminated/Unterminated: Unterminated
 - Number of Ways: 16
 - Screened/Unscreened: Unscreened
 - American Wire Gauge: 28 AWG
 - Length: 30 m
 - Width: 20.3 mm



360116 Flat

RS PRO 1.27MM 20 WAY FLAT RIBBON CABLE, GREY SHEATH, 25.4 MM


- ขนาดบรรจุภัณฑ์: **30 x MTR**
- Ribbon Cable Type: Flat
 - Pitch: 1.27 mm
 - Terminated/Unterminated: Unterminated
 - Number of Ways: 20
 - Screened/Unscreened: Unscreened
 - American Wire Gauge: 28 AWG
 - Length: 30 m
 - Width: 25.4 mm



360122 Flat

RS PRO 1.27MM 24 WAY FLAT RIBBON CABLE, GREY SHEATH, 30.5 MM

- ขนาดบรรจุภัณฑ์: **30 x MTR**
- Ribbon Cable Type: Flat
 - Pitch: 1.27 mm
 - Terminated/Unterminated: Unterminated
 - Number of Ways: 24
 - Screened/Unscreened: Unscreened
 - American Wire Gauge: 28 AWG
 - Length: 30 m
 - Width: 30.5 mm



360138 Flat

RS PRO 1.27MM 25 WAY FLAT RIBBON CABLE, GREY SHEATH, 31.8 MM


- ขนาดบรรจุภัณฑ์: **30 x MTR**
- Ribbon Cable Type: Flat
 - Pitch: 1.27 mm
 - Terminated/Unterminated: Unterminated
 - Number of Ways: 25
 - Screened/Unscreened: Unscreened
 - American Wire Gauge: 28 AWG
 - Length: 30 m
 - Width: 31.8 mm



360144 Flat

RS PRO 1.27MM 26 WAY FLAT RIBBON CABLE, GREY SHEATH, 33 MM WIDTH,

- ขนาดบรรจุภัณฑ์: **30 x MTR**
- Ribbon Cable Type: Flat
 - Pitch: 1.27 mm
 - Terminated/Unterminated: Unterminated
 - Number of Ways: 26
 - Screened/Unscreened: Unscreened
 - American Wire Gauge: 28 AWG
 - Length: 30 m
 - Width: 33 mm



360150 Flat

RS PRO 1.27MM 34 WAY FLAT RIBBON CABLE, GREY SHEATH, 43.2 MM

- ขนาดบรรจุภัณฑ์: **30 x MTR**
- Ribbon Cable Type: Flat
 - Pitch: 1.27 mm
 - Terminated/Unterminated: Unterminated
 - Number of Ways: 34
 - Screened/Unscreened: Unscreened
 - American Wire Gauge: 28 AWG
 - Length: 30 m
 - Width: 43.2 mm



360166 Flat

RS PRO 1.27MM 36 WAY FLAT RIBBON CABLE, GREY SHEATH, 45.7 MM

- ขนาดบรรจุภัณฑ์: **30 x MTR**
- Ribbon Cable Type: Flat
 - Pitch: 1.27 mm
 - Terminated/Unterminated: Unterminated
 - Number of Ways: 36
 - Screened/Unscreened: Unscreened
 - American Wire Gauge: 28 AWG
 - Length: 30 m
 - Width: 45.7 mm



360172 Flat

RS PRO 1.27MM 37 WAY FLAT RIBBON CABLE, GREY SHEATH, 47 MM WIDTH,

- ขนาดบรรจุภัณฑ์: **30 x MTR**
- Ribbon Cable Type: Flat
 - Pitch: 1.27 mm
 - Terminated/Unterminated: Unterminated
 - Number of Ways: 37
 - Screened/Unscreened: Unscreened
 - American Wire Gauge: 28 AWG
 - Length: 30 m
 - Width: 47 mm



360188 Flat

RS PRO 1.27MM 40 WAY FLAT RIBBON CABLE, GREY SHEATH, 50.8 MM

- ขนาดบรรจุภัณฑ์: **30 x MTR**
- Ribbon Cable Type: Flat
 - Pitch: 1.27 mm
 - Terminated/Unterminated: Unterminated
 - Number of Ways: 40
 - Screened/Unscreened: Unscreened
 - American Wire Gauge: 28 AWG
 - Length: 30 m
 - Width: 50.8 mm



360194 Flat

RS PRO 1.27MM 50 WAY FLAT RIBBON CABLE, GREY SHEATH, 63.5 MM

- ขนาดบรรจุภัณฑ์: **30 x MTR**
- Ribbon Cable Type: Flat
 - Pitch: 1.27 mm
 - Terminated/Unterminated: Unterminated
 - Number of Ways: 50
 - Screened/Unscreened: Unscreened
 - American Wire Gauge: 28 AWG
 - Length: 30 m
 - Width: 63.5 mm



360201 Flat

RS PRO 1.27MM 64 WAY FLAT RIBBON CABLE, GREY SHEATH, 81.3 MM


- ขนาดบรรจุภัณฑ์: **30 x MTR**
- Ribbon Cable Type: Flat
 - Pitch: 1.27 mm
 - Terminated/Unterminated: Unterminated
 - Number of Ways: 64
 - Screened/Unscreened: Unscreened
 - American Wire Gauge: 28 AWG
 - Length: 30 m
 - Width: 81.3 mm



360217 Flat

RS PRO 1.27MM 15 WAY FLAT RIBBON CABLE, GREY SHEATH, 19.1 MM

- ขนาดบรรจุภัณฑ์: **30 x MTR**
- Ribbon Cable Type: Flat
 - Pitch: 1.27 mm
 - Terminated/Unterminated: Unterminated
 - Number of Ways: 15
 - Screened/Unscreened: Unscreened
 - American Wire Gauge: 28 AWG
 - Length: 30 m
 - Width: 19.1 mm



360223 Flat

RS PRO 1.27MM 10 WAY FLAT RIBBON CABLE, MULTICOLOURED SHEATH,

- ขนาดบรรจุภัณฑ์: **25 x MTR**
- Ribbon Cable Type: Flat
 - Pitch: 1.27 mm
 - Terminated/Unterminated: Unterminated
 - Number of Ways: 10
 - Screened/Unscreened: Unscreened
 - American Wire Gauge: 26 AWG
 - Length: 25 m
 - Width: 12.7 mm



2140677 Flat

RS PRO 1.27MM 20 WAY FLAT RIBBON CABLE, MULTICOLOURED SHEATH,

- ขนาดบรรจุภัณฑ์: **10 x MTR**
- Ribbon Cable Type: Flat
 - Pitch: 1.27 mm
 - Terminated/Unterminated: Unterminated
 - Number of Ways: 20
 - Screened/Unscreened: Unscreened
 - American Wire Gauge: 26 AWG
 - Length: 10 m
 - Width: 25.4 mm



2140683 Flat

RS PRO 1.27MM 20 WAY FLAT RIBBON CABLE, MULTICOLOURED SHEATH,

- ขนาดบรรจุภัณฑ์: **25 x MTR**
- Ribbon Cable Type: Flat
 - Pitch: 1.27 mm
 - Terminated/Unterminated: Unterminated
 - Number of Ways: 20
 - Screened/Unscreened: Unscreened
 - American Wire Gauge: 26 AWG
 - Length: 25 m
 - Width: 25.4 mm



2140699 Flat

RS PRO 1.27MM 10 WAY FLAT RIBBON CABLE, GREY SHEATH, 12.7 MM

- ขนาดบรรจุภัณฑ์: **5 x MTR**
- Ribbon Cable Type: Flat
 - Pitch: 1.27 mm
 - Terminated/Unterminated: Unterminated
 - Number of Ways: 10
 - Screened/Unscreened: Unscreened
 - American Wire Gauge: 28 AWG
 - Length: 5 m
 - Width: 12.7 mm



2899846 Flat

RS PRO 1.27MM 14 WAY FLAT RIBBON CABLE, GREY SHEATH, 17.8 MM

- ขนาดบรรจุภัณฑ์: **5 x MTR**
- Ribbon Cable Type: Flat
 - Pitch: 1.27 mm
 - Terminated/Unterminated: Unterminated
 - Number of Ways: 14
 - Screened/Unscreened: Unscreened
 - American Wire Gauge: 28 AWG
 - Length: 5 m
 - Width: 17.8 mm



2899852 Flat

RS PRO 1.27MM 16 WAY FLAT RIBBON CABLE, GREY SHEATH, 20.3 MM

- ขนาดบรรจุภัณฑ์: **5 x MTR**
- Ribbon Cable Type: Flat
 - Pitch: 1.27 mm
 - Terminated/Unterminated: Unterminated
 - Number of Ways: 16
 - Screened/Unscreened: Unscreened
 - American Wire Gauge: 28 AWG
 - Length: 5 m
 - Width: 20.3 mm



2899874 Flat

RS PRO 1.27MM 20 WAY FLAT RIBBON CABLE, GREY SHEATH, 25.4 MM

- ขนาดบรรจุภัณฑ์: **5 x MTR**
- Ribbon Cable Type: Flat
 - Pitch: 1.27 mm
 - Terminated/Unterminated: Unterminated
 - Number of Ways: 20
 - Screened/Unscreened: Unscreened
 - American Wire Gauge: 28 AWG
 - Length: 5 m
 - Width: 25.4 mm



2899896 Flat

RS PRO 1.27MM 25 WAY FLAT RIBBON CABLE, GREY SHEATH, 31.8 MM

ขนาดบรรจุภัณฑ์: **5 x MTR**

- Ribbon Cable Type: Flat
- Pitch: 1.27 mm
- Terminated/Unterminated: Unterminated
- Number of Ways: 25
- Screened/Unscreened: Unscreened
- American Wire Gauge: 28 AWG
- Length: 5 m
- Width: 31.8 mm



2899919 Flat

RS PRO 1.27MM 26 WAY FLAT RIBBON CABLE, GREY SHEATH, 33 MM WIDTH,

ขนาดบรรจุภัณฑ์: **5 x MTR**

- Ribbon Cable Type: Flat
- Pitch: 1.27 mm
- Terminated/Unterminated: Unterminated
- Number of Ways: 26
- Screened/Unscreened: Unscreened
- American Wire Gauge: 28 AWG
- Length: 5 m
- Width: 33 mm



2899925 Flat

RS PRO 1.27MM 34 WAY FLAT RIBBON CABLE, GREY SHEATH, 43.2 MM

ขนาดบรรจุภัณฑ์: **5 x MTR**

- Ribbon Cable Type: Flat
- Pitch: 1.27 mm
- Terminated/Unterminated: Unterminated
- Number of Ways: 34
- Screened/Unscreened: Unscreened
- American Wire Gauge: 28 AWG
- Length: 5 m
- Width: 43.2 mm



2899931 Flat

RS PRO 1.27MM 37 WAY FLAT RIBBON CABLE, GREY SHEATH, 47 MM WIDTH,

ขนาดบรรจุภัณฑ์: **5 x MTR**

- Ribbon Cable Type: Flat
- Pitch: 1.27 mm
- Terminated/Unterminated: Unterminated
- Number of Ways: 37
- Screened/Unscreened: Unscreened
- American Wire Gauge: 28 AWG
- Length: 5 m
- Width: 47 mm



2899969 Flat

RS PRO 1.27MM 40 WAY FLAT RIBBON CABLE, GREY SHEATH, 50.8 MM

ขนาดบรรจุภัณฑ์: **5 x MTR**

- Ribbon Cable Type: Flat
- Pitch: 1.27 mm
- Terminated/Unterminated: Unterminated
- Number of Ways: 40
- Screened/Unscreened: Unscreened
- American Wire Gauge: 28 AWG
- Length: 5 m
- Width: 50.8 mm



2899975 Flat

RS PRO 1.27MM 50 WAY FLAT RIBBON CABLE, GREY SHEATH, 63.5 MM

ขนาดบรรจุภัณฑ์: **5 x MTR**

- Ribbon Cable Type: Flat
- Pitch: 1.27 mm
- Terminated/Unterminated: Unterminated
- Number of Ways: 50
- Screened/Unscreened: Unscreened
- American Wire Gauge: 28 AWG
- Length: 5 m
- Width: 63.5 mm



2899981 Flat

RS PRO 1.27MM 64 WAY FLAT RIBBON CABLE, GREY SHEATH, 81.3 MM

ขนาดบรรจุภัณฑ์: **5 x MTR**

- Ribbon Cable Type: Flat
- Pitch: 1.27 mm
- Terminated/Unterminated: Unterminated
- Number of Ways: 64
- Screened/Unscreened: Unscreened
- American Wire Gauge: 28 AWG
- Length: 5 m
- Width: 81.3 mm



2899997 Flat

RS PRO 4 CORE 28 AWG TELEPHONE CABLE, 7/0.127 MM, BLACK SHEATH,

ขนาดบรรจุภัณฑ์: **100 x MTR**

- Fire Behaviour: Flame Retardant
- Number of Cores: 4
- Shield Type: Unshielded
- Outer Sheath Material: PVC
- Core Strands: 7/0.127 mm
- Cross Sectional Area: 0.09 mm²
- American Wire Gauge: 28 AWG
- Conductor Material: Bare Copper



5185689 Flame Retardant

6 CORE TEL CABLE 50M BLACK

ขนาดบรรจุภัณฑ์: **50 x MTR**

- Fire Behaviour: Flame Retardant
- Number of Cores: 6
- Shield Type: Unshielded
- Outer Sheath Material: PVC
- Cross Sectional Area: 0.066 mm²
- American Wire Gauge: 30 AWG
- Conductor Material: Copper
- Terminated/Unterminated: Unterminated



5185746 Flame Retardant

RS PRO MULTICORE DATA CABLE, 2 PAIRS, 0.22 MM², 4 CORES, 24 AWG,

ขนาดบรรจุภัณฑ์: **100 x MTR**

- Number of Pairs: 2
- Cross Sectional Area: 0.22 mm²
- Number of Cores: 4
- American Wire Gauge: 24 AWG
- Screened/Unscreened: Screened
- Length: 100 m
- Shield Type: Unshielded
- Sheath Colour: Grey



8124680 2

RS PRO MULTICORE DATA CABLE, 1 PAIRS, 0.76 MM², 2 CORES, 22 AWG,

ขนาดบรรจุภัณฑ์: **100 x MTR**

- Number of Pairs: 1
- Cross Sectional Area: 0.76 mm²
- Number of Cores: 2
- American Wire Gauge: 22 AWG
- Screened/Unscreened: Screened
- Length: 100 m
- Shield Type: Aluminium Foil-PET Tape
- Sheath Colour: Grey



8124684 1

RS PRO MULTICORE DATA CABLE, 5 PAIRS, 0.2 MM², 10 CORES, 24 AWG,

ขนาดบรรจุภัณฑ์: **100 x MTR**

- Number of Pairs: 5
- Cross Sectional Area: 0.2 mm²
- Number of Cores: 10
- American Wire Gauge: 24 AWG
- Screened/Unscreened: Screened
- Length: 100 m
- Shield Type: Tinned Copper
- Sheath Colour: Grey



8124687 5

RS PRO TWISTED PAIR DATA CABLE, 2 PAIRS, 0.34 MM², 4 CORES, 22 AWG,

ขนาดบรรจุภัณฑ์: **100 x MTR**

- Number of Pairs: 2
- Cross Sectional Area: 0.34 mm²
- Number of Cores: 4
- American Wire Gauge: 22 AWG
- Screened/Unscreened: Screened
- Length: 100 m
- Shield Type: Aluminium Foil-PET Tape
- Sheath Colour: Grey



8124690 2

RS PRO TWISTED PAIR DATA CABLE, 3 PAIRS, 0.76 MM², 6 CORES, 22 AWG,

ขนาดบรรจุภัณฑ์: **50 x MTR**

- Number of Pairs: 3
- Cross Sectional Area: 0.76 mm²
- Number of Cores: 6
- American Wire Gauge: 22 AWG
- Screened/Unscreened: Screened
- Length: 50 m
- Shield Type: Aluminium Foil-PET Tape
- Sheath Colour: Grey



8124696 3

RS PRO MULTICORE DATA CABLE, 9 PAIRS, 0.22 MM², 18 CORES, 24 AWG,

ขนาดบรรจุภัณฑ์: **100 x MTR**

- Number of Pairs: 9
- Cross Sectional Area: 0.22 mm²
- Number of Cores: 18
- American Wire Gauge: 24 AWG
- Screened/Unscreened: Screened
- Length: 100 m
- Shield Type: Tinned Copper
- Sheath Colour: Grey



8124713 9

RS PRO TWISTED PAIR DATA CABLE, 10 PAIRS, 0.25 MM², 20 CORES, 24

ขนาดบรรจุภัณฑ์: **100 x MTR**

- Number of Pairs: 10
- Cross Sectional Area: 0.25 mm²
- Number of Cores: 20
- American Wire Gauge: 24 AWG
- Screened/Unscreened: Screened
- Shield Type: Tinned Copper
- Sheath Colour: Grey
- Outer Diameter: 9.1 mm




8124716 10

RS PRO MULTICORE DATA CABLE, 2 PAIRS, 0.64 MM², 4 CORES, 22 AWG,

ขนาดบรรจุภัณฑ์: **500 x MTR**

- Number of Pairs: 2
- Cross Sectional Area: 0.64 mm²
- Number of Cores: 4
- American Wire Gauge: 22 AWG
- Screened/Unscreened: Screened
- Length: 500 m
- Shield Type: Aluminium Foil-PET Tape
- Sheath Colour: Grey



8124735 2

RS PRO MULTICORE DATA CABLE, 2 PAIRS, 0.2 MM², 4 CORES, 24 AWG,

ขนาดบรรจุภัณฑ์: **100 x MTR**

- Number of Pairs: 2
- Cross Sectional Area: 0.2 mm²
- Number of Cores: 4
- American Wire Gauge: 24 AWG
- Screened/Unscreened: Screened
- Length: 100 m
- Shield Type: Tinned Copper
- Sheath Colour: Grey



8124738 2

RS PRO MULTICORE DATA CABLE, 1 PAIRS, 0.64 MM², 2 CORES, 22 AWG,

ขนาดบรรจุภัณฑ์: **100 x MTR**

- Number of Pairs: 1
- Cross Sectional Area: 0.64 mm²
- Number of Cores: 2
- American Wire Gauge: 22 AWG
- Screened/Unscreened: Unscreened
- Length: 100 m
- Shield Type: Unshielded
- Sheath Colour: Grey



8124741 1

RS PRO MULTICORE DATA CABLE, 2 PAIRS, 0.76 MM², 4 CORES, 22 AWG,

ขนาดบรรจุภัณฑ์: **100 x MTR**

- Number of Pairs: 2
- Cross Sectional Area: 0.76 mm²
- Number of Cores: 4
- American Wire Gauge: 22 AWG
- Screened/Unscreened: Screened
- Length: 100 m
- Shield Type: Aluminium Foil-PET Tape
- Sheath Colour: Grey




8124747 2

RS PRO TWISTED PAIR DATA CABLE, 4 PAIRS, 0.25 MM², 8 CORES, 24 AWG,

ขนาดบรรจุภัณฑ์: **100 x MTR**

- Number of Pairs: 4
- Cross Sectional Area: 0.25 mm²
- Number of Cores: 8
- American Wire Gauge: 24 AWG
- Screened/Unscreened: Screened
- Shield Type: Tinned Copper
- Sheath Colour: Grey
- Outer Diameter: 7.1 mm



8124750 4

RS PRO MULTICORE DATA CABLE, 2 PAIRS, 0.76 MM², 4 CORES, 24 AWG,

ขนาดบรรจุภัณฑ์: **100 x MTR**

- Number of Pairs: 2
- Cross Sectional Area: 0.76 mm²
- Number of Cores: 4
- American Wire Gauge: 24 AWG
- Screened/Unscreened: Screened
- Length: 100 m
- Shield Type: Aluminium Foil-PET Tape
- Sheath Colour: Grey



8124753 2

RS PRO MULTICORE DATA CABLE, 2 PAIRS, 0.22 MM², 4 CORES, 24 AWG,

ขนาดบรรจุภัณฑ์: **100 x MTR**

- Number of Pairs: 2
- Cross Sectional Area: 0.22 mm²
- Number of Cores: 4
- American Wire Gauge: 24 AWG
- Screened/Unscreened: Screened
- Length: 100 m
- Shield Type: Tinned Copper
- Sheath Colour: Grey



8124757 2

RS PRO MULTICORE DATA CABLE, 3 PAIRS, 0.76 MM², 6 CORES, 22 AWG,

ขนาดบรรจุภัณฑ์: **100 x MTR**

- Number of Pairs: 3
- Cross Sectional Area: 0.76 mm²
- Number of Cores: 6
- American Wire Gauge: 22 AWG
- Screened/Unscreened: Screened
- Length: 100 m
- Shield Type: Aluminium Foil-PET Tape
- Sheath Colour: Grey



8124766 3

RS PRO TWISTED PAIR DATA CABLE, 6 PAIRS, 0.25 MM², 12 CORES, 24 AWG,

ขนาดบรรจุภัณฑ์: **100 x MTR**

- Number of Pairs: 6
- Cross Sectional Area: 0.25 mm²
- Number of Cores: 12
- American Wire Gauge: 24 AWG
- Screened/Unscreened: Screened
- Shield Type: Tinned Copper
- Sheath Colour: Grey
- Outer Diameter: 7.5 mm



8124769 6

RS PRO MULTICORE DATA CABLE, 1 PAIRS, 0.35 MM², 2 CORES, 22 AWG,

ขนาดบรรจุภัณฑ์: **100 x MTR**

- Number of Pairs: 1
- Cross Sectional Area: 0.35 mm²
- Number of Cores: 2
- American Wire Gauge: 22 AWG
- Screened/Unscreened: Screened
- Length: 100 m
- Shield Type: Aluminium Foil-PET Tape
- Sheath Colour: Grey



8606704 1

CONNECTOR, TEST, TERMINAL POST, 4MM BUNG

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Colour: Red/Black
 - Length: 4 mm
 - Type: Banana Plug



2615064 Red/Black

SPRING TERMINAL M4S SPT2 BLACK/RED

- ขนาดบรรจุภัณฑ์: **1 x PR**
- Colour: Black, Red
 - Current Rating: 15 A
 - Voltage Rating: 48 V
 - Hole Diameter: 7.2 mm



1873803 Black, Red

TERMINAL TP6S BLACK/RED GOLD ASSEM

- ขนาดบรรจุภัณฑ์: **1 x PR**
- Colour: Black, Red
 - Contact Plating: Gold
 - Current Rating: 30 A
 - Hole Diameter: 7.2 mm



1873804 Black, Red

NI PLATE BRASS TERMINAL BINDING POST, 30A

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Colour: Silver
 - Contact Material: Brass
 - Contact Plating: Nickel
 - Current Rating: 30 A
 - Height Above Panel: 22 mm
 - Maximum Panel Thickness: 12.5 mm
 - Hole Diameter: 5 mm



6684590 Silver

RS PRO RS330 CLAMP METER, MAX CURRENT 400A AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Absolute Maximum AC Current Measurement: 400 A ac
 - Absolute Maximum AC Voltage Measurement: 600 V ac
 - Absolute Maximum DC Voltage Measurement: 600 V dc
 - Absolute Maximum Resistance Measurement: 20 MΩ
 - Model Number: RS330
 - AC Current Measurement Resolution: 1 mA
 - Clamp Meter Type: AC Auto-Ranging Clamp Meter
 - Best AC Current Accuracy: $\pm(2\% \text{ rdg} + 4\text{dgt})$



1231936 400 A ac

RS PRO ILCM03A CLAMP METER, MAX CURRENT 60A AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Absolute Maximum AC Current Measurement: 60 A ac
 - Absolute Maximum AC Voltage Measurement: 400 V ac
 - Absolute Maximum Resistance Measurement: 400 Ω
 - Model Number: ILCM03A
 - AC Current Measurement Resolution: 10 μA
 - Clamp Meter Type: Leakage Clamp Meter
 - Best AC Current Accuracy: $\pm(1\% \text{ rdg} + 3\text{dgt})$
 - Best AC Voltage Accuracy: $\pm(1.5\% \text{ rdg} + 2\text{dgt})$



1232204 60 A ac

RS PRO ICM136R CLAMP METER, 600A DC, MAX CURRENT 600A AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Absolute Maximum AC Current Measurement: 600 A ac
 - Absolute Maximum DC Current Measurement: 600 A dc
 - Absolute Maximum AC Voltage Measurement: 600 V ac
 - Absolute Maximum DC Voltage Measurement: 600 V dc
 - Absolute Maximum Resistance Measurement: 400 Ω
 - Model Number: ICM136R
 - AC Current Measurement Resolution: 100 mA
 - DC Current Measurement Resolution: 100 mA



1233222 600 A ac

RS PRO ICA39T CURRENT CLAMP ADAPTOR

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Battery Life: 66 h
 - Battery Type: 9V Alkaline
 - Maximum Conductor Size: 51 mm
 - Safety Category: CAT III 1000 V
 - Minimum Operating Temperature: 0 °C
 - Safety Category Level: CAT III
 - Safety Category Voltage: 1000 V
 - Maximum Operating Temperature: +50 °C



1233224 66 h

RS PRO ICM139R CLAMP METER, 1KA DC, MAX CURRENT 1KA AC CAT III

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Absolute Maximum AC Current Measurement: 1 kA ac
 - Absolute Maximum DC Current Measurement: 1 kA dc
 - Absolute Maximum AC Voltage Measurement: 750 V ac
 - Absolute Maximum DC Voltage Measurement: 1000 V dc
 - Absolute Maximum Resistance Measurement: 400 Ω
 - Model Number: ICM139R
 - AC Current Measurement Resolution: 100 mA
 - DC Current Measurement Resolution: 100 mA



1233227 1 kA ac

RS PRO ICM20 CLAMP METER, MAX CURRENT 400A AC CAT III 600 V

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Absolute Maximum AC Current Measurement: 400 A ac
 - Model Number: ICM20
 - AC Current Measurement Resolution: 100 mA
 - Clamp Meter Type: AC Current Clamp Meter
 - Best AC Current Accuracy: $\pm(2\% \text{ rdg} + 0.5\text{A})$
 - Functions Measured: AC Current, Continuity, Diode Test
 - Maximum Conductor Size: 27 (Dia.) mm
 - Maximum Operating Temperature: +50 °C



1233230 400 A ac

RS PRO ICMA6 CLAMP METER, MAX CURRENT 600A AC CAT II 1000 V, CAT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Absolute Maximum AC Current Measurement: 600 A ac
 - Absolute Maximum DC Voltage Measurement: 750 V dc
 - Absolute Maximum AC Voltage Measurement: 1000 V ac
 - Absolute Maximum Resistance Measurement: 2 kΩ
 - Model Number: ICMA6
 - AC Current Measurement Resolution: 100 mA
 - Clamp Meter Type: AC Current Clamp Meter
 - Best AC Current Accuracy: $\pm(1.9\% \text{ rdg} + 5\text{dgt})$



1233234 600 A ac

RS PRO ICM30R CLAMP METER, 300A DC, MAX CURRENT 300A AC CAT III

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Absolute Maximum AC Current Measurement: 300 A ac
 - Absolute Maximum DC Current Measurement: 300 A dc
 - Absolute Maximum AC Voltage Measurement: 600 V ac
 - Absolute Maximum DC Voltage Measurement: 600 V dc
 - Absolute Maximum Resistance Measurement: 40 MΩ
 - Model Number: ICM30R
 - AC Current Measurement Resolution: 10 mA
 - DC Current Measurement Resolution: 10 mA



1233252 300 A ac

RS PRO ICMA1 CLAMP METER, 300A DC, MAX CURRENT 300A AC CAT III

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Absolute Maximum AC Current Measurement: 300 A ac
 - Absolute Maximum DC Current Measurement: 300 A dc
 - Model Number: ICMA1
 - AC Current Measurement Resolution: 10 mA
 - DC Current Measurement Resolution: 10 mA
 - Best DC Current Accuracy: $\pm(1.5\% \text{ rdg} + 5\text{dgt})$
 - Clamp Meter Type: AC/DC Clamp Meter
 - Best AC Current Accuracy: $\pm(1.5\% \text{ rdg} + 5\text{dgt})$



1233256 300 A ac

RS PRO CURRENT CLAMP, AC ADAPTER, 400A AC MAX, TEST LEAD,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Adapter Type: AC
 - Maximum AC Current: 400 A ac
 - Best Accuracy: $\pm 1.9\% + 0.5 \text{ A}$
 - Resolution: 1 mV/A
 - Maximum Conductor Size: 29 mm
 - Safety Category: CAT II 600 V
 - Output Type: Current, Voltage
 - Connector Type: Test Lead



1233223 AC

RS PRO CURRENT CLAMP, AC ADAPTER, 300A AC MAX, CURRENT,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Adapter Type: AC
 - Maximum AC Current: 300 A ac
 - Best Accuracy: $\pm 1.9\% + 5 \text{ Digits}$
 - Resolution: 0.1 A
 - Maximum Conductor Size: 29 mm
 - Safety Category: CAT III 1000 V, CAT IV 600 V
 - Output Type: Current, Voltage
 - Maximum Operating Temperature: +50 °C



1238651 AC

RS PRO CURRENT PROBE, AC ADAPTER, 3KA AC MAX

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Adapter Type: AC, Rogowski Coil
 - Maximum AC Current: 3 kA ac
 - Best Accuracy: $\pm 3\%$
 - Safety Category: CAT III 1000 V, CAT IV 600 V
 - Battery Type: AAA
 - Safety Category Level: CAT III, CAT IV
 - Safety Category Voltage: 600 V, 1000 V



1611631 AC, Rogowski

RS PRO CROCODILE CLIP

ขนาดบรรจุภัณฑ์: **1 x EA**
 • Accessory Type: Crocodile Clip



218100 Crocodile Clip

RS PRO CROCODILE CLIP

ขนาดบรรจุภัณฑ์: **1 x SET**
 • Accessory Type: Crocodile Clip Set



816170 Crocodile Clip

RS PRO CROCODILE CLIP

ขนาดบรรจุภัณฑ์: **1 x EA**
 • Accessory Type: Crocodile Clip



1253738 Crocodile Clip

CROCODILE CLIP FOR MULTIMETER TEST LEADS

ขนาดบรรจุภัณฑ์: **1 x EA**
 • Accessory Type: Crocodile Clip



1253740 Crocodile Clip

CONNECTOR,TEST,CLIP,SET,INSULATED,FLUKE 80,MULTIMETER

ขนาดบรรจุภัณฑ์: **1 x PR**
 • Accessory Type: Crocodile Clip Set



2647881 Crocodile Clip

RS PRO CROCODILE CLIP

ขนาดบรรจุภัณฑ์: **1 x PR**
 • Accessory Type: Crocodile Clip
 • For Use With: Multimeter



3402566 Crocodile Clip

RS PRO CROCODILE CLIP

ขนาดบรรจุภัณฑ์: **1 x SET**
 • Accessory Type: Crocodile Clip
 • For Use With: Multimeter



4935556 Crocodile Clip

RS PRO IET1700 EARTH TESTER 4KΩ

ขนาดบรรจุภัณฑ์: **1 x EA**
 • Absolute Maximum Resistance Measurement: 4 kΩ
 • Best Accuracy: ±2% + 3 Digits
 • Display Type: LCD
 • Battery Type: AA
 • Power Source: Battery
 • Weight: 800 g
 • Height: 80 mm
 • Includes: 1 Set Test Lead, 4 x Auxiliary Earth Spikes, 8 x Battery, Carrying Case, Manual, Neck Strap



1232238 4 kΩ

ET5300 EARTH RESISTANCE TESTER- 4 WIRE

ขนาดบรรจุภัณฑ์: **1 x EA**
 • Absolute Maximum Resistance Measurement: 2 kΩ
 • Best Accuracy: ±2 %
 • Display Type: LED
 • Battery Type: AA
 • Power Source: Battery
 • Weight: 700 g
 • Height: 50 mm
 • Includes: Battery x 6, Carrying Case, Iron Rods x 4, Manual, Sets Test Kits x 4



1445339 2 kΩ

CONNECTOR,TEST,TERMINAL POST,MOUNT PLATE

ขนาดบรรจุภัณฑ์: **5 x EA**
 • Length: 35 mm
 • Enclosure Mounting Type: Mounting Plate
 • Colour: Black



404856 35 mm

RS PRO FIBRE OPTIC CLEANING PEN FOR FIBRE OPTIC CONNECTORS, 40

ขนาดบรรจุภัณฑ์: **1 x EA**
 • Cleaner Type: Pen
 • Application: Fibre Optic Connectors
 • Package Type: Pen
 • Package Size: 40 g
 • Size: 18 x 18 x 22 mm



2048308 Pen

RS PRO FIBRE OPTIC CLEANING PEN FOR FIBRE OPTIC CONNECTORS, 40

ขนาดบรรจุภัณฑ์: **1 x EA**
 • Cleaner Type: Pen
 • Application: Fibre Optic Connectors
 • Package Type: Pen
 • Package Size: 40 g
 • Size: 18 x 18 x 22 mm



2048309 Pen

RS PRO BLACK 1 MM² TEST LEAD WIRE, 1200MM, SILICONE

ขนาดบรรจุภัณฑ์: **5 x EA**
 • Cross Sectional Area: 1 mm²
 • Sheath Colour: Black
 • Length: 1200 mm
 • Insulation Material: Silicone
 • Voltage Rating: 1000 V
 • Outer Diameter: 3.55 mm
 • Current Rating: 20 A
 • Conductor Material: Copper



2070881 1 mm²

RS PRO RED 1 MM² TEST LEAD WIRE, 1200MM, SILICONE INSULATION

ขนาดบรรจุภัณฑ์: **5 x EA**
 • Cross Sectional Area: 1 mm²
 • Sheath Colour: Red
 • Length: 1200 mm
 • Insulation Material: Silicone
 • Voltage Rating: 1000 V
 • Outer Diameter: 3.55 mm
 • Current Rating: 20 A
 • Conductor Material: Copper



2070882 1 mm²

RS PRO RS5500 INSULATION TESTER, 250V MIN, 1000V MAX, 2GΩ MAX, CAT

ขนาดบรรจุภัณฑ์: **1 x EA**
 • Tester Type: Insulation Tester
 • Minimum Test Voltage: 250 V
 • Maximum Test Voltage: 1000 V
 • Maximum Insulation Resistance Measurement: 2 GΩ
 • Display Type: LCD
 • Test Current: ≤200 mA
 • Minimum Operating Temperature: 0 °C
 • Maximum Operating Temperature: +40 °C



1231931 Insulation Tester

GHT114 TEST LEAD CLIP HIGH VOLTAGE PROBE

ขนาดบรรจุภัณฑ์: **1 x EA**
 • Accessory Type: Test Lead Clip High Voltage Probe



9176314 Test Lead Clip

RS PRO IDM103N HANDHELD DIGITAL MULTIMETER, 10A AC MAX, 10A DC

ขนาดบรรจุภัณฑ์: 1 x EA

- Multimeter Type: Handheld
- True RMS: No
- Functions Measured: AC Current, AC Voltage, DC Current, DC Voltage, Frequency, Resistance
- Absolute Maximum AC Voltage Measurement: 1000 V ac
- Absolute Maximum DC Voltage Measurement: 1000 V dc
- Absolute Maximum DC Current Measurement: 10 A dc
- Absolute Maximum Resistance Measurement: 40 MΩ



1233235 Handheld

RS PRO IDM72 HANDHELD DIGITAL MULTIMETER, TRUE RMS, 10A AC MAX,

ขนาดบรรจุภัณฑ์: 1 x EA

- Multimeter Type: Handheld
- True RMS: Yes
- Functions Measured: AC Current, AC Voltage, Capacitance, Continuity, DC Current, DC Voltage, Diode, Frequency, Resistance
- Absolute Maximum Resistance Measurement: 60 MΩ
- Absolute Maximum DC Voltage Measurement: 1000 V dc
- Absolute Maximum AC Voltage Measurement: 750 V ac
- Absolute Maximum DC Current Measurement: 10 A dc
- Absolute Maximum AC Current Measurement: 10 A ac



1233242 Handheld

RS PRO IDM93N HANDHELD DIGITAL MULTIMETER, 10A AC MAX, 10A DC

ขนาดบรรจุภัณฑ์: 1 x EA

- Multimeter Type: Handheld
- True RMS: No
- Functions Measured: AC Current, AC Voltage, Capacitance, Conductance, DC Current, DC Voltage, Diode, Frequency, Resistance, RMS, Temperature
- Absolute Maximum DC Current Measurement: 10 A dc
- Absolute Maximum DC Voltage Measurement: 600 V dc
- Absolute Maximum Resistance Measurement: 20 MΩ
- Absolute Maximum AC Current Measurement: 10 A ac
- Absolute Maximum AC Voltage Measurement: 600 V ac



1233245 Handheld

RS PRO IDM5A HANDHELD DIGITAL MULTIMETER, 4mA AC MAX, 4mA DC

ขนาดบรรจุภัณฑ์: 1 x EA

- Multimeter Type: Handheld
- True RMS: No
- Functions Measured: AC Current, AC Voltage, Capacitance, Conductance, DC Current, DC Voltage, Diode, Frequency, Resistance, RMS, Temperature
- Absolute Maximum DC Voltage Measurement: 600 V dc
- Absolute Maximum DC Current Measurement: 4 mA dc
- Absolute Maximum AC Voltage Measurement: 600 V ac
- Absolute Maximum AC Current Measurement: 4 mA ac
- Absolute Maximum Resistance Measurement: 40 MΩ



1233251 Handheld

RS PRO FUSED, CROCODILE CLIP, 1M, CAT III

ขนาดบรรจุภัณฑ์: 1 x EA

- Lead Type: Test Lead
- Connector Type: Crocodile Clip
- Fused: Yes
- Lead Length: 1 m
- Safety Category Voltage: 600 V
- Safety Category: CAT III 600 V
- Safety Category Level: CAT III



212988 Test Lead

RS PRO FUSED FUSED PROBE KIT, RIGHT ANGLE PLUG, 1.2M, CAT III

ขนาดบรรจุภัณฑ์: 1 x EA

- Lead Type: Fused Probe Kit
- Connector Type: Right Angle Plug
- Fused: Yes
- Lead Length: 1.2 m
- Safety Category Voltage: 600, 1000 V
- Safety Category: CAT III 1000 V, CAT III 600 V
- Minimum Operating Temperature: -10 °C
- Maximum Operating Temperature: +150 °C



204583 Fused Probe Kit

RS PRO FUSED FUSED PROBE KIT, STRAIGHT PLUG, 1.2M, CAT III

ขนาดบรรจุภัณฑ์: 1 x EA

- Lead Type: Fused Probe Kit
- Connector Type: Straight Plug
- Fused: Yes
- Lead Length: 1.2 m
- Safety Category Voltage: 600, 1000 V
- Safety Category: CAT III 1000 V, CAT III 600 V
- Minimum Operating Temperature: -10 °C
- Maximum Operating Temperature: +150 °C



204599 Fused Probe Kit

RS PRO FUSED, CROCODILE CLIP, CAT II, CAT III

ขนาดบรรจุภัณฑ์: 1 x EA

- Lead Type: Test Lead
- Connector Type: Crocodile Clip
- Fused: Yes
- Safety Category Voltage: 600/1000 V
- Safety Category: CAT II 1000 V, CAT III 600 V
- Safety Category Level: CAT II, CAT III



816029 Test Lead

RS PRO AUTOMOTIVE TEST LEAD KIT, CROCODILE CLIP, 1.2M, 155MM, 10A

ขนาดบรรจุภัณฑ์: 1 x KT

- Lead Type: Automotive Test Lead Kit
- Connector Type: Crocodile Clip
- Lead Length: 1.2m, 155mm, 25mm, 44 mm
- Current Rating: 10 A
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +70 °C



1247400 Automotive Test

RS PRO TEST LEAD KIT, 10A

ขนาดบรรจุภัณฑ์: 1 x PR

- Lead Type: Test Lead Kit
- Product Type: Automotive Back Probe with Cable Piercer Adapter
- Current Rating: 10 A
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +70 °C



1247405 Test Lead Kit

RS PRO TEST LEAD KIT, CAT II, 20A

ขนาดบรรจุภัณฑ์: 1 x PR

- Lead Type: Test Lead Kit
- Product Type: Automotive Long Reach Sharp Prod
- Current Rating: 20 A
- Safety Category: CAT II 1000 V
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +70 °C
- Safety Category Level: CAT II



1247406 Test Lead Kit

RS PRO FUSED, CROCODILE CLIP

ขนาดบรรจุภัณฑ์: 1 x EA

- Lead Type: Test Lead
- Connector Type: Crocodile Clip
- Fused: Yes



1253730 Test Lead

RS PRO FUSED TEST LEAD KIT, RIGHT ANGLE PLUG, 1.25M, CAT III

ขนาดบรรจุภัณฑ์: 1 x EA

- Lead Type: Test Lead Kit
- Connector Type: Right Angle Plug
- Fused: Yes
- Lead Length: 1.25 m
- Safety Category Voltage: 1000 V
- Safety Category: CAT III 1000 V
- Safety Category Level: CAT III



1253731 Test Lead Kit

RS PRO TEST LEAD KIT, CROCODILE CLIP, RIGHT ANGLE PLUG, 1.2M, CAT III

ขนาดบรรจุภัณฑ์: 1 x EA

- Lead Type: Test Lead Kit
- Connector Type: Crocodile Clip, Right Angle Plug
- Lead Length: 1.2 m
- Current Rating: 15 A
- Safety Category Voltage: 1000 V
- Safety Category: CAT III 1000 V
- Safety Category Level: CAT III



1253733 Test Lead Kit

RS PRO TEST LEAD KIT, CROCODILE CLIP, RIGHT ANGLE PLUG, SPRING

ขนาดบรรจุภัณฑ์: 1 x EA

- Lead Type: Test Lead Kit
- Connector Type: Crocodile Clip, Right Angle Plug, Spring Hook, Straight Plug
- Lead Length: 1.2 m
- Current Rating: 15 A
- Safety Category Voltage: 1000 V
- Safety Category: CAT III 1000 V
- Safety Category Level: CAT III



1253735 Test Lead Kit

RS PRO, 1.2M, CAT III, CAT IV, 20A

ขนาดบรรจุภัณฑ์: 1 x EA

- Lead Type: Test Lead
- Lead Length: 1.2 m
- Current Rating: 20 A
- Safety Category Voltage: 600 V, 1000 V
- Safety Category: CAT III, CAT IV, 600 V, 1000 V
- Safety Category Level: CAT III, CAT IV



1253736 Test Lead

RS PRO FUSED FUSED PROBE KIT, RIGHT ANGLE TO STRAIGHT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Lead Type: Fused Probe Kit
 - Connector Type: Right Angle to Straight
 - Fused: Yes
 - Safety Category Voltage: 1000 V
 - Safety Category: CAT III 1000 V



1999851 Fused Probe Kit

RS PRO TEST LEAD KIT, CROCODILE CLIP, RIGHT ANGLE PLUG, 1.2M, CAT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Lead Type: Test Lead Kit
 - Connector Type: Crocodile Clip, Right Angle Plug
 - Lead Length: 1.2 m
 - Current Rating: 10 A
 - Safety Category Voltage: 1000 V
 - Safety Category: CAT III 1000 V
 - Safety Category Level: CAT III



2432998 Test Lead Kit

RS PRO TEST LEAD KIT, CROCODILE CLIP, SOCKET, 1.2M, 10A

- ขนาดบรรจุภัณฑ์: **1 x KT**
- Lead Type: Test Lead Kit
 - Connector Type: Crocodile Clip, Socket
 - Lead Length: 1.2 m
 - Current Rating: 10 A



6120835 Test Lead Kit

RS PRO FUSED TEST LEAD KIT, CROCODILE CLIP, RIGHT ANGLE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Lead Type: Test Lead Kit
 - Connector Type: Crocodile Clip, Right Angle Plug, Spring Hook, Straight Plug
 - Fused: Yes
 - Lead Length: 1.2 m
 - Safety Category Voltage: 600 V
 - Safety Category: CAT III 600 V
 - Minimum Operating Temperature: -20 °C
 - Maximum Operating Temperature: +70 °C



7315273 Test Lead Kit

RS PRO TEST LEAD KIT, CROCODILE CLIP, RIGHT ANGLE PLUG, SPRING

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Lead Type: Test Lead Kit
 - Connector Type: Crocodile Clip, Right Angle Plug, Spring Hook, Straight Plug
 - Lead Length: 1.2 m
 - Safety Category Voltage: 600 V
 - Safety Category: CAT III 600 V
 - Minimum Operating Temperature: -20 °C
 - Maximum Operating Temperature: +70 °C
 - Safety Category Level: CAT III



7315277 Test Lead Kit

RS PRO MULTI PIN CONNECTOR TEST KIT, CROCODILE CLIP, PIN SOCKET,

- ขนาดบรรจุภัณฑ์: **1 x KT**
- Lead Type: Multi Pin Connector Test Kit
 - Connector Type: Crocodile Clip, Pin Socket, Right Angle Plug
 - Lead Length: 1.2 m
 - Current Rating: 20 A
 - Safety Category Voltage: 1000 V
 - Safety Category: CAT III 1000 V
 - Safety Category Level: CAT II



7315286 Multi Pin

INDICATOR, NONCONTACT, AC VOLT STICK

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Indicator Type: Voltage
 - Battery Type: AAA
 - Power Source: Battery
 - Maximum Detection Voltage: 400 V ac
 - Maximum Operating Temperature: +50 °C
 - Minimum Operating Temperature: -20 °C



214467 Voltage

RS PRO VOLT-STICK PRO NON CONTACT VOLTAGE DETECTOR, 230V

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Indicator Type: Voltage
 - Battery Type: AAA
 - Power Source: Battery
 - Safety Category: CAT III 1000 V
 - Weight: 40 g
 - Diameter: 18 mm
 - Length: 146 mm
 - Maximum Detection Voltage: 1000 V ac



166838 Voltage

PROVING, UNIT, VOLTSTICK AUDIO

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Indicator Type: Voltage
 - Battery Type: AAA
 - Audible Tone: Yes
 - Power Source: Battery
 - Safety Category: CAT III 1000 V
 - Weight: 40 g
 - Diameter: 17 mm
 - Length: 146 mm



167645 Voltage

RS PRO IVP-1 NONCONTACT VOLTAGE INDICATOR

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Indicator Type: Voltage
 - Battery Type: AAA
 - Power Source: Battery
 - Safety Category: CAT III 1000 V / CAT IV 600 V, CAT IV, CAT III
 - Weight: 40 g
 - Height: 18 mm
 - Length: 152 mm
 - Maximum Detection Voltage: 1000 V ac



1233247 Voltage

VOLTAGE TESTER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Indicator Type: Voltage
 - Battery Type: AAA
 - Power Source: Battery
 - Safety Category: CAT III 1000 V, CAT IV 600 V
 - Weight: 34 g
 - Height: 158 mm
 - Length: 25 mm
 - Maximum Detection Voltage: 1000 V ac



1611627 Voltage

RS PRO NON CONTACT VOLTAGE INDICATOR

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Indicator Type: Voltage
 - Battery Type: AAA
 - Power Source: Battery
 - Maximum Operating Temperature: +50 °C
 - Minimum Operating Temperature: -20 °C



2383571 Voltage

INDICATOR, MAGNETIC FIELD, MAGNET STICK

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Indicator Type: Magnetic Field
 - Magnetic Sensitivity: 0.3 mT
 - Battery Type: AAA
 - Power Source: Battery
 - Safety Category: CAT III 1000 V
 - Weight: 40 g
 - Diameter: 17 mm
 - Length: 152 mm



3755422 Magnetic Field

RS PRO RS9020 PHASE ROTATION TESTER, CAT III 300 V, 400HZ MAX,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Connection Type: Crocodile Clip
 - Overvoltage Category: CAT III 600V
 - Safety Category: CAT III 300 V
 - Non-Contact: Non Contact
 - Current Consumption: 20 mA
 - Battery Life: 1 (Minimum) yr
 - Battery Type: 9V Alkaline
 - Power Source: Battery



1231932 Crocodile Clip

RS PRO RS9010 PHASE ROTATION TESTER, CAT III 600 V, CAT IV 300 V,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Connection Type: Crocodile Clip
 - Overvoltage Category: CAT III 600V, CAT IV 300V
 - Display Type: LCD
 - Safety Category: CAT III 600 V, CAT IV 300 V
 - Current Consumption: 1 mA
 - Power Source: Mains
 - Dimensions: 130 x 69 x 32 mm
 - Weight: 130 g



1231933 Crocodile Clip

RS PRO IPM6300 POWER QUALITY ANALYSER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Absolute Maximum Current Measurement: 3000 A
 - Absolute Maximum Power Measurement: 9999 kW
 - Maximum Voltage: 600 V
 - Best Voltage Measurement Accuracy: ±0.5 % ± 5 Digits
 - Best Current Measurement Accuracy: 1 %
 - Display Type: LCD
 - Measurement Type: AC Current, AC Voltage, AC Wattage, Harmonic, Phase Angle, Power Factor, Total Harmonic Distortion
 - Interface Type: RS232C



1232201 3000 A

RS PRO PT100 RTD SENSOR, 30MM LONG, PATCH SENSOR, +150°C MAX

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Type: PT100
 - Probe Length: 30 mm
 - Maximum Temperature Sensed: +150 °C
 - Cable Length: 1 m, 1 mm
 - Process Connection: Patch Sensor



7887132 PT100

RS PRO K NEEDLE TEMPERATURE PROBE, 300MM LENGTH, 6MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Type: K
 - Probe Type: Needle
 - Probe Length: 300 mm
 - Probe Diameter: 6 mm
 - Maximum Temperature Measurement: +250 °C
 - Cable Length: 2 m
 - Best Accuracy: ±0.5 %
 - Connector Type: Miniature Plug



255516 K

RS PRO K BOW SURFACE TEMPERATURE PROBE, 110MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Type: K
 - Probe Type: Surface
 - Probe Tip Type: Bow
 - Probe Length: 110 mm
 - Probe Diameter: 60 mm
 - Maximum Temperature Measurement: +180 °C
 - Cable Length: 2 m
 - Best Accuracy: ±0.25 %



255550 K

RS PRO K FLAT SPATULA TEMPERATURE PROBE, 200MM


- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Type: K
 - Probe Tip Type: Flat Spatula
 - Probe Length: 200 mm
 - Probe Diameter: 7 mm
 - Maximum Temperature Measurement: +450 °C
 - Cable Length: 2 m
 - Best Accuracy: ±0.25 %
 - Connector Type: Miniature Plug



255566 K

RS PRO K NEEDLE TEMPERATURE PROBE, 300MM LENGTH, 3.3MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Type: K
 - Probe Type: Needle
 - Probe Length: 300 mm
 - Probe Diameter: 3.3 mm
 - Maximum Temperature Measurement: +250 °C
 - Cable Length: 2 m
 - Best Accuracy: ±0.5 %
 - Connector Type: Miniature Plug



255572 K

RS PRO K GENERAL TEMPERATURE PROBE, 1000MM LENGTH, 6MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Type: K
 - Probe Type: General
 - Probe Length: 1000 mm
 - Probe Diameter: 6 mm
 - Maximum Temperature Measurement: +1100 °C
 - Cable Length: 2 m
 - Best Accuracy: ±0.25 %
 - Connector Type: Miniature Thermocouple Plug



255588 K

RS PRO K GENERAL TEMPERATURE PROBE, 300MM LENGTH, 1.5MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Type: K
 - Probe Type: General
 - Probe Length: 300 mm
 - Probe Diameter: 1.5 mm
 - Maximum Temperature Measurement: +1100 °C
 - Cable Length: 2 m
 - Best Accuracy: ±0.25 %
 - Connector Type: Miniature Plug



255594 K

RS PRO NTC AIR TEMPERATURE PROBE, 41MM LENGTH, 6MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Type: NTC
 - Probe Type: Air
 - Probe Length: 41 mm
 - Probe Diameter: 6 mm
 - Maximum Temperature Measurement: +80 °C
 - Cable Length: 1.5 m
 - Best Accuracy: ±0.5 °C



1241079 NTC

RS PRO NTC AIR TEMPERATURE PROBE, 15MM LENGTH, 6MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Type: NTC
 - Probe Type: Air
 - Probe Length: 15 mm
 - Probe Diameter: 6 mm
 - Maximum Temperature Measurement: +105 °C
 - Cable Length: 1.5 m
 - Best Accuracy: ±0.5 °C



1241080 NTC

RS PRO NTC AIR TEMPERATURE PROBE, 40MM LENGTH, 6MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Type: NTC
 - Probe Type: Air
 - Probe Length: 40 mm
 - Probe Diameter: 6 mm
 - Maximum Temperature Measurement: +150 °C
 - Cable Length: 1.5 m
 - Best Accuracy: ±0.5 °C



1241081 NTC

RS PRO NTC LIQUID TEMPERATURE PROBE, 48MM LENGTH, 6MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Type: NTC
 - Probe Type: Liquid
 - Probe Length: 48 mm
 - Probe Diameter: 6 mm
 - Maximum Temperature Measurement: +150 °C
 - Cable Length: 1.5 m
 - Best Accuracy: ±0.5 °C



1241082 NTC

RS PRO TEMPERATURE PROBE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 12 mm
 - Probe Length: 40 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +900 °C
 - Termination Type: Miniature Plug
 - Cable Length: 1.5 m



1741675 K

RS PRO TEMPERATURE PROBE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Length: 170 mm
 - Probe Material: Stainless Steel
 - Termination Type: Miniature Plug
 - Cable Length: 1.5 m



1741679 K

RS PRO TEMPERATURE PROBE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 3.3 mm
 - Probe Length: 300 mm
 - Probe Material: 316 Stainless Steel
 - Maximum Temperature Sensed: +400 °C
 - Termination Type: Miniature Plug
 - Cable Length: 2 m
 - Standards Met: IEC



1741680 K

RS PRO TEMPERATURE PROBE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 3.3 mm
 - Probe Length: 300 mm
 - Probe Material: 316 Stainless Steel
 - Maximum Temperature Sensed: +400 °C
 - Termination Type: Miniature Plug
 - Cable Length: 2 m
 - Standards Met: ANSI



1741681 K

RS PRO TEMPERATURE PROBE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 3 mm
 - Probe Length: 300 mm
 - Maximum Temperature Sensed: +850 °C
 - Termination Type: Miniature Plug
 - Cable Length: 2 m
 - Standards Met: IEC



1741683 K

RS PRO TEMPERATURE PROBE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 1.5 mm
 - Probe Length: 100 mm
 - Maximum Temperature Sensed: +850 °C
 - Termination Type: Miniature Plug
 - Cable Length: 2 m
 - Standards Met: ANSI



1741684 K

RS PRO NTC PERFORATED AIR TEMPERATURE PROBE, 110MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: NTC
 - Probe Type: Air
 - Probe Tip Type: Perforated
 - Probe Length: 110 mm
 - Probe Diameter: 4 mm
 - Maximum Temperature Measurement: 150 °C
 - Cable Length: 2 m
 - Best Accuracy: ± 0.2 °C ($\pm 0.15\%$)



2048387 NTC

RS PRO NTC NEEDLE INSERTION TEMPERATURE PROBE, 115MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: NTC
 - Probe Type: Insertion
 - Probe Tip Type: Needle
 - Probe Length: 115 mm
 - Probe Diameter: 3.3 mm
 - Maximum Temperature Measurement: 150 °C
 - Cable Length: 2 m
 - Best Accuracy: ± 0.2 °C ($\pm 0.15\%$)



2048388 NTC

RS PRO NTC FLAT INSERTION TEMPERATURE PROBE, 100MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: NTC
 - Probe Type: Insertion
 - Probe Tip Type: Flat Shaft
 - Probe Length: 100 mm
 - Probe Diameter: 85 x 3 x 5 mm
 - Maximum Temperature Measurement: 150 °C
 - Cable Length: 2 m
 - Best Accuracy: ± 0.2 °C ($\pm 0.15\%$)



2048389 NTC

RS PRO K GENERAL TEMPERATURE PROBE, 210MM LENGTH, 3MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: K
 - Probe Type: General
 - Probe Length: 210 mm
 - Probe Diameter: 3 mm
 - Maximum Temperature Measurement: 1100 °C
 - Cable Length: 1 m
 - Best Accuracy: ± 1.5 °C ($\pm 0.25\%$)
 - Connector Type: Miniature Plug



2048390 K

RS PRO K PERFORATED AIR TEMPERATURE PROBE, 110MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: K
 - Probe Type: Air
 - Probe Tip Type: Perforated
 - Probe Length: 110 mm
 - Probe Diameter: 3 mm
 - Maximum Temperature Measurement: 750 °C
 - Cable Length: 1.2 m
 - Best Accuracy: ± 1.5 °C ($\pm 0.25\%$)



2048393 K

RS PRO K SURFACE TEMPERATURE PROBE, 200MM LENGTH, 12MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: K
 - Probe Type: Surface
 - Probe Length: 200 mm
 - Probe Diameter: 12 mm
 - Maximum Temperature Measurement: 600 °C
 - Cable Length: 1 m
 - Best Accuracy: ± 1.5 °C ($\pm 0.25\%$)
 - Connector Type: Miniature Plug



2048394 K

RS PRO K MAGNETIC SURFACE TEMPERATURE PROBE, 5MM LENGTH,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: K
 - Probe Type: Surface
 - Probe Tip Type: Magnetic
 - Probe Length: 5 mm
 - Probe Diameter: 10 mm
 - Maximum Temperature Measurement: 1372 °C
 - Cable Length: 2 m
 - Best Accuracy: ± 1.5 °C ($\pm 0.25\%$)



2048396 K

RS PRO K NEEDLE TEMPERATURE PROBE, 115MM LENGTH, 3.3MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: K
 - Probe Tip Type: Needle
 - Probe Length: 115 mm
 - Probe Diameter: 3.3 mm
 - Maximum Temperature Measurement: +250 °C
 - Cable Length: 2 m
 - Best Accuracy: ± 0.5 %
 - Connector Type: Miniature Plug



3428833 K

RS PRO T NEEDLE TEMPERATURE PROBE, 115MM LENGTH, 3.3MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: T
 - Probe Type: Needle
 - Probe Length: 115 mm
 - Probe Diameter: 3.3 mm
 - Maximum Temperature Measurement: +400 °C
 - Cable Length: 2 m
 - Best Accuracy: ± 0.15 %
 - Connector Type: Miniature Thermocouple Plug



3428849 T

RS PRO K NEEDLE TEMPERATURE PROBE, 100MM LENGTH, 6MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: K
 - Probe Type: Needle
 - Probe Length: 100 mm
 - Probe Diameter: 6 mm
 - Maximum Temperature Measurement: +250 °C
 - Cable Length: 2 m
 - Best Accuracy: ± 0.5 %
 - Connector Type: Miniature Plug



3428855 K

RS PRO K GENERAL TEMPERATURE PROBE, 100MM LENGTH, 1.5MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: K
 - Probe Type: General
 - Probe Length: 100 mm
 - Probe Diameter: 1.5 mm
 - Maximum Temperature Measurement: +1100 °C
 - Cable Length: 2 m
 - Best Accuracy: ± 0.25 %
 - Connector Type: Miniature Plug



3428883 K

RS PRO K GENERAL TEMPERATURE PROBE, 100MM LENGTH, 3MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: K
 - Probe Type: General
 - Probe Length: 100 mm
 - Probe Diameter: 3 mm
 - Maximum Temperature Measurement: +1100 °C
 - Cable Length: 2 m
 - Best Accuracy: ± 0.25 %
 - Connector Type: Miniature Plug



3428899 K

RS PRO T GENERAL PURPOSE TEMPERATURE PROBE, 100MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: T
 - Probe Type: General Purpose
 - Probe Length: 100 mm
 - Probe Diameter: 1.5 mm
 - Maximum Temperature Measurement: +400 °C
 - Cable Length: 2 m
 - Best Accuracy: ± 0.15 %
 - Connector Type: Miniature Thermocouple Plug



3428912 T

RS PRO K GENERAL TEMPERATURE PROBE, 300MM LENGTH, 3MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: K
 - Probe Type: General
 - Probe Length: 300 mm
 - Probe Diameter: 3 mm
 - Maximum Temperature Measurement: +1100 °C
 - Cable Length: 2 m
 - Best Accuracy: ± 0.25 %
 - Connector Type: Miniature Plug



3428928 K

RS PRO K SURFACE TEMPERATURE PROBE, 110MM LENGTH, 10MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: K
 - Probe Type: Surface
 - Probe Length: 110 mm
 - Probe Diameter: 10 mm
 - Maximum Temperature Measurement: +250 °C
 - Cable Length: 2 m
 - Best Accuracy: ± 0.25 %
 - Connector Type: Miniature Plug



3428956 K

RS PRO K SURFACE TEMPERATURE PROBE, 110MM LENGTH, 6MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Type: K
 - Probe Type: Surface
 - Probe Length: 110 mm
 - Probe Diameter: 6 mm
 - Maximum Temperature Measurement: +600 °C
 - Cable Length: 2 m
 - Best Accuracy: ±0.25 %
 - Connector Type: Miniature Plug



3428962 K

RS PRO K SURFACE TEMPERATURE PROBE, 210MM LENGTH, 12MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Type: K
 - Probe Type: Surface
 - Probe Length: 210 mm
 - Probe Diameter: 12 mm
 - Maximum Temperature Measurement: +1100 °C
 - Cable Length: 2 m
 - Best Accuracy: ±0.25 %
 - Connector Type: Miniature Plug



3428978 K

RS PRO T SURFACE TEMPERATURE PROBE, 100MM LENGTH, 1MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Type: T
 - Probe Type: Surface
 - Probe Length: 100 mm
 - Probe Diameter: 1 mm
 - Maximum Temperature Measurement: +180 °C
 - Cable Length: 2 m
 - Best Accuracy: ±0.25 %
 - Connector Type: Miniature Thermocouple Plug



3428984 T

RS PRO TYPE K THERMOCOUPLE AIR TEMPERATURE PROBE, 110MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Probe Type: Type K Thermocouple
 - Probe Length: 110 mm
 - Probe Diameter: 4 mm
 - Maximum Temperature Measurement: +750 °C
 - Cable Length: 2 m
 - Best Accuracy: ±0.25 %
 - Connector Type: Miniature Plug



3428990 Type K

RS PRO TYPE K THERMOCOUPLE HANDLE PROBE, 3MM DIAMETER,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Probe Type: Type K Thermocouple
 - Probe Diameter: 3 mm
 - Maximum Temperature Measurement: +250 °C
 - Cable Length: 2 m
 - Best Accuracy: ±0.25 %
 - Connector Type: Miniature Plug



3429038 Type K

RS PRO K AIR TEMPERATURE PROBE, 110MM LENGTH, 4MM DIAMETER,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Type: K
 - Probe Type: Air
 - Probe Length: 110 mm
 - Probe Diameter: 4 mm
 - Maximum Temperature Measurement: +750 °C
 - Best Accuracy: ±0.25 %
 - Connector Type: Miniature Plug



3429050 K

RS PRO K GENERAL TEMPERATURE PROBE, 100MM LENGTH, 3MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Type: K
 - Probe Type: General
 - Probe Length: 100 mm
 - Probe Diameter: 3 mm
 - Maximum Temperature Measurement: +750 °C
 - Best Accuracy: ±0.25 %
 - Connector Type: Miniature Plug



3429072 K

RS PRO T GENERAL PURPOSE TEMPERATURE PROBE, 100MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Type: T
 - Probe Type: General Purpose
 - Probe Length: 100 mm
 - Probe Diameter: 3 mm
 - Maximum Temperature Measurement: +250 °C
 - Best Accuracy: ±0.15 %
 - Connector Type: Miniature Plug



3429088 T

RS PRO K INSERTION, NEEDLE TEMPERATURE PROBE, 100MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Type: K
 - Probe Type: Insertion, Needle
 - Probe Length: 100 mm
 - Probe Diameter: 3.3 mm
 - Maximum Temperature Measurement: +250 °C
 - Best Accuracy: ±0.25 %
 - Connector Type: Miniature Plug



3429094 K

RS PRO K SURFACE TEMPERATURE PROBE, 100MM LENGTH, 4MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Type: K
 - Probe Type: Surface
 - Probe Length: 100 mm
 - Probe Diameter: 4 mm
 - Maximum Temperature Measurement: +750 °C
 - Best Accuracy: ±0.25 %
 - Connector Type: Miniature Plug



3429117 K

RS PRO T SURFACE TEMPERATURE PROBE, 110MM LENGTH, 10MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Type: T
 - Probe Type: Surface
 - Probe Length: 110 mm
 - Probe Diameter: 10 mm
 - Maximum Temperature Measurement: +250 °C
 - Best Accuracy: ±0.25 %
 - Connector Type: Miniature Plug



3429139 T

RS PRO TYPE K THERMOCOUPLE TEMPERATURE PROBE KIT, +1100 °C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Probe Type: Type K Thermocouple
 - Maximum Temperature Measurement: +1100 °C
 - Cable Length: 2 m
 - Best Accuracy: ±2.5 %
 - Connector Type: Miniature Plug



3429151 Type K

RS PRO TYPE K THERMOCOUPLE TEMPERATURE PROBE KIT, +1100 °C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Probe Type: Type K Thermocouple
 - Maximum Temperature Measurement: +1100 °C
 - Cable Length: 2 m
 - Best Accuracy: ±2.5 %
 - Connector Type: Miniature Plug



3429189 Type K

RS PRO K PIPE CLAMP SURFACE TEMPERATURE PROBE, 110MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Type: K
 - Probe Type: Surface
 - Probe Tip Type: Pipe Clamp
 - Probe Length: 110 mm
 - Probe Diameter: 25 mm
 - Maximum Temperature Measurement: +150 °C
 - Cable Length: 2 m
 - Best Accuracy: ±0.25 %



3429202 K

RS PRO PT100 AIR TEMPERATURE PROBE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Type: PT100
 - Probe Type: Air
 - Probe Length: 110 mm
 - Probe Diameter: 4 mm
 - Maximum Temperature Measurement: +750 °C
 - Cable Length: 2 m
 - Best Accuracy: ±0.2 %



3482411 PT100

RS PRO PT100 RTD INSERTION, NEEDLE TEMPERATURE PROBE,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Type: PT100 RTD
 - Probe Type: Insertion, Needle
 - Probe Length: 100 mm
 - Probe Diameter: 4 mm
 - Maximum Temperature Measurement: +250 °C
 - Cable Length: 2 m
 - Best Accuracy: ±0.15 %



3482427 PT100 RTD

RS PRO PT100 RTD INSERTION, NEEDLE TEMPERATURE PROBE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100 RTD
 - Probe Type: Insertion, Needle
 - Probe Length: 100 mm
 - Probe Diameter: 3.3 mm
 - Maximum Temperature Measurement: +250 °C
 - Cable Length: 2 m
 - Best Accuracy: ±0.2 %



3482433 PT100 RTD

RS PRO AIR TEMPERATURE PROBE, TYPE K, MAX. +750 °C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: K
 - Probe Type: Air
 - Probe Length: 110 mm
 - Probe Diameter: 30 mm
 - Maximum Temperature Measurement: +750 °C
 - Cable Length: 2 m
 - Best Accuracy: ±0.25 %
 - Connector Type: Miniature Thermocouple Plug



4342421 K

RS PRO SURFACE TEMPERATURE PROBE, TYPE K, MAX. +800 °C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: K
 - Probe Type: Surface
 - Probe Tip Type: Pipe Clip
 - Probe Length: 195 mm
 - Probe Diameter: 6 mm
 - Maximum Temperature Measurement: +800 °C
 - Cable Length: 2 m
 - Best Accuracy: ±0.25 %



4342437 K

RS PRO K IMMERSION, SURFACE TEMPERATURE PROBE, 110MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: K
 - Probe Type: Immersion, Surface
 - Probe Length: 110 mm
 - Probe Diameter: 10 mm
 - Maximum Temperature Measurement: +250 °C
 - Cable Length: 2 m
 - Best Accuracy: ±0.25 %
 - Connector Type: Miniature Plug



7128196 K

RS PRO K IMMERSION TEMPERATURE PROBE, 50MM LENGTH, 4MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: K
 - Probe Type: Immersion
 - Probe Length: 50 mm
 - Probe Diameter: 4 mm
 - Maximum Temperature Measurement: +250 °C
 - Cable Length: 2 m
 - Best Accuracy: ±1.5 °C
 - Connector Type: Miniature Plug



7887144 K

RS PRO K TYPE THERMOCOUPLE CONNECTION CABLE MINI PLUG TO

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Cable Mini Plug to Mini Plug



7887122 Cable Mini Plug

RS PRO T TYPE THERMOCOUPLE CONNECTION CABLE MINI PLUG TO

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Cable Mini Plug to Mini Plug



7887126 Cable Mini Plug

RS PRO ADHESIVE THERMOCOUPLE ATTACHMENT PAD

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Thermo attachment pad



7887148 Thermo

CONNECTOR, TEST, TERMINAL, INSULATED, LARGE, 30A, RED

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Colour: Red
 - Current Rating: 30 A
 - Thread Size: M6
 - Voltage Rating: 3 kV
 - Insulated: Yes
 - Body Material: Phenolic Resin, Tenite Butyrate
 - Maximum Panel Thickness: 25 mm
 - Height Above Panel: 28 mm



444775 Red

CONNECTOR, TEST, TERMINAL, INSULATED, LARGE, 30A, BLACK

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Colour: Black
 - Current Rating: 30 A
 - Thread Size: M6
 - Voltage Rating: 3 kV
 - Insulated: Yes
 - Body Material: Phenolic Resin, Tenite Butyrate
 - Maximum Panel Thickness: 25 mm
 - Height Above Panel: 28 mm



444781 Black

SMALL PANEL TERMINAL, BLACK, 4MM

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Colour: Black
 - Hole Diameter: 4 mm
 - Current Rating: 30 A
 - Thread Size: 2BA
 - Insulated: Yes
 - Body Material: Glass Fibre Reinforced Nylon, PP
 - Maximum Panel Thickness: 7 mm
 - Height Above Panel: 33 mm



6778740 Black

SMALL PANEL TERMINAL, RED, 4MM

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Colour: Red
 - Hole Diameter: 4 mm
 - Current Rating: 30 A
 - Thread Size: 2BA
 - Insulated: Yes
 - Body Material: Glass Fibre Reinforced Nylon, PP
 - Maximum Panel Thickness: 7 mm
 - Height Above Panel: 33 mm



6778746 Red

PANEL TERMINAL POST ASSEMBLY, 4MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Colour: Black, Red
 - Hole Diameter: 4 mm
 - Current Rating: 30 A
 - Thread Size: 2BA
 - Insulated: Yes
 - Body Material: Glass Fibre Reinforced Nylon, PP
 - Height Above Panel: 30 mm



6778759 Black, Red

RS PRO TEST LEAD & CONNECTOR KIT WITH 1 BLACK LEAD ASSEMBLY, 1 RED

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Kit Contents: 1 Black Lead Assembly, 1 Red Lead Assembly



2188293 1 Black Lead

RS PRO TEST LEAD & CONNECTOR KIT WITH 1 BLACK LEAD ASSEMBLY, 1 RED

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Kit Contents: 1 Black Lead Assembly, 1 Red Lead Assembly, 1 x Black Screw-Fit Crocodile Clip, 1 x Red Screw-Fit Crocodile Clip



2188294 1 Black Lead

CONNECTOR, TEST, LEAD, 4MM, EXTENSION REEL, 12M, BLACK

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Extension Reel
 - Cable Length: 12 m
 - Cable Thickness: 1 mm²
 - Cable Colour: Black
 - Plug Size: 4 mm
 - Socket Size: 4 mm
 - Safety Category: CAT III 1000 V, CAT IV 600 V
 - Safety Category Level: CAT III, CAT IV



6120829 Extension Reel

RS PRO TEST LEAD, 10A, 5KV, BLACK, 1M LEAD LENGTH

- ขนาดบรรจุภัณฑ์: 1 x EA
- Lead Length: 1 m
 - Current Rating: 10 A
 - Colour: Black
 - Test Lead Type: 4 mm Connector Test Leads
 - Voltage Rating: 5 kV
 - Connector A Gender: Male
 - Connector A Orientation: Straight



4233175 1 m

TEST LEADS 5000V

- ขนาดบรรจุภัณฑ์: 1 x EA
- Lead Length: 1 m
 - Current Rating: 10 A
 - Colour: Red
 - Test Lead Type: 4 mm Connector Test Leads
 - Voltage Rating: 5 kV
 - Connector A Gender: Male
 - Connector A Orientation: Straight



4233197 1 m

0.5M BLACK TEST LEAD, 4MM PLUG

- ขนาดบรรจุภัณฑ์: 1 x EA
- Lead Length: 500 mm
 - Current Rating: 2.5 A
 - Colour: Black
 - Test Lead Type: 4 mm Connector Test Leads
 - Voltage Rating: 50 V ac
 - Connector A Gender: Male
 - Connector B Gender: Male
 - Connector A Stackable: Yes



6684572 500 mm

0.5M RED TEST LEAD, 4MM PLUG

- ขนาดบรรจุภัณฑ์: 1 x EA
- Lead Length: 500 mm
 - Current Rating: 2.5 A
 - Colour: Red
 - Test Lead Type: 4 mm Connector Test Leads
 - Voltage Rating: 50 V ac
 - Connector A Gender: Male
 - Connector B Gender: Male
 - Connector A Stackable: Yes



6684581 500 mm

1M BLACK TEST LEAD, 4MM PLUG

- ขนาดบรรจุภัณฑ์: 1 x EA
- Lead Length: 1 m
 - Current Rating: 2.5 A
 - Colour: Black
 - Test Lead Type: 4 mm Connector Test Leads
 - Voltage Rating: 50 V ac
 - Connector A Gender: Male
 - Connector B Gender: Male
 - Connector A Stackable: Yes



6684584 1 m

UV EPROM, M27C4001-12F1 512KX8BIT FDIP32W

- ขนาดบรรจุภัณฑ์: 1 x EA
- Lead Length: 1 m
 - Current Rating: 2.5 A
 - Colour: Red
 - Test Lead Type: 4 mm Connector Test Leads
 - Voltage Rating: 50 V ac
 - Connector A Gender: Male
 - Connector B Gender: Male
 - Connector A Stackable: Yes



6684588 1 m

MODULAR TEST LEAD STORAGE RACK

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Modular Lead Storage Rack
 - Number of Slots: 15
 - Maximum Cable Diameter: 16.9 mm
 - Colour: Grey
 - Body Material: Aluminium
 - Dimensions: 350 x 81 x 46 mm
 - Height: 46 mm
 - Length: 350 mm



6684597 Modular Lead

RS PRO POINT TEST PROBE, 1.6MM SOCKET, 2A

- ขนาดบรรจุภัณฑ์: 5 x EA
- Current Rating: 2 A
 - Probe Tip Type: Point
 - Probe Socket Diameter: 1.6 mm



521611 2 A

SMALL ULTRA THIN BACK PROBE SET

- ขนาดบรรจุภัณฑ์: 1 x SET
- Current Rating: 10 A
 - Maximum Operating Temperature: +70 °C
 - Minimum Operating Temperature: -20 °C



1247401 10 A

SMALL ULTRA THIN BACK PROBE SET

- ขนาดบรรจุภัณฑ์: 1 x PR
- Current Rating: 10 A
 - Maximum Operating Temperature: +70 °C
 - Minimum Operating Temperature: -20 °C



1247402 10 A

EXTENDED BACK PROBE SET

- ขนาดบรรจุภัณฑ์: 1 x PR
- Current Rating: 10 A
 - Maximum Operating Temperature: +70 °C
 - Minimum Operating Temperature: -20 °C



1247403 10 A

RIGHT ANGLED BACK PROBE LEAD SET

- ขนาดบรรจุภัณฑ์: 1 x PR
- Current Rating: 10 A
 - Maximum Operating Temperature: +70 °C
 - Minimum Operating Temperature: -20 °C



1247404 10 A

RS PRO TEST PROBE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Maximum Operating Temperature: +150 °C
 - Minimum Operating Temperature: -10 °C



1253732 +150 °C

RS PRO TEST PROBE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Lead Type: Fused Test Prods
 - Connector Type: Banana Jack
 - Fused: Yes
 - Safety Category Voltage: 1000 V
 - Safety Category: CAT III 1000 V
 - Safety Category Level: CAT III



1253734 Fused Test Prods

SPRUNG GRABBER FOR MULTIMETER TEST LEADS

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Grabber



1253739 Grabber

RS PRO TEST PROBE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Lead Type: Extension Lead Set
 - Fused: No
 - Safety Category Voltage: 1000 V
 - Safety Category: CAT III 1000 V



1999852 Extension Lead

RS PRO TEST PROBE

ขนาดบรรจุภัณฑ์: **1 x EA**

- Lead Type: Thin Fine Insulated Prod Set
- Fused: No
- Safety Category Voltage: 1000 V
- Safety Category: CAT III 1000 V



1999853 Thin Fine

RS PRO TYPE K TEMPERATURE PROBE 1500MM LENGTH, 7/0.2MM DIAMETER

ขนาดบรรจุภัณฑ์: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 7/0.2 mm
- Probe Length: 1500 mm
- Maximum Temperature Sensed: 280 °C
- Termination Type: Miniature Plug
- Cable Length: 1.5 m



2048391 K

K FINE WIRE THERMOCOUPLE 3M -100TO250DEG

ขนาดบรรจุภัณฑ์: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1/0.3 mm
- Probe Length: 3 m
- Maximum Temperature Sensed: +250 °C
- Termination Type: Miniature Plug
- Cable Length: 3 m
- Standards Met: RoHS Compliant
- Response Time: 0.1 s



4791788 K

RS PRO IVT-20, LCD VOLTAGE TESTER, 750V AC/DC, CONTINUITY CHECK,

ขนาดบรรจุภัณฑ์: **1 x EA**

- Maximum Voltage: 750 V ac/dc
- Continuity Check: Yes
- Safety Category: CAT III 750 V, CAT IV 600 V
- Display Type: LCD
- RCD Trip Test: Yes
- IP Rating: IP65
- Battery Type: AAA, LR03
- Power Source: Battery



1241962 750 V ac/dc

RS PRO TEST PROBE

ขนาดบรรจุภัณฑ์: **1 x EA**

- Lead Type: Extension Lead Set
- Fused: No
- Safety Category Voltage: 1000 V
- Safety Category: CAT III 1000 V



1999854 Extension Lead

RS PRO TYPE K TEMPERATURE PROBE 800MM LENGTH, 0.2MM DIAMETER →

ขนาดบรรจุภัณฑ์: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 0.2 mm
- Probe Length: 800 mm
- Maximum Temperature Sensed: +450 °C
- Termination Type: Miniature Plug
- Cable Length: 800 mm



2048392 K

THERMOMETER, PROBE, FINE WIRE, K, FIBRE GLASS

ขนาดบรรจุภัณฑ์: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1.2 mm
- Probe Length: 1 m
- Maximum Temperature Sensed: +450 °C
- Probe Material: Nickel Aluminium, Nickel Chrome
- Termination Type: Miniature Plug
- Cable Length: 1 m
- Standards Met: IEC



4094920 K

RS PRO G09-NC1, LED VOLTAGE TESTER, 1000V AC, NO, BATTERY

ขนาดบรรจุภัณฑ์: **1 x EA**

- Maximum Voltage: 1000 V ac
- Continuity Check: No
- Safety Category: CAT II 1000 V
- Display Type: LED
- Battery Type: AAA
- Power Source: Battery
- Dimensions: 152 x 4.5 mm
- Weight: 58 g



1923685 1000 V ac

CONNECTOR, TEST, ACCESSORIES, FUSED, LEAD, SPIKE

ขนาดบรรจุภัณฑ์: **1 x PR**

- Lead Type: Thin Fine Insulated Prod Set
- Safety Category Voltage: 600 V



2627770 Thin Fine

RS PRO TYPE T THERMOCOUPLE 100MM LENGTH, 1.6MM DIAMETER →

ขนาดบรรจุภัณฑ์: **1 x EA**

- Thermocouple Type: T
- Probe Diameter: 1.6 mm
- Probe Length: 100 mm
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +250 °C
- Termination Type: Cable
- Cable Length: 1.5 m
- Standards Met: IEC



2194674 T

RS PRO THERMOMETER ACCESSORY FOR USE WITH IDM 50 SERIES

ขนาดบรรจุภัณฑ์: **1 x EA**

- Accessory Type: USB Cable, WinDMM 50 Software
- For Use With: IDM 50 Series



7048135 USB Cable,

CONNECTOR, TEST, ACCESSORIES, FUSED, LEAD, LANTERN, PROBE

ขนาดบรรจุภัณฑ์: **1 x PR**

- Lead Type: Probe Set
- Connector Type: Lantern



2627786 Probe Set

THERMOMETER, PROBE, FINE WIRE, K, PTFE

ขนาดบรรจุภัณฑ์: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 0.2 mm
- Probe Length: 1 m
- Maximum Temperature Sensed: +250 °C
- Probe Material: Nickel Aluminium, Nickel Chrome
- Termination Type: Miniature Plug
- Cable Length: 1 m
- Standards Met: RoHS Compliant



4094908 K

RS PRO IVT-10, LED VOLTAGE TESTER, 750V AC/DC, CONTINUITY CHECK,

ขนาดบรรจุภัณฑ์: **1 x EA**

- Maximum Voltage: 750 V ac/dc
- Continuity Check: Yes
- Safety Category: CAT III 750 V, CAT IV 600 V
- Display Type: LED
- RCD Trip Test: Yes
- IP Rating: IP65
- Battery Type: AAA, LR03
- Power Source: Battery



1241961 750 V ac/dc

RS PRO POLYESTER BACKPACK WITH SHOULDER STRAP 340MM X 220MM X

ขนาดบรรจุภัณฑ์: **1 x EA**

- Bag Type: Backpack
- Material: Polyester
- Length: 340 mm
- Width: 220 mm
- Height: 410 mm
- Shoulder Strap: Yes
- Lock Type: Zipper



7887211 Backpack

GROMMET, EDGING STRIP, PANELS 1.6 ØÄ 2MM, 5M

- ขนาดบรรจุภัณฑ์: **5 x MTR**
- Grommet Type: Grommet Strip
 - Minimum Panel Thickness: 1 mm
 - Minimum Cable Diameter: 1.1 mm
 - Maximum Cable Diameter: 2 mm
 - Material: PE
 - Colour: Natural
 - Grommet Strip Length: 5 m
 - Maximum Panel Thickness: 5.5 mm



406928 Grommet Strip

GROMMET, EDGING STRIP, PANELS 2.4 ØÄ 3.2MM, 5M

- ขนาดบรรจุภัณฑ์: **5 x MTR**
- Grommet Type: Grommet Strip
 - Minimum Panel Thickness: 4.5 mm
 - Minimum Cable Diameter: 1.5 mm
 - Maximum Cable Diameter: 3.2 mm
 - Material: PE
 - Colour: Natural
 - Grommet Strip Length: 5 m



406938 Grommet Strip

RS PRO BLACK NYLON

- ขนาดบรรจุภัณฑ์: **1 x KT**
- Minimum Cable Diameter: 4.8 mm
 - Maximum Cable Diameter: 45 mm
 - Material: Nylon
 - Colour: Black
 - Minimum Operating Temperature: -20 °C



2326875 4.8 mm

RS PRO METAL LOCKABLE HANDLE, KEY UNLOCK

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Unlock Method: Key
 - Material: Metal



222963 Key

RS PRO CABINET LOCK

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Type: Key Lock
 - For Use With: Enclosure
 - Material: Metal



8428478 Key Lock

RS PRO GREY ABS PUSH BUTTON ENCLOSURE - 22MM DIAMETER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Series: CCS
 - Cutout Diameter: 22 mm
 - Enclosure Colour: Grey
 - Enclosure Material: ABS
 - IP Rating: IP65
 - Length: 70 mm
 - Width: 70 mm
 - Depth: 51 mm



1947454 CCS

RS PRO GREY ABS PUSH BUTTON ENCLOSURE - 1 HOLE 22MM DIAMETER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Series: CCS
 - Cutout Diameter: 22 mm
 - Number of Cutouts: 1
 - Enclosure Colour: Grey
 - Enclosure Material: ABS
 - IP Rating: IP65
 - Length: 70 mm
 - Width: 70 mm



1947455 CCS

RS PRO GREY ABS PUSH BUTTON ENCLOSURE - 1 HOLE 22MM DIAMETER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Series: CCS
 - Cutout Diameter: 22 mm
 - Number of Cutouts: 1
 - Enclosure Colour: Grey
 - Enclosure Material: ABS
 - IP Rating: IP65
 - Length: 70 mm
 - Width: 70 mm



1947458 CCS

RS PRO GREY/YELLOW ABS PUSH BUTTON ENCLOSURE - 1 HOLE 22MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Series: CCS
 - Cutout Diameter: 22 mm
 - Number of Cutouts: 1
 - Enclosure Colour: Grey/Yellow
 - Enclosure Material: ABS
 - IP Rating: IP65
 - Length: 70 mm
 - Width: 70 mm



1947456 CCS

RS PRO GREY/YELLOW ABS PUSH BUTTON ENCLOSURE - 1 HOLE 22MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Series: CCS
 - Cutout Diameter: 22 mm
 - Number of Cutouts: 1
 - Enclosure Colour: Grey/Yellow
 - Enclosure Material: ABS
 - IP Rating: IP65
 - Length: 70 mm
 - Width: 70 mm



1947459 CCS

RS PRO GREY ABS PUSH BUTTON ENCLOSURE - 22MM DIAMETER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Series: CCS
 - Cutout Diameter: 22 mm
 - Enclosure Colour: Grey
 - Enclosure Material: ABS
 - IP Rating: IP65
 - Length: 70 mm
 - Width: 70 mm
 - Depth: 74 mm



1947457 CCS

RS PRO GREY ABS PUSH BUTTON ENCLOSURE - 2 HOLE 22MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Series: CCS
 - Cutout Diameter: 22 mm
 - Number of Cutouts: 2
 - Enclosure Colour: Grey
 - Enclosure Material: ABS
 - IP Rating: IP65
 - Length: 105 mm
 - Width: 70 mm



1947461 CCS

RS PRO GREY ABS PUSH BUTTON ENCLOSURE - 2 HOLE 22MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Series: CCS
 - Cutout Diameter: 22 mm
 - Number of Cutouts: 2
 - Enclosure Colour: Grey
 - Enclosure Material: ABS
 - IP Rating: IP65
 - Length: 105 mm
 - Width: 70 mm



1947463 CCS

RS PRO GREY ABS PUSH BUTTON ENCLOSURE - 22MM DIAMETER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Series: CCS
 - Cutout Diameter: 22 mm
 - Enclosure Colour: Grey
 - Enclosure Material: ABS
 - IP Rating: IP65
 - Length: 105 mm
 - Width: 70 mm
 - Depth: 74 mm



1947462 CCS

RS PRO GREY ABS PUSH BUTTON ENCLOSURE - 22MM DIAMETER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Series: CCS
 - Cutout Diameter: 22 mm
 - Enclosure Colour: Grey
 - Enclosure Material: ABS
 - IP Rating: IP65
 - Length: 140 mm
 - Width: 70 mm
 - Depth: 51 mm



1947464 CCS

RS PRO GREY ABS PUSH BUTTON ENCLOSURE - 22MM DIAMETER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Series: CCS
 - Cutout Diameter: 22 mm
 - Enclosure Colour: Grey
 - Enclosure Material: ABS
 - IP Rating: IP65
 - Length: 140 mm
 - Width: 70 mm
 - Depth: 74 mm



1947465 CCS

RS PRO GREY ABS PUSH BUTTON ENCLOSURE - 22MM DIAMETER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Series: CCS
 - Cutout Diameter: 22 mm
 - Enclosure Colour: Grey
 - Enclosure Material: ABS
 - IP Rating: IP65
 - Length: 185 mm
 - Width: 70 mm
 - Depth: 74 mm



1947467 CCS

RS PRO WHITE ABS DESKTOP ENCLOSURE, SLOPED FRONT, 127.37 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 127.4 mm
 - External Width: 178.1 mm
 - External Height: 73.6 mm
 - External Dimensions: 127.37 x 178.14 x 73.56 mm
 - Sloped Front: Yes
 - Colour: White
 - Standards Met: UL 94 HB, ULE56070



221011 ABS

RS PRO WHITE ABS DESKTOP ENCLOSURE, SLOPED FRONT, 203.2 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 203.2 mm
 - External Width: 254 mm
 - External Height: 101.6 mm
 - External Dimensions: 203.2 x 254.01 x 101.6 mm
 - Sloped Front: Yes
 - Colour: White
 - Standards Met: UL 94 HB, ULE56070



221027 ABS

RS PRO GREY ABS DESKTOP ENCLOSURE, 250 X 275 X 75MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 250 mm
 - External Width: 275 mm
 - External Height: 75 mm
 - External Dimensions: 250 x 275 x 75 mm
 - Sloped Front: No
 - Colour: Grey
 - Standards Met: UL 94 HB



504748 ABS

RS PRO GREY ABS DESKTOP ENCLOSURE, 250 X 275 X 100MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 250 mm
 - External Width: 275 mm
 - External Height: 100 mm
 - External Dimensions: 250 x 275 x 100 mm
 - Sloped Front: No
 - Colour: Grey
 - Standards Met: UL 94 HB



504754 ABS

ENCLOSURE,CASE,DIN RAIL MOUNT,EN50/022

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Enclosure Type: DIN Rail
 - Body Material: Polycarbonate, Polystyrene
 - Length: 110 mm
 - Dimensions: 110 x 75 x 50 mm
 - Width: 75 mm
 - Height: 50 mm
 - Maximum Terminals: 12
 - Minimum Operating Temperature: -10 °C



507680 DIN Rail

RS PRO MODULAR ENCLOSURE ENCLOSURE TYPE, 53.4 X 89.4 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Enclosure Type: Modular Enclosure
 - Body Material: ABS
 - Length: 53.4 mm
 - Dimensions: 53.4 x 89.4 x 65.2 mm
 - Width: 89.4 mm
 - Height: 65 mm
 - Colour: Light Grey



1862289 Modular

LIGHTGRAY, DIN RAIL, NUMBER OF MODULES:

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Enclosure Type: Modular Enclosure
 - Body Material: ABS
 - Length: 34.4 mm
 - Dimensions: 34.4 x 88.8 x 62.8 mm
 - Width: 88.8 mm
 - Height: 63 mm
 - Colour: Light Grey



1862290 Modular

LIGHTGRAY, DIN RAIL, NUMBER OF MODULES:

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Enclosure Type: Modular Enclosure
 - Body Material: ABS
 - Length: 17.5 mm
 - Dimensions: 17.5 x 90.0 x 64.9 mm
 - Width: 90 mm
 - Height: 65 mm
 - Colour: Light Grey



1862292 Modular

RS PRO MODULAR ENCLOSURE ENCLOSURE TYPE, 35.2 X 90.1 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Enclosure Type: Modular Enclosure
 - Body Material: ABS
 - Length: 35.2 mm
 - Dimensions: 35.2 x 90.1 x 65.0 mm
 - Width: 90.1 mm
 - Height: 65 mm
 - Colour: Light Grey



1862293 Modular

RS PRO MODULAR ENCLOSURE ENCLOSURE TYPE, 52.5 X 90.0 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Enclosure Type: Modular Enclosure
 - Body Material: ABS
 - Length: 52.5 mm
 - Dimensions: 52.5 x 90.0 x 65.0 mm
 - Width: 90 mm
 - Height: 65 mm
 - Colour: Light Grey



1862294 Modular

RS PRO DIN RAIL ENCLOSURE ENCLOSURE TYPE, 105.0 X 90.0 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Enclosure Type: DIN Rail Enclosure
 - Body Material: ABS
 - Length: 105 mm
 - Dimensions: 105.0 x 90.0 x 65.3 mm
 - Width: 90 mm
 - Height: 65 mm
 - Colour: Light Grey



1862297 DIN Rail

RS PRO OPEN TOP ENCLOSURE TYPE, 90 X 53 X 114MM, POLYCARBONATE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Enclosure Type: Open Top
 - Body Material: Polycarbonate
 - DIN Rail Type: Enclosure
 - Length: 90 mm
 - Dimensions: 90 x 53 x 114 mm
 - Width: 53 mm
 - Height: 114 mm
 - Colour: Light Grey



1947471 Open Top

RS PRO OPEN TOP ENCLOSURE TYPE, 90 X 53 X 31.9MM, POLYCARBONATE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Enclosure Type: Open Top
 - Body Material: Polycarbonate
 - DIN Rail Type: Enclosure
 - Length: 90 mm
 - Dimensions: 90 x 53 x 31.9 mm
 - Width: 53 mm
 - Height: 32 mm
 - Maximum Terminals: 2



1947472 Open Top

RS PRO OPEN TOP ENCLOSURE TYPE, 90 X 53 X 31.9MM, POLYCARBONATE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Enclosure Type: Open Top
 - Body Material: Polycarbonate
 - DIN Rail Type: Enclosure
 - Length: 90 mm
 - Dimensions: 90 x 53 x 31.9 mm
 - Width: 53 mm
 - Height: 32 mm
 - Colour: Light Grey



1947473 Open Top

RS PRO SOLID TOP ENCLOSURE TYPE, 90 X 53 X 114MM, POLYCARBONATE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Enclosure Type: Solid Top
 - Body Material: Polycarbonate
 - DIN Rail Type: Enclosure
 - Length: 90 mm
 - Dimensions: 90 x 53 x 114 mm
 - Width: 53 mm
 - Height: 114 mm
 - Maximum Terminals: 2



1947474 Solid Top

RS PRO SOLID TOP ENCLOSURE TYPE, 90 X 53 X 31.9MM, POLYCARBONATE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Enclosure Type: Solid Top
 - Body Material: Polycarbonate
 - DIN Rail Type: Enclosure
 - Length: 90 mm
 - Dimensions: 90 x 53 x 31.9 mm
 - Width: 53 mm
 - Height: 32 mm
 - Maximum Terminals: 2



1947476 Solid Top

RS PRO OPEN TOP ENCLOSURE TYPE, 90 X 106.2 X 31.9MM,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Enclosure Type: Open Top
 - Body Material: Polycarbonate
 - DIN Rail Type: Enclosure
 - Length: 90 mm
 - Dimensions: 90 x 106.2 x 31.9 mm
 - Width: 106.2 mm
 - Height: 32 mm
 - Maximum Terminals: 4



1947480 Open Top

RS PRO SOLID TOP ENCLOSURE TYPE, 90 X 106.2 X 114MM,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Enclosure Type: Solid Top
 - Body Material: Polycarbonate
 - DIN Rail Type: Enclosure
 - Length: 90 mm
 - Dimensions: 90 x 106.2 x 114 mm
 - Width: 106.2 mm
 - Height: 114 mm
 - Colour: Light Grey



1947483 Solid Top

RS PRO SOLID TOP ENCLOSURE TYPE, 90 X 106.2 X 31.9MM,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Enclosure Type: Solid Top
 - Body Material: Polycarbonate
 - DIN Rail Type: Enclosure
 - Length: 90 mm
 - Dimensions: 90 x 106.2 x 31.9 mm
 - Width: 106.2 mm
 - Height: 32 mm
 - Colour: Light Grey



1947485 Solid Top

RS PRO SOLID TOP ENCLOSURE TYPE, 17.5 X 90 X 58MM, POLYCARBONATE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Enclosure Type: Solid Top
 - Body Material: Polycarbonate
 - DIN Rail Type: Enclosure Base
 - Length: 17.5 mm
 - Dimensions: 17.5 x 90 x 58 mm
 - Width: 90 mm
 - Height: 58 mm
 - Maximum Terminals: 2



1947575 Solid Top

RS PRO OPEN TOP ENCLOSURE TYPE, 17.5 X 90 X 58MM, POLYCARBONATE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Enclosure Type: Open Top
 - Body Material: Polycarbonate
 - DIN Rail Type: Enclosure Base
 - Length: 17.5 mm
 - Dimensions: 17.5 x 90 x 58 mm
 - Width: 90 mm
 - Height: 58 mm
 - Maximum Terminals: 2



1947577 Open Top

RS PRO OPEN TOP ENCLOSURE TYPE, 36 X 90 X 58MM, POLYCARBONATE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Enclosure Type: Open Top
 - Body Material: Polycarbonate
 - DIN Rail Type: Enclosure Base
 - Length: 36 mm
 - Dimensions: 36 x 90 x 58 mm
 - Width: 90 mm
 - Height: 58 mm
 - Maximum Terminals: 2



1947578 Open Top

RS PRO SOLID TOP ENCLOSURE TYPE, 36 X 90 X 58MM, POLYCARBONATE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Enclosure Type: Solid Top
 - Body Material: Polycarbonate
 - DIN Rail Type: Enclosure Base
 - Length: 36 mm
 - Dimensions: 36 x 90 x 58 mm
 - Width: 90 mm
 - Height: 58 mm
 - Maximum Terminals: 2



1947579 Solid Top

RS PRO OPEN TOP, VENTED SIDES ENCLOSURE TYPE, 36 X 90 X 58MM,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Enclosure Type: Open Top, Vented Sides
 - Body Material: Polycarbonate
 - DIN Rail Type: Enclosure Base
 - Length: 36 mm
 - Dimensions: 36 x 90 x 58 mm
 - Width: 90 mm
 - Height: 58 mm
 - Maximum Terminals: 2



1947580 Open Top,

RS PRO EXTENDED WALLS/SIDES ENCLOSURE TYPE, 36 X 90 X 58MM,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Enclosure Type: Extended Walls/Sides
 - Body Material: Polycarbonate
 - DIN Rail Type: Enclosure Base
 - Length: 36 mm
 - Dimensions: 36 x 90 x 58 mm
 - Width: 90 mm
 - Height: 58 mm
 - Maximum Terminals: 2



1947581 Extended

RS PRO SOLID TOP ENCLOSURE TYPE, 53.4 X 90 X 58MM, POLYCARBONATE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Enclosure Type: Solid Top
 - Body Material: Polycarbonate
 - DIN Rail Type: Enclosure Base
 - Length: 53.4 mm
 - Dimensions: 53.4 x 90 x 58 mm
 - Width: 90 mm
 - Height: 58 mm
 - Maximum Terminals: 2



1947584 Solid Top

RS PRO OPEN TOP, VENTED SIDES ENCLOSURE TYPE, 53.4 X 90 X 58MM,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Enclosure Type: Open Top, Vented Sides
 - Body Material: Polycarbonate
 - DIN Rail Type: Enclosure Base
 - Length: 53.4 mm
 - Dimensions: 53.4 x 90 x 58 mm
 - Width: 90 mm
 - Height: 58 mm
 - Maximum Terminals: 2



1947585 Open Top,

RS PRO OPEN TOP ENCLOSURE TYPE, 106.2 X 90 X 58MM, POLYCARBONATE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Enclosure Type: Open Top
 - Body Material: Polycarbonate
 - DIN Rail Type: Enclosure Base
 - Length: 106.2 mm
 - Width: 90 mm
 - Dimensions: 106.2 x 90 x 58 mm
 - Height: 58 mm
 - Maximum Terminals: 4



1947592 Open Top

RS PRO SOLID TOP ENCLOSURE TYPE, 106.2 X 90 X 58MM, POLYCARBONATE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Enclosure Type: Solid Top
 - Body Material: Polycarbonate
 - DIN Rail Type: Enclosure Base
 - Length: 106.2 mm
 - Dimensions: 106.2 x 90 x 58 mm
 - Width: 90 mm
 - Height: 58 mm
 - Maximum Terminals: 4



1947594 Solid Top

RS PRO EXTENDED WALLS SIDES, OPEN TOP ENCLOSURE TYPE, 106.2 X

- ขนาดบรรจุภัณฑ์: 1 x EA
- Enclosure Type: Extended Walls Sides, Open Top
 - Body Material: Polycarbonate
 - DIN Rail Type: Enclosure Base
 - Length: 106.2 mm
 - Dimensions: 106.2 x 90 x 58 mm
 - Width: 90 mm
 - Height: 58 mm
 - Maximum Terminals: 4



1947595 Extended Walls

RS PRO SOLID TOP ENCLOSURE TYPE, 159.2 X 90 X 58MM, POLYCARBONATE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Enclosure Type: Solid Top
 - Body Material: Polycarbonate
 - DIN Rail Type: Enclosure Base
 - Length: 159.2 mm
 - Dimensions: 159.2 x 90 x 58 mm
 - Width: 90 mm
 - Height: 58 mm
 - Maximum Terminals: 6



1947596 Solid Top

RS PRO OPEN TOP, VENTED SIDES ENCLOSURE TYPE, 159.2 X 90 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Enclosure Type: Open Top, Vented Sides
 - Body Material: Polycarbonate
 - DIN Rail Type: Enclosure Base
 - Length: 159.2 mm
 - Dimensions: 159.2 x 90 x 58 mm
 - Width: 90 mm
 - Height: 58 mm
 - Maximum Terminals: 6



1947597 Open Top,

RS PRO EXTENDED WALLS SIDES, OPEN TOP ENCLOSURE TYPE, 159.2 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Enclosure Type: Extended Walls Sides, Open Top
 - Body Material: Polycarbonate
 - DIN Rail Type: Enclosure Base
 - Length: 159.2 mm
 - Dimensions: 159.2 x 90 x 58 mm
 - Width: 90 mm
 - Height: 58 mm
 - Maximum Terminals: 6



1947598 Extended Walls

RS PRO OPEN TOP, VENTED SIDES ENCLOSURE TYPE, 212.1 X 90 X 58MM,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Enclosure Type: Open Top, Vented Sides
 - Body Material: Polycarbonate
 - DIN Rail Type: Enclosure Base
 - Length: 212.1 mm
 - Dimensions: 212.1 x 90 x 58 mm
 - Width: 90 mm
 - Height: 58 mm
 - Maximum Terminals: 8



1947599 Open Top,

RS PRO DIN RAIL ENCLOSURE ENCLOSURE TYPE, 22.5 X 82 X 90MM,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Enclosure Type: DIN Rail Enclosure
 - Body Material: Polyamide
 - DIN Rail Type: Enclosure
 - Length: 22.5 mm
 - Dimensions: 22.5 x 82 x 90 mm
 - Width: 82 mm
 - Height: 90 mm
 - Maximum Terminals: 12



1959128 DIN Rail

RS PRO DIN RAIL ENCLOSURE ENCLOSURE TYPE, 75 X 22.5 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Enclosure Type: DIN Rail
 - Body Material: Polycarbonate
 - DIN Rail Type: Top Hat
 - Length: 75 mm
 - Dimensions: 75 x 22.5 x 98.5 mm
 - Width: 22.5 mm
 - Height: 98.5 mm
 - Maximum Terminals: 12



2433632 DIN Rail

RS PRO DIN RAIL ENCLOSURE ENCLOSURE TYPE, 75 X 55 X 110MM,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Enclosure Type: DIN Rail
 - Body Material: Polycarbonate
 - DIN Rail Type: Top Hat
 - Length: 75 mm
 - Dimensions: 75 x 55 x 110 mm
 - Width: 55 mm
 - Height: 110 mm
 - Maximum Terminals: 16



2433654 DIN Rail

RS PRO MODULAR ENCLOSURE ENCLOSURE TYPE, 75 X 99.7 X 110MM,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Enclosure Type: DIN Rail
 - Body Material: Polycarbonate
 - DIN Rail Type: Top Hat
 - Length: 75 mm
 - Dimensions: 75 x 99.7 x 110 mm
 - Width: 99.7 mm
 - Height: 110 mm
 - Maximum Terminals: 30



2433660 DIN Rail

ENCLOSURE, IP55

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 95.5 mm
 - Dimensions: 95.5 x 80 x 135 mm
 - Width: 80 mm
 - Height: 135 mm
 - Maximum Terminals: 1
 - Colour: White
 - Series: XL-2000-01
 - Enclosure Rating: IP41, IP55



331731 95.5 mm

RS PRO STEEL SLOTTED DIN RAIL, MINI TOP HAT COMPATIBLE, 1M X 15MM X

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Compatibility: Mini Top Hat
 - Length: 1 m
 - Width: 15 mm
 - Height: 5.5 mm
 - DIN Rail Type: Slotted
 - Material: Steel



467349 Mini Top Hat

RS PRO STEEL SLOTTED DIN RAIL, G COMPATIBLE, 500MM X 32MM X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Compatibility: G
 - Length: 500 mm
 - Width: 32 mm
 - Height: 15 mm
 - DIN Rail Type: Slotted
 - Material: Steel



467355 G

RS PRO STEEL UNSLOTTED DIN RAIL, G COMPATIBLE, 500MM X 32MM X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Compatibility: G
 - Length: 500 mm
 - Width: 32 mm
 - Height: 15 mm
 - DIN Rail Type: Unslotted
 - Material: Steel



467359 G

RS PRO, UNSLOTTED DIN RAIL, 1M X 32MM X 15MM

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Compatibility: G
 - Length: 1 m
 - Width: 32 mm
 - Height: 15 mm
 - DIN Rail Type: Unslotted
 - Material: Steel

SORRY IMAGE NOT AVAILABLE.

467365 G

RS PRO STEEL SLOTTED DIN RAIL, G COMPATIBLE, 1M X 32MM X 15MM

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Compatibility: G
 - Length: 1 m
 - Width: 32 mm
 - Height: 15 mm
 - DIN Rail Type: Slotted
 - Material: Steel



467393 G

RS PRO STEEL UNSLOTTED DIN RAIL, TOP HAT COMPATIBLE, 1M X 35MM X

- ขนาดบรรจุภัณฑ์: **4 x EA**
- Compatibility: Top Hat
 - Length: 1 m
 - Width: 35 mm
 - Height: 7.5 mm
 - DIN Rail Type: Unslotted
 - Material: Steel



467399 Top Hat

RS PRO STEEL SLOTTED DIN RAIL, TOP HAT COMPATIBLE, 500MM X 35MM X


- ขนาดบรรจุภัณฑ์: **1 x EA**
- Compatibility: Top Hat
 - Length: 500 mm
 - Width: 35 mm
 - Height: 7.5 mm
 - DIN Rail Type: Slotted
 - Material: Steel



467406 Top Hat

RS PRO STEEL UNSLOTTED DIN RAIL, DEEP TOP HAT COMPATIBLE, 1M X

- ขนาดบรรจุภัณฑ์: **4 x EA**
- Compatibility: Deep Top Hat
 - Length: 1 m
 - Width: 35 mm
 - Height: 15 mm
 - DIN Rail Type: Unslotted
 - Material: Steel



467412 Deep Top Hat

RS PRO STEEL SLOTTED DIN RAIL, TOP HAT COMPATIBLE, 1M X 35MM X

- ขนาดบรรจุภัณฑ์: 4 x EA
- Compatibility: Top Hat
 - Length: 1 m
 - Width: 35 mm
 - Height: 7.5 mm
 - DIN Rail Type: Slotted
 - Material: Steel



467416 Top Hat

RS PRO STEEL SLOTTED DIN RAIL, DEEP TOP HAT COMPATIBLE, 1M X

- ขนาดบรรจุภัณฑ์: 4 x EA
- Compatibility: Deep Top Hat
 - Length: 1 m
 - Width: 35 mm
 - Height: 15 mm
 - DIN Rail Type: Slotted
 - Material: Steel



467428 Deep Top Hat

RS PRO STEEL SLOTTED DIN RAIL, DEEP TOP HAT COMPATIBLE, 500MM

- ขนาดบรรจุภัณฑ์: 4 x EA
- Compatibility: Deep Top Hat
 - Length: 500 mm
 - Width: 35 mm
 - Height: 15 mm
 - DIN Rail Type: Slotted
 - Material: Steel



467438 Deep Top Hat

RS PRO DIN RAIL ENCLOSURE KIT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Panel Screw Kit
 - For Use With: DIN Rail



606844 Panel Screw Kit

RS PRO STEEL UNSLOTTED DIN RAIL, TOP HAT COMPATIBLE, 225MM X

- ขนาดบรรจุภัณฑ์: 1 x EA
- Compatibility: Top Hat
 - Length: 225 mm
 - Width: 35 mm
 - Height: 7.5 mm
 - DIN Rail Type: Unslotted
 - Material: Steel



1882207 Top Hat

RS PRO DIN RAIL, 90MM X 35MM X 7.5MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 90 mm
 - Width: 35 mm
 - Height: 7.5 mm



2006726 90 mm

RS PRO DIN RAIL, 122MM X 35MM X 7.5MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 122 mm
 - Width: 35 mm
 - Height: 7.5 mm



2006728 122 mm

RS PRO DIN RAIL, 135MM X 35MM X 7.5MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 135 mm
 - Width: 35 mm
 - Height: 7.5 mm



2006730 135 mm

RS PRO DIN RAIL, 163MM X 35MM X 7.5MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 163 mm
 - Width: 35 mm
 - Height: 7.5 mm



2006731 163 mm

RS PRO DIN RAIL, 196MM X 35MM X 7.5MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 196 mm
 - Width: 35 mm
 - Height: 7.5 mm



2006732 196 mm

RS PRO DIN RAIL, 218MM X 35MM X 7.5MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 218 mm
 - Width: 35 mm
 - Height: 7.5 mm



2006733 218 mm

RS PRO DIN RAIL, TOP HAT COMPATIBLE, 100MM X 35MM X

- ขนาดบรรจุภัณฑ์: 1 x EA
- Compatibility: Top Hat
 - Length: 100 mm
 - Width: 35 mm
 - Height: 7.5 mm



2258317 Top Hat

RS PRO DIN RAIL, TOP HAT COMPATIBLE, 227MM X 35MM X

- ขนาดบรรจุภัณฑ์: 1 x EA
- Compatibility: Top Hat
 - Length: 227 mm
 - Width: 35 mm
 - Height: 7.5 mm



2258320 Top Hat

RS PRO DIN RAIL, TOP HAT COMPATIBLE, 53MM X 35MM X

- ขนาดบรรจุภัณฑ์: 1 x EA
- Compatibility: Top Hat
 - Length: 53 mm
 - Width: 35 mm
 - Height: 7.5 mm



2258321 Top Hat

RS PRO DIN RAIL, TOP HAT COMPATIBLE, 80MM X 35MM X

- ขนาดบรรจุภัณฑ์: 1 x EA
- Compatibility: Top Hat
 - Length: 80 mm
 - Width: 35 mm
 - Height: 7.5 mm



2258322 Top Hat

RS PRO STEEL SLOTTED DIN RAIL, TOP HAT COMPATIBLE, 134MM X 35MM X

- ขนาดบรรจุภัณฑ์: 1 x EA
- Compatibility: Top Hat
 - Length: 134 mm
 - Width: 35 mm
 - Height: 8 mm
 - DIN Rail Type: Slotted
 - Material: Steel



2382635 Top Hat

RS PRO STEEL UNSLOTTED DIN RAIL, TOP HAT COMPATIBLE, 156MM X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Compatibility: Top Hat
 - Length: 156 mm
 - Width: 35 mm
 - Height: 8 mm
 - DIN Rail Type: Unslotted
 - Material: Steel



2382641 Top Hat

RS PRO UNPERFORATED DIN RAIL, 60MM X 35MM X 8MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 60 mm
 - Width: 35 mm
 - Height: 8 mm
 - DIN Rail Type: Unperforated



2383966 60 mm

RS PRO STEEL UNSLOTTED DIN RAIL, TOP HAT COMPATIBLE, 500MM X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Compatibility: Top Hat
 - Length: 500 mm
 - Width: 35 mm
 - Height: 7.5 mm
 - DIN Rail Type: Unslotted
 - Material: Steel



7424129 Top Hat

RS PRO SQUARE BRACKET FOR USE WITH TOP HAT DIN RAIL

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Accessory Type: Square Bracket
 - Series: TS
 - For Use With: DIN Rail



467343 Square Bracket

RS PRO SQUARE BRACKET FOR USE WITH TOP HAT DIN RAIL

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Accessory Type: Square Bracket
 - Series: TS
 - For Use With: DIN Rail



467361 Square Bracket

RS PRO SQUARE BRACKET FOR USE WITH TOP HAT DIN RAIL

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Accessory Type: Square Bracket
 - Series: TS
 - For Use With: DIN Rail



467371 Square Bracket

RS PRO ANGLED BRACKET FOR USE WITH TOP HAT DIN RAIL

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Accessory Type: Angled Bracket
 - Series: TS
 - For Use With: DIN Rail



467377 Angled Bracket

RS PRO SQUARE BRACKET FOR USE WITH TOP HAT DIN RAIL

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Accessory Type: Square Bracket
 - Series: TS
 - For Use With: DIN Rail



467383 Square Bracket

RS PRO ANGLED BRACKET FOR USE WITH TOP HAT DIN RAIL

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Accessory Type: Angled Bracket
 - Series: TS
 - For Use With: DIN Rail



467387 Angled Bracket

RS PRO ANGLED BRACKET FOR USE WITH DIN RAIL

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Accessory Type: Angled Bracket
 - For Use With: DIN Rail



606850 Angled Bracket

RS PRO ANGLED BRACKET FOR USE WITH DIN RAIL

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Accessory Type: Angled Bracket
 - For Use With: DIN Rail



606866 Angled Bracket

RS PRO MOUNTING KIT FOR USE WITH 72 MM WIDTH PCB#146;S

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Mounting Kit
 - For Use With: 72 mm width PCB#146;s



1947609 Mounting Kit

DOCUMENT,POCKETS,SELF ADHESIVE,CLEAR PLASTIC,A4

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Type: Document Pocket
 - For Use With: A4 Portrait Paper
 - Material: Acrylic
 - Dimensions: 303 x 217 mm
 - Colour: Transparent
 - Quantity: 5



1966018 Document Pocket

RS PRO DOCUMENT WALLET

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Type: Document Pocket
 - For Use With: A5 Landscape Paper
 - Material: Acrylic
 - Dimensions: 216 x 155 mm
 - Colour: Transparent
 - Quantity: 5



1966024 Document Pocket

GROMMET,EDGING STRIP,PANELS 1.2 00A0E 16MM,5M

- ขนาดบรรจุภัณฑ์: **5 x MTR**
- Product Type: Edge Protection
 - Material: Polyethylene



406922 Edge Protection

GROMMET,STRIP,PANELS 2.5-3.2MM,25M

- ขนาดบรรจุภัณฑ์: **25 x MTR**
- Product Type: Edge Protection
 - Material: Polyethylene



429690 Edge Protection

RS PRO EARTHING STRAP

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Type: Earthing Strap
 - Length: 220 mm
 - For Use With: Steel Enclosure



7467384 Earthing Strap

ENCLOSURE, 19IN, RACK, LABORATORY ,KIT, EARTHING

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Type: Earthing Kit
 - For Use With: Frame



528983 Earthing Kit

RS PRO WALL MOUNT FOR USE WITH INLINE TERMINAL ENCLOSURE

- ขนาดบรรจุภัณฑ์: **1 x PR**
- Enclosure Mounting Type: Mounting Bracket
 - Material: Steel
 - For Use With: Inline Terminal Enclosure



122074 Mounting Bracket

RS PRO GALVANISED STEEL MOUNTING PLATE FOR USE WITH RS

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 126 mm
 - Enclosure Mounting Type: Mounting Plate
 - Width: 196 mm
 - Dimensions: 126 x 196 x 1.5 mm
 - Height: 2 mm
 - Material: Galvanised Steel
 - For Use With: RS PRO 1920695 Hermetic Enclosure



1920707 126 mm

RS PRO GALVANISED STEEL MOUNTING PLATE FOR USE WITH RS

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 176 mm
 - Enclosure Mounting Type: Mounting Plate
 - Width: 266.4 mm
 - Dimensions: 176 x 266.4 x 1.5 mm
 - Height: 2 mm
 - Material: Galvanised Steel
 - For Use With: RS PRO 1862265 and RS PRO 1862266 Hermetic Enclosures



1920738 176 mm

RS PRO ABS MOUNTING KIT FOR USE WITH RS PRO 7710 SERIES

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Enclosure Mounting Type: Mounting Kit
 - Colour: Grey
 - Material: ABS
 - Series: 7700
 - For Use With: RS PRO 7710 Series



1947496 Mounting Kit

RS PRO MOUNTING KIT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Enclosure Mounting Type: Mounting Bracket
 - Material: Steel



7467387 Mounting Bracket

RS PRO STAINLESS STEEL MOUNTING PLATE FOR USE WITH SBOX 3.4-200

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 198 mm
 - Enclosure Mounting Type: Mounting Plate
 - Width: 250 mm
 - Dimensions: 248 x 198 mm
 - Height: 248 mm
 - Material: Stainless Steel
 - For Use With: SBOX 3.4-200 V2, SBOX 5.5-200 V2, SBOX 6.6-200 V2



7587163 198 mm

RS PRO STEEL MOUNTING PLATE FOR USE WITH 200 X 300 ENCLOSURE, 248

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 148 mm
 - Enclosure Mounting Type: Mounting Plate
 - Dimensions: 248 x 148 mm
 - Height: 248 mm
 - Material: Steel
 - For Use With: 200 x 300 Enclosure



7587166 148 mm

RS PRO STEEL MOUNTING PLATE FOR USE WITH 400 X 300 ENCLOSURE, 248

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 348 mm
 - Enclosure Mounting Type: Mounting Plate
 - Dimensions: 248 x 348 mm
 - Height: 248 mm
 - Material: Steel
 - For Use With: 400 x 300 Enclosure



7587175 348 mm

RS PRO STEEL MOUNTING PLATE FOR USE WITH 500 X 600 ENCLOSURE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 448 mm
 - Enclosure Mounting Type: Mounting Plate
 - Dimensions: 548 x 448 mm
 - Height: 548 mm
 - Material: Steel
 - For Use With: 500 x 600 Enclosure



7587179 448 mm

RS PRO STEEL MOUNTING PLATE FOR USE WITH 300 X 400 ENCLOSURE, 348

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 248 mm
 - Enclosure Mounting Type: Mounting Plate
 - Dimensions: 348 x 248 mm
 - Height: 348 mm
 - Material: Steel
 - For Use With: 300 x 400 Enclosure



7587181 248 mm

RS PRO STEEL MOUNTING PLATE FOR USE WITH 400 X 400 ENCLOSURE, 348

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 348 mm
 - Enclosure Mounting Type: Mounting Plate
 - Dimensions: 348 x 348 mm
 - Height: 348 mm
 - Material: Steel
 - For Use With: 400 x 400 Enclosure



7587185 348 mm

RS PRO STEEL MOUNTING BRACKET FOR USE WITH WALL BOX

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Enclosure Mounting Type: Mounting Bracket
 - Height: 4 mm
 - Material: Steel
 - For Use With: Wall Box



8428471 Mounting Bracket

RS PRO STEEL MOUNTING BRACKET FOR USE WITH WALL BOX

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Enclosure Mounting Type: Mounting Bracket
 - Height: 4 mm
 - Material: Steel
 - For Use With: Wall Box



8428475 Mounting Bracket

RS PRO ABS HANDLE FOR USE WITH ABS DESK CASE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Type: Handle
 - For Use With: ABS Desk Case
 - Material: ABS



504798 Handle

RS PRO SLOTTED SCREW FOR USE WITH KM6 PANEL M2.5 X , 100 PACK

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Type: Slotted Screw
 - For Use With: KM6 Panel
 - Thread Size: M2.5
 - Quantity: 100



543116 Slotted Screw

RS PRO METAL METAL BUSH FOR USE WITH EURO-CARDS FITTED WITH 2-

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Type: Metal Bush
 - For Use With: Euro-cards fitted with 2-part indirect edge connectors to DIN41612
 - Material: Metal
 - Colour: Grey



543190 Metal Bush

SPACER,HEXAGONAL,ZINC PLATED STEEL,M6X10MM

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Type: Spacer
 - Length: 10 mm
 - For Use With: Any Enclosure
 - Material: Steel
 - Thread Size: M6



603485 Spacer

SPACER,HEXAGONAL,ZINC PLATED STEEL,M6X12MM

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Type: Spacer
 - Length: 12 mm
 - For Use With: Any Enclosure
 - Material: Steel
 - Thread Size: M6



603491 Spacer

SPACER,HEXAGONAL,ZINC PLATED STEEL,M6X14MM

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Type: Spacer
 - Length: 14 mm
 - For Use With: Any Enclosure
 - Material: Steel
 - Thread Size: M6



603508 Spacer

RS PRO STEEL SPACER FOR USE WITH ANY ENCLOSURE

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Type: Spacer
 - Length: 16 mm
 - For Use With: Any Enclosure
 - Material: Steel
 - Thread Size: M6



603514 Spacer

SPACER,HEXAGONAL,ZINC PLATED STEEL,M6X18MM

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Type: Spacer
 - Length: 18 mm
 - For Use With: Any Enclosure
 - Material: Steel
 - Thread Size: M6



603520 Spacer

SPACER,HEXAGONAL,ZINC PLATED STEEL,M6X20MM

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Type: Spacer
 - Length: 20 mm
 - For Use With: Any Enclosure
 - Material: Steel
 - Thread Size: M6



603536 Spacer

SPACER,HEXAGONAL,ZINC PLATED STEEL,FEMALE,M6X20MM

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Type: Spacer
 - Length: 20 mm
 - For Use With: Any Enclosure
 - Material: Steel
 - Thread Size: M6



603542 Spacer

RS PRO POLYCARBONATE DRAINING PLUG FOR USE WITH PANEL

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Type: Draining Plug
 - For Use With: Panel
 - Material: Polycarbonate
 - Colour: Black



838827 Draining Plug

RS PRO RUBBER FEET FOR USE WITH EXTRUDED ALUMINIUM ENCLOSURES,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Type: Feet
 - For Use With: Extruded Aluminium Enclosures
 - Width: 16 mm
 - Material: Rubber
 - Dimensions: 16 x 10 mm
 - Height: 10 mm
 - Colour: Black



1368970 Feet

RS PRO LOCK FOR USE WITH RS PRO GRP WALL BOXES, 17 X 39.6 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Type: Lock
 - Length: 17 mm
 - For Use With: RS PRO GRP Wall Boxes
 - Width: 39.6 mm
 - Dimensions: 17 x 39.6 x 40.2 mm
 - Height: 40 mm
 - Colour: Black



1927131 Lock

KEY ONLY FOR STANDARD ATLAS-CDB-10 LOCK

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Type: Key
 - For Use With: RS PRO Quarter Turn Lock
 - Colour: Black



1927135 Key

RS PRO AIR VENT FOR USE WITH RS PRO GRP WALL BOXES, 68 X 50 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Type: Air Vent
 - Length: 68 mm
 - For Use With: RS PRO GRP Wall Boxes
 - Width: 50 mm
 - Dimensions: 68 x 50 x 15.8 mm
 - Height: 16 mm
 - Colour: White
 - IP Rating: IP54



1927136 Air Vent

RS PRO AIR VENT FOR USE WITH RS PRO GRP WALL BOXES, 25.75 X 28.45 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Type: Air Vent
 - Length: 26 mm
 - For Use With: RS PRO GRP Wall Boxes
 - Width: 28.45 mm
 - Dimensions: 25.75 x 28.45 x 21.88 mm
 - Height: 22 mm
 - Colour: White
 - IP Rating: IP54



1927137 Air Vent

RS PRO ABS HINGE FOR USE WITH HERMETIC ENCLOSURE, 29 X 20 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Type: Hinge
 - Length: 29 mm
 - For Use With: Hermetic Enclosure
 - Width: 20 mm
 - Material: ABS
 - Dimensions: 29 x 20 x 19.2 mm
 - Height: 19 mm
 - Colour: Grey



2006744 Hinge

RS PRO STEEL TAMPERPROOF SCREW FOR USE WITH SEALED DIN TYPE

- ขนาดบรรจุภัณฑ์: **12 x EA**
- Type: Tamperproof Screw
 - Length: 15 mm
 - For Use With: Sealed DIN Type Enclosure
 - Material: Steel
 - Dimensions: M5 x 15 mm, M5 x 15 mm



2826589 Tamperproof

KEY LOCK KIT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Type: Compression Latch
 - Length: 50 mm
 - For Use With: Steel Enclosure
 - Width: 49 mm
 - Material: Metal, Plastic
 - Dimensions: 50 x 49 x 51 mm
 - Height: 51 mm
 - Colour: Black



7467380 Compression

RS PRO STEEL POLE MOUNTING KIT FOR USE WITH WALL BOX, 140 →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Type: Pole Mounting Kit
 - For Use With: Wall Box
 - Material: Steel
 - Dimensions: 140 → 260 mm



8428484 Pole Mounting Kit

BREATHER, IMMERSION PROOF

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Filter Type: Constant Pressure Equalization
 - Mounting Hole Diameter: M16 x 1
 - Automatic or Manual: Manual Override



838805 Constant

RS PRO GREY STEEL ENCLOSURE, FLANGED, GREY LID, 182 X 257 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Steel
 - External Length: 182 mm
 - External Height: 271 mm
 - External Width: 257 mm
 - External Dimensions: 182 x 257 x 271 mm
 - Colour: Grey
 - Lid Colour: Grey
 - Flanged: Yes



232046 Steel

RS PRO GREY STEEL ENCLOSURE, FLANGED, GREY LID, 182 X 192 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Steel
 - External Length: 182 mm
 - External Height: 246 mm
 - External Width: 192 mm
 - External Dimensions: 182 x 192 x 246 mm
 - Colour: Grey
 - Lid Colour: Grey
 - Flanged: Yes



232169 Steel

RS PRO GREY STEEL ENCLOSURE, FLANGED, GREY LID, 157 X 157 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Steel
 - External Length: 157 mm
 - External Height: 221 mm
 - External Width: 157 mm
 - External Dimensions: 157 x 157 x 221 mm
 - Colour: Grey
 - Lid Colour: Grey
 - Flanged: Yes



232175 Steel

RS PRO GREY STEEL ENCLOSURE, FLANGED, GREY LID, 117 X 132 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Steel
 - External Length: 117 mm
 - External Height: 136 mm
 - External Width: 132 mm
 - External Dimensions: 117 x 132 x 136 mm
 - Colour: Grey
 - Lid Colour: Grey
 - Flanged: Yes



232181 Steel

RS PRO GREY FIBREGLASS ENCLOSURE, IP67, GREY LID, 300 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Fibreglass
 - External Length: 300 mm
 - External Height: 175 mm
 - External Width: 370 mm
 - External Dimensions: 300 x 370 x 175 mm
 - IP Rating: IP67
 - Colour: Grey
 - Lid Colour: Grey



501480 Fibreglass

RS PRO GREY FIBREGLASS ENCLOSURE, IP66, TRANSPARENT LID,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Fibreglass
 - External Length: 372 mm
 - External Height: 175 mm
 - External Width: 302 mm
 - External Dimensions: 372 x 175 x 302 mm
 - IP Rating: IP66
 - Colour: Grey
 - Lid Colour: Transparent



501496 Fibreglass

RS PRO GREY FIBREGLASS ENCLOSURE, IP66, TRANSPARENT LID,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Fibreglass
 - External Length: 185 mm
 - External Height: 150 mm
 - External Width: 130 mm
 - External Dimensions: 185 x 130 x 150 mm
 - IP Rating: IP66
 - Colour: Grey
 - Lid Colour: Transparent



507977 Fibreglass

RS PRO GREY FIBREGLASS ENCLOSURE, IP67, GREY LID, 300 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Fibreglass
 - External Length: 300 mm
 - External Height: 175 mm
 - External Width: 300 mm
 - External Dimensions: 300 x 300 x 175 mm
 - IP Rating: IP67
 - Colour: Grey
 - Lid Colour: Grey



507999 Fibreglass

RS PRO GREY FIBREGLASS ENCLOSURE, IP67, GREY LID, 185 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Fibreglass
 - External Length: 185 mm
 - External Height: 175 mm
 - External Width: 300 mm
 - External Dimensions: 185 x 300 x 175 mm
 - IP Rating: IP67
 - Colour: Grey
 - Lid Colour: Grey



508009 Fibreglass

RS PRO GREY POLYESTER ENCLOSURE, IP67, GREY LID, 150 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Polyester
 - External Length: 150 mm
 - External Height: 130 mm
 - External Width: 185 mm
 - External Dimensions: 150 x 185 x 130 mm
 - IP Rating: IP67
 - Colour: Grey
 - Lid Colour: Grey



508015 Polyester

RS PRO GREY FIBREGLASS ENCLOSURE, IP66, TRANSPARENT LID,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Fibreglass
 - External Length: 300 mm
 - External Height: 300 mm
 - External Width: 175 mm
 - External Dimensions: 300 x 175 x 300 mm
 - IP Rating: IP66
 - Colour: Grey
 - Lid Colour: Transparent



508324 Fibreglass

RS PRO GREY FIBREGLASS ENCLOSURE, IP66, TRANSPARENT LID,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Fibreglass
 - External Length: 300 mm
 - External Height: 185 mm
 - External Width: 185 mm
 - External Dimensions: 300 x 175 x 185 mm
 - IP Rating: IP66
 - Colour: Grey
 - Lid Colour: Transparent



508330 Fibreglass

RS PRO ALUMINIUM ENCLOSURE, IP66, GREY LID, 81 X 100 X 100MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Aluminium
 - External Length: 100 mm
 - External Height: 81 mm
 - External Width: 100 mm
 - External Dimensions: 81 x 100 x 100 mm
 - IP Rating: IP66
 - Lid Colour: Grey
 - Flanged: No



1228916 Aluminium

RS PRO ALUMINIUM ENCLOSURE, IP65, IP66, IP67, IP68, GREY LID, 34 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Aluminium
 - External Length: 58 mm
 - External Height: 34 mm
 - External Width: 58 mm
 - External Dimensions: 34 x 58 x 64 mm
 - IP Rating: IP65, IP66, IP67, IP68
 - Lid Colour: Grey
 - Flanged: No



1228917 Aluminium

RS PRO GREY ALUMINIUM ENCLOSURE, IP65, IP66, IP67, IP68,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Aluminium
 - External Length: 75 mm
 - External Height: 57 mm
 - External Width: 75 mm
 - External Dimensions: 57 x 75 x 80 mm
 - IP Rating: IP65, IP66, IP67, IP68
 - Colour: Grey
 - Lid Colour: Grey



1228919 Aluminium

RS PRO GREY ALUMINIUM ENCLOSURE, IP65, IP66, IP67, IP68,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Aluminium
 - External Length: 122 mm
 - External Height: 91 mm
 - External Width: 122 mm
 - External Dimensions: 91 x 122 x 120 mm
 - IP Rating: IP65, IP66, IP67, IP68
 - Colour: Grey
 - Lid Colour: Grey



1228920 Aluminium

RS PRO ALUMINIUM ENCLOSURE, IP66, GREY LID, 180 X 330 X 230MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Aluminium
 - External Length: 330 mm
 - External Height: 180 mm
 - External Width: 330 mm
 - External Dimensions: 180 x 330 x 230 mm
 - IP Rating: IP66
 - Lid Colour: Grey
 - Flanged: No



1228921 Aluminium

RS PRO ALUMINIUM ENCLOSURE, IP65, IP66, IP67, IP68, GREY LID, 111 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Aluminium
 - External Length: 330 mm
 - External Height: 111 mm
 - External Width: 330 mm
 - External Dimensions: 111 x 330 x 230 mm
 - IP Rating: IP65, IP66, IP67, IP68
 - Lid Colour: Grey
 - Flanged: No



1228923 Aluminium

RS PRO ALUMINIUM ENCLOSURE, IP65, IP66, IP67, IP68, GREY LID, 91 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Aluminium
 - External Length: 160 mm
 - External Height: 91 mm
 - External Width: 160 mm
 - External Dimensions: 91 x 160 x 160 mm
 - IP Rating: IP65, IP66, IP67, IP68
 - Lid Colour: Grey
 - Flanged: No



1228926 Aluminium

RS PRO ALUMINIUM ENCLOSURE, IP65, IP66, IP67, IP68, GREY LID, 113 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Aluminium
 - External Length: 230 mm
 - External Height: 113 mm
 - External Width: 230 mm
 - External Dimensions: 113 x 230 x 200 mm
 - IP Rating: IP65, IP66, IP67, IP68
 - Lid Colour: Grey
 - Flanged: No



1228927 Aluminium

RS PRO ALUMINIUM ENCLOSURE, IP65, IP66, IP67, IP68, GREY LID, 81 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Aluminium
 - External Length: 220 mm
 - External Height: 81 mm
 - External Width: 220 mm
 - External Dimensions: 81 x 220 x 120 mm
 - IP Rating: IP65, IP66, IP67, IP68
 - Lid Colour: Grey
 - Flanged: No



1228928 Aluminium

RS PRO ALUMINIUM ENCLOSURE, IP65, IP66, IP67, IP68, GREY LID, 90 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Aluminium
 - External Length: 360 mm
 - External Height: 90 mm
 - External Width: 360 mm
 - External Dimensions: 90 x 360 x 160 mm
 - IP Rating: IP65, IP66, IP67, IP68
 - Lid Colour: Grey
 - Flanged: No



1228929 Aluminium

RS PRO GREY ALUMINIUM ENCLOSURE, IP65, IP66, IP67, IP68,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Aluminium
 - External Length: 260 mm
 - External Height: 90 mm
 - External Width: 260 mm
 - External Dimensions: 90 x 260 x 160 mm
 - IP Rating: IP65, IP66, IP67, IP68
 - Colour: Grey
 - Lid Colour: Grey



1228930 Aluminium

RS PRO ALUMINIUM ENCLOSURE, IP66, GREY LID, 57 X 125 X 80MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Aluminium
 - External Length: 125 mm
 - External Height: 57 mm
 - External Width: 125 mm
 - External Dimensions: 57 x 125 x 80 mm
 - IP Rating: IP66
 - Lid Colour: Grey
 - Flanged: No



1228931 Aluminium

RS PRO ALUMINIUM ENCLOSURE, IP66, GREY LID, 160 X 100 X 81MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Aluminium
 - External Length: 160 mm
 - External Height: 81 mm
 - External Width: 100 mm
 - External Dimensions: 160 x 100 x 81 mm
 - IP Rating: IP66
 - Lid Colour: Grey
 - Flanged: No



1228934 Aluminium

RS PRO ALUMINIUM ENCLOSURE, IP65, IP66, IP67, IP68, GREY LID, 110 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Aluminium
 - External Length: 280 mm
 - External Height: 110 mm
 - External Width: 280 mm
 - External Dimensions: 110 x 280 x 230 mm
 - IP Rating: IP65, IP66, IP67, IP68
 - Lid Colour: Grey
 - Flanged: No



1228932 Aluminium

RS PRO ALUMINIUM ENCLOSURE, IP66, GREY LID, 81 X 220 X 120MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Aluminium
 - External Length: 220 mm
 - External Height: 81 mm
 - External Width: 220 mm
 - External Dimensions: 81 x 220 x 120 mm
 - IP Rating: IP66
 - Lid Colour: Grey
 - Flanged: No



1228933 Aluminium

RS PRO ALUMINIUM ENCLOSURE, IP66, GREY LID, 81 X 122 X 120MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Aluminium
 - External Length: 122 mm
 - External Height: 81 mm
 - External Width: 122 mm
 - External Dimensions: 81 x 122 x 120 mm
 - IP Rating: IP66
 - Lid Colour: Grey
 - Flanged: No



1228935 Aluminium

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, GREY LID, 50.8 X 50.8 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 50.8 mm
 - External Height: 31.8 mm
 - External Width: 50.8 mm
 - External Dimensions: 50.8 x 50.8 x 31.8 mm
 - Colour: Grey
 - Lid Colour: Grey



1465294 Die Cast

RS PRO BLACK DIE CAST ALUMINIUM ENCLOSURE, BLACK LID, 110 X 60 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 110 mm
 - External Height: 54 mm
 - External Width: 60 mm
 - External Dimensions: 110 x 60 x 54 mm
 - Colour: Black
 - Lid Colour: Black



1465333 Die Cast

RS PRO WHITE ABS ENCLOSURE, WHITE LID, 190 X 110 X 60MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 190 mm
 - External Height: 60 mm
 - External Width: 110 mm
 - External Dimensions: 190 x 110 x 60 mm
 - Colour: White
 - Lid Colour: White



1533202 ABS

RS PRO WHITE ABS ENCLOSURE, WHITE LID, 112 X 62 X 31MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 112 mm
 - External Height: 31 mm
 - External Width: 62 mm
 - External Dimensions: 112 x 62 x 31 mm
 - Colour: White
 - Lid Colour: White



1533203 ABS

RS PRO BLACK ABS ENCLOSURE, BLACK LID, 130 X 65 X 50.1MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 130 mm
 - External Height: 50.1 mm
 - External Width: 65 mm
 - External Dimensions: 130 x 65 x 50.1 mm
 - Colour: Black
 - Lid Colour: Black



1533204 ABS

RS PRO WHITE ABS ENCLOSURE, WHITE LID, 55 X 55 X 42MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 55 mm
 - External Height: 42 mm
 - External Width: 55 mm
 - External Dimensions: 55 x 55 x 42 mm
 - Colour: White
 - Lid Colour: White



1533208 ABS

RS PRO WHITE ABS ENCLOSURE, WHITE LID, 150 X 80 X 50MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 150 mm
 - External Height: 50 mm
 - External Width: 80 mm
 - External Dimensions: 150 x 80 x 50 mm
 - Colour: White
 - Lid Colour: White



1533211 ABS

RS PRO BLACK ABS ENCLOSURE, BLACK LID, 125 X 125 X 45MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 125 mm
 - External Height: 45 mm
 - External Width: 125 mm
 - External Dimensions: 125 x 125 x 45 mm
 - Colour: Black
 - Lid Colour: Black



1533671 ABS

RS PRO BLACK ABS ENCLOSURE, IP54, FLANGED, BLACK LID, 99.05 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 99.1 mm
 - External Height: 28 mm
 - External Width: 52.3 mm
 - External Dimensions: 99.05 x 52.3 x 28 mm
 - IP Rating: IP54
 - Colour: Black
 - Lid Colour: Black



1533672 ABS

RS PRO BLACK ABS ENCLOSURE, IP65, FLANGED, BLACK LID, 108.2 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 108.2 mm
 - External Height: 39.5 mm
 - External Width: 58.2 mm
 - External Dimensions: 108.2 x 58.2 x 39.5 mm
 - IP Rating: IP65
 - Colour: Black
 - Lid Colour: Black



1533674 ABS

RS PRO WHITE ABS ENCLOSURE, FLANGED, WHITE LID, 127 X 70.6 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 127 mm
 - External Height: 50.5 mm
 - External Width: 70.6 mm
 - External Dimensions: 127 x 70.6 x 50.5 mm
 - Colour: White
 - Lid Colour: White
 - Flanged: Yes



1533677 ABS

RS PRO GREY ABS ENCLOSURE, IP65, FLANGED, GREY LID, 173.4 X 82.4 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 173.4 mm
 - External Height: 50.5 mm
 - External Width: 82.4 mm
 - External Dimensions: 173.4 x 82.4 x 50.5 mm
 - IP Rating: IP65
 - Colour: Grey
 - Lid Colour: Grey



1533680 ABS

RS PRO BLACK ABS ENCLOSURE, BLACK LID, 100 X 50 X 25MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 100 mm
 - External Height: 25 mm
 - External Width: 50 mm
 - External Dimensions: 100 x 50 x 25 mm
 - Colour: Black
 - Lid Colour: Black



1533681 ABS

RS PRO GREY ABS ENCLOSURE, FLANGED, GREY LID, 127 X 70.6 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 127 mm
 - External Height: 35.5 mm
 - External Width: 70.6 mm
 - External Dimensions: 127 x 70.6 x 35.5 mm
 - Colour: Grey
 - Lid Colour: Grey
 - Flanged: Yes



1533682 ABS

RS PRO BLACK ABS ENCLOSURE, IP54, FLANGED, BLACK LID, 210 X 112

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 210 mm
 - External Height: 61 mm
 - External Width: 112 mm
 - External Dimensions: 210 x 112 x 61 mm
 - IP Rating: IP54
 - Colour: Black
 - Lid Colour: Black



1533684 ABS

RS PRO WHITE ABS ENCLOSURE, WHITE LID, 125 X 125 X 45MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 125 mm
 - External Height: 45 mm
 - External Width: 125 mm
 - External Dimensions: 125 x 125 x 45 mm
 - Colour: White
 - Lid Colour: White



1533685 ABS

RS PRO WHITE ABS ENCLOSURE, WHITE LID, 105 X 70 X 50MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: ABS
 - External Length: 105 mm
 - External Height: 50 mm
 - External Width: 70 mm
 - External Dimensions: 105 x 70 x 50 mm
 - Colour: White
 - Lid Colour: White

**1533686** ABS**RS PRO WHITE ABS ENCLOSURE, WHITE LID, 120 X 65 X 40MM**

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: ABS
 - External Length: 120 mm
 - External Height: 40 mm
 - External Width: 65 mm
 - External Dimensions: 120 x 65 x 40 mm
 - Colour: White
 - Lid Colour: White

**1533687** ABS**RS PRO GREY ABS ENCLOSURE, IP65, FLANGED, GREY LID, 108.2 X 58.2 X**

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: ABS
 - External Length: 108.2 mm
 - External Height: 39.5 mm
 - External Width: 58.2 mm
 - External Dimensions: 108.2 x 58.2 x 39.5 mm
 - IP Rating: IP65
 - Colour: Grey
 - Lid Colour: Grey

**1533688** ABS**RS PRO BLACK ABS ENCLOSURE, BLACK LID, 125 X 125 X 25MM**

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: ABS
 - External Length: 125 mm
 - External Height: 25 mm
 - External Width: 125 mm
 - External Dimensions: 125 x 125 x 25 mm
 - Colour: Black
 - Lid Colour: Black

**1533689** ABS**RS PRO BLACK ABS ENCLOSURE, IP65, FLANGED, BLACK LID, 173.4 X**

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: ABS
 - External Length: 173.4 mm
 - External Height: 50.5 mm
 - External Width: 82.4 mm
 - External Dimensions: 173.4 x 82.4 x 50.5 mm
 - IP Rating: IP65
 - Colour: Black
 - Lid Colour: Black

**1533692** ABS**RS PRO BLACK ABS ENCLOSURE, BLACK LID, 170 X 85.5 X 35.5MM**

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: ABS
 - External Length: 170 mm
 - External Height: 35.5 mm
 - External Width: 85.5 mm
 - External Dimensions: 170 x 85.5 x 35.5 mm
 - Colour: Black
 - Lid Colour: Black

**1533693** ABS**RS PRO GREY ABS ENCLOSURE, IP65, FLANGED, GREY LID, 135.8 X 64.55 X**

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: ABS
 - External Length: 135.8 mm
 - External Height: 31.5 mm
 - External Width: 64.6 mm
 - External Dimensions: 135.8 x 64.55 x 31.5 mm
 - IP Rating: IP65
 - Colour: Grey
 - Lid Colour: Grey

**1533695** ABS**RS PRO BLACK ABS ENCLOSURE, BLACK LID, 105 X 70 X 35MM**

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: ABS
 - External Length: 105 mm
 - External Height: 35 mm
 - External Width: 70 mm
 - External Dimensions: 105 x 70 x 35 mm
 - Colour: Black
 - Lid Colour: Black

**1533696** ABS**RS PRO WHITE ABS ENCLOSURE, WHITE LID, 170 X 85.5 X 35.5MM**

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: ABS
 - External Length: 170 mm
 - External Height: 35.5 mm
 - External Width: 85.5 mm
 - External Dimensions: 170 x 85.5 x 35.5 mm
 - Colour: White
 - Lid Colour: White

**1533702** ABS**RS PRO BLACK DIE CAST ALUMINIUM ENCLOSURE, IP54, BLACK LID, 120 X**

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: Die Cast Aluminium
 - External Length: 120 mm
 - External Height: 39.8 mm
 - External Width: 65.5 mm
 - External Dimensions: 120 x 65.5 x 39.75 mm
 - IP Rating: IP54
 - Colour: Black
 - Lid Colour: Black

**1585310** Die Cast**RS PRO RED DIE CAST ALUMINIUM ENCLOSURE, IP54, RED LID, 120 X**

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: Die Cast Aluminium
 - External Length: 120 mm
 - External Height: 39.8 mm
 - External Width: 65.5 mm
 - External Dimensions: 120 x 65.5 x 39.75 mm
 - IP Rating: IP54
 - Colour: Red
 - Lid Colour: Red

**1585311** Die Cast**RS PRO RED DIE CAST ALUMINIUM ENCLOSURE, IP54, RED LID, 152 X 82 X**

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: Die Cast Aluminium
 - External Length: 152 mm
 - External Height: 49.8 mm
 - External Width: 82 mm
 - External Dimensions: 152 x 82 x 49.75 mm
 - IP Rating: IP54
 - Colour: Red
 - Lid Colour: Red

**1585313** Die Cast**RS PRO BLACK DIE CAST ALUMINIUM ENCLOSURE, IP54, BLACK LID, 152 X**

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: Die Cast Aluminium
 - External Length: 152 mm
 - External Height: 49.8 mm
 - External Width: 82 mm
 - External Dimensions: 152 x 82 x 49.75 mm
 - IP Rating: IP54
 - Colour: Black
 - Lid Colour: Black

**1585312** Die Cast**RS PRO BLACK DIE CAST ALUMINIUM ENCLOSURE, IP54, BLACK LID, 191.6 X**

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: Die Cast Aluminium
 - External Length: 191.6 mm
 - External Height: 60.5 mm
 - External Width: 111.6 mm
 - External Dimensions: 191.6 x 111.6 x 60.5 mm
 - IP Rating: IP54
 - Colour: Black
 - Lid Colour: Black

**1585314** Die Cast**RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP54, SILVER LID, 187.4 X**

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: Die Cast Aluminium
 - External Length: 187.4 mm
 - External Height: 56.2 mm
 - External Width: 119.2 mm
 - External Dimensions: 187.4 x 119.2 x 56.2 mm
 - IP Rating: IP54
 - Colour: Silver
 - Lid Colour: Silver

**1610919** Die Cast**RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP54, SILVER LID, 120.5 X**

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: Die Cast Aluminium
 - External Length: 120.5 mm
 - External Height: 59.3 mm
 - External Width: 79.6 mm
 - External Dimensions: 120.5 x 79.6 x 59.3 mm
 - IP Rating: IP54
 - Colour: Silver
 - Lid Colour: Silver

**1610922** Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP54, SILVER LID, 152.2 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 152.2 mm
 - External Height: 50.8 mm
 - External Width: 82.2 mm
 - External Dimensions: 152.2 x 82.2 x 50.8 mm
 - IP Rating: IP54
 - Colour: Silver
 - Lid Colour: Silver



1610926 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP54, SILVER LID, 187.4 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 187.4 mm
 - External Height: 38.2 mm
 - External Width: 119.2 mm
 - External Dimensions: 187.4 x 119.2 x 38.2 mm
 - IP Rating: IP54
 - Colour: Silver
 - Lid Colour: Silver



1610927 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP54, SILVER LID, 190.1 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 190.1 mm
 - External Height: 66.5 mm
 - External Width: 190.1 mm
 - External Dimensions: 190.1 x 190.1 x 66.5 mm
 - IP Rating: IP54
 - Colour: Silver
 - Lid Colour: Silver



1610928 Die Cast

RS PRO SILVER ALUMINIUM ALLOY ENCLOSURE, IP65, BLACK LID, 115 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Aluminium Alloy
 - External Length: 115 mm
 - External Height: 30.2 mm
 - External Width: 65 mm
 - External Dimensions: 115 x 65 x 30.2 mm
 - IP Rating: IP65
 - Colour: Silver
 - Lid Colour: Black



1610931 Aluminium Alloy

RS PRO SILVER ALUMINIUM ALLOY ENCLOSURE, IP65, SILVER LID, 158.5 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Aluminium Alloy
 - External Length: 158.5 mm
 - External Height: 101.5 mm
 - External Width: 158.5 mm
 - External Dimensions: 158.5 x 158.5 x 101.5 mm
 - IP Rating: IP65
 - Colour: Silver
 - Lid Colour: Silver



1610935 Aluminium Alloy

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP54, SILVER LID, 101 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 101 mm
 - External Height: 24.5 mm
 - External Width: 50 mm
 - External Dimensions: 101 x 50 x 24.5 mm
 - IP Rating: IP54
 - Colour: Silver
 - Lid Colour: Silver



1610937 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP54, SILVER LID, 120 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 120 mm
 - External Height: 39.8 mm
 - External Width: 65.5 mm
 - External Dimensions: 120 x 65.5 x 39.75 mm
 - IP Rating: IP54
 - Colour: Silver
 - Lid Colour: Silver



1610939 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP54, IP65, IP66, SILVER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 152 mm
 - External Height: 49.8 mm
 - External Width: 82 mm
 - External Dimensions: 152 x 82 x 49.75 mm
 - IP Rating: IP54, IP65, IP66
 - Colour: Silver
 - Lid Colour: Silver



1610940 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP54, IP65, IP66, SILVER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 191.6 mm
 - External Height: 60.5 mm
 - External Width: 111.6 mm
 - External Dimensions: 191.6 x 111.6 x 60.5 mm
 - IP Rating: IP54, IP65, IP66
 - Colour: Silver
 - Lid Colour: Silver



1610941 Die Cast

RS PRO BLACK ABS ENCLOSURE, IP65, IK07, BLACK LID, 197.7 X 144.55

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 197.7 mm
 - External Height: 52.6 mm
 - External Width: 144.6 mm
 - External Dimensions: 197.7 x 144.55 x 52.55 mm
 - IP Rating: IP65
 - Colour: Black
 - Lid Colour: Black



1862249 ABS

RS PRO BLACK ABS ENCLOSURE, IP65, IK07, BLACK LID, 198.05 X 144.7

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 198.1 mm
 - External Height: 72.3 mm
 - External Width: 144.7 mm
 - External Dimensions: 198.05 x 144.7 x 72.25 mm
 - IP Rating: IP65
 - Colour: Black
 - Lid Colour: Black



1862250 ABS

RS PRO GREY ABS ENCLOSURE, IP65, IK07, GREY LID, 197.7 X 144.55 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 197.7 mm
 - External Height: 52.6 mm
 - External Width: 144.6 mm
 - External Dimensions: 197.7 x 144.55 x 52.55 mm
 - IP Rating: IP65
 - Colour: Grey
 - Lid Colour: Grey



1862251 ABS

RS PRO GREY ABS ENCLOSURE, IP65, IK09, GREY LID, 89.35 X 74.5 X 41MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 89.4 mm
 - External Height: 41 mm
 - External Width: 74.5 mm
 - External Dimensions: 89.35 x 74.5 x 41 mm
 - IP Rating: IP65
 - Colour: Grey
 - Lid Colour: Grey



1862253 ABS

RS PRO GREY ABS ENCLOSURE, IP67, IK09, GREY LID, 89.35 X 74.5 X 41MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 89.4 mm
 - External Height: 41 mm
 - External Width: 74.5 mm
 - External Dimensions: 89.35 x 74.5 x 41 mm
 - IP Rating: IP67
 - Colour: Grey
 - Lid Colour: Grey



1862254 ABS

RS PRO GREY ABS ENCLOSURE, IP65, IK09, GREY LID, 118.15 X 78.35 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 118.2 mm
 - External Height: 54.6 mm
 - External Width: 78.4 mm
 - External Dimensions: 118.15 x 78.35 x 54.6 mm
 - IP Rating: IP65
 - Colour: Grey
 - Lid Colour: Grey



1862255 ABS

RS PRO GREY ABS ENCLOSURE, IP67, IK09, GREY LID, 118.15 X 78.35 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 118.2 mm
 - External Height: 54.6 mm
 - External Width: 78.4 mm
 - External Dimensions: 118.15 x 78.35 x 54.6 mm
 - IP Rating: IP67
 - Colour: Grey
 - Lid Colour: Grey



1862256 ABS



RS PRO GREY ABS ENCLOSURE, IP65, IK09, GREY LID, 158.15 X 82.2 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 158.2 mm
 - External Height: 54.9 mm
 - External Width: 82.2 mm
 - External Dimensions: 158.15 x 82.2 x 54.9 mm
 - IP Rating: IP65
 - Colour: Grey
 - Lid Colour: Grey



1862257 ABS

RS PRO GREY ABS ENCLOSURE, IP67, IK09, GREY LID, 158.15 X 82.2 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 158.2 mm
 - External Height: 54.9 mm
 - External Width: 82.2 mm
 - External Dimensions: 158.15 x 82.2 x 54.9 mm
 - IP Rating: IP67
 - Colour: Grey
 - Lid Colour: Grey



1862258 ABS

RS PRO GREY ABS ENCLOSURE, IP65, IK09, GREY LID, 125.3 X 115.4 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 125.3 mm
 - External Height: 58.1 mm
 - External Width: 115.4 mm
 - External Dimensions: 125.3 x 115.4 x 58.05 mm
 - IP Rating: IP65
 - Colour: Grey
 - Lid Colour: Grey



1862259 ABS

RS PRO GREY ABS ENCLOSURE, IP67, IK09, GREY LID, 125.3 X 115.4 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 125.3 mm
 - External Height: 58.1 mm
 - External Width: 115.4 mm
 - External Dimensions: 125.3 x 115.4 x 58.05 mm
 - IP Rating: IP67
 - Colour: Grey
 - Lid Colour: Grey



1862260 ABS

RS PRO GREY ABS ENCLOSURE, IP65, IK09, GREY LID, 176.8 X 125.95 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 176.8 mm
 - External Height: 56.7 mm
 - External Width: 126 mm
 - External Dimensions: 176.8 x 125.95 x 56.65 mm
 - IP Rating: IP65
 - Colour: Grey
 - Lid Colour: Grey



1862261 ABS

RS PRO GREY ABS ENCLOSURE, IP67, IK09, GREY LID, 176.8 X 125.95 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 176.8 mm
 - External Height: 56.7 mm
 - External Width: 126 mm
 - External Dimensions: 176.8 x 125.95 x 56.65 mm
 - IP Rating: IP67
 - Colour: Grey
 - Lid Colour: Grey



1862262 ABS

RS PRO GREY ABS ENCLOSURE, IP65, IK09, GREY LID, 225 X 174.8 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 225 mm
 - External Height: 81.3 mm
 - External Width: 174.8 mm
 - External Dimensions: 225 x 174.8 x 81.25 mm
 - IP Rating: IP65
 - Colour: Grey
 - Lid Colour: Grey



1862263 ABS

RS PRO GREY ABS ENCLOSURE, IP67, IK09, GREY LID, 225 X 174.8 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 225 mm
 - External Height: 81.3 mm
 - External Width: 174.8 mm
 - External Dimensions: 225 x 174.8 x 81.25 mm
 - IP Rating: IP67
 - Colour: Grey
 - Lid Colour: Grey



1862264 ABS

RS PRO GREY ABS ENCLOSURE, IP65, IK09, GREY LID, 283 X 193.2 X 96.7MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 283 mm
 - External Height: 96.7 mm
 - External Width: 193.2 mm
 - External Dimensions: 283 x 193.2 x 96.7 mm
 - IP Rating: IP65
 - Colour: Grey
 - Lid Colour: Grey



1862265 ABS

RS PRO GREY ABS ENCLOSURE, IP67, IK09, GREY LID, 283 X 193.2 X 96.7MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 283 mm
 - External Height: 96.7 mm
 - External Width: 193.2 mm
 - External Dimensions: 283 x 193.2 x 96.7 mm
 - IP Rating: IP67
 - Colour: Grey
 - Lid Colour: Grey



1862266 ABS

RS PRO GREY ABS ENCLOSURE, IP65, IK09, GREY LID, 70 X 50 X 36.75MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 70 mm
 - External Height: 36.8 mm
 - External Width: 50 mm
 - External Dimensions: 70 x 50 x 36.75 mm
 - IP Rating: IP65
 - Colour: Grey
 - Lid Colour: Grey



1862267 ABS

RS PRO GREY ABS ENCLOSURE, IP67, IK09, GREY LID, 70 X 50 X 36.75MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 70 mm
 - External Height: 36.8 mm
 - External Width: 50 mm
 - External Dimensions: 70 x 50 x 36.75 mm
 - IP Rating: IP67
 - Colour: Grey
 - Lid Colour: Grey



1862268 ABS

RS PRO GREY ABS ENCLOSURE, IP65, IK09, GREY LID, 81.95 X 79.95 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 82 mm
 - External Height: 55 mm
 - External Width: 80 mm
 - External Dimensions: 81.95 x 79.95 x 55 mm
 - IP Rating: IP65
 - Colour: Grey
 - Lid Colour: Grey



1862269 ABS

RS PRO GREY ABS ENCLOSURE, IP67, IK09, GREY LID, 81.95 X 79.95 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 82 mm
 - External Height: 55 mm
 - External Width: 80 mm
 - External Dimensions: 81.95 x 79.95 x 55 mm
 - IP Rating: IP67
 - Colour: Grey
 - Lid Colour: Grey



1862270 ABS

RS PRO GREY ABS ENCLOSURE, IP65, IK09, GREY LID, 50.95 X 48.9 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 51 mm
 - External Height: 36.2 mm
 - External Width: 48.9 mm
 - External Dimensions: 50.95 x 48.9 x 36.15 mm
 - IP Rating: IP65
 - Colour: Grey
 - Lid Colour: Grey



1862271 ABS

RS PRO GREY ABS ENCLOSURE, IP67, IK09, GREY LID, 50.95 X 48.9 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 51 mm
 - External Height: 36.2 mm
 - External Width: 48.9 mm
 - External Dimensions: 50.95 x 48.9 x 36.15 mm
 - IP Rating: IP67
 - Colour: Grey
 - Lid Colour: Grey



1862272 ABS

RS PRO GREY ABS ENCLOSURE, IP65, IK09, GREY LID, 63.15 X 57.1 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 63.2 mm
 - External Height: 36.7 mm
 - External Width: 57.1 mm
 - External Dimensions: 63.15 x 57.1 x 36.65 mm
 - IP Rating: IP65
 - Colour: Grey
 - Lid Colour: Grey



1862273 ABS

RS PRO GREY ABS ENCLOSURE, IP67, IK09, GREY LID, 63.15 X 57.1 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 63.2 mm
 - External Height: 36.7 mm
 - External Width: 57.1 mm
 - External Dimensions: 63.15 x 57.1 x 36.65 mm
 - IP Rating: IP67
 - Colour: Grey
 - Lid Colour: Grey



1862274 ABS

RS PRO GREY ABS ENCLOSURE, IP65, IK07, GREY LID, 105 X 105 X 60MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 105 mm
 - External Height: 60 mm
 - External Width: 105 mm
 - External Dimensions: 105 x 105 x 60 mm
 - IP Rating: IP65
 - Colour: Grey
 - Lid Colour: Grey



1862275 ABS

RS PRO GREY ABS, POLYCARBONATE ENCLOSURE, IP67, IK07, 105 X 105 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS, Polycarbonate
 - External Length: 105 mm
 - External Height: 60.1 mm
 - External Width: 105 mm
 - External Dimensions: 105 x 105 x 60.1 mm
 - IP Rating: IP67
 - Colour: Grey
 - Shielded: Yes



1862277 ABS,

RS PRO GREY ABS ENCLOSURE, IP65, IK07, GREY LID, 119.8 X 119.8 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 119.8 mm
 - External Height: 60.1 mm
 - External Width: 119.8 mm
 - External Dimensions: 119.8 x 119.8 x 60.1 mm
 - IP Rating: IP65
 - Colour: Grey
 - Lid Colour: Grey



1862278 ABS

RS PRO GREY ABS ENCLOSURE, IP65, IK07, GREY LID, 149.85 X 149.85 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 149.9 mm
 - External Height: 60 mm
 - External Width: 149.9 mm
 - External Dimensions: 149.85 x 149.85 x 60 mm
 - IP Rating: IP65
 - Colour: Grey
 - Lid Colour: Grey



1862284 ABS

RS PRO GREY POLYCARBONATE ENCLOSURE, IP67, IK07, GREY LID,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Polycarbonate
 - External Length: 149.9 mm
 - External Height: 60 mm
 - External Width: 149.9 mm
 - External Dimensions: 149.85 x 149.85 x 60 mm
 - IP Rating: IP67
 - Colour: Grey
 - Lid Colour: Grey



1862285 Polycarbonate

RS PRO GREY ABS, POLYCARBONATE ENCLOSURE, IP67, IK07, 149.85 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS, Polycarbonate
 - External Length: 149.9 mm
 - External Height: 60 mm
 - External Width: 149.9 mm
 - External Dimensions: 149.85 x 149.85 x 60 mm
 - IP Rating: IP67
 - Colour: Grey
 - Shielded: Yes



1862286 ABS,

RS PRO BLACK EXTRUDED ALUMINIUM HEAT SINK CASE, IP40, BLACK LID,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Extruded Aluminium
 - External Length: 300 mm
 - External Height: 41 mm
 - External Width: 300 mm
 - External Dimensions: 300 x 300 x 41 mm
 - IP Rating: IP40
 - Colour: Black
 - Lid Colour: Black



1881259 Extruded

RS PRO BLACK EXTRUDED ALUMINIUM HEAT SINK CASE, IP40, BLACK LID,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Extruded Aluminium
 - External Length: 300 mm
 - External Height: 86 mm
 - External Width: 200 mm
 - External Dimensions: 300 x 200 x 86 mm
 - IP Rating: IP40
 - Colour: Black
 - Lid Colour: Black



1881265 Extruded

RS PRO BLACK EXTRUDED ALUMINIUM HEAT SINK CASE, IP40, BLACK LID,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Extruded Aluminium
 - External Length: 400 mm
 - External Height: 86 mm
 - External Width: 200 mm
 - External Dimensions: 400 x 200 x 86 mm
 - IP Rating: IP40
 - Colour: Black
 - Lid Colour: Black



1881266 Extruded

RS PRO BLACK EXTRUDED ALUMINIUM HEAT SINK CASE, IP40, BLACK LID,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Extruded Aluminium
 - External Length: 200 mm
 - External Height: 86 mm
 - External Width: 300 mm
 - External Dimensions: 200 x 300 x 86 mm
 - IP Rating: IP40
 - Colour: Black
 - Lid Colour: Black



1881267 Extruded

RS PRO BLACK EXTRUDED ALUMINIUM HEAT SINK CASE, IP40, BLACK LID,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Extruded Aluminium
 - External Length: 300 mm
 - External Height: 86 mm
 - External Width: 300 mm
 - External Dimensions: 300 x 300 x 86 mm
 - IP Rating: IP40
 - Colour: Black
 - Lid Colour: Black



1881268 Extruded

RS PRO BLACK EXTRUDED ALUMINIUM HEAT SINK CASE, IP40, BLACK LID,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Extruded Aluminium
 - External Length: 400 mm
 - External Height: 130 mm
 - External Width: 100 mm
 - External Dimensions: 400 x 100 x 130 mm
 - IP Rating: IP40
 - Colour: Black
 - Lid Colour: Black



1881272 Extruded

RS PRO BLACK EXTRUDED ALUMINIUM HEAT SINK CASE, IP40, BLACK LID,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Extruded Aluminium
 - External Length: 200 mm
 - External Height: 130 mm
 - External Width: 200 mm
 - External Dimensions: 200 x 200 x 130 mm
 - IP Rating: IP40
 - Colour: Black
 - Lid Colour: Black



1881273 Extruded

RS PRO BLACK EXTRUDED ALUMINIUM HEAT SINK CASE, IP40, BLACK LID,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Extruded Aluminium
 - External Length: 300 mm
 - External Height: 130 mm
 - External Width: 200 mm
 - External Dimensions: 300 x 200 x 130 mm
 - IP Rating: IP40
 - Colour: Black
 - Lid Colour: Black



1881274 Extruded

RS PRO BLACK EXTRUDED ALUMINIUM HEAT SINK CASE, IP40, BLACK LID,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: Extruded Aluminium
 - External Length: 300 mm
 - External Height: 130 mm
 - External Width: 300 mm
 - External Dimensions: 300 x 300 x 130 mm
 - IP Rating: IP40
 - Colour: Black
 - Lid Colour: Black



1881277 Extruded

RS PRO BLACK EXTRUDED ALUMINIUM HEAT SINK CASE, IP40, BLACK LID,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: Extruded Aluminium
 - External Length: 200 mm
 - External Height: 175 mm
 - External Width: 200 mm
 - External Dimensions: 200 x 200 x 175 mm
 - IP Rating: IP40
 - Colour: Black
 - Lid Colour: Black



1881283 Extruded

RS PRO BLACK EXTRUDED ALUMINIUM HEAT SINK CASE, IP40, BLACK LID,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: Extruded Aluminium
 - External Length: 300 mm
 - External Height: 175 mm
 - External Width: 200 mm
 - External Dimensions: 300 x 200 x 175 mm
 - IP Rating: IP40
 - Colour: Black
 - Lid Colour: Black



1881284 Extruded

RS PRO BLACK EXTRUDED ALUMINIUM HEAT SINK CASE, IP40, BLACK LID,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: Extruded Aluminium
 - External Length: 400 mm
 - External Height: 175 mm
 - External Width: 200 mm
 - External Dimensions: 400 x 200 x 175 mm
 - IP Rating: IP40
 - Colour: Black
 - Lid Colour: Black



1881285 Extruded

RS PRO BLACK EXTRUDED ALUMINIUM HEAT SINK CASE, IP40, BLACK LID,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: Extruded Aluminium
 - External Length: 400 mm
 - External Height: 175 mm
 - External Width: 300 mm
 - External Dimensions: 400 x 300 x 175 mm
 - IP Rating: IP40
 - Colour: Black
 - Lid Colour: Black



1881288 Extruded

RS PRO BLACK EXTRUDED ALUMINIUM HEAT SINK CASE, IP40, BLACK LID,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: Extruded Aluminium
 - External Length: 300 mm
 - External Height: 219 mm
 - External Width: 200 mm
 - External Dimensions: 300 x 200 x 219 mm
 - IP Rating: IP40
 - Colour: Black
 - Lid Colour: Black



1881290 Extruded

RS PRO BLACK EXTRUDED ALUMINIUM HEAT SINK CASE, IP40, BLACK LID,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: Extruded Aluminium
 - External Length: 400 mm
 - External Height: 219 mm
 - External Width: 300 mm
 - External Dimensions: 400 x 300 x 219 mm
 - IP Rating: IP40
 - Colour: Black
 - Lid Colour: Black



1881294 Extruded

RS PRO BLACK EXTRUDED ALUMINIUM HEAT SINK CASE, IP40, BLACK LID,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: Extruded Aluminium
 - External Length: 299 mm
 - External Height: 50 mm
 - External Width: 175 mm
 - External Dimensions: 299 x 175 x 50 mm
 - IP Rating: IP40
 - Colour: Black
 - Lid Colour: Black



1881301 Extruded

RS PRO GREY EXTRUDED ALUMINIUM ENCLOSURE, IP30, GREY LID, 178 X

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: Extruded Aluminium
 - External Length: 178 mm
 - External Height: 65 mm
 - External Width: 203 mm
 - External Dimensions: 178 x 203 x 65 mm
 - IP Rating: IP30
 - Colour: Grey
 - Lid Colour: Grey



1881328 Extruded

RS PRO GREY EXTRUDED ALUMINIUM ENCLOSURE, IP30, GREY LID, 178 X

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: Extruded Aluminium
 - External Length: 178 mm
 - External Height: 175 mm
 - External Width: 305 mm
 - External Dimensions: 178 x 305 x 175 mm
 - IP Rating: IP30
 - Colour: Grey
 - Lid Colour: Grey



1881337 Extruded

RS PRO GREY FIBREGLASS REINFORCED POLYESTER

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: Fibreglass Reinforced Polyester
 - External Length: 600 mm
 - External Height: 121 mm
 - External Width: 250 mm
 - External Dimensions: 600 x 250 x 121 mm
 - IP Rating: IP66
 - Colour: Grey
 - Lid Colour: Grey



1901843 Fibreglass

RS PRO GREY FIBREGLASS REINFORCED POLYESTER GENERAL

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: Fibreglass Reinforced Polyester
 - External Length: 400 mm
 - External Height: 160 mm
 - External Width: 250 mm
 - External Dimensions: 400 x 250 x 160 mm
 - IP Rating: IP66
 - Colour: Grey
 - Lid Colour: Grey



1901847 Fibreglass

RS PRO BLACK FIBREGLASS REINFORCED POLYESTER GENERAL

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: Fibreglass Reinforced Polyester
 - External Length: 255 mm
 - External Height: 160 mm
 - External Width: 250 mm
 - External Dimensions: 255 x 250 x 160 mm
 - IP Rating: IP66, IP67, IP68
 - Colour: Black
 - Lid Colour: Black



1901848 Fibreglass

RS PRO BLACK FIBREGLASS REINFORCED POLYESTER GENERAL

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: Fibreglass Reinforced Polyester
 - External Length: 80 mm
 - External Height: 75 mm
 - External Width: 75 mm
 - External Dimensions: 80 x 75 x 75 mm
 - IP Rating: IP66, IP67, IP68
 - Colour: Black
 - Lid Colour: Black



1901854 Fibreglass

RS PRO GREY FIBREGLASS REINFORCED POLYESTER

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: Fibreglass Reinforced Polyester
 - External Length: 80 mm
 - External Height: 75 mm
 - External Width: 75 mm
 - External Dimensions: 80 x 75 x 75 mm
 - IP Rating: IP66, IP67, IP68
 - Colour: Grey
 - Lid Colour: Grey



1901856 Fibreglass

RS PRO SILVER ALUMINIUM ENCLOSURE, IP66, IP67, IP68, IK09,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: Aluminium
 - External Length: 58 mm
 - External Height: 34 mm
 - External Width: 64 mm
 - External Dimensions: 58 x 64 x 34 mm
 - IP Rating: IP66, IP67, IP68
 - Colour: Silver
 - Lid Colour: Silver



1901860 Aluminium

RS PRO SILVER ALUMINIUM ENCLOSURE, IP66, IP67, IP68, IK09,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Aluminium
 - External Length: 140 mm
 - External Height: 90 mm
 - External Width: 140 mm
 - External Dimensions: 140 x 140 x 90 mm
 - IP Rating: IP66, IP67, IP68
 - Colour: Silver
 - Lid Colour: Silver



1901861 Aluminium

RS PRO GREY ALUMINIUM ENCLOSURE, IP66, IP67, IP68, IK09,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Aluminium
 - External Length: 200 mm
 - External Height: 90 mm
 - External Width: 140 mm
 - External Dimensions: 200 x 140 x 90 mm
 - IP Rating: IP66, IP67, IP68
 - Colour: Grey
 - Lid Colour: Grey



1901864 Aluminium

RS PRO BLACK FIBREGLASS REINFORCED POLYESTER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Fibreglass Reinforced Polyester
 - External Length: 110 mm
 - External Height: 75 mm
 - External Width: 75 mm
 - External Dimensions: 110 x 75 x 75 mm
 - IP Rating: IP66, IP67, IP68
 - Colour: Black
 - RAL Code: RAL 9011



1901866 Fibreglass

RS PRO BLACK FIBREGLASS REINFORCED POLYESTER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Fibreglass Reinforced Polyester
 - External Length: 255 mm
 - External Height: 160 mm
 - External Width: 250 mm
 - External Dimensions: 255 x 250 x 160 mm
 - IP Rating: IP66, IP67, IP68
 - Colour: Black
 - RAL Code: RAL 9011



1901868 Fibreglass

RS PRO BLACK FIBREGLASS REINFORCED POLYESTER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Fibreglass Reinforced Polyester
 - External Length: 400 mm
 - External Height: 201 mm
 - External Width: 405 mm
 - External Dimensions: 400 x 405 x 201 mm
 - IP Rating: IP66, IP67, IP68
 - Colour: Black
 - RAL Code: RAL 9011



1901870 Fibreglass

RS PRO ALUMINIUM ENCLOSURE, IP66, IP67, IP68, IK09, 180 X 180 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Aluminium
 - External Length: 180 mm
 - External Height: 100 mm
 - External Width: 180 mm
 - External Dimensions: 180 x 180 x 100 mm
 - IP Rating: IP66, IP67, IP68
 - IK Rating: IK09
 - Gasket Material: Silicone



1901874 Aluminium

RS PRO ALUMINIUM ENCLOSURE, IP66, IP67, IP68, IK09, 200 X 140 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Aluminium
 - External Length: 200 mm
 - External Height: 90 mm
 - External Width: 140 mm
 - External Dimensions: 200 x 140 x 90 mm
 - IP Rating: IP66, IP67, IP68
 - IK Rating: IK09
 - Gasket Material: Silicone



1901875 Aluminium

RS PRO GREY FIBREGLASS REINFORCED POLYESTER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Fibreglass Reinforced Polyester
 - External Length: 255 mm
 - External Height: 160 mm
 - External Width: 250 mm
 - External Dimensions: 255 x 250 x 160 mm
 - IP Rating: IP66
 - Colour: Grey
 - Lid Colour: Grey



1904274 Fibreglass

RS PRO GREY FIBREGLASS REINFORCED POLYESTER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Fibreglass Reinforced Polyester
 - External Length: 110 mm
 - External Height: 75 mm
 - External Width: 75 mm
 - External Dimensions: 110 x 75 x 75 mm
 - IP Rating: IP66
 - Colour: Grey
 - Lid Colour: Grey



1904275 Fibreglass

RS PRO GREY FIBREGLASS REINFORCED POLYESTER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Fibreglass Reinforced Polyester
 - External Length: 80 mm
 - External Height: 75 mm
 - External Width: 75 mm
 - External Dimensions: 80 x 75 x 75 mm
 - IP Rating: IP66
 - Colour: Grey
 - Lid Colour: Grey



1904276 Fibreglass

RS PRO BLACK FIBREGLASS REINFORCED POLYESTER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Fibreglass Reinforced Polyester
 - External Length: 190 mm
 - External Height: 75 mm
 - External Width: 75 mm
 - External Dimensions: 190 x 75 x 75 mm
 - IP Rating: IP66
 - Colour: Black
 - Lid Colour: Black



1904279 Fibreglass

RS PRO GREY ABS ENCLOSURE, IP65, GREY LID, 139.8 X 209.7 X 60.1MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 209.7 mm
 - External Height: 75 mm
 - External Width: 139.8 mm
 - External Dimensions: 139.8 x 209.7 x 60.1 mm
 - IP Rating: IP65
 - Colour: Grey
 - Lid Colour: Grey



1920695 ABS

RS PRO GREY ABS ENCLOSURE, IP65, GREY LID, 100.1 X 150.1 X 60MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 150.1 mm
 - External Height: 60 mm
 - External Width: 100.1 mm
 - External Dimensions: 100.1 x 150.1 x 60 mm
 - IP Rating: IP65
 - Colour: Grey
 - Lid Colour: Grey



1920698 ABS

RS PRO ABS GENERAL PURPOSE ENCLOSURE, 181.55 X 100 X 60MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 181.55 mm
 - External Height: 60 mm
 - External Width: 100 mm
 - External Dimensions: 181.55 x 100 x 60 mm



1920699 ABS

RS PRO GREY ABS ENCLOSURE, IP65, GREY LID, 100 X 150 X 75MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 150 mm
 - External Height: 75 mm
 - External Width: 100 mm
 - External Dimensions: 100 x 150 x 75 mm
 - IP Rating: IP65
 - Colour: Grey
 - Lid Colour: Grey



1920700 ABS

RS PRO GREY ABS ENCLOSURE, IP65, GREY LID, 120.1 X 180.1 X 90.3MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 180.1 mm
 - External Height: 90.3 mm
 - External Width: 120.1 mm
 - External Dimensions: 120.1 x 180.1 x 90.3 mm
 - IP Rating: IP65
 - Colour: Grey
 - Lid Colour: Grey



1920702 ABS

RS PRO BLACK ABS ENCLOSURE, IP20, IK06, BLACK LID, 75.8 X 75.8 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 75.8 mm
 - External Height: 30.3 mm
 - External Width: 75.6 mm
 - External Dimensions: 75.8 x 75.8 x 30.2 mm
 - IP Rating: IP20
 - Colour: Black
 - Lid Colour: Black



1920714 ABS

RS PRO WHITE ABS ENCLOSURE, IP20, IK06, WHITE LID, 75.8 X 75.8 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 75.8 mm
 - External Height: 30.3 mm
 - External Width: 75.6 mm
 - External Dimensions: 75.8 x 75.8 x 30.2 mm
 - IP Rating: IP20
 - Colour: White
 - Lid Colour: White



1920716 ABS

RS PRO GREY ABS ENCLOSURE, IP65, IK08, GREY LID, 105 X 70 X 40MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 105 mm
 - External Height: 40 mm
 - External Width: 70 mm
 - External Dimensions: 105 x 70 x 40 mm
 - IP Rating: IP65
 - Colour: Grey
 - Lid Colour: Grey



1920721 ABS

RS PRO GREY POLYCARBONATE ENCLOSURE, IP68, IK07, GREY LID,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Polycarbonate
 - External Length: 105 mm
 - External Height: 40 mm
 - External Width: 70 mm
 - External Dimensions: 105 x 70 x 40 mm
 - IP Rating: IP68
 - Colour: Grey
 - Lid Colour: Grey



1920722 Polycarbonate

RS PRO GREY ABS, POLYCARBONATE ENCLOSURE, IP68, IK07,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS, Polycarbonate
 - External Length: 105 mm
 - External Height: 40 mm
 - External Width: 70 mm
 - External Dimensions: 105 x 70 x 40 mm
 - IP Rating: IP68
 - Colour: Grey
 - Lid Colour: Transparent



1920723 ABS,

RS PRO GREY POLYCARBONATE ENCLOSURE, IP68, IK07, FLANGED,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Polycarbonate
 - External Length: 131.3 mm
 - External Height: 40 mm
 - External Width: 71.3 mm
 - External Dimensions: 105 x 70 x 40 mm
 - IP Rating: IP68
 - Colour: Grey
 - Lid Colour: Grey



1920726 Polycarbonate

RS PRO GREY ABS, POLYCARBONATE ENCLOSURE, IP68, IK07, FLANGED,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS, Polycarbonate
 - External Length: 131.3 mm
 - External Height: 40 mm
 - External Width: 71.3 mm
 - External Dimensions: 105 x 70 x 40 mm
 - IP Rating: IP68
 - Colour: Grey
 - Lid Colour: Transparent



1920727 ABS,

RS PRO BLACK ABS ENCLOSURE, BLACK LID, 31.5 X 56.5 X 27.2MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 56.5 mm
 - External Height: 31.5 mm
 - External Width: 27.2 mm
 - External Dimensions: 31.5 x 56.5 x 27.2 mm
 - Colour: Black
 - Lid Colour: Black
 - Flanged: No



1920728 ABS

PLASTIC ENCLOSURE Z70 WITH LUGS ABS

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 75.8 mm
 - External Height: 27.9 mm
 - External Width: 77.9 mm
 - External Dimensions: 75.75 x 77.85 x 27.9 mm
 - IP Rating: IP54
 - Colour: Black
 - Flanged: Yes



1920744 ABS

RS PRO BLACK ABS ENCLOSURE, IP54, IK06, BLACK LID, 120 X 90 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 119 mm
 - External Height: 37.9 mm
 - External Width: 89.3 mm
 - External Dimensions: 120 x 90 x 38 mm
 - IP Rating: IP54
 - Colour: Black
 - Lid Colour: Black



1920746 ABS

RS PRO BLACK ABS ENCLOSURE, IP52, BLACK LID, 32 X 22 X 17.2MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 32 mm
 - External Height: 17.2 mm
 - External Width: 22 mm
 - External Dimensions: 32 x 22 x 17.2 mm
 - IP Rating: IP52
 - Colour: Black
 - Lid Colour: Black



1920750 ABS

RS PRO BLACK ABS ENCLOSURE, IP52, BLACK LID, 41.8 X 41.8 X 21.5MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 41.8 mm
 - External Height: 21.5 mm
 - External Width: 41.8 mm
 - External Dimensions: 41.8 x 41.8 x 21.5 mm
 - IP Rating: IP52
 - Colour: Black
 - Lid Colour: Black



1920754 ABS

RS PRO BLACK ABS ENCLOSURE, IP54, BLACK LID, 52 X 46 X 26MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 46 mm
 - External Height: 26 mm
 - External Width: 52 mm
 - External Dimensions: 52 x 46 x 26 mm
 - IP Rating: IP54
 - Colour: Black
 - Lid Colour: Black



1920755 ABS

RS PRO BLACK ABS ENCLOSURE, IP53, IK06, BLACK LID, 185.5 X 136 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 185.8 mm
 - External Height: 65.3 mm
 - External Width: 135.9 mm
 - External Dimensions: 185.5 x 136 x 60 mm
 - IP Rating: IP53
 - Colour: Black
 - Lid Colour: Black



1920756 ABS

RS PRO BLACK ABS ENCLOSURE, IP53, IK06, BLACK LID, 185.5 X 136 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 184.6 mm
 - External Height: 45.5 mm
 - External Width: 135.9 mm
 - External Dimensions: 185.5 x 136 x 40 mm
 - IP Rating: IP53
 - Colour: Black
 - Lid Colour: Black



1920757 ABS

RS PRO BLACK ABS ENCLOSURE, IP53, IK06, BLACK LID, 185.5 X 136 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 185.8 mm
 - External Height: 84.8 mm
 - External Width: 135.7 mm
 - External Dimensions: 185.5 x 136 x 80 mm
 - IP Rating: IP53
 - Colour: Black
 - Lid Colour: Black



1920758 ABS

RS PRO BLACK ABS ENCLOSURE, IK04, 105 X 30 X 21.5MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 105 mm
 - External Height: 21.5 mm
 - External Width: 30 mm
 - External Dimensions: 105 x 30 x 21.5 mm
 - Colour: Black
 - IK Rating: IK04



1920759 ABS

RS PRO BLACK ABS ENCLOSURE, IP54, IK07, BLACK LID, 149 X 51 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 149 mm
 - External Height: 24.1 mm
 - External Width: 50.5 mm
 - External Dimensions: 149 x 51 x 24 mm
 - IP Rating: IP54
 - Colour: Black
 - Lid Colour: Black



1920762 ABS

RS PRO BLACK ABS ENCLOSURE, IP54, IK07, BLACK LID, 189.9 X 89.8 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 189.9 mm
 - External Height: 50.5 mm
 - External Width: 89.8 mm
 - External Dimensions: 189.9 x 89.8 x 50.5 mm
 - IP Rating: IP54
 - Colour: Black
 - Lid Colour: Black



1920765 ABS

RS PRO BLACK ABS ENCLOSURE, IP54, 155 X 49 X 27MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 177.4 mm
 - External Height: 27 mm
 - External Width: 49.4 mm
 - External Dimensions: 155 x 49 x 27 mm
 - IP Rating: IP54
 - Colour: Black
 - Flanged: No



1920776 ABS

RS PRO BLACK ABS ENCLOSURE, IP40, IK05, 74 X 68 X 36MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 74.5 mm
 - External Height: 36.2 mm
 - External Width: 67.9 mm
 - External Dimensions: 74 x 68 x 36 mm
 - IP Rating: IP40
 - Colour: Black
 - Flanged: No



1920778 ABS

RS PRO BLACK ABS ENCLOSURE, IP54, 26.45 X 17.25 X 14.6MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 26.5 mm
 - External Height: 14.6 mm
 - External Width: 17.3 mm
 - External Dimensions: 26.45 x 17.25 x 14.6 mm
 - IP Rating: IP54
 - Colour: Black



1920780 ABS

RS PRO BLACK ABS ENCLOSURE, IP53, BLACK LID, 66 X 49 X 28MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 68.8 mm
 - External Height: 27.7 mm
 - External Width: 64.7 mm
 - External Dimensions: 66 x 49 x 28 mm
 - IP Rating: IP53
 - Colour: Black
 - Lid Colour: Black



1920786 ABS

RS PRO BLACK ABS ENCLOSURE, IP53, IK07, 75.9 X 58.8 X 27.9MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 75.8 mm
 - External Height: 27.9 mm
 - External Width: 58.9 mm
 - External Dimensions: 75.9 x 58.8 x 27.9 mm
 - IP Rating: IP53
 - Colour: Black
 - Flanged: No



1920789 ABS

PLASTIC ENCLOSURE Z72 ABS

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 178.9 mm
 - External Height: 54.3 mm
 - External Width: 102.1 mm
 - External Dimensions: 178.9 x 102 x 48.8 mm
 - IP Rating: IP53
 - Colour: Black
 - Flanged: No



1920791 ABS

RS PRO BLACK ABS ENCLOSURE, IP55, IK06, 109.2 X 79.15 X 31.9MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 109.2 mm
 - External Height: 31.9 mm
 - External Width: 79.2 mm
 - External Dimensions: 109.2 x 79.15 x 31.9 mm
 - IP Rating: IP55
 - Colour: Black
 - IK Rating: IK06



1920793 ABS

PLASTIC ENCLOSURE Z75 ABS

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 95 mm
 - External Height: 23.2 mm
 - External Width: 45.3 mm
 - External Dimensions: 95 x 45 x 23 mm
 - IP Rating: IP54
 - Colour: Black
 - Shielded: No



1920794 ABS

PLASTIC ENCLOSURE Z76 ABS

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 109.9 mm
 - External Height: 28.3 mm
 - External Width: 59.9 mm
 - External Dimensions: 109 x 59.5 x 28 mm
 - IP Rating: IP54
 - Colour: Black
 - Shielded: No



1920795 ABS

PLASTIC ENCLOSURE Z77 ABS

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 124.7 mm
 - External Height: 37.1 mm
 - External Width: 72 mm
 - External Dimensions: 124 x 71.5 x 38 mm
 - IP Rating: IP54
 - Colour: Black
 - Shielded: No



1920796 ABS

RS PRO BLACK ABS ENCLOSURE, IP20, IK03, 84.8 X 60.8 X 32MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 102 mm
 - External Height: 34.7 mm
 - External Width: 77.5 mm
 - External Dimensions: 84.8 x 60.8 x 32 mm
 - IP Rating: IP20
 - Colour: Black
 - Flanged: No



1920801 ABS

RS PRO SILVER DIE CAST ALUMINIUM GENERAL PURPOSE ENCLOSURE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 111 mm
 - External Height: 31 mm
 - External Width: 60 mm
 - External Dimensions: 111 x 60 x 31 mm
 - IP Rating: IP54
 - Colour: Silver
 - Lid Colour: Black



1947613 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM GENERAL PURPOSE ENCLOSURE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 119 mm
 - External Height: 56 mm
 - External Width: 94 mm
 - External Dimensions: 119 x 94 x 56 mm
 - IP Rating: IP54
 - Colour: Silver
 - Lid Colour: Black



1947614 Die Cast

RS PRO BLACK ABS GENERAL PURPOSE ENCLOSURE, IP54, BLACK

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 55 mm
 - Range: General Purpose Moulded Enclosure
 - External Height: 42 mm
 - External Width: 55 mm
 - External Dimensions: 55 x 55 x 42 mm
 - IP Rating: IP54
 - Colour: Black



1959123 ABS

RS PRO GREY ABS GENERAL PURPOSE ENCLOSURE, IP54, GREY

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 55 mm
 - Range: General Purpose Moulded Enclosure
 - External Height: 42 mm
 - External Width: 55 mm
 - External Dimensions: 55 x 55 x 42 mm
 - IP Rating: IP54
 - Colour: Grey



1959124 ABS

RS PRO GREY ABS GENERAL PURPOSE ENCLOSURE, IP54, GREY

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 200 mm
 - Range: General Purpose Moulded Enclosure
 - External Height: 65 mm
 - External Width: 250 mm
 - External Dimensions: 200 x 250 x 65 mm
 - IP Rating: IP54
 - Colour: Grey



1959125 ABS

RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Polycarbonate
 - External Length: 95 mm
 - External Height: 60 mm
 - External Width: 65 mm
 - External Dimensions: 95 x 65 x 60 mm
 - IP Rating: IP65
 - Colour: Grey
 - Lid Colour: Grey



1972005 Polycarbonate

RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Polycarbonate
 - External Length: 110 mm
 - External Height: 65 mm
 - External Width: 110 mm
 - External Dimensions: 110 x 110 x 65 mm
 - IP Rating: IP65
 - Colour: Grey
 - Lid Colour: Grey



1972006 Polycarbonate

RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Polycarbonate
 - External Length: 130 mm
 - External Height: 65 mm
 - External Width: 95 mm
 - External Dimensions: 130 x 95 x 65 mm
 - IP Rating: IP65
 - Colour: Grey
 - Lid Colour: Grey



1972008 Polycarbonate

RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Polycarbonate
 - External Length: 130 mm
 - External Height: 75 mm
 - External Width: 130 mm
 - External Dimensions: 130 x 130 x 75 mm
 - IP Rating: IP65
 - Colour: Grey
 - Lid Colour: Grey



1972009 Polycarbonate

RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Polycarbonate
 - External Length: 187 mm
 - External Height: 90 mm
 - External Width: 122 mm
 - External Dimensions: 187 x 122 x 90 mm
 - IP Rating: IP65
 - Colour: Grey
 - Lid Colour: Grey



1972010 Polycarbonate

RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Polycarbonate
 - External Length: 187 mm
 - External Height: 90 mm
 - External Width: 122 mm
 - External Dimensions: 187 x 122 x 90 mm
 - IP Rating: IP65
 - Colour: Grey
 - Lid Colour: Transparent



1972011 Polycarbonate

RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Polycarbonate
 - External Length: 240 mm
 - External Height: 107 mm
 - External Width: 191 mm
 - External Dimensions: 240 x 191 x 107 mm
 - IP Rating: IP65
 - Colour: Grey
 - Lid Colour: Grey



1972015 Polycarbonate

RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Polycarbonate
 - External Length: 240 mm
 - External Height: 107 mm
 - External Width: 191 mm
 - External Dimensions: 240 x 191 x 107 mm
 - IP Rating: IP65
 - Colour: Grey
 - Lid Colour: Transparent



1972016 Polycarbonate

RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Polycarbonate
 - External Length: 289 mm
 - External Height: 107 mm
 - External Width: 239 mm
 - External Dimensions: 289 x 239 x 107 mm
 - IP Rating: IP65
 - Colour: Grey
 - Lid Colour: Grey



1972017 Polycarbonate

RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Polycarbonate
 - External Length: 289 mm
 - External Height: 107 mm
 - External Width: 239 mm
 - External Dimensions: 289 x 239 x 107 mm
 - IP Rating: IP65
 - Colour: Grey
 - Lid Colour: Transparent



1972018 Polycarbonate

RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Polycarbonate
 - External Length: 344 mm
 - External Height: 117 mm
 - External Width: 289 mm
 - External Dimensions: 344 x 289 x 117 mm
 - IP Rating: IP65
 - Colour: Grey
 - Lid Colour: Grey



1972019 Polycarbonate

RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Polycarbonate
 - External Length: 344 mm
 - External Height: 117 mm
 - External Width: 289 mm
 - External Dimensions: 344 x 289 x 117 mm
 - IP Rating: IP65
 - Colour: Grey
 - Lid Colour: Transparent



1972020 Polycarbonate

RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Polycarbonate
 - External Length: 95 mm
 - External Height: 60 mm
 - External Width: 65 mm
 - External Dimensions: 95 x 65 x 60 mm
 - IP Rating: IP65
 - Colour: Grey
 - Lid Colour: Grey



1972021 Polycarbonate

RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Polycarbonate
 - External Length: 110 mm
 - External Height: 65 mm
 - External Width: 110 mm
 - External Dimensions: 110 x 110 x 65 mm
 - IP Rating: IP65
 - Colour: Grey
 - Lid Colour: Grey



1972022 Polycarbonate

RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Polycarbonate
 - External Length: 130 mm
 - External Height: 75 mm
 - External Width: 130 mm
 - External Dimensions: 130 x 130 x 75 mm
 - IP Rating: IP65
 - Colour: Grey
 - Lid Colour: Grey



1972024 Polycarbonate

RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Polycarbonate
 - External Length: 187 mm
 - External Height: 90 mm
 - External Width: 122 mm
 - External Dimensions: 187 x 122 x 90 mm
 - IP Rating: IP65
 - Colour: Grey
 - Lid Colour: Grey



1972025 Polycarbonate

RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Polycarbonate
 - External Length: 187 mm
 - External Height: 90 mm
 - External Width: 122 mm
 - External Dimensions: 187 x 122 x 90 mm
 - IP Rating: IP65
 - Colour: Grey
 - Lid Colour: Transparent



1972026 Polycarbonate

RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Polycarbonate
 - External Length: 201 mm
 - External Height: 98 mm
 - External Width: 163 mm
 - External Dimensions: 201 x 163 x 98 mm
 - IP Rating: IP65
 - Colour: Grey
 - Lid Colour: Grey



1972027 Polycarbonate

RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Polycarbonate
 - External Length: 201 mm
 - External Height: 98 mm
 - External Width: 163 mm
 - External Dimensions: 201 x 163 x 98 mm
 - IP Rating: IP65
 - Colour: Grey
 - Lid Colour: Transparent



1972028 Polycarbonate

RS PRO WHITE POLYCARBONATE GENERAL PURPOSE ENCLOSURE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Polycarbonate
 - Range: Z8
 - External Length: 45.9 mm
 - External Height: 22 mm
 - External Width: 35.2 mm
 - External Dimensions: 45.9 x 35.2 x 22 mm
 - IP Rating: IP52
 - Colour: White



2006660 Polycarbonate

RS PRO LIGHT GREY POLYCARBONATE ENCLOSURE, IP53,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Polycarbonate
 - Range: Z7
 - External Length: 178.9 mm
 - External Height: 48.8 mm
 - External Width: 102 mm
 - External Dimensions: 178.85 x 102 x 48.8 mm
 - IP Rating: IP53
 - Colour: Light Grey



2006698 Polycarbonate

PLASTIC ENCLOSURE Z73 LIGHTGRAY ABS

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Polycarbonate
 - Range: Z7
 - External Length: 109.2 mm
 - External Height: 31.9 mm
 - External Width: 79.2 mm
 - External Dimensions: 109.2 x 79.2 x 31.9 mm
 - IP Rating: IP65
 - Colour: Light Grey



2006700 Polycarbonate

RS PRO LIGHT GREY POLYCARBONATE ENCLOSURE, IP53,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Polycarbonate
 - Range: Z7
 - External Length: 154 mm
 - External Height: 42.5 mm
 - External Width: 84.5 mm
 - External Dimensions: 154 x 84.5 x 42.5 mm
 - IP Rating: IP53
 - Colour: Light Grey



2006704 Polycarbonate

RS PRO LIGHT GREY POLYCARBONATE ENCLOSURE, IP54,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Polycarbonate
 - Range: Z7
 - External Length: 90 mm
 - External Height: 38 mm
 - External Width: 80 mm
 - External Dimensions: 90 x 80 x 38 mm
 - IP Rating: IP54
 - Colour: Light Grey



2006705 Polycarbonate

PLASTIC ENCLOSURE Z112B LIGHTGRAY ABS

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Polycarbonate
 - Range: Z11
 - External Length: 185.5 mm
 - External Height: 80 mm
 - External Width: 136 mm
 - External Dimensions: 185.5 x 136 x 80 mm
 - IP Rating: IP53
 - Colour: Light Grey



2006718 Polycarbonate

RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Polycarbonate
 - External Length: 52 mm
 - Range: 5U2
 - External Height: 35 mm
 - External Width: 50 mm
 - External Dimensions: 50 x 52 x 35 mm
 - IP Rating: IP66
 - Colour: Grey



2010129 Polycarbonate

RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Polycarbonate
 - Range: 5U2
 - External Length: 65 mm
 - External Height: 35 mm
 - External Width: 50 mm
 - External Dimensions: 50 x 65 x 35 mm
 - IP Rating: IP66
 - Colour: Grey



2010130 Polycarbonate

RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Polycarbonate
 - External Length: 98 mm
 - Range: 5U2
 - External Height: 36.4 mm
 - External Width: 64 mm
 - External Dimensions: 64 x 98 x 36.4 mm
 - IP Rating: IP66
 - Colour: Grey



2010131 Polycarbonate

RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Polycarbonate
 - External Length: 82 mm
 - Range: 5U2
 - External Height: 55 mm
 - External Width: 80 mm
 - External Dimensions: 80 x 82 x 55 mm
 - IP Rating: IP66
 - Colour: Grey



2010132 Polycarbonate

RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Polycarbonate
 - External Length: 160 mm
 - Range: 5U2
 - External Height: 90 mm
 - External Width: 120 mm
 - External Dimensions: 120 x 160 x 90 mm
 - IP Rating: IP66
 - Colour: Grey



2010156 Polycarbonate

RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Polycarbonate
 - External Length: 160 mm
 - Range: 5U2
 - External Height: 75 mm
 - External Width: 120 mm
 - External Dimensions: 120 x 160 x 75 mm
 - IP Rating: IP66
 - Colour: Grey



2010157 Polycarbonate

RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Polycarbonate
 - External Length: 160 mm
 - Range: 5U2
 - External Height: 90 mm
 - External Width: 120 mm
 - External Dimensions: 120 x 160 x 90 mm
 - IP Rating: IP66
 - Colour: Grey



2010158 Polycarbonate

RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Polycarbonate
 - External Length: 250 mm
 - Range: 5U2
 - External Height: 90 mm
 - External Width: 160 mm
 - External Dimensions: 160 x 250 x 90 mm
 - IP Rating: IP66
 - Colour: Grey



2010159 Polycarbonate

RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Polycarbonate
 - External Length: 240.3 mm
 - Range: 5U2
 - External Height: 90 mm
 - External Width: 160.3 mm
 - External Dimensions: 160 x 240.3 x 90 mm
 - IP Rating: IP66
 - Colour: Grey



2010160 Polycarbonate

RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Polycarbonate
 - External Length: 240.3 mm
 - Range: 5U2
 - External Height: 90 mm
 - External Width: 160.3 mm
 - External Dimensions: 160.3 x 240.3 x 90 mm
 - IP Rating: IP66
 - Colour: Grey



2010161 Polycarbonate

RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Polycarbonate
 - External Length: 250 mm
 - Range: 5U2
 - External Height: 119 mm
 - External Width: 160 mm
 - External Dimensions: 160 x 250 x 119 mm
 - IP Rating: IP66
 - Colour: Grey



2010162 Polycarbonate

RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Polycarbonate
 - External Length: 240.5 mm
 - Range: 5U2
 - External Height: 100.5 mm
 - External Width: 120 mm
 - External Dimensions: 120 x 240.5 x 100.5 mm
 - IP Rating: IP66
 - Colour: Grey



2010163 Polycarbonate

RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Polycarbonate
 - External Length: 240.3 mm
 - Range: 5U2
 - External Height: 120 mm
 - External Width: 160.3 mm
 - External Dimensions: 160 x 240.3 x 120 mm
 - IP Rating: IP66
 - Colour: Grey



2010164 Polycarbonate

RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Polycarbonate
 - External Length: 160 mm
 - Range: 5U2
 - External Height: 140 mm
 - External Width: 120 mm
 - External Dimensions: 120 x 160 x 140 mm
 - IP Rating: IP66
 - Colour: Grey



2010165 Polycarbonate

RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Polycarbonate
 - External Length: 360 mm
 - Range: 5U2
 - External Height: 100 mm
 - External Width: 160 mm
 - External Dimensions: 160 x 360 x 100 mm
 - IP Rating: IP66
 - Colour: Grey



2010167 Polycarbonate

RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Polycarbonate
 - External Length: 300 mm
 - Range: 5U2
 - External Height: 85 mm
 - External Width: 230 mm
 - External Dimensions: 230 x 300 x 85 mm
 - IP Rating: IP66
 - Colour: Grey



2010168 Polycarbonate

RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Polycarbonate
 - External Length: 300 mm
 - Range: 5U2
 - External Height: 85 mm
 - External Width: 230 mm
 - External Dimensions: 230 x 300 x 85 mm
 - IP Rating: IP66
 - Colour: Grey



2010169 Polycarbonate

RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Polycarbonate
 - External Length: 300 mm
 - Range: 5U2
 - External Height: 110 mm
 - External Width: 230 mm
 - External Dimensions: 230 x 300 x 110 mm
 - IP Rating: IP66
 - Colour: Grey



2010170 Polycarbonate

RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Polycarbonate
 - External Length: 360 mm
 - Range: 5U2
 - External Height: 149.5 mm
 - External Width: 200 mm
 - External Dimensions: 200 x 360 x 149.5 mm
 - IP Rating: IP66
 - Colour: Grey



2010171 Polycarbonate

RS PRO GREY ABS GENERAL PURPOSE ENCLOSURE, IP66, IK07,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 52 mm
 - Range: 5U3
 - External Height: 35 mm
 - External Width: 50 mm
 - External Dimensions: 50 x 52 x 35 mm
 - IP Rating: IP66
 - Colour: Grey



2010172 ABS

RS PRO GREY ABS GENERAL PURPOSE ENCLOSURE, IP66, IK07,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 200 mm
 - Range: 5U3
 - External Height: 90 mm
 - External Width: 120 mm
 - External Dimensions: 120 x 200 x 90 mm
 - IP Rating: IP66
 - Colour: Grey



2010190 ABS

RS PRO GREY ABS GENERAL PURPOSE ENCLOSURE, IP66, IK07,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 160 mm
 - Range: 5U3
 - External Height: 90 mm
 - External Width: 120 mm
 - External Dimensions: 120 x 160 x 90 mm
 - IP Rating: IP66
 - Colour: Grey



2010191 ABS

RS PRO GREY ABS GENERAL PURPOSE ENCLOSURE, IP66, IK07,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 160 mm
 - Range: 5U3
 - External Height: 75 mm
 - External Width: 120 mm
 - External Dimensions: 120 x 160 x 75 mm
 - IP Rating: IP66
 - Colour: Grey



2010192 ABS

RS PRO GREY ABS GENERAL PURPOSE ENCLOSURE, IP66, IK07,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 250 mm
 - Range: 5U3
 - External Height: 90 mm
 - External Width: 160 mm
 - External Dimensions: 160 x 250 x 90 mm
 - IP Rating: IP66
 - Colour: Grey



2010193 ABS

RS PRO GREY ABS GENERAL PURPOSE ENCLOSURE, IP66, IK07,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 240.3 mm
 - Range: 5U3
 - External Height: 90 mm
 - External Width: 160.3 mm
 - External Dimensions: 160 x 240.3 x 90 mm
 - IP Rating: IP66
 - Colour: Grey



2010195 ABS

RS PRO GREY ABS GENERAL PURPOSE ENCLOSURE, IP66, IK07,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 250 mm
 - Range: 5U3
 - External Height: 119 mm
 - External Width: 160 mm
 - External Dimensions: 160 x 250 x 119 mm
 - IP Rating: IP66
 - Colour: Grey



2010196 ABS

RS PRO GREY ABS GENERAL PURPOSE ENCLOSURE, IP66, IK07,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 240.5 mm
 - Range: 5U3
 - External Height: 100.5 mm
 - External Width: 120 mm
 - External Dimensions: 120 x 240.5 x 100.5 mm
 - IP Rating: IP66
 - Colour: Grey



2010197 ABS

RS PRO GREY ABS GENERAL PURPOSE ENCLOSURE, IP66, IK07,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 240.3 mm
 - Range: 5U3
 - External Height: 120 mm
 - External Width: 160.3 mm
 - External Dimensions: 160.3 x 240.3 x 120 mm
 - IP Rating: IP66
 - Colour: Grey



2010198 ABS

RS PRO GREY ABS GENERAL PURPOSE ENCLOSURE, IP66, IK07,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 234 mm
 - Range: 5U3
 - External Height: 100 mm
 - External Width: 150 mm
 - External Dimensions: 150 x 234 x 100 mm
 - IP Rating: IP66
 - Colour: Grey



2010199 ABS

RS PRO GREY ABS GENERAL PURPOSE ENCLOSURE, IP66, IK07,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 340 mm
 - Range: 5U3
 - External Height: 120 mm
 - External Width: 150 mm
 - External Dimensions: 150 x 340 x 120 mm
 - IP Rating: IP66
 - Colour: Grey



2010200 ABS

RS PRO GREY ABS GENERAL PURPOSE ENCLOSURE, IP66, IK07,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 160 mm
 - Range: 5U3
 - External Height: 140 mm
 - External Width: 120 mm
 - External Dimensions: 120 x 160 x 140 mm
 - IP Rating: IP66
 - Colour: Grey



2010202 ABS

RS PRO GREY ABS GENERAL PURPOSE ENCLOSURE, IP66, IK07,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 250 mm
 - Range: 5U3
 - External Height: 150 mm
 - External Width: 160 mm
 - External Dimensions: 160 x 250 x 150 mm
 - IP Rating: IP66
 - Colour: Grey



2010203 ABS

RS PRO GREY ABS GENERAL PURPOSE ENCLOSURE, IP66, IK07,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 360 mm
 - Range: 5U3
 - External Height: 100 mm
 - External Width: 160 mm
 - External Dimensions: 160 x 360 x 100 mm
 - IP Rating: IP66
 - Colour: Grey



2010204 ABS

RS PRO GREY ABS GENERAL PURPOSE ENCLOSURE, IP66, IK07,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 300 mm
 - Range: 5U3
 - External Height: 85 mm
 - External Width: 230 mm
 - External Dimensions: 230 x 300 x 85 mm
 - IP Rating: IP66
 - Colour: Grey



2010205 ABS

RS PRO GREY ABS GENERAL PURPOSE ENCLOSURE, IP66, IK07,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 300 mm
 - Range: 5U3
 - External Height: 110 mm
 - External Width: 230 mm
 - External Dimensions: 230 x 300 x 110 mm
 - IP Rating: IP66
 - Colour: Grey



2010206 ABS

RS PRO GREY ABS GENERAL PURPOSE ENCLOSURE, IP66, IK07,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 360 mm
 - Range: 5U3
 - External Height: 149.5 mm
 - External Width: 200 mm
 - External Dimensions: 200 x 360 x 149.5 mm
 - IP Rating: IP66
 - Colour: Grey



2010207 ABS

WHITE ABS GENERAL PURPOSE ENCLOSURE, IP20, IK06, WHITE LID,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 100 mm
 - External Height: 35.3 mm
 - External Width: 100 mm
 - External Dimensions: 100 x 100 x 35.3 mm
 - IP Rating: IP20
 - Colour: White
 - Lid Colour: White



2069055 ABS

RS PRO LIGHT GREY POLYCARBONATE ENCLOSURE, IP65,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Polycarbonate
 - External Length: 121.4 mm
 - External Height: 45.2 mm
 - External Width: 81.6 mm
 - External Dimensions: 121.4 x 81.6 x 45.2 mm
 - IP Rating: IP65
 - Colour: Light Grey
 - Lid Colour: Light Grey



2069086 Polycarbonate

RS PRO LIGHT GREY ABS, POLYCARBONATE ENCLOSURE, IP65,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS, Polycarbonate
 - External Length: 121.4 mm
 - External Height: 45.2 mm
 - External Width: 81.6 mm
 - External Dimensions: 121.4 x 81.6 x 45.2 mm
 - IP Rating: IP65
 - Colour: Light Grey
 - Lid Colour: Transparent



2069087 ABS,

RS PRO LIGHT GREY ABS ENCLOSURE, IP65, LIGHT GREY LID,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 121.4 mm
 - External Height: 60.2 mm
 - External Width: 80 mm
 - External Dimensions: 120 x 80 x 60.2 mm
 - IP Rating: IP65
 - Colour: Light Grey
 - Lid Colour: Light Grey



2069090 ABS

LIGHT GREY ABS, POLYCARBONATE ENCLOSURE, IP65, TRANSPARENT LID,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS, Polycarbonate
 - External Length: 121.4 mm
 - External Height: 60.2 mm
 - External Width: 81.6 mm
 - External Dimensions: 121.4 x 81.6 x 60.2 mm
 - IP Rating: IP65
 - Colour: Light Grey
 - Lid Colour: Transparent



2069092 ABS,

RS PRO LIGHT GREY ABS ENCLOSURE, IP65, FLANGED, LIGHT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 121.4 mm
 - External Height: 60.2 mm
 - External Width: 81.6 mm
 - External Dimensions: 121.4 x 81.6 x 60.2 mm
 - IP Rating: IP65
 - Colour: Light Grey
 - Lid Colour: Light Grey



2069094 ABS

LIGHT GREY POLYCARBONATE ENCLOSURE, IP65, FLANGED, LIGHT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Polycarbonate
 - External Length: 121.4 mm
 - External Height: 60.2 mm
 - External Width: 81.6 mm
 - External Dimensions: 121.4 x 81.6 x 60.2 mm
 - IP Rating: IP65
 - Colour: Light Grey
 - Lid Colour: Light Grey



2069096 Polycarbonate

RS PRO LIGHT GREY ABS, POLYCARBONATE ENCLOSURE, IP65,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS, Polycarbonate
 - External Length: 121.4 mm
 - External Height: 60.2 mm
 - External Width: 81.6 mm
 - External Dimensions: 121.4 x 81.6 x 60.2 mm
 - IP Rating: IP65
 - Colour: Light Grey
 - Lid Colour: Transparent



2069097 ABS,

RS PRO LIGHT GREY POLYCARBONATE ENCLOSURE, IP65,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Polycarbonate
 - External Length: 121.4 mm
 - External Height: 60.2 mm
 - External Width: 81.6 mm
 - External Dimensions: 121.4 x 81.6 x 60.2 mm
 - IP Rating: IP65
 - Colour: Light Grey
 - Lid Colour: Transparent



2069098 Polycarbonate

LIGHT GREY ABS ENCLOSURE, IP65, LIGHT GREY LID, 120 X 80 X 75.2MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 120 mm
 - External Height: 75.2 mm
 - External Width: 80 mm
 - External Dimensions: 120 x 80 x 75.2 mm
 - IP Rating: IP65
 - Colour: Light Grey
 - Lid Colour: Light Grey



2069099 ABS

LIGHT GREY ABS, POLYCARBONATE ENCLOSURE, IP65, TRANSPARENT LID,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS, Polycarbonate
 - External Length: 120 mm
 - External Height: 75.2 mm
 - External Width: 80 mm
 - External Dimensions: 120 x 80 x 75.2 mm
 - IP Rating: IP65
 - Colour: Light Grey
 - Lid Colour: Transparent



2069101 ABS,

LIGHT GREY POLYCARBONATE ENCLOSURE, IP65, 191.3 X 240 X

- ขนาดบรรจุภัณฑ์: **1 x SET**
- Body Material: Polycarbonate
 - External Length: 191.3 mm
 - External Height: 105.7 mm
 - External Width: 240 mm
 - External Dimensions: 191.3 x 240 x 105.7 mm
 - IP Rating: IP65
 - Colour: Light Grey
 - Flanged: No



2069105 Polycarbonate

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP66, IK09, GREY LID, 91

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 91 mm
 - External Height: 120 mm
 - External Width: 220 mm
 - External Dimensions: 91 x 220 x 120 mm
 - IP Rating: IP66
 - Colour: Grey
 - Lid Colour: Grey



2131641 Die Cast

RS PRO BLACK FIBREGLASS REINFORCED POLYESTER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Fibreglass Reinforced Polyester
 - External Length: 91 mm
 - External Height: 120 mm
 - External Width: 122 mm
 - External Dimensions: 91 x 122 x 120 mm
 - IP Rating: IP66
 - Colour: Black
 - Lid Colour: Black



2131649 Fibreglass

RS PRO BLACK FIBREGLASS REINFORCED POLYESTER


- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Fibreglass Reinforced Polyester
 - External Length: 91 mm
 - External Height: 160 mm
 - External Width: 160 mm
 - External Dimensions: 91 x 160 x 160 mm
 - IP Rating: IP66
 - Colour: Black
 - Lid Colour: Black



2131651 Fibreglass

ROSE STAINLESS STEEL RMS ENCLOSURES WITH

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: 304 Stainless Steel
 - External Height: 200 mm
 - External Width: 200 mm
 - IP Rating: IP66, IP69
 - Colour: Steel
 - Transparent Door: No



2134044 304 Stainless

ROSE STAINLESS STEEL RMS ENCLOSURES WITH

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: 304 Stainless Steel
 - External Height: 600 mm
 - External Width: 300 mm
 - IP Rating: IP66, IP69
 - Colour: Steel
 - Transparent Door: No



2134081 304 Stainless

ROSE STAINLESS STEEL RMS ENCLOSURES WITH

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: 304 Stainless Steel
 - External Height: 500 mm
 - External Width: 400 mm
 - IP Rating: IP66, IP69
 - Colour: Steel
 - Transparent Door: No



2134082 304 Stainless

ROSE STAINLESS STEEL RMS ENCLOSURES WITH


- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: 304 Stainless Steel
 - External Height: 500 mm
 - External Width: 500 mm
 - IP Rating: IP66, IP69
 - Colour: Steel
 - Transparent Door: No



2134087 304 Stainless

ROSE STAINLESS STEEL RMS ENCLOSURES WITH

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: 304 Stainless Steel
 - External Height: 200 mm
 - External Width: 200 mm
 - IP Rating: IP66, IP69
 - Colour: Steel
 - Transparent Door: No



2134089 304 Stainless

ROSE STAINLESS STEEL RMS ENCLOSURES WITH

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: 304 Stainless Steel
 - External Height: 300 mm
 - External Width: 500 mm
 - IP Rating: IP66, IP69
 - Colour: Steel
 - Transparent Door: No



2134090 304 Stainless

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP65, SILVER LID, 71 X 110

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 71 mm
 - External Height: 135 mm
 - External Width: 110 mm
 - External Dimensions: 71 x 110 x 135 mm
 - IP Rating: IP65
 - Colour: Silver
 - Lid Colour: Silver



2290334 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP65, SILVER LID, 81 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 81 mm
 - External Height: 160 mm
 - External Width: 135 mm
 - External Dimensions: 81 x 135 x 160 mm
 - IP Rating: IP65
 - Colour: Silver
 - Lid Colour: Silver



2290362 Die Cast

RS PRO BLACK ABS ENCLOSURE, BLACK LID, 88.9 X 63.5 X 32.39MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 88.9 mm
 - External Height: 32.4 mm
 - External Width: 63.5 mm
 - External Dimensions: 88.9 x 63.5 x 32.39 mm
 - Colour: Black
 - Lid Colour: Black
 - Flanged: No



2374331 ABS

RS PRO BLACK ABS ENCLOSURE, FLANGED, BLACK LID, 88 X 63 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 111.8 mm
 - External Height: 28.6 mm
 - External Width: 63.5 mm
 - External Dimensions: 88 x 63 x 29 mm
 - Colour: Black
 - Lid Colour: Black
 - Flanged: Yes



2374347 ABS

RS PRO ABS ENCLOSURE, 60 X 100 X 150MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 150 mm
 - External Height: 60 mm
 - External Width: 100 mm
 - External Dimensions: 60 x 100 x 150 mm



2384026 ABS

RS PRO POLYCARBONATE ENCLOSURE, 75 X 100 X 150MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Polycarbonate
 - External Length: 150 mm
 - External Height: 75 mm
 - External Width: 100 mm
 - External Dimensions: 75 x 100 x 150 mm



2384034 Polycarbonate

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP66, GREY LID, 127 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 127 mm
 - External Height: 90 mm
 - External Width: 125 mm
 - External Dimensions: 127 x 125 x 90 mm
 - IP Rating: IP66
 - Colour: Grey
 - Lid Colour: Grey



2433682 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP66, GREY LID, 166 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 166 mm
 - External Height: 100 mm
 - External Width: 166 mm
 - External Dimensions: 166 x 166 x 100 mm
 - IP Rating: IP66
 - Colour: Grey
 - Lid Colour: Grey



2433711 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP65, SILVER LID, 73 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 73 mm
 - External Height: 102 mm
 - External Width: 102 mm
 - External Dimensions: 73 x 102 x 102 mm
 - IP Rating: IP65
 - Colour: Silver
 - Lid Colour: Silver



2821102 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP65, GREY LID, 87 X 87

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 87 mm
 - External Height: 61 mm
 - External Width: 87 mm
 - External Dimensions: 87 x 87 x 61 mm
 - IP Rating: IP65
 - Colour: Grey
 - Lid Colour: Grey



2821152 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP65, GREY LID, 102 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 102 mm
 - External Height: 61 mm
 - External Width: 102 mm
 - External Dimensions: 102 x 102 x 61 mm
 - IP Rating: IP65
 - Colour: Grey
 - Lid Colour: Grey



2821168 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP65, GREY LID, 102 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 102 mm
 - External Height: 81 mm
 - External Width: 102 mm
 - External Dimensions: 102 x 102 x 81 mm
 - IP Rating: IP65
 - Colour: Grey
 - Lid Colour: Grey



2821180 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP65, GREY LID, 122 X 75

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 122 mm
 - External Height: 61 mm
 - External Width: 75 mm
 - External Dimensions: 122 x 75 x 61 mm
 - IP Rating: IP65
 - Colour: Grey
 - Lid Colour: Grey



2821196 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP65, GREY LID, 122 X 75

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 122 mm
 - External Height: 75 mm
 - External Width: 75 mm
 - External Dimensions: 122 x 75 x 75 mm
 - IP Rating: IP65
 - Colour: Grey
 - Lid Colour: Grey



2821203 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP65, GREY LID, 202 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 202 mm
 - External Height: 61 mm
 - External Width: 102 mm
 - External Dimensions: 202 x 102 x 61 mm
 - IP Rating: IP65
 - Colour: Grey
 - Lid Colour: Grey



2821219 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP65, GREY LID, 202 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 202 mm
 - External Height: 81 mm
 - External Width: 102 mm
 - External Dimensions: 202 x 102 x 81 mm
 - IP Rating: IP65
 - Colour: Grey
 - Lid Colour: Grey



2821225 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP65, GREY LID, 252 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 252 mm
 - External Height: 61 mm
 - External Width: 87 mm
 - External Dimensions: 252 x 87 x 61 mm
 - IP Rating: IP65
 - Colour: Grey
 - Lid Colour: Grey



2821247 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP65, GREY LID, 252 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 252 mm
 - External Height: 75 mm
 - External Width: 87 mm
 - External Dimensions: 252 x 87 x 75 mm
 - IP Rating: IP65
 - Colour: Grey
 - Lid Colour: Grey



2821253 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP65, GREY LID, 262 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 262 mm
 - External Height: 91 mm
 - External Width: 127 mm
 - External Dimensions: 262 x 127 x 91 mm
 - IP Rating: IP65
 - Colour: Grey
 - Lid Colour: Grey



2821269 Die Cast

RS PRO BLACK ABS ENCLOSURE, BLACK LID, 177.8 X 127 X 76.2MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 177.8 mm
 - External Height: 76.2 mm
 - External Width: 127 mm
 - External Dimensions: 177.8 x 127 x 76.2 mm
 - Colour: Black
 - Lid Colour: Black
 - Flanged: No



2876433 ABS

RS PRO BLACK ABS ENCLOSURE, FLANGED, BLACK LID, 200.86 X 127 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 200.9 mm
 - External Height: 76.2 mm
 - External Width: 127 mm
 - External Dimensions: 200.86 x 127 x 76.2 mm
 - Colour: Black
 - Lid Colour: Black
 - Flanged: Yes



2876483 ABS

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP65, GREY LID, 152 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 152 mm
 - External Height: 81 mm
 - External Width: 102 mm
 - External Dimensions: 152 x 102 x 81 mm
 - IP Rating: IP65
 - Colour: Grey
 - Lid Colour: Grey



4349882 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP65, GREY LID, 130 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 130 mm
 - External Height: 91 mm
 - External Width: 130 mm
 - External Dimensions: 130 x 130 x 91 mm
 - IP Rating: IP65
 - Colour: Grey
 - Lid Colour: Grey



4349898 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP66, FLANGED, GREY

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 202 mm
 - External Height: 54.9 mm
 - External Width: 120.8 mm
 - External Dimensions: 202 x 120.8 x 54.9 mm
 - IP Rating: IP66
 - Colour: Grey
 - Lid Colour: Grey



4799984 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, SILVER LID, 222.1 X 145.9

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 222.1 mm
 - External Height: 55.9 mm
 - External Width: 145.9 mm
 - External Dimensions: 222.1 x 145.9 x 55.9 mm
 - Colour: Silver
 - Lid Colour: Silver
 - Flanged: No



5173260 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, SILVER LID, 114.5 X 63.6

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 114.5 mm
 - External Height: 30.3 mm
 - External Width: 63.6 mm
 - External Dimensions: 114.5 x 63.6 x 30.3 mm
 - Colour: Silver
 - Lid Colour: Silver
 - Flanged: No



5173276 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, SILVER LID, 114.4 X 63.7

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 114.4 mm
 - External Height: 55.1 mm
 - External Width: 63.7 mm
 - External Dimensions: 114.4 x 63.7 x 55.1 mm
 - Colour: Silver
 - Lid Colour: Silver
 - Flanged: No



5173298 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, SILVER LID, 275 X 175 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 275 mm
 - External Height: 65.5 mm
 - External Width: 175 mm
 - External Dimensions: 275 x 175 x 65.5 mm
 - Colour: Silver
 - Lid Colour: Silver
 - Flanged: No

**5173305** Die Cast**RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, SILVER LID, 250 X 250 X**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 250 mm
 - External Height: 100 mm
 - External Width: 250 mm
 - External Dimensions: 250 x 250 x 100 mm
 - Colour: Silver
 - Lid Colour: Silver
 - Flanged: No

**5173311** Die Cast**RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, SILVER LID, 119.9 X 100 X**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 119.9 mm
 - External Height: 35.7 mm
 - External Width: 100 mm
 - External Dimensions: 119.9 x 100 x 35.7 mm
 - Colour: Silver
 - Lid Colour: Silver
 - Flanged: No

**5173327** Die Cast**RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, SILVER LID, 114.7 X 89.7**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 114.7 mm
 - External Height: 55.1 mm
 - External Width: 89.7 mm
 - External Dimensions: 114.7 x 89.7 x 55.1 mm
 - Colour: Silver
 - Lid Colour: Silver
 - Flanged: No

**5173333** Die Cast**RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, SILVER LID, 171.9 X 120.9**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 171.9 mm
 - External Height: 55 mm
 - External Width: 120.9 mm
 - External Dimensions: 171.9 x 120.9 x 55 mm
 - Colour: Silver
 - Lid Colour: Silver
 - Flanged: No

**5173355** Die Cast**RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, SILVER LID, 139.1 X 101.5**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 139.1 mm
 - External Height: 76.7 mm
 - External Width: 101.5 mm
 - External Dimensions: 139.1 x 101.5 x 76.7 mm
 - Colour: Silver
 - Lid Colour: Silver
 - Flanged: No

**5173361** Die Cast**RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, SILVER LID, 79.9 X 54.9 X**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 79.9 mm
 - External Height: 25.5 mm
 - External Width: 54.9 mm
 - External Dimensions: 79.9 x 54.9 x 25.5 mm
 - Colour: Silver
 - Lid Colour: Silver
 - Flanged: No

**5173377** Die Cast**RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, SILVER LID, 165.8 X 127.3**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 165.8 mm
 - External Height: 76.3 mm
 - External Width: 127.3 mm
 - External Dimensions: 165.8 x 127.3 x 76.3 mm
 - Colour: Silver
 - Lid Colour: Silver
 - Flanged: No

**5173383** Die Cast**RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, SILVER LID, 60 X 54.9 X**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 60 mm
 - External Height: 30 mm
 - External Width: 54.9 mm
 - External Dimensions: 60 x 54.9 x 30 mm
 - Colour: Silver
 - Lid Colour: Silver
 - Flanged: No

**5173399** Die Cast**RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, SILVER LID, 171.9 X 120.9**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 171.9 mm
 - External Height: 106 mm
 - External Width: 120.9 mm
 - External Dimensions: 171.9 x 120.9 x 106 mm
 - Colour: Silver
 - Lid Colour: Silver
 - Flanged: No

**5173412** Die Cast**RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP66, SILVER LID, 250 X**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 250 mm
 - External Height: 100 mm
 - External Width: 250 mm
 - External Dimensions: 250 x 250 x 100 mm
 - IP Rating: IP66
 - Colour: Silver
 - Lid Colour: Silver
 - Flanged: No

**5173428** Die Cast**RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP66, SILVER LID, 171.9 X**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 171.9 mm
 - External Height: 106 mm
 - External Width: 120.9 mm
 - External Dimensions: 171.9 x 120.9 x 106 mm
 - IP Rating: IP66
 - Colour: Silver
 - Lid Colour: Silver
 - Flanged: No

**5173434** Die Cast**RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP66, SILVER LID, 275 X**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 275 mm
 - External Height: 65.5 mm
 - External Width: 175 mm
 - External Dimensions: 275 x 175 x 65.5 mm
 - IP Rating: IP66
 - Colour: Silver
 - Lid Colour: Silver

**5173440** Die Cast**RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP66, SILVER LID, 139.1 X**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 139.1 mm
 - External Height: 76.7 mm
 - External Width: 101.5 mm
 - External Dimensions: 139.1 x 101.5 x 76.7 mm
 - IP Rating: IP66
 - Colour: Silver
 - Lid Colour: Silver

**5173456** Die Cast**RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP66, SILVER LID, 114.7 X**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 114.7 mm
 - External Height: 55.1 mm
 - External Width: 89.7 mm
 - External Dimensions: 114.7 x 89.7 x 55.1 mm
 - IP Rating: IP66
 - Colour: Silver
 - Lid Colour: Silver

**5173462** Die Cast**RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP66, SILVER LID, 171.9 X**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 171.9 mm
 - External Height: 55 mm
 - External Width: 120.9 mm
 - External Dimensions: 171.9 x 120.9 x 55 mm
 - IP Rating: IP66
 - Colour: Silver
 - Lid Colour: Silver

**5173478** Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP66, SILVER LID, 114.4 X

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: Die Cast Aluminium
 - External Length: 114.4 mm
 - External Height: 55.1 mm
 - External Width: 63.7 mm
 - External Dimensions: 114.4 x 63.7 x 55.1 mm
 - IP Rating: IP66
 - Colour: Silver
 - Lid Colour: Silver



5173484 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP66, SILVER LID, 165.8 X

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: Die Cast Aluminium
 - External Length: 165.8 mm
 - External Height: 76.3 mm
 - External Width: 127.3 mm
 - External Dimensions: 165.8 x 127.3 x 76.3 mm
 - IP Rating: IP66
 - Colour: Silver
 - Lid Colour: Silver



5173490 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP66, SILVER LID, 60 X

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: Die Cast Aluminium
 - External Length: 60 mm
 - External Height: 30 mm
 - External Width: 54.9 mm
 - External Dimensions: 60 x 54.9 x 30 mm
 - IP Rating: IP66
 - Colour: Silver
 - Lid Colour: Silver



5173513 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP66, SILVER LID, 119.9 X

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: Die Cast Aluminium
 - External Length: 119.9 mm
 - External Height: 35.7 mm
 - External Width: 100 mm
 - External Dimensions: 119.9 x 100 x 35.7 mm
 - IP Rating: IP66
 - Colour: Silver
 - Lid Colour: Silver



5173529 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, GREY LID, 275 X 175 X

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: Die Cast Aluminium
 - External Length: 275 mm
 - External Height: 65.5 mm
 - External Width: 175 mm
 - External Dimensions: 275 x 175 x 65.5 mm
 - Colour: Grey
 - Lid Colour: Grey
 - Flanged: No



5173541 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, GREY LID, 250 X 250 X

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: Die Cast Aluminium
 - External Length: 250 mm
 - External Height: 100 mm
 - External Width: 250 mm
 - External Dimensions: 250 x 250 x 100 mm
 - Colour: Grey
 - Lid Colour: Grey
 - Flanged: No



5173557 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, GREY LID, 222.1 X 145.9

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: Die Cast Aluminium
 - External Length: 222.1 mm
 - External Height: 55.9 mm
 - External Width: 145.9 mm
 - External Dimensions: 222.1 x 145.9 x 55.9 mm
 - Colour: Grey
 - Lid Colour: Grey
 - Flanged: No



5173579 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, GREY LID, 114.5 X 63.6 X

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: Die Cast Aluminium
 - External Length: 114.5 mm
 - External Height: 30.3 mm
 - External Width: 63.6 mm
 - External Dimensions: 114.5 x 63.6 x 30.3 mm
 - Colour: Grey
 - Lid Colour: Grey
 - Flanged: No



5173664 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, GREY LID, 60 X 54.9 X

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: Die Cast Aluminium
 - External Length: 60 mm
 - External Height: 30 mm
 - External Width: 54.9 mm
 - External Dimensions: 60 x 54.9 x 30 mm
 - Colour: Grey
 - Lid Colour: Grey
 - Flanged: No



5173670 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, FLANGED, SILVER LID,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: Die Cast Aluminium
 - External Length: 113.9 mm
 - External Height: 30 mm
 - External Width: 35.1 mm
 - External Dimensions: 113.9 x 35.1 x 30 mm
 - Colour: Silver
 - Lid Colour: Silver
 - Flanged: Yes



5173709 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, FLANGED, SILVER LID,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: Die Cast Aluminium
 - External Length: 139.7 mm
 - External Height: 30 mm
 - External Width: 63.8 mm
 - External Dimensions: 139.7 x 63.8 x 30 mm
 - Colour: Silver
 - Lid Colour: Silver
 - Flanged: Yes



5173715 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, FLANGED, SILVER LID,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: Die Cast Aluminium
 - External Length: 139.8 mm
 - External Height: 55.2 mm
 - External Width: 89.7 mm
 - External Dimensions: 139.8 x 89.7 x 55.2 mm
 - Colour: Silver
 - Lid Colour: Silver
 - Flanged: Yes



5173721 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, FLANGED, SILVER LID,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: Die Cast Aluminium
 - External Length: 139.6 mm
 - External Height: 55 mm
 - External Width: 63.8 mm
 - External Dimensions: 139.6 x 63.8 x 55 mm
 - Colour: Silver
 - Lid Colour: Silver
 - Flanged: Yes



5173737 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, FLANGED, SILVER LID,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: Die Cast Aluminium
 - External Length: 149.8 mm
 - External Height: 35.6 mm
 - External Width: 100.2 mm
 - External Dimensions: 149.8 x 100.2 x 35.6 mm
 - Colour: Silver
 - Lid Colour: Silver
 - Flanged: Yes



5173743 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, FLANGED, SILVER LID,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: Die Cast Aluminium
 - External Length: 168.7 mm
 - External Height: 76.5 mm
 - External Width: 101.6 mm
 - External Dimensions: 168.7 x 101.6 x 76.5 mm
 - Colour: Silver
 - Lid Colour: Silver
 - Flanged: Yes



5173759 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, FLANGED, SILVER LID,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: Die Cast Aluminium
 - External Length: 194.8 mm
 - External Height: 76.3 mm
 - External Width: 127.4 mm
 - External Dimensions: 194.8 x 127.4 x 76.3 mm
 - Colour: Silver
 - Lid Colour: Silver
 - Flanged: Yes



5173765 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, FLANGED, SILVER LID,**ขนาดบรรจุภัณฑ์: 1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 201.7 mm
- External Height: 55.3 mm
- External Width: 121.2 mm
- External Dimensions: 201.7 x 121.2 x 55.3 mm
- Colour: Silver
- Lid Colour: Silver
- Flanged: Yes

**5173771** Die Cast**RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, FLANGED, SILVER LID,****ขนาดบรรจุภัณฑ์: 1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 201.7 mm
- External Height: 105.4 mm
- External Width: 121.2 mm
- External Dimensions: 201.7 x 121.2 x 105.4 mm
- Colour: Silver
- Lid Colour: Silver
- Flanged: Yes

**5173793** Die Cast**RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, GREY LID, 114.7 X 89.7 X****ขนาดบรรจุภัณฑ์: 1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 114.7 mm
- External Height: 55.1 mm
- External Width: 89.7 mm
- External Dimensions: 114.7 x 89.7 x 55.1 mm
- Colour: Grey
- Lid Colour: Grey
- Flanged: No

**5173816** Die Cast**RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, GREY LID, 114.4 X 63.7 X****ขนาดบรรจุภัณฑ์: 1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 114.4 mm
- External Height: 55.1 mm
- External Width: 63.7 mm
- External Dimensions: 114.4 x 63.7 x 55.1 mm
- Colour: Grey
- Lid Colour: Grey
- Flanged: No

**5173822** Die Cast**RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, GREY LID, 222.1 X 145.9 X****ขนาดบรรจุภัณฑ์: 1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 222.1 mm
- External Height: 55.9 mm
- External Width: 145.9 mm
- External Dimensions: 222.1 x 145.9 x 55.9 mm
- Colour: Grey
- Lid Colour: Grey
- Flanged: No

**5173838** Die Cast**RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, GREY LID, 171.9 X 120.9 X****ขนาดบรรจุภัณฑ์: 1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 171.9 mm
- External Height: 55 mm
- External Width: 120.9 mm
- External Dimensions: 171.9 x 120.9 x 55 mm
- Colour: Grey
- Lid Colour: Grey
- Flanged: No

**5173850** Die Cast**RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, GREY LID, 114.5 X 63.6 X****ขนาดบรรจุภัณฑ์: 1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 114.5 mm
- External Height: 30.3 mm
- External Width: 63.6 mm
- External Dimensions: 114.5 x 63.6 x 30.3 mm
- Colour: Grey
- Lid Colour: Grey
- Flanged: No

**5173866** Die Cast**RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, GREY LID, 89.1 X 35 X****ขนาดบรรจุภัณฑ์: 1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 89.1 mm
- External Height: 30.3 mm
- External Width: 35 mm
- External Dimensions: 89.1 x 35 x 30.3 mm
- Colour: Grey
- Lid Colour: Grey
- Flanged: No

**5173888** Die Cast**RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, GREY LID, 222.2 X 146 X****ขนาดบรรจุภัณฑ์: 1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 222.2 mm
- External Height: 106.5 mm
- External Width: 146 mm
- External Dimensions: 222.2 x 146 x 106.5 mm
- Colour: Grey
- Lid Colour: Grey
- Flanged: No

**5173894** Die Cast**RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, GREY LID, 250 X 250 X****ขนาดบรรจุภัณฑ์: 1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 250 mm
- External Height: 100 mm
- External Width: 250 mm
- External Dimensions: 250 x 250 x 100 mm
- Colour: Grey
- Lid Colour: Grey
- Flanged: No

**5173917** Die Cast**RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, GREY LID, 275 X 175 X****ขนาดบรรจุภัณฑ์: 1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 275 mm
- External Height: 65.5 mm
- External Width: 175 mm
- External Dimensions: 275 x 175 x 65.5 mm
- Colour: Grey
- Lid Colour: Grey
- Flanged: No

**5173923** Die Cast**RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, GREY LID, 165.8 X 127.3 X****ขนาดบรรจุภัณฑ์: 1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 165.8 mm
- External Height: 76.3 mm
- External Width: 127.3 mm
- External Dimensions: 165.8 x 127.3 x 76.3 mm
- Colour: Grey
- Lid Colour: Grey
- Flanged: No

**5173939** Die Cast**RS PRO BLACK DIE CAST ALUMINIUM ENCLOSURE, BLACK LID, 114.5 X 63.6 X****ขนาดบรรจุภัณฑ์: 1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 114.5 mm
- External Height: 30.3 mm
- External Width: 63.6 mm
- External Dimensions: 114.5 x 63.6 x 30.3 mm
- Colour: Black
- Lid Colour: Black
- Flanged: No

**5173951** Die Cast**RS PRO BLACK DIE CAST ALUMINIUM ENCLOSURE, BLACK LID, 114.4 X 63.7 X****ขนาดบรรจุภัณฑ์: 1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 114.4 mm
- External Height: 55.1 mm
- External Width: 63.7 mm
- External Dimensions: 114.4 x 63.7 x 55.1 mm
- Colour: Black
- Lid Colour: Black
- Flanged: No

**5173967** Die Cast**RS PRO BLACK DIE CAST ALUMINIUM ENCLOSURE, BLACK LID, 171.9 X 120.9 X****ขนาดบรรจุภัณฑ์: 1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 171.9 mm
- External Height: 55 mm
- External Width: 120.9 mm
- External Dimensions: 171.9 x 120.9 x 55 mm
- Colour: Black
- Lid Colour: Black
- Flanged: No

**5173973** Die Cast**RS PRO BLACK DIE CAST ALUMINIUM ENCLOSURE, BLACK LID, 275 X 175 X****ขนาดบรรจุภัณฑ์: 1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 275 mm
- External Height: 65.5 mm
- External Width: 175 mm
- External Dimensions: 275 x 175 x 65.5 mm
- Colour: Black
- Lid Colour: Black
- Flanged: No

**5173989** Die Cast

RS PRO BLACK DIE CAST ALUMINIUM ENCLOSURE, BLACK LID, 165.8 X 127.3

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 165.8 mm
 - External Height: 76.3 mm
 - External Width: 127.3 mm
 - External Dimensions: 165.8 x 127.3 x 76.3 mm
 - Colour: Black
 - Lid Colour: Black
 - Flanged: No



5173995 Die Cast

RS PRO BLACK DIE CAST ALUMINIUM ENCLOSURE, BLACK LID, 250 X 250 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 250 mm
 - External Height: 100 mm
 - External Width: 250 mm
 - External Dimensions: 250 x 250 x 100 mm
 - Colour: Black
 - Lid Colour: Black
 - Flanged: No



5174011 Die Cast

RS PRO BLACK DIE CAST ALUMINIUM ENCLOSURE, BLACK LID, 114.5 X 63.6

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 114.5 mm
 - External Height: 30.3 mm
 - External Width: 63.6 mm
 - External Dimensions: 114.5 x 63.6 x 30.3 mm
 - Colour: Black
 - Lid Colour: Black
 - Flanged: No



5174033 Die Cast

RS PRO BLACK DIE CAST ALUMINIUM ENCLOSURE, BLACK LID, 114.4 X 63.7

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 114.4 mm
 - External Height: 55.1 mm
 - External Width: 63.7 mm
 - External Dimensions: 114.4 x 63.7 x 55.1 mm
 - Colour: Black
 - Lid Colour: Black
 - Flanged: No



5174049 Die Cast

RS PRO BLACK DIE CAST ALUMINIUM ENCLOSURE, BLACK LID, 171.9 X 120.9

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 171.9 mm
 - External Height: 55 mm
 - External Width: 120.9 mm
 - External Dimensions: 171.9 x 120.9 x 55 mm
 - Colour: Black
 - Lid Colour: Black
 - Flanged: No



5174055 Die Cast

RS PRO BLACK DIE CAST ALUMINIUM ENCLOSURE, BLACK LID, 114.7 X 89.7

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 114.7 mm
 - External Height: 55.1 mm
 - External Width: 89.7 mm
 - External Dimensions: 114.7 x 89.7 x 55.1 mm
 - Colour: Black
 - Lid Colour: Black
 - Flanged: No



5174061 Die Cast

RS PRO BLACK DIE CAST ALUMINIUM ENCLOSURE, BLACK LID, 139.1 X 101.5

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 139.1 mm
 - External Height: 76.7 mm
 - External Width: 101.5 mm
 - External Dimensions: 139.1 x 101.5 x 76.7 mm
 - Colour: Black
 - Lid Colour: Black
 - Flanged: No



5174083 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP65, FLANGED, SILVER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 139.6 mm
 - External Height: 55 mm
 - External Width: 63.8 mm
 - External Dimensions: 139.6 x 63.8 x 55 mm
 - IP Rating: IP65
 - Colour: Silver
 - Lid Colour: Silver



5174099 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP65, FLANGED, SILVER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 113.9 mm
 - External Height: 30 mm
 - External Width: 35.1 mm
 - External Dimensions: 113.9 x 35.1 x 30 mm
 - IP Rating: IP65
 - Colour: Silver
 - Lid Colour: Silver



5174106 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP65, FLANGED, SILVER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 139.8 mm
 - External Height: 55.2 mm
 - External Width: 89.7 mm
 - External Dimensions: 139.8 x 89.7 x 55.2 mm
 - IP Rating: IP65
 - Colour: Silver
 - Lid Colour: Silver



5174112 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP65, FLANGED, SILVER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 139.7 mm
 - External Height: 30 mm
 - External Width: 63.8 mm
 - External Dimensions: 139.7 x 63.8 x 30 mm
 - IP Rating: IP65
 - Colour: Silver
 - Lid Colour: Silver



5174128 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP65, FLANGED, SILVER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 140 mm
 - External Height: 77 mm
 - External Width: 102 mm
 - External Dimensions: 140 x 102 x 77 mm
 - IP Rating: IP65
 - Colour: Silver
 - Lid Colour: Silver



5174140 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP65, FLANGED, SILVER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 201.7 mm
 - External Height: 105.4 mm
 - External Width: 121.2 mm
 - External Dimensions: 201.7 x 121.2 x 105.4 mm
 - IP Rating: IP65
 - Colour: Silver
 - Lid Colour: Silver



5174156 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP65, FLANGED, SILVER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 252 mm
 - External Height: 55.5 mm
 - External Width: 146.1 mm
 - External Dimensions: 252 x 146.1 x 55.5 mm
 - IP Rating: IP65
 - Colour: Silver
 - Lid Colour: Silver



5174162 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP65, FLANGED, SILVER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 184.8 mm
 - External Height: 76.3 mm
 - External Width: 127.4 mm
 - External Dimensions: 184.8 x 127.4 x 76.3 mm
 - IP Rating: IP65
 - Colour: Silver
 - Lid Colour: Silver



5174178 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP65, FLANGED, SILVER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 201.7 mm
 - External Height: 55.3 mm
 - External Width: 121.2 mm
 - External Dimensions: 201.7 x 121.2 x 55.3 mm
 - IP Rating: IP65
 - Colour: Silver
 - Lid Colour: Silver



5174184 Die Cast

RS PRO BLACK DIE CAST ALUMINIUM ENCLOSURE, IP66, BLACK LID, 89.1 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 89.1 mm
 - External Height: 30.3 mm
 - External Width: 35 mm
 - External Dimensions: 89.1 x 35 x 30.3 mm
 - IP Rating: IP66
 - Colour: Black
 - Lid Colour: Black

**5174257** Die Cast**RS PRO BLACK DIE CAST ALUMINIUM ENCLOSURE, IP66, BLACK LID, 114.5 X**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 114.5 mm
 - External Height: 30.3 mm
 - External Width: 63.6 mm
 - External Dimensions: 114.5 x 63.6 x 30.3 mm
 - IP Rating: IP66
 - Colour: Black
 - Lid Colour: Black

**5174263** Die Cast**RS PRO BLACK DIE CAST ALUMINIUM ENCLOSURE, IP66, BLACK LID, 114.7 X**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 114.7 mm
 - External Height: 55.1 mm
 - External Width: 89.7 mm
 - External Dimensions: 114.7 x 89.7 x 55.1 mm
 - IP Rating: IP66
 - Colour: Black
 - Lid Colour: Black

**5174279** Die Cast**RS PRO BLACK DIE CAST ALUMINIUM ENCLOSURE, IP66, BLACK LID, 171.9 X**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 171.9 mm
 - External Height: 55 mm
 - External Width: 120.9 mm
 - External Dimensions: 171.9 x 120.9 x 55 mm
 - IP Rating: IP66
 - Colour: Black
 - Lid Colour: Black

**5174285** Die Cast**RS PRO BLACK DIE CAST ALUMINIUM ENCLOSURE, IP66, BLACK LID, 165.8 X**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 165.8 mm
 - External Height: 76.3 mm
 - External Width: 127.3 mm
 - External Dimensions: 165.8 x 127.3 x 76.3 mm
 - IP Rating: IP66
 - Colour: Black
 - Lid Colour: Black

**5174308** Die Cast**RS PRO BLACK DIE CAST ALUMINIUM ENCLOSURE, IP66, BLACK LID, 250 X**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 250 mm
 - External Height: 100 mm
 - External Width: 250 mm
 - External Dimensions: 250 x 250 x 100 mm
 - IP Rating: IP66
 - Colour: Black
 - Lid Colour: Black

**5174314** Die Cast**RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP66, SILVER LID, 114.5 X**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 114.5 mm
 - External Height: 30.3 mm
 - External Width: 63.6 mm
 - External Dimensions: 114.5 x 63.6 x 30.3 mm
 - IP Rating: IP66
 - Colour: Silver
 - Lid Colour: Silver

**5174409** Die Cast**RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, SILVER LID, 222.2 X 146 X**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 222.2 mm
 - External Height: 106.5 mm
 - External Width: 146 mm
 - External Dimensions: 222.2 x 146 x 106.5 mm
 - Colour: Silver
 - Lid Colour: Silver
 - Flanged: No

**5174437** Die Cast**RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, SILVER LID, 89.1 X 35 X**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 89.1 mm
 - External Height: 30.3 mm
 - External Width: 35 mm
 - External Dimensions: 89.1 x 35 x 30.3 mm
 - Colour: Silver
 - Lid Colour: Silver
 - Flanged: No

**5174443** Die Cast**RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP66, SILVER LID, 222.1 X**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 222.1 mm
 - External Height: 55.9 mm
 - External Width: 145.9 mm
 - External Dimensions: 222.1 x 145.9 x 55.9 mm
 - IP Rating: IP66
 - Colour: Silver
 - Lid Colour: Silver

**5174459** Die Cast**RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP66, SILVER LID, 222.2 X**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 222.2 mm
 - External Height: 106.5 mm
 - External Width: 146 mm
 - External Dimensions: 222.2 x 146 x 106.5 mm
 - IP Rating: IP66
 - Colour: Silver
 - Lid Colour: Silver

**5174465** Die Cast**RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP66, FLANGED, GREY**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 168.7 mm
 - External Height: 76.5 mm
 - External Width: 101.6 mm
 - External Dimensions: 168.7 x 101.6 x 76.5 mm
 - IP Rating: IP66
 - Colour: Grey
 - Lid Colour: Grey

**6214895** Die Cast**RS PRO BLACK DIE CAST ALUMINIUM ENCLOSURE, BLACK LID, 222.1 X 145.9**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 222.1 mm
 - External Height: 55.9 mm
 - External Width: 145.9 mm
 - External Dimensions: 222.1 x 145.9 x 55.9 mm
 - Colour: Black
 - Lid Colour: Black
 - Flanged: No

**6214968** Die Cast**RS PRO BLACK DIE CAST ALUMINIUM ENCLOSURE, IP66, FLANGED, BLACK**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 139.6 mm
 - External Height: 55 mm
 - External Width: 63.8 mm
 - External Dimensions: 139.6 x 63.8 x 55 mm
 - IP Rating: IP66
 - Colour: Black
 - Lid Colour: Black

**6214980** Die Cast**RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP66, FLANGED, GREY**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 113.9 mm
 - External Height: 30 mm
 - External Width: 35.1 mm
 - External Dimensions: 113.9 x 35.1 x 30 mm
 - IP Rating: IP66
 - Colour: Grey
 - Lid Colour: Grey

**6215028** Die Cast**RS PRO BLACK DIE CAST ALUMINIUM ENCLOSURE, IP66, FLANGED, BLACK**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 168.7 mm
 - External Height: 76.5 mm
 - External Width: 101.6 mm
 - External Dimensions: 168.7 x 101.6 x 76.5 mm
 - IP Rating: IP66
 - Colour: Black
 - Lid Colour: Black

**6215034** Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP66, FLANGED, GREY

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 252 mm
 - External Height: 55.5 mm
 - External Width: 146.1 mm
 - External Dimensions: 252 x 146.1 x 55.5 mm
 - IP Rating: IP66
 - Colour: Grey
 - Lid Colour: Grey



6215078 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP67, SILVER LID, 274 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 274 mm
 - External Height: 100 mm
 - External Width: 173 mm
 - External Dimensions: 274 x 173 x 100 mm
 - IP Rating: IP67
 - Colour: Silver
 - Lid Colour: Silver



7004100 Die Cast

RS PRO BLACK DIE CAST ALUMINIUM ENCLOSURE, IP67, BLACK LID, 274 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 274 mm
 - External Height: 100 mm
 - External Width: 173 mm
 - External Dimensions: 274 x 173 x 100 mm
 - IP Rating: IP67
 - Colour: Black
 - Lid Colour: Black



7004131 Die Cast

RS PRO BLACK DIE CAST ALUMINIUM ENCLOSURE, IP67, BLACK LID, 200 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 200 mm
 - External Height: 75 mm
 - External Width: 150 mm
 - External Dimensions: 200 x 150 x 75 mm
 - IP Rating: IP67
 - Colour: Black
 - Lid Colour: Black



7004141 Die Cast

RS PRO BLACK DIE CAST ALUMINIUM ENCLOSURE, IP67, BLACK LID, 200 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 200 mm
 - External Height: 50 mm
 - External Width: 150 mm
 - External Dimensions: 200 x 150 x 50 mm
 - IP Rating: IP67
 - Colour: Black
 - Lid Colour: Black



7004147 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP66, SILVER LID, 125 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 125 mm
 - External Height: 57 mm
 - External Width: 80 mm
 - External Dimensions: 125 x 80 x 57 mm
 - IP Rating: IP66
 - Colour: Silver
 - Lid Colour: Silver



7608913 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP66, SILVER LID, 98 X 64

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 98 mm
 - External Height: 34 mm
 - External Width: 64 mm
 - External Dimensions: 98 x 64 x 34 mm
 - IP Rating: IP66
 - Colour: Silver
 - Lid Colour: Silver



7608926 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP66, SILVER LID, 75 X 80

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 75 mm
 - External Height: 57 mm
 - External Width: 80 mm
 - External Dimensions: 75 x 80 x 57 mm
 - IP Rating: IP66
 - Colour: Silver
 - Lid Colour: Silver



7608929 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP66, SILVER LID, 150 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 150 mm
 - External Height: 34 mm
 - External Width: 64 mm
 - External Dimensions: 150 x 64 x 34 mm
 - IP Rating: IP66
 - Colour: Silver
 - Lid Colour: Silver



7608932 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP66, SILVER LID, 100 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 100 mm
 - External Height: 81 mm
 - External Width: 100 mm
 - External Dimensions: 100 x 100 x 81 mm
 - IP Rating: IP66
 - Colour: Silver
 - Lid Colour: Silver



7608935 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP66, SILVER LID, 160 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 160 mm
 - External Height: 81 mm
 - External Width: 100 mm
 - External Dimensions: 160 x 100 x 81 mm
 - IP Rating: IP66
 - Colour: Silver
 - Lid Colour: Silver



7608939 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP66, SILVER LID, 260 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 260 mm
 - External Height: 90 mm
 - External Width: 160 mm
 - External Dimensions: 260 x 160 x 90 mm
 - IP Rating: IP66
 - Colour: Silver
 - Lid Colour: Silver



7608941 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP66, SILVER LID, 250 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 250 mm
 - External Height: 55 mm
 - External Width: 80 mm
 - External Dimensions: 250 x 80 x 55 mm
 - IP Rating: IP66
 - Colour: Silver
 - Lid Colour: Silver



7608945 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP66, SILVER LID, 160 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 160 mm
 - External Height: 90 mm
 - External Width: 160 mm
 - External Dimensions: 160 x 160 x 90 mm
 - IP Rating: IP66
 - Colour: Silver
 - Lid Colour: Silver



7608951 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP66, SILVER LID, 280 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 280 mm
 - External Height: 110 mm
 - External Width: 230 mm
 - External Dimensions: 280 x 230 x 110 mm
 - IP Rating: IP66
 - Colour: Silver
 - Lid Colour: Silver



7608954 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP66, SILVER LID, 220 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 200 mm
 - External Height: 91 mm
 - External Width: 120 mm
 - External Dimensions: 220 x 120 x 91 mm
 - IP Rating: IP66
 - Colour: Silver
 - Lid Colour: Silver



7608960 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP66, GREY LID, 125 X 80

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 125 mm
 - External Height: 57 mm
 - External Width: 80 mm
 - External Dimensions: 125 x 80 x 57 mm
 - IP Rating: IP66
 - Colour: Grey
 - Lid Colour: Grey



7608963 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP66, GREY LID, 122 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 122 mm
 - External Height: 81 mm
 - External Width: 120 mm
 - External Dimensions: 122 x 120 x 81 mm
 - IP Rating: IP66
 - Colour: Grey
 - Lid Colour: Grey



7608967 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP66, GREY LID, 50 X 45

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 50 mm
 - External Height: 30 mm
 - External Width: 45 mm
 - External Dimensions: 50 x 45 x 30 mm
 - IP Rating: IP66
 - Colour: Grey
 - Lid Colour: Grey



7608973 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP66, GREY LID, 98 X 64

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 98 mm
 - External Height: 34 mm
 - External Width: 64 mm
 - External Dimensions: 98 x 64 x 34 mm
 - IP Rating: IP66
 - Colour: Grey
 - Lid Colour: Grey



7608976 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP66, GREY LID, 75 X 80

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 75 mm
 - External Height: 57 mm
 - External Width: 80 mm
 - External Dimensions: 75 x 80 x 57 mm
 - IP Rating: IP66
 - Colour: Grey
 - Lid Colour: Grey



7608979 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP66, GREY LID, 150 X 64

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 150 mm
 - External Height: 34 mm
 - External Width: 64 mm
 - External Dimensions: 150 x 64 x 34 mm
 - IP Rating: IP66
 - Colour: Grey
 - Lid Colour: Grey



7608982 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP66, GREY LID, 100 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 100 mm
 - External Height: 81 mm
 - External Width: 100 mm
 - External Dimensions: 100 x 100 x 81 mm
 - IP Rating: IP66
 - Colour: Grey
 - Lid Colour: Grey



7608985 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP66, GREY LID, 160 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 160 mm
 - External Height: 81 mm
 - External Width: 100 mm
 - External Dimensions: 160 x 100 x 81 mm
 - IP Rating: IP66
 - Colour: Grey
 - Lid Colour: Grey



7608989 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP66, GREY LID, 260 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 260 mm
 - External Height: 90 mm
 - External Width: 160 mm
 - External Dimensions: 260 x 160 x 90 mm
 - IP Rating: IP66
 - Colour: Grey
 - Lid Colour: Grey



7608991 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP66, GREY LID, 250 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 250 mm
 - External Height: 57 mm
 - External Width: 80 mm
 - External Dimensions: 250 x 80 x 57 mm
 - IP Rating: IP66
 - Colour: Grey
 - Lid Colour: Grey



7608995 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP66, GREY LID, 175 X 80

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 175 mm
 - External Height: 57 mm
 - External Width: 80 mm
 - External Dimensions: 175 x 80 x 57 mm
 - IP Rating: IP66
 - Colour: Grey
 - Lid Colour: Grey



7608998 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP66, GREY LID, 58 X 64

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 58 mm
 - External Height: 34 mm
 - External Width: 64 mm
 - External Dimensions: 58 x 64 x 34 mm
 - IP Rating: IP66
 - Colour: Grey
 - Lid Colour: Grey



7609001 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP66, GREY LID, 160 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 160 mm
 - External Height: 91 mm
 - External Width: 160 mm
 - External Dimensions: 160 x 160 x 91 mm
 - IP Rating: IP66
 - Colour: Grey
 - Lid Colour: Grey



7609005 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP66, GREY LID, 280 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 280 mm
 - External Height: 110 mm
 - External Width: 230 mm
 - External Dimensions: 280 x 230 x 110 mm
 - IP Rating: IP66
 - Colour: Grey
 - Lid Colour: Grey



7609008 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP66, GREY LID, 220 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 200 mm
 - External Height: 90 mm
 - External Width: 120 mm
 - External Dimensions: 220 x 120 x 90 mm
 - IP Rating: IP66
 - Colour: Grey
 - Lid Colour: Grey



7609014 Die Cast

RS PRO SILVER ALUMINIUM ENCLOSURE, IP67, SILVER LID, 262 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Aluminium
 - External Length: 262 mm
 - External Height: 90 mm
 - External Width: 182 mm
 - External Dimensions: 262 x 182 x 90 mm
 - IP Rating: IP67
 - Colour: Silver
 - Lid Colour: Silver



7683801 Aluminium

RS PRO GREY ABS ENCLOSURE, IP55, GREY LID, 200 X 155 X 80MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 155 mm
 - External Height: 200 mm
 - External Width: 80 mm
 - External Dimensions: 200 x 155 x 80 mm
 - IP Rating: IP55
 - Colour: Grey
 - Lid Colour: Grey



7696134 ABS

RS PRO GREY ABS ENCLOSURE, IP55, GREY LID, 210 X 160 X 260MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 210 mm
 - External Height: 260 mm
 - External Width: 160 mm
 - External Dimensions: 210 x 160 x 260 mm
 - IP Rating: IP55
 - Colour: Grey
 - Lid Colour: Grey



7696140 ABS

RS PRO GREY ABS ENCLOSURE, IP55, GREY LID, 240 X 135 X 320MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 240 mm
 - External Height: 320 mm
 - External Width: 135 mm
 - External Dimensions: 240 x 135 x 320 mm
 - IP Rating: IP55
 - Colour: Grey
 - Lid Colour: Grey



7696144 ABS

RS PRO GREY ABS ENCLOSURE, IP55, GREY LID, 210 X 95 X 260MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 210 mm
 - External Height: 260 mm
 - External Width: 95 mm
 - External Dimensions: 210 x 95 x 260 mm
 - IP Rating: IP55
 - Colour: Grey
 - Lid Colour: Grey



7696147 ABS

RS PRO GREY ABS ENCLOSURE, IP55, GREY LID, 320 X 240 X 180MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 180 mm
 - External Height: 320 mm
 - External Width: 240 mm
 - External Dimensions: 320 x 240 x 180 mm
 - IP Rating: IP55
 - Colour: Grey
 - Lid Colour: Grey



7696153 ABS

RS PRO BLACK ALUMINIUM ENCLOSURE, IP67, FLANGED, BLACK

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Aluminium
 - External Length: 152 mm
 - External Height: 55 mm
 - External Width: 112 mm
 - External Dimensions: 152 x 112 x 55 mm
 - IP Rating: IP67
 - Colour: Black
 - Lid Colour: Black



7717641 Aluminium

RS PRO BLACK ALUMINIUM ENCLOSURE, IP67, FLANGED, BLACK

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Aluminium
 - External Length: 202 mm
 - External Height: 80 mm
 - External Width: 142 mm
 - External Dimensions: 202 x 142 x 80 mm
 - IP Rating: IP67
 - Colour: Black
 - Lid Colour: Black



7717651 Aluminium

RS PRO BLACK ALUMINIUM ENCLOSURE, IP67, FLANGED, BLACK

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Aluminium
 - External Length: 262 mm
 - External Height: 90 mm
 - External Width: 182 mm
 - External Dimensions: 262 x 182 x 90 mm
 - IP Rating: IP67
 - Colour: Black
 - Lid Colour: Black



7717663 Aluminium

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP66, SILVER LID, 122 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 122 mm
 - External Height: 91 mm
 - External Width: 120 mm
 - External Dimensions: 122 x 120 x 91 mm
 - IP Rating: IP66
 - Colour: Silver
 - Lid Colour: Silver



8462942 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP66, SILVER LID, 50 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 50 mm
 - External Height: 30 mm
 - External Width: 45 mm
 - External Dimensions: 50 x 45 x 30 mm
 - IP Rating: IP66
 - Colour: Silver
 - Lid Colour: Silver



8462945 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP66, SILVER LID, 220 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 220 mm
 - External Height: 81 mm
 - External Width: 120 mm
 - External Dimensions: 220 x 120 x 81 mm
 - IP Rating: IP66
 - Colour: Silver
 - Lid Colour: Silver



8462948 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP66, SILVER LID, 360 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 360 mm
 - External Height: 90 mm
 - External Width: 160 mm
 - External Dimensions: 360 x 160 x 90 mm
 - IP Rating: IP66
 - Colour: Silver
 - Lid Colour: Silver



8462951 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP66, SILVER LID, 180 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 180 mm
 - External Height: 100 mm
 - External Width: 180 mm
 - External Dimensions: 180 x 180 x 100 mm
 - IP Rating: IP66
 - Colour: Silver
 - Lid Colour: Silver



8462954 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP66, SILVER LID, 280 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 280 mm
 - External Height: 100 mm
 - External Width: 180 mm
 - External Dimensions: 280 x 180 x 100 mm
 - IP Rating: IP66
 - Colour: Silver
 - Lid Colour: Silver



8462958 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP66, SILVER LID, 330 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 330 mm
 - External Height: 110 mm
 - External Width: 230 mm
 - External Dimensions: 330 x 230 x 110 mm
 - IP Rating: IP66
 - Colour: Silver
 - Lid Colour: Silver



8462960 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP66, SILVER LID, 200 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 200 mm
 - External Height: 180 mm
 - External Width: 230 mm
 - External Dimensions: 200 x 230 x 180 mm
 - IP Rating: IP66
 - Colour: Silver
 - Lid Colour: Silver



8462964 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP66, SILVER LID, 230 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 230 mm
 - External Height: 110 mm
 - External Width: 200 mm
 - External Dimensions: 230 x 200 x 110 mm
 - IP Rating: IP66
 - Colour: Silver
 - Lid Colour: Silver



8462967 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP66, SILVER LID, 400 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 400 mm
 - External Height: 110 mm
 - External Width: 230 mm
 - External Dimensions: 400 x 230 x 110 mm
 - IP Rating: IP66
 - Colour: Silver
 - Lid Colour: Silver



8462986 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP66, GREY LID, 220 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 220 mm
 - External Height: 81 mm
 - External Width: 120 mm
 - External Dimensions: 220 x 120 x 81 mm
 - IP Rating: IP66
 - Colour: Grey
 - Lid Colour: Grey



8462998 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP66, GREY LID, 280 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 280 mm
 - External Height: 100 mm
 - External Width: 180 mm
 - External Dimensions: 280 x 180 x 100 mm
 - IP Rating: IP66
 - Colour: Grey
 - Lid Colour: Grey



8463002 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP66, GREY LID, 360 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 360 mm
 - External Height: 90 mm
 - External Width: 160 mm
 - External Dimensions: 360 x 160 x 90 mm
 - IP Rating: IP66
 - Colour: Grey
 - Lid Colour: Grey



8463005 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP66, GREY LID, 180 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 180 mm
 - External Height: 100 mm
 - External Width: 180 mm
 - External Dimensions: 180 x 180 x 100 mm
 - IP Rating: IP66
 - Colour: Grey
 - Lid Colour: Grey



8463008 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP66, GREY LID, 230 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 230 mm
 - External Height: 110 mm
 - External Width: 200 mm
 - External Dimensions: 230 x 200 x 110 mm
 - IP Rating: IP66
 - Colour: Grey
 - Lid Colour: Grey



8463011 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP66, GREY LID, 200 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 200 mm
 - External Height: 180 mm
 - External Width: 230 mm
 - External Dimensions: 200 x 230 x 180 mm
 - IP Rating: IP66
 - Colour: Grey
 - Lid Colour: Grey



8463018 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP66, GREY LID, 330 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 330 mm
 - External Height: 110 mm
 - External Width: 230 mm
 - External Dimensions: 330 x 230 x 110 mm
 - IP Rating: IP66
 - Colour: Grey
 - Lid Colour: Grey



8463014 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP66, GREY LID, 400 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 400 mm
 - External Height: 110 mm
 - External Width: 310 mm
 - External Dimensions: 400 x 310 x 110 mm
 - IP Rating: IP66
 - Colour: Grey
 - Lid Colour: Grey



8463020 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP66, GREY LID, 330 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 330 mm
 - External Height: 180 mm
 - External Width: 230 mm
 - External Dimensions: 330 x 230 x 180 mm
 - IP Rating: IP66
 - Colour: Grey
 - Lid Colour: Grey



8463027 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP66, GREY LID, 400 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Die Cast Aluminium
 - External Length: 400 mm
 - External Height: 110 mm
 - External Width: 230 mm
 - External Dimensions: 400 x 230 x 110 mm
 - IP Rating: IP66
 - Colour: Grey
 - Lid Colour: Grey



8463030 Die Cast

RS PRO BLACK PET ENCLOSURE, IP66, GREY LID, 80 X 75 X 55MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: PET
 - External Length: 80 mm
 - External Height: 55 mm
 - External Width: 75 mm
 - External Dimensions: 80 x 75 x 55 mm
 - IP Rating: IP66
 - Colour: Black
 - Lid Colour: Grey



9188724 PET

RS PRO GREY PET ENCLOSURE, IP66, GREY LID, 110 X 75 X 55MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: PET
 - External Length: 110 mm
 - External Height: 55 mm
 - External Width: 75 mm
 - External Dimensions: 110 x 75 x 55 mm
 - IP Rating: IP66
 - Colour: Grey
 - Lid Colour: Grey



9188727 PET

RS PRO GREY PET ENCLOSURE, IP66, GREY LID, 122 X 120 X 90MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: PET
 - External Length: 122 mm
 - External Height: 90 mm
 - External Width: 120 mm
 - External Dimensions: 122 x 120 x 90 mm
 - IP Rating: IP66
 - Colour: Grey
 - Lid Colour: Grey



9188746 PET

RS PRO BLACK PET ENCLOSURE, IP66, BLACK LID, 122 X 120 X 90MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: PET
 - External Length: 122 mm
 - External Height: 90 mm
 - External Width: 120 mm
 - External Dimensions: 122 x 120 x 90 mm
 - IP Rating: IP66
 - Colour: Black
 - Lid Colour: Black



9188758 PET

RS PRO BLACK PET ENCLOSURE, IP66, BLACK LID, 160 X 75 X 75MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: PET
 - External Length: 160 mm
 - External Height: 75 mm
 - External Width: 75 mm
 - External Dimensions: 160 x 75 x 75 mm
 - IP Rating: IP66
 - Colour: Black
 - Lid Colour: Black



9188783 PET

RS PRO GREY PET ENCLOSURE, IP66, GREY LID, 160 X 160 X 90MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: PET
 - External Length: 160 mm
 - External Height: 90 mm
 - External Width: 160 mm
 - External Dimensions: 160 x 160 x 90 mm
 - IP Rating: IP66
 - Colour: Grey
 - Lid Colour: Grey



9188780 PET

RS PRO GREY PET ENCLOSURE, IP66, GREY LID, 190 X 75 X 55MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: PET
 - External Length: 190 mm
 - External Height: 55 mm
 - External Width: 75 mm
 - External Dimensions: 190 x 75 x 55 mm
 - IP Rating: IP66
 - Colour: Grey
 - Lid Colour: Grey



9188806 PET

RS PRO GREY PET ENCLOSURE, IP66, GREY LID, 220 X 120 X 90MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: PET
 - External Length: 220 mm
 - External Height: 90 mm
 - External Width: 120 mm
 - External Dimensions: 220 x 120 x 90 mm
 - IP Rating: IP66
 - Colour: Grey
 - Lid Colour: Grey



9188815 PET

RS PRO GREY PET ENCLOSURE, IP66, GREY LID, 255 X 250 X 120MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: PET
 - External Length: 255 mm
 - External Height: 120 mm
 - External Width: 250 mm
 - External Dimensions: 255 x 250 x 120 mm
 - IP Rating: IP66
 - Colour: Grey
 - Lid Colour: Grey



9188825 PET

RS PRO GREY PET ENCLOSURE, IP66, GREY LID, 260 X 160 X 90MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: PET
 - External Length: 260 mm
 - External Height: 90 mm
 - External Width: 160 mm
 - External Dimensions: 260 x 160 x 90 mm
 - IP Rating: IP66
 - Colour: Grey
 - Lid Colour: Grey



9188840 PET

RS PRO BLACK POLYESTER ENCLOSURE, IP66, BLACK LID, 220 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Polyester
 - External Length: 220 mm
 - External Height: 90 mm
 - External Width: 120 mm
 - External Dimensions: 220 x 120 x 90 mm
 - IP Rating: IP66
 - Colour: Black
 - Lid Colour: Black



9188828 Polyester

RS PRO BLACK PET ENCLOSURE, IP66, BLACK LID, 360 X 160 X 90MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: PET
 - External Length: 360 mm
 - External Height: 90 mm
 - External Width: 160 mm
 - External Dimensions: 360 x 160 x 90 mm
 - IP Rating: IP66
 - Colour: Black
 - Lid Colour: Black



9188862 PET

RS PRO GREY PET ENCLOSURE, IP66, GREY LID, 400 X 250 X 120MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: PET
 - External Length: 400 mm
 - External Height: 120 mm
 - External Width: 250 mm
 - External Dimensions: 400 x 250 x 120 mm
 - IP Rating: IP66
 - Colour: Grey
 - Lid Colour: Grey



9188869 PET

RS PRO BLACK ABS ENCLOSURE, FLANGED, BLACK LID, 50 X 50 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 50 mm
 - External Height: 27 mm
 - External Width: 50 mm
 - External Dimensions: 50 x 50 x 27 mm
 - Colour: Black
 - Lid Colour: Black
 - Flanged: Yes



9190323 ABS

RS PRO BLACK ABS ENCLOSURE, FLANGED, BLACK LID, 70 X 50 X 42MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 70 mm
 - External Height: 42 mm
 - External Width: 50 mm
 - External Dimensions: 70 x 50 x 42 mm
 - Colour: Black
 - Lid Colour: Black
 - Flanged: Yes



9190339 ABS

RS PRO BLACK ABS ENCLOSURE, FLANGED, BLACK LID, 90 X 45 X 27MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 90 mm
 - External Height: 27 mm
 - External Width: 45 mm
 - External Dimensions: 90 x 45 x 27 mm
 - Colour: Black
 - Lid Colour: Black
 - Flanged: Yes



9190348 ABS

RS PRO BLACK ABS ENCLOSURE, FLANGED, BLACK LID, 80 X 80 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 80 mm
 - External Height: 43 mm
 - External Width: 80 mm
 - External Dimensions: 80 x 80 x 43 mm
 - Colour: Black
 - Lid Colour: Black
 - Flanged: Yes



9190351 ABS

RS PRO BLACK ABS ENCLOSURE, FLANGED, BLACK LID, 105 X 70 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 105 mm
 - External Height: 50 mm
 - External Width: 70 mm
 - External Dimensions: 105 x 70 x 50 mm
 - Colour: Black
 - Lid Colour: Black
 - Flanged: Yes



9190354 ABS

RS PRO WHITE ABS ENCLOSURE, FLANGED, WHITE LID, 50 X 50 X 27MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 50 mm
 - External Height: 27 mm
 - External Width: 50 mm
 - External Dimensions: 50 x 50 x 27 mm
 - Colour: White
 - Lid Colour: White
 - Flanged: Yes



9190367 ABS

RS PRO WHITE ABS ENCLOSURE, FLANGED, WHITE LID, 70 X 50 X 42MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 70 mm
 - External Height: 42 mm
 - External Width: 50 mm
 - External Dimensions: 70 x 50 x 42 mm
 - Colour: White
 - Lid Colour: White
 - Flanged: Yes



9190373 ABS

RS PRO WHITE ABS ENCLOSURE, FLANGED, WHITE LID, 105 X 70 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 105 mm
 - External Height: 50 mm
 - External Width: 70 mm
 - External Dimensions: 105 x 70 x 50 mm
 - Colour: White
 - Lid Colour: White
 - Flanged: Yes



9190398 ABS

RS PRO WHITE ABS HANDHELD ENCLOSURE, INTEGRAL BATTERY

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 96.5 mm
 - External Width: 61 mm
 - External Height: 25.5 mm
 - Integral Battery Compartment: Yes
 - Colour: White
 - External Dimensions: 96.5 x 61 x 25.5 mm
 - Standards Met: RoHS Compliant, UL 94 HB, UL E56070



222777 ABS

RS PRO WHITE ABS HANDHELD ENCLOSURE, INTEGRAL BATTERY

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 116.8 mm
 - External Width: 69.9 mm
 - External Height: 25.4 mm
 - Integral Battery Compartment: Yes
 - Colour: White
 - External Dimensions: 116.8 x 69.9 x 25.4 mm
 - Standards Met: RoHS Compliant, UL 94 HB, UL E56070



222783 ABS

RS PRO WHITE ABS HANDHELD ENCLOSURE, INTEGRAL BATTERY

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 146.1 mm
 - External Width: 91.5 mm
 - External Height: 52.9 mm
 - Integral Battery Compartment: Yes
 - Display Window: Yes
 - Colour: White
 - External Dimensions: 146.1 x 91.5 x 52.9 mm



222828 ABS

RS PRO GREY ABS HANDHELD ENCLOSURE, INTEGRAL BATTERY

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 190.5 mm
 - External Width: 101.6 mm
 - External Height: 57.2 mm
 - Integral Battery Compartment: Yes
 - Display Window: Yes
 - Colour: Grey
 - External Dimensions: 190.5 x 101.6 x 57.2 mm



222834 ABS

ENCLOSURE,ABS,INSTRUMENT CASE,BLACK,58X61X25MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 61 mm
 - External Width: 57.7 mm
 - External Height: 25.4 mm
 - Colour: Black
 - External Dimensions: 60.96 x 57.66 x 25.4 mm
 - Standards Met: RoHS Compliant, UL 94 HB, UL E56070



139669 ABS

RS PRO BLACK ABS HANDHELD ENCLOSURE, INTEGRAL BATTERY

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 96.5 mm
 - External Width: 61 mm
 - External Height: 22.9 mm
 - Integral Battery Compartment: Yes
 - Colour: Black
 - External Dimensions: 96.5 x 61 x 22.9 mm
 - Standards Met: RoHS Compliant, UL 94 HB, UL E56070



1196310 ABS

RS PRO BLACK ABS HAND HELD CASE, IP54, 53 X 33 X 15MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 53 mm
 - External Width: 33 mm
 - External Height: 15 mm
 - Weight: 8 g
 - IP Rating: IP54
 - Colour: Black
 - External Dimensions: 53 x 33 x 15 mm



1947486 ABS

RS PRO ABS HAND HELD ENCLOSURE, INTEGRAL BATTERY COMPARTMENT,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 160 mm
 - External Width: 84 mm
 - External Height: 30 mm
 - Integral Battery Compartment: Yes
 - IP Rating: IP54
 - External Dimensions: 160 x 84 x 30 mm



1981368 ABS

RS PRO ABS HAND HELD ENCLOSURE, INTEGRAL BATTERY COMPARTMENT,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 165.1 mm
 - External Width: 100.1 mm
 - External Height: 32 mm
 - Integral Battery Compartment: Yes
 - IP Rating: IP65
 - External Dimensions: 165.1 x 100 x 32 mm



1981374 ABS

RS PRO BLACK ABS HANDHELD ENCLOSURE, INTEGRAL BATTERY

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 116.8 mm
 - External Width: 69 mm
 - External Height: 38.1 mm
 - Integral Battery Compartment: Yes
 - Colour: Black
 - External Dimensions: 116.84 x 68.95 x 38.1 mm
 - Standards Met: RoHS Compliant, UL 94 HB, UL E56070



2397277 ABS

RS PRO WHITE ABS HANDHELD ENCLOSURE, 61.9 X 41.7 X 20.3MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 61.9 mm
 - External Width: 41.7 mm
 - External Height: 20.3 mm
 - Colour: White
 - External Dimensions: 61.9 x 41.7 x 20.3 mm
 - Standards Met: RoHS Compliant, UL 94 HB, UL E56070



2570523 ABS

ENCLOSURE,INSPECTION WINDOW,POLYCARBONATE,IP44,2

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 49 mm
 - Width: 27 mm
 - Height: 78 mm
 - Material: Polycarbonate
 - Colour: Grey
 - For Use With: 46277-3, DIN 43880
 - IP Rating: IP44



2971184 49 mm

ENCLOSURE,INSPECTION WINDOW,POLYCARBONATE,IP67,6

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 127 mm
 - Width: 24 mm
 - Height: 94 mm
 - Material: Polycarbonate
 - Colour: Grey
 - For Use With: 46277-3, DIN 43880
 - IP Rating: IP67



2971207 127 mm

ENCLOSURE,INSPECTION WINDOW,POLYCARBONATE,IP67,8

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 162 mm
 - Width: 24 mm
 - Height: 94 mm
 - Material: Polycarbonate
 - Colour: Grey
 - For Use With: 46277-3, DIN 43880
 - IP Rating: IP44



2971213 162 mm

ENCLOSURE,INSPECTION WINDOW,POLYCARBONATE,IP67,12

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 234 mm
 - Width: 24 mm
 - Height: 94 mm
 - Material: Polycarbonate
 - Colour: Grey
 - For Use With: 46277-3, DIN 43880
 - IP Rating: IP44



2971229 234 mm

MENNEKES GREY POLYCARBONATE IP44 INSPECTION WINDOW FOR USE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 127 mm
 - Width: 47 mm
 - Height: 94 mm
 - Material: Polycarbonate
 - Colour: Grey
 - For Use With: 46277-3, DIN 43880
 - IP Rating: IP44



2971235 127 mm

MENNEKES GREY POLYCARBONATE IP44 INSPECTION WINDOW FOR USE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 162 mm
 - Width: 47 mm
 - Height: 94 mm
 - Material: Polycarbonate
 - Colour: Grey
 - For Use With: 46277-3, DIN 43880
 - IP Rating: IP44



2971241 162 mm

MENNEKES GREY POLYCARBONATE IP44 INSPECTION WINDOW FOR USE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 234 mm
 - Width: 47 mm
 - Height: 94 mm
 - Material: Polycarbonate
 - Colour: Grey
 - For Use With: 46277-3, DIN 43880
 - IP Rating: IP44



2971263 234 mm

RS PRO GREY ABS INSTRUMENT CASE, 120 X 60 X 30MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: ABS
 - External Length: 120 mm
 - External Width: 60 mm
 - External Height: 30 mm
 - External Dimensions: 120 x 60 x 30 mm
 - Colour: Grey
 - IP Rating: IP54
 - Ventilated: No



218898 ABS

ABS,2-PART,CASE,LIGHT GREY,DARK GREY,120MM,60MM,40MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: ABS
 - External Length: 120 mm
 - External Width: 60 mm
 - External Height: 40 mm
 - External Dimensions: 120 x 60 x 40 mm
 - Colour: Grey
 - IP Rating: IP54
 - Ventilated: No



219318 ABS

RS PRO GREY ABS INSTRUMENT CASE, 150 X 80 X 45MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: ABS
 - External Length: 150 mm
 - External Width: 80 mm
 - External Height: 45 mm
 - External Dimensions: 150 x 80 x 45 mm
 - Colour: Grey
 - IP Rating: IP54
 - Ventilated: No



219330 ABS

ABS,2-PART,CASE,LIGHT GREY,DARK GREY,150MM,80MM,60MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: ABS
 - External Length: 150 mm
 - External Width: 80 mm
 - External Height: 60 mm
 - External Dimensions: 150 x 80 x 60 mm
 - Colour: Grey
 - IP Rating: IP54
 - Ventilated: No



219346 ABS

RS PRO GREY ABS INSTRUMENT CASE, 190 X 100 X 40MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: ABS
 - External Length: 190 mm
 - External Width: 100 mm
 - External Height: 40 mm
 - External Dimensions: 190 x 100 x 40 mm
 - Colour: Grey
 - IP Rating: IP54
 - Ventilated: No



219380 ABS

RS PRO GREY ABS INSTRUMENT CASE, 190 X 100 X 80MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: ABS
 - External Length: 190 mm
 - External Width: 100 mm
 - External Height: 80 mm
 - External Dimensions: 190 x 100 x 80 mm
 - Colour: Grey
 - IP Rating: IP54
 - Ventilated: No



219403 ABS

ABS,2-PART,CASE,LIGHT GREY,DARK GREY,90MM,50MM,24MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: ABS
 - External Length: 90 mm
 - External Width: 50 mm
 - External Height: 24 mm
 - External Dimensions: 90 x 50 x 24 mm
 - Colour: Grey
 - IP Rating: IP54
 - Ventilated: No



219548 ABS

ENCLOSURE,ABS,MOULDED CASE,TWO

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: ABS
 - External Length: 134 mm
 - External Width: 129 mm
 - External Height: 38 mm
 - External Dimensions: 134 x 129 x 38 mm
 - Colour: White
 - Ventilated: No
 - Carrying Handle: No



220989 ABS

RS PRO WHITE ABS INSTRUMENT CASE, 159 X 154 X 64MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: ABS
 - External Length: 159 mm
 - External Width: 154 mm
 - External Height: 64 mm
 - External Dimensions: 159 x 154 x 64 mm
 - Colour: White
 - Ventilated: No
 - Carrying Handle: No



220995 ABS

RS PRO BLACK ANODISED ALUMINIUM INSTRUMENT CASE, 442 X

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: Anodised Aluminium
 - External Length: 442 mm
 - External Width: 254 mm
 - External Height: 88 mm
 - External Dimensions: 442 x 254 x 88 mm
 - Colour: Black
 - Ventilated: No
 - Carrying Handle: No



226139 Anodised

RS PRO GREY COLD ROLLED STEEL INSTRUMENT CASE, 350 X 270 X

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: Cold Rolled Steel
 - External Length: 350 mm
 - External Width: 270 mm
 - External Height: 95 mm
 - External Dimensions: 350 x 270 x 95 mm
 - Colour: Grey
 - Ventilated: No
 - Carrying Handle: No



231992 Cold Rolled Steel

ENCLOSURE,METAL CASE,GREY,310X230X80MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: Cold Rolled Steel
 - External Length: 310 mm
 - External Width: 230 mm
 - External Height: 80 mm
 - External Dimensions: 310 x 230 x 80 mm
 - Colour: Grey
 - Ventilated: No
 - Carrying Handle: No



232002 Cold Rolled Steel

RS PRO WHITE COLD ROLLED STEEL INSTRUMENT CASE, 180 X 89 X 80MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: Cold Rolled Steel
 - External Length: 180 mm
 - External Width: 89 mm
 - External Height: 80 mm
 - External Dimensions: 180 x 89 x 80 mm
 - Colour: White
 - Ventilated: Yes
 - Carrying Handle: No



232030 Cold Rolled Steel

RS PRO WHITE COLD ROLLED STEEL INSTRUMENT CASE, 200 X 123 X 92MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Cold Rolled Steel
 - External Length: 200 mm
 - External Width: 123 mm
 - External Height: 92 mm
 - External Dimensions: 200 x 123 x 92 mm
 - Colour: White
 - Ventilated: Yes
 - Carrying Handle: No



232074 Cold Rolled Steel

RS PRO GREY COLD ROLLED STEEL INSTRUMENT CASE, 65 X 85 X 42MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Cold Rolled Steel
 - External Length: 65 mm
 - External Width: 85 mm
 - External Height: 42 mm
 - External Dimensions: 65 x 85 x 42 mm
 - Colour: Grey
 - Ventilated: No
 - Carrying Handle: No



232125 Cold Rolled Steel

RS PRO GREY COLD ROLLED STEEL INSTRUMENT CASE, 200 X 200 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Cold Rolled Steel
 - External Length: 200 mm
 - External Width: 200 mm
 - External Height: 100 mm
 - External Dimensions: 200 x 200 x 100 mm
 - Colour: Grey
 - Ventilated: No
 - Carrying Handle: No



232197 Cold Rolled Steel

RS PRO GREY COLD ROLLED STEEL INSTRUMENT CASE, 200 X 150 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Cold Rolled Steel
 - External Length: 200 mm
 - External Width: 150 mm
 - External Height: 90 mm
 - External Dimensions: 200 x 150 x 90 mm
 - Colour: Grey
 - Ventilated: No
 - Carrying Handle: No



232204 Cold Rolled Steel

RS PRO GREY COLD ROLLED STEEL INSTRUMENT CASE, 120 X 150 X 80MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Cold Rolled Steel
 - External Length: 120 mm
 - External Width: 150 mm
 - External Height: 80 mm
 - External Dimensions: 120 x 150 x 80 mm
 - Colour: Grey
 - Ventilated: No
 - Carrying Handle: No



232210 Cold Rolled Steel

ENCLOSURE, METAL CASE, GREY, C/W INTEGRAL HANDLE, ALUMINIUM FRONT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Cold Rolled Steel
 - External Length: 245 mm
 - External Width: 105 mm
 - External Height: 137 mm
 - External Dimensions: 245 x 137 x 105 mm
 - Colour: Grey
 - Ventilated: No
 - Carrying Handle: Yes



232260 Cold Rolled Steel

RS PRO GREY COLD ROLLED STEEL INSTRUMENT CASE, 204 X 152 X 76MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Cold Rolled Steel
 - External Length: 204 mm
 - External Width: 152 mm
 - External Height: 76 mm
 - External Dimensions: 204 x 152 x 76 mm
 - Colour: Grey
 - Ventilated: No
 - Carrying Handle: No



232232 Cold Rolled Steel

RS PRO GREY COLD ROLLED STEEL INSTRUMENT CASE, 300 X 200 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Cold Rolled Steel
 - External Length: 300 mm
 - External Width: 200 mm
 - External Height: 100 mm
 - External Dimensions: 300 x 200 x 100 mm
 - Colour: Grey
 - Ventilated: No
 - Carrying Handle: No



232276 Cold Rolled Steel

RS PRO GREY COLD ROLLED STEEL INSTRUMENT CASE, 406 X 197 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Cold Rolled Steel
 - External Length: 406 mm
 - External Width: 197 mm
 - External Height: 159 mm
 - External Dimensions: 406 x 197 x 159 mm
 - Colour: Grey
 - Ventilated: No
 - Carrying Handle: No



232282 Cold Rolled Steel

RS PRO GREY COLD ROLLED STEEL INSTRUMENT CASE, 254 X 197 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Cold Rolled Steel
 - External Length: 254 mm
 - External Width: 197 mm
 - External Height: 159 mm
 - External Dimensions: 254 x 197 x 159 mm
 - Colour: Grey
 - Ventilated: No
 - Carrying Handle: No



232311 Cold Rolled Steel

RS PRO GREY, ALUMINIUM & STEEL INSTRUMENT CASE, 432 X 200 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Aluminium, Steel
 - External Length: 432 mm
 - External Width: 200 mm
 - External Height: 88 mm
 - External Dimensions: 432 x 200 x 88 mm
 - Colour: Grey
 - Ventilated: No
 - Carrying Handle: No



232298 Aluminium, Steel

ENCLOSURE, POLYSTYRENE, INSTRUMENT CASE, LIGHT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 190 mm
 - External Width: 200 mm
 - External Height: 80 mm
 - External Dimensions: 190 x 140 x 80 mm
 - Colour: Grey
 - IP Rating: IP54
 - Ventilated: No



315933 ABS

RS PRO GREY ABS INSTRUMENT CASE, 190 X 140 X 60MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 190 mm
 - External Width: 140 mm
 - External Height: 60 mm
 - External Dimensions: 190 x 140 x 60 mm
 - Colour: Grey
 - IP Rating: IP54
 - Ventilated: No



315961 ABS

ENCLOSURE, INSTRUMENT CASE, DIN 43700, 96X48X138MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Noryl
 - External Length: 138 mm
 - External Width: 96 mm
 - External Height: 48 mm
 - External Dimensions: 48 x 96 x 138 mm
 - Colour: Black
 - Ventilated: No
 - Carrying Handle: No



500005 Noryl

ENCLOSURE, INSTRUMENT CASE, DIN 43700, 96X96X138MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Noryl
 - External Length: 138 mm
 - External Width: 96 mm
 - External Height: 96 mm
 - External Dimensions: 96 x 96 x 138 mm
 - Colour: Black
 - Ventilated: No
 - Carrying Handle: No



500011 Noryl

ENCLOSURE, INSTRUMENT CASE, DIN 43700, 72X72X138MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Noryl
 - External Length: 116 mm
 - External Width: 72 mm
 - External Height: 72 mm
 - External Dimensions: 72 x 72 x 116 mm
 - Colour: Black
 - Ventilated: No
 - Carrying Handle: No



500027 Noryl

ENCLOSURE, INSTRUMENT CASE, DIN 43700, 144x72x138MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: Noryl
 - External Length: 144 mm
 - External Width: 138 mm
 - External Height: 72 mm
 - External Dimensions: 72 x 138 x 144 mm
 - Colour: Black
 - Ventilated: No
 - Carrying Handle: No



500033 Noryl

ENCLOSURE, INSTRUMENT CASE, DIN 43700, 144x96x138MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: Noryl
 - External Length: 144 mm
 - External Width: 138 mm
 - External Height: 96 mm
 - External Dimensions: 96 x 138 x 144 mm
 - Colour: Black
 - Ventilated: No
 - Carrying Handle: No



500049 Noryl

RS PRO BLACK ANODISED ALUMINIUM INSTRUMENT CASE, 165 X

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: Anodised Aluminium
 - External Length: 165 mm
 - External Width: 105 mm
 - External Height: 61 mm
 - External Dimensions: 165 x 105 x 61 mm
 - Colour: Black
 - Ventilated: Yes
 - Carrying Handle: No



1853209 Anodised

RS PRO INSTRUMENT CASE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 40 mm
 - Width: 30 mm
 - Material: ABS



1951523 40 mm

RS PRO INSTRUMENT CASE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 40 mm
 - Width: 16 mm
 - Material: Aluminium



1951535 40 mm

RS PRO BLACK ALUMINIUM INSTRUMENT CASE, 120 X 63.5 X

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: Aluminium
 - External Length: 120 mm
 - External Width: 63.5 mm
 - External Height: 30 mm
 - External Dimensions: 120 x 63.5 x 30 mm
 - Colour: Black



1951537 Aluminium

RS PRO SILVER ANODISED ALUMINIUM INSTRUMENT CASE, 80 X

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: Anodised Aluminium
 - External Length: 80 mm
 - External Width: 63.5 mm
 - External Height: 30 mm
 - External Dimensions: 80 x 63.5 x 30 mm
 - Colour: Silver



1951540 Anodised

RS PRO SILVER ANODISED ALUMINIUM INSTRUMENT CASE, 80 X

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: Anodised Aluminium
 - External Length: 80 mm
 - External Width: 108.5 mm
 - External Height: 45 mm
 - External Dimensions: 80 x 108.5 x 45 mm
 - Colour: Silver



1951545 Anodised

RS PRO SILVER ANODISED ALUMINIUM INSTRUMENT CASE, 160 X

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: Anodised Aluminium
 - External Length: 160 mm
 - External Width: 108.5 mm
 - External Height: 45 mm
 - External Dimensions: 160 x 108.5 x 45 mm
 - Colour: Silver



1951546 Anodised

RS PRO SILVER ANODISED ALUMINIUM INSTRUMENT CASE, 220 X

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: Anodised Aluminium
 - External Length: 220 mm
 - External Width: 108.5 mm
 - External Height: 45 mm
 - External Dimensions: 220 x 108.5 x 45 mm
 - Colour: Silver



1951547 Anodised

RS PRO SILVER ANODISED ALUMINIUM INSTRUMENT CASE, 160 X

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: Anodised Aluminium
 - External Length: 160 mm
 - External Width: 169.8 mm
 - External Height: 53.8 mm
 - External Dimensions: 160 x 169.8 x 53.8 mm
 - Colour: Silver



1951549 Anodised

RS PRO SILVER ANODISED ALUMINIUM INSTRUMENT CASE, 220 X

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: Anodised Aluminium
 - External Length: 220 mm
 - External Width: 169.8 mm
 - External Height: 53.8 mm
 - External Dimensions: 220 x 169.8 x 53.8 mm
 - Colour: Silver



1951550 Anodised

RS PRO BLACK ABS INSTRUMENT CASE, 105 X 80 X 40MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: ABS
 - External Length: 105 mm
 - External Width: 80 mm
 - External Height: 40 mm
 - External Dimensions: 105 x 80 x 40 mm
 - Colour: Black



1981379 ABS

RS PRO BEIGE ABS INSTRUMENT CASE, 105 X 80 X 40MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: ABS
 - External Length: 105 mm
 - External Width: 80 mm
 - External Height: 40 mm
 - External Dimensions: 105 x 80 x 40 mm
 - Colour: Beige



1981378 ABS

RS PRO BEIGE ABS INSTRUMENT CASE, 50 X 100 X 130MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: ABS
 - External Length: 50 mm
 - External Width: 100 mm
 - External Height: 130 mm
 - External Dimensions: 50 x 100 x 130 mm
 - Colour: Beige



1981386 ABS

RS PRO BEIGE ABS INSTRUMENT CASE, 70 X 140 X 190MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: ABS
 - External Length: 70 mm
 - External Width: 140 mm
 - External Height: 190 mm
 - External Dimensions: 70 x 140 x 190 mm
 - Colour: Beige



1981388 ABS

RS PRO BEIGE ABS INSTRUMENT CASE, 30 X 140 X 190MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 30 mm
 - External Width: 140 mm
 - External Height: 190 mm
 - External Dimensions: 30 x 140 x 190 mm
 - Colour: Beige



1981390 ABS

RS PRO BEIGE ABS INSTRUMENT CASE, 100 X 180 X 250MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 100 mm
 - External Width: 180 mm
 - External Height: 250 mm
 - External Dimensions: 100 x 180 x 250 mm
 - Colour: Beige



1981391 ABS

RS PRO BEIGE ABS INSTRUMENT CASE, 75 X 180 X 250MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 75 mm
 - External Width: 180 mm
 - External Height: 250 mm
 - External Dimensions: 75 x 180 x 250 mm
 - Colour: Beige



1981392 ABS

RS PRO WHITE ABS INSTRUMENT CASE, 159 X 205 X 64MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 159 mm
 - External Width: 205 mm
 - External Height: 64 mm
 - External Dimensions: 159 x 205 x 64 mm
 - Colour: White
 - Ventilated: No
 - Carrying Handle: No



2205566 ABS

RS PRO BLACK ABS INSTRUMENT CASE, 231 X 212 X 67MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 231 mm
 - External Width: 212 mm
 - External Height: 67 mm
 - External Dimensions: 231 x 212 x 67 mm
 - Colour: Black
 - Ventilated: No
 - Carrying Handle: No



2374426 ABS

ENCLOSURE,CASE,PLASTIC,ABS,CF-275-000

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 231 mm
 - External Width: 212 mm
 - External Height: 80 mm
 - External Dimensions: 231 x 212 x 80 mm
 - Colour: Black
 - Ventilated: No
 - Carrying Handle: No



2374432 ABS

ENCLOSURE,CASE,PLASTIC,ABS,DM2-039

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 291 mm
 - External Width: 264 mm
 - External Height: 60 mm
 - External Dimensions: 291 x 264 x 60 mm
 - Colour: White
 - Ventilated: No
 - Carrying Handle: No



2374454 ABS

ENCLOSURE,CASE,PLASTIC,ABS,DM3-039

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 291 mm
 - External Width: 264 mm
 - External Height: 86 mm
 - External Dimensions: 291 x 264 x 86 mm
 - Colour: White
 - Ventilated: No
 - Carrying Handle: No



2374460 ABS

ENCLOSURE,CASE,PLASTIC,ABS,DM4-039

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: ABS
 - External Length: 291 mm
 - External Width: 264 mm
 - External Height: 111 mm
 - External Dimensions: 291 x 264 x 111 mm
 - Colour: White
 - Ventilated: No
 - Carrying Handle: No



2374476 ABS

RS PRO BLACK ANODISED ALUMINIUM INSTRUMENT CASE, 285 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Anodised Aluminium
 - External Length: 285 mm
 - External Width: 81.4 mm
 - External Height: 40 mm
 - External Dimensions: 285 x 81.4 x 40 mm
 - Colour: Black
 - Ventilated: Yes
 - Carrying Handle: No



4687471 Anodised

RS PRO GREY STEEL INSTRUMENT CASE, 178 X 305 X 65MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Steel
 - External Length: 178 mm
 - External Width: 305 mm
 - External Height: 65 mm
 - External Dimensions: 178 x 305 x 65 mm
 - Colour: Grey
 - Ventilated: Yes
 - Carrying Handle: No



7545951 Steel

1.5UX178DX203W ELECTRONIC ENCLOSURE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Steel
 - External Length: 178 mm
 - External Width: 203 mm
 - External Height: 65 mm
 - External Dimensions: 178 x 203 x 65 mm
 - Colour: Black
 - Ventilated: Yes
 - Carrying Handle: No



7545957 Steel

1.5UX279DX203W ELECTRONIC ENCLOSURE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Steel
 - External Length: 279 mm
 - External Width: 203 mm
 - External Height: 65 mm
 - External Dimensions: 279 x 203 x 65 mm
 - Colour: Black
 - Ventilated: Yes
 - Carrying Handle: No



7545963 Steel

RS PRO BLACK STEEL INSTRUMENT CASE, 178 X 305 X 87MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Steel
 - External Length: 178 mm
 - External Width: 305 mm
 - External Height: 87 mm
 - External Dimensions: 178 x 305 x 87 mm
 - Colour: Black
 - Ventilated: Yes
 - Carrying Handle: No



7545973 Steel

RS PRO BLACK STEEL INSTRUMENT CASE, 279 X 305 X 87MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Steel
 - External Length: 279 mm
 - External Width: 305 mm
 - External Height: 87 mm
 - External Dimensions: 279 x 305 x 87 mm
 - Colour: Black
 - Ventilated: Yes
 - Carrying Handle: No



7545985 Steel

RS PRO BLACK STEEL INSTRUMENT CASE, 279 X 432 X 87MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Steel
 - External Length: 279 mm
 - External Width: 432 mm
 - External Height: 87 mm
 - External Dimensions: 279 x 432 x 87 mm
 - Colour: Black
 - Ventilated: Yes
 - Carrying Handle: No



7545989 Steel

RS PRO BLACK STEEL PROJECT BOX, 279 X 203 X 131MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Steel
 - External Length: 279 mm
 - External Width: 203 mm
 - External Height: 131 mm
 - External Dimensions: 279 x 203 x 131 mm
 - Colour: Black
 - Ventilated: Yes
 - Carrying Handle: No



7545995 Steel

RS PRO GREY STEEL INSTRUMENT CASE, 279 X 432 X 131MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Steel
 - External Length: 279 mm
 - External Width: 432 mm
 - External Height: 131 mm
 - External Dimensions: 279 x 432 x 131 mm
 - Colour: Grey
 - Ventilated: Yes
 - Carrying Handle: No



7546001 Steel

RS PRO BEIGE, GREY STEEL INSTRUMENT CASE, 178 X 305 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Steel
 - External Length: 178 mm
 - External Width: 305 mm
 - External Height: 175 mm
 - External Dimensions: 178 x 305 x 175 mm
 - Colour: Beige, Grey
 - Ventilated: Yes
 - Carrying Handle: No



7546005 Steel

3UX279DX305W ELECTRONIC ENCLOSURE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Steel
 - External Length: 279 mm
 - External Width: 305 mm
 - External Height: 131 mm
 - External Dimensions: 279 x 305 x 131 mm
 - Colour: RAL 7035 Light Grey
 - Ventilated: Yes
 - Carrying Handle: No



7546008 Steel

4UX279DX203W ELECTRONIC ENCLOSURE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Steel
 - External Length: 279 mm
 - External Width: 203 mm
 - External Height: 175 mm
 - External Dimensions: 279 x 203 x 175 mm
 - Colour: Black
 - Ventilated: Yes
 - Carrying Handle: No



7546017 Steel

5UX279DX203W ELECTRONIC ENCLOSURE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Steel
 - External Length: 279 mm
 - External Width: 203 mm
 - External Height: 219 mm
 - External Dimensions: 279 x 203 x 219 mm
 - Colour: Black
 - Ventilated: Yes
 - Carrying Handle: No



7546023 Steel

RS PRO GREY STEEL INSTRUMENT CASE, 279 X 432 X 219MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Body Material: Steel
 - External Length: 279 mm
 - External Width: 432 mm
 - External Height: 219 mm
 - External Dimensions: 279 x 432 x 219 mm
 - Colour: Grey
 - Ventilated: Yes
 - Carrying Handle: No



7546036 Steel

RS PRO RAL 7032 STEEL JUNCTION BOX, IP66, 300 X 200 X 120MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Dimensions [L x W x H]: 300 x 200 x 120 mm
 - Material: Steel
 - Length: 300 mm
 - Width: 200 mm
 - Height: 120 mm
 - IP Rating: IP66
 - Colour: RAL 7032



122030 300 x 200 x 120

RS PRO RAL 7032 STEEL JUNCTION BOX, IP66, 400 X 200 X 120MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Dimensions [L x W x H]: 400 x 200 x 120 mm
 - Material: Steel
 - Length: 400 mm
 - Width: 200 mm
 - Height: 120 mm
 - IP Rating: IP66
 - Colour: RAL 7032



122046 400 x 200 x 120

RS PRO RAL 7032 STEEL JUNCTION BOX, IP66, 300 X 300 X 120MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Dimensions [L x W x H]: 300 x 300 x 120 mm
 - Material: Steel
 - Length: 300 mm
 - Width: 300 mm
 - Height: 120 mm
 - IP Rating: IP66
 - Colour: RAL 7032



122052 300 x 300 x 120

RS PRO RAL 7032 STEEL JUNCTION BOX, IP66, 400 X 300 X 120MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Dimensions [L x W x H]: 400 x 300 x 120 mm
 - Material: Steel
 - Length: 400 mm
 - Width: 300 mm
 - Height: 120 mm
 - IP Rating: IP66
 - Colour: RAL 7032



122068 400 x 300 x 120

RS PRO RAL 7032 STEEL JUNCTION BOX, IP66, 200 X 200 X 120MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Dimensions [L x W x H]: 200 x 200 x 120 mm
 - Material: Steel
 - Length: 200 mm
 - Width: 200 mm
 - Height: 120 mm
 - IP Rating: IP66
 - Colour: RAL 7032



122096 200 x 200 x 120

RS PRO RAL 7032 STEEL JUNCTION BOX, IP66, 150 X 150 X 80MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Dimensions [L x W x H]: 150 x 150 x 80 mm
 - Material: Steel
 - Length: 150 mm
 - Width: 150 mm
 - Height: 80 mm
 - IP Rating: IP66
 - Colour: RAL 7032



122103 150 x 150 x 80 mm

RS PRO RAL 7032 STEEL JUNCTION BOX, IP66, 300 X 150 X 80MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Dimensions [L x W x H]: 300 x 150 x 80 mm
 - Material: Steel
 - Length: 300 mm
 - Width: 150 mm
 - Height: 80 mm
 - IP Rating: IP66
 - Colour: RAL 7032



122119 300 x 150 x 80

ENCLOSURE, ELECTRICAL, INDUSTRIAL, TERMINAL, INLINE, 200X200X80MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Dimensions [L x W x H]: 200 x 200 x 80 mm
 - Material: Steel
 - Length: 200 mm
 - Width: 200 mm
 - Height: 80 mm
 - IP Rating: IP66
 - Colour: RAL 7032



122125 200 x 200 x 80

RS PRO RAL 7032 STEEL JUNCTION BOX, IP66, 300 X 200 X 80MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Dimensions [L x W x H]: 300 x 200 x 80 mm
 - Material: Steel
 - Length: 300 mm
 - Width: 200 mm
 - Height: 80 mm
 - IP Rating: IP66
 - Colour: RAL 7032



122131 300 x 200 x 80

RS PRO RAL 7032 STEEL JUNCTION BOX, IP66, 400 X 200 X 80MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Dimensions [L x W x H]: 400 x 200 x 80 mm
 - Material: Steel
 - Length: 400 mm
 - Width: 200 mm
 - Height: 80 mm
 - IP Rating: IP66
 - Colour: RAL 7032



122147 400 x 200 x 80

RS PRO RAL 7032 STEEL JUNCTION BOX, IP66, 300 X 150 X 120MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Dimensions [L x W x H]: 300 x 150 x 120 mm
 - Material: Steel
 - Length: 300 mm
 - Width: 150 mm
 - Height: 120 mm
 - IP Rating: IP66
 - Colour: RAL 7032



122153 300 x 150 x 120

RS PRO BLUE JUNCTION BOX, IP66, 150 X 150 X 80MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Dimensions [L x W x H]: 150 x 150 x 80 mm
 - Length: 150 mm
 - Width: 150 mm
 - Height: 80 mm
 - IP Rating: IP66
 - Colour: Blue
 - Number of Ways: 0
 - Series: TLX



1441348 150 x 150 x 80 mm

RS PRO BLACK JUNCTION BOX, IP66, ATEX, IECEx, 80 X 75 X 55MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Dimensions [L x W x H]: 80 x 75 x 55 mm
 - Length: 80 mm
 - Width: 75 mm
 - Height: 55 mm
 - IP Rating: IP66
 - Colour: Black
 - Hazardous Area Certification: ATEX, IECEx



1444450 80 x 75 x 55 mm

RS PRO BLACK JUNCTION BOX, IP66, ATEX, IECEx, 110 X 75 X 55MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Dimensions [L x W x H]: 110 x 75 x 55 mm
 - Length: 110 mm
 - Width: 75 mm
 - Height: 55 mm
 - IP Rating: IP66
 - Colour: Black
 - Hazardous Area Certification: ATEX, IECEx



1444451 110 x 75 x 55 mm

RS PRO BLACK JUNCTION BOX, IP66, ATEX, IECEx, 122 X 120 X 90MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Dimensions [L x W x H]: 122 x 120 x 90 mm
 - Length: 122 mm
 - Width: 120 mm
 - Height: 90 mm
 - IP Rating: IP66
 - Colour: Black
 - Hazardous Area Certification: ATEX, IECEx



1444452 122 x 120 x 90 mm

RS PRO BLACK JUNCTION BOX, IP66, ATEX, IECEx, 160 X 75 X 55MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Dimensions [L x W x H]: 160 x 75 x 55 mm
 - Length: 160 mm
 - Width: 75 mm
 - Height: 55 mm
 - IP Rating: IP66
 - Colour: Black
 - Hazardous Area Certification: ATEX, IECEx



1444453 160 x 75 x 55 mm

RS PRO BLACK JUNCTION BOX, IP66, ATEX, IECEx, 160 X 75 X 75MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Dimensions [L x W x H]: 160 x 75 x 75 mm
 - Length: 160 mm
 - Width: 75 mm
 - Height: 75 mm
 - IP Rating: IP66
 - Colour: Black
 - Hazardous Area Certification: ATEX, IECEx



1444454 160 x 75 x 75 mm

RS PRO BLACK JUNCTION BOX, IP66, ATEX, IECEx, 160 X 160 X 90MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Dimensions [L x W x H]: 160 x 160 x 90 mm
 - Length: 160 mm
 - Width: 160 mm
 - Height: 90 mm
 - IP Rating: IP66
 - Colour: Black
 - Hazardous Area Certification: ATEX, IECEx



1444455 160 x 160 x 90 mm

RS PRO BLACK JUNCTION BOX, IP66, ATEX, IECEx, 190 X 75 X 55MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Dimensions [L x W x H]: 190 x 75 x 55 mm
 - Length: 190 mm
 - Width: 75 mm
 - Height: 55 mm
 - IP Rating: IP66
 - Colour: Black
 - Hazardous Area Certification: ATEX, IECEx



1444456 190 x 75 x 55 mm

RS PRO BLACK JUNCTION BOX, IP66, ATEX, IECEx, 220 X 120 X 90MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Dimensions [L x W x H]: 220 x 120 x 90 mm
 - Length: 220 mm
 - Width: 120 mm
 - Height: 90 mm
 - IP Rating: IP66
 - Colour: Black
 - Hazardous Area Certification: ATEX, IECEx



1444457 220 x 120 x 90

RS PRO BLACK JUNCTION BOX, IP66, ATEX, IECEx, 255 X 250 X 120MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Dimensions [L x W x H]: 255 x 250 x 120 mm
 - Length: 255 mm
 - Width: 250 mm
 - Height: 120 mm
 - IP Rating: IP66
 - Colour: Black
 - Hazardous Area Certification: ATEX, IECEx



1444458 255 x 250 x 120

RS PRO BLACK JUNCTION BOX, IP66, ATEX, IECEx, 260 X 160 X 90MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Dimensions [L x W x H]: 260 x 160 x 90 mm
 - Length: 260 mm
 - Width: 160 mm
 - Height: 90 mm
 - IP Rating: IP66
 - Colour: Black
 - Hazardous Area Certification: ATEX, IECEx



1444459 260 x 160 x 90

RS PRO BLACK JUNCTION BOX, IP66, ATEX, IECEx, 360 X 160 X 90MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Dimensions [L x W x H]: 360 x 160 x 90 mm
 - Length: 360 mm
 - Width: 160 mm
 - Height: 90 mm
 - IP Rating: IP66
 - Colour: Black
 - Hazardous Area Certification: ATEX, IECEx



1444460 360 x 160 x 90

RS PRO BLACK JUNCTION BOX, IP66, ATEX, IECEx, 400 X 250 X 120MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Dimensions [L x W x H]: 400 x 250 x 120 mm
 - Length: 400 mm
 - Width: 250 mm
 - Height: 120 mm
 - IP Rating: IP66
 - Colour: Black
 - Hazardous Area Certification: ATEX, IECEx



1444461 400 x 250 x 120

RS PRO BLACK JUNCTION BOX, IP66, ATEX, IECEx, 400 X 405 X 120MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Dimensions [L x W x H]: 400 x 405 x 120 mm
 - Length: 400 mm
 - Width: 405 mm
 - Height: 120 mm
 - IP Rating: IP66
 - Colour: Black
 - Hazardous Area Certification: ATEX, IECEx



1444462 400 x 405 x 120

RS PRO UNPAINTED STAINLESS STEEL TERMINAL BOX, IP66, 400 X 120 X

- ขนาดบรรจุภัณฑ์: 1 x EA
- Dimensions (L x W x H): 400 x 120 x 200 mm
 - Material: Stainless Steel
 - Length: 400 mm
 - Width: 120 mm
 - Height: 200 mm
 - IP Rating: IP66
 - Colour: Unpainted



7491848 400 x 120 x 200

RS PRO UNPAINTED STAINLESS STEEL TERMINAL BOX, IP66, 200 X 120 X

- ขนาดบรรจุภัณฑ์: 1 x EA
- Dimensions (L x W x H): 200 x 120 x 200 mm
 - Material: Stainless Steel
 - Length: 200 mm
 - Width: 120 mm
 - Height: 200 mm
 - IP Rating: IP66
 - Colour: Unpainted



7491854 200 x 120 x 200

S/STEEL 304 TERMINAL BOX 150X150X80MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Dimensions (L x W x H): 150 x 80 x 150 mm
 - Material: Stainless Steel
 - Length: 150 mm
 - Width: 80 mm
 - Height: 150 mm
 - IP Rating: IP66
 - Colour: Unpainted



7491857 150 x 80 x 150 mm

RS PRO UNPAINTED STAINLESS STEEL TERMINAL BOX, IP66, 150 X 80 X

- ขนาดบรรจุภัณฑ์: 1 x EA
- Dimensions (L x W x H): 150 x 80 x 150 mm
 - Material: Stainless Steel
 - Length: 150 mm
 - Width: 80 mm
 - Height: 150 mm
 - IP Rating: IP66
 - Colour: Unpainted



7491860 150 x 80 x 150 mm

RS PRO UNPAINTED STAINLESS STEEL TERMINAL BOX, IP66, 300 X 80 X

- ขนาดบรรจุภัณฑ์: 1 x EA
- Dimensions (L x W x H): 300 x 80 x 150 mm
 - Material: Stainless Steel
 - Length: 300 mm
 - Width: 80 mm
 - Height: 150 mm
 - IP Rating: IP66
 - Colour: Unpainted



7491863 300 x 80 x 150

RS PRO UNPAINTED STAINLESS STEEL TERMINAL BOX, IP66, 200 X 200 X

- ขนาดบรรจุภัณฑ์: 1 x EA
- Dimensions (L x W x H): 200 x 200 x 80 mm
 - Material: Stainless Steel
 - Length: 200 mm
 - Width: 80 mm
 - Height: 200 mm
 - IP Rating: IP66
 - Colour: Unpainted



7491866 200 x 200 x 80

RS PRO UNPAINTED STAINLESS STEEL TERMINAL BOX, IP66, 300 X 80 X

- ขนาดบรรจุภัณฑ์: 1 x EA
- Dimensions (L x W x H): 300 x 80 x 200 mm
 - Material: Stainless Steel
 - Length: 300 mm
 - Width: 80 mm
 - Height: 200 mm
 - IP Rating: IP66
 - Colour: Unpainted



7491876 300 x 80 x 200

RS PRO RAL 7035 LIGHT GREY MILD STEEL TERMINAL BOX, IP66, 150 X 80 X

- ขนาดบรรจุภัณฑ์: 1 x EA
- Dimensions (L x W x H): 150 x 80 x 150 mm
 - Material: Mild Steel
 - Length: 150 mm
 - Width: 80 mm
 - Height: 150 mm
 - IP Rating: IP66
 - Colour: RAL 7035 Light Grey



7491888 150 x 80 x 150 mm

RS PRO RAL 7035 LIGHT GREY MILD STEEL TERMINAL BOX, IP66, 300 X 120 X

- ขนาดบรรจุภัณฑ์: 1 x EA
- Dimensions (L x W x H): 300 x 120 x 200 mm
 - Material: Mild Steel
 - Length: 300 mm
 - Width: 120 mm
 - Height: 200 mm
 - IP Rating: IP66
 - Colour: RAL 7035 Light Grey



7491891 300 x 120 x 200

RS PRO RAL 7035 LIGHT GREY MILD STEEL TERMINAL BOX, IP66, 300 X 150 X

- ขนาดบรรจุภัณฑ์: 1 x EA
- Dimensions (L x W x H): 300 x 120 x 150 mm
 - Material: Mild Steel
 - Length: 300 mm
 - Width: 120 mm
 - Height: 150 mm
 - IP Rating: IP66
 - Colour: RAL 7035 Light Grey



7491894 300 x 120 x 150

RS PRO UNPAINTED STAINLESS STEEL TERMINAL BOX, IP66, 300 X 150 X

- ขนาดบรรจุภัณฑ์: 1 x EA
- Dimensions (L x W x H): 300 x 150 x 80 mm
 - Material: Stainless Steel
 - Length: 300 mm
 - Width: 150 mm
 - Height: 80 mm
 - IP Rating: IP66
 - Colour: Unpainted



7587046 300 x 150 x 80

RS PRO UNPAINTED STAINLESS STEEL TERMINAL BOX, IP66, 200 X 200 X

- ขนาดบรรจุภัณฑ์: 1 x EA
- Dimensions (L x W x H): 200 x 200 x 80 mm
 - Material: Stainless Steel
 - Length: 200 mm
 - Width: 200 mm
 - Height: 80 mm
 - IP Rating: IP66
 - Colour: Unpainted



7587052 200 x 200 x 80

RS PRO UNPAINTED STAINLESS STEEL TERMINAL BOX, IP66, 300 X 150 X

- ขนาดบรรจุภัณฑ์: 1 x EA
- Dimensions (L x W x H): 300 x 150 x 120 mm
 - Material: Stainless Steel
 - Length: 300 mm
 - Width: 150 mm
 - Height: 120 mm
 - IP Rating: IP66
 - Colour: Unpainted



7587056 300 x 150 x 120

RS PRO UNPAINTED STAINLESS STEEL TERMINAL BOX, IP66, 175 X 175 X

- ขนาดบรรจุภัณฑ์: 1 x EA
- Dimensions (L x W x H): 175 x 175 x 120 mm
 - Material: Stainless Steel
 - Length: 175 mm
 - Width: 175 mm
 - Height: 120 mm
 - IP Rating: IP66
 - Colour: Unpainted



7587059 175 x 175 x 120

RS PRO UNPAINTED STAINLESS STEEL TERMINAL BOX, IP66, 300 X 200 X

- ขนาดบรรจุภัณฑ์: 1 x EA
- Dimensions (L x W x H): 300 x 200 x 80 mm
 - Material: Stainless Steel
 - Length: 300 mm
 - Width: 200 mm
 - Height: 80 mm
 - IP Rating: IP66
 - Colour: Unpainted
 - Number of Ways: 0



8428302 300 x 200 x 80

IP66 TERMINAL BOX, M/STEEL, 150X150X120

- ขนาดบรรจุภัณฑ์: 1 x EA
- Dimensions (L x W x H): 150 x 150 x 120 mm
 - Material: Steel
 - Length: 150 mm
 - Width: 150 mm
 - Height: 120 mm
 - IP Rating: IP66
 - Colour: RAL 7032
 - Number of Ways: 0



8428308 150 x 150 x 120

RS PRO UNPAINTED STAINLESS STEEL TERMINAL BOX, IP66, 300 X 150 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Dimensions (L x W x H): 300 x 150 x 80 mm
- Material: Stainless Steel
- Length: 300 mm
- Width: 150 mm
- Height: 80 mm
- IP Rating: IP66
- Colour: Unpainted
- Number of Ways: 0



8428311 300 x 150 x 80

RS PRO UNPAINTED STAINLESS STEEL TERMINAL BOX, IP66, 200 X 200 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Dimensions (L x W x H): 200 x 200 x 80 mm
- Material: Stainless Steel
- Length: 200 mm
- Width: 200 mm
- Height: 80 mm
- IP Rating: IP66
- Colour: Unpainted
- Number of Ways: 0



8428314 200 x 200 x 80

RS PRO UNPAINTED STAINLESS STEEL TERMINAL BOX, IP66, 300 X 150 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Dimensions (L x W x H): 300 x 150 x 120 mm
- Material: Stainless Steel
- Length: 300 mm
- Width: 150 mm
- Height: 120 mm
- IP Rating: IP66
- Colour: Unpainted
- Number of Ways: 0



8428318 300 x 150 x 120

RS PRO UNPAINTED STAINLESS STEEL TERMINAL BOX, IP66, 300 X 200 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Dimensions (L x W x H): 300 x 200 x 120 mm
- Material: Stainless Steel
- Length: 300 mm
- Width: 200 mm
- Height: 120 mm
- IP Rating: IP66
- Colour: Unpainted
- Number of Ways: 0



8428320 300 x 200 x 120

RS PRO UNPAINTED STAINLESS STEEL TERMINAL BOX, IP66, 400 X 200 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Dimensions (L x W x H): 400 x 200 x 120 mm
- Material: Stainless Steel
- Length: 400 mm
- Width: 200 mm
- Height: 120 mm
- IP Rating: IP66
- Colour: Unpainted
- Number of Ways: 0



8428324 400 x 200 x 120

RS PRO UNPAINTED STAINLESS STEEL TERMINAL BOX, IP66, 175 X 175 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Dimensions (L x W x H): 175 x 175 x 120 mm
- Material: Stainless Steel
- Length: 175 mm
- Width: 175 mm
- Height: 120 mm
- IP Rating: IP66
- Colour: Unpainted
- Number of Ways: 0



8428327 175 x 175 x 120

IP66 TERMINAL BOX, S/STEEL, 150X150X80

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Dimensions (L x W x H): 150 x 150 x 80 mm
- Material: Stainless Steel
- Length: 150 mm
- Width: 150 mm
- Height: 80 mm
- IP Rating: IP66
- Colour: Unpainted
- Number of Ways: 0



8428330 150 x 150 x 80 mm

RS PRO UNPAINTED STAINLESS STEEL TERMINAL BOX, IP66, 300 X 300 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Dimensions (L x W x H): 300 x 300 x 120 mm
- Material: Stainless Steel
- Length: 300 mm
- Width: 300 mm
- Height: 120 mm
- IP Rating: IP66
- Colour: Unpainted
- Number of Ways: 0



8428333 300 x 300 x 120

RS PRO UNPAINTED STAINLESS STEEL TERMINAL BOX, IP66, 200 X 200 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Dimensions (L x W x H): 200 x 200 x 120 mm
- Material: Stainless Steel
- Length: 200 mm
- Width: 200 mm
- Height: 120 mm
- IP Rating: IP66
- Colour: Unpainted
- Number of Ways: 0



8428336 200 x 200 x 120

RS PRO RAL 7032 STEEL JUNCTION BOX, IP65, 150 X 150 X 120MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Dimensions (L x W x H): 150 x 150 x 120 mm
- Material: Steel
- Length: 150 mm
- Width: 150 mm
- Height: 120 mm
- IP Rating: IP65
- Colour: RAL 7032
- Number of Ways: 0



8428481 150 x 150 x 120

RS PRO RAL 7032 STEEL JUNCTION BOX, IP65, 150 X 300 X 80MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Dimensions (L x W x H): 150 x 300 x 80 mm
- Material: Steel
- Length: 150 mm
- Width: 300 mm
- Height: 80 mm
- IP Rating: IP65
- Colour: RAL 7032
- Number of Ways: 0



8428490 150 x 300 x 80

RS PRO RAL 7032 STEEL JUNCTION BOX, IP65, 150 X 300 X 120MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Dimensions (L x W x H): 150 x 300 x 120 mm
- Material: Steel
- Length: 150 mm
- Width: 300 mm
- Height: 120 mm
- IP Rating: IP65
- Colour: RAL 7032
- Number of Ways: 0



8428493 150 x 300 x 120

RS PRO RAL 7032 STEEL JUNCTION BOX, IP65, 200 X 200 X 120MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Dimensions (L x W x H): 200 x 200 x 120 mm
- Material: Steel
- Length: 200 mm
- Width: 200 mm
- Height: 120 mm
- IP Rating: IP65
- Colour: RAL 7032
- Number of Ways: 0



8428497 200 x 200 x 120

RS PRO RAL 7032 STEEL JUNCTION BOX, IP65, 300 X 300 X 120MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Dimensions (L x W x H): 300 x 300 x 120 mm
- Material: Steel
- Length: 300 mm
- Width: 300 mm
- Height: 120 mm
- IP Rating: IP65
- Colour: RAL 7032
- Number of Ways: 0



8428500 300 x 300 x 120

RS PRO RAL 7032 STEEL JUNCTION BOX, IP65, 200 X 300 X 120MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Dimensions (L x W x H): 200 x 300 x 120 mm
- Material: Steel
- Length: 200 mm
- Width: 300 mm
- Height: 120 mm
- IP Rating: IP65
- Colour: RAL 7032
- Number of Ways: 0



8428507 200 x 300 x 120

RS PRO BLACK LOCKING HANDLE, COMPRESSION LATCH

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Handle Style: Compression Latch
- Handle Length: 48.4 mm
- Colour: Black



1927132 Compression

RS PRO BLACK LOCKING HANDLE, T-HANDLE

- ขนาดบรรจุภัณฑ์: 1 x EA
 • Handle Style: T-Handle
 • Handle Length: 17 mm
 • Colour: Black



1927133 T-Handle

RS PRO METAL LOCKING HANDLE

- ขนาดบรรจุภัณฑ์: 1 x EA
 • Material: Metal



8428469 Metal

1U 19" CABLE ENTRY WITH BRUSH

- ขนาดบรรจุภัณฑ์: 1 x EA
 • Type: Cable Entry Panel
 • Dimensions: 483 mm x 10 mm x 1 U in
 • For Use With: 1U Rack Unit
 • Material: Steel
 • Height (U): 1 U



8020285 Cable Entry

RS PRO STEEL CABLE ENTRY PANEL FOR USE WITH 2U RACK UNIT, 483

- ขนาดบรรจุภัณฑ์: 1 x EA
 • Type: Cable Entry Panel
 • Dimensions: 483 mm x 10 mm x 2 U in
 • For Use With: 2U Rack Unit
 • Material: Steel
 • Height (U): 2 U



8020289 Cable Entry

RS PRO STEEL FLOOR MOUNT KIT FOR USE WITH LAB RACK KIT

- ขนาดบรรจุภัณฑ์: 1 x EA
 • Type: Floor Mount Kit
 • For Use With: Lab Rack Kit
 • Material: Steel



528961 Floor Mount Kit

ENCLOSURE, RACK, CABINET, 19IN, IEC 297, ANODISED ALUMINIUM, NATURAL

- ขนาดบรรจุภัณฑ์: 1 x EA
 • Type: Front Panel
 • Rack Units: 1 U
 • Colour: Unpainted
 • Material: Aluminium
 • Dimensions: 482.6 x 43.7 mm
 • Length: 482.6 mm
 • Width: 43.7 mm



4393198 Front Panel

ENCLOSURE, 19IN, RACK, FRONT PANEL, 2U, NATURAL

- ขนาดบรรจุภัณฑ์: 1 x EA
 • Type: Front Panel
 • Rack Units: 2 U
 • Colour: Unpainted
 • Material: Aluminium
 • Dimensions: 482.6 x 88.1 mm
 • Length: 482.6 mm
 • Width: 88.1 mm



4393205 Front Panel

RS PRO NATURAL ANODIZED ALUMINIUM FRONT PANEL, 8U, 482.6

- ขนาดบรรจุภัณฑ์: 1 x EA
 • Type: Front Panel
 • Rack Units: 8 U
 • Colour: Natural Anodized
 • Material: Aluminium
 • Dimensions: 482.6 x 177 mm
 • Length: 482.6 mm
 • Width: 177 mm



4393261 Front Panel

RS PRO GREY ALUMINIUM FRONT PANEL, 10U, 84HP, 482.6 X 443.7MM

- ขนาดบรรจุภัณฑ์: 1 x EA
 • Type: Front Panel
 • Rack Units: 10 U
 • Horizontal Pitch: 84 HP
 • Colour: Grey
 • Material: Aluminium
 • Dimensions: 482.6 x 443.7 mm
 • Length: 482.6 mm
 • Width: 443.7 mm



4393283 Front Panel

ENCLOSURE, 19IN, RACK, FRONT PANEL, 2U, BLACK

- ขนาดบรรจุภัณฑ์: 1 x EA
 • Type: Front Panel
 • Rack Units: 2 U
 • Horizontal Pitch: 21 HP
 • Colour: Black
 • Material: Aluminium
 • Dimensions: 482.6 x 88.1 mm
 • Length: 482.6 mm
 • Width: 88.1 mm



4393328 Front Panel

ENCLOSURE, 19IN, RACK, FRONT PANEL, 3U, BLACK

- ขนาดบรรจุภัณฑ์: 1 x EA
 • Type: Front Panel
 • Rack Units: 3 U
 • Colour: Black
 • Shielded: Yes
 • Material: Aluminium
 • Dimensions: 12.7 x 74 mm
 • Length: 12.7 mm
 • Width: 74 mm



4393334 Front Panel

RS PRO BLACK ALUMINIUM FRONT DOOR, 4U, 42HP, 229.6 X 139.5MM

- ขนาดบรรจุภัณฑ์: 1 x EA
 • Type: Front Door
 • Rack Units: 4 U
 • Horizontal Pitch: 42 HP
 • Hinges: Yes
 • Colour: Black
 • Material: Aluminium
 • Dimensions: 229.6 x 139.5 mm
 • Length: 229.6 mm



4393340 Front Door

RS PRO GREY STEEL BLANKING PANEL, 2U, 483 X 9MM

- ขนาดบรรจุภัณฑ์: 1 x EA
 • Type: Blanking Panel
 • Rack Units: 2 U
 • Colour: Grey
 • Material: Steel
 • Dimensions: 483 x 9 mm
 • Length: 483 mm
 • Width: 9 mm



8020229 Blanking Panel

STEEL 2U BLANKING PANEL 19", RAL9005

- ขนาดบรรจุภัณฑ์: 1 x EA
 • Type: Blanking Panel
 • Rack Units: 2 U
 • Colour: Black
 • Material: Steel
 • Dimensions: 483 x 9 mm
 • Length: 483 mm
 • Width: 9 mm



8020254 Blanking Panel

STEEL 3U BLANKING PANEL 19", RAL9005

- ขนาดบรรจุภัณฑ์: 1 x EA
 • Type: Blanking Panel
 • Rack Units: 3 U
 • Colour: Black
 • Material: Steel
 • Dimensions: 483 x 9 mm
 • Length: 483 mm
 • Width: 9 mm



8020257 Blanking Panel

RS PRO, 1U 19-INCH RACK MOUNT CASE, 44 X 254MM

- ขนาดบรรจุภัณฑ์: 1 x EA
 • Rack Units: 1 U
 • External Dimensions: 44 x 254 mm
 • External Height: 44 mm
 • External Depth: 254 mm
 • Colour: Grey
 • External Case Material: Aluminium
 • Front Panel Material: Aluminium
 • Standards Met: IEC297



224206 1 U

RS PRO, 1U 19-INCH RACK MOUNT CASE, 44 X 89MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Rack Units: 1 U
 - External Dimensions: 44 x 89 mm
 - External Height: 44 mm
 - External Depth: 89 mm
 - Colour: Grey
 - External Case Material: Aluminium
 - Front Panel Material: Aluminium
 - Standards Met: IEC297



584205 1 U

ENCLOSURE, 19IN, RACK CASE, IEC297, GREY FRONT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Rack Units: 1 U
 - External Dimensions: 44 x 153 mm
 - External Height: 44 mm
 - External Depth: 153 mm
 - Colour: Grey
 - External Case Material: Aluminium
 - Front Panel Material: Aluminium
 - Standards Met: IEC297



584211 1 U

RS PRO, 2U 19-INCH RACK MOUNT CASE, 88 X 254MM


- ขนาดบรรจุภัณฑ์: **1 x EA**
- Rack Units: 2 U
 - External Dimensions: 88 x 254 mm
 - External Height: 88 mm
 - External Depth: 254 mm
 - Colour: Grey
 - External Case Material: Aluminium
 - Front Panel Material: Aluminium
 - Standards Met: IEC297



584227 2 U

RS PRO, 3U 10.5-INCH RACK MOUNT CASE


- ขนาดบรรจุภัณฑ์: **1 x EA**
- Rack Units: 3 U
 - External Depth: 322 mm
 - Colour: Grey
 - External Case Material: Steel
 - Standards Met: RoHS



852334 3 U

RS PRO, 6U 19-INCH RACK MOUNT CASE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Rack Units: 6 U
 - External Depth: 522 mm
 - Colour: Grey
 - External Case Material: Steel
 - Standards Met: RoHS



852356 6 U

RS PRO, 1U 19-INCH RACK MOUNT CASE, 335 X 425 X 39.6MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Rack Units: 1 U
 - External Dimensions: 335 x 425 x 39.6 mm
 - External Height: 39.6 mm
 - External Width: 425 mm
 - External Depth: 335 mm
 - Colour: Black
 - External Case Material: Aluminium, Extruded Aluminium
 - Front Panel Material: Aluminium



1881314 1 U

RS PRO, 1U 19-INCH RACK MOUNT CASE, 425 X 425 X 39.6MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Rack Units: 1 U
 - External Dimensions: 425 x 425 x 39.6 mm
 - External Height: 39.6 mm
 - External Width: 425 mm
 - External Depth: 425 mm
 - Colour: Black
 - External Case Material: Aluminium, Extruded Aluminium
 - Front Panel Material: Aluminium



1881315 1 U

RS PRO, 2U 19-INCH RACK MOUNT CASE, 245 X 425 X 84MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Rack Units: 2 U
 - External Dimensions: 245 x 425 x 84 mm
 - External Height: 84 mm
 - External Width: 425 mm
 - External Depth: 245 mm
 - Colour: Black
 - External Case Material: Aluminium, Extruded Aluminium
 - Front Panel Material: Aluminium



1881316 2 U

RS PRO, 2U 19-INCH RACK MOUNT CASE, 335 X 425 X 84MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Rack Units: 2 U
 - External Dimensions: 335 x 425 x 84 mm
 - External Height: 84 mm
 - External Width: 425 mm
 - External Depth: 335 mm
 - Colour: Black
 - External Case Material: Aluminium, Extruded Aluminium
 - Front Panel Material: Aluminium



1881317 2 U

RS PRO, 2U 19-INCH RACK MOUNT CASE, 425 X 425 X 84MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Rack Units: 2 U
 - External Dimensions: 425 x 425 x 84 mm
 - External Height: 84 mm
 - External Width: 425 mm
 - External Depth: 425 mm
 - Colour: Black
 - External Case Material: Aluminium, Extruded Aluminium
 - Front Panel Material: Aluminium



1881318 2 U

RS PRO, 3U 19-INCH RACK MOUNT CASE, 335 X 425 X 128.6MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Rack Units: 3 U
 - External Dimensions: 335 x 425 x 128.6 mm
 - External Height: 128.6 mm
 - External Width: 425 mm
 - External Depth: 335 mm
 - Colour: Black
 - External Case Material: Aluminium, Extruded Aluminium
 - Front Panel Material: Aluminium



1881319 3 U

RS PRO, 3U 19-INCH RACK MOUNT CASE, 425 X 425 X 128.6MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Rack Units: 3 U
 - External Dimensions: 425 x 425 x 128.6 mm
 - External Height: 128.6 mm
 - External Width: 425 mm
 - External Depth: 425 mm
 - Colour: Black
 - External Case Material: Aluminium, Extruded Aluminium
 - Front Panel Material: Aluminium



1881320 3 U

RS PRO, 4U 19-INCH RACK MOUNT CASE, 425 X 425 X 173MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Rack Units: 4 U
 - External Dimensions: 425 x 425 x 173 mm
 - External Height: 173 mm
 - External Width: 425 mm
 - External Depth: 425 mm
 - Colour: Black
 - External Case Material: Aluminium, Extruded Aluminium
 - Front Panel Material: Aluminium



1881322 4 U

RS PRO, 5U 19-INCH RACK MOUNT CASE, 425 X 425 X 217.3MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Rack Units: 5 U
 - External Dimensions: 425 x 425 x 217.3 mm
 - External Height: 217.3 mm
 - External Width: 425 mm
 - External Depth: 425 mm
 - Colour: Black
 - External Case Material: Aluminium, Extruded Aluminium
 - Front Panel Material: Aluminium



1881324 5 U

RS PRO, 1U RACKMOUNT ENCLOSURE VENTILATED, 44 X 483 X 466MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Rack Units: 1 U
 - External Dimensions: 44 x 483 x 466 mm
 - External Height: 34 mm
 - External Width: 436 mm
 - External Depth: 466 mm
 - Colour: Grey
 - Ventilated: Yes
 - External Case Material: Aluminium, Steel



6657630 1 U

RS PRO, 2U RACKMOUNT ENCLOSURE VENTILATED, 88 X 483 X 466MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Rack Units: 2 U
 - External Dimensions: 88 x 483 x 466 mm
 - External Height: 79 mm
 - External Width: 436 mm
 - External Depth: 466 mm
 - Colour: Grey
 - Ventilated: Yes
 - External Case Material: Aluminium, Steel



6657633 2 U

RS PRO, 3U RACKMOUNT ENCLOSURE VENTILATED, 133 X 483 X 466MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Rack Units: 3 U
 - External Dimensions: 133 x 483 x 466 mm
 - External Height: 123 mm
 - External Width: 436 mm
 - External Depth: 466 mm
 - Colour: Grey
 - Ventilated: Yes
 - External Case Material: Aluminium, Steel



6657637 3 U

RS PRO, 6U RACKMOUNT ENCLOSURE VENTILATED, 266 X 483 X 466MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Rack Units: 6 U
 - External Dimensions: 266 x 483 x 466 mm
 - External Height: 256 mm
 - External Width: 436 mm
 - External Depth: 466 mm
 - Colour: Grey
 - Ventilated: Yes
 - External Case Material: Aluminium, Steel



6657643 6 U

RS PRO, 4U RACKMOUNT ENCLOSURE VENTILATED, 177 X 483 X 466MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Rack Units: 4 U
 - External Dimensions: 177 x 483 x 466 mm
 - External Height: 168 mm
 - External Width: 436 mm
 - External Depth: 466 mm
 - Colour: Grey
 - Ventilated: Yes
 - External Case Material: Aluminium, Steel



6657646 4 U

RS PRO, 5U RACKMOUNT ENCLOSURE VENTILATED, 222 X 483 X 466MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Rack Units: 5 U
 - External Dimensions: 222 x 483 x 466 mm
 - External Height: 212 mm
 - External Width: 436 mm
 - External Depth: 466 mm
 - Colour: Grey
 - Ventilated: Yes
 - External Case Material: Aluminium, Steel



6657649 5 U

RS PRO, 1U 19-INCH RACK MOUNT CASE, 44 X 483 X 250MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Rack Units: 1 U
 - External Dimensions: 44 x 483 x 250 mm
 - External Height: 44 mm
 - External Width: 483 mm
 - External Depth: 250 mm
 - Colour: Grey
 - External Case Material: Aluminium, Steel
 - Front Panel Material: Aluminium



6657659 1 U

RS PRO, 2U 19-INCH RACK MOUNT CASE, 88 X 483 X 350MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Rack Units: 2 U
 - External Dimensions: 88 x 483 x 350 mm
 - External Height: 88 mm
 - External Width: 483 mm
 - External Depth: 350 mm
 - Colour: Grey
 - External Case Material: Aluminium, Steel
 - Front Panel Material: Aluminium



6657661 2 U

RS PRO, 3U 19-INCH RACK MOUNT CASE, 133 X 483 X 250MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Rack Units: 3 U
 - External Dimensions: 133 x 483 x 250 mm
 - External Height: 133 mm
 - External Width: 483 mm
 - External Depth: 250 mm
 - Colour: Grey
 - External Case Material: Aluminium, Steel
 - Front Panel Material: Aluminium



6657665 3 U

RS PRO, 2U 19-INCH RACK MOUNT CASE, 88 X 483 X 250MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Rack Units: 2 U
 - External Dimensions: 88 x 483 x 250 mm
 - External Height: 88 mm
 - External Width: 483 mm
 - External Depth: 250 mm
 - Colour: Grey
 - External Case Material: Aluminium, Steel
 - Front Panel Material: Aluminium



6657668 2 U

RS PRO, 2U 19-INCH RACK MOUNT CASE, 88 X 483 X 250MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Rack Units: 2 U
 - External Dimensions: 88 x 483 x 250 mm
 - External Height: 88 mm
 - External Width: 483 mm
 - External Depth: 250 mm
 - Colour: Black, Grey
 - External Case Material: Aluminium, Steel
 - Front Panel Material: Aluminium



6657671 2 U

RS PRO, 3U 19-INCH RACK MOUNT CASE, 133 X 483 X 350MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Rack Units: 3 U
 - External Dimensions: 133 x 483 x 350 mm
 - External Height: 133 mm
 - External Width: 483 mm
 - External Depth: 350 mm
 - Colour: Natural
 - External Case Material: Aluminium, Steel
 - Front Panel Material: Aluminium



6657674 3 U

RS PRO, 1U 19-INCH RACK MOUNT CASE, 44 X 483 X 250MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Rack Units: 1 U
 - External Dimensions: 44 x 483 x 250 mm
 - External Height: 44 mm
 - External Width: 483 mm
 - External Depth: 250 mm
 - Colour: Black, Grey
 - External Case Material: Aluminium, Steel
 - Front Panel Material: Aluminium



6657677 1 U

RS PRO, 2U 19-INCH RACK MOUNT CASE, 88 X 483 X 350MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Rack Units: 2 U
 - External Dimensions: 88 x 483 x 350 mm
 - External Height: 88 mm
 - External Width: 483 mm
 - External Depth: 350 mm
 - Colour: Black, Grey
 - External Case Material: Aluminium, EG
 - Front Panel Material: Aluminium



6657680 2 U

RS PRO, 3U 19-INCH RACK MOUNT CASE, 133 X 483 X 250MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Rack Units: 3 U
 - External Dimensions: 133 x 483 x 250 mm
 - External Height: 133 mm
 - External Width: 483 mm
 - External Depth: 250 mm
 - Colour: Black, Grey
 - External Case Material: Aluminium, Steel
 - Front Panel Material: Aluminium



6657683 3 U

RS PRO, 3U 19-INCH RACK MOUNT CASE, 133 X 483 X 350MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Rack Units: 3 U
 - External Dimensions: 133 x 483 x 350 mm
 - External Height: 133 mm
 - External Width: 483 mm
 - External Depth: 350 mm
 - Colour: Black, Grey
 - External Case Material: Aluminium, Steel
 - Front Panel Material: Aluminium



6657687 3 U

RS PRO, 1U 19-INCH RACK MOUNT CASE VENTILATED, 482.6 X 43.7 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Rack Units: 1 U
 - External Dimensions: 482.6 x 43.7 x 245 mm
 - External Height: 43.7 mm
 - External Width: 482.6 mm
 - External Depth: 245 mm
 - Colour: Black
 - Ventilated: Yes
 - External Case Material: Steel



6657700 1 U

RACK MOUNT ENCLOSURE, 1U 90MM BLACK

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Rack Units: 1 U
 - External Dimensions: 483 x 44 x 90 mm
 - External Height: 44 mm
 - External Width: 483 mm
 - External Depth: 90 mm
 - Colour: Black
 - Ventilated: Yes
 - External Case Material: Steel



6657706 1 U

RS PRO, 2U 19-INCH RACK MOUNT CASE VENTILATED, 482.6 X 88.1 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Rack Units: 2 U
 - External Dimensions: 482.6 x 88.1 x 335 mm
 - External Height: 88.1 mm
 - External Width: 482.6 mm
 - External Depth: 335 mm
 - Colour: Black
 - Ventilated: Yes
 - External Case Material: Steel



6657712 2 U

RS PRO, 3U 19-INCH RACK MOUNT CASE VENTILATED, 482.6 X 132.6 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Rack Units: 3 U
 - External Dimensions: 482.6 x 132.6 x 335 mm
 - External Height: 132.6 mm
 - External Width: 482.6 mm
 - External Depth: 335 mm
 - Colour: Black
 - Ventilated: Yes
 - External Case Material: Steel



6657716 3 U

RS PRO, 2U 19-INCH RACK MOUNT CASE VENTILATED, 482.6 X 88.1 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Rack Units: 2 U
 - External Dimensions: 482.6 x 88.1 x 245 mm
 - External Height: 88.1 mm
 - External Width: 482.6 mm
 - External Depth: 245 mm
 - Colour: Black
 - Ventilated: Yes
 - External Case Material: Steel



6657719 2 U

RS PRO, 4U 19-INCH RACK MOUNT CASE VENTILATED, 482.6 X 177 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Rack Units: 4 U
 - External Dimensions: 482.6 x 177 x 425 mm
 - External Height: 177 mm
 - External Width: 482.6 mm
 - External Depth: 425 mm
 - Colour: Black
 - Ventilated: Yes
 - External Case Material: Steel



6657722 4 U

RS PRO, 3U 19-INCH RACK MOUNT CASE VENTILATED, 482.6 X 132.6 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Rack Units: 3 U
 - External Dimensions: 482.6 x 132.6 x 425 mm
 - External Height: 132.6 mm
 - External Width: 482.6 mm
 - External Depth: 425 mm
 - Colour: Black
 - Ventilated: Yes
 - External Case Material: Steel



6657725 3 U

RS PRO, 4U 19-INCH RACK MOUNT CASE VENTILATED, 482.6 X 177 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Rack Units: 4 U
 - External Dimensions: 482.6 x 177 x 335 mm
 - External Height: 177 mm
 - External Width: 482.6 mm
 - External Depth: 335 mm
 - Colour: Black
 - Ventilated: Yes
 - External Case Material: Steel



6657728 4 U

RS PRO, 5U 19-INCH RACK MOUNT CASE VENTILATED, 482.6 X 221.5 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Rack Units: 5 U
 - External Dimensions: 482.6 x 221.5 x 425 mm
 - External Height: 221.5 mm
 - External Width: 482.6 mm
 - External Depth: 425 mm
 - Colour: Black
 - Ventilated: Yes
 - External Case Material: Steel



6657731 5 U

RS PRO, 6U 19-INCH RACK MOUNT CASE VENTILATED, 266 X 482 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Rack Units: 6 U
 - External Dimensions: 266 x 482 x 465 mm
 - External Height: 266 mm
 - External Width: 482 mm
 - External Depth: 465 mm
 - Colour: Black
 - Ventilated: Yes
 - External Case Material: Aluminium, Steel



6657738 6 U

SCREW KIT, MACHINE, C/W M6 PLASTIC CUPWASHERS, CAGE

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Number of Pieces: 10
 - Screw/Bolt Type: Machine Screw
 - Head Shape: Pan
 - Drive Type: Cross
 - Screw/Bolts Lengths: 16 mm
 - Thread Size: M6
 - Nut Type: Cage
 - Washer Type: Cup



5425410 10

SCREW KIT, MACHINE, C/W M6 PLASTIC CUPWASHERS, CAGE

- ขนาดบรรจุภัณฑ์: **50 x EA**
- Number of Pieces: 50
 - Screw/Bolt Type: Machine Screw
 - Head Shape: Pan
 - Drive Type: Cross
 - Screw/Bolts Lengths: 16 mm
 - Thread Size: M6
 - Nut Type: Cage
 - Washer Type: Cup



5425426 50

RS PRO 6U-RACK SERVER CABINET, 203 X 502 X 300MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Rack Units: 6 U
 - Type: Wall Mount
 - External Height: 203 mm
 - External Width: 502 mm
 - External Depth: 300 mm
 - External Dimensions: 203 x 502 x 300 mm
 - Colour: Black
 - External Case Material: Steel



7450742 6 U

RS PRO 2U-RACK SERVER RACK DRAWER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Rack Units: 2 U
 - Type: Drawer
 - External Height: 88 mm
 - External Width: 483 mm
 - External Depth: 500 mm
 - Colour: Grey
 - External Case Material: Steel



8020267 2 U

RS PRO 6U-RACK SERVER CABINET, 366 X 600 X 560MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Rack Units: 6 U
 - Type: Wall Mount
 - External Height: 366 mm
 - External Width: 600 mm
 - External Depth: 560 mm
 - External Dimensions: 366 x 600 x 560 mm
 - Colour: Grey
 - External Case Material: Steel



8020320 6 U

RS PRO 6U-RACK SERVER CABINET, 366 X 600 X 400MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Rack Units: 6 U
 - Type: Wall Mount
 - External Height: 366 mm
 - External Width: 600 mm
 - External Depth: 400 mm
 - External Dimensions: 366 x 600 x 400 mm
 - Colour: Grey
 - External Case Material: Steel



8020327 6 U

RS PRO TIE BAR ASSEMBLY TIE BAR ASSEMBLY FOR USE WITH 19-INCH

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Type: Tie Bar Assembly
 - For Use With: 19-Inch Cabinet, Wall Box
 - Material: Steel
 - Height (U): 1 U



223770 Tie Bar Assembly

RS PRO DOCUMENT POCKET DOCUMENT POCKET FOR USE WITH

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Type: Document Pocket
 - Dimensions: 278 x 234 x 40 mm
 - For Use With: A4 Documents
 - Material: Polystyrene



500308 Document Pocket

RS PRO DOCUMENT POCKET DOCUMENT POCKET FOR USE WITH

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Type: Document Pocket
 - Dimensions: 188 x 174 x 20 mm
 - For Use With: A4 & A5 Plans, DIN A3
 - Material: Polystyrene



500314 Document Pocket

RS PRO SYSTEM CARD GUIDE SYSTEM CARD GUIDE FOR USE WITH

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Type: System Card Guide
 - For Use With: KM6-II Sub Rack System
 - Material: Luranyl



500550 System Card

RS PRO SYSTEM CARD GUIDE SYSTEM CARD GUIDE FOR USE WITH

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Type: System Card Guide
 - For Use With: KM6-II Sub Rack System



500572 System Card

ENCLOSURE,SUBRACK,KM6-II,PLASTIC PCB MOUNT BRACKET

- ขนาดบรรจุภัณฑ์: **2 x EA**
- Type: Card Mounting Bracket
 - For Use With: KM6-II Sub Rack System
 - Material: Plastic



500847 Card Mounting

ENCLOSURE,SUBRACK,KM6-II,METAL PCB MOUNT BRACKET

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Type: Card Mounting Bracket
 - For Use With: KM6-II Sub Rack System
 - Material: Metal



500853 Card Mounting

RS PRO PLASTIC BUSH PLASTIC BUSH FOR USE WITH EURO-CARDS FITTED

- ขนาดบรรจุภัณฑ์: **100 x EA**
- Type: Plastic Bush
 - For Use With: Euro-Cards Fitted with 2 Part Indirect Edge Connector
 - Material: Plastic
 - Thread Size: M2.5



524571 Plastic Bush

RS PRO BAR HANDLE BAR HANDLE FOR USE WITH METAL INSTRUMENT

- ขนาดบรรจุภัณฑ์: **2 x EA**
- Type: Bar Handle
 - Dimensions: 136.5 x 9.5 x 33.5 mm
 - For Use With: Metal Instrument Case
 - Material: Steel



583820 Bar Handle

RS PRO TIE BAR RECESSED CABLE TIE BAR FOR USE WITH ELECTRICAL

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Type: Recessed Cable Tie Bar
 - For Use With: Electrical Isolator, Telecom Backmount
 - Material: Steel
 - Height (U): 1.5 U



2431888 Recessed Cable

RS PRO TAPPED STRIP TAPPED STRIP FOR USE WITH KM6-II SUB RACK

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Type: Tapped Strip
 - For Use With: KM6-II Sub Rack System
 - Material: Steel
 - Width (HP): 42 HP



4445182 Tapped Strip

RS PRO TAPPED STRIP TAPPED STRIP FOR USE WITH KM6-II SUB RACK

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Type: Tapped Strip
 - For Use With: KM6-II Sub Rack System
 - Material: Steel
 - Width (HP): 60 HP



4445520 Tapped Strip

RS PRO VENTILATED TOP COVER VENTILATED TOP COVER FOR USE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Type: Ventilated Top Cover
 - Dimensions: 423 x 466 x 3 mm
 - For Use With: 19" Racking System
 - Material: Steel



6657652 Ventilated Top

RS PRO UNVENTILATED TOP COVER UNVENTILATED TOP COVER FOR USE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Type: Unventilated Top Cover
 - Dimensions: 423 x 466 x 3 mm
 - For Use With: 19" Racking System
 - Material: Steel



6657655 Unventilated Top

RS PRO VENTILATED TOP COVER VENTILATED TOP COVER FOR USE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Type: Ventilated Top Cover
 - For Use With: 19-Inch Steel Chassis Tray
 - Material: Steel



6657693 Ventilated Top

RS PRO UNVENTILATED TOP COVER UNVENTILATED TOP COVER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Type: Unventilated Top Cover



6657696 Unventilated Top

RS PRO UNVENTILATED TOP COVER UNVENTILATED TOP COVER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Type: Unventilated Top Cover



6657699 Unventilated Top

RS PRO VENTILATED TOP COVER VENTILATED TOP COVER FOR USE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Type: Ventilated Top Cover
 - For Use With: 19-Inch Steel Chassis Tray
 - Material: Steel



6657703 Ventilated Top

RS PRO CAGED NUTS KIT CAGED NUTS KIT FOR USE WITH 19 IN RACK

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Caged Nuts Kit
 - For Use With: 19 in Rack Mounting Equipment
 - Thread Size: M6 x 16
 - Quantity: 30



7682621 Caged Nuts Kit

RS PRO BLACK TRAY, 2U, 10KG LOAD X 280MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Tray
 - Rack Units: 2 U
 - Depth: 280 mm
 - Ventilated: Yes
 - Colour: Black
 - Material: Steel
 - Maximum Load: 10 kg
 - Maximum Depth: 280 mm



1959126 Tray

2U 19" CANTILEVER SHELF

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Cantilever Shelf
 - Rack Units: 2 U
 - Depth: 250 mm
 - Ventilated: Yes
 - Colour: Grey
 - Material: Steel
 - Maximum Load: 25 kg
 - Height: 88 mm



8020273 Cantilever Shelf

1U 19" CANTILEVER SHELF

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Cantilever Shelf
 - Rack Units: 1 U
 - Depth: 150 mm
 - Ventilated: Yes
 - Colour: Grey
 - Material: Steel
 - Maximum Load: 25 kg
 - Height: 44 mm



8020279 Cantilever Shelf

RS PRO GREY CANTILEVER SHELF, 2U, 25KG LOAD, 483MM X 400MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Cantilever Shelf
 - Rack Units: 2 U
 - Depth: 400 mm
 - Ventilated: Yes
 - Colour: Grey
 - Material: Steel
 - Maximum Load: 25 kg
 - Height: 88 mm



8020282 Cantilever Shelf

RACK MOUNT CHASSIS, 84HP

- ขนาดบรรจุภัณฑ์: 1 x EA
- Horizontal Pitch: 84 HP
 - Colour: Unpainted
 - Width: 426 mm



500623 84 HP

RS PRO GLASS REINFORCED PLASTIC WALL BOX, IP66, 100 MM X 120 MM X

- ขนาดบรรจุภัณฑ์: 1 x EA
- External Height: 100 mm
 - External Width: 120 mm
 - External Depth: 140 mm
 - Body Material: Glass Reinforced Plastic
 - Transparent Door: No
 - IP Rating: IP66
 - Chassis Plate: No
 - Gland Plate: No



225568 100 mm

RS PRO STEEL WALL BOX, IP66, 250 MM X 200 MM X 150MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- External Height: 250 mm
 - External Width: 200 mm
 - External Depth: 150 mm
 - Body Material: Steel
 - IP Rating: IP66
 - Chassis Plate: Yes
 - Door Lock Type: Single Lock System
 - Gland Plate: Yes



1896587 250 mm

RS PRO STEEL WALL BOX, IP66, 250 MM X 250 MM X 150MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- External Height: 250 mm
 - External Width: 250 mm
 - External Depth: 150 mm
 - Body Material: Steel
 - IP Rating: IP66
 - Chassis Plate: Yes
 - Door Lock Type: Single Lock System
 - Gland Plate: Yes



1896588 250 mm

RS PRO STEEL WALL BOX, IP66, 300 MM X 250 MM X 200MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- External Height: 300 mm
 - External Width: 250 mm
 - External Depth: 200 mm
 - Body Material: Steel
 - IP Rating: IP66
 - Chassis Plate: Yes
 - Door Lock Type: Single Lock System
 - Gland Plate: Yes



1896589 300 mm

RS PRO STEEL WALL BOX, IP66, 400 MM X 300 MM X 150MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- External Height: 400 mm
 - External Width: 300 mm
 - External Depth: 150 mm
 - Body Material: Steel
 - IP Rating: IP66
 - Chassis Plate: Yes
 - Door Lock Type: Single Lock System
 - Gland Plate: Yes



1896590 400 mm

RS PRO STEEL WALL BOX, IP66, 500 MM X 300 MM X 150MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- External Height: 500 mm
 - External Width: 300 mm
 - External Depth: 150 mm
 - Body Material: Steel
 - IP Rating: IP66
 - Chassis Plate: Yes
 - Door Lock Type: Single Lock System
 - Gland Plate: Yes



1896591 500 mm

RS PRO STEEL WALL BOX, IP66, 600 MM X 500 MM X 150MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- External Height: 600 mm
 - External Width: 500 mm
 - External Depth: 150 mm
 - Body Material: Steel
 - IP Rating: IP66
 - Chassis Plate: Yes
 - Door Lock Type: Double Lock System
 - Gland Plate: Yes



1896592 600 mm

RS PRO STEEL WALL BOX, IP66, 500 MM X 500 MM X 200MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- External Height: 500 mm
 - External Width: 500 mm
 - External Depth: 200 mm
 - Body Material: Steel
 - IP Rating: IP66
 - Chassis Plate: Yes
 - Door Lock Type: Single Lock System
 - Gland Plate: Yes



1896594 500 mm

RS PRO STEEL WALL BOX, IP66, 400 MM X 400 MM X 250MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- External Height: 400 mm
 - External Width: 400 mm
 - External Depth: 250 mm
 - Body Material: Steel
 - IP Rating: IP66
 - Chassis Plate: Yes
 - Door Lock Type: Single Lock System
 - Gland Plate: Yes



1896595 400 mm

RS PRO STEEL WALL BOX, IP66, 500 MM X 400 MM X 250MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- External Height: 500 mm
 - External Width: 400 mm
 - External Depth: 250 mm
 - Body Material: Steel
 - IP Rating: IP66
 - Chassis Plate: Yes
 - Door Lock Type: Single Lock System
 - Gland Plate: Yes



1896596 500 mm

600H X 400W X 250DMM, DOOR & BODY: 1.2MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- External Height: 600 mm
 - External Width: 400 mm
 - External Depth: 250 mm
 - Body Material: Steel
 - IP Rating: IP66
 - Chassis Plate: Yes
 - Door Lock Type: Double Lock System
 - Gland Plate: Yes



1896597 600 mm

RS PRO STEEL WALL BOX, IP66, 600 MM X 500 MM X 250MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- External Height: 600 mm
 - External Width: 500 mm
 - External Depth: 250 mm
 - Body Material: Steel
 - IP Rating: IP66
 - Chassis Plate: Yes
 - Door Lock Type: Double Lock System
 - Gland Plate: Yes



1896598 600 mm

RS PRO STEEL WALL BOX, IP66, 600 MM X 500 MM X 300MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- External Height: 600 mm
 - External Width: 500 mm
 - External Depth: 300 mm
 - Body Material: Steel
 - IP Rating: IP66
 - Chassis Plate: Yes
 - Door Lock Type: Double Lock System
 - Gland Plate: Yes



1896599 600 mm

RS PRO STEEL WALL BOX, IP66, 1000 MM X 600 MM X 300MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- External Height: 1000 mm
 - External Width: 600 mm
 - External Depth: 300 mm
 - Body Material: Steel
 - IP Rating: IP66
 - Chassis Plate: Yes
 - Door Lock Type: Triple Lock System
 - Gland Plate: Yes



1896601 1000 mm

RS PRO STEEL WALL BOX, IP66, 1200 MM X 800 MM X 250MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- External Height: 1200 mm
 - External Width: 800 mm
 - External Depth: 250 mm
 - Body Material: Steel
 - IP Rating: IP66
 - Chassis Plate: Yes
 - Door Lock Type: Triple Lock System
 - Gland Plate: Yes



1896602 1200 mm

RS PRO STEEL WALL BOX, IP66, 1000 MM X 800 MM X 400MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- External Height: 1000 mm
 - External Width: 800 mm
 - External Depth: 400 mm
 - Body Material: Steel
 - IP Rating: IP66
 - Chassis Plate: Yes
 - Door Lock Type: Triple Lock System
 - Gland Plate: Yes



1896603 1000 mm

1200H X 800W X 400DMM, DOOR & BODY: 1.5MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- External Height: 1200 mm
 - External Width: 800 mm
 - External Depth: 400 mm
 - Body Material: Steel
 - IP Rating: IP66
 - Chassis Plate: Yes
 - Door Lock Type: Triple Lock System
 - Gland Plate: Yes



1896604 1200 mm

RS PRO FIBREGLASS REINFORCED POLYESTER WALL BOX, IP66, 300 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- External Height: 300 mm
 - External Width: 250 mm
 - External Depth: 140 mm
 - Body Material: Fibreglass Reinforced Polyester
 - Transparent Door: No
 - IP Rating: IP66
 - Chassis Plate: Yes
 - Door Lock Type: Single Lock System



1927114 300 mm

RS PRO FIBREGLASS REINFORCED POLYESTER WALL BOX, IP66, 400 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- External Height: 400 mm
 - External Width: 400 mm
 - External Depth: 200 mm
 - Body Material: Fibreglass Reinforced Polyester
 - Transparent Door: No
 - IP Rating: IP66
 - Chassis Plate: Yes
 - Door Lock Type: Double Lock System



1927115 400 mm

RS PRO FIBREGLASS REINFORCED POLYESTER WALL BOX, IP66, 400 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- External Height: 400 mm
 - External Width: 300 mm
 - External Depth: 200 mm
 - Body Material: Fibreglass Reinforced Polyester
 - Transparent Door: No
 - IP Rating: IP66
 - Chassis Plate: Yes
 - Door Lock Type: Double Lock System



1927116 400 mm

RS PRO FIBREGLASS REINFORCED POLYESTER WALL BOX, IP66, 500 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- External Height: 500 mm
 - External Width: 400 mm
 - External Depth: 200 mm
 - Body Material: Fibreglass Reinforced Polyester
 - Transparent Door: No
 - IP Rating: IP66
 - Chassis Plate: Yes
 - Door Lock Type: Double Lock System



1927117 500 mm

RS PRO FIBREGLASS REINFORCED POLYESTER WALL BOX, IP66, 600 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- External Height: 600 mm
 - External Width: 400 mm
 - External Depth: 230 mm
 - Body Material: Fibreglass Reinforced Polyester
 - Transparent Door: No
 - IP Rating: IP66
 - Chassis Plate: Yes
 - Door Lock Type: Double Lock System



1927118 600 mm

RS PRO FIBREGLASS REINFORCED POLYESTER WALL BOX, IP66, 600 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- External Height: 600 mm
 - External Width: 500 mm
 - External Depth: 230 mm
 - Body Material: Fibreglass Reinforced Polyester
 - Transparent Door: No
 - IP Rating: IP66
 - Chassis Plate: Yes
 - Door Lock Type: Double Lock System



1927119 600 mm

RS PRO FIBREGLASS REINFORCED POLYESTER WALL BOX, IP66, 800 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- External Height: 800 mm
 - External Width: 600 mm
 - External Depth: 300 mm
 - Body Material: Fibreglass Reinforced Polyester
 - Transparent Door: No
 - IP Rating: IP66
 - Chassis Plate: Yes
 - Door Lock Type: Double Lock System



1927121 800 mm

RS PRO FIBREGLASS REINFORCED POLYESTER WALL BOX, IP66,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- External Height: 300 mm
 - External Width: 250 mm
 - External Depth: 140 mm
 - Body Material: Fibreglass Reinforced Polyester
 - Transparent Door: Yes
 - IP Rating: IP66
 - Chassis Plate: Yes
 - Door Lock Type: Single Lock System



1927122 300 mm

RS PRO FIBREGLASS REINFORCED POLYESTER WALL BOX, IP66,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- External Height: 400 mm
 - External Width: 400 mm
 - External Depth: 200 mm
 - Body Material: Fibreglass Reinforced Polyester
 - Transparent Door: Yes
 - IP Rating: IP66
 - Chassis Plate: Yes
 - Door Lock Type: Double Lock System



1927123 400 mm

RS PRO FIBREGLASS REINFORCED POLYESTER WALL BOX, IP66,

- ขนาดบรรจุภัณฑ์: 1 x EA
- External Height: 400 mm
 - External Width: 300 mm
 - External Depth: 200 mm
 - Body Material: Fibreglass Reinforced Polyester
 - Transparent Door: Yes
 - IP Rating: IP66
 - Chassis Plate: Yes
 - Door Lock Type: Double Lock System



1927124 400 mm

RS PRO FIBREGLASS REINFORCED POLYESTER WALL BOX, IP66,

- ขนาดบรรจุภัณฑ์: 1 x EA
- External Height: 600 mm
 - External Width: 500 mm
 - External Depth: 230 mm
 - Body Material: Fibreglass Reinforced Polyester
 - Transparent Door: Yes
 - IP Rating: IP66
 - Chassis Plate: Yes
 - Door Lock Type: Double Lock System



1927127 600 mm

RS PRO ABS, POLYCARBONATE WALL BOX, IP65, VIEWING WINDOW, 166

- ขนาดบรรจุภัณฑ์: 1 x EA
- External Height: 166 mm
 - External Width: 161 mm
 - External Depth: 93 mm
 - Body Material: ABS, Polycarbonate
 - Transparent Door: Yes
 - IP Rating: IP65
 - Chassis Plate: No
 - Door Lock Type: Pad Lock



1947497 166 mm

RS PRO ABS, POLYCARBONATE WALL BOX, IP65, VIEWING WINDOW, 296

- ขนาดบรรจุภัณฑ์: 1 x EA
- External Height: 296 mm
 - External Width: 161 mm
 - External Depth: 188 mm
 - Body Material: ABS, Polycarbonate
 - Transparent Door: Yes
 - IP Rating: IP65
 - Chassis Plate: No
 - Door Lock Type: Pad Lock



1947501 296 mm

RS PRO POLYCARBONATE WALL BOX, IP65, 300 MM X 200 MM X 180MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- External Height: 300 mm
 - External Width: 200 mm
 - External Depth: 180 mm
 - Body Material: Polycarbonate
 - Transparent Door: No
 - IP Rating: IP65
 - Chassis Plate: Yes
 - Gland Plate: No



2068769 300 mm

RS PRO POLYCARBONATE WALL BOX, IP65, VIEWING WINDOW, 300 MM X

- ขนาดบรรจุภัณฑ์: 1 x EA
- External Height: 300 mm
 - External Width: 300 mm
 - External Depth: 180 mm
 - Body Material: Polycarbonate
 - Transparent Door: Yes
 - IP Rating: IP65
 - Chassis Plate: Yes
 - Gland Plate: No



2068774 300 mm

RS PRO POLYCARBONATE WALL BOX, IP65, VIEWING WINDOW, 400 MM X

- ขนาดบรรจุภัณฑ์: 1 x EA
- External Height: 400 mm
 - External Width: 300 mm
 - External Depth: 180 mm
 - Body Material: Polycarbonate
 - Transparent Door: Yes
 - IP Rating: IP65
 - Chassis Plate: Yes
 - Gland Plate: No



2068776 400 mm

RS PRO STEEL WALL BOX, IP65, 400 MM X 300 MM X 200MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- External Height: 400 mm
 - External Width: 300 mm
 - External Depth: 180 mm
 - Body Material: Steel
 - Transparent Door: No
 - IP Rating: IP65
 - Chassis Plate: Yes
 - Door Lock Type: Key



7467352 400 mm

RS PRO ABS WALL BOX, IP65, 400 MM X 300 MM X 195MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- External Height: 400 mm
 - External Width: 300 mm
 - External Depth: 195 mm
 - Body Material: ABS
 - Transparent Door: No
 - IP Rating: IP65
 - Chassis Plate: Yes
 - Door Lock Type: Single Lock System



7467390 400 mm

IP65 ABS WALL ENCLOSURE 280X210X130MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- External Height: 280 mm
 - External Width: 210 mm
 - External Depth: 130 mm
 - Body Material: ABS
 - Transparent Door: No
 - IP Rating: IP65
 - Chassis Plate: Yes
 - Door Lock Type: Double Lock System



7467393 280 mm

RS PRO ABS WALL BOX, IP65, 400 MM X 300 MM X 165MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- External Height: 400 mm
 - External Width: 300 mm
 - External Depth: 165 mm
 - Body Material: ABS
 - Transparent Door: No
 - IP Rating: IP65
 - Chassis Plate: Yes
 - Door Lock Type: Single Lock System



7467396 400 mm

RS PRO ABS WALL BOX, IP65, 600 MM X 400 MM X 200MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- External Height: 400 mm
 - External Width: 400 mm
 - External Depth: 200 mm
 - Body Material: ABS
 - Transparent Door: No
 - IP Rating: IP65
 - Chassis Plate: Yes
 - Door Lock Type: Single Lock System



7467403 600 mm

RS PRO ABS WALL BOX, IP65, 500 MM X 400 MM X 175MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- External Height: 500 mm
 - External Width: 400 mm
 - External Depth: 175 mm
 - Body Material: ABS
 - Transparent Door: No
 - IP Rating: IP65
 - Chassis Plate: Yes
 - Door Lock Type: Single Lock System



7467400 500 mm

RS PRO ABS WALL BOX, IP65, 700 MM X 500 MM X 245MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- External Height: 700 mm
 - External Width: 500 mm
 - External Depth: 245 mm
 - Body Material: ABS
 - Transparent Door: No
 - IP Rating: IP65
 - Chassis Plate: Yes
 - Door Lock Type: Single Lock System



7467407 700 mm

RS PRO 304 STAINLESS STEEL WALL BOX, IP66, 300 MM X 250 MM X

- ขนาดบรรจุภัณฑ์: 1 x EA
- External Height: 300 mm
 - External Width: 250 mm
 - External Depth: 150 mm
 - Body Material: 304 Stainless Steel
 - Transparent Door: No
 - IP Rating: IP66
 - Chassis Plate: Yes
 - Door Lock Type: Quick Release Lock



7491822 300 mm

RS PRO 304 STAINLESS STEEL WALL BOX, IP66, 400 MM X 300 MM X

- ขนาดบรรจุภัณฑ์: 1 x EA
- External Height: 300 mm
 - External Width: 400 mm
 - External Depth: 150 mm
 - Body Material: 304 Stainless Steel
 - Transparent Door: No
 - IP Rating: IP66
 - Chassis Plate: Yes
 - Door Lock Type: Quick Release Lock



7491826 300 mm

RS PRO 304 STAINLESS STEEL WALL BOX, IP66, 200 MM X 200 MM X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- External Height: 200 mm
 - External Width: 200 mm
 - External Depth: 150 mm
 - Body Material: 304 Stainless Steel
 - Transparent Door: No
 - IP Rating: IP66
 - Chassis Plate: Yes
 - Door Lock Type: Quick Release Lock



7491829 200 mm

RS PRO 304 STAINLESS STEEL WALL BOX, IP66, 300 MM X 300 MM X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- External Height: 300 mm
 - External Width: 300 mm
 - External Depth: 150 mm
 - Body Material: 304 Stainless Steel
 - Transparent Door: No
 - IP Rating: IP66
 - Chassis Plate: Yes
 - Door Lock Type: Quick Release Lock



7491838 300 mm

RS PRO 304 STAINLESS STEEL WALL BOX, IP66, 400 MM X 400 MM X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- External Height: 400 mm
 - External Width: 400 mm
 - External Depth: 200 mm
 - Body Material: 304 Stainless Steel
 - Transparent Door: No
 - IP Rating: IP66
 - Chassis Plate: Yes
 - Door Lock Type: Quick Release Lock



7491841 400 mm

RS PRO 304 STAINLESS STEEL WALL BOX, IP66, 500 MM X 400 MM X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- External Height: 400 mm
 - External Width: 500 mm
 - External Depth: 250 mm
 - Body Material: 304 Stainless Steel
 - Transparent Door: No
 - IP Rating: IP66
 - Chassis Plate: Yes
 - Door Lock Type: Quick Release Lock



7491844 400 mm

RS PRO 304 STAINLESS STEEL WALL BOX, IP66, 400 MM X 300 MM X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- External Height: 400 mm
 - External Width: 300 mm
 - External Depth: 200 mm
 - Body Material: 304 Stainless Steel
 - Transparent Door: No
 - IP Rating: IP66
 - Chassis Plate: Yes
 - Door Lock Type: Quick Release Lock



7586958 400 mm

RS PRO 304 STAINLESS STEEL WALL BOX, IP66, 500 MM X 400 MM X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- External Height: 500 mm
 - External Width: 400 mm
 - External Depth: 200 mm
 - Body Material: 304 Stainless Steel
 - Transparent Door: No
 - IP Rating: IP66
 - Chassis Plate: Yes
 - Door Lock Type: Quick Release Lock



7586961 500 mm

RS PRO 304 STAINLESS STEEL WALL BOX, IP66, 600 MM X 400 MM X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- External Height: 600 mm
 - External Width: 400 mm
 - External Depth: 200 mm
 - Body Material: 304 Stainless Steel
 - Transparent Door: No
 - IP Rating: IP66
 - Chassis Plate: Yes
 - Door Lock Type: Quick Release Lock



7586964 600 mm

RS PRO 304 STAINLESS STEEL WALL BOX, IP66, 300 MM X 300 MM X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- External Height: 300 mm
 - External Width: 300 mm
 - External Depth: 300 mm
 - Body Material: 304 Stainless Steel
 - Transparent Door: No
 - IP Rating: IP66
 - Chassis Plate: Yes
 - Door Lock Type: Quick Release Lock



7586986 300 mm

RS PRO 304 STAINLESS STEEL WALL BOX, IP69K, 300 MM X 300 MM X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- External Height: 300 mm
 - External Width: 300 mm
 - External Depth: 200 mm
 - Body Material: 304 Stainless Steel
 - Transparent Door: No
 - IP Rating: IP69K
 - Chassis Plate: No
 - Door Lock Type: Key



7586996 300 mm

RS PRO 304 STAINLESS STEEL WALL BOX, IP66, 400 MM X 300 MM X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- External Height: 300 mm
 - External Width: 400 mm
 - External Depth: 200 mm
 - Body Material: 304 Stainless Steel
 - Transparent Door: No
 - IP Rating: IP66
 - Chassis Plate: Yes
 - Door Lock Type: Quick Release Lock



7586999 300 mm

RS PRO 304 STAINLESS STEEL WALL BOX, IP69K, 400 MM X 300 MM X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- External Height: 400 mm
 - External Width: 300 mm
 - External Depth: 200 mm
 - Body Material: 304 Stainless Steel
 - Transparent Door: No
 - IP Rating: IP69K
 - Chassis Plate: No
 - Door Lock Type: Key



7587002 400 mm

RS PRO 316 STAINLESS STEEL WALL BOX, IP69K, 300 MM X 300 MM X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- External Height: 400 mm
 - External Width: 300 mm
 - External Depth: 300 mm
 - Body Material: 316 Stainless Steel
 - Transparent Door: No
 - IP Rating: IP69K
 - Chassis Plate: No
 - Door Lock Type: Key



7587034 300 mm

RS PRO 316 STAINLESS STEEL WALL BOX, IP69K, 400 MM X 300 MM X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- External Height: 300 mm
 - External Width: 400 mm
 - External Depth: 200 mm
 - Body Material: 316 Stainless Steel
 - Transparent Door: No
 - IP Rating: IP69K
 - Chassis Plate: No
 - Door Lock Type: Key



7587037 300 mm

SS T BOX IP66 V2 300X200X80 (304)

- ขนาดบรรจุภัณฑ์: **1 x EA**
- External Height: 200 mm
 - External Width: 300 mm
 - External Depth: 80 mm
 - Body Material: 304 Stainless Steel
 - Transparent Door: No
 - IP Rating: IP66
 - Chassis Plate: No
 - Gland Plate: No



7587040 200 mm

RS PRO 304 STAINLESS STEEL TERMINAL BOX, IP66, 300 MM X 200

- ขนาดบรรจุภัณฑ์: **1 x EA**
- External Height: 200 mm
 - External Width: 300 mm
 - External Depth: 120 mm
 - Body Material: 304 Stainless Steel
 - Transparent Door: No
 - IP Rating: IP66
 - Chassis Plate: No
 - Gland Plate: No



7587065 200 mm

RS PRO 304 STAINLESS STEEL WALL BOX, IP69K, 600 MM X 500 MM X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- External Height: 600 mm
 - External Width: 500 mm
 - External Depth: 300 mm
 - Body Material: 304 Stainless Steel
 - Transparent Door: No
 - IP Rating: IP69K
 - Chassis Plate: No
 - Door Lock Type: Key



7587214 600 mm

RS PRO 316 STAINLESS STEEL WALL BOX, IP69K, 400 MM X 400 MM X

- ขนาดบรรจุภัณฑ์: 1 x EA
- External Height: 400 mm
 - External Width: 400 mm
 - External Depth: 200 mm
 - Body Material: 316 Stainless Steel
 - Transparent Door: No
 - IP Rating: IP69K
 - Chassis Plate: No
 - Door Lock Type: Key



7587220 400 mm

RS PRO ABS WALL BOX, IP65, 600 MM X 500 MM X 220MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- External Height: 600 mm
 - External Width: 500 mm
 - External Depth: 220 mm
 - Body Material: ABS
 - Transparent Door: No
 - IP Rating: IP65
 - Chassis Plate: Yes
 - Door Lock Type: Single Lock System



7696122 600 mm

IP65 ABS WALL BOX, 330X250X130MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- External Height: 330 mm
 - External Width: 250 mm
 - External Depth: 130 mm
 - Body Material: ABS
 - Transparent Door: No
 - IP Rating: IP65
 - Chassis Plate: Yes
 - Door Lock Type: Double Lock System



7696125 330 mm

RS PRO ABS WALL BOX, IP65, 500 MM X 350 MM X 195MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- External Height: 500 mm
 - External Width: 350 mm
 - External Depth: 195 mm
 - Body Material: ABS
 - Transparent Door: No
 - IP Rating: IP65
 - Chassis Plate: Yes
 - Door Lock Type: Single Lock System



7696128 500 mm

RS PRO STEEL WALL BOX, IP66, 300 MM X 250 MM X 150MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- External Height: 300 mm
 - External Width: 250 mm
 - External Depth: 150 mm
 - Body Material: Steel
 - Transparent Door: No
 - IP Rating: IP66
 - Chassis Plate: Yes
 - Door Lock Type: Single Lock System



7755300 300 mm

RS PRO STEEL WALL BOX, IP66, 400 MM X 300 MM X 210MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- External Height: 300 mm
 - External Width: 400 mm
 - External Depth: 210 mm
 - Body Material: Steel
 - Transparent Door: No
 - IP Rating: IP66
 - Chassis Plate: Yes
 - Door Lock Type: Single Lock System



7755312 300 mm

RS PRO STEEL WALL BOX, IP66, 400 MM X 300 MM X 210MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- External Height: 400 mm
 - External Width: 300 mm
 - External Depth: 210 mm
 - Body Material: Steel
 - Transparent Door: No
 - IP Rating: IP66
 - Chassis Plate: Yes
 - Door Lock Type: Single Lock System



7755316 400 mm

RS PRO STEEL WALL BOX, IP66, 300 MM X 300 MM X 210MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- External Height: 300 mm
 - External Width: 300 mm
 - External Depth: 210 mm
 - Body Material: Steel
 - Transparent Door: No
 - IP Rating: IP66
 - Chassis Plate: Yes
 - Door Lock Type: Single Lock System



7755319 300 mm

RS PRO STEEL WALL BOX, IP66, 500 MM X 400 MM X 210MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- External Height: 500 mm
 - External Width: 400 mm
 - External Depth: 210 mm
 - Body Material: Steel
 - Transparent Door: No
 - IP Rating: IP66
 - Chassis Plate: Yes
 - Door Lock Type: Single Lock System



7755322 500 mm

RS PRO STEEL WALL BOX, IP66, 400 MM X 400 MM X 210MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- External Height: 400 mm
 - External Width: 400 mm
 - External Depth: 210 mm
 - Body Material: Steel
 - Transparent Door: No
 - IP Rating: IP66
 - Chassis Plate: Yes
 - Door Lock Type: Single Lock System



7755325 400 mm

RS PRO STEEL WALL BOX, IP66, 400 MM X 600 MM X 210MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- External Height: 400 mm
 - External Width: 600 mm
 - External Depth: 210 mm
 - Body Material: Steel
 - Transparent Door: No
 - IP Rating: IP66
 - Chassis Plate: Yes
 - Door Lock Type: Single Lock System



7755328 400 mm

RS PRO STEEL WALL BOX, IP66, 600 MM X 600 MM X 210MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- External Height: 400 mm
 - External Width: 600 mm
 - External Depth: 210 mm
 - Body Material: Steel
 - Transparent Door: No
 - IP Rating: IP66
 - Chassis Plate: Yes
 - Door Lock Type: Double Lock System



7755340 600 mm

RS PRO STEEL WALL BOX, IP66, 700 MM X 500 MM X 260MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- External Height: 700 mm
 - External Width: 500 mm
 - External Depth: 260 mm
 - Body Material: Steel
 - Transparent Door: No
 - IP Rating: IP66
 - Chassis Plate: Yes
 - Door Lock Type: Double Lock System



7755356 700 mm

RS PRO STEEL WALL BOX, IP66, 500 MM X 500 MM X 210MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- External Height: 500 mm
 - External Width: 500 mm
 - External Depth: 210 mm
 - Body Material: Steel
 - Transparent Door: No
 - IP Rating: IP66
 - Chassis Plate: Yes
 - Door Lock Type: Single Lock System



7755331 500 mm

RS PRO STEEL WALL BOX, IP66, 500 MM X 500 MM X 300MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- External Height: 500 mm
 - External Width: 500 mm
 - External Depth: 300 mm
 - Body Material: Steel
 - Transparent Door: No
 - IP Rating: IP66
 - Chassis Plate: Yes
 - Door Lock Type: Single Lock System



7755334 500 mm

RS PRO STEEL WALL BOX, IP66, 600 MM X 400 MM X 210MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- External Height: 600 mm
 - External Width: 400 mm
 - External Depth: 210 mm
 - Body Material: Steel
 - Transparent Door: No
 - IP Rating: IP66
 - Chassis Plate: Yes
 - Door Lock Type: Double Lock System



7755338 600 mm

RS PRO STEEL WALL BOX, IP66, 600 MM X 600 MM X 300MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- External Height: 600 mm
 - External Width: 600 mm
 - External Depth: 300 mm
 - Body Material: Steel
 - Transparent Door: No
 - IP Rating: IP66
 - Chassis Plate: Yes
 - Door Lock Type: Double Lock System



7755344 600 mm

RS PRO STEEL WALL BOX, IP66, 600 MM X 400 MM X 300MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- External Height: 600 mm
 - External Width: 400 mm
 - External Depth: 300 mm
 - Body Material: Steel
 - Transparent Door: No
 - IP Rating: IP66
 - Chassis Plate: Yes
 - Door Lock Type: Double Lock System



7755347 600 mm

MS WALL BOX WITH BRACKETS/CHASSIS PLATES

- ขนาดบรรจุภัณฑ์: **1 x EA**
- External Height: 200 mm
 - External Width: 200 mm
 - External Depth: 150 mm
 - Body Material: Steel
 - Transparent Door: No
 - IP Rating: IP66
 - Chassis Plate: Yes
 - Door Lock Type: Single Lock System



7755785 200 mm

RS PRO STEEL WALL BOX, IP66, 300 MM X 200 MM X 150MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- External Height: 300 mm
 - External Width: 200 mm
 - External Depth: 150 mm
 - Body Material: Steel
 - Transparent Door: No
 - IP Rating: IP66
 - Chassis Plate: Yes
 - Door Lock Type: Single Lock System



7755788 300 mm

RS PRO STEEL WALL BOX, IP66, 300 MM X 300 MM X 150MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- External Height: 300 mm
 - External Width: 300 mm
 - External Depth: 150 mm
 - Body Material: Steel
 - Transparent Door: No
 - IP Rating: IP66
 - Chassis Plate: Yes
 - Door Lock Type: Single Lock System



7755791 300 mm

RS PRO STEEL WALL BOX, IP66, 400 MM X 400 MM X 200MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- External Height: 300 mm
 - External Width: 400 mm
 - External Depth: 200 mm
 - Body Material: Steel
 - Transparent Door: No
 - IP Rating: IP66
 - Chassis Plate: Yes
 - Door Lock Type: Single Lock System



7755794 300 mm

RS PRO STEEL WALL BOX, IP66, 400 MM X 300 MM X 150MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- External Height: 400 mm
 - External Width: 300 mm
 - External Depth: 150 mm
 - Body Material: Steel
 - Transparent Door: No
 - IP Rating: IP66
 - Chassis Plate: Yes
 - Door Lock Type: Single Lock System



7755798 400 mm

RS PRO STEEL WALL BOX, IP66, 400 MM X 300 MM X 200MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- External Height: 400 mm
 - External Width: 300 mm
 - External Depth: 200 mm
 - Body Material: Steel
 - Transparent Door: No
 - IP Rating: IP66
 - Chassis Plate: Yes
 - Door Lock Type: Single Lock System



7755808 400 mm

RS PRO STEEL WALL BOX, IP66, 700 MM X 500 MM X 200MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- External Height: 700 mm
 - External Width: 500 mm
 - External Depth: 200 mm
 - Body Material: Steel
 - Transparent Door: No
 - IP Rating: IP66
 - Chassis Plate: Yes
 - Door Lock Type: Double Lock System



7755823 700 mm

RS PRO STEEL WALL BOX, IP66, 400 MM X 400 MM X 200MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- External Height: 400 mm
 - External Width: 400 mm
 - External Depth: 200 mm
 - Body Material: Steel
 - Transparent Door: No
 - IP Rating: IP66
 - Chassis Plate: Yes
 - Door Lock Type: Single Lock System



7755801 400 mm

RS PRO STEEL WALL BOX, IP66, 500 MM X 400 MM X 150MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- External Height: 500 mm
 - External Width: 400 mm
 - External Depth: 150 mm
 - Body Material: Steel
 - Transparent Door: No
 - IP Rating: IP66
 - Chassis Plate: Yes
 - Door Lock Type: Single Lock System



7755805 500 mm

RS PRO STEEL WALL BOX, IP66, 600 MM X 500 MM X 200MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- External Height: 600 mm
 - External Width: 500 mm
 - External Depth: 200 mm
 - Body Material: Steel
 - Transparent Door: No
 - IP Rating: IP66
 - Chassis Plate: Yes
 - Door Lock Type: Double Lock System



7755811 600 mm

RS PRO STEEL WALL BOX, IP66, 500 MM X 400 MM X 200MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- External Height: 500 mm
 - External Width: 400 mm
 - External Depth: 200 mm
 - Body Material: Steel
 - Transparent Door: No
 - IP Rating: IP66
 - Chassis Plate: Yes
 - Door Lock Type: Single Lock System



7755814 500 mm

RS PRO STEEL WALL BOX, IP66, 600 MM X 400 MM X 200MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- External Height: 600 mm
 - External Width: 400 mm
 - External Depth: 200 mm
 - Body Material: Steel
 - Transparent Door: No
 - IP Rating: IP66
 - Chassis Plate: Yes
 - Door Lock Type: Double Lock System



7755817 600 mm

RS PRO STEEL WALL BOX, IP66, 300 MM X 200 MM X 200MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- External Height: 300 mm
 - External Width: 200 mm
 - External Depth: 200 mm
 - Body Material: Steel
 - Transparent Door: No
 - IP Rating: IP66
 - Chassis Plate: Yes
 - Door Lock Type: Single Lock System



8428305 300 mm

RS PRO 304 STAINLESS STEEL WALL BOX, IP66, 400 MM X 300 MM X 150 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- External Height: 400 mm
 - External Width: 300 mm
 - External Depth: 200 mm
 - Body Material: 304 Stainless Steel
 - Transparent Door: No
 - IP Rating: IP66
 - Chassis Plate: Yes
 - Door Lock Type: Single Lock System



8428342 400 mm

RS PRO 304 STAINLESS STEEL WALL BOX, IP66, 500 MM X 400 MM X

- ขนาดบรรจุภัณฑ์: 1 x EA
- External Height: 500 mm
 - External Width: 400 mm
 - External Depth: 200 mm
 - Body Material: 304 Stainless Steel
 - Transparent Door: No
 - IP Rating: IP66
 - Chassis Plate: No
 - Door Lock Type: Single Lock System



8428346 500 mm

RS PRO 304 STAINLESS STEEL WALL BOX, IP66, 600 MM X 400 MM X

- ขนาดบรรจุภัณฑ์: 1 x EA
- External Height: 600 mm
 - External Width: 400 mm
 - External Depth: 200 mm
 - Body Material: 304 Stainless Steel
 - Transparent Door: No
 - IP Rating: IP66
 - Chassis Plate: Yes
 - Door Lock Type: Double Lock System



8428355 600 mm

RS PRO 304 STAINLESS STEEL WALL BOX, IP66, 600 MM X 400 MM X

- ขนาดบรรจุภัณฑ์: 1 x EA
- External Height: 600 mm
 - External Width: 400 mm
 - External Depth: 200 mm
 - Body Material: 304 Stainless Steel
 - Transparent Door: No
 - IP Rating: IP66
 - Chassis Plate: No
 - Door Lock Type: Single Lock System



8428349 600 mm

RS PRO 304 STAINLESS STEEL WALL BOX, IP66, 400 MM X 300 MM X

- ขนาดบรรจุภัณฑ์: 1 x EA
- External Height: 400 mm
 - External Width: 300 mm
 - External Depth: 150 mm
 - Body Material: 304 Stainless Steel
 - Transparent Door: No
 - IP Rating: IP66
 - Chassis Plate: Yes
 - Door Lock Type: Single Lock System



8428361 400 mm

RS PRO 304 STAINLESS STEEL WALL BOX, IP66, 700 MM X 500 MM X

- ขนาดบรรจุภัณฑ์: 1 x EA
- External Height: 700 mm
 - External Width: 500 mm
 - External Depth: 250 mm
 - Body Material: 304 Stainless Steel
 - Transparent Door: No
 - IP Rating: IP66
 - Chassis Plate: No
 - Door Lock Type: Double Lock System



8428364 700 mm

RS PRO 304 STAINLESS STEEL WALL BOX, IP66, 300 MM X 300 MM X

- ขนาดบรรจุภัณฑ์: 1 x EA
- External Height: 300 mm
 - External Width: 300 mm
 - External Depth: 200 mm
 - Body Material: 304 Stainless Steel
 - Transparent Door: No
 - IP Rating: IP66
 - Chassis Plate: No
 - Door Lock Type: Single Lock System



8428370 300 mm

RS PRO 304 STAINLESS STEEL WALL BOX, IP66, 500 MM X 500 MM X

- ขนาดบรรจุภัณฑ์: 1 x EA
- External Height: 500 mm
 - External Width: 500 mm
 - External Depth: 200 mm
 - Body Material: 304 Stainless Steel
 - Transparent Door: No
 - IP Rating: IP66
 - Chassis Plate: No
 - Door Lock Type: Single Lock System



8428374 500 mm

RS PRO 304 STAINLESS STEEL WALL BOX, IP66, 400 MM X 300 MM X

- ขนาดบรรจุภัณฑ์: 1 x EA
- External Height: 500 mm
 - External Width: 300 mm
 - External Depth: 150 mm
 - Body Material: 304 Stainless Steel
 - Transparent Door: No
 - IP Rating: IP66
 - Chassis Plate: No
 - Door Lock Type: Single Lock System



8428380 400 mm

RS PRO 304 STAINLESS STEEL WALL BOX, IP66, 400 MM X 300 MM X

- ขนาดบรรจุภัณฑ์: 1 x EA
- External Height: 400 mm
 - External Width: 300 mm
 - External Depth: 200 mm
 - Body Material: 304 Stainless Steel
 - Transparent Door: No
 - IP Rating: IP66
 - Chassis Plate: No
 - Door Lock Type: Single Lock System



8428383 400 mm

RS PRO 304 STAINLESS STEEL WALL BOX, IP66, 300 MM X 250 MM X

- ขนาดบรรจุภัณฑ์: 1 x EA
- External Height: 300 mm
 - External Width: 250 mm
 - External Depth: 150 mm
 - Body Material: 304 Stainless Steel
 - Transparent Door: No
 - IP Rating: IP66
 - Chassis Plate: No
 - Door Lock Type: Single Lock System



8428386 300 mm

IP66 WALL BOX, S/STEEL, 200X200X150MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- External Height: 200 mm
 - External Width: 200 mm
 - External Depth: 150 mm
 - Body Material: 304 Stainless Steel
 - Transparent Door: No
 - IP Rating: IP66
 - Chassis Plate: No
 - Door Lock Type: Single Lock System



8428399 200 mm

RS PRO 304 STAINLESS STEEL WALL BOX, IP66, 500 MM X 400 MM X

- ขนาดบรรจุภัณฑ์: 1 x EA
- External Height: 500 mm
 - External Width: 400 mm
 - External Depth: 250 mm
 - Body Material: 304 Stainless Steel
 - Transparent Door: No
 - IP Rating: IP66
 - Chassis Plate: No
 - Door Lock Type: Single Lock System



8428403 500 mm

RS PRO 304 STAINLESS STEEL WALL BOX, IP66, 300 MM X 300 MM X

- ขนาดบรรจุภัณฑ์: 1 x EA
- External Height: 300 mm
 - External Width: 300 mm
 - External Depth: 150 mm
 - Body Material: 304 Stainless Steel
 - Transparent Door: No
 - IP Rating: IP66
 - Chassis Plate: No
 - Door Lock Type: Single Lock System



8428406 300 mm

RS PRO 304 STAINLESS STEEL WALL BOX, IP66, 400 MM X 400 MM X

- ขนาดบรรจุภัณฑ์: 1 x EA
- External Height: 400 mm
 - External Width: 400 mm
 - External Depth: 200 mm
 - Body Material: 304 Stainless Steel
 - Transparent Door: No
 - IP Rating: IP66
 - Chassis Plate: No
 - Door Lock Type: Single Lock System



8428409 400 mm

RS PRO 304 STAINLESS STEEL WALL BOX, IP66, 360 MM X 180 MM X

- ขนาดบรรจุภัณฑ์: 1 x EA
- External Height: 360 mm
 - External Width: 180 mm
 - External Depth: 150 mm
 - Body Material: 304 Stainless Steel
 - Transparent Door: No
 - IP Rating: IP66
 - Chassis Plate: No
 - Door Lock Type: Single Lock System



8428421 360 mm

RS PRO 304 STAINLESS STEEL WALL BOX, IP66, 480 MM X 360 MM X

- ขนาดบรรจุภัณฑ์: 1 x EA
- External Height: 480 mm
 - External Width: 360 mm
 - External Depth: 150 mm
 - Body Material: 304 Stainless Steel
 - Transparent Door: No
 - IP Rating: IP66
 - Chassis Plate: No
 - Door Lock Type: Single Lock System



8428437 480 mm

RS PRO 304 STAINLESS STEEL WALL BOX, IP66, 360 MM X 360 MM X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- External Height: 360 mm
 - External Width: 360 mm
 - External Depth: 240 mm
 - Body Material: 304 Stainless Steel
 - Transparent Door: No
 - IP Rating: IP66
 - Chassis Plate: No
 - Door Lock Type: Single Lock System



8428440 360 mm

IP66 WALL BOX, S/STEEL, 240X180X150MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- External Height: 240 mm
 - External Width: 180 mm
 - External Depth: 150 mm
 - Body Material: 304 Stainless Steel
 - Transparent Door: No
 - IP Rating: IP66
 - Chassis Plate: No
 - Door Lock Type: Single Lock System



8428412 240 mm

RS PRO 304 STAINLESS STEEL WALL BOX, IP66, 240 MM X 240 MM X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- External Height: 240 mm
 - External Width: 240 mm
 - External Depth: 150 mm
 - Body Material: 304 Stainless Steel
 - Transparent Door: No
 - IP Rating: IP66
 - Chassis Plate: No
 - Door Lock Type: Single Lock System



8428419 240 mm

RS PRO 304 STAINLESS STEEL WALL BOX, IP66, 360 MM X 240 MM X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- External Height: 360 mm
 - External Width: 240 mm
 - External Depth: 150 mm
 - Body Material: 304 Stainless Steel
 - Transparent Door: No
 - IP Rating: IP66
 - Chassis Plate: No
 - Door Lock Type: Single Lock System



8428434 360 mm

RS PRO STEEL WALL BOX, IP66, 500 MM X 400 MM X 300MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- External Height: 500 mm
 - External Width: 400 mm
 - External Depth: 300 mm
 - Body Material: Steel
 - Transparent Door: No
 - IP Rating: IP66
 - Chassis Plate: No
 - Door Lock Type: Single Lock System



8428447 500 mm

RS PRO STEEL WALL BOX, IP66, 400 MM X 400 MM X 150MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- External Height: 400 mm
 - External Width: 400 mm
 - External Depth: 150 mm
 - Body Material: Steel
 - Transparent Door: No
 - IP Rating: IP66
 - Chassis Plate: Yes
 - Door Lock Type: Single Lock System



8428443 400 mm

RS PRO STEEL WALL BOX, IP66, 600 MM X 600 MM X 200MM

- ขนาดบรรจุภัณฑ์: **1 x KT**
- External Height: 600 mm
 - External Width: 600 mm
 - External Depth: 200 mm
 - Body Material: Steel
 - Transparent Door: No
 - IP Rating: IP66
 - Chassis Plate: Yes
 - Door Lock Type: Double Lock System



9155963 600 mm

RS PRO STEEL WALL BOX, IP66, 400 MM X 210 MM X 600MM

- ขนาดบรรจุภัณฑ์: **1 x KT**
- External Height: 400 mm
 - External Width: 210 mm
 - External Depth: 600 mm
 - Body Material: Steel
 - Transparent Door: No
 - IP Rating: IP66
 - Chassis Plate: Yes
 - Door Lock Type: Single Lock System



9155979 400 mm

RS PRO TOP PLUNGER, 2NC/1NO, IP67, PLASTIC HOUSING

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Normal State Configuration: 2NC/1NO
 - IP Rating: IP67
 - Housing Material: Plastic
 - Connection Type: M20
 - Length: 31 mm
 - Width: 31 mm
 - Depth: 95 mm
 - Mechanical Life: 10000000 Operacje



1797561 2NC/1NO

RS PRO TOP PLUNGER, 2NC, IP67, PLASTIC HOUSING

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Normal State Configuration: 2NC
 - IP Rating: IP67
 - Housing Material: Plastic
 - Connection Type: M20
 - Length: 31 mm
 - Width: 31 mm
 - Depth: 95 mm
 - Mechanical Life: 10000000 Operacje



1797562 2NC

RS PRO TOP PLUNGER, NO/NC, IP67, PLASTIC HOUSING

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Normal State Configuration: NO/NC
 - IP Rating: IP67
 - Housing Material: Plastic
 - Connection Type: M20
 - Length: 31 mm
 - Width: 31 mm
 - Depth: 95 mm
 - Mechanical Life: 10000000 Operacje



1797563 NO/NC

RS PRO CATS WHISKER TOP PLUNGER, NO/NC, IP67, GLASS

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Actuator Type: Cats Whisker
 - Normal State Configuration: NO/NC
 - IP Rating: IP67
 - Housing Material: Glass Reinforced Plastic (GRP)
 - Length: 31 mm
 - Width: 31 mm
 - Depth: 172 mm
 - Mechanical Life: 10000000 Operacje



1797565 Cats Whisker

RS PRO ROLLER LEVER INTERLOCK SWITCH, NO/NC, IP67, GLASS

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Actuator Type: Roller Lever
 - Normal State Configuration: NO/NC
 - IP Rating: IP67
 - Housing Material: Glass Reinforced Plastic (GRP)
 - Length: 31 mm
 - Width: 31 mm
 - Depth: 89 mm
 - Mechanical Life: 10000000 Operacje



1797566 Roller Lever

RS PRO ROLLER PLUNGER TOP PLUNGER, NO/NC, IP67, GLASS

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Actuator Type: Roller Plunger
 - Normal State Configuration: NO/NC
 - IP Rating: IP67
 - Housing Material: Glass Reinforced Plastic (GRP)
 - Length: 31 mm
 - Width: 30.5 mm
 - Depth: 84.5 mm
 - Mechanical Life: 10000000 Operacje



1797567 Roller Plunger

RS PRO PLUNGER LIMIT SWITCH, NO/NC, IP67, GLASS REINFORCED

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Actuator Type: Plunger
 - Normal State Configuration: NO/NC
 - IP Rating: IP67
 - Housing Material: Glass Reinforced Plastic (GRP)
 - Length: 31 mm
 - Width: 31 mm
 - Depth: 74.5 mm
 - Mechanical Life: 10000000 Operations



1797568 Plunger

RS PRO ROLLER LEVER LIMIT SWITCH, NO/NC, IP67, GLASS REINFORCED

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Actuator Type: Roller Lever
 - Normal State Configuration: NO/NC
 - IP Rating: IP67
 - Housing Material: Glass Reinforced Plastic (GRP)
 - Length: 31 mm
 - Width: 45 mm
 - Depth: 62 mm
 - Mechanical Life: 10000000 Operacje



1797569 Roller Lever

RS PRO ROLLER LEVER TOP PLUNGER, NO/NC, IP67, GLASS REINFORCED

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Actuator Type: Roller Lever
 - Normal State Configuration: NO/NC
 - IP Rating: IP67
 - Housing Material: Glass Reinforced Plastic (GRP)
 - Length: 31 mm
 - Width: 47.5 mm
 - Depth: 107 mm
 - Mechanical Life: 10000000 Operacje



1797570 Roller Lever

RS PRO LIMIT SWITCH OPERATING HEAD FOR USE WITH 1797561,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Actuator
 - For Use With: 1797561, 1797563, 1797564



1808172 Actuator

RS PRO SAFETY INTERLOCK SWITCH, 600V AC, 2NC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 600 V ac
 - Actuator Type: Key
 - Conduit Entry: PG13.5
 - Normal State Configuration: 2NC
 - Housing Material: Plastic
 - IP Rating: IP67
 - Maximum AC Voltage: 600 V
 - Width: 31 mm



1797564 600 V ac

RS PRO IMAGER 2D SCANNING BARCODE SCANNER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Product Type: Barcode Scanner
 - Model: H261U
 - Scanning Technology: Imager
 - Maximum Scan Distance: 50 cm
 - Wireless: No
 - 2D Scanning: Yes
 - Interface: USB
 - Dimensions: 180 x 65 x 105 mm



2067501 Barcode Scanner

RS PRO CAT6 ETHERNET CABLE, RJ45 TO RJ45, U/UTP SHIELD, BLUE PVC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- LAN Category: Cat6
 - Terminated/Unterminated: Terminated
 - Connector A: RJ45
 - Connector A Gender: Male
 - Connector B: RJ45
 - Connector B Gender: Male
 - Length: 2 m
 - Outer Sheath Material: PVC



2055985 Cat6

RS PRO PLASTIC FIBRE OPTIC SENSOR 0.01 MM, NPN OUTPUT IO-

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Detection Range: 0.01 mm
 - Output Type: NPN
 - Fibre Optic Type: Plastic
 - Terminal Type: 2m PVC cable
 - Response Time: 60 seconds
 - Power Consumption: 1.44 W
 - IP Rating: IP54
 - Supply Voltage: 24 V dc



2040681 0.01 mm

RS PRO PLASTIC FIBRE OPTIC SENSOR 0.01 MM, PNP OUTPUT IO-

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Detection Range: 0.01 mm
 - Output Type: PNP
 - Fibre Optic Type: Plastic
 - Terminal Type: 2m PVC cable
 - Response Time: <0.0002 (Fine mode) seconds, <0.0005 (Turbo mode) seconds, <0.00055 (Super) seconds
 - Power Consumption: 1.44 W
 - IP Rating: IP54
 - Supply Voltage: 24 V dc



2040682 0.01 mm

RS PRO PLASTIC FIBRE OPTIC SENSOR 180 MM, IP54

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Detection Range: 180 mm
 - Fibre Optic Type: Plastic
 - Terminal Type: Fiber Amplifier
 - IP Rating: IP54
 - Housing Material: Plastic
 - Maximum Operating Temperature: +70 °C
 - Minimum Operating Temperature: -55 °C



2199007 180 mm

RS PRO PLASTIC FIBRE OPTIC SENSOR 140 MM, IP54

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Detection Range: 140 mm
 - Fibre Optic Type: Plastic
 - Terminal Type: Fiber Amplifier
 - IP Rating: IP54
 - Housing Material: Plastic
 - Maximum Operating Temperature: +70 °C
 - Minimum Operating Temperature: -55 °C



2199008 140 mm

RS PRO PLASTIC FIBRE OPTIC SENSOR 500 MM, IP54

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Detection Range: 500 mm
 - Fibre Optic Type: Plastic
 - Terminal Type: Fiber Amplifier
 - IP Rating: IP54
 - Housing Material: Plastic
 - Maximum Operating Temperature: +70 °C
 - Minimum Operating Temperature: -55 °C



2199009 500 mm

RS PRO PLASTIC FIBRE OPTIC SENSOR 1000 MM, IP54

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Detection Range: 1000 mm
 - Fibre Optic Type: Plastic
 - Terminal Type: Fiber Amplifier
 - IP Rating: IP54
 - Housing Material: Plastic
 - Maximum Operating Temperature: +70 °C
 - Minimum Operating Temperature: -55 °C



2199010 1000 mm

RS PRO PLASTIC FIBRE OPTIC SENSOR 1000 MM, IP54

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Detection Range: 1000 mm
 - Fibre Optic Type: Plastic
 - Terminal Type: Fiber Amplifier
 - IP Rating: IP54
 - Housing Material: Plastic
 - Maximum Operating Temperature: +70 °C
 - Minimum Operating Temperature: -55 °C



2199011 1000 mm

RS PRO FIBRE OPTIC SENSOR 500 MM, IP65

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Detection Range: 500 mm
 - Terminal Type: M4
 - Electrical Connection: Cable
 - IP Rating: IP65
 - Length: 500 mm
 - Standards Met: CE



8967285 500 mm

RS PRO FIBRE OPTIC SENSOR 110 MM, IP65

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Detection Range: 110 mm
 - Terminal Type: M6
 - Electrical Connection: Cable
 - IP Rating: IP65
 - Length: 110 mm
 - Standards Met: CE



8967298 110 mm

RS PRO FIBRE OPTIC SENSOR, NPN-NO, PNP-NC OUTPUT, IP65, 12 → 24 V

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Type: NPN-NO, PNP-NC
 - Response Time: <1 ms
 - Light Source: Red LED
 - Electrical Connection: PVC Cable
 - Switching Frequency: 50 Hz
 - IP Rating: IP65
 - Housing Material: ABS, PC
 - Supply Voltage: 12 → 24 V dc



8967305 NPN-NO, PNP-NC

RS PRO CIRCULAR CONNECTOR

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Connector A: M12 A Coded CANopen/DeviceNet Terminating Resistor
 - Connector A Gender: Male
 - Connector B Gender: Male
 - Connector A Number of Contacts: 4
 - Current Rating: 4 A
 - IP Rating: IP67
 - Voltage Rating: 30 V
 - Maximum Operating Temperature: +75 °C



2055982 M12 A Coded

SWITCH,SENSOR,PROXIMITY,REED,H D,FORM A,N/O

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Switch Shape: Rectangular
 - Normal State Configuration: NO
 - Maximum Current: 5 A
 - Maximum AC Voltage: 1500 V
 - Maximum DC Voltage: 1500 V
 - Contact Resistance: 100 mΩ
 - Length: 80 mm
 - Maximum Operating Temperature: +85 °C



339746 Rectangular

SWITCH,SENSOR,PROXIMITY,REED,H D,FORM C,CHANGEOVER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Switch Shape: Rectangular
 - Maximum Current: 2 A
 - Maximum AC Voltage: 400 V
 - Maximum DC Voltage: 400 V
 - Contact Resistance: 100 mΩ
 - Length: 80 mm
 - Width: 10 mm
 - Maximum Operating Temperature: +85 °C



339752 Rectangular

REED SWITCH SIDE FACING

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Switch Shape: Rectangular
 - Pole and Throw Configuration: SPST-NO
 - Normal State Configuration: NO/NC
 - Terminal Type: Wire Lead
 - Maximum Current: 250 mA
 - Maximum AC Voltage: 140 V
 - Maximum DC Voltage: 200 V
 - Switching Frequency: 100 Hz



1365753 Rectangular

RS PRO REED SWITCH RECTANGULAR 140V, NO/NC, 2.75A

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Switch Shape: Rectangular
 - Pole and Throw Configuration: NO/NC
 - Terminal Type: Wire Lead
 - Maximum Current: 2.75 A
 - Maximum AC Voltage: 140 V
 - Maximum DC Voltage: 200 V
 - Switching Frequency: 100 Hz
 - Contact Resistance: 100 mΩ



1365754 Rectangular

RS PRO REED SWITCH RECTANGULAR 140V, NO/NC, 2.75A

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Switch Shape: Rectangular
 - Pole and Throw Configuration: SPST-NO
 - Normal State Configuration: NO/NC
 - Terminal Type: Wire Lead
 - Maximum Current: 2.75 A
 - Maximum AC Voltage: 140 V
 - Maximum DC Voltage: 200 V
 - Switching Frequency: 100 Hz



1365755 Rectangular

RS PRO REED SWITCH RECTANGULAR 140V, NO/NC, 2.75A

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Switch Shape: Rectangular
 - Pole and Throw Configuration: SPST-NO
 - Normal State Configuration: NO/NC
 - Terminal Type: Wire Lead
 - Maximum Current: 2.75 A
 - Maximum AC Voltage: 140 V
 - Maximum DC Voltage: 200 V
 - Switching Frequency: 100 Hz



1365756 Rectangular

RS PRO REED SWITCH RECTANGULAR 140V, NO/NC, 2.75A

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Switch Shape: Rectangular
 - Pole and Throw Configuration: SPST-NO
 - Normal State Configuration: NO/NC
 - Terminal Type: Wire Lead
 - Maximum Current: 2.75 A
 - Maximum AC Voltage: 140 V
 - Maximum DC Voltage: 200 V
 - Switching Frequency: 100 Hz



1365757 Rectangular

RS PRO REED SWITCH RECTANGULAR 400V, NC, 1A

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Switch Shape: Rectangular
 - Pole and Throw Configuration: SPST-NO
 - Normal State Configuration: NC
 - Terminal Type: Wire Lead
 - Maximum Current: 1 A
 - Maximum AC Voltage: 400 V
 - Contact Resistance: 150 mΩ
 - Total Length: 1032.5 mm



1365758 Rectangular

RS PRO REED SWITCH RECTANGULAR 200V, NO, 500MA, IP67

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Switch Shape: Rectangular
 - Normal State Configuration: NO
 - Maximum Current: 500 mA
 - Maximum AC Voltage: 200 V
 - Contact Resistance: 300 mΩ
 - Total Length: 312 mm
 - Length: 32 mm
 - Depth: 15 mm



3614911 Rectangular

RS PRO REED SWITCH CYLINDRICAL 200V, NO, 500MA

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Switch Shape: Cylindrical
 - Normal State Configuration: NO
 - Terminal Type: Screw
 - Maximum Current: 500 mA
 - Maximum AC Voltage: 200 V
 - Maximum DC Voltage: 200 V
 - Contact Resistance: 200 mΩ
 - Total Length: 308 mm



3614933 Cylindrical

REED PROXIMITY SWITCHES, CYLINDRICAL REED SENSOR 4MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Switch Shape: Cylindrical
 - Pole and Throw Configuration: SPST
 - Normal State Configuration: NO
 - Terminal Type: Wire Lead
 - Maximum Current: 1.5 A
 - Maximum AC Voltage: 180 V
 - Maximum DC Voltage: 180 V
 - Contact Resistance: 160 mΩ



5308911 Cylindrical

REED PROXIMITY SWITCHES, CYLINDRICAL REED SENSOR ONLY

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Switch Shape: Cylindrical
 - Pole and Throw Configuration: SPST
 - Normal State Configuration: NO
 - Terminal Type: Wire Lead
 - Maximum Current: 1 A
 - Maximum AC Voltage: 400 V
 - Maximum DC Voltage: 400 V
 - Contact Resistance: 150 mΩ



5308927 Cylindrical

REED PROXIMITY SWITCHES, MOULDED REED SENSOR, SCREW

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Switch Shape: Flat
 - Pole and Throw Configuration: SPST
 - Normal State Configuration: NO
 - Terminal Type: Screw
 - Maximum Current: 500 mA
 - Maximum AC Voltage: 180 V
 - Maximum DC Voltage: 500 V
 - Contact Resistance: 150 mΩ



5308949 Flat

RS PRO REED SWITCH FLAT 200V, NO, 1A

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Switch Shape: Flat
 - Pole and Throw Configuration: SPST
 - Normal State Configuration: NO
 - Maximum Current: 1 A
 - Maximum AC Voltage: 200 V
 - Maximum DC Voltage: 200 V
 - Contact Resistance: 150 mΩ
 - Total Length: 19.5 mm



5308961 Flat

RS PRO REED SWITCH FLAT 200V, NO, 500MA

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Switch Shape: Flat
 - Pole and Throw Configuration: SPST
 - Normal State Configuration: NO
 - Maximum Current: 500 mA
 - Maximum AC Voltage: 200 V
 - Maximum DC Voltage: 200 V
 - Contact Resistance: 150 mΩ
 - Total Length: 15.6 mm



5308977 Flat

RS PRO REED SWITCH FLAT 170V, NO, 500MA

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Switch Shape: Flat
 - Pole and Throw Configuration: SPST
 - Normal State Configuration: NO
 - Maximum Current: 500 mA
 - Maximum AC Voltage: 170 V
 - Maximum DC Voltage: 170 V
 - Contact Resistance: 200 mΩ
 - Total Length: 12.5 mm



5308999 Flat

RS PRO REED SWITCH FLAT 200V, NO, 1.5A

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Switch Shape: Flat
 - Pole and Throw Configuration: SPNO
 - Normal State Configuration: NO
 - Maximum Current: 1.5 A
 - Maximum AC Voltage: 200 V
 - Maximum DC Voltage: 200 V
 - Contact Resistance: 150 mΩ
 - Total Length: 15.6 mm



5309009 Flat

RS PRO PROXIMITY SWITCH RECTANGULAR 250V, NO, 500MA

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Switch Shape: Rectangular
 - Normal State Configuration: NO
 - Terminal Type: Wire Lead
 - Maximum Current: 500 mA
 - Maximum AC Voltage: 250 V
 - Maximum DC Voltage: 150 V
 - Switching Frequency: 200 Hz
 - Contact Resistance: 150 mΩ



8110736 Rectangular

REED SWITCH, CHANGE OVER, 175VAC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Switch Shape: Rectangular
 - Normal State Configuration: CO
 - Terminal Type: Wire Lead
 - Maximum Current: 400 mA
 - Maximum AC Voltage: 125 V
 - Maximum DC Voltage: 175 V
 - Contact Resistance: 120 mΩ
 - Total Length: 328.5 mm



8110748 Rectangular

RS PRO CYLINDRICAL MAGNET 3MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Magnet Type: Cylindrical
 - Width/Diameter: 3 mm
 - Length: 12 mm



5361726 Cylindrical

RS PRO DIFFUSE PHOTOELECTRIC SENSOR, BARREL SENSOR, 200 MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Style: Barrel
 - Detection Type: Diffuse
 - Detection Range: 200 mm
 - Output Type: PNP
 - Electrical Connection: M12 Connector
 - Maximum DC Voltage: 30 V
 - Light Source: Infrared
 - IP Rating: IP67



256405 Barrel

RS PRO POLARISED RETRO REFLECTION PHOTOELECTRIC

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Style: Block
 - Detection Type: Polarised Retro Reflection
 - Detection Range: 3 m
 - Output Type: NPN NO/NC
 - Electrical Connection: Cable
 - Maximum DC Voltage: 30 V
 - Terminal Type: M8 Connector
 - Light Source: LED



2018161 Block

RS PRO POLARISED RETRO REFLECTION PHOTOELECTRIC

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Style: Block
 - Detection Type: Polarised Retro Reflection
 - Detection Range: 3 m
 - Output Type: PNP NO/NC
 - Electrical Connection: Cable
 - Maximum DC Voltage: 30 V
 - Terminal Type: M8 Connector
 - Light Source: LED



2018163 Block

RS PRO DIFFUSE PHOTOELECTRIC SENSOR, BLOCK SENSOR, 1 M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Style: Block
 - Detection Type: Diffuse
 - Detection Range: 1 m
 - Output Type: NPN
 - Electrical Connection: Cable 2 m
 - Terminal Type: Cable 2 m
 - Series: PSE



2024424 Block

RS PRO DIFFUSE PHOTOELECTRIC SENSOR, BLOCK SENSOR, 1 M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Style: Block
 - Detection Type: Diffuse
 - Detection Range: 1 m
 - Output Type: PNP
 - Electrical Connection: Cable 2 m
 - Terminal Type: Cable 2 m
 - Series: PSE



2024426 Block

RS PRO DIFFUSE PHOTOELECTRIC SENSOR, BLOCK SENSOR, 100 MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Style: Block
 - Detection Type: Diffuse
 - Detection Range: 100 mm
 - Output Type: NPN
 - Electrical Connection: Cable 2 m
 - Terminal Type: Cable 2 m
 - Series: PSE



2024428 Block

RS PRO DIFFUSE PHOTOELECTRIC SENSOR, BLOCK SENSOR, 100 MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Style: Block
 - Detection Type: Diffuse
 - Detection Range: 100 mm
 - Output Type: NPN
 - Electrical Connection: M8 Connector
 - Terminal Type: M8 Connector
 - Series: PSE



2024429 Block

RS PRO DIFFUSE PHOTOELECTRIC SENSOR, BLOCK SENSOR, 100 MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Style: Block
 - Detection Type: Diffuse
 - Detection Range: 100 mm
 - Output Type: PNP
 - Electrical Connection: M8 Connector
 - Terminal Type: M8 Connector
 - Series: PSE



2024432 Block

RS PRO DIFFUSE PHOTOELECTRIC SENSOR, BLOCK SENSOR, 300 MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Style: Block
 - Detection Type: Diffuse
 - Detection Range: 300 mm
 - Output Type: PNP NO/NC
 - Electrical Connection: M8 Connector
 - Terminal Type: M8 Connector
 - Series: PSE



2024436 Block

RS PRO POLARISED RETRO REFLECTION PHOTOELECTRIC

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Style: Block
 - Detection Type: Polarised Retro Reflection
 - Detection Range: 4 m
 - Output Type: PNP NO/NC
 - Electrical Connection: M8 Connector
 - Terminal Type: M8 Connector
 - Series: PSE



2024440 Block

RS PRO THROUGH BEAM RECEIVER PHOTOELECTRIC SENSOR, BLOCK

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Style: Block
 - Detection Type: Through Beam Receiver
 - Detection Range: 10 m
 - Output Type: PNP NO/NC
 - Electrical Connection: M8 Connector
 - Terminal Type: M8 Connector
 - Series: PSE



2024442 Block

RS PRO THROUGH BEAM RECEIVER PHOTOELECTRIC SENSOR, BLOCK

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Style: Block
 - Detection Type: Through Beam Receiver
 - Detection Range: 10 m
 - Output Type: PNP NO/NC
 - Electrical Connection: M8 Connector
 - Terminal Type: M8 Connector
 - Series: PSE



2024444 Block

RS PRO BACKGROUND SUPPRESSION PHOTOELECTRIC SENSOR, BLOCK

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Style: Block
 - Detection Type: Background Suppression
 - Detection Range: 350 mm
 - Output Type: PNP NO/NC
 - Electrical Connection: M8 Connector
 - Terminal Type: M8 Connector
 - Series: PSE



2024451 Block

RS PRO THROUGH BEAM RECEIVER PHOTOELECTRIC SENSOR, BLOCK

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Style: Block
 - Detection Type: Through Beam Receiver
 - Detection Range: 10 m
 - Output Type: NPN NO/NC
 - Electrical Connection: Cable 2 m
 - Terminal Type: Cable 2 m
 - Series: PSE



2024441 Block

RS PRO THROUGH BEAM RECEIVER PHOTOELECTRIC SENSOR, BLOCK

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Style: Block
 - Detection Type: Through Beam Receiver
 - Detection Range: 4 m
 - Output Type: PNP NO/NC
 - Electrical Connection: Cable 2 m
 - Terminal Type: Cable 2 m
 - Series: PSE



2024443 Block

RS PRO THROUGH BEAM EMITTER PHOTOELECTRIC SENSOR, BLOCK

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Style: Block
 - Detection Type: Through Beam Emitter
 - Detection Range: 10 m
 - Electrical Connection: Cable 2 m
 - Terminal Type: Cable 2 m
 - Series: PSE



2024445 Block

RS PRO POLARISED RETRO REFLECTION PHOTOELECTRIC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Style: Block
 - Detection Type: Polarised Retro Reflection
 - Detection Range: 3 m
 - Output Type: NPN NO/NC
 - Electrical Connection: Cable 2 m
 - Terminal Type: Cable 2 m
 - Series: PSR



2024457 Block

RS PRO THROUGH BEAM EMITTER PHOTOELECTRIC SENSOR, BLOCK

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Style: Block
 - Detection Type: Through Beam Emitter
 - Detection Range: 20 m
 - Electrical Connection: Cable 2 m
 - Terminal Type: Cable 2 m
 - Series: PSR



2024461 Block

RS PRO THROUGH BEAM RECEIVER PHOTOELECTRIC SENSOR, BLOCK

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Style: Block
 - Detection Type: Through Beam Receiver
 - Detection Range: 20 m
 - Output Type: NPN NO/NC
 - Electrical Connection: Cable 2 m
 - Terminal Type: Cable 2 m
 - Series: PSR



2024463 Block

RS PRO THROUGH BEAM RECEIVER PHOTOELECTRIC SENSOR, BLOCK

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Style: Block
 - Detection Type: Through Beam Receiver
 - Detection Range: 20 m
 - Output Type: PNP NO/NC
 - Electrical Connection: Cable 2 m
 - Terminal Type: Cable 2 m
 - Series: PSR



2024465 Block

RS PRO DIFFUSE PHOTOELECTRIC SENSOR, BLOCK SENSOR, 2 M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Style: Block
 - Detection Type: Diffuse
 - Detection Range: 2 m
 - Output Type: PNP/NPN
 - Electrical Connection: Cable 2 m
 - Terminal Type: Cable 2 m
 - Series: PTE



2024472 Block

RS PRO DIFFUSE PHOTOELECTRIC SENSOR, BLOCK SENSOR, 2 M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Style: Block
 - Detection Type: Diffuse
 - Detection Range: 2 m
 - Output Type: Relay NO/NC
 - Electrical Connection: Cable 2 m
 - Terminal Type: Cable 2 m
 - Series: PTE



2024475 Block

RS PRO POLARISED RETRO REFLECTION PHOTOELECTRIC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Style: Block
 - Detection Type: Polarised Retro Reflection
 - Detection Range: 5 m
 - Output Type: Relay NO/NC
 - Electrical Connection: Cable 2 m
 - Terminal Type: Cable 2 m
 - Series: PTE



2024479 Block

RS PRO THROUGH BEAM EMITTER PHOTOELECTRIC SENSOR, BLOCK

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Style: Block
 - Detection Type: Through Beam Emitter
 - Detection Range: 60 m
 - Output Type: Relay
 - Electrical Connection: Cable 2 m
 - Terminal Type: Cable 2 m
 - Series: PTE



2024482 Block

RS PRO THROUGH BEAM EMITTER PHOTOELECTRIC SENSOR, BLOCK

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Style: Block
 - Detection Type: Through Beam Emitter
 - Detection Range: 20 m
 - Electrical Connection: M12 Connector
 - Terminal Type: M12 Connector
 - Series: PSR



2024462 Block

RS PRO THROUGH BEAM RECEIVER PHOTOELECTRIC SENSOR, BLOCK

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Style: Block
 - Detection Type: Through Beam Receiver
 - Detection Range: 20 m
 - Output Type: NPN NO/NC
 - Electrical Connection: M12 Connector
 - Terminal Type: M12 Connector
 - Series: PSR



2024464 Block

RS PRO THROUGH BEAM RECEIVER PHOTOELECTRIC SENSOR, BLOCK

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Style: Block
 - Detection Type: Through Beam Receiver
 - Detection Range: 20 m
 - Output Type: PNP NO/NC
 - Electrical Connection: M12 Connector
 - Terminal Type: M12 Connector
 - Series: PSR



2024466 Block

RS PRO THROUGH BEAM RECEIVER PHOTOELECTRIC SENSOR, BLOCK

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Style: Block
 - Detection Type: Through Beam Receiver
 - Detection Range: 60 m
 - Output Type: Relay NO/NC
 - Electrical Connection: Cable 2 m
 - Terminal Type: Cable 2 m
 - Series: PTE



2024483 Block

RS PRO DIFFUSE PHOTOELECTRIC SENSOR, BLOCK SENSOR, 0 → 2 M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Style: Block
 - Detection Type: Diffuse
 - Detection Range: 0 → 2 m
 - Output Type: NPN NO/NC
 - Electrical Connection: Terminal Block
 - Terminal Type: Terminal
 - Light Source: Infrared LED
 - Maximum Operating Temperature: +55 °C



2025448 Block

RS PRO DIFFUSE PHOTOELECTRIC SENSOR, BLOCK SENSOR, 0 → 2 M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Style: Block
 - Detection Type: Diffuse
 - Detection Range: 0 → 2 m
 - Output Type: PNP NO/NC
 - Electrical Connection: Terminal Block
 - Terminal Type: Terminal
 - Light Source: Infrared LED
 - IP Rating: IP67



2025450 Block

RS PRO DIFFUSE PHOTOELECTRIC SENSOR, BLOCK SENSOR, 0 → 2 M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Style: Block
 - Detection Type: Diffuse
 - Detection Range: 0 → 2 m
 - Output Type: Relay NO/NC
 - Electrical Connection: Terminal Block
 - Terminal Type: Terminal
 - Light Source: Infrared LED
 - IP Rating: IP67



2025451 Block

RS PRO DIFFUSE PHOTOELECTRIC SENSOR, BLOCK SENSOR, 0 → 800

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Style: Block
 - Detection Type: Diffuse
 - Detection Range: 0 → 800 mm
 - Output Type: Relay NO/NC
 - Electrical Connection: Terminal Block
 - Terminal Type: Terminal
 - IP Rating: IP67
 - Maximum Operating Temperature: +55 °C



2025452 Block

RS PRO RETROREFLECTIVE PHOTOELECTRIC SENSOR, BLOCK

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Style: Block
 - Detection Type: Retroreflective
 - Detection Range: 5 m
 - Output Type: Relay NO/NC
 - Electrical Connection: Terminal Block
 - Maximum AC Voltage: 240 V
 - Maximum DC Voltage: 240 V
 - Terminal Type: Terminal



2025456 Block

RS PRO POLARISED RETRO REFLECTION PHOTOELECTRIC

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Style: Block
 - Detection Type: Polarised Retro Reflection
 - Detection Range: 12 m
 - Output Type: NPN NO/NC
 - Electrical Connection: Terminal Block
 - Maximum DC Voltage: 30 V
 - Terminal Type: Terminal
 - Light Source: Red LED



2025457 Block

RS PRO THROUGH BEAM PHOTOELECTRIC SENSOR, BLOCK

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Style: Block
 - Detection Type: Through Beam
 - Detection Range: 30 m
 - Output Type: Relay
 - Electrical Connection: Terminal Block
 - Maximum AC Voltage: 240 V
 - Maximum DC Voltage: 240 V
 - Terminal Type: Terminal



2025460 Block

RS PRO THROUGH BEAM PHOTOELECTRIC SENSOR, BLOCK

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Style: Block
 - Detection Type: Through Beam
 - Detection Range: 30 m
 - Output Type: Relay NO/NC
 - Electrical Connection: Terminal Block
 - Maximum AC Voltage: 240 V
 - Maximum DC Voltage: 240 V
 - Terminal Type: Terminal



2025462 Block

RS PRO DIFFUSE PHOTOELECTRIC SENSOR, BARREL SENSOR, 150 MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Style: Barrel
 - Detection Type: Diffuse
 - Detection Range: 150 mm
 - Output Type: NPN NO
 - Electrical Connection: Cable 2 m
 - Maximum DC Voltage: 30 V
 - Terminal Type: Cable 2 m
 - Light Source: Yellow LED



2043961 Barrel

RS PRO DIFFUSE PHOTOELECTRIC SENSOR, BARREL SENSOR, 150 MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Style: Barrel
 - Detection Type: Diffuse
 - Detection Range: 150 mm
 - Output Type: PNP NO
 - Electrical Connection: Cable 2 m
 - Maximum DC Voltage: 30 V
 - Terminal Type: Cable 2 m
 - Light Source: Yellow LED



2043962 Barrel

RS PRO DIFFUSE PHOTOELECTRIC SENSOR, BARREL SENSOR, 150 MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Style: Barrel
 - Detection Type: Diffuse
 - Detection Range: 150 mm
 - Output Type: NPN NO
 - Electrical Connection: M12 Connector
 - Maximum DC Voltage: 30 V
 - Terminal Type: M12 Connector
 - Light Source: Yellow LED



2043963 Barrel

RS PRO DIFFUSE PHOTOELECTRIC SENSOR, BARREL SENSOR, 150 MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Style: Barrel
 - Detection Type: Diffuse
 - Detection Range: 150 mm
 - Output Type: PNP NO
 - Electrical Connection: Cable 2 m
 - Maximum DC Voltage: 30 V
 - Terminal Type: Cable 2 m
 - Light Source: Yellow LED



2043967 Barrel

RS PRO DIFFUSE PHOTOELECTRIC SENSOR, BARREL SENSOR, 150 MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Style: Barrel
 - Detection Type: Diffuse
 - Detection Range: 150 mm
 - Output Type: PNP NO
 - Electrical Connection: M12 Connector
 - Maximum DC Voltage: 30 V
 - Terminal Type: M12 Connector
 - Light Source: Yellow LED



2043965 Barrel

RS PRO DIFFUSE PHOTOELECTRIC SENSOR, BARREL SENSOR, 400 MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Style: Barrel
 - Detection Type: Diffuse
 - Detection Range: 400 mm
 - Output Type: NPN NO/NC
 - Electrical Connection: Cable 2 m
 - Maximum DC Voltage: 30 V
 - Terminal Type: Cable 2 m
 - Light Source: Yellow LED



2043968 Barrel

RS PRO DIFFUSE PHOTOELECTRIC SENSOR, BARREL SENSOR, 400 MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Style: Barrel
 - Detection Type: Diffuse
 - Detection Range: 400 mm
 - Output Type: PNP NO/NC
 - Electrical Connection: Cable 2 m
 - Maximum DC Voltage: 30 V
 - Terminal Type: Cable 2 m
 - Light Source: Yellow LED



2043969 Barrel

RS PRO DIFFUSE PHOTOELECTRIC SENSOR, BARREL SENSOR, 400 MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Style: Barrel
 - Detection Type: Diffuse
 - Detection Range: 400 mm
 - Output Type: PNP NO/NC
 - Electrical Connection: M12 Connector
 - Maximum DC Voltage: 30 V
 - Terminal Type: M12 Connector
 - Light Source: Yellow LED



2043971 Barrel

RS PRO DIFFUSE PHOTOELECTRIC SENSOR, BARREL SENSOR, 400 MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Style: Barrel
 - Detection Type: Diffuse
 - Detection Range: 400 mm
 - Output Type: NPN NO/NC
 - Electrical Connection: M12 Connector
 - Maximum DC Voltage: 30 V
 - Terminal Type: M12 Connector
 - Light Source: Yellow LED



2043970 Barrel

RS PRO RETROREFLECTIVE PHOTOELECTRIC SENSOR, BARREL

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Style: Barrel
 - Detection Type: Retroreflective
 - Detection Range: 3 m
 - Output Type: PNP NO
 - Electrical Connection: M12 Connector
 - Maximum DC Voltage: 30 V
 - Terminal Type: M12 Connector
 - Light Source: Yellow LED



2043983 Barrel

RS PRO DIFFUSE PHOTOELECTRIC SENSOR, BARREL SENSOR, 400 MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Style: Barrel
 - Detection Type: Diffuse
 - Detection Range: 400 mm
 - Output Type: NPN NO/NC
 - Electrical Connection: Cable 2 m
 - Maximum DC Voltage: 30 V
 - Terminal Type: Cable 2 m
 - Light Source: Yellow LED



2043972 Barrel

RS PRO THROUGH BEAM PHOTOELECTRIC SENSOR, BARREL

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Style: Barrel
 - Detection Type: Through Beam
 - Detection Range: 20 m
 - Output Type: NPN NO/NC
 - Electrical Connection: Cable 2 m
 - Maximum DC Voltage: 30 V
 - Terminal Type: Cable 2 m
 - Light Source: LED



2043998 Barrel

RS PRO THROUGH BEAM PHOTOELECTRIC SENSOR, BARREL

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Style: Barrel
 - Detection Type: Through Beam
 - Detection Range: 20 m
 - Output Type: PNP NO/NC
 - Electrical Connection: Cable 2 m
 - Maximum DC Voltage: 30 V
 - Terminal Type: Cable 2 m
 - Light Source: LED



2043999 Barrel

RS PRO THROUGH BEAM (TRANSMITTER) PHOTOELECTRIC

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Style: Barrel
 - Detection Type: Through Beam (transmitter)
 - Detection Range: 10 m
 - Electrical Connection: Cable 2 m
 - Maximum DC Voltage: 30 V
 - Terminal Type: Cable 2 m
 - Light Source: LED
 - IP Rating: IP67



2044000 Barrel

RS PRO THROUGH BEAM PHOTOELECTRIC SENSOR, BARREL

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Style: Barrel
 - Detection Type: Through Beam
 - Detection Range: 10 m
 - Output Type: PNP NO/NC
 - Electrical Connection: Cable 2 m
 - Maximum DC Voltage: 30 V
 - Terminal Type: Cable 2 m
 - Light Source: LED



2044003 Barrel

RS PRO THROUGH BEAM PHOTOELECTRIC SENSOR, BARREL

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Style: Barrel
 - Detection Type: Through Beam
 - Detection Range: 20 m
 - Output Type: NPN NO/NC
 - Electrical Connection: Cable 2 m
 - Maximum DC Voltage: 30 V
 - Terminal Type: Cable 2 m
 - Light Source: LED



2044004 Barrel

RS PRO THROUGH BEAM PHOTOELECTRIC SENSOR, BARREL

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Style: Barrel
 - Detection Type: Through Beam
 - Detection Range: 10 m
 - Output Type: NPN NO/NC
 - Electrical Connection: Cable 2 m
 - Maximum DC Voltage: 30 V
 - Terminal Type: Cable 2 m
 - Light Source: LED



2044001 Barrel

RS PRO THROUGH BEAM PHOTOELECTRIC SENSOR, BARREL

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Style: Barrel
 - Detection Type: Through Beam
 - Detection Range: 20 m
 - Output Type: PNP NO/NC
 - Electrical Connection: Cable 2 m
 - Maximum DC Voltage: 30 V
 - Terminal Type: Cable 2 m
 - Light Source: LED



2044006 Barrel

RS PRO BACKGROUND SUPPRESSION PHOTOELECTRIC SENSOR, BARREL

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Style: Barrel
 - Detection Type: Background Suppression
 - Detection Range: 100 mm
 - Output Type: NPN NO/NC
 - Electrical Connection: Cable 2 m
 - Maximum DC Voltage: 30 V
 - Terminal Type: Cable 2 m
 - Light Source: LED



2044014 Barrel

RS PRO POLARISED RETRO REFLECTION PHOTOELECTRIC

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Style: Barrel
 - Detection Type: Polarised Retro Reflection
 - Detection Range: 3 m
 - Output Type: NPN NO/NC
 - Electrical Connection: Cable 2 m
 - Maximum DC Voltage: 30 V
 - Terminal Type: Cable 2 m
 - Light Source: LED



2044017 Barrel

SENSOR, M12, RETRO SCAN, PNP, N/O

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Style: Barrel
 - Detection Type: Retroreflective
 - Detection Range: 2 m
 - Output Type: PNP
 - Electrical Connection: M12 Connector
 - Maximum DC Voltage: 30 V
 - Light Source: LED
 - IP Rating: IP67



4405623 Barrel

RS PRO DIFFUSE PHOTOELECTRIC SENSOR, BARREL SENSOR, 100 MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Style: Barrel
 - Detection Type: Diffuse
 - Detection Range: 100 mm
 - Output Type: PNP
 - Electrical Connection: M12 Connector
 - Maximum DC Voltage: 30 V
 - Light Source: Infrared
 - IP Rating: IP67



4405639 Barrel

RS PRO BACKGROUND SUPPRESSION PHOTOELECTRIC SENSOR, BARREL

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Style: Barrel
 - Detection Type: Background Suppression
 - Detection Range: 1 → 140 mm
 - Output Type: NPN
 - Electrical Connection: 4-Pin M12 Connector
 - Maximum DC Voltage: 30 V
 - Light Source: LED
 - IP Rating: IP67



7295090 Barrel

RS PRO RETROREFLECTIVE PHOTOELECTRIC SENSOR, BARREL

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Style: Barrel
 - Detection Type: Retro-Reflective
 - Detection Range: 0.05 → 7 m
 - Output Type: NPN
 - Electrical Connection: 4-Pin M12 Connector
 - Maximum DC Voltage: 30 V
 - Light Source: LED
 - IP Rating: IP67



7295101 Barrel

RS PRO BACKGROUND SUPPRESSION PHOTOELECTRIC SENSOR, BARREL

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Style: Barrel
 - Detection Type: Background Suppression
 - Detection Range: 1 → 140 mm
 - Output Type: PNP
 - Electrical Connection: 4-Pin M12 Connector
 - Maximum DC Voltage: 30 V
 - Light Source: LED
 - IP Rating: IP67



7295104 Barrel

RS PRO BACKGROUND SUPPRESSION PHOTOELECTRIC SENSOR, BARREL

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Style: Barrel
 - Detection Type: Background Suppression
 - Detection Range: 1 → 140 mm
 - Output Type: PNP
 - Electrical Connection: Cable
 - Maximum DC Voltage: 30 V
 - Light Source: LED
 - IP Rating: IP67



7295107 Barrel

RS PRO RETROREFLECTIVE PHOTOELECTRIC SENSOR, BARREL

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Style: Barrel
 - Detection Type: Retroreflective
 - Detection Range: 0.05 → 7 m
 - Output Type: NPN
 - Electrical Connection: 4-Wire Cable 2m
 - Maximum DC Voltage: 30 V
 - Light Source: LED
 - IP Rating: IP67



7295110 Barrel

RS PRO RETROREFLECTIVE PHOTOELECTRIC SENSOR, BARREL

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Style: Barrel
 - Detection Type: Retro-Reflective
 - Detection Range: 0.05 → 7 m
 - Output Type: PNP
 - Electrical Connection: 4-Pin M12 Connector
 - Maximum DC Voltage: 30 V
 - Light Source: LED
 - IP Rating: IP67



7295113 Barrel

RS PRO RETROREFLECTIVE PHOTOELECTRIC SENSOR, BARREL

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Style: Barrel
 - Detection Type: Retro-Reflective
 - Detection Range: 0.05 → 7 m
 - Output Type: PNP
 - Electrical Connection: Cable
 - Maximum DC Voltage: 30 V
 - Light Source: LED
 - IP Rating: IP67



7295117 Barrel

RS PRO THROUGH BEAM PHOTOELECTRIC SENSOR, BARREL

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Style: Barrel
 - Detection Type: Through Beam (Emitter)
 - Detection Range: 28 m
 - Output Type: PNP
 - Electrical Connection: 4-Pin M12 Connector
 - Maximum DC Voltage: 30 V
 - Light Source: LED
 - IP Rating: IP67



7295123 Barrel

RS PRO DIFFUSE PHOTOELECTRIC SENSOR, BLOCK SENSOR, 40 MM → 1

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Style: Block
 - Detection Type: Diffuse
 - Detection Range: 40 → 1000 mm
 - Output Type: NPN
 - Electrical Connection: 4-Pin M12 Connector
 - Maximum DC Voltage: 30 V
 - Light Source: LED
 - IP Rating: IP67



7295135 Block

RS PRO DIFFUSE PHOTOELECTRIC SENSOR, BLOCK SENSOR, 40 MM → 1

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Style: Block
 - Detection Type: Diffuse
 - Detection Range: 40 → 1000 mm
 - Output Type: NPN
 - Electrical Connection: Cable
 - Maximum DC Voltage: 30 V
 - Light Source: LED
 - IP Rating: IP67



7295139 Block

RS PRO DIFFUSE PHOTOELECTRIC SENSOR, BLOCK SENSOR, 40 MM → 1

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Style: Block
 - Detection Type: Diffuse
 - Detection Range: 40 → 1000 mm
 - Output Type: PNP
 - Electrical Connection: Cable
 - Maximum DC Voltage: 30 V
 - Light Source: LED
 - IP Rating: IP67



7295141 Block

RS PRO DIFFUSE PHOTOELECTRIC SENSOR, BLOCK SENSOR, 40 MM → 1

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Style: Block
 - Detection Type: Diffuse
 - Detection Range: 40 → 1000 mm
 - Output Type: PNP
 - Electrical Connection: 4-Pin M12 Connector
 - Maximum DC Voltage: 30 V
 - Light Source: LED
 - IP Rating: IP67



7295148 Block

RS PRO RETROREFLECTIVE PHOTOELECTRIC SENSOR, BLOCK

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Style: Block
 - Detection Type: Retro-reflective
 - Detection Range: 0.15 → 10 m
 - Output Type: PNP
 - Electrical Connection: 4-Wire Cable 2m
 - Maximum DC Voltage: 30 V
 - Light Source: LED
 - IP Rating: IP67



7295151 Block

RS PRO RETROREFLECTIVE PHOTOELECTRIC SENSOR, BLOCK

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Style: Block
 - Detection Type: Retroreflective
 - Detection Range: 0.15 → 10 m
 - Output Type: PNP
 - Electrical Connection: 4-Pin M12 Connector
 - Maximum DC Voltage: 30 V
 - Light Source: LED
 - IP Rating: IP67



7295157 Block

RS PRO BACKGROUND SUPPRESSION PHOTOELECTRIC SENSOR, BLOCK

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Style: Block
 - Detection Type: Background Suppression
 - Detection Range: 5 → 250 mm
 - Output Type: PNP
 - Electrical Connection: 4-Pin M8 Connector
 - Maximum DC Voltage: 24 V
 - Light Source: LED
 - IP Rating: IP67



7295185 Block

RS PRO RETROREFLECTIVE PHOTOELECTRIC SENSOR, BLOCK

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Style: Block
 - Detection Type: Retroreflective
 - Detection Range: 7.2 m
 - Output Type: NPN
 - Electrical Connection: Cable
 - Maximum DC Voltage: 24 V
 - Light Source: LED
 - IP Rating: IP67



7295191 Block

RS PRO RETROREFLECTIVE PHOTOELECTRIC SENSOR, BLOCK

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Style: Block
 - Detection Type: Retro-Reflective
 - Detection Range: 7.2 m
 - Output Type: PNP
 - Electrical Connection: 4-Pin M8 Connector
 - Maximum DC Voltage: 24 V
 - Light Source: LED
 - IP Rating: IP67



7295195 Block

RS PRO RETROREFLECTIVE PHOTOELECTRIC SENSOR, BLOCK

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Style: Block
 - Detection Type: Retroreflective
 - Detection Range: 7.2 m
 - Output Type: NPN
 - Electrical Connection: 4-Pin M8 Connector
 - Maximum DC Voltage: 24 V
 - Light Source: LED
 - IP Rating: IP67



7295198 Block

RS PRO RETROREFLECTIVE PHOTOELECTRIC SENSOR, BLOCK

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Style: Block
 - Detection Type: Retroreflective
 - Detection Range: 7.2 m
 - Output Type: PNP
 - Electrical Connection: 3-Wire Cable 2m
 - Maximum DC Voltage: 24 V
 - Light Source: LED
 - IP Rating: IP67



7295205 Block

RS PRO THROUGH BEAM PHOTOELECTRIC SENSOR, FORK

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Style: Fork
 - Detection Type: Through Beam
 - Detection Range: 30 mm
 - Output Type: NPN NO/NC
 - Electrical Connection: 4 Wire Cable 2 m
 - Maximum DC Voltage: 30 V
 - Terminal Type: Pre-Wired
 - Light Source: Infrared



9033927 Fork

RS PRO THROUGH BEAM PHOTOELECTRIC SENSOR, FORK

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Style: Fork
 - Detection Type: Through Beam
 - Detection Range: 30 mm
 - Output Type: PNP NO
 - Electrical Connection: 4 Wire Cable 2 m
 - Maximum DC Voltage: 30 V
 - Terminal Type: Pre-Wired
 - Light Source: Infrared



9033933 Fork

RS PRO THROUGH BEAM PHOTOELECTRIC SENSOR, FORK

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Style: Fork
 - Detection Type: Through Beam
 - Detection Range: 30 mm
 - Output Type: PNP NO
 - Electrical Connection: 4 Wire Cable 2 m
 - Maximum DC Voltage: 30 V
 - Terminal Type: Pre-Wired
 - Light Source: Infrared



9033936 Fork

RS PRO THROUGH BEAM PHOTOELECTRIC SENSOR, FORK

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Style: Fork
 - Detection Type: Through Beam
 - Detection Range: 30 mm
 - Output Type: NPN NO
 - Electrical Connection: 4 Wire Cable 2 m
 - Maximum DC Voltage: 30 V
 - Terminal Type: Pre-Wired
 - Light Source: Infrared



9033939 Fork

RS PRO THROUGH BEAM PHOTOELECTRIC SENSOR, FORK

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Style: Fork
 - Detection Type: Through Beam
 - Detection Range: 7 mm
 - Output Type: PNP
 - Electrical Connection: Cable
 - Maximum DC Voltage: 30 V
 - Terminal Type: Pre-Wired
 - Light Source: Infrared



9033942 Fork

RS PRO INDUCTIVE BLOCK-STYLE PROXIMITY SENSOR, 15 MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Technology: Inductive
 - Body Style: Block
 - Output Type: PNP-NO
 - Detection Range: 15 mm
 - Terminal Type: M12 - 4 Pin
 - IP Rating: IP68
 - Supply Voltage: 10 → 30 V dc
 - Length: 46 mm



208128 Inductive

RS PRO INDUCTIVE BLOCK-STYLE PROXIMITY SENSOR, 75 MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Technology: Inductive
 - Body Style: Block
 - Output Type: PNP-NO
 - Detection Range: 75 mm
 - Terminal Type: M20 Gland
 - IP Rating: IP67
 - Supply Voltage: 10 → 30 V dc
 - Length: 80 mm



208134 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M12 X 1, 8 MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Technology: Inductive
 - Body Style: Barrel
 - Thread Size: M12 x 1
 - Output Type: PNP-NO
 - Detection Range: 8 mm
 - Terminal Type: Cable
 - Supply Voltage: 10 → 30 V dc
 - IP Rating: IP68



208156 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M8 X 1, 4 MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Technology: Inductive
 - Body Style: Barrel
 - Thread Size: M8 x 1
 - Output Type: PNP-NO
 - Detection Range: 4 mm
 - Terminal Type: Cable
 - IP Rating: IP68
 - Supply Voltage: 10 → 30 V dc



208178 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M12 X 1, 3 MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Technology: Inductive
 - Body Style: Barrel
 - Thread Size: M12 x 1
 - Output Type: PNP-NO
 - Detection Range: 3 mm
 - Terminal Type: Cable
 - IP Rating: IP68
 - Supply Voltage: 10 → 30 V dc



208184 Inductive

RS PRO INDUCTIVE BLOCK-STYLE PROXIMITY SENSOR, 35 MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Technology: Inductive
 - Body Style: Block
 - Output Type: PNP-NO
 - Detection Range: 35 mm
 - Terminal Type: M12 - 4 Pin
 - IP Rating: IP68
 - Supply Voltage: 10 → 30 V dc
 - Length: 65 mm



208190 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M18 X 1, 5 MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Technology: Inductive
 - Body Style: Barrel
 - Thread Size: M18 x 1
 - Output Type: PNP-NO
 - Detection Range: 5 mm
 - Terminal Type: M12 - 4 Pin
 - Supply Voltage: 10 → 30 V dc
 - IP Rating: IP68



208213 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M12 X 1, 8 MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Technology: Inductive
 - Body Style: Barrel
 - Thread Size: M12 x 1
 - Output Type: PNP-NO
 - Detection Range: 8 mm
 - Terminal Type: M12 - 4 Pin
 - IP Rating: IP68
 - Supply Voltage: 10 → 30 V dc



208257 Inductive

RS PRO INDUCTIVE BLOCK-STYLE PROXIMITY SENSOR, 25 MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Technology: Inductive
 - Body Style: Block
 - Output Type: PNP-NO
 - Detection Range: 25 mm
 - Terminal Type: M20 Gland
 - IP Rating: IP68
 - Supply Voltage: 10 → 30 V dc
 - Length: 114 mm



208263 Inductive

RS PRO INDUCTIVE BLOCK-STYLE PROXIMITY SENSOR, 40 MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Technology: Inductive
 - Body Style: Block
 - Output Type: PNP-NO
 - Detection Range: 40 mm
 - Terminal Type: M20 Gland
 - IP Rating: IP68
 - Supply Voltage: 10 → 30 V dc
 - Length: 114 mm



208279 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M30 X 1.5, 20

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Technology: Inductive
 - Body Style: Barrel
 - Thread Size: M30 x 1.5
 - Output Type: PNP-NO
 - Detection Range: 20 mm
 - Terminal Type: Cable
 - IP Rating: IP68
 - Supply Voltage: 10 → 30 V dc



208285 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M30 X 1.5, 10

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Technology: Inductive
 - Body Style: Barrel
 - Thread Size: M30 x 1.5
 - Output Type: PNP-NO
 - Detection Range: 10 mm
 - Terminal Type: Cable
 - IP Rating: IP68
 - Supply Voltage: 10 → 30 V dc



208314 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M8 X 1, 1.5 MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Technology: Inductive
 - Body Style: Barrel
 - Thread Size: M8 x 1
 - Output Type: PNP-NO
 - Detection Range: 1.5 mm
 - Terminal Type: Cable
 - IP Rating: IP68
 - Supply Voltage: 10 → 30 V dc



208320 Inductive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M12 X 1, 4 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Capacitive
 - Body Style: Barrel
 - Thread Size: M12 x 1
 - Output Type: PNP
 - Detection Range: 4 mm
 - Terminal Type: Cable
 - IP Rating: IP67
 - Supply Voltage: 10 → 30 V dc



1466754 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M12 X 1, 2 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Capacitive
 - Body Style: Barrel
 - Thread Size: M12 x 1
 - Output Type: PNP
 - Detection Range: 2 mm
 - Terminal Type: 4-Pin M12 Connector
 - Supply Voltage: 10 → 30 V dc
 - IP Rating: IP67



1466755 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M12 X 1, 4 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Capacitive
 - Body Style: Barrel
 - Thread Size: M12 x 1
 - Output Type: PNP
 - Detection Range: 4 mm
 - Terminal Type: 4-Pin M12 Connector
 - IP Rating: IP67
 - Supply Voltage: 10 → 30 V dc



1466756 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M18 X 1, 8 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Capacitive
 - Body Style: Barrel
 - Thread Size: M18 x 1
 - Output Type: PNP
 - Detection Range: 8 mm
 - Terminal Type: Cable
 - IP Rating: IP67
 - Supply Voltage: 10 → 30 V dc



1466757 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M18 X 1, 5 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Capacitive
 - Body Style: Barrel
 - Thread Size: M18 x 1
 - Output Type: PNP
 - Detection Range: 5 mm
 - Terminal Type: 4-Pin M12 Connector
 - IP Rating: IP67
 - Supply Voltage: 10 → 30 V dc



1466758 Capacitive

RS PRO CAPACITIVE BLOCK-STYLE PROXIMITY SENSOR, 10 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Capacitive
 - Body Style: Block
 - Output Type: PNP
 - Detection Range: 10 mm
 - Terminal Type: Cable
 - Supply Voltage: 10 → 30 V dc
 - IP Rating: IP67
 - Length: 50 mm



1466759 Capacitive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M8 X 1, 1.5 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Inductive
 - Body Style: Barrel
 - Thread Size: M8 x 1
 - Output Type: PNP
 - Detection Range: 1.5 mm
 - Terminal Type: Cable
 - IP Rating: IP67
 - Supply Voltage: 10 → 30 V dc



1646091 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M8 X 1, 1.5 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Inductive
 - Body Style: Barrel
 - Thread Size: M8 x 1
 - Output Type: PNP
 - Detection Range: 1.5 mm
 - Terminal Type: Cable
 - Supply Voltage: 10 → 30 V dc
 - IP Rating: IP67



1646092 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M8 X 1, 1.5 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Inductive
 - Body Style: Barrel
 - Thread Size: M8 x 1
 - Output Type: NPN
 - Detection Range: 1.5 mm
 - Terminal Type: Cable
 - Supply Voltage: 10 → 30 V dc
 - IP Rating: IP67



1646093 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M8 X 1, 1.5 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Inductive
 - Body Style: Barrel
 - Thread Size: M8 x 1
 - Output Type: NPN
 - Detection Range: 1.5 mm
 - Terminal Type: Cable
 - Supply Voltage: 10 → 30 V dc
 - IP Rating: IP67



1646094 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M8 X 1, 2.5 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Inductive
 - Body Style: Barrel
 - Thread Size: M8 x 1
 - Output Type: PNP
 - Detection Range: 2.5 mm
 - Terminal Type: Cable
 - Supply Voltage: 10 → 30 V dc
 - IP Rating: IP67



1646095 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M8 X 1, 2.5 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Inductive
 - Body Style: Barrel
 - Thread Size: M8 x 1
 - Output Type: PNP
 - Detection Range: 2.5 mm
 - Terminal Type: Cable
 - Supply Voltage: 10 → 30 V dc
 - IP Rating: IP67



1646096 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M8 X 1, 2.5 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Inductive
 - Body Style: Barrel
 - Thread Size: M8 x 1
 - Output Type: NPN
 - Detection Range: 2.5 mm
 - Terminal Type: Cable
 - Supply Voltage: 10 → 30 V dc
 - IP Rating: IP67



1646097 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M8 X 1, 2.5 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Inductive
 - Body Style: Barrel
 - Thread Size: M8 x 1
 - Output Type: NPN
 - Detection Range: 2.5 mm
 - Terminal Type: Cable
 - Supply Voltage: 10 → 30 V dc
 - IP Rating: IP67



1646098 Inductive

RS PRO CAPACITIVE BLOCK-STYLE PROXIMITY SENSOR, 5 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Capacitive
 - Body Style: Block
 - Output Type: PNP
 - Detection Range: 5 mm
 - Terminal Type: Cable
 - IP Rating: IP67
 - Supply Voltage: 10 → 30 V dc
 - Length: 30 mm



1845570 Capacitive

RS PRO CAPACITIVE BLOCK-STYLE PROXIMITY SENSOR, PNP NORMALLY

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Capacitive
 - Body Style: Block
 - Output Type: PNP Normally Open
 - Terminal Type: 2 m PVC Cable
 - IP Rating: IP67
 - Supply Voltage: 10 → 30 V dc
 - Length: 43 mm
 - Width: 24 mm



1845574 Capacitive

RS PRO CAPACITIVE BLOCK-STYLE PROXIMITY SENSOR, 10 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Capacitive
 - Body Style: Block
 - Output Type: NPN
 - Detection Range: 10 mm
 - Terminal Type: Cable
 - IP Rating: IP67
 - Supply Voltage: 10 → 30 V dc
 - Length: 50 mm



1845577 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M12 X 1, 2 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Capacitive
 - Body Style: Barrel
 - Thread Size: M12 x 1
 - Output Type: PNP
 - Detection Range: 2 mm
 - Terminal Type: 4-Pin M12 Connector
 - Supply Voltage: 10 → 30 V dc
 - IP Rating: IP67



1845585 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M12 X 1, 4 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Capacitive
 - Body Style: Barrel
 - Thread Size: M12 x 1
 - Output Type: NPN
 - Detection Range: 4 mm
 - Terminal Type: Cable
 - Supply Voltage: 10 → 30 V dc
 - IP Rating: IP67



1845586 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M18 X 1, 5 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Capacitive
 - Body Style: Barrel
 - Thread Size: M18 x 1
 - Detection Range: 5 mm
 - Terminal Type: Cable
 - IP Rating: IP67
 - Supply Voltage: 20 → 250 V ac
 - Length: 70 mm



1845591 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M18 X 1, 5 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Capacitive
 - Body Style: Barrel
 - Thread Size: M18 x 1
 - Output Type: NPN
 - Detection Range: 5 mm
 - Terminal Type: Cable
 - Supply Voltage: 10 → 30 V dc
 - IP Rating: IP67



1845593 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M18 X 1, 5 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Capacitive
 - Body Style: Barrel
 - Thread Size: M18 x 1
 - Output Type: PNP
 - Detection Range: 5 mm
 - Terminal Type: Cable
 - Supply Voltage: 10 → 30 V dc
 - IP Rating: IP67



1845596 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M18 X 1, 8 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Capacitive
 - Thread Size: M18 x 1
 - Body Style: Barrel
 - Detection Range: 8 mm
 - Terminal Type: 4-Pin M12 Connector
 - IP Rating: IP67
 - Supply Voltage: 20 → 250 V ac
 - Length: 91.5 mm



1845598 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M18 X 1, 8 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Capacitive
 - Body Style: Barrel
 - Thread Size: M18 x 1
 - Output Type: NPN
 - Detection Range: 8 mm
 - Terminal Type: Cable
 - Supply Voltage: 10 → 30 V dc
 - IP Rating: IP67



1845599 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M18 X 1, 8 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Capacitive
 - Body Style: Barrel
 - Thread Size: M18 x 1
 - Output Type: NPN
 - Detection Range: 8 mm
 - Terminal Type: 4-Pin M12 Connector
 - Supply Voltage: 10 → 30 V dc
 - IP Rating: IP67



1845600 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M18 X 1, 5 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Capacitive
 - Body Style: Barrel
 - Thread Size: M18 x 1
 - Output Type: NPN Normally Open & Normally Closed
 - Detection Range: 5 mm
 - Terminal Type: Cable
 - Supply Voltage: 10 → 30 V dc
 - IP Rating: IP67



1845604 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M18 X 1, 5 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Capacitive
 - Body Style: Barrel
 - Thread Size: M18 x 1
 - Output Type: PNP
 - Detection Range: 5 mm
 - Terminal Type: Cable
 - Supply Voltage: 10 → 30 V dc
 - IP Rating: IP67



1845606 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M18 X 1, 5 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Capacitive
 - Body Style: Barrel
 - Thread Size: M18 x 1
 - Output Type: PNP
 - Detection Range: 5 mm
 - Terminal Type: 4-Pin M12 Connector
 - Supply Voltage: 10 → 30 V dc
 - IP Rating: IP67



1845607 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M18 X 1, 8 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Capacitive
 - Body Style: Barrel
 - Thread Size: M18 x 1
 - Output Type: PNP
 - Detection Range: 8 mm
 - Terminal Type: 4-Pin M12 Connector
 - Supply Voltage: 10 → 30 V dc
 - IP Rating: IP67



1845612 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M18 X 1, 8 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Capacitive
 - Body Style: Barrel
 - Thread Size: M18 x 1
 - Output Type: NPN
 - Detection Range: 8 mm
 - Terminal Type: Cable
 - Supply Voltage: 10 → 30 V dc
 - IP Rating: IP67



1845609 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M18 X 1, 8 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Capacitive
 - Body Style: Barrel
 - Thread Size: M18 x 1
 - Output Type: PNP
 - Detection Range: 8 mm
 - Terminal Type: Cable
 - Supply Voltage: 10 → 30 V dc
 - IP Rating: IP67



1845611 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M30 X 1.5, 10

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Capacitive
 - Body Style: Barrel
 - Thread Size: M30 x 1.5
 - Output Type: PNP
 - Detection Range: 10 mm
 - Terminal Type: 4-Pin M12 Connector
 - Supply Voltage: 10 → 30 V dc
 - IP Rating: IP67



1845619 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M30 X 1.5, 15

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Capacitive
 - Thread Size: M30 x 1.5
 - Body Style: Barrel
 - Output Type: NPN
 - Detection Range: 15 mm
 - Terminal Type: Cable
 - IP Rating: IP67
 - Supply Voltage: 10 → 30 V dc



1845622 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M30 X 1.5, 15

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Capacitive
 - Body Style: Barrel
 - Thread Size: M30 x 1.5
 - Detection Range: 15 mm
 - Terminal Type: 4-Pin M12 Connector
 - IP Rating: IP67
 - Supply Voltage: 20 → 250 V ac
 - Length: 91 mm



1845621 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M30 X 1.5, 15

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Capacitive
 - Body Style: Barrel
 - Thread Size: M30 x 1.5
 - Output Type: NPN
 - Detection Range: 15 mm
 - Terminal Type: 4-Pin M12 Connector
 - Supply Voltage: 10 → 30 V dc
 - IP Rating: IP67



1845623 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M30 X 1.5, 15

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Capacitive
 - Body Style: Barrel
 - Thread Size: M30 x 1.5
 - Output Type: PNP
 - Detection Range: 15 mm
 - Terminal Type: 4-Pin M12 Connector
 - Supply Voltage: 10 → 30 V dc
 - IP Rating: IP67



1845626 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M30 X 1.5, 10

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Capacitive
 - Body Style: Barrel
 - Thread Size: M30 x 1.5
 - Output Type: NPN Normally Open & Normally Closed
 - Detection Range: 10 mm
 - Terminal Type: Cable
 - IP Rating: IP67
 - Supply Voltage: 10 → 30 V dc



1845629 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M30 X 1.5, 10

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Capacitive
 - Body Style: Barrel
 - Thread Size: M30 x 1.5
 - Output Type: PNP
 - Detection Range: 10 mm
 - Terminal Type: Cable
 - Supply Voltage: 10 → 30 V dc
 - IP Rating: IP67



1845632 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M30 X 1.5, 10

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Capacitive
 - Body Style: Barrel
 - Thread Size: M30 x 1.5
 - Detection Range: 10 mm
 - Terminal Type: Cable
 - IP Rating: IP67
 - Supply Voltage: 20 → 250 V ac/dc
 - Length: 62 mm



1845634 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M30 X 1.5, 15

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Capacitive
 - Body Style: Barrel
 - Thread Size: M30 x 1.5
 - Output Type: NPN
 - Detection Range: 15 mm
 - Terminal Type: Cable
 - Supply Voltage: 10 → 30 V dc
 - IP Rating: IP67



1845638 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M30 X 1.5, 15

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Capacitive
 - Body Style: Barrel
 - Thread Size: M30 x 1.5
 - Output Type: NPN
 - Detection Range: 15 mm
 - Terminal Type: 4-Pin M12 Connector
 - Supply Voltage: 10 → 30 V dc
 - IP Rating: IP67



1845639 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M30 X 1.5, 15

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Capacitive
 - Body Style: Barrel
 - Thread Size: M30 x 1.5
 - Output Type: PNP
 - Detection Range: 15 mm
 - Terminal Type: Cable
 - Supply Voltage: 10 → 30 V dc
 - IP Rating: IP67



1845640 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M30 X 1.5, 15

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Capacitive
 - Thread Size: M30 x 1.5
 - Body Style: Barrel
 - Output Type: PNP
 - Detection Range: 15 mm
 - Terminal Type: 4-Pin M12 Connector
 - IP Rating: IP67
 - Supply Voltage: 10 → 30 V dc



1845641 Capacitive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M4 X 0.5, 0.6

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Inductive
 - Body Style: Barrel
 - Thread Size: M4 x 0.5
 - Output Type: PNP
 - Detection Range: 0.6 mm
 - Terminal Type: 2 m, 3-wire, Cable
 - IP Rating: IP67
 - Supply Voltage: 10 → 30 V dc



2066124 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M5 X 0.5, 1.5

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Inductive
 - Body Style: Barrel
 - Thread Size: M5 x 0.5
 - Output Type: PNP
 - Detection Range: 1.5 mm
 - Terminal Type: 2 m, 3-wire, Cable
 - IP Rating: IP67
 - Supply Voltage: 10 → 30 V dc



2066129 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M8 X 1, 2 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Inductive
 - Body Style: Barrel
 - Thread Size: M8 x 1
 - Output Type: PNP
 - Detection Range: 2 mm
 - Terminal Type: 3-Pin M8 Connector
 - IP Rating: IP68
 - Supply Voltage: 10 → 30 V dc



2066133 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M8 X 1, 2 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Inductive
 - Body Style: Barrel
 - Thread Size: M8 x 1
 - Output Type: PNP
 - Detection Range: 2 mm
 - Terminal Type: 2 m, 3-wire, Cable
 - IP Rating: IP68
 - Supply Voltage: 10 → 30 V dc



2066135 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M8 X 1, 4 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Inductive
 - Body Style: Barrel
 - Thread Size: M8 x 1
 - Output Type: PNP
 - Detection Range: 4 mm
 - Terminal Type: 2 m, 3-wire, Cable
 - IP Rating: IP68
 - Supply Voltage: 10 → 30 V dc



2066136 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M12 X 1, 4 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Inductive
 - Body Style: Barrel
 - Thread Size: M12 x 1
 - Output Type: PNP
 - Detection Range: 4 mm
 - Terminal Type: 4-Pin M12 Connector
 - IP Rating: IP68
 - Supply Voltage: 10 → 30 V dc



2066156 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M12 X 1, 4 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Inductive
 - Body Style: Barrel
 - Thread Size: M12 x 1
 - Output Type: PNP
 - Detection Range: 4 mm
 - Terminal Type: 2 m, 3-wire, Cable
 - IP Rating: IP68
 - Supply Voltage: 10 → 30 V dc



2066157 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M12 X 1, 8 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Inductive
 - Body Style: Barrel
 - Thread Size: M12 x 1
 - Output Type: NPN
 - Detection Range: 8 mm
 - Terminal Type: 2 m, 3-wire, Cable
 - IP Rating: IP68
 - Supply Voltage: 10 → 30 V dc



2066158 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M12 X 1, 8 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Inductive
 - Body Style: Barrel
 - Thread Size: M12 x 1
 - Output Type: PNP
 - Detection Range: 8 mm
 - Terminal Type: 4-Pin M12 Connector
 - IP Rating: IP68
 - Supply Voltage: 10 → 30 V dc



2066159 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M12 X 1, 8 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Inductive
 - Body Style: Barrel
 - Thread Size: M12 x 1
 - Output Type: PNP
 - Detection Range: 8 mm
 - Terminal Type: 2 m, 3-wire, Cable
 - IP Rating: IP68
 - Supply Voltage: 10 → 30 V dc



2066160 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M18 X 1, 8 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Inductive
 - Body Style: Barrel
 - Thread Size: M18 x 1
 - Output Type: PNP
 - Detection Range: 8 mm
 - Terminal Type: 4-Pin M12 Connector
 - IP Rating: IP68
 - Supply Voltage: 10 → 30 V dc



2066161 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M18 X 1, 8 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Inductive
 - Body Style: Barrel
 - Thread Size: M18 x 1
 - Output Type: PNP
 - Detection Range: 8 mm
 - Terminal Type: 4-Pin M12 Connector
 - IP Rating: IP68
 - Supply Voltage: 10 → 30 V dc



2066162 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M18 X 1, 8 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Inductive
 - Body Style: Barrel
 - Thread Size: M18 x 1
 - Output Type: PNP
 - Detection Range: 8 mm
 - Terminal Type: 2 m, 3-wire, Cable
 - IP Rating: IP68
 - Supply Voltage: 10 → 30 V dc



2066163 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M18 X 1, 20 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Inductive
 - Body Style: Barrel
 - Thread Size: M18 x 1
 - Output Type: PNP
 - Detection Range: 20 mm
 - Terminal Type: 4-Pin M12 Connector
 - IP Rating: IP68
 - Supply Voltage: 10 → 30 V dc



2066164 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M30 X 1.5, 10

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Inductive
 - Body Style: Barrel
 - Thread Size: M30 x 1.5
 - Output Type: PNP
 - Detection Range: 10 mm
 - Terminal Type: 2 m, 3-wire, Cable
 - IP Rating: IP68
 - Supply Voltage: 10 → 30 V dc



2066165 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M30 X 1.5, 38

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Inductive
 - Body Style: Barrel
 - Thread Size: M30 x 1.5
 - Output Type: PNP Normally Open
 - Detection Range: 38 mm
 - Terminal Type: 2 m, 3-wire, Cable
 - IP Rating: IP68
 - Supply Voltage: 10 → 30 V dc



2066167 Inductive

RS PRO INDUCTIVE RECTANGULAR-STYLE PROXIMITY SENSOR, 3 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Inductive
 - Body Style: Rectangular
 - Output Type: PNP
 - Detection Range: 3 mm
 - Terminal Type: 2 m, 3-wire, Cable
 - Supply Voltage: 10 → 30 V dc
 - IP Rating: IP68
 - Length: 16 mm



2066172 Inductive

RS PRO INDUCTIVE RECTANGULAR-STYLE PROXIMITY SENSOR, 20 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Inductive
 - Body Style: Rectangular
 - Output Type: PNP
 - Detection Range: 20 mm
 - Terminal Type: 4-Pin M12 Connector
 - Supply Voltage: 10 → 30 V dc
 - IP Rating: IP67
 - Length: 66 mm



2066176 Inductive

RS PRO INDUCTIVE RECTANGULAR-STYLE PROXIMITY SENSOR, 40 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Inductive
 - Body Style: Rectangular
 - Output Type: PNP
 - Detection Range: 40 mm
 - Terminal Type: 4-Pin M12 Connector
 - Supply Voltage: 10 → 30 V dc
 - IP Rating: IP67
 - Length: 66 mm



2066180 Inductive

RS PRO INDUCTIVE RECTANGULAR-STYLE PROXIMITY SENSOR, 40 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Inductive
 - Body Style: Rectangular
 - Output Type: PNP
 - Detection Range: 40 mm
 - Terminal Type: Cable
 - Supply Voltage: 10 → 30 V dc
 - IP Rating: IP67
 - Length: 118 mm



2066181 Inductive

RS PRO INDUCTIVE RECTANGULAR-STYLE PROXIMITY SENSOR, 40 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Inductive
 - Body Style: Rectangular
 - Output Type: PNP
 - Detection Range: 40 mm
 - Terminal Type: Cable
 - Supply Voltage: 10 → 30 V dc
 - IP Rating: IP67
 - Length: 118 mm



2066183 Inductive

RS PRO ULTRASONIC BARREL-STYLE PROXIMITY SENSOR, M30, 2000 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Ultrasonic
 - Body Style: Barrel
 - Thread Size: M30
 - Output Type: Analogue 4-20mA
 - Detection Range: 2000 mm
 - Terminal Type: 4-Pin M12 Connector
 - IP Rating: IP67
 - Length: 110 mm



2181168 Ultrasonic

RS PRO ULTRASONIC BARREL-STYLE PROXIMITY SENSOR, M30, 2000 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Ultrasonic
 - Body Style: Barrel
 - Thread Size: M30
 - Output Type: PNP
 - Detection Range: 2000 mm
 - Terminal Type: 4-Pin M12 Connector
 - IP Rating: IP67
 - Length: 110 mm



2181169 Ultrasonic

RS PRO ULTRASONIC BARREL-STYLE PROXIMITY SENSOR, M18, 300 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Ultrasonic
 - Body Style: Barrel
 - Thread Size: M18
 - Output Type: Analogue 4-20mA
 - Detection Range: 300 mm
 - Terminal Type: 4-Pin M12 Connector
 - IP Rating: IP67
 - Length: 86 mm



2181171 Ultrasonic

RS PRO ULTRASONIC BARREL-STYLE PROXIMITY SENSOR, M18, 300 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Ultrasonic
 - Body Style: Barrel
 - Thread Size: M18
 - Output Type: PNP
 - Detection Range: 300 mm
 - Terminal Type: 4-Pin M12 Connector
 - IP Rating: IP67
 - Length: 86 mm



2181172 Ultrasonic

RS PRO ULTRASONIC BARREL-STYLE PROXIMITY SENSOR, M30, 4000 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Ultrasonic
 - Body Style: Barrel
 - Thread Size: M30
 - Output Type: Analogue 4-20mA
 - Detection Range: 4000 mm
 - Terminal Type: 4-Pin M12 Connector
 - IP Rating: IP67
 - Length: 110 mm



2181175 Ultrasonic

RS PRO ULTRASONIC BARREL-STYLE PROXIMITY SENSOR, 0 → 300 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Ultrasonic
 - Body Style: Barrel
 - Detection Range: 0 → 300 mm
 - Terminal Type: PCB
 - Supply Voltage: 20 V
 - Length: 7.1 mm
 - Maximum Operating Temperature: +85 °C
 - Minimum Operating Temperature: -40 °C



2370799 Ultrasonic

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M18 X 1, 5 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Inductive
 - Body Style: Barrel
 - Thread Size: M18 x 1
 - Output Type: PNP-NO
 - Detection Range: 5 mm
 - Terminal Type: Cable
 - IP Rating: IP67
 - Supply Voltage: 10 → 30 V dc



7018213 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M30 X 1.5, 10

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Inductive
 - Body Style: Barrel
 - Thread Size: M30 x 1.5
 - Output Type: PNP-NO
 - Detection Range: 10 mm
 - Terminal Type: Cable
 - IP Rating: IP67
 - Supply Voltage: 10 → 30 V dc



7018216 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M30 X 1.5, 10

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Inductive
 - Body Style: Barrel
 - Thread Size: M30 x 1.5
 - Output Type: NPN-NO
 - Detection Range: 10 mm
 - Terminal Type: Cable
 - IP Rating: IP67
 - Supply Voltage: 10 → 30 V dc



7018219 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M18 X 1, 5 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Inductive
 - Body Style: Barrel
 - Thread Size: M18 x 1
 - Output Type: NPN-NO
 - Detection Range: 5 mm
 - Terminal Type: Cable
 - IP Rating: IP67
 - Supply Voltage: 10 → 30 V dc



7018222 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M12 X 1, 2 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Inductive
 - Body Style: Barrel
 - Thread Size: M12 x 1
 - Output Type: PNP-NO
 - Detection Range: 2 mm
 - Terminal Type: Cable
 - IP Rating: IP67
 - Supply Voltage: 10 → 30 V dc



7018225 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M12 X 1, 2 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Inductive
 - Body Style: Barrel
 - Thread Size: M12 x 1
 - Output Type: NPN-NO
 - Detection Range: 2 mm
 - Terminal Type: Cable
 - Supply Voltage: 10 → 30 V dc
 - IP Rating: IP67



7018229 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M12 X 1, 2 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Inductive
 - Body Style: Barrel
 - Thread Size: M12 x 1
 - Output Type: PNP-NO
 - Detection Range: 2 mm
 - Terminal Type: M12 - 4 Pin
 - IP Rating: IP67
 - Supply Voltage: 10 → 30 V dc



7018231 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M18 X 1, 5 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Inductive
 - Body Style: Barrel
 - Thread Size: M18 x 1
 - Output Type: NPN-NO
 - Detection Range: 5 mm
 - Terminal Type: M12 - 4 Pin
 - IP Rating: IP67
 - Supply Voltage: 10 → 30 V dc



7018235 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M12 X 1, 2 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Inductive
 - Body Style: Barrel
 - Thread Size: M12 x 1
 - Output Type: NPN-NO
 - Detection Range: 2 mm
 - Terminal Type: M12 - 4 Pin
 - IP Rating: IP67
 - Supply Voltage: 10 → 30 V dc



7018238 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M30 X 1.5, 10

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Inductive
 - Body Style: Barrel
 - Thread Size: M30 x 1.5
 - Output Type: PNP-NO
 - Detection Range: 10 mm
 - Terminal Type: M12 - 4 Pin
 - IP Rating: IP67
 - Supply Voltage: 10 → 30 V dc



7018241 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M18 X 1, 5 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Inductive
 - Body Style: Barrel
 - Thread Size: M18 x 1
 - Output Type: PNP-NO
 - Detection Range: 5 mm
 - Terminal Type: M12 - 4 Pin
 - IP Rating: IP67
 - Supply Voltage: 10 → 30 V dc



7018244 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M30 X 1.5, 10

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Inductive
 - Body Style: Barrel
 - Thread Size: M30 x 1.5
 - Output Type: NPN-NO
 - Detection Range: 10 mm
 - Terminal Type: M12 - 4 Pin
 - IP Rating: IP67
 - Supply Voltage: 10 → 30 V dc



7018247 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M12 X 1, 4 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Inductive
 - Body Style: Barrel
 - Thread Size: M12 x 1
 - Output Type: NPN-NO
 - Detection Range: 4 mm
 - Terminal Type: Cable
 - IP Rating: IP67
 - Supply Voltage: 10 → 30 V dc



7018250 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M12 X 1, 4 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Inductive
 - Body Style: Barrel
 - Thread Size: M12 x 1
 - Output Type: PNP-NO
 - Detection Range: 4 mm
 - Terminal Type: Cable
 - IP Rating: IP67
 - Supply Voltage: 10 → 30 V dc



7018253 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M18 X 1, 8 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Inductive
 - Body Style: Barrel
 - Thread Size: M18 x 1
 - Output Type: NPN-NO
 - Detection Range: 8 mm
 - Terminal Type: Cable
 - IP Rating: IP67
 - Supply Voltage: 10 → 30 V dc



7018257 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M30 X 1.5, 15

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Inductive
 - Body Style: Barrel
 - Thread Size: M30 x 1.5
 - Output Type: PNP-NO
 - Detection Range: 15 mm
 - Terminal Type: Cable
 - IP Rating: IP67
 - Supply Voltage: 10 → 30 V dc



7018263 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M18 X 1, 8 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Inductive
 - Body Style: Barrel
 - Thread Size: M18 x 1
 - Output Type: PNP-NO
 - Detection Range: 8 mm
 - Terminal Type: Cable
 - IP Rating: IP67
 - Supply Voltage: 10 → 30 V dc



7018266 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M30 X 1.5, 15

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Inductive
 - Body Style: Barrel
 - Thread Size: M30 x 1.5
 - Output Type: NPN-NO
 - Detection Range: 15 mm
 - Terminal Type: Cable
 - Supply Voltage: 10 → 30 V dc
 - IP Rating: IP67



7018269 Inductive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M18 X 1, 8 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Capacitive
 - Body Style: Barrel
 - Thread Size: M18 x 1
 - Output Type: NPN
 - Detection Range: 8 mm
 - Terminal Type: Cable
 - IP Rating: IP67
 - Supply Voltage: 10 → 30 V dc



8967223 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M18 X 1, 5 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Capacitive
 - Body Style: Barrel
 - Thread Size: M18 x 1
 - Output Type: NPN Normally Open
 - Detection Range: 5 mm
 - Terminal Type: Cable
 - IP Rating: IP67
 - Supply Voltage: 10 → 30 V dc



8967229 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M18 X 1, 5 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Capacitive
 - Body Style: Barrel
 - Thread Size: M18 x 1
 - Output Type: PNP
 - Detection Range: 5 mm
 - Terminal Type: Cable
 - IP Rating: IP67
 - Supply Voltage: 10 → 30 V dc



8967232 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M18 X 1, 8 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Capacitive
 - Body Style: Barrel
 - Thread Size: M18 x 1
 - Output Type: PNP
 - Detection Range: 8 mm
 - Terminal Type: Cable
 - Supply Voltage: 10 → 30 V dc
 - IP Rating: IP67



8967235 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M18 X 1, 5 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Capacitive
 - Body Style: Barrel
 - Thread Size: M18 x 1
 - Detection Range: 5 mm
 - Terminal Type: Cable
 - Supply Voltage: 20 → 250 V ac
 - IP Rating: IP67
 - Length: 83.5 mm



8967241 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M18 X 1, 8 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Capacitive
 - Body Style: Barrel
 - Thread Size: M18 x 1
 - Detection Range: 8 mm
 - Terminal Type: Cable
 - Supply Voltage: 20 → 250 V ac
 - IP Rating: IP67
 - Length: 78 mm



8967245 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M18 X 1, 8 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Capacitive
 - Body Style: Barrel
 - Thread Size: M18 x 1
 - Output Type: PNP
 - Detection Range: 8 mm
 - Terminal Type: 4-Pin M12 Connector
 - IP Rating: IP67
 - Supply Voltage: 10 → 30 V dc



8967248 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M30 X 1.5, 10

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Capacitive
 - Body Style: Barrel
 - Thread Size: M30 x 1.5
 - Output Type: PNP
 - Detection Range: 10 mm
 - Terminal Type: Cable
 - IP Rating: IP67
 - Supply Voltage: 10 → 30 V dc



8967251 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M30 X 1.5, 10

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Capacitive
 - Body Style: Barrel
 - Thread Size: M30 x 1.5
 - Output Type: NPN Normally Open
 - Detection Range: 10 mm
 - Terminal Type: Cable
 - IP Rating: IP67
 - Supply Voltage: 10 → 30 V dc



8967254 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M30 X 1.5, 15

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Capacitive
 - Body Style: Barrel
 - Thread Size: M30 x 1.5
 - Output Type: NPN
 - Detection Range: 15 mm
 - Terminal Type: Cable
 - IP Rating: IP67
 - Supply Voltage: 10 → 30 V dc



8967257 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M30 X 1.5, 15

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Capacitive
 - Body Style: Barrel
 - Thread Size: M30 x 1.5
 - Output Type: PNP
 - Detection Range: 15 mm
 - Terminal Type: Cable
 - IP Rating: IP67
 - Supply Voltage: 10 → 30 V dc



8967260 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M30 X 1.5, 10

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Capacitive
 - Body Style: Barrel
 - Thread Size: M30 x 1.5
 - Output Type: PNP
 - Detection Range: 10 mm
 - Terminal Type: 4-Pin M12 Connector
 - IP Rating: IP67
 - Supply Voltage: 10 → 30 V dc



8967263 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M30 X 1.5, 15

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Capacitive
 - Body Style: Barrel
 - Thread Size: M30 x 1.5
 - Output Type: PNP
 - Detection Range: 15 mm
 - Terminal Type: 4-Pin M12 Connector
 - IP Rating: IP67
 - Supply Voltage: 10 → 30 V dc



8967267 Capacitive

RS PRO CAPACITIVE BLOCK-STYLE PROXIMITY SENSOR, 10 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Capacitive
 - Body Style: Block
 - Output Type: PNP
 - Detection Range: 10 mm
 - Terminal Type: Cable
 - IP Rating: IP67
 - Supply Voltage: 10 → 30 V dc
 - Length: 50 mm



8967273 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M30 X 1.5, 15

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Capacitive
 - Body Style: Barrel
 - Thread Size: M30 x 1.5
 - Detection Range: 15 mm
 - Terminal Type: Cable
 - Supply Voltage: 20 → 250 V ac/dc
 - IP Rating: IP67
 - Length: 91 mm



8967276 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M30 X 1.5, 15

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Capacitive
 - Body Style: Barrel
 - Thread Size: M30 x 1.5
 - Detection Range: 15 mm
 - Terminal Type: Cable
 - Supply Voltage: 20 → 250 V ac/dc
 - IP Rating: IP67
 - Length: 91 mm



8967279 Capacitive

RS PRO CAPACITIVE BLOCK-STYLE PROXIMITY SENSOR, 8 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Technology: Capacitive
 - Body Style: Block
 - Output Type: PNP
 - Detection Range: 8 mm
 - Terminal Type: Cable
 - IP Rating: IP67
 - Supply Voltage: 10 → 30 V dc
 - Length: 50 mm



8967282 Capacitive

RS PRO RIGHT ANGLE FEMALE M12 TO UNTERMINATED SENSOR ACTUATOR

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Connector A: M12
 - Sheath Colour: Black
 - Connector B: Unterminated
 - Connector A Gender: Female
 - Connector A Orientation: Right Angle
 - Number of Cores: 4
 - Length: 15 m
 - Sheath Material: PUR



2055980 M12

RS PRO STRAIGHT FEMALE M8 TO UNTERMINATED SENSOR ACTUATOR

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Connector A: M8
 - Sheath Colour: Black
 - Connector B: Unterminated
 - Connector A Gender: Female
 - Connector A Orientation: Straight
 - Number of Cores: 3
 - Length: 10 m
 - Sheath Material: PVC



2055987 M8

RS PRO STRAIGHT FEMALE M12 TO UNTERMINATED SENSOR ACTUATOR

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Connector A: M12
 - Sheath Colour: Black
 - Connector B: Unterminated
 - Connector A Gender: Female
 - Connector A Orientation: Straight
 - Number of Cores: 4
 - Length: 10 m
 - Sheath Material: PUR



2055992 M12

RS PRO RIGHT ANGLE FEMALE M12 TO UNTERMINATED SENSOR ACTUATOR

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Connector A: M12
 - Sheath Colour: Black
 - Connector B: Unterminated
 - Connector A Gender: Female
 - Connector A Orientation: Right Angle
 - Number of Cores: 4
 - Length: 20 m
 - Sheath Material: PUR



2055993 M12

RS PRO RIGHT ANGLE FEMALE M8 TO UNTERMINATED SENSOR ACTUATOR

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Connector A: M8
 - Connector B: Unterminated
 - Connector A Gender: Female
 - Connector A Orientation: Right Angle
 - Number of Cores: 4
 - Length: 2 m
 - Connector A Number of Contacts: 4
 - Series: CBF08



2121693 M8

RS PRO RIGHT ANGLE FEMALE M8 TO UNTERMINATED SENSOR ACTUATOR

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Connector A: M8
 - Connector B: Unterminated
 - Connector A Gender: Female
 - Connector A Orientation: Right Angle
 - Number of Cores: 4
 - Length: 5 m
 - Connector A Number of Contacts: 4
 - Series: CBF08



2121694 M8

RS PRO RIGHT ANGLE FEMALE M8 TO UNTERMINATED SENSOR ACTUATOR

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Connector A: M8
 - Connector B: Unterminated
 - Connector A Gender: Female
 - Connector A Orientation: Right Angle
 - Number of Cores: 4
 - Length: 5 m
 - Connector A Number of Contacts: 4
 - Series: CBF08



2121695 M8

RS PRO STRAIGHT FEMALE M12 TO STRAIGHT MALE M12 SENSOR

ขนาดบรรจุภัณฑ์: 1 x EA

- Connector A: M12
- Connector B: M12
- Connector A Gender: Female
- Connector B Gender: Male
- Connector A Orientation: Straight
- Connector B Orientation: Straight
- Number of Cores: 4
- Length: 5 m



2121723 M12

RS PRO CONNECTOR

ขนาดบรรจุภัณฑ์: 1 x EA

- Connector A: M12
- Connector B: Unterminated
- Connector A Gender: Female
- Connector A Orientation: Straight
- Number of Cores: 4
- Mounting Type: Panel Mount
- Length: 2 m
- Sheath Material: PUR



2121724 M12

RS PRO MAGNET FOR USE WITH PROXIMITY SWITCH

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Magnet
- For Use With: Proximity Switch
- Application: Proximity Switch



285245 Magnet

RS PRO MAGNET FOR USE WITH MAGNETIC PROXIMITY SWITCH

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Magnet
- For Use With: Magnetic Proximity Switch
- Application: Magnetic Proximity Switch



339768 Magnet

RS PRO MOUNTING BRACKET FOR USE WITH M18 SENSOR

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Mounting Bracket
- For Use With: M18 Sensor
- Application: Mounting
- Series: M18



2133659 Mounting Bracket

RS PRO MOUNTING BRACKET FOR USE WITH M12 SENSOR

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Mounting Bracket
- For Use With: M12 Sensor
- Application: Mounting
- Series: M12



2133660 Mounting Bracket

RS PRO MOUNTING BRACKET FOR USE WITH M30 SENSOR

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Mounting Bracket
- For Use With: M30 Sensor
- Application: Mounting
- Series: M30



2133662 Mounting Bracket

RS PRO MAGNET FOR USE WITH PROXIMITY SWITCH

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Magnet
- For Use With: Proximity Switch
- Application: Proximity Switch



3614927 Magnet

RS PRO MAGNET FOR USE WITH PROXIMITY SWITCH

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Magnet
- For Use With: Proximity Switch
- Application: Proximity Switch



3617011 Magnet

RS PRO MAGNET FOR USE WITH TRANSDUCER

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Magnet
- For Use With: Transducer
- Application: Transducer



5361710 Magnet

RS PRO MAGNET FOR USE WITH TRANSDUCER

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Magnet
- For Use With: Transducer
- Application: Transducer



5361748 Magnet

RS PRO MOUNTING BRACKET FOR USE WITH M4 → M18 PROXIMITY

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Mounting Bracket
- For Use With: M4 → M18 Proximity Sensors



7141697 Mounting Bracket

RS PRO MAGNET FOR USE WITH LINEAR ACTUATOR

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Magnet
- For Use With: Linear Actuator
- Application: Linear Actuator



8110745 Magnet

HAND HELD PROXIMITY SWITCH TESTER

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Sensor Tester
- Application: Proximity Switch
- Standards Met: RoHS Compliant




8399875 Sensor Tester

RS PRO SENSOR CONNECTOR TO FREE END WIRE TO BOARD CABLE

ขนาดบรรจุภัณฑ์: 1 x EA

- Connector A: Sensor Connector
- Connector A Gender: Male
- Connector B: Free End
- Connector A Number of Contacts: 4
- Sheath Colour: Black



2055977 Sensor

RS PRO SENSOR CONNECTOR TO FREE END WIRE TO BOARD CABLE

ขนาดบรรจุภัณฑ์: 1 x EA

- Connector A: Sensor Connector
- Connector A Gender: Male
- Connector B: Free End
- Connector A Number of Contacts: 3
- Sheath Colour: Multicoloured



2055983 Sensor

RS PRO TOUCH-SCREEN HMI DISPLAY - 7 IN, TFT LCD DISPLAY, 800 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Display Type: TFT LCD
 - Display Size: 7 in
 - Display Resolution: 800 x 480 pixels
 - Display Colour: Colour
 - Number of Ports: 3
 - Port Type: COM1,COM2, USB Host, USB Client
 - Interface: USB
 - Processor Type: ARM Cortex



2156604 TFT LCD

RS PRO TOUCH-SCREEN HMI DISPLAY - 10.2 IN, TFT LCD DISPLAY, 1024 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Display Type: TFT LCD
 - Display Size: 10.2 in
 - Display Resolution: 1024 x 600 pixels
 - Display Colour: Colour
 - Number of Ports: 4
 - Port Type: COM1,COM2, USB Host, USB Client
 - Interface: USB, Ethernet
 - Processor Type: ARM Cortex



2156606 TFT LCD

RS PRO TOUCH-SCREEN HMI DISPLAY - 7 IN, TFT LCD DISPLAY, 800 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Display Type: TFT LCD
 - Display Size: 7 in
 - Display Resolution: 800 x 480 pixels
 - Display Colour: Colour
 - Number of Ports: 4
 - Port Type: COM1,COM2, USB Host, USB Client
 - Interface: USB, Ethernet
 - Processor Type: ARM Cortex



2156605 TFT LCD

RS PRO DIN RAIL MOUNT ETHERNET SWITCH, 8 RJ45 PORTS,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Transmission Speed: 10/100 Mbit/s
 - RJ45 Ports: 8
 - Mounting: DIN Rail
 - Maximum Operating Temperature: +80 °C
 - Maximum Supply Voltage: 30 V dc
 - Minimum Operating Temperature: -40 °C
 - For Use With: Ethernet Network



1448674 10/100 Mbit/s

RS PRO DIN RAIL MOUNT ETHERNET SWITCH, 5 RJ45 PORTS,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Transmission Speed: 10/100 Mbit/s
 - RJ45 Ports: 5
 - Mounting: DIN Rail
 - Maximum Operating Temperature: +80 °C
 - Maximum Supply Voltage: 30 V dc
 - Minimum Operating Temperature: -40 °C
 - For Use With: Ethernet Network



1448673 10/100 Mbit/s

RS PRO DIN RAIL MOUNT ETHERNET SWITCH, 5 RJ45 PORTS,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Transmission Speed: 10/100 Mbit/s
 - RJ45 Ports: 5
 - Mounting: DIN Rail
 - Height: 99 mm
 - Maximum Operating Temperature: +80 °C
 - Maximum Supply Voltage: 30 V dc
 - Minimum Operating Temperature: -40 °C
 - Minimum Supply Voltage: 5 V dc



1448675 10/100 Mbit/s

RS PRO DIN RAIL MOUNT ETHERNET SWITCH, 8 RJ45 PORTS,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Transmission Speed: 10/100 Mbit/s
 - RJ45 Ports: 8
 - Mounting: DIN Rail
 - Depth: 115 mm
 - Height: 99 mm
 - Maximum Operating Temperature: +80 °C
 - Maximum Supply Voltage: 30 V dc
 - Minimum Operating Temperature: -40 °C



1448676 10/100 Mbit/s

RS PRO WALL MOUNT ETHERNET SWITCH, 8 RJ45 PORTS,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Transmission Speed: 10/100 Mbit/s
 - RJ45 Ports: 8
 - Nominal Supply Voltage: 30 V dc
 - Mounting: Wall
 - Series: RS-008
 - Height: 102 mm
 - Maximum Operating Temperature: +60 °C
 - Minimum Operating Temperature: -10 °C



2263243 10/100 Mbit/s

RS PRO LOGIC MODULE - 8 INPUTS, 4 OUTPUTS, DIGITAL, RELAY, MODBUS

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Number of Inputs: 8
 - Output Type: Digital, Relay
 - Input Type: Digital
 - Supply Voltage: 110 → 240 V ac
 - Number of Outputs: 4
 - Network Type: ModBus
 - Display Included: Yes
 - Communication Port Type: Serial



9176361 8

RS PRO LOGIC MODULE - 8 INPUTS, 4 OUTPUTS, DIGITAL, RELAY, MODBUS

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Number of Inputs: 8
 - Output Type: Digital, Relay
 - Input Type: Analogue, Digital
 - Supply Voltage: 12 → 24 V dc
 - Number of Outputs: 4
 - Network Type: ModBus
 - Display Included: Yes
 - Communication Port Type: Serial



9176370 8

RS PRO LOGIC MODULE - 8 INPUTS, 4 OUTPUTS, DIGITAL, RELAY, MODBUS

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Number of Inputs: 8
 - Output Type: Digital, Relay
 - Input Type: Digital
 - Supply Voltage: 110 → 240 V ac
 - Number of Outputs: 4
 - Network Type: ModBus
 - Communication Port Type: Serial
 - Program Capacity: 250 lines



9176373 8

LOGIC MODULE W/O DISPLAY 8I/4O

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Number of Inputs: 8
 - Output Type: Digital, Relay
 - Input Type: Analogue, Digital
 - Supply Voltage: 12 → 24 V dc
 - Number of Outputs: 4
 - Network Type: ModBus
 - Communication Port Type: Serial
 - Program Capacity: 250 lines



9176377 8

RS PRO COMMUNICATION MODULE - 1 INPUTS, 1 OUTPUTS, RS485

- ขนาดบรรจุภัณฑ์: **1 x EA**
- For Use With: RS PRO Logic Modules
 - Number of Inputs: 1
 - Output Type: RS485 Protocol (D-), RS485 Protocol (D+), RS485 Protocol (Two Wires)
 - Input Type: TTL Level
 - Supply Voltage: 110 → 240 V ac
 - Number of Outputs: 1
 - Network Type: ModBus
 - Communication Port Type: RS485



9176383 RS PRO Logic

RS PRO I/O EXTENSION MODULE - 8 INPUTS, 4 OUTPUTS, DIGITAL, RELAY,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- For Use With: RS PRO Logic Modules
 - Number of Inputs: 8
 - Output Type: Digital, Relay
 - Input Type: Digital
 - Supply Voltage: 110 → 240 V ac
 - Number of Outputs: 4
 - Network Type: ModBus
 - Communication Port Type: Serial



9176386 RS PRO Logic

RS PRO COMMUNICATION MODULE - 1 INPUTS, 1 OUTPUTS, RS485

- ขนาดบรรจุภัณฑ์: **1 x EA**
- For Use With: RS PRO Logic Modules
 - Number of Inputs: 1
 - Output Type: RS485 Protocol (D-), RS485 Protocol (D+), RS485 Protocol (Two Wires)
 - Input Type: TTL Level
 - Supply Voltage: 12 → 24 V dc
 - Number of Outputs: 1
 - Network Type: ModBus
 - Communication Port Type: RS485



9176392 RS PRO Logic

RS PRO MEMORY MODULE FOR USE WITH RS PRO LOGIC MODULES

- ขนาดบรรจุภัณฑ์: **1 x EA**
- For Use With: RS PRO Logic Modules
 - Maximum Operating Temperature: +55 °C



9176399 RS PRO Logic

LOGIC MODULE USB PROGRAMMING CABLE


- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: USB Cable
 - For Use With: Logic Module
 - Application: Automation, Commercial, Industrial
 - Termination: Plug-In



9176395 USB Cable

RS PRO 2 PORT PCI RS232 SERIAL CARD

- ขนาดบรรจุภัณฑ์: 1 x EA
- Bus Type: PCI
 - Communication Interface: Serial
 - Number of Ports: 2
 - Connection Port: RS232



6161892 PCI

RS PRO CAR CHARGER, 11 → 16V DC INPUT, 19V DC OUTPUT PLUG IN, 4.7A

- ขนาดบรรจุภัณฑ์: 1 x EA
- Input Voltage: 11 → 16 V dc
 - Output Voltage: 19 V dc
 - Output Power Continuous: 89 W
 - Output Connection Type: Plug In
 - Output Current: 4.7 A
 - Length: 105.9 mm
 - Width: 51.5 mm
 - Depth: 18.4 mm



417916 11 → 16 V dc

RS PRO DC-DC CONVERTER, 12V DC/, 21.6 → 26.4 V DC INPUT, 1W, PCB

- ขนาดบรรจุภัณฑ์: 1 x EA
- Output Voltage: 12 V dc
 - Input Voltage Range: 21.6 → 26.4 V dc
 - Power Rating: 1 W
 - Input Voltage Nominal: 24 V dc
 - Mounting Type: PCB Mount
 - Isolated: Yes
 - Isolation Voltage: 1.5 kV
 - Railway Approved: No



2240352 12 V dc

RS PRO WALL MOUNT LINEAR POWER SUPPLY, 230V AC INPUT, 24V AC

- ขนาดบรรจุภัณฑ์: 1 x EA
- Input Voltage: 230 V ac
 - Output Voltage: 24 V ac
 - Output Current: 7 A
 - Number of Outputs: 1
 - Embedded: Yes
 - Power Rating: 168 VA
 - Length: 122.2 mm
 - Width: 89.9 mm



1244715 230 V ac

RS PRO CONNECTOR KIT, FOR USE WITH RPS-75

- ขนาดบรรจุภัณฑ์: 1 x KT
- Accessory Type: Connector Kit
 - For Use With: RPS-75



381835 Connector Kit

RS PRO CONNECTOR KIT, FOR USE WITH PS-35, RPS-60

- ขนาดบรรจุภัณฑ์: 1 x KT
- Accessory Type: Connector Kit
 - For Use With: PS-35, RPS-60



381841 Connector Kit

RS PRO CONNECTOR KIT, FOR USE WITH RPD-60, RPT-60

- ขนาดบรรจุภัณฑ์: 1 x KT
- Accessory Type: Connector Kit
 - For Use With: RPD-60, RPT-60



381845 Connector Kit

RS PRO CONNECTOR KIT, FOR USE WITH PPT-125

- ขนาดบรรจุภัณฑ์: 1 x KT
- Accessory Type: Connector Kit
 - For Use With: PPT-125



381851 Connector Kit

POWER SUPPLY, SWITCH MODE, RS RANGE, AC/DC, CONNECTOR

- ขนาดบรรจุภัณฑ์: 1 x KT
- Accessory Type: Connector Kit
 - For Use With: PPS-125, PPS-200, RPD-75, RPT-75



381857 Connector Kit

RS PRO CONNECTOR KIT, FOR USE WITH ASP-150

- ขนาดบรรจุภัณฑ์: 1 x KT
- Accessory Type: Connector Kit
 - For Use With: ASP-150



424392 Connector Kit

RS PRO CONNECTOR KIT, FOR USE WITH USP-350

- ขนาดบรรจุภัณฑ์: 1 x KT
- Accessory Type: Connector Kit
 - For Use With: USP-350



453827 Connector Kit

RS PRO SWITCHING POWER SUPPLY, 12V DC, 5A, 60W, 1 OUTPUT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Output Voltage: 12 V dc
 - Output Current: 5 A
 - Power Rating: 60 W
 - Number of Outputs: 1
 - Input Voltage: 100 → 230 V ac
 - Mounting Type: Panel Mount
 - Package Type: Open Frame
 - Length: 101.6 mm



1244709 12 V dc

RS PRO SWITCHING POWER SUPPLY, 24V DC, 2.5A, 60W, 1 OUTPUT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Output Voltage: 24 V dc
 - Output Current: 2.5 A
 - Power Rating: 60 W
 - Number of Outputs: 1
 - Input Voltage: 100 → 230 V ac
 - Mounting Type: Panel Mount
 - Package Type: Open Frame
 - Length: 101.6 mm



1244711 24 V dc

RS PRO SWITCHING POWER SUPPLY, 48V DC, 1.25A, 60W, 1 OUTPUT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Output Voltage: 48 V dc
 - Output Current: 1.25 A
 - Power Rating: 60 W
 - Number of Outputs: 1
 - Input Voltage: 100 → 230 V ac
 - Mounting Type: Panel Mount
 - Package Type: Open Frame
 - Length: 101.6 mm



1244714 48 V dc

RS PRO SWITCHING POWER SUPPLY, 15V DC, 1.7A, 25.5W, 1 OUTPUT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Output Voltage: 15 V dc
 - Output Current: 1.7 A
 - Power Rating: 25.5 W
 - Number of Outputs: 1
 - Input Voltage: 88 → 264 V ac
 - Mounting Type: Chassis Mount
 - Package Type: Enclosed
 - Length: 85 mm



1618216 15 V dc

RS PRO SWITCHING POWER SUPPLY, 12V DC, 16.7A, 200W, 1 OUTPUT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Output Voltage: 12 V dc
 - Output Current: 16.7 A
 - Power Rating: 200 W
 - Number of Outputs: 1
 - Input Voltage: 120 → 370 V dc, 85 → 264 V ac
 - Mounting Type: PCB Mount
 - Package Type: Enclosed
 - Length: 199 mm



1618219 12 V dc

RS PRO SWITCHING POWER SUPPLY, 24V DC, 8.4A, 200W, 1 OUTPUT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Output Voltage: 24 V dc
 - Output Current: 8.4 A
 - Power Rating: 200 W
 - Number of Outputs: 1
 - Input Voltage: 120 → 370 V dc, 85 → 264 V ac
 - Mounting Type: PCB Mount
 - Package Type: Enclosed
 - Length: 199 mm



1618221 24 V dc

RS PRO SWITCHING POWER SUPPLY, 36V DC, 5.6A, 200W, 1 OUTPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 36 V dc
 - Output Current: 5.6 A
 - Power Rating: 200 W
 - Number of Outputs: 1
 - Input Voltage: 120 → 370 V dc, 85 → 264 V ac
 - Mounting Type: PCB Mount
 - Package Type: Enclosed
 - Length: 199 mm



1618222 36 V dc

RS PRO SWITCHING POWER SUPPLY, 48V DC, 4.2A, 200W, 1 OUTPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 48 V dc
 - Output Current: 4.2 A
 - Power Rating: 200 W
 - Number of Outputs: 1
 - Input Voltage: 120 → 370 V dc, 85 → 264 V ac
 - Mounting Type: PCB Mount
 - Package Type: Enclosed
 - Length: 199 mm



1618223 48 V dc

RS PRO SWITCHING POWER SUPPLY, 24V DC, 10A, 240W, 1 OUTPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 24 V dc
 - Output Current: 10 A
 - Power Rating: 240 W
 - Number of Outputs: 1
 - Input Voltage: 85 → 264 V ac
 - Mounting Type: Chassis Mount
 - Package Type: Enclosed
 - Length: 199 mm



1618226 24 V dc

RS PRO SWITCHING POWER SUPPLY, 48V DC, 5A, 240W, 1 OUTPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 48 V dc
 - Output Current: 5 A
 - Power Rating: 240 W
 - Number of Outputs: 1
 - Input Voltage: 85 → 264 V ac
 - Mounting Type: Chassis Mount
 - Package Type: Enclosed
 - Length: 199 mm



1618227 48 V dc

RS PRO SWITCHING POWER SUPPLY, 12V DC, 25A, 300W, 1 OUTPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 12 V dc
 - Output Current: 25 A
 - Power Rating: 300 W
 - Number of Outputs: 1
 - Input Voltage: 120 → 370 V dc, 90 → 264 V ac
 - Mounting Type: PCB Mount
 - Package Type: Enclosed
 - Length: 199 mm



1618228 12 V dc

RS PRO SWITCHING POWER SUPPLY, 24V DC, 13A, 300W, 1 OUTPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 24 V dc
 - Output Current: 13 A
 - Power Rating: 300 W
 - Number of Outputs: 1
 - Input Voltage: 120 → 370 V dc, 90 → 264 V ac
 - Mounting Type: PCB Mount
 - Package Type: Enclosed
 - Length: 199 mm



1618229 24 V dc

RS PRO SWITCHING POWER SUPPLY, 48V DC, 6.7A, 300W, 1 OUTPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 48 V dc
 - Output Current: 6.7 A
 - Power Rating: 300 W
 - Number of Outputs: 1
 - Input Voltage: 120 → 370 V dc, 90 → 264 V ac
 - Mounting Type: PCB Mount
 - Package Type: Enclosed
 - Length: 199 mm



1618230 48 V dc

RS PRO SWITCHING POWER SUPPLY, 12V DC, 34A, 480W, 1 OUTPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 12 V dc
 - Output Current: 34 A
 - Power Rating: 480 W
 - Number of Outputs: 1
 - Input Voltage: 90 → 264 V ac
 - Mounting Type: Chassis Mount
 - Package Type: Enclosed
 - Length: 218 mm



1618231 12 V dc

RS PRO SWITCHING POWER SUPPLY, 24V DC, 22A, 480W, 1 OUTPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 24 V dc
 - Output Current: 22 A
 - Power Rating: 480 W
 - Number of Outputs: 1
 - Input Voltage: 90 → 264 V ac
 - Mounting Type: Chassis Mount
 - Package Type: Enclosed
 - Length: 218 mm



1618232 24 V dc

RS PRO SWITCHING POWER SUPPLY, 27V DC, 18A, 480W, 1 OUTPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 27 V dc
 - Output Current: 18 A
 - Power Rating: 480 W
 - Number of Outputs: 1
 - Input Voltage: 90 → 264 V ac
 - Mounting Type: Chassis Mount
 - Package Type: Enclosed
 - Length: 218 mm



1618233 27 V dc

RS PRO SWITCHING POWER SUPPLY, 36V DC, 14A, 480W, 1 OUTPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 36 V dc
 - Output Current: 14 A
 - Power Rating: 480 W
 - Number of Outputs: 1
 - Input Voltage: 90 → 264 V ac
 - Mounting Type: Chassis Mount
 - Package Type: Enclosed
 - Length: 218 mm



1618234 36 V dc

RS PRO SWITCHING POWER SUPPLY, 48V DC, 11A, 480W, 1 OUTPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 48 V dc
 - Output Current: 11 A
 - Power Rating: 480 W
 - Number of Outputs: 1
 - Input Voltage: 90 → 264 V ac
 - Mounting Type: Chassis Mount
 - Package Type: Enclosed
 - Length: 218 mm



1618235 48 V dc

RS PRO SWITCHING POWER SUPPLY, 24V DC, 21A, 504W, 1 OUTPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 24 V dc
 - Output Current: 21 A
 - Power Rating: 504 W
 - Number of Outputs: 1
 - Input Voltage: 88 → 264 V ac
 - Mounting Type: Chassis Mount
 - Package Type: Enclosed
 - Length: 183 mm



1618237 24 V dc

RS PRO SWITCHING POWER SUPPLY, 24V DC, 26.5A, 600W, 1 OUTPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 24 V dc
 - Output Current: 26.5 A
 - Power Rating: 600 W
 - Number of Outputs: 1
 - Input Voltage: 90 → 264 V ac
 - Mounting Type: Chassis Mount
 - Package Type: Enclosed
 - Length: 218 mm



1618240 24 V dc

RS PRO SWITCHING POWER SUPPLY, 48V DC, 13.6A, 588W, 1 OUTPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 48 V dc
 - Output Current: 13.6 A
 - Power Rating: 588 W
 - Number of Outputs: 1
 - Input Voltage: 90 → 264 V ac
 - Mounting Type: Chassis Mount
 - Package Type: Enclosed
 - Length: 218 mm



1618242 48 V dc

RS PRO SWITCHING POWER SUPPLY, 24V DC, 27A, 799W, 1 OUTPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 24 V dc
 - Output Current: 27 A
 - Power Rating: 799 W
 - Number of Outputs: 1
 - Input Voltage: 90 → 264 V ac
 - Mounting Type: Chassis Mount
 - Package Type: Enclosed
 - Length: 226 mm



1618243 24 V dc

RS PRO SWITCHING POWER SUPPLY, 27V DC, 23A, 799W, 1 OUTPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 27 V dc
 - Output Current: 23 A
 - Power Rating: 799 W
 - Number of Outputs: 1
 - Input Voltage: 90 → 264 V ac
 - Mounting Type: Chassis Mount
 - Package Type: Enclosed
 - Length: 226 mm



1618244 27 V dc

RS PRO SWITCHING POWER SUPPLY, 48V DC, 14A, 800W, 1 OUTPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 48 V dc
 - Output Current: 14 A
 - Power Rating: 800 W
 - Number of Outputs: 1
 - Input Voltage: 90 → 264 V ac
 - Mounting Type: Chassis Mount
 - Package Type: Enclosed
 - Length: 226 mm



1618245 48 V dc

RS PRO SWITCHING POWER SUPPLY, 24V DC, 1KW

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 24 V dc
 - Power Rating: 1 kW
 - Mounting Type: Chassis Mount
 - Package Type: Enclosed



1618246 24 V dc

RS PRO SWITCHING POWER SUPPLY, 48V DC, 1KW

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 48 V dc
 - Power Rating: 1 kW
 - Mounting Type: Chassis Mount
 - Package Type: Enclosed



1618247 48 V dc

RS PRO SWITCHING POWER SUPPLY, 5V DC, 8A, 40W, 1 OUTPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 5 V dc
 - Output Current: 8 A
 - Power Rating: 40 W
 - Number of Outputs: 1
 - Input Voltage: 127 → 370 V dc, 90 → 264 V ac
 - Mounting Type: Chassis Mount
 - Package Type: Open Frame
 - Length: 101.6 mm



1618251 5 V dc

RS PRO SWITCHING POWER SUPPLY, 12V DC, 4.5A, 54W, 1 OUTPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 12 V dc
 - Output Current: 4.5 A
 - Power Rating: 54 W
 - Number of Outputs: 1
 - Input Voltage: 127 → 370 V dc, 90 → 264 V ac
 - Mounting Type: Chassis Mount
 - Package Type: Open Frame
 - Length: 101.6 mm



1618252 12 V dc

RS PRO SWITCHING POWER SUPPLY, 15V DC, 3.6A, 54W, 1 OUTPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 15 V dc
 - Output Current: 3.6 A
 - Power Rating: 54 W
 - Number of Outputs: 1
 - Input Voltage: 127 → 370 V dc, 90 → 264 V ac
 - Mounting Type: Chassis Mount
 - Package Type: Open Frame
 - Length: 101.6 mm



1618253 15 V dc

RS PRO SWITCHING POWER SUPPLY, 24V DC, 2.5A, 60W, 1 OUTPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 24 V dc
 - Output Current: 2.5 A
 - Power Rating: 60 W
 - Number of Outputs: 1
 - Input Voltage: 127 → 370 V dc, 90 → 264 V ac
 - Mounting Type: Chassis Mount
 - Package Type: Open Frame
 - Length: 101.6 mm



1618254 24 V dc

RS PRO SWITCHING POWER SUPPLY, 5V DC, 20A, 100W, 1 OUTPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 5 V dc
 - Output Current: 20 A
 - Power Rating: 100 W
 - Number of Outputs: 1
 - Input Voltage: 90 → 264 V ac
 - Mounting Type: Chassis Mount
 - Package Type: Open Frame
 - Length: 127 mm



1618256 5 V dc

RS PRO SWITCHING POWER SUPPLY, 12V DC, 10.5A, 126W, 1 OUTPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 12 V dc
 - Output Current: 10.5 A
 - Power Rating: 126 W
 - Number of Outputs: 1
 - Input Voltage: 90 → 264 V ac
 - Mounting Type: Chassis Mount
 - Package Type: Open Frame
 - Length: 127 mm



1618257 12 V dc

RS PRO SWITCHING POWER SUPPLY, 24V DC, 5.2A, 124.8W, 1 OUTPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 24 V dc
 - Output Current: 5.2 A
 - Power Rating: 124.8 W
 - Number of Outputs: 1
 - Input Voltage: 90 → 264 V ac
 - Mounting Type: Chassis Mount
 - Package Type: Open Frame
 - Length: 127 mm



1618260 24 V dc

RS PRO SWITCHING POWER SUPPLY, 48V DC, 2.6A, 124.8W, 1 OUTPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 48 V dc
 - Output Current: 2.6 A
 - Power Rating: 124.8 W
 - Number of Outputs: 1
 - Input Voltage: 90 → 264 V ac
 - Mounting Type: Chassis Mount
 - Package Type: Open Frame
 - Length: 127 mm



1618262 48 V dc

RS PRO SWITCHING POWER SUPPLY, 12V DC, 16.6A, 199W, 1 OUTPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 12 V dc
 - Output Current: 16.6 A
 - Power Rating: 199 W
 - Number of Outputs: 1
 - Input Voltage: 127 → 370 V dc, 90 → 264 V ac
 - Mounting Type: Chassis Mount
 - Package Type: Open Frame
 - Length: 128 mm



1618263 12 V dc

RS PRO SWITCHING POWER SUPPLY, 24V DC, 8.1A, 201.6W, 1 OUTPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 24 V dc
 - Output Current: 8.1 A
 - Power Rating: 201.6 W
 - Number of Outputs: 1
 - Input Voltage: 127 → 370 V dc, 90 → 264 V ac
 - Mounting Type: Chassis Mount
 - Package Type: Open Frame
 - Length: 128 mm



1618265 24 V dc

RS PRO SWITCHING POWER SUPPLY, 12V DC, 16.7A, 200W, 1 OUTPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 12 V dc
 - Output Current: 16.7 A
 - Power Rating: 200 W
 - Number of Outputs: 1
 - Input Voltage: 90 → 264 V ac
 - Mounting Type: Chassis Mount
 - Package Type: Enclosed
 - Length: 200 mm



1618269 12 V dc

RS PRO SWITCHING POWER SUPPLY, 24V DC, 8.4A, 200W, 1 OUTPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 24 V dc
 - Output Current: 8.4 A
 - Power Rating: 200 W
 - Number of Outputs: 1
 - Input Voltage: 90 → 264 V ac
 - Mounting Type: Chassis Mount
 - Package Type: Enclosed
 - Length: 200 mm



1618270 24 V dc

RS PRO SWITCHING POWER SUPPLY, 5V DC, 7A, 35W, 1 OUTPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 5 V dc
 - Output Current: 7 A
 - Power Rating: 35 W
 - Number of Outputs: 1
 - Mounting Type: Chassis Mount
 - Package Type: Enclosed
 - Length: 99 mm
 - Width: 82 mm



1618272 5 V dc

RS PRO SWITCHING POWER SUPPLY, 15V DC, 2.4A, 36W, 1 OUTPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 15 V dc
 - Output Current: 2.4 A
 - Power Rating: 36 W
 - Number of Outputs: 1
 - Mounting Type: Chassis Mount
 - Package Type: Enclosed
 - Length: 99 mm
 - Width: 82 mm



1618274 15 V dc

RS PRO SWITCHING POWER SUPPLY, 36V DC, 1A, 36W, 1 OUTPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 36 V dc
 - Output Current: 1 A
 - Power Rating: 36 W
 - Number of Outputs: 1
 - Mounting Type: Chassis Mount
 - Package Type: Enclosed
 - Length: 99 mm
 - Width: 82 mm



1618276 36 V dc

RS PRO SWITCHING POWER SUPPLY, 48V DC, 800mA, 38W, 1 OUTPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 48 V dc
 - Output Current: 800 mA
 - Power Rating: 38 W
 - Number of Outputs: 1
 - Mounting Type: Chassis Mount
 - Package Type: Enclosed
 - Length: 99 mm
 - Width: 82 mm



1618277 48 V dc

RS PRO SWITCHING POWER SUPPLY, 15V DC, 51W, 1 OUTPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 15 V dc
 - Power Rating: 51 W
 - Number of Outputs: 1
 - Input Voltage: 100 → 240 V ac
 - Mounting Type: Chassis Mount
 - Package Type: Enclosed
 - Length: 99 mm
 - Width: 82 mm



1618280 15 V dc

RS PRO SWITCHING POWER SUPPLY, 36V DC, 1.45A, 55W, 1 OUTPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 36 V dc
 - Output Current: 1.45 A
 - Power Rating: 55 W
 - Number of Outputs: 1
 - Input Voltage: 100 → 240 V ac
 - Mounting Type: Chassis Mount
 - Package Type: Enclosed
 - Length: 99 mm



1618282 36 V dc

RS PRO SWITCHING POWER SUPPLY, 48V DC, 1.1A, 52.8W, 1 OUTPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 48 V dc
 - Output Current: 1.1 A
 - Power Rating: 52.8 W
 - Number of Outputs: 1
 - Input Voltage: 100 → 240 V ac
 - Mounting Type: Chassis Mount
 - Package Type: Enclosed
 - Length: 99 mm



1618283 48 V dc

RS PRO SWITCHING POWER SUPPLY, 5V DC, 14A, 60W, 1 OUTPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 5 V dc
 - Output Current: 14 A
 - Power Rating: 60 W
 - Number of Outputs: 1
 - Input Voltage: 100 → 240 V ac
 - Mounting Type: Chassis Mount
 - Package Type: Enclosed
 - Length: 99 mm



1618284 5 V dc

RS PRO SWITCHING POWER SUPPLY, 12V DC, 6A, 72W, 1 OUTPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 12 V dc
 - Output Current: 6 A
 - Power Rating: 72 W
 - Number of Outputs: 1
 - Input Voltage: 100 → 240 V ac
 - Mounting Type: Chassis Mount
 - Package Type: Enclosed
 - Length: 97 mm



1618285 12 V dc

RS PRO SWITCHING POWER SUPPLY, 24V DC, 3.2A, 76.8W, 1 OUTPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 24 V dc
 - Output Current: 3.2 A
 - Power Rating: 76.8 W
 - Number of Outputs: 1
 - Input Voltage: 100 → 240 V ac
 - Mounting Type: Chassis Mount
 - Package Type: Enclosed
 - Length: 97 mm



1618288 24 V dc

RS PRO SWITCHING POWER SUPPLY, 36V DC, 2.1A, 75.6W, 1 OUTPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 36 V dc
 - Output Current: 2.1 A
 - Power Rating: 75.6 W
 - Number of Outputs: 1
 - Input Voltage: 100 → 240 V ac
 - Mounting Type: Chassis Mount
 - Package Type: Enclosed
 - Length: 97 mm



1618289 36 V dc

RS PRO SWITCHING POWER SUPPLY, 48V DC, 1.6A, 76.8W, 1 OUTPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 48 V dc
 - Output Current: 1.6 A
 - Power Rating: 76.8 W
 - Number of Outputs: 1
 - Input Voltage: 100 → 240 V ac
 - Mounting Type: Chassis Mount
 - Package Type: Enclosed
 - Length: 97 mm



1618290 48 V dc

RS PRO SWITCHING POWER SUPPLY, 15V DC, 105W, 1 OUTPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 15 V dc
 - Power Rating: 105 W
 - Number of Outputs: 1
 - Input Voltage: 85 → 264 V ac
 - Mounting Type: Chassis Mount
 - Package Type: Enclosed
 - Length: 129 mm
 - Width: 97 mm



1618293 15 V dc

RS PRO SWITCHING POWER SUPPLY, 36V DC, 2.8A, 101W, 1 OUTPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 36 V dc
 - Output Current: 2.8 A
 - Power Rating: 101 W
 - Number of Outputs: 1
 - Input Voltage: 85 → 264 V ac
 - Mounting Type: Chassis Mount
 - Package Type: Enclosed
 - Length: 129 mm



1618295 36 V dc

RS PRO SWITCHING POWER SUPPLY, 48V DC, 2.3A, 110W, 1 OUTPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 48 V dc
 - Output Current: 2.3 A
 - Power Rating: 110 W
 - Number of Outputs: 1
 - Input Voltage: 85 → 264 V ac
 - Mounting Type: Chassis Mount
 - Package Type: Enclosed
 - Length: 129 mm



1618296 48 V dc

RS PRO SWITCHING POWER SUPPLY, 12V DC, 12.5A, 150W, 1 OUTPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 12 V dc
 - Output Current: 12.5 A
 - Power Rating: 150 W
 - Number of Outputs: 1
 - Input Voltage: 170 → 264 V ac, 85 → 132 V ac
 - Mounting Type: Chassis Mount
 - Package Type: Enclosed
 - Length: 159 mm



1618297 12 V dc

RS PRO SWITCHING POWER SUPPLY, 15V DC, 150W, 1 OUTPUT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Output Voltage: 15 V dc
 - Power Rating: 150 W
 - Number of Outputs: 1
 - Input Voltage: 170 → 264 V ac, 85 → 132 V ac
 - Mounting Type: Chassis Mount
 - Package Type: Enclosed
 - Length: 99 mm
 - Width: 82 mm



1618298 15 V dc

RS PRO SWITCHING POWER SUPPLY, 24V DC, 6.5A, 156W, 1 OUTPUT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Output Voltage: 24 V dc
 - Output Current: 6.5 A
 - Power Rating: 156 W
 - Number of Outputs: 1
 - Input Voltage: 170 → 264 V ac, 85 → 132 V ac
 - Mounting Type: Chassis Mount
 - Package Type: Enclosed
 - Length: 159 mm



1618299 24 V dc

RS PRO SWITCHING POWER SUPPLY, 36V DC, 4.3A, 155W, 1 OUTPUT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Output Voltage: 36 V dc
 - Output Current: 4.3 A
 - Power Rating: 155 W
 - Number of Outputs: 1
 - Input Voltage: 170 → 264 V ac, 85 → 132 V ac
 - Mounting Type: Chassis Mount
 - Package Type: Enclosed
 - Length: 99 mm



1618300 36 V dc

RS PRO SWITCHING POWER SUPPLY, 48V DC, 3.3A, 158W, 1 OUTPUT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Output Voltage: 48 V dc
 - Output Current: 3.3 A
 - Power Rating: 158 W
 - Number of Outputs: 1
 - Input Voltage: 170 → 264 V ac, 85 → 132 V ac
 - Mounting Type: Chassis Mount
 - Package Type: Enclosed
 - Length: 99 mm



1618301 48 V dc

RS PRO SWITCHING POWER SUPPLY, 5V DC, 600MA, 3W, 1 OUTPUT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Output Voltage: 5 V dc
 - Output Current: 600 mA
 - Power Rating: 3 W
 - Number of Outputs: 1
 - Input Voltage: 110 → 370 V dc, 85 → 264 V ac
 - Mounting Type: PCB Mount
 - Package Type: Encapsulated
 - Length: 37 mm



6675760 5 V dc

RS PRO SWITCHING POWER SUPPLY, 9V DC, 330MA, 3W, 1 OUTPUT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Output Voltage: 9 V dc
 - Output Current: 330 mA
 - Power Rating: 3 W
 - Number of Outputs: 1
 - Input Voltage: 110 → 370 V dc, 85 → 264 V ac
 - Mounting Type: PCB Mount
 - Package Type: Encapsulated
 - Length: 37 mm



6675764 9 V dc

RS PRO SWITCHING POWER SUPPLY, 12V DC, 250MA, 3W, 1 OUTPUT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Output Voltage: 12 V dc
 - Output Current: 250 mA
 - Power Rating: 3 W
 - Number of Outputs: 1
 - Input Voltage: 110 → 370 V dc, 85 → 264 V ac
 - Mounting Type: PCB Mount
 - Package Type: Encapsulated
 - Length: 37 mm



6675773 12 V dc

RS PRO SWITCHING POWER SUPPLY, 5V DC, 1A, 5W, 1 OUTPUT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Output Voltage: 5 V dc
 - Output Current: 1 A
 - Power Rating: 5 W
 - Number of Outputs: 1
 - Input Voltage: 110 → 370 V dc, 85 → 264 V ac
 - Mounting Type: PCB Mount
 - Package Type: Encapsulated
 - Length: 50.8 mm



6675789 5 V dc

RS PRO SWITCHING POWER SUPPLY, 24V DC, 2.5A, 60W, 1 OUTPUT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Output Voltage: 24 V dc
 - Output Current: 2.5 A
 - Power Rating: 60 W
 - Number of Outputs: 1
 - Input Voltage: 88 → 264 V ac
 - Mounting Type: Chassis Mount
 - Package Type: Enclosed
 - Length: 98 mm



7112636 24 V dc

RS PRO SWITCHING POWER SUPPLY, 24V DC, 1.25A, 30W, 1 OUTPUT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Output Voltage: 24 V dc
 - Output Current: 1.25 A
 - Power Rating: 30 W
 - Number of Outputs: 1
 - Input Voltage: 85 → 265 V ac
 - Mounting Type: PCB Mount
 - Package Type: Enclosed
 - Length: 89 mm



7511421 24 V dc

RS PRO SWITCHING POWER SUPPLY, 24V DC, 625MA, 15W, 1 OUTPUT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Output Voltage: 24 V dc
 - Output Current: 625 mA
 - Power Rating: 15 W
 - Number of Outputs: 1
 - Input Voltage: 120 → 375 V dc, 85 → 265 V ac
 - Mounting Type: PCB Mount
 - Package Type: Enclosed
 - Length: 76.2 mm



7719436 24 V dc

RS PRO SWITCHING REGULATOR, SURFACE MOUNT, 3.3V DC OUTPUT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Output Voltage: 3.3 V dc
 - Input Voltage: 4.75 → 36 V dc
 - Output Current: 500 mA
 - Mounting Type: Surface Mount
 - Number of Outputs: 1
 - Package: SMD
 - Efficiency: 86/80 %
 - Ripple And Noise: 50 mV Pk-Pk



1933954 3.3 V dc

RS PRO SWITCHING REGULATOR, SURFACE MOUNT, 5V DC OUTPUT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Output Voltage: 5 V dc
 - Input Voltage: 6.5 → 36 V dc
 - Output Current: 500 mA
 - Mounting Type: Surface Mount
 - Number of Outputs: 1
 - Package: SMD
 - Efficiency: 90/84 %
 - Ripple And Noise: 50 mV Pk-Pk



1933956 5 V dc

RS PRO SWITCHING REGULATOR, PCB MOUNT, 3.3V DC OUTPUT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Output Voltage: 3.3 V dc
 - Input Voltage: 4.75 → 36 V dc
 - Output Current: 500 mA
 - Mounting Type: PCB Mount
 - Number of Outputs: 1
 - Efficiency: 86/80 %
 - Ripple And Noise: 75 mV Pk-Pk
 - Minimum Temperature: -40 °C



1933966 3.3 V dc

RS PRO SWITCHING REGULATOR, PCB MOUNT, 5V DC OUTPUT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Output Voltage: 5 V dc
 - Input Voltage: 6.5 → 36 V dc
 - Output Current: 500 mA
 - Mounting Type: PCB Mount
 - Number of Outputs: 1
 - Efficiency: 90/84 %
 - Ripple And Noise: 75 mV Pk-Pk
 - Minimum Temperature: -40 °C



1933969 5 V dc

RS PRO SWITCHING REGULATOR, PCB MOUNT, 12V DC OUTPUT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Output Voltage: 12 V dc
 - Input Voltage: 15 → 36 V dc
 - Output Current: 500 mA
 - Mounting Type: PCB Mount
 - Number of Outputs: 1
 - Efficiency: 94/91 %
 - Ripple And Noise: 75 mV Pk-Pk
 - Minimum Temperature: -40 °C



1933971 12 V dc

RS PRO SWITCHING REGULATOR, PCB MOUNT, 3.3V DC OUTPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 3.3 V dc
 - Input Voltage: 4.75 → 36 V dc
 - Output Current: 500 mA
 - Mounting Type: PCB Mount
 - Number of Outputs: 1
 - Efficiency: 86/80 %
 - Ripple And Noise: 75 mV Pk-Pk
 - Minimum Temperature: -40 °C



1933974 3.3 V dc

RS PRO SWITCHING REGULATOR, PCB MOUNT, 5V DC OUTPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 5 V dc
 - Input Voltage: 6.5 → 36 V dc
 - Output Current: 500 mA
 - Mounting Type: PCB Mount
 - Number of Outputs: 1
 - Efficiency: 90/84 %
 - Ripple And Noise: 75 mV Pk-Pk
 - Minimum Temperature: -40 °C



1933976 5 V dc

RS PRO SWITCHING REGULATOR, PCB MOUNT, 9V DC OUTPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 9 V dc
 - Input Voltage: 12 → 36 V dc
 - Output Current: 500 mA
 - Mounting Type: PCB Mount
 - Number of Outputs: 1
 - Efficiency: 93/90 %
 - Ripple And Noise: 75 mV Pk-Pk
 - Minimum Temperature: -40 °C



1933978 9 V dc

RS PRO SWITCHING REGULATOR, PCB MOUNT, 12V DC OUTPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 12 V dc
 - Input Voltage: 15 → 36 V dc
 - Output Current: 500 mA
 - Mounting Type: PCB Mount
 - Number of Outputs: 1
 - Efficiency: 94/91 %
 - Ripple And Noise: 75 mV Pk-Pk
 - Minimum Temperature: -40 °C



1933980 12 V dc

RS PRO SWITCHING REGULATOR, 5V DC OUTPUT VOLTAGE, 6.5 → 36V DC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 5 V dc
 - Input Voltage: 6.5 → 36 V dc
 - Output Current: 500 mA
 - Number of Outputs: 1
 - Efficiency: 90/84 %
 - Ripple And Noise: 75 mV Pk-Pk
 - Minimum Temperature: -40 °C
 - Maximum Temperature: +85 °C



1933984 5 V dc

RS PRO SWITCHING REGULATOR, PCB MOUNT, 5V DC OUTPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 5 V dc
 - Input Voltage: 8 → 36 V dc
 - Output Current: 1 A
 - Mounting Type: PCB Mount
 - Number of Outputs: 1
 - Efficiency: 93/86 %
 - Ripple And Noise: 75 mV Pk-Pk
 - Minimum Temperature: -40 °C



1933998 5 V dc

RS PRO SWITCHING REGULATOR, PCB MOUNT, 12V DC OUTPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 12 V dc
 - Input Voltage: 16 → 36 V dc
 - Output Current: 1 A
 - Mounting Type: PCB Mount
 - Number of Outputs: 1
 - Efficiency: 95/92 %
 - Ripple And Noise: 75 mV Pk-Pk
 - Minimum Temperature: -40 °C



1934000 12 V dc

RS PRO SWITCHING REGULATOR, PCB MOUNT, 3.3V DC OUTPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 3.3 V dc
 - Input Voltage: 6 → 36 V dc
 - Output Current: 1 A
 - Mounting Type: PCB Mount
 - Number of Outputs: 1
 - Efficiency: 90/80 %
 - Ripple And Noise: 75 mV Pk-Pk
 - Minimum Temperature: -40 °C



1934002 3.3 V dc

RS PRO SWITCHING REGULATOR, PCB MOUNT, 5V DC OUTPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 5 V dc
 - Input Voltage: 8 → 36 V dc
 - Output Current: 1 A
 - Mounting Type: PCB Mount
 - Number of Outputs: 1
 - Efficiency: 93/85 %
 - Ripple And Noise: 75 mV Pk-Pk
 - Minimum Temperature: -40 °C



1934004 5 V dc

RS PRO SWITCHING REGULATOR, PCB MOUNT, 6.5V DC OUTPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 6.5 V dc
 - Input Voltage: 10 → 36 V dc
 - Output Current: 1 A
 - Mounting Type: PCB Mount
 - Number of Outputs: 1
 - Efficiency: 93/85 %
 - Ripple And Noise: 75 mV Pk-Pk
 - Maximum Temperature: +85 °C



1934006 6.5 V dc

RS PRO SWITCHING REGULATOR, PCB MOUNT, 9V DC OUTPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 9 V dc
 - Input Voltage: 13 → 36 V dc
 - Output Current: 1 A
 - Mounting Type: PCB Mount
 - Number of Outputs: 1
 - Efficiency: 94/89 %
 - Ripple And Noise: 75 mV Pk-Pk
 - Minimum Temperature: -40 °C



1934008 9 V dc

RS PRO SWITCHING REGULATOR, PCB MOUNT, 12V DC OUTPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 12 V dc
 - Input Voltage: 16 → 36 V dc
 - Output Current: 1 A
 - Mounting Type: PCB Mount
 - Number of Outputs: 1
 - Efficiency: 95/92 %
 - Ripple And Noise: 75 mV Pk-Pk
 - Minimum Temperature: -40 °C



1934010 12 V dc

RS PRO SWITCHING REGULATOR, PCB MOUNT, 3.3V DC OUTPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 3.3 V dc
 - Input Voltage: 6 → 36 V dc
 - Output Current: 1 A
 - Mounting Type: PCB Mount
 - Number of Outputs: 1
 - Efficiency: 90/81 %
 - Ripple And Noise: 75 mV Pk-Pk
 - Minimum Temperature: -40 °C



1934013 3.3 V dc

RS PRO SWITCHING REGULATOR, PCB MOUNT, 5V DC OUTPUT

- ขนาดบรรจุภัณฑ์: **44 x EA**
- Output Voltage: 5 V dc
 - Input Voltage: 8 → 36 V dc
 - Output Current: 1 A
 - Mounting Type: PCB Mount
 - Number of Outputs: 1
 - Efficiency: 93/86 %
 - Ripple And Noise: 75 mV Pk-Pk
 - Maximum Temperature: +85 °C



1934014 5 V dc

RS PRO SWITCHING REGULATOR, PCB MOUNT, 5V DC OUTPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 5 V dc
 - Input Voltage: 8 → 36 V dc
 - Output Current: 1 A
 - Mounting Type: PCB Mount
 - Number of Outputs: 1
 - Efficiency: 93/86 %
 - Ripple And Noise: 75 mV Pk-Pk
 - Maximum Temperature: +85 °C



1934015 5 V dc

RS PRO SWITCHING REGULATOR, PCB MOUNT, 9V DC OUTPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 9 V dc
 - Input Voltage: 13 → 36 V dc
 - Output Current: 1 A
 - Mounting Type: PCB Mount
 - Number of Outputs: 1
 - Efficiency: 95/90 %
 - Ripple And Noise: 75 mV Pk-Pk
 - Minimum Temperature: -40 °C



1934017 9 V dc

RS PRO SWITCHING REGULATOR, PCB MOUNT, 12V DC OUTPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 12 V dc
 - Input Voltage: 16 → 36 V dc
 - Output Current: 1 A
 - Mounting Type: PCB Mount
 - Number of Outputs: 1
 - Efficiency: 96/93 %
 - Ripple And Noise: 75 mV Pk-Pk
 - Minimum Temperature: -40 °C



1934019 12 V dc

RS PRO SWITCHING REGULATOR, PCB MOUNT, 15V DC OUTPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 15 V dc
 - Input Voltage: 18 → 36 V dc
 - Output Current: 1 A
 - Mounting Type: PCB Mount
 - Number of Outputs: 1
 - Efficiency: 96/94 %
 - Ripple And Noise: 75 mV Pk-Pk
 - Minimum Temperature: -40 °C



1934021 15 V dc

RS PRO SWITCHING REGULATOR, PCB MOUNT, 3.3V DC OUTPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 3.3 V dc
 - Input Voltage: 6 → 36 V dc
 - Output Current: 1 A
 - Mounting Type: PCB Mount
 - Number of Outputs: 1
 - Efficiency: 90/81 %
 - Ripple And Noise: 75 mV Pk-Pk
 - Minimum Temperature: -40 °C



1934023 3.3 V dc

RS PRO SWITCHING REGULATOR, PCB MOUNT, 5V DC OUTPUT

- ขนาดบรรจุภัณฑ์: **44 x EA**
- Output Voltage: 5 V dc
 - Input Voltage: 6 → 36 V dc
 - Output Current: 1 A
 - Mounting Type: PCB Mount
 - Number of Outputs: 1
 - Efficiency: 93/86 %
 - Ripple And Noise: 75 mV Pk-Pk
 - Minimum Temperature: -40 °C



1934024 5 V dc

RS PRO SWITCHING REGULATOR, PCB MOUNT, 5V DC OUTPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 5 V dc
 - Input Voltage: 8 → 36 V dc
 - Output Current: 1 A
 - Mounting Type: PCB Mount
 - Number of Outputs: 1
 - Efficiency: 93/86 %
 - Ripple And Noise: 75 mV Pk-Pk
 - Minimum Temperature: -40 °C



1934025 5 V dc

RS PRO SWITCHING REGULATOR, PCB MOUNT, 12V DC OUTPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 12 V dc
 - Input Voltage: 16 → 36 V dc
 - Output Current: 1 A
 - Mounting Type: PCB Mount
 - Number of Outputs: 1
 - Efficiency: 96/93 %
 - Ripple And Noise: 75 mV Pk-Pk
 - Minimum Temperature: -40 °C



1934028 12 V dc

RS PRO SWITCHING REGULATOR, PCB MOUNT, 3.3V DC OUTPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 3.3 V dc
 - Input Voltage: 6 → 36 V dc
 - Output Current: 2 A
 - Mounting Type: PCB Mount
 - Number of Outputs: 1
 - Efficiency: 89/85 %
 - Ripple And Noise: 75 mV Pk-Pk
 - Minimum Temperature: -40 °C



1934030 3.3 V dc

RS PRO SWITCHING REGULATOR, PCB MOUNT, 5V DC OUTPUT

- ขนาดบรรจุภัณฑ์: **44 x EA**
- Output Voltage: 5 V dc
 - Input Voltage: 8 → 36 V dc
 - Output Current: 2 A
 - Mounting Type: PCB Mount
 - Number of Outputs: 1
 - Efficiency: 92/89 %
 - Ripple And Noise: 75 mV Pk-Pk
 - Minimum Temperature: -40 °C



1934031 5 V dc

RS PRO SWITCHING REGULATOR, PCB MOUNT, 5V DC OUTPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 5 V dc
 - Input Voltage: 8 → 36 V dc
 - Output Current: 2 A
 - Mounting Type: PCB Mount
 - Number of Outputs: 1
 - Efficiency: 92/89 %
 - Ripple And Noise: 75 mV Pk-Pk
 - Minimum Temperature: -40 °C



1934032 5 V dc

RS PRO SWITCHING REGULATOR, PCB MOUNT, 9V DC OUTPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 9 V dc
 - Input Voltage: 13 → 36 V dc
 - Output Current: 2 A
 - Mounting Type: PCB Mount
 - Number of Outputs: 1
 - Efficiency: 95/92 %
 - Ripple And Noise: 75 mV Pk-Pk
 - Minimum Temperature: -40 °C



1934035 9 V dc

RS PRO SWITCHING REGULATOR, PCB MOUNT, 12V DC OUTPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 12 V dc
 - Input Voltage: 16 → 36 V dc
 - Output Current: 2 A
 - Mounting Type: PCB Mount
 - Number of Outputs: 1
 - Efficiency: 96/94 %
 - Ripple And Noise: 75 mV Pk-Pk
 - Maximum Temperature: +85 °C



1934037 12 V dc

RS PRO SWITCHING REGULATOR, PCB MOUNT, 3.3V DC OUTPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 3.3 V dc
 - Input Voltage: 8 → 36 V dc
 - Output Current: 2 A
 - Mounting Type: PCB Mount
 - Number of Outputs: 1
 - Efficiency: 92/89 %
 - Ripple And Noise: 75 mV Pk-Pk
 - Maximum Temperature: +85 °C



1934041 3.3 V dc

RS PRO SWITCHING REGULATOR, PCB MOUNT, 5V DC OUTPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 5 V dc
 - Input Voltage: 8 → 36 V dc
 - Output Current: 2 A
 - Mounting Type: PCB Mount
 - Number of Outputs: 1
 - Efficiency: 92/89 %
 - Ripple And Noise: 75 mV Pk-Pk
 - Minimum Temperature: -40 °C



1934043 5 V dc

RS PRO SWITCHING REGULATOR, PCB MOUNT, 12V DC OUTPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Voltage: 12 V dc
 - Input Voltage: 16 → 36 V dc
 - Output Current: 2 A
 - Mounting Type: PCB Mount
 - Number of Outputs: 1
 - Efficiency: 96/94 %
 - Ripple And Noise: 75 mV Pk-Pk
 - Minimum Temperature: -40 °C



1934045 12 V dc

RS PRO VERTICAL PP FLOAT SWITCH, FLOAT, 300MM CABLE, DIRECT LOAD,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Device Type: Float
 - Mounting Type: Vertical
 - Switch Output: Direct Load
 - Body Material: PP
 - Cable Length: 300 mm
 - Minimum Operating Temperature: -20 °C
 - Maximum Operating Temperature: +80 °C
 - Maximum AC Voltage: 250 V



519232 Float

RS PRO VERTICAL PP FLOAT SWITCH, FLOAT, 300MM CABLE, DIRECT LOAD,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Device Type: Float
 - Mounting Type: Vertical
 - Switch Output: Direct Load
 - Body Material: PP
 - Cable Length: 300 mm
 - Minimum Operating Temperature: -20 °C
 - Maximum Operating Temperature: +80 °C
 - Maximum AC Voltage: 140 V



519236 Float

RS PRO VERTICAL PP FLOAT SWITCH, FLOAT, 300MM CABLE, DIRECT LOAD,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Device Type: Float
 - Mounting Type: Vertical
 - Switch Output: Direct Load
 - Body Material: PP
 - Cable Length: 300 mm
 - Minimum Operating Temperature: -20 °C
 - Maximum Operating Temperature: +80 °C
 - Maximum AC Voltage: 140 V



519242 Float

RS PRO VERTICAL PP FLOAT SWITCH, FLOAT, 300MM CABLE, DIRECT LOAD,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Device Type: Float
 - Mounting Type: Vertical
 - Switch Output: Direct Load
 - Body Material: PP
 - Cable Length: 300 mm
 - Minimum Operating Temperature: -20 °C
 - Maximum Operating Temperature: +80 °C
 - Maximum AC Voltage: 130 V



519248 Float

RS PRO VERTICAL PP FLOAT SWITCH, FLOAT, 300MM CABLE, DIRECT LOAD,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Device Type: Float
 - Mounting Type: Vertical
 - Switch Output: Direct Load
 - Body Material: PP
 - Cable Length: 300 mm
 - Minimum Operating Temperature: -20 °C
 - Maximum Operating Temperature: +80 °C
 - Maximum AC Voltage: 250 V



519258 Float

RS PRO FLANGE MOUNT ALUMINIUM (ENCLOSURE), SS 316L (FLOAT) FLOAT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Device Type: Float
 - Mounting Type: Flange Mount
 - Switch Output: SPDT
 - Body Material: Aluminium (Enclosure), SS 316L (Float)
 - Minimum Operating Temperature: 0 °C
 - Maximum Operating Temperature: +130 °C
 - Maximum AC Voltage: 250 V
 - Maximum DC Voltage: 30 V



1880316 Float

RS PRO HORIZONTAL STAINLESS STEEL FLOAT SWITCH, FLOAT, 300MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Device Type: Float
 - Mounting Type: Horizontal
 - Switch Output: Direct Load
 - Body Material: Stainless Steel
 - Cable Length: 300 mm
 - Minimum Operating Temperature: -10 °C
 - Maximum Operating Temperature: +120 °C
 - Maximum AC Voltage: 300 V



2356204 Float

RS PRO VERTICAL STAINLESS STEEL FLOAT SWITCH, FLOAT, 300MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Device Type: Float
 - Mounting Type: Vertical
 - Switch Output: Direct Load
 - Body Material: Stainless Steel
 - Cable Length: 300 mm
 - Minimum Operating Temperature: -10 °C
 - Maximum Operating Temperature: +120 °C
 - Maximum AC Voltage: 300 V



3127164 Float

RS PRO VERTICAL STAINLESS STEEL FLOAT SWITCH, FLOAT, 300MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Device Type: Float
 - Mounting Type: Vertical
 - Switch Output: NO/NC
 - Body Material: Stainless Steel
 - Cable Length: 300 mm
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +125 °C
 - Maximum AC Voltage: 250 V



7621036 Float

RS PRO HORIZONTAL STAINLESS STEEL FLOAT SWITCH, FLOAT, 300MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Device Type: Float
 - Mounting Type: Horizontal
 - Switch Output: NO
 - Body Material: Stainless Steel
 - Cable Length: 300 mm
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +125 °C
 - Maximum AC Voltage: 250 V



7621039 Float

RS PRO RADIAL FLOW TURBINE FLOW METER FOR LIQUID, 1.5 L/MIN MIN, 30

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Media Monitored: Liquid
 - Device Type: Radial Flow Turbine
 - Minimum Flow Rate: 1.5 L/min
 - Maximum Flow Rate: 30 L/min
 - Supply Voltage: 4.5 → 16 V dc
 - Pipe Diameter Range: 15 mm
 - Maximum Pressure: 20 bar
 - Material: Acetal Copolymer



257133 Liquid

RS PRO RADIAL FLOW TURBINE FLOW METER FOR LIQUID, 0.25 L/MIN MIN,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Media Monitored: Liquid
 - Device Type: Radial Flow Turbine
 - Minimum Flow Rate: 0.25 L/min
 - Maximum Flow Rate: 6.5 L/min
 - Supply Voltage: 4.5 → 16 V dc
 - Pipe Diameter Range: 15 mm
 - Maximum Pressure: 20 bar
 - Material: Acetal Copolymer



257149 Liquid

RS PRO OVAL GEAR FLOW METER FOR LIQUID, 0.01 L/MIN MIN, 1 L/MIN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Media Monitored: Liquid
 - Device Type: Oval Gear
 - Minimum Flow Rate: 0.01 L/min
 - Maximum Flow Rate: 1 L/min
 - Supply Voltage: 5 → 24 V dc
 - Pipe Diameter Range: 1/4 in
 - Connection Type: 1/4 BSP
 - Maximum Pressure: 50 bar



4474427 Liquid

RS PRO OVAL GEAR FLOW METER FOR LIQUID, 0.01 L/MIN MIN, 4 L/MIN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Media Monitored: Liquid
 - Device Type: Oval Gear
 - Minimum Flow Rate: 0.01 L/min
 - Maximum Flow Rate: 4 L/min
 - Supply Voltage: 5 → 24 V dc
 - Pipe Diameter Range: 1/4 in
 - Connection Type: 1/4 BSP
 - Maximum Pressure: 50 bar



4474449 Liquid

RS PRO FLOW METER, 0.05 → 10 L/MIN MAX

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Maximum Flow Rate: 0.05 → 10 L/min
 - Supply Voltage: 4.5 → 24 V dc
 - Pipe Diameter Range: 8 mm
 - Minimum Operating Temperature: -25 °C
 - Maximum Operating Temperature: +125 °C
 - Current Rating: 8 mA



5082704 0.05 → 10 L/min

RS PRO PISTON INLINE FLOW SWITCH FOR LIQUID, 0.04 L/MIN MIN, 0.13

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Media Monitored: Liquid
 - Device Type: Piston Inline
 - Minimum Flow Rate: 0.04 L/min
 - Maximum Flow Rate: 0.13 L/min
 - Supply Voltage: 200 V ac
 - Pipe Diameter Range: 1/4 in
 - Connection Type: 1/4 BSP
 - Maximum Pressure: 300 bar



5100559 Liquid

RS PRO PISTON INLINE FLOW SWITCH FOR LIQUID, 0.1 L/MIN MIN, 0.6 L/MIN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Media Monitored: Liquid
 - Device Type: Piston Inline
 - Minimum Flow Rate: 0.1 L/min
 - Maximum Flow Rate: 0.6 L/min
 - Supply Voltage: 200 V ac
 - Pipe Diameter Range: 1/4 in
 - Connection Type: 1/4 BSP
 - Maximum Pressure: 300 bar



5100565 Liquid

RS PRO PISTON INLINE FLOW SWITCH FOR LIQUID, 0.5 L/MIN MIN, 3 L/MIN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Media Monitored: Liquid
 - Device Type: Piston Inline
 - Minimum Flow Rate: 0.5 L/min
 - Maximum Flow Rate: 3 L/min
 - Supply Voltage: 200 V ac
 - Pipe Diameter Range: 1/4 in
 - Connection Type: 1/4 BSP
 - Maximum Pressure: 300 bar



5100571 Liquid

RS PRO FLOW METER, 2.5 → 30.0 L/MIN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Maximum Flow Rate: 2.5 → 30.0 L/min
 - Supply Voltage: 4.5 → 24 V dc
 - Pipe Diameter Range: 1/2 in
 - Minimum Operating Temperature: -25 °C
 - Maximum Operating Temperature: +125 °C
 - Current Rating: 10 mA



5113909 2.5 → 30.0 L/min

RS PRO FLOW METER, 6 → 100 L/MIN MAX

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Maximum Flow Rate: 6 → 100 L/min
 - Supply Voltage: 4.5 → 24 V dc
 - Pipe Diameter Range: 3/4 in
 - Minimum Operating Temperature: -25 °C
 - Maximum Operating Temperature: +125 °C
 - Current Rating: 10 mA



5113915 6 → 100 L/min

RS PRO TURBINE FLOW METER FOR LIQUID, 0.25 L/MIN MIN, 6.5 L/MIN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Media Monitored: Liquid
 - Device Type: Turbine
 - Minimum Flow Rate: 0.25 L/min
 - Maximum Flow Rate: 6.5 L/min
 - Supply Voltage: 4.5 → 24 V dc
 - Pipe Diameter Range: 1/4 in
 - Connection Type: 1/4 BSP
 - Maximum Pressure: 10 bar



5113965 Liquid

RS PRO TURBINE FLOW METER FOR LIQUID, 0.5 L/MIN MIN, 15 L/MIN MAX

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Media Monitored: Liquid
 - Device Type: Turbine
 - Minimum Flow Rate: 0.5 L/min
 - Maximum Flow Rate: 15 L/min
 - Supply Voltage: 4.5 → 24 V dc
 - Pipe Diameter Range: 1/2 in
 - Connection Type: 1/2 BSP
 - Maximum Pressure: 10 bar



5113971 Liquid

RS PRO FLOW METER FOR LIQUID, 0.6 L/MIN MIN, 10 L/MIN MAX

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Media Monitored: Beverage
 - Device Type: Beverage
 - Minimum Flow Rate: 0.6 L/min
 - Maximum Flow Rate: 10 L/min
 - Supply Voltage: 4.5 → 24 V dc
 - Pipe Diameter Range: 4/32 in
 - Connection Type: 3/8 Push On
 - Maximum Pressure: 10 bar



5114772 Liquid

RS PRO PADDLE FLOW SWITCH FOR GAS, LIQUID, 4 L/MIN MIN, 5.5 L/MIN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Media Monitored: Gas, Liquid
 - Device Type: Paddle
 - Minimum Flow Rate: 4 L/min
 - Maximum Flow Rate: 5.5 L/min
 - Supply Voltage: 250 V ac
 - Pipe Diameter Range: 10 mm
 - Connection Type: 3/8 BSP Female
 - Maximum Pressure: 25 bar



6134216 Gas, Liquid

RS PRO PADDLE FLOW SWITCH FOR GAS, LIQUID, 5.5 L/MIN MIN, 7 L/MIN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Media Monitored: Gas, Liquid
 - Device Type: Paddle
 - Minimum Flow Rate: 5.5 L/min
 - Maximum Flow Rate: 7 L/min
 - Supply Voltage: 250 V ac
 - Pipe Diameter Range: 15 mm
 - Connection Type: 1/2 BSP Female
 - Maximum Pressure: 25 bar



6134238 Gas, Liquid

RS PRO PADDLE FLOW SWITCH FOR GAS, LIQUID, 14 L/MIN MIN, 18 L/MIN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Media Monitored: Gas, Liquid
 - Device Type: Paddle
 - Minimum Flow Rate: 14 L/min
 - Maximum Flow Rate: 18 L/min
 - Supply Voltage: 250 V ac
 - Pipe Diameter Range: 25 mm
 - Connection Type: 1 BSP Female
 - Maximum Pressure: 25 bar



6134244 Gas, Liquid

RS PRO PRESSURE SENSOR, 0BAR MIN, 1BAR MAX, ANALOGUE OUTPUT,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Pressure Reading Type: Relative
 - Minimum Pressure Reading: 0 bar
 - Maximum Pressure Reading: 1 bar
 - Accuracy: ±0.25 %
 - Output Type: Analogue
 - Process Connection: G1/4
 - Electrical Connection: M12 4-pin
 - Analogue Output: 4 → 20 mA



1754983 Relative

RS PRO PRESSURE SENSOR, 0BAR MIN, 10BAR MAX, ANALOGUE OUTPUT,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Pressure Reading Type: Relative
 - Minimum Pressure Reading: 0 bar
 - Maximum Pressure Reading: 10 bar
 - Accuracy: ±0.25 %
 - Output Type: Analogue
 - Process Connection: G1/4
 - Analogue Output: 4 → 20 mA
 - Electrical Connection: M12 4-pin



1754985 Relative

RS PRO PRESSURE SENSOR, 0BAR MIN, 10BAR MAX, ANALOGUE OUTPUT,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Pressure Reading Type: Relative
 - Minimum Pressure Reading: 0 bar
 - Maximum Pressure Reading: 10 bar
 - Accuracy: ±0.25 %
 - Output Type: Analogue
 - Process Connection: G1/4
 - Electrical Connection: M12 4-pin
 - Analogue Output: 0 → 5 V



1754986 Relative

RS PRO PRESSURE SENSOR, 0BAR MIN, 100BAR MAX, ANALOGUE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Pressure Reading Type: Relative
 - Minimum Pressure Reading: 0 bar
 - Maximum Pressure Reading: 100 bar
 - Accuracy: ±0.25 %
 - Output Type: Analogue
 - Process Connection: G1/4
 - Analogue Output: 0 → 5 V
 - Electrical Connection: M12 4-pin



1754989 Relative

RS PRO PRESSURE SENSOR, 0BAR MIN, 16BAR MAX, ANALOGUE OUTPUT,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Pressure Reading Type: Relative
 - Minimum Pressure Reading: 0 bar
 - Maximum Pressure Reading: 16 bar
 - Accuracy: ±0.25 %
 - Output Type: Analogue
 - Process Connection: G1/4
 - Analogue Output: 4 → 20 mA
 - Electrical Connection: M12 4-pin



1754990 Relative

RS PRO PRESSURE SENSOR, 0BAR MIN, 400BAR MAX, ANALOGUE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Pressure Reading Type: Relative
 - Minimum Pressure Reading: 0 bar
 - Maximum Pressure Reading: 400 bar
 - Accuracy: ±0.25 %
 - Output Type: Analogue
 - Process Connection: G1/4
 - Analogue Output: 4 → 20 mA
 - Electrical Connection: M12 4-pin



1754999 Relative

RS PRO PRESSURE SENSOR, 0BAR MIN, 5BAR MAX, CURRENT OUTPUT,

ขนาดบรรจุภัณฑ์: **1 x EA**

- Pressure Reading Type: Relative
- Minimum Pressure Reading: 0 bar
- Maximum Pressure Reading: 5 bar
- Accuracy: $\pm 0.25\%$
- Output Type: Current
- Media Measured: Sewage, Viscous Fluid, Water
- Process Connection: G3/4
- Analogue Output: 4 → 20 mA



8285763 Relative

RS PRO PRESSURE SENSOR, 0BAR MIN, 10BAR MAX, CURRENT OUTPUT,

ขนาดบรรจุภัณฑ์: **1 x EA**

- Pressure Reading Type: Relative
- Minimum Pressure Reading: 0 bar
- Maximum Pressure Reading: 10 bar
- Accuracy: $\pm 0.25\%$
- Output Type: Current
- Media Measured: Sewage, Viscous Fluid, Water
- Process Connection: G3/4
- Electrical Connection: M12 Connector



8285767 Relative

RS PRO PRESSURE SENSOR, 0BAR MIN, 20BAR MAX, CURRENT OUTPUT,

ขนาดบรรจุภัณฑ์: **1 x EA**

- Pressure Reading Type: Relative
- Minimum Pressure Reading: 0 bar
- Maximum Pressure Reading: 20 bar
- Accuracy: $\pm 0.25\%$
- Output Type: Current
- Media Measured: Sewage, Viscous Fluid, Water
- Process Connection: G3/4
- Analogue Output: 4 → 20 mA



8285776 Relative

RS PRO PRESSURE SENSOR, -1BAR MIN, 1BAR MAX, CURRENT OUTPUT,

ขนาดบรรจุภัณฑ์: **1 x EA**

- Pressure Reading Type: Relative
- Minimum Pressure Reading: -1 bar
- Maximum Pressure Reading: 1 bar
- Accuracy: $\pm 0.25\%$
- Output Type: Current
- Media Measured: Sewage, Viscous Fluid, Water
- Process Connection: G3/4
- Analogue Output: 4 → 20 mA



8285811 Relative

RS PRO PRESSURE SENSOR, -1BAR MIN, 9BAR MAX, CURRENT OUTPUT,

ขนาดบรรจุภัณฑ์: **1 x EA**

- Pressure Reading Type: Relative
- Minimum Pressure Reading: -1 bar
- Maximum Pressure Reading: 9 bar
- Accuracy: $\pm 0.25\%$
- Output Type: Current
- Media Measured: Sewage, Viscous Fluid, Water
- Process Connection: G3/4
- Analogue Output: 4 → 20 mA



8285818 Relative

RS PRO PRESSURE SENSOR, 0BAR MIN, 1BAR MAX, CURRENT OUTPUT,

ขนาดบรรจุภัณฑ์: **1 x EA**

- Pressure Reading Type: Absolute
- Minimum Pressure Reading: 0 bar
- Maximum Pressure Reading: 1 bar
- Accuracy: $\pm 0.25\%$
- Output Type: Current
- Media Measured: Sewage, Viscous Fluid, Water
- Process Connection: G3/4
- Electrical Connection: M12 Connector



8285820 Absolute

RS PRO YELLOW DIE CAST ALUMINIUM PUSH BUTTON

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Cutout Diameter: 22 mm
 - Number of Cutouts: 1
 - Enclosure Colour: Yellow
 - Enclosure Material: Die Cast Aluminium
 - IP Rating: IP65
 - Length: 72 mm
 - Width: 72 mm



1368581 22 mm

RS PRO YELLOW DIE CAST ALUMINIUM PUSH BUTTON

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Cutout Diameter: 22 mm
 - Number of Cutouts: 1
 - Enclosure Colour: Yellow
 - Enclosure Material: Die Cast Aluminium
 - IP Rating: IP65
 - Length: 105 mm
 - Width: 68 mm



1368582 22 mm

RS PRO STAINLESS STEEL PUSH BUTTON ENCLOSURE - 1 HOLE 22MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Cutout Diameter: 22 mm
 - Number of Cutouts: 1
 - Enclosure Material: Stainless Steel
 - IP Rating: IP66, IP69K
 - Length: 75 mm
 - Width: 50 mm
 - Depth: 75 mm
 - Dimensions: 75 x 50 x 75 mm



1611521 22 mm

RS PRO STAINLESS STEEL PUSH BUTTON ENCLOSURE - 2 HOLE 22MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Cutout Diameter: 22 mm
 - Number of Cutouts: 2
 - Enclosure Material: Stainless Steel
 - IP Rating: IP66, IP69K
 - Length: 100 mm
 - Width: 85 mm
 - Depth: 160 mm
 - Dimensions: 100 x 85 x 160 mm



1611522 22 mm

RS PRO STAINLESS STEEL PUSH BUTTON ENCLOSURE - 3 HOLE 22MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Cutout Diameter: 22 mm
 - Number of Cutouts: 3
 - Enclosure Material: Stainless Steel
 - IP Rating: IP66, IP69K
 - Length: 100 mm
 - Width: 85 mm
 - Depth: 220 mm
 - Dimensions: 100 x 85 x 220 mm



1611523 22 mm

RS PRO STAINLESS STEEL PUSH BUTTON ENCLOSURE - 1 HOLE 22MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Cutout Diameter: 22 mm
 - Number of Cutouts: 1
 - Enclosure Material: Stainless Steel
 - IP Rating: IP66, IP69K
 - Length: 115 mm
 - Width: 85 mm
 - Depth: 115 mm
 - Dimensions: 115 x 85 x 115 mm



1611524 22 mm

RS PRO ELECTRONIC SOUNDER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: 12 V Pulsing Sounder
 - For Use With: Alarm Circuit



9092562 12 V Pulsing

RS PRO ELECTRONIC SOUNDER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: 24 V Pulsing Sounder
 - For Use With: Alarm Circuit



9092566 24 V Pulsing

SWITCH, FOOT, ACTUATOR, AIR OPERATED, BLACK

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Bellow
 - For Use With: Air Operated Switch



316945 Bellow

RS PRO FOOT SWITCH BELLOWS FOR IPX7 PLASTIC FOOT SWITCH

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Bellow
 - For Use With: IPX7 Plastic Foot Switch



335353 Bellow

SWITCH, FOOT, ACTUATOR, AIR OPERATED, RED

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Bellow
 - For Use With: Foot Switch



335375 Bellow

SWITCH, FOOT, ACTUATOR, AIR OPERATED, GREY

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Bellow
 - For Use With: Foot Switch



335397 Bellow

SWITCH, FOOT, HAND, PVC, BLACK, 3A, 24VDC, N/O, 100000

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Bellow
 - For Use With: IPX7 Plastic Foot Switch



335404 Bellow

FOOT SWITCH GUARD COVER FOR FOOT SWITCH

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Cover
 - For Use With: Foot Switch



116653 Cover

FOOT SWITCH GUARD COVER FOR FOOT SWITCH

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Guard
 - For Use With: Foot Switch



116726 Guard

RS PRO FOOT SWITCH MOMENTARY ON-OFF FOOT SWITCH - 16 SWG MILD

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Switch Operation: Momentary On-Off
 - Case Material: 16 SWG Mild Steel
 - Switch Environment: Foot Switch
 - IP Rating: IPX2
 - Guard Cover: No
 - Colour: Black, Grey
 - Height: 24 mm
 - Width: 66 mm



170806 Momentary On-

RS PRO MOMENTARY ON-OFF FOOT SWITCH - DIE CAST ALUMINIUM CASE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Foot Switch Type: Heavy Duty Foot Switch
 - Switch Operation: Momentary On-Off
 - Case Material: Die Cast Aluminium
 - Switch Environment: Heavy Duty
 - IP Rating: IPX7
 - Guard Cover: No
 - Colour: Black
 - Standards Met: 2014/35/EU, EN 60950, EN 61058, EN 61058-2-1



317718 Heavy Duty Foot

RS PRO FOOT SWITCH BELLOW MOMENTARY FOOT SWITCH - PVC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Foot Switch Type: Momentary Foot Switch
 - Contact Configuration: Single Pole Single Throw (SPST)
 - Switch Operation: Momentary
 - Case Material: PVC
 - Contact Voltage Rating (DC): 24 V
 - Contact Current Rating: 50 mA
 - Switch Environment: Foot Switch Bellow
 - IP Rating: IP67



335303 Momentary Foot

SWITCH, FOOT, HAND, BLACK, 1 N/O, 30MA, 24VDC, 100000, IP67

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Foot Switch Type: Momentary Foot Switch
 - Contact Configuration: SPST N/O
 - Switch Operation: Momentary
 - Case Material: PVC
 - Contact Voltage Rating (DC): 24 V
 - Contact Current Rating: 50 mA @ 24 V
 - Switch Environment: Foot Switch Bellow
 - IP Rating: IP67



335319 Momentary Foot

SWITCH, AIR OPERATED, HAND, INDUSTRIAL, GLASS

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Contact Configuration: SPST-NO
 - Switch Operation: Momentary On-Off
 - Case Material: Thermoplastic
 - Switch Environment: Light Industrial
 - IP Rating: IPX7
 - Guard Cover: Yes
 - Colour: Black
 - Standards Met: 2014/35/EU, EN 60950



335381 SPST-NO

RS PRO LIGHT INDUSTRIAL MOMENTARY USB PROGRAMMABLE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Foot Switch Type: Momentary Foot Switch
 - Contact Configuration: Single Pole Single Throw (SPST)
 - Switch Operation: Momentary
 - Case Material: Glass Fibre Reinforced Polymer
 - Contact Voltage Rating (AC): 5 V
 - Contact Current Rating: 25 mA @ 5 V ac
 - Switch Environment: Light Industrial
 - IP Rating: IPX2



474537 Momentary Foot

HEAVY DUTY FOOTSWITCH (NO GUARD)

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Contact Configuration: SP-CO
 - Foot Switch Type: Heavy Duty Foot Switch
 - Switch Operation: Slow Action
 - Contact Voltage Rating (AC): 600 V
 - Contact Voltage Rating (DC): 500 V
 - Contact Current Rating: 10 A
 - Switch Environment: Heavy Duty
 - IP Rating: IP65



1222790 SP-CO

RS PRO MOMENTARY HEAVY DUTY FOOT SWITCH - SP-CO, 10 A

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Contact Configuration: SP-CO
 - Foot Switch Type: Heavy Duty Foot Switch
 - Switch Operation: Momentary
 - Contact Voltage Rating (AC): 600 V
 - Contact Voltage Rating (DC): 500 V
 - Contact Current Rating: 10 A
 - Switch Environment: Heavy Duty
 - IP Rating: IP65



1222791 SP-CO

RS PRO MOMENTARY STAGGERED HEAVY DUTY FOOT SWITCH - DIE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Foot Switch Type: Heavy Duty Foot Switch
 - Contact Configuration: DPST + DPST
 - Switch Operation: Momentary Staggered
 - Case Material: Die Cast Aluminium
 - Contact Voltage Rating (AC): 500 V
 - Contact Voltage Rating (DC): 24 V
 - Contact Current Rating: 6 A (AC15 230V), 6 A (DC13 24V)
 - Switch Environment: Heavy Duty



2083265 Heavy Duty Foot

RS PRO MOMENTARY HEAVY DUTY FOOT SWITCH - DIE CAST ALUMINIUM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Foot Switch Type: Heavy Duty Foot Switch
 - Contact Configuration: Single Pole Single Throw (SPST)
 - Switch Operation: Momentary
 - Case Material: Die Cast Aluminium
 - Contact Voltage Rating (AC): 500 V
 - Contact Voltage Rating (DC): 24 V
 - Contact Current Rating: 12 A
 - Switch Environment: Heavy Duty



4405566 Heavy Duty Foot

RS PRO MEDICALLY APPROVED FOOT SWITCH BELLOW MOMENTARY

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Foot Switch Type: Momentary Foot Switch
 - Contact Configuration: Single Pole Single Throw (SPST)
 - Switch Operation: Momentary
 - Case Material: PVC
 - Contact Voltage Rating (DC): 30 V
 - Contact Current Rating: 50 mA
 - Switch Environment: Medically Approved Foot Switch Bellow
 - IP Rating: IP67



4561701 Momentary Foot

SWITCH, FOOT, SMALL, IP67, RED

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Foot Switch Type: Momentary Foot Switch
 - Contact Configuration: Single Pole Single Throw (SPST)
 - Switch Operation: Momentary
 - Case Material: PVC
 - Contact Voltage Rating (DC): 30 V
 - Contact Current Rating: 50 mA
 - Switch Environment: Foot Switch Bellow
 - IP Rating: IP67



4561717 Momentary Foot

RS PRO MEDICALLY APPROVED FOOT SWITCH BELLOW MOMENTARY

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Foot Switch Type: Momentary Foot Switch
 - Contact Configuration: Single Pole Single Throw (SPST)
 - Switch Operation: Momentary
 - Case Material: PVC
 - Contact Voltage Rating (DC): 30 V
 - Contact Current Rating: 50 mA
 - Switch Environment: Medically Approved Foot Switch Bellow
 - IP Rating: IP67



4561739 Momentary Foot

FOOT SWITCH, PLASTIC IP67, SPDT, 3A

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Contact Configuration: Single Pole Double Throw (SPDT)
 - Foot Switch Type: Momentary Foot Switch
 - Switch Operation: Momentary
 - Case Material: Thermoplastic
 - Contact Voltage Rating (AC): 24 V
 - Contact Voltage Rating (DC): 24 V
 - Contact Current Rating: 3 A
 - Switch Environment: General Purpose



7748614 Single Pole

6210-VO BLACK FOOT POTENTIOMETER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Foot Switch Type: Momentary Foot Switch
 - Switch Operation: Momentary
 - Case Material: Thermoplastic
 - Contact Voltage Rating (AC): 12 V
 - Contact Current Rating: 6 A @ 250 V ac
 - Switch Environment: Light Industrial
 - IP Rating: IPX2
 - Colour: Black



8039772 Momentary Foot

RS PRO GENERAL PURPOSE MOMENTARY FOOT SWITCH -

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Contact Configuration: SP-CO
 - Foot Switch Type: Momentary Foot Switch
 - Switch Operation: Momentary
 - Case Material: Thermoplastic
 - Contact Voltage Rating (AC): 24 V
 - Contact Voltage Rating (DC): 24 V
 - Contact Current Rating: 1.75 A
 - Switch Environment: General Purpose



8086982 SP-CO

RS PRO GENERAL PURPOSE MOMENTARY FOOT SWITCH -

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Contact Configuration: SP-CO
 - Foot Switch Type: Momentary Foot Switch
 - Switch Operation: Momentary
 - Case Material: Thermoplastic
 - Contact Voltage Rating (AC): 24 V
 - Contact Voltage Rating (DC): 24 V
 - Contact Current Rating: 1.75 A
 - Switch Environment: General Purpose



8086986 SP-CO

GREY IPX2 COMPACT FOOTSWITCH NO/NC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Contact Configuration: SP-CO
 - Foot Switch Type: Momentary Foot Switch
 - Switch Operation: Momentary
 - Case Material: Thermoplastic
 - Contact Voltage Rating (AC): 24 V
 - Contact Voltage Rating (DC): 24 V
 - Contact Current Rating: 1.75 A
 - Switch Environment: General Purpose



8086989 SP-CO

IPX7 DOUBLE PEDAL FOOTSWITCH 2 X SPNO

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Foot Switch Type: Momentary Foot Switch
 - Contact Configuration: Double Pole Single Throw (DPST)
 - Switch Operation: Momentary
 - Case Material: Thermoplastic
 - Contact Voltage Rating (AC): 24 V
 - Contact Voltage Rating (DC): 24 V
 - Contact Current Rating: 3 A
 - Switch Environment: General Purpose



8086992 Momentary Foot

RS PRO GENERAL PURPOSE MOMENTARY FOOT SWITCH -

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Foot Switch Type: Momentary Foot Switch
 - Contact Configuration: SP-CO
 - Switch Operation: Momentary
 - Case Material: Thermoplastic
 - Contact Voltage Rating (AC): 24 V
 - Contact Voltage Rating (DC): 24 V
 - Contact Current Rating: 1.75 A
 - Switch Environment: General Purpose



8086995 Momentary Foot

IPX7 DOUBLE PEDAL FOOTSWITCH 2 X NO/NC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Foot Switch Type: Momentary Foot Switch
 - Contact Configuration: Double Pole Single Throw (DPST)
 - Switch Operation: Momentary
 - Case Material: Thermoplastic
 - Contact Voltage Rating (AC): 24 V
 - Contact Voltage Rating (DC): 24 V
 - Contact Current Rating: 3 A
 - Switch Environment: General Purpose



8087005 Momentary Foot

RS PRO FLEXIBLE TUBE, 3MM ID, PVC, 10M

- ขนาดบรรจุภัณฑ์: **10 x MTR**
- Inner Diameter: 3 mm
 - Outer Diameter: 6 mm
 - Material: PVC
 - Length: 10 m



317724 3 mm

WEDGE INDICATOR LIGHT, CLEAR, 12 V, 83 MA, 5000H

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Voltage Rating: 12 V
 - Lamp Base: Wedge
 - Current Rating: 83 mA
 - Diameter: 5 mm
 - Lamp Size: T1 1/2
 - Length: 20 mm
 - Lens Colour: Clear
 - Luminosity: 3 lm



6559564 12 V

RS PRO 4P POLE PANEL MOUNT ISOLATOR SWITCH - 32A MAXIMUM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Number of Poles: 4P
 - Maximum Current: 32 A
 - Mounting Type: Panel Mount
 - IP Rating: IP65
 - Power Rating: 15 kW
 - Voltage Rating: 690 V ac
 - Electrical Phase: 3
 - Handle Colour: Red



7737964 4P

RS PRO 6P POLE ISOLATOR SWITCH - 32A MAXIMUM CURRENT, 15KW

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Number of Poles: 6P
 - Maximum Current: 32 A
 - IP Rating: IP65
 - Power Rating: 15 kW
 - Voltage Rating: 690 V ac
 - Electrical Phase: 1, 3
 - Handle Colour: Red
 - Accepts Padlocks: Yes



7737970 6P

RS PRO 4P POLE PANEL MOUNT ISOLATOR SWITCH - 40A MAXIMUM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Number of Poles: 4P
 - Maximum Current: 40 A
 - Mounting Type: Panel Mount
 - IP Rating: IP65
 - Power Rating: 18.5 kW
 - Voltage Rating: 690 V ac
 - Electrical Phase: 3
 - Handle Colour: Red



7737973 4P

RS PRO 6P POLE ISOLATOR SWITCH - 25A MAXIMUM CURRENT, 15KW

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Number of Poles: 6P
 - Maximum Current: 25 A
 - IP Rating: IP65
 - Power Rating: 15 kW
 - Voltage Rating: 690 V ac
 - Electrical Phase: 1, 3
 - Handle Colour: Red
 - Accepts Padlocks: Yes



7737976 6P

RS PRO 6P POLE ISOLATOR SWITCH - 125A MAXIMUM CURRENT, 55KW

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Number of Poles: 6P
 - Maximum Current: 125 A
 - IP Rating: IP65
 - Power Rating: 55 kW
 - Voltage Rating: 690 V ac
 - Electrical Phase: 1, 3
 - Handle Colour: Red
 - Accepts Padlocks: Yes



7737986 6P

RS PRO 6P POLE ISOLATOR SWITCH - 63A MAXIMUM CURRENT, 30KW

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Number of Poles: 6P
 - Maximum Current: 63 A
 - IP Rating: IP65
 - Power Rating: 30 kW
 - Voltage Rating: 690 V ac
 - Electrical Phase: 1, 3
 - Handle Colour: Red
 - Accepts Padlocks: Yes



7737989 6P

RS PRO 4P POLE PANEL MOUNT ISOLATOR SWITCH - 32A MAXIMUM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Number of Poles: 4P
 - Maximum Current: 32 A
 - Mounting Type: Panel Mount
 - IP Rating: IP65
 - Power Rating: 15 kW
 - Voltage Rating: 690 V ac
 - Electrical Phase: 3
 - Accepts Padlocks: Yes



7737992 4P

RS PRO 4P POLE PANEL MOUNT ISOLATOR SWITCH - 40A MAXIMUM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Number of Poles: 4P
 - Maximum Current: 40 A
 - Mounting Type: Panel Mount
 - IP Rating: IP65
 - Power Rating: 18.5 kW
 - Voltage Rating: 690 V ac
 - Electrical Phase: 3
 - Handle Colour: Red



7738005 4P

RS PRO 4P POLE PANEL MOUNT ISOLATOR SWITCH - 63A MAXIMUM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Number of Poles: 4P
 - Maximum Current: 63 A
 - Mounting Type: Panel Mount
 - IP Rating: IP65
 - Power Rating: 30 kW
 - Voltage Rating: 690 V ac
 - Electrical Phase: 3
 - Handle Colour: Red



7738008 4P

RS PRO 3P POLE PANEL MOUNT ISOLATOR SWITCH - 32A MAXIMUM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Number of Poles: 3P
 - Maximum Current: 32 A
 - Mounting Type: Panel Mount
 - IP Rating: IP65
 - Power Rating: 15 kW
 - Voltage Rating: 690 V ac
 - Electrical Phase: 3
 - Handle Colour: Red



7738011 3P

RS PRO 3P POLE PANEL MOUNT ISOLATOR SWITCH - 63A MAXIMUM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Number of Poles: 3P
 - Maximum Current: 63 A
 - Mounting Type: Panel Mount
 - IP Rating: IP54
 - Power Rating: 18.5 kW
 - Voltage Rating: 690 V ac
 - Electrical Phase: 3
 - Handle Colour: Red



7738018 3P

RS PRO 4P POLE PANEL MOUNT ISOLATOR SWITCH - 32A MAXIMUM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Number of Poles: 4P
 - Maximum Current: 32 A
 - Mounting Type: Panel Mount
 - IP Rating: IP54
 - Power Rating: 18.5 kW
 - Voltage Rating: 690 V ac
 - Electrical Phase: 3
 - Handle Colour: Red



7738024 4P

RS PRO 4P POLE PANEL MOUNT ISOLATOR SWITCH - 80A MAXIMUM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Number of Poles: 4P
 - Maximum Current: 80 A
 - Mounting Type: Panel Mount
 - IP Rating: IP54
 - Power Rating: 37 kW
 - Voltage Rating: 690 V ac
 - Electrical Phase: 3
 - Handle Colour: Red



7738030 4P

RS PRO 4P POLE PANEL MOUNT ISOLATOR SWITCH - 40A MAXIMUM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Number of Poles: 4P
 - Maximum Current: 40 A
 - Mounting Type: Panel Mount
 - IP Rating: IP54
 - Voltage Rating: 690 V ac
 - Electrical Phase: 3
 - Handle Colour: Red
 - Accepts Padlocks: Yes



7738033 4P

RS PRO 4P POLE PANEL MOUNT ISOLATOR SWITCH - 63A MAXIMUM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Number of Poles: 4P
 - Maximum Current: 63 A
 - Mounting Type: Panel Mount
 - IP Rating: IP54
 - Power Rating: 18.5 kW
 - Voltage Rating: 690 V ac
 - Electrical Phase: 3
 - Handle Colour: Red



7738036 4P

RS PRO 4P POLE PANEL MOUNT ISOLATOR SWITCH - 125A MAXIMUM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Number of Poles: 4P
 - Maximum Current: 125 A
 - Mounting Type: Panel Mount
 - IP Rating: IP54
 - Power Rating: 75 kW
 - Voltage Rating: 690 V ac
 - Electrical Phase: 3
 - Handle Colour: Red



7738042 4P

RS PRO 4P POLE PANEL MOUNT ISOLATOR SWITCH - 100A MAXIMUM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Number of Poles: 4P
 - Maximum Current: 100 A
 - Mounting Type: Panel Mount
 - IP Rating: IP54
 - Power Rating: 55 kW
 - Voltage Rating: 690 V ac
 - Electrical Phase: 3
 - Accepts Padlocks: Yes



7738049 4P

RS PRO 2 POSITION SELECTOR SWITCH HEAD, 22MM CUTOUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Number of Positions: 2
 - Cutout Diameter: 22 mm
 - Switch Actuation: Latching
 - IP Rating: IP65
 - Angle of Throw: 30 °



1881146 2

RS PRO 2 POSITION SELECTOR SWITCH HEAD, 22MM CUTOUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Number of Positions: 2
 - Cutout Diameter: 22 mm
 - Switch Actuation: Spring Return
 - IP Rating: IP65
 - Angle of Throw: 30 °



1881148 2

RS PRO 2-POSITION KEY SWITCH HEAD, LATCHING, 22MM CUTOUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Cutout Diameter: 22 mm
 - Number of Positions: 2
 - Switch Actuation: Latching
 - IP Rating: IP65
 - Angle of Throw: 30 °



1881149 22 mm

RS PRO 3 POSITION SELECTOR SWITCH HEAD, 22MM CUTOUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Number of Positions: 3
 - Cutout Diameter: 22 mm
 - Switch Actuation: Latching
 - IP Rating: IP65
 - Angle of Throw: 45 °



1881151 3

RS PRO 3 POSITION SELECTOR SWITCH HEAD, 22MM CUTOUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Number of Positions: 3
 - Cutout Diameter: 22 mm
 - Switch Actuation: Spring Return
 - IP Rating: IP65
 - Angle of Throw: 45 °



1881152 3

RS PRO 3-POSITION KEY SWITCH HEAD, LATCHING, 22MM CUTOUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Cutout Diameter: 22 mm
 - Number of Positions: 3
 - Switch Actuation: Latching
 - IP Rating: IP65
 - Angle of Throw: 40 °



1881154 22 mm

RS PRO 3-POSITION KEY SWITCH HEAD, SPRING RETURN, 22MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Cutout Diameter: 22 mm
 - Number of Positions: 3
 - Switch Actuation: Spring Return
 - IP Rating: IP65
 - Angle of Throw: 40 °



1881155 22 mm

RS PRO 2 POSITION SELECTOR SWITCH HEAD, 22MM CUTOUT,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Actuator Colour: Green
 - Illuminated: Yes
 - Number of Positions: 2
 - Cutout Diameter: 22 mm
 - Switch Actuation: Latching
 - IP Rating: IP65
 - Angle of Throw: 30 °



1881156 Green

RS PRO 2 POSITION SELECTOR SWITCH HEAD, 22MM CUTOUT,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Actuator Colour: Green
 - Illuminated: Yes
 - Number of Positions: 2
 - Cutout Diameter: 22 mm
 - Switch Actuation: Spring Return
 - IP Rating: IP65
 - Angle of Throw: 30 °



1881157 Green

RS PRO 2 POSITION SELECTOR SWITCH HEAD, 22MM CUTOUT, RED

- ขนาดบรรจุภัณฑ์: 1 x EA
- Actuator Colour: Red
 - Illuminated: Yes
 - Number of Positions: 2
 - Cutout Diameter: 22 mm
 - Switch Actuation: Latching
 - IP Rating: IP65
 - Angle of Throw: 30 °



1881158 Red

RS PRO 2 POSITION SELECTOR SWITCH HEAD, 22MM CUTOUT, RED

- ขนาดบรรจุภัณฑ์: 1 x EA
- Actuator Colour: Red
 - Illuminated: Yes
 - Number of Positions: 2
 - Cutout Diameter: 22 mm
 - Switch Actuation: Spring Return
 - IP Rating: IP65
 - Angle of Throw: 30 °



1881159 Red

RS PRO 2 POSITION SELECTOR SWITCH HEAD, 22MM CUTOUT, AMBER

- ขนาดบรรจุภัณฑ์: 1 x EA
- Actuator Colour: Amber
 - Illuminated: Yes
 - Number of Positions: 2
 - Cutout Diameter: 22 mm
 - Switch Actuation: Latching
 - IP Rating: IP65
 - Angle of Throw: 30 °



1881160 Amber

RS PRO 2 POSITION SELECTOR SWITCH HEAD, 22MM CUTOUT, AMBER

- ขนาดบรรจุภัณฑ์: 1 x EA
- Actuator Colour: Amber
 - Illuminated: Yes
 - Number of Positions: 2
 - Cutout Diameter: 22 mm
 - Switch Actuation: Spring Return
 - IP Rating: IP65
 - Angle of Throw: 30 °



1881161 Amber

RS PRO 3 POSITION SELECTOR SWITCH HEAD, 22MM CUTOUT, GREEN

- ขนาดบรรจุภัณฑ์: 1 x EA
- Actuator Colour: Green
 - Illuminated: Yes
 - Number of Positions: 3
 - Cutout Diameter: 22 mm
 - Switch Actuation: Spring Return
 - IP Rating: IP65
 - Angle of Throw: 30 °



1881163 Green

RS PRO 3 POSITION SELECTOR SWITCH HEAD, 22MM CUTOUT, GREEN

- ขนาดบรรจุภัณฑ์: 1 x EA
- Actuator Colour: Green
 - Illuminated: Yes
 - Number of Positions: 3
 - Cutout Diameter: 22 mm
 - Switch Actuation: Spring Return
 - IP Rating: IP65
 - Angle of Throw: 30 °



1881164 Green

RS PRO 686 SERIES MOMENTARY AIR SWITCH, SURFACE MOUNTED

- ขนาดบรรจุภัณฑ์: 1 x EA
- Manufacturer Series: 686
 - Type: Momentary
 - Mounting Type: Surface
 - Operation: NO/NC
 - For Use With: 3 mm I/D Tubing, Battery Charging Rooms, Garages or Wherever Explosive Gases, Laboratories, Vapours or Powders May Exist



316951 686

RS PRO 6871 SERIES MOMENTARY AIR SWITCH, 250MM FLY LEAD, SURFACE MOUNTED

- ขนาดบรรจุภัณฑ์: 1 x EA
- Manufacturer Series: 6871
 - Type: Momentary
 - Mounting Type: Surface
 - Operation: SPCO
 - Fly Lead Length: 250 mm
 - For Use With: 3 mm I/D Tubing, Battery Charging Rooms, Garages or Wherever Explosive Gases, Laboratories, Vapours or Powders May Exist



319708 6871

RS PRO 6871 SERIES LATCHING AIR SWITCH, 250MM FLY LEAD, SURFACE MOUNTED

- ขนาดบรรจุภัณฑ์: 1 x EA
- Manufacturer Series: 6871
 - Type: Latching
 - Mounting Type: Surface
 - Operation: SPCO
 - Fly Lead Length: 250 mm
 - For Use With: 3 mm I/D Tubing, Battery Charging Rooms, Garages or Wherever Explosive Gases, Laboratories, Vapours or Powders May Exist



319714 6871

RS PRO 6871 SERIES MOMENTARY AIR SWITCH, 250MM FLY LEAD, PANEL MOUNTED

- ขนาดบรรจุภัณฑ์: 1 x EA
- Manufacturer Series: 6871
 - Type: Momentary
 - Mounting Type: Panel
 - Operation: SPCO
 - Fly Lead Length: 250 mm
 - For Use With: 3 mm I/D Tubing, Battery Charging Rooms, Garages or Wherever Explosive Gases, Laboratories, Vapours or Powders May Exist



319720 6871

RS PRO 6871 SERIES LATCHING AIR SWITCH, 250MM FLY LEAD, PANEL MOUNTED

- ขนาดบรรจุภัณฑ์: 1 x EA
- Manufacturer Series: 6871
 - Type: Latching
 - Mounting Type: Panel
 - Operation: SPCO
 - Fly Lead Length: 250 mm
 - For Use With: 3 mm I/D Tubing, Battery Charging Rooms, Garages or Wherever Explosive Gases, Laboratories, Vapours or Powders May Exist



319736 6871

RS PRO 687 SERIES MOMENTARY AIR SWITCH, 250MM FLY LEAD, PANEL MOUNTED

- ขนาดบรรจุภัณฑ์: 1 x EA
- Manufacturer Series: 687
 - Type: Momentary
 - Mounting Type: Panel
 - Operation: NO/NC
 - Fly Lead Length: 250 mm
 - For Use With: 3 mm I/D Tubing, Battery Charging Rooms, Garages or Wherever Explosive Gases, Laboratories, Vapours or Powders May Exist



319742 687

RS PRO 687 SERIES LATCHING AIR SWITCH, PANEL MOUNTED

- ขนาดบรรจุภัณฑ์: 1 x EA
- Manufacturer Series: 687
 - Type: Latching
 - Mounting Type: Panel
 - Operation: NO/NC
 - For Use With: 3 mm I/D Tubing, Battery Charging Rooms, Garages or Wherever Explosive Gases, Laboratories, Vapours or Powders May Exist



319758 687

RS PRO RED PILOT LIGHT HEAD, 22.5MM CUTOUT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Cutout Diameter: 22.5 mm
 - Pilot Light Colour: Red
 - Pilot Light Shape: Round
 - Pilot Light Material: Plastic
 - IP Rating: IP65
 - Mounting Type: Panel Mount



1881201 22.5 mm

RS PRO BLUE PILOT LIGHT HEAD, 22.5MM CUTOUT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Cutout Diameter: 22.5 mm
 - Pilot Light Colour: Blue
 - Pilot Light Shape: Round
 - Pilot Light Material: Plastic
 - IP Rating: IP65
 - Mounting Type: Panel Mount



1881202 22.5 mm

RS PRO WHITE PILOT LIGHT HEAD, 22.5MM CUTOUT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Cutout Diameter: 22.5 mm
 - Pilot Light Colour: White
 - Pilot Light Shape: Round
 - Pilot Light Material: Plastic
 - IP Rating: IP65
 - Mounting Type: Panel Mount



1881203 22.5 mm

RS PRO YELLOW PILOT LIGHT HEAD, 22.5MM CUTOUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Cutout Diameter: 22.5 mm
 - Pilot Light Colour: Yellow
 - Pilot Light Shape: Round
 - Pilot Light Material: Plastic
 - IP Rating: IP65
 - Mounting Type: Panel Mount



1881205 22.5 mm

RS PRO GREEN PILOT LIGHT HEAD, 22.5MM CUTOUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Cutout Diameter: 22.5 mm
 - Pilot Light Colour: Green
 - Pilot Light Shape: Round
 - Pilot Light Material: Plastic
 - IP Rating: IP65
 - Mounting Type: Panel Mount



1881206 22.5 mm

RS PRO AMBER PILOT LIGHT HEAD, 22.5MM CUTOUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Cutout Diameter: 22.5 mm
 - Pilot Light Colour: Amber
 - Pilot Light Shape: Round
 - Pilot Light Material: Plastic
 - IP Rating: IP65
 - Mounting Type: Panel Mount



1881207 22.5 mm

RS PRO, PANEL MOUNT WHITE LED PILOT LIGHT, 22MM CUTOUT, IP65,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Pilot Light Type: Pilot Light Complete Unit
 - Voltage Rating: 24 V ac/dc
 - Pilot Light Colour: White
 - Cutout Diameter: 22 mm
 - Lamp Type: LED
 - Mounting Type: Panel Mount
 - IP Rating: IP65
 - Terminal Type: Screw



7637905 Pilot Light

RS PRO, PANEL MOUNT RED LED PILOT LIGHT, 22MM CUTOUT, IP65,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Pilot Light Type: Pilot Light Complete Unit
 - Voltage Rating: 24 V ac/dc
 - Pilot Light Colour: Red
 - Cutout Diameter: 22 mm
 - Lamp Type: LED
 - Mounting Type: Panel Mount
 - IP Rating: IP65
 - Terminal Type: Screw



7637909 Pilot Light

RS PRO, PANEL MOUNT BLUE LED PILOT LIGHT, 22MM CUTOUT, IP65,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Pilot Light Type: Pilot Light Complete Unit
 - Voltage Rating: 24 V ac/dc
 - Pilot Light Colour: Blue
 - Cutout Diameter: 22 mm
 - Lamp Type: LED
 - Mounting Type: Panel Mount
 - IP Rating: IP65
 - Terminal Type: Screw



7637911 Pilot Light

RS PRO, PANEL MOUNT AMBER LED PILOT LIGHT, 22MM CUTOUT, IP65,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Pilot Light Type: Pilot Light Complete Unit
 - Voltage Rating: 24 V ac/dc
 - Pilot Light Colour: Amber
 - Cutout Diameter: 22 mm
 - Lamp Type: LED
 - Mounting Type: Panel Mount
 - IP Rating: IP65
 - Terminal Type: Screw



7637915 Pilot Light

RS PRO, PANEL MOUNT GREEN LED PILOT LIGHT, 22MM CUTOUT, IP65,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Pilot Light Type: Pilot Light Complete Unit
 - Voltage Rating: 24 V ac/dc
 - Pilot Light Colour: Green
 - Cutout Diameter: 22 mm
 - Lamp Type: LED
 - Mounting Type: Panel Mount
 - IP Rating: IP65
 - Terminal Type: Screw



7637918 Pilot Light

RS PRO, PANEL MOUNT RED LED PILOT LIGHT, 22MM CUTOUT, IP65,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Pilot Light Type: Pilot Light Complete Unit
 - Voltage Rating: 12 V ac/dc
 - Pilot Light Colour: Red
 - Cutout Diameter: 22 mm
 - Lamp Type: LED
 - Mounting Type: Panel Mount
 - IP Rating: IP65
 - Terminal Type: Screw



7918573 Pilot Light

RS PRO, PANEL MOUNT WHITE LED PILOT LIGHT, 22MM CUTOUT, IP65,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Pilot Light Type: Pilot Light Complete Unit
 - Voltage Rating: 12 V ac/dc
 - Pilot Light Colour: White
 - Cutout Diameter: 22 mm
 - Lamp Type: LED
 - Mounting Type: Panel Mount
 - IP Rating: IP65
 - Terminal Type: Screw



7918579 Pilot Light

RS PRO, PANEL MOUNT GREEN LED PILOT LIGHT, 22MM CUTOUT, IP65,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Pilot Light Type: Pilot Light Complete Unit
 - Voltage Rating: 12 V ac/dc
 - Pilot Light Colour: Green
 - Cutout Diameter: 22 mm
 - Lamp Type: LED
 - Mounting Type: Panel Mount
 - IP Rating: IP65
 - Terminal Type: Screw



7918582 Pilot Light

RS PRO, PANEL MOUNT BLUE LED PILOT LIGHT, 22MM CUTOUT, IP65,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Pilot Light Type: Pilot Light Complete Unit
 - Voltage Rating: 12 V ac/dc
 - Pilot Light Colour: Blue
 - Cutout Diameter: 22 mm
 - Lamp Type: LED
 - Mounting Type: Panel Mount
 - IP Rating: IP65
 - Terminal Type: Screw



7918585 Pilot Light

RS PRO, PANEL MOUNT AMBER LED PILOT LIGHT, 22MM CUTOUT, IP65,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Pilot Light Type: Pilot Light Complete Unit
 - Voltage Rating: 12 V ac/dc
 - Pilot Light Colour: Amber
 - Cutout Diameter: 22 mm
 - Lamp Type: LED
 - Mounting Type: Panel Mount
 - IP Rating: IP65
 - Terminal Type: Screw



7918589 Pilot Light

RS PRO, PANEL MOUNT BLUE LED PILOT LIGHT COMPLETE, 16MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Pilot Light Type: Pilot Light Complete Unit
 - Voltage Rating: 12 V ac/dc
 - Pilot Light Colour: Blue
 - Cutout Diameter: 16 mm
 - Lamp Type: LED
 - Mounting Type: Panel Mount
 - IP Rating: IP40
 - Terminal Type: Screw



9092415 Pilot Light

RS PRO, PANEL MOUNT BLUE LED PILOT LIGHT COMPLETE, 16MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Pilot Light Type: Pilot Light Complete Unit
 - Voltage Rating: 24 V ac/dc
 - Pilot Light Colour: Blue
 - Cutout Diameter: 16 mm
 - Lamp Type: LED
 - Mounting Type: Panel Mount
 - IP Rating: IP40
 - Terminal Type: Screw



9092424 Pilot Light

RS PRO, PANEL MOUNT GREEN LED PILOT LIGHT COMPLETE, 16MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Pilot Light Type: Pilot Light Complete Unit
 - Voltage Rating: 12 V ac/dc
 - Pilot Light Colour: Green
 - Cutout Diameter: 16 mm
 - Lamp Type: LED
 - Mounting Type: Panel Mount
 - IP Rating: IP40
 - Terminal Type: Screw



9092430 Pilot Light

RS PRO, PANEL MOUNT RED LED PILOT LIGHT COMPLETE, 22MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Pilot Light Type: Pilot Light Complete Unit
 - Voltage Rating: 12 V ac/dc
 - Pilot Light Colour: Red
 - Cutout Diameter: 22 mm
 - Lamp Type: LED
 - Mounting Type: Panel Mount
 - IP Rating: IP30
 - Terminal Type: Screw



9092553 Pilot Light

LED INDICATOR WITH SOUNDER 22MM RED 24V

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Pilot Light Type: Pilot Light Complete Unit
 - Voltage Rating: 24 V ac/dc
 - Pilot Light Colour: Red
 - Cutout Diameter: 22 mm
 - Lamp Type: LED
 - Mounting Type: Panel Mount
 - IP Rating: IP30
 - Terminal Type: Screw



9092556 Pilot Light

RS PRO 6419 SERIES BANJO THREADED-TO-TUBE ADAPTOR, G 1/8

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Manufacturer Series: 6419
 - Pneumatic Fitting Type: Banjo Threaded-to-Tube Adaptor
 - Connection Style: Threaded-to-Tube
 - Connector A: G 1/8 Male
 - Connector B: Push In 3 mm
 - Threaded Connection: 1/8 in Male BSP
 - Body Material: Nylon
 - Minimum Operating Temperature: -10 °C



317752 6419

RS PRO 6401 SERIES TEE TUBE-TO-TUBE ADAPTOR, PUSH IN 3 MM TO

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Manufacturer Series: 6401
 - Pneumatic Fitting Type: Tee Tube-to-Tube Adaptor
 - Connection Style: Tube-to-Tube
 - Connector A: Push In 3 mm
 - Connector B: Push In 3 mm
 - Body Material: Nylon
 - Minimum Operating Temperature: -10 °C
 - Maximum Operating Temperature: +60 °C



317768 6401

RS PRO BLUE ROUND NO PUSH BUTTON HEAD, SPRING RETURN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Cutout Diameter: 22 mm
 - Push Button Colour: Blue
 - Push Button Actuation: Spring Return
 - Push Button Style: Round
 - Push Button Material: Plastic
 - IP Rating: IP65
 - Push Button Diameter: 30.2 mm
 - Illuminated: No



1881122 22 mm

RS PRO RED ROUND NO PUSH BUTTON HEAD, SPRING RETURN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Cutout Diameter: 22 mm
 - Push Button Colour: Red
 - Push Button Actuation: Spring Return
 - Push Button Style: Round
 - Push Button Material: Plastic
 - IP Rating: IP65
 - Push Button Diameter: 30.2 mm
 - Illuminated: No



1881123 22 mm

RS PRO GREEN ROUND NO PUSH BUTTON HEAD, SPRING RETURN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Cutout Diameter: 22 mm
 - Push Button Colour: Green
 - Push Button Actuation: Spring Return
 - Push Button Style: Round
 - Push Button Material: Plastic
 - IP Rating: IP65
 - Push Button Diameter: 30.2 mm
 - Illuminated: No



1881124 22 mm

RS PRO YELLOW ROUND NO PUSH BUTTON HEAD, SPRING RETURN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Cutout Diameter: 22 mm
 - Push Button Colour: Yellow
 - Push Button Actuation: Spring Return
 - Push Button Style: Round
 - Push Button Material: Plastic
 - IP Rating: IP65
 - Push Button Diameter: 30.2 mm
 - Illuminated: No



1881126 22 mm

RS PRO BLACK ROUND NO PUSH BUTTON HEAD, SPRING RETURN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Cutout Diameter: 22 mm
 - Push Button Colour: Black
 - Push Button Actuation: Spring Return
 - Push Button Style: Round
 - Push Button Material: Plastic
 - IP Rating: IP65
 - Push Button Diameter: 30.2 mm
 - Illuminated: No



1881127 22 mm

RS PRO WHITE ROUND NO PUSH BUTTON HEAD, SPRING RETURN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Cutout Diameter: 22 mm
 - Push Button Colour: White
 - Push Button Actuation: Spring Return
 - Push Button Style: Round
 - Push Button Material: Plastic
 - IP Rating: IP65
 - Push Button Diameter: 30.2 mm
 - Illuminated: No



1881128 22 mm

RS PRO RED ROUND NO PUSH BUTTON HEAD, SPRING RETURN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Cutout Diameter: 22 mm
 - Push Button Colour: Red
 - Push Button Actuation: Spring Return
 - Push Button Style: Round
 - Push Button Material: Plastic
 - IP Rating: IP65
 - Push Button Diameter: 30.2 mm
 - Illuminated: No



1881129 22 mm

RS PRO RED ROUND NO PUSH BUTTON HEAD, SPRING RETURN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Cutout Diameter: 22 mm
 - Push Button Colour: Red
 - Push Button Actuation: Spring Return
 - Push Button Style: Round
 - Push Button Material: Plastic
 - IP Rating: IP65
 - Push Button Diameter: 30.2 mm
 - Illuminated: No



1881132 22 mm

RS PRO GREEN ROUND NO PUSH BUTTON HEAD, SPRING RETURN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Cutout Diameter: 22 mm
 - Push Button Colour: Green
 - Push Button Actuation: Spring Return
 - Push Button Style: Round
 - Push Button Material: Plastic
 - IP Rating: IP65
 - Push Button Diameter: 30.2 mm
 - Illuminated: No



1881133 22 mm

RS PRO RED ROUND NO PUSH BUTTON HEAD, SPRING RETURN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Cutout Diameter: 22 mm
 - Push Button Colour: Red
 - Push Button Actuation: Spring Return
 - Push Button Style: Round
 - Push Button Material: Plastic
 - IP Rating: IP65
 - Push Button Diameter: 30.2 mm
 - Illuminated: No



1881134 22 mm

RS PRO BLUE ROUND NO PUSH BUTTON HEAD, SPRING RETURN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Cutout Diameter: 22 mm
 - Push Button Colour: Blue
 - Push Button Actuation: Spring Return
 - Push Button Style: Round
 - Push Button Material: Plastic
 - IP Rating: IP65
 - Push Button Diameter: 30.2 mm
 - Illuminated: No



1881137 22 mm

RS PRO BLACK ROUND NO PUSH BUTTON HEAD, SPRING RETURN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Cutout Diameter: 22 mm
 - Push Button Colour: Black
 - Push Button Actuation: Spring Return
 - Push Button Style: Round
 - Push Button Material: Plastic
 - IP Rating: IP65
 - Push Button Diameter: 30.2 mm
 - Illuminated: No



1881138 22 mm

RS PRO BLACK ROUND NO PUSH BUTTON HEAD, SPRING RETURN

ขนาดบรรจุภัณฑ์: 1 x EA

- Cutout Diameter: 22 mm
- Push Button Colour: Black
- Push Button Actuation: Spring Return
- Push Button Style: Round
- Push Button Material: Plastic
- IP Rating: IP65
- Push Button Diameter: 30.2 mm
- Illuminated: No



1881139 22 mm

RS PRO GREEN ROUND NO PUSH BUTTON HEAD, SPRING RETURN

ขนาดบรรจุภัณฑ์: 1 x EA

- Cutout Diameter: 22 mm
- Push Button Colour: Green
- Push Button Actuation: Spring Return
- Push Button Style: Round
- Push Button Material: Plastic
- IP Rating: IP65
- Push Button Diameter: 30.2 mm
- Illuminated: No



1881140 22 mm

RS PRO BLUE ROUND NO PUSH BUTTON HEAD, SPRING RETURN

ขนาดบรรจุภัณฑ์: 1 x EA

- Cutout Diameter: 22 mm
- Push Button Colour: Blue
- Push Button Actuation: Spring Return
- Push Button Style: Round
- Push Button Material: Plastic
- IP Rating: IP65
- Push Button Diameter: 30.2 mm
- Illuminated: No



1881141 22 mm

RS PRO RED ROUND NO PUSH BUTTON HEAD, SPRING RETURN

ขนาดบรรจุภัณฑ์: 1 x EA

- Cutout Diameter: 22 mm
- Push Button Colour: Red
- Push Button Actuation: Spring Return
- Push Button Style: Round
- Push Button Material: Plastic
- IP Rating: IP65
- Push Button Diameter: 30.2 mm
- Illuminated: No



1881142 22 mm

RS PRO GREEN ROUND NO PUSH BUTTON HEAD, SPRING RETURN

ขนาดบรรจุภัณฑ์: 1 x EA

- Cutout Diameter: 22 mm
- Push Button Colour: Green
- Push Button Actuation: Spring Return
- Push Button Style: Round
- Push Button Material: Plastic
- IP Rating: IP65
- Push Button Diameter: 30.2 mm
- Illuminated: No



1881143 22 mm

RS PRO YELLOW ROUND NO PUSH BUTTON HEAD, SPRING RETURN

ขนาดบรรจุภัณฑ์: 1 x EA

- Cutout Diameter: 22 mm
- Push Button Colour: Yellow
- Push Button Actuation: Spring Return
- Push Button Style: Round
- Push Button Material: Plastic
- IP Rating: IP65
- Push Button Diameter: 30.2 mm
- Illuminated: No



1881144 22 mm

RS PRO WHITE ROUND NO PUSH BUTTON HEAD, SPRING RETURN

ขนาดบรรจุภัณฑ์: 1 x EA

- Cutout Diameter: 22 mm
- Push Button Colour: White
- Push Button Actuation: Spring Return
- Push Button Style: Round
- Push Button Material: Plastic
- IP Rating: IP65
- Push Button Diameter: 30.2 mm
- Illuminated: No



1881145 22 mm

RS PRO GREEN, RED NO PUSH BUTTON HEAD, SPRING RETURN

ขนาดบรรจุภัณฑ์: 1 x EA

- Cutout Diameter: 22 mm
- Push Button Colour: Green, Red
- Push Button Actuation: Spring Return
- Push Button Material: Plastic
- IP Rating: IP65
- Illuminated: No



1881199 22 mm

RS PRO GREEN, RED NO PUSH BUTTON HEAD, SPRING RETURN

ขนาดบรรจุภัณฑ์: 1 x EA

- Cutout Diameter: 22 mm
- Push Button Colour: Green, Red
- Push Button Actuation: Spring Return
- Push Button Material: Plastic
- IP Rating: IP65
- Illuminated: No



1881200 22 mm

RS PRO BLUE ROUND NO PUSH BUTTON HEAD, MOMENTARY

ขนาดบรรจุภัณฑ์: 1 x EA

- Series: RCAS
- Cutout Diameter: 22 mm
- Push Button Colour: Blue
- Push Button Actuation: Momentary
- Push Button Style: Round
- Push Button Material: Metal
- IP Rating: IP65
- Illuminated: No



2052353 RCAS

RS PRO RED ROUND NO PUSH BUTTON HEAD, MOMENTARY

ขนาดบรรจุภัณฑ์: 1 x EA

- Series: RCAS
- Cutout Diameter: 22 mm
- Push Button Colour: Red
- Push Button Actuation: Momentary
- Push Button Style: Round
- Push Button Material: Metal
- IP Rating: IP65
- Illuminated: No



2052354 RCAS

RS PRO GREEN ROUND NO PUSH BUTTON HEAD, MOMENTARY

ขนาดบรรจุภัณฑ์: 1 x EA

- Series: RCAS
- Cutout Diameter: 22 mm
- Push Button Colour: Green
- Push Button Actuation: Momentary
- Push Button Style: Round
- Push Button Material: Metal
- IP Rating: IP65
- Illuminated: No



2052355 RCAS

RS PRO BLACK ROUND NO PUSH BUTTON HEAD, MOMENTARY

ขนาดบรรจุภัณฑ์: 1 x EA

- Series: RCAS
- Cutout Diameter: 22 mm
- Push Button Colour: Black
- Push Button Actuation: Momentary
- Push Button Style: Round
- Push Button Material: Metal
- IP Rating: IP65
- Illuminated: No



2052358 RCAS

RS PRO WHITE ROUND NO PUSH BUTTON HEAD, MOMENTARY

ขนาดบรรจุภัณฑ์: 1 x EA

- Series: RCAS
- Cutout Diameter: 22 mm
- Push Button Colour: White
- Push Button Actuation: Momentary
- Push Button Style: Round
- Push Button Material: Metal
- IP Rating: IP65
- Illuminated: No



2052359 RCAS

RS PRO RED ROUND NO PUSH BUTTON HEAD, MOMENTARY

ขนาดบรรจุภัณฑ์: 1 x EA

- Series: RCAS
- Cutout Diameter: 22 mm
- Push Button Colour: Red
- Push Button Actuation: Momentary
- Push Button Style: Round
- Push Button Material: Metal
- IP Rating: IP65
- Illuminated: No



2052360 RCAS

RS PRO GREEN ROUND NO PUSH BUTTON HEAD, MOMENTARY

ขนาดบรรจุภัณฑ์: 1 x EA

- Series: RCAS
- Cutout Diameter: 22 mm
- Push Button Colour: Green
- Push Button Actuation: Momentary
- Push Button Style: Round
- Push Button Material: Metal
- IP Rating: IP65
- Illuminated: No



2052361 RCAS

RS PRO GREEN ROUND NO PUSH BUTTON HEAD, MOMENTARY

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Series: RCAS
 - Cutout Diameter: 22 mm
 - Push Button Colour: Green
 - Push Button Actuation: Momentary
 - Push Button Style: Round
 - Push Button Material: Metal
 - IP Rating: IP65
 - Illuminated: No



2052363 RCAS

RS PRO RED ROUND NO PUSH BUTTON HEAD, MOMENTARY

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Series: RCAS
 - Cutout Diameter: 22 mm
 - Push Button Colour: Red
 - Push Button Actuation: Momentary
 - Push Button Style: Round
 - Push Button Material: Metal
 - IP Rating: IP65
 - Illuminated: No



2052366 RCAS

RS PRO LOCKING RING WRENCH

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Lock Ring Hand Tool
 - For Use With: 22 mm LEDtec Indicator, 22 mm LEDtec Push Button



1753953 Lock Ring Hand

RS PRO LEGEND PLATE FOR USE WITH PTEC PUSH BUTTON

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Accessory Type: Legend Plate
 - For Use With: Ptec Push Button



1753954 Legend Plate

RS PRO LEGEND PLATE FOR USE WITH PTEC PUSH BUTTON

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Accessory Type: Legend Plate
 - For Use With: Ptec Push Button



1753955 Legend Plate

RS PRO LEGEND PLATE FOR USE WITH PTEC PUSH BUTTON

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Accessory Type: Legend Plate
 - For Use With: Ptec Push Button



1753956 Legend Plate

RS PRO LEGEND PLATE FOR USE WITH PTEC PUSH BUTTON

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Accessory Type: Legend Plate
 - For Use With: Ptec Push Button



1753958 Legend Plate

RS PRO LEGEND PLATE FOR USE WITH PTEC PUSH BUTTON

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Accessory Type: Legend Plate
 - For Use With: Ptec Push Button



1753959 Legend Plate

RS PRO LEGEND PLATE FOR USE WITH PTEC PUSH BUTTON

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Accessory Type: Legend Plate
 - For Use With: Ptec Push Button



1753960 Legend Plate

RS PRO LEGEND PLATE FOR USE WITH PTEC PUSH BUTTON

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Accessory Type: Legend Plate
 - For Use With: Ptec Push Button



1753961 Legend Plate

RS PRO LEGEND PLATE FOR USE WITH PTEC PUSH BUTTON

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Accessory Type: Legend Plate
 - For Use With: Ptec Push Button



1753962 Legend Plate

RS PRO LEGEND PLATE FOR USE WITH PTEC PUSH BUTTON

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Accessory Type: Legend Plate
 - For Use With: Ptec Push Button



1753964 Legend Plate

RS PRO LEGEND PLATE FOR USE WITH PTEC PUSH BUTTON

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Accessory Type: Legend Plate
 - For Use With: Ptec Push Button



1753965 Legend Plate

RS PRO LEGEND PLATE FOR USE WITH PTEC PUSH BUTTON

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Accessory Type: Legend Plate
 - For Use With: Ptec Push Button



1753966 Legend Plate

RS PRO LEGEND PLATE FOR USE WITH PTEC PUSH BUTTON

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Accessory Type: Legend Plate
 - For Use With: Ptec Push Button



1753967 Legend Plate

RS PRO BELLOW

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Manufacturer Series: 6438
 - Type: Bellows
 - Colour: White
 - Nominal Diameter: 50 mm
 - Length: 42.5 mm



1900434 6438

RS PRO BELLOW

- ขนาดบรรจุภัณฑ์: 1 x EA
- Manufacturer Series: 6438
 - Type: Bellows
 - Colour: Red
 - Nominal Diameter: 50 mm
 - Length: 42.5 mm



1900440 6438

RS PRO BELLOW

- ขนาดบรรจุภัณฑ์: 1 x EA
- Manufacturer Series: 6438
 - Type: Bellows
 - Colour: Green
 - Nominal Diameter: 50 mm
 - Length: 42.5 mm



1900456 6438

RS PRO BELLOW

- ขนาดบรรจุภัณฑ์: 1 x EA
- Manufacturer Series: 6438
 - Type: Bellows
 - Colour: Black
 - Nominal Diameter: 50 mm
 - Length: 42.5 mm



1900478 6438

RS PRO PUSH BUTTON SWITCH

- ขนาดบรรจุภัณฑ์: 1 x EA
- Manufacturer Series: 6442
 - Type: Push Button
 - Air Connection: 4 mm
 - Colour: Chrome
 - Nominal Diameter: 42 → 45 mm



8370975 6442

RS PRO GASKET, FOR USE WITH PANEL AND DOOR ISOLATOR

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Gasket
 - For Use With: Panel and Door Isolator
 - IP Rating: IP65



7737995 Gasket

RS PRO AIR SWITCH ACTUATOR

- ขนาดบรรจุภัณฑ์: 1 x EA
- Manufacturer Series: 6470



317055 6470

RS PRO AIR SWITCH ACTUATOR

- ขนาดบรรจุภัณฑ์: 1 x EA
- Manufacturer Series: 6442



317730 6442

RS PRO BRAIDED WIRE 90 A, 24 X 12 X 0.20 MM, 25M BS4109

- ขนาดบรรจุภัณฑ์: **25 x MTR**
- Size: 24 x 12 x 0.20 mm
 - Conductor Material: Tinned Copper
 - Cross Sectional Area: 9.05 mm²
 - Current Rating: 90 A
 - Length: 25 m
 - Conductor Resistance: 1.91 Ω/km
 - Cable Shape: Single Core
 - Standards Met: BS4109



365559 24 x 12 x 0.20 mm

WIRE,BRAID,COPPER,FLAT,TINNED,1.9X0.6MM,25M,10A

- ขนาดบรรจุภัณฑ์: **25 x MTR**
- Size: 1.9 x 0.6 mm
 - Conductor Material: Tinned Copper
 - Cross Sectional Area: 0.5 mm²
 - Current Rating: 10 A
 - Length: 25 m
 - Conductor Resistance: 35 Ω/km
 - Cable Shape: Single Core
 - Standards Met: BS4109



358006 1.9 x 0.6 mm

WIRE,BRAID,COPPER,FLAT,TINNED,5X0.7MM,25M,30A

- ขนาดบรรจุภัณฑ์: **25 x MTR**
- Size: 4 x 0.8 mm
 - Conductor Material: Tinned Copper
 - Cross Sectional Area: 1.7 mm²
 - Current Rating: 30 A
 - Length: 25 m
 - Conductor Resistance: 10.44 Ω/km
 - Cable Shape: Single Core
 - Standards Met: BS4109



358012 4 x 0.8 mm

WIRE,BRAID,COPPER,FLAT,TINNED,10X2MM,25M,63A

- ขนาดบรรจุภัณฑ์: **25 x MTR**
- Size: 10 x 2 mm
 - Conductor Material: Tinned Copper
 - Cross Sectional Area: 7.5 mm²
 - Current Rating: 63 A
 - Length: 25 m
 - Conductor Resistance: 2.349 Ω/km
 - Cable Shape: Single Core
 - Standards Met: BS4109



365543 10 x 2 mm

EARTH,STRAP,ASSEMBLY,25MM,CSA BRAID,M8,500MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Size: 3 x 2 x 16 x 0.2 mm
 - Conductor Material: Tinned Copper
 - Cross Sectional Area: 36.19 mm²
 - Length: 0.5 m
 - Conductor Resistance: 0.481 Ω/km
 - Stud Size: M8
 - Cable Shape: Single Core
 - Standards Met: BS EN 13602:2002, BS4109



489153 3 x 2 x 16 x 0.2

EARTH,STRAP,ASSEMBLY,25MM,CSA BRAID,M8,400MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Size: 2 x 24 x 16 x 0.2 mm
 - Conductor Material: Tinned Copper
 - Cross Sectional Area: 24.13 mm²
 - Length: 0.4 m
 - Conductor Resistance: 734 Ω/km
 - Stud Size: M8
 - Cable Shape: Single Core
 - Standards Met: BS EN 13602:2002, BS4109



489157 2 x 24 x 16 x 0.2

EARTH,STRAP,ASSEMBLY,15MM,CSA BRAID,M6,250MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Size: 24 x 20 x 0.2 mm
 - Conductor Material: Tinned Copper
 - Cross Sectional Area: 15.08 mm²
 - Length: 0.25 m
 - Conductor Resistance: 1174 Ω/km
 - Stud Size: M6
 - Cable Shape: Single Core
 - Standards Met: BS EN 13602:2002, BS4109



489163 24 x 20 x 0.2 mm

EARTH,STRAP,ASSEMBLY,15MM,CSA BRAID,M6,150MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Size: 24 x 20 x 0.2 mm
 - Conductor Material: Tinned Copper
 - Cross Sectional Area: 15.08 mm²
 - Length: 0.4 m
 - Conductor Resistance: 1174 Ω/km
 - Stud Size: M6
 - Cable Shape: Single Core
 - Standards Met: BS EN 13602:2002, BS4109



489169 24 x 20 x 0.2 mm

EARTH,STRAP,ASSEMBLY,1.13MM,CSA BRAID,M3.5,100MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Size: 16 x 4 x 0.15 mm
 - Conductor Material: Tinned Copper
 - Cross Sectional Area: 1.13 mm²
 - Length: 0.1 m
 - Conductor Resistance: 15.41 Ω/km
 - Stud Size: M3.5
 - Cable Shape: Single Core
 - Standards Met: BS EN 13602:2002, BS4109



489179 16 x 4 x 0.15 mm

EARTH,STRAP,ASSEMBLY,2.26MM,CSA BRAID,M8,200MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Size: 16 x 8 x 0.15 mm
 - Conductor Material: Tinned Copper
 - Cross Sectional Area: 2.26 mm²
 - Length: 0.2 m
 - Conductor Resistance: 7830 Ω/km
 - Stud Size: M8
 - Cable Shape: Single Core
 - Standards Met: BS EN 13602:2002, BS4109



489185 16 x 8 x 0.15 mm

EARTH,STRAP,ASSEMBLY,10MM,CSA BRAID,M5,100MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Size: 16 x 20 x 0.2 mm
 - Conductor Material: Tinned Copper
 - Cross Sectional Area: 10.05 mm²
 - Length: 0.1 m
 - Conductor Resistance: 1762 Ω/km
 - Stud Size: M5
 - Cable Shape: Single Core
 - Standards Met: BS EN 13602:2002, BS4109



489197 16 x 20 x 0.2 mm

EARTH,STRAP,ASSEMBLY,8.29MM,CSA BRAID,M5,150MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Size: 24 x 11 x 0.2 mm
 - Conductor Material: Tinned Copper
 - Cross Sectional Area: 8.29 mm²
 - Length: 0.15 m
 - Conductor Resistance: 2.1 Ω/km
 - Stud Size: M5
 - Cable Shape: Single Core
 - Standards Met: BS EN 13602:2002, BS4109



489204 24 x 11 x 0.2 mm

EARTH,STRAP,ASSEMBLY,10MM,CSA BRAID,M5,150MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Size: 16 x 20 x 0.2 mm
 - Conductor Material: Tinned Copper
 - Cross Sectional Area: 10.05 mm²
 - Length: 0.15 m
 - Conductor Resistance: 1762 Ω/km
 - Stud Size: M5
 - Cable Shape: Single Core
 - Standards Met: BS EN 13602:2002, BS4109



489208 16 x 20 x 0.2 mm

EARTH,STRAP,ASSEMBLY,15MM,CSA BRAID,M6,150MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Size: 24 x 20 x 0.2 mm
 - Conductor Material: Tinned Copper
 - Cross Sectional Area: 10.05 mm²
 - Length: 0.15 m
 - Conductor Resistance: 1762 Ω/km
 - Stud Size: M6
 - Cable Shape: Single Core
 - Standards Met: BS EN 13602:2002, BS4109



489210 24 x 20 x 0.2 mm

EARTH,STRAP,ASSEMBLY,10MM,CSA BRAID,M5,200MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Size: 16 x 20 x 0.2 mm
 - Conductor Material: Tinned Copper
 - Cross Sectional Area: 10.05 mm²
 - Length: 0.2 m
 - Conductor Resistance: 1762 Ω/km
 - Stud Size: M5
 - Cable Shape: Single Core
 - Standards Met: BS EN 13602:2002, BS4109



489214 16 x 20 x 0.2 mm

RS PRO BRAIDED WIRE, M5 STUD SIZE, DIA 0.2 MM, 0.2M BS EN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Size: Dia 0.2 mm
 - Conductor Material: Tinned Copper
 - Length: 0.2 m
 - Conductor Resistance: 2349 Ω/km
 - Stud Size: M5
 - Cable Shape: Earth Lead
 - Standards Met: BS EN 13602:2002, BS4109



489191 Dia 0.2 mm

RS PRO DIN RAIL MOUNT INTERFACE RELAY, 12V AC/DC COIL, 6A LOAD

- ขนาดบรรจุภัณฑ์: 1 x EA
- Coil Voltage: 12 V ac/dc
 - Contact Configuration: SPDT
 - Mounting Type: DIN Rail
 - Load Current Rating: 6 A
 - Length: 96 mm
 - Depth: 6.2 mm
 - Height: 78.8 mm
 - Input Current: 8 A



1441578 12 V ac/dc

RS PRO DIN RAIL MOUNT INTERFACE RELAY, 24V AC/DC COIL, 6A LOAD

- ขนาดบรรจุภัณฑ์: 1 x EA
- Coil Voltage: 24 V ac/dc
 - Maximum Input Voltage: 24 V dc
 - Contact Configuration: SPDT
 - Mounting Type: DIN Rail
 - Load Current Rating: 6 A
 - Length: 96 mm
 - Depth: 6.2 mm
 - Height: 78.8 mm



1441579 24 V ac/dc

RS PRO DIN RAIL MOUNT INTERFACE RELAY, 48V AC/DC COIL, 6A LOAD

- ขนาดบรรจุภัณฑ์: 1 x EA
- Coil Voltage: 48 V ac/dc
 - Maximum Input Voltage: 48 V dc
 - Contact Configuration: SPDT
 - Mounting Type: DIN Rail
 - Load Current Rating: 6 A
 - Length: 96 mm
 - Depth: 6.2 mm
 - Height: 78.8 mm



1441580 48 V ac/dc

RS PRO DIN RAIL MOUNT INTERFACE RELAY, 12V AC/DC COIL, SPDT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Coil Voltage: 12 V ac/dc
 - Contact Configuration: SPDT
 - Mounting Type: DIN Rail
 - Length: 96 mm
 - Depth: 6.2 mm
 - Height: 103 mm
 - Input Current: 8 A
 - Minimum Operating Temperature: -40 °C



1441584 12 V ac/dc

RS PRO DIN RAIL MOUNT INTERFACE RELAY, 24V DC COIL, SPDT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Coil Voltage: 24 V dc
 - Contact Configuration: SPDT
 - Mounting Type: DIN Rail
 - Length: 96 mm
 - Depth: 6.2 mm
 - Height: 103 mm
 - Input Current: 8 A
 - Minimum Operating Temperature: -40 °C



1441585 24 V dc

RS PRO DIN RAIL MOUNT INTERFACE RELAY, 48V AC/DC COIL, SPDT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Coil Voltage: 48 V ac/dc
 - Contact Configuration: SPDT
 - Mounting Type: DIN Rail
 - Length: 96 mm
 - Depth: 6.2 mm
 - Height: 103 mm
 - Input Current: 8 A
 - Minimum Operating Temperature: -40 °C



1441586 48 V ac/dc

RS PRO DIN RAIL MOUNT INTERFACE RELAY, 24V DC COIL, SPDT

- ขนาดบรรจุภัณฑ์: 5 x EA
- Coil Voltage: 24 V dc
 - Contact Configuration: SPDT
 - Mounting Type: DIN Rail
 - Terminal Type: Screw
 - Length: 6.2 mm
 - Depth: 73 mm
 - Height: 93 mm
 - Contact Material: Silver Alloy



8886792 24 V dc

RS PRO DIN RAIL MOUNT INTERFACE RELAY, 24V DC COIL, SPDT

- ขนาดบรรจุภัณฑ์: 5 x EA
- Coil Voltage: 24 V dc
 - Contact Configuration: SPDT
 - Mounting Type: DIN Rail
 - Terminal Type: Screw
 - Length: 6.2 mm
 - Depth: 86 mm
 - Height: 78 mm
 - Contact Material: Silver Alloy



8886798 24 V dc

RS PRO DIN RAIL MOUNT INTERFACE RELAY, 24V DC COIL, SPDT

- ขนาดบรรจุภัณฑ์: 5 x EA
- Minimum Input Voltage: 19.2 V
 - Coil Voltage: 24 V dc
 - Maximum Input Voltage: 30 V
 - Contact Configuration: SPDT
 - Mounting Type: DIN Rail
 - Switching Voltage: 17 → 250 V
 - Terminal Type: Screw
 - Length: 6.2 mm



8886802 19.2 V

RS PRO DIN RAIL MOUNT INTERFACE RELAY, 24V DC COIL, SPDT

- ขนาดบรรจุภัณฑ์: 5 x EA
- Coil Voltage: 24 V dc
 - Minimum Input Voltage: 19.2 V
 - Maximum Input Voltage: 30 V
 - Contact Configuration: SPDT
 - Mounting Type: DIN Rail
 - Switching Voltage: 1 → 250 V
 - Terminal Type: Screw
 - Length: 6.2 mm



8886805 24 V dc

RS PRO DIN RAIL MOUNT INTERFACE RELAY, 24V AC/DC COIL, SPDT

- ขนาดบรรจุภัณฑ์: 5 x EA
- Coil Voltage: 24 V ac/dc
 - Contact Configuration: SPDT
 - Mounting Type: DIN Rail
 - Terminal Type: Screw
 - Length: 6.2 mm
 - Depth: 73 mm
 - Height: 93 mm
 - Contact Material: Silver Alloy



8886809 24 V ac/dc

RS PRO DIN RAIL MOUNT INTERFACE RELAY, 24V AC/DC COIL, SPDT

- ขนาดบรรจุภัณฑ์: 5 x EA
- Coil Voltage: 24 V ac/dc
 - Minimum Input Voltage: 19.2 V
 - Maximum Input Voltage: 30 V
 - Contact Configuration: SPDT
 - Mounting Type: DIN Rail
 - Switching Voltage: 17 → 250 V
 - Terminal Type: Screw
 - Length: 6.2 mm



8886811 24 V ac/dc

RS PRO DIN RAIL MOUNT INTERFACE RELAY, 24V AC/DC COIL, SPDT

- ขนาดบรรจุภัณฑ์: 5 x EA
- Coil Voltage: 24 V ac/dc
 - Minimum Input Voltage: 19.2 V
 - Maximum Input Voltage: 30 V
 - Contact Configuration: SPDT
 - Mounting Type: DIN Rail
 - Switching Voltage: 1 → 250 V
 - Terminal Type: Screw
 - Length: 6.2 mm



8886815 24 V ac/dc

RS PRO DIN RAIL MOUNT INTERFACE RELAY, 24V AC/DC COIL, SPDT

- ขนาดบรรจุภัณฑ์: 5 x EA
- Coil Voltage: 24 V ac/dc
 - Contact Configuration: SPDT
 - Mounting Type: DIN Rail
 - Terminal Type: Screw
 - Length: 6.2 mm
 - Depth: 73 mm
 - Height: 93 mm
 - Contact Material: Silver Alloy



8886818 24 V ac/dc

RS PRO DIN RAIL MOUNT INTERFACE RELAY, 24V DC COIL, SPDT

- ขนาดบรรจุภัณฑ์: 5 x EA
- Coil Voltage: 24 V dc
 - Contact Configuration: SPDT
 - Mounting Type: DIN Rail
 - Switching Voltage: 250 V ac/dc
 - Terminal Type: Push In
 - Length: 6.2 mm
 - Depth: 76 mm
 - Series: LCIS



8886871 24 V dc

RS PRO DIN RAIL MOUNT INTERFACE RELAY, 24V DC COIL, SPDT

- ขนาดบรรจุภัณฑ์: 5 x EA
- Coil Voltage: 24 V dc
 - Contact Configuration: SPDT
 - Mounting Type: DIN Rail
 - Terminal Type: Push In
 - Length: 6.2 mm
 - Depth: 73 mm
 - Height: 93 mm
 - Contact Material: Silver Alloy



8886874 24 V dc

RS PRO DIN RAIL MOUNT INTERFACE RELAY, 24V DC COIL, SPDT

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Coil Voltage: 24 V dc
 - Contact Configuration: SPDT
 - Mounting Type: DIN Rail
 - Switching Voltage: 250 V ac/dc
 - Terminal Type: Push In
 - Length: 6.2 mm
 - Series: LCIS
 - Depth: 76 mm



8886877 24 V dc

PUSH 6.2MM RLY 24VAC/DC 1 C/O 6A 250VAC

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Coil Voltage: 24 V ac/dc
 - Contact Configuration: SPDT
 - Mounting Type: DIN Rail
 - Terminal Type: Push In
 - Length: 6.2 mm
 - Depth: 73 mm
 - Height: 93 mm
 - Contact Material: Silver Alloy



8886880 24 V ac/dc

RS PRO DIN RAIL MOUNT INTERFACE RELAY, 24V AC/DC COIL, SPDT

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Coil Voltage: 24 V ac/dc
 - Contact Configuration: SPDT
 - Mounting Type: DIN Rail
 - Switching Voltage: 250 V ac/dc
 - Terminal Type: Push In
 - Length: 6.2 mm
 - Depth: 76 mm
 - Series: LCIS



8886896 24 V ac/dc

INTERFACE RELAY MODULE BUSBAR FOR USE WITH INTERFACE RELAY

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Jumper Bar
 - For Use With: Interface Relay



1441590 Jumper Bar

RELAY JUMPER BAR

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Maximum Load Current: 6 A
 - Terminal Type: Plug In
 - Number of Poles: 8
 - Operating Temperature Range: -40 → +80 °C
 - Standards Met: RoHS Compliant
 - Length: 70 mm



8886944 6 A

RELAY JUMPER BAR

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Maximum Load Current: 6 A
 - Terminal Type: Plug In
 - Number of Poles: 16
 - Operating Temperature Range: -40 → +80 °C
 - Standards Met: RoHS Compliant
 - Length: 79 mm



8886953 6 A

RS PRO JUMPER MALE STRAIGHT BEIGE JUMPER LINK 2 WAY 1 ROW

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Type: Jumper Link
 - Number of Contacts: 2
 - Pitch: 6.1 mm
 - Gender: Male
 - Colour: Beige
 - Number of Rows: 1
 - Width: 6.1 mm
 - Series: RS Pro



2125490 Jumper Link

RS PRO JUMPER MALE STRAIGHT BEIGE JUMPER LINK 10 WAY 1 ROW

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Type: Jumper Link
 - Number of Contacts: 10
 - Pitch: 6.1 mm
 - Gender: Male
 - Colour: Beige
 - Number of Rows: 1
 - Width: 60.4 mm
 - Series: RS Pro



2125491 Jumper Link

RS PRO LINEAR SOLENOID, 24 V DC, 26 X 16 X 20 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Action: Pull
 - Supply Voltage: 24 V dc
 - Dimensions: 26 x 16 x 20 mm



1770113 Pull

RS PRO LINEAR SOLENOID, 24 V DC, 29.35 X 15.9 X 19.1 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Action: Push
 - Supply Voltage: 24 V dc
 - Dimensions: 29.35 x 15.9 x 19.1 mm



1770114 Push

RS PRO LINEAR SOLENOID, 12 V, 40 X 14 X 19 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Action: Push
 - Supply Voltage: 12 V
 - Dimensions: 40 x 14 x 19 mm



1770115 Pull

RS PRO LINEAR SOLENOID, 12 V, 37 X 20.3 X 26 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Action: Pull
 - Supply Voltage: 12 V
 - Dimensions: 37 x 20.3 x 26 mm



1770116 Pull

RS PRO LINEAR SOLENOID, 24 V DC, 40 X 24 X 29 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Action: Pull
 - Supply Voltage: 24 V dc
 - Dimensions: 40 x 24 x 29 mm



1770117 Pull

RS PRO LINEAR SOLENOID, 12 V, 40 X 24 X 29 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Action: Pull
 - Supply Voltage: 12 V
 - Dimensions: 40 x 24 x 29 mm



1770118 Pull

RS PRO LINEAR SOLENOID, 6 V DC, 40 X 24 X 29 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Action: Pull
 - Supply Voltage: 6 V dc
 - Dimensions: 40 x 24 x 29 mm



1770119 Pull

RS PRO LINEAR SOLENOID, 12 V, 53.5 X 27 X 30 MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Action: Pull
 - Supply Voltage: 12 V
 - Dimensions: 53.5 x 27 x 30 mm



1770120 Pull

RS PRO LINEAR SOLENOID, 24 V DC, 64 X 30 X 38 MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Action: Pull
 - Supply Voltage: 24 V dc
 - Dimensions: 64 x 30 x 38 mm



1770121 Pull

RS PRO LINEAR SOLENOID, 12 V, 35.5 X 25.4 X 31.8 MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Action: Pull
 - Supply Voltage: 12 V
 - Dimensions: 35.5 x 25.4 x 31.8 mm



1770122 Pull

RS PRO LINEAR SOLENOID, 24 V DC, 35.5 X 25.4 X 31.8 MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Action: Pull
 - Supply Voltage: 24 V dc
 - Dimensions: 35.5 x 25.4 x 31.8 mm



1770123 Pull

RS PRO LINEAR SOLENOID, 24 V DC, 58 X 25.4 X 31.8 MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Action: Pull
 - Supply Voltage: 24 V dc
 - Dimensions: 58 x 25.4 x 31.8 mm



1770125 Pull

RS PRO LINEAR SOLENOID, 12 V, 58 X 25.4 X 31.8 MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Action: Pull
 - Supply Voltage: 12 V
 - Dimensions: 58 x 25.4 x 31.8 mm



1770127 Pull

RS PRO LINEAR SOLENOID, 12 V, 44 X 32 X 38 MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Action: Pull
 - Supply Voltage: 12 V
 - Dimensions: 44 x 32 x 38 mm



1770128 Pull

RS PRO LINEAR SOLENOID, 24 V DC, 50 X 37 X 41 MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Action: Pull
 - Supply Voltage: 24 V dc
 - Dimensions: 50 x 37 x 41 mm



1770130 Pull

RS PRO LINEAR SOLENOID, 12 V, 50 X 37 X 41 MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Action: Pull
 - Supply Voltage: 12 V
 - Dimensions: 50 x 37 x 41 mm



1770131 Pull

RS PRO LINEAR SOLENOID, 12 V, 84 X 52 X 58 MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Action: Pull
 - Supply Voltage: 12 V
 - Dimensions: 84 x 52 x 58 mm



1770134 Pull

RS PRO LINEAR SOLENOID, 12 V, 42.5 X 40.9 X 40.9 MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Action: Pull
 - Supply Voltage: 12 V
 - Dimensions: 42.5 x 40.9 x 40.9 mm



1770135 Pull

RS PRO LINEAR SOLENOID, 6 V DC, 42.5 X 40.9 X 40.9 MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Action: Pull
 - Supply Voltage: 6 V dc
 - Dimensions: 42.5 x 40.9 x 40.9 mm



1770136 Pull

RS PRO LINEAR SOLENOID, 6 V DC, 16 X 13 X 20 MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Power Consumption: 15 W
 - Supply Voltage: 6 V dc
 - Plunger Diameter: 5 mm
 - Product Height: 16 mm
 - Product Width: 13 mm
 - Product Depth: 20 mm
 - Dimensions: 16 x 13 x 20 mm



1770137 15 W

RS PRO LINEAR SOLENOID, 12 V, 16 X 14 X 30 MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Power Consumption: 30 W
 - Supply Voltage: 12 V
 - Plunger Diameter: 7 mm
 - Product Height: 16 mm
 - Product Width: 14 mm
 - Product Depth: 30 mm
 - Dimensions: 16 x 14 x 30 mm



1770138 30 W

RS PRO LINEAR SOLENOID, 12 V, 26 X 20 X 36.8 MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Power Consumption: 40 W
 - Supply Voltage: 12 V
 - Plunger Diameter: 10 mm
 - Product Height: 26 mm
 - Product Width: 20 mm
 - Product Depth: 36.8 mm
 - Dimensions: 26 x 20 x 36.8 mm



1770139 40 W

RS PRO LINEAR SOLENOID, 24 V DC, 30 X 27 X 53.5 MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Power Consumption: 80 W
 - Supply Voltage: 24 V dc
 - Plunger Diameter: 12 mm
 - Product Height: 30 mm
 - Product Width: 27 mm
 - Product Depth: 53.5 mm
 - Dimensions: 30 x 27 x 53.5 mm



1770140 80 W

RS PRO LINEAR SOLENOID, 24 V DC

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 24 V dc
 - Action: Pull



1770141 24 V dc

RS PRO LINEAR SOLENOID, 12 V

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 12 V
 - Action: Pull



1770142 12 V

RS PRO LINEAR SOLENOID, 24 V DC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Action: Pull
 - Supply Voltage: 24 V dc
 - Maximum Stroke: 10 mm



1770143 Pull

RS PRO LINEAR SOLENOID, 12 V

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Action: Pull
 - Supply Voltage: 12 V
 - Maximum Stroke: 10 mm



1770144 Pull

RS PRO LINEAR SOLENOID, 24 V DC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 24 V dc
 - Action: Pull



1770145 24 V dc

RS PRO LINEAR SOLENOID, 24 V DC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 24 V dc
 - Action: Pull



1770146 24 V dc

BATTERY VOLTAGE ALARM RELAY

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Monitoring Application: Voltage
 - Contact Configuration: SPDT
 - Voltage Sensitivity: Undervoltage
 - Electrical Phase: 1
 - Voltage Sensing Range: 12 → 24 V dc
 - Time Delay: 0 → 30 s
 - Mounting Type: DIN Rail
 - Series: L



1026130 Voltage

RS PRO DIN RAIL VOLTAGE MONITORING RELAY, 48 → 63HZ, 1

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Monitoring Application: Voltage
 - Contact Configuration: SPDT
 - Voltage Sensitivity: Overvoltage, Undervoltage
 - Electrical Phase: 1
 - Time Delay: 0.2 → 10 s
 - Frequency Sensing Range: 48 → 63 Hz
 - Mounting Type: DIN Rail
 - Series: L



1026131 Voltage

RS PRO DIN RAIL VOLTAGE MONITORING RELAY, MAXIMUM OF

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Monitoring Application: Voltage
 - Contact Configuration: SPDT
 - Voltage Sensitivity: Overvoltage, Undervoltage
 - Electrical Phase: 1
 - Voltage Sensing Range: Maximum of 500 V
 - Time Delay: 0.1 → 30 s
 - Frequency Sensing Range: 48 → 63 Hz
 - Mounting Type: DIN Rail



1026133 Voltage

RS PRO DIN RAIL CURRENT MONITORING RELAY, 1 → 10A, 48 →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Monitoring Application: Current
 - Contact Configuration: SPDT
 - Electrical Phase: 1
 - Current Sensitivity: Overcurrent, Undercurrent
 - Minimum Current Sensed: 1 A
 - Maximum Current Sensed: 10 A
 - Time Delay: 0.1 → 30 s
 - Mounting Type: DIN Rail



1026134 Current

RS PRO DIN RAIL PHASE, VOLTAGE MONITORING RELAY, MAXIMUM OF

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Monitoring Application: Phase, Voltage
 - Contact Configuration: SPDT
 - Voltage Sensitivity: Undervoltage
 - Electrical Phase: 3
 - Voltage Sensing Range: Maximum of 280 V
 - Phase Sensitivity: Phase Failure, Phase Sequence
 - Time Delay: 100 ms
 - Mounting Type: DIN Rail



1026135 Phase, Voltage

RS PRO DIN RAIL PHASE, VOLTAGE MONITORING RELAY, 48 → 63HZ, 3

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Monitoring Application: Phase, Voltage
 - Contact Configuration: SPDT
 - Voltage Sensitivity: Undervoltage
 - Electrical Phase: 3
 - Phase Sensitivity: Phase Failure, Phase Sequence
 - Time Delay: 0.2 → 10 s
 - Frequency Sensing Range: 48 → 63 Hz
 - Mounting Type: DIN Rail



1026136 Phase, Voltage

RS PRO DIN RAIL PHASE, VOLTAGE MONITORING RELAY, 48 → 63HZ, 3

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Monitoring Application: Phase, Voltage
 - Contact Configuration: SPDT
 - Voltage Sensitivity: Overvoltage, Undervoltage
 - Electrical Phase: 3
 - Phase Sensitivity: Phase Failure, Phase Sequence
 - Time Delay: 0.2 → 10 s
 - Series: L
 - Frequency Sensing Range: 48 → 63 Hz



1026137 Phase, Voltage

RS PRO PLUGGABLE FUNCTION MODULE, LED MODULE FOR USE WITH

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: LED Module
 - For Use With: RFT Relay



1441613 LED Module

RS PRO PLUGGABLE FUNCTION MODULE, RC CIRCUIT FOR USE WITH

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: RC Circuit
 - For Use With: RFT Relay



1441616 RC Circuit

RS PRO PLUG IN POWER RELAY, 12V DC COIL, 10A SWITCHING CURRENT,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Coil Voltage: 12 V dc
 - Contact Configuration: DPDT
 - Mounting Type: Plug In
 - Switching Current: 10 A
 - Number of Poles: 2
 - Latching: No
 - Terminal Type: Through Hole
 - Coil Resistance: 120 Ω



348756 12 V dc

RS PRO PLUG IN POWER RELAY, 230V AC COIL, 10A SWITCHING CURRENT,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Coil Voltage: 230 V ac
 - Contact Configuration: DPDT
 - Mounting Type: Plug In
 - Switching Current: 10 A
 - Number of Poles: 2
 - Latching: No
 - Terminal Type: Through Hole
 - Coil Resistance: 8.2 kΩ



348762 230 V ac

RS PRO, 115V AC COIL NON-LATCHING RELAY DPDT, 10A

- ขนาดบรรจุภัณฑ์: 1 x EA
- Coil Voltage: 115 V ac
 - Coil Power: 2 W
 - Coil Resistance: 2 k Ω
 - Isolation Coil To Contact: 1.5 kV ac
 - Contact Configuration: DPDT
 - Mounting Type: Plug In
 - Switching Current: 10 A
 - Terminal Type: Through Hole



348778 115 V ac

RS PRO PLUG IN POWER RELAY, 24V DC COIL, 10A SWITCHING CURRENT,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Coil Voltage: 24 V dc
 - Contact Configuration: DPDT
 - Mounting Type: Plug In
 - Switching Current: 10 A
 - Number of Poles: 2
 - Latching: No
 - Terminal Type: Through Hole
 - Coil Resistance: 478 Ω



348784 24 V dc

11PIN 3PDT PLUG-IN RELAY, 10A 230VAC COIL

- ขนาดบรรจุภัณฑ์: 1 x EA
- Coil Voltage: 230 V ac
 - Contact Configuration: 3PDT
 - Mounting Type: Plug In
 - Switching Current: 10 A
 - Number of Poles: 3
 - Latching: No
 - Terminal Type: Through Hole
 - Coil Resistance: 8.2 k Ω



348813 230 V ac

RELAY, 11 PIN, 24VDC COIL, 475 OHM, 10A, 3PCO

- ขนาดบรรจุภัณฑ์: 1 x EA
- Coil Voltage: 24 V dc
 - Contact Configuration: 3PDT
 - Mounting Type: Plug In
 - Switching Current: 10 A
 - Number of Poles: 3
 - Latching: No
 - Terminal Type: Through Hole
 - Coil Resistance: 478 Ω



348829 24 V dc

RS PRO PLUG IN POWER RELAY, 115V AC COIL, 10A SWITCHING CURRENT,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Coil Voltage: 115 V ac
 - Contact Configuration: 3PDT
 - Mounting Type: Plug In
 - Switching Current: 10 A
 - Number of Poles: 3
 - Latching: No
 - Terminal Type: Through Hole
 - Coil Resistance: 2 k Ω



349282 115 V ac

RS PRO PLUG IN POWER RELAY, 24V AC COIL, 10A SWITCHING CURRENT,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Coil Voltage: 24 V ac
 - Contact Configuration: DPDT
 - Mounting Type: Plug In
 - Switching Current: 10 A
 - Number of Poles: 2
 - Latching: No
 - Terminal Type: Through Hole
 - Coil Resistance: 85 Ω



349327 24 V ac

RS PRO PLUG IN POWER RELAY, 12V DC COIL, 5A SWITCHING CURRENT,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Coil Voltage: 12 V dc
 - Contact Configuration: 4PDT
 - Mounting Type: Plug In
 - Switching Current: 5 A
 - Number of Poles: 4
 - Latching: No
 - Terminal Type: Plug In
 - Coil Power: 150 W



121795 12 V dc

RS PRO PLUG IN POWER RELAY, 24V DC COIL, 5A SWITCHING CURRENT,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Coil Voltage: 12 V dc
 - Contact Configuration: 4PDT
 - Mounting Type: Plug In
 - Switching Current: 5 A
 - Number of Poles: 4
 - Latching: No
 - Terminal Type: Plug In
 - Coil Power: 150 W



121796 24 V dc

RS PRO PLUG IN POWER RELAY, 12V DC COIL, 6A SWITCHING CURRENT,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Coil Voltage: 12 V dc
 - Contact Configuration: 4PDT
 - Mounting Type: Plug In
 - Switching Current: 6 A
 - Number of Poles: 4
 - Latching: No
 - Terminal Type: Plug In
 - Coil Power: 180 W



121797 12 V dc

RS PRO PLUG IN POWER RELAY, 24V DC COIL, 6A SWITCHING CURRENT,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Coil Voltage: 24 V dc
 - Contact Configuration: 4PDT
 - Mounting Type: Plug In
 - Switching Current: 6 A
 - Number of Poles: 4
 - Latching: No
 - Terminal Type: Plug In
 - Coil Power: 180 W



121798 24 V dc

RS PRO PLUG IN POWER RELAY, 24V AC COIL, 6A SWITCHING CURRENT,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Coil Voltage: 24 V ac
 - Contact Configuration: 4PDT
 - Mounting Type: Plug In
 - Switching Current: 6 A
 - Number of Poles: 4
 - Latching: No
 - Terminal Type: Plug In
 - Coil Power: 180 W



121799 24 V ac

RS PRO PLUG IN POWER RELAY, 12V DC COIL, 16A SWITCHING CURRENT,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Coil Voltage: 12 V dc
 - Contact Configuration: SPDO
 - Mounting Type: Plug In
 - Switching Current: 16 A
 - Number of Poles: 1
 - Latching: No
 - Terminal Type: Plug In
 - Coil Power: 480 W



121780 12 V dc

RS PRO PLUG IN POWER RELAY, 24V DC COIL, 16A SWITCHING CURRENT,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Coil Voltage: 24 V dc
 - Contact Configuration: SPDT
 - Mounting Type: Plug In
 - Switching Current: 16 A
 - Number of Poles: 1
 - Latching: No
 - Terminal Type: Plug In
 - Coil Power: 480 W



1217806 24 V dc

RS PRO PLUG IN POWER RELAY, 24V AC COIL, 16A SWITCHING CURRENT,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Coil Voltage: 24 V ac
 - Contact Configuration: SPDT
 - Mounting Type: Plug In
 - Switching Current: 16 A
 - Number of Poles: 1
 - Latching: No
 - Terminal Type: Plug In
 - Coil Power: 480 W



1217807 24 V ac

RS PRO PLUG IN POWER RELAY, 12V DC COIL, 10A SWITCHING CURRENT,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Coil Voltage: 12 V dc
 - Contact Configuration: DPDT
 - Mounting Type: Plug In
 - Switching Current: 10 A
 - Number of Poles: 2
 - Latching: No
 - Terminal Type: Plug In
 - Coil Power: 300 W



1217810 12 V dc

RS PRO PLUG IN POWER RELAY, 24V DC COIL, 10A SWITCHING CURRENT,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Coil Voltage: 24 V dc
 - Contact Configuration: DPDT
 - Mounting Type: Plug In
 - Switching Current: 10 A
 - Number of Poles: 2
 - Latching: No
 - Terminal Type: Plug In
 - Coil Power: 300 W



1217811 24 V dc

RS PRO PLUG IN POWER RELAY, 24V AC COIL, 10A SWITCHING CURRENT,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Coil Voltage: 24 V ac
 - Contact Configuration: DPDT
 - Mounting Type: Plug In
 - Switching Current: 10 A
 - Number of Poles: 2
 - Latching: No
 - Terminal Type: Plug In
 - Coil Power: 300 W

**1217812** 24 V ac**RS PRO PLUG IN POWER RELAY, 12V DC COIL, 10A SWITCHING CURRENT,**

- ขนาดบรรจุภัณฑ์: 1 x EA
- Coil Voltage: 12 V dc
 - Contact Configuration: 3PDT
 - Mounting Type: Plug In
 - Switching Current: 10 A
 - Number of Poles: 3
 - Latching: No
 - Terminal Type: Plug In
 - Coil Power: 300 W

**1217815** 12 V dc**RS PRO PLUG IN POWER RELAY, 24V DC COIL, 10A SWITCHING CURRENT,**

- ขนาดบรรจุภัณฑ์: 1 x EA
- Coil Voltage: 24 V dc
 - Contact Configuration: 3PDT
 - Mounting Type: Plug In
 - Switching Current: 10 A
 - Number of Poles: 3
 - Latching: No
 - Terminal Type: Plug In
 - Coil Power: 300 W

**1217816** 24 V dc**RS PRO PLUG IN POWER RELAY, 12V DC COIL, 10A SWITCHING CURRENT,**

- ขนาดบรรจุภัณฑ์: 1 x EA
- Coil Voltage: 12 V dc
 - Contact Configuration: 4PDT
 - Mounting Type: Plug In
 - Switching Current: 10 A
 - Number of Poles: 4
 - Latching: No
 - Terminal Type: Plug In
 - Coil Power: 300 W

**1217820** 12 V dc**RS PRO PLUG IN POWER RELAY, 24V DC COIL, 10A SWITCHING CURRENT,**

- ขนาดบรรจุภัณฑ์: 1 x EA
- Coil Voltage: 24 V dc
 - Contact Configuration: 4PDT
 - Mounting Type: Plug In
 - Switching Current: 10 A
 - Number of Poles: 4
 - Latching: No
 - Terminal Type: Plug In
 - Coil Power: 300 W

**1217821** 24 V dc**RS PRO PLUG IN POWER RELAY, 12V DC COIL, 10A SWITCHING CURRENT,**

- ขนาดบรรจุภัณฑ์: 1 x EA
- Coil Voltage: 12 V dc
 - Contact Configuration: DPDT
 - Mounting Type: Plug In
 - Switching Current: 10 A
 - Number of Poles: 2
 - Latching: No
 - Terminal Type: Plug In
 - Coil Power: 300 W

**1217828** 12 V dc**RS PRO PLUG IN POWER RELAY, 24V DC COIL, 10A SWITCHING CURRENT,**

- ขนาดบรรจุภัณฑ์: 1 x EA
- Coil Voltage: 24 V dc
 - Contact Configuration: DPDT
 - Mounting Type: Plug In
 - Switching Current: 10 A
 - Number of Poles: 2
 - Latching: No
 - Terminal Type: Plug In
 - Coil Power: 300 W

**1217829** 24 V dc**RS PRO PLUG IN POWER RELAY, 24V DC COIL, 10A SWITCHING CURRENT,**

- ขนาดบรรจุภัณฑ์: 1 x EA
- Coil Voltage: 24 V dc
 - Contact Configuration: 3PDT
 - Mounting Type: Plug In
 - Switching Current: 10 A
 - Number of Poles: 3
 - Latching: No
 - Terminal Type: Plug In
 - Coil Power: 300 W

**1217835** 24 V dc**RS PRO PLUG IN POWER RELAY, 24V AC COIL, 10A SWITCHING CURRENT,**

- ขนาดบรรจุภัณฑ์: 1 x EA
- Coil Voltage: 24 V ac
 - Contact Configuration: 3PDT
 - Mounting Type: Plug In
 - Switching Current: 10 A
 - Number of Poles: 3
 - Latching: No
 - Terminal Type: Plug In
 - Coil Power: 300 W

**1217836** 24 V ac**RELAY, INDUSTRIAL, PLUG IN, 4RT, 5A, 20VAC, 12VDC**

- ขนาดบรรจุภัณฑ์: 1 x EA
- Coil Voltage: 12 V dc
 - Contact Configuration: 4PDT
 - Mounting Type: Plug In
 - Switching Current: 5 A
 - Number of Poles: 4
 - Latching: No
 - Terminal Type: Through Hole
 - Coil Resistance: 160 Ω

**3949065** 12 V dc**RS PRO PLUG IN POWER RELAY, 24V DC COIL, 5A SWITCHING CURRENT,**

- ขนาดบรรจุภัณฑ์: 1 x EA
- Coil Voltage: 24 V dc
 - Contact Configuration: 4PDT
 - Mounting Type: Plug In
 - Switching Current: 5 A
 - Number of Poles: 4
 - Latching: No
 - Terminal Type: Through Hole
 - Coil Resistance: 636 Ω

**3949087** 24 V dc**4PDT INDUSTRIAL RELAY, 3A 24VAC COIL**

- ขนาดบรรจุภัณฑ์: 1 x EA
- Coil Voltage: 24 V ac
 - Contact Configuration: 4PDT
 - Mounting Type: Plug In
 - Switching Current: 5 A
 - Number of Poles: 4
 - Terminal Type: Through Hole
 - Coil Resistance: 180 Ω
 - Coil Power: 1.2 W

**3949093** 24 V ac**RS PRO PLUG IN POWER RELAY, 120V AC COIL, 5A SWITCHING CURRENT,**

- ขนาดบรรจุภัณฑ์: 1 x EA
- Coil Voltage: 120 V ac
 - Contact Configuration: 4PDT
 - Mounting Type: Plug In
 - Switching Current: 5 A
 - Number of Poles: 4
 - Latching: No
 - Terminal Type: Through Hole
 - Coil Resistance: 4.43 kΩ

**3949100** 120 V ac**RS PRO PLUG IN POWER RELAY, 240V AC COIL, 5A SWITCHING CURRENT,**

- ขนาดบรรจุภัณฑ์: 1 x EA
- Coil Voltage: 240 V ac
 - Contact Configuration: 4PDT
 - Mounting Type: Plug In
 - Switching Current: 5 A
 - Number of Poles: 4
 - Latching: No
 - Terminal Type: Through Hole
 - Coil Resistance: 18.79 kΩ

**3949116** 240 V ac**RS PRO PCB MOUNT POWER RELAY, 240V AC COIL, 12A SWITCHING**

- ขนาดบรรจุภัณฑ์: 1 x EA
- Coil Voltage: 240 V ac
 - Contact Configuration: DPDT
 - Mounting Type: PCB Mount
 - Switching Current: 12 A
 - Number of Poles: 2
 - Latching: No
 - Terminal Type: Through Hole
 - Coil Resistance: 9.11 kΩ

**4500201** 240 V ac**RS PRO PCB MOUNT POWER RELAY, 110V AC COIL, 15A SWITCHING**

- ขนาดบรรจุภัณฑ์: 1 x EA
- Coil Voltage: 110 V ac
 - Contact Configuration: SPDT
 - Mounting Type: PCB Mount
 - Switching Current: 15 A
 - Number of Poles: 1
 - Latching: No
 - Terminal Type: PCB Pin
 - Coil Resistance: 3.83 kΩ

**4500217** 110 V ac

RS PRO PCB MOUNT POWER RELAY, 12V DC COIL, 15A SWITCHING

- ขนาดบรรจุภัณฑ์: 1 x EA
- Coil Voltage: 12 V dc
 - Contact Configuration: SPDT
 - Mounting Type: PCB Mount
 - Switching Current: 15 A
 - Number of Poles: 1
 - Latching: No
 - Terminal Type: PCB Pin
 - Coil Resistance: 188 Ω



4500223 12 V dc

RS PRO PCB MOUNT POWER RELAY, 24V AC COIL, 15A SWITCHING

- ขนาดบรรจุภัณฑ์: 1 x EA
- Coil Voltage: 24 V ac
 - Contact Configuration: SPDT
 - Mounting Type: PCB Mount
 - Switching Current: 15 A
 - Number of Poles: 1
 - Latching: No
 - Terminal Type: PCB Pin
 - Coil Resistance: 180 Ω



4500245 24 V ac

RS PRO PCB MOUNT POWER RELAY, 24V DC COIL, 15A SWITCHING

- ขนาดบรรจุภัณฑ์: 1 x EA
- Coil Voltage: 24 V dc
 - Contact Configuration: SPDT
 - Mounting Type: PCB Mount
 - Switching Current: 15 A
 - Number of Poles: 1
 - Latching: No
 - Terminal Type: PCB Pin
 - Coil Resistance: 750 Ω



4500251 24 V dc

RS PRO PCB MOUNT POWER RELAY, 110V AC COIL, 15A SWITCHING

- ขนาดบรรจุภัณฑ์: 1 x EA
- Coil Voltage: 110 V ac
 - Contact Configuration: SPDT
 - Mounting Type: PCB Mount
 - Switching Current: 15 A
 - Number of Poles: 1
 - Latching: No
 - Terminal Type: PCB Pin
 - Coil Resistance: 3.83 kΩ



4500267 110 V ac

RS PRO PCB MOUNT POWER RELAY, 12V DC COIL, 15A SWITCHING

- ขนาดบรรจุภัณฑ์: 1 x EA
- Coil Voltage: 12 V dc
 - Contact Configuration: SPDT
 - Mounting Type: PCB Mount
 - Switching Current: 15 A
 - Number of Poles: 1
 - Latching: No
 - Terminal Type: PCB Pin
 - Coil Resistance: 188 Ω



4500273 12 V dc

RELAY, MINIATURE, PLUG IN, INDICATOR, 24VDC COIL, 750

- ขนาดบรรจุภัณฑ์: 1 x EA
- Coil Voltage: 24 V dc
 - Contact Configuration: SPDT
 - Mounting Type: Plug In
 - Switching Current: 15 A
 - Number of Poles: 1
 - Latching: No
 - Terminal Type: PCB Pin
 - Coil Resistance: 750 Ω



4500295 24 V dc

RS PRO PLUG IN POWER RELAY, 110V AC COIL, 10A SWITCHING CURRENT,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Coil Voltage: 110 V ac
 - Contact Configuration: DPDT
 - Mounting Type: Plug In
 - Switching Current: 10 A
 - Number of Poles: 2
 - Latching: No
 - Terminal Type: PCB Pin
 - Coil Resistance: 3.83 kΩ



4500302 110 V ac

RS PRO PLUG IN POWER RELAY, 12V DC COIL, 10A SWITCHING CURRENT,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Coil Voltage: 12 V dc
 - Contact Configuration: DPDT
 - Mounting Type: Plug In
 - Switching Current: 10 A
 - Number of Poles: 2
 - Latching: No
 - Terminal Type: PCB Pin
 - Coil Resistance: 160 Ω



4500318 12 V dc

RELAY, MINIATURE, POWER, 230VAC COIL, 10A, DPCCO

- ขนาดบรรจุภัณฑ์: 1 x EA
- Coil Voltage: 230 V ac
 - Contact Configuration: DPDT
 - Mounting Type: Plug In
 - Switching Current: 10 A
 - Number of Poles: 2
 - Latching: No
 - Terminal Type: PCB Pin
 - Coil Resistance: 12.5 kΩ



4500324 230 V ac

RELAY, MINIATURE, POWER, 240VAC COIL, 10A, DPCCO

- ขนาดบรรจุภัณฑ์: 1 x EA
- Coil Voltage: 240 V ac
 - Contact Configuration: DPDT
 - Mounting Type: Plug In
 - Switching Current: 10 A
 - Number of Poles: 2
 - Latching: No
 - Terminal Type: PCB Pin
 - Coil Resistance: 15.7 kΩ



4500330 240 V ac

RS PRO PLUG IN POWER RELAY, 24V AC COIL, 10A SWITCHING CURRENT,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Coil Voltage: 24 V ac
 - Contact Configuration: DPDT
 - Mounting Type: Plug In
 - Switching Current: 10 A
 - Number of Poles: 2
 - Latching: No
 - Terminal Type: PCB Pin
 - Coil Resistance: 180 Ω



4500346 24 V ac

RS PRO PLUG IN POWER RELAY, 24V DC COIL, 10A SWITCHING CURRENT,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Coil Voltage: 24 V dc
 - Contact Configuration: DPDT
 - Mounting Type: Plug In
 - Switching Current: 10 A
 - Number of Poles: 2
 - Latching: No
 - Terminal Type: PCB Pin
 - Coil Resistance: 650 Ω



4500352 24 V dc

RS PRO PLUG IN POWER RELAY, 12V DC COIL, 10A SWITCHING CURRENT,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Coil Voltage: 12 V dc
 - Contact Configuration: DPDT
 - Mounting Type: Plug In
 - Switching Current: 10 A
 - Number of Poles: 2
 - Latching: No
 - Terminal Type: PCB Pin
 - Coil Resistance: 160 Ω



4500374 12 V dc

RS PRO PLUG IN POWER RELAY, 230V AC COIL, 10A SWITCHING CURRENT,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Coil Voltage: 230 V ac
 - Contact Configuration: DPDT
 - Mounting Type: Plug In
 - Switching Current: 10 A
 - Number of Poles: 2
 - Latching: No
 - Terminal Type: PCB Pin
 - Coil Resistance: 12.5 kΩ



4500380 230 V ac

RELAY, MINIATURE, PLUG IN, INDICATOR, 240VAC

- ขนาดบรรจุภัณฑ์: 1 x EA
- Coil Voltage: 240 V ac
 - Contact Configuration: DPDT
 - Mounting Type: Plug In
 - Switching Current: 10 A
 - Number of Poles: 2
 - Latching: No
 - Terminal Type: PCB Pin
 - Coil Resistance: 15.7 kΩ



4500403 240 V ac

RS PRO PLUG IN POWER RELAY, 24V AC COIL, 10A SWITCHING CURRENT,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Coil Voltage: 24 V ac
 - Contact Configuration: DPDT
 - Mounting Type: Plug In
 - Switching Current: 10 A
 - Number of Poles: 2
 - Latching: No
 - Terminal Type: PCB Pin
 - Coil Resistance: 180 Ω



4500419 24 V ac

RELAY, MINIATURE, PLUG IN, INDICATOR, 24VDC COIL, 650

- ขนาดบรรจุภัณฑ์: 1 x EA
- Coil Voltage: 24 V dc
 - Contact Configuration: DPDT
 - Mounting Type: Plug In
 - Switching Current: 10 A
 - Number of Poles: 2
 - Latching: No
 - Terminal Type: PCB Pin
 - Coil Resistance: 650 Ω



4500425 24 V dc

RS PRO PLUG IN POWER RELAY, 240V AC COIL, 12A SWITCHING CURRENT,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Coil Voltage: 240 V ac
 - Contact Configuration: 3PDT
 - Mounting Type: Plug In
 - Switching Current: 12 A
 - Number of Poles: 3
 - Latching: No
 - Terminal Type: PCB Pin
 - Coil Resistance: 12.1 kΩ



6133594 240 V ac

RS PRO PLUG IN POWER RELAY, 110V AC COIL, 12A SWITCHING CURRENT,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Coil Voltage: 110 V ac
 - Contact Configuration: 3PDT
 - Mounting Type: Plug In
 - Switching Current: 12 A
 - Number of Poles: 4
 - Latching: No
 - Terminal Type: PCB Pin
 - Coil Resistance: 1.8 kΩ



6133768 110 V ac

RS PRO PLUG IN POWER RELAY, 12V DC COIL, 12A SWITCHING CURRENT,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Coil Voltage: 12 V dc
 - Contact Configuration: 4PDT
 - Mounting Type: Plug In
 - Switching Current: 12 A
 - Number of Poles: 4
 - Latching: No
 - Terminal Type: PCB Pin
 - Coil Resistance: 96 Ω



6133780 12 V dc

RS PRO PLUG IN POWER RELAY, 240V AC COIL, 12A SWITCHING CURRENT,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Coil Voltage: 240 V ac
 - Contact Configuration: 4PDT
 - Mounting Type: Plug In
 - Switching Current: 12 A
 - Number of Poles: 4
 - Latching: No
 - Terminal Type: PCB Pin
 - Coil Resistance: 9.12 kΩ



6133796 240 V ac

RS PRO PLUG IN POWER RELAY, 24V AC COIL, 12A SWITCHING CURRENT,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Coil Voltage: 24 V ac
 - Contact Configuration: 4PDT
 - Mounting Type: Plug In
 - Switching Current: 12 A
 - Number of Poles: 4
 - Latching: No
 - Terminal Type: PCB Pin
 - Coil Resistance: 84.5 Ω



6133803 24 V ac

RS PRO PLUG IN POWER RELAY, 24V DC COIL, 12A SWITCHING CURRENT,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Coil Voltage: 24 V dc
 - Contact Configuration: 4PDT
 - Mounting Type: Plug In
 - Switching Current: 12 A
 - Number of Poles: 4
 - Latching: No
 - Terminal Type: PCB Pin
 - Coil Resistance: 388 Ω



6133819 24 V dc

RS PRO MARKER FOR USE WITH SOLID STATE RELAYS, 120 PIECES

- ขนาดบรรจุภัณฑ์: 120 x EA
- Accessory Type: Marker
 - For Use With: Solid State Relays
 - Pack Quantity: 120



8886950 Marker

DIN RAIL SKT RISING/SCREW 14 PINCLIP&TAG

- ขนาดบรรจุภัณฑ์: 1 x EA
- Voltage: 300 V
 - For Use With: RS PRO RKE & RKF 14 Pin Relays
 - Termination Type: Screw
 - Number of Contacts: 14
 - Current Rating: 10 A
 - Mounting Type: DIN Rail



1217802 300 V

RS PRO RELAY SOCKET FOR USE WITH RS PRO RKE & RKF 14 PIN

- ขนาดบรรจุภัณฑ์: 1 x EA
- Voltage: 300 V
 - For Use With: RS PRO RKE & RKF 14 Pin Relays
 - Termination Type: Screw
 - Number of Contacts: 14
 - Current Rating: 10 A
 - Mounting Type: DIN Rail



1217803 300 V

DIN RAIL SKT RISING/SCREW CLIP&TAG

- ขนาดบรรจุภัณฑ์: 1 x EA
- Voltage: 300 V
 - For Use With: RS PRO RKL Relays DPDT
 - Termination Type: Screw
 - Number of Contacts: 8
 - Current Rating: 16 A
 - Mounting Type: DIN Rail



1217825 300 V

RS PRO RELAY SOCKET FOR USE WITH RS PRO RKL RELAYS 3PDT 11

- ขนาดบรรจุภัณฑ์: 1 x EA
- Voltage: 300 V
 - For Use With: RS PRO RKL Relays 3PDT
 - Termination Type: Screw
 - Number of Contacts: 11
 - Current Rating: 16 A
 - Mounting Type: DIN Rail



1217826 300 V

DIN RAIL SKT RISING/SCREWCLIP&TAG

- ขนาดบรรจุภัณฑ์: 1 x EA
- Voltage: 300 V
 - For Use With: RS PRO RKL Relays 4PDT
 - Termination Type: Screw
 - Number of Contacts: 14
 - Current Rating: 16 A
 - Mounting Type: DIN Rail



1217827 300 V

RS PRO RELAY SOCKET FOR USE WITH RS PRO RUB RELAYS 8 PIN, DIN

- ขนาดบรรจุภัณฑ์: 1 x EA
- Voltage: 300 V
 - For Use With: RS PRO RUB Relays
 - Termination Type: Screw
 - Number of Contacts: 8
 - Current Rating: 12 A
 - Mounting Type: DIN Rail



1217839 300 V

RS PRO RELAY SOCKET FOR USE WITH RS PRO RUB RELAYS 11 PIN, DIN

- ขนาดบรรจุภัณฑ์: 1 x EA
- Voltage: 300 V
 - For Use With: RS PRO RUB Relays
 - Termination Type: Screw
 - Number of Contacts: 11
 - Current Rating: 12 A
 - Mounting Type: DIN Rail



1217840 300 V

RS PRO RELAY SOCKET FOR USE WITH RS PRO RUB RELAYS 8 PIN, DIN

- ขนาดบรรจุภัณฑ์: 1 x EA
- Voltage: 300 V
 - For Use With: RS PRO RUB Relays
 - Termination Type: Screw
 - Number of Contacts: 8
 - Current Rating: 15 A
 - Mounting Type: DIN Rail



1217841 300 V

DIN RAIL SKT 11-PIN RISING

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Voltage: 300 V
 - For Use With: RS PRO RUB Relays
 - Termination Type: Screw
 - Number of Contacts: 11
 - Current Rating: 15 A
 - Mounting Type: DIN Rail



1217842 300 V

SOCKET RFT2 RISE PLT CLAMP PLASTIC CLIP

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Voltage: 300 V
 - For Use With: RFT Interface Relay
 - Termination Type: Screw
 - Number of Contacts: 8
 - Current Rating: 10 A
 - Mounting Type: DIN Rail



1441609 300 V

SOCKET RFT1 RISE PLT CLAMP PLASTIC CLIP

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Voltage: 300 V
 - For Use With: RFT Interface Relay
 - Termination Type: Screw
 - Number of Contacts: 5
 - Current Rating: 10 A
 - Mounting Type: DIN Rail



1441610 300 V

RS PRO RELAY SOCKET FOR USE WITH RFT RELAY, DIN RAIL, 300V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Voltage: 300 V ac
 - For Use With: RFT Relay
 - Mounting Type: DIN Rail
 - Current Rating: 16 A



1441611 300 V ac

RS PRO RELAY SOCKET FOR USE WITH RFT RELAY, DIN RAIL, 300V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Voltage: 300 V ac
 - For Use With: RFT Relay
 - Mounting Type: DIN Rail
 - Current Rating: 10 A



1441612 300 V ac

RS PRO SIGNAL CONDITIONER, 8 → 30V DC, FREQUENCY INPUT,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Module Type: Frequency Converter
 - Input Signal Type: Frequency
 - Output Signal Type: Current
 - Supply Voltage: 8 → 30 V dc
 - Input Range: 0 → 1 kHz
 - Output Range: 4 → 20 mA
 - Mounting Type: DIN Rail Mount
 - Operating Temperature Range: 0 → +45 °C



223363 Frequency

RS PRO SIGNAL CONDITIONER, 8 → 30V DC, FREQUENCY INPUT,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Module Type: Frequency Converter
 - Input Signal Type: Frequency
 - Output Signal Type: Current
 - Supply Voltage: 8 → 30 V dc
 - Input Range: 0 → 100 Hz
 - Output Range: 4 → 20 mA
 - Mounting Type: DIN Rail Mount
 - Operating Temperature Range: 0 → +45 °C



223385 Frequency

RS PRO SIGNAL CONDITIONER, 24 → 230V AC, VOLTAGE INPUT, CURRENT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Module Type: Signal Isolator
 - Input Signal Type: Voltage
 - Output Signal Type: Current
 - Supply Voltage: 24 → 230 V ac
 - Input Range: 0 → 10 V dc
 - Output Range: 4 → 20 mA
 - Mounting Type: DIN Rail Mount
 - Operating Temperature Range: -20 → +60 °C



629522 Signal Isolator

RS PRO SIGNAL CONDITIONER, 24 → 240V AC/DC, CURRENT, VOLTAGE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Module Type: Analogue Signal Converter
 - Input Signal Type: Current, Voltage
 - Output Signal Type: Current, Voltage
 - Supply Voltage: 24 → 240 V ac/dc
 - Input Range: 0 → 10 V, 0 → 20 mA, 4 → 20 mA
 - Output Range: 0 → 10 V, 0 → 20 mA, 4 → 20 mA
 - Mounting Type: DIN Rail Mount
 - Operating Temperature Range: -25 → +60 °C



1923389 Analogue Signal

RS PRO SIGNAL CONDITIONER, 24 → 240V AC/DC, CURRENT, VOLTAGE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Module Type: Analogue Signal Converter
 - Input Signal Type: Current, Voltage
 - Output Signal Type: Current, Voltage
 - Supply Voltage: 24 → 240 V ac/dc
 - Input Range: 0 → 1 V, 0 → 2 V, 0 → 5 mA, 0 → 5 V, 0 → 10 mA, 0 → 10 V, 0 → 20 mA, 0 → 20 V, 0 → 60 mV, 0 → 100 mV, 0 → 300 mV, 0 → 500 mV, 2 → 10 V, 4 → 20 mA, ±5 mA, ±20 mA
 - Output Range: 0 → 10 V, 0 → 20 mA, 4 → 20 mA
 - Mounting Type: DIN Rail Mount
 - Operating Temperature Range: -25 → +60 °C



1923390 Analogue Signal

RS PRO SIGNAL CONDITIONER, CURRENT INPUT, CURRENT OUTPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Module Type: Analogue Signal Converter
 - Input Signal Type: Current
 - Output Signal Type: Current
 - Input Range: 4 → 20 mA
 - Output Range: 4 → 20 mA
 - Mounting Type: DIN Rail Mount
 - Operating Temperature Range: -25 → +60 °C
 - Minimum Operating Temperature: -25 °C



1923391 Analogue Signal

RS PRO SIGNAL CONDITIONER, 24V AC/DC, VOLTAGE INPUT, VOLTAGE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Module Type: Analogue Signal Converter
 - Input Signal Type: Voltage
 - Output Signal Type: Voltage
 - Supply Voltage: 24 V ac/dc
 - Input Range: 0 → 10 V dc
 - Output Range: 0 → 10 V dc
 - Mounting Type: DIN Rail Mount
 - Operating Temperature Range: -25 → +60 °C



1923392 Analogue Signal

RS PRO SIGNAL CONDITIONER, 24V AC/DC, VOLTAGE INPUT, CURRENT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Module Type: Analogue Signal Converter
 - Input Signal Type: Voltage
 - Output Signal Type: Current
 - Supply Voltage: 24 V ac/dc
 - Input Range: 0 → 10 V dc
 - Output Range: 4 → 20 mA
 - Mounting Type: DIN Rail Mount
 - Operating Temperature Range: -25 → +60 °C



1923393 Analogue Signal

RS PRO SIGNAL CONDITIONER, 24V AC/DC, CURRENT INPUT, CURRENT,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Module Type: Analogue Signal Converter
 - Input Signal Type: Current
 - Output Signal Type: Current, Voltage
 - Supply Voltage: 24 V ac/dc
 - Input Range: 4 → 20 mA
 - Output Range: 0 → 10 V dc
 - Mounting Type: DIN Rail Mount
 - Operating Temperature Range: -25 → +60 °C



1923394 Analogue Signal

RS PRO SIGNAL CONDITIONER, 24V AC/DC, CURRENT INPUT, CURRENT,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Module Type: Analogue Signal Converter
 - Input Signal Type: Current
 - Output Signal Type: Current, Voltage
 - Supply Voltage: 24 V ac/dc
 - Input Range: 4 → 20 mA
 - Output Range: 4 → 20 mA
 - Mounting Type: DIN Rail Mount
 - Operating Temperature Range: -25 → +60 °C



1923395 Analogue Signal

RS PRO SIGNAL CONDITIONER, 24V AC/DC, CURRENT, VOLTAGE INPUT,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Module Type: Analogue Signal Converter
 - Input Signal Type: Current, Voltage
 - Output Signal Type: Current, Voltage
 - Supply Voltage: 24 V ac/dc
 - Input Range: 0 → 10 V, 0 → 20 mA, 4 → 20 mA
 - Output Range: 0 → 10 V, 0 → 20 mA, 4 → 20 mA
 - Mounting Type: DIN Rail Mount
 - Operating Temperature Range: -25 → +60 °C



1923396 Analogue Signal

RS PRO SIGNAL CONDITIONER, 24 → 240V AC/DC, CURRENT, VOLTAGE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Module Type: Analogue Signal Converter
 - Input Signal Type: Current, Voltage
 - Output Signal Type: Current, Voltage
 - Supply Voltage: 24 → 240 V ac/dc
 - Input Range: 0 → 10 V, 0 → 20 mA, 4 → 20 mA
 - Output Range: 0 → 10 V, 0 → 20 mA, 4 → 20 mA
 - Mounting Type: DIN Rail Mount
 - Operating Temperature Range: -25 → +60 °C



1923397 Analogue Signal

RS PRO SIGNAL CONDITIONER, 24V AC/DC, VOLTAGE INPUT, CURRENT,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Module Type: Analogue Signal Converter
 - Input Signal Type: Voltage
 - Output Signal Type: Current, Voltage
 - Supply Voltage: 24 V ac/dc
 - Input Range: 0 → 10 V dc
 - Output Range: 0 → 10 V, 0 → 20 mA, 4 → 20 mA
 - Mounting Type: DIN Rail Mount
 - Operating Temperature Range: -25 → +60 °C



1923398 Analogue Signal

RS PRO SIGNAL CONDITIONER, 24V AC/DC, CURRENT INPUT, CURRENT,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Module Type: Analogue Signal Converter
 - Input Signal Type: Current
 - Output Signal Type: Current, Voltage
 - Supply Voltage: 24 V ac/dc
 - Input Range: 4 → 20 mA
 - Output Range: 0 → 10 V, 0 → 20 mA, 4 → 20 mA
 - Mounting Type: DIN Rail Mount
 - Operating Temperature Range: -25 → +60 °C



1923399 Analogue Signal

RS PRO SIGNAL CONDITIONER, 10 → 30V DC, CURRENT INPUT, RELAY

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Module Type: Trip Amplifier
 - Input Signal Type: Current
 - Output Signal Type: Relay
 - Supply Voltage: 10 → 30 V dc
 - Input Range: 4 → 20 mA
 - Mounting Type: DIN Rail Mount
 - Operating Temperature Range: 0 → +50 °C
 - Minimum Operating Temperature: 0 °C



2184453 Trip Amplifier

RS PRO SIGNAL CONDITIONER, 24V DC, CURRENT INPUT, VOLTAGE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Module Type: Signal Isolator
 - Input Signal Type: Current
 - Output Signal Type: Voltage
 - Supply Voltage: 24 V dc
 - Input Range: 4 → 20 mA
 - Output Range: 0 → 10 V dc
 - Mounting Type: DIN Rail Mount
 - Operating Temperature Range: 0 → +45 °C



4662258 Signal Isolator

RS PRO SIGNAL CONDITIONER, 9 → 30V DC, CURRENT INPUT, CURRENT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Module Type: Signal Isolator
 - Input Signal Type: Current
 - Output Signal Type: Current
 - Supply Voltage: 9 → 30 V dc
 - Input Range: 4 → 20 mA
 - Output Range: 2 x 4 → 20 mA
 - Mounting Type: DIN Rail Mount
 - Operating Temperature Range: 0 → +45 °C



4662264 Signal Isolator

RS PRO SIGNAL CONDITIONER, 20 → 240 V AC, 20 → 240V DC, UNIVERSAL

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Module Type: Universal Signal Converter
 - Input Signal Type: Universal
 - Output Signal Type: Current, Voltage, Relay
 - Supply Voltage: 20 → 240 V ac, 20 → 240 V dc
 - Input Range: 1 → 100 kΩ, -10 → 10 V dc, -200 → +2000 °C, -25 → 25 mA
 - Output Range: 0 → 12 V, 0 → 20 mA
 - Mounting Type: DIN Rail Mount
 - Operating Temperature Range: -20 → +70 °C



7886987 Universal Signal

RS PRO SIGNAL CONDITIONER, 10 → 32 V AC, 10 → 48V DC, CURRENT,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Module Type: Signal Isolator
 - Input Signal Type: Current, Voltage
 - Output Signal Type: Current, Voltage
 - Supply Voltage: 10 → 32 V ac, 10 → 48 V dc
 - Input Range: -50 → +50 mA, -50 → +50 V
 - Output Range: 0 → 21.5 mA, -10 → +10 V
 - Mounting Type: DIN Rail Mount
 - Operating Temperature Range: -30 → +70 °C



7886996 Signal Isolator

RS PRO SIGNAL CONDITIONER, 10 → 32 V AC, 10 → 48V DC, RTD,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Module Type: Temperature Converter
 - Input Signal Type: RTD, Thermocouple
 - Output Signal Type: Current, Voltage
 - Supply Voltage: 10 → 32 V ac, 10 → 48 V dc
 - Input Range: 0 → 100 kΩ, -100 → 200 mV, -200 → +2000 °C
 - Output Range: 0 → 10 V, 0 → 21.5 mA
 - Mounting Type: DIN Rail Mount
 - Operating Temperature Range: -30 → +70 °C



7886999 Temperature

RS PRO SIGNAL CONDITIONER, 16.8 → 30 V DC, 19.2 → 28.8V AC,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Module Type: Frequency Converter
 - Input Signal Type: Frequency
 - Output Signal Type: Current, Voltage
 - Supply Voltage: 16.8 → 30 V dc, 19.2 → 28.8 V ac
 - Input Range: 0 → 1 kHz, 0 → 10 kHz, 0 → 100 Hz, 0 → 12 kHz, 0 → 16 kHz, 0 → 2 kHz, 0 → 2.5 kHz, 0 → 20 kHz, 0 → 200 Hz, 0 → 24 kHz, 0 → 250 Hz, 0 → 28.8 kHz, 0 → 3 kHz, 0 → 4 kHz, 0 → 400 Hz, 0 → 5 kHz, 0 → 500 Hz, 0 → 6 kHz, 0 → 750 Hz, 0 → 8 kHz
 - Output Range: 0 → 10 V, 0 → 20 mA, 4 → 20 mA
 - Mounting Type: DIN Rail Mount
 - Operating Temperature Range: -25 → +60 °C



7948524 Frequency

RS PRO SIGNAL CONDITIONER, 16.8 → 30V, RTD, THERMOCOUPLE INPUT,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Module Type: Temperature Converter
 - Input Signal Type: RTD, Thermocouple
 - Output Signal Type: Current, Voltage
 - Supply Voltage: 16.8 → 30 V
 - Input Range: -210 → +2310 °C, -220 → +850 °C
 - Output Range: 0 → 10 V, 0 → 20 mA, -10 → +10 V, 4 → 20 mA
 - Mounting Type: DIN Rail Mount
 - Operating Temperature Range: -40 → +70 °C



7948533 Temperature

RS PRO SIGNAL CONDITIONER, 16.8 → 30V, CURRENT INPUT, CURRENT,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Module Type: Analogue Signal Converter
 - Input Signal Type: Current
 - Output Signal Type: Current, Voltage
 - Supply Voltage: 16.8 → 30 V
 - Input Range: ±1 A, 0 → 1 A
 - Output Range: 0 → 10 V, 0 → 20 mA, 4 → 20 mA
 - Mounting Type: DIN Rail Mount
 - Operating Temperature Range: -25 → +60 °C



7948549 Analogue Signal

RS PRO SIGNAL CONDITIONER, 16.8 → 30V, CURRENT, VOLTAGE INPUT,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Module Type: Analogue Signal Converter
 - Input Signal Type: Current, Voltage
 - Output Signal Type: Current, Voltage
 - Supply Voltage: 16.8 → 30 V
 - Input Range: ±30 V, ±5 A, ±50 mA
 - Output Range: 0 → 10 V, 0 → 20 mA, -10 → +10 V, 4 → 20 mA
 - Mounting Type: DIN Rail Mount
 - Operating Temperature Range: -40 → +70 °C



7948570 Analogue Signal

RS PRO SIGNAL CONDITIONER, 16.8 → 30V, CURRENT, VOLTAGE INPUT,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Module Type: Analogue Splitter
 - Input Signal Type: Current, Voltage
 - Output Signal Type: Current, Voltage
 - Supply Voltage: 16.8 → 30 V
 - Input Range: 0 → 10 V, 0 → 20 mA, 4 → 20 mA
 - Output Range: 0 → 10 V, 0 → 20 mA, 4 → 20 mA
 - Mounting Type: DIN Rail Mount
 - Operating Temperature Range: -40 → +70 °C



7948574 Analogue Splitter

RS PRO DIN RAIL SOLID STATE INTERFACE RELAY, 6 A MAX LOAD, 60

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Maximum Load Current: 6 A
 - Mounting Type: DIN Rail
 - Maximum Load Voltage: 60 V dc
 - Minimum Control Voltage: 32 V dc
 - Minimum Control Voltage: 4 V dc
 - Capacitance: 10 pF
 - Contact Configuration: SP
 - Control Voltage Range: 4 → 32 V dc



1213885 6 A

RS PRO DIN RAIL SOLID STATE INTERFACE RELAY, 6 A MAX LOAD,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Maximum Load Current: 6 A
 - Mounting Type: DIN Rail
 - Maximum Load Voltage: 280 V ac
 - Minimum Control Voltage: 280 V ac
 - Minimum Control Voltage: 200 V ac
 - Capacitance: 10 pF
 - Contact Configuration: SP
 - Control Voltage Range: 200 → 265 V rms



1213887 6 A

RS PRO DIN RAIL SOLID STATE INTERFACE RELAY, 6 A MAX LOAD,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Maximum Load Current: 6 A
 - Mounting Type: DIN Rail
 - Maximum Load Voltage: 280 V ac
 - Maximum Control Voltage: 32 V dc
 - Minimum Control Voltage: 4 V dc
 - Capacitance: 10 pF
 - Contact Configuration: SP
 - Control Voltage Range: 4 → 32 V dc



1213888 6 A

RS PRO DIN RAIL SOLID STATE RELAY, 20 A MAX. LOAD, 530 VRMS MAX.

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Maximum Load Current: 20 A
 - Mounting Type: DIN Rail
 - Minimum Load Voltage: 48 Vrms
 - Maximum Load Voltage: 530 Vrms
 - Minimum Control Voltage: 90 V ac
 - Maximum Control Voltage: 280 V ac
 - Switching Type: Random
 - Contact Configuration: SP



1213889 20 A

RS PRO DIN RAIL SOLID STATE RELAY, 20 A MAX. LOAD, 530 VRMS MAX.

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Maximum Load Current: 20 A
 - Mounting Type: DIN Rail
 - Minimum Load Voltage: 48 Vrms
 - Maximum Load Voltage: 530 Vrms
 - Minimum Control Voltage: 90 V ac
 - Maximum Control Voltage: 280 V ac
 - Switching Type: Zero Crossing
 - Contact Configuration: SP



1213890 20 A

RS PRO DIN RAIL SOLID STATE RELAY, 20 A MAX. LOAD, 530 VRMS MAX.

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Maximum Load Current: 20 A
 - Mounting Type: DIN Rail
 - Minimum Load Voltage: 48 Vrms
 - Maximum Load Voltage: 530 Vrms
 - Minimum Control Voltage: 4 V dc
 - Maximum Control Voltage: 32 V dc
 - Switching Type: Random
 - Contact Configuration: SP



1213891 20 A

RS PRO DIN RAIL SOLID STATE RELAY, 20 A MAX. LOAD, 530 VRMS MAX.

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Maximum Load Current: 20 A
 - Mounting Type: DIN Rail
 - Minimum Load Voltage: 48 Vrms
 - Maximum Load Voltage: 530 Vrms
 - Minimum Control Voltage: 4 V dc
 - Maximum Control Voltage: 32 V dc
 - Switching Type: Zero Crossing
 - Contact Configuration: SP



1213892 20 A

RS PRO DIN RAIL SOLID STATE RELAY, 30 A MAX. LOAD, 530 VRMS MAX.

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Maximum Load Current: 30 A
 - Mounting Type: DIN Rail
 - Minimum Load Voltage: 48 Vrms
 - Maximum Load Voltage: 530 Vrms
 - Minimum Control Voltage: 90 V ac
 - Maximum Control Voltage: 280 V ac
 - Switching Type: Zero Crossing
 - Contact Configuration: SP



1213894 30 A

RS PRO DIN RAIL SOLID STATE RELAY, 30 A MAX. LOAD, 530 VRMS MAX.

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Maximum Load Current: 30 A
 - Mounting Type: DIN Rail
 - Minimum Load Voltage: 48 Vrms
 - Maximum Load Voltage: 530 Vrms
 - Minimum Control Voltage: 4 V dc
 - Maximum Control Voltage: 32 V dc
 - Switching Type: Random
 - Contact Configuration: SP



1213895 30 A

RS PRO DIN RAIL SOLID STATE RELAY, 30 A MAX. LOAD, 530 VRMS MAX.

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Maximum Load Current: 30 A
 - Mounting Type: DIN Rail
 - Minimum Load Voltage: 48 Vrms
 - Maximum Load Voltage: 530 Vrms
 - Minimum Control Voltage: 4 V dc
 - Maximum Control Voltage: 32 V dc
 - Switching Type: Zero Crossing
 - Contact Configuration: SP



1213896 30 A

RS PRO DIN RAIL SOLID STATE RELAY

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Series: RS PRO
 - Mounting Type: DIN Rail
 - Dimensions: 60.8 x 67.5 x 6.1 mm
 - Operating Temperature Range: -25 → +60 °C
 - Minimum Operating Temperature: -25 °C
 - Length: 60.8 mm
 - Depth: 6.1 mm
 - Maximum Operating Temperature: +60 °C



2125492 RS PRO

RS PRO DIN RAIL SOLID STATE RELAY

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Series: RS PRO
 - Mounting Type: DIN Rail
 - Dimensions: 60.8 x 67.5 x 6.1 mm
 - Operating Temperature Range: -25 → +60 °C
 - Minimum Operating Temperature: -25 °C
 - Length: 60.8 mm
 - Depth: 6.1 mm
 - Maximum Operating Temperature: +60 °C



2125493 RS PRO

RS PRO DIN RAIL SOLID STATE RELAY


- ขนาดบรรจุภัณฑ์: **1 x EA**
- Series: RS PRO
 - Mounting Type: DIN Rail
 - Dimensions: 60.8 x 67.5 x 6.1 mm
 - Operating Temperature Range: -25 → +60 °C
 - Minimum Operating Temperature: -25 °C
 - Length: 60.8 mm
 - Depth: 6.1 mm
 - Maximum Operating Temperature: +60 °C



2125495 RS PRO

RS PRO DIN RAIL SOLID STATE RELAY

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Series: RS PRO
 - Mounting Type: DIN Rail
 - Dimensions: 60.8 x 67.5 x 6.1 mm
 - Operating Temperature Range: -25 → +60 °C
 - Minimum Operating Temperature: -25 °C
 - Length: 60.8 mm
 - Depth: 6.1 mm
 - Maximum Operating Temperature: +60 °C



2125496 RS PRO

RS PRO DIN RAIL SOLID STATE RELAY

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Series: RS PRO
 - Mounting Type: DIN Rail
 - Dimensions: 60.8 x 67.5 x 6.1 mm
 - Operating Temperature Range: -25 → +60 °C
 - Minimum Operating Temperature: -25 °C
 - Length: 60.8 mm
 - Depth: 6.1 mm
 - Maximum Operating Temperature: +60 °C



2125497 RS PRO

RS PRO DIN RAIL SOLID STATE RELAY

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Series: RS PRO
 - Mounting Type: DIN Rail
 - Dimensions: 60.8 x 67.5 x 6.1 mm
 - Operating Temperature Range: -25 → +60 °C
 - Minimum Operating Temperature: -25 °C
 - Length: 60.8 mm
 - Depth: 6.1 mm
 - Maximum Operating Temperature: +60 °C



2125499 RS PRO

DC SWITCHING 200 VOLT 20A PANEL MOUNT SS

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Minimum Load Current: 5 mA
 - Maximum Load Current: 20 A
 - Series: RMID
 - Mounting Type: Panel Mount
 - Minimum Load Voltage: 1 V ac/dc
 - Maximum Load Voltage: 200 V ac/dc
 - Switching Type: DC Switching
 - Contact Configuration: SPNO



2303311 5 mA

RS PRO DIN RAIL SOLID STATE RELAY, 2 A MAX. LOAD, 264 V MAX. LOAD, 30

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Minimum Load Current: 5 mA
 - Maximum Load Current: 2 A
 - Mounting Type: DIN Rail
 - Minimum Load Voltage: 20 V
 - Maximum Load Voltage: 264 V
 - Minimum Control Voltage: 11 V
 - Maximum Control Voltage: 30 V
 - Switching Type: AC



8886855 5 mA

RS PRO DIN RAIL SOLID STATE RELAY, 2 A MAX. LOAD, 30 V MAX. LOAD, 30 V

- ขนาดบรรจุภัณฑ์: 5 x EA
- Minimum Load Current: 1 mA
 - Maximum Load Current: 2 A
 - Mounting Type: DIN Rail
 - Minimum Load Voltage: 10 V
 - Maximum Load Voltage: 30 V
 - Minimum Control Voltage: 11 V
 - Maximum Control Voltage: 130 V
 - Switching Type: DC



8886859 1 mA

RS PRO DIN RAIL SOLID STATE RELAY, 5 A MAX. LOAD, 30 V MAX. LOAD, 30 V

- ขนาดบรรจุภัณฑ์: 5 x EA
- Minimum Load Current: 1 mA
 - Maximum Load Current: 5 A
 - Mounting Type: DIN Rail
 - Minimum Load Voltage: 10 V
 - Maximum Load Voltage: 30 V
 - Minimum Control Voltage: 11 V
 - Maximum Control Voltage: 30 V
 - Switching Type: DC



8886868 1 mA

RS PRO DIN RAIL SOLID STATE RELAY, 2 A MAX. LOAD, 264 V MAX. LOAD, 30 V

- ขนาดบรรจุภัณฑ์: 5 x EA
- Minimum Load Current: 5 mA
 - Maximum Load Current: 2 A
 - Mounting Type: DIN Rail
 - Minimum Load Voltage: 20 V
 - Maximum Load Voltage: 264 V
 - Minimum Control Voltage: 11 V
 - Maximum Control Voltage: 30 V
 - Switching Type: AC



8886922 5 mA

RS PRO DIN RAIL SOLID STATE RELAY, 5 A MAX. LOAD, 30 V MAX. LOAD, 30 V

- ขนาดบรรจุภัณฑ์: 5 x EA
- Minimum Load Current: 1 mA
 - Maximum Load Current: 5 A
 - Mounting Type: DIN Rail
 - Minimum Load Voltage: 10 V
 - Maximum Load Voltage: 30 V
 - Minimum Control Voltage: 11 V
 - Maximum Control Voltage: 30 V
 - Switching Type: DC



8886934 1 mA

RS PRO DIN RAIL SOLID STATE RELAY, 3 A MAX. LOAD, 30 V MAX. LOAD, 230 V

- ขนาดบรรจุภัณฑ์: 5 x EA
- Minimum Load Current: 1 mA
 - Maximum Load Current: 3 A
 - Mounting Type: DIN Rail
 - Minimum Load Voltage: 10 V
 - Maximum Load Voltage: 30 V
 - Minimum Control Voltage: 110 V
 - Maximum Control Voltage: 230 V
 - Switching Type: DC



8886938 1 mA

OPTOCOUPLER, 100MA DC, DIN, 5-30VDC

- ขนาดบรรจุภัณฑ์: 1 x EA
- Series: RS PRO
 - Mounting Type: DIN Rail
 - Dimensions: 60.8 x 67.5 x 6.1 mm
 - Operating Temperature Range: -25 → +60 °C
 - Minimum Operating Temperature: -25 °C
 - Length: 60.8 mm
 - Depth: 6.1 mm
 - Maximum Operating Temperature: +60 °C



9054277 RS PRO

RS PRO DIN RAIL SOLID STATE RELAY

- ขนาดบรรจุภัณฑ์: 1 x EA
- Series: RS PRO
 - Mounting Type: DIN Rail
 - Dimensions: 61.7 x 91 x 6.2 mm
 - Operating Temperature Range: -25 → +60 °C
 - Minimum Operating Temperature: -25 °C
 - Length: 61.7 mm
 - Depth: 6.2 mm
 - Maximum Operating Temperature: +60 °C



9054302 RS PRO

MULTIFUNCTION TIMER

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 12 → 230 V ac/dc
 - Mounting Type: DIN Rail
 - Time Range: 0.1 s → 100 h
 - Mode of Operation: Multifunction
 - Number of Timer Functions: Multi Function
 - Contact Configuration: SPDT
 - Time Increment: Hours, Seconds
 - Maximum Voltage: 230 V



1026122 12 → 230 V ac/dc

TWO POLE MULTIFUNCTION TIMER

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 12 → 230 V ac/dc
 - Mounting Type: DIN Rail
 - Time Range: 0.1 s → 100 h
 - Mode of Operation: Multifunction
 - Number of Timer Functions: Multi Function
 - Contact Configuration: DPDT
 - Time Increment: Hours, Seconds
 - Maximum Voltage: 230 V



1026123 12 → 230 V ac/dc

RS PRO DIN RAIL MULTI FUNCTION TIMER RELAY, 12 → 230V AC/DC,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 12 → 230 V ac/dc
 - Mounting Type: DIN Rail
 - Time Range: 0.1 s → 100 h
 - Mode of Operation: ON Delay
 - Number of Timer Functions: Multi Function
 - Contact Configuration: SPDT
 - Time Increment: Hours, Seconds
 - Maximum Voltage: 230 V



1026124 12 → 230 V ac/dc

RS PRO DIN RAIL MULTI FUNCTION TIMER RELAY, 12 → 230V AC/DC,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 12 → 230 V ac/dc
 - Mounting Type: DIN Rail
 - Time Range: 0.1 s → 100 h
 - Mode of Operation: ON Delay
 - Number of Timer Functions: Multi Function
 - Contact Configuration: DPDT
 - Time Increment: Hours, Seconds
 - Maximum Voltage: 230 V



1026125 12 → 230 V ac/dc

RS PRO DIN RAIL MULTI FUNCTION TIMER RELAY, 12 → 230V AC/DC,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 12 → 230 V ac/dc
 - Mounting Type: DIN Rail
 - Time Range: 0.1 s → 100 h
 - Number of Timer Functions: Multi Function
 - Contact Configuration: SPDT
 - Time Increment: Hours, Seconds
 - Maximum Voltage: 230 V
 - Maximum Current: 8 A



1026127 12 → 230 V ac/dc

DELAY OFF TIMER (SWITCH INITIATED)

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 12 → 230 V ac/dc
 - Mounting Type: DIN Rail
 - Time Range: 0.1 s → 100 h
 - Number of Timer Functions: Multi Function
 - Contact Configuration: SPDT
 - Time Increment: Hours, Seconds
 - Maximum Voltage: 230 V
 - Maximum Current: 8 A



1026128 12 → 230 V ac/dc

RS PRO DIN RAIL MULTI FUNCTION TIMER RELAY, 12 → 230V AC/DC,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 12 → 230 V ac/dc
 - Mounting Type: DIN Rail
 - Time Range: 0.1 s → 100 h
 - Number of Timer Functions: Multi Function
 - Contact Configuration: SPDT
 - Time Increment: Hours, Seconds
 - Maximum Voltage: 230 V
 - Maximum Current: 8 A



1026129 12 → 230 V ac/dc

RS PRO ROTATING BEACON, 12 V DC, 24 V DC, SURFACE MOUNT,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 12 V dc, 24 V dc
 - Light Effect: Rotating
 - Mounting Style: Surface Mount
 - Bulb Type: Incandescent
 - Current Type: DC
 - Base Diameter: 166 mm
 - Housing Colour: Black
 - Lamp Included: Yes



236284 12 V dc, 24 V dc

XENON SP 10-100VDC/20-72VAC 2W RED

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 10 → 100 V dc, 20 → 72 V ac
 - Light Effect: Flashing
 - Lens Colour: Red
 - Mounting Style: Surface Mount, Wall Mount
 - Bulb Type: Xenon
 - Current Type: AC, DC
 - Current Consumption: 130 mA
 - Base Diameter: 72 mm



1879642 10 → 100 V dc, 20

XENON SP 10-100VDC/20-72VAC 2W AMBER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 10 → 100 V dc, 20 → 72 V ac
 - Light Effect: Flashing
 - Lens Colour: Amber
 - Mounting Style: Surface Mount, Wall Mount
 - Bulb Type: Xenon
 - Current Type: AC, DC
 - Current Consumption: 130 mA
 - Base Diameter: 72 mm



1879643 10 → 100 V dc, 20

XENON LP 10-100VDC/20-72VAC 2W RED

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 10 → 100 V dc, 20 → 72 V ac
 - Light Effect: Flashing
 - Lens Colour: Red
 - Mounting Style: Stud Mount, Surface Mount
 - Bulb Type: Xenon
 - Current Consumption: 110 mA
 - Current Type: AC, DC
 - Base Diameter: 76 mm



1879651 10 → 100 V dc, 20

XENON LP 18-30VDC 1W AMBER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 18 → 30 V dc
 - Light Effect: Flashing
 - Lens Colour: Amber
 - Mounting Style: Stud Mount, Surface Mount
 - Bulb Type: Xenon
 - Current Consumption: 40 mA
 - Current Type: DC
 - Base Diameter: 76 mm



1879652 18 → 30 V dc

XENON LP 18-30VDC 1W RED

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 18 → 30 V dc
 - Light Effect: Flashing
 - Lens Colour: Red
 - Mounting Style: Stud Mount, Surface Mount
 - Bulb Type: Xenon
 - Current Consumption: 40 mA
 - Current Type: DC
 - Base Diameter: 76 mm



1879653 18 → 30 V dc

XENON LP 10-100VDC/20-72VAC 2W AMBER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 10 → 100 V dc, 20 → 72 V ac
 - Light Effect: Flashing
 - Lens Colour: Amber
 - Mounting Style: Stud Mount, Surface Mount
 - Bulb Type: Xenon
 - Current Consumption: 110 mA
 - Current Type: AC, DC
 - Base Diameter: 76 mm



1879654 10 → 100 V dc, 20

RS PRO RED STEADY BEACON, 12 V DC, LED BULB, IP67

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 12 V dc
 - Light Effect: Steady
 - Lens Colour: Red
 - Bulb Type: LED
 - Current Type: DC
 - Housing Colour: Red
 - Lamp Included: Yes
 - Height: 16 mm



1902923 12 V dc

RS PRO RED STEADY BEACON, 24 V DC, LED BULB, IP67

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 24 V dc
 - Light Effect: Steady
 - Lens Colour: Red
 - Bulb Type: LED
 - Current Type: DC
 - Housing Colour: Red
 - Lamp Included: Yes
 - Height: 16 mm



1902924 24 V dc

RS PRO GREEN STEADY BEACON, 24 VDC, SCREW MOUNT, LED BULB, IP66

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 24 Vdc
 - Light Effect: Steady
 - Lens Colour: Green
 - Mounting Style: Screw Mount
 - Bulb Type: LED
 - Current Consumption: 40 mA
 - Base Diameter: 70 mm
 - Housing Colour: White



1999729 24 Vdc

RS PRO BLUE STEADY BEACON, 24 VDC, SCREW MOUNT, LED BULB, IP66

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 24 Vdc
 - Light Effect: Steady
 - Lens Colour: Blue
 - Mounting Style: Screw Mount
 - Bulb Type: LED
 - Current Consumption: 40 mA
 - Base Diameter: 70 mm
 - Housing Colour: White



1999731 24 Vdc

RS PRO RED STEADY BEACON, 24 VDC, SCREW MOUNT, LED BULB, IP66

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 24 Vdc
 - Light Effect: Steady
 - Lens Colour: Red
 - Mounting Style: Screw Mount
 - Bulb Type: LED
 - Current Consumption: 40 mA
 - Base Diameter: 70 mm
 - Housing Colour: White



1999733 24 Vdc

RS PRO RED MULTIPLE EFFECT BEACON, 12 V AC/DC, 24 V AC/DC,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 12 V ac/dc, 24 V ac/dc
 - Light Effect: Flashing, Rotating, Steady
 - Lens Colour: Red
 - Mounting Style: Base Mount
 - Bulb Type: LED
 - Current Type: AC, DC
 - Series: M-LINE FLR



1999763 12 V ac/dc, 24 V

RS PRO AMBER MULTIPLE EFFECT BEACON, 12 V AC/DC, 24 V AC/DC,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 12 V ac/dc, 24 V ac/dc
 - Light Effect: Flashing, Rotating, Steady
 - Lens Colour: Amber
 - Mounting Style: Base Mount
 - Bulb Type: LED
 - Current Type: AC, DC
 - Series: M-LINE FLR



1999764 12 V ac/dc, 24 V

RS PRO GREEN MULTIPLE EFFECT BEACON, 12 V AC/DC, 24 V AC/DC,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 12 V ac/dc, 24 V ac/dc
 - Light Effect: Flashing, Rotating, Steady
 - Lens Colour: Green
 - Mounting Style: Base Mount
 - Bulb Type: LED
 - Current Type: AC, DC
 - Series: M-LINE FLR



1999766 12 V ac/dc, 24 V

LED BEACON, AMBER, DUAL VOLTAGE, 12/24V

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 12 V dc, 24 V dc
 - Light Effect: Flashing
 - Lens Colour: Amber
 - Mounting Style: Surface Mount, Wall Mount
 - Bulb Type: LED
 - Current Consumption: 350 mA
 - Current Type: DC
 - Housing Colour: Black



9075955 12 V dc, 24 V dc

LED BEACON, RED, DUAL VOLTAGE, 12/24V

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 12 V dc, 24 V dc
 - Light Effect: Flashing
 - Lens Colour: Red
 - Mounting Style: Surface Mount, Wall Mount
 - Bulb Type: LED
 - Current Consumption: 350 mA
 - Current Type: DC
 - Housing Colour: Black

**9075959** 12 V dc, 24 V dc**LED BEACON, AMBER, LOW PROF, 10-100VDC**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 10 → 100 V dc
 - Light Effect: Flashing
 - Lens Colour: Amber
 - Mounting Style: Screw Mount
 - Bulb Type: LED
 - Current Type: DC
 - Base Diameter: 77 mm
 - Housing Colour: Black

**9075961** 10 → 100 V dc**LED BEACON, RED, LOW PROF, 10-100VDC**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 10 → 100 V dc
 - Light Effect: Flashing
 - Lens Colour: Red
 - Mounting Style: Screw Mount
 - Bulb Type: LED
 - Current Type: DC
 - Base Diameter: 77 mm
 - Housing Colour: Black

**9075965** 10 → 100 V dc**RS PRO GREEN FLASHING LIGHT MODULE, 12 V DC, 24 V DC, SURFACE**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 12 V dc, 24 V dc
 - Light Effect: Flashing
 - Lens Colour: Green
 - Mounting Style: Surface Mount, Wall Mount
 - Bulb Type: LED
 - Current Consumption: 350 mA
 - Current Type: DC
 - Housing Colour: Black

**9075968** 12 V dc, 24 V dc**RS PRO GREEN FLASHING BEACON, 10 → 100 V DC, SCREW MOUNT, LED**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 10 → 100 V dc
 - Light Effect: Flashing
 - Lens Colour: Green
 - Mounting Style: Screw Mount
 - Bulb Type: LED
 - Current Type: DC
 - Base Diameter: 77 mm
 - Housing Colour: Black

**9075974** 10 → 100 V dc**RS PRO AMBER FLASHING BEACON, 10 → 100 V DC, SCREW MOUNT, LED**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 10 → 100 V dc
 - Light Effect: Flashing
 - Lens Colour: Amber
 - Mounting Style: Screw Mount
 - Bulb Type: LED
 - Current Type: DC
 - Base Diameter: 77 mm
 - Housing Colour: Black

**9075980** 10 → 100 V dc**LED BEACON, RED, TALL PROF, 10-100VDC**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 10 → 100 V dc
 - Light Effect: Flashing
 - Lens Colour: Red
 - Mounting Style: Screw Mount
 - Bulb Type: LED
 - Current Type: DC
 - Base Diameter: 77 mm
 - Housing Colour: Black

**9075983** 10 → 100 V dc**RS PRO AMBER FLASHING BEACON, 10 → 100 V DC, MAGNETIC MOUNT, LED**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 10 → 100 V dc
 - Light Effect: Flashing
 - Lens Colour: Amber
 - Mounting Style: Magnetic Mount
 - Bulb Type: LED
 - Current Consumption: 300 mA, 600 mA
 - Current Type: DC
 - Base Diameter: 150 mm

**9075993** 10 → 100 V dc**RS PRO AMBER FLASHING BEACON, 10 → 100 V DC, FLEXI DIN MOUNT, LED**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 10 → 100 V dc
 - Light Effect: Flashing
 - Lens Colour: Amber
 - Mounting Style: Flexi DIN Mount
 - Bulb Type: LED
 - Current Consumption: 300 mA, 600 mA
 - Current Type: DC
 - Base Diameter: 108 mm

**9076003** 10 → 100 V dc**RS PRO RED FLASHING BEACON, 10 → 100 V DC, MAGNETIC MOUNT, LED**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 10 → 100 V dc
 - Light Effect: Flashing
 - Lens Colour: Red
 - Mounting Style: Magnetic Mount
 - Bulb Type: LED
 - Current Consumption: 300 mA, 600 mA
 - Current Type: DC
 - Base Diameter: 150 mm

**9076006** 10 → 100 V dc**RS PRO GREEN FLASHING BEACON, 10 → 100 V DC, MAGNETIC MOUNT, LED**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 10 → 100 V dc
 - Light Effect: Flashing
 - Lens Colour: Green
 - Mounting Style: Magnetic Mount
 - Bulb Type: LED
 - Current Consumption: 300 mA, 600 mA
 - Current Type: DC
 - Base Diameter: 150 mm

**9076009** 10 → 100 V dc**RS PRO RED FLASHING BEACON, 10 → 100 V DC, FLEXI DIN MOUNT, LED**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 10 → 100 V dc
 - Light Effect: Flashing
 - Lens Colour: Red
 - Mounting Style: Flexi DIN Mount
 - Bulb Type: LED
 - Current Consumption: 300 mA, 600 mA
 - Current Type: DC
 - Base Diameter: 108 mm

**9076012** 10 → 100 V dc**RS PRO AMBER FLASHING BEACON, 10 → 100 V DC, DIN MOUNT, TUBE**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 10 → 100 V dc
 - Light Effect: Flashing
 - Lens Colour: Amber
 - Mounting Style: DIN Mount, Tube Mount
 - Bulb Type: LED
 - Current Type: DC
 - Current Consumption: 300 mA, 600 mA
 - Base Diameter: 108 mm

**9076019** 10 → 100 V dc**RS PRO GREEN FLASHING BEACON, 10 → 100 V DC, DIN MOUNT, TUBE**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 10 → 100 V dc
 - Light Effect: Flashing
 - Lens Colour: Green
 - Mounting Style: DIN Mount, Tube Mount
 - Bulb Type: LED
 - Current Consumption: 300 mA, 600 mA
 - Current Type: DC
 - Base Diameter: 108 mm

**9076021** 10 → 100 V dc**RS PRO AMBER FLASHING BEACON, 10 → 100 V DC, SURFACE MOUNT, LED**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 10 → 100 V dc
 - Light Effect: Flashing
 - Lens Colour: Amber
 - Mounting Style: Surface Mount, Wall Mount
 - Bulb Type: LED
 - Current Consumption: 300 mA, 600 mA
 - Current Type: DC
 - Base Diameter: 150 mm

**9076025** 10 → 100 V dc**RS PRO RED FLASHING BEACON, 10 → 100 V DC, DIN MOUNT, TUBE MOUNT, LED**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 10 → 100 V dc
 - Light Effect: Flashing
 - Lens Colour: Red
 - Mounting Style: DIN Mount, Tube Mount
 - Bulb Type: LED
 - Current Consumption: 300 mA, 600 mA
 - Current Type: DC
 - Base Diameter: 108 mm

**9076028** 10 → 100 V dc

RS PRO AMBER FLASHING BEACON, 10 → 100 V DC, SINGLE POINT MOUNT,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 10 → 100 V dc
 - Light Effect: Flashing
 - Lens Colour: Amber
 - Mounting Style: Single Point Mount
 - Bulb Type: LED
 - Current Consumption: 300 mA, 600 mA
 - Current Type: DC
 - Base Diameter: 108 mm



9076031 10 → 100 V dc

RS PRO RED FLASHING BEACON, 10 → 100 V DC, SURFACE MOUNT, WALL

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 10 → 100 V dc
 - Light Effect: Flashing
 - Lens Colour: Red
 - Mounting Style: Surface Mount, Wall Mount
 - Bulb Type: LED
 - Current Consumption: 300 mA, 600 mA
 - Current Type: DC
 - Base Diameter: 150 mm



9076034 10 → 100 V dc

RS PRO GREEN FLASHING BEACON, 10 → 100 V DC, SURFACE MOUNT,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 10 → 100 V dc
 - Light Effect: Flashing
 - Lens Colour: Green
 - Mounting Style: Surface Mount, Wall Mount
 - Bulb Type: LED
 - Current Consumption: 300 mA, 600 mA
 - Current Type: DC
 - Base Diameter: 150 mm



9076037 10 → 100 V dc

RS PRO RED FLASHING BEACON, 10 → 100 V DC, SINGLE POINT MOUNT, LED

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 10 → 100 V dc
 - Light Effect: Flashing
 - Lens Colour: Red
 - Mounting Style: Single Point Mount
 - Bulb Type: LED
 - Current Type: DC
 - Current Consumption: 300 mA, 600 mA
 - Base Diameter: 108 mm



9076040 10 → 100 V dc

RS PRO GREEN FLASHING BEACON, 10 → 100 V DC, SINGLE POINT MOUNT,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 10 → 100 V dc
 - Light Effect: Flashing
 - Lens Colour: Green
 - Mounting Style: Single Point Mount
 - Bulb Type: LED
 - Current Consumption: 300 mA, 600 mA
 - Current Type: DC
 - Base Diameter: 108 mm



9076043 10 → 100 V dc

RS PRO AMBER FLASHING BEACON, 10 → 30 V DC, FLEXI DIN MOUNT, LED

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 10 → 30 V dc
 - Light Effect: Flashing
 - Lens Colour: Amber
 - Mounting Style: Flexi DIN Mount
 - Bulb Type: LED
 - Current Consumption: 1.3 A, 2 A
 - Current Type: DC
 - Base Diameter: 137 mm



9076047 10 → 30 V dc

RS PRO AMBER FLASHING BEACON, 10 → 30 V DC, SURFACE MOUNT,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 10 → 30 V dc
 - Light Effect: Flashing
 - Lens Colour: Amber
 - Mounting Style: Surface Mount, Wall Mount
 - Bulb Type: LED
 - Current Consumption: 1.3 A, 2 A
 - Current Type: DC
 - Base Diameter: 150 mm



9076056 10 → 30 V dc

RS PRO BLACK SINGLE-TONE ELECTRONIC SOUNDER, 12 → 80 V DC,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 12 → 80 V dc
 - Decibels at 1 Metre: 97 dB
 - Current Type: DC
 - Number Of Tones: 1
 - Housing Colour: Black
 - Mounting Style: Universal
 - Application Type: Sounder
 - Maximum Decibel: 97 dB



235354 12 → 80 V dc

RS PRO BLACK SINGLE-TONE ELECTRONIC SOUNDER, 12 → 80 V DC,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 12 → 80 V dc
 - Decibels at 1 Metre: 107 dB
 - Current Type: DC
 - Number Of Tones: 1
 - Housing Colour: Black
 - Mounting Style: Universal
 - Application Type: Sounder
 - Maximum Decibel: 107 dB



235360 12 → 80 V dc

RS PRO BLACK SINGLE-TONE ELECTRONIC SOUNDER, 12 → 80 V DC,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 12 → 80 V dc
 - Decibels at 1 Metre: 97 dB
 - Current Type: DC
 - Number Of Tones: 1
 - Housing Colour: Black
 - Mounting Style: Universal
 - Application Type: Sounder
 - Maximum Decibel: 97 dB



235405 12 → 80 V dc

RS PRO BLACK SINGLE-TONE ELECTRONIC SOUNDER, 12 → 80 V DC,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 12 → 80 V dc
 - Decibels at 1 Metre: 107 dB
 - Current Type: DC
 - Number Of Tones: 1
 - Housing Colour: Black
 - Mounting Style: Universal
 - Application Type: Sounder
 - Maximum Decibel: 107 dB



235411 12 → 80 V dc

RS PRO RED 8-TONE ELECTRONIC SOUNDER, 10 → 30 V DC, CONDUIT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 10 → 30 V dc
 - IP Rating: IP54, IP65
 - Current Type: DC
 - Number Of Tones: 8
 - Housing Colour: Red
 - Mounting Style: Conduit Box, Panel Mount, Surface Mount
 - Diameter: 101 mm
 - Application Type: Sounder



1145945 10 → 30 V dc

RS PRO RED SINGLE-TONE ELECTRONIC SOUNDER, 24 V, 114DB

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 24 V
 - Decibels at 1 Metre: 114 dB
 - Current Type: DC
 - Number Of Tones: 1
 - Housing Colour: Red
 - Application Type: Sounder
 - Series: superCELERE



1999748 24 V

RS PRO RED SINGLE-TONE SIREN, 24 V, 114dB AT 1 METRE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 24 V
 - Decibels at 1 Metre: 114 dB
 - Current Type: AC, DC
 - Number Of Tones: 1
 - Housing Colour: Red
 - Application Type: Sounder
 - Series: superCELERE



1999750 24 V

RS PRO GREY SINGLE-TONE SIREN, 24 V, 96DB AT 1 METRE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 24 V
 - Decibels at 1 Metre: 96 dB
 - Current Type: DC
 - Number Of Tones: 1
 - Housing Colour: Grey
 - Application Type: Sounder
 - Maximum Decibel: 93 dB
 - Series: MICRO W10



1999752 24 V

RS PRO RED ELECTRONIC SOUNDER, 24 V, 114dB AT 1 METRE, IP44

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 24 V
 - IP Rating: IP44
 - Decibels at 1 Metre: 114 dB
 - Current Type: DC
 - Housing Colour: Red
 - Application Type: Sounder



1999770 24 V

RS PRO 95DB PANEL MOUNT BUZZER, 10V DC MIN, 20V DC MAX

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Mounting Type: Panel Mount
 - Minimum Supply Voltage: 10 V dc
 - Maximum Supply Voltage: 20 V dc
 - Sound Level: 95 dB



2262981 Panel Mount

RS PRO 95DB PANEL MOUNT BUZZER, 130V AC MIN, 240V AC MAX

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Mounting Type: Panel Mount
 - Minimum Supply Voltage: 130 V ac
 - Maximum Supply Voltage: 240 V ac
 - Sound Level: 95 dB



2262982 Panel Mount

RS PRO 95DB PANEL MOUNT BUZZER, 10V DC MIN, 28V DC MAX

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Mounting Type: Panel Mount
 - Minimum Supply Voltage: 10 V dc
 - Maximum Supply Voltage: 28 V dc
 - Sound Level: 95 dB



2262983 Panel Mount

RS PRO RED/GREEN LED BEACON, 2 LIGHTS, 24 V DC, SURFACE MOUNT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Series: LED-TLM
 - Number of Light Elements: 2
 - Lens Colour: Red/Green
 - Bulb Type: LED
 - LED Colour: Red/Green
 - Light Effect: Steady
 - Multifunction: Yes
 - Mounting Style: Surface Mount



1445948 LED-TLM

RS PRO RED/GREEN/AMBER LED BEACON, 3 LIGHTS, 24 V DC,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Series: LED-TLM
 - Number of Light Elements: 3
 - Lens Colour: Red/Green/Amber
 - Bulb Type: LED
 - LED Colour: Amber, Green, Red
 - Light Effect: Steady
 - Multifunction: Yes
 - Mounting Style: Surface Mount



1445949 LED-TLM

RS PRO RED/GREEN SIGNAL TOWER, 24 V AC/DC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Lens Colour: Red/Green
 - Bulb Type: LED
 - Light Effect: Steady
 - Height: 193 mm
 - Base Diameter: 100 mm
 - Supply Voltage: 24 V ac/dc
 - IP Rating: IP66
 - Maximum Temperature: +50 °C



1902805 Red/Green

RS PRO RED/GREEN/AMBER SIGNAL TOWER, 24 V AC/DC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Lens Colour: Red/Green/Amber
 - Bulb Type: LED
 - Light Effect: Steady
 - Height: 228 mm
 - Base Diameter: 100 mm
 - Supply Voltage: 24 V ac/dc
 - IP Rating: IP66
 - Maximum Temperature: +50 °C



1902807 Red/Green/Amber

RS PRO RED/GREEN SIGNAL TOWER, 24 V AC/DC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Lens Colour: Red/Green
 - Bulb Type: LED
 - Light Effect: Flashing, Steady
 - Multifunction: Yes
 - Height: 190 mm
 - Base Diameter: 48 mm
 - IP Rating: IP66
 - Supply Voltage: 24 V ac/dc



1902831 Red/Green

RS PRO RED/GREEN/AMBER SIGNAL TOWER, 24 V AC/DC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Lens Colour: Red/Green/Amber
 - Bulb Type: LED
 - Light Effect: Flashing, Steady
 - Multifunction: Yes
 - Height: 237 mm
 - Base Diameter: 48 mm
 - IP Rating: IP66
 - Supply Voltage: 24 V ac/dc



1902834 Red/Green/Amber

RS PRO RED/GREEN SIGNAL TOWER, 24 V AC/DC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Lens Colour: Red/Green
 - Bulb Type: LED
 - Light Effect: Steady
 - Height: 200 mm
 - Base Diameter: 68 mm
 - Supply Voltage: 24 V ac/dc
 - IP Rating: IP66
 - Maximum Temperature: +50 °C



1902859 Red/Green

RS PRO SIGNAL TOWER, 2 LIGHTS, 24 V

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Series: BABY TWS
 - Number of Light Elements: 2
 - Bulb Type: LED
 - Sounder Component: No Sounder Component
 - Supply Voltage: 24 V



1999758 BABY TWS

RS PRO SIGNAL TOWER, 3 LIGHTS, 24 V

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Series: BABY TWS
 - Number of Light Elements: 3
 - Bulb Type: LED
 - Sounder Component: No Sounder Component
 - Supply Voltage: 24 V



1999760 BABY TWS

RS PRO STEADY EFFECT BASE, 24 V AC/DC, AC, DC, IP66

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Component Type: Steady Light Connection Base
 - Multifunction: Yes
 - Current Type: AC, DC
 - Light Effect: Steady
 - Supply Voltage: 24 V ac/dc
 - Height: 78 mm
 - Base Diameter: 70 mm
 - IP Rating: IP66



1902813 Steady Light

RS PRO MULTIPLE EFFECT BASE, 24 V AC/DC, AC, DC, IP66

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Component Type: Multi-Function Connection Base
 - Multifunction: Yes
 - Current Type: AC, DC
 - Light Effect: Flashing, Steady
 - Supply Voltage: 24 V ac/dc
 - Height: 78 mm
 - Base Diameter: 70 mm
 - IP Rating: IP66



1902815 Multi-Function

RS PRO AMBER MULTIPLE EFFECT BEACON UNIT, 24 V AC/DC, LED

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Component Type: Beacon
 - Multifunction: Yes
 - Current Type: AC, DC
 - Light Effect: Flashing, Steady
 - Lens Colour: Amber
 - Lamp Included: Yes
 - Bulb Type: LED
 - Supply Voltage: 24 V ac/dc



1902839 Beacon

RS PRO RED MULTIPLE EFFECT BEACON UNIT, 24 V AC/DC, LED

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Component Type: Beacon
 - Multifunction: Yes
 - Current Type: AC, DC
 - Light Effect: Flashing, Steady
 - Lens Colour: Red
 - Lamp Included: Yes
 - Bulb Type: LED
 - Supply Voltage: 24 V ac/dc



1902840 Beacon

RS PRO GREEN MULTIPLE EFFECT BEACON UNIT, 24 V AC/DC, LED

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Component Type: Beacon
 - Multifunction: Yes
 - Current Type: AC, DC
 - Light Effect: Flashing, Steady
 - Lens Colour: Green
 - Lamp Included: Yes
 - Bulb Type: LED
 - Supply Voltage: 24 V ac/dc



1902841 Beacon

RS PRO YELLOW MULTIPLE EFFECT BEACON UNIT, 24 V AC/DC, LED

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Component Type: Beacon
 - Multifunction: Yes
 - Current Type: AC, DC
 - Light Effect: Flashing, Steady
 - Lens Colour: Yellow
 - Lamp Included: Yes
 - Bulb Type: LED
 - Supply Voltage: 24 V ac/dc



1902842 Beacon

RS PRO CLEAR MULTIPLE EFFECT BEACON UNIT, 24 V AC/DC, LED

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Component Type: Beacon
 - Multifunction: Yes
 - Current Type: AC, DC
 - Light Effect: Flashing, Steady
 - Lens Colour: Clear
 - Lamp Included: Yes
 - Bulb Type: LED
 - Supply Voltage: 24 V ac/dc



1902843 Beacon

RS PRO BLUE STEADY EFFECT STEADY LIGHT ELEMENT, 24 V AC/DC, LED

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Component Type: Beacon
 - Current Type: AC, DC
 - Light Effect: Steady
 - Lens Colour: Blue
 - Lamp Included: Yes
 - Bulb Type: LED
 - Supply Voltage: 24 V ac/dc
 - Height: 59 mm



1902872 Beacon

RS PRO AMBER STEADY EFFECT STEADY LIGHT ELEMENT, 24 V AC/DC,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Component Type: Beacon
 - Current Type: AC, DC
 - Light Effect: Steady
 - Lens Colour: Amber
 - Lamp Included: Yes
 - Bulb Type: LED
 - Supply Voltage: 24 V ac/dc
 - Height: 59 mm



1902873 Beacon

RS PRO RED STEADY EFFECT STEADY LIGHT ELEMENT, 24 V AC/DC, LED

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Component Type: Beacon
 - Current Type: AC, DC
 - Light Effect: Steady
 - Lens Colour: Red
 - Lamp Included: Yes
 - Bulb Type: LED
 - Supply Voltage: 24 V ac/dc
 - Height: 59 mm



1902874 Beacon

RS PRO GREEN STEADY EFFECT STEADY LIGHT ELEMENT, 24 V AC/DC,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Component Type: Beacon
 - Current Type: AC, DC
 - Light Effect: Steady
 - Lens Colour: Green
 - Lamp Included: Yes
 - Bulb Type: LED
 - Supply Voltage: 24 V ac/dc
 - Height: 59 mm



1902875 Beacon

RS PRO YELLOW STEADY EFFECT STEADY LIGHT ELEMENT, 24 V AC/DC,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Component Type: Beacon
 - Current Type: AC, DC
 - Light Effect: Steady
 - Lens Colour: Yellow
 - Lamp Included: Yes
 - Bulb Type: LED
 - Supply Voltage: 24 V ac/dc
 - Height: 59 mm



1902876 Beacon

RS PRO CLEAR STEADY EFFECT STEADY LIGHT ELEMENT, 24 V AC/DC,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Component Type: Beacon
 - Current Type: AC, DC
 - Light Effect: Steady
 - Lens Colour: Clear
 - Lamp Included: Yes
 - Bulb Type: LED
 - Supply Voltage: 24 V ac/dc
 - Height: 59 mm



1902877 Beacon

RS PRO AMBER BUZZER BEACON, 12 V DC, 24 V DC, BASE MOUNT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 12 V dc, 24 V dc
 - Lens Colour: Amber
 - Mounting Style: Base Mount
 - Current Type: DC
 - Light Effect: Flashing
 - Series: CPM
 - Bulb Type: LED
 - Maximum Decibel: 96 dB



1999746 12 V dc, 24 V dc

RS PRO SOUNDER BEACON, 24 V, IP44, 114dB AT 1 METRE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 24 V
 - Current Type: DC
 - Decibels at 1 Metre: 114 dB
 - Housing Colour: Red
 - Number Of Tones: 32
 - IP Rating: IP44



1999772 24 V

RS PRO IP56 RATED DIN MOUNTING STEM FOR USE WITH DIN & FLEXI DIN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: DIN Mounting Stem
 - For Use With: DIN & Flexi DIN Beacons
 - IP Rating: IP56



235613 DIN Mounting

130MM HIGH BULB CAGE FOR USE WITH XENON BULB

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Bulb Cage
 - For Use With: Xenon Bulb
 - Dimensions: 130 (H) mm



235691 Bulb Cage

RS PRO HALOGEN CLEAR BULB, P14.5S 24 V

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Bulb
 - Colour: Clear
 - Bulb Type: Halogen
 - Lamp Base: P14.5s
 - Voltage Rating: 24 V
 - Dimensions: 10 x 68 mm



235720 Bulb

RS PRO HALOGEN CLEAR BULB, P14.5S 12 V

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Bulb
 - Colour: Clear
 - Bulb Type: Halogen
 - Lamp Base: P14.5s
 - Voltage Rating: 12 V
 - Dimensions: 10 x 68 mm



235736 Bulb

RS PRO AMBER LENS FOR USE WITH INCANDESCENT BEACONS

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Lens
 - Colour: Amber
 - For Use With: Incandescent Beacons



235792 Lens

RS PRO CLEAR LENS FOR USE WITH XENON BEACONS

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Lens
 - Colour: Clear
 - For Use With: Xenon Beacons



235809 Lens

RS PRO RED LENS FOR USE WITH XENON BEACONS

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Lens
 - Colour: Red
 - For Use With: Xenon Beacons



235815 Lens

RS PRO BLUE LENS FOR USE WITH XENON BEACONS

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Lens
 - Colour: Blue
 - For Use With: Xenon Beacons



236010 Lens

VWD, BEACON, XENON, LENS, AMBER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Lens
 - Colour: Amber
 - For Use With: Xenon Beacons



236032 Lens

RS PRO IP65 RATED RED DEEP BASE FOR USE WITH AE40M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Deep Base
 - Colour: Red
 - For Use With: AE40M
 - IP Rating: IP65
 - Dimensions: 93 [Dia.] x 40 mm



1445947 Deep Base

LED BEACON LAMP, AMBER, PC, 24 V DC, 14 CHIP

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Colour: Amber



1999727 Amber

RS PRO, 8MM GROOVE, SLOT 40 X 40, 2M L

- ขนาดบรรจุภัณฑ์: 1 x EA
- Product Family: RS Structural System
 - Fits Strut Profile: 40 x 40
 - Fits Groove Size: 8 mm
 - Length: 2 m
 - Internal Width: 28 mm
 - Internal Height: 35 mm



8508492 RS Structural

RS PRO, 8MM GROOVE, SLOT 40 X 80, 2M L

- ขนาดบรรจุภัณฑ์: 1 x EA
- Product Family: RS Structural System
 - Fits Strut Profile: 40 x 80
 - Fits Groove Size: 8 mm
 - Length: 2 m
 - Internal Width: 68 mm
 - Internal Height: 35 mm



8508502 RS Structural

RS PRO 2-WAY CONNECTOR CONNECTING COMPONENT, STRUT

- ขนาดบรรจุภัณฑ์: 4 x EA
- Connector Type: 2-Way Connector
 - Structural Element Type: Connector Bracket & Joint
 - Fits Strut Profile: 25 mm
 - Fits Square Tube Profile: 25 mm
 - Product Family: RS Square Tube System
 - Material: Polymer
 - Product System: Versatile Construction System



621691 2-Way Connector

RS PRO 3-WAY CONNECTOR CONNECTING COMPONENT, STRUT

- ขนาดบรรจุภัณฑ์: 4 x EA
- Connector Type: 3-Way Connector
 - Structural Element Type: Connector Bracket & Joint
 - Fits Strut Profile: 25 mm
 - Fits Square Tube Profile: 25 mm
 - Product Family: RS Square Tube System
 - Material: Polymer
 - Product System: Versatile Construction System



621708 3-Way

RS PRO 3-WAY CONNECTOR CONNECTING COMPONENT, STRUT

- ขนาดบรรจุภัณฑ์: 4 x EA
- Connector Type: 3-Way Connector
 - Structural Element Type: Connector Bracket & Joint
 - Fits Strut Profile: 25 mm
 - Fits Square Tube Profile: 25 mm
 - Product Family: RS Square Tube System
 - Material: Polymer
 - Product System: Versatile Construction System



621714 3-Way

RS PRO 4-WAY CONNECTOR CONNECTING COMPONENT, STRUT

- ขนาดบรรจุภัณฑ์: 4 x EA
- Connector Type: 4-Way Connector
 - Structural Element Type: Connector Bracket & Joint
 - Fits Strut Profile: 25 mm
 - Fits Square Tube Profile: 25 mm
 - Product Family: RS Square Tube System
 - Material: Polymer
 - Product System: Versatile Construction System



621720 4-Way

RS PRO 4-WAY CONNECTOR CONNECTING COMPONENT, STRUT

- ขนาดบรรจุภัณฑ์: 4 x EA
- Connector Type: 4-Way Connector
 - Structural Element Type: Connector Bracket & Joint
 - Fits Strut Profile: 25 mm
 - Fits Square Tube Profile: 25 mm
 - Product Family: RS Square Tube System
 - Material: Polymer
 - Product System: Versatile Construction System



621736 4-Way

RS PRO 5-WAY CONNECTOR CONNECTING COMPONENT, STRUT

- ขนาดบรรจุภัณฑ์: 4 x EA
- Connector Type: 5-Way Connector
 - Structural Element Type: Connector Bracket & Joint
 - Fits Strut Profile: 25 mm
 - Fits Square Tube Profile: 25 mm
 - Product Family: RS Square Tube System
 - Material: Polymer
 - Product System: Versatile Construction System



621742 5-Way

RS PRO SHELF CLIP CONNECTING COMPONENT, STRUT PROFILE 25 MM

- ขนาดบรรจุภัณฑ์: 12 x EA
- Connector Type: Shelf Clip
 - Structural Element Type: Connector Bracket & Joint
 - Fits Strut Profile: 25 mm
 - Fits Square Tube Profile: 25 mm
 - Product Family: RS Square Tube System
 - Material: Steel
 - Product System: Versatile Construction System



621792 Shelf Clip

RS PRO T-SLOT NUT CONNECTING COMPONENT, STRUT PROFILE 20 MM,

- ขนาดบรรจุภัณฑ์: 10 x EA
- Connector Type: T-Slot Nut
 - Structural Element Type: Fixing & Connection Element
 - Fits Groove Size: 5 mm
 - Thread Size: M3
 - Length: 12 mm
 - Fits Strut Profile: 20 mm
 - Product Family: RS Structural System
 - Material: Steel



1809102 T-Slot Nut

RS PRO T-SLOT NUT CONNECTING COMPONENT, STRUT PROFILE 20 MM,

- ขนาดบรรจุภัณฑ์: 10 x EA
- Connector Type: T-Slot Nut
 - Structural Element Type: Fixing & Connection Element
 - Fits Groove Size: 5 mm
 - Thread Size: M4
 - Length: 12 mm
 - Fits Strut Profile: 20 mm
 - Product Family: RS Structural System
 - Material: Steel



1809103 T-Slot Nut

RS PRO T-SLOT NUT CONNECTING COMPONENT, STRUT PROFILE 20 MM,

- ขนาดบรรจุภัณฑ์: 10 x EA
- Connector Type: T-Slot Nut
 - Structural Element Type: Fixing & Connection Element
 - Fits Groove Size: 5 mm
 - Thread Size: M5
 - Length: 12 mm
 - Fits Strut Profile: 20 mm
 - Product Family: RS Structural System
 - Material: Steel



1809104 T-Slot Nut

RS PRO T-SLOT NUT CONNECTING COMPONENT, STRUT PROFILE 20 MM,

- ขนาดบรรจุภัณฑ์: 10 x EA
- Connector Type: T-Slot Nut
 - Structural Element Type: Fixing & Connection Element
 - Fits Groove Size: 5 mm
 - Thread Size: M3
 - Length: 12 mm
 - Fits Strut Profile: 20 mm
 - Product Family: RS Structural System
 - Material: Steel



1809105 T-Slot Nut

RS PRO T-SLOT NUT CONNECTING COMPONENT, STRUT PROFILE 20 MM,

- ขนาดบรรจุภัณฑ์: 10 x EA
- Connector Type: T-Slot Nut
 - Structural Element Type: Fixing & Connection Element
 - Fits Groove Size: 5 mm
 - Thread Size: M4
 - Length: 12 mm
 - Fits Strut Profile: 20 mm
 - Product Family: RS Structural System
 - Material: Steel



1809106 T-Slot Nut

RS PRO T-SLOT NUT CONNECTING COMPONENT, STRUT PROFILE 20 MM,

- ขนาดบรรจุภัณฑ์: 10 x EA
- Connector Type: T-Slot Nut
 - Structural Element Type: Fixing & Connection Element
 - Fits Groove Size: 5 mm
 - Thread Size: M5
 - Length: 12 mm
 - Fits Strut Profile: 20 mm
 - Product Family: RS Structural System
 - Material: Steel



1809107 T-Slot Nut

RS PRO T-SLOT NUT CONNECTING COMPONENT, STRUT PROFILE 20 MM,

- ขนาดบรรจุภัณฑ์: 10 x EA
- Connector Type: T-Slot Nut
 - Structural Element Type: Fixing & Connection Element
 - Fits Groove Size: 5 mm
 - Thread Size: M4
 - Length: 12 mm
 - Fits Strut Profile: 20 mm
 - Product Family: RS Structural System
 - Material: Stainless Steel



1809108 T-Slot Nut

RS PRO T-SLOT NUT CONNECTING COMPONENT, STRUT PROFILE 20 MM,

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Connector Type: T-Slot Nut
 - Structural Element Type: Fixing & Connection Element
 - Fits Groove Size: 5 mm
 - Thread Size: M5
 - Length: 12 mm
 - Fits Strut Profile: 20 mm
 - Product Family: RS Structural System
 - Material: Stainless Steel


1809109 T-Slot Nut

RS PRO T-SLOT NUT CONNECTING COMPONENT, STRUT PROFILE 20 MM,

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Connector Type: T-Slot Nut
 - Structural Element Type: Fixing & Connection Element
 - Fits Groove Size: 5 mm
 - Thread Size: M4
 - Length: 18 mm
 - Fits Strut Profile: 20 mm
 - Product Family: RS Structural System
 - Material: Steel


1809110 T-Slot Nut

RS PRO T-SLOT NUT CONNECTING COMPONENT, STRUT PROFILE 20 MM,

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Connector Type: T-Slot Nut
 - Structural Element Type: Fixing & Connection Element
 - Fits Groove Size: 5 mm
 - Thread Size: M5
 - Length: 18 mm
 - Fits Strut Profile: 20 mm
 - Product Family: RS Structural System
 - Material: Steel


1809111 T-Slot Nut

RS PRO T-SLOT NUT CONNECTING COMPONENT, STRUT PROFILE 30 MM,

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Connector Type: T-Slot Nut
 - Structural Element Type: Fixing & Connection Element
 - Fits Groove Size: 6 mm
 - Thread Size: M4
 - Length: 17 mm
 - Fits Strut Profile: 30 mm
 - Product Family: RS Structural System
 - Material: Steel


1809114 T-Slot Nut

RS PRO T-SLOT NUT CONNECTING COMPONENT, STRUT PROFILE 30 MM,

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Connector Type: T-Slot Nut
 - Structural Element Type: Fixing & Connection Element
 - Fits Groove Size: 6 mm
 - Thread Size: M6
 - Length: 17 mm
 - Fits Strut Profile: 30 mm
 - Product Family: RS Structural System
 - Material: Steel


1809116 T-Slot Nut

RS PRO T-SLOT NUT CONNECTING COMPONENT, STRUT PROFILE 30 MM,

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Connector Type: T-Slot Nut
 - Structural Element Type: Fixing & Connection Element
 - Fits Groove Size: 6 mm
 - Thread Size: M6
 - Length: 16 mm
 - Fits Strut Profile: 30 mm
 - Product Family: RS Structural System
 - Material: Steel


1809124 T-Slot Nut

RS PRO T-SLOT NUT CONNECTING COMPONENT, STRUT PROFILE 30 MM,

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Connector Type: T-Slot Nut
 - Structural Element Type: Fixing & Connection Element
 - Fits Groove Size: 6 mm
 - Thread Size: M6
 - Length: 16 mm
 - Fits Strut Profile: 30 mm
 - Product Family: RS Structural System
 - Material: Steel


1809127 T-Slot Nut

RS PRO PIVOT JOINT CONNECTING COMPONENT, STRUT PROFILE 20 MM,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Connector Type: Pivot Joint
 - Structural Element Type: Connector Bracket & Joint
 - Fits Groove Size: 5 mm, 6 mm
 - Fits Strut Profile: 20 mm
 - Product Family: RS Structural System
 - Material: Die Cast Aluminium
 - Product System: 20


1809134 Pivot Joint

RS PRO PIVOT JOINT CONNECTING COMPONENT, STRUT PROFILE 20 MM,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Connector Type: Pivot Joint
 - Structural Element Type: Connector Bracket & Joint
 - Fits Groove Size: 5 mm, 6 mm
 - Fits Strut Profile: 20 mm
 - Product Family: RS Structural System
 - Material: Die Cast Aluminium
 - Product System: 20


1809135 Pivot Joint

RS PRO ANGLE BRACKET CONNECTING COMPONENT, STRUT

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Connector Type: Angle Bracket
 - Structural Element Type: Connector Bracket & Joint
 - Fits Groove Size: 5 mm
 - Length: 18 mm
 - Fits Strut Profile: 20 mm
 - Product Family: RS Structural System
 - Material: Die Cast Aluminium
 - Product System: 20


1809136 Angle Bracket

RS PRO ANGLE BRACKET CONNECTING COMPONENT, STRUT

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Connector Type: Angle Bracket
 - Structural Element Type: Connector Bracket & Joint
 - Fits Groove Size: 6 mm
 - Fits Strut Profile: 20 mm
 - Product Family: RS Structural System
 - Material: Die Cast Aluminium
 - Product System: 20


1809137 Angle Bracket

RS PRO ANGLE BRACKET CONNECTING COMPONENT, STRUT

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Connector Type: Angle Bracket
 - Structural Element Type: Connector Bracket & Joint
 - Fits Groove Size: 5 mm
 - Thread Size: M5
 - Length: 18 mm
 - Fits Strut Profile: 20 mm
 - Product Family: RS Structural System
 - Material: Die Cast Zinc


1809138 Angle Bracket

RS PRO 3-WAY CONNECTOR CONNECTING COMPONENT, STRUT

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Connector Type: 3-Way Connector
 - Structural Element Type: Connector Bracket & Joint
 - Fits Groove Size: 5 mm
 - Fits Strut Profile: 20 mm
 - Product Family: RS Structural System
 - Material: Nylon
 - Product System: 20


1809140 3-Way

RS PRO CUBE CONNECTOR CONNECTING COMPONENT, STRUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Connector Type: Cube Connector
 - Structural Element Type: Connector Bracket & Joint
 - Fits Groove Size: 5 mm
 - Fits Strut Profile: 20 mm
 - Product Family: RS Structural System
 - Material: Die Cast Aluminium
 - Product System: 20


1809141 Cube Connector

RS PRO T-SLOT NUT CONNECTING COMPONENT, STRUT PROFILE 40 MM,

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Connector Type: T-Slot Nut
 - Structural Element Type: Fixing & Connection Element
 - Fits Groove Size: 8 mm
 - Thread Size: M8
 - Length: 22 mm
 - Fits Strut Profile: 40 mm
 - Product Family: RS Structural System
 - Material: Steel


2247637 T-Slot Nut

STORAGE, STEEL TUBE FITTING, SHORT TEE, 1IN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Structural Element Type: Round Tube
 - Connector Type: T-Connector
 - Fits Strut Profile: Type 1
 - Fits Tube Diameter: 33.7 mm
 - Product Family: RS Handrail System
 - Material: Cast Iron
 - Product System: 101


2863308 Round Tube

RS PRO T-CONNECTOR CONNECTING COMPONENT, STRUT PROFILE TYPE 2,

ขนาดบรรจุภัณฑ์: 1 x EA

- Connector Type: T-Connector
- Structural Element Type: Connector Bracket & Joint
- Fits Strut Profile: Type 2
- Fits Tube Diameter: 42.4 mm
- Fits Round Tube Size: Type 2
- Product Family: RS Handrail System
- Material: Cast Iron
- Product System: 101



2863314 T-Connector

RS PRO T-CONNECTOR CONNECTING COMPONENT, STRUT PROFILE TYPE 3,

ขนาดบรรจุภัณฑ์: 1 x EA

- Connector Type: T-Connector
- Structural Element Type: Connector Bracket & Joint
- Fits Strut Profile: Type 3
- Fits Tube Diameter: 48.3 mm
- Fits Round Tube Size: Type 3
- Product Family: RS Handrail System
- Material: Cast Iron
- Product System: 101



2863320 T-Connector

RS PRO JOINT CLAMP CONNECTING COMPONENT, STRUT PROFILE TYPE 2,

ขนาดบรรจุภัณฑ์: 1 x EA

- Connector Type: Joint Clamp
- Structural Element Type: Connector Bracket & Joint
- Length: 102 mm
- Fits Strut Profile: Type 2
- Fits Tube Diameter: 42.4 mm
- Fits Round Tube Size: Type 2
- Product Family: RS Handrail System
- Material: Cast Iron



2863358 Joint Clamp

RS PRO JOINT CLAMP CONNECTING COMPONENT, STRUT PROFILE TYPE 3,

ขนาดบรรจุภัณฑ์: 1 x EA

- Connector Type: Joint Clamp
- Structural Element Type: Connector Bracket & Joint
- Length: 100 mm
- Fits Strut Profile: Type 3
- Fits Tube Diameter: 48.3 mm
- Fits Round Tube Size: Type 3
- Product Family: RS Handrail System
- Material: Cast Iron



2863364 Joint Clamp

STORAGE, STEEL TUBE FITTING, ELBOW, 90DEG, 1IN

ขนาดบรรจุภัณฑ์: 1 x EA

- Structural Element Type: Round Tube
- Connector Type: 2-Way Connector
- Fits Strut Profile: Type 1
- Fits Tube Diameter: 33.7 mm
- Fits Round Tube Size: Type 1
- Product Family: RS Handrail System
- Material: Cast Iron
- Product System: 125



2863370 Round Tube

RS PRO 2-WAY CONNECTOR CONNECTING COMPONENT, STRUT

ขนาดบรรจุภัณฑ์: 1 x EA

- Connector Type: 2-Way Connector
- Structural Element Type: Connector Bracket & Joint
- Fits Strut Profile: Type 2
- Fits Tube Diameter: 42.4 mm
- Fits Round Tube Size: Type 2
- Product Family: RS Handrail System
- Material: Cast Iron
- Product System: 125



2863386 2-Way Connector

RS PRO 3-WAY CONNECTOR CONNECTING COMPONENT, STRUT

ขนาดบรรจุภัณฑ์: 1 x EA

- Connector Type: 3-Way Connector
- Structural Element Type: Connector Bracket & Joint
- Fits Strut Profile: Type 1
- Fits Tube Diameter: 33.7 mm
- Fits Round Tube Size: Type 1
- Product Family: RS Handrail System
- Material: Cast Iron
- Product System: 128



2863392 3-Way

RS PRO 3-WAY CONNECTOR CONNECTING COMPONENT, STRUT

ขนาดบรรจุภัณฑ์: 1 x EA

- Connector Type: 3-Way Connector
- Structural Element Type: Connector Bracket & Joint
- Fits Strut Profile: Type 2
- Fits Tube Diameter: 42.4 mm
- Fits Round Tube Size: Type 2
- Product Family: RS Handrail System
- Material: Cast Iron
- Product System: 128



2863409 3-Way

RS PRO 3-WAY CONNECTOR CONNECTING COMPONENT, STRUT

ขนาดบรรจุภัณฑ์: 1 x EA

- Connector Type: 3-Way Connector
- Structural Element Type: Connector Bracket & Joint
- Fits Strut Profile: Type 1
- Fits Tube Diameter: 33.7 mm
- Fits Round Tube Size: Type 1
- Product Family: RS Handrail System
- Material: Cast Iron
- Product System: 116



2863421 3-Way

RS PRO 3-WAY CONNECTOR CONNECTING COMPONENT, STRUT

ขนาดบรรจุภัณฑ์: 1 x EA

- Connector Type: 3-Way Connector
- Structural Element Type: Connector Bracket & Joint
- Fits Strut Profile: Type 2
- Fits Tube Diameter: 42.4 mm
- Fits Round Tube Size: Type 2
- Product Family: RS Handrail System
- Material: Cast Iron
- Product System: 116



2863437 3-Way

STORAGE, STEEL TUBE FITTING, LONG TEE, 1IN

ขนาดบรรจุภัณฑ์: 1 x EA

- Structural Element Type: Round Tube
- Connector Type: T-Connector
- Length: 96 mm
- Fits Strut Profile: Type 1
- Fits Tube Diameter: 33.7 mm
- Fits Round Tube Size: Type 1
- Product Family: RS Handrail System
- Material: Cast Iron
- Product System: 104



2863459 Round Tube

RS PRO T-CONNECTOR CONNECTING COMPONENT, STRUT PROFILE TYPE 2,

ขนาดบรรจุภัณฑ์: 1 x EA

- Connector Type: T-Connector
- Structural Element Type: Connector Bracket & Joint
- Length: 122 mm
- Fits Strut Profile: Type 2
- Fits Tube Diameter: 42.4 mm
- Fits Round Tube Size: Type 2
- Product Family: RS Handrail System
- Material: Cast Iron



2863465 T-Connector

RS PRO 2-WAY CONNECTOR CONNECTING COMPONENT, STRUT

ขนาดบรรจุภัณฑ์: 1 x EA

- Connector Type: 2-Way Connector
- Structural Element Type: Connector Bracket & Joint
- Length: 48 mm
- Fits Strut Profile: Type 1
- Fits Tube Diameter: 33.7 mm
- Fits Round Tube Size: Type 1
- Product Family: RS Handrail System
- Material: Cast Iron



2863487 2-Way Connector

RS PRO 2-WAY CONNECTOR CONNECTING COMPONENT, STRUT

ขนาดบรรจุภัณฑ์: 1 x EA

- Connector Type: 2-Way Connector
- Structural Element Type: Connector Bracket & Joint
- Length: 60 mm
- Fits Strut Profile: Type 2
- Fits Tube Diameter: 42.4 mm
- Fits Round Tube Size: Type 2
- Product Family: RS Handrail System
- Material: Cast Iron



2863500 2-Way Connector

RS PRO SINGLE SWIVEL COMBINATION CONNECTING

ขนาดบรรจุภัณฑ์: 1 x EA

- Connector Type: Single Swivel Combination
- Structural Element Type: Connector Bracket & Joint
- Fits Strut Profile: Type 3
- Fits Tube Diameter: 48.3 mm
- Fits Round Tube Size: Type 3
- Product Family: RS Handrail System
- Material: Cast Iron
- Product System: 173



2863538 Single Swivel

RS PRO ROUND TUBE HANDRAIL BRACKET, STRUT PROFILE TYPE 1,

ขนาดบรรจุภัณฑ์: 1 x EA

- Structural Element Type: Round Tube
- Connector Type: Handrail Bracket
- Fits Strut Profile: Type 1
- Fits Tube Diameter: 33.7 mm
- Product Family: RS Handrail System
- Material: Cast Iron
- Product System: 143



2863689 Round Tube

RS PRO HANDRAIL BRACKET CONNECTING COMPONENT, STRUTขนาดบรรจุภัณฑ์: **1 x EA**

- Connector Type: Handrail Bracket
- Structural Element Type: Connector Bracket & Joint
- Fits Strut Profile: Type 2
- Fits Tube Diameter: 42.4 mm
- Fits Round Tube Size: Type 2
- Product Family: RS Handrail System
- Material: Cast Iron
- Product System: 143

**2863695** Handrail Bracket**RS PRO HANDRAIL BRACKET CONNECTING COMPONENT, STRUT**ขนาดบรรจุภัณฑ์: **1 x EA**

- Connector Type: Handrail Bracket
- Structural Element Type: Connector Bracket & Joint
- Fits Strut Profile: Type 3
- Fits Tube Diameter: 48.3 mm
- Fits Round Tube Size: Type 3
- Product Family: RS Handrail System
- Material: Cast Iron
- Product System: 143

**2863702** Handrail Bracket**RS PRO SINGLE SWIVEL COMBINATION CONNECTING**ขนาดบรรจุภัณฑ์: **1 x EA**

- Connector Type: Single Swivel Combination
- Structural Element Type: Connector Bracket & Joint
- Fits Strut Profile: Type 2
- Fits Tube Diameter: 42.4 mm
- Fits Round Tube Size: Type 2
- Product Family: RS Handrail System
- Material: Cast Iron
- Product System: 173

**2863752** Single Swivel**RS PRO 2-WAY CONNECTOR CONNECTING COMPONENT, STRUT**ขนาดบรรจุภัณฑ์: **1 x EA**

- Connector Type: 2-Way Connector
- Structural Element Type: Connector Bracket & Joint
- Thread Size: M6
- Fits Strut Profile: Type 3
- Fits Tube Diameter: 48.3 mm
- Fits Round Tube Size: Type 3
- Product Family: RS Handrail System
- Material: Cast Iron

**2863954** 2-Way Connector**RS PRO 15 TO 60 DEGREE ELBOW CONNECTING COMPONENT, STRUT**ขนาดบรรจุภัณฑ์: **1 x EA**

- Connector Type: 15 to 60 Degree Elbow
- Structural Element Type: Connector Bracket & Joint
- Fits Strut Profile: Type 2
- Fits Tube Diameter: 42.4 mm
- Fits Round Tube Size: Type 2
- Product Family: RS Handrail System
- Material: Cast Iron
- Product System: 124

**4155980** 15 to 60 Degree**RS PRO T-CONNECTOR CONNECTING COMPONENT, STRUT PROFILE TYPE 1,**ขนาดบรรจุภัณฑ์: **1 x EA**

- Connector Type: T-Connector
- Structural Element Type: Connector Bracket & Joint
- Fits Strut Profile: Type 1
- Fits Tube Diameter: 33.7 mm
- Fits Round Tube Size: Type 1
- Product Family: RS Handrail System
- Material: Cast Iron
- Product System: 129

**4156006** T-Connector**RS PRO ROUND TUBE T-CLAMP, STRUT PROFILE TYPE 2,**ขนาดบรรจุภัณฑ์: **1 x EA**

- Structural Element Type: Round Tube
- Connector Type: T-Clamp
- Fits Strut Profile: Type 2
- Fits Tube Diameter: 42.4 mm
- Fits Round Tube Size: Type 1
- Product Family: RS Handrail System
- Material: Cast Iron
- Product System: 135

**4156078** Round Tube**RS PRO T-CLAMP CONNECTING COMPONENT, STRUT PROFILE TYPE 3,**ขนาดบรรจุภัณฑ์: **1 x EA**

- Connector Type: T-Clamp
- Structural Element Type: Connector Bracket & Joint
- Fits Strut Profile: Type 3
- Fits Tube Diameter: 48.3 mm
- Fits Round Tube Size: Type 3
- Product Family: RS Handrail System
- Material: Cast Iron
- Product System: 135

**4156084** T-Clamp**RS PRO T-CONNECTOR CONNECTING COMPONENT, STRUT PROFILE TYPE 3,**ขนาดบรรจุภัณฑ์: **1 x EA**

- Connector Type: T-Connector
- Structural Element Type: Connector Bracket & Joint
- Fits Strut Profile: Type 3
- Fits Tube Diameter: 48.3 mm
- Fits Round Tube Size: Type 3
- Product Family: RS Handrail System
- Material: Cast Iron
- Product System: 148

**4156214** T-Connector**RS PRO 90° CONNECTOR CONNECTING COMPONENT, STRUT**ขนาดบรรจุภัณฑ์: **1 x EA**

- Connector Type: 90° Connector
- Structural Element Type: Connector Bracket & Joint
- Thread Size: M6, M8
- Fits Strut Profile: Type 1
- Fits Tube Diameter: 33.7 mm
- Fits Round Tube Size: Type 1
- Product Family: RS Handrail System
- Material: Cast Iron

**4156309** 90° Connector**RS PRO 90° CONNECTOR CONNECTING COMPONENT, STRUT**ขนาดบรรจุภัณฑ์: **1 x EA**

- Connector Type: 90° Connector
- Structural Element Type: Connector Bracket & Joint
- Fits Strut Profile: Type 3
- Fits Tube Diameter: 48.3 mm
- Fits Round Tube Size: Type 3
- Product Family: RS Handrail System
- Material: Cast Iron
- Product System: 161

**4156337** 90° Connector**RS PRO T-CLAMP CONNECTING COMPONENT, STRUT PROFILE TYPE 1,**ขนาดบรรจุภัณฑ์: **1 x EA**

- Connector Type: T-Clamp
- Structural Element Type: Connector Bracket & Joint
- Thread Size: M6
- Fits Strut Profile: Type 1
- Fits Tube Diameter: 33.7 mm
- Fits Round Tube Size: Type 1
- Product Family: RS Handrail System
- Material: Cast Iron

**4157021** T-Clamp**RS PRO 4-WAY CONNECTOR CONNECTING COMPONENT, STRUT**ขนาดบรรจุภัณฑ์: **1 x EA**

- Connector Type: 4-Way Connector
- Structural Element Type: Connector Bracket & Joint
- Fits Strut Profile: Type 1
- Fits Tube Diameter: 33.7 mm
- Fits Round Tube Size: Type 1
- Product Family: RS Handrail System
- Material: Cast Iron
- Product System: 158

**4244614** 4-Way**RS PRO T-CONNECTOR CONNECTING COMPONENT, STRUT PROFILE TYPE 1,**ขนาดบรรจุภัณฑ์: **1 x EA**

- Connector Type: T-Connector
- Structural Element Type: Connector Bracket & Joint
- Fits Strut Profile: Type 1
- Fits Tube Diameter: 33.7 mm
- Fits Round Tube Size: Type 1
- Product Family: RS Handrail System
- Material: Cast Iron
- Product System: 176

**4244658** T-Connector**RS PRO CONNECTING CLAMP CONNECTING COMPONENT**ขนาดบรรจุภัณฑ์: **1 x EA**

- Connector Type: Connecting Clamp
- Structural Element Type: Fixing & Connection Element
- Thread Size: M5
- Fits Tube Diameter: 8 mm
- Product Family: Elessa Connecting Clamps
- Material: Aluminium
- Product System: MSM

**7865980** Connecting**RS PRO CONNECTING CLAMP CONNECTING COMPONENT**ขนาดบรรจุภัณฑ์: **1 x EA**

- Connector Type: Connecting Clamp
- Structural Element Type: Connector Bracket & Joint
- Thread Size: M4
- Fits Tube Diameter: 8 mm
- Product Family: Elessa Connecting Clamps
- Material: Aluminium
- Product System: MSM

**7865986** Connecting

**RS PRO CONNECTING CLAMP
CONNECTING COMPONENT**

ขนาดบรรจุภัณฑ์: **1 x EA**

- Connector Type: Connecting Clamp
- Structural Element Type: Fixing & Connection Element
- Thread Size: M6
- Fits Tube Diameter: 16 mm
- Product Family: Elessa Connecting Clamps
- Material: Aluminium
- Product System: MSM



7866144 Connecting

**RS PRO BASE CLAMP CONNECTING
COMPONENT**

ขนาดบรรจุภัณฑ์: **1 x EA**

- Connector Type: Base Clamp
- Structural Element Type: Connector Bracket & Joint
- Thread Size: M6
- Fits Tube Diameter: 20 mm
- Fits Square Tube Profile: 16 mm
- Product Family: Elessa Connecting Clamps
- Material: Aluminium
- Product System: MSM



7866166 Base Clamp

**RS PRO CONNECTING CLAMP
CONNECTING COMPONENT**

ขนาดบรรจุภัณฑ์: **1 x EA**

- Connector Type: Connecting Clamp
- Structural Element Type: Connector Bracket & Joint
- Thread Size: M6
- Fits Tube Diameter: 20 mm
- Fits Square Tube Profile: 16 mm
- Product Family: Elessa Connecting Clamps
- Material: Aluminium
- Product System: MSM



7866169 Connecting

**RS PRO CONNECTING CLAMP
CONNECTING COMPONENT**

ขนาดบรรจุภัณฑ์: **1 x EA**

- Connector Type: Connecting Clamp
- Structural Element Type: Fixing & Connection Element
- Thread Size: M6
- Fits Tube Diameter: 20 mm
- Fits Square Tube Profile: 16 mm
- Product Family: Elessa Connecting Clamps
- Material: Aluminium
- Product System: MSM



7866175 Connecting

RS PRO CONNECTING COMPONENT

ขนาดบรรจุภัณฑ์: **1 x EA**

- Structural Element Type: Connecting Clamp
- Thread Size: M5
- Product Family: Elessa Connecting Clamps
- Material: Stainless Steel
- Product System: MSM



7866210 Connecting

**RS PRO, BLACK PP T-SLOT COVERS,
5MM GROOVE SIZE, 2M LENGTH**

ขนาดบรรจุภัณฑ์: **10 x EA**

- Product Family: RS Structural System
- Fits Groove Size: 5 mm
- Fits Strut Profile: 20 mm
- Length: 2 m
- Material: PP
- Colour: Black



1809131 RS Structural

**RS PRO ALUMINIUM ALLOY COVER
STRIP, 8MM GROOVE SIZE, 2M**

ขนาดบรรจุภัณฑ์: **10 x EA**

- Product Family: RS Structural System
- Fits Groove Size: 8 mm
- Fits Strut Profile: 40 mm
- Length: 2 m
- Material: Aluminium Alloy
- Series: Profile 8



8508511 RS Structural

RS PRO, DOOR HINGE

ขนาดบรรจุภัณฑ์: **2 x EA**

- Component Type: Plastic Hinge
- Product Family: RS Structural System
- Fits Strut Profile: 20 mm



1809098 Plastic Hinge

RS PRO, DOOR HINGE, 20 5MM SLOT

ขนาดบรรจุภัณฑ์: **2 x EA**

- Component Type: Plastic Hinge
- Product Family: RS Structural System
- Product System: 20
- Fits Strut Profile: 20 mm
- Fits Groove Size: 5 mm



1809099 Plastic Hinge

RS PRO, DOOR HINGE, 20 6MM SLOT

ขนาดบรรจุภัณฑ์: **2 x EA**

- Component Type: Plastic Hinge
- Product Family: RS Structural System
- Product System: 20
- Fits Strut Profile: 20 mm
- Fits Groove Size: 6 mm



1809100 Plastic Hinge

RS PRO 5MM SLOT

ขนาดบรรจุภัณฑ์: **1 x KT**

- Fits Strut Profile: 20 mm
- Fits Groove Size: 5 mm



1809101 20 mm

BPS.30 BALL SHAPED DOOR LOCK

ขนาดบรรจุภัณฑ์: **1 x EA**

- Component Type: Ball Latch Kit
- Product Family: Elessa
- Product System: BPS
- Fits Strut Profile: Minimum of 15 mm



7865974 Ball Latch Kit

**STORAGE,STEEL TUBE FITTING,BASE
FLANGE,IIN**

ขนาดบรรจุภัณฑ์: **1 x EA**

- Component Type: Wall Flange
- Structural Element Type: Round Tube
- Product Family: RS Handrail System
- Product System: 131
- Fits Round Tube Size: Type 1
- Fits Tube Diameter: 33.7 mm
- Fits Strut Profile: Type 1
- Material: Cast Iron



2863588 Wall Flange

**RS PRO CAST IRON 131 WALL FLANGE,
¼2MM ROUND TUBE, TYPE 2**

ขนาดบรรจุภัณฑ์: **1 x EA**

- Component Type: Wall Flange
- Structural Element Type: Round Tube
- Product Family: RS Handrail System
- Product System: 131
- Fits Round Tube Size: Type 2
- Fits Tube Diameter: 42 mm
- Fits Strut Profile: Type 2
- Material: Cast Iron



2863594 Wall Flange

**RS PRO CAST IRON 131 WALL FLANGE,
¼8MM ROUND TUBE, TYPE 3**

ขนาดบรรจุภัณฑ์: **1 x EA**

- Component Type: Wall Flange
- Structural Element Type: Round Tube
- Product Family: RS Handrail System
- Product System: 131
- Fits Round Tube Size: Type 3
- Fits Tube Diameter: 48 mm
- Fits Strut Profile: Type 3
- Material: Cast Iron



2863601 Wall Flange

**STORAGE,STEEL TUBE FITTING,RAIL
BASE FLANGE,IIN**

ขนาดบรรจุภัณฑ์: **1 x EA**

- Component Type: Base Flange
- Structural Element Type: Round Tube
- Product Family: RS Handrail System
- Product System: 132
- Fits Round Tube Size: Type 1
- Fits Tube Diameter: 33.7 mm
- Fits Strut Profile: Type 1
- Material: Cast Iron



2863623 Base Flange

RS PRO CAST IRON 132 BASE FLANGE, 42MM ROUND TUBE, TYPE 2

ขนาดบรรจุภัณฑ์: 1 x EA

- Component Type: Base Flange
- Structural Element Type: Round Tube
- Product Family: RS Handrail System
- Product System: 132
- Fits Round Tube Size: Type 2
- Fits Tube Diameter: 42 mm
- Fits Strut Profile: Type 2
- Material: Cast Iron



2863639 Base Flange

RS PRO CAST IRON 132 BASE FLANGE, 48MM ROUND TUBE, TYPE 3

ขนาดบรรจุภัณฑ์: 1 x EA

- Component Type: Base Flange
- Structural Element Type: Round Tube
- Product Family: RS Handrail System
- Product System: 132
- Fits Round Tube Size: Type 3
- Fits Tube Diameter: 48 mm
- Fits Strut Profile: Type 3
- Material: Cast Iron



2863645 Base Flange

CAPS,END,SQUARE TUBE SYSTEM,BLACK PLASTIC

ขนาดบรรจุภัณฑ์: 12 x EA

- Structural Element Type: Square End Cap
- Fits Square Tube Profile: 25 mm
- Fits Strut Profile: 25 mm
- Material: Plastic
- Colour: Black
- Product Family: RS Square Tube System



621764 Square End Cap

RS PRO BLACK END CAP, GROOVE 5MM

ขนาดบรรจุภัณฑ์: 10 x EA

- Structural Element Type: End Cap
- Fits Tube Diameter: 42.5 mm
- Fits Groove Size: 5 mm
- Colour: Black
- Product Family: RS Structural System
- Product System: 20



1880351 End Cap

BLACK PROFILE END CAP 20 X 40

ขนาดบรรจุภัณฑ์: 10 x EA

- Structural Element Type: End Cap
- Fits Tube Diameter: 4.5 mm
- Fits Strut Profile: 20 x 40 mm
- Fits Groove Size: 5 mm
- Colour: Black
- Product Family: RS Structural System
- Product System: 20



1880353 End Cap

INSERT,ROUND TUBE,IMPERIAL,1 1/2IN

ขนาดบรรจุภัณฑ์: 100 x EA

- Structural Element Type: Round Tube Plug
- Fits Tube Diameter: 38.1 mm
- Colour: Black
- Product Family: RS



2372199 Round Tube Plug

STORAGE,STEEL TUBE FITTING,STOP END,PLASTIC,1IN

ขนาดบรรจุภัณฑ์: 10 x EA

- Structural Element Type: Round End Cap
- Fits Tube Diameter: 33.7 mm
- Fits Strut Profile: Type 1
- Material: Plastic
- Product Family: RS Handrail System
- Product System: 133



2863718 Round End Cap

STORAGE,STEEL TUBE FITTING,STOP END PLASTIC,1 1/4IN

ขนาดบรรจุภัณฑ์: 10 x EA

- Structural Element Type: Round End Cap
- Fits Tube Diameter: 42.4 mm
- Fits Strut Profile: Type 2
- Material: Plastic
- Product Family: RS Handrail System
- Product System: 133



2863724 Round End Cap

RS PRO PLASTIC ROUND END CAP TYPE 3 STRUT PROFILE

ขนาดบรรจุภัณฑ์: 10 x EA

- Structural Element Type: Round End Cap
- Fits Tube Diameter: 48.3 mm
- Fits Strut Profile: Type 3
- Material: Plastic
- Product Family: RS Handrail System
- Product System: 133



2863730 Round End Cap

RS PRO CAST IRON ROUND TUBE GATE EYE, 48.3MM OD

ขนาดบรรจุภัณฑ์: 1 x EA

- Component Type: Gate Eye
- Structural Element Type: Round Tube
- Product Family: RS Handrail System
- Product System: 138
- Fits Strut Profile: Type 3
- Fits Round Tube Size: Type 3
- Fits Tube Diameter: 48.3 mm
- Material: Cast Iron



4156129 Gate Eye

GROMMET FOR MINI IN-LINE CONNECTOR PK 25

- ขนาดบรรจุภัณฑ์: **25 x EA**
- Grommet Type: Cable Grommet
 - Minimum Cable Diameter: 1 mm
 - Maximum Cable Diameter: 3 mm
 - Material: Rubber
 - Colour: Black



6667365 Cable Grommet

PROCESS HEATER,MAT,1.25W,50X25MM,12VDC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Mat Shape: Rectangle
 - Power Rating: 1.25 W
 - Rectangular Mat Size: 25 x 50 mm
 - Peak Temperature: +300 °C
 - Supply Voltage: 12 V dc
 - Dimensions: 25 x 50 mm



245499 Rectangle

RS PRO SILICONE HEATER MAT, 5 W, 50 X 100MM, 12 V

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Mat Shape: Rectangle
 - Power Rating: 5 W
 - Rectangular Mat Size: 50 x 100 mm
 - Peak Temperature: +300 °C
 - Supply Voltage: 12 V
 - Dimensions: 50 x 100 mm



245528 Rectangle

PROCESS HEATER,MAT,7.5W,100X75MM,12VDC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Mat Shape: Rectangle
 - Power Rating: 7.5 W
 - Rectangular Mat Size: 75 x 100 mm
 - Peak Temperature: +300 °C
 - Supply Voltage: 12 V dc
 - Dimensions: 75 x 100 mm



245534 Rectangle

PROCESS HEATER,MAT,2.50W,50X50MM,12VD

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Mat Shape: Rectangle
 - Power Rating: 2.5 W
 - Rectangular Mat Size: 50 x 50 mm
 - Peak Temperature: +300 °C
 - Supply Voltage: 12 V dc
 - Dimensions: 50 x 50 mm



245506 Rectangle

RS PRO SILICONE HEATER MAT, 3.75 W, 50 X 75MM, 12 V

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Mat Shape: Rectangle
 - Power Rating: 3.75 W
 - Rectangular Mat Size: 50 x 75 mm
 - Peak Temperature: +300 °C
 - Supply Voltage: 12 V
 - Dimensions: 50 x 75 mm



245512 Rectangle

RS PRO SILICONE HEATER MAT, 10 W, 100 X 100MM, 12 V DC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Mat Shape: Square
 - Power Rating: 10 W
 - Rectangular Mat Size: 100 x 100 mm
 - Peak Temperature: +300 °C
 - Supply Voltage: 12 V dc
 - Dimensions: 100 x 100 mm



245540 Square

PROCESS HEATER,MAT,750W,50X150MM,12VD

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Mat Shape: Rectangle
 - Power Rating: 7.5 W
 - Rectangular Mat Size: 50 x 150 mm
 - Peak Temperature: +300 °C
 - Supply Voltage: 12 V dc
 - Dimensions: 50 x 150 mm



245556 Rectangle

PROCESS HEATER,MAT,15W,200X75MM,12VDC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Mat Shape: Rectangle
 - Power Rating: 15 W
 - Rectangular Mat Size: 75 x 200 mm
 - Peak Temperature: +300 °C
 - Supply Voltage: 12 V dc
 - Dimensions: 75 x 200 mm



245562 Rectangle

RS PRO SILICONE HEATER MAT, 80 W, 200 X 400MM, 12 V DC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Mat Shape: Rectangle
 - Power Rating: 80 W
 - Rectangular Mat Size: 200 x 400 mm
 - Peak Temperature: +300 °C
 - Supply Voltage: 12 V dc
 - Dimensions: 200 x 400 mm



245578 Rectangle

PROCESS HEATER,MAT,2W,50MM DIA,12VDC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Mat Shape: Circle
 - Power Rating: 2 W
 - Circular Mat Diameter: 50 mm
 - Peak Temperature: +300 °C
 - Supply Voltage: 12 V dc
 - Dimensions: 50 mm



245584 Circle

RS PRO SILICONE HEATER MAT, 4 W, 12 V DC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Mat Shape: Circle
 - Power Rating: 4 W
 - Circular Mat Diameter: 75 mm
 - Peak Temperature: +300 °C
 - Supply Voltage: 12 V dc
 - Dimensions: 75 mm



245590 Circle

PROCESS HEATER,MAT,8W,100MM DIA,12VDC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Mat Shape: Circle
 - Power Rating: 8 W
 - Circular Mat Diameter: 100 mm
 - Peak Temperature: +300 °C
 - Supply Voltage: 12 V dc
 - Dimensions: 100 mm



245607 Circle

PROCESS HEATER,MAT,15W,100X150MM,12V

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Mat Shape: Rectangle
 - Power Rating: 15 W
 - Rectangular Mat Size: 100 x 150 mm
 - Peak Temperature: +300 °C
 - Supply Voltage: 12 V dc
 - Dimensions: 100 x 150 mm



731350 Rectangle

PROCESS HEATER,MAT,30W,150X200MM,12V

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Mat Shape: Rectangle
 - Power Rating: 30 W
 - Rectangular Mat Size: 150 x 200 mm
 - Peak Temperature: +300 °C
 - Supply Voltage: 12 V dc
 - Dimensions: 150 x 200 mm



731366 Rectangle

PROCESS HEATER,MAT,60W,200X300MM,12V

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Mat Shape: Rectangle
 - Power Rating: 60 W
 - Rectangular Mat Size: 200 x 300 mm
 - Peak Temperature: +300 °C
 - Supply Voltage: 12 V dc
 - Dimensions: 200 x 300 mm



731372 Rectangle

PROCESS HEATER, MAT, MULTI ELEMENT, 150W, 50W, 38W, 25W, 18.5


- ขนาดบรรจุภัณฑ์: 1 x EA
- Mat Shape: Rectangle
 - Power Rating: 150 W
 - Rectangular Mat Size: 150 x 300 mm
 - Peak Temperature: +300 °C
 - Supply Voltage: 30 V dc
 - Dimensions: 150 x 300 mm



731388 Rectangle

RS PRO SILICONE HEATER MAT, 100 W, 100 X 150MM, 240 V AC

- ขนาดบรรจุภัณฑ์: 1 x EA
- Mat Shape: Rectangle
 - Power Rating: 100 W
 - Rectangular Mat Size: 100 x 150 mm
 - Peak Temperature: +180 °C
 - Supply Voltage: 240 V ac
 - Dimensions: 100 x 150 mm



1065407 Rectangle

RS PRO SILICONE HEATER MAT, 400 W, 200 X 300MM, 240 V AC

- ขนาดบรรจุภัณฑ์: 1 x EA
- Mat Shape: Rectangle
 - Power Rating: 400 W
 - Rectangular Mat Size: 200 x 300 mm
 - Peak Temperature: +180 °C
 - Supply Voltage: 240 V ac
 - Dimensions: 200 x 300 mm



1065409 Rectangle

RS PRO SILICONE HEATER MAT, 35 W, 110 V AC

- ขนาดบรรจุภัณฑ์: 1 x EA
- Mat Shape: Cylindrical
 - Power Rating: 35 W
 - Circular Mat Diameter: 28 mm
 - Peak Temperature: +200 °C
 - Supply Voltage: 110 V ac
 - Dimensions: 28 mm



1065412 Cylindrical

RS PRO SILICONE HEATER MAT, 69 W, 110 V AC

- ขนาดบรรจุภัณฑ์: 1 x EA
- Mat Shape: Cylindrical
 - Power Rating: 69 W
 - Circular Mat Diameter: 28 mm
 - Peak Temperature: +200 °C
 - Supply Voltage: 110 V ac
 - Dimensions: 28 mm



1065413 Cylindrical

RS PRO SILICONE HEATER MAT, 52 W, 240 V AC

- ขนาดบรรจุภัณฑ์: 1 x EA
- Mat Shape: Cylindrical
 - Power Rating: 52 W
 - Circular Mat Diameter: 42 mm
 - Peak Temperature: +200 °C
 - Supply Voltage: 240 V ac
 - Dimensions: 42 mm



1065414 Cylindrical

RS PRO SILICONE HEATER MAT, 105 W, 240 V AC

- ขนาดบรรจุภัณฑ์: 1 x EA
- Mat Shape: Cylindrical
 - Power Rating: 105 W
 - Circular Mat Diameter: 42 mm
 - Peak Temperature: +200 °C
 - Supply Voltage: 240 V ac
 - Dimensions: 42 mm



1065415 Cylindrical

RS PRO SILICONE HEATER MAT, 69 W, 240 V AC

- ขนาดบรรจุภัณฑ์: 1 x EA
- Mat Shape: Cylindrical
 - Power Rating: 69 W
 - Circular Mat Diameter: 55 mm
 - Peak Temperature: +200 °C
 - Supply Voltage: 240 V ac
 - Dimensions: 55 mm



1065417 Cylindrical

RS PRO SILICONE HEATER MAT, 105 W, 240 V AC

- ขนาดบรรจุภัณฑ์: 1 x EA
- Mat Shape: Cylindrical
 - Power Rating: 105 W
 - Circular Mat Diameter: 83 mm
 - Peak Temperature: +200 °C
 - Supply Voltage: 240 V ac
 - Dimensions: 83 mm



1065420 Cylindrical

RS PRO SILICONE HEATER MAT, 414 W, 240 V AC

- ขนาดบรรจุภัณฑ์: 1 x EA
- Mat Shape: Cylindrical
 - Power Rating: 414 W
 - Circular Mat Diameter: 115 mm
 - Peak Temperature: +200 °C
 - Supply Voltage: 240 V ac
 - Dimensions: 115 mm



1065425 Cylindrical

RS PRO SILICONE HEATER MAT, 176 W, 200 X 200MM, 240 V AC

- ขนาดบรรจุภัณฑ์: 1 x EA
- Mat Shape: Square
 - Power Rating: 176 W
 - Rectangular Mat Size: 200 x 200 mm
 - Peak Temperature: +180 °C
 - Supply Voltage: 240 V ac
 - Dimensions: 200 x 200 mm



1065427 Square

RS PRO SILICONE HEATER MAT, 275 W, 250 X 250MM, 240 V AC

- ขนาดบรรจุภัณฑ์: 1 x EA
- Mat Shape: Square
 - Power Rating: 275 W
 - Rectangular Mat Size: 250 x 250 mm
 - Peak Temperature: +180 °C
 - Supply Voltage: 240 V ac
 - Dimensions: 250 x 250 mm



1065428 Square

RS PRO SILICONE HEATER MAT, 100 W, 50 X 254MM, 120 V AC

- ขนาดบรรจุภัณฑ์: 1 x EA
- Mat Shape: Rectangle
 - Power Rating: 100 W
 - Rectangular Mat Size: 50 x 254 mm
 - Peak Temperature: +180 °C
 - Supply Voltage: 120 V ac
 - Dimensions: 2 x 10 in



1812055 Rectangle

RS PRO SILICONE HEATER MAT, 180 W, 152 X 305MM, 120 V AC

- ขนาดบรรจุภัณฑ์: 1 x EA
- Mat Shape: Rectangle
 - Power Rating: 180 W
 - Rectangular Mat Size: 152 x 305 mm
 - Peak Temperature: +180 °C
 - Supply Voltage: 120 V ac
 - Dimensions: 6 x 12 in



1812057 Rectangle

RS PRO SILICONE HEATER MAT, 60 W, 50 X 152MM, 12 V DC

- ขนาดบรรจุภัณฑ์: 1 x EA
- Mat Shape: Rectangle
 - Power Rating: 60 W
 - Rectangular Mat Size: 50 x 152 mm
 - Peak Temperature: +180 °C
 - Supply Voltage: 12 V dc
 - Dimensions: 2 x 6 in



1812061 Rectangle

SILICONE HEATER MAT 2" X 8" 12V 80W 20"

- ขนาดบรรจุภัณฑ์: 1 x EA
- Mat Shape: Rectangle
 - Power Rating: 80 W
 - Rectangular Mat Size: 50 x 203 mm
 - Peak Temperature: +180 °C
 - Supply Voltage: 12 V dc
 - Dimensions: 2 x 8 in



1812063 Rectangle

RS PRO SILICONE HEATER MAT, 250 W, 127 X 254MM, 230 V AC

- ขนาดบรรจุภัณฑ์: 1 x EA
- Mat Shape: Rectangle
 - Power Rating: 250 W
 - Rectangular Mat Size: 127 x 254 mm
 - Peak Temperature: +180 °C
 - Supply Voltage: 230 V ac
 - Dimensions: 5 x 10 in



1812064 Rectangle

SILICONE HEATER MAT 4" X 8" 230V 160W 20

- ขนาดบรรจุภัณฑ์: 1 x EA
- Mat Shape: Rectangle
 - Power Rating: 160 W
 - Rectangular Mat Size: 102 x 203 mm
 - Peak Temperature: +180 °C
 - Supply Voltage: 230 V ac
 - Dimensions: 4 x 8 in



1812065 Rectangle

RS PRO SILICONE HEATER MAT, 500 W, 254 X 254MM, 230 V AC

- ขนาดบรรจุภัณฑ์: 1 x EA
- Mat Shape: Rectangle
 - Power Rating: 500 W
 - Rectangular Mat Size: 254 x 254 mm
 - Peak Temperature: +180 °C
 - Supply Voltage: 230 V ac
 - Dimensions: 10 x 10 in



1812066 Rectangle

RS PRO SILICONE HEATER MAT, 320 W, 203 X 203MM, 230 V AC

- ขนาดบรรจุภัณฑ์: 1 x EA
- Mat Shape: Rectangle
 - Power Rating: 320 W
 - Rectangular Mat Size: 203 x 203 mm
 - Peak Temperature: +180 °C
 - Supply Voltage: 230 V ac
 - Dimensions: 8 x 8 in



1812067 Rectangle

RS PRO SILICONE HEATER MAT, 500 W, 127 X 508MM, 230 V AC

- ขนาดบรรจุภัณฑ์: 1 x EA
- Mat Shape: Rectangle
 - Power Rating: 500 W
 - Rectangular Mat Size: 127 x 508 mm
 - Peak Temperature: +180 °C
 - Supply Voltage: 230 V ac
 - Dimensions: 5 x 20 in



1812068 Rectangle

RS PRO MICA HEATING PAD, 100 W, 230 V

- ขนาดบรรจุภัณฑ์: 1 x EA
- Power Rating: 100 W
 - Peak Temperature: +260 °C
 - Supply Voltage: 230 V
 - Dimensions: 60 x 60 mm



7904827 100 W

RS PRO MICA HEATING PAD, 300 W, 230 V


- ขนาดบรรจุภัณฑ์: 1 x EA
- Power Rating: 300 W
 - Peak Temperature: +260 °C
 - Supply Voltage: 230 V
 - Dimensions: 200 x 100 mm



7904833 300 W

RS PRO MICA HEATING PAD, 220 W, 230 V

- ขนาดบรรจุภัณฑ์: 1 x EA
- Power Rating: 220 W
 - Peak Temperature: +260 °C
 - Supply Voltage: 230 V
 - Dimensions: 70 x 75 mm



7904836 220 W

RS PRO MICA HEATING PAD, 300 W, 230 V

- ขนาดบรรจุภัณฑ์: 1 x EA
- Power Rating: 300 W
 - Peak Temperature: +260 °C
 - Supply Voltage: 230 V
 - Dimensions: 190 x 320 mm



7904839 300 W

RS PRO MICA HEATING PAD, 80 W, 230 V

- ขนาดบรรจุภัณฑ์: 1 x EA
- Power Rating: 80 W
 - Peak Temperature: +260 °C
 - Supply Voltage: 230 V
 - Dimensions: 50 x 50 mm



7904842 80 W

RS PRO HEATER MAT, 1.25 W, 25 X 50MM, 12 V

- ขนาดบรรจุภัณฑ์: 1 x EA
- Mat Shape: Rectangle
 - Power Rating: 1.25 W
 - Rectangular Mat Size: 25 x 50 mm
 - Supply Voltage: 12 V
 - Dimensions: 25 x 50 x 0.2 mm
 - Maximum Operating Temperature: +200 °C
 - Thickness: 0.2 mm



7983741 Rectangle

RS PRO HEATER MAT, 2 W, 25 X 75MM, 12 V

- ขนาดบรรจุภัณฑ์: 1 x EA
- Mat Shape: Rectangle
 - Power Rating: 2 W
 - Rectangular Mat Size: 25 x 75 mm
 - Supply Voltage: 12 V
 - Dimensions: 25 x 75 x 0.2 mm
 - Maximum Operating Temperature: +200 °C
 - Thickness: 0.2 mm



7983750 Rectangle

RS PRO HEATER MAT, 4 W, 25 X 100MM, 12 V


- ขนาดบรรจุภัณฑ์: 1 x EA
- Power Rating: 4 W
 - Rectangular Mat Size: 25 x 100 mm
 - Supply Voltage: 12 V
 - Dimensions: 25 x 100 x 0.2 mm
 - Maximum Operating Temperature: +200 °C
 - Thickness: 0.2 mm



7983753 4 W

RS PRO HEATER MAT, 2.5 W, 50 X 50MM, 12 V


- ขนาดบรรจุภัณฑ์: 1 x EA
- Power Rating: 2.5 W
 - Rectangular Mat Size: 50 x 50 mm
 - Supply Voltage: 12 V
 - Dimensions: 50 x 50 x 0.2 mm
 - Maximum Operating Temperature: +200 °C
 - Thickness: 0.2 mm



7983757 2.5 W

RS PRO HEATER MAT, 7.5 W, 75 X 100MM, 12 V

- ขนาดบรรจุภัณฑ์: 1 x EA
- Power Rating: 7.5 W
 - Rectangular Mat Size: 75 x 100 mm
 - Supply Voltage: 12 V
 - Dimensions: 75 x 100 x 0.2 mm
 - Maximum Operating Temperature: +200 °C
 - Thickness: 0.2 mm



7983763 7.5 W

RS PRO HEATER MAT, 2 W, 12 V

- ขนาดบรรจุภัณฑ์: 1 x EA
- Power Rating: 2 W
 - Circular Mat Diameter: 50 x 0.2 mm
 - Supply Voltage: 12 V
 - Dimensions: 50 x 0.2 mm
 - Thickness: 0.2 mm
 - Maximum Operating Temperature: 200 °C



7983772 2 W

HEATING ELEMENT, 1 KW, 230 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Drum Heater - Silicone
 - Power Rating: 1 kW
 - Supply Voltage: 230 V ac



1799541 Drum Heater -

HEATING ELEMENT, 1 KW

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Drum Heater - Silicone
 - Power Rating: 1 kW



1799543 Drum Heater -

HEATING ELEMENT, 1.5 KW, 230 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Drum Heater - Silicone
 - Power Rating: 1.5 kW
 - Supply Voltage: 230 V ac



1799545 Drum Heater -

HEATING ELEMENT, 1.8 KW, 230 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Drum Heater - Silicone
 - Power Rating: 1.8 kW
 - Supply Voltage: 230 V ac



1799549 Drum Heater -

HEATING ELEMENT, 450 W, 230 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Drum Heater - Silicone
 - Power Rating: 450 W
 - Supply Voltage: 230 V ac



1799550 Drum Heater -

HEATING ELEMENT, 1.2 KW, 230 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Drum Heater - Silicone
 - Power Rating: 1.2 kW
 - Supply Voltage: 230 V ac



1799551 Drum Heater -

REFLECTOR,CERAMIC HEATER,60X245MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 255 mm
 - Width: 92 mm
 - Thickness: 60 mm
 - Heating Element Form: Reflector Bracket
 - Dimensions: 255 x 92 x 60 mm



2462501 255 mm

REFLECTOR,CERAMIC,HEATER,60X12 2MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 160 mm
 - Width: 92 mm
 - Thickness: 32 mm
 - Heating Element Form: Reflector Bracket
 - Dimensions: 160 x 92 x 32 mm



2462517 160 mm

MICA SEALED NOZZLE HEATER 150W 240V

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Band Heater
 - Power Rating: 150 W
 - Supply Voltage: 240 V
 - Width: 30 mm
 - Diameter: 35 mm
 - Dimensions: 35 (Dia.) x 30 mm



7904855 Band Heater

MICA SEALED NOZZLE HEATER 225W 230V

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Band Heater
 - Power Rating: 225 W
 - Supply Voltage: 240 V
 - Width: 25 mm
 - Diameter: 60 mm
 - Dimensions: 60 (Dia.) x 25 mm



7904858 Band Heater

MICA SEALED NOZZLE HEATER 200W 230V

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Band Heater
 - Power Rating: 200 W
 - Supply Voltage: 240 V
 - Width: 32 mm
 - Diameter: 42 mm
 - Dimensions: 42 (Dia.) x 32 mm



7904864 Band Heater

MICA SEALED NOZZLE HEATER 150W 240V


- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Band Heater
 - Power Rating: 150 W
 - Supply Voltage: 230 V
 - Width: 1.5 in
 - Diameter: 25 mm
 - Dimensions: 1 (Dia.) x 1.5 mm



7904867 Band Heater

HEATING ELEMENT, 3.75 W, 12 V

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Heater Mat
 - Power Rating: 3.75 W
 - Supply Voltage: 12 V



7983766 Heater Mat

KAPTON HEATER MAT, 50X100MM, 12V, 5W

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Heater Mat
 - Power Rating: 5 W
 - Supply Voltage: 12 V



7983769 Heater Mat

HEATING ELEMENT, 75MM, 175 W, 220 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Cartridge Heater
 - Power Rating: 175 W
 - Supply Voltage: 220 V ac
 - Length: 75 mm
 - Diameter: 12.5 mm



8606732 Cartridge Heater

CARTRIDGE HEATER, 10MM X 70MM, 250W

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Cartridge Heater
 - Power Rating: 250 W
 - Supply Voltage: 220 V ac
 - Length: 70 mm
 - Diameter: 10 mm



8606741 Cartridge Heater

CARTRIDGE HEATER, 10MM X 75MM, 125W

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Cartridge Heater
 - Power Rating: 125 W
 - Supply Voltage: 220 V ac
 - Length: 75 mm
 - Diameter: 10 mm



8606744 Cartridge Heater

HEATING ELEMENT, 90MM, 150 W, 220 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Cartridge Heater
 - Power Rating: 150 W
 - Supply Voltage: 220 V ac
 - Length: 90 mm
 - Diameter: 10 mm



8606748 Cartridge Heater

HEATING ELEMENT, 2IN, 120 W, 120 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Cartridge Heater
 - Power Rating: 120 W
 - Supply Voltage: 120 V ac
 - Length: 2 in
 - Diameter: 1/2 in



8606750 Cartridge Heater

HEATING ELEMENT, 90MM, 300 W, 220 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Cartridge Heater
 - Power Rating: 300 W
 - Supply Voltage: 220 V ac
 - Length: 90 mm
 - Diameter: 10 mm



8606757 Cartridge Heater

HEATING ELEMENT, 3IN, 200 W, 220 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Cartridge Heater
 - Power Rating: 200 W
 - Supply Voltage: 220 V ac
 - Length: 3 in
 - Diameter: 1/2 in



8606760 Cartridge Heater

HEATING ELEMENT, 2IN, 270 W, 220 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Cartridge Heater
 - Power Rating: 270 W
 - Supply Voltage: 220 V ac
 - Length: 2 in
 - Diameter: 1/2 in



8606763 Cartridge Heater

HEATING ELEMENT, 3IN, 535 W, 220 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Cartridge Heater
 - Power Rating: 535 W
 - Supply Voltage: 220 V ac
 - Length: 3 in
 - Diameter: 1/2 in



8606766 Cartridge Heater

HEATING ELEMENT, 4IN, 275 W, 220 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Cartridge Heater
 - Power Rating: 275 W
 - Supply Voltage: 220 V ac
 - Length: 4 in
 - Diameter: 1/2 in



8606776 Cartridge Heater

HEATING ELEMENT, 3IN, 335 W, 220 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Cartridge Heater
 - Power Rating: 335 W
 - Supply Voltage: 220 V ac
 - Length: 3 in
 - Diameter: 1/2 in



8606772 Cartridge Heater

HEATING ELEMENT, 3IN, 200 W, 120 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Cartridge Heater
 - Power Rating: 200 W
 - Supply Voltage: 120 V ac
 - Length: 3 in
 - Diameter: 1/2 in



8606779 Cartridge Heater

HEATING ELEMENT, 4IN, 275 W, 220 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Cartridge Heater
 - Power Rating: 275 W
 - Supply Voltage: 220 V ac
 - Length: 4 in
 - Diameter: 1/2 in



8606785 Cartridge Heater

HEATING ELEMENT, 50MM, 200 W, 220 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Cartridge Heater
 - Power Rating: 200 W
 - Supply Voltage: 220 V ac
 - Length: 50 mm
 - Diameter: 13 mm



8606794 Cartridge Heater

HEATING ELEMENT, 8IN, 650 W, 220 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Cartridge Heater
 - Power Rating: 650 W
 - Supply Voltage: 220 V ac
 - Length: 8 in
 - Diameter: 1/2 in



8606801 Cartridge Heater

HEATING ELEMENT, 1.5IN, 20 W, 120 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Cartridge Heater
 - Power Rating: 20 W
 - Supply Voltage: 120 V ac
 - Length: 1.5 in
 - Diameter: 1/4 in



8606805 Cartridge Heater

HEATING ELEMENT, 6IN, 425 W, 220 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Cartridge Heater
 - Power Rating: 425 W
 - Supply Voltage: 220 V ac
 - Length: 6 in
 - Diameter: 1/2 in



8606808 Cartridge Heater

HEATING ELEMENT, 3IN, 100 W, 220 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Cartridge Heater
 - Power Rating: 100 W
 - Supply Voltage: 220 V ac
 - Length: 3 in
 - Diameter: 1/4 in



8606811 Cartridge Heater

CARTRIDGE HEATER, 1/4" X 1-1/2", 50W

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Cartridge Heater
 - Power Rating: 50 W
 - Supply Voltage: 220 V ac
 - Length: 1.5 in
 - Diameter: 1/4 in


8606814 Cartridge Heater

HEATING ELEMENT, 3.5IN, 90 W, 220 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Cartridge Heater
 - Power Rating: 90 W
 - Supply Voltage: 220 V ac
 - Length: 3.5 in
 - Diameter: 1/4 in


8606820 Cartridge Heater

HEATING ELEMENT, 4IN, 110 W, 220 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Cartridge Heater
 - Power Rating: 110 W
 - Supply Voltage: 220 V ac
 - Length: 4 in
 - Diameter: 1/4 in


8606823 Cartridge Heater

HEATING ELEMENT, 4IN, 235 W, 220 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Cartridge Heater
 - Power Rating: 235 W
 - Supply Voltage: 220 V ac
 - Length: 4 in
 - Diameter: 1/4 in


8606827 Cartridge Heater

CARTRIDGE HEATER, 1/4" X 4", 300W

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Cartridge Heater
 - Power Rating: 300 W
 - Supply Voltage: 220 V ac
 - Length: 4 in
 - Diameter: 1/4 in


8606836 Cartridge Heater

HEATING ELEMENT, 4IN, 300 W, 120 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Cartridge Heater
 - Power Rating: 300 W
 - Supply Voltage: 120 V ac
 - Length: 4 in
 - Diameter: 1/4 in


8606839 Cartridge Heater


HEATING ELEMENT, 5IN, 400 W, 220 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Cartridge Heater
 - Power Rating: 400 W
 - Supply Voltage: 220 V ac
 - Length: 5 in
 - Diameter: 1/4 in


8606842 Cartridge Heater

HEATING ELEMENT, 75MM, 150 W, 120 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Cartridge Heater
 - Power Rating: 150 W
 - Supply Voltage: 120 V ac
 - Length: 75 mm
 - Diameter: 6.5 mm


8606845 Cartridge Heater

CARTRIDGE HEATER, 1/4" X 1-1/2", 30W

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Cartridge Heater
 - Power Rating: 30 W
 - Supply Voltage: 220 V ac
 - Length: 1.5 in
 - Diameter: 1/4 in


8606849 Cartridge Heater


CARTRIDGE HEATER, 1/4" X 2-1/2", 75W

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Cartridge Heater
 - Power Rating: 75 W
 - Supply Voltage: 220 V ac
 - Length: 2.5 in
 - Diameter: 1/4 in


8606851 Cartridge Heater

HEATING ELEMENT, 3IN, 100 W, 120 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Cartridge Heater
 - Power Rating: 100 W
 - Supply Voltage: 120 V ac
 - Length: 3 in
 - Diameter: 1/4 in


8606855 Cartridge Heater

HEATING ELEMENT, 2IN, 50 W, 220 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Cartridge Heater
 - Power Rating: 50 W
 - Supply Voltage: 120 V ac
 - Length: 2 in
 - Diameter: 1/4 in


8606858 Cartridge Heater

HEATING ELEMENT, 3.5IN, 200 W, 220 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Cartridge Heater
 - Power Rating: 200 W
 - Supply Voltage: 220 V ac
 - Length: 3.5 in
 - Diameter: 1/4 in


8606867 Cartridge Heater

CARTRIDGE HEATER, 10MM X 100MM, 350W

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Cartridge Heater
 - Power Rating: 350 W
 - Supply Voltage: 220 V ac
 - Length: 100 mm
 - Diameter: 10 mm


8606870 Cartridge Heater

HEATING ELEMENT, 100MM, 500 W, 120 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Cartridge Heater
 - Power Rating: 500 W
 - Supply Voltage: 120 V ac
 - Length: 100 mm
 - Diameter: 10 mm


8606877 Cartridge Heater

HEATING ELEMENT, 100MM, 500 W, 120 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Cartridge Heater
 - Power Rating: 500 W
 - Supply Voltage: 120 V ac
 - Length: 100 mm
 - Diameter: 10 mm


8606883 Cartridge Heater

CARTRIDGE HEATER, 10MM X 100MM, 150W

- ขนาดบรรจุภัณฑ์: 1 x EA
- Element Type: Cartridge Heater
 - Power Rating: 150 W
 - Supply Voltage: 220 V ac
 - Length: 100 mm
 - Diameter: 10 mm



8606886 Cartridge Heater

CARTRIDGE HEATER, 10MM X 100MM, 200W

- ขนาดบรรจุภัณฑ์: 1 x EA
- Element Type: Cartridge Heater
 - Power Rating: 200 W
 - Supply Voltage: 220 V ac
 - Length: 100 mm
 - Diameter: 10 mm



8606889 Cartridge Heater

CARTRIDGE HEATER, 10MM X 125MM, 500W

- ขนาดบรรจุภัณฑ์: 1 x EA
- Element Type: Cartridge Heater
 - Power Rating: 500 W
 - Supply Voltage: 220 V ac
 - Length: 125 mm
 - Diameter: 10 mm



8606895 Cartridge Heater

CARTRIDGE HEATER, 10MM X 150MM, 300W

- ขนาดบรรจุภัณฑ์: 1 x EA
- Element Type: Cartridge Heater
 - Power Rating: 300 W
 - Supply Voltage: 220 V ac
 - Length: 150 mm
 - Diameter: 10 mm



8606899 Cartridge Heater

CARTRIDGE HEATER, 10MM X 40MM, 50W

- ขนาดบรรจุภัณฑ์: 1 x EA
- Element Type: Cartridge Heater
 - Power Rating: 50 W
 - Supply Voltage: 220 V ac
 - Length: 40 mm
 - Diameter: 10 mm



8606902 Cartridge Heater

HEATING ELEMENT, 50MM, 75 W, 120 V AC

- ขนาดบรรจุภัณฑ์: 1 x EA
- Element Type: Cartridge Heater
 - Power Rating: 75 W
 - Supply Voltage: 120 V ac
 - Length: 50 mm
 - Diameter: 10 mm



8606906 Cartridge Heater

CARTRIDGE HEATER, 10MM X 40MM, 200W

- ขนาดบรรจุภัณฑ์: 1 x EA
- Element Type: Cartridge Heater
 - Power Rating: 200 W
 - Supply Voltage: 220 V ac
 - Length: 40 mm
 - Diameter: 10 mm



8606909 Cartridge Heater

CARTRIDGE HEATER, 10MM X 50MM, 200W

- ขนาดบรรจุภัณฑ์: 1 x EA
- Element Type: Cartridge Heater
 - Power Rating: 200 W
 - Supply Voltage: 220 V ac
 - Length: 50 mm
 - Diameter: 10 mm



8606912 Cartridge Heater

HEATING ELEMENT, 50MM, 75 W, 220 V AC

- ขนาดบรรจุภัณฑ์: 1 x EA
- Element Type: Cartridge Heater
 - Power Rating: 75 W
 - Supply Voltage: 220 V ac
 - Length: 50 mm
 - Diameter: 10 mm



8606915 Cartridge Heater

CARTRIDGE HEATER, 10MM X 50MM, 150W

- ขนาดบรรจุภัณฑ์: 1 x EA
- Element Type: Cartridge Heater
 - Power Rating: 150 W
 - Supply Voltage: 220 V ac
 - Length: 50 mm
 - Diameter: 10 mm



8606918 Cartridge Heater

CARTRIDGE HEATER, 10MM X 65MM, 300W

- ขนาดบรรจุภัณฑ์: 1 x EA
- Element Type: Cartridge Heater
 - Power Rating: 300 W
 - Supply Voltage: 220 V ac
 - Length: 65 mm
 - Diameter: 10 mm



8606921 Cartridge Heater

HEATING ELEMENT, 100MM, 250 W, 120 V AC

- ขนาดบรรจุภัณฑ์: 1 x EA
- Element Type: Cartridge Heater
 - Power Rating: 250 W
 - Supply Voltage: 220 V ac
 - Length: 100 mm
 - Diameter: 13 mm



8606930 Cartridge Heater

HEATING ELEMENT, 100MM, 450 W, 220 V AC

- ขนาดบรรจุภัณฑ์: 1 x EA
- Element Type: Cartridge Heater
 - Power Rating: 450 W
 - Supply Voltage: 220 V ac
 - Length: 100 mm
 - Diameter: 13 mm



8606934 Cartridge Heater

HEATING ELEMENT, 100MM, 250 W, 220 V AC

- ขนาดบรรจุภัณฑ์: 1 x EA
- Element Type: Cartridge Heater
 - Power Rating: 250 W
 - Supply Voltage: 220 V ac
 - Length: 100 mm
 - Diameter: 12.5 mm



8606937 Cartridge Heater

HEATING ELEMENT, 125MM, 325 W, 220 V AC

- ขนาดบรรจุภัณฑ์: 1 x EA
- Element Type: Cartridge Heater
 - Power Rating: 325 W
 - Supply Voltage: 220 V ac
 - Length: 125 mm
 - Diameter: 12.5 mm



8606943 Cartridge Heater

HEATING ELEMENT, 200MM, 600 W, 220 V AC

- ขนาดบรรจุภัณฑ์: 1 x EA
- Element Type: Cartridge Heater
 - Power Rating: 600 W
 - Supply Voltage: 220 V ac
 - Length: 200 mm
 - Diameter: 12.5 mm



8606956 Cartridge Heater

HEATING ELEMENT, 175MM, 500 W, 220 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Cartridge Heater
 - Power Rating: 500 W
 - Supply Voltage: 220 V ac
 - Length: 175 mm
 - Diameter: 12.5 mm



8606959 Cartridge Heater

HEATING ELEMENT, 50MM, 200 W, 120 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Cartridge Heater
 - Power Rating: 200 W
 - Supply Voltage: 120 V ac
 - Length: 50 mm
 - Diameter: 13 mm



8606965 Cartridge Heater

HEATING ELEMENT, 65MM, 150 W, 220 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Cartridge Heater
 - Power Rating: 150 W
 - Supply Voltage: 220 V ac
 - Length: 65 mm
 - Diameter: 13 mm



8606968 Cartridge Heater

HEATING ELEMENT, 100MM, 350 W, 220 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Cartridge Heater
 - Power Rating: 350 W
 - Supply Voltage: 220 V ac
 - Length: 100 mm
 - Diameter: 16 mm



8606980 Cartridge Heater

CARTRIDGE HEATER, 16MM X 200MM, 700W

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Cartridge Heater
 - Power Rating: 700 W
 - Supply Voltage: 220 V ac
 - Length: 200 mm
 - Diameter: 16 mm



8606990 Cartridge Heater

HEATING ELEMENT, 150MM, 500 W, 220 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Cartridge Heater
 - Power Rating: 500 W
 - Supply Voltage: 220 V ac
 - Length: 150 mm
 - Diameter: 16 mm



8606993 Cartridge Heater

HEATING ELEMENT, 175MM, 600 W, 220 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Cartridge Heater
 - Power Rating: 600 W
 - Supply Voltage: 220 V ac
 - Length: 175 mm
 - Diameter: 16 mm



8606996 Cartridge Heater

HEATING ELEMENT, 75MM, 225 W, 220 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Cartridge Heater
 - Power Rating: 225 W
 - Supply Voltage: 220 V ac
 - Length: 75 mm
 - Diameter: 16 mm



8607000 Cartridge Heater

CARTRIDGE HEATER, 16MM X 200MM, 1000W

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Cartridge Heater
 - Power Rating: 1 kW
 - Supply Voltage: 220 V ac
 - Length: 200 mm
 - Diameter: 16 mm



8607003 Cartridge Heater

HEATING ELEMENT, 50MM, 250 W, 220 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Cartridge Heater
 - Power Rating: 250 W
 - Supply Voltage: 220 V ac
 - Length: 50 mm
 - Diameter: 16 mm



8607006 Cartridge Heater

HEATING ELEMENT, 6IN, 500 W, 220 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Cartridge Heater
 - Power Rating: 500 W
 - Supply Voltage: 220 V ac
 - Length: 6 in
 - Diameter: 19 mm



8607012 Cartridge Heater

HEATING ELEMENT, 2IN, 100 W, 120 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Cartridge Heater
 - Power Rating: 100 W
 - Supply Voltage: 120 V ac
 - Length: 2 in
 - Diameter: 3/8 in



8607025 Cartridge Heater

HEATING ELEMENT, 2IN, 150 W, 220 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Cartridge Heater
 - Power Rating: 150 W
 - Supply Voltage: 220 V ac
 - Length: 2 in
 - Diameter: 3/8 in



8607028 Cartridge Heater

HEATING ELEMENT, 2.5IN, 300 W, 220 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Cartridge Heater
 - Power Rating: 300 W
 - Supply Voltage: 220 V ac
 - Length: 2.5 in
 - Diameter: 3/8 in



8607031 Cartridge Heater

HEATING ELEMENT, 3IN, 250 W, 120 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Cartridge Heater
 - Power Rating: 250 W
 - Supply Voltage: 120 V ac
 - Length: 3 in
 - Diameter: 3/8 in



8607038 Cartridge Heater

HEATING ELEMENT, 3.5IN, 150 W, 220 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Cartridge Heater
 - Power Rating: 150 W
 - Supply Voltage: 220 V ac
 - Length: 3.5 in
 - Diameter: 3/8 in



8607040 Cartridge Heater

HEATING ELEMENT, 3IN, 400 W, 220 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Cartridge Heater
 - Power Rating: 400 W
 - Supply Voltage: 220 V ac
 - Length: 3 in
 - Diameter: 3/8 in



8607047 Cartridge Heater

HEATING ELEMENT, 4IN, 500 W, 240 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Cartridge Heater
 - Power Rating: 500 W
 - Supply Voltage: 240 V ac
 - Length: 4 in
 - Diameter: 3/8 in



8607050 Cartridge Heater

HEATING ELEMENT, 4IN, 350 W, 220 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Cartridge Heater
 - Power Rating: 350 W
 - Supply Voltage: 220 V ac
 - Length: 4 in
 - Diameter: 3/8 in



8607053 Cartridge Heater

HEATING ELEMENT, 4IN, 350 W, 120 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Cartridge Heater
 - Power Rating: 350 W
 - Supply Voltage: 120 V ac
 - Length: 4 in
 - Diameter: 3/8 in



8607056 Cartridge Heater

HEATING ELEMENT, 5IN, 500 W, 220 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Cartridge Heater
 - Power Rating: 500 W
 - Supply Voltage: 220 V ac
 - Length: 5 in
 - Diameter: 3/8 in



8607062 Cartridge Heater

CARTRIDGE HEATER, 3/8 " X 1-1/2", 100W

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Cartridge Heater
 - Power Rating: 100 W
 - Supply Voltage: 220 V ac
 - Length: 1.5 in
 - Diameter: 3/8 in



8607066 Cartridge Heater

HEATING ELEMENT, 5IN, 280 W, 220 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Cartridge Heater
 - Power Rating: 280 W
 - Supply Voltage: 220 V ac
 - Length: 5 in
 - Diameter: 3/8 in



8607069 Cartridge Heater

HEATING ELEMENT, 2IN, 200 W, 220 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Cartridge Heater
 - Power Rating: 200 W
 - Supply Voltage: 220 V ac
 - Length: 2 in
 - Diameter: 3/8 in



8607072 Cartridge Heater

CARTRIDGE HEATER, 3/8" X 1-1/2", 200W

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Cartridge Heater
 - Power Rating: 200 W
 - Supply Voltage: 220 V ac
 - Length: 1.5 in
 - Diameter: 3/8 in



8607075 Cartridge Heater

HEATING ELEMENT, 1.5IN, 50 W, 220 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Cartridge Heater
 - Power Rating: 50 W
 - Supply Voltage: 220 V ac
 - Length: 1.5 in
 - Diameter: 3/8 in



8607078 Cartridge Heater

HEATING ELEMENT, 6IN, 350 W, 220 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Cartridge Heater
 - Power Rating: 350 W
 - Supply Voltage: 220 V ac
 - Length: 6 in
 - Diameter: 3/8 in



8607081 Cartridge Heater

HEATING ELEMENT, 6IN, 540 W, 220 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Cartridge Heater
 - Power Rating: 540 W
 - Supply Voltage: 220 V ac
 - Length: 6 in
 - Diameter: 5/8 in



8607090 Cartridge Heater

CARTRIDGE HEATER, 6.5MM X 100MM, 100W

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Cartridge Heater
 - Power Rating: 100 W
 - Supply Voltage: 220 V ac
 - Length: 100 mm
 - Diameter: 6.5 mm



8607101 Cartridge Heater

HEATING ELEMENT, 8IN, 750 W, 220 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Cartridge Heater
 - Power Rating: 750 W
 - Supply Voltage: 220 V ac
 - Length: 8 in
 - Diameter: 5/8 in



8607104 Cartridge Heater

CARTRIDGE HEATER, 6.5MM X 100MM, 400W

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Cartridge Heater
 - Power Rating: 400 W
 - Supply Voltage: 220 V ac
 - Length: 100 mm
 - Diameter: 6.5 mm



8607113 Cartridge Heater

HEATING ELEMENT, 100MM, 300 W, 220 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Cartridge Heater
 - Power Rating: 300 W
 - Supply Voltage: 220 V ac
 - Length: 100 mm
 - Diameter: 6.5 mm



8607117 Cartridge Heater

CARTRIDGE HEATER, 6.5MM X 100MM, 250W

- ขนาดบรรจุภัณฑ์: 1 x EA
 • Element Type: Cartridge Heater
 • Power Rating: 250 W
 • Supply Voltage: 220 V ac
 • Length: 100 mm
 • Diameter: 6.5 mm



8607126 Cartridge Heater

CARTRIDGE HEATER, 6.5MM X 40MM, 50W

- ขนาดบรรจุภัณฑ์: 1 x EA
 • Element Type: Cartridge Heater
 • Power Rating: 50 W
 • Supply Voltage: 220 V ac
 • Length: 40 mm
 • Diameter: 6.5 mm



8607139 Cartridge Heater

HEATING ELEMENT, 60MM, 100 W, 120 V AC

- ขนาดบรรจุภัณฑ์: 1 x EA
 • Element Type: Cartridge Heater
 • Power Rating: 100 W
 • Supply Voltage: 120 V ac
 • Length: 60 mm
 • Diameter: 6.5 mm



8607141 Cartridge Heater

CARTRIDGE HEATER, 6.5MM X 90MM, 200W

- ขนาดบรรจุภัณฑ์: 1 x EA
 • Element Type: Cartridge Heater
 • Power Rating: 200 W
 • Supply Voltage: 220 V ac
 • Length: 90 mm
 • Diameter: 6.5 mm



8607151 Cartridge Heater

CARTRIDGE HEATER, 6.5MM X 75MM, 100W

- ขนาดบรรจุภัณฑ์: 1 x EA
 • Element Type: Cartridge Heater
 • Power Rating: 100 W
 • Supply Voltage: 220 V ac
 • Length: 75 mm
 • Diameter: 6.5 mm



8607154 Cartridge Heater

HEATING ELEMENT, 4IN, 500 W, 220 V AC

- ขนาดบรรจุภัณฑ์: 1 x EA
 • Element Type: Cartridge Heater
 • Power Rating: 500 W
 • Supply Voltage: 220 V ac
 • Length: 4 in
 • Diameter: 1/2 in



8607160 Cartridge Heater

CARTRIDGE HEATER, 10MM X 40MM, 100W

- ขนาดบรรจุภัณฑ์: 1 x EA
 • Element Type: Cartridge Heater
 • Power Rating: 100 W
 • Supply Voltage: 220 V ac
 • Length: 40 mm
 • Diameter: 10 mm
 • Heating Element Form: Tubular



8607163 Cartridge Heater

HEATING ELEMENT, 150MM, 600 W, 220 V AC

- ขนาดบรรจุภัณฑ์: 1 x EA
 • Element Type: Cartridge Heater
 • Power Rating: 600 W
 • Supply Voltage: 220 V ac
 • Length: 150 mm
 • Diameter: 10 mm



8607167 Cartridge Heater

HEATING ELEMENT, 150MM, 400 W, 220 V AC

- ขนาดบรรจุภัณฑ์: 1 x EA
 • Element Type: Cartridge Heater
 • Power Rating: 400 W
 • Supply Voltage: 220 V ac
 • Length: 150 mm
 • Diameter: 16 mm



8607173 Cartridge Heater

HEATING ELEMENT, 4IN, 400 W, 220 V AC

- ขนาดบรรจุภัณฑ์: 1 x EA
 • Element Type: Cartridge Heater
 • Power Rating: 400 W
 • Supply Voltage: 220 V ac
 • Length: 4 in
 • Diameter: 1/4 in



8607179 Cartridge Heater

HEATING ELEMENT, 400 W, 120 V AC

- ขนาดบรรจุภัณฑ์: 1 x EA
 • Element Type: Air Heater
 • Power Rating: 400 W
 • Supply Voltage: 120 V ac



8607182 Air Heater

HEATING ELEMENT, 400 W, 240 V AC

- ขนาดบรรจุภัณฑ์: 1 x EA
 • Element Type: Air Heater
 • Power Rating: 400 W
 • Supply Voltage: 240 V ac



8607185 Air Heater

HEATING ELEMENT, 600 W, 120 V AC

- ขนาดบรรจุภัณฑ์: 1 x EA
 • Element Type: Air Heater
 • Power Rating: 600 W
 • Supply Voltage: 120 V ac



8607189 Air Heater

AIR HEATER, 600W, 240V AC, INC LEAD

- ขนาดบรรจุภัณฑ์: 1 x EA
 • Element Type: Air Heater
 • Power Rating: 600 W
 • Supply Voltage: 240 V ac



8607198 Air Heater

HEATING ELEMENT, 600 W, 240 V AC

- ขนาดบรรจุภัณฑ์: 1 x EA
 • Element Type: Air Heater
 • Power Rating: 600 W
 • Supply Voltage: 240 V ac



8607208 Air Heater

HEATING ELEMENT, 235 W, 230 V AC

- ขนาดบรรจุภัณฑ์: 1 x EA
 • Element Type: Band Heater
 • Power Rating: 235 W
 • Supply Voltage: 230 V ac
 • Diameter: 38 mm



9209956 Band Heater

HEATING ELEMENT, 345 W, 230 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Band Heater
 - Power Rating: 345 W
 - Supply Voltage: 230 V ac
 - Diameter: 40 mm



9209962 Band Heater

HEATING ELEMENT, 415 W, 230 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Band Heater
 - Power Rating: 415 W
 - Supply Voltage: 230 V ac
 - Diameter: 60 mm



9209966 Band Heater

HEATING ELEMENT, 270 W, 230 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Band Heater
 - Power Rating: 270 W
 - Supply Voltage: 230 V ac
 - Diameter: 40 mm



9209969 Band Heater

NOZZLE HEATER, 40X38MM, 300W, 230V

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Band Heater
 - Power Rating: 300 W
 - Supply Voltage: 230 V ac
 - Diameter: 40 mm



9209975 Band Heater

HEATING ELEMENT, 390 W, 230 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Band Heater
 - Power Rating: 390 W
 - Supply Voltage: 230 V ac
 - Diameter: 50 mm



9209981 Band Heater

HEATING ELEMENT, 375 W, 230 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Band Heater
 - Power Rating: 375 W
 - Supply Voltage: 230 V ac
 - Diameter: 60 mm



9209984 Band Heater

HEATING ELEMENT, 440 W, 230 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Band Heater
 - Power Rating: 440 W
 - Supply Voltage: 230 V ac
 - Diameter: 70 mm



9209988 Band Heater

HEATING ELEMENT, 560 W, 230 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Band Heater
 - Power Rating: 560 W
 - Supply Voltage: 230 V ac
 - Diameter: 70 mm



9209997 Band Heater

HEATING ELEMENT, 750 W, 230 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Mica Strip
 - Power Rating: 750 W
 - Supply Voltage: 230 V ac



9210023 Mica Strip

HEATING ELEMENT, 600 W, 230 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Mica Strip
 - Power Rating: 600 W
 - Supply Voltage: 230 V ac



9210032 Mica Strip

HEATING ELEMENT, 400 W, 230 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Mica Strip
 - Power Rating: 400 W
 - Supply Voltage: 230 V ac



9210035 Mica Strip

HEATING ELEMENT, 950 W, 230 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Mica Strip
 - Power Rating: 950 W
 - Supply Voltage: 230 V ac



9210039 Mica Strip

HEATING ELEMENT, 450 W, 230 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Mica Strip
 - Power Rating: 450 W
 - Supply Voltage: 230 V ac



9210041 Mica Strip

HEATING ELEMENT, 850 W, 230 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Mica Strip
 - Power Rating: 850 W
 - Supply Voltage: 230 V ac



9210054 Mica Strip

HEATING ELEMENT, 550 W, 230 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Mica Strip
 - Power Rating: 550 W
 - Supply Voltage: 230 V ac



9210057 Mica Strip

HEATING ELEMENT, 1.45 KW, 230 V AC


- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Mica Strip
 - Power Rating: 1.45 kW
 - Supply Voltage: 230 V ac



9210067 Mica Strip

HEATING ELEMENT, 2 KW, 230 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Mica Strip
 - Power Rating: 2 kW
 - Supply Voltage: 230 V ac


9210073 Mica Strip

HEATING ELEMENT, 700 W, 230 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Mica Strip
 - Power Rating: 700 W
 - Supply Voltage: 230 V ac


9210079 Mica Strip

HEATING ELEMENT, 1.6 KW, 230 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Mica Strip
 - Power Rating: 1.6 kW
 - Supply Voltage: 230 V ac


9210082 Mica Strip

HEATING ELEMENT, 800 W, 230 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Element Type: Mica Strip
 - Power Rating: 800 W
 - Supply Voltage: 230 V ac


9210089 Mica Strip

INFRARED TEMPERATURE SENSOR

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: V Output Signal
 - Response Time: 250 ms
 - Accuracy: $\pm 1.5^{\circ}\text{C}$ or $\pm 1.5\%$ of reading
 - Cable Length: 1 m
 - Supply Voltage: 24 V dc
 - Minimum Temperature Sensed: 0 $^{\circ}\text{C}$
 - Output Type: Alarm, Analogue
 - Light Source: Infrared


1618103 V Output Signal

RS PRO V OUTPUT SIGNAL UART, USB INFRARED TEMPERATURE SENSOR, 1M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: V Output Signal
 - Response Time: 250 ms
 - Accuracy: $\pm 1.5^{\circ}\text{C}$ or $\pm 1.5\%$ of reading
 - Cable Length: 1 m
 - Supply Voltage: 24 V dc
 - Minimum Temperature Sensed: 0 $^{\circ}\text{C}$
 - Output Type: Alarm, Analogue
 - Maximum Temperature Sensed: +1000 $^{\circ}\text{C}$


2387241 V Output Signal

DIGITAL PROCESS INDICATOR, 77X35MM DIMEN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Properties Measured: Current, Voltage
 - Display Type: Digital
 - Cutout Height: 71 mm
 - Cutout Width: 29 mm
 - Depth: 62.5 mm
 - Number of Digits: 4
 - Meter Type: Process Indicator


1981166 Current, Voltage

THERMOMETER, PLATINUM RESISTANCE, PT100, STAINLESS

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Probe Length: 100 mm
 - Probe Diameter: 3 mm
 - Minimum Temperature Sensed: -50 $^{\circ}\text{C}$
 - Maximum Temperature Sensed: +200 $^{\circ}\text{C}$
 - Termination Type: Lead Wire
 - Cable Length: 1 m
 - Probe Material: Stainless Steel


158985 PT100

RS PRO PT100 RTD SENSOR, 6MM DIA, 200MM LONG, 4 WIRE, PROBE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Probe Length: 200 mm
 - Probe Diameter: 6 mm
 - Minimum Temperature Sensed: -50 $^{\circ}\text{C}$
 - Maximum Temperature Sensed: +450 $^{\circ}\text{C}$
 - Termination Type: Connection Head
 - Probe Material: Stainless Steel
 - Process Connection: Probe


285633 PT100

RS PRO PT100 RTD SENSOR, 6MM DIA, 400MM LONG, 4 WIRE, PROBE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Probe Length: 400 mm
 - Probe Diameter: 6 mm
 - Minimum Temperature Sensed: -50 $^{\circ}\text{C}$
 - Maximum Temperature Sensed: +450 $^{\circ}\text{C}$
 - Termination Type: Connection Head
 - Probe Material: Stainless Steel
 - Process Connection: Probe


285649 PT100

RS PRO PT100 RTD SENSOR, 6MM DIA, 600MM LONG, 4 WIRE, PROBE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Probe Length: 600 mm
 - Probe Diameter: 6 mm
 - Minimum Temperature Sensed: -50 $^{\circ}\text{C}$
 - Maximum Temperature Sensed: +450 $^{\circ}\text{C}$
 - Termination Type: Connection Head
 - Probe Material: Stainless Steel
 - Process Connection: Probe


285655 PT100

THERMOMETER, PLATINUM RESISTANCE, PT100, PATCH, SELF

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Probe Length: 40 mm
 - Probe Diameter: 13 mm
 - Minimum Temperature Sensed: -50 $^{\circ}\text{C}$
 - Maximum Temperature Sensed: +150 $^{\circ}\text{C}$
 - Termination Type: Lead Wire
 - Cable Length: 2 m
 - Probe Material: Aluminium Foil Backing, Silicone Rubber


285661 PT100

RS PRO PT100 RTD SENSOR, +70°C MAX

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Minimum Temperature Sensed: -30 $^{\circ}\text{C}$
 - Maximum Temperature Sensed: +70 $^{\circ}\text{C}$


813862 PT100

RS PRO PT100 RTD SENSOR, +70°C MAX

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Minimum Temperature Sensed: -30 $^{\circ}\text{C}$
 - Maximum Temperature Sensed: +70 $^{\circ}\text{C}$


813878 PT100

RS PRO PT100 RTD SENSOR, +110°C MAX

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Minimum Temperature Sensed: -30 $^{\circ}\text{C}$
 - Maximum Temperature Sensed: +110 $^{\circ}\text{C}$, +40 $^{\circ}\text{C}$


813890 PT100

RS PRO PT100 RTD SENSOR, 2.8MM DIA, 15MM LONG, 2 WIRE, PROBE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Probe Length: 15 mm
 - Probe Diameter: 2.8 mm
 - Minimum Temperature Sensed: -50 $^{\circ}\text{C}$
 - Maximum Temperature Sensed: +350 $^{\circ}\text{C}$
 - Termination Type: Lead Wire
 - Cable Length: 300 mm
 - Probe Material: Glass Fibre


1104460 PT100

RS PRO PT100 RTD SENSOR, 4.5MM DIA, 200MM LONG, 4 WIRE, PROBE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Probe Length: 200 mm
 - Probe Diameter: 4.5 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Cable
 - Cable Length: 2 m
 - Probe Material: Stainless Steel



1235599 PT100

PRTD PT100, 6MM X 50MM 2 MTR CABLE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Probe Length: 50 mm
 - Probe Diameter: 6 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Cable
 - Cable Length: 2 m
 - Probe Material: Stainless Steel



1235600 PT100

PRTD PT100, 6MM X 100MM 2 MTR CABLE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Probe Length: 100 mm
 - Probe Diameter: 6 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Cable
 - Cable Length: 2 m
 - Probe Material: Stainless Steel



1235602 PT100

RS PRO PT100 RTD SENSOR, 6MM DIA, 125MM LONG, 4 WIRE, PROBE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Probe Length: 125 mm
 - Probe Diameter: 6 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Cable
 - Cable Length: 2 m
 - Probe Material: Stainless Steel



1235603 PT100

PRTD PT100, 6MM X 150MM 2 MTR CABLE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Probe Length: 150 mm
 - Probe Diameter: 6 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Cable
 - Cable Length: 2 m
 - Probe Material: Stainless Steel



1235604 PT100

PRTD PT100, 6MM X 300MM 2 MTR CABLE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Probe Length: 300 mm
 - Probe Diameter: 6 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Cable
 - Cable Length: 2 m
 - Probe Material: Stainless Steel



1235606 PT100

PRTD PT100, 4MM X 25MM 1 MTR CABLE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Probe Length: 25 mm
 - Probe Diameter: 4 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +200 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Probe Material: Stainless Steel



1235607 PT100

PRTD PT100, 4MM X 40MM 1 MTR CABLE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Probe Length: 40 mm
 - Probe Diameter: 4 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +200 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Probe Material: Stainless Steel



1235608 PT100

RS PRO PT100 RTD SENSOR, 4MM DIA, 65MM LONG, 4 WIRE, PROBE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Probe Length: 65 mm
 - Probe Diameter: 4 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +200 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Probe Material: Stainless Steel



1235609 PT100

PRTD PT1000, 4MM X 40MM 1 MTR CABLE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT1000
 - Probe Length: 40 mm
 - Probe Diameter: 4 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +200 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Probe Material: Stainless Steel



1235612 PT1000

RS PRO PT1000 RTD SENSOR, 4MM DIA, 75MM LONG, 2 WIRE, PROBE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT1000
 - Probe Length: 75 mm
 - Probe Diameter: 4 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +200 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Probe Material: 316 Stainless Steel



1365901 PT1000

PT1000 PLATINUM RESISTANCE THERMOMETER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT1000
 - Probe Length: 125 mm
 - Probe Diameter: 4 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +200 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Probe Material: 316 Stainless Steel



1365902 PT1000

RS PRO PT100 RTD SENSOR, 0.9MM DIA, 15MM LONG, PROBE, +650°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Probe Length: 15 mm
 - Probe Diameter: 0.9 mm
 - Minimum Temperature Sensed: -200 °C
 - Maximum Temperature Sensed: +650 °C
 - Termination Type: Solder
 - Probe Material: Alumina Ceramic (Body)
 - Process Connection: Probe



1741656 PT100

RS PRO PT100 RTD SENSOR, 2.8MM DIA, 25MM LONG, PROBE, +650°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Probe Length: 25 mm
 - Probe Diameter: 2.8 mm
 - Minimum Temperature Sensed: -200 °C
 - Maximum Temperature Sensed: +650 °C
 - Termination Type: Solder
 - Probe Material: Alumina Ceramic (Body)
 - Process Connection: Probe



1741659 PT100

RS PRO PT100 RTD SENSOR, 6MM DIA, 150MM LONG, G1/4, +850°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Probe Length: 150 mm
 - Probe Diameter: 6 mm
 - Minimum Temperature Sensed: -200 °C
 - Maximum Temperature Sensed: +850 °C
 - Termination Type: Connection Head
 - Probe Material: Stainless Steel
 - Process Connection: G1/4



1747512 PT100

RS PRO PT100 RTD SENSOR, 6MM DIA, 200MM LONG, G1/4, +850°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Probe Length: 200 mm
 - Probe Diameter: 6 mm
 - Minimum Temperature Sensed: -200 °C
 - Maximum Temperature Sensed: +850 °C
 - Termination Type: Connection Head
 - Probe Material: Stainless Steel
 - Process Connection: G1/4



1747513 PT100

RS PRO PT100 RTD SENSOR, 6MM DIA, 100MM LONG, NPT 1/4, +850°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Type: PT100
 - Probe Length: 100 mm
 - Probe Diameter: 6 mm
 - Minimum Temperature Sensed: -200 °C
 - Maximum Temperature Sensed: +850 °C
 - Termination Type: Connection Head
 - Probe Material: Stainless Steel
 - Process Connection: NPT 1/4



1747526 PT100

RS PRO PT100 RTD SENSOR, 6MM DIA, 150MM LONG, NPT 1/4, +850°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Type: PT100
 - Probe Length: 150 mm
 - Probe Diameter: 6 mm
 - Minimum Temperature Sensed: -200 °C
 - Maximum Temperature Sensed: +850 °C
 - Termination Type: Connection Head
 - Probe Material: Stainless Steel
 - Process Connection: NPT 1/4



1747527 PT100

RS PRO PT100 RTD SENSOR, 6MM DIA, 400MM LONG, NPT 1/4, +850°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Type: PT100
 - Probe Length: 400 mm
 - Probe Diameter: 6 mm
 - Minimum Temperature Sensed: -200 °C
 - Maximum Temperature Sensed: +850 °C
 - Termination Type: Connection Head
 - Probe Material: Stainless Steel
 - Process Connection: NPT 1/4



1747531 PT100

PLATINUM RESISTANCE PT1000 CLASS B SENSO

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Type: PT1000
 - Probe Length: 25 mm
 - Probe Diameter: 4 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +200 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Probe Material: 316 Stainless Steel



1780974 PT1000

RS PRO PT1000 RTD SENSOR, 4MM DIA, 150MM LONG, 2 WIRE, PROBE,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Type: PT1000
 - Probe Length: 150 mm
 - Probe Diameter: 4 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +200 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Probe Material: 316 Stainless Steel



1780975 PT1000

RS PRO PT100 RTD SENSOR, 2MM DIA, 10MM LONG, CHIP, CLASS B

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Type: PT100
 - Probe Length: 10 mm
 - Probe Diameter: 2 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +600 °C
 - Termination Type: Solder
 - Process Connection: Chip
 - Accuracy: Class B



1811980 PT100

SENSOR PT-100

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Type: PT100
 - Probe Length: 2 mm
 - Probe Diameter: 2 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +600 °C
 - Termination Type: Solder
 - Process Connection: Chip
 - Accuracy: Class A



1812028 PT100

RS PRO PT100 RTD SENSOR, 6MM DIA, 100MM LONG, 2 X 3 WIRE, G1/2,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Type: PT100
 - Probe Length: 100 mm
 - Probe Diameter: 6 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: KNE Terminal Head
 - Probe Material: 316 Stainless Steel
 - Process Connection: G1/2



2000588 PT100

RS PRO PT100 RTD SENSOR, 6MM DIA, 250MM LONG, 2 X 3 WIRE,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Type: PT100
 - Probe Length: 250 mm
 - Probe Diameter: 6 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: KNE Terminal Head
 - Probe Material: 316 Stainless Steel
 - Process Connection: Probe



2000592 PT100

RS PRO PT100 RTD SENSOR, 6MM DIA, 75MM LONG, 3 WIRE, G1/2,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Type: PT100
 - Probe Length: 75 mm
 - Probe Diameter: 6 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +250 °C
 - Probe Material: 316 Stainless Steel
 - Process Connection: G1/2
 - Number Of Wires: 3



2000594 PT100

RS PRO PT100 RTD SENSOR, 6MM DIA, 150MM LONG, 3 WIRE, G1/2,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Type: PT100
 - Probe Length: 150 mm
 - Probe Diameter: 6 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +250 °C
 - Probe Material: 316 Stainless Steel
 - Process Connection: G1/2
 - Number Of Wires: 3



2000596 PT100

RS PRO PT100 RTD SENSOR, 6MM DIA, 300MM LONG, 3 WIRE, PROBE,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Type: PT100
 - Probe Length: 300 mm
 - Probe Diameter: 6 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +250 °C
 - Probe Material: 316 Stainless Steel
 - Process Connection: Probe
 - Number Of Wires: 3



2000598 PT100

RS PRO PT100 RTD SENSOR, 6MM DIA, 150MM LONG, 4 WIRE, PROBE,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Type: PT100
 - Probe Length: 150 mm
 - Probe Diameter: 6 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Probe Material: Stainless Steel



2364261 PT100

PROBE, INDUSTRIAL PT100, 6MM DIA X 250MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Type: PT100
 - Probe Length: 250 mm
 - Probe Diameter: 6 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Probe Material: Stainless Steel



2364277 PT100

SENSOR, TEMPERATURE, EXTERNAL/C OLD STORE, PT100

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Type: PT100
 - Probe Length: 75 mm
 - Probe Diameter: 12.7 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +150 °C
 - Termination Type: Cable Gland
 - Probe Material: Stainless Steel
 - Process Connection: Wall



2364283 PT100

SENSOR, TEMPERATURE, PRECISION, PT100

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Type: PT100
 - Probe Length: 250 mm
 - Probe Diameter: 6 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Cable
 - Cable Length: 2 m
 - Probe Material: Stainless Steel



2364299 PT100

ELEMENT, PLATINUM FILM, PT100, THIN FILM TECHNOLOGY

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Probe Length: 10 mm
 - Probe Diameter: 2 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +500 °C
 - Termination Type: Solder
 - Probe Material: Platinum
 - Process Connection: Chip


2371607 PT100

ELEMENT, PLATINUM FILM, PT100, THIN FILM TECHNOLOGY, STAINLESS STEEL

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Probe Length: 35 mm
 - Probe Diameter: 6 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Lead Wire
 - Cable Length: 1 m
 - Probe Material: Stainless Steel


2371613 PT100

RS PRO PT100 RTD SENSOR, 5MM DIA, 35MM LONG, 4 WIRE, PROBE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Probe Length: 35 mm
 - Probe Diameter: 5 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +450 °C
 - Termination Type: Lead Wire
 - Cable Length: 450 mm
 - Probe Material: Platinum


2371635 PT100

SENSOR, TUBULAR CERAMIC ENCASED, PT100, 2 WIRE, MULTI

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Probe Length: 35 mm
 - Probe Diameter: 5 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Lead Wire
 - Cable Length: 50 mm
 - Probe Material: Platinum


2371641 PT100

SENSOR, TUBULAR CERAMIC ENCASED, PT100, 2 WIRE, MULTI

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Probe Length: 35 mm
 - Probe Diameter: 5 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Lead Wire
 - Cable Length: 450 mm
 - Probe Material: Platinum


2371657 PT100

CONNECTOR, PT 100 PROBE, 4 WIRE OUTPUT, 1M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Probe Length: 150 mm
 - Probe Diameter: 4 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Lead Wire
 - Cable Length: 1 m
 - Probe Material: Stainless Steel


2371663 PT100

RS PRO PT100 RTD SENSOR, 2MM DIA, 5MM LONG, 2 WIRE, CHIP,

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Sensor Type: PT100
 - Probe Length: 5 mm
 - Probe Diameter: 2 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +500 °C
 - Termination Type: Solder
 - Probe Material: Platinum
 - Process Connection: Chip


2905070 PT100

PROBE PT100

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT1000
 - Probe Length: 10 mm
 - Probe Diameter: 2 mm
 - Minimum Temperature Sensed: -70 °C
 - Maximum Temperature Sensed: +550 °C
 - Termination Type: Solder
 - Process Connection: Chip
 - Accuracy: Class 1/3 B


2938446 PT1000

RS PRO PT100 RTD SENSOR, 1.6MM DIA, 8MM LONG, PROBE, CLASS 1/10

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Probe Length: 8 mm
 - Probe Diameter: 1.6 mm
 - Minimum Temperature Sensed: -200 °C
 - Maximum Temperature Sensed: +600 °C
 - Termination Type: Solder
 - Probe Material: Platinum
 - Process Connection: Probe


2938480 PT100

RS PRO PT100 RTD SENSOR, 2.8MM DIA, 25MM LONG, PROBE, CLASS A

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Probe Length: 25 mm
 - Probe Diameter: 2.8 mm
 - Minimum Temperature Sensed: -200 °C
 - Maximum Temperature Sensed: +600 °C
 - Termination Type: Solder
 - Probe Material: Platinum
 - Process Connection: Probe


2938496 PT100

RS PRO RTD SENSOR, +40°C MAX

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Minimum Temperature Sensed: 0 °C
 - Maximum Temperature Sensed: +40 °C


3122939 0 °C

RS PRO RTD SENSOR, +50°C MAX

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Minimum Temperature Sensed: -20 °C
 - Maximum Temperature Sensed: +50 °C


3122945 -20 °C

RS PRO RTD SENSOR, +50°C MAX

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Minimum Temperature Sensed: -20 °C
 - Maximum Temperature Sensed: +50 °C


3122951 -20 °C

TEMP SENSOR, PT1000, 6MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT1000
 - Probe Length: 100 mm
 - Probe Diameter: 6 mm
 - Minimum Temperature Sensed: -20 °C
 - Maximum Temperature Sensed: +100 °C
 - Termination Type: Cable
 - Cable Length: 2 m
 - Probe Material: Stainless Steel


3342616 PT1000

SENSOR, AIR/TEMPERATURE, CLEAN ROOM, PT00

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Minimum Temperature Sensed: 0 °C
 - Maximum Temperature Sensed: +70 °C
 - Termination Type: Cable Gland
 - Process Connection: Wall
 - Accuracy: Class B


3389491 PT100

SENSOR, TEMPERATURE, THERMOCOUPLE, PLATINUM, THIN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Probe Length: 10 mm
 - Probe Diameter: 2 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +500 °C
 - Termination Type: Solder
 - Probe Material: Platinum
 - Process Connection: Chip


3629799 PT100

SENSOR,TEMPERATURE,THERMOCOUPLE,PLATINUM,THIN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Probe Length: 10 mm
 - Probe Diameter: 2 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +500 °C
 - Termination Type: Solder
 - Probe Material: Platinum
 - Process Connection: Chip



3629812 PT100

SENSOR,TEMPERATURE,THERMOCOUPLE,PLATINUM,THIN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Probe Length: 2.3 mm
 - Probe Diameter: 2 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +500 °C
 - Termination Type: Solder
 - Probe Material: Platinum
 - Process Connection: Chip



3629834 PT100

SENSOR,TEMPERATURE,THERMOCOUPLE,PLATINUM,THIN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Probe Length: 2.3 mm
 - Probe Diameter: 2 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +500 °C
 - Termination Type: Solder
 - Probe Material: Platinum
 - Process Connection: Chip



3629840 PT100

SENSOR,TEMPERATURE,THERMOCOUPLE,PLATINUM,THIN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Probe Length: 2.3 mm
 - Probe Diameter: 2 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +500 °C
 - Termination Type: Solder
 - Probe Material: Platinum
 - Process Connection: Chip



3629856 PT100

SENSOR,TEMPERATURE,THERMOCOUPLE,PLATINUM,THIN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT1000
 - Probe Length: 10 mm
 - Probe Diameter: 2 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +500 °C
 - Termination Type: Solder
 - Probe Material: Platinum
 - Process Connection: Chip



3629907 PT1000

SENSOR,TEMPERATURE,THERMOCOUPLE,PLATINUM,THIN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT1000
 - Probe Length: 10 mm
 - Probe Diameter: 2 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +500 °C
 - Termination Type: Solder
 - Probe Material: Platinum
 - Process Connection: Chip



3629913 PT1000

RS PRO PT100 RTD SENSOR, 3MM DIA, 150MM LONG, 4 WIRE, PROBE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Probe Length: 150 mm
 - Probe Diameter: 3 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Probe Material: Stainless Steel



3629935 PT100

PROBE,INDUSTRIAL,PT100,3MM DIA,250MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Probe Length: 250 mm
 - Probe Diameter: 3 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Probe Material: Stainless Steel



3629941 PT100

TEMPERATURE PROBE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Probe Length: 100 mm
 - Probe Diameter: 6 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +200 °C
 - Termination Type: Cable
 - Cable Length: 2 m
 - Probe Material: Stainless Steel



3730372 PT100

RS PRO PT100 RTD SENSOR, +60°C MAX

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Minimum Temperature Sensed: -10 °C
 - Maximum Temperature Sensed: +60 °C



3761477 PT100

RS PRO PT100 RTD SENSOR, 3MM DIA, 150MM LONG, 4 WIRE, PROBE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Probe Length: 150 mm
 - Probe Diameter: 3 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +500 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Probe Material: Stainless Steel



3971315 PT100

RS PRO PT100 RTD SENSOR, 3MM DIA, 250MM LONG, 4 WIRE, PROBE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Probe Length: 250 mm
 - Probe Diameter: 3 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +500 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Probe Material: Stainless Steel



3971321 PT100

RS PRO PT100 RTD SENSOR, 6MM DIA, 150MM LONG, 4 WIRE, PROBE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Probe Length: 150 mm
 - Probe Diameter: 6 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +500 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Probe Material: Stainless Steel



3971337 PT100

RS PRO PT100 RTD SENSOR, 6MM DIA, 150MM LONG, 2 X 3 WIRE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Probe Length: 150 mm
 - Probe Diameter: 6 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Probe Material: Stainless Steel



3971393 PT100

RS PRO PT100 RTD SENSOR, 6MM DIA, 150MM LONG, 2 X 3 WIRE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Probe Length: 150 mm
 - Probe Diameter: 6 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +500 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Probe Material: Stainless Steel



3971416 PT100

RS PRO PT100 RTD SENSOR, 1.5MM DIA, 15MM LONG, 2 WIRE, PROBE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Probe Length: 15 mm
 - Probe Diameter: 1.5 mm
 - Minimum Temperature Sensed: -200 °C
 - Maximum Temperature Sensed: +650 °C
 - Termination Type: Solder
 - Probe Material: Ceramic
 - Process Connection: Probe



3971595 PT100

RS PRO PT100 RTD SENSOR, 6MM DIA, 150MM LONG, 4 WIRE, CLASS B

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Probe Length: 150 mm
 - Probe Diameter: 6 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +200 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Probe Material: Stainless Steel



3971832 PT100

PT100 PROBE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Probe Length: 60 mm
 - Probe Diameter: 6 mm
 - Minimum Temperature Sensed: -20 °C
 - Maximum Temperature Sensed: +200 °C
 - Termination Type: Cable
 - Cable Length: 2.5 m
 - Probe Material: Stainless Steel



4071387 PT100

RS PRO PT100 RTD SENSOR, 6MM DIA, 100MM LONG, 3 WIRE, G1/2,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Probe Length: 100 mm
 - Probe Diameter: 6 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Connection Head
 - Probe Material: Stainless Steel
 - Process Connection: G1/2



4071624 PT100

RS PRO PT100 RTD SENSOR, 6MM DIA, 250MM LONG, 3 WIRE, G1/2,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Probe Length: 250 mm
 - Probe Diameter: 6 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Connection Head
 - Probe Material: Stainless Steel
 - Process Connection: G1/2



4071630 PT100

SENSOR,PRT,GENERAL PURPOSE,6X50MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Probe Length: 50 mm
 - Probe Diameter: 6 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +200 °C
 - Termination Type: Cable
 - Cable Length: 2 m
 - Probe Material: Stainless Steel



4553968 PT100

RS PRO PT100 RTD SENSOR, 8MM DIA, 250MM LONG, 4 WIRE, G1/2,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Probe Length: 250 mm
 - Probe Diameter: 8 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +450 °C
 - Termination Type: Connection Head
 - Probe Material: Stainless Steel
 - Process Connection: G1/2



4553980 PT100

RS PRO PT100 RTD SENSOR, 6MM DIA, 150MM LONG, 4 WIRE, G1/2,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Probe Length: 150 mm
 - Probe Diameter: 6 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +450 °C
 - Termination Type: Connection Head
 - Probe Material: Stainless Steel
 - Process Connection: G1/2



4554040 PT100

RS PRO PT100 RTD SENSOR, 6MM DIA, 250MM LONG, 4 WIRE, G1/2,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Probe Length: 250 mm
 - Probe Diameter: 6 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +450 °C
 - Termination Type: Connection Head
 - Probe Material: Stainless Steel
 - Process Connection: G1/2



4554056 PT100

RS PRO PT100 RTD SENSOR, 12.7MM DIA, 75MM LONG, 2 X 4 WIRE, WALL,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Probe Length: 75 mm
 - Probe Diameter: 12.7 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +150 °C
 - Termination Type: Cable Gland
 - Probe Material: Stainless Steel
 - Process Connection: Wall



4554208 PT100

BOX,OUTSIDE,AIR,4-20MA


- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Probe Length: 75 mm
 - Probe Diameter: 12.7 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +150 °C
 - Termination Type: Cable Gland
 - Probe Material: Stainless Steel
 - Process Connection: Wall



4554214 PT100

RS PRO PT1000 RTD SENSOR, 2MM DIA, 5MM LONG, CHIP, CLASS B

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT1000
 - Probe Length: 5 mm
 - Probe Diameter: 2 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +600 °C
 - Termination Type: Solder
 - Process Connection: Chip
 - Accuracy: Class B



4573596 PT1000

CAPTEUR PT-1000

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT1000
 - Probe Length: 5 mm
 - Probe Diameter: 2 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +600 °C
 - Termination Type: Solder
 - Process Connection: Chip
 - Accuracy: Class A



4573603 PT1000

SONDE TYPE 109-06

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Probe Length: 10 mm
 - Probe Diameter: 2 mm
 - Minimum Temperature Sensed: 0 °C
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Cable
 - Cable Length: 2 m
 - Process Connection: Probe



4573625 PT100

SONDE DE TEMP. PT1000

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT1000
 - Probe Length: 35 mm
 - Probe Diameter: 6 mm
 - Minimum Temperature Sensed: -20 °C
 - Maximum Temperature Sensed: +100 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Probe Material: Stainless Steel



4573653 PT1000

SONDE PT-100

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Probe Length: 60 mm
 - Probe Diameter: 6 mm
 - Minimum Temperature Sensed: -20 °C
 - Maximum Temperature Sensed: +200 °C
 - Termination Type: Cable
 - Cable Length: 2.5 m
 - Probe Material: Stainless Steel



4573704 PT100

SONDE PT-100

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Probe Length: 30 mm
 - Probe Diameter: 3 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Cable
 - Cable Length: 2 m
 - Probe Material: Stainless Steel



4573710 PT100

RS PRO PT100 RTD SENSOR, 6MM DIA, 300MM LONG, 3 WIRE, PROBE,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Type: PT100
 - Probe Length: 300 mm
 - Probe Diameter: 6 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Connection Head
 - Probe Material: 316 Stainless Steel
 - Process Connection: Probe



5477562 PT100

RS PRO PT100 RTD SENSOR, 8MM DIA, 350MM LONG, 3 WIRE, G1/2,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Type: PT100
 - Probe Length: 350 mm
 - Probe Diameter: 8 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Connection Head
 - Probe Material: Stainless Steel
 - Process Connection: G1/2



5477590 PT100

RS PRO PT100 RTD SENSOR, 8MM DIA, 250MM LONG, 3 WIRE, G1/2,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Type: PT100
 - Probe Length: 250 mm
 - Probe Diameter: 8 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Connection Head
 - Probe Material: Stainless Steel
 - Process Connection: G1/2



5477635 PT100

RS PRO PT100 RTD SENSOR, 8MM DIA, 50MM LONG, 3 WIRE, G1/2,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Type: PT100
 - Probe Length: 50 mm
 - Probe Diameter: 8 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Connection Head
 - Probe Material: Stainless Steel
 - Process Connection: G1/2



5477663 PT100

RS PRO PT100 RTD SENSOR, 8MM DIA, 100MM LONG, 3 WIRE, G1/2,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Type: PT100
 - Probe Length: 100 mm
 - Probe Diameter: 8 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Connection Head
 - Probe Material: Stainless Steel
 - Process Connection: G1/2



5477714 PT100

SENSOR,TEMPERATURE,THERMOCOUPLE,PLATINUM,THIN

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Type: PT100
 - Probe Length: 5 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +500 °C
 - Termination Type: Solder
 - Probe Material: Platinum
 - Process Connection: Chip
 - Number Of Wires: 2



6117788 PT100

SENSOR,TEMPERATURE,SIMPLEX,PLATINUM,PT100,WIREWOUND,2

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Type: PT100
 - Probe Length: 25 mm
 - Probe Diameter: 2.8 mm
 - Minimum Temperature Sensed: -200 °C
 - Maximum Temperature Sensed: +650 °C
 - Termination Type: Solder
 - Probe Material: Platinum
 - Process Connection: Probe



6117794 PT100

SENSOR,TEMPERATURE,THERMOCOUPLE,PLATINUM,THIN

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Type: PT100
 - Probe Length: 5 mm
 - Probe Diameter: 8 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +500 °C
 - Termination Type: Solder
 - Probe Material: Platinum
 - Process Connection: Chip



6117801 PT100

RS PRO PT100 RTD SENSOR, 2.8MM DIA, 25MM LONG, PROBE, CLASS A

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Type: PT100
 - Probe Length: 25 mm
 - Probe Diameter: 2.8 mm
 - Minimum Temperature Sensed: -200 °C
 - Maximum Temperature Sensed: +650 °C
 - Termination Type: Solder
 - Probe Material: Platinum
 - Process Connection: Probe



6117817 PT100

RS PRO PT100 RTD SENSOR, 2.8MM DIA, 15MM LONG, PROBE, CLASS B

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Type: PT100
 - Probe Length: 15 mm
 - Probe Diameter: 2.8 mm
 - Minimum Temperature Sensed: -200 °C
 - Maximum Temperature Sensed: +650 °C
 - Termination Type: Solder
 - Probe Material: Platinum
 - Process Connection: Probe



6117823 PT100

SENSOR,TEMPERATURE,SIMPLEX,PLATINUM,PT100,WIREWOUND,2

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Type: PT100
 - Probe Length: 15 mm
 - Probe Diameter: 1.5 mm
 - Minimum Temperature Sensed: -200 °C
 - Maximum Temperature Sensed: +650 °C
 - Termination Type: Solder
 - Probe Material: Platinum
 - Process Connection: Probe



6117839 PT100

RS PRO PT100 RTD SENSOR, 2.8MM DIA, 15MM LONG, PROBE, CLASS A

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Type: PT100
 - Probe Length: 15 mm
 - Probe Diameter: 2.8 mm
 - Minimum Temperature Sensed: -200 °C
 - Maximum Temperature Sensed: +650 °C
 - Termination Type: Solder
 - Probe Material: Platinum
 - Process Connection: Probe



6117845 PT100

SENSOR,TEMPERATURE,SIMPLEX,PLATINUM,PT100,WIREWOUND,2

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Type: PT100
 - Probe Length: 8 mm
 - Probe Diameter: 1.5 mm
 - Minimum Temperature Sensed: -200 °C
 - Maximum Temperature Sensed: +650 °C
 - Termination Type: Solder
 - Probe Material: Platinum
 - Process Connection: Probe



6117851 PT100

SENSOR,TEMPERATURE,SIMPLEX,PLATINUM,PT100,WIREWOUND,2

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Type: PT100
 - Probe Length: 15 mm
 - Probe Diameter: 1.5 mm
 - Minimum Temperature Sensed: -200 °C
 - Maximum Temperature Sensed: +650 °C
 - Termination Type: Solder
 - Probe Material: Platinum
 - Process Connection: Probe



6117867 PT100

SENSOR,TEMPERATURE,SIMPLEX,PLATINUM,PT100,WIREWOUND,2

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Type: PT100
 - Probe Length: 8 mm
 - Probe Diameter: 1.5 mm
 - Minimum Temperature Sensed: -200 °C
 - Maximum Temperature Sensed: +650 °C
 - Termination Type: Solder
 - Probe Material: Platinum
 - Process Connection: Probe



6117873 PT100

SENSOR,PRT,GENERAL PURPOSE,6X100MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Type: PT100
 - Probe Length: 100 mm
 - Probe Diameter: 6 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +200 °C
 - Termination Type: Cable
 - Cable Length: 2 m
 - Probe Material: Stainless Steel



6118264 PT100

THIN FILM PT100 DETECT 1.6X1.2MM CLASS B

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Probe Length: 1.6 mm
 - Probe Diameter: 1.2 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +500 °C
 - Termination Type: Solder
 - Probe Material: Platinum
 - Process Connection: Chip



6667353 PT100

RS PRO PT100 RTD SENSOR, 1MM DIA, 3MM LONG, CHIP, CLASS B +500°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Probe Length: 3 mm
 - Probe Diameter: 1 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +500 °C
 - Termination Type: Solder
 - Probe Material: Platinum
 - Process Connection: Chip



6667356 PT100

THIN FILM PT100 DETECTOR, 3X1MM, CLASS A

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Probe Length: 3 mm
 - Probe Diameter: 1 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +500 °C
 - Termination Type: Solder
 - Probe Material: Platinum
 - Process Connection: Chip



6667359 PT100

THIN FILM PT100 DETECT 1.6X1.2MM CLASS A

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Probe Length: 1.6 mm
 - Probe Diameter: 1.2 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +500 °C
 - Termination Type: Solder
 - Probe Material: Platinum
 - Process Connection: Chip



6667362 PT100

RS PRO PT1000 RTD SENSOR, 15MM DIA, 30MM LONG, 2 WIRE, PATCH

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT1000
 - Probe Length: 30 mm
 - Probe Diameter: 15 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +150 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Probe Material: Aluminium Foil Backing, Silicone Rubber



7621130 PT1000

PT100 PROBE 1MTR TEFLON LEAD

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Probe Length: 25 mm
 - Probe Diameter: 3 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +200 °C
 - Termination Type: Lead Wire
 - Cable Length: 1 m
 - Probe Material: Stainless Steel



7621134 PT100

PT100 4 WIRE 5MTS TEFLON LEAD

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Probe Length: 40 mm
 - Probe Diameter: 13 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +150 °C
 - Termination Type: Lead Wire
 - Cable Length: 5 m
 - Probe Material: Aluminium Foil Backing, Silicone Rubber



7621137 PT100

PT100 PROBE 3.0X50MM B 1MTR TEFLON LEAD

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Probe Length: 50 mm
 - Probe Diameter: 3 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +200 °C
 - Termination Type: Lead Wire
 - Cable Length: 1 m
 - Probe Material: Stainless Steel



7621143 PT100

RS PRO PT100 RTD SENSOR, 1.2MM DIA, CHIP, +500°C MAX

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Probe Diameter: 1.2 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +500 °C
 - Termination Type: Solder
 - Process Connection: Chip



8140162 PT100

RS PRO PT100 RTD SENSOR, 1.2MM DIA, CHIP, +500°C MAX


- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Probe Diameter: 1.2 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +500 °C
 - Termination Type: Solder
 - Process Connection: Chip



8140165 PT100

RS PRO PT100 RTD SENSOR, 1.2MM DIA, CHIP, +500°C MAX

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Probe Diameter: 1.2 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +500 °C
 - Termination Type: Solder
 - Process Connection: Chip



8140169 PT100

RS PRO PT1000 RTD SENSOR, 1.25MM DIA, CHIP, +500°C MAX

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT1000
 - Probe Diameter: 1.25 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +500 °C
 - Termination Type: Solder
 - Process Connection: Chip



8140175 PT1000

RS PRO PT1000 RTD SENSOR, 2MM DIA, CHIP, +500°C MAX

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT1000
 - Probe Diameter: 2 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +500 °C
 - Termination Type: Solder
 - Process Connection: Chip



8140178 PT1000

RS PRO PT100 RTD SENSOR, 6MM DIA, 150MM LONG, 3 WIRE, G1/2,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Probe Length: 150 mm
 - Probe Diameter: 6 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +450 °C
 - Termination Type: Connection Head
 - Probe Material: Stainless Steel
 - Process Connection: G1/2



8722701 PT100

RS PRO PT100 RTD SENSOR, 6MM DIA, 150MM LONG, 3 WIRE, G1/2,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Probe Length: 150 mm
 - Probe Diameter: 6 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +450 °C
 - Termination Type: Connection Head
 - Probe Material: Stainless Steel
 - Process Connection: G1/2



8722705 PT100

RS PRO PT100 RTD SENSOR, 6MM DIA, 100MM LONG, 4 WIRE, PROBE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Probe Length: 100 mm
 - Probe Diameter: 6 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +450 °C
 - Termination Type: Connection Head
 - Probe Material: Stainless Steel
 - Process Connection: Probe



8722717 PT100

RS PRO PT100 RTD SENSOR, 6MM DIA, 200MM LONG, 4 WIRE, PROBE,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Type: PT100
 - Probe Length: 200 mm
 - Probe Diameter: 6 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +450 °C
 - Termination Type: Connection Head
 - Probe Material: Stainless Steel
 - Process Connection: Probe



8722720 PT100

RS PRO PT100 RTD SENSOR, 6MM DIA, 250MM LONG, 4 WIRE, PROBE,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Type: PT100
 - Probe Length: 250 mm
 - Probe Diameter: 6 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +450 °C
 - Termination Type: Connection Head
 - Probe Material: Stainless Steel
 - Process Connection: Probe



8722723 PT100

RS PRO PT100 RTD SENSOR, 6MM DIA, 300MM LONG, 4 WIRE, PROBE,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Type: PT100
 - Probe Length: 300 mm
 - Probe Diameter: 6 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +450 °C
 - Termination Type: Connection Head
 - Probe Material: Stainless Steel
 - Process Connection: Probe



8722727 PT100

RS PRO PT100 RTD SENSOR, 6MM DIA, 150MM LONG, 4 WIRE, PROBE,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Type: PT100
 - Probe Length: 150 mm
 - Probe Diameter: 6 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +450 °C
 - Termination Type: Connection Head
 - Probe Material: Stainless Steel
 - Process Connection: Probe



8722739 PT100

RS PRO PT100 RTD SENSOR, 6MM DIA, 300MM LONG, 4 WIRE, CLASS B

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Type: PT100
 - Probe Length: 300 mm
 - Probe Diameter: 6 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +450 °C
 - Termination Type: Connection Head
 - Probe Material: Stainless Steel
 - Number Of Wires: 4



8722745 PT100

RS PRO PT100 RTD SENSOR, 6MM DIA, 500MM LONG, 4 WIRE, PROBE,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Type: PT100
 - Probe Length: 500 mm
 - Probe Diameter: 6 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +450 °C
 - Termination Type: Connection Head
 - Probe Material: Stainless Steel
 - Process Connection: Probe



8722749 PT100

PT100 2X10 CLASS B 300 MM LEADS, 7/0.2

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Type: PT100
 - Probe Length: 10 mm
 - Probe Diameter: 2 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Lead Wire
 - Cable Length: 300 mm
 - Probe Material: Platinum



8919132 PT100

PT100 2X10 CLASS B 500 MM LEADS, 7/0.2

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Type: PT100
 - Probe Length: 10 mm
 - Probe Diameter: 2 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Lead Wire
 - Cable Length: 500 mm
 - Probe Material: Platinum



8919135 PT100

PT100 2X10 CLASS B 1000 MM LEADS, 7/0.2

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Type: PT100
 - Probe Length: 10 mm
 - Probe Diameter: 2 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Lead Wire
 - Cable Length: 1 m
 - Probe Material: Platinum



8919139 PT100

PT100 2X10 CLASS A 500 MM LEADS, 7/0.15

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Type: PT100
 - Probe Length: 10 mm
 - Probe Diameter: 2 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Lead Wire
 - Cable Length: 500 mm
 - Probe Material: Platinum



8919141 PT100

PT100 2X10 CLASS A 1000 MM LEADS, 7/0.15

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Type: PT100
 - Probe Length: 10 mm
 - Probe Diameter: 2 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Lead Wire
 - Cable Length: 1 m
 - Probe Material: Platinum



8919145 PT100

PT100 2X10 CLASS A 300 MM LEADS, 7/0.15

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Type: PT100
 - Probe Length: 10 mm
 - Probe Diameter: 2 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Lead Wire
 - Cable Length: 300 mm
 - Probe Material: Platinum



8919148 PT100

PT1000 2X10 CLASS B 1000 MM LEADS, 7/0.2

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Type: PT1000
 - Probe Length: 10 mm
 - Probe Diameter: 2 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Lead Wire
 - Cable Length: 1 m
 - Probe Material: Platinum



8919151 PT1000

PT1000 2X10 CLASS B 300 MM LEADS, 7/0.2

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Type: PT1000
 - Probe Length: 10 mm
 - Probe Diameter: 2 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Lead Wire
 - Cable Length: 300 mm
 - Probe Material: Platinum



8919154 PT1000

PT1000 2X10 CLASS B 500 MM LEADS, 7/0.2

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Type: PT1000
 - Probe Length: 10 mm
 - Probe Diameter: 2 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Lead Wire
 - Cable Length: 500 mm
 - Probe Material: Platinum



8919157 PT1000

PT100/1528 CLASS B 1000 MM LEADS, 1/0.4

- ขนาดบรรจุภัณฑ์: 1 x EA
- Sensor Type: PT100
 - Probe Length: 15 mm
 - Probe Diameter: 2.8 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +350 °C
 - Termination Type: Lead Wire
 - Cable Length: 1 m
 - Probe Material: Platinum



8919163 PT100

RS PRO PT100 RTD SENSOR, 5MM DIA, 50MM LONG, +100°C MAX

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Probe Length: 50 mm
 - Probe Diameter: 5 mm
 - Minimum Temperature Sensed: -20 °C
 - Maximum Temperature Sensed: +100 °C
 - Termination Type: Cable
 - Cable Length: 1.5 m
 - Probe Material: Stainless Steel



8968395 PT100

RTD 5X50 PT1000 2 WIRES CABLE LG 1,5M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT1000
 - Probe Length: 50 mm
 - Probe Diameter: 5 mm
 - Minimum Temperature Sensed: -20 °C
 - Maximum Temperature Sensed: +100 °C
 - Termination Type: Cable
 - Cable Length: 1.5 m
 - Probe Material: Stainless Steel



8968399 PT1000

RTD 1XPT100 6X200 HEAD/SLIDING FITTING

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Probe Length: 200 mm
 - Probe Diameter: 6 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Connection Head
 - Probe Material: Stainless Steel
 - Process Connection: G1/4



8968406 PT100

RTD 1XPT100 5X120 HEAD/THERMOWELL

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Sensor Type: PT100
 - Probe Length: 120 mm
 - Probe Diameter: 5.7 mm
 - Minimum Temperature Sensed: -50 °C
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Connection Head
 - Probe Material: Stainless Steel
 - Process Connection: G1/2



8968415 PT100

GLAND, COMPRESSION, STAINLESS STEEL, 1/8 BSP, 3.0MM DIA BORE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Thermocouple Compression Fitting
 - For Use With: Thermocouple
 - Application: 1/8 BSPT Connector
 - Connector Size: 1/8 BSPT
 - Probe Diameter: 3 mm
 - Standards Met: RoHS Compliant



158610 Thermocouple

RS PRO THERMOCOUPLE COMPRESSION FITTING FOR USE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Thermocouple Compression Fitting
 - For Use With: Thermocouple
 - Application: 1/8 BSPT Connector
 - Connector Size: 1/8 BSPT
 - Probe Diameter: 1.5 mm
 - Standards Met: RoHS Compliant



286715 Thermocouple

RS PRO THERMOCOUPLE COMPRESSION FITTING FOR USE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Thermocouple Compression Fitting
 - For Use With: Thermocouple
 - Application: 1/8 BSPT Connector
 - Connector Size: 1/8 BSPT
 - Probe Diameter: 3 mm
 - Standards Met: RoHS Compliant



286721 Thermocouple

RS PRO THERMOCOUPLE COMPRESSION FITTING FOR USE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Thermocouple Compression Fitting
 - For Use With: Thermocouple
 - Application: 1/8 BSPT Connector
 - Connector Size: 1/8 BSPT
 - Probe Diameter: 4.5 mm
 - Standards Met: RoHS Compliant



286737 Thermocouple

RS PRO THERMOCOUPLE COMPRESSION FITTING FOR USE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Thermocouple Compression Fitting
 - For Use With: Thermocouple
 - Application: 1/2 BSPT Connector
 - Connector Size: 1/2 BSPT
 - Probe Diameter: 6 mm
 - Standards Met: RoHS Compliant



286771 Thermocouple

RS PRO THERMOCOUPLE COMPRESSION FITTING FOR USE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Thermocouple Compression Fitting
 - For Use With: Thermocouple
 - Application: 1/2 BSPT Connector
 - Connector Size: 1/2 BSPT
 - Probe Diameter: 4.5 mm
 - Standards Met: RoHS Compliant



286787 Thermocouple

RS PRO THERMOCOUPLE COMPRESSION FITTING FOR USE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Thermocouple Compression Fitting
 - For Use With: Thermocouple
 - Application: 1/2 BSPT Connector
 - Connector Size: 1/2 BSPT
 - Probe Diameter: 6 mm
 - Standards Met: RoHS Compliant



286793 Thermocouple

RS PRO THERMOCOUPLE FLANGE FOR USE WITH TEMPERATURE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Thermocouple Flange
 - For Use With: Temperature Sensor
 - Application: 1/8 BSPT Flange
 - Connector Size: 1/8 BSP
 - Mounting Type: Chassis Mount
 - Standards Met: RoHS Compliant



286816 Thermocouple

RS PRO BAYONET ADAPTER FOR USE WITH TEMPERATURE SENSOR, 1/8

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Bayonet Adapter
 - For Use With: Temperature Sensor
 - Application: 1/8 BSP Connector
 - Connector Size: 1/8 BSP
 - Probe Diameter: 6 mm
 - Standards Met: RoHS Compliant



286866 Bayonet Adapter

RS PRO BAYONET ADAPTER FOR USE WITH TEMPERATURE SENSOR, 1/8

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Bayonet Adapter
 - For Use With: Temperature Sensor
 - Application: 1/8 BSP Connector
 - Connector Size: 1/8 BSP
 - Standards Met: RoHS Compliant



286872 Bayonet Adapter

RS PRO BAYONET ADAPTER FOR USE WITH TEMPERATURE SENSOR, 1/8

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Bayonet Adapter
 - For Use With: Temperature Sensor
 - Application: 1/8 BSP Connector
 - Connector Size: 1/8 BSP
 - Standards Met: RoHS Compliant



286888 Bayonet Adapter

RS PRO BAYONET ADAPTER FOR USE WITH TEMPERATURE SENSOR, 1/8

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Bayonet Adapter
 - For Use With: Temperature Sensor
 - Application: 1/8 BSP Connector
 - Connector Size: 1/8 BSP
 - Standards Met: RoHS Compliant



286894 Bayonet Adapter

RS PRO BAYONET ADAPTER FOR USE WITH TEMPERATURE SENSOR, 1/8

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Bayonet Adapter
 - For Use With: Temperature Sensor
 - Application: 1/8 BSP Connector
 - Connector Size: 1/8 BSP
 - Probe Diameter: 6 mm
 - Standards Met: RoHS Compliant



286901 Bayonet Adapter

RS PRO BAYONET ADAPTER FOR USE WITH TEMPERATURE SENSOR, M10,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Bayonet Adapter
 - For Use With: Temperature Sensor
 - Application: M10 Connector
 - Connector Size: M10
 - Standards Met: RoHS Compliant



286917 Bayonet Adapter

RS PRO PANEL MOUNT THERMOCOUPLE CONNECTOR FOR

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Thermocouple Connector
 - For Use With: Type J Thermocouple
 - Application: Standard Panel Mount Connector
 - Connector Type: Panel Mount
 - Plug/Socket: Socket
 - Connector Size: Standard
 - Mounting Type: Nylon Clip
 - Standards Met: BS



475583 Thermocouple

RS PRO THERMOCOUPLE COMPRESSION FITTING FOR USE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Thermocouple Compression Fitting
 - For Use With: Thermocouple
 - Application: 1/8 BSPT Connector
 - Connector Size: 1/8 BSPT
 - Probe Diameter: 1/4 in
 - Standards Met: RoHS Compliant



1104475 Thermocouple

RS PRO THERMOCOUPLE COMPRESSION FITTING FOR USE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Thermocouple Compression Fitting
 - For Use With: Thermocouple
 - Application: 1/8 BSP Connector
 - Connector Size: 1/8 BSP
 - Probe Diameter: 1/4 in
 - Standards Met: RoHS Compliant



1104476 Thermocouple

RS PRO IN-LINE THERMOCOUPLE COMPRESSION FITTING FOR USE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Thermocouple Compression Fitting
 - For Use With: Thermocouple
 - Application: 1/8 NPT In-Line Connector
 - Connector Type: In-Line
 - Connector Size: 1/8 NPT
 - Probe Diameter: 4 mm
 - Standards Met: RoHS Compliant



1235558 Thermocouple

RS PRO IN-LINE THERMOCOUPLE COMPRESSION FITTING FOR USE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Thermocouple Compression Fitting
 - For Use With: Thermocouple
 - Application: 1/8 NPT In-Line Connector
 - Connector Type: In-Line
 - Connector Size: 1/8 NPT
 - Probe Diameter: 1 mm
 - Standards Met: RoHS Compliant



1235559 Thermocouple

RS PRO IN-LINE THERMOCOUPLE COMPRESSION FITTING FOR USE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Thermocouple Compression Fitting
 - For Use With: Thermocouple
 - Application: 1/8 NPT In-Line Connector
 - Connector Type: In-Line
 - Connector Size: 1/8 NPT
 - Probe Diameter: 1.5 mm
 - Standards Met: RoHS Compliant



1235560 Thermocouple

RS PRO IN-LINE THERMOCOUPLE COMPRESSION FITTING FOR USE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Thermocouple Compression Fitting
 - For Use With: Thermocouple
 - Application: 1/8 NPT In-Line Connector
 - Connector Type: In-Line
 - Connector Size: 1/8 NPT
 - Probe Diameter: 3 mm
 - Standards Met: RoHS Compliant



1235561 Thermocouple

RS PRO IN-LINE THERMOCOUPLE COMPRESSION FITTING FOR USE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Thermocouple Compression Fitting
 - For Use With: Thermocouple
 - Application: 1/8 NPT In-Line Connector
 - Connector Type: In-Line
 - Connector Size: 1/8 NPT
 - Probe Diameter: 1/8 in
 - Standards Met: RoHS Compliant



1235562 Thermocouple

RS PRO IN-LINE THERMOCOUPLE COMPRESSION FITTING FOR USE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Thermocouple Compression Fitting
 - For Use With: Thermocouple
 - Application: 1/8 NPT In-Line Connector
 - Connector Type: In-Line
 - Connector Size: 1/8 NPT
 - Probe Diameter: 4.5 mm
 - Standards Met: RoHS Compliant



1235563 Thermocouple

RS PRO IN-LINE THERMOCOUPLE COMPRESSION FITTING FOR USE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Thermocouple Compression Fitting
 - For Use With: Thermocouple
 - Application: 1/8 NPT In-Line Connector
 - Connector Type: In-Line
 - Connector Size: 1/8 NPT
 - Probe Diameter: 3/16 in
 - Standards Met: RoHS Compliant



1235564 Thermocouple

RS PRO IN-LINE THERMOCOUPLE COMPRESSION FITTING FOR USE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Thermocouple Compression Fitting
 - For Use With: Thermocouple
 - Application: 1/8 NPT In-Line Connector
 - Connector Type: In-Line
 - Connector Size: 1/8 NPT
 - Probe Diameter: 6 mm
 - Standards Met: RoHS Compliant



1235565 Thermocouple

RS PRO IN-LINE THERMOCOUPLE COMPRESSION FITTING FOR USE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Thermocouple Compression Fitting
 - For Use With: Thermocouple
 - Application: 1/8 NPT In-Line Connector
 - Connector Type: In-Line
 - Connector Size: 1/8 NPT
 - Probe Diameter: 1/4 in
 - Standards Met: RoHS Compliant



1235566 Thermocouple

RS PRO IN-LINE THERMOCOUPLE COMPRESSION FITTING FOR USE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Thermocouple Compression Fitting
 - For Use With: Thermocouple
 - Application: 1/4 NPT In-Line Connector
 - Connector Type: In-Line
 - Connector Size: 1/4 NPT
 - Probe Diameter: 1.5 mm
 - Standards Met: RoHS Compliant



1235567 Thermocouple

RS PRO IN-LINE THERMOCOUPLE COMPRESSION FITTING FOR USE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Thermocouple Compression Fitting
 - For Use With: Thermocouple
 - Application: 1/4 NPT In-Line Connector
 - Connector Type: In-Line
 - Connector Size: 1/4 NPT
 - Probe Diameter: 3 mm
 - Standards Met: RoHS Compliant



1235568 Thermocouple

RS PRO IN-LINE THERMOCOUPLE COMPRESSION FITTING FOR USEขนาดบรรจุภัณฑ์: **1 x EA**

- Accessory Type: Thermocouple Compression Fitting
- For Use With: Thermocouple
- Application: 1/4 NPT In-Line Connector
- Connector Type: In-Line
- Connector Size: 1/4 NPT
- Probe Diameter: 1/8 in
- Standards Met: RoHS Compliant

**1235569** Thermocouple**RS PRO IN-LINE THERMOCOUPLE COMPRESSION FITTING FOR USE**ขนาดบรรจุภัณฑ์: **1 x EA**

- Accessory Type: Thermocouple Compression Fitting
- For Use With: Thermocouple
- Application: 1/4 NPT In-Line Connector
- Connector Type: In-Line
- Connector Size: 1/4 NPT
- Probe Diameter: 4.5 mm
- Standards Met: RoHS Compliant

**1235570** Thermocouple**RS PRO IN-LINE THERMOCOUPLE COMPRESSION FITTING FOR USE**ขนาดบรรจุภัณฑ์: **1 x EA**

- Accessory Type: Thermocouple Compression Fitting
- For Use With: Thermocouple
- Application: 1/4 NPT In-Line Connector
- Connector Type: In-Line
- Connector Size: 1/4 NPT
- Probe Diameter: 3/16 in
- Standards Met: RoHS Compliant

**1235571** Thermocouple**RS PRO IN-LINE THERMOCOUPLE COMPRESSION FITTING FOR USE**ขนาดบรรจุภัณฑ์: **1 x EA**

- Accessory Type: Thermocouple Compression Fitting
- For Use With: Thermocouple
- Application: 1/4 NPT In-Line Connector
- Connector Type: In-Line
- Connector Size: 1/4 NPT
- Probe Diameter: 6 mm
- Standards Met: RoHS Compliant

**1235572** Thermocouple**RS PRO IN-LINE THERMOCOUPLE COMPRESSION FITTING FOR USE**ขนาดบรรจุภัณฑ์: **1 x EA**

- Accessory Type: Thermocouple Compression Fitting
- For Use With: Thermocouple
- Application: 1/2 NPT In-Line Connector
- Connector Type: In-Line
- Connector Size: 1/4 NPT
- Probe Diameter: 1/4 in
- Standards Met: RoHS Compliant

**1235575** Thermocouple**RS PRO IN-LINE THERMOCOUPLE COMPRESSION FITTING FOR USE**ขนาดบรรจุภัณฑ์: **1 x EA**

- Accessory Type: Thermocouple Compression Fitting
- For Use With: Thermocouple
- Application: 1/2 NPT In-Line Connector
- Connector Type: In-Line
- Connector Size: 1/2 NPT
- Probe Diameter: 4.5 mm
- Standards Met: RoHS Compliant

**1235577** Thermocouple**RS PRO IN-LINE THERMOCOUPLE COMPRESSION FITTING FOR USE**ขนาดบรรจุภัณฑ์: **1 x EA**

- Accessory Type: Thermocouple Compression Fitting
- For Use With: Thermocouple
- Application: 1/2 NPT In-Line Connector
- Connector Type: In-Line
- Connector Size: 1/2 NPT
- Probe Diameter: 6 mm
- Standards Met: RoHS Compliant

**1235578** Thermocouple**RS PRO IN-LINE THERMOCOUPLE COMPRESSION FITTING FOR USE**ขนาดบรรจุภัณฑ์: **1 x EA**

- Accessory Type: Thermocouple Compression Fitting
- For Use With: Thermocouple
- Application: 1/2 NPT In-Line Connector
- Connector Type: In-Line
- Connector Size: 1/2 NPT
- Probe Diameter: 8 mm
- Standards Met: RoHS Compliant

**1235579** Thermocouple**RS PRO IN-LINE THERMOCOUPLE COMPRESSION FITTING FOR USE**ขนาดบรรจุภัณฑ์: **1 x EA**

- Accessory Type: Thermocouple Compression Fitting
- For Use With: Thermocouple
- Application: 1/2 NPT In-Line Connector
- Connector Type: In-Line
- Connector Size: 1/2 NPT
- Probe Diameter: 1/4 in
- Standards Met: RoHS Compliant

**1235582** Thermocouple**RS PRO STAINLESS STEEL COMPRESSION FITTING FOR USE**ขนาดบรรจุภัณฑ์: **1 x EA**

- Accessory Type: Stainless Steel Compression Fitting
- For Use With: 2 mm Diameter Thermocouple Probe
- Application: 1/8 in BSPP Connector
- Connection Gender: Male

**1314765** Stainless Steel**RS PRO STAINLESS STEEL COMPRESSION FITTING FOR USE**ขนาดบรรจุภัณฑ์: **1 x EA**

- Accessory Type: Stainless Steel Compression Fitting
- For Use With: 2 mm Diameter Thermocouple Probe
- Application: 1/8 in BSPP Connector
- Connection Gender: Male

**1314766** Stainless Steel**RS PRO IN-LINE THERMOCOUPLE COMPRESSION FITTING FOR USE**ขนาดบรรจุภัณฑ์: **1 x EA**

- Accessory Type: Thermocouple Compression Fitting
- For Use With: 3 mm Probe Thermocouple
- Application: 1/8 NPT In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Plug
- Connector Size: 1/8 NPT
- Standards Met: RoHS Compliant

**1365852** Thermocouple**RS PRO IN-LINE THERMOCOUPLE COMPRESSION FITTING FOR USE**ขนาดบรรจุภัณฑ์: **1 x EA**

- Accessory Type: Thermocouple Compression Fitting
- For Use With: 3 mm Probe Thermocouple
- Application: 1/4 NPT In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Plug
- Connector Size: 1/4 NPT
- Standards Met: RoHS Compliant

**1365854** Thermocouple**RS PRO IN-LINE THERMOCOUPLE COMPRESSION FITTING FOR USE**ขนาดบรรจุภัณฑ์: **1 x EA**

- Accessory Type: Thermocouple Compression Fitting
- For Use With: 6 mm Probe Thermocouple
- Application: 1/4 NPT In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Plug
- Connector Size: 1/4 NPT
- Standards Met: RoHS Compliant

**1365855** Thermocouple**RS PRO IN-LINE THERMOCOUPLE COMPRESSION FITTING FOR USE**ขนาดบรรจุภัณฑ์: **1 x EA**

- Accessory Type: Thermocouple Compression Fitting
- For Use With: 1.5 mm Probe Thermocouple
- Application: M8 In-Line Connector
- Connector Type: In-Line
- Connector Size: M8
- Standards Met: RoHS Compliant

**1365857** Thermocouple**RS PRO IN-LINE THERMOCOUPLE COMPRESSION FITTING FOR USE**ขนาดบรรจุภัณฑ์: **1 x EA**

- Accessory Type: Thermocouple Compression Fitting
- For Use With: 3 mm Probe Thermocouple
- Application: M8 In-Line Connector
- Connector Type: In-Line
- Connector Size: M8
- Standards Met: RoHS Compliant

**1365859** Thermocouple

RS PRO THERMOWELL FOR USE WITH TEMPERATURE PROBE, 1/2 BSP, 3 MM,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Thermowell
 - For Use With: Temperature Probe
 - Application: 1/2 BSP Connector
 - Plug/Socket: Plug
 - Connector Size: 1/2 BSP
 - Probe Diameter: 3 mm, 8 [Pocket] mm



1780953 Thermowell

RS PRO THERMOWELL FOR USE WITH TEMPERATURE PROBE, 1/2 BSP, 3 MM,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Thermowell
 - For Use With: Temperature Probe
 - Application: 1/2 BSP Connector
 - Plug/Socket: Plug
 - Connector Size: 1/2 BSP
 - Probe Diameter: 3 mm, 8 [Pocket] mm



1780954 Thermowell

RS PRO THERMOWELL FOR USE WITH TEMPERATURE PROBE, 1/2 BSP, 6MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Thermowell
 - For Use With: Temperature Probe
 - Application: 1/2 BSP Connector
 - Plug/Socket: Plug
 - Connector Size: 1/2 BSP
 - Probe Diameter: 6 mm



1780956 Thermowell

RS PRO THERMOWELL FOR USE WITH TEMPERATURE PROBE, 1/2 BSP, 6 MM,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Thermowell
 - For Use With: Temperature Probe
 - Application: 1/2 BSP Connector
 - Plug/Socket: Plug
 - Connector Size: 1/2 BSP
 - Probe Diameter: 6 mm, 11.1 [Pocket] mm



1780957 Thermowell

RS PRO THERMOWELL FOR USE WITH TEMPERATURE PROBE, 1/2 BSP, 6 MM,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Thermowell
 - For Use With: Temperature Probe
 - Application: 1/2 BSP Connector
 - Plug/Socket: Plug
 - Connector Size: 1/2 BSP
 - Probe Diameter: 6 mm, 11.1 [Pocket] mm



1780958 Thermowell

RS PRO IN-LINE THERMOCOUPLE COMPRESSION FITTING FOR USE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Thermocouple Compression Fitting
 - For Use With: Thermocouple
 - Application: 1/4 BSP In-Line Connector
 - Connector Type: In-Line
 - Plug/Socket: Plug
 - Connector Size: 1/4 BSP
 - Probe Diameter: 1.5 mm



1780960 Thermocouple

RS PRO IN-LINE THERMOCOUPLE COMPRESSION FITTING FOR USE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Thermocouple Compression Fitting
 - For Use With: Thermocouple
 - Application: 1/4 BSP In-Line Connector
 - Connector Type: In-Line
 - Plug/Socket: Plug
 - Connector Size: 1/4 BSP
 - Probe Diameter: 4 mm



1780961 Thermocouple

RS PRO IN-LINE THERMOCOUPLE COMPRESSION FITTING FOR USE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Thermocouple Compression Fitting
 - For Use With: Thermocouple
 - Application: 1/8 BSPT In-Line Connector
 - Connector Type: In-Line
 - Plug/Socket: Plug
 - Connector Size: 1/8 BSPT
 - Probe Diameter: 4 mm



1780963 Thermocouple

RS PRO IN-LINE THERMOCOUPLE COMPRESSION FITTING FOR USE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Thermocouple Compression Fitting
 - For Use With: Thermocouple
 - Application: 1/4 BSPT In-Line Connector
 - Connector Type: In-Line
 - Plug/Socket: Plug
 - Connector Size: 1/4 BSPT
 - Probe Diameter: 4 mm



1780965 Thermocouple

RS PRO IN-LINE THERMOCOUPLE COMPRESSION FITTING FOR USE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Thermocouple Compression Fitting
 - For Use With: Thermocouple
 - Application: M8 In-Line Connector
 - Connector Type: In-Line
 - Plug/Socket: Plug
 - Connector Size: M8
 - Probe Diameter: 4 mm



1780966 Thermocouple

RS PRO IN-LINE THERMOCOUPLE COMPRESSION FITTING FOR USE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Thermocouple Compression Fitting
 - For Use With: Thermocouple
 - Application: M8 In-Line Connector
 - Connector Type: In-Line
 - Plug/Socket: Plug
 - Connector Size: M8
 - Probe Diameter: 4.5 mm



1780967 Thermocouple

RS PRO IN-LINE THERMOCOUPLE COMPRESSION FITTING FOR USE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Thermocouple Compression Fitting
 - For Use With: Thermocouple
 - Application: M8 In-Line Connector
 - Connector Type: In-Line
 - Plug/Socket: Plug
 - Connector Size: M8
 - Probe Diameter: 4.7625 mm



1780969 Thermocouple

RS PRO IN-LINE THERMOCOUPLE COMPRESSION FITTING FOR USE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Thermocouple Compression Fitting
 - For Use With: Thermocouple
 - Application: 1/8 NPT In-Line Connector
 - Connector Type: In-Line
 - Plug/Socket: Plug
 - Connector Size: 1/8 NPT
 - Probe Diameter: 2 mm



1780973 Thermocouple

RS PRO BAYONET ADAPTER FOR USE WITH BAYONET CAP STYLE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Bayonet Adapter
 - For Use With: Bayonet Cap Style Thermocouples
 - Application: Single Pair Connector
 - Connector Size: Single Pair



2000617 Bayonet Adapter

RS PRO FASCIA THERMOCOUPLE CONNECTOR FOR USE WITH TYPE K

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Thermocouple Connector
 - For Use With: Type K Thermocouple
 - Application: Standard Panel Mount Connector
 - Connector Type: Fascia
 - Plug/Socket: Socket
 - Connector Size: Standard
 - Mounting Type: Nylon Clip
 - Standards Met: IEC



2194949 Thermocouple

RS PRO FASCIA THERMOCOUPLE CONNECTOR FOR USE WITH TYPE T

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Thermocouple Connector
 - For Use With: Type T Thermocouple
 - Application: Standard Panel Mount Connector
 - Connector Type: Fascia
 - Plug/Socket: Socket
 - Connector Size: Standard
 - Mounting Type: Nylon Clip
 - Standards Met: IEC



2194977 Thermocouple

RS PRO FASCIA THERMOCOUPLE CONNECTOR FOR USE WITH TYPE J

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Thermocouple Connector
 - For Use With: Type J Thermocouple
 - Application: Standard Panel Mount Connector
 - Connector Type: Fascia
 - Plug/Socket: Socket
 - Connector Size: Standard
 - Mounting Type: Nylon Clip
 - Standards Met: IEC



2195009 Thermocouple

RS PRO FASCIA THERMOCOUPLE CONNECTOR FOR USE WITH TYPE R/S

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Thermocouple Connector
 - For Use With: Type R/S Thermocouple
 - Application: Standard Panel Mount Connector
 - Connector Type: Fascia
 - Plug/Socket: Socket
 - Connector Size: Standard
 - Mounting Type: Nylon Clip
 - Standards Met: IEC



2195037 Thermocouple

RS PRO THERMOCOUPLE CONNECTOR FOR USE WITH

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Thermocouple Connector
 - For Use With: Thermocouple
 - Application: Miniature In-Line Connector
 - Connection Gender: Male-Female
 - Plug/Socket: Plug & Socket
 - Connector Size: Miniature
 - Standards Met: ANSI



2209519 Thermocouple

RS PRO THERMOCOUPLE CONNECTOR FOR USE WITH

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Thermocouple Connector
 - For Use With: Thermocouple
 - Application: Standard In-Line Connector
 - Connection Gender: Male-Female
 - Plug/Socket: Plug & Socket
 - Connector Size: Standard
 - Standards Met: ANSI



2209520 Thermocouple

RS PRO DUPLEX THERMOCOUPLE CONNECTOR FOR USE WITH TYPE J

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Thermocouple Connector
 - For Use With: Type J Thermocouple
 - Application: Standard Duplex Connector
 - Connector Type: Duplex
 - Plug/Socket: Plug
 - Connector Size: Standard
 - Standards Met: IEC



2364081 Thermocouple

RS PRO THERMOCOUPLE CLAMP FOR USE WITH MINIATURE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Thermocouple Clamp
 - For Use With: Miniature Thermocouple Connector
 - Mounting Type: Chassis Mount
 - Standards Met: RoHS Compliant



2364104 Thermocouple

RS PRO THERMOCOUPLE CLAMP FOR USE WITH STANDARD

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Thermocouple Clamp
 - For Use With: Thermocouple Connector
 - Mounting Type: Chassis Mount
 - Standards Met: RoHS Compliant



2364110 Thermocouple

RS PRO THERMOCOUPLE PANEL FOR USE WITH MINIATURE SOCKET,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Thermocouple Panel
 - For Use With: Miniature Socket
 - Application: Miniature Faceplate
 - Connector Size: Miniature
 - Mounting Type: Flange Mount
 - Standards Met: RoHS Compliant



2364132 Thermocouple

RS PRO THERMOCOUPLE PANEL FOR USE WITH STANDARD SOCKET,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Thermocouple Panel
 - For Use With: Standard Socket
 - Application: Standard Faceplate
 - Connector Size: Standard
 - Mounting Type: Flange Mount
 - Standards Met: RoHS Compliant



2364148 Thermocouple

RS PRO THERMOCOUPLE PANEL FOR USE WITH STANDARD SOCKET,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Thermocouple Panel
 - For Use With: Standard Socket
 - Application: Standard Faceplate
 - Connector Size: Standard
 - Mounting Type: Flange Mount
 - Standards Met: RoHS Compliant



2364154 Thermocouple

RS PRO THERMOCOUPLE SPADE LUG FOR USE WITH TYPE K

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Thermocouple Spade Lug
 - For Use With: Type K Thermocouple
 - Application: Connector
 - Standards Met: RoHS Compliant



2364160 Thermocouple

RS PRO BARRIER TERMINAL THERMOCOUPLE TERMINAL BLOCK

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Thermocouple Terminal Block
 - For Use With: Type J Thermocouple
 - Application: Single Pair Barrier Terminal
 - Connector Type: Barrier Terminal
 - Plug/Socket: Socket
 - Connector Size: Single Pair
 - Standards Met: IEC



2364198 Thermocouple

RS PRO BARRIER TERMINAL THERMOCOUPLE TERMINAL BLOCK

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Thermocouple Terminal Block
 - For Use With: Type K Thermocouple
 - Application: Single Pair Barrier Terminal
 - Connector Type: Barrier Terminal
 - Plug/Socket: Socket
 - Connector Size: Single Pair
 - Standards Met: IEC



2364205 Thermocouple

THERMO,PADS,SHEET X20

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Self-adhesive Thermocouple Thermopads
 - For Use With: Welded Tip Thermocouple
 - Standards Met: IEC



2905058 Self-adhesive

RS PRO THERMOCOUPLE CLAMP FOR USE WITH THERMOCOUPLE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Thermocouple Clamp
 - For Use With: Thermocouple Connectors
 - Mounting Type: Chassis Mount
 - Standards Met: RoHS Compliant



3139987 Thermocouple

RS PRO BAYONET ADAPTER FOR USE WITH TEMPERATURE SENSOR, M12,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Bayonet Adapter
 - For Use With: Temperature Sensor
 - Application: M12 Connector
 - Connector Size: M12
 - Standards Met: RoHS Compliant



3242128 Bayonet Adapter

RS PRO BAYONET ADAPTER FOR USE WITH TEMPERATURE SENSOR, 1/4

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Bayonet Adapter
 - For Use With: Temperature Sensor
 - Application: 1/4 GCY Connector
 - Connector Size: 1/4 GCY
 - Standards Met: RoHS Compliant



3242162 Bayonet Adapter

RS PRO BAYONET ADAPTER FOR USE WITH TEMPERATURE SENSOR, M10,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Bayonet Adapter
 - For Use With: Temperature Sensor
 - Application: M10 Connector
 - Connector Size: M10
 - Standards Met: RoHS Compliant



3242184 Bayonet Adapter

RS PRO BAYONET ADAPTER FOR USE WITH TEMPERATURE SENSOR, M12,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Bayonet Adapter
 - For Use With: Temperature Sensor
 - Application: M12 Connector
 - Connector Size: M12
 - Standards Met: RoHS Compliant



3242314 Bayonet Adapter

RS PRO THERMOCOUPLE COMPRESSION FITTING FOR USE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Thermocouple Compression Fitting
 - For Use With: Thermocouple
 - Application: M6 Connector
 - Connector Size: M6
 - Probe Diameter: 1 mm
 - Standards Met: RoHS Compliant



3342795 Thermocouple

RS PRO THERMOWELL FOR USE WITH TEMPERATURE SENSOR, 1/2 BSP,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Thermowell
 - For Use With: Temperature Sensor
 - Application: 1/2 BSP Connector
 - Connector Size: 1/2 BSP
 - Mounting Type: Threaded
 - Probe Diameter: 6 mm
 - Standards Met: RoHS Compliant



3389508 Thermowell

RS PRO FASCIA THERMOCOUPLE CONNECTOR FOR USE WITH

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Thermocouple Connector
 - For Use With: Temperature Sensor
 - Application: Standard Panel Mount Connector
 - Connector Type: Fascia
 - Plug/Socket: Socket
 - Connector Size: Standard
 - Mounting Type: Nylon Clip
 - Standards Met: IEC



3629783 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE J

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Thermocouple Connector
 - For Use With: Type J Thermocouple
 - Application: Standard Quickwire Connector
 - Connector Type: Quickwire
 - Plug/Socket: Socket
 - Connector Size: Standard
 - Standards Met: IEC



3629963 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE J

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Thermocouple Connector
 - For Use With: Type J Thermocouple
 - Application: Standard Quickwire Connector
 - Connector Type: Quickwire
 - Plug/Socket: Socket
 - Connector Size: Standard
 - Standards Met: IEC



3629979 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE K

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Thermocouple Connector
 - For Use With: Type K Thermocouple
 - Application: Standard Quickwire Connector
 - Connector Type: Quickwire
 - Plug/Socket: Plug
 - Connector Size: Standard
 - Standards Met: IEC



3629991 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE K

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Thermocouple Connector
 - For Use With: Type K Thermocouple
 - Application: Standard Quickwire Connector
 - Connector Type: Quickwire
 - Plug/Socket: Socket
 - Connector Size: Standard
 - Standards Met: IEC



3630008 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE T

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Thermocouple Connector
 - For Use With: Type T Thermocouple
 - Application: Standard Quickwire Connector
 - Connector Type: Quickwire
 - Plug/Socket: Socket
 - Connector Size: Standard
 - Standards Met: IEC



3630020 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE N

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Thermocouple Connector
 - For Use With: Type N Thermocouple
 - Application: Standard Quickwire Connector
 - Connector Type: Quickwire
 - Plug/Socket: Socket
 - Connector Size: Standard
 - Standards Met: IEC



3630042 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE R/S

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Thermocouple Connector
 - For Use With: Type R/S Thermocouple
 - Application: Standard Quickwire Connector
 - Connector Type: Quickwire
 - Plug/Socket: Plug
 - Connector Size: Standard
 - Standards Met: IEC



3630058 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE R/S

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Thermocouple Connector
 - For Use With: Type R/S Thermocouple
 - Application: Standard Quickwire Connector
 - Connector Type: Quickwire
 - Plug/Socket: Socket
 - Connector Size: Standard
 - Standards Met: IEC



3630064 Thermocouple

RS PRO HIGH TEMPERATURE THERMOCOUPLE CONNECTOR FOR

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Thermocouple Connector
 - For Use With: Type K Thermocouple
 - Application: Standard In-Line Connector
 - Connector Type: High Temperature Plastic
 - Plug/Socket: Plug
 - Connector Size: Standard
 - Standards Met: IEC



3630137 Thermocouple

RS PRO HIGH TEMPERATURE THERMOCOUPLE CONNECTOR FOR

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Thermocouple Connector
 - For Use With: Type K Thermocouple
 - Application: Standard In-Line Connector
 - Connector Type: High Temperature Plastic
 - Plug/Socket: Socket
 - Connector Size: Standard
 - Standards Met: IEC



3630159 Thermocouple

RS PRO STRAIGHT FEMALE/MALE THERMOCOUPLE EXTENSION CABLE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Thermocouple Extension Cable
 - For Use With: Type K Thermocouple
 - Application: Straight Female/Male Connector
 - Connector Type: Straight Female/Male
 - Plug/Socket: Plug & Socket
 - Standards Met: RoHS Compliant



3706149 Thermocouple

RS PRO THERMOCOUPLE COMPRESSION FITTING FOR USE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Thermocouple Compression Fitting
 - For Use With: Thermocouple
 - Application: 1/8 BSPP Connector
 - Connector Size: 1/8 BSPP
 - Probe Diameter: 3 mm
 - Standards Met: RoHS Compliant



3817277 Thermocouple

RS PRO THERMOCOUPLE COMPRESSION FITTING FOR USE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Thermocouple Compression Fitting
 - For Use With: Thermocouple
 - Application: 1/4 BSPT Connector
 - Connector Size: 1/4 BSPT
 - Probe Diameter: 3 mm
 - Standards Met: RoHS Compliant



3817283 Thermocouple

RS PRO THERMOCOUPLE COMPRESSION FITTING FOR USE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Thermocouple Compression Fitting
 - For Use With: Thermocouple
 - Application: 1/4 BSPP Connector
 - Connector Size: 1/4 BSPP
 - Probe Diameter: 3 mm
 - Standards Met: RoHS Compliant



3817306 Thermocouple

RS PRO THERMOCOUPLE COMPRESSION FITTING FOR USE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Thermocouple Compression Fitting
 - For Use With: Thermocouple
 - Application: 1/8 BSPP Connector
 - Connector Size: 1/8 BSPP
 - Probe Diameter: 1.5 mm
 - Standards Met: RoHS Compliant



3817334 Thermocouple

RS PRO THERMOCOUPLE COMPRESSION FITTING FOR USE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Thermocouple Compression Fitting
 - For Use With: Thermocouple
 - Application: 1/8 BSPP Connector
 - Connector Size: 1/8 BSPP
 - Probe Diameter: 3 mm
 - Standards Met: RoHS Compliant



3817340 Thermocouple

RS PRO THERMOCOUPLE COMPRESSION FITTING FOR USE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Thermocouple Compression Fitting
 - For Use With: Thermocouple
 - Application: 1/8 BSPP Connector
 - Connector Size: 1/4 BSPP
 - Probe Diameter: 6 mm
 - Standards Met: RoHS Compliant



3817356 Thermocouple

RS PRO THERMOCOUPLE COMPRESSION FITTING FOR USE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Thermocouple Compression Fitting
 - For Use With: Thermocouple
 - Application: 1/4 BSPP Connector
 - Connector Size: 1/4 BSPP
 - Probe Diameter: 3 mm
 - Standards Met: RoHS Compliant



3817362 Thermocouple

RS PRO THERMOCOUPLE COMPRESSION FITTING FOR USE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Thermocouple Compression Fitting
 - For Use With: Thermocouple
 - Application: 1/4 BSPP Connector
 - Connector Size: 1/4 BSPP
 - Probe Diameter: 6 mm
 - Standards Met: RoHS Compliant



3817378 Thermocouple

RS PRO THERMOCOUPLE COMPRESSION FITTING FOR USE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Thermocouple Compression Fitting
 - For Use With: Thermocouple
 - Application: 1/4 BSPT Connector
 - Connector Size: 1/4 BSPT
 - Probe Diameter: 3 mm
 - Standards Met: RoHS Compliant



3817384 Thermocouple

RS PRO THERMOCOUPLE COMPRESSION FITTING FOR USE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Thermocouple Compression Fitting
 - For Use With: Thermocouple
 - Application: 1/4 BSPT Connector
 - Connector Size: 1/4 BSPT
 - Probe Diameter: 6 mm
 - Standards Met: RoHS Compliant



3817390 Thermocouple

RS PRO THERMOCOUPLE COMPRESSION FITTING FOR USE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Thermocouple Compression Fitting
 - For Use With: Thermocouple
 - Application: 1/2 BSPP Connector
 - Connector Size: 1/2 BSPP
 - Probe Diameter: 6 mm
 - Standards Met: RoHS Compliant



3817407 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE J

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Thermocouple Connector
 - For Use With: Type J Thermocouple
 - Application: Miniature Quickwire Connector
 - Connector Type: Quickwire
 - Plug/Socket: Plug
 - Connector Size: Miniature
 - Standards Met: IEC



3817413 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE J

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Thermocouple Connector
 - For Use With: Type J Thermocouple
 - Application: Miniature Quickwire Connector
 - Connector Type: Quickwire
 - Plug/Socket: Socket
 - Connector Size: Miniature
 - Standards Met: IEC



3817429 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE K

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Thermocouple Connector
 - For Use With: Type K Thermocouple
 - Application: Miniature Quickwire Connector
 - Connector Type: Quickwire
 - Plug/Socket: Plug
 - Connector Size: Miniature
 - Standards Met: IEC



3817435 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE K

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Thermocouple Connector
 - For Use With: Type K Thermocouple
 - Application: Miniature Quickwire Connector
 - Connector Type: Quickwire
 - Plug/Socket: Socket
 - Connector Size: Miniature
 - Standards Met: IEC



3817441 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE T

ขนาดบรรจุภัณฑ์: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type T Thermocouple
- Application: Standard Quickwire Connector
- Connector Type: Quickwire
- Plug/Socket: Plug
- Connector Size: Miniature
- Standards Met: IEC



3817457 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE T

ขนาดบรรจุภัณฑ์: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type T Thermocouple
- Application: Standard Quickwire Connector
- Connector Type: Quickwire
- Plug/Socket: Socket
- Connector Size: Miniature
- Standards Met: IEC



3817463 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE N

ขนาดบรรจุภัณฑ์: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type N Thermocouple
- Application: Standard Quickwire Connector
- Connector Type: Quickwire
- Plug/Socket: Plug
- Connector Size: Miniature
- Standards Met: IEC



3817485 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE N

ขนาดบรรจุภัณฑ์: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type N Thermocouple
- Application: Standard Quickwire Connector
- Connector Type: Quickwire
- Plug/Socket: Socket
- Connector Size: Miniature
- Standards Met: IEC



3817491 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE R/S

ขนาดบรรจุภัณฑ์: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type R/S Thermocouple
- Application: Miniature Quickwire Connector
- Connector Type: Quickwire
- Plug/Socket: Plug
- Connector Size: Miniature
- Standards Met: IEC



3817508 Thermocouple

RS PRO PCB MOUNTING THERMOCOUPLE CONNECTOR FOR

ขนาดบรรจุภัณฑ์: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type K Thermocouple
- Application: Miniature PCB Mounting Connector
- Connector Type: PCB Mounting
- Plug/Socket: Socket
- Connector Size: Miniature
- Mounting Type: PCB Mount
- Standards Met: IEC



3817564 Thermocouple

RS PRO PCB MOUNTING THERMOCOUPLE CONNECTOR FOR

ขนาดบรรจุภัณฑ์: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type T Thermocouple
- Application: Miniature PCB Mounting Connector
- Connector Type: PCB Mounting
- Plug/Socket: Socket
- Connector Size: Miniature
- Mounting Type: PCB Mount
- Standards Met: IEC



3817570 Thermocouple

RS PRO THERMOCOUPLE PANEL FOR USE WITH MINIATURE SOCKET,

ขนาดบรรจุภัณฑ์: **1 x EA**

- Accessory Type: Thermocouple Panel
- For Use With: Miniature Socket
- Application: Miniature Faceplate
- Connector Size: Miniature
- Mounting Type: Flange Mount
- Standards Met: RoHS Compliant



3971674 Thermocouple

RS PRO THERMOCOUPLE PANEL FOR USE WITH MINIATURE SOCKET,

ขนาดบรรจุภัณฑ์: **1 x EA**

- Accessory Type: Thermocouple Panel
- For Use With: Miniature Socket
- Application: Miniature Faceplate
- Connector Size: Miniature
- Mounting Type: Flange Mount
- Standards Met: RoHS Compliant



3971703 Thermocouple

RS PRO THERMOCOUPLE PANEL FOR USE WITH MINIATURE SOCKET,

ขนาดบรรจุภัณฑ์: **1 x EA**

- Accessory Type: Thermocouple Panel
- For Use With: Miniature Socket
- Application: Standard Faceplate
- Connector Size: Miniature
- Mounting Type: Flange Mount
- Standards Met: RoHS Compliant




3971719 Thermocouple

RS PRO THERMOCOUPLE PANEL FOR USE WITH STANDARD SOCKET,

ขนาดบรรจุภัณฑ์: **1 x EA**

- Accessory Type: Thermocouple Panel
- For Use With: Standard Socket
- Application: Standard Faceplate
- Connector Size: Standard
- Mounting Type: Flange Mount
- Standards Met: RoHS Compliant



3971731 Thermocouple

RS PRO THERMOCOUPLE PANEL FOR USE WITH STANDARD SOCKET,

ขนาดบรรจุภัณฑ์: **1 x EA**

- Accessory Type: Thermocouple Panel
- For Use With: Standard Socket
- Application: Standard Faceplate
- Connector Size: Standard
- Mounting Type: Flange Mount
- Standards Met: RoHS Compliant



3971769 Thermocouple

RS PRO MINIATURE BLANKING PLUG FOR USE WITH CONNECTOR

ขนาดบรรจุภัณฑ์: **1 x EA**

- Accessory Type: Miniature Blanking Plug
- For Use With: Connector Faceplates
- Mounting Type: Nylon Clip
- Standards Met: RoHS Compliant



3971797 Miniature

RS PRO THERMOWELL FOR USE WITH TEMPERATURE SENSOR, 1/2 BSP,

ขนาดบรรจุภัณฑ์: **1 x EA**

- Accessory Type: Thermowell
- For Use With: Temperature Sensor
- Application: 1/2 BSP Connector
- Connector Size: 1/2 BSP
- Mounting Type: Threaded
- Probe Diameter: 6 mm
- Standards Met: RoHS Compliant



4360665 Thermowell

RS PRO THERMOCOUPLE CONNECTION HEAD FOR USE WITH

ขนาดบรรจุภัณฑ์: **1 x EA**

- Accessory Type: Thermocouple Connection Head
- For Use With: Temperature Sensor
- Application: 1/2 BSPP Connector
- Connector Size: 1/2 BSPP
- Standards Met: RoHS Compliant



4553801 Thermocouple

RS PRO THERMOCOUPLE CONNECTION HEAD FOR USE WITH

ขนาดบรรจุภัณฑ์: **1 x EA**

- Accessory Type: Thermocouple Connection Head
- For Use With: Temperature Sensor
- Application: 1/2 BSPP Connector
- Connector Size: 1/2 BSPP
- Standards Met: RoHS Compliant



4553817 Thermocouple

RS PRO THERMOCOUPLE CONNECTION HEAD FOR USE WITH

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Thermocouple Connection Head
- For Use With: Temperature Sensor
- Application: 1/8 BSPP Connector
- Connector Size: 1/8 BSPP
- Standards Met: RoHS Compliant



4553823 Thermocouple

RS PRO SCREW THERMOCOUPLE TERMINAL BLOCK FOR USE WITH KNS

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Thermocouple Terminal Block
- For Use With: KNS Head
- Connector Type: Screw
- Standards Met: RoHS Compliant



4553839 Thermocouple

RS PRO SCREW THERMOCOUPLE TERMINAL BLOCK FOR USE WITH TYPE

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Thermocouple Terminal Block
- For Use With: Type K Thermocouple
- Connector Type: Screw
- Standards Met: RoHS Compliant



4553867 Thermocouple

RS PRO SCREW THERMOCOUPLE TERMINAL BLOCK FOR USE WITH TYPE

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Thermocouple Terminal Block
- For Use With: Type K Thermocouple
- Connector Type: Screw
- Standards Met: RoHS Compliant



4553902 Thermocouple

RS PRO SCREW THERMOCOUPLE TERMINAL BLOCK FOR USE WITH

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Thermocouple Terminal Block
- For Use With: Terminal Block Head
- Connector Type: Screw
- Standards Met: RoHS Compliant



4553924 Thermocouple

RS PRO SCREW THERMOCOUPLE TERMINAL BLOCK FOR USE WITH

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Thermocouple Terminal Block
- For Use With: Terminal Block Head
- Connector Type: Screw
- Standards Met: RoHS Compliant



4553918 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE J

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Thermocouple Connector
- For Use With: Type J Thermocouple
- Application: Miniature In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Socket
- Connector Size: Miniature
- Standards Met: BS



4559506 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE K

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Thermocouple Connector
- For Use With: Type K Thermocouple
- Application: Miniature In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Socket
- Connector Size: Miniature
- Standards Met: BS



4559512 Thermocouple

RS PRO PANEL MOUNT THERMOCOUPLE CONNECTOR FOR

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Thermocouple Connector
- For Use With: Type K Thermocouple
- Application: Miniature Panel Mount Connector
- Connector Type: Panel Mount
- Plug/Socket: Socket
- Connector Size: Miniature
- Mounting Type: Nylon Clip
- Standards Met: BS



4559528 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE K

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Thermocouple Connector
- For Use With: Type K Thermocouple
- Application: Miniature In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Plug
- Connector Size: Miniature
- Standards Met: BS



4559534 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE K

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Thermocouple Connector
- For Use With: Type K Thermocouple
- Application: Miniature In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Plug & Socket
- Connector Size: Miniature
- Standards Met: BS



4559540 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE T

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Thermocouple Connector
- For Use With: Type T Thermocouple
- Application: Miniature In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Socket
- Connector Size: Miniature
- Standards Met: BS



4559562 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE T

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Thermocouple Connector
- For Use With: Type T Thermocouple
- Application: Miniature In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Plug
- Connector Size: Miniature
- Standards Met: BS



4559578 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE T

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Thermocouple Connector
- For Use With: Type T Thermocouple
- Application: Miniature In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Plug & Socket
- Connector Size: Miniature
- Standards Met: IEC



4559584 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE J

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Thermocouple Connector
- For Use With: Type J Thermocouple
- Application: Standard In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Plug
- Connector Size: Standard
- Standards Met: BS



4559590 Thermocouple

RS PRO PANEL MOUNT THERMOCOUPLE CONNECTOR FOR

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Thermocouple Connector
- For Use With: Type K Thermocouple
- Application: Standard Panel Mount Connector
- Connector Type: Panel Mount
- Plug/Socket: Socket
- Connector Size: Standard
- Mounting Type: Nylon Clip
- Standards Met: BS



4559607 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE K

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Thermocouple Connector
 - For Use With: Type K Thermocouple
 - Application: Standard In-Line Connector
 - Connector Type: In-Line
 - Plug/Socket: Plug
 - Connector Size: Standard
 - Standards Met: BS



4559629 Thermocouple

RS PRO FASCIA THERMOCOUPLE CONNECTOR FOR USE WITH COPPER

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Thermocouple Connector
 - For Use With: Copper Thermocouple
 - Application: Miniature Panel Mount Connector
 - Connector Type: Fascia
 - Plug/Socket: Socket
 - Connector Size: Miniature
 - Mounting Type: Nylon Clip
 - Standards Met: IEC



4559657 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE CU

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Thermocouple Connector
 - For Use With: Type CU Thermocouple
 - Application: Miniature In-Line Connector
 - Connector Type: In-Line
 - Plug/Socket: Socket
 - Connector Size: Miniature
 - Standards Met: IEC



4559663 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE CU

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Thermocouple Connector
 - For Use With: Type CU Thermocouple
 - Application: Miniature In-Line Connector
 - Connector Type: In-Line
 - Plug/Socket: Plug
 - Connector Size: Miniature
 - Standards Met: IEC



4559679 Thermocouple

RS PRO FASCIA THERMOCOUPLE CONNECTOR FOR USE WITH TYPE J

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Thermocouple Connector
 - For Use With: Type J Thermocouple
 - Application: Miniature Panel Mount Connector
 - Connector Type: Fascia
 - Plug/Socket: Socket
 - Connector Size: Miniature
 - Mounting Type: Nylon Clip
 - Standards Met: IEC



4559691 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE J

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Thermocouple Connector
 - For Use With: Type J Thermocouple
 - Application: Miniature In-Line Connector
 - Connector Type: In-Line
 - Plug/Socket: Socket
 - Connector Size: Miniature
 - Standards Met: IEC



4559708 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE J

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Thermocouple Connector
 - For Use With: Type J Thermocouple
 - Application: Miniature In-Line Connector
 - Connector Type: In-Line
 - Plug/Socket: Plug
 - Connector Size: Miniature
 - Standards Met: IEC



4559714 Thermocouple

RS PRO PANEL MOUNT THERMOCOUPLE CONNECTOR FOR

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Thermocouple Connector
 - For Use With: Type J Thermocouple
 - Application: Miniature Panel Mount Connector
 - Connector Type: Panel Mount
 - Plug/Socket: Socket
 - Connector Size: Miniature
 - Mounting Type: Stainless Steel Bracket
 - Standards Met: IEC



4559720 Thermocouple

RS PRO FASCIA THERMOCOUPLE CONNECTOR FOR USE WITH TYPE K

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Thermocouple Connector
 - For Use With: Type K Thermocouple
 - Application: Miniature Panel Mount Connector
 - Connector Type: Fascia
 - Plug/Socket: Socket
 - Connector Size: Miniature
 - Mounting Type: Nylon Clip
 - Standards Met: IEC



4559742 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE K

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Thermocouple Connector
 - For Use With: Type K Thermocouple
 - Application: Miniature In-Line Connector
 - Connector Type: In-Line
 - Plug/Socket: Socket
 - Connector Size: Miniature
 - Standards Met: IEC



4559758 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE K

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Thermocouple Connector
 - For Use With: Type K Thermocouple
 - Application: Miniature In-Line Connector
 - Connector Type: In-Line
 - Plug/Socket: Plug
 - Connector Size: Miniature
 - Standards Met: IEC



4559764 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE K

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Thermocouple Connector
 - For Use With: Type K Thermocouple
 - Application: Miniature In-Line Connector
 - Connector Type: In-Line
 - Plug/Socket: Plug & Socket
 - Connector Size: Miniature
 - Standards Met: IEC



4559786 Thermocouple

RS PRO PANEL MOUNT THERMOCOUPLE CONNECTOR FOR

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Thermocouple Connector
 - For Use With: Type K Thermocouple
 - Application: Miniature Panel Mount Connector
 - Connector Type: Panel Mount
 - Plug/Socket: Socket
 - Connector Size: Miniature
 - Mounting Type: Stainless Steel Bracket
 - Standards Met: IEC



4559792 Thermocouple

RS PRO FASCIA THERMOCOUPLE CONNECTOR FOR USE WITH TYPE N

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Thermocouple Connector
 - For Use With: Type N Thermocouple
 - Application: Miniature Panel Mount Connector
 - Connector Type: Fascia
 - Plug/Socket: Socket
 - Connector Size: Miniature
 - Mounting Type: Nylon Clip
 - Standards Met: IEC



4559815 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE N

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Thermocouple Connector
 - For Use With: Type N Thermocouple
 - Application: Miniature In-Line Connector
 - Connector Type: In-Line
 - Plug/Socket: Socket
 - Connector Size: Miniature
 - Standards Met: IEC



4559821 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE N

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Thermocouple Connector
 - For Use With: Type N Thermocouple
 - Application: Miniature In-Line Connector
 - Connector Type: In-Line
 - Plug/Socket: Plug
 - Connector Size: Miniature
 - Standards Met: IEC



4559843 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE T

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Thermocouple Connector
 - For Use With: Type T Thermocouple
 - Application: Standard In-Line Connector
 - Connector Type: In-Line
 - Plug/Socket: Socket
 - Connector Size: Standard
 - Standards Met: IEC



4560045 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE T

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Thermocouple Connector
 - For Use With: Type T Thermocouple
 - Application: Standard In-Line Connector
 - Connector Type: In-Line
 - Plug/Socket: Plug
 - Connector Size: Standard
 - Standards Met: IEC



4560051 Thermocouple

RS PRO PANEL MOUNT THERMOCOUPLE CONNECTOR FOR

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Thermocouple Connector
 - For Use With: Type J Thermocouple
 - Application: Standard Panel Mount Connector
 - Connector Type: Panel Mount
 - Plug/Socket: Socket
 - Connector Size: Standard
 - Mounting Type: Stainless Steel Bracket
 - Standards Met: IEC



4560089 Thermocouple

RS PRO PANEL MOUNT THERMOCOUPLE CONNECTOR FOR

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Thermocouple Connector
 - For Use With: Type K Thermocouple
 - Application: Standard Panel Mount Connector
 - Connector Type: Panel Mount
 - Plug/Socket: Socket
 - Connector Size: Standard
 - Mounting Type: Stainless Steel Bracket
 - Standards Met: IEC



4560102 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE K

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Thermocouple Connector
 - For Use With: Type K Thermocouple
 - Application: Standard In-Line Connector
 - Connector Type: In-Line
 - Plug/Socket: Socket
 - Connector Size: Standard
 - Standards Met: BS



4560540 Thermocouple

RS PRO THERMOWELL FOR USE WITH PT 100 + 10K3A1 THERMOCOUPLE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Thermowell
 - For Use With: PT 100 Thermocouple
 - Standards Met: RoHS Compliant



4941040 Thermowell

RS PRO BAYONET ADAPTER FOR USE WITH TYPE J THERMOCOUPLE, ROHS

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Bayonet Adapter
 - For Use With: Type J Thermocouple
 - Standards Met: RoHS Compliant



5477815 Bayonet Adapter

RS PRO THERMOCOUPLE COMPRESSION FITTING FOR USE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Thermocouple Compression Fitting
 - For Use With: Thermocouple
 - Application: 1/8 BSP Connector
 - Connector Size: 1/8 BSP
 - Probe Diameter: 3 mm
 - Standards Met: RoHS Compliant



5477837 Thermocouple

RS PRO HIGH TEMPERATURE THERMOCOUPLE CONNECTOR FOR

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Thermocouple Connector
 - For Use With: Type K Thermocouple
 - Application: Miniature In-Line Connector
 - Connector Type: High Temperature Plastic
 - Plug/Socket: Plug
 - Connector Size: Miniature
 - Standards Met: IEC



6118113 Thermocouple

RS PRO HIGH TEMPERATURE THERMOCOUPLE CONNECTOR FOR

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Thermocouple Connector
 - For Use With: Type K Thermocouple
 - Application: Miniature In-Line Connector
 - Connector Type: High Temperature Plastic
 - Plug/Socket: Socket
 - Connector Size: Miniature
 - Standards Met: IEC



6118135 Thermocouple

RS PRO HIGH TEMPERATURE THERMOCOUPLE CONNECTOR FOR

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Thermocouple Connector
 - For Use With: Type J Thermocouple
 - Application: Miniature In-Line Connector
 - Connector Type: High Temperature Plastic
 - Plug/Socket: Plug
 - Connector Size: Miniature
 - Standards Met: IEC



6118141 Thermocouple

RS PRO PCB MOUNTING THERMOCOUPLE CONNECTOR FOR

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Thermocouple Connector
 - For Use With: Temperature Sensor
 - Application: Miniature PCB Mounting Connector
 - Connector Type: PCB Mounting
 - Plug/Socket: Socket
 - Connector Size: Miniature
 - Mounting Type: PCB Mount
 - Standards Met: IEC



6118157 Thermocouple

RS PRO HIGH TEMPERATURE THERMOCOUPLE CONNECTOR FOR

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Thermocouple Connector
 - For Use With: Type J Thermocouple
 - Application: Miniature In-Line Connector
 - Connector Type: High Temperature Plastic
 - Plug/Socket: Socket
 - Connector Size: Miniature
 - Standards Met: IEC



6118163 Thermocouple

RS PRO HIGH TEMPERATURE THERMOCOUPLE CONNECTOR FOR

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Thermocouple Connector
 - For Use With: Type J Thermocouple
 - Application: Standard In-Line Connector
 - Connector Type: High Temperature Plastic
 - Plug/Socket: Plug
 - Connector Size: Standard
 - Standards Met: IEC



6118179 Thermocouple

RS PRO HIGH TEMPERATURE THERMOCOUPLE CONNECTOR FOR

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Thermocouple Connector
 - For Use With: Type J Thermocouple
 - Application: Standard In-Line Connector
 - Connector Type: High Temperature Plastic
 - Plug/Socket: Socket
 - Connector Size: Standard
 - Standards Met: IEC



6118185 Thermocouple

RS PRO THERMOCOUPLE PANEL FOR USE WITH MINIATURE SOCKET,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Thermocouple Panel
 - For Use With: Miniature Socket
 - Application: Miniature Faceplate
 - Connector Size: Miniature
 - Mounting Type: Flange Mount
 - Standards Met: RoHS Compliant



6118191 Thermocouple

RS PRO THERMOCOUPLE PANEL FOR USE WITH MINIATURE SOCKET,

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Thermocouple Panel
- For Use With: Miniature Socket
- Application: Miniature Faceplate
- Connector Size: Miniature
- Mounting Type: Flange Mount
- Standards Met: RoHS Compliant



6118214 Thermocouple

RS PRO THERMOCOUPLE PANEL FOR USE WITH MINIATURE SOCKET,

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Thermocouple Panel
- For Use With: Miniature Socket
- Application: Miniature Faceplate
- Connector Size: Miniature
- Mounting Type: Flange Mount
- Standards Met: RoHS Compliant



6118220 Thermocouple

RS PRO THERMOCOUPLE PANEL FOR USE WITH STANDARD SOCKET,

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Thermocouple Panel
- For Use With: Standard Socket
- Application: Standard Faceplate
- Connector Size: Standard
- Mounting Type: Flange Mount
- Standards Met: RoHS Compliant



6118258 Thermocouple

RS PRO THERMOCOUPLE PANEL FOR USE WITH STANDARD SOCKET,

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Thermocouple Panel
- For Use With: Standard Socket
- Application: Standard Faceplate
- Connector Size: Standard
- Mounting Type: Flange Mount
- Standards Met: RoHS Compliant



6118270 Thermocouple

RS PRO BAYONET ADAPTER FOR USE WITH J & K TYPE ADJUSTABLE

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Bayonet Adapter
- For Use With: J & K Type Adjustable Bayonet
- Application: 1/8 BSP Connector
- Connector Size: 1/8 BSP
- Standards Met: RoHS Compliant



6212243 Bayonet Adapter

RS PRO THERMOCOUPLE PANEL FOR USE WITH MINIATURE SOCKET,

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Thermocouple Panel
- For Use With: Miniature Socket
- Application: Miniature Faceplate
- Connector Size: Miniature
- Mounting Type: Flange Mount
- Standards Met: RoHS Compliant



7621156 Thermocouple

RS PRO BRASS LOCKNUT FOR USE WITH TEMPERATURE SENSOR, M8,

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Brass Locknut
- For Use With: Temperature Sensor
- Application: M8 Locknut
- Connector Size: M8
- Mounting Type: M8
- Standards Met: RoHS Compliant



7621162 Brass Locknut

RS PRO THERMOCOUPLE PANEL FOR USE WITH MINIATURE SOCKET,

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Thermocouple Panel
- For Use With: Miniature Socket
- Application: Miniature Faceplate
- Connector Size: Miniature
- Mounting Type: Flange Mount
- Standards Met: RoHS Compliant



7621165 Thermocouple

RS PRO THERMOCOUPLE PANEL FOR USE WITH MINIATURE SOCKET,

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Thermocouple Panel
- For Use With: Miniature Socket
- Application: Miniature Faceplate
- Connector Size: Miniature
- Mounting Type: Flange Mount
- Standards Met: RoHS Compliant



7621168 Thermocouple

RS PRO BRASS LOCKNUT FOR USE WITH TEMPERATURE SENSOR, 1/8

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Brass Locknut
- For Use With: Temperature Sensor
- Application: 1/8 BSPP Locknut
- Connector Size: 1/8 BSPP
- Mounting Type: 1/8 BSPP
- Standards Met: RoHS Compliant



7621171 Brass Locknut

RS PRO BRASS LOCKNUT FOR USE WITH TEMPERATURE SENSOR, 1/4

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Brass Locknut
- For Use With: Temperature Sensor
- Application: 1/4 BSPP Locknut
- Connector Size: 1/4 BSPP
- Mounting Type: 1/4 BSPP
- Standards Met: RoHS Compliant



7621174 Brass Locknut

RS PRO BRASS LOCKNUT FOR USE WITH TEMPERATURE SENSOR, 1/2

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Brass Locknut
- For Use With: Temperature Sensor
- Application: 1/2 BSPP Locknut
- Connector Size: 1/2 BSPP
- Mounting Type: 1/2 BSPP
- Standards Met: RoHS Compliant



7621178 Brass Locknut

RS PRO STAINLESS STEEL LOCKNUT FOR USE WITH TEMPERATURE

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Stainless Steel Locknut
- For Use With: Temperature Sensor
- Application: 1/8 BSPP Locknut
- Connector Size: 1/8 BSPP
- Mounting Type: 1/8 BSPP
- Standards Met: RoHS Compliant



7621180 Stainless Steel

RS PRO STAINLESS STEEL LOCKNUT FOR USE WITH TEMPERATURE

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Stainless Steel Locknut
- For Use With: Temperature Sensor
- Application: 1/4 BSPP Locknut
- Connector Size: 1/4 BSPP
- Mounting Type: 1/4 BSPP
- Standards Met: RoHS Compliant



7621184 Stainless Steel

RS PRO STAINLESS STEEL LOCKNUT FOR USE WITH TEMPERATURE

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Stainless Steel Locknut
- For Use With: Temperature Sensor
- Application: M8 Locknut
- Connector Size: M8
- Mounting Type: M8x1
- Standards Met: RoHS Compliant



7621187 Stainless Steel

RS PRO STAINLESS STEEL LOCKNUT FOR USE WITH TEMPERATURE

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Stainless Steel Locknut
- For Use With: Temperature Sensor
- Application: 1/2 BSPP Locknut
- Connector Size: 1/2 BSPP
- Mounting Type: 1/2 BSPP
- Standards Met: RoHS Compliant



7621193 Stainless Steel

RS PRO FASCIA THERMOCOUPLE CONNECTOR FOR USE WITH TYPE R/S

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Thermocouple Connector
- For Use With: Type R/S Thermocouple
- Application: Standard Panel Mount Connector
- Connector Type: Fascia
- Plug/Socket: Socket
- Connector Size: Standard
- Mounting Type: Nylon Clip
- Standards Met: ANSI



7691394 Thermocouple

RS PRO FASCIA THERMOCOUPLE CONNECTOR FOR USE WITH TYPE T

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Thermocouple Connector
- For Use With: Type T Thermocouple
- Application: Standard Panel Mount Connector
- Connector Type: Fascia
- Plug/Socket: Socket
- Connector Size: Standard
- Mounting Type: Nylon Clip
- Standards Met: ANSI



7691397 Thermocouple

RS PRO PANEL MOUNT THERMOCOUPLE CONNECTOR FOR

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Thermocouple Connector
- For Use With: Type J Thermocouple
- Application: Standard Quickwire Panel Mount Connector
- Connector Type: Panel Mount
- Plug/Socket: Socket
- Connector Size: Standard
- Mounting Type: Stainless Steel Bracket
- Standards Met: ANSI



7691404 Thermocouple

RS PRO PANEL MOUNT THERMOCOUPLE CONNECTOR FOR

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Thermocouple Connector
- For Use With: Type K Thermocouple
- Application: Standard Quickwire Panel Mount Connector
- Connector Type: Panel Mount
- Plug/Socket: Socket
- Connector Size: Standard
- Mounting Type: Stainless Steel Bracket
- Standards Met: ANSI



7691408 Thermocouple

RS PRO QUICKWIRE PANEL MOUNT THERMOCOUPLE CONNECTOR FOR

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Thermocouple Connector
- For Use With: Type J Thermocouple
- Application: Standard Quickwire Panel Mount Connector
- Connector Type: Quickwire Panel Mount
- Plug/Socket: Socket
- Connector Size: Standard
- Mounting Type: Stainless Steel Bracket
- Standards Met: ANSI



7691420 Thermocouple

RS PRO DUPLEX THERMOCOUPLE CONNECTOR FOR USE WITH TYPE K

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Thermocouple Connector
- For Use With: Type K Thermocouple
- Application: Standard Duplex Connector
- Connector Type: Duplex
- Plug/Socket: Plug
- Connector Size: Standard
- Standards Met: ANSI



7691454 Thermocouple

RS PRO DUPLEX THERMOCOUPLE CONNECTOR FOR USE WITH TYPE K

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Thermocouple Connector
- For Use With: Type K Thermocouple
- Application: Standard Duplex Connector
- Connector Type: Duplex
- Plug/Socket: Plug
- Connector Size: Standard
- Standards Met: ANSI



7691470 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE J

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Thermocouple Connector
- For Use With: Type J Thermocouple
- Application: Miniature In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Plug
- Connector Size: Miniature
- Standards Met: JIS



7718761 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE E

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Thermocouple Connector
- For Use With: Type E Thermocouple
- Application: Miniature In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Plug
- Connector Size: Miniature
- Standards Met: JIS



7718767 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE K

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Thermocouple Connector
- For Use With: Type K Thermocouple
- Application: Miniature In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Plug
- Connector Size: Miniature
- Standards Met: JIS



7718770 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE R/S

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Thermocouple Connector
- For Use With: Type R/S Thermocouple
- Application: Miniature In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Plug
- Connector Size: Miniature
- Standards Met: JIS



7718773 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE T

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Thermocouple Connector
- For Use With: Type T Thermocouple
- Application: Miniature In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Plug
- Connector Size: Miniature
- Standards Met: JIS



7718777 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE J

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Thermocouple Connector
- For Use With: Type J Thermocouple
- Application: Miniature In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Socket
- Connector Size: Miniature
- Standards Met: JIS



7718783 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE E

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Thermocouple Connector
- For Use With: Type E Thermocouple
- Application: Miniature In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Socket
- Connector Size: Miniature
- Standards Met: JIS



7718789 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE K

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Thermocouple Connector
- For Use With: Type K Thermocouple
- Application: Miniature In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Socket
- Connector Size: Miniature
- Standards Met: JIS



7718792 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE R/S

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Thermocouple Connector
- For Use With: Type R/S Thermocouple
- Application: Miniature In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Socket
- Connector Size: Miniature
- Standards Met: JIS



7718795 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE T

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Thermocouple Connector
- For Use With: Type T Thermocouple
- Application: Miniature In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Socket
- Connector Size: Miniature
- Standards Met: JIS



7718799 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE J

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Thermocouple Connector
- For Use With: Type J Thermocouple
- Application: Miniature Quickwire Connector
- Connector Type: Quickwire
- Plug/Socket: Plug
- Connector Size: Miniature
- Standards Met: JIS



7718806 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE B

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Thermocouple Connector
- For Use With: Type B Thermocouple
- Application: Miniature Quickwire Connector
- Connector Type: Quickwire
- Plug/Socket: Plug
- Connector Size: Miniature
- Standards Met: JIS



7718809 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE T

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Thermocouple Connector
- For Use With: Type T Thermocouple
- Application: Miniature Quickwire Connector
- Connector Type: Quickwire
- Plug/Socket: Plug
- Connector Size: Miniature
- Standards Met: JIS



7718812 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE K

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Thermocouple Connector
- For Use With: Type K Thermocouple
- Application: Miniature Quickwire Connector
- Connector Type: Quickwire
- Plug/Socket: Plug
- Connector Size: Miniature
- Standards Met: JIS



7718815 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE R/S

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Thermocouple Connector
- For Use With: Type R/S Thermocouple
- Application: Miniature Quickwire Connector
- Connector Type: Quickwire
- Plug/Socket: Plug
- Connector Size: Miniature
- Standards Met: JIS



7718818 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE J

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Thermocouple Connector
- For Use With: Type J Thermocouple
- Application: Miniature Quickwire Connector
- Connector Type: Quickwire
- Plug/Socket: Plug
- Connector Size: Miniature
- Standards Met: JIS



7718828 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE T

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Thermocouple Connector
- For Use With: Type T Thermocouple
- Application: Miniature Quickwire Connector
- Connector Type: Quickwire
- Plug/Socket: Socket
- Connector Size: Miniature
- Standards Met: JIS



7718834 Thermocouple

RS PRO FASCIA THERMOCOUPLE CONNECTOR FOR USE WITH TYPE T

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Thermocouple Connector
- For Use With: Type T Thermocouple
- Application: Miniature Panel Mount Connector
- Connector Type: Fascia
- Plug/Socket: Socket
- Connector Size: Miniature
- Mounting Type: Nylon Clip
- Standards Met: JIS



7718856 Thermocouple

RS PRO FASCIA THERMOCOUPLE CONNECTOR FOR USE WITH TYPE K

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Thermocouple Connector
- For Use With: Type K Thermocouple
- Application: Miniature Panel Mount Connector
- Connector Type: Fascia
- Plug/Socket: Socket
- Connector Size: Miniature
- Mounting Type: Nylon Clip
- Standards Met: JIS



7718859 Thermocouple

RS PRO PANEL MOUNT THERMOCOUPLE CONNECTOR FOR

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Thermocouple Connector
- For Use With: Type K Thermocouple
- Application: Miniature Panel Mount Connector
- Connector Type: Panel Mount
- Plug/Socket: Socket
- Connector Size: Miniature
- Mounting Type: Stainless Steel Bracket
- Standards Met: JIS



7718871 Thermocouple

RS PRO PANEL MOUNT THERMOCOUPLE CONNECTOR FOR

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Thermocouple Connector
- For Use With: Type T Thermocouple
- Application: Miniature Panel Mount Connector
- Connector Type: Panel Mount
- Plug/Socket: Socket
- Connector Size: Miniature
- Mounting Type: Stainless Steel Bracket
- Standards Met: JIS



7718878 Thermocouple

RS PRO PCB MOUNTING THERMOCOUPLE CONNECTOR FOR

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Thermocouple Connector
- For Use With: Type K Thermocouple
- Application: Miniature PCB Mounting Connector
- Connector Type: PCB Mounting
- Plug/Socket: Socket
- Connector Size: Miniature
- Mounting Type: PCB Mount
- Standards Met: JIS



7718916 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE E

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Thermocouple Connector
- For Use With: Type E Thermocouple
- Application: Standard In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Plug
- Connector Size: Standard
- Standards Met: JIS



7718925 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE J

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Thermocouple Connector
- For Use With: Type J Thermocouple
- Application: Standard In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Plug
- Connector Size: Standard
- Standards Met: JIS



7718929 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE R/S

ขนาดบรรจุภัณฑ์: 1 x EA

- Accessory Type: Thermocouple Connector
- For Use With: Type R/S Thermocouple
- Application: Standard In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Plug
- Connector Size: Standard
- Standards Met: JIS



7718931 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE B

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Thermocouple Connector
 - For Use With: Type B Thermocouple
 - Application: Miniature In-Line Connector
 - Connector Type: In-Line
 - Plug/Socket: Plug
 - Connector Size: Miniature
 - Standards Met: IEC



7747181 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE E

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Thermocouple Connector
 - For Use With: Type E Thermocouple
 - Application: Miniature In-Line Connector
 - Connector Type: In-Line
 - Plug/Socket: Plug
 - Connector Size: Miniature
 - Standards Met: IEC



7747185 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE B

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Thermocouple Connector
 - For Use With: Type B Thermocouple
 - Application: Miniature Quickwire Connector
 - Connector Type: Quickwire
 - Plug/Socket: Plug
 - Connector Size: Miniature
 - Standards Met: IEC



7747191 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE B

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Thermocouple Connector
 - For Use With: Type B Thermocouple
 - Application: Miniature In-Line Connector
 - Connector Type: In-Line
 - Plug/Socket: Socket
 - Connector Size: Miniature
 - Standards Met: IEC



7747194 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE E

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Thermocouple Connector
 - For Use With: Type E Thermocouple
 - Application: Miniature Quickwire Connector
 - Connector Type: Quickwire
 - Plug/Socket: Plug
 - Connector Size: Miniature
 - Standards Met: IEC



7747201 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE E

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Thermocouple Connector
 - For Use With: Type E Thermocouple
 - Application: Miniature Quickwire Connector
 - Connector Type: Quickwire
 - Plug/Socket: Socket
 - Connector Size: Miniature
 - Standards Met: IEC



7747208 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE K

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Thermocouple Connector
 - For Use With: Type K Thermocouple
 - Application: Miniature Quickwire Panel Mount Connector
 - Connector Type: Quickwire
 - Plug/Socket: Socket
 - Connector Size: Miniature
 - Mounting Type: Stainless Steel Bracket
 - Standards Met: IEC



7747236 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE T

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Thermocouple Connector
 - For Use With: Type T Thermocouple
 - Application: Miniature Quickwire Panel Mount Connector
 - Connector Type: Quickwire
 - Plug/Socket: Socket
 - Connector Size: Miniature
 - Mounting Type: Stainless Steel Bracket
 - Standards Met: IEC



7747242 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE E

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Thermocouple Connector
 - For Use With: Type E Thermocouple
 - Application: Standard In-Line Connector
 - Connector Type: In-Line
 - Plug/Socket: Socket
 - Connector Size: Standard
 - Standards Met: IEC



7747264 Thermocouple

RS PRO PANEL MOUNT THERMOCOUPLE CONNECTOR FOR

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Thermocouple Connector
 - For Use With: Type R/S Thermocouple
 - Application: Standard Panel Mount Connector
 - Connector Type: Panel Mount
 - Plug/Socket: Socket
 - Connector Size: Standard
 - Mounting Type: Stainless Steel Bracket
 - Standards Met: IEC



7747302 Thermocouple

RS PRO QUICKWIRE PANEL MOUNT THERMOCOUPLE CONNECTOR FOR

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Thermocouple Connector
 - For Use With: Type K Thermocouple
 - Application: Standard Quickwire Panel Mount Connector
 - Connector Type: Quickwire Panel Mount
 - Plug/Socket: Socket
 - Connector Size: Standard
 - Mounting Type: Stainless Steel Bracket
 - Standards Met: IEC



7747315 Thermocouple

RS PRO THERMOCOUPLE COMPRESSION FITTING FOR USE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Thermocouple Compression Fitting
 - For Use With: Thermocouple
 - Application: 1/8 BSPP Connector
 - Connector Size: 1/8 BSP
 - Probe Diameter: 1 mm
 - Standards Met: RoHS Compliant



8047975 Thermocouple

RS PRO THERMOCOUPLE COMPRESSION FITTING FOR USE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Thermocouple Compression Fitting
 - For Use With: Thermocouple
 - Application: 1/8 BSPT Connector
 - Connector Size: 1/8 BSPT
 - Probe Diameter: 1 mm
 - Standards Met: RoHS Compliant



8047984 Thermocouple

RS PRO ELECTRODE FOR USE WITH THERMOCOUPLE & FINE WIRE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Electrode
 - For Use With: Thermocouple & Fine Wire Welder
 - Standards Met: RoHS Compliant



8140184 Electrode

RS PRO IN-LINE THERMOCOUPLE COMPRESSION FITTING FOR USE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Thermocouple Compression Fitting
 - For Use With: Thermocouple
 - Application: 1/8 BSPP In-Line Connector
 - Connector Type: In-Line
 - Connector Size: 1/8 BSPP
 - Probe Diameter: 1.5 mm
 - Standards Met: RoHS Compliant



8399496 Thermocouple

RS PRO IN-LINE THERMOCOUPLE COMPRESSION FITTING FOR USE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Accessory Type: Thermocouple Compression Fitting
 - For Use With: Thermocouple
 - Application: 1/8 BSPP In-Line Connector
 - Connector Type: In-Line
 - Connector Size: 1/8 BSPP
 - Probe Diameter: 6 mm
 - Standards Met: RoHS Compliant



8399507 Thermocouple

RS PRO IN-LINE THERMOCOUPLE COMPRESSION FITTING FOR USE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Thermocouple Compression Fitting
 - For Use With: Thermocouple
 - Application: 1/8 BSPT In-Line Connector
 - Connector Type: In-Line
 - Connector Size: 1/8 BSPT
 - Probe Diameter: 3/16 in
 - Standards Met: RoHS Compliant



8399597 Thermocouple

RS PRO IN-LINE THERMOCOUPLE COMPRESSION FITTING FOR USE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Thermocouple Compression Fitting
 - For Use With: Thermocouple
 - Application: 1/4 BSPT In-Line Connector
 - Connector Type: In-Line
 - Connector Size: 1/4 BSPT
 - Probe Diameter: 4.5 mm
 - Standards Met: RoHS Compliant



8399604 Thermocouple

RS PRO PROBE SUPPORT FOR USE WITH THERMOCOUPLE CONNECTOR,

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Accessory Type: Probe Support
 - For Use With: Thermocouple Connector
 - Application: Miniature Connector
 - Connector Size: Miniature
 - Mounting Type: Crimp
 - Probe Diameter: 3 mm
 - Standards Met: RoHS Compliant



8399755 Probe Support

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE J

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Thermocouple Connector
 - For Use With: Type J Thermocouple
 - Application: Miniature In-Line Connector
 - Connector Type: In-Line
 - Plug/Socket: Plug & Socket
 - Connector Size: Miniature
 - Standards Met: IEC



8919012 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE K

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Thermocouple Connector
 - For Use With: Type K Thermocouple
 - Application: Miniature In-Line Connector
 - Connector Type: In-Line
 - Plug/Socket: Plug & Socket
 - Connector Size: Miniature
 - Standards Met: ANSI



8919016 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE K

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Thermocouple Connector
 - For Use With: Type K Thermocouple
 - Application: Standard In-Line Connector
 - Connector Type: In-Line
 - Plug/Socket: Plug & Socket
 - Connector Size: Standard
 - Standards Met: IEC



8919022 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE K

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Thermocouple Connector
 - For Use With: Type K Thermocouple
 - Application: Standard In-Line Connector
 - Connector Type: In-Line
 - Plug/Socket: Plug & Socket
 - Connector Size: Standard
 - Standards Met: ANSI



8919025 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE J

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Thermocouple Connector
 - For Use With: Type J Thermocouple
 - Application: Standard In-Line Connector
 - Connector Type: In-Line
 - Plug/Socket: Plug & Socket
 - Connector Size: Standard
 - Standards Met: IEC



8919028 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE K

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Thermocouple Connector
 - For Use With: Type K Thermocouple
 - Application: Miniature Quickwire Connector
 - Connector Type: Quickwire
 - Plug/Socket: Plug & Socket
 - Connector Size: Miniature
 - Standards Met: IEC



8919031 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE K

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Thermocouple Connector
 - For Use With: Type K Thermocouple
 - Application: Miniature Quickwire Connector
 - Connector Type: Quickwire
 - Plug/Socket: Plug & Socket
 - Connector Size: Miniature
 - Standards Met: ANSI



8919034 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE K

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Thermocouple Connector
 - For Use With: Type K Thermocouple
 - Application: Standard Quickwire Connector
 - Connector Type: Quickwire
 - Plug/Socket: Plug & Socket
 - Connector Size: Standard
 - Standards Met: IEC



8919038 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE K

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Thermocouple Connector
 - For Use With: Type K Thermocouple
 - Application: Standard Quickwire Connector
 - Connector Type: Quickwire
 - Plug/Socket: Plug & Socket
 - Connector Size: Standard
 - Standards Met: ANSI



8919047 Thermocouple

RS PRO THERMOCOUPLE SELECTOR SWITCH FOR USE WITH TYPE K

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Thermocouple Selector Switch
 - For Use With: Type K Thermocouple
 - Mounting Type: Bench
 - Standards Met: ANSI, RoHS Compliant



8919053 Thermocouple

RS PRO THERMOCOUPLE SELECTOR SWITCH FOR USE WITH TYPE K

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Thermocouple Selector Switch
 - For Use With: Type K Thermocouple
 - Mounting Type: Bench
 - Standards Met: IEC, RoHS Compliant



8919056 Thermocouple

RS PRO THERMOCOUPLE SELECTOR SWITCH FOR USE WITH TYPE K

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Thermocouple Selector Switch
 - For Use With: Type K Thermocouple
 - Mounting Type: Bench
 - Standards Met: ANSI, RoHS Compliant



8919062 Thermocouple

RS PRO AIR PURGE COLLAR FOR USE WITH INFRARED TEMPERATURE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Air Purge Collar
 - For Use With: Infrared Temperature Sensor



9058770 Air Purge Collar

RS PRO ADJUSTABLE MOUNTING BRACKET FOR USE WITH INFRARED

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Adjustable Mounting Bracket
 - For Use With: Infrared Temperature Sensor



9058777 Adjustable

ANALOGUE THERMOSTAT, 96X96, 8A RELAY

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Type: Relay
 - Supply Voltage: 230 V ac
 - Size: 96 x 96 mm
 - Number of Outputs: 1
 - Minimum Operating Temperature: 0 °C
 - Maximum Operating Temperature: +400 °C
 - IP Rating: IP65
 - Mounting Type: Panel Mount



1241044 Relay

RS PRO PANEL MOUNT ON/OFF TEMPERATURE CONTROLLER, 77 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Type: Relay
 - Supply Voltage: 230 V ac
 - Size: 77 x 35 mm
 - Number of Inputs: 1
 - Number of Outputs: 1
 - Minimum Operating Temperature: 0 °C
 - Maximum Operating Temperature: +50 °C
 - IP Rating: IP20, IP65



1241051 Relay

RS PRO DIN RAIL PID TEMPERATURE CONTROLLER, 22.5 X 110MM 3 INPUT,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Type: Changeover Relay, Relay
 - Supply Voltage: 24 V ac/dc
 - Size: 22.5 x 110 mm
 - Number of Inputs: 3
 - Number of Outputs: 2
 - Minimum Operating Temperature: 0 °C
 - Maximum Operating Temperature: +55 °C
 - Control Type: Controller



1448683 Changeover

RS PRO DIN RAIL PID TEMPERATURE CONTROLLER, 22.5 X 110MM 3 INPUT,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Type: Changeover Relay, Relay
 - Supply Voltage: 100 → 240 V ac
 - Size: 22.5 x 110 mm
 - Number of Inputs: 3
 - Number of Outputs: 2
 - Minimum Operating Temperature: 0 °C
 - Maximum Operating Temperature: +55 °C
 - Control Type: Controller



1448684 Changeover

RS PRO PID TEMPERATURE CONTROLLER, 72 X 72MM 1 INPUT, 2

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Type: Relay, SSR
 - Supply Voltage: 230 V ac
 - Size: 72 x 72 mm
 - Number of Inputs: 1
 - Number of Outputs: 2
 - Minimum Operating Temperature: 0 °C
 - Maximum Operating Temperature: +50 °C
 - Temperature Range: 0 → 400 °C, 0 → 50 °C



1885159 Relay, SSR

RS PRO PID TEMPERATURE CONTROLLER, 72 X 72MM 1 INPUT, 2

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Type: Relay, SSR
 - Supply Voltage: 230 V ac
 - Size: 72 x 72 mm
 - Number of Inputs: 1
 - Number of Outputs: 2
 - Minimum Operating Temperature: 0 °C
 - Maximum Operating Temperature: +50 °C
 - Temperature Range: 0 → 50 °C, 0 → 800 °C



1885160 Relay, SSR

RS PRO PID TEMPERATURE CONTROLLER, 96 X 96MM 1 INPUT, 2

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Type: Relay, SSR
 - Supply Voltage: 230 V ac
 - Size: 96 x 96 mm
 - Number of Inputs: 1
 - Number of Outputs: 2
 - Minimum Operating Temperature: 0 °C
 - Maximum Operating Temperature: +50 °C
 - Temperature Range: 0 → 400 °C, 0 → 50 °C



1885162 Relay, SSR

TEMPERATURE CONTROLLER, POWER SUPPLY: 24

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Type: Relay, SSR
 - Supply Voltage: 24 V ac
 - Size: 96 x 96 mm
 - Number of Inputs: 1
 - Number of Outputs: 2
 - Minimum Operating Temperature: 0 °C
 - Maximum Operating Temperature: +50 °C
 - Temperature Range: 0 → 50 °C, -200 → +1700 °C



1885164 Relay, SSR

TEMPERATURE CONTROLLER, POWER SUPPLY: 23

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Type: Relay, SSR
 - Supply Voltage: 230 V ac
 - Size: 96 x 96 mm
 - Number of Inputs: 1
 - Number of Outputs: 2
 - Minimum Operating Temperature: 0 °C
 - Maximum Operating Temperature: +50 °C
 - Temperature Range: 0 → 50 °C, -200 → +1700 °C



1885167 Relay, SSR

DIGITAL ON/OFF TEMPERATURE CONTROLLER, 4

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Type: Relay
 - Supply Voltage: 100 → 240 V ac
 - Size: 48 x 48 mm
 - Number of Outputs: 2
 - Minimum Operating Temperature: 0 °C
 - Maximum Operating Temperature: +50 °C
 - IP Rating: IP20, IP65
 - Input Type: K Type Thermocouple



1981172 Relay

DIGITAL ON/OFF TEMPERATURE CONTROLLER, 4

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Type: Relay
 - Supply Voltage: 10 → 30 V dc
 - Size: 48 x 48 mm
 - Number of Outputs: 2
 - Minimum Operating Temperature: 0 °C
 - Maximum Operating Temperature: +50 °C
 - IP Rating: IP20, IP65
 - Input Type: K Type Thermocouple



1981173 Relay

RS PRO ON/OFF TEMPERATURE CONTROLLER, 96MM 1 INPUT, 2

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Type: Analogue Relay
 - Supply Voltage: 230 V ac
 - Size: 96mm x 96 mm
 - Number of Inputs: 1
 - Number of Outputs: 2
 - Minimum Operating Temperature: 0 °C
 - Maximum Operating Temperature: +50 °C
 - Input Type: J Type Thermocouple



1981175 Analogue Relay

RS PRO ON/OFF TEMPERATURE CONTROLLER, 96MM 1 INPUT, 2

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Type: Analogue Relay
 - Supply Voltage: 230 V ac
 - Size: 96mm x 96 mm
 - Number of Inputs: 1
 - Number of Outputs: 2
 - Minimum Operating Temperature: 0 °C
 - Maximum Operating Temperature: +50 °C
 - IP Rating: IP20, IP65



1981176 Analogue Relay

PID CONTROL UNIT, POWER SUPPLY: 100-240

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Type: Relay, SSR
 - Supply Voltage: 100 → 240 V
 - Size: 48 x 48 mm
 - Number of Inputs: 2
 - Number of Outputs: 3
 - Minimum Operating Temperature: 0 °C
 - Maximum Operating Temperature: +50 °C
 - Temperature Range: 0 → +50 °C



2228113 Relay, SSR

PID CONTROL UNIT, POWER SUPPLY: 100-240

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Type: Relay, SSR
 - Supply Voltage: 100 → 240 V
 - Size: 48 x 48 mm
 - Number of Inputs: 2
 - Number of Outputs: 3
 - Minimum Operating Temperature: 0 °C
 - Maximum Operating Temperature: +50 °C
 - Temperature Range: 0 → +50 °C



2228114 Relay, SSR

ON/OFF CONTROL UNIT, POWER SUPPLY: 230 V

 ขนาดบรรจุภัณฑ์: **1 x EA**

- Output Type: Relay
- Supply Voltage: 230 V
- Size: 77 x 35 mm
- Number of Inputs: 1
- Number of Outputs: 1
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +70 °C
- Temperature Range: -20 → +70 °C


2228123 Relay

PID CONTROL UNIT, POWER SUPPLY: 100-240

 ขนาดบรรจุภัณฑ์: **1 x EA**

- Output Type: Relay
- Supply Voltage: 100 → 240 V
- Size: 77 x 35 mm
- Number of Inputs: 1
- Number of Outputs: 2
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +70 °C
- Temperature Range: -20 → +70 °C


2228134 Relay

PID CONTROL UNIT, POWER SUPPLY: 24 VAC/D

 ขนาดบรรจุภัณฑ์: **1 x EA**

- Output Type: Relay
- Supply Voltage: 24 V
- Size: 77 x 35 mm
- Number of Inputs: 1
- Number of Outputs: 2
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +70 °C
- Temperature Range: -20 → +70 °C


2228136 Relay

PID CONTROL UNIT, POWER SUPPLY: 10-30 VD

 ขนาดบรรจุภัณฑ์: **1 x EA**

- Output Type: Relay, SSR
- Supply Voltage: 10 → 30 V
- Size: 77 x 35 mm
- Number of Inputs: 1
- Number of Outputs: 2
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +70 °C
- Temperature Range: -20 → +70 °C


2228139 Relay, SSR

ON/OFF CONTROL UNIT, POWER SUPPLY: 100-2

 ขนาดบรรจุภัณฑ์: **1 x EA**

- Output Type: Relay
- Supply Voltage: 100 → 240 V
- Size: 48 x 48 mm
- Number of Inputs: 1
- Number of Outputs: 1
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: +50 °C
- Temperature Range: 0 → +50 °C


2228140 Relay

RS PRO DIN RAIL PID TEMPERATURE CONTROLLER, 72 X 72MM, 3 OUTPUT

 ขนาดบรรจุภัณฑ์: **1 x EA**

- Output Type: SSR
- Supply Voltage: 24 V ac/dc
- Size: 72 x 72 mm
- Number of Outputs: 3
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: +50 °C
- Temperature Range: 0 → +1700 [Type R Thermocouple] °C, 0 → +1700 [Type S Thermocouple] °C, -199.9 → +650 [RTD - PT 100] °C, -200 → +1300 [Type K Thermocouple] °C, -200 → +400 [Type T Thermocouple] °C, -200 → +650 [RTD - PT 100] °C, -200 → +900 [Type J Thermocouple] °C
- Control Type: ON/OFF, PID Controller


7864772 SSR

PID TEMP CONTROLLER, 72X72, 230VAC

 ขนาดบรรจุภัณฑ์: **1 x EA**

- Output Type: SSR
- Supply Voltage: 230 V ac
- Size: 72 x 72 mm
- Number of Outputs: 3
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: +50 °C
- Temperature Range: 0 → +1700 [Type R Thermocouple] °C, 0 → +1700 [Type S Thermocouple] °C, -199.9 → +650 [RTD - PT 100] °C, -200 → +1300 [Type K Thermocouple] °C, -200 → +400 [Type T Thermocouple] °C, -200 → +650 [RTD - PT 100] °C, -200 → +900 [Type J Thermocouple] °C
- Control Type: ON/OFF, PID Controller


7864775 SSR

ON/OFF TEMP CONTROLLER, 76X35, 24VDC

 ขนาดบรรจุภัณฑ์: **1 x EA**

- Output Type: Relay
- Supply Voltage: 10 → 30 V dc
- Size: 76 x 34.5 mm
- Number of Inputs: 1
- Number of Outputs: 3
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: +50 °C
- IP Rating: NEMA 4X


7983435 Relay

RS PRO PANEL MOUNT PID TEMPERATURE CONTROLLER, 72 X

 ขนาดบรรจุภัณฑ์: **1 x EA**

- Output Type: Relay, SSR
- Supply Voltage: 100 → 240 V ac
- Size: 72 x 72 mm
- Number of Outputs: 3
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: +50 °C
- Temperature Range: 0 → +50 °C
- Control Type: ON/OFF, PID Controller


7983466 Relay, SSR

RS PRO PANEL MOUNT PID TEMPERATURE CONTROLLER, 96 X

 ขนาดบรรจุภัณฑ์: **1 x EA**

- Output Type: SSR
- Supply Voltage: 230 V ac
- Size: 96 x 96 mm
- Number of Outputs: 3
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: +50 °C
- Temperature Range: 0 → +50 °C
- Control Type: ON/OFF, PID Controller


7983472 SSR

RS PRO PANEL MOUNT PID TEMPERATURE CONTROLLER, 96 X

 ขนาดบรรจุภัณฑ์: **1 x EA**

- Output Type: Relay, SSR
- Supply Voltage: 100 → 240 V ac
- Size: 96 x 96 mm
- Number of Outputs: 3
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: +50 °C
- Temperature Range: 0 → +50 °C
- Control Type: ON/OFF, PID Controller


7983479 Relay, SSR

RS PRO 1/8 DIN (H) ON/OFF TEMPERATURE CONTROLLER, 48 X

 ขนาดบรรจุภัณฑ์: **1 x EA**

- Output Type: Relay, SSR
- Supply Voltage: 100 → 240 V ac
- Size: 48 x 96 mm
- Number of Inputs: 1
- Number of Outputs: 2
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: +50 °C
- IP Rating: IP65, NEMA 4X


8751214 Relay

ON/OFF TEMP CONTROLLER, 96X96, 230VAC

 ขนาดบรรจุภัณฑ์: **1 x EA**

- Output Type: Relay
- Supply Voltage: 230 V ac
- Size: 96 x 96 mm
- Number of Inputs: 1
- Number of Outputs: 1
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: +50 °C
- IP Rating: IP65, NEMA 4X


8751232 Relay

ON/OFF TEMP CONTROLLER, 72X72, 230VAC

 ขนาดบรรจุภัณฑ์: **1 x EA**

- Output Type: Relay
- Supply Voltage: 230 V ac
- Size: 72 x 72 mm
- Number of Inputs: 1
- Number of Outputs: 1
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: +50 °C
- IP Rating: IP65, NEMA 4X


8751239 Relay

PID TEMP CONTROLLER, 76X34.5, 230VAC

 ขนาดบรรจุภัณฑ์: **1 x EA**

- Output Type: Relay
- Supply Voltage: 230 V ac
- Size: 76 x 34.5 mm
- Number of Inputs: 4
- Number of Outputs: 4
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: +50 °C
- Temperature Range: 0 → +100 °C


8751242 Relay

PID TEMP CONTROLLER, 76X34.5, 230VAC

 ขนาดบรรจุภัณฑ์: **1 x EA**

- Output Type: Relay
- Supply Voltage: 230 V ac
- Size: 76 x 34.5 mm
- Number of Inputs: 1
- Number of Outputs: 3
- Minimum Operating Temperature: -30 °C
- Maximum Operating Temperature: +80 °C
- Temperature Range: 0 → +100 °C


8751245 Relay

RS PRO 1/16 DIN ON/OFF TEMPERATURE CONTROLLER, 35 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Type: SSR
 - Supply Voltage: 230 V ac
 - Size: 35 x 77 mm
 - Number of Inputs: 1
 - Number of Outputs: 1
 - Minimum Operating Temperature: 0 °C
 - Maximum Operating Temperature: +50 °C
 - IP Rating: IP65, NEMA 4X



8751264 SSR

RS PRO 1/16 DIN ON/OFF TEMPERATURE CONTROLLER, 35 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Output Type: Relay
 - Supply Voltage: 230 V ac
 - Size: 35 x 77 mm
 - Number of Inputs: 1
 - Number of Outputs: 1
 - Minimum Operating Temperature: 0 °C
 - Maximum Operating Temperature: +50 °C
 - IP Rating: IP65, NEMA 4X



8751267 Relay

TEMPERATURE, SENSITIVE LABEL, CLOCK TYPE, SCALE 1, 4, 0-

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Minimum Temperature Sensitivity: 40 °C
 - Maximum Temperature Sensitivity: 54 °C
 - Number of Temperature Levels: 5
 - Orientation: Circle
 - Reversibility: No
 - Label Diameter: 14 mm



285964 40 °C

TERMINAL COVER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Adapter



1241083 Adapter

TEMPERATURE, SENSITIVE LABEL, CLOCK TYPE, SCALE 2, 6, 0-

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Minimum Temperature Sensitivity: 60 °C
 - Maximum Temperature Sensitivity: 82 °C
 - Number of Temperature Levels: 5
 - Orientation: Circle
 - Reversibility: No
 - Label Diameter: 14 mm



285970 60 °C

TEMPERATURE, SENSITIVE LABEL, CLOCK TYPE, SCALE 3, 8, 8-

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Minimum Temperature Sensitivity: 88 °C
 - Maximum Temperature Sensitivity: 110 °C
 - Number of Temperature Levels: 5
 - Orientation: Circle
 - Reversibility: No
 - Label Diameter: 14 mm



285986 88 °C

TEMPERATURE, SENSITIVE LABEL, CLOCK TYPE, SCALE 4, 11, 6-

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Minimum Temperature Sensitivity: 116 °C
 - Maximum Temperature Sensitivity: 138 °C
 - Number of Temperature Levels: 5
 - Orientation: Circle
 - Reversibility: No
 - Label Diameter: 14 mm



285992 116 °C

TEMPERATURE, SENSITIVE LABEL, CLOCK TYPE, SCALE 5, 14, 3-

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Minimum Temperature Sensitivity: 143 °C
 - Maximum Temperature Sensitivity: 166 °C
 - Number of Temperature Levels: 5
 - Orientation: Circle
 - Reversibility: No
 - Label Diameter: 14 mm



286002 143 °C

RS PRO NON-REVERSIBLE TEMPERATURE SENSITIVE LABEL, 171 °C

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Minimum Temperature Sensitivity: 171 °C
 - Maximum Temperature Sensitivity: 193 °C
 - Number of Temperature Levels: 5
 - Orientation: Circle
 - Reversibility: No
 - Label Diameter: 14 mm



286018 171 °C

RS PRO NON-REVERSIBLE TEMPERATURE SENSITIVE LABEL, 40 °C

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Minimum Temperature Sensitivity: 40 °C
 - Maximum Temperature Sensitivity: 46 °C
 - Number of Temperature Levels: 4
 - Orientation: Circle
 - Reversibility: No
 - Label Length: 11 mm
 - Label Width: 4 mm



286080 40 °C

TEMPERATURE, SENSITIVE LABEL, MICRO, SCALE 2, 4, 9-65 DEGC

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Minimum Temperature Sensitivity: 49 °C
 - Maximum Temperature Sensitivity: 65 °C
 - Number of Temperature Levels: 4
 - Orientation: Circle
 - Reversibility: No
 - Label Length: 11 mm
 - Label Width: 4 mm



286096 49 °C

RS PRO NON-REVERSIBLE TEMPERATURE SENSITIVE LABEL, 71 °C

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Minimum Temperature Sensitivity: 71 °C
 - Maximum Temperature Sensitivity: 88 °C
 - Number of Temperature Levels: 4
 - Orientation: Circle
 - Reversibility: No
 - Label Length: 11 mm
 - Label Width: 4 mm



286103 71 °C

RS PRO NON-REVERSIBLE TEMPERATURE SENSITIVE LABEL, 93 °C

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Minimum Temperature Sensitivity: 93 °C
 - Maximum Temperature Sensitivity: 110 °C
 - Number of Temperature Levels: 4
 - Orientation: Circle
 - Reversibility: No
 - Label Length: 11 mm
 - Label Width: 4 mm



286119 93 °C

TEMPERATURE, SENSITIVE LABEL, MICRO, SCALE 5, 11, 6-132 DEGC

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Minimum Temperature Sensitivity: 116 °C
 - Maximum Temperature Sensitivity: 132 °C
 - Number of Temperature Levels: 4
 - Orientation: Circle
 - Reversibility: No
 - Label Length: 11 mm
 - Label Width: 4 mm



286125 116 °C

RS PRO NON-REVERSIBLE TEMPERATURE SENSITIVE LABEL,

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Minimum Temperature Sensitivity: 138 °C
 - Maximum Temperature Sensitivity: 154 °C
 - Number of Temperature Levels: 4
 - Orientation: Circle
 - Reversibility: No
 - Label Length: 11 mm
 - Label Width: 4 mm



286131 138 °C

LABEL, TEMPERATURE SENSITIVE, MICRO KIT 1, 10X40-

- ขนาดบรรจุภัณฑ์: **1 x KT**
- Minimum Temperature Sensitivity: 40 °C
 - Maximum Temperature Sensitivity: 88 °C
 - Number of Temperature Levels: 4
 - Labels Per Product: 30
 - Orientation: Horizontal
 - Reversibility: No
 - Label Length: 4 mm
 - Label Width: 11 mm



552618 40 °C

LABEL, TEMPERATURE SENSITIVE, MICRO KIT 2, 10X93-

- ขนาดบรรจุภัณฑ์: **1 x KT**
- Minimum Temperature Sensitivity: 93 °C
 - Maximum Temperature Sensitivity: 154 °C
 - Number of Temperature Levels: 4
 - Labels Per Product: 30
 - Orientation: Horizontal
 - Reversibility: No
 - Label Length: 4 mm
 - Label Width: 11 mm



552624 93 °C

RS PRO NON-REVERSIBLE TEMPERATURE SENSITIVE LABEL,


- ขนาดบรรจุภัณฑ์: **1 x KT**
- Minimum Temperature Sensitivity: 160 °C
 - Maximum Temperature Sensitivity: 224 °C
 - Number of Temperature Levels: 4
 - Labels Per Product: 30
 - Orientation: Horizontal
 - Reversibility: No
 - Label Length: 4 mm
 - Label Width: 11 mm



552630 160 °C

LABEL, TEMPERATURE SENSITIVE, SCALE B, 71-110DEGC


- ขนาดบรรจุภัณฑ์: **10 x EA**
- Minimum Temperature Sensitivity: 71 °C
 - Maximum Temperature Sensitivity: 110 °C
 - Number of Temperature Levels: 8
 - Orientation: Vertical
 - Reversibility: No
 - Label Length: 18 mm
 - Label Width: 51 mm



555409 71 °C

LABEL, TEMPERATURE SENSITIVE, SCALE C, 116-154DEGC

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Minimum Temperature Sensitivity: 116 °C
 - Maximum Temperature Sensitivity: 154 °C
 - Number of Temperature Levels: 8
 - Orientation: Vertical
 - Reversibility: No
 - Label Length: 18 mm
 - Label Width: 51 mm



555415 116 °C

LABEL, TEMPERATURE SENSITIVE, SCALE D, 160-199DEGC

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Minimum Temperature Sensitivity: 160 °C
 - Maximum Temperature Sensitivity: 199 °C
 - Number of Temperature Levels: 8
 - Orientation: Vertical
 - Reversibility: No
 - Label Length: 18 mm
 - Label Width: 51 mm



555421 160 °C

LABEL, TEMPERATURE SENSITIVE, SCALE E, 204-260DEGC

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Minimum Temperature Sensitivity: 204 °C
 - Maximum Temperature Sensitivity: 260 °C
 - Number of Temperature Levels: 8
 - Orientation: Vertical
 - Reversibility: No
 - Label Length: 18 mm
 - Label Width: 51 mm



555437 204 °C

11 LEVEL REVERSIBLE SCA STRIPS VERTICAL

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Minimum Temperature Sensitivity: 0 °C
 - Maximum Temperature Sensitivity: 50 °C
 - Number of Temperature Levels: 11
 - Labels Per Product: 10
 - Orientation: Vertical
 - Reversibility: Yes
 - Label Length: 18 mm
 - Label Width: 18 mm



9064599 0 °C

TRAFFIC LIGHT INDICATOR REVERSIBLE STRIP

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Minimum Temperature Sensitivity: 50 °C
 - Maximum Temperature Sensitivity: 70 °C
 - Number of Temperature Levels: 3
 - Labels Per Product: 10
 - Reversibility: Yes
 - Label Length: 52 mm
 - Label Width: 48 mm



9064602 50 °C

RS PRO TEMPERATURE LABEL INDICATOR, 2°C TO 8°C, 2 LEVELS

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Minimum Temperature Sensitivity: 2 °C
 - Maximum Temperature Sensitivity: 8 °C
 - Number of Temperature Levels: 2
 - Labels Per Product: 10
 - Orientation: Horizontal
 - Reversibility: Yes
 - Label Length: 40 mm
 - Label Width: 96 mm



9064606 2 °C

11 LEVEL REVERSIBLE SCA STRIPS VERTICAL

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Minimum Temperature Sensitivity: 50 °C
 - Maximum Temperature Sensitivity: 100 °C
 - Number of Temperature Levels: 11
 - Labels Per Product: 10
 - Orientation: Vertical
 - Reversibility: Yes
 - Label Length: 51 mm
 - Label Width: 33 mm



9064609 50 °C

RS PRO TEMPERATURE LABEL INDICATOR, 1°C TO 12°C, 12 LEVELS

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Minimum Temperature Sensitivity: 1 °C
 - Maximum Temperature Sensitivity: 12 °C
 - Number of Temperature Levels: 12
 - Labels Per Product: 10
 - Orientation: Horizontal
 - Reversibility: Yes
 - Label Length: 10 mm
 - Label Width: 90 mm



9064612 1 °C

RS PRO TEMPERATURE LABEL INDICATOR, 50°C

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Minimum Temperature Sensitivity: 50 °C
 - Labels Per Product: 10
 - Orientation: Vertical
 - Label Diameter: 37 mm



9064615 50 °C

ROOM THERMOMETER REVERSIBLE 10C - 32C

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Minimum Temperature Sensitivity: 10 °C
 - Maximum Temperature Sensitivity: 32 °C
 - Number of Temperature Levels: 12
 - Labels Per Product: 10
 - Orientation: Horizontal
 - Reversibility: Yes
 - Label Length: 10 mm
 - Label Width: 90 mm



9064618 10 °C

RS PRO TEMPERATURE TRANSMITTER PT100 INPUT, 12 → 36 V DC, 0 → +100

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Input Type: PT100
 - Supply Voltage: 12 → 36 V dc
 - Diameter: 42 mm
 - Minimum Operating Temperature: 0 °C
 - Maximum Operating Temperature: +100 °C
 - Series: RS PRO
 - Depth: 32 mm



1852284 PT100

RS PRO TEMPERATURE TRANSMITTER PT100 INPUT, 12 → 36 V DC, 0 → +200

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Input Type: PT100
 - Supply Voltage: 12 → 36 V dc
 - Diameter: 42 mm
 - Minimum Operating Temperature: 0 °C
 - Maximum Operating Temperature: +200 °C
 - Series: RS PRO
 - Depth: 32 mm



1852290 PT100

RS PRO TEMPERATURE TRANSMITTER THERMOCOUPLE TYPE J INPUT, 12 →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Input Type: Thermocouple Type J
 - Supply Voltage: 12 → 36 V dc
 - Diameter: 42 mm
 - Minimum Operating Temperature: 0 °C
 - Maximum Operating Temperature: +300 °C
 - Series: RS PRO
 - Depth: 32 mm



1852341 Thermocouple

RS PRO TEMPERATURE TRANSMITTER THERMOCOUPLE TYPE K INPUT, 12 →

ขนาดบรรจุภัณฑ์: **1 x EA**

- Input Type: Thermocouple Type K
- Supply Voltage: 12 → 36 V dc
- Diameter: 42 mm
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: +200 °C
- Series: RS PRO
- Depth: 32 mm



1852357 Thermocouple

RS PRO TEMPERATURE TRANSMITTER THERMOCOUPLE TYPE K INPUT, 12 →

ขนาดบรรจุภัณฑ์: **1 x EA**

- Input Type: Thermocouple Type K
- Supply Voltage: 12 → 36 V dc
- Diameter: 42 mm
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: +1100 °C
- Series: RS PRO
- Depth: 32 mm



1852363 Thermocouple

RS PRO TEMPERATURE TRANSMITTER PT100 INPUT, 10 → 30 V DC, 0 → +70 °C

ขนาดบรรจุภัณฑ์: **1 x EA**

- Input Type: PT100
- Supply Voltage: 10 → 30 V dc
- Diameter: 42 mm
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: +70 °C
- Series: RS PRO
- Depth: 33 mm



3630216 PT100

RS PRO TEMPERATURE TRANSMITTER VARIOUS INPUT, 10 → 30 V DC

ขนาดบรรจุภัณฑ์: **1 x EA**

- Input Type: Thermocouple Type J, Thermocouple Type K, Thermocouple Type T
- Supply Voltage: 10 → 30 V dc
- Diameter: 42 mm
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: +70 °C
- Series: RS PRO
- Depth: 23 mm



3630222 Thermocouple

RS PRO TEMPERATURE TRANSMITTER PT100 INPUT, 10 → 30 V DC, 0 → +70 °C

ขนาดบรรจุภัณฑ์: **1 x EA**

- Input Type: PT100
- Supply Voltage: 10 → 30 V dc
- Diameter: 43 mm
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: +70 °C
- Series: RS PRO
- Depth: 21 mm



3630238 PT100

RS PRO TEMPERATURE TRANSMITTER VARIOUS INPUT, 8 → 30 V DC

ขนาดบรรจุภัณฑ์: **1 x EA**

- Input Type: mV, Thermocouple Type E, Thermocouple Type J, Thermocouple Type K, Thermocouple Type N, Thermocouple Type R, Thermocouple Type S, Thermocouple Type T
- Supply Voltage: 8 → 30 V dc
- Diameter: 43 mm
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +70 °C
- Series: RS PRO
- Depth: 21 mm



3817132 mV,

RS PRO TYPE J THERMOCOUPLE WIRE, 10M, UNSCREENED, PVC

ขนาดบรรจุภัณฑ์: **10 x MTR**

- Length: 10 m
- Insulation Material: PVC
- Thermocouple Type: J
- Screened/Unscreened: Unscreened
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: BS



150010 10 m

RS PRO TYPE K THERMOCOUPLE WIRE, 10M, UNSCREENED, GLASS

ขนาดบรรจุภัณฑ์: **10 x MTR**

- Length: 10 m
- Insulation Material: Glass Fibre
- Maximum Operating Temperature: +350 °C
- Thermocouple Type: K
- Screened/Unscreened: Unscreened
- Core Strands: 1/0.315 mm
- Cable Shape: Flat Pair
- Number of Strands: 2



151209 10 m

RS PRO TYPE K THERMOCOUPLE WIRE, 25M, UNSCREENED, PVC

ขนาดบรรจุภัณฑ์: **25 x MTR**

- Length: 25 m
- Insulation Material: PVC
- Maximum Operating Temperature: +80 °C
- Thermocouple Type: K
- Screened/Unscreened: Unscreened
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2



151316 25 m

RS PRO TYPE K THERMOCOUPLE WIRE, 100M, PVC INSULATION,

ขนาดบรรจุภัณฑ์: **100 x MTR**

- Length: 100 m
- Insulation Material: PVC
- Thermocouple Type: K
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: BS




158963 100 m

RS PRO TYPE E THERMOCOUPLE WIRE, 10M, PVC INSULATION,

ขนาดบรรจุภัณฑ์: **1 x EA**

- Length: 10 m
- Insulation Material: PVC
- Thermocouple Type: E
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: IEC



1365863 10 m

RS PRO TYPE E THERMOCOUPLE WIRE, 25M, PVC INSULATION,

ขนาดบรรจุภัณฑ์: **1 x EA**

- Length: 25 m
- Insulation Material: PVC
- Thermocouple Type: E
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: IEC



1365864 25 m

RS PRO TYPE E THERMOCOUPLE WIRE, 10M, PFA INSULATION,

ขนาดบรรจุภัณฑ์: **1 x EA**

- Length: 10 m
- Insulation Material: PFA
- Thermocouple Type: E
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: IEC



1365865 10 m

RS PRO TYPE J THERMOCOUPLE WIRE, 25M, PFA INSULATION,

ขนาดบรรจุภัณฑ์: **1 x EA**

- Length: 25 m
- Insulation Material: PFA
- Thermocouple Type: J
- Core Strands: 1/0.3 mm
- Number of Strands: 2
- Standards Met: IEC



1365866 25 m

RS PRO TYPE J THERMOCOUPLE WIRE, 10M, SCREENED, PFA

ขนาดบรรจุภัณฑ์: **1 x EA**

- Length: 10 m
- Insulation Material: PFA
- Maximum Operating Temperature: +260 °C
- Thermocouple Type: J
- Screened/Unscreened: Screened
- Core Strands: 1/0.3 mm
- Cable Shape: Twin Twisted
- Number of Strands: 2



1780950 10 m

RS PRO TYPE K THERMOCOUPLE WIRE, 25M, PVC INSULATION, +105°C

ขนาดบรรจุภัณฑ์: **1 x EA**

- Length: 25 m
- Insulation Material: PVC
- Thermocouple Type: K
- Maximum Operating Temperature: +105 °C
- Core Strands: 23/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: IEC



1853004 25 m

RS PRO RESISTANCE THERMOMETER DETECTOR (RTD) WIRE, 5M,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 5 m
 - Insulation Material: PVC
 - Screened/Unscreened: Screened
 - Core Strands: 7/0.2 mm
 - Number of Strands: 4



1853010 5 m

RS PRO TYPE K THERMOCOUPLE WIRE, 5M, GLASS FIBRE INSULATION,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 5 m
 - Insulation Material: Glass Fibre
 - Thermocouple Type: K
 - Maximum Operating Temperature: +350 °C
 - Core Strands: 1/0.315 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: BS



1853011 5 m

RS PRO TYPE RTD RESISTANCE THERMOMETER DETECTOR (RTD)

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 5 m
 - Insulation Material: Silicone Rubber
 - Thermocouple Type: RTD
 - Maximum Operating Temperature: +200 °C
 - Core Strands: 7/0.2 mm
 - Number of Strands: 4



1853014 5 m

RS PRO TYPE RTD RESISTANCE THERMOMETER DETECTOR (RTD)

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 5 m
 - Insulation Material: PTFE
 - Thermocouple Type: RTD
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 7/0.2 mm
 - Number of Strands: 4



1853015 5 m

RS PRO TYPE K THERMOCOUPLE WIRE, 5M, GLASS FIBRE INSULATION,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 5 m
 - Insulation Material: Glass Fibre
 - Maximum Operating Temperature: +350 °C
 - Thermocouple Type: K
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Voltage Rating: 220 → 250 V ac



1853016 5 m

RS PRO TYPE K THERMOCOUPLE WIRE, 5M, PFA INSULATION, +260°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 5 m
 - Insulation Material: PFA
 - Thermocouple Type: K
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 1/0.315 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: IEC



1853019 5 m

RS PRO TYPE K THERMOCOUPLE WIRE, 5M, PFA INSULATION, +260°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 5 m
 - Insulation Material: PFA
 - Maximum Operating Temperature: +260 °C
 - Thermocouple Type: K
 - Core Strands: 1/0.2 mm
 - Number of Strands: 2
 - Standards Met: IEC



1853020 5 m

RS PRO TYPE K THERMOCOUPLE WIRE, 25M, PFA INSULATION, +250°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 25 m
 - Insulation Material: PFA
 - Thermocouple Type: K
 - Maximum Operating Temperature: +250 °C
 - Core Strands: 1/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: IEC



2000618 25 m

RS PRO TYPE K THERMOCOUPLE WIRE, 100M, HIGH TEMPERATURE


- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 100 m
 - Insulation Material: High Temperature Glass Fibre
 - Maximum Operating Temperature: +700 °C
 - Thermocouple Type: K
 - Core Strands: 1/0.711 mm
 - Number of Strands: 2
 - Standards Met: ANSI



2000622 100 m

RS PRO TYPE K THERMOCOUPLE WIRE, 25M, PFA INSULATION, +250°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 25 m
 - Insulation Material: PFA
 - Thermocouple Type: K
 - Maximum Operating Temperature: +250 °C
 - Core Strands: 1/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: ANSI



2000623 25 m

RS PRO TYPE K THERMOCOUPLE WIRE, 25M, PFA INSULATION, +250°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 25 m
 - Insulation Material: PFA
 - Thermocouple Type: K
 - Maximum Operating Temperature: +250 °C
 - Core Strands: 1/0.3 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: ANSI



2000625 25 m

RS PRO TYPE K THERMOCOUPLE WIRE, 100M, PFA INSULATION,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 100 m
 - Insulation Material: PFA
 - Thermocouple Type: K
 - Maximum Operating Temperature: +250 °C
 - Core Strands: 1/0.5 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: ANSI



2000628 100 m

RS PRO TYPE J THERMOCOUPLE WIRE, 50M, UNSCREENED, PVC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 50 m
 - Insulation Material: PVC
 - Maximum Operating Temperature: +105 °C
 - Thermocouple Type: J
 - Screened/Unscreened: Unscreened
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2



2154870 50 m

RS PRO TYPE J THERMOCOUPLE WIRE, 10M, SCREENED, PVC MYLAR

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 10 m
 - Insulation Material: PVC Mylar
 - Maximum Operating Temperature: +105 °C
 - Thermocouple Type: J
 - Screened/Unscreened: Screened
 - Core Strands: 7/0.2 mm
 - Cable Shape: Twisted
 - Number of Strands: 2



2154871 10 m

RS PRO TYPE J THERMOCOUPLE WIRE, 10M, UNSCREENED, PTFE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 10 m
 - Insulation Material: PTFE
 - Maximum Operating Temperature: +260 °C
 - Thermocouple Type: J
 - Screened/Unscreened: Unscreened
 - Core Strands: 1/0.508 mm
 - Cable Shape: Twin Twisted
 - Number of Strands: 2



2154882 10 m

RS PRO TYPE J THERMOCOUPLE WIRE, 10M, UNSCREENED, PFA

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 10 m
 - Insulation Material: PFA
 - Maximum Operating Temperature: +260 °C
 - Thermocouple Type: J
 - Screened/Unscreened: Unscreened
 - Core Strands: 1/0.508 mm
 - Cable Shape: Twin Twisted
 - Number of Strands: 2



2154886 10 m

RS PRO TYPE J THERMOCOUPLE WIRE, 100M, UNSCREENED, PTFE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 100 m
 - Insulation Material: PTFE
 - Maximum Operating Temperature: +260 °C
 - Thermocouple Type: J
 - Screened/Unscreened: Unscreened
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2



2154888 100 m

RS PRO TYPE J THERMOCOUPLE WIRE, 10M, UNSCREENED, SILICONE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 10 m
 - Insulation Material: Silicone Rubber
 - Maximum Operating Temperature: +200 °C
 - Thermocouple Type: J
 - Screened/Unscreened: Unscreened
 - Core Strands: 7/0.2 mm
 - Cable Shape: Twisted
 - Number of Strands: 2



2154889 10 m

RS PRO TYPE K THERMOCOUPLE WIRE, 10M, UNSCREENED, PVC


- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 10 m
 - Insulation Material: PVC
 - Maximum Operating Temperature: +105 °C
 - Thermocouple Type: K
 - Screened/Unscreened: Unscreened
 - Core Strands: 13/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2



2154893 10 m

RS PRO TYPE K THERMOCOUPLE WIRE, 50M, UNSCREENED, PVC


- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 50 m
 - Insulation Material: PVC
 - Maximum Operating Temperature: +105 °C
 - Thermocouple Type: K
 - Screened/Unscreened: Unscreened
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2



2154895 50 m

RS PRO TYPE K THERMOCOUPLE WIRE, 10M, UNSCREENED, PVC

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 10 m
 - Insulation Material: PVC
 - Maximum Operating Temperature: +105 °C
 - Thermocouple Type: K
 - Screened/Unscreened: Unscreened
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2



2154896 10 m

RS PRO TYPE K THERMOCOUPLE WIRE, 10M, UNSCREENED, PTFE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 10 m
 - Insulation Material: PTFE
 - Maximum Operating Temperature: +260 °C
 - Thermocouple Type: K
 - Screened/Unscreened: Unscreened
 - Core Strands: 1/0.508 mm
 - Cable Shape: Twin Twisted
 - Number of Strands: 2



2154899 10 m

RS PRO TYPE K THERMOCOUPLE WIRE, 10M, UNSCREENED, PFA

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 10 m
 - Insulation Material: PFA
 - Maximum Operating Temperature: +260 °C
 - Thermocouple Type: K
 - Screened/Unscreened: Unscreened
 - Core Strands: 1/0.3 mm
 - Cable Shape: Twin Twisted
 - Number of Strands: 2



2154901 10 m

RS PRO TYPE K THERMOCOUPLE WIRE, 10M, UNSCREENED, PFA

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 10 m
 - Insulation Material: PFA
 - Maximum Operating Temperature: +260 °C
 - Thermocouple Type: K
 - Screened/Unscreened: Unscreened
 - Core Strands: 1/0.3 mm
 - Cable Shape: Twin Twisted
 - Number of Strands: 2



2154902 10 m

RS PRO TYPE K THERMOCOUPLE WIRE, 10M, UNSCREENED, PTFE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 10 m
 - Insulation Material: PTFE
 - Maximum Operating Temperature: +260 °C
 - Thermocouple Type: K
 - Screened/Unscreened: Unscreened
 - Core Strands: 1/0.315 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2



2154905 10 m

RS PRO TYPE K THERMOCOUPLE WIRE, 50M, UNSCREENED, GLASS

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 50 m
 - Insulation Material: Glass Fibre
 - Maximum Operating Temperature: +350 °C
 - Thermocouple Type: K
 - Screened/Unscreened: Unscreened
 - Core Strands: 1/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2



2154927 50 m

RS PRO TYPE K THERMOCOUPLE WIRE, 10M, UNSCREENED, PVC

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 10 m
 - Insulation Material: PVC
 - Maximum Operating Temperature: +105 °C
 - Thermocouple Type: K
 - Screened/Unscreened: Unscreened
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2



2154936 10 m

RS PRO TYPE K THERMOCOUPLE WIRE, 50M, UNSCREENED, PVC

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 50 m
 - Insulation Material: PVC
 - Maximum Operating Temperature: +105 °C
 - Thermocouple Type: K
 - Screened/Unscreened: Unscreened
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2



2154937 50 m

RS PRO TYPE K THERMOCOUPLE WIRE, 10M, UNSCREENED, PVC

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 10 m
 - Insulation Material: PVC
 - Maximum Operating Temperature: +260 °C
 - Thermocouple Type: K
 - Screened/Unscreened: Unscreened
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2



2154938 10 m

RS PRO TYPE K THERMOCOUPLE WIRE, 25M, UNSCREENED, PVC

- ขนาดบรรจุภัณฑ์: 25 x MTR
- Length: 25 m
 - Insulation Material: PVC
 - Maximum Operating Temperature: +105 °C
 - Thermocouple Type: K
 - Screened/Unscreened: Unscreened
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2



2194551 25 m

RS PRO TYPE K THERMOCOUPLE WIRE, 100M, UNSCREENED, PVC

- ขนาดบรรจุภัณฑ์: 100 x MTR
- Length: 100 m
 - Insulation Material: PVC
 - Maximum Operating Temperature: +105 °C
 - Thermocouple Type: K
 - Screened/Unscreened: Unscreened
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2



2194573 100 m

RS PRO TYPE K THERMOCOUPLE WIRE, 10M, UNSCREENED, GLASS

- ขนาดบรรจุภัณฑ์: 10 x MTR
- Length: 10 m
 - Insulation Material: Glass Fibre
 - Maximum Operating Temperature: +400 °C
 - Thermocouple Type: K
 - Screened/Unscreened: Unscreened
 - Core Strands: 1/0.315 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2



2194589 10 m

RS PRO TYPE K THERMOCOUPLE WIRE, 10M, UNSCREENED, GLASS

- ขนาดบรรจุภัณฑ์: 10 x MTR
- Length: 10 m
 - Insulation Material: Glass Fibre
 - Maximum Operating Temperature: +400 °C
 - Thermocouple Type: K
 - Screened/Unscreened: Unscreened
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2



2194595 10 m

RS PRO TYPE N THERMOCOUPLE WIRE, 10M, UNSCREENED, PVC

- ขนาดบรรจุภัณฑ์: 10 x MTR
- Length: 10 m
 - Insulation Material: PVC
 - Maximum Operating Temperature: +105 °C
 - Thermocouple Type: N
 - Screened/Unscreened: Unscreened
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2



2194668 10 m

RS PRO TYPE T THERMOCOUPLE WIRE, 10M, UNSCREENED, PVC

- ขนาดบรรจุภัณฑ์: 10 x MTR
- Length: 10 m
 - Insulation Material: PVC
 - Maximum Operating Temperature: +105 °C
 - Thermocouple Type: T
 - Screened/Unscreened: Unscreened
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2



2194703 10 m

RS PRO TYPE J THERMOCOUPLE WIRE, 10M, UNSCREENED, PVC

- ขนาดบรรจุภัณฑ์: 10 x MTR
- Length: 10 m
 - Insulation Material: PVC
 - Maximum Operating Temperature: +105 °C
 - Thermocouple Type: J
 - Screened/Unscreened: Unscreened
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2



2194753 10 m

RS PRO TYPE R/S THERMOCOUPLE WIRE, 10M, UNSCREENED, PVC

- ขนาดบรรจุภัณฑ์: 10 x MTR
- Length: 10 m
 - Insulation Material: PVC
 - Maximum Operating Temperature: +105 °C
 - Thermocouple Type: R/S
 - Screened/Unscreened: Unscreened
 - Core Strands: 13/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2



2194769 10 m

RS PRO TYPE E THERMOCOUPLE WIRE, 25M, UNSCREENED, PFA

- ขนาดบรรจุภัณฑ์: 1 x EA
- Insulation Material: PFA
 - Length: 25 m
 - Maximum Operating Temperature: +260 °C
 - Thermocouple Type: E
 - Screened/Unscreened: Unscreened
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2



2209471 PFA

RS PRO TYPE E THERMOCOUPLE WIRE, 50M, UNSCREENED, PFA

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 50 m
 - Insulation Material: PFA
 - Maximum Operating Temperature: +260 °C
 - Thermocouple Type: E
 - Screened/Unscreened: Unscreened
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2



2209472 50 m

RS PRO TYPE E THERMOCOUPLE WIRE, 100M, UNSCREENED, PFA

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 100 m
 - Insulation Material: PFA
 - Maximum Operating Temperature: +260 °C
 - Thermocouple Type: E
 - Screened/Unscreened: Unscreened
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2



2209474 100 m

RS PRO TYPE T THERMOCOUPLE WIRE, 100M, UNSCREENED, GLASS

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 100 m
 - Insulation Material: Glass Fibre
 - Maximum Operating Temperature: +350 °C
 - Thermocouple Type: T
 - Screened/Unscreened: Unscreened
 - Core Strands: 1/0.315 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2



2209481 100 m

RS PRO TYPE K THERMOCOUPLE & EXTENSION WIRE, 10M, SCREENED,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 10 m
 - Insulation Material: PFA
 - Maximum Operating Temperature: +260 °C
 - Thermocouple Type: K
 - Screened/Unscreened: Screened
 - Cable Shape: Twisted
 - Number of Strands: 2
 - Standards Met: IEC



2209492 10 m

RS PRO TYPE K THERMOCOUPLE & EXTENSION WIRE, 10M, SCREENED,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 10 m
 - Insulation Material: PFA
 - Maximum Operating Temperature: +260 °C
 - Thermocouple Type: K
 - Screened/Unscreened: Screened
 - Cable Shape: Twisted
 - Number of Strands: 2
 - Standards Met: IEC



2209493 10 m

RS PRO TYPE K THERMOCOUPLE & EXTENSION WIRE, 1M, SCREENED,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 1 m
 - Insulation Material: PFA
 - Maximum Operating Temperature: +260 °C
 - Thermocouple Type: K
 - Screened/Unscreened: Screened
 - Cable Shape: Twisted
 - Number of Strands: 2
 - Standards Met: IEC



2209494 1 m

RS PRO TYPE K THERMOCOUPLE & EXTENSION WIRE, 3M, SCREENED,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 3 m
 - Insulation Material: PFA
 - Maximum Operating Temperature: +260 °C
 - Thermocouple Type: K
 - Screened/Unscreened: Screened
 - Cable Shape: Twisted
 - Number of Strands: 2
 - Standards Met: IEC



2209495 3 m

RS PRO TYPE K THERMOCOUPLE & EXTENSION WIRE, 3M, SCREENED,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 3 m
 - Insulation Material: PFA
 - Maximum Operating Temperature: +260 °C
 - Thermocouple Type: K
 - Screened/Unscreened: Screened
 - Cable Shape: Twisted
 - Number of Strands: 2
 - Standards Met: IEC



2209497 3 m

RS PRO TYPE T THERMOCOUPLE WIRE, 10M, UNSCREENED, PTFE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 10 m
 - Insulation Material: PTFE
 - Maximum Operating Temperature: +260 °C
 - Thermocouple Type: T
 - Screened/Unscreened: Unscreened
 - Core Strands: 1/0.315 mm
 - Cable Shape: Twin Twisted
 - Number of Strands: 2



2209501 10 m

RS PRO TYPE T THERMOCOUPLE WIRE, 100M, UNSCREENED, PTFE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 100 m
 - Insulation Material: PTFE
 - Maximum Operating Temperature: +260 °C
 - Thermocouple Type: T
 - Screened/Unscreened: Unscreened
 - Core Strands: 1/0.315 mm
 - Cable Shape: Twin Twisted
 - Number of Strands: 2



2209503 100 m

RS PRO TYPE U THERMOCOUPLE WIRE, 25M, SCREENED, GLASS FIBRE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 25 m
 - Insulation Material: Glass Fibre
 - Maximum Operating Temperature: +350 °C
 - Thermocouple Type: U
 - Screened/Unscreened: Screened
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2



2209506 25 m

RS PRO TYPE U THERMOCOUPLE WIRE, 100M, SCREENED, GLASS FIBRE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 100 m
 - Insulation Material: Glass Fibre
 - Maximum Operating Temperature: +350 °C
 - Thermocouple Type: U
 - Screened/Unscreened: Screened
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2



2209508 100 m

RS PRO TYPE T THERMOCOUPLE WIRE, 10M, UNSCREENED, PTFE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 10 m
 - Insulation Material: PTFE
 - Maximum Operating Temperature: +260 °C
 - Thermocouple Type: T
 - Screened/Unscreened: Unscreened
 - Core Strands: 1/0.376 mm
 - Cable Shape: Single Shot
 - Number of Strands: 2



2209523 10 m

RS PRO TYPE K THERMOCOUPLE & EXTENSION WIRE, 10M, UNSCREENED,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 10 m
 - Insulation Material: PVC
 - Maximum Operating Temperature: +105 °C
 - Thermocouple Type: K
 - Screened/Unscreened: Unscreened
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2



2318468 10 m

RS PRO TYPE K THERMOCOUPLE & EXTENSION WIRE, 1M, UNSCREENED,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 1 m
 - Insulation Material: PVC
 - Maximum Operating Temperature: +105 °C
 - Thermocouple Type: K
 - Screened/Unscreened: Unscreened
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2



2318472 1 m

RS PRO TYPE K THERMOCOUPLE WIRE, 25M, UNSCREENED, PVC

- ขนาดบรรจุภัณฑ์: 25 x MTR
- Length: 25 m
 - Insulation Material: PVC
 - Maximum Operating Temperature: +105 °C
 - Thermocouple Type: K
 - Screened/Unscreened: Unscreened
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2



2363820 25 m

RS PRO TYPE K THERMOCOUPLE WIRE, 25M, UNSCREENED, GLASS

- ขนาดบรรจุภัณฑ์: 25 x MTR
- Length: 25 m
 - Insulation Material: Glass Fibre
 - Maximum Operating Temperature: +400 °C
 - Thermocouple Type: K
 - Screened/Unscreened: Unscreened
 - Core Strands: 1/0.315 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2



2363836 25 m

RS PRO TYPE K THERMOCOUPLE WIRE, 25M, SCREENED, GLASS FIBRE

- ขนาดบรรจุภัณฑ์: 25 x MTR
- Length: 25 m
 - Insulation Material: Glass Fibre
 - Maximum Operating Temperature: +400 °C
 - Thermocouple Type: K
 - Screened/Unscreened: Screened
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2



2363842 25 m

RS PRO TYPE K THERMOCOUPLE WIRE, 25M, UNSCREENED, PTFE

- ขนาดบรรจุภัณฑ์: 25 x MTR
- Length: 25 m
 - Insulation Material: PTFE
 - Maximum Operating Temperature: +250 °C
 - Thermocouple Type: K
 - Screened/Unscreened: Unscreened
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2



2363858 25 m

RS PRO TYPE K THERMOCOUPLE WIRE, 25M, SCREENED, PVC

- ขนาดบรรจุภัณฑ์: 25 x MTR
- Length: 25 m
 - Insulation Material: PVC
 - Maximum Operating Temperature: +105 °C
 - Thermocouple Type: K
 - Screened/Unscreened: Screened
 - Core Strands: 7/0.2 mm
 - Cable Shape: Multicore
 - Number of Strands: 2



2363864 25 m

RS PRO TYPE T THERMOCOUPLE WIRE, 25M, UNSCREENED, PVC

- ขนาดบรรจุภัณฑ์: 25 x MTR
- Length: 25 m
 - Insulation Material: PVC
 - Maximum Operating Temperature: +105 °C
 - Thermocouple Type: T
 - Screened/Unscreened: Unscreened
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2



2363870 25 m

RS PRO TYPE T THERMOCOUPLE WIRE, 10M, UNSCREENED, GLASS

- ขนาดบรรจุภัณฑ์: 10 x MTR
- Length: 10 m
 - Insulation Material: Glass Fibre
 - Maximum Operating Temperature: +400 °C
 - Thermocouple Type: T
 - Screened/Unscreened: Unscreened
 - Core Strands: 1/0.315 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2



2363909 10 m

RS PRO TYPE J THERMOCOUPLE WIRE, 100M, UNSCREENED, PVC

- ขนาดบรรจุภัณฑ์: 100 x MTR
- Length: 100 m
 - Insulation Material: PVC
 - Maximum Operating Temperature: +105 °C
 - Thermocouple Type: J
 - Screened/Unscreened: Unscreened
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2



2363915 100 m

RS PRO TYPE J THERMOCOUPLE WIRE, 25M, SCREENED, PVC

- ขนาดบรรจุภัณฑ์: 25 x MTR
- Length: 25 m
 - Insulation Material: PVC
 - Maximum Operating Temperature: +105 °C
 - Thermocouple Type: J
 - Screened/Unscreened: Screened
 - Core Strands: 7/0.2 mm
 - Cable Shape: Multicore
 - Number of Strands: 2



2363921 25 m

RS PRO TYPE J THERMOCOUPLE WIRE, 25M, SCREENED, GLASS FIBRE

- ขนาดบรรจุภัณฑ์: 25 x MTR
- Length: 25 m
 - Insulation Material: Glass Fibre
 - Maximum Operating Temperature: +400 °C
 - Thermocouple Type: J
 - Screened/Unscreened: Screened
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2



2363937 25 m

RS PRO TYPE K THERMOCOUPLE WIRE, 25M, SCREENED, PVC

- ขนาดบรรจุภัณฑ์: 25 x MTR
- Length: 25 m
 - Insulation Material: PVC
 - Maximum Operating Temperature: +105 °C
 - Thermocouple Type: K
 - Screened/Unscreened: Screened
 - Core Strands: 7/0.2 mm
 - Cable Shape: Multicore
 - Number of Strands: 2



2363959 25 m

RS PRO TYPE RTD RESISTANCE THERMOMETER DETECTOR (RTD)

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 25 m
 - Insulation Material: PVC
 - Maximum Operating Temperature: +105 °C
 - Thermocouple Type: RTD
 - Screened/Unscreened: Screened
 - Core Strands: 7/0.2 mm
 - Cable Shape: Multicore
 - Number of Strands: 4


2904954 25 m

RS PRO TYPE K THERMOCOUPLE WIRE, 25M, UNSCREENED, PTFE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 25 m
 - Insulation Material: PTFE
 - Maximum Operating Temperature: +250 °C
 - Thermocouple Type: K
 - Screened/Unscreened: Unscreened
 - Core Strands: 1/0.2 mm
 - Cable Shape: Twin Twisted
 - Number of Strands: 2


3630389 25 m

RS PRO TYPE T THERMOCOUPLE WIRE, 25M, UNSCREENED, PTFE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 25 m
 - Insulation Material: PTFE
 - Maximum Operating Temperature: +250 °C
 - Thermocouple Type: T
 - Screened/Unscreened: Unscreened
 - Core Strands: 1/0.2 mm
 - Cable Shape: Single Core
 - Number of Strands: 2


3630402 25 m

RS PRO TYPE T THERMOCOUPLE WIRE, 25M, UNSCREENED, PTFE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 25 m
 - Insulation Material: PTFE
 - Maximum Operating Temperature: +250 °C
 - Thermocouple Type: T
 - Screened/Unscreened: Screened
 - Core Strands: 1/0.315 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2


3630418 25 m

RS PRO TYPE RTD THERMOCOUPLE & EXTENSION WIRE, 25M, SCREENED,

- ขนาดบรรจุภัณฑ์: **25 x MTR**
- Length: 25 m
 - Insulation Material: PVC
 - Thermocouple Type: RTD
 - Maximum Operating Temperature: +80 °C
 - Screened/Unscreened: Screened
 - Core Strands: 7/0.2 mm
 - Cable Shape: Multicore
 - Number of Strands: 7


4071466 25 m

RS PRO TYPE K THERMOCOUPLE & EXTENSION WIRE, 20M,

- ขนาดบรรจุภัณฑ์: **20 x MTR**
- Length: 20 m
 - Insulation Material: Fibreglass
 - Maximum Operating Temperature: +600 °C
 - Thermocouple Type: K
 - Screened/Unscreened: Unscreened
 - Cable Shape: Single Core
 - Number of Strands: 2


4071545 20 m

RS PRO TYPE J THERMOCOUPLE & EXTENSION WIRE, 20M,

- ขนาดบรรจุภัณฑ์: **20 x MTR**
- Length: 20 m
 - Insulation Material: Glass Fibre
 - Maximum Operating Temperature: +600 °C
 - Thermocouple Type: J
 - Screened/Unscreened: Unscreened
 - Cable Shape: Single Core
 - Number of Strands: 2


4071551 20 m

RS PRO TYPE K THERMOCOUPLE & EXTENSION WIRE, 20M,

- ขนาดบรรจุภัณฑ์: **20 x MTR**
- Length: 20 m
 - Insulation Material: Fibreglass
 - Maximum Operating Temperature: +800 °C
 - Thermocouple Type: K
 - Screened/Unscreened: Unscreened
 - Cable Shape: Single Core
 - Number of Strands: 2


4071567 20 m

RS PRO TYPE K THERMOCOUPLE & EXTENSION WIRE, 20M,

- ขนาดบรรจุภัณฑ์: **20 x MTR**
- Length: 20 m
 - Insulation Material: Ceramic Fibre
 - Maximum Operating Temperature: +1200 °C
 - Thermocouple Type: K
 - Screened/Unscreened: Unscreened
 - Cable Shape: Single Core
 - Number of Strands: 2


4071573 20 m

RS PRO TYPE T THERMOCOUPLE WIRE, 25M, UNSCREENED, SILICONE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 25 m
 - Insulation Material: Silicone Rubber
 - Maximum Operating Temperature: +260 °C
 - Thermocouple Type: T
 - Screened/Unscreened: Unscreened
 - Core Strands: 7/0.2 mm
 - Cable Shape: Multicore
 - Number of Strands: 2


4554236 25 m

RS PRO TYPE RTD RESISTANCE THERMOMETER DETECTOR (RTD)

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 25 m
 - Insulation Material: PTFE
 - Thermocouple Type: RTD
 - Maximum Operating Temperature: +200 °C
 - Screened/Unscreened: Unscreened
 - Core Strands: 7/0.2 mm
 - Cable Shape: Multicore
 - Number of Strands: 4


4554242 25 m

RS PRO TYPE J THERMOCOUPLE WIRE, 25M, UNSCREENED, PTFE

- ขนาดบรรจุภัณฑ์: **25 x MTR**
- Length: 25 m
 - Insulation Material: PTFE
 - Maximum Operating Temperature: +250 °C
 - Thermocouple Type: J
 - Screened/Unscreened: Unscreened
 - Core Strands: 7/0.2 mm
 - Cable Shape: Multicore
 - Number of Strands: 2


4554258 25 m

RS PRO TYPE RTD RESISTANCE THERMOMETER DETECTOR (RTD)

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 10 m
 - Insulation Material: PVC
 - Thermocouple Type: RTD
 - Maximum Operating Temperature: +105 °C
 - Screened/Unscreened: Screened
 - Core Strands: 7/0.2 mm
 - Cable Shape: Multicore
 - Number of Strands: 4


4929753 10 m

RS PRO RESISTANCE THERMOMETER DETECTOR (RTD) WIRE, 10M,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 10 m
 - Insulation Material: PTFE
 - Maximum Operating Temperature: +260 °C
 - Screened/Unscreened: Screened
 - Core Strands: 7/0.2 mm
 - Cable Shape: Multicore
 - Number of Strands: 4


4929775 10 m

RS PRO TYPE K THERMOCOUPLE WIRE, 100M, UNSCREENED, PVC

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Length: 100 m
 - Insulation Material: PVC
 - Maximum Operating Temperature: +105 °C
 - Thermocouple Type: K
 - Screened/Unscreened: Unscreened
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2


6117889 100 m

RS PRO TYPE K THERMOCOUPLE WIRE, 100M, SCREENED, PVC

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Length: 100 m
 - Insulation Material: PVC
 - Thermocouple Type: K
 - Maximum Operating Temperature: +105 °C
 - Screened/Unscreened: Screened
 - Core Strands: 7/0.2 mm
 - Cable Shape: Multicore
 - Number of Strands: 2


6117895 100 m

RS PRO TYPE R/S THERMOCOUPLE WIRE, 25M, UNSCREENED, PVC

- ขนาดบรรจุภัณฑ์: **25 x MTR**
- Length: 25 m
 - Insulation Material: PVC
 - Maximum Operating Temperature: +105 °C
 - Thermocouple Type: R/S
 - Screened/Unscreened: Unscreened
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2



6117902 25 m

RS PRO TYPE J THERMOCOUPLE WIRE, 100M, SCREENED, PVC


- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Length: 100 m
 - Insulation Material: PVC
 - Maximum Operating Temperature: +105 °C
 - Thermocouple Type: J
 - Screened/Unscreened: Screened
 - Core Strands: 7/0.2 mm
 - Cable Shape: Multicore
 - Number of Strands: 2



6117918 100 m

RS PRO TYPE K THERMOCOUPLE WIRE, 100M, SCREENED, PVC

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Length: 100 m
 - Insulation Material: PVC
 - Maximum Operating Temperature: +105 °C
 - Thermocouple Type: K
 - Screened/Unscreened: Screened
 - Core Strands: 7/0.2 mm
 - Cable Shape: Multicore
 - Number of Strands: 2



6117924 100 m

RS PRO TYPE K THERMOCOUPLE WIRE, 100M, UNSCREENED, PFA

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Length: 100 m
 - Insulation Material: PFA
 - Maximum Operating Temperature: +260 °C
 - Thermocouple Type: K
 - Screened/Unscreened: Unscreened
 - Core Strands: 7/0.2 mm
 - Cable Shape: Multicore
 - Number of Strands: 2



6117946 100 m

RS PRO TYPE T THERMOCOUPLE WIRE, 100M, UNSCREENED, PFA

- ขนาดบรรจุภัณฑ์: **100 x MTR**
- Length: 100 m
 - Insulation Material: PFA
 - Maximum Operating Temperature: +260 °C
 - Thermocouple Type: T
 - Screened/Unscreened: Unscreened
 - Core Strands: 1/0.2 mm
 - Cable Shape: Multicore
 - Number of Strands: 2



6117952 100 m

RS PRO TYPE K THERMOCOUPLE WIRE, 50M, UNSCREENED, PFA

- ขนาดบรรจุภัณฑ์: **50 x MTR**
- Length: 50 m
 - Insulation Material: PFA
 - Maximum Operating Temperature: +260 °C
 - Thermocouple Type: K
 - Screened/Unscreened: Unscreened
 - Core Strands: 1/0.2 mm
 - Cable Shape: Multicore
 - Number of Strands: 2



6117968 50 m

RS PRO TYPE T THERMOCOUPLE WIRE, 50M, UNSCREENED, PFA


- ขนาดบรรจุภัณฑ์: **50 x MTR**
- Length: 50 m
 - Insulation Material: PFA
 - Maximum Operating Temperature: +260 °C
 - Thermocouple Type: T
 - Screened/Unscreened: Unscreened
 - Core Strands: 1/0.2 mm
 - Cable Shape: Twisted
 - Number of Strands: 2



6117974 50 m

RS PRO TYPE K THERMOCOUPLE WIRE, 25M, UNSCREENED, PFA

- ขนาดบรรจุภัณฑ์: **25 x MTR**
- Length: 25 m
 - Insulation Material: PFA
 - Maximum Operating Temperature: +260 °C
 - Thermocouple Type: K
 - Screened/Unscreened: Unscreened
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2



6117980 25 m

RS PRO TYPE N THERMOCOUPLE WIRE, 25M, UNSCREENED, PFA

- ขนาดบรรจุภัณฑ์: **25 x MTR**
- Length: 25 m
 - Insulation Material: PFA
 - Maximum Operating Temperature: +260 °C
 - Thermocouple Type: N
 - Screened/Unscreened: Unscreened
 - Core Strands: 1/0.2 mm
 - Cable Shape: Twisted
 - Number of Strands: 2



6117996 25 m

RS PRO TYPE K THERMOCOUPLE WIRE, 50M, UNSCREENED, PFA

- ขนาดบรรจุภัณฑ์: **50 x MTR**
- Length: 50 m
 - Insulation Material: PFA
 - Maximum Operating Temperature: +260 °C
 - Thermocouple Type: K
 - Screened/Unscreened: Unscreened
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2



6118006 50 m

RS PRO TYPE K THERMOCOUPLE WIRE, 25M, UNSCREENED, PFA

- ขนาดบรรจุภัณฑ์: **25 x MTR**
- Length: 25 m
 - Insulation Material: PFA
 - Maximum Operating Temperature: +260 °C
 - Thermocouple Type: K
 - Screened/Unscreened: Unscreened
 - Core Strands: 1/0.315 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2



6118012 25 m

RS PRO TYPE T THERMOCOUPLE WIRE, 50M, UNSCREENED, PFA

- ขนาดบรรจุภัณฑ์: **50 x MTR**
- Length: 50 m
 - Insulation Material: PFA
 - Maximum Operating Temperature: +260 °C
 - Thermocouple Type: T
 - Screened/Unscreened: Unscreened
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2



6118040 50 m

RS PRO TYPE J THERMOCOUPLE WIRE, 50M, UNSCREENED, PFA

- ขนาดบรรจุภัณฑ์: **50 x MTR**
- Length: 50 m
 - Insulation Material: PFA
 - Maximum Operating Temperature: +260 °C
 - Thermocouple Type: J
 - Screened/Unscreened: Unscreened
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2



6118056 50 m

RS PRO TYPE N THERMOCOUPLE WIRE, 25M, UNSCREENED, PFA

- ขนาดบรรจุภัณฑ์: **25 x MTR**
- Length: 25 m
 - Insulation Material: PFA
 - Maximum Operating Temperature: +260 °C
 - Thermocouple Type: N
 - Screened/Unscreened: Unscreened
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2



6118062 25 m

RS PRO RESISTANCE THERMOMETER DETECTOR (RTD) WIRE, 10M,

- ขนาดบรรจุภัณฑ์: **10 x MTR**
- Length: 10 m
 - Insulation Material: PFA
 - Maximum Operating Temperature: +260 °C
 - Screened/Unscreened: Screened
 - Core Strands: 7/0.2 mm
 - Cable Shape: Multicore
 - Number of Strands: 4



6118078 10 m

RS PRO RESISTANCE THERMOMETER DETECTOR (RTD) WIRE, 25M,

- ขนาดบรรจุภัณฑ์: **25 x MTR**
- Length: 25 m
 - Insulation Material: PFA
 - Maximum Operating Temperature: +260 °C
 - Screened/Unscreened: Screened
 - Core Strands: 7/0.2 mm
 - Cable Shape: Multicore
 - Number of Strands: 4



6118090 25 m

RS PRO RESISTANCE THERMOMETER DETECTOR (RTD) WIRE, 25M,

ขนาดบรรจุภัณฑ์: 25 x MTR

- Length: 25 m
- Insulation Material: PFA
- Maximum Operating Temperature: +260 °C
- Screened/Unscreened: Screened
- Core Strands: 7/0.2 mm
- Cable Shape: Multicore
- Number of Strands: 6



6118107 25 m

RS PRO RESISTANCE THERMOMETER DETECTOR (RTD) WIRE, 50M,

ขนาดบรรจุภัณฑ์: 50 x MTR

- Length: 50 m
- Insulation Material: PVC
- Maximum Operating Temperature: +105 °C
- Screened/Unscreened: Screened
- Core Strands: 7/0.2 mm
- Cable Shape: Multicore
- Number of Strands: 4




6118129 50 m

RS PRO TYPE T THERMOCOUPLE WIRE, 25M, SCREENED, PVC

ขนาดบรรจุภัณฑ์: 25 x MTR

- Length: 25 m
- Insulation Material: PVC
- Maximum Operating Temperature: +105 °C
- Thermocouple Type: T
- Screened/Unscreened: Screened
- Core Strands: 7/0.2 mm
- Cable Shape: Twisted
- Number of Strands: 2



7621140 25 m

RS PRO TYPE T THERMOCOUPLE WIRE, 100M, UNSCREENED, PVC

ขนาดบรรจุภัณฑ์: 100 x MTR

- Length: 100 m
- Insulation Material: PVC
- Maximum Operating Temperature: +105 °C
- Thermocouple Type: T
- Screened/Unscreened: Unscreened
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2



7621146 100 m

RS PRO TYPE K THERMOCOUPLE WIRE, 100M, UNSCREENED, PVC

ขนาดบรรจุภัณฑ์: 100 x MTR

- Length: 100 m
- Insulation Material: PVC
- Maximum Operating Temperature: +105 °C
- Thermocouple Type: K
- Screened/Unscreened: Unscreened
- Core Strands: 13/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2



7621152 100 m

RS PRO TYPE K EXTENSION CABLE, 2M, PVC INSULATION, +220°C MAX,

ขนาดบรรจุภัณฑ์: 1 x EA

- Length: 2 m
- Insulation Material: PVC
- Thermocouple Type: K
- Maximum Operating Temperature: +220 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Multicore
- Number of Strands: 2
- Standards Met: IEC, RoHS Compliant



7686581 2 m

RS PRO TYPE K EXTENSION CABLE, 5M, PVC INSULATION, +220°C MAX,

ขนาดบรรจุภัณฑ์: 1 x EA

- Length: 5 m
- Insulation Material: PVC
- Thermocouple Type: K
- Maximum Operating Temperature: +220 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Multicore
- Number of Strands: 2
- Standards Met: IEC, RoHS Compliant



7686585 5 m

RS PRO TYPE J EXTENSION CABLE, 5M, PVC INSULATION, +220°C MAX,

ขนาดบรรจุภัณฑ์: 1 x EA

- Length: 5 m
- Insulation Material: PVC
- Thermocouple Type: J
- Maximum Operating Temperature: +220 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Multicore
- Number of Strands: 2
- Standards Met: IEC, RoHS Compliant



7686591 5 m

RS PRO TYPE K EXTENSION CABLE, 10M, PVC INSULATION, +220°C MAX,

ขนาดบรรจุภัณฑ์: 1 x EA

- Length: 10 m
- Insulation Material: PVC
- Thermocouple Type: K
- Maximum Operating Temperature: +220 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Multicore
- Number of Strands: 2
- Standards Met: IEC, RoHS Compliant



7686594 10 m

RS PRO TYPE J EXTENSION CABLE, 2M, PVC INSULATION, +220°C MAX,

ขนาดบรรจุภัณฑ์: 1 x EA

- Length: 2 m
- Insulation Material: PVC
- Thermocouple Type: J
- Maximum Operating Temperature: +220 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Multicore
- Number of Strands: 2
- Standards Met: IEC, RoHS Compliant



7686597 2 m

RS PRO TYPE J EXTENSION CABLE, 10M, PVC INSULATION, +220°C MAX,

ขนาดบรรจุภัณฑ์: 1 x EA

- Length: 10 m
- Insulation Material: PVC
- Thermocouple Type: J
- Maximum Operating Temperature: +220 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Multicore
- Number of Strands: 2
- Standards Met: IEC, RoHS Compliant



7686601 10 m

RS PRO TYPE T EXTENSION CABLE, 2M, PVC INSULATION, +220°C MAX,

ขนาดบรรจุภัณฑ์: 1 x EA

- Length: 2 m
- Insulation Material: PVC
- Thermocouple Type: T
- Maximum Operating Temperature: +220 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Multicore
- Number of Strands: 2
- Standards Met: IEC, RoHS Compliant



7686604 2 m

RS PRO TYPE T EXTENSION CABLE, 5M, PVC INSULATION, +220°C MAX,

ขนาดบรรจุภัณฑ์: 1 x EA

- Length: 5 m
- Insulation Material: PVC
- Thermocouple Type: T
- Maximum Operating Temperature: +220 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Multicore
- Number of Strands: 2
- Standards Met: IEC, RoHS Compliant



7686608 5 m

RS PRO TYPE N EXTENSION CABLE, 2M, PVC INSULATION, +220°C MAX,

ขนาดบรรจุภัณฑ์: 1 x EA

- Length: 2 m
- Insulation Material: PVC
- Thermocouple Type: N
- Maximum Operating Temperature: +220 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Multicore
- Number of Strands: 2
- Standards Met: IEC, RoHS Compliant



7686610 2 m

RS PRO TYPE N EXTENSION CABLE, 5M, PVC INSULATION, +220°C MAX,

ขนาดบรรจุภัณฑ์: 1 x EA

- Length: 5 m
- Insulation Material: PVC
- Thermocouple Type: N
- Maximum Operating Temperature: +220 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Multicore
- Number of Strands: 2
- Standards Met: IEC, RoHS Compliant



7686614 5 m

RS PRO TYPE T EXTENSION CABLE, 10M, PVC INSULATION, +220°C MAX,

ขนาดบรรจุภัณฑ์: 1 x EA

- Length: 10 m
- Insulation Material: PVC
- Thermocouple Type: T
- Maximum Operating Temperature: +220 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Multicore
- Number of Strands: 2
- Standards Met: IEC, RoHS Compliant



7686617 10 m

RS PRO TYPE K EXTENSION CABLE, 2M, PVC INSULATION, +220°C MAX,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 2 m
 - Insulation Material: PVC
 - Thermocouple Type: K
 - Maximum Operating Temperature: +220 °C
 - Core Strands: 7/0.2 mm
 - Cable Shape: Multicore
 - Number of Strands: 2
 - Standards Met: IEC, RoHS Compliant



7686626 2 m

RS PRO TYPE J EXTENSION CABLE, 5M, PVC INSULATION, +220°C MAX,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 5 m
 - Insulation Material: PVC
 - Thermocouple Type: J
 - Maximum Operating Temperature: +220 °C
 - Core Strands: 7/0.2 mm
 - Cable Shape: Multicore
 - Number of Strands: 2
 - Standards Met: IEC, RoHS Compliant



7686636 5 m

RS PRO TYPE T EXTENSION CABLE, 2M, PVC INSULATION, +220°C MAX,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 2 m
 - Insulation Material: PVC
 - Thermocouple Type: T
 - Maximum Operating Temperature: +220 °C
 - Core Strands: 7/0.2 mm
 - Cable Shape: Multicore
 - Number of Strands: 2
 - Standards Met: IEC, RoHS Compliant



7686648 2 m

RS PRO TYPE K EXTENSION CABLE, 5M, GLASS FIBRE INSULATION,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 5 m
 - Insulation Material: Glass Fibre
 - Thermocouple Type: K
 - Core Strands: 7/0.2 mm
 - Number of Strands: 2



7799671 5 m

RS PRO TYPE K EXTENSION CABLE, 2M, GLASS FIBRE INSULATION,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 2 m
 - Insulation Material: Glass Fibre
 - Thermocouple Type: K
 - Core Strands: 7/0.2 mm
 - Number of Strands: 2



7799678 2 m

RS PRO TYPE K EXTENSION CABLE, 2M, PFA INSULATION, 7/0.2MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 2 m
 - Insulation Material: PFA
 - Thermocouple Type: K
 - Core Strands: 7/0.2 mm
 - Number of Strands: 2



7799697 2 m

RS PRO TYPE K EXTENSION CABLE, 5M, PFA INSULATION, 7/0.2MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 5 m
 - Insulation Material: PFA
 - Thermocouple Type: K
 - Core Strands: 7/0.2 mm
 - Number of Strands: 2



7799707 5 m

RS PRO TYPE K EXTENSION CABLE, 2M, PVC INSULATION, 7/0.2MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 2 m
 - Insulation Material: PVC
 - Thermocouple Type: K
 - Core Strands: 7/0.2 mm
 - Number of Strands: 2



7799713 2 m

RS PRO TYPE K EXTENSION CABLE, 5M, PVC INSULATION, 7/0.2MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 5 m
 - Insulation Material: PVC
 - Thermocouple Type: K
 - Core Strands: 7/0.2 mm
 - Number of Strands: 2



7799716 5 m

RS PRO TYPE J THERMOCOUPLE WIRE, 25M, UNSCREENED, PVC


- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 25 m
 - Insulation Material: PVC
 - Maximum Operating Temperature: +105 °C
 - Thermocouple Type: J
 - Screened/Unscreened: Unscreened
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2



8139995 25 m

RS PRO TYPE J THERMOCOUPLE WIRE, 100M, UNSCREENED, PVC


- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 100 m
 - Insulation Material: PVC
 - Maximum Operating Temperature: +105 °C
 - Thermocouple Type: J
 - Screened/Unscreened: Unscreened
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2



8140005 100 m

RS PRO TYPE J THERMOCOUPLE WIRE, 100M, SCREENED, PVC MYLAR


- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 100 m
 - Insulation Material: PVC Mylar
 - Maximum Operating Temperature: +105 °C
 - Thermocouple Type: J
 - Screened/Unscreened: Screened
 - Core Strands: 7/0.2 mm
 - Cable Shape: Twisted
 - Number of Strands: 2



8140011 100 m

RS PRO TYPE K THERMOCOUPLE WIRE, 25M, PVC INSULATION, +105°C


- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 25 m
 - Insulation Material: PVC
 - Thermocouple Type: K
 - Maximum Operating Temperature: +105 °C
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: ANSI



8140018 25 m

RS PRO TYPE K THERMOCOUPLE WIRE, 200M, PVC INSULATION,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 200 m
 - Insulation Material: PVC
 - Thermocouple Type: K
 - Maximum Operating Temperature: +105 °C
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: ANSI



8140020 200 m

RS PRO TYPE K THERMOCOUPLE WIRE, 25M, PFA INSULATION, +260°C


- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 25 m
 - Insulation Material: PFA
 - Thermocouple Type: K
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 1/0.3 mm
 - Cable Shape: Twisted
 - Number of Strands: 2
 - Standards Met: ANSI



8140024 25 m

RS PRO TYPE K THERMOCOUPLE WIRE, 100M, PVC INSULATION,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 100 m
 - Insulation Material: PVC
 - Thermocouple Type: K
 - Maximum Operating Temperature: +105 °C
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: ANSI



8140027 100 m

RS PRO TYPE K THERMOCOUPLE WIRE, 25M, PFA INSULATION, +260°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 25 m
 - Insulation Material: PFA
 - Thermocouple Type: K
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 1/0.2 mm
 - Cable Shape: Twisted
 - Number of Strands: 2
 - Standards Met: ANSI



8140030 25 m

RS PRO TYPE K THERMOCOUPLE WIRE, 50M, PFA INSULATION, +260°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 50 m
 - Insulation Material: PFA
 - Thermocouple Type: K
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 1/0.3 mm
 - Cable Shape: Twisted
 - Number of Strands: 2
 - Standards Met: ANSI



8140033 50 m

RS PRO TYPE K THERMOCOUPLE WIRE, 100M, PFA INSULATION,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 100 m
 - Insulation Material: PFA
 - Thermocouple Type: K
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 1/0.3 mm
 - Cable Shape: Twisted
 - Number of Strands: 2
 - Standards Met: ANSI



8140036 100 m

RS PRO TYPE K THERMOCOUPLE WIRE, 100M, PFA INSULATION,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 100 m
 - Insulation Material: PFA
 - Thermocouple Type: K
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 1/0.2 mm
 - Cable Shape: Twisted
 - Number of Strands: 2
 - Standards Met: ANSI



8140042 100 m

RS PRO TYPE K THERMOCOUPLE WIRE, 25M, PFA INSULATION, +260°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 25 m
 - Insulation Material: PFA
 - Thermocouple Type: K
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 7/0.2 mm
 - Cable Shape: Twisted
 - Number of Strands: 2
 - Standards Met: ANSI



8140046 25 m

RS PRO TYPE K THERMOCOUPLE WIRE, 50M, PFA INSULATION, +260°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 50 m
 - Insulation Material: PFA
 - Thermocouple Type: K
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 1/0.2 mm
 - Cable Shape: Twisted
 - Number of Strands: 2
 - Standards Met: ANSI



8140049 50 m

RS PRO TYPE K THERMOCOUPLE WIRE, 25M, GLASS FIBRE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 25 m
 - Insulation Material: Glass Fibre
 - Thermocouple Type: K
 - Maximum Operating Temperature: +350 °C
 - Core Strands: 1/0.315 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: ANSI



8140052 25 m

RS PRO TYPE K THERMOCOUPLE WIRE, 50M, PFA INSULATION, +260°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 50 m
 - Insulation Material: PFA
 - Thermocouple Type: K
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 7/0.2 mm
 - Cable Shape: Twisted
 - Number of Strands: 2
 - Standards Met: ANSI



8140055 50 m

RS PRO TYPE K THERMOCOUPLE WIRE, 50M, GLASS FIBRE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 50 m
 - Insulation Material: Glass Fibre
 - Thermocouple Type: K
 - Maximum Operating Temperature: +350 °C
 - Core Strands: 1/0.315 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: ANSI



8140061 50 m

RS PRO TYPE K THERMOCOUPLE WIRE, 100M, GLASS FIBRE


- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 100 m
 - Insulation Material: Glass Fibre
 - Thermocouple Type: K
 - Maximum Operating Temperature: +350 °C
 - Core Strands: 1/0.315 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: ANSI



8140064 100 m

RS PRO TYPE K THERMOCOUPLE WIRE, 25M, SCREENED, PVC MYLAR


- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 25 m
 - Insulation Material: PVC Mylar
 - Maximum Operating Temperature: +105 °C
 - Thermocouple Type: K
 - Screened/Unscreened: Screened
 - Core Strands: 7/0.2 mm
 - Cable Shape: Twisted
 - Number of Strands: 2



8140068 25 m

RS PRO TYPE K THERMOCOUPLE WIRE, 200M, SCREENED, PVC MYLAR

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 200 m
 - Insulation Material: PVC Mylar
 - Maximum Operating Temperature: +105 °C
 - Thermocouple Type: K
 - Screened/Unscreened: Screened
 - Core Strands: 7/0.2 mm
 - Cable Shape: Twisted
 - Number of Strands: 2



8140070 200 m

RS PRO TYPE T THERMOCOUPLE WIRE, 25M, PVC INSULATION, +105°C


- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 25 m
 - Insulation Material: PVC
 - Thermocouple Type: T
 - Maximum Operating Temperature: +105 °C
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: ANSI



8140074 25 m

RS PRO TYPE T THERMOCOUPLE WIRE, 25M, PFA INSULATION, +260°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 25 m
 - Insulation Material: PFA
 - Thermocouple Type: T
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 1/0.3 mm
 - Cable Shape: Twisted
 - Number of Strands: 2
 - Standards Met: ANSI



8140080 25 m

RS PRO TYPE T THERMOCOUPLE WIRE, 100M, PVC INSULATION,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 100 m
 - Insulation Material: PVC
 - Thermocouple Type: T
 - Maximum Operating Temperature: +105 °C
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: ANSI



8140083 100 m

RS PRO TYPE T THERMOCOUPLE WIRE, 200M, PVC INSULATION,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 200 m
 - Insulation Material: PVC
 - Maximum Operating Temperature: +105 °C
 - Thermocouple Type: T
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: ANSI



8140086 200 m


RS PRO TYPE T THERMOCOUPLE WIRE, 100M, PFA INSULATION,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 100 m
 - Insulation Material: PFA
 - Thermocouple Type: T
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 1/0.3 mm
 - Cable Shape: Twisted
 - Number of Strands: 2
 - Standards Met: ANSI


8140092 100 m

RS PRO TYPE T THERMOCOUPLE WIRE, 25M, PFA INSULATION, +260°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 25 m
 - Insulation Material: PFA
 - Thermocouple Type: T
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 1/0.2 mm
 - Cable Shape: Twisted
 - Number of Strands: 2
 - Standards Met: ANSI


8140096 25 m

RS PRO TYPE T THERMOCOUPLE WIRE, 50M, PFA INSULATION, +260°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 50 m
 - Insulation Material: PFA
 - Thermocouple Type: T
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 1/0.3 mm
 - Cable Shape: Twisted
 - Number of Strands: 2
 - Standards Met: ANSI


8140099 50 m

RS PRO TYPE K THERMOCOUPLE WIRE, 25M, PVC INSULATION, +105°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 25 m
 - Insulation Material: PVC
 - Thermocouple Type: K
 - Maximum Operating Temperature: +105 °C
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: ANSI


8140103 25 m


RS PRO TYPE T THERMOCOUPLE WIRE, 50M, PFA INSULATION, +260°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 50 m
 - Insulation Material: PFA
 - Thermocouple Type: T
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 1/0.2 mm
 - Cable Shape: Twisted
 - Number of Strands: 2
 - Standards Met: ANSI


8140106 50 m

RS PRO TYPE T THERMOCOUPLE WIRE, 100M, PFA INSULATION,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 100 m
 - Insulation Material: PFA
 - Thermocouple Type: T
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 1/0.2 mm
 - Cable Shape: Twisted
 - Number of Strands: 2
 - Standards Met: ANSI


8140109 100 m

RS PRO TYPE K THERMOCOUPLE WIRE, 200M, PVC INSULATION,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 200 m
 - Insulation Material: PVC
 - Thermocouple Type: K
 - Maximum Operating Temperature: +105 °C
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: ANSI


8140115 200 m

RS PRO TYPE K THERMOCOUPLE WIRE, 25M, PVC INSULATION, +260°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 25 m
 - Insulation Material: PVC
 - Thermocouple Type: K
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: ANSI


8140119 25 m


RS PRO TYPE K THERMOCOUPLE WIRE, 100M, PVC INSULATION,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 100 m
 - Insulation Material: PVC
 - Thermocouple Type: K
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: ANSI


8140121 100 m

RS PRO TYPE K THERMOCOUPLE WIRE, 50M, PVC INSULATION, +260°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 50 m
 - Insulation Material: PVC
 - Thermocouple Type: K
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: ANSI


8140128 50 m

RS PRO TYPE J THERMOCOUPLE WIRE, 25M, PVC INSULATION, +105°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 25 m
 - Insulation Material: PVC
 - Thermocouple Type: J
 - Maximum Operating Temperature: +105 °C
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: IEC


8275592 25 m

RS PRO TYPE J THERMOCOUPLE WIRE, 50M, PVC INSULATION, +105°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 50 m
 - Insulation Material: PVC
 - Thermocouple Type: J
 - Maximum Operating Temperature: +105 °C
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: IEC


8275596 50 m

RS PRO TYPE K THERMOCOUPLE WIRE, 50M, PVC INSULATION, +105°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 50 m
 - Insulation Material: PVC
 - Thermocouple Type: K
 - Maximum Operating Temperature: +105 °C
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: IEC


8275603 50 m

RS PRO TYPE J THERMOCOUPLE WIRE, 200M, PVC INSULATION,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 200 m
 - Insulation Material: PVC
 - Thermocouple Type: J
 - Maximum Operating Temperature: +105 °C
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: IEC


8275606 200 m

RS PRO TYPE K THERMOCOUPLE WIRE, 10M, PVC INSULATION, +105°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 10 m
 - Insulation Material: PVC
 - Thermocouple Type: K
 - Maximum Operating Temperature: +105 °C
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: IEC


8275609 10 m

RS PRO TYPE K THERMOCOUPLE WIRE, 200M, PVC INSULATION,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 200 m
 - Insulation Material: PVC
 - Thermocouple Type: K
 - Maximum Operating Temperature: +105 °C
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: IEC


8275612 200 m

RS PRO TYPE K THERMOCOUPLE WIRE, 10M, PVC INSULATION, +105°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 10 m
 - Insulation Material: PVC
 - Thermocouple Type: K
 - Maximum Operating Temperature: +105 °C
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: IEC



8275615 10 m

RS PRO TYPE K THERMOCOUPLE WIRE, 10M, PVC INSULATION, +105°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 10 m
 - Insulation Material: PVC
 - Thermocouple Type: K
 - Maximum Operating Temperature: +105 °C
 - Core Strands: 13/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: IEC



8275621 10 m

RS PRO TYPE K THERMOCOUPLE WIRE, 25M, PVC INSULATION, +105°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 25 m
 - Insulation Material: PVC
 - Thermocouple Type: K
 - Maximum Operating Temperature: +105 °C
 - Core Strands: 13/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: IEC



8275625 25 m

RS PRO TYPE K THERMOCOUPLE WIRE, 200M, PVC INSULATION, +105°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 200 m
 - Insulation Material: PVC
 - Thermocouple Type: K
 - Maximum Operating Temperature: +105 °C
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: IEC



8275628 200 m

RS PRO TYPE N THERMOCOUPLE WIRE, 50M, PVC INSULATION, +105°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 50 m
 - Insulation Material: PVC
 - Thermocouple Type: N
 - Maximum Operating Temperature: +105 °C
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: IEC



8275631 50 m

RS PRO TYPE N THERMOCOUPLE WIRE, 25M, PVC INSULATION, +105°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 25 m
 - Insulation Material: PVC
 - Thermocouple Type: N
 - Maximum Operating Temperature: +105 °C
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: IEC



8275637 25 m

RS PRO TYPE N THERMOCOUPLE WIRE, 100M, PVC INSULATION, +105°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 100 m
 - Insulation Material: PVC
 - Thermocouple Type: N
 - Maximum Operating Temperature: +105 °C
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: IEC



8275640 100 m

RS PRO TYPE R/S THERMOCOUPLE WIRE, 25M, PVC INSULATION, +105°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 25 m
 - Insulation Material: PVC
 - Thermocouple Type: R/S
 - Maximum Operating Temperature: +105 °C
 - Core Strands: 13/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: IEC



8275643 25 m

RS PRO TYPE R/S THERMOCOUPLE WIRE, 50M, PVC INSULATION, +105°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 50 m
 - Insulation Material: PVC
 - Thermocouple Type: R/S
 - Maximum Operating Temperature: +105 °C
 - Core Strands: 13/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: IEC



8275647 50 m

RS PRO TYPE T THERMOCOUPLE WIRE, 50M, PVC INSULATION, +105°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 50 m
 - Insulation Material: PVC
 - Thermocouple Type: T
 - Maximum Operating Temperature: +105 °C
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: IEC



8275653 50 m

RS PRO TYPE R/S THERMOCOUPLE WIRE, 10M, PVC INSULATION, +105°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 10 m
 - Insulation Material: PVC
 - Thermocouple Type: R/S
 - Maximum Operating Temperature: +105 °C
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: IEC



8275656 10 m

RS PRO TYPE R/S THERMOCOUPLE WIRE, 50M, PVC INSULATION, +105°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 50 m
 - Insulation Material: PVC
 - Thermocouple Type: R/S
 - Maximum Operating Temperature: +105 °C
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: IEC



8275659 50 m

RS PRO TYPE J THERMOCOUPLE WIRE, 10M, SCREENED, PVC


- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 10 m
 - Insulation Material: PVC
 - Maximum Operating Temperature: +105 °C
 - Thermocouple Type: J
 - Screened/Unscreened: Screened
 - Core Strands: 7/0.2 mm
 - Cable Shape: Twisted
 - Number of Strands: 2



8275665 10 m

RS PRO TYPE K THERMOCOUPLE WIRE, 50M, SCREENED, PVC


- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 50 m
 - Insulation Material: PVC
 - Maximum Operating Temperature: +105 °C
 - Thermocouple Type: K
 - Screened/Unscreened: Screened
 - Core Strands: 7/0.2 mm
 - Cable Shape: Twisted
 - Number of Strands: 2



8275671 50 m

RS PRO TYPE K THERMOCOUPLE WIRE, 200M, SCREENED, PVC


- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 200 m
 - Insulation Material: PVC
 - Maximum Operating Temperature: +105 °C
 - Thermocouple Type: K
 - Screened/Unscreened: Screened
 - Core Strands: 7/0.2 mm
 - Cable Shape: Twisted
 - Number of Strands: 2



8275675 200 m

RS PRO TYPE K THERMOCOUPLE WIRE, 10M, PVC INSULATION, +105°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 10 m
 - Insulation Material: PVC
 - Thermocouple Type: K
 - Maximum Operating Temperature: +105 °C
 - Core Strands: 7/0.2 mm
 - Cable Shape: Twisted
 - Number of Strands: 2
 - Standards Met: IEC




8275678 10 m

RS PRO TYPE K THERMOCOUPLE WIRE, 10M, PVC INSULATION, +105°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 10 m
 - Insulation Material: PVC
 - Thermocouple Type: K
 - Maximum Operating Temperature: +105 °C
 - Core Strands: 7/0.2 mm
 - Cable Shape: Twisted
 - Number of Strands: 2
 - Standards Met: IEC

**8275690** 10 m**RS PRO TYPE K THERMOCOUPLE WIRE, 50M, PVC INSULATION, +105°C**

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 50 m
 - Insulation Material: PVC
 - Thermocouple Type: K
 - Maximum Operating Temperature: +105 °C
 - Core Strands: 7/0.2 mm
 - Cable Shape: Twisted
 - Number of Strands: 2
 - Standards Met: IEC

**8275693** 50 m**RS PRO TYPE K THERMOCOUPLE WIRE, 50M, GLASS FIBRE**

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 50 m
 - Insulation Material: Glass Fibre
 - Thermocouple Type: K
 - Maximum Operating Temperature: +350 °C
 - Core Strands: 1/0.315 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: BS

**8275700** 50 m**RS PRO TYPE K THERMOCOUPLE WIRE, 25M, GLASS FIBRE**

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 25 m
 - Insulation Material: Glass Fibre
 - Thermocouple Type: K
 - Maximum Operating Temperature: +350 °C
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: BS

**8275704** 25 m**RS PRO TYPE K THERMOCOUPLE WIRE, 25M, GLASS FIBRE**

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 25 m
 - Insulation Material: Glass Fibre
 - Thermocouple Type: K
 - Maximum Operating Temperature: +350 °C
 - Core Strands: 1/0.315 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: BS

**8275707** 25 m**RS PRO TYPE K THERMOCOUPLE WIRE, 100M, PFA INSULATION, +260°C**


- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 100 m
 - Insulation Material: PFA
 - Thermocouple Type: K
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: IEC

**8275710** 100 m**RS PRO TYPE K THERMOCOUPLE WIRE, 50M, GLASS FIBRE**

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 50 m
 - Insulation Material: Glass Fibre
 - Thermocouple Type: K
 - Maximum Operating Temperature: +350 °C
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: BS

**8275713** 50 m**RS PRO TYPE K THERMOCOUPLE WIRE, 10M, PFA INSULATION, +260°C**

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 10 m
 - Insulation Material: PFA
 - Thermocouple Type: K
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: IEC

**8275716** 10 m**RS PRO TYPE K THERMOCOUPLE WIRE, 50M, PFA INSULATION, +260°C**


- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 50 m
 - Insulation Material: PFA
 - Thermocouple Type: K
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 1/0.315 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: IEC

**8275722** 50 m**RS PRO TYPE K THERMOCOUPLE WIRE, 100M, PFA INSULATION, +260°C**

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 100 m
 - Insulation Material: PFA
 - Thermocouple Type: K
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 1/0.315 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: IEC

**8275726** 100 m**RS PRO TYPE K THERMOCOUPLE WIRE, 10M, PFA INSULATION, +260°C**

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 10 m
 - Insulation Material: PFA
 - Thermocouple Type: K
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 1/0.315 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: IEC

**8275729** 10 m**RS PRO TYPE J THERMOCOUPLE WIRE, 10M, PFA INSULATION, +260°C**

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 10 m
 - Insulation Material: PFA
 - Thermocouple Type: J
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: IEC

**8275732** 10 m**RS PRO TYPE T THERMOCOUPLE WIRE, 10M, PFA INSULATION, +260°C**

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 10 m
 - Insulation Material: PFA
 - Thermocouple Type: T
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: IEC

**8275735** 10 m**RS PRO TYPE T THERMOCOUPLE WIRE, 100M, PFA INSULATION, +260°C**

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 100 m
 - Insulation Material: PFA
 - Thermocouple Type: T
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: IEC

**8275738** 100 m**RS PRO TYPE J THERMOCOUPLE WIRE, 100M, PFA INSULATION, +260°C**

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 100 m
 - Insulation Material: PFA
 - Thermocouple Type: J
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: IEC

**8275741** 100 m**RS PRO TYPE N THERMOCOUPLE WIRE, 10M, PFA INSULATION, +260°C**

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 10 m
 - Insulation Material: PFA
 - Thermocouple Type: N
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: IEC

**8275744** 10 m

RS PRO TYPE K THERMOCOUPLE WIRE, 25M, PFA INSULATION, +260°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 25 m
 - Insulation Material: PFA
 - Thermocouple Type: K
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 7/0.2 mm
 - Cable Shape: Twin Twisted
 - Number of Strands: 2
 - Standards Met: IEC



8275750 25 m

RS PRO TYPE K THERMOCOUPLE WIRE, 10M, PFA INSULATION, +260°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 10 m
 - Insulation Material: PFA
 - Thermocouple Type: K
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 7/0.2 mm
 - Cable Shape: Twin Twisted
 - Number of Strands: 2
 - Standards Met: IEC



8275757 10 m

RS PRO TYPE N THERMOCOUPLE WIRE, 10M, PFA INSULATION, +260°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 10 m
 - Insulation Material: PFA
 - Thermocouple Type: N
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 1/0.2 mm
 - Cable Shape: Twin Twisted
 - Number of Strands: 2
 - Standards Met: IEC



8275760 10 m

RS PRO TYPE K THERMOCOUPLE WIRE, 10M, PFA INSULATION, +260°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 10 m
 - Insulation Material: PFA
 - Thermocouple Type: K
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 1/0.2 mm
 - Cable Shape: Twin Twisted
 - Number of Strands: 2
 - Standards Met: IEC



8275763 10 m

RS PRO TYPE K THERMOCOUPLE WIRE, 25M, PFA INSULATION, +260°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 25 m
 - Insulation Material: PFA
 - Thermocouple Type: K
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 1/0.2 mm
 - Cable Shape: Twin Twisted
 - Number of Strands: 2
 - Standards Met: IEC



8275766 25 m

RS PRO TYPE K THERMOCOUPLE WIRE, 10M, PTFE INSULATION, +260°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 10 m
 - Insulation Material: PTFE
 - Thermocouple Type: K
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: IEC



8275776 10 m

RS PRO TYPE T THERMOCOUPLE WIRE, 10M, PFA INSULATION, +260°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 10 m
 - Insulation Material: PFA
 - Thermocouple Type: T
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 1/0.2 mm
 - Cable Shape: Twin Twisted
 - Number of Strands: 2
 - Standards Met: IEC



8275779 10 m

RS PRO TYPE T THERMOCOUPLE WIRE, 50M, PTFE INSULATION, +260°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 50 m
 - Insulation Material: PTFE
 - Thermocouple Type: T
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: IEC



8275782 50 m

RS PRO TYPE K THERMOCOUPLE WIRE, 50M, PTFE INSULATION, +260°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 50 m
 - Insulation Material: PTFE
 - Thermocouple Type: K
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: IEC



8275785 50 m

RS PRO TYPE T THERMOCOUPLE WIRE, 10M, PTFE INSULATION, +260°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 10 m
 - Insulation Material: PTFE
 - Thermocouple Type: T
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 1/0.315 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: IEC



8275791 10 m

RS PRO TYPE T THERMOCOUPLE WIRE, 50M, PTFE INSULATION, +260°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 50 m
 - Insulation Material: PTFE
 - Thermocouple Type: T
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 1/0.315 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: IEC



8275794 50 m

RS PRO TYPE J THERMOCOUPLE WIRE, 10M, PTFE INSULATION, +260°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 10 m
 - Insulation Material: PTFE
 - Thermocouple Type: J
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: IEC



8275798 10 m

RS PRO TYPE K THERMOCOUPLE WIRE, 10M, PTFE INSULATION, +260°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 10 m
 - Insulation Material: PTFE
 - Thermocouple Type: K
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 1/0.2 mm
 - Cable Shape: Twin Twisted
 - Number of Strands: 2
 - Standards Met: IEC



8275801 10 m

RS PRO TYPE K THERMOCOUPLE WIRE, 50M, PTFE INSULATION, +260°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 50 m
 - Insulation Material: PTFE
 - Thermocouple Type: K
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 1/0.2 mm
 - Cable Shape: Twin Twisted
 - Number of Strands: 2
 - Standards Met: IEC



8275805 50 m

RS PRO TYPE J THERMOCOUPLE WIRE, 50M, PTFE INSULATION, +260°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 50 m
 - Insulation Material: PTFE
 - Thermocouple Type: J
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: IEC



8275808 50 m

RS PRO TYPE K THERMOCOUPLE WIRE, 100M, PTFE INSULATION, +260°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 100 m
 - Insulation Material: PTFE
 - Thermocouple Type: K
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 1/0.2 mm
 - Cable Shape: Twin Twisted
 - Number of Strands: 2
 - Standards Met: IEC



8275814 100 m

RS PRO TYPE T THERMOCOUPLE WIRE, 10M, PTFE INSULATION, +260°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 10 m
 - Insulation Material: PTFE
 - Thermocouple Type: T
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 1/0.2 mm
 - Cable Shape: Twin Twisted
 - Number of Strands: 2
 - Standards Met: IEC


8275817 10 m

RS PRO TYPE T THERMOCOUPLE WIRE, 100M, PTFE INSULATION,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 100 m
 - Insulation Material: PTFE
 - Thermocouple Type: T
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 1/0.2 mm
 - Cable Shape: Twin Twisted
 - Number of Strands: 2
 - Standards Met: IEC


8275820 100 m

RS PRO TYPE RTD RESISTANCE THERMOMETER DETECTOR (RTD)

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 10 m
 - Insulation Material: PFA
 - Thermocouple Type: RTD
 - Maximum Operating Temperature: +200 °C
 - Core Strands: 7/0.2 mm
 - Cable Shape: Twisted
 - Number of Strands: 4


8275823 10 m

RS PRO TYPE RTD RESISTANCE THERMOMETER DETECTOR (RTD)

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 50 m
 - Insulation Material: PFA
 - Thermocouple Type: RTD
 - Maximum Operating Temperature: +260 °C
 - Screened/Unscreened: Screened
 - Core Strands: 7/0.2 mm
 - Cable Shape: Twisted
 - Number of Strands: 4


8275827 50 m

RS PRO TYPE K THERMOCOUPLE WIRE, 50M, GLASS FIBRE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 50 m
 - Insulation Material: Glass Fibre
 - Thermocouple Type: K
 - Maximum Operating Temperature: +350 °C
 - Core Strands: 1/0.315 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: IEC


8275833 50 m

RS PRO TYPE RTD RESISTANCE THERMOMETER DETECTOR (RTD)

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 100 m
 - Insulation Material: PFA
 - Thermocouple Type: RTD
 - Maximum Operating Temperature: +260 °C
 - Screened/Unscreened: Screened
 - Core Strands: 7/0.2 mm
 - Cable Shape: Twisted
 - Number of Strands: 4


8275836 100 m

RS PRO TYPE K THERMOCOUPLE WIRE, 100M, GLASS FIBRE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 100 m
 - Insulation Material: Glass Fibre
 - Thermocouple Type: K
 - Maximum Operating Temperature: +350 °C
 - Core Strands: 1/0.315 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: IEC


8275842 100 m

RS PRO TYPE K THERMOCOUPLE WIRE, 200M, GLASS FIBRE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 200 m
 - Insulation Material: Glass Fibre
 - Thermocouple Type: K
 - Maximum Operating Temperature: +350 °C
 - Core Strands: 1/0.315 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: IEC


8275845 200 m

RS PRO TYPE T THERMOCOUPLE WIRE, 25M, GLASS FIBRE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 25 m
 - Insulation Material: Glass Fibre
 - Thermocouple Type: T
 - Maximum Operating Temperature: +350 °C
 - Core Strands: 1/0.315 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: IEC


8275849 25 m

RS PRO TYPE J THERMOCOUPLE WIRE, 10M, GLASS FIBRE INSULATION,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 10 m
 - Insulation Material: Glass Fibre
 - Thermocouple Type: J
 - Maximum Operating Temperature: +350 °C
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: IEC


8275851 10 m

RS PRO TYPE K THERMOCOUPLE WIRE, 100M, GLASS FIBRE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 100 m
 - Insulation Material: Glass Fibre
 - Thermocouple Type: K
 - Maximum Operating Temperature: +350 °C
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: IEC


8275861 100 m

RS PRO TYPE K THERMOCOUPLE WIRE, 50M, GLASS FIBRE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Insulation Material: Glass Fibre
 - Length: 50 m
 - Maximum Operating Temperature: +350 °C
 - Thermocouple Type: K
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: IEC


8275867 Glass Fibre

RS PRO TYPE J THERMOCOUPLE WIRE, 10M, GLASS FIBRE INSULATION,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 10 m
 - Insulation Material: Glass Fibre
 - Thermocouple Type: J
 - Maximum Operating Temperature: +350 °C
 - Core Strands: 7/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: IEC


8275870 10 m

RS PRO TYPE K THERMOCOUPLE WIRE, 25M, PVC INSULATION, +105°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 25 m
 - Insulation Material: PVC
 - Thermocouple Type: K
 - Maximum Operating Temperature: +105 °C
 - Core Strands: 13/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: IEC


8275883 25 m

RS PRO TYPE K THERMOCOUPLE WIRE, 25M, SILICONE RUBBER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 25 m
 - Insulation Material: Silicone Rubber
 - Thermocouple Type: K
 - Maximum Operating Temperature: +200 °C
 - Core Strands: 7/0.2 mm
 - Cable Shape: Twisted
 - Number of Strands: 2
 - Standards Met: IEC


8275906 25 m

RS PRO TYPE J THERMOCOUPLE WIRE, 25M, PFA INSULATION, +260°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 25 m
 - Insulation Material: PFA
 - Thermocouple Type: J
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 1/0.2 mm
 - Cable Shape: Twisted
 - Number of Strands: 2
 - Standards Met: IEC


8275918 25 m

RS PRO TYPE K THERMOCOUPLE WIRE, 25M, PFA INSULATION, +260°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 25 m
 - Insulation Material: PFA
 - Thermocouple Type: K
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 1/0.3 mm
 - Cable Shape: Twisted
 - Number of Strands: 2
 - Standards Met: IEC



8275924 25 m

RS PRO TYPE K THERMOCOUPLE WIRE, 50M, PFA INSULATION, +260°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 50 m
 - Insulation Material: PFA
 - Thermocouple Type: K
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 1/0.3 mm
 - Cable Shape: Twisted
 - Number of Strands: 2
 - Standards Met: IEC



8275928 50 m

RS PRO TYPE K THERMOCOUPLE WIRE, 100M, PFA INSULATION, +260°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 100 m
 - Insulation Material: PFA
 - Thermocouple Type: K
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 1/0.3 mm
 - Cable Shape: Twisted
 - Number of Strands: 2
 - Standards Met: IEC



8275937 100 m

RS PRO TYPE T THERMOCOUPLE WIRE, 25M, PFA INSULATION, +260°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 25 m
 - Insulation Material: PFA
 - Thermocouple Type: T
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 1/0.3 mm
 - Cable Shape: Twisted
 - Number of Strands: 2
 - Standards Met: IEC



8275943 25 m

RS PRO TYPE T THERMOCOUPLE WIRE, 50M, PFA INSULATION, +260°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 50 m
 - Insulation Material: PFA
 - Thermocouple Type: T
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 1/0.508 mm
 - Cable Shape: Twisted
 - Number of Strands: 2
 - Standards Met: IEC



8275959 50 m

RS PRO TYPE K THERMOCOUPLE WIRE, 50M, PFA INSULATION, +260°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 50 m
 - Insulation Material: PFA
 - Thermocouple Type: K
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 1/0.508 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: IEC



8275962 50 m

RS PRO TYPE T THERMOCOUPLE WIRE, 25M, PFA INSULATION, +260°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 25 m
 - Insulation Material: PFA
 - Thermocouple Type: T
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 1/0.315 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: IEC



8275971 25 m

RS PRO TYPE T THERMOCOUPLE WIRE, 50M, PFA INSULATION, +260°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 50 m
 - Insulation Material: PFA
 - Thermocouple Type: T
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 1/0.315 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: IEC



8275974 50 m

RS PRO TYPE J THERMOCOUPLE WIRE, 50M, PTFE INSULATION, +260°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 50 m
 - Insulation Material: PTFE
 - Thermocouple Type: J
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 1/0.2 mm
 - Cable Shape: Twisted
 - Number of Strands: 2
 - Standards Met: IEC



8275984 50 m

RS PRO TYPE T THERMOCOUPLE WIRE, 50M, PFA INSULATION, +260°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 50 m
 - Insulation Material: PFA
 - Thermocouple Type: T
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 1/0.5 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: IEC



8275987 50 m

RS PRO TYPE K THERMOCOUPLE WIRE, 25M, PTFE INSULATION, +260°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 25 m
 - Insulation Material: PTFE
 - Thermocouple Type: K
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 1/0.315 mm
 - Cable Shape: Twisted
 - Number of Strands: 2
 - Standards Met: IEC



8276000 25 m

RS PRO TYPE J THERMOCOUPLE WIRE, 25M, PTFE INSULATION, +260°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 25 m
 - Insulation Material: PTFE
 - Thermocouple Type: J
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 7/0.2 mm
 - Cable Shape: Twisted
 - Number of Strands: 2
 - Standards Met: IEC



8276006 25 m

RS PRO TYPE K THERMOCOUPLE WIRE, 50M, PTFE INSULATION, +260°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 50 m
 - Insulation Material: PTFE
 - Thermocouple Type: K
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 1/0.315 mm
 - Cable Shape: Twisted
 - Number of Strands: 2
 - Standards Met: IEC



8276019 50 m

RS PRO TYPE K THERMOCOUPLE WIRE, 25M, PTFE INSULATION, +260°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 25 m
 - Insulation Material: PTFE
 - Thermocouple Type: K
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 1/0.315 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: IEC



8276038 25 m

RS PRO TYPE T THERMOCOUPLE WIRE, 25M, PTFE INSULATION, +260°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 25 m
 - Insulation Material: PTFE
 - Thermocouple Type: T
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 1/0.508 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: IEC



8276040 25 m

RS PRO TYPE K THERMOCOUPLE WIRE, 50M, PTFE INSULATION, +260°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 50 m
 - Insulation Material: PTFE
 - Thermocouple Type: K
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 1/0.315 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: IEC



8276047 50 m

RS PRO TYPE K THERMOCOUPLE WIRE, 2M, POLYURETHANE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 2 m
 - Insulation Material: Polyurethane
 - Thermocouple Type: K
 - Maximum Operating Temperature: +125 °C
 - Core Strands: 10/0.12
 - Cable Shape: Curly
 - Number of Strands: 2
 - Standards Met: IEC



8276056 2 m

RS PRO TYPE J THERMOCOUPLE WIRE, 25M, GLASS FIBRE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 25 m
 - Insulation Material: Glass Fibre
 - Thermocouple Type: J
 - Maximum Operating Temperature: +350 °C
 - Core Strands: 1/0.315 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: IEC



8276062 25 m

RS PRO TYPE K THERMOCOUPLE WIRE, 25M, GLASS FIBRE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 25 m
 - Insulation Material: Glass Fibre
 - Thermocouple Type: K
 - Maximum Operating Temperature: +350 °C
 - Core Strands: 1/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: IEC



8276066 25 m

RS PRO TYPE J THERMOCOUPLE WIRE, 25M, GLASS FIBRE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 25 m
 - Insulation Material: Glass Fibre
 - Thermocouple Type: J
 - Maximum Operating Temperature: +350 °C
 - Core Strands: 1/0.2 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: IEC



8276069 25 m

RS PRO TYPE K THERMOCOUPLE WIRE, 25M, GLASS FIBRE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 25 m
 - Insulation Material: Glass Fibre
 - Thermocouple Type: K
 - Maximum Operating Temperature: +350 °C
 - Core Strands: 1/0.508 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: IEC



8276075 25 m

RS PRO TYPE N THERMOCOUPLE WIRE, 25M, GLASS FIBRE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 25 m
 - Insulation Material: Glass Fibre
 - Thermocouple Type: N
 - Maximum Operating Temperature: +350 °C
 - Core Strands: 1/0.315 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: IEC



8276081 25 m

THERMOCOUPLE, WELDED TIP, J, GLASS FIBRE INSULATED, -

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: J
 - Probe Diameter: 1/0.3 mm
 - Probe Length: 2 m
 - Maximum Temperature Sensed: +400 °C
 - Termination Type: Cable
 - Cable Length: 2 m
 - Standards Met: BS



150004 J

RS PRO TYPE J THERMOCOUPLE 200MM LENGTH, 6MM DIAMETER, -

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: J
 - Probe Diameter: 6 mm
 - Probe Length: 200 mm
 - Maximum Temperature Sensed: +350 °C
 - Termination Type: Cable
 - Standards Met: BS
 - Minimum Temperature Sensed: -60 °C



150026 J

THERMOCOUPLE, WELDED TIP, K, GLASS FIBRE INSULATED

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1/0.3 mm
 - Probe Length: 2 m
 - Maximum Temperature Sensed: +400 °C
 - Termination Type: Cable
 - Cable Length: 2 m
 - Standards Met: BS



151192 K

RS PRO TYPE T THERMOCOUPLE 100MM LENGTH, 1.6MM DIAMETER →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: T
 - Probe Diameter: 1.6 mm
 - Probe Length: 100 mm
 - Probe Material: Constantan, Copper
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Cable
 - Cable Length: 1.5 m
 - Standards Met: BS



151271 T

RS PRO TYPE K THERMOCOUPLE 300MM LENGTH, 3MM DIAMETER →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 3 mm
 - Probe Length: 300 mm
 - Probe Material: 316 Stainless Steel
 - Maximum Temperature Sensed: +1000 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: IEC



158604 K

THERMOCOUPLE, SELF ADHESIVE, K

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 7 mm
 - Probe Length: 1 m
 - Probe Material: Copper
 - Maximum Temperature Sensed: +200 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: BS



158626 K

RS PRO TYPE T THERMOCOUPLE 1M LENGTH, 1/0.2MM DIAMETER →

- ขนาดบรรจุภัณฑ์: 5 x EA
- Thermocouple Type: T
 - Probe Diameter: 1/0.2 mm
 - Probe Length: 1 m
 - Maximum Temperature Sensed: +200 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: BS



158907 T

THERMOCOUPLE, WELDED TIP, K, PTFE INSULATED

- ขนาดบรรจุภัณฑ์: 5 x EA
- Thermocouple Type: K
 - Probe Diameter: 1/0.2 mm
 - Probe Length: 1 m
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: BS



158913 K

RS PRO TYPE K THERMOCOUPLE 500MM LENGTH, 1.5MM DIAMETER →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1.5 mm
 - Probe Length: 500 mm
 - Probe Material: 316 Stainless Steel
 - Maximum Temperature Sensed: +800 °C
 - Termination Type: Cable
 - Cable Length: 100 mm
 - Standards Met: BS



159023 K

RS PRO TYPE K THERMOCOUPLE 1M LENGTH, 1.5MM DIAMETER → +800°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1.5 mm
 - Probe Length: 1 m
 - Probe Material: 316 Stainless Steel
 - Maximum Temperature Sensed: +800 °C
 - Termination Type: Cable
 - Cable Length: 100 mm
 - Standards Met: BS



159039 K

RS PRO TYPE K THERMOCOUPLE 500MM LENGTH, 1.5MM DIAMETER →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1.5 mm
 - Probe Length: 500 mm
 - Probe Material: Inconel 600
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 100 mm
 - Standards Met: BS



159095 K

RS PRO TYPE K THERMOCOUPLE 1M LENGTH, 1.5MM DIAMETER → +1100°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1.5 mm
 - Probe Length: 1 m
 - Probe Material: Inconel 600
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 100 mm
 - Standards Met: BS



159102 K

RS PRO TYPE K THERMOCOUPLE 500MM LENGTH, 3MM DIAMETER →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 3 mm
 - Probe Length: 500 mm
 - Probe Material: Inconel 600
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 100 mm
 - Standards Met: BS



159118 K

RS PRO TYPE K THERMOCOUPLE 1M LENGTH, 3MM DIAMETER → +1100°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 3 mm
 - Probe Length: 1 m
 - Probe Material: Inconel 600
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 100 mm
 - Standards Met: BS



159124 K

RS PRO TYPE K THERMOCOUPLE 2M LENGTH, 3MM DIAMETER → +1100°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 3 mm
 - Probe Length: 2 m
 - Probe Material: Inconel 600
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 100 mm
 - Standards Met: BS



159130 K

THERMOCOUPLE, BAYONET, J

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: J
 - Probe Diameter: 6 mm
 - Probe Length: 170 mm
 - Maximum Temperature Sensed: +350 °C
 - Probe Material: Stainless Steel
 - Termination Type: Cable
 - Cable Length: 2 m
 - Standards Met: RoHS Compliant



259328 J

THERMOCOUPLE, ADJ BAYONET, K

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 6 mm
 - Probe Length: 170 mm
 - Maximum Temperature Sensed: +400 °C
 - Probe Material: Stainless Steel
 - Termination Type: Cable
 - Cable Length: 2 m
 - Standards Met: RoHS Compliant



259334 K

RS PRO TYPE NTC TEMPERATURE SENSOR, -10°C → +60°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: NTC
 - Maximum Temperature Sensed: +60 °C
 - Minimum Temperature Sensed: -10 °C



813806 NTC

RS PRO TYPE NTC TEMPERATURE SENSOR, -10°C → +110°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: NTC
 - Maximum Temperature Sensed: +110 °C, +40 °C
 - Minimum Temperature Sensed: -10 °C



813828 NTC

RS PRO TYPE NTC TEMPERATURE SENSOR, -30°C → +70°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: NTC
 - Maximum Temperature Sensed: +70 °C
 - Minimum Temperature Sensed: -30 °C



813834 NTC

RS PRO TYPE NTC TEMPERATURE SENSOR, -30°C → +70°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: NTC
 - Maximum Temperature Sensed: +70 °C
 - Minimum Temperature Sensed: -30 °C



813840 NTC

RS PRO TYPE K THERMOCOUPLE 1M LENGTH, → +220°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Length: 1 m
 - Maximum Temperature Sensed: +220 °C
 - Termination Type: Miniature Plug
 - Cable Length: 1 m
 - Standards Met: IEC, RoHS Compliant



1104463 K

RS PRO TYPE K THERMOCOUPLE 2M LENGTH, → +220°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Length: 2 m
 - Maximum Temperature Sensed: +220 °C
 - Termination Type: Miniature Plug
 - Cable Length: 2 m
 - Standards Met: IEC, RoHS Compliant



1104468 K

TYPE T THERMOCOUPLE WITH 2M CABLE TIDY

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: T
 - Probe Length: 2 m
 - Maximum Temperature Sensed: +220 °C
 - Termination Type: Miniature Plug
 - Cable Length: 2 m
 - Standards Met: IEC, RoHS Compliant



1104470 T

RS PRO TYPE K THERMOCOUPLE → +220°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Maximum Temperature Sensed: +220 °C
 - Termination Type: Standard Plug
 - Cable Length: 2 m
 - Standards Met: ANSI, RoHS Compliant



1104472 K

RS PRO TYPE T THERMOCOUPLE → +220°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: T
 - Maximum Temperature Sensed: +220 °C
 - Termination Type: Miniature Plug
 - Cable Length: 2 m
 - Standards Met: ANSI, RoHS Compliant



1104474 T

TYPE K THERMOCOUPLE 2M WITH MINI PLUG

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 1/0.2 mm
 - Probe Length: 2 m
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Miniature Plug
 - Cable Length: 2 m
 - Standards Met: IEC



110482 K

TYPE K IEC 1/0.2MM THERMOCOUPLE+PLUG 5M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 1/0.2 mm
 - Probe Length: 5 m
 - Maximum Temperature Sensed: +260 °C
 - Termination Type: Miniature Plug
 - Cable Length: 5 m
 - Standards Met: IEC



1236306 K

RS PRO TYPE K THERMOCOUPLE 10M LENGTH, 1/0.2MM DIAMETER →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 1/0.2 mm
 - Probe Length: 10 m
 - Maximum Temperature Sensed: +260 °C
 - Termination Type: Miniature Plug
 - Cable Length: 10 m
 - Standards Met: IEC



1236307 K

RS PRO TYPE J THERMOCOUPLE 2M LENGTH, 1/0.2MM DIAMETER →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: J
 - Probe Diameter: 1/0.2 mm
 - Probe Length: 2 m
 - Maximum Temperature Sensed: +260 °C
 - Termination Type: Miniature Plug
 - Cable Length: 2 m
 - Standards Met: IEC



1236308 J

RS PRO TYPE J THERMOCOUPLE → +260°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: J
 - Maximum Temperature Sensed: +260 °C
 - Termination Type: Miniature Plug
 - Cable Length: 5 m
 - Standards Met: IEC



1236309 J

RS PRO TYPE J THERMOCOUPLE 10M LENGTH, 1/0.2MM DIAMETER →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: J
 - Probe Diameter: 1/0.2 mm
 - Probe Length: 10 m
 - Maximum Temperature Sensed: +260 °C
 - Termination Type: Miniature Plug
 - Cable Length: 10 m
 - Standards Met: IEC



1236310 J

RS PRO TYPE T THERMOCOUPLE 2M LENGTH, 1/0.2MM DIAMETER →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: T
 - Probe Diameter: 1/0.2 mm
 - Probe Length: 2 m
 - Maximum Temperature Sensed: +260 °C
 - Termination Type: Miniature Plug
 - Cable Length: 2 m
 - Standards Met: IEC



1236311 T

TYPE T IEC 1/0.2MM THERMOCOUPLE+PLUG 5M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: T
 - Probe Diameter: 1/0.2 mm
 - Probe Length: 5 m
 - Maximum Temperature Sensed: +260 °C
 - Termination Type: Miniature Plug
 - Cable Length: 5 m
 - Standards Met: IEC



1236312 T

RS PRO TYPE T THERMOCOUPLE 10M LENGTH, 1/0.2MM DIAMETER →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: T
 - Probe Diameter: 1/0.2 mm
 - Probe Length: 10 m
 - Maximum Temperature Sensed: +260 °C
 - Termination Type: Miniature Plug
 - Cable Length: 10 m
 - Standards Met: IEC



1236313 T

RS PRO TYPE K THERMOCOUPLE 1M LENGTH, 1/0.508MM DIAMETER →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 1/0.508 mm
 - Probe Length: 1 m
 - Maximum Temperature Sensed: +350 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: IEC



1236314 K

RS PRO TYPE K THERMOCOUPLE 1/0.508MM DIAMETER → +350°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 1/0.508 mm
 - Maximum Temperature Sensed: +350 °C
 - Termination Type: Cable
 - Cable Length: 10 m
 - Standards Met: IEC



1236315 K

RS PRO TYPE K THERMOCOUPLE 1/0.508MM DIAMETER → +350°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 1/0.508 mm
 - Maximum Temperature Sensed: +350 °C
 - Termination Type: Miniature Plug
 - Cable Length: 1 m
 - Standards Met: IEC



1236316 K

RS PRO TYPE K THERMOCOUPLE 10M LENGTH, → +350°C


- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Length: 10 m
 - Maximum Temperature Sensed: +350 °C
 - Termination Type: Miniature Plug
 - Cable Length: 10 m
 - Standards Met: IEC



1236317 K

RS PRO TYPE K THERMOCOUPLE 1/0.315MM DIAMETER → +250°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 1/0.315 mm
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Miniature Plug
 - Cable Length: 1 m
 - Standards Met: IEC



1236318 K

TYPE K IEC 0.315MM THERMOCOUPLE+PLUG 2M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 1/0.315 mm
 - Probe Length: 2 m
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Miniature Plug
 - Cable Length: 2 m
 - Standards Met: IEC



1236319 K

TYPE K IEC 7/0.2MM THERMOCOUPLE+PLUG 1M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 7/0.2 mm
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Miniature Plug
 - Cable Length: 1 m
 - Standards Met: IEC



1236320 K

RS PRO TYPE K THERMOCOUPLE 2M LENGTH, 7/0.2MM DIAMETER →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 7/0.2 mm
 - Probe Length: 2 m
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Miniature Plug
 - Cable Length: 2 m
 - Standards Met: IEC



1236321 K

RS PRO TYPE K THERMOCOUPLE 1M LENGTH, 1/0.2MM DIAMETER →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1/0.2 mm
 - Probe Length: 1 m
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Miniature Plug
 - Cable Length: 1 m
 - Standards Met: IEC



1236322 K

TYPE K IEC 1/0.2MM THERMOCOUPLE+PLUG 2M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1/0.2 mm
 - Probe Length: 2 m
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Miniature Plug
 - Cable Length: 2 m
 - Standards Met: IEC



1236323 K

RS PRO TYPE K THERMOCOUPLE 10M LENGTH, → +250°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Length: 10 m
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Miniature Plug
 - Cable Length: 10 m
 - Standards Met: IEC



1236324 K

TYPE J IEC 1/0.2MM THERMOCOUPLE+PLUG 1M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: J
 - Probe Length: 1 m
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Miniature Plug
 - Cable Length: 1 m
 - Standards Met: IEC



1236325 J

RS PRO TYPE J THERMOCOUPLE → +250°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: J
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Miniature Plug
 - Cable Length: 10 m
 - Standards Met: IEC



1236327 J

TYPE T IEC 0.315MM THERMOCOUPLE+PLUG 1M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: T
 - Probe Diameter: 1/0.3 mm
 - Probe Length: 1 m
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Miniature Plug
 - Cable Length: 1 m
 - Standards Met: IEC



1236328 T

TYPE T IEC 0.315MM THERMOCOUPLE+PLUG 2M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: T
 - Probe Diameter: 1/0.315 mm
 - Probe Length: 2 m
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Miniature Plug
 - Cable Length: 2 m
 - Standards Met: IEC



1236329 T

RS PRO TYPE T THERMOCOUPLE 7/0.2MM DIAMETER → +250°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: T
 - Probe Diameter: 7/0.2 mm
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Miniature Plug
 - Cable Length: 1 m
 - Standards Met: IEC



1236330 T

RS PRO TYPE T THERMOCOUPLE 7/0.2MM DIAMETER → +250°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: T
 - Probe Diameter: 7/0.2 mm
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Miniature Plug
 - Cable Length: 2 m
 - Standards Met: IEC



1236331 T

RS PRO TYPE T THERMOCOUPLE 1M LENGTH, → +250°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: T
 - Probe Length: 1 m
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Miniature Plug
 - Cable Length: 1 m
 - Standards Met: IEC



1236332 T

RS PRO TYPE T THERMOCOUPLE 2M LENGTH, 1/0.2MM DIAMETER →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: T
 - Probe Diameter: 1/0.2 mm
 - Probe Length: 2 m
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Miniature Plug
 - Cable Length: 2 m
 - Standards Met: IEC



1236333 T

RS PRO TYPE T THERMOCOUPLE 10M LENGTH, → +250°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: T
 - Probe Length: 10 m
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Miniature Plug
 - Cable Length: 10 m
 - Standards Met: IEC



1236334 T

RS PRO TYPE K THERMOCOUPLE 1IN DIAMETER → +250°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1 in
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Miniature Plug
 - Cable Length: 1 m
 - Standards Met: IEC



1314735 K

RS PRO TYPE K THERMOCOUPLE 2M LENGTH, 1/2IN DIAMETER → +250°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1/2 in
 - Probe Length: 2 m
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Miniature Plug
 - Cable Length: 2 m
 - Standards Met: IEC



1314736 K

RS PRO TYPE K THERMOCOUPLE 50MM LENGTH, → +100°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Length: 50 mm
 - Maximum Temperature Sensed: +100 °C
 - Termination Type: Miniature Plug
 - Cable Length: 1 m
 - Standards Met: IEC



1314737 K

**RS PRO TYPE K THERMOCOUPLE
40MM LENGTH, → +150°C**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Length: 40 mm
 - Maximum Temperature Sensed: +150 °C
 - Termination Type: Cable
 - Cable Length: 2 m
 - Standards Met: IEC


1314738 K
**RS PRO TYPE K THERMOCOUPLE 1M
LENGTH, 6.35MM DIAMETER → +200°C**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 6.35 mm
 - Probe Length: 1 m
 - Probe Material: Copper
 - Maximum Temperature Sensed: +200 °C
 - Termination Type: Miniature Plug
 - Cable Length: 1 m
 - Standards Met: IEC


1314739 K
**IEC TYPE K FINE WIRE
THERMOCOUPLE 2M**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 6.35 mm
 - Probe Length: 2 m
 - Probe Material: Copper
 - Maximum Temperature Sensed: +200 °C
 - Termination Type: Miniature Plug
 - Cable Length: 2 m
 - Standards Met: IEC


1314740 K
**RS PRO TYPE J THERMOCOUPLE 2M
LENGTH, 6.35MM DIAMETER → +200°C**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: J
 - Probe Diameter: 6.35 mm
 - Probe Length: 2 m
 - Probe Material: Copper
 - Maximum Temperature Sensed: +200 °C
 - Termination Type: Miniature Plug
 - Cable Length: 2 m
 - Standards Met: IEC


1314742 J
**RS PRO TYPE K THERMOCOUPLE 2M
LENGTH, 6MM DIAMETER → +350°C**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 6 mm
 - Probe Length: 2 m
 - Maximum Temperature Sensed: +350 °C
 - Termination Type: Standard Plug
 - Cable Length: 2 m
 - Standards Met: IEC


1314743 K
**RS PRO TYPE J THERMOCOUPLE 6MM
DIAMETER → +350°C**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: J
 - Probe Diameter: 6 mm
 - Maximum Temperature Sensed: +350 °C
 - Termination Type: Standard Plug
 - Cable Length: 2 m
 - Standards Met: IEC


1314744 J
**RS PRO TYPE K THERMOCOUPLE →
+350°C**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Maximum Temperature Sensed: +350 °C
 - Termination Type: Standard Plug
 - Cable Length: 2 m
 - Standards Met: IEC


1314745 K
LEAF THERMOCOUPLE TYPE K 2M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Length: 25 mm
 - Maximum Temperature Sensed: +350 °C
 - Termination Type: Standard Plug
 - Cable Length: 2 m
 - Standards Met: IEC


1314746 K
**RS PRO TYPE K THERMOCOUPLE
150MM LENGTH, 4.5MM DIAMETER →**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 4.5 mm
 - Probe Length: 150 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +350 °C
 - Termination Type: Standard Plug
 - Cable Length: 2 m
 - Standards Met: IEC


1314748 K
**THERMOCOUPLE HIGH TEMP
EXPOSED JUNCTION**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Length: 5 m
 - Maximum Temperature Sensed: +700 °C
 - Termination Type: Standard Plug
 - Cable Length: 5 m
 - Standards Met: ANSI


1314749 K
**RS PRO TYPE K THERMOCOUPLE 10M
LENGTH, → +700°C**


- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Length: 10 m
 - Maximum Temperature Sensed: +700 °C
 - Termination Type: Standard Plug
 - Cable Length: 10 m
 - Standards Met: ANSI


1314750 K
**RS PRO TYPE K THERMOCOUPLE 20M
LENGTH, → +700°C**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Length: 20 m
 - Maximum Temperature Sensed: +700 °C
 - Termination Type: Standard Plug
 - Cable Length: 20 m
 - Standards Met: ANSI


1314751 K
**RS PRO TYPE K THERMOCOUPLE 2M
LENGTH, → +260°C**


- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Length: 2 m
 - Maximum Temperature Sensed: +260 °C
 - Termination Type: Miniature Plug
 - Cable Length: 2 m
 - Standards Met: IEC


1314753 K
**THERMOCOUPLE MINI TYPE K IEC
PLUG 3M**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 1/0.3 mm
 - Probe Length: 3 m
 - Maximum Temperature Sensed: +260 °C
 - Termination Type: Miniature Plug
 - Cable Length: 3 m
 - Standards Met: IEC


1314754 K
**RS PRO TYPE K THERMOCOUPLE 3M
LENGTH, → +260°C**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Length: 3 m
 - Maximum Temperature Sensed: +260 °C
 - Termination Type: Miniature Plug
 - Cable Length: 3 m
 - Standards Met: IEC


1314757 K
**RS PRO TYPE K THERMOCOUPLE 1M
LENGTH, → +260°C**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Length: 1 m
 - Maximum Temperature Sensed: +260 °C
 - Termination Type: Miniature Plug
 - Cable Length: 1 m
 - Standards Met: ANSI


1314758 K

RS PRO TYPE K THERMOCOUPLE 2M LENGTH, → +260°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Length: 2 m
 - Maximum Temperature Sensed: +260 °C
 - Termination Type: Miniature Plug
 - Cable Length: 2 m
 - Standards Met: ANSI



1314759 K

RS PRO TYPE K THERMOCOUPLE 3M LENGTH, → +260°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Length: 3 m
 - Maximum Temperature Sensed: +260 °C
 - Termination Type: Miniature Plug
 - Cable Length: 3 m
 - Standards Met: ANSI



1314760 K

RS PRO TYPE K THERMOCOUPLE 6MM DIAMETER → +350°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 6 mm
 - Maximum Temperature Sensed: +350 °C
 - Termination Type: Standard Plug
 - Cable Length: 2 m
 - Standards Met: IEC



1314761 K

RS PRO TYPE K THERMOCOUPLE 3M LENGTH, 6MM DIAMETER → +350°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 6 mm
 - Probe Length: 3 m
 - Maximum Temperature Sensed: +350 °C
 - Termination Type: Standard Plug
 - Cable Length: 3 m
 - Standards Met: IEC



1314762 K

RS PRO TYPE J THERMOCOUPLE 2M LENGTH, 6MM DIAMETER → +350°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: J
 - Probe Diameter: 6 mm
 - Probe Length: 2 m
 - Maximum Temperature Sensed: +350 °C
 - Termination Type: Standard Plug
 - Cable Length: 2 m
 - Standards Met: IEC



1314763 J

RS PRO TYPE J THERMOCOUPLE 3M LENGTH, 6MM DIAMETER → +350°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: J
 - Probe Diameter: 6 mm
 - Probe Length: 3 m
 - Maximum Temperature Sensed: +350 °C
 - Termination Type: Standard Plug
 - Cable Length: 3 m
 - Standards Met: IEC



1314764 J

RS PRO TYPE K THERMOCOUPLE 250MM LENGTH, 6MM DIAMETER →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 6 mm
 - Probe Length: 250 mm
 - Maximum Temperature Sensed: +1100 °C
 - Probe Material: 310 Stainless Steel
 - Termination Type: Miniature Plug
 - Standards Met: IEC 584



1365850 K

RS PRO TYPE J THERMOCOUPLE 0.3MM DIAMETER → +250°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: J
 - Probe Diameter: 0.3 mm
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Miniature Plug
 - Cable Length: 1 m
 - Standards Met: RoHS Compliant



1365868 J

RS PRO TYPE J THERMOCOUPLE 2M LENGTH, 0.3MM DIAMETER → +250°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: J
 - Probe Diameter: 0.3 mm
 - Probe Length: 2 m
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Miniature Plug
 - Cable Length: 2 m
 - Standards Met: RoHS Compliant



1365870 J

RS PRO TYPE J THERMOCOUPLE 2M LENGTH, → +250°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: J
 - Probe Length: 2 m
 - Maximum Temperature Sensed: +250 °C
 - Probe Material: Teflon PFA
 - Termination Type: Miniature Plug
 - Cable Length: 2 m
 - Standards Met: EN 60584-3:2008, IEC 584-3



1365874 J

RS PRO TYPE J THERMOCOUPLE → +250°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: J
 - Maximum Temperature Sensed: +250 °C
 - Probe Material: Teflon PFA
 - Termination Type: Miniature Plug
 - Cable Length: 5 m
 - Standards Met: EN 60584-3:2008, IEC 584-3



1365877 J

RS PRO TYPE K THERMOCOUPLE 1M LENGTH, → +250°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Length: 1 m
 - Maximum Temperature Sensed: +250 °C
 - Probe Material: Teflon PFA
 - Termination Type: Miniature Plug
 - Cable Length: 1 m
 - Standards Met: EN 60584-3:2008, IEC 584-3



1365879 K

RS PRO TYPE K THERMOCOUPLE 2M LENGTH, → +250°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Length: 2 m
 - Maximum Temperature Sensed: +250 °C
 - Probe Material: Teflon PFA
 - Termination Type: Miniature Plug
 - Cable Length: 2 m
 - Standards Met: EN 60584-3:2008, IEC 584-3



1365880 K

TYPE K EXP. JUNCTION THERMOCOUPLE PFA 3M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Maximum Temperature Sensed: +250 °C
 - Probe Material: Teflon PFA
 - Termination Type: Miniature Plug
 - Cable Length: 3 m
 - Standards Met: EN 60584-3:2008, IEC 584-3



1365882 K

RS PRO TYPE K THERMOCOUPLE → +250°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Maximum Temperature Sensed: +250 °C
 - Probe Material: Teflon PFA
 - Termination Type: Miniature Plug
 - Cable Length: 5 m
 - Standards Met: EN 60584-3:2008, IEC 584-3



1365883 K

RS PRO TYPE K THERMOCOUPLE 10M LENGTH, → +250°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Length: 10 m
 - Maximum Temperature Sensed: +250 °C
 - Probe Material: Teflon PFA
 - Termination Type: Miniature Plug
 - Cable Length: 10 m
 - Standards Met: EN 60584-3:2008, IEC 584-3



1365884 K

TYPE K EXP. JUNCTION THERMOCOUPLE PFA 1M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Length: 1 m
 - Maximum Temperature Sensed: +250 °C
 - Probe Material: Teflon PFA
 - Termination Type: Miniature Plug
 - Cable Length: 1 m
 - Standards Met: EN 60584-3:2008, IEC 584-3



1365885 K

RS PRO TYPE K THERMOCOUPLE 2M LENGTH, → +250°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Length: 2 m
 - Maximum Temperature Sensed: +250 °C
 - Probe Material: Teflon PFA
 - Termination Type: Miniature Plug
 - Cable Length: 2 m
 - Standards Met: EN 60584-3:2008, IEC 584-3



1365886 K

TYPE K EXP. JUNCTION THERMOCOUPLE PFA 3M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Length: 3 m
 - Maximum Temperature Sensed: +250 °C
 - Probe Material: Teflon PFA
 - Termination Type: Miniature Plug
 - Cable Length: 3 m
 - Standards Met: EN 60584-3:2008, IEC 584-3



1365887 K

TYPE K EXP. JUNCTION THERMOCOUPLE PFA 5M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Length: 5 m
 - Maximum Temperature Sensed: +250 °C
 - Probe Material: Teflon PFA
 - Termination Type: Miniature Plug
 - Cable Length: 5 m
 - Standards Met: EN 60584-3:2008, IEC 584-3



1365888 K

RS PRO TYPE K THERMOCOUPLE 1M LENGTH, → +250°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Length: 1 m
 - Maximum Temperature Sensed: +250 °C
 - Probe Material: Teflon PFA
 - Termination Type: Miniature Plug
 - Cable Length: 1 m
 - Standards Met: EN 60584-3:2008, IEC 584-3



1365889 K

RS PRO TYPE K THERMOCOUPLE 2M LENGTH, → +250°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Length: 2 m
 - Maximum Temperature Sensed: +250 °C
 - Probe Material: Teflon PFA
 - Termination Type: Miniature Plug
 - Cable Length: 2 m
 - Standards Met: EN 60584-3:2008, IEC 584-3



1365890 K

RS PRO TYPE K THERMOCOUPLE 3M LENGTH, → +250°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Length: 3 m
 - Maximum Temperature Sensed: +250 °C
 - Probe Material: Teflon PFA
 - Termination Type: Miniature Plug
 - Cable Length: 3 m
 - Standards Met: EN 60584-3:2008, IEC 584-3



1365891 K

RS PRO TYPE K THERMOCOUPLE → +250°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Maximum Temperature Sensed: +250 °C
 - Probe Material: Teflon PFA
 - Termination Type: Miniature Plug
 - Cable Length: 5 m
 - Standards Met: EN 60584-3:2008, IEC 584-3



1365892 K

RS PRO TYPE K THERMOCOUPLE → +250°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Maximum Temperature Sensed: +250 °C
 - Probe Material: Teflon PFA
 - Termination Type: Miniature Plug
 - Cable Length: 10 m
 - Standards Met: EN 60584-3:2008, IEC 584-3



1365893 K

RS PRO TYPE K THERMOCOUPLE 150MM LENGTH, 2MM DIAMETER →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 2 mm
 - Probe Length: 150 mm
 - Maximum Temperature Sensed: +1100 °C
 - Probe Material: 310 Stainless Steel
 - Termination Type: Miniature Plug
 - Standards Met: IEC 584



1365894 K

RS PRO TYPE K THERMOCOUPLE 250MM LENGTH, 2MM DIAMETER →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 2 mm
 - Probe Length: 250 mm
 - Maximum Temperature Sensed: +1100 °C
 - Probe Material: 310 Stainless Steel
 - Termination Type: Miniature Plug
 - Standards Met: IEC 584



1365895 K

RS PRO TYPE K THERMOCOUPLE 150MM LENGTH, 2MM DIAMETER →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 2 mm
 - Probe Length: 150 mm
 - Maximum Temperature Sensed: +1100 °C
 - Probe Material: 310 Stainless Steel
 - Termination Type: Miniature Plug
 - Standards Met: IEC 584



1365896 K

RS PRO TYPE K THERMOCOUPLE 150MM LENGTH, 2MM DIAMETER →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 2 mm
 - Probe Length: 150 mm
 - Maximum Temperature Sensed: +1100 °C
 - Probe Material: 310 Stainless Steel
 - Termination Type: Miniature Plug
 - Standards Met: IEC 584



1365899 K

RS PRO TYPE K THERMOCOUPLE 250MM LENGTH, 2MM DIAMETER →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 2 mm
 - Probe Length: 250 mm
 - Maximum Temperature Sensed: +1100 °C
 - Probe Material: 310 Stainless Steel
 - Termination Type: Miniature Plug
 - Standards Met: IEC 584



1365900 K

RS PRO TYPE J THERMOCOUPLE 150MM LENGTH, 3MM DIAMETER →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: J
 - Probe Diameter: 3 mm
 - Probe Length: 150 mm
 - Maximum Temperature Sensed: +760 °C
 - Termination Type: Miniature Plug
 - Standards Met: IEC 584



1741665 J

RS PRO TYPE J THERMOCOUPLE 500MM LENGTH, 3MM DIAMETER →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: J
 - Probe Diameter: 3 mm
 - Probe Length: 500 mm
 - Maximum Temperature Sensed: +760 °C
 - Termination Type: Miniature Plug
 - Standards Met: IEC 584



1741667 J

RS PRO TYPE K THERMOCOUPLE → +250°C

ขนาดบรรจุภัณฑ์: 1 x EA

- Thermocouple Type: K
- Maximum Temperature Sensed: +250 °C
- Probe Material: Stainless Steel
- Termination Type: Miniature Plug
- Cable Length: 1 m
- Standards Met: IEC 584



1741669 K

RS PRO TYPE K THERMOCOUPLE → +250°C

ขนาดบรรจุภัณฑ์: 1 x EA

- Thermocouple Type: K
- Maximum Temperature Sensed: +250 °C
- Probe Material: Stainless Steel
- Termination Type: Miniature Plug
- Cable Length: 3 m
- Standards Met: IEC 584



1741670 K

RS PRO TYPE J THERMOCOUPLE 3M LENGTH, → +250°C

ขนาดบรรจุภัณฑ์: 1 x EA

- Thermocouple Type: J
- Probe Length: 3 m
- Maximum Temperature Sensed: +250 °C
- Probe Material: Stainless Steel
- Termination Type: Miniature Plug
- Cable Length: 3 m
- Standards Met: IEC 584



1741672 J

RS PRO TYPE K THERMOCOUPLE 200MM LENGTH, 6MM DIAMETER →

ขนาดบรรจุภัณฑ์: 1 x EA

- Thermocouple Type: K
- Probe Diameter: 6 mm
- Probe Length: 200 mm
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +1350 °C
- Termination Type: Connection Head



1747523 K

RS PRO TYPE K THERMOCOUPLE 400MM LENGTH, 6MM DIAMETER →

ขนาดบรรจุภัณฑ์: 1 x EA

- Thermocouple Type: K
- Probe Diameter: 6 mm
- Probe Length: 400 mm
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +1350 °C
- Termination Type: Connection Head



1747525 K

RS PRO TYPE K THERMOCOUPLE 300MM LENGTH, 6MM DIAMETER →

ขนาดบรรจุภัณฑ์: 1 x EA

- Thermocouple Type: K
- Probe Diameter: 6 mm
- Probe Length: 300 mm
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +1350 °C
- Termination Type: Connection Head



1747538 K

RS PRO TYPE K THERMOCOUPLE 400MM LENGTH, 6MM DIAMETER →

ขนาดบรรจุภัณฑ์: 1 x EA

- Thermocouple Type: K
- Probe Diameter: 6 mm
- Probe Length: 400 mm
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +1350 °C
- Termination Type: Connection Head



1747539 K

RS PRO TYPE K THERMOCOUPLE 150MM LENGTH, 6MM DIAMETER →

ขนาดบรรจุภัณฑ์: 1 x EA

- Thermocouple Type: K
- Probe Diameter: 6 mm
- Probe Length: 150 mm
- Maximum Temperature Sensed: +1100 °C
- Termination Type: Connection Head
- Cable Length: 150 mm



1780979 K

RS PRO TYPE K THERMOCOUPLE 250MM LENGTH, 6MM DIAMETER →

ขนาดบรรจุภัณฑ์: 1 x EA

- Thermocouple Type: K
- Probe Diameter: 6 mm
- Probe Length: 250 mm
- Maximum Temperature Sensed: +1100 °C
- Termination Type: Connection Head
- Cable Length: 250 mm



1780980 K

RS PRO TYPE K THERMOCOUPLE 500MM LENGTH, 6MM DIAMETER →

ขนาดบรรจุภัณฑ์: 1 x EA

- Thermocouple Type: K
- Probe Diameter: 6 mm
- Probe Length: 500 mm
- Maximum Temperature Sensed: +1100 °C
- Termination Type: Connection Head
- Cable Length: 500 mm



1780981 K

RS PRO TYPE K THERMOCOUPLE 4MM LENGTH, 4MM DIAMETER → +400°C

ขนาดบรรจุภัณฑ์: 1 x EA

- Thermocouple Type: K
- Probe Diameter: 4 mm
- Probe Length: 4 mm
- Probe Material: Nickel Aluminium, Nickel Chrome
- Maximum Temperature Sensed: +400 °C
- Termination Type: Bare Wire Tail
- Cable Length: 1 m



2000600 K

RS PRO TYPE K THERMOCOUPLE 4MM LENGTH, 3.2MM DIAMETER → +400°C

ขนาดบรรจุภัณฑ์: 1 x EA

- Thermocouple Type: K
- Probe Diameter: 3.2 mm
- Probe Length: 4 mm
- Probe Material: Nickel Aluminium, Nickel Chrome
- Maximum Temperature Sensed: +400 °C
- Termination Type: Bare Wire Tail
- Cable Length: 1 m



2000601 K

RS PRO TYPE J THERMOCOUPLE 4MM LENGTH, 4MM DIAMETER → +400°C

ขนาดบรรจุภัณฑ์: 1 x EA

- Thermocouple Type: J
- Probe Diameter: 4 mm
- Probe Length: 4 mm
- Maximum Temperature Sensed: +400 °C
- Termination Type: Bare Wire Tail
- Cable Length: 1 m



2000603 J

RS PRO TYPE J THERMOCOUPLE 4MM LENGTH, 3.2MM DIAMETER → +400°C

ขนาดบรรจุภัณฑ์: 1 x EA

- Thermocouple Type: J
- Probe Diameter: 3.2 mm
- Probe Length: 4 mm
- Maximum Temperature Sensed: +400 °C
- Termination Type: Bare Wire Tail
- Cable Length: 1 m



2000604 J

RS PRO TYPE J THERMOCOUPLE 3.5MM DIAMETER → +350°C

ขนาดบรรจุภัณฑ์: 1 x EA

- Thermocouple Type: J
- Probe Diameter: 3.5 mm
- Probe Material: Copper
- Maximum Temperature Sensed: +350 °C
- Termination Type: Bare Wire Tail
- Cable Length: 2 m



2000605 J

RS PRO TYPE K THERMOCOUPLE 3.5MM DIAMETER → +350°C

ขนาดบรรจุภัณฑ์: 1 x EA

- Thermocouple Type: K
- Probe Diameter: 3.5 mm
- Probe Material: Copper
- Maximum Temperature Sensed: +350 °C
- Termination Type: Bare Wire Tail
- Cable Length: 2 m



2000606 K

RS PRO TYPE J THERMOCOUPLE 4MM DIAMETER → +350°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: J
 - Probe Diameter: 4 mm
 - Probe Material: Copper
 - Maximum Temperature Sensed: +350 °C
 - Termination Type: Bare Wire Tail
 - Cable Length: 2 m



2000607 J

RS PRO TYPE K THERMOCOUPLE 4MM DIAMETER → +350°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 4 mm
 - Probe Material: Copper
 - Maximum Temperature Sensed: +350 °C
 - Termination Type: Bare Wire Tail
 - Cable Length: 2 m



2000609 K

RS PRO TYPE J THERMOCOUPLE 5MM DIAMETER → +350°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: J
 - Probe Diameter: 5 mm
 - Probe Material: Copper
 - Maximum Temperature Sensed: +350 °C
 - Termination Type: Bare Wire Tail
 - Cable Length: 2 m



2000610 J

RS PRO TYPE K THERMOCOUPLE 5MM DIAMETER → +350°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 5 mm
 - Probe Material: Copper
 - Maximum Temperature Sensed: +350 °C
 - Termination Type: Bare Wire Tail
 - Cable Length: 2 m



2000611 K

RS PRO TYPE J THERMOCOUPLE 8MM DIAMETER → +350°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: J
 - Probe Diameter: 8 mm
 - Probe Material: Copper
 - Maximum Temperature Sensed: +350 °C
 - Termination Type: Bare Wire Tail
 - Cable Length: 2 m



2000612 J

RS PRO TYPE K THERMOCOUPLE 8MM DIAMETER → +350°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 8 mm
 - Probe Material: Copper
 - Maximum Temperature Sensed: +350 °C
 - Termination Type: Bare Wire Tail
 - Cable Length: 2 m



2000613 K

RS PRO TYPE J THERMOCOUPLE 10MM DIAMETER → +350°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: J
 - Probe Diameter: 10 mm
 - Probe Material: Copper
 - Maximum Temperature Sensed: +350 °C
 - Termination Type: Bare Wire Tail
 - Cable Length: 2 m



2000615 J

RS PRO TYPE K THERMOCOUPLE 10MM DIAMETER → +350°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 10 mm
 - Probe Material: Copper
 - Maximum Temperature Sensed: +350 °C
 - Termination Type: Bare Wire Tail
 - Cable Length: 2 m



2000616 K

RS PRO TYPE K THERMOCOUPLE 1M LENGTH, 1MM DIAMETER → +750°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 1 mm
 - Probe Length: 1 m
 - Probe Material: 316 Stainless Steel
 - Maximum Temperature Sensed: +750 °C
 - Termination Type: Cable
 - Cable Length: 100 mm
 - Standards Met: IEC



2194359 K

THERMOCOUPLE,MI,K,1.5MMX0.5M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 1.5 mm
 - Probe Length: 500 mm
 - Probe Material: 316 Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 100 mm
 - Standards Met: IEC



2194365 K

RS PRO TYPE K THERMOCOUPLE 1M LENGTH, 1.5MM DIAMETER → +1100°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 1.5 mm
 - Probe Length: 1 m
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 100 mm
 - Standards Met: IEC



2194371 K

RS PRO TYPE K THERMOCOUPLE 500MM LENGTH, 3MM DIAMETER →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 3 mm
 - Probe Length: 500 mm
 - Probe Material: 316 Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 100 mm
 - Standards Met: IEC



2194387 K

THERMOCOUPLE,MI,K,3.0MMX1.0M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 3 mm
 - Probe Length: 1 m
 - Probe Material: 316 Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 100 mm
 - Standards Met: IEC



2194393 K

RS PRO TYPE K THERMOCOUPLE 1M LENGTH, 1MM DIAMETER → +750°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 1 mm
 - Probe Length: 1 m
 - Probe Material: Inconel 600
 - Maximum Temperature Sensed: +750 °C
 - Termination Type: Cable
 - Cable Length: 100 mm
 - Standards Met: IEC



2194450 K

RS PRO TYPE K THERMOCOUPLE 500MM LENGTH, 1.5MM DIAMETER →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 1.5 mm
 - Probe Length: 500 mm
 - Probe Material: Inconel 600
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 100 mm
 - Standards Met: IEC



2194466 K

RS PRO TYPE K THERMOCOUPLE 1M LENGTH, 1.5MM DIAMETER → +1100°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 1.5 mm
 - Probe Length: 1 m
 - Probe Material: Inconel 600
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 100 mm
 - Standards Met: IEC



2194472 K

RS PRO TYPE K THERMOCOUPLE 500MM LENGTH, 3MM DIAMETER →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 3 mm
 - Probe Length: 500 mm
 - Probe Material: Inconel 600
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 100 mm
 - Standards Met: IEC



2194488 K

THERMOCOUPLE, MI, 3MMX3.0M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 3 mm
 - Probe Length: 300 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: IEC



2194539 K

THERMOCOUPLE, K, MAGNETIC BASE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Length: 50 mm
 - Maximum Temperature Sensed: +100 °C
 - Termination Type: Miniature Plug
 - Cable Length: 2 m
 - Standards Met: IEC



2194545 K

THERMOCOUPLE, N, 3X300MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: N
 - Probe Diameter: 3 mm
 - Probe Length: 300 mm
 - Probe Material: Nicrosil Alloy
 - Maximum Temperature Sensed: +1300 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: IEC



2194652 N

THERMOCOUPLE, PROBE HD, J

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: J
 - Probe Diameter: 4.5 mm
 - Probe Length: 150 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +350 °C
 - Termination Type: Cable
 - Cable Length: 2 m
 - Standards Met: IEC



2194725 J

RS PRO TYPE J THERMOCOUPLE 76MM LENGTH, 3MM DIAMETER →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: J
 - Probe Diameter: 3 mm
 - Probe Length: 76 mm
 - Maximum Temperature Sensed: +500 °C
 - Probe Material: Constantan, Iron
 - Termination Type: Standard Plug
 - Standards Met: IEC



2194731 J

RS PRO TYPE J THERMOCOUPLE 3M LENGTH, 1/0.2MM DIAMETER, -75°C →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: J
 - Probe Diameter: 1/0.2 mm
 - Probe Length: 3 m
 - Maximum Temperature Sensed: +260 °C
 - Probe Material: Teflon PTFE
 - Termination Type: Twin Twisted Tail
 - Cable Length: 3 m
 - Standards Met: IEC 584-3



2209486 J

RS PRO TYPE K THERMOCOUPLE 3M LENGTH, 1/0.2MM DIAMETER, -75°C →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1/0.2 mm
 - Probe Length: 3 m
 - Probe Material: Teflon PTFE
 - Maximum Temperature Sensed: +260 °C
 - Termination Type: Twin Twisted Tail
 - Cable Length: 3 m
 - Minimum Temperature Sensed: -75 °C



2209487 K

RS PRO TYPE T THERMOCOUPLE 3M LENGTH, 1/0.2MM DIAMETER, -75°C →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: T
 - Probe Diameter: 1/0.2 mm
 - Probe Length: 3 m
 - Probe Material: Teflon PTFE
 - Maximum Temperature Sensed: +260 °C
 - Termination Type: Twin Twisted Tail
 - Cable Length: 3 m
 - Minimum Temperature Sensed: -75 °C



2209488 T

RS PRO TYPE K THERMOCOUPLE 2M LENGTH, 1/0.076MM DIAMETER, -75°C


- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1/0.076 mm
 - Probe Length: 2 m
 - Maximum Temperature Sensed: +260 °C
 - Probe Material: Teflon PTFE
 - Termination Type: 2-Wire Tail
 - Cable Length: 2 m
 - Standards Met: ANSI MC96.1



2209490 K

RS PRO TYPE K THERMOCOUPLE 500MM LENGTH, 1/0.076MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1/0.076 mm
 - Probe Length: 500 mm
 - Probe Material: Teflon PTFE
 - Maximum Temperature Sensed: +260 °C
 - Termination Type: 2-Wire Tail
 - Cable Length: 500 m
 - Minimum Temperature Sensed: -75 °C



2209491 K

RS PRO TYPE K THERMOCOUPLE 3M LENGTH, 1/0.376MM DIAMETER, -75°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1/0.376 mm
 - Probe Length: 3 m
 - Probe Material: Teflon PTFE
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Miniature Plug
 - Cable Length: 3 m
 - Minimum Temperature Sensed: -75 °C



2209509 K

THERMOCOUPLE, MINERAL INSULATED, K, STAINLESS STEEL

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1.5 mm
 - Probe Length: 150 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 100 mm
 - Standards Met: IEC



2287445 K

RS PRO TYPE K THERMOCOUPLE 250MM LENGTH, 1.5MM DIAMETER →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1.5 mm
 - Probe Length: 250 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 100 mm
 - Standards Met: IEC



2287451 K

RS PRO TYPE K THERMOCOUPLE 150MM LENGTH, 3MM DIAMETER →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 3 mm
 - Probe Length: 150 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 100 mm
 - Standards Met: IEC



2287467 K

RS PRO TYPE K THERMOCOUPLE 250MM LENGTH, 3MM DIAMETER →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 3 mm
 - Probe Length: 250 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 100 mm
 - Standards Met: IEC



2287489 K

**RS PRO TYPE K THERMOCOUPLE
250MM LENGTH, 6MM DIAMETER →**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 6 mm
 - Probe Length: 250 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 100 mm
 - Standards Met: IEC



2287495 K

**RS PRO TYPE K THERMOCOUPLE 2M
LENGTH, 12.5MM DIAMETER, -50°C →**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 12.5 mm
 - Probe Length: 2 m
 - Maximum Temperature Sensed: +250 °C
 - Probe Material: PFA
 - Series: ANSI
 - Termination Type: Miniature Plug
 - Cable Length: 2 m



2318457 K

**RS PRO TYPE K THERMOCOUPLE
50MM LENGTH, 25 X 50MM**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 25 x 50 mm
 - Probe Length: 50 mm
 - Maximum Temperature Sensed: +100 °C
 - Probe Material: PFA
 - Series: ANSI
 - Termination Type: Miniature Plug
 - Cable Length: 2 m



2318459 K

**RS PRO TYPE K THERMOCOUPLE
50MM LENGTH, 25 X 50MM**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 25 x 50 mm
 - Probe Length: 50 mm
 - Maximum Temperature Sensed: +100 °C
 - Probe Material: PFA
 - Series: ANSI
 - Termination Type: Miniature Plug
 - Cable Length: 1 m



2318461 K

**RS PRO TYPE K THERMOCOUPLE
40MM LENGTH, 40 X 13 X 5MM**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 40 x 13 x 5 mm
 - Probe Length: 40 mm
 - Maximum Temperature Sensed: +100 °C
 - Probe Material: Silicone Rubber
 - Series: ANSI
 - Termination Type: Miniature Plug
 - Cable Length: 2 m



2318463 K

**RS PRO TYPE K THERMOCOUPLE 3M
LENGTH, , -75°C → +250°C**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Length: 3 m
 - Maximum Temperature Sensed: +250 °C
 - Probe Material: PVC
 - Series: ANSI
 - Termination Type: Miniature Plug
 - Cable Length: 3 m
 - Standards Met: RoHS



2318474 K

**RS PRO TYPE T THERMOCOUPLE
3M LENGTH, , -75°C → +250°C**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: Type T
 - Probe Length: 3 m
 - Maximum Temperature Sensed: +250 °C
 - Probe Material: PVC
 - Series: ANSI
 - Termination Type: Miniature Plug
 - Cable Length: 3 m
 - Standards Met: RoHS



2318478 Type T

**RS PRO TYPE T THERMOCOUPLE
3M LENGTH, , -75°C → +250°C**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: Type T
 - Probe Length: 3 m
 - Maximum Temperature Sensed: +250 °C
 - Probe Material: PFA
 - Series: ANSI
 - Termination Type: Bare Wire Tail
 - Cable Length: 3 m
 - Standards Met: RoHS



2318480 Type T

**PROBE,BUTTON
MAGNET,THERMOCOUPLE,K**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 6 mm
 - Maximum Temperature Sensed: +250 °C
 - Probe Material: Stainless Steel
 - Termination Type: Miniature Plug
 - Cable Length: 1 m
 - Standards Met: IEC



2364255 K

**RS PRO JIS TYPE K EXPOSED WELDED
TIP THE**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 1/0.2 mm
 - Probe Length: 10 m
 - Maximum Temperature Sensed: +250 °C
 - Probe Material: PFA
 - Termination Type: Miniature Plug
 - Series: XQ



2394532 K 880.08

**RS PRO JIS TYPE K EXPOSED WELDED
TIP THE**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 1/0.3 mm
 - Probe Length: 5 m
 - Maximum Temperature Sensed: +250 °C
 - Probe Material: PFA
 - Termination Type: Bare Wire Tail
 - Series: XQ



2394542 K

**RS PRO JIS TYPE K EXPOSED WELDED
TIP THE**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 1/0.3 mm
 - Probe Length: 10 m
 - Maximum Temperature Sensed: +250 °C
 - Probe Material: PFA
 - Termination Type: Bare Wire Tail
 - Series: XQ



2394544 K

**RS PRO JIS TYPE K EXPOSED WELDED
TIP THE**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 7/0.2 mm
 - Probe Length: 5 m
 - Maximum Temperature Sensed: +250 °C
 - Probe Material: PFA
 - Termination Type: Bare Wire Tail
 - Series: XO



2394552 K

THERMOCOUPLE,PATCH,K

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 1/0.2 mm
 - Probe Length: 40 mm
 - Probe Material: Aluminium Foil Backing, Silicone Rubber
 - Maximum Temperature Sensed: +150 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: IEC



2905036 K

**RS PRO TYPE J THERMOCOUPLE
20MM LENGTH, 5MM DIAMETER →**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: J
 - Probe Diameter: 5 mm
 - Probe Length: 20 mm
 - Maximum Temperature Sensed: +400 °C
 - Probe Material: 316 Stainless Steel
 - Termination Type: Cable
 - Cable Length: 2.5 m
 - Standards Met: RoHS Compliant



3241721 J

**RS PRO TYPE J THERMOCOUPLE
20MM LENGTH, 5MM DIAMETER →**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: J
 - Probe Diameter: 5 mm
 - Probe Length: 20 mm
 - Maximum Temperature Sensed: +400 °C
 - Probe Material: 316 Stainless Steel
 - Termination Type: Cable
 - Cable Length: 2.5 m
 - Standards Met: RoHS Compliant



3241737 J

RS PRO TYPE J THERMOCOUPLE 20MM LENGTH, 5MM DIAMETER →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: J
 - Probe Diameter: 5 mm
 - Probe Length: 20 mm
 - Maximum Temperature Sensed: +400 °C
 - Probe Material: 316 Stainless Steel
 - Termination Type: Cable
 - Cable Length: 2.5 m
 - Standards Met: RoHS Compliant



3241844 J

RS PRO TYPE J THERMOCOUPLE 20MM LENGTH, 6MM DIAMETER →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: J
 - Probe Diameter: 6 mm
 - Probe Length: 20 mm
 - Maximum Temperature Sensed: +600 °C
 - Probe Material: 316 Stainless Steel
 - Termination Type: Cable
 - Cable Length: 2.5 m
 - Standards Met: RoHS Compliant



3241894 J

RS PRO TYPE J THERMOCOUPLE 20MM LENGTH, 8MM DIAMETER →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: J
 - Probe Diameter: 8 mm
 - Probe Length: 20 mm
 - Maximum Temperature Sensed: +400 °C
 - Probe Material: 316 Stainless Steel
 - Termination Type: Cable
 - Cable Length: 2.5 m
 - Standards Met: RoHS Compliant



3241967 J

RS PRO TYPE J THERMOCOUPLE 150MM LENGTH, 1MM DIAMETER →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: J
 - Probe Diameter: 1 mm
 - Probe Length: 150 mm
 - Maximum Temperature Sensed: +400 °C
 - Probe Material: 316 Stainless Steel
 - Termination Type: Cable
 - Cable Length: 2 m
 - Standards Met: RoHS Compliant



3242443 J

RS PRO TYPE J THERMOCOUPLE 300MM LENGTH, 1MM DIAMETER →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: J
 - Probe Diameter: 1 mm
 - Probe Length: 300 mm
 - Maximum Temperature Sensed: +400 °C
 - Probe Material: 316 Stainless Steel
 - Termination Type: Cable
 - Cable Length: 2 m
 - Standards Met: RoHS Compliant



3242459 J

RS PRO TYPE J THERMOCOUPLE 150MM LENGTH, 1.5MM DIAMETER →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: J
 - Probe Diameter: 1.5 mm
 - Probe Length: 150 mm
 - Maximum Temperature Sensed: +400 °C
 - Probe Material: 316 Stainless Steel
 - Termination Type: Cable
 - Cable Length: 2 m
 - Standards Met: RoHS Compliant



3242465 J

THERMOCOUPLE K PROBE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 5 mm
 - Probe Length: 20 mm
 - Maximum Temperature Sensed: +750 °C
 - Probe Material: 316L Stainless Steel
 - Termination Type: Cable
 - Cable Length: 2.5 m
 - Standards Met: RoHS Compliant



3342622 K

THERMOCOUPLE J PROBE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: J
 - Probe Diameter: 5 mm
 - Probe Length: 20 mm
 - Maximum Temperature Sensed: +600 °C
 - Probe Material: 316L Stainless Steel
 - Termination Type: Cable
 - Cable Length: 2.5 m
 - Standards Met: RoHS Compliant



3342638 J

RS PRO TYPE J THERMOCOUPLE 5MM LENGTH, 3MM DIAMETER → +500°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: J
 - Probe Diameter: 3 mm
 - Probe Length: 5 mm
 - Maximum Temperature Sensed: +500 °C
 - Probe Material: Constantan, Iron
 - Termination Type: Standard Plug
 - Standards Met: IEC



3534578 J

THERMOCOUPLE, EXPOSED JUNCTION, MIN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: J
 - Probe Diameter: 1/0.2 mm
 - Probe Length: 1 m
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Miniature Plug
 - Cable Length: 1 m
 - Standards Met: IEC



3630244 J

THERMOCOUPLE, EXPOSED JUNCTION, MIN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 1/0.2 mm
 - Probe Length: 1 m
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Miniature Plug
 - Cable Length: 1 m
 - Standards Met: IEC



3630250 K

THERMOCOUPLE, EXPOSED JUNCTION, MIN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: T
 - Probe Diameter: 1/0.2 mm
 - Probe Length: 1 m
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Miniature Plug
 - Cable Length: 1 m
 - Standards Met: IEC



3630266 T

THERMOCOUPLE, EXPOSED JUNCTION, MIN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: J
 - Probe Diameter: 1/0.3 mm
 - Probe Length: 2 m
 - Maximum Temperature Sensed: +350 °C
 - Termination Type: Miniature Plug
 - Cable Length: 2 m
 - Standards Met: IEC



3630288 J

RS PRO TYPE K THERMOCOUPLE 2M LENGTH, 1/0.315MM DIAMETER →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 1/0.315 mm
 - Probe Length: 2 m
 - Maximum Temperature Sensed: +350 °C
 - Termination Type: Miniature Plug
 - Cable Length: 2 m
 - Standards Met: IEC
 - Response Time: Fast



3630294 K

RS PRO TYPE N THERMOCOUPLE 1/0.3MM DIAMETER → +350°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: N
 - Probe Diameter: 1/0.3 mm
 - Maximum Temperature Sensed: +350 °C
 - Termination Type: Miniature Plug
 - Cable Length: 2 m
 - Standards Met: IEC



3630301 N

RS PRO TYPE J THERMOCOUPLE 1M LENGTH, 1/0.2MM DIAMETER →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: J
 - Probe Diameter: 1/0.2 mm
 - Probe Length: 1 m
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Miniature Plug
 - Cable Length: 1 m
 - Standards Met: IEC



3630317 J

THERMOCOUPLE, EXPOSED JUNCTION, MIN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 1/0.2 mm
 - Probe Length: 1 m
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Miniature Plug
 - Cable Length: 1 m
 - Standards Met: IEC



3630323 K

THERMOCOUPLE, EXPOSED JUNCTION, MIN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: T
 - Probe Diameter: 1/0.2 mm
 - Probe Length: 1 m
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Miniature Plug
 - Cable Length: 1 m
 - Standards Met: IEC



3630339 T

SENSOR, THERMOCOUPLE, K, MINERAL INSULATED, 1.5MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 1.5 mm
 - Probe Length: 150 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: IEC



3971236 K

SENSOR, THERMOCOUPLE, K, MINERAL INSULATED, 1.5MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 1.5 mm
 - Probe Length: 250 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: IEC



3971258 K

SENSOR, THERMOCOUPLE, K, MINERAL INSULATED, 3.0MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 3 mm
 - Probe Length: 150 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: IEC



3971264 K

SENSOR, THERMOCOUPLE, K, MINERAL INSULATED, 3.0MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 3 mm
 - Probe Length: 250 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: IEC



3971270 K

SENSOR, THERMOCOUPLE, K, MINERAL INSULATED, 6.0MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 6 mm
 - Probe Length: 150 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: IEC



3971286 K

RS PRO TYPE K THERMOCOUPLE 250MM LENGTH, 6MM DIAMETER →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 6 mm
 - Probe Length: 250 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: IEC



3971292 K

SENSOR, THERMOCOUPLE, K, MINERAL INSULATED, DUPLEX, 1000MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 3 mm
 - Probe Length: 150 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: IEC



3971359 K

RS PRO TYPE K THERMOCOUPLE 250MM LENGTH, 3MM DIAMETER →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 3 mm
 - Probe Length: 250 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: IEC



3971365 K

SENSOR, THERMOCOUPLE, K, MINERAL INSULATED, DUPLEX, 1000MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 6 mm
 - Probe Length: 150 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: IEC



3971371 K

RS PRO TYPE K THERMOCOUPLE 250MM LENGTH, 6MM DIAMETER →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 6 mm
 - Probe Length: 250 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: IEC



3971387 K

SENSOR, THERMOCOUPLE, K, MINERAL INSULATED, MIN PLUG, 1.5MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 1.5 mm
 - Probe Length: 150 mm
 - Maximum Temperature Sensed: +1100 °C
 - Probe Material: Stainless Steel
 - Termination Type: Miniature Plug
 - Standards Met: IEC



3971450 K

SENSOR, THERMOCOUPLE, K, MINERAL INSULATED, MIN PLUG, 1.5MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 1.5 mm
 - Probe Length: 250 mm
 - Maximum Temperature Sensed: +1100 °C
 - Probe Material: Stainless Steel
 - Termination Type: Miniature Plug
 - Standards Met: IEC



3971472 K

SENSOR, THERMOCOUPLE, K, MINERAL INSULATED, MIN PLUG, 3.0MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 3 mm
 - Probe Length: 150 mm
 - Maximum Temperature Sensed: +1100 °C
 - Probe Material: Stainless Steel
 - Termination Type: Miniature Plug
 - Standards Met: IEC



3971488 K

SENSOR, THERMOCOUPLE, K, MINERAL INSULATED, MIN PLUG, 3.0MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 3 mm
 - Probe Length: 250 mm
 - Maximum Temperature Sensed: +1100 °C
 - Probe Material: Stainless Steel
 - Termination Type: Miniature Plug
 - Standards Met: IEC



3971494 K

SENSOR, THERMOCOUPLE, K, MINERAL INSULATED, STD PLUG, 1.5MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1.5 mm
 - Probe Length: 150 mm
 - Maximum Temperature Sensed: +1100 °C
 - Probe Material: Nickel Aluminium, Nickel Chrome
 - Termination Type: Standard Plug
 - Standards Met: IEC



3971501 K

SENSOR, THERMOCOUPLE, K, MINERAL INSULATED, STD PLUG, 1.5MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1.5 mm
 - Probe Length: 250 mm
 - Maximum Temperature Sensed: +1100 °C
 - Probe Material: Stainless Steel
 - Termination Type: Standard Plug
 - Standards Met: IEC



3971517 K

SENSOR, THERMOCOUPLE, K, MINERAL INSULATED, STD PLUG, 3.0MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 3 mm
 - Probe Length: 150 mm
 - Maximum Temperature Sensed: +1100 °C
 - Probe Material: Stainless Steel
 - Termination Type: Standard Plug
 - Standards Met: IEC



3971539 K

SENSOR, THERMOCOUPLE, K, MINERAL INSULATED, STD PLUG, 3.0MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 3 mm
 - Probe Length: 250 mm
 - Maximum Temperature Sensed: +1100 °C
 - Probe Material: Stainless Steel
 - Termination Type: Standard Plug
 - Standards Met: IEC



3971545 K

SENSOR, THERMOCOUPLE, K, MINERAL INSULATED, STD PLUG, 6.0MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 6 mm
 - Probe Length: 150 mm
 - Maximum Temperature Sensed: +1100 °C
 - Probe Material: Stainless Steel
 - Termination Type: Standard Plug
 - Standards Met: IEC



3971551 K

SENSOR, THERMOCOUPLE, K, MINERAL INSULATED, STD PLUG, 6.0MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 6 mm
 - Probe Length: 250 mm
 - Maximum Temperature Sensed: +1100 °C
 - Probe Material: Stainless Steel
 - Termination Type: Standard Plug
 - Standards Met: IEC



3971567 K

SENSOR, THERMOCOUPLE, K, FINE GAUGE, BARE WIRE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 0.025 mm
 - Probe Length: 200 mm
 - Termination Type: Cable
 - Cable Length: 200 mm
 - Standards Met: IEC



3971573 K

RS PRO TYPE K TEMPERATURE PROBE 3M LENGTH, 2.8 X 3.9MM DIAMETER →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 2.8 x 3.9 mm
 - Probe Length: 3 m
 - Maximum Temperature Sensed: +1200 °C
 - Probe Material: Ceramic Fiber
 - Termination Type: Cable
 - Cable Length: 3 m
 - Standards Met: RoHS Compliant



4071393 K

RS PRO TYPE K THERMOCOUPLE 70MM LENGTH, 3MM DIAMETER →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 3 mm
 - Probe Length: 70 mm
 - Maximum Temperature Sensed: +700 °C
 - Probe Material: Stainless Steel
 - Termination Type: Miniature Plug
 - Cable Length: 300 mm
 - Standards Met: RoHS Compliant



4334379 K

RS PRO TYPE K THERMOCOUPLE 300MM LENGTH, 3MM DIAMETER →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 3 mm
 - Probe Length: 300 mm
 - Maximum Temperature Sensed: +1200 °C
 - Probe Material: Stainless Steel
 - Termination Type: Miniature Plug
 - Cable Length: 2 m
 - Standards Met: RoHS Compliant



4334420 K

RS PRO TYPE K THERMOCOUPLE 300MM LENGTH, 4.5MM DIAMETER →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 4.5 mm
 - Probe Length: 300 mm
 - Maximum Temperature Sensed: +1200 °C
 - Probe Material: Stainless Steel
 - Termination Type: Miniature Plug
 - Cable Length: 3 m
 - Standards Met: RoHS Compliant



4334436 K

THERMOCOUPLE, GROUNDED, K, MI, 0.5X150MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 0.5 mm
 - Probe Length: 150 mm
 - Maximum Temperature Sensed: +750 °C
 - Probe Material: Stainless Steel
 - Termination Type: Cable
 - Cable Length: 100 mm
 - Standards Met: IEC



4437917 K

THERMOCOUPLE, GROUNDED, K, MI, 0.5X500MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 0.5 mm
 - Probe Length: 500 mm
 - Maximum Temperature Sensed: +750 °C
 - Probe Material: Stainless Steel
 - Termination Type: Cable
 - Cable Length: 100 mm
 - Standards Met: IEC



4437939 K

RS PRO TYPE K THERMOCOUPLE 500MM LENGTH, 0.5MM DIAMETER →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 0.5 mm
 - Probe Length: 500 mm
 - Maximum Temperature Sensed: +750 °C
 - Probe Material: Stainless Steel
 - Termination Type: Cable
 - Cable Length: 100 mm
 - Standards Met: IEC



4437951 K

THERMOCOUPLE, GROUNDED, K, MI, 0.5X150MM, +MP

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 0.5 mm
 - Probe Length: 150 mm
 - Maximum Temperature Sensed: +750 °C
 - Probe Material: Stainless Steel
 - Termination Type: Miniature Plug
 - Standards Met: IEC



4437967 K

THERMOCOUPLE, GROUNDED, K, MI, 0.5X250MM, +MP

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 0.5 mm
 - Probe Length: 250 mm
 - Maximum Temperature Sensed: +750 °C
 - Probe Material: Stainless Steel
 - Termination Type: Miniature Plug
 - Standards Met: IEC



4437973 K

**RS PRO TYPE K THERMOCOUPLE
150MM LENGTH, 0.5MM DIAMETER →**

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 0.5 mm
 - Probe Length: 150 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +750 °C
 - Termination Type: Cable
 - Cable Length: 100 mm
 - Standards Met: IEC



4441231 K

**THERMOCOUPLE,INSULATED,K,MI,0.5
X150MM,+MP**

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 0.5 mm
 - Probe Length: 150 mm
 - Maximum Temperature Sensed: +750 °C
 - Probe Material: Stainless Steel
 - Termination Type: Miniature Plug
 - Standards Met: IEC



4441275 K

**THERMOCOUPLE,INSULATED,K,MI,0.5
X250MM,+MP**

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 0.5 mm
 - Probe Length: 250 mm
 - Maximum Temperature Sensed: +1100 °C
 - Probe Material: Stainless Steel
 - Termination Type: Miniature Plug
 - Standards Met: IEC



4441281 K

**RS PRO TYPE K THERMOCOUPLE 3M
LENGTH, 3MM DIAMETER → +1100°C**

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 3 mm
 - Probe Length: 3 m
 - Probe Material: Inconel 600
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 100 mm
 - Standards Met: IEC



4553750 K

**THERMOCOUPLE,SENSOR,MINERAL,
INSULATED,J,1.5X150MM,1M**

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: J
 - Probe Diameter: 1.5 mm
 - Probe Length: 150 mm
 - Maximum Temperature Sensed: +760 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: IEC



4554270 J

**RS PRO TYPE J THERMOCOUPLE
250MM LENGTH, 1.5MM DIAMETER →**

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: J
 - Probe Diameter: 1.5 mm
 - Probe Length: 250 mm
 - Probe Material: Nickel Aluminium, Nickel Chrome
 - Maximum Temperature Sensed: +760 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: IEC



4554286 J

**THERMOCOUPLE,SENSOR,MINERAL,
INSULATED,J,3.0X150MM,1M**

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: J
 - Probe Diameter: 3 mm
 - Probe Length: 150 mm
 - Maximum Temperature Sensed: +760 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: IEC



4554292 J

**RS PRO TYPE J THERMOCOUPLE
250MM LENGTH, 3MM DIAMETER →**

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: J
 - Probe Diameter: 3 mm
 - Probe Length: 250 mm
 - Maximum Temperature Sensed: +760 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: IEC



4554309 J

**RS PRO TYPE J THERMOCOUPLE
150MM LENGTH, 6MM DIAMETER →**

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: J
 - Probe Diameter: 6 mm
 - Probe Length: 150 mm
 - Maximum Temperature Sensed: +760 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: IEC



4554315 J

**RS PRO TYPE J THERMOCOUPLE
30MM LENGTH, 5MM DIAMETER →**


- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: J
 - Probe Diameter: 5 mm
 - Probe Length: 30 mm
 - Maximum Temperature Sensed: +400 °C
 - Probe Material: Stainless Steel
 - Termination Type: Cable
 - Cable Length: 2 m
 - Standards Met: RoHS Compliant



5477865 J

**SENSOR,THERMOCOUPLE,N,MINERAL
INSULATED,INCONEL SHEATH,1.5MM**

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: N
 - Probe Diameter: 1.5 mm
 - Probe Length: 500 mm
 - Probe Material: Inconel 600
 - Maximum Temperature Sensed: +1250 °C
 - Termination Type: Cable
 - Cable Length: 2 m
 - Standards Met: IEC



6118286 N

**RS PRO TYPE N THERMOCOUPLE
500MM LENGTH, 3MM DIAMETER →**

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: N
 - Probe Diameter: 3 mm
 - Probe Length: 500 mm
 - Probe Material: Inconel 600
 - Maximum Temperature Sensed: +1250 °C
 - Termination Type: Cable
 - Cable Length: 2 m
 - Standards Met: IEC



6118292 N

**RS PRO TYPE N THERMOCOUPLE
500MM LENGTH, 1.5MM DIAMETER →**

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: N
 - Probe Diameter: 1.5 mm
 - Probe Length: 500 mm
 - Probe Material: Nicrosil Alloy
 - Maximum Temperature Sensed: +1250 °C
 - Termination Type: Cable
 - Cable Length: 2 m
 - Standards Met: IEC



6118309 N

**RS PRO TYPE N THERMOCOUPLE
500MM LENGTH, 3MM DIAMETER →**

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: N
 - Probe Diameter: 3 mm
 - Probe Length: 500 mm
 - Probe Material: Nicrosil Alloy
 - Maximum Temperature Sensed: +1250 °C
 - Termination Type: Cable
 - Cable Length: 2 m
 - Standards Met: IEC



6118315 N

**THERMOCOUPLE TYPE J VISIBLE
WELDING TIP,CABLE PTFE INSULATED**

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: J
 - Probe Diameter: 2 mm
 - Probe Length: 1 m
 - Maximum Temperature Sensed: +250 °C
 - Probe Material: Teflon PTFE
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: RoHS Compliant



6212142 J

**THERMOCOUPLE TYPE K VISIBLE
WELDING TIP,CABLE PTFE INSULATED**

- ขนาดบรรจุภัณฑ์: 5 x EA
- Thermocouple Type: K
 - Probe Diameter: 2 mm
 - Probe Length: 1 m
 - Maximum Temperature Sensed: +250 °C
 - Probe Material: Teflon PTFE
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: RoHS Compliant



6212158 K

RS PRO TYPE T THERMOCOUPLE 1M LENGTH, 2MM DIAMETER → +350°C

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Thermocouple Type: T
 - Probe Diameter: 2 mm
 - Probe Length: 1 m
 - Maximum Temperature Sensed: +350 °C
 - Probe Material: Teflon PTFE
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: RoHS Compliant



6212164 T

RS PRO TYPE K THERMOCOUPLE 2M LENGTH, 0.3MM DIAMETER → +600°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 0.3 mm
 - Probe Length: 2 m
 - Maximum Temperature Sensed: +600 °C
 - Probe Material: Glass Fibre
 - Termination Type: Cable
 - Cable Length: 2 m
 - Standards Met: RoHS Compliant



6212170 K

THERMOCOUPLE, INDUSTRIAL, WELDED TIP GLASS FIBRE, J, 2M, RS, E06065

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: J
 - Probe Diameter: 0.3 mm
 - Probe Length: 2 m
 - Maximum Temperature Sensed: +750 °C
 - Termination Type: Cable
 - Cable Length: 2 m
 - Standards Met: RoHS Compliant
 - Response Time: 0.7 s



6212186 J

THERMOCOUPLE, N, GLASS FIBRE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: N
 - Probe Diameter: 0.3 mm
 - Probe Length: 2 m
 - Maximum Temperature Sensed: +1200 °C
 - Termination Type: Cable
 - Cable Length: 2 m
 - Standards Met: RoHS Compliant
 - Response Time: 0.7 s



6212192 N

THERMOCOUPLE, INDUSTRIAL, WELDED TIP GLASS FIBRE, T, 2M, RS, E06068

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: T
 - Probe Diameter: 0.3 mm
 - Probe Length: 2 m
 - Maximum Temperature Sensed: +350 °C
 - Termination Type: Cable
 - Cable Length: 2 m
 - Standards Met: RoHS Compliant
 - Response Time: 0.7 s



6212209 T

THERMOCOUPLE, ADJUSTABLE BAYONET, TYPE J, 6X170MM SPRING,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: J
 - Probe Diameter: 6 mm
 - Probe Length: 175 mm
 - Maximum Temperature Sensed: +350 °C
 - Probe Material: Stainless Steel
 - Termination Type: Cable
 - Cable Length: 2 m
 - Standards Met: RoHS Compliant



6212215 J

RS PRO TYPE K THERMOCOUPLE 175MM LENGTH, 6MM DIAMETER →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 6 mm
 - Probe Length: 175 mm
 - Maximum Temperature Sensed: +1100 °C
 - Probe Material: Stainless Steel
 - Termination Type: Cable
 - Cable Length: 2 m
 - Standards Met: RoHS Compliant



6212221 K

RS PRO TYPE J THERMOCOUPLE 2M LENGTH, 0.2MM DIAMETER → +400°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: J
 - Probe Diameter: 0.2 mm
 - Probe Length: 2 m
 - Maximum Temperature Sensed: +400 °C
 - Probe Material: Stainless Steel
 - Termination Type: Cable
 - Cable Length: 2 m
 - Standards Met: RoHS Compliant



6212259 J

TYPE J WASHER, 6MM DIAMETER, 2M STAINLESS STEEL BRAIDED

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: J
 - Probe Diameter: 6 mm
 - Probe Length: 2 m
 - Maximum Temperature Sensed: +350 °C
 - Probe Material: Stainless Steel
 - Termination Type: Cable
 - Cable Length: 2 m
 - Standards Met: RoHS Compliant



6212265 J

TYPE K WASHER, 6MM DIAMETER, 2M STAINLESS STEEL BRAIDED

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 6 mm
 - Probe Length: 2 m
 - Maximum Temperature Sensed: +350 °C
 - Probe Material: Stainless Steel
 - Termination Type: Cable
 - Cable Length: 2 m
 - Standards Met: RoHS Compliant



6212271 K

THERMOCOUPLE, SELF ADHESIVE, K, 1M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 6.35 mm
 - Probe Length: 1 m
 - Maximum Temperature Sensed: +200 °C
 - Probe Material: Copper
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: RoHS Compliant



6212287 K

THERMOCOUPLE, TYPE K, PIPE SURFACE, DIA 13-20MM, 0 TO

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 13 → 20 mm
 - Probe Length: 2 m
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 2 m
 - Standards Met: RoHS Compliant
 - Response Time: 0.7 s



6212293 K

RS PRO TYPE K THERMOCOUPLE 2M LENGTH, 22 → 30MM DIAMETER →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 22 → 30 mm
 - Probe Length: 2 m
 - Maximum Temperature Sensed: +1100 °C
 - Probe Material: 316 Stainless Steel
 - Termination Type: Cable
 - Cable Length: 2 m
 - Standards Met: RoHS Compliant



6212300 K

RS PRO TYPE K THERMOCOUPLE 2M LENGTH, 30 → 40MM DIAMETER →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 30 → 40 mm
 - Probe Length: 2 m
 - Maximum Temperature Sensed: +1100 °C
 - Probe Material: 316 Stainless Steel
 - Termination Type: Cable
 - Cable Length: 2 m
 - Standards Met: RoHS Compliant



6212316 K

RS PRO TYPE K THERMOCOUPLE 2M LENGTH, 40 → 50MM DIAMETER →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 40 → 50 mm
 - Probe Length: 2 m
 - Maximum Temperature Sensed: +1100 °C
 - Probe Material: 316 Stainless Steel
 - Termination Type: Cable
 - Cable Length: 2 m
 - Standards Met: RoHS Compliant



6212322 K

RS PRO TYPE K THERMOCOUPLE 150MM LENGTH, 6MM DIAMETER →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 6 mm
 - Probe Length: 150 mm
 - Maximum Temperature Sensed: +1100 °C
 - Probe Material: Stainless Steel
 - Termination Type: Connection Head
 - Standards Met: RoHS Compliant



6212338 K

**RS PRO TYPE K THERMOCOUPLE
250MM LENGTH, 6MM DIAMETER →**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 6 mm
 - Probe Length: 250 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Connection Head
 - Cable Length: 1 m
 - Standards Met: RoHS Compliant



6212350 K

**RS PRO TYPE K THERMOCOUPLE
500MM LENGTH, 6MM DIAMETER →**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 6 mm
 - Probe Length: 500 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Connection Head
 - Cable Length: 1 m
 - Standards Met: RoHS Compliant



6212366 K

**RS PRO TYPE J THERMOCOUPLE
200MM LENGTH, 6MM DIAMETER →**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: J
 - Probe Diameter: 6 mm
 - Probe Length: 200 mm
 - Maximum Temperature Sensed: +700 °C
 - Probe Material: 316L Stainless Steel
 - Termination Type: Connection Head
 - Standards Met: RoHS Compliant
 - Response Time: 5 s



6212388 J

**RS PRO TYPE K THERMOCOUPLE
200MM LENGTH, 6MM DIAMETER →**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 6 mm
 - Probe Length: 200 mm
 - Maximum Temperature Sensed: +700 °C
 - Probe Material: 310 Stainless Steel
 - Termination Type: Connection Head
 - Standards Met: RoHS Compliant
 - Response Time: 5 s



6212401 K

**RS PRO TYPE K THERMOCOUPLE
165MM LENGTH, 8MM DIAMETER →**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 8 mm
 - Probe Length: 165 mm
 - Maximum Temperature Sensed: +800 °C
 - Probe Material: 316L Stainless Steel
 - Termination Type: Connection Head
 - Standards Met: RoHS Compliant
 - Response Time: 20 s



6212417 K

**RS PRO TYPE K THERMOCOUPLE
400MM LENGTH, 6MM DIAMETER →**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 6 mm
 - Probe Length: 400 mm
 - Maximum Temperature Sensed: +800 °C
 - Probe Material: 310 Stainless Steel
 - Termination Type: Connection Head
 - Standards Met: RoHS Compliant
 - Response Time: 2.2 s



6212423 K

**RS PRO TYPE K THERMOCOUPLE
265MM LENGTH, 8MM DIAMETER →**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 8 mm
 - Probe Length: 265 mm
 - Maximum Temperature Sensed: +800 °C
 - Probe Material: 316L Stainless Steel
 - Termination Type: Connection Head
 - Standards Met: RoHS Compliant
 - Response Time: 20 s



6212439 K

**RS PRO TYPE K THERMOCOUPLE
600MM LENGTH, 6MM DIAMETER →**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 6 mm
 - Probe Length: 600 mm
 - Maximum Temperature Sensed: +800 °C
 - Probe Material: 310 Stainless Steel
 - Termination Type: Connection Head
 - Standards Met: RoHS Compliant
 - Response Time: 5 s



6212445 K

**RS PRO TYPE K THERMOCOUPLE
150MM LENGTH, 7/0.2MM DIAMETER**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 7/0.2 mm
 - Probe Length: 150 mm
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Miniature Plug
 - Cable Length: 5 m
 - Standards Met: IEC



7621112 K

**THERMOCOUPLE TYPE K HD MAGNET
2MTS**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 4.5 mm
 - Probe Length: 2 m
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Miniature Plug
 - Cable Length: 2 m
 - Standards Met: IEC



7621115 K

**THERMOCOUPLE TYPE K WELDED TIP
5M**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 1/0.3 mm
 - Probe Length: 5 m
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Miniature Plug
 - Cable Length: 5 m
 - Standards Met: IEC



7621118 K

**THERMOCOUPLE TYPE T WELDED TIP
5M**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: T
 - Probe Diameter: 1/0.315 mm
 - Probe Length: 5 m
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Miniature Plug
 - Cable Length: 5 m
 - Standards Met: IEC



7621121 T

**RS PRO TYPE T THERMOCOUPLE 5M
LENGTH, 7/0.2MM DIAMETER →**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: T
 - Probe Diameter: 7/0.2 mm
 - Probe Length: 5 m
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Miniature Plug
 - Cable Length: 5 m
 - Standards Met: IEC



7621124 T

THERMOCOUPLE TYPE K 2MTS CABLE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 4.5 mm
 - Probe Length: 150 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +350 °C
 - Termination Type: Cable
 - Cable Length: 2 m
 - Standards Met: IEC



7621128 K

**RS PRO TYPE K THERMOCOUPLE
150MM LENGTH, 1MM DIAMETER →**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 1 mm
 - Probe Length: 150 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: IEC



7877696 K

**RS PRO TYPE K THERMOCOUPLE 1M
LENGTH, 1MM DIAMETER → +1100°C**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 1 mm
 - Probe Length: 1 m
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: IEC



7877703 K

TYPE K INSULATED THERMOCOUPLE, 1.0X250MM


- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1 mm
 - Probe Length: 250 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: IEC



7877706 K

TYPE K INSULATED THERMOCOUPLE, 1.0X500MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1 mm
 - Probe Length: 500 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: IEC



7877709 K

RS PRO TYPE K THERMOCOUPLE 1.5M LENGTH, 1MM DIAMETER → +1100°C


- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1 mm
 - Probe Length: 1.5 m
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: IEC



7877712 K

TYPE K INSULATED THERMOCOUPLE, 1.0X2000MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1 mm
 - Probe Length: 2 m
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: IEC



7877715 K

TYPE K INSULATED THERMOCOUPLE, 1.5X500MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1.5 mm
 - Probe Length: 500 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: IEC



7877719 K

RS PRO TYPE K THERMOCOUPLE 1.5M LENGTH, 1.5MM DIAMETER → +1100°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1.5 mm
 - Probe Length: 1.5 m
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: IEC



7877721 K

RS PRO TYPE K THERMOCOUPLE 2M LENGTH, 1.5MM DIAMETER → +1100°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1.5 mm
 - Probe Length: 2 m
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: IEC



7877725 K

RS PRO TYPE K THERMOCOUPLE 1M LENGTH, 1.5MM DIAMETER → +1100°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1.5 mm
 - Probe Length: 1 m
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: IEC



7877728 K

RS PRO TYPE K THERMOCOUPLE 1.5M LENGTH, 3MM DIAMETER → +1100°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 3 mm
 - Probe Length: 1.5 m
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: IEC



7877731 K

TYPE K INSULATED THERMOCOUPLE, 3X500MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 3 mm
 - Probe Length: 500 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: IEC



7877734 K

TYPE K INSULATED THERMOCOUPLE, 3X1000MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 3 mm
 - Probe Length: 1 m
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: IEC



7877737 K

RS PRO TYPE K THERMOCOUPLE 500MM LENGTH, 6MM DIAMETER →


- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 6 mm
 - Probe Length: 500 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: IEC



7877759 K

K INSULATED THERMOCOUPLE/PLUG, 1X150MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1 mm
 - Probe Length: 150 mm
 - Maximum Temperature Sensed: +750 °C
 - Probe Material: Stainless Steel
 - Termination Type: Miniature Plug
 - Standards Met: IEC



7877762 K

K INSULATED THERMOCOUPLE/PLUG, 1X250MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1 mm
 - Probe Length: 250 mm
 - Maximum Temperature Sensed: +750 °C
 - Probe Material: Stainless Steel
 - Termination Type: Miniature Plug
 - Standards Met: IEC



7877765 K

RS PRO TYPE K THERMOCOUPLE 500MM LENGTH, 1MM DIAMETER →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1 mm
 - Probe Length: 500 mm
 - Maximum Temperature Sensed: +750 °C
 - Probe Material: Stainless Steel
 - Termination Type: Miniature Plug
 - Standards Met: IEC



7877769 K

K INSULATED THERMOCOUPLE/PLUG, 1.5X500MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1.5 mm
 - Probe Length: 500 mm
 - Maximum Temperature Sensed: +1100 °C
 - Probe Material: Stainless Steel
 - Termination Type: Miniature Plug
 - Standards Met: IEC



7877771 K

K INSULATED THERMOCOUPLE/W/PLUG,1.5X1000MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1.5 mm
 - Probe Length: 1 m
 - Maximum Temperature Sensed: +1100 °C
 - Probe Material: Stainless Steel
 - Termination Type: Miniature Plug
 - Standards Met: IEC



787775 K

K INSULATED THERMOCOUPLE/W/PLUG,1X1000MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1 mm
 - Probe Length: 1 m
 - Maximum Temperature Sensed: +750 °C
 - Probe Material: Stainless Steel
 - Termination Type: Miniature Plug
 - Standards Met: IEC



787778 K

RS PRO TYPE K THERMOCOUPLE 500MM LENGTH, 1.5MM DIAMETER →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1.5 mm
 - Probe Length: 500 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Standard Plug
 - Cable Length: 100 mm
 - Standards Met: IEC



787781 K

K INSULATED THERMOCOUPLE W/PLUG,3X500MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 3 mm
 - Probe Length: 500 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Miniature Plug
 - Cable Length: 100 mm
 - Standards Met: IEC



787784 K

RS PRO TYPE K THERMOCOUPLE 1M LENGTH, 3MM DIAMETER → +1100°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 3 mm
 - Probe Length: 1 m
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Miniature Plug
 - Cable Length: 100 mm
 - Standards Met: IEC



787787 K

RS PRO TYPE K THERMOCOUPLE 1M LENGTH, 3MM DIAMETER → +1100°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 3 mm
 - Probe Length: 1 m
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Standard Plug
 - Cable Length: 100 mm
 - Standards Met: IEC



787797 K

RS PRO TYPE K THERMOCOUPLE 1M LENGTH, 6MM DIAMETER → +1100°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 6 mm
 - Probe Length: 1 m
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Standard Plug
 - Cable Length: 100 mm
 - Standards Met: IEC



787780 K

RS PRO TYPE K THERMOCOUPLE 100MM LENGTH, 6MM DIAMETER →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 6 mm
 - Probe Length: 100 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 100 mm
 - Standards Met: IEC



7877804 K

RS PRO TYPE K THERMOCOUPLE 250MM LENGTH, 6MM DIAMETER →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 6 mm
 - Probe Length: 250 mm
 - Maximum Temperature Sensed: +1100 °C
 - Probe Material: Stainless Steel
 - Termination Type: Cable
 - Standards Met: IEC



7877810 K

RS PRO TYPE K THERMOCOUPLE 150MM LENGTH, 6MM DIAMETER →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 6 mm
 - Probe Length: 150 mm
 - Maximum Temperature Sensed: +1100 °C
 - Probe Material: Stainless Steel
 - Termination Type: Cable
 - Standards Met: IEC



7877813 K

RS PRO TYPE K THERMOCOUPLE 200MM LENGTH, 6MM DIAMETER →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 6 mm
 - Probe Length: 200 mm
 - Maximum Temperature Sensed: +1100 °C
 - Probe Material: Stainless Steel
 - Termination Type: Cable
 - Standards Met: IEC



7877816 K

RS PRO TYPE K THERMOCOUPLE 150MM LENGTH, 1MM DIAMETER →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1 mm
 - Probe Length: 150 mm
 - Probe Material: Inconel 600, Stainless Steel
 - Maximum Temperature Sensed: +750 °C
 - Termination Type: Cable
 - Cable Length: 100 mm
 - Standards Met: IEC



7877822 K

RS PRO TYPE K THERMOCOUPLE 250MM LENGTH, 1MM DIAMETER →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1 mm
 - Probe Length: 250 mm
 - Probe Material: Inconel 600, Stainless Steel
 - Maximum Temperature Sensed: +750 °C
 - Termination Type: Cable
 - Cable Length: 100 mm
 - Standards Met: IEC



7877826 K

RS PRO TYPE K THERMOCOUPLE 300MM LENGTH, 6MM DIAMETER →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 6 mm
 - Probe Length: 300 mm
 - Maximum Temperature Sensed: +1100 °C
 - Probe Material: Stainless Steel
 - Termination Type: Cable
 - Standards Met: IEC



7877829 K

RS PRO TYPE K THERMOCOUPLE 500MM LENGTH, 1MM DIAMETER →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1 mm
 - Probe Length: 500 mm
 - Probe Material: Inconel 600, Stainless Steel
 - Maximum Temperature Sensed: +750 °C
 - Termination Type: Cable
 - Cable Length: 100 mm
 - Standards Met: IEC



7877835 K

RS PRO TYPE K THERMOCOUPLE 1.5M LENGTH, 1.5MM DIAMETER → +1100°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1.5 mm
 - Probe Length: 1.5 m
 - Probe Material: Inconel 600, Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 100 mm
 - Standards Met: IEC



7877841 K

RS PRO TYPE K THERMOCOUPLE 2M LENGTH, 1.5MM DIAMETER → +1100°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1.5 mm
 - Probe Length: 2 m
 - Probe Material: Inconel 600, Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 100 mm
 - Standards Met: IEC



7877844 K

RS PRO TYPE K THERMOCOUPLE 1.5M LENGTH, 3MM DIAMETER → +1100°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 3 mm
 - Probe Length: 1.5 m
 - Probe Material: Inconel 600, Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 100 mm
 - Standards Met: IEC



7877848 K

RS PRO TYPE K THERMOCOUPLE 250MM LENGTH, 4.5MM DIAMETER →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 4.5 mm
 - Probe Length: 250 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 100 mm
 - Standards Met: IEC



7877850 K

RS PRO TYPE K THERMOCOUPLE 150MM LENGTH, 4.5MM DIAMETER →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 4.5 mm
 - Probe Length: 150 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 100 mm
 - Standards Met: IEC



7877857 K

RS PRO TYPE K THERMOCOUPLE 1M LENGTH, 0.5MM DIAMETER → +750°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 0.5 mm
 - Probe Length: 1 m
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +750 °C
 - Termination Type: Cable
 - Cable Length: 100 mm
 - Standards Met: IEC



7877860 K

RS PRO TYPE K THERMOCOUPLE 1M LENGTH, 0.5MM DIAMETER → +750°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 0.5 mm
 - Probe Length: 1 m
 - Probe Material: Inconel 600, Stainless Steel
 - Maximum Temperature Sensed: +750 °C
 - Termination Type: Cable
 - Cable Length: 100 mm
 - Standards Met: IEC



7877866 K

IEC G/F THERMOCOUPLE, MINI PLUG, K, 5M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1/0.3 mm
 - Probe Length: 5 m
 - Maximum Temperature Sensed: +350 °C
 - Termination Type: Miniature Plug
 - Cable Length: 5 m
 - Standards Met: IEC



8047874 K

RS PRO TYPE K THERMOCOUPLE CONNECTOR 10M LENGTH, , -75°C →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Length: 10 m
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Miniature Plug
 - Standards Met: IEC
 - Minimum Temperature Sensed: -75 °C



8047886 K

RS PRO TYPE T THERMOCOUPLE CONNECTOR 10M LENGTH, , -75°C →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: T
 - Probe Length: 10 m
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Miniature Plug
 - Standards Met: IEC
 - Minimum Temperature Sensed: -75 °C



8047892 T

RS PRO TYPE K THERMOCOUPLE CONNECTOR 5M LENGTH, , -75°C →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Length: 5 m
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Miniature Plug
 - Standards Met: IEC
 - Minimum Temperature Sensed: -75 °C



8047899 K

RS PRO TYPE T THERMOCOUPLE CONNECTOR 5M LENGTH, , -75°C →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: T
 - Probe Length: 5 m
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Miniature Plug
 - Standards Met: IEC
 - Minimum Temperature Sensed: -75 °C



8047906 T

RS PRO TYPE K THERMOCOUPLE CONNECTOR 150MM LENGTH, 1.5MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1.5 mm
 - Probe Length: 150 mm
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Miniature Plug
 - Standards Met: ANSI
 - Minimum Temperature Sensed: -40 °C



8047909 K

RS PRO TYPE K THERMOCOUPLE CONNECTOR 250MM LENGTH, 3MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 3 mm
 - Probe Length: 250 mm
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Miniature Plug
 - Standards Met: ANSI
 - Minimum Temperature Sensed: -40 °C



8047915 K

RS PRO TYPE K THERMOCOUPLE CONNECTOR 150MM LENGTH, 1MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1 mm
 - Probe Length: 150 mm
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Miniature Plug
 - Standards Met: ANSI
 - Minimum Temperature Sensed: -40 °C



8047931 K

RS PRO TYPE K THERMOCOUPLE CONNECTOR 1M LENGTH, 1.5MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1.5 mm
 - Probe Length: 1 m
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Miniature Plug
 - Standards Met: ANSI
 - Minimum Temperature Sensed: -40 °C



8047956 K

RS PRO TYPE K THERMOCOUPLE CONNECTOR 3MM DIAMETER, -40°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 3 mm
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Miniature Plug
 - Standards Met: ANSI
 - Minimum Temperature Sensed: -40 °C



8047965 K

RS PRO TYPE K THERMOCOUPLE 1M LENGTH, , -75°C → +260°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Length: 1 m
 - Maximum Temperature Sensed: +260 °C
 - Termination Type: Cable
 - Standards Met: IEC
 - Minimum Temperature Sensed: -75 °C



8047981 K

RS PRO TYPE K THERMOCOUPLE 500MM LENGTH, , -75°C → +260°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Length: 500 mm
 - Maximum Temperature Sensed: +260 °C
 - Termination Type: Cable
 - Standards Met: IEC
 - Minimum Temperature Sensed: -75 °C



8047987 K

RS PRO TYPE K THERMOCOUPLE 2M LENGTH, , -75°C → +260°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Length: 2 m
 - Maximum Temperature Sensed: +260 °C
 - Termination Type: Cable
 - Standards Met: IEC
 - Minimum Temperature Sensed: -75 °C



8047990 K

RS PRO TYPE K THERMOCOUPLE → +250°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Maximum Temperature Sensed: +250 °C
 - Probe Material: Nickel Aluminium, Nickel Chrome
 - Termination Type: Miniature Plug
 - Cable Length: 1 m
 - Standards Met: ANSI



8140125 K

ANSI K PFA EXPOSED JUNCTION + MP, 2M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 1/0.2 mm
 - Probe Length: 2 m
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Miniature Plug
 - Cable Length: 2 m
 - Standards Met: ANSI



8140131 K

ANSI K PFA EXPOSED JUNCTION + MP, 2M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 1/0.3 mm
 - Probe Length: 2 m
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Miniature Plug
 - Cable Length: 2 m
 - Standards Met: ANSI



8140134 K

ANSI K PFA EXPOSED JUNCTION + MP, 1M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 1/0.2 mm
 - Probe Length: 1 m
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Miniature Plug
 - Cable Length: 1 m
 - Standards Met: ANSI



8140137 K

RS PRO TYPE K THERMOCOUPLE 7/0.2MM DIAMETER → +250°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 7/0.2 mm
 - Maximum Temperature Sensed: +250 °C
 - Probe Material: Nickel Aluminium, Nickel Chrome
 - Termination Type: Miniature Plug
 - Cable Length: 1 m
 - Standards Met: ANSI



8140140 K

RS PRO TYPE K THERMOCOUPLE 2M LENGTH, 7/0.2MM DIAMETER →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 7/0.2 mm
 - Probe Length: 2 m
 - Probe Material: Nickel Aluminium, Nickel Chrome
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Miniature Plug
 - Cable Length: 2 m
 - Standards Met: ANSI



8140143 K

ANSI K F/G EXPOSED JUNCTION + MP, 1M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 1/0.3 mm
 - Probe Length: 1 m
 - Maximum Temperature Sensed: +350 °C
 - Termination Type: Miniature Plug
 - Cable Length: 1 m
 - Standards Met: ANSI



8140147 K

ANSI T PFA EXPOSED JUNCTION + MP, 2M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: T
 - Probe Diameter: 0.2mm, 0.3 mm
 - Probe Length: 2 m
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Miniature Plug
 - Cable Length: 2 m
 - Standards Met: ANSI



8140153 T

ANSI K F/G EXPOSED JUNCTION + MP, 2M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 7/0.3 mm
 - Probe Length: 2 m
 - Maximum Temperature Sensed: +350 °C
 - Termination Type: Miniature Plug
 - Cable Length: 2 m
 - Standards Met: ANSI



8140156 K

RS PRO TYPE T THERMOCOUPLE 1M LENGTH, 1/0.3MM DIAMETER →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: T
 - Probe Diameter: 1/0.3 mm
 - Probe Length: 1 m
 - Probe Material: Copper
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Miniature Plug
 - Cable Length: 1 m
 - Standards Met: ANSI



8140159 T

RS PRO TYPE K THERMOCOUPLE 250MM LENGTH, 1.5MM DIAMETER →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 1.5 mm
 - Probe Length: 250 mm
 - Maximum Temperature Sensed: +900 °C
 - Probe Material: Inconel 600
 - Termination Type: Standard Plug
 - Standards Met: RoHS Compliant
 - Response Time: 0.9 s



8240509 K

RS PRO TYPE K THERMOCOUPLE 150MM LENGTH, 3MM DIAMETER →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 3 mm
 - Probe Length: 150 mm
 - Maximum Temperature Sensed: +1200 °C
 - Probe Material: Inconel 600, Stainless Steel
 - Termination Type: Standard Plug
 - Standards Met: RoHS Compliant
 - Response Time: 2.1 s



8240512 K

RS PRO TYPE K THERMOCOUPLE 250MM LENGTH, 6MM DIAMETER →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 6 mm
 - Probe Length: 250 mm
 - Maximum Temperature Sensed: +1200 °C
 - Probe Material: 310 Stainless Steel
 - Termination Type: Standard Plug
 - Standards Met: RoHS Compliant
 - Response Time: 5 s



8240584 K

**RS PRO TYPE K THERMOCOUPLE
500MM LENGTH, 6MM DIAMETER →**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 6 mm
 - Probe Length: 500 mm
 - Maximum Temperature Sensed: +1200 °C
 - Probe Material: 310 Stainless Steel
 - Termination Type: Standard Plug
 - Standards Met: RoHS Compliant
 - Response Time: 5 s



8240596 K

**K TYPE INSULATED THERMOCOUPLE
100MM**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 1 mm
 - Probe Length: 100 mm
 - Maximum Temperature Sensed: +800 °C
 - Probe Material: Inconel 600
 - Termination Type: Miniature Plug
 - Standards Met: RoHS Compliant
 - Response Time: 0.7 s



8240603 K

**K TYPE INSULATED THERMOCOUPLE
1000MM**


- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 1 mm
 - Probe Length: 1 m
 - Maximum Temperature Sensed: +800 °C
 - Probe Material: Inconel 600
 - Termination Type: Miniature Plug
 - Standards Met: RoHS Compliant
 - Response Time: 0.7 s



8240613 K

**RS PRO TYPE K THERMOCOUPLE
500MM LENGTH, 1MM DIAMETER →**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 1 mm
 - Probe Length: 500 mm
 - Maximum Temperature Sensed: +800 °C
 - Probe Material: Inconel 600
 - Termination Type: Miniature Plug
 - Standards Met: RoHS Compliant
 - Response Time: 0.7 s



8240619 K

**K TYPE INSULATED THERMOCOUPLE
100MM**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 1.5 mm
 - Probe Length: 100 mm
 - Maximum Temperature Sensed: +800 °C
 - Probe Material: Inconel 600
 - Termination Type: Miniature Plug
 - Standards Met: RoHS Compliant
 - Response Time: 0.9 s



8240622 K

**RS PRO TYPE K THERMOCOUPLE
150MM LENGTH, 1.5MM DIAMETER →**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 1.5 mm
 - Probe Length: 150 mm
 - Maximum Temperature Sensed: +800 °C
 - Probe Material: Inconel 600
 - Termination Type: Miniature Plug
 - Standards Met: RoHS Compliant
 - Response Time: 0.9 s



8240625 K

**RS PRO TYPE K THERMOCOUPLE
250MM LENGTH, 1.5MM DIAMETER →**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 1.5 mm
 - Probe Length: 250 mm
 - Maximum Temperature Sensed: +800 °C
 - Probe Material: Inconel 600
 - Termination Type: Miniature Plug
 - Standards Met: RoHS Compliant
 - Response Time: 0.9 s



8240629 K

**K TYPE INSULATED THERMOCOUPLE
1000MM**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 1.5 mm
 - Probe Length: 1 m
 - Maximum Temperature Sensed: +800 °C
 - Probe Material: Inconel 600
 - Termination Type: Miniature Plug
 - Standards Met: RoHS Compliant
 - Response Time: 0.9 s



8240631 K

**K TYPE INSULATED THERMOCOUPLE
100MM**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 1 mm
 - Probe Length: 100 mm
 - Maximum Temperature Sensed: +800 °C
 - Probe Material: Inconel 600
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: RoHS Compliant



8240635 K

**RS PRO TYPE K THERMOCOUPLE
500MM LENGTH, 1.5MM DIAMETER →**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 1.5 mm
 - Probe Length: 500 mm
 - Maximum Temperature Sensed: +800 °C
 - Probe Material: Inconel 600
 - Termination Type: Miniature Plug
 - Standards Met: RoHS Compliant
 - Response Time: 0.9 s



8240638 K

**RS PRO TYPE K THERMOCOUPLE
500MM LENGTH, 1MM DIAMETER →**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 1 mm
 - Probe Length: 500 mm
 - Maximum Temperature Sensed: +800 °C
 - Probe Material: Inconel 600
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: RoHS Compliant



8240641 K

**K TYPE INSULATED THERMOCOUPLE
150MM**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 1 mm
 - Probe Length: 150 mm
 - Maximum Temperature Sensed: +800 °C
 - Probe Material: Inconel 600
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: RoHS Compliant



8240644 K

**RS PRO TYPE K THERMOCOUPLE
250MM LENGTH, 1MM DIAMETER →**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 1 mm
 - Probe Length: 250 mm
 - Maximum Temperature Sensed: +800 °C
 - Probe Material: Inconel 600
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: RoHS Compliant



8240647 K

**RS PRO TYPE K THERMOCOUPLE
150MM LENGTH, 1.5MM DIAMETER →**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 1.5 mm
 - Probe Length: 150 mm
 - Maximum Temperature Sensed: +800 °C
 - Probe Material: Inconel 600
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: RoHS Compliant



8240653 K

**RS PRO TYPE K THERMOCOUPLE 2M
LENGTH, 1.5MM DIAMETER → +800°C**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 1.5 mm
 - Probe Length: 2 m
 - Maximum Temperature Sensed: +800 °C
 - Probe Material: Inconel 600
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: RoHS Compliant



8240672 K

**K TYPE INSULATED THERMOCOUPLE
150MM**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 3 mm
 - Probe Length: 150 mm
 - Maximum Temperature Sensed: +1200 °C
 - Probe Material: Inconel 600, Stainless Steel
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: RoHS Compliant



8240675 K

K TYPE INSULATED THERMOCOUPLE 250MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 3 mm
 - Probe Length: 250 mm
 - Maximum Temperature Sensed: +1200 °C
 - Probe Material: Inconel 600, Stainless Steel
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: RoHS Compliant



8240679 K

K TYPE INSULATED THERMOCOUPLE 500MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 3 mm
 - Probe Length: 500 mm
 - Maximum Temperature Sensed: +1200 °C
 - Probe Material: Inconel 600, Stainless Steel
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: RoHS Compliant



8240688 K

TYPE K THERMOCOUPLE, S/S, 1X150MM + ANSI

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1 mm
 - Probe Length: 150 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +750 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: ANSI



8471019 K

RS PRO TYPE K THERMOCOUPLE 500MM LENGTH, 1MM DIAMETER →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1 mm
 - Probe Length: 500 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: ANSI



8471021 K

RS PRO TYPE K THERMOCOUPLE 150MM LENGTH, 1.5MM DIAMETER →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1.5 mm
 - Probe Length: 150 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: ANSI



8471025 K

RS PRO TYPE K THERMOCOUPLE 250MM LENGTH, 1MM DIAMETER →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1 mm
 - Probe Length: 250 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: ANSI



8471028 K

RS PRO TYPE K THERMOCOUPLE 150MM LENGTH, 3MM DIAMETER →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 3 mm
 - Probe Length: 150 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: ANSI



8471031 K

RS PRO TYPE K THERMOCOUPLE 500MM LENGTH, 1.5MM DIAMETER →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1.5 mm
 - Probe Length: 500 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: ANSI



8471037 K

RS PRO TYPE K THERMOCOUPLE 250MM LENGTH, 3MM DIAMETER →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 3 mm
 - Probe Length: 250 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: ANSI



8471040 K

RS PRO TYPE K THERMOCOUPLE 150MM LENGTH, 4.5MM DIAMETER →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 4.5 mm
 - Probe Length: 150 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: ANSI



8471047 K

RS PRO TYPE K THERMOCOUPLE 150MM LENGTH, 6MM DIAMETER →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 6 mm
 - Probe Length: 150 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: ANSI



8471053 K

RS PRO TYPE K THERMOCOUPLE 250MM LENGTH, 6MM DIAMETER →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 6 mm
 - Probe Length: 250 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: ANSI



8471062 K

RS PRO TYPE K THERMOCOUPLE 500MM LENGTH, 6MM DIAMETER →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 6 mm
 - Probe Length: 500 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: ANSI



8471065 K

RS PRO TYPE K THERMOCOUPLE 500MM LENGTH, 0.5MM DIAMETER →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 0.5 mm
 - Probe Length: 500 mm
 - Probe Material: Inconel 600, Stainless Steel
 - Maximum Temperature Sensed: +750 °C
 - Termination Type: Cable
 - Cable Length: 100 mm
 - Standards Met: ANSI



8471075 K

RS PRO TYPE K THERMOCOUPLE 1M LENGTH, 1.5MM DIAMETER → +1100°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1.5 mm
 - Probe Length: 1 m
 - Probe Material: Inconel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 100 mm
 - Standards Met: ANSI



8471081 K

RS PRO TYPE K THERMOCOUPLE 500MM LENGTH, 0.5MM DIAMETER,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 0.5 mm
 - Probe Length: 500 mm
 - Maximum Temperature Sensed: +750 °C
 - Probe Material: Inconel
 - Termination Type: Cable
 - Cable Length: 100 mm
 - Standards Met: ANSI



8471084 K

RS PRO TYPE K THERMOCOUPLE 1M LENGTH, 3MM DIAMETER → +1100°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 3 mm
 - Probe Length: 1 m
 - Probe Material: Inconel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 100 mm
 - Standards Met: ANSI



8471093 K

RS PRO TYPE K THERMOCOUPLE 2M LENGTH, 3MM DIAMETER → +1100°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 3 mm
 - Probe Length: 2 m
 - Probe Material: Inconel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 100 mm
 - Standards Met: ANSI



8471097 K

RS PRO TYPE K THERMOCOUPLE 500MM LENGTH, 3MM DIAMETER →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 3 mm
 - Probe Length: 500 mm
 - Probe Material: Inconel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 100 mm
 - Standards Met: ANSI



8471100 K

RS PRO TYPE K THERMOCOUPLE 3M LENGTH, 3MM DIAMETER → +1100°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 3 mm
 - Probe Length: 3 m
 - Probe Material: Inconel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 100 mm
 - Standards Met: ANSI



8471107 K

RS PRO TYPE K THERMOCOUPLE 250MM LENGTH, 0.5MM DIAMETER →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 0.5 mm
 - Probe Length: 250 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 100 mm
 - Standards Met: ANSI



8471116 K

TYPE K THERMOCOUPLE, S/S, 1X150MM +

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1 mm
 - Probe Length: 150 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +750 °C
 - Termination Type: Cable
 - Cable Length: 100 mm
 - Standards Met: ANSI



8471122 K

RS PRO TYPE K THERMOCOUPLE 250MM LENGTH, 1MM DIAMETER →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1 mm
 - Probe Length: 250 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 100 mm
 - Standards Met: ANSI



8471126 K

RS PRO TYPE K THERMOCOUPLE 1M LENGTH, 1MM DIAMETER → +1100°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1 mm
 - Probe Length: 1 m
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 100 mm
 - Standards Met: ANSI



8471129 K

RS PRO TYPE K THERMOCOUPLE 500MM LENGTH, 1MM DIAMETER →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1 mm
 - Probe Length: 500 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 100 mm
 - Standards Met: ANSI



8471135 K

RS PRO TYPE K THERMOCOUPLE 1M LENGTH, 1.5MM DIAMETER → +1100°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1.5 mm
 - Probe Length: 1 m
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 100 mm
 - Standards Met: ANSI



8471138 K

RS PRO TYPE K THERMOCOUPLE 250MM LENGTH, 1.5MM DIAMETER →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1.5 mm
 - Probe Length: 250 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 100 mm
 - Standards Met: ANSI



8471141 K

RS PRO TYPE K THERMOCOUPLE 500MM LENGTH, 1.5MM DIAMETER →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1.5 mm
 - Probe Length: 500 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 100 mm
 - Standards Met: ANSI



8471144 K

RS PRO TYPE K THERMOCOUPLE 2M LENGTH, 3MM DIAMETER → +1100°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 3 mm
 - Probe Length: 2 m
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 100 mm
 - Standards Met: ANSI



8471150 K

RS PRO TYPE K THERMOCOUPLE 250MM LENGTH, 3MM DIAMETER →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 3 mm
 - Probe Length: 250 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 100 mm
 - Standards Met: ANSI



8471154 K

RS PRO TYPE K THERMOCOUPLE 150MM LENGTH, 3MM DIAMETER →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 3 mm
 - Probe Length: 150 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 100 mm
 - Standards Met: ANSI



8471157 K

ANSI K THERMOCOUPLE EXPOSED JUNCTION 2M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1/0.2 mm
 - Probe Length: 2 m
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Cable
 - Cable Length: 2 m
 - Standards Met: ANSI



8479665 K

ANSI K THERMOCOUPLE EXPOSED JUNCTION 1M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1/0.2 mm
 - Probe Length: 1 m
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: ANSI



8479669 K

RS PRO TYPE K THERMOCOUPLE 2M LENGTH, 1/0.3MM DIAMETER →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1/0.3 mm
 - Probe Length: 2 m
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Cable
 - Cable Length: 2 m
 - Standards Met: ANSI



8479671 K

RS PRO TYPE K THERMOCOUPLE 1M LENGTH, 1/0.3MM DIAMETER →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1/0.3 mm
 - Probe Length: 1 m
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: ANSI



8479675 K

RS PRO TYPE K THERMOCOUPLE 1M LENGTH, → +250°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Length: 1 m
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: ANSI



8479678 K

RS PRO TYPE T THERMOCOUPLE 1M LENGTH, 1/0.3MM DIAMETER →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: T
 - Probe Diameter: 1/0.3 mm
 - Probe Length: 1 m
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: ANSI



8479681 T

RS PRO TYPE K THERMOCOUPLE 2M LENGTH, 1/0.3MM DIAMETER →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1/0.3 mm
 - Probe Length: 2 m
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Cable
 - Cable Length: 2 m
 - Standards Met: ANSI



8479684 K

ANSI T THERMOCOUPLE EXPOSED JUNCTION 2M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: T
 - Probe Diameter: 1/0.3 mm
 - Probe Length: 2 m
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Cable
 - Cable Length: 2 m
 - Standards Met: ANSI



8479687 T

RS PRO TYPE K THERMOCOUPLE 1M LENGTH, → +250°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Length: 1 m
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: ANSI



8479690 K

RS PRO TYPE K THERMOCOUPLE 2M LENGTH, 7/0.2MM DIAMETER →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 7/0.2 mm
 - Probe Length: 2 m
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Cable
 - Cable Length: 2 m
 - Standards Met: ANSI



8479693 K

RS PRO TYPE K THERMOCOUPLE 1/0.2MM DIAMETER → +250°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1/0.2 mm
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Cable
 - Cable Length: 5 m
 - Standards Met: ANSI



8479697 K

RS PRO TYPE K THERMOCOUPLE 5M LENGTH, 1/0.3MM DIAMETER →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1/0.3 mm
 - Probe Length: 5 m
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Cable
 - Cable Length: 5 m
 - Standards Met: ANSI



8479700 K

RS PRO TYPE T THERMOCOUPLE 1/0.3MM DIAMETER → +250°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: T
 - Probe Diameter: 1/0.3 mm
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Cable
 - Cable Length: 5 m
 - Standards Met: ANSI



8479704 T

RS PRO TYPE K THERMOCOUPLE 5M LENGTH, 1/0.3MM DIAMETER →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1/0.3 mm
 - Probe Length: 5 m
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Cable
 - Cable Length: 5 m
 - Standards Met: ANSI



8479707 K

RS PRO TYPE K THERMOCOUPLE 5M LENGTH, 1/0.3MM DIAMETER →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1/0.3 mm
 - Probe Length: 5 m
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Miniature Plug
 - Cable Length: 5 m
 - Standards Met: ANSI



8479710 K

RS PRO TYPE K THERMOCOUPLE 5M LENGTH, → +250°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Length: 5 m
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Cable
 - Cable Length: 5 m
 - Standards Met: ANSI



8479713 K

RS PRO TYPE K THERMOCOUPLE 5M LENGTH, 1/0.2MM DIAMETER →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1/0.2 mm
 - Probe Length: 5 m
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Miniature Plug
 - Cable Length: 5 m
 - Standards Met: ANSI



8479716 K

RS PRO TYPE T THERMOCOUPLE 5M LENGTH, → +250°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: T
 - Probe Length: 5 m
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Miniature Plug
 - Cable Length: 5 m
 - Standards Met: ANSI



8479722 T

RS PRO TYPE K THERMOCOUPLE 5M LENGTH, 7/0.2MM DIAMETER →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 7/0.2 mm
 - Probe Length: 5 m
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Miniature Plug
 - Cable Length: 5 m
 - Standards Met: ANSI



8479726 K

RS PRO TYPE K THERMOCOUPLE 5M LENGTH, 1/0.3MM DIAMETER →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 1/0.3 mm
 - Probe Length: 5 m
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Miniature Plug
 - Cable Length: 5 m
 - Standards Met: ANSI



8479729 K

RS PRO TYPE K THERMOCOUPLE 10M LENGTH, 1/0.3MM DIAMETER →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 1/0.3 mm
 - Probe Length: 10 m
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Cable
 - Cable Length: 10 m
 - Standards Met: ANSI



8479732 K

RS PRO TYPE K THERMOCOUPLE 10M LENGTH, 1/0.2MM DIAMETER →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 1/0.2 mm
 - Probe Length: 10 m
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Cable
 - Cable Length: 10 m
 - Standards Met: ANSI



8479735 K

RS PRO TYPE K THERMOCOUPLE 10M LENGTH, → +250°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Length: 10 m
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Cable
 - Cable Length: 10 m
 - Standards Met: ANSI



8479738 K

RS PRO TYPE T THERMOCOUPLE 10M LENGTH, → +250°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: T
 - Probe Length: 10 m
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Cable
 - Cable Length: 10 m
 - Standards Met: ANSI



8479741 T

RS PRO TYPE K THERMOCOUPLE 10M LENGTH, 7/0.2MM DIAMETER →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 7/0.2 mm
 - Probe Length: 10 m
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Cable
 - Cable Length: 10 m
 - Standards Met: ANSI



8479744 K

RS PRO TYPE K THERMOCOUPLE 10M LENGTH, → +250°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Length: 10 m
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Miniature Plug
 - Cable Length: 10 m
 - Standards Met: ANSI



8479748 K

RS PRO TYPE K THERMOCOUPLE 10M LENGTH, 1/0.3MM DIAMETER →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 1/0.3 mm
 - Probe Length: 10 m
 - Maximum Temperature Sensed: +350 °C
 - Termination Type: Miniature Plug
 - Cable Length: 10 m
 - Standards Met: ANSI



8479750 K

RS PRO TYPE T THERMOCOUPLE 10M LENGTH, → +250°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: T
 - Probe Length: 10 m
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Miniature Plug
 - Cable Length: 10 m
 - Standards Met: ANSI



8479754 T

RS PRO TYPE K THERMOCOUPLE 10M LENGTH, → +250°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Length: 10 m
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Miniature Plug
 - Cable Length: 10 m
 - Standards Met: ANSI



8479757 K

RS PRO TYPE K THERMOCOUPLE 10M LENGTH, → +250°C

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Length: 10 m
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Miniature Plug
 - Cable Length: 10 m
 - Standards Met: ANSI



8479763 K

TYPE K THERMOCOUPLE 2M BRAIDED CABLE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 3.18 mm
 - Probe Length: 25 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +350 °C
 - Termination Type: Cable
 - Cable Length: 2 m
 - Standards Met: IEC



8722503 K

TYPE K THERMOCOUPLE 2M BRAIDED CABLE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 3.18 mm
 - Probe Length: 13 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +350 °C
 - Termination Type: Cable
 - Cable Length: 2 m
 - Standards Met: IEC



8722509 K

RS PRO TYPE K THERMOCOUPLE 40MM LENGTH, 3.18MM DIAMETER →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 3.18 mm
 - Probe Length: 40 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +350 °C
 - Termination Type: Cable
 - Cable Length: 2 m
 - Standards Met: IEC



8722512 K

RS PRO TYPE J THERMOCOUPLE 25MM LENGTH, 4MM DIAMETER →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: J
 - Probe Diameter: 4 mm
 - Probe Length: 25 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +350 °C
 - Termination Type: Cable
 - Cable Length: 2 m
 - Standards Met: IEC



8722519 J

RS PRO TYPE K THERMOCOUPLE 13MM LENGTH, 4MM DIAMETER →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 4 mm
 - Probe Length: 13 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +350 °C
 - Termination Type: Cable
 - Cable Length: 2 m
 - Standards Met: IEC



8722521 K

TYPE K THERMOCOUPLE 2M BRAIDED CABLE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 4 mm
 - Probe Length: 25 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +350 °C
 - Termination Type: Cable
 - Cable Length: 2 m
 - Standards Met: IEC



8722525 K

TYPE J THERMOCOUPLE 2M BRAIDED CABLE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: J
 - Probe Diameter: 4 mm
 - Probe Length: 40 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +350 °C
 - Termination Type: Cable
 - Cable Length: 2 m
 - Standards Met: IEC



8722528 J

TYPE K THERMOCOUPLE 2M BRAIDED CABLE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 4 mm
 - Probe Length: 40 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +350 °C
 - Termination Type: Cable
 - Cable Length: 2 m
 - Standards Met: IEC



8722534 K

RS PRO TYPE J THERMOCOUPLE 40MM LENGTH, 4.76MM DIAMETER →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: J
 - Probe Diameter: 4.76 mm
 - Probe Length: 40 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +350 °C
 - Termination Type: Cable
 - Cable Length: 2 m
 - Standards Met: IEC



8722540 J

RS PRO TYPE J THERMOCOUPLE 75MM LENGTH, 4.76MM DIAMETER →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: J
 - Probe Diameter: 4.76 mm
 - Probe Length: 75 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +350 °C
 - Termination Type: Cable
 - Cable Length: 2 m
 - Standards Met: IEC



8722543 J

RS PRO TYPE J THERMOCOUPLE 100MM LENGTH, 4.76MM DIAMETER →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: J
 - Probe Diameter: 4.76 mm
 - Probe Length: 100 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +350 °C
 - Termination Type: Cable
 - Cable Length: 2 m
 - Standards Met: IEC



8722547 J

RS PRO TYPE K THERMOCOUPLE 40MM LENGTH, 4.76MM DIAMETER →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 4.76 mm
 - Probe Length: 40 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +350 °C
 - Termination Type: Cable
 - Cable Length: 2 m
 - Standards Met: IEC



8722553 K

RS PRO TYPE K THERMOCOUPLE 13MM LENGTH, 4.76MM DIAMETER →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 4.76 mm
 - Probe Length: 13 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +350 °C
 - Termination Type: Cable
 - Cable Length: 2 m
 - Standards Met: IEC



8722556 K

RS PRO TYPE K THERMOCOUPLE 25MM LENGTH, 4.76MM DIAMETER →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 4.76 mm
 - Probe Length: 25 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +350 °C
 - Termination Type: Cable
 - Cable Length: 2 m
 - Standards Met: IEC



8722559 K

RS PRO TYPE K THERMOCOUPLE 75MM LENGTH, 4.76MM DIAMETER →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 4.76 mm
 - Probe Length: 75 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +350 °C
 - Termination Type: Cable
 - Cable Length: 2 m
 - Standards Met: IEC



8722562 K

RS PRO TYPE K THERMOCOUPLE 100MM LENGTH, 4.76MM DIAMETER →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 4.76 mm
 - Probe Length: 100 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +350 °C
 - Termination Type: Cable
 - Cable Length: 2 m
 - Standards Met: IEC



8722565 K

RS PRO TYPE J THERMOCOUPLE 13MM LENGTH, M8 BOLT DIAMETER →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: J
 - Probe Diameter: M8 Bolt
 - Probe Length: 13 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Cable
 - Cable Length: 2 m
 - Standards Met: IEC



8722569 J

RS PRO TYPE J THERMOCOUPLE 25MM LENGTH, M8 BOLT DIAMETER →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: J
 - Probe Diameter: M8 Bolt
 - Probe Length: 25 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Cable
 - Cable Length: 2 m
 - Standards Met: IEC



8722581 K

RS PRO TYPE K THERMOCOUPLE 13MM LENGTH, M8 BOLT DIAMETER →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: M8 Bolt
 - Probe Length: 13 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Cable
 - Cable Length: 2 m
 - Standards Met: IEC



8722581 K

**RS PRO TYPE J THERMOCOUPLE
25MM LENGTH, M12 BOLT DIAMETER**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: J
 - Probe Diameter: M12 Bolt
 - Probe Length: 25 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Cable
 - Cable Length: 2 m
 - Standards Met: IEC



8722587 J

**RS PRO TYPE K THERMOCOUPLE
25MM LENGTH, M8 DIAMETER →**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: M8
 - Probe Length: 25 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Cable
 - Cable Length: 2 m
 - Standards Met: IEC



8722590 K

**RS PRO TYPE K THERMOCOUPLE
13MM LENGTH, M10 DIAMETER →**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: M10
 - Probe Length: 13 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Cable
 - Cable Length: 2 m
 - Standards Met: IEC



8722593 K

**RS PRO TYPE K THERMOCOUPLE
25MM LENGTH, M10 DIAMETER →**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: M10
 - Probe Length: 25 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Cable
 - Cable Length: 2 m
 - Standards Met: IEC



8722597 K

**RS PRO TYPE K THERMOCOUPLE 2M
LENGTH, 1/0.508MM DIAMETER →**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 1/0.508 mm
 - Probe Length: 2 m
 - Probe Material: Glass Fibre
 - Maximum Temperature Sensed: +350 °C
 - Termination Type: Miniature Plug
 - Cable Length: 2 m
 - Standards Met: IEC



8722604 K

**RS PRO TYPE K THERMOCOUPLE
13MM LENGTH, M12 BOLT DIAMETER →**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: M12 Bolt
 - Probe Length: 13 mm
 - Maximum Temperature Sensed: +250 °C
 - Probe Material: Stainless Steel
 - Termination Type: Cable
 - Cable Length: 2 m
 - Standards Met: IEC



8722607 K

**IEC G/F THERMOCOUPLE, MINI
PLUG, K, 10M**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 1/0.3 mm
 - Probe Length: 10 m
 - Probe Material: Glass Fibre
 - Maximum Temperature Sensed: +350 °C
 - Termination Type: Miniature Plug
 - Cable Length: 10 m
 - Standards Met: IEC



8722610 K

**RS PRO TYPE K THERMOCOUPLE
1/0.508MM DIAMETER → +350°C**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 1/0.508 mm
 - Maximum Temperature Sensed: +350 °C
 - Probe Material: Glass Fibre
 - Termination Type: Miniature Plug
 - Cable Length: 5 m
 - Standards Met: IEC



8722613 K

**IEC G/F THERMOCOUPLE, MINI
PLUG, K, 1M**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 1/0.3 mm
 - Maximum Temperature Sensed: +350 °C
 - Probe Material: Glass Fibre
 - Termination Type: Miniature Plug
 - Cable Length: 1 m
 - Standards Met: IEC



8722616 K

**RS PRO TYPE J THERMOCOUPLE 5M
LENGTH, → +350°C**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: J
 - Probe Length: 5 m
 - Maximum Temperature Sensed: +350 °C
 - Probe Material: Glass Fibre
 - Termination Type: Miniature Plug
 - Cable Length: 5 m
 - Standards Met: IEC



8722622 J

**RS PRO TYPE J THERMOCOUPLE 10M
LENGTH, 1/0.3MM DIAMETER →**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: J
 - Probe Diameter: 1/0.3 mm
 - Probe Length: 10 m
 - Probe Material: Glass Fibre
 - Maximum Temperature Sensed: +350 °C
 - Termination Type: Miniature Plug
 - Cable Length: 10 m
 - Standards Met: IEC



8722626 J

**RS PRO TYPE J THERMOCOUPLE 1M
LENGTH, → +350°C**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: J
 - Probe Length: 1 m
 - Maximum Temperature Sensed: +350 °C
 - Probe Material: Glass Fibre
 - Termination Type: Miniature Plug
 - Cable Length: 1 m
 - Standards Met: IEC



8722629 J

**RS PRO TYPE K THERMOCOUPLE
1/0.376MM DIAMETER → +250°C**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 1/0.376 mm
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Miniature Plug
 - Cable Length: 2 m
 - Standards Met: IEC



8722638 K

TYPE T THERMOCOUPLE + PLUG, 1M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: T
 - Probe Length: 1 m
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Miniature Plug
 - Cable Length: 1 m
 - Standards Met: IEC



8722644 T

**RS PRO TYPE T THERMOCOUPLE 2M
LENGTH, → +250°C**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: T
 - Probe Length: 2 m
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Miniature Plug
 - Cable Length: 2 m
 - Standards Met: IEC



8722648 T

**RS PRO TYPE T THERMOCOUPLE 10M
LENGTH, → +250°C**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: T
 - Probe Length: 10 m
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Miniature Plug
 - Cable Length: 10 m
 - Standards Met: IEC



8722650 T

RS PRO TYPE T THERMOCOUPLE 5M LENGTH, → +250°C

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: T
 - Probe Length: 5 m
 - Maximum Temperature Sensed: +250 °C
 - Termination Type: Miniature Plug
 - Cable Length: 5 m
 - Standards Met: IEC



8722657 T

TYPE K THERMOCOUPLE + PLUG & SOCKET

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1.5 mm
 - Probe Length: 300 mm
 - Maximum Temperature Sensed: +1100 °C
 - Probe Material: Stainless Steel
 - Termination Type: Miniature Plug
 - Standards Met: IEC



8722660 K

TYPE K THERMOCOUPLE + PLUG & SOCKET

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1 mm
 - Probe Length: 300 mm
 - Maximum Temperature Sensed: +750 °C
 - Probe Material: Stainless Steel
 - Termination Type: Miniature Plug
 - Standards Met: IEC



8722663 K

TYPE K THERMOCOUPLE + PLUG & SOCKET

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 3 mm
 - Probe Length: 150 mm
 - Maximum Temperature Sensed: +1100 °C
 - Probe Material: Stainless Steel
 - Termination Type: Miniature Plug
 - Standards Met: IEC



8722679 K

TYPE K THERMOCOUPLE + PLUG

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 4.5 mm
 - Probe Length: 750 mm
 - Maximum Temperature Sensed: +1100 °C
 - Probe Material: Stainless Steel
 - Termination Type: Standard Plug
 - Standards Met: IEC



8722682 K

TYPE K THERMOCOUPLE + PLUG

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 4.5 mm
 - Probe Length: 300 mm
 - Maximum Temperature Sensed: +1100 °C
 - Probe Material: Stainless Steel
 - Termination Type: Standard Plug
 - Standards Met: IEC



8722685 K

RS PRO TYPE K THERMOCOUPLE 2M LENGTH, 1/0.508MM DIAMETER →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1/0.508 mm
 - Probe Length: 2 m
 - Probe Material: Glass Fibre
 - Maximum Temperature Sensed: +350 °C
 - Termination Type: Cable
 - Cable Length: 2 m
 - Standards Met: IEC



8722795 K

RS PRO TYPE K THERMOCOUPLE 5M LENGTH, 1/0.508MM DIAMETER →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1/0.508 mm
 - Probe Length: 5 m
 - Probe Material: Glass Fibre
 - Maximum Temperature Sensed: +350 °C
 - Termination Type: Cable
 - Cable Length: 5 m
 - Standards Met: IEC



8722799 K

RS PRO TYPE J THERMOCOUPLE 25MM LENGTH, 3.18MM DIAMETER →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: J
 - Probe Diameter: 3.18 mm
 - Probe Length: 25 mm
 - Probe Material: Glass Fibre
 - Maximum Temperature Sensed: +350 °C
 - Termination Type: Cable
 - Cable Length: 2 m
 - Standards Met: IEC



8722802 J

RS PRO TYPE J THERMOCOUPLE 40MM LENGTH, 3.18MM DIAMETER →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: J
 - Probe Diameter: 3.18 mm
 - Probe Length: 40 mm
 - Probe Material: Glass Fibre
 - Maximum Temperature Sensed: +350 °C
 - Termination Type: Cable
 - Cable Length: 2 m
 - Standards Met: IEC



8722806 J

RS PRO TYPE J THERMOCOUPLE 13MM LENGTH, 3.18MM DIAMETER →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: J
 - Probe Diameter: 3.18 mm
 - Probe Length: 13 mm
 - Probe Material: Glass Fibre
 - Maximum Temperature Sensed: +350 °C
 - Termination Type: Cable
 - Cable Length: 2 m
 - Standards Met: IEC



8722809 J

RS PRO TYPE T THERMOCOUPLE 500MM LENGTH, 1MM DIAMETER,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: T
 - Probe Diameter: 1 mm
 - Probe Length: 500 mm
 - Maximum Temperature Sensed: +400 °C
 - Termination Type: Miniature Plug
 - Standards Met: IEC
 - Minimum Temperature Sensed: -100 °C



8919078 T

IEC TYPE T THERMOCOUPLE 1.0X150MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: T
 - Probe Diameter: 1 mm
 - Probe Length: 150 mm
 - Probe Material: 316 Stainless Steel
 - Maximum Temperature Sensed: +400 °C
 - Termination Type: Cable
 - Cable Length: 100 mm
 - Standards Met: IEC



8919090 T

RS PRO TYPE T THERMOCOUPLE 1M LENGTH, 1.5MM DIAMETER, -100°C →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: T
 - Probe Diameter: 1.5 mm
 - Probe Length: 1 m
 - Maximum Temperature Sensed: +400 °C
 - Termination Type: Miniature Plug
 - Standards Met: IEC
 - Minimum Temperature Sensed: -100 °C



8919097 T

RS PRO TYPE T THERMOCOUPLE 250MM LENGTH, 1.5MM DIAMETER →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: T
 - Probe Diameter: 1.5 mm
 - Probe Length: 250 mm
 - Probe Material: 316 Stainless Steel
 - Maximum Temperature Sensed: +400 °C
 - Termination Type: Cable
 - Cable Length: 100 mm
 - Standards Met: IEC



8919110 T

RS PRO TYPE T THERMOCOUPLE 500MM LENGTH, 1.5MM DIAMETER →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Thermocouple Type: T
 - Probe Diameter: 1.5 mm
 - Probe Length: 500 mm
 - Probe Material: 316 Stainless Steel
 - Maximum Temperature Sensed: +400 °C
 - Termination Type: Cable
 - Cable Length: 100 mm
 - Standards Met: IEC



8919113 T

**RS PRO TYPE T THERMOCOUPLE
150MM LENGTH, 3MM DIAMETER →**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: T
 - Probe Diameter: 3 mm
 - Probe Length: 150 mm
 - Probe Material: 316 Stainless Steel
 - Maximum Temperature Sensed: +400 °C
 - Termination Type: Cable
 - Cable Length: 100 mm
 - Standards Met: IEC



8919126 T

**THERMOCOUPLE 6X250 SLIDING
FITTING**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Thermocouple Type: K
 - Probe Diameter: 6 mm
 - Probe Length: 250 mm
 - Maximum Temperature Sensed: +1000 °C
 - Probe Material: Stainless Steel
 - Termination Type: Connection Head
 - Standards Met: RoHS Compliant
 - Response Time: <2 s



8968409 K

**SENSOR,PIEZO,CERAMIC,BI-
MORPH,VIBRATION**

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Switching Frequency: 100 Hz
 - Length: 15 mm
 - Width: 1.5 mm
 - Depth: 0.6 mm
 - Minimum Operating Temperature: -15 °C
 - Maximum Operating Temperature: +55 °C
 - Dimensions: 15 x 1.5 x 0.6 mm



285784 100 Hz

METER, PANEL, ANALOGUE, EDGE INDICATING, 100-0-100UA, NULL

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Maximum Value: 100 μ A
 - Cutout Width: 50 mm
 - Depth: 14 mm
 - Meter Accuracy: ± 20 %
 - Minimum Temperature: -10 °C
 - Maximum Temperature: $+55$ °C
 - Approvals: RoHS Compliant
 - Series: RS PRO



259549 100 μ A

METER, PANEL, ANALOGUE, EDGE INDICATING, 0-100UA, SCALE 0-10

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Maximum Value: 100 μ A
 - Cutout Width: 50 mm
 - Depth: 14 mm
 - Meter Accuracy: ± 20 %
 - Minimum Temperature: -10 °C
 - Maximum Temperature: $+55$ °C
 - Approvals: RoHS Compliant
 - Series: RS PRO



259561 100 μ A

RS PRO DIGITAL AMMETER AC, 43.5MM X 92MM, $\pm 0.5\%$ + 1 DIGIT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Current Type: AC
 - Cutout Height: 43.5 mm
 - Cutout Width: 92 mm
 - Depth: 68 mm
 - Meter Accuracy: $\pm 0.5\%$ + 1 Digit
 - Minimum Temperature: 0 °C
 - Maximum Temperature: $+50$ °C
 - Measurement Range: 1 \rightarrow 5 (Input) A



1365385 AC

RS PRO DIGITAL AMMETER AC, 92MM X 92MM, $\pm 0.5\%$ + 1 DIGIT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Current Type: AC
 - Cutout Height: 92 mm
 - Cutout Width: 92 mm
 - Depth: 55 mm
 - Meter Accuracy: $\pm 0.5\%$ + 1 Digit
 - Minimum Temperature: 0 °C
 - Maximum Temperature: $+50$ °C
 - Measurement Range: 1 \rightarrow 5 (Input) A



1365387 AC

RS PRO DIGITAL AMMETER AC, 43.5MM X 92MM, $\pm 0.5\%$ + 1 DIGIT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Current Type: AC
 - Cutout Height: 43.5 mm
 - Cutout Width: 92 mm
 - Depth: 68 mm
 - Meter Accuracy: $\pm 0.5\%$ + 1 Digit
 - Minimum Temperature: 0 °C
 - Maximum Temperature: $+50$ °C
 - Measurement Range: 1 \rightarrow 5 (Input) A



1365390 AC

RS PRO DIGITAL PANEL AMMETER, 90MM X 90MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Cutout Height: 90 mm
 - Cutout Width: 90 mm
 - Depth: 55 mm
 - Meter Accuracy: Class 1.0



1797573 90 mm

RS PRO DIGITAL AMMETER, 90MM X 90MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Cutout Height: 90 mm
 - Cutout Width: 90 mm
 - Depth: 55 mm
 - Meter Accuracy: Class 1.0



1797575 90 mm

RS PRO ANALOGUE PANEL AMMETER 5 (INPUT, SCALE) A AC, 45MM X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Maximum Value: 5 (Input, Scale) A
 - Current Type: AC
 - Moving Element: Moving Iron
 - Cutout Height: 45 mm
 - Cutout Width: 45 mm
 - Depth: 54 (<30 A) mm
 - Meter Accuracy: 1 %
 - Minimum Temperature: -10 °C



1862412 5 (Input, Scale) A

RS PRO ANALOGUE PANEL AMMETER 10 (INPUT, SCALE) A AC, 45MM X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Maximum Value: 10 (Input, Scale) A
 - Current Type: AC
 - Moving Element: Moving Iron
 - Cutout Height: 45 mm
 - Cutout Width: 45 mm
 - Depth: 54 (<30 A) mm
 - Meter Accuracy: 1 %
 - Minimum Temperature: -10 °C



1862413 10 (Input, Scale)

RS PRO ANALOGUE PANEL AMMETER 25 (INPUT, SCALE) A AC, 45MM X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Maximum Value: 25 (Input, Scale) A
 - Current Type: AC
 - Moving Element: Moving Iron
 - Cutout Height: 45 mm
 - Cutout Width: 45 mm
 - Depth: 54 (<30 A) mm
 - Meter Accuracy: 1 %
 - Minimum Temperature: -10 °C



1862414 25 (Input, Scale)

RS PRO ANALOGUE PANEL AMMETER 30 (INPUT, SCALE) A AC, 45MM X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Maximum Value: 30 (Input, Scale) A
 - Current Type: AC
 - Moving Element: Moving Iron
 - Cutout Height: 45 mm
 - Cutout Width: 45 mm
 - Depth: 54 (<30 A) mm, 72 (30 \rightarrow 60 A) mm
 - Meter Accuracy: 1 %
 - Minimum Temperature: -10 °C



1862415 30 (Input, Scale)

RS PRO ANALOGUE PANEL AMMETER 40 (INPUT, SCALE) A AC, 45MM X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Maximum Value: 40 (Input, Scale) A
 - Current Type: AC
 - Moving Element: Moving Iron
 - Cutout Height: 45 mm
 - Cutout Width: 45 mm
 - Depth: 54 (<30 A) mm, 72 (30 \rightarrow 60 A) mm
 - Meter Accuracy: 1 %
 - Minimum Temperature: -10 °C



1862416 40 (Input, Scale)

RS PRO ANALOGUE PANEL AMMETER 3 (INPUT, SCALE) A AC, 45MM X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Maximum Value: 3 (Input, Scale) A
 - Current Type: AC
 - Moving Element: Moving Iron
 - Cutout Height: 45 mm
 - Cutout Width: 45 mm
 - Depth: 54 (<30 A) mm
 - Meter Accuracy: 1 %
 - Minimum Temperature: -10 °C



1862417 3 (Input, Scale) A

RS PRO ANALOGUE PANEL AMMETER 10 (INPUT, SCALE) A AC, 45MM X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Maximum Value: 10 (Input, Scale) A
 - Current Type: AC
 - Moving Element: Moving Iron
 - Cutout Height: 45 mm
 - Cutout Width: 45 mm
 - Depth: 54 (<30 A) mm
 - Meter Accuracy: 1 %
 - Minimum Temperature: -10 °C



1862418 10 (Input, Scale)

RS PRO ANALOGUE PANEL AMMETER 10 (INPUT) A, 100 (SCALE) A, 50/5 (CT)

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Maximum Value: 10 (Input) A, 100 (Scale) A, 50/5 (CT) A
 - Current Type: AC
 - Moving Element: Moving Iron
 - Cutout Height: 45 mm
 - Cutout Width: 45 mm
 - Depth: 54 (<30 A) mm, 72 (30 \rightarrow 60 A) mm
 - Meter Accuracy: 1 %
 - Minimum Temperature: -10 °C



1862419 10 (Input) A, 100

RS PRO ANALOGUE PANEL AMMETER 10 (INPUT) A, 100/5 (CT) A, 200

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Maximum Value: 10 (Input) A, 100/5 (CT) A, 200 (Scale) A
 - Current Type: AC
 - Moving Element: Moving Iron
 - Cutout Height: 45 mm
 - Cutout Width: 45 mm
 - Depth: 54 (<30 A) mm, 72 (30 \rightarrow 60 A) mm
 - Meter Accuracy: 1 %
 - Minimum Temperature: -10 °C



1862420 10 (Input) A,

RS PRO ANALOGUE PANEL AMMETER 10 (INPUT) A, 250/5 (CT) A, 500

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Maximum Value: 10 (Input) A, 250/5 (CT) A, 500 (Scale) A
 - Current Type: AC
 - Moving Element: Moving Iron
 - Cutout Height: 45 mm
 - Cutout Width: 45 mm
 - Depth: 54 (<30 A) mm, 72 (30 → 60 A) mm
 - Meter Accuracy: 1 %
 - Minimum Temperature: -10 °C


1862421 10 (Input) A,

RS PRO ANALOGUE PANEL AMMETER 20 (INPUT) A AC, 45MM X 45MM, 1 %

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Maximum Value: 20 (Input) A
 - Current Type: AC
 - Moving Element: Moving Iron
 - Cutout Height: 45 mm
 - Cutout Width: 45 mm
 - Depth: 54 (<30 A) mm
 - Meter Accuracy: 1 %
 - Minimum Temperature: -10 °C


1862422 20 (Input) A

RS PRO ANALOGUE PANEL AMMETER 30 (INPUT) A AC, 45MM X 45MM, 1 %

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Maximum Value: 30 (Input) A
 - Current Type: AC
 - Moving Element: Moving Iron
 - Cutout Height: 45 mm
 - Cutout Width: 45 mm
 - Depth: 54 (<30 A) mm, 72 (30 → 60 A) mm
 - Meter Accuracy: 1 %
 - Minimum Temperature: -10 °C


1862423 30 (Input) A

RS PRO ANALOGUE PANEL AMMETER 50 (INPUT) A AC, 45MM X 45MM, 1 %

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Maximum Value: 50 (Input) A
 - Current Type: AC
 - Moving Element: Moving Iron
 - Cutout Height: 45 mm
 - Cutout Width: 45 mm
 - Depth: 54 (<30 A) mm, 72 (30 → 60 A) mm
 - Meter Accuracy: 1 %
 - Minimum Temperature: -10 °C


1862425 50 (Input) A

RS PRO ANALOGUE PANEL AMMETER 100 (SCALE) A, 100/5 (CT) A, 5 (INPUT)

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Maximum Value: 100 (Scale) A, 100/5 (CT) A, 5 (Input) A
 - Current Type: AC
 - Moving Element: Moving Iron
 - Cutout Height: 68 mm
 - Cutout Width: 68 mm
 - Depth: 54 (<30 A) mm, 62 (30 → 60 A) mm, 66 (100 A) mm
 - Meter Accuracy: 1 %
 - Minimum Temperature: -10 °C


1862435 100 (Scale) A,

RS PRO ANALOGUE PANEL AMMETER 150 (SCALE) A, 150/5 (CT) A, 5 (INPUT)

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Maximum Value: 150 (Scale) A, 150/5 (CT) A, 5 (Input) A
 - Current Type: AC
 - Moving Element: Moving Iron
 - Cutout Height: 68 mm
 - Cutout Width: 68 mm
 - Depth: 54 (<30 A) mm, 62 (30 → 60 A) mm, 66 (100 A) mm
 - Meter Accuracy: 1 %
 - Minimum Temperature: -10 °C


1862436 150 (Scale) A,

RS PRO ANALOGUE PANEL AMMETER 200 (SCALE) A, 200/5 (CT) A, 5 (INPUT)

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Maximum Value: 200 (Scale) A, 200/5 (CT) A, 5 (Input) A
 - Current Type: AC
 - Moving Element: Moving Iron
 - Cutout Height: 68 mm
 - Cutout Width: 68 mm
 - Depth: 54 (<30 A) mm, 62 (30 → 60 A) mm, 66 (100 A) mm
 - Meter Accuracy: 1 %
 - Minimum Temperature: -10 °C


1862437 200 (Scale) A,

RS PRO ANALOGUE PANEL AMMETER 10 (INPUT) A AC, 68MM X 68MM, 1 %

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Maximum Value: 10 (Input) A
 - Current Type: AC
 - Moving Element: Moving Iron
 - Cutout Height: 68 mm
 - Cutout Width: 68 mm
 - Depth: 54 (<30 A) mm
 - Meter Accuracy: 1 %
 - Minimum Temperature: -10 °C


1862438 10 (Input) A

RS PRO ANALOGUE PANEL AMMETER 25 (INPUT) A AC, 68MM X 68MM, 1 %

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Maximum Value: 25 (Input) A
 - Current Type: AC
 - Moving Element: Moving Iron
 - Cutout Height: 68 mm
 - Cutout Width: 68 mm
 - Depth: 54 (<30 A) mm
 - Meter Accuracy: 1 %
 - Minimum Temperature: -10 °C


1862439 25 (Input) A

RS PRO ANALOGUE PANEL AMMETER 60 (INPUT) A AC, 68MM X 68MM, 1 %

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Maximum Value: 60 (Input) A
 - Current Type: AC
 - Moving Element: Moving Iron
 - Cutout Height: 68 mm
 - Cutout Width: 68 mm
 - Depth: 54 (<30 A) mm, 62 (30 → 60 A) mm
 - Meter Accuracy: 1 %
 - Minimum Temperature: -10 °C


1862440 60 (Input) A

RS PRO ANALOGUE PANEL AMMETER 3 (INPUT) A AC, 68MM X 68MM, 1 %

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Maximum Value: 3 (Input) A
 - Current Type: AC
 - Moving Element: Moving Iron
 - Cutout Height: 68 mm
 - Cutout Width: 68 mm
 - Depth: 54 (<30 A) mm
 - Meter Accuracy: 1 %
 - Minimum Temperature: -10 °C


1862441 3 (Input) A

RS PRO ANALOGUE PANEL AMMETER 10 (INPUT) A, 100 (SCALE) A, 50/5 (CT)

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Maximum Value: 10 (Input) A, 100 (Scale) A, 50/5 (CT) A
 - Current Type: AC
 - Moving Element: Moving Iron
 - Cutout Height: 68 mm
 - Cutout Width: 68 mm
 - Depth: 54 (<30 A) mm, 62 (30 → 60 A) mm, 66 (100 A) mm
 - Meter Accuracy: 1 %
 - Minimum Temperature: -10 °C


1862443 10 (Input) A, 100

RS PRO ANALOGUE PANEL AMMETER 10 (INPUT) A, 100/5 (CT) A, 200

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Maximum Value: 10 (Input) A, 100/5 (CT) A, 200 (Scale) A
 - Current Type: AC
 - Moving Element: Moving Iron
 - Cutout Height: 68 mm
 - Cutout Width: 68 mm
 - Depth: 54 (<30 A) mm, 62 (30 → 60 A) mm, 66 (100 A) mm
 - Meter Accuracy: 1 %
 - Minimum Temperature: -10 °C


1862444 10 (Input) A,

RS PRO ANALOGUE PANEL AMMETER 10 (INPUT) A, 200/5 (CT) A, 400

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Maximum Value: 10 (Input) A, 200/5 (CT) A, 400 (Scale) A
 - Current Type: AC
 - Moving Element: Moving Iron
 - Cutout Height: 68 mm
 - Cutout Width: 68 mm
 - Depth: 54 (<30 A) mm, 62 (30 → 60 A) mm, 66 (100 A) mm
 - Meter Accuracy: 1 %
 - Minimum Temperature: -10 °C


1862445 10 (Input) A,

RS PRO ANALOGUE PANEL AMMETER 10 (INPUT) A, 250/5 (CT) A, 500

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Maximum Value: 10 (Input) A, 250/5 (CT) A, 500 (Scale) A
 - Current Type: AC
 - Moving Element: Moving Iron
 - Cutout Height: 68 mm
 - Cutout Width: 68 mm
 - Depth: 54 (<30 A) mm, 62 (30 → 60 A) mm, 66 (100 A) mm
 - Meter Accuracy: 1 %
 - Minimum Temperature: -10 °C


1862446 10 (Input) A,

RS PRO ANALOGUE PANEL AMMETER 20 (INPUT) A AC, 68MM X 68MM, 1 %

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Maximum Value: 20 (Input) A
 - Current Type: AC
 - Moving Element: Moving Iron
 - Cutout Height: 68 mm
 - Cutout Width: 68 mm
 - Depth: 54 (<30 A) mm
 - Meter Accuracy: 1 %
 - Minimum Temperature: -10 °C


1862447 20 (Input) A

RS PRO ANALOGUE PANEL AMMETER 50 (INPUT)A AC, 68MM X 68MM, 1 %

- ขนาดบรรจุภัณฑ์: 1 x EA
- Maximum Value: 50 (Input) A
 - Current Type: AC
 - Moving Element: Moving Iron
 - Cutout Height: 68 mm
 - Cutout Width: 68 mm
 - Depth: 54 (<30 A) mm, 62 (30 → 60 A) mm
 - Meter Accuracy: 1 %
 - Minimum Temperature: -10 °C



1862451 50 (Input) A

RS PRO ANALOGUE PANEL AMMETER 80 (INPUT)A AC, 68MM X 68MM, 1 %

- ขนาดบรรจุภัณฑ์: 1 x EA
- Maximum Value: 80 (Input) A
 - Current Type: AC
 - Moving Element: Moving Iron
 - Cutout Height: 68 mm
 - Cutout Width: 68 mm
 - Depth: 54 (<30 A) mm, 62 (30 → 60 A) mm, 66 (100 A) mm
 - Meter Accuracy: 1 %
 - Minimum Temperature: -10 °C



1862453 80 (Input) A

RS PRO ANALOGUE PANEL AMMETER 5 (INPUT, SCALE)A AC, 92MM X 92MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Maximum Value: 5 (Input, Scale) A
 - Current Type: AC
 - Moving Element: Moving Iron
 - Cutout Height: 92 mm
 - Cutout Width: 92 mm
 - Depth: 54 (<30 A) mm
 - Meter Accuracy: 1 %
 - Minimum Temperature: -10 °C



1862458 5 (Input, Scale) A

RS PRO ANALOGUE PANEL AMMETER 10 (INPUT)A AC, 92MM X 92MM, 1 %

- ขนาดบรรจุภัณฑ์: 1 x EA
- Maximum Value: 10 (Input) A
 - Current Type: AC
 - Moving Element: Moving Iron
 - Cutout Height: 92 mm
 - Cutout Width: 92 mm
 - Depth: 54 (<30 A) mm
 - Meter Accuracy: 1 %
 - Minimum Temperature: -10 °C



1862459 10 (Input) A

RS PRO ANALOGUE PANEL AMMETER 25 (INPUT)A AC, 92MM X 92MM, 1 %

- ขนาดบรรจุภัณฑ์: 1 x EA
- Maximum Value: 25 (Input) A
 - Current Type: AC
 - Moving Element: Moving Iron
 - Cutout Height: 92 mm
 - Cutout Width: 92 mm
 - Depth: 54 (<30 A) mm
 - Meter Accuracy: 1 %
 - Minimum Temperature: -10 °C



1862460 25 (Input) A

RS PRO ANALOGUE PANEL AMMETER 10 (INPUT, SCALE)A AC, 92MM X 92MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Maximum Value: 10 (Input, Scale) A
 - Current Type: AC
 - Moving Element: Moving Iron
 - Cutout Height: 92 mm
 - Cutout Width: 92 mm
 - Depth: 54 (<30 A) mm
 - Meter Accuracy: 1 %
 - Minimum Temperature: -10 °C



1862462 10 (Input, Scale)

RS PRO ANALOGUE PANEL AMMETER 10 (INPUT) A, 100 (SCALE) A, 50/5 (CT)

- ขนาดบรรจุภัณฑ์: 1 x EA
- Maximum Value: 10 (Input) A, 100 (Scale) A, 50/5 (CT)
 - Current Type: AC
 - Moving Element: Moving Iron
 - Cutout Height: 92 mm
 - Cutout Width: 92 mm
 - Depth: 54 (<30 A) mm, 62 (30 → 60 A) mm, 66 (100 A) mm
 - Meter Accuracy: 1 %
 - Minimum Temperature: -10 °C



1862463 10 (Input) A, 100

RS PRO ANALOGUE PANEL AMMETER 20 (INPUT)A AC, 92MM X 92MM, 1 %

- ขนาดบรรจุภัณฑ์: 1 x EA
- Maximum Value: 20 (Input) A
 - Current Type: AC
 - Moving Element: Moving Iron
 - Cutout Height: 92 mm
 - Cutout Width: 92 mm
 - Depth: 54 (<30 A) mm
 - Meter Accuracy: 1 %
 - Minimum Temperature: -10 °C



1862464 20 (Input) A

RS PRO ANALOGUE PANEL AMMETER 30 (INPUT)A AC, 92MM X 92MM, 1 %

- ขนาดบรรจุภัณฑ์: 1 x EA
- Maximum Value: 30 (Input) A
 - Current Type: AC
 - Moving Element: Moving Iron
 - Cutout Height: 92 mm
 - Cutout Width: 92 mm
 - Depth: 54 (<30 A) mm, 62 (30 → 60 A) mm
 - Meter Accuracy: 1 %
 - Minimum Temperature: -10 °C



1862465 30 (Input) A

RS PRO ANALOGUE PANEL AMMETER 40 (INPUT)A AC, 92MM X 92MM, 1 %

- ขนาดบรรจุภัณฑ์: 1 x EA
- Maximum Value: 40 (Input) A
 - Current Type: AC
 - Moving Element: Moving Iron
 - Cutout Height: 92 mm
 - Cutout Width: 92 mm
 - Depth: 54 (<30 A) mm, 62 (30 → 60 A) mm
 - Meter Accuracy: 1 %
 - Minimum Temperature: -10 °C



1862466 40 (Input) A

RS PRO ANALOGUE PANEL AMMETER 50 (INPUT)A AC, 92MM X 92MM, 1 %

- ขนาดบรรจุภัณฑ์: 1 x EA
- Maximum Value: 50 (Input) A
 - Current Type: AC
 - Moving Element: Moving Iron
 - Cutout Height: 92 mm
 - Cutout Width: 92 mm
 - Depth: 54 (<30 A) mm, 62 (30 → 60 A) mm
 - Meter Accuracy: 1 %
 - Minimum Temperature: -10 °C



1862467 50 (Input) A

RS PRO ANALOGUE PANEL AMMETER 20 (INPUT)MA DC, 45MM X 45MM, 1 %

- ขนาดบรรจุภัณฑ์: 1 x EA
- Maximum Value: 20 (Input) mA
 - Current Type: DC
 - Moving Element: Moving Coil
 - Cutout Height: 45 mm
 - Cutout Width: 45 mm
 - Depth: 54 (<30 A) mm
 - Meter Accuracy: 1 %
 - Minimum Temperature: -10 °C



1862475 20 (Input) mA

RS PRO ANALOGUE PANEL AMMETER DC, 45MM X 45MM, 1 % MOVING

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Type: DC
 - Moving Element: Moving Coil
 - Cutout Height: 45 mm
 - Cutout Width: 45 mm
 - Depth: 54 (<30 A) mm, 72 (30 → 60 A) mm
 - Meter Accuracy: 1 %
 - Minimum Temperature: -10 °C
 - Maximum Temperature: +65 °C



1862477 DC

RS PRO ANALOGUE PANEL AMMETER DC, 45MM X 45MM, 1 % MOVING

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Type: DC
 - Moving Element: Moving Coil
 - Cutout Height: 45 mm
 - Cutout Width: 45 mm
 - Depth: 54 (<30 A) mm, 72 (30 → 60 A) mm
 - Meter Accuracy: 1 %
 - Minimum Temperature: -10 °C
 - Maximum Temperature: +65 °C



1862478 DC

RS PRO ANALOGUE PANEL AMMETER DC, 45MM X 45MM, 1 % MOVING

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Type: DC
 - Moving Element: Moving Coil
 - Cutout Height: 45 mm
 - Cutout Width: 45 mm
 - Depth: 54 (<30 A) mm, 72 (30 → 60 A) mm
 - Meter Accuracy: 1 %
 - Minimum Temperature: -10 °C
 - Maximum Temperature: +65 °C



1862479 DC

RS PRO ANALOGUE PANEL AMMETER DC, 45MM X 45MM, 1 % MOVING

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Type: DC
 - Moving Element: Moving Coil
 - Cutout Height: 45 mm
 - Cutout Width: 45 mm
 - Depth: 54 (<30 A) mm, 72 (30 → 60 A) mm
 - Meter Accuracy: 1 %
 - Minimum Temperature: -10 °C
 - Maximum Temperature: +65 °C



1862483 DC

RS PRO ANALOGUE PANEL AMMETER DC, 92MM X 92MM, 1% MOVING

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Type: DC
 - Moving Element: Moving Coil
 - Cutout Height: 92 mm
 - Cutout Width: 92 mm
 - Depth: 54 (-4 A) mm, 67 (5 → 60 A) mm, 67 (60 → 100 A) mm
 - Meter Accuracy: 1%
 - Minimum Temperature: -10 °C
 - Maximum Temperature: +65 °C



1862511 DC

RS PRO ANALOGUE PANEL AMMETER DC, 92MM X 92MM, 1% MOVING

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Type: DC
 - Moving Element: Moving Coil
 - Cutout Height: 92 mm
 - Cutout Width: 92 mm
 - Depth: 54 (-4 A) mm, 67 (5 → 60 A) mm, 67 (60 → 100 A) mm
 - Meter Accuracy: 1%
 - Minimum Temperature: -10 °C
 - Maximum Temperature: +65 °C



1862513 DC

RS PRO ANALOGUE PANEL AMMETER 80 (INPUT)A AC, 76MM X 74MM, ±1.5

- ขนาดบรรจุภัณฑ์: 1 x EA
- Maximum Value: 80 (Input) A
 - Current Type: AC
 - Cutout Height: 76 mm
 - Cutout Width: 74 mm
 - Depth: 45.7 mm
 - Meter Accuracy: ±1.5 %
 - Minimum Temperature: 0 °C
 - Maximum Temperature: +60 °C



1862517 80 (Input) A

RS PRO ANALOGUE PANEL AMMETER 1 (INPUT)A DC, 76MM X 74MM, ±1.5 %

- ขนาดบรรจุภัณฑ์: 1 x EA
- Maximum Value: 1 (Input) A
 - Current Type: DC
 - Moving Element: Moving Coil
 - Cutout Height: 76 mm
 - Cutout Width: 74 mm
 - Depth: 45.7 mm
 - Meter Accuracy: ±1.5 %
 - Minimum Temperature: 0 °C



1862527 1 (Input) A

RS PRO ANALOGUE PANEL AMMETER 5 (INPUT)A DC, 76MM X 74MM, ±1.5 %

- ขนาดบรรจุภัณฑ์: 1 x EA
- Maximum Value: 5 (Input) A
 - Current Type: DC
 - Moving Element: Moving Coil
 - Cutout Height: 76 mm
 - Cutout Width: 74 mm
 - Depth: 45.7 mm
 - Meter Accuracy: ±1.5 %
 - Minimum Temperature: 0 °C



1862528 5 (Input) A

RS PRO ANALOGUE PANEL AMMETER 10 (INPUT)A DC, 76MM X 74MM, ±1.5

- ขนาดบรรจุภัณฑ์: 1 x EA
- Maximum Value: 10 (Input) A
 - Current Type: DC
 - Moving Element: Moving Coil
 - Cutout Height: 76 mm
 - Cutout Width: 74 mm
 - Depth: 45.7 mm
 - Meter Accuracy: ±1.5 %
 - Minimum Temperature: 0 °C



1862529 10 (Input) A

RS PRO ANALOGUE PANEL AMMETER 50 (INPUT)A DC, 76MM X 74MM, ±1.5

- ขนาดบรรจุภัณฑ์: 1 x EA
- Maximum Value: 50 (Input) A
 - Current Type: DC
 - Moving Element: Moving Coil
 - Cutout Height: 76 mm
 - Cutout Width: 74 mm
 - Depth: 45.7 mm
 - Meter Accuracy: ±1.5 %
 - Minimum Temperature: 0 °C



1862530 50 (Input) A

RS PRO ANALOGUE PANEL AMMETER DC, 76MM X 74MM, ±1.5 % MOVING

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Type: DC
 - Moving Element: Moving Coil
 - Cutout Height: 76 mm
 - Cutout Width: 74 mm
 - Depth: 45.7 mm
 - Meter Accuracy: ±1.5 %
 - Minimum Temperature: 0 °C
 - Maximum Temperature: +60 °C



1862531 DC

RS PRO ANALOGUE PANEL AMMETER DC, 57MM X 44MM, ±1.5 % MOVING

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Type: DC
 - Moving Element: Moving Coil
 - Cutout Height: 57 mm
 - Cutout Width: 44 mm
 - Depth: 45.7 mm
 - Meter Accuracy: ±1.5 %
 - Minimum Temperature: 0 °C
 - Maximum Temperature: +60 °C



1862533 DC

RS PRO ANALOGUE PANEL AMMETER DC, 57MM X 44MM, ±1.5 % MOVING

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Type: DC
 - Moving Element: Moving Coil
 - Cutout Height: 57 mm
 - Cutout Width: 44 mm
 - Depth: 45.7 mm
 - Meter Accuracy: ±1.5 %
 - Minimum Temperature: 0 °C
 - Maximum Temperature: +60 °C



1862534 DC

RS PRO ANALOGUE PANEL AMMETER 50 (INPUT)MA DC, 57MM X 44MM,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Maximum Value: 50 (Input) mA
 - Current Type: DC
 - Moving Element: Moving Coil
 - Cutout Height: 57 mm
 - Cutout Width: 44 mm
 - Depth: 45.7 mm
 - Meter Accuracy: ±1.5 %
 - Minimum Temperature: 0 °C



1862535 50 (Input) mA

RS PRO ANALOGUE PANEL AMMETER 100 (INPUT)MA DC, 57MM X 44MM,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Maximum Value: 100 (Input) mA
 - Current Type: DC
 - Moving Element: Moving Coil
 - Cutout Height: 57 mm
 - Cutout Width: 44 mm
 - Depth: 45.7 mm
 - Meter Accuracy: ±1.5 %
 - Minimum Temperature: 0 °C



1862536 100 (Input) mA

RS PRO DIGITAL AMMETER

- ขนาดบรรจุภัณฑ์: 1 x EA
- Depth: 66 mm
 - Minimum Temperature: -20 °C
 - Maximum Temperature: +60 °C
 - Measurement Range: 4 → 20 mA



1883473 66 mm

AC AMMETER 48X48 90 DEG 0-20/40A

- ขนาดบรรจุภัณฑ์: 1 x EA
- Maximum Value: 20 A
 - Current Type: AC
 - Moving Element: Moving Iron
 - Cutout Height: 46 mm
 - Cutout Width: 46 mm
 - Depth: 39 mm
 - Meter Accuracy: ±1.5 %
 - Minimum Temperature: -25 °C



9010330 20 A

AC AMMETER 48X48 90 DEG 0-10/20A

- ขนาดบรรจุภัณฑ์: 1 x EA
- Maximum Value: 10 A
 - Current Type: AC
 - Moving Element: Moving Iron
 - Cutout Height: 46 mm
 - Cutout Width: 46 mm
 - Depth: 39 mm
 - Meter Accuracy: ±1.5 %
 - Minimum Temperature: -25 °C



9010337 10 A

AC AMMETER 72X72 90 DEG 0-20/40A

- ขนาดบรรจุภัณฑ์: 1 x EA
- Maximum Value: 40 A
 - Current Type: AC
 - Moving Element: Moving Iron
 - Cutout Height: 68 mm
 - Cutout Width: 68 mm
 - Depth: 59 mm
 - Meter Accuracy: ±1.5 %
 - Minimum Temperature: -25 °C



9010340 40 A

**RS PRO ANALOGUE PANEL AMMETER
5A AC, 68MM X 68MM, ±1.5 %**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Maximum Value: 5 A
 - Current Type: AC
 - Moving Element: Moving Iron
 - Cutout Height: 68 mm
 - Cutout Width: 68 mm
 - Depth: 36.5 mm
 - Meter Accuracy: ±1.5 %
 - Minimum Temperature: -25 °C



9010343 5 A

AC AMMETER 72X72 90 DEG 0-10/20A

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Maximum Value: 10 A
 - Current Type: AC
 - Moving Element: Moving Iron
 - Cutout Height: 68 mm
 - Cutout Width: 68 mm
 - Depth: 36.5 mm
 - Meter Accuracy: ±1.5 %
 - Minimum Temperature: -25 °C



9010346 10 A

AC AMMETER 96X96 90 DEG 0-10/20A

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Maximum Value: 10 A
 - Current Type: AC
 - Moving Element: Moving Iron
 - Cutout Height: 92 mm
 - Cutout Width: 92 mm
 - Depth: 45 mm
 - Meter Accuracy: ±1.5 %
 - Minimum Temperature: -25 °C



9010356 10 A

AC AMMETER 72X72 90 DEG 0-30/60A

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Maximum Value: 30 A
 - Current Type: AC
 - Moving Element: Moving Iron
 - Cutout Height: 68 mm
 - Cutout Width: 68 mm
 - Depth: 36.5 mm
 - Meter Accuracy: ±1.5 %
 - Minimum Temperature: -25 °C



9010359 30 A

**RS PRO ANALOGUE PANEL AMMETER
40A AC, 92MM X 92MM, ±1.5 %**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Maximum Value: 40 A
 - Current Type: AC
 - Moving Element: Moving Iron
 - Cutout Height: 92 mm
 - Cutout Width: 92 mm
 - Depth: 45 mm
 - Meter Accuracy: ±1.5 %
 - Minimum Temperature: -25 °C



9010365 40 A

**RS PRO ANALOGUE PANEL AMMETER
30A AC, 92MM X 92MM, ±1.5 %**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Maximum Value: 30 A
 - Current Type: AC
 - Moving Element: Moving Iron
 - Cutout Height: 92 mm
 - Cutout Width: 92 mm
 - Depth: 45 mm
 - Meter Accuracy: ±1.5 %
 - Minimum Temperature: -25 °C



9010368 30 A

4 DIGIT HAND HELD TALLY COUNTER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Count Mode: Pulse
 - Display Type: Mechanical
 - Input Type: Manual
 - Reset Method: Manual
 - Number of Digits: 4
 - Mounting Type: Surface Mount
 - Count Direction: Up
 - Digit Height: 4 mm



7105212 Pulse

4 DIGIT DESK MOUNTED TALLY COUNTER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Count Mode: Pulse
 - Display Type: Mechanical
 - Input Type: Manual
 - Reset Method: Manual
 - Number of Digits: 4
 - Mounting Type: Surface Mount
 - Count Direction: Up
 - Digit Height: 4 mm



7105216 Pulse

5 DIGIT LHS SHAFT MECH STROKE COUNTER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Count Mode: Impulses
 - Display Type: Mechanical
 - Input Type: Manual
 - Reset Method: Manual
 - Number of Digits: 5
 - Mounting Type: Screw Clamp
 - Count Direction: Up
 - Digit Height: 4.8 mm



7105219 Impulses

4 DIGIT BANK OF 4 TALLY COUNTER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Display Type: Mechanical
 - Input Type: Manual
 - Reset Method: Manual
 - Number of Digits: 4
 - Mounting Type: Surface Mount
 - Count Direction: Up
 - Digit Height: 4 mm
 - Cutout Width: 1350 mm



7105225 Mechanical

5 DIGIT RHS SHAFT MECH STROKE COUNTER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Count Mode: Impulses
 - Display Type: Mechanical
 - Input Type: Manual
 - Reset Method: Manual
 - Number of Digits: 5
 - Mounting Type: Screw Clamp
 - Count Direction: Up
 - Digit Height: 4.8 mm



7105228 Impulses

**RS PRO COUNTER COUNTER, 6 DIGIT,
20KHZ, 230 V AC**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 230 V ac
 - Count Mode: Seconds
 - Display Type: LED
 - Input Type: Transistor
 - Connection Type: Flying Lead
 - Reset Method: Automatic, Manual
 - Number of Digits: 6
 - Mounting Type: Panel Mount



8086605 230 V ac

COUNTER, 6 DIGIT, 48X48, 24V

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 24 V
 - Count Mode: Pulse
 - Display Type: LED
 - Input Type: Transistor
 - Connection Type: Flying Lead
 - Reset Method: Automatic, Manual
 - Number of Digits: 6
 - Mounting Type: Panel Mount



8086614 24 V

**RS PRO COUNTER COUNTER, 6 DIGIT,
20KHZ, 230 V AC**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 230 V ac
 - Count Mode: Seconds
 - Display Type: LED
 - Input Type: Transistor
 - Connection Type: Flying Lead
 - Reset Method: Automatic, Manual
 - Number of Digits: 6
 - Mounting Type: Panel Mount



8086617 230 V ac

COUNTER, 6 DIGIT, 96X48, 230V

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 230 V ac
 - Count Mode: Impulses
 - Display Type: LED
 - Input Type: Transistor
 - Connection Type: Screw Clamp
 - Reset Method: Automatic, Manual
 - Number of Digits: 6
 - Mounting Type: Panel Mount



8086627 230 V ac

**RS PRO COUNTER COUNTER, 6 DIGIT,
20KHZ, 24 V**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 24 V
 - Count Mode: Impulses
 - Display Type: LED
 - Input Type: Transistor
 - Connection Type: Flying Lead
 - Reset Method: Automatic, Manual
 - Number of Digits: 6
 - Mounting Type: Panel Mount



8086633 24 V

COUNTER, 6 DIGIT, 96X48, 24V

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 24 V
 - Count Mode: Impulses
 - Display Type: LED
 - Input Type: Transistor
 - Connection Type: Flying Lead
 - Reset Method: Automatic, Manual
 - Number of Digits: 6
 - Mounting Type: Panel Mount



8086636 24 V

RS PRO COUNTER, 6 DIGIT, 20KHZ, 230 V AC

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 230 V ac
 - Count Mode: Seconds
 - Display Type: LED
 - Input Type: Transistor
 - Connection Type: Flying Lead
 - Reset Method: Automatic, Manual
 - Number of Digits: 6
 - Mounting Type: Panel Mount



8086639 230 V ac

RS PRO COUNTER, PROGRAMMABLE TIMER COUNTER, 6 DIGIT, 6KHZ, 100

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 100 → 240 V ac
 - Count Mode: Seconds
 - Display Type: LED
 - Input Type: NPN, PNP
 - Connection Type: Terminal
 - Reset Method: Automatic, Manual
 - Number of Digits: 6
 - Mounting Type: Panel Mount



8751309 100 → 240 V ac

RS PRO COUNTER, PROGRAMMABLE TIMER COUNTER, 6 DIGIT, 6KHZ, 24 V

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 24 V ac/dc
 - Count Mode: Seconds
 - Display Type: LED
 - Input Type: NPN, PNP
 - Connection Type: Terminal
 - Reset Method: Automatic, Manual
 - Number of Digits: 6
 - Mounting Type: Panel Mount



8751318 24 V ac/dc

HOURS RUN METER 48 X 48MM 90-264VAC

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 90 → 264 V ac
 - Count Mode: Hours
 - Display Type: Analogue
 - Input Type: Voltage
 - Connection Type: Spade Terminal
 - Reset Method: No Reset
 - Number of Digits: 6
 - Mounting Type: Panel Mount



8966894 90 → 264 V ac

RS PRO HOUR METER COUNTER, 6 DIGIT, 50HZ, 10 → 80 V DC

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 10 → 80 V dc
 - Count Mode: Hours
 - Display Type: Analogue
 - Input Type: Voltage
 - Connection Type: Spade Terminal
 - Reset Method: No Reset
 - Number of Digits: 6
 - Mounting Type: Panel Mount



8966898 10 → 80 V dc

RS PRO HOUR METER COUNTER, 6 DIGIT, 50HZ, 90 → 264 V AC

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 90 → 264 V ac
 - Count Mode: Hours
 - Display Type: Analogue
 - Input Type: Voltage
 - Connection Type: Spade Terminal
 - Reset Method: No Reset
 - Number of Digits: 6
 - Mounting Type: Panel Mount



8966905 90 → 264 V ac

HOURS RUN METER 3 HOLE FIXING 10-80VDC

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 10 → 80 V dc
 - Count Mode: Hours
 - Display Type: Analogue
 - Input Type: Voltage
 - Connection Type: Spade Terminal
 - Reset Method: No Reset
 - Number of Digits: 6
 - Mounting Type: Panel Mount



8966911 10 → 80 V dc

RS PRO HOUR METER COUNTER, 6 DIGIT, 50HZ, 10 → 80 V DC

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 10 → 80 V dc
 - Count Mode: Hours
 - Display Type: Analogue
 - Input Type: Voltage
 - Connection Type: Spade Terminal
 - Reset Method: No Reset
 - Number of Digits: 6
 - Mounting Type: Panel Mount



8966914 10 → 80 V dc

RS PRO HOUR METER COUNTER, 6 DIGIT, 50HZ, 90 → 264 V AC

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 90 → 264 V ac
 - Count Mode: Hours
 - Display Type: Analogue
 - Input Type: Voltage
 - Connection Type: Spade Terminal
 - Reset Method: No Reset
 - Number of Digits: 6
 - Mounting Type: Panel Mount



8966917 90 → 264 V ac

RS PRO HOUR METER COUNTER, 6 DIGIT, 50HZ, 4 → 30 V AC/DC

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 4 → 30 V ac/dc
 - Count Mode: Hours
 - Display Type: Analogue
 - Input Type: Voltage
 - Connection Type: Spade Terminal
 - Reset Method: No Reset
 - Number of Digits: 6
 - Mounting Type: Panel Mount



8966920 4 → 30 V ac/dc

RS PRO HOUR METER COUNTER, 6 DIGIT, 50HZ, 4 → 30 V AC/DC

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 4 → 30 V ac/dc
 - Count Mode: Hours
 - Display Type: Analogue
 - Input Type: Voltage
 - Connection Type: Spade Terminal
 - Reset Method: No Reset
 - Number of Digits: 6
 - Mounting Type: Panel Mount



8966923 4 → 30 V ac/dc

RS PRO HOUR METER COUNTER, 6 DIGIT, 50HZ, 90 → 264 V AC

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 90 → 264 V ac
 - Count Mode: Hours
 - Display Type: Analogue
 - Input Type: Voltage
 - Connection Type: Spade Terminal
 - Reset Method: No Reset
 - Number of Digits: 6
 - Mounting Type: Panel Mount



8966927 90 → 264 V ac

HOURS RUN METER CLAMP FIXING 90-264VAC

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 90 → 264 V ac
 - Count Mode: Hours
 - Display Type: Analogue
 - Input Type: Voltage
 - Connection Type: Spade Terminal
 - Reset Method: No Reset
 - Number of Digits: 6
 - Mounting Type: Panel Mount



8966933 90 → 264 V ac

RS PRO HOUR METER COUNTER, 6 DIGIT, 50HZ, 10 → 80 V DC

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 10 → 80 V dc
 - Count Mode: Hours
 - Display Type: Analogue
 - Input Type: Voltage
 - Connection Type: Spade Terminal
 - Reset Method: No Reset
 - Number of Digits: 6
 - Mounting Type: Panel Mount



8966936 10 → 80 V dc

HOURS RUN METER CLAMP FIXING 10-80VDC

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 10 → 80 V dc
 - Count Mode: Hours
 - Display Type: Analogue
 - Input Type: Voltage
 - Connection Type: Spade Terminal
 - Reset Method: No Reset
 - Number of Digits: 6
 - Mounting Type: Panel Mount



8966939 10 → 80 V dc

RS PRO HOUR METER COUNTER, 6 DIGIT, 50HZ, 4 → 30 V AC/DC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 4 → 30 V ac/dc
 - Count Mode: Hours
 - Display Type: Analogue
 - Input Type: Voltage
 - Connection Type: Spade Terminal
 - Reset Method: No Reset
 - Number of Digits: 6
 - Mounting Type: Panel Mount



8966942 4 → 30 V ac/dc

HOURS RUN METER 90-264VAC/270-460VAC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 270 → 460 V ac, 90 → 264 V ac
 - Count Mode: Hours
 - Display Type: Analogue
 - Input Type: Voltage
 - Connection Type: Spade Terminal
 - Reset Method: No Reset
 - Number of Digits: 6
 - Mounting Type: DIN Rail



8966945 270 → 460 V ac,

HOURS RUN METER DIN RAIL MOUNT 10-80VDC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 10 → 80 V dc
 - Count Mode: Hours
 - Display Type: Analogue
 - Input Type: Voltage
 - Connection Type: Spade Terminal
 - Reset Method: No Reset
 - Number of Digits: 6
 - Mounting Type: DIN Rail



8966949 10 → 80 V dc

RS PRO HOUR METER COUNTER, 6 DIGIT, 50HZ, 85 → 265 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 85 → 265 V ac
 - Count Mode: Hours
 - Display Type: LCD
 - Input Type: Voltage
 - Connection Type: Screw
 - Reset Method: Remote
 - Number of Digits: 6
 - Mounting Type: Flush Mount, Panel Mount



8966951 85 → 265 V ac

RS PRO HOUR METER COUNTER, 6 DIGIT, 50HZ, 12 → 48 V AC/DC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 12 → 48 V ac/dc
 - Count Mode: Hours
 - Display Type: LCD
 - Input Type: Voltage
 - Connection Type: Screw
 - Reset Method: Remote
 - Number of Digits: 6
 - Mounting Type: Flush Mount, Panel Mount



8966955 12 → 48 V ac/dc

RS PRO HOUR METER COUNTER, 6 DIGIT, 110 V DC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 110 V dc
 - Count Mode: Hours
 - Display Type: Analogue
 - Input Type: Voltage
 - Connection Type: Spade Terminal
 - Reset Method: No Reset
 - Number of Digits: 6
 - Mounting Type: DIN Rail



8966958 110 V dc

DIGITAL HOURS RUN METER 12-48VAC/DC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 12 → 48 V ac/dc
 - Count Mode: Hours
 - Display Type: LCD
 - Input Type: Voltage
 - Connection Type: Screw
 - Reset Method: Remote
 - Number of Digits: 6
 - Mounting Type: Flush Mount, Panel Mount



8966961 12 → 48 V ac/dc

RS PRO HOUR METER COUNTER, 6 DIGIT, 10 → 80 V DC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 10 → 80 V dc
 - Count Mode: Hours
 - Display Type: LCD
 - Input Type: Voltage
 - Connection Type: Screw
 - Reset Method: Remote
 - Number of Digits: 6
 - Mounting Type: Flush Mount, Panel Mount



8966964 10 → 80 V dc

RS PRO HOUR METER COUNTER, 6 DIGIT, 50HZ, 85 → 265 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 85 → 265 V ac
 - Count Mode: Hours
 - Display Type: LCD
 - Input Type: Voltage
 - Connection Type: Screw
 - Reset Method: Remote
 - Number of Digits: 6
 - Mounting Type: Flush Mount, Panel Mount



8966967 85 → 265 V ac

RS PRO HOUR METER COUNTER, 6 DIGIT, 10 → 80 V DC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 10 → 80 V dc
 - Count Mode: Hours
 - Display Type: LCD
 - Input Type: Voltage
 - Connection Type: Crimp Terminal
 - Reset Method: Remote
 - Number of Digits: 6
 - Mounting Type: Flush Mount, Panel Mount



8966970 10 → 80 V dc

RS PRO HOUR METER COUNTER, 6 DIGIT, 50HZ, 85 → 265 V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 85 → 265 V ac
 - Count Mode: Hours
 - Display Type: LCD
 - Input Type: Voltage
 - Connection Type: Screw
 - Reset Method: Remote
 - Number of Digits: 6
 - Mounting Type: Flush Mount, Panel Mount



8966973 85 → 265 V ac

RS PRO HOUR METER COUNTER, 6 DIGIT, 50HZ, 12 → 48 V AC/DC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 12 → 48 V ac/dc
 - Count Mode: Hours
 - Display Type: LCD
 - Input Type: Voltage
 - Connection Type: Screw
 - Reset Method: Remote
 - Number of Digits: 6
 - Mounting Type: Flush Mount, Panel Mount



8966977 12 → 48 V ac/dc

RS PRO COUNTER, DIGITAL HOUR METER COUNTER, 7 DIGIT, 40HZ, 85 →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 85 → 265 V ac/dc
 - Count Mode: Hours, Minutes, Seconds
 - Display Type: LCD
 - Input Type: Voltage
 - Connection Type: Terminal
 - Reset Method: Automatic, Manual, No Reset
 - Number of Digits: 7
 - Mounting Type: Flush Mount, Panel Mount



8966983 85 → 265 V ac/dc

RS PRO HOUR METER COUNTER, 6 DIGIT, 10 → 80 V DC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 10 → 80 V dc
 - Count Mode: Hours
 - Display Type: LCD
 - Input Type: Voltage
 - Connection Type: Screw
 - Reset Method: Remote
 - Number of Digits: 6
 - Mounting Type: Flush Mount, Panel Mount



8966986 10 → 80 V dc

DIGITAL HOUR METER & COUNTER 9-30VDC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 9 → 30 V dc
 - Count Mode: Hours, Minutes, Seconds
 - Display Type: LCD
 - Input Type: Voltage
 - Connection Type: Terminal
 - Reset Method: Automatic, Manual, No Reset
 - Number of Digits: 7
 - Mounting Type: Flush Mount, Panel Mount



8966992 9 → 30 V dc

RS PRO COUNTER, 7 DIGIT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Display Type: LCD
 - Number of Digits: 7
 - Digit Height: 6.5 mm
 - Depth: 62 mm
 - Series: RS PRO
 - Approvals: RoHS Compliant
 - Measurement Range: 0 → 9999999
 - Meter Type: Digital



8966995 LCD

DIGITAL IMPULSE COUNTER 12-48VAC/DC

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 12 → 48 V ac/dc
 - Count Mode: Pulse
 - Display Type: LCD
 - Input Type: Voltage
 - Connection Type: Terminal
 - Reset Method: Electrical
 - Number of Digits: 6
 - Mounting Type: Flush Mount, Panel Mount



8966999 12 → 48 V ac/dc

RS PRO IMPULSE COUNTER, 6 DIGIT, 10HZ, 85 → 265 V

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 85 → 265 V ac
 - Count Mode: Pulse
 - Display Type: LCD
 - Input Type: Voltage
 - Connection Type: Terminal
 - Reset Method: Electrical
 - Number of Digits: 6
 - Mounting Type: Flush Mount, Panel Mount



8967002 85 → 265 V ac

RS PRO IMPULSE COUNTER, 6 DIGIT, 30HZ, 10 → 80 V

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 10 → 80 V dc
 - Count Mode: Pulse
 - Display Type: LCD
 - Input Type: Voltage
 - Connection Type: Terminal
 - Reset Method: Electrical
 - Number of Digits: 6
 - Mounting Type: Flush Mount, Panel Mount



8967005 10 → 80 V dc

RS PRO IMPULSE COUNTER, 6 DIGIT, 10HZ, 110 V DC

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 110 V dc
 - Count Mode: Pulse
 - Display Type: Digital
 - Input Type: Voltage
 - Connection Type: Terminal Strip
 - Reset Method: No Reset
 - Number of Digits: 6
 - Mounting Type: Panel Mount



8967009 110 V dc

ELECTROMECH IMPULSE COUNTER 56X48MM 230V

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 230 V ac
 - Count Mode: Pulse
 - Display Type: Digital
 - Input Type: Voltage
 - Connection Type: Terminal Strip
 - Reset Method: Manual
 - Number of Digits: 6
 - Mounting Type: Panel Mount



8967011 230 V ac

ELECTROMECH IMPULSE COUNTER 56X48MM 24V

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 24 V dc
 - Count Mode: Pulse
 - Display Type: Impulse
 - Input Type: Voltage
 - Connection Type: Terminal Strip
 - Reset Method: Manual
 - Number of Digits: 6
 - Mounting Type: Panel Mount



8967015 24 V dc

RS PRO IMPULSE COUNTER, 6 DIGIT, 10HZ, 220 V DC

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 220 V dc
 - Count Mode: Pulse
 - Display Type: Digital
 - Input Type: Voltage
 - Connection Type: Terminal Strip
 - Reset Method: Manual
 - Number of Digits: 6
 - Mounting Type: Panel Mount



8967018 220 V dc

ELECTROMECH IMPULSE COUNTER 56X29MM 12V

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 12 V dc
 - Count Mode: Pulse
 - Display Type: Digital
 - Input Type: Voltage
 - Connection Type: Terminal Strip
 - Reset Method: Manual
 - Number of Digits: 6
 - Mounting Type: Panel Mount



8967021 12 V dc

ELECTROMECH IMPULSE COUNTER 56X29MM 230V

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 230 V ac
 - Count Mode: Pulse
 - Display Type: Digital
 - Input Type: Voltage
 - Connection Type: Terminal Strip
 - Reset Method: Manual
 - Number of Digits: 6
 - Mounting Type: Panel Mount



8967024 230 V ac

RS PRO IMPULSE COUNTER, 6 DIGIT, 10HZ, 115 V AC

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 115 V ac
 - Count Mode: Pulse
 - Display Type: Digital
 - Input Type: Voltage
 - Connection Type: Terminal Strip
 - Reset Method: Manual
 - Number of Digits: 6
 - Mounting Type: Panel Mount



8967027 115 V ac

ELECTROMECH IMPULSE COUNTER 56X29MM 24V

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 24 V dc
 - Count Mode: Pulse
 - Display Type: Mechanical
 - Input Type: Voltage
 - Connection Type: Flying Lead
 - Reset Method: Manual
 - Number of Digits: 6
 - Mounting Type: Panel Mount



8967030 24 V dc

ELECTROMECH IMPULSE COUNTER 56X26MM 24V

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 24 V dc
 - Count Mode: Pulse
 - Display Type: Digital
 - Input Type: Voltage
 - Connection Type: Terminal Strip
 - Reset Method: No Reset
 - Number of Digits: 6
 - Mounting Type: Panel Mount



8967033 24 V dc

RS PRO IMPULSE COUNTER, 7 DIGIT, 10HZ, 12 V DC

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 12 V dc
 - Count Mode: Pulse
 - Display Type: Digital
 - Input Type: Voltage
 - Connection Type: Screw
 - Reset Method: No Reset
 - Number of Digits: 7
 - Mounting Type: Panel Mount



8967037 12 V dc

RS PRO IMPULSE COUNTER, 7 DIGIT, 10HZ, 24 V DC

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 24 V dc
 - Count Mode: Pulse
 - Display Type: Digital
 - Input Type: Voltage
 - Connection Type: Screw
 - Reset Method: No Reset
 - Number of Digits: 7
 - Mounting Type: Panel Mount



8967043 24 V dc

RS PRO IMPULSE COUNTER, 7 DIGIT, 10HZ, 24 V DC

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 24 V dc
 - Count Mode: Pulse
 - Display Type: Digital
 - Input Type: Voltage
 - Connection Type: Screw
 - Reset Method: No Reset
 - Number of Digits: 7
 - Mounting Type: Panel Mount



8967046 24 V dc

RS PRO IMPULSE COUNTER, 7 DIGIT, 10HZ, 12 V DC

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 12 V dc
 - Count Mode: Pulse
 - Display Type: Digital
 - Input Type: Voltage
 - Connection Type: Screw
 - Reset Method: No Reset
 - Number of Digits: 7
 - Mounting Type: Panel Mount



8967049 12 V dc

RS PRO CURRENT TRANSFORMER, 50:1, 21 X 10MM BORE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Ratio: 50:1
 - Bore Size: 21 x 10 mm
 - Overall Height: 65 mm
 - Overall Width: 7.2 mm
 - Overall Depth: 40 mm
 - Dimensions: 45 x 40 x 65 mm



1718749 50:1

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 50A INPUT, 50:5, 5 A

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Ratio: 50:5
 - Bore Size: 21 x 10 mm
 - Transformer Type: Base Mounted
 - Input Current: 50 A
 - Output Current: 5 A
 - Overall Height: 65 mm
 - Overall Width: 7.2 mm
 - Overall Depth: 40 mm



1718750 50:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 60A INPUT, 60:5, 5 A

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Ratio: 60:5
 - Bore Size: 21 x 10 mm
 - Transformer Type: Base Mounted
 - Input Current: 60 A
 - Output Current: 5 A
 - Overall Height: 65 mm
 - Overall Width: 7.2 mm
 - Overall Depth: 40 mm



1718751 60:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 80A INPUT, 80:5, 5 A

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Ratio: 80:5
 - Bore Size: 21 x 10 mm
 - Transformer Type: Base Mounted
 - Input Current: 80 A
 - Output Current: 5 A
 - Overall Height: 65 mm
 - Overall Width: 7.2 mm
 - Overall Depth: 40 mm



1718753 80:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 100A INPUT, 100:5, 5

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Ratio: 100:5
 - Bore Size: 21 x 10 mm
 - Transformer Type: Base Mounted
 - Input Current: 100 A
 - Output Current: 5 A
 - Overall Height: 65 mm
 - Overall Width: 45 mm
 - Overall Depth: 40 mm



1718755 100:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 125A INPUT, 125:5, 5

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Ratio: 125:5
 - Bore Size: 21 x 10 mm
 - Transformer Type: Base Mounted
 - Input Current: 125 A
 - Output Current: 5 A
 - Overall Height: 65 mm
 - Overall Width: 45 mm
 - Overall Depth: 40 mm



1718756 125:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 150A INPUT, 150:5, 5

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Ratio: 150:5
 - Bore Size: 21 x 10 mm
 - Transformer Type: Base Mounted
 - Input Current: 150 A
 - Output Current: 5 A
 - Overall Height: 65 mm
 - Overall Width: 45 mm
 - Overall Depth: 40 mm



1718758 150:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 200A INPUT, 200:5, 5

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Ratio: 200:5
 - Bore Size: 21 x 10 mm
 - Transformer Type: Base Mounted
 - Input Current: 200 A
 - Output Current: 5 A
 - Overall Height: 65 mm
 - Overall Width: 45 mm
 - Overall Depth: 40 mm



1718760 200:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 80A INPUT, 80:5, 5 A

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Ratio: 80:5
 - Bore Size: 30 x 10 mm
 - Transformer Type: Base Mounted
 - Input Current: 80 A
 - Output Current: 5 A
 - Overall Height: 70 mm
 - Overall Width: 50 mm
 - Overall Depth: 31 mm



1718763 80:5

RS PRO CURRENT TRANSFORMER, 100:1, 30 X 10MM BORE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Ratio: 100:1
 - Bore Size: 30 x 10 mm
 - Overall Height: 70 mm
 - Overall Width: 50 mm
 - Overall Depth: 30 mm
 - Dimensions: 50 x 30 x 70 mm



1718764 100:1

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 100A INPUT, 100:5, 5

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Ratio: 100:5
 - Bore Size: 30 x 10 mm
 - Transformer Type: Base Mounted
 - Input Current: 100 A
 - Output Current: 5 A
 - Overall Height: 70 mm
 - Overall Width: 50 mm
 - Overall Depth: 31 mm



1718765 100:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 125A INPUT, 125:5, 5

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Ratio: 125:5
 - Bore Size: 30 x 10 mm
 - Transformer Type: Base Mounted
 - Input Current: 125 A
 - Output Current: 5 A
 - Overall Height: 70 mm
 - Overall Width: 50 mm
 - Overall Depth: 31 mm



1718766 125:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 150A INPUT, 150:5, 5

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Ratio: 150:5
 - Bore Size: 30 x 10 mm
 - Transformer Type: Base Mounted
 - Input Current: 150 A
 - Output Current: 5 A
 - Overall Height: 70 mm
 - Overall Width: 50 mm
 - Overall Depth: 31 mm



1718769 150:5

RS PRO CURRENT TRANSFORMER, 200:1, 30 X 10MM BORE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Ratio: 200:1
 - Bore Size: 30 x 10 mm
 - Overall Height: 70 mm
 - Overall Width: 50 mm
 - Overall Depth: 30 mm
 - Dimensions: 50 x 30 x 70 mm



1718770 200:1

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 200A INPUT, 200:5, 5

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Ratio: 200:5
 - Bore Size: 30 x 10 mm
 - Transformer Type: Base Mounted
 - Input Current: 200 A
 - Output Current: 5 A
 - Overall Height: 70 mm
 - Overall Width: 50 mm
 - Overall Depth: 31 mm



1718771 200:5

RS PRO CURRENT TRANSFORMER, 250:1, 30 X 10MM BORE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Ratio: 250:1
 - Bore Size: 30 x 10 mm
 - Overall Height: 70 mm
 - Overall Width: 50 mm
 - Overall Depth: 30 mm
 - Dimensions: 50 x 30 x 70 mm



1718772 250:1

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 250A INPUT, 250:5, 5

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Ratio: 250:5
 - Bore Size: 30 x 10 mm
 - Transformer Type: Base Mounted
 - Input Current: 250 A
 - Output Current: 5 A
 - Overall Height: 70 mm
 - Overall Width: 50 mm
 - Overall Depth: 31 mm



1718773 250:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 300A INPUT, 300:5, 5

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Ratio: 300:5
 - Bore Size: 30 x 10 mm
 - Transformer Type: Base Mounted
 - Input Current: 300 A
 - Output Current: 5 A
 - Overall Height: 70 mm
 - Overall Width: 50 mm
 - Overall Depth: 31 mm



1718775 300:5

RS PRO CURRENT TRANSFORMER, 400:1, 30 X 10MM BORE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Ratio: 400:1
 - Bore Size: 30 x 10 mm
 - Overall Height: 70 mm
 - Overall Width: 50 mm
 - Overall Depth: 30 mm
 - Dimensions: 50 x 30 x 70 mm



1718776 400:1

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 400A INPUT, 400:5, 5

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Ratio: 400:5
 - Bore Size: 30 x 10 mm
 - Transformer Type: Base Mounted
 - Input Current: 400 A
 - Output Current: 5 A
 - Overall Height: 70 mm
 - Overall Width: 50 mm
 - Overall Depth: 31 mm



1718777 400:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 500A INPUT, 500:5, 5

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Ratio: 500:5
 - Bore Size: 30 x 10 mm
 - Transformer Type: Base Mounted
 - Input Current: 500 A
 - Output Current: 5 A
 - Overall Height: 70 mm
 - Overall Width: 50 mm
 - Overall Depth: 31 mm



1718778 500:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 600A INPUT, 600:5, 5

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Ratio: 600:5
 - Bore Size: 30 x 10 mm
 - Transformer Type: Base Mounted
 - Input Current: 600 A
 - Output Current: 5 A
 - Overall Height: 70 mm
 - Overall Width: 50 mm
 - Overall Depth: 31 mm



1718779 600:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 100A INPUT, 100:5, 5

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Ratio: 100:5
 - Bore Size: 30 x 11 mm
 - Transformer Type: Base Mounted
 - Input Current: 100 A
 - Output Current: 5 A
 - Overall Height: 78 mm
 - Overall Width: 62 mm
 - Overall Depth: 40 mm



1718781 100:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 125A INPUT, 125:5, 5

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Ratio: 125:5
 - Bore Size: 30 x 11 mm
 - Transformer Type: Base Mounted
 - Input Current: 125 A
 - Output Current: 5 A
 - Overall Height: 78 mm
 - Overall Width: 62 mm
 - Overall Depth: 40 mm



1718782 125:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 150A INPUT, 150:5, 5

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Ratio: 150:5
 - Bore Size: 30 x 11 mm
 - Transformer Type: Base Mounted
 - Input Current: 150 A
 - Output Current: 5 A
 - Overall Height: 78 mm
 - Overall Width: 62 mm
 - Overall Depth: 40 mm



1718783 150:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 100A INPUT, 100:5, 5

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Ratio: 100:5
 - Bore Size: 40 x 11 mm
 - Transformer Type: Base Mounted
 - Input Current: 100 A
 - Output Current: 5 A
 - Overall Height: 78 mm
 - Overall Width: 62 mm
 - Overall Depth: 40 mm



1718785 100:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 200A INPUT, 200:5, 5

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Ratio: 200:5
 - Bore Size: 40 x 11 mm
 - Transformer Type: Base Mounted
 - Input Current: 200 A
 - Output Current: 5 A
 - Overall Height: 78 mm
 - Overall Width: 62 mm
 - Overall Depth: 40 mm



1718787 200:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 250A INPUT, 250:5, 5

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Ratio: 250:5
 - Bore Size: 40 x 11 mm
 - Transformer Type: Base Mounted
 - Input Current: 250 A
 - Output Current: 5 A
 - Overall Height: 78 mm
 - Overall Width: 62 mm
 - Overall Depth: 40 mm



1718788 250:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 300A INPUT, 300:5, 5

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Ratio: 300:5
 - Bore Size: 40 x 11 mm
 - Transformer Type: Base Mounted
 - Input Current: 300 A
 - Output Current: 5 A
 - Overall Height: 78 mm
 - Overall Width: 62 mm
 - Overall Depth: 40 mm



1718789 300:5

RS PRO CURRENT TRANSFORMER, 400:1, 40 X 11MM BORE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Ratio: 400:1
 - Bore Size: 40 x 11 mm
 - Overall Height: 78 mm
 - Overall Width: 62 mm
 - Overall Depth: 40 mm
 - Dimensions: 62 x 40 x 78 mm



1718790 400:1

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 400A INPUT, 400:5, 5

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Ratio: 400:5
 - Bore Size: 40 x 11 mm
 - Transformer Type: Base Mounted
 - Input Current: 400 A
 - Output Current: 5 A
 - Overall Height: 78 mm
 - Overall Width: 62 mm
 - Overall Depth: 40 mm



1718791 400:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 500A INPUT, 500:5, 5

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Ratio: 500:5
 - Bore Size: 40 x 11 mm
 - Transformer Type: Base Mounted
 - Input Current: 500 A
 - Output Current: 5 A
 - Overall Height: 78 mm
 - Overall Width: 62 mm
 - Overall Depth: 40 mm



1718792 500:5

RS PRO CURRENT TRANSFORMER, 600:1, 40 X 11MM BORE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Current Ratio: 600:1
 - Bore Size: 40 x 11 mm
 - Overall Height: 78 mm
 - Overall Width: 62 mm
 - Overall Depth: 40 mm
 - Dimensions: 62 x 40 x 78 mm



1718793 600:1

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 600A INPUT, 600:5, 5

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Current Ratio: 600:5
 - Bore Size: 40 x 11 mm
 - Transformer Type: Base Mounted
 - Input Current: 600 A
 - Output Current: 5 A
 - Overall Height: 78 mm
 - Overall Width: 62 mm
 - Overall Depth: 40 mm



1718794 600:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 800A INPUT, 800:5, 5

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Current Ratio: 800:5
 - Bore Size: 40 x 11 mm
 - Transformer Type: Base Mounted
 - Input Current: 800 A
 - Output Current: 5 A
 - Overall Height: 78 mm
 - Overall Width: 62 mm
 - Overall Depth: 40 mm



1718798 800:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 400A INPUT, 400:5, 5

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Current Ratio: 400:5
 - Bore Size: 41 x 41 mm
 - Transformer Type: Base Mounted
 - Input Current: 400 A
 - Output Current: 5 A
 - Overall Height: 98 mm
 - Overall Width: 74 mm
 - Overall Depth: 45 mm



1718799 400:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 500A INPUT, 500:5, 5

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Current Ratio: 500:5
 - Bore Size: 41 x 41 mm
 - Transformer Type: Base Mounted
 - Input Current: 500 A
 - Output Current: 5 A
 - Overall Height: 98 mm
 - Overall Width: 74 mm
 - Overall Depth: 45 mm



1718800 500:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 600A INPUT, 600:5, 5

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Current Ratio: 600:5
 - Bore Size: 41 x 41 mm
 - Transformer Type: Base Mounted
 - Input Current: 600 A
 - Output Current: 5 A
 - Overall Height: 98 mm
 - Overall Width: 74 mm
 - Overall Depth: 45 mm



1718801 600:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 800A INPUT, 800:5, 5

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Current Ratio: 800:5
 - Bore Size: 41 x 41 mm
 - Transformer Type: Base Mounted
 - Input Current: 800 A
 - Output Current: 5 A
 - Overall Height: 98 mm
 - Overall Width: 74 mm
 - Overall Depth: 45 mm



1718802 800:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 1000A INPUT, 1000:5, 5

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Current Ratio: 1000:5
 - Bore Size: 41 x 41 mm
 - Transformer Type: Base Mounted
 - Input Current: 1000 A
 - Output Current: 5 A
 - Overall Height: 98 mm
 - Overall Width: 74 mm
 - Overall Depth: 45 mm



1718804 1000:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 1000A INPUT, 1000:5, 5

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Current Ratio: 1000:5
 - Bore Size: 61 x 51 mm
 - Transformer Type: Base Mounted
 - Input Current: 1000 A
 - Output Current: 5 A
 - Overall Height: 110 mm
 - Overall Width: 86 mm
 - Overall Depth: 45 mm



1718805 1000:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 1250A INPUT, 1250:5, 5

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Current Ratio: 1250:5
 - Bore Size: 61 x 51 mm
 - Transformer Type: Base Mounted
 - Input Current: 1250 A
 - Output Current: 5 A
 - Overall Height: 110 mm
 - Overall Width: 86 mm
 - Overall Depth: 45 mm



1718807 1250:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 1500A INPUT, 1500:5, 5

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Current Ratio: 1500:5
 - Bore Size: 61 x 51 mm
 - Transformer Type: Base Mounted
 - Input Current: 1500 A
 - Output Current: 5 A
 - Overall Height: 110 mm
 - Overall Width: 86 mm
 - Overall Depth: 45 mm



1718809 1500:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 800A INPUT, 800:5, 5

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Current Ratio: 800:5
 - Bore Size: 80 x 12 mm
 - Transformer Type: Base Mounted
 - Input Current: 800 A
 - Output Current: 5 A
 - Overall Height: 126 mm
 - Overall Width: 104 mm
 - Overall Depth: 45 mm



1718811 800:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 1000A INPUT, 1000:5, 5

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Current Ratio: 1000:5
 - Bore Size: 80 x 12 mm
 - Transformer Type: Base Mounted
 - Input Current: 1000 A
 - Output Current: 5 A
 - Overall Height: 126 mm
 - Overall Width: 104 mm
 - Overall Depth: 45 mm



1718812 1000:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 1250A INPUT, 1250:5, 5

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Current Ratio: 1250:5
 - Bore Size: 80 x 12 mm
 - Transformer Type: Base Mounted
 - Input Current: 1250 A
 - Output Current: 5 A
 - Overall Height: 126 mm
 - Overall Width: 104 mm
 - Overall Depth: 45 mm



1718814 1250:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 1500A INPUT, 1500:5, 5

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Current Ratio: 1500:5
 - Bore Size: 80 x 12 mm
 - Transformer Type: Base Mounted
 - Input Current: 1500 A
 - Output Current: 5 A
 - Overall Height: 126 mm
 - Overall Width: 104 mm
 - Overall Depth: 45 mm



1718815 1500:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 1600A INPUT, 1600:5, 5

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Current Ratio: 1600:5
 - Bore Size: 80 x 12 mm
 - Transformer Type: Base Mounted
 - Input Current: 1600 A
 - Output Current: 5 A
 - Overall Height: 126 mm
 - Overall Width: 104 mm
 - Overall Depth: 45 mm



1718816 1600:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 2000A INPUT,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Ratio: 2000:5
 - Bore Size: 80 x 12 mm
 - Transformer Type: Base Mounted
 - Input Current: 2000 A
 - Output Current: 5 A
 - Overall Height: 126 mm
 - Overall Width: 104 mm
 - Overall Depth: 45 mm



1718817 2000:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 2000A INPUT,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Ratio: 2000:5
 - Bore Size: 100 x 30 mm
 - Transformer Type: Base Mounted
 - Input Current: 2000 A
 - Output Current: 5 A
 - Overall Height: 155 mm
 - Overall Width: 140 mm
 - Overall Depth: 45 mm



1718821 2000:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 2500A INPUT,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Ratio: 2500:5
 - Bore Size: 100 x 30 mm
 - Transformer Type: Base Mounted
 - Input Current: 2500 A
 - Output Current: 5 A
 - Overall Height: 155 mm
 - Overall Width: 140 mm
 - Overall Depth: 45 mm



1718822 2500:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 3000A INPUT,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Ratio: 3000:5
 - Bore Size: 100 x 30 mm
 - Transformer Type: Base Mounted
 - Input Current: 3000 A
 - Output Current: 5 A
 - Overall Height: 155 mm
 - Overall Width: 140 mm
 - Overall Depth: 45 mm



1718823 3000:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 100A INPUT, 100:5, 5

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Ratio: 100:5
 - Bore Size: 35 mm
 - Transformer Type: Base Mounted
 - Input Current: 100 A
 - Output Current: 5 A
 - Overall Height: 87.5 mm
 - Overall Width: 105 mm
 - Overall Depth: 38 mm



1718824 100:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 125A INPUT, 125:5, 5

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Ratio: 125:5
 - Bore Size: 35 mm
 - Transformer Type: Base Mounted
 - Input Current: 125 A
 - Output Current: 5 A
 - Overall Height: 87.5 mm
 - Overall Width: 105 mm
 - Overall Depth: 38 mm



1718825 125:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 150A INPUT, 150:5, 5

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Ratio: 150:5
 - Bore Size: 35 mm
 - Transformer Type: Base Mounted
 - Input Current: 150 A
 - Output Current: 5 A
 - Overall Height: 87.5 mm
 - Overall Width: 105 mm
 - Overall Depth: 38 mm



1718826 150:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 160A INPUT, 160:5, 5

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Ratio: 160:5
 - Bore Size: 35 mm
 - Transformer Type: Base Mounted
 - Input Current: 160 A
 - Output Current: 5 A
 - Overall Height: 87.5 mm
 - Overall Width: 105 mm
 - Overall Depth: 38 mm



1718827 160:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 200A INPUT, 200:5, 5

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Ratio: 200:5
 - Bore Size: 35 mm
 - Transformer Type: Base Mounted
 - Input Current: 200 A
 - Output Current: 5 A
 - Overall Height: 87.5 mm
 - Overall Width: 105 mm
 - Overall Depth: 38 mm



1718828 200:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 250A INPUT, 250:5, 5

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Ratio: 250:5
 - Bore Size: 35 mm
 - Transformer Type: Base Mounted
 - Input Current: 250 A
 - Output Current: 5 A
 - Overall Height: 87.5 mm
 - Overall Width: 105 mm
 - Overall Depth: 38 mm



1718829 250:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 250A INPUT, 250:5, 5

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Ratio: 250:5
 - Bore Size: 45 mm
 - Transformer Type: Base Mounted
 - Input Current: 250 A
 - Output Current: 5 A
 - Overall Height: 102.5 mm
 - Overall Width: 141 mm
 - Overall Depth: 38 mm



1718830 250:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 300A INPUT, 300:5, 5

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Ratio: 300:5
 - Bore Size: 45 mm
 - Transformer Type: Base Mounted
 - Input Current: 300 A
 - Output Current: 5 A
 - Overall Height: 102.5 mm
 - Overall Width: 141 mm
 - Overall Depth: 38 mm



1718831 300:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 400A INPUT, 400:5, 5

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Ratio: 400:5
 - Bore Size: 45 mm
 - Transformer Type: Base Mounted
 - Input Current: 400 A
 - Output Current: 5 A
 - Overall Height: 102.5 mm
 - Overall Width: 141 mm
 - Overall Depth: 38 mm



1718832 400:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 600A INPUT, 600:5, 5

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Ratio: 600:5
 - Bore Size: 45 mm
 - Transformer Type: Base Mounted
 - Input Current: 600 A
 - Output Current: 5 A
 - Overall Height: 102.5 mm
 - Overall Width: 141 mm
 - Overall Depth: 38 mm



1718833 600:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 1000A INPUT, 1000:5,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Ratio: 1000:5
 - Bore Size: 38 x 128 mm
 - Transformer Type: Base Mounted
 - Input Current: 1000 A
 - Output Current: 5 A
 - Overall Height: 170 mm
 - Overall Width: 99 mm
 - Overall Depth: 45 mm



1718834 1000:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 2000A INPUT,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Ratio: 2000:5
 - Bore Size: 38 x 128 mm
 - Transformer Type: Base Mounted
 - Input Current: 2000 A
 - Output Current: 5 A
 - Overall Height: 170 mm
 - Overall Width: 99 mm
 - Overall Depth: 45 mm



1718838 2000:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 2500A INPUT,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Current Ratio: 2500:5
 - Bore Size: 38 x 128 mm
 - Transformer Type: Base Mounted
 - Input Current: 2500 A
 - Output Current: 5 A
 - Overall Height: 170 mm
 - Overall Width: 99 mm
 - Overall Depth: 45 mm



1718839 2500:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 1000A INPUT, 1000:5,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Current Ratio: 1000:5
 - Bore Size: 101 x 56 mm
 - Transformer Type: Base Mounted
 - Input Current: 1000 A
 - Output Current: 5 A
 - Overall Height: 170 mm
 - Overall Width: 130 mm
 - Overall Depth: 60 mm



1718840 1000:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 2500A INPUT,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Current Ratio: 2500:5
 - Bore Size: 101 x 56 mm
 - Transformer Type: Base Mounted
 - Input Current: 2500 A
 - Output Current: 5 A
 - Overall Height: 170 mm
 - Overall Width: 130 mm
 - Overall Depth: 60 mm



1718845 2500:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 100A INPUT, 100:5, 5

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Current Ratio: 100:5
 - Bore Size: 33 x 23 mm
 - Transformer Type: Base Mounted
 - Input Current: 100 A
 - Output Current: 5 A
 - Overall Height: 106 mm
 - Overall Width: 93 mm
 - Overall Depth: 40 mm



1718846 100:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 200A INPUT, 200:5, 5

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Current Ratio: 200:5
 - Bore Size: 33 x 23 mm
 - Transformer Type: Base Mounted
 - Input Current: 200 A
 - Output Current: 5 A
 - Overall Height: 106 mm
 - Overall Width: 93 mm
 - Overall Depth: 40 mm



1718848 200:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 250A INPUT, 250:5, 5

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Current Ratio: 250:5
 - Bore Size: 33 x 23 mm
 - Transformer Type: Base Mounted
 - Input Current: 250 A
 - Output Current: 5 A
 - Overall Height: 106 mm
 - Overall Width: 93 mm
 - Overall Depth: 40 mm



1718849 250:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 300A INPUT, 300:5, 5

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Current Ratio: 300:5
 - Bore Size: 33 x 23 mm
 - Transformer Type: Base Mounted
 - Input Current: 300 A
 - Output Current: 5 A
 - Overall Height: 106 mm
 - Overall Width: 93 mm
 - Overall Depth: 40 mm



1718850 300:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 400A INPUT, 400:5, 5

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Current Ratio: 400:5
 - Bore Size: 33 x 23 mm
 - Transformer Type: Base Mounted
 - Input Current: 400 A
 - Output Current: 5 A
 - Overall Height: 106 mm
 - Overall Width: 93 mm
 - Overall Depth: 40 mm



1718851 400:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 500A INPUT, 500:5, 5

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Current Ratio: 500:5
 - Bore Size: 55 x 43 mm
 - Transformer Type: Base Mounted
 - Input Current: 500 A
 - Output Current: 5 A
 - Overall Height: 125 mm
 - Overall Width: 108 mm
 - Overall Depth: 51 mm



1718852 500:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 600A INPUT, 600:5, 5

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Current Ratio: 600:5
 - Bore Size: 55 x 43 mm
 - Transformer Type: Base Mounted
 - Input Current: 600 A
 - Output Current: 5 A
 - Overall Height: 125 mm
 - Overall Width: 108 mm
 - Overall Depth: 51 mm



1718854 600:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 5A INPUT, 5:5, 5 A

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Current Ratio: 5:5
 - Bore Size: 62 x 40 mm
 - Transformer Type: Base Mounted
 - Input Current: 5 A
 - Output Current: 5 A
 - Overall Height: 78 mm
 - Overall Width: 62 mm
 - Overall Depth: 40 mm



1718855 5:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 10A INPUT, 10:5, 5 A

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Current Ratio: 10:5
 - Bore Size: 62 x 40 mm
 - Transformer Type: Base Mounted
 - Input Current: 10 A
 - Output Current: 5 A
 - Overall Height: 78 mm
 - Overall Width: 62 mm
 - Overall Depth: 40 mm



1718856 10:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 15A INPUT, 15:5, 5 A

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Current Ratio: 15:5
 - Bore Size: 62 x 40 mm
 - Transformer Type: Base Mounted
 - Input Current: 15 A
 - Output Current: 5 A
 - Overall Height: 78 mm
 - Overall Width: 62 mm
 - Overall Depth: 40 mm



1718857 15:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 20A INPUT, 20:5, 5 A

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Current Ratio: 20:5
 - Bore Size: 62 x 40 mm
 - Transformer Type: Base Mounted
 - Input Current: 20 A
 - Output Current: 5 A
 - Overall Height: 78 mm
 - Overall Width: 62 mm
 - Overall Depth: 40 mm



1718858 20:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 30A INPUT, 30:5, 5 A

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Current Ratio: 30:5
 - Bore Size: 62 x 40 mm
 - Transformer Type: Base Mounted
 - Input Current: 30 A
 - Output Current: 5 A
 - Overall Height: 78 mm
 - Overall Width: 62 mm
 - Overall Depth: 40 mm



1718859 30:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 40A INPUT, 40:5, 5 A

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Current Ratio: 40:5
 - Bore Size: 74 x 45 mm
 - Transformer Type: Base Mounted
 - Input Current: 40 A
 - Output Current: 5 A
 - Overall Height: 98 mm
 - Overall Width: 74 mm
 - Overall Depth: 45 mm



1718860 40:5

RS PRO 3 PHASE ENERGY METER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Cutout Height: 90 mm
 - Cutout Width: 90 mm
 - Display Type: Digital
 - Number of Digits: 4
 - Number of Phases: 3
 - Depth: 55 mm
 - Digit Height: 10 mm
 - Meter Accuracy: Class 1



1797572 90 mm

RS PRO 3 PHASE LED ENERGY METER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Cutout Height: 90 mm
 - Cutout Width: 90 mm
 - Display Type: LED
 - Number of Digits: 4 (Instantaneous), 6 (Integrated)
 - Number of Phases: 3
 - Depth: 55 mm
 - Digit Height: 10 mm
 - Meter Accuracy: Class 1



1797577 90 mm

RS PRO COUNTER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Display Type: Analogue
 - Cutout Size: 72 x 72 mm
 - Meter Type: Moving Iron
 - Maximum Temperature: +50 °C
 - Measurement Range: 45 → 65 Hz
 - Cutout Height: 72 mm
 - Approvals: CE, RoHS Compliant, TUV Certified, UL E327849
 - Cutout Width: 72 mm



9010573 Analogue

RS PRO COUNTER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Display Type: Analogue
 - Cutout Size: 96 x 96 mm
 - Meter Type: Moving Iron
 - Maximum Temperature: +50 °C
 - Measurement Range: 45 → 65 Hz
 - Cutout Height: 96 mm
 - Approvals: CE, RoHS Compliant, TUV Certified, UL E327849
 - Cutout Width: 96 mm



9010576 Analogue

RS PRO LED DIGITAL PANEL MULTI-FUNCTION METER, 92MM X 92MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Properties Measured: Current, Frequency, On Hour, RPM, Run Hour, Voltage
 - Display Type: LED
 - Cutout Height: 92 mm
 - Cutout Width: 92 mm
 - Depth: 55 mm
 - Number of Digits: 3
 - Minimum Temperature: -10 °C
 - Maximum Temperature: +55 °C



1365377 Current,

RS PRO LED DIGITAL PANEL MULTI-FUNCTION METER, 92MM X 92MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Properties Measured: Current, Frequency, On Hour, RPM, Run Hour, Voltage
 - Display Type: LED
 - Cutout Height: 92 mm
 - Cutout Width: 92 mm
 - Number of Digits: 3
 - Depth: 55 mm
 - Minimum Temperature: -10 °C
 - Maximum Temperature: +55 °C



1365378 Current,

RS PRO LED DIGITAL PANEL MULTI-FUNCTION METER, 92MM X 92MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Properties Measured: AC Current, AC Voltage, Frequency, Hour, RPM
 - Display Type: LED
 - Cutout Height: 92 mm
 - Cutout Width: 92 mm
 - Depth: 62 mm
 - Number of Digits: 4
 - Digit Height: 20 mm
 - Minimum Temperature: -20 °C



1365379 AC Current, AC

RS PRO LED DIGITAL PANEL MULTI-FUNCTION METER, 92MM X 92MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Properties Measured: AC Current, AC Voltage, Frequency, Hour, RPM
 - Display Type: LED
 - Cutout Height: 92 mm
 - Cutout Width: 92 mm
 - Depth: 62 mm
 - Number of Digits: 4
 - Digit Height: 20 mm
 - Minimum Temperature: -20 °C



1365380 AC Current, AC

RS PRO LED DIGITAL PANEL MULTI-FUNCTION METER, 92MM X 92MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Properties Measured: Current, Frequency, System Active Power, System Re-Active Power, Voltage
 - Display Type: LED
 - Cutout Height: 92 mm
 - Cutout Width: 92 mm
 - Depth: 55 mm
 - Number of Digits: 4
 - Minimum Temperature: 0 °C
 - Maximum Temperature: +50 °C



1365381 Current,

RS PRO LED DIGITAL PANEL MULTI-FUNCTION METER, 92MM X 92MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Properties Measured: Current, Frequency, System Active Power, System Re-Active Power, Voltage
 - Display Type: LED
 - Cutout Height: 92 mm
 - Cutout Width: 92 mm
 - Depth: 55 mm
 - Number of Digits: 4
 - Minimum Temperature: 0 °C
 - Maximum Temperature: +50 °C



1365382 Current,

RS PRO LED DIGITAL PANEL MULTI-FUNCTION METER, 92MM X 92MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Properties Measured: AC Current, AC Voltage, Active, Apparent Power, Frequency, Import Export Energy, Reactive
 - Display Type: LED
 - Cutout Height: 92 mm
 - Cutout Width: 92 mm
 - Depth: 55 mm
 - Number of Digits: 4
 - Minimum Temperature: -20 °C
 - Maximum Temperature: +70 °C



1365383 AC Current, AC

RS PRO 7 SEGMENT LED DIGITAL PANEL MULTI-FUNCTION METER FOR

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Properties Measured: Current, Voltage
 - Display Type: 7 Segment LED
 - Depth: 66 mm
 - Number of Digits: 4
 - Digit Height: 14 mm
 - Minimum Temperature: -20 °C
 - Maximum Temperature: +60 °C
 - Measurement Range: ±2 → ±10 (Voltage) V, -20 → 20 (Current) mA



1883474 Current, Voltage

MAGNET,CENTRE POLE,SURFACE MOUNT

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Accessory Type: Centre Pole Magnet
 - For Use With: Hall Effect Switch, Reed Proximity Switch, Reed Relay



260369 Centre Pole

RS PRO BEZEL FOR USE WITH 55 X 55 HOUR METER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: Bezel
 - For Use With: 55 x 55 Hour Meter



8966908 Bezel

RS PRO 60A METER SCALE FOR USE WITH 72 X 72 ANALOGUE PANEL

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: 60A Meter Scale
 - For Use With: 72 x 72 Analogue Panel Ammeter



9010422 60A Meter Scale

RS PRO 250A METER SCALE FOR USE WITH 72 X 72 ANALOGUE PANEL

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: 250A Meter Scale
 - For Use With: 72 x 72 Analogue Panel Ammeter



9010444 250A Meter Scale

RS PRO 60A METER SCALE FOR USE WITH 96 X 96 ANALOGUE PANEL

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Accessory Type: 60A Meter Scale
 - For Use With: 96 x 96 Analogue Panel Ammeter



9010472 60A Meter Scale

DIGITAL TIMER, 35X77, 230V AC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 230 V ac
 - Mounting Type: Panel Mount
 - Mode of Operation: Multifunction
 - Number of Timer Functions: Multi Function
 - Time Increment: Seconds
 - Maximum Voltage: 230 V
 - Terminal Type: Screw
 - Minimum Voltage: 100 V



1241077 230 V ac

RS PRO PANEL MOUNT MULTI FUNCTION TIMER RELAY, 24V AC/DC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 24 V ac/dc
 - Mounting Type: Panel Mount
 - Mode of Operation: Multifunction
 - Number of Timer Functions: Multi Function
 - Time Increment: Seconds
 - Maximum Voltage: 230 V
 - Terminal Type: Screw
 - Minimum Voltage: 100 V



1241078 24 V ac/dc

RS PRO PANEL MOUNT MULTI FUNCTION TIMER RELAY, 12 → 48 V

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 12 → 48 V dc, 24 → 48 V ac
 - Mounting Type: Panel Mount
 - Number of Contacts: 2
 - Time Range: 0.1 s → 300 h
 - Mode of Operation: Flicker OFF Start, Flicker ON Start, Interval, ON Delay, Signal OFF Delay, Signal ON/OFF Delay
 - Number of Timer Functions: Multi Function
 - Contact Configuration: DPDT
 - Time Increment: Hours, Seconds



1792916 12 → 48 V dc, 24 →

RS PRO PANEL MOUNT MULTI FUNCTION TIMER RELAY, 12 → 48 V

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 12 → 48 V dc, 24 → 48 V ac
 - Mounting Type: Panel Mount
 - Number of Contacts: 2
 - Time Range: 0.1 s → 300 h
 - Mode of Operation: Flicker ON Start, Interval, ON Delay, One Shot
 - Number of Timer Functions: Multi Function
 - Contact Configuration: DPDT
 - Time Increment: Hours, Seconds



1792918 12 → 48 V dc, 24 →

RS PRO PANEL MOUNT MULTI FUNCTION TIMER RELAY, 24V DC,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 24 V dc
 - Mounting Type: Panel Mount
 - Number of Contacts: 2
 - Time Range: 0.1 s → 300 h
 - Mode of Operation: Flicker OFF Start, Flicker ON Start, Interval, ON Delay, Signal OFF Delay, Signal ON/OFF Delay
 - Number of Timer Functions: Multi Function
 - Contact Configuration: DPDT
 - Time Increment: Hours, Seconds



1792922 24 V dc

RS PRO PANEL MOUNT SINGLE FUNCTION TIMER RELAY, 24V DC, 2 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 24 V dc
 - Mounting Type: Panel Mount
 - Number of Contacts: 2
 - Time Range: 0.1 s → 300 h
 - Mode of Operation: ON Delay
 - Number of Timer Functions: Single
 - Contact Configuration: 2 x SPDT
 - Time Increment: Hours, Seconds



1792926 24 V dc

RS PRO PLUG IN SINGLE FUNCTION TIMER RELAY, 24V DC, DPDT, 0.1 → 1S

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 24 V dc
 - Mounting Type: Plug In
 - Number of Contacts: 2
 - Time Range: 0.1 s → 1 s
 - Mode of Operation: ON Delay
 - Number of Timer Functions: Single
 - Contact Configuration: DPDT
 - Time Increment: Seconds



1792947 24 V dc

RS PRO PLUG IN SINGLE FUNCTION TIMER RELAY, 24V DC, DPDT, 0.2 → 5S

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 24 V dc
 - Mounting Type: Plug In
 - Number of Contacts: 2
 - Time Range: 0.2 → 5 s
 - Mode of Operation: ON Delay
 - Number of Timer Functions: Single
 - Contact Configuration: DPDT
 - Time Increment: Seconds



1792948 24 V dc

RS PRO PLUG IN SINGLE FUNCTION TIMER RELAY, 24V DC, DPDT, 0.5 →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 24 V dc
 - Mounting Type: Plug In
 - Number of Contacts: 2
 - Time Range: 0.5 → 10 s
 - Mode of Operation: ON Delay
 - Number of Timer Functions: Single
 - Contact Configuration: DPDT
 - Time Increment: Seconds



1792949 24 V dc

RS PRO PLUG IN SINGLE FUNCTION TIMER RELAY, 24V DC, DPDT, 1 → 30S

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 24 V dc
 - Mounting Type: Plug In
 - Number of Contacts: 2
 - Time Range: 1 → 30 s
 - Mode of Operation: ON Delay
 - Number of Timer Functions: Single
 - Contact Configuration: DPDT
 - Time Increment: Seconds



1792950 24 V dc

RS PRO PLUG IN SINGLE FUNCTION TIMER RELAY, 24V DC, DPDT, 0.1 →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 24 V dc
 - Mounting Type: Plug In
 - Number of Contacts: 2
 - Time Range: 0.1 → 3 min
 - Mode of Operation: ON Delay
 - Number of Timer Functions: Single
 - Contact Configuration: DPDT
 - Time Increment: Minutes



1792953 24 V dc

RS PRO PLUG IN SINGLE FUNCTION TIMER RELAY, 24V DC, DPDT, 0.5 →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 24 V dc
 - Mounting Type: Plug In
 - Number of Contacts: 2
 - Time Range: 0.5 → 10 min
 - Mode of Operation: ON Delay
 - Number of Timer Functions: Single
 - Contact Configuration: DPDT
 - Time Increment: Minutes



1792955 24 V dc

RS PRO PLUG IN SINGLE FUNCTION TIMER RELAY, 24V DC, DPDT, 1 →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 24 V dc
 - Mounting Type: Plug In
 - Number of Contacts: 2
 - Time Range: 1 → 30 min
 - Mode of Operation: ON Delay
 - Number of Timer Functions: Single
 - Contact Configuration: DPDT
 - Time Increment: Minutes



1792956 24 V dc

RS PRO PLUG IN SINGLE FUNCTION TIMER RELAY, 24V DC, 4PDT, 0.5 →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 24 V dc
 - Mounting Type: Plug In
 - Number of Contacts: 4
 - Time Range: 0.5 → 10 s
 - Mode of Operation: ON Delay
 - Number of Timer Functions: Single
 - Contact Configuration: 4PDT
 - Time Increment: Seconds



1792979 24 V dc

RS PRO PLUG IN SINGLE FUNCTION TIMER RELAY, 24V DC, 4PDT, 1 → 30S

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 24 V dc
 - Mounting Type: Plug In
 - Number of Contacts: 4
 - Time Range: 1 → 30 s
 - Mode of Operation: ON Delay
 - Number of Timer Functions: Single
 - Contact Configuration: 4PDT
 - Time Increment: Seconds



1792981 24 V dc

RS PRO PLUG IN SINGLE FUNCTION TIMER RELAY, 24V DC, 4PDT, 0.5 →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 24 V dc
 - Mounting Type: Plug In
 - Number of Contacts: 4
 - Time Range: 0.5 → 10 min
 - Mode of Operation: ON Delay
 - Number of Timer Functions: Single
 - Contact Configuration: 4PDT
 - Time Increment: Minutes



1792985 24 V dc

RS PRO PLUG IN SINGLE FUNCTION TIMER RELAY, 24V DC, 4PDT, 1 →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 24 V dc
 - Mounting Type: Plug In
 - Number of Contacts: 4
 - Time Range: 1 → 30 min
 - Mode of Operation: ON Delay
 - Number of Timer Functions: Single
 - Contact Configuration: 4PDT
 - Time Increment: Minutes



1792986 24 V dc

TIMER, 4 DIGIT, 76X34.5, 230VAC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 230 V ac
 - Mounting Type: Clamp
 - Number of Contacts: 1
 - Mode of Operation: Interval
 - Number of Timer Functions: Single
 - Contact Configuration: NC, SPNO
 - Time Increment: Hours, Minutes, Seconds
 - Maximum Voltage: 230 V ac



7983444 230 V ac

TIMER, 4 DIGIT, 76X34.5, 10-30V

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 10 → 30 V dc
 - Mounting Type: Clamp
 - Number of Contacts: 1
 - Mode of Operation: Interval
 - Number of Timer Functions: Single
 - Contact Configuration: NC, SPNO
 - Time Increment: Hours, Minutes, Seconds
 - Maximum Voltage: 30 V dc



7983448 10 → 30 V dc

RS PRO PANEL MOUNT SINGLE FUNCTION TIMER RELAY, 230V AC,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 230 V ac
 - Mounting Type: Panel Mount
 - Number of Contacts: 1
 - Mode of Operation: One Shot
 - Number of Timer Functions: Single
 - Contact Configuration: SPDT
 - Time Increment: Minutes, Seconds
 - Maximum Voltage: 230 V ac



8086620 230 V ac

RS PRO PANEL MOUNT SINGLE FUNCTION TIMER RELAY, 24V AC/DC,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 24 V ac/dc
 - Mounting Type: Panel Mount
 - Number of Contacts: 1
 - Mode of Operation: One Shot
 - Number of Timer Functions: Single
 - Contact Configuration: SPDT
 - Time Increment: Hours, Minutes, Seconds
 - Maximum Voltage: 24 V ac/dc



8086623 24 V ac/dc

ON-DELAY TIME RELAY 240VAC & 24VAC/DC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 24 V ac/dc, 240 V ac
 - Mounting Type: DIN Rail
 - Number of Contacts: 1
 - Time Range: 0.3 s → 30 h
 - Mode of Operation: ON Delay
 - Number of Timer Functions: Single
 - Contact Configuration: SPDT
 - Time Increment: Seconds



8966810 24 V ac/dc, 240 V

TIME RELAY MULTI-FUNCTION 12- 240VAC/DC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 12 → 240 V ac/dc
 - Mounting Type: DIN Rail
 - Number of Contacts: 1
 - Time Range: 0.1 s → 100 h
 - Mode of Operation: Multifunction
 - Number of Timer Functions: Multi Function
 - Contact Configuration: SPDT
 - Time Increment: Hours, Minutes, Seconds



8966813 12 → 240 V ac/dc

RS PRO DIN RAIL SINGLE FUNCTION TIMER RELAY, 24V AC, SPDT, 0.3 S →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 24 V ac/dc, 110 V ac
 - Mounting Type: DIN Rail
 - Number of Contacts: 1
 - Time Range: 0.3 s → 30 h
 - Mode of Operation: ON Delay
 - Number of Timer Functions: Single
 - Contact Configuration: SPDT
 - Time Increment: Seconds



8966816 24 V ac/dc, 110 V

RS PRO DIN RAIL SINGLE FUNCTION TIMER RELAY, 24V AC, SPDT, 0.3 S →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 24 V ac/dc, 240 V ac
 - Mounting Type: DIN Rail
 - Number of Contacts: 1
 - Time Range: 0.3 s → 30 h
 - Mode of Operation: OFF Delay
 - Number of Timer Functions: Single
 - Contact Configuration: SPDT
 - Time Increment: Seconds



8966822 24 V ac/dc, 240 V

ASYMMETRIC RECYCLING TIME RELAY

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 12 → 240 V ac/dc
 - Mounting Type: DIN Rail
 - Number of Contacts: 1
 - Time Range: 0.1 s → 100 h
 - Mode of Operation: Asymmetric OFF/ON, Asymmetric ON/OFF
 - Number of Timer Functions: Multi Function
 - Contact Configuration: SPDT
 - Time Increment: Hours, Minutes, Seconds



8966826 12 → 240 V ac/dc

RS PRO DIN RAIL SINGLE FUNCTION TIMER RELAY, 24V AC, SPDT, 0.3 S →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 24 V ac/dc, 110 V ac
 - Mounting Type: DIN Rail
 - Number of Contacts: 1
 - Time Range: 0.3 s → 30 h
 - Mode of Operation: OFF Delay
 - Number of Timer Functions: Single
 - Contact Configuration: SPDT
 - Time Increment: Seconds



8966829 24 V ac/dc, 110 V

RS PRO DIN RAIL SINGLE FUNCTION TIMER RELAY, 240 → 415V AC, 2 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 240 → 415 V ac
 - Mounting Type: DIN Rail
 - Number of Contacts: 2
 - Time Range: 3 → 120 s
 - Mode of Operation: Star Delta
 - Number of Timer Functions: Single
 - Contact Configuration: 2 x SPNO
 - Time Increment: Seconds



8966832 240 → 415 V ac

RS PRO DIN RAIL SINGLE FUNCTION TIMER RELAY, 115V AC, SPNO, 3 →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 115 V ac
 - Mounting Type: DIN Rail
 - Number of Contacts: 2
 - Time Range: 3 → 120 s
 - Mode of Operation: Star Delta
 - Number of Timer Functions: Single
 - Contact Configuration: SPNO
 - Time Increment: Seconds



8966835 115 V ac

RS PRO DIN RAIL SINGLE FUNCTION TIMER RELAY, 240V AC, SPNO, 3 →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 240 V ac
 - Mounting Type: DIN Rail
 - Number of Contacts: 2
 - Time Range: 3 → 120 s
 - Mode of Operation: Star Delta
 - Number of Timer Functions: Single
 - Contact Configuration: SPNO
 - Time Increment: Seconds



8966838 240 V ac

DPCO TIME RELAY MULTI-RANGE 24- 240VAC/DC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 24 → 240 V ac/dc
 - Mounting Type: DIN Rail
 - Number of Contacts: 1
 - Time Range: 0.1 s → 120 days
 - Mode of Operation: Multifunction
 - Number of Timer Functions: Multi Function
 - Contact Configuration: SPDT
 - Time Increment: Seconds



8966841 24 → 240 V ac/dc

**RS PRO DIN RAIL SINGLE FUNCTION
TIMER RELAY, 24 → 240V AC/DC,**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 24 → 240 V ac/dc
 - Mounting Type: DIN Rail
 - Number of Contacts: 2
 - Time Range: 0.6 s → 600 s
 - Mode of Operation: True OFF Delay
 - Number of Timer Functions: Single
 - Contact Configuration: DPDT
 - Time Increment: Seconds


8966844 24 → 240 V ac/dc

**DPCO TIME RELAY MULTI-RANGE 24-
240VAC/DC**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 24 → 240 V ac/dc
 - Mounting Type: DIN Rail
 - Number of Contacts: 2
 - Time Range: 0.1 s → 10 h
 - Mode of Operation: ON Delay
 - Number of Timer Functions: Multi Function
 - Contact Configuration: SPDT
 - Time Increment: Seconds


8966848 24 → 240 V ac/dc

**8 FUNCTION TIME RELAY 24-
240VAC/DC**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 24 → 240 V ac/dc
 - Mounting Type: DIN Rail
 - Number of Contacts: 1
 - Time Range: 0.1 s → 999 h
 - Mode of Operation: Multifunction
 - Number of Timer Functions: Multi Function
 - Contact Configuration: SPDT
 - Time Increment: Hours, Minutes, Seconds


8966854 24 → 240 V ac/dc

**RS PRO DIN RAIL SINGLE FUNCTION
TIMER RELAY, 24 → 240V AC/DC,**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 24 → 240 V ac/dc
 - Mounting Type: DIN Rail
 - Number of Contacts: 2
 - Time Range: 3 → 120 s
 - Mode of Operation: Star Delta
 - Number of Timer Functions: Single
 - Contact Configuration: SPNO
 - Time Increment: Seconds


8966857 24 → 240 V ac/dc

**RS PRO DIN RAIL MULTI FUNCTION
TIMER RELAY, 24 → 240V AC/DC,**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 24 → 240 V ac/dc
 - Mounting Type: DIN Rail
 - Number of Contacts: 2
 - Time Range: 0.1 s → 999 h
 - Mode of Operation: Multifunction
 - Number of Timer Functions: Multi Function
 - Contact Configuration: DPNO
 - Time Increment: Hours, Minutes, Seconds


8966860 24 → 240 V ac/dc

**18 FUNCTION TIME RELAY 24-
240VAC/DC**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 24 → 240 V ac/dc
 - Mounting Type: DIN Rail
 - Number of Contacts: 1
 - Time Range: 0.1 s → 999 h
 - Mode of Operation: Multifunction
 - Number of Timer Functions: Multi Function
 - Contact Configuration: SPDT
 - Time Increment: Hours, Minutes, Seconds


8966863 24 → 240 V ac/dc

**RS PRO DIN RAIL MULTI FUNCTION
TIMER RELAY, 24 → 240V AC/DC,**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 24 → 240 V ac/dc
 - Mounting Type: DIN Rail
 - Number of Contacts: 2
 - Time Range: 0.1 s → 999 h
 - Mode of Operation: Multifunction
 - Number of Timer Functions: Multi Function
 - Contact Configuration: ZNO
 - Time Increment: Hours, Minutes, Seconds


8966866 24 → 240 V ac/dc

**RS PRO PANEL MOUNT MULTI
FUNCTION TIMER RELAY, 110 → 240V**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 110 → 240 V ac
 - Mounting Type: Panel Mount
 - Number of Contacts: 2
 - Time Range: 0.1 s → 999 days
 - Mode of Operation: Multifunction
 - Number of Timer Functions: Multi Function
 - Contact Configuration: DPDT
 - Time Increment: Days, Hours, Minutes, Seconds


8966872 110 → 240 V ac

**RS PRO PANEL MOUNT MULTI
FUNCTION TIMER RELAY, 110 → 240V**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 110 → 240 V ac
 - Mounting Type: Panel Mount
 - Number of Contacts: 2
 - Time Range: 0.1 s → 999 days
 - Mode of Operation: Multifunction
 - Number of Timer Functions: Multi Function
 - Contact Configuration: DPDT
 - Time Increment: Days, Hours, Minutes, Seconds


8966879 110 → 240 V ac

**DIG VOLTMETER, 48X96, 1PH, 40-
300V AC/DC**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Current Type: AC
 - Number of Digits: 4
 - Display Type: LED
 - Cutout Height: 43.5 mm
 - Cutout Width: 92 mm
 - Depth: 68 mm
 - Digit Height: 14 mm
 - Meter Accuracy: $\pm 0.5 + 1 \text{ Digit } \%$


1365388 AC

**RS PRO DIGITAL VOLTMETER AC, LED
DISPLAY 4-DIGITS $\pm 0.5 + 1 \text{ DIGIT } \%$**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Current Type: AC
 - Number of Digits: 4
 - Display Type: LED
 - Cutout Height: 92 mm
 - Cutout Width: 92 mm
 - Depth: 55 mm
 - Digit Height: 14 mm
 - Meter Accuracy: $\pm 0.5 + 1 \text{ Digit } \%$


1365389 AC

**RS PRO DIGITAL VOLTMETER AC, LED
DISPLAY 4-DIGITS $\pm 0.5 + 1 \text{ DIGIT } \%$**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Current Type: AC
 - Number of Digits: 4
 - Display Type: LED
 - Cutout Height: 43.5 mm
 - Cutout Width: 92 mm
 - Depth: 68 mm
 - Digit Height: 14 mm
 - Meter Accuracy: $\pm 0.5 + 1 \text{ Digit } \%$


1365393 AC

**RS PRO DIGITAL VOLTMETER AC, LED
DISPLAY 4-DIGITS $\pm 0.5 + 1 \text{ DIGIT } \%$**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Current Type: AC
 - Number of Digits: 4
 - Display Type: LED
 - Cutout Height: 92 mm
 - Cutout Width: 92 mm
 - Depth: 55 mm
 - Digit Height: 14 mm
 - Meter Accuracy: $\pm 0.5 + 1 \text{ Digit } \%$


1365394 AC

**RS PRO DIGITAL VOLTMETER, DIGITAL
DISPLAY 4-DIGITS CLASS 1.0, 90 X 90**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Number of Digits: 4
 - Display Type: Digital
 - Cutout Height: 90 mm
 - Cutout Width: 90 mm
 - Depth: 55 mm
 - Digit Height: 10 mm
 - Meter Accuracy: Class 1.0
 - Meter Type: Voltmeter


1797574 4

**RS PRO DIGITAL VOLTMETER, DIGITAL
DISPLAY 4-DIGITS CLASS 1.0, 90 X 90**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Number of Digits: 4
 - Display Type: Digital
 - Cutout Height: 90 mm
 - Cutout Width: 90 mm
 - Depth: 55 mm
 - Digit Height: 10 mm
 - Meter Accuracy: Class 1.0
 - Meter Type: Voltmeter


1797576 4

**RS PRO ANALOGUE VOLTMETER AC,
ANALOGUE DISPLAY 0.01**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Current Type: AC
 - Display Type: Analogue
 - Cutout Height: 45 mm
 - Cutout Width: 45 mm
 - Depth: 54 (-30 A) mm, 72 (30 → 60 A) mm
 - Meter Accuracy: 0.01
 - Minimum Temperature: -10 °C
 - Maximum Temperature: +65 °C


1862430 AC

RS PRO ANALOGUE VOLTMETER AC, ANALOGUE DISPLAY 0.01

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Type: AC
 - Display Type: Analogue
 - Cutout Height: 45 mm
 - Cutout Width: 45 mm
 - Depth: 54 (-30 A) mm, 72 (30 → 60 A) mm
 - Meter Accuracy: 0.01
 - Minimum Temperature: -10 °C
 - Maximum Temperature: +65 °C



1862431 AC

RS PRO ANALOGUE VOLTMETER AC, ANALOGUE DISPLAY 0.01

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Type: AC
 - Display Type: Analogue
 - Cutout Height: 68 mm
 - Cutout Width: 68 mm
 - Depth: 66 (100 A) mm
 - Meter Accuracy: 0.01
 - Minimum Temperature: -10 °C
 - Maximum Temperature: +65 °C



1862456 AC

RS PRO ANALOGUE VOLTMETER AC, ANALOGUE DISPLAY 0.01

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Type: AC
 - Display Type: Analogue
 - Cutout Height: 68 mm
 - Cutout Width: 68 mm
 - Depth: 66 (100 A) mm
 - Meter Accuracy: 0.01
 - Minimum Temperature: -10 °C
 - Maximum Temperature: +65 °C



1862457 AC

RS PRO ANALOGUE VOLTMETER AC, ANALOGUE DISPLAY 0.01

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Type: AC
 - Display Type: Analogue
 - Cutout Height: 92 mm
 - Cutout Width: 92 mm
 - Depth: 66 (100 A) mm
 - Meter Accuracy: 0.01
 - Minimum Temperature: -10 °C
 - Maximum Temperature: +65 °C



1862472 AC

RS PRO ANALOGUE VOLTMETER AC, ANALOGUE DISPLAY 0.01

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Type: AC
 - Display Type: Analogue
 - Cutout Height: 92 mm
 - Cutout Width: 92 mm
 - Depth: 66 (100 A) mm
 - Meter Accuracy: 0.01
 - Minimum Temperature: -10 °C
 - Maximum Temperature: +65 °C



1862473 AC

RS PRO DIGITAL VOLTMETER DC, LED DISPLAY 1%

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Type: DC
 - Display Type: LED
 - Cutout Height: 37 mm
 - Cutout Width: 25 mm
 - Meter Accuracy: 1%
 - Meter Type: Battery Meter



2337810 DC

LEAD-ACID BATTERY INDICATOR, 12/24VDC. D

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Type: DC
 - Display Type: LED
 - Cutout Height: 27.1 mm
 - Cutout Width: 32 mm
 - Meter Accuracy: 1%
 - Meter Type: Battery Meter



2337811 DC

AC VOLTMETER 48X48MM 90 DEG SCALE 300V

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Type: AC
 - Cutout Height: 46 mm
 - Cutout Width: 46 mm
 - Depth: 39 mm
 - Meter Accuracy: 1.5 %
 - Minimum Temperature: -25 °C
 - Meter Type: Voltmeter
 - Maximum Temperature: +50 °C



9010514 AC

AC VOLTMETER 72X72MM 90 DEG SCALE 500V

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Type: AC
 - Cutout Height: 68 mm
 - Cutout Width: 68 mm
 - Depth: 36.5 mm
 - Meter Accuracy: ±1.5 %
 - Minimum Temperature: -25 °C
 - Meter Type: Voltmeter
 - Maximum Temperature: +50 °C



9010520 AC

AC VOLTMETER 48X48MM 90 DEG SCALE 500V

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Type: AC
 - Cutout Height: 46 mm
 - Cutout Width: 46 mm
 - Depth: 39 mm
 - Meter Accuracy: 1.5 %
 - Minimum Temperature: -25 °C
 - Meter Type: Voltmeter
 - Maximum Temperature: +50 °C



9010523 AC

RS PRO ANALOGUE VOLTMETER AC ±1.5 %, 68 X 68 MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Type: AC
 - Cutout Height: 68 mm
 - Cutout Width: 68 mm
 - Depth: 36.5 mm
 - Meter Accuracy: ±1.5 %
 - Minimum Temperature: -25 °C
 - Meter Type: Voltmeter
 - Maximum Temperature: +50 °C



9010526 AC

AC VOLTMETER 96X96MM 90 DEG SCALE 500V

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Type: AC
 - Cutout Height: 92 mm
 - Cutout Width: 92 mm
 - Depth: 45 mm
 - Meter Accuracy: ±1.5 %
 - Minimum Temperature: -25 °C
 - Meter Type: Voltmeter
 - Maximum Temperature: +50 °C



9010532 AC

AC VOLTMETER 96X96MM 90 DEG SCALE 300V

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Type: AC
 - Cutout Height: 92 mm
 - Cutout Width: 92 mm
 - Depth: 45 mm
 - Meter Accuracy: ±1.5 %
 - Minimum Temperature: -25 °C
 - Meter Type: Voltmeter
 - Maximum Temperature: +50 °C



9010539 AC

RS PRO ANALOGUE VOLTMETER DC ±1.5 %, 68 X 68 MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Type: DC
 - Cutout Height: 68 mm
 - Cutout Width: 68 mm
 - Depth: 36.5 mm
 - Meter Accuracy: ±1.5 %
 - Minimum Temperature: -25 °C
 - Meter Type: Voltmeter
 - Maximum Temperature: +50 °C



9010542 DC

DC VOLTMETER 48X48MM 90 DEG SCALE 150V

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Type: DC
 - Cutout Height: 46 mm
 - Cutout Width: 46 mm
 - Depth: 39 mm
 - Meter Accuracy: 1.5 %
 - Minimum Temperature: -25 °C
 - Meter Type: Voltmeter
 - Maximum Temperature: +50 °C



9010548 DC

DC VOLTMETER 72X72MM 90 DEG SCALE 40V

- ขนาดบรรจุภัณฑ์: 1 x EA
- Current Type: DC
 - Cutout Height: 68 mm
 - Cutout Width: 68 mm
 - Depth: 36.5 mm
 - Meter Accuracy: ±1.5 %
 - Minimum Temperature: -25 °C
 - Meter Type: Voltmeter
 - Maximum Temperature: +50 °C



9010551 DC

**RS PRO ANALOGUE VOLTMETER DC
±1.5 %, 68 X 68 MM**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Current Type: DC
 - Cutout Height: 68 mm
 - Cutout Width: 68 mm
 - Depth: 36.5 mm
 - Meter Accuracy: ±1.5 %
 - Minimum Temperature: -25 °C
 - Meter Type: Voltmeter
 - Maximum Temperature: +50 °C


9010554 DC

**RS PRO ANALOGUE VOLTMETER DC
±1.5 %, 92 X 92 MM**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Current Type: DC
 - Cutout Height: 92 mm
 - Cutout Width: 92 mm
 - Depth: 45 mm
 - Meter Accuracy: ±1.5 %
 - Minimum Temperature: -25 °C
 - Meter Type: Voltmeter
 - Maximum Temperature: +50 °C


9010558 DC

**RS PRO ANALOGUE VOLTMETER DC
±1.5 %, 90.5 X 90.5 MM**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Current Type: DC
 - Cutout Height: 90.5 mm
 - Cutout Width: 90.5 mm
 - Depth: 45 mm
 - Meter Accuracy: ±1.5 %
 - Minimum Temperature: -25 °C
 - Meter Type: Voltmeter
 - Maximum Temperature: +50 °C


9010560 DC

**RS PRO ANALOGUE VOLTMETER DC
±1.5 %, 92 X 92 MM**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Current Type: DC
 - Cutout Height: 92 mm
 - Cutout Width: 92 mm
 - Depth: 45 mm
 - Meter Accuracy: ±1.5 %
 - Minimum Temperature: -25 °C
 - Meter Type: Voltmeter
 - Maximum Temperature: +50 °C


9010567 DC



PART OF **RS** GROUP



ติดต่อเราเพื่อสั่งซื้อ

อีเมล: mktg@dhrit.com

เบอร์: 02 678 2224 , 06 4159 0479

Line ID: @domnickhunterr1

ที่อยู่: บริษัท ดอมนิค ฮันเตอร์-อาร์แอล (ประเทศไทย) จำกัด

99/1-3 ถ.นราธิวาสราชนครินทร์ แขวง ซ่องนนทรี เขต ยานนาวา กรุงเทพฯ 10120



@domnickhunterr1

บริษัท อาร์เอส คอมโพเน็นส์ จำกัด

ฝ่ายคำสั่งซื้อ

orders.TH@rsgroup.com

เบอร์: 02 648 6868

ฝ่ายตอบข้อมูลสอบถาม

rcustomerserviceth@rsgroup.com

ฝ่ายสนับสนุนทางเทคนิค

tech.TH@rsgroup.com

ที่ตั้งสำนักงาน

บริษัท อาร์เอส คอมโพเน็นส์ จำกัด (สำนักงานใหญ่)

50 จีเอ็มเอ็ม แกรมมีเพลส ชั้นที่ 19

ห้อง 1901-1904 ถนนสุขุมวิท 21 (อโศก) แขวงคลองตันเหนือ

เขตวัฒนา จังหวัดกรุงเทพมหานคร ประเทศไทย 10110

