

RS PRO Range Guide

Your Smart Choice for

HYDRAULICS & PNEUMATICS



p.2

Hose
& Pumps



p.37

Hydraulics



p.46

Plumbing



p.73

Pneumatics



RS PRO COMPRESSED AIR PIPE BLUE PUR, PVC 6MM X 30M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Inside Diameter: 4 mm
 - Hose Outside Diameter: 6 mm
 - Colour: Blue
 - Material: PUR, PVC
 - Length: 30 m
 - Maximum Operating Pressure: 40 bar
 - Minimum Operating Temperature: -15 °C
 - Maximum Operating Temperature: +60 °C



1745728 4 mm

RS PRO COMPRESSED AIR PIPE BLUE PUR, PVC 8MM X 30M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Inside Diameter: 5 mm
 - Hose Outside Diameter: 8 mm
 - Colour: Blue
 - Material: PUR, PVC
 - Length: 30 m
 - Maximum Operating Pressure: 40 bar
 - Minimum Operating Temperature: -15 °C
 - Maximum Operating Temperature: +60 °C



1745733 5 mm

RS PRO COMPRESSED AIR PIPE BLUE PUR, PVC 10MM X 30M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Inside Diameter: 6.5 mm
 - Hose Outside Diameter: 10 mm
 - Colour: Blue
 - Material: PUR, PVC
 - Length: 30 m
 - Maximum Operating Pressure: 30 bar
 - Minimum Operating Temperature: -15 °C
 - Maximum Operating Temperature: +60 °C



1745737 6.5 mm

RS PRO COMPRESSED AIR PIPE GREY PUR, PVC 10MM X 30M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Inside Diameter: 6.5 mm
 - Hose Outside Diameter: 10 mm
 - Colour: Grey
 - Material: PUR, PVC
 - Length: 30 m
 - Maximum Operating Pressure: 30 bar
 - Minimum Operating Temperature: -15 °C
 - Maximum Operating Temperature: +60 °C



1745738 6.5 mm

RS PRO COMPRESSED AIR PIPE WHITE PUR, PVC 10MM X 30M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Inside Diameter: 6.5 mm
 - Hose Outside Diameter: 10 mm
 - Colour: White
 - Material: PUR, PVC
 - Length: 30 m
 - Maximum Operating Pressure: 30 bar
 - Minimum Operating Temperature: -15 °C
 - Maximum Operating Temperature: +60 °C



1745739 6.5 mm

RS PRO COMPRESSED AIR PIPE BLUE PUR, PVC 12MM X 30M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Inside Diameter: 8 mm
 - Hose Outside Diameter: 12 mm
 - Colour: Blue
 - Material: PUR, PVC
 - Length: 30 m
 - Maximum Operating Pressure: 26 bar
 - Minimum Operating Temperature: -15 °C
 - Maximum Operating Temperature: +60 °C



1745741 8 mm

RS PRO COMPRESSED AIR PIPE PE 6MM X 30M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Inside Diameter: 4 mm
 - Hose Outside Diameter: 6 mm
 - Material: PE
 - Application: Food Industry
 - Length: 30 m



2020982 4 mm

RS PRO COMPRESSED AIR PIPE NATURAL PE 8MM X 30M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Inside Diameter: 5 mm
 - Hose Outside Diameter: 8 mm
 - Colour: Natural
 - Material: PE
 - Application: Food Industry
 - Length: 30 m



2020984 5 mm

RS PRO COMPRESSED AIR PIPE NATURAL PE 10MM X 30M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Inside Diameter: 7 mm
 - Hose Outside Diameter: 10 mm
 - Colour: Natural
 - Material: PE
 - Application: Food Industry
 - Length: 30 m



2020986 7 mm

RS PRO COMPRESSED AIR PIPE BLUE PUR 10MM X 25M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Inside Diameter: 6.5 mm
 - Hose Outside Diameter: 10 mm
 - Colour: Blue
 - Material: PUR
 - Length: 25 m
 - Maximum Operating Pressure: 10 bar
 - Minimum Operating Temperature: 0 °C
 - Maximum Operating Temperature: +60 °C



2395725 6.5 mm

RS PRO FITTING FITTING M5

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Fitting Type: Fitting
 - Thread Size 1: M5



1762043 Fitting

RS PRO FITTING FITTING 1/8IN

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Fitting Type: Fitting
 - Thread Size 1: 1/8 in



1762044 Fitting

RS PRO FITTING FITTING 1/4IN

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Fitting Type: Fitting
 - Thread Size 1: 1/4 in



1762045 Fitting

RS PRO FITTING FITTING 3/8IN

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Fitting Type: Fitting
 - Thread Size 1: 3/8 in



1762046 Fitting

RS PRO PUR 10M LONG CLEAR, GREY FLEXIBLE DUCTING REINFORCED, 25

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 25.4 mm
 - Outer Diameter: 30.5 mm
 - Material: PUR
 - Length: 10 m
 - Suitable Applications: Abrasive Material, Agriculture, Construction Industries, Fumes, Grain, Grit, Hazardous Areas, Industrial, Industrial Vacuum Cleaners, Marine, Mining, Saw Dust, Sugar, Wood Chip
 - Colour: Clear, Grey
 - Bend Radius: (Minimum) 25 mm
 - Reinforced: Yes



1369452 25.4 mm

RS PRO PUR 10M LONG ICTA FLEXIBLE CONDUIT REINFORCED, 32

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 32 mm
 - Outer Diameter: 38 mm
 - Material: PUR
 - Length: 10 m
 - Suitable Applications: Abrasive Materials, Fumes
 - Colour: Clear, Grey
 - Bend Radius: (Minimum) 32 mm
 - Reinforced: Yes



1369453 32 mm

RS PRO PUR 10M LONG ICTA FLEXIBLE CONDUIT REINFORCED, 38

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 38 mm
 - Outer Diameter: 44.4 mm
 - Material: PUR
 - Length: 10 m
 - Suitable Applications: Abrasive Materials, Fumes
 - Colour: Clear, Grey
 - Bend Radius: (Minimum) 38 mm
 - Reinforced: Yes



1369454 38 mm

RS PRO PUR, PVC 10M LONG FLEXIBLE DUCTING REINFORCED, 51

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 51 mm
 - Outer Diameter: 59 mm
 - Material: PUR, PVC
 - Length: 10 m
 - Suitable Applications: Abrasive Materials, Agricultural, Construction, Extraction of Fumes, Extraction of Grain, Extraction of Grit, Extraction of Sawdust, Extraction of Sugar, Extraction of Wood Chippings, Hazardous Areas, Industrial, Industrial Vacuum Cleaners, Marine, Mining
 - Bend Radius: (Minimum) 51 mm
 - Reinforced: Yes



1369455 51 mm

RS PRO PUR, PVC 10M LONG FLEXIBLE DUCTING REINFORCED, 63

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 63 mm
 - Outer Diameter: 70.6 mm
 - Material: PUR, PVC
 - Length: 10 m
 - Suitable Applications: Abrasive Materials, Agricultural, Construction, Extraction of Fumes, Extraction of Grain, Extraction of Grit, Extraction of Sawdust, Extraction of Sugar, Extraction of Wood Chippings, Hazardous Areas, Industrial, Industrial Vacuum Cleaners, Marine, Mining
 - Bend Radius: (Minimum) 63 mm
 - Reinforced: Yes



1369456 63 mm

RS PRO PUR, PVC 10M LONG FLEXIBLE DUCTING REINFORCED, 76

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 76 mm
 - Outer Diameter: 84.8 mm
 - Material: PUR, PVC
 - Length: 10 m
 - Suitable Applications: Abrasive Materials, Agricultural, Construction, Extraction of Fumes, Extraction of Grain, Extraction of Grit, Extraction of Sawdust, Extraction of Sugar, Extraction of Wood Chippings, Hazardous Areas, Industrial, Industrial Vacuum Cleaners, Marine, Mining
 - Bend Radius: (Minimum) 76 mm
 - Reinforced: Yes



1369457 76 mm

RS PRO PUR 10M LONG FLEXIBLE DUCTING REINFORCED, 102

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 102 mm
 - Outer Diameter: 113 mm
 - Material: PUR
 - Length: 10 m
 - Suitable Applications: Abrasive Materials, Fumes
 - Colour: Clear, Grey
 - Bend Radius: (Minimum) 102 mm
 - Reinforced: Yes



1369459 102 mm

RS PRO PUR 5M LONG ICTA FLEXIBLE CONDUIT REINFORCED, 102

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 102 mm
 - Outer Diameter: 113 mm
 - Material: PUR
 - Length: 5 m
 - Suitable Applications: Abrasive Materials, Fumes
 - Colour: Clear, Grey
 - Bend Radius: (Minimum) 102 mm
 - Reinforced: Yes



1369460 102 mm

RS PRO PUR 5M LONG FLEXIBLE DUCTING REINFORCED, 152

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 152 mm
 - Outer Diameter: 164.4 mm
 - Material: PUR
 - Length: 5 m
 - Suitable Applications: Abrasive Materials, Fumes
 - Colour: Clear
 - Bend Radius: (Minimum) 152 mm
 - Reinforced: Yes



1369461 152 mm

RS PRO PVC 10M LONG FLEXIBLE DUCTING REINFORCED, 32

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 32 mm
 - Outer Diameter: 38.6 mm
 - Material: PVC
 - Length: 10 m
 - Suitable Applications: Abrasive Materials, Fumes
 - Colour: Dark Grey
 - Bend Radius: (Minimum) 32 mm
 - Reinforced: Yes



1369475 32 mm

RS PRO PVC 10M LONG FLEXIBLE DUCTING REINFORCED, 38

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 38 mm
 - Outer Diameter: 44.8 mm
 - Material: PVC
 - Length: 10 m
 - Suitable Applications: Abrasive Materials, Fumes
 - Colour: Dark Grey
 - Bend Radius: (Minimum) 38 mm
 - Reinforced: Yes



1369476 38 mm

RS PRO PVC 10M LONG FLEXIBLE DUCTING REINFORCED, 51

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 51.6 mm
 - Outer Diameter: 58.6 mm
 - Material: PVC
 - Length: 10 m
 - Suitable Applications: Abrasive Materials, Fumes
 - Colour: Dark Grey
 - Bend Radius: (Minimum) 51 mm
 - Reinforced: Yes



1369477 51.6 mm

RS PRO PVC 5M LONG FLEXIBLE DUCTING REINFORCED, 51

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 51.6 mm
 - Outer Diameter: 58.6 mm
 - Material: PVC
 - Length: 5 m
 - Suitable Applications: Abrasive Materials, Fumes
 - Colour: Dark Grey
 - Bend Radius: (Minimum) 51 mm
 - Reinforced: Yes



1369478 51.6 mm

RS PRO PVC 10M LONG FLEXIBLE DUCTING REINFORCED, 63

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 63.5 mm
 - Outer Diameter: 71.5 mm
 - Material: PVC
 - Length: 10 m
 - Suitable Applications: Abrasive Materials, Fumes
 - Colour: Dark Grey
 - Bend Radius: (Minimum) 63 mm
 - Reinforced: Yes



1369479 63.5 mm

RS PRO PVC 5M LONG FLEXIBLE DUCTING REINFORCED, 63

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 63.5 mm
 - Outer Diameter: 71.5 mm
 - Material: PVC
 - Length: 5 m
 - Suitable Applications: Abrasive Materials, Fumes
 - Colour: Dark Grey
 - Bend Radius: (Minimum) 63 mm
 - Reinforced: Yes



1369480 63.5 mm

RS PRO PVC 10M LONG FLEXIBLE DUCTING REINFORCED, 76

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 76 mm
 - Outer Diameter: 85 mm
 - Material: PVC
 - Length: 10 m
 - Suitable Applications: Abrasive Materials, Fumes
 - Colour: Dark Grey
 - Bend Radius: (Minimum) 76 mm
 - Reinforced: Yes



1369481 76 mm

RS PRO PVC 5M LONG FLEXIBLE DUCTING REINFORCED, 76

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 76 mm
 - Outer Diameter: 85 mm
 - Material: PVC
 - Length: 5 m
 - Suitable Applications: Abrasive Materials, Fumes
 - Colour: Dark Grey
 - Bend Radius: (Minimum) 76 mm
 - Reinforced: Yes



1369482 76 mm

RS PRO PVC 5M LONG FLEXIBLE DUCTING REINFORCED

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Material: PVC
 - Length: 5 m
 - Suitable Applications: Abrasive Materials, Fumes
 - Colour: Dark Grey
 - Reinforced: Yes



1369484 PVC

RS PRO PVC 10M LONG FLEXIBLE DUCTING REINFORCED, 102

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 102 mm
 - Outer Diameter: 112 mm
 - Material: PVC
 - Length: 10 m
 - Suitable Applications: Abrasive Materials, Fumes
 - Colour: Dark Grey
 - Bend Radius: (Minimum) 102 mm
 - Reinforced: Yes



1369485 102 mm

RS PRO PVC 5M LONG FLEXIBLE DUCTING REINFORCED, 102

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 102 mm
 - Outer Diameter: 112 mm
 - Material: PVC
 - Length: 5 m
 - Suitable Applications: Abrasive Materials, Fumes
 - Colour: Dark Grey
 - Bend Radius: (Minimum) 102 mm
 - Reinforced: Yes



1369486 102 mm

RS PRO PVC 10M LONG FLEXIBLE DUCTING REINFORCED, 127

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 127 mm
 - Outer Diameter: 138 mm
 - Material: PVC
 - Length: 10 m
 - Suitable Applications: Abrasive Materials, Fumes
 - Colour: Dark Grey
 - Bend Radius: (Minimum) 127 mm
 - Reinforced: Yes



1369487 127 mm

RS PRO PVC 5M LONG FLEXIBLE DUCTING REINFORCED, 127


- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 127 mm
 - Outer Diameter: 138 mm
 - Material: PVC
 - Length: 5 m
 - Suitable Applications: Abrasive Materials, Fumes
 - Colour: Dark Grey
 - Bend Radius: (Minimum) 127 mm
 - Reinforced: Yes



1369488 127 mm

RS PRO FLEXIBLE HOSE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Inside Diameter: 8 mm
 - Hose Outside Diameter: 13 mm
 - Colour: Blue
 - Material: PVC
 - Length: 10 m
 - Maximum Operating Pressure: 20 bar
 - Minimum Operating Temperature: -15 °C
 - Maximum Operating Temperature: +60 °C



1745719 8 mm

RS PRO FLAT ROLL-UP HOSE WITH COUPLINGS, 3 BAR, 25M LONG

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 25 m
 - Material: PVC
 - Maximum Working Pressure: 3 bar
 - Suitable Applications: Chemical, Water



1860543 25 m

RS PRO FLEXIBLE HOSE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Inside Diameter: 6 mm
 - Hose Outside Diameter: 14 mm
 - Colour: Red
 - Material: PVC Nitrile Blend
 - Application: Compressed Air Tools, Garages, Workshops
 - Length: 5 m
 - Maximum Operating Pressure: 20 bar
 - Minimum Operating Temperature: -25 °C



9120904 6 mm

RS PRO FLEXIBLE HOSE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Inside Diameter: 6 mm
 - Hose Outside Diameter: 14 mm
 - Colour: Red
 - Material: PVC Nitrile Blend
 - Application: Compressed Air Tools, Garages, Workshops
 - Length: 20 m
 - Maximum Operating Pressure: 20 bar
 - Minimum Operating Temperature: -25 °C



9120910 6 mm

RS PRO FLEXIBLE HOSE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Inside Diameter: 8 mm
 - Hose Outside Diameter: 15 mm
 - Colour: Red
 - Material: PVC Nitrile Blend
 - Application: Compressed Air Tools, Garages, Workshops
 - Length: 10 m
 - Maximum Operating Pressure: 20 bar
 - Minimum Operating Temperature: -25 °C



9120923 8 mm

RS PRO FLEXIBLE HOSE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Inside Diameter: 8 mm
 - Hose Outside Diameter: 15 mm
 - Colour: Red
 - Material: PVC Nitrile Blend
 - Application: Compressed Air Tools, Garages, Workshops
 - Length: 5 m
 - Maximum Operating Pressure: 20 bar
 - Minimum Operating Temperature: -25 °C



9120914 8 mm

RS PRO FLEXIBLE HOSE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Inside Diameter: 10 mm
 - Hose Outside Diameter: 17 mm
 - Colour: Red
 - Material: PVC Nitrile Blend
 - Application: Compressed Air Tools, Garages, Workshops
 - Length: 5 m
 - Maximum Operating Pressure: 20 bar
 - Minimum Operating Temperature: -25 °C



9120939 10 mm

RS PRO FLEXIBLE HOSE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Inside Diameter: 8 mm
 - Hose Outside Diameter: 15 mm
 - Colour: Red
 - Material: PVC Nitrile Blend
 - Application: Compressed Air Tools, Garages, Workshops
 - Length: 20 m
 - Maximum Operating Pressure: 20 bar
 - Minimum Operating Temperature: -25 °C



9120920 8 mm

RS PRO FLEXIBLE HOSE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Inside Diameter: 13 mm
 - Hose Outside Diameter: 21 mm
 - Colour: Red
 - Material: PVC Nitrile Blend
 - Application: Compressed Air Tools, Garages, Workshops
 - Length: 10 m
 - Maximum Operating Pressure: 20 bar
 - Minimum Operating Temperature: -25 °C



9120942 13 mm

RS PRO FLEXIBLE HOSE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Inside Diameter: 13 mm
 - Hose Outside Diameter: 21 mm
 - Colour: Red
 - Material: PVC Nitrile Blend
 - Application: Compressed Air Tools, Garages, Workshops
 - Length: 5 m
 - Maximum Operating Pressure: 20 bar
 - Minimum Operating Temperature: -25 °C



9120948 13 mm

RS PRO FLEXIBLE HOSE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Inside Diameter: 13 mm
 - Hose Outside Diameter: 21 mm
 - Colour: Red
 - Material: PVC Nitrile Blend
 - Application: Compressed Air Tools, Garages, Workshops
 - Length: 20 m
 - Maximum Operating Pressure: 20 bar
 - Minimum Operating Temperature: -25 °C



9120954 13 mm

RS PRO HOSE CONNECTOR, STRAIGHT CAMLOCK ADAPTOR, BSPT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Connector Type: Camlock Adaptor
 - Connector Gender: Female
 - Coupling Connector Direction: Straight
 - Thread Standard: BSPT
 - Thread Size: 2 in
 - Hose Inner Diameter: 2 in
 - Maximum Working Pressure: 17 bar
 - Body Material: Stainless Steel



307178 Camlock Adaptor

COUPLING,STAINLESS STEEL 316,CAM AND GROOVE,PART C ADAPTOR,1IN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Connector Type: Camlock Coupling
 - Connector Gender: Male
 - Coupling Connector Direction: Straight
 - Thread Size: 1 in
 - Hose Inner Diameter: 1 in
 - Maximum Working Pressure: 17 bar
 - Body Material: Stainless Steel



307213 Camlock

RS PRO HOSE CONNECTOR, STRAIGHT CAMLOCK COUPLING 1-

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Connector Type: Camlock Coupling
 - Connector Gender: Female
 - Coupling Connector Direction: Straight
 - Thread Size: 1-1/2 in
 - Hose Inner Diameter: 1-1/2 in
 - Maximum Working Pressure: 17 bar
 - Body Material: Stainless Steel



307229 Camlock

RS PRO HOSE CONNECTOR, STRAIGHT CAMLOCK COUPLING 2IN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Connector Type: Camlock Coupling
 - Connector Gender: Female
 - Coupling Connector Direction: Straight
 - Thread Size: 2 in
 - Hose Inner Diameter: 2 in
 - Maximum Working Pressure: 17 bar
 - Body Material: Stainless Steel



307235 Camlock

COUPLING,STAINLESS STEEL 316,CAM AND GROOVE,PART E ADAPTOR,1IN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Connector Type: Camlock Adaptor
 - Connector Gender: Female
 - Coupling Connector Direction: Straight
 - Thread Size: 1 in
 - Hose Inner Diameter: 1 in
 - Maximum Working Pressure: 17 bar
 - Body Material: Stainless Steel



307279 Camlock Adaptor

RS PRO HOSE CONNECTOR, STRAIGHT CAMLOCK ADAPTOR 1-

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Connector Type: Camlock Adaptor
 - Connector Gender: Female
 - Coupling Connector Direction: Straight
 - Thread Size: 1-1/2 in
 - Hose Inner Diameter: 1-1/2 in
 - Maximum Working Pressure: 17 bar
 - Body Material: Stainless Steel



307285 Camlock Adaptor

RS PRO HOSE CONNECTOR, STRAIGHT CAM & GROOVE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Connector Type: Cam & Groove Coupling
 - Connector Gender: Female
 - Coupling Connector Direction: Straight
 - Thread Size: 2 in
 - Hose Inner Diameter: 2 in
 - Maximum Working Pressure: 17 bar
 - Body Material: Stainless Steel



307291 Cam & Groove

RS PRO HOSE CONNECTOR, STRAIGHT CAM & GROOVE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Connector Type: Cam & Groove Coupling
 - Connector Gender: Male
 - Coupling Connector Direction: Straight
 - Thread Standard: BSPT
 - Thread Size: 1 in
 - Hose Inner Diameter: 1 in
 - Maximum Working Pressure: 17 bar
 - Body Material: Stainless Steel



307308 Cam & Groove

RS PRO HOSE CONNECTOR, STRAIGHT CAMLOCK ADAPTOR, R 1-

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Connector Type: Camlock Adaptor
 - Connector Gender: Male
 - Coupling Connector Direction: Straight
 - Thread Standard: R
 - Thread Size: 1-1/2 in
 - Hose Inner Diameter: 1-1/2 in
 - Maximum Working Pressure: 17 bar
 - Body Material: Stainless Steel



307314 Camlock Adaptor

RS PRO HOSE CONNECTOR, STRAIGHT CAMLOCK ADAPTOR, R 2IN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Connector Type: Camlock Adaptor
 - Connector Gender: Male
 - Coupling Connector Direction: Straight
 - Thread Standard: R
 - Thread Size: 2 in
 - Hose Inner Diameter: 2 in
 - Maximum Working Pressure: 17 bar
 - Body Material: Stainless Steel



307320 Camlock Adaptor

RS PRO HOSE CONNECTOR DUST CAP 2IN ID

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Connector Type: Dust Cap
 - Hose Inner Diameter: 2 in
 - Body Material: Stainless Steel



307358 Dust Cap

RS PRO HOSE CONNECTOR, STRAIGHT CAMLOCK ADAPTOR, BSPT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Connector Type: Camlock Adaptor
 - Connector Gender: Female
 - Coupling Connector Direction: Straight
 - Thread Standard: BSPT
 - Thread Size: 1-1/2 in
 - Hose Inner Diameter: 1-1/2 in
 - Maximum Working Pressure: 17 bar
 - Body Material: Stainless Steel



317507 Camlock Adaptor

CONNECTOR,HOSE,POLYAMIDE,TAPE R BSP,5MM I/DX1/4IN BSP

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Hose Connector Type: Hose Tail Adaptor
 - Connector Gender: Male
 - Coupling Connector Direction: Straight
 - Thread Standard: BSP
 - Thread Size: 1/4 in
 - Hose Inner Diameter: 5 mm
 - Body Material: Nylon



795095 Hose Tail Adaptor

CONNECTOR,HOSE,POLYAMIDE,TAPE R BSP,6MM I/DX1/8IN BSP

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Hose Connector Type: Hose Tail Adaptor
 - Connector Gender: Male
 - Coupling Connector Direction: Straight
 - Thread Standard: BSP
 - Thread Size: 1/8 in
 - Hose Inner Diameter: 6 mm
 - Body Material: Nylon



795102 Hose Tail Adaptor

CONNECTOR,HOSE,POLYAMIDE,TAPE R BSP,6MM I/DX1/4IN BSP

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Hose Inner Diameter: 6 mm
 - Coupling Connector Type: Adaptor
 - Body Material: Nylon
 - Threaded Connection: 1/4 in BSP Male
 - Thread Size: 1/4 in
 - Coupling Gender: Male
 - Coupling Connector Direction: Straight
 - Thread Gender: Male



795118 6 mm

CONNECTOR,HOSE,POLYAMIDE,TAPE R BSP,8MM I/DX1/8IN BSP

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Hose Connector Type: Hose Tail Adaptor
 - Connector Gender: Male
 - Coupling Connector Direction: Straight
 - Thread Standard: BSP
 - Thread Size: 1/8 in
 - Hose Inner Diameter: 8 mm
 - Body Material: Nylon



795130 Hose Tail Adaptor

CONNECTOR,HOSE,POLYAMIDE,TAPE R BSP,8MM I/DX1/4IN BSP

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Hose Connector Type: Hose Tail Adaptor
 - Connector Gender: Male
 - Coupling Connector Direction: Straight
 - Thread Standard: BSP
 - Thread Size: 1/4 in
 - Hose Inner Diameter: 8 mm
 - Body Material: Nylon



795146 Hose Tail Adaptor

RS PRO HOSE CONNECTOR, STRAIGHT HOSE TAIL ADAPTOR, BSP

- ขนาดบรรจุภัณฑ์: 5 x EA
- Hose Connector Type: Hose Tail Adaptor
 - Connector Gender: Male
 - Coupling Connector Direction: Straight
 - Thread Standard: BSP
 - Thread Size: 3/8 in
 - Hose Inner Diameter: 8 mm
 - Body Material: Nylon



795152 Hose Tail Adaptor

RS PRO HOSE CONNECTOR, STRAIGHT HOSE TAIL ADAPTOR, BSP

- ขนาดบรรจุภัณฑ์: 5 x EA
- Hose Connector Type: Hose Tail Adaptor
 - Connector Gender: Male
 - Coupling Connector Direction: Straight
 - Thread Standard: BSP
 - Thread Size: 1/2 in
 - Hose Inner Diameter: 8 mm
 - Body Material: Nylon



795168 Hose Tail Adaptor

CONNECTOR,HOSE,POLYAMIDE,TAPE R BSP,10MM 1/DX1/4IN BSP

- ขนาดบรรจุภัณฑ์: 5 x EA
- Hose Connector Type: Hose Tail Adaptor
 - Connector Gender: Male
 - Coupling Connector Direction: Straight
 - Thread Standard: BSP
 - Thread Size: 1/4 in
 - Hose Inner Diameter: 10 mm
 - Body Material: Nylon



795174 Hose Tail Adaptor

RS PRO HOSE CONNECTOR, STRAIGHT HOSE TAIL ADAPTOR, BSP

- ขนาดบรรจุภัณฑ์: 5 x EA
- Hose Connector Type: Hose Tail Adaptor
 - Connector Gender: Male
 - Coupling Connector Direction: Straight
 - Thread Standard: BSP
 - Thread Size: 3/8 in
 - Hose Inner Diameter: 10 mm
 - Body Material: Nylon



795180 Hose Tail Adaptor

RS PRO HOSE CONNECTOR, STRAIGHT HOSE TAIL ADAPTOR, BSP

- ขนาดบรรจุภัณฑ์: 5 x EA
- Hose Connector Type: Hose Tail Adaptor
 - Connector Gender: Male
 - Coupling Connector Direction: Straight
 - Thread Standard: BSP
 - Thread Size: 3/8 in
 - Hose Inner Diameter: 12 mm
 - Body Material: Nylon



795196 Hose Tail Adaptor

CONNECTOR,HOSE,POLYAMIDE,TAPE R BSP,12MM 1/DX1/2IN BSP

- ขนาดบรรจุภัณฑ์: 5 x EA
- Hose Inner Diameter: 12 mm
 - Body Material: Nylon
 - Threaded Connection: 1/2 in BSP Male
 - Thread Size: 1/2 in
 - Coupling Gender: Male
 - Coupling Connector Direction: Straight
 - Thread Standard: BSP



795203 12 mm

RS PRO HOSE CONNECTOR, STRAIGHT HOSE TAIL ADAPTOR, BSP

- ขนาดบรรจุภัณฑ์: 5 x EA
- Hose Connector Type: Hose Tail Adaptor
 - Connector Gender: Male
 - Coupling Connector Direction: Straight
 - Thread Standard: BSP
 - Thread Size: 3/4 in
 - Hose Inner Diameter: 19 mm
 - Body Material: Nylon



795219 Hose Tail Adaptor

CONNECTOR,HOSE,POLYAMIDE,ELBOW,TAPER BSP,6MM 1/DX1/4IN BSP

- ขนาดบรรจุภัณฑ์: 5 x EA
- Hose Connector Type: Hose Tail Adaptor
 - Connector Gender: Male
 - Coupling Connector Direction: Elbow
 - Thread Standard: BSP
 - Thread Size: 1/4 in
 - Hose Inner Diameter: 6 mm
 - Body Material: Nylon



795225 Hose Tail Adaptor

RS PRO HOSE CONNECTOR, ELBOW HOSE TAIL ADAPTOR, BSP 1/8IN 8MM

- ขนาดบรรจุภัณฑ์: 5 x EA
- Hose Connector Type: Hose Tail Adaptor
 - Connector Gender: Male
 - Coupling Connector Direction: Elbow
 - Thread Standard: BSP
 - Thread Size: 1/8 in
 - Hose Inner Diameter: 8 mm
 - Body Material: Nylon



795247 Hose Tail Adaptor

CONNECTOR,HOSE,POLYAMIDE,ELBOW,TAPER BSP,8MM 1/DX1/4IN BSP

- ขนาดบรรจุภัณฑ์: 5 x EA
- Hose Connector Type: Hose Tail Adaptor
 - Connector Gender: Male
 - Coupling Connector Direction: Elbow
 - Thread Standard: BSP
 - Thread Size: 1/4 in
 - Hose Inner Diameter: 8 mm
 - Body Material: Nylon



795253 Hose Tail Adaptor

RS PRO HOSE CONNECTOR, ELBOW HOSE TAIL ADAPTOR, BSP 3/8IN 8MM

- ขนาดบรรจุภัณฑ์: 5 x EA
- Hose Connector Type: Hose Tail Adaptor
 - Connector Gender: Male
 - Coupling Connector Direction: Elbow
 - Thread Standard: BSP
 - Thread Size: 3/8 in
 - Hose Inner Diameter: 8 mm
 - Body Material: Nylon



795269 Hose Tail Adaptor

RS PRO HOSE CONNECTOR, ELBOW HOSE TAIL ADAPTOR, BSP 1/2IN 8MM

- ขนาดบรรจุภัณฑ์: 5 x EA
- Hose Connector Type: Hose Tail Adaptor
 - Connector Gender: Male
 - Coupling Connector Direction: Elbow
 - Thread Standard: BSP
 - Thread Size: 1/2 in
 - Hose Inner Diameter: 8 mm
 - Body Material: Nylon



795275 Hose Tail Adaptor

RS PRO HOSE CONNECTOR, ELBOW HOSE TAIL ADAPTOR, BSP 1/4IN 10MM

- ขนาดบรรจุภัณฑ์: 5 x EA
- Hose Connector Type: Hose Tail Adaptor
 - Connector Gender: Male
 - Coupling Connector Direction: Elbow
 - Thread Standard: BSP
 - Thread Size: 1/4 in
 - Hose Inner Diameter: 10 mm
 - Body Material: Nylon



795281 Hose Tail Adaptor

RS PRO HOSE CONNECTOR, ELBOW HOSE TAIL ADAPTOR, BSP 3/8IN

- ขนาดบรรจุภัณฑ์: 5 x EA
- Hose Connector Type: Hose Tail Adaptor
 - Connector Gender: Male
 - Coupling Connector Direction: Elbow
 - Thread Standard: BSP
 - Thread Size: 3/8 in
 - Hose Inner Diameter: 10 mm
 - Body Material: Nylon



795297 Hose Tail Adaptor

RS PRO HOSE CONNECTOR, ELBOW HOSE TAIL ADAPTOR, BSP 3/8IN

- ขนาดบรรจุภัณฑ์: 5 x EA
- Hose Connector Type: Hose Tail Adaptor
 - Connector Gender: Male
 - Coupling Connector Direction: Elbow
 - Thread Standard: BSP
 - Thread Size: 3/8 in
 - Hose Inner Diameter: 12 mm
 - Body Material: Nylon



795304 Hose Tail Adaptor

RS PRO HOSE CONNECTOR, ELBOW HOSE TAIL ADAPTOR, BSP 1/2IN 12MM

- ขนาดบรรจุภัณฑ์: 5 x EA
- Hose Connector Type: Hose Tail Adaptor
 - Connector Gender: Male
 - Coupling Connector Direction: Elbow
 - Thread Standard: BSP
 - Thread Size: 1/2 in
 - Hose Inner Diameter: 12 mm
 - Body Material: Nylon



795310 Hose Tail Adaptor

RS PRO HOSE CONNECTOR, ELBOW HOSE TAIL ADAPTOR, BSP 3/4IN

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Hose Connector Type: Hose Tail Adaptor
 - Connector Gender: Male
 - Coupling Connector Direction: Elbow
 - Thread Standard: BSP
 - Thread Size: 3/4 in
 - Hose Inner Diameter: 19 mm
 - Body Material: Nylon



795326 Hose Tail Adaptor

CONNECTOR,HOSE,ACETAL RESIN,PUSH ON,STRAIGHT,5MM I/D

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Hose Connector Type: Hose Joiner
 - Connector Gender: Male
 - Coupling Connector Direction: Straight
 - Hose Inner Diameter: 3 mm
 - Body Material: Acetal



795332 Hose Joiner

CONNECTOR,HOSE,ACETAL RESIN,STRAIGHT,6MM I/D

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Hose Connector Type: Hose Joiner
 - Connector Gender: Male
 - Coupling Connector Direction: Straight
 - Hose Inner Diameter: 6 mm
 - Body Material: Acetal



795348 Hose Joiner

CONNECTOR,HOSE,ACETAL RESIN,STRAIGHT,8MM I/D

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Hose Connector Type: Hose Joiner
 - Connector Gender: Male
 - Coupling Connector Direction: Straight
 - Hose Inner Diameter: 8 mm
 - Body Material: Acetal



795354 Hose Joiner

CONNECTOR,HOSE,ACETAL RESIN,STRAIGHT,10MM I/D

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Hose Connector Type: Hose Joiner
 - Connector Gender: Male
 - Coupling Connector Direction: Straight
 - Hose Inner Diameter: 10 mm
 - Body Material: Acetal



795360 Hose Joiner

CONNECTOR,HOSE,ACETAL RESIN,STRAIGHT,12MM I/D

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Hose Connector Type: Hose Joiner
 - Connector Gender: Male
 - Coupling Connector Direction: Straight
 - Hose Inner Diameter: 12 mm
 - Body Material: Acetal



795376 Hose Joiner

RS PRO HOSE CONNECTOR, STRAIGHT HOSE JOINER 19MM ID

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Hose Connector Type: Hose Joiner
 - Connector Gender: Male
 - Coupling Connector Direction: Straight
 - Hose Inner Diameter: 19 mm
 - Body Material: Acetal



795382 Hose Joiner

CONNECTOR,HOSE,ACETAL RESIN,TEE,5MM I/D

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Hose Connector Type: Hose Joiner
 - Connector Gender: Male
 - Coupling Connector Direction: Tee
 - Hose Inner Diameter: 5 mm
 - Body Material: Acetal



795398 Hose Joiner

CONNECTOR,HOSE,ACETAL RESIN,TEE,6MM I/D

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Hose Connector Type: Hose Joiner
 - Connector Gender: Male
 - Coupling Connector Direction: Tee
 - Hose Inner Diameter: 6 mm
 - Body Material: Acetal



795405 Hose Joiner

CONNECTOR,HOSE,ACETAL RESIN,TEE,8MM I/D

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Hose Connector Type: Hose Joiner
 - Connector Gender: Male
 - Coupling Connector Direction: Tee
 - Hose Inner Diameter: 8 mm
 - Body Material: Acetal



795411 Hose Joiner

CONNECTOR,HOSE,ACETAL RESIN,TEE,10MM I/D

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Hose Connector Type: Hose Joiner
 - Connector Gender: Male
 - Coupling Connector Direction: Tee
 - Hose Inner Diameter: 10 mm
 - Body Material: Acetal



795427 Hose Joiner

CONNECTOR,HOSE,ACETAL RESIN,TEE,12MM I/D

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Hose Connector Type: Hose Joiner
 - Connector Gender: Male
 - Coupling Connector Direction: Tee
 - Hose Inner Diameter: 12 mm
 - Body Material: Acetal



795433 Hose Joiner

RS PRO HOSE CONNECTOR, TEE HOSE JOINER 19MM ID

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Hose Connector Type: Hose Joiner
 - Connector Gender: Male
 - Coupling Connector Direction: Tee
 - Hose Inner Diameter: 19 mm
 - Body Material: Acetal



795449 Hose Joiner

RS PRO HOSE CONNECTOR, ELBOW HOSE JOINER 5MM ID

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Hose Connector Type: Hose Joiner
 - Connector Gender: Male
 - Coupling Connector Direction: Elbow
 - Hose Inner Diameter: 5 mm
 - Body Material: Acetal



795455 Hose Joiner

CONNECTOR,HOSE,ACETAL RESIN,ELBOW,6MM I/D

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Hose Connector Type: Hose Joiner
 - Connector Gender: Male
 - Coupling Connector Direction: Elbow
 - Hose Inner Diameter: 6 mm
 - Body Material: Acetal



795461 Hose Joiner

CONNECTOR,HOSE,ACETAL RESIN,ELBOW,8MM I/D

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Hose Connector Type: Hose Joiner
 - Connector Gender: Male
 - Coupling Connector Direction: Elbow
 - Hose Inner Diameter: 8 mm
 - Body Material: Acetal



795477 Hose Joiner

RS PRO HOSE CONNECTOR, ELBOW HOSE JOINER 12MM ID

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Hose Connector Type: Hose Joiner
 - Connector Gender: Male
 - Coupling Connector Direction: Elbow
 - Hose Inner Diameter: 12 mm
 - Body Material: Acetal



795499 Hose Joiner

CONNECTOR,HOSE,ACETAL RESIN,Y,5MM I/D

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Hose Connector Type: Hose Joiner
 - Connector Gender: Male
 - Coupling Connector Direction: Y
 - Hose Inner Diameter: 5 mm
 - Body Material: Acetal



795512 Hose Joiner

CONNECTOR,HOSE,ACETAL RESIN,Y,6MM I/D

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Hose Connector Type: Hose Joiner
 - Connector Gender: Male
 - Coupling Connector Direction: Y
 - Hose Inner Diameter: 6 mm
 - Body Material: Acetal



795528 Hose Joiner

CONNECTOR,HOSE,ACETAL RESIN,Y,8MM I/D

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Hose Connector Type: Hose Joiner
 - Connector Gender: Male
 - Coupling Connector Direction: Y
 - Hose Inner Diameter: 8 mm
 - Body Material: Acetal



795534 Hose Joiner

CONNECTOR,HOSE,ACETAL RESIN,Y,10MM I/D

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Hose Connector Type: Hose Joiner
 - Connector Gender: Male
 - Coupling Connector Direction: Y
 - Hose Inner Diameter: 10 mm
 - Maximum Working Pressure: 10 bar
 - Body Material: Acetal



795540 Hose Joiner

CONNECTOR,HOSE,ACETAL RESIN,Y,12MM I/D

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Hose Connector Type: Hose Joiner
 - Connector Gender: Male
 - Coupling Connector Direction: Y
 - Hose Inner Diameter: 12 mm
 - Body Material: Acetal



795556 Hose Joiner

RS PRO HOSE CONNECTOR, Y HOSE JOINER 19MM ID

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Hose Connector Type: Hose Joiner
 - Connector Gender: Male
 - Coupling Connector Direction: Y
 - Hose Inner Diameter: 19 mm
 - Body Material: Acetal



795562 Hose Joiner

RS PRO HOSE CONNECTOR HOSE TAIL ADAPTOR, BSP 3/4IN 1/2IN ID

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Hose Connector Type: Hose Tail Adaptor
 - Connector Gender: Male
 - Thread Standard: BSP
 - Thread Size: 3/4 in
 - Hose Inner Diameter: 1/2 in
 - Body Material: Brass



1463028 Hose Tail Adaptor

RS PRO HOSE CONNECTOR HOSE TAIL ADAPTOR, BSP 1/2IN 1/2IN ID

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Hose Connector Type: Hose Tail Adaptor
 - Connector Gender: Male
 - Thread Standard: BSP
 - Thread Size: 1/2 in
 - Hose Inner Diameter: 1/2 in
 - Body Material: Brass



1463051 Hose Tail Adaptor

RS PRO HOSE CONNECTOR HOSE TAIL ADAPTOR, BSP 1IN 1IN ID

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Hose Connector Type: Hose Tail Adaptor
 - Connector Gender: Male
 - Thread Standard: BSP
 - Thread Size: 1 in
 - Hose Inner Diameter: 1 in
 - Body Material: Brass



1463053 Hose Tail Adaptor

RS PRO HOSE CONNECTOR HOSE TAIL ADAPTOR, BSP 1/4IN 1.26IN ID

- ขนาดบรรจุภัณฑ์: **2 x EA**
- Hose Connector Type: Hose Tail Adaptor
 - Connector Gender: Male
 - Thread Standard: BSP
 - Thread Size: 1/4 in
 - Hose Inner Diameter: 1.26 in
 - Body Material: Brass



1463054 Hose Tail Adaptor

RS PRO HOSE CONNECTOR HOSE TAIL ADAPTOR, BSP 1/2IN

- ขนาดบรรจุภัณฑ์: **2 x EA**
- Hose Connector Type: Hose Tail Adaptor
 - Connector Gender: Male
 - Thread Standard: BSP
 - Thread Size: 1/2 in
 - Body Material: Brass



1463056 Hose Tail Adaptor

RS PRO HOSE CONNECTOR HOSE TO TAP CONNECTOR, BSP 3/4IN 1/2IN ID

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Hose Connector Type: Hose to Tap Connector
 - Connector Gender: Female
 - Thread Standard: BSP
 - Thread Size: 3/4 in
 - Hose Inner Diameter: 1/2 in
 - Body Material: Brass



1463061 Hose to Tap

RS PRO HOSE CONNECTOR HOSE TAIL ADAPTOR, BSP 1IN 3/4IN ID

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Hose Connector Type: Hose Tail Adaptor
 - Connector Gender: Male
 - Thread Standard: BSP
 - Thread Size: 1 in
 - Hose Inner Diameter: 3/4 in
 - Body Material: Brass



1463062 Hose Tail Adaptor

RS PRO HOSE CONNECTOR HOSE TO TAP CONNECTOR, BSP 1/2IN 0.59IN

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Hose Connector Type: Hose to Tap Connector
 - Connector Gender: Male
 - Thread Standard: BSP
 - Thread Size: 1/2 in
 - Hose Inner Diameter: 0.59 in
 - Maximum Working Pressure: 25 bar
 - Body Material: Brass



1463068 Hose to Tap

1/2IN BSPT FEMALE X 1/2IN HOSETAIL

- ขนาดบรรจุภัณฑ์: **2 x EA**
- Hose Connector Type: Hose to Tap Connector
 - Connector Gender: Male
 - Thread Standard: BSP
 - Thread Size: 1/2 in
 - Hose Inner Diameter: 1/2 in
 - Maximum Working Pressure: 25 bar
 - Body Material: Brass



1463182 Hose to Tap

RS PRO HOSE CONNECTOR HOSE TO TAP CONNECTOR, BSP 3/4IN 3/4IN ID

- ขนาดบรรจุภัณฑ์: **2 x EA**
- Hose Connector Type: Hose to Tap Connector
 - Connector Gender: Male
 - Thread Standard: BSP
 - Thread Size: 3/4 in
 - Hose Inner Diameter: 3/4 in
 - Body Material: Brass



1463183 Hose to Tap

MALE HOSE ADAPTOR - BSPT 1/8

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Hose Connector Type: Hose Tail Adaptor
 - Connector Gender: Male
 - Thread Standard: BSPT
 - Thread Size: 1/8 in
 - Hose Inner Diameter: 4 mm
 - Maximum Working Pressure: 5 MPa, 50 bar
 - Body Material: Brass



1762014 Hose Tail Adaptor

RS PRO HOSE CONNECTOR HOSE TAIL ADAPTOR, BSPT 1/8IN 6MM ID, 5

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Hose Connector Type: Hose Tail Adaptor
 - Connector Gender: Male
 - Thread Standard: BSPT
 - Thread Size: 1/8 in
 - Hose Inner Diameter: 6 mm
 - Maximum Working Pressure: 5 MPa, 50 bar
 - Body Material: Brass



1762015 Hose Tail Adaptor

RS PRO HOSE CONNECTOR HOSE TAIL ADAPTOR, BSPT 1/4IN 7MM ID, 5

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Hose Connector Type: Hose Tail Adaptor
 - Connector Gender: Male
 - Thread Standard: BSPT
 - Thread Size: 1/4 in
 - Hose Inner Diameter: 7 mm
 - Maximum Working Pressure: 5 MPa, 50 bar
 - Body Material: Brass



1762016 Hose Tail Adaptor

RS PRO HOSE CONNECTOR HOSE TAIL ADAPTOR, BSPT 3/4IN 25MM ID,

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Hose Connector Type: Hose Tail Adaptor
 - Connector Gender: Male
 - Thread Standard: BSPT
 - Thread Size: 3/4 in
 - Hose Inner Diameter: 25 mm
 - Maximum Working Pressure: 5 MPa, 50 bar
 - Body Material: Brass



1762019 Hose Tail Adaptor

RS PRO HOSE CONNECTOR HOSE TAIL ADAPTOR, BSPT 1/8IN 10MM ID, 5

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Hose Connector Type: Hose Tail Adaptor
 - Connector Gender: Male
 - Thread Standard: BSPT
 - Thread Size: 1/8 in
 - Hose Inner Diameter: 10 mm
 - Maximum Working Pressure: 5 MPa, 50 bar
 - Body Material: Brass



1762020 Hose Tail Adaptor

RS PRO HOSE CONNECTOR HOSE TAIL ADAPTOR, BSPT 1/4IN 10MM ID, 5

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Hose Connector Type: Hose Tail Adaptor
 - Connector Gender: Male
 - Thread Standard: BSPT
 - Thread Size: 1/4 in
 - Hose Inner Diameter: 10 mm
 - Maximum Working Pressure: 5 MPa, 50 bar
 - Body Material: Brass



1762021 Hose Tail Adaptor

RS PRO HOSE CONNECTOR HOSE TAIL ADAPTOR, BSPT 3/8IN 10MM ID,

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Hose Connector Type: Hose Tail Adaptor
 - Connector Gender: Male
 - Thread Standard: BSPT
 - Thread Size: 3/8 in
 - Hose Inner Diameter: 10 mm
 - Maximum Working Pressure: 5 MPa, 50 bar
 - Body Material: Brass



1762022 Hose Tail Adaptor

RS PRO HOSE CONNECTOR HOSE TAIL ADAPTOR, BSPT 1/2IN 16MM ID, 5

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Hose Connector Type: Hose Tail Adaptor
 - Connector Gender: Male
 - Thread Standard: BSPT
 - Thread Size: 1/2 in
 - Hose Inner Diameter: 16 mm
 - Maximum Working Pressure: 5 MPa, 50 bar
 - Body Material: Brass



1762026 Hose Tail Adaptor

RS PRO HOSE CONNECTOR HOSE TAIL ADAPTOR, BSPT 3/4IN 16MM ID,

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Hose Connector Type: Hose Tail Adaptor
 - Connector Gender: Male
 - Thread Standard: BSPT
 - Thread Size: 3/4 in
 - Hose Inner Diameter: 16 mm
 - Maximum Working Pressure: 5 MPa, 50 bar
 - Body Material: Brass



1762027 Hose Tail Adaptor

RS PRO HOSE CONNECTOR HOSE TAIL ADAPTOR, BSPT 3/4IN 18MM ID,

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Hose Connector Type: Hose Tail Adaptor
 - Connector Gender: Male
 - Thread Standard: BSPT
 - Thread Size: 3/4 in
 - Hose Inner Diameter: 18 mm
 - Maximum Working Pressure: 5 MPa, 50 bar
 - Body Material: Brass



1762029 Hose Tail Adaptor

RS PRO HOSE CONNECTOR HOSE TAIL ADAPTOR, BSPT 1IN 25MM ID, 5

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Hose Connector Type: Hose Tail Adaptor
 - Connector Gender: Male
 - Thread Standard: BSPT
 - Thread Size: 1 in
 - Hose Inner Diameter: 25 mm
 - Maximum Working Pressure: 5 MPa, 50 bar
 - Body Material: Brass



1762031 Hose Tail Adaptor

MALE HOSE ADAPTOR - BSPP 8-1/4

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Hose Connector Type: Hose Tail Adaptor
 - Connector Gender: Male
 - Thread Standard: BSPP
 - Thread Size: 1/4 in
 - Hose Inner Diameter: 8 mm
 - Maximum Working Pressure: 5 MPa, 50 bar
 - Body Material: Brass



1762034 Hose Tail Adaptor

MALE HOSE ADAPTOR - BSPP 6-1/4

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Hose Connector Type: Hose Tail Adaptor
 - Connector Gender: Male
 - Thread Standard: BSPP
 - Thread Size: 1/4 in
 - Hose Inner Diameter: 6 mm
 - Maximum Working Pressure: 5 MPa, 50 bar
 - Body Material: Brass



1762038 Hose Tail Adaptor

RS PRO HOSE CONNECTOR HOSE TAIL ADAPTOR, BSPP 1/4IN 10MM ID,

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Hose Connector Type: Hose Tail Adaptor
 - Connector Gender: Male
 - Thread Standard: BSPP
 - Thread Size: 1/4 in
 - Hose Inner Diameter: 10 mm
 - Maximum Working Pressure: 5 MPa, 50 bar
 - Body Material: Brass



1762040 Hose Tail Adaptor

RS PRO HOSE CONNECTOR HOSE TAIL ADAPTOR, BSPP 3/8IN 10MM ID,

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Hose Connector Type: Hose Tail Adaptor
 - Connector Gender: Male
 - Thread Standard: BSPP
 - Thread Size: 3/8 in
 - Hose Inner Diameter: 10 mm
 - Maximum Working Pressure: 5 MPa, 50 bar
 - Body Material: Brass



1762041 Hose Tail Adaptor

RS PRO HOSE CONNECTOR HOSE TAIL ADAPTOR, BSPP 1/2IN 10MM ID,

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Hose Connector Type: Hose Tail Adaptor
 - Connector Gender: Male
 - Thread Standard: BSPP
 - Thread Size: 1/2 in
 - Hose Inner Diameter: 10 mm
 - Maximum Working Pressure: 5 MPa, 50 bar
 - Body Material: Brass



1762042 Hose Tail Adaptor

RS PRO HOSE CONNECTOR, BSPT 1/4IN 8MM ID, 100 BAR

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Connector Gender: Male
 - Thread Standard: BSPT
 - Thread Size: 1/4 in
 - Hose Inner Diameter: 8 mm
 - Maximum Working Pressure: 100 bar
 - Body Material: Brass



2312537 Male

RS PRO HOSE CONNECTOR, STRAIGHT CAMLOCK ADAPTOR, BSP

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Connector Type: Camlock Adaptor
 - Coupling Connector Direction: Straight
 - Thread Standard: BSP
 - Thread Size: 1 in
 - Hose Inner Diameter: 1 in
 - Maximum Working Pressure: 7 bar
 - Body Material: PP



2333273 Camlock Adaptor

RS PRO HOSE CONNECTOR, STRAIGHT CAMLOCK ADAPTOR, BSP

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Connector Type: Camlock Adaptor
 - Coupling Connector Direction: Straight
 - Thread Standard: BSP
 - Thread Size: 1-1/2 in
 - Hose Inner Diameter: 1-1/2 in
 - Maximum Working Pressure: 7 bar
 - Body Material: PP



2333289 Camlock Adaptor

RS PRO HOSE CONNECTOR, STRAIGHT CAMLOCK ADAPTOR, BSP

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Connector Type: Camlock Adaptor
 - Coupling Connector Direction: Straight
 - Thread Standard: BSP
 - Thread Size: 2 in
 - Hose Inner Diameter: 2 in
 - Maximum Working Pressure: 7 bar
 - Body Material: PP



2333295 Camlock Adaptor

RS PRO HOSE CONNECTOR, STRAIGHT CAMLOCK ADAPTOR 1IN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Connector Type: Camlock Adaptor
 - Connector Gender: Male
 - Coupling Connector Direction: Straight
 - Thread Size: 1 in
 - Hose Inner Diameter: 1 in
 - Maximum Working Pressure: 7 bar
 - Body Material: PP



2333302 Camlock Adaptor

RS PRO HOSE CONNECTOR, STRAIGHT CAMLOCK ADAPTOR 1-

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Connector Type: Camlock Adaptor
 - Connector Gender: Male
 - Coupling Connector Direction: Straight
 - Thread Size: 1-1/2 in
 - Hose Inner Diameter: 1-1/2 in
 - Maximum Working Pressure: 7 bar
 - Body Material: PP



2333318 Camlock Adaptor

RS PRO HOSE CONNECTOR, STRAIGHT CAMLOCK COUPLING 1IN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Connector Type: Camlock Coupling
 - Connector Gender: Male
 - Coupling Connector Direction: Straight
 - Thread Size: 1 in
 - Hose Inner Diameter: 1 in
 - Maximum Working Pressure: 7 bar
 - Body Material: PP



2333330 Camlock

RS PRO HOSE CONNECTOR, STRAIGHT CAMLOCK COUPLING 1-

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Connector Type: Camlock Coupling
 - Connector Gender: Female
 - Coupling Connector Direction: Straight
 - Thread Size: 1-1/2 in
 - Hose Inner Diameter: 1-1/2 in
 - Maximum Working Pressure: 7 bar
 - Body Material: PP



2333346 Camlock

RS PRO HOSE CONNECTOR, STRAIGHT CAMLOCK COUPLING 2IN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Connector Type: Camlock Coupling
 - Connector Gender: Female
 - Coupling Connector Direction: Straight
 - Thread Size: 2 in
 - Hose Inner Diameter: 2 in
 - Maximum Working Pressure: 7 bar
 - Body Material: PP



2333352 Camlock

RS PRO HOSE CONNECTOR DUST CAP 2IN ID, 7 BAR

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Connector Type: Dust Cap
 - Connector Gender: Female
 - Hose Inner Diameter: 2 in
 - Maximum Working Pressure: 7 bar
 - Body Material: PP



3250595 Dust Cap

RS PRO HOSE CONNECTOR DUST CAP 2IN ID, 7 BAR

- ขนาดบรรจุภัณฑ์: **2 x EA**
- Hose Connector Type: Dust Cap
 - Connector Gender: Male
 - Hose Inner Diameter: 2 in
 - Maximum Working Pressure: 7 bar
 - Body Material: PP



3250630 Dust Cap

RS PRO HOSE CONNECTOR, STRAIGHT CAM & GROOVE ADAPTOR,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Connector Type: Cam & Groove Adaptor
 - Connector Gender: Male
 - Coupling Connector Direction: Straight
 - Thread Standard: BSP
 - Thread Size: 1 in
 - Hose Inner Diameter: 1 in
 - Maximum Working Pressure: 17 bar
 - Body Material: Aluminium



3626649 Cam & Groove

RS PRO HOSE CONNECTOR, STRAIGHT CAM & GROOVE ADAPTOR,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Connector Type: Cam & Groove Adaptor
 - Connector Gender: Male
 - Coupling Connector Direction: Straight
 - Thread Standard: BSP
 - Thread Size: 2 in
 - Hose Inner Diameter: 2 in
 - Maximum Working Pressure: 17 bar
 - Body Material: Aluminium



3626661 Cam & Groove

RS PRO HOSE CONNECTOR, STRAIGHT CAM & GROOVE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Connector Type: Cam & Groove Coupling
 - Connector Gender: Male
 - Coupling Connector Direction: Straight
 - Thread Standard: BSP
 - Thread Size: 1-1/2 in
 - Hose Inner Diameter: 1-1/2 in
 - Maximum Working Pressure: 17 bar
 - Body Material: Aluminium



3626699 Cam & Groove

RS PRO HOSE CONNECTOR, STRAIGHT CAM & GROOVE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Connector Type: Cam & Groove Coupling
 - Connector Gender: Male
 - Coupling Connector Direction: Straight
 - Thread Standard: BSP
 - Thread Size: 2 in
 - Hose Inner Diameter: 2 in
 - Maximum Working Pressure: 17 bar
 - Body Material: Aluminium



3626706 Cam & Groove

RS PRO HOSE CONNECTOR, STRAIGHT CAM & GROOVE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Connector Type: Cam & Groove Coupling
 - Connector Gender: Male
 - Coupling Connector Direction: Straight
 - Thread Size: 1 in
 - Hose Inner Diameter: 1 in
 - Maximum Working Pressure: 17 bar
 - Body Material: Aluminium



3626712 Cam & Groove

RS PRO HOSE CONNECTOR, STRAIGHT CAM & GROOVE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Connector Type: Cam & Groove Coupling
 - Connector Gender: Male
 - Coupling Connector Direction: Straight
 - Thread Size: 1.5 in
 - Hose Inner Diameter: 1.5 in
 - Maximum Working Pressure: 17 bar
 - Body Material: Aluminium



3626728 Cam & Groove

RS PRO HOSE CONNECTOR, STRAIGHT CAM & GROOVE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Connector Type: Cam & Groove Coupling
 - Connector Gender: Female
 - Coupling Connector Direction: Straight
 - Thread Size: 1 in
 - Hose Inner Diameter: 1 in
 - Maximum Working Pressure: 17 bar
 - Body Material: Aluminium



3626756 Cam & Groove

RS PRO HOSE CONNECTOR, STRAIGHT CAM & GROOVE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Connector Type: Cam & Groove Coupling
 - Connector Gender: Female
 - Coupling Connector Direction: Straight
 - Thread Standard: BSP
 - Thread Size: 2 in
 - Hose Inner Diameter: 2 in
 - Maximum Working Pressure: 17 bar
 - Body Material: Aluminium



3626778 Cam & Groove

RS PRO HOSE CONNECTOR, STRAIGHT CAM & GROOVE ADAPTOR,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Connector Type: Cam & Groove Adaptor
 - Connector Gender: Male
 - Coupling Connector Direction: Straight
 - Thread Standard: BSP
 - Thread Size: 1 in
 - Hose Inner Diameter: 1 in
 - Maximum Working Pressure: 17 bar
 - Body Material: Aluminium



3626813 Cam & Groove

RS PRO HOSE CONNECTOR, STRAIGHT CAM & GROOVE ADAPTOR,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Connector Type: Cam & Groove Adaptor
 - Connector Gender: Male
 - Coupling Connector Direction: Straight
 - Thread Standard: BSP
 - Thread Size: 1-1/2 in
 - Hose Inner Diameter: 1-1/2 in
 - Maximum Working Pressure: 17 bar
 - Body Material: Aluminium



3626829 Cam & Groove

RS PRO HOSE CONNECTOR, STRAIGHT CAM & GROOVE ADAPTOR,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Connector Type: Cam & Groove Adaptor
 - Connector Gender: Male
 - Coupling Connector Direction: Straight
 - Thread Standard: BSP
 - Thread Size: 2 in
 - Hose Inner Diameter: 2 in
 - Maximum Working Pressure: 17 bar
 - Body Material: Aluminium



3626835 Cam & Groove

RS PRO HOSE CONNECTOR DUST CAP 2 IN ID, 17 BAR

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Connector Type: Dust Cap
 - Hose Inner Diameter: 2 in
 - Maximum Working Pressure: 17 bar
 - Body Material: Aluminium



3626908 Dust Cap

RS PRO HOSE CONNECTOR HOSE TAIL ADAPTOR, BSP 1/4 IN 1/4 IN ID

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Connector Type: Hose Tail Adaptor
 - Thread Standard: BSP
 - Thread Size: 1/4 in
 - Hose Inner Diameter: 1/4 in
 - Body Material: Brass



3626914 Hose Tail Adaptor

RS PRO HOSE CONNECTOR HOSE TAIL ADAPTOR, BSP 3/8 IN 1/4 IN ID

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Connector Type: Hose Tail Adaptor
 - Thread Standard: BSP
 - Thread Size: 3/8 in
 - Hose Inner Diameter: 1/4 in
 - Body Material: Brass



3626920 Hose Tail Adaptor

RS PRO HOSE CONNECTOR HOSE TAIL ADAPTOR, BSP 3/8 IN 5/16 IN ID

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Connector Type: Hose Tail Adaptor
 - Thread Standard: BSP
 - Thread Size: 3/8 in
 - Hose Inner Diameter: 5/16 in
 - Body Material: Brass



3626936 Hose Tail Adaptor

RS PRO HOSE CONNECTOR HOSE TAIL ADAPTOR, BSP 3/8 IN 3/8 IN ID

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Connector Type: Hose Tail Adaptor
 - Thread Standard: BSP
 - Thread Size: 3/8 in
 - Hose Inner Diameter: 3/8 in
 - Body Material: Brass



3626942 Hose Tail Adaptor

RS PRO HOSE CONNECTOR HOSE TAIL ADAPTOR, BSP 1/4 IN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Connector Type: Hose Tail Adaptor
 - Thread Standard: BSP
 - Thread Size: 1/4 in
 - Body Material: Brass



3626970 Hose Tail Adaptor

RS PRO HOSE CONNECTOR HOSE TAIL ADAPTOR, BSP 3/8 IN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Connector Type: Hose Tail Adaptor
 - Connector Gender: Female
 - Thread Standard: BSP
 - Thread Size: 3/8 in
 - Body Material: Brass



3626986 Hose Tail Adaptor

RS PRO STAINLESS STEEL HOSE CONNECTOR, 1/2 IN BSP MALE, 20

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Inner Diameter: 1/2 in
 - Threaded Connection: 1/2 in BSP Male
 - Body Material: Stainless Steel
 - Maximum Working Pressure: 20 bar
 - Thread Gender: Male
 - Thread Size: 1/2 in
 - Thread Standard: BSP



3627103 1/2 in

RS PRO HOSE CONNECTOR HOSE TAIL ADAPTOR, BSP 1/2 IN 3/4 IN ID, 20

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Connector Type: Hose Tail Adaptor
 - Connector Gender: Male
 - Thread Standard: BSP
 - Thread Size: 1/2 in
 - Hose Inner Diameter: 3/4 in
 - Maximum Working Pressure: 20 bar
 - Body Material: Stainless Steel



3627119 Hose Tail Adaptor

RS PRO HOSE CONNECTOR, STRAIGHT CAMLOCK COUPLING, BSP

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Connector Type: Camlock Coupling
 - Coupling Connector Direction: Straight
 - Thread Standard: BSP
 - Thread Size: 2 in
 - Hose Inner Diameter: 2 in
 - Maximum Working Pressure: 7 bar
 - Body Material: PP



3825688 Camlock

RS PRO HOSE CONNECTOR, STRAIGHT CAMLOCK ADAPTOR, BSPT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Connector Type: Camlock Adaptor
 - Connector Gender: Male
 - Coupling Connector Direction: Straight
 - Thread Standard: BSPT
 - Thread Size: 1 in
 - Hose Inner Diameter: 1 in
 - Maximum Working Pressure: 7 bar
 - Body Material: PP



3825694 Camlock Adaptor

RS PRO HOSE CONNECTOR, STRAIGHT CAMLOCK ADAPTOR, R 1-

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Connector Type: Camlock Adaptor
 - Connector Gender: Male
 - Coupling Connector Direction: Straight
 - Thread Standard: R
 - Thread Size: 1-1/2 in
 - Hose Inner Diameter: 1-1/2 in
 - Maximum Working Pressure: 7 bar
 - Body Material: PP



3825701 Camlock Adaptor

RS PRO HOSE CONNECTOR, STRAIGHT CAMLOCK ADAPTOR, R 2IN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Connector Type: Camlock Adaptor
 - Connector Gender: Male
 - Coupling Connector Direction: Straight
 - Thread Standard: R
 - Thread Size: 2 in
 - Hose Inner Diameter: 2 in
 - Maximum Working Pressure: 7 bar
 - Body Material: PP



3825717 Camlock Adaptor

CONNECTOR,HOSE,ELBOW,PUSH ON,3MM I/D

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Hose Connector Type: Hose Joiner
 - Connector Gender: Male
 - Coupling Connector Direction: Elbow
 - Hose Inner Diameter: 3 mm
 - Body Material: Acetal



4197221 Hose Joiner

RS PRO HOSE CONNECTOR, ELBOW HOSE JOINER 4MM ID

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Hose Connector Type: Hose Joiner
 - Connector Gender: Male
 - Coupling Connector Direction: Elbow
 - Hose Inner Diameter: 4 mm
 - Body Material: Acetal



4197237 Hose Joiner

CONNECTOR,HOSE,EQUAL,Y,PUSH ON,3MM I/D

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Hose Connector Type: Hose Joiner
 - Connector Gender: Male
 - Coupling Connector Direction: Y
 - Hose Inner Diameter: 3 mm
 - Body Material: Acetal



4197259 Hose Joiner

CONNECTOR,HOSE,EQUAL,Y,PUSH ON,4MM I/D

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Hose Connector Type: Hose Joiner
 - Connector Gender: Male
 - Coupling Connector Direction: Y
 - Hose Inner Diameter: 4 mm
 - Body Material: Acetal



4197265 Hose Joiner

RS PRO HOSE CONNECTOR, Y HOSE JOINER 16MM ID

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Hose Connector Type: Hose Joiner
 - Connector Gender: Male
 - Coupling Connector Direction: Y
 - Hose Inner Diameter: 16 mm
 - Body Material: Acetal



4197271 Hose Joiner

CONNECTOR,HOSE,STRAIGHT,PUSH ON,3MM I/D

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Hose Connector Type: Hose Joiner
 - Connector Gender: Male
 - Coupling Connector Direction: Straight
 - Hose Inner Diameter: 2.5 mm
 - Body Material: Acetal



4197287 Hose Joiner

CONNECTOR,HOSE,STRAIGHT,PUSH ON,4MM I/D

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Hose Connector Type: Hose Joiner
 - Connector Gender: Male
 - Coupling Connector Direction: Straight
 - Hose Inner Diameter: 4 mm
 - Body Material: Acetal



4197300 Hose Joiner

RS PRO HOSE CONNECTOR, STRAIGHT HOSE JOINER 16MM ID

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Hose Connector Type: Hose Joiner
 - Connector Gender: Male
 - Coupling Connector Direction: Straight
 - Hose Inner Diameter: 16 mm
 - Body Material: Acetal



4197316 Hose Joiner

RS PRO HOSE CONNECTOR, TEE HOSE TAIL ADAPTOR, R 1/8IN 4MM ID

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Hose Connector Type: Hose Tail Adaptor
 - Connector Gender: Male
 - Coupling Connector Direction: Tee
 - Thread Standard: R
 - Thread Size: 1/8 in
 - Hose Inner Diameter: 4 mm
 - Body Material: Polyamide



4197322 Hose Tail Adaptor

RS PRO HOSE CONNECTOR, TEE HOSE TAIL ADAPTOR, R 1/4IN 6MM ID

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Hose Connector Type: Hose Tail Adaptor
 - Connector Gender: Male
 - Coupling Connector Direction: Tee
 - Thread Standard: R
 - Thread Size: 1/4 in
 - Hose Inner Diameter: 6 mm
 - Body Material: Polyamide



4197366 Hose Tail Adaptor

RS PRO HOSE CONNECTOR, ELBOW HOSE TAIL ADAPTOR, R 1/8IN 4MM ID

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Hose Connector Type: Hose Tail Adaptor
 - Connector Gender: Male
 - Coupling Connector Direction: Elbow
 - Thread Standard: R
 - Thread Size: 1/8 in
 - Hose Inner Diameter: 4 mm
 - Body Material: Polyamide



4197388 Hose Tail Adaptor

CONNECTOR,HOSE,ELBOW TAPER THREAD,6MM I/D,THREAD R1/8

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Hose Connector Type: Hose Tail Adaptor
 - Connector Gender: Male
 - Coupling Connector Direction: Elbow
 - Thread Standard: R
 - Thread Size: 1/8 in
 - Hose Inner Diameter: 6 mm
 - Body Material: Polyamide



4197394 Hose Tail Adaptor

**CONNECTOR,HOSE,STRAIGHT TAPER
THREAD,4MM I/D,THREAD R1/8**

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Hose Connector Type: Hose Tail Adaptor
 - Connector Gender: Male
 - Coupling Connector Direction: Straight
 - Thread Standard: R
 - Thread Size: 1/8 in
 - Hose Inner Diameter: 4 mm
 - Body Material: Polyamide



4197401 Hose Tail Adaptor

**CONNECTOR,HOSE,EQUAL,TEE,PUSH
ON,32MM I/D**

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Hose Connector Type: Hose Joiner
 - Connector Gender: Male
 - Coupling Connector Direction: Tee
 - Hose Inner Diameter: 3 mm
 - Body Material: Acetal



4198117 Hose Joiner

**CONNECTOR,HOSE,EQUAL,TEE,PUSH
ON,4MM I/D**

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Hose Connector Type: Hose Joiner
 - Connector Gender: Male
 - Coupling Connector Direction: Tee
 - Hose Inner Diameter: 3 mm
 - Body Material: Acetal



4198123 Hose Joiner

**WATER,BRASS,HOSE TAIL
ADAPTOR,MALE 1/8BSP-PX3/8IN ID**

- ขนาดบรรจุภัณฑ์: **2 x EA**
- Hose Connector Type: Hose Tail Adaptor
 - Connector Gender: Male
 - Thread Standard: G
 - Thread Size: 1/8 in
 - Hose Inner Diameter: 3/8 in
 - Body Material: Brass



5067171 Hose Tail Adaptor

**WATER,BRASS,HOSE TAIL
ADAPTOR,MALE 1/4BSP-PX1/4IN ID**

- ขนาดบรรจุภัณฑ์: **2 x EA**
- Hose Connector Type: Hose Tail Adaptor
 - Connector Gender: Male
 - Thread Standard: G
 - Thread Size: 1/4 in
 - Hose Inner Diameter: 1/4 in
 - Body Material: Brass



5067187 Hose Tail Adaptor

**WATER,BRASS,HOSE TAIL
ADAPTOR,MALE 1/4BSP-PX5/16IN ID**

- ขนาดบรรจุภัณฑ์: **2 x EA**
- Hose Connector Type: Hose Tail Adaptor
 - Connector Gender: Male
 - Thread Standard: G
 - Thread Size: 1/4 in
 - Hose Inner Diameter: 5/16 in
 - Body Material: Brass



5067193 Hose Tail Adaptor

**WATER,BRASS,HOSE TAIL
ADAPTOR,MALE 1/4BSP-PX3/8IN ID**

- ขนาดบรรจุภัณฑ์: **2 x EA**
- Hose Connector Type: Hose Tail Adaptor
 - Connector Gender: Male
 - Thread Standard: G
 - Thread Size: 1/4 in
 - Hose Inner Diameter: 3/8 in
 - Body Material: Brass



5067200 Hose Tail Adaptor

**WATER,BRASS,HOSE TAIL
ADAPTOR,MALE 1/4BSP-PX1/2IN ID**

- ขนาดบรรจุภัณฑ์: **2 x EA**
- Hose Connector Type: Hose Tail Adaptor
 - Connector Gender: Male
 - Thread Standard: G
 - Thread Size: 1/4 in
 - Hose Inner Diameter: 1/2 in
 - Body Material: Brass



5067216 Hose Tail Adaptor

**WATER,BRASS,HOSE TAIL
ADAPTOR,MALE 3/8BSP-PX1/4IN ID**

- ขนาดบรรจุภัณฑ์: **2 x EA**
- Hose Connector Type: Hose Tail Adaptor
 - Connector Gender: Male
 - Thread Standard: G
 - Thread Size: 3/8 in
 - Hose Inner Diameter: 1/4 in
 - Body Material: Brass



5067238 Hose Tail Adaptor

**WATER,BRASS,HOSE TAIL
ADAPTOR,MALE 3/8BSP-PX3/8IN ID**

- ขนาดบรรจุภัณฑ์: **2 x EA**
- Hose Connector Type: Hose Tail Adaptor
 - Connector Gender: Male
 - Thread Standard: G
 - Thread Size: 3/8 in
 - Hose Inner Diameter: 3/8 in
 - Body Material: Brass



5067244 Hose Tail Adaptor

**WATER,BRASS,HOSE TAIL
ADAPTOR,MALE 3/8BSP-PX1/2IN ID**

- ขนาดบรรจุภัณฑ์: **2 x EA**
- Hose Connector Type: Hose Tail Adaptor
 - Connector Gender: Male
 - Thread Standard: G
 - Thread Size: 3/8 in
 - Hose Inner Diameter: 1/2 in
 - Body Material: Brass



5067250 Hose Tail Adaptor

**WATER,BRASS,HOSE TAIL
ADAPTOR,MALE 1/2BSP-PX1/4IN ID**

- ขนาดบรรจุภัณฑ์: **2 x EA**
- Hose Connector Type: Hose Tail Adaptor
 - Connector Gender: Male
 - Thread Standard: G
 - Thread Size: 1/2 in
 - Hose Inner Diameter: 1/4 in
 - Body Material: Brass



5067266 Hose Tail Adaptor

**WATER,BRASS,HOSE TAIL
ADAPTOR,MALE 1/2BSP-PX5/16IN ID**

- ขนาดบรรจุภัณฑ์: **2 x EA**
- Hose Connector Type: Hose Tail Adaptor
 - Connector Gender: Male
 - Thread Standard: G
 - Thread Size: 1/2 in
 - Hose Inner Diameter: 5/16 in
 - Body Material: Brass



5067272 Hose Tail Adaptor

**WATER,BRASS,HOSE TAIL
ADAPTOR,MALE 1/2BSP-PX3/8IN ID**

- ขนาดบรรจุภัณฑ์: **2 x EA**
- Hose Connector Type: Hose Tail Adaptor
 - Connector Gender: Male
 - Thread Standard: G
 - Thread Size: 1/2 in
 - Hose Inner Diameter: 3/8 in
 - Body Material: Brass



5067288 Hose Tail Adaptor

**WATER,BRASS,HOSE TAIL
ADAPTOR,MALE 1/2BSP-PX1/2IN ID**

- ขนาดบรรจุภัณฑ์: **2 x EA**
- Hose Connector Type: Hose Tail Adaptor
 - Connector Gender: Male
 - Thread Standard: G
 - Thread Size: 1/2 in
 - Hose Inner Diameter: 1/2 in
 - Body Material: Brass



5067294 Hose Tail Adaptor

**WATER,BRASS,HOSE TAIL
ADAPTOR,MALE 3/4BSP-PX3/4IN ID**

- ขนาดบรรจุภัณฑ์: **2 x EA**
- Hose Connector Type: Hose Tail Adaptor
 - Connector Gender: Male
 - Thread Standard: G
 - Thread Size: 3/4 in
 - Hose Inner Diameter: 3/4 in
 - Body Material: Brass



5067301 Hose Tail Adaptor

WATER, BRASS, HOSE TAIL ADAPTOR, MALE 1INBSP-PX1IN ID

- ขนาดบรรจุภัณฑ์: 2 x EA
- Hose Connector Type: Hose Tail Adaptor
 - Connector Gender: Male
 - Thread Standard: G
 - Thread Size: 1 in
 - Hose Inner Diameter: 1 in
 - Body Material: Brass



5067317 Hose Tail Adaptor

RS PRO TRANSPARENT FLEXIBLE TUBING, 8MM ID, PVC, 16 BAR MAX

- ขนาดบรรจุภัณฑ์: 25 x MTR
- Inner Diameter: 8 mm
 - Outer Diameter: 13.5 mm
 - Maximum Working Pressure: 16 bar
 - Material: PVC
 - Suitable Applications: Chemical, Compressed Air, Food, Liquid, Water
 - Minimum Operating Temperature: -15 °C
 - Maximum Operating Temperature: +60 °C
 - Length: 25 m



440054 8 mm

RS PRO TRANSPARENT FLEXIBLE TUBING, 4.75MM ID, PVC, 27 BAR

- ขนาดบรรจุภัณฑ์: 25 x MTR
- Inner Diameter: 4.75 mm
 - Outer Diameter: 10 mm
 - Maximum Working Pressure: 27 bar
 - Material: PVC
 - Suitable Applications: Chemical, Compressed Air, Food, Liquid, Water
 - Minimum Operating Temperature: -15 °C
 - Maximum Operating Temperature: +60 °C
 - Length: 25 m



440868 4.75 mm

RS PRO TRANSPARENT FLEXIBLE TUBING, 6.3MM ID, PVC, 16 BAR MAX

- ขนาดบรรจุภัณฑ์: 25 x MTR
- Inner Diameter: 6.3 mm
 - Outer Diameter: 11.5 mm
 - Maximum Working Pressure: 16 bar
 - Material: PVC
 - Suitable Applications: Chemical, Compressed Air, Food, Liquid, Water
 - Minimum Operating Temperature: -15 °C
 - Maximum Operating Temperature: +60 °C
 - Length: 25 m



440874 6.3 mm

RS PRO TRANSPARENT FLEXIBLE TUBING, 12.5MM ID, PVC, 15 BAR MAX

- ขนาดบรรจุภัณฑ์: 25 x MTR
- Inner Diameter: 12.5 mm
 - Outer Diameter: 18.5 mm
 - Maximum Working Pressure: 15 bar
 - Material: PVC
 - Suitable Applications: Chemical, Compressed Air, Food, Liquid, Water
 - Minimum Operating Temperature: -15 °C
 - Maximum Operating Temperature: +60 °C
 - Length: 25 m



440880 12.5 mm

RS PRO TRANSPARENT FLEXIBLE TUBING, 19MM ID, PVC, 10 BAR MAX

- ขนาดบรรจุภัณฑ์: 25 x MTR
- Inner Diameter: 19 mm
 - Outer Diameter: 25.75 mm
 - Maximum Working Pressure: 10 bar
 - Material: PVC
 - Suitable Applications: Chemical, Compressed Air, Food, Liquid, Water
 - Minimum Operating Temperature: -15 °C
 - Maximum Operating Temperature: +60 °C
 - Length: 25 m



440896 19 mm

RS PRO BLUE HOSE PIPE, 6.3MM ID, EPDM, SBR, 25M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 6.3 mm
 - Outer Diameter: 13.3 mm
 - Material: EPDM, SBR
 - Suitable Applications: Oxygen
 - Length: 25 m
 - Colour: Blue
 - Outer Material: EPDM
 - Flexible: Yes



486473 6.3 mm

RS PRO BLACK HOSE PIPE, 16MM ID, SBR, 25M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 16 mm
 - Outer Diameter: 26 mm
 - Material: SBR
 - Suitable Applications: Air, Water
 - Length: 25 m
 - Colour: Black
 - Bend Radius: 112 mm
 - Outer Material: SBR



486485 16 mm

RS PRO RED HOSE PIPE, 6.3MM ID, RUBBER, 25M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 6.3 mm
 - Outer Diameter: 13.3 mm
 - Material: Rubber
 - Suitable Applications: Acetylene Gas
 - Length: 25 m
 - Colour: Red
 - Reinforced: Yes
 - Bend Radius: 63 mm



486518 6.3 mm

RS PRO ORANGE HOSE PIPE, 6.3MM ID, EPDM, NBR, 25M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 6.3 mm
 - Outer Diameter: 13.3 mm
 - Material: EPDM, NBR
 - Suitable Applications: Butane, Liquefied Petroleum Gas, Propane
 - Length: 25 m
 - Colour: Orange
 - Reinforced: Yes
 - Flexible: Yes



486570 6.3 mm

RS PRO BLACK HOSE PIPE, 12.7MM ID, CR, NBR, 25M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 12.7 mm
 - Outer Diameter: 21.5 mm
 - Material: CR, NBR
 - Suitable Applications: Diesel, Oil, Paraffin
 - Length: 25 m
 - Colour: Black
 - Reinforced: Yes
 - Bend Radius: 50 mm



486637 12.7 mm

RS PRO BLACK HOSE PIPE, 7.9MM ID, CR, NBR, 25M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 7.9 mm
 - Outer Diameter: 15.9 mm
 - Material: CR, NBR
 - Suitable Applications: Diesel, Oil, Paraffin
 - Length: 25 m
 - Colour: Black
 - Reinforced: Yes
 - Bend Radius: 25 mm



486669 7.9 mm

RS PRO TRANSPARENT FLEXIBLE TUBING, 6MM ID, PVC, 4 BAR MAX

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 6 mm
 - Outer Diameter: 12 mm
 - Maximum Working Pressure: 4 bar
 - Material: PVC
 - Suitable Applications: Alcohol, Grease, Oil, Petrol, Solvent
 - Minimum Operating Temperature: -15 °C
 - Maximum Operating Temperature: +60 °C
 - Length: 25 m



797344 6 mm

RS PRO TRANSPARENT FLEXIBLE TUBING, 8MM ID, PVC, 4 BAR MAX

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 8 mm
 - Outer Diameter: 14 mm
 - Maximum Working Pressure: 4 bar
 - Material: PVC
 - Suitable Applications: Alcohol, Grease, Oil, Petrol, Solvent
 - Minimum Operating Temperature: -15 °C
 - Maximum Operating Temperature: +60 °C
 - Length: 25 m



797350 8 mm

RS PRO TRANSPARENT FLEXIBLE TUBING, 10MM ID, PVC, 4 BAR MAX

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 10 mm
 - Outer Diameter: 16 mm
 - Maximum Working Pressure: 4 bar
 - Material: PVC
 - Suitable Applications: Alcohol, Grease, Oil, Petrol, Solvent
 - Minimum Operating Temperature: -15 °C
 - Maximum Operating Temperature: +60 °C
 - Length: 25 m



797366 10 mm

RS PRO TRANSPARENT FLEXIBLE TUBING, 12MM ID, PVC, 4 BAR MAX

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 12 mm
 - Outer Diameter: 18 mm
 - Maximum Working Pressure: 4 bar
 - Material: PVC
 - Suitable Applications: Alcohol, Grease, Oil, Petrol, Solvent
 - Minimum Operating Temperature: -15 °C
 - Maximum Operating Temperature: +60 °C
 - Length: 25 m



797372 12 mm

RS PRO TRANSPARENT FLEXIBLE TUBING, 19MM ID, PVC, 4 BAR MAX

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 19 mm
 - Outer Diameter: 25 mm
 - Maximum Working Pressure: 4 bar
 - Material: PVC
 - Suitable Applications: Alcohol, Grease, Oil, Petrol, Solvent
 - Minimum Operating Temperature: -15 °C
 - Maximum Operating Temperature: +60 °C
 - Length: 25 m



797388 19 mm

RS PRO TRANSPARENT FLEXIBLE TUBING, 10MM ID, PVC, 15 BAR MAX

- ขนาดบรรจุภัณฑ์: **25 x MTR**
- Inner Diameter: 10 mm
 - Outer Diameter: 16 mm
 - Maximum Working Pressure: 15 bar
 - Material: PVC
 - Suitable Applications: Chemical, Compressed Air, Food, Liquid, Water
 - Minimum Operating Temperature: -15 °C
 - Maximum Operating Temperature: +60 °C
 - Length: 25 m



797394 10 mm

RS PRO BLACK FLEXIBLE TUBING, 19MM ID, PVC, 2 BAR MAX WORKING

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 19 mm
 - Outer Diameter: 23.7 mm
 - Maximum Working Pressure: 2 bar
 - Material: PVC
 - Suitable Applications: Agriculture, Aquatics, Domestic, Garden Ponds, Leisure, Marine
 - Minimum Operating Temperature: -10 °C
 - Maximum Operating Temperature: +55 °C
 - Length: 30 m



1369420 19 mm

RS PRO BLACK FLEXIBLE TUBING, 25.4MM ID, PVC, 2 BAR MAX

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 25.4 mm
 - Outer Diameter: 30.9 mm
 - Maximum Working Pressure: 2 bar
 - Material: PVC
 - Suitable Applications: Agriculture, Aquatics, Domestic, Garden Ponds, Leisure, Marine
 - Minimum Operating Temperature: -10 °C
 - Maximum Operating Temperature: +55 °C
 - Length: 30 m



1369421 25.4 mm

RS PRO BLACK FLEXIBLE TUBING, 38MM ID, PVC, 2 BAR MAX WORKING

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 38 mm
 - Outer Diameter: 44.4 mm
 - Maximum Working Pressure: 2 bar
 - Material: PVC
 - Suitable Applications: Agriculture, Aquatics, Domestic, Garden Ponds, Leisure, Marine
 - Minimum Operating Temperature: -10 °C
 - Maximum Operating Temperature: +55 °C
 - Length: 30 m



1369423 38 mm

RS PRO GREEN FLEXIBLE TUBING, 40.3MM ID, PVC, 6.5 BAR MAX

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 40.3 mm
 - Outer Diameter: 47.6 mm
 - Maximum Working Pressure: 6.5 bar
 - Material: PVC
 - Suitable Applications: Agriculture, Horticulture, Marine, Slurries
 - Minimum Operating Temperature: -10 °C
 - Maximum Operating Temperature: +55 °C
 - Length: 5 m



1369426 40.3 mm

RS PRO GREEN FLEXIBLE TUBING, 45MM ID, PVC, 6 BAR MAX WORKING

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 45 mm
 - Outer Diameter: 52.8 mm
 - Maximum Working Pressure: 6 bar
 - Material: PVC
 - Suitable Applications: Agriculture, Horticulture, Marine, Slurries
 - Minimum Operating Temperature: -10 °C
 - Maximum Operating Temperature: +55 °C
 - Length: 5 m



1369429 45 mm

RS PRO CLEAR FLEXIBLE TUBING, 51.6MM ID, PVC, 6 BAR MAX

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 51.6 mm
 - Outer Diameter: 59.8 mm
 - Maximum Working Pressure: 6 bar
 - Material: PVC
 - Suitable Applications: Food, Liquid
 - Minimum Operating Temperature: -10 °C
 - Maximum Operating Temperature: +55 °C
 - Length: 10 m



1369432 51.6 mm

RS PRO CLEAR FLEXIBLE TUBING, 51.6MM ID, PVC, 6 BAR MAX

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 51.6 mm
 - Outer Diameter: 59.8 mm
 - Maximum Working Pressure: 6 bar
 - Material: PVC
 - Suitable Applications: Food, Liquid
 - Minimum Operating Temperature: -10 °C
 - Maximum Operating Temperature: +55 °C
 - Length: 5 m



1369433 51.6 mm

RS PRO TRANSPARENT, WHITE FLEXIBLE TUBING, 19MM ID, PVC, 9

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 19 mm
 - Outer Diameter: 24.6 mm
 - Maximum Working Pressure: 9 bar
 - Material: PVC
 - Suitable Applications: Delivery, Food Contact Applications, Light Duty Suction of Liquids, Powder, Slurries, Water
 - Minimum Operating Temperature: -10 °C
 - Maximum Operating Temperature: +55 °C
 - Length: 10 m



1369436 19 mm

RS PRO TRANSPARENT, WHITE FLEXIBLE TUBING, 32MM ID, PVC, 7

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 32 mm
 - Outer Diameter: 39.2 mm
 - Maximum Working Pressure: 7 bar
 - Material: PVC
 - Suitable Applications: Delivery, Food Contact Applications, Light Duty Suction of Liquids, Powder, Slurries, Water
 - Minimum Operating Temperature: -10 °C
 - Maximum Operating Temperature: +55 °C
 - Length: 10 m



1369438 32 mm

RS PRO TRANSPARENT, WHITE FLEXIBLE TUBING, 45MM ID, PVC, 6

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 45 mm
 - Outer Diameter: 52.8 mm
 - Maximum Working Pressure: 6 bar
 - Material: PVC
 - Suitable Applications: Delivery, Food Contact Applications, Light Duty Suction of Liquids, Powder, Slurries, Water
 - Minimum Operating Temperature: -10 °C
 - Maximum Operating Temperature: +55 °C
 - Length: 10 m



1369441 45 mm

RS PRO TRANSPARENT, WHITE FLEXIBLE TUBING, 102MM ID, PVC, 4

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 102 mm
 - Outer Diameter: 114.6 mm
 - Maximum Working Pressure: 4 bar
 - Material: PVC
 - Suitable Applications: Delivery, Food Contact Applications, Light Duty Suction of Liquids, Powder, Slurries, Water
 - Minimum Operating Temperature: -10 °C
 - Maximum Operating Temperature: +55 °C
 - Length: 10 m



1369446 102 mm

RS PRO GREEN FLEXIBLE TUBING, 19MM ID, PVC, 9 BAR MAX WORKING

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 19 mm
 - Outer Diameter: 25.6 mm
 - Maximum Working Pressure: 9 bar
 - Material: PVC
 - Suitable Applications: Agriculture, Horticulture, Marine, Slurries
 - Minimum Operating Temperature: -10 °C
 - Maximum Operating Temperature: +55 °C
 - Length: 10 m



1369447 19 mm

RS PRO GREEN FLEXIBLE TUBING, 25.4MM ID, PVC, 8 BAR MAX

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 25.4 mm
 - Outer Diameter: 32 mm
 - Maximum Working Pressure: 8 bar
 - Material: PVC
 - Suitable Applications: Agriculture, Horticulture, Marine, Slurries
 - Minimum Operating Temperature: -10 °C
 - Maximum Operating Temperature: +55 °C
 - Length: 10 m



1369448 25.4 mm

RS PRO GREEN FLEXIBLE TUBING, 32MM ID, PVC, 7 BAR MAX WORKING

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 32 mm
 - Outer Diameter: 39.6 mm
 - Maximum Working Pressure: 7 bar
 - Material: PVC
 - Suitable Applications: Agriculture, Horticulture, Marine, Slurries
 - Minimum Operating Temperature: -10 °C
 - Maximum Operating Temperature: +55 °C
 - Length: 10 m



1369449 32 mm

RS PRO GREEN FLEXIBLE TUBING, 51.6MM ID, PVC, 6 BAR MAX

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 51.6 mm
 - Outer Diameter: 60.2 mm
 - Maximum Working Pressure: 6 bar
 - Material: PVC
 - Suitable Applications: Agriculture, Horticulture, Marine, Slurries
 - Minimum Operating Temperature: -10 °C
 - Maximum Operating Temperature: +55 °C
 - Length: 10 m



1369451 51.6 mm

RS PRO BLUE FLEXIBLE TUBING, 38MM ID, PVC, 5M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 38 mm
 - Outer Diameter: 47 mm
 - Material: PVC
 - Suitable Applications: Agriculture, Automotive, Construction Industries, Delivery, Diesel, Hazardous Areas, Industrial, Kerosene, Marine, Mineral Based Hydraulic Oils, Mining, Rail, Spirits, Suction
 - Minimum Operating Temperature: -10 °C
 - Maximum Operating Temperature: +55 °C
 - Length: 5 m
 - Colour: Blue



1369470 38 mm

RS PRO YELLOW FLEXIBLE TUBING, 12.5MM ID, PVC, 10 BAR MAX

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 12.5 mm
 - Outer Diameter: 17.5 mm
 - Maximum Working Pressure: 10 bar
 - Material: PVC
 - Suitable Applications: Agriculture, Delivery, Horticulture, Irrigator, Leisure, Sport, Wash Down, Water
 - Minimum Operating Temperature: -10 °C
 - Maximum Operating Temperature: +55 °C
 - Length: 25 m



1369491 12.5 mm

RS PRO YELLOW FLEXIBLE TUBING, 19MM ID, PVC, 10 BAR MAX WORKING

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 19 mm
 - Outer Diameter: 19.0 mm
 - Maximum Working Pressure: 10 bar
 - Material: PVC
 - Suitable Applications: Agriculture, Delivery, Horticulture, Irrigator, Leisure, Sport, Wash Down, Water
 - Minimum Operating Temperature: -10 °C
 - Maximum Operating Temperature: +55 °C
 - Length: 25 m



1369492 19 mm

RS PRO YELLOW FLEXIBLE TUBING, 19MM ID, PVC, 10 BAR MAX WORKING

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 19 mm
 - Outer Diameter: 19.0 mm
 - Maximum Working Pressure: 10 bar
 - Material: PVC
 - Suitable Applications: Agriculture, Delivery, Horticulture, Irrigator, Leisure, Sport, Wash Down, Water
 - Minimum Operating Temperature: -10 °C
 - Maximum Operating Temperature: +55 °C
 - Length: 50 m



1369495 19 mm

RS PRO CLEAR HOSE PIPE, 19MM ID, PVC, 10M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 19 mm
 - Outer Diameter: 26 mm
 - Material: PVC
 - Length: 10 m
 - Colour: Clear
 - Reinforced: Yes
 - Bend Radius: 45 mm



1369497 19 mm

RS PRO CLEAR HOSE PIPE, 19MM ID, PVC, 5M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 19 mm
 - Outer Diameter: 26 mm
 - Material: PVC
 - Length: 5 m
 - Colour: Clear
 - Reinforced: Yes
 - Bend Radius: 45 mm



1369498 19 mm

RS PRO CLEAR HOSE PIPE, 25MM ID, PVC, 10M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 25 mm
 - Outer Diameter: 33 mm
 - Material: PVC
 - Length: 10 m
 - Colour: Clear
 - Reinforced: Yes
 - Bend Radius: 60 mm



1369499 25 mm

RS PRO CLEAR HOSE PIPE, 25MM ID, PVC, 5M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 25 mm
 - Outer Diameter: 33 mm
 - Material: PVC
 - Length: 5 m
 - Colour: Clear
 - Reinforced: Yes
 - Bend Radius: 60 mm



1369500 25 mm

RS PRO CLEAR HOSE PIPE, 32MM ID, PVC, 10M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 32 mm
 - Outer Diameter: 40.2 mm
 - Material: PVC
 - Length: 10 m
 - Colour: Clear
 - Reinforced: Yes
 - Bend Radius: 75 mm



1369501 32 mm

RS PRO CLEAR HOSE PIPE, 35MM ID, PVC, 5M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 35 mm
 - Outer Diameter: 43 mm
 - Material: PVC
 - Suitable Applications: Agriculture, Construction Industries, Delivery, Dilute Chemicals, Food, Food Processing, Granule, Marine, Plastics Handling, Slurries,
 - Length: 5 m
 - Colour: Clear
 - Reinforced: Yes



1369505 35 mm

RS PRO CLEAR HOSE PIPE, 38MM ID, PVC, 5M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 38 mm
 - Outer Diameter: 47 mm
 - Material: PVC
 - Suitable Applications: Agriculture, Construction Industries, Delivery, Dilute Chemicals, Food, Food Processing, Granule, Marine, Plastics Handling, Slurries,
 - Length: 5 m
 - Colour: Clear
 - Reinforced: Yes
 - Bend Radius: 90 mm



1369507 38 mm

RS PRO CLEAR HOSE PIPE, 51MM ID, PVC, 5M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 51 mm
 - Outer Diameter: 61.8 mm
 - Material: PVC
 - Length: 5 m
 - Colour: Clear
 - Reinforced: Yes
 - Bend Radius: 128 mm



1369511 51 mm

RS PRO CLEAR HOSE PIPE, 60MM ID, PVC, 5M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 60 mm
 - Outer Diameter: 72 mm
 - Material: PVC
 - Suitable Applications: Agriculture, Construction Industries, Delivery, Dilute Chemicals, Food, Food Processing, Granule, Marine, Plastics Handling, Slurries,
 - Length: 5 m
 - Colour: Clear
 - Reinforced: Yes
 - Bend Radius: 140 mm



1369513 60 mm

RS PRO CLEAR HOSE PIPE, 80MM ID, PVC, 10M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 80 mm
 - Outer Diameter: 94 mm
 - Material: PVC
 - Suitable Applications: Agriculture, Construction Industries, Delivery, Dilute Chemicals, Food, Food Processing, Granule, Marine, Plastics Handling, Slurries,
 - Length: 10 m
 - Colour: Clear
 - Reinforced: Yes
 - Bend Radius: 220 mm



1369516 80 mm

RS PRO CLEAR HOSE PIPE, 19MM ID, PVC, 10M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 19 mm
 - Outer Diameter: 26 mm
 - Material: PVC
 - Length: 10 m
 - Colour: Clear
 - Reinforced: Yes
 - Bend Radius: 45 mm



1369520 19 mm

RS PRO CLEAR HOSE PIPE, 19MM ID, PVC, 11 BAR MAX WORKING

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 19 mm
 - Outer Diameter: 26 mm
 - Maximum Working Pressure: 11 bar
 - Material: PVC
 - Suitable Applications: Agricultural, Construction Industries, Food Processing, Foodstuffs/Dilute Chemicals, Granules, Marine, Plastics Handling, Slurries, Suction/Delivery of Water
 - Minimum Operating Temperature: -10 °C
 - Maximum Operating Temperature: +55 °C
 - Length: 5 m



1369521 19 mm

RS PRO CLEAR HOSE PIPE, 25MM ID, PVC, 10 BAR MAX WORKING

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 25 mm
 - Outer Diameter: 33 mm
 - Maximum Working Pressure: 10 bar
 - Material: PVC
 - Suitable Applications: Agricultural, Construction Industries, Food Processing, Foodstuffs/Dilute Chemicals, Granules, Marine, Plastics Handling, Slurries, Suction/Delivery of Water
 - Minimum Operating Temperature: -10 °C
 - Maximum Operating Temperature: +55 °C
 - Length: 10 m



1369522 25 mm

RS PRO CLEAR HOSE PIPE, 25MM ID, PVC, 10 BAR MAX WORKING

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 25 mm
 - Outer Diameter: 33 mm
 - Maximum Working Pressure: 10 bar
 - Material: PVC
 - Suitable Applications: Agricultural, Construction Industries, Food Processing, Foodstuffs/Dilute Chemicals, Granules, Marine, Plastics Handling, Slurries, Suction/Delivery of Water
 - Minimum Operating Temperature: -10 °C
 - Maximum Operating Temperature: +55 °C
 - Length: 5 m



1369523 25 mm

RS PRO CLEAR HOSE PIPE, 32MM ID, PVC, 9 BAR MAX WORKING

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 32 mm
 - Outer Diameter: 40.2 mm
 - Maximum Working Pressure: 9 bar
 - Material: PVC
 - Suitable Applications: Agricultural, Construction Industries, Food Processing, Foodstuffs/Dilute Chemicals, Granules, Marine, Plastics Handling, Slurries, Suction/Delivery of Water
 - Minimum Operating Temperature: -10 °C
 - Maximum Operating Temperature: +55 °C
 - Length: 10 m



1369525 32 mm

RS PRO CLEAR HOSE PIPE, 51MM ID, PVC, 10M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 51 mm
 - Outer Diameter: 61.8 mm
 - Material: PVC
 - Length: 10 m
 - Colour: Clear
 - Reinforced: Yes
 - Bend Radius: 128 mm



1369529 51 mm

RS PRO CLEAR HOSE PIPE, 51MM ID, PVC, 5M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 51 mm
 - Outer Diameter: 61.8 mm
 - Material: PVC
 - Length: 5 m
 - Colour: Clear
 - Reinforced: Yes
 - Bend Radius: 128 mm



1369531 51 mm

RS PRO BLACK HOSE PIPE, 9.5MM ID, EPDM, 25M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 9.5 mm
 - Outer Diameter: 16.5 mm
 - Material: EPDM
 - Suitable Applications: Air, Water
 - Length: 25 m
 - Colour: Black
 - Bend Radius: 50 mm
 - Outer Material: EPDM



1467725 9.5 mm

RS PRO BLACK HOSE PIPE, 19MM ID, 25M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 19 mm
 - Suitable Applications: Air, Water
 - Length: 25 m
 - Colour: Black
 - Outer Material: EPDM
 - Inner Material: EPDM



1467727 19 mm

RS PRO BLACK/BLUE HOSE PIPE, 9.5MM ID, EPDM, 25M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 9.5 mm
 - Outer Diameter: 16.5 mm
 - Material: EPDM
 - Suitable Applications: Air, Water
 - Length: 25 m
 - Colour: Black/Blue
 - Outer Material: EPDM
 - Flexible: Yes



1467730 9.5 mm

RS PRO BLACK/BLUE HOSE PIPE, 12.7MM ID, EPDM, 25M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 12.7 mm
 - Outer Diameter: 21.5 mm
 - Material: EPDM
 - Suitable Applications: Air, Water
 - Length: 25 m
 - Colour: Black/Blue
 - Outer Material: EPDM
 - Flexible: Yes



1467731 12.7 mm

RS PRO BLACK/BLUE HOSE PIPE, 19MM ID, EPDM, 25M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 19 mm
 - Outer Diameter: 27 mm
 - Material: EPDM
 - Suitable Applications: Air, Water
 - Length: 25 m
 - Colour: Black/Blue
 - Outer Material: EPDM
 - Flexible: Yes



1467732 19 mm

RS PRO BLACK/RED HOSE PIPE, 9.5MM ID, EPDM, 25M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 9.5 mm
 - Outer Diameter: 16.6 mm
 - Material: EPDM
 - Suitable Applications: Air, Water
 - Length: 25 m
 - Colour: Black/Red
 - Outer Material: EPDM
 - Flexible: Yes



1467734 9.5 mm

RS PRO BLACK/RED HOSE PIPE, 19MM ID, EPDM, 25M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 19 mm
 - Outer Diameter: 27 mm
 - Material: EPDM
 - Suitable Applications: Air, Water
 - Length: 25 m
 - Colour: Black/Red
 - Outer Material: EPDM
 - Flexible: Yes



1467737 19 mm

RS PRO BLACK, ORANGE HOSE PIPE, 8MM ID, EPDM, NBR, 25M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 8 mm
 - Outer Diameter: 15 mm
 - Material: EPDM, NBR
 - Suitable Applications: Butane, Liquefied Petroleum Gas, Propane
 - Length: 25 m
 - Colour: Black, Orange
 - Reinforced: Yes
 - Flexible: Yes



1467752 8 mm

RS PRO BLACK, RED, BLUE HOSE PIPE, 6.3MM ID, EPDM, 25M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 6.3 mm
 - Outer Diameter: 13.5 mm
 - Material: EPDM
 - Suitable Applications: Acetylene Gas
 - Length: 25 m
 - Colour: Black, Red, Blue
 - Reinforced: Yes
 - Flexible: Yes



1467756 6.3 mm

RS PRO BLACK, RED, BLUE HOSE PIPE, 8MM ID, EPDM, 25M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 8 mm
 - Outer Diameter: 15.2 mm
 - Material: EPDM
 - Suitable Applications: Acetylene Gas
 - Length: 25 m
 - Colour: Black, Red, Blue
 - Reinforced: Yes
 - Flexible: Yes



1467758 8 mm

RS PRO BLACK HOSE PIPE, 5MM ID, EPDM, 25M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 5 mm
 - Outer Diameter: 11 mm
 - Material: EPDM
 - Suitable Applications: Argon
 - Length: 25 m
 - Colour: Black
 - Reinforced: Yes
 - Outer Material: SBR



1467760 5 mm

RS PRO NATURAL FLEXIBLE TUBING, 4MM ID,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 4 mm
 - Outer Diameter: 6 mm
 - Material: Polytetrafluoroethylene (PTFE)
 - Suitable Applications: Chemical Transfer, Fuel And Lubricant Lines, Pneumatic Control System
 - Minimum Operating Temperature: -60 °C
 - Maximum Operating Temperature: +250 °C
 - Length: 50 m
 - Colour: Natural



1860591 4 mm

RS PRO NATURAL FLEXIBLE TUBING, 6MM ID,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 6 mm
 - Outer Diameter: 8 mm
 - Material: Polytetrafluoroethylene (PTFE)
 - Suitable Applications: Chemical Transfer, Fuel And Lubricant Lines, Pneumatic Control System
 - Minimum Operating Temperature: -60 °C
 - Maximum Operating Temperature: +250 °C
 - Length: 50 m
 - Colour: Natural



1860592 6 mm

RS PRO NATURAL FLEXIBLE TUBING, 8MM ID,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 8 mm
 - Outer Diameter: 10 mm
 - Material: Polytetrafluoroethylene (PTFE)
 - Suitable Applications: Chemical Transfer, Fuel And Lubricant Lines, Pneumatic Control System
 - Minimum Operating Temperature: -60 °C
 - Maximum Operating Temperature: +250 °C
 - Length: 50 m
 - Colour: Natural



1860593 8 mm

RS PRO NATURAL FLEXIBLE TUBING, 10MM ID,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 10 mm
 - Outer Diameter: 16 mm
 - Material: Polytetrafluoroethylene (PTFE)
 - Suitable Applications: Chemical Transfer, Fuel And Lubricant Lines, Pneumatic Control System
 - Minimum Operating Temperature: -60 °C
 - Maximum Operating Temperature: +250 °C
 - Length: 50 m
 - Colour: Natural



1860595 10 mm

RS PRO WHITE FLEXIBLE TUBING, 10MM ID, PVC, 10 BAR MAX

- ขนาดบรรจุภัณฑ์: 10 x MTR
- Inner Diameter: 10 mm
 - Outer Diameter: 16 mm
 - Maximum Working Pressure: 10 bar
 - Material: PVC
 - Suitable Applications: Water
 - Minimum Operating Temperature: -15 °C
 - Maximum Operating Temperature: +70 °C
 - Length: 10 m



1978229 10 mm

RS PRO WHITE FLEXIBLE TUBING, 12.5MM ID, PVC, 10 BAR MAX

- ขนาดบรรจุภัณฑ์: 10 x MTR
- Inner Diameter: 12.5 mm
 - Outer Diameter: 19 mm
 - Maximum Working Pressure: 10 bar
 - Material: PVC
 - Suitable Applications: Water
 - Minimum Operating Temperature: -15 °C
 - Maximum Operating Temperature: +70 °C
 - Length: 10 m



1978241 12.5 mm

HOSE, WATER, VENDING, CODEFLEX AQUAVEND, 19MM BORE X 26MM O/D

- ขนาดบรรจุภัณฑ์: 10 x MTR
- Inner Diameter: 19 mm
 - Outer Diameter: 26 mm
 - Material: PVC
 - Colour: White
 - Reinforced: Yes
 - Suitable Applications: Water
 - Minimum Operating Temperature: -15 °C



1978257 19 mm

RS PRO BLACK, YELLOW HOSE, 8MM ID, PVC, 20 BAR MAX WORKING

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 8 mm
 - Outer Diameter: 16 mm
 - Maximum Working Pressure: 20 bar
 - Material: PVC
 - Length: 30 m
 - Colour: Black, Yellow



1978522 8 mm

RS PRO BLACK, YELLOW HOSE, 10MM ID, PVC, 30MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 10 mm
 - Outer Diameter: 18 mm
 - Material: PVC
 - Length: 30 m
 - Colour: Black, Yellow



1978538 10 mm

RS PRO YELLOW FLEXIBLE TUBING, 12MM ID, PVC, 10 BAR MAX WORKING

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 12 mm
 - Outer Diameter: 17.5 mm
 - Maximum Working Pressure: 10 bar
 - Material: PVC
 - Suitable Applications: Water
 - Minimum Operating Temperature: -15 °C
 - Maximum Operating Temperature: +60 °C
 - Length: 25 m



1978279 12 mm

RS PRO BLACK, YELLOW HOSE, 12.5MM ID, 30M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 12.5 mm
 - Outer Diameter: 22 mm
 - Length: 30 m
 - Colour: Black, Yellow



1978544 12.5 mm

RS PRO BLACK, YELLOW HOSE, 30M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 30 m
 - Colour: Black, Yellow



1978550 30 m

RS PRO GREEN FLEXIBLE TUBING, 12MM ID, PVC, 15M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 12 mm
 - Outer Diameter: 15.3 mm
 - Material: PVC
 - Minimum Operating Temperature: -15 °C
 - Maximum Operating Temperature: +60 °C
 - Length: 15 m
 - Colour: Green
 - Reinforced: Yes



2020988 12 mm

RS PRO TRANSLUCENT WHITE FLEXIBLE TUBE, 2MM ID, RUBBER, 50M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 2 mm
 - Material: Rubber
 - Suitable Applications: Chemical Transfer, Drinking Water Supply, Electrically Insulating Tube, Food Processing, Laboratories, Medical, Peristaltic pumps
 - Length: 50 m
 - Colour: Translucent White
 - Reinforced: No
 - Flexible: Yes
 - Outer Material: Silicone Rubber



2354805 2 mm

RS PRO TRANSLUCENT WHITE FLEXIBLE TUBE, 5MM ID, RUBBER, 25M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 5 mm
 - Material: Rubber
 - Suitable Applications: Chemical Transfer, Drinking Water Supply, Electrically Insulating Tube, Food Processing, Laboratories, Medical, Peristaltic pumps
 - Length: 25 m
 - Colour: Translucent White
 - Reinforced: No
 - Flexible: Yes
 - Outer Material: Silicone Rubber



2354806 5 mm

RS PRO TRANSLUCENT WHITE FLEXIBLE TUBE, 6MM ID, RUBBER, 25M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 6 mm
 - Material: Rubber
 - Suitable Applications: Chemical Transfer, Drinking Water Supply, Electrically Insulating Tube, Food Processing, Laboratories, Medical, Peristaltic pumps
 - Length: 25 m
 - Colour: Translucent White
 - Reinforced: No
 - Flexible: Yes
 - Outer Material: Silicone Rubber



2354807 6 mm

RS PRO TRANSLUCENT WHITE FLEXIBLE TUBE, 8MM ID, RUBBER, 25M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 8 mm
 - Material: Rubber
 - Suitable Applications: Chemical Transfer, Drinking Water Supply, Electrically Insulating Tube, Food Processing, Laboratories, Medical, Peristaltic pumps
 - Length: 25 m
 - Colour: Translucent White
 - Reinforced: No
 - Flexible: Yes
 - Outer Material: Silicone Rubber



2354808 8 mm

RS PRO TRANSPARENT HOSE PIPE, 20MM ID, 5M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 20 mm
 - Hose Pipe Action: Delivery
 - Suitable Applications: Agricultural, Food, Marine, Water
 - Length: 5 m
 - Colour: Transparent
 - Reinforced: Yes
 - Outer Material: PVC
 - Flexible: Yes



2354811 20 mm

RS PRO TRANSPARENT FLEXIBLE TUBING, 25MM ID, PVC, 10 BAR MAX

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 25 mm
 - Outer Diameter: 32.5 mm
 - Maximum Working Pressure: 10 bar
 - Material: PVC
 - Suitable Applications: Chemical, Compressed Air, Food, Liquid, Water
 - Minimum Operating Temperature: -15 °C
 - Maximum Operating Temperature: +60 °C
 - Length: 15 m



2430166 25 mm

RS PRO BLUE FLEXIBLE TUBING, 8MM ID, PVC, 15 BAR MAX WORKING

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 8 mm
 - Outer Diameter: 12.5 mm
 - Maximum Working Pressure: 15 bar
 - Material: PVC
 - Suitable Applications: Compressed Air, Water
 - Minimum Operating Temperature: -15 °C
 - Maximum Operating Temperature: +60 °C
 - Length: 30 m



2932088 8 mm

RS PRO BLUE FLEXIBLE TUBING, 12MM ID, PVC, 11 BAR MAX WORKING

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 12 mm
 - Outer Diameter: 17 mm
 - Maximum Working Pressure: 11 bar
 - Material: PVC
 - Suitable Applications: Compressed Air, Water
 - Minimum Operating Temperature: -15 °C
 - Maximum Operating Temperature: +60 °C
 - Length: 30 m



2932101 12 mm

RS PRO BLUE FLEXIBLE TUBING, 19MM ID, PVC, 11 BAR MAX WORKING

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 19 mm
 - Outer Diameter: 24.5 mm
 - Maximum Working Pressure: 11 bar
 - Material: PVC
 - Suitable Applications: Compressed Air, Water
 - Minimum Operating Temperature: -15 °C
 - Maximum Operating Temperature: +60 °C
 - Length: 30 m



2932123 19 mm

HOSE, WATER, REINFORCED, GH SERIES, 12MM BORE X 30M, COIL

- ขนาดบรรจุภัณฑ์: **30 x MTR**
- Inner Diameter: 12 mm
 - Material: PVC
 - Colour: Green
 - Reinforced: Yes
 - Suitable Applications: Water
 - Length: 30 m
 - Minimum Operating Temperature: -15 °C
 - Maximum Operating Temperature: +60 °C



3300858 12 mm

RS PRO GREEN FLEXIBLE TUBING, 12MM ID, PVC, 10 BAR MAX WORKING

- ขนาดบรรจุภัณฑ์: **50 x MTR**
- Inner Diameter: 12 mm
 - Maximum Working Pressure: 10 bar
 - Material: PVC
 - Suitable Applications: Water
 - Minimum Operating Temperature: -15 °C
 - Maximum Operating Temperature: +60 °C
 - Length: 50 m
 - Colour: Green



3300870 12 mm

RS PRO BLUE FLEXIBLE TUBING, 6MM ID, PVC, 14 BAR MAX WORKING

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 6 mm
 - Outer Diameter: 9 mm
 - Maximum Working Pressure: 14 bar
 - Material: PVC
 - Suitable Applications: Chemical, Gas, Water
 - Minimum Operating Temperature: -15 °C
 - Maximum Operating Temperature: +60 °C
 - Length: 25 m



3396039 6 mm

RS PRO BLUE FLEXIBLE TUBING, 8MM ID, PVC, 14 BAR MAX WORKING

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 8 mm
 - Outer Diameter: 10.5 mm
 - Maximum Working Pressure: 14 bar
 - Material: PVC
 - Suitable Applications: Chemical, Gas, Water
 - Minimum Operating Temperature: -15 °C
 - Maximum Operating Temperature: +60 °C
 - Length: 25 m



3396045 8 mm

RS PRO BLUE FLEXIBLE TUBING, 10MM ID, PVC, 12 BAR MAX WORKING

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 10 mm
 - Outer Diameter: 13 mm
 - Maximum Working Pressure: 12 bar
 - Material: PVC
 - Suitable Applications: Chemical, Gas, Water
 - Minimum Operating Temperature: -15 °C
 - Maximum Operating Temperature: +60 °C
 - Length: 25 m



3396051 10 mm

RS PRO BLUE FLEXIBLE TUBING, 8MM ID, PVC, 16 BAR MAX WORKING

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 8 mm
 - Outer Diameter: 13.5 mm
 - Maximum Working Pressure: 16 bar
 - Material: PVC
 - Suitable Applications: Chemical, Compressed Air, Food, Liquid, Water
 - Minimum Operating Temperature: -15 °C
 - Maximum Operating Temperature: +60 °C
 - Length: 25 m



3396089 8 mm

RS PRO BLUE FLEXIBLE TUBING, 10MM ID, PVC, 15 BAR MAX WORKING

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 10 mm
 - Outer Diameter: 16 mm
 - Maximum Working Pressure: 15 bar
 - Material: PVC
 - Suitable Applications: Chemical, Compressed Air, Food, Liquid, Water
 - Minimum Operating Temperature: -15 °C
 - Maximum Operating Temperature: +60 °C
 - Length: 25 m



3396095 10 mm

RS PRO BLUE FLEXIBLE TUBING, 12.5MM ID, PVC, 15 BAR MAX

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 12.5 mm
 - Outer Diameter: 18.5 mm
 - Maximum Working Pressure: 15 bar
 - Material: PVC
 - Suitable Applications: Chemical, Compressed Air, Food, Liquid, Water
 - Minimum Operating Temperature: -15 °C
 - Maximum Operating Temperature: +60 °C
 - Length: 25 m



3396102 12.5 mm

RS PRO RED FLEXIBLE TUBING, 8MM ID, PVC, 16 BAR MAX WORKING

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 8 mm
 - Outer Diameter: 13.5 mm
 - Maximum Working Pressure: 16 bar
 - Material: PVC
 - Suitable Applications: Chemical, Compressed Air, Food, Liquid, Water
 - Minimum Operating Temperature: -15 °C
 - Maximum Operating Temperature: +60 °C
 - Length: 25 m



3396124 8 mm

RS PRO RED FLEXIBLE TUBING, 10MM ID, PVC, 15 BAR MAX WORKING

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 10 mm
 - Outer Diameter: 16 mm
 - Maximum Working Pressure: 15 bar
 - Material: PVC
 - Suitable Applications: Chemical, Compressed Air, Food, Liquid, Water
 - Minimum Operating Temperature: -15 °C
 - Maximum Operating Temperature: +60 °C
 - Length: 25 m



3396130 10 mm

RS PRO RED FLEXIBLE TUBING, 12.5MM ID, PVC, 15 BAR MAX

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 12.5 mm
 - Outer Diameter: 18.5 mm
 - Maximum Working Pressure: 15 bar
 - Material: PVC
 - Suitable Applications: Chemical, Compressed Air, Food, Liquid, Water
 - Minimum Operating Temperature: -15 °C
 - Maximum Operating Temperature: +60 °C
 - Length: 25 m



3396146 12.5 mm

RS PRO BLACK FLEXIBLE TUBING, 6.3MM ID, PVC, 16 BAR MAX

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 6.3 mm
 - Outer Diameter: 11.5 mm
 - Maximum Working Pressure: 16 bar
 - Material: PVC
 - Suitable Applications: Chemical, Compressed Air, Food, Liquid, Water
 - Minimum Operating Temperature: -15 °C
 - Maximum Operating Temperature: +60 °C
 - Length: 25 m



3396253 6.3 mm

RS PRO BLACK FLEXIBLE TUBING, 10MM ID, PVC, 15 BAR MAX

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 10 mm
 - Outer Diameter: 16 mm
 - Maximum Working Pressure: 15 bar
 - Material: PVC
 - Suitable Applications: Chemical, Compressed Air, Food, Liquid, Water
 - Minimum Operating Temperature: -15 °C
 - Maximum Operating Temperature: +60 °C
 - Length: 25 m



3396275 10 mm

RS PRO TRANSPARENT FLEXIBLE TUBING, 6.3MM ID, PUR, 13 BAR MAX

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 6.3 mm
 - Outer Diameter: 12 mm
 - Maximum Working Pressure: 13 bar
 - Material: PUR
 - Suitable Applications: Fuel, Gas, Granule, Liquid, Powder, Solvent
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +65 °C
 - Length: 25 m



3396281 6.3 mm

RS PRO TRANSPARENT FLEXIBLE TUBING, 8MM ID, PUR, 11 BAR MAX

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 8 mm
 - Outer Diameter: 14 mm
 - Maximum Working Pressure: 11 bar
 - Material: PUR
 - Suitable Applications: Fuel, Gas, Granule, Liquid, Powder, Solvent
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +65 °C
 - Length: 25 m



3396297 8 mm

RS PRO TRANSPARENT FLEXIBLE TUBING, 10MM ID, PUR, 10 BAR MAX

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 10 mm
 - Outer Diameter: 15.75 mm
 - Maximum Working Pressure: 10 bar
 - Material: PUR
 - Suitable Applications: Fuel, Gas, Granule, Liquid, Powder, Solvent
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +65 °C
 - Length: 25 m



3396304 10 mm

RS PRO TRANSPARENT FLEXIBLE TUBING, 12.5MM ID, PUR, 7 BAR MAX

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 12.5 mm
 - Outer Diameter: 18.5 mm
 - Maximum Working Pressure: 7 bar
 - Material: PUR
 - Suitable Applications: Fuel, Gas, Granule, Liquid, Powder, Solvent
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +65 °C
 - Length: 25 m



3396310 12.5 mm

TUBE,CLEAR,UNREINFORCED POLYURETHANE,6.3MM I/D X25M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 6.3 mm
 - Outer Diameter: 12 mm
 - Material: PUR
 - Colour: Transparent
 - Reinforced: No
 - Suitable Applications: Gas, Liquid, Powder
 - Length: 25 m
 - Minimum Operating Temperature: -40 °C



3396326 6.3 mm

RS PRO TRANSPARENT FLEXIBLE TUBING, 8MM ID, PUR, 10 BAR MAX

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 8 mm
 - Outer Diameter: 14 mm
 - Maximum Working Pressure: 10 bar
 - Material: PUR
 - Suitable Applications: Gas, Liquid, Powder
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +65 °C
 - Length: 25 m



3396332 8 mm

RS PRO TRANSPARENT FLEXIBLE TUBING, 10MM ID, PUR, 10 BAR MAX

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 10 mm
 - Outer Diameter: 16 mm
 - Maximum Working Pressure: 10 bar
 - Material: PUR
 - Suitable Applications: Gas, Liquid, Powder
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +65 °C
 - Length: 25 m



3396348 10 mm

RS PRO TRANSPARENT FLEXIBLE TUBING, 12.5MM ID, PUR, 10 BAR MAX

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 12.5 mm
 - Outer Diameter: 19 mm
 - Maximum Working Pressure: 10 bar
 - Material: PUR
 - Suitable Applications: Gas, Liquid, Powder
 - Minimum Operating Temperature: -40 °C
 - Maximum Operating Temperature: +65 °C
 - Length: 25 m



3396354 12.5 mm

RS PRO BLUE FLEXIBLE TUBING, 77MM ID, PVC, 4 BAR MAX WORKING

- ขนาดบรรจุภัณฑ์: **10 x MTR**
- Inner Diameter: 77 mm
 - Outer Diameter: 80.6 mm
 - Maximum Working Pressure: 4 bar
 - Material: PVC
 - Suitable Applications: Chemical, Water
 - Minimum Operating Temperature: -25 °C
 - Maximum Operating Temperature: +60 °C
 - Length: 10 m



3396360 77 mm

RS PRO BLUE FLEXIBLE TUBING, 77MM ID, PVC, 4 BAR MAX WORKING

- ขนาดบรรจุภัณฑ์: **20 x MTR**
- Inner Diameter: 77 mm
 - Outer Diameter: 80.6 mm
 - Maximum Working Pressure: 4 bar
 - Material: PVC
 - Suitable Applications: Chemical, Water
 - Minimum Operating Temperature: -25 °C
 - Maximum Operating Temperature: +60 °C
 - Length: 20 m



3396376 77 mm

RS PRO YELLOW FLEXIBLE TUBING, 12MM ID, PVC, 10 BAR MAX WORKING

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 12 mm
 - Outer Diameter: 17.5 mm
 - Maximum Working Pressure: 10 bar
 - Material: PVC
 - Suitable Applications: Water
 - Minimum Operating Temperature: -15 °C
 - Maximum Operating Temperature: +60 °C
 - Length: 50 m



3520563 12 mm

RS PRO TRANSPARENT FLEXIBLE TUBING, 6.3MM ID, PET, PVC, 10 BAR

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 6.3 mm
 - Outer Diameter: 10.5 mm
 - Maximum Working Pressure: 10 bar
 - Material: PET, PVC
 - Suitable Applications: Compressed Air, Food, Water
 - Minimum Operating Temperature: -15 °C
 - Maximum Operating Temperature: +60 °C
 - Length: 25 m



3680176 6.3 mm

RS PRO TRANSPARENT FLEXIBLE TUBING, 8MM ID, PET, PVC, 10 BAR

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 8 mm
 - Outer Diameter: 12 mm
 - Maximum Working Pressure: 10 bar
 - Material: PET, PVC
 - Suitable Applications: Compressed Air, Food, Water
 - Minimum Operating Temperature: -15 °C
 - Maximum Operating Temperature: +60 °C
 - Length: 25 m



3680182 8 mm

RS PRO TRANSPARENT FLEXIBLE TUBING, 10MM ID, PET, PVC, 10 BAR

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 10 mm
 - Outer Diameter: 14 mm
 - Maximum Working Pressure: 10 bar
 - Material: PET, PVC
 - Suitable Applications: Compressed Air, Food, Water
 - Minimum Operating Temperature: -15 °C
 - Maximum Operating Temperature: +60 °C
 - Length: 25 m



3680205 10 mm

RS PRO TRANSPARENT FLEXIBLE TUBING, 12.5MM ID, PET, PVC, 10 BAR

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 12.5 mm
 - Outer Diameter: 17.5 mm
 - Maximum Working Pressure: 10 bar
 - Material: PET, PVC
 - Suitable Applications: Compressed Air, Food, Water
 - Minimum Operating Temperature: -15 °C
 - Maximum Operating Temperature: +60 °C
 - Length: 25 m



3680211 12.5 mm

RS PRO TRANSPARENT FLEXIBLE TUBING, 16MM ID, PET, PVC, 10 BAR

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 16 mm
 - Outer Diameter: 22 mm
 - Maximum Working Pressure: 10 bar
 - Material: PET, PVC
 - Suitable Applications: Compressed Air, Food, Water
 - Minimum Operating Temperature: -15 °C
 - Maximum Operating Temperature: +60 °C
 - Length: 25 m



3680227 16 mm

RS PRO TRANSPARENT FLEXIBLE TUBING, 19MM ID, PET, PVC, 10 BAR

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 19 mm
 - Outer Diameter: 24 mm
 - Maximum Working Pressure: 10 bar
 - Material: PET, PVC
 - Suitable Applications: Compressed Air, Food, Water
 - Minimum Operating Temperature: -15 °C
 - Maximum Operating Temperature: +60 °C
 - Length: 25 m



3680233 19 mm

RS PRO TRANSPARENT FLEXIBLE TUBING, 25MM ID, PET, PVC, 10 BAR

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 25 mm
 - Outer Diameter: 31 mm
 - Maximum Working Pressure: 10 bar
 - Material: PET, PVC
 - Suitable Applications: Compressed Air, Food, Water
 - Minimum Operating Temperature: -15 °C
 - Maximum Operating Temperature: +60 °C
 - Length: 25 m



3680249 25 mm

RS PRO BLACK, YELLOW HOSE, 25MM ID, PVC, 20 BARS MAX WORKING

- ขนาดบรรจุภัณฑ์: 30 x MTR
- Inner Diameter: 25 mm
 - Maximum Working Pressure: 20 bars
 - Material: PVC
 - Length: 30 m
 - Colour: Black, Yellow



3809901 25 mm

RS PRO TRANSPARENT FLEXIBLE TUBING, 25MM ID, PVC, 4 BAR MAX

- ขนาดบรรจุภัณฑ์: 25 x MTR
- Inner Diameter: 25 mm
 - Outer Diameter: 31 mm
 - Maximum Working Pressure: 4 bar
 - Material: PVC
 - Suitable Applications: Alcohol, Grease, Oil, Petrol, Solvent
 - Minimum Operating Temperature: -15 °C
 - Maximum Operating Temperature: +60 °C
 - Length: 25 m



3815417 25 mm

RS PRO BLACK HOSE, 8MM ID, 30M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 8 mm
 - Length: 30 m
 - Colour: Black



3991151 8 mm

RS PRO BLACK HOSE, 10MM ID, 30M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 10 mm
 - Length: 30 m
 - Colour: Black



3991167 10 mm

RS PRO BLACK HOSE, 13MM ID, 30M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 13 mm
 - Length: 30 m
 - Colour: Black



3991173 13 mm

RS PRO TRANSPARENT HOSE PIPE, 4.8MM ID, SANTOPRENE, 3M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 4.8 mm
 - Outer Diameter: 8 mm
 - Material: Santoprene
 - Suitable Applications: Peristaltic pumps
 - Length: 3 m
 - Colour: Transparent
 - Peristaltic Pump Compatible: Yes
 - Food Grade: Yes



6678422 4.8 mm

RS PRO NATURAL HOSE PIPE, 6.4MM ID, SANTOPRENE, 3M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 6.4 mm
 - Outer Diameter: 9.6 mm
 - Material: Santoprene
 - Suitable Applications: Peristaltic pumps
 - Length: 3 m
 - Colour: Natural
 - Peristaltic Pump Compatible: Yes
 - Food Grade: Yes



6678426 6.4 mm

RS PRO TRANSPARENT HOSE PIPE, 3.2MM ID, SANTOPRENE, 3M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 3.2 mm
 - Outer Diameter: 6.4 mm
 - Material: Santoprene
 - Suitable Applications: Peristaltic pumps
 - Length: 3 m
 - Colour: Transparent
 - Food Grade: Yes
 - Peristaltic Pump Compatible: Yes



6678429 3.2 mm

SILICONE TUBING, 0.8MM BORE 3M L

- ขนาดบรรจุภัณฑ์: 1 x EA
- Material: Silicone
 - Bore Size: 0.8 mm
 - Length: 3 m
 - Food Grade: Yes
 - Internal Diameter: 0.8 mm
 - External Diameter: 4 mm
 - Colour: Transparent
 - Peristaltic Pump Compatible: Yes



6678432 Silicone

RS PRO CREAM HOSE PIPE, 8MM ID, SANTOPRENE, 3M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 8 mm
 - Outer Diameter: 11.2 mm
 - Material: Santoprene
 - Suitable Applications: Peristaltic pumps
 - Length: 3 m
 - Colour: Cream
 - Peristaltic Pump Compatible: Yes
 - Food Grade: Yes



6678435 8 mm

RS PRO TRANSPARENT HOSE PIPE, 0.5MM ID, SILICONE, 3M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 0.5 mm
 - Outer Diameter: 3.7 mm
 - Material: Silicone
 - Suitable Applications: Peristaltic pumps
 - Length: 3 m
 - Colour: Transparent
 - Peristaltic Pump Compatible: Yes
 - Food Grade: Yes



6678438 0.5 mm

RS PRO TRANSPARENT HOSE PIPE, 1.6MM ID, SILICONE, 3M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 1.6 mm
 - Outer Diameter: 4.8 mm
 - Material: Silicone
 - Suitable Applications: Peristaltic pumps
 - Length: 3 m
 - Colour: Transparent
 - Peristaltic Pump Compatible: Yes
 - Food Grade: Yes



6678441 1.6 mm

RS PRO TRANSPARENT HOSE PIPE, 3.2MM ID, SILICONE, 3M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 3.2 mm
 - Outer Diameter: 6.4 mm
 - Material: Silicone
 - Suitable Applications: Peristaltic pumps
 - Length: 3 m
 - Colour: Transparent
 - Peristaltic Pump Compatible: Yes
 - Food Grade: Yes



6678444 3.2 mm

RS PRO TRANSPARENT HOSE PIPE, 4.8MM ID, SILICONE, 3M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 4.8 mm
 - Outer Diameter: 8 mm
 - Material: Silicone
 - Suitable Applications: Peristaltic pumps
 - Length: 3 m
 - Colour: Transparent
 - Peristaltic Pump Compatible: Yes
 - Food Grade: Yes



6678448 4.8 mm

RS PRO TRANSPARENT HOSE PIPE, 8MM ID, SILICONE, 3M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 8 mm
 - Outer Diameter: 11.2 mm
 - Material: Silicone
 - Suitable Applications: Peristaltic pumps
 - Length: 3 m
 - Colour: Transparent
 - Peristaltic Pump Compatible: Yes
 - Food Grade: Yes



6678450 8 mm

RS PRO TRANSPARENT HOSE PIPE, 6.4MM ID, SILICONE, 3M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 6.4 mm
 - Outer Diameter: 9.6 mm
 - Material: Silicone
 - Suitable Applications: Peristaltic pumps
 - Length: 3 m
 - Colour: Transparent
 - Peristaltic Pump Compatible: Yes
 - Food Grade: Yes



6678457 6.4 mm

RS PRO YELLOW HOSE, 6MM ID, 30M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 6 mm
 - Length: 30 m
 - Colour: Yellow



9120958 6 mm

RS PRO YELLOW HOSE, 10MM ID, 30M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 10 mm
 - Length: 30 m
 - Colour: Yellow



9120960 10 mm

RS PRO YELLOW HOSE, 13MM ID, 30M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 13 mm
 - Length: 30 m
 - Colour: Yellow



9120964 13 mm

RS PRO CLEAR FLEXIBLE TUBING, 25MM ID, PVC, 25M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 25 mm
 - Outer Diameter: 31 mm
 - Material: PVC
 - Suitable Applications: Alcohol, Grease, Oil, Petrol, Solvent
 - Minimum Operating Temperature: -15 °C
 - Maximum Operating Temperature: +60 °C
 - Length: 25 m
 - Colour: Clear



9145503 25 mm

RS PRO CLEAR FLEXIBLE TUBING, 10MM ID, PVC, 25M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 10 mm
 - Outer Diameter: 13 mm
 - Material: PVC
 - Suitable Applications: Alcohol, Grease, Oil, Petrol, Solvent
 - Minimum Operating Temperature: -15 °C
 - Maximum Operating Temperature: +60 °C
 - Length: 25 m
 - Colour: Clear



9145506 10 mm

RS PRO CLEAR FLEXIBLE TUBING, 12MM ID, PVC, 25M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 12 mm
 - Outer Diameter: 15 mm
 - Material: PVC
 - Suitable Applications: Alcohol, Grease, Oil, Petrol, Solvent
 - Minimum Operating Temperature: -15 °C
 - Maximum Operating Temperature: +60 °C
 - Length: 25 m
 - Colour: Clear



9145509 12 mm

RS PRO CLEAR FLEXIBLE TUBING, 3MM ID, PVC, 25M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 3 mm
 - Outer Diameter: 6 mm
 - Material: PVC
 - Suitable Applications: Alcohol, Grease, Oil, Petrol, Solvent
 - Minimum Operating Temperature: -15 °C
 - Maximum Operating Temperature: +60 °C
 - Length: 25 m
 - Colour: Clear



9145515 3 mm

RS PRO CLEAR FLEXIBLE TUBING, 5MM ID, PVC, 25M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 5 mm
 - Outer Diameter: 8 mm
 - Material: PVC
 - Suitable Applications: Alcohol, Grease, Oil, Petrol, Solvent
 - Minimum Operating Temperature: -15 °C
 - Maximum Operating Temperature: +60 °C
 - Length: 25 m
 - Colour: Clear



9145519 5 mm

RS PRO CLEAR FLEXIBLE TUBING, 8MM ID, PVC, 25M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 8 mm
 - Outer Diameter: 11 mm
 - Material: PVC
 - Suitable Applications: Alcohol, Grease, Oil, Petrol, Solvent
 - Minimum Operating Temperature: -15 °C
 - Maximum Operating Temperature: +60 °C
 - Length: 25 m
 - Colour: Clear



9145521 8 mm

RS PRO BLACK HOSE, 10MM ID

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 10 mm
 - Colour: Black



9145525 10 mm

RS PRO CLEAR FLEXIBLE TUBING, 6MM ID, PVC, 25M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 6 mm
 - Outer Diameter: 9 mm
 - Material: PVC
 - Suitable Applications: Alcohol, Grease, Oil, Petrol, Solvent
 - Minimum Operating Temperature: -15 °C
 - Maximum Operating Temperature: +60 °C
 - Length: 25 m
 - Colour: Clear



9145528 6 mm

RS PRO BLACK HOSE, 12.5MM ID

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 12.5 mm
 - Colour: Black



9145534 12.5 mm

RS PRO BLACK HOSE, 6MM ID

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 6 mm
 - Colour: Black



9145540 6 mm

RS PRO BLACK HOSE, 8MM ID

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 8 mm
 - Colour: Black



9145543 8 mm

RS PRO BLACK HOSE PIPE, 10MM ID, EPDM, 20M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 10 mm
 - Material: EPDM
 - Suitable Applications: Automotive, Heater Hose, Hot Water
 - Length: 20 m
 - Colour: Black
 - Reinforced: Yes



9145547 10 mm

RS PRO BLACK HOSE PIPE, 25MM ID, EPDM, 20M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 25 mm
 - Material: EPDM
 - Suitable Applications: Automotive, Heater Hose, Hot Water
 - Length: 20 m
 - Colour: Black
 - Reinforced: Yes



9145553 25 mm

RS PRO BLACK HOSE PIPE, 13MM ID, EPDM, 20M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 13 mm
 - Material: EPDM
 - Suitable Applications: Automotive, Heater Hose, Hot Water
 - Length: 20 m
 - Colour: Black
 - Reinforced: Yes



9145556 13 mm

RS PRO GREEN HOSE PIPE, 32MM ID, PVC, 10M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 32 mm
 - Outer Diameter: 39.6 mm
 - Material: PVC
 - Suitable Applications: Chemical, Light Duty Solid, Liquid, Slurries
 - Length: 10 m
 - Colour: Green
 - Reinforced: Yes
 - Bend Radius: 127 mm



9174933 32 mm

RS PRO GREEN HOSE PIPE, 25MM ID, PVC, 10M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 25 mm
 - Outer Diameter: 32 mm
 - Material: PVC
 - Suitable Applications: Chemical, Light Duty Solid, Liquid, Slurries
 - Length: 10 m
 - Colour: Green
 - Reinforced: Yes
 - Bend Radius: 102 mm



9174939 25 mm

RS PRO GREEN HOSE PIPE, 51MM ID, PVC, 10M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 51 mm
 - Outer Diameter: 60.2 mm
 - Material: PVC
 - Suitable Applications: Chemical, Light Duty Solid, Liquid, Slurries
 - Length: 10 m
 - Colour: Green
 - Reinforced: Yes
 - Bend Radius: 204 mm



9174945 51 mm

RS PRO GREEN HOSE PIPE, 32MM ID, PVC, 30M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 32 mm
 - Outer Diameter: 39.6 mm
 - Material: PVC
 - Suitable Applications: Chemical, Light Duty Solid, Liquid, Slurries
 - Length: 30 m
 - Colour: Green
 - Reinforced: Yes
 - Bend Radius: 127 mm



9174951 32 mm

RS PRO GREEN HOSE PIPE, 25MM ID, PVC, 30M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 25 mm
 - Outer Diameter: 32 mm
 - Material: PVC
 - Suitable Applications: Chemical, Light Duty Solid, Liquid, Slurries
 - Length: 30 m
 - Colour: Green
 - Reinforced: Yes
 - Bend Radius: 102 mm



9174958 25 mm

RS PRO GREEN HOSE PIPE, 32MM ID, PVC, 5M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 32 mm
 - Outer Diameter: 39.6 mm
 - Material: PVC
 - Suitable Applications: Chemical, Light Duty Solid, Liquid, Slurries
 - Length: 5 m
 - Colour: Green
 - Reinforced: Yes
 - Bend Radius: 127 mm



9174961 32 mm

RS PRO GREEN HOSE PIPE, 25MM ID, PVC, 5M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 25 mm
 - Outer Diameter: 32 mm
 - Material: PVC
 - Suitable Applications: Chemical, Light Duty Solid, Liquid, Slurries
 - Length: 5 m
 - Colour: Green
 - Reinforced: Yes
 - Bend Radius: 102 mm



9174967 25 mm

RS PRO GREEN HOSE PIPE, 51MM ID, PVC, 5M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 51 mm
 - Outer Diameter: 60.2 mm
 - Material: PVC
 - Suitable Applications: Chemical, Light Duty Solid, Liquid, Slurries
 - Length: 5 m
 - Colour: Green
 - Reinforced: Yes
 - Bend Radius: 204 mm



9174973 51 mm

RS PRO GREEN HOSE PIPE, 19MM ID, PVC, 10M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 19 mm
 - Material: PVC
 - Suitable Applications: Chemical, Light Duty Solid, Liquid, Slurries
 - Length: 10 m
 - Colour: Green
 - Reinforced: Yes



9174977 19 mm

RS PRO GREEN HOSE PIPE, 25MM ID, PVC, 10M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 25 mm
 - Outer Diameter: 32 mm
 - Material: PVC
 - Suitable Applications: Chemical, Light Duty Solid, Liquid, Slurries
 - Length: 10 m
 - Colour: Green
 - Reinforced: Yes
 - Bend Radius: 114 mm



9174986 25 mm

RS PRO GREEN HOSE PIPE, 32MM ID, PVC, 10M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 32 mm
 - Outer Diameter: 39.2 mm
 - Material: PVC
 - Suitable Applications: Chemical, Light Duty Solid, Liquid, Slurries
 - Length: 10 m
 - Colour: Green
 - Reinforced: Yes
 - Bend Radius: 143 mm



9174989 32 mm

RS PRO GREEN HOSE PIPE, 45MM ID, PVC, 10M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 45 mm
 - Material: PVC
 - Suitable Applications: Chemical, Light Duty Solid, Liquid, Slurries
 - Length: 10 m
 - Colour: Green
 - Reinforced: Yes



9174992 45 mm

RS PRO GREEN HOSE PIPE, 51MM ID, PVC, 10M


- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 51 mm
 - Outer Diameter: 59.8 mm
 - Material: PVC
 - Suitable Applications: Chemical, Light Duty Solid, Liquid, Slurries
 - Length: 10 m
 - Colour: Green
 - Reinforced: Yes
 - Bend Radius: 284 mm



9174995 51 mm

RS PRO GREEN HOSE PIPE, 25MM ID, PVC, 30M


- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 25 mm
 - Outer Diameter: 32 mm
 - Material: PVC
 - Suitable Applications: Chemical, Light Duty Solid, Liquid, Slurries
 - Length: 30 m
 - Colour: Green
 - Reinforced: Yes
 - Bend Radius: 114 mm



9174999 25 mm

RS PRO GREEN HOSE PIPE, 32MM ID, PVC, 30M


- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 32 mm
 - Outer Diameter: 39.2 mm
 - Material: PVC
 - Suitable Applications: Chemical, Light Duty Solid, Liquid, Slurries
 - Length: 30 m
 - Colour: Green
 - Reinforced: Yes
 - Bend Radius: 143 mm



9175002 32 mm

RS PRO GREEN HOSE PIPE, 25MM ID, PVC, 5M


- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 25 mm
 - Outer Diameter: 32 mm
 - Material: PVC
 - Suitable Applications: Chemical, Light Duty Solid, Liquid, Slurries
 - Length: 5 m
 - Colour: Green
 - Reinforced: Yes
 - Bend Radius: 114 mm



9175011 25 mm

RS PRO GREEN HOSE PIPE, 32MM ID, PVC, 5M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 32 mm
 - Outer Diameter: 39.2 mm
 - Material: PVC
 - Suitable Applications: Chemical, Light Duty Solid, Liquid, Slurries
 - Length: 5 m
 - Colour: Green
 - Reinforced: Yes
 - Bend Radius: 143 mm



9175015 32 mm

RS PRO GREEN HOSE PIPE, 19MM ID, PVC, 5M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 19 mm
 - Material: PVC
 - Suitable Applications: Chemical, Light Duty Solid, Liquid, Slurries
 - Length: 5 m
 - Colour: Green
 - Reinforced: Yes



9175018 19 mm

RS PRO GREEN HOSE PIPE, 51MM ID, PVC, 5M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 51 mm
 - Outer Diameter: 59.8 mm
 - Material: PVC
 - Suitable Applications: Chemical, Light Duty Solid, Liquid, Slurries
 - Length: 5 m
 - Colour: Green
 - Reinforced: Yes
 - Bend Radius: 284 mm



9175021 51 mm

RS PRO GREEN HOSE PIPE, 38MM ID, PVC, 5M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 38 mm
 - Outer Diameter: 45.4 mm
 - Material: PVC
 - Suitable Applications: Chemical, Light Duty Solid, Liquid, Slurries
 - Length: 5 m
 - Colour: Green
 - Reinforced: Yes
 - Bend Radius: 171 mm



9175024 38 mm

RS PRO GREEN HOSE PIPE, 45MM ID, PVC, 5M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 45 mm
 - Material: PVC
 - Suitable Applications: Chemical, Light Duty Solid, Liquid, Slurries
 - Length: 5 m
 - Colour: Green
 - Reinforced: Yes



9175027 45 mm

RS PRO YELLOW HOSE PIPE, 19MM ID, PVC, 10M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 19 mm
 - Material: PVC
 - Suitable Applications: Agriculture, Horticulture, Marine, Slurries
 - Length: 10 m
 - Colour: Yellow
 - Reinforced: Yes



9175033 19 mm

RS PRO YELLOW HOSE PIPE, 25.4MM ID, PVC, 10M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 25.4 mm
 - Outer Diameter: 32 mm
 - Material: PVC
 - Suitable Applications: Agriculture, Horticulture, Marine, Slurries
 - Length: 10 m
 - Colour: Yellow
 - Reinforced: Yes
 - Bend Radius: 114 mm



9175037 25.4 mm

RS PRO YELLOW HOSE PIPE, 51.6MM ID, PVC, 10M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 51.6 mm
 - Outer Diameter: 59.8 mm
 - Material: PVC
 - Suitable Applications: Agriculture, Horticulture, Marine, Slurries
 - Length: 10 m
 - Colour: Yellow
 - Reinforced: Yes
 - Bend Radius: 230 mm



9175052 51.6 mm

RS PRO GREEN FLEXIBLE TUBING, 6MM ID, PUR, 20 BAR MAX WORKING

- ขนาดบรรจุภัณฑ์: 1 x EA
- Inner Diameter: 6 mm
 - Outer Diameter: 10 mm
 - Maximum Working Pressure: 20 bar
 - Material: PUR
 - Suitable Applications: Air, Water
 - Minimum Operating Temperature: -15 °C
 - Maximum Operating Temperature: +60 °C
 - Length: 100 m



9175055 6 mm

**RS PRO GREEN FLEXIBLE TUBING,
13MM ID, PUR, 20 BAR MAX**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 13 mm
 - Outer Diameter: 19 mm
 - Maximum Working Pressure: 20 bar
 - Material: PUR
 - Suitable Applications: Air, Water
 - Minimum Operating Temperature: -15 °C
 - Maximum Operating Temperature: +60 °C
 - Length: 30 m



9175059 13 mm

**RS PRO GREEN FLEXIBLE TUBING,
8MM ID, PUR, 20 BAR MAX WORKING**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 8 mm
 - Outer Diameter: 12 mm
 - Maximum Working Pressure: 20 bar
 - Material: PUR
 - Suitable Applications: Air, Water
 - Minimum Operating Temperature: -15 °C
 - Maximum Operating Temperature: +60 °C
 - Length: 60 m



9175061 8 mm

**RS PRO GREEN HOSE PIPE, 38MM ID,
PVC, 10M**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 38 mm
 - Outer Diameter: 45.8 mm
 - Material: PVC
 - Suitable Applications: Agriculture, Foundry, Industrial
 - Length: 10 m
 - Colour: Green
 - Reinforced: Yes
 - Bend Radius: 86 mm



9175065 38 mm

**RS PRO GREEN FLEXIBLE TUBING,
10MM ID, PUR, 20 BAR MAX**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 10 mm
 - Outer Diameter: 15 mm
 - Maximum Working Pressure: 20 bar
 - Material: PUR
 - Suitable Applications: Air, Water
 - Minimum Operating Temperature: -15 °C
 - Maximum Operating Temperature: +60 °C
 - Length: 50 m



9175068 10 mm

**RS PRO GREEN HOSE PIPE, 102MM ID,
PVC, 10M**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 102 mm
 - Outer Diameter: 113 mm
 - Material: PVC
 - Suitable Applications: Agriculture, Foundry, Industrial
 - Length: 10 m
 - Colour: Green
 - Reinforced: Yes
 - Bend Radius: 284 mm



9175074 102 mm

**RS PRO GREEN HOSE PIPE, 51MM ID,
PVC, 10M**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 51 mm
 - Outer Diameter: 60.2 mm
 - Material: PVC
 - Suitable Applications: Agriculture, Foundry, Industrial
 - Length: 10 m
 - Colour: Green
 - Reinforced: Yes
 - Bend Radius: 114 mm



9175077 51 mm

**RS PRO BLUE HOSE PIPE, 38MM ID,
PVC, 10M**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 38 mm
 - Outer Diameter: 47 mm
 - Material: PVC
 - Suitable Applications: Fuel
 - Length: 10 m
 - Colour: Blue
 - Reinforced: Yes
 - Bend Radius: 171 mm



9175083 38 mm

**RS PRO BLUE HOSE PIPE, 25MM ID,
PVC, 10M**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 25 mm
 - Outer Diameter: 33.8 mm
 - Material: PVC
 - Suitable Applications: Fuel
 - Length: 10 m
 - Colour: Blue
 - Reinforced: Yes
 - Bend Radius: 113 mm



9175087 25 mm

**RS PRO BLUE HOSE PIPE, 51MM ID,
PVC, 10M**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 51 mm
 - Outer Diameter: 60.9 mm
 - Material: PVC
 - Suitable Applications: Fuel
 - Length: 10 m
 - Colour: Blue
 - Reinforced: Yes
 - Bend Radius: 230 mm



9175096 51 mm

**RS PRO BLUE HOSE PIPE, 51MM ID,
PVC, 5M**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 51 mm
 - Outer Diameter: 60.9 mm
 - Material: PVC
 - Suitable Applications: Fuel
 - Length: 5 m
 - Colour: Blue
 - Reinforced: Yes
 - Bend Radius: 230 mm



9175100 51 mm

**RS PRO BLUE HOSE PIPE, 25MM ID,
PVC, 5M**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 25 mm
 - Outer Diameter: 33.8 mm
 - Material: PVC
 - Suitable Applications: Fuel
 - Length: 5 m
 - Colour: Blue
 - Reinforced: Yes
 - Bend Radius: 113 mm



9175106 25 mm

**RS PRO YELLOW FLEXIBLE TUBING,
19MM ID, PVC, 39 BAR MAX**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 19 mm
 - Outer Diameter: 25.5 mm
 - Maximum Working Pressure: 39 bar
 - Material: PVC
 - Suitable Applications: Water
 - Minimum Operating Temperature: -15 °C
 - Maximum Operating Temperature: +65 °C
 - Length: 25 m



9175112 19 mm

**RS PRO YELLOW FLEXIBLE TUBING,
25MM ID, PVC, 24 BAR MAX**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 25 mm
 - Outer Diameter: 32.5 mm
 - Maximum Working Pressure: 24 bar
 - Material: PVC
 - Suitable Applications: Water
 - Minimum Operating Temperature: -15 °C
 - Maximum Operating Temperature: +65 °C
 - Length: 25 m



9175116 25 mm

**RS PRO YELLOW FLEXIBLE TUBING,
12.5MM ID, PVC, 16 BAR MAX**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 12.5 mm
 - Outer Diameter: 17.5 mm
 - Maximum Working Pressure: 16 bar
 - Material: PVC
 - Suitable Applications: Water
 - Minimum Operating Temperature: -15 °C
 - Maximum Operating Temperature: +65 °C
 - Length: 25 m



9175119 12.5 mm

**RS PRO YELLOW FLEXIBLE TUBING,
12.5MM ID, PVC, 16 BAR MAX**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 12.5 mm
 - Outer Diameter: 17.5 mm
 - Maximum Working Pressure: 16 bar
 - Material: PVC
 - Suitable Applications: Water
 - Minimum Operating Temperature: -15 °C
 - Maximum Operating Temperature: +65 °C
 - Length: 50 m



9175125 12.5 mm

**RS PRO YELLOW FLEXIBLE TUBING,
19MM ID, PVC, 39 BAR MAX**

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inner Diameter: 19 mm
 - Outer Diameter: 25.5 mm
 - Maximum Working Pressure: 39 bar
 - Material: PVC
 - Suitable Applications: Water
 - Minimum Operating Temperature: -15 °C
 - Maximum Operating Temperature: +65 °C
 - Length: 50 m



9175128 19 mm

RS PRO 50M LONG HOSE PROTECTOR, 1 1/4 → 20MM HOSE SIZE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Size Compatibility: 1 1/4 → 20 mm
 - Length: 50 m
 - Outer Diameter: 20 mm
 - Maximum Compatible Hose Size: 20 mm
 - Minimum Compatible Hose Size: 1 1/4 mm



1860556 1 1/4 → 20 mm

RS PRO 50M LONG HOSE PROTECTOR, 20 → 25MM HOSE SIZE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Size Compatibility: 20 → 25 mm
 - Length: 50 m
 - Outer Diameter: 25 mm
 - Maximum Compatible Hose Size: 25 mm
 - Minimum Compatible Hose Size: 20 mm



1860557 20 → 25 mm

RS PRO 50M LONG HOSE PROTECTOR, 25 → 32MM HOSE SIZE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Size Compatibility: 25 → 32 mm
 - Length: 50 m
 - Outer Diameter: 32 mm
 - Maximum Compatible Hose Size: 32 mm
 - Minimum Compatible Hose Size: 25 mm



1860558 25 → 32 mm

RS PRO 50M LONG HOSE PROTECTOR, 3/2 → 40MM HOSE SIZE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Size Compatibility: 3/2 → 40 mm
 - Length: 50 m
 - Outer Diameter: 40 mm
 - Maximum Compatible Hose Size: 40 mm
 - Minimum Compatible Hose Size: 32 mm



1860559 3/2 → 40 mm

RS PRO 20M LONG HOSE PROTECTOR, 3/8 → 50MM HOSE SIZE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Size Compatibility: 3/8 → 50 mm
 - Length: 20 m
 - Outer Diameter: 50 mm
 - Maximum Compatible Hose Size: 50 mm
 - Minimum Compatible Hose Size: 38 mm



1860560 3/8 → 50 mm

RS PRO 20M LONG HOSE PROTECTOR, 50 → 63MM HOSE SIZE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Size Compatibility: 50 → 63 mm
 - Length: 20 m
 - Outer Diameter: 63 mm
 - Maximum Compatible Hose Size: 63 mm
 - Minimum Compatible Hose Size: 50 mm



1860561 50 → 63 mm

RS PRO 20M LONG HOSE PROTECTOR, 60 → 75MM HOSE SIZE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Size Compatibility: 60 → 75 mm
 - Length: 20 m
 - Outer Diameter: 75 mm
 - Maximum Compatible Hose Size: 75 mm
 - Minimum Compatible Hose Size: 60 mm



1860562 60 → 75 mm

RS PRO 50M LONG HOSE PROTECTOR, 11.5 → 16MM HOSE SIZE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Size Compatibility: 11.5 → 16 mm
 - Length: 50 m
 - Outer Diameter: 16 mm
 - Maximum Compatible Hose Size: 16 mm
 - Minimum Compatible Hose Size: 11.5 mm



1860564 11.5 → 16 mm

RS PRO 50M LONG HOSE PROTECTOR, 20 → 25MM HOSE SIZE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Size Compatibility: 20 → 25 mm
 - Length: 50 m
 - Outer Diameter: 25 mm
 - Maximum Compatible Hose Size: 25 mm
 - Minimum Compatible Hose Size: 20 mm



1860567 20 → 25 mm

RS PRO 50M LONG HOSE PROTECTOR, 25 → 32MM HOSE SIZE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Size Compatibility: 25 → 32 mm
 - Length: 50 m
 - Outer Diameter: 32 mm
 - Maximum Compatible Hose Size: 32 mm
 - Minimum Compatible Hose Size: 25 mm



1860568 25 → 32 mm

RS PRO 20M LONG HOSE PROTECTOR, 60 → 75MM HOSE SIZE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Size Compatibility: 60 → 75 mm
 - Length: 20 m
 - Outer Diameter: 75 mm
 - Maximum Compatible Hose Size: 75 mm
 - Minimum Compatible Hose Size: 60 mm



1860573 60 → 75 mm

RS PRO 50M LONG HOSE PROTECTOR, 1 1/4 → 20MM HOSE SIZE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Size Compatibility: 1 1/4 → 20 mm
 - Length: 50 m
 - Outer Diameter: 20 mm
 - Maximum Compatible Hose Size: 20 mm
 - Minimum Compatible Hose Size: 1 1/4 mm



1860565 1 1/4 → 20 mm

RS PRO 50M LONG HOSE PROTECTOR, 11.5 → 16MM HOSE SIZE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Size Compatibility: 11.5 → 16 mm
 - Length: 50 m
 - Outer Diameter: 12 mm
 - Maximum Compatible Hose Size: 16 mm
 - Minimum Compatible Hose Size: 11.5 mm



1860574 11.5 → 16 mm

RS PRO 50M LONG HOSE PROTECTOR, 3/2 → 40MM HOSE SIZE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Size Compatibility: 3/2 → 40 mm
 - Length: 50 m
 - Outer Diameter: 40 mm
 - Maximum Compatible Hose Size: 40 mm
 - Minimum Compatible Hose Size: 32 mm



1860579 3/2 → 40 mm

RS PRO 20M LONG HOSE PROTECTOR, 3/8 → 50MM HOSE SIZE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Size Compatibility: 3/8 → 50 mm
 - Length: 20 m
 - Outer Diameter: 50 mm
 - Maximum Compatible Hose Size: 50 mm
 - Minimum Compatible Hose Size: 38 mm



1860580 3/8 → 50 mm

RS PRO 20M LONG HOSE PROTECTOR, 50 → 63MM HOSE SIZE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Size Compatibility: 50 → 63 mm
 - Length: 20 m
 - Outer Diameter: 63 mm
 - Maximum Compatible Hose Size: 63 mm
 - Minimum Compatible Hose Size: 50 mm



1860581 50 → 63 mm

RS PRO 100M LONG HOSE PROTECTOR, 4 → 8MM HOSE SIZE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Size Compatibility: 4 → 8 mm
 - Length: 100 m
 - Inner Diameter: 6 mm
 - Outer Diameter: 8 mm
 - Maximum Compatible Hose Size: 8 mm
 - Minimum Compatible Hose Size: 4 mm



1860583 4 → 8 mm

RS PRO 25M LONG HOSE PROTECTOR, 29 → 34MM HOSE SIZE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Size Compatibility: 29 → 34 mm
 - Length: 25 m
 - Inner Diameter: 30 mm
 - Outer Diameter: 34 mm
 - Maximum Compatible Hose Size: 34 mm
 - Minimum Compatible Hose Size: 29 mm



1860590 29 → 34 mm

WIRE, GALVANISED, WHIPCHECK B, 1/4IN, MULTISTRAND, FLEXIBLE, 2330

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Size Compatibility: 1-1/2 in → 3 in
 - Material: Galvanised Steel
 - Maximum Compatible Hose Size: 3 in
 - Minimum Compatible Hose Size: 1-1/2 in



3626633 1-1/2 in → 3 in

WIRE, GALVANISED, WHIPCHECK A, 1/8IN, MULTISTRAND, FLEXIBLE, 580K

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Size Compatibility: 1/2 in → 1-1/4 in
 - Material: Galvanised Steel
 - Maximum Compatible Hose Size: 1-1/4 in
 - Minimum Compatible Hose Size: 1/2 in



3627709 1/2 in → 1-1/4 in

SPRING DRIVEN HOSE REEL, 8MM ID, 9M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inlet Connection: 1/4 in BSPT
 - Hose Inner Diameter: 8 mm
 - Hose Included: Yes
 - Reel Diameter: 277 mm
 - Maximum Working Pressure: 8.3 bar
 - Inlet Connection Size: 1/2 in
 - Inlet Thread Standard: BSPT
 - Mounting: Wall Mounting



9119443 1/4 in BSPT

RS PRO 1/4 IN BSPT 10MM 424MM HOSE REEL 13.8 BAR 15M LENGTH,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inlet Connection: 1/4 in BSPT
 - Hose Inner Diameter: 10 mm
 - Hose Included: Yes
 - Reel Diameter: 424 mm
 - Hose Length: 15 m
 - Maximum Working Pressure: 13.8 bar
 - Inlet Connection Size: 1/2 in
 - Inlet Thread Standard: BSPT



9119447 1/4 in BSPT

RS PRO 12MM 494MM HOSE REEL 10 BAR 20M LENGTH, WALL MOUNTING

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Inner Diameter: 12 mm
 - Hose Included: Yes
 - Reel Diameter: 494 mm
 - Hose Length: 20 m
 - Maximum Working Pressure: 10 bar
 - Mounting: Wall Mounting
 - Retraction Operation: Automatic



9119456 12 mm

RS PRO 12MM 517MM HOSE REEL 10 BAR 30M LENGTH, WALL MOUNTING

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Inner Diameter: 12 mm
 - Hose Included: Yes
 - Reel Diameter: 517 mm
 - Hose Length: 30 m
 - Maximum Working Pressure: 10 bar
 - Mounting: Wall Mounting
 - Retraction Operation: Automatic



9119459 12 mm

262MM SYNTHETIC RUBBER HYDRAULIC HOSE ASSEMBLY,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Overall Length: 262 mm
 - Inside Diameter: 1/4 in
 - Connector A: Straight G 1/4 Female
 - Connector B: Straight G 1/4 Female
 - Inner Hose Material: Synthetic Rubber
 - Reinforcing Material: Steel
 - Cover Material: Synthetic Rubber
 - Maximum Operating Pressure: 400 bar



1101987 262 mm

362MM SYNTHETIC RUBBER HYDRAULIC HOSE ASSEMBLY,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Overall Length: 362 mm
 - Inside Diameter: 1/4 in
 - Connector A: Straight G 1/4 Female
 - Connector B: Straight G 1/4 Female
 - Inner Hose Material: Synthetic Rubber
 - Reinforcing Material: Steel
 - Cover Material: Synthetic Rubber
 - Maximum Operating Pressure: 400 bar



1101988 362 mm

562MM SYNTHETIC RUBBER HYDRAULIC HOSE ASSEMBLY,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Overall Length: 562 mm
 - Inside Diameter: 1/4 in
 - Connector A: Straight G 1/4 Female
 - Connector B: Straight G 1/4 Female
 - Inner Hose Material: Synthetic Rubber
 - Reinforcing Material: Steel
 - Cover Material: Synthetic Rubber
 - Maximum Operating Pressure: 400 bar



1101990 562 mm

762MM SYNTHETIC RUBBER HYDRAULIC HOSE ASSEMBLY,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Overall Length: 762 mm
 - Inside Diameter: 1/4 in
 - Connector A: Straight G 1/4 Female
 - Connector B: Straight G 1/4 Female
 - Inner Hose Material: Synthetic Rubber
 - Reinforcing Material: Steel
 - Cover Material: Synthetic Rubber
 - Maximum Operating Pressure: 400 bar



1101992 762 mm

962MM SYNTHETIC RUBBER HYDRAULIC HOSE ASSEMBLY,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Overall Length: 962 mm
 - Inside Diameter: 1/4 in
 - Connector A: Straight G 1/4 Female
 - Connector B: Straight G 1/4 Female
 - Inner Hose Material: Synthetic Rubber
 - Reinforcing Material: Steel
 - Cover Material: Synthetic Rubber
 - Maximum Operating Pressure: 400 bar



1101993 962 mm

1162MM SYNTHETIC RUBBER HYDRAULIC HOSE ASSEMBLY,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Overall Length: 1162 mm
 - Inside Diameter: 1/4 in
 - Connector A: Straight G 1/4 Female
 - Connector B: Straight G 1/4 Female
 - Inner Hose Material: Synthetic Rubber
 - Reinforcing Material: Steel
 - Cover Material: Synthetic Rubber
 - Maximum Operating Pressure: 400 bar



1101994 1162 mm

1462MM SYNTHETIC RUBBER HYDRAULIC HOSE ASSEMBLY,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Overall Length: 1462 mm
 - Inside Diameter: 1/4 in
 - Connector A: Straight G 1/4 Female
 - Connector B: Straight G 1/4 Female
 - Inner Hose Material: Synthetic Rubber
 - Reinforcing Material: Steel
 - Cover Material: Synthetic Rubber
 - Maximum Operating Pressure: 400 bar



1101995 1462 mm

1762MM SYNTHETIC RUBBER HYDRAULIC HOSE ASSEMBLY,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Overall Length: 1762 mm
 - Inside Diameter: 1/4 in
 - Connector A: Straight G 1/4 Female
 - Connector B: Straight G 1/4 Female
 - Inner Hose Material: Synthetic Rubber
 - Reinforcing Material: Steel
 - Cover Material: Synthetic Rubber
 - Maximum Operating Pressure: 400 bar



1101996 1762 mm

1956MM SYNTHETIC RUBBER HYDRAULIC HOSE ASSEMBLY, 275BAR

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Overall Length: 1956 mm
 - Inside Diameter: 1/2 in
 - Connector A: Straight G 1/2 Female
 - Connector B: Straight G 1/2 Female
 - Inner Hose Material: Synthetic Rubber
 - Reinforcing Material: Steel
 - Cover Material: Synthetic Rubber
 - Maximum Operating Pressure: 275 bar



1102019 1956 mm

262MM SYNTHETIC RUBBER HYDRAULIC HOSE ASSEMBLY, 215BAR

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Overall Length: 262 mm
 - Inside Diameter: 1/4 in
 - Connector A: Straight G 1/4 Female
 - Connector B: 90° Elbow G 1/4 Female
 - Inner Hose Material: Synthetic Rubber
 - Reinforcing Material: Steel
 - Cover Material: Synthetic Rubber
 - Maximum Operating Pressure: 215 bar



1102203 262 mm

762MM SYNTHETIC RUBBER HYDRAULIC HOSE ASSEMBLY,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Overall Length: 762 mm
 - Inside Diameter: 1/4 in
 - Connector A: Straight G 1/4 Female
 - Connector B: G 1/4 Female
 - Inner Hose Material: Synthetic Rubber
 - Reinforcing Material: Steel
 - Cover Material: Synthetic Rubber
 - Maximum Operating Pressure: 400 bar



1102208 762 mm

862MM SYNTHETIC RUBBER HYDRAULIC HOSE ASSEMBLY,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Overall Length: 862 mm
 - Inside Diameter: 1/4 in
 - Connector A: Straight G 1/4 Female
 - Connector B: G 1/4 Female
 - Inner Hose Material: Synthetic Rubber
 - Reinforcing Material: Steel
 - Cover Material: Synthetic Rubber
 - Maximum Operating Pressure: 400 bar



1102209 862 mm

1162MM SYNTHETIC RUBBER HYDRAULIC HOSE ASSEMBLY,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Overall Length: 1162 mm
 - Inside Diameter: 1/4 in
 - Connector A: Straight G 1/4 Female
 - Connector B: G 1/4 Female
 - Inner Hose Material: Synthetic Rubber
 - Reinforcing Material: Steel
 - Cover Material: Synthetic Rubber
 - Maximum Operating Pressure: 400 bar



1102211 1162 mm

1462MM SYNTHETIC RUBBER HYDRAULIC HOSE ASSEMBLY,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Overall Length: 1462 mm
 - Inside Diameter: 1/4 in
 - Connector A: Straight G 1/4 Female
 - Connector B: G 1/4 Female
 - Inner Hose Material: Synthetic Rubber
 - Reinforcing Material: Steel
 - Cover Material: Synthetic Rubber
 - Maximum Operating Pressure: 400 bar



1102212 1462 mm

1962MM SYNTHETIC RUBBER HYDRAULIC HOSE ASSEMBLY,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Overall Length: 1962 mm
 - Inside Diameter: 1/4 in
 - Connector A: Straight G 1/4 Female
 - Connector B: G 1/4 Female
 - Inner Hose Material: Synthetic Rubber
 - Reinforcing Material: Steel
 - Cover Material: Synthetic Rubber
 - Maximum Operating Pressure: 400 bar



1102213 1962 mm

658MM SYNTHETIC RUBBER HYDRAULIC HOSE ASSEMBLY,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Overall Length: 658 mm
 - Inside Diameter: 3/8 in
 - Connector A: Straight G 3/8 Female
 - Connector B: G 3/8 Female
 - Inner Hose Material: Synthetic Rubber
 - Reinforcing Material: Steel
 - Cover Material: Synthetic Rubber
 - Maximum Operating Pressure: 330 bar



1102219 658 mm

758MM SYNTHETIC RUBBER HYDRAULIC HOSE ASSEMBLY,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Overall Length: 758 mm
 - Inside Diameter: 3/8 in
 - Connector A: Straight G 3/8 Female
 - Connector B: G 3/8 Female
 - Inner Hose Material: Synthetic Rubber
 - Reinforcing Material: Steel
 - Cover Material: Synthetic Rubber
 - Maximum Operating Pressure: 330 bar



1102220 758 mm

1158MM SYNTHETIC RUBBER HYDRAULIC HOSE ASSEMBLY,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Overall Length: 1158 mm
 - Inside Diameter: 3/8 in
 - Connector A: Straight G 3/8 Female
 - Connector B: G 3/8 Female
 - Inner Hose Material: Synthetic Rubber
 - Reinforcing Material: Steel
 - Cover Material: Synthetic Rubber
 - Maximum Operating Pressure: 330 bar



1102223 1158 mm

1758MM SYNTHETIC RUBBER HYDRAULIC HOSE ASSEMBLY,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Overall Length: 1758 mm
 - Inside Diameter: 3/8 in
 - Connector A: Straight G 3/8 Female
 - Connector B: G 3/8 Female
 - Inner Hose Material: Synthetic Rubber
 - Reinforcing Material: Steel
 - Cover Material: Synthetic Rubber
 - Maximum Operating Pressure: 330 bar



1102225 1758 mm

1958MM SYNTHETIC RUBBER HYDRAULIC HOSE ASSEMBLY,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Overall Length: 1958 mm
 - Inside Diameter: 3/8 in
 - Connector A: Straight G 3/8 Female
 - Connector B: G 3/8 Female
 - Inner Hose Material: Synthetic Rubber
 - Reinforcing Material: Steel
 - Cover Material: Synthetic Rubber
 - Maximum Operating Pressure: 330 bar



1102226 1958 mm

556MM SYNTHETIC RUBBER HYDRAULIC HOSE ASSEMBLY, 275BAR

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Overall Length: 556 mm
 - Inside Diameter: 1/2 in
 - Connector A: Straight G 1/2 Female
 - Connector B: G 1/2 Female
 - Inner Hose Material: Synthetic Rubber
 - Reinforcing Material: Steel
 - Cover Material: Synthetic Rubber
 - Maximum Operating Pressure: 275 bar



1102228 556 mm

1156MM SYNTHETIC RUBBER HYDRAULIC HOSE ASSEMBLY, 275BAR

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Overall Length: 1156 mm
 - Inside Diameter: 1/2 in
 - Connector A: Straight G 1/2 Female
 - Connector B: G 1/2 Female
 - Inner Hose Material: Synthetic Rubber
 - Reinforcing Material: Steel
 - Cover Material: Synthetic Rubber
 - Maximum Operating Pressure: 275 bar



1102232 1156 mm

RS PRO NICKEL PLATED BRASS FEMALE QUICK AIR COUPLING, G 1/8

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Coupling Gender: Female
 - Threaded Connection: G 1/8 Female
 - Connection Type: Threaded
 - Thread Size: 1/8 in
 - Material: Nickel Plated Brass
 - Thread Gender: Female
 - Thread Standard: BSP
 - Maximum Operating Pressure: 12 bar



1761901 Female

RS PRO NICKEL PLATED BRASS MALE QUICK AIR COUPLING, 6MM HOSE

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Coupling Gender: Male
 - Connection Type: Hose Barb
 - Hose Barb Connection: 6 mm
 - Material: Nickel Plated Brass
 - Maximum Operating Pressure: 12 bar
 - Minimum Operating Temperature: -20 °C
 - Maximum Operating Temperature: +80 °C



1761904 Male

RS PRO NICKEL PLATED BRASS MALE QUICK AIR COUPLING, 8MM HOSE

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Coupling Gender: Male
 - Connection Type: Hose Barb
 - Hose Barb Connection: 8 mm
 - Material: Nickel Plated Brass
 - Maximum Operating Pressure: 12 bar
 - Minimum Operating Temperature: -20 °C
 - Maximum Operating Temperature: +80 °C



1761905 Male

RS PRO NICKEL PLATED BRASS MALE QUICK AIR COUPLING, 10MM HOSE

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Coupling Gender: Male
 - Connection Type: Hose Barb
 - Hose Barb Connection: 10 mm
 - Material: Nickel Plated Brass
 - Maximum Operating Pressure: 12 bar
 - Minimum Operating Temperature: -20 °C
 - Maximum Operating Temperature: +80 °C



1761914 Male

RS PRO NICKEL PLATED BRASS FEMALE QUICK AIR COUPLING, G 1/4

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Coupling Gender: Female
 - Threaded Connection: G 1/4 Male
 - Connection Type: Threaded
 - Thread Size: 1/4 in
 - Material: Nickel Plated Brass
 - Thread Gender: Male
 - Thread Standard: BSP
 - Maximum Operating Pressure: 12 bar



1761915 Female

RS PRO NICKEL PLATED BRASS FEMALE QUICK AIR COUPLING, G 1/4

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Coupling Gender: Female
 - Threaded Connection: G 1/4 Female
 - Connection Type: Threaded
 - Thread Size: 1/4 in
 - Material: Nickel Plated Brass
 - Thread Gender: Female
 - Thread Standard: BSP
 - Maximum Operating Pressure: 12 bar



1761929 Female

RS PRO NICKEL PLATED BRASS FEMALE QUICK AIR COUPLING, G 1/2

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Coupling Gender: Female
 - Threaded Connection: G 1/2 Male
 - Connection Type: Threaded
 - Thread Size: 1/2 in
 - Material: Nickel Plated Brass
 - Thread Gender: Male
 - Thread Standard: BSP
 - Maximum Operating Pressure: 12 bar



1761935 Female

RS PRO NICKEL PLATED BRASS FEMALE QUICK AIR COUPLING, G 1/4

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Coupling Gender: Female
 - Threaded Connection: G 1/4 Female
 - Connection Type: Threaded
 - Thread Size: 1/4 in
 - Material: Nickel Plated Brass
 - Thread Gender: Female
 - Thread Standard: BSP
 - Maximum Operating Pressure: 12 bar



1761936 Female

RS PRO NICKEL PLATED BRASS FEMALE QUICK AIR COUPLING, G 1/2

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Coupling Gender: Female
 - Threaded Connection: G 1/2 Female
 - Connection Type: Threaded
 - Thread Size: 1/2 in
 - Material: Nickel Plated Brass
 - Thread Gender: Female
 - Thread Standard: BSP
 - Maximum Operating Pressure: 12 bar



1761938 Female

RS PRO NICKEL PLATED BRASS MALE COUPLER NIPPLE, G 1/8 MALE 1/8 IN

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Coupling Gender: Male
 - Threaded Connection: G 1/8 Male
 - Connection Type: Threaded
 - Thread Size: 1/8 in
 - Hose Barb Connection: 1/8 in
 - Material: Nickel Plated Brass
 - Thread Gender: Male
 - Maximum Operating Pressure: 12 bar



1761944 Male

RS PRO NICKEL PLATED BRASS MALE COUPLER NIPPLE, G 1/4 FEMALE 1/4 IN

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Coupling Gender: Male
 - Threaded Connection: G 1/4 Female
 - Connection Type: Threaded
 - Thread Size: 1/4 in
 - Hose Barb Connection: 1/4 in
 - Material: Nickel Plated Brass
 - Thread Gender: Female
 - Maximum Operating Pressure: 12 bar



1761947 Male

RS PRO NICKEL PLATED BRASS MALE COUPLER NIPPLE, 4MM HOSE BARB

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Coupling Gender: Male
 - Connection Type: Hose Barb
 - Hose Barb Connection: 4 mm
 - Material: Nickel Plated Brass
 - Maximum Operating Pressure: 12 bar
 - Minimum Operating Temperature: -20 °C
 - Maximum Operating Temperature: +80 °C



1761948 Male

RS PRO NICKEL PLATED BRASS MALE COUPLER NIPPLE, 6MM HOSE BARB

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Coupling Gender: Male
 - Connection Type: Hose Barb
 - Hose Barb Connection: 6 mm
 - Material: Nickel Plated Brass
 - Maximum Operating Pressure: 12 bar
 - Minimum Operating Temperature: -20 °C
 - Maximum Operating Temperature: +80 °C



1761949 Male

RS PRO NICKEL PLATED BRASS MALE COUPLER NIPPLE, 8MM HOSE BARB

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Coupling Gender: Male
 - Connection Type: Hose Barb
 - Hose Barb Connection: 8 mm
 - Material: Nickel Plated Brass
 - Maximum Operating Pressure: 12 bar
 - Minimum Operating Temperature: -20 °C
 - Maximum Operating Temperature: +80 °C



1761950 Male

RS PRO NICKEL PLATED BRASS MALE COUPLER NIPPLE, G 1/4 MALE 1/4 IN

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Coupling Gender: Male
 - Threaded Connection: G 1/4 Male
 - Connection Type: Threaded
 - Thread Size: 1/4 in
 - Hose Barb Connection: 1/4 in
 - Material: Nickel Plated Brass
 - Thread Gender: Male
 - Maximum Operating Pressure: 12 bar



1761951 Male

RS PRO NICKEL PLATED BRASS MALE COUPLER NIPPLE, G 3/8 FEMALE

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Coupling Gender: Male
 - Threaded Connection: G 3/8 Female
 - Connection Type: Threaded
 - Thread Size: 3/8 in
 - Hose Barb Connection: 3/8 in
 - Material: Nickel Plated Brass
 - Thread Gender: Female
 - Maximum Operating Pressure: 12 bar



1761954 Male

RS PRO NICKEL PLATED BRASS FEMALE QUICK AIR COUPLING, M5

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Coupling Gender: Female
 - Threaded Connection: M5 Male
 - Connection Type: Threaded
 - Thread Size: M5
 - Material: Nickel Plated Brass
 - Thread Gender: Male
 - Thread Standard: BSP
 - Maximum Operating Pressure: 12 bar



1761999 Female

RS PRO NICKEL PLATED BRASS MALE QUICK AIR COUPLING, G 1/2 MALE

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Coupling Gender: Male
 - Threaded Connection: G 1/2 Male
 - Connection Type: Threaded
 - Thread Size: 1/2 in
 - Hose Barb Connection: 1/2 in
 - Material: Nickel Plated Brass
 - Thread Gender: Male
 - Thread Standard: BSP



1762005 Male

RS PRO NICKEL PLATED BRASS MALE COUPLER NIPPLE, G 1/2 MALE 1/2IN

ขนาดบรรจุภัณฑ์: 10 x EA

- Coupling Gender: Male
- Threaded Connection: G 1/2 Male
- Connection Type: Threaded
- Thread Size: 1/2 in
- Hose Barb Connection: 1/2 in
- Material: Nickel Plated Brass
- Thread Gender: Male
- Maximum Operating Pressure: 12 bar



1762011 Male

RS PRO NICKEL PLATED BRASS FEMALE COUPLER NIPPLE, G 1/2

ขนาดบรรจุภัณฑ์: 10 x EA

- Coupling Gender: Female
- Threaded Connection: G 1/2 Female
- Connection Type: Threaded
- Thread Size: 1/2 in
- Material: Nickel Plated Brass
- Thread Gender: Female
- Maximum Operating Pressure: 12 bar
- Minimum Operating Temperature: -20 °C



1762013 Female

RS PRO BRASS FEMALE QUICK AIR COUPLING, G 1/8 MALE THREADED

ขนาดบรรจุภัณฑ์: 2 x EA

- Coupling Gender: Female
- Threaded Connection: G 1/8 Male
- Connection Type: Threaded
- Thread Size: 1/8 in
- Material: Brass
- Thread Gender: Male
- Thread Standard: BSP
- Maximum Operating Pressure: 12 bar



1878764 Female

RS PRO BRASS MALE QUICK AIR COUPLING, 4MM HOSE BARB

ขนาดบรรจุภัณฑ์: 2 x EA

- Coupling Gender: Male
- Connection Type: Hose Barb
- Hose Barb Connection: 4 mm
- Material: Brass
- Maximum Operating Pressure: 12 bar
- Seal Material: NBR
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +80 °C



1878768 Male

RS PRO BRASS MALE QUICK AIR COUPLING, 6MM HOSE BARB

ขนาดบรรจุภัณฑ์: 2 x EA

- Coupling Gender: Male
- Connection Type: Hose Barb
- Hose Barb Connection: 6 mm
- Material: Brass
- Maximum Operating Pressure: 12 bar
- Seal Material: NBR
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +80 °C



1878769 Male

RS PRO BRASS FEMALE QUICK AIR COUPLING, G 1/4 MALE THREADED

ขนาดบรรจุภัณฑ์: 2 x EA

- Coupling Gender: Female
- Threaded Connection: G 1/4 Male
- Connection Type: Threaded
- Thread Size: 1/4 in
- Material: Brass
- Thread Gender: Male
- Thread Standard: BSP
- Maximum Operating Pressure: 16 bar



1878773 Female

RS PRO BRASS FEMALE QUICK AIR COUPLING, G 3/8 MALE THREADED

ขนาดบรรจุภัณฑ์: 2 x EA

- Coupling Gender: Female
- Threaded Connection: G 3/8 Male
- Connection Type: Threaded
- Thread Size: 3/8 in
- Material: Brass
- Thread Gender: Male
- Thread Standard: BSP
- Maximum Operating Pressure: 16 bar



1878774 Female

RS PRO BRASS FEMALE QUICK AIR COUPLING, G 1/2 FEMALE THREADED

ขนาดบรรจุภัณฑ์: 2 x EA

- Coupling Gender: Female
- Threaded Connection: G 1/2 Female
- Connection Type: Threaded
- Thread Size: 1/2 in
- Material: Brass
- Thread Gender: Male
- Thread Standard: BSP
- Maximum Operating Pressure: 16 bar



1878776 Female

RS PRO BRASS FEMALE QUICK AIR COUPLING, G 1/8 FEMALE THREADED

ขนาดบรรจุภัณฑ์: 2 x EA

- Coupling Gender: Female
- Threaded Connection: G 1/8 Female
- Connection Type: Threaded
- Thread Size: 1/8 in
- Material: Brass
- Thread Gender: Female
- Thread Standard: BSP
- Maximum Operating Pressure: 12 bar



1878795 Female

RS PRO BRASS FEMALE QUICK AIR COUPLING, G 1/4 FEMALE THREADED

ขนาดบรรจุภัณฑ์: 2 x EA

- Coupling Gender: Female
- Threaded Connection: G 1/4 Female
- Connection Type: Threaded
- Thread Size: 1/4 in
- Material: Brass
- Thread Gender: Female
- Thread Standard: BSP
- Maximum Operating Pressure: 12 bar



1878796 Female

RS PRO BRASS FEMALE QUICK AIR COUPLING, G 1/4 MALE THREADED

ขนาดบรรจุภัณฑ์: 2 x EA

- Coupling Gender: Female
- Threaded Connection: G 1/4 Male
- Connection Type: Threaded
- Thread Size: 1/4 in
- Material: Brass
- Thread Gender: Male
- Thread Standard: BSP
- Maximum Operating Pressure: 16 bar



1878800 Female

RS PRO BRASS FEMALE QUICK AIR COUPLING, G 1/2 MALE THREADED

ขนาดบรรจุภัณฑ์: 2 x EA

- Coupling Gender: Female
- Threaded Connection: G 1/2 Male
- Connection Type: Threaded
- Thread Size: 1/2 in
- Material: Brass
- Thread Gender: Male
- Thread Standard: BSP
- Maximum Operating Pressure: 16 bar



1878802 Female

RS PRO BRASS MALE COUPLER NIPPLE, G 1/8 MALE 1/8IN THREADED

ขนาดบรรจุภัณฑ์: 2 x EA

- Coupling Gender: Male
- Threaded Connection: G 1/8 Male
- Connection Type: Threaded
- Thread Size: 1/8 in
- Hose Barb Connection: 1/8 in
- Material: Brass
- Thread Gender: Male
- Maximum Operating Pressure: 12 bar



1878810 Male

RS PRO BRASS MALE COUPLER NIPPLE, G 1/4 MALE 1/4IN THREADED

ขนาดบรรจุภัณฑ์: 2 x EA

- Coupling Gender: Male
- Threaded Connection: G 1/4 Male
- Connection Type: Threaded
- Thread Size: 1/4 in
- Hose Barb Connection: 1/4 in
- Material: Brass
- Thread Gender: Male
- Thread Standard: BSP



1878811 Male

RS PRO BRASS MALE COUPLER NIPPLE, G 1/8 FEMALE 1/8IN

ขนาดบรรจุภัณฑ์: 2 x EA

- Coupling Gender: Male
- Threaded Connection: G 1/8 Female
- Connection Type: Threaded
- Thread Size: 1/8 in
- Hose Barb Connection: 1/8 in
- Material: Brass
- Thread Gender: Female
- Maximum Operating Pressure: 12 bar



1878812 Male

RS PRO BRASS MALE COUPLER NIPPLE, G 1/4 FEMALE 1/4IN

ขนาดบรรจุภัณฑ์: 2 x EA

- Coupling Gender: Male
- Threaded Connection: G 1/4 Female
- Connection Type: Threaded
- Thread Size: 1/4 in
- Hose Barb Connection: 1/4 in
- Material: Brass
- Thread Gender: Female
- Maximum Operating Pressure: 12 bar



1878813 Male

CONNECTOR WITH BARB 4MM

- ขนาดบรรจุภัณฑ์: **2 x EA**
- Coupling Gender: Male
 - Connection Type: Hose Barb
 - Hose Barb Connection: 4 mm
 - Material: Brass
 - Maximum Operating Pressure: 12 bar
 - Seal Material: NBR
 - Minimum Operating Temperature: -20 °C
 - Maximum Operating Temperature: +80 °C



1878814 Male

RS PRO BRASS MALE COUPLER NIPPLE, 6MM HOSE BARB

- ขนาดบรรจุภัณฑ์: **2 x EA**
- Coupling Gender: Male
 - Connection Type: Hose Barb
 - Hose Barb Connection: 6 mm
 - Material: Brass
 - Maximum Operating Pressure: 12 bar
 - Seal Material: NBR
 - Minimum Operating Temperature: -20 °C
 - Maximum Operating Temperature: +80 °C



1878815 Male

RS PRO BRASS MALE COUPLER NIPPLE, 8MM HOSE BARB

- ขนาดบรรจุภัณฑ์: **2 x EA**
- Coupling Gender: Male
 - Connection Type: Hose Barb
 - Hose Barb Connection: 8 mm
 - Material: Brass
 - Maximum Operating Pressure: 12 bar
 - Seal Material: NBR
 - Minimum Operating Temperature: -20 °C
 - Maximum Operating Temperature: +80 °C



1878816 Male

RS PRO BRASS MALE COUPLER NIPPLE, G 1/8 MALE 1/8IN THREADED

- ขนาดบรรจุภัณฑ์: **2 x EA**
- Coupling Gender: Male
 - Threaded Connection: G 1/8 Male
 - Connection Type: Threaded
 - Thread Size: 1/8 in
 - Hose Barb Connection: 1/8 in
 - Material: Brass
 - Thread Gender: Male
 - Maximum Operating Pressure: 12 bar



1878824 Male

RS PRO BRASS MALE COUPLER NIPPLE, G 1/4 MALE 1/4IN THREADED

- ขนาดบรรจุภัณฑ์: **2 x EA**
- Coupling Gender: Male
 - Threaded Connection: G 1/4 Male
 - Connection Type: Threaded
 - Thread Size: 1/4 in
 - Hose Barb Connection: 1/4 in
 - Material: Brass
 - Thread Gender: Male
 - Maximum Operating Pressure: 12 bar



1878825 Male

RS PRO BRASS MALE COUPLER NIPPLE, G 1/4 FEMALE 1/4IN

- ขนาดบรรจุภัณฑ์: **2 x EA**
- Coupling Gender: Male
 - Threaded Connection: G 1/4 Female
 - Connection Type: Threaded
 - Thread Size: 1/4 in
 - Hose Barb Connection: 1/4 in
 - Material: Brass
 - Thread Gender: Female
 - Maximum Operating Pressure: 12 bar



1878827 Male

RS PRO BRASS MALE COUPLER NIPPLE, 1/2IN HOSE BARB

- ขนาดบรรจุภัณฑ์: **2 x EA**
- Coupling Gender: Male
 - Connection Type: Hose Barb
 - Hose Barb Connection: 1/2 in
 - Material: Brass
 - Maximum Operating Pressure: 15 bar
 - Seal Material: NBR
 - Minimum Operating Temperature: -15 °C
 - Maximum Operating Temperature: +200 °C



1878833 Male

RS PRO BRASS FEMALE QUICK AIR COUPLING, M5 MALE THREADED

- ขนาดบรรจุภัณฑ์: **2 x EA**
- Coupling Gender: Female
 - Threaded Connection: M5 Male
 - Connection Type: Threaded
 - Thread Size: M5
 - Material: Brass
 - Thread Gender: Male
 - Thread Standard: BSP
 - Maximum Operating Pressure: 12 bar



1878860 Female

RS PRO IRON MALE PNEUMATIC QUICK CONNECT COUPLING, NPT 1

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Connection Standard: European
 - Coupling Gender: Male
 - Threaded Connection: NPT 1 Male
 - Manufacturer Series: UM
 - Connection Type: Threaded
 - Thread Size: 1 in
 - Material: Iron
 - Thread Gender: Male



7730531 European

RS PRO IRON MALE PNEUMATIC QUICK CONNECT COUPLING, NPT 1/2

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Connection Standard: European
 - Coupling Gender: Male
 - Threaded Connection: NPT 1/2 Male
 - Manufacturer Series: UM
 - Connection Type: Threaded
 - Thread Size: 1/2 in
 - Material: Iron
 - Thread Gender: Male



7730534 European

RS PRO IRON MALE PNEUMATIC QUICK CONNECT COUPLING, NPT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Connection Standard: European
 - Coupling Gender: Male
 - Threaded Connection: NPT 3/4 Male
 - Manufacturer Series: UM
 - Connection Type: Threaded
 - Thread Size: 3/4 in
 - Material: Iron
 - Thread Gender: Male



7730537 European

RS PRO IRON FEMALE PNEUMATIC QUICK CONNECT COUPLING, NPT 1/2

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Connection Standard: European
 - Coupling Gender: Female
 - Threaded Connection: NPT 1/2 Female
 - Manufacturer Series: UF
 - Connection Type: Threaded
 - Thread Size: 1/2 in
 - Material: Iron
 - Thread Gender: Female



7730540 European

RS PRO IRON FEMALE PNEUMATIC QUICK CONNECT COUPLING, NPT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Connection Standard: European
 - Coupling Gender: Female
 - Threaded Connection: NPT 3/4 Female
 - Manufacturer Series: UF
 - Connection Type: Threaded
 - Thread Size: 3/4 in
 - Material: Iron
 - Thread Gender: Female



7730543 European

RS PRO IRON FEMALE PNEUMATIC QUICK CONNECT COUPLING, NPT 1

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Connection Standard: European
 - Coupling Gender: Female
 - Threaded Connection: NPT 1 Female
 - Manufacturer Series: UF
 - Connection Type: Threaded
 - Thread Size: 1 in
 - Material: Iron
 - Thread Gender: Female



7730547 European

RS PRO IRON FEMALE PNEUMATIC QUICK CONNECT COUPLING, G 3/4

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Connection Standard: European
 - Coupling Gender: Female
 - Threaded Connection: G 3/4 Female
 - Manufacturer Series: OF
 - Connection Type: Threaded
 - Thread Size: 3/4 in
 - Material: Iron
 - Thread Gender: Female



7730584 European

RS PRO IRON MALE PNEUMATIC QUICK CONNECT COUPLING, G 3/4

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Connection Standard: European
 - Coupling Gender: Male
 - Threaded Connection: G 3/4 Male
 - Manufacturer Series: OM
 - Connection Type: Threaded
 - Thread Size: 3/4 in
 - Material: Iron
 - Thread Gender: Male



7730593 European

MICRO PUMP, NYLON BODY, GAS, LIQUID, 3V

- ขนาดบรรจุภัณฑ์: 1 x EA
- Pump Type: Diaphragm
 - Drive Type: Electric
 - Maximum Flow Rate: 250-300 ml/min
 - Maximum Working Pressure: 1 bar
 - IP Rating: IP50
 - Series: D200
 - Maximum Fluid Temperature: +100 °C
 - Body Material: Nylon



7026894 Diaphragm

MICRO PUMP, ALLOY BODY, GAS, LIQUID, 3V

- ขนาดบรรจุภัณฑ์: 1 x EA
- Pump Type: Diaphragm
 - Drive Type: Electric
 - Maximum Flow Rate: 380 ml/min
 - Maximum Working Pressure: 11 psi
 - IP Rating: IP50
 - Series: D250
 - Maximum Fluid Temperature: +100 °C
 - Body Material: Aluminium



7026898 Diaphragm

RS PRO PROCESS PUMP CONTROLLER FOR BRUSHLESS

- ขนาดบรรจุภัณฑ์: 1 x EA
- Compatible Pump Type: Brushless Micropump
 - Supply Voltage: 12 → 30 V dc
 - Connection: 2 Screw Terminal (Input), 3 Screw Terminal (Output)
 - Maximum Output Pressure: 10 bar



1253567 Brushless

RS PRO PROCESS PUMP CONTROLLER FOR BRUSHLESS

- ขนาดบรรจุภัณฑ์: 1 x EA
- Compatible Pump Type: Brushless Micropump
 - Supply Voltage: 12 → 30 V dc
 - Connection: 2 Screw Terminal (Input), 3 Screw Terminal (Output)
 - Maximum Fluid Temperature: +80 °C
 - Maximum Output Pressure: 10 bar



1253568 Brushless

RS PRO PROCESS PUMP CONTROLLER FOR BRUSHLESS

- ขนาดบรรจุภัณฑ์: 1 x EA
- Compatible Pump Type: Brushless Micropump
 - Supply Voltage: 12 → 30 V dc
 - Connection: 2 Screw Terminal (Input), 3 Screw Terminal (Output)
 - Maximum Fluid Temperature: +80 °C
 - Maximum Output Pressure: 10 bar



1253569 Brushless

RS PRO PROCESS PUMP CONTROLLER FOR BRUSHLESS

- ขนาดบรรจุภัณฑ์: 1 x EA
- Compatible Pump Type: Brushless Micropump
 - Supply Voltage: 12 → 30 V dc
 - Connection: 2 Screw Terminal (Input), 3 Screw Terminal (Output)
 - Maximum Fluid Temperature: +80 °C
 - Maximum Output Pressure: 10 bar



1253571 Brushless

RS PRO SOLENOID VALVE, 2 PORT(S), NC, 24 V DC

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 24 V dc
 - Number of Ports: 2
 - Operation: Pilot
 - Connection: G 3/8
 - Default Valve Position: NC
 - Suitable Applications: Gas, Liquid
 - Body Material: Brass
 - Maximum Working Pressure: 15 bar



1440794 24 V dc

RS PRO SOLENOID VALVE, 2 PORT(S), NC, 24 V DC

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 24 V dc
 - Number of Ports: 2
 - Operation: Pilot
 - Connection: 1/2 in G
 - Default Valve Position: NC
 - Suitable Applications: Gas, Liquid
 - Body Material: Brass
 - Maximum Working Pressure: 15 bar



1440797 24 V dc

RS PRO SOLENOID VALVE, 2 PORT(S), NC, 24 V DC

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 24 V dc
 - Number of Ports: 2
 - Operation: Pilot
 - Connection: 3/4 in G
 - Default Valve Position: NC
 - Suitable Applications: Gas, Liquid
 - Body Material: Brass
 - Maximum Working Pressure: 15 bar



1440799 24 V dc

RS PRO SOLENOID VALVE, 2 PORT(S), NC, 24 V DC

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 24 V dc
 - Number of Ports: 2
 - Operation: Pilot
 - Connection: 1 in G
 - Default Valve Position: NC
 - Suitable Applications: Gas, Liquid
 - Body Material: Brass
 - Maximum Working Pressure: 12 bar



1440801 24 V dc

RS PRO SOLENOID VALVE, 2 PORT(S), NC, 24 V DC

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 24 V dc
 - Number of Ports: 2
 - Operation: Pilot
 - Connection: 1-1/4 in G
 - Default Valve Position: NC
 - Suitable Applications: Gas, Liquid
 - Body Material: Brass
 - Maximum Working Pressure: 12 bar



1440803 24 V dc

RS PRO SOLENOID VALVE, 2 PORT(S), NC, 24 V DC

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 24 V dc
 - Number of Ports: 2
 - Operation: Pilot
 - Connection: 2 in G
 - Default Valve Position: NC
 - Suitable Applications: Gas, Liquid
 - Body Material: Brass
 - Maximum Working Pressure: 10 bar



1440807 24 V dc

RS PRO SOLENOID VALVE, 2 PORT(S), NO, 24 V DC

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 24 V dc
 - Number of Ports: 2
 - Operation: Pilot
 - Connection: 1/2 in G
 - Default Valve Position: NO
 - Suitable Applications: Gas, Liquid
 - Body Material: Brass
 - Maximum Working Pressure: 15 bar



1440811 24 V dc

RS PRO SOLENOID VALVE, 2 PORT(S), NO, 24 V DC

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 24 V dc
 - Number of Ports: 2
 - Operation: Pilot
 - Connection: 3/4 in G
 - Default Valve Position: NO
 - Suitable Applications: Gas, Liquid
 - Body Material: Brass
 - Maximum Working Pressure: 15 bar



1440813 24 V dc

RS PRO SOLENOID VALVE, 2 PORT(S), NO, 24 V DC

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 24 V dc
 - Number of Ports: 2
 - Operation: Pilot
 - Connection: 1 in G
 - Default Valve Position: NO
 - Suitable Applications: Gas, Liquid
 - Body Material: Brass
 - Maximum Working Pressure: 12 bar



1440815 24 V dc

WATER SOLENOID VALVE 2 PORT 180° NC 1/2"

- ขนาดบรรจุภัณฑ์: 1 x EA
- Supply Voltage: 24 V ac/dc
 - Number of Ports: 2
 - Operation: Solenoid
 - Connection: 1/2 in BSP
 - Connection Size: 1/2 in
 - Default Valve Position: NC
 - Suitable Applications: Water
 - Type: 2 (Port)



1904135 24 V ac/dc

RS PRO SOLENOID VALVE, 2 PORT(S) , NC, 230 V AC/DC, 3/4IN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 230 V ac/dc
 - Number of Ports: 2
 - Operation: Solenoid
 - Connection: 3/4 in BSP
 - Connection Size: 3/4 in
 - Default Valve Position: NC
 - Suitable Applications: Water
 - Type: 2 (Port)



1904136 230 V ac/dc

RS PRO SOLENOID VALVE, 2 PORT(S) , NC, 24 V AC/DC, 3/4IN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 24 V ac/dc
 - Number of Ports: 2
 - Operation: Solenoid
 - Connection: 3/4 in BSP
 - Connection Size: 3/4 in
 - Default Valve Position: NC
 - Suitable Applications: Water
 - Type: 2 (Port)



1904137 24 V ac/dc

RS PRO SOLENOID VALVE, 2 PORT(S) , NC, 230 V AC/DC, 3/8IN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 230 V ac/dc
 - Number of Ports: 2
 - Operation: Solenoid
 - Connection Size: 3/8 in
 - Default Valve Position: NC
 - Suitable Applications: Water
 - Type: 2 (Port)
 - Orifice Diameter: 2.6 mm



1904138 230 V ac/dc

RS PRO SOLENOID VALVE, 2 PORT(S) , NC, 24 V AC/DC, 3/8IN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 24 V ac/dc
 - Number of Ports: 2
 - Operation: Solenoid
 - Connection Size: 3/8 in
 - Default Valve Position: NC
 - Suitable Applications: Water
 - Type: 2 (Port)
 - Orifice Diameter: 2.6 mm



1904139 24 V ac/dc

WATER SOLENOID VALVE 2 PORT 180° NC 3/4"

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 230 V ac/dc
 - Number of Ports: 2
 - Operation: Solenoid
 - Connection: 3/4 in BSP
 - Connection Size: 3/4 in
 - Default Valve Position: NC
 - Suitable Applications: Water
 - Type: 2 (Port)



1904140 230 V ac/dc

WATER SOLENOID VALVE 2 PORT 180° NC 3/4"

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 24 V ac/dc
 - Number of Ports: 2
 - Operation: Solenoid
 - Connection: 3/4 in BSP
 - Connection Size: 3/4 in
 - Default Valve Position: NC
 - Suitable Applications: Water
 - Type: 2 (Port)



1904141 24 V ac/dc

RS PRO SOLENOID VALVE, 2 PORT(S) , NC, 230 V AC/DC, 3/4IN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 230 V ac/dc
 - Number of Ports: 2
 - Operation: Solenoid
 - Connection: 3/4 in BSP
 - Connection Size: 3/4 in
 - Default Valve Position: NC
 - Suitable Applications: Water
 - Type: 2 (Port)



1904142 230 V ac/dc

WATER SOLENOID VALVE 2 PORT 90° NC 3/4"

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 24 V ac/dc
 - Number of Ports: 2
 - Operation: Solenoid
 - Connection: 3/4 in BSP
 - Connection Size: 3/4 in
 - Default Valve Position: NC
 - Suitable Applications: Water
 - Type: 2 (Port)



1904143 24 V ac/dc

RS PRO SOLENOID VALVE, 3 PORT(S) , NC, 230 V AC/DC, 3/4IN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 230 V ac/dc
 - Number of Ports: 3
 - Operation: Solenoid
 - Connection: 3/4 in BSP
 - Connection Size: 3/4 in
 - Default Valve Position: NC
 - Suitable Applications: Water
 - Maximum Working Pressure: 10 bar



1904144 230 V ac/dc

RS PRO SOLENOID VALVE, 3 PORT(S) , NC, 24 V AC/DC, 3/4IN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 24 V ac/dc
 - Number of Ports: 3
 - Operation: Solenoid
 - Connection: 3/4 in BSP
 - Connection Size: 3/4 in
 - Default Valve Position: NC
 - Suitable Applications: Water
 - Maximum Working Pressure: 10 bar



1904145 24 V ac/dc

RS PRO SOLENOID VALVE, 3 PORT(S) , NC, 230 V AC/DC, 3/4IN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 230 V ac/dc
 - Number of Ports: 3
 - Operation: Solenoid
 - Connection: 3/4 in BSP
 - Connection Size: 3/4 in
 - Default Valve Position: NC
 - Suitable Applications: Water
 - Maximum Working Pressure: 10 bar



1904146 230 V ac/dc

RS PRO SOLENOID VALVE, 3 PORT(S) , NC, 24 V AC/DC, 3/4IN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 24 V ac/dc
 - Number of Ports: 3
 - Operation: Solenoid
 - Connection: 3/4 in BSP
 - Connection Size: 3/4 in
 - Default Valve Position: NC
 - Suitable Applications: Water
 - Maximum Working Pressure: 10 bar



1904147 24 V ac/dc

SOLEN.30MM H D13 12V DC 8W

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 12 V dc



1875715 12 V dc

SOLEN.30MM H D13 12V DC 14W

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 12 V dc



1875716 12 V dc

SOLEN.30MM H D13 24V AC 14VA

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 24 V ac



1875717 24 V ac

RS PRO 110 V AC SOLENOID VALVE COIL

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 110 V ac



1875718 110 V ac

SOLEN.30MM H D13 220V AC14VA

- ขนาดบรรจุภัณฑ์: **1 x EA**
 • Supply Voltage: 220 V ac



1875719 220 V ac

SOLEN.30MM H D13 220V AC21VA

- ขนาดบรรจุภัณฑ์: **1 x EA**
 • Supply Voltage: 220 V ac



1875720 220 V ac

RS PRO, 3 → 4 V 327 MBAR CENTRIFUGAL WATER PUMP,

- ขนาดบรรจุภัณฑ์: **1 x EA**
 • Maximum Flow Rate: 650 ml/min
 • Supply Voltage: 3 → 4 V
 • Input Connection: 3.2 mm Tube
 • Maximum Head: 1.9 m
 • Maximum Working Pressure: 327 mbar
 • Body Material: Aluminium
 • Input Power: 0.84 → 1.6 W
 • Maximum Fluid Temperature: +120 °C



480122 650 ml/min

RS PRO, 6 V 1.5 BAR DIRECT COUPLING CENTRIFUGAL WATER

- ขนาดบรรจุภัณฑ์: **1 x EA**
 • Maximum Flow Rate: 3.8 L/min
 • Supply Voltage: 6 V
 • Input Connection: 8 mm Tube
 • Maximum Working Pressure: 1.5 bar
 • Body Material: Anodised Aluminium
 • Coupling Type: Direct
 • Input Power: 4.2 W
 • Maximum Fluid Temperature: +100 °C



1253555 3.8 L/min

RS PRO, 6 → 24 V 1.5 BAR DIRECT COUPLING CENTRIFUGAL WATER

- ขนาดบรรจุภัณฑ์: **1 x EA**
 • Maximum Flow Rate: 3.8 L/min
 • Supply Voltage: 6 → 24 V
 • Input Connection: 8 mm Tube
 • Maximum Working Pressure: 1.5 bar
 • Body Material: Anodised Aluminium
 • Coupling Type: Direct
 • Input Power: 4.2 → 22.8 W
 • Maximum Fluid Temperature: +100 °C



1253556 3.8 L/min

RS PRO, 6 → 24 V 4 BAR DIRECT COUPLING WATER PUMP, 850ML/MIN

- ขนาดบรรจุภัณฑ์: **1 x EA**
 • Maximum Flow Rate: 850 ml/min
 • Supply Voltage: 6 → 24 V
 • Input Connection: 1/8 BSP
 • Maximum Working Pressure: 4 bar
 • Body Material: Anodised Aluminium
 • Coupling Type: Direct
 • Input Power: 3 → 30 W
 • Maximum Fluid Temperature: +100 °C



1253561 850 ml/min

RS PRO, 6 → 24 V 10 BAR DIRECT COUPLING WATER PUMP, 400ML/MIN

- ขนาดบรรจุภัณฑ์: **1 x EA**
 • Maximum Flow Rate: 400 ml/min
 • Supply Voltage: 6 → 24 V
 • Input Connection: 1/8 BSP
 • Maximum Working Pressure: 10 bar
 • Body Material: Anodised Aluminium
 • Coupling Type: Direct
 • Input Power: 3 → 30 W
 • Maximum Fluid Temperature: +100 °C



1253562 400 ml/min

RS PRO, 6 → 24 V 15 BAR DIRECT COUPLING WATER PUMP, 1.75L/MIN

- ขนาดบรรจุภัณฑ์: **1 x EA**
 • Maximum Flow Rate: 1.75 L/min
 • Supply Voltage: 6 → 24 V
 • Input Connection: 1/8 BSP
 • Maximum Working Pressure: 15 bar
 • Body Material: Anodised Aluminium
 • Coupling Type: Direct
 • Input Power: 15 → 99 W
 • Maximum Fluid Temperature: +80 °C



1253564 1.75 L/min

RS PRO, 12 V 380 MBAR WATER PUMP, 1150ML/MIN

- ขนาดบรรจุภัณฑ์: **1 x EA**
 • Maximum Flow Rate: 1150 ml/min
 • Supply Voltage: 12 V
 • Input Connection: 3.2 mm Tube
 • Maximum Working Pressure: 380 mbar
 • Body Material: Anodised Aluminium
 • Input Power: 5.8 W
 • Maximum Fluid Temperature: +100 °C
 • Input Connection Size: 3.2 mm



1253580 1150 ml/min

RS PRO, 3 → 6 V 0.7 MBAR WATER PUMP, 3.6L/MIN

- ขนาดบรรจุภัณฑ์: **1 x EA**
 • Maximum Flow Rate: 3.6 L/min
 • Supply Voltage: 3 → 6 V
 • Maximum Working Pressure: 0.7 mbar
 • Body Material: ABS, PC
 • Input Power: 0.3 → 2.1 W
 • Maximum Fluid Temperature: +60 °C
 • IP Rating: IP41



1253593 3.6 L/min

MICRO PUMP, 2.80 L/M, 3-12V, 6MM TUBING

- ขนาดบรรจุภัณฑ์: **1 x EA**
 • Maximum Flow Rate: 2.8 L/min
 • Supply Voltage: 12 V
 • Input Connection: 5 mm Tube
 • Maximum Head: 3.5 m
 • Maximum Working Pressure: 324 mbar
 • Body Material: Aluminium
 • Input Power: 6 W
 • Maximum Fluid Temperature: +120 °C



7026872 2.8 L/min

MICRO PUMP, 2.00 L/M, 3-12V, 3MM TUBING

- ขนาดบรรจุภัณฑ์: **1 x EA**
 • Maximum Flow Rate: 2 L/min
 • Supply Voltage: 12 V
 • Input Connection: 3.2 mm Tube
 • Maximum Head: 3.5 m
 • Maximum Working Pressure: 345 mbar
 • Body Material: Anodised Aluminium
 • Coupling Type: Direct
 • Input Power: 6 W



7026876 2 L/min

MICRO PUMP, 2.80 L/M, 3-12V, 6MM TUBING

- ขนาดบรรจุภัณฑ์: **1 x EA**
 • Maximum Flow Rate: 2.8 L/min
 • Supply Voltage: 12 V
 • Input Connection: 5 mm Tube
 • Maximum Head: 3.5 m
 • Maximum Working Pressure: 323 mbar
 • Body Material: Aluminium
 • Input Power: 6 W
 • Maximum Fluid Temperature: +120 °C



7026882 2.8 L/min

RS PRO, 12 V 325 MBAR CENTRIFUGAL WATER PUMP,

- ขนาดบรรจุภัณฑ์: **1 x EA**
 • Maximum Flow Rate: 2800 ml/min
 • Supply Voltage: 12 V
 • Input Connection: 5 mm Tube
 • Maximum Head: 3.5 m
 • Maximum Working Pressure: 325 mbar
 • Body Material: Aluminium
 • Input Power: 6 W
 • Maximum Fluid Temperature: +100 °C



7026885 2800 ml/min

RS PRO, 12 V 345 MBAR DIRECT COUPLING CENTRIFUGAL WATER

- ขนาดบรรจุภัณฑ์: **1 x EA**
 • Maximum Flow Rate: 2000 ml/min
 • Supply Voltage: 12 V
 • Input Connection: 3.2 mm Tube
 • Maximum Head: 3.5 m
 • Maximum Working Pressure: 345 mbar
 • Body Material: Anodised Aluminium
 • Coupling Type: Direct
 • Input Power: 6 W



7026888 2000 ml/min

RS PRO, 12 V 380 MBAR DIRECT COUPLING CENTRIFUGAL WATER

- ขนาดบรรจุภัณฑ์: **1 x EA**
 • Maximum Flow Rate: 2685 ml/min
 • Supply Voltage: 12 V
 • Input Connection: 6 mm Tube
 • Maximum Working Pressure: 380 mbar
 • Body Material: Aluminium Alloy
 • Coupling Type: Direct
 • Input Power: 7.1 W
 • Maximum Fluid Temperature: +100 °C



8170706 2685 ml/min

RS PRO, 6 V 10 PSI, -8 PSI DIRECT COUPLING WATER PUMP,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Maximum Flow Rate: 380 ml/min, 450 ml/min
 - Supply Voltage: 6 V
 - Input Connection: 2.4 mm Tube
 - Maximum Working Pressure: 10 psi, -8 psi
 - Body Material: Glass Filled Nylon
 - Coupling Type: Direct
 - Input Power: 0.7 W
 - Maximum Fluid Temperature: +100 °C



8170712 380 ml/min, 450

RS PRO, 6 V 12 PSI, -8 PSI DIRECT COUPLING WATER PUMP,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Maximum Flow Rate: 420 ml/min, 620 ml/min
 - Supply Voltage: 6 V
 - Input Connection: 2.4 mm Tube
 - Maximum Working Pressure: 12 psi, -8 psi
 - Body Material: Anodised Aluminium
 - Coupling Type: Direct
 - Input Power: 0.7 W
 - Maximum Fluid Temperature: +100 °C



8170716 420 ml/min, 620

RS PRO, 6 V 8 BAR DIRECT COUPLING WATER PUMP, 500ML/MIN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Maximum Flow Rate: 500 ml/min
 - Supply Voltage: 6 V
 - Input Connection: 4 mm Tube
 - Maximum Working Pressure: 8 bar
 - Body Material: Aluminium Alloy
 - Coupling Type: Direct
 - Input Power: 30 W
 - Maximum Fluid Temperature: +100 °C



8170722 500 ml/min

RS PRO, 4.5 V 11 PSI, -8 PSI DIRECT COUPLING WATER PUMP,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Maximum Flow Rate: 360 ml/min, 580 ml/min
 - Supply Voltage: 4.5 V
 - Input Connection: 2.4 mm Tube
 - Maximum Working Pressure: 11 psi, -8 psi
 - Body Material: Anodised Aluminium
 - Coupling Type: Direct
 - Input Power: 0.4 W
 - Maximum Fluid Temperature: +100 °C



8170725 360 ml/min, 580

RS PRO, 6 V 6 BAR DIRECT COUPLING WATER PUMP, 850ML/MIN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Maximum Flow Rate: 850 ml/min
 - Supply Voltage: 6 V
 - Input Connection: 4 mm Tube
 - Maximum Working Pressure: 6 bar
 - Body Material: Aluminium Alloy
 - Coupling Type: Direct
 - Input Power: 30 W
 - Maximum Fluid Temperature: +100 °C



8170731 850 ml/min

RS PRO, 6 → 24 V 10 BAR DIRECT COUPLING WATER PUMP, 630ML/MIN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Maximum Flow Rate: 630 ml/min
 - Supply Voltage: 6 → 24 V
 - Input Connection: 4 mm Tube
 - Maximum Working Pressure: 10 bar
 - Body Material: Anodised Aluminium
 - Coupling Type: Direct
 - Input Power: 3 → 30 W
 - Maximum Fluid Temperature: +100 °C



8170734 630 ml/min

RS PRO, 6 → 24 V 15 BAR DIRECT COUPLING WATER PUMP, 1.75L/MIN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Maximum Flow Rate: 1.75 L/min
 - Supply Voltage: 6 → 24 V
 - Input Connection: 6 mm Tube
 - Maximum Working Pressure: 15 bar
 - Body Material: Aluminium Alloy
 - Coupling Type: Direct
 - Input Power: 15 → 99 W
 - Maximum Fluid Temperature: +100 °C



8170766 1.75 L/min

RS PRO, 6 → 24 V 580 MBAR DIRECT COUPLING WATER PUMP,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Maximum Flow Rate: 8000 ml/min
 - Supply Voltage: 6 → 24 V
 - Input Connection: 8 mm Tube
 - Maximum Working Pressure: 580 mbar
 - Body Material: Aluminium Alloy
 - Coupling Type: Direct
 - Maximum Fluid Temperature: +100 °C
 - Input Connection Size: 8 mm



8170772 8000 ml/min

RS PRO, 6 → 24 V 8 BAR DIRECT COUPLING WATER PUMP, 10L/MIN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Maximum Flow Rate: 10 L/min
 - Supply Voltage: 6 → 24 V
 - Input Connection: 8 mm Tube
 - Maximum Working Pressure: 8 bar
 - Body Material: Aluminium Alloy
 - Coupling Type: Direct
 - Maximum Fluid Temperature: +100 °C
 - Input Connection Size: 8 mm



8170781 10 L/min

RS PRO, 6 → 24 V DIRECT COUPLING WATER PUMP, 10L/MIN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Maximum Flow Rate: 10 L/min
 - Supply Voltage: 6 → 24 V
 - Input Connection: 8 mm Tube
 - Body Material: Aluminium Alloy
 - Coupling Type: Direct
 - Maximum Fluid Temperature: +100 °C
 - Input Connection Size: 8 mm
 - Output Connection Size: 8 mm



8170784 10 L/min

RS PRO, 4 V 323 MBAR CENTRIFUGAL WATER PUMP, 661ML/MIN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Maximum Flow Rate: 661 ml/min
 - Supply Voltage: 4 V
 - Input Connection: 3.2 mm Tube
 - Maximum Working Pressure: 323 mbar
 - Body Material: Aluminium
 - Input Power: 2 W
 - Maximum Fluid Temperature: +100 °C
 - Input Connection Size: 3.2 mm



9146956 661 ml/min

RS PRO, 12 V 380 MBAR CENTRIFUGAL WATER PUMP,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Maximum Flow Rate: 2685 ml/min
 - Supply Voltage: 12 V
 - Input Connection: 6 mm Tube
 - Maximum Working Pressure: 380 mbar
 - Body Material: Aluminium
 - Input Power: 7.1 W
 - Maximum Fluid Temperature: +100 °C
 - Input Connection Size: 6 mm



9146969 2685 ml/min

RS PRO, 6 → 24 V 8 BAR WATER PUMP, 2.4L/MIN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Maximum Flow Rate: 2.4 L/min
 - Supply Voltage: 6 → 24 V
 - Maximum Working Pressure: 8 bar
 - Body Material: Aluminium
 - Input Power: 15 → 99 W
 - Maximum Fluid Temperature: +100 °C
 - IP Rating: IP67



9147016 2.4 L/min

HEAVY DUTY WASH GUN 1/2" BSPF

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Maximum Working Pressure: 24 bar
 - Threaded Connection: 1/2 in BSP Female
 - Thread Size: 1/2 in
 - Thread Standard: BSP



1756263 24 bar

RS PRO 1/2 IN BSP FEMALE SPRAY GUN, 24 BAR

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Maximum Working Pressure: 24 bar
 - Threaded Connection: 1/2 in BSP Female
 - Thread Size: 1/2 in
 - Thread Standard: BSP



1756264 24 bar

RS PRO 1/2 IN BSP SPRAY GUN, 24 BAR

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Maximum Working Pressure: 24 bar
 - Threaded Connection: 1/2 in BSP
 - Thread Size: 1/2 in
 - Thread Standard: BSP



3627096 24 bar

RS PRO STEEL HYDRAULIC BALL VALVE G 1/4

- ขนาดบรรจุภัณฑ์: 1 x EA
- Manufacturer Series: BK3
 - Number of Ports: 3-way
 - Connection Port Thread: G 1/4
 - Body Material: Steel
 - Seal Material: Nitrile Rubber (Stem Seal), POM-Mos2 (Ball Seal)
 - Maximum Operating Pressure: 500 bar
 - Thread Standard: G
 - Thread Size: 1/4 in



2431793 BK3

RS PRO STEEL HYDRAULIC BALL VALVE G 3/8

- ขนาดบรรจุภัณฑ์: 1 x EA
- Manufacturer Series: BK3
 - Number of Ports: 3-way
 - Connection Port Thread: G 3/8
 - Body Material: Steel
 - Seal Material: Nitrile Rubber (Stem Seal), POM-Mos2 (Ball Seal)
 - Maximum Operating Pressure: 315 bar
 - Thread Standard: G
 - Thread Size: 3/8 in



2431800 BK3

RS PRO STEEL HYDRAULIC BALL VALVE G 1/2

- ขนาดบรรจุภัณฑ์: 1 x EA
- Manufacturer Series: BK3
 - Number of Ports: 3-way
 - Connection Port Thread: G 1/2
 - Body Material: Steel
 - Seal Material: Nitrile Rubber (Stem Seal), POM-Mos2 (Ball Seal)
 - Maximum Operating Pressure: 500 bar
 - Thread Standard: G
 - Thread Size: 1/2 in



2431816 BK3

RS PRO STEEL HYDRAULIC BALL VALVE G 3/4

- ขนาดบรรจุภัณฑ์: 1 x EA
- Manufacturer Series: BK3
 - Number of Ports: 3-way
 - Connection Port Thread: G 3/4
 - Body Material: Steel
 - Seal Material: Nitrile Rubber (Stem Seal), POM-Mos2 (Ball Seal)
 - Maximum Operating Pressure: 315 bar
 - Thread Standard: G
 - Thread Size: 3/4 in



2431822 BK3

VALVE,BALL,HYDRAULIC,2 WAY,1/4IN BSP,CARBON STEEL,500 BAR

- ขนาดบรรจุภัณฑ์: 1 x EA
- Manufacturer Series: BKH
 - Number of Ports: 2-way
 - Connection Port Thread: G 1/4
 - Body Material: Zinc Passivated Steel
 - Seal Material: Nitrile Rubber (Stem Seal), POM-Mos2 (Ball Seal)
 - Maximum Operating Pressure: 500 bar
 - Thread Standard: G
 - Thread Size: 1/4 in



2975827 BKH

VALVE,BALL,HYDRAULIC,2 WAY,3/8IN BSP,CARBON STEEL,500 BAR

- ขนาดบรรจุภัณฑ์: 1 x EA
- Manufacturer Series: BKH
 - Number of Ports: 2-way
 - Connection Port Thread: G 3/8
 - Body Material: Zinc Passivated Steel
 - Seal Material: Nitrile Rubber (Stem Seal), POM-Mos2 (Ball Seal)
 - Maximum Operating Pressure: 500 bar
 - Thread Standard: G
 - Thread Size: 3/8 in



2975833 BKH

VALVE,BALL,HYDRAULIC,2 WAY,1/2IN BSP,CARBON STEEL,500 BAR

- ขนาดบรรจุภัณฑ์: 1 x EA
- Manufacturer Series: BKH
 - Number of Ports: 2-way
 - Connection Port Thread: G 1/2
 - Body Material: Zinc Passivated Steel
 - Seal Material: Nitrile Rubber (Stem Seal), POM-Mos2 (Ball Seal)
 - Maximum Operating Pressure: 500 bar
 - Thread Standard: G
 - Thread Size: 1/2 in



2975849 BKH

RS PRO ZINC PASSIVATED STEEL HYDRAULIC BALL VALVE G 3/4

- ขนาดบรรจุภัณฑ์: 1 x EA
- Manufacturer Series: BKH
 - Number of Ports: 2-way
 - Connection Port Thread: G 3/4
 - Body Material: Zinc Passivated Steel
 - Seal Material: Nitrile Rubber (Stem Seal), POM-Mos2 (Ball Seal)
 - Maximum Operating Pressure: 400 bar
 - Thread Standard: G
 - Thread Size: 3/4 in



2975861 BKH

RS PRO ZINC PASSIVATED STEEL HYDRAULIC BALL VALVE G 1

- ขนาดบรรจุภัณฑ์: 1 x EA
- Manufacturer Series: BKH
 - Number of Ports: 2-way
 - Connection Port Thread: G 1
 - Body Material: Zinc Passivated Steel
 - Seal Material: Nitrile Rubber (Stem Seal), POM-Mos2 (Ball Seal)
 - Maximum Operating Pressure: 350 bar
 - Thread Standard: G
 - Thread Size: 1 in



2975877 BKH

RS PRO STAINLESS STEEL HYDRAULIC BALL VALVE NPT 1/4

- ขนาดบรรจุภัณฑ์: 1 x EA
- Manufacturer Series: B6BI
 - Number of Ports: 2-way
 - Connection Port Thread: NPT 1/4
 - Body Material: Stainless Steel
 - Seal Material: PTFE (Stem Seal), Teflon/kel-F (Ball Seal)
 - Maximum Operating Pressure: 6000 psi
 - Thread Standard: NPT
 - Thread Size: 1/4 in



3244988 B6BI

RS PRO STAINLESS STEEL HYDRAULIC BALL VALVE NPT 3/8

- ขนาดบรรจุภัณฑ์: 1 x EA
- Manufacturer Series: B6BI
 - Number of Ports: 2-way
 - Connection Port Thread: NPT 3/8
 - Body Material: Stainless Steel
 - Seal Material: PTFE (Stem Seal), Teflon/kel-F (Ball Seal)
 - Maximum Operating Pressure: 6000 psi
 - Thread Standard: NPT
 - Thread Size: 3/8 in



3244994 B6BI

RS PRO STAINLESS STEEL HYDRAULIC BALL VALVE NPT 1/2

- ขนาดบรรจุภัณฑ์: 1 x EA
- Manufacturer Series: B6BI
 - Number of Ports: 2-way
 - Connection Port Thread: NPT 1/2
 - Body Material: Stainless Steel
 - Seal Material: PTFE (Stem Seal), Teflon/kel-F (Ball Seal)
 - Maximum Operating Pressure: 6000 psi
 - Thread Standard: NPT
 - Thread Size: 1/2 in



3245004 B6BI

RS PRO STAINLESS STEEL HYDRAULIC BALL VALVE G 1/2

- ขนาดบรรจุภัณฑ์: 1 x EA
- Manufacturer Series: B6BI
 - Number of Ports: 2-way
 - Connection Port Thread: G 1/2
 - Body Material: Stainless Steel
 - Seal Material: PTFE (Stem Seal), Teflon/kel-F (Ball Seal)
 - Maximum Operating Pressure: 6000 psi
 - Thread Standard: G
 - Thread Size: 1/2 in



3245032 B6BI

VALVE,BALL,HYDRAULIC,MHA,LOCKIN G KITS,1/4IN-1/2IN

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: Steel



4075446 Steel

VALVE,IN LINE,NON RETURN,HYDRAULIC,1/4IN

- ขนาดบรรจุภัณฑ์: 1 x EA
- Manufacturer Series: FT260
 - Maximum Operating Pressure: 350 bar
 - Maximum Flow Rate: 15 L/min
 - Minimum Operating Temperature: -20 °C
 - Maximum Operating Temperature: +100 °C
 - Thread Size: 1/4 in
 - Connection Port Thread: G 1/4
 - Body Material: Steel



2838295 FT260

VALVE,IN LINE,NON RETURN,HYDRAULIC,3/8IN

- ขนาดบรรจุภัณฑ์: 1 x EA
- Manufacturer Series: FT260
 - Maximum Operating Pressure: 350 bar
 - Maximum Flow Rate: 30 L/min
 - Minimum Operating Temperature: -20 °C
 - Maximum Operating Temperature: +100 °C
 - Thread Size: 3/8 in
 - Connection Port Thread: G 3/8
 - Body Material: Steel



2838302 FT260

VALVE, IN LINE, NON RETURN, HYDRAULIC, 1/2 IN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Manufacturer Series: FT260
 - Maximum Operating Pressure: 350 bar
 - Maximum Flow Rate: 55 L/min
 - Minimum Operating Temperature: -20 °C
 - Maximum Operating Temperature: +100 °C
 - Thread Size: 1/2 in
 - Connection Port Thread: G 1/2
 - Body Material: Steel



2838318 FT260

RS PRO STEEL INLINE MOUNTING, HYDRAULIC CHECK VALVE, G 3/4,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Manufacturer Series: FT260
 - Maximum Operating Pressure: 350 bar
 - Maximum Flow Rate: 80 L/min
 - Minimum Operating Temperature: -20 °C
 - Maximum Operating Temperature: +100 °C
 - Thread Size: 3/4 in
 - Connection Port Thread: G 3/4
 - Body Material: Steel



2838324 FT260

RS PRO STAINLESS STEEL, STEEL INLINE MOUNTING, HYDRAULIC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Manufacturer Series: FT257
 - Maximum Operating Pressure: 400 bar
 - Maximum Flow Rate: 110 L/min
 - Minimum Operating Temperature: -20 °C
 - Maximum Operating Temperature: +200 °C
 - Thread Size: 1/4 in
 - Connection Port Thread: BSP 1/4
 - Body Material: Stainless Steel, Steel



3244944 FT257

RS PRO STAINLESS STEEL, STEEL INLINE MOUNTING, HYDRAULIC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Manufacturer Series: FT257
 - Maximum Operating Pressure: 400 bar
 - Maximum Flow Rate: 40 L/min
 - Minimum Operating Temperature: -20 °C
 - Maximum Operating Temperature: +200 °C
 - Thread Size: 3/8 in
 - Connection Port Thread: BSP 3/8
 - Body Material: Stainless Steel, Steel



3244950 FT257

RS PRO STAINLESS STEEL, STEEL INLINE MOUNTING, HYDRAULIC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Manufacturer Series: FT257
 - Maximum Operating Pressure: 400 bar
 - Maximum Flow Rate: 90 L/min
 - Minimum Operating Temperature: -20 °C
 - Maximum Operating Temperature: +200 °C
 - Thread Size: 3/4 in
 - Connection Port Thread: BSP 3/4
 - Body Material: Stainless Steel, Steel



3244972 FT257

HYDRAULIC, SPIN ON, 10 MICRON ELEMENT, FILTER, ON, PAPER, 9

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Filtration Size: 10 µm
 - Maximum Flow Rate: 65 L/min
 - Connection Thread: G 3/4
 - Maximum Operating Pressure: 12 bar
 - Thread Standard: G
 - Thread Size: 3/4 in
 - Maximum Operating Temperature: +100 °C
 - Minimum Operating Temperature: -32 °C



512544 10 µm

RS PRO 12 BAR 1-1/4 IN HYDRAULIC SPIN-ON FILTER CAN, 95L/MIN MAX,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Filtration Size: 10 µm
 - Maximum Flow Rate: 95 L/min
 - Connection Thread: BSP 1-1/4 (Filter), G 1-1/4 (Element)
 - Maximum Operating Pressure: 12 bar
 - Thread Standard: BSP (Filter), G (Element/Indicator)
 - Thread Size: 1-1/4 in
 - Maximum Operating Temperature: +100 °C
 - Minimum Operating Temperature: -32 °C



512578 10 µm

HYDRAULIC, SPIN ON, 10 MICRON ELEMENT, FILTER, ON, PAPER, 6

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Filtration Size: 10 µm
 - Maximum Flow Rate: 65 L/min
 - Connection Thread: BSP 3/4 (Filter), G 3/4 (Element)
 - Maximum Operating Pressure: 12 bar
 - Thread Standard: BSP (Filter), G (Element)
 - Thread Size: 3/4 in
 - Maximum Operating Temperature: +100 °C
 - Minimum Operating Temperature: -32 °C



512588 10 µm

RS PRO 12 BAR 1-1/4 IN HYDRAULIC SPIN-ON FILTER CAN, 95L/MIN MAX,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Filtration Size: 10 µm
 - Maximum Flow Rate: 95 L/min
 - Connection Thread: BSP 1-1/4 (Filter), G 1-1/4 (Element)
 - Maximum Operating Pressure: 12 bar
 - Thread Standard: BSP (Filter), G (Element)
 - Thread Size: 1-1/4 in
 - Maximum Operating Temperature: +100 °C
 - Minimum Operating Temperature: -32 °C



512617 10 µm

RS PRO 12 BAR 1-1/4 IN HYDRAULIC SPIN-ON FILTER CAN, 95L/MIN MAX,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Filtration Size: 10 µm
 - Maximum Flow Rate: 95 L/min
 - Connection Thread: G 1-1/4
 - Maximum Operating Pressure: 12 bar
 - Thread Standard: G
 - Thread Size: 1-1/4 in
 - Maximum Operating Temperature: +100 °C
 - Minimum Operating Temperature: -32 °C



512635 10 µm

RS PRO 12 BAR 3/4 IN HYDRAULIC SPIN-ON FILTER CAN, 65L/MIN MAX,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Filtration Size: 10 µm
 - Maximum Flow Rate: 65 L/min
 - Connection Thread: BSP 3/4 (Filter), G 3/4 (Element)
 - Maximum Operating Pressure: 12 bar
 - Thread Standard: BSP (Filter), G (Element/Indicator)
 - Thread Size: 3/4 in
 - Maximum Operating Temperature: +100 °C
 - Minimum Operating Temperature: -32 °C



512667 10 µm

RS PRO REPLACEMENT HYDRAULIC FILTER ELEMENT, 20MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Manufacturer Series: SP
 - Filtration Size: 20 µm
 - Maximum Flow Rate: 401 L/min
 - Overall Length: 115 mm
 - Overall Diameter: 49.5 mm
 - Maximum Operating Pressure: 420 bar



512645 SP

RS PRO REPLACEMENT HYDRAULIC FILTER ELEMENT, 10MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Manufacturer Series: SP
 - Filtration Size: 10 µm
 - Maximum Flow Rate: 35 L/min
 - Overall Length: 112.5 mm
 - Overall Diameter: 45.5 mm
 - Maximum Operating Pressure: 420 bar



512651 SP

RS PRO REPLACEMENT HYDRAULIC FILTER ELEMENT, 10MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Manufacturer Series: SE
 - Filtration Size: 10 µm
 - Maximum Flow Rate: 20 L/min
 - Overall Length: 94.5 mm
 - Overall Diameter: 35 mm
 - Maximum Operating Pressure: 420 bar



512702 SE

RS PRO REPLACEMENT HYDRAULIC FILTER ELEMENT, 10MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Manufacturer Series: SP
 - Filtration Size: 10 µm
 - Maximum Flow Rate: 250 L/min
 - Overall Length: 114 mm
 - Overall Diameter: 80 mm
 - Maximum Operating Pressure: 420 bar



512720 SP

RS PRO REPLACEMENT HYDRAULIC FILTER ELEMENT, 10MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Manufacturer Series: SE
 - Filtration Size: 10 µm
 - Maximum Flow Rate: 30 L/min
 - Overall Length: 89 mm
 - Overall Diameter: 44.5 mm
 - Maximum Operating Pressure: 420 bar



512730 SE

RS PRO REPLACEMENT HYDRAULIC FILTER ELEMENT, 10MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Manufacturer Series: SE
 - Filtration Size: 10 µm
 - Maximum Flow Rate: 58 L/min
 - Overall Length: 156.5 mm
 - Overall Diameter: 44.5 mm
 - Maximum Operating Pressure: 420 bar



512736 SE

VALVE, NEEDLE, HYDRAULIC, 350 BAR, 1/4" IN BSP

- ขนาดบรรจุภัณฑ์: 1 x EA
- Manufacturer Series: NDV
 - Connection Port Thread: G 1/4
 - Maximum Flow Rate: 50 L/min
 - Body Material: Steel
 - Seal Material: Nitrile Rubber
 - Maximum Operating Pressure: 350 bar
 - Thread Size: 1/4 in
 - Thread Standard: G



2435521 NDV

RS PRO INLINE MOUNTING HYDRAULIC FLOW CONTROL VALVE,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Manufacturer Series: NDV
 - Connection Port Thread: G 3/8
 - Maximum Flow Rate: 75 L/min
 - Body Material: Steel
 - Seal Material: Nitrile Rubber
 - Maximum Operating Pressure: 350 bar
 - Thread Size: 3/8 in
 - Thread Standard: G



2435537 NDV

RS PRO INLINE MOUNTING HYDRAULIC FLOW CONTROL VALVE,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Manufacturer Series: NDV
 - Connection Port Thread: G 1/2
 - Maximum Flow Rate: 140 L/min
 - Body Material: Steel
 - Seal Material: Nitrile Rubber
 - Maximum Operating Pressure: 350 bar
 - Thread Size: 1/2 in
 - Thread Standard: G



2435543 NDV

RS PRO INLINE MOUNTING HYDRAULIC FLOW CONTROL VALVE,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Manufacturer Series: NDV
 - Connection Port Thread: G 3/4
 - Maximum Flow Rate: 175 L/min
 - Body Material: Steel
 - Seal Material: Nitrile Rubber
 - Maximum Operating Pressure: 350 bar
 - Thread Size: 3/4 in
 - Thread Standard: G



2435559 NDV

RS PRO INLINE MOUNTING HYDRAULIC FLOW CONTROL VALVE,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Manufacturer Series: NDRV
 - Connection Port Thread: G 1/4
 - Maximum Flow Rate: 50 L/min
 - Body Material: Steel
 - Seal Material: Nitrile Rubber
 - Maximum Operating Pressure: 350 bar
 - Thread Size: 1/4 in
 - Thread Standard: G



2435571 NDRV

VALVE, FLOW CONTROL, HYDRAULIC, 350 BAR, 3/8 IN

- ขนาดบรรจุภัณฑ์: 1 x EA
- Manufacturer Series: NDRV
 - Connection Port Thread: G 3/8
 - Maximum Flow Rate: 75 L/min
 - Body Material: Steel
 - Seal Material: Nitrile Rubber
 - Maximum Operating Pressure: 350 bar
 - Thread Size: 3/8 in
 - Thread Standard: G



2435587 NDRV

RS PRO INLINE MOUNTING HYDRAULIC FLOW CONTROL VALVE,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Manufacturer Series: NDRV
 - Connection Port Thread: G 1/2
 - Maximum Flow Rate: 140 L/min
 - Body Material: Steel
 - Seal Material: Nitrile Rubber
 - Maximum Operating Pressure: 350 bar
 - Thread Size: 1/2 in
 - Thread Standard: G



2435593 NDRV

RS PRO INLINE MOUNTING HYDRAULIC FLOW CONTROL VALVE,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Manufacturer Series: NDRV
 - Connection Port Thread: G 3/4
 - Maximum Flow Rate: 175 L/min
 - Body Material: Steel
 - Seal Material: Nitrile Rubber
 - Maximum Operating Pressure: 350 bar
 - Thread Size: 3/4 in
 - Thread Standard: G



2435600 NDRV

RS PRO INLINE MOUNTING HYDRAULIC FLOW CONTROL VALVE,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Manufacturer Series: FT1251/2
 - Connection Port Thread: BSP 3/8
 - Maximum Flow Rate: 30 L/min
 - Body Material: Nickel Plated Brass
 - Seal Material: Nitrile Rubber
 - Maximum Operating Pressure: 210 bar
 - Thread Size: 3/8 in
 - Thread Standard: BSP



2833997 FT1251/2

VALVE, NEEDLE, HYDRAULIC, IN LINE, DOUBLE ACTING, 1/2 IN BSP, 210

- ขนาดบรรจุภัณฑ์: 1 x EA
- Manufacturer Series: FT1251/2
 - Connection Port Thread: BSP 1/2
 - Maximum Flow Rate: 50 L/min
 - Body Material: Nickel Plated Brass
 - Seal Material: Nitrile Rubber
 - Maximum Operating Pressure: 210 bar
 - Thread Size: 1/2 in
 - Thread Standard: BSP



2834007 FT1251/2

RS PRO INLINE MOUNTING HYDRAULIC FLOW CONTROL VALVE,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Manufacturer Series: FT1251/5
 - Connection Port Thread: G 1/2
 - Maximum Flow Rate: 50 L/min
 - Body Material: Nickel Plated Brass
 - Seal Material: Nitrile Rubber
 - Maximum Operating Pressure: 210 bar
 - Thread Size: 1/2 in
 - Thread Standard: G



2834035 FT1251/5

VALVE, NEEDLE, HYDRAULIC, IN LINE, DOUBLE ACTING, 1/4 IN BSP, 210

- ขนาดบรรจุภัณฑ์: 1 x EA
- Manufacturer Series: FT1251/2
 - Connection Port Thread: BSP 1/4
 - Maximum Flow Rate: 20 L/min
 - Body Material: Nickel Plated Brass
 - Seal Material: Nitrile Rubber
 - Maximum Operating Pressure: 210 bar
 - Thread Size: 1/4 in
 - Thread Standard: BSP



2838289 FT1251/2

RS PRO INLINE MOUNTING HYDRAULIC FLOW CONTROL VALVE,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Manufacturer Series: F
 - Connection Port Thread: G 1/2
 - Maximum Flow Rate: 40 L/min
 - Body Material: Carbon Steel
 - Seal Material: PTFE
 - Maximum Operating Pressure: 700 bar
 - Thread Size: 1/2 in
 - Thread Standard: G



2975906 F

RS PRO INLINE MOUNTING HYDRAULIC FLOW CONTROL VALVE,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Manufacturer Series: F
 - Connection Port Thread: NPT 1/4
 - Maximum Flow Rate: 40 L/min
 - Body Material: Carbon Steel
 - Seal Material: PTFE
 - Maximum Operating Pressure: 700 bar
 - Thread Size: 1/4 in
 - Thread Standard: NPT



2975928 F

RS PRO INLINE MOUNTING HYDRAULIC FLOW CONTROL VALVE,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Manufacturer Series: F
 - Connection Port Thread: NPT 3/8
 - Maximum Flow Rate: 40 L/min
 - Body Material: Carbon Steel
 - Seal Material: PTFE
 - Maximum Operating Pressure: 700 bar
 - Thread Size: 3/8 in
 - Thread Standard: NPT



2975934 F

RS PRO INLINE MOUNTING HYDRAULIC FLOW CONTROL VALVE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Manufacturer Series: F
 - Connection Port Thread: NPT 1/2
 - Maximum Flow Rate: 40 L/min
 - Body Material: Carbon Steel
 - Seal Material: PTFE
 - Maximum Operating Pressure: 700 bar
 - Thread Size: 1/2 in
 - Thread Standard: NPT



2975940 F

RS PRO INLINE MOUNTING HYDRAULIC FLOW CONTROL VALVE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Manufacturer Series: VBRF
 - Connection Port Thread: G 1/2
 - Maximum Flow Rate: 45 L/min
 - Body Material: Carbon Steel
 - Seal Material: Nitrile Rubber
 - Maximum Operating Pressure: 350 bar
 - Thread Size: 1/2 in
 - Thread Standard: G



3635930 VBRF

RS PRO INLINE MOUNTING HYDRAULIC FLOW CONTROL VALVE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Connection Port Thread: G 1/8
 - Maximum Flow Rate: 7.8 L/min
 - Body Material: Steel
 - Seal Material: Nitrile Rubber
 - Thread Size: 1/8 in
 - Thread Standard: G
 - Maximum Operating Temperature: +100 °C
 - Minimum Operating Temperature: -20 °C



3907667 G 1/8

RS PRO INLINE MOUNTING HYDRAULIC FLOW CONTROL VALVE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Manufacturer Series: FT257
 - Connection Port Thread: G 1/4
 - Maximum Flow Rate: 25 L/min
 - Body Material: Carbon Steel
 - Seal Material: Nitrile Rubber
 - Maximum Operating Pressure: 400 bar
 - Thread Size: 1/4 in
 - Thread Standard: G



3907673 FT257

RS PRO INLINE MOUNTING HYDRAULIC FLOW CONTROL VALVE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Manufacturer Series: FT257
 - Connection Port Thread: G 3/8
 - Maximum Flow Rate: 60 L/min
 - Body Material: Carbon Steel
 - Seal Material: Nitrile Rubber
 - Maximum Operating Pressure: 400 bar
 - Thread Size: 3/8 in
 - Thread Standard: G



3907689 FT257

RS PRO INLINE MOUNTING HYDRAULIC FLOW CONTROL VALVE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Manufacturer Series: FT257
 - Connection Port Thread: G 1/2
 - Maximum Flow Rate: 75 L/min
 - Body Material: Carbon Steel
 - Seal Material: Nitrile Rubber
 - Maximum Operating Pressure: 400 bar
 - Thread Size: 1/2 in
 - Thread Standard: G



3907695 FT257

RS PRO INLINE MOUNTING HYDRAULIC FLOW CONTROL VALVE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Connection Port Thread: G 1/8
 - Maximum Flow Rate: 6.2 L/min
 - Body Material: Steel
 - Seal Material: Nitrile Rubber
 - Thread Size: 1/8 in
 - Thread Standard: G
 - Maximum Operating Temperature: +100 °C
 - Minimum Operating Temperature: -20 °C



3907724 G 1/8

RS PRO INLINE MOUNTING HYDRAULIC FLOW CONTROL VALVE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Connection Port Thread: G 1/4
 - Maximum Flow Rate: 13.5 L/min
 - Body Material: Steel
 - Seal Material: Nitrile Rubber
 - Thread Size: 1/4 in
 - Thread Standard: G
 - Maximum Operating Temperature: +100 °C
 - Minimum Operating Temperature: -20 °C



3907730 G 1/4

500MM GALVANIZED STEEL WIRE HYDRAULIC HOSE ASSEMBLY, 190BAR

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Overall Length: 500 mm
 - Inside Diameter: 1/4 in
 - Connector A: Straight G 1/4 Female
 - Connector B: Straight G 1/4 Female
 - Inner Hose Material: Synthetic Rubber
 - Reinforcing Material: Steel
 - Cover Material: Galvanized Steel Wire
 - Maximum Operating Pressure: 190 bar



1102243 500 mm

1000MM GALVANIZED STEEL WIRE HYDRAULIC HOSE ASSEMBLY, 190BAR

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Overall Length: 1000 mm
 - Inside Diameter: 1/4 in
 - Connector A: Straight G 1/4 Female
 - Connector B: Straight G 1/4 Female
 - Inner Hose Material: Synthetic Rubber
 - Reinforcing Material: Steel
 - Cover Material: Galvanized Steel Wire
 - Maximum Operating Pressure: 190 bar



1102245 1000 mm

1500MM GALVANIZED STEEL WIRE HYDRAULIC HOSE ASSEMBLY, 190BAR

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Overall Length: 1500 mm
 - Inside Diameter: 1/4 in
 - Connector A: Straight G 1/4 Female
 - Connector B: Straight G 1/4 Female
 - Inner Hose Material: Synthetic Rubber
 - Reinforcing Material: Steel
 - Cover Material: Galvanized Steel Wire
 - Maximum Operating Pressure: 190 bar



1102246 1500 mm

2000MM GALVANIZED STEEL WIRE HYDRAULIC HOSE ASSEMBLY, 190BAR

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Overall Length: 2000 mm
 - Inside Diameter: 1/4 in
 - Connector A: Straight G 1/4 Female
 - Connector B: Straight G 1/4 Female
 - Inner Hose Material: Synthetic Rubber
 - Reinforcing Material: Steel
 - Cover Material: Galvanized Steel Wire
 - Maximum Operating Pressure: 190 bar



1102247 2000 mm

500MM GALVANIZED STEEL WIRE HYDRAULIC HOSE ASSEMBLY, 155BAR

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Overall Length: 500 mm
 - Inside Diameter: 3/8 in
 - Connector A: Straight G 3/8 Female
 - Connector B: Straight G 3/8 Female
 - Inner Hose Material: Synthetic Rubber
 - Reinforcing Material: Steel
 - Cover Material: Galvanized Steel Wire
 - Maximum Operating Pressure: 155 bar



1102248 500 mm

1000MM GALVANIZED STEEL WIRE HYDRAULIC HOSE ASSEMBLY, 155BAR

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Overall Length: 1000 mm
 - Inside Diameter: 3/8 in
 - Connector A: Straight G 3/8 Female
 - Connector B: Straight G 3/8 Female
 - Inner Hose Material: Synthetic Rubber
 - Reinforcing Material: Steel
 - Cover Material: Galvanized Steel Wire
 - Maximum Operating Pressure: 155 bar



1102250 1000 mm

2000MM GALVANIZED STEEL WIRE HYDRAULIC HOSE ASSEMBLY, 155BAR

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Overall Length: 2000 mm
 - Inside Diameter: 3/8 in
 - Connector A: Straight G 3/8 Female
 - Connector B: Straight G 3/8 Female
 - Inner Hose Material: Synthetic Rubber
 - Reinforcing Material: Steel
 - Cover Material: Galvanized Steel Wire
 - Maximum Operating Pressure: 155 bar



1102251 2000 mm

750MM GALVANIZED STEEL WIRE HYDRAULIC HOSE ASSEMBLY, 140BAR

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Overall Length: 750 mm
 - Inside Diameter: 1/2 in
 - Connector A: Straight G 1/2 Female
 - Connector B: Straight G 1/2 Female
 - Inner Hose Material: Synthetic Rubber
 - Reinforcing Material: Steel
 - Cover Material: Galvanized Steel Wire
 - Maximum Operating Pressure: 140 bar



1102253 750 mm

1000MM GALVANIZED STEEL WIRE HYDRAULIC HOSE ASSEMBLY, 140BAR

- ขนาดบรรจุภัณฑ์: 1 x EA
- Overall Length: 1000 mm
 - Inside Diameter: 1/2 in
 - Connector A: Straight G 1/2 Female
 - Connector B: Straight G 1/2 Female
 - Inner Hose Material: Synthetic Rubber
 - Reinforcing Material: Steel
 - Cover Material: Galvanized Steel Wire
 - Maximum Operating Pressure: 140 bar



1102385 1000 mm

2000MM GALVANIZED STEEL WIRE HYDRAULIC HOSE ASSEMBLY, 140BAR

- ขนาดบรรจุภัณฑ์: 1 x EA
- Overall Length: 2000 mm
 - Inside Diameter: 1/2 in
 - Connector A: Straight G 1/2 Female
 - Connector B: Straight G 1/2 Female
 - Inner Hose Material: Synthetic Rubber
 - Reinforcing Material: Steel
 - Cover Material: Galvanized Steel Wire
 - Maximum Operating Pressure: 140 bar



1103013 2000 mm

1000MM GALVANIZED STEEL WIRE HYDRAULIC HOSE ASSEMBLY, 85BAR

- ขนาดบรรจุภัณฑ์: 1 x EA
- Overall Length: 1000 mm
 - Inside Diameter: 3/4 in
 - Connector A: Straight G 3/4 Female
 - Connector B: Straight G 3/4 Female
 - Inner Hose Material: Synthetic Rubber
 - Reinforcing Material: Steel
 - Cover Material: Galvanized Steel Wire
 - Maximum Operating Pressure: 85 bar



1103867 1000 mm

RS PRO BC SERIES 12V DC HYDRAULIC OIL COOLER, 25 TO

- ขนาดบรรจุภัณฑ์: 1 x EA
- Manufacturer Series: BC
 - Maximum Flow Rate: 25 to 100 L/min
 - Voltage: 12 V dc
 - Maximum Operating Pressure: 16 (Dynamic) bar, 25 (Static) bar
 - Dimensions: 322.5 x 277 x 167 mm
 - Weight: 6 kg
 - Thread Standard: BSP
 - Depth: 167 mm



8625629 BC

RS PRO SINGLE TUBE CLAMP

- ขนาดบรรจุภัณฑ์: 5 x EA
- Number of Tubes Held: Single
 - For Tube Outside Diameter: 6.4 mm
 - Clamp Spacing: 1 m
 - Body Material: PP
 - Maximum Operating Temperature: +90 °C
 - Minimum Operating Temperature: -30 °C
 - Maximum Tube Outer Diameter: 6.4 mm



1459751 Single

RS PRO SINGLE TUBE CLAMP

- ขนาดบรรจุภัณฑ์: 5 x EA
- Number of Tubes Held: Single
 - For Tube Outside Diameter: 6 mm
 - Clamp Spacing: 1 m
 - Body Material: PP
 - Maximum Operating Temperature: +90 °C
 - Minimum Operating Temperature: -30 °C
 - Maximum Tube Outer Diameter: 6 mm



1459752 Single

RS PRO SINGLE TUBE CLAMP

- ขนาดบรรจุภัณฑ์: 5 x EA
- Number of Tubes Held: Single
 - For Tube Outside Diameter: 8 mm
 - Clamp Spacing: 1 m
 - Body Material: PP
 - Maximum Operating Temperature: +90 °C
 - Minimum Operating Temperature: -30 °C
 - Maximum Tube Outer Diameter: 8 mm



1459754 Single

RS PRO DOUBLE TUBE CLAMP

- ขนาดบรรจุภัณฑ์: 5 x EA
- Number of Tubes Held: Double
 - For Tube Outside Diameter: 8 mm
 - Clamp Spacing: 1 m
 - Body Material: PP
 - Maximum Operating Temperature: +90 °C
 - Minimum Operating Temperature: -30 °C
 - Maximum Tube Outer Diameter: 8 mm



1459755 Double

RS PRO SINGLE TUBE CLAMP

- ขนาดบรรจุภัณฑ์: 5 x EA
- Number of Tubes Held: Single
 - For Tube Outside Diameter: 9 mm
 - Clamp Spacing: 1 m
 - Body Material: PP
 - Maximum Operating Temperature: +90 °C
 - Minimum Operating Temperature: -30 °C
 - Maximum Tube Outer Diameter: 9 mm



1459756 Single

RS PRO SINGLE TUBE CLAMP

- ขนาดบรรจุภัณฑ์: 5 x EA
- Number of Tubes Held: Single
 - For Tube Outside Diameter: 10 mm
 - Clamp Spacing: 1.2 m
 - Body Material: PP
 - Maximum Operating Temperature: +90 °C
 - Minimum Operating Temperature: -30 °C
 - Maximum Tube Outer Diameter: 10 mm



1459757 Single

RS PRO SINGLE TUBE CLAMP

- ขนาดบรรจุภัณฑ์: 5 x EA
- Number of Tubes Held: Single
 - For Tube Outside Diameter: 12 mm
 - Clamp Spacing: 1.2 m
 - Body Material: PP
 - Maximum Operating Temperature: +90 °C
 - Minimum Operating Temperature: -30 °C
 - Maximum Tube Outer Diameter: 12 mm



1459759 Single

RS PRO DOUBLE TUBE CLAMP

- ขนาดบรรจุภัณฑ์: 5 x EA
- Number of Tubes Held: Double
 - For Tube Outside Diameter: 12 mm
 - Clamp Spacing: 1.2 m
 - Body Material: PP
 - Maximum Operating Temperature: +90 °C
 - Minimum Operating Temperature: -30 °C
 - Maximum Tube Outer Diameter: 12 mm



1459760 Double

RS PRO SINGLE TUBE CLAMP

- ขนาดบรรจุภัณฑ์: 5 x EA
- Number of Tubes Held: Single
 - For Tube Outside Diameter: 12.7 mm
 - Clamp Spacing: 1.2 m
 - Body Material: PP
 - Maximum Operating Temperature: +90 °C
 - Minimum Operating Temperature: -30 °C
 - Maximum Tube Outer Diameter: 12 mm



1459761 Single

RS PRO DOUBLE TUBE CLAMP

- ขนาดบรรจุภัณฑ์: 5 x EA
- Number of Tubes Held: Double
 - For Tube Outside Diameter: 15 mm
 - Clamp Spacing: 1.2 m
 - Body Material: PP
 - Maximum Operating Temperature: +90 °C
 - Minimum Operating Temperature: -30 °C
 - Maximum Tube Outer Diameter: 15 mm



1459763 Double

RS PRO SINGLE TUBE CLAMP

- ขนาดบรรจุภัณฑ์: 5 x EA
- Number of Tubes Held: Single
 - For Tube Outside Diameter: 15 mm
 - Clamp Spacing: 1.2 m
 - Body Material: PP
 - Maximum Operating Temperature: +90 °C
 - Minimum Operating Temperature: -30 °C
 - Maximum Tube Outer Diameter: 15 mm



1459764 Single

RS PRO SINGLE TUBE CLAMP

- ขนาดบรรจุภัณฑ์: 5 x EA
- Number of Tubes Held: Single
 - For Tube Outside Diameter: 16 mm
 - Clamp Spacing: 1.2 m
 - Body Material: PP
 - Maximum Operating Temperature: +90 °C
 - Minimum Operating Temperature: -30 °C
 - Maximum Tube Outer Diameter: 16 mm



1459765 Single

CLAMP, HOSE, SINGLE, 38MM

ขนาดบรรจุภัณฑ์: 5 x EA

- Number of Tubes Held: Single
- For Tube Outside Diameter: 38 mm
- Clamp Spacing: 2 m
- Body Material: PP
- Maximum Operating Temperature: +90 °C
- Minimum Operating Temperature: -30 °C
- Maximum Tube Outer Diameter: 38 mm



4141509 Single

RS PRO HYDRAULIC PRESSURE GAUGE ISOLATION VALVE, G 1/4

ขนาดบรรจุภัณฑ์: 1 x EA

- Orientation: In Line
- Connection Port Thread: G 1/4 Male
- Body Material: Carbon Steel
- Maximum Operating Pressure: 400 bar
- Minimum Operating Temperature: -20 °C
- Thread Diameter: 1/4 in
- Thread Gender: Male
- Thread Standard: G



2788774 In Line

VALVE, HYDRAULIC, GAUGE, ANGLED, ISOLATOR, 1/4 IN BSP SWIVEL FEMALE-

ขนาดบรรจุภัณฑ์: 1 x EA

- Orientation: Angled
- Connection Port Thread: G 1/4 Male
- Body Material: Carbon Steel
- Maximum Operating Pressure: 400 bar
- Minimum Operating Temperature: -20 °C
- Thread Diameter: 1/4 in
- Thread Gender: Male
- Thread Standard: G



2788780 Angled

RS PRO HYDRAULIC PRESSURE GAUGE ISOLATION VALVE, G 1/4

ขนาดบรรจุภัณฑ์: 1 x EA

- Orientation: In Line
- Connection Port Thread: G 1/4 Female
- Body Material: Carbon Steel
- Maximum Operating Pressure: 400 bar
- Minimum Operating Temperature: -20 °C
- Thread Diameter: 1/4 in
- Thread Gender: Female
- Thread Standard: G



2788803 In Line

VALVE, HYDRAULIC, GAUGE, ANGLED, ISOLATOR, 1/4 IN BSP SWIVEL FEMALE-

ขนาดบรรจุภัณฑ์: 1 x EA

- Orientation: Angled
- Connection Port Thread: G 1/4 Female
- Body Material: Carbon Steel
- Maximum Operating Pressure: 400 bar
- Minimum Operating Temperature: -20 °C
- Thread Diameter: 1/4 in
- Thread Gender: Female
- Thread Standard: G



2789086 Angled

RS PRO HYDRAULIC PRESSURE SENSOR, BSP 1/4, M2 (DIN PLUG),

ขนาดบรรจุภัณฑ์: 1 x EA

- Input Connection Thread: BSP 1/4
- Output Connection Type: M2 (Din Plug)
- Maximum Pressure: 50 bar
- Minimum Pressure: 5 bar
- Minimum Operating Temperature: -25 °C
- Maximum Operating Temperature: +85 °C
- Input Connection Thread Standard: BSP
- Input Connection Thread Size: 1/4 in



8802283 BSP 1/4

RS PRO HYDRAULIC PRESSURE SENSOR, BSP 1/4, M2 (DIN PLUG),

ขนาดบรรจุภัณฑ์: 1 x EA

- Input Connection Thread: BSP 1/4
- Output Connection Type: M2 (Din Plug)
- Maximum Pressure: 100 bar
- Minimum Pressure: 10 bar
- Minimum Operating Temperature: -25 °C
- Maximum Operating Temperature: +85 °C
- Input Connection Thread Standard: BSP
- Input Connection Thread Size: 1/4 in



8802292 BSP 1/4

RS PRO HYDRAULIC PRESSURE SENSOR, BSP 1/4, M2 (DIN PLUG),

ขนาดบรรจุภัณฑ์: 1 x EA

- Input Connection Thread: BSP 1/4
- Output Connection Type: M2 (Din Plug)
- Maximum Pressure: 200 bar
- Minimum Pressure: 20 bar
- Minimum Operating Temperature: -25 °C
- Maximum Operating Temperature: +85 °C
- Input Connection Thread Standard: BSP
- Input Connection Thread Size: 1/4 in



8802295 BSP 1/4

RS PRO CARBON STEEL MALE HYDRAULIC QUICK CONNECT

ขนาดบรรจุภัณฑ์: 1 x EA

- Series: RS
- Compatible With: ISO-DIS 16028
- Type: Union
- Coupling Gender: Male
- Locking Style: Screw Lock
- Thread: Rs 3/8 Male
- Material: Carbon Steel
- Finish: Yellow Passivated, Zinc Plated



7335625 RS

RS PRO CARBON STEEL MALE HYDRAULIC QUICK CONNECT

ขนาดบรรจุภัณฑ์: 1 x EA

- Series: RS
- Compatible With: ISO-DIS 16028
- Type: Union
- Coupling Gender: Male
- Locking Style: Screw Lock
- Thread: Rs 1/2 Male
- Material: Carbon Steel
- Finish: Yellow Passivated, Zinc Plated



7335637 RS

1/2 IN BSP FEMALE SELF SEALING COUPLER

ขนาดบรรจุภัณฑ์: 1 x EA

- Compatible With: Faster ANV Series, Hansen HA 15000 (Gromelle), Intertraco A Series, Safeway S565, Stucchi BIR Series
- Type: Union
- Coupling Gender: Female
- Locking Style: Ball Lock
- Thread: BSP 1/2 Female
- Material: Steel
- Finish: Yellow Passivated, Zinc Plated
- Seal Material: Nitrile Rubber



7454693 Faster ANV

RS PRO STEEL FEMALE HYDRAULIC QUICK CONNECT COUPLING, BSP

ขนาดบรรจุภัณฑ์: 1 x EA

- Compatible With: Faster ANV Series, Hansen HA 15000 (Gromelle), Intertraco A Series, Safeway S565, Stucchi BIR Series
- Type: Union
- Coupling Gender: Female
- Locking Style: Ball Lock
- Thread: BSP 3/4 Female
- Material: Steel
- Finish: Yellow Passivated, Zinc Plated
- Seal Material: Nitrile Rubber



7454697 Faster ANV

1/4 IN BSP MALE SELF SEALING COUPLER

ขนาดบรรจุภัณฑ์: 1 x EA

- Compatible With: Faster ANV Series, Hansen HA 15000 (Gromelle), Intertraco A Series, Safeway S565, Stucchi BIR Series
- Type: Union
- Coupling Gender: Male
- Locking Style: Ball Lock
- Thread: BSP 1/4 Male
- Material: Steel
- Finish: Yellow Passivated, Zinc Plated
- Seal Material: Nitrile Rubber



7454700 Faster ANV

1/4 IN BSP FEMALE SELF SEALING COUPLER

ขนาดบรรจุภัณฑ์: 1 x EA

- Compatible With: Faster ANV Series, Hansen HA 15000 (Gromelle), Intertraco A Series, Safeway S565, Stucchi BIR Series
- Type: Union
- Coupling Gender: Female
- Locking Style: Ball Lock
- Thread: BSP 1/4 Female
- Material: Steel
- Finish: Yellow Passivated, Zinc Plated
- Seal Material: Nitrile Rubber



7454704 Faster ANV

RS PRO STEEL MALE HYDRAULIC QUICK CONNECT COUPLING, BSP

ขนาดบรรจุภัณฑ์: 1 x EA

- Compatible With: Faster ANV Series, Hansen HA 15000 (Gromelle), Intertraco A Series, Safeway S565, Stucchi BIR Series
- Type: Union
- Coupling Gender: Male
- Locking Style: Ball Lock
- Thread: BSP 3/4 Male
- Material: Steel
- Finish: Yellow Passivated, Zinc Plated
- Seal Material: Nitrile Rubber



7454707 Faster ANV

1/2 IN BSP MALE SELF SEALING COUPLER

ขนาดบรรจุภัณฑ์: 1 x EA

- Compatible With: Faster ANV Series, Hansen HA 15000 (Gromelle), Intertraco A Series, Safeway S565, Stucchi BIR Series
- Type: Union
- Coupling Gender: Male
- Locking Style: Ball Lock
- Thread: BSP 1/2 Male
- Material: Steel
- Finish: Yellow Passivated, Zinc Plated
- Seal Material: Nitrile Rubber



7454710 Faster ANV

RS PRO STEEL MALE HYDRAULIC QUICK CONNECT COUPLING, BSP 1

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Compatible With: Faster ANV Series, Hansen HA 15000 (Gromelle), Intertraco A Series, Safeway S565, Stucchi BIR Series
 - Type: Union
 - Coupling Gender: Male
 - Locking Style: Ball Lock
 - Thread: BSP 1 Male
 - Material: Steel
 - Finish: Yellow Passivated, Zinc Plated
 - Seal Material: Nitrile Rubber



7454713 Faster ANV

3/8IN BSP FEMALE SELF SEALING COUPLER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Compatible With: Faster ANV Series, Hansen HA 15000 (Gromelle), Intertraco A Series, Safeway S565, Stucchi BIR Series
 - Type: Union
 - Coupling Gender: Female
 - Locking Style: Ball Lock
 - Thread: BSP 3/8 Female
 - Material: Steel
 - Finish: Yellow Passivated, Zinc Plated
 - Seal Material: Nitrile Rubber



7454716 Faster ANV

3/8IN BSP MALE SELF SEALING COUPLER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Compatible With: Faster ANV Series, Hansen HA 15000 (Gromelle), Intertraco A Series, Safeway S565, Stucchi BIR Series
 - Type: Union
 - Coupling Gender: Male
 - Locking Style: Ball Lock
 - Thread: BSP 3/8 Male
 - Material: Steel
 - Finish: Yellow Passivated, Zinc Plated
 - Seal Material: Nitrile Rubber



7454722 Faster ANV

RS PRO STEEL FEMALE HYDRAULIC QUICK CONNECT COUPLING, BSP 1

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Compatible With: Faster ANV Series, Hansen HA 15000 (Gromelle), Intertraco A Series, Safeway S565, Stucchi BIR Series
 - Type: Union
 - Coupling Gender: Female
 - Locking Style: Ball Lock
 - Thread: BSP 1 Female
 - Material: Steel
 - Finish: Yellow Passivated, Zinc Plated
 - Seal Material: Nitrile Rubber



7454729 Faster ANV

RS PRO BRASS FEMALE HYDRAULIC QUICK CONNECT COUPLING, BSP 1/4

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Series: IRBO
 - Compatible With: ISO 7241-1-B
 - Type: Union
 - Coupling Gender: Female
 - Locking Style: Ball Lock
 - Thread: BSP 1/4 Female
 - Material: Brass
 - Seal Material: FMK



7685813 IRBO

RS PRO BRASS FEMALE HYDRAULIC QUICK CONNECT COUPLING, BSP 1/8

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Series: IRBO
 - Compatible With: ISO 7241-1-B
 - Type: Union
 - Coupling Gender: Female
 - Locking Style: Ball Lock
 - Thread: BSP 1/8 Female
 - Material: Brass
 - Seal Material: FMK



7685816 IRBO

RS PRO BRASS MALE HYDRAULIC QUICK CONNECT COUPLING, BSP 1/4

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Series: IRBO
 - Compatible With: ISO 7241-1-B
 - Type: Union
 - Coupling Gender: Male
 - Locking Style: Ball Lock
 - Thread: BSP 1/4 Male
 - Material: Brass
 - Seal Material: FMK



7685819 IRBO

RS PRO BRASS MALE HYDRAULIC QUICK CONNECT COUPLING, BSP

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Series: IRBO
 - Compatible With: ISO 7241-1-B
 - Type: Union
 - Coupling Gender: Male
 - Locking Style: Ball Lock
 - Thread: BSP 3/8 Male
 - Material: Brass
 - Seal Material: FMK



7685822 IRBO

RS PRO BRASS FEMALE HYDRAULIC QUICK CONNECT COUPLING, BSP

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Series: IRBO
 - Compatible With: ISO 7241-1-B
 - Type: Union
 - Coupling Gender: Female
 - Locking Style: Ball Lock
 - Thread: BSP 3/8 Female
 - Material: Brass
 - Seal Material: FMK



7685825 IRBO

RS PRO BRASS MALE HYDRAULIC QUICK CONNECT COUPLING, BSP 1/2

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Series: IRBO
 - Compatible With: ISO 7241-1-B
 - Type: Union
 - Coupling Gender: Male
 - Locking Style: Ball Lock
 - Thread: BSP 1/2 Male
 - Material: Brass
 - Seal Material: FMK



7685829 IRBO

RS PRO BRASS MALE HYDRAULIC QUICK CONNECT COUPLING, BSP

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Series: IRBO
 - Compatible With: ISO 7241-1-B
 - Type: Union
 - Coupling Gender: Male
 - Locking Style: Ball Lock
 - Thread: BSP 3/4 Male
 - Material: Brass
 - Seal Material: FMK



7685831 IRBO

RS PRO BRASS FEMALE HYDRAULIC QUICK CONNECT COUPLING, BSP

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Series: IRBO
 - Compatible With: ISO 7241-1-B
 - Type: Union
 - Coupling Gender: Female
 - Locking Style: Ball Lock
 - Thread: BSP 3/4 Female
 - Material: Brass
 - Seal Material: FMK



7685835 IRBO

RS PRO BRASS FEMALE HYDRAULIC QUICK CONNECT COUPLING, BSP 1/2

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Series: IRBO
 - Compatible With: ISO 7241-1-B
 - Type: Union
 - Coupling Gender: Female
 - Locking Style: Ball Lock
 - Thread: BSP 1/2 Female
 - Material: Brass
 - Seal Material: FMK



7685838 IRBO

RS PRO PRESSURE SWITCH, NPT 1/4 0.2BAR TO ¼ BAR

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Minimum Operating Pressure: 0.2 bar
 - Maximum Operating Pressure: ¼ bar
 - Pressure Type: Electro-Mechanical
 - Suitable Media: Compressed Air, Gas, Pneumatic
 - Connection: NPT 1/4
 - Connection Thread Size: 1/4
 - Connection Thread Standard: NPT
 - Minimum Operating Temperature: -10 °C



1366270 0.2 bar

RS PRO PRESSURE SWITCH, M12 X 1 0.5BAR TO 8 BAR

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Minimum Operating Pressure: 0.5 bar
 - Maximum Operating Pressure: 8 bar
 - Pressure Type: Electro-Mechanical
 - Suitable Media: Compressed Air, Gas, Pneumatic
 - Connection: M12 x 1
 - Voltage Rating: 30 V
 - Connection Thread Size: M12 x 1
 - Connection Thread Standard: NPT



1366271 0.5 bar

RS PRO PRESSURE SWITCH, M12 X 1 1BAR TO 16 BAR

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Minimum Operating Pressure: 1 bar
 - Maximum Operating Pressure: 16 bar
 - Pressure Type: Electro-Mechanical
 - Suitable Media: Compressed Air, Gas, Pneumatic
 - Connection: M12 x 1
 - Voltage Rating: 30 V
 - Connection Thread Size: M12 x 1
 - Connection Thread Standard: NPT



1366273 1 bar

RS PRO PRESSURE SWITCH, M12 X 1 0.2BAR TO 2 BAR

ขนาดบรรจุภัณฑ์: **1 x EA**

- Minimum Operating Pressure: 0.2 bar
- Maximum Operating Pressure: 2 bar
- Pressure Type: Electro-Mechanical
- Suitable Media: Gas, Liquid
- Connection: M12 x 1
- Voltage Rating: 30 V
- Connection Thread Size: M12 x 1
- Connection Thread Standard: NPT



1366275 0.2 bar

RS PRO PRESSURE SWITCH, M12 X 1 0.5BAR TO 8 BAR

ขนาดบรรจุภัณฑ์: **1 x EA**

- Minimum Operating Pressure: 0.5 bar
- Maximum Operating Pressure: 8 bar
- Pressure Type: Electro-Mechanical
- Suitable Media: Gas, Liquid
- Connection: M12 x 1
- Voltage Rating: 30 V
- Connection Thread Size: M12 x 1
- Connection Thread Standard: NPT



1366276 0.5 bar

RS PRO PRESSURE SWITCH, M12 X 1 1BAR TO 16 BAR

ขนาดบรรจุภัณฑ์: **1 x EA**

- Minimum Operating Pressure: 1 bar
- Maximum Operating Pressure: 16 bar
- Pressure Type: Electro-Mechanical
- Suitable Media: Gas, Liquid
- Connection: M12 x 1
- Voltage Rating: 30 V
- Connection Thread Size: M12 x 1
- Connection Thread Standard: NPT



1366277 1 bar

RS PRO PRESSURE SWITCH, G 1/4 0.2BAR TO 2.5 BAR

ขนาดบรรจุภัณฑ์: **1 x EA**

- Minimum Operating Pressure: 0.2 bar
- Maximum Operating Pressure: 2.5 bar
- Pressure Type: Positive Pressure
- Connection: G 1/4
- Type: Adjustable
- Voltage Rating: 250 V ac
- Connection Thread Size: 1/4 in
- Manufacturer Series: F4



2970046 0.2 bar

RS PRO PRESSURE SWITCH, G 1/4 1BAR TO 12 BAR

ขนาดบรรจุภัณฑ์: **1 x EA**

- Minimum Operating Pressure: 1 bar
- Maximum Operating Pressure: 12 bar
- Pressure Type: Positive Pressure
- Connection: G 1/4
- Type: Adjustable
- Voltage Rating: 250 V ac
- Connection Thread Size: 1/4 in
- Manufacturer Series: F4



2970052 1 bar

RS PRO PRESSURE SWITCH, G 1/4 1BAR TO 10 BAR

ขนาดบรรจุภัณฑ์: **1 x EA**

- Minimum Operating Pressure: 1 bar
- Maximum Operating Pressure: 10 bar
- Pressure Type: Positive Pressure
- Connection: G 1/4
- Type: Adjustable
- Voltage Rating: 250 V ac/dc
- Connection Thread Size: 1/4 in
- Manufacturer Series: K3



3635968 1 bar

RS PRO PRESSURE SWITCH, G 1/4 30BAR TO 250 BAR

ขนาดบรรจุภัณฑ์: **1 x EA**

- Minimum Operating Pressure: 30 bar
- Maximum Operating Pressure: 250 bar
- Pressure Type: Positive Pressure
- Connection: G 1/4
- Type: Adjustable
- Voltage Rating: 250 V ac/dc
- Connection Thread Size: 1/4 in
- Manufacturer Series: K3



3636006 30 bar

RS PRO PRESSURE SWITCH, 1/4 IN BSP MALE 1BAR TO 12 BAR

ขนาดบรรจุภัณฑ์: **1 x EA**

- Minimum Operating Pressure: 1 bar
- Maximum Operating Pressure: 12 bar
- Suitable Media: Fluid
- Connection: 1/4 in BSP Male
- Type: Adjustable
- Voltage Rating: 250 V ac
- Connection Thread Size: 1/4 in
- Manufacturer Series: F4



8802289 1 bar

RS PRO PRESSURE SWITCH, 1/4 IN BSP MALE 0.2BAR TO 2.5 BAR

ขนาดบรรจุภัณฑ์: **1 x EA**

- Minimum Operating Pressure: 0.2 bar
- Maximum Operating Pressure: 2.5 bar
- Suitable Media: Fluid
- Connection: 1/4 in BSP Male
- Type: Adjustable
- Voltage Rating: 250 V ac
- Connection Thread Size: 1/4 in
- Manufacturer Series: F4



8802299 0.2 bar

RS PRO BRASS AIR VENT

ขนาดบรรจุภัณฑ์: **1 x EA**

- Body Material: Brass
- Maximum Working Pressure: 6 bar
- Female Thread Size: 3/4 in
- Male Thread Size: 1/8 in
- Thread Standard: BSPT



2463318 Brass

RS PRO BRASS REDUCED BORE, 3 WAY, BALL VALVE, BSPP 12.7MM,

ขนาดบรรจุภัณฑ์: **1 x EA**

- Type: Reduced Bore, 3 Way
- Ball Material: Brass
- Attachment Type: Threaded
- Thread Standard: BSPP
- Thread Size: 12.7 mm
- Body Material: Brass
- Pipe Diameter: 14 mm
- Safe for Use With: Air, Oil, Steam, Water



486243 Reduced Bore, 3

PLUMBING, T PORT, FULL BORE, BALL VALVE, 1/4 IN BSP FEM

ขนาดบรรจุภัณฑ์: **1 x EA**

- Attachment Type: Threaded
- Threaded Connection: 1/4 in BSPP
- Body Material: Brass
- Thread Size: 1/4 in
- Safe for Use With: Air, Oil, Steam, Water
- Maximum Working Pressure: 30 bar
- Connection Size (mm): 8 mm
- Connection Size (inch): 1/4 in



486249 Threaded

RS PRO BRASS REDUCED BORE BALL VALVE 3/4 IN BSPP 3 WAY

ขนาดบรรจุภัณฑ์: **1 x EA**

- Attachment Type: Threaded
- Threaded Connection: 3/4 in BSPP
- Body Material: Brass
- Thread Size: 3/4 in
- Safe for Use With: Air, Oil, Steam, Water
- Maximum Working Pressure: 25 bar
- Connection Size (mm): 20 mm
- Connection Size (inch): 3/4 in



486287 Threaded

RS PRO BRASS REDUCED BORE, 2 WAY, BALL VALVE 15MM, 15MM

ขนาดบรรจุภัณฑ์: **1 x EA**

- Type: Reduced Bore, 2 Way
- Ball Material: Brass
- Attachment Type: Compression
- Thread Size: 15 mm
- Compression Fitting Size: 15 mm
- Body Material: Brass
- Safe for Use With: Gas, Oil, Petrol, Water
- Handle Type: Lever



486293 Reduced Bore, 2

RS PRO BRASS REDUCED BORE, 2 WAY, BALL VALVE, 15MM

ขนาดบรรจุภัณฑ์: **1 x EA**

- Type: Reduced Bore, 2 Way
- Ball Material: Brass
- Attachment Type: Compression
- Compression Fitting Size: 15 mm
- Body Material: Brass
- Safe for Use With: Water
- Handle Type: Lever
- Handle Material: PVC Coated Steel



486299 Reduced Bore, 2

RS PRO BRASS FULL BORE, 2 WAY, BALL VALVE, BSPP 28MM, 28MM

ขนาดบรรจุภัณฑ์: **1 x EA**

- Type: Full Bore, 2 Way
- Ball Material: Brass
- Attachment Type: Compression
- Thread Standard: BSPP
- Thread Size: 28 mm
- Compression Fitting Size: 28 mm
- Body Material: Brass
- Safe for Use With: Gas, Oil, Petrol, Water



486300 Full Bore, 2 Way

RS PRO BRASS REDUCED BORE, 3 WAY, BALL VALVE, BSPP 6.35MM,

ขนาดบรรจุภัณฑ์: **1 x EA**

- Type: Reduced Bore, 3 Way
- Ball Material: Brass
- Attachment Type: Threaded
- Thread Standard: BSPP
- Thread Size: 6.35 mm
- Body Material: Brass
- Pipe Diameter: 10 mm
- Safe for Use With: Air, Oil, Steam, Water



486312 Reduced Bore, 3

RS PRO BRASS REDUCED BORE BALL VALVE 3/4 IN BSP 3 WAY

ขนาดบรรจุภัณฑ์: **1 x EA**

- Attachment Type: Threaded
- Threaded Connection: 3/4 in BSP
- Body Material: Brass
- Thread Size: 3/4 in
- Safe for Use With: Air, Oil, Steam, Water
- Maximum Working Pressure: 25 bar
- Connection Size (mm): 20 mm
- Connection Size (inch): 3/4 in



486328 Threaded

RS PRO BRASS REDUCED BORE BALL VALVE 1/2 IN BSP 3 WAY

ขนาดบรรจุภัณฑ์: **1 x EA**

- Attachment Type: Threaded
- Threaded Connection: 1/2 in BSP
- Body Material: Brass
- Thread Size: 1/2 in
- Safe for Use With: Air, Oil, Steam, Water
- Maximum Working Pressure: 30 bar
- Connection Size (mm): 15 mm
- Connection Size (inch): 1/2 in



486338 Threaded

RS PRO BRASS FULL BORE, 2 WAY, BALL VALVE, 28MM

ขนาดบรรจุภัณฑ์: **1 x EA**

- Type: Full Bore, 2 Way
- Ball Material: Brass
- Attachment Type: Compression
- Compression Fitting Size: 28 mm
- Body Material: Brass
- Safe for Use With: Gas, Oil, Petrol, Water
- Handle Type: Lever
- Handle Material: PVC Coated Steel



486344 Full Bore, 2 Way

RS PRO BRASS FULL BORE, 2 WAY, BALL VALVE, BSPP 9.53MM, 40BAR

ขนาดบรรจุภัณฑ์: **1 x EA**

- Type: Full Bore, 2 Way
- Ball Material: Brass
- Attachment Type: Threaded
- Thread Standard: BSPP
- Thread Size: 9.53 mm
- Body Material: Brass
- Pipe Diameter: 10 mm
- Safe for Use With: Water



1417706 Full Bore, 2 Way

RS PRO BRASS FULL BORE, 2 WAY, BALL VALVE, BSPP 6.35MM

ขนาดบรรจุภัณฑ์: **1 x EA**

- Type: Full Bore, 2 Way
- Ball Material: Brass
- Attachment Type: Threaded
- Thread Standard: BSPP
- Thread Size: 6.35 mm
- Body Material: Brass
- Safe for Use With: Water
- Handle Type: Lever



1417721 Full Bore, 2 Way

RS PRO BRASS FULL BORE, 2 WAY, BALL VALVE, BSPP 6.35MM

ขนาดบรรจุภัณฑ์: **1 x EA**

- Type: Full Bore, 2 Way
- Ball Material: Brass
- Attachment Type: Threaded
- Thread Standard: BSPP
- Thread Size: 6.35 mm
- Body Material: Brass
- Safe for Use With: Water
- Handle Type: T-Handle



1417726 Full Bore, 2 Way

RS PRO BRASS FULL BORE, 2 WAY, BALL VALVE, BSPP 12.7MM

ขนาดบรรจุภัณฑ์: **1 x EA**

- Type: Full Bore, 2 Way
- Ball Material: Brass
- Attachment Type: Threaded
- Thread Standard: BSPP
- Thread Size: 12.7 mm
- Body Material: Brass
- Safe for Use With: Water
- Handle Type: T-Handle



1417728 Full Bore, 2 Way

RS PRO STAINLESS STEEL L PORT, 3 WAY, BALL VALVE, BSPP 6.35MM,

ขนาดบรรจุภัณฑ์: **1 x EA**

- Type: L Port, 3 Way
- Ball Material: Stainless Steel
- Attachment Type: Threaded
- Thread Standard: BSPP
- Thread Size: 6.35 mm
- Body Material: Stainless Steel
- Safe for Use With: Gas, Oil, Water
- Handle Type: Lever



4991865 L Port, 3 Way

RS PRO STAINLESS STEEL L PORT, 3 WAY, BALL VALVE, BSPP 9.53MM,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Type: L Port, 3 Way
 - Ball Material: Stainless Steel
 - Attachment Type: Threaded
 - Thread Standard: BSPP
 - Thread Size: 9.53 mm
 - Body Material: Stainless Steel
 - Safe for Use With: Gas, Oil, Water
 - Handle Type: Lever



4991871 L Port, 3 Way

RS PRO STAINLESS STEEL L PORT, 3 WAY, BALL VALVE, BSPP 12.7MM,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Type: L Port, 3 Way
 - Ball Material: Stainless Steel
 - Attachment Type: Threaded
 - Thread Standard: BSPP
 - Thread Size: 12.7 mm
 - Body Material: Stainless Steel
 - Safe for Use With: Gas, Oil, Water
 - Handle Type: Lever



4991887 L Port, 3 Way

RS PRO STAINLESS STEEL L PORT, 3 WAY, BALL VALVE, BSPP 19.05MM,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Type: L Port, 3 Way
 - Ball Material: Stainless Steel
 - Attachment Type: Threaded
 - Thread Standard: BSPP
 - Thread Size: 19.05 mm
 - Body Material: Stainless Steel
 - Safe for Use With: Gas, Oil, Water
 - Handle Type: Lever



4991893 L Port, 3 Way

RS PRO STAINLESS STEEL T PORT, 3 WAY, BALL VALVE, BSPP 9.53MM,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Type: T Port, 3 Way
 - Ball Material: Stainless Steel
 - Attachment Type: Threaded
 - Thread Standard: BSPP
 - Thread Size: 9.53 mm
 - Body Material: Stainless Steel
 - Safe for Use With: Gas, Oil, Water
 - Handle Type: Lever



4991938 T Port, 3 Way

RS PRO STAINLESS STEEL T PORT, 3 WAY, BALL VALVE, BSPP 12.7MM,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Type: T Port, 3 Way
 - Ball Material: Stainless Steel
 - Attachment Type: Threaded
 - Thread Standard: BSPP
 - Thread Size: 12.7 mm
 - Body Material: Stainless Steel
 - Safe for Use With: Gas, Oil, Water
 - Handle Type: Lever



4991944 T Port, 3 Way

RS PRO STAINLESS STEEL T PORT, 3 WAY, BALL VALVE, BSPP 19.05MM,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Type: T Port, 3 Way
 - Ball Material: Stainless Steel
 - Attachment Type: Threaded
 - Thread Standard: BSPP
 - Thread Size: 19.05 mm
 - Body Material: Stainless Steel
 - Safe for Use With: Gas, Oil, Water
 - Handle Type: Lever



4991950 T Port, 3 Way

RS PRO STAINLESS STEEL T PORT, 3 WAY, BALL VALVE, BSPP 25.4MM,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Type: T Port, 3 Way
 - Ball Material: Stainless Steel
 - Attachment Type: Threaded
 - Thread Standard: BSPP
 - Thread Size: 25.4 mm
 - Body Material: Stainless Steel
 - Safe for Use With: Gas, Oil, Water
 - Handle Type: Lever



4991966 T Port, 3 Way

RS PRO STAINLESS STEEL REDUCED BORE, 2 WAY, BALL VALVE, BSPP

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Type: Reduced Bore, 2 Way
 - Ball Material: Stainless Steel
 - Attachment Type: Threaded
 - Thread Standard: BSPP
 - Thread Size: 6.35 mm
 - Body Material: Stainless Steel
 - Safe for Use With: Gas, Oil, Water
 - Handle Type: Lever



4992789 Reduced Bore, 2

RS PRO STAINLESS STEEL REDUCED BORE, 2 WAY, BALL VALVE, BSPP

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Type: Reduced Bore, 2 Way
 - Ball Material: Stainless Steel
 - Attachment Type: Threaded
 - Thread Standard: BSPP
 - Thread Size: 12.7 mm
 - Body Material: Stainless Steel
 - Safe for Use With: Gas, Oil, Water
 - Handle Type: Lever



4992795 Reduced Bore, 2

RS PRO STAINLESS STEEL REDUCED BORE, 2 WAY, BALL VALVE, BSPP

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Type: Reduced Bore, 2 Way
 - Ball Material: Stainless Steel
 - Attachment Type: Threaded
 - Thread Standard: BSPP
 - Thread Size: 19.05 mm
 - Body Material: Stainless Steel
 - Safe for Use With: Gas, Oil, Water
 - Handle Type: Lever



4992802 Reduced Bore, 2

RS PRO STAINLESS STEEL REDUCED BORE, 2 WAY, BALL VALVE, BSPP

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Type: Reduced Bore, 2 Way
 - Ball Material: Stainless Steel
 - Attachment Type: Threaded
 - Thread Standard: BSPP
 - Thread Size: 25.4 mm
 - Body Material: Stainless Steel
 - Safe for Use With: Gas, Oil, Water
 - Handle Type: Lever



4992818 Reduced Bore, 2

RS PRO STAINLESS STEEL REDUCED BORE, 2 WAY, BALL VALVE, BSPP

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Type: Reduced Bore, 2 Way
 - Ball Material: Stainless Steel
 - Attachment Type: Threaded
 - Thread Standard: BSPP
 - Thread Size: 31.75 mm
 - Body Material: Stainless Steel
 - Safe for Use With: Gas, Oil, Water
 - Handle Type: Lever



4992824 Reduced Bore, 2

RS PRO STAINLESS STEEL REDUCED BORE, 2 WAY, BALL VALVE, BSPP

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Type: Reduced Bore, 2 Way
 - Ball Material: Stainless Steel
 - Attachment Type: Threaded
 - Thread Standard: BSPP
 - Thread Size: 38.1 mm
 - Body Material: Stainless Steel
 - Safe for Use With: Gas, Oil, Water
 - Handle Type: Lever



4992830 Reduced Bore, 2

RS PRO STAINLESS STEEL REDUCED BORE, 2 WAY, BALL VALVE, BSPP

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Type: Reduced Bore, 2 Way
 - Ball Material: Stainless Steel
 - Attachment Type: Threaded
 - Thread Standard: BSPP
 - Thread Size: 50.8 mm
 - Body Material: Stainless Steel
 - Safe for Use With: Gas, Oil, Water
 - Handle Type: Lever



4992846 Reduced Bore, 2

RS PRO BRASS FULL BORE, 2 WAY, BALL VALVE, BSPP 9.53MM, 30 →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Type: Full Bore, 2 Way
 - Ball Material: Brass
 - Attachment Type: Threaded
 - Thread Standard: BSPP
 - Thread Size: 9.53 mm
 - Body Material: Brass
 - Safe for Use With: Air, Oil, Steam, Water
 - Handle Type: Lever



7335120 Full Bore, 2 Way

RS PRO BRASS FULL BORE, 2 WAY, BALL VALVE, BSPP 6.35MM, 40 →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Type: Full Bore, 2 Way
 - Ball Material: Chrome Plated Brass
 - Attachment Type: Threaded
 - Thread Standard: BSPP
 - Thread Size: 6.35 mm
 - Body Material: Brass
 - Pipe Diameter: 8 mm
 - Safe for Use With: Air, Oil, Steam, Water



7335126 Full Bore, 2 Way

RS PRO BRASS FULL BORE, 2 WAY, BALL VALVE, BSPP 19.05MM, 40 →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Full Bore, 2 Way
 - Ball Material: Chrome Plated Brass
 - Attachment Type: Threaded
 - Thread Standard: BSPP
 - Thread Size: 19.05 mm
 - Body Material: Brass
 - Pipe Diameter: 20 mm
 - Safe for Use With: Air, Oil, Steam, Water



7335132 Full Bore, 2 Way

RS PRO BRASS FULL BORE, 2 WAY, BALL VALVE, BSPP 25.4MM, 40 →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Full Bore, 2 Way
 - Ball Material: Chrome Plated Brass
 - Attachment Type: Threaded
 - Thread Standard: BSPP
 - Thread Size: 25.4 mm
 - Body Material: Brass
 - Pipe Diameter: 25 mm
 - Safe for Use With: Air, Oil, Steam, Water



7335136 Full Bore, 2 Way

RS PRO BRASS FULL BORE, 2 WAY, BALL VALVE, BSPP 12.7MM, 40 →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Full Bore, 2 Way
 - Ball Material: Chrome Plated Brass
 - Attachment Type: Threaded
 - Thread Standard: BSPP
 - Thread Size: 12.7 mm
 - Body Material: Brass
 - Pipe Diameter: 15 mm
 - Safe for Use With: Air, Oil, Steam, Water



7335139 Full Bore, 2 Way

RS PRO BRASS FULL BORE, 2 WAY, BALL VALVE, BSPP 50.8MM, 40 →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Full Bore, 2 Way
 - Ball Material: Chrome Plated Brass
 - Attachment Type: Threaded
 - Thread Standard: BSPP
 - Thread Size: 50.8 mm
 - Body Material: Brass
 - Pipe Diameter: 50 mm
 - Safe for Use With: Air, Oil, Steam, Water



7335142 Full Bore, 2 Way

RS PRO BRASS FULL BORE, 2 WAY, BALL VALVE, BSPP 31.75MM, 40 →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Full Bore, 2 Way
 - Ball Material: Chrome Plated Brass
 - Attachment Type: Threaded
 - Thread Standard: BSPP
 - Thread Size: 31.75 mm
 - Body Material: Brass
 - Pipe Diameter: 32 mm
 - Safe for Use With: Air, Oil, Steam, Water



7335145 Full Bore, 2 Way

RS PRO BRASS FULL BORE, 2 WAY, BALL VALVE, BSPP 38.1MM, 40 →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Full Bore, 2 Way
 - Ball Material: Chrome Plated Brass
 - Attachment Type: Threaded
 - Thread Standard: BSPP
 - Thread Size: 38.1 mm
 - Body Material: Brass
 - Pipe Diameter: 40 mm
 - Safe for Use With: Air, Oil, Steam, Water



7335148 Full Bore, 2 Way

RS PRO BRASS FULL BORE, 2 WAY, BALL VALVE, BSPP 6.35MM, 40 →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Full Bore, 2 Way
 - Ball Material: Brass
 - Attachment Type: Threaded
 - Thread Standard: BSPP
 - Thread Size: 6.35 mm
 - Body Material: Brass
 - Pipe Diameter: 8 mm
 - Safe for Use With: Gas



7335151 Full Bore, 2 Way

RS PRO BRASS FULL BORE, 2 WAY, BALL VALVE, BSPP 9.53MM, 40 →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Full Bore, 2 Way
 - Ball Material: Brass
 - Attachment Type: Threaded
 - Thread Standard: BSPP
 - Thread Size: 9.53 mm
 - Body Material: Brass
 - Pipe Diameter: 10 mm
 - Safe for Use With: Gas



7335154 Full Bore, 2 Way

RS PRO BRASS FULL BORE, 2 WAY, BALL VALVE, BSPP 12.7MM, 40 →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Full Bore, 2 Way
 - Ball Material: Brass
 - Attachment Type: Threaded
 - Thread Standard: BSPP
 - Thread Size: 12.7 mm
 - Body Material: Brass
 - Pipe Diameter: 15 mm
 - Safe for Use With: Gas



7335158 Full Bore, 2 Way

RS PRO BRASS FULL BORE, 2 WAY, BALL VALVE, BSPP 25.4MM, 40 →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Full Bore, 2 Way
 - Ball Material: Brass
 - Attachment Type: Threaded
 - Thread Standard: BSPP
 - Thread Size: 25.4 mm
 - Body Material: Brass
 - Pipe Diameter: 25 mm
 - Safe for Use With: Gas



7335160 Full Bore, 2 Way

RS PRO BRASS FULL BORE, 2 WAY, BALL VALVE, BSPP 19.05MM, 40 →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Full Bore, 2 Way
 - Ball Material: Brass
 - Attachment Type: Threaded
 - Thread Standard: BSPP
 - Thread Size: 19.05 mm
 - Body Material: Brass
 - Pipe Diameter: 20 mm
 - Safe for Use With: Gas



7335167 Full Bore, 2 Way

RS PRO BRASS FULL BORE, 2 WAY, BALL VALVE, BSPP 12.7MM, 40 →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Full Bore, 2 Way
 - Ball Material: Brass
 - Attachment Type: Threaded
 - Thread Standard: BSPP
 - Thread Size: 12.7 mm
 - Body Material: Brass
 - Pipe Diameter: 15 mm
 - Safe for Use With: Air, Oil, Steam, Water



7335170 Full Bore, 2 Way

RS PRO NICKEL PLATED BRASS FULL BORE, 2 WAY, BALL VALVE, BSPP

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Full Bore, 2 Way
 - Ball Material: Chrome Plated Brass
 - Attachment Type: Threaded
 - Thread Standard: BSPP
 - Thread Size: 25.4 mm
 - Body Material: Nickel Plated Brass
 - Pipe Diameter: 25 mm
 - Safe for Use With: Air, Oil, Steam, Water



7335182 Full Bore, 2 Way

RS PRO NICKEL PLATED BRASS FULL BORE, 2 WAY, BALL VALVE, BSPP

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Full Bore, 2 Way
 - Ball Material: Chrome Plated Brass
 - Attachment Type: Threaded
 - Thread Standard: BSPP
 - Thread Size: 31.75 mm
 - Body Material: Nickel Plated Brass
 - Pipe Diameter: 32 mm
 - Safe for Use With: Air, Oil, Steam, Water



7335186 Full Bore, 2 Way

RS PRO NICKEL PLATED BRASS FULL BORE, 2 WAY, BALL VALVE, BSPP

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Full Bore, 2 Way
 - Ball Material: Chrome Plated Brass
 - Attachment Type: Threaded
 - Thread Standard: BSPP
 - Thread Size: 19.05 mm
 - Body Material: Nickel Plated Brass
 - Pipe Diameter: 20 mm
 - Safe for Use With: Air, Oil, Steam, Water



7335189 Full Bore, 2 Way

RS PRO NICKEL PLATED BRASS FULL BORE, 2 WAY, BALL VALVE, BSPP

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Full Bore, 2 Way
 - Ball Material: Chrome Plated Brass
 - Attachment Type: Threaded
 - Thread Standard: BSPP
 - Thread Size: 6.35 mm
 - Body Material: Nickel Plated Brass
 - Pipe Diameter: 15 mm
 - Safe for Use With: Air, Oil, Steam, Water



7335192 Full Bore, 2 Way

RS PRO NICKEL PLATED BRASS FULL BORE, 2 WAY, BALL VALVE, BSPP

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Type: Full Bore, 2 Way
 - Ball Material: Chrome Plated Brass
 - Attachment Type: Threaded
 - Thread Standard: BSPP
 - Thread Size: 38.1 mm
 - Body Material: Nickel Plated Brass
 - Pipe Diameter: 40 mm
 - Safe for Use With: Air, Oil, Steam, Water



7335195 Full Bore, 2 Way

RS PRO NICKEL PLATED BRASS FULL BORE, 2 WAY, BALL VALVE, BSPP

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Type: Full Bore, 2 Way
 - Ball Material: Chrome Plated Brass
 - Attachment Type: Threaded
 - Thread Standard: BSPP
 - Thread Size: 50.8 mm
 - Body Material: Nickel Plated Brass
 - Pipe Diameter: 50 mm
 - Safe for Use With: Air, Oil, Steam, Water



7335198 Full Bore, 2 Way

RS PRO BRASS FULL BORE, 2 WAY, BALL VALVE, BSPP 9.53MM, 40 →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Type: Full Bore, 2 Way
 - Ball Material: Chrome Plated Brass
 - Attachment Type: Threaded
 - Thread Standard: BSPP
 - Thread Size: 9.53 mm
 - Body Material: Brass
 - Pipe Diameter: 10 mm
 - Safe for Use With: Air, Oil, Steam, Water



7335202 Full Bore, 2 Way

RS PRO BRASS FULL BORE, 2 WAY, BALL VALVE, BSPP 6.35MM, 40 →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Type: Full Bore, 2 Way
 - Ball Material: Chrome Plated Brass
 - Attachment Type: Threaded
 - Thread Standard: BSPP
 - Thread Size: 6.35 mm
 - Body Material: Brass
 - Pipe Diameter: 8 mm
 - Safe for Use With: Air, Oil, Steam, Water



7335211 Full Bore, 2 Way

RS PRO BRASS FULL BORE, 2 WAY, BALL VALVE, BSPP 9.53MM, 40 →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Type: Full Bore, 2 Way
 - Ball Material: Chrome Plated Brass
 - Attachment Type: Threaded
 - Thread Standard: BSPP
 - Thread Size: 9.53 mm
 - Body Material: Brass
 - Pipe Diameter: 10 mm
 - Safe for Use With: Air, Oil, Steam, Water



7335215 Full Bore, 2 Way

RS PRO BRASS FULL BORE, 2 WAY, BALL VALVE, BSPP 25.4MM, 40 →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Type: Full Bore, 2 Way
 - Ball Material: Chrome Plated Brass
 - Attachment Type: Threaded
 - Thread Standard: BSPP
 - Thread Size: 25.4 mm
 - Body Material: Brass
 - Pipe Diameter: 25 mm
 - Safe for Use With: Air, Oil, Steam, Water



7335218 Full Bore, 2 Way

RS PRO BRASS FULL BORE, 2 WAY, BALL VALVE, BSPP 25.4MM, 40 →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Type: Full Bore, 2 Way
 - Ball Material: Chrome Plated Brass
 - Attachment Type: Threaded
 - Thread Standard: BSPP
 - Thread Size: 25.4 mm
 - Body Material: Brass
 - Pipe Diameter: 25 mm
 - Safe for Use With: Air, Oil, Steam, Water



7335221 Full Bore, 2 Way

RS PRO BRASS FULL BORE, 2 WAY, BALL VALVE, BSPP 12.7MM, 40 →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Type: Full Bore, 2 Way
 - Ball Material: Chrome Plated Brass
 - Attachment Type: Threaded
 - Thread Standard: BSPP
 - Thread Size: 12.7 mm
 - Body Material: Brass
 - Pipe Diameter: 15 mm
 - Safe for Use With: Air, Oil, Steam, Water



7335224 Full Bore, 2 Way

RS PRO BRASS FULL BORE, 2 WAY, BALL VALVE, BSPP 19.05MM, 40 →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Type: Full Bore, 2 Way
 - Ball Material: Chrome Plated Brass
 - Attachment Type: Threaded
 - Thread Standard: BSPP
 - Thread Size: 19.05 mm
 - Body Material: Brass
 - Pipe Diameter: 20 mm
 - Safe for Use With: Air, Oil, Steam, Water



7335227 Full Bore, 2 Way

RS PRO BRASS HIGH PRESSURE BALL VALVE 1/4 IN BSPP 2 WAY

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Attachment Type: Threaded
 - Threaded Connection: 1/4 in BSPP
 - Body Material: Brass
 - Thread Size: 1/4 in
 - Safe for Use With: Air, Oil, Steam, Water
 - Maximum Working Pressure: 32 bar
 - Connection Size (mm): 8 mm
 - Connection Size (inch): 1/4 in



7335230 Threaded

RS PRO BRASS FULL BORE, 2 WAY, BALL VALVE, BSPP 9.53MM, 40 →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Type: Full Bore, 2 Way
 - Ball Material: Chrome Plated Brass
 - Attachment Type: Threaded
 - Thread Standard: BSPP
 - Thread Size: 9.53 mm
 - Body Material: Brass
 - Pipe Diameter: 10 mm
 - Safe for Use With: Air, Oil, Steam, Water



7335233 Full Bore, 2 Way

RS PRO BRASS FULL BORE, 2 WAY, BALL VALVE, BSPP 12.7MM, 40 →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Type: Full Bore, 2 Way
 - Ball Material: Chrome Plated Brass
 - Attachment Type: Threaded
 - Thread Standard: BSPP
 - Thread Size: 12.7 mm
 - Body Material: Brass
 - Pipe Diameter: 15 mm
 - Safe for Use With: Air, Oil, Steam, Water



7335237 Full Bore, 2 Way

RS PRO BRASS FULL BORE, 2 WAY, BALL VALVE, BSPP 31.75MM, 40 →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Type: Full Bore, 2 Way
 - Ball Material: Chrome Plated Brass
 - Attachment Type: Threaded
 - Thread Standard: BSPP
 - Thread Size: 31.75 mm
 - Body Material: Brass
 - Pipe Diameter: 32 mm
 - Safe for Use With: Air, Oil, Steam, Water



7335243 Full Bore, 2 Way

RS PRO BRASS FULL BORE, 2 WAY, BALL VALVE, BSPP 19.05MM, 40 →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Type: Full Bore, 2 Way
 - Ball Material: Chrome Plated Brass
 - Attachment Type: Threaded
 - Thread Standard: BSPP
 - Thread Size: 19.05 mm
 - Body Material: Brass
 - Pipe Diameter: 20 mm
 - Safe for Use With: Air, Oil, Steam, Water



7335246 Full Bore, 2 Way

RS PRO BRASS FULL BORE, 2 WAY, BALL VALVE, BSPP 25.4MM, 40 →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Type: Full Bore, 2 Way
 - Ball Material: Chrome Plated Brass
 - Attachment Type: Threaded
 - Thread Standard: BSPP
 - Thread Size: 25.4 mm
 - Body Material: Brass
 - Pipe Diameter: 25 mm
 - Safe for Use With: Air, Oil, Steam, Water



7335249 Full Bore, 2 Way

RS PRO BRASS FULL BORE, 2 WAY, BALL VALVE, BSPP 12.7MM, 40 →

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Type: Full Bore, 2 Way
 - Ball Material: Chrome Plated Brass
 - Attachment Type: Threaded
 - Thread Standard: BSPP
 - Thread Size: 12.7 mm
 - Body Material: Brass
 - Pipe Diameter: 15 mm
 - Safe for Use With: Gas



7335261 Full Bore, 2 Way

RS PRO BRASS FULL BORE, 2 WAY, BALL VALVE, BSPP 19.05MM, 40 →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Full Bore, 2 Way
 - Ball Material: Chrome Plated Brass
 - Attachment Type: Threaded
 - Thread Standard: BSPP
 - Thread Size: 19.05 mm
 - Body Material: Brass
 - Pipe Diameter: 20 mm
 - Safe for Use With: Gas



7335265 Full Bore, 2 Way

RS PRO BRASS 2 WAY, BALL VALVE, BSPP 9.53MM, 40 → 30BAR

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: 2 Way
 - Ball Material: Chrome Plated Brass
 - Attachment Type: Threaded
 - Thread Standard: BSPP
 - Thread Size: 9.53 mm
 - Body Material: Brass
 - Pipe Diameter: 10 mm
 - Safe for Use With: Gas



7335271 2 Way

RS PRO BRASS FULL BORE, 2 WAY, BALL VALVE, BSPP 25.4MM, 40 →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Full Bore, 2 Way
 - Ball Material: Chrome Plated Brass
 - Attachment Type: Threaded
 - Thread Standard: BSPP
 - Thread Size: 25.4 mm
 - Body Material: Brass
 - Pipe Diameter: 25 mm
 - Safe for Use With: Gas



7335274 Full Bore, 2 Way

RS PRO BRASS 2 WAY, BALL VALVE, BSPP 12.7MM, 40 → 30BAR

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: 2 Way
 - Ball Material: Chrome Plated Brass
 - Attachment Type: Threaded
 - Thread Standard: BSPP
 - Thread Size: 12.7 mm
 - Body Material: Brass
 - Pipe Diameter: 15 mm
 - Safe for Use With: Gas



7335280 2 Way

RS PRO BRASS 2 WAY, BALL VALVE, BSPP 12.7MM, 40 → 30BAR

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: 2 Way
 - Ball Material: Chrome Plated Brass
 - Attachment Type: Threaded
 - Thread Standard: BSPP
 - Thread Size: 12.7 mm
 - Body Material: Brass
 - Pipe Diameter: 15 mm
 - Safe for Use With: Gas



7335293 2 Way

RS PRO BRASS 2 WAY, BALL VALVE, BSPP 6.35MM, 40 → 30BAR

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: 2 Way
 - Ball Material: Chrome Plated Brass
 - Attachment Type: Threaded
 - Thread Standard: BSPP
 - Thread Size: 6.35 mm
 - Body Material: Brass
 - Pipe Diameter: 8 mm
 - Safe for Use With: Gas



7335296 2 Way

RS PRO BRASS FULL BORE, 2 WAY, BALL VALVE, BSPP 19.05MM, 40 →

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Full Bore, 2 Way
 - Ball Material: Chrome Plated Brass
 - Attachment Type: Threaded
 - Thread Standard: BSPP
 - Thread Size: 19.05 mm
 - Body Material: Brass
 - Pipe Diameter: 20 mm
 - Safe for Use With: Gas



7335303 Full Bore, 2 Way

RS PRO CARBON STEEL FULL BORE, 2 WAY, BALL VALVE, BSPP 31.75MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Full Bore, 2 Way
 - Ball Material: Stainless Steel
 - Attachment Type: Threaded
 - Thread Standard: BSPP
 - Thread Size: 31.75 mm
 - Body Material: Carbon Steel
 - Safe for Use With: Gas, Oil, Water
 - Handle Type: Lever



7644228 Full Bore, 2 Way

RS PRO STAINLESS STEEL FULL BORE, 2 WAY, BALL VALVE, BSPP 12.7MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Full Bore, 2 Way
 - Ball Material: Stainless Steel
 - Attachment Type: Threaded
 - Thread Standard: BSPP
 - Thread Size: 12.7 mm
 - Body Material: Stainless Steel
 - Pipe Diameter: 15 mm
 - Safe for Use With: Gas, Oil, Water



7644234 Full Bore, 2 Way

RS PRO STAINLESS STEEL FULL BORE, 2 WAY, BALL VALVE, BSPP 19.05MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Full Bore, 2 Way
 - Ball Material: Stainless Steel
 - Attachment Type: Threaded
 - Thread Standard: BSPP
 - Thread Size: 19.05 mm
 - Body Material: Stainless Steel
 - Pipe Diameter: 20 mm
 - Safe for Use With: Gas, Oil, Water



7644238 Full Bore, 2 Way

RS PRO STAINLESS STEEL FULL BORE, 2 WAY, BALL VALVE, BSPP 31.75MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Full Bore, 2 Way
 - Ball Material: Stainless Steel
 - Attachment Type: Threaded
 - Thread Standard: BSPP
 - Thread Size: 31.75 mm
 - Body Material: Stainless Steel
 - Safe for Use With: Gas, Oil, Water
 - Handle Type: Lever



7644240 Full Bore, 2 Way

RS PRO STAINLESS STEEL FULL BORE, 2 WAY, BALL VALVE, BSPP 38.1MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Full Bore, 2 Way
 - Ball Material: Stainless Steel
 - Attachment Type: Threaded
 - Thread Standard: BSPP
 - Thread Size: 38.1 mm
 - Body Material: Stainless Steel
 - Safe for Use With: Gas, Oil, Water
 - Handle Type: Lever



7644244 Full Bore, 2 Way

RS PRO STAINLESS STEEL FULL BORE, 2 WAY, BALL VALVE, BSPP 25.4MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Full Bore, 2 Way
 - Ball Material: Stainless Steel
 - Attachment Type: Threaded
 - Thread Standard: BSPP
 - Thread Size: 25.4 mm
 - Body Material: Stainless Steel
 - Pipe Diameter: 25 mm
 - Safe for Use With: Gas, Oil, Water



7644247 Full Bore, 2 Way

RS PRO STAINLESS STEEL FULL BORE, 2 WAY, BALL VALVE, BSPP 12.7MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Full Bore, 2 Way
 - Ball Material: Stainless Steel
 - Attachment Type: Threaded
 - Thread Standard: BSPP
 - Thread Size: 12.7 mm
 - Body Material: Stainless Steel
 - Pipe Diameter: 15 mm
 - Safe for Use With: Gas, Oil, Water



7644250 Full Bore, 2 Way

RS PRO STAINLESS STEEL FULL BORE, 2 WAY, BALL VALVE, BSPP 50.8MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Full Bore, 2 Way
 - Ball Material: Stainless Steel
 - Attachment Type: Threaded
 - Thread Standard: BSPP
 - Thread Size: 50.8 mm
 - Body Material: Stainless Steel
 - Pipe Diameter: 50 mm
 - Safe for Use With: Gas, Oil, Water



7644253 Full Bore, 2 Way

RS PRO STAINLESS STEEL FULL BORE, 2 WAY, BALL VALVE, BSPP 6.35MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Full Bore, 2 Way
 - Ball Material: Stainless Steel
 - Attachment Type: Threaded
 - Thread Standard: BSPP
 - Thread Size: 6.35 mm
 - Body Material: Stainless Steel
 - Pipe Diameter: 11.6 mm
 - Safe for Use With: Gas, Oil, Water



7644256 Full Bore, 2 Way

RS PRO STAINLESS STEEL FULL BORE, 2 WAY, BALL VALVE, BSPP 25.4MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Full Bore, 2 Way
 - Ball Material: Stainless Steel
 - Attachment Type: Threaded
 - Thread Standard: BSPP
 - Thread Size: 25.4 mm
 - Body Material: Stainless Steel
 - Pipe Diameter: 25 mm
 - Safe for Use With: Gas, Oil, Water



7644262 Full Bore, 2 Way

RS PRO STAINLESS STEEL FULL BORE, 2 WAY, BALL VALVE, BSPP 31.75MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Full Bore, 2 Way
 - Ball Material: Stainless Steel
 - Attachment Type: Threaded
 - Thread Standard: BSPP
 - Thread Size: 31.75 mm
 - Body Material: Stainless Steel
 - Safe for Use With: Gas, Oil, Water
 - Handle Type: Lever



7644266 Full Bore, 2 Way

RS PRO STAINLESS STEEL FULL BORE, 2 WAY, BALL VALVE, BSPP 19.05MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Full Bore, 2 Way
 - Ball Material: Stainless Steel
 - Attachment Type: Threaded
 - Thread Standard: BSPP
 - Thread Size: 19.05 mm
 - Body Material: Stainless Steel
 - Pipe Diameter: 20 mm
 - Safe for Use With: Gas, Oil, Water



7644269 Full Bore, 2 Way

RS PRO STAINLESS STEEL FULL BORE, 2 WAY, BALL VALVE, BSPP 38.1MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Full Bore, 2 Way
 - Ball Material: Stainless Steel
 - Attachment Type: Threaded
 - Thread Standard: BSPP
 - Thread Size: 38.1 mm
 - Body Material: Stainless Steel
 - Pipe Diameter: 38 mm
 - Safe for Use With: Gas, Oil, Water



7644275 Full Bore, 2 Way

RS PRO STAINLESS STEEL FULL BORE, 2 WAY, BALL VALVE, BSPP 50.8MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Full Bore, 2 Way
 - Ball Material: Stainless Steel
 - Attachment Type: Threaded
 - Thread Standard: BSPP
 - Thread Size: 50.8 mm
 - Body Material: Stainless Steel
 - Safe for Use With: Gas, Oil, Water
 - Handle Type: Lever



7644278 Full Bore, 2 Way

RS PRO NICKEL PLATED BRASS 2 WAY, BALL VALVE, BSP, 8MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: 2 Way
 - Ball Material: Stainless Steel
 - Attachment Type: Compression
 - Thread Standard: BSP
 - Compression Fitting Size: 8 mm
 - Body Material: Nickel Plated Brass
 - Pipe Diameter: 8 mm
 - Safe for Use With: Gas



7845412 2 Way

RS PRO BRASS FULL BORE, 2 WAY, BALL VALVE, BSP 25.4MM, 30BAR

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Full Bore, 2 Way
 - Ball Material: Brass
 - Attachment Type: Threaded
 - Thread Standard: BSP
 - Thread Size: 25.4 mm
 - Body Material: Brass
 - Pipe Diameter: 25 mm
 - Safe for Use With: Water



8125132 Full Bore, 2 Way

RS PRO BRASS FULL BORE, 2 WAY, BALL VALVE, BSP 12.7MM, 30BAR

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Full Bore, 2 Way
 - Ball Material: Brass
 - Attachment Type: Threaded
 - Thread Standard: BSP
 - Thread Size: 12.7 mm
 - Body Material: Brass
 - Pipe Diameter: 15 mm
 - Safe for Use With: Water



8125135 Full Bore, 2 Way

RS PRO NICKEL PLATED BRASS FULL BORE, 2 WAY, BALL VALVE, BSP

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Full Bore, 2 Way
 - Ball Material: Chrome Plated Brass
 - Attachment Type: Threaded
 - Thread Standard: BSP
 - Thread Size: 25.4 mm
 - Body Material: Nickel Plated Brass
 - Pipe Diameter: 25 mm
 - Handle Type: Lever



8125154 Full Bore, 2 Way

RS PRO NICKEL PLATED BRASS FULL BORE, 2 WAY, BALL VALVE, BSP

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Full Bore, 2 Way
 - Ball Material: Chrome Plated Brass
 - Attachment Type: Threaded
 - Thread Standard: BSP
 - Thread Size: 38.1 mm
 - Body Material: Nickel Plated Brass
 - Pipe Diameter: 40 mm
 - Handle Type: Lever



8125166 Full Bore, 2 Way

RS PRO BRASS FULL BORE, 2 WAY, BALL VALVE, BSP 9.53MM, 14BAR

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Full Bore, 2 Way
 - Ball Material: Chrome Plated Brass
 - Attachment Type: Threaded
 - Thread Standard: BSP
 - Thread Size: 9.53 mm
 - Body Material: Brass
 - Pipe Diameter: 10 mm
 - Handle Type: Lever



8125172 Full Bore, 2 Way

RS PRO BRASS FULL BORE, 2 WAY, BALL VALVE, BSP 12.7MM, 14BAR

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Full Bore, 2 Way
 - Ball Material: Chrome Plated Brass
 - Attachment Type: Threaded
 - Thread Standard: BSP
 - Thread Size: 12.7 mm
 - Body Material: Brass
 - Pipe Diameter: 15 mm
 - Handle Type: Lever



8125176 Full Bore, 2 Way

RS PRO BRASS FULL BORE, 2 WAY, BALL VALVE, BSP 6.35MM, 14BAR

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Full Bore, 2 Way
 - Ball Material: Chrome Plated Brass
 - Attachment Type: Threaded
 - Thread Standard: BSP
 - Thread Size: 6.35 mm
 - Body Material: Brass
 - Pipe Diameter: 8 mm
 - Handle Type: Lever



8125179 Full Bore, 2 Way

RS PRO BRASS FULL BORE, 2 WAY, BALL VALVE, BSP 19.05MM, 14BAR

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Full Bore, 2 Way
 - Ball Material: Chrome Plated Brass
 - Attachment Type: Threaded
 - Thread Standard: BSP
 - Thread Size: 19.05 mm
 - Body Material: Brass
 - Pipe Diameter: 20 mm
 - Handle Type: Lever



8125185 Full Bore, 2 Way

RS PRO BRASS FULL BORE, 2 WAY, BALL VALVE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Full Bore, 2 Way
 - Attachment Type: Threaded
 - Body Material: Brass



8125236 Full Bore, 2 Way

RS PRO BRASS FULL BORE, 2 WAY, BALL VALVE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Full Bore, 2 Way
 - Attachment Type: Threaded
 - Body Material: Brass



8125249 Full Bore, 2 Way

RS PRO NICKEL PLATED BRASS FULL BORE, 2 WAY, BALL VALVE, BSP

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Full Bore, 2 Way
 - Ball Material: Chrome Plated Brass
 - Attachment Type: Threaded
 - Thread Standard: BSP
 - Thread Size: 38.1 mm
 - Body Material: Nickel Plated Brass
 - Pipe Diameter: 40 mm
 - Operating Pressure: 40 bar



8125255 Full Bore, 2 Way

RS PRO NICKEL PLATED BRASS FULL BORE, 2 WAY, BALL VALVE, BSPT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Full Bore, 2 Way
 - Ball Material: Chrome Plated Brass
 - Attachment Type: Threaded
 - Thread Standard: BSPT
 - Thread Size: 9.53 mm
 - Body Material: Nickel Plated Brass
 - Pipe Diameter: 10 mm
 - Safe for Use With: Gas, Oil, Water



8125261 Full Bore, 2 Way

RS PRO NICKEL PLATED BRASS FULL BORE, 2 WAY, BALL VALVE, BSPT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Full Bore, 2 Way
 - Ball Material: Chrome Plated Brass
 - Attachment Type: Threaded
 - Thread Standard: BSPT
 - Thread Size: 6.35 mm
 - Body Material: Nickel Plated Brass
 - Pipe Diameter: 8 mm
 - Safe for Use With: Gas, Oil, Water



8125267 Full Bore, 2 Way

RS PRO NICKEL PLATED BRASS FULL BORE, 2 WAY, BALL VALVE, BSPT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Full Bore, 2 Way
 - Ball Material: Chrome Plated Brass
 - Attachment Type: Threaded
 - Thread Standard: BSPT
 - Thread Size: 19.05 mm
 - Body Material: Nickel Plated Brass
 - Pipe Diameter: 20 mm
 - Safe for Use With: Gas, Oil, Water



8125273 Full Bore, 2 Way

RS PRO NICKEL PLATED BRASS FULL BORE, 2 WAY, BALL VALVE, BSPT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Full Bore, 2 Way
 - Ball Material: Chrome Plated Brass
 - Attachment Type: Threaded
 - Thread Standard: BSPT
 - Thread Size: 25.4 mm
 - Body Material: Nickel Plated Brass
 - Pipe Diameter: 25 mm
 - Safe for Use With: Gas, Oil, Water



8125277 Full Bore, 2 Way

RS PRO NICKEL PLATED BRASS FULL BORE, 2 WAY, BALL VALVE, BSPT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Full Bore, 2 Way
 - Ball Material: Chrome Plated Brass
 - Attachment Type: Threaded
 - Thread Standard: BSPT
 - Thread Size: 50.8 mm
 - Body Material: Nickel Plated Brass
 - Pipe Diameter: 50 mm
 - Safe for Use With: Gas, Oil, Water



8125283 Full Bore, 2 Way

RS PRO STAINLESS STEEL 2 WAY, BALL VALVE, NPT 6.35MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: 2 Way
 - Ball Material: Stainless Steel
 - Attachment Type: Threaded
 - Thread Standard: NPT
 - Thread Size: 6.35 mm
 - Body Material: Stainless Steel
 - Pipe Diameter: 0.25 mm
 - Safe for Use With: Industry



8267153 2 Way

RS PRO STAINLESS STEEL 2 WAY, BALL VALVE, NPT 12.7MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: 2 Way
 - Ball Material: Stainless Steel
 - Attachment Type: Threaded
 - Thread Standard: NPT
 - Thread Size: 12.7 mm
 - Body Material: Stainless Steel
 - Pipe Diameter: 0.5 mm
 - Safe for Use With: Industry



8267157 2 Way

RS PRO BRASS PIPE FITTING, STRAIGHT COMPRESSION COUPLER,

- ขนาดบรรจุภัณฑ์: 2 x EA
- Pipe Fitting Connection Type: Compression
 - Fitting Direction: Straight
 - Fitting Type: Coupler
 - Thread Size 1: 3/4 in
 - Connection Gender 1: Male
 - Connection Gender 2: Female
 - Material: Brass
 - Compatible Pipe Size: 15 mm



798066 Compression

RS PRO BRASS PIPE FITTING, 90° COMPRESSION WALL PLATE ELBOW

- ขนาดบรรจุภัณฑ์: 1 x EA
- Pipe Fitting Connection Type: Compression
 - Fitting Direction: 90°
 - Fitting Type: Wall Plate Elbow Adapter
 - Thread Size 1: 1/2 in
 - Connection Gender 1: Female
 - Connection Gender 2: Female
 - Material: Brass
 - Compatible Pipe Size: 15 mm



798230 Compression

RS PRO BRASS COMPRESSION FITTING, STRAIGHT COUPLER

- ขนาดบรรจุภัณฑ์: 2 x EA
- Fitting Direction: Straight
 - Fitting Type: Coupler
 - Material: Brass



2858665 Straight

RS PRO BRASS COMPRESSION FITTING, STRAIGHT COUPLER

- ขนาดบรรจุภัณฑ์: 2 x EA
- Fitting Direction: Straight
 - Fitting Type: Coupler
 - Material: Brass



2858693 Straight

RS PRO BRASS COMPRESSION FITTING, ELBOW COUPLER

- ขนาดบรรจุภัณฑ์: 2 x EA
- Fitting Direction: Elbow
 - Fitting Type: Coupler
 - Material: Brass



2858845 Elbow

PLUMBING, EQUAL ELBOW, 90DEG, MALE/FEMALE, 1/2IN

- ขนาดบรรจุภัณฑ์: 2 x EA
- Pipe Fitting Connection Type: Threaded
 - Fitting Direction: 90°
 - Fitting Type: Elbow
 - Thread Standard 1: BSPP
 - Thread Size 1: 1/2 in
 - Connection Gender 1: Male
 - Thread Standard 2: BSPP
 - Thread Size 2: 1/2 in



2972159 Threaded

25

- ขนาดบรรจุภัณฑ์: 2 x EA
- Fitting Direction: Straight
 - Fitting Type: Reducer Bush
 - Thread Standard 1: BSPT
 - Thread Size 1: 1 in
 - Connection Gender 1: Male
 - Thread Standard 2: BSPP
 - Thread Size 2: 1/2 in
 - Connection Gender 2: Female



2972216 Straight

25

- ขนาดบรรจุภัณฑ์: 2 x EA
- Fitting Direction: Straight
 - Fitting Type: Reducer Bush
 - Thread Standard 1: BSPT
 - Thread Size 1: 1 in
 - Connection Gender 1: Male
 - Thread Standard 2: BSPP
 - Thread Size 2: 3/4 in
 - Connection Gender 2: Female



2972222 Straight

RS PRO THREADED FITTING, STRAIGHT COUPLER, FEMALE BSPP

- ขนาดบรรจุภัณฑ์: 2 x EA
- Fitting Direction: Straight
 - Fitting Type: Coupler
 - Thread Standard 1: BSPP
 - Thread Size 1: 3/4 in
 - Connection Gender 1: Female
 - Thread Standard 2: BSPP
 - Thread Size 2: 3/4 in
 - Connection Gender 2: Female



2972238 Straight

PLUMBING, HEX NIPPLE, TAPER MALE BSP, 1/2 IN

- ขนาดบรรจุภัณฑ์: 2 x EA
- Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Fitting Type: Nipple
 - Thread Standard 1: BSPT
 - Thread Size 1: 1/2 in
 - Connection Gender 1: Male
 - Thread Standard 2: BSPT
 - Thread Size 2: 1/2 in



2972250 Threaded

RS PRO THREADED FITTING, STRAIGHT PLUG, MALE BSPT 3/4 IN

- ขนาดบรรจุภัณฑ์: 5 x EA
- Fitting Direction: Straight
 - Fitting Type: Plug
 - Thread Standard 1: BSPT
 - Thread Size 1: 3/4 in
 - Connection Gender 1: Male
 - Material: Bronze



2972301 Straight

RS PRO BRASS COMPRESSION FITTING, STRAIGHT COUPLER

- ขนาดบรรจุภัณฑ์: 2 x EA
- Fitting Direction: Straight
 - Fitting Type: Coupler
 - Material: Brass



3691520 Straight

RS PRO BRASS COMPRESSION FITTING, STRAIGHT COUPLER

- ขนาดบรรจุภัณฑ์: 1 x EA
- Fitting Direction: Straight
 - Fitting Type: Coupler
 - Material: Brass



3691564 Straight

RS PRO BRASS COMPRESSION FITTING, STRAIGHT COUPLER

- ขนาดบรรจุภัณฑ์: 1 x EA
- Fitting Direction: Straight
 - Fitting Type: Coupler
 - Material: Brass



3691586 Straight

RS PRO BRASS COMPRESSION FITTING, STRAIGHT COUPLER

- ขนาดบรรจุภัณฑ์: 2 x EA
- Fitting Direction: Straight
 - Fitting Type: Coupler
 - Material: Brass



3691592 Straight

RS PRO BRASS COMPRESSION FITTING END STOP

- ขนาดบรรจุภัณฑ์: 2 x EA
- Fitting Type: End Stop
 - Material: Brass



3691615 End Stop

PLUMBING, ELBOW, EQUAL, BRASS, 15X 15MM COPPER

- ขนาดบรรจุภัณฑ์: 2 x EA
- Fitting Direction: Elbow
 - Fitting Type: Coupler
 - Material: Brass



3691621 Elbow

RS PRO BRASS COMPRESSION FITTING, ELBOW COUPLER

- ขนาดบรรจุภัณฑ์: 2 x EA
- Fitting Direction: Elbow
 - Fitting Type: Coupler
 - Material: Brass



3691643 Elbow

RS PRO BRASS COMPRESSION FITTING EQUAL TEE

- ขนาดบรรจุภัณฑ์: 2 x EA
- Fitting Type: Equal Tee
 - Material: Brass



3691665 Equal Tee

RS PRO BRASS COMPRESSION FITTING, STRAIGHT COUPLER

- ขนาดบรรจุภัณฑ์: 2 x EA
- Fitting Direction: Straight
 - Fitting Type: Coupler
 - Material: Brass



4320241 Straight

RS PRO BRASS COMPRESSION FITTING, STRAIGHT COUPLER

- ขนาดบรรจุภัณฑ์: 2 x EA
- Fitting Direction: Straight
 - Fitting Type: Coupler
 - Material: Brass



4320263 Straight

RS PRO BRASS COMPRESSION FITTING, STRAIGHT COUPLER

- ขนาดบรรจุภัณฑ์: 2 x EA
- Fitting Direction: Straight
 - Fitting Type: Coupler
 - Material: Brass



4320279 Straight

RS PRO BRASS COMPRESSION FITTING, STRAIGHT COUPLER

- ขนาดบรรจุภัณฑ์: 2 x EA
- Fitting Direction: Straight
 - Fitting Type: Coupler
 - Material: Brass



4320285 Straight

RS PRO BRASS COMPRESSION FITTING, STRAIGHT COUPLER

- ขนาดบรรจุภัณฑ์: 2 x EA
- Fitting Direction: Straight
 - Fitting Type: Coupler
 - Material: Brass



4320291 Straight

RS PRO BRASS COMPRESSION FITTING, STRAIGHT COUPLER

- ขนาดบรรจุภัณฑ์: 2 x EA
- Fitting Direction: Straight
 - Fitting Type: Coupler
 - Material: Brass



4320308 Straight

RS PRO BRASS COMPRESSION FITTING, STRAIGHT COUPLER

- ขนาดบรรจุภัณฑ์: 2 x EA
- Fitting Direction: Straight
 - Fitting Type: Coupler
 - Material: Brass



4320320 Straight

RS PRO BRASS COMPRESSION FITTING, STRAIGHT COUPLER

- ขนาดบรรจุภัณฑ์: 2 x EA
- Fitting Direction: Straight
 - Fitting Type: Coupler
 - Material: Brass



4320336 Straight

RS PRO BRASS COMPRESSION FITTING, STRAIGHT COUPLER

- ขนาดบรรจุภัณฑ์: 2 x EA
- Fitting Direction: Straight
 - Fitting Type: Coupler
 - Material: Brass



4320358 Straight

RS PRO BRASS COMPRESSION FITTING, 90° ELBOW

- ขนาดบรรจุภัณฑ์: 2 x EA
- Fitting Direction: 90°
 - Fitting Type: Elbow
 - Material: Brass



4320392 90°

RS PRO BRASS COMPRESSION FITTING, ELBOW COUPLER

- ขนาดบรรจุภัณฑ์: 2 x EA
- Fitting Direction: Elbow
 - Fitting Type: Coupler
 - Material: Brass



4320459 Elbow

RS PRO BRASS PIPE FITTING, STRAIGHT THREADED 7.6 MM X 14.9

- ขนาดบรรจุภัณฑ์: 1 x PR
- Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Fitting Type: 7.6 mm x 14.9 mm Ceramic Top Gland
 - Thread Standard 1: BSP
 - Thread Size 1: 1/2 in
 - Connection Gender 1: Male
 - Material: Brass



7845324 Threaded

PLUMBING, SPRING LOADED, NON RETURN, VALVE, 1/2 IN BSP

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Single
 - Body Material: Brass
 - Maximum Working Pressure: 12 bar
 - Thread Size: 1/2 in
 - Thread Standard: BSPP



486148 Single

PLUMBING, SPRING LOADED, NON RETURN, VALVE, 3/4 IN BSP

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Single
 - Connection: 3/4 in BSPP
 - Body Material: Brass
 - Maximum Working Pressure: 12 bar
 - Thread Size: 3/4 in
 - Thread Standard: BSPP



486158 Single

RS PRO BRASS SINGLE CHECK VALVE, BSPP 1-1/4 IN, 12 BAR

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Single
 - Body Material: Brass
 - Maximum Working Pressure: 12 bar
 - Thread Size: 1-1/4 in
 - Thread Standard: BSPP



486160 Single

PLUMBING, SPRING LOADED, NON RETURN, VALVE, 1 IN BSP FE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Single
 - Connection: 1 in BSPP
 - Body Material: Brass
 - Maximum Working Pressure: 12 bar
 - Thread Size: 1 in
 - Thread Standard: BSPP



486164 Single

PLUMBING, SPRING LOADED, NON RETURN, VALVE, 3/8 IN BSP

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Single
 - Connection: 3/8 in BSPP
 - Body Material: Brass
 - Maximum Working Pressure: 12 bar
 - Thread Size: 3/8 in
 - Thread Standard: BSPP



486170 Single

RS PRO BRASS SINGLE CHECK VALVE, BSP 2 IN, 16 BAR

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Single
 - Body Material: Brass
 - Maximum Working Pressure: 16 bar
 - Thread Size: 2 in
 - Thread Standard: BSP



486182 Single

PLUMBING, BRASS, SWING CHECK VALVE, METAL-METAL SEAT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Single
 - Body Material: Brass
 - Maximum Working Pressure: 16 bar
 - Thread Size: 1 in
 - Thread Standard: BSP



486205 Single

PLUMBING, BRASS, SWING CHECK VALVE, METAL-METAL SEAT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Single
 - Body Material: Brass
 - Maximum Working Pressure: 16 bar
 - Thread Size: 1/2 in
 - Thread Standard: BSP



486209 Single

RS PRO BRASS SINGLE CHECK VALVE, BSP 1-1/4 IN, 16 BAR

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Single
 - Body Material: Brass
 - Maximum Working Pressure: 16 bar
 - Thread Size: 1-1/4 in
 - Thread Standard: BSP



486211 Single

RS PRO BRASS SINGLE CHECK VALVE, BSP 1-1/2IN, 16 BAR

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Single
 - Body Material: Brass
 - Maximum Working Pressure: 16 bar
 - Thread Size: 1-1/2 in
 - Thread Standard: BSP



486221 Single

PLUMBING, SPRING LOADED, NON RETURN, VALVE, 2IN BSP FE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Single
 - Connection: 2 in BSP
 - Body Material: Brass
 - Maximum Working Pressure: 12 bar
 - Thread Size: 2 in
 - Thread Standard: BSPP



486233 Single

RS PRO BRASS SINGLE NON RETURN VALVE 1-1/2 IN BSPP

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Single
 - Connection: 1-1/2 in BSPP
 - Body Material: Brass
 - Maximum Working Pressure: 12 bar
 - Thread Size: 1-1/2 in
 - Thread Standard: BSPP



486237 Single

RS PRO STAINLESS STEEL SINGLE CHECK VALVE, BSP 1/2IN, 14 BAR

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Single
 - Body Material: Stainless Steel
 - Maximum Working Pressure: 14 bar
 - Thread Size: 1/2 in
 - Thread Standard: BSP



4992622 Single

RS PRO STAINLESS STEEL SINGLE CHECK VALVE, BSP 3/4IN, 14 BAR

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Single
 - Body Material: Stainless Steel
 - Maximum Working Pressure: 14 bar
 - Thread Size: 3/4 in
 - Thread Standard: BSP



4992638 Single

RS PRO STAINLESS STEEL SINGLE CHECK VALVE, BSP 1IN, 14 BAR

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Single
 - Body Material: Stainless Steel
 - Maximum Working Pressure: 14 bar
 - Thread Size: 1 in
 - Thread Standard: BSP



4992650 Single

RS PRO STAINLESS STEEL SINGLE CHECK VALVE, BSP 1-1/4IN, 14 BAR

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Single
 - Body Material: Stainless Steel
 - Maximum Working Pressure: 14 bar
 - Thread Size: 1-1/4 in
 - Thread Standard: BSP



4992666 Single

RS PRO STAINLESS STEEL SINGLE CHECK VALVE, BSP 1-1/2IN, 14 BAR

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Single
 - Body Material: Stainless Steel
 - Maximum Working Pressure: 14 bar
 - Thread Size: 1-1/2 in
 - Thread Standard: BSP



4992672 Single

RS PRO STAINLESS STEEL SINGLE CHECK VALVE, BSP 2IN, 14 BAR

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Single
 - Body Material: Stainless Steel
 - Maximum Working Pressure: 14 bar
 - Thread Size: 2 in
 - Thread Standard: BSP



4992688 Single

RS PRO BRONZE SINGLE CHECK VALVE, BSPT 3/4IN, 20 BAR

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Single
 - Body Material: Bronze
 - Maximum Working Pressure: 20 bar
 - Thread Size: 3/4 in
 - Thread Standard: BSPT



5103788 Single

3/4IN. STEAM NON RETURN VALVE BSP

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Single
 - Body Material: Stainless Steel
 - Maximum Working Pressure: 25 bar
 - Thread Size: 3/4 in
 - Thread Standard: BSP



7209273 Single

1/2IN. STEAM NON RETURN VALVE BSP

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Single
 - Body Material: Stainless Steel
 - Maximum Working Pressure: 25 bar
 - Thread Size: 1/2 in
 - Thread Standard: BSP



7209279 Single

1IN. STEAM NON RETURN VALVE BSP

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Single
 - Body Material: Stainless Steel
 - Maximum Working Pressure: 25 bar
 - Thread Size: 1 in
 - Thread Standard: BSP



7209282 Single

RS PRO STAINLESS STEEL SINGLE NON RETURN VALVE 15MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Single
 - Body Material: Stainless Steel
 - Thread Size: 15 mm



7209285 Single

RS PRO STAINLESS STEEL SINGLE NON RETURN VALVE 40MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Single
 - Body Material: Stainless Steel
 - Thread Size: 40 mm



7209295 Single

RS PRO STAINLESS STEEL SINGLE NON RETURN VALVE 25MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Single
 - Body Material: Stainless Steel
 - Thread Size: 25 mm



7209298 Single

RS PRO STAINLESS STEEL NON RETURN VALVE, ANSI 50MM, 40 BAR

- ขนาดบรรจุภัณฑ์: 1 x EA
- Body Material: Stainless Steel
 - Maximum Working Pressure: 40 bar
 - Thread Size: 50 mm
 - Thread Standard: ANSI



7209305 Stainless Steel

RS PRO BRASS SIGHT GLASS NON RETURN VALVE, BSP 1IN, 12 BAR

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Sight Glass
 - Body Material: Brass
 - Maximum Working Pressure: 12 bar
 - Thread Size: 1 in
 - Thread Standard: BSP



7209349 Sight Glass

PLUMBING, FLOAT, PLASTIC, 1/2IN, C/W 5/16 BSW FEMALE BRASS

- ขนาดบรรจุภัณฑ์: 1 x EA
- Connection Size: 1/2 in
 - Compatible Float Diameter 1: 4-1/2 in



797338 1/2 in

RS PRO, BOTTOM ENTRY, FLOAT VALVE, 1/2IN

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Bottom Entry
 - Connection Size: 1/2 in



5426570 Bottom Entry

RS PRO, BOTTOM ENTRY, FLOAT VALVE, 1/2IN

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Bottom Entry
 - Connection Size: 1/2 in
 - Maximum Working Pressure: 16 bar
 - Float Included: Yes



7845611 Bottom Entry

PLUMBING, BRASS, FULLWAY GATE VALVE, BSP THREADED PORTS 1/2IN

- ขนาดบรรจุภัณฑ์: 1 x EA
- Connection: 1/2 in BSPT
 - Maximum Working Pressure: 20 bar
 - Handle Height from Center: 85 mm
 - Body Material: Brass
 - Connection Size: 1/2 in
 - Thread Standard or Connection Type: BSPT Female



2610299 1/2 in BSPT

PLUMBING, BRASS, FULLWAY GATE VALVE, BSP THREADED PORTS 3/4IN

- ขนาดบรรจุภัณฑ์: 1 x EA
- Connection: 3/4 in BSPT
 - Maximum Working Pressure: 20 bar
 - Handle Height from Center: 95 mm
 - Body Material: Brass
 - Connection Size: 3/4 in
 - Thread Standard or Connection Type: BSPT Female



2610306 3/4 in BSPT

PLUMBING, BRASS, FULLWAY GATE VALVE, BSP THREADED PORTS 1IN

- ขนาดบรรจุภัณฑ์: 1 x EA
- Connection: 1 in BSPT
 - Maximum Working Pressure: 20 bar
 - Handle Height from Center: 110 mm
 - Body Material: Brass
 - Connection Size: 1 in
 - Thread Standard or Connection Type: BSPT Female



2610328 1 in BSPT

PLUMBING, BRASS, FULLWAY GATE VALVE, BSP THREADED PORTS 2IN

- ขนาดบรรจุภัณฑ์: 1 x EA
- Connection: 2 in BSPT
 - Maximum Working Pressure: 20 bar
 - Handle Height from Center: 170 mm
 - Body Material: Brass
 - Connection Size: 2 in
 - Thread Standard or Connection Type: BSPT Female



2610356 2 in BSPT

RS PRO GATE VALVE, 3/4IN

- ขนาดบรรจุภัณฑ์: 1 x EA
- Connection: 3/4 in BSPT
 - Maximum Working Pressure: 20 bar
 - Handle Height from Center: 98 mm
 - Body Material: Bronze
 - Disc Material: Bronze
 - Connection Size: 3/4 in
 - Thread Standard or Connection Type: BSPT Female



2842553 3/4 in BSPT

RS PRO GATE VALVE, 1-1/2IN

- ขนาดบรรจุภัณฑ์: 1 x EA
- Connection: 1-1/2 in BSPT
 - Maximum Working Pressure: 20 bar
 - Handle Height from Center: 145 mm
 - Body Material: Bronze
 - Connection Size: 1-1/2 in
 - Thread Standard or Connection Type: BSPT Female



5103823 1-1/2 in BSPT

RS PRO GATE VALVE, 1IN

- ขนาดบรรจุภัณฑ์: 1 x EA
- Connection: 1 in BSPT
 - Maximum Working Pressure: 20 bar
 - Handle Height from Center: 110 mm
 - Body Material: Bronze
 - Connection Size: 1 in
 - Thread Standard or Connection Type: BSPT Female



5103845 1 in BSPT

RS PRO GATE VALVE, 1/2IN

- ขนาดบรรจุภัณฑ์: 1 x EA
- Connection: 1/2 in BSPT
 - Maximum Working Pressure: 20 bar
 - Handle Height from Center: 85 mm
 - Body Material: Bronze
 - Connection Size: 1/2 in
 - Thread Standard or Connection Type: BSPT Female



5103851 1/2 in BSPT

RS PRO GATE VALVE, 2IN

- ขนาดบรรจุภัณฑ์: 1 x EA
- Connection: 2 in BSPT
 - Maximum Working Pressure: 20 bar
 - Handle Height from Center: 170 mm
 - Body Material: Bronze
 - Connection Size: 2 in
 - Thread Standard or Connection Type: BSPT Female



5103867 2 in BSPT

RS PRO GATE VALVE, 1-1/4IN

- ขนาดบรรจุภัณฑ์: 1 x EA
- Connection: 1-1/4 in BSPT
 - Maximum Working Pressure: 20 bar
 - Handle Height from Center: 125 mm
 - Body Material: Bronze
 - Connection Size: 1-1/4 in
 - Thread Standard or Connection Type: BSPT Female



5115078 1-1/4 in BSPT

RS PRO GATE VALVE, 0.59IN

- ขนาดบรรจุภัณฑ์: 1 x EA
- Connection: 15 mm Compression
 - Maximum Working Pressure: 16 bar
 - Handle Height from Center: 80 mm
 - Body Material: Brass
 - Disc Material: Mild Steel
 - Connection Size: 0.59 in
 - Thread Standard or Connection Type: Compression



7845721 15 mm

RS PRO STAINLESS STEEL GLOBE VALVE, 1/2 IN BSP 32 BAR

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Connection: 1/2 in BSP
 - Maximum Working Pressure: 32 bar
 - Body Material: Stainless Steel
 - Connection Gender: Female
 - Thread Size: 1/2 in
 - Thread Standard: BSP



4992559 1/2 in BSP

RS PRO STAINLESS STEEL GLOBE VALVE, 3/4 IN BSP 32 BAR

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Connection: 3/4 in BSP
 - Maximum Working Pressure: 32 bar
 - Body Material: Stainless Steel
 - Connection Gender: Female
 - Thread Size: 3/4 in
 - Thread Standard: BSP



4992565 3/4 in BSP

RS PRO STAINLESS STEEL GLOBE VALVE, 1 IN BSP 32 BAR

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Connection: 1 in BSP
 - Maximum Working Pressure: 32 bar
 - Body Material: Stainless Steel
 - Connection Gender: Female
 - Thread Size: 1 in
 - Thread Standard: BSP



4992571 1 in BSP

RS PRO STAINLESS STEEL GLOBE VALVE, 1-1/4 IN BSP 32 BAR

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Connection: 1-1/4 in BSP
 - Maximum Working Pressure: 32 bar
 - Body Material: Stainless Steel
 - Connection Gender: Female
 - Thread Size: 1-1/4 in
 - Thread Standard: BSP



4992593 1-1/4 in BSP

RS PRO STAINLESS STEEL GLOBE VALVE, 2 IN BSP 32 BAR

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Connection: 2 in BSP
 - Maximum Working Pressure: 32 bar
 - Body Material: Stainless Steel
 - Connection Gender: Female
 - Thread Size: 2 in
 - Thread Standard: BSP



4992616 2 in BSP

RS PRO 1 BAR ALUMINIUM HEATING OIL FILTER, 1/4 IN BSPP, 61 X 61 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Connection: 1/4 in BSPP
 - Dimensions: 61 x 61 x 75 mm
 - Height: 75 mm
 - Width: 61 mm
 - Length: 61 mm
 - Maximum Working Pressure: 1 bar
 - Micron Size: 100 µm
 - Housing Material: Aluminium



3137048 1/4 in BSPP

RS PRO 2 BAR ALUMINIUM HEATING OIL FILTER, 3/8 IN BSPP, 61 X 61 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Connection: 3/8 in BSPP
 - Dimensions: 61 x 61 x 75 mm
 - Height: 75 mm
 - Width: 61 mm
 - Length: 61 mm
 - Maximum Working Pressure: 2 bar
 - Micron Size: 100 µm
 - Housing Material: Aluminium



3137060 3/8 in BSPP

RS PRO 1 BAR ALUMINIUM HEATING OIL FILTER, 1/2 IN BSPP, 81 X 81 X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Connection: 1/2 in BSPP
 - Dimensions: 81 x 81 x 84 mm
 - Height: 84 mm
 - Width: 81 mm
 - Length: 81 mm
 - Maximum Working Pressure: 1 bar
 - Micron Size: 100 µm
 - Housing Material: Aluminium



3137098 1/2 in BSPP

RS PRO HOSE ASSEMBLY, FEMALE 1/2IN TO 15MM, 10 BAR (DN20, DN25),

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 450 mm
 - Connection Gender 1: Female
 - Connection Size 1: 1/2 in
 - Connection Size 2: 15 mm
 - Material: Brass, EPDM
 - Maximum Working Pressure: 10 bar (DN20, DN25), 12 bar (DN10, DN13)
 - Liner Material: EPDM



1904127 450 mm

RS PRO HOSE ASSEMBLY, FEMALE BSP 1/2IN TO COMPRESSION 15MM,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 300 mm
 - Connection Gender 1: Female
 - Thread Standard or Connection Type 1: BSP
 - Connection Size 1: 1/2 in
 - Thread Standard or Connection Type 2: Compression
 - Connection Size 2: 15 mm
 - Material: Brass, EPDM
 - Maximum Working Pressure: 15 bar



7118442 300 mm

BRAIDED HOSE 1/2IN BSPP F-F 300MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 300 mm
 - Connection Gender 1: Female
 - Thread Standard or Connection Type 1: BSP
 - Connection Size 1: 1/2 in
 - Connection Gender 2: Female
 - Thread Standard or Connection Type 2: BSP
 - Connection Size 2: 1/2 in
 - Material: Brass, EPDM



7118451 300 mm

BRAIDED HOSE ELBOW 1/2IN BSPP F-F 300MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 300 mm
 - Connection Gender 1: Female
 - Thread Standard or Connection Type 1: BSP
 - Connection Size 1: 1/2 in
 - Connection Gender 2: Female
 - Thread Standard or Connection Type 2: BSP
 - Connection Size 2: 1/2 in
 - Material: Brass, EPDM



7118467 300 mm

BRAIDED HOSE 3/4IN BSPPX 3/4IN BSPP 30CM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 300 mm
 - Connection Gender 1: Female
 - Thread Standard or Connection Type 1: BSP
 - Connection Size 1: 3/4 in
 - Connection Gender 2: Male
 - Thread Standard or Connection Type 2: BSP
 - Connection Size 2: 3/4 in
 - Material: Brass, EPDM



7118495 300 mm

RS PRO HOSE ASSEMBLY BSP 3/4IN TO BSP 3/4IN, 6 BAR, 1.5M LONG

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 1.5 m
 - Thread Standard or Connection Type 1: BSP
 - Connection Size 1: 3/4 in
 - Thread Standard or Connection Type 2: BSP
 - Connection Size 2: 3/4 in
 - Material: Polyethylene Terephthalate (PET)
 - Maximum Working Pressure: 6 bar
 - Suitable Applications: Potable Water



7118509 1.5 m

RS PRO HOSE ASSEMBLY BSP 3/4IN TO BSP 3/4IN, 6 BAR, 2.5M LONG

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 2.5 m
 - Thread Standard or Connection Type 1: BSP
 - Connection Size 1: 3/4 in
 - Thread Standard or Connection Type 2: BSP
 - Connection Size 2: 3/4 in
 - Material: Polyethylene Terephthalate (PET)
 - Maximum Working Pressure: 6 bar
 - Suitable Applications: Potable Water



7118518 2.5 m

RS PRO FLEXIBLE SANITARY HOSE, 1.5M LONG

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 1.5 m
 - Material: PVC
 - Suitable Applications: Household Appliances



7844964 1.5 m

RS PRO HOSE ASSEMBLY 15MM TO FEMALE BSP 1/2IN, 900MM LONG

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 900 mm
 - Connection Size 1: 15 mm
 - Connection Gender 2: Female
 - Thread Standard or Connection Type 2: BSP
 - Connection Size 2: 1/2 in
 - Material: Brass, EPDM, Stainless Steel
 - Suitable Applications: Sanitary Installation



7845093 900 mm

RS PRO HOSE ASSEMBLY 15MM TO FEMALE BSP 1/2IN, 500MM LONG

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 500 mm
 - Connection Size 1: 15 mm
 - Connection Gender 2: Female
 - Thread Standard or Connection Type 2: BSP
 - Connection Size 2: 1/2 in
 - Material: Brass, EPDM, Stainless Steel
 - Suitable Applications: Sanitary Installation



7845260 500 mm

RS PRO HOSE ASSEMBLY 15MM TO FEMALE BSP 1/2IN, 900MM LONG

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 900 mm
 - Connection Size 1: 15 mm
 - Connection Gender 2: Female
 - Thread Standard or Connection Type 2: BSP
 - Connection Size 2: 1/2 in
 - Material: Brass, EPDM, Stainless Steel
 - Suitable Applications: Sanitary Installation



7845263 900 mm

RS PRO HOSE ASSEMBLY, FEMALE 15MM TO FEMALE 1/2IN, 500MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 500 mm
 - Connection Gender 1: Female
 - Connection Size 1: 15 mm
 - Connection Gender 2: Female
 - Connection Size 2: 1/2 in
 - Material: EPDM, Stainless Steel
 - Suitable Applications: Cold Water, Hot Water
 - Liner Material: EPDM, Stainless Steel



7845291 500 mm

RS PRO FLEXIBLE SANITARY HOSE, 2.5M LONG

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Length: 2.5 m
 - Material: PVC
 - Suitable Applications: Household Appliances



7845658 2.5 m

RS PRO HOSE CONNECTOR HEXAGON NUT 2IN ID

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Connector Type: Hexagon Nut
 - Connector Gender: Male
 - Hose Inner Diameter: 2 in
 - Body Material: Stainless Steel



2654340 Hexagon Nut

RS PRO HOSE CONNECTOR COUPLING UNION 2-1/2IN ID

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Connector Type: Coupling Union
 - Connector Gender: Male
 - Hose Inner Diameter: 2-1/2 in
 - Body Material: Stainless Steel



2654479 Coupling Union

RS PRO HOSE CONNECTOR HOSE LINER 2IN ID

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Connector Type: Hose Liner
 - Connector Gender: Male
 - Hose Inner Diameter: 2 in
 - Body Material: Stainless Steel



2654564 Hose Liner

RS PRO HOSE CONNECTOR DUST CAP 2IN ID

- ขนาดบรรจุภัณฑ์: **2 x EA**
- Hose Connector Type: Dust Cap
 - Connector Gender: Male
 - Hose Inner Diameter: 2 in
 - Body Material: Stainless Steel



2654621 Dust Cap

RS PRO HOSE CONNECTOR DUST CAP 3IN ID

- ขนาดบรรจุภัณฑ์: **2 x EA**
- Hose Connector Type: Dust Cap
 - Connector Gender: Male
 - Hose Inner Diameter: 3 in
 - Body Material: Stainless Steel



2654643 Dust Cap

PLUMBING, BALL, VALVE, MIN, HANDLE CONTROL, 1/4IN FEMALE-FEMALE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Manufacturer Series: S.35
 - Number of Ports: 2-way
 - Connection Port Thread: G 1/4
 - Body Material: Chrome Plated Brass
 - Seal Material: PTFE
 - Maximum Operating Pressure: 30 bar
 - Thread Standard: G
 - Thread Size: 1/4 in



486277 S.35

PLUMBING, BALL, VALVE, MIN, HANDLE CONTROL, 1/4IN MALE-FEMALE ENDS

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Manufacturer Series: S.35
 - Number of Ports: 2-way
 - Connection Port Thread: G 1/4
 - Body Material: Chrome Plated Brass
 - Seal Material: PTFE
 - Maximum Operating Pressure: 30 bar
 - Thread Standard: G
 - Thread Size: 1/4 in



486334 S.35

RS PRO CHROME PLATED BRASS HYDRAULIC BALL VALVE G 3/8

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Manufacturer Series: S.35
 - Number of Ports: 2-way
 - Connection Port Thread: G 3/8
 - Body Material: Chrome Plated Brass
 - Seal Material: PTFE
 - Maximum Operating Pressure: 30 bar
 - Thread Standard: G
 - Thread Size: 3/8 in



486340 S.35

PLUMBING, BALL, VALVE, MIN, HANDLE CONTROL, 1/2IN FEMALE-FEMALE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Manufacturer Series: S.35
 - Number of Ports: 2-way
 - Connection Port Thread: G 1/2
 - Body Material: Chrome Plated Brass
 - Seal Material: PTFE
 - Maximum Operating Pressure: 30 bar
 - Thread Standard: G
 - Thread Size: 1/2 in



486350 S.35

PLUMBING, BALL, VALVE, MIN, HANDLE CONTROL, 1/2IN MALE-FEMALE ENDS

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Manufacturer Series: S.35
 - Number of Ports: 2-way
 - Connection Port Thread: G 1/2
 - Body Material: Chrome Plated Brass
 - Seal Material: PTFE
 - Maximum Operating Pressure: 30 bar
 - Thread Standard: G
 - Thread Size: 1/2 in



486356 S.35

PLUMBING, BALL, VALVE, MIN, HANDLE CONTROL, 3/8IN MALE-FEMALE ENDS

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Manufacturer Series: S.35
 - Number of Ports: 2-way
 - Connection Port Thread: G 3/8
 - Body Material: Chrome Plated Brass
 - Seal Material: PTFE
 - Maximum Operating Pressure: 30 bar
 - Thread Standard: G
 - Thread Size: 3/8 in



486366 S.35

RS PRO LIMIT SWITCH, NO/NC, IP67, ALUMINIUM HOUSING

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Normal State Configuration: NO/NC
 - IP Rating: IP67
 - Housing Material: Aluminium
 - Connection Type: M20
 - Length: 112 mm
 - Maximum Operating Temperature: +80 °C
 - Minimum Operating Temperature: -20 °C
 - Depth: 93 mm



7605722 NO/NC

RS PRO SWITCHBOX, IP67, ALUMINIUM HOUSING

- ขนาดบรรจุภัณฑ์: **1 x EA**
- IP Rating: IP67
 - Housing Material: Aluminium
 - Connection Type: M20
 - Minimum Operating Temperature: -20 °C
 - Maximum Operating Temperature: +80 °C



7998840 IP67

RS PRO BLACK MALLEABLE IRON FITTING BARREL NIPPLE, MALE BSPT

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Fitting Type: Barrel Nipple
 - Connection Gender 1: Male
 - Thread Standard 1: BSPT
 - Thread Size 1: 3/8 in
 - Connection Gender 2: Male
 - Thread Standard 2: BSPT
 - Thread Size 2: 3/8 in
 - Finish: Black



2577906 Barrel Nipple

RS PRO BLACK MALLEABLE IRON FITTING BARREL NIPPLE, MALE BSPT

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Fitting Type: Barrel Nipple
 - Connection Gender 1: Male
 - Thread Standard 1: BSPT
 - Thread Size 1: 1 in
 - Connection Gender 2: Male
 - Thread Standard 2: BSPT
 - Thread Size 2: 1 in
 - Finish: Black



2577928 Barrel Nipple

RS PRO BLACK MALLEABLE IRON FITTING BARREL NIPPLE, MALE BSPT

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Fitting Type: Barrel Nipple
 - Connection Gender 1: Male
 - Thread Standard 1: BSPT
 - Thread Size 1: 1/2 in
 - Connection Gender 2: Male
 - Thread Standard 2: BSPT
 - Thread Size 2: 1/2 in
 - Finish: Black



2578331 Barrel Nipple

RS PRO MOTORISED VALVE, BALL TYPE , 1000 PSI

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Maximum Working Pressure: 1000 psi
 - Valve Type: Ball



7605700 1000 psi

RS PRO MOTORISED VALVE, BALL TYPE , 1000 PSI

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Maximum Working Pressure: 1000 psi
 - Valve Type: Ball



7605712 1000 psi

RS PRO 24 V DC 2 PORT MOTORISED VALVE, BALL VALVE TYPE , 3/4IN PIPE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Compatible Pipe Size: 3/4 in
 - Number of Ports: 2
 - Maximum Working Pressure: 1000 psi
 - Supply Voltage: 24 V dc
 - Valve Type: Ball Valve



7605719 3/4 in

RS PRO MOTORISED VALVE, BALL TYPE , 1000 PSI

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Maximum Working Pressure: 1000 psi
 - Valve Type: Ball



7605728 1000 psi

RS PRO 24 V, 110 V, 220 V 3 PORT MOTORISED VALVE, BALL VALVE TYPE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Compatible Pipe Size: 1/2 in
 - Number of Ports: 3
 - Maximum Working Pressure: 1000 psi
 - Supply Voltage: 24 V, 110 V, 220 V
 - Body Material: Stainless Steel
 - Valve Type: Ball Valve



7998834 1/2 in

RS PRO 24 V, 110 V, 220 V 3 PORT MOTORISED VALVE, BALL VALVE TYPE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Compatible Pipe Size: 1 in
 - Number of Ports: 3
 - Maximum Working Pressure: 1000 psi
 - Supply Voltage: 24 V, 110 V, 220 V
 - Body Material: Stainless Steel
 - Valve Type: Ball Valve



7998847 1 in

TUBE,BENDER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Pipe Material: Aluminium, Copper, Steel
 - Suitable Pipe Diameters: 6, 8, 10 mm



3883684 Aluminium,

PLUMBING,CLIP,PIPE,STAINLESS STEEL,1IN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Pipe Diameter: 1 in
 - Type: Hinged Pipe Clip
 - Material: Stainless Steel
 - Fixing Hole Diameter: 1 in
 - Colour: Silver



2654889 1 in

RS PRO STAINLESS STEEL SILVER HINGED PIPE CLAMP, 2 1/2IN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Pipe Diameter: 2-1/2 in
 - Type: Hinged Pipe Clip
 - Material: Stainless Steel
 - Fixing Hole Diameter: 2 1/2 in
 - Colour: Silver



2654895 2-1/2 in

PLUMBING,CLIP,PIPE,STAINLESS STEEL,3IN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Pipe Diameter: 3 in
 - Type: Hinged Pipe Clip
 - Material: Stainless Steel
 - Fixing Hole Diameter: 3 in
 - Colour: Silver



2654902 3 in

PLUMBING,PIPE,CLIP,STAINLESS STEEL,1 1/2IN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Pipe Diameter: 1-1/2 in
 - Type: Hinged Pipe Clip
 - Material: Stainless Steel
 - Fixing Hole Diameter: 1 1/2 in
 - Colour: Silver



2655270 1-1/2 in

PLUMBING, PIPE, CLIP, STAINLESS STEEL, 2IN

- ขนาดบรรจุภัณฑ์: 1 x EA
- Pipe Diameter: 2 in
 - Type: Hinged Pipe Clip
 - Material: Stainless Steel
 - Fixing Hole Diameter: 2 in
 - Colour: Silver



2655286 2 in

15MM CHROME EFFECT STAND OFF CLIPS

- ขนาดบรรจุภัณฑ์: 2 x EA
- Type: Pipe Stand Off Bracket
 - Pipe Diameter: 15 mm
 - Material: Brass
 - Height: 20 mm
 - Width: 152 mm
 - Finish: Chrome Plated
 - Colour: Silver



7845002 Pipe Stand Off

TAPE, INSULATION, SELF ADHESIVE, 15MX50X3MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Length: 15 m
 - Material: Nitrile Rubber
 - Wall Thickness: 3 mm
 - Colour: Black



486069 15 m

RS PRO 90° KNUCKLE BEND PVC PIPE FITTING, 32MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Fitting Type: Knuckle Bend
 - Fitting Direction: 90°
 - Compatible Pipe Size: 32 mm
 - Colour: White



1960544 Knuckle Bend

RS PRO 135° MULTI-FIT BEND PVC PIPE FITTING, 40MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Fitting Type: Multi-Fit Bend
 - Fitting Direction: 135°
 - Compatible Pipe Size: 40 mm
 - Colour: White



1960546 Multi-Fit Bend

RS PRO STRAIGHT COUPLER PVC PIPE FITTING, 40MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Fitting Type: Coupler
 - Fitting Direction: Straight
 - Compatible Pipe Size: 40 mm
 - Colour: White



1960548 Coupler

RS PRO 88° TEE SWEPT TEE PVC PIPE FITTING, 40MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Fitting Type: Swept Tee
 - Compatible Pipe Size: 40 mm
 - Colour: White



1960549 Swept Tee

CLEANER, PIPE AND SINK

- ขนาดบรรจุภัณฑ์: 1 x EA
- Type: Wire Cleaner
 - Application: Clearing Sink; Bath & Shower Waste Pipes



3888409 Wire Cleaner

RS PRO BALL TYPE PNEUMATIC ACTUATED VALVE, BSP 3/8IN, 40 BAR

- ขนาดบรรจุภัณฑ์: 1 x EA
- Valve Type: Ball
 - Default Valve Position: NC
 - Return Type: Direct Action
 - Thread Standard: BSP
 - Thread Size: 3/8 in
 - Maximum Working Pressure: 40 bar



7605573 Ball

RS PRO BALL TYPE PNEUMATIC ACTUATED VALVE, BSP 1/2IN, 40 BAR

- ขนาดบรรจุภัณฑ์: 1 x EA
- Valve Type: Ball
 - Default Valve Position: NC
 - Return Type: Direct Action
 - Thread Standard: BSP
 - Thread Size: 1/2 in
 - Maximum Working Pressure: 40 bar



7605576 Ball

RS PRO BALL TYPE PNEUMATIC ACTUATED VALVE, BSP 1-1/2IN, 40 BAR

- ขนาดบรรจุภัณฑ์: 1 x EA
- Valve Type: Ball
 - Default Valve Position: NC
 - Return Type: Direct Action
 - Thread Standard: BSP
 - Thread Size: 1-1/2 in
 - Maximum Working Pressure: 40 bar



7605586 Ball

RS PRO BALL TYPE PNEUMATIC ACTUATED VALVE, BSP 1IN, 40 BAR

- ขนาดบรรจุภัณฑ์: 1 x EA
- Valve Type: Ball
 - Default Valve Position: NC
 - Return Type: Direct Action
 - Thread Standard: BSP
 - Thread Size: 1 in
 - Maximum Working Pressure: 40 bar



7605589 Ball

RS PRO BALL TYPE PNEUMATIC ACTUATED VALVE, BSP 2IN, 40 BAR

- ขนาดบรรจุภัณฑ์: 1 x EA
- Valve Type: Ball
 - Default Valve Position: NC
 - Return Type: Direct Action
 - Thread Standard: BSP
 - Thread Size: 2 in
 - Maximum Working Pressure: 40 bar



7605595 Ball

RS PRO BALL TYPE PNEUMATIC ACTUATED VALVE, BSP 1/2IN, 40 BAR

- ขนาดบรรจุภัณฑ์: 1 x EA
- Valve Type: Ball
 - Default Valve Position: NC
 - Return Type: Spring
 - Thread Standard: BSP
 - Thread Size: 1/2 in
 - Maximum Working Pressure: 40 bar



7605602 Ball

RS PRO BALL TYPE PNEUMATIC ACTUATED VALVE, BSP 1/4IN, 40 BAR

- ขนาดบรรจุภัณฑ์: 1 x EA
- Valve Type: Ball
 - Default Valve Position: NC
 - Return Type: Spring
 - Thread Standard: BSP
 - Thread Size: 1/4 in
 - Maximum Working Pressure: 40 bar



7605609 Ball

RS PRO BALL TYPE PNEUMATIC ACTUATED VALVE, BSP 1-1/4IN, 40 BAR

- ขนาดบรรจุภัณฑ์: 1 x EA
- Valve Type: Ball
 - Default Valve Position: NC
 - Return Type: Spring
 - Thread Standard: BSP
 - Thread Size: 1-1/4 in
 - Maximum Working Pressure: 40 bar



7605618 Ball

RS PRO BALL TYPE PNEUMATIC ACTUATED VALVE, BSP 1IN, 1000 PSI

ขนาดบรรจุภัณฑ์: **1 x EA**

- Valve Type: Ball
- Default Valve Position: NC
- Return Type: Direct Action
- Thread Standard: BSP
- Thread Size: 1 in
- Maximum Working Pressure: 1000 psi



7605633 Ball

RS PRO BALL TYPE PNEUMATIC ACTUATED VALVE, BSP 1/4IN, 1000 PSI

ขนาดบรรจุภัณฑ์: **1 x EA**

- Valve Type: Ball
- Default Valve Position: NC
- Return Type: Spring
- Thread Standard: BSP
- Thread Size: 1/4 in
- Maximum Working Pressure: 1000 psi



7605643 Ball

RS PRO BALL TYPE PNEUMATIC ACTUATED VALVE, BSP 2IN, 1000 PSI

ขนาดบรรจุภัณฑ์: **1 x EA**

- Valve Type: Ball
- Default Valve Position: NC
- Return Type: Direct Action
- Thread Standard: BSP
- Thread Size: 2 in
- Maximum Working Pressure: 1000 psi



7605649 Ball

RS PRO BALL TYPE PNEUMATIC ACTUATED VALVE, BSP 3/4IN, 1000

ขนาดบรรจุภัณฑ์: **1 x EA**

- Valve Type: Ball
- Default Valve Position: NC
- Return Type: Spring
- Thread Standard: BSP
- Thread Size: 3/4 in
- Maximum Working Pressure: 1000 psi



7605659 Ball

RS PRO BALL TYPE PNEUMATIC ACTUATED VALVE, BSP 1IN, 1000 PSI

ขนาดบรรจุภัณฑ์: **1 x EA**

- Valve Type: Ball
- Default Valve Position: NC
- Return Type: Spring
- Thread Standard: BSP
- Thread Size: 1 in
- Maximum Working Pressure: 1000 psi



7605668 Ball

RS PRO BALL TYPE PNEUMATIC ACTUATED VALVE, BSP 2IN, 1000 PSI

ขนาดบรรจุภัณฑ์: **1 x EA**

- Valve Type: Ball
- Default Valve Position: NC
- Return Type: Spring
- Thread Standard: BSP
- Thread Size: 2 in
- Maximum Working Pressure: 1000 psi



7605674 Ball

RS PRO BALL TYPE PNEUMATIC ACTUATED VALVE, BSP 1IN, 40 BAR

ขนาดบรรจุภัณฑ์: **1 x EA**

- Valve Type: Ball
- Default Valve Position: NC
- Return Type: Direct Action
- Thread Standard: BSP
- Thread Size: 1 in
- Maximum Working Pressure: 40 bar



7605687 Ball

RS PRO BALL TYPE PNEUMATIC ACTUATED VALVE, BSP 2IN, 40 BAR

ขนาดบรรจุภัณฑ์: **1 x EA**

- Valve Type: Ball
- Default Valve Position: NC
- Return Type: Direct Action
- Thread Standard: BSP
- Thread Size: 2 in
- Maximum Working Pressure: 40 bar



7605693 Ball

RS PRO BALL TYPE PNEUMATIC ACTUATED VALVE 2IN, 800 PSI

ขนาดบรรจุภัณฑ์: **1 x EA**

- Valve Type: Ball
- Return Type: Spring
- Thread Size: 2 in
- Maximum Working Pressure: 800 psi



7998796 Ball

RS PRO BUTTERFLY TYPE PNEUMATIC ACTUATED VALVE 2IN

ขนาดบรรจุภัณฑ์: **1 x EA**

- Valve Type: Butterfly
- Thread Size: 2 in



7998799 Butterfly

RS PRO BUTTERFLY TYPE PNEUMATIC ACTUATED VALVE 3IN

ขนาดบรรจุภัณฑ์: **1 x EA**

- Valve Type: Butterfly
- Thread Size: 3 in



7998800 Butterfly

RS PRO TUBING SLEEVE

ขนาดบรรจุภัณฑ์: **1 x EA**

- Accessory Type: Tubing Sleeve
- Connector A - Thread Size: 3/8
- Connector B - Thread Size: 3/8
- Connector B - Thread Standard: BSP



3522020 Tubing Sleeve

RS PRO PRESSURE GAUGE COCK 3/8 IN G FEMALE 3/8 IN G MALE

ขนาดบรรจุภัณฑ์: **1 x EA**

- Connection 1: 3/8 in G Female
- Connection 2: 3/8 in G Male
- Maximum Working Pressure: 16 bar
- Connection Gender 1: Female
- Connection Gender 2: Male
- Thread Size 1: 3/8 in
- Thread Size 2: 3/8 in
- Thread Standard 1: G



189046 3/8 in G Female

RS PRO PRESSURE GAUGE COCK 3/8 IN BSP FEMALE 3/8 IN BSP FEMALE

ขนาดบรรจุภัณฑ์: **1 x EA**

- Connection 1: 3/8 in BSP Female
- Connection 2: 3/8 in BSP Female
- Maximum Working Pressure: 16 bar
- Connection Gender 1: Female
- Connection Gender 2: Female
- Thread Size 1: 3/8 in
- Thread Size 2: 3/8 in
- Thread Standard 1: BSP



3521998 3/8 in BSP

RS PRO PRESSURE GAUGE COCK 1/2 IN BSP FEMALE 1/2 IN BSP FEMALE

ขนาดบรรจุภัณฑ์: **1 x EA**

- Connection 1: 1/2 in BSP Female
- Connection 2: 1/2 in BSP Female
- Maximum Working Pressure: 16 bar
- Connection Gender 1: Female
- Connection Gender 2: Female
- Thread Size 1: 1/2 in
- Thread Size 2: 1/2 in
- Thread Standard 1: BSP



3522014 1/2 in BSP Female

PLUMBING, VALVE, PRESSURE REDUCING, BRASS, CHROMIUM

ขนาดบรรจุภัณฑ์: **1 x EA**

- Connection: 1/2 in Screwed Iron Female
- Minimum Outlet Pressure: 1 bar
- Maximum Outlet Pressure: 6 bar
- Body Material: Chrome Plated Brass
- Maximum Flow Rate: 2 L/s
- Connection Gender: Female
- Connection Size: 1/2 in
- Thread Standard or Connection Type: Screwed Iron



761345 1/2 in Screwed

PLUMBING, VALVE, PRESSURE REDUCING, BRASS, CHROMIUM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Connection: 3/4 in Screwed Iron Female
 - Minimum Outlet Pressure: 1 bar
 - Maximum Outlet Pressure: 6 bar
 - Body Material: Chrome Plated Brass
 - Maximum Flow Rate: 2 L/s
 - Connection Gender: Female
 - Connection Size: 3/4 in
 - Thread Standard or Connection Type: Screwed Iron



761351 3/4 in Screwed

PLUMBING, CLASS 600, STAINLESS STEEL, Y STRAINER VALVE, 1/4 IN BSP

- ขนาดบรรจุภัณฑ์: 1 x EA
- Strainer or Filter: Strainer
 - Suitable Media: Liquid
 - Connection: 1/4 in BSP
 - Body Material: Stainless Steel
 - Connection Size: 1/4 in
 - Maximum Working Pressure: 800 WOG
 - Thread Standard or Connection Type: BSP



4992694 Strainer

PLUMBING, CLASS 600, STAINLESS STEEL, Y STRAINER VALVE, 3/8 IN BSP

- ขนาดบรรจุภัณฑ์: 1 x EA
- Strainer or Filter: Strainer
 - Suitable Media: Liquid
 - Connection: 3/8 in BSP
 - Body Material: Stainless Steel
 - Connection Size: 3/8 in
 - Maximum Working Pressure: 800 WOG
 - Thread Standard or Connection Type: BSP



4992717 Strainer

RS PRO, 1/2 IN BSP STAINLESS STEEL Y STRAINER

- ขนาดบรรจุภัณฑ์: 1 x EA
- Strainer or Filter: Strainer
 - Suitable Media: Liquid
 - Connection: 1/2 in BSP
 - Body Material: Stainless Steel
 - Connection Size: 1/2 in
 - Maximum Working Pressure: 40 bar
 - Thread Standard or Connection Type: BSP



4992723 Strainer

RS PRO, 3/4 IN BSP STAINLESS STEEL Y STRAINER

- ขนาดบรรจุภัณฑ์: 1 x EA
- Strainer or Filter: Strainer
 - Suitable Media: Liquid
 - Connection: 3/4 in BSP
 - Body Material: Stainless Steel
 - Connection Size: 3/4 in
 - Maximum Working Pressure: 800 WOG
 - Thread Standard or Connection Type: BSP



4992739 Strainer

RS PRO, 1 IN BSP STAINLESS STEEL Y STRAINER

- ขนาดบรรจุภัณฑ์: 1 x EA
- Strainer or Filter: Strainer
 - Suitable Media: Liquid
 - Connection: 1 in BSP
 - Body Material: Stainless Steel
 - Connection Size: 1 in
 - Maximum Working Pressure: 40 bar
 - Thread Standard or Connection Type: BSP



4992745 Strainer

RS PRO, 1-1/4 IN BSP STAINLESS STEEL Y STRAINER

- ขนาดบรรจุภัณฑ์: 1 x EA
- Strainer or Filter: Strainer
 - Suitable Media: Liquid
 - Connection: 1-1/4 in BSP
 - Body Material: Stainless Steel
 - Connection Size: 1-1/4 in
 - Maximum Working Pressure: 800 WOG
 - Thread Standard or Connection Type: BSP



4992751 Strainer

PLUMBING, CLASS 600, STAINLESS STEEL, Y STRAINER VALVE, 2 IN BSP

- ขนาดบรรจุภัณฑ์: 1 x EA
- Strainer or Filter: Strainer
 - Suitable Media: Liquid
 - Connection: 2 in BSP
 - Body Material: Stainless Steel
 - Connection Size: 2 in
 - Maximum Working Pressure: 800 WOG
 - Thread Standard or Connection Type: BSP



4992773 Strainer

AUTOMATIC AIR VENT RS PRO

- ขนาดบรรจุภัณฑ์: 1 x EA
- Connection 1: 3/8 in BSPT
 - Connection 2: 2 in BSPT
 - Body Material: Brass
 - Valve Type: Manual
 - Maximum Working Pressure: 10 bar
 - Connection Size 1: 3/8 in
 - Connection Size 2: 3/8 in
 - Thread Standard or Connection Type 1: BSPT



3137032 3/8 in BSPT

RS PRO MAGNETIC SCALE INHIBITOR, 64.8L/MIN

- ขนาดบรรจุภัณฑ์: 1 x EA
- Scale Prevention Mechanism: Magnetic
 - Connection: 15 mm Compression
 - Maximum Flow Rate: 64.8 L/min
 - Maximum Working Pressure: 12 bar
 - Connection Size: 15 mm
 - WRAS Approval: Yes
 - Thread Standard or Connection Type: Compression



7382719 Magnetic

RS PRO MAGNETIC & ELECTROLYTIC SCALE INHIBITOR, 64.8L/MIN

- ขนาดบรรจุภัณฑ์: 1 x EA
- Scale Prevention Mechanism: Magnetic & Electrolytic
 - Connection: 22 mm Compression
 - Maximum Flow Rate: 64.8 L/min
 - Maximum Working Pressure: 12 bar
 - Connection Size: 22 mm
 - WRAS Approval: Yes
 - Thread Standard or Connection Type: Compression



7382734 Magnetic G

RS PRO STAINLESS STEEL PIPE FITTING HEXAGON PLUG, MALE NPT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Fitting Type: Plug
 - Pipe Fitting Connection Type: Threaded
 - Shape: Hexagon
 - Thread Size: 1/2 in
 - Connection Gender: 1: Male
 - Thread Standard 1: NPT



2226591 Plug

RS PRO STAINLESS STEEL PIPE FITTING HEXAGON PLUG, MALE NPT

- ขนาดบรรจุภัณฑ์: 1 x EA
- Fitting Type: Plug
 - Pipe Fitting Connection Type: Threaded
 - Shape: Hexagon
 - Thread Size: 3/4 in
 - Connection Gender 1: Male
 - Thread Standard 1: NPT



2226614 Plug

RS PRO STAINLESS STEEL PIPE FITTING HEXAGON NIPPLE JOINT,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Fitting Type: Nipple
 - Pipe Fitting Connection Type: Threaded
 - Shape: Hexagon
 - Thread Size 1: 1/2 in
 - Thread Size 2: 1/2 in
 - Connection Gender 1: Male
 - Connection Gender 2: Male
 - Thread Standard 1: NPT



2226636 Nipple

RS PRO STAINLESS STEEL PIPE FITTING HEXAGON NIPPLE JOINT,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Fitting Type: Nipple
 - Pipe Fitting Connection Type: Threaded
 - Shape: Hexagon
 - Thread Size 1: 1 in
 - Thread Size 2: 1 in
 - Connection Gender 1: Male
 - Connection Gender 2: Male
 - Thread Standard 1: NPT



2226658 Nipple

RS PRO STAINLESS STEEL PIPE FITTING, 90° ELBOW 25.4MM

- ขนาดบรรจุภัณฑ์: 1 x EA
- Fitting Type: Elbow
 - Pipe Fitting Connection Type: Solder
 - Fitting Direction: 90°
 - Thread Size 1: 25.4 mm



2654047 Elbow

RS PRO STAINLESS STEEL PIPE FITTING, 90° ELBOW 38.1MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Fitting Type: Elbow
 - Pipe Fitting Connection Type: Solder
 - Fitting Direction: 90°
 - Thread Size 1: 38.1 mm



2654053 Elbow

RS PRO STAINLESS STEEL PIPE FITTING, 90° ELBOW 50.8MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Fitting Type: Elbow
 - Pipe Fitting Connection Type: Solder
 - Fitting Direction: 90°
 - Thread Size 1: 50.8 mm



2654069 Elbow

RS PRO STAINLESS STEEL PIPE FITTING, 90° ELBOW 50.8MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Fitting Type: Elbow
 - Pipe Fitting Connection Type: Solder
 - Fitting Direction: 90°
 - Thread Size 1: 50.8 mm



2654126 Elbow

RS PRO STAINLESS STEEL PIPE FITTING, 45° ELBOW 38.1MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Fitting Type: Elbow
 - Pipe Fitting Connection Type: Solder
 - Fitting Direction: 45°
 - Thread Size 1: 38.1 mm



4793245 Elbow

PLUMBING,ELBOW,EQUAL,STAINLESS STEEL 316,BSP

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Fitting Type: Elbow
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: 90°
 - Thread Size 1: 1/4 in
 - Thread Size 2: 1/4 in
 - Connection Gender 1: Female
 - Connection Gender 2: Female
 - Thread Standard 1: G



4992852 Elbow

PLUMBING,ELBOW,EQUAL,STAINLESS STEEL 316,BSP

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Fitting Type: Elbow
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: 90°
 - Thread Size 1: 3/8 in
 - Thread Size 2: 3/8 in
 - Connection Gender 1: Female
 - Connection Gender 2: Female
 - Thread Standard 1: G



4992874 Elbow

PLUMBING,TEE,EQUAL,STAINLESS STEEL 316,BSP

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Fitting Type: Tee
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Tee
 - Shape: Circular
 - Thread Size 1: 1/4 in
 - Thread Size 2: 1/4 in
 - Thread Size 3: 1/4 in
 - Connection Gender 1: Female



4992880 Tee

PLUMBING,TEE,EQUAL,STAINLESS STEEL 316,BSP

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Fitting Type: Tee
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Tee
 - Shape: Circular
 - Thread Size 1: 3/8 in
 - Thread Size 2: 3/8 in
 - Thread Size 3: 3/8 in
 - Connection Gender 1: Female



4992896 Tee

PLUMBING,SOCKET,EQUAL,STAINLESS STEEL 316,BSP

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Fitting Type: Socket
 - Pipe Fitting Connection Type: Threaded
 - Thread Size 1: 1/4 in
 - Thread Size 2: 1/4 in
 - Connection Gender 1: Female
 - Connection Gender 2: Female
 - Thread Standard 1: G
 - Thread Standard 2: G



4992903 Socket

PLUMBING,SOCKET,EQUAL,STAINLESS STEEL 316,BSP

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Fitting Type: Socket
 - Pipe Fitting Connection Type: Threaded
 - Thread Size 1: 3/8 in
 - Thread Size 2: 3/8 in
 - Connection Gender 1: Female
 - Connection Gender 2: Female
 - Thread Standard 1: G
 - Thread Standard 2: G



4992919 Socket

PLUMBING,NIPPLE,HEXAGON,STAINLESS STEEL 316,BSP

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Fitting Type: Hexagon Nipple
 - Pipe Fitting Connection Type: Threaded
 - Shape: Hexagon
 - Thread Size 1: 1/4 in
 - Thread Size 2: 1/4 in
 - Connection Gender 1: Male
 - Connection Gender 2: Male
 - Thread Standard 1: R (taper)



4992931 Hexagon Nipple

PLUMBING,NIPPLE,HEXAGON,STAINLESS STEEL 316,BSP

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Fitting Type: Hexagon Nipple
 - Pipe Fitting Connection Type: Threaded
 - Shape: Hexagon
 - Thread Size 1: 3/8 in
 - Thread Size 2: 3/8 in
 - Connection Gender 1: Male
 - Connection Gender 2: Male
 - Thread Standard 1: R (taper)



4992947 Hexagon Nipple

PLUMBING,ELBOW,EQUAL,90DEG,STAINLESS STEEL,1/2IN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Fitting Type: Elbow
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: 90°
 - Shape: Circular
 - Thread Size 1: 1/2 in
 - Thread Size 2: 1/2 in
 - Connection Gender 1: Female
 - Connection Gender 2: Female



4992953 Elbow

PLUMBING,ELBOW,EQUAL,90DEG,STAINLESS STEEL,3/4IN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Fitting Type: Elbow
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: 90°
 - Shape: Circular
 - Thread Size 1: 3/4 in
 - Thread Size 2: 3/4 in
 - Connection Gender 1: Female
 - Connection Gender 2: Female



4992969 Elbow

PLUMBING,ELBOW,EQUAL,90DEG,STAINLESS STEEL,1IN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Fitting Type: Elbow
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: 90°
 - Shape: Circular
 - Thread Size 1: 1 in
 - Thread Size 2: 1 in
 - Connection Gender 1: Female
 - Connection Gender 2: Female



4992975 Elbow

PLUMBING,ELBOW,EQUAL,TEE,STAINLESS STEEL,1/2IN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Fitting Type: Tee
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Tee
 - Shape: Circular
 - Thread Size 1: 1/2 in
 - Thread Size 2: 1/2 in
 - Thread Size 3: 1/2 in
 - Connection Gender 1: Female



4992981 Tee

PLUMBING, ELBOW, EQUAL TEE, STAINLESS STEEL, 3/4 IN

- ขนาดบรรจุภัณฑ์: 1 x EA
- Fitting Type: Tee
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Tee
 - Shape: Circular
 - Thread Size 1: 3/4 in
 - Thread Size 2: 3/4 in
 - Thread Size 3: 3/4 in
 - Connection Gender 1: Female



4992997 Tee

PLUMBING, ELBOW, EQUAL TEE, STAINLESS STEEL, 1 IN

- ขนาดบรรจุภัณฑ์: 1 x EA
- Fitting Type: Tee
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Tee
 - Shape: Circular
 - Thread Size 1: 1 in
 - Thread Size 2: 1 in
 - Thread Size 3: 1 in
 - Connection Gender 1: Female



4993007 Tee

PLUMBING, EQUAL SOCKET, STAINLESS STEEL, 1/2 IN

- ขนาดบรรจุภัณฑ์: 1 x EA
- Fitting Type: Socket
 - Pipe Fitting Connection Type: Threaded
 - Thread Size 1: 1/2 in
 - Thread Size 2: 1/2 in
 - Connection Gender 1: Female
 - Connection Gender 2: Female
 - Thread Standard 1: G
 - Thread Standard 2: G



4993013 Socket

PLUMBING, ELBOW, EQUAL SOCKET, STAINLESS STEEL, 3/4 IN

- ขนาดบรรจุภัณฑ์: 1 x EA
- Fitting Type: Socket
 - Pipe Fitting Connection Type: Threaded
 - Thread Size 1: 3/4 in
 - Thread Size 2: 3/4 in
 - Connection Gender 1: Female
 - Connection Gender 2: Female
 - Thread Standard 1: G
 - Thread Standard 2: G



4993029 Socket

PLUMBING, ELBOW, EQUAL SOCKET, STAINLESS STEEL, 1 IN

- ขนาดบรรจุภัณฑ์: 1 x EA
- Fitting Type: Socket
 - Pipe Fitting Connection Type: Threaded
 - Thread Size 1: 1 in
 - Thread Size 2: 1 in
 - Connection Gender 1: Female
 - Connection Gender 2: Female
 - Thread Standard 1: G
 - Thread Standard 2: G



4993035 Socket

PLUMBING, NIPPLE, HEXAGON, STAINLESS STEEL, 1/2 IN

- ขนาดบรรจุภัณฑ์: 1 x EA
- Fitting Type: Hexagon Nipple
 - Pipe Fitting Connection Type: Threaded
 - Shape: Hexagon
 - Thread Size 1: 1/2 in
 - Thread Size 2: 1/2 in
 - Connection Gender 1: Male
 - Connection Gender 2: Male
 - Thread Standard 1: R (taper)



4993041 Hexagon Nipple

PLUMBING, NIPPLE, HEXAGON, STAINLESS STEEL, 3/4 IN

- ขนาดบรรจุภัณฑ์: 1 x EA
- Fitting Type: Hexagon Nipple
 - Pipe Fitting Connection Type: Threaded
 - Shape: Hexagon
 - Thread Size 1: 3/4 in
 - Thread Size 2: 3/4 in
 - Connection Gender 1: Male
 - Connection Gender 2: Male
 - Thread Standard 1: R (taper)



4993057 Hexagon Nipple

PLUMBING, NIPPLE, HEXAGON, STAINLESS STEEL, 1 IN

- ขนาดบรรจุภัณฑ์: 1 x EA
- Fitting Type: Hexagon Nipple
 - Pipe Fitting Connection Type: Threaded
 - Shape: Hexagon
 - Thread Size 1: 1 in
 - Thread Size 2: 1 in
 - Connection Gender 1: Male
 - Connection Gender 2: Male
 - Thread Standard 1: R (taper)



4993063 Hexagon Nipple

RS PRO STAINLESS STEEL PIPE FITTING, 90° CIRCULAR ELBOW,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Fitting Type: Elbow
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: 90°
 - Shape: Circular
 - Thread Size 1: 1-1/4 in
 - Thread Size 2: 1-1/4 in
 - Connection Gender 1: Female
 - Connection Gender 2: Female



4993079 Elbow

RS PRO STAINLESS STEEL PIPE FITTING, 90° CIRCULAR ELBOW,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Fitting Type: Elbow
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: 90°
 - Shape: Circular
 - Thread Size 1: 2 in
 - Thread Size 2: 2 in
 - Connection Gender 1: Female
 - Connection Gender 2: Female



4993108 Elbow

RS PRO STAINLESS STEEL PIPE FITTING, TEE CIRCULAR TEE, FEMALE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Fitting Type: Tee
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Tee
 - Shape: Circular
 - Thread Size 1: 1-1/4 in
 - Thread Size 2: 1-1/4 in
 - Thread Size 3: 1-1/4 in
 - Connection Gender 1: Female



4993114 Tee

PLUMBING, FITTING, STAINLESS STEEL 316, 150LB, BSP SCREWED, 1 1/2 IN, TEE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Fitting Type: Tee
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Tee
 - Shape: Circular
 - Thread Size 1: 1-1/2 in
 - Thread Size 2: 1-1/2 in
 - Thread Size 3: 1-1/2 in
 - Connection Gender 1: Female



4993120 Tee

RS PRO STAINLESS STEEL PIPE FITTING SOCKET, FEMALE G 1-1/4 IN X

- ขนาดบรรจุภัณฑ์: 1 x EA
- Fitting Type: Socket
 - Pipe Fitting Connection Type: Threaded
 - Thread Size 1: 1-1/4 in
 - Thread Size 2: 1-1/4 in
 - Connection Gender 1: Female
 - Connection Gender 2: Female
 - Thread Standard 1: G
 - Thread Standard 2: G



4993136 Socket

RS PRO STAINLESS STEEL PIPE FITTING SOCKET, FEMALE G 1-1/2 IN X

- ขนาดบรรจุภัณฑ์: 1 x EA
- Fitting Type: Socket
 - Pipe Fitting Connection Type: Threaded
 - Thread Size 1: 1-1/2 in
 - Thread Size 2: 1-1/2 in
 - Connection Gender 1: Female
 - Connection Gender 2: Female
 - Thread Standard 1: G
 - Thread Standard 2: G



4993142 Socket

RS PRO STAINLESS STEEL PIPE FITTING SOCKET, FEMALE G 2 IN X

- ขนาดบรรจุภัณฑ์: 1 x EA
- Fitting Type: Socket
 - Pipe Fitting Connection Type: Threaded
 - Thread Size 1: 2 in
 - Thread Size 2: 2 in
 - Connection Gender 1: Female
 - Connection Gender 2: Female
 - Thread Standard 1: G
 - Thread Standard 2: G



4993164 Socket

PLUMBING, FITTING, STAINLESS STEEL 316, 150LB, BSP SCREWED, 1 1/4 IN, HEX

- ขนาดบรรจุภัณฑ์: 1 x EA
- Fitting Type: Hexagon Nipple
 - Pipe Fitting Connection Type: Threaded
 - Shape: Hexagon
 - Thread Size 1: 1-1/4 in
 - Thread Size 2: 1-1/4 in
 - Connection Gender 1: Male
 - Connection Gender 2: Male
 - Thread Standard 1: R (taper)



4993170 Hexagon Nipple

RS PRO STAINLESS STEEL PIPE FITTING HEXAGON HEXAGON NIPPLE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Fitting Type: Hexagon Nipple
 - Pipe Fitting Connection Type: Threaded
 - Shape: Hexagon
 - Thread Size 1: 1-1/2 in
 - Thread Size 2: 1-1/2 in
 - Connection Gender 1: Male
 - Connection Gender 2: Male
 - Thread Standard 1: R (taper)



4993186 Hexagon Nipple

PLUMBING, FITTING, STAINLESS STEEL 316, 150LB, BSP SCREWED, 2IN, HEX

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Fitting Type: Hexagon Nipple
 - Pipe Fitting Connection Type: Threaded
 - Shape: Hexagon
 - Thread Size 1: 2 in
 - Thread Size 2: 2 in
 - Connection Gender 1: Male
 - Connection Gender 2: Male
 - Thread Standard 1: R (taper)



4993192 Hexagon Nipple

PLUMBING, STAINLESS STEEL 316, 150LB, BARREL NIPPLE, 1/4 IN BSP

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Fitting Type: Barrel Nipple
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Shape: Circular
 - Thread Size 1: 1/4 in
 - Thread Size 2: 1/4 in
 - Connection Gender 1: Male
 - Connection Gender 2: Male



4993221 Barrel Nipple

PLUMBING, STAINLESS STEEL 316, 150LB, BARREL NIPPLE, 3/8 IN BSP

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Fitting Type: Barrel Nipple
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Shape: Circular
 - Thread Size 1: 3/8 in
 - Thread Size 2: 3/8 in
 - Connection Gender 1: Male
 - Connection Gender 2: Male



4993237 Barrel Nipple

PLUMBING, STAINLESS STEEL 316, 150LB, BARREL NIPPLE, 1/2 IN BSP

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Fitting Type: Barrel Nipple
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Shape: Circular
 - Thread Size 1: 1/2 in
 - Thread Size 2: 1/2 in
 - Connection Gender 1: Male
 - Connection Gender 2: Male



4993243 Barrel Nipple

PLUMBING, STAINLESS STEEL 316, 150LB, BARREL NIPPLE, 3/4 IN BSP

- ขนาดบรรจุภัณฑ์: **2 x EA**
- Fitting Type: Barrel Nipple
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Shape: Circular
 - Thread Size 1: 3/4 in
 - Thread Size 2: 3/4 in
 - Connection Gender 1: Male
 - Connection Gender 2: Male



4993259 Barrel Nipple

PLUMBING, STAINLESS STEEL 316, 150LB, BARREL NIPPLE, 1 IN BSP

- ขนาดบรรจุภัณฑ์: **2 x EA**
- Fitting Type: Barrel Nipple
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Shape: Circular
 - Thread Size 1: 1 in
 - Thread Size 2: 1 in
 - Connection Gender 1: Male
 - Connection Gender 2: Male



4993265 Barrel Nipple

RS PRO STAINLESS STEEL PIPE FITTING, STRAIGHT CIRCULAR

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Fitting Type: Barrel Nipple
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Shape: Circular
 - Thread Size 1: 1-1/2 in
 - Thread Size 2: 1-1/2 in
 - Connection Gender 1: Male
 - Connection Gender 2: Male



4993287 Barrel Nipple

RS PRO STAINLESS STEEL PIPE FITTING, STRAIGHT CIRCULAR

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Fitting Type: Barrel Nipple
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Shape: Circular
 - Thread Size 1: 2 in
 - Thread Size 2: 2 in
 - Connection Gender 1: Male
 - Connection Gender 2: Male



4993293 Barrel Nipple

PLUMBING, STAINLESS STEEL 316, 150LB, STREET ELBOW, 1/4 IN BSP

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Fitting Type: Elbow
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: 90°
 - Shape: Circular
 - Thread Size 1: 1/4 in
 - Thread Size 2: 1/4 in
 - Connection Gender 1: Female
 - Connection Gender 2: Male



4993300 Elbow

PLUMBING, STAINLESS STEEL 316, 150LB, STREET ELBOW, 3/8 IN BSP

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Fitting Type: Elbow
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: 90°
 - Shape: Circular
 - Thread Size 1: 3/8 in
 - Thread Size 2: 3/8 in
 - Connection Gender 1: Female
 - Connection Gender 2: Male



4993316 Elbow

PLUMBING, STAINLESS STEEL 316, 150LB, STREET ELBOW, 1/2 IN BSP

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Fitting Type: Elbow
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: 90°
 - Shape: Circular
 - Thread Size 1: 1/2 in
 - Thread Size 2: 1/2 in
 - Connection Gender 1: Female
 - Connection Gender 2: Male



4993322 Elbow

PLUMBING, STAINLESS STEEL 316, 150LB, STREET ELBOW, 3/4 IN BSP

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Fitting Type: Elbow
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: 90°
 - Shape: Circular
 - Thread Size 1: 3/4 in
 - Thread Size 2: 3/4 in
 - Connection Gender 1: Female
 - Connection Gender 2: Male



4993338 Elbow

PLUMBING, STAINLESS STEEL 316, 150LB, STREET ELBOW, 1 IN BSP

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Fitting Type: Elbow
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: 90°
 - Shape: Circular
 - Thread Size 1: 1 in
 - Thread Size 2: 1 in
 - Connection Gender 1: Female
 - Connection Gender 2: Male



4993344 Elbow

RS PRO STAINLESS STEEL PIPE FITTING, 90° CIRCULAR ELBOW,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Fitting Type: Elbow
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: 90°
 - Shape: Circular
 - Thread Size 1: 1-1/4 in
 - Thread Size 2: 1-1/4 in
 - Connection Gender 1: Female
 - Connection Gender 2: Male



4993350 Elbow

RS PRO STAINLESS STEEL PIPE FITTING, 90° CIRCULAR ELBOW,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Fitting Type: Elbow
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: 90°
 - Shape: Circular
 - Thread Size 1: 1-1/2 in
 - Thread Size 2: 1-1/2 in
 - Connection Gender 1: Female
 - Connection Gender 2: Male



4993366 Elbow

RS PRO STAINLESS STEEL PIPE FITTING, 90° CIRCULAR ELBOW,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Fitting Type: Elbow
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: 90°
 - Shape: Circular
 - Thread Size 1: 2 in
 - Thread Size 2: 2 in
 - Connection Gender 1: Female
 - Connection Gender 2: Male



4993388 Elbow

PLUMBING,PLUG,STAINLESS STEEL 316,BSP SCREW,150LB,BS1740,1/4IN

- ขนาดบรรจุภัณฑ์: 1 x EA
- Fitting Type: Plug
 - Pipe Fitting Connection Type: Threaded
 - Shape: Hexagon
 - Thread Size 1: 1/4 in
 - Connection Gender 1: Male
 - Thread Standard 1: R (taper)
 - Length: 18.034 mm



4993394 Plug

PLUMBING,PLUG,STAINLESS STEEL 316,BSP SCREW,150LB,BS1740,3/8IN

- ขนาดบรรจุภัณฑ์: 1 x EA
- Fitting Type: Plug
 - Pipe Fitting Connection Type: Threaded
 - Shape: Hexagon
 - Thread Size 1: 3/8 in
 - Connection Gender 1: Male
 - Thread Standard 1: R (taper)
 - Length: 19.558 mm



4993401 Plug

RS PRO STAINLESS STEEL PIPE FITTING, STRAIGHT HEXAGON UNION,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Fitting Type: Union
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Shape: Hexagon
 - Thread Size 1: 1/4 in
 - Thread Size 2: 1/4 in
 - Connection Gender 1: Female
 - Connection Gender 2: Female



4993417 Union

RS PRO STAINLESS STEEL PIPE FITTING, STRAIGHT OCTAGON

- ขนาดบรรจุภัณฑ์: 1 x EA
- Fitting Type: Union
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Shape: Octagon
 - Thread Size 1: 3/8 in
 - Thread Size 2: 3/8 in
 - Connection Gender 1: Female
 - Connection Gender 2: Female



4993423 Union

PLUMBING,BUSH,HEXAGON,STAINLESS STEEL 316,BSP

- ขนาดบรรจุภัณฑ์: 1 x EA
- Fitting Type: Bush
 - Pipe Fitting Connection Type: Threaded
 - Shape: Hexagon
 - Thread Size 1: 1/2 in
 - Thread Size 2: 3/8 in
 - Connection Gender 1: Male
 - Connection Gender 2: Female
 - Thread Standard 1: R (taper)



4993445 Bush

PLUMBING,BUSH,HEXAGON,STAINLESS STEEL 316,BSP

- ขนาดบรรจุภัณฑ์: 1 x EA
- Fitting Type: Bush
 - Pipe Fitting Connection Type: Threaded
 - Shape: Hexagon
 - Thread Size 1: 1/2 in
 - Thread Size 2: 1/4 in
 - Connection Gender 1: Male
 - Connection Gender 2: Female
 - Thread Standard 1: R (taper)



4993451 Bush

PLUMBING,PLUG,STAINLESS STEEL,1/2IN

- ขนาดบรรจุภัณฑ์: 1 x EA
- Fitting Type: Plug
 - Pipe Fitting Connection Type: Threaded
 - Shape: Hexagon
 - Thread Size 1: 1/2 in
 - Connection Gender 1: Male
 - Thread Standard 1: R (taper)
 - Length: 22.606 mm



4993467 Plug

PLUMBING,PLUG,STAINLESS STEEL,3/4IN

- ขนาดบรรจุภัณฑ์: 1 x EA
- Fitting Type: Plug
 - Pipe Fitting Connection Type: Threaded
 - Shape: Hexagon
 - Thread Size 1: 3/4 in
 - Connection Gender 1: Male
 - Thread Standard 1: R (taper)
 - Length: 23.368 mm



4993473 Plug

PLUMBING,PLUG,STAINLESS STEEL,1IN

- ขนาดบรรจุภัณฑ์: 1 x EA
- Fitting Type: Plug
 - Pipe Fitting Connection Type: Threaded
 - Shape: Hexagon
 - Thread Size 1: 1 in
 - Connection Gender 1: Male
 - Thread Standard 1: R (taper)
 - Length: 26.924 mm



4993489 Plug

PLUMBING,UNION,STRAIGHT,STAINLESS STEEL,1/2IN

- ขนาดบรรจุภัณฑ์: 1 x EA
- Fitting Type: Union
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Shape: Octagon
 - Thread Size 1: 1/2 in
 - Thread Size 2: 1/2 in
 - Connection Gender 1: Female
 - Connection Gender 2: Female



4993495 Union

PLUMBING,UNION,STRAIGHT,STAINLESS STEEL,3/4IN

- ขนาดบรรจุภัณฑ์: 1 x EA
- Fitting Type: Union
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Shape: Octagon
 - Thread Size 1: 3/4 in
 - Thread Size 2: 3/4 in
 - Connection Gender 1: Female
 - Connection Gender 2: Female



4993502 Union

PLUMBING,UNION,STRAIGHT,STAINLESS STEEL,1IN

- ขนาดบรรจุภัณฑ์: 1 x EA
- Fitting Type: Union
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Shape: Octagon
 - Thread Size 1: 1 in
 - Thread Size 2: 1 in
 - Connection Gender 1: Female
 - Connection Gender 2: Female



4993518 Union

PLUMBING,BUSH,HEXAGON,STAINLESS STEEL,3/4X1/2IN

- ขนาดบรรจุภัณฑ์: 1 x EA
- Fitting Type: Bush
 - Pipe Fitting Connection Type: Threaded
 - Shape: Hexagon
 - Thread Size 1: 3/4 in
 - Thread Size 2: 1/2 in
 - Connection Gender 1: Male
 - Connection Gender 2: Female
 - Thread Standard 1: R (taper)



4993524 Bush

PLUMBING,BUSH,HEXAGON,STAINLESS STEEL,1X1/2IN

- ขนาดบรรจุภัณฑ์: 1 x EA
- Fitting Type: Bush
 - Pipe Fitting Connection Type: Threaded
 - Shape: Hexagon
 - Thread Size 1: 1 in
 - Thread Size 2: 1/2 in
 - Connection Gender 1: Male
 - Connection Gender 2: Female
 - Thread Standard 1: R (taper)



4993530 Bush

PLUMBING,BUSH,HEXAGON,STAINLESS STEEL,1X3/4IN

- ขนาดบรรจุภัณฑ์: 1 x EA
- Fitting Type: Bush
 - Pipe Fitting Connection Type: Threaded
 - Shape: Hexagon
 - Thread Size 1: 1 in
 - Thread Size 2: 3/4 in
 - Connection Gender 1: Male
 - Connection Gender 2: Female
 - Thread Standard 1: R (taper)



4993546 Bush

RS PRO STAINLESS STEEL PIPE FITTING HEXAGON BUSH, MALE R 1-

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Fitting Type: Bush
 - Pipe Fitting Connection Type: Threaded
 - Shape: Hexagon
 - Thread Size 1: 1-1/4 in
 - Thread Size 2: 1/2 in
 - Connection Gender 1: Male
 - Connection Gender 2: Female
 - Thread Standard 1: R (taper)



4993552 Bush

RS PRO STAINLESS STEEL PIPE FITTING HEXAGON BUSH, MALE R 1-

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Fitting Type: Bush
 - Pipe Fitting Connection Type: Threaded
 - Shape: Hexagon
 - Thread Size 1: 1-1/4 in
 - Thread Size 2: 3/4 in
 - Connection Gender 1: Male
 - Connection Gender 2: Female
 - Thread Standard 1: R (taper)



4993568 Bush

PLUMBING,BUSH,HEXAGON,STAINLESS STEEL,1 1/4X1IN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Fitting Type: Bush
 - Pipe Fitting Connection Type: Threaded
 - Shape: Hexagon
 - Thread Size 1: 1-1/4 in
 - Thread Size 2: 1 in
 - Connection Gender 1: Male
 - Connection Gender 2: Female
 - Thread Standard 1: R (taper)



4993574 Bush

PLUMBING,BUSH,HEXAGON,STAINLESS STEEL,1 1/2X1/2IN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Fitting Type: Bush
 - Pipe Fitting Connection Type: Threaded
 - Shape: Hexagon
 - Thread Size 1: 1-1/2 in
 - Thread Size 2: 1/2 in
 - Connection Gender 1: Male
 - Connection Gender 2: Female
 - Thread Standard 1: R (taper)



4993580 Bush

RS PRO STAINLESS STEEL PIPE FITTING HEXAGON BUSH, MALE R 1-

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Fitting Type: Bush
 - Pipe Fitting Connection Type: Threaded
 - Shape: Hexagon
 - Thread Size 1: 1-1/2 in
 - Thread Size 2: 3/4 in
 - Connection Gender 1: Male
 - Connection Gender 2: Female
 - Thread Standard 1: R (taper)



4993603 Bush

RS PRO STAINLESS STEEL PIPE FITTING HEXAGON BUSH, MALE R 1-

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Fitting Type: Bush
 - Pipe Fitting Connection Type: Threaded
 - Shape: Hexagon
 - Thread Size 1: 1-1/2 in
 - Thread Size 2: 1 in
 - Connection Gender 1: Male
 - Connection Gender 2: Female
 - Thread Standard 1: R (taper)



4993619 Bush

RS PRO STAINLESS STEEL PIPE FITTING HEXAGON BUSH, MALE R 2IN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Fitting Type: Bush
 - Pipe Fitting Connection Type: Threaded
 - Shape: Hexagon
 - Thread Size 1: 2 in
 - Thread Size 2: 1 in
 - Connection Gender 1: Male
 - Connection Gender 2: Female
 - Thread Standard 1: R (taper)



4993631 Bush

RS PRO STAINLESS STEEL PIPE FITTING HEXAGON PLUG, MALE R 1-

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Fitting Type: Plug
 - Pipe Fitting Connection Type: Threaded
 - Shape: Hexagon
 - Thread Size 1: 1-1/4 in
 - Connection Gender 1: Male
 - Thread Standard 1: R (taper)
 - Length: 30.48 mm



4993647 Plug

RS PRO STAINLESS STEEL PIPE FITTING HEXAGON PLUG, MALE R 1-

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Fitting Type: Plug
 - Pipe Fitting Connection Type: Threaded
 - Shape: Hexagon
 - Thread Size 1: 1-1/2 in
 - Connection Gender 1: Male
 - Thread Standard 1: R (taper)
 - Length: 30.734 mm



4993669 Plug

RS PRO STAINLESS STEEL PIPE FITTING HEXAGON PLUG, MALE R 2IN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Fitting Type: Plug
 - Pipe Fitting Connection Type: Threaded
 - Shape: Hexagon
 - Thread Size 1: 2 in
 - Connection Gender 1: Male
 - Thread Standard 1: R (taper)
 - Length: 34.036 mm



4993675 Plug

RS PRO STAINLESS STEEL PIPE FITTING, STRAIGHT DECAGON

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Fitting Type: Union
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Shape: Decagon
 - Thread Size 1: 1-1/4 in
 - Thread Size 2: 1-1/4 in
 - Connection Gender 1: Female
 - Connection Gender 2: Female



4993681 Union

RS PRO STAINLESS STEEL PIPE FITTING, STRAIGHT DECAGON

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Fitting Type: Union
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Shape: Decagon
 - Thread Size 1: 1-1/2 in
 - Thread Size 2: 1-1/2 in
 - Connection Gender 1: Female
 - Connection Gender 2: Female



4993697 Union

RS PRO STAINLESS STEEL PIPE FITTING, STRAIGHT DECAGON

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Fitting Type: Union
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Shape: Decagon
 - Thread Size 1: 2 in
 - Thread Size 2: 2 in
 - Connection Gender 1: Female
 - Connection Gender 2: Female



4993704 Union

PLUMBING,FITTING,STAINLESS STEEL 316,150LB,BSP SCREWED,HEX

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Fitting Type: Bush
 - Pipe Fitting Connection Type: Threaded
 - Shape: Hexagon
 - Thread Size 1: 2 in
 - Thread Size 2: 1/2 in
 - Connection Gender 1: Male
 - Connection Gender 2: Female
 - Thread Standard 1: R (taper)



4993726 Bush

PLUMBING,STAINLESS STEEL 316,150LB,HOSE TAIL,1/4IN BSP

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Fitting Type: Hose Nipple
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Shape: Hexagon
 - Thread Size 1: 1/4 in
 - Connection Gender 1: Male
 - Connection Gender 2: Male
 - Thread Standard 1: R (taper)



4993732 Hose Nipple

PLUMBING,STAINLESS STEEL 316,150LB,HOSE TAIL,3/8IN BSP

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Fitting Type: Hose Nipple
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Shape: Hexagon
 - Thread Size 1: 3/8 in
 - Connection Gender 1: Male
 - Connection Gender 2: Male
 - Thread Standard 1: R (taper)



4993748 Hose Nipple

PLUMBING, STAINLESS STEEL 316, 150LB, HOSE TAIL, 1/2IN BSP

- ขนาดบรรจุภัณฑ์: 1 x EA
- Fitting Type: Hose Nipple
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Shape: Hexagon
 - Thread Size 1: 1/2 in
 - Connection Gender 1: Male
 - Connection Gender 2: Male
 - Thread Standard 1: R (taper)



4993754 Hose Nipple

PLUMBING, STAINLESS STEEL 316, 150LB, HOSE TAIL, 3/4IN BSP

- ขนาดบรรจุภัณฑ์: 1 x EA
- Fitting Type: Hose Nipple
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Shape: Hexagon
 - Thread Size 1: 3/4 in
 - Connection Gender 1: Male
 - Connection Gender 2: Male
 - Thread Standard 1: R (taper)



4993760 Hose Nipple

PLUMBING, STAINLESS STEEL 316, 150LB, HOSE TAIL, 1IN BSP

- ขนาดบรรจุภัณฑ์: 1 x EA
- Fitting Type: Hose Nipple
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Shape: Hexagon
 - Thread Size 1: 1 in
 - Connection Gender 1: Male
 - Connection Gender 2: Male
 - Thread Standard 1: R (taper)



4993776 Hose Nipple

PLUMBING, STAINLESS STEEL 316, 150LB, HOSE TAIL, 1 1/4IN BSP

- ขนาดบรรจุภัณฑ์: 1 x EA
- Fitting Type: Hose Nipple
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Shape: Hexagon
 - Thread Size 1: 1-1/4 in
 - Connection Gender 1: Male
 - Connection Gender 2: Male
 - Thread Standard 1: R (taper)



4993782 Hose Nipple

PLUMBING, STAINLESS STEEL 316, 150LB, HOSE TAIL, 1/2IN BSP

- ขนาดบรรจุภัณฑ์: 1 x EA
- Fitting Type: Hose Nipple
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Shape: Hexagon
 - Thread Size 1: 1/2 in
 - Connection Gender 1: Male
 - Connection Gender 2: Male
 - Thread Standard 1: R (taper)



4993798 Hose Nipple

RS PRO STAINLESS STEEL PIPE FITTING, STRAIGHT HEXAGON HOSE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Fitting Type: Hose Nipple
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Shape: Hexagon
 - Thread Size 1: 2 in
 - Connection Gender 1: Male
 - Connection Gender 2: Male
 - Thread Standard 1: R (taper)



4993805 Hose Nipple

RS PRO STAINLESS STEEL PIPE FITTING, 90° CIRCULAR ELBOW,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Fitting Type: Elbow
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: 90°
 - Shape: Circular
 - Thread Size 1: 1/4 in
 - Thread Size 2: 1/4 in
 - Connection Gender 1: Female
 - Connection Gender 2: Female



8266914 Elbow

RS PRO STAINLESS STEEL PIPE FITTING, 90° CIRCULAR ELBOW, MALE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Fitting Type: Elbow
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: 90°
 - Shape: Circular
 - Thread Size 1: 1/2 in
 - Thread Size 2: 1/2 in
 - Connection Gender 1: Male
 - Connection Gender 2: Female



8266946 Elbow

RS PRO STAINLESS STEEL PIPE FITTING, 90° CIRCULAR ELBOW, MALE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Fitting Type: Elbow
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: 90°
 - Shape: Circular
 - Thread Size 1: 1/4 in
 - Thread Size 2: 1/4 in
 - Connection Gender 1: Male
 - Connection Gender 2: Female



8266949 Elbow

RS PRO STAINLESS STEEL PIPE FITTING, TEE CIRCULAR TEE, FEMALE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Fitting Type: Tee
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Tee
 - Shape: Circular
 - Thread Size 1: 1/4 in
 - Thread Size 2: 1/4 in
 - Thread Size 3: 1/4 in
 - Connection Gender 1: Female



8266968 Tee

RS PRO STAINLESS STEEL PIPE FITTING, TEE CIRCULAR TEE, FEMALE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Fitting Type: Tee
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Tee
 - Shape: Circular
 - Thread Size 1: 3/8 in
 - Thread Size 2: 3/8 in
 - Thread Size 3: 3/8 in
 - Connection Gender 1: Female



8266977 Tee

RS PRO STAINLESS STEEL PIPE FITTING, STRAIGHT CIRCULAR

- ขนาดบรรจุภัณฑ์: 1 x EA
- Fitting Type: Coupler
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Shape: Circular
 - Thread Size 1: 1/4 in
 - Thread Size 2: 1/4 in
 - Connection Gender 1: Female
 - Connection Gender 2: Female



8266992 Coupler

RS PRO STAINLESS STEEL PIPE FITTING, STRAIGHT CIRCULAR

- ขนาดบรรจุภัณฑ์: 1 x EA
- Fitting Type: Coupler
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Shape: Circular
 - Thread Size 1: 3/8 in
 - Thread Size 2: 3/8 in
 - Connection Gender 1: Female
 - Connection Gender 2: Female



8266996 Coupler

RS PRO STAINLESS STEEL PIPE FITTING, STRAIGHT CIRCULAR

- ขนาดบรรจุภัณฑ์: 1 x EA
- Fitting Type: Coupler
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Shape: Circular
 - Thread Size 1: 3/4 in
 - Thread Size 2: 3/4 in
 - Connection Gender 1: Female
 - Connection Gender 2: Female



8267002 Coupler

RS PRO STAINLESS STEEL PIPE FITTING, STRAIGHT CIRCULAR

- ขนาดบรรจุภัณฑ์: 1 x EA
- Fitting Type: Coupler
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Shape: Circular
 - Thread Size 1: 1 in
 - Thread Size 2: 1 in
 - Connection Gender 1: Female
 - Connection Gender 2: Female



8267006 Coupler

RS PRO STAINLESS STEEL PIPE FITTING, STRAIGHT CIRCULAR

- ขนาดบรรจุภัณฑ์: 1 x EA
- Fitting Type: Coupler
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Shape: Circular
 - Thread Size 1: 1/2 in
 - Thread Size 2: 1/2 in
 - Connection Gender 1: Female
 - Connection Gender 2: Female



8267009 Coupler

RS PRO STAINLESS STEEL PIPE FITTING, STRAIGHT CIRCULAR

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Fitting Type: Coupler
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Shape: Circular
 - Thread Size 1: 1-1/4 in
 - Thread Size 2: 1-1/4 in
 - Connection Gender 1: Female
 - Connection Gender 2: Female



8267015 Coupler

1/4IN F/STEEL 316 HEX PLUG MALE JOINT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Fitting Type: Hexagon Plug
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Shape: Hexagon
 - Thread Size 1: 1/4 in
 - Connection Gender 1: Male
 - Thread Standard 1: R (taper)
 - Length: 17.018 mm



8267021 Hexagon Plug

RS PRO STAINLESS STEEL PIPE FITTING, STRAIGHT HEXAGON

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Fitting Type: Hexagon Plug
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Shape: Hexagon
 - Thread Size 1: 3/8 in
 - Connection Gender 1: Male
 - Thread Standard 1: R (taper)
 - Length: 20.828 mm



8267024 Hexagon Plug

RS PRO STAINLESS STEEL PIPE FITTING, STRAIGHT HEXAGON

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Fitting Type: Hexagon Plug
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Shape: Hexagon
 - Thread Size 1: 1/2 in
 - Connection Gender 1: Male
 - Thread Standard 1: R (taper)
 - Length: 21.844 mm



8267028 Hexagon Plug

RS PRO STAINLESS STEEL PIPE FITTING, STRAIGHT HEXAGON

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Fitting Type: Hexagon Plug
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Shape: Hexagon
 - Thread Size 1: 1 in
 - Connection Gender 1: Male
 - Thread Standard 1: R (taper)
 - Length: 28.956 mm



8267030 Hexagon Plug

1/4IN F/STEEL 316 HEX NIPPLE M/M JOINT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Fitting Type: Nipple
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Shape: Hexagon
 - Thread Size 1: 1/4 in
 - Thread Size 2: 1/4 in
 - Connection Gender 1: Male
 - Connection Gender 2: Male



8267040 Nipple

RS PRO STAINLESS STEEL PIPE FITTING, STRAIGHT HEXAGON

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Fitting Type: Hexagon Plug
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Shape: Hexagon
 - Thread Size 1: 1-1/2 in
 - Connection Gender 1: Male
 - Thread Standard 1: R (taper)
 - Length: 37.084 mm



8267043 Hexagon Plug

RS PRO STAINLESS STEEL PIPE FITTING, STRAIGHT HEXAGON

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Fitting Type: Hexagon Plug
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Shape: Hexagon
 - Thread Size 1: 2 in
 - Connection Gender 1: Male
 - Thread Standard 1: R (taper)
 - Length: 40.132 mm



8267046 Hexagon Plug

1/2IN F/STEEL 316 HEX NIPPLE M/M JOINT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Fitting Type: Nipple
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Shape: Hexagon
 - Thread Size 1: 1/2 in
 - Thread Size 2: 1/2 in
 - Connection Gender 1: Male
 - Connection Gender 2: Male



8267052 Nipple

3/4IN F/STEEL 316 HEX NIPPLE M/M JOINT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Fitting Type: Nipple
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Shape: Hexagon
 - Thread Size 1: 3/4 in
 - Thread Size 2: 3/4 in
 - Connection Gender 1: Male
 - Connection Gender 2: Male



8267056 Nipple

RS PRO STAINLESS STEEL PIPE FITTING, STRAIGHT HEXAGON NIPPLE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Fitting Type: Nipple
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Shape: Hexagon
 - Thread Size 1: 3/8 in
 - Thread Size 2: 3/8 in
 - Connection Gender 1: Male
 - Connection Gender 2: Male



8267059 Nipple

RS PRO STAINLESS STEEL PIPE FITTING, STRAIGHT HEXAGON NIPPLE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Fitting Type: Nipple
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Shape: Hexagon
 - Thread Size 1: 1-1/2 in
 - Thread Size 2: 1-1/2 in
 - Connection Gender 1: Male
 - Connection Gender 2: Male



8267062 Nipple

1IN F/STEEL 316 HEX NIPPLE M/M JOINT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Fitting Type: Nipple
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Shape: Hexagon
 - Thread Size 1: 1 in
 - Thread Size 2: 1 in
 - Connection Gender 1: Male
 - Connection Gender 2: Male



8267065 Nipple

1/4IN F/STEEL 316 HEX BUSHING M/F JOINT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Fitting Type: Bush
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Shape: Hexagon
 - Thread Size 1: 1/4 in
 - Thread Size 2: 1/8 in
 - Connection Gender 1: Male
 - Connection Gender 2: Female



8267074 Bush

3/8IN F/STEEL 316 HEX BUSHING M/F JOINT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Fitting Type: Bush
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Shape: Hexagon
 - Thread Size 1: 3/8 in
 - Thread Size 2: 1/4 in
 - Connection Gender 1: Male
 - Connection Gender 2: Female



8267078 Bush

3/4IN F/STEEL 316 HEX BUSHING M/F JOINT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Fitting Type: Bush
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Shape: Hexagon
 - Thread Size 1: 3/4 in
 - Thread Size 2: 1/2 in
 - Connection Gender 1: Male
 - Connection Gender 2: Female



8267080 Bush

1/2 IN F/STEEL 316 HEX BUSHING M/F JOINT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Fitting Type: Bush
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Shape: Hexagon
 - Thread Size 1: 1 in
 - Thread Size 2: 3/4 in
 - Connection Gender 1: Male
 - Connection Gender 2: Female



8267084 Bush

1/2 IN F/STEEL 316 HEX BUSHING M/F JOINT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Fitting Type: Bush
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Shape: Hexagon
 - Thread Size 1: 1/2 in
 - Thread Size 2: 1/4 in
 - Connection Gender 1: Male
 - Connection Gender 2: Female



8267087 Bush

RS PRO STAINLESS STEEL PIPE FITTING, STRAIGHT HEXAGON BUSH,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Fitting Type: Bush
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Shape: Hexagon
 - Thread Size 1: 2 in
 - Thread Size 2: 1 in
 - Connection Gender 1: Male
 - Connection Gender 2: Female



8267090 Bush

RS PRO STAINLESS STEEL PIPE FITTING, STRAIGHT HEXAGON BUSH,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Fitting Type: Bush
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Shape: Hexagon
 - Thread Size 1: 1-1/4 in
 - Thread Size 2: 1 in
 - Connection Gender 1: Male
 - Connection Gender 2: Female



8267093 Bush

RS PRO STAINLESS STEEL PIPE FITTING, STRAIGHT HEXAGON BUSH,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Fitting Type: Bush
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Shape: Hexagon
 - Thread Size 1: 1-1/2 in
 - Thread Size 2: 1 in
 - Connection Gender 1: Male
 - Connection Gender 2: Female



8267096 Bush

RS PRO STAINLESS STEEL PIPE FITTING, STRAIGHT HEXAGON UNION,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Fitting Type: Union
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Shape: Hexagon
 - Thread Size 1: 1/4 in
 - Thread Size 2: 1/4 in
 - Connection Gender 1: Female
 - Connection Gender 2: Female



8267100 Union

RS PRO STAINLESS STEEL PIPE FITTING, STRAIGHT OCTAGON

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Fitting Type: Union
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Shape: Octagon
 - Thread Size 1: 1 in
 - Thread Size 2: 1 in
 - Connection Gender 1: Female
 - Connection Gender 2: Female



8267119 Union

RS PRO STAINLESS STEEL PIPE FITTING, STRAIGHT OCTAGON

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Fitting Type: Union
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Shape: Octagon
 - Thread Size 1: 3/4 in
 - Thread Size 2: 3/4 in
 - Connection Gender 1: Male
 - Connection Gender 2: Female



8267135 Union

RS PRO STAINLESS STEEL PIPE FITTING, STRAIGHT OCTAGON

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Fitting Type: Union
 - Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Shape: Octagon
 - Thread Size 1: 1 in
 - Thread Size 2: 1 in
 - Connection Gender 1: Male
 - Connection Gender 2: Female



8267144 Union

RS PRO STAINLESS STEEL PIPE FITTING, STRAIGHT CIRCULAR

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Fitting Type: Fitting
 - Pipe Fitting Connection Type: Solder
 - Fitting Direction: Straight
 - Shape: Circular
 - Thread Size 1: 62 mm
 - Length: 22 mm



9186116 Fitting

RS PRO STAINLESS STEEL PIPE FITTING, STRAIGHT CIRCULAR

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Fitting Type: Fitting
 - Pipe Fitting Connection Type: Solder
 - Fitting Direction: Straight
 - Shape: Circular
 - Thread Size 1: 31 mm
 - Length: 20 mm



9186125 Fitting

RS PRO STAINLESS STEEL PIPE FITTING, STRAIGHT CIRCULAR

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Fitting Type: Fitting
 - Pipe Fitting Connection Type: Solder
 - Fitting Direction: Straight
 - Shape: Circular
 - Thread Size 1: 18 mm
 - Length: 4.5 mm



9186273 Fitting

RS PRO STAINLESS STEEL PIPE FITTING, STRAIGHT CIRCULAR

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Fitting Type: Fitting
 - Pipe Fitting Connection Type: Solder
 - Fitting Direction: Straight
 - Shape: Circular
 - Thread Size 1: 48 mm
 - Length: 13 mm



9186276 Fitting

RS PRO STAINLESS STEEL PIPE FITTING, STRAIGHT CIRCULAR

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Fitting Type: Fitting
 - Pipe Fitting Connection Type: Solder
 - Fitting Direction: Straight
 - Shape: Circular
 - Thread Size 1: 23 mm
 - Length: 4.5 mm



9186282 Fitting

RS PRO STAINLESS STEEL PIPE FITTING, STRAIGHT CIRCULAR

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Fitting Type: Fitting
 - Pipe Fitting Connection Type: Solder
 - Fitting Direction: Straight
 - Shape: Circular
 - Thread Size 1: 30 mm
 - Length: 5 mm



9186285 Fitting

RS PRO STAINLESS STEEL PIPE FITTING, STRAIGHT CIRCULAR

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Fitting Type: Fitting
 - Pipe Fitting Connection Type: Solder
 - Fitting Direction: Straight
 - Shape: Circular
 - Thread Size 1: 54 mm
 - Length: 5 mm



9186291 Fitting

RS PRO STAINLESS STEEL PIPE FITTING, STRAIGHT CIRCULAR

ขนาดบรรจุภัณฑ์: **10 x EA**

- Fitting Type: Fitting
- Pipe Fitting Connection Type: Solder
- Fitting Direction: Straight
- Shape: Circular
- Thread Size 1: 42 mm
- Length: 5 mm



9186298 Fitting

RS PRO 42 BAR CARBON STEEL THERMODYNAMIC STEAM TRAP, 1/2

ขนาดบรรจุภัณฑ์: **1 x EA**

- Trap Type: Thermodynamic
- Connection: 1/2 in BSP Female
- Orientation: Horizontal
- Maximum Working Pressure: 42 bar
- Maximum Temperature: +300 °C
- Body Material: Carbon Steel
- Gasket Material: Graphite
- Connection Gender: Female



7209194 Thermodynamic

RS PRO 42 BAR STAINLESS STEEL THERMODYNAMIC STEAM TRAP, 3/4

ขนาดบรรจุภัณฑ์: **1 x EA**

- Trap Type: Thermodynamic
- Connection: 3/4 in BSP Female
- Orientation: Horizontal
- Maximum Working Pressure: 42 bar
- Maximum Temperature: +300 °C
- Body Material: Stainless Steel
- Connection Gender: Female
- Connection Size: 3/4 in



7209204 Thermodynamic

RS PRO 42 BAR STAINLESS STEEL THERMODYNAMIC STEAM TRAP, 1 IN

ขนาดบรรจุภัณฑ์: **1 x EA**

- Trap Type: Thermodynamic
- Connection: 1 in BSP Female
- Orientation: Horizontal
- Maximum Working Pressure: 42 bar
- Maximum Temperature: +300 °C
- Body Material: Stainless Steel
- Gasket Material: Graphite
- Connection Gender: Female



7209207 Thermodynamic

RS PRO 14 BAR IRON FLOAT & THERMOSTATIC STEAM TRAP, 1/2 IN

ขนาดบรรจุภัณฑ์: **1 x EA**

- Trap Type: Float & Thermostatic
- Connection: 1/2 in BSP Female
- Orientation: Horizontal, Vertical
- Maximum Working Pressure: 14 bar
- Maximum Temperature: +198 °C
- Body Material: Iron
- Connection Gender: Female
- Connection Size: 1/2 in



7209213 Float &

RS PRO 10 BAR IRON FLOAT & THERMOSTATIC STEAM TRAP, 3/4 IN

ขนาดบรรจุภัณฑ์: **1 x EA**

- Trap Type: Float & Thermostatic
- Connection: 3/4 in BSP Female
- Orientation: Horizontal, Vertical
- Maximum Working Pressure: 10 bar
- Maximum Temperature: +198 °C
- Body Material: Iron
- Connection Gender: Female
- Connection Size: 3/4 in



7209226 Float &

RS PRO 14 BAR SG IRON FLOAT & THERMOSTATIC STEAM TRAP, 1 IN BSP

ขนาดบรรจุภัณฑ์: **1 x EA**

- Trap Type: Float & Thermostatic
- Connection: 1 in BSP Female
- Orientation: Horizontal, Vertical
- Maximum Working Pressure: 14 bar
- Maximum Temperature: +198 °C
- Body Material: SG Iron
- Gasket Material: Graphite, Stainless Steel
- Connection Gender: Female



7209235 Float &

RS PRO 13 BAR BRASS THERMOSTATIC STEAM TRAP, 1/2 IN

ขนาดบรรจุภัณฑ์: **1 x EA**

- Trap Type: Thermostatic
- Connection: 1/2 in BSP Female
- Orientation: Vertical
- Maximum Working Pressure: 13 bar
- Maximum Temperature: +200 °C
- Body Material: Brass
- Gasket Material: Graphite
- Connection Gender: Female



7209239 Thermostatic

RS PRO 8 BAR SG IRON INVERTED BUCKET STEAM TRAP, 3/4 IN BSP

ขนาดบรรจุภัณฑ์: **1 x EA**

- Trap Type: Inverted Bucket
- Connection: 3/4 in BSP Female
- Orientation: Horizontal
- Maximum Working Pressure: 8 bar
- Maximum Temperature: +230 °C
- Body Material: SG Iron
- Connection Gender: Female
- Connection Size: 3/4 in



7209251 Inverted Bucket

RS PRO 12 BAR IRON INVERTED BUCKET STEAM TRAP, 1/2 IN BSP

ขนาดบรรจุภัณฑ์: **1 x EA**

- Trap Type: Inverted Bucket
- Connection: 1/2 in BSP Female
- Orientation: Horizontal
- Maximum Working Pressure: 12 bar
- Maximum Temperature: +230 °C
- Body Material: Iron
- Connection Gender: Female
- Connection Size: 1/2 in



7209254 Inverted Bucket

RS PRO CHROME PLATED BRASS LEVER BIB TAP, 3/8 IN

ขนาดบรรจุภัณฑ์: **1 x EA**

- Control Type: Lever
- Body Material: Brass
- Finish: Chrome Plated
- Maximum Working Pressure: 21 bar
- Component Type: Bib Tap
- Thread Size: 3/8 in
- Thread Standard: BSP
- Hose Inner Diameter: 10 mm



486154 Lever

PLUMBING, CIM 3/4, BIB TAP WITH HOSE UNION, 1/2 IN BSP

ขนาดบรรจุภัณฑ์: **1 x EA**

- Control Type: Lever
- Body Material: Brass
- Finish: Chrome Plated
- Maximum Working Pressure: 21 bar
- Component Type: Bib Tap
- Thread Size: 1/2 in
- Thread Standard: BSP
- Hose Inner Diameter: 12 mm



486192 Lever

PLUMBING, CIM 3/4, BIB TAP WITH HOSE UNION, 3/4 IN BSP

ขนาดบรรจุภัณฑ์: **1 x EA**

- Hose Inner Diameter: 12 mm
- Threaded Connection: 3/4 in BSP
- Body Material: Brass
- Maximum Working Pressure: 21 bar
- Thread Size: 3/4 in
- Thread Standard: BSP



486198 12 mm

RS PRO BRASS TWIST HANDLE BIB TAP, 1/2 IN

ขนาดบรรจุภัณฑ์: **1 x EA**

- Control Type: Twist Handle
- Body Material: Brass
- Maximum Working Pressure: 16 bar
- Component Type: Bib Tap
- Thread Size: 1/2 in, 3/4 in
- Thread Standard: BSP



7845728 Twist Handle

RS PRO NITRILE THERMAL INSULATING SHEET, 2M X 500MM X 19MM

ขนาดบรรจุภัณฑ์: **1 x EA**

- Material: Nitrile
- Length: 2 m
- Width: 500 mm
- Thickness: 19 mm
- Thermal Conductivity: 0.034 W/mK, 0.036 W/mK, 0.038 W/mK, 0.04 W/mK
- Colour: Black



486019 Nitrile

RS PRO NITRILE THERMAL INSULATING SHEET, 2M X 500MM X 13MM

ขนาดบรรจุภัณฑ์: **1 x EA**

- Material: Nitrile
- Length: 2 m
- Width: 500 mm
- Thickness: 13 mm
- Thermal Conductivity: 0.034 W/mK, 0.036 W/mK, 0.038 W/mK, 0.04 W/mK
- Colour: Black



486029 Nitrile

RS PRO NITRILE THERMAL INSULATING SHEET, 2M X 500MM X 9MM

ขนาดบรรจุภัณฑ์: 1 x EA

- Material: Nitrile
- Length: 2 m
- Width: 500 mm
- Thickness: 9 mm
- Thermal Conductivity: 0.034 W/mK, 0.036 W/mK, 0.038 W/mK, 0.04 W/mK
- Colour: Black



486031 Nitrile

RS PRO NITRILE THERMAL INSULATING SHEET, 2M X 500MM X 25MM

ขนาดบรรจุภัณฑ์: 1 x EA

- Material: Nitrile
- Length: 2 m
- Width: 500 mm
- Thickness: 25 mm
- Thermal Conductivity: 0.034 W/mK, 0.036 W/mK, 0.038 W/mK, 0.04 W/mK
- Colour: Black



486047 Nitrile

RS PRO PNEUMATIC 5 PORT VALVE ACTUATOR - SINGLE ACTING, 4 →

ขนาดบรรจุภัณฑ์: 1 x EA

- Number of Ports Supported: 5
- Actuator Type: Pneumatic
- Function: Single Acting
- Maximum Torque: 12.6 Nm
- Operating Pressure Range: 4 → 7 bar



8056042 5

RS PRO PNEUMATIC 2 PORT VALVE ACTUATOR - DOUBLE ACTING, 3 →

ขนาดบรรจุภัณฑ์: 1 x EA

- Number of Ports Supported: 2
- Actuator Type: Pneumatic
- Function: Double Acting
- Maximum Torque: 58.56 Nm
- Operating Pressure Range: 3 → 8 bar



8056048 2

RS PRO PNEUMATIC 2 PORT VALVE ACTUATOR - SINGLE ACTING, 4 →

ขนาดบรรจุภัณฑ์: 1 x EA

- Number of Ports Supported: 2
- Actuator Type: Pneumatic
- Function: Single Acting
- Maximum Torque: 29.9 Nm
- Operating Pressure Range: 4 → 7 bar



8056051 2

RS PRO PNEUMATIC 2 PORT VALVE ACTUATOR - SINGLE ACTING, 4 →

ขนาดบรรจุภัณฑ์: 1 x EA

- Number of Ports Supported: 2
- Actuator Type: Pneumatic
- Function: Single Acting
- Maximum Torque: 62.7 Nm
- Operating Pressure Range: 4 → 7 bar



8056058 2

RS PRO 80 X WASHER & SEAL KIT, 12 COMPARTMENTS, KIT CONTENTS

ขนาดบรรจุภัณฑ์: 1 x EA

- Kit Contents: Mixer, Valve
- Number of Compartments: 12
- Quantity Included: 80



4008288 Mixer, Valve

RS PRO WASHER & SEAL KIT, 12 COMPARTMENTS, KIT CONTENTS 1 IN

ขนาดบรรจุภัณฑ์: 1 x EA

- Kit Contents: 1 in Flat Rubber Washer, 1/2 in Ball Valve Seat Fibre Washer, 1/2 in Flat Rubber Washer, 1-1/4 Ball Float Valve, 3/4 in Flat Rubber Washer, 5/8 in Flat Rubber Washer, 7/8 in Flat Rubber Washer, Aquasave Rubber Washer, Low Pressure & High Pressure Seat,
- Number of Compartments: 12



4008294 1 in Flat Rubber

RS PRO 100 X WASHER & SEAL KIT, 12 COMPARTMENTS, KIT CONTENTS 1/2

ขนาดบรรจุภัณฑ์: 1 x EA

- Kit Contents: 1/2 in Delta Tap Washer, 1/2 in Flat Rubber Washer, 1/2 in Flat/Dome Jumper, 1/2 in Supertop A Washer, 1/2 in Supertop D Washer, 1/2 in Tantofex Rubber Washer, 3/4 in Delta Tap Washer, 3/4 in Flat Rubber Washer, 3/4 in Flat/Dome Jumper, 3/4 in

- Number of Compartments: 12
- Quantity Included: 100



4008301 1/2 in Delta Tap

PLUMBING, WASHER, FIBRE, RUBBER, REPLACEMENT, KIT

ขนาดบรรจุภัณฑ์: 1 x EA

- Kit Contents: 1/2 in Ball Valve Seat Fibre Washer, 1/2 in Shower Hose Rubber Washer, 1/2 in Top of Tap Body Fibre Washer, 15 mm Fibre Tap Connector Washer, 15 mm Flexible Tap Connector Washer, 22 mm Fibre Tap Connector Washer, 22 mm Flexible Tap Connector

- Number of Compartments: 12
- Quantity Included: 100



4008317 1/2 in Ball Valve

RS PRO 100 X WASHER & SEAL KIT, KIT CONTENTS 1/2 IN FLEXIBLE TAP

ขนาดบรรจุภัณฑ์: 100 x EA

- Kit Contents: 1/2 in Flexible Tap Connector Fibre Washer
- Quantity Included: 100



7844970 1/2 in Flexible Tap

RS PRO 1 X WASHER & SEAL KIT, KIT CONTENTS 3/4 IN BACK NUT

ขนาดบรรจุภัณฑ์: 1 x EA

- Kit Contents: 3/4 in Back Nut
- Quantity Included: 1



7845456 3/4 in Back Nut

FIBRE TAP WASHER WASHERS, 3/4 IN

ขนาดบรรจุภัณฑ์: 50 x EA

- For Screw/Bolt Size: 3/4 in
- Washer Type: Tap Washer
- Material: Fibre
- Finish: Plain
- Thickness: 1.5 mm



7845184 3/4 in

RS PRO COMPRESSED AIR PIPE TRANSLUCENT NYLON 4MM X 30M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Inside Diameter: 2.5 mm
 - Hose Outside Diameter: 4 mm
 - Colour: Translucent
 - Material: Nylon
 - Application: Air Brake, Fuel & Lube Applications, Industrial & Automotive Production Lines, Instrumentation & Secondary Air Systems
 - Length: 30 m
 - Maximum Operating Pressure: 15.5 bar
 - Manufacturer Series: NMSF



723911 2.5 mm

RS PRO COMPRESSED AIR PIPE BLACK NYLON 4MM X 30M NMSF

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Inside Diameter: 2.5 mm
 - Hose Outside Diameter: 4 mm
 - Colour: Black
 - Material: Nylon
 - Application: Air Brake, Fuel & Lube Applications, Industrial & Automotive Production Lines, Instrumentation & Secondary Air Systems
 - Length: 30 m
 - Maximum Operating Pressure: 15.5 bar
 - Manufacturer Series: NMSF



723927 2.5 mm

RS PRO COMPRESSED AIR PIPE BLUE NYLON 4MM X 30M NMSF SERIES

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Inside Diameter: 2.5 mm
 - Hose Outside Diameter: 4 mm
 - Colour: Blue
 - Material: Nylon
 - Application: Air Brake, Fuel & Lube Applications, Industrial & Automotive Production Lines, Instrumentation & Secondary Air Systems
 - Length: 30 m
 - Maximum Operating Pressure: 15.5 bar
 - Manufacturer Series: NMSF



723933 2.5 mm

RS PRO COMPRESSED AIR PIPE RED NYLON 4MM X 30M NMSF SERIES

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Inside Diameter: 2.5 mm
 - Hose Outside Diameter: 4 mm
 - Colour: Red
 - Material: Nylon
 - Application: Air Brake, Fuel & Lube Applications, Industrial & Automotive Production Lines, Instrumentation & Secondary Air Systems
 - Length: 30 m
 - Maximum Operating Pressure: 15.5 bar
 - Manufacturer Series: NMSF



723949 2.5 mm

RS PRO COMPRESSED AIR PIPE YELLOW NYLON 4MM X 30M NMSF

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Inside Diameter: 2.5 mm
 - Hose Outside Diameter: 4 mm
 - Colour: Yellow
 - Material: Nylon
 - Application: Air Brake, Fuel & Lube Applications, Industrial & Automotive Production Lines, Instrumentation & Secondary Air Systems
 - Length: 30 m
 - Maximum Operating Pressure: 15.5 bar
 - Manufacturer Series: NMSF



723961 2.5 mm

RS PRO COMPRESSED AIR PIPE TRANSLUCENT NYLON 5MM X 30M

- ขนาดบรรจุภัณฑ์: **30 x MTR**
- Hose Inside Diameter: 3.3 mm
 - Hose Outside Diameter: 5 mm
 - Colour: Translucent
 - Material: Nylon
 - Application: Air Brake, Fuel & Lube Applications, Industrial & Automotive Production Lines, Instrumentation & Secondary Air Systems
 - Length: 30 m
 - Maximum Operating Pressure: 24 bar
 - Manufacturer Series: NMF



725490 3.3 mm

RS PRO COMPRESSED AIR PIPE BLACK NYLON 5MM X 30M NMF

- ขนาดบรรจุภัณฑ์: **30 x MTR**
- Hose Inside Diameter: 3.3 mm
 - Hose Outside Diameter: 5 mm
 - Colour: Black
 - Material: Nylon
 - Application: Air Brake, Fuel & Lube Applications, Industrial & Automotive Production Lines, Instrumentation & Secondary Air Systems
 - Length: 30 m
 - Maximum Operating Pressure: 24 bar
 - Manufacturer Series: NMF



725507 3.3 mm

RS PRO COMPRESSED AIR PIPE RED NYLON 5MM X 30M NMF SERIES

- ขนาดบรรจุภัณฑ์: **30 x MTR**
- Hose Inside Diameter: 3.3 mm
 - Hose Outside Diameter: 5 mm
 - Colour: Red
 - Material: Nylon
 - Application: Air Brake, Fuel & Lube Applications, Industrial & Automotive Production Lines, Instrumentation & Secondary Air Systems
 - Length: 30 m
 - Maximum Operating Pressure: 24 bar
 - Manufacturer Series: NMF



725529 3.3 mm

RS PRO COMPRESSED AIR PIPE BLUE NYLON 5MM X 30M NMF SERIES

- ขนาดบรรจุภัณฑ์: **30 x MTR**
- Hose Inside Diameter: 3.3 mm
 - Hose Outside Diameter: 5 mm
 - Colour: Blue
 - Material: Nylon
 - Application: Air Brake, Fuel & Lube Applications, Industrial & Automotive Production Lines, Instrumentation & Secondary Air Systems
 - Length: 30 m
 - Maximum Operating Pressure: 24 bar
 - Manufacturer Series: NMF



725535 3.3 mm

RS PRO COMPRESSED AIR PIPE BLACK NYLON 4MM X 30M NMF

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Inside Diameter: 2.5 mm
 - Hose Outside Diameter: 4 mm
 - Colour: Black
 - Material: Nylon
 - Length: 30 m
 - Manufacturer Series: NMF



2020950 2.5 mm

RS PRO COMPRESSED AIR PIPE TRANSLUCENT NYLON 6MM X 30M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Inside Diameter: 4 mm
 - Hose Outside Diameter: 6 mm
 - Colour: Black
 - Material: Nylon
 - Length: 30 m
 - Manufacturer Series: NMF



2020956 4 mm

RS PRO COMPRESSED AIR PIPE RED NYLON 6MM X 30M NMF SERIES

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Inside Diameter: 4 mm
 - Hose Outside Diameter: 6 mm
 - Colour: Red
 - Material: Nylon
 - Length: 30 m
 - Manufacturer Series: NMF



2020959 4 mm

RS PRO COMPRESSED AIR PIPE YELLOW NYLON 6MM X 30M NMF

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Inside Diameter: 4 mm
 - Hose Outside Diameter: 6 mm
 - Colour: Yellow
 - Material: Nylon
 - Length: 30 m
 - Manufacturer Series: NMF



2020960 4 mm

RS PRO COMPRESSED AIR PIPE TRANSLUCENT NYLON 8MM X 30M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Inside Diameter: 5.5 mm
 - Hose Outside Diameter: 8 mm
 - Colour: Translucent
 - Material: Nylon
 - Length: 30 m
 - Manufacturer Series: NMF



2020963 5.5 mm

RS PRO COMPRESSED AIR PIPE BLACK NYLON 8MM X 30M NMF

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Inside Diameter: 5.5 mm
 - Hose Outside Diameter: 8 mm
 - Colour: Black
 - Material: Nylon
 - Length: 30 m
 - Manufacturer Series: NMF



2020964 5.5 mm

RS PRO COMPRESSED AIR PIPE BLACK NYLON 12MM X 30M NMF

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Inside Diameter: 8.5 mm
 - Hose Outside Diameter: 12 mm
 - Colour: Black
 - Material: Nylon
 - Length: 30 m
 - Manufacturer Series: NMF



2020976 8.5 mm

RS PRO COMPRESSED AIR PIPE BLACK POLYETHYLENE 6MM X 50M PE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Inside Diameter: 4 mm
 - Hose Outside Diameter: 6 mm
 - Colour: Black
 - Material: Polyethylene
 - Application: Food Industry
 - Length: 50 m
 - Manufacturer Series: PE



2351205 4 mm

RS PRO COMPRESSED AIR PIPE BLUE POLYETHYLENE 8MM X 50M CDPU

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Inside Diameter: 6 mm
 - Hose Outside Diameter: 8 mm
 - Colour: Blue
 - Material: Polyethylene
 - Application: Food Industry
 - Length: 50 m
 - Manufacturer Series: CDPU



2351206 6 mm

RS PRO COMPRESSED AIR PIPE BLUE POLYURETHANE 4MM X 100M CDPU

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Inside Diameter: 2.5 mm
 - Hose Outside Diameter: 4 mm
 - Colour: Blue
 - Material: Polyurethane
 - Length: 100 m
 - Manufacturer Series: CDPU



2351222 2.5 mm

RS PRO COMPRESSED AIR PIPE BLUE POLYURETHANE 6MM X 20M CDPU

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Inside Diameter: 4 mm
 - Hose Outside Diameter: 6 mm
 - Colour: Blue
 - Material: Polyurethane
 - Length: 20 m
 - Manufacturer Series: CDPU



2351225 4 mm

RS PRO COMPRESSED AIR PIPE BLUE POLYURETHANE 8MM X 20M CDPU

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Inside Diameter: 5.5 mm
 - Hose Outside Diameter: 8 mm
 - Colour: Blue
 - Material: Polyurethane
 - Length: 20 m
 - Manufacturer Series: CDPU



2351226 5.5 mm

RS PRO COMPRESSED AIR PIPE BLUE POLYURETHANE 10MM X 20M CDPU

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Inside Diameter: 6.5 mm
 - Hose Outside Diameter: 10 mm
 - Colour: Blue
 - Material: Polyurethane
 - Length: 20 m
 - Manufacturer Series: CDPU



2351228 6.5 mm

RS PRO COMPRESSED AIR PIPE TRANSLUCENT NYLON 6MM X 30M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Inside Diameter: 4 mm
 - Hose Outside Diameter: 6 mm
 - Colour: Translucent
 - Material: Nylon
 - Application: Air Brake, Fuel & Lube Applications, Industrial & Automotive Production Lines, Instrumentation & Secondary Air Systems
 - Length: 30 m
 - Maximum Operating Pressure: 14.5 bar
 - Manufacturer Series: NMSF



3866190 4 mm

RS PRO COMPRESSED AIR PIPE BLACK NYLON 6MM X 30M NMSF

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Inside Diameter: 4 mm
 - Hose Outside Diameter: 6 mm
 - Colour: Black
 - Material: Nylon
 - Application: Air Brake, Fuel & Lube Applications, Industrial & Automotive Production Lines, Instrumentation & Secondary Air Systems
 - Length: 30 m
 - Maximum Operating Pressure: 14.5 bar
 - Manufacturer Series: NMSF



3866207 4 mm

RS PRO COMPRESSED AIR PIPE BLUE NYLON 6MM X 30M NMSF SERIES

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Inside Diameter: 4 mm
 - Hose Outside Diameter: 6 mm
 - Colour: Blue
 - Material: Nylon
 - Application: Air Brake, Fuel & Lube Applications, Industrial & Automotive Production Lines, Instrumentation & Secondary Air Systems
 - Length: 30 m
 - Maximum Operating Pressure: 14.5 bar
 - Manufacturer Series: NMSF



3866213 4 mm

RS PRO COMPRESSED AIR PIPE RED NYLON 6MM X 30M NMSF SERIES

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Inside Diameter: 4 mm
 - Hose Outside Diameter: 6 mm
 - Colour: Red
 - Material: Nylon
 - Application: Air Brake, Fuel & Lube Applications, Industrial & Automotive Production Lines, Instrumentation & Secondary Air Systems
 - Length: 30 m
 - Maximum Operating Pressure: 14.5 bar
 - Manufacturer Series: NMSF



3866229 4 mm

RS PRO COMPRESSED AIR PIPE TRANSLUCENT NYLON 8MM X 30M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Inside Diameter: 5.5 mm
 - Hose Outside Diameter: 8 mm
 - Colour: Translucent
 - Material: Nylon
 - Application: Air Brake, Fuel & Lube Applications, Industrial & Automotive Production Lines, Instrumentation & Secondary Air Systems
 - Length: 30 m
 - Maximum Operating Pressure: 13.5 bar
 - Manufacturer Series: NMSF



3866235 5.5 mm

RS PRO COMPRESSED AIR PIPE BLACK NYLON 8MM X 30M NMSF

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Inside Diameter: 5.5 mm
 - Hose Outside Diameter: 8 mm
 - Colour: Black
 - Material: Nylon
 - Application: Air Brake, Fuel & Lube Applications, Industrial & Automotive Production Lines, Instrumentation & Secondary Air Systems
 - Length: 30 m
 - Maximum Operating Pressure: 13.5 bar
 - Manufacturer Series: NMSF



3866241 5.5 mm

RS PRO COMPRESSED AIR PIPE BLUE NYLON 8MM X 30M NMSF SERIES

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Inside Diameter: 5.5 mm
 - Hose Outside Diameter: 8 mm
 - Colour: Blue
 - Material: Nylon
 - Application: Air Brake, Fuel & Lube Applications, Industrial & Automotive Production Lines, Instrumentation & Secondary Air Systems
 - Length: 30 m
 - Maximum Operating Pressure: 13.5 bar
 - Manufacturer Series: NMSF



3866257 5.5 mm

RS PRO COMPRESSED AIR PIPE RED NYLON 8MM X 30M NMSF SERIES

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Inside Diameter: 5.5 mm
 - Hose Outside Diameter: 8 mm
 - Colour: Red
 - Material: Nylon
 - Application: Air Brake, Fuel & Lube Applications, Industrial & Automotive Production Lines, Instrumentation & Secondary Air Systems
 - Length: 30 m
 - Maximum Operating Pressure: 13.5 bar
 - Manufacturer Series: NMSF



3866263 5.5 mm

RS PRO COMPRESSED AIR PIPE TRANSLUCENT NYLON 6MM X 30M

- ขนาดบรรจุภัณฑ์: **30 x MTR**
- Hose Inside Diameter: 4.5 mm
 - Hose Outside Diameter: 6 mm
 - Colour: Translucent
 - Material: Nylon
 - Application: Air Brake, Fuel & Lube Applications, Industrial & Automotive Production Lines, Instrumentation & Secondary Air Systems
 - Length: 30 m
 - Maximum Operating Pressure: 16 bar
 - Manufacturer Series: NLF



4150288 4.5 mm

RS PRO COMPRESSED AIR PIPE BLACK NYLON 6MM X 30M NLF SERIES

- ขนาดบรรจุภัณฑ์: **30 x MTR**
- Hose Inside Diameter: 4.5 mm
 - Hose Outside Diameter: 6 mm
 - Colour: Black
 - Material: Nylon
 - Length: 30 m
 - Maximum Operating Pressure: 10 bar
 - Manufacturer Series: NLF
 - Minimum Operating Temperature: -40 °C



4150294 4.5 mm

RS PRO COMPRESSED AIR PIPE GREEN NYLON 6MM X 30M NLF

ขนาดบรรจุภัณฑ์: 30 x MTR

- Hose Inside Diameter: 4.5 mm
- Hose Outside Diameter: 6 mm
- Colour: Green
- Material: Nylon
- Length: 30 m
- Maximum Operating Pressure: 16 bar
- Manufacturer Series: NLF
- Minimum Operating Temperature: -40 °C



4150301 4.5 mm

RS PRO COMPRESSED AIR PIPE BLUE NYLON 6MM X 30M NLF SERIES

ขนาดบรรจุภัณฑ์: 30 x MTR

- Hose Inside Diameter: 4.5 mm
- Hose Outside Diameter: 6 mm
- Colour: Blue
- Material: Nylon
- Application: Air Brake, Fuel & Lube Applications, Industrial & Automotive Production Lines, Instrumentation & Secondary Air Systems
- Length: 30 m
- Maximum Operating Pressure: 16 bar
- Manufacturer Series: NLF



4150323 4.5 mm

RS PRO COMPRESSED AIR PIPE YELLOW NYLON 6MM X 30M NLF

ขนาดบรรจุภัณฑ์: 30 x MTR

- Hose Inside Diameter: 4.5 mm
- Hose Outside Diameter: 6 mm
- Colour: Yellow
- Material: Nylon
- Application: Air Brake, Fuel & Lube Applications, Industrial & Automotive Production Lines, Instrumentation & Secondary Air Systems
- Length: 30 m
- Maximum Operating Pressure: 16 bar
- Manufacturer Series: NLF



4150339 4.5 mm

RS PRO COMPRESSED AIR PIPE TRANSLUCENT NYLON 8MM X 30M

ขนาดบรรจุภัณฑ์: 30 x MTR

- Hose Inside Diameter: 6 mm
- Hose Outside Diameter: 8 mm
- Colour: Translucent
- Material: Nylon
- Application: Air Brake, Fuel & Lube Applications, Industrial & Automotive Production Lines, Instrumentation & Secondary Air Systems
- Length: 30 m
- Maximum Operating Pressure: 17 bar
- Manufacturer Series: NLF



4150345 6 mm

RS PRO COMPRESSED AIR PIPE BLACK NYLON 8MM X 30M NLF

ขนาดบรรจุภัณฑ์: 30 x MTR

- Hose Inside Diameter: 6 mm
- Hose Outside Diameter: 8 mm
- Colour: Black
- Material: Nylon
- Length: 30 m
- Maximum Operating Pressure: 17 bar
- Manufacturer Series: NLF
- Minimum Operating Temperature: -40 °C



4150351 6 mm

RS PRO COMPRESSED AIR PIPE RED NYLON 8MM X 30M NLF SERIES

ขนาดบรรจุภัณฑ์: 30 x MTR

- Hose Inside Diameter: 6 mm
- Hose Outside Diameter: 8 mm
- Colour: Red
- Material: Nylon
- Application: Air Brake, Fuel & Lube Applications, Industrial & Automotive Production Lines, Instrumentation & Secondary Air Systems
- Length: 30 m
- Maximum Operating Pressure: 17 bar
- Manufacturer Series: NLF



4150389 6 mm

RS PRO COMPRESSED AIR PIPE BLUE NYLON 8MM X 30M NLF SERIES

ขนาดบรรจุภัณฑ์: 30 x MTR

- Hose Inside Diameter: 6 mm
- Hose Outside Diameter: 8 mm
- Colour: Blue
- Material: Nylon
- Application: Air Brake, Fuel & Lube Applications, Industrial & Automotive Production Lines, Instrumentation & Secondary Air Systems
- Length: 30 m
- Maximum Operating Pressure: 17 bar
- Manufacturer Series: NLF



4150395 6 mm

RS PRO COMPRESSED AIR PIPE YELLOW NYLON 8MM X 30M NLF

ขนาดบรรจุภัณฑ์: 30 x MTR

- Hose Inside Diameter: 6 mm
- Hose Outside Diameter: 8 mm
- Colour: Yellow
- Material: Nylon
- Application: Air Brake, Fuel & Lube Applications, Industrial & Automotive Production Lines, Instrumentation & Secondary Air Systems
- Length: 30 m
- Maximum Operating Pressure: 17 bar
- Manufacturer Series: NLF



4150402 6 mm

RS PRO COMPRESSED AIR PIPE TRANSLUCENT NYLON 10MM X 30M

ขนาดบรรจุภัณฑ์: 30 x MTR

- Hose Inside Diameter: 7.5 mm
- Hose Outside Diameter: 10 mm
- Colour: Translucent
- Material: Nylon
- Application: Air Brake, Fuel & Lube Applications, Industrial & Automotive Production Lines, Instrumentation & Secondary Air Systems
- Length: 30 m
- Maximum Operating Pressure: 17 bar
- Manufacturer Series: NLF



4150418 7.5 mm

RS PRO COMPRESSED AIR PIPE BLACK NYLON 10MM X 30M NLF

ขนาดบรรจุภัณฑ์: 30 x MTR

- Hose Inside Diameter: 7.5 mm
- Hose Outside Diameter: 10 mm
- Colour: Black
- Material: Nylon
- Application: Air Brake, Fuel & Lube Applications, Industrial & Automotive Production Lines, Instrumentation & Secondary Air Systems
- Length: 30 m
- Maximum Operating Pressure: 17 bar
- Manufacturer Series: NLF



4150430 7.5 mm

RS PRO COMPRESSED AIR PIPE GREEN NYLON 10MM X 30M NLF

ขนาดบรรจุภัณฑ์: 30 x MTR

- Hose Inside Diameter: 7.5 mm
- Hose Outside Diameter: 10 mm
- Colour: Green
- Material: Nylon
- Application: Air Brake, Fuel & Lube Applications, Industrial & Automotive Production Lines, Instrumentation & Secondary Air Systems
- Length: 30 m
- Maximum Operating Pressure: 17 bar
- Manufacturer Series: NLF



4150446 7.5 mm

RS PRO COMPRESSED AIR PIPE BLUE NYLON 10MM X 30M NLF SERIES

ขนาดบรรจุภัณฑ์: 30 x MTR

- Hose Inside Diameter: 7.5 mm
- Hose Outside Diameter: 10 mm
- Colour: Blue
- Material: Nylon
- Application: Air Brake, Fuel & Lube Applications, Industrial & Automotive Production Lines, Instrumentation & Secondary Air Systems
- Length: 30 m
- Maximum Operating Pressure: 17 bar
- Manufacturer Series: NLF



4150468 7.5 mm

RS PRO COMPRESSED AIR PIPE TRANSLUCENT NYLON 12MM X 30M

ขนาดบรรจุภัณฑ์: 30 x MTR

- Hose Inside Diameter: 9.5 mm
- Hose Outside Diameter: 12 mm
- Colour: Translucent
- Material: Nylon
- Application: Air Brake, Fuel & Lube Applications, Industrial & Automotive Production Lines, Instrumentation & Secondary Air Systems
- Length: 30 m
- Maximum Operating Pressure: 14 bar
- Manufacturer Series: NLF



4150480 9.5 mm

RS PRO COMPRESSED AIR PIPE BLACK NYLON 12MM X 30M NLF

ขนาดบรรจุภัณฑ์: 30 x MTR

- Hose Inside Diameter: 9.5 mm
- Hose Outside Diameter: 12 mm
- Colour: Black
- Material: Nylon
- Application: Air Brake, Fuel & Lube Applications, Industrial & Automotive Production Lines, Instrumentation & Secondary Air Systems
- Length: 30 m
- Maximum Operating Pressure: 14 bar
- Manufacturer Series: NLF



4150496 9.5 mm

RS PRO COMPRESSED AIR PIPE RED NYLON 12MM X 30M NLF SERIES

ขนาดบรรจุภัณฑ์: 30 x MTR

- Hose Inside Diameter: 10 mm
- Hose Outside Diameter: 12 mm
- Colour: Red
- Material: Nylon
- Application: Push In Systems
- Length: 30 m
- Maximum Operating Pressure: 14 bar
- Manufacturer Series: NLF



4150519 10 mm

RS PRO COMPRESSED AIR PIPE BLUE NYLON 12MM X 30M NLF SERIES

ขนาดบรรจุภัณฑ์: 30 x MTR

- Hose Inside Diameter: 9.5 mm
- Hose Outside Diameter: 12 mm
- Colour: Blue
- Material: Nylon
- Application: Air Brake, Fuel & Lube Applications, Industrial & Automotive Production Lines, Instrumentation & Secondary Air Systems
- Length: 30 m
- Maximum Operating Pressure: 14 bar
- Manufacturer Series: NLF



4150525 9.5 mm

RS PRO COMPRESSED AIR PIPE BLACK NYLON 10MM X 30M NMF

- ขนาดบรรจุภัณฑ์: **30 x MTR**
- Hose Inside Diameter: 7 mm
 - Hose Outside Diameter: 10 mm
 - Colour: Black
 - Material: Nylon
 - Application: Air Brake, Fuel & Lube Applications, Industrial & Automotive Production Lines, Instrumentation & Secondary Air Systems
 - Length: 30 m
 - Maximum Operating Pressure: 22 bar
 - Manufacturer Series: NMF



4835052 7 mm

RS PRO COMPRESSED AIR PIPE GREEN NYLON 10MM X 30M NMF

- ขนาดบรรจุภัณฑ์: **30 x MTR**
- Hose Inside Diameter: 7 mm
 - Hose Outside Diameter: 10 mm
 - Colour: Green
 - Material: Nylon
 - Application: Air Brake, Fuel & Lube Applications, Industrial & Automotive Production Lines, Instrumentation & Secondary Air Systems
 - Length: 30 m
 - Maximum Operating Pressure: 22 bar
 - Manufacturer Series: NMF



4835074 7 mm

RS PRO COMPRESSED AIR PIPE BLUE NYLON 10MM X 30M NMF SERIES

- ขนาดบรรจุภัณฑ์: **30 x MTR**
- Hose Inside Diameter: 7 mm
 - Hose Outside Diameter: 10 mm
 - Colour: Blue
 - Material: Nylon
 - Application: Air Brake, Fuel & Lube Applications, Industrial & Automotive Production Lines, Instrumentation & Secondary Air Systems
 - Length: 30 m
 - Maximum Operating Pressure: 22 bar
 - Manufacturer Series: NMF



4835080 7 mm

RS PRO COMPRESSED AIR PIPE YELLOW NYLON 10MM X 30M NMF

- ขนาดบรรจุภัณฑ์: **30 x MTR**
- Hose Inside Diameter: 7 mm
 - Hose Outside Diameter: 10 mm
 - Colour: Yellow
 - Material: Nylon
 - Application: Air Brake, Fuel & Lube Applications, Industrial & Automotive Production Lines, Instrumentation & Secondary Air Systems
 - Length: 30 m
 - Maximum Operating Pressure: 22 bar
 - Manufacturer Series: NMF



4835096 7 mm

RS PRO COMPRESSED AIR PIPE BLACK NYLON 12MM X 30M NMF

- ขนาดบรรจุภัณฑ์: **30 x MTR**
- Hose Inside Diameter: 8.5 mm
 - Hose Outside Diameter: 12 mm
 - Colour: Black
 - Material: Nylon
 - Application: Air Brake, Fuel & Lube Applications, Industrial & Automotive Production Lines, Instrumentation & Secondary Air Systems
 - Length: 30 m
 - Maximum Operating Pressure: 21 bar
 - Manufacturer Series: NMF



4835103 8.5 mm

RS PRO COMPRESSED AIR PIPE BLUE NYLON 12MM X 30M NMF SERIES

- ขนาดบรรจุภัณฑ์: **30 x MTR**
- Hose Inside Diameter: 8.5 mm
 - Hose Outside Diameter: 12 mm
 - Colour: Blue
 - Material: Nylon
 - Application: Air Brake, Fuel & Lube Applications, Industrial & Automotive Production Lines, Instrumentation & Secondary Air Systems
 - Length: 30 m
 - Maximum Operating Pressure: 24 bar
 - Manufacturer Series: NMF



4835131 8.5 mm

RS PRO COMPRESSED AIR PIPE NATURAL NYLON 4MM X 30M NMF

- ขนาดบรรจุภัณฑ์: **30 x MTR**
- Hose Inside Diameter: 2.5 mm
 - Hose Outside Diameter: 4 mm
 - Colour: Natural
 - Material: Nylon
 - Application: Air Brake, Fuel & Lube Applications, Industrial & Automotive Production Lines, Instrumentation & Secondary Air Systems
 - Length: 30 m
 - Maximum Operating Pressure: 26 bar
 - Manufacturer Series: NMF



4835535 2.5 mm

RS PRO COMPRESSED AIR PIPE RED NYLON 4MM X 30M NMF SERIES

- ขนาดบรรจุภัณฑ์: **30 x MTR**
- Hose Inside Diameter: 2.5 mm
 - Hose Outside Diameter: 4 mm
 - Colour: Red
 - Material: Nylon
 - Application: Air Brake, Fuel & Lube Applications, Industrial & Automotive Production Lines, Instrumentation & Secondary Air Systems
 - Length: 30 m
 - Maximum Operating Pressure: 26 bar
 - Manufacturer Series: NMF



4835541 2.5 mm

RS PRO COMPRESSED AIR PIPE TRANSLUCENT NYLON 6MM X 30M

- ขนาดบรรจุภัณฑ์: **30 x MTR**
- Hose Inside Diameter: 4 mm
 - Hose Outside Diameter: 6 mm
 - Colour: Translucent
 - Material: Nylon
 - Application: Air Brake, Fuel & Lube Applications, Industrial & Automotive Production Lines, Instrumentation & Secondary Air Systems
 - Length: 30 m
 - Maximum Operating Pressure: 24 bar
 - Manufacturer Series: NMF



4835557 4 mm

RS PRO COMPRESSED AIR PIPE RED NYLON 6MM X 30M NMF SERIES

- ขนาดบรรจุภัณฑ์: **30 x MTR**
- Hose Inside Diameter: 4 mm
 - Hose Outside Diameter: 6 mm
 - Colour: Red
 - Material: Nylon
 - Application: Air Brake, Fuel & Lube Applications, Industrial & Automotive Production Lines, Instrumentation & Secondary Air Systems
 - Length: 30 m
 - Maximum Operating Pressure: 24 bar
 - Manufacturer Series: NMF



4835579 4 mm

RS PRO COMPRESSED AIR PIPE RED NYLON 8MM X 30M NMF SERIES

- ขนาดบรรจุภัณฑ์: **30 x MTR**
- Hose Inside Diameter: 5.5 mm
 - Hose Outside Diameter: 8 mm
 - Colour: Red
 - Material: Nylon
 - Application: Air Brake, Fuel & Lube Applications, Industrial & Automotive Production Lines, Instrumentation & Secondary Air Systems
 - Length: 30 m
 - Maximum Operating Pressure: 22 bar
 - Manufacturer Series: NMF



4835585 5.5 mm

RS PRO COMPRESSED AIR PIPE TRANSLUCENT NYLON 10MM X 30M

- ขนาดบรรจุภัณฑ์: **30 x MTR**
- Hose Inside Diameter: 7 mm
 - Hose Outside Diameter: 10 mm
 - Colour: Translucent
 - Material: Nylon
 - Application: Air Brake, Fuel & Lube Applications, Industrial & Automotive Production Lines, Instrumentation & Secondary Air Systems
 - Length: 30 m
 - Maximum Operating Pressure: 22 bar
 - Manufacturer Series: NMF



4835591 7 mm

RS PRO COMPRESSED AIR PIPE TRANSLUCENT NYLON 12MM X 30M

- ขนาดบรรจุภัณฑ์: **30 x MTR**
- Hose Inside Diameter: 8.5 mm
 - Hose Outside Diameter: 12 mm
 - Colour: Translucent
 - Material: Nylon
 - Application: Air Brake, Fuel & Lube Applications, Industrial & Automotive Production Lines, Instrumentation & Secondary Air Systems
 - Length: 30 m
 - Maximum Operating Pressure: 21 bar
 - Manufacturer Series: NMF



4835614 8.5 mm

RS PRO COMPRESSED AIR PIPE RED NYLON 12MM X 30M NMF SERIES

- ขนาดบรรจุภัณฑ์: **30 x MTR**
- Hose Inside Diameter: 8.5 mm
 - Hose Outside Diameter: 12 mm
 - Colour: Red
 - Material: Nylon
 - Application: Air Brake, Fuel & Lube Applications, Industrial & Automotive Production Lines, Instrumentation & Secondary Air Systems
 - Length: 30 m
 - Maximum Operating Pressure: 24 bar
 - Manufacturer Series: NMF



4835636 8.5 mm

RS PRO COMPRESSED AIR PIPE BLACK POLYURETHANE 4MM X 30M

- ขนาดบรรจุภัณฑ์: **1 x MTR**
- Hose Inside Diameter: 2.5 mm
 - Hose Outside Diameter: 4 mm
 - Colour: Black
 - Material: Polyurethane
 - Application: Chemical Transfer Tubing, Fuel & Lubrication Lines, Pneumatic Control Systems
 - Length: 30 m
 - Maximum Operating Pressure: 11 bar
 - Manufacturer Series: CPU



9172365 2.5 mm

RS PRO COMPRESSED AIR PIPE BLACK POLYURETHANE 6MM X 30M

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Inside Diameter: 4 mm
 - Hose Outside Diameter: 6 mm
 - Colour: Black
 - Material: Polyurethane
 - Application: Chemical Transfer Tubing, Fuel & Lubrication Lines, Pneumatic Control Systems
 - Length: 30 m
 - Maximum Operating Pressure: 10 bar
 - Manufacturer Series: CPU



9172369 4 mm

RS PRO COMPRESSED AIR PIPE RED POLYURETHANE 4MM X 30M CPU

- ขนาดบรรจุภัณฑ์: 1 x MTR
- Hose Inside Diameter: 2.5 mm
 - Hose Outside Diameter: 4 mm
 - Colour: Red
 - Material: Polyurethane
 - Application: Chemical Transfer Tubing, Fuel & Lubrication Lines, Pneumatic Control Systems
 - Length: 30 m
 - Maximum Operating Pressure: 11 bar
 - Manufacturer Series: CPU



9172429 2.5 mm

RS PRO COMPRESSED AIR PIPE YELLOW POLYURETHANE 4MM X 30M

- ขนาดบรรจุภัณฑ์: 1 x MTR
- Hose Inside Diameter: 2.5 mm
 - Hose Outside Diameter: 4 mm
 - Colour: Yellow
 - Material: Polyurethane
 - Application: Chemical Transfer Lines, Fuel & Lubrication Lines, Pneumatic Control Systems, Transfer of Food & Liquids
 - Length: 30 m
 - Maximum Operating Pressure: 11 bar
 - Manufacturer Series: CPU



9172432 2.5 mm

RS PRO COMPRESSED AIR PIPE RED POLYURETHANE 10MM X 30M CPU

- ขนาดบรรจุภัณฑ์: 1 x EA
- Hose Inside Diameter: 7.5 mm
 - Hose Outside Diameter: 10 mm
 - Colour: Red
 - Material: Polyurethane
 - Application: Chemical Transfer Tubing, Fuel & Lubrication Lines, Pneumatic Control Systems
 - Length: 30 m
 - Maximum Operating Pressure: 7.5 bar
 - Manufacturer Series: CPU



9172435 7.5 mm

RS PRO COMPRESSED AIR PIPE YELLOW POLYURETHANE 6MM X 30M

- ขนาดบรรจุภัณฑ์: 1 x MTR
- Hose Inside Diameter: 4 mm
 - Hose Outside Diameter: 6 mm
 - Colour: Yellow
 - Material: Polyurethane
 - Application: Chemical Transfer Tubing, Fuel & Lubrication Lines, Pneumatic Control Systems
 - Length: 30 m
 - Maximum Operating Pressure: 10 bar
 - Manufacturer Series: CPU



9172441 4 mm

RS PRO COMPRESSED AIR PIPE YELLOW POLYURETHANE 8MM X 30M

- ขนาดบรรจุภัณฑ์: 1 x EA
- Hose Inside Diameter: 5 mm
 - Hose Outside Diameter: 8 mm
 - Colour: Yellow
 - Material: Polyurethane
 - Application: Chemical Transfer Tubing, Fuel & Lubrication Lines, Pneumatic Control Systems
 - Length: 30 m
 - Maximum Operating Pressure: 10 bar
 - Manufacturer Series: CPU



9172444 5 mm

RS PRO BRASS PIPE FITTING, STRAIGHT THREADED NIPPLE, MALE

- ขนาดบรรจุภัณฑ์: 10 x EA
- Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Fitting Type: Nipple
 - Thread Size 1: 1/8 in
 - Connection Gender 1: Male
 - Thread Size 2: 1/8 in
 - Connection Gender 2: Male



1760978 Threaded

RS PRO BRASS PIPE FITTING, STRAIGHT THREADED NIPPLE, MALE

- ขนาดบรรจุภัณฑ์: 10 x EA
- Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Fitting Type: Nipple
 - Thread Size 1: 1/4 in
 - Connection Gender 1: Male
 - Thread Size 2: 1/4 in
 - Connection Gender 2: Male



1760979 Threaded

RS PRO BRASS PIPE FITTING, STRAIGHT THREADED NIPPLE, MALE

- ขนาดบรรจุภัณฑ์: 10 x EA
- Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Fitting Type: Nipple
 - Thread Size 1: 1 in
 - Connection Gender 1: Male
 - Thread Size 2: 1 in
 - Connection Gender 2: Male



1760984 Threaded

RS PRO BRASS PIPE FITTING, STRAIGHT THREADED NIPPLE, MALE

- ขนาดบรรจุภัณฑ์: 10 x EA
- Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Fitting Type: Nipple
 - Thread Size 1: 1/4 in
 - Connection Gender 1: Male
 - Thread Size 2: 1/4 in
 - Connection Gender 2: Male



1760986 Threaded

RS PRO BRASS PIPE FITTING, STRAIGHT THREADED FITTING, MALE

- ขนาดบรรจุภัณฑ์: 10 x EA
- Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Fitting Type: Fitting
 - Thread Size 1: 1/4 in
 - Connection Gender 1: Male
 - Thread Size 2: 3/8 in
 - Connection Gender 2: Male



1760990 Threaded

RS PRO BRASS PIPE FITTING, STRAIGHT THREADED FITTING, MALE

- ขนาดบรรจุภัณฑ์: 10 x EA
- Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Fitting Type: Fitting
 - Thread Size 1: 3/8 in
 - Connection Gender 1: Male
 - Thread Size 2: 1/2 in
 - Connection Gender 2: Male



1760992 Threaded

RS PRO BRASS PIPE FITTING, STRAIGHT THREADED FITTING, MALE

- ขนาดบรรจุภัณฑ์: 10 x EA
- Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Fitting Type: Fitting
 - Thread Size 1: 1/2 in
 - Connection Gender 1: Male
 - Thread Size 2: 3/4 in
 - Connection Gender 2: Male



1760993 Threaded

RS PRO BRASS PIPE FITTING, STRAIGHT THREADED FITTING, MALE

- ขนาดบรรจุภัณฑ์: 10 x EA
- Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Fitting Type: Fitting
 - Thread Size 1: 1/8 in
 - Connection Gender 1: Male
 - Thread Size 2: 1/4 in
 - Connection Gender 2: Male



1760995 Threaded

RS PRO BRASS PIPE FITTING, STRAIGHT THREADED REDUCER, MALE

- ขนาดบรรจุภัณฑ์: 10 x EA
- Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Fitting Type: Reducer
 - Thread Size 1: 1/4 in
 - Connection Gender 1: Male
 - Thread Size 2: 1/4 in
 - Connection Gender 2: Female



1760998 Threaded

RS PRO BRASS PIPE FITTING, STRAIGHT THREADED REDUCER, MALE

- ขนาดบรรจุภัณฑ์: 10 x EA
- Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Fitting Type: Reducer
 - Thread Size 1: 1/4 in
 - Connection Gender 1: Male
 - Thread Size 2: 3/8 in
 - Connection Gender 2: Female



1761000 Threaded

RS PRO BRASS PIPE FITTING, STRAIGHT THREADED REDUCER, MALE

- ขนาดบรรจุภัณฑ์: 10 x EA
- Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Fitting Type: Reducer
 - Thread Size 1: 3/8 in
 - Connection Gender 1: Male
 - Thread Size 2: 3/8 in
 - Connection Gender 2: Female



1761002 Threaded

REDUCER - BSPP 1/8-1/4

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Fitting Type: Reducer
 - Thread Size 1: 1/8 in
 - Connection Gender 1: Male
 - Thread Size 2: 1/4 in
 - Connection Gender 2: Female
 - Material: Brass



1761004 Threaded

RS PRO BRASS PIPE FITTING, STRAIGHT THREADED INCREASER,

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Fitting Type: Increaser
 - Thread Size 1: 1/8 in
 - Connection Gender 1: Male
 - Thread Size 2: 1/8 in
 - Connection Gender 2: Female



1761005 Threaded

RS PRO BRASS PIPE FITTING, STRAIGHT THREADED REDUCER, MALE

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Fitting Type: Reducer
 - Thread Size 1: 1/4 in
 - Connection Gender 1: Male
 - Thread Size 2: 1/8 in
 - Connection Gender 2: Female



1761010 Threaded

RS PRO BRASS PIPE FITTING, STRAIGHT THREADED REDUCER, MALE

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Fitting Type: Reducer
 - Thread Size 1: 1/2 in
 - Connection Gender 1: Male
 - Thread Size 2: 1/4 in
 - Connection Gender 2: Female



1761013 Threaded

RS PRO BRASS PIPE FITTING, STRAIGHT THREADED REDUCER, MALE

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Fitting Type: Reducer
 - Thread Size 1: 1/2 in
 - Connection Gender 1: Male
 - Thread Size 2: 3/8 in
 - Connection Gender 2: Female



1761024 Threaded

RS PRO BRASS PIPE FITTING, STRAIGHT THREADED REDUCER, MALE

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Fitting Type: Reducer
 - Thread Size 1: 3/4 in
 - Connection Gender 1: Male
 - Thread Size 2: 1/2 in
 - Connection Gender 2: Female
 - Material: Brass



1761025 Threaded

RS PRO FITTING FITTING 1/4 IN

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Pipe Fitting Connection Type: Fitting
 - Thread Size 1: 1/4 in



1761036 Fitting

RS PRO BRASS PIPE FITTING, STRAIGHT THREADED REDUCER,

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Fitting Type: Reducer
 - Thread Size 1: 1/8 in
 - Connection Gender 1: Female
 - Thread Size 2: 3/8 in
 - Connection Gender 2: Female
 - Material: Brass



1761041 Threaded

RS PRO FITTING FITTING 3/8 IN

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Fitting Type: Fitting
 - Thread Size 1: 3/8 in



1761045 Fitting

RS PRO FITTING FITTING 1/2 IN

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Fitting Type: Fitting
 - Thread Size 1: 1/2 in



1761046 Fitting

RS PRO BRASS PIPE FITTING, STRAIGHT THREADED PLUG, MALE

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Fitting Type: Plug
 - Thread Standard 1: R
 - Thread Size 1: 1/4 in
 - Connection Gender 1: Male
 - Material: Brass



1761055 Threaded

RS PRO BRASS PIPE FITTING, STRAIGHT THREADED PLUG, MALE R

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Pipe Fitting Connection Type: Threaded
 - Fitting Direction: Straight
 - Fitting Type: Plug
 - Thread Standard 1: R
 - Thread Size 1: 3/8 in
 - Connection Gender 1: Male
 - Material: Brass



1761056 Threaded

FEMALE TEE 1/4

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Fitting Type: Fitting



1761060 Fitting

RS PRO FITTING FITTING

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Fitting Type: Fitting



1761061 Fitting

RS PRO FITTING FITTING

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Fitting Type: Fitting



1761066 Fitting

RS PRO FITTING, TEE FITTING, MALE G 3/8 IN TO FEMALE G 3/8 IN

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Fitting Direction: Tee
 - Fitting Type: Fitting
 - Thread Standard 1: G
 - Thread Size 1: 3/8 in
 - Connection Gender 1: Male
 - Thread Standard 2: G
 - Thread Size 2: 3/8 in
 - Connection Gender 2: Female



1761067 Tee

RS PRO FITTING FITTING

ขนาดบรรจุภัณฑ์: 10 x EA
 • Fitting Type: Fitting



1761072 Fitting

RS PRO FITTING FITTING

ขนาดบรรจุภัณฑ์: 10 x EA
 • Fitting Type: Fitting



1761073 Fitting

RS PRO FITTING FITTING

ขนาดบรรจุภัณฑ์: 10 x EA
 • Fitting Type: Fitting



1761076 Fitting

RS PRO FITTING FITTING

ขนาดบรรจุภัณฑ์: 10 x EA
 • Fitting Type: Fitting



1761080 Fitting

RS PRO BRASS PIPE FITTING, 90° THREADED ELBOW, FEMALE 3/8 IN TO

ขนาดบรรจุภัณฑ์: 10 x EA
 • Pipe Fitting Connection Type: Threaded
 • Fitting Direction: 90°
 • Fitting Type: Elbow
 • Thread Size 1: 3/8 in
 • Connection Gender 1: Female
 • Thread Size 2: 3/8 in
 • Connection Gender 2: Female
 • Material: Brass



1761081 Threaded

RS PRO FITTING FITTING

ขนาดบรรจุภัณฑ์: 10 x EA
 • Fitting Type: Fitting



1761084 Fitting

RS PRO FITTING FITTING

ขนาดบรรจุภัณฑ์: 10 x EA
 • Fitting Type: Fitting



1761085 Fitting

RS PRO FITTING FITTING

ขนาดบรรจุภัณฑ์: 10 x EA
 • Fitting Type: Fitting



1761092 Fitting

ADAT.F-BSP/M-NPTF 1/8-1/8 NIC. 1/8-1/8

ขนาดบรรจุภัณฑ์: 10 x EA
 • Fitting Type: Fitting



1761113 Fitting

ADAT.F-BSP/M-NPTF 1/4-1/4 NIC. 1/4-1/4 N

ขนาดบรรจุภัณฑ์: 10 x EA
 • Fitting Type: Fitting



1761114 Fitting

RS PRO FITTING FITTING

ขนาดบรรจุภัณฑ์: 10 x EA
 • Fitting Type: Fitting



1761115 Fitting

RS PRO FITTING FITTING

ขนาดบรรจุภัณฑ์: 10 x EA
 • Fitting Type: Fitting



1761117 Fitting

RS PRO FITTING FITTING

ขนาดบรรจุภัณฑ์: 10 x EA
 • Fitting Type: Fitting



1761118 Fitting

RS PRO BRASS PIPE FITTING, STRAIGHT THREADED ADAPTER, MALE

ขนาดบรรจุภัณฑ์: 10 x EA
 • Pipe Fitting Connection Type: Threaded
 • Fitting Direction: Straight
 • Fitting Type: Adapter
 • Thread Standard 1: G
 • Thread Size 1: 3/8 in
 • Connection Gender 1: Male
 • Thread Size 2: 3/8 in
 • Connection Gender 2: Female



1761119 Threaded

RS PRO FITTING FITTING

ขนาดบรรจุภัณฑ์: 10 x EA
 • Fitting Type: Fitting



1761120 Fitting

TEE CONNECTOR COMPRESSION

ขนาดบรรจุภัณฑ์: 10 x EA
 • Fitting Direction: Tee
 • Fitting Type: Tee
 • Material: Brass



2312553 Tee

RS PRO BRASS PUSH FIT FITTING, TEE COMPRESSION TEE, FEMALE METRIC

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Pipe Fitting Connection Type: Compression
 - Fitting Direction: Tee
 - Fitting Type: Tee
 - Thread Standard 1: Metric
 - Thread Size 1: M14
 - Connection Gender 1: Female
 - Thread Standard 2: Metric
 - Thread Size 2: M14



2312554 Compression

STRAIGHT FEMALE ADAPTOR COMPRESSION

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Fitting Direction: Straight
 - Fitting Type: Adapter
 - Material: Brass



2312627 Straight

NIPPLE TAPER - NPTF

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Fitting Direction: Straight
 - Fitting Type: Nipple
 - Material: Brass



2312778 Straight

NIPPLE TAPER - NPTF

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Fitting Direction: Straight
 - Fitting Type: Nipple
 - Material: Brass



2312779 Straight

RS PRO 1500BTU/H 35CFM PNEUMATIC CABINET COOLER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Control Device Included: No
 - Maximum Cooling Capacity: 1500 Btu/h
 - Maximum Flow Rate: 35 cfm



2915386 No

RS PRO 1500BTU/H 35CFM PNEUMATIC CABINET COOLER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Control Device Included: No
 - Maximum Cooling Capacity: 1500 Btu/h
 - Maximum Flow Rate: 35 cfm



4453060 No

RS PRO ADJUSTABLE 2500BTU/H 991L/MIN COLD AIR GUN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Type: Adjustable
 - Maximum Cooling Capacity: 2500 Btu/h
 - Maximum Flow Rate: 991 L/min



4453054 Adjustable

RS PRO R 3/8 AUTOMATIC CONDENSATE DRAIN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Manufacturer Series: V9112
 - Drain Type: Automatic
 - Inlet Port: R 3/8
 - Outlet Port: R 3/8
 - Dimensions: 123 x 96 mm



2066123 V9112

PNEUMATIC,TUBE,COPPER,1/4 O/D

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Nominal Outer Diameter: 6.35 mm
 - Length: 10 m
 - Maximum Working Pressure: 120 bar
 - Finish: Copper



846474 6.35 mm

RS PRO 94 BAR 10M LONG COPPER PIPE, 7.9MM OUTER DIAM. COPPER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Nominal Outer Diameter: 7.9 mm
 - Length: 10 m
 - Maximum Working Pressure: 94 bar
 - Finish: Copper



846480 7.9 mm

RS PRO 77 BAR 10M LONG COPPER PIPE, 9.5MM OUTER DIAM. COPPER

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Nominal Outer Diameter: 9.5 mm
 - Length: 10 m
 - Maximum Working Pressure: 77 bar
 - Finish: Copper



846496 9.5 mm

PNEUMATIC,TUBE,COPPER,4MM O/D

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Nominal Outer Diameter: 4 mm
 - Length: 10 m
 - Maximum Working Pressure: 128 bar
 - Finish: Copper



846503 4 mm

PNEUMATIC,TUBE,COPPER,5MM O/D

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Nominal Outer Diameter: 5 mm
 - Length: 10 m
 - Maximum Working Pressure: 138 bar
 - Finish: Copper



846519 5 mm

PNEUMATIC,TUBE,COPPER,6MM O/D

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Nominal Outer Diameter: 6 mm
 - Length: 10 m
 - Maximum Working Pressure: 112 bar
 - Finish: Copper



846525 6 mm

RS PRO 77 BAR 3M LONG COPPER PIPE, 12.7MM OUTER DIAM. COPPER

- ขนาดบรรจุภัณฑ์: **3 x EA**
- Nominal Outer Diameter: 12.7 mm
 - Length: 3 m
 - Maximum Working Pressure: 77 bar
 - Finish: Copper



846531 12.7 mm

PNEUMATIC,TUBE,COPPER,8MM O/D

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Nominal Outer Diameter: 8 mm
 - Length: 10 m
 - Maximum Working Pressure: 81 bar
 - Finish: Copper



846828 8 mm

RS PRO SOLENOID VALVE CONNECTOR

- ขนาดบรรจุภัณฑ์: 1 x EA
 • Colour: Black
 • IP Rating: IP65



1762067 Black

RS PRO G 1/8 FRL, MANUAL, SEMI AUTOMATIC DRAIN, 20MM

- ขนาดบรรจุภัณฑ์: 1 x EA
 • Manufacturer Series: T100 Mini
 • Port Connection: G 1/8
 • Drain Type: Manual, Semi Automatic
 • Filtration Size: 20 µm
 • Pressure Gauge Port Size: G 1/8
 • Minimum Operating Pressure: 0 bar
 • Port Connection Thread Size: 1/8 in
 • Port Connection Thread Standard: G



1977906 T100 Mini

RS PRO G 1/4 FRL, MANUAL, SEMI AUTOMATIC DRAIN, 20MM

- ขนาดบรรจุภัณฑ์: 1 x EA
 • Manufacturer Series: T100 Mini
 • Port Connection: G 1/4
 • Drain Type: Manual, Semi Automatic
 • Filtration Size: 20 µm
 • Pressure Gauge Port Size: G 1/8
 • Minimum Operating Pressure: 0 bar
 • Port Connection Thread Size: 1/4 in
 • Port Connection Thread Standard: G



1977907 T100 Mini

RS PRO G 1/2 FRL, MANUAL, SEMI AUTOMATIC DRAIN, 20MM

- ขนาดบรรจุภัณฑ์: 1 x EA
 • Manufacturer Series: T100
 • Port Connection: G 1/2
 • Drain Type: Manual, Semi Automatic
 • Filtration Size: 20 µm
 • Pressure Gauge Port Size: G 1/8
 • Minimum Operating Pressure: 0 bar
 • Port Connection Thread Size: 1/2 in
 • Port Connection Thread Standard: G



1977910 T100

RS PRO G 1/2 FILTER REGULATOR LUBRICATOR, AUTO DRAIN, 5M

- ขนาดบรรจุภัณฑ์: 1 x EA
 • Manufacturer Series: EAC4000
 • Port Connection: G 1/2
 • Drain Type: Auto
 • Filtration Size: 5 µm



2351094 EAC4000

RS PRO G 1/4 FILTER REGULATOR LUBRICATOR, AUTO DRAIN, 40M

- ขนาดบรรจุภัณฑ์: 1 x EA
 • Manufacturer Series: EA3000
 • Port Connection: G 1/4
 • Drain Type: Auto
 • Filtration Size: 40 µm



2351101 EA3000

RS PRO G 1/4 FILTER REGULATOR LUBRICATOR, MANUAL DRAIN, 25M

- ขนาดบรรจุภัณฑ์: 1 x EA
 • Manufacturer Series: EA3000
 • Port Connection: G 1/4
 • Drain Type: Manual
 • Filtration Size: 25 µm



2351106 EC

RS PRO G 1/2 FILTER REGULATOR LUBRICATOR, AUTO DRAIN, 25M

- ขนาดบรรจุภัณฑ์: 1 x EA
 • Manufacturer Series: EA3000
 • Port Connection: G 1/2
 • Drain Type: Auto
 • Filtration Size: 25 µm



2351107 EA3000

RS PRO G 1/2 FRL, 20M FILTRATION SIZE - WITH PRESSURE GAUGE

- ขนาดบรรจุภัณฑ์: 1 x EA
 • Manufacturer Series: S80
 • Port Connection: G 1/2
 • Filtration Size: 20 µm
 • Integrated Pressure Gauge: With Pressure Gauge
 • Minimum Operating Pressure: 0 bar
 • Minimum Ambient Operating Temperature: -10 °C
 • Port Connection Thread Size: 1/2 in
 • Port Connection Thread Standard: G



7840085 S80

RS PRO FILTER REGULATOR, 20MM, G 1/4

- ขนาดบรรจุภัณฑ์: 1 x EA
 • Port Connection: G 1/4
 • Filtration Size: 20 µm
 • Pressure Gauge Port: G 1/4
 • Pressure Gauge Port Thread Size: 1/8 in
 • Port Connection Thread Size: G 1/4
 • Maximum Operating Pressure: 8 bar
 • Maximum Ambient Operating Temperature: +50 °C
 • Minimum Process Operating Temperature: -10 °C



1761727 G 1/4

RS PRO FILTER REGULATOR, 20MM, G 1/2

- ขนาดบรรจุภัณฑ์: 1 x EA
 • Port Connection: G 1/2
 • Filtration Size: 20 µm
 • Pressure Gauge Port: G 1/2
 • Pressure Gauge Port Thread Size: 1/8 in
 • Port Connection Thread Size: G 1/2
 • Maximum Operating Pressure: 8 bar
 • Maximum Ambient Operating Temperature: +50 °C
 • Minimum Process Operating Temperature: -10 °C



1761738 G 1/2

RS PRO FILTER REGULATOR, 20MM, G 3/4

- ขนาดบรรจุภัณฑ์: 1 x EA
 • Port Connection: G 3/4
 • Filtration Size: 20 µm
 • Pressure Gauge Port: G 3/4
 • Pressure Gauge Port Thread Size: 1/8 in
 • Port Connection Thread Size: G 3/4
 • Maximum Operating Pressure: 8 bar
 • Maximum Ambient Operating Temperature: +50 °C
 • Minimum Process Operating Temperature: -10 °C



1761741 G 3/4

RS PRO FILTER REGULATOR, 20MM, G 1/8, MANUAL, SEMI AUTOMATIC

- ขนาดบรรจุภัณฑ์: 1 x EA
 • Port Connection: G 1/8
 • Drain Type: Manual, Semi Automatic
 • Filtration Size: 20 µm
 • Pressure Gauge Port: G 1/8
 • Pressure Gauge Port Thread Size: 1/8 in
 • Port Connection Thread Size: 1/8 in
 • Maximum Operating Pressure: 12 bar
 • Port Connection Thread Standard: G



1977904 G 1/8

RS PRO EA4000 FILTER REGULATOR, 40MM, G 1/2, AUTO

- ขนาดบรรจุภัณฑ์: 1 x EA
 • Manufacturer Series: EA4000
 • Port Connection: G 1/2
 • Drain Type: Auto
 • Filtration Size: 40 µm
 • Maximum Operating Pressure: 10 bar



2351104 EA4000

RS PRO EC FILTER REGULATOR, 5M, G 1/4, MANUAL

- ขนาดบรรจุภัณฑ์: 1 x EA
 • Manufacturer Series: EC
 • Port Connection: G 1/4
 • Drain Type: Manual
 • Filtration Size: 5 µm
 • Maximum Operating Pressure: 10 bar



2351110 EC

CLEVIS, KIT, SHORT, 4MM

- ขนาดบรรจุภัณฑ์: 1 x EA
 • Rod Connection Thread: M4 x 0.7
 • Ball Diameter: 4 mm
 • Overall Length: 21 mm
 • Overall Width: 8 mm
 • Material: Steel
 • Finish: Zinc



3120157 M4 x 0.7

CLEVIS,SHORT,KIT,8MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Rod Connection Thread: M8 x 1.25
 - Ball Diameter: 8 mm
 - Overall Length: 42 mm
 - Overall Width: 16 mm
 - Material: Steel
 - Finish: Zinc



3120236 M8 x 1.25

CLEVIS,SHORT,KIT,6MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Rod Connection Thread: M6 x 1
 - Ball Diameter: 6 mm
 - Overall Length: 31 mm
 - Overall Width: 12 mm
 - Material: Steel
 - Finish: Zinc



3120242 M6 x 1

RS PRO HOSE CONNECTOR HOSE TAIL ADAPTOR 1/4IN 7MM ID, 14 MPA,

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Hose Connector Type: Hose Tail Adaptor
 - Connector Gender: Male
 - Thread Size: 1/4 in
 - Hose Inner Diameter: 7 mm
 - Maximum Working Pressure: 14 Mpa, 140 bar
 - Body Material: Stainless Steel



1762202 Hose Tail Adaptor

RS PRO HOSE CONNECTOR HOSE TAIL ADAPTOR 1/8IN 7MM ID, 14 MPA,

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Hose Connector Type: Hose Tail Adaptor
 - Connector Gender: Male
 - Thread Size: 1/8 in
 - Hose Inner Diameter: 7 mm
 - Maximum Working Pressure: 14 Mpa, 140 bar
 - Body Material: Stainless Steel



1762203 Hose Tail Adaptor

RS PRO HOSE CONNECTOR HOSE TAIL ADAPTOR 3/8IN 10MM ID, 14

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Hose Connector Type: Hose Tail Adaptor
 - Connector Gender: Male
 - Thread Size: 3/8 in
 - Hose Inner Diameter: 10 mm
 - Maximum Working Pressure: 14 Mpa, 140 bar
 - Body Material: Stainless Steel



1762205 Hose Tail Adaptor

RS PRO BLUE FLEXIBLE TUBING, 33MM ID, PVC, 7 BAR MAX WORKING

- ขนาดบรรจุภัณฑ์: **10 x MTR**
- Inner Diameter: 33 mm
 - Outer Diameter: 36.2 mm
 - Maximum Working Pressure: 7 bar
 - Material: PVC
 - Suitable Applications: Chemical, Water
 - Minimum Operating Temperature: -25 °C
 - Maximum Operating Temperature: +60 °C
 - Length: 10 m



2357415 33 mm

RS PRO BLUE FLEXIBLE TUBING, 33MM ID, PVC, 7 BAR MAX WORKING

- ขนาดบรรจุภัณฑ์: **20 x MTR**
- Inner Diameter: 33 mm
 - Outer Diameter: 36.2 mm
 - Maximum Working Pressure: 7 bar
 - Material: PVC
 - Suitable Applications: Chemical, Water
 - Minimum Operating Temperature: -25 °C
 - Maximum Operating Temperature: +60 °C
 - Length: 20 m



2357421 33 mm

HOSE,LAY FLAT,38MMX10M

- ขนาดบรรจุภัณฑ์: **10 x MTR**
- Inner Diameter: 38 mm
 - Outer Diameter: 43.2 mm
 - Material: PVC
 - Colour: Blue
 - Reinforced: Yes
 - Suitable Applications: Chemical, Water
 - Length: 10 m
 - Minimum Operating Temperature: -25 °C



2357437 38 mm

RS PRO BLUE FLEXIBLE TUBING, 52MM ID, PVC, 4.5 BAR MAX WORKING

- ขนาดบรรจุภัณฑ์: **20 x MTR**
- Inner Diameter: 52 mm
 - Outer Diameter: 55.3 mm
 - Maximum Working Pressure: 4.5 bar
 - Material: PVC
 - Suitable Applications: Chemical, Water
 - Minimum Operating Temperature: -25 °C
 - Maximum Operating Temperature: +60 °C
 - Length: 20 m



2357471 52 mm

RS PRO CLEAR FLEXIBLE TUBE, 2.5MM ID, 5M

- ขนาดบรรจุภัณฑ์: **5 x MTR**
- Inner Diameter: 2.5 mm
 - Length: 5 m
 - Colour: Clear



4868901 2.5 mm

RS PRO CLEAR FLEXIBLE TUBE, 8MM ID, 5M

- ขนาดบรรจุภัณฑ์: **5 x MTR**
- Inner Diameter: 8 mm
 - Length: 5 m
 - Colour: Clear



4868945 8 mm

RS PRO CLEAR FLEXIBLE TUBE, 10MM ID, 5M

- ขนาดบรรจุภัณฑ์: **5 x MTR**
- Inner Diameter: 10 mm
 - Length: 5 m
 - Colour: Clear



4868951 10 mm

RS PRO 1/4 IN BSPT 8MM HOSE REEL 15 BAR 10M LENGTH, WALL MOUNTED

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inlet Connection: 1/4 in BSPT
 - Hose Inner Diameter: 8 mm
 - Hose Length: 10 m
 - Maximum Working Pressure: 15 bar
 - Inlet Connection Size: 1/4 in
 - Inlet Thread Standard: BSPT
 - Mounting: Wall Mounted
 - Retraction Operation: Automatic



7883732 1/4 in BSPT

RS PRO 1/4 IN BSPT 8MM HOSE REEL 15 BAR 15M LENGTH, WALL MOUNTED

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inlet Connection: 1/4 in BSPT
 - Hose Inner Diameter: 8 mm
 - Hose Length: 15 m
 - Maximum Working Pressure: 15 bar
 - Inlet Connection Size: 1/4 in
 - Inlet Thread Standard: BSPT
 - Mounting: Wall Mounted
 - Retraction Operation: Automatic



7883736 1/4 in BSPT

RS PRO 1/4 IN BSPT 8MM HOSE REEL 15 BAR 10M LENGTH, WALL MOUNTED

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Inlet Connection: 1/4 in BSPT
 - Hose Inner Diameter: 8 mm
 - Hose Length: 10 m
 - Maximum Working Pressure: 15 bar
 - Inlet Connection Size: 1/4 in
 - Inlet Thread Standard: BSPT
 - Mounting: Wall Mounted
 - Retraction Operation: Automatic



7883739 1/4 in BSPT

RS PRO 8MM HOSE REEL 200 PSI 30M LENGTH, FREE STANDING

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Inner Diameter: 8 mm
 - Hose Included: Yes
 - Hose Length: 30 m
 - Maximum Working Pressure: 200 psi
 - Inlet Connection Size: 1/4 in
 - Inlet Thread Standard: BSPT
 - Mounting: Free Standing
 - Retraction Operation: Manual



8738854 8 mm

RS PRO 9.5MM HOSE REEL 200 PSI 25M LENGTH, FREE STANDING

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Inner Diameter: 9.5 mm
 - Hose Included: Yes
 - Hose Length: 25 m
 - Maximum Working Pressure: 200 psi
 - Inlet Connection Size: 3/8 in
 - Inlet Thread Standard: BSPT
 - Mounting: Free Standing
 - Retraction Operation: Manual



8738857 9.5 mm

RS PRO 10MM HOSE REEL 200 PSI 20M LENGTH, FREE STANDING

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Hose Inner Diameter: 10 mm
 - Hose Included: Yes
 - Hose Length: 20 m
 - Maximum Working Pressure: 200 psi
 - Inlet Connection Size: 3/8 in
 - Inlet Thread Standard: BSPT
 - Mounting: Free Standing
 - Retraction Operation: Manual



8738860 10 mm

RS PRO DSM SERIES REED SWITCH, 2.5M FLY LEAD, BAND MOUNTED

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Manufacturer Series: DSM
 - Type: Reed
 - Mounting Type: Band
 - Operation: NO
 - Fly Lead Length: 2.5 m



3043959 DSM

RS PRO VDMA 24562 SERIES REED SWITCH, 1M FLY LEAD, GROOVE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Manufacturer Series: VDMA 24562
 - Type: Reed
 - Mounting Type: Groove
 - Operation: NO
 - Fly Lead Length: 1 m



4802349 VDMA 24562

TUBE CUTTER 3MM - 15MM

- ขนาดบรรจุภัณฑ์: **1 x SET**
- Cutting Capacity: 15 mm
 - Material Cut: Plastic
 - Body Material: Plastic



1728969 15 mm

RS PRO CUTTER BLADE 15 MM, CUTS PLASTIC

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Cutting Capacity: 15 mm
 - Material Cut: Plastic



1728970 15 mm

PLASTIC TUBE CUTTER

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Material Cut: Plastic



1760977 Plastic

RS PRO CYLINDER CLEVIS, TO FIT 63MM BORE SIZE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- To Fit Bore Size: 63 mm
 - Product Type: Clevis



1761561 63 mm

RS PRO CYLINDER CLEVIS, TO FIT 50MM BORE SIZE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- To Fit Bore Size: 50 mm



1761565 50 mm

RS PRO CYLINDER CLEVIS, TO FIT 40MM BORE SIZE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- To Fit Bore Size: 40 mm



1761566 40 mm

RS PRO CYLINDER CLEVIS, TO FIT 80MM BORE SIZE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- To Fit Bore Size: 80 mm



1761569 80 mm

RS PRO CYLINDER CLEVIS, TO FIT 50MM BORE SIZE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- To Fit Bore Size: 50 mm



1761571 50 mm

RS PRO CYLINDER CLEVIS, TO FIT 32MM BORE SIZE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- To Fit Bore Size: 32 mm



1761573 32 mm

RS PRO CLEVIS PIN, TO FIT 63MM BORE SIZE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- To Fit Bore Size: 63 mm
 - Product Type: Pin



1761579 63 mm

RS PRO CLEVIS PIN, TO FIT 80MM BORE SIZE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- To Fit Bore Size: 80 mm
 - Product Type: Pin



1761589 80 mm

RS PRO CLEVIS PIN, TO FIT 50MM BORE SIZE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- To Fit Bore Size: 50 mm
 - Product Type: Pin



1761591 50 mm

RS PRO CLEVIS PIN, TO FIT 32MM BORE SIZE

- ขนาดบรรจุภัณฑ์: 1 x EA
 • To Fit Bore Size: 32 mm
 • Product Type: Pin



1761593 32 mm

RS PRO CYLINDER CLEVIS, TO FIT 20MM BORE SIZE

- ขนาดบรรจุภัณฑ์: 1 x EA
 • To Fit Bore Size: 20 mm



1761609 20 mm

RS PRO CLEVIS ROD CYLINDER, TO FIT 50MM BORE SIZE

- ขนาดบรรจุภัณฑ์: 1 x EA
 • To Fit Bore Size: 50 mm
 • Product Type: Yoke



1761613 50 mm

RS PRO CLEVIS ROD CYLINDER, TO FIT 25MM BORE SIZE

- ขนาดบรรจุภัณฑ์: 1 x EA
 • To Fit Bore Size: 25 mm
 • Product Type: Yoke



1761615 25 mm

RS PRO CLEVIS ROD CYLINDER, TO FIT 20MM BORE SIZE

- ขนาดบรรจุภัณฑ์: 1 x EA
 • To Fit Bore Size: 20 mm
 • Product Type: Yoke



1761616 20 mm

RS PRO CLEVIS ROD CYLINDER, TO FIT 12MM BORE SIZE

- ขนาดบรรจุภัณฑ์: 1 x EA
 • To Fit Bore Size: 12 mm
 • Product Type: Yoke



1761617 12 mm

RS PRO CYLINDER BRACKET, TO FIT 20MM BORE SIZE

- ขนาดบรรจุภัณฑ์: 1 x EA
 • To Fit Bore Size: 20 mm



1761621 20 mm

RS PRO SENSOR BRACKET, TO FIT 20MM BORE SIZE

- ขนาดบรรจุภัณฑ์: 1 x EA
 • To Fit Bore Size: 20 mm



1761624 20 mm

RS PRO FOOT, FOR USE WITH C85 SERIES SINGLE & DOUBLE ACTING

- ขนาดบรรจุภัณฑ์: 1 x EA
 • Manufacturer Series: AP
 • For Use With: C85 Series Single & Double Acting Cylinders
 • To Fit Bore Size: 20 mm, 25 mm



3043640 AP

RS PRO REAR CLEVIS, TO FIT 40MM BORE SIZE

- ขนาดบรรจุภัณฑ์: 1 x EA
 • Manufacturer Series: CERF
 • To Fit Bore Size: 40 mm
 • Product Type: Rear Clevis



3044211 CERF

RS PRO REAR HINGE, TO FIT 50MM BORE SIZE

- ขนาดบรรจุภัณฑ์: 1 x EA
 • Manufacturer Series: CERF
 • To Fit Bore Size: 50 mm
 • Product Type: Rear Hinge



3044299 CERF

RS PRO CETOP CLEVIS, FOR USE WITH BORE SIZE 32MM, TO FIT 32MM

- ขนาดบรรจุภัณฑ์: 1 x EA
 • Manufacturer Series: 314
 • For Use With: Bore Size 32mm
 • To Fit Bore Size: 32 mm



3120292 314

RS PRO CETOP CLEVIS, FOR USE WITH BORE SIZE 12MM, TO FIT 12MM

- ขนาดบรรจุภัณฑ์: 1 x EA
 • Manufacturer Series: 314
 • For Use With: Bore Size 12mm
 • To Fit Bore Size: 12 mm



3120309 314

RS PRO REED CYLINDER MAGNETIC SENSOR, 3 TO 130V AC/DC, NO

- ขนาดบรรจุภัณฑ์: 1 x EA
 • Compatible With: Pneumatic Actuator
 • Type: Reed
 • LED Indicator: Yes
 • Supply Voltage: 3 to 130 V ac/dc
 • Operation: NO
 • Minimum Operating Temperature: -20 °C
 • Maximum Operating Temperature: +70 °C



1761580 Pneumatic

RS PRO PNP-HALL CYLINDER MAGNETIC SENSOR, 10 TO 30V DC,

- ขนาดบรรจุภัณฑ์: 1 x EA
 • Compatible With: Pneumatic Actuator
 • Type: PNP-Hall
 • LED Indicator: Yes
 • Supply Voltage: 10 to 30 V dc
 • Operation: NO
 • Minimum Operating Temperature: -20 °C
 • Maximum Operating Temperature: +70 °C



1761618 Pneumatic

RS PRO 20MM G 3/4 15 BAR FILTER 6250NL/MIN MAX

- ขนาดบรรจุภัณฑ์: 1 x EA
 • Filtration Size: 20 µm
 • Port Connection: G 3/4
 • Maximum Flow Rate: 6250 NL/min
 • Maximum Operating Pressure: 15 bar
 • Maximum Operating Temperature: +50 °C
 • Port Connection Thread Standard: G
 • Minimum Operating Temperature: -10 °C
 • Port Connection Thread Size: 19.05 mm



1761722 20 µm

PP PLUG 4 MM

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Accessory Type: Blanking Plug
 - Tube Size: 4 mm
 - Material: Plastic
 - Overall Length: 28 mm
 - Outer Diameter: 4 mm



1442648 Blanking Plug

PP PLUG 6 MM

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Accessory Type: Blanking Plug
 - Tube Size: 6 mm
 - Material: Plastic
 - Overall Length: 33 mm
 - Outer Diameter: 6 mm



1442649 Blanking Plug

PP PLUG 8 MM

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Accessory Type: Blanking Plug
 - Tube Size: 8 mm
 - Material: Plastic
 - Overall Length: 36 mm
 - Outer Diameter: 8 mm



1442650 Blanking Plug

RS PRO PLASTIC BLANKING PLUG FOR 10MM

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Accessory Type: Blanking Plug
 - Tube Size: 10 mm
 - Material: Plastic
 - Overall Length: 42.5 mm
 - Outer Diameter: 10 mm



1442651 Blanking Plug

RS PRO PLASTIC BLANKING PLUG FOR 12MM

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Accessory Type: Blanking Plug
 - Tube Size: 12 mm
 - Material: Plastic
 - Overall Length: 43 mm
 - Outer Diameter: 12 mm



1442652 Blanking Plug

MALE PLUG WITH NBR ORING - BSPP 1/8

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Accessory Type: Plug Connector
 - Threaded Connection: G 1/8 Male
 - Material: NBR
 - Threaded Connection - Thread Size: 3.175 mm
 - Threaded Connection - Thread Standard: BSPP
 - Outer Diameter: 14 mm
 - Overall Length: 8.5 mm



1761048 Plug Connector

MALE PLUG WITH NBR ORING - BSPP 1/4

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Accessory Type: Plug Connector
 - Threaded Connection: G 1/4 Male
 - Material: NBR
 - Threaded Connection - Thread Size: 6.35 mm
 - Threaded Connection - Thread Standard: BSPP
 - Outer Diameter: 17 mm
 - Overall Length: 11 mm



1761049 Plug Connector

RS PRO G 3/8 MALE NBR PLUG FITTING

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Accessory Type: Plug Connector
 - Threaded Connection: G 3/8 Male
 - Material: NBR
 - Threaded Connection - Thread Size: 9.525 mm
 - Threaded Connection - Thread Standard: BSPP
 - Outer Diameter: 20 mm
 - Overall Length: 12.5 mm



1761050 Plug Connector

RS PRO G 1/2 MALE NBR PLUG FITTING

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Accessory Type: Plug Connector
 - Threaded Connection: G 1/2 Male
 - Material: NBR
 - Threaded Connection - Thread Size: 12.7 mm
 - Threaded Connection - Thread Standard: BSPP
 - Outer Diameter: 25 mm
 - Overall Length: 13.5 mm



1761051 Plug Connector

RS PRO 1/8 IN MALE NICKEL PLATED BRASS PLUG FITTING

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Accessory Type: Plug Connector
 - Threaded Connection: 1/8 in Male
 - Material: Nickel Plated Brass
 - Threaded Connection - Thread Size: 3.175 mm
 - Threaded Connection - Thread Standard: BSPP



1761052 Plug Connector

RS PRO 1/4 IN MALE NICKEL PLATED BRASS PLUG FITTING

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Accessory Type: Plug Connector
 - Threaded Connection: 1/4 in Male
 - Material: Nickel Plated Brass
 - Threaded Connection - Thread Size: 6.35 mm
 - Threaded Connection - Thread Standard: BSPP



1761053 Plug Connector

RS PRO 1/8 IN MALE NICKEL PLATED BRASS PLUG FITTING

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Accessory Type: Plug Connector
 - Threaded Connection: 1/8 in Male
 - Material: Nickel Plated Brass
 - Threaded Connection - Thread Size: 3.175 mm
 - Threaded Connection - Thread Standard: BSPP



1761054 Plug Connector

RS PRO NICKEL PLATED BRASS PLUG FITTING

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Accessory Type: Plug Connector
 - Material: Nickel Plated Brass
 - Threaded Connection - Thread Size: 12.7 mm
 - Threaded Connection - Thread Standard: BSPP



1761057 Plug Connector

RS PRO 1/2 IN MALE NICKEL PLATED BRASS PLUG FITTING FOR 10MM

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Accessory Type: Plug Connector
 - Manufacturer Series: 3020
 - Tube Size: 10 mm
 - Threaded Connection: 1/2 in Male
 - Material: Nickel Plated Brass
 - Threaded Connection - Thread Size: 1/2 in
 - Food Grade: Yes



2312536 Plug Connector

RS PRO STRAIGHT THREADED ADAPTOR, R 3/8 MALE TO PUSH IN 8

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Pneumatic Fitting Type: Straight Threaded Adaptor
 - Connection Style: Threaded-to-Tube
 - Connector A: R 3/8 Male
 - Connector B: Push In 8 mm
 - Body Material: Plastic
 - Minimum Operating Temperature: 0 °C
 - Maximum Operating Temperature: +60 °C
 - Maximum Operating Pressure: 9.9 kgf/cm², 990 kPa



1442604 Straight

RS PRO STRAIGHT THREADED ADAPTOR, R 3/8 MALE TO PUSH IN 10

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Pneumatic Fitting Type: Straight Threaded Adaptor
 - Connection Style: Threaded-to-Tube
 - Connector A: R 3/8 Male
 - Connector B: Push In 10 mm
 - Body Material: Plastic
 - Minimum Operating Temperature: 0 °C
 - Maximum Operating Temperature: +60 °C
 - Maximum Operating Pressure: 9.9 kgf/cm², 990 kPa



1442605 Straight

RS PRO ELBOW TUBE-TO-TUBE ADAPTOR, PUSH IN 12 MM TO PUSH IN

ขนาดบรรจุภัณฑ์: **10 x EA**

- Pneumatic Fitting Type: Elbow Tube-to-Tube Adaptor
- Connection Style: Tube-to-Tube
- Connector A: Push In 12 mm
- Connector B: Push In 12 mm
- Body Material: Plastic
- Minimum Operating Temperature: 0 °C
- Maximum Operating Pressure: 9.9 kgf/cm², 990 kPa
- Maximum Operating Temperature: +60 °C



1442625 Elbow Tube-

RS PRO TEE TUBE-TO-TUBE ADAPTOR PUSH IN 12 MM, PUSH IN 12 MM TO

ขนาดบรรจุภัณฑ์: **10 x EA**

- Pneumatic Fitting Type: Tee Tube-to-Tube Adaptor
- Connection Style: Tube-to-Tube
- Connector A: Push In 12 mm
- Connector B: Push In 12 mm
- Body Material: Plastic
- Minimum Operating Temperature: 0 °C
- Maximum Operating Pressure: 9.9 kgf/cm², 990 kPa
- Maximum Operating Temperature: +60 °C



1442626 Tee Tube-to-Tube

RS PRO Y TUBE-TO-TUBE ADAPTOR, PUSH IN 12 MM TO PUSH IN 12 MM,

ขนาดบรรจุภัณฑ์: **10 x EA**

- Pneumatic Fitting Type: Y Tube-to-Tube Adaptor
- Connection Style: Tube-to-Tube
- Connector A: Push In 12 mm
- Connector B: Push In 12 mm
- Connector C: Push In 12 mm
- Body Material: Plastic
- Minimum Operating Temperature: 0 °C
- Maximum Operating Pressure: 9.9 kgf/cm², 990 kPa



1442627 Y Tube-to-Tube

RS PRO STRAIGHT TUBE-TO-TUBE ADAPTOR, PUSH IN 4 MM TO PUSH IN

ขนาดบรรจุภัณฑ์: **10 x EA**

- Pneumatic Fitting Type: Straight Tube-to-Tube Adaptor
- Connection Style: Tube-to-Tube
- Connector A: Push In 4 mm
- Connector B: Push In 12 mm
- Body Material: Plastic
- Minimum Operating Temperature: 0 °C
- Maximum Operating Pressure: 9.9 kgf/cm², 990 kPa
- Maximum Operating Temperature: +60 °C



1442628 Straight Tube-to-

RS PRO STRAIGHT TUBE-TO-TUBE ADAPTOR, PUSH IN 6 MM TO PUSH IN

ขนาดบรรจุภัณฑ์: **10 x EA**

- Pneumatic Fitting Type: Straight Tube-to-Tube Adaptor
- Connection Style: Tube-to-Tube
- Connector A: Push In 6 mm
- Connector B: Push In 8 mm
- Body Material: Plastic
- Minimum Operating Temperature: 0 °C
- Maximum Operating Pressure: 9.9 kgf/cm², 990 kPa
- Maximum Operating Temperature: +60 °C



1442629 Straight Tube-to-

RS PRO STRAIGHT TUBE-TO-TUBE ADAPTOR, PUSH IN 8 MM TO PUSH IN

ขนาดบรรจุภัณฑ์: **10 x EA**

- Pneumatic Fitting Type: Straight Tube-to-Tube Adaptor
- Connection Style: Tube-to-Tube
- Connector A: Push In 8 mm
- Connector B: Push In 10 mm
- Body Material: Plastic
- Minimum Operating Temperature: 0 °C
- Maximum Operating Pressure: 9.9 kgf/cm², 990 kPa
- Maximum Operating Temperature: +60 °C



1442630 Straight Tube-to-

RS PRO STRAIGHT TUBE-TO-TUBE ADAPTOR, PUSH IN 10 MM TO PUSH IN

ขนาดบรรจุภัณฑ์: **10 x EA**

- Pneumatic Fitting Type: Straight Tube-to-Tube Adaptor
- Connection Style: Tube-to-Tube
- Connector A: Push In 10 mm
- Connector B: Push In 12 mm
- Body Material: Plastic
- Minimum Operating Temperature: 0 °C
- Maximum Operating Pressure: 9.9 kgf/cm², 990 kPa
- Maximum Operating Temperature: +60 °C



1442631 Straight Tube-to-

RS PRO BULKHEAD TUBE-TO-TUBE ADAPTOR, PUSH IN 12 MM TO PUSH IN

ขนาดบรรจุภัณฑ์: **10 x EA**

- Pneumatic Fitting Type: Bulkhead Tube-to-Tube Adaptor
- Connection Style: Tube-to-Tube
- Connector A: Push In 12 mm
- Connector B: Push In 12 mm
- Thread Material: Brass
- Finish: Nickel Plated
- Minimum Operating Temperature: 0 °C
- Maximum Operating Pressure: 9.9 kgf/cm², 990 kPa
- Maximum Operating Temperature: +60 °C



1442632 Bulkhead Tube-

RS PRO STRAIGHT THREADED ADAPTOR, M5 FEMALE TO PUSH IN 6

ขนาดบรรจุภัณฑ์: **10 x EA**

- Pneumatic Fitting Type: Straight Threaded Adaptor
- Connection Style: Threaded-to-Tube
- Connector A: M5 Female
- Connector B: Push In 6 mm
- Body Material: Plastic
- Minimum Operating Temperature: 0 °C
- Maximum Operating Pressure: +60 °C
- Maximum Operating Pressure: 9.9 kgf/cm², 990 kPa



1442635 Straight

RS PRO STRAIGHT THREADED ADAPTOR, R 1/8 FEMALE TO PUSH IN 6

ขนาดบรรจุภัณฑ์: **10 x EA**

- Pneumatic Fitting Type: Straight Threaded Adaptor
- Connection Style: Threaded-to-Tube
- Connector A: R 1/8 Female
- Connector B: Push In 6 mm
- Body Material: Plastic
- Minimum Operating Temperature: 0 °C
- Maximum Operating Pressure: +60 °C
- Maximum Operating Pressure: 9.9 kgf/cm², 990 kPa



1442636 Straight

RS PRO STRAIGHT THREADED ADAPTOR, R 3/8 TO PUSH IN 8 MM,

ขนาดบรรจุภัณฑ์: **10 x EA**

- Pneumatic Fitting Type: Straight Threaded Adaptor
- Connection Style: Threaded-to-Tube
- Connector A: R 3/8
- Connector B: Push In 8 mm
- Body Material: Plastic
- Minimum Operating Temperature: 0 °C
- Maximum Operating Pressure: +60 °C
- Maximum Operating Pressure: 9.9 kgf/cm², 990 kPa



1442637 Straight

RS PRO STRAIGHT THREADED ADAPTOR, R 3/8 TO PUSH IN 10 MM,

ขนาดบรรจุภัณฑ์: **10 x EA**

- Pneumatic Fitting Type: Straight Threaded Adaptor
- Connection Style: Threaded-to-Tube
- Connector A: R 3/8
- Connector B: Push In 10 mm
- Body Material: Plastic
- Minimum Operating Temperature: 0 °C
- Maximum Operating Pressure: +60 °C
- Maximum Operating Pressure: 9.9 kgf/cm², 990 kPa



1442638 Straight

RS PRO BANJO THREADED-TO-TUBE ADAPTOR, M5 MALE TO PUSH IN 4

ขนาดบรรจุภัณฑ์: **10 x EA**

- Pneumatic Fitting Type: Banjo Threaded-to-Tube Adaptor
- Connection Style: Threaded-to-Tube
- Connector A: M5 Male
- Connector B: Push In 4 mm
- Threaded Connection: M5 Male
- Finish: Nickel Plated
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: +60 °C



1442639 Banjo Threaded-

RS PRO BANJO THREADED-TO-TUBE ADAPTOR, M5 MALE TO PUSH IN 6

ขนาดบรรจุภัณฑ์: **10 x EA**

- Pneumatic Fitting Type: Banjo Threaded-to-Tube Adaptor
- Connection Style: Threaded-to-Tube
- Connector A: M5 Male
- Connector B: Push In 6 mm
- Threaded Connection: M5 Male
- Finish: Nickel Plated
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: +60 °C



1442641 Banjo Threaded-

RS PRO STRAIGHT TUBE-TO-TUBE ADAPTOR, PUSH IN 4 MM TO PUSH IN

ขนาดบรรจุภัณฑ์: **10 x EA**

- Pneumatic Fitting Type: Straight Tube-to-Tube Adaptor
- Connection Style: Tube-to-Tube
- Connector A: Push In 4 mm
- Connector B: Push In 6 mm
- Body Material: Plastic
- Minimum Operating Temperature: 0 °C
- Maximum Operating Pressure: 9.9 kgf/cm², 990 kPa
- Maximum Operating Temperature: +60 °C



1442643 Straight Tube-to-

RS PRO STRAIGHT TUBE-TO-TUBE ADAPTOR, PUSH IN 4 MM TO PUSH IN

ขนาดบรรจุภัณฑ์: **10 x EA**

- Pneumatic Fitting Type: Straight Tube-to-Tube Adaptor
- Connection Style: Tube-to-Tube
- Connector A: Push In 4 mm
- Connector B: Push In 8 mm
- Body Material: Plastic
- Minimum Operating Temperature: 0 °C
- Maximum Operating Pressure: 9.9 kgf/cm², 990 kPa
- Maximum Operating Temperature: +60 °C



1442644 Straight Tube-to-

RS PRO PUSH-IN FITTING, PUSH IN 10 MM TO PUSH IN 8 MM, TUBE-TO-TUBE

ขนาดบรรจุภัณฑ์: 10 x EA

- Pneumatic Fitting Type: Push-in Fitting
- Connection Style: Tube-to-Tube
- Connector A: Push In 10 mm
- Connector B: Push In 8 mm
- Connector C: Push In 8 mm
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +80 °C
- Maximum Operating Pressure: 20 bar



1761834 Push-in Fitting

RS PRO BANJO BOLT, THREADED-TO-TUBE CONNECTION STYLE

ขนาดบรรจุภัณฑ์: 10 x EA

- Pneumatic Fitting Type: Banjo Bolt
- Connection Style: Threaded-to-Tube
- Body Material: Brass
- Minimum Operating Temperature: -20 °C
- Finish: Nickel Plated
- Maximum Operating Temperature: +80 °C
- Maximum Operating Pressure: 20 bar



1761842 Banjo Bolt

RS PRO BANJO BOLT, THREADED-TO-TUBE CONNECTION STYLE

ขนาดบรรจุภัณฑ์: 10 x EA

- Pneumatic Fitting Type: Banjo Bolt
- Connection Style: Threaded-to-Tube
- Body Material: Brass
- Minimum Operating Temperature: -20 °C
- Finish: Nickel Plated
- Maximum Operating Temperature: +80 °C
- Maximum Operating Pressure: 20 bar



1761844 Banjo Bolt

RS PRO BANJO BOLT, THREADED-TO-TUBE CONNECTION STYLE

ขนาดบรรจุภัณฑ์: 10 x EA

- Pneumatic Fitting Type: Banjo Bolt
- Connection Style: Threaded-to-Tube
- Body Material: Brass
- Minimum Operating Temperature: -20 °C
- Finish: Nickel Plated
- Maximum Operating Temperature: +80 °C
- Maximum Operating Pressure: 20 bar



1761845 Banjo Bolt

RS PRO BANJO BOLT, M5 MALE, THREADED-TO-TUBE CONNECTION

ขนาดบรรจุภัณฑ์: 10 x EA

- Pneumatic Fitting Type: Banjo Bolt
- Connection Style: Threaded-to-Tube
- Connector A: M5 Male
- Threaded Connection: M5
- Body Material: Brass
- Finish: Nickel Plated
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +80 °C



1761846 Banjo Bolt

RS PRO BANJO BOLT, M12 MALE, THREADED-TO-TUBE CONNECTION

ขนาดบรรจุภัณฑ์: 10 x EA

- Pneumatic Fitting Type: Banjo Bolt
- Connection Style: Threaded-to-Tube
- Connector A: M12 Male
- Threaded Connection: M12 x 1.5
- Body Material: Brass
- Finish: Nickel Plated
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +80 °C



1761848 Banjo Bolt

RS PRO BANJO TUBE BODIES, M5 FEMALE TO PUSH IN 4 MM,

ขนาดบรรจุภัณฑ์: 10 x EA

- Pneumatic Fitting Type: Banjo Tube Bodies
- Connection Style: Threaded-to-Tube
- Connector A: M5 Female
- Connector B: Push In 4 mm
- Threaded Connection: M5
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +80 °C
- Maximum Operating Pressure: 20 bar



1761849 Banjo Tube

RS PRO BANJO TUBE BODIES, M6 FEMALE TO PUSH IN 4 MM,

ขนาดบรรจุภัณฑ์: 10 x EA

- Pneumatic Fitting Type: Banjo Tube Bodies
- Connection Style: Threaded-to-Tube
- Connector A: M6 Female
- Connector B: Push In 4 mm
- Threaded Connection: M6
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +80 °C
- Maximum Operating Pressure: 20 bar



1761850 Banjo Tube

RS PRO BANJO TUBE BODIES TO PUSH IN 4 MM, THREADED-TO-TUBE

ขนาดบรรจุภัณฑ์: 10 x EA

- Pneumatic Fitting Type: Banjo Tube Bodies
- Connection Style: Threaded-to-Tube
- Connector B: Push In 4 mm
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +80 °C
- Maximum Operating Pressure: 20 bar



1761851 Banjo Tube

RS PRO BANJO TUBE BODIES TO PUSH IN 6 MM, THREADED-TO-TUBE

ขนาดบรรจุภัณฑ์: 10 x EA

- Pneumatic Fitting Type: Banjo Tube Bodies
- Connection Style: Threaded-to-Tube
- Connector B: Push In 6 mm
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +80 °C
- Maximum Operating Pressure: 20 bar



1761858 Banjo Tube

RS PRO BANJO TUBE BODIES TO PUSH IN 8 MM, THREADED-TO-TUBE

ขนาดบรรจุภัณฑ์: 10 x EA

- Pneumatic Fitting Type: Banjo Tube Bodies
- Connection Style: Threaded-to-Tube
- Connector B: Push In 8 mm
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +80 °C
- Maximum Operating Pressure: 20 bar



1761860 Banjo Tube

RS PRO PUSH-IN FITTING

ขนาดบรรจุภัณฑ์: 10 x EA

- Pneumatic Fitting Type: Push-in Fitting



1761866 Push-in Fitting

RS PRO PUSH-IN FITTING, PUSH IN 10 MM TO PUSH IN 8 MM, TUBE-TO-TUBE

ขนาดบรรจุภัณฑ์: 10 x EA

- Pneumatic Fitting Type: Push-in Fitting
- Connection Style: Tube-to-Tube
- Connector A: Push In 10 mm
- Connector B: Push In 8 mm
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +80 °C
- Maximum Operating Pressure: 20 bar



1761868 Push-in Fitting

RS PRO PUSH-IN FITTING, PUSH IN 12 MM TO PUSH IN 8 MM, TUBE-TO-TUBE

ขนาดบรรจุภัณฑ์: 10 x EA

- Pneumatic Fitting Type: Push-in Fitting
- Connection Style: Tube-to-Tube
- Connector A: Push In 12 mm
- Connector B: Push In 8 mm
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +80 °C
- Maximum Operating Pressure: 20 bar



1761869 Push-in Fitting

RS PRO PUSH-IN FITTING, PUSH IN 10 MM TO PUSH IN 6 MM, TUBE-TO-TUBE

ขนาดบรรจุภัณฑ์: 10 x EA

- Pneumatic Fitting Type: Push-in Fitting
- Connection Style: Tube-to-Tube
- Connector A: Push In 10 mm
- Connector B: Push In 6 mm
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +80 °C
- Maximum Operating Pressure: 20 bar



1761871 Push-in Fitting

RS PRO PUSH-IN FITTING, PUSH IN 14 MM TO PUSH IN 12 MM, TUBE-TO-TUBE

ขนาดบรรจุภัณฑ์: 10 x EA

- Pneumatic Fitting Type: Push-in Fitting
- Connection Style: Tube-to-Tube
- Connector A: Push In 14 mm
- Connector B: Push In 12 mm
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +80 °C
- Maximum Operating Pressure: 20 bar



1761872 Push-in Fitting

RS PRO PUSH-IN FITTING, G 1/8 MALE TO PUSH IN 8 MM, THREADED-TO-

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Pneumatic Fitting Type: Push-in Fitting
 - Connection Style: Threaded-to-Tube
 - Connector A: G 1/8 Male
 - Connector B: Push In 8 mm
 - Body Material: Nickel Plated Brass
 - Minimum Operating Temperature: -20 °C
 - Maximum Operating Pressure: 20 bar
 - Maximum Operating Temperature: +80 °C



1977766 Push-in Fitting

RS PRO PUSH-IN FITTING, G 3/8 MALE TO PUSH IN 8 MM, THREADED-TO-

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Pneumatic Fitting Type: Push-in Fitting
 - Connection Style: Threaded-to-Tube
 - Connector A: G 3/8 Male
 - Connector B: Push In 8 mm
 - Body Material: Nickel Plated Brass
 - Minimum Operating Temperature: -20 °C
 - Maximum Operating Pressure: 20 bar
 - Maximum Operating Temperature: +80 °C



1977768 Push-in Fitting

RS PRO 57000 SERIES PUSH-IN FITTING, PUSH IN 8 MM TO PUSH IN 8

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Manufacturer Series: 57000
 - Pneumatic Fitting Type: Push-in Fitting
 - Connection Style: Tube-to-Tube
 - Connector A: Push In 8 mm
 - Connector B: Push In 8 mm
 - Body Material: Nickel Plated Brass
 - Minimum Operating Temperature: -20 °C
 - Maximum Operating Pressure: 20 bar



1977774 57000

RS PRO 57000 SERIES PUSH-IN FITTING, PUSH IN 14 MM TO PUSH IN

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Manufacturer Series: 57000
 - Pneumatic Fitting Type: Push-in Fitting
 - Connection Style: Tube-to-Tube
 - Connector A: Push In 14 mm
 - Connector B: Push In 14 mm
 - Body Material: Nickel Plated Brass
 - Minimum Operating Temperature: -20 °C
 - Maximum Operating Pressure: 20 bar



1977777 57000

RS PRO PUSH-IN FITTING, PUSH IN 6 MM TO PUSH IN 6 MM, THREADED-TO-

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Pneumatic Fitting Type: Push-in Fitting
 - Connection Style: Threaded-to-Tube
 - Connector A: Push In 6 mm
 - Connector B: Push In 6 mm
 - Body Material: Nickel Plated Brass
 - Minimum Operating Temperature: -20 °C
 - Maximum Operating Pressure: 20 bar
 - Maximum Operating Temperature: +80 °C



1977797 Push-in Fitting

RS PRO PUSH-IN FITTING PUSH IN 6 MM, PUSH IN 6 MM TO PUSH IN 6 MM,

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Pneumatic Fitting Type: Push-in Fitting
 - Connection Style: Tube-to-Tube
 - Connector B: Push In 6 mm
 - Connector A: Push In 6 mm
 - Body Material: Brass
 - Minimum Operating Temperature: -20 °C
 - Maximum Operating Pressure: 20 bar
 - Maximum Operating Temperature: +80 °C



1977847 Push-in Fitting

RS PRO 57550 SERIES PUSH-IN FITTING, M5 MALE TO PUSH IN 4 MM,

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Manufacturer Series: 57550
 - Pneumatic Fitting Type: Push-in Fitting
 - Connection Style: Threaded-to-Tube
 - Connector A: M5 Male
 - Connector B: Push In 4 mm
 - Threaded Connection: M5
 - Body Material: Nickel Plated Brass
 - Minimum Operating Temperature: -20 °C



1977857 57550

RS PRO PUSH-IN FITTING, PUSH IN 10 MM TO PUSH IN 4 MM, TUBE-TO-TUBE

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Pneumatic Fitting Type: Push-in Fitting
 - Connection Style: Tube-to-Tube
 - Connector A: Push In 10 mm
 - Connector B: Push In 4 mm
 - Body Material: Nickel Plated Brass
 - Minimum Operating Temperature: -20 °C
 - Maximum Operating Pressure: 20 bar
 - Maximum Operating Temperature: +80 °C



1977885 Push-in Fitting

RS PRO PUSH-IN FITTING, PUSH IN 12 MM TO PUSH IN 8 MM, TUBE-TO-TUBE

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Pneumatic Fitting Type: Push-in Fitting
 - Connection Style: Tube-to-Tube
 - Connector A: Push In 12 mm
 - Connector B: Push In 8 mm
 - Body Material: Nickel Plated Brass
 - Minimum Operating Temperature: -20 °C
 - Maximum Operating Pressure: 20 bar
 - Maximum Operating Temperature: +80 °C



1977887 Push-in Fitting

RS PRO 162 SERIES STRAIGHT FITTING, BSP 3/8 BSP FEMALE TO 3/8

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Manufacturer Series: 162
 - Pneumatic Fitting Type: Straight Fitting
 - Connection Style: Threaded-to-Tube
 - Connector A: BSP 3/8 BSP Female
 - Connector B: 3/8 in Female
 - Threaded Connection: 3/8 in Female



2312499 162

RS PRO 3060 SERIES BULKHEAD THREADED ADAPTOR, BSP 1/2 BSP

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Manufacturer Series: 3060
 - Pneumatic Fitting Type: Bulkhead Threaded Adaptor
 - Connection Style: Threaded
 - Connector A: BSP 1/2 BSP Female
 - Connector B: M28
 - Threaded Connection: 1/2 in Female



2312548 3060

RS PRO 55705 SERIES STRAIGHT FITTING, PUSH IN 4 MM TO PUSH IN 6

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Manufacturer Series: 55705
 - Pneumatic Fitting Type: Straight Fitting
 - Connection Style: Tube-to-Tube
 - Connector A: Push In 4 mm
 - Connector B: Push In 6 mm
 - Inlet Port: Push In 4 mm



2312677 55705

RS PRO 55705 SERIES STRAIGHT FITTING, PUSH IN 6 MM TO PUSH IN 8

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Manufacturer Series: 55705
 - Pneumatic Fitting Type: Straight Fitting
 - Connection Style: Tube-to-Tube
 - Connector A: Push In 6 mm
 - Connector B: Push In 8 mm
 - Inlet Port: Push In 6 mm



2312678 55705

RS PRO 69460 SERIES STRAIGHT FITTING, PUSH IN 6 MM TO PUSH IN 6

- ขนาดบรรจุภัณฑ์: **2 x EA**
- Manufacturer Series: 69460
 - Pneumatic Fitting Type: Straight Fitting
 - Connection Style: Tube-to-Tube
 - Connector A: Push In 6 mm
 - Connector B: Push In 6 mm
 - Inlet Port: Push In 6 mm



2312731 69460

RS PRO 69480 SERIES STRAIGHT FITTING, BSP 1/4 BSP MALE TO PUSH

- ขนาดบรรจุภัณฑ์: **2 x EA**
- Pneumatic Fitting Type: Straight Fitting
 - Manufacturer Series: 69480
 - Connection Style: Threaded-to-Tube
 - Connector A: BSP 1/4 BSP Male
 - Connector B: Push In 6 mm
 - Threaded Connection: 1/4 BSP Male
 - Inlet Port: 1/4 in Male



2312734 Straight Fitting

RS PRO NSF SERIES STRAIGHT TUBE-TO-TUBE ADAPTOR, TUBE-TO-TUBE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Manufacturer Series: NSF
 - Pneumatic Fitting Type: Straight Tube-to-Tube Adaptor
 - Connection Style: Tube-to-Tube
 - Inlet Port: Push In 8 mm
 - Number of Inlet Ports: 1
 - Number of Outlet Ports: 1
 - Outlet Port: Push In 8 mm
 - Maximum Operating Pressure: 10 bar



2351196 NSF

RS PRO PC SERIES THREADED-TO-TUBE, THREADED-TO-TUBE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Manufacturer Series: PC
 - Pneumatic Fitting Type: Threaded-to-Tube
 - Connection Style: Threaded-to-Tube
 - Threaded Connection: BSPT 1/2 in Male
 - Number of Inlet Ports: 1
 - Outlet Port: Push In 10 mm
 - Number of Outlet Ports: 1
 - Maximum Operating Pressure: 10.2 bar



2351202 PC

RS PRO PGJ SERIES PUSH-IN FITTING, TUBE-TO-TUBE CONNECTION STYLE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Manufacturer Series: PGJ
 - Pneumatic Fitting Type: Push-in Fitting
 - Connection Style: Tube-to-Tube
 - Inlet Port: Push In 8 mm
 - Number of Inlet Ports: 1
 - Number of Outlet Ports: 1
 - Outlet Port: Push In 6 mm
 - Maximum Operating Pressure: 10.2 bar



2351207 PGJ

RS PRO PMF-G SERIES BULKHEAD THREADED-TO-TUBE ADAPTOR,

- ขนาดบรรจุภัณฑ์: 1 x EA
- Manufacturer Series: PMF-G
 - Pneumatic Fitting Type: Bulkhead Threaded-to-Tube Adaptor
 - Connection Style: Threaded-to-Tube
 - Threaded Connection: BSPP 1/8 in Female
 - Number of Inlet Ports: 1
 - Outlet Port: Push In 6 mm
 - Number of Outlet Ports: 1
 - Maximum Operating Pressure: 10.2 bar



2351211 PMF-G

RS PRO PUL SERIES ELBOW TUBE-TOTUBE ADAPTOR, TUBE-TO-TUBE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Manufacturer Series: PUL
 - Pneumatic Fitting Type: Elbow Tube-to-Tube Adaptor
 - Connection Style: Tube-to-Tube
 - Inlet Port: Push In 10 mm
 - Number of Inlet Ports: 1
 - Number of Outlet Ports: 1
 - Outlet Port: Push In 10 mm
 - Maximum Operating Pressure: 10.2 bar



2351233 PUL

RS PRO STRAIGHT THREADED ADAPTOR, G 1/8 MALE TO PUSH IN 4

- ขนาดบรรจุภัณฑ์: 5 x EA
- Pneumatic Fitting Type: Straight Threaded Adaptor
 - Connection Style: Threaded-to-Tube
 - Connector A: G 1/8 Male
 - Connector B: Push In 4 mm
 - Threaded Connection: G 1/8 Male
 - Minimum Operating Temperature: -18 °C
 - Maximum Operating Pressure: 15 bar
 - Maximum Operating Temperature: +70 °C



2993796 Straight

RS PRO STRAIGHT THREADED ADAPTOR, G 1/8 MALE TO PUSH IN 5

- ขนาดบรรจุภัณฑ์: 5 x EA
- Pneumatic Fitting Type: Straight Threaded Adaptor
 - Connection Style: Threaded-to-Tube
 - Connector A: G 1/8 Male
 - Connector B: Push In 5 mm
 - Threaded Connection: G 1/8 Male
 - Minimum Operating Temperature: -18 °C
 - Maximum Operating Pressure: 15 bar
 - Maximum Operating Temperature: +70 °C



2993803 Straight

RS PRO STRAIGHT THREADED ADAPTOR, G 1/8 MALE TO PUSH IN 6

- ขนาดบรรจุภัณฑ์: 5 x EA
- Pneumatic Fitting Type: Straight Threaded Adaptor
 - Connection Style: Threaded-to-Tube
 - Connector A: G 1/8 Male
 - Connector B: Push In 6 mm
 - Minimum Operating Temperature: -18 °C
 - Maximum Operating Pressure: 15 bar
 - Maximum Operating Temperature: +70 °C
 - Mounting Type: Inline



2993819 Straight

RS PRO STRAIGHT THREADED ADAPTOR, G 3/8 MALE TO PUSH IN 6

- ขนาดบรรจุภัณฑ์: 5 x EA
- Pneumatic Fitting Type: Straight Threaded Adaptor
 - Connection Style: Threaded-to-Tube
 - Connector A: G 3/8 Male
 - Connector B: Push In 6 mm
 - Minimum Operating Temperature: -18 °C
 - Maximum Operating Pressure: 15 bar
 - Maximum Operating Temperature: +70 °C
 - Mounting Type: Inline



2993825 Straight

RS PRO STRAIGHT THREADED ADAPTOR, G 1/8 MALE TO PUSH IN 8

- ขนาดบรรจุภัณฑ์: 5 x EA
- Pneumatic Fitting Type: Straight Threaded Adaptor
 - Connection Style: Threaded-to-Tube
 - Connector A: G 1/8 Male
 - Connector B: Push In 8 mm
 - Minimum Operating Temperature: -18 °C
 - Maximum Operating Pressure: 15 bar
 - Maximum Operating Temperature: +70 °C
 - Mounting Type: Inline



2993831 Straight

RS PRO 1130 SERIES ELBOW TUBE-TOTUBE ADAPTOR, PUSH IN 6 MM TO

- ขนาดบรรจุภัณฑ์: 5 x EA
- Manufacturer Series: 1130
 - Pneumatic Fitting Type: Elbow Tube-to-Tube Adaptor
 - Connection Style: Tube-to-Tube
 - Connector A: Push In 6 mm
 - Connector B: Push In 6 mm
 - Body Material: Stainless Steel
 - Minimum Operating Temperature: -18 °C
 - Maximum Operating Pressure: 15 bar



2993869 1130

RS PRO 1130 SERIES ELBOW TUBE-TOTUBE ADAPTOR, PUSH IN 8 MM TO

- ขนาดบรรจุภัณฑ์: 5 x EA
- Manufacturer Series: 1130
 - Pneumatic Fitting Type: Elbow Tube-to-Tube Adaptor
 - Connection Style: Tube-to-Tube
 - Connector A: Push In 8 mm
 - Connector B: Push In 8 mm
 - Body Material: Stainless Steel
 - Minimum Operating Temperature: -18 °C
 - Maximum Operating Pressure: 15 bar



2993875 1130

RS PRO STRAIGHT THREADED ADAPTOR, R 1/8 MALE TO PUSH IN 6

- ขนาดบรรจุภัณฑ์: 5 x EA
- Pneumatic Fitting Type: Straight Threaded Adaptor
 - Connection Style: Threaded-to-Tube
 - Connector A: R 1/8 Male
 - Connector B: Push In 6 mm
 - Threaded Connection: R 1/8 Male
 - Minimum Operating Temperature: -18 °C
 - Maximum Operating Pressure: 15 bar
 - Maximum Operating Temperature: +70 °C



2993932 Straight

RS PRO STRAIGHT THREADED ADAPTOR, R 1/8 MALE TO PUSH IN 5

- ขนาดบรรจุภัณฑ์: 5 x EA
- Pneumatic Fitting Type: Straight Threaded Adaptor
 - Connection Style: Threaded-to-Tube
 - Connector A: R 1/8 Male
 - Connector B: Push In 5 mm
 - Threaded Connection: R 1/8 Male
 - Minimum Operating Temperature: -18 °C
 - Maximum Operating Pressure: 15 bar
 - Maximum Operating Temperature: +70 °C



2993948 Straight

RS PRO STRAIGHT THREADED ADAPTOR, R 1/8 MALE TO PUSH IN 4

- ขนาดบรรจุภัณฑ์: 5 x EA
- Pneumatic Fitting Type: Straight Threaded Adaptor
 - Connection Style: Threaded-to-Tube
 - Connector A: R 1/8 Male
 - Connector B: Push In 4 mm
 - Threaded Connection: R 1/8 Male
 - Minimum Operating Temperature: -18 °C
 - Maximum Operating Pressure: 15 bar
 - Maximum Operating Temperature: +70 °C



2993960 Straight

RS PRO STRAIGHT THREADED ADAPTOR, G 3/8 MALE TO PUSH IN 8

- ขนาดบรรจุภัณฑ์: 5 x EA
- Pneumatic Fitting Type: Straight Threaded Adaptor
 - Connection Style: Threaded-to-Tube
 - Connector A: G 3/8 Male
 - Connector B: Push In 8 mm
 - Threaded Connection: G 3/8 Male
 - Minimum Operating Temperature: -18 °C
 - Maximum Operating Pressure: 15 bar
 - Maximum Operating Temperature: +70 °C



2993976 Straight

RS PRO STRAIGHT THREADED ADAPTOR, G 1/4 MALE TO PUSH IN 8

- ขนาดบรรจุภัณฑ์: 5 x EA
- Pneumatic Fitting Type: Straight Threaded Adaptor
 - Connection Style: Threaded-to-Tube
 - Connector A: G 1/4 Male
 - Connector B: Push In 8 mm
 - Threaded Connection: G 1/4 Male
 - Minimum Operating Temperature: -18 °C
 - Maximum Operating Pressure: 15 bar
 - Maximum Operating Temperature: +70 °C



2993982 Straight

RS PRO STRAIGHT THREADED ADAPTOR, G 1/4 MALE TO PUSH IN 6

- ขนาดบรรจุภัณฑ์: 5 x EA
- Pneumatic Fitting Type: Straight Threaded Adaptor
 - Connection Style: Threaded-to-Tube
 - Connector A: G 1/4 Male
 - Connector B: Push In 6 mm
 - Threaded Connection: G 1/4 Male
 - Minimum Operating Temperature: -18 °C
 - Maximum Operating Pressure: 15 bar
 - Maximum Operating Temperature: +70 °C



2993998 Straight

RS PRO STRAIGHT THREADED ADAPTOR, R 1/4 MALE TO PUSH IN 8

- ขนาดบรรจุภัณฑ์: 5 x EA
- Pneumatic Fitting Type: Straight Threaded Adaptor
 - Connection Style: Threaded-to-Tube
 - Connector A: R 1/4 Male
 - Connector B: Push In 8 mm
 - Minimum Operating Temperature: -18 °C
 - Maximum Operating Pressure: 15 bar
 - Maximum Operating Temperature: +70 °C
 - Mounting Type: Inline



2994014 Straight

RS PRO STRAIGHT THREADED ADAPTOR, R 1/8 MALE TO PUSH IN 8

- ขนาดบรรจุภัณฑ์: 5 x EA
- Pneumatic Fitting Type: Straight Threaded Adaptor
 - Connection Style: Threaded-to-Tube
 - Connector A: R 1/8 Male
 - Connector B: Push In 8 mm
 - Minimum Operating Temperature: -18 °C
 - Maximum Operating Pressure: 15 bar
 - Maximum Operating Temperature: +70 °C
 - Mounting Type: Inline



2994036 Straight

RS PRO STRAIGHT THREADED ADAPTOR, R 3/8 MALE TO PUSH IN 6

- ขนาดบรรจุภัณฑ์: 5 x EA
- Pneumatic Fitting Type: Straight Threaded Adaptor
 - Connection Style: Threaded-to-Tube
 - Connector A: R 3/8 Male
 - Connector B: Push In 6 mm
 - Minimum Operating Temperature: -18 °C
 - Maximum Operating Pressure: 15 bar
 - Maximum Operating Temperature: +70 °C
 - Mounting Type: Inline



2994042 Straight

RS PRO STRAIGHT THREADED ADAPTOR, R 1/4 MALE TO PUSH IN 6

- ขนาดบรรจุภัณฑ์: 5 x EA
- Manufacturer Series: 1100
 - Pneumatic Fitting Type: Straight Threaded Adaptor
 - Connection Style: Threaded-to-Tube
 - Connector A: R 1/4 Male
 - Connector B: Push In 6 mm
 - Threaded Connection: R 1/4 Male
 - Minimum Operating Temperature: -18 °C
 - Maximum Operating Pressure: 15 bar
 - Maximum Operating Temperature: +70 °C



2994058 Straight

RS PRO ELBOW THREADED ADAPTOR, R 1/4 MALE TO PUSH IN 8 MM,

- ขนาดบรรจุภัณฑ์: 5 x EA
- Pneumatic Fitting Type: Elbow Threaded Adaptor
 - Connection Style: Threaded-to-Tube
 - Connector A: R 1/4 Male
 - Connector B: Push In 8 mm
 - Threaded Connection: R 1/4 Male
 - Minimum Operating Temperature: -18 °C
 - Maximum Operating Pressure: 15 bar
 - Maximum Operating Temperature: +70 °C



2994070 Elbow Threaded

RS PRO 1100 SERIES ELBOW THREADED ADAPTOR, R 1/8 MALE TO

- ขนาดบรรจุภัณฑ์: 5 x EA
- Manufacturer Series: 1100
 - Pneumatic Fitting Type: Elbow Threaded Adaptor
 - Connection Style: Threaded-to-Tube
 - Connector A: R 1/8 Male
 - Connector B: Push In 8 mm
 - Threaded Connection: R 1/8 Male
 - Minimum Operating Temperature: -18 °C
 - Maximum Operating Pressure: 15 bar
 - Maximum Operating Temperature: +70 °C



2994086 1100

RS PRO 1100 SERIES ELBOW THREADED ADAPTOR, R 1/4 MALE TO

- ขนาดบรรจุภัณฑ์: 5 x EA
- Manufacturer Series: 1100
 - Pneumatic Fitting Type: Elbow Threaded Adaptor
 - Connection Style: Threaded-to-Tube
 - Connector A: R 1/4 Male
 - Connector B: Push In 6 mm
 - Threaded Connection: R 1/4 Male
 - Minimum Operating Temperature: -18 °C
 - Maximum Operating Pressure: 15 bar
 - Maximum Operating Temperature: +70 °C



2994109 1100

RS PRO 1100 SERIES ELBOW THREADED ADAPTOR, R 1/8 MALE TO

- ขนาดบรรจุภัณฑ์: 5 x EA
- Manufacturer Series: 1100
 - Pneumatic Fitting Type: Elbow Threaded Adaptor
 - Connection Style: Threaded-to-Tube
 - Connector A: R 1/8 Male
 - Connector B: Push In 6 mm
 - Threaded Connection: R 1/8 Male
 - Minimum Operating Temperature: -18 °C
 - Maximum Operating Pressure: 15 bar
 - Maximum Operating Temperature: +70 °C



2994115 1100

RS PRO ELBOW THREADED ADAPTOR, R 1/8 MALE TO PUSH IN 4 MM,

- ขนาดบรรจุภัณฑ์: 5 x EA
- Pneumatic Fitting Type: Elbow Threaded Adaptor
 - Connection Style: Threaded-to-Tube
 - Connector A: R 1/8 Male
 - Connector B: Push In 4 mm
 - Threaded Connection: R 1/8 Male
 - Minimum Operating Temperature: -18 °C
 - Maximum Operating Pressure: 15 bar
 - Maximum Operating Temperature: +70 °C



2994137 Elbow Threaded

RS PRO ELBOW THREADED ADAPTOR, G 1/4 MALE TO PUSH IN 8 MM,

- ขนาดบรรจุภัณฑ์: 5 x EA
- Pneumatic Fitting Type: Elbow Threaded Adaptor
 - Connection Style: Threaded-to-Tube
 - Connector A: G 1/4 Male
 - Connector B: Push In 8 mm
 - Threaded Connection: G 1/4 Male
 - Minimum Operating Temperature: -18 °C
 - Maximum Operating Pressure: 15 bar
 - Maximum Operating Temperature: +70 °C



2994143 Elbow Threaded

RS PRO ELBOW THREADED ADAPTOR, G 1/4 MALE TO PUSH IN 6 MM,

- ขนาดบรรจุภัณฑ์: 5 x EA
- Pneumatic Fitting Type: Elbow Threaded Adaptor
 - Connection Style: Threaded-to-Tube
 - Connector A: G 1/4 Male
 - Connector B: Push In 6 mm
 - Threaded Connection: G 1/4 Male
 - Minimum Operating Temperature: -18 °C
 - Maximum Operating Pressure: 15 bar
 - Maximum Operating Temperature: +70 °C



2994165 Elbow Threaded

RS PRO ELBOW THREADED ADAPTOR, G 1/8 MALE TO PUSH IN 6 MM,

- ขนาดบรรจุภัณฑ์: 5 x EA
- Pneumatic Fitting Type: Elbow Threaded Adaptor
 - Connection Style: Threaded-to-Tube
 - Connector A: G 1/8 Male
 - Connector B: Push In 6 mm
 - Threaded Connection: G 1/8 Male
 - Minimum Operating Temperature: -18 °C
 - Maximum Operating Pressure: 15 bar
 - Maximum Operating Temperature: +70 °C



2994171 Elbow Threaded

RS PRO 1200 SERIES TEE THREADED ADAPTOR, PUSH IN 8 MM TO PUSH IN

- ขนาดบรรจุภัณฑ์: 5 x EA
- Pneumatic Fitting Type: Tee Threaded Adaptor
 - Manufacturer Series: 1200
 - Connection Style: Threaded-to-Tube
 - Connector A: Push In 8 mm
 - Connector B: Push In 8 mm
 - Threaded Connection: R 1/4 Male
 - Minimum Operating Temperature: -18 °C
 - Maximum Operating Temperature: +70 °C



2994250 Tee Threaded

RS PRO 19 SERIES Y THREADED ADAPTOR PUSH IN 6 MM, R 1/4 MALE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Manufacturer Series: 19
 - Pneumatic Fitting Type: Y Threaded Adaptor
 - Connection Style: Threaded-to-Tube
 - Connector B: R 1/4 Male
 - Connector A: R 1/4 Male
 - Connector C: Hose Barb
 - Threaded Connection: R 1/4 Male
 - Body Material: Brass



6671712 19

RS PRO STRAIGHT THREADED ADAPTOR, M5 TO PUSH IN 4 MM,

- ขนาดบรรจุภัณฑ์: 10 x EA
- Pneumatic Fitting Type: Straight Threaded Adaptor
 - Connection Style: Threaded-to-Tube
 - Connector A: M5
 - Connector B: Push In 4 mm
 - Body Material: Nickel Plated Brass
 - Minimum Operating Temperature: 0 °C
 - Maximum Operating Temperature: +60 °C
 - Maximum Operating Pressure: 10 bar



9160697 Straight

RS PRO CROSS TUBE-TO-TUBE ADAPTOR, PUSH IN 8 MM TO PUSH IN

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Pneumatic Fitting Type: Cross Tube-to-Tube Adaptor
 - Connection Style: Tube-to-Tube
 - Connector A: Push In 8 mm
 - Connector B: Push In 8 mm
 - Connector C: Push In 8 mm
 - Connector D: Push In 8 mm
 - Body Material: Polyoxymethylene
 - Finish: Nickel Plated



9160937 Cross Tube-to-

RS PRO THREADED FLOW REGULATOR, 1/4 IN FEMALE INLET

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Type: Flow Controller
 - Inlet Port Type: Threaded
 - Threaded Inlet Port: 1/4 in Female
 - Outlet Port Type: Threaded
 - Threaded Outlet Port: 1/4 in Male
 - Threaded Outlet Thread Gender: Male
 - Threaded Inlet Thread Gender: Female
 - Body Material: Steel



1370946 Flow Controller

RS PRO THREADED SPEED CONTROLLER, M5 INLET PORT X 4MM

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Type: Flow Controller
 - Inlet Port Type: Threaded
 - Threaded Inlet Port: M5
 - Tube Outlet Port: 4 mm
 - Minimum Outlet Pressure: 0 kgf/cm², 0 kPa
 - Maximum Outlet Pressure: 9.9 kgf/cm², 990 kPa
 - Threaded Inlet Thread Gender: Male
 - Threaded Inlet Thread Standard: Metric



1442657 Flow Controller

RS PRO THREADED SPEED CONTROLLER, M6 INLET PORT X 6MM

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Type: Flow Controller
 - Inlet Port Type: Threaded
 - Threaded Inlet Port: M6
 - Tube Outlet Port: 6 mm
 - Minimum Outlet Pressure: 0 kgf/cm², 0 kPa
 - Maximum Outlet Pressure: 9.9 kgf/cm², 990 kPa
 - Threaded Inlet Thread Gender: Male
 - Threaded Inlet Thread Standard: Metric



1442658 Flow Controller

RS PRO THREADED SPEED CONTROLLER X 6MM TUBE OUTLET

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Type: Flow Controller
 - Inlet Port Type: Threaded
 - Tube Outlet Port: 6 mm
 - Minimum Outlet Pressure: 0 kgf/cm², 0 kPa
 - Maximum Outlet Pressure: 9.9 kgf/cm², 990 kPa
 - Threaded Inlet Thread Gender: Male
 - Threaded Inlet Thread Standard: BSPT
 - Threaded Inlet Thread Size: 1/4 in



1442659 Flow Controller

RS PRO THREADED SPEED CONTROLLER X 8MM TUBE OUTLET

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Type: Flow Controller
 - Inlet Port Type: Threaded
 - Tube Outlet Port: 8 mm
 - Minimum Outlet Pressure: 0 kgf/cm², 0 kPa
 - Maximum Outlet Pressure: 9.9 kgf/cm², 990 kPa
 - Threaded Inlet Thread Gender: Male
 - Threaded Inlet Thread Standard: BSPT
 - Threaded Inlet Thread Size: 1/4 in



1442660 Flow Controller

RS PRO TUBE SPEED CONTROLLER, PUSH IN 4MM TUBE INLET PORT X

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Type: Flow Controller
 - Inlet Port Type: Tube
 - Tube Inlet Port: Push In 4 mm
 - Tube Outlet Port: 4 mm
 - Minimum Outlet Pressure: 0 kPa, 0 kgf/cm²
 - Maximum Outlet Pressure: 9.9 kgf/cm², 990 kPa



1442661 Flow Controller

RS PRO TUBE SPEED CONTROLLER, PUSH IN 6MM TUBE INLET PORT X

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Type: Flow Controller
 - Inlet Port Type: Tube
 - Tube Inlet Port: Push In 6 mm
 - Tube Outlet Port: 6 mm
 - Minimum Outlet Pressure: 0 kPa, 0 kgf/cm²
 - Maximum Outlet Pressure: 9.9 kgf/cm², 990 kPa



1442662 Flow Controller

RS PRO TUBE SPEED CONTROLLER, PUSH IN 8MM TUBE INLET PORT X

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Type: Flow Controller
 - Inlet Port Type: Tube
 - Tube Inlet Port: Push In 8 mm
 - Tube Outlet Port: 8 mm
 - Minimum Outlet Pressure: 0 kgf/cm², 0 kPa
 - Maximum Outlet Pressure: 9.9 kgf/cm², 990 kPa



1442663 Flow Controller

RS PRO THREADED FLOW REGULATOR X PUSH IN 8 MM TUBE OUTLET PORT

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Type: Flow Controller
 - Inlet Port Type: Threaded
 - Outlet Port Type: Tube
 - Tube Outlet Port: Push In 8 mm
 - Minimum Outlet Pressure: 1 bar
 - Maximum Outlet Pressure: 10 bar
 - Threaded Inlet Thread Gender: Male
 - Threaded Inlet Thread Size: 6.35 mm



1761881 Flow Controller

RS PRO THREADED FLOW REGULATOR X PUSH IN 6 MM TUBE OUTLET PORT

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Type: Flow Controller
 - Inlet Port Type: Threaded
 - Outlet Port Type: Tube
 - Tube Outlet Port: Push In 6 mm
 - Minimum Outlet Pressure: 1 bar
 - Maximum Outlet Pressure: 10 bar
 - Threaded Inlet Thread Gender: Male
 - Threaded Inlet Thread Size: 6.35 mm



1761883 Flow Controller

RS PRO THREADED FLOW REGULATOR X PUSH IN 10 MM TUBE OUTLET PORT

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Type: Flow Controller
 - Inlet Port Type: Threaded
 - Outlet Port Type: Tube
 - Tube Outlet Port: Push In 10 mm
 - Minimum Outlet Pressure: 1 bar
 - Maximum Outlet Pressure: 10 bar
 - Threaded Inlet Thread Gender: Male
 - Threaded Inlet Thread Size: 9.525 mm



1761888 Flow Controller

RS PRO TUBE FLOW REGULATOR, PUSH IN 6MM TUBE INLET PORT X

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Type: Flow Controller
 - Inlet Port Type: Tube
 - Tube Inlet Port: Push In 6 mm
 - Outlet Port Type: Tube
 - Tube Outlet Port: Push In 6 mm
 - Minimum Outlet Pressure: 1 bar
 - Maximum Outlet Pressure: 10 bar



1761889 Flow Controller

RS PRO TUBE FLOW REGULATOR, PUSH IN 8MM TUBE INLET PORT X

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Type: Flow Controller
 - Inlet Port Type: Tube
 - Tube Inlet Port: Push In 8 mm
 - Outlet Port Type: Tube
 - Tube Outlet Port: Push In 8 mm
 - Minimum Outlet Pressure: 1 bar
 - Maximum Outlet Pressure: 10 bar



1761890 Flow Controller

RS PRO TUBE FLOW REGULATOR, PUSH IN 10MM TUBE INLET PORT X

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Type: Flow Controller
 - Inlet Port Type: Tube
 - Tube Inlet Port: Push In 10 mm
 - Outlet Port Type: Tube
 - Tube Outlet Port: Push In 10 mm
 - Minimum Outlet Pressure: 1 bar
 - Maximum Outlet Pressure: 10 bar



1761891 Flow Controller

RS PRO TUBE FLOW REGULATOR, PUSH IN 4MM TUBE INLET PORT X

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Type: Flow Controller
 - Inlet Port Type: Tube
 - Tube Inlet Port: Push In 4 mm
 - Outlet Port Type: Tube
 - Tube Outlet Port: Push In 4 mm
 - Minimum Outlet Pressure: 1 bar
 - Maximum Outlet Pressure: 10 bar



1761892 Flow Controller

RS PRO THREADED FLOW REGULATOR X PUSH IN 6 MM TUBE OUTLET PORT

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Type: Flow Controller
 - Inlet Port Type: Threaded
 - Outlet Port Type: Tube
 - Tube Outlet Port: Push In 6 mm
 - Minimum Outlet Pressure: 1 bar
 - Maximum Outlet Pressure: 10 bar
 - Threaded Inlet Thread Gender: Male
 - Threaded Inlet Thread Standard: Metric



1761894 Flow Controller

RS PRO THREADED FLOW REGULATOR X PUSH IN 4 MM TUBE OUTLET PORT

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Type: Flow Controller
 - Inlet Port Type: Threaded
 - Outlet Port Type: Tube
 - Tube Outlet Port: Push In 4 mm
 - Minimum Outlet Pressure: 1 bar
 - Maximum Outlet Pressure: 10 bar
 - Threaded Inlet Thread Gender: Male
 - Threaded Inlet Thread Standard: Metric



1761895 Flow Controller

RS PRO TUBE FLOW REGULATOR, 4MM TUBE INLET PORT

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Type: Flow Controller
 - Inlet Port Type: Tube
 - Tube Inlet Port: 4 mm
 - Outlet Port Type: Threaded
 - Minimum Outlet Pressure: 1 bar
 - Maximum Outlet Pressure: 10 bar
 - Threaded Outlet Thread Standard: Metric
 - Threaded Outlet Thread Size: M5



1875678 Flow Controller

RS PRO THREADED SPEED CONTROLLER, 1/8 IN MALE INLET

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Type: Speed Controller
 - Inlet Port Type: Threaded
 - Threaded Inlet Port: 1/8 in Male
 - Tube Outlet Port: 6 mm



2351187 Speed Controller

RS PRO THREADED SPEED CONTROLLER, M5 MALE INLET PORT X

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Type: Speed Controller
 - Inlet Port Type: Threaded
 - Threaded Inlet Port: M5 Male
 - Tube Outlet Port: 6 mm



2351188 Speed Controller

RS PRO THREADED SPEED CONTROLLER, 1/8 IN MALE INLET

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Type: Speed Controller
 - Inlet Port Type: Threaded
 - Threaded Inlet Port: 1/8 in Male
 - Tube Outlet Port: 8 mm



2351189 Speed Controller

RS PRO THREADED SPEED CONTROLLER X 6MM TUBE OUTLET

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Type: Flow Controller
 - Inlet Port Type: Threaded
 - Outlet Port Type: Tube
 - Tube Outlet Port: 6 mm
 - Minimum Outlet Pressure: -1 bar
 - Maximum Outlet Pressure: 15 bar
 - Threaded Inlet Thread Gender: Male
 - Body Material: Polyoxymethylene



9160952 Flow Controller

RS PRO THREADED SPEED CONTROLLER X 8MM TUBE OUTLET

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Type: Flow Controller
 - Inlet Port Type: Threaded
 - Outlet Port Type: Tube
 - Tube Outlet Port: 8 mm
 - Minimum Outlet Pressure: -1 bar
 - Maximum Outlet Pressure: 15 bar
 - Threaded Inlet Thread Gender: Male
 - Body Material: Polyoxymethylene



9160956 Flow Controller

RS PRO THREADED SPEED CONTROLLER X 4MM TUBE OUTLET

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Type: Flow Controller
 - Inlet Port Type: Threaded
 - Outlet Port Type: Tube
 - Tube Outlet Port: 4 mm
 - Minimum Outlet Pressure: -1 bar
 - Maximum Outlet Pressure: 15 bar
 - Threaded Inlet Thread Gender: Male
 - Body Material: Polyoxymethylene



9160959 Flow Controller

RS PRO MANIFOLD

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Maximum Operating Pressure: 100 bar
 - Maximum Operating Temperature: +300 °C



1761098 100 bar

RS PRO 3 OUTLET MANIFOLD, G 3/8 G 1/4

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Number of Outlet Ports: 3
 - Outlet Port: G 1/4 Female
 - Number of Inlet Ports: 2
 - Inlet Port: G 3/8 Female
 - Material: Aluminium
 - Maximum Operating Pressure: 75 bar
 - Outlet Port - Thread Size: 1/4 bsp in
 - Maximum Operating Temperature: +300 °C



1761102 3

RS PRO 6 OUTLET MANIFOLD, G 3/8 G 1/4

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Number of Outlet Ports: 6
 - Outlet Port: G 1/4 Female
 - Number of Inlet Ports: 2
 - Inlet Port: G 3/8 Female
 - Material: Aluminium
 - Maximum Operating Pressure: 75 bar
 - Outlet Port - Thread Size: 1/4 bsp in
 - Maximum Operating Temperature: +300 °C



1761104 6

RS PRO 3 OUTLET MANIFOLD PUSH IN 8 MM PUSH IN 6 MM

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Number of Outlet Ports: 3
 - Outlet Port: Push In 6 mm
 - Number of Inlet Ports: 1
 - Inlet Port: Push In 8 mm
 - Maximum Operating Pressure: 20 bar
 - Maximum Operating Temperature: +80 °C
 - Minimum Operating Temperature: -20 °C
 - Inlet Port - Connection Type: Push In



1761838 3

RS PRO 3 OUTLET MANIFOLD PUSH IN 10 MM PUSH IN 6 MM

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Number of Outlet Ports: 3
 - Outlet Port: Push In 6 mm
 - Number of Inlet Ports: 1
 - Inlet Port: Push In 10 mm
 - Maximum Operating Pressure: 20 bar
 - Maximum Operating Temperature: +80 °C
 - Minimum Operating Temperature: -20 °C
 - Inlet Port - Connection Type: Push In



1761839 3

RS PRO HANDLE 3/2 PNEUMATIC MANUAL CONTROL VALVE, 1/8IN

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Control Mechanism: Handle
 - Function: 3/2
 - Thread Size: 1/8 in
 - Thread Standard: BSPT
 - Control Button/Switch Colour: Blue
 - Maximum Operating Pressure: 9.9 kgf/cm², 990 kPa
 - Minimum Operating Temperature: 0 °C
 - Maximum Operating Temperature: +60 °C



1442678 Handle

RS PRO HANDLE 3/2 PNEUMATIC MANUAL CONTROL VALVE, 1/4IN

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Control Mechanism: Handle
 - Function: 3/2
 - Thread Size: 1/4 in
 - Thread Standard: BSPT
 - Control Button/Switch Colour: Blue
 - Maximum Operating Pressure: 9.9 kgf/cm², 990 kPa
 - Minimum Operating Temperature: 0 °C
 - Maximum Operating Temperature: +60 °C



1442679 Handle

RS PRO HANDLE 3/2 PNEUMATIC MANUAL CONTROL VALVE, 1/4IN

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Control Mechanism: Handle
 - Function: 3/2
 - Thread Size: 1/4 in
 - Thread Standard: BSPT
 - Control Button/Switch Colour: Blue
 - Maximum Operating Pressure: 9.9 kgf/cm², 990 kPa
 - Minimum Operating Temperature: 0 °C
 - Maximum Operating Temperature: +60 °C



1442688 Handle

RS PRO HANDLE MICRO VALVE, R 1/4, 6.35MM

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Control Mechanism: Handle
 - Connection Port Thread: R 1/4
 - Thread Size: 6.35 mm
 - Thread Standard: ISO 7
 - Control Button/Switch Colour: Red
 - Maximum Operating Pressure: 20 bar
 - Body Material: Brass
 - Maximum Flow Rate: 1.4 m³/h



1762139 Handle

RS PRO HANDLE MICRO VALVE, R 3/8, 9.525MM

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Control Mechanism: Handle
 - Connection Port Thread: R 3/8
 - Thread Size: 9.525 mm
 - Thread Standard: ISO 7
 - Control Button/Switch Colour: Red
 - Maximum Operating Pressure: 20 bar
 - Body Material: Brass
 - Maximum Flow Rate: 3.1 m³/h



1762140 Handle

RS PRO HANDLE MICRO VALVE, R 1/8, 3.175MM

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Control Mechanism: Handle
 - Connection Port Thread: R 1/8
 - Thread Size: 3.175 mm
 - Thread Standard: ISO 7
 - Control Button/Switch Colour: Red
 - Maximum Operating Pressure: 20 bar
 - Body Material: Brass
 - Maximum Flow Rate: 1.6 m³/h



1762141 Handle

RS PRO HANDLE MICRO VALVE, R 1/4, 6.35MM

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Control Mechanism: Handle
 - Connection Port Thread: R 1/4
 - Thread Size: 6.35 mm
 - Thread Standard: ISO 7
 - Control Button/Switch Colour: Red
 - Maximum Operating Pressure: 20 bar
 - Body Material: Brass
 - Maximum Flow Rate: 1.4 m³/h



1762142 Handle

RS PRO HANDLE MICRO VALVE, R 3/8, 9.525MM

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Control Mechanism: Handle
 - Connection Port Thread: R 3/8
 - Thread Size: 9.525 mm
 - Thread Standard: ISO 7
 - Control Button/Switch Colour: Red
 - Maximum Operating Pressure: 20 bar
 - Body Material: Brass
 - Maximum Flow Rate: 3.1 m³/h



1762143 Handle

RS PRO HANDLE MICRO VALVE, PUSH IN 6 MM

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Control Mechanism: Handle
 - Connection Port Thread: Push In 6 mm
 - Control Button/Switch Colour: Red
 - Maximum Operating Pressure: 20 bar
 - Body Material: Brass
 - Minimum Operating Temperature: -20 °C
 - Maximum Operating Temperature: +80 °C
 - Number of Ports: 2



1762145 Handle

RS PRO HANDLE MICRO VALVE, PUSH IN 8 MM

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Control Mechanism: Handle
 - Connection Port Thread: Push In 8 mm
 - Control Button/Switch Colour: Red
 - Maximum Operating Pressure: 20 bar
 - Body Material: Brass
 - Minimum Operating Temperature: -20 °C
 - Maximum Operating Temperature: +80 °C
 - Number of Ports: 2



1762146 Handle

RS PRO PNEUMATIC MANUAL CONTROL VALVE

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Maximum Operating Pressure: 10 bars



1762265 10 bars

RS PRO MANUAL 5/2 PNEUMATIC MANUAL CONTROL VALVE H SERIES, G

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Control Mechanism: Manual
 - Function: 5/2
 - Connection Port Thread: G 1/4
 - Thread Size: 1/4 in
 - Thread Standard: G
 - Manufacturer Series: H



2351154 Manual

RS PRO MANUAL 5/3 PNEUMATIC MANUAL CONTROL VALVE H SERIES, G

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Control Mechanism: Manual
 - Function: 5/3
 - Connection Port Thread: G 1/4
 - Thread Size: 1/4 in
 - Thread Standard: G
 - Manufacturer Series: H



2351155 Manual

RS PRO MANUAL PNEUMATIC MANUAL CONTROL VALVE HBVU

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Control Mechanism: Manual
 - Connection Port Thread: One Touch Fitting 12 mm
 - Thread Size: 12 mm
 - Thread Standard: Metric
 - Manufacturer Series: HBVU



2351156 Manual

RS PRO MANUAL 3/2 PNEUMATIC MANUAL CONTROL VALVE MV SERIES,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Control Mechanism: Manual
 - Function: 3/2
 - Connection Port Thread: G 1/8
 - Thread Size: 1/8 in
 - Thread Standard: G
 - Manufacturer Series: MV



2351190 Manual

RS PRO ROLLER LEVER 3/2 PNEUMATIC CONTROL VALVE, G 1/8,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Control Mechanism: Roller Lever
 - Function: 3/2
 - Connection Port Thread: G 1/8
 - Thread Size: 1/8 in
 - Thread Standard: G



2354723 Roller Lever

RS PRO EMERGENCY STOP 3/2 PNEUMATIC MANUAL CONTROL

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Control Mechanism: Emergency Stop
 - Function: 3/2
 - Connection Port Thread: G 1/8
 - Thread Size: 1/8 in
 - Thread Standard: G



2354726 Emergency Stop

RS PRO PUSH PULL 4/2 PNEUMATIC MANUAL CONTROL VALVE BHP

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Control Mechanism: Push Pull
 - Function: 4/2
 - Connection Port Thread: Push In 4 mm
 - Thread Size: 4 mm
 - Thread Standard: Push In
 - Manufacturer Series: BHP
 - Control Button/Switch Colour: Red
 - Maximum Operating Pressure: 16 bar



7840072 Push Pull

RS PRO LEVER 3/2 PNEUMATIC MANUAL CONTROL VALVE BR SERIES,

ขนาดบรรจุภัณฑ์: **1 x EA**

- Control Mechanism: Lever
- Function: 3/2
- Connection Port Thread: Metric M5
- Thread Size: M5
- Thread Standard: Metric
- Manufacturer Series: BR
- Maximum Operating Pressure: 10 bar
- Maximum Flow Rate: 125 L/min



7840079 Lever

IN-LINE MANUAL CONTROL VALVE, 8 MM

ขนาดบรรจุภัณฑ์: **10 x EA**

- Control Mechanism: Rotary Knob
- Thread Size: 8 mm
- Manufacturer Series: HVFF
- Control Button/Switch Colour: Blue
- Maximum Operating Pressure: 10 bars
- Body Material: Polyoxymethylene
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: +60 °C



9160962 Rotary Knob

IN-LINE MANUAL CONTROL VALVE, 6 MM

ขนาดบรรจุภัณฑ์: **10 x EA**

- Control Mechanism: Rotary Knob
- Thread Size: 6 mm
- Manufacturer Series: HVFF
- Control Button/Switch Colour: Blue
- Maximum Operating Pressure: 10 bars
- Body Material: Polyoxymethylene
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: +60 °C



9160968 Rotary Knob

IN-LINE MANUAL CONTROL VALVE, 10 MM

ขนาดบรรจุภัณฑ์: **10 x EA**

- Control Mechanism: Rotary Knob
- Thread Size: 10 mm
- Manufacturer Series: HVFF
- Control Button/Switch Colour: Blue
- Maximum Operating Pressure: 10 bars
- Body Material: Polyoxymethylene
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: +60 °C



9160971 Rotary Knob

RS PRO NON RETURN VALVE, 4MM TUBE OUTLET, 0 TO 9.9 KGf/CM², 0

ขนาดบรรจุภัณฑ์: **1 x EA**

- Inlet Connection Type: Threaded
- Tube Outlet Connection: 4 mm
- Threaded Inlet Gender: Male
- Minimum Operating Pressure: 0 kgf/cm², 0 kPa
- Maximum Operating Pressure: 9.9 kgf/cm², 990 kPa
- Maximum Operating Temperature: +60 °C
- Threaded Inlet Thread Size: 1/8 in
- Threaded Inlet Thread Standard: BSPT



1442693 Threaded

RS PRO NON RETURN VALVE, 6MM TUBE OUTLET, 0 TO 9.9 KGf/CM², 0

ขนาดบรรจุภัณฑ์: **1 x EA**

- Inlet Connection Type: Threaded
- Tube Outlet Connection: 6 mm
- Threaded Inlet Gender: Male
- Minimum Operating Pressure: 0 kgf/cm², 0 kPa
- Maximum Operating Pressure: 9.9 kgf/cm², 990 kPa
- Maximum Operating Temperature: +60 °C
- Threaded Inlet Thread Size: 1/8 in
- Threaded Inlet Thread Standard: BSPT



1442694 Threaded

RS PRO NON RETURN VALVE, 6MM TUBE OUTLET, 0 TO 9.9 KGf/CM², 0

ขนาดบรรจุภัณฑ์: **1 x EA**

- Inlet Connection Type: Threaded
- Tube Outlet Connection: 6 mm
- Threaded Inlet Gender: Male
- Minimum Operating Pressure: 0 kgf/cm², 0 kPa
- Maximum Operating Pressure: 9.9 kgf/cm², 990 kPa
- Maximum Operating Temperature: +60 °C
- Threaded Inlet Thread Size: 1/4 in
- Threaded Inlet Thread Standard: BSPT



1442695 Threaded

RS PRO NON RETURN VALVE, 8MM TUBE OUTLET, 0 TO 9.9 KGf/CM², 0

ขนาดบรรจุภัณฑ์: **1 x EA**

- Inlet Connection Type: Threaded
- Tube Outlet Connection: 8 mm
- Threaded Inlet Gender: Male
- Minimum Operating Pressure: 0 kPa, 0 kgf/cm²
- Maximum Operating Pressure: 9.9 kgf/cm², 990 kPa
- Maximum Operating Temperature: +60 °C
- Threaded Inlet Thread Size: 1/8 in
- Threaded Inlet Thread Standard: BSPT



1442696 Threaded

RS PRO NON RETURN VALVE, 8MM TUBE OUTLET, 0 TO 9.9 KGf/CM², 0

ขนาดบรรจุภัณฑ์: **1 x EA**

- Inlet Connection Type: Threaded
- Tube Outlet Connection: 8 mm
- Threaded Inlet Gender: Male
- Minimum Operating Pressure: 0 kPa, 0 kgf/cm²
- Maximum Operating Pressure: 9.9 kgf/cm², 990 kPa
- Maximum Operating Temperature: +60 °C
- Threaded Inlet Thread Size: 1/4 in
- Threaded Inlet Thread Standard: BSPT



1442697 Threaded

RS PRO NON RETURN VALVE, 10MM TUBE OUTLET, 0 TO 9.9 KGf/CM², 0

ขนาดบรรจุภัณฑ์: **1 x EA**

- Inlet Connection Type: Threaded
- Tube Outlet Connection: 10 mm
- Threaded Inlet Gender: Male
- Minimum Operating Pressure: 0 kgf/cm², 0 kPa
- Maximum Operating Pressure: 9.9 kgf/cm², 990 kPa
- Maximum Operating Temperature: +60 °C
- Threaded Inlet Thread Size: 3/8 in
- Threaded Inlet Thread Standard: BSPT



1442699 Threaded

RS PRO NON RETURN VALVE, 12MM TUBE OUTLET, 0 TO 9.9 KGf/CM², 0

ขนาดบรรจุภัณฑ์: **1 x EA**

- Inlet Connection Type: Threaded
- Tube Outlet Connection: 12 mm
- Threaded Inlet Gender: Male
- Minimum Operating Pressure: 0 kPa, 0 kgf/cm²
- Maximum Operating Pressure: 9.9 kgf/cm², 990 kPa
- Maximum Operating Temperature: +60 °C
- Threaded Inlet Thread Size: 1/2 in
- Threaded Inlet Thread Standard: BSPT



1442701 Threaded

RS PRO NON RETURN VALVE, 12MM TUBE INLET, 12MM TUBE OUTLET, 0 TO 9.9 KGf/CM², 0

ขนาดบรรจุภัณฑ์: **1 x EA**

- Inlet Connection Type: Tube
- Tube Inlet Connection: 12 mm
- Tube Outlet Connection: 12 mm
- Minimum Operating Pressure: 0 kgf/cm², 0 kPa
- Maximum Operating Pressure: 9.9 kgf/cm², 990 kPa
- Maximum Operating Temperature: +60 °C
- Minimum Operating Temperature: 0 °C
- Operating Pressure Range: 0 to 9.9 kgf/cm², 0 to 990 kPa



1442702 Tube

RS PRO NON RETURN VALVE

ขนาดบรรจุภัณฑ์: **1 x EA**

- Maximum Operating Pressure: 9.9 kgf/cm², 990 kPa
- Maximum Operating Temperature: +60 °C
- Minimum Operating Temperature: 0 °C



1442703 9.9 kgf/cm², 990

RS PRO NON RETURN VALVE

ขนาดบรรจุภัณฑ์: **1 x EA**

- Maximum Operating Pressure: 9.9 kgf/cm², 990 kPa
- Maximum Operating Temperature: +60 °C
- Minimum Operating Temperature: 0 °C



1442704 9.9 kgf/cm², 990

RS PRO NON RETURN VALVE

ขนาดบรรจุภัณฑ์: **1 x EA**

- Maximum Operating Pressure: 9.9 kgf/cm², 990 kPa
- Maximum Operating Temperature: +60 °C
- Minimum Operating Temperature: 0 °C



1442705 9.9 kgf/cm², 990

RS PRO NON RETURN VALVE

ขนาดบรรจุภัณฑ์: **1 x EA**

- Maximum Operating Pressure: 9.9 kgf/cm², 990 kPa
- Maximum Operating Temperature: +60 °C
- Minimum Operating Temperature: 0 °C



1442706 9.9 kgf/cm², 990

RS PRO NON RETURN VALVE, 2 TO 8BAR

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Threaded Inlet Gender: Female
 - Minimum Operating Pressure: 2 bar
 - Maximum Operating Pressure: 8 bar
 - Maximum Operating Temperature: +80 °C
 - Threaded Outlet Gender: Female
 - Threaded Inlet Thread Size: 6.35 mm
 - Operating Pressure Range: 2 to 8 bar
 - Threaded Outlet Thread Size: 6.35 mm



1762267 Female

RS PRO NON RETURN VALVE, 2 TO 8BAR

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Threaded Inlet Gender: Female
 - Minimum Operating Pressure: 2 bar
 - Maximum Operating Pressure: 8 bar
 - Maximum Operating Temperature: +80 °C
 - Threaded Outlet Gender: Female
 - Threaded Inlet Thread Size: 12.7 mm
 - Operating Pressure Range: 2 to 8 bar
 - Threaded Outlet Thread Size: 12.7 mm



1762269 Female

RS PRO NON RETURN VALVE, PUSH IN 4MM TUBE INLET, PUSH IN 4MM TUBE

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Tube Inlet Connection: Push In 4 mm
 - Tube Outlet Connection: Push In 4 mm
 - Minimum Operating Pressure: 2 bar
 - Maximum Operating Pressure: 8 bar
 - Maximum Operating Temperature: +80 °C
 - Threaded Inlet Thread Size: 12.7 mm
 - Operating Pressure Range: 2 to 8 bar
 - Body Material: Brass



1762270 Push In 4 mm

RS PRO NON RETURN VALVE, PUSH IN 6MM TUBE INLET, PUSH IN 6MM TUBE

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Tube Inlet Connection: Push In 6 mm
 - Tube Outlet Connection: Push In 6 mm
 - Minimum Operating Pressure: 2 bar
 - Maximum Operating Pressure: 8 bar
 - Maximum Operating Temperature: +80 °C
 - Threaded Inlet Thread Size: 12.7 mm
 - Operating Pressure Range: 2 to 8 bar
 - Body Material: Brass



1762271 Push In 6 mm

RS PRO 6063 NON RETURN VALVE 1/4 IN MALE INLET, 2 TO 8BAR

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Manufacturer Series: 6063
 - Inlet Connection Type: Threaded
 - Threaded Inlet Connection: 1/4 in Male
 - Outlet Connection Type: Threaded
 - Threaded Inlet Gender: Male
 - Minimum Operating Pressure: 2 bar
 - Maximum Operating Pressure: 8 bar
 - Maximum Operating Temperature: +80 °C



1875697 6063

RS PRO CVPU NON RETURN VALVE, 4MM TUBE INLET, 4MM TUBE OUTLET,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Manufacturer Series: CVPU
 - Inlet Connection Type: Tube
 - Tube Inlet Connection: 4 mm
 - Outlet Connection Type: Tube
 - Tube Outlet Connection: 4 mm
 - Minimum Operating Pressure: 0 bar
 - Maximum Operating Pressure: 10 bar
 - Maximum Operating Temperature: +60 °C



9160934 CVPU

RS PRO CVPU NON RETURN VALVE, 10MM TUBE INLET, 10MM TUBE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Manufacturer Series: CVPU
 - Inlet Connection Type: Tube
 - Tube Inlet Connection: 10 mm
 - Outlet Connection Type: Tube
 - Tube Outlet Connection: 10 mm
 - Minimum Operating Pressure: 0 bar
 - Maximum Operating Pressure: 10 bar
 - Maximum Operating Temperature: +60 °C



9160940 CVPU

RS PRO CVPU NON RETURN VALVE, 6MM TUBE INLET, 6MM TUBE OUTLET,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Manufacturer Series: CVPU
 - Inlet Connection Type: Tube
 - Tube Inlet Connection: 6 mm
 - Outlet Connection Type: Tube
 - Tube Outlet Connection: 6 mm
 - Minimum Operating Pressure: 0 bar
 - Maximum Operating Pressure: 10 bar
 - Maximum Operating Temperature: +60 °C



9160943 CVPU

RS PRO CVPU NON RETURN VALVE, 8MM TUBE INLET, 8MM TUBE OUTLET,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Manufacturer Series: CVPU
 - Inlet Connection Type: Tube
 - Tube Inlet Connection: 8 mm
 - Outlet Connection Type: Tube
 - Tube Outlet Connection: 8 mm
 - Minimum Operating Pressure: 0 bar
 - Maximum Operating Pressure: 10 bar
 - Maximum Operating Temperature: +60 °C



9160946 CVPU

RS PRO PNEUMATIC COMPACT CYLINDER - 32MM BORE, 50MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Stroke: 50 mm
 - Bore: 32 mm
 - Action: Double
 - Cushioning Type: Not Cushioned
 - Dimensions: 101 x 49 x 49 mm
 - Length: 101 mm
 - Width: 49 mm
 - Maximum Operating Pressure: 10 bar



1761586 50 mm

RS PRO ROUNDLINE CYLINDER - 16MM BORE, 100MM STROKE, DOUBLE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Stroke: 100 mm
 - Bore: 16 mm
 - Action: Double
 - Cushioning Type: Not Cushioned
 - Dimensions: 19 Dia. x 209 mm
 - Length: 209 mm
 - Maximum Operating Pressure: 10 bar
 - Maximum Operating Temperature: +80 °C



1761604 100 mm

RS PRO ROUNDLINE CYLINDER - 16MM BORE, 80MM STROKE, DOUBLE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Stroke: 80 mm
 - Bore: 16 mm
 - Action: Double
 - Cushioning Type: Not Cushioned
 - Dimensions: 19 Dia. x 189 mm
 - Length: 189 mm
 - Maximum Operating Pressure: 10 bar
 - Maximum Operating Temperature: +80 °C



1761606 80 mm

RS PRO ROUNDLINE CYLINDER - 16MM BORE, 50MM STROKE, DOUBLE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Stroke: 50 mm
 - Bore: 16 mm
 - Action: Double
 - Cushioning Type: Not Cushioned
 - Dimensions: 19 Dia. x 159 mm
 - Length: 159 mm
 - Maximum Operating Pressure: 10 bar
 - Maximum Operating Temperature: +80 °C



1761607 50 mm

RS PRO ROUNDLINE CYLINDER - 20MM BORE, 80MM STROKE, DOUBLE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Stroke: 80 mm
 - Bore: 20 mm
 - Action: Double
 - Cushioning Type: Not Cushioned
 - Dimensions: 27 Dia. x 211 mm
 - Length: 211 mm
 - Maximum Operating Pressure: 10 bar
 - Maximum Operating Temperature: +80 °C



1761610 80 mm

RS PRO ROUNDLINE CYLINDER - 16MM BORE, 25MM STROKE, DOUBLE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Stroke: 25 mm
 - Bore: 16 mm
 - Action: Double
 - Cushioning Type: Not Cushioned
 - Dimensions: 19 Dia. x 134 mm
 - Length: 134 mm
 - Maximum Operating Pressure: 10 bar
 - Maximum Operating Temperature: +80 °C



1761619 25 mm

RS PRO ROUNDLINE CYLINDER - 25MM BORE, 80MM STROKE, DOUBLE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Stroke: 80 mm
 - Bore: 25 mm
 - Action: Double
 - Cushioning Type: Not Cushioned
 - Dimensions: 30 Dia. x 220 mm
 - Length: 220 mm
 - Maximum Operating Pressure: 10 bar
 - Maximum Operating Temperature: +80 °C



1761620 80 mm

RS PRO ROUNDLINE CYLINDER - 25MM BORE, 100MM STROKE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Stroke: 100 mm
 - Bore: 25 mm
 - Action: Double
 - Cushioning Type: Not Cushioned
 - Dimensions: 30 Dia. x 240 mm
 - Length: 240 mm
 - Maximum Operating Pressure: 10 bar
 - Maximum Operating Temperature: +80 °C



1761630 100 mm

RS PRO ROUNDLINE CYLINDER - 20MM BORE, 50MM STROKE, DOUBLE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Stroke: 50 mm
 - Bore: 20 mm
 - Action: Double
 - Cushioning Type: Not Cushioned
 - Dimensions: 27 Dia. x 181 mm
 - Length: 181 mm
 - Maximum Operating Pressure: 10 bar
 - Maximum Operating Temperature: +80 °C



1761631 50 mm

RS PRO ROUNDLINE CYLINDER - 25MM BORE, 50MM STROKE, DOUBLE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Stroke: 50 mm
 - Bore: 25 mm
 - Action: Double
 - Cushioning Type: Not Cushioned
 - Dimensions: 30 Dia. x 190 mm
 - Length: 190 mm
 - Maximum Operating Pressure: 10 bar
 - Maximum Operating Temperature: +80 °C



1761632 50 mm

RS PRO ROUNDLINE CYLINDER - 25MM BORE, 25MM STROKE, DOUBLE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Stroke: 25 mm
 - Bore: 25 mm
 - Action: Double
 - Cushioning Type: Not Cushioned
 - Dimensions: 30 Dia. x 165 mm
 - Length: 165 mm
 - Maximum Operating Pressure: 10 bar
 - Maximum Operating Temperature: +80 °C



1761633 25 mm

RS PRO ROUNDLINE CYLINDER - 20MM BORE, 160MM STROKE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Stroke: 160 mm
 - Bore: 20 mm
 - Action: Double
 - Cushioning Type: Not Cushioned
 - Dimensions: 27 Dia. x 291 mm
 - Length: 291 mm
 - Maximum Operating Pressure: 10 bar
 - Maximum Operating Temperature: +80 °C



1761635 160 mm

RS PRO ROUNDLINE CYLINDER - 20MM BORE, 125MM STROKE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Stroke: 125 mm
 - Bore: 20 mm
 - Action: Double
 - Cushioning Type: Not Cushioned
 - Dimensions: 27 Dia. x 256 mm
 - Length: 256 mm
 - Maximum Operating Pressure: 10 bar
 - Maximum Operating Temperature: +80 °C



1761636 125 mm

RS PRO ROUNDLINE CYLINDER - 20MM BORE, 100MM STROKE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Stroke: 100 mm
 - Bore: 20 mm
 - Action: Double
 - Cushioning Type: Not Cushioned
 - Dimensions: 27 Dia. x 231 mm
 - Length: 231 mm
 - Maximum Operating Pressure: 10 bar
 - Maximum Operating Temperature: +80 °C



1761637 100 mm

RS PRO ROUNDLINE CYLINDER - 25MM BORE, 125MM STROKE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Stroke: 125 mm
 - Bore: 25 mm
 - Action: Double
 - Cushioning Type: Not Cushioned
 - Dimensions: 30 Dia. x 265 mm
 - Length: 265 mm
 - Maximum Operating Pressure: 10 bar
 - Maximum Operating Temperature: +80 °C



1761639 125 mm

RS PRO ISO STANDARD CYLINDER - 50MM BORE, 250MM STROKE,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Stroke: 250 mm
 - Bore: 50 mm
 - Action: Double
 - Cushioning Type: Cushioned
 - Dimensions: 393 x 64 x 64 mm
 - Length: 393 mm
 - Width: 64 mm
 - Maximum Operating Pressure: 10 bar



1761645 250 mm

RS PRO ISO STANDARD CYLINDER - 50MM BORE, 50MM STROKE, DOUBLE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Stroke: 50 mm
 - Bore: 50 mm
 - Action: Double
 - Cushioning Type: Cushioned
 - Dimensions: 193 x 64 x 64 mm
 - Length: 193 mm
 - Width: 64 mm
 - Maximum Operating Pressure: 10 bar



1761651 50 mm

RS PRO PNEUMATIC COMPACT CYLINDER - 100MM BORE, 50MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Stroke: 50 mm
 - Bore: 100 mm
 - Action: Double
 - Cushioning Type: Not Cushioned
 - Dimensions: 127 x 120 x 120 mm
 - Length: 127 mm
 - Width: 120 mm
 - Maximum Operating Pressure: 10 bar



1761710 50 mm

RS PRO ISO STANDARD CYLINDER - 32MM BORE, 80MM STROKE, DOUBLE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Stroke: 80 mm
 - Bore: 32 mm
 - Action: Double
 - Cushioning Type: Cushioned
 - Dimensions: 200 x 46 x 46 mm
 - Length: 200 mm
 - Width: 46 mm
 - Maximum Operating Pressure: 10 bar



1761714 80 mm

RS PRO DOUBLE ACTING CYLINDER - 10MM BORE, 25MM STROKE, IA

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Stroke: 25 mm
 - Bore: 10 mm
 - Action: Double
 - Manufacturer Series: IA



2351168 25 mm

RS PRO PNEUMATIC COMPACT CYLINDER - 16MM BORE, 40MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Stroke: 40 mm
 - Bore: 16 mm
 - Action: Double
 - Manufacturer Series: IAC



2351173 40 mm

RS PRO PNEUMATIC PISTON ROD CYLINDER - 20MM BORE, 50MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Stroke: 50 mm
 - Bore: 20 mm
 - Action: Single
 - Manufacturer Series: ISO 6432
 - Cushioning Type: Buffer
 - Maximum Operating Pressure: 10 bar
 - Maximum Operating Temperature: +80 °C
 - Minimum Operating Temperature: -20 °C



3043325 50 mm

RS PRO PNEUMATIC PISTON ROD CYLINDER - 10MM BORE, 25MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Stroke: 25 mm
 - Bore: 10 mm
 - Action: Single
 - Manufacturer Series: ISO 6432
 - Cushioning Type: Buffer
 - Maximum Operating Pressure: 10 bar
 - Maximum Operating Temperature: +80 °C
 - Minimum Operating Temperature: -20 °C



3043353 25 mm

RS PRO PNEUMATIC PISTON ROD CYLINDER - 25MM BORE, 125MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Stroke: 125 mm
 - Bore: 25 mm
 - Action: Double
 - Manufacturer Series: ISO 6432
 - Cushioning Type: Buffer
 - Maximum Operating Pressure: 10 bar
 - Maximum Operating Temperature: +80 °C
 - Minimum Operating Temperature: -20 °C



3043921 125 mm

RS PRO PNEUMATIC PISTON ROD CYLINDER - 32MM BORE, 160MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Stroke: 160 mm
 - Bore: 32 mm
 - Action: Double
 - Manufacturer Series: CDEM
 - Cushioning Type: Rubber
 - Dimensions: 281 x 48 x 48 mm
 - Length: 281 mm
 - Width: 48 mm



4802153 160 mm

RS PRO PNEUMATIC PISTON ROD CYLINDER - 32MM BORE, 200MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Stroke: 200 mm
 - Bore: 32 mm
 - Action: Double
 - Manufacturer Series: CDEM
 - Cushioning Type: Rubber
 - Dimensions: 321 x 48 x 48 mm
 - Length: 321 mm
 - Width: 48 mm



4802169 200 mm

RS PRO PNEUMATIC PISTON ROD CYLINDER - 40MM BORE, 80MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Stroke: 80 mm
 - Bore: 40 mm
 - Action: Double
 - Manufacturer Series: CDEM
 - Cushioning Type: Rubber
 - Dimensions: 215 x 54 x 54 mm
 - Length: 215 mm
 - Width: 54 mm



4802197 80 mm

RS PRO PNEUMATIC PISTON ROD CYLINDER - 40MM BORE, 100MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Stroke: 100 mm
 - Bore: 40 mm
 - Action: Double
 - Manufacturer Series: CDEM
 - Cushioning Type: Rubber
 - Dimensions: 235 x 54 x 54 mm
 - Length: 235 mm
 - Width: 54 mm



4802204 100 mm

RS PRO PNEUMATIC PISTON ROD CYLINDER - 50MM BORE, 50MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Stroke: 50 mm
 - Bore: 50 mm
 - Action: Double
 - Manufacturer Series: CDEM
 - Cushioning Type: Rubber
 - Dimensions: 193 x 65 x 65 mm
 - Length: 193 mm
 - Width: 65 mm



4802248 50 mm

RS PRO PNEUMATIC PISTON ROD CYLINDER - 50MM BORE, 100MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Stroke: 100 mm
 - Bore: 50 mm
 - Action: Double
 - Manufacturer Series: CDEM
 - Cushioning Type: Rubber
 - Dimensions: 243 x 65 x 65 mm
 - Length: 243 mm
 - Width: 65 mm



4802276 100 mm

RS PRO MALE COUPLER NIPPLE, 1/4 IN MALE

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Coupling Gender: Male
 - Threaded Connection: 1/4 in Male
 - Thread Size: 6.35 mm
 - Thread Gender: Male



1761105 Male

RS PRO MALE COUPLER NIPPLE, 1/2 IN MALE

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Coupling Gender: Male
 - Threaded Connection: 1/2 in Male
 - Thread Size: 12.7 mm
 - Thread Gender: Male



1761107 Male

RS PRO FEMALE COUPLER NIPPLE, 1/4 IN FEMALE

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Coupling Gender: Female
 - Threaded Connection: 1/4 in Female
 - Thread Size: 6.35 mm
 - Thread Gender: Female



1761108 Female

RS PRO FEMALE COUPLER NIPPLE, 1/2 IN FEMALE

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Coupling Gender: Female
 - Threaded Connection: 1/2 in Female
 - Thread Size: 12.7 mm
 - Thread Gender: Female



1761110 Female

RS PRO COUPLER NIPPLE

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Hose Inner Diameter: 6 mm
 - Coupling Connector Type: Hose Barb Insert
 - Body Material: Brass
 - Coupling Connector Direction: Straight
 - Maximum Working Pressure: 16 bar



1761272 6 mm

RS PRO BRASS COUPLER NIPPLE

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Material: Brass
 - Maximum Operating Pressure: 16 bar



1761760 Brass

FEMALE PLUG - EUROPEAN PROFIL - 7,8 MM

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Coupling Gender: Female
 - Threaded Connection: 1/4 in Female
 - Manufacturer Series: 262
 - Connection Type: Threaded, Tube
 - Thread Size: 1/4 in
 - Material: Nickel Plated Brass



2312516 Female

STRAIGHT MALE ADAPTOR (PARALLEL)

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Coupling Gender: Male
 - Threaded Connection: M7 Male
 - Manufacturer Series: 56020
 - Connection Type: Threaded, Tube
 - Thread Size: M7
 - Hose Barb Connection: 6 mm
 - Material: Nickel Plated Brass



2312683 Male

RS PRO NICKEL PLATED BRASS MALE PNEUMATIC STRAIGHT THREADED-TO-

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Coupling Gender: Male
 - Threaded Connection: M5 Male
 - Manufacturer Series: 70020
 - Connection Type: Threaded, Tube
 - Thread Size: M5
 - Hose Barb Connection: 4 mm
 - Material: Nickel Plated Brass



2312742 Male

RS PRO NICKEL PLATED BRASS MALE PNEUMATIC STRAIGHT THREADED-TO-

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Coupling Gender: Male
 - Threaded Connection: 1/8 in Male
 - Manufacturer Series: 70020
 - Connection Type: Threaded, Tube
 - Thread Size: 1/8 in
 - Hose Barb Connection: 6 mm
 - Material: Nickel Plated Brass



2312745 Male

STRAIGHT MALE ADAPTOR (PARALLEL) - FOOD

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Coupling Gender: Male
 - Threaded Connection: 1/4 in Male
 - Manufacturer Series: 70020
 - Connection Type: Threaded, Tube
 - Thread Size: 1/4 in
 - Hose Barb Connection: 6 mm
 - Material: Nickel Plated Brass



2312746 Male

RS PRO NICKEL PLATED BRASS MALE PNEUMATIC STRAIGHT THREADED-TO-

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Coupling Gender: Male
 - Threaded Connection: 1/8 in Male
 - Manufacturer Series: 70020
 - Connection Type: Threaded, Tube
 - Thread Size: 1/8 in
 - Hose Barb Connection: 8 mm
 - Material: Nickel Plated Brass



2312747 Male

STRAIGHT MALE ADAPTOR (PARALLEL) - FOOD

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Coupling Gender: Male
 - Threaded Connection: 1/4 in Male
 - Manufacturer Series: 70020
 - Connection Type: Threaded, Tube
 - Thread Size: 1/4 in
 - Hose Barb Connection: 8 mm
 - Material: Nickel Plated Brass



2312748 Male

RS PRO NICKEL PLATED BRASS MALE PNEUMATIC STRAIGHT THREADED-TO-

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Coupling Gender: Male
 - Threaded Connection: 1/4 in Male
 - Manufacturer Series: 70020
 - Connection Type: Threaded, Tube
 - Thread Size: 1/4 in
 - Hose Barb Connection: 10 mm
 - Material: Nickel Plated Brass



2312749 Male

ORIENTING ELBOW MALE ADAPTOR (PARALLEL)

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Coupling Gender: Male
 - Threaded Connection: M5 Male
 - Manufacturer Series: 70116
 - Connection Type: Threaded, Tube
 - Thread Size: M5
 - Hose Barb Connection: 4 mm
 - Material: Nickel Plated Brass



2312757 Male

RS PRO NICKEL PLATED BRASS MALE PNEUMATIC ELBOW THREADED-TO-

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Coupling Gender: Male
 - Threaded Connection: 1/8 in Male
 - Manufacturer Series: 70116
 - Connection Type: Threaded, Tube
 - Thread Size: 1/8 in
 - Hose Barb Connection: 4 mm
 - Material: Nickel Plated Brass



2312758 Male

ORIENTING ELBOW MALE ADAPTOR (PARALLEL)

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Coupling Gender: Male
 - Threaded Connection: 1/8 in Male
 - Manufacturer Series: 70116
 - Connection Type: Threaded, Tube
 - Thread Size: 1/8 in
 - Hose Barb Connection: 6 mm
 - Material: Nickel Plated Brass



2312760 Male

ORIENTING ELBOW MALE ADAPTOR (PARALLEL)

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Coupling Gender: Male
 - Threaded Connection: 1/4 in Male
 - Manufacturer Series: 70116
 - Connection Type: Threaded, Tube
 - Thread Size: 1/4 in
 - Hose Barb Connection: 8 mm
 - Material: Nickel Plated Brass



2312763 Male

RS PRO STAINLESS STEEL 316 MALE PNEUMATIC STRAIGHT THREADED-TO-

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Coupling Gender: Male
 - Threaded Connection: NPT 1/8 Male
 - Manufacturer Series: SSPC
 - Connection Type: Threaded
 - Hose Barb Connection: 6 mm
 - Material: Stainless Steel 316



2351278 Male

RS PRO STAINLESS STEEL 316 MALE PNEUMATIC STRAIGHT THREADED-TO-

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Coupling Gender: Male
 - Threaded Connection: NPT 1/4 Male
 - Manufacturer Series: SSPC
 - Connection Type: Threaded
 - Hose Barb Connection: 8 mm
 - Material: Stainless Steel 316



2351279 Male

RS PRO BRASS MALE PNEUMATIC QUICK CONNECT COUPLING, 6MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Connection Standard: Rectus 17, Schrader NW5
 - Coupling Gender: Male
 - Manufacturer Series: 17
 - Connection Type: Hose Barb
 - Hose Barb Connection: 6 mm
 - Material: Brass
 - Thread Gender: Male
 - Maximum Operating Pressure: 35 bar



6671677 Rectus 17,

RS PRO BRASS FEMALE PNEUMATIC QUICK CONNECT COUPLING, G 1/8

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Connection Standard: Rectus 17, Schrader NW5
 - Coupling Gender: Female
 - Threaded Connection: G 1/8 Female
 - Manufacturer Series: 17
 - Connection Type: Threaded
 - Thread Size: 1/8 in
 - Material: Brass
 - Thread Gender: Female



6671683 Rectus 17,

RS PRO BRASS MALE PNEUMATIC QUICK CONNECT COUPLING, 10MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Connection Standard: Rectus 17, Schrader NW5
 - Coupling Gender: Male
 - Manufacturer Series: 17
 - Connection Type: Hose Barb
 - Hose Barb Connection: 10 mm
 - Material: Brass
 - Thread Gender: Male
 - Maximum Operating Pressure: 35 bar



6671686 Rectus 17,

RS PRO BRASS FEMALE PNEUMATIC QUICK CONNECT COUPLING, G 1/4

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Connection Standard: Rectus 17, Schrader NW5
 - Coupling Gender: Female
 - Threaded Connection: G 1/4 Female
 - Manufacturer Series: 17
 - Connection Type: Threaded
 - Thread Size: 1/4 in
 - Material: Brass
 - Thread Gender: Female



6671689 Rectus 17,

RS PRO BRASS FEMALE PNEUMATIC QUICK CONNECT COUPLING, G 1/4

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Connection Standard: Rectus 17, Schrader NW5
 - Coupling Gender: Female
 - Threaded Connection: G 1/4 Female
 - Manufacturer Series: 17
 - Connection Type: Threaded
 - Thread Size: 1/4 in
 - Material: Brass
 - Thread Gender: Female



6671692 Rectus 17,

MALE THREAD COUPLER R1/4"

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Connection Standard: Rectus 17, Schrader NW5
 - Coupling Gender: Male
 - Threaded Connection: R 1/4 Male
 - Manufacturer Series: 17
 - Connection Type: Threaded
 - Thread Size: 1/4 in
 - Material: Brass, Steel
 - Thread Gender: Male



6671695 Rectus 17,

RS PRO BRASS, STEEL MALE PNEUMATIC QUICK CONNECT

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Connection Standard: Rectus 17, Schrader NW5
 - Coupling Gender: Male
 - Threaded Connection: R 1/4 Male
 - Manufacturer Series: 17
 - Connection Type: Threaded
 - Thread Size: 1/4 in
 - Material: Brass, Steel
 - Thread Gender: Male



6671702 Rectus 17,

RS PRO BRASS MALE PNEUMATIC QUICK CONNECT COUPLING, 6MM

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Connection Standard: Rectus 17, Schrader NW5
 - Coupling Gender: Male
 - Manufacturer Series: 17
 - Connection Type: Hose Barb
 - Hose Barb Connection: 6 mm
 - Material: Brass
 - Thread Gender: Male
 - Maximum Operating Pressure: 35 bar



6671706 Rectus 17,

RS PRO BRASS MALE PNEUMATIC QUICK CONNECT COUPLING, 10MM

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Connection Standard: Rectus 17, Schrader NW5
 - Coupling Gender: Male
 - Manufacturer Series: 17
 - Connection Type: Hose Barb
 - Hose Barb Connection: 10 mm
 - Material: Brass
 - Thread Gender: Male
 - Maximum Operating Pressure: 35 bar



6671718 Rectus 17,

RS PRO BRASS MALE PNEUMATIC QUICK CONNECT COUPLING, 6MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Connection Standard: PLC 60, Rectus 19
 - Coupling Gender: Male
 - Manufacturer Series: 19
 - Connection Type: Hose Barb
 - Hose Barb Connection: 6 mm
 - Material: Brass
 - Thread Gender: Male
 - Maximum Operating Pressure: 35 bar



6671721 PLC 60, Rectus 19

STANDARD HOSE BARB COUPLER 10 MM 3/8"

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Connection Standard: PLC 60, Rectus 19
 - Coupling Gender: Male
 - Manufacturer Series: 19
 - Connection Type: Hose Barb
 - Hose Barb Connection: 10 mm
 - Material: Brass
 - Thread Gender: Male
 - Maximum Operating Pressure: 35 bar



6671724 PLC 60, Rectus 19

FEMALE THREAD COUPLER G1/4"

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Connection Standard: PLC 60, Rectus 19
 - Coupling Gender: Female
 - Threaded Connection: G 1/4 Female
 - Manufacturer Series: 19
 - Connection Type: Threaded
 - Thread Size: 1/4 in
 - Material: Brass
 - Thread Gender: Female



6671728 PLC 60, Rectus 19

MALE THREAD PLUG R 1/4"

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Connection Standard: PLC 60, Rectus 19
 - Coupling Gender: Male
 - Threaded Connection: R 1/4 Male
 - Manufacturer Series: 19
 - Connection Type: Threaded
 - Thread Size: 1/4 in
 - Material: Brass
 - Thread Gender: Male



6671730 PLC 60, Rectus 19

RS PRO BRASS FEMALE PNEUMATIC QUICK CONNECT COUPLING, G 3/8

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Connection Standard: PLC 60, Rectus 19
 - Coupling Gender: Female
 - Threaded Connection: G 3/8 Female
 - Manufacturer Series: 19
 - Connection Type: Threaded
 - Thread Size: 3/8 in
 - Material: Brass
 - Thread Gender: Female



6671737 PLC 60, Rectus 19

RS PRO BRASS MALE PNEUMATIC QUICK CONNECT COUPLING, R 1/4

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Connection Standard: PLC 60, Rectus 19
 - Coupling Gender: Male
 - Threaded Connection: R 1/4 Male
 - Manufacturer Series: 19
 - Connection Type: Threaded
 - Thread Size: 1/4 in
 - Material: Brass
 - Thread Gender: Male



6671743 PLC 60, Rectus 19

RS PRO BRASS MALE PNEUMATIC QUICK CONNECT COUPLING, 10MM

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Connection Standard: PLC 60, Rectus 19
 - Coupling Gender: Male
 - Threaded Connection: R 1/4 Male
 - Manufacturer Series: 19
 - Connection Type: Hose Barb
 - Hose Barb Connection: 10 mm
 - Material: Brass
 - Thread Gender: Male
 - Maximum Operating Pressure: 35 bar



6671756 PLC 60, Rectus 19

RS PRO BRASS MALE PNEUMATIC QUICK CONNECT COUPLING, 6MM

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Connection Standard: PLC 60, Rectus 19
 - Coupling Gender: Male
 - Threaded Connection: R 1/4 Male
 - Manufacturer Series: 19
 - Connection Type: Hose Barb
 - Hose Barb Connection: 6 mm
 - Material: Brass
 - Thread Gender: Male
 - Maximum Operating Pressure: 35 bar



6671759 PLC 60, Rectus 19

RS PRO BRASS FEMALE PNEUMATIC QUICK CONNECT COUPLING, METRIC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Connection Standard: Rectus 20, Rectus 91, Walther 06-003
 - Coupling Gender: Female
 - Threaded Connection: Metric M5 Female
 - Manufacturer Series: 20
 - Connection Type: Threaded
 - Thread Size: M5
 - Material: Brass
 - Thread Gender: Female



6671762 Rectus 20, Rectus

RS PRO BRASS MALE PNEUMATIC QUICK CONNECT COUPLING, G 1/4

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Connection Standard: PLC 60, Rectus 19
 - Coupling Gender: Male
 - Threaded Connection: G 1/4 Female
 - Manufacturer Series: 19
 - Connection Type: Threaded
 - Thread Size: 1/4 in
 - Material: Brass
 - Thread Gender: Female



6671765 PLC 60, Rectus 19

RS PRO BRASS FEMALE, MALE PNEUMATIC QUICK CONNECT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Connection Standard: PLC 60, Rectus 19
 - Coupling Gender: Female, Male
 - Threaded Connection: G 1/4 Female, R 1/4 Male
 - Manufacturer Series: 19
 - Connection Type: Threaded
 - Thread Size: 1/4 in
 - Material: Brass
 - Thread Gender: Female, Male



6671768 PLC 60, Rectus 19

RS PRO BRASS FEMALE PNEUMATIC QUICK CONNECT COUPLING, G 1/8

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Connection Standard: Rectus 20, Rectus 91, Walther 06-003
 - Coupling Gender: Female
 - Threaded Connection: G 1/8 Female
 - Manufacturer Series: 20
 - Connection Type: Threaded
 - Thread Size: 1/8 in
 - Material: Brass
 - Thread Gender: Female



6671771 Rectus 20, Rectus

PLASTIC HOSE PLUG 3MM 1/8"

ขนาดบรรจุภัณฑ์: **5 x EA**

- Connection Standard: Rectus 20, Rectus 91, Walther 06-003
- Coupling Gender: Male
- Manufacturer Series: 20
- Connection Type: Hose Barb
- Hose Barb Connection: 3 mm
- Material: Brass
- Maximum Operating Pressure: 35 bar
- Finish: Nickel Plated



6671774 Rectus 20, Rectus

PLASTIC HOSE PLUG 4MM 1/6"

ขนาดบรรจุภัณฑ์: **5 x EA**

- Connection Standard: Rectus 20, Rectus 91, Walther 06-003
- Coupling Gender: Male
- Manufacturer Series: 20
- Connection Type: Hose Barb
- Hose Barb Connection: 4 mm
- Material: Brass
- Maximum Operating Pressure: 35 bar
- Finish: Nickel Plated



6671778 Rectus 20, Rectus

PANEL MOUNT PLASTIC HOSE COUPLING 4MM

ขนาดบรรจุภัณฑ์: **1 x EA**

- Connection Standard: Rectus 20, Rectus 91, Walther 06-003
- Coupling Gender: Male
- Threaded Connection: Metric M7 Male
- Manufacturer Series: 20
- Connection Type: Hose Barb
- Hose Barb Connection: 4 mm
- Material: Brass
- Thread Gender: Male



6671780 Rectus 20, Rectus

RS PRO BRASS MALE PNEUMATIC QUICK CONNECT COUPLING, METRIC

ขนาดบรรจุภัณฑ์: **1 x EA**

- Connection Standard: Rectus 20, Rectus 91, Walther 06-003
- Coupling Gender: Male
- Threaded Connection: Metric M5 Male
- Manufacturer Series: 20
- Connection Type: Threaded
- Thread Size: M5
- Material: Brass
- Thread Gender: Male



6671784 Rectus 20, Rectus

RS PRO BRASS MALE PNEUMATIC QUICK CONNECT COUPLING, METRIC

ขนาดบรรจุภัณฑ์: **1 x EA**

- Connection Standard: Rectus 20, Rectus 91, Walther 06-003
- Coupling Gender: Male
- Threaded Connection: Metric M7 Male
- Manufacturer Series: 20
- Connection Type: Hose Barb
- Hose Barb Connection: 3 mm
- Material: Brass
- Thread Gender: Male



6671787 Rectus 20, Rectus

RS PRO BRASS MALE PNEUMATIC QUICK CONNECT COUPLING, G 1/8

ขนาดบรรจุภัณฑ์: **5 x EA**

- Connection Standard: Rectus 20, Rectus 91, Walther 06-003
- Coupling Gender: Male
- Threaded Connection: G 1/8 Male
- Manufacturer Series: 20
- Connection Type: Threaded
- Thread Size: 1/8 in
- Material: Brass
- Thread Gender: Male



6671790 Rectus 20, Rectus

RS PRO BRASS MALE PNEUMATIC QUICK CONNECT COUPLING, G 1/8

ขนาดบรรจุภัณฑ์: **1 x EA**

- Connection Standard: Rectus 20, Rectus 91, Walther 06-003
- Coupling Gender: Male
- Threaded Connection: G 1/8 Male
- Manufacturer Series: 20
- Connection Type: Threaded
- Thread Size: 1/8 in
- Material: Brass
- Thread Gender: Male



6671793 Rectus 20, Rectus

MALE THREAD PLUG M5

ขนาดบรรจุภัณฑ์: **5 x EA**

- Connection Standard: Rectus 20, Rectus 91, Walther 06-003
- Coupling Gender: Male
- Threaded Connection: Metric M5 Male
- Manufacturer Series: 20
- Connection Type: Threaded
- Thread Size: M5
- Material: Brass
- Thread Gender: Male



6671796 Rectus 20, Rectus

RS PRO BRASS FEMALE PNEUMATIC QUICK CONNECT COUPLING, METRIC

ขนาดบรรจุภัณฑ์: **5 x EA**

- Connection Standard: Rectus 20, Rectus 91, Walther 06-003
- Coupling Gender: Female
- Threaded Connection: Metric M5 Female
- Manufacturer Series: 20
- Connection Type: Threaded
- Thread Size: M5
- Material: Brass
- Thread Gender: Female



6671800 Rectus 20, Rectus

RS PRO BRASS FEMALE PNEUMATIC QUICK CONNECT COUPLING, G 1/8

ขนาดบรรจุภัณฑ์: **5 x EA**

- Connection Standard: Rectus 20, Rectus 91, Walther 06-003
- Coupling Gender: Female
- Threaded Connection: G 1/8 Female
- Manufacturer Series: 20
- Connection Type: Threaded
- Thread Size: 1/8 in
- Material: Brass
- Thread Gender: Female



6671803 Rectus 20, Rectus

MALE THREAD PLUG G 1/8"

ขนาดบรรจุภัณฑ์: **5 x EA**

- Connection Standard: Camozzi, Legris, Rectus 21, Rectus 90
- Coupling Gender: Male
- Threaded Connection: G 1/8 Male
- Manufacturer Series: 21
- Connection Type: Threaded
- Thread Size: 1/8 in
- Material: Brass
- Thread Gender: Male



6671807 Camozzi, Legris,

STANDARD HOSE BARB COUPLER 4 MM 1/6"

ขนาดบรรจุภัณฑ์: **1 x EA**

- Connection Standard: Camozzi, Legris, Rectus 21, Rectus 90
- Coupling Gender: Male
- Manufacturer Series: 21
- Connection Type: Hose Barb
- Hose Barb Connection: 4 mm
- Material: Brass
- Thread Gender: Male
- Maximum Operating Pressure: 35 bar



6671813 Camozzi, Legris,

MALE THREAD PLUG G 1/4"

ขนาดบรรจุภัณฑ์: **5 x EA**

- Connection Standard: Camozzi, Legris, Rectus 21, Rectus 90
- Coupling Gender: Male
- Threaded Connection: G 1/4 Male
- Manufacturer Series: 21
- Connection Type: Threaded
- Thread Size: 1/4 in
- Material: Brass
- Thread Gender: Male



6671816 Camozzi, Legris,

RS PRO BRASS MALE PNEUMATIC QUICK CONNECT COUPLING, G 3/8

ขนาดบรรจุภัณฑ์: **5 x EA**

- Connection Standard: Camozzi, Legris, Rectus 21, Rectus 90
- Coupling Gender: Male
- Threaded Connection: G 3/8 Male
- Manufacturer Series: 21
- Connection Type: Threaded
- Thread Size: 3/8 in
- Material: Brass
- Thread Gender: Male



6671819 Camozzi, Legris,

HOSE BARB COUPLER, 1/4"

ขนาดบรรจุภัณฑ์: **1 x EA**

- Connection Standard: Camozzi, Legris, Rectus 21, Rectus 90
- Coupling Gender: Male
- Manufacturer Series: 21
- Connection Type: Hose Barb
- Hose Barb Connection: 6 mm
- Material: Brass
- Thread Gender: Male
- Maximum Operating Pressure: 35 bar



6671822 Camozzi, Legris,

STANDARD HOSE BARB COUPLER 9MM 5/14"

ขนาดบรรจุภัณฑ์: **1 x EA**

- Connection Standard: Camozzi, Legris, Rectus 21, Rectus 90
- Coupling Gender: Male
- Manufacturer Series: 21
- Connection Type: Hose Barb
- Hose Barb Connection: 9 mm
- Material: Brass
- Thread Gender: Male
- Maximum Operating Pressure: 35 bar



6671825 Camozzi, Legris,

FEMALE THREAD COUPLER G 1/8"

ขนาดบรรจุภัณฑ์: **1 x EA**

- Connection Standard: Camozzi, Legris, Rectus 21, Rectus 90
- Coupling Gender: Female
- Threaded Connection: G 1/8 Female
- Manufacturer Series: 21
- Connection Type: Threaded
- Thread Size: 1/8 in
- Material: Brass
- Thread Gender: Female



6671829 Camozzi, Legris,

RS PRO BRASS FEMALE PNEUMATIC QUICK CONNECT COUPLING, G 3/8

ขนาดบรรจุภัณฑ์: **1 x EA**

- Connection Standard: Camozzi, Legris, Rectus 21, Rectus 90
- Coupling Gender: Female
- Threaded Connection: G 3/8 Female
- Manufacturer Series: 21
- Connection Type: Threaded
- Thread Size: 3/8 in
- Material: Brass
- Thread Gender: Female



6671831 Camozzi, Legris,

MALE THREAD COUPLER G 1/8"

ขนาดบรรจุภัณฑ์: **1 x EA**

- Connection Standard: Camozzi, Legris, Rectus 21, Rectus 90
- Coupling Gender: Male
- Threaded Connection: G 1/8 Male
- Manufacturer Series: 21
- Connection Type: Threaded
- Thread Size: 1/8 in
- Material: Brass
- Thread Gender: Male



6671835 Camozzi, Legris,

FEMALE THREAD COUPLER G 1/4"

ขนาดบรรจุภัณฑ์: **1 x EA**

- Connection Standard: Camozzi, Legris, Rectus 21, Rectus 90
- Coupling Gender: Female
- Threaded Connection: G 1/4 Female
- Manufacturer Series: 21
- Connection Type: Threaded
- Thread Size: 1/4 in
- Material: Brass
- Thread Gender: Female



6671838 Camozzi, Legris,

RS PRO BRASS FEMALE PNEUMATIC QUICK CONNECT COUPLING, G 1/8

ขนาดบรรจุภัณฑ์: **5 x EA**

- Connection Standard: Camozzi, Legris, Rectus 21, Rectus 90
- Coupling Gender: Female
- Threaded Connection: G 1/8 Female
- Manufacturer Series: 21
- Connection Type: Threaded
- Thread Size: 1/8 in
- Material: Brass
- Thread Gender: Female



6671841 Camozzi, Legris,

MALE THREAD COUPLER G 1/4"

ขนาดบรรจุภัณฑ์: **1 x EA**

- Connection Standard: Camozzi, Legris, Rectus 21, Rectus 90
- Coupling Gender: Male
- Threaded Connection: G 1/4 Male
- Manufacturer Series: 21
- Connection Type: Threaded
- Thread Size: 1/4 in
- Material: Brass
- Thread Gender: Male



6671844 Camozzi, Legris,

RS PRO BRASS MALE PNEUMATIC QUICK CONNECT COUPLING, G 3/8

ขนาดบรรจุภัณฑ์: **1 x EA**

- Connection Standard: Camozzi, Legris, Rectus 21, Rectus 90
- Coupling Gender: Male
- Threaded Connection: G 3/8 Male
- Manufacturer Series: 21
- Connection Type: Threaded
- Thread Size: 3/8 in
- Material: Brass
- Thread Gender: Male



6671847 Camozzi, Legris,

FEMALE THREAD PLUG G 1/4"

ขนาดบรรจุภัณฑ์: **5 x EA**

- Connection Standard: Camozzi, Legris, Rectus 21, Rectus 90
- Coupling Gender: Female
- Threaded Connection: G 1/4 Female
- Manufacturer Series: 21
- Connection Type: Threaded
- Thread Size: 1/4 in
- Material: Brass
- Thread Gender: Female



6671850 Camozzi, Legris,

RS PRO BRASS FEMALE PNEUMATIC QUICK CONNECT COUPLING, G 3/8

ขนาดบรรจุภัณฑ์: **5 x EA**

- Connection Standard: Camozzi, Legris, Rectus 21, Rectus 90
- Coupling Gender: Female
- Threaded Connection: G 3/8 Female
- Manufacturer Series: 21
- Connection Type: Threaded
- Thread Size: 3/8 in
- Material: Brass
- Thread Gender: Female



6671853 Camozzi, Legris,

PLASTIC HOSE PLUG 4MM 1/8"

ขนาดบรรจุภัณฑ์: **5 x EA**

- Connection Standard: Camozzi, Legris, Rectus 21, Rectus 90
- Coupling Gender: Male
- Manufacturer Series: 21
- Connection Type: Hose Barb
- Hose Barb Connection: 4 mm
- Material: Brass
- Thread Gender: Male
- Maximum Operating Pressure: 35 bar



6671857 Camozzi, Legris,

RS PRO BRASS MALE PNEUMATIC QUICK CONNECT COUPLING, R 1/4

ขนาดบรรจุภัณฑ์: **1 x EA**

- Connection Standard: CEJN 310, Forster, Hansen 3000, Parker PBF 1/4, Rectus 23, TST 024 Atlas Copco QIC 08, US MIL SpeCC 4109 1/4
- Coupling Gender: Male
- Threaded Connection: R 1/4 Male
- Manufacturer Series: 23
- Connection Type: Threaded
- Thread Size: 1/4 in
- Material: Brass
- Thread Gender: Male



6671863 CEJN 310,

PLASTIC HOSE PLUG 6MM 1/4"

ขนาดบรรจุภัณฑ์: **5 x EA**

- Connection Standard: Camozzi, Legris, Rectus 21, Rectus 90
- Coupling Gender: Male
- Manufacturer Series: 21
- Connection Type: Hose Barb
- Hose Barb Connection: 6 mm
- Material: Brass
- Thread Gender: Male
- Maximum Operating Pressure: 35 bar



6671866 Camozzi, Legris,

PLASTIC HOSE PLUG 9MM 5/16

ขนาดบรรจุภัณฑ์: **5 x EA**

- Connection Standard: Camozzi, Legris, Rectus 21, Rectus 90
- Coupling Gender: Male
- Manufacturer Series: 21
- Connection Type: Hose Barb
- Hose Barb Connection: 9 mm
- Material: Brass
- Thread Gender: Male
- Maximum Operating Pressure: 35 bar



6671869 Camozzi, Legris,

FEMALE THREAD COUPLER G 1/4"

ขนาดบรรจุภัณฑ์: **1 x EA**

- Connection Standard: CEJN 310, Forster, Hansen 3000, ISO 6150 B, Parker Legris 1/4, Rectus 23, TST 024 Atlas Copco QIC 08, US MIL 4109 1/4
- Coupling Gender: Female
- Threaded Connection: G 1/4 Female
- Manufacturer Series: 23
- Connection Type: Threaded
- Thread Size: 1/4 in
- Material: Brass
- Thread Gender: Female



6671881 CEJN 310,

RS PRO BRASS MALE PNEUMATIC QUICK CONNECT COUPLING, 10MM

ขนาดบรรจุภัณฑ์: **5 x EA**

- Connection Standard: CEJN 310, Forster, Hansen 3000, ISO 6150 B, Parker Legris 1/4, Rectus 23, TST 024 Atlas Copco QIC 08, US MIL 4109 1/4
- Coupling Gender: Male
- Manufacturer Series: 23
- Connection Type: Hose Barb
- Hose Barb Connection: 10 mm
- Material: Brass
- Thread Gender: Male
- Maximum Operating Pressure: 35 bar



6671888 CEJN 310,

RS PRO BRASS FEMALE PNEUMATIC QUICK CONNECT COUPLING, G 1/2

ขนาดบรรจุภัณฑ์: **1 x EA**

- Connection Standard: CEJN 310, Forster, Hansen 3000, ISO 6150 B, Parker Legris 1/4, Rectus 23, TST 024 Atlas Copco QIC 08, US MIL 4109 1/4
- Coupling Gender: Female
- Threaded Connection: G 1/2 Female
- Manufacturer Series: 23
- Connection Type: Threaded
- Thread Size: 1/2 in
- Material: Brass
- Thread Gender: Female



6671894 CEJN 310,

RS PRO BRASS MALE PNEUMATIC QUICK CONNECT COUPLING, 6MM

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Connection Standard: CEJN 310, Forster, Hansen 3000, ISO 6150 B, Parker Legris 1/4, Rectus 23, TST 024 Atlas Copco QIC 08, US MIL 4109 1/4
 - Coupling Gender: Male
 - Manufacturer Series: 23
 - Connection Type: Hose Barb
 - Hose Barb Connection: 6 mm
 - Material: Brass
 - Thread Gender: Male
 - Maximum Operating Pressure: 35 bar



6671897 CEJN 310,

FEMALE THREAD PLUG G 1/4"

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Connection Standard: CEJN 310, Forster, Hansen 3000, ISO 6150 B, Parker Legris 1/4, Rectus 23, TST 024 Atlas Copco QIC 08, US MIL 4109 1/4
 - Coupling Gender: Female
 - Threaded Connection: G 1/4 Female
 - Manufacturer Series: 23
 - Connection Type: Threaded
 - Thread Size: 1/8 in
 - Material: Brass
 - Thread Gender: Female



6671904 CEJN 310,

MALE THREAD PLUG G1/4"

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Connection Standard: CEJN 310, Dynaquip DC3, ISO 6150B, Rectus 23 & 24, US MIL C4109 1/4
 - Coupling Gender: Male
 - Threaded Connection: G 1/4 Male
 - Manufacturer Series: 23
 - Connection Type: Threaded
 - Thread Size: 1/4 in
 - Material: Steel
 - Thread Gender: Male



6671908 CEJN 310,

FEMALE THRD COUPLER G 3/8

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Connection Standard: CEJN 320, JWL 520, JWL 530, Legris, Parker PEF, Rectus 25, Rectus 26, TST 026
 - Coupling Gender: Female
 - Threaded Connection: G 3/8 Female
 - Manufacturer Series: 25
 - Connection Type: Threaded
 - Thread Size: 3/8 in
 - Material: Steel
 - Thread Gender: Female



6671910 CEJN 320, JWL

FEMALE THRD COUPLER G 1/2

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Connection Standard: CEJN 320, JWL 520, JWL 530, Legris, Parker PEF, Rectus 25, Rectus 26, TST 026
 - Coupling Gender: Female
 - Threaded Connection: G 1/2 Female
 - Manufacturer Series: 25
 - Connection Type: Threaded
 - Thread Size: 1/2 in
 - Material: Steel
 - Thread Gender: Female



6671914 CEJN 320, JWL

FEMALE THRD COUPLER G 1/4

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Connection Standard: CEJN 320, JWL 520, JWL 530, Legris, Parker PEF, Rectus 25, Rectus 26, TST 026
 - Coupling Gender: Female
 - Threaded Connection: G 1/4 Female
 - Manufacturer Series: 25
 - Connection Type: Threaded
 - Thread Size: 1/4 in
 - Material: Steel
 - Thread Gender: Female



6671917 CEJN 320, JWL

STANDARD HOSE BARB COUPLER 10 MM 3/8"

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Connection Standard: CEJN 320, JWL 520, JWL 530, Legris, Parker PEF, Rectus 25, Rectus 26, TST 026
 - Coupling Gender: Male
 - Manufacturer Series: 25
 - Connection Type: Hose Barb
 - Hose Barb Connection: 10 mm
 - Material: Steel
 - Thread Gender: Male
 - Maximum Operating Pressure: 35 bar



6671920 CEJN 320, JWL

HOSE BARB COUPLER,6MM,1/4

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Connection Standard: CEJN 320, JWL 520, JWL 530, Legris, Parker PEF, Rectus 25, Rectus 26, TST 026
 - Coupling Gender: Male
 - Manufacturer Series: 25
 - Connection Type: Hose Barb
 - Hose Barb Connection: 6 mm
 - Material: Steel
 - Thread Gender: Male
 - Maximum Operating Pressure: 35 bar



6671923 CEJN 320, JWL

HOSEBARB COUPLER,8MM,5/16

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Connection Standard: CEJN 320, JWL 520, JWL 530, Legris, Parker PEF, Rectus 25, Rectus 26, TST 026
 - Coupling Gender: Male
 - Manufacturer Series: 25
 - Connection Type: Hose Barb
 - Hose Barb Connection: 8 mm
 - Material: Steel
 - Thread Gender: Male
 - Maximum Operating Pressure: 35 bar



6671926 CEJN 320, JWL

MALE THREAD COUPLER G 1/4

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Connection Standard: CEJN 320, JWL 520, JWL 530, Parker PEF, Rectus 25, Rectus 26, TST 026
 - Coupling Gender: Male
 - Threaded Connection: G 1/4 Male
 - Manufacturer Series: 25
 - Connection Type: Threaded
 - Thread Size: 1/4 in
 - Material: Brass, Steel
 - Thread Gender: Male



6671932 CEJN 320, JWL

STANDARD HOSE BARB COUPLER 13 MM 1/2"

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Connection Standard: CEJN 320, JWL 520, JWL 530, Legris, Parker PEF, Rectus 25, Rectus 26, TST 026
 - Coupling Gender: Male
 - Manufacturer Series: 25
 - Connection Type: Hose Barb
 - Hose Barb Connection: 13 mm
 - Material: Steel
 - Thread Gender: Male
 - Maximum Operating Pressure: 35 bar



6671939 CEJN 320, JWL

MALE THREAD PLUG G1/4"

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Connection Standard: CEJN 320, JWL 520, JWL 530, Parker PEF, Rectus 25, Rectus 26, TST 026
 - Coupling Gender: Male
 - Threaded Connection: G 3/8 Male
 - Manufacturer Series: 25
 - Connection Type: Threaded
 - Thread Size: 3/8 in
 - Material: Brass, Steel
 - Thread Gender: Male



6671942 CEJN 320, JWL

MALE THREAD COUPLER R 1/2

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Connection Standard: CEJN 320, JWL 520, JWL 530, Parker PEF, Rectus 25, Rectus 26, TST 026
 - Coupling Gender: Male
 - Threaded Connection: G 1/2 Male
 - Manufacturer Series: 25
 - Connection Type: Threaded
 - Thread Size: 1/2 in
 - Material: Brass, Steel
 - Thread Gender: Male



6671945 CEJN 320, JWL

MALE THREAD PLUG G 1/8"

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Connection Standard: CEJN 320, JWL 520, JWL 530, Parker PEF, Rectus 25, Rectus 26, TST 026
 - Coupling Gender: Male
 - Threaded Connection: G 1/4 Male
 - Manufacturer Series: 25
 - Connection Type: Threaded
 - Thread Size: 1/4 in
 - Material: Brass, Steel
 - Thread Gender: Male



6671948 CEJN 320, JWL

MALE THREAD PLUG R1/2"

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Connection Standard: CEJN 320, JWL 520, JWL 530, Parker PEF, Rectus 25, Rectus 26, TST 026
 - Coupling Gender: Male
 - Threaded Connection: G 1/2 Male
 - Manufacturer Series: 25
 - Connection Type: Threaded
 - Thread Size: 1/2 in
 - Material: Brass, Steel
 - Thread Gender: Male



6671951 CEJN 320, JWL

HOSE BARB PLUG 6MM 1/4"

- ขนาดบรรจุภัณฑ์: **5 x EA**
- Connection Standard: CEJN 320, JWL 520, JWL 530, Legris, Parker PEF, Rectus 25, Rectus 26, TST 026
 - Coupling Gender: Male
 - Manufacturer Series: 25
 - Connection Type: Hose Barb
 - Hose Barb Connection: 6 mm
 - Material: Steel
 - Thread Gender: Male
 - Maximum Operating Pressure: 35 bar



6671954 CEJN 320, JWL

HOSE BARB PLUG 13MM, 1/2"

ขนาดบรรจุภัณฑ์: **5 x EA**

- Connection Standard: CEJN 320, JWL 520, JWL 530, Legris, Parker PEF, Rectus 25, Rectus 26, TST 026
- Coupling Gender: Male
- Manufacturer Series: 25
- Connection Type: Hose Barb
- Hose Barb Connection: 13 mm
- Material: Steel
- Thread Gender: Male
- Maximum Operating Pressure: 35 bar



6671960 CEJN 320, JWL

FEMALE PLUG, G 1/4 IN.

ขนาดบรรจุภัณฑ์: **5 x EA**

- Connection Standard: CEJN 320, JWL 520, JWL 530, Legris, Parker PEF, Rectus 25, Rectus 26, TST 026
- Coupling Gender: Male
- Threaded Connection: G 1/4 Female
- Manufacturer Series: 25
- Connection Type: Threaded
- Thread Size: 1/4 in
- Material: Steel
- Thread Gender: Female



6671964 CEJN 320, JWL

HOSE BARB PLUG 10MM 3/8"

ขนาดบรรจุภัณฑ์: **5 x EA**

- Connection Standard: CEJN 320, JWL 520, JWL 530, Legris, Parker PEF, Rectus 25, Rectus 26, TST 026
- Coupling Gender: Male
- Manufacturer Series: 25
- Connection Type: Hose Barb
- Hose Barb Connection: 10 mm
- Material: Steel
- Thread Gender: Male
- Maximum Operating Pressure: 35 bar



6671967 CEJN 320, JWL

FEMALE COUPLER, G 1/4 IN.

ขนาดบรรจุภัณฑ์: **1 x EA**

- Connection Standard: CEJN 320, JWL 520, JWL 530, Parker PE, Rectus 25, Rectus 26, TST 025
- Coupling Gender: Female
- Threaded Connection: G 1/4 Female
- Manufacturer Series: 26
- Connection Type: Threaded
- Thread Size: 1/4 in
- Material: Brass
- Thread Gender: Female



6671970 CEJN 320, JWL

FEMALE PLUG, G 1/2 IN.

ขนาดบรรจุภัณฑ์: **5 x EA**

- Connection Standard: CEJN 320, JWL 520, JWL 530, Legris, Parker PEF, Rectus 25, Rectus 26, TST 026
- Coupling Gender: Male
- Threaded Connection: G 1/2 Female
- Manufacturer Series: 25
- Connection Type: Threaded
- Thread Size: 1/2 in
- Material: Steel
- Thread Gender: Female



6671976 CEJN 320, JWL

RS PRO BRASS FEMALE PNEUMATIC QUICK CONNECT COUPLING, G 1/2

ขนาดบรรจุภัณฑ์: **1 x EA**

- Connection Standard: CEJN 320, JWL 520, JWL 530, Parker PE, Rectus 25, Rectus 26, TST 025
- Coupling Gender: Female
- Threaded Connection: G 1/2 Female
- Manufacturer Series: 26
- Connection Type: Threaded
- Thread Size: 1/2 in
- Material: Brass
- Thread Gender: Female



6671982 CEJN 320, JWL

MALE THREAD COUPLER R 1/2"

ขนาดบรรจุภัณฑ์: **1 x EA**

- Connection Standard: CEJN 320, JWL 520, JWL 530, Parker PE, Rectus 25, Rectus 26, TST 025
- Coupling Gender: Male
- Threaded Connection: G 1/2 Male
- Manufacturer Series: 26
- Connection Type: Threaded
- Thread Size: 1/2 in
- Material: Brass
- Thread Gender: Male



6671992 CEJN 320, JWL

MALE THREAD COUPLER G 1/4"

ขนาดบรรจุภัณฑ์: **1 x EA**

- Connection Standard: CEJN 320, JWL 520, JWL 530, Parker PE, Rectus 25, Rectus 26, TST 025
- Coupling Gender: Female
- Threaded Connection: G 1/4 Male
- Manufacturer Series: 26
- Connection Type: Threaded
- Thread Size: 1/4 in
- Material: Brass
- Thread Gender: Male



6671995 CEJN 320, JWL

RS PRO BRASS FEMALE PNEUMATIC QUICK CONNECT COUPLING, G 1/2

ขนาดบรรจุภัณฑ์: **1 x EA**

- Connection Standard: CEJN 410, Rectus 27, TST 410
- Coupling Gender: Female
- Threaded Connection: G 1/2 Female
- Manufacturer Series: 27
- Connection Type: Threaded
- Thread Size: 1/2 in
- Material: Brass
- Thread Gender: Female



6672027 CEJN 410, Rectus

MALE THREAD PLUG G 1/2"

ขนาดบรรจุภัณฑ์: **1 x EA**

- Connection Standard: CEJN 410, Rectus 27, TST 410
- Coupling Gender: Male
- Threaded Connection: G 1/2 Male
- Manufacturer Series: 27
- Connection Type: Threaded
- Thread Size: 1/2 in
- Material: Brass
- Thread Gender: Male



6672036 CEJN 410, Rectus

RS PRO BRASS MALE PNEUMATIC QUICK CONNECT COUPLING, G 1/4

ขนาดบรรจุภัณฑ์: **1 x EA**

- Connection Standard: CEJN 410, Rectus 27, TST 410
- Coupling Gender: Male
- Threaded Connection: G 1/4 Male
- Manufacturer Series: 27
- Connection Type: Threaded
- Thread Size: 1/4 in
- Material: Brass
- Thread Gender: Male



6672049 CEJN 410, Rectus

RS PRO STEEL FEMALE PNEUMATIC QUICK CONNECT COUPLING, RP 1/4

ขนาดบรรจุภัณฑ์: **1 x EA**

- Connection Standard: PCL
- Coupling Gender: Female
- Threaded Connection: Rp 1/4 Female
- Manufacturer Series: AA
- Connection Type: Threaded
- Thread Size: 1/4 in
- Material: Steel
- Thread Gender: Female



7768340 PCL

RS PRO STEEL MALE PNEUMATIC QUICK CONNECT COUPLING, G 1/4

ขนาดบรรจุภัณฑ์: **1 x EA**

- Connection Standard: PCL
- Coupling Gender: Male
- Threaded Connection: G 1/4 Male
- Manufacturer Series: AA
- Connection Type: Threaded
- Thread Size: 1/4 in
- Material: Steel
- Thread Gender: Male



7768343 PCL

RS PRO STEEL FEMALE PNEUMATIC QUICK CONNECT COUPLING, RP 1/4

ขนาดบรรจุภัณฑ์: **1 x EA**

- Connection Standard: PCL
- Coupling Gender: Female
- Threaded Connection: Rp 1/4 Female
- Manufacturer Series: AC
- Connection Type: Threaded
- Thread Size: 1/4 in
- Material: Steel
- Thread Gender: Female



7768352 PCL

RS PRO QUICK EXHAUST VALVE, R 1/8 IN FEMALE X 10 BAR, THREADED

ขนาดบรรจุภัณฑ์: **10 x EA**

- Connection Type: Threaded
- Threaded Connections: R 1/8 in Female
- Built-In Silencer: Yes
- Threaded Connection - Gender: Female
- Threaded Connection Size: 1/8 in
- Minimum Operating Pressure: 0.3 bar
- Threaded Connection Type: R
- Maximum Operating Pressure: 10 bar



1762258 Threaded

RS PRO QUICK EXHAUST VALVE, R 1/4 IN FEMALE X 10 BAR, THREADED

ขนาดบรรจุภัณฑ์: **10 x EA**

- Connection Type: Threaded
- Threaded Connections: R 1/4 in Female
- Built-In Silencer: Yes
- Threaded Connection - Gender: Female
- Threaded Connection Size: 1/4 in
- Minimum Operating Pressure: 0.3 bar
- Threaded Connection Type: R
- Maximum Operating Pressure: 10 bar



1762259 Threaded

RS PRO QUICK EXHAUST VALVE, R 3/8 IN FEMALE X 10 BAR, THREADED

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Connection Type: Threaded
 - Threaded Connections: R 3/8 in Female
 - Built-In Silencer: Yes
 - Threaded Connection - Gender: Female
 - Threaded Connection Size: 3/8 in
 - Minimum Operating Pressure: 0.3 bar
 - Threaded Connection Type: R
 - Maximum Operating Pressure: 10 bar



1762261 Threaded

RS PRO QUICK EXHAUST VALVE, R 1/2 IN FEMALE X 10 BAR, THREADED

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Connection Type: Threaded
 - Threaded Connections: R 1/2 in Female
 - Built-In Silencer: Yes
 - Threaded Connection - Gender: Female
 - Threaded Connection Size: 1/2 in
 - Minimum Operating Pressure: 0.3 bar
 - Threaded Connection Type: R
 - Maximum Operating Pressure: 10 bar



1762262 Threaded

RS PRO G 1/4 REGULATOR -, 1/4IN, 8BAR MAX. INPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Port Connection: G 1/4
 - Maximum Input Pressure: 8 bar
 - Pressure Gauge Port Size: 1/4 in
 - Port Connection Thread Size: 1/4 in
 - Pressure Gauge Port Thread Size: 1/8 in
 - Maximum Flow Rate: 2050 NL/min
 - Port Connection Thread Standard: G
 - Minimum Operating Temperature: -10 °C



1761723 G 1/4

RS PRO G 1/2 REGULATOR -, 1/2IN, 8BAR MAX. INPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Port Connection: G 1/2
 - Maximum Input Pressure: 8 bar
 - Pressure Gauge Port Size: 1/2 in
 - Port Connection Thread Size: 1/2 in
 - Pressure Gauge Port Thread Size: 1/8 in
 - Maximum Flow Rate: 3200 NL/min
 - Port Connection Thread Standard: G
 - Minimum Operating Temperature: -10 °C



1761725 G 1/2

RS PRO G 1/8 REGULATOR - 0BAR TO 12BAR, 1/8IN, 15BAR MAX. INPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Port Connection: G 1/8
 - Minimum Outlet Pressure: 0 bar
 - Maximum Outlet Pressure: 12 bar
 - Maximum Input Pressure: 15 bar
 - Manufacturer Series: T020-MINI
 - Pressure Gauge Port Size: G 1/8
 - Port Connection Thread Size: 1/8 in
 - Pressure Gauge Port Thread Size: 1/8 in



1977902 G 1/8

RS PRO G 1/4 REGULATOR - 0BAR TO 12BAR, 1/4IN, 15BAR MAX. INPUT

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Port Connection: G 1/4
 - Minimum Outlet Pressure: 0 bar
 - Maximum Outlet Pressure: 12 bar
 - Maximum Input Pressure: 15 bar
 - Manufacturer Series: T020-MINI
 - Pressure Gauge Port Size: G 1/8
 - Port Connection Thread Size: 1/4 in
 - Pressure Gauge Port Thread Size: 1/8 in



1977903 G 1/4

RS PRO G 1/4 REGULATOR - 0BAR TO 8BAR

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Port Connection: G 1/4
 - Minimum Outlet Pressure: 0 bar
 - Maximum Outlet Pressure: 8 bar
 - Manufacturer Series: T080 Mini



2312782 G 1/4

RS PRO G 1/4 PNEUMATIC REGULATOR - 0.3BAR TO 10BAR,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Port Connection: G 1/4
 - Minimum Outlet Pressure: 0.3 bar
 - Maximum Outlet Pressure: 10 bar
 - Maximum Input Pressure: 15 bar
 - Manufacturer Series: ER



2351139 G 1/4

RS PRO PNEUMATIC REGULATOR - 0.02BAR TO 0.5BAR, 8BAR MAX.

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Minimum Outlet Pressure: 0.02 bar
 - Maximum Outlet Pressure: 0.5 bar
 - Maximum Input Pressure: 8 bar



2354733 0.02 bar

RS PRO PNEUMATIC REGULATOR - 0.5BAR TO 8.5BAR, 10BAR MAX.

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Minimum Outlet Pressure: 0.5 bar
 - Maximum Outlet Pressure: 8.5 bar
 - Maximum Input Pressure: 10 bar



2354738 0.5 bar

RS PRO PNEUMATIC REGULATOR - 0.5BAR TO 8.5BAR, 10BAR MAX.

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Minimum Outlet Pressure: 0.5 bar
 - Maximum Outlet Pressure: 8.5 bar
 - Maximum Input Pressure: 10 bar



2354741 0.5 bar

RS PRO MAGNETIC PROXIMITY SWITCH, FVBC SERIES, FOR USE WITH

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Manufacturer Series: FVBC
 - Accessory Type: Magnetic Proximity Switch
 - For Use With: Pneumatic Cylinders



2351167 FVBC

RS PRO STAINLESS STEEL 10BAR PNEUMATIC SILENCER, THREADED

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Type: Silencer
 - Inlet Connection Type: Threaded
 - Maximum Input Pressure: 10 bar
 - Material: Stainless Steel
 - Minimum Operating Temperature: -20 °C
 - Threaded Inlet Connection Thread Gender: Male
 - Maximum Operating Temperature: +300 °C
 - Threaded Inlet Connection Thread Size: 3.175 mm



1762220 Silencer

RS PRO STAINLESS STEEL 10BAR PNEUMATIC SILENCER, THREADED

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Type: Silencer
 - Inlet Connection Type: Threaded
 - Maximum Input Pressure: 10 bar
 - Material: Stainless Steel
 - Minimum Operating Temperature: -20 °C
 - Threaded Inlet Connection Thread Gender: Male
 - Maximum Operating Temperature: +300 °C
 - Threaded Inlet Connection Thread Size: 6.35 mm



1762221 Silencer

RS PRO BRASS 10BAR PNEUMATIC SILENCER, THREADED, 3/8 IN MALE

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Type: Silencer
 - Inlet Connection Type: Threaded
 - Threaded Inlet Connection: 3/8 in Male
 - Maximum Input Pressure: 10 bar
 - Material: Brass
 - Minimum Operating Temperature: -10 °C
 - Threaded Inlet Connection Thread Gender: Male
 - Maximum Operating Temperature: +80 °C



1762275 Silencer

RS PRO BRASS 10BAR PNEUMATIC SILENCER, THREADED, 1/2 IN MALE

- ขนาดบรรจุภัณฑ์: **10 x EA**
- Type: Silencer
 - Inlet Connection Type: Threaded
 - Threaded Inlet Connection: 1/2 in Male
 - Maximum Input Pressure: 10 bar
 - Material: Brass
 - Minimum Operating Temperature: -10 °C
 - Threaded Inlet Connection Thread Gender: Male
 - Maximum Operating Temperature: +80 °C



1762277 Silencer

RS PRO BRASS 12BAR PNEUMATIC SILENCER, THREADED, 1/4 IN MALE

- ขนาดบรรจุภัณฑ์: 10 x EA
- Type: Silencer
 - Inlet Connection Type: Threaded
 - Threaded Inlet Connection: 1/4 in Male
 - Maximum Input Pressure: 12 bar
 - Material: Brass
 - Minimum Operating Temperature: -10 °C
 - Threaded Inlet Connection Thread Gender: Male
 - Maximum Operating Temperature: +80 °C



1762280 Silencer

RS PRO BRASS 12BAR PNEUMATIC SILENCER, THREADED, 3/8 IN MALE

- ขนาดบรรจุภัณฑ์: 10 x EA
- Type: Silencer
 - Inlet Connection Type: Threaded
 - Threaded Inlet Connection: 3/8 in Male
 - Maximum Input Pressure: 12 bar
 - Material: Brass
 - Minimum Operating Temperature: -10 °C
 - Threaded Inlet Connection Thread Gender: Male
 - Maximum Operating Temperature: +80 °C



1762281 Silencer

RS PRO BRASS 12BAR PNEUMATIC SILENCER, THREADED, 1/2 IN MALE

- ขนาดบรรจุภัณฑ์: 10 x EA
- Type: Silencer
 - Inlet Connection Type: Threaded
 - Threaded Inlet Connection: 1/2 in Male
 - Maximum Input Pressure: 12 bar
 - Material: Brass
 - Minimum Operating Temperature: -10 °C
 - Threaded Inlet Connection Thread Gender: Male
 - Maximum Operating Temperature: +80 °C



1762282 Silencer

RS PRO BRASS 12BAR PNEUMATIC SILENCER, THREADED, 1/8 IN MALE

- ขนาดบรรจุภัณฑ์: 10 x EA
- Type: Silencer
 - Inlet Connection Type: Threaded
 - Threaded Inlet Connection: 1/8 in Male
 - Maximum Input Pressure: 12 bar
 - Material: Brass
 - Minimum Operating Temperature: -10 °C
 - Threaded Inlet Connection Thread Gender: Male
 - Maximum Operating Temperature: +80 °C



1762283 Silencer

RS PRO BRASS 12BAR PNEUMATIC SILENCER, THREADED, 1/4 IN MALE

- ขนาดบรรจุภัณฑ์: 10 x EA
- Type: Silencer
 - Inlet Connection Type: Threaded
 - Threaded Inlet Connection: 1/4 in Male
 - Maximum Input Pressure: 12 bar
 - Material: Brass
 - Minimum Operating Temperature: -10 °C
 - Threaded Inlet Connection Thread Gender: Male
 - Maximum Operating Temperature: +80 °C



1762284 Silencer

RS PRO 10BAR PNEUMATIC SILENCER, THREADED, M5 MALE

- ขนาดบรรจุภัณฑ์: 10 x EA
- Type: Silencer
 - Inlet Connection Type: Threaded
 - Threaded Inlet Connection: M5 Male
 - Maximum Input Pressure: 10 bar
 - Minimum Operating Temperature: -15 °C
 - Threaded Inlet Connection Thread Gender: Male
 - Maximum Operating Temperature: +100 °C
 - Threaded Inlet Connection Thread Standard: Metric



1762287 Silencer

RS PRO 10BAR PNEUMATIC SILENCER, THREADED

- ขนาดบรรจุภัณฑ์: 10 x EA
- Type: Silencer
 - Inlet Connection Type: Threaded
 - Maximum Input Pressure: 10 bar
 - Minimum Operating Temperature: -15 °C
 - Threaded Inlet Connection Thread Gender: Male
 - Maximum Operating Temperature: +100 °C
 - Threaded Inlet Connection Thread Size: G 1/8 Male



1762288 Silencer

RS PRO 10BAR PNEUMATIC SILENCER, THREADED

- ขนาดบรรจุภัณฑ์: 10 x EA
- Type: Silencer
 - Inlet Connection Type: Threaded
 - Maximum Input Pressure: 10 bar
 - Minimum Operating Temperature: -15 °C
 - Threaded Inlet Connection Thread Gender: Male
 - Maximum Operating Temperature: +100 °C
 - Threaded Inlet Connection Thread Size: G 1/4 Male



1762289 Silencer

RS PRO 10BAR PNEUMATIC SILENCER, THREADED

- ขนาดบรรจุภัณฑ์: 10 x EA
- Type: Silencer
 - Inlet Connection Type: Threaded
 - Maximum Input Pressure: 10 bar
 - Minimum Operating Temperature: -15 °C
 - Threaded Inlet Connection Thread Gender: Male
 - Maximum Operating Temperature: +100 °C
 - Threaded Inlet Connection Thread Size: G 3/8 Male



1762290 Silencer

RS PRO 10BAR PNEUMATIC SILENCER, THREADED

- ขนาดบรรจุภัณฑ์: 10 x EA
- Type: Silencer
 - Inlet Connection Type: Threaded
 - Maximum Input Pressure: 10 bar
 - Minimum Operating Temperature: -15 °C
 - Threaded Inlet Connection Thread Gender: Male
 - Maximum Operating Temperature: +100 °C
 - Threaded Inlet Connection Thread Size: G1/2 Male



1762291 Silencer

RS PRO BRASS 10BAR PNEUMATIC SILENCER, THREADED, 1/8 IN MALE

- ขนาดบรรจุภัณฑ์: 10 x EA
- Type: Silencer
 - Inlet Connection Type: Threaded
 - Threaded Inlet Connection: 1/8 in Male
 - Maximum Input Pressure: 10 bar
 - Material: Brass
 - Minimum Operating Temperature: -20 °C
 - Threaded Inlet Connection Thread Gender: Male
 - Maximum Operating Temperature: +150 °C



1762294 Silencer

RS PRO PSU PLASTIC PNEUMATIC SILENCER, THREADED, 1/8 IN MALE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Manufacturer Series: PSU
 - Type: Muffler
 - Inlet Connection Type: Threaded
 - Threaded Inlet Connection: 1/8 in Male
 - Material: Plastic



2351217 PSU

RS PRO PSU PLASTIC PNEUMATIC SILENCER, THREADED, 1/4 IN MALE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Manufacturer Series: PSU
 - Type: Muffler
 - Inlet Connection Type: Threaded
 - Threaded Inlet Connection: 1/4 in Male
 - Material: Plastic



2351218 PSU

RS PRO PSU PLASTIC PNEUMATIC SILENCER, THREADED, 1/2 IN MALE

- ขนาดบรรจุภัณฑ์: 1 x EA
- Manufacturer Series: PSU
 - Type: Muffler
 - Inlet Connection Type: Threaded
 - Threaded Inlet Connection: 1/2 in Male
 - Material: Plastic



2351219 PSU

RS PRO PE 10BAR PNEUMATIC SILENCER, THREADED, G 1/2 MALE, G

- ขนาดบรรจุภัณฑ์: 1 x KT
- Type: Silencer
 - Inlet Connection Type: Threaded
 - Threaded Inlet Connection: G 1/2 Male, G 1/4 Male, G 1/8 Male, G 3/4 Male, G 3/8 Male, M5 Male
 - Maximum Input Pressure: 10 bar
 - Material: PE
 - Minimum Operating Temperature: -10 °C
 - Threaded Inlet Connection Thread Gender: Male
 - Maximum Operating Temperature: +80 °C



7444517 Silencer

RS PRO 3/2 NORMALLY CLOSED PNEUMATIC SOLENOID VALVE -

- ขนาดบรรจุภัณฑ์: 1 x EA
- Mounting Style: Base Mount
 - Function: 3/2 Normally Closed
 - Connection Port Thread: G 1/4
 - Actuation Type: Pneumatic
 - Body Material: Aluminium
 - Maximum Flow Rate: 1200 NL/min
 - Minimum Operating Pressure: 2 bar
 - Minimum Operating Temperature: -10 °C



1762104 Base Mount

RS PRO 3/2 NORMALLY CLOSED PNEUMATIC SOLENOID VALVE -

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Mounting Style: Base Mount
 - Function: 3/2 Normally Closed
 - Connection Port Thread: G 1/2
 - Actuation Type: Pneumatic
 - Body Material: Aluminium
 - Maximum Flow Rate: 5000 NL/min
 - Minimum Operating Pressure: 2 bar
 - Minimum Operating Temperature: -10 °C



1762105 Base Mount

RS PRO 5/2 MONOSTABLE PNEUMATIC SOLENOID VALVE -

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Mounting Style: Base Mount
 - Function: 5/2 Monostable
 - Connection Port Thread: G 1/4
 - Actuation Type: Pneumatic
 - Body Material: Aluminium
 - Maximum Flow Rate: 1200 NL/min
 - Minimum Operating Pressure: 2 bar
 - Minimum Operating Temperature: -10 °C



1762107 Base Mount

RS PRO 5/2 BISTABLE PNEUMATIC SOLENOID VALVE - PNEUMATIC G 1/4

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Mounting Style: Base Mount
 - Function: 5/2 Bistable
 - Connection Port Thread: G 1/4
 - Actuation Type: Pneumatic
 - Body Material: Aluminium
 - Maximum Flow Rate: 1200 NL/min
 - Minimum Operating Pressure: 1 bar
 - Minimum Operating Temperature: -10 °C



1762110 Base Mount

RS PRO 3/2 NORMALLY CLOSED PNEUMATIC SOLENOID VALVE -

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Mounting Style: Base Mount
 - Function: 3/2 Normally Closed
 - Connection Port Thread: G 1/8
 - Actuation Type: Solenoid
 - Solenoid Fitted: Yes
 - Body Material: Aluminium
 - Maximum Flow Rate: 740 NL/min
 - Solenoid Voltage: 12 V dc, 24 V ac/dc, 110 V ac, 220 V ac



1762112 Base Mount

RS PRO 3/2 NORMALLY CLOSED PNEUMATIC SOLENOID VALVE -

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Mounting Style: Base Mount
 - Function: 3/2 Normally Closed
 - Connection Port Thread: G 1/4
 - Actuation Type: Solenoid
 - Solenoid Fitted: Yes
 - Body Material: Aluminium
 - Maximum Flow Rate: 1200 NL/min
 - Solenoid Voltage: 12 V dc, 24 V ac/dc, 110 V ac, 220 V ac



1762113 Base Mount

RS PRO 5/2 MONOSTABLE PNEUMATIC SOLENOID VALVE -

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Mounting Style: Base Mount
 - Function: 5/2 Monostable
 - Connection Port Thread: G 1/8
 - Actuation Type: Solenoid
 - Solenoid Fitted: No
 - Body Material: Aluminium
 - Maximum Flow Rate: 740 NL/min
 - Solenoid Power Consumption: 2 W, 3 VA



1762115 Base Mount

RS PRO 5/2 MONOSTABLE PNEUMATIC SOLENOID VALVE -

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Mounting Style: Base Mount
 - Function: 5/2 Monostable
 - Connection Port Thread: G 1/2
 - Actuation Type: Solenoid
 - Solenoid Fitted: Yes
 - Body Material: Aluminium
 - Maximum Flow Rate: 5000 NL/min
 - Solenoid Voltage: 12 V dc, 24 V ac/dc, 110 V ac, 220 V ac



1762117 Base Mount

RS PRO 5/3 NORMALLY CLOSED PNEUMATIC SOLENOID VALVE -

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Mounting Style: Base Mount
 - Function: 5/3 Normally Closed
 - Connection Port Thread: G 1/4
 - Actuation Type: Solenoid
 - Solenoid Fitted: Yes
 - Body Material: Aluminium
 - Maximum Flow Rate: 1200 NL/min
 - Solenoid Voltage: 12 V dc, 24 V ac/dc, 110 V ac, 220 V ac



1762120 Base Mount

RS PRO 5/2 BISTABLE PNEUMATIC SOLENOID VALVE - SOLENOID G 1/8 12

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Mounting Style: Base Mount
 - Function: 5/2 Bistable
 - Connection Port Thread: G 1/8
 - Actuation Type: Solenoid
 - Solenoid Fitted: Yes
 - Body Material: Aluminium
 - Maximum Flow Rate: 740 NL/min
 - Solenoid Voltage: 12 V dc, 24 V ac/dc, 110 V ac, 220 V ac



1762125 Base Mount

RS PRO 5/2 BISTABLE PNEUMATIC SOLENOID VALVE - SOLENOID G 1/4 12

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Mounting Style: Base Mount
 - Function: 5/2 Bistable
 - Connection Port Thread: G 1/4
 - Actuation Type: Solenoid
 - Solenoid Fitted: Yes
 - Body Material: Aluminium
 - Maximum Flow Rate: 1200 NL/min
 - Solenoid Voltage: 12 V dc, 24 V ac/dc, 110 V ac, 220 V ac



1762126 Base Mount

RS PRO 5/2 MONOSTABLE PNEUMATIC SOLENOID VALVE -

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Mounting Style: Base Mount
 - Function: 5/2 Monostable
 - Connection Port Thread: G 1/4
 - Actuation Type: Solenoid
 - Solenoid Fitted: Yes
 - Body Material: Aluminium
 - Maximum Flow Rate: 1200 NL/min
 - Solenoid Voltage: 12 V dc, 24 V ac/dc, 110 V ac, 220 V ac



1762132 Base Mount

RS PRO 5/2 PNEUMATIC SOLENOID VALVE - SOLENOID/SPRING G 1/4

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Manufacturer Series: MNH
 - Mounting Style: NAMUR
 - Function: 5/2
 - Connection Port Thread: G 1/4
 - Actuation Type: Solenoid/Spring
 - Solenoid Fitted: Yes
 - Maximum Flow Rate: 1250 L/min
 - Solenoid Voltage: 12 V dc, 24 V dc, 110 V ac, 230 V ac



7840044 MNH

RS PRO 3/2 PNEUMATIC SOLENOID VALVE - SOLENOID/SPRING G 1/8

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Manufacturer Series: MDS
 - Mounting Style: Free standing
 - Function: 3/2
 - Connection Port Thread: G 1/8
 - Actuation Type: Solenoid/Spring
 - Solenoid Fitted: Yes
 - Maximum Flow Rate: 450 L/min
 - Solenoid Voltage: 24 V dc



7840048 MDS

RS PRO PNEUMATIC SOLENOID VALVE - SOLENOID/AIR G 1/8 V50 SERIES

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Manufacturer Series: V50
 - Mounting Style: Inline, Manifold
 - Connection Port Thread: G 1/8
 - Actuation Type: Solenoid/Air
 - Body Material: Die Cast Aluminium
 - Maximum Flow Rate: 480 L/min
 - Solenoid Voltage: 24 V dc
 - Solenoid Power Consumption: 2.9 W



9076374 V50

RS PRO PNEUMATIC SOLENOID VALVE - SOLENOID/SOLENOID G 1/4 V51

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Manufacturer Series: V51
 - Mounting Style: Inline, Manifold
 - Connection Port Thread: G 1/4
 - Actuation Type: Solenoid/Solenoid
 - Body Material: Die Cast Aluminium
 - Maximum Flow Rate: 1020 L/min
 - Solenoid Voltage: 24 V dc
 - Solenoid Power Consumption: 2 W



9076380 V51

RS PRO PNEUMATIC SOLENOID VALVE - SOLENOID/AIR G 1/8 V50 SERIES

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Manufacturer Series: V50
 - Mounting Style: Inline, Manifold
 - Connection Port Thread: G 1/8
 - Actuation Type: Solenoid/Air
 - Body Material: Die Cast Aluminium
 - Maximum Flow Rate: 480 L/min
 - Solenoid Voltage: 24 V dc
 - Solenoid Power Consumption: 2.9 W



9076384 V50

RS PRO PNEUMATIC SOLENOID VALVE - SOLENOID/SPRING G 1/4 V51 SERIES

- ขนาดบรรจุภัณฑ์: 1 x EA
- Manufacturer Series: V51
 - Mounting Style: Inline, Manifold
 - Connection Port Thread: G 1/4
 - Actuation Type: Solenoid/Spring
 - Body Material: Die Cast Aluminium
 - Maximum Flow Rate: 1020 L/min
 - Solenoid Voltage: 24 V dc
 - Solenoid Power Consumption: 2 W



9076387 V51

RS PRO PNEUMATIC SOLENOID VALVE - SOLENOID/SPRING G 1/4 V51 SERIES

- ขนาดบรรจุภัณฑ์: 1 x EA
- Manufacturer Series: V51
 - Mounting Style: Inline, Manifold
 - Connection Port Thread: G 1/4
 - Actuation Type: Solenoid/Spring
 - Body Material: Die Cast Aluminium
 - Maximum Flow Rate: 1020 L/min
 - Solenoid Voltage: 24 V dc
 - Solenoid Power Consumption: 2 W



9076393 V51

RS PRO PNEUMATIC SOLENOID VALVE - SOLENOID/SPRING G 1/2 V53

- ขนาดบรรจุภัณฑ์: 1 x EA
- Manufacturer Series: V53
 - Mounting Style: Inline, Manifold
 - Connection Port Thread: G 1/2
 - Actuation Type: Solenoid/Spring
 - Body Material: Die Cast Aluminium
 - Maximum Flow Rate: 2480 L/min
 - Solenoid Voltage: 24 V dc
 - Solenoid Power Consumption: 2 W



9076396 V53

3/2 PILOT / SPRING OPERATED VALVE, G 1/8"

- ขนาดบรรจุภัณฑ์: 1 x EA
- Manufacturer Series: V50
 - Mounting Style: Inline, Manifold
 - Connection Port Thread: G 1/8
 - Actuation Type: Pilot/Spring
 - Body Material: Die Cast Aluminium
 - Maximum Flow Rate: 480 L/min
 - Minimum Operating Pressure: 0 bar
 - Minimum Operating Temperature: -5 °C



9076400 V50

RS PRO PNEUMATIC DISTRIBUTOR - PILOT/SPRING G 1/8 V50 SERIES

- ขนาดบรรจุภัณฑ์: 1 x EA
- Manufacturer Series: V50
 - Mounting Style: Inline, Manifold
 - Connection Port Thread: G 1/8
 - Actuation Type: Pilot/Spring
 - Body Material: Die Cast Aluminium
 - Maximum Flow Rate: 480 L/min
 - Minimum Operating Pressure: 0 bar
 - Minimum Operating Temperature: -5 °C



9076403 V50

RS PRO PNEUMATIC SOLENOID VALVE - PILOT/AIR G 1/8 V50 SERIES

- ขนาดบรรจุภัณฑ์: 1 x EA
- Manufacturer Series: V50
 - Mounting Style: Inline, Manifold
 - Connection Port Thread: G 1/8
 - Actuation Type: Pilot/Air
 - Body Material: Die Cast Aluminium
 - Maximum Flow Rate: 480 L/min
 - Minimum Operating Pressure: 0 bar
 - Minimum Operating Temperature: -5 °C



9076407 V50

RS PRO PNEUMATIC SOLENOID VALVE - PILOT/SPRING G 1/4 V51 SERIES

- ขนาดบรรจุภัณฑ์: 1 x EA
- Manufacturer Series: V51
 - Mounting Style: Inline, Manifold
 - Connection Port Thread: G 1/4
 - Actuation Type: Pilot/Spring
 - Body Material: Die Cast Aluminium
 - Maximum Flow Rate: 1020 L/min
 - Minimum Operating Pressure: 0 bar
 - Minimum Operating Temperature: -5 °C



9076416 V51

RS PRO PNEUMATIC SOLENOID VALVE - PILOT/SPRING G 1/4 V51 SERIES

- ขนาดบรรจุภัณฑ์: 1 x EA
- Manufacturer Series: V51
 - Mounting Style: Inline, Manifold
 - Connection Port Thread: G 1/4
 - Actuation Type: Pilot/Spring
 - Body Material: Die Cast Aluminium
 - Maximum Flow Rate: 1020 L/min
 - Minimum Operating Pressure: 0 bar
 - Minimum Operating Temperature: -5 °C



9076419 V51

RS PRO PNEUMATIC SOLENOID VALVE - PILOT/AIR G 1/2 V53 SERIES

- ขนาดบรรจุภัณฑ์: 1 x EA
- Manufacturer Series: V53
 - Mounting Style: Inline, Manifold
 - Connection Port Thread: G 1/2
 - Actuation Type: Pilot/Air
 - Body Material: Die Cast Aluminium
 - Maximum Flow Rate: 2480 L/min
 - Minimum Operating Pressure: 0 bar
 - Minimum Operating Temperature: -5 °C



9076422 V53

RS PRO RED ROUND PUSH BUTTON

- ขนาดบรรจุภัณฑ์: 1 x EA
- Push Button Colour: Red
 - Push Button Style: Round



7840060 Red

RS PRO 2.5M, PA RECOIL HOSE, WITH BSP 1/4" MALE CONNECTOR

- ขนาดบรรจุภัณฑ์: 1 x EA
- Connector: BSP 1/4" Male
 - Manufacturer Series: EC Series
 - Colour: Blue
 - Maximum Operating Length: 2.5 m
 - Tube Inside Diameter: 6 mm
 - Tube Outside Diameter: 8 mm
 - Material: PA



2020926 BSP 1/4" Male

RS PRO 2.5M, PA RECOIL HOSE, WITH BSP 1/4" MALE CONNECTOR

- ขนาดบรรจุภัณฑ์: 1 x EA
- Connector: BSP 1/4" Male
 - Manufacturer Series: EC Series
 - Colour: Red
 - Maximum Operating Length: 2.5 m
 - Tube Inside Diameter: 6 mm
 - Tube Outside Diameter: 8 mm
 - Material: PA



2020928 BSP 1/4" Male

RS PRO 5M, PA RECOIL HOSE, WITH BSP 1/4" MALE CONNECTOR

- ขนาดบรรจุภัณฑ์: 1 x EA
- Connector: BSP 1/4" Male
 - Manufacturer Series: EC Series
 - Colour: Blue
 - Maximum Operating Length: 5 m
 - Tube Inside Diameter: 6 mm
 - Tube Outside Diameter: 8 mm
 - Material: PA



2020929 BSP 1/4" Male

RS PRO 10M, PA RECOIL HOSE, WITH BSP 1/4" MALE CONNECTOR

- ขนาดบรรจุภัณฑ์: 1 x EA
- Connector: BSP 1/4" Male
 - Manufacturer Series: EC Series
 - Colour: Blue
 - Maximum Operating Length: 10 m
 - Tube Inside Diameter: 6 mm
 - Tube Outside Diameter: 8 mm
 - Material: PA



2020931 BSP 1/4" Male

RS PRO 10M, PA RECOIL HOSE, WITH BSP 1/4" MALE CONNECTOR

- ขนาดบรรจุภัณฑ์: 1 x EA
- Connector: BSP 1/4" Male
 - Manufacturer Series: EC Series
 - Colour: Red
 - Maximum Operating Length: 10 m
 - Tube Inside Diameter: 6 mm
 - Tube Outside Diameter: 8 mm
 - Material: PA



2020932 BSP 1/4" Male

RS PRO 2.5M, PA RECOIL HOSE, WITH BSP 1/4" MALE CONNECTOR

- ขนาดบรรจุภัณฑ์: 1 x EA
- Connector: BSP 1/4" Male
 - Manufacturer Series: EC Series
 - Colour: Red
 - Maximum Operating Length: 2.5 m
 - Tube Inside Diameter: 6 mm
 - Tube Outside Diameter: 8 mm
 - Material: PA



2020937 BSP 1/4" Male

RS PRO 5M, PA RECOIL HOSE, WITH BSP 1/4" MALE CONNECTOR

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Connector: BSP 1/4" Male
 - Manufacturer Series: EC Series
 - Colour: Blue
 - Maximum Operating Length: 5 m
 - Tube Inside Diameter: 8 mm
 - Tube Outside Diameter: 10 mm
 - Material: PA



2020938 BSP 1/4" Male

RS PRO 10M, PA RECOIL HOSE, WITH BSP 1/4" MALE CONNECTOR

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Connector: BSP 1/4" Male
 - Manufacturer Series: EC Series
 - Colour: Red
 - Maximum Operating Length: 10 m
 - Tube Inside Diameter: 8 mm
 - Tube Outside Diameter: 10 mm
 - Material: PA



2020941 BSP 1/4" Male

RS PRO 5M, PA RECOIL HOSE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Manufacturer Series: EC Series
 - Colour: Red
 - Maximum Operating Length: 5 m
 - Tube Inside Diameter: 9 mm
 - Tube Outside Diameter: 12 mm
 - Material: PA



2020945 EC Series

RS PRO 4M, POLYURETHANE RECOIL HOSE, WITH R 1/4" CONNECTOR

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Connector: R 1/4"
 - Manufacturer Series: USB
 - Colour: Red
 - Maximum Operating Length: 4 m
 - Tube Inside Diameter: 5 mm
 - Tube Outside Diameter: 8 mm
 - Material: Polyurethane
 - Maximum Operating Pressure: 12 bar



7005649 R 1/4"

RS PRO 4M, POLYURETHANE RECOIL HOSE, WITH R 1/4" CONNECTOR

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Connector: R 1/4"
 - Manufacturer Series: USB
 - Colour: Yellow
 - Maximum Operating Length: 4 m
 - Tube Inside Diameter: 5 mm
 - Tube Outside Diameter: 8 mm
 - Material: Polyurethane
 - Maximum Operating Pressure: 12 bar



7005651 R 1/4"

RS PRO 4M, POLYURETHANE RECOIL HOSE, WITH R 1/4" CONNECTOR

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Connector: R 1/4"
 - Manufacturer Series: USB
 - Colour: Blue
 - Maximum Operating Length: 4 m
 - Tube Inside Diameter: 5 mm
 - Tube Outside Diameter: 8 mm
 - Material: Polyurethane
 - Maximum Operating Pressure: 12 bar



7005658 R 1/4"

RS PRO 3.6M, PA RECOIL HOSE, WITH R 1/4" CONNECTOR

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Connector: R 1/4"
 - Manufacturer Series: N6C
 - Colour: Red
 - Maximum Operating Length: 3.6 m
 - Tube Inside Diameter: 7.5 mm
 - Tube Outside Diameter: 10 mm
 - Material: PA
 - Maximum Operating Pressure: 18 bar



7005712 R 1/4"

RS PRO 3.6M, PA RECOIL HOSE, WITH R 1/4" CONNECTOR

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Connector: R 1/4"
 - Manufacturer Series: N6C
 - Colour: Blue
 - Maximum Operating Length: 3.6 m
 - Tube Inside Diameter: 7.5 mm
 - Tube Outside Diameter: 10 mm
 - Material: PA
 - Maximum Operating Pressure: 18 bar



7005721 R 1/4"

RS PRO 3.6M, PA RECOIL HOSE, WITH R 1/4" CONNECTOR

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Connector: R 1/4"
 - Manufacturer Series: N6C
 - Colour: Black
 - Maximum Operating Length: 3.6 m
 - Tube Inside Diameter: 7.5 mm
 - Tube Outside Diameter: 10 mm
 - Material: PA
 - Maximum Operating Pressure: 18 bar



7005724 R 1/4"

RS PRO 3.6M, PA RECOIL HOSE, WITH BSP 1/4" MALE CONNECTOR

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Connector: BSP 1/4" Male
 - Colour: Black
 - Maximum Operating Length: 3.6 m
 - Tube Inside Diameter: 8 mm
 - Tube Outside Diameter: 10 mm
 - Material: PA
 - Maximum Operating Pressure: 15 bar
 - Minimum Operating Temperature: -40 °C



9172321 BSP 1/4" Male

RS PRO 2M, POLYURETHANE RECOIL HOSE, WITH BSPT 1/4" MALE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Connector: BSPT 1/4" Male
 - Manufacturer Series: CPC
 - Colour: Blue
 - Maximum Operating Length: 2 m
 - Tube Inside Diameter: 5 mm
 - Tube Outside Diameter: 8 mm
 - Material: Polyurethane
 - Maximum Operating Pressure: 10 bar



9172325 BSPT 1/4" Male

RS PRO 6M, POLYURETHANE RECOIL HOSE, WITH BSPT 1/4" MALE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Connector: BSPT 1/4" Male
 - Manufacturer Series: CPC
 - Colour: Blue
 - Maximum Operating Length: 6 m
 - Tube Inside Diameter: 5 mm
 - Tube Outside Diameter: 8 mm
 - Material: Polyurethane
 - Maximum Operating Pressure: 10 bar



9172331 BSPT 1/4" Male

RS PRO 4M, POLYURETHANE RECOIL HOSE, WITH BSP 1/4" MALE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Connector: BSP 1/4" Male
 - Manufacturer Series: CPC
 - Colour: Blue
 - Maximum Operating Length: 4 m
 - Tube Inside Diameter: 5 mm
 - Tube Outside Diameter: 8 mm
 - Material: Polyurethane
 - Maximum Operating Pressure: 10 bar



9172334 BSP 1/4" Male

RS PRO 4M, POLYURETHANE RECOIL HOSE, WITH BSPT 1/4" MALE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Connector: BSPT 1/4" Male
 - Manufacturer Series: CPC
 - Colour: Blue
 - Maximum Operating Length: 4 m
 - Tube Inside Diameter: 5 mm
 - Tube Outside Diameter: 8 mm
 - Material: Polyurethane
 - Maximum Operating Pressure: 10 bar



9172337 BSPT 1/4" Male

RS PRO 2M, POLYURETHANE RECOIL HOSE, WITH BSPT 1/4" MALE

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Connector: BSPT 1/4" Male
 - Manufacturer Series: CPC
 - Colour: Blue
 - Maximum Operating Length: 2 m
 - Tube Inside Diameter: 6.5 mm
 - Tube Outside Diameter: 10 mm
 - Material: Polyurethane
 - Maximum Operating Pressure: 10 bar



9172340 BSPT 1/4" Male

RS PRO 2M, POLYURETHANE RECOIL HOSE, WITH BSPT 3/8" CONNECTOR

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Connector: BSPT 3/8"
 - Manufacturer Series: CPC
 - Colour: Blue
 - Maximum Operating Length: 2 m
 - Tube Inside Diameter: 8 mm
 - Tube Outside Diameter: 12 mm
 - Material: Polyurethane
 - Maximum Operating Pressure: 10 bar



9172343 BSPT 3/8"

RS PRO 4M, POLYURETHANE RECOIL HOSE, WITH BSPT 1/4" MALE

ขนาดบรรจุภัณฑ์: 1 x EA

- Connector: BSPT 1/4" Male
- Manufacturer Series: CPC
- Colour: Blue
- Maximum Operating Length: 4 m
- Tube Inside Diameter: 6.5 mm
- Tube Outside Diameter: 10 mm
- Material: Polyurethane
- Maximum Operating Pressure: 10 bar



9172347 BSPT 1/4" Male

BLUE POLYURETHANE AIRLINE, 12MM OD, 6M L

ขนาดบรรจุภัณฑ์: 1 x EA

- Connector: BSPT 3/8
- Manufacturer Series: CPC
- Colour: Blue
- Maximum Operating Length: 6 m
- Tube Inside Diameter: 8 mm
- Tube Outside Diameter: 12 mm
- Material: Polyurethane
- Maximum Operating Pressure: 10 bar



9172353 BSPT 3/8

RS PRO 4M, POLYURETHANE RECOIL HOSE, WITH BSPT 3/8 CONNECTOR

ขนาดบรรจุภัณฑ์: 1 x EA

- Connector: BSPT 3/8
- Manufacturer Series: CPC
- Colour: Blue
- Maximum Operating Length: 4 m
- Tube Inside Diameter: 8 mm
- Tube Outside Diameter: 12 mm
- Material: Polyurethane
- Maximum Operating Pressure: 10 bar



9172356 BSPT 3/8

RS PRO 6M, POLYURETHANE RECOIL HOSE, WITH BSPT 1/4" MALE

ขนาดบรรจุภัณฑ์: 1 x EA

- Connector: BSPT 1/4" Male
- Manufacturer Series: CPC
- Colour: Blue
- Maximum Operating Length: 6 m
- Tube Inside Diameter: 6.5 mm
- Tube Outside Diameter: 10 mm
- Material: Polyurethane
- Maximum Operating Pressure: 10 bar



9172359 BSPT 1/4" Male

RS PRO 3.6M, PA RECOIL HOSE, WITH BSP 1/4" MALE CONNECTOR

ขนาดบรรจุภัณฑ์: 1 x EA

- Connector: BSP 1/4" Male
- Colour: Blue
- Maximum Operating Length: 3.6 m
- Tube Inside Diameter: 8 mm
- Tube Outside Diameter: 10 mm
- Material: PA
- Maximum Operating Pressure: 15 bar
- Minimum Operating Temperature: -40 °C



9172362 BSP 1/4" Male

RS PRO 3.6M, PA RECOIL HOSE, WITH BSP 1/4" MALE CONNECTOR

ขนาดบรรจุภัณฑ์: 1 x EA

- Connector: BSP 1/4" Male
- Colour: Red
- Maximum Operating Length: 3.6 m
- Tube Inside Diameter: 8 mm
- Tube Outside Diameter: 10 mm
- Material: PA
- Maximum Operating Pressure: 15 bar
- Minimum Operating Temperature: -40 °C



9172448 BSP 1/4" Male

RS PRO 4M, POLYURETHANE RECOIL HOSE, WITH BSPT 1/4" MALE

ขนาดบรรจุภัณฑ์: 1 x EA

- Connector: BSPT 1/4" Male
- Manufacturer Series: CPC
- Colour: Red
- Maximum Operating Length: 4 m
- Tube Inside Diameter: 8 mm
- Tube Outside Diameter: 12 mm
- Material: Polyurethane
- Maximum Operating Pressure: 10 bar



9172450 BSPT 1/4" Male

RS PRO 2M, POLYURETHANE RECOIL HOSE, WITH BSPT 1/4" MALE

ขนาดบรรจุภัณฑ์: 1 x EA

- Connector: BSPT 1/4" Male
- Manufacturer Series: CPC
- Colour: Red
- Maximum Operating Length: 2 m
- Tube Inside Diameter: 5 mm
- Tube Outside Diameter: 8 mm
- Material: Polyurethane
- Maximum Operating Pressure: 10 bar



9172457 BSPT 1/4" Male

RS PRO 2M, POLYURETHANE RECOIL HOSE, WITH BSPT 3/8 CONNECTOR

ขนาดบรรจุภัณฑ์: 1 x EA

- Connector: BSPT 3/8
- Manufacturer Series: CPC
- Colour: Red
- Maximum Operating Length: 2 m
- Tube Inside Diameter: 8 mm
- Tube Outside Diameter: 12 mm
- Material: Polyurethane
- Maximum Operating Pressure: 10 bar



9172460 BSPT 3/8

RS PRO 6M, POLYURETHANE RECOIL HOSE, WITH BSPT 1/4" MALE

ขนาดบรรจุภัณฑ์: 1 x EA

- Connector: BSPT 1/4" Male
- Manufacturer Series: CPC
- Colour: Red
- Maximum Operating Length: 6 m
- Tube Inside Diameter: 5 mm
- Tube Outside Diameter: 8 mm
- Material: Polyurethane
- Maximum Operating Pressure: 10 bar



9172463 BSPT 1/4" Male

RS PRO 4M, POLYURETHANE RECOIL HOSE, WITH BSPT 3/8 CONNECTOR

ขนาดบรรจุภัณฑ์: 1 x EA

- Connector: BSPT 3/8
- Manufacturer Series: CPC
- Colour: Red
- Maximum Operating Length: 4 m
- Tube Inside Diameter: 8 mm
- Tube Outside Diameter: 12 mm
- Material: Polyurethane
- Maximum Operating Pressure: 10 bar



9172472 BSPT 3/8

RS PRO 6M, POLYURETHANE RECOIL HOSE, WITH BSPT 1/4" MALE

ขนาดบรรจุภัณฑ์: 1 x EA

- Connector: BSPT 1/4" Male
- Manufacturer Series: CPC
- Colour: Red
- Maximum Operating Length: 6 m
- Tube Inside Diameter: 8 mm
- Tube Outside Diameter: 10 mm
- Material: Polyurethane
- Maximum Operating Pressure: 10 bar



9172476 BSPT 1/4" Male

RS PRO 4M, PA RECOIL HOSE, WITH BSP 1/4" MALE CONNECTOR

ขนาดบรรจุภัณฑ์: 1 x EA

- Connector: BSP 1/4" Male
- Colour: Yellow
- Maximum Operating Length: 4 m
- Tube Inside Diameter: 5 mm
- Tube Outside Diameter: 8 mm
- Material: PA
- Maximum Operating Pressure: 10 bar
- Minimum Operating Temperature: -40 °C



9172488 BSP 1/4" Male

RS PRO M8 X 1.25 FEMALE STEEL ROD END, 8MM BORE, 48MM LONG,

ขนาดบรรจุภัณฑ์: 1 x EA

- Connection Size: M8 x 1.25 Female
- Bore Size: 8 mm
- Static Load Rating: 1900 kg
- Overall Length: 48 mm
- Material: Steel
- Connection Thread Standard: Metric
- Connection Gender: Female



1761568 M8 x 1.25 Female

RS PRO M12 X 1.25 FEMALE STEEL ROD END, 12MM BORE, 67MM LONG,

ขนาดบรรจุภัณฑ์: 1 x EA

- Connection Size: M12 x 1.25 Female
- Bore Size: 12 mm
- Static Load Rating: 3700 kg
- Overall Length: 67 mm
- Material: Steel
- Connection Thread Standard: Metric
- Connection Gender: Female



1761576 M12 x 1.25 Female

RS PRO STEEL ROD END

ขนาดบรรจุภัณฑ์: 1 x EA

- Material: Steel



1761597 Steel

RS PRO M10 X 1.25 FEMALE STEEL ROD END, 10MM BORE, 58MM LONG,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Connection Size: M10 x 1.25 Female
 - Bore Size: 10 mm
 - Static Load Rating: 3100 kg
 - Overall Length: 58 mm
 - Material: Steel
 - Connection Thread Standard: Metric
 - Connection Gender: Female



1761608 M10 x 1.25 Female

RS PRO M12 X 1.25 FEMALE STEEL ROD END, 10MM BORE, 66MM LONG,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Connection Size: M12 x 1.25 Female
 - Bore Size: 10 mm
 - Static Load Rating: 1900 N
 - Overall Length: 66 mm
 - Material: Steel
 - Connection Thread Standard: Metric
 - Maximum Operating Temperature: +150 °C
 - Minimum Operating Temperature: -30 °C



3034034 M12 x 1.25 Female

RS PRO M16 X 1.5 FEMALE STEEL ROD END, 16MM BORE, 85MM LONG,

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Connection Size: M16 x 1.5 Female
 - Bore Size: 16 mm
 - Static Load Rating: 1800 N
 - Overall Length: 85 mm
 - Material: Steel
 - Connection Thread Standard: Metric
 - Maximum Operating Temperature: +150 °C
 - Minimum Operating Temperature: -30 °C



3034040 M16 x 1.5 Female

RS PRO 110 V DC, 220 V AC SOLENOID VALVE COIL

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 110 V dc, 220 V ac



1762062 110 V dc, 220 V ac

RS PRO 24 V AC SOLENOID VALVE COIL

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 24 V ac



1762068 24 V ac

COIL.22MM H D10 24V DC 6,5W

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 24 V dc



1762069 24 V dc

COIL.22MM H D10 220V AC7,5VA

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 110 V dc, 220 V ac



1762071 110 V dc, 220 V ac

RS PRO 24 V AC SOLENOID VALVE COIL

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 24 V ac



1762072 24 V ac

RS PRO 24 V DC SOLENOID VALVE COIL

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 24 V dc



1762073 24 V dc

SOLENIOD COIL, 22MM, 24VDC

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Supply Voltage: 24 V dc



7840082 24 V dc

RS PRO SOLENOID VALVE, 2 PORT(S), NC, 1/4IN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Number of Parts: 2
 - Operation: Solenoid
 - Connection: 1/4 in G Female
 - Connection Size: 1/4 in
 - Default Valve Position: NC
 - Type: 2/2
 - Orifice Diameter: 2.5 mm
 - Body Material: Brass



1762050 2

RS PRO SOLENOID VALVE, 2 PORT(S), NC, 1/4IN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Number of Ports: 2
 - Operation: Solenoid
 - Connection: 1/4 in G Female
 - Connection Size: 1/4 in
 - Default Valve Position: NC
 - Type: 2/2
 - Orifice Diameter: 3 mm
 - Body Material: Brass



1762054 2

RS PRO SOLENOID VALVE, 2 PORT(S), NC, 1/4IN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Number of Ports: 2
 - Operation: Solenoid
 - Connection: 1/4 in G Female
 - Connection Size: 1/4 in
 - Default Valve Position: NC
 - Type: 2/2
 - Orifice Diameter: 4 mm
 - Body Material: Brass



1762056 2

RS PRO SOLENOID VALVE, 2 PORT(S), NC, 1/4IN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Number of Ports: 2
 - Operation: Solenoid
 - Connection: 1/4 in G Female
 - Connection Size: 1/4 in
 - Default Valve Position: NC
 - Type: 2/2
 - Orifice Diameter: 4 mm
 - Body Material: Brass



1762057 2

RS PRO SOLENOID VALVE, 2 PORT(S), NC, 1/2IN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Number of Ports: 2
 - Operation: Solenoid
 - Connection: 1/2 in G Female
 - Connection Size: 1/2 in
 - Default Valve Position: NC
 - Type: 2/2
 - Orifice Diameter: 12 mm
 - Body Material: Brass



1762059 2

RS PRO SOLENOID VALVE, 2 PORT(S), NC, 1/8IN

- ขนาดบรรจุภัณฑ์: **1 x EA**
- Number of Ports: 2
 - Operation: Solenoid
 - Connection: 1/8 in G Female
 - Connection Size: 1/8 in
 - Default Valve Position: NC
 - Type: 2/2
 - Orifice Diameter: 1.5 mm
 - Body Material: Brass



1762060 2

RS PRO SOLENOID VALVE, 2 PORT(S), NO, 1/2IN

- ขนาดบรรจุภัณฑ์: 1 x EA
- Number of Ports: 2
 - Operation: Solenoid
 - Connection: 1/2 in G Female
 - Connection Size: 1/2 in
 - Default Valve Position: NO
 - Type: 2/2
 - Orifice Diameter: 12 mm
 - Body Material: Brass



1762061 2

RS PRO SOLENOID VALVE, 2 PORT(S), NC, 1IN

- ขนาดบรรจุภัณฑ์: 1 x EA
- Number of Ports: 2
 - Operation: Solenoid
 - Connection: 1 in G Female
 - Connection Size: 1 in
 - Default Valve Position: NC
 - Type: 2/2
 - Orifice Diameter: 25 mm
 - Body Material: Brass



1762064 2

RS PRO FITTING, STRAIGHT NIPPLE JOINT, MALE R 1/2IN X MALE R 3/4IN

- ขนาดบรรจุภัณฑ์: 10 x EA
- Fitting Type: Nipple
 - Fitting Direction: Straight
 - Thread Size 1: 1/2 in
 - Thread Size 2: 3/4 in
 - Connection Gender 1: Male
 - Connection Gender 2: Male
 - Thread Standard 1: R
 - Thread Standard 2: R



1762185 Nipple

RS PRO FITTING FITTING 1/4IN

- ขนาดบรรจุภัณฑ์: 10 x EA
- Fitting Type: Fitting
 - Thread Size 1: 1/4 in



1762187 Fitting

RS PRO FITTING FITTING 1/4IN

- ขนาดบรรจุภัณฑ์: 10 x EA
- Fitting Type: Fitting
 - Thread Size 1: 1/4 in



1762189 Fitting

RS PRO FITTING FITTING 3/8IN

- ขนาดบรรจุภัณฑ์: 10 x EA
- Fitting Type: Fitting
 - Thread Size 1: 3/8 in



1762196 Fitting

RS PRO FITTING FITTING 1/8IN

- ขนาดบรรจุภัณฑ์: 10 x EA
- Fitting Type: Fitting
 - Thread Size 1: 1/8 in



1762207 Fitting

RS PRO FITTING FITTING 1/4IN

- ขนาดบรรจุภัณฑ์: 10 x EA
- Fitting Type: Fitting
 - Thread Size 1: 1/4 in



1762217 Fitting

RS PRO PRESSURE SWITCH, G1/4 -1BAR TO 0BAR

- ขนาดบรรจุภัณฑ์: 1 x EA
- Minimum Operating Pressure: -1 bar
 - Maximum Operating Pressure: 0 bar
 - Pressure Type: Vacuum
 - Suitable Media: Air, Inert Gas
 - Connection: G1/4



2354729 -1 bar

RS PRO PRESSURE SWITCH, G1/4 1BAR TO 16BAR

- ขนาดบรรจุภัณฑ์: 1 x EA
- Minimum Operating Pressure: 1 bar
 - Maximum Operating Pressure: 16 bar
 - Pressure Type: Positive Pressure
 - Suitable Media: Air, Inert Gas
 - Connection: G1/4



2354731 1 bar



PART OF **RS** GROUP



ติดต่อเราเพื่อสั่งซื้อ

อีเมล: mktg@dhrit.com

เบอร์: 02 678 2224 , 06 4159 0479

Line ID: @domnickhunterr1

ที่อยู่: บริษัท ดอมนิค ฮันเตอร์-อาร์แอล (ประเทศไทย) จำกัด

99/1-3 ถ.นราธิวาสราชนครินทร์ แขวง ซ่องนนทรี เขต ยานนาวา กรุงเทพฯ 10120



@domnickhunterr1

บริษัท อาร์เอส คอมโพเน็นส์ จำกัด

ฝ่ายคำสั่งซื้อ

orders.TH@rsgroup.com

เบอร์: 02 648 6868

ฝ่ายตอบข้อมูลสอบถาม

rcustomerserviceth@rsgroup.com

ฝ่ายสนับสนุนทางเทคนิค

tech.TH@rsgroup.com

ที่ตั้งสำนักงาน

บริษัท อาร์เอส คอมโพเน็นส์ จำกัด (สำนักงานใหญ่)

50 จีเอ็มเอ็ม แกรมมีเพลส ชั้นที่ 19

ห้อง 1901-1904 ถนนสุขุมวิท 21 (อโศก) แขวงคลองตันเหนือ

เขตวัฒนา จังหวัดกรุงเทพมหานคร ประเทศไทย 10110

