

RS PRO Range Guide

Your Smart Choice for

ELECTRICAL

	p.2 Cable Accs		p.109 Cable Mgt & Elec Acc
	p.132 Current, Position & movement sensors		p.133 DIN Rail Terminal Blocks
	p.141 Drives & Motors		p.152 Elec & Data Cable
	p.178 Electrical T&M		p.188 Enclosures
	p.250 Machine Safety		p.251 Photoelectric & proximity Sensors
	p.270 PLC, HMI & IPC		p.272 Power Management
	p.279 Pressure , level and flow		p.285 Push But & Swit
	p.296 Pwr & Ind Cable		p.297 Relays
	p.309 Sounders /Beacons		p.315 Structural Systems
	p.332 Temp Sensors & Control		p.415 Timers, Counters



FAST FITTING FEET,TYPE 1 20MM DIAx10MM H

Pack size: **50 x EA**

- Anti Vibration Mount Type: Rubber Foot
- Diameter: 20 mm
- Foot Height: 10 mm
- Overall Height: 10 mm
- Foot Shape: Round



1720855 Rubber Foot

FAST FITTING FEET,TYPE 1 24MM DIAx14MM H

Pack size: **50 x EA**

- Anti Vibration Mount Type: Rubber Foot
- Diameter: 24 mm
- Foot Height: 14 mm
- Overall Height: 14 mm
- Foot Shape: Round



1720856 Rubber Foot

RS PRO ROUND ANTI VIBRATION MOUNT, RUBBER FOOT

Pack size: **50 x EA**

- Anti Vibration Mount Type: Rubber Foot
- Diameter: 21 mm
- Foot Height: 4.2 mm
- Overall Height: 4.2 mm
- Foot Shape: Round



1720858 Rubber Foot

RS PRO ROUND ANTI VIBRATION MOUNT, RUBBER FOOT

Pack size: **40 x EA**

- Anti Vibration Mount Type: Rubber Foot
- Diameter: 40 mm
- Foot Height: 10 mm
- Overall Height: 10 mm
- Foot Shape: Round



1720859 Rubber Foot

RS PRO ROUND ANTI VIBRATION MOUNT, RUBBER FOOT

Pack size: **40 x EA**

- Anti Vibration Mount Type: Rubber Foot
- Diameter: 21 mm
- Foot Height: 6 mm
- Overall Height: 6 mm
- Foot Shape: Round



1720875 Rubber Foot

PUSH ON FEET

Pack size: **40 x EA**

- Anti Vibration Mount Type: Rubber Foot
- Diameter: 13.4 mm
- Foot Height: 15.2 mm
- Overall Height: 15.2 mm
- Material: Rubber
- Foot Shape: Round



1720860 Rubber Foot

RS PRO ROUND ANTI VIBRATION MOUNT, RUBBER FOOT

Pack size: **40 x EA**

- Anti Vibration Mount Type: Rubber Foot
- Diameter: 14.2 mm
- Foot Height: 5.5 mm
- Overall Height: 5.5 mm
- Foot Shape: Round



1720870 Rubber Foot

RS PRO ROUND ANTI VIBRATION MOUNT, RUBBER FOOT

Pack size: **40 x EA**

- Anti Vibration Mount Type: Rubber Foot
- Diameter: 15 mm
- Foot Height: 6 mm
- Overall Height: 6 mm
- Foot Shape: Round



1720866 Rubber Foot

RS PRO ROUND ANTI VIBRATION MOUNT, RUBBER FOOT

Pack size: **40 x EA**

- Anti Vibration Mount Type: Rubber Foot
- Diameter: 15 mm
- Foot Height: 6 mm
- Overall Height: 6 mm
- Foot Shape: Round



1720876 Rubber Foot

RS PRO ROUND ANTI VIBRATION MOUNT, RUBBER FOOT

Pack size: **40 x EA**

- Anti Vibration Mount Type: Rubber Foot
- Diameter: 15 mm
- Foot Height: 9 mm
- Overall Height: 9 mm
- Foot Shape: Round



1720871 Rubber Foot

RS PRO ROUND ANTI VIBRATION MOUNT, RUBBER FOOT

Pack size: **40 x EA**

- Anti Vibration Mount Type: Rubber Foot
- Diameter: 15 mm
- Foot Height: 6 mm
- Overall Height: 6 mm
- Foot Shape: Round



1720877 Rubber Foot

RS PRO ROUND ANTI VIBRATION MOUNT, RUBBER FOOT

Pack size: **40 x EA**

- Anti Vibration Mount Type: Rubber Foot
- Diameter: 21 mm
- Foot Height: 8 mm
- Overall Height: 8 mm
- Foot Shape: Round



1720878 Rubber Foot

CABLE,CLAMP,RIBBON,SELF ADHESIVE,PVC,25.4MM,13MM

Pack size: **100 x EA**

- Cable Clip/Clamp Style: Flat Cable Clamp
- Affixing Method: Self Adhesive
- Material: PVC
- Colour: Grey
- Length: 13 mm
- Width: 25 mm
- Depth: 6 mm
- Self Adhesive: Yes



233180 Flat Cable

CABLE,CLAMP,RIBBON,SELF ADHESIVE,PVC,25.4MM,25MM

Pack size: **100 x EA**

- Cable Clip/Clamp Style: Flat Cable Clamp
- Affixing Method: Self Adhesive
- Material: PVC
- Colour: Grey
- Length: 24 mm
- Width: 25 mm
- Depth: 9 mm
- Self Adhesive: Yes



233190 Flat Cable

CABLE,CLIP,CIRCULAR,TV,BLACK POLYPROPYLENE,DIA 5/6MM

Pack size: **100 x EA**

- Cable Clip/Clamp Style: TV Cable Clip
- Maximum Bundle Diameter: 6 mm
- Affixing Method: Nail
- Material: PE
- Colour: Black
- Width: 4.69 mm
- Depth: 7.18 mm
- Dimensions [L x W (x DJ)]: 4.69 x 7.18 mm



233415 TV Cable Clip

CABLE,CLIP,CIRCULAR,TV,BLACK POLYPROPYLENE,DIA 7/8MM

Pack size: **100 x EA**

- Cable Clip/Clamp Style: TV Cable Clip
- Maximum Bundle Diameter: 8 mm
- Affixing Method: Nail
- Material: PE
- Colour: Black
- Length: 9.9 mm
- Width: 5.6 mm
- Depth: 10.9 mm



233433 TV Cable Clip

RS PRO WHITE PE RECTANGULAR CABLE CLIP

Pack size: **100 x EA**

- Cable Clip/Clamp Style: Rectangular Cable Clip
- Affixing Method: Nail
- Material: PE
- Colour: White
- Length: 9.9 mm
- Width: 18 mm
- Depth: 12.9 mm
- Dimensions [L x W (x D)]: 9.9 x 18 x 12.9 mm



233443 Rectangular

RS PRO GREY PE RECTANGULAR CABLE CLIP

Pack size: **100 x EA**

- Cable Clip/Clamp Style: Rectangular Cable Clip
- Affixing Method: Nail
- Material: PE
- Colour: Grey
- Length: 9.9 mm
- Width: 26.6 mm
- Depth: 12.9 mm
- Dimensions [L x W (x D)]: 9.9 x 26.6 x 12.9 mm



233459 Rectangular

RS PRO WHITE PE ROUND CLIP, 5MM MAX. BUNDLE

Pack size: **100 x EA**

- Cable Clip/Clamp Style: Round Clip
- Maximum Bundle Diameter: 5 mm
- Affixing Method: Nail
- Material: PE
- Colour: White
- Width: 5 mm
- Depth: 7.6 mm
- Dimensions [L x W (x D)]: 5 x 7.4 mm



233512 Round Clip

RS PRO WHITE PE ROUND CLIP, 3.5MM MAX. BUNDLE

Pack size: **100 x EA**

- Cable Clip/Clamp Style: Round Clip
- Maximum Bundle Diameter: 3.5 mm
- Affixing Method: Nail
- Material: PE
- Colour: White
- Width: 3.5 mm
- Depth: 5.9 mm
- Dimensions [L x W (x D)]: 3.5 x 6.4 mm



233516 Round Clip

CABLE,CLIP,ROUND,PLASTIC,WHITE,7.0MM DIA

Pack size: **100 x EA**

- Cable Clip/Clamp Style: Round Clip
- Maximum Bundle Diameter: 7 mm
- Affixing Method: Nail
- Material: PE
- Colour: White
- Width: 7 mm
- Depth: 11 mm
- Dimensions [L x W (x D)]: 7 x 11 mm



233522 Round Clip

RS PRO WHITE PE RECTANGULAR CABLE CLIP

Pack size: **100 x EA**

- Cable Clip/Clamp Style: Rectangular Cable Clip
- Affixing Method: Nail
- Material: PE
- Colour: White
- Length: 10 mm
- Width: 11.6 mm
- Depth: 9.7 mm
- Dimensions [L x W (x D)]: 10 x 11.6 x 9.7 mm



233556 Rectangular

RS PRO WHITE PE RECTANGULAR CABLE CLIP

Pack size: **100 x EA**

- Cable Clip/Clamp Style: Rectangular Cable Clip
- Affixing Method: Nail
- Material: PE
- Colour: White
- Length: 9.3 mm
- Width: 8 mm
- Depth: 8 mm
- Dimensions [L x W (x D)]: 9.3 x 8 x 8 mm



233562 Rectangular

RS PRO WHITE PE RECTANGULAR CABLE CLIP

Pack size: **100 x EA**

- Cable Clip/Clamp Style: Rectangular Cable Clip
- Affixing Method: Nail
- Material: PE
- Colour: White
- Length: 9.9 mm
- Width: 8.5 mm
- Depth: 8 mm
- Dimensions [L x W (x D)]: 9.9 x 8.5 x 8 mm



233578 Rectangular

RS PRO WHITE PE RECTANGULAR CABLE CLIP

Pack size: **100 x EA**

- Cable Clip/Clamp Style: Rectangular Cable Clip
- Affixing Method: Nail
- Material: PE
- Colour: White
- Length: 9.8 mm
- Width: 10 mm
- Depth: 10 mm
- Dimensions [L x W (x D)]: 9.8 x 10 x 10 mm



233584 Rectangular

RS PRO GREY PE RECTANGULAR CABLE CLIP, 1.5MM MAX. BUNDLE

Pack size: **100 x EA**

- Cable Clip/Clamp Style: Rectangular Cable Clip
- Maximum Bundle Diameter: 1.5 mm
- Affixing Method: Nail
- Material: PE
- Colour: Grey
- Length: 9.9 mm
- Width: 8.5 mm
- Depth: 8 mm



233629 Rectangular

RS PRO GREY PE RECTANGULAR CABLE CLIP, 6MM MAX. BUNDLE

Pack size: **100 x EA**

- Cable Clip/Clamp Style: Rectangular Cable Clip
- Maximum Bundle Diameter: 6 mm
- Affixing Method: Nail
- Material: PE
- Colour: Grey
- Length: 9.4 mm
- Width: 13.5 mm
- Depth: 11.6 mm



233657 Rectangular

CABLE,CLIP,NYLON,SELF-ADHESIVE,15.7MM,BUNDLE

Pack size: **50 x EA**

- Cable Clip/Clamp Style: Cable Clip
- Maximum Bundle Diameter: 15.75 mm
- Affixing Method: Self Adhesive
- Material: Nylon 66
- Colour: Natural
- Length: 32.5 mm
- Width: 28.3 mm
- Depth: 15.2 mm



404427 Cable Clip

CABLE,CLIP,NYLON,SELF-ADHESIVE,7MM,BUNDLE

Pack size: **50 x EA**

- Cable Clip/Clamp Style: Cable Clip
- Maximum Bundle Diameter: 7.11 mm
- Affixing Method: Self Adhesive
- Material: Nylon 66
- Colour: Natural
- Length: 26.8 mm
- Width: 26.5 mm
- Depth: 11.7 mm



404433 Cable Clip

CABLE,CLIP,NYLON,SELF-ADHESIVE,13.5MM,BUNDLE

Pack size: **50 x EA**

- Cable Clip/Clamp Style: Cable Clip
- Maximum Bundle Diameter: 13.51 mm
- Affixing Method: Self Adhesive
- Material: Nylon 66
- Colour: Natural
- Length: 25.6 mm
- Width: 25.5 mm
- Depth: 17.2 mm



404437 Cable Clip

CABLE,CLAMP,NYLON,SELF-ADHESIVE,ADJUSTABLE,25MM

Pack size: **100 x EA**

- Cable Clip/Clamp Style: Adjustable Clamp
- Maximum Bundle Diameter: 26 mm
- Affixing Method: Self Adhesive
- Material: Nylon 66
- Colour: Grey
- Length: 30.5 mm
- Width: 21 mm
- Depth: 108 mm



404443 Adjustable

RS PRO GREY NYLON ADJUSTABLE CLAMP, 22MM MAX. BUNDLE

Pack size: **100 x EA**

- Cable Clip/Clamp Style: Adjustable Clamp
- Maximum Bundle Diameter: 22 mm
- Affixing Method: Self Adhesive
- Material: Nylon 66
- Colour: Grey
- Length: 30.5 mm
- Width: 21 mm
- Depth: 90 mm



404449 Adjustable

CABLE, CLAMP, NYLON, SELF-ADHESIVE, ADJUSTABLE, 18MM

Pack size: **100 x EA**

- Cable Clip/Clamp Style: Adjustable Clamp
- Maximum Bundle Diameter: 17 mm
- Affixing Method: Self Adhesive
- Material: Nylon 66
- Colour: Grey
- Length: 25 mm
- Width: 18 mm
- Depth: 70 mm



404455 Adjustable

CABLE, CLIP, NYLON, SELF-ADHESIVE, 4MM, BUNDLE

Pack size: **50 x EA**

- Cable Clip/Clamp Style: Round Clip
- Maximum Bundle Diameter: 4.06 mm
- Affixing Method: Self Adhesive
- Material: Nylon 66
- Colour: Natural
- Length: 19 mm
- Width: 19 mm
- Depth: 7.2 mm



404459 Round Clip

CABLE, CLIP, HOOK, SELF-ADHESIVE, WHITE, PLASTICISED, AL

Pack size: **100 x EA**

- Cable Clip/Clamp Style: Hook Clip
- Affixing Method: Self Adhesive
- Material: Aluminium
- Colour: White
- Length: 69.8 mm
- Width: 25.4 mm
- Depth: 7.9 mm
- Self Adhesive: Yes



475142 Hook Clip

RS PRO NATURAL ALUMINIUM BUCKLE CLIP, 13MM MAX. BUNDLE

Pack size: **250 x EA**

- Cable Clip/Clamp Style: Buckle Clip
- Maximum Bundle Diameter: 13 mm
- Affixing Method: Self Adhesive
- Material: Aluminium
- Colour: Natural
- Length: 63.5 mm
- Width: 25.4 mm
- Depth: 6.4 mm



475148 Buckle Clip

CABLE, CLIP, RIBBON, ALUMINIUM, SELF-ADHESIVE, 13MM, 10

Pack size: **100 x EA**

- Cable Clip/Clamp Style: Open Arm Clip
- Maximum Bundle Diameter: 12.7 mm
- Affixing Method: Self Adhesive
- Material: Aluminium
- Colour: Natural
- Length: 12.9 mm
- Width: 9.8 mm
- Depth: 6.3 mm



475154 Open Arm Clip

RS PRO NATURAL ALUMINIUM BUCKLE CLIP, 19.3MM MAX. BUNDLE

Pack size: **250 x EA**

- Cable Clip/Clamp Style: Buckle Clip
- Maximum Bundle Diameter: 19.3 mm
- Affixing Method: Self Adhesive
- Material: Aluminium
- Colour: Natural
- Length: 89 mm
- Width: 25.4 mm
- Depth: 8 mm



475158 Buckle Clip

CABLE, CLIP, METAL, ALUMINIUM, SELF-ADHESIVE, MAX DIA 9

Pack size: **250 x EA**

- Cable Clip/Clamp Style: Open Arm Clip
- Maximum Bundle Diameter: 9.5 mm
- Affixing Method: Self Adhesive
- Material: Aluminium
- Colour: Natural
- Length: 19 mm
- Width: 16 mm
- Depth: 14.9 mm



475160 Open Arm Clip

CABLE, CLIP, RIBBON, ALUMINIUM, SELF-ADHESIVE, 19.3MM, 1

Pack size: **100 x EA**

- Cable Clip/Clamp Style: Open Arm Clip
- Maximum Bundle Diameter: 13 mm
- Affixing Method: Self Adhesive
- Material: Aluminium
- Colour: Natural
- Length: 19.3 mm
- Width: 9.8 mm
- Depth: 6.3 mm



475164 Open Arm Clip

CABLE, CLIP, RIBBON, ALUMINIUM, SELF-ADHESIVE, 25.7MM, 2

Pack size: **100 x EA**

- Cable Clip/Clamp Style: Open Arm Clip
- Maximum Bundle Diameter: 10 mm
- Affixing Method: Self Adhesive
- Material: Aluminium
- Colour: Natural
- Length: 25.6 mm
- Width: 9.8 mm
- Depth: 7.6 mm



475170 Open Arm Clip

RS PRO NATURAL ALUMINIUM OPEN ARM CLIP

Pack size: **100 x EA**

- Cable Clip/Clamp Style: Open Arm Clip
- Affixing Method: Self Adhesive
- Material: Aluminium
- Colour: Natural
- Length: 33 mm
- Width: 9.8 mm
- Depth: 9.8 mm
- Self Adhesive: Yes



475182 Open Arm Clip

RS PRO NATURAL ALUMINIUM OPEN ARM CLIP, 10MM MAX. BUNDLE

Pack size: **100 x EA**

- Cable Clip/Clamp Style: Open Arm Clip
- Maximum Bundle Diameter: 10 mm
- Affixing Method: Self Adhesive
- Material: Aluminium
- Colour: Natural
- Length: 44 mm
- Width: 9.8 mm
- Depth: 12.2 mm



475186 Open Arm Clip

RS PRO NATURAL ALUMINIUM OPEN ARM CLIP

Pack size: **100 x EA**

- Cable Clip/Clamp Style: Open Arm Clip
- Affixing Method: Self Adhesive
- Material: Aluminium
- Colour: Natural
- Length: 63.7 mm
- Width: 9.8 mm
- Depth: 17.5 mm
- Self Adhesive: Yes



475192 Open Arm Clip

CABLE, CLIP, METAL, ALUMINIUM, SELF-ADHESIVE, MAX DIA 6

Pack size: **250 x EA**

- Cable Clip/Clamp Style: Open Arm Clip
- Maximum Bundle Diameter: 6 mm
- Affixing Method: Self Adhesive
- Material: Aluminium
- Colour: Natural
- Length: 16 mm
- Width: 10.6 mm
- Depth: 9.4 mm



475198 Open Arm Clip

RS PRO 6.4MM NATURAL NYLON P CLIP

Pack size: **100 x EA**

- Closed Inside Diameter: 6.4 mm
- Width: 10 mm
- Fixing Hole Diameter: 4.6 mm
- Material: Nylon
- Coating/Lining: None
- Colour: Natural



479544 6.4 mm

CABLE, CLAMP, P CLIPS, NATURAL, 12.7MM DIA

Pack size: **100 x EA**

- Cable Clip/Clamp Style: Cable Clip



479548 Cable Clip

RS PRO NATURAL NYLON SADDLE CLIP

Pack size: **100 x EA**

- Cable Clip/Clamp Style: Saddle Clip
- Affixing Method: Push In
- Material: Nylon 66
- Colour: Natural
- Length: 5.5 mm
- Width: 15.9 mm
- Depth: 9 mm
- Fire Behaviour: Flame Retardant



479550 Saddle Clip

RS PRO NATURAL NYLON SADDLE CLIP

Pack size: **100 x EA**

- Cable Clip/Clamp Style: Saddle Clip
- Affixing Method: Push In
- Material: Nylon 66
- Colour: Natural
- Length: 5.5 mm
- Width: 15.9 mm
- Depth: 14.2 mm
- Dimensions [L x W (x D)]: 5.5 x 15.9 x 14.2 mm



479560 Saddle Clip

RS PRO NATURAL NYLON SADDLE CLIP

Pack size: **100 x EA**

- Cable Clip/Clamp Style: Saddle Clip
- Affixing Method: Push In
- Material: Nylon 66
- Colour: Natural
- Length: 5.5 mm
- Width: 15.9 mm
- Depth: 23 mm
- Dimensions [L x W (x D)]: 5.5 x 15.9 x 23 mm



479572 Saddle Clip

RS PRO NATURAL NYLON SADDLE CLIP

Pack size: **100 x EA**

- Cable Clip/Clamp Style: Saddle Clip
- Affixing Method: Push In
- Material: Nylon 66
- Colour: Natural
- Length: 5.5 mm
- Width: 15.9 mm
- Depth: 31.1 mm
- Dimensions [L x W (x D)]: 5.5 x 15.9 x 31.1 mm



479576 Saddle Clip

RS PRO WHITE NYLON SADDLE CLIP, 10.2MM MAX. BUNDLE

Pack size: **25 x EA**

- Cable Clip/Clamp Style: Saddle Clip
- Maximum Bundle Diameter: 10.2 mm
- Material: Nylon 66
- Colour: White
- Width: 15.9 mm
- Depth: 5.6 mm
- Dimensions [L x W (x D)]: 15.9 x 5.6 mm



479582 Saddle Clip

CABLE,CLIP,BUNNY,ADHESIVE BASE,BUNDLE DIA 12.7MM

Pack size: **20 x EA**

- Cable Clip/Clamp Style: Bunny Clip
- Maximum Bundle Diameter: 14.8 mm
- Affixing Method: Self Adhesive
- Material: Nylon 66
- Colour: Natural
- Length: 35.2 mm
- Width: 22 mm
- Dimensions [L x W (x D)]: 35.2 x 22 mm



479601 Bunny Clip

CABLE,CLIP,BUNNY,ADHESIVE BASE,BUNDLE DIA 10MM

Pack size: **20 x EA**

- Cable Clip/Clamp Style: Bunny Clip
- Maximum Bundle Diameter: 7.9 mm
- Affixing Method: Self Adhesive
- Material: Nylon 66
- Colour: Natural
- Length: 27.5 mm
- Width: 17.4 mm
- Dimensions [L x W (x D)]: 27.5 x 17.4 mm



479605 Bunny Clip

RS PRO GREY PVC DUCT CLIP, 9.5MM MAX. BUNDLE

Pack size: **25 x EA**

- Cable Clip/Clamp Style: Duct Clip
- Maximum Bundle Diameter: 9.5 mm
- Affixing Method: Self Adhesive
- Material: PVC
- Colour: Grey
- Length: 28.5 mm
- Width: 25.4 mm
- Depth: 13.8 mm



479611 Duct Clip

RS PRO NATURAL NYLON TWISTER CLIP, 7MM MAX. BUNDLE

Pack size: **100 x EA**

- Cable Clip/Clamp Style: Twister Clip
- Maximum Bundle Diameter: 7 mm
- Affixing Method: Twist
- Material: Nylon 66
- Colour: Natural
- Length: 25 mm
- Width: 2 mm
- Dimensions [L x W (x D)]: 25 x 2 mm



819832 Twister Clip

RS PRO NATURAL NYLON TWISTER CLIP, 15MM MAX. BUNDLE

Pack size: **100 x EA**

- Cable Clip/Clamp Style: Twister Clip
- Maximum Bundle Diameter: 15 mm
- Affixing Method: Twist
- Material: Nylon 66
- Colour: Natural
- Length: 33.8 mm
- Width: 1.9 mm
- Dimensions [L x W (x D)]: 33.8 x 1.9 mm



819848 Twister Clip

RS PRO NATURAL NYLON TWISTER CLIP, 23.6MM MAX. BUNDLE

Pack size: **100 x EA**

- Cable Clip/Clamp Style: Twister Clip
- Maximum Bundle Diameter: 23.6 mm
- Affixing Method: Twist
- Material: Nylon 66
- Colour: Natural
- Length: 45 mm
- Width: 2 mm
- Dimensions [L x W (x D)]: 45 x 2 mm



821239 Twister Clip

RS PRO NATURAL NYLON CABLE CLAMP, 4.3MM MAX. BUNDLE

Pack size: **100 x EA**

- Cable Clip/Clamp Style: Cable Clamp
- Maximum Bundle Diameter: 4.3 mm
- Affixing Method: Adhesive
- Material: Nylon
- Colour: Natural
- Width: 9.5 mm
- Depth: 6.5 mm



1720839 Cable Clamp

RS PRO NATURAL STEEL CABLE CLIP, 8MM MAX. BUNDLE

Pack size: **100 x EA**

- Cable Clip/Clamp Style: Cable Clip
- Maximum Bundle Diameter: 8 mm
- Affixing Method: Screw
- Material: Steel
- Colour: Natural
- Length: 56 mm
- Width: 20 mm
- Depth: 8 mm



1823854 Cable Clip

RS PRO NATURAL STEEL CABLE CLIP, 20MM MAX. BUNDLE

Pack size: **50 x EA**

- Cable Clip/Clamp Style: Cable Clip
- Maximum Bundle Diameter: 20 mm
- Affixing Method: Screw
- Material: Steel
- Colour: Natural
- Length: 110.5 mm
- Width: 20 mm
- Depth: 20 mm



1823855 Cable Clip

CABLE,CLEAT,LDPE,BLACK,SIZE 5,12.7MM,QTY 50

Pack size: **50 x EA**

- Cable Clip/Clamp Style: Cable Clip
- Maximum Bundle Diameter: 12.7 mm
- Affixing Method: Screw
- Material: PE
- Colour: Black
- Width: 17.5 mm
- Depth: 28 mm
- Dimensions [L x W (x D)]: 17.5 x 28 mm



1845214 Cable Clip

RS PRO BLACK NYLON C CLAMP, 17MM MAX. BUNDLE

Pack size: **100 x EA**

- Cable Clip/Clamp Style: C Clamp
- Maximum Bundle Diameter: 17 mm
- Affixing Method: Adhesive
- Material: Nylon
- Colour: Black
- Length: 41.3 mm
- Width: 15.6 mm
- Fire Behaviour: Flame Retardant



2138532 C Clamp

RS PRO BLACK NYLON C CLAMP, 12MM MAX. BUNDLE

Pack size: **50 x EA**

- Cable Clip/Clamp Style: C Clamp
- Maximum Bundle Diameter: 12 mm
- Affixing Method: Adhesive
- Material: Nylon
- Colour: Black
- Length: 34.8 mm
- Width: 16.5 mm
- Fire Behaviour: Flame Retardant



2138533 C Clamp

RS PRO NATURAL NYLON CABLE CLIP,
2.8MM MAX. BUNDLE

- Pack size: **100 x EA**
- Cable Clip/Clamp Style: Cable Clip
 - Maximum Bundle Diameter: 2.8 mm
 - Affixing Method: Adhesive
 - Material: Nylon
 - Colour: Natural
 - Length: 13 mm
 - Width: 9.5 mm
 - Fire Behaviour: Flame Retardant



2138534 Cable Clip

RS PRO NATURAL NYLON CABLE CLIP,
7MM MAX. BUNDLE

- Pack size: **100 x EA**
- Cable Clip/Clamp Style: Cable Clip
 - Maximum Bundle Diameter: 7 mm
 - Affixing Method: Adhesive
 - Material: Nylon
 - Colour: Natural
 - Length: 25 mm
 - Width: 25 mm
 - Fire Behaviour: Flame Retardant



2138535 Cable Clip

RS PRO NATURAL NYLON CABLE CLIP,
12.8MM MAX. BUNDLE

- Pack size: **50 x EA**
- Cable Clip/Clamp Style: Cable Clip
 - Maximum Bundle Diameter: 12.8 mm
 - Affixing Method: Adhesive
 - Material: Nylon
 - Colour: Natural
 - Length: 33.7 mm
 - Width: 27.5 mm
 - Fire Behaviour: Flame Retardant



2138536 Cable Clip

RS PRO NATURAL NYLON CABLE CLIP,
5.5MM MAX. BUNDLE

- Pack size: **100 x EA**
- Cable Clip/Clamp Style: Cable Clip
 - Maximum Bundle Diameter: 5.5 mm
 - Affixing Method: Adhesive
 - Material: Nylon
 - Colour: Natural
 - Length: 27 mm
 - Width: 17 mm
 - Fire Behaviour: Flame Retardant



2138537 Cable Clip

RS PRO BLACK NYLON FLAT CABLE
CLAMP

- Pack size: **100 x EA**
- Cable Clip/Clamp Style: Flat Cable Clamp
 - Affixing Method: Adhesive
 - Material: Nylon
 - Colour: Black
 - Length: 52.2 mm
 - Width: 56.8 mm
 - Fire Behaviour: Flame Retardant
 - Dimensions [L x W (x D)]: 52.2 x 56.8 x 26.2 mm



2138538 Flat Cable

RS PRO NATURAL NYLON ROUND
CLIP, 4.9MM MAX. BUNDLE

- Pack size: **100 x EA**
- Cable Clip/Clamp Style: Round Clip
 - Maximum Bundle Diameter: 4.9 mm
 - Affixing Method: Adhesive
 - Material: Nylon 66
 - Colour: Natural
 - Length: 52.2 mm
 - Width: 56.8 mm
 - Fire Behaviour: Flame Retardant



2163629 Round Clip

RS PRO NATURAL NYLON CABLE
CLAMP

- Pack size: **50 x EA**
- Cable Clip/Clamp Style: Cable Clamp
 - Affixing Method: Adhesive
 - Material: Nylon 66
 - Colour: Natural
 - Length: 4.1 mm
 - Width: 9.4 mm
 - Fire Behaviour: Self-extinguishing
 - Self Adhesive: Yes



2414760 Cable Clamp

RS PRO NATURAL NYLON CABLE
CLAMP

- Pack size: **50 x EA**
- Cable Clip/Clamp Style: Cable Clamp
 - Affixing Method: Adhesive
 - Material: Nylon 66
 - Colour: Natural
 - Length: 6.1 mm
 - Width: 9.4 mm
 - Fire Behaviour: Self-extinguishing
 - Self Adhesive: Yes



2414776 Cable Clamp

RS PRO NATURAL NYLON CABLE
CLAMP

- Pack size: **50 x EA**
- Cable Clip/Clamp Style: Cable Clamp
 - Affixing Method: Adhesive
 - Material: Nylon 66
 - Colour: Natural
 - Length: 7.4 mm
 - Width: 12.7 mm
 - Fire Behaviour: Self-extinguishing
 - Self Adhesive: Yes



2414782 Cable Clamp

RS PRO NATURAL NYLON CABLE
CLAMP

- Pack size: **50 x EA**
- Cable Clip/Clamp Style: Cable Clamp
 - Affixing Method: Adhesive
 - Material: Nylon 66
 - Colour: Natural
 - Length: 9.1 mm
 - Width: 12.7 mm
 - Fire Behaviour: Self-extinguishing
 - Self Adhesive: Yes



2414798 Cable Clamp

RS PRO NATURAL NYLON CABLE
CLAMP

- Pack size: **50 x EA**
- Cable Clip/Clamp Style: Cable Clamp
 - Affixing Method: Adhesive
 - Material: Nylon 66
 - Colour: Natural
 - Length: 11.2 mm
 - Width: 12.7 mm
 - Fire Behaviour: Self-extinguishing
 - Self Adhesive: Yes



2414805 Cable Clamp

RS PRO NATURAL NYLON CABLE
CLAMP

- Pack size: **50 x EA**
- Cable Clip/Clamp Style: Cable Clamp
 - Affixing Method: Adhesive
 - Material: Nylon 66
 - Colour: Natural
 - Length: 13 mm
 - Width: 12.7 mm
 - Fire Behaviour: Self-extinguishing
 - Self Adhesive: Yes



2414827 Cable Clamp

RS PRO NATURAL PE CABLE CLIP

- Pack size: **100 x EA**
- Cable Clip/Clamp Style: Cable Clip
 - Affixing Method: Nail
 - Material: PE
 - Colour: Natural
 - Length: 5.2 mm
 - Width: 4.6 mm
 - Depth: 5.2 mm
 - Dimensions [L x W (x D)]: 4.6 x 5.2 mm



7389363 Cable Clip

WIRE SADDLE, 7.9X3.8X9.7MM

- Pack size: **50 x EA**
- Cable Clip/Clamp Style: Wire Saddle
 - Maximum Bundle Diameter: 6.4 mm
 - Affixing Method: Push In
 - Material: Nylon 66
 - Colour: White
 - Length: 7.9 mm
 - Width: 3.8 mm
 - Depth: 9.7 mm



8178895 Wire Saddle

RS PRO WHITE NYLON WIRE SADDLE,
3.5MM MAX. BUNDLE

- Pack size: **50 x EA**
- Cable Clip/Clamp Style: Wire Saddle
 - Maximum Bundle Diameter: 3.5 mm
 - Affixing Method: Push In
 - Material: Nylon 66
 - Colour: White
 - Length: 6.6 mm
 - Width: 3.8 mm
 - Depth: 7.8 mm



8178899 Wire Saddle

RS PRO NATURAL NYLON WIRE
SADDLE, 10.7MM MAX. BUNDLE

- Pack size: **50 x EA**
- Cable Clip/Clamp Style: Wire Saddle
 - Maximum Bundle Diameter: 10.7 mm
 - Affixing Method: Push In
 - Material: Nylon 66
 - Colour: Natural
 - Length: 9.3 mm
 - Width: 4 mm
 - Depth: 13.4 mm



8178902 Wire Saddle

MOUNTING TWIST TIE, 15~20MM BUNDLE DIA

Pack size: **20 x EA**

- Cable Clip/Clamp Style: Cable Clip
- Maximum Bundle Diameter: 20 mm
- Affixing Method: Twist
- Material: Nylon 66
- Colour: Natural
- Length: 40 mm
- Width: 25.5 mm
- Dimensions [L x W (x D)]: 40 x 25.5 mm



8178906 Cable Clip

STANDOFF TWIST TIE, 10.4MM DIA

Pack size: **100 x EA**

- Cable Clip/Clamp Style: Twister Clip
- Maximum Bundle Diameter: 10.4 mm
- Affixing Method: Push In
- Material: Nylon 66
- Colour: Natural
- Length: 27.3 mm
- Dimensions [L x W (x D)]: 27.3 x 10.4 mm



8178909 Twister Clip

TWIST TIE, 10.1MM BUNDLE DIA

Pack size: **50 x EA**

- Cable Clip/Clamp Style: Twister Clip
- Maximum Bundle Diameter: 10.1 mm
- Affixing Method: Twist
- Material: Nylon 66
- Colour: Natural
- Length: 29.8 mm
- Width: 1.7 mm
- Depth: 11.6 mm



8178915 Twister Clip

TWIST TIE, 13.4MM BUNDLE DIA

Pack size: **50 x EA**

- Cable Clip/Clamp Style: Twister Clip
- Maximum Bundle Diameter: 13.4 mm
- Affixing Method: Twist
- Material: Nylon 66
- Colour: Natural
- Length: 33.8 mm
- Width: 1.9 mm
- Depth: 15 mm



8178918 Twister Clip

RS PRO WHITE METAL CABLE CLIP

Pack size: **50 x EA**

- Cable Clip/Clamp Style: Cable Clip
- Affixing Method: Self Adhesive
- Material: Metal
- Colour: White
- Length: 19.4 mm
- Width: 10 mm
- Depth: 0.5 mm
- Self Adhesive: Yes



8178921 Cable Clip

RS PRO NATURAL NYLON TWISTER CLIP, 7MM MAX. BUNDLE

Pack size: **50 x EA**

- Cable Clip/Clamp Style: Twister Clip
- Maximum Bundle Diameter: 7 mm
- Affixing Method: Twist
- Material: Nylon 66
- Colour: Natural
- Length: 25 mm
- Width: 2 mm
- Depth: 7 mm



8178924 Twister Clip

TWIST TIE, 21.3MM BUNDLE DIA

Pack size: **50 x EA**

- Cable Clip/Clamp Style: Twister Clip
- Maximum Bundle Diameter: 21.3 mm
- Affixing Method: Twist
- Material: Nylon 66
- Colour: Natural
- Length: 45 mm
- Width: 2 mm
- Depth: 23.6 mm



8178928 Twister Clip

RS PRO WHITE NYLON CABLE CLAMP, 15.4MM MAX. BUNDLE

Pack size: **100 x EA**

- Cable Clip/Clamp Style: Cable Clamp
- Maximum Bundle Diameter: 15.4 mm
- Affixing Method: Push In
- Material: Nylon 66
- Colour: White
- Length: 37 mm
- Width: 18.4 mm
- Depth: 31.8 mm



8178937 Cable Clamp

RS PRO NATURAL NYLON CABLE CLAMP

Pack size: **10 x EA**

- Cable Clip/Clamp Style: Cable Clamp
- Affixing Method: Snap In
- Material: Nylon 66
- Colour: Natural
- Length: 67 mm
- Width: 15.7 mm
- Depth: 16.3 mm
- Fire Behaviour: Self-extinguishing



8178943 Cable Clamp

RS PRO NATURAL NYLON CABLE CLAMP

Pack size: **10 x EA**

- Cable Clip/Clamp Style: Cable Clamp
- Affixing Method: Snap In
- Material: Nylon 66
- Colour: Natural
- Length: 45.1 mm
- Width: 18.5 mm
- Depth: 16.3 mm
- Fire Behaviour: Self-extinguishing



8178946 Cable Clamp

CABLE CLAMP, 5MM BUNDLE DIA

Pack size: **100 x EA**

- Cable Clip/Clamp Style: Cable Clamp
- Maximum Bundle Diameter: 5 mm
- Affixing Method: Screw
- Material: Nylon 66
- Colour: Natural
- Length: 18.6 mm
- Width: 9.6 mm
- Depth: 1.2 mm



8178952 Cable Clamp

CABLE CLAMP, 3.1MM BUNDLE DIA

Pack size: **100 x EA**

- Cable Clip/Clamp Style: Cable Clamp
- Maximum Bundle Diameter: 3.1 mm
- Affixing Method: Screw
- Material: Nylon 66
- Colour: Natural
- Length: 17 mm
- Width: 9.6 mm
- Depth: 1.2 mm



8178956 Cable Clamp

CABLE CLAMP, 12.7MM BUNDLE DIA

Pack size: **100 x EA**

- Cable Clip/Clamp Style: P Clamp
- Maximum Bundle Diameter: 12.7 mm
- Affixing Method: Screw
- Material: Nylon 66
- Colour: Natural
- Length: 31 mm
- Width: 12 mm
- Depth: 1.5 mm



8178959 P Clamp

RS PRO GREY NYLON CABLE CLAMP, 14MM MAX. BUNDLE

Pack size: **50 x EA**

- Cable Clip/Clamp Style: Cable Clamp
- Maximum Bundle Diameter: 14 mm
- Affixing Method: Self Adhesive
- Material: Nylon 66
- Colour: Grey
- Length: 30 mm
- Width: 24.5 mm
- Dimensions [L x W (x D)]: 30 x 24.5 mm



8178962 Cable Clamp

CABLE CLAMP, 6.35MM BUNDLE DIA

Pack size: **100 x EA**

- Cable Clip/Clamp Style: Cable Clamp
- Maximum Bundle Diameter: 6.4 mm
- Affixing Method: Screw
- Material: Nylon 66
- Colour: Natural
- Length: 20 mm
- Width: 10 mm
- Depth: 1.4 mm




8178968 Cable Clamp

CABLE CLAMP, 16~18MM BUNDLE DIA

Pack size: **50 x EA**

- Cable Clip/Clamp Style: Cable Clamp
- Maximum Bundle Diameter: 18 mm
- Affixing Method: Self Adhesive
- Material: Nylon 66
- Colour: Grey
- Length: 30 mm
- Width: 24.5 mm
- Dimensions [L x W (x D)]: 30 x 24.5 mm



8178971 Cable Clamp

CABLE CLAMP, 6~7MM BUNDLE DIA

Pack size: **50 x EA**

- Cable Clip/Clamp Style: Cable Clamp
- Maximum Bundle Diameter: 7 mm
- Affixing Method: Self Adhesive
- Material: Nylon 66
- Colour: Grey
- Length: 25 mm
- Width: 20 mm
- Dimensions [L x W (x D)]: 25 x 20 mm



8178974 Cable Clamp

CABLE CLAMP, 9~10MM BUNDLE DIA

Pack size: **50 x EA**

- Cable Clip/Clamp Style: Cable Clamp
- Maximum Bundle Diameter: 10 mm
- Affixing Method: Self Adhesive
- Material: Nylon 66
- Colour: Grey
- Length: 30 mm
- Width: 24.5 mm
- Dimensions [L x W (x D)]: 30 x 24.5 mm



8178978 Cable Clamp

CABLEMAT CARPET TOP

Pack size: **1 x EA**

- Length: 1200 mm
- Internal Dimensions: 400 x 1200 mm
- Width: 400 mm
- Colour: Black
- Material: Rubber
- Standards Met: EN 13501-1, EN 14041



1757246 1200 mm

RS PRO 1.2M BLACK CABLE COVER IN RUBBER

Pack size: **1 x EA**

- Length: 1.2 m
- Internal Dimensions: 400 x 1200 mm
- Width: 400 mm
- Colour: Black
- Material: Rubber
- Standards Met: EN 13501-1



1757247 1.2 m

RS PRO 1M BLACK, RED CABLE COVER IN RUBBER

Pack size: **1 x EA**

- Length: 1 m
- Width: 24.9 mm
- Colour: Black, Red
- Material: Rubber
- Number of Channels: 2



2184305 1 m

RS PRO 1M BLACK, RED CABLE COVER IN RUBBER

Pack size: **1 x EA**

- Length: 1 m
- Width: 50.0 mm
- Colour: Black, Red
- Material: Rubber
- Number of Channels: 3



2184306 1 m

RS PRO 1.83M GREY CABLE COVER IN PVC, 7.4MM INSIDE DIA.

Pack size: **1 x EA**

- Inside Diameter: 7.4 mm
- Length: 1.83 m
- Width: 25.4 mm
- Internal Dimensions: 7.4 x 3.8 mm
- Colour: Grey
- Material: PVC



8659492 7.4 mm

RS PRO 1.83M BROWN CABLE COVER IN PVC, 7.4MM INSIDE DIA.

Pack size: **1 x EA**

- Inside Diameter: 7.4 mm
- Length: 1.83 m
- Width: 25.4 mm
- Internal Dimensions: 7.4 x 3.8 mm
- Colour: Brown
- Material: PVC



8659495 7.4 mm

RS PRO 1.83M WHITE CABLE COVER IN PVC, 7.4MM INSIDE DIA.

Pack size: **1 x EA**

- Inside Diameter: 7.4 mm
- Length: 1.83 m
- Width: 25.4 mm
- Internal Dimensions: 7.4 x 3.8 mm
- Colour: White
- Material: PVC



8659499 7.4 mm

RS PRO 1.83M GREY CABLE COVER IN PVC, 14.8MM INSIDE DIA.

Pack size: **1 x EA**

- Inside Diameter: 14.8 mm
- Length: 1.83 m
- Width: 50.8 mm
- Internal Dimensions: 14.8 x 7.4 mm
- Colour: Grey
- Material: PVC



8659502 14.8 mm

RS PRO 1.83M BROWN CABLE COVER IN PVC, 14.8MM INSIDE DIA.

Pack size: **1 x EA**

- Inside Diameter: 14.8 mm
- Length: 1.83 m
- Width: 50.8 mm
- Internal Dimensions: 14.8 x 7.4 mm
- Colour: Brown
- Material: PVC



8659506 14.8 mm

RS PRO 1.83M BLACK CABLE COVER IN PVC, 7.4MM INSIDE DIA.

Pack size: **1 x EA**

- Inside Diameter: 7.4 mm
- Length: 1.83 m
- Width: 25.4 mm
- Internal Dimensions: 7.4 x 3.8 mm
- Colour: Black
- Material: PVC



8659509 7.4 mm

RS PRO 1.83M GREY CABLE COVER IN PVC, 19MM INSIDE DIA.

Pack size: **1 x EA**

- Inside Diameter: 19 mm
- Length: 1.83 m
- Width: 66 mm
- Internal Dimensions: 19 x 10.9 mm
- Colour: Grey
- Material: PVC



8659512 19 mm

RS PRO 1.83M WHITE CABLE COVER IN PVC, 14.8MM INSIDE DIA.

Pack size: **1 x EA**

- Inside Diameter: 14.8 mm
- Length: 1.83 m
- Width: 50.8 mm
- Internal Dimensions: 14.8 x 7.8 mm
- Colour: White
- Material: PVC



8659515 14.8 mm

RS PRO 1.83M BLACK CABLE COVER IN PVC, 14.8MM INSIDE DIA.

Pack size: **1 x EA**

- Inside Diameter: 14.8 mm
- Length: 1.83 m
- Width: 50.8 mm
- Internal Dimensions: 14.8 x 7.8 mm
- Colour: Black
- Material: PVC



8659518 14.8 mm

RS PRO 1.83M BROWN CABLE COVER IN PVC, 19MM INSIDE DIA.

Pack size: **1 x EA**

- Inside Diameter: 19 mm
- Length: 1.83 m
- Width: 66 mm
- Internal Dimensions: 19 x 10.9 mm
- Colour: Brown
- Material: PVC



8659521 19 mm

RS PRO 1.83M WHITE CABLE COVER IN PVC, 19MM INSIDE DIA.

Pack size: **1 x EA**

- Inside Diameter: 19 mm
- Length: 1.83 m
- Width: 66 mm
- Internal Dimensions: 19 x 10.9 mm
- Colour: White
- Material: PVC



8659524 19 mm

RS PRO 1.83M BLACK CABLE COVER IN PVC, 19MM INSIDE DIA.

Pack size: **1 x EA**

- Inside Diameter: 19 mm
- Length: 1.83 m
- Width: 66 mm
- Internal Dimensions: 19 x 10.9 mm
- Colour: Black
- Material: PVC



8659528 19 mm

RS PRO 1.83M GREY CABLE COVER IN PVC, 22MM INSIDE DIA.

Pack size: **1 x EA**

- Inside Diameter: 22 mm
- Length: 1.83 m
- Width: 76.2 mm
- Internal Dimensions: 22 x 11.6 mm
- Colour: Grey
- Material: PVC



8659537 22 mm

RS PRO 1.83M BLACK CABLE COVER IN PVC, 22MM INSIDE DIA.

Pack size: **1 x EA**

- Inside Diameter: 22 mm
- Length: 1.83 m
- Width: 76.2 mm
- Internal Dimensions: 22 x 11.6 mm
- Colour: Black
- Material: PVC



8659543 22 mm

RS PRO 1.83M GREY CABLE COVER IN PVC, 29.4MM INSIDE DIA.

Pack size: **1 x EA**

- Inside Diameter: 29.4 mm
- Length: 1.83 m
- Width: 101.6 mm
- Internal Dimensions: 29.4 x 15.4 mm
- Colour: Grey
- Material: PVC



8659546 29.4 mm

RS PRO 1.83M BLACK CABLE COVER IN PVC, 29.4MM INSIDE DIA.

Pack size: **1 x EA**

- Inside Diameter: 29.4 mm
- Length: 1.83 m
- Width: 101.6 mm
- Internal Dimensions: 29.4 x 15.4 mm
- Colour: Black
- Material: PVC



8659552 29.4 mm

RS PRO 1M GREY CABLE COVER IN PVC, 7.4MM INSIDE DIA.

Pack size: **1 x EA**

- Inside Diameter: 7.4 mm
- Length: 1 m
- Width: 25.4 mm
- Internal Dimensions: 7.4 x 3.8 mm
- Colour: Grey
- Material: PVC



8659556 7.4 mm

RS PRO 1.83M WHITE CABLE COVER IN PVC, 29.4MM INSIDE DIA.

Pack size: **1 x EA**

- Inside Diameter: 29.4 mm
- Length: 1.83 m
- Width: 101.6 mm
- Internal Dimensions: 29.4 x 15.4 mm
- Colour: White
- Material: PVC



8659559 29.4 mm

RS PRO 1M BLACK CABLE COVER IN PVC, 7.4MM INSIDE DIA.

Pack size: **1 x EA**

- Inside Diameter: 7.4 mm
- Length: 1 m
- Width: 25.4 mm
- Internal Dimensions: 7.4 x 3.8 mm
- Colour: Black
- Material: PVC



8659562 7.4 mm

RS PRO 1M BROWN CABLE COVER IN PVC, 7.4MM INSIDE DIA.

Pack size: **1 x EA**

- Inside Diameter: 7.4 mm
- Length: 1 m
- Width: 25.4 mm
- Internal Dimensions: 7.4 x 3.8 mm
- Colour: Brown
- Material: PVC



8659565 7.4 mm

RS PRO 1M WHITE CABLE COVER IN PVC, 7.4MM INSIDE DIA.

Pack size: **1 x EA**

- Inside Diameter: 7.4 mm
- Length: 1 m
- Width: 25.4 mm
- Internal Dimensions: 7.4 x 3.8 mm
- Colour: White
- Material: PVC



8659568 7.4 mm

RS PRO 1M GREY CABLE COVER IN PVC, 14.8MM INSIDE DIA.

Pack size: **1 x EA**

- Inside Diameter: 14.8 mm
- Length: 1 m
- Width: 50.8 mm
- Internal Dimensions: 14.8 mm x 7.8 mm
- Colour: Grey
- Material: PVC



8659571 14.8 mm

RS PRO 1M BROWN CABLE COVER IN PVC, 14.8MM INSIDE DIA.

Pack size: **1 x EA**

- Inside Diameter: 14.8 mm
- Length: 1 m
- Width: 50.8 mm
- Internal Dimensions: 14.8 mm x 7.8 mm
- Colour: Brown
- Material: PVC



8659574 14.8 mm

RS PRO 1M WHITE CABLE COVER IN PVC, 14.8 X 7.8MM INSIDE DIA.

Pack size: **1 x EA**

- Inside Diameter: 14.8 x 7.8 mm
- Length: 1 m
- Width: 50.8 mm
- Internal Dimensions: 14.8 x 7.8 mm
- Colour: White
- Material: PVC



8659578 14.8 x 7.8 mm

RS PRO 1M GREY CABLE COVER IN PVC, 19 X 10.9MM INSIDE DIA.

Pack size: **1 x EA**

- Inside Diameter: 19 x 10.9 mm
- Length: 1 m
- Width: 66 mm
- Internal Dimensions: 19 x 10.9 mm
- Colour: Grey
- Material: PVC



8659580 19 x 10.9 mm

RS PRO 1M BROWN CABLE COVER IN PVC, 19 X 10.9MM INSIDE DIA.

Pack size: **1 x EA**

- Inside Diameter: 19 x 10.9 mm
- Length: 1 m
- Width: 66 mm
- Internal Dimensions: 19 x 10.9 mm
- Colour: Brown
- Material: PVC



8659584 19 x 10.9 mm

RS PRO 1M BLACK CABLE COVER IN PVC, 14.8 X 7.8MM INSIDE DIA.

Pack size: **1 x EA**

- Inside Diameter: 14.8 x 7.8 mm
- Length: 1 m
- Width: 50.8 mm
- Internal Dimensions: 14.8 x 7.8 mm
- Colour: Black
- Material: PVC



8659587 14.8 x 7.8 mm

RS PRO 1M GREY CABLE COVER IN PVC, 22MM INSIDE DIA.

Pack size: **1 x EA**

- Inside Diameter: 22 mm
- Length: 1 m
- Width: 76.2 mm
- Internal Dimensions: 22 x 11.6 mm
- Colour: Grey
- Material: PVC



8659590 22 mm

RS PRO 1M WHITE CABLE COVER IN PVC, 19 X 10.9MM INSIDE DIA.

Pack size: **1 x EA**

- Inside Diameter: 19 x 10.9 mm
- Length: 1 m
- Width: 66 mm
- Internal Dimensions: 19 x 10.9 mm
- Colour: White
- Material: PVC



8659593 19 x 10.9 mm

RS PRO 1M BLACK CABLE COVER IN PVC, 19 X 10.9MM INSIDE DIA.

Pack size: **1 x EA**

- Inside Diameter: 19 x 10.9 mm
- Length: 1 m
- Internal Dimensions: 19 x 10.9 mm
- Width: 66 mm
- Colour: Black
- Material: PVC



8659596 19 x 10.9 mm

RS PRO 1M WHITE CABLE COVER IN PVC, 22 X 11.6MM INSIDE DIA.

Pack size: **1 x EA**

- Inside Diameter: 22 x 11.6 mm
- Length: 1 m
- Width: 76.2 mm
- Internal Dimensions: 22 x 11.6 mm
- Colour: White
- Material: PVC



8659603 22 x 11.6 mm

RS PRO 1M BLACK CABLE COVER IN PVC, 22MM INSIDE DIA.

Pack size: **1 x EA**

- Inside Diameter: 22 mm
- Length: 1 m
- Width: 76.2 mm
- Internal Dimensions: 22 x 11.6 mm
- Colour: Black
- Material: PVC



8659607 22 mm

RS PRO 1M GREY CABLE COVER IN PVC, 29.4MM INSIDE DIA.

Pack size: **1 x EA**

- Inside Diameter: 29.4 mm
- Length: 1 m
- Width: 101.6 mm
- Internal Dimensions: 29.4 x 15.4 mm
- Colour: Grey
- Material: PVC



8659616 29.4 mm

RS PRO 1M BROWN CABLE COVER IN PVC, 29.4MM INSIDE DIA.

Pack size: **1 x EA**

- Inside Diameter: 29.4 mm
- Length: 1 m
- Width: 101.6 mm
- Internal Dimensions: 29.4 x 15.4 mm
- Colour: Brown
- Material: PVC



8659619 29.4 mm

RS PRO 1M BLACK CABLE COVER IN PVC, 29.4MM INSIDE DIA.

Pack size: **1 x EA**

- Inside Diameter: 29.4 mm
- Length: 1 m
- Width: 101.6 mm
- Internal Dimensions: 29.4 x 15.4 mm
- Colour: Black
- Material: PVC



8659622 29.4 mm

ABB CABLE GLAND ADAPTOR, PG16 EXTERIOR THREAD, M16 INTERIOR

Pack size: **5 x EA**

- Exterior Thread Size: PG16
- Interior Thread Size: M16
- Material: Nylon 66
- Type: Adaptor
- Thread Size: PG16 → M16
- Colour: Grey
- Standards Met: UL 94V-2
- Minimum Operating Temperature: -20 °C



2813296 PG16

RS PRO CABLE GLAND ADAPTOR, PG13 EXTERIOR THREAD, M16

Pack size: **5 x EA**

- Exterior Thread Size: PG13
- Interior Thread Size: M16
- Material: Nylon 66
- Type: Adaptor
- Thread Size: PG13 → M16
- Colour: Grey
- Standards Met: UL 94V-2



8178883 PG13

RS PRO CABLE GLAND ADAPTOR, PG9 EXTERIOR THREAD, M16

Pack size: **5 x EA**

- Exterior Thread Size: PG9
- Interior Thread Size: M16
- Material: Nylon 66
- Type: Adaptor
- Thread Size: PG9 → M16
- Colour: Grey
- Standards Met: UL 94V-2



8178886 PG9

RS PRO CABLE GLAND ADAPTOR, PG11 EXTERIOR THREAD, M16

Pack size: **5 x EA**

- Exterior Thread Size: PG11
- Interior Thread Size: M16
- Material: Nylon 66
- Type: Adaptor
- Thread Size: PG11 → M16
- Colour: Grey
- Standards Met: UL 94V-2



8178889 PG11

RS PRO CABLE GLAND ADAPTOR, M25 X 1.5 EXTERIOR THREAD, M32 X

Pack size: **10 x EA**

- Exterior Thread Size: M25 x 1.5
- Interior Thread Size: M32 x 1.5
- Material: Nylon 66
- Type: Enlarger
- Thread Size: M25 → M32
- Colour: Grey
- Standards Met: UL 94V-2



8229852 M25 x 1.5

RS PRO CABLE GLAND ADAPTOR, M16 X 1.5 EXTERIOR THREAD, M20 X 1.5

Pack size: **10 x EA**

- Exterior Thread Size: M16 x 1.5
- Interior Thread Size: M20 x 1.5
- Material: Nylon 66
- Type: Enlarger
- Thread Size: M16 → M20
- Colour: Grey
- Standards Met: UL 94V-2



8229855 M16 x 1.5

RS PRO CABLE GLAND ADAPTOR, M20 X 1.5 EXTERIOR THREAD, M25 X

Pack size: **10 x EA**

- Exterior Thread Size: M20 x 1.5
- Interior Thread Size: M25 x 1.5
- Material: Nylon 66
- Type: Enlarger
- Thread Size: M20 → M25
- Colour: Grey
- Standards Met: UL 94V-2



8229858 M20 x 1.5

RS PRO CABLE GLAND ADAPTOR, M12 X 1.5 EXTERIOR THREAD, M16 X 1.5

Pack size: **10 x EA**

- Exterior Thread Size: M12 x 1.5
- Interior Thread Size: M16 x 1.5
- Material: Nylon 66
- Type: Enlarger
- Thread Size: M12 → M16
- Colour: Black
- Standards Met: UL 94V-2



8229861 M12 x 1.5

RS PRO CABLE GLAND ADAPTOR, M16 X 1.5 EXTERIOR THREAD, M20 X 1.5

Pack size: **10 x EA**

- Exterior Thread Size: M16 x 1.5
- Interior Thread Size: M20 x 1.5
- Material: Nylon 66
- Type: Enlarger
- Thread Size: M16 → M20
- Colour: Black
- Standards Met: UL 94V-2



8229864 M16 x 1.5

RS PRO CABLE GLAND ADAPTOR, M25 X 1.5 EXTERIOR THREAD, M20 X

Pack size: **10 x EA**

- Exterior Thread Size: M25 x 1.5
- Interior Thread Size: M20 x 1.5
- Material: Nylon 66
- Type: Enlarger
- Thread Size: M25 → M20
- Colour: Black
- Standards Met: UL 94V-2



8229868 M25 x 1.5

RS PRO CABLE GLAND ADAPTOR, M16 X 1.5 EXTERIOR THREAD, M12 X 1.5

Pack size: **10 x EA**

- Exterior Thread Size: M16 x 1.5
- Interior Thread Size: M12 x 1.5
- Material: Nylon 66
- Type: Reducer
- Thread Size: M16 → M12
- Colour: Black
- Standards Met: UL 94V-2



8229870 M16 x 1.5

RS PRO CABLE GLAND ADAPTOR, M20 X 1.5 EXTERIOR THREAD, M16 X

Pack size: **10 x EA**

- Exterior Thread Size: M20 x 1.5
- Interior Thread Size: M16 x 1.5
- Material: Nylon 66
- Type: Reducer
- Thread Size: M20 → M16
- Colour: Black
- Standards Met: UL 94V-2



8229874 M20 x 1.5

RS PRO CABLE GLAND ADAPTOR, M25 X 1.5 EXTERIOR THREAD, M32 X

Pack size: **10 x EA**

- Exterior Thread Size: M25 x 1.5
- Interior Thread Size: M32 x 1.5
- Material: Nylon 66
- Type: Enlarger
- Thread Size: M25 → M32
- Colour: Black
- Standards Met: UL 94V-2



8229877 M25 x 1.5

RS PRO CABLE GLAND ADAPTOR, M16 X 1.5 EXTERIOR THREAD, M12 X 1.5

Pack size: **10 x EA**

- Exterior Thread Size: M16 x 1.5
- Interior Thread Size: M12 x 1.5
- Material: Nylon 66
- Type: Reducer
- Thread Size: M16 → M12
- Colour: Grey
- Standards Met: UL 94V-2



8229880 M16 x 1.5

RS PRO CABLE GLAND ADAPTOR, M25 X 1.5 EXTERIOR THREAD, M20 X

Pack size: **10 x EA**

- Exterior Thread Size: M25 x 1.5
- Interior Thread Size: M20 x 1.5
- Material: Nylon 66
- Type: Reducer
- Thread Size: M25 → M20
- Colour: Black
- Standards Met: UL 94V-2



8229883 M25 x 1.5

RS PRO CABLE GLAND ADAPTOR, M32 X 1.5 EXTERIOR THREAD, M25 X

Pack size: **10 x EA**

- Exterior Thread Size: M32 x 1.5
- Interior Thread Size: M25 x 1.5
- Material: Nylon 66
- Type: Reducer
- Thread Size: M32 → M25
- Colour: Black
- Standards Met: UL 94V-2



8229886 M32 x 1.5

RS PRO CABLE GLAND ADAPTOR, M25 X 1.5 EXTERIOR THREAD, M20 X

Pack size: **10 x EA**

- Exterior Thread Size: M25 x 1.5
- Interior Thread Size: M20 x 1.5
- Material: Nylon 66
- Type: Reducer
- Thread Size: M25 → M20
- Colour: Grey
- Standards Met: UL 94V-2



8229892 M25 x 1.5

RS PRO CABLE GLAND ADAPTOR, M32 X 1.5 EXTERIOR THREAD, M25 X

Pack size: **10 x EA**

- Exterior Thread Size: M32 x 1.5
- Interior Thread Size: M25 x 1.5
- Material: Nylon 66
- Type: Reducer
- Thread Size: M32 → M25
- Colour: Grey
- Standards Met: UL 94V-2



8229896 M32 x 1.5

RS PRO CABLE GLAND ADAPTOR, M20 X 1.5 EXTERIOR THREAD, M16 X

Pack size: **10 x EA**

- Exterior Thread Size: M20 x 1.5
- Interior Thread Size: M16 x 1.5
- Material: Nylon 66
- Type: Reducer
- Thread Size: M20 → M16
- Colour: Grey
- Standards Met: UL 94V-2



8229899 M20 x 1.5

RS PRO GREY NYLON 66 CABLE GLAND LOCKNUT, PG13.5 THREAD, IP68

Pack size: **25 x EA**

- Material: Nylon 66
- Thread Size: PG13.5
- Colour: Grey
- IP Rating: IP68



8229704 Nylon 66

RS PRO BLACK NYLON 66 CABLE GLAND LOCKNUT, PG9 THREAD, IP68

Pack size: **25 x EA**

- Material: Nylon 66
- Thread Size: PG9
- Colour: Black
- IP Rating: IP68



8229717 Nylon 66

RS PRO BLACK NYLON 66 CABLE GLAND LOCKNUT, PG13.5 THREAD, IP68

Pack size: **25 x EA**

- Material: Nylon 66
- Thread Size: PG13.5
- Colour: Black
- IP Rating: IP68



8229729 Nylon 66

RS PRO BLACK NYLON 66 CABLE GLAND LOCKNUT, PG21 THREAD, IP68

Pack size: **25 x EA**

- Material: Nylon 66
- Thread Size: PG21
- Colour: Black
- IP Rating: IP68



8229732 Nylon 66

RS PRO BLACK NYLON 66 CABLE GLAND LOCKNUT, PG29 THREAD,

Pack size: **25 x EA**

- Material: Nylon 66
- Thread Size: PG29
- Colour: Black
- IP Rating: IP68



8229735 Nylon 66

M12 X 1.5 GREY LOCKNUT IP68

Pack size: **25 x EA**

- Material: Nylon 66
- Thread Size: M12
- Colour: Grey
- IP Rating: IP68



8229791 Nylon 66

M16 X 1.5 GREY LOCKNUT IP68

Pack size: **25 x EA**

- Material: Nylon 66
- Thread Size: M16
- Colour: Grey
- IP Rating: IP68



8229795 Nylon 66

M32 X 1.5 GREY LOCKNUT IP68

Pack size: **25 x EA**

- Material: Nylon 66
- Thread Size: M32
- Colour: Grey
- IP Rating: IP68



8229802 Nylon 66

M20 X 1.5 GREY LOCKNUT IP68

Pack size: **25 x EA**

- Material: Nylon 66
- Thread Size: M20
- Colour: Grey
- IP Rating: IP68



8229805 Nylon 66

M25 X 1.5 GREY LOCKNUT IP68

Pack size: **25 x EA**

- Material: Nylon 66
- Thread Size: M25
- Colour: Grey
- IP Rating: IP68



8229808 Nylon 66

M16 X 1.5 WHITE LOCKNUT IP68

Pack size: **25 x EA**

- Material: Nylon 66
- Thread Size: M16
- Colour: White
- IP Rating: IP68



8229811 Nylon 66

M20 X 1.5 WHITE LOCKNUT IP68

Pack size: **25 x EA**

- Material: Nylon 66
- Thread Size: M20
- Colour: White
- IP Rating: IP68



8229814 Nylon 66

RS PRO WHITE NYLON 66 CABLE GLAND LOCKNUT, M25 THREAD, IP68

Pack size: **25 x EA**

- Material: Nylon 66
- Thread Size: M25
- Colour: White
- IP Rating: IP68



8229818 Nylon 66

RS PRO RED NYLON 66 CABLE GLAND LOCKNUT, M20 THREAD, IP68

Pack size: **25 x EA**

- Material: Nylon 66
- Thread Size: M20
- Colour: Red
- IP Rating: IP68



8229820 Nylon 66

RS PRO RED NYLON 66 CABLE GLAND LOCKNUT, M25 THREAD, IP68

Pack size: **25 x EA**

- Material: Nylon 66
- Thread Size: M25
- Colour: Red
- IP Rating: IP68



8229824 Nylon 66

M20 X 1.5 BLACK LOCKNUT IP68

Pack size: **25 x EA**

- Material: Nylon 66
- Thread Size: M20
- Colour: Black
- IP Rating: IP68



8229830 Nylon 66

M12 X 1.5 BLACK LOCKNUT IP68

Pack size: **25 x EA**

- Material: Nylon 66
- Thread Size: M12
- Colour: Black
- IP Rating: IP68



8229833 Nylon 66

RS PRO BLACK NYLON 66 CABLE GLAND LOCKNUT, M16 THREAD, IP68

Pack size: **25 x EA**

- Material: Nylon 66
- Thread Size: M16
- Colour: Black
- IP Rating: IP68



8229836 Nylon 66

RS PRO BLACK NYLON 66 CABLE GLAND LOCKNUT, M32 THREAD, IP68

Pack size: **25 x EA**

- Material: Nylon 66
- Thread Size: M32
- Colour: Black
- IP Rating: IP68



8229842 Nylon 66

M25 X 1.5 BLACK LOCKNUT IP68

Pack size: **25 x EA**

- Material: Nylon 66
- Thread Size: M25
- Colour: Black
- IP Rating: IP68



8229849 Nylon 66

RS PRO BLANKING PLUG, M12, 12.2MM HOLE DIAMETER, NICKEL

Pack size: **5 x EA**

- Thread Size: M12
- Hole Diameter: 12.2 mm
- Material: Nickel Plated Brass
- Plug Type: Blanking
- Threaded/Unthreaded: Threaded
- Hazardous Area Certification: ATEX
- IP Rating: IP68
- Series: Ex-HSPM



2116788 M12

RS PRO BLANKING PLUG, M16, 16.2MM HOLE DIAMETER, NICKEL

Pack size: **5 x EA**

- Thread Size: M16
- Hole Diameter: 16.2 mm
- Material: Nickel Plated Brass
- Plug Type: Blanking
- Threaded/Unthreaded: Threaded
- Hazardous Area Certification: ATEX
- IP Rating: IP68
- Series: Ex-HSPM



2116789 M16

RS PRO BLANKING PLUG, M20, 20.2MM HOLE DIAMETER, NICKEL

Pack size: **5 x EA**

- Thread Size: M20
- Hole Diameter: 20.2 mm
- Material: Nickel Plated Brass
- Plug Type: Blanking
- Threaded/Unthreaded: Threaded
- Hazardous Area Certification: ATEX
- IP Rating: IP68
- Series: Ex-HSPM



2116790 M20

RS PRO BLANKING PLUG, M25, 25.2MM HOLE DIAMETER, NICKEL

Pack size: **5 x EA**

- Thread Size: M25
- Hole Diameter: 25.2 mm
- Material: Nickel Plated Brass
- Plug Type: Blanking
- Threaded/Unthreaded: Threaded
- Hazardous Area Certification: ATEX
- IP Rating: IP68
- Series: Ex-HSPM



2116791 M25

RS PRO BLANKING PLUG, M32, 32.2MM HOLE DIAMETER, NICKEL

Pack size: **5 x EA**

- Thread Size: M32
- Hole Diameter: 32.2 mm
- Material: Nickel Plated Brass
- Plug Type: Blanking
- Threaded/Unthreaded: Threaded
- Hazardous Area Certification: ATEX
- IP Rating: IP68
- Series: Ex-HSPM



2116792 M32

RS PRO STOPPING PLUG, M20, 20.2MM HOLE DIAMETER, THREADED

Pack size: **10 x EA**

- Thread Size: M20
- Hole Diameter: 20.2 mm
- Plug Type: Stopping
- Threaded/Unthreaded: Threaded
- Hazardous Area Certification: ATEX
- IP Rating: IP68
- Series: Ex-SPM



2116793 M20

RS PRO STOPPING PLUG, M25, 25.2MM HOLE DIAMETER, THREADED

Pack size: **10 x EA**

- Thread Size: M25
- Hole Diameter: 25.2 mm
- Plug Type: Stopping
- Threaded/Unthreaded: Threaded
- Hazardous Area Certification: ATEX
- IP Rating: IP68
- Series: Ex-SPM



2116794 M25

RS PRO STOPPING PLUG, M40, 40.2MM HOLE DIAMETER, THREADED

Pack size: **10 x EA**

- Thread Size: M40
- Hole Diameter: 40.2 mm
- Plug Type: Stopping
- Threaded/Unthreaded: Threaded
- Hazardous Area Certification: ATEX
- IP Rating: IP68
- Series: Ex-SPM



2116795 M40

RS PRO BLANKING PLUG, 19.1MM HOLE DIAMETER, NYLON 66, 22.9MM

Pack size: **25 x EA**

- Hole Diameter: 19.1 mm
- Material: Nylon 66
- Plug Type: Blanking
- Diameter: 22.9 mm
- Threaded/Unthreaded: Unthreaded
- Colour: Black
- Series: 81788
- Standards Met: UL 94V-2



8178845 19.1 mm

RS PRO BLANKING PLUG, 5MM HOLE DIAMETER, NYLON 66, 6.3MM

Pack size: **25 x EA**

- Hole Diameter: 5 mm
- Material: Nylon 66
- Plug Type: Blanking
- Diameter: 6.3 mm
- Threaded/Unthreaded: Unthreaded
- Colour: Black
- Series: 81788
- Standards Met: UL 94V-2



8178849 5 mm

RS PRO BLANKING PLUG, 9.5MM HOLE DIAMETER, NYLON 66, 13MM

Pack size: **25 x EA**

- Hole Diameter: 9.5 mm
- Material: Nylon 66
- Plug Type: Blanking
- Diameter: 13 mm
- Threaded/Unthreaded: Unthreaded
- Colour: Black
- Series: 81788
- Standards Met: UL 94V-2



8178851 9.5 mm

RS PRO BLANKING PLUG, 12.7MM HOLE DIAMETER, NYLON 66, 14.5MM

Pack size: **25 x EA**

- Hole Diameter: 12.7 mm
- Material: Nylon 66
- Plug Type: Blanking
- Diameter: 14.5 mm
- Threaded/Unthreaded: Unthreaded
- Colour: Black
- Series: 81788
- Standards Met: UL 94V-2



8178855 12.7 mm

RS PRO BLANKING PLUG, 6MM HOLE DIAMETER, NYLON 66, 7.8MM

Pack size: **25 x EA**

- Hole Diameter: 6 mm
- Material: Nylon 66
- Plug Type: Blanking
- Diameter: 7.8 mm
- Threaded/Unthreaded: Unthreaded
- Colour: Black
- Series: 81788
- Standards Met: UL 94V-2



8178858 6 mm

RS PRO BLANKING PLUG, 15.9MM HOLE DIAMETER, NYLON 66, 19.5MM

Pack size: **25 x EA**

- Hole Diameter: 15.9 mm
- Material: Nylon 66
- Plug Type: Blanking
- Diameter: 19.5 mm
- Threaded/Unthreaded: Unthreaded
- Colour: Black
- Series: 81788
- Standards Met: UL 94V-2



8178864 15.9 mm

RS PRO BLANKING PLUG, 25.4MM HOLE DIAMETER, NYLON 66, 29MM

Pack size: **25 x EA**

- Hole Diameter: 25.4 mm
- Material: Nylon 66
- Plug Type: Blanking
- Diameter: 29 mm
- Threaded/Unthreaded: Unthreaded
- Colour: Black
- Series: 81788
- Standards Met: UL 94V-2



8178867 25.4 mm

RS PRO BLANKING BLANKING PLUG, M20 X 1.5, 19.9MM HOLE DIAMETER,

Pack size: **100 x EA**

- Thread Size: M20 x 1.5
- Hole Diameter: 19.9 mm
- Material: Nylon 66
- Plug Type: Blanking
- Diameter: 24 mm
- Threaded/Unthreaded: Threaded
- Colour: Black
- Series: 86597



8659742 M20 x 1.5

RS PRO BLANKING BLANKING PLUG, M12 X 1.5, 11.7MM HOLE DIAMETER,

Pack size: **100 x EA**

- Thread Size: M12 x 1.5
- Hole Diameter: 11.7 mm
- Material: Nylon 66
- Plug Type: Blanking
- Diameter: 15 mm
- Threaded/Unthreaded: Threaded
- Colour: Black
- Series: 86597



8659745 M12 x 1.5

RS PRO BLANKING BLANKING PLUG, M16 X 1.5, 15.7MM HOLE DIAMETER,

Pack size: **100 x EA**

- Thread Size: M16 x 1.5
- Hole Diameter: 15.7 mm
- Material: Nylon 66
- Plug Type: Blanking
- Diameter: 20 mm
- Threaded/Unthreaded: Threaded
- Colour: Black
- Series: 86597



8659748 M16 x 1.5

RS PRO BLANKING BLANKING PLUG, M25 X 1.5, 24.7MM HOLE DIAMETER,

Pack size: **100 x EA**

- Thread Size: M25 x 1.5
- Hole Diameter: 24.7 mm
- Material: Nylon 66
- Plug Type: Blanking
- Diameter: 29.7 mm
- Threaded/Unthreaded: Threaded
- Colour: Black
- Series: 86597



8659751 M25 x 1.5

RS PRO BLANKING BLANKING PLUG, M32 X 1.5, 31.7MM HOLE DIAMETER,

Pack size: **50 x EA**

- Thread Size: M32 x 1.5
- Hole Diameter: 31.7 mm
- Material: Nylon 66
- Plug Type: Blanking
- Diameter: 36.6 mm
- Threaded/Unthreaded: Threaded
- Colour: Black
- Series: 86597



8659754 M32 x 1.5

RS PRO BLANKING BLANKING PLUG, M40 X 1.5, 39.9MM HOLE DIAMETER,

Pack size: **50 x EA**

- Thread Size: M40 x 1.5
- Hole Diameter: 39.9 mm
- Material: Nylon 66
- Plug Type: Blanking
- Diameter: 45.8 mm
- Threaded/Unthreaded: Threaded
- Colour: Black
- Series: 86597



8659758 M40 x 1.5

RS PRO BLANKING BLANKING PLUG, M63 X 1.5, 62.4MM HOLE DIAMETER,

Pack size: **10 x EA**

- Thread Size: M63 x 1.5
- Hole Diameter: 62.4 mm
- Material: Nylon 66
- Plug Type: Blanking
- Diameter: 69.3 mm
- Threaded/Unthreaded: Threaded
- Colour: Black
- Series: 86597



8659760 M63 x 1.5

RS PRO BLANKING BLANKING PLUG, M12 X 1.5, 11.7MM HOLE DIAMETER,

Pack size: **100 x EA**

- Thread Size: M12 x 1.5
- Hole Diameter: 11.7 mm
- Material: Nylon 66
- Plug Type: Blanking
- Diameter: 15 mm
- Threaded/Unthreaded: Threaded
- Colour: Grey
- Series: 86597



8659764 M12 x 1.5

RS PRO BLANKING BLANKING PLUG, M50 X 1.5, 49.9MM HOLE DIAMETER,

Pack size: **10 x EA**

- Thread Size: M50 x 1.5
- Hole Diameter: 49.9 mm
- Material: Nylon 66
- Plug Type: Blanking
- Diameter: 55.5 mm
- Threaded/Unthreaded: Threaded
- Colour: Black
- Series: 86597



8659767 M50 x 1.5

RS PRO BLANKING BLANKING PLUG, M25 X 1.5, 24.7MM HOLE DIAMETER,

Pack size: **100 x EA**

- Thread Size: M25 x 1.5
- Hole Diameter: 24.7 mm
- Material: Nylon 66
- Plug Type: Blanking
- Diameter: 29.7 mm
- Threaded/Unthreaded: Threaded
- Colour: Grey
- Series: 86597



8659770 M25 x 1.5

RS PRO BLANKING BLANKING PLUG, M16 X 1.5, 15.7MM HOLE DIAMETER,

Pack size: **100 x EA**

- Thread Size: M16 x 1.5
- Hole Diameter: 15.7 mm
- Material: Nylon 66
- Plug Type: Blanking
- Diameter: 20 mm
- Threaded/Unthreaded: Threaded
- Colour: Grey
- Series: 86597



8659773 M16 x 1.5

RS PRO BLANKING BLANKING PLUG, M20 X 1.5, 19.9MM HOLE DIAMETER,

Pack size: **100 x EA**

- Thread Size: M20 x 1.5
- Hole Diameter: 19.9 mm
- Material: Nylon 66
- Plug Type: Blanking
- Diameter: 24 mm
- Threaded/Unthreaded: Threaded
- Colour: Grey
- Series: 86597



8659776 M20 x 1.5

RS PRO BLANKING BLANKING PLUG, M40 X 1.5, 39.9MM HOLE DIAMETER,

Pack size: **50 x EA**

- Thread Size: M40 x 1.5
- Hole Diameter: 39.9 mm
- Material: Nylon 66
- Plug Type: Blanking
- Diameter: 45.8 mm
- Threaded/Unthreaded: Threaded
- Colour: Grey
- Series: 86597



8659782 M40 x 1.5

RS PRO BLANKING BLANKING PLUG, M50 X 1.5, 49.9MM HOLE DIAMETER,

Pack size: **10 x EA**

- Thread Size: M50 x 1.5
- Hole Diameter: 49.9 mm
- Material: Nylon 66
- Plug Type: Blanking
- Diameter: 55.5 mm
- Threaded/Unthreaded: Threaded
- Colour: Grey
- Series: 86597



8659786 M50 x 1.5

RS PRO BLANKING BLANKING PLUG, M32 X 1.5, 31.7MM HOLE DIAMETER,

Pack size: **50 x EA**

- Thread Size: M32 x 1.5
- Hole Diameter: 31.7 mm
- Material: Nylon 66
- Plug Type: Blanking
- Diameter: 36.6 mm
- Threaded/Unthreaded: Threaded
- Colour: Grey
- Series: 86597



8659789 M32 x 1.5

RS PRO BLANKING BLANKING PLUG, 12.7MM HOLE DIAMETER, NYLON 66,

Pack size: **100 x EA**

- Hole Diameter: 12.7 mm
- Material: Nylon 66
- Plug Type: Blanking
- Diameter: 16.5 mm
- Threaded/Unthreaded: Unthreaded
- Colour: Black
- For Use With: Chassis Thickness Under 3.2 mm
- Series: 86597



8659792 12.7 mm

RS PRO BLANKING BLANKING PLUG, M63 X 1.5, 62.4MM HOLE DIAMETER,

Pack size: **10 x EA**

- Thread Size: M63 x 1.5
- Hole Diameter: 62.4 mm
- Material: Nylon 66
- Plug Type: Blanking
- Diameter: 69.3 mm
- Threaded/Unthreaded: Threaded
- Colour: Grey
- Series: 86597



8659795 M63 x 1.5

RS PRO BLANKING BLANKING PLUG, 7.9MM HOLE DIAMETER, NYLON 66,

Pack size: **100 x EA**

- Hole Diameter: 7.9 mm
- Material: Nylon 66
- Plug Type: Blanking
- Diameter: 10.3 mm
- Threaded/Unthreaded: Unthreaded
- Colour: Black
- For Use With: Chassis Thickness Under 3.2 mm
- Series: 86597



8659798 7.9 mm

RS PRO BLANKING BLANKING PLUG, 14.3MM HOLE DIAMETER, NYLON 66,

Pack size: **100 x EA**

- Hole Diameter: 14.3 mm
- Material: Nylon 66
- Plug Type: Blanking
- Diameter: 16.7 mm
- Threaded/Unthreaded: Unthreaded
- Colour: Black
- For Use With: Chassis Thickness Under 3.2 mm
- Series: 86598



8659802 14.3 mm

RS PRO BLANKING BLANKING PLUG, 22.2MM HOLE DIAMETER, NYLON 66,

Pack size: **100 x EA**

- Hole Diameter: 22.2 mm
- Material: Nylon 66
- Plug Type: Blanking
- Diameter: 25.8 mm
- Threaded/Unthreaded: Unthreaded
- Colour: Black
- For Use With: Chassis Thickness Under 3.2 mm
- Series: 86598



8659805 22.2 mm

RS PRO BLANKING BLANKING PLUG, 30.1MM HOLE DIAMETER, NYLON 66,

Pack size: **100 x EA**

- Hole Diameter: 30.1 mm
- Material: Nylon 66
- Plug Type: Blanking
- Diameter: 34.2 mm
- Threaded/Unthreaded: Unthreaded
- Colour: Black
- For Use With: Chassis Thickness Under 3.2 mm
- Series: 86598



8659809 30.1 mm

RS PRO BLANKING BLANKING PLUG, 44.5MM HOLE DIAMETER, NYLON 66,

Pack size: **100 x EA**

- Hole Diameter: 44.5 mm
- Material: Nylon 66
- Plug Type: Blanking
- Diameter: 49.7 mm
- Threaded/Unthreaded: Unthreaded
- Colour: Black
- For Use With: Chassis Thickness Under 3.2 mm
- Series: 86598



8659811 44.5 mm

RS PRO BLANKING BLANKING PLUG, 38.1MM HOLE DIAMETER, NYLON 66,

Pack size: **100 x EA**

- Hole Diameter: 38.1 mm
- Material: Nylon 66
- Plug Type: Blanking
- Diameter: 42.1 mm
- Threaded/Unthreaded: Unthreaded
- Colour: Black
- For Use With: Chassis Thickness Under 3.2 mm
- Series: 86598



8659818 38.1 mm

RS PRO BLACK PLASTIC CABLE GLAND, M20 THREAD, 4MM MIN, 7MM

Pack size: **100 x EA**

- Thread Size: M20
- Maximum Cable Diameter: 7 mm
- Minimum Cable Diameter: 4 mm
- Material: Plastic
- Colour: Black
- IP Rating: IP55
- Locknut Included: Yes
- Fire Behaviour: Low Smoke & Fume (LSF)



127170 M20

RS PRO BLACK PLASTIC CABLE GLAND, M16 THREAD, 7MM MIN,

Pack size: **5 x EA**

- Thread Size: M16
- Maximum Cable Diameter: 10.5 mm
- Minimum Cable Diameter: 7 mm
- Material: Plastic
- Colour: Black
- IP Rating: IP55
- Locknut Included: Yes
- Fire Behaviour: Low Smoke & Fume (LSF)



127209 M16

RS PRO BLACK PLASTIC CABLE GLAND, M20 THREAD, 8MM MIN,

Pack size: **5 x EA**

- Thread Size: M20
- Maximum Cable Diameter: 13 mm
- Minimum Cable Diameter: 8 mm
- Material: Plastic
- Colour: Black
- IP Rating: IP55
- Locknut Included: Yes
- Fire Behaviour: Low Smoke & Fume (LSF)



127215 M20

RS PRO BLACK PLASTIC CABLE GLAND, M20 THREAD, 8MM MIN,

Pack size: **100 x EA**

- Thread Size: M20
- Maximum Cable Diameter: 13 mm
- Minimum Cable Diameter: 8 mm
- Material: Plastic
- Colour: Black
- IP Rating: IP55
- Locknut Included: Yes
- Fire Behaviour: Low Smoke & Fume (LSF)



127221 M20

RS PRO WHITE PLASTIC CABLE GLAND, M20 THREAD, 4MM MIN, 7MM

Pack size: **5 x EA**

- Thread Size: M20
- Maximum Cable Diameter: 7 mm
- Minimum Cable Diameter: 4 mm
- Material: Plastic
- Colour: White
- IP Rating: IP55
- Locknut Included: Yes
- Minimum Operating Temperature: -20 °C



127338 M20

HEX,HEAD,NYLON,CABLE,GLAND,IP5 5,WHITE,M16,7-10.5MM

Pack size: **5 x EA**

- Thread Size: M16
- Maximum Cable Diameter: 10.5 mm
- Minimum Cable Diameter: 7 mm
- Material: Plastic
- Colour: White
- IP Rating: IP55
- Locknut Included: Yes
- Minimum Operating Temperature: -20 °C



127344 M16

RS PRO WHITE PLASTIC CABLE GLAND, M20 THREAD, 4MM MIN, 7MM

Pack size: **100 x EA**

- Thread Size: M20
- Maximum Cable Diameter: 7 mm
- Minimum Cable Diameter: 4 mm
- Material: Plastic
- Colour: White
- IP Rating: IP55
- Locknut Included: Yes
- Fire Behaviour: Low Smoke & Fume (LSF)



127372 M20

RS PRO WHITE PLASTIC CABLE GLAND, M20 THREAD, 8MM MIN,

Pack size: **5 x EA**

- Thread Size: M20
- Maximum Cable Diameter: 13 mm
- Minimum Cable Diameter: 8 mm
- Material: Plastic
- Colour: White
- IP Rating: IP55
- Locknut Included: Yes
- Minimum Operating Temperature: -20 °C



127401 M20

RS PRO BLACK PLASTIC CABLE GLAND, M20 THREAD, 7MM MIN,

Pack size: **100 x EA**

- Thread Size: M20
- Maximum Cable Diameter: 10.5 mm
- Minimum Cable Diameter: 7 mm
- Material: Plastic
- Colour: Black
- IP Rating: IP55
- Locknut Included: Yes
- Fire Behaviour: Low Smoke & Fume (LSF)



127619 M20

RS PRO BLACK PLASTIC CABLE GLAND, M20 THREAD, 7MM MIN,

Pack size: **5 x EA**

- Thread Size: M20
- Maximum Cable Diameter: 10.5 mm
- Minimum Cable Diameter: 7 mm
- Material: Plastic
- Colour: Black
- IP Rating: IP55
- Locknut Included: Yes
- Fire Behaviour: Low Smoke & Fume (LSF)



127631 M20

RS PRO BLACK PLASTIC CABLE GLAND KIT, M20 THREAD, 4MM MIN, 7MM

Pack size: **5 x EA**

- Thread Size: M20
- Maximum Cable Diameter: 7 mm
- Minimum Cable Diameter: 4 mm
- Material: Plastic
- Colour: Black
- IP Rating: IP65
- Locknut Included: Yes
- Fire Behaviour: Low Smoke & Fume (LSF)



127647 M20

RS PRO BLACK NYLON CABLE GLAND KIT, M5 THREAD, IP66

Pack size: **1 x EA**

- Thread Size: M5
- Material: Nylon 66
- Colour: Black
- IP Rating: IP66
- Locknut Included: No
- Fire Behaviour: Halogen Free
- Maximum Operating Temperature: +120 °C
- Minimum Operating Temperature: -40 °C



1856068 M5

RS PRO BLACK NYLON CABLE GLAND KIT, M5 THREAD, IP66

Pack size: **1 x EA**

- Thread Size: M5
- Material: Nylon 66
- Colour: Black
- IP Rating: IP66
- Locknut Included: No
- Fire Behaviour: Halogen Free, Self-extinguishing
- Maximum Operating Temperature: +120 °C
- Minimum Operating Temperature: -40 °C



1856069 M5

RS PRO BLACK NYLON CABLE GLAND KIT, M5 THREAD, IP66

Pack size: **1 x EA**

- Thread Size: M5
- Material: Nylon 66
- Colour: Black
- IP Rating: IP66
- Locknut Included: No
- Fire Behaviour: Halogen Free, Self-extinguishing
- Maximum Operating Temperature: +120 °C
- Minimum Operating Temperature: -40 °C



1856070 M5

RS PRO BLACK NYLON CABLE GLAND KIT, M5 THREAD, IP66

Pack size: **1 x EA**

- Thread Size: M5
- Material: Nylon 66
- Colour: Black
- IP Rating: IP66
- Locknut Included: No
- Fire Behaviour: Halogen Free, Self-extinguishing
- Maximum Operating Temperature: +120 °C
- Minimum Operating Temperature: -40 °C



1856071 M5

RS PRO GREY CABLE GLAND KIT, IP66

Pack size: **10 x EA**

- Colour: Grey
- IP Rating: IP66
- Locknut Included: No
- Number of Pieces: 10
- Standards Met: RoHS Compliant
- Kit Includes: Seal Dummy



1856072 Grey

RS PRO GREY CABLE GLAND KIT, 2MM MAX, IP66

Pack size: **10 x EA**

- Maximum Cable Diameter: 2 mm
- Colour: Grey
- IP Rating: IP66
- Locknut Included: No
- Number of Pieces: 10
- Standards Met: RoHS Compliant
- Kit Includes: Seal



1856073 2 mm

RS PRO GREY CABLE GLAND KIT, 4MM MAX, IP66

Pack size: **10 x EA**

- Maximum Cable Diameter: 4 mm
- Colour: Grey
- IP Rating: IP66
- Locknut Included: No
- Number of Pieces: 10
- Standards Met: RoHS Compliant
- Kit Includes: Seal



1856074 4 mm

RS PRO GREY CABLE GLAND KIT, 6MM MAX, IP66

Pack size: **10 x EA**

- Maximum Cable Diameter: 6 mm
- Colour: Grey
- IP Rating: IP66
- Locknut Included: No
- Number of Pieces: 10
- Standards Met: RoHS Compliant
- Kit Includes: Seal



1856075 6 mm

RS PRO GREY TPE CABLE GLAND KIT, 7MM MIN, 8MM MAX, IP66

Pack size: **10 x EA**

- Maximum Cable Diameter: 8 mm
- Minimum Cable Diameter: 7 mm
- Material: TPE
- Colour: Grey
- IP Rating: IP66
- Locknut Included: No
- Maximum Operating Temperature: +90 °C
- Minimum Operating Temperature: -40 °C



1856076 8 mm

RS PRO GREY TPE CABLE GLAND KIT, 9MM MIN, 10MM MAX, IP66

Pack size: **10 x EA**

- Maximum Cable Diameter: 10 mm
- Minimum Cable Diameter: 9 mm
- Material: TPE
- Colour: Grey
- IP Rating: IP66
- Locknut Included: No
- Maximum Operating Temperature: +90 °C
- Minimum Operating Temperature: -40 °C



1856077 10 mm

RS PRO GREY CABLE GLAND KIT, 12MM MAX, IP66

Pack size: **10 x EA**

- Maximum Cable Diameter: 12 mm
- Colour: Grey
- IP Rating: IP66
- Locknut Included: No
- Number of Pieces: 10
- Standards Met: RoHS Compliant
- Kit Includes: Seal



1856079 12 mm

RS PRO GREY CABLE GLAND KIT, 14MM MAX, IP66

Pack size: **10 x EA**

- Maximum Cable Diameter: 14 mm
- Colour: Grey
- IP Rating: IP66
- Locknut Included: No
- Number of Pieces: 10
- Standards Met: RoHS Compliant
- Kit Includes: Seal



1856080 14 mm

RS PRO GREY CABLE GLAND KIT, 5MM MAX, IP66

Pack size: **10 x EA**

- Maximum Cable Diameter: 5 mm
- Colour: Grey
- IP Rating: IP66
- Locknut Included: No
- Number of Pieces: 10
- Standards Met: RoHS Compliant
- Kit Includes: Seal



1856082 5 mm

RS PRO GREY CABLE GLAND KIT, 6MM MAX, IP66

Pack size: **10 x EA**

- Maximum Cable Diameter: 6 mm
- Colour: Grey
- IP Rating: IP66
- Locknut Included: No
- Number of Pieces: 10
- Standards Met: RoHS Compliant
- Kit Includes: Seal



1856083 6 mm

RS PRO GREY CABLE GLAND KIT, 3MM MAX, IP66

Pack size: **10 x EA**

- Maximum Cable Diameter: 3 mm
- Colour: Grey
- IP Rating: IP66
- Locknut Included: No
- Number of Pieces: 10
- Standards Met: RoHS Compliant
- Kit Includes: Seal



1856085 3 mm

RS PRO GREY CABLE GLAND KIT, 4MM MAX, IP66

Pack size: **10 x EA**

- Maximum Cable Diameter: 4 mm
- Colour: Grey
- IP Rating: IP66
- Locknut Included: No
- Number of Pieces: 10
- Standards Met: RoHS Compliant
- Kit Includes: Seal



1856086 4 mm

RS PRO GREY CABLE GLAND KIT, 4.5MM MAX, IP66

Pack size: **10 x EA**

- Maximum Cable Diameter: 4.5 mm
- Colour: Grey
- IP Rating: IP66
- Locknut Included: No
- Number of Pieces: 10
- Standards Met: RoHS Compliant
- Kit Includes: Seal



1856087 4.5 mm

RS PRO GREY CABLE GLAND KIT, 6.5MM MAX, IP66

Pack size: **10 x EA**

- Maximum Cable Diameter: 6.5 mm
- Colour: Grey
- IP Rating: IP66
- Locknut Included: No
- Number of Pieces: 10
- Standards Met: RoHS Compliant
- Kit Includes: Seal



1856088 6.5 mm

RS PRO GREY CABLE GLAND KIT, IP66

Pack size: **10 x EA**

- Colour: Grey
- IP Rating: IP66
- Locknut Included: No
- Number of Pieces: 10
- Standards Met: RoHS Compliant
- Kit Includes: Seal Dummy



1856089 Grey

RS PRO GREY CABLE GLAND KIT, 16MM MAX, IP66

Pack size: **10 x EA**

- Maximum Cable Diameter: 16 mm
- Colour: Grey
- IP Rating: IP66
- Locknut Included: No
- Number of Pieces: 10
- Standards Met: RoHS Compliant
- Kit Includes: Seal



1856091 16 mm

RS PRO BLACK NYLON CABLE GLAND KIT, M20 THREAD, IP66

Pack size: **10 x EA**

- Thread Size: M20
- Material: Nylon 66
- Colour: Black
- IP Rating: IP66
- Locknut Included: Yes
- Fire Behaviour: Halogen Free, Self-extinguishing
- Maximum Operating Temperature: +120 °C
- Minimum Operating Temperature: -40 °C



1856101 M20

RS PRO BLACK NYLON CABLE GLAND KIT, M25 THREAD, IP66

Pack size: **10 x EA**

- Thread Size: M25
- Material: Nylon 66
- Colour: Black
- IP Rating: IP66
- Locknut Included: No
- Fire Behaviour: Halogen Free, Self-extinguishing
- Maximum Operating Temperature: +120 °C
- Minimum Operating Temperature: -40 °C



1856102 M25

RS PRO BLACK NYLON CABLE GLAND KIT, M32 THREAD, IP66

Pack size: **10 x EA**

- Thread Size: M32
- Material: Nylon 66
- Colour: Black
- IP Rating: IP66
- Locknut Included: No
- Fire Behaviour: Halogen Free, Self-extinguishing
- Maximum Operating Temperature: +120 °C
- Minimum Operating Temperature: -40 °C



1856103 M32

RS PRO BLACK NYLON CABLE GLAND KIT, M50 THREAD, IP66

Pack size: **5 x EA**

- Thread Size: M50
- Material: Nylon 66
- Colour: Black
- IP Rating: IP66
- Locknut Included: No
- Fire Behaviour: Halogen Free, Self-extinguishing
- Maximum Operating Temperature: +120 °C
- Minimum Operating Temperature: -40 °C



1856105 M50

RS PRO METALLIC BRASS CABLE GLAND, PG9 THREAD, 4MM MIN, 8MM

Pack size: **1 x EA**

- Thread Size: PG9
- Maximum Cable Diameter: 8 mm
- Minimum Cable Diameter: 4 mm
- Material: Brass
- Colour: Metallic
- Series: RS Pro
- IP Rating: IP68
- Locknut Included: No



2084378 PG9

RS PRO METALLIC BRASS CABLE GLAND, PG11 THREAD, 5MM MIN, 10MM

Pack size: **1 x EA**

- Thread Size: PG11
- Maximum Cable Diameter: 10 mm
- Minimum Cable Diameter: 5 mm
- Material: Brass
- Colour: Metallic
- Series: RS Pro
- IP Rating: IP68
- Locknut Included: No



2084379 PG11

RS PRO METALLIC BRASS CABLE GLAND, PG21 THREAD, 13MM MIN, 18MM

Pack size: **1 x EA**

- Thread Size: PG21
- Maximum Cable Diameter: 18 mm
- Minimum Cable Diameter: 13 mm
- Material: Brass
- Colour: Metallic
- Series: RS Pro
- IP Rating: IP68
- Locknut Included: No



2084383 PG21

RS PRO METALLIC BRASS CABLE GLAND, PG29 THREAD, 18MM MIN, 25MM

Pack size: **1 x EA**

- Thread Size: PG29
- Maximum Cable Diameter: 25 mm
- Minimum Cable Diameter: 18 mm
- Material: Brass
- Colour: Metallic
- Series: RS Pro
- IP Rating: IP68
- Locknut Included: No



2084384 PG29

RS PRO METALLIC NICKEL PLATED BRASS CABLE GLAND, M12 X 1.5

Pack size: **5 x EA**

- Thread Size: M12 x 1.5
- Maximum Cable Diameter: 6.5 mm
- Minimum Cable Diameter: 3 mm
- Material: Nickel Plated Brass
- Colour: Metallic
- IP Rating: IP68
- Locknut Included: Yes
- Maximum Operating Temperature: +100 °C



2100592 M12 x 1.5

RS PRO METALLIC NICKEL PLATED BRASS CABLE GLAND, M16 X 1.5

Pack size: **1 x EA**

- Thread Size: M16 x 1.5
- Maximum Cable Diameter: 8 mm
- Minimum Cable Diameter: 4 mm
- Material: Nickel Plated Brass
- Colour: Metallic
- IP Rating: IP68
- Locknut Included: Yes
- Maximum Operating Temperature: +100 °C



2100594 M16 x 1.5

RS PRO METALLIC NICKEL PLATED BRASS CABLE GLAND, M16 X 1.5

Pack size: **1 x EA**

- Thread Size: M16 x 1.5
- Maximum Cable Diameter: 8 mm
- Minimum Cable Diameter: 4 mm
- Material: Nickel Plated Brass
- Colour: Metallic
- IP Rating: IP68
- Locknut Included: No
- Maximum Operating Temperature: +100 °C



2100595 M16 x 1.5

RS PRO METALLIC NICKEL PLATED BRASS CABLE GLAND, PG13.5

Pack size: **5 x EA**

- Thread Size: PG13.5
- Maximum Cable Diameter: 12 mm
- Minimum Cable Diameter: 6 mm
- Material: Nickel Plated Brass
- Colour: Metallic
- IP Rating: IP68
- Locknut Included: Yes
- Maximum Operating Temperature: +100 °C



2100621 PG13.5

RS PRO METALLIC NICKEL PLATED BRASS CABLE GLAND, PG16 THREAD,

Pack size: **5 x EA**

- Thread Size: PG16
- Maximum Cable Diameter: 14 mm
- Minimum Cable Diameter: 10 mm
- Material: Nickel Plated Brass
- Colour: Metallic
- IP Rating: IP68
- Locknut Included: Yes
- Maximum Operating Temperature: +100 °C



2100624 PG16

RS PRO METALLIC NICKEL PLATED BRASS CABLE GLAND, PG16 THREAD,

Pack size: **1 x EA**

- Thread Size: PG16
- Maximum Cable Diameter: 14 mm
- Minimum Cable Diameter: 10 mm
- Material: Nickel Plated Brass
- Colour: Metallic
- IP Rating: IP68
- Locknut Included: No
- Maximum Operating Temperature: +100 °C



2100626 PG16

RS PRO METALLIC NICKEL PLATED BRASS CABLE GLAND, PG21 THREAD,

Pack size: **1 x EA**

- Thread Size: PG21
- Maximum Cable Diameter: 16 mm
- Minimum Cable Diameter: 9 mm
- Material: Nickel Plated Brass
- Colour: Metallic
- IP Rating: IP68
- Locknut Included: No
- Maximum Operating Temperature: +100 °C



2100628 PG21

RS PRO BLACK NYLON CABLE GLAND, M12 X 1.5 THREAD, 3MM MIN, 6.5MM

Pack size: **100 x EA**

- Thread Size: M12 x 1.5
- Maximum Cable Diameter: 6.5 mm
- Minimum Cable Diameter: 3 mm
- Material: Nylon 66
- Colour: Black
- Series: KSS METRIC THREAD
- IP Rating: IP68
- Locknut Included: No



2101317 M12 x 1.5

RS PRO BLACK NYLON CABLE GLAND, M12 X 1.5 THREAD, 3MM MIN, 6.5MM

Pack size: **5 x EA**

- Thread Size: M12 x 1.5
- Maximum Cable Diameter: 6.5 mm
- Minimum Cable Diameter: 3 mm
- Material: Nylon 66
- Colour: Black
- Series: KSS METRIC THREAD
- IP Rating: IP68
- Locknut Included: No



2101318 M12 x 1.5

RS PRO GREY NYLON CABLE GLAND, M12 X 1.5 THREAD, 3MM MIN, 6.5MM

Pack size: **5 x EA**

- Thread Size: M12 x 1.5
- Maximum Cable Diameter: 6.5 mm
- Minimum Cable Diameter: 3 mm
- Material: Nylon 66
- Colour: Grey
- Series: KSS METRIC THREAD
- IP Rating: IP68
- Locknut Included: Yes



2101319 M12 x 1.5

RS PRO BLACK NYLON CABLE GLAND, M12 X 1.25 THREAD, 3MM MIN, 6.5MM

Pack size: **5 x EA**

- Thread Size: M12 x 1.25
- Maximum Cable Diameter: 6.5 mm
- Minimum Cable Diameter: 3 mm
- Material: Nylon 66
- Colour: Black
- Series: KSS METRIC THREAD (Strain Relief type)
- IP Rating: IP68
- Locknut Included: Yes



2101320 M12 x 1.25

RS PRO GREY NYLON CABLE GLAND, M12 X 1.25 THREAD, 3MM MIN, 6.5MM

Pack size: **5 x EA**

- Thread Size: M12 x 1.25
- Maximum Cable Diameter: 6.5 mm
- Minimum Cable Diameter: 3 mm
- Material: Nylon 66
- Colour: Grey
- Series: KSS METRIC THREAD (Strain Relief type)
- IP Rating: IP68
- Locknut Included: Yes



2101321 M12 x 1.25

RS PRO BLACK NYLON CABLE GLAND, M16 X 1.5 THREAD, 5MM MIN, 10MM

Pack size: **5 x EA**

- Thread Size: M16 x 1.5
- Maximum Cable Diameter: 10 mm
- Minimum Cable Diameter: 5 mm
- Material: Nylon 66
- Colour: Black
- Series: KSS METRIC THREAD
- IP Rating: IP68
- Locknut Included: Yes



2101322 M16 x 1.5

RS PRO GREY NYLON CABLE GLAND, M16 X 1.5 THREAD, 5MM MIN, 10MM

Pack size: **5 x EA**

- Thread Size: M16 x 1.5
- Maximum Cable Diameter: 10 mm
- Minimum Cable Diameter: 5 mm
- Material: Nylon 66
- Colour: Grey
- Series: KSS METRIC THREAD
- IP Rating: IP68
- Locknut Included: Yes



2101323 M16 x 1.5

RS PRO BLACK NYLON CABLE GLAND, M16 X 1.5 THREAD, 5MM MIN, 10MM

Pack size: **5 x EA**

- Thread Size: M16 x 1.5
- Maximum Cable Diameter: 10 mm
- Minimum Cable Diameter: 5 mm
- Material: Nylon 66
- Colour: Black
- Series: KSS METRIC THREAD (Strain Relief type)
- IP Rating: IP68
- Locknut Included: Yes



2101324 M16 x 1.5

RS PRO GREY NYLON CABLE GLAND, M16 X 1.5 THREAD, 5MM MIN, 10MM

Pack size: **5 x EA**

- Thread Size: M16 x 1.5
- Maximum Cable Diameter: 10 mm
- Minimum Cable Diameter: 5 mm
- Material: Nylon 66
- Colour: Grey
- Series: KSS METRIC THREAD (Strain Relief type)
- IP Rating: IP68
- Locknut Included: Yes



2101325 M16 x 1.5

RS PRO BLACK NYLON CABLE GLAND, M20 X 1.5 THREAD, 8MM MIN, 12MM

Pack size: **5 x EA**

- Thread Size: M20 x 1.5
- Maximum Cable Diameter: 12 mm
- Minimum Cable Diameter: 8 mm
- Material: Nylon 66
- Colour: Black
- Series: KSS METRIC THREAD
- IP Rating: IP68
- Locknut Included: Yes



2101326 M20 x 1.5

RS PRO GREY NYLON CABLE GLAND, M20 X 1.5 THREAD, 8MM MIN, 12MM

Pack size: **5 x EA**

- Thread Size: M20 x 1.5
- Maximum Cable Diameter: 12 mm
- Minimum Cable Diameter: 8 mm
- Material: Nylon 66
- Colour: Grey
- Series: KSS METRIC THREAD
- IP Rating: IP68
- Locknut Included: Yes



2101327 M20 x 1.5

RS PRO BLACK NYLON CABLE GLAND, M20 X 1.5 THREAD, 10MM MIN, 14MM

Pack size: **5 x EA**

- Thread Size: M20 x 1.5
- Maximum Cable Diameter: 14 mm
- Minimum Cable Diameter: 10 mm
- Material: Nylon 66
- Colour: Black
- Series: KSS METRIC THREAD (Strain Relief type)
- IP Rating: IP68
- Locknut Included: Yes



2101328 M20 x 1.5

RS PRO BLACK NYLON CABLE GLAND, M25 X 1.5 THREAD, 11MM MIN, 17MM

Pack size: **5 x EA**

- Thread Size: M25 x 1.5
- Maximum Cable Diameter: 17 mm
- Minimum Cable Diameter: 11 mm
- Material: Nylon 66
- Colour: Black
- Series: KSS METRIC THREAD
- IP Rating: IP68
- Locknut Included: Yes



2101331 M25 x 1.5

RS PRO GREY NYLON CABLE GLAND, M25 X 1.5 THREAD, 11MM MIN, 17MM

Pack size: **5 x EA**

- Thread Size: M25 x 1.5
- Maximum Cable Diameter: 17 mm
- Minimum Cable Diameter: 11 mm
- Material: Nylon 66
- Colour: Grey
- Series: KSS METRIC THREAD
- IP Rating: IP68
- Locknut Included: Yes



2101332 M25 x 1.5

RS PRO BLACK NYLON CABLE GLAND, M25 X 1.5 THREAD, 13MM MIN, 18MM

Pack size: **5 x EA**

- Thread Size: M25 x 1.5
- Maximum Cable Diameter: 18 mm
- Minimum Cable Diameter: 13 mm
- Material: Nylon 66
- Colour: Black
- Series: KSS METRIC THREAD (Strain Relief type)
- IP Rating: IP68
- Locknut Included: Yes



2101333 M25 x 1.5

RS PRO GREY NYLON CABLE GLAND, M25 X 1.5 THREAD, 13MM MIN, 18MM

Pack size: **5 x EA**

- Thread Size: M25 x 1.5
- Maximum Cable Diameter: 18 mm
- Minimum Cable Diameter: 13 mm
- Material: Nylon 66
- Colour: Grey
- Series: KSS METRIC THREAD (Strain Relief type)
- IP Rating: IP68
- Locknut Included: Yes



2101334 M25 x 1.5

RS PRO BLACK NYLON CABLE GLAND, M32 X 1.5 THREAD, 15MM MIN, 21MM

Pack size: **5 x EA**

- Thread Size: M32 x 1.5
- Maximum Cable Diameter: 21 mm
- Minimum Cable Diameter: 15 mm
- Material: Nylon 66
- Colour: Black
- Series: KSS METRIC THREAD
- IP Rating: IP68
- Locknut Included: Yes



2101336 M32 x 1.5

RS PRO GREY NYLON CABLE GLAND, M32 X 1.5 THREAD, 15MM MIN, 21MM

Pack size: **5 x EA**

- Thread Size: M32 x 1.5
- Maximum Cable Diameter: 21 mm
- Minimum Cable Diameter: 15 mm
- Material: Nylon 66
- Colour: Grey
- Series: KSS METRIC THREAD
- IP Rating: IP68
- Locknut Included: Yes



2101337 M32 x 1.5

RS PRO GREY NYLON CABLE GLAND, M12 X 1.5 THREAD, 3MM MIN, 6.5MM

Pack size: **5 x EA**

- Thread Size: M12 x 1.5
- Maximum Cable Diameter: 6.5 mm
- Minimum Cable Diameter: 3 mm
- Material: Nylon 66
- Colour: Grey
- Series: KSS METRIC THREAD
- IP Rating: IP68
- Locknut Included: No



2101339 M12 x 1.5

RS PRO BLACK NYLON CABLE GLAND, M16 X 1.5 THREAD, 5MM MIN, 10MM

Pack size: **5 x EA**

- Thread Size: M16 x 1.5
- Maximum Cable Diameter: 10 mm
- Minimum Cable Diameter: 5 mm
- Material: Nylon 66
- Colour: Black
- Series: KSS METRIC THREAD
- IP Rating: IP68
- Locknut Included: No



2101340 M16 x 1.5

RS PRO GREY NYLON CABLE GLAND, M16 X 1.5 THREAD, 5MM MIN, 10MM

Pack size: **5 x EA**

- Thread Size: M16 x 1.5
- Maximum Cable Diameter: 10 mm
- Minimum Cable Diameter: 5 mm
- Material: Nylon 66
- Colour: Grey
- Series: KSS METRIC THREAD
- IP Rating: IP68
- Locknut Included: No



2101341 M16 x 1.5

RS PRO BLACK NYLON CABLE GLAND, M20 X 1.5 THREAD, 8MM MIN, 12MM

Pack size: **5 x EA**

- Thread Size: M20 x 1.5
- Maximum Cable Diameter: 12 mm
- Minimum Cable Diameter: 8 mm
- Material: Nylon 66
- Colour: Black
- Series: KSS METRIC THREAD
- IP Rating: IP68
- Locknut Included: No



2101342 M20 x 1.5

RS PRO GREY NYLON CABLE GLAND, M20 X 1.5 THREAD, 8MM MIN, 12MM

Pack size: **5 x EA**

- Thread Size: M20 x 1.5
- Maximum Cable Diameter: 12 mm
- Minimum Cable Diameter: 8 mm
- Material: Nylon 66
- Colour: Grey
- Series: KSS METRIC THREAD
- IP Rating: IP68
- Locknut Included: No



2101343 M20 x 1.5

RS PRO BLACK NYLON CABLE GLAND, M25 X 1.5 THREAD, 11MM MIN, 17MM

Pack size: **5 x EA**

- Thread Size: M25 x 1.5
- Maximum Cable Diameter: 17 mm
- Minimum Cable Diameter: 11 mm
- Material: Nylon 66
- Colour: Black
- Series: KSS METRIC THREAD
- IP Rating: IP68
- Locknut Included: No



2101344 M25 x 1.5

RS PRO GREY NYLON CABLE GLAND, M25 X 1.5 THREAD, 11MM MIN, 17MM

Pack size: **5 x EA**

- Thread Size: M25 x 1.5
- Maximum Cable Diameter: 17 mm
- Minimum Cable Diameter: 11 mm
- Material: Nylon 66
- Colour: Grey
- Series: KSS METRIC THREAD
- IP Rating: IP68
- Locknut Included: No



2101345 M25 x 1.5

RS PRO BLACK NYLON CABLE GLAND, M32 X 1.5 THREAD, 15MM MIN, 21MM

Pack size: **5 x EA**

- Thread Size: M32 x 1.5
- Maximum Cable Diameter: 21 mm
- Minimum Cable Diameter: 15 mm
- Material: Nylon 66
- Colour: Black
- Series: KSS METRIC THREAD
- IP Rating: IP68
- Locknut Included: No



2101346 M32 x 1.5

RS PRO GREY NYLON CABLE GLAND, PG13.5 THREAD, 6MM MIN, 12MM

Pack size: **5 x EA**

- Thread Size: PG13.5
- Maximum Cable Diameter: 12 mm
- Minimum Cable Diameter: 6 mm
- Material: Nylon 66
- Colour: Grey
- Series: KSS PG THREAD (DIN STANDARD)
- IP Rating: IP68
- Locknut Included: No



2101348 PG13.5

RS PRO GREY NYLON CABLE GLAND, PG7 THREAD, 3MM MIN, 6.5MM MAX,

Pack size: **5 x EA**

- Thread Size: PG7
- Maximum Cable Diameter: 6.5 mm
- Minimum Cable Diameter: 3 mm
- Material: Nylon 66
- Colour: Grey
- Series: KSS PG THREAD (DIN STANDARD)
- IP Rating: IP68
- Locknut Included: No



2101349 PG7

RS PRO BLACK NYLON CABLE GLAND, PG11 THREAD, 5MM MIN, 10MM MAX,

Pack size: **5 x EA**

- Thread Size: PG11
- Maximum Cable Diameter: 10 mm
- Minimum Cable Diameter: 5 mm
- Material: Nylon 66
- Colour: Black
- Series: KSS PG THREAD (DIN STANDARD)
- IP Rating: IP68
- Locknut Included: No



2101350 PG11

RS PRO GREY NYLON CABLE GLAND, PG11 THREAD, 5MM MIN, 10MM MAX,

Pack size: **5 x EA**

- Thread Size: PG11
- Maximum Cable Diameter: 10 mm
- Minimum Cable Diameter: 5 mm
- Material: Nylon 66
- Colour: Grey
- Series: KSS PG THREAD (DIN STANDARD)
- IP Rating: IP68
- Locknut Included: No



2101351 PG11

RS PRO BLACK NYLON CABLE GLAND, PG13.5 THREAD, 6MM MIN, 12MM

Pack size: **5 x EA**

- Thread Size: PG13.5
- Maximum Cable Diameter: 12 mm
- Minimum Cable Diameter: 6 mm
- Material: Nylon 66
- Colour: Black
- Series: KSS PG THREAD (DIN STANDARD)
- IP Rating: IP68
- Locknut Included: No



2101352 PG13.5

RS PRO BLACK NYLON CABLE GLAND, PG16 THREAD, 10MM MIN, 14MM MAX,

Pack size: **5 x EA**

- Thread Size: PG16
- Maximum Cable Diameter: 14 mm
- Minimum Cable Diameter: 10 mm
- Material: Nylon 66
- Colour: Black
- Series: KSS PG THREAD (DIN STANDARD)
- IP Rating: IP68
- Locknut Included: No



2101353 PG16

RS PRO BLACK NYLON CABLE GLAND, PG21 THREAD, 13MM MIN, 18MM MAX,

Pack size: **5 x EA**

- Thread Size: PG21
- Maximum Cable Diameter: 18 mm
- Minimum Cable Diameter: 13 mm
- Material: Nylon 66
- Colour: Black
- Series: KSS PG THREAD (DIN STANDARD)
- IP Rating: IP68
- Locknut Included: No



2101355 PG21

RS PRO GREY NYLON CABLE GLAND, PG21 THREAD, 13MM MIN, 18MM MAX,

Pack size: **5 x EA**

- Thread Size: PG21
- Maximum Cable Diameter: 18 mm
- Minimum Cable Diameter: 13 mm
- Material: Nylon 66
- Colour: Grey
- Series: KSS PG THREAD (DIN STANDARD)
- IP Rating: IP68
- Locknut Included: No



2101356 PG21

RS PRO BLACK NYLON CABLE GLAND, PG29 THREAD, 18MM MIN, 25MM

Pack size: **5 x EA**

- Thread Size: PG29
- Maximum Cable Diameter: 25 mm
- Minimum Cable Diameter: 18 mm
- Material: Nylon 66
- Colour: Black
- Series: KSS PG THREAD (DIN STANDARD)
- IP Rating: IP68
- Locknut Included: No



2101358 PG29

RS PRO GREY NYLON CABLE GLAND, PG29 THREAD, 18MM MIN, 25MM

Pack size: **5 x EA**

- Thread Size: PG29
- Maximum Cable Diameter: 25 mm
- Minimum Cable Diameter: 18 mm
- Material: Nylon 66
- Colour: Grey
- Series: KSS PG THREAD (DIN STANDARD)
- IP Rating: IP68
- Locknut Included: No



2101359 PG29

RS PRO BLACK NYLON CABLE GLAND, PG7 THREAD, 3MM MIN, 6.5MM MAX,

Pack size: **5 x EA**

- Thread Size: PG7
- Maximum Cable Diameter: 6.5 mm
- Minimum Cable Diameter: 3 mm
- Material: Nylon 66
- Colour: Black
- Series: KSS PG THREAD (DIN STANDARD)
- IP Rating: IP68
- Locknut Included: No



2101360 PG7

RS PRO BLACK NYLON CABLE GLAND, PG9 THREAD, 4MM MIN, 8MM MAX,

Pack size: **5 x EA**

- Thread Size: PG9
- Maximum Cable Diameter: 8 mm
- Minimum Cable Diameter: 4 mm
- Material: Nylon 66
- Colour: Black
- Series: KSS PG THREAD (DIN STANDARD)
- IP Rating: IP68
- Locknut Included: No



2101361 PG9

RS PRO GREY NYLON CABLE GLAND, PG9 THREAD, 4MM MIN, 8MM MAX,

Pack size: **5 x EA**

- Thread Size: PG9
- Maximum Cable Diameter: 8 mm
- Minimum Cable Diameter: 4 mm
- Material: Nylon 66
- Colour: Grey
- Series: KSS PG THREAD (DIN STANDARD)
- IP Rating: IP68
- Locknut Included: No



2101362 PG9

RS PRO GREY NYLON CABLE GLAND, PG11 THREAD, 5MM MIN, 10MM MAX,

Pack size: **10 x EA**

- Thread Size: PG11
- Maximum Cable Diameter: 10 mm
- Minimum Cable Diameter: 5 mm
- Material: Nylon 66
- Colour: Grey
- Series: KSS PG THREAD (DIN STANDARD) (Strain Relief type)
- IP Rating: IP68
- Locknut Included: Yes



2101365 PG11

RS PRO GREY NYLON CABLE GLAND, PG13.5 THREAD, 6MM MIN, 12MM

Pack size: **10 x EA**

- Thread Size: PG13.5
- Maximum Cable Diameter: 12 mm
- Minimum Cable Diameter: 6 mm
- Material: Nylon 66
- Colour: Grey
- Series: KSS PG THREAD (DIN STANDARD)
- IP Rating: IP68
- Locknut Included: Yes



2101366 PG13.5

RS PRO GREY NYLON CABLE GLAND, PG16 THREAD, 10MM MIN, 14MM MAX,

Pack size: **10 x EA**

- Thread Size: PG16
- Maximum Cable Diameter: 14 mm
- Minimum Cable Diameter: 10 mm
- Material: Nylon 66
- Colour: Grey
- Series: KSS PG THREAD (DIN STANDARD) (Strain Relief type)
- IP Rating: IP68
- Locknut Included: Yes



2101368 PG16

RS PRO GREY NYLON CABLE GLAND, PG21 THREAD, 13MM MIN, 18MM MAX,

Pack size: **10 x EA**

- Thread Size: PG21
- Maximum Cable Diameter: 18 mm
- Minimum Cable Diameter: 13 mm
- Material: Nylon 66
- Colour: Grey
- Series: KSS PG THREAD (DIN STANDARD)
- IP Rating: IP68
- Locknut Included: Yes



2101369 PG21

RS PRO GREY NYLON CABLE GLAND, PG29 THREAD, 18MM MIN, 25MM

Pack size: **10 x EA**

- Thread Size: PG29
- Maximum Cable Diameter: 25 mm
- Minimum Cable Diameter: 18 mm
- Material: Nylon 66
- Colour: Grey
- Series: KSS PG THREAD (DIN STANDARD)
- IP Rating: IP68
- Locknut Included: Yes



2101371 PG29

RS PRO BLACK NYLON CABLE GLAND, PG7 THREAD, 3MM MIN, 6.5MM MAX,

Pack size: **10 x EA**

- Thread Size: PG7
- Maximum Cable Diameter: 6.5 mm
- Minimum Cable Diameter: 3 mm
- Material: Nylon 66
- Colour: Black
- Series: KSS PG THREAD (DIN STANDARD)
- IP Rating: IP68
- Locknut Included: Yes



2101372 PG7

RS PRO NICKEL PLATED BRASS CABLE GLAND, M20 X 1.5 THREAD, 10MM

Pack size: **1 x EA**

- Thread Size: M20 x 1.5
- Maximum Cable Diameter: 14 mm
- Minimum Cable Diameter: 10 mm
- Material: Nickel Plated Brass
- Series: Han CGM-M
- IP Rating: IP68
- Locknut Included: No
- Minimum Operating Temperature: -40 °C



2116798 M20 x 1.5

RS PRO WHITE NYLON CABLE GLAND, M20X1.5 THREAD, 8MM MIN, 12MM

Pack size: **10 x EA**

- Thread Size: M20X1.5
- Maximum Cable Diameter: 12 mm
- Minimum Cable Diameter: 8 mm
- Material: Nylon 66
- Colour: White
- IP Rating: IP68
- Locknut Included: Yes
- Fire Behaviour: Fire Resistant



2141066 M20X1.5

RS PRO GREY NYLON CABLE GLAND, M20X1.5 THREAD, 10MM MIN, 14MM

Pack size: **50 x EA**

- Thread Size: M20X1.5
- Maximum Cable Diameter: 14 mm
- Minimum Cable Diameter: 10 mm
- Material: Nylon 66
- Colour: Grey
- Locknut Included: No
- Fire Behaviour: Fire Resistant
- Minimum Operating Temperature: -40 °C



2141076 M20X1.5

RS PRO GREY NYLON CABLE GLAND, PG7 THREAD, 3MM MIN, 6.5MM MAX,

Pack size: **10 x EA**

- Thread Size: PG7
- Maximum Cable Diameter: 6.5 mm
- Minimum Cable Diameter: 3 mm
- Material: Nylon 66
- Colour: Grey
- Series: KSS PG THREAD (DIN STANDARD) (Strain Relief type)
- IP Rating: IP68
- Locknut Included: Yes



2101374 PG7

RS PRO GREY NYLON CABLE GLAND, M12X1.5 THREAD, 3MM MIN, 6.5MM

Pack size: **10 x EA**

- Thread Size: M12X1.5
- Maximum Cable Diameter: 6.5 mm
- Minimum Cable Diameter: 3 mm
- Material: Nylon 66
- Colour: Grey
- IP Rating: IP68
- Locknut Included: Yes
- Fire Behaviour: Fire Resistant



2141063 M12X1.5

RS PRO WHITE NYLON CABLE GLAND, M40X1.5 THREAD, 22MM MIN, 32MM

Pack size: **5 x EA**

- Thread Size: M40X1.5
- Maximum Cable Diameter: 32 mm
- Minimum Cable Diameter: 22 mm
- Material: Nylon 66
- Colour: White
- IP Rating: IP68
- Locknut Included: Yes
- Fire Behaviour: Fire Resistant



2141070 M40X1.5

RS PRO GREY NYLON CABLE GLAND, M25XP1.5 THREAD, 11MM MIN, 17MM

Pack size: **5 x EA**

- Thread Size: M25xP1.5
- Maximum Cable Diameter: 17 mm
- Minimum Cable Diameter: 11 mm
- Material: Nylon 66
- Colour: Grey
- Locknut Included: No
- Fire Behaviour: Fire Resistant
- Minimum Operating Temperature: -40 °C



2141077 M25xP1.5

RS PRO GREY NYLON CABLE GLAND, PG9 THREAD, 4MM MIN, 8MM MAX,

Pack size: **10 x EA**

- Thread Size: PG9
- Maximum Cable Diameter: 8 mm
- Minimum Cable Diameter: 4 mm
- Material: Nylon 66
- Colour: Grey
- Series: KSS PG THREAD (DIN STANDARD)
- IP Rating: IP68
- Locknut Included: Yes



2101375 PG9

RS PRO BLACK NYLON CABLE GLAND, M16X1.5 THREAD, 5MM MIN, 10MM

Pack size: **10 x EA**

- Thread Size: M16X1.5
- Maximum Cable Diameter: 10 mm
- Minimum Cable Diameter: 5 mm
- Material: Nylon 66
- Colour: Black
- IP Rating: IP68
- Locknut Included: Yes
- Fire Behaviour: Fire Resistant



2141064 M16X1.5

RS PRO BLACK NYLON CABLE GLAND, M40X1.5 THREAD, 20MM MIN, 28MM

Pack size: **5 x EA**

- Thread Size: M40X1.5
- Maximum Cable Diameter: 28 mm
- Minimum Cable Diameter: 20 mm
- Material: Nylon 66
- Colour: Black
- IP Rating: IP68
- Locknut Included: Yes
- Fire Behaviour: Fire Resistant



2141071 M40X1.5

RS PRO GREY NYLON CABLE GLAND, M32X1.5 THREAD, 15MM MIN, 21MM

Pack size: **5 x EA**

- Thread Size: M32X1.5
- Maximum Cable Diameter: 21 mm
- Minimum Cable Diameter: 15 mm
- Material: Nylon 66
- Colour: Grey
- Locknut Included: No
- Fire Behaviour: Fire Resistant
- Minimum Operating Temperature: -40 °C



2141078 M32X1.5

RS PRO GREY NYLON CABLE GLAND, PG9 THREAD, 4MM MIN, 8MM MAX,

Pack size: **10 x EA**

- Thread Size: PG9
- Maximum Cable Diameter: 8 mm
- Minimum Cable Diameter: 4 mm
- Material: Nylon 66
- Colour: Grey
- Series: KSS PG THREAD (DIN STANDARD) (Strain Relief type)
- IP Rating: IP68
- Locknut Included: Yes



2101376 PG9

RS PRO GREY NYLON CABLE GLAND, M20X1.5 THREAD, 8MM MIN, 12MM

Pack size: **10 x EA**

- Thread Size: M20X1.5
- Maximum Cable Diameter: 12 mm
- Minimum Cable Diameter: 8 mm
- Material: Nylon 66
- Colour: Grey
- IP Rating: IP68
- Locknut Included: Yes
- Fire Behaviour: Fire Resistant



2141065 M20X1.5

RS PRO GREY NYLON CABLE GLAND, M40X1.5 THREAD, 20MM MIN, 28MM

Pack size: **5 x EA**

- Thread Size: M40X1.5
- Maximum Cable Diameter: 28 mm
- Minimum Cable Diameter: 20 mm
- Material: Nylon 66
- Colour: Grey
- IP Rating: IP68
- Locknut Included: Yes
- Fire Behaviour: Fire Resistant



2141072 M40X1.5

RS PRO GREY NYLON CABLE GLAND, PG11 THREAD, 5MM MIN, 10MM MAX,

Pack size: **5 x EA**

- Thread Size: PG11
- Maximum Cable Diameter: 10 mm
- Minimum Cable Diameter: 5 mm
- Material: Nylon 66
- Colour: Grey
- IP Rating: IP68
- Locknut Included: Yes
- Fire Behaviour: Fire Resistant



2141082 PG11

RS PRO GREY NYLON CABLE GLAND, PG36 THREAD, 22MM MIN, 32MM

Pack size: **5 x EA**

- Thread Size: PG36
- Maximum Cable Diameter: 32 mm
- Minimum Cable Diameter: 22 mm
- Material: Nylon 66
- Colour: Grey
- IP Rating: IP68
- Locknut Included: Yes
- Fire Behaviour: Fire Resistant



2141083 PG36

RS PRO GREY NYLON CABLE GLAND, PG9 THREAD, 4MM MIN, 8MM MAX,

Pack size: **5 x EA**

- Thread Size: PG9
- Maximum Cable Diameter: 8 mm
- Minimum Cable Diameter: 4 mm
- Material: Nylon 66
- Colour: Grey
- IP Rating: IP68
- Locknut Included: Yes
- Fire Behaviour: Fire Resistant



2141084 PG9

ABB METALLIC NICKEL PLATED BRASS CABLE GLAND, M16 THREAD, 6MM

Pack size: **5 x EA**

- Thread Size: M16
- Maximum Cable Diameter: 9 mm
- Minimum Cable Diameter: 6 mm
- Material: Nickel Plated Brass
- Colour: Metallic
- IP Rating: IP68
- Locknut Included: No
- Minimum Operating Temperature: -40 °C



2647308 M16

ABB METALLIC NICKEL PLATED BRASS CABLE GLAND, M25 THREAD, 6MM

Pack size: **5 x EA**

- Thread Size: M25
- Maximum Cable Diameter: 11 mm
- Minimum Cable Diameter: 6 mm
- Material: Nickel Plated Brass
- Colour: Metallic
- IP Rating: IP68
- Locknut Included: No
- Minimum Operating Temperature: -40 °C



2647364 M25

ABB METALLIC NICKEL PLATED BRASS CABLE GLAND, M25 THREAD, 17MM

Pack size: **5 x EA**

- Thread Size: M25
- Maximum Cable Diameter: 20 mm
- Minimum Cable Diameter: 17 mm
- Material: Nickel Plated Brass
- Colour: Metallic
- IP Rating: IP68
- Locknut Included: No
- Minimum Operating Temperature: -40 °C



2647415 M25

ABB METALLIC NICKEL PLATED BRASS CABLE GLAND, M16 THREAD, 7MM

Pack size: **5 x EA**

- Thread Size: M16
- Maximum Cable Diameter: 11 mm
- Minimum Cable Diameter: 7 mm
- Material: Nickel Plated Brass
- Colour: Metallic
- IP Rating: IP68
- Locknut Included: No
- Minimum Operating Temperature: -40 °C



2650269 M16

RS PRO GREY EPDM CABLE GLAND, M16 THREAD, 5MM MIN, 9MM MAX,

Pack size: **10 x EA**

- Thread Size: M16
- Maximum Cable Diameter: 9 mm
- Minimum Cable Diameter: 5 mm
- Material: EPDM
- Colour: Grey
- IP Rating: IP67
- Fire Behaviour: Halogen Free
- Maximum Operating Temperature: +110 °C



2797009 M16

CABLE, GLAND, RUBBER, HALOGEN FREE, IP67, CABLE DIA 14-20MM

Pack size: **10 x EA**

- Thread Size: M32
- Maximum Cable Diameter: 20 mm
- Minimum Cable Diameter: 15 mm
- Material: EPDM
- Colour: Grey
- IP Rating: IP67
- Maximum Operating Temperature: +110 °C
- Minimum Operating Temperature: -40 °C



2797065 M32

WHT NYLON ROUNDTOP IP68 CABLE GLAND, M12

Pack size: **5 x EA**

- Thread Size: M12
- Maximum Cable Diameter: 6.5 mm
- Minimum Cable Diameter: 3 mm
- Material: Nylon 66
- Colour: White
- IP Rating: IP68
- Locknut Included: Yes
- Maximum Operating Temperature: +85 °C



6694642 M12

RS PRO WHITE NYLON CABLE GLAND, M12 THREAD, 3MM MIN, 6.5MM MAX,

Pack size: **100 x EA**

- Thread Size: M12
- Maximum Cable Diameter: 6.5 mm
- Minimum Cable Diameter: 3 mm
- Material: Nylon 66
- Colour: White
- IP Rating: IP68
- Locknut Included: Yes
- Maximum Operating Temperature: +85 °C



6694651 M12

IP68 BLACK NYLON GLAND, M12, 3-6.5MM

Pack size: **5 x EA**

- Thread Size: M12
- Maximum Cable Diameter: 6.5 mm
- Minimum Cable Diameter: 3 mm
- Material: Nylon 66
- Colour: Black
- IP Rating: IP68
- Locknut Included: Yes
- Maximum Operating Temperature: +85 °C



6694654 M12

RS PRO BLACK NYLON CABLE GLAND, M12 THREAD, 3MM MIN, 6.5MM MAX,

Pack size: **100 x EA**

- Thread Size: M12
- Maximum Cable Diameter: 6.5 mm
- Minimum Cable Diameter: 3 mm
- Material: Nylon 66
- Colour: Black
- IP Rating: IP68
- Locknut Included: Yes
- Maximum Operating Temperature: +85 °C



6694658 M12

RS PRO BLACK NYLON CABLE GLAND, M20 THREAD, 4MM MIN, 9MM MAX,

Pack size: **5 x EA**

- Thread Size: M20
- Maximum Cable Diameter: 9 mm
- Minimum Cable Diameter: 4 mm
- Material: Nylon
- Colour: Black
- IP Rating: IP68
- Locknut Included: Yes
- Maximum Operating Temperature: +85 °C



6694660 M20

IP68 BLACK NYLON GLAND, M20, 6-12MM

Pack size: **5 x EA**

- Thread Size: M20
- Maximum Cable Diameter: 12 mm
- Minimum Cable Diameter: 6 mm
- Material: Nylon
- Colour: Black
- IP Rating: IP68
- Locknut Included: Yes
- Maximum Operating Temperature: +85 °C



6694664 M20

BLACK ROUNDTOP IP68 CABLE GLAND, M16

Pack size: **5 x EA**

- Thread Size: M16
- Maximum Cable Diameter: 7 mm
- Minimum Cable Diameter: 3 mm
- Material: Nylon
- Colour: Black
- IP Rating: IP68
- Locknut Included: Yes
- Maximum Operating Temperature: +85 °C



6694667 M16

BLACK ROUNDTOP IP68 CABLE GLAND, M32

Pack size: **5 x EA**

- Thread Size: M32
- Maximum Cable Diameter: 25 mm
- Minimum Cable Diameter: 18 mm
- Material: Nylon 66
- Colour: Black
- IP Rating: IP68
- Locknut Included: Yes
- Maximum Operating Temperature: +85 °C



6694670 M32

IP68 BLACK NYLON GLAND, M20, 10-14MM

Pack size: **5 x EA**

- Thread Size: M20
- Maximum Cable Diameter: 14 mm
- Minimum Cable Diameter: 10 mm
- Material: Nylon 66
- Colour: Black
- IP Rating: IP68
- Locknut Included: Yes
- Maximum Operating Temperature: +85 °C



6694673 M20

BLACK ROUNDTOP IP68 CABLE GLAND, M25

Pack size: **5 x EA**

- Thread Size: M25
- Maximum Cable Diameter: 18 mm
- Minimum Cable Diameter: 13 mm
- Material: Nylon 66
- Colour: Black
- IP Rating: IP68
- Locknut Included: Yes
- Maximum Operating Temperature: +85 °C



6694676 M25

RS PRO BLACK NYLON CABLE GLAND, M50 THREAD, 30MM MIN, 38MM

Pack size: **5 x EA**

- Thread Size: M50
- Maximum Cable Diameter: 38 mm
- Minimum Cable Diameter: 30 mm
- Material: Nylon 66
- Colour: Black
- IP Rating: IP68
- Locknut Included: Yes
- Minimum Operating Temperature: -60 °C



6694682 M50

RS PRO BLACK NYLON CABLE GLAND, M63 THREAD, 34MM MIN, 44MM MAX,

Pack size: **5 x EA**

- Thread Size: M63
- Maximum Cable Diameter: 44 mm
- Minimum Cable Diameter: 34 mm
- Material: Nylon 66
- Colour: Black
- IP Rating: IP68
- Locknut Included: Yes
- Maximum Operating Temperature: +85 °C



6694686 M63

BLACK ROUNDTOP IP68 CABLE GLAND, M40

Pack size: **5 x EA**

- Thread Size: M40
- Maximum Cable Diameter: 32 mm
- Minimum Cable Diameter: 22 mm
- Material: Nylon 66
- Colour: Black
- IP Rating: IP68
- Locknut Included: Yes
- Maximum Operating Temperature: +85 °C



6694689 M40

RS PRO GREY NYLON CABLE GLAND, PG7 THREAD, 3.5MM MIN, 6MM MAX,

Pack size: **10 x EA**

- Thread Size: PG7
- Maximum Cable Diameter: 6 mm
- Minimum Cable Diameter: 3.5 mm
- Material: Nylon 66
- Colour: Grey
- IP Rating: IP68
- Locknut Included: Yes
- Standards Met: UL 94 V-2



8229571 PG7

RS PRO GREY NYLON CABLE GLAND, PG9 THREAD, 4MM MIN, 8MM MAX,

Pack size: **10 x EA**

- Thread Size: PG9
- Maximum Cable Diameter: 8 mm
- Minimum Cable Diameter: 4 mm
- Material: Nylon 66
- Colour: Grey
- IP Rating: IP68
- Locknut Included: Yes
- Standards Met: UL 94 V-2



8229580 PG9

RS PRO GREY NYLON CABLE GLAND, PG13.5 THREAD, 6MM MIN, 12MM

Pack size: **10 x EA**

- Thread Size: PG13.5
- Maximum Cable Diameter: 12 mm
- Minimum Cable Diameter: 6 mm
- Material: Nylon 66
- Colour: Grey
- IP Rating: IP68
- Locknut Included: Yes
- Standards Met: UL 94 V-2



8229587 PG13.5

RS PRO BLACK NYLON CABLE GLAND, PG7 THREAD, 3.5MM MIN, 6MM MAX,

Pack size: **10 x EA**

- Thread Size: PG7
- Maximum Cable Diameter: 6 mm
- Minimum Cable Diameter: 3.5 mm
- Material: Nylon 66
- Colour: Black
- IP Rating: IP68
- Locknut Included: Yes
- Standards Met: UL 94 V-2



8229593 PG7

RS PRO GREY NYLON CABLE GLAND, PG21 THREAD, 13MM MIN, 18MM MAX,

Pack size: **10 x EA**

- Thread Size: PG21
- Maximum Cable Diameter: 18 mm
- Minimum Cable Diameter: 13 mm
- Material: Nylon 66
- Colour: Grey
- IP Rating: IP68
- Locknut Included: Yes
- Standards Met: UL 94 V-2



8229599 PG21

RS PRO BLACK NYLON CABLE GLAND, PG13.5 THREAD, 6MM MIN, 12MM

Pack size: **10 x EA**

- Thread Size: PG13.5
- Maximum Cable Diameter: 12 mm
- Minimum Cable Diameter: 6 mm
- Material: Nylon 66
- Colour: Black
- IP Rating: IP68
- Locknut Included: Yes
- Standards Met: UL 94 V-2



8229600 PG13.5

RS PRO BLACK NYLON CABLE GLAND, PG9 THREAD, 4MM MIN, 8MM MAX,

Pack size: **10 x EA**

- Thread Size: PG9
- Maximum Cable Diameter: 8 mm
- Minimum Cable Diameter: 4 mm
- Material: Nylon 66
- Colour: Black
- IP Rating: IP68
- Locknut Included: Yes
- Standards Met: UL 94 V-2



8229603 PG9

CABLE GLAND PG11 BLACK IP68

Pack size: **10 x EA**

- Thread Size: PG11
- Maximum Cable Diameter: 10 mm
- Minimum Cable Diameter: 5 mm
- Material: Nylon 66
- Colour: Black
- IP Rating: IP68
- Locknut Included: Yes
- Standards Met: UL 94 V-2



8229606 PG11

RS PRO BLACK NYLON CABLE GLAND, PG21 THREAD, 13MM MIN, 18MM MAX,

Pack size: **10 x EA**

- Thread Size: PG21
- Maximum Cable Diameter: 18 mm
- Minimum Cable Diameter: 13 mm
- Material: Nylon 66
- Colour: Black
- IP Rating: IP68
- Locknut Included: Yes
- Standards Met: UL 94 V-2



8229612 PG21

RS PRO GREY NYLON CABLE GLAND, M12 THREAD, 3MM MIN, 6.5MM MAX,

Pack size: **10 x EA**

- Thread Size: M12
- Maximum Cable Diameter: 6.5 mm
- Minimum Cable Diameter: 3 mm
- Material: Nylon 66
- Colour: Grey
- IP Rating: IP68
- Locknut Included: Yes
- Standards Met: UL 94 V-2



8229616 M12

RS PRO GREY NYLON CABLE GLAND, M25 THREAD, 13MM MIN, 18MM MAX,

Pack size: **10 x EA**

- Thread Size: M25
- Maximum Cable Diameter: 18 mm
- Minimum Cable Diameter: 13 mm
- Material: Nylon 66
- Colour: Grey
- IP Rating: IP68
- Locknut Included: Yes
- Standards Met: UL 94 V-2



8229622 M25

CABLE GLANDM16 X 1.5 GREY IP68

Pack size: **10 x EA**

- Thread Size: M16
- Maximum Cable Diameter: 10 mm
- Minimum Cable Diameter: 5 mm
- Material: Nylon 66
- Colour: Grey
- IP Rating: IP68
- Locknut Included: Yes
- Standards Met: UL 94 V-2



8229625 M16

CABLE GLANDM12 X 1.5 BLACK IP68

Pack size: **10 x EA**

- Thread Size: M12
- Maximum Cable Diameter: 6.5 mm
- Minimum Cable Diameter: 3 mm
- Material: Nylon 66
- Colour: Black
- IP Rating: IP68
- Locknut Included: Yes
- Standards Met: UL 94 V-2



8229631 M12

RS PRO BLACK NYLON CABLE GLAND, M16 THREAD, 5MM MIN, 10MM MAX,

Pack size: **10 x EA**

- Thread Size: M16
- Maximum Cable Diameter: 10 mm
- Minimum Cable Diameter: 5 mm
- Material: Nylon 66
- Colour: Black
- IP Rating: IP68
- Locknut Included: Yes
- Standards Met: UL 94 V-2



8229634 M16

CABLE GLANDM20 X 1.5 BLACK IP68

Pack size: **10 x EA**

- Thread Size: M20
- Maximum Cable Diameter: 14 mm
- Minimum Cable Diameter: 10 mm
- Material: Nylon 66
- Colour: Black
- IP Rating: IP68
- Locknut Included: Yes
- Standards Met: UL 94 V-2



8229638 M20

ROUND TOP CABLE GLAND PG7 GREY IP68

Pack size: **10 x EA**

- Thread Size: PG7
- Maximum Cable Diameter: 6 mm
- Minimum Cable Diameter: 3.5 mm
- Material: Nylon 66
- Colour: Grey
- IP Rating: IP68
- Locknut Included: Yes
- Standards Met: UL 94 V-2



8229640 PG7

RS PRO GREY NYLON CABLE GLAND, PG9 THREAD, 4MM MIN, 8MM MAX,

Pack size: **10 x EA**

- Thread Size: PG9
- Maximum Cable Diameter: 8 mm
- Minimum Cable Diameter: 4 mm
- Material: Nylon 66
- Colour: Grey
- IP Rating: IP68
- Locknut Included: Yes
- Standards Met: UL 94 V-2



8229644 PG9

RS PRO BLACK NYLON CABLE GLAND, M25 THREAD, 13MM MIN, 18MM MAX,

Pack size: **10 x EA**

- Thread Size: M25
- Maximum Cable Diameter: 18 mm
- Minimum Cable Diameter: 13 mm
- Material: Nylon 66
- Colour: Black
- IP Rating: IP68
- Locknut Included: Yes
- Standards Met: UL 94 V-2



8229647 M25

ROUND TOP CABLE GLAND PG16 GREY IP68

Pack size: **10 x EA**

- Thread Size: PG16
- Maximum Cable Diameter: 14 mm
- Minimum Cable Diameter: 10 mm
- Material: Nylon 66
- Colour: Grey
- IP Rating: IP68
- Locknut Included: Yes
- Standards Met: UL 94 V-2



8229650 PG16

ROUND TOP CABLE GLAND PG11 GREY IP68

Pack size: **10 x EA**

- Thread Size: PG11
- Maximum Cable Diameter: 10 mm
- Minimum Cable Diameter: 5 mm
- Material: Nylon 66
- Colour: Grey
- IP Rating: IP68
- Locknut Included: Yes
- Standards Met: UL 94 V-2



8229653 PG11

ROUND TOP CABLE GLAND PG13.5 GREY IP68

Pack size: **10 x EA**

- Thread Size: PG13.5
- Maximum Cable Diameter: 12 mm
- Minimum Cable Diameter: 6 mm
- Material: Nylon 66
- Colour: Grey
- IP Rating: IP68
- Locknut Included: Yes
- Standards Met: UL 94 V-2



8229656 PG13.5

ROUND TOP CABLE GLAND PG29 GREY IP68

Pack size: **10 x EA**

- Thread Size: PG29
- Maximum Cable Diameter: 25 mm
- Minimum Cable Diameter: 18 mm
- Material: Nylon 66
- Colour: Grey
- IP Rating: IP68
- Locknut Included: Yes
- Standards Met: UL 94 V-2



8229662 PG29

ROUND TOP CABLE GLAND PG7 BLACK IP68

Pack size: **10 x EA**

- Thread Size: PG7
- Maximum Cable Diameter: 6 mm
- Minimum Cable Diameter: 3.5 mm
- Material: Nylon 66
- Colour: Black
- IP Rating: IP68
- Locknut Included: Yes
- Standards Met: UL 94 V-2



8229666 PG7

ROUND TOP CABLE GLAND PG21 GREY IP68

Pack size: **10 x EA**

- Thread Size: PG21
- Maximum Cable Diameter: 18 mm
- Minimum Cable Diameter: 13 mm
- Material: Nylon 66
- Colour: Grey
- IP Rating: IP68
- Locknut Included: Yes
- Standards Met: UL 94 V-2



8229669 PG21

ROUND TOP CABLE GLAND PG13.5 BLACK IP68

Pack size: **10 x EA**

- Thread Size: PG13.5
- Maximum Cable Diameter: 12 mm
- Minimum Cable Diameter: 6 mm
- Material: Nylon 66
- Colour: Black
- IP Rating: IP68
- Locknut Included: Yes
- Standards Met: UL 94 V-2



8229672 PG13.5

ROUND TOP CABLE GLAND PG9 BLACK IP68

Pack size: **10 x EA**

- Thread Size: PG9
- Maximum Cable Diameter: 8 mm
- Minimum Cable Diameter: 4 mm
- Material: Nylon 66
- Colour: Black
- IP Rating: IP68
- Locknut Included: Yes
- Standards Met: UL 94 V-2



8229675 PG9

ROUND TOP CABLE GLAND PG11 BLACK IP68

Pack size: **10 x EA**

- Thread Size: PG11
- Maximum Cable Diameter: 10 mm
- Minimum Cable Diameter: 5 mm
- Material: Nylon 66
- Colour: Black
- IP Rating: IP68
- Locknut Included: Yes
- Standards Met: UL 94 V-2



8229678 PG11

ROUND TOP CABLE GLAND PG16 BLACK IP68

Pack size: **10 x EA**

- Thread Size: PG16
- Maximum Cable Diameter: 14 mm
- Minimum Cable Diameter: 10 mm
- Material: Nylon 66
- Colour: Black
- IP Rating: IP68
- Locknut Included: Yes
- Standards Met: UL 94 V-2



8229681 PG16

ROUND TOP CABLE GLAND PG21 BLACK IP68

Pack size: **10 x EA**

- Thread Size: PG21
- Maximum Cable Diameter: 18 mm
- Minimum Cable Diameter: 13 mm
- Material: Nylon 66
- Colour: Black
- IP Rating: IP68
- Locknut Included: Yes
- Standards Met: UL 94 V-2



8229684 PG21

RS PRO BLACK NYLON CABLE GLAND, PG29 THREAD, 18MM MIN, 25MM

Pack size: **10 x EA**

- Thread Size: PG29
- Maximum Cable Diameter: 25 mm
- Minimum Cable Diameter: 18 mm
- Material: Nylon 66
- Colour: Black
- IP Rating: IP68
- Locknut Included: Yes
- Standards Met: UL 94 V-2



8229688 PG29

ROUND TOPCABLE GLANDM12 X 1.5 GREY IP68

Pack size: **10 x EA**

- Thread Size: M12
- Maximum Cable Diameter: 6.5 mm
- Minimum Cable Diameter: 3 mm
- Material: Nylon 66
- Colour: Grey
- IP Rating: IP68
- Locknut Included: Yes
- Standards Met: UL 94 V-2



8229739 M12

ROUND TOPCABLE GLANDM20 X 1.5 GREY IP68

Pack size: **10 x EA**

- Thread Size: M20
- Maximum Cable Diameter: 14 mm
- Minimum Cable Diameter: 10 mm
- Material: Nylon 66
- Colour: Grey
- IP Rating: IP68
- Locknut Included: Yes
- Standards Met: UL 94 V-2



8229741 M20

ROUND TOPCABLE GLANDM25 X 1.5 GREY IP68

Pack size: **10 x EA**

- Thread Size: M25
- Maximum Cable Diameter: 18 mm
- Minimum Cable Diameter: 13 mm
- Material: Nylon 66
- Colour: Grey
- IP Rating: IP68
- Locknut Included: Yes
- Standards Met: UL 94 V-2



8229745 M25

ROUND TOPCABLE GLANDM16 X 1.5 GREY IP68

Pack size: **10 x EA**

- Thread Size: M16
- Maximum Cable Diameter: 10 mm
- Minimum Cable Diameter: 5 mm
- Material: Nylon 66
- Colour: Grey
- IP Rating: IP68
- Locknut Included: Yes
- Standards Met: UL 94 V-2



8229748 M16

ROUND TOPCABLE GLANDM25S X 1.5 GREY IP68

Pack size: **10 x EA**

- Thread Size: M25
- Maximum Cable Diameter: 18 mm
- Minimum Cable Diameter: 13 mm
- Material: Nylon 66
- Colour: Grey
- IP Rating: IP68
- Locknut Included: Yes
- Standards Met: UL 94 V-2



8229751 M25

ROUND TOPCABLE GLANDM32 X 1.5 GREY IP68

Pack size: **10 x EA**

- Thread Size: M32
- Maximum Cable Diameter: 25 mm
- Minimum Cable Diameter: 18 mm
- Material: Nylon 66
- Colour: Grey
- IP Rating: IP68
- Locknut Included: Yes
- Standards Met: UL 94 V-2



8229754 M32

ROUND TOPCABLE GLANDM20S X 1.5 GREYIP68

Pack size: **10 x EA**

- Thread Size: M20
- Maximum Cable Diameter: 14 mm
- Minimum Cable Diameter: 10 mm
- Material: Nylon 66
- Colour: Grey
- IP Rating: IP68
- Locknut Included: Yes
- Standards Met: UL 94 V-2



8229757 M20

RS PRO BLACK NYLON CABLE GLAND, M25 THREAD, 13MM MIN, 18MM MAX,

Pack size: **10 x EA**

- Thread Size: M25
- Maximum Cable Diameter: 18 mm
- Minimum Cable Diameter: 13 mm
- Material: Nylon 66
- Colour: Black
- IP Rating: IP68
- Locknut Included: Yes
- Standards Met: UL 94 V-2



8229763 M25

RS PRO WHITE NYLON CABLE GLAND, M16 THREAD, 5MM MIN, 10MM MAX,

Pack size: **10 x EA**

- Thread Size: M16
- Maximum Cable Diameter: 10 mm
- Minimum Cable Diameter: 5 mm
- Material: Nylon 66
- Colour: White
- IP Rating: IP68
- Locknut Included: Yes
- Standards Met: UL 94 V-2



8229767 M16

ROUND TOPCABLE GLANDM32 X 1.5 WHITE IP68

Pack size: **10 x EA**

- Thread Size: M32
- Maximum Cable Diameter: 25 mm
- Minimum Cable Diameter: 18 mm
- Material: Nylon 66
- Colour: White
- IP Rating: IP68
- Locknut Included: Yes
- Standards Met: UL 94 V-2



8229773 M32

RS PRO WHITE NYLON CABLE GLAND, M20 THREAD, 10MM MIN, 14MM MAX,

Pack size: **10 x EA**

- Thread Size: M20
- Maximum Cable Diameter: 14 mm
- Minimum Cable Diameter: 10 mm
- Material: Nylon 66
- Colour: White
- IP Rating: IP68
- Locknut Included: Yes
- Standards Met: UL 94 V-2



8229776 M20

ROUND TOPCABLE GLANDM25 X 1.5 WHITE IP68

Pack size: **10 x EA**

- Thread Size: M25
- Maximum Cable Diameter: 18 mm
- Minimum Cable Diameter: 13 mm
- Material: Nylon 66
- Colour: White
- IP Rating: IP68
- Locknut Included: Yes
- Standards Met: UL 94 V-2



8229779 M25

ROUND TOPCABLE GLANDM20S X 1.5 WHITEIP68

Pack size: **10 x EA**

- Thread Size: M20
- Maximum Cable Diameter: 14 mm
- Minimum Cable Diameter: 10 mm
- Material: Nylon 66
- Colour: White
- IP Rating: IP68
- Locknut Included: Yes
- Standards Met: UL 94 V-2



8229782 M20

RS PRO WHITE NYLON CABLE GLAND, M25 THREAD, 13MM MIN, 18MM MAX,

Pack size: **10 x EA**

- Thread Size: M25
- Maximum Cable Diameter: 18 mm
- Minimum Cable Diameter: 13 mm
- Material: Nylon 66
- Colour: White
- IP Rating: IP68
- Locknut Included: Yes
- Standards Met: UL 94 V-2



8229785 M25

M16 BRASS CABLE GLAND + LOCKNUT,5-10MM

Pack size: **5 x EA**

- Thread Size: M16 x 1.5
- Maximum Cable Diameter: 10 mm
- Minimum Cable Diameter: 5 mm
- Material: Nickel Plated Brass
- Colour: Metallic
- IP Rating: IP68
- Locknut Included: Yes
- Minimum Operating Temperature: -40 °C



8319021 M16 x 1.5

M50 BRASS CABLE GLAND + LOCKNUT,31-38MM

Pack size: **1 x EA**

- Thread Size: M50 x 1.5
- Maximum Cable Diameter: 38 mm
- Minimum Cable Diameter: 31 mm
- Material: Nickel Plated Brass
- Colour: Metallic
- IP Rating: IP68
- Locknut Included: Yes
- Minimum Operating Temperature: -40 °C



8319034 M50 x 1.5

PG7 BRASS CABLE GLAND + LOCKNUT,3-6.5MM

Pack size: **5 x EA**

- Thread Size: PG7
- Maximum Cable Diameter: 6.5 mm
- Minimum Cable Diameter: 3 mm
- Material: Nickel Plated Brass
- Colour: Metallic
- IP Rating: IP68
- Locknut Included: Yes
- Minimum Operating Temperature: -40 °C



8319046 PG7

RS PRO RED NYLON CABLE GLAND, M20 THREAD, 10MM MIN, 14MM MAX,

Pack size: **10 x EA**

- Thread Size: M20
- Maximum Cable Diameter: 14 mm
- Minimum Cable Diameter: 10 mm
- Material: Nylon 66
- Colour: Red
- IP Rating: IP68
- Locknut Included: Yes
- Standards Met: UL 94 V-2



8229789 M20

M20 BRASS CABLE GLAND + LOCKNUT,8-14MM

Pack size: **5 x EA**

- Thread Size: M20
- Maximum Cable Diameter: 14 mm
- Minimum Cable Diameter: 8 mm
- Material: Nickel Plated Brass
- Colour: Metallic
- IP Rating: IP68
- Locknut Included: Yes
- Minimum Operating Temperature: -40 °C



8319024 M20

M32 BRASS CABLE GLAND + LOCKNUT,15-22MM

Pack size: **5 x EA**

- Thread Size: M32
- Maximum Cable Diameter: 22 mm
- Minimum Cable Diameter: 15 mm
- Material: Nickel Plated Brass
- Colour: Metallic
- IP Rating: IP68
- Locknut Included: Yes
- Minimum Operating Temperature: -40 °C



8319037 M32

PG13.5 BRASS CABLEGLAND + LOCKNUT,6-12MM

Pack size: **5 x EA**

- Thread Size: PG13.5
- Maximum Cable Diameter: 12 mm
- Minimum Cable Diameter: 6 mm
- Material: Nickel Plated Brass
- Colour: Metallic
- IP Rating: IP68
- Locknut Included: Yes
- Minimum Operating Temperature: -40 °C



8319052 PG13.5

RS PRO RED NYLON CABLE GLAND, M25 THREAD, 13MM MIN, 18MM MAX,

Pack size: **10 x EA**

- Thread Size: M25
- Maximum Cable Diameter: 18 mm
- Minimum Cable Diameter: 13 mm
- Material: Nylon 66
- Colour: Red
- IP Rating: IP68
- Locknut Included: Yes
- Standards Met: UL 94 V-2



8229798 M25

M25 BRASS CABLE GLAND + LOCKNUT,9-16MM

Pack size: **5 x EA**

- Thread Size: M25
- Maximum Cable Diameter: 16 mm
- Minimum Cable Diameter: 9 mm
- Material: Nickel Plated Brass
- Colour: Metallic
- IP Rating: IP68
- Locknut Included: Yes
- Minimum Operating Temperature: -40 °C



8319028 M25

PG9 BRASS CABLE GLAND + LOCKNUT,4-8MM

Pack size: **5 x EA**

- Thread Size: PG9
- Maximum Cable Diameter: 8 mm
- Minimum Cable Diameter: 4 mm
- Material: Nickel Plated Brass
- Colour: Metallic
- IP Rating: IP68
- Locknut Included: Yes
- Minimum Operating Temperature: -40 °C



8319040 PG9

RS PRO METALLIC NICKEL PLATED BRASS CABLE GLAND, PG16 THREAD,

Pack size: **5 x EA**

- Thread Size: PG16
- Maximum Cable Diameter: 14 mm
- Minimum Cable Diameter: 8 mm
- Material: Nickel Plated Brass
- Colour: Metallic
- IP Rating: IP68
- Locknut Included: Yes
- Minimum Operating Temperature: -40 °C



8319056 PG16

M12 BRASS CABLE GLAND + LOCKNUT,3-6.5MM

Pack size: **5 x EA**

- Thread Size: M12
- Maximum Cable Diameter: 6.5 mm
- Minimum Cable Diameter: 3 mm
- Material: Nickel Plated Brass
- Colour: Metallic
- IP Rating: IP68
- Locknut Included: Yes
- Minimum Operating Temperature: -40 °C



8319012 M12

M40 BRASS CABLE GLAND + LOCKNUT,22-32MM

Pack size: **5 x EA**

- Thread Size: M40
- Maximum Cable Diameter: 32 mm
- Minimum Cable Diameter: 22 mm
- Material: Nickel Plated Brass
- Colour: Metallic
- IP Rating: IP68
- Locknut Included: Yes
- Minimum Operating Temperature: -40 °C



8319030 M40

RS PRO METALLIC NICKEL PLATED BRASS CABLE GLAND, M63 THREAD,

Pack size: **1 x EA**

- Thread Size: M63
- Maximum Cable Diameter: 44 mm
- Minimum Cable Diameter: 37 mm
- Material: Nickel Plated Brass
- Colour: Metallic
- IP Rating: IP68
- Locknut Included: Yes
- Minimum Operating Temperature: -40 °C



8319043 M63

PG11 BRASS CABLE GLAND + LOCKNUT,5-10MM

Pack size: **5 x EA**

- Thread Size: PG11
- Maximum Cable Diameter: 10 mm
- Minimum Cable Diameter: 5 mm
- Material: Nickel Plated Brass
- Colour: Metallic
- IP Rating: IP68
- Locknut Included: Yes
- Minimum Operating Temperature: -40 °C



8319059 PG11

PG21 BRASS CABLE GLAND + LOCKNUT,13-18MM

Pack size: **5 x EA**

- Thread Size: PG21
- Maximum Cable Diameter: 18 mm
- Minimum Cable Diameter: 13 mm
- Material: Nickel Plated Brass
- Colour: Metallic
- IP Rating: IP68
- Locknut Included: Yes
- Minimum Operating Temperature: -40 °C



8319065 PG21

RS PRO METALLIC NICKEL PLATED BRASS CABLE GLAND, PG29 THREAD,

Pack size: **5 x EA**

- Thread Size: PG29
- Maximum Cable Diameter: 25 mm
- Minimum Cable Diameter: 18 mm
- Material: Nickel Plated Brass
- Colour: Metallic
- IP Rating: IP68
- Locknut Included: Yes
- Minimum Operating Temperature: -40 °C



8319068 PG29

EMC CABLE GLAND C/W LOCKNUT,PG9,4-8 MM

Pack size: **1 x EA**

- Thread Size: PG9
- Maximum Cable Diameter: 8 mm
- Minimum Cable Diameter: 4 mm
- Material: Nickel Plated Brass
- Colour: Metallic
- IP Rating: IP68
- Locknut Included: Yes
- Minimum Operating Temperature: -40 °C



8354087 PG9

EMC CABLE GLAND C/W LOCKNUT,PG16, 8-14MM

Pack size: **1 x EA**

- Thread Size: PG16
- Maximum Cable Diameter: 14 mm
- Minimum Cable Diameter: 8 mm
- Material: Nickel Plated Brass
- Colour: Metallic
- IP Rating: IP68
- Locknut Included: Yes
- Minimum Operating Temperature: -40 °C



8354093 PG16

RS PRO METALLIC NICKEL PLATED BRASS CABLE GLAND, PG11 THREAD,

Pack size: **1 x EA**

- Thread Size: PG11
- Maximum Cable Diameter: 10 mm
- Minimum Cable Diameter: 5 mm
- Material: Nickel Plated Brass
- Colour: Metallic
- IP Rating: IP68
- Locknut Included: Yes
- Maximum Operating Temperature: +110 °C



8354096 PG11

EMC CABLE GLANDC/W LOCKNUT,PG13.5 6-12MM

Pack size: **1 x EA**

- Thread Size: PG13.5
- Maximum Cable Diameter: 12 mm
- Minimum Cable Diameter: 6 mm
- Material: Nickel Plated Brass
- Colour: Metallic
- IP Rating: IP68
- Locknut Included: Yes
- Minimum Operating Temperature: -40 °C



8354099 PG13.5

RS PRO METALLIC NICKEL PLATED BRASS CABLE GLAND, PG36 THREAD,

Pack size: **1 x EA**

- Thread Size: PG36
- Maximum Cable Diameter: 32 mm
- Minimum Cable Diameter: 22 mm
- Material: Nickel Plated Brass
- Colour: Metallic
- IP Rating: IP68
- Locknut Included: Yes
- Minimum Operating Temperature: -40 °C



8354100 PG36

RS PRO METALLIC NICKEL PLATED BRASS CABLE GLAND, PG29 THREAD,

Pack size: **1 x EA**

- Thread Size: PG29
- Maximum Cable Diameter: 25 mm
- Minimum Cable Diameter: 18 mm
- Material: Nickel Plated Brass
- Colour: Metallic
- IP Rating: IP68
- Locknut Included: Yes
- Minimum Operating Temperature: -40 °C



8354106 PG29

RS PRO METALLIC NICKEL PLATED BRASS CABLE GLAND, M20 THREAD,

Pack size: **1 x EA**

- Thread Size: M20
- Maximum Cable Diameter: 12 mm
- Minimum Cable Diameter: 6 mm
- Material: Nickel Plated Brass
- Colour: Metallic
- IP Rating: IP68
- Locknut Included: Yes
- Minimum Operating Temperature: -40 °C



8354112 M20

EMC CABLE GLAND C/W LOCKNUT,M25S 10-16MM

Pack size: **1 x EA**

- Thread Size: M25
- Maximum Cable Diameter: 16 mm
- Minimum Cable Diameter: 10 mm
- Material: Nickel Plated Brass
- Colour: Metallic
- IP Rating: IP68
- Locknut Included: Yes
- Minimum Operating Temperature: -40 °C



8354116 M25

EMC CABLE GLAND C/W LOCKNUT,M16, 4-8 MM

Pack size: **1 x EA**

- Thread Size: M16
- Maximum Cable Diameter: 8 mm
- Minimum Cable Diameter: 4 mm
- Material: Nickel Plated Brass
- Colour: Metallic
- IP Rating: IP68
- Locknut Included: Yes
- Minimum Operating Temperature: -40 °C



8354119 M16

EMC CABLE GLAND C/W LOCKNUT,M50 30-38MM

Pack size: **1 x EA**

- Thread Size: M50
- Maximum Cable Diameter: 38 mm
- Minimum Cable Diameter: 30 mm
- Material: Nickel Plated Brass
- Colour: Metallic
- IP Rating: IP68
- Locknut Included: Yes
- Maximum Operating Temperature: +110 °C



8354122 M50

EMC CABLE GLAND C/W LOCKNUT,M32S 15-22MM

Pack size: **1 x EA**

- Thread Size: M32
- Maximum Cable Diameter: 22 mm
- Minimum Cable Diameter: 15 mm
- Material: Nickel Plated Brass
- Colour: Metallic
- IP Rating: IP68
- Locknut Included: Yes
- Minimum Operating Temperature: -40 °C



8354125 M32

RS PRO BLACK PVC 6.4MM CABLE GROMMET FOR MAXIMUM OF 4MM

Pack size: **100 x EA**

- Grommet Type: Cable Grommet
- Maximum Cable Diameter: 4 mm
- Panel Hole Diameter: 6.4 mm
- Material: PVC
- Colour: Black
- Maximum Panel Thickness: 1.6 mm



543197 Cable Grommet

EMC CABLE GLAND C/W LOCKNUT, M40S21-30MM

Pack size: **1 x EA**

- Thread Size: M40
- Maximum Cable Diameter: 30 mm
- Minimum Cable Diameter: 21 mm
- Material: Nickel Plated Brass
- Colour: Metallic
- IP Rating: IP68
- Locknut Included: Yes
- Minimum Operating Temperature: -40 °C



8354128 M40

RS PRO BLACK PVC 9.5MM CABLE GROMMET FOR MAXIMUM OF 6.4MM

Pack size: **100 x EA**

- Grommet Type: Cable Grommet
- Maximum Cable Diameter: 6.4 mm
- Panel Hole Diameter: 9.5 mm
- Material: PVC
- Colour: Black
- Maximum Panel Thickness: 1.6 mm



543204 Cable Grommet

RS PRO BLACK PVC 12.5MM CABLE GROMMET FOR MAXIMUM OF 9.5MM

Pack size: **100 x EA**

- Grommet Type: Cable Grommet
- Maximum Cable Diameter: 9.5 mm
- Panel Hole Diameter: 12.5 mm
- Material: PVC
- Colour: Black
- Maximum Panel Thickness: 1.6 mm



543210 Cable Grommet

RS PRO BLACK PVC 25MM CABLE GROMMET FOR MAXIMUM OF

Pack size: **100 x EA**

- Grommet Type: Cable Grommet
- Maximum Cable Diameter: 20.5 mm
- Panel Hole Diameter: 25 mm
- Material: PVC
- Colour: Black
- Maximum Panel Thickness: 1.5 mm



605677 Cable Grommet

RS PRO BLACK PVC 9.52MM CABLE GROMMET FOR MAXIMUM OF

Pack size: **50 x EA**

- Grommet Type: Cable Grommet
- Maximum Cable Diameter: 6.35 mm
- Panel Hole Diameter: 9.52 mm
- Material: PVC
- Colour: Black
- Maximum Panel Thickness: 2.4 mm



543282 Cable Grommet

GROMMET DA 80/110/ 10

Pack size: **100 x EA**

- Grommet Type: Cable Grommet
- Maximum Cable Diameter: 8 mm
- Panel Hole Diameter: 11 mm
- Material: Polychloroprene
- Colour: Black
- Series: HELAVIA
- Maximum Panel Thickness: 1 mm



1366064 Cable Grommet

RS PRO BLACK PVC 20MM CABLE GROMMET FOR MAXIMUM OF 16MM

Pack size: **100 x EA**

- Grommet Type: Cable Grommet
- Maximum Cable Diameter: 16 mm
- Panel Hole Diameter: 20 mm
- Material: PVC
- Colour: Black
- Maximum Panel Thickness: 1.5 mm



605661 Cable Grommet

RS PRO BLACK PVC 25MM CABLE GROMMET FOR MAXIMUM OF 18.5MM

Pack size: **100 x EA**

- Grommet Type: Cable Grommet
- Maximum Cable Diameter: 18.5 mm
- Panel Hole Diameter: 25 mm
- Material: PVC
- Colour: Black
- Maximum Panel Thickness: 1.6 mm



605655 Cable Grommet

RS PRO BLACK PVC 20MM CABLE GROMMET FOR MAXIMUM OF 16MM

Pack size: **100 x EA**

- Grommet Type: Cable Grommet
- Maximum Cable Diameter: 16 mm
- Panel Hole Diameter: 20 mm
- Material: PVC
- Colour: Black
- Maximum Panel Thickness: 1.6 mm



605649 Cable Grommet

GROMMET DA 90/160/15

Pack size: **100 x EA**

- Grommet Type: Cable Grommet
- Maximum Cable Diameter: 9 mm
- Panel Hole Diameter: 20 mm
- Material: Polychloroprene
- Colour: Black
- Series: HELAVIA
- Maximum Panel Thickness: 1.5 mm



1366402 Cable Grommet

MEMBRANE GROMMET DG 53

Pack size: **50 x EA**

- Grommet Type: Cable Grommet
- Minimum Cable Diameter: 1 mm
- Maximum Cable Diameter: 53 mm
- Panel Hole Diameter: 64 mm
- Material: Polychloroprene
- Colour: Black
- Series: DG



1366705 Cable Grommet

PVC GROMMET DK 3/5/8-2

Pack size: **100 x EA**

- Grommet Type: Cable Grommet
- Maximum Cable Diameter: 3 mm
- Panel Hole Diameter: 5 mm
- Material: PVC
- Colour: Black
- Series: PLIO
- Maximum Panel Thickness: 2 mm



1366812 Cable Grommet

PVC GROMMET DK 5.5/8/12-1.5

Pack size: **100 x EA**

- Grommet Type: Cable Grommet
- Maximum Cable Diameter: 5.5 mm
- Panel Hole Diameter: 8 mm
- Material: PVC
- Colour: Black
- Series: PLIO
- Maximum Panel Thickness: 1.5 mm



1366890 Cable Grommet

PVC GROMMET DK 6/9/12-1.5

Pack size: **100 x EA**

- Grommet Type: Cable Grommet
- Maximum Cable Diameter: 6 mm
- Panel Hole Diameter: 9 mm
- Material: PVC
- Colour: Black
- Series: PLIO
- Maximum Panel Thickness: 1.5 mm



1366963 Cable Grommet

PVC GROMMET DK 7/14/18-1

Pack size: **100 x EA**

- Grommet Type: Cable Grommet
- Maximum Cable Diameter: 7 mm
- Panel Hole Diameter: 14 mm
- Material: PVC
- Colour: Black
- Series: PLIO
- Maximum Panel Thickness: 1 mm



1367023 Cable Grommet

RS PRO BLACK PVC 18MM CABLE GROMMET FOR MAXIMUM OF 10MM

Pack size: **100 x EA**

- Grommet Type: Cable Grommet
- Maximum Cable Diameter: 10 mm
- Panel Hole Diameter: 18 mm
- Material: PVC
- Colour: Black
- Series: PLIO
- Maximum Panel Thickness: 1 mm



1367130 Cable Grommet

RS PRO BLACK PVC 22MM CABLE GROMMET FOR MAXIMUM OF 14MM

Pack size: **100 x EA**

- Grommet Type: Cable Grommet
- Maximum Cable Diameter: 14 mm
- Panel Hole Diameter: 22 mm
- Material: PVC
- Colour: Black
- Series: PLIO
- Maximum Panel Thickness: 3 mm



1367297 Cable Grommet

PVC GROMMET DK 18/22/27-3

Pack size: **100 x EA**

- Grommet Type: Cable Grommet
- Maximum Cable Diameter: 18 mm
- Panel Hole Diameter: 22 mm
- Material: PVC
- Colour: Black
- Series: PLIO
- Maximum Panel Thickness: 3 mm



1367405 Cable Grommet

PVC GROMMET DK 16/22/27-2

Pack size: **100 x EA**

- Grommet Type: Cable Grommet
- Maximum Cable Diameter: 16 mm
- Panel Hole Diameter: 22 mm
- Material: PVC
- Colour: Black
- Series: PLIO
- Maximum Panel Thickness: 2 mm



1367348 Cable Grommet

RS PRO BLACK POLYETHYLENE GROMMET STRIP

Pack size: **1 x EA**

- Grommet Type: Grommet Strip
- Minimum Panel Thickness: 1.6 mm
- Material: Polyethylene
- Colour: Black
- Grommet Strip Length: 1.2 m



2133609 Grommet Strip

RS PRO GREY POLYETHYLENE GROMMET STRIP

Pack size: **30 x MTR**

- Grommet Type: Grommet Strip
- Minimum Panel Thickness: 2 mm
- Material: Polyethylene
- Colour: Grey
- Grommet Strip Length: 30 m



2133611 Grommet Strip

RS PRO BLACK PVC 31.7MM CABLE GROMMET FOR MAXIMUM OF 25MM

Pack size: **50 x EA**

- Minimum Panel Thickness: 1.5 mm
- Grommet Type: Cable Grommet
- Panel Hole Diameter: 31.7 mm
- Maximum Cable Diameter: 25 mm
- Material: PVC
- Colour: Black



2133616 1.5 mm

RS PRO BLACK PVC 10.9MM CABLE GROMMET FOR MAXIMUM OF 7.8MM

Pack size: **100 x EA**

- Minimum Panel Thickness: 2.3 mm
- Grommet Type: Cable Grommet
- Panel Hole Diameter: 10.9 mm
- Maximum Cable Diameter: 7.8 mm
- Material: PVC
- Colour: Black



2133617 2.3 mm

RS PRO GREY POLYETHYLENE CABLE GROMMET

Pack size: **25 x MTR**

- Grommet Type: Cable Grommet
- Minimum Panel Thickness: 1.2 mm
- Material: Polyethylene
- Colour: Grey
- Grommet Strip Length: 25 m



2133618 Cable Grommet

RS PRO GREY POLYETHYLENE CABLE GROMMET

Pack size: **25 x MTR**

- Grommet Type: Cable Grommet
- Minimum Panel Thickness: 2 mm
- Material: Polyethylene
- Colour: Grey
- Grommet Strip Length: 25 m



2133619 Cable Grommet

RS PRO GREY NYLON 66 CABLE GROMMET

Pack size: **100 x EA**

- Grommet Type: Cable Grommet
- Minimum Panel Thickness: 2.4 mm
- Material: Nylon 66
- Colour: Grey



2133621 Cable Grommet

RS PRO GREY POLYETHYLENE CABLE GROMMET

Pack size: **25 x MTR**

- Grommet Type: Cable Grommet
- Minimum Panel Thickness: 3.2 mm
- Material: Polyethylene
- Colour: Grey
- Grommet Strip Length: 25 m



2133622 Cable Grommet

RS PRO BLACK PVC 12MM CABLE GROMMET FOR MAXIMUM OF 8MM

Pack size: **100 x EA**

- Grommet Type: Cable Grommet
- Maximum Cable Diameter: 8 mm
- Panel Hole Diameter: 12 mm
- Material: PVC
- Colour: Black
- Maximum Panel Thickness: 3 mm



2414580 Cable Grommet

RS PRO BLACK PVC 16MM CABLE GROMMET FOR MAXIMUM OF 12MM

Pack size: **100 x EA**

- Grommet Type: Cable Grommet
- Maximum Cable Diameter: 12 mm
- Panel Hole Diameter: 16 mm
- Material: PVC
- Colour: Black
- Maximum Panel Thickness: 3 mm



2414596 Cable Grommet

RS PRO BLACK PVC 22MM CABLE GROMMET FOR MAXIMUM OF 18MM

Pack size: **100 x EA**

- Grommet Type: Cable Grommet
- Maximum Cable Diameter: 18 mm
- Panel Hole Diameter: 22 mm
- Material: PVC
- Colour: Black
- Maximum Panel Thickness: 3 mm



2414603 Cable Grommet

437 PIECE PVC BLACK GROMMET KIT

Pack size: **1 x KT**

- Grommet Type: Cable Grommet Kit
- Minimum Cable Diameter: 3 mm
- Maximum Cable Diameter: 19 mm
- Material: PVC
- Colour: Black



6664584 Cable Grommet

PVC BLACK GROMMET 13.3MM BAG 100

Pack size: **100 x EA**

- Grommet Type: Cable Grommet
- Maximum Cable Diameter: 6.4 mm
- Panel Hole Diameter: 10 mm
- Material: PVC
- Colour: Black
- Maximum Panel Thickness: 1.7 mm



6664590 Cable Grommet

PVC BLACK GROMMET 8.5MM BAG 100

Pack size: **100 x EA**

- Grommet Type: Cable Grommet
- Maximum Cable Diameter: 3 mm
- Panel Hole Diameter: 6 mm
- Material: PVC
- Colour: Black
- Maximum Panel Thickness: 1.7 mm



6664593 Cable Grommet

PVC BLACK GROMMET 10.2MM BAG 100

Pack size: **100 x EA**

- Grommet Type: Cable Grommet
- Maximum Cable Diameter: 5 mm
- Panel Hole Diameter: 7.2 mm
- Material: PVC
- Colour: Black
- Maximum Panel Thickness: 1.7 mm



6664596 Cable Grommet

PVC BLACK GROMMET 15.5MM BAG 100

Pack size: **100 x EA**

- Grommet Type: Cable Grommet
- Maximum Cable Diameter: 7.8 mm
- Panel Hole Diameter: 11 mm
- Material: PVC
- Colour: Black
- Maximum Panel Thickness: 3 mm



6664600 Cable Grommet

PVC BLACK GROMMET 19.5MM BAG 100

Pack size: **100 x EA**

- Grommet Type: Cable Grommet
- Maximum Cable Diameter: 10.5 mm
- Panel Hole Diameter: 13.9 mm
- Material: PVC
- Colour: Black
- Maximum Panel Thickness: 3.4 mm



6664603 Cable Grommet

PVC BLACK GROMMET 23.7MM BAG 100

Pack size: **100 x EA**

- Grommet Type: Cable Grommet
- Maximum Cable Diameter: 15.5 mm
- Panel Hole Diameter: 20.1 mm
- Material: PVC
- Colour: Black
- Maximum Panel Thickness: 1.7 mm



6664607 Cable Grommet

PVC BLACK GROMMET 23.9MM BAG 100

Pack size: **100 x EA**

- Grommet Type: Cable Grommet
- Maximum Cable Diameter: 15.5 mm
- Panel Hole Diameter: 19.6 mm
- Material: PVC
- Colour: Black
- Maximum Panel Thickness: 2 mm



6664613 Cable Grommet

PVC BLACK GROMMET 29.9MM BAG 100

Pack size: **100 x EA**

- Grommet Type: Cable Grommet
- Maximum Cable Diameter: 18.9 mm
- Panel Hole Diameter: 25.1 mm
- Material: PVC
- Colour: Black
- Maximum Panel Thickness: 1.5 mm



6664616 Cable Grommet

PVC BLACK GROMMET 38.1MM BAG 100

Pack size: **100 x EA**

- Grommet Type: Cable Grommet
- Maximum Cable Diameter: 25 mm
- Panel Hole Diameter: 31.7 mm
- Material: PVC
- Colour: Black
- Maximum Panel Thickness: 1.5 mm



6664619 Cable Grommet

PVC BLACK GROMMET 30MM BAG 100

Pack size: **100 x EA**

- Grommet Type: Cable Grommet
- Maximum Cable Diameter: 20.8 mm
- Panel Hole Diameter: 26 mm
- Material: PVC
- Colour: Black
- Maximum Panel Thickness: 2.4 mm



6664622 Cable Grommet

EDGING GROMMET PE NATURAL 1.0MM

Pack size: **1 x EA**

- Grommet Type: Grommet Strip
- Minimum Panel Thickness: 0.5 mm
- Minimum Cable Diameter: 0.5 mm
- Maximum Cable Diameter: 1 mm
- Material: PE
- Colour: Natural
- Grommet Strip Length: 10 m
- Maximum Panel Thickness: 1 mm



8659714 Grommet Strip

RS PRO NATURAL PE GROMMET STRIP FOR 0.6 → 1.2MM CABLE DIA.

Pack size: **1 x EA**

- Grommet Type: Grommet Strip
- Minimum Panel Thickness: 1 mm
- Minimum Cable Diameter: 0.6 mm
- Maximum Cable Diameter: 1.2 mm
- Material: PE
- Colour: Natural
- Grommet Strip Length: 10 m
- Maximum Panel Thickness: 2 mm



8659723 Grommet Strip

RS PRO NATURAL PE GROMMET STRIP FOR 0.9 → 1.6MM CABLE DIA.

Pack size: **1 x EA**

- Grommet Type: Grommet Strip
- Minimum Panel Thickness: 1.2 mm
- Minimum Cable Diameter: 0.9 mm
- Maximum Cable Diameter: 1.6 mm
- Material: PE
- Colour: Natural
- Grommet Strip Length: 10 m
- Maximum Panel Thickness: 1.6 mm



8659726 Grommet Strip

RS PRO NATURAL PE GROMMET STRIP FOR 1.5 → 3.2MM CABLE DIA.

Pack size: **1 x EA**

- Grommet Type: Grommet Strip
- Minimum Panel Thickness: 2.4 mm
- Minimum Cable Diameter: 1.5 mm
- Maximum Cable Diameter: 3.2 mm
- Material: PE
- Colour: Natural
- Grommet Strip Length: 10 m
- Maximum Panel Thickness: 3.2 mm



8659732 Grommet Strip

RS PRO NATURAL PE GROMMET STRIP FOR 1.1 → 2MM CABLE DIA.

Pack size: **1 x EA**

- Grommet Type: Grommet Strip
- Minimum Panel Thickness: 1.6 mm
- Minimum Cable Diameter: 1.1 mm
- Maximum Cable Diameter: 2 mm
- Material: PE
- Colour: Natural
- Grommet Strip Length: 10 m
- Maximum Panel Thickness: 2 mm



8659720 Grommet Strip

RS PRO NATURAL PE GROMMET STRIP FOR 1.2 → 2.4MM CABLE DIA.

Pack size: **1 x EA**

- Grommet Type: Grommet Strip
- Minimum Panel Thickness: 2 mm
- Minimum Cable Diameter: 1.2 mm
- Maximum Cable Diameter: 2.4 mm
- Material: PE
- Colour: Natural
- Grommet Strip Length: 10 m
- Maximum Panel Thickness: 2.4 mm



8659739 Grommet Strip

EDGING GROMMET PE NATURAL 4.5-5.5MM

Pack size: **1 x EA**

- Grommet Type: Grommet Strip
- Minimum Panel Thickness: 4.5 mm
- Minimum Cable Diameter: 4.5 mm
- Maximum Cable Diameter: 5.5 mm
- Material: PE
- Colour: Natural
- Grommet Strip Length: 10 m
- Maximum Panel Thickness: 5.5 mm



8659736 Grommet Strip

TOOL,APPLICATION,CABLE MARKER,0.7/4MM SQ

Pack size: **1 x EA**

- Accessory Type: Cable Marker Application Tool
- For Use With: Helagrip Cable Markers Size B



404405 Cable Marker

TOOL,APPLICATION,CABLE MARKER,4/16MM SQ

Pack size: **1 x EA**

- Accessory Type: Cable Marker Application Tool
- For Use With: Helagrip Cable Markers Size C



404409 Cable Marker

RS PRO MARKER STRIP FOR OVAL SHAPE CABLE MARKER 9MM

Pack size: **100 x EA**

- Accessory Type: Marker Strip
- For Use With: Oval shape cable marker
- Carrier Width: 9 mm
- Material: Nylon 66



2153048 Marker Strip

TOOL,APPLICATION,CABLE MARKER,0.5/0.78MM SQ

Pack size: **1 x EA**

- Accessory Type: Cable Marker Application Tool
- For Use With: Helagrip Cable Markers Size A



404415 Cable Marker

RS PRO MARKER STRIP FOR OVAL SHAPE CABLE MARKER 9MM

Pack size: **100 x EA**

- Accessory Type: Marker Strip
- For Use With: Oval shape cable marker
- Carrier Width: 9 mm
- Material: Nylon 66



2153050 Marker Strip

RS PRO CABLE TIE CABLE MARKERS, WHITE

Pack size: **100 x EA**

- Affixing Method: Cable Tie
- Maximum Cable Diameter: 4.8 mm
- Colour: White
- Length: 38.5 mm
- Width: 19 mm
- Quantity: 100
- Printable: No
- Material: Nylon 66



492291 Cable Tie

RS PRO CABLE TIE CABLE MARKERS, WHITE

Pack size: **100 x EA**

- Affixing Method: Cable Tie
- Maximum Cable Diameter: 4.8 mm
- Colour: White
- Length: 45.3 mm
- Width: 19 mm
- Quantity: 100
- Printable: No
- Material: Nylon 66



492308 Cable Tie

CABLE,MARKER,PLATE,NYLON,19.1X5 0.8MM

Pack size: **100 x EA**

- Affixing Method: Cable Tie
- Maximum Cable Diameter: 4.8 mm
- Colour: White
- Length: 50.5 mm
- Width: 19 mm
- Quantity: 100
- Printable: No
- Material: Nylon 66



492314 Cable Tie

RS PRO CABLE TIE CABLE MARKERS, WHITE

Pack size: **100 x EA**

- Affixing Method: Cable Tie
- Maximum Cable Diameter: 4.8 mm
- Colour: White
- Length: 65 mm
- Width: 19 mm
- Quantity: 100
- Printable: No
- Material: Nylon 66



492320 Cable Tie

RS PRO SLIDE ON CABLE MARKER, WHITE ON BLACK, PRE-PRINTED "0"

Pack size: **250 x EA**

- Affixing Method: Slide On
- Legend: 0
- Minimum Cable Diameter: 1.3 mm
- Maximum Cable Diameter: 3 mm
- Colour: White on Black
- Material: PVC
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: 60 °C



2153019 Slide On

RS PRO SLIDE ON CABLE MARKER, WHITE ON BROWN, PRE-PRINTED "1"

Pack size: **250 x EA**

- Affixing Method: Slide On
- Legend: 1
- Minimum Cable Diameter: 1.3 mm
- Maximum Cable Diameter: 3 mm
- Colour: White on Brown
- Material: PVC
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: 60 °C



2153021 Slide On

RS PRO SLIDE ON CABLE MARKER, BLACK ON RED, PRE-PRINTED "2"

Pack size: **250 x EA**

- Affixing Method: Slide On
- Legend: 2
- Minimum Cable Diameter: 1.3 mm
- Maximum Cable Diameter: 3 mm
- Colour: Black on Red
- Material: PVC
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: 60 °C



2153022 Slide On

RS PRO SLIDE ON CABLE MARKER, BLACK ON ORANGE, PRE-PRINTED "3"

Pack size: **250 x EA**

- Affixing Method: Slide On
- Legend: 3
- Minimum Cable Diameter: 1.3 mm
- Maximum Cable Diameter: 3 mm
- Colour: Black on Orange
- Material: PVC
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: 60 °C



2153023 Slide On

RS PRO SLIDE ON CABLE MARKER, BLACK ON YELLOW, PRE-PRINTED "4"

Pack size: **250 x EA**

- Affixing Method: Slide On
- Legend: 4
- Minimum Cable Diameter: 1.3 mm
- Maximum Cable Diameter: 3 mm
- Colour: Black on Yellow
- Material: PVC
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: 60 °C



2153024 Slide On

RS PRO SLIDE ON CABLE MARKER, BLACK ON GREEN, PRE-PRINTED "5"

Pack size: **250 x EA**

- Affixing Method: Slide On
- Legend: 5
- Minimum Cable Diameter: 1.3 mm
- Maximum Cable Diameter: 3 mm
- Colour: Black on Green
- Material: PVC
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: 60 °C



2153025 Slide On

RS PRO SLIDE ON CABLE MARKER, BLACK ON BLUE, PRE-PRINTED "6"

- Pack size: **250 x EA**
- Affixing Method: Slide On
 - Legend: 6
 - Minimum Cable Diameter: 1.3 mm
 - Maximum Cable Diameter: 3 mm
 - Colour: Black on Blue
 - Material: PVC
 - Minimum Operating Temperature: 0 °C
 - Maximum Operating Temperature: 60 °C



2153026 Slide On

RS PRO SLIDE ON CABLE MARKER, BLACK ON WHITE, PRE-PRINTED "1"

- Pack size: **250 x EA**
- Affixing Method: Slide On
 - Legend: 1
 - Minimum Cable Diameter: 1.3 mm
 - Maximum Cable Diameter: 3 mm
 - Colour: Black on White
 - Material: PVC
 - Minimum Operating Temperature: 0 °C
 - Maximum Operating Temperature: 60 °C



2153031 Slide On

RS PRO SLIDE ON CABLE MARKER, BLACK ON RED, PRE-PRINTED "2"

- Pack size: **1000 x EA**
- Affixing Method: Slide On
 - Legend: 2
 - Minimum Cable Diameter: 2.5 mm
 - Maximum Cable Diameter: 5.1 mm
 - Colour: Black on Red
 - Material: PVC
 - Minimum Operating Temperature: 0 °C
 - Maximum Operating Temperature: 60 °C



2153036 Slide On

RS PRO SLIDE ON CABLE MARKER, BLACK ON YELLOW, PRE-PRINTED "4"

- Pack size: **250 x EA**
- Affixing Method: Slide On
 - Legend: 4
 - Minimum Cable Diameter: 2.5 mm
 - Maximum Cable Diameter: 5.1 mm
 - Colour: Black on Yellow
 - Material: PVC
 - Minimum Operating Temperature: 0 °C
 - Maximum Operating Temperature: 60 °C



2153039 Slide On

RS PRO SLIDE ON CABLE MARKER, BLACK ON VIOLET, PRE-PRINTED "7"

- Pack size: **250 x EA**
- Affixing Method: Slide On
 - Legend: 7
 - Minimum Cable Diameter: 1.3 mm
 - Maximum Cable Diameter: 3 mm
 - Colour: Black on Violet
 - Material: PVC
 - Minimum Operating Temperature: 0 °C
 - Maximum Operating Temperature: 60 °C



2153028 Slide On

RS PRO SLIDE ON CABLE MARKER, WHITE ON BLACK, PRE-PRINTED "0"

- Pack size: **250 x EA**
- Affixing Method: Slide On
 - Legend: 0
 - Minimum Cable Diameter: 2.5 mm
 - Maximum Cable Diameter: 5.1 mm
 - Colour: White on Black
 - Material: PVC
 - Minimum Operating Temperature: 0 °C
 - Maximum Operating Temperature: 60 °C



2153033 Slide On

RS PRO SLIDE ON CABLE MARKER, BLACK ON RED, PRE-PRINTED "2"

- Pack size: **250 x EA**
- Affixing Method: Slide On
 - Legend: 2
 - Minimum Cable Diameter: 2.5 mm
 - Maximum Cable Diameter: 5.1 mm
 - Colour: Black on Red
 - Material: PVC
 - Minimum Operating Temperature: 0 °C
 - Maximum Operating Temperature: 60 °C



2153037 Slide On

RS PRO SLIDE ON CABLE MARKER, BLACK ON BLUE, PRE-PRINTED "6"

- Pack size: **250 x EA**
- Affixing Method: Slide On
 - Legend: 6
 - Minimum Cable Diameter: 2.5 mm
 - Maximum Cable Diameter: 5.1 mm
 - Colour: Black on Blue
 - Material: PVC
 - Minimum Operating Temperature: 0 °C
 - Maximum Operating Temperature: 60 °C



2153041 Slide On

RS PRO SLIDE ON CABLE MARKER, BLACK ON GREY, PRE-PRINTED "8"

- Pack size: **250 x EA**
- Affixing Method: Slide On
 - Legend: 8
 - Minimum Cable Diameter: 1.3 mm
 - Maximum Cable Diameter: 3 mm
 - Colour: Black on Grey
 - Material: PVC
 - Minimum Operating Temperature: 0 °C
 - Maximum Operating Temperature: 60 °C



2153029 Slide On

RS PRO SLIDE ON CABLE MARKER, WHITE ON BROWN, PRE-PRINTED "1"

- Pack size: **1000 x EA**
- Affixing Method: Slide On
 - Legend: 1
 - Minimum Cable Diameter: 2.5 mm
 - Maximum Cable Diameter: 5.1 mm
 - Colour: White on Brown
 - Material: PVC
 - Minimum Operating Temperature: 0 °C
 - Maximum Operating Temperature: 60 °C



2153034 Slide On

RS PRO SLIDE ON CABLE MARKER, BLACK ON GREEN, PRE-PRINTED "5"

- Pack size: **250 x EA**
- Affixing Method: Slide On
 - Legend: 5
 - Minimum Cable Diameter: 2.5 mm
 - Maximum Cable Diameter: 5.1 mm
 - Colour: Black on Green
 - Material: PVC
 - Minimum Operating Temperature: 0 °C
 - Maximum Operating Temperature: 60 °C



2153040 Slide On

RS PRO SLIDE ON CABLE MARKER, BLACK ON VIOLET, PRE-PRINTED "7"

- Pack size: **250 x EA**
- Affixing Method: Slide On
 - Legend: 7
 - Minimum Cable Diameter: 2.5 mm
 - Maximum Cable Diameter: 5.1 mm
 - Colour: Black on Violet
 - Material: PVC
 - Minimum Operating Temperature: 0 °C
 - Maximum Operating Temperature: 60 °C



2153042 Slide On

RS PRO SLIDE ON CABLE MARKER, BLACK ON WHITE, PRE-PRINTED "9"

- Pack size: **250 x EA**
- Affixing Method: Slide On
 - Legend: 9
 - Minimum Cable Diameter: 1.3 mm
 - Maximum Cable Diameter: 3 mm
 - Colour: Black on White
 - Material: PVC
 - Minimum Operating Temperature: 0 °C
 - Maximum Operating Temperature: 60 °C



2153030 Slide On

RS PRO SLIDE ON CABLE MARKER, WHITE ON BROWN, PRE-PRINTED "1"

- Pack size: **250 x EA**
- Affixing Method: Slide On
 - Legend: 1
 - Minimum Cable Diameter: 2.5 mm
 - Maximum Cable Diameter: 5.1 mm
 - Colour: White on Brown
 - Material: PVC
 - Minimum Operating Temperature: 0 °C
 - Maximum Operating Temperature: 60 °C



2153035 Slide On

RS PRO SLIDE ON CABLE MARKER, BLACK ON ORANGE, PRE-PRINTED "3"

- Pack size: **250 x EA**
- Affixing Method: Slide On
 - Legend: 3
 - Minimum Cable Diameter: 2.5 mm
 - Maximum Cable Diameter: 5.1 mm
 - Colour: Black on Orange
 - Material: PVC
 - Minimum Operating Temperature: 0 °C
 - Maximum Operating Temperature: 60 °C



2153038 Slide On

RS PRO SLIDE ON CABLE MARKER, BLACK ON GREY, PRE-PRINTED "8"

- Pack size: **250 x EA**
- Affixing Method: Slide On
 - Legend: 8
 - Minimum Cable Diameter: 2.5 mm
 - Maximum Cable Diameter: 5.1 mm
 - Colour: Black on Grey
 - Material: PVC
 - Minimum Operating Temperature: 0 °C
 - Maximum Operating Temperature: 60 °C



2153043 Slide On

RS PRO SLIDE ON CABLE MARKER, BLACK ON WHITE, PRE-PRINTED "9"

Pack size: **250 x EA**

- Affixing Method: Slide On
- Legend: 9
- Minimum Cable Diameter: 2.5 mm
- Maximum Cable Diameter: 5.1 mm
- Colour: Black on White
- Material: PVC
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: 60 °C



2153044 Slide On

RS PRO TIE CABLE MARKER, NATURAL

Pack size: **50 x EA**

- Affixing Method: Tie
- Colour: Natural
- Length: 30 mm
- Width: 9.5 mm
- Material: PE
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: 70 °C
- Operating Temperature Range: 0°C→+70°C



2153046 Tie

RS PRO TIE CABLE MARKER, NATURAL

Pack size: **50 x EA**

- Affixing Method: Tie
- Colour: Natural
- Length: 40 mm
- Width: 17 mm
- Material: PE
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: 70 °C
- Operating Temperature Range: 0°C→+70°C



2153047 Tie

RS PRO CLIP ON CABLE MARKER, WHITE ON BLACK, PRE-PRINTED "0"

Pack size: **1200 x EA**

- Affixing Method: Clip On
- Legend: 0
- Minimum Cable Diameter: 2.2 mm
- Maximum Cable Diameter: 2.8 mm
- Colour: White on Black
- Material: Nylon 66
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: 85 °C



2153051 Clip On

RS PRO SLIDE ON CABLE MARKER, BLACK ON WHITE, PRE-PRINTED

Pack size: **250 x EA**

- Affixing Method: Slide On
- Legend: Earth
- Minimum Cable Diameter: 3 mm
- Maximum Cable Diameter: 4.2 mm
- Colour: Black on White
- Printable: No
- Material: PVC
- Minimum Operating Temperature: 0 °C



2252177 Slide On

RS PRO CLIP ON CABLE MARKER, WHITE ON BROWN, PRE-PRINTED "1"

Pack size: **1200 x EA**

- Affixing Method: Clip On
- Legend: 1
- Minimum Cable Diameter: 3 mm
- Maximum Cable Diameter: 3.6 mm
- Colour: White on Brown
- Material: Nylon 66
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: 85 °C



2153056 Clip On

RS PRO SLIDE ON CABLE MARKERS, BLACK ON YELLOW, PRE-PRINTED "1",

Pack size: **1000 x EA**

- Affixing Method: Slide On
- Legend: 1
- Minimum Cable Diameter: 3 mm
- Maximum Cable Diameter: 4.2 mm
- Colour: Black on Yellow
- Length: 4 mm
- Quantity: 1000
- Printable: No



8120802 Slide On

RS PRO SLIDE ON CABLE MARKER, BLACK ON WHITE, 3 → 4.2MM CABLE

Pack size: **250 x EA**

- Affixing Method: Slide On
- Minimum Cable Diameter: 3 mm
- Maximum Cable Diameter: 4.2 mm
- Colour: Black on White
- Printable: No
- Material: PVC
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: +70 °C



2252169 Slide On

RS PRO SLIDE ON CABLE MARKERS, BLACK ON YELLOW, PRE-PRINTED "0",

Pack size: **1000 x EA**

- Affixing Method: Slide On
- Legend: 0
- Minimum Cable Diameter: 3 mm
- Maximum Cable Diameter: 4.2 mm
- Colour: Black on Yellow
- Length: 4 mm
- Quantity: 1000
- Printable: No



8120809 Slide On

RS PRO SLIDE ON CABLE MARKER, BLACK ON WHITE, PRE-PRINTED "+", 3

Pack size: **250 x EA**

- Affixing Method: Slide On
- Legend: +
- Minimum Cable Diameter: 3 mm
- Maximum Cable Diameter: 4.2 mm
- Colour: Black on White
- Printable: No
- Material: PVC
- Minimum Operating Temperature: 0 °C



2252170 Slide On

RS PRO SLIDE ON CABLE MARKERS, BLACK ON YELLOW, PRE-PRINTED "3",

Pack size: **1000 x EA**

- Affixing Method: Slide On
- Legend: 3
- Minimum Cable Diameter: 3 mm
- Maximum Cable Diameter: 4.2 mm
- Colour: Black on Yellow
- Length: 4 mm
- Quantity: 1000
- Printable: No



8120815 Slide On

RS PRO SLIDE ON CABLE MARKERS, BLACK ON YELLOW, PRE-PRINTED "6",

Pack size: **1000 x EA**

- Affixing Method: Slide On
- Legend: 6
- Minimum Cable Diameter: 3 mm
- Maximum Cable Diameter: 4.2 mm
- Colour: Black on Yellow
- Length: 4 mm
- Quantity: 1000
- Printable: No



8120821 Slide On

RS PRO SLIDE ON CABLE MARKERS, BLACK ON YELLOW, PRE-PRINTED "2",

Pack size: **1000 x EA**

- Affixing Method: Slide On
- Legend: 2
- Minimum Cable Diameter: 3 mm
- Maximum Cable Diameter: 4.2 mm
- Colour: Black on Yellow
- Length: 4 mm
- Quantity: 1000
- Printable: No



8120806 Slide On

RS PRO SLIDE ON CABLE MARKERS, BLACK ON YELLOW, PRE-PRINTED "7",

Pack size: **1000 x EA**

- Affixing Method: Slide On
- Legend: 7
- Minimum Cable Diameter: 3 mm
- Maximum Cable Diameter: 4.2 mm
- Colour: Black on Yellow
- Length: 4 mm
- Quantity: 1000
- Printable: No



8120824 Slide On

RS PRO SLIDE ON CABLE MARKERS, BLACK ON YELLOW, PRE-PRINTED "8",

Pack size: **1000 x EA**

- Affixing Method: Slide On
- Legend: 8
- Minimum Cable Diameter: 3 mm
- Maximum Cable Diameter: 4.2 mm
- Colour: Black on Yellow
- Length: 4 mm
- Quantity: 1000
- Printable: No



8120828 Slide On

RS PRO SLIDE ON CABLE MARKERS, BLACK ON YELLOW, PRE-PRINTED "A",

Pack size: **1000 x EA**

- Affixing Method: Slide On
- Legend: A
- Minimum Cable Diameter: 3 mm
- Maximum Cable Diameter: 4.2 mm
- Colour: Black on Yellow
- Length: 4 mm
- Quantity: 1000
- Printable: No



8120830 Slide On

**RS PRO SLIDE ON CABLE MARKERS,
BLACK ON YELLOW, PRE-PRINTED**

Pack size: **1000 x EA**

- Affixing Method: Slide On
- Legend: C
- Minimum Cable Diameter: 3 mm
- Maximum Cable Diameter: 4.2 mm
- Colour: Black on Yellow
- Length: 4 mm
- Quantity: 1000
- Printable: No



8120843 Slide On

**RS PRO SLIDE ON CABLE MARKERS,
BLACK ON YELLOW, PRE-PRINTED "5",**

Pack size: **1000 x EA**

- Affixing Method: Slide On
- Legend: 5
- Minimum Cable Diameter: 3 mm
- Maximum Cable Diameter: 4.2 mm
- Colour: Black on Yellow
- Length: 4 mm
- Quantity: 1000
- Printable: No



8120812 Slide On

RS PRO SLIDE ON CABLE MARKERS, BLACK ON YELLOW, PRE-PRINTED "L",

Pack size: **1000 x EA**

- Affixing Method: Slide On
- Legend: L
- Minimum Cable Diameter: 3 mm
- Maximum Cable Diameter: 4.2 mm
- Colour: Black on Yellow
- Length: 4 mm
- Quantity: 1000
- Printable: No



8120871 Slide On

RS PRO SLIDE ON CABLE MARKERS, BLACK ON YELLOW. PRE-PRINTED "F".

Pack size: **1000 x EA**

- Affixing Method: Slide On
- Legend: F
- Minimum Cable Diameter: 3 mm
- Maximum Cable Diameter: 4.2 mm
- Colour: Black on Yellow
- Length: 4 mm
- Quantity: 1000
- Printable: No



8120859 Slide On

RS PRO SLIDE ON CABLE MARKERS, BLACK ON YELLOW, PRE-PRINTED "A".

Pack size: **500 x EA**

- Affixing Method: Slide On
- Legend: A
- Minimum Cable Diameter: 3.6 mm
- Maximum Cable Diameter: 7.4 mm
- Colour: Black on Yellow
- Length: 5 mm
- Quantity: 500
- Printable: No



8120963 Slide On

**RS PRO SLIDE ON CABLE MARKERS,
BLACK ON YELLOW, PRE-PRINTED**

Pack size: **500 x EA**

- Affixing Method: Slide On
- Legend: C
- Minimum Cable Diameter: 3.6 mm
- Maximum Cable Diameter: 7.4 mm
- Colour: Black on Yellow
- Length: 5 mm
- Quantity: 500
- Printable: No



8120975 Slide On

RS PRO SLIDE ON CABLE MARKERS, BLACK ON YELLOW. PRE-PRINTED "E".

Pack size: **500 x EA**

- Affixing Method: Slide On
- Legend: E
- Minimum Cable Diameter: 3.6 mm
- Maximum Cable Diameter: 7.4 mm
- Colour: Black on Yellow
- Length: 5 mm
- Quantity: 500
- Printable: No



8120988 Slide On

**RS PRO SLIDE ON CABLE MARKERS,
BLACK ON YELLOW, PRE-PRINTED**

Pack size: **500 x EA**

- Affixing Method: Slide On
- Legend: M
- Minimum Cable Diameter: 3.6 mm
- Maximum Cable Diameter: 7.4 mm
- Colour: Black on Yellow
- Length: 5 mm
- Quantity: 500
- Printable: No



8121001 Slide On

RS PRO SLIDE ON CABLE MARKERS, BLACK ON YELLOW, PRE-PRINTED "0".

Pack size: **500 x EA**

- Affixing Method: Slide On
- Legend: 0
- Minimum Cable Diameter: 3.5 mm
- Maximum Cable Diameter: 7 mm
- Colour: Black on Yellow
- Length: 5 mm
- Quantity: 500
- Printable: No



8121076 Slide On

RS PRO SLIDE ON CABLE MARKERS, BLACK ON YELLOW, PRE-PRINTED "5".

Pack size: **500 x EA**

- Affixing Method: Slide On
- Legend: 5
- Minimum Cable Diameter: 3.5 mm
- Maximum Cable Diameter: 7 mm
- Colour: Black on Yellow
- Length: 5 mm
- Quantity: 500
- Printable: No



8121089 Slide On

RS PRO SLIDE ON CABLE MARKERS, BLACK ON YELLOW. PRE-PRINTED "B".

Pack size: **500 x EA**

- Affixing Method: Slide On
- Legend: B
- Minimum Cable Diameter: 3.5 mm
- Maximum Cable Diameter: 7 mm
- Colour: Black on Yellow
- Length: 5 mm
- Quantity: 500
- Printable: No



8121102 Slide On

**RS PRO SLIDE ON CABLE MARKERS,
BLACK ON YELLOW, PRE-PRINTED "L",**

Pack size: **500 x EA**

- Affixing Method: Slide On
- Legend: L
- Minimum Cable Diameter: 3.5 mm
- Maximum Cable Diameter: 7 mm
- Colour: Black on Yellow
- Length: 5 mm
- Quantity: 500
- Printable: No



8121149 Slide On

RS PRO SLIDE ON CABLE MARKERS, BLACK ON YELLOW, PRE-PRINTED

Pack size: **500 x EA**

- Affixing Method: Slide On
- Legend: O
- Minimum Cable Diameter: 3.5 mm
- Maximum Cable Diameter: 7 mm
- Colour: Black on Yellow
- Length: 5 mm
- Quantity: 500
- Printable: No



8121155 Slide On

RS PRO SLIDE ON CABLE MARKERS, BLACK ON YELLOW, PRE-PRINTED "T",

Pack size: **500 x EA**

- Affixing Method: Slide On
- Legend: T
- Minimum Cable Diameter: 3.5 mm
- Maximum Cable Diameter: 7 mm
- Colour: Black on Yellow
- Length: 5 mm
- Quantity: 500
- Printable: No



8121168 Slide On

RS PRO SLIDE ON CABLE MARKERS, BLACK ON YELLOW, PRE-PRINTED "V",

Pack size: **500 x EA**

- Affixing Method: Slide On
- Legend: V
- Minimum Cable Diameter: 3.5 mm
- Maximum Cable Diameter: 7 mm
- Colour: Black on Yellow
- Length: 5 mm
- Quantity: 500
- Printable: No



8121170 Slide On

RS PRO SLIDE ON CABLE MARKERS, BLACK ON YELLOW, PRE-PRINTED

Pack size: **500 x EA**

- Affixing Method: Slide On
- Legend: W
- Minimum Cable Diameter: 3.5 mm
- Maximum Cable Diameter: 7 mm
- Colour: Black on Yellow
- Length: 5 mm
- Quantity: 500
- Printable: No



8121174 Slide On

RS PRO SLIDE ON CABLE MARKERS, BLACK ON YELLOW, PRE-PRINTED "U",

Pack size: **500 x EA**

- Affixing Method: Slide On
- Legend: U
- Minimum Cable Diameter: 3.5 mm
- Maximum Cable Diameter: 7 mm
- Colour: Black on Yellow
- Length: 5 mm
- Quantity: 500
- Printable: No



8121177 Slide On

RS PRO SLIDE ON CABLE MARKERS, BLACK ON YELLOW, PRE-PRINTED "-",

Pack size: **500 x EA**

- Affixing Method: Slide On
- Legend: -
- Minimum Cable Diameter: 3.5 mm
- Maximum Cable Diameter: 7 mm
- Colour: Black on Yellow
- Length: 5 mm
- Quantity: 500
- Printable: No



8121196 Slide On

RS PRO SLIDE ON CABLE MARKERS, BLACK ON YELLOW, PRE-PRINTED "/"

Pack size: **500 x EA**

- Affixing Method: Slide On
- Legend: /
- Minimum Cable Diameter: 3.5 mm
- Maximum Cable Diameter: 7 mm
- Colour: Black on Yellow
- Length: 5 mm
- Quantity: 500
- Printable: No



8121199 Slide On

RS PRO CLIP ON CABLE MARKERS, YELLOW, PRE-PRINTED "0 → 9"

Pack size: **150 x EA**

- Affixing Method: Clip On
- Legend: 0 → 9
- Colour: Yellow
- Length: 2.9 mm
- Quantity: 150
- Printable: No
- Material: Nylon 66
- Standards Met: RoHS Compliant, UL, UL 94 V-2



8121203 Clip On

RS PRO CLIP ON CABLE MARKERS, BLACK ON YELLOW, PRE-PRINTED "A

Pack size: **195 x EA**

- Affixing Method: Clip On
- Legend: A → M
- Colour: Black on Yellow
- Length: 2.9 mm
- Quantity: 195
- Printable: No
- Material: Nylon 66
- Standards Met: RoHS Compliant, UL, UL 94 V-2



8121212 Clip On

RS PRO CLIP ON CABLE MARKERS, BLACK, BROWN, GREEN, GREY,

Pack size: **150 x EA**

- Affixing Method: Clip On
- Legend: 0 → 9
- Colour: Black, Brown, Green, Grey, Orange, Red, Violet, White, Yellow
- Length: 2.8 mm
- Quantity: 150
- Printable: No
- Material: Nylon 66
- Standards Met: RoHS Compliant, UL, UL 94 V-2



8121219 Clip On

RS PRO CLIP ON CABLE MARKERS, BLACK, BROWN, GREEN, GREY,

Pack size: **100 x EA**

- Affixing Method: Clip On
- Legend: 0 → 9
- Colour: Black, Brown, Green, Grey, Orange, Red, Violet, White, Yellow
- Length: 2.9 mm
- Quantity: 100
- Printable: No
- Material: Nylon 66
- Standards Met: RoHS Compliant, UL, UL 94 V-2



8121225 Clip On

RS PRO CLIP ON CABLE MARKERS, BLACK, BROWN, GREEN, GREY,

Pack size: **250 x EA**

- Affixing Method: Clip On
- Legend: 0 → 9
- Colour: Black, Brown, Green, Grey, Orange, Red, Violet, White, Yellow
- Length: 2.3 mm
- Quantity: 250
- Printable: No
- Material: Nylon 66
- Standards Met: RoHS Compliant, UL, UL 94 V-2



8121231 Clip On

RS PRO CLIP ON CABLE MARKERS, BLACK ON YELLOW, PRE-PRINTED "A

Pack size: **130 x EA**

- Affixing Method: Clip On
- Legend: A → M
- Colour: Black on Yellow
- Length: 2.9 mm
- Quantity: 130
- Printable: No
- Material: Nylon 66
- Standards Met: RoHS Compliant, UL, UL 94 V-2



8121234 Clip On

RS PRO CLIP ON CABLE MARKERS, BLACK ON YELLOW, PRE-PRINTED "N

Pack size: **130 x EA**

- Affixing Method: Clip On
- Legend: N → Z
- Colour: Black on Yellow
- Length: 2.9 mm
- Quantity: 130
- Printable: No
- Material: Nylon 66
- Standards Met: RoHS Compliant, UL, UL 94 V-2



8121237 Clip On

RS PRO CLIP ON CABLE MARKERS, BLACK ON YELLOW, PRE-PRINTED "/"

Pack size: **325 x EA**

- Affixing Method: Clip On
- Legend: A → M
- Colour: Black on Yellow
- Length: 2.3 mm
- Quantity: 325
- Printable: No
- Material: Nylon 66
- Standards Met: RoHS Compliant, UL, UL 94 V-2



8121240 Clip On

RS PRO CLIP ON CABLE MARKERS, BLACK ON YELLOW, PRE-PRINTED "N

Pack size: **325 x EA**

- Affixing Method: Clip On
- Legend: N → Z
- Colour: Black on Yellow
- Length: 2.3 mm
- Quantity: 325
- Printable: No
- Material: Nylon 66
- Standards Met: RoHS Compliant, UL, UL 94 V-2



8121243 Clip On

**RS PRO SNAP ON CABLE MARKERS,
BLACK ON ORANGE, PRE-PRINTED**

Pack size: **100 x EA**

- Affixing Method: Snap On
- Legend: 4
- Minimum Cable Diameter: 3 mm
- Maximum Cable Diameter: 3.4 mm
- Colour: Black on Orange
- Length: 4 mm
- Quantity: 100
- Printable: No



8121262 Snap On

RS PRO SNAP ON CABLE MARKERS, BLACK ON ORANGE, PRE-PRINTED

Pack size: **100 x EA**

- Affixing Method: Snap On
- Legend: 9
- Minimum Cable Diameter: 3 mm
- Maximum Cable Diameter: 3.4 mm
- Colour: Black on Orange
- Length: 4 mm
- Quantity: 100
- Printable: No



8121275 Snap On

**RS PRO SNAP ON CABLE MARKERS,
BLACK ON ORANGE, PRE-PRINTED**

Pack size: **100 x EA**

- Affixing Method: Snap On
- Legend: 2
- Minimum Cable Diameter: 4 mm
- Maximum Cable Diameter: 5 mm
- Colour: Black on Orange
- Length: 4 mm
- Quantity: 100
- Printable: No



8121398 Snap On

**RS PRO SNAP ON CABLE MARKERS,
BLACK ON ORANGE. PRE-PRINTED**

Pack size: **100 x EA**

- Affixing Method: Snap On
- Legend: 8
- Minimum Cable Diameter: 4 mm
- Maximum Cable Diameter: 5 mm
- Colour: Black on Orange
- Length: 4 mm
- Quantity: 100
- Printable: No



8121411 Snap On

RS PRO SNAP ON CABLE MARKERS, BLACK ON ORANGE, PRE-PRINTED

Pack size: **100 x EA**

- Affixing Method: Snap On
- Legend: 6
- Minimum Cable Diameter: 4 mm
- Maximum Cable Diameter: 5 mm
- Colour: Black on Orange
- Length: 4 mm
- Quantity: 100
- Printable: No



8121414 Snap On

RS PRO SNAP ON CABLE MARKERS, BLACK ON ORANGE, PRE-PRINTED

Pack size: **100 x EA**

- Affixing Method: Snap On
- Legend: 7
- Minimum Cable Diameter: 4 mm
- Maximum Cable Diameter: 5 mm
- Colour: Black on Orange
- Length: 4 mm
- Quantity: 100
- Printable: No



8121417 Snap On

RS PRO SNAP ON CABLE MARKERS, BLACK ON ORANGE, PRE-PRINTED

Pack size: **100 x EA**

- Affixing Method: Snap On
- Legend: 9
- Minimum Cable Diameter: 4 mm
- Maximum Cable Diameter: 5 mm
- Colour: Black on Orange
- Length: 4 mm
- Quantity: 100
- Printable: No



8121420 Snap On

RS PRO SNAP ON CABLE MARKERS, BLACK ON ORANGE, PRE-PRINTED

Pack size: **100 x EA**

- Affixing Method: Snap On
- Legend: A
- Minimum Cable Diameter: 4 mm
- Maximum Cable Diameter: 5 mm
- Colour: Black on Orange
- Length: 4 mm
- Quantity: 100
- Printable: No



8121423 Snap On

RS PRO SNAP ON CABLE MARKERS, BLACK ON ORANGE, PRE-PRINTED

Pack size: **100 x EA**

- Affixing Method: Snap On
- Legend: B
- Minimum Cable Diameter: 4 mm
- Maximum Cable Diameter: 5 mm
- Colour: Black on Orange
- Length: 4 mm
- Quantity: 100
- Printable: No



8121427 Snap On

RS PRO SNAP ON CABLE MARKERS, BLACK ON ORANGE, PRE-PRINTED

Pack size: **100 x EA**

- Affixing Method: Snap On
- Legend: C
- Minimum Cable Diameter: 4 mm
- Maximum Cable Diameter: 5 mm
- Colour: Black on Orange
- Length: 4 mm
- Quantity: 100
- Printable: No



8121436 Snap On

RS PRO SNAP ON CABLE MARKERS, BLACK ON ORANGE, PRE-PRINTED

Pack size: **100 x EA**

- Affixing Method: Snap On
- Legend: D
- Minimum Cable Diameter: 4 mm
- Maximum Cable Diameter: 5 mm
- Colour: Black on Orange
- Length: 4 mm
- Quantity: 100
- Printable: No



8121439 Snap On

RS PRO SNAP ON CABLE MARKERS, BLACK ON ORANGE, PRE-PRINTED

Pack size: **100 x EA**

- Affixing Method: Snap On
- Legend: M
- Minimum Cable Diameter: 4 mm
- Maximum Cable Diameter: 5 mm
- Colour: Black on Orange
- Length: 4 mm
- Quantity: 100
- Printable: No



8121467 Snap On

RS PRO SNAP ON CABLE MARKERS, BLACK ON ORANGE, PRE-PRINTED

Pack size: **100 x EA**

- Affixing Method: Snap On
- Legend: P
- Minimum Cable Diameter: 4 mm
- Maximum Cable Diameter: 5 mm
- Colour: Black on Orange
- Length: 4 mm
- Quantity: 100
- Printable: No



8121473 Snap On

RS PRO SNAP ON CABLE MARKERS, BLACK ON ORANGE, PRE-PRINTED

Pack size: **100 x EA**

- Affixing Method: Snap On
- Legend: R
- Minimum Cable Diameter: 4 mm
- Maximum Cable Diameter: 5 mm
- Colour: Black on Orange
- Length: 4 mm
- Quantity: 100
- Printable: No



8121486 Snap On

RS PRO SNAP ON CABLE MARKERS, BLACK ON ORANGE, PRE-PRINTED

Pack size: **100 x EA**

- Affixing Method: Snap On
- Legend: U
- Minimum Cable Diameter: 4 mm
- Maximum Cable Diameter: 5 mm
- Colour: Black on Orange
- Length: 4 mm
- Quantity: 100
- Printable: No



8121492 Snap On

RS PRO ADHESIVE CABLE MARKERS, BLACK ON WHITE, PRE-PRINTED "0" →

Pack size: **1 x EA**

- Affixing Method: Adhesive
- Legend: 0 → 9
- Colour: Black on White
- Length: 33 mm
- Width: 5.6 mm
- Quantity: 10
- Printable: No
- Material: Vinyl Coated Cloth



8121528 Adhesive

RS PRO ADHESIVE CABLE MARKERS, BLACK ON WHITE, PRE-PRINTED "1" →

Pack size: **1 x EA**

- Affixing Method: Adhesive
- Legend: 1 → 45
- Colour: Black on White
- Length: 33 mm
- Width: 5.6 mm
- Quantity: 10
- Printable: No
- Material: Vinyl Coated Cloth



8121530 Adhesive

RS PRO ADHESIVE CABLE MARKERS, BLACK ON WHITE, PRE-PRINTED "46" →

Pack size: **1 x EA**

- Affixing Method: Adhesive
- Legend: 46 → 90
- Colour: Black on White
- Length: 33 mm
- Width: 5.6 mm
- Quantity: 10
- Printable: No
- Material: Vinyl Coated Cloth



8121534 Adhesive

RS PRO ADHESIVE CABLE MARKERS, BLACK ON WHITE, PRE-PRINTED "0" →

Pack size: **1 x EA**

- Affixing Method: Adhesive
- Legend: 0 → 15; -; /; +; A → Z
- Colour: Black on White
- Length: 33 mm
- Width: 5.6 mm
- Quantity: 10
- Printable: No
- Material: Vinyl Coated Cloth



8121537 Adhesive

RS PRO CABLE TIE CABLE MARKERS, NATURAL

Pack size: **100 x EA**

- Affixing Method: Cable Tie
- Colour: Natural
- Length: 130 mm
- Width: 2.5 mm
- Quantity: 100
- Printable: No
- Material: Nylon 66
- Standards Met: cULus E97527, RoHS Compliant, UL, UL 94 V-2



8121540 Cable Tie

RS PRO CABLE TIE CABLE MARKERS, NATURAL

Pack size: **100 x EA**

- Affixing Method: Cable Tie
- Colour: Natural
- Length: 270 mm
- Width: 4.6 mm
- Quantity: 100
- Printable: No
- Material: Nylon 66
- Standards Met: cULus E97527, RoHS Compliant, UL, UL 94 V-2



8121543 Cable Tie

RS PRO CABLE TIE CABLE MARKERS, NATURAL

Pack size: **100 x EA**

- Affixing Method: Cable Tie
- Colour: Natural
- Length: 200 mm
- Width: 4.6 mm
- Quantity: 100
- Printable: No
- Material: Nylon 66
- Standards Met: cULus E97527, RoHS Compliant, UL, UL 94 V-2



8121546 Cable Tie

RS PRO CABLE TIE CABLE MARKERS, NATURAL

Pack size: **100 x EA**

- Affixing Method: Cable Tie
- Colour: Natural
- Length: 300 mm
- Width: 4.8 mm
- Quantity: 100
- Printable: No
- Material: Nylon 66
- Standards Met: cULus E97527, RoHS Compliant, UL, UL 94 V-2



8121552 Cable Tie

RS PRO CABLE TIE CABLE MARKERS, NATURAL

Pack size: **100 x EA**

- Affixing Method: Cable Tie
- Colour: Natural
- Length: 110 mm
- Width: 2.5 mm
- Quantity: 100
- Printable: No
- Material: Nylon 66
- Standards Met: cULus E97527, RoHS Compliant, UL, UL 94 V-2



8121559 Cable Tie

RS PRO HEAT SHRINK CABLE MARKER, WHITE, 1.1 → 2.7MM CABLE

Pack size: **250 x EA**

- Affixing Method: Heat Shrink
- Minimum Cable Diameter: 1.1 mm
- Maximum Cable Diameter: 2.7 mm
- Colour: White
- Width: 3.2 mm
- Quantity: 250
- Material: Polyolefin
- Minimum Operating Temperature: -55 °C



8726202 Heat Shrink

RS PRO HEAT SHRINK CABLE MARKER, WHITE, 2.3 → 5.5MM CABLE

Pack size: **1000 x EA**

- Affixing Method: Heat Shrink
- Minimum Cable Diameter: 2.3 mm
- Maximum Cable Diameter: 5.5 mm
- Colour: White
- Width: 6.4 mm
- Quantity: 1000
- Material: Polyolefin
- Minimum Operating Temperature: -55 °C



8726242 Heat Shrink

RS PRO HEAT SHRINK CABLE MARKER, WHITE, 2.3 → 5.5MM CABLE

Pack size: **250 x EA**

- Affixing Method: Heat Shrink
- Minimum Cable Diameter: 2.3 mm
- Maximum Cable Diameter: 5.5 mm
- Colour: White
- Width: 6.4 mm
- Quantity: 250
- Material: Polyolefin
- Minimum Operating Temperature: -55 °C



8726249 Heat Shrink

RS PRO HEAT SHRINK CABLE MARKER, WHITE, 4.7 → 10.8MM CABLE

Pack size: **250 x EA**

- Affixing Method: Heat Shrink
- Minimum Cable Diameter: 4.7 mm
- Maximum Cable Diameter: 10.8 mm
- Colour: White
- Width: 12.7 mm
- Quantity: 250
- Material: Polyolefin
- Minimum Operating Temperature: -55 °C



8726261 Heat Shrink

RS PRO SLIDE ON CABLE MARKER KIT, BLACK, BLUE, BROWN, GREEN, GREY,

Pack size: **1 x KT**

- Affixing Method: Slide On
- Legend: -, +, 0 → 9, Earth, L, N, Plain, R, S, T
- Minimum Cable Diameter: 2 mm
- Maximum Cable Diameter: 8 mm
- Colour: Black, Blue, Brown, Green, Grey, Orange, Red, Violet, White, Yellow
- Quantity: 3600
- Printable: No
- Material: PVC



9140592 Slide On

RS PRO SLIDE ON CABLE MARKER KIT, BLACK, BLUE, BROWN, GREEN, GREY,

Pack size: **1 x KT**

- Affixing Method: Slide On
- Legend: -, +, 0 → 9, Earth, L, N, Plain, R, S, T
- Minimum Cable Diameter: 0.75 mm
- Maximum Cable Diameter: 3.5 mm
- Colour: Black, Blue, Brown, Green, Grey, Orange, Red, Violet, White, Yellow
- Quantity: 4500
- Printable: No
- Material: PVC



9140602 Slide On

RS PRO SLIDE ON CABLE MARKER KIT, BLACK, BLUE, BROWN, GREEN, GREY,

Pack size: **1 x KT**

- Affixing Method: Slide On
- Legend: -, +, 0 → 9, Earth, L, N, Plain, R, S, T
- Minimum Cable Diameter: 3.5 mm
- Maximum Cable Diameter: 8 mm
- Colour: Black, Blue, Brown, Green, Grey, Orange, Red, Violet, White, Yellow
- Quantity: 2700
- Printable: No
- Material: PVC



9140605 Slide On

CABLE, SLEEVE, HEAT RESISTING, GLASS FIBRE, BORE

Pack size: **3 x EA**

- Sleeve Diameter: 2 mm
- Colour: Red
- Material: Acrylic Fibreglass
- Sleeve Length: 5 m
- Braided: Yes
- Expandable: No
- Minimum Operating Temperature: -25 °C
- Maximum Operating Temperature: +155 °C



398745 2 mm

CABLE, SLEEVE, HEAT RESISTING, GLASS FIBRE, BORE

Pack size: **3 x EA**

- Sleeve Diameter: 2 mm
- Colour: Black
- Material: Acrylic Fibreglass
- Sleeve Length: 5 m
- Braided: Yes
- Expandable: No
- Minimum Cable Diameter: 2 mm
- Minimum Operating Temperature: -25 °C



398751 2 mm

CABLE, SLEEVE, HEAT RESISTING, GLASS FIBRE, BORE

Pack size: **3 x EA**

- Sleeve Diameter: 4 mm
- Colour: Red
- Material: Acrylic Fibreglass
- Sleeve Length: 5 m
- Braided: Yes
- Expandable: No
- Minimum Cable Diameter: 4 mm
- Minimum Operating Temperature: -25 °C



398846 4 mm

RS PRO BRAIDED ACRYLIC FIBREGLASS BLACK CABLE SLEEVE,

Pack size: **3 x EA**

- Sleeve Diameter: 4 mm
- Colour: Black
- Material: Acrylic Fibreglass
- Sleeve Length: 5 m
- Braided: Yes
- Expandable: No
- Minimum Cable Diameter: 4 mm
- Maximum Cable Diameter: 4 mm



398852 4 mm

RS PRO BRAIDED ACRYLIC FIBREGLASS GREEN CABLE SLEEVE,

Pack size: **3 x EA**

- Sleeve Diameter: 4 mm
- Colour: Green
- Material: Acrylic Fibreglass
- Sleeve Length: 5 m
- Braided: Yes
- Expandable: No
- Minimum Cable Diameter: 4 mm
- Minimum Operating Temperature: -25 °C



398874 4 mm

CABLE,SLEEVE,HEAT RESISTING,GLASS FIBRE,BORE

Pack size: **3 x EA**

- Sleeve Diameter: 4 mm
- Colour: Blue
- Material: Acrylic Fibreglass
- Sleeve Length: 5 m
- Braided: Yes
- Expandable: No
- Minimum Cable Diameter: 4 mm
- Minimum Operating Temperature: -25 °C



398880 4 mm

CABLE,SLEEVE,HEAT RESISTING,GLASS FIBRE,BORE

Pack size: **2 x EA**

- Sleeve Diameter: 6 mm
- Colour: Red
- Material: Acrylic Fibreglass
- Sleeve Length: 5 m
- Braided: Yes
- Expandable: No
- Minimum Cable Diameter: 6 mm
- Minimum Operating Temperature: -25 °C



398896 6 mm

CABLE,SLEEVE,HEAT RESISTING,GLASS FIBRE,BORE

Pack size: **2 x EA**

- Sleeve Diameter: 6 mm
- Colour: Black
- Material: Acrylic Fibreglass
- Sleeve Length: 5 m
- Braided: Yes
- Expandable: No
- Minimum Cable Diameter: 6 mm
- Minimum Operating Temperature: -25 °C



398903 6 mm

RS PRO SILICONE RUBBER GREEN CABLE SLEEVE, 1MM DIAMETER, 15M

Pack size: **15 x MTR**

- Sleeve Diameter: 1 mm
- Colour: Green
- Material: Silicone Rubber
- Sleeve Length: 15 m
- Braided: No
- Minimum Operating Temperature: -60 °C
- Maximum Operating Temperature: +180 °C
- Standards Met: RoHS Compliant, UL E345553



399401 1 mm

RS PRO SILICONE RUBBER RED CABLE SLEEVE, 1MM DIAMETER, 15M LENGTH

Pack size: **15 x MTR**

- Sleeve Diameter: 1 mm
- Colour: Red
- Material: Silicone Rubber
- Sleeve Length: 15 m
- Braided: No
- Minimum Operating Temperature: -60 °C
- Maximum Operating Temperature: +180 °C
- Dielectric Strength: 20 kV/mm



399417 1 mm

CABLE,SLEEVE,HEAT RESISTANT,SILICONE RUBBER,BORE

Pack size: **10 x MTR**

- Sleeve Diameter: 2 mm
- Colour: Green
- Material: Silicone Rubber
- Sleeve Length: 10 m
- Braided: No
- Minimum Operating Temperature: -60 °C
- Maximum Operating Temperature: +180 °C
- Dielectric Strength: 20 kV/mm



399439 2 mm

CABLE,SLEEVE,HEAT RESISTANT,SILICONE RUBBER,BORE

Pack size: **10 x MTR**

- Sleeve Diameter: 2 mm
- Colour: Red
- Material: Silicone Rubber
- Sleeve Length: 10 m
- Braided: No
- Minimum Operating Temperature: -60 °C
- Maximum Operating Temperature: +180 °C
- Dielectric Strength: 20 kV/mm



399445 2 mm

RS PRO BRAIDED ACRYLIC FIBREGASS BROWN CABLE SLEEVE,

Pack size: **3 x EA**

- Sleeve Diameter: 4 mm
- Colour: Brown
- Material: Acrylic Fibreglass
- Sleeve Length: 5 m
- Braided: Yes
- Expandable: No
- Minimum Cable Diameter: 4 mm
- Minimum Operating Temperature: -25 °C



399568 4 mm

CABLE,SLEEVE,PVC,3MM BORE,GREEN/YELLOW,40M

Pack size: **40 x MTR**

- Sleeve Diameter: 3 mm
- Colour: Green, Yellow
- Material: PVC
- Sleeve Length: 40 m
- Braided: No
- Minimum Cable Diameter: 3 mm
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +85 °C



404130 3 mm

RS PRO PVC BLUE CABLE SLEEVE, 3MM DIAMETER, 40M LENGTH

Pack size: **40 x MTR**

- Sleeve Diameter: 3 mm
- Colour: Blue
- Material: PVC
- Sleeve Length: 40 m
- Braided: No
- Minimum Cable Diameter: 3 mm
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +85 °C



404134 3 mm

CABLE,SLEEVE,PVC,3MM BORE,BLACK,40M

Pack size: **40 x MTR**

- Sleeve Diameter: 3 mm
- Colour: Black
- Material: PVC
- Sleeve Length: 40 m
- Braided: No
- Minimum Cable Diameter: 3 mm
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +85 °C



404140 3 mm

RS PRO PVC RED CABLE SLEEVE, 4MM DIAMETER, 30M LENGTH

Pack size: **30 x MTR**

- Sleeve Diameter: 4 mm
- Colour: Red
- Material: PVC
- Sleeve Length: 30 m
- Braided: No
- Minimum Cable Diameter: 4 mm
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +85 °C



404146 4 mm

RS PRO PVC GREEN, YELLOW CABLE SLEEVE, 4MM DIAMETER, 30M LENGTH

Pack size: **30 x MTR**

- Sleeve Diameter: 4 mm
- Colour: Green, Yellow
- Material: PVC
- Sleeve Length: 30 m
- Braided: No
- Minimum Cable Diameter: 4 mm
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +85 °C



404162 4 mm

RS PRO PVC BLUE CABLE SLEEVE, 4MM DIAMETER, 30M LENGTH

Pack size: **30 x MTR**

- Sleeve Diameter: 4 mm
- Colour: Blue
- Material: PVC
- Sleeve Length: 30 m
- Braided: No
- Minimum Cable Diameter: 4 mm
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +85 °C



404168 4 mm

RS PRO PVC GREEN CABLE SLEEVE, 4MM DIAMETER, 30M LENGTH

Pack size: **30 x MTR**

- Sleeve Diameter: 4 mm
- Colour: Green
- Material: PVC
- Sleeve Length: 30 m
- Braided: No
- Minimum Cable Diameter: 4 mm
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +85 °C



404174 4 mm

RS PRO PVC BROWN CABLE SLEEVE, 4MM DIAMETER, 30M LENGTH

Pack size: **30 x MTR**

- Sleeve Diameter: 4 mm
- Colour: Brown
- Material: PVC
- Sleeve Length: 30 m
- Braided: No
- Minimum Cable Diameter: 4 mm
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +85 °C



404178 4 mm

CABLE,SLEEVE,PVC,4MM BORE,BLACK,30M

Pack size: **30 x MTR**

- Sleeve Diameter: 4 mm
- Colour: Black
- Material: PVC
- Sleeve Length: 30 m
- Braided: No
- Minimum Cable Diameter: 4 mm
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +85 °C



404180 4 mm

RS PRO PVC GREY CABLE SLEEVE, 4MM DIAMETER, 30M LENGTH

Pack size: **30 x MTR**

- Sleeve Diameter: 4 mm
- Colour: Grey
- Material: PVC
- Sleeve Length: 30 m
- Braided: No
- Minimum Cable Diameter: 4 mm
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +85 °C



404184 4 mm

RS PRO PVC RED CABLE SLEEVE, 2MM DIAMETER, 50M LENGTH

Pack size: **50 x MTR**

- Sleeve Diameter: 2 mm
- Colour: Red
- Material: PVC
- Sleeve Length: 50 m
- Braided: No
- Minimum Cable Diameter: 2 mm
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +85 °C



404190 2 mm

CABLE,SLEEVE,PVC,6MM BORE,BLACK,10M

Pack size: **10 x MTR**

- Sleeve Diameter: 6 mm
- Colour: Black
- Material: PVC
- Sleeve Length: 10 m
- Braided: No
- Minimum Cable Diameter: 6 mm
- Maximum Cable Diameter: 6 mm
- Minimum Operating Temperature: -20 °C



404196 6 mm

CABLE,SLEEVE,PVC,6MM BORE,BLUE,10M

Pack size: **10 x MTR**

- Sleeve Diameter: 6 mm
- Colour: Blue
- Material: PVC
- Sleeve Length: 10 m
- Braided: No
- Minimum Cable Diameter: 6 mm
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +85 °C



404203 6 mm

RS PRO PVC BROWN CABLE SLEEVE, 6MM DIAMETER, 10M LENGTH

Pack size: **10 x MTR**

- Sleeve Diameter: 6 mm
- Colour: Brown
- Material: PVC
- Sleeve Length: 10 m
- Braided: No
- Minimum Cable Diameter: 6 mm
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +85 °C



404207 6 mm

CABLE,SLEEVE,PVC,6MM BORE,GREY,10M

Pack size: **10 x MTR**

- Sleeve Diameter: 6 mm
- Colour: Grey
- Material: PVC
- Sleeve Length: 10 m
- Braided: No
- Minimum Cable Diameter: 6 mm
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +85 °C



404213 6 mm

CABLE,SLEEVE,PVC,6MM BORE,GREEN/YELLOW,10M

Pack size: **10 x MTR**

- Sleeve Diameter: 6 mm
- Colour: Green, Yellow
- Material: PVC
- Sleeve Length: 10 m
- Braided: No
- Minimum Cable Diameter: 6 mm
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +85 °C



404219 6 mm

RS PRO PVC GREEN CABLE SLEEVE, 2MM DIAMETER, 50M LENGTH

Pack size: **50 x MTR**

- Sleeve Diameter: 2 mm
- Colour: Green
- Material: PVC
- Sleeve Length: 50 m
- Braided: No
- Minimum Cable Diameter: 2 mm
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +85 °C



404225 2 mm

CABLE,SLEEVE,PVC,10MM BORE,BLACK,10M

Pack size: **10 x MTR**

- Sleeve Diameter: 10 mm
- Colour: Black
- Material: PVC
- Sleeve Length: 10 m
- Braided: No
- Minimum Cable Diameter: 10 mm
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +85 °C



404229 10 mm

CABLE,SLEEVE,PVC,2MM BORE,GREEN/YELLOW,50M

Pack size: **50 x MTR**

- Sleeve Diameter: 2 mm
- Colour: Green, Yellow
- Material: PVC
- Sleeve Length: 50 m
- Braided: No
- Minimum Cable Diameter: 2 mm
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +85 °C



404231 2 mm

CABLE,SLEEVE,PVC,2MM BORE,BLACK,50M

Pack size: **50 x MTR**

- Sleeve Diameter: 2 mm
- Colour: Black
- Material: PVC
- Sleeve Length: 50 m
- Braided: No
- Minimum Cable Diameter: 2 mm
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +85 °C



404235 2 mm

RS PRO PVC GREY CABLE SLEEVE, 2MM DIAMETER, 50M LENGTH

Pack size: **50 x MTR**

- Sleeve Diameter: 2 mm
- Colour: Grey
- Material: PVC
- Sleeve Length: 50 m
- Braided: No
- Minimum Cable Diameter: 2 mm
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +85 °C



404247 2 mm

RS PRO PVC BROWN CABLE SLEEVE, 10MM DIAMETER, 10M LENGTH

Pack size: **10 x MTR**

- Sleeve Diameter: 10 mm
- Colour: Brown
- Material: PVC
- Sleeve Length: 10 m
- Braided: No
- Minimum Cable Diameter: 10 mm
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +85 °C



404499 10 mm

RS PRO PVC BLUE CABLE SLEEVE, 10MM DIAMETER, 10M LENGTH

Pack size: **10 x MTR**

- Sleeve Diameter: 10 mm
- Colour: Blue
- Material: PVC
- Sleeve Length: 10 m
- Braided: No
- Minimum Cable Diameter: 10 mm
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +85 °C



404506 10 mm

CABLE,SLEEVE,PVC,10MM BORE,GREEN/YELLOW,10M

Pack size: **10 x MTR**

- Sleeve Diameter: 10 mm
- Colour: Green, Yellow
- Material: PVC
- Sleeve Length: 10 m
- Braided: No
- Minimum Cable Diameter: 10 mm
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +85 °C



404528 10 mm

CABLE,SLEEVE,EXPANDABLE,BRAIDED ,FLEXIBLE,GREY,DIA.

Pack size: **5 x MTR**

- Sleeve Diameter: 30 mm
- Colour: Grey
- Material: PET
- Sleeve Length: 5 m
- Braided: Yes
- Expandable: Yes
- Minimum Cable Diameter: 25 mm
- Maximum Cable Diameter: 45 mm



408192 30 mm

CABLE,SLEEVE,EXPANDABLE,BRAIDED ,FLEXIBLE,BLACK,DIA

Pack size: **5 x MTR**

- Sleeve Diameter: 5 mm
- Colour: Black
- Material: PET
- Sleeve Length: 5 m
- Braided: Yes
- Expandable: Yes
- Minimum Cable Diameter: 3 mm
- Maximum Cable Diameter: 10 mm



408198 5 mm

CABLE,SLEEVE,EXPANDABLE,BRAIDED ,FLEXIBLE,BLACK,DIA

Pack size: **5 x MTR**

- Sleeve Diameter: 15 mm
- Colour: Black
- Material: PET
- Sleeve Length: 5 m
- Braided: Yes
- Expandable: Yes
- Minimum Cable Diameter: 10 mm
- Maximum Cable Diameter: 25 mm



408205 15 mm

CABLE,SLEEVE,EXPANDABLE,BRAIDED ,FLEXIBLE,BLACK,DIA

Pack size: **5 x MTR**

- Sleeve Diameter: 10 mm
- Colour: Black
- Material: PET
- Sleeve Length: 5 m
- Braided: Yes
- Expandable: Yes
- Minimum Cable Diameter: 6 mm
- Maximum Cable Diameter: 18 mm



408209 10 mm

CABLE,SLEEVE,EXPANDABLE,BRAIDED ,FLEXIBLE,BLACK,DIA

Pack size: **5 x MTR**

- Sleeve Diameter: 30 mm
- Colour: Black
- Material: PET
- Sleeve Length: 5 m
- Braided: Yes
- Expandable: Yes
- Minimum Cable Diameter: 25 mm
- Maximum Cable Diameter: 45 mm



408211 30 mm

CABLE,SLEEVE,EXPANDABLE,BRAIDED ,FLEXIBLE,BLACK,DIA

Pack size: **5 x MTR**

- Sleeve Diameter: 20 mm
- Colour: Black
- Material: PET
- Sleeve Length: 5 m
- Braided: Yes
- Expandable: Yes
- Minimum Cable Diameter: 12 mm
- Maximum Cable Diameter: 30 mm



408215 20 mm

CABLE,SLEEVE,EXPANDABLE,BRAIDED ,FLEXIBLE,BLACK,DIA

Pack size: **5 x MTR**

- Sleeve Diameter: 40 mm
- Colour: Black
- Material: PET
- Sleeve Length: 5 m
- Braided: Yes
- Expandable: Yes
- Minimum Cable Diameter: 35 mm
- Maximum Cable Diameter: 60 mm



408221 40 mm

CABLE,SLEEVE,EXPANDABLE,BRAIDED ,FLEXIBLE,BLACK,DIA

Pack size: **5 x MTR**

- Sleeve Diameter: 50 mm
- Colour: Black
- Material: PET
- Sleeve Length: 5 m
- Braided: Yes
- Expandable: Yes
- Minimum Cable Diameter: 45 mm
- Maximum Cable Diameter: 73 mm



408227 50 mm

CABLE,SLEEVE,EXPANDABLE,BRAIDED ,FLEXIBLE,GREY,DIA.

Pack size: **5 x MTR**

- Sleeve Diameter: 20 mm
- Colour: Grey
- Material: PET
- Sleeve Length: 5 m
- Braided: Yes
- Expandable: Yes
- Minimum Cable Diameter: 12 mm
- Maximum Cable Diameter: 30 mm



408233 20 mm

CABLE,SLEEVE,EXPANDABLE,BRAIDED ,FLEXIBLE,GREY,DIA.

Pack size: **5 x MTR**

- Sleeve Diameter: 10 mm
- Colour: Grey
- Material: PET
- Sleeve Length: 5 m
- Braided: Yes
- Expandable: Yes
- Minimum Cable Diameter: 6 mm
- Maximum Cable Diameter: 18 mm



408237 10 mm

CABLE,SLEEVE,EXPANDABLE,BRAIDED ,FLEXIBLE,GREY,DIA.

Pack size: **5 x MTR**

- Sleeve Diameter: 5 mm
- Colour: Grey
- Material: PET
- Sleeve Length: 5 m
- Braided: Yes
- Expandable: Yes
- Minimum Cable Diameter: 3 mm
- Maximum Cable Diameter: 10 mm



408243 5 mm

RS PRO EXPANDABLE BRAIDED PET GREY CABLE SLEEVE, 15MM

Pack size: **5 x MTR**

- Sleeve Diameter: 15 mm
- Colour: Grey
- Material: PET
- Sleeve Length: 5 m
- Braided: Yes
- Expandable: Yes
- Minimum Cable Diameter: 10 mm
- Maximum Cable Diameter: 25 mm



408249 15 mm

RS PRO EXPANDABLE BRAIDED PET GREY CABLE SLEEVE, 50MM

Pack size: **5 x MTR**

- Sleeve Diameter: 50 mm
- Colour: Grey
- Material: PET
- Sleeve Length: 5 m
- Braided: Yes
- Expandable: Yes
- Minimum Cable Diameter: 45 mm
- Maximum Cable Diameter: 73 mm



408255 50 mm

RS PRO EXPANDABLE BRAIDED PET GREY CABLE SLEEVE, 40MM

Pack size: **5 x MTR**

- Sleeve Diameter: 40 mm
- Colour: Grey
- Material: PET
- Sleeve Length: 5 m
- Braided: Yes
- Expandable: Yes
- Minimum Cable Diameter: 35 mm
- Maximum Cable Diameter: 60 mm



408259 40 mm

CABLE,SLEEVING,BRAIDED,EXPANDABLE,POLYESTER,25MM,1

Pack size: **10 x MTR**

- Sleeve Diameter: 25 mm
- Colour: Black
- Material: PET
- Sleeve Length: 10 m
- Braided: Yes
- Expandable: Yes
- Minimum Cable Diameter: 10 mm
- Maximum Cable Diameter: 30 mm



408271 25 mm

CABLE,SLEEVING,BRAIDED,EXPANDABLE,POLYESTER,15MM,1

Pack size: **10 x MTR**

- Sleeve Diameter: 10 mm
- Colour: Black
- Material: PET
- Sleeve Length: 10 m
- Braided: Yes
- Expandable: Yes
- Minimum Cable Diameter: 5 mm
- Maximum Cable Diameter: 21 mm



408277 10 mm

CABLE, SLEEVING, BRAIDED, EXPANDABLE, POLYESTER, 12MM, 3

Pack size: **30 x MTR**

- Sleeve Diameter: 12 mm
- Colour: Black
- Material: PET
- Sleeve Length: 30 m
- Braided: Yes
- Expandable: Yes
- Minimum Cable Diameter: 6.35 mm
- Maximum Cable Diameter: 19 mm



408283 12 mm

CABLE, SLEEVING, BRAIDED, EXPANDABLE, POLYESTER, 40MM, 1

Pack size: **10 x MTR**

- Sleeve Diameter: 40 mm
- Colour: Black
- Material: PET
- Sleeve Length: 10 m
- Braided: Yes
- Expandable: Yes
- Minimum Cable Diameter: 18 mm
- Maximum Cable Diameter: 54 mm



408287 40 mm

CABLE, SLEEVING, BRAIDED, EXPANDABLE, POLYESTER, 3MM, 30

Pack size: **30 x MTR**

- Sleeve Diameter: 3 mm
- Colour: Black
- Material: PET
- Sleeve Length: 30 m
- Braided: Yes
- Expandable: Yes
- Minimum Cable Diameter: 2.36 mm
- Maximum Cable Diameter: 6.35 mm



408293 3 mm

CABLE, SLEEVING, BRAIDED, EXPANDABLE, POLYESTER, 19MM, 3

Pack size: **30 x MTR**

- Sleeve Diameter: 19 mm
- Colour: Black
- Material: PET
- Sleeve Length: 30 m
- Braided: Yes
- Expandable: Yes
- Minimum Cable Diameter: 12.7 mm
- Maximum Cable Diameter: 31.7 mm



408299 19 mm

RS PRO PTFE CLEAR CABLE SLEEVE, 1.91MM DIAMETER

Pack size: **5 x MTR**

- Sleeve Diameter: 1.91 mm
- Colour: Clear
- Material: PTFE
- Braided: No
- Minimum Operating Temperature: -65 °C
- Maximum Operating Temperature: +260 °C
- Fire Behaviour: Flame Retardant
- Dielectric Strength: 45 kV/mm



1789504 1.91 mm

CLEAR PTFE 5M SLEEVE, 1.27MM BORE

Pack size: **5 x MTR**

- Sleeve Diameter: 1.27 mm
- Colour: Clear
- Material: PTFE
- Braided: No
- Minimum Operating Temperature: -65 °C
- Maximum Operating Temperature: +260 °C
- Fire Behaviour: Flame Retardant
- Dielectric Strength: 45 kV/mm



1789505 1.27 mm

CLEAR PTFE 5M SLEEVE, 3.05MM BORE

Pack size: **5 x MTR**

- Sleeve Diameter: 3.05 mm
- Colour: Clear
- Material: PTFE
- Braided: No
- Minimum Operating Temperature: -65 °C
- Maximum Operating Temperature: +260 °C
- Fire Behaviour: Flame Retardant
- Dielectric Strength: 45 kV/mm



1789506 3.05 mm

RS PRO PTFE CLEAR CABLE SLEEVE, 1.01MM DIAMETER

Pack size: **5 x MTR**

- Sleeve Diameter: 1.01 mm
- Colour: Clear
- Material: PTFE
- Braided: No
- Minimum Operating Temperature: -65 °C
- Maximum Operating Temperature: +260 °C
- Fire Behaviour: Flame Retardant
- Dielectric Strength: 45 kV/mm



1789507 1.01 mm

CLEAR PTFE 5M SLEEVE, 0.71MM BORE

Pack size: **5 x MTR**

- Sleeve Diameter: 0.71 mm
- Colour: Clear
- Material: PTFE
- Sleeve Length: 5 m
- Braided: No
- Minimum Operating Temperature: -65 °C
- Maximum Operating Temperature: +260 °C
- Fire Behaviour: Flame Retardant



1789508 0.71 mm

RS PRO PTFE CLEAR CABLE SLEEVE, 0.89MM DIAMETER

Pack size: **5 x MTR**

- Sleeve Diameter: 0.89 mm
- Colour: Clear
- Material: PTFE
- Braided: No
- Minimum Operating Temperature: -65 °C
- Maximum Operating Temperature: +260 °C
- Fire Behaviour: Flame Retardant
- Dielectric Strength: 45 kV/mm



1789509 0.89 mm

BLACK EXPANDABLE BRAIDED SLEEVING 3-9MM

Pack size: **25 x MTR**

- Sleeve Diameter: 5 mm
- Colour: Black
- Material: PET
- Sleeve Length: 25 m
- Braided: Yes
- Expandable: Yes
- Minimum Cable Diameter: 3 mm
- Maximum Cable Diameter: 9 mm



1797007 5 mm

RS PRO EXPANDABLE BRAIDED PET GREY CABLE SLEEVE, 5MM DIAMETER,

Pack size: **25 x MTR**

- Sleeve Diameter: 5 mm
- Colour: Grey
- Material: PET
- Sleeve Length: 25 m
- Braided: Yes
- Expandable: Yes
- Minimum Cable Diameter: 3 mm
- Maximum Cable Diameter: 9 mm



1797008 5 mm

RS PRO EXPANDABLE BRAIDED PET BLACK CABLE SLEEVE, 6MM

Pack size: **25 x MTR**

- Sleeve Diameter: 6 mm
- Colour: Black
- Material: PET
- Sleeve Length: 25 m
- Braided: Yes
- Expandable: Yes
- Minimum Cable Diameter: 4 mm
- Maximum Cable Diameter: 11 mm



1797009 6 mm

RS PRO EXPANDABLE BRAIDED PET GREY CABLE SLEEVE, 6MM DIAMETER,

Pack size: **25 x MTR**

- Sleeve Diameter: 6 mm
- Colour: Grey
- Material: PET
- Sleeve Length: 25 m
- Braided: Yes
- Expandable: Yes
- Minimum Cable Diameter: 4 mm
- Maximum Cable Diameter: 11 mm



1797010 6 mm

BLACK EXPANDABLE BRAIDED SLEEVING 5-12MM

Pack size: **15 x MTR**

- Sleeve Diameter: 8 mm
- Colour: Black
- Material: PET
- Sleeve Length: 15 m
- Braided: Yes
- Expandable: Yes
- Minimum Cable Diameter: 5 mm
- Maximum Cable Diameter: 12 mm



1797011 8 mm

RS PRO EXPANDABLE BRAIDED PET GREY CABLE SLEEVE, 8MM DIAMETER,

Pack size: **15 x MTR**

- Sleeve Diameter: 8 mm
- Colour: Grey
- Material: PET
- Sleeve Length: 15 m
- Braided: Yes
- Expandable: Yes
- Minimum Cable Diameter: 5 mm
- Maximum Cable Diameter: 12 mm



1797012 8 mm

BLACK EXPANDABLE BRAIDED SLEEVING 7-15MM

Pack size: **15 x MTR**

- Sleeve Diameter: 10 mm
- Colour: Black
- Material: PET
- Sleeve Length: 15 m
- Braided: Yes
- Expandable: Yes
- Minimum Cable Diameter: 7 mm
- Maximum Cable Diameter: 15 mm



1797013 10 mm

GREY EXPANDABLE BRAIDED SLEEVING 7-15MM

Pack size: **15 x MTR**

- Sleeve Diameter: 10 mm
- Colour: Grey
- Material: PET
- Sleeve Length: 15 m
- Braided: Yes
- Expandable: Yes
- Minimum Cable Diameter: 7 mm
- Maximum Cable Diameter: 15 mm



1797014 10 mm

RS PRO EXPANDABLE BRAIDED PET BLACK CABLE SLEEVE, 12MM

Pack size: **15 x MTR**

- Sleeve Diameter: 12 mm
- Colour: Black
- Material: PET
- Sleeve Length: 15 m
- Braided: Yes
- Expandable: Yes
- Minimum Cable Diameter: 8 mm
- Maximum Cable Diameter: 17 mm



1797015 12 mm

RS PRO EXPANDABLE BRAIDED PET BLACK CABLE SLEEVE, 15MM

Pack size: **15 x MTR**

- Sleeve Diameter: 15 mm
- Colour: Black
- Material: PET
- Sleeve Length: 15 m
- Braided: Yes
- Expandable: Yes
- Minimum Cable Diameter: 10 mm
- Maximum Cable Diameter: 21 mm



1797017 15 mm

RS PRO EXPANDABLE BRAIDED PET BLACK CABLE SLEEVE, 20MM

Pack size: **10 x MTR**

- Sleeve Diameter: 20 mm
- Colour: Black
- Material: PET
- Sleeve Length: 10 m
- Braided: Yes
- Expandable: Yes
- Minimum Cable Diameter: 14 mm
- Maximum Cable Diameter: 27 mm



1797019 20 mm

RS PRO EXPANDABLE BRAIDED PET BLACK CABLE SLEEVE, 25MM

Pack size: **10 x MTR**

- Sleeve Diameter: 25 mm
- Colour: Black
- Material: PET
- Sleeve Length: 10 m
- Braided: Yes
- Expandable: Yes
- Minimum Cable Diameter: 18 mm
- Maximum Cable Diameter: 34 mm



1797021 25 mm

RS PRO EXPANDABLE BRAIDED PET GREY CABLE SLEEVE, 25MM

Pack size: **10 x MTR**

- Sleeve Diameter: 25 mm
- Colour: Grey
- Material: PET
- Sleeve Length: 10 m
- Braided: Yes
- Expandable: Yes
- Minimum Cable Diameter: 18 mm
- Maximum Cable Diameter: 34 mm



1797022 25 mm

BLACK EXPANDABLE BRAIDED SLEEVING 28-47MM

Pack size: **10 x MTR**

- Sleeve Diameter: 30 mm
- Colour: Black
- Material: PET
- Sleeve Length: 10 m
- Braided: Yes
- Expandable: Yes
- Minimum Cable Diameter: 28 mm
- Maximum Cable Diameter: 47 mm



1797023 30 mm

RS PRO EXPANDABLE BRAIDED PET GREY CABLE SLEEVE, 30MM

Pack size: **10 x MTR**

- Sleeve Diameter: 30 mm
- Colour: Grey
- Material: PET
- Sleeve Length: 10 m
- Braided: Yes
- Expandable: Yes
- Minimum Cable Diameter: 28 mm
- Maximum Cable Diameter: 47 mm



1797024 30 mm

METAL SCREENING BRAID

Pack size: **10 x MTR**

- Sleeve Diameter: 3 mm
- Material: Tin Plated Copper
- Sleeve Length: 10 m
- Braided: Yes
- Expandable: Yes
- Minimum Cable Diameter: 2.5 mm
- Maximum Cable Diameter: 5 mm
- Minimum Operating Temperature: -65 °C



1811979 3 mm

RS PRO EXPANDABLE BRAIDED TIN PLATED COPPER CABLE SLEEVE, 6MM

Pack size: **10 x MTR**

- Sleeve Diameter: 6 mm
- Material: Tin Plated Copper
- Sleeve Length: 10 m
- Braided: Yes
- Expandable: Yes
- Minimum Cable Diameter: 4.5 mm
- Maximum Cable Diameter: 9.5 mm
- Minimum Operating Temperature: -65 °C



1811982 6 mm

RS PRO EXPANDABLE BRAIDED TIN PLATED COPPER CABLE SLEEVE,

Pack size: **10 x MTR**

- Sleeve Diameter: 7.5 mm
- Material: Tin Plated Copper
- Sleeve Length: 10 m
- Braided: Yes
- Expandable: Yes
- Minimum Cable Diameter: 7 mm
- Maximum Cable Diameter: 14 mm
- Minimum Operating Temperature: -65 °C



1811983 7.5 mm

RS PRO EXPANDABLE BRAIDED TIN PLATED COPPER CABLE SLEEVE,

Pack size: **10 x MTR**

- Sleeve Diameter: 10 mm
- Material: Tin Plated Copper
- Sleeve Length: 10 m
- Braided: Yes
- Expandable: Yes
- Minimum Cable Diameter: 8 mm
- Maximum Cable Diameter: 22 mm
- Minimum Operating Temperature: -65 °C



1811984 10 mm

RS PRO EXPANDABLE BRAIDED NICKEL PLATED COPPER CABLE

Pack size: **10 x MTR**

- Sleeve Diameter: 4 mm
- Material: Nickel Plated Copper
- Sleeve Length: 10 m
- Braided: Yes
- Expandable: Yes
- Minimum Cable Diameter: 3.5 mm
- Maximum Cable Diameter: 7.5 mm
- Minimum Operating Temperature: -65 °C



1811988 4 mm

RS PRO EXPANDABLE BRAIDED NICKEL PLATED COPPER CABLE

Pack size: **10 x MTR**

- Sleeve Diameter: 6 mm
- Material: Nickel Plated Copper
- Sleeve Length: 10 m
- Braided: Yes
- Expandable: Yes
- Minimum Cable Diameter: 4.5 mm
- Maximum Cable Diameter: 9.5 mm
- Minimum Operating Temperature: -65 °C



1811989 6 mm

RS PRO EXPANDABLE BRAIDED NICKEL PLATED COPPER CABLE

Pack size: **10 x MTR**

- Sleeve Diameter: 7.5 mm
- Material: Nickel Plated Copper
- Sleeve Length: 10 m
- Braided: Yes
- Expandable: Yes
- Minimum Cable Diameter: 7 mm
- Maximum Cable Diameter: 14 mm
- Minimum Operating Temperature: -65 °C



1811990 7.5 mm

RS PRO EXPANDABLE BRAIDED NICKEL PLATED COPPER CABLE

Pack size: **10 x MTR**

- Sleeve Diameter: 10 mm
- Material: Nickel Plated Copper
- Sleeve Length: 10 m
- Braided: Yes
- Expandable: Yes
- Minimum Cable Diameter: 8 mm
- Maximum Cable Diameter: 22 mm
- Minimum Operating Temperature: -65 °C



1811991 10 mm

RS PRO EXPANDABLE BRAIDED NICKEL PLATED COPPER CABLE

Pack size: **10 x MTR**

- Sleeve Diameter: 12.5 mm
- Material: Nickel Plated Copper
- Sleeve Length: 10 m
- Braided: Yes
- Expandable: Yes
- Minimum Cable Diameter: 11 mm
- Maximum Cable Diameter: 24 mm
- Minimum Operating Temperature: -65 °C



1811992 12.5 mm

RS PRO EXPANDABLE BRAIDED TIN PLATED COPPER CABLE SLEEVE, 3MM

Pack size: **10 x MTR**

- Sleeve Diameter: 3 mm
- Material: Tin Plated Copper
- Sleeve Length: 10 m
- Braided: Yes
- Expandable: Yes
- Minimum Cable Diameter: 2.5 mm
- Maximum Cable Diameter: 5 mm
- Minimum Operating Temperature: -65 °C



1811994 3 mm

RS PRO EXPANDABLE BRAIDED TIN PLATED COPPER CABLE SLEEVE, 4MM

Pack size: **10 x MTR**

- Sleeve Diameter: 4 mm
- Material: Tin Plated Copper
- Sleeve Length: 10 m
- Braided: Yes
- Expandable: Yes
- Minimum Cable Diameter: 3.5 mm
- Maximum Cable Diameter: 7.5 mm
- Minimum Operating Temperature: -65 °C



1811995 4 mm

RS PRO EXPANDABLE BRAIDED TIN PLATED COPPER CABLE SLEEVE, 6MM

Pack size: **10 x MTR**

- Sleeve Diameter: 6 mm
- Material: Tin Plated Copper
- Sleeve Length: 10 m
- Braided: Yes
- Expandable: Yes
- Minimum Cable Diameter: 4.5 mm
- Maximum Cable Diameter: 9.5 mm
- Minimum Operating Temperature: -65 °C



1811997 6 mm

RS PRO EXPANDABLE BRAIDED TIN PLATED COPPER CABLE SLEEVE,

Pack size: **10 x MTR**

- Sleeve Diameter: 7.5 mm
- Material: Tin Plated Copper
- Sleeve Length: 10 m
- Braided: Yes
- Expandable: Yes
- Minimum Cable Diameter: 7 mm
- Maximum Cable Diameter: 14 mm
- Minimum Operating Temperature: -65 °C



1811998 7.5 mm

RS PRO EXPANDABLE BRAIDED TIN PLATED COPPER CABLE SLEEVE,

Pack size: **10 x MTR**

- Sleeve Diameter: 12.5 mm
- Material: Tin Plated Copper
- Sleeve Length: 10 m
- Braided: Yes
- Expandable: Yes
- Minimum Cable Diameter: 11 mm
- Maximum Cable Diameter: 24 mm
- Minimum Operating Temperature: -65 °C



1812000 12.5 mm

RS PRO EXPANDABLE BRAIDED TIN PLATED COPPER CABLE SLEEVE,

Pack size: **10 x MTR**

- Sleeve Diameter: 15 mm
- Material: Tin Plated Copper
- Sleeve Length: 10 m
- Braided: Yes
- Expandable: Yes
- Minimum Cable Diameter: 14.5 mm
- Maximum Cable Diameter: 30 mm
- Minimum Operating Temperature: -65 °C



1812001 15 mm

RS PRO EXPANDABLE BRAIDED TIN PLATED COPPER CABLE SLEEVE,

Pack size: **10 x MTR**

- Sleeve Diameter: 20 mm
- Material: Tin Plated Copper
- Sleeve Length: 10 m
- Braided: Yes
- Expandable: Yes
- Minimum Cable Diameter: 16 mm
- Maximum Cable Diameter: 38 mm
- Minimum Operating Temperature: -65 °C



1812002 20 mm

RS PRO EXPANDABLE BRAIDED TIN PLATED COPPER CABLE SLEEVE, 4MM

Pack size: **100 x MTR**

- Sleeve Diameter: 4 mm
- Material: Tin Plated Copper
- Sleeve Length: 100 m
- Braided: Yes
- Expandable: Yes
- Minimum Cable Diameter: 3.5 mm
- Maximum Cable Diameter: 7.5 mm
- Minimum Operating Temperature: -65 °C



1812004 4 mm

RS PRO EXPANDABLE BRAIDED TIN PLATED COPPER CABLE SLEEVE, 3MM

Pack size: **100 x MTR**

- Sleeve Diameter: 3 mm
- Material: Tin Plated Copper
- Sleeve Length: 100 m
- Braided: Yes
- Expandable: Yes
- Minimum Cable Diameter: 2.5 mm
- Maximum Cable Diameter: 5 mm
- Minimum Operating Temperature: -65 °C



1812019 3 mm

BLACK SILICONE RUBBER SLEEVE, 1MM BORE

Pack size: **15 x MTR**

- Sleeve Diameter: 1 mm
- Colour: Black
- Material: Silicone
- Sleeve Length: 15 m
- Braided: No
- Expandable: No
- Minimum Operating Temperature: -60 °C
- Maximum Operating Temperature: +180 °C



1874820 1 mm

BLACK SILICONE RUBBER SLEEVE, 2MM BORE

Pack size: **10 x MTR**

- Sleeve Diameter: 2 mm
- Colour: Black
- Material: Silicone
- Sleeve Length: 10 m
- Braided: No
- Expandable: No
- Minimum Operating Temperature: -60 °C
- Maximum Operating Temperature: +180 °C



1874821 2 mm

RS PRO PVC BLACK CABLE SLEEVE, 3 MM±0.25 DIAMETER, 30.48M LENGTH

Pack size: **30 x MTR**

- Sleeve Diameter: 3 mm±0.25
- Colour: Black
- Material: PVC
- Sleeve Length: 30.48 m
- Braided: No
- Expandable: No
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +105 °C



1893170 3 mm±0.25

RS PRO PVC BLACK CABLE SLEEVE

Pack size: **30 x MTR**

- Colour: Black
- Material: PVC
- Braided: No
- Expandable: No
- Fire Behaviour: Flame Retardant
- Dielectric Strength: 2500 V/m
- Standards Met: RoHS Compliant
- Wall Thickness: 0.47 mm



1893171 Black

RS PRO CABLE SLEEVE

Pack size: **30 x MTR**

- Wall Thickness: 0.47 mm



1893172 0.47 mm

RS PRO PVC BLACK CABLE SLEEVE

Pack size: **30 x MTR**

- Colour: Black
- Material: PVC
- Braided: No
- Expandable: No
- Fire Behaviour: Flame Retardant
- Dielectric Strength: 2500 V/m
- Standards Met: RoHS Compliant
- Wall Thickness: 0.47 mm



1893173 Black

RS PRO PVC BLACK CABLE SLEEVE, 30.48M LENGTH

Pack size: **30 x MTR**

- Colour: Black
- Material: PVC
- Sleeve Length: 30.48 m
- Braided: No
- Expandable: No
- Maximum Cable Diameter: 12.70 mm ±0.35
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +105 °C



1893179 Black

CABLE,SLEEVE,SILICON RUBBER,1.5MM,GREEN

Pack size: **15 x MTR**

- Sleeve Diameter: 1.5 mm
- Colour: Green
- Material: Silicone Rubber
- Sleeve Length: 15 m
- Braided: No
- Maximum Cable Diameter: 1.5 mm
- Minimum Operating Temperature: -60 °C
- Maximum Operating Temperature: +180 °C



2521739 1.5 mm

RS PRO EXPANDABLE BRAIDED SILICONE RUBBER GLASS BLACK

Pack size: **1 x EA**

- Sleeve Diameter: 12 mm
- Colour: Black
- Material: Silicone Rubber Glass
- Sleeve Length: 1 m
- Braided: Yes
- Expandable: Yes
- Minimum Cable Diameter: 12 mm
- Maximum Cable Diameter: 19.2 mm



6681232 12 mm

RS PRO PVC BLACK CABLE SLEEVE

Pack size: **30 x MTR**

- Colour: Black
- Material: PVC
- Braided: No
- Expandable: No
- Fire Behaviour: Flame Retardant
- Dielectric Strength: 2500 V/m
- Standards Met: RoHS Compliant
- Wall Thickness: 0.47 mm



1893174 Black

CABLE,SLEEVE,SILICON RUBBER,1.2MM,BLACK

Pack size: **15 x MTR**

- Sleeve Diameter: 1.2 mm
- Colour: Black
- Material: Silicone Rubber
- Sleeve Length: 15 m
- Braided: No
- Minimum Operating Temperature: -60 °C
- Maximum Operating Temperature: +180 °C
- Standards Met: RoHS Compliant



2521688 1.2 mm

CABLE,SLEEVE,SILICON RUBBER,1.5MM,RED

Pack size: **15 x MTR**

- Sleeve Diameter: 1.5 mm
- Colour: Red
- Material: Silicone Rubber
- Sleeve Length: 15 m
- Braided: No
- Maximum Cable Diameter: 1.5 mm
- Minimum Operating Temperature: -60 °C
- Maximum Operating Temperature: +180 °C



2521745 1.5 mm

RS PRO EXPANDABLE BRAIDED SILICONE RUBBER GLASS BLACK

Pack size: **1 x EA**

- Sleeve Diameter: 16 mm
- Colour: Black
- Material: Silicone Rubber Glass
- Sleeve Length: 1 m
- Braided: Yes
- Expandable: Yes
- Minimum Cable Diameter: 16 mm
- Maximum Cable Diameter: 25.6 mm



6681236 16 mm

RS PRO PVC BLACK CABLE SLEEVE

Pack size: **30 x MTR**

- Colour: Black
- Material: PVC
- Braided: No
- Expandable: No
- Fire Behaviour: Flame Retardant
- Dielectric Strength: 2500 V/m
- Standards Met: RoHS Compliant
- Wall Thickness: 0.47 mm



1893175 Black

RS PRO SILICONE RUBBER GREEN CABLE SLEEVE, 1.2MM DIAMETER, 15M

Pack size: **15 x MTR**

- Sleeve Diameter: 1.2 mm
- Colour: Green
- Material: Silicone Rubber
- Sleeve Length: 15 m
- Braided: No
- Minimum Operating Temperature: -60 °C
- Maximum Operating Temperature: +180 °C
- Standards Met: RoHS Compliant



2521694 1.2 mm

RS PRO EXPANDABLE BRAIDED SILICONE RUBBER GLASS BLACK

Pack size: **1 x EA**

- Sleeve Diameter: 2 mm
- Colour: Black
- Material: Silicone Rubber Glass
- Sleeve Length: 1 m
- Braided: Yes
- Expandable: Yes
- Minimum Cable Diameter: 2 mm
- Maximum Cable Diameter: 3.2 mm



6681223 2 mm

RS PRO EXPANDABLE BRAIDED SILICONE RUBBER GLASS BLACK

Pack size: **1 x EA**

- Sleeve Diameter: 8 mm
- Colour: Black
- Material: Silicone Rubber Glass
- Sleeve Length: 1 m
- Braided: Yes
- Expandable: Yes
- Minimum Cable Diameter: 8 mm
- Maximum Cable Diameter: 12.8 mm



6681239 8 mm

RS PRO PVC BLACK CABLE SLEEVE

Pack size: **30 x MTR**

- Colour: Black
- Material: PVC
- Braided: No
- Expandable: No
- Fire Behaviour: Flame Retardant
- Dielectric Strength: 2500 V/m
- Standards Met: RoHS Compliant
- Wall Thickness: 0.60 mm



1893176 Black

CABLE,SLEEVE,SILICON RUBBER,1.5MM,BLACK

Pack size: **15 x MTR**

- Sleeve Diameter: 1.5 mm
- Colour: Black
- Material: Silicone Rubber
- Sleeve Length: 15 m
- Braided: No
- Minimum Operating Temperature: -60 °C
- Maximum Operating Temperature: +180 °C
- Standards Met: RoHS Compliant



2521717 1.5 mm

CONFORM EXP SILICONE/GLASS SLEEVING 4MM

Pack size: **1 x EA**

- Sleeve Diameter: 4 mm
- Colour: Black
- Material: Silicone Rubber Glass
- Sleeve Length: 1 m
- Braided: Yes
- Expandable: Yes
- Minimum Cable Diameter: 4 mm
- Maximum Cable Diameter: 6.4 mm



6681226 4 mm

VSR10 HGH TEMP GLASS SLEEVING 10MM

Pack size: **5 x MTR**

- Sleeve Diameter: 10 mm
- Colour: Natural
- Material: Fibreglass
- Sleeve Length: 5 m
- Braided: Yes
- Expandable: No
- Minimum Cable Diameter: 10 mm
- Minimum Operating Temperature: -40 °C



6681242 10 mm

VSR10 HGH TEMP GLASS SLEEVING 6MM

Pack size: **5 x MTR**

- Sleeve Diameter: 6 mm
- Colour: Natural
- Material: Fibreglass
- Sleeve Length: 5 m
- Braided: Yes
- Expandable: No
- Minimum Cable Diameter: 6 mm
- Minimum Operating Temperature: -40 °C



6681245 6 mm

VSR10 HGH TEMP GLASS SLEEVING 8MM

Pack size: **5 x MTR**

- Sleeve Diameter: 8 mm
- Colour: Natural
- Material: Fibreglass
- Sleeve Length: 5 m
- Braided: Yes
- Expandable: No
- Minimum Cable Diameter: 8 mm
- Minimum Operating Temperature: -40 °C



6681248 8 mm

VSR10 HGH TEMP GLASS SLEEVING 12MM

Pack size: **5 x MTR**

- Sleeve Diameter: 12 mm
- Colour: Natural
- Material: Fibreglass
- Sleeve Length: 5 m
- Braided: Yes
- Expandable: No
- Minimum Cable Diameter: 12 mm
- Minimum Operating Temperature: -40 °C



6681251 12 mm

VSR10 HGH TEMP GLASS SLEEVING 16MM

Pack size: **5 x MTR**

- Sleeve Diameter: 16 mm
- Colour: Natural
- Material: Fibreglass
- Sleeve Length: 5 m
- Braided: Yes
- Expandable: No
- Minimum Cable Diameter: 16 mm
- Minimum Operating Temperature: -40 °C



6681254 16 mm

VSR10 HGH TEMP GLASS SLEEVING 20MM

Pack size: **5 x MTR**

- Sleeve Diameter: 20 mm
- Colour: Natural
- Material: Fibreglass
- Sleeve Length: 5 m
- Braided: Yes
- Expandable: No
- Minimum Cable Diameter: 20 mm
- Minimum Operating Temperature: -40 °C



6681258 20 mm

PLAS 7 SELF CLOSING SLEEVE 4MM

Pack size: **3 x MTR**

- Sleeve Diameter: 4 mm
- Colour: Black
- Material: PET
- Sleeve Length: 3 m
- Braided: Yes
- Expandable: No
- Minimum Cable Diameter: 4 mm
- Maximum Cable Diameter: 8 mm



6681260 4 mm

PLAS 7 SELF CLOSING SLEEVE 7MM

Pack size: **3 x MTR**

- Sleeve Diameter: 7 mm
- Colour: Black
- Material: PET
- Sleeve Length: 3 m
- Braided: Yes
- Expandable: No
- Minimum Cable Diameter: 7 mm
- Maximum Cable Diameter: 12 mm



6681264 7 mm

VSR10 HGH TEMP GLASS SLEEVING 25MM

Pack size: **5 x MTR**

- Sleeve Diameter: 25 mm
- Colour: Natural
- Material: Fibreglass
- Sleeve Length: 5 m
- Braided: Yes
- Expandable: No
- Minimum Cable Diameter: 25 mm
- Minimum Operating Temperature: -40 °C



6681267 25 mm

PLAS 7 SELF CLOSING SLEEVE 20MM

Pack size: **3 x MTR**

- Sleeve Diameter: 20 mm
- Colour: Black
- Material: PET
- Sleeve Length: 3 m
- Braided: Yes
- Expandable: No
- Minimum Cable Diameter: 20 mm
- Maximum Cable Diameter: 28 mm



6681270 20 mm

PLAS 7 SELF CLOSING SLEEVE 10MM

Pack size: **3 x MTR**

- Sleeve Diameter: 10 mm
- Colour: Black
- Material: PET
- Sleeve Length: 3 m
- Braided: Yes
- Expandable: No
- Minimum Cable Diameter: 10 mm
- Maximum Cable Diameter: 15 mm



6681273 10 mm

PLAS 7 SELF CLOSING SLEEVE 14MM

Pack size: **3 x MTR**

- Sleeve Diameter: 14 mm
- Colour: Black
- Material: PET
- Sleeve Length: 3 m
- Braided: Yes
- Expandable: No
- Minimum Cable Diameter: 14 mm
- Maximum Cable Diameter: 21 mm



6681276 14 mm

PLAS 7 SELF CLOSING SLEEVE 32MM

Pack size: **3 x MTR**

- Sleeve Diameter: 32 mm
- Colour: Black
- Material: PET
- Sleeve Length: 3 m
- Braided: Yes
- Expandable: No
- Minimum Cable Diameter: 32 mm
- Maximum Cable Diameter: 44 mm



6681282 32 mm

RS PRO BRAIDED PET BLACK CABLE SLEEVE, 44MM DIAMETER, 3M LENGTH

Pack size: **3 x MTR**

- Sleeve Diameter: 44 mm
- Colour: Black
- Material: PET
- Sleeve Length: 3 m
- Braided: Yes
- Expandable: No
- Minimum Cable Diameter: 44 mm
- Minimum Operating Temperature: -50 °C



6681286 44 mm

RS PRO BRAIDED PET BLACK CABLE SLEEVE, 26MM DIAMETER, 3M LENGTH

Pack size: **3 x MTR**

- Sleeve Diameter: 26 mm
- Colour: Black
- Material: PET
- Sleeve Length: 3 m
- Braided: Yes
- Expandable: No
- Minimum Cable Diameter: 26 mm
- Maximum Cable Diameter: 34 mm



6681289 26 mm

VSR10 EXPANDABLE GLASS SLEEVING 10MM

Pack size: **5 x MTR**

- Sleeve Diameter: 10 mm
- Colour: Natural
- Material: Fibreglass
- Sleeve Length: 5 m
- Braided: Yes
- Expandable: Yes
- Minimum Cable Diameter: 10 mm
- Maximum Cable Diameter: 22 mm



6681295 10 mm

VSR10 EXPANDABLE GLASS SLEEVING 20MM

Pack size: **5 x MTR**

- Sleeve Diameter: 20 mm
- Colour: Natural
- Material: Fibreglass
- Sleeve Length: 5 m
- Braided: Yes
- Expandable: Yes
- Minimum Cable Diameter: 20 mm
- Maximum Cable Diameter: 55 mm



6681298 20 mm

CABLE SLEEVE TOOL INSTALLATION, FOR USE WITH KS, KL SERIES SPIRAL

Pack size: **1 x EA**

- Tool Type: Sleeve Installation
- For Use With: KS, KL Series Spiral Wraps
- Series: KT



2044433 Sleeve

CABLE SLEEVE TOOL INSTALLATION, FOR USE WITH KS, KL SERIES SPIRAL

Pack size: **1 x EA**

- Tool Type: Sleeve Installation
- For Use With: KS, KL Series Spiral Wraps
- Series: KT



2044438 Sleeve

CABLE,RETENTION,SPIRAL WRAP,POLYTHENE,DIA 13/80MM

Pack size: **3 x MTR**

- Minimum Cable Diameter: 9 mm
- Maximum Cable Diameter: 12 mm
- Colour: Natural
- Internal Diameter: 9 mm
- Material: Polyethylene
- Maximum Bundle Diameter: 32 mm
- Minimum Operating Temperature: -50 °C
- Maximum Operating Temperature: +50 °C



227980 9 mm

RS PRO SPIRAL WRAP, I.D 8MM 10MM POLYPROPYLENE

Pack size: **25 x MTR**

- Minimum Cable Diameter: 8 mm
- Maximum Cable Diameter: 10 mm
- Colour: Black
- Internal Diameter: 8 mm
- Material: Polypropylene
- Maximum Bundle Diameter: 10 mm
- Fire Behaviour: Halogen Free
- Wall Thickness: 0.8 mm



2044415 8 mm

CABLE SLEEVE TOOL INSTALLATION, FOR USE WITH KS, KL SERIES SPIRAL

Pack size: **1 x EA**

- Tool Type: Sleeve Installation
- For Use With: KS, KL Series Spiral Wraps
- Series: KT



2044435 Sleeve

CABLE SLEEVE TOOL HARNESS WRAP APPLICATOR TOOL

Pack size: **1 x EA**

- Tool Type: Harness Wrap Applicator Tool



6877679 Harness Wrap

RS PRO SPIRAL WRAP, I.D 32MM 35MM POLYPROPYLENE

Pack size: **25 x MTR**

- Minimum Cable Diameter: 35 mm
- Maximum Cable Diameter: 35 mm
- Colour: Black
- Internal Diameter: 32 mm
- Material: Polypropylene
- Maximum Bundle Diameter: 35 mm
- Fire Behaviour: Halogen Free
- Wall Thickness: 1.3 mm



2044414 35 mm

RS PRO SPIRAL WRAP, I.D 15MM 16MM POLYPROPYLENE

Pack size: **25 x MTR**

- Minimum Cable Diameter: 15 mm
- Maximum Cable Diameter: 16 mm
- Colour: Black
- Internal Diameter: 15 mm
- Material: Polypropylene
- Maximum Bundle Diameter: 16 mm
- Fire Behaviour: Halogen Free
- Wall Thickness: 0.8 mm



2044418 15 mm

CABLE SLEEVE TOOL INSTALLATION, FOR USE WITH KS, KL SERIES SPIRAL

Pack size: **1 x EA**

- Tool Type: Sleeve Installation
- For Use With: KS, KL Series Spiral Wraps
- Series: KT



2044436 Sleeve

CABLE,RETENTION,SPIRAL WRAP,POLYTHENE,DIA 3.2/12.7MM

Pack size: **5 x MTR**

- Minimum Cable Diameter: 1.5 mm
- Maximum Cable Diameter: 3 mm
- Colour: Natural
- Internal Diameter: 1.5 mm
- Material: Polyethylene
- Maximum Bundle Diameter: 10 mm
- Minimum Operating Temperature: -50 °C
- Maximum Operating Temperature: +50 °C



227968 1.5 mm

RS PRO SPIRAL WRAP, I.D 12MM POLYETHYLENE

Pack size: **5 x MTR**

- Minimum Cable Diameter: 12 mm
- Maximum Cable Diameter: 32 mm
- Colour: Natural
- Internal Diameter: 12 mm
- Material: Polyethylene
- Fire Behaviour: Halogen Free
- Wall Thickness: 0.85 mm
- Length: 5 m



2044416 12 mm

RS PRO SPIRAL WRAP, I.D 15MM 16MM POLYPROPYLENE

Pack size: **2 x MTR**

- Minimum Cable Diameter: 15 mm
- Maximum Cable Diameter: 16 mm
- Colour: Grey
- Internal Diameter: 15 mm
- Material: Polypropylene
- Maximum Bundle Diameter: 16 mm
- Fire Behaviour: Halogen Free
- Wall Thickness: 0.8 mm



2044419 15 mm

CABLE SLEEVE TOOL INSTALLATION, FOR USE WITH KS, KL SERIES SPIRAL

Pack size: **1 x EA**

- Tool Type: Sleeve Installation
- For Use With: KS, KL Series Spiral Wraps
- Series: KT



2044437 Sleeve

CABLE,RETENTION,SPIRAL WRAP,POLYTHENE,DIA 6.4/50MM

Pack size: **5 x MTR**

- Minimum Cable Diameter: 4 mm
- Maximum Cable Diameter: 6 mm
- Colour: Natural
- Internal Diameter: 4 mm
- Material: Polyethylene
- Maximum Bundle Diameter: 25 mm
- Minimum Operating Temperature: -50 °C
- Maximum Operating Temperature: +50 °C



227974 4 mm

RS PRO SPIRAL WRAP, I.D 19MM POLYETHYLENE

Pack size: **30 x MTR**

- Minimum Cable Diameter: 19 mm
- Maximum Cable Diameter: 50 mm
- Colour: Natural
- Internal Diameter: 19 mm
- Material: Polyethylene
- Fire Behaviour: Halogen Free
- Wall Thickness: 1.2 mm
- Length: 30.5 m



2044417 19 mm

RS PRO SPIRAL WRAP, I.D 20MM 22MM POLYPROPYLENE

Pack size: **25 x MTR**

- Minimum Cable Diameter: 20 mm
- Maximum Cable Diameter: 22 mm
- Colour: Black
- Internal Diameter: 20 mm
- Material: Polypropylene
- Maximum Bundle Diameter: 22 mm
- Fire Behaviour: Halogen Free
- Wall Thickness: 0.9 mm



2044420 20 mm

RS PRO SPIRAL WRAP, I.D 25MM 27MM POLYPROPYLENE

Pack size: **25 x MTR**

- Minimum Cable Diameter: 25 mm
- Maximum Cable Diameter: 27 mm
- Colour: Black
- Internal Diameter: 25 mm
- Material: Polypropylene
- Maximum Bundle Diameter: 27 mm
- Fire Behaviour: Halogen Free
- Wall Thickness: 1.3 mm



2044422 25 mm

RS PRO SPIRAL WRAP, I.D 25MM 27MM POLYPROPYLENE

Pack size: **2 x MTR**

- Minimum Cable Diameter: 25 mm
- Maximum Cable Diameter: 27 mm
- Colour: Grey
- Internal Diameter: 25 mm
- Material: Polypropylene
- Maximum Bundle Diameter: 27 mm
- Fire Behaviour: Halogen Free
- Wall Thickness: 1.3 mm



2044423 25 mm

RS PRO SPIRAL WRAP, I.D 25MM 27MM POLYPROPYLENE

Pack size: **2 x MTR**

- Minimum Cable Diameter: 25 mm
- Maximum Cable Diameter: 27 mm
- Colour: Black
- Internal Diameter: 25 mm
- Material: Polypropylene
- Maximum Bundle Diameter: 27 mm
- Fire Behaviour: Halogen Free
- Wall Thickness: 1.3 mm



2044421 25 mm

RS PRO SPIRAL WRAP, I.D 6MM POLYETHYLENE

Pack size: **30 x MTR**

- Minimum Cable Diameter: 6 mm
- Maximum Cable Diameter: 25 mm
- Colour: Natural
- Internal Diameter: 6 mm
- Material: Polyethylene
- Fire Behaviour: Halogen Free
- Wall Thickness: 0.6 mm
- Length: 30.5 m



2044424 6 mm

RS PRO SPIRAL WRAP, I.D 19MM POLYETHYLENE

Pack size: **30 x MTR**

- Minimum Cable Diameter: 19 mm
- Maximum Cable Diameter: 50 mm
- Colour: Black
- Internal Diameter: 19 mm
- Material: Polyethylene
- Fire Behaviour: Halogen Free
- Wall Thickness: 1.2 mm
- Length: 30.5 m



2044425 19 mm

RS PRO SPIRAL WRAP, I.D 6MM POLYETHYLENE

Pack size: **30 x MTR**

- Minimum Cable Diameter: 6 mm
- Maximum Cable Diameter: 25 mm
- Colour: Black
- Internal Diameter: 6 mm
- Material: Polyethylene
- Fire Behaviour: Halogen Free
- Wall Thickness: 0.6 mm
- Length: 30.5 m



2044426 6 mm

RS PRO SPIRAL WRAP, I.D 12MM POLYETHYLENE

Pack size: **5 x MTR**

- Minimum Cable Diameter: 12 mm
- Maximum Cable Diameter: 32 mm
- Colour: Black
- Internal Diameter: 12 mm
- Material: Polyethylene
- Fire Behaviour: Halogen Free
- Wall Thickness: 0.85 mm
- Length: 5 m



2044427 12 mm

RS PRO SPIRAL WRAP, I.D 12MM POLYETHYLENE

Pack size: **5 x MTR**

- Minimum Cable Diameter: 12 mm
- Maximum Cable Diameter: 32 mm
- Colour: Grey
- Internal Diameter: 12 mm
- Material: Polyethylene
- Fire Behaviour: Halogen Free
- Wall Thickness: 0.85 mm
- Length: 5 m



2044429 12 mm

RS PRO SPIRAL WRAP, I.D 6MM POLYETHYLENE

Pack size: **5 x MTR**

- Minimum Cable Diameter: 6 mm
- Maximum Cable Diameter: 25 mm
- Colour: Grey
- Internal Diameter: 6 mm
- Material: Polyethylene
- Fire Behaviour: Halogen Free
- Wall Thickness: 0.85 mm
- Length: 5 m



2044430 6 mm

RS PRO SPIRAL WRAP, I.D 15MM 16MM POLYPROPYLENE

Pack size: **2 x MTR**

- Minimum Cable Diameter: 15 mm
- Maximum Cable Diameter: 16 mm
- Colour: Black
- Internal Diameter: 15 mm
- Material: Polypropylene
- Maximum Bundle Diameter: 16 mm
- Fire Behaviour: Halogen Free
- Wall Thickness: 0.8 mm



2044431 15 mm

RS PRO SPIRAL WRAP, I.D 6MM POLYETHYLENE

Pack size: **5 x MTR**

- Minimum Cable Diameter: 6 mm
- Colour: Natural
- Internal Diameter: 6 mm
- Material: Polyethylene
- Length: 30.5 m
- Series: KS



2044432 6 mm

RS PRO SPIRAL WRAP, I.D 8MM 10MM PA 6 NYLON

Pack size: **5 x MTR**

- Minimum Cable Diameter: 8 mm
- Maximum Cable Diameter: 10 mm
- Colour: Black
- Internal Diameter: 8 mm
- Material: PA 6
- Maximum Bundle Diameter: 10 mm
- Wall Thickness: 0.8 mm
- Length: 5 m



2108572 8 mm

RS PRO SPIRAL WRAP, I.D 13.4MM 16MM NYLON 6

Pack size: **5 x MTR**

- Minimum Cable Diameter: 15 mm
- Maximum Cable Diameter: 16 mm
- Colour: Black
- Internal Diameter: 13.4 mm
- Material: Nylon 6
- Maximum Bundle Diameter: 16 mm
- Wall Thickness: 0.8 mm
- Length: 5 m



2108588 15 mm

RS PRO SPIRAL WRAP, I.D 25MM 25MM PA 6 NYLON

Pack size: **5 x MTR**

- Maximum Cable Diameter: 25 mm
- Colour: Black
- Internal Diameter: 25 mm
- Material: PA 6
- Maximum Bundle Diameter: 25 mm
- Wall Thickness: 1 mm
- Length: 5 m



2108594 25 mm

RS PRO SPIRAL WRAP, I.D 15MM 16MM PP

Pack size: **25 x MTR**

- Minimum Cable Diameter: 15 mm
- Maximum Cable Diameter: 16 mm
- Colour: White
- Internal Diameter: 15 mm
- Material: PP
- Maximum Bundle Diameter: 16 mm
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: +70 °C



2144061 15 mm

RS PRO SPIRAL WRAP, I.D 25MM 27MM PP

Pack size: **25 x MTR**

- Minimum Cable Diameter: 25 mm
- Maximum Cable Diameter: 27 mm
- Colour: White
- Internal Diameter: 25 mm
- Material: PP
- Maximum Bundle Diameter: 27 mm
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: +70 °C



2144063 25 mm

RS PRO SPIRAL WRAP, I.D 9MM 32MM POLYETHYLENE

Pack size: **25 x MTR**

- Minimum Cable Diameter: 9 mm
- Maximum Cable Diameter: 32 mm
- Colour: Natural
- Internal Diameter: 9 mm
- Material: Polyethylene
- Maximum Bundle Diameter: 32 mm
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: 70 °C



2144065 9 mm

RS PRO SPIRAL WRAP, I.D 4MM 25MM POLYETHYLENE

Pack size: **25 x MTR**

- Minimum Cable Diameter: 4 mm
- Maximum Cable Diameter: 25 mm
- Colour: Natural
- Internal Diameter: 4 mm
- Material: Polyethylene
- Maximum Bundle Diameter: 25 mm
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: 70 °C



2144066 4 mm

RS PRO SPIRAL WRAP, I.D 9MM 32MM POLYETHYLENE

Pack size: **31 x MTR**

- Minimum Cable Diameter: 9 mm
- Maximum Cable Diameter: 32 mm
- Colour: Grey
- Internal Diameter: 9 mm
- Material: Polyethylene
- Maximum Bundle Diameter: 32 mm
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: 70 °C



2144068 9 mm

RS PRO SPIRAL WRAP, I.D 4MM 25MM POLYETHYLENE

Pack size: **31 x MTR**

- Minimum Cable Diameter: 4 mm
- Maximum Cable Diameter: 25 mm
- Colour: White
- Internal Diameter: 4 mm
- Material: Polyethylene
- Maximum Bundle Diameter: 25 mm
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: 70 °C



2144071 4 mm

RS PRO SPIRAL WRAP, I.D 20MM 23MM PA 6 NYLON

Pack size: **5 x MTR**

- Minimum Cable Diameter: 20 mm
- Maximum Cable Diameter: 23 mm
- Colour: Black
- Internal Diameter: 20 mm
- Material: PA 6
- Maximum Bundle Diameter: 23 mm
- Wall Thickness: 0.9 mm
- Length: 5 m



2884923 20 mm

RS PRO SPIRAL WRAP, I.D 9MM 32MM POLYETHYLENE

Pack size: **3 x MTR**

- Minimum Cable Diameter: 9 mm
- Maximum Cable Diameter: 12 mm
- Colour: Black
- Internal Diameter: 9 mm
- Material: Polyethylene
- Maximum Bundle Diameter: 32 mm
- Wall Thickness: 0.85 mm
- Length: 3 m



8117620 9 mm

PE SPIRAL WRAP 3MM BLACK 5M

Pack size: **5 x MTR**

- Minimum Cable Diameter: 1.5 mm
- Maximum Cable Diameter: 3 mm
- Colour: Black
- Internal Diameter: 1.5 mm
- Material: Polyethylene
- Maximum Bundle Diameter: 10 mm
- Minimum Operating Temperature: -50 °C
- Maximum Operating Temperature: +50 °C



8117632 1.5 mm

RS PRO SPIRAL WRAP, I.D 10.3MM 32MM POLYETHYLENE

Pack size: **30 x MTR**

- Minimum Cable Diameter: 9 mm
- Maximum Cable Diameter: 12 mm
- Colour: Natural
- Internal Diameter: 10.3 mm
- Material: Polyethylene
- Maximum Bundle Diameter: 32 mm
- Wall Thickness: 0.85 mm
- Length: 30.5 m



8117636 9 mm

PE SPIRAL WRAPPING, 6MM BLACK 5M

Pack size: **5 x MTR**

- Minimum Cable Diameter: 4 mm
- Maximum Cable Diameter: 6 mm
- Colour: Black
- Internal Diameter: 4 mm
- Material: Polyethylene
- Maximum Bundle Diameter: 25 mm
- Minimum Operating Temperature: -50 °C
- Maximum Operating Temperature: +50 °C



8117639 4 mm

PE SPIRAL WRAP 12MM BLACK 30.5M

Pack size: **30 x MTR**

- Minimum Cable Diameter: 9 mm
- Maximum Cable Diameter: 12 mm
- Colour: Black
- Internal Diameter: 10.3 mm
- Material: Polyethylene
- Maximum Bundle Diameter: 32 mm
- Wall Thickness: 0.85 mm
- Length: 30.5 m



8117642 9 mm

PE SPIRAL WRAP 6MM NATURAL 30.5M

Pack size: **30 x MTR**

- Minimum Cable Diameter: 4 mm
- Maximum Cable Diameter: 4.5 mm
- Colour: Natural
- Internal Diameter: 4 mm
- Material: Polyethylene
- Maximum Bundle Diameter: 15 mm
- Wall Thickness: 0.6 mm
- Length: 30.5 m



8117645 4 mm

PE SPIRAL WRAP 3MM NATURAL 30.5M

Pack size: **30 x MTR**

- Minimum Cable Diameter: 1.5 mm
- Maximum Cable Diameter: 3 mm
- Colour: Natural
- Internal Diameter: 1.5 mm
- Material: Polyethylene
- Maximum Bundle Diameter: 10 mm
- Minimum Operating Temperature: -50 °C
- Maximum Operating Temperature: +50 °C



8117648 1.5 mm

RS PRO SPIRAL WRAP, I.D 4MM 15MM POLYETHYLENE

Pack size: **30 x MTR**

- Minimum Cable Diameter: 4 mm
- Maximum Cable Diameter: 4.5 mm
- Colour: Black
- Internal Diameter: 4 mm
- Material: Polyethylene
- Maximum Bundle Diameter: 15 mm
- Wall Thickness: 0.6 mm
- Length: 30.5 m



8117651 4 mm

RS PRO SPIRAL WRAP, I.D 1.5MM 10MM POLYETHYLENE

Pack size: **30 x MTR**

- Minimum Cable Diameter: 1.5 mm
- Maximum Cable Diameter: 3 mm
- Colour: Black
- Internal Diameter: 1.5 mm
- Material: Polyethylene
- Maximum Bundle Diameter: 10 mm
- Minimum Operating Temperature: -50 °C
- Maximum Operating Temperature: +50 °C



8117654 1.5 mm

PE SPIRAL CABLE WRAP 8MM BLACK 3M

Pack size: **3 x MTR**

- Minimum Cable Diameter: 6 mm
- Maximum Cable Diameter: 8 mm
- Colour: Black
- Internal Diameter: 6 mm
- Material: Polyethylene
- Maximum Bundle Diameter: 30 mm
- Wall Thickness: 0.75 mm
- Length: 3 m



8117658 6 mm

PE SPIRAL CABLE WRAP 8MM BLACK 30.5M

Pack size: **30 x MTR**

- Minimum Cable Diameter: 6 mm
- Maximum Cable Diameter: 8 mm
- Colour: Black
- Internal Diameter: 6 mm
- Material: Polyethylene
- Maximum Bundle Diameter: 30 mm
- Wall Thickness: 0.75 mm
- Length: 30.5 m



8117660 6 mm

RS PRO SPIRAL WRAP, I.D 6MM 30MM POLYETHYLENE

Pack size: **30 x MTR**

- Minimum Cable Diameter: 6 mm
- Maximum Cable Diameter: 8 mm
- Colour: Natural
- Internal Diameter: 6 mm
- Material: Polyethylene
- Maximum Bundle Diameter: 30 mm
- Wall Thickness: 0.75 mm
- Length: 30 m



8117664 6 mm

PE SPIRAL CABLE WRAP 8 MM NATURAL 3M

Pack size: **3 x MTR**

- Minimum Cable Diameter: 6 mm
- Maximum Cable Diameter: 8 mm
- Colour: Natural
- Internal Diameter: 6 mm
- Material: Polyethylene
- Maximum Bundle Diameter: 30 mm
- Wall Thickness: 0.75 mm
- Length: 3 m



8117667 6 mm

PE SPIRAL WRAP 12MM BLACK 10M

Pack size: **10 x MTR**

- Minimum Cable Diameter: 9 mm
- Maximum Cable Diameter: 12 mm
- Colour: Black
- Internal Diameter: 9 mm
- Material: Polyethylene
- Maximum Bundle Diameter: 32 mm
- Wall Thickness: 0.85 mm
- Length: 10 m



8117670 9 mm

PE SPIRAL WRAP 6MM BLACK 10M

Pack size: **10 x MTR**

- Minimum Cable Diameter: 4 mm
- Maximum Cable Diameter: 6 mm
- Colour: Black
- Internal Diameter: 4 mm
- Material: Polyethylene
- Maximum Bundle Diameter: 15 mm
- Wall Thickness: 0.6 mm
- Length: 10 m



8117673 4 mm

PE SPIRAL WRAP 8MM BLACK 10M

Pack size: **10 x MTR**

- Minimum Cable Diameter: 6 mm
- Maximum Cable Diameter: 8 mm
- Colour: Black
- Internal Diameter: 6 mm
- Material: Polyethylene
- Maximum Bundle Diameter: 30 mm
- Wall Thickness: 0.75 mm
- Length: 10 m



8117676 6 mm

PE SPIRAL WRAP 6MM NATURAL 10M

Pack size: **10 x MTR**

- Minimum Cable Diameter: 4 mm
- Maximum Cable Diameter: 4.5 mm
- Colour: Natural
- Internal Diameter: 4 mm
- Material: Polyethylene
- Maximum Bundle Diameter: 15 mm
- Wall Thickness: 0.6 mm
- Length: 10 m



8117682 4 mm

PE SPIRAL WRAP 8MM NATURAL 10M

Pack size: **10 x MTR**

- Minimum Cable Diameter: 6 mm
- Maximum Cable Diameter: 8 mm
- Colour: Natural
- Internal Diameter: 6 mm
- Material: Polyethylene
- Maximum Bundle Diameter: 30 mm
- Wall Thickness: 0.75 mm
- Length: 10 m



8117686 6 mm

PE SPIRAL WRAP 15MM BLACK 10M

Pack size: **10 x MTR**

- Minimum Cable Diameter: 12 mm
- Maximum Cable Diameter: 15 mm
- Colour: Black
- Internal Diameter: 15 mm
- Material: Polyethylene
- Maximum Bundle Diameter: 35 mm
- Wall Thickness: 1 mm
- Length: 10 m



8117689 12 mm

RS PRO SPIRAL WRAP, I.D 4MM 25MM NYLON

Pack size: **10 x MTR**

- Minimum Cable Diameter: 4 mm
- Maximum Cable Diameter: 4.5 mm
- Colour: Black
- Internal Diameter: 4 mm
- Material: Nylon
- Maximum Bundle Diameter: 25 mm
- Wall Thickness: 0.45 mm
- Length: 10 m



8117692 4 mm

RS PRO SPIRAL WRAP, I.D 10.3MM 32MM POLYETHYLENE

Pack size: **10 x MTR**

- Minimum Cable Diameter: 9 mm
- Maximum Cable Diameter: 12 mm
- Colour: Natural
- Internal Diameter: 10.3 mm
- Material: Polyethylene
- Maximum Bundle Diameter: 32 mm
- Minimum Operating Temperature: -50 °C
- Maximum Operating Temperature: +50 °C



8117695 9 mm

RS PRO SPIRAL WRAP, I.D 12MM 35MM POLYETHYLENE

Pack size: **10 x MTR**

- Minimum Cable Diameter: 12 mm
- Maximum Cable Diameter: 15 mm
- Colour: Natural
- Internal Diameter: 12 mm
- Material: Polyethylene
- Maximum Bundle Diameter: 35 mm
- Wall Thickness: 1 mm
- Length: 10 m



8117698 12 mm

NYLON SPIRAL WRAP 8MM BLACK 10M

Pack size: **10 x MTR**

- Minimum Cable Diameter: 6 mm
- Maximum Cable Diameter: 8 mm
- Colour: Black
- Internal Diameter: 6 mm
- Material: Nylon
- Maximum Bundle Diameter: 30 mm
- Wall Thickness: 0.7 mm
- Length: 10 m



8117702 6 mm

NYLON SPIRAL WRAP 12MM BLACK 10M

Pack size: **10 x MTR**

- Minimum Cable Diameter: 9 mm
- Maximum Cable Diameter: 12 mm
- Colour: Black
- Internal Diameter: 10.6 mm
- Material: Nylon
- Maximum Bundle Diameter: 32 mm
- Wall Thickness: 0.7 mm
- Length: 10 m



8117705 9 mm

RS PRO SPIRAL WRAP, I.D 12MM 35MM NYLON

Pack size: **10 x MTR**

- Minimum Cable Diameter: 12 mm
- Maximum Cable Diameter: 15 mm
- Colour: Black
- Internal Diameter: 12 mm
- Material: Nylon
- Maximum Bundle Diameter: 35 mm
- Wall Thickness: 0.8 mm
- Length: 10 m



8117709 12 mm

NYLON SPIRAL WRAP 8MM NATURAL 10M

Pack size: **10 x MTR**

- Minimum Cable Diameter: 6 mm
- Maximum Cable Diameter: 8 mm
- Colour: Natural
- Internal Diameter: 6 mm
- Material: Nylon
- Maximum Bundle Diameter: 30 mm
- Wall Thickness: 0.7 mm
- Length: 10 m



8117711 6 mm

RS PRO SPIRAL WRAP, I.D 12MM 35MM POLYETHYLENE

Pack size: **10 x MTR**

- Minimum Cable Diameter: 12 mm
- Maximum Cable Diameter: 15 mm
- Colour: Natural
- Internal Diameter: 12 mm
- Material: Polyethylene
- Maximum Bundle Diameter: 35 mm
- Wall Thickness: 0.8 mm
- Length: 10 m



8117724 12 mm

NYLON SPIRAL WRAP 6MM NATURAL 10M

Pack size: **10 x MTR**

- Minimum Cable Diameter: 4 mm
- Maximum Cable Diameter: 4.5 mm
- Colour: Natural
- Internal Diameter: 4 mm
- Material: Nylon
- Maximum Bundle Diameter: 25 mm
- Wall Thickness: 0.45 mm
- Length: 10 m




8117718 4 mm

RS PRO CABLE DRUM ROLLER, 1 SHELF

Pack size: **1 x EA**

- Type: Cable Drum Roller
- Number of Shelves: 1
- Height: 128 mm
- Width: 558 mm
- Length: 565 mm
- Diameter: 120 mm → 1200 mm
- Material: Aluminium, Steel



666688 Cable Drum

RS PRO SPIRAL WRAP, I.D 10.6MM 32MM NYLON

Pack size: **10 x MTR**

- Minimum Cable Diameter: 9 mm
- Maximum Cable Diameter: 12 mm
- Colour: Natural
- Internal Diameter: 10.6 mm
- Material: Nylon
- Maximum Bundle Diameter: 32 mm
- Wall Thickness: 0.7 mm
- Length: 10 m



8117715 9 mm

RS PRO EMPTY CABLE REEL 30M

Pack size: **1 x EA**

- Type: Empty Cable Reel
- Maximum Cable Length Capacity: 30 m
- Cable Diameter Capacity: 12 mm
- Height: 367 mm
- Diameter: 310 mm
- Material: Rubber
- Series: VDG T



1245323 Empty Cable

RS PRO EMPTY CABLE REEL 55M

Pack size: **1 x EA**

- Type: Empty Cable Reel
- Maximum Cable Length Capacity: 55 m, 65 m, 215 m
- Cable Diameter Capacity: 6.5 mm, 12 mm, 14 mm
- Height: 40 mm
- Width: 120 mm
- Diameter: 380 mm
- Material: Steel



3793705 Empty Cable

RS PRO EMPTY CABLE REEL 20M

Pack size: **1 x EA**

- Type: Empty Cable Reel
- Maximum Cable Length Capacity: 20 m, 25 m, 60 m
- Cable Diameter Capacity: 6.5 mm, 12 mm, 14 mm
- Height: 30 mm
- Width: 100 mm
- Diameter: 240 mm
- Material: Plastic



3793727 Empty Cable

RS PRO EMPTY CABLE REEL 30M

Pack size: **1 x EA**

- Type: Empty Cable Reel
- Maximum Cable Length Capacity: 30 m, 33 m, 115 m
- Cable Diameter Capacity: 6.5 mm, 12 mm, 14 mm
- Height: 30 mm
- Width: 100 mm
- Diameter: 300 mm
- Material: Plastic



3793733 Empty Cable

RS PRO EMPTY CABLE REEL 90M

Pack size: **1 x EA**

- Type: Empty Cable Reel
- Maximum Cable Length Capacity: 90 m, 110 m, 350 m
- Cable Diameter Capacity: 6.5 mm, 12 mm, 14 mm
- Height: 40 mm
- Width: 120 mm
- Diameter: 460 mm
- Material: Steel



3793755 Empty Cable

PLIERS,CABLE TIE,MAX 5MM

Pack size: **1 x EA**

- Tool Type: Cable Tie Plier



549909 Cable Tie Plier

RS PRO CABLE TIE GUN, 2.2 → 4.8MM CAPACITY

Pack size: **1 x EA**

- Series: RS PRO
- Cable Tie Capacity: 2.2 → 4.8 mm
- Height Safe: No



2061753 RS PRO

TOOL,CABLE TIE,STAINLESS STEEL,CT3

Pack size: **1 x EA**

- Cable Tie Capacity: 0.3 → 12 mm
- Material: Steel



4931958 0.3 → 12 mm

CABLE TIE TOOL FOR 1.8 -4.8 MM

Pack size: **1 x EA**

- Cable Tie Capacity: 2.2 → 4.8 mm



8111732 2.2 → 4.8 mm

CABLE TIE TOOL FOR 2.5-10.0 MM

Pack size: **1 x EA**

- Cable Tie Capacity: 2.5 → 10 mm



8111735 2.5 → 10 mm

RS PRO SELF ADHESIVE CABLE TIE MOUNT 19.5 MM X 19.5MM, 4.6MM

Pack size: **50 x EA**

- Cable Tie Width Acceptance: 4.6 mm
- Length: 19.5 mm
- Width: 19.5 mm
- Fixing Hole Diameter: 3.2 mm
- Self Adhesive: Yes
- Material: Nylon 66
- Series: HC
- Minimum Operating Temperature: -28 °C



227996 4.6 mm

RS PRO SELF ADHESIVE NATURAL CABLE TIE MOUNT 29 MM X 29MM,

Pack size: **50 x EA**

- Colour: Natural
- Cable Tie Width Acceptance: 5 mm
- Length: 29 mm
- Width: 29 mm
- Fixing Hole Diameter: 5 mm
- Self Adhesive: Yes
- Material: Nylon 66
- Series: HC



229560 Natural

RS PRO BLACK CABLE TIE MOUNT 10 MM X 15MM, 4.8MM MAX. CABLE TIE

Pack size: **250 x EA**

- Colour: Black
- Cable Tie Width Acceptance: 4.8 mm
- Length: 15 mm
- Width: 10 mm
- Fixing Hole Diameter: 3.5 mm
- Self Adhesive: No
- Material: Nylon 66
- Series: HC



233663 Black

CABLE,TIE,CLAMP,NYLON,BLACK,M6

Pack size: **250 x EA**

- Colour: Black
- Cable Tie Width Acceptance: 8 mm
- Length: 23 mm
- Width: 16 mm
- Fixing Hole Diameter: 6.3 mm
- Material: Nylon 66
- Series: HC
- Minimum Operating Temperature: -45 °C



233685 Black

CABLE,TIE,CLAMP,NYLON,WHITE,M3

Pack size: **250 x EA**

- Colour: White
- Cable Tie Width Acceptance: 5 mm
- Length: 15 mm
- Width: 10 mm
- Fixing Hole Diameter: 3 mm
- Material: Nylon 66
- Series: SM
- Minimum Operating Temperature: -45 °C



666717 White

CABLE,TIE,CLAMP,NYLON,WHITE,M6

Pack size: **250 x EA**

- Colour: White
- Cable Tie Width Acceptance: 9 mm
- Length: 23 mm
- Width: 16 mm
- Fixing Hole Diameter: 6 mm
- Material: Nylon 66
- Series: SM
- Minimum Operating Temperature: -45 °C



666739 White

CABLE,TIE,BASE,NYLON,SELF ADHESIVE,12.7X12.7X2.5MM

Pack size: **50 x EA**

- Colour: Natural
- Cable Tie Width Acceptance: 2.5 mm
- Length: 13 mm
- Width: 13 mm
- Self Adhesive: Yes
- Material: Nylon 66
- Series: HC
- Minimum Operating Temperature: -28 °C



666751 Natural

RS PRO SELF ADHESIVE NATURAL CABLE TIE MOUNT 12.5 MM X 12.5MM,

Pack size: **100 x EA**

- Colour: Natural
- Cable Tie Width Acceptance: 3.2 mm
- Length: 12.5 mm
- Width: 12.5 mm
- Fixing Hole Diameter: 3.2 mm
- Self Adhesive: Yes
- Material: Nylon 66
- Minimum Operating Temperature: -40 °C



2040240 Natural

RS PRO SELF ADHESIVE BLACK CABLE TIE MOUNT 19.5 MM X 19.5MM, 4.6MM

Pack size: **100 x EA**

- Colour: Black
- Cable Tie Width Acceptance: 4.6 mm
- Length: 19.5 mm
- Width: 19.5 mm
- Fixing Hole Diameter: 3.9 mm
- Self Adhesive: Yes
- Material: Nylon 66
- Minimum Operating Temperature: -40 °C



2040241 Black

RS PRO SELF ADHESIVE BLACK CABLE TIE MOUNT 19.5 MM X 19.5MM, 4.6MM

Pack size: **10 x EA**

- Colour: Black
- Cable Tie Width Acceptance: 4.6 mm
- Length: 19.5 mm
- Width: 19.5 mm
- Fixing Hole Diameter: 3.9 mm
- Self Adhesive: Yes
- Material: Nylon 66
- Minimum Operating Temperature: -40 °C



2040242 Black

RS PRO SELF ADHESIVE NATURAL CABLE TIE MOUNT 19.5 MM X 19.5MM,

Pack size: **100 x EA**

- Colour: Natural
- Cable Tie Width Acceptance: 4.6 mm
- Length: 19.5 mm
- Width: 19.5 mm
- Fixing Hole Diameter: 3.9 mm
- Self Adhesive: Yes
- Material: Nylon 66
- Minimum Operating Temperature: -40 °C



2040243 Natural

RS PRO SELF ADHESIVE BLACK CABLE TIE MOUNT 28.6 MM X 28.6MM,

Pack size: **100 x EA**

- Colour: Black
- Cable Tie Width Acceptance: 5.5 mm
- Length: 28.6 mm
- Width: 28.6 mm
- Fixing Hole Diameter: 5.3 mm
- Self Adhesive: Yes
- Material: Nylon 66
- Minimum Operating Temperature: -40 °C



2040244 Black

RS PRO SELF ADHESIVE BLACK CABLE TIE MOUNT 28.6 MM X 28.6MM,

Pack size: **10 x EA**

- Colour: Black
- Cable Tie Width Acceptance: 5.5 mm
- Length: 28.6 mm
- Width: 28.6 mm
- Fixing Hole Diameter: 5.3 mm
- Self Adhesive: Yes
- Material: Nylon 66
- Minimum Operating Temperature: -40 °C



2040245 Black

RS PRO SELF ADHESIVE NATURAL CABLE TIE MOUNT 28.6 MM X

Pack size: **100 x EA**

- Colour: Natural
- Cable Tie Width Acceptance: 5.5 mm
- Length: 28.6 mm
- Width: 28.6 mm
- Fixing Hole Diameter: 5.3 mm
- Self Adhesive: Yes
- Material: Nylon 66
- Minimum Operating Temperature: -40 °C



2040247 Natural

RS PRO SELF ADHESIVE NATURAL CABLE TIE MOUNT 38.5 MM X

Pack size: **100 x EA**

- Colour: Natural
- Cable Tie Width Acceptance: 10.2 mm
- Length: 38.5 mm
- Width: 38.5 mm
- Fixing Hole Diameter: 7.6 mm
- Self Adhesive: Yes
- Material: Nylon 66
- Minimum Operating Temperature: -40 °C



2040248 Natural

RS PRO SELF ADHESIVE BLACK CABLE TIE MOUNT 12.5 MM X 12.5MM, 3.2MM

Pack size: **100 x EA**

- Colour: Black
- Cable Tie Width Acceptance: 3.2 mm
- Length: 12.5 mm
- Width: 12.5 mm
- Fixing Hole Diameter: 3.2 mm
- Self Adhesive: Yes
- Material: Nylon 66
- Minimum Operating Temperature: -40 °C



2040249 Black

RS PRO SELF ADHESIVE BLACK CABLE TIE MOUNT 38.5 MM X 38.5MM,

Pack size: **10 x EA**

- Colour: Black
- Cable Tie Width Acceptance: 10.2 mm
- Length: 38.5 mm
- Width: 38.5 mm
- Fixing Hole Diameter: 7.6 mm
- Self Adhesive: Yes
- Material: Nylon 66
- Minimum Operating Temperature: -40 °C



2040250 Black

RS PRO BLACK CABLE TIE MOUNT 14.9 MM X 40.2MM, 10MM MAX. CABLE TIE

Pack size: **100 x EA**

- Colour: Black
- Cable Tie Width Acceptance: 10 mm
- Length: 40.2 mm
- Width: 14.9 mm
- Fixing Hole Diameter: 8 mm
- Self Adhesive: No
- Material: Nylon 66
- Minimum Operating Temperature: -40 °C



2138519 Black

RS PRO NATURAL CABLE TIE MOUNT 9.5 MM X 19MM, 5MM MAX. CABLE TIE

Pack size: **100 x EA**

- Colour: Natural
- Cable Tie Width Acceptance: 5 mm
- Length: 19 mm
- Width: 9.5 mm
- Fixing Hole Diameter: 5.2 mm
- Self Adhesive: No
- Material: Nylon 66
- Minimum Operating Temperature: -40 °C



2138520 Natural

RS PRO NATURAL CABLE TIE MOUNT 9.5 MM X 19MM, 5MM MAX. CABLE TIE

Pack size: **100 x EA**

- Colour: Natural
- Cable Tie Width Acceptance: 5 mm
- Length: 19 mm
- Width: 9.5 mm
- Fixing Hole Diameter: 4.3 mm
- Self Adhesive: No
- Material: Nylon 66
- Minimum Operating Temperature: -40 °C



2138521 Natural

NATURAL CABLE TIE MOUNT 10 MM X 15MM, 5.1MM MAX. CABLE TIE WIDTH

Pack size: **500 x EA**

- Colour: Natural
- Cable Tie Width Acceptance: 5.1 mm
- Length: 15 mm
- Width: 10 mm
- Fixing Hole Diameter: 3.5 mm
- Self Adhesive: No
- Material: Nylon 66
- Minimum Operating Temperature: -40 °C



2138522 Natural

SELF ADHESIVE WHITE CABLE TIE MOUNT 28.6 MM X 28.6MM, 5.5MM

Pack size: **50 x EA**

- Colour: White
- Cable Tie Width Acceptance: 5.5 mm
- Length: 28.6 mm
- Width: 28.6 mm
- Fixing Hole Diameter: 5 mm
- Self Adhesive: Yes
- Material: Nylon 66
- Minimum Operating Temperature: -40 °C



2138523 White

SELF ADHESIVE BLACK CABLE TIE MOUNT 29.2 MM X 29.2MM, 5.5MM

Pack size: **100 x EA**

- Colour: Black
- Cable Tie Width Acceptance: 5.5 mm
- Length: 29.2 mm
- Width: 29.2 mm
- Fixing Hole Diameter: 5 mm
- Self Adhesive: Yes
- Material: Nylon 66
- Minimum Operating Temperature: -40 °C



2138524 Black

NATURAL CABLE TIE MOUNT 16 MM X 23MM, 9MM MAX. CABLE TIE WIDTH

Pack size: **500 x EA**

- Colour: Natural
- Cable Tie Width Acceptance: 9 mm
- Length: 23 mm
- Width: 16 mm
- Fixing Hole Diameter: 6.3 mm
- Self Adhesive: No
- Material: Nylon 66
- Minimum Operating Temperature: -40 °C



2138525 Natural

SELF ADHESIVE NATURAL CABLE TIE MOUNT 26.1 MM X 26.1MM, 8MM MAX.

Pack size: **100 x EA**

- Colour: Natural
- Cable Tie Width Acceptance: 8 mm
- Length: 26.1 mm
- Width: 26.1 mm
- Fixing Hole Diameter: 4.3 mm
- Self Adhesive: Yes
- Material: Nylon 66
- Minimum Operating Temperature: -40 °C



2138526 Natural

SELF ADHESIVE BLACK CABLE TIE MOUNT 26.1 MM X 26.1MM, 8MM MAX.

Pack size: **100 x EA**

- Colour: Black
- Cable Tie Width Acceptance: 8 mm
- Length: 26.1 mm
- Width: 26.1 mm
- Fixing Hole Diameter: 4.3 mm
- Self Adhesive: Yes
- Material: Nylon 66
- Minimum Operating Temperature: -40 °C



2138527 Black

BLACK CABLE TIE MOUNT 13.8 MM X 23MM, 9.5MM MAX. CABLE TIE WIDTH

Pack size: **100 x EA**

- Colour: Black
- Cable Tie Width Acceptance: 9.5 mm
- Length: 23 mm
- Width: 13.8 mm
- Fixing Hole Diameter: 5.3 mm
- Self Adhesive: No
- Material: Nylon 66
- Minimum Operating Temperature: -40 °C



2138528 Black

RS PRO SELF ADHESIVE BLACK CABLE TIE MOUNT 38.5 MM X 38.5MM,

Pack size: **50 x EA**

- Colour: Black
- Cable Tie Width Acceptance: 10.2 mm
- Length: 38.5 mm
- Width: 38.5 mm
- Fixing Hole Diameter: 5 mm
- Self Adhesive: Yes
- Material: Nylon 66
- Minimum Operating Temperature: -40 °C



2138529 Black

RS PRO BLACK CABLE TIE MOUNT 9.6 MM X 18.5MM, 8.1MM MAX. CABLE TIE

Pack size: **100 x EA**

- Colour: Black
- Cable Tie Width Acceptance: 8.1 mm
- Length: 18.5 mm
- Width: 9.6 mm
- Fixing Hole Diameter: 6.2 mm
- Self Adhesive: No
- Material: Nylon 66
- Minimum Operating Temperature: -40 °C



2138531 Black

RS PRO SELF ADHESIVE NATURAL CABLE TIE MOUNT 28 MM X 28MM,

Pack size: **100 x EA**

- Colour: Natural
- Cable Tie Width Acceptance: 5.3 mm
- Length: 28 mm
- Width: 28 mm
- Fixing Hole Diameter: 5.6 mm
- Self Adhesive: Yes
- Material: Nylon 66
- Minimum Operating Temperature: -40 °C



2138539 Natural

RS PRO SELF ADHESIVE NATURAL CABLE TIE MOUNT 16 MM X 23MM,

Pack size: **50 x EA**

- Colour: Natural
- Cable Tie Width Acceptance: 9 mm
- Length: 23 mm
- Width: 16 mm
- Fixing Hole Diameter: 5 mm
- Self Adhesive: Yes
- Material: Nylon 66
- Minimum Operating Temperature: -40 °C



2138540 Natural

RS PRO NATURAL CABLE TIE MOUNT 10 MM X 15MM, 5.1MM MAX. CABLE

Pack size: **100 x EA**

- Colour: Natural
- Cable Tie Width Acceptance: 5.1 mm
- Length: 15 mm
- Width: 10 mm
- Fixing Hole Diameter: 3.5 mm
- Self Adhesive: No
- Material: Nylon 66
- Minimum Operating Temperature: -40 °C



2163630 Natural

CABLE,TIE,BASE,NYLON,SELF ADHESIVE,38X38X10.2,WITH

Pack size: **50 x EA**

- Colour: Natural
- Cable Tie Width Acceptance: 10.2 mm
- Length: 38.5 mm
- Width: 38.5 mm
- Fixing Hole Diameter: 5 mm
- Self Adhesive: Yes
- Material: Nylon 66
- Series: HC



6292514 Natural

BLACK S/ADHESIVE C/TIE BASE, 38X38MM

Pack size: **100 x EA**

- Colour: Black
- Cable Tie Width Acceptance: 10.2 mm
- Length: 38 mm
- Width: 38 mm
- Fixing Hole Diameter: 5 mm
- Self Adhesive: Yes
- Material: Nylon 66
- Series: HC



7300335 Black

RS PRO SELF ADHESIVE NATURAL CABLE TIE MOUNT 19.5 MM X 19.5MM,

Pack size: **250 x EA**

- Colour: Natural
- Cable Tie Width Acceptance: 4.6 mm
- Length: 19.5 mm
- Width: 19.5 mm
- Fixing Hole Diameter: 3.2 mm
- Self Adhesive: Yes
- Material: Nylon 66
- Series: HC



8111713 Natural

CABLE TIE MOUNT 12.5X12.5 BLACK NYLON 66

Pack size: **50 x EA**

- Colour: Black
- Cable Tie Width Acceptance: 3.2 mm
- Length: 12.5 mm
- Width: 12.5 mm
- Fixing Hole Diameter: 3.2 mm
- Self Adhesive: Yes
- Material: Nylon 66
- Series: HC



8111723 Black

CABLE TIE MOUNT 19.5X19.5 BLACK NYLON 66

Pack size: **50 x EA**

- Colour: Black
- Cable Tie Width Acceptance: 4.6 mm
- Length: 19.5 mm
- Width: 19.5 mm
- Fixing Hole Diameter: 3.2 mm
- Self Adhesive: Yes
- Material: Nylon 66
- Series: HC



8111726 Black

CABLE TIE MOUNT 29.2X29.2 BLACK NYLON 66

Pack size: **50 x EA**

- Colour: Black
- Cable Tie Width Acceptance: 5.5 mm
- Length: 29.2 mm
- Width: 29.2 mm
- Fixing Hole Diameter: 5 mm
- Self Adhesive: Yes
- Material: Nylon 66
- Series: HC



8111729 Black

PUSH TIE MOUNT NYLON 94V-2 NATURAL 3.8MM

Pack size: **100 x EA**

- Colour: Natural
- Cable Tie Width Acceptance: 3.8 mm
- Length: 15 mm
- Width: 6.5 mm
- Fixing Hole Diameter: 4.8 mm
- Material: Nylon 66
- Series: PHC
- Quantity: 100



8659675 Natural

RS PRO NATURAL CABLE TIE MOUNT 16.1MM, 5MM MAX. CABLE TIE WIDTH

Pack size: **100 x EA**

- Colour: Natural
- Cable Tie Width Acceptance: 5 mm
- Length: 16.1 mm
- Width: 7 mm
- Fixing Hole Diameter: 6 mm
- Material: Nylon 66
- Series: PHC
- Quantity: 100



8659679 Natural

RS PRO NATURAL CABLE TIE MOUNT 12.1 MM X 17.6MM, 6.5MM MAX.

Pack size: **100 x EA**

- Colour: Natural
- Cable Tie Width Acceptance: 6.5 mm
- Length: 17.6 mm
- Width: 12.1 mm
- Fixing Hole Diameter: 9 x 8 mm
- Material: Nylon 66
- Series: PHC
- Quantity: 100



8659681 Natural

RS PRO NATURAL CABLE TIE MOUNT 16.1MM, 5MM MAX. CABLE TIE WIDTH

Pack size: **100 x EA**

- Colour: Natural
- Cable Tie Width Acceptance: 5 mm
- Length: 16.1 mm
- Width: 7 mm
- Fixing Hole Diameter: 6 mm
- Material: Nylon 66
- Series: PHC
- Quantity: 100



8659688 Natural

SELF ADH TIE MOUNT NYLON NATURAL 19X19MM

Pack size: **100 x EA**

- Colour: Natural
- Cable Tie Width Acceptance: 4.1 mm
- Length: 19 mm
- Width: 19 mm
- Fixing Hole Diameter: 4.4 mm
- Self Adhesive: Yes
- Material: Nylon 66
- Series: HC



8659701 Natural

SELF ADH TIE MOUNT NYLON NATURAL 26.5MM

Pack size: **100 x EA**

- Colour: Natural
- Cable Tie Width Acceptance: 5.6 mm
- Length: 26.3 mm
- Width: 26.3 mm
- Fixing Hole Diameter: 5 mm
- Self Adhesive: Yes
- Material: Nylon 66
- Series: HC



8659704 Natural

RS PRO NATURAL CABLE TIE MOUNT 13.8 MM X 23MM, 9.5MM MAX. CABLE

Pack size: **100 x EA**

- Colour: Natural
- Cable Tie Width Acceptance: 9.5 mm
- Length: 23 mm
- Width: 13.8 mm
- Fixing Hole Diameter: 5.3 mm
- Material: Nylon 66
- Series: HC
- Quantity: 100



8659708 Natural

RS PRO NATURAL CABLE TIE MOUNT 14.7 MM X 30MM, 9.3MM MAX. CABLE

Pack size: **100 x EA**

- Colour: Natural
- Cable Tie Width Acceptance: 9.3 mm
- Length: 30 mm
- Width: 14.7 mm
- Fixing Hole Diameter: 5 mm
- Material: Nylon 66
- Series: HC
- Quantity: 100



8659717 Natural

RS PRO CABLE TIE, LADDER, 225MM X 7 MM, METALLIC 316 STAINLESS STEEL,

Pack size: **100 x EA**

- Length: 225 mm
- Width: 7 mm
- Colour: Metallic
- Material: 316 Stainless Steel
- Type: Ladder
- Quantity: 100
- Minimum Operating Temperature: -80 °C
- Maximum Operating Temperature: +539 °C



121618 225 mm

RS PRO CABLE TIE, LADDER, 300MM X 7 MM, METALLIC 316 STAINLESS STEEL,

Pack size: **100 x EA**

- Length: 300 mm
- Width: 7 mm
- Colour: Metallic
- Material: 316 Stainless Steel
- Type: Ladder
- Quantity: 100
- Minimum Operating Temperature: -80 °C
- Maximum Operating Temperature: +539 °C



121624 300 mm

RS PRO CABLE TIE, LADDER, 610MM X 12 MM, METALLIC 316 STAINLESS

Pack size: **100 x EA**

- Length: 610 mm
- Width: 12 mm
- Colour: Metallic
- Material: 316 Stainless Steel
- Type: Ladder
- Quantity: 100
- Minimum Operating Temperature: -80 °C
- Maximum Operating Temperature: +539 °C




121646 610 mm

RS PRO CABLE TIE, LADDER, 225MM X 7 MM, BLACK POLYESTER COATED

Pack size: **100 x EA**

- Length: 225 mm
- Width: 7 mm
- Colour: Black
- Material: Polyester Coated Stainless Steel
- Type: Ladder
- Quantity: 100
- Minimum Operating Temperature: -80 °C
- Maximum Operating Temperature: +150 °C



121652 225 mm

RS PRO CABLE TIE, LADDER, 300MM X 7 MM, BLACK POLYESTER COATED

Pack size: **100 x EA**

- Length: 300 mm
- Width: 7 mm
- Colour: Black
- Material: Polyester Coated Stainless Steel
- Type: Ladder
- Quantity: 100
- Minimum Operating Temperature: -80 °C
- Maximum Operating Temperature: +150 °C




121668 300 mm

RS PRO CABLE TIE, LADDER, 610MM X 7 MM, BLACK POLYESTER COATED

Pack size: **100 x EA**

- Length: 610 mm
- Width: 7 mm
- Colour: Black
- Material: Polyester Coated Stainless Steel
- Type: Ladder
- Quantity: 100
- Minimum Operating Temperature: -80 °C
- Maximum Operating Temperature: +150 °C



121674 610 mm

RS PRO CABLE TIE, 150MM X 3.6 MM, NATURAL NYLON, PK-100

Pack size: **100 x EA**

- Length: 150 mm
- Width: 3.6 mm
- Colour: Natural
- Material: Nylon 66
- Type: Non-Releasable
- Quantity: 100
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



178478 150 mm

RS PRO CABLE TIE, 190MM X 4.8 MM, NATURAL NYLON, PK-100

Pack size: **100 x EA**

- Length: 190 mm
- Width: 4.8 mm
- Colour: Natural
- Material: Nylon 66
- Type: Non-Releasable
- Quantity: 100
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



178484 190 mm

RS PRO CABLE TIE, 292MM X 3.6 MM, NATURAL NYLON, PK-100

Pack size: **100 x EA**

- Length: 292 mm
- Width: 3.6 mm
- Colour: Natural
- Material: Nylon 66
- Type: Non-Releasable
- Quantity: 100
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



178490 292 mm

RS PRO CABLE TIE, 368MM X 4.8 MM, NATURAL NYLON, PK-100

Pack size: **100 x EA**

- Length: 368 mm
- Width: 4.8 mm
- Colour: Natural
- Material: Nylon 66
- Type: Non-Releasable
- Quantity: 100
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



178507 368 mm

RS PRO CABLE TIE, 380MM X 7.6 MM, NATURAL NYLON, PK-100

Pack size: **100 x EA**

- Length: 380 mm
- Width: 7.6 mm
- Colour: Natural
- Material: Nylon 66
- Type: Non-Releasable
- Quantity: 100
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



178513 380 mm

RS PRO CABLE TIE, 100MM X 2.5 MM, ASSORTED NYLON, PK-1000

Pack size: **1000 x EA**

- Length: 100 mm
- Width: 2.5 mm
- Colour: Assorted
- Material: Nylon 66
- Type: Non-Releasable
- Quantity: 1000
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



233118 100 mm

RS PRO CABLE TIE, 100MM X 2.5 MM, 4.6 MM, 4.8 MM, ASSORTED NYLON,

Pack size: **650 x EA**

- Length: 100 mm, 203 mm, 280 mm
- Width: 2.5 mm, 4.6 mm, 4.8 mm
- Colour: Assorted
- Material: Nylon 66
- Type: Non-Releasable
- Quantity: 650
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



233124 100 mm, 203 mm,

RS PRO CABLE TIE, 100MM X 2.5 MM, 4.6 MM, 4.8 MM, ASSORTED NYLON,

Pack size: **850 x EA**

- Length: 100 mm, 203 mm, 280 mm
- Width: 2.5 mm, 4.6 mm, 4.8 mm
- Colour: Assorted
- Material: Nylon 66
- Type: Non-Releasable
- Quantity: 850
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



233130 100 mm, 203 mm,

RS PRO CABLE TIE, 100MM X 2.5 MM, BLUE NYLON, PK-100

Pack size: **100 x EA**

- Length: 100 mm
- Width: 2.5 mm
- Colour: Blue
- Material: Nylon 66
- Type: Non-Releasable
- Quantity: 100
- Minimum Operating Temperature: -50 °C
- Maximum Operating Temperature: +85 °C



233203 100 mm

RS PRO CABLE TIE, 100MM X 2.5 MM, RED NYLON, PK-100

Pack size: **100 x EA**

- Length: 100 mm
- Width: 2.5 mm
- Colour: Red
- Material: Nylon 66
- Type: Non-Releasable
- Quantity: 100
- Minimum Operating Temperature: -50 °C
- Maximum Operating Temperature: +85 °C



233207 100 mm

RS PRO CABLE TIE, 100MM X 2.5 MM, GREEN NYLON, PK-100

Pack size: **100 x EA**

- Length: 100 mm
- Width: 2.5 mm
- Colour: Green
- Material: Nylon 66
- Type: Non-Releasable
- Quantity: 100
- Minimum Operating Temperature: -50 °C
- Maximum Operating Temperature: +85 °C



233225 100 mm

RS PRO CABLE TIE, 100MM X 2.5 MM, YELLOW NYLON, PK-100

Pack size: **100 x EA**

- Length: 100 mm
- Width: 2.5 mm
- Colour: Yellow
- Material: Nylon 66
- Type: Non-Releasable
- Quantity: 100
- Minimum Operating Temperature: -50 °C
- Maximum Operating Temperature: +85 °C



233229 100 mm

RS PRO CABLE TIE, 165MM X 2.5 MM, RED NYLON, PK-100

Pack size: **100 x EA**

- Length: 165 mm
- Width: 2.5 mm
- Colour: Red
- Material: Nylon 66
- Type: Non-Releasable
- Quantity: 100
- Minimum Operating Temperature: -50 °C
- Maximum Operating Temperature: +85 °C



233231 165 mm

RS PRO CABLE TIE, 100MM X 2.5 MM, ORANGE NYLON, PK-100

Pack size: **100 x EA**

- Length: 100 mm
- Width: 2.5 mm
- Colour: Orange
- Material: Nylon 66
- Type: Non-Releasable
- Quantity: 100
- Minimum Operating Temperature: -50 °C
- Maximum Operating Temperature: +85 °C



233235 100 mm

RS PRO CABLE TIE, 165MM X 2.5 MM, BLUE NYLON, PK-100

Pack size: **100 x EA**

- Length: 165 mm
- Width: 2.5 mm
- Colour: Blue
- Material: Nylon 66
- Type: Non-Releasable
- Quantity: 100
- Minimum Operating Temperature: -50 °C
- Maximum Operating Temperature: +85 °C



233241 165 mm

RS PRO CABLE TIE, 165MM X 2.5 MM, YELLOW NYLON, PK-100

Pack size: **100 x EA**

- Length: 165 mm
- Width: 2.5 mm
- Colour: Yellow
- Material: Nylon 66
- Type: Non-Releasable
- Quantity: 100
- Minimum Operating Temperature: -50 °C
- Maximum Operating Temperature: +85 °C



233269 165 mm

RS PRO CABLE TIE, 165MM X 2.5 MM, GREEN NYLON, PK-100

Pack size: **100 x EA**

- Length: 165 mm
- Width: 2.5 mm
- Colour: Green
- Material: Nylon 66
- Type: Non-Releasable
- Quantity: 100
- Minimum Operating Temperature: -50 °C
- Maximum Operating Temperature: +85 °C



233275 165 mm

RS PRO CABLE TIE, 165MM X 2.5 MM, ORANGE NYLON, PK-100

Pack size: **100 x EA**

- Length: 165 mm
- Width: 2.5 mm
- Colour: Orange
- Material: Nylon 66
- Type: Non-Releasable
- Quantity: 100
- Minimum Operating Temperature: -50 °C
- Maximum Operating Temperature: +85 °C



233281 165 mm

RS PRO CABLE TIE, 203MM X 2.5 MM, RED NYLON, PK-100

Pack size: **100 x EA**

- Length: 203 mm
- Width: 2.5 mm
- Colour: Red
- Material: Nylon 66
- Type: Non-Releasable
- Quantity: 100
- Minimum Operating Temperature: -50 °C
- Maximum Operating Temperature: +85 °C



233297 203 mm

RS PRO CABLE TIE, 203MM X 2.5 MM, BLUE NYLON, PK-100

Pack size: **100 x EA**

- Length: 203 mm
- Width: 2.5 mm
- Colour: Blue
- Material: Nylon 66
- Type: Non-Releasable
- Quantity: 100
- Minimum Operating Temperature: -50 °C
- Maximum Operating Temperature: +85 °C



233304 203 mm

RS PRO CABLE TIE, 203MM X 2.5 MM, YELLOW NYLON, PK-100

Pack size: **100 x EA**

- Length: 203 mm
- Width: 2.5 mm
- Colour: Yellow
- Material: Nylon 66
- Type: Non-Releasable
- Quantity: 100
- Minimum Operating Temperature: -50 °C
- Maximum Operating Temperature: +85 °C



233310 203 mm

RS PRO CABLE TIE, 203MM X 2.5 MM, GREEN NYLON, PK-100

Pack size: **100 x EA**

- Length: 203 mm
- Width: 2.5 mm
- Colour: Green
- Material: Nylon 66
- Type: Non-Releasable
- Quantity: 100
- Minimum Operating Temperature: -50 °C
- Maximum Operating Temperature: +85 °C



233354 203 mm

RS PRO CABLE TIE, 203MM X 2.5 MM, ORANGE NYLON, PK-100

Pack size: **100 x EA**

- Length: 203 mm
- Width: 2.5 mm
- Colour: Orange
- Material: Nylon 66
- Type: Non-Releasable
- Quantity: 100
- Minimum Operating Temperature: -50 °C
- Maximum Operating Temperature: +85 °C



233386 203 mm

RS PRO CABLE TIE, 100MM X 2.5 MM, BLACK NYLON, PK-100

Pack size: **100 x EA**

- Length: 100 mm
- Width: 2.5 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releasable
- Quantity: 100
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



233455 100 mm

RS PRO CABLE TIE, 150MM X 3.6 MM, BLACK NYLON, PK-100

Pack size: **100 x EA**

- Length: 150 mm
- Width: 3.6 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releasable
- Quantity: 100
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



233465 150 mm

RS PRO CABLE TIE, 190MM X 4.8 MM, BLACK NYLON, PK-100

Pack size: **100 x EA**

- Length: 190 mm
- Width: 4.8 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releasable
- Quantity: 100
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



233461 190 mm

RS PRO CABLE TIE, 292MM X 3.6 MM, BLACK NYLON, PK-100

Pack size: **100 x EA**

- Length: 292 mm
- Width: 3.6 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releasable
- Quantity: 100
- UV Resistant: Yes
- Minimum Operating Temperature: -40 °C



233477 292 mm

RS PRO CABLE TIE, 203MM X 4.6 MM, BLACK NYLON, PK-100

Pack size: **100 x EA**

- Length: 203 mm
- Width: 4.6 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releasable
- Quantity: 100
- UV Resistant: Yes
- Minimum Operating Temperature: -40 °C



233471 203 mm

RS PRO CABLE TIE, 368MM X 4.8 MM, BLACK NYLON, PK-100

Pack size: **100 x EA**

- Length: 368 mm
- Width: 4.8 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releasable
- Quantity: 100
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



233483 368 mm

RS PRO CABLE TIE, 300MM X 4.8 MM, BLACK NYLON, PK-100

Pack size: **100 x EA**

- Length: 300 mm
- Width: 4.8 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releasable
- Quantity: 100
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



233487 300 mm

RS PRO CABLE TIE, 380MM X 7.6 MM, BLACK NYLON, PK-100

Pack size: **100 x EA**

- Length: 380 mm
- Width: 7.6 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releasable
- Quantity: 100
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



233493 380 mm

RS PRO CABLE TIE, 150MM X 3.6 MM, BLACK NYLON, PK-1000

Pack size: **1000 x EA**

- Length: 150 mm
- Width: 3.6 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releasable
- Quantity: 1000
- UV Resistant: No
- Minimum Operating Temperature: -40 °C



233500 150 mm

RS PRO CABLE TIE, 100MM X 2.5 MM, BLACK NYLON, PK-1000

Pack size: **1000 x EA**

- Length: 100 mm
- Width: 2.5 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releasable
- Quantity: 1000
- UV Resistant: No
- Minimum Operating Temperature: -40 °C



233499 100 mm

RS PRO CABLE TIE, 190MM X 4.8 MM, BLACK NYLON, PK-1000

Pack size: **1000 x EA**

- Length: 190 mm
- Width: 4.8 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releasable
- Quantity: 1000
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



233506 190 mm

RS PRO CABLE TIE, 100MM X 2.5 MM, ASSORTED NYLON, PK-250

Pack size: **250 x EA**

- Length: 100 mm
- Width: 2.5 mm
- Colour: Assorted
- Material: Nylon 66
- Type: Non-Releasable
- Quantity: 250
- Minimum Operating Temperature: -50 °C
- Maximum Operating Temperature: +85 °C



233528 100 mm

RS PRO CABLE TIE, 203MM X 2.5 MM, ASSORTED NYLON, PK-250

Pack size: **250 x EA**

- Length: 203 mm
- Width: 2.5 mm
- Colour: Assorted
- Material: Nylon 66
- Type: Non-Releasable
- Quantity: 250
- Minimum Operating Temperature: -50 °C
- Maximum Operating Temperature: +85 °C



233540 203 mm

RS PRO CABLE TIE, 150MM X 3.6 MM, ASSORTED NYLON, PK-250

Pack size: **250 x EA**

- Length: 150 mm
- Width: 3.6 mm
- Colour: Assorted
- Material: Nylon 66
- Type: Non-Releasable
- Quantity: 250
- Minimum Operating Temperature: -50 °C
- Maximum Operating Temperature: +85 °C



233691 150 mm

RS PRO CABLE TIE, 165MM X 2.5 MM, ASSORTED NYLON, PK-250

Pack size: **250 x EA**

- Length: 165 mm
- Width: 2.5 mm
- Colour: Assorted
- Material: Nylon 66
- Type: Non-Releasable
- Quantity: 250
- Minimum Operating Temperature: -50 °C
- Maximum Operating Temperature: +85 °C



233534 165 mm

RS PRO CABLE TIE, 203MM X 4.6 MM, ASSORTED NYLON, PK-250

Pack size: **250 x EA**

- Length: 203 mm
- Width: 4.6 mm
- Colour: Assorted
- Material: Nylon 66
- Type: Non-Releasable
- Quantity: 250
- Minimum Operating Temperature: -50 °C
- Maximum Operating Temperature: +85 °C



233708 203 mm

RS PRO CABLE TIE, 300MM X 4.8 MM, ASSORTED NYLON, PK-250

Pack size: **250 x EA**

- Length: 300 mm
- Width: 4.8 mm
- Colour: Assorted
- Material: Nylon 66
- Type: Non-Releasable
- Quantity: 250
- Minimum Operating Temperature: -50 °C
- Maximum Operating Temperature: +85 °C



233714 300 mm

RS PRO CABLE TIE, 385MM X 4.8 MM, ASSORTED NYLON, PK-250

Pack size: **250 x EA**

- Length: 385 mm
- Width: 4.8 mm
- Colour: Assorted
- Material: Nylon 66
- Type: Non-Releasable
- Quantity: 250
- Minimum Operating Temperature: -50 °C
- Maximum Operating Temperature: +85 °C



233792 385 mm

RS PRO CABLE TIE, 100MM X 2.5 MM, WHITE NYLON, PK-100

Pack size: **100 x EA**

- Length: 100 mm
- Width: 2.5 mm
- Colour: White
- Material: Nylon 66
- Type: Non-Releasable
- Quantity: 100
- Minimum Operating Temperature: -50 °C
- Maximum Operating Temperature: +85 °C



389864 100 mm

RS PRO CABLE TIE, 190MM X 4.8 MM, WHITE NYLON, PK-100

Pack size: **100 x EA**

- Length: 190 mm
- Width: 4.8 mm
- Colour: White
- Material: Nylon 66
- Type: Non-Releasable
- Quantity: 100
- Minimum Operating Temperature: -10 °C
- Maximum Operating Temperature: +85 °C



389870 190 mm

RS PRO CABLE TIE, 203MM X 3.6 MM, PINK NYLON, PK-100

Pack size: **100 x EA**

- Length: 203 mm
- Width: 3.6 mm
- Colour: Pink
- Material: Nylon 66
- Type: Non-Releasable
- Quantity: 100
- Tensile Strength: 176.4 N
- Maximum Bundle Diameter: 52 mm



404538 203 mm

RS PRO CABLE TIE, 100MM X 2.5 MM, WHITE NYLON, PK-100

Pack size: **100 x EA**

- Length: 100 mm
- Width: 2.5 mm
- Colour: White
- Material: Nylon 66
- Type: Non-Releasable
- Quantity: 100
- Minimum Operating Temperature: -50 °C
- Maximum Operating Temperature: +85 °C




390274 100 mm

RS PRO CABLE TIE, 200MM X 3.6 MM, BLUE NYLON, PK-100

Pack size: **100 x EA**

- Length: 200 mm
- Width: 3.6 mm
- Colour: Blue
- Material: Nylon 66
- Type: Non-Releasable
- Quantity: 100
- Tensile Strength: 176.4 N



404534 200 mm

RS PRO CABLE TIE, 203MM X 3.6 MM, YELLOW NYLON, PK-100

Pack size: **100 x EA**

- Length: 203 mm
- Width: 3.6 mm
- Colour: Yellow
- Material: Nylon 66
- Type: Non-Releasable
- Quantity: 100
- Tensile Strength: 176.4 N
- Maximum Bundle Diameter: 52 mm



404540 203 mm

RS PRO CABLE TIE, 203MM X 3.6 MM, GREEN NYLON, PK-100

Pack size: **100 x EA**

- Length: 203 mm
- Width: 3.6 mm
- Colour: Green
- Material: Nylon 66
- Type: Non-Releasable
- Quantity: 100
- Tensile Strength: 176.4 N
- Maximum Bundle Diameter: 52 mm



404544 203 mm

RS PRO CABLE TIE, 203MM X 3.6 MM, ORANGE NYLON, PK-100

Pack size: **100 x EA**

- Length: 203 mm
- Width: 3.6 mm
- Colour: Orange
- Material: Nylon 66
- Type: Non-Releasable
- Quantity: 100
- Tensile Strength: 176.4 N
- Maximum Bundle Diameter: 52 mm



404550 203 mm

RS PRO CABLE TIE, 143MM X 1.8 MM, NATURAL NYLON, PK-100

Pack size: **100 x EA**

- Length: 143 mm
- Width: 1.8 mm
- Colour: Natural
- Material: Nylon 66
- Type: Non-Releasable
- Quantity: 100
- Fire Behaviour: Flame Retardant
- Tensile Strength: 49 N



479588 143 mm

RS PRO CABLE TIE, 143MM X 1.8 MM, WHITE NYLON, PK-1000

Pack size: **1000 x EA**

- Length: 143 mm
- Width: 1.8 mm
- Colour: White
- Material: Nylon 66
- Type: Non-Releasable
- Quantity: 1000
- Fire Behaviour: Flame Retardant
- Tensile Strength: 49 N



479594 143 mm

RS PRO CABLE TIE, SCREW MOUNT, 113MM X 2.5 MM, NATURAL NYLON,

Pack size: **100 x EA**

- Length: 113 mm
- Width: 2.5 mm
- Colour: Natural
- Material: Nylon 66
- Type: Screw Mount
- Quantity: 100
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



601079 113 mm

RS PRO CABLE TIE, SCREW MOUNT, 171.5MM X 3.7 MM, NATURAL NYLON,

Pack size: **100 x EA**

- Length: 171.5 mm
- Width: 3.7 mm
- Colour: Natural
- Material: Nylon 66
- Type: Screw Mount
- Quantity: 100
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



601085 171.5 mm

RS PRO CABLE TIE, SCREW MOUNT, 221.3MM X 4.2 MM, NATURAL NYLON,

Pack size: **100 x EA**

- Length: 221.3 mm
- Width: 4.2 mm
- Colour: Natural
- Material: Nylon 66
- Type: Screw Mount
- Quantity: 100
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



601091 221.3 mm

RS PRO CABLE TIE, SCREW MOUNT, 317.2MM X 7.8 MM, NATURAL NYLON,

Pack size: **100 x EA**

- Length: 317.2 mm
- Width: 7.8 mm
- Colour: Natural
- Material: Nylon 66
- Type: Screw Mount
- Quantity: 100
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



601108 317.2 mm

RS PRO CABLE TIE, ROLLER BALL, 840MM X 12 MM, STEEL STAINLESS

Pack size: **100 x EA**

- Length: 840 mm
- Width: 12 mm
- Colour: Steel
- Material: Stainless Steel
- Type: Roller Ball
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +300 °C
- Fire Behaviour: Halogen Free



1235028 840 mm

RS PRO CABLE TIE, ROLLER BALL, 360MM X 12 MM, STEEL STAINLESS

Pack size: **100 x EA**

- Length: 360 mm
- Width: 12 mm
- Colour: Steel
- Material: Stainless Steel
- Type: Roller Ball
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +300 °C
- Fire Behaviour: Halogen Free



1235029 360 mm

RS PRO CABLE TIE, ROLLER BALL, 520MM X 12 MM, STEEL STAINLESS

Pack size: **100 x EA**

- Length: 520 mm
- Width: 12 mm
- Colour: Steel
- Material: Stainless Steel
- Type: Roller Ball
- Minimum Operating Temperature: -80 °C
- Maximum Operating Temperature: +538 °C
- Tensile Strength: 2225 N



1235030 520 mm

RS PRO CABLE TIE, ROLLER BALL, 680MM X 12 MM, STEEL STAINLESS

Pack size: **100 x EA**

- Length: 680 mm
- Width: 12 mm
- Colour: Steel
- Material: Stainless Steel
- Type: Roller Ball
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +300 °C
- Fire Behaviour: Halogen Free



1235033 680 mm

RS PRO CABLE TIE, ROLLER BALL, 200MM X 4.6 MM, STEEL STAINLESS

Pack size: **100 x EA**

- Length: 200 mm
- Width: 4.6 mm
- Colour: Steel
- Material: Stainless Steel
- Type: Roller Ball
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +300 °C
- Fire Behaviour: Halogen Free



1235034 200 mm

RS PRO CABLE TIE, ROLLER BALL, 360MM X 7.9 MM, STEEL STAINLESS

Pack size: **100 x EA**

- Length: 360 mm
- Width: 7.9 mm
- Colour: Steel
- Material: Stainless Steel
- Type: Roller Ball
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +300 °C
- Fire Behaviour: Halogen Free



1235035 360 mm

RS PRO CABLE TIE, ROLLER BALL, 125MM X 4.6 MM, STEEL STAINLESS

Pack size: **100 x EA**

- Length: 125 mm
- Width: 4.6 mm
- Colour: Steel
- Material: Stainless Steel
- Type: Roller Ball
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +300 °C
- Fire Behaviour: Halogen Free



1235036 125 mm

RS PRO CABLE TIE, ROLLER BALL, 360MM X 4.6 MM, STEEL STAINLESS

Pack size: **100 x EA**

- Length: 360 mm
- Width: 4.6 mm
- Colour: Steel
- Material: Stainless Steel
- Type: Roller Ball
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +300 °C
- Fire Behaviour: Halogen Free



1235037 360 mm

RS PRO CABLE TIE, ROLLER BALL, 200MM X 7.9 MM, METALLIC 316

Pack size: **100 x EA**

- Length: 200 mm
- Width: 7.9 mm
- Colour: Metallic
- Material: 316 Stainless Steel
- Type: Roller Ball
- Quantity: 100
- Minimum Operating Temperature: -80 °C
- Maximum Operating Temperature: +538 °C



1595313 200 mm

RS PRO CABLE TIE, ROLLER BALL, 360MM X 4.6 MM, METALLIC 316

Pack size: **100 x EA**

- Length: 360 mm
- Width: 4.6 mm
- Colour: Metallic
- Material: 316 Stainless Steel
- Type: Roller Ball
- Quantity: 100
- Minimum Operating Temperature: -80 °C
- Maximum Operating Temperature: +538 °C



1595329 360 mm

RS PRO CABLE TIE, ROLLER BALL, 360MM X 7.9 MM, METALLIC 316

Pack size: **100 x EA**

- Length: 360 mm
- Width: 7.9 mm
- Colour: Metallic
- Material: 316 Stainless Steel
- Type: Roller Ball
- Quantity: 100
- Minimum Operating Temperature: -80 °C
- Maximum Operating Temperature: +538 °C



1595335 360 mm

RS PRO CABLE TIE, BALL LOCK, 200MM X 4.6 MM, METALLIC 316

Pack size: **100 x EA**

- Length: 200 mm
- Width: 4.6 mm
- Colour: Metallic
- Material: 316 Stainless Steel
- Type: Ball Lock
- Quantity: 100
- Minimum Operating Temperature: -80 °C
- Maximum Operating Temperature: +538 °C



1595357 200 mm

RS PRO CABLE TIE, METAL DETECTABLE, 203MM X 4.6 MM, BLUE

Pack size: **100 x EA**

- Length: 203 mm
- Width: 4.6 mm
- Colour: Blue
- Material: Metal Detectable Nylon
- Type: Metal Detectable
- Quantity: 100
- Maximum Bundle Diameter: 52 mm



1721765 203 mm

RS PRO CABLE TIE, METAL DETECTABLE, 150MM X 3.6 MM, BLUE

Pack size: **100 x EA**

- Length: 150 mm
- Width: 3.6 mm
- Colour: Blue
- Material: Metal Detectable Nylon
- Type: Metal Detectable
- Quantity: 100
- Maximum Bundle Diameter: 36 mm



1721766 150 mm

RS PRO CABLE TIE, METAL DETECTABLE, 400MM X 4.6 MM, BLUE

Pack size: **100 x EA**

- Length: 400 mm
- Width: 4.6 mm
- Colour: Blue
- Material: Metal Detectable Nylon
- Type: Metal Detectable
- Quantity: 100
- Maximum Bundle Diameter: 116 mm



1721767 400 mm

RS PRO CABLE TIE, METAL DETECTABLE, 380MM X 7.6 MM, BLUE

Pack size: **100 x EA**

- Length: 380 mm
- Width: 7.6 mm
- Colour: Blue
- Material: Metal Detectable Nylon
- Type: Metal Detectable
- Quantity: 100
- Maximum Bundle Diameter: 105 mm



1721768 380 mm

RS PRO CABLE TIE, METAL DETECTABLE, 250MM X 4.5 MM, BLUE

Pack size: **100 x EA**

- Length: 250 mm
- Width: 4.5 mm
- Colour: Blue
- Material: Metal Detectable Nylon
- Type: Metal Detectable
- Quantity: 100
- Maximum Bundle Diameter: 65 mm



1721769 250 mm

RS PRO CABLE TIE, 200MM X 4.6 MM, BLACK PP, PK-100

Pack size: **100 x EA**

- Length: 200 mm
- Width: 4.6 mm
- Colour: Black
- Material: PP
- Type: Metal Detectable
- Quantity: 100
- Tensile Strength: 10 kg
- Maximum Bundle Diameter: 52 mm



1789487 200 mm

RS PRO CABLE TIE, 300MM X 7.6 MM, BLACK PP, PK-100

Pack size: **100 x EA**

- Length: 300 mm
- Width: 7.6 mm
- Colour: Black
- Material: PP
- Quantity: 100
- Tensile Strength: 23 kg
- Maximum Bundle Diameter: 80 mm



1789488 300 mm

RS PRO CABLE TIE, DOUBLE HEAD KNOT, 150MM X 3.6 MM, NATURAL PE

Pack size: **100 x EA**

- Length: 150 mm
- Width: 3.6 mm
- Colour: Natural
- Material: PE
- Type: Double Head Knot
- Quantity: 100
- Maximum Bundle Diameter: 38 mm



1789498 150 mm

RS PRO CABLE TIE, HOOK AND LOOP, 150MM X 17 MM, BLACK NYLON

Pack size: **10 x EA**

- Length: 150 mm
- Width: 17 mm
- Colour: Black
- Material: Nylon 66
- Type: Hook and Loop



1797165 150 mm

RS PRO CABLE TIE, HOOK AND LOOP, 225MM X 25 MM, BLACK NYLON

Pack size: **10 x EA**

- Length: 225 mm
- Width: 25 mm
- Colour: Black
- Material: Nylon 66
- Type: Hook and Loop



1797166 225 mm

RS PRO CABLE TIE, HOOK AND LOOP, 225MM X 25 MM, RED NYLON

- Pack size: **10 x EA**
- Length: 225 mm
 - Width: 25 mm
 - Colour: Red
 - Material: Nylon 66
 - Type: Hook and Loop



1797167 225 mm

RS PRO CABLE TIE, HOOK AND LOOP, 225MM X 25 MM, YELLOW NYLON

- Pack size: **10 x EA**
- Length: 225 mm
 - Width: 25 mm
 - Colour: Yellow
 - Material: Nylon 66
 - Type: Hook and Loop



1797168 225 mm

RS PRO CABLE TIE, HOOK AND LOOP, 225MM X 25 MM, GREEN NYLON

- Pack size: **10 x EA**
- Length: 225 mm
 - Width: 25 mm
 - Colour: Green
 - Material: Nylon 66
 - Type: Hook and Loop



1797169 225 mm

RS PRO CABLE TIE, HOOK AND LOOP, 325MM X 25 MM, BLACK NYLON


- Pack size: **10 x EA**
- Length: 325 mm
 - Width: 25 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Hook and Loop



1797172 325 mm

RS PRO CABLE TIE, HOOK AND LOOP, 225MM X 25 MM, BLUE NYLON

- Pack size: **10 x EA**
- Length: 225 mm
 - Width: 25 mm
 - Colour: Blue
 - Material: Nylon 66
 - Type: Hook and Loop



1797170 225 mm

RS PRO CABLE TIE, HOOK AND LOOP, 225MM X 25 MM, WHITE NYLON

- Pack size: **10 x EA**
- Length: 225 mm
 - Width: 25 mm
 - Colour: White
 - Material: Nylon 66
 - Type: Hook and Loop



1797171 225 mm

RS PRO CABLE TIE, HOOK AND LOOP, 325MM X 25 MM, GREEN NYLON

- Pack size: **10 x EA**
- Length: 325 mm
 - Width: 25 mm
 - Colour: Green
 - Material: Nylon 66
 - Type: Hook and Loop



1797175 325 mm

RS PRO CABLE TIE, HOOK AND LOOP, 325MM X 25 MM, BLUE NYLON

- Pack size: **10 x EA**
- Length: 325 mm
 - Width: 25 mm
 - Colour: Blue
 - Material: Nylon 66
 - Type: Hook and Loop



1797176 325 mm

RS PRO CABLE TIE, HOOK AND LOOP, 5M X 16 MM, BLACK NYLON

- Pack size: **5 x MTR**
- Length: 5 m
 - Width: 16 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Hook and Loop



1797177 5 m

RS PRO CABLE TIE, HOOK AND LOOP, 5M X 16 MM, RED NYLON

- Pack size: **5 x MTR**
- Length: 5 m
 - Width: 16 mm
 - Colour: Red
 - Material: Nylon 66
 - Type: Hook and Loop



1797178 5 m

RS PRO CABLE TIE, HOOK AND LOOP, 5M X 16 MM, YELLOW NYLON

- Pack size: **5 x MTR**
- Length: 5 m
 - Width: 16 mm
 - Colour: Yellow
 - Material: Nylon 66
 - Type: Hook and Loop



1797179 5 m

RS PRO CABLE TIE, HOOK AND LOOP, 5M X 16 MM, BLUE NYLON

- Pack size: **5 x MTR**
- Length: 5 m
 - Width: 16 mm
 - Colour: Blue
 - Material: Nylon 66
 - Type: Hook and Loop



1797180 5 m

RS PRO CABLE TIE, HOOK AND LOOP, 310MM X 20 MM, RED NYLON, PK-10

- Pack size: **10 x EA**
- Length: 310 mm
 - Width: 20 mm
 - Colour: Red
 - Material: Nylon 66
 - Type: Hook and Loop
 - Quantity: 10



1797183 310 mm

RS PRO CABLE TIE, HOOK AND LOOP, 5M X 16 MM, WHITE NYLON

- Pack size: **5 x MTR**
- Length: 5 m
 - Width: 16 mm
 - Colour: White
 - Material: Nylon 66
 - Type: Hook and Loop



1797181 5 m

RS PRO CABLE TIE, HOOK AND LOOP, 310MM X 20 MM, BLACK NYLON, PK-10

- Pack size: **5 x MTR**
- Length: 310 mm
 - Width: 20 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Hook and Loop
 - Quantity: 10



1797182 310 mm

RS PRO CABLE TIE, HOOK AND LOOP, 300MM X 20 MM, YELLOW NYLON, PK-10

- Pack size: **10 x EA**
- Length: 300 mm
 - Width: 20 mm
 - Colour: Yellow
 - Material: Nylon 66
 - Type: Hook and Loop
 - Quantity: 10



1797184 300 mm

RS PRO CABLE TIE, HOOK AND LOOP, 300MM X 20 MM, GREEN NYLON, PK-10

Pack size: **10 x EA**

- Length: 300 mm
- Width: 20 mm
- Colour: Green
- Material: Nylon 66
- Type: Hook and Loop
- Quantity: 10



1797185 300 mm

RS PRO CABLE TIE, HOOK AND LOOP, 300MM X 20 MM, BLUE NYLON, PK-10

Pack size: **10 x EA**

- Length: 300 mm
- Width: 20 mm
- Colour: Blue
- Material: Nylon 66
- Type: Hook and Loop
- Quantity: 10



1797186 300 mm

RS PRO CABLE TIE, HOOK AND LOOP, 310MM X 20 MM, WHITE NYLON, PK-10

Pack size: **10 x EA**

- Length: 310 mm
- Width: 20 mm
- Colour: White
- Material: Nylon 66
- Type: Hook and Loop
- Quantity: 10



1797187 310 mm

RS PRO CABLE TIE, 360MM X 4.6 MM, BLACK 316 STAINLESS STEEL

Pack size: **100 x EA**

- Length: 360 mm
- Width: 4.6 mm
- Colour: Black
- Material: 316 Stainless Steel
- UV Resistant: Yes
- Minimum Operating Temperature: -80 °C
- Maximum Operating Temperature: +150 °C
- Fire Behaviour: Halogen Free



1834160 360 mm

RS PRO CABLE TIE, ZIG ZAG, 100MM X 4.6 MM 316 STAINLESS STEEL

Pack size: **100 x EA**

- Length: 100 mm
- Width: 4.6 mm
- Material: 316 Stainless Steel
- Type: Zig Zag
- UV Resistant: Yes
- Minimum Operating Temperature: -80 °C
- Maximum Operating Temperature: +500 °C
- Fire Behaviour: Fire Resistant



1834162 100 mm

RS PRO CABLE TIE, ZIG ZAG, 150MM X 4.6 MM 316 STAINLESS STEEL

Pack size: **100 x EA**

- Length: 150 mm
- Width: 4.6 mm
- Material: 316 Stainless Steel
- Type: Zig Zag
- UV Resistant: Yes
- Minimum Operating Temperature: -80 °C
- Maximum Operating Temperature: +500 °C
- Fire Behaviour: Fire Resistant



1834165 150 mm

RS PRO CABLE TIE, LADDER SINGLE LOCK, 300MM X 7 MM, BLACK 316

Pack size: **100 x EA**

- Length: 300 mm
- Width: 7 mm
- Colour: Black
- Material: 316 Stainless Steel
- Type: Ladder Single Lock
- Quantity: 100
- UV Resistant: Yes
- Minimum Operating Temperature: -80 °C



1834173 300 mm

RS PRO CABLE TIE, LADDER SINGLE LOCK, 225MM X 7 MM 316 STAINLESS

Pack size: **100 x EA**

- Length: 225 mm
- Width: 7 mm
- Material: 316 Stainless Steel
- Type: Ladder Single Lock
- Quantity: 100
- UV Resistant: Yes
- Minimum Operating Temperature: -80 °C
- Maximum Operating Temperature: +500 °C



1834175 225 mm

RS PRO CABLE TIE, LADDER SINGLE LOCK, 610MM X 7 MM 316 STAINLESS

Pack size: **100 x EA**

- Length: 610 mm
- Width: 7 mm
- Material: 316 Stainless Steel
- Type: Ladder Single Lock
- Quantity: 100
- UV Resistant: Yes
- Minimum Operating Temperature: -80 °C
- Maximum Operating Temperature: +500 °C



1834177 610 mm

RS PRO CABLE TIE, LADDER SINGLE LOCK, 610MM X 12 MM 316 STAINLESS

Pack size: **100 x EA**

- Length: 610 mm
- Width: 12 mm
- Material: 316 Stainless Steel
- Type: Ladder Single Lock
- Quantity: 100
- UV Resistant: Yes
- Minimum Operating Temperature: -80 °C
- Maximum Operating Temperature: +500 °C



1834178 610 mm

RS PRO CABLE TIE, RELEASEABLE, 330MM X 10 MM, BLACK 316

Pack size: **100 x EA**

- Length: 330 mm
- Width: 10 mm
- Colour: Black
- Material: 316 Stainless Steel
- Type: Releaseable
- UV Resistant: Yes
- Minimum Operating Temperature: -80 °C
- Maximum Operating Temperature: +150 °C



1834183 330 mm

RS PRO CABLE TIE, BALL LOCK, 125MM X 4.6 MM 316 STAINLESS STEEL

Pack size: **100 x EA**

- Length: 125 mm
- Width: 4.6 mm
- Material: 316 Stainless Steel
- Type: Ball Lock
- UV Resistant: Yes
- Minimum Operating Temperature: -80 °C
- Maximum Operating Temperature: +500 °C
- Fire Behaviour: Fire Resistant



1834228 125 mm

RS PRO CABLE TIE, BALL LOCK, 360MM X 4.6 MM 304 STAINLESS

Pack size: **100 x EA**

- Length: 360 mm
- Width: 4.6 mm
- Material: 304 Stainless Steel
- Type: Ball Lock
- UV Resistant: Yes
- Minimum Operating Temperature: -80 °C
- Maximum Operating Temperature: +500 °C
- Tensile Strength: 1100 N



1834225 360 mm

RS PRO CABLE TIE, BALL LOCK, 100MM X 4.6 MM 316 STAINLESS STEEL

Pack size: **100 x EA**

- Length: 100 mm
- Width: 4.6 mm
- Material: 316 Stainless Steel
- Type: Ball Lock
- UV Resistant: Yes
- Minimum Operating Temperature: -80 °C
- Maximum Operating Temperature: +500 °C
- Fire Behaviour: Fire Resistant



1834227 100 mm

RS PRO CABLE TIE, BALL LOCK, 150MM X 4.6 MM 316 STAINLESS STEEL

Pack size: **100 x EA**

- Length: 150 mm
- Width: 4.6 mm
- Material: 316 Stainless Steel
- Type: Ball Lock
- UV Resistant: Yes
- Minimum Operating Temperature: -80 °C
- Maximum Operating Temperature: +500 °C
- Fire Behaviour: Fire Resistant



1834229 150 mm

RS PRO CABLE TIE, BALL LOCK, 200MM X 4.6 MM 316 STAINLESS

Pack size: **100 x EA**

- Length: 200 mm
- Width: 4.6 mm
- Material: 316 Stainless Steel
- Type: Ball Lock
- UV Resistant: Yes
- Minimum Operating Temperature: -80 °C
- Maximum Operating Temperature: +500 °C
- Fire Behaviour: Fire Resistant



1834230 200 mm

RS PRO CABLE TIE, BALL LOCK, 360MM X 4.6 MM 316 STAINLESS

Pack size: **100 x EA**

- Length: 360 mm
- Width: 4.6 mm
- Material: 316 Stainless Steel
- Type: Ball Lock
- UV Resistant: Yes
- Minimum Operating Temperature: -80 °C
- Maximum Operating Temperature: +500 °C
- Fire Behaviour: Fire Resistant



1834231 360 mm

RS PRO CABLE TIE, BALL LOCK, 360MM X 7.9 MM 316 STAINLESS

Pack size: **100 x EA**

- Length: 360 mm
- Width: 7.9 mm
- Material: 316 Stainless Steel
- Type: Ball Lock
- UV Resistant: Yes
- Minimum Operating Temperature: -80 °C
- Maximum Operating Temperature: +500 °C
- Fire Behaviour: Fire Resistant



1834238 360 mm

RS PRO CABLE TIE, BALL LOCK, 840MM X 4.6 MM 316 STAINLESS

Pack size: **100 x EA**

- Length: 840 mm
- Width: 4.6 mm
- Material: 316 Stainless Steel
- Type: Ball Lock
- UV Resistant: Yes
- Minimum Operating Temperature: -80 °C
- Maximum Operating Temperature: +500 °C
- Fire Behaviour: Fire Resistant



1834234 840 mm

RS PRO CABLE TIE, BALL LOCK, 200MM X 7.9 MM 316 STAINLESS

Pack size: **100 x EA**

- Length: 200 mm
- Width: 7.9 mm
- Material: 316 Stainless Steel
- Type: Ball Lock
- UV Resistant: Yes
- Minimum Operating Temperature: -80 °C
- Maximum Operating Temperature: +500 °C
- Fire Behaviour: Fire Resistant



1834237 200 mm

RS PRO CABLE TIE, BALL LOCK, 520MM X 7.9 MM 316 STAINLESS

Pack size: **100 x EA**

- Length: 520 mm
- Width: 7.9 mm
- Material: 316 Stainless Steel
- Type: Ball Lock
- UV Resistant: Yes
- Minimum Operating Temperature: -80 °C
- Maximum Operating Temperature: +500 °C
- Fire Behaviour: Fire Resistant



1834239 520 mm

RS PRO CABLE TIE, BALL LOCK, 680MM X 7.9 MM 316 STAINLESS

Pack size: **100 x EA**

- Length: 680 mm
- Width: 7.9 mm
- Material: 316 Stainless Steel
- Type: Ball Lock
- UV Resistant: Yes
- Minimum Operating Temperature: -80 °C
- Maximum Operating Temperature: +500 °C
- Fire Behaviour: Fire Resistant



1834240 680 mm

RS PRO CABLE TIE, BALL LOCK, 520MM X 12 MM 316 STAINLESS STEEL

Pack size: **100 x EA**

- Length: 520 mm
- Width: 12 mm
- Material: 316 Stainless Steel
- Type: Ball Lock
- UV Resistant: Yes
- Minimum Operating Temperature: -80 °C
- Maximum Operating Temperature: +500 °C
- Fire Behaviour: Fire Resistant



1834246 520 mm

RS PRO CABLE TIE, BALL LOCK, 100MM X 4.6 MM, BLACK 316

Pack size: **100 x EA**

- Length: 100 mm
- Width: 4.6 mm
- Colour: Black
- Material: 316 Stainless Steel
- Type: Ball Lock
- UV Resistant: Yes
- Minimum Operating Temperature: -80 °C
- Maximum Operating Temperature: +150 °C



1834251 100 mm

RS PRO CABLE TIE, BALL LOCK, 680MM X 12 MM 316 STAINLESS STEEL

Pack size: **100 x EA**

- Length: 680 mm
- Width: 12 mm
- Material: 316 Stainless Steel
- Type: Ball Lock
- UV Resistant: Yes
- Minimum Operating Temperature: -80 °C
- Maximum Operating Temperature: +500 °C
- Fire Behaviour: Fire Resistant



1834247 680 mm

RS PRO CABLE TIE, BALL LOCK, 760MM X 12 MM 316 STAINLESS STEEL

Pack size: **100 x EA**

- Length: 760 mm
- Width: 12 mm
- Material: 316 Stainless Steel
- Type: Ball Lock
- UV Resistant: Yes
- Minimum Operating Temperature: -80 °C
- Maximum Operating Temperature: +500 °C
- Fire Behaviour: Fire Resistant



1834248 760 mm

RS PRO CABLE TIE, BALL LOCK, 125MM X 4.6 MM, BLACK 316

Pack size: **100 x EA**

- Length: 125 mm
- Width: 4.6 mm
- Colour: Black
- Material: 316 Stainless Steel
- Type: Ball Lock
- UV Resistant: Yes
- Minimum Operating Temperature: -80 °C
- Maximum Operating Temperature: +150 °C



1834252 125 mm

RS PRO CABLE TIE, BALL LOCK, 150MM X 4.6 MM, BLACK 316

Pack size: **100 x EA**

- Length: 150 mm
- Width: 4.6 mm
- Colour: Black
- Material: 316 Stainless Steel
- Type: Ball Lock
- UV Resistant: Yes
- Minimum Operating Temperature: -80 °C
- Maximum Operating Temperature: +150 °C



1834253 150 mm

RS PRO CABLE TIE, BALL LOCK, 360MM X 7.9 MM, BLACK 316

Pack size: **100 x EA**

- Length: 360 mm
- Width: 7.9 mm
- Colour: Black
- Material: 316 Stainless Steel
- Type: Ball Lock
- UV Resistant: Yes
- Minimum Operating Temperature: -80 °C
- Maximum Operating Temperature: +150 °C



1834261 360 mm

RS PRO CABLE TIE, BALL LOCK, 200MM X 4.6 MM, BLACK 316

Pack size: **100 x EA**

- Length: 200 mm
- Width: 4.6 mm
- Colour: Black
- Material: 316 Stainless Steel
- Type: Ball Lock
- UV Resistant: Yes
- Minimum Operating Temperature: -80 °C
- Maximum Operating Temperature: +150 °C



1834254 200 mm

RS PRO CABLE TIE, RELEASEABLE, 330MM X 10 MM, BLACK 316

Pack size: **100 x EA**

- Length: 330 mm
- Width: 10 mm
- Colour: Black
- Material: 316 Stainless Steel
- Type: Releaseable
- Quantity: 100
- UV Resistant: Yes
- Minimum Operating Temperature: -80 °C



1859364 330 mm

RS PRO CABLE TIE, 368MM X 4.8 MM, BLACK NYLON, PK-100

Pack size: **100 x EA**

- Length: 368 mm
- Width: 4.8 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releaseable
- Quantity: 100
- UV Resistant: Yes
- Minimum Operating Temperature: -40 °C



2012389 368 mm

RS PRO CABLE TIE, BALL LOCK, 520MM X 4.6 MM, BLACK 316

Pack size: **100 x EA**

- Length: 520 mm
- Width: 4.6 mm
- Colour: Black
- Material: 316 Stainless Steel
- Type: Ball Lock
- UV Resistant: Yes
- Minimum Operating Temperature: -80 °C
- Maximum Operating Temperature: +150 °C



1834256 520 mm

RS PRO CABLE TIE, BALL LOCK, 1.2M X 12 MM, BLACK 316 STAINLESS STEEL

Pack size: **100 x EA**

- Length: 1.2 m
- Width: 12 mm
- Colour: Black
- Material: 316 Stainless Steel
- Type: Ball Lock
- UV Resistant: Yes
- Minimum Operating Temperature: -80 °C
- Maximum Operating Temperature: +150 °C



1834269 1.2 m

RS PRO CABLE TIE, RELEASABLE, 230MM X 5 MM, BLACK POLYESTER

Pack size: **100 x EA**

- Length: 230 mm
- Width: 5 mm
- Colour: Black
- Material: Polyester Coated Stainless Steel
- Type: Releasable
- Quantity: 100
- Minimum Operating Temperature: -80 °C
- Maximum Operating Temperature: +150 °C



1858670 230 mm

RS PRO CABLE TIE KIT, 203MM X 3.6 MM, BLACK NYLON, PK-100

Pack size: **100 x EA**

- Length: 203 mm
- Width: 3.6 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releasable
- Quantity: 100
- UV Resistant: Yes
- Minimum Operating Temperature: -40 °C



2012390 203 mm

RS PRO CABLE TIE, HEAT RESISTANT, NON-RELEASABLE, 203MM X 4.6 MM,

Pack size: **100 x EA**

- Length: 203 mm
- Width: 4.6 mm
- Colour: Natural
- Material: PA 4.6
- Type: Heat Resistant, Non-Releasable
- Maximum Operating Temperature: +150 °C
- Fire Behaviour: Halogen Free
- Tensile Strength: 50 lb



2066627 203 mm

RS PRO CABLE TIE, HEAT RESISTANT, NON-RELEASABLE, 385MM X 4.8 MM,

Pack size: **100 x EA**

- Length: 385 mm
- Width: 4.8 mm
- Colour: Natural
- Material: PA 4.6
- Type: Heat Resistant, Non-Releasable
- Maximum Operating Temperature: +150 °C
- Fire Behaviour: Halogen Free
- Tensile Strength: 50 lb



2066628 385 mm

RS PRO CABLE TIE, 102MM X 2.4 MM, BLACK NYLON, PK-100

Pack size: **100 x EA**

- Length: 102 mm
- Width: 2.4 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releasable
- Quantity: 100
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



2098130 102 mm

RS PRO CABLE TIE, 155MM X 3.6 MM, BLACK NYLON, PK-100

Pack size: **100 x EA**

- Length: 155 mm
- Width: 3.6 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releasable
- Quantity: 100
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



2098131 155 mm

RS PRO CABLE TIE KIT, BLACK PA66MP

Pack size: **1 x KT**

- Colour: Black
- Material: PA66MP
- Fire Behaviour: Self-extinguishing



2013590 Black

RS PRO CABLE TIE, 284MM X 3.6 MM, BLACK NYLON, PK-100

Pack size: **100 x EA**

- Length: 284 mm
- Width: 3.6 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releasable
- Quantity: 100
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



2098133 284 mm

RS PRO CABLE TIE, HEAT RESISTANT, NON-RELEASABLE, 100MM X 2.5 MM,

Pack size: **100 x EA**

- Length: 100 mm
- Width: 2.5 mm
- Colour: Natural
- Material: PA 4.6
- Type: Heat Resistant, Non-Releasable
- Maximum Operating Temperature: +150 °C
- Fire Behaviour: Halogen Free
- Tensile Strength: 18 lb



2066625 100 mm

RS PRO CABLE TIE, 350MM X 8 MM, BLACK NYLON, PK-100

Pack size: **500 x EA**

- Length: 350 mm
- Width: 8 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releasable
- Quantity: 100
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



2098136 350 mm

RS PRO CABLE TIE, 350MM X 8 MM, BLACK NYLON, PK-100

Pack size: **100 x EA**

- Length: 350 mm
- Width: 8 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releasable
- Quantity: 100
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



2098135 350 mm

RS PRO CABLE TIE, 186MM X 4.8 MM, BLACK NYLON, PK-100

Pack size: **100 x EA**

- Length: 186 mm
- Width: 4.8 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releasable
- Quantity: 100
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



2098132 186 mm

RS PRO CABLE TIE, 203MM X 3.6 MM, NATURAL NYLON

Pack size: **100 x EA**

- Length: 203 mm
- Width: 3.6 mm
- Colour: Natural
- Material: Nylon 66
- Type: Non-Releasable
- UV Resistant: No
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



2132982 203 mm

RS PRO CABLE TIE, 203MM X 3.6 MM, NATURAL NYLON

Pack size: **1000 x EA**

- Length: 203 mm
- Width: 3.6 mm
- Colour: Natural
- Material: Nylon 66
- Type: Non-Releasable
- UV Resistant: No
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



2132983 203 mm

RS PRO CABLE TIE, 203MM X 3.5 MM, NATURAL NYLON

Pack size: **1000 x EA**

- Length: 203 mm
- Width: 3.5 mm
- Colour: Natural
- Material: Nylon 66
- Type: Non-Releaseable
- UV Resistant: No
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



2132984 203 mm

RS PRO CABLE TIE, 284MM X 3.6 MM, BLACK NYLON, PK-100

Pack size: **1000 x EA**

- Length: 284 mm
- Width: 3.6 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releaseable
- Quantity: 100
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



2098134 284 mm

RS PRO CABLE TIE, 250MM X 4.8 MM, NATURAL NYLON

Pack size: **1000 x EA**

- Length: 250 mm
- Width: 4.8 mm
- Colour: Natural
- Material: Nylon 66
- Type: Non-Releaseable
- UV Resistant: No
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



2132987 250 mm

RS PRO CABLE TIE, 368MM X 3.6 MM, NATURAL NYLON

Pack size: **100 x EA**

- Length: 368 mm
- Width: 3.6 mm
- Colour: Natural
- Material: Nylon 66
- Type: Non-Releaseable
- UV Resistant: No
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



2132989 368 mm

RS PRO CABLE TIE, 450MM X 8 MM, BLACK NYLON

Pack size: **50 x EA**

- Length: 450 mm
- Width: 8 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releaseable
- UV Resistant: No
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



2132990 450 mm

RS PRO CABLE TIE, 142MM X 3.2 MM, BLACK NYLON

Pack size: **1000 x EA**

- Length: 142 mm
- Width: 3.2 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releaseable
- UV Resistant: Yes
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



2132992 142 mm

RS PRO CABLE TIE, 165MM X 2.5 MM, BLACK NYLON

Pack size: **100 x EA**

- Length: 165 mm
- Width: 2.5 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releaseable
- UV Resistant: Yes
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



2132993 165 mm

RS PRO CABLE TIE, 230MM X 2.5 MM, BLACK NYLON

Pack size: **1000 x EA**

- Length: 230 mm
- Width: 2.5 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releaseable
- UV Resistant: Yes
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



2132995 230 mm

RS PRO CABLE TIE, 190MM X 4.8 MM, BLACK NYLON

Pack size: **1000 x EA**

- Length: 190 mm
- Width: 4.8 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releaseable
- UV Resistant: Yes
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



2132994 190 mm

RS PRO CABLE TIE, 230MM X 2.5 MM, BLACK NYLON

Pack size: **100 x EA**

- Length: 230 mm
- Width: 2.5 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releaseable
- UV Resistant: Yes
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



2132996 230 mm

RS PRO CABLE TIE, 250MM X 4.8 MM, BLACK NYLON

Pack size: **1000 x EA**

- Length: 250 mm
- Width: 4.8 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releaseable
- UV Resistant: Yes
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



2132997 250 mm

RS PRO CABLE TIE, 292MM X 3.6 MM, BLACK NYLON

Pack size: **100 x EA**

- Length: 292 mm
- Width: 3.6 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releaseable
- UV Resistant: Yes
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



2132999 292 mm

RS PRO CABLE TIE, 368MM X 3.6 MM, BLACK NYLON

Pack size: **1000 x EA**

- Length: 368 mm
- Width: 3.6 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releaseable
- UV Resistant: Yes
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



2133000 368 mm

RS PRO CABLE TIE, 450MM X 8 MM, BLACK NYLON

Pack size: **50 x EA**

- Length: 450 mm
- Width: 8 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releaseable
- UV Resistant: Yes
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



2133002 450 mm

RS PRO CABLE TIE, DOUBLE HEADED, 500MM X 12.7 MM, BLACK NYLON

Pack size: **50 x EA**

- Length: 500 mm
- Width: 12.7 mm
- Colour: Black
- Material: Nylon 66
- Type: Double Headed
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C
- Fire Behaviour: Self-extinguishing



2133018 500 mm

RS PRO CABLE TIE, 361MM X 4.8 MM, BLACK NYLON, PK-100

Pack size: **100 x EA**

- Length: 361 mm
- Width: 4.8 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releaseable
- Quantity: 100
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



2098137 361 mm

RS PRO CABLE TIE, 100MM X 2.5 MM→4.8 MM, NATURAL NYLON, PK-250

Pack size: **1 x KT**

- Length: 100 mm→385 mm
- Width: 2.5 mm→4.8 mm
- Colour: Natural
- Material: Nylon 66
- Type: Non-Releaseable
- Quantity: 2500
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



2206253 100 mm→385 mm

RS PRO CABLE TIE, 100MM X 2.5 MM→4.8 MM, BLACK NYLON, PK-2500

Pack size: **1 x KT**

- Length: 100 mm→385 mm
- Width: 2.5 mm→4.8 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releaseable
- Quantity: 2500
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



2206254 100 mm→385 mm

RS PRO CABLE TIE, 350MM X 12 MM, BLACK 316 STAINLESS STEEL, PK-100

Pack size: **100 x EA**

- Length: 350 mm
- Width: 12 mm
- Colour: Black
- Material: 316 Stainless Steel
- Type: Non-Releaseable
- Quantity: 100
- UV Resistant: Yes
- Minimum Operating Temperature: -40 °C



2242227 350 mm

RS PRO CABLE TIE, 250MM X 4.8 MM, NATURAL NYLON

Pack size: **100 x EA**

- Length: 250 mm
- Width: 4.8 mm
- Colour: Natural
- Material: Nylon 66
- Type: Non-Releaseable
- UV Resistant: No
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



2132986 250 mm

RS PRO CABLE TIE, DOUBLE HEADED, 900MM X 8 MM, BLUE NYLON, PK-50

Pack size: **50 x EA**

- Length: 900 mm
- Width: 8 mm
- Colour: Blue
- Material: Nylon 66
- Type: Double Headed
- Quantity: 50
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



2133019 900 mm

RS PRO CABLE TIE, 450MM X 12 MM, BLACK 316 STAINLESS STEEL, PK-100

Pack size: **100 x EA**

- Length: 450 mm
- Width: 12 mm
- Colour: Black
- Material: 316 Stainless Steel
- Type: Non-Releaseable
- Quantity: 100
- UV Resistant: Yes
- Minimum Operating Temperature: -40 °C



2242229 450 mm

RS PRO CABLE TIE, 550MM X 12 MM, BLACK 316 STAINLESS STEEL, PK-100

Pack size: **100 x EA**

- Length: 550 mm
- Width: 12 mm
- Colour: Black
- Material: 316 Stainless Steel
- Type: Non-Releaseable
- Quantity: 100
- UV Resistant: Yes
- Minimum Operating Temperature: -40 °C



2242230 550 mm

RS PRO CABLE TIE, 150MM X 4.6 MM, BLACK 316 STAINLESS STEEL, PK-100

Pack size: **100 x EA**

- Length: 150 mm
- Width: 4.6 mm
- Colour: Black
- Material: 316 Stainless Steel
- Type: Non-Releaseable
- Quantity: 100
- UV Resistant: Yes
- Minimum Operating Temperature: -40 °C



2242232 150 mm

RS PRO CABLE TIE, 200MM X 4.6 MM, BLACK 316 STAINLESS STEEL, PK-100

Pack size: **100 x EA**

- Length: 200 mm
- Width: 4.6 mm
- Colour: Black
- Material: 316 Stainless Steel
- Type: Non-Releaseable
- Quantity: 100
- UV Resistant: Yes
- Minimum Operating Temperature: -40 °C



2242233 200 mm

RS PRO CABLE TIE, 350MM X 4.6 MM, BLACK 316 STAINLESS STEEL, PK-100

Pack size: **100 x EA**

- Length: 350 mm
- Width: 4.6 mm
- Colour: Black
- Material: 316 Stainless Steel
- Type: Non-Releaseable
- Quantity: 100
- UV Resistant: Yes
- Minimum Operating Temperature: -40 °C



2242235 350 mm

RS PRO CABLE TIE, 450MM X 4.6 MM, BLACK 316 STAINLESS STEEL, PK-100

Pack size: **100 x EA**

- Length: 450 mm
- Width: 4.6 mm
- Colour: Black
- Material: 316 Stainless Steel
- Type: Non-Releaseable
- Quantity: 100
- UV Resistant: Yes
- Minimum Operating Temperature: -40 °C



2242236 450 mm

RS PRO CABLE TIE, 650MM X 4.6 MM, BLACK 316 STAINLESS STEEL, PK-100

Pack size: **100 x EA**

- Length: 650 mm
- Width: 4.6 mm
- Colour: Black
- Material: 316 Stainless Steel
- Type: Non-Releaseable
- Quantity: 100
- UV Resistant: Yes
- Minimum Operating Temperature: -40 °C



2242238 650 mm

RS PRO CABLE TIE, 1M X 8 MM, BLACK 316 STAINLESS STEEL, PK-100

Pack size: **100 x EA**

- Length: 1 m
- Width: 8 mm
- Colour: Black
- Material: 316 Stainless Steel
- Type: Non-Releaseable
- Quantity: 100
- UV Resistant: Yes
- Minimum Operating Temperature: -40 °C



2242241 1 m

RS PRO CABLE TIE, 350MM X 8 MM, BLACK 316 STAINLESS STEEL, PK-100

Pack size: **100 x EA**

- Length: 350 mm
- Width: 8 mm
- Colour: Black
- Material: 316 Stainless Steel
- Type: Non-Releaseable
- Quantity: 100
- UV Resistant: Yes
- Minimum Operating Temperature: -40 °C



2242243 350 mm

RS PRO CABLE TIE, 450MM X 8 MM, BLACK 316 STAINLESS STEEL, PK-100

Pack size: **100 x EA**

- Length: 450 mm
- Width: 8 mm
- Colour: Black
- Material: 316 Stainless Steel
- Type: Non-Releaseable
- Quantity: 100
- UV Resistant: Yes
- Minimum Operating Temperature: -40 °C



2242244 450 mm

RS PRO CABLE TIE, 650MM X 8 MM, BLACK 316 STAINLESS STEEL, PK-100

Pack size: **100 x EA**

- Length: 650 mm
- Width: 8 mm
- Colour: Black
- Material: 316 Stainless Steel
- Type: Non-Releaseable
- Quantity: 100
- UV Resistant: Yes
- Minimum Operating Temperature: -40 °C



2242246 650 mm

RS PRO CABLE TIE, 100 MM, 150 MM, 203 MM X 2.5 MM, 3.6 MM, 4.6 MM,

Pack size: **500 x EA**

- Length: 100 mm, 150 mm, 203 mm
- Width: 2.5 mm, 3.6 mm, 4.6 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releaseable
- UV Resistant: No
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



2243112 100 mm, 150 mm,

RS PRO CABLE TIE, 1.168 M X 9 MM, NATURAL NYLON

Pack size: **50 x EA**

- Length: 1.168 m
- Width: 9 mm
- Colour: Natural
- Material: Nylon 66
- Type: Non-Releaseable
- UV Resistant: No
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



2243117 1.168 m

RS PRO CABLE TIE, 1.168 M X 9 MM, BLACK NYLON

Pack size: **50 x EA**

- Length: 1.168 m
- Width: 9 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releaseable
- UV Resistant: No
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



2243119 1.168 m

RS PRO CABLE TIE, 150MM X 3.6 MM, GREEN NYLON

Pack size: **100 x EA**

- Length: 150 mm
- Width: 3.6 mm
- Colour: Green
- Material: Nylon 66
- Type: Non-Releaseable
- UV Resistant: No
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



2243122 150 mm

RS PRO CABLE TIE, 203MM X 4.6 MM, NATURAL NYLON

Pack size: **500 x EA**

- Length: 203 mm
- Width: 4.6 mm
- Colour: Natural
- Material: Nylon 66
- Type: Non-Releaseable
- UV Resistant: No
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



2243126 203 mm

RS PRO CABLE TIE, 150MM X 3.6 MM, RED NYLON

Pack size: **100 x EA**

- Length: 150 mm
- Width: 3.6 mm
- Colour: Red
- Material: Nylon 66
- Type: Non-Releaseable
- UV Resistant: No
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



2243123 150 mm

RS PRO CABLE TIE, 150MM X 3.6 MM, BLACK NYLON

Pack size: **100 x EA**

- Length: 150 mm
- Width: 3.6 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releaseable
- UV Resistant: Yes
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



2243124 150 mm

RS PRO CABLE TIE, 203MM X 4.6 MM, BLUE NYLON

Pack size: **100 x EA**

- Length: 203 mm
- Width: 4.6 mm
- Colour: Blue
- Material: Nylon 66
- Type: Non-Releaseable
- UV Resistant: No
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



2243127 203 mm

RS PRO CABLE TIE, 203MM X 4.6 MM, GREEN NYLON

Pack size: **100 x EA**

- Length: 203 mm
- Width: 4.6 mm
- Colour: Green
- Material: Nylon 66
- Type: Non-Releaseable
- UV Resistant: No
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



2243128 203 mm

RS PRO CABLE TIE, 203MM X 4.6 MM, ORANGE NYLON

Pack size: **100 x EA**

- Length: 203 mm
- Width: 4.6 mm
- Colour: Orange
- Material: Nylon 66
- Type: Non-Releaseable
- UV Resistant: No
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



2243130 203 mm

RS PRO CABLE TIE, 203MM X 4.6 MM, RED NYLON

Pack size: **100 x EA**

- Length: 203 mm
- Width: 4.6 mm
- Colour: Red
- Material: Nylon 66
- Type: Non-Releaseable
- UV Resistant: No
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



2243131 203 mm

RS PRO CABLE TIE, 203MM X 4.6 MM, YELLOW NYLON

Pack size: **100 x EA**

- Length: 203 mm
- Width: 4.6 mm
- Colour: Yellow
- Material: Nylon 66
- Type: Non-Releaseable
- UV Resistant: No
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



2243133 203 mm

RS PRO CABLE TIE, 250MM X 2.5 MM, NATURAL NYLON

Pack size: **100 x EA**

- Length: 250 mm
- Width: 2.5 mm
- Colour: Natural
- Material: Nylon 66
- Type: Non-Releaseable
- UV Resistant: No
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



2243134 250 mm

RS PRO CABLE TIE, 280MM X 4.8 MM, BLUE NYLON

Pack size: **100 x EA**

- Length: 280 mm
- Width: 4.8 mm
- Colour: Blue
- Material: Nylon 66
- Type: Non-Releaseable
- UV Resistant: No
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



2243138 280 mm

RS PRO CABLE TIE, 280MM X 4.8 MM, BLACK NYLON

Pack size: **100 x EA**

- Length: 280 mm
- Width: 4.8 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releaseable
- UV Resistant: No
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



2243139 280 mm

RS PRO CABLE TIE, 280MM X 4.8 MM, BLACK NYLON

Pack size: **100 x EA**

- Length: 280 mm
- Width: 4.8 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releaseable
- UV Resistant: Yes
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



2243141 280 mm

RS PRO CABLE TIE, 280MM X 4.8 MM, YELLOW NYLON

Pack size: **100 x EA**

- Length: 280 mm
- Width: 4.8 mm
- Colour: Yellow
- Material: Nylon 66
- Type: Non-Releaseable
- UV Resistant: No
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



2243143 280 mm

RS PRO CABLE TIE, 300MM X 4.8 MM, NATURAL

Pack size: **100 x EA**

- Length: 300 mm
- Width: 4.8 mm
- Colour: Natural
- Type: Non-Releaseable
- UV Resistant: No
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +150 °C
- Fire Behaviour: Self-extinguishing



2243146 300 mm

RS PRO CABLE TIE, 360MM X 7.6 MM, BLACK NYLON

Pack size: **100 x EA**

- Length: 360 mm
- Width: 7.6 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releaseable
- UV Resistant: Yes
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



2243147 360 mm

RS PRO CABLE TIE, 368MM X 4.8 MM NYLON

Pack size: **100 x EA**

- Length: 368 mm
- Width: 4.8 mm
- Material: Nylon 66
- Type: Non-Releaseable
- UV Resistant: No
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +105 °C
- Fire Behaviour: Self-extinguishing



2243148 368 mm

RS PRO CABLE TIE, 368MM X 4.8 MM, WHITE NYLON

Pack size: **100 x EA**

- Length: 368 mm
- Width: 4.8 mm
- Colour: White
- Material: Nylon 66
- Type: Non-Releaseable
- UV Resistant: No
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



2243149 368 mm

RS PRO CABLE TIE, 380MM X 7.6 MM, BLUE NYLON

Pack size: **100 x EA**

- Length: 380 mm
- Width: 7.6 mm
- Colour: Blue
- Material: Nylon 66
- Type: Non-Releaseable
- UV Resistant: No
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



2243151 380 mm

RS PRO CABLE TIE, 380MM X 7.6 MM, NATURAL NYLON

Pack size: **100 x EA**

- Length: 380 mm
- Width: 7.6 mm
- Colour: Natural
- Material: Nylon 66
- Type: Non-Releaseable
- UV Resistant: No
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +150 °C



2243154 380 mm

RS PRO CABLE TIE, 380MM X 7.6 MM, RED NYLON

Pack size: **100 x EA**

- Length: 380 mm
- Width: 7.6 mm
- Colour: Red
- Material: Nylon 66
- Type: Non-Releaseable
- UV Resistant: No
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



2243155 380 mm

RS PRO CABLE TIE, 385MM X 4.8 MM, BLACK NYLON

Pack size: **100 x EA**

- Length: 385 mm
- Width: 4.8 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releaseable
- UV Resistant: No
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



2243161 385 mm

RS PRO CABLE TIE, 385MM X 4.8 MM, RED NYLON

Pack size: **100 x EA**

- Length: 385 mm
- Width: 4.8 mm
- Colour: Red
- Material: Nylon 66
- Type: Non-Releaseable
- UV Resistant: No
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



2243166 385 mm

RS PRO CABLE TIE, 450MM X 8 MM, BLACK NYLON

Pack size: **100 x EA**

- Length: 450 mm
- Width: 8 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releaseable
- UV Resistant: No
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +105 °C



2243168 450 mm

RS PRO CABLE TIE, 450MM X 4.8 MM, BLACK NYLON

Pack size: **500 x EA**

- Length: 450 mm
- Width: 4.8 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releaseable
- UV Resistant: No
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



2243169 450 mm

RS PRO CABLE TIE, 610MM X 7.6 MM, NATURAL NYLON

Pack size: **50 x EA**

- Length: 610 mm
- Width: 7.6 mm
- Colour: Natural
- Material: Nylon 66
- Type: Non-Releaseable
- UV Resistant: No
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



2243171 610 mm

RS PRO CABLE TIE, 610MM X 7.6 MM, BLACK NYLON

Pack size: **50 x EA**

- Length: 610 mm
- Width: 7.6 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releaseable
- UV Resistant: No
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



2243172 610 mm

RS PRO CABLE TIE, 610MM X 7.6 MM, BLACK NYLON

Pack size: **50 x EA**

- Length: 610 mm
- Width: 7.6 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releaseable
- UV Resistant: No
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



2243173 610 mm

RS PRO CABLE TIE, 370MM X 4.8 MM, BLACK NYLON

Pack size: **100 x EA**

- Length: 370 mm
- Width: 4.8 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releaseable
- UV Resistant: No
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



2243175 370 mm

RS PRO CABLE TIE, 940MM X 9 MM, BLACK NYLON

Pack size: **25 x EA**

- Length: 940 mm
- Width: 9 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releasable
- UV Resistant: No
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



2243174 940 mm

RS PRO CABLE TIE, RELEASABLE, 200MM X 7.6 MM, BLACK NYLON

Pack size: **100 x EA**

- Length: 200 mm
- Width: 7.6 mm
- Colour: Black
- Material: Nylon 66
- Type: Releasable
- UV Resistant: No
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



2243180 200 mm

RS PRO CABLE TIE, 250MM X 7.6 MM, BLACK NYLON

Pack size: **100 x EA**

- Length: 250 mm
- Width: 7.6 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releasable
- UV Resistant: Yes
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



2243181 250 mm

RS PRO CABLE TIE, 112MM X 2.5 MM, NATURAL NYLON

Pack size: **25 x EA**

- Length: 112 mm
- Width: 2.5 mm
- Colour: Natural
- Material: Nylon 66
- Type: Non-Releasable
- UV Resistant: No
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



2243189 112 mm

RS PRO CABLE TIE, 200MM X 4.6 MM, RED NYLON

Pack size: **25 x EA**

- Length: 200 mm
- Width: 4.6 mm
- Colour: Red
- Material: Nylon 66
- Type: Non-Releasable
- UV Resistant: No
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



2243194 200 mm

RS PRO CABLE TIE, 200MM X 4.6 MM, YELLOW NYLON

Pack size: **100 x EA**

- Length: 200 mm
- Width: 4.6 mm
- Colour: Yellow
- Material: Nylon 66
- Type: Non-Releasable
- UV Resistant: No
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



2243195 200 mm

RS PRO CABLE TIE, 300MM X 4.8 MM, NATURAL NYLON

Pack size: **100 x EA**

- Length: 300 mm
- Width: 4.8 mm
- Colour: Natural
- Material: Nylon 66
- Type: Non-Releasable
- UV Resistant: No
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



2243196 300 mm

RS PRO CABLE TIE, 370MM X 4.8 MM, NATURAL NYLON

Pack size: **100 x EA**

- Length: 370 mm
- Width: 4.8 mm
- Colour: Natural
- Material: Nylon 66
- Type: Non-Releasable
- UV Resistant: No
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



2243197 370 mm

RS PRO CABLE TIE, 150MM X 2.9 MM, NATURAL NYLON

Pack size: **100 x EA**

- Length: 150 mm
- Width: 2.9 mm
- Colour: Natural
- Material: Nylon 66
- Type: Non-Releasable
- UV Resistant: No
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



2243199 150 mm

RS PRO CABLE TIE, HOOK AND LOOP, 150MM X 20 MM, BLACK FABRIC

Pack size: **25 x EA**

- Length: 150 mm
- Width: 20 mm
- Colour: Black
- Material: Fabric
- Type: Hook and Loop



2854562 150 mm

RS PRO CABLE TIE, HOOK AND LOOP, 203.5MM X 12 MM, BLACK FABRIC

Pack size: **25 x EA**

- Length: 203.5 mm
- Width: 12 mm
- Colour: Black
- Material: Fabric
- Type: Hook and Loop



2854578 203.5 mm

RS PRO CABLE TIE, HOOK AND LOOP, 305MM X 12 MM, BLACK FABRIC

Pack size: **25 x EA**

- Length: 305 mm
- Width: 12 mm
- Colour: Black
- Material: Fabric
- Type: Hook and Loop



2854584 305 mm

RICHCO CABLE TIE, STANDARD, 150MM X 3.6 MM, NATURAL NYLON,

Pack size: **100 x EA**

- Length: 150 mm
- Width: 3.6 mm
- Colour: Natural
- Material: Polypropylene
- Type: Standard
- Quantity: 100
- Minimum Operating Temperature: -50 °C
- Maximum Operating Temperature: +120 °C



3210092 150 mm

RICHCO CABLE TIE, RELEASABLE, 152.4MM X 2.4 MM, BLUE

Pack size: **100 x EA**

- Length: 152.4 mm
- Width: 2.4 mm
- Colour: Blue
- Material: Polypropylene
- Type: Releasable
- Quantity: 100
- Series: BT
- Maximum Bundle Diameter: 44.5 mm



3212543 152.4 mm

RS PRO CABLE TIE, 203MM X 4.6 MM, NATURAL NYLON, PK-100

Pack size: **100 x EA**

- Length: 203 mm
- Width: 4.6 mm
- Colour: Natural
- Material: Nylon 66
- Type: Non-Releasable
- Quantity: 100
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



4892140 203 mm

RS PRO CABLE TIE, 300MM X 4.8 MM, NATURAL NYLON, PK-100

Pack size: **100 x EA**

- Length: 300 mm
- Width: 4.8 mm
- Colour: Natural
- Material: Nylon 66
- Type: Non-Releasable
- Quantity: 100
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



4892156 300 mm

RS PRO CABLE TIE, 100MM X 2.5 MM, NATURAL NYLON, PK-1000

Pack size: **1000 x EA**

- Length: 100 mm
- Width: 2.5 mm
- Colour: Natural
- Material: Nylon 66
- Type: Non-Releaseable
- Quantity: 1000
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



4920447 100 mm

RS PRO CABLE TIE, 150MM X 3.6 MM, NATURAL NYLON, PK-1000

Pack size: **1000 x EA**

- Length: 150 mm
- Width: 3.6 mm
- Colour: Natural
- Material: Nylon 66
- Type: Non-Releaseable
- Quantity: 1000
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



4920453 150 mm

RS PRO CABLE TIE, 190MM X 4.8 MM, NATURAL NYLON, PK-1000

Pack size: **1000 x EA**

- Length: 190 mm
- Width: 4.8 mm
- Colour: Natural
- Material: Nylon 66
- Type: Non-Releaseable
- Quantity: 1000
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



4920469 190 mm

RS PRO CABLE TIE, ROLLER BALL, 520MM X 4.6 MM, METALLIC 316

Pack size: **100 x EA**

- Length: 520 mm
- Width: 4.6 mm
- Colour: Metallic
- Material: 316 Stainless Steel
- Type: Roller Ball
- Quantity: 100
- Minimum Operating Temperature: -80 °C
- Maximum Operating Temperature: +538 °C



5474305 520 mm

RS PRO CABLE TIE, ROLLER BALL, 520MM X 7.9 MM, METALLIC 316

Pack size: **100 x EA**

- Length: 520 mm
- Width: 7.9 mm
- Colour: Metallic
- Material: 316 Stainless Steel
- Type: Roller Ball
- Quantity: 100
- Minimum Operating Temperature: -80 °C
- Maximum Operating Temperature: +538 °C



5474311 520 mm

RS PRO CABLE TIE, ROLLER BALL, 200MM X 4.6 MM, BLACK POLYESTER

Pack size: **100 x EA**

- Length: 200 mm
- Width: 4.6 mm
- Colour: Black
- Material: Polyester Coated Stainless Steel
- Type: Roller Ball
- Quantity: 100
- Minimum Operating Temperature: -80 °C
- Maximum Operating Temperature: +150 °C



5474327 200 mm

RS PRO CABLE TIE, ROLLER BALL, 360MM X 4.6 MM, BLACK POLYESTER

Pack size: **100 x EA**

- Length: 360 mm
- Width: 4.6 mm
- Colour: Black
- Material: Polyester Coated Stainless Steel
- Type: Roller Ball
- Quantity: 100
- Minimum Operating Temperature: -80 °C
- Maximum Operating Temperature: +150 °C



5474333 360 mm

RS PRO CABLE TIE, ROLLER BALL, 200MM X 7.9 MM, METALLIC

Pack size: **100 x EA**

- Length: 200 mm
- Width: 7.9 mm
- Colour: Metallic
- Material: Polyester Coated Stainless Steel
- Type: Roller Ball
- Quantity: 100
- Minimum Operating Temperature: -80 °C
- Maximum Operating Temperature: +150 °C



5474355 200 mm

RS PRO CABLE TIE, ROLLER BALL, 360MM X 7.9 MM, METALLIC

Pack size: **100 x EA**

- Length: 360 mm
- Width: 7.9 mm
- Colour: Metallic
- Material: Polyester Coated Stainless Steel
- Type: Roller Ball
- Quantity: 100
- Minimum Operating Temperature: -80 °C
- Maximum Operating Temperature: +150 °C



5474377 360 mm

RS PRO CABLE TIE, RELEASABLE, 230MM X 10 MM, METALLIC 316

Pack size: **100 x EA**

- Length: 230 mm
- Width: 10 mm
- Colour: Metallic
- Material: 316 Stainless Steel
- Type: Releaseable
- Quantity: 100
- UV Resistant: Yes
- Minimum Operating Temperature: -80 °C



5474399 230 mm

RS PRO CABLE TIE, RELEASABLE, 450MM X 10 MM, METALLIC 316

Pack size: **100 x EA**

- Length: 450 mm
- Width: 10 mm
- Colour: Metallic
- Material: 316 Stainless Steel
- Type: Releaseable
- Quantity: 100
- Minimum Operating Temperature: -80 °C
- Maximum Operating Temperature: +150 °C



5474406 450 mm

RS PRO CABLE TIE, ROLLER BALL, 125MM X 4.6 MM, METALLIC 316

Pack size: **100 x EA**

- Length: 125 mm
- Width: 4.6 mm
- Colour: Metallic
- Material: 316 Stainless Steel
- Type: Roller Ball
- Quantity: 100
- Minimum Operating Temperature: -80 °C
- Maximum Operating Temperature: +538 °C



5474434 125 mm

RS PRO CABLE TIE, SUB MINIATURE, 71MM X 1.6 MM, WHITE NYLON, PK-

Pack size: **100 x EA**

- Length: 71 mm
- Width: 1.6 mm
- Colour: White
- Material: Nylon 66
- Type: Sub Miniature
- Quantity: 100
- Fire Behaviour: Flame Retardant
- Tensile Strength: 78.4 N



6642883 71 mm

RS PRO CABLE TIE, SUB MINIATURE, 71MM X 1.6 MM, BLACK NYLON, PK-

Pack size: **100 x EA**

- Length: 71 mm
- Width: 1.6 mm
- Colour: Black
- Material: Nylon 66
- Type: Sub Miniature
- Quantity: 100
- UV Resistant: Yes
- Fire Behaviour: Flame Retardant



6642887 71 mm

RS PRO CABLE TIE, DOUBLE LOCKING, 132MM X 9 MM, BLACK NYLON, PK-

Pack size: **100 x EA**

- Length: 132 mm
- Width: 9 mm
- Colour: Black
- Material: Nylon 66
- Type: Double Locking
- Quantity: 100
- Fire Behaviour: Flame Retardant
- Tensile Strength: 343 N



6644672 132 mm

RS PRO CABLE TIE, DOUBLE LOCKING, 180MM X 9 MM, BLACK NYLON, PK-

Pack size: **100 x EA**

- Length: 180 mm
- Width: 9 mm
- Colour: Black
- Material: Nylon 66
- Type: Double Locking
- Quantity: 100
- Fire Behaviour: Flame Retardant
- Tensile Strength: 343 N



6644675 180 mm

RS PRO CABLE TIE, DOUBLE LOCKING, 235MM X 9 MM, BLACK NYLON, PK-

Pack size: **100 x EA**

- Length: 235 mm
- Width: 9 mm
- Colour: Black
- Material: Nylon 66
- Type: Double Locking
- Quantity: 100
- Fire Behaviour: Flame Retardant
- Tensile Strength: 539 N



6664679 235 mm

RS PRO CABLE TIE, DOUBLE LOCKING, 300MM X 9 MM, BLACK NYLON, PK-

Pack size: **100 x EA**

- Length: 300 mm
- Width: 9 mm
- Colour: Black
- Material: Nylon 66
- Type: Double Locking
- Quantity: 100
- Fire Behaviour: Flame Retardant
- Tensile Strength: 539 N



6664681 300 mm

RS PRO CABLE TIE, DOUBLE LOCKING, 360MM X 9 MM, BLACK NYLON, PK-

Pack size: **100 x EA**

- Length: 360 mm
- Width: 9 mm
- Colour: Black
- Material: Nylon 66
- Type: Double Locking
- Quantity: 100
- Fire Behaviour: Flame Retardant
- Tensile Strength: 539 N



6664685 360 mm

RS PRO CABLE TIE, DOUBLE LOCKING, 265MM X 9 MM, BLACK NYLON, PK-

Pack size: **100 x EA**

- Length: 265 mm
- Width: 9 mm
- Colour: Black
- Material: Nylon 66
- Type: Double Locking
- Quantity: 100
- Fire Behaviour: Flame Retardant
- Tensile Strength: 539 N



6664688 265 mm

RS PRO CABLE TIE, DOUBLE LOCKING, 760MM X 9 MM, BLACK NYLON, PK-

Pack size: **100 x EA**

- Length: 760 mm
- Width: 9 mm
- Colour: Black
- Material: Nylon 66
- Type: Double Locking
- Quantity: 100
- Fire Behaviour: Flame Retardant
- Tensile Strength: 539 N



6664691 760 mm

RS PRO CABLE TIE, DOUBLE LOCKING, 510MM X 9 MM, BLACK NYLON, PK-

Pack size: **100 x EA**

- Length: 510 mm
- Width: 9 mm
- Colour: Black
- Material: Nylon 66
- Type: Double Locking
- Quantity: 100
- Fire Behaviour: Flame Retardant
- Tensile Strength: 539 N



6664694 510 mm

RS PRO CABLE TIE, DOUBLE LOCKING, 610MM X 9 MM, BLACK NYLON, PK-

Pack size: **100 x EA**

- Length: 610 mm
- Width: 9 mm
- Colour: Black
- Material: Nylon 66
- Type: Double Locking
- Quantity: 100
- Fire Behaviour: Flame Retardant
- Tensile Strength: 539 N



6664697 610 mm

RS PRO CABLE TIE, DOUBLE LOCKING, 300MM X 9 MM, NATURAL NYLON, PK-

Pack size: **100 x EA**

- Length: 300 mm
- Width: 9 mm
- Colour: Natural
- Material: Nylon 66
- Type: Double Locking
- Quantity: 100
- Fire Behaviour: Flame Retardant
- Tensile Strength: 539 N



6664710 300 mm

RS PRO CABLE TIE, DOUBLE LOCKING, 760MM X 9 MM, NATURAL NYLON, PK-

Pack size: **100 x EA**

- Length: 760 mm
- Width: 9 mm
- Colour: Natural
- Material: Nylon 66
- Type: Double Locking
- Quantity: 100
- Fire Behaviour: Flame Retardant
- Tensile Strength: 539 N



6664720 760 mm

RS PRO CABLE TIE, DOUBLE LOCKING, 510MM X 9 MM, NATURAL NYLON, PK-

Pack size: **100 x EA**

- Length: 510 mm
- Width: 9 mm
- Colour: Natural
- Material: Nylon 66
- Type: Double Locking
- Quantity: 100
- Fire Behaviour: Flame Retardant
- Tensile Strength: 539 N



6664723 510 mm

RS PRO CABLE TIE, ROLLER BALL, 680MM X 7.9 MM, METALLIC 316

Pack size: **100 x EA**

- Length: 680 mm
- Width: 7.9 mm
- Colour: Metallic
- Material: 316 Stainless Steel
- Type: Roller Ball
- Quantity: 100
- Minimum Operating Temperature: -80 °C
- Maximum Operating Temperature: +538 °C



7436166 680 mm

RS PRO CABLE TIE, ROLLER BALL, 150MM X 4.6 MM, METALLIC 316

Pack size: **100 x EA**

- Length: 150 mm
- Width: 4.6 mm
- Colour: Metallic
- Material: 316 Stainless Steel
- Type: Roller Ball
- Quantity: 100
- Minimum Operating Temperature: -80 °C
- Maximum Operating Temperature: +538 °C



7436169 150 mm

RS PRO CABLE TIE, ROLLER BALL, 1M X 4.6 MM, METALLIC 316 STAINLESS

Pack size: **100 x EA**

- Length: 1 m
- Width: 4.6 mm
- Colour: Metallic
- Material: 316 Stainless Steel
- Type: Roller Ball
- Quantity: 100
- Minimum Operating Temperature: -80 °C
- Maximum Operating Temperature: +538 °C



7436172 1 m

RS PRO CABLE TIE, ROLLER BALL, 840MM X 4.6 MM, METALLIC 316

Pack size: **100 x EA**

- Length: 840 mm
- Width: 4.6 mm
- Colour: Metallic
- Material: 316 Stainless Steel
- Type: Roller Ball
- Quantity: 100
- Minimum Operating Temperature: -80 °C
- Maximum Operating Temperature: +538 °C



7436175 840 mm

RS PRO CABLE TIE, ROLLER BALL, 840MM X 7.9 MM, METALLIC 316

Pack size: **100 x EA**

- Length: 840 mm
- Width: 7.9 mm
- Colour: Metallic
- Material: 316 Stainless Steel
- Type: Roller Ball
- Quantity: 100
- Minimum Operating Temperature: -80 °C
- Maximum Operating Temperature: +538 °C



7436178 840 mm

RS PRO CABLE TIE, ROLLER BALL, 100MM X 4.6 MM, BLACK POLYESTER

Pack size: **100 x EA**

- Length: 100 mm
- Width: 4.6 mm
- Colour: Black
- Material: Polyester Coated Stainless Steel
- Type: Roller Ball
- Quantity: 100
- Minimum Operating Temperature: -80 °C
- Maximum Operating Temperature: +150 °C



7436184 100 mm

RS PRO CABLE TIE, ROLLER BALL, 680MM X 4.6 MM, BLACK POLYESTER

Pack size: **100 x EA**

- Length: 680 mm
- Width: 4.6 mm
- Colour: Black
- Material: Polyester Coated Stainless Steel
- Type: Roller Ball
- Quantity: 100
- Minimum Operating Temperature: -80 °C
- Maximum Operating Temperature: +150 °C



7436190 680 mm

RS PRO CABLE TIE, ROLLER BALL, 680MM X 7.9 MM, BLACK POLYESTER

Pack size: **100 x EA**

- Length: 680 mm
- Width: 7.9 mm
- Colour: Black
- Material: Polyester Coated Stainless Steel
- Type: Roller Ball
- Quantity: 100
- Minimum Operating Temperature: -80 °C
- Maximum Operating Temperature: +150 °C



7436194 680 mm

RS PRO CABLE TIE, ROLLER BALL, 150MM X 4.6 MM, BLACK POLYESTER

Pack size: **100 x EA**

- Length: 150 mm
- Width: 4.6 mm
- Colour: Black
- Material: Polyester Coated Stainless Steel
- Type: Roller Ball
- Quantity: 100
- Minimum Operating Temperature: -80 °C
- Maximum Operating Temperature: +150 °C



7436197 150 mm

RS PRO CABLE TIE, ROLLER BALL, 100MM X 4.6 MM, YELLOW

Pack size: **100 x EA**

- Length: 100 mm
- Width: 4.6 mm
- Colour: Yellow
- Material: Polyester Coated Stainless Steel
- Type: Roller Ball
- Quantity: 100
- Minimum Operating Temperature: -80 °C
- Maximum Operating Temperature: +150 °C



7436239 100 mm

RS PRO CABLE TIE, ROLLER BALL, 150MM X 4.6 MM, YELLOW

Pack size: **100 x EA**

- Length: 150 mm
- Width: 4.6 mm
- Colour: Yellow
- Material: Polyester Coated Stainless Steel
- Type: Roller Ball
- Quantity: 100
- Minimum Operating Temperature: -80 °C
- Maximum Operating Temperature: +150 °C



7436241 150 mm

RS PRO CABLE TIE, ROLLER BALL, 360MM X 4.6 MM, GREEN POLYESTER

Pack size: **100 x EA**

- Length: 360 mm
- Width: 4.6 mm
- Colour: Green
- Material: Polyester Coated Stainless Steel
- Type: Roller Ball
- Quantity: 100
- Minimum Operating Temperature: -80 °C
- Maximum Operating Temperature: +150 °C




7436273 360 mm

RS PRO CABLE TIE, ROLLER BALL, 150MM X 4.6 MM, BLUE POLYESTER

Pack size: **100 x EA**

- Length: 150 mm
- Width: 4.6 mm
- Colour: Blue
- Material: Polyester Coated Stainless Steel
- Type: Roller Ball
- Quantity: 100
- Minimum Operating Temperature: -80 °C
- Maximum Operating Temperature: +150 °C



7436298 150 mm

RS PRO CABLE TIE, ZIG ZAG, 125MM X 4.6 MM, METALLIC 316 STAINLESS

Pack size: **100 x EA**

- Length: 125 mm
- Width: 4.6 mm
- Colour: Metallic
- Material: 316 Stainless Steel
- Type: Zig Zag
- Quantity: 100
- Minimum Operating Temperature: -80 °C
- Maximum Operating Temperature: +540 °C



7436336 125 mm

RS PRO CABLE TIE, ZIG ZAG, 360MM X 4.6 MM, METALLIC 316 STAINLESS

Pack size: **100 x EA**

- Length: 360 mm
- Width: 4.6 mm
- Colour: Metallic
- Material: 316 Stainless Steel
- Type: Zig Zag
- Quantity: 100
- Minimum Operating Temperature: -80 °C
- Maximum Operating Temperature: +540 °C



7436346 360 mm

RS PRO CABLE TIE, ZIG ZAG, 520MM X 7.9 MM, METALLIC 316 STAINLESS

Pack size: **100 x EA**

- Length: 520 mm
- Width: 7.9 mm
- Colour: Metallic
- Material: 316 Stainless Steel
- Type: Zig Zag
- Quantity: 100
- Minimum Operating Temperature: -80 °C
- Maximum Operating Temperature: +540 °C



7436352 520 mm

RS PRO CABLE TIE, ZIG ZAG, 360MM X 7.9 MM, METALLIC 316 STAINLESS

Pack size: **100 x EA**

- Length: 360 mm
- Width: 7.9 mm
- Colour: Metallic
- Material: 316 Stainless Steel
- Type: Zig Zag
- Quantity: 100
- Minimum Operating Temperature: -80 °C
- Maximum Operating Temperature: +540 °C



7436355 360 mm

RS PRO CABLE TIE, ZIG ZAG, 520MM X 4.6 MM, METALLIC 316 STAINLESS

Pack size: **100 x EA**

- Length: 520 mm
- Width: 4.6 mm
- Colour: Metallic
- Material: 316 Stainless Steel
- Type: Zig Zag
- Quantity: 100
- Minimum Operating Temperature: -80 °C
- Maximum Operating Temperature: +540 °C



7436358 520 mm

RS PRO CABLE TIE, 100MM X 4.6 MM, BLACK STAINLESS STEEL

Pack size: **100 x EA**

- Length: 100 mm
- Width: 4.6 mm
- Colour: Black
- Material: Stainless Steel



7436361 100 mm

RS PRO CABLE TIE, ROLLER BALL, 440MM X 12 MM, METALLIC 316

Pack size: **100 x EA**

- Length: 440 mm
- Width: 12 mm
- Colour: Metallic
- Material: 316 Stainless Steel
- Type: Roller Ball
- Quantity: 100
- Minimum Operating Temperature: -80 °C
- Maximum Operating Temperature: +540 °C



7436399 440 mm

RS PRO CABLE TIE, ROLLER BALL, 440MM X 12 MM, METALLIC

Pack size: **100 x EA**

- Length: 440 mm
- Width: 12 mm
- Colour: Metallic
- Material: Polyester Coated Stainless Steel
- Type: Roller Ball
- Quantity: 100
- UV Resistant: Yes
- Minimum Operating Temperature: -80 °C



7436409 440 mm

RS PRO CABLE TIE, 100MM X 2.5 MM, BLACK NYLON, PK-100

Pack size: **100 x EA**

- Length: 100 mm
- Width: 2.5 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releaseable
- Quantity: 100
- UV Resistant: Yes
- Fire Behaviour: Flame Retardant



8111482 100 mm

RS PRO CABLE TIE, 142MM X 3.2 MM, BLACK NYLON, PK-100

Pack size: **100 x EA**

- Length: 142 mm
- Width: 3.2 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releaseable
- Quantity: 100
- UV Resistant: Yes
- Fire Behaviour: Flame Retardant



8111486 142 mm

RS PRO CABLE TIE, 385MM X 4.8 MM, BLACK NYLON, PK-100

Pack size: **100 x EA**

- Length: 385 mm
- Width: 4.8 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releaseable
- Quantity: 100
- UV Resistant: Yes
- Fire Behaviour: Flame Retardant



8111492 385 mm

RS PRO CABLE TIE, 190MM X 4.8 MM, BLACK NYLON, PK-100

Pack size: **100 x EA**

- Length: 190 mm
- Width: 4.8 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releaseable
- Quantity: 100
- UV Resistant: Yes
- Fire Behaviour: Flame Retardant



8111495 190 mm

RS PRO CABLE TIE, 203MM X 4.6 MM, BLACK NYLON, PK-100

Pack size: **100 x EA**

- Length: 203 mm
- Width: 4.6 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releaseable
- Quantity: 100
- UV Resistant: Yes
- Fire Behaviour: Flame Retardant



8111498 203 mm

RS PRO CABLE TIE, 450MM X 4.8 MM, BLACK NYLON, PK-100

Pack size: **100 x EA**

- Length: 450 mm
- Width: 4.8 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releaseable
- Quantity: 100
- UV Resistant: Yes
- Fire Behaviour: Flame Retardant



8111502 450 mm

RS PRO CABLE TIE, 380MM X 7.6 MM, BLACK NYLON, PK-100

Pack size: **100 x EA**

- Length: 380 mm
- Width: 7.6 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releaseable
- Quantity: 100
- UV Resistant: Yes
- Fire Behaviour: Flame Retardant



8111509 380 mm

RS PRO CABLE TIE, 300MM X 7.6 MM, BLACK NYLON, PK-100

Pack size: **100 x EA**

- Length: 300 mm
- Width: 7.6 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releaseable
- Quantity: 100
- UV Resistant: Yes
- Fire Behaviour: Flame Retardant



8111511 300 mm

RS PRO CABLE TIE, 450MM X 8 MM, BLACK NYLON, PK-100

Pack size: **100 x EA**

- Length: 450 mm
- Width: 8 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releaseable
- Quantity: 100
- UV Resistant: Yes
- Fire Behaviour: Flame Retardant



8111515 450 mm

RS PRO CABLE TIE, 240MM X 7.6 MM, BLACK NYLON, PK-100

Pack size: **100 x EA**

- Length: 240 mm
- Width: 7.6 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releaseable
- Quantity: 100
- UV Resistant: Yes
- Fire Behaviour: Flame Retardant



8111518 240 mm

RS PRO CABLE TIE, 385MM X 4.8 MM, NATURAL NYLON, PK-100

Pack size: **100 x EA**

- Length: 385 mm
- Width: 4.8 mm
- Colour: Natural
- Material: Nylon 66
- Type: Non-Releaseable
- Quantity: 100
- UV Resistant: Yes
- Fire Behaviour: Flame Retardant



8111530 385 mm

RS PRO CABLE TIE, 203MM X 4.6 MM, NATURAL NYLON, PK-100

Pack size: **100 x EA**

- Length: 203 mm
- Width: 4.6 mm
- Colour: Natural
- Material: Nylon 66
- Type: Non-Releaseable
- Quantity: 100
- UV Resistant: Yes
- Fire Behaviour: Flame Retardant



8111521 203 mm

RS PRO CABLE TIE, 610MM X 9 MM, BLACK NYLON, PK-100

Pack size: **100 x EA**

- Length: 610 mm
- Width: 9 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releaseable
- Quantity: 100
- UV Resistant: Yes
- Fire Behaviour: Flame Retardant



8111524 610 mm

RS PRO CABLE TIE, 450MM X 4.8 MM, NATURAL NYLON, PK-100

Pack size: **100 x EA**

- Length: 450 mm
- Width: 4.8 mm
- Colour: Natural
- Material: Nylon 66
- Type: Non-Releaseable
- Quantity: 100
- UV Resistant: Yes
- Fire Behaviour: Flame Retardant



8111533 450 mm

RS PRO CABLE TIE, 300MM X 4.8 MM, NATURAL NYLON, PK-100

Pack size: **100 x EA**

- Length: 300 mm
- Width: 4.8 mm
- Colour: Natural
- Material: Nylon 66
- Type: Non-Releaseable
- Quantity: 100
- UV Resistant: Yes
- Fire Behaviour: Flame Retardant



8111537 300 mm

RS PRO CABLE TIE, 300MM X 7.6 MM, NATURAL NYLON, PK-100

Pack size: **100 x EA**

- Length: 300 mm
- Width: 7.6 mm
- Colour: Natural
- Material: Nylon 66
- Type: Non-Releaseable
- Quantity: 100
- UV Resistant: Yes
- Fire Behaviour: Flame Retardant



8111543 300 mm

RS PRO CABLE TIE, 380MM X 7.6 MM, NATURAL NYLON, PK-100

Pack size: **100 x EA**

- Length: 380 mm
- Width: 7.6 mm
- Colour: Natural
- Material: Nylon 66
- Type: Non-Releaseable
- Quantity: 100
- UV Resistant: Yes
- Fire Behaviour: Flame Retardant



8111546 380 mm

RS PRO CABLE TIE, 240MM X 7.6 MM, NATURAL NYLON, PK-100

Pack size: **100 x EA**

- Length: 240 mm
- Width: 7.6 mm
- Colour: Natural
- Material: Nylon 66
- Type: Non-Releaseable
- Quantity: 100
- UV Resistant: Yes
- Fire Behaviour: Flame Retardant



8111549 240 mm

RS PRO CABLE TIE, 450MM X 8 MM, NATURAL NYLON, PK-100

Pack size: **100 x EA**

- Length: 450 mm
- Width: 8 mm
- Colour: Natural
- Material: Nylon 66
- Type: Non-Releaseable
- Quantity: 100
- UV Resistant: Yes
- Fire Behaviour: Flame Retardant



8111552 450 mm

RS PRO CABLE TIE, 610MM X 9 MM, NATURAL NYLON, PK-100

Pack size: **100 x EA**

- Length: 610 mm
- Width: 9 mm
- Colour: Natural
- Material: Nylon 66
- Type: Non-Releaseable
- Quantity: 100
- UV Resistant: Yes
- Fire Behaviour: Flame Retardant



8111555 610 mm

RS PRO CABLE TIE, 750MM X 7.5 MM, NATURAL NYLON, PK-100

Pack size: **100 x EA**

- Length: 750 mm
- Width: 7.5 mm
- Colour: Natural
- Material: Nylon 66
- Type: Non-Releaseable
- Quantity: 100
- UV Resistant: Yes
- Fire Behaviour: Flame Retardant



8111559 750 mm

RS PRO CABLE TIE, 142MM X 3.2 MM, NATURAL NYLON, PK-100

Pack size: **100 x EA**

- Length: 142 mm
- Width: 3.2 mm
- Colour: Natural
- Material: Nylon 66
- Type: Non-Releaseable
- Quantity: 100
- UV Resistant: Yes
- Fire Behaviour: Flame Retardant



8111561 142 mm

RS PRO CABLE TIE, 190MM X 4.8 MM, NATURAL NYLON, PK-100

Pack size: **100 x EA**

- Length: 190 mm
- Width: 4.8 mm
- Colour: Natural
- Material: Nylon 66
- Type: Non-Releaseable
- Quantity: 100
- UV Resistant: Yes
- Fire Behaviour: Flame Retardant



8111565 190 mm

RS PRO CABLE TIE, 100MM X 2.5 MM, NATURAL NYLON, PK-100

Pack size: **100 x EA**

- Length: 100 mm
- Width: 2.5 mm
- Colour: Natural
- Material: Nylon 66
- Type: Non-Releaseable
- Quantity: 100
- UV Resistant: Yes
- Fire Behaviour: Flame Retardant



8111568 100 mm

RS PRO CABLE TIE, HEAT STABILISED, 203MM X 2.5 MM, BLACK NYLON, PK-

Pack size: **100 x EA**

- Length: 203 mm
- Width: 2.5 mm
- Colour: Black
- Material: Nylon 66
- Type: Heat Stabilised
- Quantity: 100
- Maximum Operating Temperature: +105 °C
- Fire Behaviour: Flame Retardant



8111571 203 mm

RS PRO CABLE TIE, HEAT STABILISED, 142MM X 2.5 MM, BLACK NYLON, PK-

Pack size: **100 x EA**

- Length: 142 mm
- Width: 2.5 mm
- Colour: Black
- Material: Nylon 66
- Type: Heat Stabilised
- Quantity: 100
- Maximum Operating Temperature: +105 °C
- Fire Behaviour: Flame Retardant



8111574 142 mm

RS PRO CABLE TIE, HEAT STABILISED, 100MM X 2.5 MM, BLACK NYLON, PK-

Pack size: **100 x EA**

- Length: 100 mm
- Width: 2.5 mm
- Colour: Black
- Material: Nylon 66
- Type: Heat Stabilised
- Quantity: 100
- Maximum Operating Temperature: +105 °C
- Fire Behaviour: Flame Retardant



8111577 100 mm

RS PRO CABLE TIE, HEAT STABILISED, 150MM X 3.6 MM, BLACK NYLON, PK-

Pack size: **100 x EA**

- Length: 150 mm
- Width: 3.6 mm
- Colour: Black
- Material: Nylon 66
- Type: Heat Stabilised
- Quantity: 100
- Maximum Operating Temperature: +105 °C
- Fire Behaviour: Flame Retardant



8111580 150 mm

RS PRO CABLE TIE, HEAT STABILISED, 160MM X 4.8 MM, BLACK NYLON, PK-

Pack size: **100 x EA**

- Length: 160 mm
- Width: 4.8 mm
- Colour: Black
- Material: Nylon 66
- Type: Heat Stabilised
- Quantity: 100
- Maximum Operating Temperature: +105 °C
- Fire Behaviour: Flame Retardant



8111583 160 mm

RS PRO CABLE TIE, HEAT STABILISED, 180MM X 3.6 MM, BLACK NYLON, PK-

Pack size: **100 x EA**

- Length: 180 mm
- Width: 3.6 mm
- Colour: Black
- Material: Nylon 66
- Type: Heat Stabilised
- Quantity: 100
- Maximum Operating Temperature: +105 °C
- Fire Behaviour: Flame Retardant



8111587 180 mm

RS PRO CABLE TIE, HEAT STABILISED, 265MM X 3.6 MM, BLACK NYLON, PK-

Pack size: **100 x EA**

- Length: 265 mm
- Width: 3.6 mm
- Colour: Black
- Material: Nylon 66
- Type: Heat Stabilised
- Quantity: 100
- Maximum Operating Temperature: +105 °C
- Fire Behaviour: Flame Retardant



8111593 265 mm

RS PRO CABLE TIE, HEAT STABILISED, 203MM X 3.6 MM, BLACK NYLON, PK-

Pack size: **100 x EA**

- Length: 203 mm
- Width: 3.6 mm
- Colour: Black
- Material: Nylon 66
- Type: Heat Stabilised
- Quantity: 100
- Maximum Operating Temperature: +105 °C
- Fire Behaviour: Flame Retardant



8111596 203 mm

RS PRO CABLE TIE, HEAT STABILISED, 292MM X 3.6 MM, BLACK NYLON, PK-

Pack size: **100 x EA**

- Length: 292 mm
- Width: 3.6 mm
- Colour: Black
- Material: Nylon 66
- Type: Heat Stabilised
- Quantity: 100
- Maximum Operating Temperature: +105 °C
- Fire Behaviour: Flame Retardant



8111599 292 mm

RS PRO CABLE TIE, RELEASABLE, 150MM X 7.6 MM, BLACK NYLON, PK-

Pack size: **100 x EA**

- Length: 150 mm
- Width: 7.6 mm
- Colour: Black
- Material: Nylon 66
- Type: Releasable
- Quantity: 100
- Fire Behaviour: Flame Retardant
- Tensile Strength: 215.6 N



8111600 150 mm

RS PRO CABLE TIE, HEAT STABILISED, 203MM X 4.6 MM, BLACK NYLON, PK-

Pack size: **100 x EA**

- Length: 203 mm
- Width: 4.6 mm
- Colour: Black
- Material: Nylon 66
- Type: Heat Stabilised
- Quantity: 100
- Maximum Operating Temperature: +105 °C
- Fire Behaviour: Flame Retardant



8111603 203 mm

RS PRO CABLE TIE, HEAT STABILISED, 550MM X 12.7 MM, BLACK NYLON, PK-

Pack size: **100 x EA**

- Length: 550 mm
- Width: 12.7 mm
- Colour: Black
- Material: Nylon 66
- Type: Heat Stabilised
- Quantity: 100
- Maximum Operating Temperature: +105 °C
- Fire Behaviour: Self-extinguishing



8111606 550 mm

RS PRO CABLE TIE, RELEASABLE, 150MM X 7.6 MM, NATURAL NYLON,

Pack size: **100 x EA**

- Length: 150 mm
- Width: 7.6 mm
- Colour: Natural
- Material: Nylon 66
- Type: Releasable
- Quantity: 100
- Fire Behaviour: Flame Retardant
- Tensile Strength: 215.6 N



8111612 150 mm

RS PRO CABLE TIE, RELEASABLE, 250MM X 7.6 MM, NATURAL NYLON,

Pack size: **100 x EA**

- Length: 250 mm
- Width: 7.6 mm
- Colour: Natural
- Material: Nylon 66
- Type: Releasable
- Quantity: 100
- Fire Behaviour: Flame Retardant
- Tensile Strength: 215.6 N



8111616 250 mm

RS PRO CABLE TIE, RELEASABLE, 250MM X 7.6 MM, BLACK NYLON, PK-

Pack size: **100 x EA**

- Length: 250 mm
- Width: 7.6 mm
- Colour: Black
- Material: Nylon 66
- Type: Releasable
- Quantity: 100
- Fire Behaviour: Flame Retardant
- Tensile Strength: 215.6 N



8111619 250 mm

RS PRO CABLE TIE, HEAT STABILISED, 203MM X 2.5 MM, NATURAL NYLON,

Pack size: **100 x EA**

- Length: 203 mm
- Width: 2.5 mm
- Colour: Natural
- Material: Nylon 66
- Type: Heat Stabilised
- Quantity: 100
- Maximum Operating Temperature: +105 °C
- Fire Behaviour: Flame Retardant



8111622 203 mm

RS PRO CABLE TIE, HEAT STABILISED, 142MM X 2.5 MM, NATURAL NYLON,

Pack size: **100 x EA**

- Length: 142 mm
- Width: 2.5 mm
- Colour: Natural
- Material: Nylon 66
- Type: Heat Stabilised
- Quantity: 100
- Maximum Operating Temperature: +105 °C
- Fire Behaviour: Flame Retardant



8111625 142 mm

RS PRO CABLE TIE, HEAT STABILISED, 150MM X 3.6 MM, NATURAL NYLON,

Pack size: **100 x EA**

- Length: 150 mm
- Width: 3.6 mm
- Colour: Natural
- Material: Nylon 66
- Type: Heat Stabilised
- Quantity: 100
- Maximum Operating Temperature: +105 °C
- Fire Behaviour: Flame Retardant



8111631 150 mm

RS PRO CABLE TIE, HEAT STABILISED, 160MM X 4.8 MM, NATURAL NYLON,

Pack size: **100 x EA**

- Length: 160 mm
- Width: 4.8 mm
- Colour: Natural
- Material: Nylon 66
- Type: Heat Stabilised
- Quantity: 100
- Maximum Operating Temperature: +105 °C
- Fire Behaviour: Flame Retardant



8111634 160 mm

RS PRO CABLE TIE, HEAT STABILISED, 180MM X 3.6 MM, NATURAL NYLON,

Pack size: **100 x EA**

- Length: 180 mm
- Width: 3.6 mm
- Colour: Natural
- Material: Nylon 66
- Type: Heat Stabilised
- Quantity: 100
- Maximum Operating Temperature: +105 °C
- Fire Behaviour: Flame Retardant



8111638 180 mm

RS PRO CABLE TIE, HEAT STABILISED, 292MM X 3.6 MM, NATURAL NYLON,

Pack size: **100 x EA**

- Length: 292 mm
- Width: 3.6 mm
- Colour: Natural
- Material: Nylon 66
- Type: Heat Stabilised
- Quantity: 100
- Maximum Operating Temperature: +105 °C
- Fire Behaviour: Flame Retardant



8111640 292 mm

RS PRO CABLE TIE, HEAT STABILISED, 265MM X 3.6 MM, NATURAL NYLON,

Pack size: **100 x EA**

- Length: 265 mm
- Width: 3.6 mm
- Colour: Natural
- Material: Nylon 66
- Type: Heat Stabilised
- Quantity: 100
- Maximum Operating Temperature: +105 °C
- Fire Behaviour: Flame Retardant



8111644 265 mm

RS PRO CABLE TIE, HEAT STABILISED, 203MM X 3.6 MM, NATURAL NYLON,

Pack size: **100 x EA**

- Length: 203 mm
- Width: 3.6 mm
- Colour: Natural
- Material: Nylon 66
- Type: Heat Stabilised
- Quantity: 100
- Maximum Operating Temperature: +105 °C
- Fire Behaviour: Flame Retardant



8111647 203 mm

RS PRO CABLE TIE, 300MM X 4.8 MM, BLACK NYLON, PK-1000

Pack size: **1000 x EA**

- Length: 300 mm
- Width: 4.8 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releasable
- Quantity: 1000
- Fire Behaviour: Flame Retardant
- Maximum Bundle Diameter: 83 mm



8111650 300 mm

RS PRO CABLE TIE, HEAT STABILISED, 203MM X 4.6 MM, NATURAL NYLON,

Pack size: **100 x EA**

- Length: 203 mm
- Width: 4.6 mm
- Colour: Natural
- Material: Nylon 66
- Type: Heat Stabilised
- Quantity: 100
- Maximum Operating Temperature: +105 °C
- Fire Behaviour: Flame Retardant



8111653 203 mm

RS PRO CABLE TIE, 368MM X 4.8 MM, BLACK NYLON, PK-1000

Pack size: **1000 x EA**

- Length: 368 mm
- Width: 4.8 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releaseable
- Quantity: 1000
- Fire Behaviour: Flame Retardant
- Maximum Bundle Diameter: 105 mm



8111662 368 mm

RS PRO CABLE TIE, 203MM X 4.6 MM, BLACK NYLON, PK-1000

Pack size: **1000 x EA**

- Length: 203 mm
- Width: 4.6 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releaseable
- Quantity: 1000
- Fire Behaviour: Flame Retardant
- Tensile Strength: 215.6 N



8111666 203 mm

RS PRO CABLE TIE, 380MM X 7.6 MM, BLACK NYLON, PK-1000

Pack size: **1000 x EA**

- Length: 380 mm
- Width: 7.6 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releaseable
- Quantity: 1000
- Fire Behaviour: Flame Retardant
- Maximum Bundle Diameter: 105 mm



8111669 380 mm

RS PRO CABLE TIE, 610MM X 9 MM, BLACK NYLON, PK-100

Pack size: **100 x EA**

- Length: 610 mm
- Width: 9 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releaseable
- Quantity: 100
- Fire Behaviour: Flame Retardant
- Tensile Strength: 784 N



8111672 610 mm

RS PRO CABLE TIE, 550MM X 12.7 MM, BLACK NYLON, PK-100

Pack size: **100 x EA**

- Length: 550 mm
- Width: 12.7 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releaseable
- Quantity: 100
- Fire Behaviour: Flame Retardant
- Tensile Strength: 1117.2 N



8111675 550 mm

RS PRO CABLE TIE, 450MM X 8 MM, BLACK NYLON, PK-100

Pack size: **100 x EA**

- Length: 450 mm
- Width: 8 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releaseable
- Quantity: 100
- Fire Behaviour: Flame Retardant
- Tensile Strength: 588 N



8111678 450 mm

RS PRO CABLE TIE, 762MM X 9 MM, BLACK NYLON, PK-100

Pack size: **100 x EA**

- Length: 762 mm
- Width: 9 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releaseable
- Quantity: 100
- Fire Behaviour: Flame Retardant
- Tensile Strength: 784 N



8111681 762 mm

RS PRO CABLE TIE, 340MM X 7.6 MM, BLACK NYLON, PK-100

Pack size: **100 x EA**

- Length: 340 mm
- Width: 7.6 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releaseable
- Quantity: 100
- Fire Behaviour: Flame Retardant
- Tensile Strength: 539 N



8111684 340 mm

RS PRO CABLE TIE, 300MM X 7.6 MM, BLACK NYLON, PK-100

Pack size: **100 x EA**

- Length: 300 mm
- Width: 7.6 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releaseable
- Quantity: 100
- Fire Behaviour: Flame Retardant
- Tensile Strength: 539 N



8111688 300 mm

RS PRO CABLE TIE, 100MM X 2.5 MM, NATURAL NYLON, PK-1000

Pack size: **1000 x EA**

- Length: 100 mm
- Width: 2.5 mm
- Colour: Natural
- Material: Nylon 66
- Type: Non-Releaseable
- Quantity: 1000
- Fire Behaviour: Flame Retardant
- Tensile Strength: 78.4 N



8111690 100 mm

RS PRO CABLE TIE, 203MM X 2.5 MM, NATURAL NYLON, PK-100

Pack size: **100 x EA**

- Length: 203 mm
- Width: 2.5 mm
- Colour: Natural
- Material: Nylon 66
- Type: Non-Releaseable
- Quantity: 100
- Fire Behaviour: Flame Retardant
- Tensile Strength: 78.4 N



8111694 203 mm

RS PRO CABLE TIE, 250MM X 4.8 MM, BLACK NYLON, PK-100

Pack size: **100 x EA**

- Length: 250 mm
- Width: 4.8 mm
- Colour: Black
- Material: Nylon 66
- Type: Non-Releaseable
- Quantity: 100
- Fire Behaviour: Flame Retardant
- Tensile Strength: 215.6 N



8111697 250 mm

RS PRO CABLE TIE, 550MM X 12.7 MM, NATURAL NYLON, PK-100

Pack size: **100 x EA**

- Length: 550 mm
- Width: 12.7 mm
- Colour: Natural
- Material: Nylon 66
- Type: Non-Releaseable
- Quantity: 100
- Fire Behaviour: Flame Retardant
- Tensile Strength: 1117.2 N



8111701 550 mm

RS PRO CABLE TIE, 142MM X 2.5 MM, NATURAL NYLON, PK-100

Pack size: **100 x EA**

- Length: 142 mm
- Width: 2.5 mm
- Colour: Natural
- Material: Nylon 66
- Type: Non-Releaseable
- Quantity: 100
- Fire Behaviour: Flame Retardant
- Tensile Strength: 78.4 N



8111704 142 mm

RS PRO CABLE TIE, 385MM X 4.8 MM, NATURAL NYLON, PK-100

Pack size: **100 x EA**

- Length: 385 mm
- Width: 4.8 mm
- Colour: Natural
- Material: Nylon 66
- Type: Non-Releaseable
- Quantity: 100
- Fire Behaviour: Flame Retardant
- Tensile Strength: 215.6 N



8111707 385 mm

RS PRO CABLE TIE, 160MM X 4.8 MM, NATURAL NYLON, PK-100

Pack size: **100 x EA**

- Length: 160 mm
- Width: 4.8 mm
- Colour: Natural
- Material: Nylon 66
- Type: Non-Releaseable
- Quantity: 100
- Fire Behaviour: Flame Retardant
- Tensile Strength: 215.6 N



8111710 160 mm

RS PRO CABLE TIE, FLAME RETARDANT, 380MM X 12.7 MM,

Pack size: **50 x EA**

- Length: 380 mm
- Width: 12.7 mm
- Colour: Black
- Material: Nylon 66
- Type: Flame Retardant
- Quantity: 100
- Fire Behaviour: Flame Retardant
- Tensile Strength: 1117.2 N



8111741 380 mm

RS PRO CABLE TIE, FLAME RETARDANT, 480MM X 12.7 MM,

Pack size: **50 x EA**

- Length: 480 mm
- Width: 12.7 mm
- Colour: Black
- Material: Nylon 66
- Type: Flame Retardant
- Quantity: 100
- Fire Behaviour: Flame Retardant
- Tensile Strength: 1117.2 N



8111745 480 mm

RS PRO CABLE TIE, FLAME RETARDANT, 280MM X 12.7 MM,

Pack size: **50 x EA**

- Length: 280 mm
- Width: 12.7 mm
- Colour: Black
- Material: Nylon 66
- Type: Flame Retardant
- Quantity: 100
- Fire Behaviour: Flame Retardant
- Tensile Strength: 1117.2 N



8111748 280 mm

RS PRO CABLE TIE, FLAME RETARDANT, 550MM X 12.7 MM,

Pack size: **50 x EA**

- Length: 550 mm
- Width: 12.7 mm
- Colour: Black
- Material: Nylon 66
- Type: Flame Retardant
- Quantity: 100
- Fire Behaviour: Flame Retardant
- Tensile Strength: 1117.2 N



8111754 550 mm

RS PRO CABLE TIE, FLAME RETARDANT, 100MM X 2.5 MM, BLACK

Pack size: **100 x EA**

- Length: 100 mm
- Width: 2.5 mm
- Colour: Black
- Material: Nylon 66
- Type: Flame Retardant
- Quantity: 100
- Fire Behaviour: Flame Retardant
- Tensile Strength: 78.4 N



8111773 100 mm

RS PRO CABLE TIE, FLAME RETARDANT, 150MM X 3.6 MM, BLACK

Pack size: **100 x EA**

- Length: 150 mm
- Width: 3.6 mm
- Colour: Black
- Material: Nylon 66
- Type: Flame Retardant
- Quantity: 100
- Fire Behaviour: Flame Retardant
- Tensile Strength: 176.4 N



8111776 150 mm

RS PRO CABLE TIE, FLAME RETARDANT, 203MM X 4.8 MM,

Pack size: **100 x EA**

- Length: 203 mm
- Width: 4.8 mm
- Colour: Black
- Material: Nylon 66
- Type: Flame Retardant
- Quantity: 100
- Fire Behaviour: Flame Retardant
- Tensile Strength: 215.6 N



8111779 203 mm

RS PRO CABLE TIE, FLAME RETARDANT, 380MM X 7.6 MM,

Pack size: **100 x EA**

- Length: 380 mm
- Width: 7.6 mm
- Colour: Black
- Material: Nylon 66
- Type: Flame Retardant
- Quantity: 100
- Fire Behaviour: Flame Retardant
- Tensile Strength: 539 N



8111782 380 mm

RS PRO CABLE TIE, 111MM X 2.6 MM, NATURAL NYLON, PK-100

Pack size: **100 x EA**

- Length: 111 mm
- Width: 2.6 mm
- Colour: Natural
- Material: Nylon 66
- Type: Non-Releasable
- Quantity: 100
- Fire Behaviour: Flame Retardant
- Maximum Bundle Diameter: 20 mm



8111785 111 mm

RS PRO CABLE TIE, RELEASABLE, 125MM X 4.5 MM, BLACK NYLON, PK-

Pack size: **100 x EA**

- Length: 125 mm
- Width: 4.5 mm
- Colour: Black
- Material: Nylon 66
- Type: Releasable
- Quantity: 100
- Fire Behaviour: Flame Retardant
- Tensile Strength: 215.6 N



8111795 125 mm

RS PRO CABLE TIE, RELEASABLE, 250MM X 4.5 MM, BLACK NYLON, PK-

Pack size: **100 x EA**

- Length: 250 mm
- Width: 4.5 mm
- Colour: Black
- Material: Nylon 66
- Type: Releasable
- Quantity: 100
- Fire Behaviour: Flame Retardant
- Tensile Strength: 215.6 N



8111802 250 mm

RS PRO CABLE TIE, RELEASABLE, 150MM X 4.5 MM, BLACK NYLON, PK-

Pack size: **100 x EA**

- Length: 150 mm
- Width: 4.5 mm
- Colour: Black
- Material: Nylon 66
- Type: Releasable
- Quantity: 100
- Fire Behaviour: Flame Retardant
- Tensile Strength: 215.6 N



8111805 150 mm

RS PRO CABLE TIE, RELEASABLE, 200MM X 4.5 MM, BLACK NYLON, PK-

Pack size: **100 x EA**

- Length: 200 mm
- Width: 4.5 mm
- Colour: Black
- Material: Nylon 66
- Type: Releasable
- Quantity: 100
- Fire Behaviour: Flame Retardant
- Tensile Strength: 215.6 N



8111808 200 mm

RS PRO CABLE TIE, RELEASABLE, 300MM X 4.5 MM, BLACK NYLON, PK-

Pack size: **100 x EA**

- Length: 300 mm
- Width: 4.5 mm
- Colour: Black
- Material: Nylon 66
- Type: Releasable
- Quantity: 100
- Fire Behaviour: Flame Retardant
- Tensile Strength: 215.6 N



8111811 300 mm

RS PRO CABLE TIE, DOUBLE LOCKING, 132MM X 6 MM, BLACK NYLON, PK-

Pack size: **100 x EA**

- Length: 132 mm
- Width: 6 mm
- Colour: Black
- Material: Nylon 66
- Type: Double Locking
- Quantity: 100
- Fire Behaviour: Flame Retardant
- Tensile Strength: 22 kg



8659625 132 mm

RS PRO CABLE TIE, DOUBLE LOCKING, 180MM X 6 MM, BLACK NYLON, PK-

Pack size: **100 x EA**

- Length: 180 mm
- Width: 6 mm
- Colour: Black
- Material: Nylon 66
- Type: Double Locking
- Quantity: 100
- Fire Behaviour: Flame Retardant
- Tensile Strength: 22 kg



8659629 180 mm

RS PRO CABLE TIE, DOUBLE LOCKING, 382MM X 9 MM, BLACK NYLON, PK-

- Pack size: **100 x EA**
- Length: 382 mm
 - Width: 9 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Double Locking
 - Quantity: 100
 - Fire Behaviour: Flame Retardant
 - Tensile Strength: 55 kg



8659641 382 mm

RS PRO CABLE TIE, DOUBLE LOCKING, 292MM X 9 MM, BLACK NYLON, PK-

- Pack size: **100 x EA**
- Length: 292 mm
 - Width: 9 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Double Locking
 - Quantity: 100
 - Fire Behaviour: Flame Retardant
 - Tensile Strength: 55 kg



8659644 292 mm

RS PRO CABLE TIE, DOUBLE LOCKING, 760MM X 9 MM, BLACK NYLON, PK-

- Pack size: **100 x EA**
- Length: 760 mm
 - Width: 9 mm
 - Colour: Black
 - Material: Nylon 66
 - Type: Double Locking
 - Quantity: 100
 - Fire Behaviour: Flame Retardant
 - Tensile Strength: 55 kg



8659657 760 mm

RS PRO CRIMPING TOOL

- Pack size: **1 x EA**
- Crimp Tool Type: Crimping Tool
 - For Use With: Cable Bushings
 - Overall Length: 174 mm



392012 Crimping Tool

STRAIN RELIEF BUSH,5.6-6.22MM CABLE DIA

- Pack size: **25 x EA**
- Material: Nylon 66
 - Colour: Black



8178861 Nylon 66

STRAIN RELIEF BUSH,6.37-7.37MM CABLE DIA

- Pack size: **25 x EA**
- Material: Nylon 66
 - Colour: Black



8178870 Nylon 66

STRAIN RELIEF BUSH,7.6MM CABLE DIA

- Pack size: **25 x EA**
- Material: Nylon 66
 - Colour: Black



8178873 Nylon 66

STRAIN RELIEF BUSH,8.25-9.14MM CABLE DIA

- Pack size: **25 x EA**
- Material: Nylon 66
 - Colour: Black



8178877 Nylon 66

BREAK-AWAY FAN MOUNT 83,5MM

- Pack size: **50 x EA**
- Mount Type: Rivet



1720861 Rivet

FAN MOUNT RIVET 22,2MM 40 SHORE A

- Pack size: **50 x EA**
- Mount Type: Rivet



1720862 Rivet

CABLE, HEATSHRINK, SLEEVE, LOW TEMPERATURE, BORE 1.6MM

Pack size: **25 x MTR**

- Sleeve Diameter: 1.6 mm
- Shrunk Diameter: 0.8 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 25 m
- Material: Polyolefin



389628 1.6 mm

CABLE, HEATSHRINK, SLEEVE, LOW TEMPERATURE, BORE 2.4MM

Pack size: **25 x MTR**

- Sleeve Diameter: 2.4 mm
- Shrunk Diameter: 1.2 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 25 m
- Material: Polyolefin



389634 2.4 mm

RS PRO HEAT SHRINK TUBING, BLACK 3.2MM SLEEVE DIA. X 20M LENGTH 2:1

Pack size: **20 x MTR**

- Sleeve Diameter: 3.2 mm
- Shrunk Diameter: 1.6 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 20 m
- Material: Polyolefin



389640 3.2 mm

RS PRO HEAT SHRINK TUBING, BLACK 4.8MM SLEEVE DIA. X 20M LENGTH 2:1

Pack size: **20 x MTR**

- Sleeve Diameter: 4.8 mm
- Shrunk Diameter: 2.4 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 20 m
- Material: Polyolefin



389656 4.8 mm

CABLE, HEATSHRINK, SLEEVE, LOW TEMPERATURE, BORE 6.4MM

Pack size: **15 x MTR**

- Sleeve Diameter: 6.4 mm
- Shrunk Diameter: 3.2 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 15 m
- Material: Polyolefin



389662 6.4 mm

RS PRO HEAT SHRINK TUBING, BLACK 9.5MM SLEEVE DIA. X 12M LENGTH 2:1

Pack size: **12 x MTR**

- Sleeve Diameter: 9.5 mm
- Shrunk Diameter: 4.7 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 12 m
- Material: Polyolefin



389678 9.5 mm

CABLE, HEATSHRINK, SLEEVE, LOW TEMPERATURE, BORE 12.7MM

Pack size: **10 x MTR**

- Sleeve Diameter: 12.7 mm
- Shrunk Diameter: 6.3 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 10 m
- Material: Polyolefin



389684 12.7 mm

RS PRO HEAT SHRINK TUBING, BLACK 19MM SLEEVE DIA. X 6M LENGTH 2:1

Pack size: **6 x MTR**

- Sleeve Diameter: 19 mm
- Shrunk Diameter: 9.5 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 6 m
- Material: Polyolefin



389690 19 mm

CABLE, HEATSHRINK, SLEEVE, LOW TEMPERATURE, BORE 25.4MM

Pack size: **3 x MTR**

- Sleeve Diameter: 25.4 mm
- Shrunk Diameter: 12.7 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 3 m
- Material: Polyolefin



389707 25.4 mm

CABLE, HEATSHRINK, SLEEVE, WHITE, POLYOLEFIN, 1.2, BORE 1.6MM

Pack size: **5 x EA**

- Sleeve Diameter: 1.6 mm
- Shrunk Diameter: 0.8 mm
- Colour: White
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



392220 1.6 mm

CABLE, HEATSHRINK, SLEEVE, WHITE, POLYOLEFIN, 1.2, BORE 2.4MM

Pack size: **5 x EA**

- Sleeve Diameter: 2.4 mm
- Shrunk Diameter: 1.2 mm
- Colour: White
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



392236 2.4 mm

RS PRO HEAT SHRINK TUBING, WHITE 3.2MM SLEEVE DIA. X 1.2M LENGTH 2:1

Pack size: **5 x EA**

- Sleeve Diameter: 3.2 mm
- Shrunk Diameter: 1.6 mm
- Colour: White
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



392242 3.2 mm

RS PRO HEAT SHRINK TUBING, WHITE 4.8MM SLEEVE DIA. X 1.2M LENGTH 2:1

Pack size: **5 x EA**

- Sleeve Diameter: 4.8 mm
- Shrunk Diameter: 2.4 mm
- Colour: White
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



392258 4.8 mm

CABLE, HEATSHRINK, SLEEVE, WHITE, POLYOLEFIN, 1.2, BORE 6.4MM

Pack size: **5 x EA**

- Sleeve Diameter: 6.4 mm
- Shrunk Diameter: 3.2 mm
- Colour: White
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



392264 6.4 mm

CABLE, HEATSHRINK, SLEEVE, WHITE, POLYOLEFIN, 1.2, BORE 9.5MM

Pack size: **5 x EA**

- Sleeve Diameter: 9.5 mm
- Shrunk Diameter: 4.8 mm
- Colour: White
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



392270 9.5 mm

CABLE, HEATSHRINK, SLEEVE, WHITE, POLYOLEFIN, 1.2, BORE 12.7MM

Pack size: **5 x EA**

- Sleeve Diameter: 12.7 mm
- Shrunk Diameter: 6.4 mm
- Colour: White
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



392286 12.7 mm

RS PRO HEAT SHRINK TUBING, WHITE 19.1MM SLEEVE DIA. X 1.2M LENGTH

Pack size: **5 x EA**

- Sleeve Diameter: 19.1 mm
- Shrunk Diameter: 9.5 mm
- Colour: White
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



392292 19.1 mm

RS PRO HEAT SHRINK TUBING, WHITE 25.4MM SLEEVE DIA. X 1.2M LENGTH

Pack size: **5 x EA**

- Sleeve Diameter: 25.4 mm
- Shrunk Diameter: 12.7 mm
- Colour: White
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



392309 25.4 mm

RS PRO HEAT SHRINK TUBING, WHITE 38.1MM SLEEVE DIA. X 1.2M LENGTH

Pack size: **5 x EA**

- Sleeve Diameter: 38.1 mm
- Shrunk Diameter: 19.1 mm
- Colour: White
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



392315 38.1 mm

RS PRO HEAT SHRINK TUBING, WHITE 50.8MM SLEEVE DIA. X 1.2M LENGTH

Pack size: **5 x EA**

- Sleeve Diameter: 50.8 mm
- Shrunk Diameter: 25.4 mm
- Colour: White
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



392321 50.8 mm

CABLE, HEATSHRINK, SLEEVE, KIT, 1.0-6.4MM

Pack size: **1 x EA**

- Sleeve Diameter: 2.4 mm, 3 mm, 3.2 mm, 4.8 mm, 6.4 mm, 9.5 mm, 12.7 mm
- Shrunk Diameter: Assortment
- Colour: Black, Blue, Brown, Green/Yellow, Red, White, Yellow
- Sleeve Type: Heat Shrink
- Adhesive Lined: Yes
- Shrink Ratio: 2:1, 3:1
- Material: Polyolefin
- Flame Retardant: Yes



397679 2.4 mm, 3 mm,

CABLE, HEATSHRINK, SLEEVE, BLUE POLYOLEFIN, 1.2, BORE 1.6MM

Pack size: **5 x EA**

- Sleeve Diameter: 1.6 mm
- Shrunk Diameter: 0.8 mm
- Colour: Blue
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



397871 1.6 mm

CABLE, HEATSHRINK, SLEEVE, BLUE POLYOLEFIN, 1.2, BORE 2.4MM

Pack size: **5 x EA**

- Sleeve Diameter: 2.4 mm
- Shrunk Diameter: 1.2 mm
- Colour: Blue
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



397887 2.4 mm

CABLE, HEATSHRINK, SLEEVE, BLUE POLYOLEFIN, 1.2, BORE 3.2MM

Pack size: **5 x EA**

- Sleeve Diameter: 3.2 mm
- Shrunk Diameter: 1.6 mm
- Colour: Blue
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



397893 3.2 mm

RS PRO HEAT SHRINK TUBING, BLUE 4.8MM SLEEVE DIA. X 1.2M LENGTH 2:1

Pack size: **5 x EA**

- Sleeve Diameter: 4.8 mm
- Shrunk Diameter: 2.4 mm
- Colour: Blue
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



397900 4.8 mm

CABLE, HEATSHRINK, SLEEVE, BLUE POLYOLEFIN, 1.2, BORE 6.4MM

Pack size: **5 x EA**

- Sleeve Diameter: 6.4 mm
- Shrunk Diameter: 3.2 mm
- Colour: Blue
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



397916 6.4 mm

CABLE, HEATSHRINK, SLEEVE, BLUE POLYOLEFIN, 1.2, BORE 9.5MM

Pack size: **5 x EA**

- Sleeve Diameter: 9.5 mm
- Shrunk Diameter: 4.8 mm
- Colour: Blue
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



397922 9.5 mm

CABLE, HEATSHRINK, SLEEVE, BLUE POLYOLEFIN, 1.2, BORE 12.7MM

Pack size: **5 x EA**

- Sleeve Diameter: 12.7 mm
- Shrunk Diameter: 6.4 mm
- Colour: Blue
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin




397938 12.7 mm

RS PRO HEAT SHRINK TUBING, BLUE 19.1MM SLEEVE DIA. X 1.2M LENGTH

Pack size: **5 x EA**

- Sleeve Diameter: 19.1 mm
- Shrunk Diameter: 9.5 mm
- Colour: Blue
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



397944 19.1 mm

CABLE, HEATSHRINK, SLEEVE, BLUE POLYOLEFIN, 1.2, BORE 25.4MM

Pack size: **5 x EA**

- Sleeve Diameter: 25.4 mm
- Shrunk Diameter: 12.7 mm
- Colour: Blue
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin




397950 25.4 mm

CABLE, HEATSHRINK, SLEEVE, BLUE POLYOLEFIN, 1.2, BORE 38.0MM

Pack size: **5 x EA**

- Sleeve Diameter: 38.1 mm
- Shrunk Diameter: 19.1 mm
- Colour: Blue
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



397966 38.1 mm

RS PRO HEAT SHRINK TUBING, BLUE 50.8MM SLEEVE DIA. X 1.2M LENGTH

Pack size: **5 x EA**

- Sleeve Diameter: 50.8 mm
- Shrunk Diameter: 25.4 mm
- Colour: Blue
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



397972 50.8 mm

CABLE, HEATSHRINK, SLEEVE, RED, POLYOLEFIN, 1.2, BORE 1.6MM

Pack size: **5 x EA**

- Sleeve Diameter: 1.6 mm
- Shrunk Diameter: 0.8 mm
- Colour: Red
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



397988 1.6 mm

CABLE, HEATSHRINK, SLEEVE, RED, POLYOLEFIN, 1.2, BORE 2.4MM

Pack size: **5 x EA**

- Sleeve Diameter: 2.4 mm
- Shrunk Diameter: 1.2 mm
- Colour: Red
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



397994 2.4 mm

CABLE, HEATSHRINK, SLEEVE, GREEN/YELLOW, POLYOLEFIN, 1.2, BORE

Pack size: **5 x EA**

- Sleeve Diameter: 25.4 mm
- Shrunk Diameter: 12.7 mm
- Colour: Green
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



398032 25.4 mm

CABLE, HEATSHRINK, SLEEVE, GREEN/YELLOW, POLYOLEFIN, 1.2, BORE 19.0MM

Pack size: **5 x EA**

- Sleeve Diameter: 19.1 mm
- Shrunk Diameter: 9.5 mm
- Colour: Green
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



398048 19.1 mm

CABLE, HEATSHRINK, SLEEVE, GREEN/YELLOW, POLYOLEFIN, 1.2, BORE 9.5MM

Pack size: **5 x EA**

- Sleeve Diameter: 9.5 mm
- Shrunk Diameter: 4.8 mm
- Colour: Green
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



398060 9.5 mm

CABLE, HEATSHRINK, SLEEVE, GREEN/YELLOW, POLYOLEFIN, 1.2, BORE 12.7MM

Pack size: **5 x EA**

- Sleeve Diameter: 12.7 mm
- Shrunk Diameter: 6.4 mm
- Colour: Green
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



398054 12.7 mm

CABLE, HEATSHRINK, SLEEVE, GREEN/YELLOW, POLYOLEFIN, 1.2, BORE 6.4MM

Pack size: **5 x EA**

- Sleeve Diameter: 6.4 mm
- Shrunk Diameter: 3.2 mm
- Colour: Green
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



398076 6.4 mm

CABLE, HEATSHRINK, SLEEVE, GREEN/YELLOW, POLYOLEFIN, 1.2, BORE 4.8MM

Pack size: **5 x EA**

- Sleeve Diameter: 4.8 mm
- Shrunk Diameter: 2.4 mm
- Colour: Green, Yellow
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



398082 4.8 mm

CABLE, HEATSHRINK, SLEEVE, GREEN/YELLOW, POLYOLEFIN, 1.2, BORE 1.6MM

Pack size: **5 x EA**

- Sleeve Diameter: 3.2 mm
- Shrunk Diameter: 1.6 mm
- Colour: Green
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



398098 3.2 mm

CABLE, HEATSHRINK, SLEEVE, BLACK, POLYOLEFIN, 1.2, BORE 50.8MM

Pack size: **5 x EA**

- Sleeve Diameter: 50.8 mm
- Shrunk Diameter: 25.4 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



398127 50.8 mm

CABLE, HEATSHRINK, SLEEVE, BLACK, POLYOLEFIN, 1.2, BORE 38.0MM

Pack size: **5 x EA**

- Sleeve Diameter: 38.1 mm
- Shrunk Diameter: 19.1 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



398133 38.1 mm

CABLE, HEATSHRINK, SLEEVE, BLACK, POLYOLEFIN, 1.2, BORE 25.4MM

Pack size: **5 x EA**

- Sleeve Diameter: 25.4 mm
- Shrunk Diameter: 12.7 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



398149 25.4 mm

CABLE, HEATSHRINK, SLEEVE, BLACK, POLYOLEFIN, 1.2, BORE 19.9MM

Pack size: **5 x EA**

- Sleeve Diameter: 19.1 mm
- Shrunk Diameter: 9.5 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



398155 19.1 mm

CABLE, HEATSHRINK, SLEEVE, BLACK, POLYOLEFIN, 1.2, BORE 12.7MM

Pack size: **5 x EA**

- Sleeve Diameter: 12.7 mm
- Shrunk Diameter: 6.4 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



398161 12.7 mm

CABLE, HEATSHRINK, SLEEVE, BLACK, POLYOLEFIN, 1.2, BORE 9.5MM

Pack size: **5 x EA**

- Sleeve Diameter: 9.5 mm
- Shrunk Diameter: 4.8 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



398177 9.5 mm

CABLE, HEATSHRINK, SLEEVE, BLACK, POLYOLEFIN, 1.2, BORE 6.4MM

Pack size: **5 x EA**

- Sleeve Diameter: 6.4 mm
- Shrunk Diameter: 3.2 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



398183 6.4 mm

CABLE, HEATSHRINK, SLEEVE, BLACK, POLYOLEFIN, 1.2, BORE .48MM

Pack size: **5 x EA**

- Sleeve Diameter: 4.8 mm
- Shrunk Diameter: 2.4 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



398199 4.8 mm

CABLE, HEATSHRINK, SLEEVE, BLACK, POLYOLEFIN, 1.2, BORE 3.2MM

Pack size: **5 x EA**

- Sleeve Diameter: 3.2 mm
- Shrunk Diameter: 1.6 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



398206 3.2 mm

CABLE, HEATSHRINK, SLEEVE, BLACK, POLYOLEFIN, 1.2, BORE 2.4MM

Pack size: **5 x EA**

- Sleeve Diameter: 2.4 mm
- Shrunk Diameter: 1.2 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



398212 2.4 mm

CABLE, HEATSHRINK, SLEEVE, BLACK, POLYOLEFIN, 1.2, BORE 1.6MM

Pack size: **5 x EA**

- Sleeve Diameter: 1.6 mm
- Shrunk Diameter: 0.8 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



398228 1.6 mm

CABLE, HEATSHRINK, SLEEVE, RED, POLYOLEFIN, 1.2, BORE 50.8MM

Pack size: **5 x EA**

- Sleeve Diameter: 50.8 mm
- Shrunk Diameter: 25.4 mm
- Colour: Red
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



398234 50.8 mm

CABLE, HEATSHRINK, SLEEVE, RED, POLYOLEFIN, 1.2, BORE 38.4MM

Pack size: **5 x EA**

- Sleeve Diameter: 38.1 mm
- Shrunk Diameter: 19.1 mm
- Colour: Red
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



398240 38.1 mm

CABLE, HEATSHRINK, SLEEVE, RED, POLYOLEFIN, 1.2, BORE 25.4MM

Pack size: **5 x EA**

- Sleeve Diameter: 25.4 mm
- Shrunk Diameter: 12.7 mm
- Colour: Red
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



398256 25.4 mm

CABLE, HEATSHRINK, SLEEVE, RED, POLYOLEFIN, 1.2, BORE 19.0MM

Pack size: **5 x EA**

- Sleeve Diameter: 19.1 mm
- Shrunk Diameter: 9.5 mm
- Colour: Red
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



398262 19.1 mm

CABLE, HEATSHRINK, SLEEVE, RED, POLYOLEFIN, 1.2, BORE 12.7MM

Pack size: **5 x EA**

- Sleeve Diameter: 12.7 mm
- Shrunk Diameter: 6.4 mm
- Colour: Red
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



398278 12.7 mm

CABLE, HEATSHRINK, SLEEVE, RED, POLYOLEFIN, 1.2, BORE 9.5MM

Pack size: **5 x EA**

- Sleeve Diameter: 9.5 mm
- Shrunk Diameter: 4.8 mm
- Colour: Red
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



398284 9.5 mm

CABLE, HEATSHRINK, SLEEVE, RED, POLYOLEFIN, 1.2, BORE 6.4MM

Pack size: **5 x EA**

- Sleeve Diameter: 6.4 mm
- Shrunk Diameter: 3.2 mm
- Colour: Red
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



398290 6.4 mm

CABLE, HEATSHRINK, SLEEVE, RED, POLYOLEFIN, 1.2, BORE 4.8MM

Pack size: **5 x EA**

- Sleeve Diameter: 4.8 mm
- Shrunk Diameter: 2.4 mm
- Colour: Red
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



398307 4.8 mm

RS PRO HEAT SHRINK TUBING, RED 3.2MM SLEEVE DIA. X 1.2M LENGTH 2:1

Pack size: **5 x EA**

- Sleeve Diameter: 3.2 mm
- Shrunk Diameter: 1.6 mm
- Colour: Red
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



398313 3.2 mm

CABLE, HEATSHRINK, SLEEVE, HIGH TEMP, POLYVINYLIDENE, BORE

Pack size: **1 x EA**

- Sleeve Diameter: 25.4 mm
- Shrunk Diameter: 12.7 mm
- Colour: Clear
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Fluoropolymer



398385 25.4 mm

CABLE, HEATSHRINK, SLEEVE, HIGH TEMP, POLYVINYLIDENE, BORE 19.0MM

Pack size: **1 x EA**

- Sleeve Diameter: 19.1 mm
- Shrunk Diameter: 9.5 mm
- Colour: Clear
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Fluoropolymer



398391 19.1 mm

CABLE, HEATSHRINK, SLEEVE, HIGH TEMP, POLYVINYLIDENE, BORE 12.7MM

Pack size: **1 x EA**

- Sleeve Diameter: 12.7 mm
- Shrunk Diameter: 6.4 mm
- Colour: Clear
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Fluoropolymer



398408 12.7 mm

CABLE, HEATSHRINK, SLEEVE, HIGH TEMP, POLYVINYLIDENE, BORE 9.5MM

Pack size: **1 x EA**

- Sleeve Diameter: 9.5 mm
- Shrunk Diameter: 4.8 mm
- Colour: Clear
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Fluoropolymer



398414 9.5 mm

CABLE, HEATSHRINK, SLEEVE, HIGH TEMP, POLYVINYLIDENE, BORE 6.4MM

Pack size: **1 x EA**

- Sleeve Diameter: 6.4 mm
- Shrunk Diameter: 3.2 mm
- Colour: Clear
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Fluoropolymer



398420 6.4 mm

CABLE, HEATSHRINK, SLEEVE, HIGH TEMP, POLYVINYLIDENE, BORE 4.8MM

Pack size: **1 x EA**

- Sleeve Diameter: 4.8 mm
- Shrunk Diameter: 2.4 mm
- Colour: Clear
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Fluoropolymer



398436 4.8 mm

CABLE, HEATSHRINK, SLEEVE, HIGH TEMP, POLYVINYLIDENE, BORE 3.2MM

Pack size: **1 x EA**

- Sleeve Diameter: 3.2 mm
- Shrunk Diameter: 1.6 mm
- Colour: Clear
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Fluoropolymer



398442 3.2 mm

CABLE, HEATSHRINK, SLEEVE, HIGH TEMP, POLYVINYLIDENE, BORE 2.4MM

Pack size: **1 x EA**

- Sleeve Diameter: 2.4 mm
- Shrunk Diameter: 1.2 mm
- Colour: Clear
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Fluoropolymer



398458 2.4 mm

CABLE, HEATSHRINK, SLEEVE, HIGH TEMP, POLYVINYLIDENE, BORE 1.6MM

Pack size: **1 x EA**

- Sleeve Diameter: 1.6 mm
- Shrunk Diameter: 0.8 mm
- Colour: Clear
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Fluoropolymer



398464 1.6 mm

CABLE, HEATSHRINK, SLEEVE, YELLOW POLYOLEFIN, 1.2, BORE 1.6MM

Pack size: **5 x EA**

- Sleeve Diameter: 1.6 mm
- Shrunk Diameter: 0.8 mm
- Colour: Yellow
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



399489 1.6 mm

CABLE, HEATSHRINK, SLEEVE, YELLOW POLYOLEFIN, 1.2, BORE 2.4MM

Pack size: **5 x EA**

- Sleeve Diameter: 2.4 mm
- Shrunk Diameter: 1.2 mm
- Colour: Yellow
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



399495 2.4 mm

CABLE, HEATSHRINK, SLEEVE, YELLOW POLYOLEFIN, 1.2, BORE 3.2MM

Pack size: **5 x EA**

- Sleeve Diameter: 3.2 mm
- Shrunk Diameter: 1.6 mm
- Colour: Yellow
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



399502 3.2 mm

RS PRO HEAT SHRINK TUBING, YELLOW 4.8MM SLEEVE DIA. X 1.2M

Pack size: **5 x EA**

- Sleeve Diameter: 4.8 mm
- Shrunk Diameter: 2.4 mm
- Colour: Yellow
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



399518 4.8 mm

RS PRO HEAT SHRINK TUBING, YELLOW 6.4MM SLEEVE DIA. X 1.2M

Pack size: **5 x EA**

- Sleeve Diameter: 6.4 mm
- Shrunk Diameter: 3.2 mm
- Colour: Yellow
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



399524 6.4 mm

RS PRO HEAT SHRINK TUBING, YELLOW 9.5MM SLEEVE DIA. X 1.2M

Pack size: **5 x EA**

- Sleeve Diameter: 9.5 mm
- Shrunk Diameter: 4.8 mm
- Colour: Yellow
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



399619 9.5 mm

CABLE, HEATSHRINK, SLEEVE, YELLOW POLYOLEFIN, 1.2, BORE 12.7MM

Pack size: **5 x EA**

- Sleeve Diameter: 12.7 mm
- Shrunk Diameter: 6.4 mm
- Colour: Yellow
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



399625 12.7 mm

RS PRO HEAT SHRINK TUBING, YELLOW 19.1MM SLEEVE DIA. X 1.2M

Pack size: **5 x EA**

- Sleeve Diameter: 19.1 mm
- Shrunk Diameter: 9.5 mm
- Colour: Yellow
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



399631 19.1 mm

RS PRO HEAT SHRINK TUBING, YELLOW 25.4MM SLEEVE DIA. X 1.2M

Pack size: **5 x EA**

- Sleeve Diameter: 25.4 mm
- Shrunk Diameter: 12.7 mm
- Colour: Yellow
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



399647 25.4 mm

RS PRO HEAT SHRINK TUBING, YELLOW 38.1MM SLEEVE DIA. X 1.2M

Pack size: **5 x EA**

- Sleeve Diameter: 38.1 mm
- Shrunk Diameter: 19.1 mm
- Colour: Yellow
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



399653 38.1 mm

RS PRO HEAT SHRINK TUBING, YELLOW 50.8MM SLEEVE DIA. X 1.2M

Pack size: **5 x EA**

- Sleeve Diameter: 50.8 mm
- Shrunk Diameter: 25.4 mm
- Colour: Yellow
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



399669 50.8 mm

CABLE, HEATSHRINK, SLEEVE, CLEAR, POLYOLEFIN, 1.2M BORE 1.6MM

Pack size: **5 x EA**

- Sleeve Diameter: 1.6 mm
- Shrunk Diameter: 0.8 mm
- Colour: Clear
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



399899 1.6 mm

CABLE, HEATSHRINK, SLEEVE, CLEAR, POLYOLEFIN, 1.2M BORE 2.4MM

Pack size: **5 x EA**

- Sleeve Diameter: 2.4 mm
- Shrunk Diameter: 1.2 mm
- Colour: Clear
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



399906 2.4 mm

CABLE, HEATSHRINK, SLEEVE, CLEAR, POLYOLEFIN, 1.2M BORE 6.4MM

Pack size: **5 x EA**

- Sleeve Diameter: 6.4 mm
- Shrunk Diameter: 3.2 mm
- Colour: Clear
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



399934 6.4 mm

CABLE, HEATSHRINK, SLEEVE, CLEAR, POLYOLEFIN, 1.2M BORE 4.8MM

Pack size: **5 x EA**

- Sleeve Diameter: 4.8 mm
- Shrunk Diameter: 2.4 mm
- Colour: Clear
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



399928 4.8 mm

CABLE, HEATSHRINK, SLEEVE, CLEAR, POLYOLEFIN, 1.2M BORE 9.5MM

Pack size: **5 x EA**

- Sleeve Diameter: 9.5 mm
- Shrunk Diameter: 4.8 mm
- Colour: Clear
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



399940 9.5 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, CLEAR 3.2MM SLEEVE DIA. X

Pack size: **5 x EA**

- Sleeve Diameter: 3.2 mm
- Shrunk Diameter: 1.6 mm
- Colour: Clear
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



399912 3.2 mm

CABLE, HEATSHRINK, SLEEVE, CLEAR, POLYOLEFIN, 1.2M BORE 19.0MM

Pack size: **5 x EA**

- Sleeve Diameter: 19.1 mm
- Shrunk Diameter: 9.5 mm
- Colour: Clear
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



399962 19.1 mm

CABLE, HEATSHRINK, SLEEVE, CLEAR, POLYOLEFIN, 1.2M BORE 25.4MM

Pack size: **5 x EA**

- Sleeve Diameter: 25.4 mm
- Shrunk Diameter: 12.7 mm
- Colour: Clear
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



399978 25.4 mm

CABLE, HEATSHRINK, SLEEVE, CLEAR, POLYOLEFIN, 1.2M BORE 12.7MM

Pack size: **5 x EA**

- Sleeve Diameter: 12.7 mm
- Shrunk Diameter: 6.4 mm
- Colour: Clear
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



399956 12.7 mm

CABLE, HEATSHRINK, SLEEVE, CLEAR, POLYOLEFIN, 1.2M BORE 50.8MM

Pack size: **5 x EA**

- Sleeve Diameter: 50.8 mm
- Shrunk Diameter: 25.4 mm
- Colour: Clear
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



399990 50.8 mm

CABLE, HEATSHRINK, SLEEVE, CLEAR, POLYOLEFIN, 1.2M BORE 38.0MM

Pack size: **5 x EA**

- Sleeve Diameter: 38.1 mm
- Shrunk Diameter: 19.1 mm
- Colour: Clear
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



399984 38.1 mm

RS PRO ADHESIVE LINED HEAT SHRINK TUBING, BLUE, RED, WHITE,

Pack size: **1 x KT**

- Sleeve Diameter: 12.7 mm, 19.1 mm, 25.4 mm, 38.1 mm
- Shrunk Diameter: Set
- Colour: Blue, Red, White, Yellow
- Sleeve Type: Heat Shrink
- Adhesive Lined: Yes
- Shrink Ratio: 2:1, 3:1
- Sleeve Length: Set
- Material: Polyolefin



562640 12.7 mm, 19.1 mm,

RS PRO HEAT SHRINK TUBING, BLACK, BLUE, GREEN/YELLOW, RED,

Pack size: **1 x KT**

- Sleeve Diameter: 6.4 mm, 9.5 mm, 12.7 mm, 19.1 mm, 25.4 mm
- Shrunk Diameter: Set
- Colour: Black, Blue, Green/Yellow, Red, White
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: Set
- Material: Polyolefin



562652 6.4 mm, 9.5 mm,

DUAL WALL, HEATSHRINK W3NH BLACK 40/13

Pack size: **1 x EA**

- Sleeve Diameter: 40 mm
- Shrunk Diameter: 13 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: Yes
- Shrink Ratio: 3:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



562656 40 mm

TERMINATION KIT

Pack size: **1 x KT**

- Sleeve Diameter: 3.2 mm, 4.8 mm, 6.4 mm, 9.5 mm
- Shrunk Diameter: Assortment
- Colour: Black, Blue, Green/Yellow, Red, White
- Sleeve Type: Heat Shrink
- Adhesive Lined: Yes
- Shrink Ratio: 2:1
- Sleeve Length: 110 mm
- Material: Polyolefin



562646 3.2 mm, 4.8 mm,

DUAL WALL, HEATSHRINK W3NH BLACK 19/6

Pack size: **1 x EA**

- Sleeve Diameter: 19.1 mm
- Shrunk Diameter: 6 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: Yes
- Shrink Ratio: 3:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



562662 19.1 mm

DUAL WALL, HEATSHRINK W3NH BLACK 12/4

Pack size: **1 x EA**

- Sleeve Diameter: 12.7 mm
- Shrunk Diameter: 4 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: Yes
- Shrink Ratio: 3:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



562668 12.7 mm

DUAL WALL, HEATSHRINK W3NH BLACK 9/3

Pack size: **1 x EA**

- Sleeve Diameter: 9 mm
- Shrunk Diameter: 3 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: Yes
- Shrink Ratio: 3:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



562678 9 mm

DUAL WALL, HEATSHRINK W3NH BLACK 6/2

Pack size: **1 x EA**

- Sleeve Diameter: 6.4 mm
- Shrunk Diameter: 2 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: Yes
- Shrink Ratio: 3:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



562684 6.4 mm

CABLE, HEATSHRINK, SLEEVE, BLACK, P OLYOLEFIN, 1.6MM

Pack size: **25 x EA**

- Sleeve Diameter: 1.6 mm
- Shrunk Diameter: 0.8 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 25 m
- Material: Polyolefin



666852 1.6 mm

RS PRO HEAT SHRINK TUBING, BLACK 2.4MM SLEEVE DIA. X 25M LENGTH 2:1

Pack size: **25 x EA**

- Sleeve Diameter: 2.4 mm
- Shrunk Diameter: 1.2 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 25 m
- Material: Polyolefin



666868 2.4 mm

CABLE, HEATSHRINK, SLEEVE, BLACK, P OLYOLEFIN, 3.2MM

Pack size: **20 x EA**

- Sleeve Diameter: 3.2 mm
- Shrunk Diameter: 1.6 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 20 m
- Material: Polyolefin



666874 3.2 mm

CABLE, HEATSHRINK, SLEEVE, BLACK, P OLYOLEFIN, 4.8MM

Pack size: **20 x EA**

- Sleeve Diameter: 4.8 mm
- Shrunk Diameter: 2.4 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 20 m
- Material: Polyolefin



666880 4.8 mm

RS PRO HEAT SHRINK TUBING, BLACK 6.4MM SLEEVE DIA. X 15M LENGTH 2:1

Pack size: **15 x EA**

- Sleeve Diameter: 6.4 mm
- Shrunk Diameter: 3.2 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 15 m
- Material: Polyolefin



666896 6.4 mm

CABLE, HEATSHRINK, SLEEVE, BLACK, P OLYOLEFIN, 9.5MM

Pack size: **12 x EA**

- Sleeve Diameter: 9.5 mm
- Shrunk Diameter: 4.8 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 12 m
- Material: Polyolefin



666903 9.5 mm

CABLE, HEATSHRINK, SLEEVE, BLACK, P OLYOLEFIN, 12.7MM

Pack size: **10 x EA**

- Sleeve Diameter: 12.7 mm
- Shrunk Diameter: 6.4 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 10 m
- Material: Polyolefin



666919 12.7 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, BLACK 1.6MM SLEEVE DIA. X

Pack size: **5 x EA**

- Sleeve Diameter: 1.6 mm
- Shrunk Diameter: 0.8 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



2116191 1.6 mm

CABLE, HEATSHRINK, SLEEVE, BLACK, P OLYOLEFIN, 19.0MM

Pack size: **6 x MTR**

- Sleeve Diameter: 19.1 mm
- Shrunk Diameter: 9.5 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 6 m
- Material: Polyolefin



666925 19.1 mm

CABLE, HEATSHRINK, SLEEVE, BLACK, P OLYOLEFIN, 25.4MM

Pack size: **3 x EA**

- Sleeve Diameter: 25.4 mm
- Shrunk Diameter: 12.7 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 3 m
- Material: Polyolefin



666931 25.4 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, BLACK 2.4MM SLEEVE DIA. X

Pack size: **5 x EA**

- Sleeve Diameter: 2.4 mm
- Shrunk Diameter: 1.2 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



2116208 2.4 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, BLACK 3.2MM SLEEVE DIA. X

Pack size: **5 x EA**

- Sleeve Diameter: 3.2 mm
- Shrunk Diameter: 1.6 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



2116214 3.2 mm

CABLE, HEATSHRINK, LSF, ZERO HALOGEN 2:1, 4.8MM DIA

Pack size: **5 x EA**

- Sleeve Diameter: 4.8 mm
- Shrunk Diameter: 2.4 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



2116220 4.8 mm

CABLE, HEATSHRINK, LSF, ZERO HALOGEN 2:1, 6.4MM DIA

Pack size: **5 x EA**

- Sleeve Diameter: 6.4 mm
- Shrunk Diameter: 3.2 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



2116236 6.4 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, BLACK 9.5MM SLEEVE DIA. X

Pack size: **5 x EA**

- Sleeve Diameter: 9.5 mm
- Shrunk Diameter: 4.8 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



2116242 9.5 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, BLACK 12.7MM SLEEVE DIA. X

Pack size: **5 x EA**

- Sleeve Diameter: 12.7 mm
- Shrunk Diameter: 6.4 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



2116258 12.7 mm

CABLE, HEATSHRINK, LSF, ZERO HALOGEN 2:1, 19.1MM DIA

Pack size: **5 x EA**

- Sleeve Diameter: 19.1 mm
- Shrunk Diameter: 9.5 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



2116270 19.1 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, BLACK 38.1MM SLEEVE DIA. X

Pack size: **5 x EA**

- Sleeve Diameter: 38.1 mm
- Shrunk Diameter: 19.1 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



2116292 38.1 mm

RS PRO HEAVY WALL ADHESIVE LINED HEAT SH

Pack size: **1 x EA**

- Sleeve Diameter: 13 mm
- Shrunk Diameter: 4 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: Yes
- Shrink Ratio: 3:1
- Sleeve Length: 1.22 m



2269083 13 mm

RS PRO HEAVY WALL ADHESIVE LINED HEAT SH

Pack size: **1 x EA**

- Sleeve Diameter: 22 mm
- Shrunk Diameter: 6 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: Yes
- Shrink Ratio: 3:1
- Sleeve Length: 1.22 m



2269084 22 mm

RS PRO HIGH RATIO HEAVY WALL HEAT SHRINK

Pack size: **1 x EA**

- Sleeve Diameter: 19 mm
- Shrunk Diameter: 3.2 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: Yes
- Shrink Ratio: 6:1
- Sleeve Length: 1.22 m



2269089 19 mm

RS PRO HIGH RATIO HEAVY WALL HEAT SHRINK

Pack size: **1 x EA**

- Sleeve Diameter: 33 mm
- Shrunk Diameter: 5.5 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: Yes
- Shrink Ratio: 6:1
- Sleeve Length: 1.22 m



2269090 33 mm

RS PRO HIGH RATIO HEAVY WALL HEAT SHRINK

Pack size: **1 x EA**

- Sleeve Diameter: 33 mm
- Shrunk Diameter: 5.5 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: Yes
- Shrink Ratio: 6:1
- Sleeve Length: 254 mm



2269091 33 mm

RS PRO HIGH RATIO HEAVY WALL HEAT SHRINK

Pack size: **1 x EA**

- Sleeve Diameter: 45 mm
- Shrunk Diameter: 7.4 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: Yes
- Shrink Ratio: 6:1
- Sleeve Length: 254 mm



2269092 45 mm

RS PRO HIGH RATIO HEAVY WALL HEAT SHRINK

Pack size: **1 x EA**

- Sleeve Diameter: 45 mm
- Shrunk Diameter: 7.4 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: Yes
- Shrink Ratio: 6:1
- Sleeve Length: 1.22 m



2269093 45 mm

RS PRO HIGH RATIO HEAVY WALL HEAT SHRINK

Pack size: **1 x EA**

- Sleeve Diameter: 51 mm
- Shrunk Diameter: 8.3 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: Yes
- Shrink Ratio: 6:1
- Sleeve Length: 1.22 m



2269095 51 mm

RS PRO HIGH RATIO HEAVY WALL HEAT SHRINK

Pack size: **1 x EA**

- Sleeve Diameter: 70 mm
- Shrunk Diameter: 11.7 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: Yes
- Shrink Ratio: 6:1
- Sleeve Length: 254 mm



2269097 70 mm

RS PRO MEDIUM WALL ADHESIVE LINED HEAT S

Pack size: **1 x EA**

- Sleeve Diameter: 12 mm
- Shrunk Diameter: 3 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: Yes
- Shrink Ratio: 3:1
- Sleeve Length: 1.22 m



2269098 12 mm

RS PRO MEDIUM WALL ADHESIVE LINED HEAT S

Pack size: **1 x EA**

- Sleeve Diameter: 16 mm
- Shrunk Diameter: 5 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: Yes
- Shrink Ratio: 3:1
- Sleeve Length: 1.22 m



2269099 16 mm

RS PRO MEDIUM WALL ADHESIVE LINED HEAT S

Pack size: **1 x EA**

- Sleeve Diameter: 19 mm
- Shrunk Diameter: 5 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: Yes
- Shrink Ratio: 3:1
- Sleeve Length: 1.22 m



2269101 19 mm

RS PRO MEDIUM WALL ADHESIVE LINED HEAT S

Pack size: **1 x EA**

- Sleeve Diameter: 33 mm
- Shrunk Diameter: 8 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: Yes
- Shrink Ratio: 3:1
- Sleeve Length: 1.22 m



2269102 33 mm

RS PRO MEDIUM WALL ADHESIVE LINED HEAT S

Pack size: **1 x EA**

- Sleeve Diameter: 115 mm
- Shrunk Diameter: 34 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: Yes
- Shrink Ratio: 3:1
- Sleeve Length: 1.22 m



2269106 115 mm

RS PRO HEAT SHRINK TUBING, BLACK 1.6MM S

Pack size: **1 x EA**

- Sleeve Diameter: 2 mm
- Shrunk Diameter: 0.8 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 12 m
- Material: Polyolefin



2269107 2 mm

RS PRO HEAT SHRINK TUBING, BLACK 3MM SLE

Pack size: **1 x EA**

- Sleeve Diameter: 3.5 mm
- Shrunk Diameter: 1.5 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 10 m
- Material: Polyolefin



2269108 3.5 mm

RS PRO HEAT SHRINK TUBING, BLACK 6MM SLE

Pack size: **1 x EA**

- Sleeve Diameter: 6.5 mm
- Shrunk Diameter: 3 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 7.5 m
- Material: Polyolefin



2269111 6.5 mm

RS PRO HEAT SHRINK TUBING, BLACK 9MM SLE

Pack size: **1 x EA**

- Sleeve Diameter: 9.6 mm
- Shrunk Diameter: 4.5 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 5 m
- Material: Polyolefin



2269112 9.6 mm

RS PRO HEAT SHRINK TUBING, BLACK 12.7MM

Pack size: **1 x EA**

- Sleeve Diameter: 12.7 mm
- Shrunk Diameter: 6 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 5 m
- Material: Polyolefin



2269113 12.7 mm

RS PRO HEAT SHRINK TUBING, BLACK 12MM SLEEVE DIA. X 5M LENGTH 3:1

Pack size: **1 x EA**

- Sleeve Diameter: 12 mm
- Shrunk Diameter: 4 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 3:1
- Sleeve Length: 5 m
- Material: Polyolefin



2269118 12 mm

RS PRO HEAT SHRINK TUBING, BLACK 18MM SL

Pack size: **1 x EA**

- Sleeve Diameter: 19 mm
- Shrunk Diameter: 9 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 5 m
- Material: Polyolefin



2269114 19 mm

RS PRO ADHESIVE LINED HEAT SHRINK TUBING, BLACK 3.2MM

Pack size: **1 x EA**

- Sleeve Diameter: 3.2 mm
- Shrunk Diameter: 1 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: Yes
- Shrink Ratio: 3:1
- Sleeve Length: 3 m



2269139 3.2 mm

RS PRO ADHESIVE LINED HEAT SHRINK TUBING

Pack size: **1 x EA**

- Sleeve Diameter: 25 mm
- Shrunk Diameter: 8 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: Yes
- Shrink Ratio: 3:1
- Sleeve Length: 3 m



2269140 25 mm

RS PRO ADHESIVE LINED HEAT SHRINK TUBING

Pack size: **1 x EA**

- Sleeve Diameter: 25 mm
- Shrunk Diameter: 8 mm
- Colour: Clear
- Sleeve Type: Heat Shrink
- Adhesive Lined: Yes
- Shrink Ratio: 3:1
- Sleeve Length: 3 m



2269141 25 mm

BLACK ADHESIVE LINED TUBING, 6-2MM I/D

Pack size: **1 x EA**

- Sleeve Diameter: 6.4 mm
- Shrunk Diameter: 2 mm
- Colour: Black
- Sleeve Type: Heat Shrink Tubing
- Adhesive Lined: Yes
- Shrink Ratio: 3:1
- Sleeve Length: 1.22 m
- Material: Polyolefin



2345886 6.4 mm

RS PRO ADHESIVE LINED HEAT SHRINK TUBING, BLACK 12.7MM

Pack size: **1 x EA**

- Sleeve Diameter: 12.7 mm
- Shrunk Diameter: 4 mm
- Colour: Black
- Sleeve Type: Heat Shrink Tubing
- Adhesive Lined: Yes
- Shrink Ratio: 3:1
- Sleeve Length: 1.22 m
- Material: Polyolefin



2345887 12.7 mm

RS PRO ADHESIVE LINED HEAT SHRINK TUBING, BLACK 19.1MM

Pack size: **1 x EA**

- Sleeve Diameter: 19.1 mm
- Shrunk Diameter: 6 mm
- Colour: Black
- Sleeve Type: Heat Shrink Tubing
- Adhesive Lined: Yes
- Shrink Ratio: 3:1
- Sleeve Length: 1.22 m
- Material: Polyolefin



2345889 19.1 mm

RS PRO ADHESIVE LINED HEAT SHRINK TUBING, BLACK 8MM SLEEVE

Pack size: **1 x EA**

- Sleeve Diameter: 8 mm
- Shrunk Diameter: 2 mm
- Colour: Black
- Sleeve Type: Heat Shrink Tubing
- Adhesive Lined: Yes
- Shrink Ratio: 4:1
- Sleeve Length: 1.22 m
- Material: Polyolefin



2345895 8 mm

RS PRO ADHESIVE LINED HEAT SHRINK TUBING, BLACK 4.8MM

Pack size: **1 x EA**

- Sleeve Diameter: 4.8 mm
- Shrunk Diameter: 1.6 mm
- Colour: Black
- Sleeve Type: Heat Shrink Tubing
- Adhesive Lined: Yes
- Shrink Ratio: 3:1
- Sleeve Length: 1.22 m
- Material: Polyolefin



2345892 4.8 mm

BLACK ADHESIVE LINED TUBING, 4-1MM I/D

Pack size: **1 x EA**

- Sleeve Diameter: 4 mm
- Shrunk Diameter: 1 mm
- Colour: Black
- Sleeve Type: Heat Shrink Tubing
- Adhesive Lined: Yes
- Shrink Ratio: 4:1
- Sleeve Length: 1.22 m
- Material: Polyolefin



2345893 4 mm

RS PRO ADHESIVE LINED HEAT SHRINK TUBING, BLACK 12MM SLEEVE

Pack size: **1 x EA**

- Sleeve Diameter: 12 mm
- Shrunk Diameter: 3 mm
- Colour: Black
- Sleeve Type: Heat Shrink Tubing
- Adhesive Lined: Yes
- Shrink Ratio: 4:1
- Sleeve Length: 1.22 m
- Material: Polyolefin



2345896 12 mm

BLACK ADHESIVE LINED TUBING, 16-4MM I/D

Pack size: **1 x EA**

- Sleeve Diameter: 16 mm
- Shrunk Diameter: 4 mm
- Colour: Black
- Sleeve Type: Heat Shrink Tubing
- Adhesive Lined: Yes
- Shrink Ratio: 4:1
- Sleeve Length: 1.22 m
- Material: Polyolefin



2345897 16 mm

BLACK ADHESIVE LINED TUBING, 24-6MM I/D

Pack size: **1 x EA**

- Sleeve Diameter: 24 mm
- Shrunk Diameter: 6 mm
- Colour: Black
- Sleeve Type: Heat Shrink Tubing
- Adhesive Lined: Yes
- Shrink Ratio: 4:1
- Sleeve Length: 1.22 m
- Material: Polyolefin



2345898 24 mm

BLACK ADHESIVE LINED TUBING, 32-8MM I/D

Pack size: **1 x EA**

- Sleeve Diameter: 32 mm
- Shrunk Diameter: 8 mm
- Colour: Black
- Sleeve Type: Heat Shrink Tubing
- Adhesive Lined: Yes
- Shrink Ratio: 4:1
- Sleeve Length: 1.22 m
- Material: Polyolefin



2345899 32 mm

ADHESIVE LINED HEATSHRINK TUBING, 3MM

Pack size: **1 x EA**

- Sleeve Diameter: 3.2 mm
- Shrunk Diameter: 1 mm
- Colour: Black
- Sleeve Type: Heat Shrink Tubing
- Adhesive Lined: Yes
- Shrink Ratio: 3:1
- Sleeve Length: 1.22 m
- Material: Polyolefin



2345901 3.2 mm

ADHESIVE LINED HEATSHRINK TUBING, 6MM

Pack size: **1 x EA**

- Sleeve Diameter: 6.4 mm
- Shrunk Diameter: 2 mm
- Colour: Black
- Sleeve Type: Heat Shrink Tubing
- Adhesive Lined: Yes
- Shrink Ratio: 3:1
- Sleeve Length: 1.22 m
- Material: Polyolefin



2345902 6.4 mm

BLACK HEATSHRINK TUBING, 1.2MM BORE

Pack size: **1 x EA**

- Sleeve Diameter: 1.2 mm
- Shrunk Diameter: 0.6 mm
- Colour: Black
- Sleeve Type: Heat Shrink Tubing
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.22 m
- Material: Polyolefin



2345906 1.2 mm

BLACK HEATSHRINK TUBING, 2.4MM BORE

Pack size: **1 x EA**

- Sleeve Diameter: 2.4 mm
- Shrunk Diameter: 1.2 mm
- Colour: Black
- Sleeve Type: Heat Shrink Tubing
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.22 m
- Material: Polyolefin



2345909 2.4 mm

RS PRO HEAT SHRINK TUBE, CLEAR 1.2MM SLEEVE DIA. X 1.22M LENGTH

Pack size: **1 x EA**

- Sleeve Diameter: 1.2 mm
- Shrunk Diameter: 0.6 mm
- Colour: Clear
- Sleeve Type: Heat Shrink Tubing
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.22 m
- Material: Polyolefin



2345907 1.2 mm

BLACK HEATSHRINK TUBING, 1.6MM BORE

Pack size: **1 x EA**

- Sleeve Diameter: 1.6 mm
- Shrunk Diameter: 0.8 mm
- Colour: Black
- Sleeve Type: Heat Shrink Tubing
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.22 m
- Material: Polyolefin



2345908 1.6 mm

RS PRO HEAT SHRINK TUBE, CLEAR 3.2MM SLEEVE DIA. X 1.22M LENGTH

Pack size: **1 x EA**

- Sleeve Diameter: 3.2 mm
- Shrunk Diameter: 1.6 mm
- Colour: Clear
- Sleeve Type: Heat Shrink Tubing
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.22 m
- Material: Polyolefin



2345911 3.2 mm

RS PRO HEAT SHRINK TUBE, BLACK 6.4MM SLEEVE DIA. X 1.22M LENGTH

Pack size: **1 x EA**

- Sleeve Diameter: 6.4 mm
- Shrunk Diameter: 3.2 mm
- Colour: Black
- Sleeve Type: Heat Shrink Tubing
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.22 m
- Material: Polyolefin



2345914 6.4 mm

BLACK HEATSHRINK TUBING, 4.8MM BORE

Pack size: **1 x EA**

- Sleeve Diameter: 4.8 mm
- Shrunk Diameter: 2.4 mm
- Colour: Black
- Sleeve Type: Heat Shrink Tubing
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.22 m
- Material: Polyolefin



2345912 4.8 mm

RS PRO HEAT SHRINK TUBE, CLEAR 4.8MM SLEEVE DIA. X 1.22M LENGTH

Pack size: **1 x EA**

- Sleeve Diameter: 4.8 mm
- Shrunk Diameter: 2.4 mm
- Colour: Clear
- Sleeve Type: Heat Shrink Tubing
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.22 m
- Material: Polyolefin



2345913 4.8 mm

RS PRO HEAT SHRINK TUBE, BLACK 9.5MM SLEEVE DIA. X 1.22M LENGTH

Pack size: **1 x EA**

- Sleeve Diameter: 9.5 mm
- Shrunk Diameter: 4.8 mm
- Colour: Black
- Sleeve Type: Heat Shrink Tubing
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.22 m
- Material: Polyolefin



2345916 9.5 mm

RS PRO HEAT SHRINK TUBE, BLACK 12.7MM SLEEVE DIA. X 1.22M LENGTH

Pack size: **1 x EA**

- Sleeve Diameter: 12.7 mm
- Shrunk Diameter: 6.4 mm
- Colour: Black
- Sleeve Type: Heat Shrink Tubing
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.22 m
- Material: Polyolefin



2345919 12.7 mm

BLACK HEATSHRINK TUBING, 19.1MM BORE

Pack size: **1 x EA**

- Sleeve Diameter: 19.1 mm
- Shrunk Diameter: 9.5 mm
- Colour: Black
- Sleeve Type: Heat Shrink Tubing
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.22 m
- Material: Polyolefin



2345921 19.1 mm

RS PRO HEAT SHRINK TUBE, CLEAR 19.1MM SLEEVE DIA. X 1.22M LENGTH

Pack size: **1 x EA**

- Sleeve Diameter: 19.1 mm
- Shrunk Diameter: 9.5 mm
- Colour: Clear
- Sleeve Type: Heat Shrink Tubing
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.22 m
- Material: Polyolefin



2345922 19.1 mm

BLACK HEATSHRINK TUBING, 25.4MM BORE

Pack size: **1 x EA**

- Sleeve Diameter: 25.4 mm
- Shrunk Diameter: 12.7 mm
- Colour: Black
- Sleeve Type: Heat Shrink Tubing
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.22 m
- Material: Polyolefin



2345924 25.4 mm

RS PRO HEAT SHRINK TUBE, CLEAR 25.4MM SLEEVE DIA. X 1.22M LENGTH

Pack size: **1 x EA**

- Sleeve Diameter: 25.4 mm
- Shrunk Diameter: 12.7 mm
- Colour: Clear
- Sleeve Type: Heat Shrink Tubing
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.22 m
- Material: Polyolefin



2345925 25.4 mm

BLACK HEATSHRINK TUBING, 50.8MM BORE

Pack size: **1 x EA**

- Sleeve Diameter: 50.8 mm
- Shrunk Diameter: 25.4 mm
- Colour: Black
- Sleeve Type: Heat Shrink Tubing
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.22 m
- Material: Polyolefin



2345928 50.8 mm

RS PRO HEAT SHRINK TUBE, CLEAR 50.8MM SLEEVE DIA. X 1.22M LENGTH

Pack size: **1 x EA**

- Sleeve Diameter: 50.8 mm
- Shrunk Diameter: 25.4 mm
- Colour: Clear
- Sleeve Type: Heat Shrink Tubing
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.22 m
- Material: Polyolefin



2345929 50.8 mm

RS PRO HEAT SHRINK TUBE, BLACK 76.2MM SLEEVE DIA. X 1.22M LENGTH

Pack size: **1 x EA**

- Sleeve Diameter: 76.2 mm
- Shrunk Diameter: 38.1 mm
- Colour: Black
- Sleeve Type: Heat Shrink Tubing
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.22 m
- Material: Polyolefin



2345930 76.2 mm

BLACK HEATSHRINK TUBING, 101.6MM BORE

Pack size: **1 x EA**

- Sleeve Diameter: 101.6 mm
- Shrunk Diameter: 50.8 mm
- Colour: Black
- Sleeve Type: Heat Shrink Tubing
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.22 m
- Material: Polyolefin



2345931 101.6 mm

RS PRO HEAT SHRINK TUBE, BLACK 25MM SLEEVE DIA. X 1.22M LENGTH

Pack size: **1 x EA**

- Sleeve Diameter: 25 mm
- Shrunk Diameter: 8 mm
- Colour: Black
- Sleeve Type: Heat Shrink Tubing
- Adhesive Lined: No
- Shrink Ratio: 3:1
- Sleeve Length: 1.22 m
- Material: Polyolefin



2345935 25 mm

RNF 3000 HEATSHRINK

Pack size: **1 x EA**

- Sleeve Diameter: 3 mm
- Shrunk Diameter: 1 mm
- Colour: Black
- Sleeve Type: Heat Shrink Tubing
- Adhesive Lined: No
- Shrink Ratio: 3:1
- Sleeve Length: 1.22 m
- Material: Polyolefin



2345932 3 mm

RS PRO HEAT SHRINK TUBE, BLACK 9.1MM SLEEVE DIA. X 1.22M LENGTH

Pack size: **1 x EA**

- Sleeve Diameter: 9.1 mm
- Shrunk Diameter: 3 mm
- Colour: Black
- Sleeve Type: Heat Shrink Tubing
- Adhesive Lined: No
- Shrink Ratio: 3:1
- Sleeve Length: 1.22 m
- Material: Polyolefin



2345933 9.1 mm

RS PRO HEAT SHRINK TUBE, CLEAR 6.4MM SLEEVE DIA. X 1.2M LENGTH 2:1

Pack size: **1 x EA**

- Sleeve Diameter: 6.4 mm
- Shrunk Diameter: 3.2 mm
- Colour: Clear
- Sleeve Type: Heat Shrink Tubing
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyvinylidene Fluoride



2345938 6.4 mm

RS PRO HEAT SHRINK TUBE, CLEAR 1.2MM SLEEVE DIA. X 1.2M LENGTH 2:1

Pack size: **1 x EA**

- Sleeve Diameter: 1.2 mm
- Shrunk Diameter: 0.6 mm
- Colour: Clear
- Sleeve Type: Heat Shrink Tubing
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyvinylidene Fluoride



2345936 1.2 mm

CLEAR HEATSHRINK TUBING,2.4MM I/D

Pack size: **1 x EA**

- Sleeve Diameter: 2.4 mm
- Shrunk Diameter: 1.2 mm
- Colour: Clear
- Sleeve Type: Heat Shrink Tubing
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyvinylidene Fluoride



2345937 2.4 mm

RS PRO HEAT SHRINK TUBE, CLEAR 9.5MM SLEEVE DIA. X 1.2M LENGTH 2:1

Pack size: **1 x EA**

- Sleeve Diameter: 9.5 mm
- Shrunk Diameter: 4.8 mm
- Colour: Clear
- Sleeve Type: Heat Shrink Tubing
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyvinylidene Fluoride



2345940 9.5 mm

RS PRO HEAT SHRINK TUBING, CLEAR 2MM SLEEVE DIA. X 1.22M LENGTH 4:1

Pack size: **1 x EA**

- Sleeve Diameter: 2 mm
- Shrunk Diameter: 0.5 mm
- Colour: Clear
- Sleeve Type: Heat Shrink Tubing
- Adhesive Lined: No
- Shrink Ratio: 4:1
- Sleeve Length: 1.22 m
- Material: PTFE



2345955 2 mm

CLEAR HEATSHRINK TUBING,19.0MM I/D

Pack size: **1 x EA**

- Sleeve Diameter: 19.1 mm
- Shrunk Diameter: 9.5 mm
- Colour: Clear
- Sleeve Type: Heat Shrink Tubing
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyvinylidene Fluoride



2345942 19.1 mm

RS PRO HEAT SHRINK TUBE, CLEAR 12.7MM SLEEVE DIA. X 1.2M LENGTH

Pack size: **1 x EA**

- Sleeve Diameter: 12.7 mm
- Shrunk Diameter: 6.4 mm
- Colour: Clear
- Sleeve Type: Heat Shrink Tubing
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyvinylidene Fluoride



2345941 12.7 mm

CLEAR HEATSHRINK TUBING,4.8MM I/D

Pack size: **1 x EA**

- Sleeve Diameter: 4.8 mm
- Shrunk Diameter: 2.4 mm
- Colour: Clear
- Sleeve Type: Heat Shrink Tubing
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyvinylidene Fluoride



2345944 4.8 mm

RS PRO HEAT SHRINK TUBING, TRANSPARENT 1.2MM SLEEVE DIA. X

Pack size: **1 x EA**

- Sleeve Diameter: 1.2 mm
- Shrunk Diameter: 0.6 mm
- Colour: Transparent
- Sleeve Type: Heat Shrink Tubing
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyvinylidene Fluoride



2345946 1.2 mm

RS PRO HEAT SHRINK TUBING, CLEAR 3.5MM SLEEVE DIA. X 1.22M LENGTH

Pack size: **1 x EA**

- Sleeve Diameter: 3.5 mm
- Shrunk Diameter: 0.85 mm
- Colour: Clear
- Sleeve Type: Heat Shrink Tubing
- Adhesive Lined: No
- Shrink Ratio: 4:1
- Sleeve Length: 1.22 m
- Material: PTFE



2345956 3.5 mm

HIGH TEMP HEATSHRINK TUBING,6.4MM I/D

Pack size: **1 x EA**

- Sleeve Diameter: 6 mm
- Shrunk Diameter: 1.5 mm
- Colour: Clear
- Sleeve Type: Heat Shrink Tubing
- Adhesive Lined: No
- Shrink Ratio: 4:1
- Sleeve Length: 1.22 m
- Material: PTFE



2345957 6 mm

CABLE,HEATSHRINK,ADHESIVE LINED,40/13 WHITE

Pack size: **1 x EA**

- Sleeve Diameter: 40 mm
- Shrunk Diameter: 13 mm
- Colour: White
- Sleeve Type: Heat Shrink
- Adhesive Lined: Yes
- Shrink Ratio: 3:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



2417618 40 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, YELLOW 38.1MM SLEEVE DIA.

Pack size: **1 x EA**

- Sleeve Diameter: 38.1 mm
- Shrunk Diameter: 19.1 mm
- Colour: Yellow
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



2672051 38.1 mm

RS PRO HEAT SHRINK TUBING, CLEAR 9.5MM SLEEVE DIA. X 1.22M LENGTH

Pack size: **1 x EA**

- Sleeve Diameter: 9.5 mm
- Shrunk Diameter: 2.8 mm
- Colour: Clear
- Sleeve Type: Heat Shrink Tubing
- Adhesive Lined: No
- Shrink Ratio: 4:1
- Sleeve Length: 1.22 m
- Material: PTFE



2345958 9.5 mm

CABLE,HEATSHRINK,ADHESIVE LINED,40/13 RED

Pack size: **1 x EA**

- Sleeve Diameter: 40 mm
- Shrunk Diameter: 13 mm
- Colour: Red
- Sleeve Type: Heat Shrink
- Adhesive Lined: Yes
- Shrink Ratio: 3:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



2417602 40 mm

CABLE,HEATSHRINK,MEDIUM WALL,LFH,2:1,BLUE,6.4MM

Pack size: **1 x EA**

- Sleeve Diameter: 6.4 mm
- Shrunk Diameter: 3.2 mm
- Colour: Blue
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



2672102 6.4 mm

CABLE,HEATSHRINK,MEDIUM WALL,LFH,2:1,BLUE,3.2MM

Pack size: **1 x EA**

- Sleeve Diameter: 3.2 mm
- Shrunk Diameter: 1.6 mm
- Colour: Blue
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



2672089 3.2 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, BLUE 12.7MM SLEEVE DIA. X

Pack size: **1 x EA**

- Sleeve Diameter: 12.7 mm
- Shrunk Diameter: 6.4 mm
- Colour: Blue
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



2672124 12.7 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, BLUE 19.1MM SLEEVE DIA. X

Pack size: **1 x EA**

- Sleeve Diameter: 19.1 mm
- Shrunk Diameter: 9.5 mm
- Colour: Blue
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



2672130 19.1 mm

CABLE,HEATSHRINK,MEDIUM WALL,LFH,2:1,BLUE,25.4MM

Pack size: **1 x EA**

- Sleeve Diameter: 25.4 mm
- Shrunk Diameter: 12.7 mm
- Colour: Blue
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



2672146 25.4 mm

CABLE,HEATSHRINK,MEDIUM WALL,LFH,2:1,BLUE,38MM

Pack size: **1 x EA**

- Sleeve Diameter: 38.1 mm
- Shrunk Diameter: 19.1 mm
- Colour: Blue
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



2672152 38.1 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, RED 1.6MM SLEEVE DIA. X

Pack size: **1 x EA**

- Sleeve Diameter: 1.6 mm
- Shrunk Diameter: 0.8 mm
- Colour: Red
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



2672168 1.6 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, RED 3.2MM SLEEVE DIA. X

Pack size: **1 x EA**

- Sleeve Diameter: 3.2 mm
- Shrunk Diameter: 1.6 mm
- Colour: Red
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



2672180 3.2 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, RED 2.4MM SLEEVE DIA. X

Pack size: **1 x EA**

- Sleeve Diameter: 2.4 mm
- Shrunk Diameter: 1.2 mm
- Colour: Red
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



2672174 2.4 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, RED 4.8MM SLEEVE DIA. X

Pack size: **1 x EA**

- Sleeve Diameter: 4.8 mm
- Shrunk Diameter: 2.4 mm
- Colour: Red
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



2672203 4.8 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, BLUE 4.8MM SLEEVE DIA. X

Pack size: **1 x EA**

- Sleeve Diameter: 4.8 mm
- Shrunk Diameter: 2.4 mm
- Colour: Blue
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



2672095 4.8 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, RED 9.5MM SLEEVE DIA. X

Pack size: **1 x EA**

- Sleeve Diameter: 9.5 mm
- Shrunk Diameter: 4.8 mm
- Colour: Red
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



2672225 9.5 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, RED 12.7MM SLEEVE DIA. X

Pack size: **1 x EA**

- Sleeve Diameter: 12.7 mm
- Shrunk Diameter: 6.4 mm
- Colour: Red
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



2672231 12.7 mm

CABLE,HEATSHRINK,MEDIUM WALL,LFH,2:1,RED,19MM

Pack size: **1 x EA**

- Sleeve Diameter: 19.1 mm
- Shrunk Diameter: 9.5 mm
- Colour: Red
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



2672247 19.1 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, RED 25.4MM SLEEVE DIA. X

Pack size: **1 x EA**

- Sleeve Diameter: 25.4 mm
- Shrunk Diameter: 12.7 mm
- Colour: Red
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



2672269 25.4 mm

CABLE,HEATSHRINK,MEDIUM WALL,LFH,2:1,RED,38MM

Pack size: **1 x EA**

- Sleeve Diameter: 38.1 mm
- Shrunk Diameter: 19.1 mm
- Colour: Red
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



2672275 38.1 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, WHITE 4.8MM SLEEVE DIA. X

Pack size: **1 x EA**

- Sleeve Diameter: 4.8 mm
- Shrunk Diameter: 2.4 mm
- Colour: White
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



2672326 4.8 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, WHITE 9.5MM SLEEVE DIA. X

Pack size: **1 x EA**

- Sleeve Diameter: 9.5 mm
- Shrunk Diameter: 4.8 mm
- Colour: White
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



2672348 9.5 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, WHITE 12.7MM SLEEVE DIA. X

Pack size: **1 x EA**

- Sleeve Diameter: 12.7 mm
- Shrunk Diameter: 6.4 mm
- Colour: White
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



2672354 12.7 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, RED 6.4MM SLEEVE DIA. X

Pack size: **1 x EA**

- Sleeve Diameter: 6.4 mm
- Shrunk Diameter: 3.2 mm
- Colour: Red
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



2672219 6.4 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, WHITE 38.1MM SLEEVE DIA. X

Pack size: **1 x EA**

- Sleeve Diameter: 38.1 mm
- Shrunk Diameter: 19.1 mm
- Colour: White
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



2672382 38.1 mm

CABLE,HEATSHRINK,MEDIUM WALL,LFH,2:1,GREEN/YELLOW,1.6MM

Pack size: **1 x EA**

- Sleeve Diameter: 1.6 mm
- Shrunk Diameter: 0.8 mm
- Colour: Green
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



2684969 1.6 mm

CABLE,HEATSHRINK,MEDIUM WALL,LFH,2:1,GREEN/YELLOW,2.4MM

Pack size: **1 x EA**

- Sleeve Diameter: 2.4 mm
- Shrunk Diameter: 1.2 mm
- Colour: Green
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



2684975 2.4 mm

CABLE,HEATSHRINK,MEDIUM WALL,LFH,2:1,BLUE,9.5MM

Pack size: **1 x EA**

- Sleeve Diameter: 9.5 mm
- Shrunk Diameter: 4.8 mm
- Colour: Blue
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



2672118 9.5 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, WHITE 19.1MM SLEEVE DIA. X

Pack size: **1 x EA**

- Sleeve Diameter: 19.1 mm
- Shrunk Diameter: 9.5 mm
- Colour: White
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



2672360 19.1 mm

CABLE,HEATSHRINK,MEDIUM WALL,LFH,2:1,GREEN/YELLOW,6.4MM

Pack size: **1 x EA**

- Sleeve Diameter: 6.4 mm
- Shrunk Diameter: 3.2 mm
- Colour: Green
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



2685007 6.4 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, GREEN 9.5MM SLEEVE DIA. X

Pack size: **1 x EA**

- Sleeve Diameter: 9.5 mm
- Shrunk Diameter: 4.8 mm
- Colour: Green
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



2685013 9.5 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, GREEN 19.1MM SLEEVE DIA. X

Pack size: **1 x EA**

- Sleeve Diameter: 19.1 mm
- Shrunk Diameter: 9.5 mm
- Colour: Green
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



2685035 19.1 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, GREEN 12.7MM SLEEVE DIA. X

Pack size: **1 x EA**

- Sleeve Diameter: 12.7 mm
- Shrunk Diameter: 6.4 mm
- Colour: Green
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



2685029 12.7 mm

CABLE,HEATSHRINK,MEDIUM WALL,LFH,2:1,GREEN/YELLOW,3.2MM

Pack size: **1 x EA**

- Sleeve Diameter: 3.2 mm
- Shrunk Diameter: 1.6 mm
- Colour: Green
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



2684981 3.2 mm

CABLE,HEATSHRINK,MEDIUM WALL,LFH,2:1,GREEN/YELLOW,38MM

Pack size: **1 x EA**

- Sleeve Diameter: 38.1 mm
- Shrunk Diameter: 19.1 mm
- Colour: Green
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



2685057 38.1 mm

CABLE,HEATSHRINK,MEDIUM WALL,LFH,2:1,GREEN/YELLOW,4.8MM

Pack size: **1 x EA**

- Sleeve Diameter: 4.8 mm
- Shrunk Diameter: 2.4 mm
- Colour: Green, Yellow
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



2684997 4.8 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, GREEN 25.4MM SLEEVE DIA.

Pack size: **1 x EA**

- Sleeve Diameter: 25.4 mm
- Shrunk Diameter: 12.7 mm
- Colour: Green
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



2685041 25.4 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, BLACK 3MM SLEEVE DIA. X

Pack size: **5 x EA**

- Sleeve Diameter: 3 mm
- Shrunk Diameter: 1 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 3:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



2812811 3 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, BLACK 9MM SLEEVE DIA. X

Pack size: **5 x EA**

- Sleeve Diameter: 9 mm
- Shrunk Diameter: 3 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 3:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



2812833 9 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, BLACK 18MM SLEEVE DIA. X

Pack size: **5 x EA**

- Sleeve Diameter: 18 mm
- Shrunk Diameter: 6 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 3:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



2812855 18 mm

CABLE,HEATSHRINK,SLEEVE,BLACK,P OLYOLEFIN,30CM,201.6MM

Pack size: **20 x EA**

- Sleeve Diameter: 1.6 mm
- Shrunk Diameter: 0.8 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 300 mm
- Material: Polyolefin



4177211 1.6 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, BLACK 40MM SLEEVE DIA. X

Pack size: **5 x EA**

- Sleeve Diameter: 40 mm
- Shrunk Diameter: 13 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 3:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



2812883 40 mm

CABLE,HEATSHRINK,KIT,ZERO HALOGEN,FLAME RETARDENT,2:1

Pack size: **1 x KT**

- Sleeve Diameter: 2.4 mm, 3.2 mm, 4.8 mm, 6.4 mm, 9.5 mm, 12.7 mm
- Shrunk Diameter: Assortment
- Colour: Black, Blue, Green/Yellow, Red, White
- Sleeve Type: Heat Shrink
- Adhesive Lined: Yes
- Shrink Ratio: 2:1
- Sleeve Length: 10 cm, 14 cm, 18 cm, 20 cm, 25 cm
- Material: Polyolefin



3974263 2.4 mm, 3.2 mm,

CABLE,HEATSHRINK,SLEEVE,BLACK,P OLYOLEFIN,30CM,202.4MM

Pack size: **20 x EA**

- Sleeve Diameter: 2.4 mm
- Shrunk Diameter: 1.2 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 300 mm
- Material: Polyolefin



4177227 2.4 mm

CABLE,HEATSHRINK,SLEEVE,BLACK,P OLYOLEFIN,30CM,203.2MM

Pack size: **20 x EA**

- Sleeve Diameter: 3.2 mm
- Shrunk Diameter: 1.6 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 300 mm
- Material: Polyolefin



4177249 3.2 mm

CABLE,HEATSHRINK,SLEEVE,BLACK,P OLYOLEFIN,30CM,204.8MM

Pack size: **20 x EA**

- Sleeve Diameter: 4.8 mm
- Shrunk Diameter: 2.4 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 300 mm
- Material: Polyolefin



4177255 4.8 mm

CABLE,HEATSHRINK,SLEEVE,BLACK,P OLYOLEFIN,30CM,206.4MM

Pack size: **20 x EA**

- Sleeve Diameter: 6.4 mm
- Shrunk Diameter: 3.2 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 300 mm
- Material: Polyolefin



4177261 6.4 mm

CABLE,HEATSHRINK,SLEEVE,BLACK,P OLYOLEFIN,30CM,209.5MM

Pack size: **20 x EA**

- Sleeve Diameter: 9.5 mm
- Shrunk Diameter: 4.8 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 300 mm
- Material: Polyolefin



4177277 9.5 mm

CABLE,HEATSHRINK,SLEEVE,BLACK,P OLYOLEFIN,30CM,2012.7MM

Pack size: **20 x EA**

- Sleeve Diameter: 12.7 mm
- Shrunk Diameter: 6.4 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 300 mm
- Material: Polyolefin



4177283 12.7 mm

RS PRO HEAT SHRINK TUBING, BLACK 19.1MM SLEEVE DIA. X 300MM LENGTH

Pack size: **20 x EA**

- Sleeve Diameter: 19.1 mm
- Shrunk Diameter: 9.5 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 300 mm
- Material: Polyolefin



4177299 19.1 mm

RS PRO HEAT SHRINK TUBING, BLACK 38MM SLEEVE DIA. X 300MM LENGTH

Pack size: **20 x EA**

- Sleeve Diameter: 38 mm
- Shrunk Diameter: 19 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 300 mm
- Material: Polyolefin



4177312 38 mm

RS PRO HEAT SHRINK TUBING, BLACK 50.8MM SLEEVE DIA. X 300MM

Pack size: **20 x EA**

- Sleeve Diameter: 50.8 mm
- Shrunk Diameter: 25.4 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 300 mm
- Material: Polyolefin



4177328 50.8 mm

CABLE,HEATSHRINK,LAME RETARDANT,KIT,ADHESIVE

Pack size: **1 x KT**

- Sleeve Diameter: 3 mm
- Shrunk Diameter: 1.5 mm
- Colour: Blue, Red, White, Yellow
- Sleeve Type: Heat Shrink
- Adhesive Lined: Yes
- Shrink Ratio: 3:1
- Sleeve Length: Assortment
- Material: Polyolefin



4179087 3 mm

CABLE,HEATSHRINK,SLEEVE,POLYOLEFIN,30CM,20 PIECES,1.6MM,CLEAR

Pack size: **20 x EA**

- Sleeve Diameter: 1.6 mm
- Shrunk Diameter: 0.8 mm
- Colour: Clear
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 300 mm
- Material: Polyolefin



4434889 1.6 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, CLEAR 2.4MM SLEEVE DIA. X

- Pack size: **20 x EA**
- Sleeve Diameter: 2.4 mm
 - Shrunk Diameter: 1.2 mm
 - Colour: Clear
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 300 mm
 - Material: Polyolefin



4434895 2.4 mm

CABLE,HEATSHRINK,SLEEVE,POLYOLE FIN,30CM,20 PIECES,3.2MM,CLEAR

- Pack size: **20 x EA**
- Sleeve Diameter: 3.2 mm
 - Shrunk Diameter: 1.6 mm
 - Colour: Clear
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 300 mm
 - Material: Polyolefin



4434902 3.2 mm

CABLE,HEATSHRINK,SLEEVE,POLYOLE FIN,30CM,20 PIECES,4.8MM,CLEAR

- Pack size: **20 x EA**
- Sleeve Diameter: 4.8 mm
 - Shrunk Diameter: 2.4 mm
 - Colour: Clear
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 300 mm
 - Material: Polyolefin



4434924 4.8 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, CLEAR 6.4MM SLEEVE DIA. X

- Pack size: **20 x EA**
- Sleeve Diameter: 6.4 mm
 - Shrunk Diameter: 3.2 mm
 - Colour: Clear
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 300 mm
 - Material: Polyolefin



4434930 6.4 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, CLEAR 9.5MM SLEEVE DIA. X

- Pack size: **20 x EA**
- Sleeve Diameter: 9.5 mm
 - Shrunk Diameter: 4.8 mm
 - Colour: Clear
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 300 mm
 - Material: Polyolefin



4434946 9.5 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, CLEAR 12.7MM SLEEVE DIA. X

- Pack size: **20 x EA**
- Sleeve Diameter: 12.7 mm
 - Shrunk Diameter: 6.4 mm
 - Colour: Clear
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 300 mm
 - Material: Polyolefin



4434952 12.7 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, CLEAR 19.1MM SLEEVE DIA. X

- Pack size: **20 x EA**
- Sleeve Diameter: 19.1 mm
 - Shrunk Diameter: 9.5 mm
 - Colour: Clear
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 300 mm
 - Material: Polyolefin



4434968 19.1 mm

CABLE,HEATSHRINK,SLEEVE,POLYOLE FIN,30CM,20 PIECES,25.4MM,CLEAR

- Pack size: **20 x EA**
- Sleeve Diameter: 25.4 mm
 - Shrunk Diameter: 12.7 mm
 - Colour: Clear
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 300 mm
 - Material: Polyolefin



4434974 25.4 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, CLEAR 38.1MM SLEEVE DIA. X

- Pack size: **20 x EA**
- Sleeve Diameter: 38.1 mm
 - Shrunk Diameter: 19.1 mm
 - Colour: Clear
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 300 mm
 - Material: Polyolefin



4434980 38.1 mm

CABLE,HEATSHRINK,SLEEVE,POLYOLE FIN,30CM,20 PIECES,50.8MM,CLEAR

- Pack size: **20 x EA**
- Sleeve Diameter: 50.8 mm
 - Shrunk Diameter: 25.4 mm
 - Colour: Clear
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 300 mm
 - Material: Polyolefin



4434996 50.8 mm

HEATSHRINK,CABLE,SLEEVE,KIT,2:1,3:1,CLEAR

- Pack size: **1 x EA**
- Sleeve Diameter: 3 mm, 3.2 mm, 6.4 mm, 9 mm
 - Shrunk Diameter: Assortment
 - Colour: Clear
 - Sleeve Type: Heat Shrink
 - Shrink Ratio: 2:1
 - Sleeve Length: 100 mm
 - Material: Fluoropolymer, Polyolefin, PVDF
 - Flame Retardant: Yes



4580639 3 mm, 3.2 mm,

RS PRO HEAT SHRINK TUBING, ASSORTED 3.2MM SLEEVE DIA. X

- Pack size: **1 x EA**
- Sleeve Diameter: 3.2 mm, 6.4 mm, 9.5 mm, 12.7 mm
 - Shrunk Diameter: Assortment
 - Colour: Assorted
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 3.6 cm, 4.1 cm, 6 cm, 9 cm, 12 cm, 15 cm, 20 cm, 25 cm
 - Material: Polyolefin



4580645 3.2 mm, 6.4 mm,

HEATSHRINK,CABLE,SLEEVE,POLYOLE FIN,3/1X30CM,X20

- Pack size: **20 x EA**
- Sleeve Diameter: 3.2 mm
 - Shrunk Diameter: 0.6 mm
 - Colour: Clear
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: Yes
 - Shrink Ratio: 3:1
 - Sleeve Length: 300 mm
 - Material: Polyolefin



4580673 3.2 mm

HEATSHRINK,CABLE,SLEEVE,HIGH TEMPERATURE,FLAME

- Pack size: **4 x EA**
- Sleeve Diameter: 6.4 mm
 - Shrunk Diameter: 3.2 mm
 - Colour: Clear
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 300 mm
 - Material: Fluoropolymer



4580651 6.4 mm

HEATSHRINK,CABLE,SLEEVE,HIGH TEMPERATURE,FLAME

- Pack size: **4 x EA**
- Sleeve Diameter: 3.2 mm
 - Shrunk Diameter: 1.6 mm
 - Colour: Clear
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: No
 - Shrink Ratio: 2:1
 - Sleeve Length: 300 mm
 - Material: Fluoropolymer



4580667 3.2 mm

HEATSHRINK,ADHESIVE LINED,FLAME RETARDANT,BLACK,3/1,1.2M

- Pack size: **1 x EA**
- Sleeve Diameter: 3 mm
 - Shrunk Diameter: 1 mm
 - Colour: Black
 - Sleeve Type: Heat Shrink
 - Adhesive Lined: Yes
 - Shrink Ratio: 3:1
 - Sleeve Length: 1.2 m
 - Material: Polyolefin



4811775 3 mm

HEATSHRINK, CABLE, SLEEVE, POLYOLEFIN, 9/3X30CM, X20

Pack size: **20 x EA**

- Sleeve Diameter: 9.5 mm
- Shrunk Diameter: 3 mm
- Colour: Clear
- Sleeve Type: Heat Shrink
- Adhesive Lined: Yes
- Shrink Ratio: 3:1
- Sleeve Length: 300 mm
- Material: Polyolefin



4580689 9.5 mm

HEATSHRINK, CABLE, SLEEVE, POLYOLEFIN, 12/4X30CM, X20

Pack size: **20 x EA**

- Sleeve Diameter: 12.7 mm
- Shrunk Diameter: 4 mm
- Colour: Clear
- Sleeve Type: Heat Shrink
- Adhesive Lined: Yes
- Shrink Ratio: 3:1
- Sleeve Length: 300 mm
- Material: Polyolefin



4580695 12.7 mm

HEATSHRINK, ADHESIVE LINED, FLAME RETARDANT, BLACK, 6/2, 1.2M

Pack size: **1 x EA**

- Sleeve Diameter: 6.4 mm
- Shrunk Diameter: 2 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: Yes
- Shrink Ratio: 3:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



4811797 6.4 mm

HEATSHRINK, ADHESIVE LINED, FLAME RETARDANT, BLACK, 9/3, 1.2M

Pack size: **1 x EA**

- Sleeve Diameter: 9.5 mm
- Shrunk Diameter: 3 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: Yes
- Shrink Ratio: 3:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



4811804 9.5 mm

RS PRO ADHESIVE LINED HEAT SHRINK TUBING, BLACK 12.7MM

Pack size: **1 x EA**

- Sleeve Diameter: 12.7 mm
- Shrunk Diameter: 4 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: Yes
- Shrink Ratio: 3:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



4811810 12.7 mm

HEATSHRINK, ADHESIVE LINED, FLAME RETARDANT, BLACK, 19/6, 1.2M

Pack size: **1 x EA**

- Sleeve Diameter: 19 mm
- Shrunk Diameter: 6 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: Yes
- Shrink Ratio: 3:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



4811826 19 mm

HEATSHRINK, ADHESIVE LINED, FLAME RETARDANT, BLACK, 24/8, 1.2M

Pack size: **1 x EA**

- Sleeve Diameter: 24 mm
- Shrunk Diameter: 8 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: Yes
- Shrink Ratio: 3:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



4811832 24 mm

HEATSHRINK, ADHESIVE LINED, FLAME RETARDANT, BLACK, 40/13, 1.2M

Pack size: **1 x EA**

- Sleeve Diameter: 40 mm
- Shrunk Diameter: 13 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: Yes
- Shrink Ratio: 3:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



4811854 40 mm

CABLE, HEATSHRINK, SLEEVE, GREY, POLYOLEFIN, 1.2, BORE 1.6MM

Pack size: **5 x EA**

- Sleeve Diameter: 1.6 mm
- Shrunk Diameter: 0.8 mm
- Colour: Grey
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



4834100 1.6 mm

RS PRO HEAT SHRINK TUBING, GREY 2.4MM SLEEVE DIA. X 1.2M LENGTH 2:1

Pack size: **5 x EA**

- Sleeve Diameter: 2.4 mm
- Shrunk Diameter: 1.2 mm
- Colour: Grey
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



4834122 2.4 mm

CABLE, HEATSHRINK, SLEEVE, GREY, POLYOLEFIN, 1.2, BORE 3.2MM

Pack size: **5 x EA**

- Sleeve Diameter: 3.2 mm
- Shrunk Diameter: 1.6 mm
- Colour: Grey
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



4834138 3.2 mm

CABLE, HEATSHRINK, SLEEVE, GREY, POLYOLEFIN, 1.2, BORE 4.8MM

Pack size: **5 x EA**

- Sleeve Diameter: 4.8 mm
- Shrunk Diameter: 2.4 mm
- Colour: Grey
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



4834144 4.8 mm

CABLE, HEATSHRINK, SLEEVE, GREY, POLYOLEFIN, 1.2, BORE 6.4MM

Pack size: **5 x EA**

- Sleeve Diameter: 6.4 mm
- Shrunk Diameter: 3.2 mm
- Colour: Grey
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



4834150 6.4 mm

RS PRO HEAT SHRINK TUBING, GREY 9.5MM SLEEVE DIA. X 1.2M LENGTH 2:1

Pack size: **5 x EA**

- Sleeve Diameter: 9.5 mm
- Shrunk Diameter: 4.8 mm
- Colour: Grey
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



4834166 9.5 mm

CABLE, HEATSHRINK, SLEEVE, GREY, POLYOLEFIN, 1.2, BORE 12.7MM

Pack size: **5 x EA**

- Sleeve Diameter: 12.7 mm
- Shrunk Diameter: 6.4 mm
- Colour: Grey
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



4834172 12.7 mm

CABLE, HEATSHRINK, SLEEVE, GREY, POLYOLEFIN, 1.2, BORE 19.1MM

Pack size: **5 x EA**

- Sleeve Diameter: 19 mm
- Shrunk Diameter: 9.5 mm
- Colour: Grey
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



4834188 19 mm

RS PRO HEAT SHRINK TUBING, GREY 25.4MM SLEEVE DIA. X 1.2M LENGTH

Pack size: **5 x EA**

- Sleeve Diameter: 25.4 mm
- Shrunk Diameter: 12.7 mm
- Colour: Grey
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



4834194 25.4 mm

RS PRO HEAT SHRINK TUBING, GREY 38MM SLEEVE DIA. X 1.2M LENGTH 2:1

Pack size: **5 x EA**

- Sleeve Diameter: 38 mm
- Shrunk Diameter: 19 mm
- Colour: Grey
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



4834201 38 mm

RS PRO HEAT SHRINK TUBING, GREY 50.8MM SLEEVE DIA. X 1.2M LENGTH

Pack size: **5 x EA**

- Sleeve Diameter: 50.8 mm
- Shrunk Diameter: 25.4 mm
- Colour: Grey
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



4834217 50.8 mm

RS PRO HEAT SHRINK TUBING, BROWN 3.2MM SLEEVE DIA. X 1.2M

Pack size: **5 x EA**

- Sleeve Diameter: 3.2 mm
- Shrunk Diameter: 1.6 mm
- Colour: Brown
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



4834245 3.2 mm

RS PRO HEAT SHRINK TUBING, BROWN 4.8MM SLEEVE DIA. X 1.2M

Pack size: **5 x EA**

- Sleeve Diameter: 4.8 mm
- Shrunk Diameter: 2.4 mm
- Colour: Brown
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



4834251 4.8 mm

CABLE, HEATSHRINK, SLEEVE, BROWN, POLYOLEFIN, 1.2, BORE 6.4MM

Pack size: **5 x EA**

- Sleeve Diameter: 6.4 mm
- Shrunk Diameter: 3.2 mm
- Colour: Brown
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



4834267 6.4 mm

RS PRO HEAT SHRINK TUBING, BROWN 9.5MM SLEEVE DIA. X 1.2M

Pack size: **5 x EA**

- Sleeve Diameter: 9.5 mm
- Shrunk Diameter: 4.8 mm
- Colour: Brown
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



4834289 9.5 mm

CABLE, HEATSHRINK, SLEEVE, BROWN, POLYOLEFIN, 1.2, BORE 12.7MM

Pack size: **5 x EA**

- Sleeve Diameter: 12.7 mm
- Shrunk Diameter: 6.4 mm
- Colour: Brown
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



4834295 12.7 mm

RS PRO HEAT SHRINK TUBING, BROWN 19MM SLEEVE DIA. X 1.2M

Pack size: **5 x EA**

- Sleeve Diameter: 19 mm
- Shrunk Diameter: 9.5 mm
- Colour: Brown
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



4834302 19 mm

RS PRO HEAT SHRINK TUBING, BROWN 25.4MM SLEEVE DIA. X 1.2M

Pack size: **5 x EA**

- Sleeve Diameter: 25.4 mm
- Shrunk Diameter: 12.7 mm
- Colour: Brown
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



4834318 25.4 mm

RS PRO HEAT SHRINK TUBING, BROWN 38MM SLEEVE DIA. X 1.2M

Pack size: **5 x EA**

- Sleeve Diameter: 38 mm
- Shrunk Diameter: 19 mm
- Colour: Brown
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



4834324 38 mm

RS PRO HEAT SHRINK TUBING, BROWN 50.8MM SLEEVE DIA. X 1.2M

Pack size: **5 x EA**

- Sleeve Diameter: 50.8 mm
- Shrunk Diameter: 25.4 mm
- Colour: Brown
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



4834346 50.8 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, BROWN 1.6MM SLEEVE DIA. X

Pack size: **1 x EA**

- Sleeve Diameter: 1.6 mm
- Shrunk Diameter: 0.8 mm
- Colour: Brown
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



5377945 1.6 mm

CABLE, HEATSHRINK, MEDIUM WALL, LFH, 2:1, BROWN, 2.4MM

Pack size: **1 x EA**

- Sleeve Diameter: 2.4 mm
- Shrunk Diameter: 1.2 mm
- Colour: Brown
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



5377967 2.4 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, BROWN 3.2MM SLEEVE DIA.

Pack size: **1 x EA**

- Sleeve Diameter: 3.2 mm
- Shrunk Diameter: 1.6 mm
- Colour: Brown
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



5377995 3.2 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, GREY 4.8MM SLEEVE DIA. X

Pack size: **1 x EA**

- Sleeve Diameter: 4.8 mm
- Shrunk Diameter: 2.4 mm
- Colour: Grey
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



5378005 4.8 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, BROWN 4.8MM SLEEVE DIA.

Pack size: **1 x EA**

- Sleeve Diameter: 4.8 mm
- Shrunk Diameter: 2.4 mm
- Colour: Brown
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



5378011 4.8 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, GREY 6.4MM SLEEVE DIA. X

Pack size: **1 x EA**

- Sleeve Diameter: 6.4 mm
- Shrunk Diameter: 3.2 mm
- Colour: Grey
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



5378027 6.4 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, BROWN 6.4MM SLEEVE DIA.

Pack size: **1 x EA**

- Sleeve Diameter: 6.4 mm
- Shrunk Diameter: 3.2 mm
- Colour: Brown
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



5378033 6.4 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, GREY 9.5MM SLEEVE DIA. X

Pack size: **1 x EA**

- Sleeve Diameter: 9.5 mm
- Shrunk Diameter: 4.8 mm
- Colour: Grey
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



5378049 9.5 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, GREY 12.7MM SLEEVE DIA. X

Pack size: **1 x EA**

- Sleeve Diameter: 12.7 mm
- Shrunk Diameter: 6.4 mm
- Colour: Grey
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



5378077 12.7 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, BROWN 12.7MM SLEEVE DIA.

Pack size: **1 x EA**

- Sleeve Diameter: 12.7 mm
- Shrunk Diameter: 6.4 mm
- Colour: Brown
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



5378083 12.7 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, GREY 19.1MM SLEEVE DIA. X

Pack size: **1 x EA**

- Sleeve Diameter: 19.1 mm
- Shrunk Diameter: 9.5 mm
- Colour: Grey
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



5378099 19.1 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, BROWN 19.1MM SLEEVE DIA.

Pack size: **1 x EA**

- Sleeve Diameter: 19.1 mm
- Shrunk Diameter: 9.5 mm
- Colour: Brown
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



5378106 19.1 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, GREY 25.4MM SLEEVE DIA. X

Pack size: **1 x EA**

- Sleeve Diameter: 25.4 mm
- Shrunk Diameter: 12.7 mm
- Colour: Grey
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



5378128 25.4 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, BROWN 25.4MM SLEEVE DIA.

Pack size: **1 x EA**

- Sleeve Diameter: 25.4 mm
- Shrunk Diameter: 12.7 mm
- Colour: Brown
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



5378134 25.4 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, GREY 38.1MM SLEEVE DIA. X

Pack size: **1 x EA**

- Sleeve Diameter: 38.1 mm
- Shrunk Diameter: 19.1 mm
- Colour: Grey
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



5378140 38.1 mm

RS PRO HALOGEN FREE HEAT SHRINK TUBING, BROWN 38.1MM SLEEVE DIA.

Pack size: **1 x EA**

- Sleeve Diameter: 38.1 mm
- Shrunk Diameter: 19.1 mm
- Colour: Brown
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 1.2 m
- Material: Polyolefin



5378156 38.1 mm

CLEAR HEATSHRINK TUBE 9/3MM I/D

Pack size: **5 x MTR**

- Sleeve Diameter: 9 mm
- Shrunk Diameter: 3 mm
- Colour: Clear
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 3:1
- Sleeve Length: 5 m
- Material: Polyolefin



7004450 9 mm

CLEAR HEATSHRINK TUBE 6/2MM I/D

Pack size: **7 x MTR**

- Sleeve Diameter: 6 mm
- Shrunk Diameter: 2 mm
- Colour: Clear
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 3:1
- Sleeve Length: 7 m
- Material: Polyolefin



7004456 6 mm

CLEAR HEATSHRINK TUBE 3/1MM I/D

Pack size: **10 x MTR**

- Sleeve Diameter: 3 mm
- Shrunk Diameter: 1 mm
- Colour: Clear
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 3:1
- Sleeve Length: 10 m
- Material: Polyolefin



7004453 3 mm

CLEAR HEATSHRINK TUBE 18/6MM I/D

Pack size: **3 x MTR**

- Sleeve Diameter: 18 mm
- Shrunk Diameter: 6 mm
- Colour: Clear
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 3:1
- Sleeve Length: 3 m
- Material: Polyolefin



7004462 18 mm

CLEAR HEATSHRINK TUBE 24/8MM I/D

Pack size: **3 x MTR**

- Sleeve Diameter: 24 mm
- Shrunk Diameter: 8 mm
- Colour: Clear
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 3:1
- Sleeve Length: 3 m
- Material: Polyolefin



7004466 24 mm

CLEAR HEATSHRINK TUBE 12/4MM I/D

Pack size: **4 x MTR**

- Sleeve Diameter: 12 mm
- Shrunk Diameter: 4 mm
- Colour: Clear
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 3:1
- Sleeve Length: 4 m
- Material: Polyolefin



7004469 12 mm

YELLOW HEATSHRINK TUBE 9/3MM I/D

Pack size: **5 x MTR**

- Sleeve Diameter: 9 mm
- Shrunk Diameter: 3 mm
- Colour: Yellow
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 3:1
- Sleeve Length: 5 m
- Material: Polyolefin



7004472 9 mm

YELLOW HEATSHRINK TUBE 3/1MM I/D

Pack size: **10 x MTR**

- Sleeve Diameter: 3 mm
- Shrunk Diameter: 1 mm
- Colour: Yellow
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 3:1
- Sleeve Length: 10 m
- Material: Polyolefin



7004475 3 mm

YELLOW HEATSHRINK TUBE 6/2MM I/D

Pack size: **7 x MTR**

- Sleeve Diameter: 6 mm
- Shrunk Diameter: 2 mm
- Colour: Yellow
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 3:1
- Sleeve Length: 7 m
- Material: Polyolefin



7004478 6 mm

RS PRO HEAT SHRINK TUBING, YELLOW 12MM SLEEVE DIA. X 4M

Pack size: **4 x MTR**

- Sleeve Diameter: 12 mm
- Shrunk Diameter: 4 mm
- Colour: Yellow
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 3:1
- Sleeve Length: 4 m
- Material: Polyolefin



7004481 12 mm

YELLOW HEATSHRINK TUBE 18/6MM I/D

Pack size: **3 x MTR**

- Sleeve Diameter: 18 mm
- Shrunk Diameter: 6 mm
- Colour: Yellow
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 3:1
- Sleeve Length: 3 m
- Material: Polyolefin



7004484 18 mm

YELLOW HEATSHRINK TUBE 24/8MM I/D

Pack size: **3 x MTR**

- Sleeve Diameter: 24 mm
- Shrunk Diameter: 8 mm
- Colour: Yellow
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 3:1
- Sleeve Length: 3 m
- Material: Polyolefin



7004488 24 mm

BLUE HEATSHRINK TUBE 6/2MM I/D

Pack size: **7 x MTR**

- Sleeve Diameter: 6 mm
- Shrunk Diameter: 2 mm
- Colour: Blue
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 3:1
- Sleeve Length: 7 m
- Material: Polyolefin



7004490 6 mm

BLUE HEATSHRINK TUBE 9/3MM I/D

Pack size: **5 x MTR**

- Sleeve Diameter: 9 mm
- Shrunk Diameter: 3 mm
- Colour: Blue
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 3:1
- Sleeve Length: 5 m
- Material: Polyolefin



7004494 9 mm

BLUE HEATSHRINK TUBE 3/1MM I/D

Pack size: **10 x MTR**

- Sleeve Diameter: 3 mm
- Shrunk Diameter: 1 mm
- Colour: Blue
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 3:1
- Sleeve Length: 10 m
- Material: Polyolefin



7004497 3 mm

BLUE HEATSHRINK TUBE 24/8MM I/D

Pack size: **3 x MTR**

- Sleeve Diameter: 24 mm
- Shrunk Diameter: 8 mm
- Colour: Blue
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 3:1
- Sleeve Length: 3 m
- Material: Polyolefin



7004501 24 mm

BLUE HEATSHRINK TUBE 12/4MM I/D

Pack size: **4 x MTR**

- Sleeve Diameter: 12 mm
- Shrunk Diameter: 4 mm
- Colour: Blue
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 3:1
- Sleeve Length: 4 m
- Material: Polyolefin



7004504 12 mm

BLUE HEATSHRINK TUBE 18/6MM I/D

Pack size: **3 x MTR**

- Sleeve Diameter: 18 mm
- Shrunk Diameter: 6 mm
- Colour: Blue
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 3:1
- Sleeve Length: 3 m
- Material: Polyolefin



7004507 18 mm

RED HEATSHRINK TUBE 3/1MM I/D

Pack size: **10 x MTR**

- Sleeve Diameter: 3 mm
- Shrunk Diameter: 1 mm
- Colour: Red
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 3:1
- Sleeve Length: 10 m
- Material: Polyolefin



7004510 3 mm

RED HEATSHRINK TUBE 6/2MM I/D

Pack size: **7 x MTR**

- Sleeve Diameter: 6 mm
- Shrunk Diameter: 2 mm
- Colour: Red
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 3:1
- Sleeve Length: 7 m
- Material: Polyolefin



7004513 6 mm

RED HEATSHRINK TUBE 9/3MM I/D

Pack size: **5 x MTR**

- Sleeve Diameter: 9 mm
- Shrunk Diameter: 3 mm
- Colour: Red
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 3:1
- Sleeve Length: 5 m
- Material: Polyolefin



7004517 9 mm

RED HEATSHRINK TUBE 24/8MM I/D

Pack size: **3 x MTR**

- Sleeve Diameter: 24 mm
- Shrunk Diameter: 8 mm
- Colour: Red
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 3:1
- Sleeve Length: 3 m
- Material: Polyolefin



7004523 24 mm

RED HEATSHRINK TUBE 12/4MM I/D

Pack size: **4 x MTR**

- Sleeve Diameter: 12 mm
- Shrunk Diameter: 4 mm
- Colour: Red
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 3:1
- Sleeve Length: 4 m
- Material: Polyolefin



7004526 12 mm

RED HEATSHRINK TUBE 18/6MM I/D

Pack size: **3 x MTR**

- Sleeve Diameter: 18 mm
- Shrunk Diameter: 6 mm
- Colour: Red
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 3:1
- Sleeve Length: 3 m
- Material: Polyolefin



7004529 18 mm

BLACK HEATSHRINK TUBE 3/1MM I/D

Pack size: **10 x MTR**

- Sleeve Diameter: 3 mm
- Shrunk Diameter: 1 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 3:1
- Sleeve Length: 10 m
- Material: Polyolefin



7004532 3 mm

BLACK HEATSHRINK TUBE 6/2MM I/D

Pack size: **7 x MTR**

- Sleeve Diameter: 6 mm
- Shrunk Diameter: 2 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 3:1
- Sleeve Length: 7 m
- Material: Polyolefin



7004535 6 mm

BLACK HEATSHRINK TUBE 9/3MM I/D

Pack size: **5 x MTR**

- Sleeve Diameter: 9 mm
- Shrunk Diameter: 3 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 3:1
- Sleeve Length: 5 m
- Material: Polyolefin



7004539 9 mm

BLACK HEATSHRINK TUBE 18/6MM I/D

Pack size: **3 x MTR**

- Sleeve Diameter: 18 mm
- Shrunk Diameter: 6 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 3:1
- Sleeve Length: 3 m
- Material: Polyolefin



7004541 18 mm

BLACK HEATSHRINK TUBE 24/8MM I/D

Pack size: **3 x MTR**

- Sleeve Diameter: 24 mm
- Shrunk Diameter: 8 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 3:1
- Sleeve Length: 3 m
- Material: Polyolefin



7004545 24 mm

BLACK HEATSHRINK TUBE 12/4MM I/D

Pack size: **4 x MTR**

- Sleeve Diameter: 12 mm
- Shrunk Diameter: 4 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 3:1
- Sleeve Length: 4 m
- Material: Polyolefin



7004548 12 mm

WHITE HEATSHRINK TUBE 9/3MM I/D

Pack size: **5 x MTR**

- Sleeve Diameter: 9 mm
- Shrunk Diameter: 3 mm
- Colour: White
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 3:1
- Sleeve Length: 5 m
- Material: Polyolefin



7004551 9 mm

WHITE HEATSHRINK TUBE 3/1MM I/D

Pack size: **10 x MTR**

- Sleeve Diameter: 3 mm
- Shrunk Diameter: 1 mm
- Colour: White
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 3:1
- Sleeve Length: 10 m
- Material: Polyolefin



7004554 3 mm

WHITE HEATSHRINK TUBE 6/2MM I/D

Pack size: **7 x MTR**

- Sleeve Diameter: 6 mm
- Shrunk Diameter: 2 mm
- Colour: White
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 3:1
- Sleeve Length: 7 m
- Material: Polyolefin



7004557 6 mm

WHITE HEATSHRINK TUBE 12/4MM I/D

Pack size: **4 x MTR**

- Sleeve Diameter: 12 mm
- Shrunk Diameter: 4 mm
- Colour: White
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 3:1
- Sleeve Length: 4 m
- Material: Polyolefin



7004560 12 mm

WHITE HEATSHRINK TUBE 18/6MM I/D

Pack size: **3 x MTR**

- Sleeve Diameter: 18 mm
- Shrunk Diameter: 6 mm
- Colour: White
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 3:1
- Sleeve Length: 3 m
- Material: Polyolefin



7004567 18 mm

WHITE HEATSHRINK TUBE 24/8MM I/D

Pack size: **3 x MTR**

- Sleeve Diameter: 24 mm
- Shrunk Diameter: 8 mm
- Colour: White
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 3:1
- Sleeve Length: 3 m
- Material: Polyolefin



7004573 24 mm

RS PRO HEAT SHRINK TUBING, GREEN, YELLOW 3MM SLEEVE DIA. X

Pack size: **10 x MTR**

- Sleeve Diameter: 3 mm
- Shrunk Diameter: 1 mm
- Colour: Green, Yellow
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 3:1
- Sleeve Length: 10 m
- Material: Polyolefin



7004582 3 mm

GREEN/YELLOW HEATSHRINK TUBE 6/2MM I/D

Pack size: **7 x MTR**

- Sleeve Diameter: 6 mm
- Shrunk Diameter: 2 mm
- Colour: Green, Yellow
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 3:1
- Sleeve Length: 7 m
- Material: Polyolefin



7004589 6 mm

GREEN/YELLOW HEATSHRINK TUBE 9/3MM I/D

Pack size: **5 x MTR**

- Sleeve Diameter: 9 mm
- Shrunk Diameter: 3 mm
- Colour: Green, Yellow
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 3:1
- Sleeve Length: 5 m
- Material: Polyolefin



7004595 9 mm

GREEN/YELLOW HEATSHRINK TUBE 12/4MM I/D

Pack size: **4 x MTR**

- Sleeve Diameter: 12 mm
- Shrunk Diameter: 4 mm
- Colour: Green, Yellow
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 3:1
- Sleeve Length: 4 m
- Material: Polyolefin



7004608 12 mm

GREEN/YELLOW HEATSHRINK TUBE 18/6MM I/D

Pack size: **3 x MTR**

- Sleeve Diameter: 18 mm
- Shrunk Diameter: 6 mm
- Colour: Green, Yellow
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 3:1
- Sleeve Length: 3 m
- Material: Polyolefin



7004611 18 mm

GREEN/YELLOW HEATSHRINK TUBE 24/8MM I/D

Pack size: **3 x MTR**

- Sleeve Diameter: 24 mm
- Shrunk Diameter: 8 mm
- Colour: Green, Yellow
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 3:1
- Sleeve Length: 3 m
- Material: Polyolefin



7004618 24 mm

BLACK LOW SHRINK TEMP TUBE 1.6MM I/D

Pack size: **10 x MTR**

- Sleeve Diameter: 1.6 mm
- Shrunk Diameter: 0.8 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 10 m
- Material: Polyolefin



7004620 1.6 mm

BLACK LOW SHRINK TEMP TUBE 2.4MM I/D

Pack size: **10 x MTR**

- Sleeve Diameter: 2.4 mm
- Shrunk Diameter: 1.2 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 10 m
- Material: Polyolefin



7004624 2.4 mm

BLACK LOW SHRINK TEMP TUBE 3.2MM I/D

Pack size: **10 x MTR**

- Sleeve Diameter: 3.2 mm
- Shrunk Diameter: 1.6 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 10 m
- Material: Polyolefin



7004630 3.2 mm

BLACK LOW SHRINK TEMP TUBE 6.4MM I/D

Pack size: **8 x MTR**

- Sleeve Diameter: 6.4 mm
- Shrunk Diameter: 3.2 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 8 m
- Material: Polyolefin



7004646 6.4 mm

BLACK LOW SHRINK TEMP TUBE 4.8MM I/D

Pack size: **9 x MTR**

- Sleeve Diameter: 4.8 mm
- Shrunk Diameter: 2.4 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 9 m
- Material: Polyolefin



7004649 4.8 mm

BLACK LOW SHRINK TEMP TUBE 9.5MM I/D

Pack size: **6 x MTR**

- Sleeve Diameter: 9.5 mm
- Shrunk Diameter: 4.8 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 6 m
- Material: Polyolefin



7004658 9.5 mm

BLACK LOWSHRINK TEMP TUBE 12.7MM I/D

Pack size: **6 x MTR**

- Sleeve Diameter: 12.7 mm
- Shrunk Diameter: 6.4 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 6 m
- Material: Polyolefin



7004661 12.7 mm

BLACK LOWSHRINK TEMP TUBE 19.0MM I/D

Pack size: **5 x MTR**

- Sleeve Diameter: 19 mm
- Shrunk Diameter: 9.5 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 5 m
- Material: Polyolefin



7004664 19 mm

BLACK LOWSHRINK TEMP TUBE 25.4MM I/D

Pack size: **3 x MTR**

- Sleeve Diameter: 25.4 mm
- Shrunk Diameter: 12.7 mm
- Colour: Black
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 3 m
- Material: Polyolefin



7004668 25.4 mm

RED LOW SHRINK TEMP TUBE 2.4MM I/D

Pack size: **10 x MTR**

- Sleeve Diameter: 2.4 mm
- Shrunk Diameter: 1.2 mm
- Colour: Red
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 10 m
- Material: Polyolefin



7004670 2.4 mm

RED LOW SHRINK TEMP TUBE 3.2MM I/D

Pack size: **10 x MTR**

- Sleeve Diameter: 3.2 mm
- Shrunk Diameter: 1.6 mm
- Colour: Red
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 10 m
- Material: Polyolefin



7004674 3.2 mm

RED LOW SHRINK TEMP TUBE 1.6MM I/D

Pack size: **10 x MTR**

- Sleeve Diameter: 1.6 mm
- Shrunk Diameter: 0.8 mm
- Colour: Red
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 10 m
- Material: Polyolefin



7004677 1.6 mm

RED LOW SHRINK TEMP TUBE 9.5MM I/D

Pack size: **6 x MTR**

- Sleeve Diameter: 9.5 mm
- Shrunk Diameter: 4.8 mm
- Colour: Red
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 6 m
- Material: Polyolefin



7004680 9.5 mm

RED LOW SHRINK TEMP TUBE 4.8MM I/D

Pack size: **9 x MTR**

- Sleeve Diameter: 4.8 mm
- Shrunk Diameter: 2.4 mm
- Colour: Red
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 9 m
- Material: Polyolefin



7004683 4.8 mm

RED LOW SHRINK TEMP TUBE 6.4MM I/D

Pack size: **8 x MTR**

- Sleeve Diameter: 6.4 mm
- Shrunk Diameter: 3.2 mm
- Colour: Red
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 8 m
- Material: Polyolefin



7004686 6.4 mm

RED LOW SHRINK TEMP TUBE 19.0MM I/D

Pack size: **5 x MTR**

- Sleeve Diameter: 19 mm
- Shrunk Diameter: 9.5 mm
- Colour: Red
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 5 m
- Material: Polyolefin



7004692 19 mm

RED LOW SHRINK TEMP TUBE 25.4MM I/D

Pack size: **3 x MTR**

- Sleeve Diameter: 25.4 mm
- Shrunk Diameter: 12.7 mm
- Colour: Red
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 3 m
- Material: Polyolefin



7004696 25.4 mm

RED LOW SHRINK TEMP TUBE 12.7MM I/D

Pack size: **6 x MTR**

- Sleeve Diameter: 12.7 mm
- Shrunk Diameter: 6.4 mm
- Colour: Red
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 6 m
- Material: Polyolefin



7004699 12.7 mm

RS PRO HEAT SHRINK TUBING, YELLOW 3.2MM SLEEVE DIA. X 10M

Pack size: **10 x MTR**

- Sleeve Diameter: 3.2 mm
- Shrunk Diameter: 1.6 mm
- Colour: Yellow
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 10 m
- Material: Polyolefin



7004703 3.2 mm

RS PRO HEAT SHRINK TUBING, YELLOW 1.6MM SLEEVE DIA. X 10M

Pack size: **10 x MTR**

- Sleeve Diameter: 1.6 mm
- Shrunk Diameter: 0.8 mm
- Colour: Yellow
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 10 m
- Material: Polyolefin



7004706 1.6 mm

YELLOW LOW SHRINK TEMP TUBE 2.4MM I/D

Pack size: **10 x MTR**

- Sleeve Diameter: 2.4 mm
- Shrunk Diameter: 1.2 mm
- Colour: Yellow
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 10 m
- Material: Polyolefin



7004709 2.4 mm

RS PRO HEAT SHRINK TUBING, YELLOW 4.8MM SLEEVE DIA. X 9M

Pack size: **9 x MTR**

- Sleeve Diameter: 4.8 mm
- Shrunk Diameter: 2.4 mm
- Colour: Yellow
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 9 m
- Material: Polyolefin



7004712 4.8 mm

RS PRO HEAT SHRINK TUBING, YELLOW 6.4MM SLEEVE DIA. X 8M

Pack size: **8 x MTR**

- Sleeve Diameter: 6.4 mm
- Shrunk Diameter: 3.2 mm
- Colour: Yellow
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 8 m
- Material: Polyolefin



7004715 6.4 mm

YELLOW LOW SHRINK TEMP TUBE 9.5MM I/D

Pack size: **6 x MTR**

- Sleeve Diameter: 9.5 mm
- Shrunk Diameter: 4.8 mm
- Colour: Yellow
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 6 m
- Material: Polyolefin



7004719 9.5 mm

RS PRO HEAT SHRINK TUBING, YELLOW 19MM SLEEVE DIA. X 5M

Pack size: **5 x MTR**

- Sleeve Diameter: 19 mm
- Shrunk Diameter: 9.5 mm
- Colour: Yellow
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 5 m
- Material: Polyolefin



7004721 19 mm

RS PRO HEAT SHRINK TUBING, YELLOW 25.4MM SLEEVE DIA. X 3M

Pack size: **3 x MTR**

- Sleeve Diameter: 25.4 mm
- Shrunk Diameter: 12.7 mm
- Colour: Yellow
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 3 m
- Material: Polyolefin



7004725 25.4 mm

YELLOW LOW SHRINK TEMP TUBE 12.7MM I/D

Pack size: **6 x MTR**

- Sleeve Diameter: 12.7 mm
- Shrunk Diameter: 6.4 mm
- Colour: Yellow
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 6 m
- Material: Polyolefin



7004728 12.7 mm

BLUE LOW SHRINK TEMP TUBE 3.2MM I/D

Pack size: **10 x MTR**

- Sleeve Diameter: 3.2 mm
- Shrunk Diameter: 1.6 mm
- Colour: Blue
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 10 m
- Material: Polyolefin



7004731 3.2 mm

BLUE LOW SHRINK TEMP TUBE 1.6MM I/D

Pack size: **10 x MTR**

- Sleeve Diameter: 1.6 mm
- Shrunk Diameter: 0.8 mm
- Colour: Blue
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 10 m
- Material: Polyolefin



7004734 1.6 mm

BLUE LOW SHRINK TEMP TUBE 2.4MM I/D

Pack size: **10 x MTR**

- Sleeve Diameter: 2.4 mm
- Shrunk Diameter: 1.2 mm
- Colour: Blue
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 10 m
- Material: Polyolefin



7004737 2.4 mm

BLUE LOW SHRINK TEMP TUBE 4.8MM I/D

Pack size: **9 x MTR**

- Sleeve Diameter: 4.8 mm
- Shrunk Diameter: 2.4 mm
- Colour: Blue
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 9 m
- Material: Polyolefin



7004740 4.8 mm

RS PRO HEAT SHRINK TUBING, BLUE 6.4MM SLEEVE DIA. X 8M LENGTH 2:1

Pack size: **8 x MTR**

- Sleeve Diameter: 6.4 mm
- Shrunk Diameter: 3.2 mm
- Colour: Blue
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 8 m
- Material: Polyolefin



7004743 6.4 mm

RS PRO HEAT SHRINK TUBING, BLUE 9.5MM SLEEVE DIA. X 6M LENGTH 2:1

Pack size: **6 x MTR**

- Sleeve Diameter: 9.5 mm
- Shrunk Diameter: 4.8 mm
- Colour: Blue
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 6 m
- Material: Polyolefin



7004747 9.5 mm

BLUE LOW SHRINK TEMP TUBE 25.4MM I/D

Pack size: **3 x MTR**

- Sleeve Diameter: 25.4 mm
- Shrunk Diameter: 12.7 mm
- Colour: Blue
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 3 m
- Material: Polyolefin



7004753 25.4 mm

BLUE LOW SHRINK TEMP TUBE 12.7MM I/D

Pack size: **6 x MTR**

- Sleeve Diameter: 12.7 mm
- Shrunk Diameter: 6.4 mm
- Colour: Blue
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 6 m
- Material: Polyolefin



7004756 12.7 mm

BLUE LOW SHRINK TEMP TUBE 19.0MM I/D

Pack size: **5 x MTR**

- Sleeve Diameter: 19 mm
- Shrunk Diameter: 9.5 mm
- Colour: Blue
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 5 m
- Material: Polyolefin



7004759 19 mm

RS PRO HEAT SHRINK TUBING, WHITE 1.6MM SLEEVE DIA. X 10M LENGTH 2:1

Pack size: **10 x MTR**

- Sleeve Diameter: 1.6 mm
- Shrunk Diameter: 0.8 mm
- Colour: White
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 10 m
- Material: Polyolefin



7004762 1.6 mm

WHITE LOW SHRINK TEMP TUBE 2.4MM I/D

Pack size: **10 x MTR**

- Sleeve Diameter: 2.4 mm
- Shrunk Diameter: 1.2 mm
- Colour: White
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 10 m
- Material: Polyolefin



7004765 2.4 mm

WHITE LOW SHRINK TEMP TUBE 3.2MM I/D

Pack size: **10 x MTR**

- Sleeve Diameter: 3.2 mm
- Shrunk Diameter: 1.6 mm
- Colour: White
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 10 m
- Material: Polyolefin



7004769 3.2 mm

WHITE LOW SHRINK TEMP TUBE 6.4MM I/D

Pack size: **8 x MTR**

- Sleeve Diameter: 6.4 mm
- Shrunk Diameter: 3.2 mm
- Colour: White
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 8 m
- Material: Polyolefin



7004771 6.4 mm

WHITE LOW SHRINK TEMP TUBE 9.5MM I/D

Pack size: **6 x MTR**

- Sleeve Diameter: 9.5 mm
- Shrunk Diameter: 4.8 mm
- Colour: White
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 6 m
- Material: Polyolefin



7004775 9.5 mm

WHITE LOW SHRINK TEMP TUBE 4.8MM I/D

Pack size: **9 x MTR**

- Sleeve Diameter: 4.8 mm
- Shrunk Diameter: 2.4 mm
- Colour: White
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 9 m
- Material: Polyolefin



7004778 4.8 mm

RS PRO HEAT SHRINK TUBING, WHITE 25.4MM SLEEVE DIA. X 3M LENGTH 2:1

Pack size: **3 x MTR**

- Sleeve Diameter: 25.4 mm
- Shrunk Diameter: 12.7 mm
- Colour: White
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 3 m
- Material: Polyolefin



7004781 25.4 mm

WHITE LOW SHRINK TEMP TUBE 12.7MM I/D

Pack size: **6 x MTR**

- Sleeve Diameter: 12.7 mm
- Shrunk Diameter: 6.4 mm
- Colour: White
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 6 m
- Material: Polyolefin



7004784 12.7 mm

WHITE LOW SHRINK TEMP TUBE 19.0MM I/D

Pack size: **5 x MTR**

- Sleeve Diameter: 19 mm
- Shrunk Diameter: 9.5 mm
- Colour: White
- Sleeve Type: Heat Shrink
- Adhesive Lined: No
- Shrink Ratio: 2:1
- Sleeve Length: 5 m
- Material: Polyolefin



7004787 19 mm

CABLE,TIES,ONE WRAP,HOOK/LOOP,50 PCS,200MML

Pack size: **1 x EA**

- Width: 20 mm
- Length: 200 mm
- Hook Type: Hook & Loop
- Pre-cut Width: 20 x 200 mm



4499189 20 mm

CABLE,CLAMP,P CLIPS,NATURAL,9.5MM DIA

Pack size: **100 x EA**

- Closed Inside Diameter: 9.5 mm
- Width: 12 mm
- Fixing Hole Diameter: 5 mm
- Material: Nylon
- Coating/Lining: None
- Colour: Natural



479538 9.5 mm

RS PRO 25.4MM NATURAL NYLON P CLIP

Pack size: **100 x EA**

- Closed Inside Diameter: 25.4 mm
- Width: 12 mm
- Fixing Hole Diameter: 4.6 mm
- Material: Nylon
- Coating/Lining: None
- Colour: Natural



479554 25.4 mm

RS PRO 7.9MM NATURAL NYLON 66 P CLIP

Pack size: **100 x EA**

- Closed Inside Diameter: 7.9 mm
- Width: 10 mm
- Fixing Hole Diameter: 5 mm
- Material: Nylon 66
- Colour: Natural



2209397 7.9 mm

RS PRO 15.8MM NATURAL NYLON 66 P CLIP

Pack size: **100 x EA**

- Closed Inside Diameter: 15.8 mm
- Width: 14.4 mm
- Fixing Hole Diameter: 5 mm
- Material: Nylon 66
- Colour: Natural



2209398 15.8 mm

RS PRO 5MM BLACK NYLON 66 P CLIP

Pack size: **100 x EA**

- Closed Inside Diameter: 5 mm
- Width: 9.6 mm
- Fixing Hole Diameter: 4.8 mm
- Material: Nylon 66
- Colour: Black



2209399 5 mm

RS PRO CABLE CLAMP, BLACK NYLON 66, 9.4V-

Pack size: **100 x EA**

- Closed Inside Diameter: 6.4 mm
- Width: 10.1 mm
- Fixing Hole Diameter: 4.6 mm
- Material: Nylon 66
- Colour: Black



2209400 6.4 mm

RS PRO 7.9MM BLACK NYLON 66 P CLIP

Pack size: **100 x EA**

- Closed Inside Diameter: 7.9 mm
- Width: 10 mm
- Fixing Hole Diameter: 5 mm
- Material: Nylon 66
- Colour: Black



2209402 7.9 mm

RS PRO 9.5MM BLACK NYLON 66 P CLIP

Pack size: **100 x EA**

- Closed Inside Diameter: 9.5 mm
- Width: 12.3 mm
- Fixing Hole Diameter: 5 mm
- Material: Nylon 66
- Colour: Black



2209403 9.5 mm

RS PRO 12.7MM BLACK NYLON 66 P CLIP

Pack size: **100 x EA**

- Closed Inside Diameter: 12.7 mm
- Width: 12.2 mm
- Fixing Hole Diameter: 5 mm
- Material: Nylon 66
- Colour: Black



2209404 12.7 mm

RS PRO 15.8MM BLACK NYLON 66 P CLIP

Pack size: **100 x EA**

- Closed Inside Diameter: 15.8 mm
- Width: 14.4 mm
- Fixing Hole Diameter: 5 mm
- Material: Nylon 66
- Colour: Black



2209405 15.8 mm

CABLE,P CLIP,NYLON,4.8/6.4MM DIA

Pack size: **25 x EA**

- Closed Inside Diameter: 6.4 mm
- Width: 13 mm
- Fixing Hole Diameter: 5 x 10.4 mm, 5.5 mm
- Material: Nylon
- Coating/Lining: None
- Colour: Natural



4726396 6.4 mm

CABLE,P CLIP,NYLON 6.4/9.5MM DIA

Pack size: **25 x EA**

- Closed Inside Diameter: 9.5 mm
- Width: 13 mm
- Fixing Hole Diameter: 5 x 16.1 mm, 5.5 mm
- Material: Nylon
- Coating/Lining: None
- Colour: Natural



4726403 9.5 mm

CABLE,P CLIP,NYLON,9.5/14.3,MM DIA

Pack size: **25 x EA**

- Closed Inside Diameter: 14.3 mm
- Width: 13 mm
- Fixing Hole Diameter: 5 x 20.7 mm, 5.5 mm
- Material: Nylon
- Coating/Lining: None
- Colour: Natural



4726425 14.3 mm

RS PRO BLUE LOW-DENSITY POLYETHYLENE SOLDER SLEEVE

Pack size: **100 x EA**

- Minimum Cable Diameter: 3.7 mm
- Maximum Cable Diameter: 6 mm
- Sleeve Length: 32.5 mm
- Material: Low-Density Polyethylene
- Dielectric Strength: 1 kV
- Minimum Operating Temperature: -55 °C
- Maximum Operating Temperature: +125 °C
- Quantity: 1



8726280 3.7 mm

SOLDER SLEEVE SIZE 1

Pack size: **100 x EA**

- Minimum Cable Diameter: 1.4 mm
- Maximum Cable Diameter: 2.7 mm
- Sleeve Length: 24.5 mm
- Material: Low-Density Polyethylene
- Dielectric Strength: 1 kV
- Minimum Operating Temperature: -55 °C
- Maximum Operating Temperature: +125 °C
- Quantity: 1



8726283 1.4 mm

RS PRO BLUE LOW-DENSITY POLYETHYLENE SOLDER SLEEVE

Pack size: **100 x EA**

- Minimum Cable Diameter: 2.3 mm
- Maximum Cable Diameter: 4.5 mm
- Sleeve Length: 29.3 mm
- Material: Low-Density Polyethylene
- Dielectric Strength: 1 kV
- Minimum Operating Temperature: -55 °C
- Maximum Operating Temperature: +125 °C
- Quantity: 1



8726286 2.3 mm

SOLDER SLEEVE ASSORTMENT KIT

Pack size: **25 x EA**

- Minimum Cable Diameter: 1.4 mm
- Maximum Cable Diameter: 13 mm
- Material: Low-Density Polyethylene
- Minimum Operating Temperature: -55 °C
- Maximum Operating Temperature: +125 °C
- Quantity: 25
- Colour: Transparent
- Standards Met: RoHS Compliant



8726296 1.4 mm

RS PRO BLUE LOW-DENSITY POLYETHYLENE SOLDER SLEEVE

Pack size: **25 x EA**

- Minimum Cable Diameter: 5.8 mm
- Maximum Cable Diameter: 11.5 mm
- Sleeve Length: 35.5 mm
- Material: Low-Density Polyethylene
- Dielectric Strength: 1 kV
- Minimum Operating Temperature: -55 °C
- Maximum Operating Temperature: +125 °C
- Quantity: 1



8726299 5.8 mm

HEATSHRINK,CABLE,SLEEVE,CRIMP SPLICE TERMINAL,RED,X10

Pack size: **10 x EA**

- Insulation: Insulated



4580702 Insulated

HEATSHRINK,CABLE,SLEEVE,CRIMP SPLICE TERMINAL,BLUE,X10

Pack size: **10 x EA**

- Insulation: Insulated



4580718 Insulated

HEATSHRINK,CABLE,SLEEVE,CRIMP SPLICE TERMINAL,YELLOW,X10

Pack size: **10 x EA**

- Insulation: Insulated



4580724 Insulated

HEAT SHRINK BUTT, RED 0.5-1.5MM

Pack size: **10 x EA**

- Sleeve Length: 35 mm
- Material: Copper
- Voltage Rating: 600 V
- Minimum Operating Temperature: -55 °C
- Maximum Operating Temperature: +125 °C
- Shrink Temperature: +150 °C
- Colour: Red



8199870 35 mm

HEAT SHRINK BUTT BLUE 1.5-2.5MM

Pack size: **10 x EA**

- Sleeve Length: 35 mm
- Material: Copper
- Voltage Rating: 600 V
- Minimum Operating Temperature: -55 °C
- Maximum Operating Temperature: +125 °C
- Shrink Temperature: +150 °C
- Colour: Blue



8199874 35 mm

RS PRO WIRE SPLICE CONNECTOR

Pack size: **10 x EA**

- Sleeve Length: 41 mm
- Material: Copper
- Voltage Rating: 600 V
- Minimum Operating Temperature: -55 °C
- Maximum Operating Temperature: +125 °C
- Shrink Temperature: +150 °C
- Colour: Yellow



8199883 41 mm

RS PRO WIRE STRIPPER

Pack size: **1 x EA**

- Accessory Type: Cable Stripper
- For Use With: Smart Meter Cable



1749107 Cable Stripper

RS PRO WIRE STRIPPER

Pack size: **1 x EA**

- Accessory Type: Cable Stripper
- For Use With: Smart Meter Cable



1749108 Cable Stripper

RS PRO STEEL GALVANISED ADAPTABLE BOX, 75MM X 75MM X

Pack size: **1 x EA**

- Material: Steel
- Finish: Galvanised
- Length: 75 mm
- Width: 75 mm
- Depth: 50 mm
- Height: 75 mm
- Knockout Size: 20/25 mm



563898 Steel

CONDUIT,STEEL,ADAPTABLE BOX,GALVANISED,100X100X50MM

Pack size: **1 x EA**

- Material: Steel
- Finish: Galvanised
- Number of Knockouts: 8
- Length: 100 mm
- Width: 100 mm
- Depth: 50 mm
- Height: 100 mm
- Knockout Size: 20/25 mm



563905 Steel

RS PRO 304 STAINLESS STEEL SATIN ADAPTABLE ENCLOSURE BOX, 100MM

Pack size: **1 x EA**

- Material: 304 Stainless Steel
- Finish: Satin
- Length: 100 mm
- Width: 100 mm
- Depth: 50 mm
- Height: 100 mm



1219691 304 Stainless

RS PRO 304 STAINLESS STEEL SATIN ADAPTABLE ENCLOSURE BOX, 100MM

Pack size: **1 x EA**

- Material: 304 Stainless Steel
- Finish: Satin
- Length: 100 mm
- Width: 100 mm
- Depth: 50 mm
- Height: 160 mm



1219692 304 Stainless

RS PRO 304 STAINLESS STEEL SATIN ADAPTABLE ENCLOSURE BOX, 100MM

Pack size: **1 x EA**

- Material: 304 Stainless Steel
- Finish: Satin
- Length: 100 mm
- Width: 100 mm
- Depth: 85 mm
- Height: 100 mm



1219693 304 Stainless

RS PRO 304 STAINLESS STEEL SATIN ADAPTABLE ENCLOSURE BOX, 160MM

Pack size: **1 x EA**

- Material: 304 Stainless Steel
- Finish: Satin
- Length: 160 mm
- Width: 100 mm
- Depth: 85 mm
- Height: 160 mm



1219694 304 Stainless

RS PRO 304 STAINLESS STEEL SATIN ADAPTABLE ENCLOSURE BOX, 220MM

Pack size: **1 x EA**

- Material: 304 Stainless Steel
- Finish: Satin
- Length: 220 mm
- Width: 100 mm
- Depth: 85 mm
- Height: 220 mm



1219695 304 Stainless

RS PRO 304 STAINLESS STEEL SATIN ADAPTABLE ENCLOSURE BOX, 220MM

Pack size: **1 x EA**

- Material: 304 Stainless Steel
- Finish: Satin
- Length: 220 mm
- Width: 160 mm
- Depth: 85 mm
- Height: 220 mm



1219697 304 Stainless

RS PRO 304 STAINLESS STEEL SATIN ADAPTABLE ENCLOSURE BOX, 280MM

Pack size: **1 x EA**

- Material: 304 Stainless Steel
- Finish: Satin
- Length: 280 mm
- Width: 220 mm
- Depth: 85 mm
- Height: 280 mm



1219699 304 Stainless

RS PRO 304 STAINLESS STEEL SATIN ADAPTABLE BOX, 75MM X 75MM X

Pack size: **1 x EA**

- Material: 304 Stainless Steel
- Finish: Satin
- Length: 75 mm
- Width: 75 mm
- Depth: 50 mm
- Height: 75 mm



1466772 304 Stainless

RS PRO 316 STAINLESS STEEL SATIN ADAPTABLE ENCLOSURE BOX, 104MM

Pack size: **1 x EA**

- Material: 316 Stainless Steel
- Finish: Satin
- Length: 104 mm
- Width: 104 mm
- Depth: 50 mm
- Height: 104 mm



4711580 316 Stainless

RS PRO 316 STAINLESS STEEL SATIN ADAPTABLE ENCLOSURE BOX, 160MM

Pack size: **1 x EA**

- Material: 316 Stainless Steel
- Finish: Satin
- Length: 160 mm
- Width: 160 mm
- Depth: 85 mm
- Height: 160 mm



4711625 316 Stainless

RS PRO 316 STAINLESS STEEL SATIN ADAPTABLE ENCLOSURE BOX, 220MM

Pack size: **1 x EA**

- Material: 316 Stainless Steel
- Finish: Satin
- Length: 220 mm
- Width: 220 mm
- Depth: 85 mm
- Height: 220 mm



4711631 316 Stainless

RS PRO STEEL ADAPTABLE BOX, 75MM X 75MM X 50MM

Pack size: **1 x EA**

- Material: Steel
- Length: 75 mm
- Width: 75 mm
- Depth: 50 mm
- Height: 75 mm



7639201 Steel

RS PRO STEEL ADAPTABLE BOX, 100MM X 100MM X 50MM

Pack size: **1 x EA**

- Material: Steel
- Length: 100 mm
- Width: 100 mm
- Depth: 50 mm
- Height: 100 mm



7639204 Steel

RS PRO ADAPTABLE BOX, 150MM X 150MM X 50MM

Pack size: **1 x EA**

- Length: 150 mm
- Width: 150 mm
- Depth: 50 mm
- Height: 150 mm



7639208 150 mm

RS PRO STEEL GALVANISED ADAPTABLE BOX, 150MM X 150MM X

Pack size: **1 x EA**

- Material: Steel
- Finish: Galvanised
- Length: 150 mm
- Width: 150 mm
- Depth: 50 mm
- Height: 150 mm



7639242 Steel

RS PRO STEEL GALVANISED ADAPTABLE BOX, 100MM X 100MM X

Pack size: **1 x EA**

- Material: Steel
- Finish: Galvanised
- Length: 100 mm
- Width: 100 mm
- Depth: 50 mm
- Height: 100 mm



7639248 Steel

RS PRO STEEL GALVANISED ADAPTABLE BOX, 75MM X 75MM X

Pack size: **1 x EA**

- Material: Steel
- Finish: Galvanised
- Length: 75 mm
- Width: 75 mm
- Depth: 50 mm
- Height: 75 mm



7639251 Steel

RS PRO GREY BACK BOX, BS, IP20, 1 GANGS

Pack size: **1 x EA**

- Number of Gangs: 1
- Depth: 42 mm
- Series: RS Metalclad
- Earth Terminal: Yes
- Width: 86 mm
- Colour Shade: Grey
- Colour: Grey
- IP Rating: IP20



3611962 1

RS PRO GREY BACK BOX, BS, IP20, 2 GANGS

Pack size: **1 x EA**

- Number of Gangs: 2
- Depth: 42 mm
- Series: RS Metalclad
- Earth Terminal: Yes
- Width: 147 mm
- Colour Shade: Grey
- Colour: Grey
- IP Rating: IP20



3611984 2

RS PRO WHITE PVC ELECTRICAL ENCLOSURE, BS, 2 GANGS, 147 X 86 X

Pack size: **1 x EA**

- Number of Gangs: 2
- Depth: 32 mm
- Series: Mini
- Material: PVC
- Earth Terminal: No
- Width: 147 mm
- Colour: White
- Dimensions: 147 x 86 x 32 mm



9171615 2

RS PRO WHITE PVC BACK BOX, BS, 2 GANGS

Pack size: **1 x EA**

- Number of Gangs: 2
- Depth: 32 mm
- Material: PVC
- Series: Mini
- Earth Terminal: No
- Width: 147 mm
- Colour: White
- Fixing Standard: BS



9171637 2

CONNECTOR, TERMINAL, SCREW, SINGLE POLE, INTERLOCKING, TAB/TAB

Pack size: **10 x EA**

- Number of Contacts: 1
- Contact Material: Steel
- Contact Plating: Zinc
- Screw Size: M4
- Wire Size: 22 → 12 AWG
- Material: Polyamide
- Fixing Centre: 11.2 mm
- Current Rating: 20 A



425415 1

RS PRO BARRIER STRIP, 1 CONTACT, 20A, 600 V

Pack size: **10 x EA**

- Number of Contacts: 1
- Contact Material: Steel
- Contact Plating: Zinc
- Screw Size: M4
- Wire Size: 22 → 12 AWG
- Material: Polyamide
- Fixing Centre: 11.2 mm
- Current Rating: 20 A



425421 1

CONNECTOR, TERMINAL, GROUP PANEL, MIN

Pack size: **5 x EA**

- Number of Contacts: 36
- Pitch: 6.35 mm
- Number of Rows: 2
- Dimensions: 117 x 38 x 7.5 mm
- Depth: 38 mm
- Length: 117 mm
- Width: 38 mm



433703 36

CONNECTOR, TERMINAL, TAG STRIP, STD

Pack size: **10 x EA**

- Number of Contacts: 28
- Pitch: 9.5 mm
- Fixing Centre: 28.6 mm
- Dimensions: 266.7 x 17.9 x 10.6 mm
- Depth: 10.6 mm
- Width: 17.9 mm
- Length: 266.7 mm



433775 28

RS PRO BARRIER STRIP, 28 CONTACT, 6.3MM PITCH

Pack size: **10 x EA**

- Number of Contacts: 28
- Pitch: 6.3 mm
- Fixing Centre: 28.6 mm
- Dimensions: 194 x 16.7 x 4 mm
- Depth: 4 mm
- Width: 16.7 mm
- Length: 194 mm



433781 28

RS PRO BARRIER STRIP, 9.5MM PITCH, 20A, 750 V, SCREW

Pack size: **5 x EA**

- Pitch: 9.5 mm
- Contact Material: Brass
- Contact Plating: Tin
- Wire Size: 12 AWG
- Material: Polyamide
- Current Rating: 20 A
- Voltage Rating: 750 V
- Minimum Operating Temperature: -40 °C



7638110 9.5 mm

RS PRO NATURAL STEEL SADDLE CLAMP, 20MM MAX. BUNDLE

Pack size: **50 x EA**

- Cable Clip/Clamp Style: Saddle Clamp
- Maximum Bundle Diameter: 20 mm
- Affixing Method: Screw
- Material: Steel
- Colour: Natural



605100 Saddle Clamp

RS PRO NATURAL GALVANISED STEEL SADDLE CLAMP, 20MM MAX. BUNDLE

Pack size: **25 x EA**

- Cable Clip/Clamp Style: Saddle Clamp
- Maximum Bundle Diameter: 20 mm
- Affixing Method: Screw
- Material: Galvanised Steel
- Colour: Natural



606002 Saddle Clamp

RS PRO NATURAL STEEL SADDLE CLAMP, 25MM MAX. BUNDLE

Pack size: **25 x EA**

- Cable Clip/Clamp Style: Saddle Clamp
- Maximum Bundle Diameter: 25 mm
- Affixing Method: Screw
- Material: Steel
- Colour: Natural



606018 Saddle Clamp

RS PRO BLACK STEEL SADDLE CLAMP, 20MM MAX. BUNDLE

Pack size: **50 x EA**

- Cable Clip/Clamp Style: Saddle Clamp
- Maximum Bundle Diameter: 20 mm
- Affixing Method: Screw
- Material: Steel
- Colour: Black



608121 Saddle Clamp

RS PRO BLACK STEEL SADDLE CLAMP, 20MM MAX. BUNDLE

Pack size: **25 x EA**

- Cable Clip/Clamp Style: Saddle Clamp
- Maximum Bundle Diameter: 20 mm
- Affixing Method: Screw
- Material: Steel
- Colour: Black



608143 Saddle Clamp

RS PRO BLACK NYLON P CLAMP, 20MM MAX. BUNDLE

Pack size: **10 x EA**

- Cable Clip/Clamp Style: P Clamp
- Maximum Bundle Diameter: 20 mm
- Affixing Method: Screw
- Material: Nylon
- Colour: Black



614019 P Clamp

RS PRO STEEL SADDLE CLAMP, 25MM MAX. BUNDLE

Pack size: **50 x EA**

- Cable Clip/Clamp Style: Saddle Clamp
- Maximum Bundle Diameter: 25 mm
- Affixing Method: Screw
- Material: Steel



651513 Saddle Clamp

CONDUIT, P CLIP, PLATED STEEL, PVC INSERT, 10MM, 5MM FIXING

Pack size: **5 x EA**

- Cable Clip/Clamp Style: P Clamp
- Maximum Bundle Diameter: 10 mm
- Affixing Method: Screw
- Material: Plated Steel
- Colour: Black
- Width: 12.7 mm
- Depth: 1.4 mm
- Dimensions [L x W (x D)]: 12.7 x 1.4 mm



1865353 P Clamp

CONDUIT, P CLIP, PLATED STEEL, PVC INSERT, 12MM, 5MM FIXING

Pack size: **5 x EA**

- Cable Clip/Clamp Style: P Clamp
- Maximum Bundle Diameter: 14 mm
- Affixing Method: Screw
- Material: Plated Steel
- Colour: Black
- Width: 12.7 mm
- Depth: 1.4 mm
- Dimensions [L x W (x D)]: 12.7 x 1.4 mm



1865375 P Clamp

CONDUIT, P CLIP, PLATED STEEL, PVC INSERT, 16MM, 5MM FIXING

Pack size: **5 x EA**

- Cable Clip/Clamp Style: P Clamp
- Maximum Bundle Diameter: 16 mm
- Affixing Method: Screw
- Material: Plated Steel
- Colour: Black
- Width: 12.7 mm
- Depth: 1.4 mm
- Dimensions [L x W (x D)]: 12.7 x 1.4 mm



1865381 P Clamp

CONDUIT, P CLIP, PLATED STEEL, PVC INSERT, 20MM, 5MM FIXING

Pack size: **5 x EA**

- Cable Clip/Clamp Style: P Clamp
- Maximum Bundle Diameter: 20 mm
- Affixing Method: Screw
- Material: Plated Steel
- Colour: Black
- Width: 12.7 mm
- Depth: 1.4 mm
- Dimensions [L x W (x D)]: 12.7 x 1.4 mm



1865397 P Clamp

CONDUIT, P CLIP, PLATED STEEL, PVC INSERT, 25MM, 5MM FIXING

Pack size: **5 x EA**

- Cable Clip/Clamp Style: P Clamp
- Maximum Bundle Diameter: 25 mm
- Affixing Method: Screw
- Material: Plated Steel
- Colour: Black
- Width: 12.7 mm
- Depth: 1.4 mm
- Dimensions [L x W (x D)]: 12.7 x 1.4 mm



1865404 P Clamp

CONDUIT, P CLIP, PLATED STEEL, PVC INSERT, 32MM, 5MM FIXING

Pack size: **2 x EA**

- Cable Clip/Clamp Style: P Clamp
- Maximum Bundle Diameter: 32 mm
- Affixing Method: Screw
- Material: Plated Steel
- Colour: Black
- Width: 12.7 mm
- Depth: 1.4 mm
- Dimensions [L x W (x D)]: 12.7 x 1.4 mm



1865410 P Clamp

RS PRO BLACK PLATED STEEL P CLAMP, 40MM MAX. BUNDLE

Pack size: **2 x EA**

- Cable Clip/Clamp Style: P Clamp
- Maximum Bundle Diameter: 40 mm
- Affixing Method: Screw
- Material: Plated Steel
- Colour: Black
- Width: 19.1 mm
- Depth: 2.4 mm
- Dimensions [L x W (x D)]: 19.1 x 2.4 mm



2875581 P Clamp

RS PRO BLACK PLATED STEEL P CLAMP, 50MM MAX. BUNDLE

Pack size: **2 x EA**

- Cable Clip/Clamp Style: P Clamp
- Maximum Bundle Diameter: 50 mm
- Affixing Method: Screw
- Material: Plated Steel
- Colour: Black
- Width: 25.4 mm
- Depth: 2.4 mm
- Dimensions [L x W (x D)]: 25.4 x 2.4 mm



2875597 P Clamp

RS PRO SILVER 316 STAINLESS STEEL SADDLE CLAMP, 20MM MAX. BUNDLE

Pack size: **4 x EA**

- Cable Clip/Clamp Style: Saddle Clamp
- Maximum Bundle Diameter: 20 mm
- Affixing Method: Screw
- Material: 316 Stainless Steel
- Colour: Silver
- Dimensions [L x W (x D)]: 19.3 x 18.2 mm



4711300 Saddle Clamp

RS PRO SILVER 316 STAINLESS STEEL SADDLE CLAMP, 25MM MAX. BUNDLE

Pack size: **4 x EA**

- Cable Clip/Clamp Style: Saddle Clamp
- Maximum Bundle Diameter: 25 mm
- Affixing Method: Screw
- Material: 316 Stainless Steel
- Colour: Silver
- Dimensions [L x W (x D)]: 56 x 19.3 x 19.5 mm



4711316 Saddle Clamp

LOCKNUT, BRASS, NICKEL PLATED, M16

Pack size: **10 x EA**

- Material: Brass
- Thread Size: M16



127164 Brass

CONDUIT, LOCKNUTS, NYLON, BLACK, METRIC, M16, 6.7MM THICK, 19MM A/F

Pack size: **25 x EA**

- Material: PA 6
- Thread Size: M16
- Colour: Black
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +80 °C



127259 PA 6

LOCKNUT,BRASS,NICKEL PLATED,M40

- Pack size: **10 x EA**
- Material: Brass
 - Thread Size: M40
 - Colour: Nickel



127388 Brass

CONDUIT,LOCKNUTS,NYLON,BLACK,METRIC,M20,8MM THICK,23MM A/F

- Pack size: **25 x EA**
- Material: PA 6
 - Thread Size: M20
 - Colour: Black
 - Minimum Operating Temperature: -20 °C
 - Maximum Operating Temperature: +80 °C



127417 PA 6

RS PRO BLACK NYLON CABLE GLAND LOCKNUT, PG13.5 THREAD

- Pack size: **25 x EA**
- Material: Nylon
 - Thread Size: PG13.5
 - Colour: Black
 - Minimum Operating Temperature: -20 °C
 - Maximum Operating Temperature: +80 °C



127423 Nylon

LOCKNUT,BRASS,NICKEL PLATED,M20

- Pack size: **10 x EA**
- Material: Nickel Plated Brass
 - Thread Size: M20
 - Colour: Nickel



127473 Nickel Plated

LOCKNUT,BRASS,NICKEL PLATED,M25

- Pack size: **10 x EA**
- Material: Brass
 - Thread Size: M25



127489 Brass

LOCKNUT,BRASS,NICKEL PLATED,M32

- Pack size: **10 x EA**
- Material: Brass
 - Thread Size: M32



127495 Brass

LOCKNUT,BRASS,NICKEL PLATED,M50

- Pack size: **10 x EA**
- Material: Brass
 - Thread Size: M50



127502 Brass

CONDUIT,LOCKNUTS,NYLON,BLACK,METRIC,M32,9MM THICK,37MM A/F

- Pack size: **5 x EA**
- Material: PA 6
 - Thread Size: M32
 - Colour: Black
 - Minimum Operating Temperature: -20 °C
 - Maximum Operating Temperature: +80 °C



127524 PA 6

CONDUIT,LOCKNUTS,NYLON,BLACK,METRIC,M50,10MM THICK,60MM A/F

- Pack size: **5 x EA**
- Material: PA 6
 - Thread Size: M50
 - Colour: Black
 - Minimum Operating Temperature: -20 °C
 - Maximum Operating Temperature: +80 °C



127530 PA 6

CONDUIT,LOCKNUTS,NYLON,BLACK,METRIC,M40,10MM THICK,50MM A/F

- Pack size: **5 x EA**
- Material: PA 6
 - Thread Size: M40
 - Colour: Black
 - Minimum Operating Temperature: -20 °C
 - Maximum Operating Temperature: +80 °C



127546 PA 6

CONDUIT,LOCKNUTS,NYLON,BLACK,METRIC,M25,9MM THICK,28MM A/F

- Pack size: **25 x EA**
- Material: PA 6
 - Thread Size: M25
 - Colour: Black
 - Minimum Operating Temperature: -20 °C
 - Maximum Operating Temperature: +80 °C



127653 PA 6

RS PRO BLACK STEEL CABLE GLAND LOCKNUT, M16 THREAD

- Pack size: **10 x EA**
- Material: Steel
 - Thread Size: M16
 - Colour: Black



608806 Steel

CONDUIT,LOCKNUT,STEEL,BLACK ENAMELLED,20MM,27AF

- Pack size: **10 x EA**
- Material: Steel
 - Thread Size: M20
 - Colour: Black



608812 Steel

RS PRO BLACK STEEL CABLE GLAND LOCKNUT, M25 THREAD

- Pack size: **10 x EA**
- Material: Steel
 - Thread Size: M25
 - Colour: Black



608828 Steel

RS PRO BLACK STEEL CABLE GLAND LOCKNUT, M32 THREAD

- Pack size: **10 x EA**
- Material: Steel
 - Thread Size: M32
 - Colour: Black



608834 Steel

CONDUIT,LOCKNUTS,STEEL,GALVANIZED,16MM,22 AF

- Pack size: **10 x EA**
- Material: Steel
 - Thread Size: M16
 - Colour: Silver
 - For Use With: All ISO Threaded Conduit Fittings & Accessories



621102 Steel

RS PRO SILVER STEEL CABLE GLAND LOCKNUT, M20 THREAD

Pack size: **10 x EA**

- Material: Steel
- Thread Size: M20
- Colour: Silver
- For Use With: All ISO Threaded Conduit Fittings & Accessories



621118 Steel

CONDUIT, LOCKNUTS, STEEL, GALVANI SED, 25MM, 35 AF

Pack size: **10 x EA**

- Material: Steel
- Thread Size: M25
- Colour: Silver
- For Use With: All ISO Threaded Conduit Fittings & Accessories



621124 Steel

RS PRO SILVER STEEL CABLE GLAND LOCKNUT, M32 THREAD

Pack size: **10 x EA**

- Material: Steel
- Thread Size: M32
- Colour: Silver
- For Use With: All ISO Threaded Conduit Fittings & Accessories



621130 Steel

RS PRO SILVER 316 STAINLESS STEEL CABLE GLAND LOCKNUT, M20

Pack size: **10 x EA**

- Material: 316 Stainless Steel
- Thread Size: M20
- Colour: Silver
- IP Rating: IP66, IP67



4711394 316 Stainless

RS PRO SILVER 316 STAINLESS STEEL CABLE GLAND LOCKNUT, M25

Pack size: **10 x EA**

- Material: 316 Stainless Steel
- Thread Size: M25
- Colour: Silver



4711401 316 Stainless

TAPE, WIREMAN, COILED SPRING STEEL, 10M

Pack size: **1 x EA**

- Routing Tool Type: Draw Wire
- Maximum Length: 10 m
- Material: Spring Steel
- Kit Includes: Tape



2902560 Draw Wire

RS PRO SPRING STEEL CABLE ROD DRAW WIRE

Pack size: **1 x EA**

- Routing Tool Type: Draw Wire
- Maximum Length: 20 m
- Material: Spring Steel
- Kit Includes: Tape



2902576 Draw Wire

TAPE, WIREMAN, PLAIN TAPE AND WINDER

Pack size: **1 x EA**

- Routing Tool Type: Draw Wire
- Maximum Length: 15 m
- Material: Spring Steel
- Kit Includes: Tape



2902605 Draw Wire

RS PRO GLASS FIBRE REINFORCED PLASTIC (GRP) CABLE ROD DRAW

Pack size: **1 x EA**

- Routing Tool Type: Draw Wire
- Maximum Length: 15 m
- Material: Glass Fibre Reinforced Plastic (GRP)
- Kit Includes: Tape



2902627 Draw Wire

ROUND NYLON WIREMANS TAPE 10M

Pack size: **1 x EA**

- Routing Tool Type: Draw Wire
- Maximum Length: 10 m
- Material: Nylon
- Kit Includes: Nylon Cable Rod With Cable Grip



9184970 Draw Wire

ROUND NYLON WIREMANS TAPE 20M

Pack size: **1 x EA**

- Routing Tool Type: Draw Wire
- Maximum Length: 20 m
- Material: Nylon
- Kit Includes: Nylon Cable Rod With Cable Grip



9184977 Draw Wire

RS PRO WIRE, 304 STAINLESS STEEL 3M X 100 MM X 30 MM WING

Pack size: **8 x EA**

- Tray/Basket Type: Wire Tray
- Length: 3 m
- Width: 100 mm
- Depth: 30 mm wing
- Material: 304 Stainless Steel



2216323 Wire Tray

TRUNKING, FLEXIBLE, SLOTTED, SELF ADHESIVE, 9X11X500MM

Pack size: **10 x EA**

- Width: 9 mm
- Depth: 11 mm
- Trunking/Chain Type: Slotted Flexible Panel Trunking
- Colour: White
- Material: Polypropylene
- Length: 0.5 m
- Slot Type: Flexible
- Fire Behaviour: Flame Retardant, Halogen Free, Low Smoke Density, Self-extinguishing



598591 9 mm

TRUNKING, FLEXIBLE, SLOTTED, SELF ADHESIVE, 20X500MM

Pack size: **10 x EA**

- Width: 20 mm
- Depth: 20 mm
- Trunking/Chain Type: Slotted Flexible Panel Trunking
- Colour: White
- Material: Polypropylene
- Length: 0.5 m
- Slot Type: Flexible
- Fire Behaviour: Flame Retardant, Halogen Free, Low Smoke Density, Self-extinguishing



598608 20 mm

TRUNKING, FLEXIBLE, SLOTTED, SELF ADHESIVE, 30X500MM

Pack size: **10 x EA**

- Width: 30 mm
- Depth: 30 mm
- Trunking/Chain Type: Slotted Flexible Panel Trunking
- Colour: White
- Material: Polypropylene
- Length: 0.5 m
- Slot Type: Flexible
- Fire Behaviour: Flame Retardant, Halogen Free, Low Smoke Density, Self-extinguishing



598614 30 mm

TRUNKING, FLEXIBLE, SLOTTED, SELF ADHESIVE, 40X500MM

Pack size: **5 x EA**

- Width: 40 mm
- Depth: 40 mm
- Trunking/Chain Type: Slotted Flexible Panel Trunking
- Colour: White
- Material: Polypropylene
- Length: 0.5 m
- Slot Type: Flexible
- Fire Behaviour: Flame Retardant, Halogen Free, Low Smoke Density, Self-extinguishing



598620 40 mm

RS PRO GREY SLOTTED PANEL TRUNKING - OPEN SLOT, W100 MM X

Pack size: **12 x EA**

- Width: 100 mm
- Depth: 80 mm
- Trunking/Chain Type: Slotted Panel Trunking
- Colour: Grey
- Material: PVC
- Length: 2 m
- Slot Type: Open
- Fire Behaviour: Self-extinguishing



1548103 100 mm

RS PRO WHITE PARAPET TRUNKING, W130 MM X D70MM, L2M, PVC

Pack size: **6 x EA**

- Width: 130 mm
- Depth: 70 mm
- Trunking/Chain Type: Parapet Trunking
- Colour: White
- Material: PVC
- Length: 2 m



2215295 130 mm

RS PRO BLACK SLOTTED PANEL TRUNKING - OPEN SLOT, W25 MM X

Pack size: **12 x EA**

- Width: 25 mm
- Depth: 50 mm
- Trunking/Chain Type: Slotted Panel Trunking
- Colour: Black
- Material: PVC
- Length: 2 m
- Slot Type: Open
- Series: Wiring Duct



2339167 25 mm

RS PRO BLACK SLOTTED PANEL TRUNKING - OPEN SLOT, W25 MM X

Pack size: **4 x EA**

- Width: 25 mm
- Depth: 50 mm
- Trunking/Chain Type: Slotted Panel Trunking
- Colour: Black
- Material: PVC
- Length: 1 m
- Slot Type: Open
- Series: Wiring Duct



2339168 25 mm

RS PRO OPEN SLOT 8MM WIRING DUCT, GREY P

Pack size: **4 x EA**

- Width: 25 mm
- Depth: 50 mm
- Trunking/Chain Type: Slotted Panel Trunking
- Colour: Grey
- Material: PVC
- Length: 1 m
- Slot Type: Open
- Series: Wiring Duct



2339169 25 mm

RS PRO GREY SLOTTED PANEL TRUNKING - OPEN SLOT, W25 MM X

Pack size: **4 x EA**

- Width: 25 mm
- Depth: 75 mm
- Trunking/Chain Type: Slotted Panel Trunking
- Colour: Grey
- Material: PVC
- Length: 1 m
- Slot Type: Open
- Series: Wiring Duct



2339172 25 mm

RS PRO GREY SLOTTED PANEL TRUNKING - OPEN SLOT, W50 MM X

Pack size: **4 x EA**

- Width: 50 mm
- Depth: 25 mm
- Trunking/Chain Type: Slotted Panel Trunking
- Colour: Grey
- Material: PVC
- Length: 1 m
- Slot Type: Open
- Series: Wiring Duct



2339175 50 mm

RS PRO BLACK SLOTTED PANEL TRUNKING - OPEN SLOT, W50 MM X

Pack size: **4 x EA**

- Width: 50 mm
- Depth: 50 mm
- Trunking/Chain Type: Slotted Panel Trunking
- Colour: Black
- Material: PVC
- Length: 1 m
- Slot Type: Open
- Series: Wiring Duct



2339176 50 mm

RS PRO GREY SLOTTED PANEL TRUNKING - OPEN SLOT, W50 MM X

Pack size: **4 x EA**

- Width: 50 mm
- Depth: 50 mm
- Trunking/Chain Type: Slotted Panel Trunking
- Colour: Grey
- Material: PVC
- Length: 1 m
- Slot Type: Open
- Series: Wiring Duct



2339177 50 mm

RS PRO BLACK SLOTTED PANEL TRUNKING - CLOSED SLOT, W25 MM X

Pack size: **4 x EA**

- Width: 25 mm
- Depth: 30 mm
- Trunking/Chain Type: Slotted Panel Trunking
- Colour: Black
- Material: PVC
- Length: 1 m
- Slot Type: Closed
- Series: Wiring Duct



2339187 25 mm

RS PRO GREY SLOTTED PANEL TRUNKING - CLOSED SLOT, W40 MM

Pack size: **12 x EA**

- Width: 40 mm
- Depth: 40 mm
- Trunking/Chain Type: Slotted Panel Trunking
- Colour: Grey
- Material: PVC
- Length: 2 m
- Slot Type: Closed
- Series: Wiring Duct



2339188 40 mm

RS PRO BLACK SLOTTED PANEL TRUNKING - OPEN SLOT, W25 MM X

Pack size: **4 x EA**

- Width: 25 mm
- Depth: 40 mm
- Trunking/Chain Type: Slotted Panel Trunking
- Colour: Black
- Material: PVC
- Length: 1 m
- Slot Type: Open
- Series: Wiring Duct



2339191 25 mm

RS PRO WHITE MINI TRUNKING, W18 MM X D18MM, L2M, PVC

Pack size: **8 x EA**

- Width: 18 mm
- Depth: 18 mm
- Trunking/Chain Type: Mini Trunking
- Colour: White
- Material: PVC
- Length: 2 m



2374041 18 mm

RS PRO WHITE MINI TRUNKING, W30 MM X D30MM, L2M, PVC

Pack size: **25 x EA**

- Width: 30 mm
- Depth: 30 mm
- Trunking/Chain Type: Mini Trunking
- Colour: White
- Material: PVC
- Length: 2 m



2374042 30 mm

RS PRO WHITE MINI TRUNKING, W30 MM X D30MM, L2M, PVC

Pack size: **5 x EA**

- Width: 30 mm
- Depth: 30 mm
- Trunking/Chain Type: Mini Trunking
- Colour: White
- Material: PVC
- Length: 2 m



2374043 30 mm

RS PRO WHITE MINI TRUNKING, W40 MM X D40MM, L2M, PVC

Pack size: **16 x EA**

- Width: 40 mm
- Depth: 40 mm
- Trunking/Chain Type: Mini Trunking
- Colour: White
- Material: PVC
- Length: 2 m



2374046 40 mm

RS PRO WHITE MINI TRUNKING, W40 MM X D40MM, L2M, PVC

Pack size: **4 x EA**

- Width: 40 mm
- Depth: 40 mm
- Trunking/Chain Type: Mini Trunking
- Colour: White
- Material: PVC
- Length: 2 m



2374047 40 mm

RS PRO WHITE MINI TRUNKING, W60 MM X D40MM, L2M, PVC

Pack size: **14 x EA**

- Width: 60 mm
- Depth: 40 mm
- Trunking/Chain Type: Mini Trunking
- Colour: White
- Material: PVC
- Length: 2 m



2374048 60 mm

RS PRO WHITE MINI TRUNKING, W60 MM X D60MM, L2M, PVC

Pack size: **12 x EA**

- Width: 60 mm
- Depth: 60 mm
- Trunking/Chain Type: Mini Trunking
- Colour: White
- Material: PVC
- Length: 2 m



2374051 60 mm

RS PRO WHITE MINI TRUNKING, W60 MM X D60MM, L2M, PVC

Pack size: **4 x EA**

- Width: 60 mm
- Depth: 60 mm
- Trunking/Chain Type: Mini Trunking
- Colour: White
- Material: PVC
- Length: 2 m



2374052 60 mm

RS PRO GREY SLOTTED PANEL TRUNKING - OPEN SLOT, W25 MM X

Pack size: **8 x EA**

- Width: 25 mm
- Depth: 25 mm
- Trunking/Chain Type: Slotted Panel Trunking
- Colour: Grey
- Material: PVC
- Length: 2 m
- Slot Type: Open
- Fire Behaviour: Self-extinguishing



3011924 25 mm

RS PRO GREY SLOTTED PANEL TRUNKING - OPEN SLOT, W50 MM X

Pack size: **8 x EA**

- Width: 50 mm
- Depth: 50 mm
- Trunking/Chain Type: Slotted Panel Trunking
- Colour: Grey
- Material: PVC
- Length: 2 m
- Slot Type: Open
- Fire Behaviour: Self-extinguishing



3011974 50 mm

RS PRO GREY SLOTTED PANEL TRUNKING - OPEN SLOT, W25 MM X

Pack size: **4 x EA**

- Width: 25 mm
- Depth: 25 mm
- Trunking/Chain Type: Slotted Panel Trunking
- Colour: Grey
- Material: PVC
- Length: 1 m
- Slot Type: Open
- Fire Behaviour: Self-extinguishing



8793713 25 mm

RS PRO GREY SLOTTED PANEL TRUNKING - OPEN SLOT, W60 MM X

Pack size: **4 x EA**

- Width: 60 mm
- Depth: 60 mm
- Trunking/Chain Type: Slotted Panel Trunking
- Colour: Grey
- Material: PVC
- Length: 1 m
- Slot Type: Open
- Fire Behaviour: Self-extinguishing



8793722 60 mm

RS PRO GREY SLOTTED PANEL TRUNKING - NARROW SLOT, W40 MM X

Pack size: **4 x EA**

- Width: 40 mm
- Depth: 40 mm
- Trunking/Chain Type: Slotted Panel Trunking
- Colour: Grey
- Material: PVC
- Length: 1 m
- Slot Type: Narrow
- Fire Behaviour: Self-extinguishing



8793725 40 mm

RS PRO GREY SLOTTED PANEL TRUNKING - OPEN SLOT, W100 MM X

Pack size: **4 x EA**

- Width: 100 mm
- Depth: 100 mm
- Trunking/Chain Type: Slotted Panel Trunking
- Colour: Grey
- Material: PVC
- Length: 1 m
- Slot Type: Open
- Fire Behaviour: Self-extinguishing



8793729 100 mm

RS PRO GREY SLOTTED PANEL TRUNKING - OPEN SLOT, W40 MM X

Pack size: **4 x EA**

- Width: 40 mm
- Depth: 60 mm
- Trunking/Chain Type: Slotted Panel Trunking
- Colour: Grey
- Material: PVC
- Length: 1 m
- Slot Type: Open
- Fire Behaviour: Self-extinguishing



8793731 40 mm

RS PRO GREY SLOTTED PANEL TRUNKING - OPEN SLOT, W80 MM X

Pack size: **4 x EA**

- Width: 80 mm
- Depth: 80 mm
- Trunking/Chain Type: Slotted Panel Trunking
- Colour: Grey
- Material: PVC
- Length: 1 m
- Slot Type: Open
- Fire Behaviour: Self-extinguishing



8793735 80 mm

RS PRO GREY SLOTTED PANEL TRUNKING - OPEN SLOT, W40 MM X

Pack size: **4 x EA**

- Width: 40 mm
- Depth: 80 mm
- Trunking/Chain Type: Slotted Panel Trunking
- Colour: Grey
- Material: PVC
- Length: 1 m
- Slot Type: Open
- Fire Behaviour: Self-extinguishing



8793738 40 mm

RS PRO GREY SLOTTED PANEL TRUNKING - NARROW SLOT, W40 MM X

Pack size: **4 x EA**

- Width: 40 mm
- Depth: 60 mm
- Trunking/Chain Type: Slotted Panel Trunking
- Colour: Grey
- Material: PVC
- Length: 1 m
- Slot Type: Narrow
- Fire Behaviour: Self-extinguishing



8793741 40 mm

RS PRO GREY SLOTTED PANEL TRUNKING - OPEN SLOT, W60 MM X

Pack size: **4 x EA**

- Width: 60 mm
- Depth: 80 mm
- Trunking/Chain Type: Slotted Panel Trunking
- Colour: Grey
- Material: PVC
- Length: 1 m
- Slot Type: Open
- Fire Behaviour: Self-extinguishing



8793744 60 mm

RS PRO GREY SLOTTED PANEL TRUNKING - NARROW SLOT, W40 MM X

Pack size: **4 x EA**

- Width: 40 mm
- Depth: 80 mm
- Trunking/Chain Type: Slotted Panel Trunking
- Colour: Grey
- Material: PVC
- Length: 1 m
- Slot Type: Narrow
- Fire Behaviour: Self-extinguishing



8793747 40 mm

RS PRO GREY SLOTTED PANEL TRUNKING - NARROW SLOT, W60 MM

Pack size: **4 x EA**

- Width: 60 mm
- Depth: 80 mm
- Trunking/Chain Type: Slotted Panel Trunking
- Colour: Grey
- Material: PVC
- Length: 1 m
- Slot Type: Narrow
- Fire Behaviour: Self-extinguishing



8793750 60 mm

RS PRO GREY SLOTTED PANEL TRUNKING - OPEN SLOT, W80 MM X

Pack size: **4 x EA**

- Width: 80 mm
- Depth: 80 mm
- Trunking/Chain Type: Slotted Panel Trunking
- Colour: Grey
- Material: PVC
- Length: 1 m
- Slot Type: Open
- Fire Behaviour: Self-extinguishing



8793753 80 mm

RS PRO GALVANISED STEEL CABLE TRUNKING ACCESSORY, 50 X 50MM

Pack size: **2 x EA**

- Trunking Accessory Type: Flanged Coupler
- Material: Galvanised Steel
- Width: 50 mm
- Height: 50 mm
- Dimensions: 50 x 50 mm
- Series: Galvanised Steel



562930 Flanged Coupler

RS PRO GALVANISED STEEL CABLE TRUNKING ACCESSORY, 75 X 75MM

Pack size: **2 x EA**

- Trunking Accessory Type: Flanged Coupler
- Material: Galvanised Steel
- Width: 75 mm
- Height: 75 mm
- Dimensions: 75 x 75 mm
- Series: Galvanised Steel



562946 Flanged Coupler

RS PRO PVC CABLE TRUNKING END CAP, 110 X 70MM

Pack size: **1 x EA**

- Trunking Accessory Type: End Cap
- Material: PVC
- Dimensions: 110 x 70 mm



2215304 End Cap

RS PRO PVC CABLE TRUNKING, 110 X 70MM

Pack size: **1 x EA**

- Trunking Accessory Type: Flat Angle
- Material: PVC
- Dimensions: 110 x 70 mm



2215306 Flat Angle

RS PRO PVC CABLE TRUNKING FLAT CORNER

Pack size: **1 x EA**

- Trunking Accessory Type: Mounting Box
- Material: PVC
- Height: 45 mm



2215308 Mounting Box

RS PRO PVC CABLE TRUNKING SOCKET BOX

Pack size: **1 x EA**

- Trunking Accessory Type: Mounting Box
- Material: PVC
- Height: 45 mm



2215309 Mounting Box

RS PRO 304 STAINLESS STEEL CABLE TRUNKING ACCESSORY, 75 X 75MM

Pack size: **1 x EA**

- Trunking Accessory Type: 90° Bend Front Lid
- Material: 304 Stainless Steel
- Width: 75 mm
- Height: 75 mm
- Dimensions: 75 x 75 mm
- Series: Stainless Steel
- Standards Met: UL



4711451 90° Bend Front

RS PRO 304 STAINLESS STEEL CABLE TRUNKING ACCESSORY, 75 X 75MM

Pack size: **1 x EA**

- Trunking Accessory Type: Coupling
- Material: 304 Stainless Steel
- Width: 75 mm
- Height: 75 mm
- Dimensions: 75 x 75 mm
- Series: Stainless Steel
- Standards Met: UL



4711530 Coupling

RS PRO 304 STAINLESS STEEL CABLE TRUNKING ACCESSORY, 75 X 75MM

Pack size: **1 x EA**

- Trunking Accessory Type: Flanged Coupler
- Material: 304 Stainless Steel
- Width: 75 mm
- Height: 75 mm
- Dimensions: 75 x 75 mm
- Series: Stainless Steel
- Standards Met: UL



4711552 Flanged Coupler

RS PRO 304 STAINLESS STEEL CABLE TRUNKING ACCESSORY, 75 X 75MM

Pack size: **1 x EA**

- Trunking Accessory Type: End Cap
- Material: 304 Stainless Steel
- Width: 75 mm
- Height: 75 mm
- Dimensions: 75 x 75 mm
- Series: Stainless Steel
- Standards Met: UL



4711574 End Cap

RS PRO PVC CABLE TRUNKING ACCESSORY, 16 X 16MM

Pack size: **2 x EA**

- Trunking Accessory Type: Coupling
- Material: PVC
- Width: 16 mm
- Height: 16 mm
- Dimensions: 16 x 16 mm
- Series: Mini



9171546 Coupling

RS PRO PVC CABLE TRUNKING ACCESSORY, 38 X 25MM

Pack size: **2 x EA**

- Trunking Accessory Type: Coupling
- Material: PVC
- Width: 38 mm
- Height: 25 mm
- Dimensions: 38 x 25 mm
- Series: Mini



9171552 Coupling

RS PRO PVC CABLE TRUNKING ACCESSORY, 25 X 16MM

Pack size: **2 x EA**

- Trunking Accessory Type: Coupling
- Material: PVC
- Width: 25 mm
- Height: 16 mm
- Dimensions: 25 x 16 mm
- Series: Mini



9171555 Coupling

RS PRO PVC CABLE TRUNKING ACCESSORY, 16 X 16MM

Pack size: **1 x EA**

- Trunking Accessory Type: Flat Tee
- Material: PVC
- Width: 16 mm
- Height: 16 mm
- Dimensions: 16 x 16 mm
- Series: Mini



9171561 Flat Tee

RS PRO PVC CABLE TRUNKING ACCESSORY, 38 X 25MM

Pack size: **1 x EA**

- Trunking Accessory Type: Flat Tee
- Material: PVC
- Width: 38 mm
- Height: 25 mm
- Dimensions: 38 x 25 mm
- Series: Mini



9171568 Flat Tee

RS PRO PVC CABLE TRUNKING ACCESSORY, 25 X 16MM

Pack size: **2 x EA**

- Trunking Accessory Type: Flat Angle
- Material: PVC
- Width: 25 mm
- Height: 16 mm
- Dimensions: 25 x 16 mm
- Series: Mini



9171570 Flat Angle

RS PRO PVC CABLE TRUNKING ACCESSORY, 16 X 16MM

Pack size: **2 x EA**

- Trunking Accessory Type: Flat Angle
- Material: PVC
- Width: 16 mm
- Height: 16 mm
- Dimensions: 16 x 16 mm
- Series: Mini



9171577 Flat Angle

RS PRO PVC CABLE TRUNKING ACCESSORY, 25 X 16MM

Pack size: **2 x EA**

- Trunking Accessory Type: External Angle
- Material: PVC
- Width: 25 mm
- Height: 16 mm
- Dimensions: 25 x 16 mm
- Series: Mini



9171580 External Angle

RS PRO PVC CABLE TRUNKING ACCESSORY, 16 X 16MM

Pack size: **2 x EA**

- Trunking Accessory Type: External Angle
- Material: PVC
- Width: 16 mm
- Height: 16 mm
- Dimensions: 16 x 16 mm
- Series: Mini



9171586 External Angle

RS PRO PVC CABLE TRUNKING ACCESSORY, 16 X 16MM

Pack size: **2 x EA**

- Trunking Accessory Type: Internal Angle
- Material: PVC
- Width: 16 mm
- Height: 16 mm
- Dimensions: 16 x 16 mm
- Series: Mini



9171596 Internal Angle

RS PRO PVC CABLE TRUNKING ACCESSORY, 25 X 16MM

Pack size: **2 x EA**

- Trunking Accessory Type: Internal Angle
- Material: PVC
- Width: 25 mm
- Height: 16 mm
- Dimensions: 25 x 16 mm
- Series: Mini



9171606 Internal Angle

RS PRO PVC CABLE TRUNKING ACCESSORY, 25 X 16MM

Pack size: **1 x EA**

- Trunking Accessory Type: Flat Tee
- Material: PVC
- Width: 25 mm
- Height: 16 mm
- Dimensions: 25 x 16 mm
- Series: Mini



9171631 Flat Tee

RS PRO FLEXIBLE CONDUIT, 25MM NOMINAL DIAMETER, PLASTIC, GREY

Pack size: **5 x MTR**

- Nominal Diameter: 25 mm
- Material: Plastic
- Conduit Type: Flexible
- Outer Diameter: 25.8 mm
- Colour: Grey
- Interior Diameter: 21.2 mm
- Length: 5 m
- IP Rating: IP55



429666 25 mm

RS PRO FLEXIBLE CONDUIT, 20MM NOMINAL DIAMETER, PLASTIC, GREY

Pack size: **5 x MTR**

- Nominal Diameter: 20 mm
- Material: Plastic
- Conduit Type: Flexible
- Outer Diameter: 20 mm
- Colour: Grey
- Interior Diameter: 14.1 mm
- Length: 5 m
- IP Rating: IP55



429672 20 mm

RS PRO FLEXIBLE CONDUIT, 16MM NOMINAL DIAMETER, PLASTIC, GREY

Pack size: **5 x MTR**

- Nominal Diameter: 16 mm
- Material: Plastic
- Conduit Type: Flexible
- Outer Diameter: 16 mm
- Colour: Grey
- Interior Diameter: 10.7 mm
- Length: 5 m
- IP Rating: IP55



429678 16 mm

RS PRO FLEXIBLE CONDUIT, 10MM NOMINAL DIAMETER, PLASTIC, GREY

Pack size: **5 x MTR**

- Nominal Diameter: 10 mm
- Material: Plastic
- Conduit Type: Flexible
- Outer Diameter: 10.2 mm
- Colour: Grey
- Interior Diameter: 7.4 mm
- Length: 5 m
- IP Rating: IP55



429688 10 mm

RS PRO FLEXIBLE CONTRACTOR PACK CONDUIT, 20MM NOMINAL

Pack size: **1 x EA**

- Nominal Diameter: 20 mm
- Material: Plastic
- Conduit Type: Flexible Contractor Pack
- Colour: Black
- Length: 10 m
- IP Rating: IP66
- Maximum Operating Temperature: +105 °C
- Standards Met: EN 50086, UL Listed



5132376 20 mm

RS PRO FLEXIBLE CONDUIT, 25MM NOMINAL DIAMETER, PLASTIC, BLACK

Pack size: **10 x MTR**

- Nominal Diameter: 25 mm
- Material: Plastic
- Conduit Type: Flexible
- Outer Diameter: 28.5 mm
- Colour: Black
- Interior Diameter: 23 mm
- Length: 10 m
- Coating Material: Uncoated



7559001 25 mm

RS PRO FLEXIBLE CONDUIT, 16MM NOMINAL DIAMETER, PLASTIC, BLACK

Pack size: **25 x MTR**

- Nominal Diameter: 16 mm
- Material: Plastic
- Conduit Type: Flexible
- Outer Diameter: 15.8 mm
- Colour: Black
- Interior Diameter: 12.2 mm
- Length: 25 m
- Coating Material: Uncoated



7559004 16 mm

RS PRO FLEXIBLE CONDUIT, 20MM NOMINAL DIAMETER, PLASTIC, BLACK

Pack size: **25 x MTR**

- Nominal Diameter: 20 mm
- Material: Plastic
- Conduit Type: Flexible
- Outer Diameter: 21.7 mm
- Colour: Black
- Interior Diameter: 16.8 mm
- Length: 25 m
- Coating Material: Uncoated



7559007 20 mm

RS PRO FLEXIBLE CONDUIT, 32MM NOMINAL DIAMETER, PLASTIC, BLACK

Pack size: **10 x MTR**

- Nominal Diameter: 32 mm
- Material: Plastic
- Conduit Type: Flexible
- Outer Diameter: 34.4 mm
- Colour: Black
- Interior Diameter: 28.6 mm
- Length: 10 m
- Coating Material: Uncoated



7559010 32 mm

RS PRO FLEXIBLE, SPLIT CONDUIT, 16MM NOMINAL DIAMETER, PLASTIC,

Pack size: **25 x MTR**

- Nominal Diameter: 16 mm
- Material: Plastic
- Conduit Type: Flexible, Split
- Outer Diameter: 16 mm
- Colour: Black
- Interior Diameter: 10.7 mm
- Length: 25 m
- Coating Material: Uncoated



7559013 16 mm

RS PRO FLEXIBLE, SPLIT CONDUIT, 20MM NOMINAL DIAMETER, PLASTIC,

Pack size: **25 x MTR**

- Nominal Diameter: 20 mm
- Material: Plastic
- Conduit Type: Flexible, Split
- Outer Diameter: 19.5 mm
- Colour: Black
- Interior Diameter: 15 mm
- Length: 25 m
- Coating Material: Uncoated



7559017 20 mm

RS PRO FLEXIBLE CONDUIT, 16MM NOMINAL DIAMETER, PLASTIC, BLACK

Pack size: **25 x MTR**

- Nominal Diameter: 16 mm
- Material: Plastic
- Conduit Type: Flexible
- Outer Diameter: 16 mm
- Colour: Black
- Interior Diameter: 10.7 mm
- Length: 25 m
- Coating Material: Uncoated



7559023 16 mm

RS PRO FLEXIBLE, SPLIT CONDUIT, 25MM NOMINAL DIAMETER, PLASTIC,

Pack size: **10 x MTR**

- Nominal Diameter: 25 mm
- Material: Plastic
- Conduit Type: Flexible, Split
- Outer Diameter: 25.8 mm
- Colour: Black
- Interior Diameter: 21.2 mm
- Length: 10 m
- Coating Material: Uncoated



7559026 25 mm

RS PRO FLEXIBLE, SPLIT CONDUIT, 32MM NOMINAL DIAMETER, PLASTIC,

Pack size: **10 x MTR**

- Nominal Diameter: 32 mm
- Material: Plastic
- Conduit Type: Flexible, Split
- Outer Diameter: 32 mm
- Colour: Black
- Interior Diameter: 24.3 mm
- Length: 10 m
- Coating Material: Uncoated



7559029 32 mm

RS PRO FLEXIBLE CONDUIT, 20MM NOMINAL DIAMETER, PLASTIC, BLACK

Pack size: **25 x MTR**

- Nominal Diameter: 20 mm
- Material: Plastic
- Conduit Type: Flexible
- Outer Diameter: 19.5 mm
- Colour: Black
- Interior Diameter: 15 mm
- Length: 25 m
- Coating Material: Uncoated



7559032 20 mm

RS PRO FLEXIBLE CONDUIT, 25MM NOMINAL DIAMETER, PLASTIC, BLACK

Pack size: **10 x MTR**

- Nominal Diameter: 25 mm
- Material: Plastic
- Conduit Type: Flexible
- Outer Diameter: 25.8 mm
- Colour: Black
- Interior Diameter: 21.2 mm
- Length: 10 m
- Coating Material: Uncoated



7559035 25 mm

RS PRO FLEXIBLE CONDUIT, 32MM NOMINAL DIAMETER, PLASTIC, BLACK

Pack size: **10 x MTR**

- Nominal Diameter: 32 mm
- Material: Plastic
- Conduit Type: Flexible
- Outer Diameter: 32 mm
- Colour: Black
- Interior Diameter: 24.3 mm
- Length: 10 m
- Coating Material: Uncoated



7559039 32 mm

RS PRO FLEXIBLE CONDUIT, 12MM NOMINAL DIAMETER, GALVANISED

Pack size: **25 x MTR**

- Nominal Diameter: 12 mm
- Material: Galvanised Steel
- Conduit Type: Flexible
- Outer Diameter: 11 mm
- Colour: Black
- Interior Diameter: 8.2 mm
- Length: 25 m
- Coating Material: PVC



7840094 12 mm

RS PRO TERMINAL BOX, CONDUIT FITTING, 20MM NOMINAL SIZE, STEEL

Pack size: **5 x EA**

- Nominal Size: 20 mm
- Fitting Type: Terminal Box
- Material: Steel
- Colour: Black
- Finish: Black Enamel
- Standards Met: BS EN 50086



228722 20 mm

RS PRO ANGLE BOX, CONDUIT FITTING, 25MM NOMINAL SIZE, STEEL

Pack size: **5 x EA**

- Nominal Size: 25 mm
- Fitting Type: Angle Box
- Material: Steel
- Finish: Galvanised
- Standards Met: BS EN 50086



228772 25 mm

RS PRO T PIECE, CONDUIT FITTING, 25MM NOMINAL SIZE, STEEL

Pack size: **5 x EA**

- Nominal Size: 25 mm
- Fitting Type: T Piece
- Material: Steel
- Finish: Galvanised
- Standards Met: BS EN 50086



228788 25 mm

RS PRO THROUGH BOX, CONDUIT FITTING, 25MM NOMINAL SIZE, STEEL

Pack size: **5 x EA**

- Nominal Size: 25 mm
- Fitting Type: Through Box
- Material: Steel
- Finish: Galvanised
- Standards Met: BS EN 50086



228794 25 mm

RS PRO TERMINAL BOX, CONDUIT FITTING, 25MM NOMINAL SIZE, STEEL

Pack size: **5 x EA**

- Nominal Size: 25 mm
- Fitting Type: Terminal Box
- Material: Steel
- Finish: Galvanised
- Standards Met: BS EN 50086



228851 25 mm

RS PRO M20-M16 REDUCER CABLE CONDUIT FITTING, 20MM NOMINAL

Pack size: **5 x EA**

- Fitting Type: Reducer
- Nominal Size: 20 mm
- Material: Brass
- Thread Size: M20-M16
- Finish: Nickel Plated



127467 Reducer

RS PRO T PIECE, CONDUIT FITTING, 20MM NOMINAL SIZE, STEEL

Pack size: **5 x EA**

- Nominal Size: 20 mm
- Fitting Type: T Piece
- Material: Steel
- Finish: Galvanised
- Standards Met: BS EN 50086



228873 20 mm

RS PRO TERMINAL BOX, CONDUIT FITTING, 20MM NOMINAL SIZE, M4,

Pack size: **5 x EA**

- Nominal Size: 20 mm
- Fitting Type: Terminal Box
- Thread Size: M4
- Material: Steel
- Finish: Galvanised



228889 20 mm

RS PRO THROUGH BOX, CONDUIT FITTING, 20MM NOMINAL SIZE, STEEL

Pack size: **5 x EA**

- Nominal Size: 20 mm
- Fitting Type: Through Box
- Material: Steel
- Finish: Galvanised
- Standards Met: BS EN 50086



228895 20 mm

CONDUIT,FLEXIBLE,POLYETHYLENE,M 25,STRAIGHT ADAPTOR

Pack size: **5 x EA**

- Fitting Type: Straight
- Nominal Size: 25 mm
- Material: Nylon 66
- Thread Size: M25
- Colour: Grey
- Finish: Grey
- IP Rating: IP55



429640 Straight

RS PRO STRAIGHT, CONDUIT FITTING, 20MM NOMINAL SIZE, NYLON 66,

Pack size: **5 x EA**

- Nominal Size: 20 mm
- Fitting Type: Straight
- Material: Nylon 66
- Colour: Grey
- IP Rating: IP55
- Finish: Grey
- Standards Met: UL 94 V-0



429650 20 mm

RS PRO STRAIGHT, CONDUIT FITTING, 16MM NOMINAL SIZE, NYLON 66,

Pack size: **5 x EA**

- Nominal Size: 16 mm
- Fitting Type: Straight
- Material: Nylon 66
- Colour: Grey
- IP Rating: IP55
- Finish: Grey
- Standards Met: UL 94 V-0



429656 16 mm

RS PRO STRAIGHT, CONDUIT FITTING, 10MM NOMINAL SIZE, M12, NYLON 66,

Pack size: **5 x EA**

- Nominal Size: 10 mm
- Fitting Type: Straight
- Thread Size: M12
- Material: Nylon 66
- Colour: Grey
- IP Rating: IP55
- Finish: Grey



429662 10 mm

RS PRO M20 DOME COVER CONDUIT FITTING, 20MM NOMINAL SIZE

Pack size: **10 x EA**

- Fitting Type: Dome Cover
- Nominal Size: 20 mm
- Material: Steel
- Thread Size: M20
- Finish: Galvanised
- Standards Met: BS EN 50086



606024 Dome Cover

RS PRO COUPLER CABLE CONDUIT FITTING, 20MM NOMINAL SIZE

Pack size: **25 x EA**

- Fitting Type: Coupler
- Nominal Size: 20 mm
- Material: Steel
- Finish: Galvanised
- Standards Met: BS EN 50086



606030 Coupler

RS PRO COUPLER, CONDUIT FITTING, 25MM NOMINAL SIZE, STEEL

Pack size: **25 x EA**

- Nominal Size: 25 mm
- Fitting Type: Coupler
- Material: Steel
- Finish: Galvanised
- Standards Met: BS EN 50086



606046 25 mm

RS PRO M20 LOCK RING CABLE CONDUIT FITTING, 20MM NOMINAL

Pack size: **50 x EA**

- Fitting Type: Lock Ring
- Nominal Size: 20 mm
- Material: Steel
- Thread Size: M20
- Standards Met: BS EN 50086



607982 Lock Ring

RS PRO LOCK RING, CONDUIT FITTING, 25MM NOMINAL SIZE, M25,

Pack size: **50 x EA**

- Nominal Size: 25 mm
- Fitting Type: Lock Ring
- Thread Size: M25
- Material: Steel
- Standards Met: BS EN 50086



607998 25 mm

RS PRO DOME COVER, CONDUIT FITTING, 20MM NOMINAL SIZE, M20,

Pack size: **10 x EA**

- Nominal Size: 20 mm
- Fitting Type: Dome Cover
- Thread Size: M20
- Material: Steel
- Colour: Black
- Finish: Black
- Standards Met: BS EN 50086



608165 20 mm

RS PRO COUPLER, CONDUIT FITTING, 20MM NOMINAL SIZE, STEEL, BLACK

Pack size: **25 x EA**

- Nominal Size: 20 mm
- Fitting Type: Coupler
- Material: Steel
- Colour: Black
- Finish: Black Enamel
- Standards Met: BS EN 50086



608171 20 mm

RS PRO COUPLER, CONDUIT FITTING, 25MM NOMINAL SIZE, STEEL, BLACK

Pack size: **25 x EA**

- Nominal Size: 25 mm
- Fitting Type: Coupler
- Material: Steel
- Colour: Black
- Finish: Black Enamel
- Standards Met: BS EN 50086



608187 25 mm

RS PRO REDUCER CABLE CONDUIT FITTING, 25MM NOMINAL SIZE

Pack size: **10 x EA**

- Fitting Type: Reducer
- Nominal Size: 25 mm
- Material: Steel
- Finish: Enamelled
- Standards Met: BS EN 50086



608216 Reducer

RS PRO M20 MALE BUSH CABLE CONDUIT FITTING, 20MM NOMINAL

- Pack size: **25 x EA**
- Fitting Type: Male Bush
 - Nominal Size: 20 mm
 - Material: Brass
 - Thread Size: M20
 - Standards Met: BS EN 50086



608222 Male Bush

RS PRO MALE BUSH, CONDUIT FITTING, 25MM NOMINAL SIZE,

- Pack size: **25 x EA**
- Nominal Size: 25 mm
 - Fitting Type: Male Bush
 - Material: Brass
 - Standards Met: BS EN 50086



608238 25 mm

RS PRO M20 MALE BUSH CABLE CONDUIT FITTING, 20MM NOMINAL

- Pack size: **25 x EA**
- Fitting Type: Male Bush
 - Nominal Size: 20 mm
 - Material: Brass
 - Thread Size: M20
 - Standards Met: BS EN 50086



608244 Male Bush

RS PRO FEMALE BUSH, CONDUIT FITTING, 20MM NOMINAL SIZE, BRASS

- Pack size: **25 x EA**
- Nominal Size: 20 mm
 - Fitting Type: Female Bush
 - Material: Brass
 - Standards Met: BS EN 50086



608250 20 mm

RS PRO MALE HOOK CONDUIT FITTING, BLACK 20MM NOMINAL SIZE

- Pack size: **10 x EA**
- Fitting Type: Male Hook
 - Nominal Size: 20 mm
 - Material: Steel
 - Colour: Black
 - Finish: Enamelled
 - Standards Met: BS EN 50086



608266 Male Hook

RS PRO FLANGE COUPLER CABLE CONDUIT FITTING, 20MM NOMINAL

- Pack size: **10 x EA**
- Fitting Type: Flange Coupler
 - Nominal Size: 20 mm
 - Material: Steel
 - Finish: Galvanised
 - Standards Met: BS EN 50086



619957 Flange Coupler

RS PRO FLANGE COUPLER, CONDUIT FITTING, 25MM NOMINAL SIZE, STEEL

- Pack size: **10 x EA**
- Nominal Size: 25 mm
 - Fitting Type: Flange Coupler
 - Material: Steel
 - Finish: Galvanised
 - Standards Met: BS EN 50086



619963 25 mm

RS PRO REDUCER, CONDUIT FITTING, 20MM NOMINAL SIZE, STEEL

- Pack size: **10 x EA**
- Nominal Size: 20 mm
 - Fitting Type: Reducer
 - Material: Steel
 - Finish: Enamelled
 - Standards Met: BS EN 50086



619979 20 mm

RS PRO MALE BUSH, CONDUIT FITTING, 25MM NOMINAL SIZE,

- Pack size: **25 x EA**
- Nominal Size: 25 mm
 - Fitting Type: Male Bush
 - Material: Brass
 - Standards Met: BS EN 50086



619985 25 mm

RS PRO JACK CHAIN CONDUIT FITTING, BLACK #8 NOMINAL SIZE

- Pack size: **1 x EA**
- Fitting Type: Jack Chain
 - Nominal Size: 8 mm
 - Material: Steel
 - Colour: Black
 - Finish: Black
 - Standards Met: BS EN 50086



621089 Jack Chain

RS PRO JACK CHAIN, CONDUIT FITTING, 2.9MM NOMINAL SIZE,

- Pack size: **1 x EA**
- Nominal Size: 2.9 mm
 - Fitting Type: Jack Chain
 - Material: Galvanised Steel
 - Finish: Galvanised
 - Standards Met: BS EN 50086



621095 2.9 mm

RS PRO THREAD CONVERTER, CONDUIT FITTING, 9MM NOMINAL

- Pack size: **5 x EA**
- Nominal Size: 9 mm
 - Fitting Type: Thread Converter
 - Thread Size: PG9 → M16
 - Material: Brass
 - Finish: Nickel Plated



623899 9 mm

RS PRO THREAD CONVERTER, CONDUIT FITTING, 9MM NOMINAL

- Pack size: **5 x EA**
- Nominal Size: 9 mm
 - Fitting Type: Thread Converter
 - Thread Size: PG9 → M20
 - Material: Brass
 - Finish: Nickel Plated



623906 9 mm

RS PRO THREAD CONVERTER, CONDUIT FITTING, 16MM NOMINAL

- Pack size: **5 x EA**
- Nominal Size: 16 mm
 - Fitting Type: Thread Converter
 - Thread Size: PG11 → M16
 - Material: Brass
 - Finish: Nickel Plated



623912 16 mm

RS PRO THREAD CONVERTER, CONDUIT FITTING, 13MM NOMINAL

- Pack size: **5 x EA**
- Nominal Size: 13 mm
 - Fitting Type: Thread Converter
 - Thread Size: PG13.5 → M20
 - Material: Brass
 - Finish: Nickel Plated



623934 13 mm

RS PRO THREAD CONVERTER, CONDUIT FITTING, 16MM NOMINAL

- Pack size: **5 x EA**
- Nominal Size: 16 mm
 - Fitting Type: Thread Converter
 - Thread Size: PG16 → M20
 - Material: Brass
 - Colour: Black
 - IP Rating: IP66
 - Finish: Nickel Plated



623940 16 mm

RS PRO THREAD CONVERTER, CONDUIT FITTING, 21MM NOMINAL

Pack size: **5 x EA**

- Nominal Size: 21 mm
- Fitting Type: Thread Converter
- Thread Size: PG21 → M25
- Material: Brass
- Finish: Nickel Plated



623956 21 mm

RS PRO THROUGH BOX, CONDUIT FITTING, 20MM NOMINAL SIZE, 316

Pack size: **1 x EA**

- Nominal Size: 20 mm
- Fitting Type: Through Box
- Material: 316 Stainless Steel
- Colour: Silver
- IP Rating: IP67
- Finish: Satin
- Standards Met: BS EN 60529:1992 - IEC 529:1989, UL



4711243 20 mm

RS PRO ANGLE BOX, CONDUIT FITTING, 25MM NOMINAL SIZE, 316

Pack size: **1 x EA**

- Nominal Size: 25 mm
- Fitting Type: Angle Box
- Material: 316 Stainless Steel
- Colour: Silver
- IP Rating: IP67
- Finish: Satin
- Standards Met: BS EN 60529:1992 - IEC 529:1989, UL



4711271 25 mm

RS PRO 3 WAY TEE BOX, CONDUIT FITTING, 20MM NOMINAL SIZE, 316

Pack size: **1 x EA**

- Nominal Size: 20 mm
- Fitting Type: 3 Way Tee Box
- Material: 316 Stainless Steel
- Colour: Silver
- IP Rating: IP67
- Finish: Satin
- Standards Met: BS EN 60529:1992 - IEC 529:1989, UL



4711287 20 mm

RS PRO 3 WAY TEE BOX, CONDUIT FITTING, 25MM NOMINAL SIZE, 316

Pack size: **1 x EA**

- Nominal Size: 25 mm
- Fitting Type: 3 Way Tee Box
- Material: 316 Stainless Steel
- Colour: Silver
- IP Rating: IP67
- Finish: Satin
- Standards Met: BS EN 60529:1992 - IEC 529:1989, UL



4711293 25 mm

RS PRO FLANGE COUPLER, CONDUIT FITTING, 20MM NOMINAL SIZE, 316

Pack size: **4 x EA**

- Nominal Size: 20 mm
- Fitting Type: Flange Coupler
- Material: 316 Stainless Steel
- Colour: Silver
- Finish: Satin
- Standards Met: BS EN 60529:1992 - IEC 529:1989, UL



4711322 20 mm

RS PRO COUPLER, CONDUIT FITTING, 20MM NOMINAL SIZE, 316 STAINLESS

Pack size: **4 x EA**

- Nominal Size: 20 mm
- Fitting Type: Coupler
- Material: 316 Stainless Steel
- Colour: Silver
- Finish: Satin
- Standards Met: BS EN 60529:1992 - IEC 529:1989, UL



4711344 20 mm

RS PRO COUPLER, CONDUIT FITTING, 25MM NOMINAL SIZE, 316 STAINLESS

Pack size: **4 x EA**

- Nominal Size: 25 mm
- Fitting Type: Coupler
- Material: 316 Stainless Steel
- Colour: Silver
- Finish: Satin
- Standards Met: BS EN 60529:1992 - IEC 529:1989, UL



4711350 25 mm

RS PRO MALE BUSH, CONDUIT FITTING, 20MM NOMINAL SIZE, 316

Pack size: **4 x EA**

- Nominal Size: 20 mm
- Fitting Type: Male Bush
- Material: 316 Stainless Steel
- Colour: Silver
- IP Rating: IP67
- Finish: Satin
- Standards Met: BS EN 60529:1992 - IEC 529:1989, UL



4711366 20 mm

RS PRO SHORT NIPPLE, CONDUIT FITTING, 20MM NOMINAL SIZE, 316

Pack size: **4 x EA**

- Nominal Size: 20 mm
- Fitting Type: Short Nipple
- Material: 316 Stainless Steel
- Colour: Silver
- Finish: Satin
- Standards Met: BS EN 60529:1992 - IEC 529:1989, UL



4711417 20 mm

RS PRO SHORT NIPPLE, CONDUIT FITTING, 25MM NOMINAL SIZE, 316

Pack size: **4 x EA**

- Nominal Size: 25 mm
- Fitting Type: Short Nipple
- Material: 316 Stainless Steel
- Colour: Silver
- Finish: Satin
- Standards Met: BS EN 60529:1992 - IEC 529:1989, UL



4711423 25 mm

RS PRO ADAPTER, CONDUIT FITTING, 20MM NOMINAL SIZE, PG21, NYLON

Pack size: **10 x EA**

- Nominal Size: 20 mm
- Fitting Type: Adapter
- Thread Size: PG21
- Material: Nylon 66



7559051 20 mm

RS PRO ADAPTER, CONDUIT FITTING, 16MM NOMINAL SIZE, PG9, NYLON 66

Pack size: **10 x EA**

- Nominal Size: 16 mm
- Fitting Type: Adapter
- Thread Size: PG9
- Material: Nylon 66



7559057 16 mm

RS PRO ADAPTER, CONDUIT FITTING, 32MM NOMINAL SIZE, PG29, NYLON

Pack size: **10 x EA**

- Nominal Size: 32 mm
- Fitting Type: Adapter
- Thread Size: PG29
- Material: Nylon 66



7559063 32 mm

RS PRO ADAPTER, CONDUIT FITTING, 16MM NOMINAL SIZE, NYLON 66

Pack size: **10 x EA**

- Nominal Size: 16 mm
- Fitting Type: Adapter
- Material: Nylon 66



7559067 16 mm

RS PRO ADAPTER, CONDUIT FITTING, 32MM NOMINAL SIZE, NYLON 66

Pack size: **10 x EA**

- Nominal Size: 32 mm
- Fitting Type: Adapter
- Material: Nylon 66



7559073 32 mm

RS PRO ADAPTER, CONDUIT FITTING, 20MM NOMINAL SIZE, NYLON 66

Pack size: **10 x EA**

- Nominal Size: 20 mm
- Fitting Type: Adapter
- Material: Nylon 66



7559076 20 mm

RS PRO ADAPTER, CONDUIT FITTING, 25MM NOMINAL SIZE, NYLON 66

Pack size: **10 x EA**

- Nominal Size: 25 mm
- Fitting Type: Adapter
- Material: Nylon 66



7559079 25 mm

RS PRO INSPECTION BEND, CONDUIT FITTING, 20MM NOMINAL SIZE, STEEL

Pack size: **5 x EA**

- Nominal Size: 20 mm
- Fitting Type: Inspection Bend
- Material: Steel
- Colour: Silver
- Finish: Galvanised
- Standards Met: BS EN 50086



7639181 20 mm

RS PRO INSPECTION BEND, CONDUIT FITTING, 25MM NOMINAL SIZE, STEEL

Pack size: **5 x EA**

- Nominal Size: 25 mm
- Fitting Type: Inspection Bend
- Material: Steel
- Colour: Silver
- Finish: Galvanised
- Standards Met: BS EN 50086



7639188 25 mm

RS PRO Y BOX, CONDUIT FITTING, 25MM NOMINAL SIZE, STEEL

Pack size: **5 x EA**

- Nominal Size: 25 mm
- Fitting Type: Y Box
- Material: Steel
- Finish: Galvanised
- Standards Met: BS EN 50086



7639191 25 mm

RS PRO Y BOX, CONDUIT FITTING, 20MM NOMINAL SIZE, M4, STEEL

Pack size: **5 x EA**

- Nominal Size: 20 mm
- Fitting Type: Y Box
- Thread Size: M4
- Material: Steel
- Colour: Silver
- Finish: Galvanised
- Standards Met: BS EN 50086



7639194 20 mm

RS PRO INSPECTION ELBOW, CONDUIT FITTING, 20MM NOMINAL

Pack size: **5 x EA**

- Nominal Size: 20 mm
- Fitting Type: Inspection Elbow
- Material: Steel
- Colour: Silver
- Finish: Galvanised
- Standards Met: BS EN 50086



7639210 20 mm

RS PRO INSPECTION ELBOW, CONDUIT FITTING, 25MM NOMINAL

Pack size: **5 x EA**

- Nominal Size: 25 mm
- Fitting Type: Inspection Elbow
- Material: Steel
- Colour: Silver
- Finish: Galvanised
- Standards Met: BS EN 50086



7639214 25 mm

RS PRO RECESSED COVER, CONDUIT FITTING, 20MM NOMINAL SIZE, STEEL

Pack size: **25 x EA**

- Nominal Size: 20 mm, 25 mm
- Fitting Type: Recessed Cover
- Material: Steel
- Finish: Galvanised
- Standards Met: BS EN 50086



7639217 20 mm, 25 mm

RS PRO GASKET, CONDUIT FITTING, 20MM NOMINAL SIZE, RUBBER

Pack size: **25 x EA**

- Nominal Size: 20 mm, 25 mm
- Fitting Type: Gasket
- Material: Rubber
- Colour: Black
- Standards Met: BS EN 50086



7639220 20 mm, 25 mm

RS PRO INSPECTION TEE, CONDUIT FITTING, 20MM NOMINAL SIZE, STEEL

Pack size: **5 x EA**

- Nominal Size: 20 mm
- Fitting Type: Inspection Tee
- Material: Steel
- Colour: Silver
- Finish: Galvanised
- Standards Met: BS EN 50086



7639223 20 mm

RS PRO INSPECTION TEE, CONDUIT FITTING, 25MM NOMINAL SIZE, STEEL

Pack size: **5 x EA**

- Nominal Size: 25 mm
- Fitting Type: Inspection Tee
- Material: Steel
- Colour: Silver
- Finish: Galvanised
- Standards Met: BS EN 50086



7639226 25 mm

RS PRO RECESSED COVER, CONDUIT FITTING, 20MM NOMINAL SIZE, STEEL

Pack size: **25 x EA**

- Nominal Size: 20 mm, 25 mm
- Fitting Type: Recessed Cover
- Material: Steel
- Colour: Black
- Finish: Black Enamel
- Standards Met: BS EN 50086



7639232 20 mm, 25 mm

RS PRO NIPPLE, CONDUIT FITTING, 20MM NOMINAL SIZE, STEEL, SILVER

Pack size: **25 x EA**

- Nominal Size: 20 mm
- Fitting Type: Nipple
- Material: Steel
- Colour: Silver
- Finish: Zinc
- Standards Met: BS EN 50086



7639236 20 mm

RS PRO NIPPLE, CONDUIT FITTING, 25MM NOMINAL SIZE, STEEL, SILVER

Pack size: **25 x EA**

- Nominal Size: 25 mm
- Fitting Type: Nipple
- Material: Steel
- Colour: Silver
- Finish: Zinc
- Standards Met: BS EN 50086



7639245 25 mm

RS PRO ADAPTER, CONDUIT FITTING, 6.35MM NOMINAL SIZE, M16, ZINC

Pack size: **10 x EA**

- Nominal Size: 6.35 mm
- Fitting Type: Adapter
- Thread Size: M16
- Material: Zinc Alloy



7840114 6.35 mm

RS PRO, CONDUIT FITTING, PLASTIC, BLACK

Pack size: **5 x EA**

- Material: Plastic
- Colour: Black



9172000 Plastic

RS PRO, CONDUIT FITTING, PLASTIC, WHITE

Pack size: **5 x EA**

- Material: Plastic
- Colour: White



9172006 Plastic

RS PRO COUPLER, CONDUIT FITTING, (DIA) 20MM NOMINAL SIZE, PVC,

Pack size: **4 x EA**

- Nominal Size: (Dia) 20 mm
- Fitting Type: Coupler
- Material: PVC
- Colour: White



9172044 (Dia) 20 mm

RS PRO T PIECE, CONDUIT FITTING, (DIA) 20MM NOMINAL SIZE, 20MM,

Pack size: **1 x EA**

- Nominal Size: (Dia) 20 mm
- Fitting Type: T Piece
- Thread Size: 20 mm
- Material: PVC
- Colour: White



9172066 (Dia) 20 mm

RS PRO THROUGH BOX, CONDUIT FITTING, (DIA) 20MM NOMINAL SIZE,

Pack size: **1 x EA**

- Nominal Size: (Dia) 20 mm
- Fitting Type: Through Box
- Material: PVC
- Colour: White



9172069 (Dia) 20 mm

RS PRO INSPECTION ELBOW, CONDUIT FITTING, 20MM NOMINAL

Pack size: **1 x EA**

- Nominal Size: 20 mm
- Fitting Type: Inspection Elbow
- Material: PVC
- Colour: Black



9172072 20 mm

RS PRO INSPECTION ELBOW, CONDUIT FITTING, 20MM NOMINAL

Pack size: **1 x EA**

- Nominal Size: 20 mm
- Fitting Type: Inspection Elbow
- Material: PVC
- Colour: White



9172078 20 mm

RS PRO COUPLER, CONDUIT FITTING, (DIA) 20MM NOMINAL SIZE, PVC,

Pack size: **4 x EA**

- Nominal Size: (Dia) 20 mm
- Fitting Type: Coupler
- Material: PVC
- Colour: Black



9172088 (Dia) 20 mm

RS PRO THROUGH BOX, CONDUIT FITTING, (DIA) 20MM NOMINAL SIZE,

Pack size: **1 x EA**

- Nominal Size: (Dia) 20 mm
- Fitting Type: Through Box
- Material: PVC
- Colour: Black



9172094 (Dia) 20 mm

RS PRO ANGLE BOX, CONDUIT FITTING, (DIA) 20MM NOMINAL SIZE,

Pack size: **1 x EA**

- Nominal Size: (Dia) 20 mm
- Fitting Type: Angle Box
- Material: PVC
- Colour: Black



9172104 (Dia) 20 mm

RS PRO 3 WAY TEE BOX, CONDUIT FITTING, (DIA) 20MM NOMINAL SIZE,

Pack size: **1 x EA**

- Nominal Size: (Dia) 20 mm
- Fitting Type: 3 Way Tee Box
- Material: PVC
- Colour: Black



9172107 (Dia) 20 mm

RS PRO INSPECTION BEND, CONDUIT FITTING, (DIA) 25MM NOMINAL SIZE,

Pack size: **1 x EA**

- Nominal Size: (Dia) 25 mm
- Fitting Type: Inspection Bend
- Material: PVC
- Colour: Black



9172126 (Dia) 25 mm

RS PRO CLEAR DIN RAIL TERMINAL BLOCK, 16MM², 450 V

Pack size: **3 x EA**

- Colour: Clear
- American Wire Gauge: 10 → 5 AWG
- Termination Method: Screw
- Cable CSA: 16 mm², 6 mm²
- Voltage Rating: 450 V
- Current Rating: 100 A
- Maximum Operating Temperature: +85 °C



3882833 Clear

RS PRO CLEAR NON-FUSED DIN RAIL TERMINAL, 16MM², 450 V

Pack size: **3 x EA**

- Colour: Clear
- American Wire Gauge: 10 → 5 AWG
- Termination Method: Screw
- Cable CSA: 16 mm², 6 mm²
- Voltage Rating: 450 V
- Current Rating: 100 A
- Maximum Operating Temperature: +85 °C



3882855 Clear

RS PRO CLEAR TERMINAL BLOCK, 35MM², 450 V, 450 V

Pack size: **3 x EA**

- Colour: Clear
- American Wire Gauge: 10 → 2 AWG, 10 → 2 AWG
- Termination Method: Screw
- Cable CSA: 35 mm², 35 mm²
- Voltage Rating: 450 V
- Current Rating: 170 A, 170 A
- Maximum Operating Temperature: +85 °C



3882861 Clear

RS PRO COMMONING BLOCK, 11 WAY, 750 V

Pack size: **1 x EA**

- Number of Ways: 11
- Termination Method: Screw
- Wire Size: 6 mm²
- Voltage Rating: 750 V
- Maximum Operating Temperature: +85 °C



8680752 11

RS PRO COMMONING BLOCK, 4 WAY, 450 V

Pack size: **5 x EA**

- Number of Ways: 4
- Termination Method: Screw
- Wire Size: 16 mm²
- Voltage Rating: 450 V
- Maximum Operating Temperature: +85 °C



8680755 4

RS PRO COMMONING BLOCK, 5 WAY, 450 V

Pack size: **5 x EA**

- Number of Ways: 5
- Termination Method: Screw
- Wire Size: 6 mm²
- Voltage Rating: 450 V
- Maximum Operating Temperature: +85 °C



8680774 5

RS PRO COMMONING BLOCK, 3 WAY, 450 V

Pack size: **5 x EA**

- Number of Ways: 3
- Termination Method: Screw
- Wire Size: 6 mm²
- Voltage Rating: 450 V
- Maximum Operating Temperature: +85 °C



8680786 3

DERIVATIO TERMINAL BLOCK 6-16 6P

Pack size: **1 x EA**

- Number of Ways: 6
- Termination Method: Screw
- Wire Size: 6 mm²
- Voltage Rating: 750 V
- Maximum Operating Temperature: +85 °C



8680792 6

RS PRO COMMONING BLOCK, 6 WAY, 750 V

Pack size: **1 x EA**

- Number of Ways: 6
- Termination Method: Screw
- Wire Size: 16 mm²
- Voltage Rating: 750 V
- Maximum Operating Temperature: +85 °C



8680799 6

RS PRO 8-WAY DOUBLE SCREW EARTH TERMINAL BLOCK, 0 → 16 AWG

Pack size: **5 x EA**

- Earth Block Type: Double Screw
- Wire Size: 0 → 16 mm²
- Colour: Grey
- Number of Ways: 8
- Termination Method: Screw Down
- Housing Material: Brass
- Length: 86 mm
- Width: 18.5 mm



425550 Double Screw

RS PRO 3-WAY DOUBLE SCREW EARTH TERMINAL BLOCK, 0 TO

Pack size: **5 x EA**

- Earth Block Type: Double Screw
- Wire Size: 0 → 16 mm²
- Cable CSA: 0 to 16 mm²
- Colour: Grey
- Number of Ways: 3
- Termination Method: Screw Down
- Housing Material: Brass
- Length: 42.6 mm



2830730 Double Screw

RS PRO COMMONING BLOCK, 3 WAY, 750 V

Pack size: **1 x EA**

- Number of Ways: 3
- Termination Method: Screw
- Wire Size: 35 mm²
- Voltage Rating: 750 V
- Maximum Operating Temperature: +85 °C



8680806 3

RS PRO 6-WAY DOUBLE SCREW EARTH TERMINAL BLOCK, 0 TO

Pack size: **5 x EA**

- Earth Block Type: Double Screw
- Wire Size: 0 → 16 mm²
- Cable CSA: 0 to 16 mm²
- Colour: Grey
- Number of Ways: 6
- Termination Method: Screw Down
- Housing Material: Brass
- Length: 69 mm



2830768 Double Screw

RS PRO 4-WAY DOUBLE SCREW EARTH TERMINAL BLOCK, 0 TO

Pack size: **5 x EA**

- Earth Block Type: Double Screw
- Wire Size: 0 → 16 mm²
- Cable CSA: 0 to 16 mm²
- Colour: Grey
- Number of Ways: 4
- Termination Method: Screw Down
- Housing Material: Brass
- Length: 51.4 mm



425544 Double Screw

RS PRO 3-WAY CE (BS EN 60998) EARTH BLOCK, 0 → 16 AWG WIRE,

Pack size: **1 x EA**

- Earth Block Type: CE (BS EN 60998)
- Wire Size: 0 → 16 AWG
- Cable CSA: 0 to 16 mm²
- Number of Ways: 3
- Termination Method: Screw Down
- Housing Material: Brass
- Length: 42.3 mm
- Width: 18 mm
- Height: 12 mm



8670991 CE (BS EN

RS PRO 5-WAY CE (BS EN 60998) EARTH BLOCK, 0 → 16 AWG WIRE,

Pack size: **1 x EA**

- Earth Block Type: CE (BS EN 60998)
- Wire Size: 0 → 16 AWG
- Number of Ways: 5
- Termination Method: Screw Down
- Housing Material: Brass
- Length: 59.7 mm
- Width: 18 mm
- Height: 12 mm



8671004 CE (BS EN

RS PRO 8-WAY CE (BS EN 60998) EARTH BLOCK, 0 → 16 AWG WIRE,

Pack size: **1 x EA**

- Earth Block Type: CE (BS EN 60998)
- Wire Size: 0 → 16 AWG
- Number of Ways: 8
- Termination Method: Screw Down
- Housing Material: Brass
- Length: 86 mm
- Width: 18 mm
- Height: 12 mm



8671007 CE (BS EN

RS PRO 5-WAY DOUBLE SCREW EARTH TERMINAL BLOCK, 0 TO

Pack size: **5 x EA**

- Earth Block Type: Double Screw
- Wire Size: 0 → 16 mm²
- Cable CSA: 0 to 16 mm²
- Colour: Grey
- Number of Ways: 5
- Termination Method: Screw Down
- Housing Material: Brass
- Length: 60 mm



2830746 Double Screw

RS PRO 7-WAY DOUBLE SCREW EARTH TERMINAL BLOCK, 0 TO

Pack size: **5 x EA**

- Earth Block Type: Double Screw
- Wire Size: 0 → 16 mm²
- Cable CSA: 0 to 16 mm²
- Colour: Grey
- Number of Ways: 7
- Termination Method: Screw Down
- Housing Material: Brass
- Length: 77.2 mm



2830774 Double Screw

CONNECTOR, TERMINAL BLOCK, TEETUBE, 3 POLE, BLACK

Pack size: **1 x EA**

- Material: Nylon
- Length: 115 mm
- Height: 26.5 mm
- IP Rating: IP68
- Number of Terminals: 3
- Colour: Black
- Number of Ways: 3
- Cable Entry: 2



4691795 Nylon

RS PRO BLACK JUNCTION BOX, 4 TERMINALS

Pack size: **5 x EA**

- Number of Terminals: 4
- Colour: Black
- Number of Ways: 4
- Current Rating: 5 A
- Diameter: 62 mm



7767646 4

CONNECTOR, TERMINAL BLOCK, TEETUBE, 5 POLE, BLACK

Pack size: **1 x EA**

- Material: Nylon
- Length: 130 mm
- Height: 32 mm
- IP Rating: IP68
- Number of Terminals: 5
- Colour: Black
- Number of Ways: 5
- Cable Entry: 2



4691818 Nylon

RS PRO GREY 1 BLANKING PLATE

Pack size: **1 x EA**

- Colour: Grey
- Material: Metal
- Number of Gangs: 1
- Series: RS Metalclad



3611940 Grey

RS PRO BLACK JUNCTION BOX, 4 TERMINALS

Pack size: **5 x EA**

- Number of Terminals: 4
- Colour: Black
- Number of Ways: 4
- Current Rating: 20 A
- Diameter: 76 mm



7767640 4

RS PRO BLACK JUNCTION BOX, 3 TERMINALS

Pack size: **5 x EA**

- Number of Terminals: 3
- Colour: Black
- Number of Ways: 4
- Current Rating: 30 A
- Diameter: 76 mm



7767659 3

RS PRO GREY 2 BLANKING PLATE

Pack size: **1 x EA**

- Colour: Grey
- Material: Steel
- Number of Gangs: 2
- Series: RS Metalclad



3611956 Grey

RS PRO 1 WAY BRUSH PLATE

Pack size: **1 x EA**

- Type: Brush Plate
- Number of Outlets: 1
- Number of Ways: 1
- Length: 86 mm
- Width: 86 mm
- Depth: 10 mm



8781091 Brush Plate

RS PRO 2 WAY BRUSH PLATE

Pack size: **1 x EA**

- Type: Brush Plate
- Number of Outlets: 2
- Number of Ways: 2
- Length: 86 mm
- Width: 121 mm
- Depth: 10 mm



8781101 Brush Plate

CONNECTOR, TERMINAL, SOLDER TAG, M4/3BA

Pack size: **250 x EA**

- Inner Diameter: 4.3 mm
- Contact Material: Brass
- Contact Plating: Tin



1867848 4.3 mm

CONNECTOR, TERMINAL, SOLDER TAG, M6/0BA

Pack size: **250 x EA**

- Inner Diameter: 6.4 mm
- Contact Material: Brass
- Contact Plating: Tin



1867826 6.4 mm

CONNECTOR, TERMINAL, SOLDER TAG, M5/2BA

Pack size: **250 x EA**

- Inner Diameter: 5.3 mm
- Contact Material: Brass
- Contact Plating: Tin



1867832 5.3 mm

RS PRO SOLDER TAG, BRASS CONTACTS, TIN

Pack size: **250 x EA**

- Inner Diameter: 3.5 mm
- Contact Material: Brass
- Contact Plating: Tin



1867854 3.5 mm

RS PRO 3-WAY NON-FUSED TERMINAL BLOCK, 40A, SCREW DOWN

Pack size: **5 x EA**

- Number of Ways: 3
- Current Rating: 40 A
- Wire Size: 22 → 8 AWG
- Termination Method: Screw Down
- Mounting Type: Screw Down
- Fused: No
- Material: Nylon
- Pitch: 17.7 mm



465637 3

RS PRO 3-WAY FUSED TERMINAL BLOCK, 6.3A, SCREW TERMINALS,

Pack size: **10 x EA**

- Number of Ways: 3
- Current Rating: 6.3 A
- Termination Method: Screw
- Mounting Type: Panel Mount
- Fused: Yes
- Material: Nylon 66
- Pitch: 9 mm
- Voltage Rating: 450 V



1225193 3

CONNECTOR, TERMINAL, SOLDER TAG, M3/6BA

Pack size: **250 x EA**

- Inner Diameter: 3.2 mm
- Contact Material: Brass
- Contact Plating: Tin



1867860 3.2 mm

CONNECTOR, TERMINAL, SOLDER TAG, M2/8BA

Pack size: **250 x EA**

- Inner Diameter: 2.2 mm
- Contact Material: Brass
- Contact Plating: Tin



1867876 2.2 mm

CONNECTOR,TERMINAL BLOCK,NYLON,6,6,24A,12 WAY

Pack size: **5 x EA**

- Number of Ways: 12
- Current Rating: 24 A
- Wire Size: 2.5 mm²
- Termination Method: Screw Down
- Mounting Type: Through Hole
- Fused: No
- Material: Nylon
- Voltage Rating: 400 V



4649738 12

CONNECTOR,TERMINAL BLOCK,NYLON,6,6,41A,12 WAY

Pack size: **5 x EA**

- Number of Ways: 12
- Current Rating: 50 A
- Wire Size: 10 mm²
- Termination Method: Screw Down
- Fused: No
- Material: Nylon
- Voltage Rating: 400 V
- Pitch: 15 mm



4649700 12

CONNECTOR,TERMINAL BLOCK,NYLON,6,6,32A,12 WAY

Pack size: **5 x EA**

- Number of Ways: 12
- Current Rating: 41 A
- Wire Size: 4 mm²
- Termination Method: Screw Down
- Mounting Type: Through Hole
- Fused: No
- Material: Nylon
- Pitch: 12 mm



4649722 12

CONNECTOR,TERMINAL BLOCK,NYLON,6,6,17.5A,12 WAY

Pack size: **5 x EA**

- Number of Ways: 12
- Current Rating: 24 A
- Wire Size: 2.5 mm²
- Termination Method: Screw Down
- Mounting Type: Free Hanging
- Fused: No
- Material: Nylon
- Voltage Rating: 380 V



4649744 12

RS PRO 12-WAY NON-FUSED TERMINAL BLOCK, 57A, SCREW

Pack size: **5 x EA**

- Number of Ways: 12
- Current Rating: 57 A
- Wire Size: 6 mm²
- Termination Method: Screw Down
- Mounting Type: Through Hole
- Fused: No
- Material: Glass Fibre Reinforced Nylon
- Voltage Rating: 400 V



4649750 12

CONNECTOR,TERMINAL BLOCK,HIGH TEMP,32A,12 WAY

Pack size: **5 x EA**

- Number of Ways: 12
- Current Rating: 41 A
- Wire Size: 4 mm²
- Termination Method: Screw Down
- Mounting Type: Through Hole
- Fused: No
- Material: Nylon
- Pitch: 12 mm



4649766 12

CONNECTOR,TERMINAL BLOCK,12 WAY,1.5MM2,NYLON,250-

Pack size: **5 x EA**

- Number of Ways: 12
- Current Rating: 24 A
- Wire Size: 2.5 mm²
- Termination Method: Screw Down
- Mounting Type: Through Hole
- Fused: No
- Material: Nylon
- Pitch: 8 mm



4928687 12

CONNECTOR,TERMINAL BLOCK,HIGH TEMP,17.5A,12 WAY

Pack size: **5 x EA**

- Number of Ways: 12
- Current Rating: 24 A
- Wire Size: 2.5 mm²
- Termination Method: Screw Down
- Mounting Type: Through Hole
- Fused: No
- Material: Nylon
- Pitch: 8 mm



4649772 12

CONNECTOR,TERMINAL BLOCK,HIGH TEMP,24A,12 WAY

Pack size: **5 x EA**

- Number of Ways: 12
- Current Rating: 32 A
- Wire Size: 2.5 mm²
- Termination Method: Screw Down
- Mounting Type: Through Hole
- Fused: No
- Material: Nylon
- Voltage Rating: 400 V



4649788 12

CONNECTOR,TERMINAL BLOCK,12 WAY,2.5MM2,NYLON,400V,NATURAL

Pack size: **5 x EA**

- Number of Ways: 12
- Current Rating: 32 A
- Wire Size: 4 mm²
- Termination Method: Screw Down
- Mounting Type: Through Hole
- Fused: No
- Material: Nylon
- Voltage Rating: 400 V



4928700 12

RS PRO 12-WAY NON-FUSED TERMINAL BLOCK, 41A, SCREW

Pack size: **5 x EA**

- Number of Ways: 12
- Current Rating: 41 A
- Wire Size: 6 mm²
- Termination Method: Screw Down
- Mounting Type: Through Hole
- Fused: No
- Material: Nylon
- Voltage Rating: 400 V



4928716 12

CONNECTOR,TERMINAL BLOCK,12 WAY,6MM2,NYLON,400V,NATURAL

Pack size: **5 x EA**

- Number of Ways: 12
- Current Rating: 57 A
- Wire Size: 10 mm²
- Termination Method: Screw Down
- Mounting Type: Through Hole
- Fused: No
- Material: Nylon
- Voltage Rating: 400 V



4928722 12

RS PRO 2-WAY NON-FUSED TERMINAL BLOCK, 16A, SCREW DOWN

Pack size: **5 x EA**

- Number of Ways: 2
- Current Rating: 16 A
- Wire Size: 2.5 mm²
- Termination Method: Screw Down
- Mounting Type: Cable Mount
- Fused: No
- Material: Nylon
- Voltage Rating: 400 V



4956187 2

CONNECTOR,TERMINAL BLOCK,2 WAY,2.5MM2,NYLON,400V,BROWN,

Pack size: **5 x EA**

- Number of Ways: 2
- Current Rating: 16 A
- Wire Size: 2.5 mm²
- Termination Method: Screw Down
- Mounting Type: Cable Mount
- Fused: No
- Material: Nylon
- Voltage Rating: 400 V



4956193 2

RS PRO 2-WAY NON-FUSED TERMINAL BLOCK, 16A, SCREW DOWN

Pack size: **5 x EA**

- Number of Ways: 2
- Current Rating: 16 A
- Wire Size: 2.5 mm²
- Termination Method: Screw Down
- Mounting Type: Cable Mount
- Fused: No
- Material: Nylon
- Voltage Rating: 400 V



4956200 2

RS PRO 2-WAY NON-FUSED TERMINAL BLOCK, 16A, SCREW DOWN

Pack size: **5 x EA**

- Number of Ways: 2
- Current Rating: 16 A
- Wire Size: 2.5 mm²
- Termination Method: Screw Down
- Mounting Type: Cable Mount
- Fused: No
- Material: Nylon
- Voltage Rating: 400 V



4956216 2

RS PRO 3-WAY NON-FUSED TERMINAL BLOCK, 16A, SCREW DOWN

Pack size: **5 x EA**

- Number of Ways: 3
- Current Rating: 16 A
- Wire Size: 2.5 mm²
- Termination Method: Screw Down
- Mounting Type: Cable Mount
- Fused: No
- Material: Nylon
- Voltage Rating: 400 V



4956238 3

RS PRO 3-WAY NON-FUSED TERMINAL BLOCK, 16A, SCREW DOWN

Pack size: **5 x EA**

- Number of Ways: 3
- Current Rating: 16 A
- Wire Size: 2.5 mm²
- Termination Method: Screw Down
- Mounting Type: Cable Mount
- Fused: No
- Material: Nylon
- Voltage Rating: 400 V



4956250 3

RS PRO 3-WAY NON-FUSED TERMINAL BLOCK, 16A, SCREW DOWN

Pack size: **5 x EA**

- Number of Ways: 3
- Current Rating: 16 A
- Wire Size: 2.5 mm²
- Termination Method: Screw Down
- Mounting Type: Cable Mount
- Fused: No
- Material: Nylon
- Voltage Rating: 400 V



4956266 3

RS PRO 3-WAY NON-FUSED TERMINAL BLOCK, 16A, SCREW DOWN

Pack size: **5 x EA**

- Number of Ways: 3
- Current Rating: 16 A
- Wire Size: 2.5 mm²
- Termination Method: Screw Down
- Mounting Type: Cable Mount
- Fused: No
- Material: Nylon
- Voltage Rating: 400 V



4956272 3

RS PRO 3-WAY NON-FUSED TERMINAL BLOCK, 16A, SCREW DOWN

Pack size: **5 x EA**

- Number of Ways: 3
- Current Rating: 16 A
- Wire Size: 2.5 mm²
- Termination Method: Screw Down
- Mounting Type: Cable Mount
- Fused: No
- Material: Nylon
- Voltage Rating: 400 V



4956288 3

RS PRO 3-WAY NON-FUSED TERMINAL BLOCK, 16A, SCREW DOWN

Pack size: **5 x EA**

- Number of Ways: 3
- Current Rating: 16 A
- Wire Size: 2.5 mm²
- Termination Method: Screw Down
- Mounting Type: Cable Mount
- Fused: No
- Material: Nylon
- Voltage Rating: 400 V



4956294 3

RS PRO 3-WAY NON-FUSED TERMINAL BLOCK, 16A, SCREW DOWN

Pack size: **5 x EA**

- Number of Ways: 3
- Current Rating: 16 A
- Wire Size: 2.5 mm²
- Termination Method: Screw Down
- Mounting Type: Cable Mount
- Fused: No
- Material: Nylon
- Voltage Rating: 400 V



4956301 3

12 WAY POLYPROPYLENE 6A TERMINAL BLOCK

Pack size: **5 x EA**

- Number of Ways: 12
- Current Rating: 6 A
- Wire Size: 14 AWG
- Termination Method: Screw Down
- Fused: No
- Material: PP
- Pitch: 8 mm
- Voltage Rating: 400 V



7033814 12

12 WAY POLYPROPYLENE 10A TERMINAL BLOCK

Pack size: **5 x EA**

- Number of Ways: 12
- Current Rating: 24 A
- Wire Size: 12 AWG
- Termination Method: Screw Down
- Fused: No
- Material: PP
- Pitch: 10 mm
- Voltage Rating: 380 V



7033818 12

RS PRO 12-WAY NON-FUSED TERMINAL BLOCK, 76A, SCREW

Pack size: **5 x EA**

- Number of Ways: 12
- Current Rating: 76 A
- Wire Size: 6 AWG
- Termination Method: Screw Down
- Fused: No
- Material: PP
- Pitch: 15 mm
- Voltage Rating: 400 V



7033820 12

RS PRO 12-WAY NON-FUSED TERMINAL BLOCK, 101A, SCREW

Pack size: **5 x EA**

- Number of Ways: 12
- Current Rating: 101 A
- Wire Size: 4 AWG
- Termination Method: Screw Down
- Fused: No
- Material: PP
- Pitch: 19.5 mm
- Voltage Rating: 400 V



7033824 12

RS PRO 12-WAY NON-FUSED TERMINAL BLOCK, 20A, SCREW

Pack size: **5 x EA**

- Number of Ways: 12
- Current Rating: 20 A
- Wire Size: 10 AWG
- Termination Method: Screw Down
- Fused: No
- Material: PP
- Pitch: 12 mm
- Voltage Rating: 380 V



7033827 12

BLACK 6MMSQ. TERMINAL STRIP 450V

Pack size: **5 x EA**

- Number of Ways: 12
- Current Rating: 32 A
- Wire Size: 6 mm²
- Termination Method: Screw
- Fused: No
- Material: POLYPROPYLENE
- Pitch: 12 mm
- Voltage Rating: 380 V



7033830 12

BLACK 2.5MMSQ. TERMINAL STRIP 250V

Pack size: **5 x EA**

- Number of Ways: 12
- Current Rating: 24 A
- Wire Size: 2.5 mm²
- Termination Method: Screw
- Fused: No
- Material: POLYPROPYLENE
- Pitch: 8 mm
- Voltage Rating: 400 V



7033833 12

BLACK 4MMSQ. TERMINAL STRIP 450V

Pack size: **5 x EA**

- Number of Ways: 12
- Current Rating: 24 A
- Wire Size: 4 mm²
- Termination Method: Screw
- Fused: No
- Material: POLYPROPYLENE
- Pitch: 10 mm
- Voltage Rating: 380 V



7033836 12

BLACK 16MMSQ. TERMINAL STRIP 450V

Pack size: **5 x EA**

- Number of Ways: 12
- Current Rating: 76 A
- Wire Size: 16 mm²
- Termination Method: Screw
- Fused: No
- Material: POLYPROPYLENE
- Pitch: 15 mm
- Voltage Rating: 400 V



7033842 12

2 WAY 10A CERAMIC TERMINAL BLOCK 230V

Pack size: **5 x EA**

- Number of Ways: 2
- Current Rating: 32 A
- Wire Size: 12 AWG
- Termination Method: Screw Down
- Fused: No
- Material: Ceramic
- Voltage Rating: 450 V
- Minimum Operating Temperature: -40 °C



7033846 2

BLACK 10MMSQ. TERMINAL STRIP 450V

Pack size: **5 x EA**

- Number of Ways: 12
- Current Rating: 57 A
- Wire Size: 10 mm²
- Termination Method: Screw
- Fused: No
- Material: POLYPROPYLENE
- Pitch: 11 mm
- Voltage Rating: 400 V



7033849 12

3 WAY 15A TERMINAL BLOCK

Pack size: **5 x EA**

- Number of Ways: 3
- Current Rating: 57 A
- Wire Size: 8 AWG
- Termination Method: Screw Down
- Fused: No
- Material: Ceramic
- Voltage Rating: 450 V
- Minimum Operating Temperature: -40 °C



7033852 3

RS PRO 3-WAY NON-FUSED TERMINAL BLOCK, 32A, SCREW DOWN

Pack size: **5 x EA**

- Number of Ways: 3
- Current Rating: 32 A
- Wire Size: 12 AWG
- Termination Method: Screw Down
- Fused: No
- Material: Ceramic
- Voltage Rating: 450 V
- Minimum Operating Temperature: -40 °C



7033855 3

2 WAY 15A CERAMIC TERMINAL BLOCK 450V

Pack size: **5 x EA**

- Number of Ways: 2
- Current Rating: 57 A
- Wire Size: 8 AWG
- Termination Method: Screw Down
- Fused: No
- Material: Ceramic
- Voltage Rating: 450 V
- Minimum Operating Temperature: -40 °C



7033858 2

2 WAY 30A CERAMIC TERMINAL BLOCK 450V

Pack size: **5 x EA**

- Number of Ways: 2
- Current Rating: 76 A
- Wire Size: 6 AWG
- Termination Method: Screw Down
- Fused: No
- Material: Ceramic
- Voltage Rating: 450 V
- Minimum Operating Temperature: -40 °C



7033861 2

3 WAY 30A CERAMIC TERMINAL BLOCK 450V

Pack size: **5 x EA**

- Number of Ways: 3
- Current Rating: 76 A
- Wire Size: 6 AWG
- Termination Method: Screw Down
- Fused: No
- Material: Ceramic
- Voltage Rating: 450 V
- Minimum Operating Temperature: -40 °C



7033864 3

12 WAY POLYETHYLENE TERMINAL BLOCK, 3A

Pack size: **10 x EA**

- Number of Ways: 12
- Current Rating: 3 → 24 A
- Wire Size: 12 AWG
- Termination Method: Screw
- Mounting Type: Free Hanging, Panel Mount
- Fused: No
- Material: PE
- Pitch: 8 mm



7638113 12

12 WAY POLYETHYLENE TERMINAL BLOCK, 5A

Pack size: **10 x EA**

- Number of Ways: 12
- Current Rating: 5 → 32 A
- Wire Size: 10 AWG
- Termination Method: Screw
- Mounting Type: Free Hanging, Panel Mount
- Fused: No
- Material: PE
- Pitch: 10 mm



7638116 12

12 WAY MOULDED BARRIER STRIP, 15A

Pack size: **1 x EA**

- Number of Ways: 12
- Current Rating: 20 A
- Wire Size: 12 AWG
- Termination Method: Screw
- Mounting Type: Free Hanging, Panel Mount
- Fused: No
- Material: Polyamide
- Voltage Rating: 750 V



7638122 12

3 WAY MOULDED BARRIER STRIP, 15A

Pack size: **5 x EA**

- Number of Ways: 3
- Current Rating: 20 A
- Wire Size: 12 AWG
- Termination Method: Screw
- Mounting Type: Free Hanging, Panel Mount
- Fused: No
- Material: Polyamide
- Voltage Rating: 750 V



7638129 3

RS PRO 10-WAY NON-FUSED TERMINAL BLOCK, 24A, SCREW

Pack size: **10 x EA**

- Number of Ways: 10
- Current Rating: 24 A
- Wire Size: 1.5 mm²
- Termination Method: Screw
- Fused: No
- Material: PC
- Pitch: 9.4 mm
- Voltage Rating: 450 V



7869196 10

RS PRO 10-WAY NON-FUSED TERMINAL BLOCK, 57A, SCREW

Pack size: **6 x EA**

- Number of Ways: 10
- Current Rating: 57 A
- Wire Size: 10 mm²
- Termination Method: Screw
- Fused: No
- Material: PC
- Voltage Rating: 500 V
- Pitch: 16.5 mm



7869207 10

RS PRO 1-WAY NON-FUSED TERMINAL BLOCK, 125A, SCREW TERMINALS, 35

Pack size: **5 x EA**

- Number of Ways: 1
- Current Rating: 125 A
- Wire Size: 35 mm²
- Termination Method: Screw
- Fused: No
- Material: PC
- Voltage Rating: 500 V
- Minimum Operating Temperature: +85 °C



7869213 1

CERAMIC TERMINAL BLOCKS, 4 MM2, 4 POLES

Pack size: **5 x EA**

- Number of Ways: 4
- Current Rating: 5 → 32 A
- Wire Size: 12 AWG
- Termination Method: Screw Down
- Mounting Type: Screw
- Fused: No
- Material: Ceramic
- Voltage Rating: 450 V



8133098 4

RS PRO 4-WAY NON-FUSED TERMINAL BLOCK, 30 → 76A, SCREW DOWN

Pack size: **5 x EA**

- Number of Ways: 4
- Current Rating: 30 → 76 A
- Wire Size: 6 AWG
- Termination Method: Screw Down
- Mounting Type: Screw
- Fused: No
- Material: Ceramic
- Voltage Rating: 450 V



8133101 4

CERAMIC TERMINAL BLOCKS, 4 MM2,3 POLES

Pack size: **5 x EA**

- Number of Ways: 3
- Current Rating: 5 → 32 A
- Wire Size: 12 AWG
- Termination Method: Screw Down
- Mounting Type: Screw
- Fused: No
- Material: Ceramic
- Voltage Rating: 250 V



8133105 3

RS PRO 4-WAY NON-FUSED TERMINAL BLOCK, 15 → 57A, SCREW DOWN

Pack size: **5 x EA**

- Number of Ways: 4
- Current Rating: 15 → 57 A
- Wire Size: 8 AWG
- Termination Method: Screw Down
- Mounting Type: Screw
- Fused: No
- Material: Ceramic
- Voltage Rating: 450 V



8133108 4

RS PRO 1-WAY NON-FUSED TERMINAL BLOCK, 30 → 76A, SCREW DOWN

Pack size: **10 x EA**

- Number of Ways: 1
- Current Rating: 30 → 76 A
- Wire Size: 6 AWG
- Termination Method: Screw Down
- Mounting Type: Screw
- Fused: No
- Material: Ceramic
- Voltage Rating: 450 V



8133111 1

CERAMIC TERMINAL BLOCKS, 4 MM2, 1 POLE

Pack size: **10 x EA**

- Number of Ways: 1
- Current Rating: 5 → 32 A
- Wire Size: 12 AWG
- Termination Method: Screw Down
- Mounting Type: Screw
- Fused: No
- Material: Ceramic
- Voltage Rating: 450 V



8133114 1

CERAMIC TERMINAL BLOCKS , 10 MM2, 1 POLE

Pack size: **10 x EA**

- Number of Ways: 1
- Current Rating: 15 → 32 A
- Wire Size: 8 AWG
- Termination Method: Screw Down
- Mounting Type: Screw
- Fused: No
- Material: Ceramic
- Voltage Rating: 450 V



8133117 1

PA TERMINAL BLOCKS,4MM2

Pack size: **5 x EA**

- Number of Ways: 12
- Current Rating: 3 → 24 A
- Wire Size: 12 AWG
- Termination Method: Screw Down
- Mounting Type: Screw
- Fused: No
- Material: Polyamide
- Voltage Rating: 380 V



8133120 12

PA TERMINAL BLOCKS, 6 MM2

Pack size: **5 x EA**

- Number of Ways: 12
- Current Rating: 5 → 32 A
- Wire Size: 10 AWG
- Termination Method: Screw Down
- Mounting Type: Screw
- Fused: No
- Material: Polyamide
- Voltage Rating: 380 V



8133123 12

RS PRO 12-WAY NON-FUSED TERMINAL BLOCK, 10 → 57A, SCREW

Pack size: **5 x EA**

- Number of Ways: 12
- Current Rating: 10 → 57 A
- Wire Size: 8 AWG
- Termination Method: Screw Down
- Mounting Type: Screw
- Fused: No
- Material: Polyamide
- Voltage Rating: 400 V



8133127 12

RS PRO 12-WAY NON-FUSED TERMINAL BLOCK, 15 → 61A, SCREW

Pack size: **5 x EA**

- Number of Ways: 12
- Current Rating: 15 → 61 A
- Wire Size: 7 AWG
- Termination Method: Screw Down
- Mounting Type: Screw
- Fused: No
- Material: Polyamide
- Voltage Rating: 400 V



8133136 12

RS PRO 12-WAY NON-FUSED TERMINAL BLOCK, 30 → 76A, SCREW

Pack size: **5 x EA**

- Number of Ways: 12
- Current Rating: 30 → 76 A
- Wire Size: 6 AWG
- Termination Method: Screw Down
- Mounting Type: Screw
- Fused: No
- Material: Polyamide
- Voltage Rating: 400 V



8133139 12

RS PRO 12-WAY NON-FUSED TERMINAL BLOCK, 10 → 57A, SCREW

Pack size: **5 x EA**

- Number of Ways: 12
- Current Rating: 10 → 57 A
- Wire Size: 8 AWG
- Termination Method: Screw
- Mounting Type: Cable Mount
- Fused: No
- Material: Polyamide
- Voltage Rating: 450 V



8407923 12

PA TERMINAL BLOCK 2.5MM2

Pack size: **5 x EA**

- Number of Ways: 12
- Current Rating: 2.5 → 20 A
- Wire Size: 14 AWG
- Termination Method: Screw
- Mounting Type: Cable Mount
- Fused: No
- Material: Polyamide
- Voltage Rating: 450 V



8407929 12

RS PRO 12-WAY NON-FUSED TERMINAL BLOCK, 5 → 32A, SCREW

Pack size: **5 x EA**

- Number of Ways: 12
- Current Rating: 5 → 32 A
- Wire Size: 10 AWG
- Termination Method: Screw
- Mounting Type: Cable Mount
- Fused: No
- Material: Polyamide
- Voltage Rating: 450 V



8407932 12

RS PRO 12-WAY NON-FUSED TERMINAL BLOCK, 3 → 24A, SCREW

Pack size: **5 x EA**

- Number of Ways: 12
- Current Rating: 3 → 24 A
- Wire Size: 12 AWG
- Termination Method: Screw
- Mounting Type: Cable Mount
- Fused: No
- Material: Polyamide
- Voltage Rating: 450 V



8407935 12

RS PRO 12-WAY NON-FUSED TERMINAL BLOCK, 17.5A, SCREW

Pack size: **5 x EA**

- Number of Ways: 12
- Current Rating: 17.5 A
- Wire Size: 16 AWG
- Termination Method: Screw
- Mounting Type: Cable Mount
- Fused: No
- Material: Polyamide
- Voltage Rating: 450 V



8407939 12

RS PRO 12-WAY NON-FUSED TERMINAL BLOCK, 32A, SCREW

Pack size: **5 x EA**

- Number of Ways: 12
- Current Rating: 32 A
- Wire Size: 12 AWG
- Termination Method: Screw
- Mounting Type: Cable Mount
- Fused: No
- Material: Polyamide
- Voltage Rating: 450 V



8407941 12

RS PRO 12-WAY NON-FUSED TERMINAL BLOCK, 32A, SCREW

Pack size: **5 x EA**

- Number of Ways: 12
- Current Rating: 32 A
- Wire Size: 12 AWG
- Termination Method: Screw
- Mounting Type: Cable Mount
- Fused: No
- Material: Polyamide
- Voltage Rating: 450 V



8407951 12

PA TERMINAL BLOCK 2.5MM2

Pack size: **5 x EA**

- Number of Ways: 12
- Current Rating: 17.5 A
- Wire Size: 16 AWG
- Termination Method: Screw
- Mounting Type: Cable Mount
- Fused: No
- Material: Polyamide
- Voltage Rating: 450 V



8407954 12

RS PRO 12-WAY NON-FUSED TERMINAL BLOCK, 24A, SCREW

Pack size: **5 x EA**

- Number of Ways: 12
- Current Rating: 24 A
- Wire Size: 14 AWG
- Termination Method: Screw
- Mounting Type: Cable Mount
- Fused: No
- Material: Polyamide
- Voltage Rating: 450 V



8407957 12

RS PRO 12-WAY NON-FUSED TERMINAL BLOCK, 41A, SCREW

Pack size: **5 x EA**

- Number of Ways: 12
- Current Rating: 41 A
- Wire Size: 10 AWG
- Termination Method: Screw
- Mounting Type: Cable Mount
- Fused: No
- Material: Polyamide
- Voltage Rating: 450 V



8407960 12

RS PRO 12-WAY NON-FUSED TERMINAL BLOCK, 2.5 → 20A, SCREW

Pack size: **1 x EA**

- Number of Ways: 12
- Current Rating: 2.5 → 20 A
- Wire Size: 14 AWG
- Termination Method: Screw
- Fused: No
- Material: Polyamide
- Voltage Rating: 450 V
- Pitch: 7.2 mm



8659821 12

PA TERM BLOCKS HORIZONTAL PLUG 4MM2

Pack size: **1 x EA**

- Number of Ways: 12
- Current Rating: 3 → 24 A
- Wire Size: 12 AWG
- Termination Method: Screw
- Fused: No
- Material: Polyamide
- Voltage Rating: 450 V
- Minimum Operating Temperature: -40 °C



8659830 12

RS PRO 12-WAY NON-FUSED TERMINAL BLOCK, 5 → 32A, SCREW

Pack size: **1 x EA**

- Number of Ways: 12
- Current Rating: 5 → 32 A
- Wire Size: 10 AWG
- Termination Method: Screw
- Fused: No
- Material: Polyamide
- Voltage Rating: 450 V
- Minimum Operating Temperature: -40 °C



8659833 12

RS PRO 12-WAY NON-FUSED TERMINAL BLOCK, 10 → 57A, SCREW

Pack size: **5 x EA**

- Number of Ways: 12
- Current Rating: 10 → 57 A
- Wire Size: 8 AWG
- Termination Method: Screw Down
- Mounting Type: Cable Mount
- Fused: No
- Material: PE
- Voltage Rating: 400 V



8670963 12

RS PRO 12-WAY NON-FUSED TERMINAL BLOCK, 15 → 61A, SCREW

Pack size: **5 x EA**

- Number of Ways: 12
- Current Rating: 15 → 61 A
- Wire Size: 7 AWG
- Termination Method: Screw Down
- Mounting Type: Cable Mount
- Fused: No
- Material: PE
- Voltage Rating: 400 V



8670972 12

RS PRO 12-WAY NON-FUSED TERMINAL BLOCK, 30 → 76A, SCREW

Pack size: **5 x EA**

- Number of Ways: 12
- Current Rating: 30 → 76 A
- Wire Size: 6 AWG
- Termination Method: Screw Down
- Mounting Type: Cable Mount
- Fused: No
- Material: PE
- Voltage Rating: 400 V



8670975 12

RS PRO 12-WAY NON-FUSED TERMINAL BLOCK, 60 → 101A, SCREW

Pack size: **5 x EA**

- Number of Ways: 12
- Current Rating: 60 → 101 A
- Wire Size: 4 AWG
- Termination Method: Screw Down
- Mounting Type: Cable Mount
- Fused: No
- Material: PE
- Voltage Rating: 400 V



8670979 12

RS PRO 12-WAY NON-FUSED TERMINAL BLOCK, 60 → 101A, SCREW

Pack size: **5 x EA**

- Number of Ways: 12
- Current Rating: 60 → 101 A
- Wire Size: 4 AWG
- Termination Method: Screw Down
- Mounting Type: Cable Mount
- Fused: No
- Material: PA 66
- Voltage Rating: 400 V



8670988 12

RS PRO 12-WAY NON-FUSED TERMINAL BLOCK, SCREW

Pack size: **1 x EA**

- Number of Ways: 12
- Wire Size: 25 mm²
- Termination Method: Screw
- Mounting Type: Panel Mount
- Fused: No
- Material: PP
- Pitch: 19.5 mm
- Voltage Rating: 500 V



8680742 12

RS PRO 10-WAY NON-FUSED TERMINAL BLOCK, SCREW

Pack size: **10 x EA**

- Number of Ways: 10
- Wire Size: 2.5 mm²
- Termination Method: Screw
- Mounting Type: Panel Mount
- Fused: No
- Material: PC
- Voltage Rating: 450 V
- Maximum Operating Temperature: +85 °C



8680733 10

RS PRO 10-WAY NON-FUSED TERMINAL BLOCK, SCREW

Pack size: **5 x EA**

- Number of Ways: 10
- Wire Size: 10 mm²
- Termination Method: Screw
- Mounting Type: Panel Mount
- Fused: No
- Material: PC
- Voltage Rating: 450 V
- Maximum Operating Temperature: +85 °C



8680758 10

RS PRO 10-WAY NON-FUSED TERMINAL BLOCK, SCREW

Pack size: **10 x EA**

- Number of Ways: 10
- Wire Size: 1.5 mm²
- Termination Method: Screw
- Mounting Type: Panel Mount
- Fused: No
- Material: PC
- Voltage Rating: 450 V
- Maximum Operating Temperature: +85 °C



8680768 10

RS PRO 10-WAY NON-FUSED TERMINAL BLOCK, SCREW

Pack size: **10 x EA**

- Number of Ways: 10
- Wire Size: 4 mm²
- Termination Method: Screw
- Mounting Type: Panel Mount
- Fused: No
- Material: PC
- Voltage Rating: 450 V
- Maximum Operating Temperature: +85 °C



8680796 10

RS PRO 3-WAY NON-FUSED TERMINAL BLOCK, SCREW TERMINALS, 2.5 MM²,

Pack size: **10 x EA**

- Number of Ways: 3
- Wire Size: 2.5 mm²
- Termination Method: Screw
- Mounting Type: Panel Mount
- Fused: No
- Material: Polyamide
- Voltage Rating: 400 V
- Maximum Operating Temperature: +100 °C



8680777 3

RS PRO 12-WAY NON-FUSED TERMINAL BLOCK, SCREW

Pack size: **5 x EA**

- Number of Ways: 12
- Wire Size: 16 mm²
- Termination Method: Screw
- Mounting Type: Panel Mount
- Fused: No
- Material: PP
- Pitch: 15 mm
- Voltage Rating: 450 V



8680803 12

TERM.BLOCK 1WAY 2.5-TR

Pack size: **50 x EA**

- Number of Ways: 1
- Wire Size: 2.5 mm²
- Termination Method: Screw
- Fused: No
- Material: PC
- Voltage Rating: 450 V
- Maximum Operating Temperature: +85 °C
- Enclosed: Yes



8680809 1

RS PRO 3-WAY NON-FUSED TERMINAL BLOCK, SCREW TERMINALS, 2.5 MM²,

Pack size: **10 x EA**

- Number of Ways: 3
- Wire Size: 2.5 mm²
- Termination Method: Screw
- Mounting Type: Panel Mount
- Fused: No
- Material: Polyamide
- Pitch: 21.5 mm
- Voltage Rating: 450 V



8680812 3

RS PRO 12-WAY DISCONNECT TERMINAL BLOCK, 76A, SCREW

Pack size: **1 x EA**

- Number of Ways: 12
- Current Rating: 76 A
- Wire Size: 16 mm²
- Termination Method: Screw
- Mounting Type: Surface Mount
- Fused: No
- Material: Glass Fibre Reinforced, Polyamide
- Voltage Rating: 450 V



9106788 12

RS PRO 12-WAY NON-FUSED TERMINAL BLOCK, SCREW

Pack size: **5 x EA**

- Number of Ways: 12
- Wire Size: 4 mm²
- Termination Method: Screw
- Mounting Type: Panel Mount
- Fused: No
- Material: Polyamide
- Pitch: 12 mm
- Voltage Rating: 400 V



8680815 12

RS PRO TERMINAL BLOCK COVER FOR USE WITH TERMINAL BLOCKS

Pack size: **4 x EA**

- Accessory Type: Terminal Block Cover
- For Use With: Terminal Block



4649794 Terminal Block

RS PRO END COVER FOR USE WITH FOR USE WITH TERMINAL BLOCKS

Pack size: **5 x EA**

- Accessory Type: End Cover
- For Use With: Terminal Block
- Series: Polyamide



425437 End Cover

NYLON TERMINAL BLOCK HOUSING IP44, CABLE MOUNT

Pack size: **5 x EA**

- IP Rating: IP44
- Series: TH110
- Material: Nylon
- Mounting Type: Cable Mount
- Number of Contacts: 3
- Maximum Operating Temperature: 125.0 °C
- Minimum Operating Temperature: -20.0 °C



4561060 IP44

RS PRO SHROUD KIT FOR USE WITH TERMINAL BLOCKS

Pack size: **5 x EA**

- Accessory Type: Shroud Kit
- For Use With: Terminal Block



4649801 Shroud Kit

NYLON TERMINAL BLOCK HOUSING IP67, CABLE MOUNT

Pack size: **1 x EA**

- IP Rating: IP67
- Series: TH200
- Material: Nylon
- Mounting Type: Cable Mount
- Number of Contacts: 3
- Maximum Operating Temperature: 125.0 °C
- Minimum Operating Temperature: -20.0 °C



4924641 IP67

NYLON TERMINAL BLOCK HOUSING IP68, CABLE MOUNT

Pack size: **1 x EA**

- IP Rating: IP68
- Series: TH387
- Material: Nylon
- Mounting Type: Cable Mount
- Number of Contacts: 4
- Maximum Operating Temperature: 125.0 °C
- Minimum Operating Temperature: -20.0 °C



9106781 IP68

NYLON TERMINAL BLOCK HOUSING IP68, CABLE MOUNT

Pack size: **1 x EA**

- IP Rating: IP68
- Series: TH387
- Material: Nylon
- Mounting Type: Cable Mount
- Number of Contacts: 4
- Maximum Operating Temperature: 125.0 °C
- Minimum Operating Temperature: -20.0 °C



9106772 IP68

RS PRO MAGNETIC PICKUP

Pack size: **1 x EA**

- Supply Voltage: 10 V
- Overall Height: 22 mm
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +100 °C



304166 10 V

RS PRO SPLIT CORE CURRENT TRANSDUCER, 5A INPUT

Pack size: **1 x EA**

- Transformer Type: Split Core
- Input Current: 5 A
- Overall Height: 51 mm
- Overall Depth: 26.5 mm
- Minimum Temperature: -20 °C
- Maximum Temperature: +65 °C
- Series: CVH5R0VP01
- Mounting Type: Panel Mount



2100645 Split Core

RS PRO SPLIT CORE CURRENT TRANSDUCER, 50A INPUT, 24 V

Pack size: **1 x EA**

- Transformer Type: Split Core
- Supply Voltage: 24 V
- Input Current: 50 A
- Overall Height: 51 mm
- Overall Depth: 26.5 mm
- Minimum Temperature: -25 °C
- Maximum Temperature: +65 °C
- Series: CVH500IP01



2100642 Split Core

RS PRO INCREMENTAL ENCODER, 1024 PPR, HTL INVERTED SIGNAL,

Pack size: **1 x EA**

- Encoder Technology: Incremental
- Pulses Per Revolution: 1024
- Maximum Revolutions: 10000 rpm
- Output Signal Type: HTL Inverted
- Shaft Type: Solid
- Supply Voltage: 5 → 30 V dc
- Shaft Diameter: 6 mm
- Resolution: 2500 ppr



7951028 Incremental

RS PRO MAGNETIC PICKUP

Pack size: **1 x EA**

- Supply Voltage: 5 → 15 V dc
- Overall Height: 28.6 mm
- Minimum Operating Temperature: -25 °C
- Maximum Operating Temperature: +85 °C



304172 5 → 15 V dc

RS PRO INCREMENTAL ENCODER, 50 PPR, HTL INVERTED SIGNAL, SOLID

Pack size: **1 x EA**

- Encoder Technology: Incremental
- Pulses Per Revolution: 50
- Maximum Revolutions: 8000 rpm
- Output Signal Type: HTL Inverted
- Shaft Type: Solid
- Supply Voltage: 5 → 30 V dc
- Shaft Diameter: 10 mm
- Resolution: 50 ppr



7951031 Incremental

RS PRO INCREMENTAL ENCODER, 200 PPR, HTL INVERTED SIGNAL, SOLID

Pack size: **1 x EA**

- Encoder Technology: Incremental
- Pulses Per Revolution: 200
- Maximum Revolutions: 8000 rpm
- Output Signal Type: HTL Inverted
- Shaft Type: Solid
- Supply Voltage: 5 → 30 V dc
- Shaft Diameter: 10 mm
- Resolution: 2500 ppr



7951040 Incremental

RS PRO TRANSDUCER LINEAR TRANSDUCER

Pack size: **1 x EA**

- Encoder Technology: Transducer
- Stroke: 25 mm
- IP Rating: IP65
- Overall Height: 8.6 mm
- Overall Width: 28.1 mm
- Overall Depth: 52 mm
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



9094196 Transducer

RS PRO INCREMENTAL ENCODER, 4096 PPR, HTL INVERTED SIGNAL,

Pack size: **1 x EA**

- Encoder Technology: Incremental
- Pulses Per Revolution: 4096
- Maximum Revolutions: 6000 rpm
- Output Signal Type: HTL Inverted
- Shaft Type: Hollow
- Supply Voltage: 10 → 30 V dc
- Shaft Diameter: 12 mm
- Resolution: 5000 ppr



7951141 Incremental

RS PRO TRANSDUCER LINEAR TRANSDUCER

Pack size: **1 x EA**

- Encoder Technology: Transducer
- Stroke: 100 mm
- IP Rating: IP65
- Overall Height: 8.6 mm
- Overall Width: 28.1 mm
- Overall Depth: 127 mm
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



9094203 Transducer

RS PRO TRANSDUCER LINEAR TRANSDUCER

Pack size: **1 x EA**

- Encoder Technology: Transducer
- Stroke: 50 mm
- IP Rating: IP65
- Overall Height: 8.6 mm
- Overall Width: 28.1 mm
- Overall Depth: 77 mm
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



9094209 Transducer

RS PRO TRANSDUCER LINEAR TRANSDUCER

Pack size: **1 x EA**

- Encoder Technology: Transducer
- Stroke: 200 mm
- IP Rating: IP65
- Overall Height: 8.6 mm
- Overall Width: 28.1 mm
- Overall Depth: 227 mm
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +85 °C



9094212 Transducer

RS PRO WHITE DIN RAIL TERMINAL BLOCK, SINGLE LEVEL, 0.2 → 2.5MM²,

Pack size: **10 x EA**

- Colour: White
- Number of Levels: Single
- Cable CSA: 0.2 → 2.5 mm²
- Current Rating: 24 A
- Voltage Rating: 800 V
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +105 °C



501613 White

RS PRO BROWN FEED THROUGH TERMINAL BLOCK, SINGLE LEVEL, 0.2

Pack size: **10 x EA**

- Colour: Brown
- Number of Levels: Single
- Cable CSA: 0.2 → 2.5 mm²
- Current Rating: 24 A
- Voltage Rating: 800 V
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +105 °C



501635 Brown

RS PRO GREY FEED THROUGH TERMINAL BLOCK, SINGLE LEVEL, 0.2

Pack size: **10 x EA**

- Colour: Grey
- Number of Levels: Single
- Cable CSA: 0.2 → 2.5 mm²
- Current Rating: 24 A
- Voltage Rating: 800 V
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +105 °C



501639 Grey

RS PRO YELLOW DIN RAIL TERMINAL BLOCK, SINGLE LEVEL, 0.2 → 2.5MM²,

Pack size: **10 x EA**

- Colour: Yellow
- Number of Levels: Single
- Cable CSA: 0.2 → 2.5 mm²
- Current Rating: 24 A
- Voltage Rating: 800 V
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +105 °C



501641 Yellow

RS PRO BLACK DIN RAIL TERMINAL BLOCK, SINGLE LEVEL, 0.2 → 4MM²,

Pack size: **10 x EA**

- Colour: Black
- Number of Levels: Single
- Cable CSA: 0.2 → 4 mm²
- Current Rating: 32 A
- Voltage Rating: 800 V
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +105 °C



501645 Black

RS PRO ORANGE DIN RAIL TERMINAL BLOCK, SINGLE LEVEL, 0.2 → 4MM²,

Pack size: **10 x EA**

- Colour: Orange
- Number of Levels: Single
- Cable CSA: 0.2 → 4 mm²
- Current Rating: 32 A
- Voltage Rating: 800 V
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +105 °C



501651 Orange

RS PRO YELLOW DIN RAIL TERMINAL BLOCK, 0.2 → 4MM²

Pack size: **10 x EA**

- Colour: Yellow
- Cable CSA: 0.2 → 4 mm²
- Current Rating: 32 A



501663 Yellow

RS PRO RED DIN RAIL TERMINAL BLOCK, SINGLE LEVEL, 0.2 → 4MM²,

Pack size: **10 x EA**

- Colour: Red
- Number of Levels: Single
- Cable CSA: 0.2 → 4 mm²
- Current Rating: 32 A
- Voltage Rating: 800 V
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +105 °C



501673 Red

RS PRO BROWN DIN RAIL TERMINAL BLOCK, 16 → 50MM², 1 KV

Pack size: **1 x EA**

- Colour: Brown
- Series: RK
- American Wire Gauge: 6 → 0 AWG
- Cable CSA: 16 → 50 mm²
- Voltage Rating: 1 kV
- Current Rating: 150 A



501714 Brown

RS PRO BROWN DIN RAIL TERMINAL BLOCK, SINGLE LEVEL, 0.2 → 4MM²,

Pack size: **10 x EA**

- Colour: Brown
- Number of Levels: Single
- Cable CSA: 0.2 → 4 mm²
- Current Rating: 32 A
- Voltage Rating: 800 V
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +105 °C



501720 Brown

RS PRO BROWN DIN RAIL TERMINAL BLOCK, 2.5 → 35MM², 800 V

Pack size: **10 x EA**

- Colour: Brown
- Series: RK
- American Wire Gauge: 12 → 2 AWG
- Cable CSA: 2.5 → 35 mm²
- Voltage Rating: 800 V
- Current Rating: 125 A



501724 Brown

RS PRO BROWN DIN RAIL TERMINAL BLOCK, 35 → 95MM², 1 KV

Pack size: **1 x EA**

- Colour: Brown
- Series: RK
- American Wire Gauge: 2 → 0000 AWG
- Cable CSA: 35 → 95 mm²
- Voltage Rating: 1 kV
- Current Rating: 232 A



501718 Brown

RS PRO BROWN DIN RAIL TERMINAL BLOCK, 2.5 → 16MM², 800 V

Pack size: **10 x EA**

- Colour: Brown
- American Wire Gauge: 10 → 4 AWG
- Series: RK
- Termination Method: Screw
- Cable CSA: 2.5 → 16 mm²
- Voltage Rating: 800 V
- Current Rating: 85 A



501770 Brown

RS PRO ORANGE DIN RAIL TERMINAL BLOCK, SINGLE LEVEL, 0.2 → 2.5MM²,

Pack size: **10 x EA**

- Colour: Orange
- Number of Levels: Single
- Cable CSA: 0.2 → 2.5 mm²
- Current Rating: 24 A
- Voltage Rating: 800 V
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +105 °C



501730 Orange

RS PRO BLUE DIN RAIL TERMINAL BLOCK, 0.2 → 10MM², 800 V

Pack size: **10 x EA**

- Colour: Blue
- Series: RK
- American Wire Gauge: 22 → 6 AWG
- Cable CSA: 0.2 → 10 mm²
- Voltage Rating: 800 V
- Current Rating: 65 A



501819 Blue

RS PRO GREY DIN RAIL TERMINAL BLOCK, SINGLE LEVEL, 0.2 → 4MM²,

Pack size: **10 x EA**

- Colour: Grey
- Number of Levels: Single
- Cable CSA: 0.2 → 4 mm²
- Current Rating: 32 A
- Voltage Rating: 800 V
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +105 °C



501803 Grey

RS PRO RED DIN RAIL TERMINAL BLOCK, SINGLE LEVEL, 0.2 → 2.5MM²,

Pack size: **10 x EA**

- Colour: Red
- Number of Levels: Single
- Cable CSA: 0.2 → 2.5 mm²
- Current Rating: 24 A
- Voltage Rating: 800 V
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +105 °C



501821 Red

RS PRO BLUE DIN RAIL TERMINAL BLOCK, 0.2 → 4MM², 500 V

Pack size: **10 x EA**

- Colour: Blue
- Series: RK
- American Wire Gauge: 22 → 10 AWG
- Cable CSA: 0.2 → 4 mm²
- Voltage Rating: 500 V
- Current Rating: 40 A
- Pitch: 6 mm



501831 Blue

RS PRO BLACK FUSED DIN RAIL TERMINAL, 0.5 → 10MM², 400 V

Pack size: **10 x EA**

- Colour: Black
- Series: SK
- Termination Method: Screw
- Cable CSA: 0.5 → 10 mm²
- Fused: Yes
- Voltage Rating: 400 V
- Current Rating: 10 A
- Pitch: 12.2 mm



501837 Black

RS PRO BEIGE FEED THROUGH TERMINAL BLOCK, 500 V

Pack size: **1 x EA**

- Colour: Beige
- American Wire Gauge: 22 → 12 AWG
- Series: STKD 1
- Termination Method: Screw
- Voltage Rating: 500 V
- Current Rating: 6.3 A



501843 Beige

RS PRO BLACK FUSED DIN RAIL TERMINAL, 0.5 → 10MM², 400 V

Pack size: **10 x EA**

- Colour: Black
- American Wire Gauge: 22 → 8 AWG
- Series: SK
- Termination Method: Screw
- Cable CSA: 0.5 → 10 mm²
- Fused: Yes
- Voltage Rating: 400 V
- Current Rating: 10 A




501875 Black

CONNECTOR, TERMINAL, DIN RAIL, THREE TIER, 3 IN 1 OUT,

Pack size: **1 x EA**

- Colour: Red
- Number of Levels: Triple
- Series: IK
- Cable CSA: 0.2 → 2.5 mm²
- Current Rating: 24 A
- Voltage Rating: 24 V dc
- Pitch: 5 mm



501893 Red

RS PRO BEIGE STUD TERMINAL, SINGLE LEVEL, 1 KV

Pack size: **1 x EA**

- Colour: Beige
- Number of Levels: Single
- American Wire Gauge: 10 AWG
- Series: HSK
- Current Rating: 269 A
- Voltage Rating: 1 kV
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +120 °C



501910 Beige

RS PRO WHITE DIN RAIL TERMINAL BLOCK, SINGLE LEVEL, 0.2 → 4MM²,

Pack size: **10 x EA**

- Colour: White
- Number of Levels: Single
- Cable CSA: 0.2 → 4 mm²
- Current Rating: 32 A
- Voltage Rating: 800 V
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +105 °C



501932 White

RS PRO BLACK DIN RAIL TERMINAL BLOCK, SINGLE LEVEL, 0.2 → 2.5MM²,

Pack size: **10 x EA**

- Colour: Black
- Number of Levels: Single
- Cable CSA: 0.2 → 2.5 mm²
- Current Rating: 24 A
- Voltage Rating: 800 V
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +105 °C



501976 Black

RS PRO BEIGE STUD TERMINAL, SINGLE LEVEL, 1 KV

Pack size: **1 x EA**

- Colour: Beige
- Number of Levels: Single
- American Wire Gauge: 14 → 2 AWG
- Series: HSK
- Current Rating: 125 A
- Voltage Rating: 1 kV
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +120 °C



501982 Beige

RS PRO STUD TERMINAL, 1 KV

Pack size: **1 x EA**

- Series: HSK
- American Wire Gauge: 14 → 0 AWG
- Voltage Rating: 1 kV
- Current Rating: 150 A



501988 HSK

RS PRO BROWN DIN RAIL TERMINAL BLOCK, DOUBLE LEVEL, 0.2 → 2.5MM²,

Pack size: **5 x EA**

- Colour: Brown
- Number of Levels: Double
- American Wire Gauge: 22 → 12 AWG
- Series: RKD
- Termination Method: Screw
- Cable CSA: 0.2 → 2.5 mm²
- Current Rating: 24 A
- Voltage Rating: 500 V



501994 Brown

RS PRO BROWN DIN RAIL TERMINAL BLOCK, DOUBLE LEVEL, 0.2 → 4MM²,

Pack size: **5 x EA**

- Colour: Brown
- Number of Levels: Double
- American Wire Gauge: 22 → 10 AWG
- Series: RKD
- Termination Method: Screw
- Cable CSA: 0.2 → 4 mm²
- Voltage Rating: 500 V
- Current Rating: 32 A



501998 Brown

RS PRO BLUE DIN RAIL TERMINAL BLOCK, 0.2 → 2.5MM², 800 V

Pack size: **10 x EA**

- Colour: Blue
- American Wire Gauge: 22 → 12 AWG
- Series: RK
- Termination Method: Screw
- Cable CSA: 0.2 → 2.5 mm²
- Current Rating: 24 A
- Voltage Rating: 800 V
- Minimum Operating Temperature: -40 °C



802783 Blue

RS PRO BLUE DIN RAIL TERMINAL BLOCK, 0.2 → 4MM², 500 V

Pack size: **10 x EA**

- Colour: Blue
- American Wire Gauge: 22 → 10 AWG
- Series: RK
- Termination Method: Screw
- Cable CSA: 0.2 → 4 mm²
- Current Rating: 40 A
- Voltage Rating: 500 V
- Minimum Operating Temperature: -40 °C



815644 Blue

RS PRO BEIGE DIN RAIL TERMINAL BLOCK, 0.2 → 4MM², 800 V

Pack size: **10 x EA**

- Colour: Beige
- American Wire Gauge: 22 → 11 AWG
- Series: RK
- Termination Method: Screw
- Cable CSA: 0.2 → 4 mm²
- Current Rating: 40 A
- Voltage Rating: 800 V
- Minimum Operating Temperature: -40 °C



815666 Beige

RS PRO BLUE FEED THROUGH TERMINAL BLOCK, 0.2 → 4MM², 800 V

Pack size: **10 x EA**

- Colour: Blue
- American Wire Gauge: 22 → 11 AWG
- Series: RK
- Termination Method: Screw
- Cable CSA: 0.2 → 4 mm²
- Current Rating: 40 A
- Voltage Rating: 800 V
- Minimum Operating Temperature: -40 °C



815672 Blue

RS PRO BROWN DIN RAIL TERMINAL BLOCK, 0.2 → 10MM², 800 V

Pack size: **10 x EA**

- Colour: Brown
- American Wire Gauge: 22 → 8 AWG
- Series: RK
- Termination Method: Screw
- Cable CSA: 0.2 → 10 mm²
- Current Rating: 65 A
- Voltage Rating: 800 V
- Minimum Operating Temperature: -40 °C



815694 Brown

RS PRO BROWN DOUBLE LEVEL TERMINAL BLOCK, DOUBLE LEVEL, 0.5

Pack size: **10 x EA**

- Colour: Brown
- Number of Levels: Double
- American Wire Gauge: 22 → 12 AWG
- Series: RKD
- Termination Method: Screw
- Cable CSA: 0.5 → 4 mm²
- Current Rating: 32 A
- Voltage Rating: 500 V



815701 Brown

RS PRO BROWN DIN RAIL TERMINAL BLOCK, 0.5 → 5MM², 600 V

Pack size: **5 x EA**

- Colour: Brown
- American Wire Gauge: 22 → 12 AWG
- Series: TRK
- Termination Method: Screw
- Cable CSA: 0.5 → 5 mm²
- Current Rating: 15 A
- Voltage Rating: 600 V
- Minimum Operating Temperature: -40 °C



815723 Brown

RS PRO GREY FEED THROUGH TERMINAL BLOCK, SINGLE LEVEL,

Pack size: **5 x EA**

- Colour: Grey
- Number of Levels: Single
- American Wire Gauge: 22 → 8 AWG
- Series: WK
- Termination Method: Screw
- Cable CSA: 6 mm²
- Voltage Rating: 1 kV
- Current Rating: 41 A



3846972 Grey

RS PRO GREY FEED THROUGH TERMINAL BLOCK, SINGLE LEVEL,

Pack size: **5 x EA**

- Colour: Grey
- Number of Levels: Single
- American Wire Gauge: 16 → 6 AWG
- Series: WKN
- Termination Method: Screw
- Cable CSA: 10 mm²
- Voltage Rating: 1 kV
- Current Rating: 57 A



3846988 Grey

RS PRO GREY FEED THROUGH TERMINAL BLOCK, 12 → 4 AWG,

Pack size: **5 x EA**

- Colour: Grey
- Wire Size: 12 → 4 AWG
- Number of Levels: Single
- Series: WKN
- Termination Method: Screw
- Cable CSA: 16 mm²
- Voltage Rating: 1 kV
- Current Rating: 57 A



3846994 Grey

RS PRO GREY FEED THROUGH TERMINAL BLOCK, 0.5 → 2.5MM², 300

Pack size: **1 x EA**

- Colour: Grey
- Series: WS
- Termination Method: Screw
- Cable CSA: 0.5 → 2.5 mm²
- Voltage Rating: 300 V
- Current Rating: 10 A



4709593 Grey

RS PRO BLUE FEED THROUGH TERMINAL BLOCK, SINGLE LEVEL,

Pack size: **10 x EA**

- Colour: Blue
- Number of Levels: Single
- American Wire Gauge: 22 → 12 AWG
- Series: SRK
- Termination Method: Screw
- Cable CSA: 2.5 mm²
- Voltage Rating: 1 kV
- Current Rating: 24 A



7622503 Blue

RS PRO BEIGE FEED THROUGH TERMINAL BLOCK, SINGLE LEVEL,

Pack size: **10 x EA**

- Colour: Beige
- Number of Levels: Single
- American Wire Gauge: 22 → 12 AWG
- Series: SRK
- Termination Method: Screw
- Cable CSA: 2.5 mm²
- Voltage Rating: 1 kV
- Current Rating: 24 A



7622509 Beige

RS PRO BEIGE DIN RAIL TERMINAL BLOCK, SINGLE LEVEL, 4MM², 1 KV

Pack size: **10 x EA**

- Colour: Beige
- Number of Levels: Single
- American Wire Gauge: 22 → 11 AWG
- Series: SRK
- Termination Method: Screw
- Cable CSA: 4 mm²
- Voltage Rating: 1 kV
- Current Rating: 40 A



7622512 Beige

RS PRO BLUE DIN RAIL TERMINAL BLOCK, DOUBLE LEVEL, 4MM², 1 KV

Pack size: **10 x EA**

- Colour: Blue
- Number of Levels: Double
- American Wire Gauge: 22 → 11 AWG
- Series: SRK
- Termination Method: Screw
- Cable CSA: 4 mm²
- Voltage Rating: 1 kV
- Current Rating: 40 A



7622515 Blue

RS PRO BEIGE DIN RAIL TERMINAL BLOCK, DOUBLE LEVEL, 6MM², 1 KV

Pack size: **10 x EA**

- Colour: Beige
- Number of Levels: Double
- American Wire Gauge: 22 → 8 AWG
- Series: SRK
- Termination Method: Screw
- Cable CSA: 6 mm²
- Voltage Rating: 1 kV
- Current Rating: 65 A



7622519 Beige

RS PRO BEIGE DIN RAIL TERMINAL BLOCK, DOUBLE LEVEL, 10MM², 1 KV

Pack size: **10 x EA**

- Colour: Beige
- Number of Levels: Double
- American Wire Gauge: 10 → 6 AWG
- Series: SRK
- Termination Method: Screw
- Cable CSA: 10 mm²
- Voltage Rating: 1 kV
- Current Rating: 85 A



7622521 Beige

RS PRO BLUE DIN RAIL TERMINAL BLOCK, DOUBLE LEVEL, 10MM², 1 KV

Pack size: **10 x EA**

- Colour: Blue
- Number of Levels: Double
- American Wire Gauge: 10 → 6 AWG
- Series: SRK
- Termination Method: Screw
- Cable CSA: 10 mm²
- Voltage Rating: 1 kV
- Current Rating: 85 A



7622525 Blue

RS PRO BLUE DIN RAIL TERMINAL BLOCK, DOUBLE LEVEL, 6MM², 1 KV

Pack size: **10 x EA**

- Colour: Blue
- Number of Levels: Double
- American Wire Gauge: 22 → 8 AWG
- Series: SRK
- Termination Method: Screw
- Cable CSA: 6 mm²
- Voltage Rating: 1 kV
- Current Rating: 65 A



7622528 Blue

RS PRO GREEN/YELLOW EARTH TERMINAL BLOCK, SINGLE LEVEL,

Pack size: **10 x EA**

- Colour: Green/Yellow
- Number of Levels: Single
- American Wire Gauge: 22 → 12 AWG
- Series: SSL
- Termination Method: Screw
- Cable CSA: 2.5 mm²
- Pitch: 5.1 mm
- Minimum Operating Temperature: -40 °C



7622534 Green/Yellow

RS PRO GREEN/YELLOW EARTH TERMINAL BLOCK, SINGLE LEVEL,

Pack size: **10 x EA**

- Colour: Green/Yellow
- Number of Levels: Single
- American Wire Gauge: 22 → 11 AWG
- Series: SSL
- Termination Method: Screw
- Cable CSA: 4 mm²
- Pitch: 6.1 mm
- Minimum Operating Temperature: -40 °C



7622537 Green/Yellow

RS PRO GREEN/YELLOW EARTH TERMINAL BLOCK, SINGLE LEVEL,

Pack size: **10 x EA**

- Colour: Green/Yellow
- Number of Levels: Single
- American Wire Gauge: 10 → 6 AWG
- Series: SSL
- Termination Method: Screw
- Cable CSA: 10 mm²
- Pitch: 10.1 mm
- Minimum Operating Temperature: -40 °C



7622540 Green/Yellow

RS PRO GREY DIN RAIL TERMINAL BLOCK, SINGLE LEVEL, 2.5MM², 600 V

Pack size: **10 x EA**

- Colour: Grey
- Number of Levels: Single
- American Wire Gauge: 20 → 12 AWG
- Series: ZRK
- Termination Method: Spring Clamp
- Cable CSA: 2.5 mm²
- Current Rating: 27 A
- Voltage Rating: 600 V



7637404 Grey

RS PRO BLUE DIN RAIL TERMINAL BLOCK, DOUBLE LEVEL, 2.5MM², 600

Pack size: **10 x EA**

- Colour: Blue
- Number of Levels: Double
- American Wire Gauge: 20 → 12 AWG
- Series: ZRK
- Termination Method: Spring Clamp
- Cable CSA: 2.5 mm²
- Current Rating: 27 A
- Voltage Rating: 600 V



7637413 Blue

RS PRO BLUE DIN RAIL TERMINAL BLOCK, DOUBLE LEVEL, 2.5MM², 600

Pack size: **10 x EA**

- Colour: Blue
- Number of Levels: Double
- American Wire Gauge: 20 → 12 AWG
- Series: ZRK
- Termination Method: Spring Clamp
- Cable CSA: 2.5 mm²
- Current Rating: 27 A
- Voltage Rating: 600 V



7637422 Blue

RS PRO GREEN/YELLOW EARTH TERMINAL BLOCK, SINGLE LEVEL,

Pack size: **10 x EA**

- Colour: Green/Yellow
- Number of Levels: Single
- American Wire Gauge: 20 → 12 AWG
- Series: ZSL
- Termination Method: Spring Clamp
- Cable CSA: 2.5 mm²
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +120 °C



7637426 Green/Yellow

RS PRO GREY DIN RAIL TERMINAL BLOCK, DOUBLE LEVEL, 2.5MM², 600

Pack size: **10 x EA**

- Colour: Grey
- Number of Levels: Double
- American Wire Gauge: 20 → 12 AWG
- Series: ZRK
- Termination Method: Spring Clamp
- Cable CSA: 2.5 mm²
- Current Rating: 27 A
- Voltage Rating: 600 V



7637429 Grey

RS PRO GREY DOUBLE LEVEL TERMINAL BLOCK, DOUBLE LEVEL,

Pack size: **10 x EA**

- Colour: Grey
- Number of Levels: Double
- American Wire Gauge: 20 → 12 AWG
- Series: ZRKD
- Termination Method: Spring Clamp
- Cable CSA: 2.5 mm²
- Current Rating: 24 A
- Voltage Rating: 500 V



7637438 Grey

RS PRO GREY MULTI LEVEL TERMINAL BLOCK, TRIPLE LEVEL, 2.5MM², 500 V

Pack size: **10 x EA**

- Colour: Grey
- Number of Levels: Triple
- American Wire Gauge: 20 → 12 AWG
- Series: ZIKD
- Termination Method: Spring Clamp
- Cable CSA: 2.5 mm²
- Current Rating: 24 A
- Voltage Rating: 500 V



7637444 Grey

RS PRO GREY DIN RAIL TERMINAL BLOCK, DOUBLE LEVEL, 4MM², 600 V

Pack size: **10 x EA**

- Colour: Grey
- Number of Levels: Double
- American Wire Gauge: 16 → 10 AWG
- Series: ZRK
- Termination Method: Spring Clamp
- Cable CSA: 4 mm²
- Current Rating: 35 A
- Voltage Rating: 600 V



7637460 Grey

RS PRO GREEN/YELLOW EARTH TERMINAL BLOCK, SINGLE LEVEL,

Pack size: **10 x EA**

- Colour: Green/Yellow
- Number of Levels: Single
- American Wire Gauge: 20 → 10 AWG
- Series: ZSL
- Termination Method: Spring Clamp
- Cable CSA: 4 mm²
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +120 °C



7637472 Green/Yellow

RS PRO GREY DIN RAIL TERMINAL BLOCK, DOUBLE LEVEL, 4MM², 600 V

Pack size: **10 x EA**

- Colour: Grey
- Number of Levels: Double
- American Wire Gauge: 20 → 10 AWG
- Series: ZRK
- Termination Method: Spring Clamp
- Cable CSA: 4 mm²
- Current Rating: 35 A
- Voltage Rating: 600 V



7637485 Grey

RS PRO GREEN/YELLOW EARTH TERMINAL BLOCK, SINGLE LEVEL,

Pack size: **10 x EA**

- Colour: Green/Yellow
- Number of Levels: Single
- American Wire Gauge: 22 → 8 AWG
- Series: ZSL
- Termination Method: Spring Clamp
- Cable CSA: 6 mm²
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +120 °C



7637514 Green/Yellow

RS PRO BEIGE FEED THROUGH TERMINAL BLOCK, SINGLE LEVEL, 1 KV

Pack size: **5 x EA**

- Colour: Beige
- Number of Levels: Single
- American Wire Gauge: 16 → 4 AWG
- Series: 17124.2
- Termination Method: Screw
- Current Rating: 101 (IEC) A, 85 (CSA) A, 85 (UL) A
- Voltage Rating: 1 kV
- Minimum Operating Temperature: -40 °C



8724688 Beige

RS PRO GREEN, YELLOW EARTH TERMINAL BLOCK, SINGLE LEVEL

Pack size: **1 x EA**

- Colour: Green, Yellow
- Number of Levels: Single
- American Wire Gauge: 16 → 4 AWG
- Series: 17130.2
- Termination Method: Screw
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +120 °C



8724690 Green, Yellow

RS PRO BEIGE FEED THROUGH TERMINAL BLOCK, SINGLE LEVEL, 1 KV

Pack size: **1 x EA**

- Colour: Beige
- Number of Levels: Single
- American Wire Gauge: 16 → 1/0 AWG
- Series: 17140.2
- Termination Method: Screw
- Current Rating: 150 (CSA) A, 150 (IEC) A, 150 (UL) A
- Voltage Rating: 1 kV
- Minimum Operating Temperature: -40 °C



8724694 Beige

RS PRO BLUE FEED THROUGH TERMINAL BLOCK, SINGLE LEVEL, 1 KV

Pack size: **5 x EA**

- Colour: Blue
- Number of Levels: Single
- American Wire Gauge: 16 → 4 AWG
- Series: 17124.5
- Termination Method: Screw
- Current Rating: 101 (IEC) A, 85 (CSA) A, 85 (UL) A
- Voltage Rating: 1 kV
- Minimum Operating Temperature: -40 °C



8724697 Blue

RS PRO GREEN, YELLOW EARTH TERMINAL BLOCK, DOUBLE LEVEL

Pack size: **1 x EA**

- Colour: Green, Yellow
- Number of Levels: Double
- American Wire Gauge: 8 → 0 AWG
- Series: 17158.2
- Termination Method: Screw
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +120 °C



8724701 Green, Yellow

RS PRO GREEN, YELLOW EARTH TERMINAL BLOCK, SINGLE LEVEL

Pack size: **1 x EA**

- Colour: Green, Yellow
- Number of Levels: Single
- American Wire Gauge: 16 → 1/0 AWG
- Series: 17145.2
- Termination Method: Screw
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +120 °C



8724704 Green, Yellow

RS PRO BEIGE FEED THROUGH TERMINAL BLOCK, DOUBLE LEVEL, 1

Pack size: **1 x EA**

- Colour: Beige
- Number of Levels: Double
- American Wire Gauge: 4 → 0 AWG
- Series: 17165.2
- Termination Method: Screw
- Current Rating: 220 (CSA) A, 228 (UL) A, 290 (IEC) A
- Voltage Rating: 1 kV
- Minimum Operating Temperature: -40 °C



8724717 Beige

RS PRO GREEN, YELLOW EARTH TERMINAL BLOCK, DOUBLE LEVEL

Pack size: **1 x EA**

- Colour: Green, Yellow
- Number of Levels: Double
- American Wire Gauge: 30 → 12 AWG
- Series: 17182.2
- Termination Method: Screw
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +120 °C



8724791 Green, Yellow

RS PRO BEIGE STUD TERMINAL, DOUBLE LEVEL, 1 KV

Pack size: **1 x EA**

- Colour: Beige
- Number of Levels: Double
- American Wire Gauge: 14 → 2 AWG
- Series: 17170.2
- Termination Method: Bolt
- Current Rating: 115 (UL) A, 125 (IEC) A, 130 (CSA) A
- Voltage Rating: 1 kV
- Minimum Operating Temperature: -40 °C



8724824 Beige

RS PRO BLACK DISCONNECT TERMINAL BLOCK, SINGLE LEVEL, 600

Pack size: **1 x EA**

- Colour: Black
- Number of Levels: Single
- American Wire Gauge: 22 → 11 AWG
- Series: 17150.4
- Termination Method: Screw
- Current Rating: 10 (IEC) A, 16 (cUL) A, 16 (UL) A
- Voltage Rating: 600 V
- Minimum Operating Temperature: -40 °C



8724827 Black

RS PRO BEIGE STUD TERMINAL, DOUBLE LEVEL, 1 KV

Pack size: **1 x EA**

- Colour: Beige
- Number of Levels: Double
- American Wire Gauge: 10 AWG
- Series: 17024.2
- Termination Method: Bolt
- Current Rating: 353 (IEC) A, 360 (CSA) A, 380 (UL) A
- Voltage Rating: 1 kV
- Minimum Operating Temperature: -40 °C



8724830 Beige

RS PRO BEIGE STUD TERMINAL, DOUBLE LEVEL, 1 KV

Pack size: **1 x EA**

- Colour: Beige
- Number of Levels: Double
- American Wire Gauge: 14 → 0 AWG
- Series: 17035.2
- Termination Method: Bolt
- Current Rating: 170 (CSA) A, 175 (UL) A, 192 (IEC) A
- Voltage Rating: 1 kV
- Minimum Operating Temperature: -40 °C



8724833 Beige

RS PRO BEIGE STUD TERMINAL, DOUBLE LEVEL, 1 KV

Pack size: **1 x EA**

- Colour: Beige
- Number of Levels: Double
- American Wire Gauge: 10 AWG
- Series: 17023.2
- Termination Method: Bolt
- Current Rating: 269 (IEC) A, 310 (CSA) A, 310 (UL) A
- Voltage Rating: 1 kV
- Minimum Operating Temperature: -40 °C



8724836 Beige

RS PRO GREY FEED THROUGH TERMINAL BLOCK, SINGLE LEVEL, 800

Pack size: **10 x EA**

- Colour: Grey
- Number of Levels: Single
- American Wire Gauge: 22 → 12 AWG
- Series: 1296.2
- Termination Method: Screw
- Current Rating: 20 (cUL) A, 20 (UL) A, 24 (IEC) A
- Voltage Rating: 800 V
- Minimum Operating Temperature: -40 °C



8725603 Grey

RS PRO BEIGE DOUBLE LEVEL TERMINAL BLOCK, DOUBLE LEVEL, 500

Pack size: **5 x EA**

- Colour: Beige
- Number of Levels: Double
- American Wire Gauge: 22 → 14 AWG
- Series: 1206.2
- Termination Method: Screw
- Current Rating: 20 (cUL) A, 20 (UL) A, 24 (IEC) A
- Voltage Rating: 500 V
- Minimum Operating Temperature: -40 °C



8725609 Beige

RS PRO BEIGE FEED THROUGH TERMINAL BLOCK, SINGLE LEVEL, 500

Pack size: **5 x EA**

- Colour: Beige
- Number of Levels: Single
- American Wire Gauge: 22 → 10 AWG
- Series: 1015.2
- Termination Method: Screw
- Current Rating: 30 (UL) A, 32 (IEC) A, 40 (CSA) A
- Voltage Rating: 500 V
- Minimum Operating Temperature: -40 °C



8725612 Beige

RS PRO BEIGE DISCONNECT TERMINAL BLOCK, SINGLE LEVEL,

Pack size: **10 x EA**

- Colour: Beige
- Number of Levels: Single
- American Wire Gauge: 22 → 12 AWG
- Series: 2190.2
- Termination Method: Screw
- Cable CSA: 4 mm²
- Current Rating: 16 (UL) A, 6.3 (CSA) A, 6.3 (IEC) A
- Voltage Rating: 600 V



8725615 Beige

RS PRO BEIGE FEED THROUGH TERMINAL BLOCK, TRIPLE LEVEL, 300

Pack size: **5 x EA**

- Colour: Beige
- Number of Levels: Triple
- American Wire Gauge: 22 → 14 AWG
- Series: 2268.2
- Termination Method: Screw
- Current Rating: 20 (CSA) A, 20 (CSAus) A, 24 (IEC) A
- Voltage Rating: 300 V
- Minimum Operating Temperature: -40 °C



8725619 Beige

RS PRO GREEN, YELLOW EARTH TERMINAL BLOCK, SINGLE LEVEL

Pack size: **10 x EA**

- Colour: Green, Yellow
- Number of Levels: Single
- American Wire Gauge: 20 → 6 AWG
- Series: 1213.2
- Termination Method: Screw
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +105 °C



8725621 Green, Yellow

RS PRO BEIGE STUD TERMINAL, SINGLE LEVEL, 1 kV

Pack size: **10 x EA**

- Colour: Beige
- Number of Levels: Single
- American Wire Gauge: 14 → 2 AWG
- Series: 17001.2
- Termination Method: Bolt
- Current Rating: 115 (CSA) A, 115 (CSAus) A, 125 (IEC) A
- Voltage Rating: 1 kV
- Minimum Operating Temperature: -40 °C



8725625 Beige

RS PRO GREEN, YELLOW EARTH TERMINAL BLOCK, SINGLE LEVEL

Pack size: **10 x EA**

- Colour: Green, Yellow
- Number of Levels: Single
- American Wire Gauge: 22 → 12 AWG
- Series: 1056.2
- Termination Method: Screw
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +105 °C



8725628 Green, Yellow

RS PRO DOUBLE LEVEL TERMINAL BLOCK, DOUBLE LEVEL, 2.5MM², 800

Pack size: **5 x EA**

- Number of Levels: Double
- Series: CDK 2.5
- American Wire Gauge: 22 → 12 AWG
- Termination Method: Screw
- Cable CSA: 2.5 mm²
- Current Rating: 20 (UL/CSA) A, 24 (IEC) A
- Voltage Rating: 800 V



8787471 Double

RS PRO DOUBLE LEVEL TERMINAL BLOCK, DOUBLE LEVEL, 4MM², 800 V

Pack size: **10 x EA**

- Number of Levels: Double
- Series: CDK 4
- American Wire Gauge: 22 → 10 AWG
- Termination Method: Screw
- Cable CSA: 4 mm²
- Current Rating: 30 (UL/CSA) A, 32 (IEC) A
- Voltage Rating: 800 V



8787483 Double

RS PRO DOUBLE LEVEL TERMINAL BLOCK, DOUBLE LEVEL, 2.5MM², 800

Pack size: **10 x EA**

- Number of Levels: Double
- Series: CDK 2.5
- American Wire Gauge: 22 → 12 AWG
- Termination Method: Screw
- Cable CSA: 2.5 mm²
- Current Rating: 20 (UL/CSA) A, 24 (IEC) A
- Voltage Rating: 800 V



8787480 Double

RS PRO DIN RAIL TERMINAL BLOCK, SINGLE LEVEL, 2.5MM², 800 V

Pack size: **10 x EA**

- Number of Levels: Single
- Series: CDU 2.5
- American Wire Gauge: 22 → 10 AWG
- Termination Method: Screw
- Cable CSA: 2.5 mm²
- Current Rating: 24 A
- Voltage Rating: 800 V



8787487 Single

RS PRO DIN RAIL TERMINAL BLOCK, SINGLE LEVEL, 2.5MM², 400 V

Pack size: **10 x EA**

- Number of Levels: Single
- Series: CDU 2.5
- American Wire Gauge: 22 → 12 AWG
- Termination Method: Screw
- Cable CSA: 2.5 mm²
- Current Rating: 20 (UL/CSA) A, 24 (IEC) A
- Voltage Rating: 400 V



8787493 Single

RS PRO BLUE DIN RAIL TERMINAL BLOCK, SINGLE LEVEL, 2.5MM², 800 V

Pack size: **10 x EA**

- Colour: Blue
- Number of Levels: Single
- American Wire Gauge: 22 → 10 AWG
- Series: CDU 2.5
- Termination Method: Screw
- Cable CSA: 2.5 mm²
- Voltage Rating: 800 V
- Current Rating: 24 A



8787499 Blue

RS PRO DIN RAIL TERMINAL BLOCK, SINGLE LEVEL, 3.5MM², 1 kV

Pack size: **10 x EA**

- Number of Levels: Single
- Series: CDU 3.5
- American Wire Gauge: 10 → 2 AWG
- Termination Method: Screw
- Cable CSA: 3.5 mm²
- Current Rating: 114 (UL/CSA) A, 125 (IEC) A
- Voltage Rating: 1 kV



8787500 Single

RS PRO DIN RAIL TERMINAL BLOCK, SINGLE LEVEL, 2.5MM², 800 V

Pack size: **10 x EA**

- Number of Levels: Single
- Series: CDU 2.5
- American Wire Gauge: 28 → 12 AWG
- Termination Method: Screw
- Cable CSA: 2.5 mm²
- Current Rating: 20 (UL/CSA) A, 24 (IEC) A
- Voltage Rating: 800 V



8787503 Single

RS PRO DIN RAIL TERMINAL BLOCK, SINGLE LEVEL, 2.5MM², 800 V

Pack size: **10 x EA**

- Number of Levels: Single
- Series: CDU 2.5
- American Wire Gauge: 28 → 12 AWG
- Termination Method: Screw
- Cable CSA: 2.5 mm²
- Current Rating: 20 (UL/CSA) A, 24 (IEC) A
- Voltage Rating: 800 V



8787506 Single

RS PRO DIN RAIL TERMINAL BLOCK, SINGLE LEVEL, 4MM², 400 V

Pack size: **10 x EA**

- Number of Levels: Single
- Series: CDU 4
- American Wire Gauge: 22 → 10 AWG
- Termination Method: Screw
- Cable CSA: 4 mm²
- Current Rating: 30 A
- Voltage Rating: 400 V



8787512 Single

RS PRO DIN RAIL TERMINAL BLOCK, SINGLE LEVEL, 4MM², 800 V

Pack size: **10 x EA**

- Number of Levels: Single
- Series: CDU 4
- American Wire Gauge: 22 → 10 AWG
- Termination Method: Screw
- Cable CSA: 4 mm²
- Current Rating: 30 (UL/CSA) A, 32 (IEC) A
- Voltage Rating: 800 V



8787516 Single

RS PRO DIN RAIL TERMINAL BLOCK, SINGLE LEVEL, 4MM², 800 V

Pack size: **10 x EA**

- Number of Levels: Single
- Series: CDU 4
- American Wire Gauge: 22 → 8 AWG
- Termination Method: Screw
- Cable CSA: 4 mm²
- Current Rating: 32 (IEC) A, 35 (UL/CSA) A
- Voltage Rating: 800 V



8787519 Single

RS PRO BLACK DIN RAIL TERMINAL BLOCK, SINGLE LEVEL, 2.5MM², 800 V

Pack size: **10 x EA**

- Colour: Black
- Number of Levels: Single
- American Wire Gauge: 22 → 10 AWG
- Series: CDU 2.5
- Termination Method: Screw
- Cable CSA: 2.5 mm²
- Voltage Rating: 800 V
- Current Rating: 24 A



8787496 Black

RS PRO DIN RAIL TERMINAL BLOCK, SINGLE LEVEL, 4MM², 800 V

Pack size: **10 x EA**

- Number of Levels: Single
- Series: CDU 4
- American Wire Gauge: 22 → 10 AWG
- Termination Method: Screw
- Cable CSA: 4 mm²
- Current Rating: 30 (UL/CSA) A, 32 (IEC) A
- Voltage Rating: 800 V



8787525 Single

RS PRO DIN RAIL TERMINAL BLOCK, SINGLE LEVEL, 4MM², 800 V

Pack size: **10 x EA**

- Number of Levels: Single
- Series: CDU 4
- American Wire Gauge: 22 → 10 AWG
- Termination Method: Screw
- Cable CSA: 4 mm²
- Current Rating: 30 (UL/CSA) A, 32 (IEC) A
- Voltage Rating: 800 V



8787528 Single

RS PRO DIN RAIL TERMINAL BLOCK, SINGLE LEVEL, 4MM², 600 V

Pack size: **10 x EA**

- Number of Levels: Single
- Series: CDU 4
- American Wire Gauge: 22 → 8 AWG
- Termination Method: Screw
- Cable CSA: 4 mm²
- Current Rating: 32 (IEC) A, 35 (UL/CSA) A
- Voltage Rating: 600 V



8787531 Single

RS PRO DIN RAIL TERMINAL BLOCK, SINGLE LEVEL, 4MM², 800 V

Pack size: **10 x EA**

- Number of Levels: Single
- Series: CDU 4
- American Wire Gauge: 22 → 10 AWG
- Termination Method: Screw
- Cable CSA: 4 mm²
- Current Rating: 30 (UL/CSA) A, 32 (IEC) A
- Voltage Rating: 800 V



8787522 Single

RS PRO DIN RAIL TERMINAL BLOCK, SINGLE LEVEL, 6MM², 800 V

Pack size: **10 x EA**

- Number of Levels: Single
- Series: CDU 6
- American Wire Gauge: 20 → 8 AWG
- Termination Method: Screw
- Cable CSA: 6 mm²
- Current Rating: 41 (IEC) A, 50 (UL/CSA) A
- Voltage Rating: 800 V



8787534 Single

RS PRO DIN RAIL TERMINAL BLOCK, SINGLE LEVEL, 800 V

Pack size: **10 x EA**

- Number of Levels: Single
- Series: CDU 6
- American Wire Gauge: 26 → 8 AWG
- Termination Method: Screw
- Current Rating: 50 (UL/CSA) A, 57 (IEC) A
- Voltage Rating: 800 V



8787547 Single

RS PRO DIN RAIL TERMINAL BLOCK, SINGLE LEVEL, 6MM², 800 V

Pack size: **10 x EA**

- Number of Levels: Single
- Series: CDU 6
- American Wire Gauge: 26 → 8 AWG
- Termination Method: Screw
- Cable CSA: 6 mm²
- Current Rating: 50 (UL/CSA) A, 57 (IEC) A
- Voltage Rating: 800 V



8787538 Single

RS PRO DISCONNECT TERMINAL BLOCK, SINGLE LEVEL, 4MM², 800 V

Pack size: **5 x EA**

- Number of Levels: Single
- Series: CTR 4
- American Wire Gauge: 22 → 10 AWG
- Termination Method: Screw
- Cable CSA: 4 mm²
- Current Rating: 22 A
- Voltage Rating: 800 V



8787588 Single

RS PRO DISCONNECT TERMINAL BLOCK, SINGLE LEVEL, 2.5MM², 600 V

Pack size: **10 x EA**

- Number of Levels: Single
- Series: CTR 2.5
- American Wire Gauge: 22 → 12 AWG
- Termination Method: Screw
- Cable CSA: 2.5 mm²
- Current Rating: 12 (UL/CSA) A, 15 (IEC) A
- Voltage Rating: 600 V



8787584 Single

RS PRO GREY FUSED DIN RAIL TERMINAL, SINGLE LEVEL, 24 → 240 V

Pack size: **5 x EA**

- Colour: Grey
- Number of Levels: Single
- Series: ENYA
- Termination Method: Screw
- Fused: Yes
- Current Rating: 8 A
- Voltage Rating: 24 → 240 V ac/dc
- Minimum Operating Temperature: -25 °C



9064595 Grey

RS PRO DISCONNECT TERMINAL BLOCK, SINGLE LEVEL, 4MM², 400 V

Pack size: **5 x EA**

- Number of Levels: Single
- Series: CTR 4
- American Wire Gauge: 22 → 14 AWG
- Termination Method: Screw
- Cable CSA: 4 mm²
- Current Rating: 15 A
- Voltage Rating: 400 V



8787597 Single

RS PRO ORANGE DIN RAIL TERMINAL BLOCK, 2.5MM², 800 V

Pack size: **10 x EA**

- Colour: Orange
- American Wire Gauge: 22 → 10 AWG
- Termination Method: Screw
- Cable CSA: 2.5 mm²
- Voltage Rating: 800 V
- Current Rating: 24 A



9131207 Orange

RS PRO RED DIN RAIL TERMINAL BLOCK, 2.5MM², 800 V

Pack size: **1 x EA**

- Colour: Red
- American Wire Gauge: 22 → 10 AWG
- Termination Method: Screw
- Cable CSA: 2.5 mm²
- Voltage Rating: 800 V
- Current Rating: 24 A



9131201 Red

RS PRO BLUE DIN RAIL TERMINAL BLOCK, 4MM², 800 V

Pack size: **1 x EA**

- Colour: Blue
- American Wire Gauge: 22 → 8 AWG
- Termination Method: Screw
- Cable CSA: 4 mm²
- Voltage Rating: 800 V
- Current Rating: 32 (IEC) A, 35 (CSA) A, 35 (UL) A



9131210 Blue

RS PRO BEIGE DIN RAIL TERMINAL BLOCK, 10MM², 1 kV

Pack size: **10 x EA**

- Colour: Beige
- American Wire Gauge: 16 → 6 AWG
- Termination Method: Screw
- Cable CSA: 10 mm²
- Voltage Rating: 1 kV
- Current Rating: 57 (IEC) A, 65 (CSA) A, 65 (UL) A



9131213 Beige

RS PRO BLUE DIN RAIL TERMINAL BLOCK, 2.5MM², 800 V

Pack size: **10 x EA**

- Colour: Blue
- American Wire Gauge: 28 → 12 AWG
- Termination Method: Screw
- Cable CSA: 2.5 mm²
- Voltage Rating: 800 V
- Current Rating: 20 (CSA) A, 20 (UL) A, 24 (IEC) A



9131223 Blue

RS PRO BEIGE DIN RAIL TERMINAL BLOCK, 16MM², 1 KV

- Pack size: **10 x EA**
- Colour: Beige
 - American Wire Gauge: 14 → 4 AWG
 - Termination Method: Screw
 - Cable CSA: 16 mm²
 - Voltage Rating: 1 kV
 - Current Rating: 76 (IEC) A, 78 (CSA) A, 78 (UL) A



9131217 Beige

RS PRO DIN RAIL TERMINAL BLOCK, 2.5MM², 800 V

- Pack size: **1 x EA**
- American Wire Gauge: 22 → 10 AWG
 - Termination Method: Screw
 - Cable CSA: 2.5 mm²
 - Voltage Rating: 800 V
 - Current Rating: 24 A



9131229 22 → 10 AWG

RS PRO BEIGE DIN RAIL TERMINAL BLOCK, 6MM², 800 V

- Pack size: **5 x EA**
- Colour: Beige
 - American Wire Gauge: 20 → 8 AWG
 - Termination Method: Screw
 - Cable CSA: 6 mm²
 - Voltage Rating: 800 V
 - Current Rating: 41 (IEC) A, 50 (CSA) A, 50 (UL) A



9131226 Beige

RS PRO BEIGE DIN RAIL TERMINAL BLOCK, 2.5MM², 800 V

- Pack size: **5 x EA**
- Colour: Beige
 - American Wire Gauge: 24 → 6 AWG
 - Termination Method: Screw
 - Cable CSA: 2.5 mm²
 - Voltage Rating: 800 V
 - Current Rating: 65 (CSA) A, 65 (UL) A, 76 (IEC) A



9131232 Beige

RS PRO BEIGE DIN RAIL TERMINAL BLOCK, 2.5MM², 800 V

- Pack size: **10 x EA**
- Colour: Beige
 - American Wire Gauge: 28 → 12 AWG
 - Termination Method: Spring Clamp
 - Cable CSA: 2.5 mm²
 - Voltage Rating: 800 V
 - Current Rating: 20 (CSA) A, 20 (UL) A, 32 (IEC) A



9131235 Beige

RS PRO BRUSHED GEARED, 7.9 W, 6 → 15 V, 29 NCM, 210 RPM, 6MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 6 → 15 V
- DC Motor Type: Brushed Geared
- Power Rating: 7.9 W
- Output Speed: 210 rpm
- Shaft Diameter: 6 mm
- Maximum Output Torque: 3000 gcm
- Gearhead Type: Spur
- Current Rating: 990 mA



420568 6 → 15 V

RS PRO BRUSHED GEARED, 7.9 W, 6 → 15 V, 9 NCM, 617 RPM, 6MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 6 → 15 V dc
- DC Motor Type: Brushed Geared
- Power Rating: 7.9 W
- Output Speed: 617 rpm
- Shaft Diameter: 6 mm
- Maximum Output Torque: 915 gcm
- Gearhead Type: Spur
- Current Rating: 340 mA



420564 6 → 15 V dc

RS PRO BRUSHED GEARED, 19.8 W, 12 V, 59 NCM, 29 RPM, 6MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 12 V dc
- DC Motor Type: Brushed Geared
- Power Rating: 19.8 W
- Output Speed: 29 rpm
- Shaft Diameter: 6 mm
- Maximum Output Torque: 6000 gcm
- Gearhead Type: Spur
- Current Rating: 2.81 A



420586 12 V dc

RS PRO BRUSHED GEARED, 7.9 W, 6 → 15 V, 4 NCM, 1644 RPM, 6MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 6 → 15 V
- DC Motor Type: Brushed Geared
- Power Rating: 7.9 W
- Output Speed: 1644 rpm
- Shaft Diameter: 6 mm
- Maximum Output Torque: 381 gcm
- Gearhead Type: Spur
- Current Rating: 990 mA



420574 6 → 15 V

RS PRO BRUSHED GEARED, 19.35 W, 6 → 15 V, 59 NCM, 4 RPM, 6MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 6 → 15 V
- DC Motor Type: Brushed Geared
- Power Rating: 19.35 W
- Output Speed: 4 rpm
- Shaft Diameter: 6 mm
- Maximum Output Torque: 6000 gcm
- Gearhead Type: Spur
- Current Rating: 2.75 A



420570 6 → 15 V

RS PRO BRUSHED GEARED, 7.98 W, 12 V, 59 NCM, 116 RPM, 6MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 12 V dc
- DC Motor Type: Brushed Geared
- Power Rating: 7.98 W
- Output Speed: 116 rpm
- Shaft Diameter: 6 mm
- Maximum Output Torque: 6000 gcm
- Gearhead Type: Spur
- Current Rating: 990 mA



420596 12 V dc

RS PRO BRUSHED GEARED, 36.88 W, 12 V, 98 NCM, 9 RPM, 12MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 12 V dc
- DC Motor Type: Brushed Geared
- Power Rating: 36.88 W
- Output Speed: 9 rpm
- Shaft Diameter: 12 mm
- Maximum Output Torque: 100000 gcm
- Gearhead Type: Planetary
- Current Rating: 4.61 A



420615 12 V dc

RS PRO BRUSHED GEARED, 38.7 W, 12 V, 98 NCM, 43 RPM, 12MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 12 V dc
- DC Motor Type: Brushed Geared
- Power Rating: 38.7 W
- Output Speed: 43 rpm
- Shaft Diameter: 12 mm
- Maximum Output Torque: 100000 gcm
- Gearhead Type: Planetary
- Current Rating: 4.61 A



420609 12 V dc

RS PRO BRUSHED GEARED, 41.3 W, 12 V, 2.9 NM, 11 RPM, 8MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 12 V dc
- DC Motor Type: Brushed Geared
- Power Rating: 41.3 W
- Output Speed: 11 rpm
- Shaft Diameter: 8 mm
- Maximum Output Torque: 30000 gcm
- Gearhead Type: Planetary
- Current Rating: 5.5 A



420619 12 V dc

RS PRO BRUSHED GEARED, 38.7 W, 12 V, 95 NCM, 1085 RPM, 12MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 12 V dc
- DC Motor Type: Brushed Geared
- Power Rating: 38.7 W
- Output Speed: 1085 rpm
- Shaft Diameter: 12 mm
- Maximum Output Torque: 9734 gcm
- Gearhead Type: Planetary
- Current Rating: 4.61 A



420625 12 V dc

RS PRO BRUSHED GEARED, 41.3 W, 12 V, 2 NM, 55 RPM, 8MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 12 V dc
- DC Motor Type: Brushed Geared
- Power Rating: 41.3 W
- Output Speed: 55 rpm
- Shaft Diameter: 8 mm
- Maximum Output Torque: 20000 gcm
- Gearhead Type: Planetary
- Current Rating: 5.5 A



420621 12 V dc

RS PRO BRUSHED GEARED, 41.3 W, 12 V, 29 NCM, 1425 RPM, 8MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 12 V dc
- DC Motor Type: Brushed Geared
- Power Rating: 41.3 W
- Output Speed: 1425 rpm
- Shaft Diameter: 8 mm
- Maximum Output Torque: 3000 gcm
- Gearhead Type: Planetary
- Current Rating: 5.28 A



420631 12 V dc

RS PRO BRUSHED GEARED, 1.5 W, 12 V, 25 NCM, 29 RPM, 4MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 12 V dc
- DC Motor Type: Brushed Geared
- Power Rating: 1.5 W
- Output Speed: 29 rpm
- Shaft Diameter: 4 mm
- Maximum Output Torque: 2500 gcm
- Gearhead Type: Planetary
- Current Rating: 200 mA



420637 12 V dc

RS PRO BRUSHED GEARED, 1.31 W, 12 V, 15 NCM, 6 RPM, 4MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 12 V, 12 → 24 V dc
- DC Motor Type: Brushed Geared
- Power Rating: 1.31 W
- Output Speed: 6 rpm
- Shaft Diameter: 4 mm
- Maximum Output Torque: 1500 gcm
- Gearhead Type: Spur
- Current Rating: 190 mA



420647 12 V, 12 → 24 V dc

RS PRO BRUSHED GEARED, 19.8 W, 12 V, 20 NCM, 753 RPM, 6MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 12 V dc
- DC Motor Type: Brushed Geared
- Power Rating: 19.8 W
- Output Speed: 753 rpm
- Shaft Diameter: 6 mm
- Maximum Output Torque: 2000 gcm
- Gearhead Type: Spur
- Current Rating: 2.81 A



420665 12 V dc

RS PRO BRUSHED GEARED, 19.8 W, 12 V, 29 NCM, 256 RPM, 6MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 12 V dc
- DC Motor Type: Brushed Geared
- Power Rating: 19.8 W
- Output Speed: 256 rpm
- Shaft Diameter: 6 mm
- Maximum Output Torque: 3000 gcm
- Gearhead Type: Spur
- Current Rating: 2.81 A



420669 12 V dc

RS PRO BRUSHED GEARED, 7.92 W, 12 V, 59 NCM, 20 RPM, 6MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 12 V dc
- DC Motor Type: Brushed Geared
- Power Rating: 7.92 W
- Output Speed: 20 rpm
- Shaft Diameter: 6 mm
- Maximum Output Torque: 6000 gcm
- Gearhead Type: Spur
- Current Rating: 990 mA



420671 12 V dc

RS PRO BRUSHED GEARED, 19.8 W, 12 V, 10 NCM, 2008 RPM, 6MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 12 V dc
- DC Motor Type: Brushed Geared
- Power Rating: 19.8 W
- Output Speed: 2008 rpm
- Shaft Diameter: 6 mm
- Maximum Output Torque: 1000 gcm
- Gearhead Type: Spur
- Current Rating: 2.81 A



420675 12 V dc

RS PRO BRUSHED GEARED, 1.71 W, 3 V, 15 NCM, 7 RPM, 4MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 3 V dc
- DC Motor Type: Brushed Geared
- Power Rating: 1.71 W
- Output Speed: 7 rpm
- Shaft Diameter: 4 mm
- Maximum Output Torque: 1500 gcm
- Gearhead Type: Spur
- Current Rating: 1.06 A



420681 3 V dc

RS PRO BRUSHED GEARED, 1.3 W, 12 V, 12 NCM, 27 RPM, 4MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 12 V dc
- DC Motor Type: Brushed Geared
- Power Rating: 1.3 W
- Output Speed: 27 rpm
- Shaft Diameter: 4 mm
- Maximum Output Torque: 1200 gcm
- Gearhead Type: Spur
- Current Rating: 194 mA



420693 12 V dc

RS PRO BRUSHED GEARED, 19.8 W, 4.5 → 15 V, 59 NCM, 120 RPM, 6MM

Pack size: **1 x EA**

- Supply Voltage: 4.5 V
- DC Motor Type: Brushed Geared
- Power Rating: 19.8 W
- Output Speed: 120 rpm
- Shaft Diameter: 6 mm
- Maximum Output Torque: 6000 gcm
- Gearhead Type: Spur
- Current Rating: 2.81 A



420697 4.5 V

RS PRO BRUSHED GEARED, 1.5 W, 12 V, 24 MNM, 1675 RPM, 4MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 12 V dc
- DC Motor Type: Brushed Geared
- Power Rating: 1.5 W
- Output Speed: 1675 rpm
- Shaft Diameter: 4 mm
- Maximum Output Torque: 246 gcm
- Gearhead Type: Planetary
- Current Rating: 200 mA



420700 12 V dc

RS PRO BRUSHED GEARED, 1.5 W, 12 V, 20 NCM, 76 RPM, 4MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 12 V dc
- DC Motor Type: Brushed Geared
- Power Rating: 1.5 W
- Output Speed: 76 rpm
- Shaft Diameter: 4 mm
- Maximum Output Torque: 2000 gcm
- Gearhead Type: Planetary
- Current Rating: 200 mA



420704 12 V dc

RS PRO BRUSHED GEARED, 0.39 W, 12 V, 24 NCM, 6 RPM, 3MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 12 V dc
- DC Motor Type: Brushed Geared
- Power Rating: 0.39 W
- Output Speed: 6 rpm
- Shaft Diameter: 3 mm
- Maximum Output Torque: 2400 gcm
- Gearhead Type: Planetary
- Current Rating: 60 mA



420710 12 V dc

RS PRO BRUSHED GEARED, 1.5 W, 12 V, 20 NCM, 108 RPM, 4MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 12 V dc
- DC Motor Type: Brushed Geared
- Power Rating: 1.5 W
- Output Speed: 108 rpm
- Shaft Diameter: 4 mm
- Maximum Output Torque: 2000 gcm
- Gearhead Type: Planetary
- Current Rating: 200 mA



420716 12 V dc

RS PRO BRUSHED GEARED, 24 V, 40 NCM, 86 RPM, 5.5MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 24 V
- DC Motor Type: Brushed Geared
- Output Speed: 86 rpm
- Shaft Diameter: 5.5 mm
- Maximum Output Torque: 40 Ncm
- Gearhead Type: Spur
- Gear Ratio: 60:1
- Dimensions: 40 x 40 x 68.5 mm



1440536 24 V

RS PRO BRUSHLESS, 12 V, 0.019 NM, 5170 RPM, 20MM SHAFT DIAMETER

Pack size: **1 x EA**

- Supply Voltage: 12 V
- DC Motor Type: Brushless
- Output Speed: 5170 rpm
- Shaft Diameter: 20 mm
- Maximum Output Torque: 0.019 Nm
- Current Rating: 0.63A
- Length: 14 mm



2163784 12 V

RS PRO BRUSHLESS, 12 V, 0.075 NM, 2800 RPM, 20MM SHAFT DIAMETER

Pack size: **1 x EA**

- Supply Voltage: 12 V
- DC Motor Type: Brushless
- Output Speed: 2800 rpm
- Shaft Diameter: 20 mm
- Maximum Output Torque: 0.075 Nm
- Length: 17.9 mm



2163787 12 V

RS PRO BRUSHLESS, 24 V, 0.05 NM, 4800 RPM, 25MM SHAFT DIAMETER

Pack size: **1 x EA**

- Supply Voltage: 24 V
- DC Motor Type: Brushless
- Output Speed: 4800 rpm
- Shaft Diameter: 25 mm
- Maximum Output Torque: 0.05 Nm
- Length: 20 mm



2163788 24 V

RS PRO BRUSHLESS, 24 V, 0.11 NM, 4800 RPM, 25MM SHAFT DIAMETER

Pack size: **1 x EA**

- Supply Voltage: 24 V
- DC Motor Type: Brushless
- Output Speed: 4800 rpm
- Shaft Diameter: 25 mm
- Maximum Output Torque: 0.11 Nm
- Length: 40 mm



2163789 24 V

RS PRO BRUSHLESS, 24 V, 0.21 NM, 4500 RPM, 25MM SHAFT DIAMETER

Pack size: **1 x EA**

- Supply Voltage: 24 V
- DC Motor Type: Brushless
- Output Speed: 4500 rpm
- Shaft Diameter: 25 mm
- Maximum Output Torque: 0.21 Nm
- Length: 57 mm



2163790 24 V

RS PRO BRUSHLESS, 24 V, 0.24 NM, 4800 RPM, 25MM SHAFT DIAMETER

Pack size: **1 x EA**

- Supply Voltage: 24 V
- DC Motor Type: Brushless
- Output Speed: 4800 rpm
- Shaft Diameter: 25 mm
- Maximum Output Torque: 0.24 Nm
- Length: 60 mm



2163791 24 V

RS PRO BRUSHLESS, 48 V, 0.9 NM, 3700 RPM, 20MM SHAFT DIAMETER

Pack size: **1 x EA**

- Supply Voltage: 48 V
- DC Motor Type: Brushless
- Output Speed: 3700 rpm
- Shaft Diameter: 20 mm
- Maximum Output Torque: 0.9 Nm
- Length: 38 mm



2163797 48 V

RS PRO BRUSHED, 41 W, 14.5 V, 13 NCM, 3000 RPM, 6MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 14.5 V dc
- DC Motor Type: Brushed
- Power Rating: 41 W
- Output Speed: 3000 rpm
- Shaft Diameter: 6 mm
- Maximum Output Torque: 13 Ncm
- Dimensions: 120 (Dia.) x 37.7 mm
- Current Rating: 6.9 A



2259541 14.5 V dc

RS PRO BRUSHED, 110 W, 23.5 V, 35 NCM, 3000 RPM, 10MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 23.5 V dc
- DC Motor Type: Brushed
- Power Rating: 110 W
- Output Speed: 3000 rpm
- Shaft Diameter: 10 mm
- Maximum Output Torque: 35 Ncm
- Dimensions: 152 (Dia.) x 60 mm
- Current Rating: 7.6 A



2259579 23.5 V dc

RS PRO BRUSHED GEARED, 2.51 W, 3 V, 5 MNM, 2 → 3700 RPM, 2MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 3 V, 1.5 → 3 V dc
- DC Motor Type: Brushed Geared
- Power Rating: 2.51 W
- Output Speed: 4 - 3825 rpm
- Shaft Diameter: 2 mm
- Maximum Output Torque: 50 gcm
- Gearhead Type: Spur
- Current Rating: 260 mA



2389642 3 V, 1.5 → 3 V dc

RS PRO BRUSHED GEARED, 19.8 W, 12 V, 10 NCM, 1095 RPM, 6MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 12 V dc
- DC Motor Type: Brushed Geared
- Power Rating: 19.8 W
- Output Speed: 1095 rpm
- Shaft Diameter: 6 mm
- Maximum Output Torque: 1000 gcm
- Gearhead Type: Spur
- Current Rating: 2.81 A



2389664 12 V dc

RS PRO BRUSHED GEARED, 19.8 W, 12 V, 59 NCM, 84 RPM, 6MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 12 V, 4.5 → 15 V dc
- DC Motor Type: Brushed Geared
- Power Rating: 19.8 W
- Output Speed: 84 rpm
- Shaft Diameter: 6 mm
- Maximum Output Torque: 6000 gcm
- Gearhead Type: Spur
- Current Rating: 2.75 A



2389670 12 V, 4.5 → 15 V dc

RS PRO BRUSHED, 1.21 W, 1.5 → 3 V, 10.4 GCM, 8200 → 14000 RPM, 2MM

Pack size: **1 x EA**

- Supply Voltage: 1.5 → 3 V dc
- DC Motor Type: Brushed
- Power Rating: 1.21 W
- Output Speed: 8200 → 14000 rpm
- Shaft Diameter: 2 mm
- Maximum Output Torque: 10.4 gcm
- Dimensions: 21 (Dia.) x 38 mm
- Current Rating: 960 mA



2389692 1.5 → 3 V dc

RS PRO GEARED, 5.75 W, 6 → 15 V, 58.8 GCM, 10668 RPM, 2.31MM

Pack size: **1 x EA**

- Supply Voltage: 6 → 15 V dc
- DC Motor Type: Geared
- Power Rating: 5.75 W
- Output Speed: 10668 rpm
- Shaft Diameter: 2.31 mm
- Maximum Output Torque: 58.8 gcm
- Dimensions: 27.63 (Dia.) x 32.5 mm
- Current Rating: 770 mA



2389715 6 → 15 V dc

RS PRO GEARED, 7.98 W, 6 → 15 V, 78.4 GCM, 9869 RPM, 2.31MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 6 → 15 V dc
- DC Motor Type: Geared
- Power Rating: 7.98 W
- Output Speed: 9869 rpm
- Shaft Diameter: 2.31 mm
- Maximum Output Torque: 78.4 gcm
- Dimensions: 27.7 (Dia.) x 38 mm
- Current Rating: 990 mA



2389737 6 → 15 V dc

RS PRO GEARED, 21.2 W, 4.5 → 15 V, 154.4 GCM, 13360 RPM, 3.18MM

Pack size: **1 x EA**

- Supply Voltage: 4.5 → 15 V dc
- DC Motor Type: Geared
- Power Rating: 21.2 W
- Output Speed: 13360 rpm
- Shaft Diameter: 3.18 mm
- Maximum Output Torque: 154.4 gcm
- Dimensions: 35.8 (Dia.) x 50 mm
- Current Rating: 2.85 A



2389759 4.5 → 15 V dc

RS PRO BRUSHED GEARED, 1.62 W, 12 → 24 V, 5 MNM, 2 → 4199 RPM, 2MM

Pack size: **1 x EA**

- Supply Voltage: 12 → 24 V dc
- DC Motor Type: Brushed Geared
- Power Rating: 1.62 W
- Output Speed: 2 - 2100 rpm
- Shaft Diameter: 2 mm
- Maximum Output Torque: 50 gcm
- Gearhead Type: Spur
- Current Rating: 300 mA



2389822 12 → 24 V dc

RS PRO BRUSHED GEARED, 1.6 W, 3 V, 5 MNM, 1 → 2300 RPM, 2MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 3 V dc
- DC Motor Type: Brushed Geared
- Power Rating: 1.6 W
- Output Speed: 2 - 2300 rpm
- Shaft Diameter: 2 mm
- Maximum Output Torque: 50 gcm
- Gearhead Type: Spur
- Current Rating: 850 mA



2389844 3 V dc

RS PRO GEARED, 12 V, 10 NCM, 180 RPM, 5MM SHAFT DIAMETER

Pack size: **1 x EA**

- Supply Voltage: 12 V dc
- DC Motor Type: Geared
- Output Speed: 180 rpm
- Shaft Diameter: 5 mm
- Maximum Output Torque: 100 mNm
- Gearhead Type: Spur
- Length: 57.8 mm
- Width: 27.7 mm



2588287 12 V dc

RS PRO GEARED, 24 V, 10 NCM, 190 RPM, 5MM SHAFT DIAMETER

Pack size: **1 x EA**

- Supply Voltage: 24 V dc
- DC Motor Type: Geared
- Output Speed: 190 rpm
- Shaft Diameter: 5 mm
- Maximum Output Torque: 100 mNm
- Gearhead Type: Spur
- Length: 57.8 mm
- Width: 27.7 mm



2588293 24 V dc

RS PRO GEARED, 12 V, 20 NCM, 70 RPM, 5MM SHAFT DIAMETER

Pack size: **1 x EA**

- Supply Voltage: 12 V dc
- DC Motor Type: Geared
- Output Speed: 70 rpm
- Shaft Diameter: 5 mm
- Maximum Output Torque: 200 mNm
- Gearhead Type: Spur
- Length: 57.8 mm
- Width: 27.7 mm



2588300 12 V dc

RS PRO GEARED, 24 V, 20 NCM, 75 RPM, 5MM SHAFT DIAMETER

Pack size: **1 x EA**

- Supply Voltage: 24 V dc
- DC Motor Type: Geared
- Output Speed: 75 rpm
- Shaft Diameter: 5 mm
- Maximum Output Torque: 200 mNm
- Gearhead Type: Spur
- Length: 57.8 mm
- Width: 27.7 mm



2588316 24 V dc

RS PRO GEARED, 12 V, 30 NCM, 29 RPM, 5MM SHAFT DIAMETER

Pack size: **1 x EA**

- Supply Voltage: 12 V dc
- DC Motor Type: Geared
- Output Speed: 29 rpm
- Shaft Diameter: 5 mm
- Maximum Output Torque: 300 mNm
- Gearhead Type: Spur
- Length: 62.3 mm
- Width: 27.7 mm



2588322 12 V dc

RS PRO GEARED, 24 V, 30 NCM, 30 RPM, 5MM SHAFT DIAMETER

Pack size: **1 x EA**

- Supply Voltage: 24 V dc
- DC Motor Type: Geared
- Output Speed: 30 rpm
- Shaft Diameter: 5 mm
- Maximum Output Torque: 300 mNm
- Gearhead Type: Spur
- Length: 62.3 mm
- Width: 27.7 mm



2588344 24 V dc

RS PRO GEARED, 12 V, 30 NCM, 11 RPM, 5MM SHAFT DIAMETER

Pack size: **1 x EA**

- Supply Voltage: 12 V dc
- DC Motor Type: Geared
- Output Speed: 11 rpm
- Shaft Diameter: 5 mm
- Maximum Output Torque: 300 mNm
- Gearhead Type: Spur
- Length: 62.3 mm
- Width: 27.7 mm



2588350 12 V dc

RS PRO GEARED, 24 V, 30 NCM, 12 RPM, 5MM SHAFT DIAMETER

Pack size: **1 x EA**

- Supply Voltage: 24 V dc
- DC Motor Type: Geared
- Output Speed: 12 rpm
- Shaft Diameter: 5 mm
- Maximum Output Torque: 300 mNm
- Gearhead Type: Spur
- Length: 62.3 mm
- Width: 27.7 mm



2588366 24 V dc

RS PRO GEARED, 12 V, 30 NCM, 5 RPM, 5MM SHAFT DIAMETER

Pack size: **1 x EA**

- Supply Voltage: 12 V dc
- DC Motor Type: Geared
- Output Speed: 5 rpm
- Shaft Diameter: 5 mm
- Maximum Output Torque: 300 mNm
- Gearhead Type: Spur
- Length: 66.8 mm
- Width: 27.7 mm



2588372 12 V dc

RS PRO GEARED, 24 V, 30 NCM, 5 RPM, 5MM SHAFT DIAMETER

Pack size: **1 x EA**

- Supply Voltage: 24 V dc
- DC Motor Type: Geared
- Output Speed: 5 rpm
- Shaft Diameter: 5 mm
- Maximum Output Torque: 300 mNm
- Gearhead Type: Spur
- Length: 66.8 mm
- Width: 27.7 mm



2588388 24 V dc

RS PRO BRUSHED GEARED, 19.8 W, 12 V, 29 NCM, 241 RPM, 6MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 12 V dc
- DC Motor Type: Brushed Geared
- Power Rating: 19.8 W
- Output Speed: 241 rpm
- Shaft Diameter: 6 mm
- Maximum Output Torque: 3000 gcm
- Gearhead Type: Spur
- Current Rating: 2.75 A



3213164 12 V dc

RS PRO BRUSHED GEARED, 19.8 W, 12 V, 59 NCM, 15 RPM, 6MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 12 V dc
- DC Motor Type: Brushed Geared
- Power Rating: 19.8 W
- Output Speed: 15 rpm
- Shaft Diameter: 6 mm
- Maximum Output Torque: 6000 gcm
- Gearhead Type: Spur
- Current Rating: 2.75 A



3213170 12 V dc

RS PRO, 36.88 W, 12 V, 82.08 GCM, 4289 RPM, 6.35MM SHAFT DIAMETER

Pack size: **1 x EA**

- Supply Voltage: 12 V dc
- Power Rating: 36.88 W
- Output Speed: 4289 rpm
- Shaft Diameter: 6.35 mm
- Maximum Output Torque: 82.08 gcm
- Dimensions: 51.8 (Dia.) x 69 mm
- Current Rating: 5.28 A
- Length: 69 mm



3213186 12 V dc

RS PRO BRUSHED GEARED, 13.2 W, 24 V, 75 NCM, 1260 RPM, 6MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 24 V dc
- DC Motor Type: Brushed Geared
- Power Rating: 13.2 W
- Output Speed: 1260 rpm
- Shaft Diameter: 6 mm
- Maximum Output Torque: 0.75 Nm
- Gearhead Type: Planetary
- Current Rating: 850 mA



3989776 24 V dc

RS PRO BRUSHED GEARED, 13.2 W, 24 V, 13 NCM, 450 RPM, 6MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 24 V dc
- DC Motor Type: Brushed Geared
- Power Rating: 13.2 W
- Output Speed: 450 rpm
- Shaft Diameter: 6 mm
- Maximum Output Torque: 134 mNm
- Gearhead Type: Planetary
- Current Rating: 850 mA



3989782 24 V dc

RS PRO BRUSHED GEARED, 13.2 W, 24 V, 4.5 NM, 63 RPM, 6MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 24 V dc
- DC Motor Type: Brushed Geared
- Power Rating: 13.2 W
- Output Speed: 63 rpm
- Shaft Diameter: 6 mm
- Maximum Output Torque: 4.5 Nm
- Gearhead Type: Planetary
- Current Rating: 850 mA



3989833 24 V dc

RS PRO BRUSHED GEARED, 13.2 W, 24 V, 4.5 NM, 27 RPM, 6MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 24 V dc
- DC Motor Type: Brushed Geared
- Power Rating: 13.2 W
- Output Speed: 27 rpm
- Shaft Diameter: 6 mm
- Maximum Output Torque: 4.5 Nm
- Gearhead Type: Planetary
- Current Rating: 850 mA



3989849 24 V dc

RS PRO BRUSHED GEARED, 1.71 W, 3 V, 4 NCM, 604 RPM, 4MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 3 V dc
- DC Motor Type: Brushed Geared
- Power Rating: 1.71 W
- Output Speed: 604 rpm
- Shaft Diameter: 4 mm
- Maximum Output Torque: 400 gcm
- Gearhead Type: Spur
- Current Rating: 1.06 A



4130587 3 V dc

RS PRO BRUSHED GEARED, 1.71 W, 3 V, 6 NCM, 240 RPM, 4MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 3 V dc
- DC Motor Type: Brushed Geared
- Power Rating: 1.71 W
- Output Speed: 240 rpm
- Shaft Diameter: 4 mm
- Maximum Output Torque: 600 gcm
- Gearhead Type: Spur
- Current Rating: 1.06 A



4130593 3 V dc

RS PRO BRUSHED GEARED, 1.71 W, 3 V, 10 NCM, 72 RPM, 4MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 3 V dc
- DC Motor Type: Brushed Geared
- Power Rating: 1.71 W
- Output Speed: 72 rpm
- Shaft Diameter: 4 mm
- Maximum Output Torque: 1000 gcm
- Gearhead Type: Spur
- Current Rating: 1.06 A



4130600 3 V dc

RS PRO BRUSHED GEARED, 1.31 W, 12 V, 4 NCM, 442 RPM, 4MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 12 V dc
- DC Motor Type: Brushed Geared
- Power Rating: 1.31 W
- Output Speed: 442 rpm
- Shaft Diameter: 4 mm
- Maximum Output Torque: 400 gcm
- Gearhead Type: Spur
- Current Rating: 190 mA



4130616 12 V dc

RS PRO BRUSHED GEARED, 1.31 W, 12 V, 10 NCM, 66 RPM, 4MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 12 V, 12 → 24 V dc
- DC Motor Type: Brushed Geared
- Power Rating: 1.31 W
- Output Speed: 66 rpm
- Shaft Diameter: 4 mm
- Maximum Output Torque: 1000 gcm
- Gearhead Type: Spur
- Current Rating: 190 mA



4130622 12 V, 12 → 24 V dc

RS PRO BRUSHED GEARED, 1.31 W, 12 V, 59 MNM, 221 RPM, 4MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 12 V dc
- DC Motor Type: Brushed Geared
- Power Rating: 1.31 W
- Output Speed: 221 rpm
- Shaft Diameter: 4 mm
- Maximum Output Torque: 600 gcm
- Gearhead Type: Spur
- Current Rating: 190 mA



4130638 12 V dc

RS PRO BRUSHED GEARED, 19.8 W, 12 V, 5 NCM, 4819 RPM, 6MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 12 V dc
- DC Motor Type: Brushed Geared
- Power Rating: 19.8 W
- Output Speed: 4819 rpm
- Shaft Diameter: 6 mm
- Maximum Output Torque: 500 gcm
- Gearhead Type: Spur
- Current Rating: 2.85 A



4179633 12 V dc

RS PRO BRUSHED GEARED, 19.8 W, 12 V, 59 NCM, 4 RPM, 6MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 12 V dc
- DC Motor Type: Brushed Geared
- Power Rating: 19.8 W
- Output Speed: 4 rpm
- Shaft Diameter: 6 mm
- Maximum Output Torque: 6000 gcm
- Gearhead Type: Spur
- Current Rating: 2.8 A



4179649 12 V dc

RS PRO BRUSHED GEARED, 7.92 W, 12 V, 13 NCM, 1974 RPM, 6MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 12 V dc
- DC Motor Type: Brushed Geared
- Power Rating: 7.92 W
- Output Speed: 1974 rpm
- Shaft Diameter: 6 mm
- Maximum Output Torque: 1284 gcm
- Gearhead Type: Planetary
- Current Rating: 990 mA



4179655 12 V dc

RS PRO BRUSHED GEARED, 7.92 W, 12 V, 98 NCM, 99 RPM, 6MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 12 V dc
- DC Motor Type: Brushed Geared
- Power Rating: 7.92 W
- Output Speed: 99 rpm
- Shaft Diameter: 6 mm
- Maximum Output Torque: 10000 gcm
- Gearhead Type: Planetary
- Current Rating: 990 mA



4179661 12 V dc

RS PRO BRUSHED GEARED, 7.92 W, 12 V, 98 NCM, 19 RPM, 6MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 12 V dc
- DC Motor Type: Brushed Geared
- Power Rating: 7.92 W
- Output Speed: 19 rpm
- Shaft Diameter: 6 mm
- Maximum Output Torque: 10000 gcm
- Gearhead Type: Planetary
- Current Rating: 990 mA



4179677 12 V dc

RS PRO BRUSHED GEARED, 0.394 W, 12 V, 7 MNM, 1550 RPM, 3MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 12 V dc
- DC Motor Type: Brushed Geared
- Power Rating: 0.394 W
- Output Speed: 1550 rpm
- Shaft Diameter: 3 mm
- Maximum Output Torque: 68 gcm
- Gearhead Type: Planetary
- Current Rating: 85 mA



4179683 12 V dc

RS PRO BRUSHED GEARED, 0.394 W, 12 V, 8 NCM, 100 RPM, 3MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 12 V dc
- DC Motor Type: Brushed Geared
- Power Rating: 0.394 W
- Output Speed: 100 rpm
- Shaft Diameter: 3 mm
- Maximum Output Torque: 794 gcm
- Gearhead Type: Planetary
- Current Rating: 85 mA



4179706 12 V dc

RS PRO BRUSHED GEARED, 0.394 W, 12 V, 20 NCM, 27 RPM, 3MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 12 V dc
- DC Motor Type: Brushed Geared
- Power Rating: 0.394 W
- Output Speed: 27 rpm
- Shaft Diameter: 3 mm
- Maximum Output Torque: 2000 gcm
- Gearhead Type: Planetary
- Current Rating: 85 mA



4179712 12 V dc

RS PRO BRUSHED GEARED, 7.92 W, 12 V, 5 NCM, 3948 RPM, 6MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 12 V dc
- DC Motor Type: Brushed Geared
- Power Rating: 7.92 W
- Output Speed: 3948 rpm
- Shaft Diameter: 6 mm
- Maximum Output Torque: 520 gcm
- Gearhead Type: Planetary
- Current Rating: 990 mA



4540798 12 V dc

RS PRO BRUSHED GEARED, 7.92 W, 12 V, 10 NCM, 1645 RPM, 6MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 12 V dc
- DC Motor Type: Brushed Geared
- Power Rating: 7.92 W
- Output Speed: 1645 rpm
- Shaft Diameter: 6 mm
- Maximum Output Torque: 1000 gcm
- Gearhead Type: Spur
- Current Rating: 990 mA



4540805 12 V dc

RS PRO BRUSHED GEARED, 7.92 W, 12 V, 10 NCM, 897 RPM, 6MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 12 V dc
- DC Motor Type: Brushed Geared
- Power Rating: 7.92 W
- Output Speed: 897 rpm
- Shaft Diameter: 6 mm
- Maximum Output Torque: 1000 gcm
- Gearhead Type: Spur
- Current Rating: 990 mA



4540827 12 V dc

RS PRO BRUSHED GEARED, 7.92 W, 12 V, 29 NCM, 197 RPM, 6MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 12 V dc
- DC Motor Type: Brushed Geared
- Power Rating: 7.92 W
- Output Speed: 197 rpm
- Shaft Diameter: 6 mm
- Maximum Output Torque: 3000 gcm
- Gearhead Type: Spur
- Current Rating: 990 mA



4540833 12 V dc

RS PRO BRUSHED GEARED, 7.92 W, 12 V, 59 NCM, 12 RPM, 6MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 12 V dc
- DC Motor Type: Brushed Geared
- Power Rating: 7.92 W
- Output Speed: 12 rpm
- Shaft Diameter: 6 mm
- Maximum Output Torque: 6000 gcm
- Gearhead Type: Spur
- Current Rating: 990 mA



4540855 12 V dc

RS PRO BRUSHED GEARED, 7.92 W, 12 V, 59 NCM, 67 RPM, 6MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 12 V dc
- DC Motor Type: Brushed Geared
- Power Rating: 7.92 W
- Output Speed: 67 rpm
- Shaft Diameter: 6 mm
- Maximum Output Torque: 6000 gcm
- Gearhead Type: Spur
- Current Rating: 990 mA



4540849 12 V dc

MOTOR,GEARED,4.5-15VDC,PLANETARY,EPICYCLIC,GEARHE

Pack size: **1 x EA**

- Supply Voltage: 12 V dc
- DC Motor Type: Brushed Geared
- Power Rating: 19.8 W
- Output Speed: 120 rpm
- Shaft Diameter: 6 mm
- Maximum Output Torque: 10000 gcm
- Gearhead Type: Planetary
- Current Rating: 2.75 A



4540883 12 V dc

RS PRO BRUSHED GEARED, 19.8 W, 12 V, 20 NCM, 3090 RPM, 6MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 12 V dc
- DC Motor Type: Brushed Geared
- Power Rating: 19.8 W
- Output Speed: 3090 rpm
- Shaft Diameter: 6 mm
- Maximum Output Torque: 2000 gcm
- Gearhead Type: Planetary
- Current Rating: 2.8 A



4540877 12 V dc

RS PRO BRUSHED GEARED, 19.8 W, 12 V, 1.2 NM, 24 RPM, 6MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 12 V dc
- DC Motor Type: Brushed Geared
- Power Rating: 19.8 W
- Output Speed: 24 rpm
- Shaft Diameter: 6 mm
- Maximum Output Torque: 12000 gcm
- Gearhead Type: Spur
- Current Rating: 2.81 A



4540899 12 V dc

RS PRO BRUSHLESS, 24 V, 0.19 NM, 4000 RPM, 5MM SHAFT DIAMETER

Pack size: **1 x EA**

- Supply Voltage: 24 V dc
- DC Motor Type: Brushless
- Output Speed: 4000 rpm
- Shaft Diameter: 5 mm
- Maximum Output Torque: 0.19 Nm
- Dimensions: 41 x 42 x 42 mm
- Current Rating: 5.4 A
- Length: 41 mm



5366024 24 V dc

RS PRO BRUSHED GEARED, 7.92 W, 12 V, 59 NCM, 3 RPM, 6MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 12 V dc
- DC Motor Type: Brushed Geared
- Power Rating: 7.92 W
- Output Speed: 3 rpm
- Shaft Diameter: 6 mm
- Maximum Output Torque: 6000 gcm
- Gearhead Type: Spur
- Current Rating: 990 mA



4540861 12 V dc

RS PRO BRUSHLESS, 24 V, 0.75 NM, 4000 RPM, 5MM SHAFT DIAMETER

Pack size: **1 x EA**

- Supply Voltage: 24 V dc
- DC Motor Type: Brushless
- Output Speed: 4000 rpm
- Shaft Diameter: 5 mm
- Maximum Output Torque: 0.75 Nm
- Dimensions: 100 x 42 x 42 mm
- Current Rating: 20 A
- Length: 100 mm



5366030 24 V dc

RS PRO BRUSHLESS, 36 V, 0.68 NM, 4000 RPM, 8MM SHAFT DIAMETER

Pack size: **1 x EA**

- Supply Voltage: 36 V dc
- DC Motor Type: Brushless
- Output Speed: 4000 rpm
- Shaft Diameter: 8 mm
- Maximum Output Torque: 0.68 Nm
- Dimensions: 57 (Dia.) x 74 mm
- Current Rating: 9.8 A
- Length: 74 mm



5366046 36 V dc

RS PRO GEARED, 11 W, 4.5 → 15 V, 206 GCM, 5216 RPM, 6MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 4.5 → 15 V
- DC Motor Type: Geared
- Power Rating: 11 W
- Output Speed: 5216 rpm
- Shaft Diameter: 6 mm
- Maximum Output Torque: 206 gcm
- Dimensions: 41 x 42 x 84.1 mm
- Current Rating: 1.26 A



7521949 4.5 → 15 V

RS PRO GEARED, 7.98 W, 6 → 15 V, 78.4 GCM, 112 RPM, 6MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 6 → 15 V
- DC Motor Type: Geared
- Power Rating: 7.98 W
- Output Speed: 112 rpm
- Shaft Diameter: 6 mm
- Maximum Output Torque: 78.4 gcm
- Dimensions: 32 (Dia.) x 73.9 mm
- Current Rating: 990 mA



7521964 6 → 15 V

RS PRO GEARED, 11 W, 4.5 → 15 V, 6000 GCM, 12 RPM, 6MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 4.5 → 15 V
- DC Motor Type: Geared
- Power Rating: 11 W
- Output Speed: 12 rpm
- Shaft Diameter: 6 mm
- Maximum Output Torque: 6000 gcm
- Dimensions: 37 (Dia.) x 86.6 mm
- Current Rating: 1.26 A



7521958 4.5 → 15 V

RS PRO GEARED, 7.98 W, 6 → 15 V, 78.4 GCM, 41 RPM, 6MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 6 → 15 V
- DC Motor Type: Geared
- Power Rating: 7.98 W
- Output Speed: 41 rpm
- Shaft Diameter: 6 mm
- Maximum Output Torque: 78.4 gcm
- Dimensions: 32 (Dia.) x 80.5 mm
- Current Rating: 990 mA



7521967 6 → 15 V

RS PRO BRUSHED GEARED, 0.394 W, 12 V, 16 NCM, 60 RPM, 3MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 12 V dc
- DC Motor Type: Brushed Geared
- Power Rating: 0.394 W
- Output Speed: 60 rpm
- Shaft Diameter: 3 mm
- Maximum Output Torque: 1600 gcm
- Gearhead Type: Planetary
- Dimensions: 16 (Dia.) x 49 mm



7521970 12 V dc

RS PRO GEARED, 7 W, 4.5 → 15 V, 114 GCM, 7300 RPM, 6MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 4.5 → 15 V
- DC Motor Type: Geared
- Power Rating: 7 W
- Output Speed: 7300 rpm
- Shaft Diameter: 6 mm
- Maximum Output Torque: 114 gcm
- Dimensions: 37 (Dia.) x 76.1 mm
- Current Rating: 840 mA



7521983 4.5 → 15 V

RS PRO GEARED, 7 W, 4.5 → 15 V, 114 GCM, 7300 RPM, 6MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 4.5 → 15 V
- DC Motor Type: Geared
- Power Rating: 7 W
- Output Speed: 7300 rpm
- Shaft Diameter: 6 mm
- Maximum Output Torque: 114 gcm
- Dimensions: 37 (Dia.) x 73.6 mm
- Current Rating: 840 mA



7521989 4.5 → 15 V

RS PRO BRUSHED GEARED, 0.46 W, 6 V, 202 GCM, 145 RPM, 3MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 6 V
- DC Motor Type: Brushed Geared
- Power Rating: 0.46 W
- Output Speed: 145 rpm
- Shaft Diameter: 3 mm
- Maximum Output Torque: 700 gcm
- Gearhead Type: Spur
- Dimensions: 15.1 x 12 x 10 mm



7522002 6 V

RS PRO BRUSHED GEARED, 0.46 W, 6 V, 17 MNM, 230 RPM, 3MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 6 V dc
- DC Motor Type: Brushed Geared
- Power Rating: 0.46 W
- Output Speed: 230 rpm
- Shaft Diameter: 3 mm
- Maximum Output Torque: 173 gcm
- Gearhead Type: Spur
- Dimensions: 29.25 x 12 x 10 mm



7521999 6 V dc

RS PRO BRUSHED, 0.58 W, 6 V, 3.9 GCM, 13500 RPM, 2.5MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 6 V
- DC Motor Type: Brushed
- Power Rating: 0.58 W
- Output Speed: 13500 rpm
- Shaft Diameter: 2.5 mm
- Maximum Output Torque: 3.9 gcm
- Dimensions: 15.1 x 12 x 10 mm
- Current Rating: 320 mA



7522005 6 V

RS PRO BRUSHED GEARED, 19.8 W, 12 V, 29 NCM, 12048 RPM, 6MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 12 V
- DC Motor Type: Brushed Geared
- Power Rating: 19.8 W
- Output Speed: 12048 rpm
- Shaft Diameter: 6 mm
- Maximum Output Torque: 29 Ncm
- Gearhead Type: Spur
- Current Rating: 2.85 A



8347593 12 V

RS PRO BRUSHED GEARED, 7 W, 12 V, 10 NCM, 822 RPM, 6MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 12 V
- DC Motor Type: Brushed Geared
- Power Rating: 7 W
- Output Speed: 822 rpm
- Shaft Diameter: 6 mm
- Maximum Output Torque: 10 Ncm
- Gearhead Type: Spur
- Dimensions: 32 [Dia.] x 89.4 mm



8347603 12 V

RS PRO BRUSHED GEARED, 12.8 W, 12 V, 20 NCM, 1354 RPM, 6MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 12 V
- DC Motor Type: Brushed Geared
- Power Rating: 12.8 W
- Output Speed: 1354 rpm
- Shaft Diameter: 6 mm
- Maximum Output Torque: 20 Ncm
- Gearhead Type: Planetary
- Dimensions: 37 [Dia.] x 112.5 mm



8347613 12 V

RS PRO BRUSHED GEARED, 7 W, 12 V, 1.2 NM, 8 RPM, 6MM SHAFT DIAMETER

Pack size: **1 x EA**

- Supply Voltage: 12 V
- DC Motor Type: Brushed Geared
- Power Rating: 7 W
- Output Speed: 8 rpm
- Shaft Diameter: 6 mm
- Maximum Output Torque: 1.2 Nm
- Gearhead Type: Planetary
- Dimensions: 32 [Dia.] x 108.6 mm



8347616 12 V

RS PRO BRUSHED GEARED, 0.39 W, 12 V, 20 NCM, 14 RPM, 3MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 12 V
- DC Motor Type: Brushed Geared
- Power Rating: 0.39 W
- Output Speed: 14 rpm
- Shaft Diameter: 3 mm
- Maximum Output Torque: 20 Ncm
- Gearhead Type: Spur
- Current Rating: 85 mA



8347619 12 V

RS PRO BRUSHED GEARED, 12.8 W, 12 V, 1.2 NM, 14 RPM, 6MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 12 V
- DC Motor Type: Brushed Geared
- Power Rating: 12.8 W
- Output Speed: 14 rpm
- Shaft Diameter: 6 mm
- Maximum Output Torque: 1.2 Nm
- Gearhead Type: Planetary
- Dimensions: 37 [Dia.] x 120 mm



8347625 12 V

RS PRO BRUSHED GEARED, 7 W, 12 V, 10 NCM, 992 RPM, 6MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 12 V
- DC Motor Type: Brushed Geared
- Power Rating: 7 W
- Output Speed: 992 rpm
- Shaft Diameter: 6 mm
- Maximum Output Torque: 10 Ncm
- Gearhead Type: Spur
- Dimensions: 27.9 [Dia.] x 87.1 mm



8347629 12 V

RS PRO BRUSHED GEARED, 7 W, 12 V, 59 NCM, 60 RPM, 6MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 12 V
- DC Motor Type: Brushed Geared
- Power Rating: 7 W
- Output Speed: 60 rpm
- Shaft Diameter: 6 mm
- Maximum Output Torque: 59 Ncm
- Gearhead Type: Spur
- Dimensions: 27.9 [Dia.] x 92.1 mm



8347631 12 V

RS PRO BRUSHED GEARED, 0.58 W, 3 V, 4 MNM, 1350 RPM, 3MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 3 V
- DC Motor Type: Brushed Geared
- Power Rating: 0.58 W
- Output Speed: 1350 rpm
- Shaft Diameter: 3 mm
- Maximum Output Torque: 4 mNm
- Gearhead Type: Spur
- Dimensions: 29.25 x 10 x 12 mm



8347635 3 V

RS PRO BRUSHED GEARED, 41.3 W, 12 V, 1.8 NM, 116 RPM, 8MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 12 V
- DC Motor Type: Brushed Geared
- Power Rating: 41.3 W
- Output Speed: 116 rpm
- Shaft Diameter: 8 mm
- Maximum Output Torque: 1.8 Nm
- Gearhead Type: Planetary
- Dimensions: 44.6 [Dia.] x 133.9 mm



8347641 12 V

RS PRO BRUSHED GEARED, 0.58 W, 3 V, 3 NCM, 137 RPM, 3MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 3 V
- DC Motor Type: Brushed Geared
- Power Rating: 0.58 W
- Output Speed: 137 rpm
- Shaft Diameter: 3 mm
- Maximum Output Torque: 3 Ncm
- Gearhead Type: Spur
- Dimensions: 29.25 x 10 x 12 mm



8347644 3 V

RS PRO BRUSHED GEARED, 0.58 W, 3 V, 9 NCM, 45 RPM, 3MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 3 V
- DC Motor Type: Brushed Geared
- Power Rating: 0.58 W
- Output Speed: 45 rpm
- Shaft Diameter: 3 mm
- Maximum Output Torque: 9 Ncm
- Gearhead Type: Spur
- Dimensions: 29.25 x 10 x 12 mm



8347647 3 V

RS PRO BRUSHED GEARED, 41.3 W, 12 V, 2.5 NM, 27 RPM, 8MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 12 V
- DC Motor Type: Brushed Geared
- Power Rating: 41.3 W
- Output Speed: 27 rpm
- Shaft Diameter: 8 mm
- Maximum Output Torque: 2.5 Nm
- Gearhead Type: Planetary
- Dimensions: 44.6 [Dia.] x 140.6 mm



8347650 12 V

RS PRO BRUSHED GEARED, 7.85 W, 12 V, 1482 GCM, 431 RPM, 6MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 12 V
- DC Motor Type: Brushed Geared
- Power Rating: 7.85 W
- Output Speed: 431 rpm
- Shaft Diameter: 6 mm
- Maximum Output Torque: 1482 gcm
- Gearhead Type: Planetary
- Dimensions: 32 [Dia.] x 67.5 mm



8347663 12 V

RS PRO BRUSHED GEARED, 7 W, 12 V, 59 NCM, 2.6RPM, 6MM SHAFT

Pack size: 1 x EA

- Supply Voltage: 12 V
- DC Motor Type: Brushed Geared
- Power Rating: 7 W
- Output Speed: 2.6rpm
- Shaft Diameter: 6 mm
- Maximum Output Torque: 59 Ncm
- Gearhead Type: Spur
- Dimensions: 37 (Dia.) x 83.6mm



8347666 12 V

RS PRO BRUSHED GEARED, 7.85 W, 12 V, 2399 GCM, 228 RPM, 6MM SHAFT

Pack size: 1 x EA

- Supply Voltage: 12 V
- DC Motor Type: Brushed Geared
- Power Rating: 7.85 W
- Output Speed: 228 rpm
- Shaft Diameter: 6 mm
- Maximum Output Torque: 2399 gcm
- Gearhead Type: Planetary
- Dimensions: 32 (Dia.) x 73.9mm



8347669 12 V

RS PRO BRUSHED GEARED, 19.8 W, 12 V, 3024 GCM, 537 RPM, 6MM SHAFT

Pack size: 1 x EA

- Supply Voltage: 12 V
- DC Motor Type: Brushed Geared
- Power Rating: 19.8 W
- Output Speed: 537 rpm
- Shaft Diameter: 6 mm
- Maximum Output Torque: 3024 gcm
- Gearhead Type: Planetary
- Dimensions: 35.8 (Dia.) x 82.9mm



8347672 12 V

RS PRO BRUSHED GEARED, 0.46 W, 6 V, 24 GCM, 1800 RPM, 3MM SHAFT

Pack size: 1 x EA

- Supply Voltage: 6 V
- DC Motor Type: Brushed Geared
- Power Rating: 0.46 W
- Output Speed: 1800 rpm
- Shaft Diameter: 3 mm
- Maximum Output Torque: 24 gcm
- Gearhead Type: Spur
- Dimensions: 24.25 x 10 x 12mm



8347675 6 V

RS PRO BRUSHED GEARED, 12.8 W, 12 V, 223 GCM, 5258 RPM, 3.175MM

Pack size: 1 x EA

- Supply Voltage: 12 V
- DC Motor Type: Brushed Geared
- Power Rating: 12.8 W
- Output Speed: 5258 rpm
- Shaft Diameter: 3.175 mm
- Maximum Output Torque: 223 gcm
- Dimensions: 37 (Dia.) x 57.1mm
- Current Rating: 1.42 A



8347679 12 V

RS PRO BRUSHLESS, 24 V, 0.021 NM, 4600 RPM, 6.2MM SHAFT DIAMETER

Pack size: 1 x EA

- Supply Voltage: 24 V
- DC Motor Type: Brushless
- Output Speed: 4600 rpm
- Shaft Diameter: 6.2 mm
- Maximum Output Torque: 0.021 Nm
- Dimensions: 22 (Dia.) x 55.7 mm
- Current Rating: 1.1 A
- Length: 55.7 mm



8928757 24 V

RS PRO BRUSHLESS, 24 V, 0.25 NM, 5260 RPM, 4MM SHAFT DIAMETER

Pack size: 1 x EA

- Supply Voltage: 24 V
- DC Motor Type: Brushless
- Output Speed: 5260 rpm
- Shaft Diameter: 4 mm
- Maximum Output Torque: 0.25 Nm
- Dimensions: 42.8 (Dia.) x 42.2 mm
- Current Rating: 7 A
- Length: 42.2 mm



8928767 24 V

RS PRO BRUSHED GEARED, 12 V, 10 NCM, 155 RPM, 6MM SHAFT

Pack size: 1 x EA

- Supply Voltage: 12 V
- DC Motor Type: Brushed Geared
- Output Speed: 155 rpm
- Shaft Diameter: 6 mm
- Maximum Output Torque: 10 Ncm
- Gearhead Type: Spur
- Gear Ratio: 30:1
- Dimensions: 38 x 38 x 40 mm



9013282 12 V

RS PRO BRUSHED GEARED, 12 V, 70 MNM, 260 RPM, 6MM SHAFT

Pack size: 1 x EA

- Supply Voltage: 12 V
- DC Motor Type: Brushed Geared
- Output Speed: 260 rpm
- Shaft Diameter: 6 mm
- Maximum Output Torque: 70 mNm
- Gearhead Type: Spur
- Gear Ratio: 18:1
- Dimensions: 71.2 x 38 x 38 mm



9013288 12 V

RS PRO BRUSHED GEARED, 12 V, 20 NCM, 80 RPM, 6MM SHAFT DIAMETER

Pack size: 1 x EA

- Supply Voltage: 12 V
- DC Motor Type: Brushed Geared
- Output Speed: 80 rpm
- Shaft Diameter: 6 mm
- Maximum Output Torque: 20 Ncm
- Gearhead Type: Spur
- Gear Ratio: 60:1
- Dimensions: 73.7 x 38 x 38 mm



9013291 12 V

RS PRO BRUSHED GEARED, 12 V, 30 NCM, 47 RPM, 6MM SHAFT DIAMETER

Pack size: 1 x EA

- Supply Voltage: 12 V
- DC Motor Type: Brushed Geared
- Output Speed: 47 rpm
- Shaft Diameter: 6 mm
- Maximum Output Torque: 30 Ncm
- Gearhead Type: Spur
- Gear Ratio: 100:1
- Dimensions: 73.7 x 38 x 38 mm



9013294 12 V

RS PRO BRUSHED GEARED, 12 V, 600 MNM, 23 RPM, 6MM SHAFT DIAMETER

Pack size: 1 x EA

- Supply Voltage: 12 V
- DC Motor Type: Brushed Geared
- Output Speed: 23 rpm
- Shaft Diameter: 6 mm
- Maximum Output Torque: 600 mNm
- Gearhead Type: Spur
- Gear Ratio: 200:1
- Dimensions: 76.5 x 38 x 38 mm



9013298 12 V

RS PRO BRUSHED GEARED, 12 V, 600 MNM, 5 RPM, 6MM SHAFT DIAMETER

Pack size: 1 x EA

- Supply Voltage: 12 V
- DC Motor Type: Brushed Geared
- Output Speed: 5 rpm
- Shaft Diameter: 6 mm
- Maximum Output Torque: 600 mNm
- Gearhead Type: Spur
- Gear Ratio: 900:1
- Dimensions: 38 x 38 x 47.5 mm



9013301 12 V

RS PRO BRUSHED GEARED, 24 V, 70 MNM, 260 RPM, 6MM SHAFT

Pack size: 1 x EA

- Supply Voltage: 24 V
- DC Motor Type: Brushed Geared
- Output Speed: 260 rpm
- Shaft Diameter: 6 mm
- Maximum Output Torque: 70 mNm
- Gearhead Type: Spur
- Gear Ratio: 18:1
- Dimensions: 71.2 x 38 x 38 mm



9013305 24 V

RS PRO BRUSHED GEARED, 12 V, 600 MNM, 9 RPM, 6MM SHAFT DIAMETER

Pack size: 1 x EA

- Supply Voltage: 12 V
- DC Motor Type: Brushed Geared
- Output Speed: 9 rpm
- Shaft Diameter: 6 mm
- Maximum Output Torque: 600 mNm
- Gearhead Type: Spur
- Gear Ratio: 500:1
- Dimensions: 79 x 38 x 38 mm



9013308 12 V

RS PRO BRUSHED GEARED, 24 V, 30 NCM, 47 RPM, 6MM SHAFT DIAMETER

Pack size: 1 x EA

- Supply Voltage: 24 V
- DC Motor Type: Brushed Geared
- Output Speed: 47 rpm
- Shaft Diameter: 6 mm
- Maximum Output Torque: 30 Ncm
- Gearhead Type: Spur
- Gear Ratio: 100:1
- Dimensions: 73.7 x 38 x 38 mm



9013311 24 V

RS PRO BRUSHED GEARED, 24 V, 10 NCM, 155 RPM, 6MM SHAFT

Pack size: **1 x EA**

- Supply Voltage: 24 V
- DC Motor Type: Brushed Geared
- Output Speed: 155 rpm
- Shaft Diameter: 6 mm
- Maximum Output Torque: 10 Ncm
- Gearhead Type: Spur
- Gear Ratio: 30:1
- Dimensions: 38 x 38 x 40 mm



9013314 24 V

RS PRO BRUSHED GEARED, 24 V, 20 NCM, 80 RPM, 6MM SHAFT DIAMETER

Pack size: **1 x EA**

- Supply Voltage: 24 V
- DC Motor Type: Brushed Geared
- Output Speed: 80 rpm
- Shaft Diameter: 6 mm
- Maximum Output Torque: 20 Ncm
- Gearhead Type: Spur
- Gear Ratio: 60:1
- Dimensions: 73.7 x 38 x 38 mm



9013317 24 V

RS PRO BRUSHED GEARED, 24 V, 600 MNM, 23 RPM, 6MM SHAFT DIAMETER

Pack size: **1 x EA**

- Supply Voltage: 24 V
- DC Motor Type: Brushed Geared
- Output Speed: 23 rpm
- Shaft Diameter: 6 mm
- Maximum Output Torque: 600 mNm
- Gearhead Type: Spur
- Gear Ratio: 200:1
- Dimensions: 107.6 x 38 x 38 mm



9013320 24 V

RS PRO BRUSHED GEARED, 24 V, 600 MNM, 9 RPM, 6MM SHAFT DIAMETER

Pack size: **1 x EA**

- Supply Voltage: 24 V
- DC Motor Type: Brushed Geared
- Output Speed: 9 rpm
- Shaft Diameter: 6 mm
- Maximum Output Torque: 600 mNm
- Gearhead Type: Spur
- Gear Ratio: 500:1
- Dimensions: 79 x 38 x 38 mm



9013323 24 V

RS PRO BRUSHED GEARED, 24 V, 600 MNM, 5 RPM, 6MM SHAFT DIAMETER

Pack size: **1 x EA**

- Supply Voltage: 24 V
- DC Motor Type: Brushed Geared
- Output Speed: 5 rpm
- Shaft Diameter: 6 mm
- Maximum Output Torque: 600 mNm
- Gearhead Type: Spur
- Gear Ratio: 900:1
- Dimensions: 38 x 38 x 47.5 mm



9013327 24 V

GEARBOX, SPUR, OVOID, PRECISION DC MOTOR, 160:1

Pack size: **1 x EA**

- Gear Ratio: 160:1
- Gearbox Type: Ovoid
- Shaft Diameter: 4 mm
- Overall Width: 50 mm



336258 160:1

GEARBOX, SPUR, OVOID, PRECISION DC MOTOR, 640:1

Pack size: **1 x EA**

- Gear Ratio: 640:1
- Gearbox Type: Ovoid
- Shaft Diameter: 4 mm
- Overall Width: 50 mm



336264 640:1

GEARBOX, SPUR, OVOID, PRECISION DC MOTOR, 1250:1

Pack size: **1 x EA**

- Gear Ratio: 1250:1
- Gearbox Type: Ovoid
- Shaft Diameter: 4 mm
- Overall Width: 50 mm



336270 1250:1

RS PRO INVERTER DRIVE, 1-PHASE IN, 0.4 KW, 230 V AC, 7.2 A

Pack size: **1 x EA**

- Power Rating: 0.4 kW
- Phase: 1
- Supply Voltage: 230 V ac
- Current Rating: 7.2 A
- Output Frequency: 0.01 → 599 Hz
- For Use With: AC Motors
- Series: RS510
- IP Rating: IP20



1223410 0.4 kW

RS PRO INVERTER DRIVE, 1-PHASE IN, 0.75 KW, 230 V AC, 11 A

Pack size: **1 x EA**

- Power Rating: 0.75 kW
- Phase: 1
- Supply Voltage: 230 V ac
- Current Rating: 11 A
- Output Frequency: 0.01 → 599 Hz
- For Use With: AC Motors
- Series: RS510
- IP Rating: IP20



1223411 0.75 kW

RS PRO INVERTER DRIVE, 1-PHASE IN, 1.5 KW, 230 V AC, 15.5 A

Pack size: **1 x EA**

- Power Rating: 1.5 kW
- Phase: 1
- Supply Voltage: 230 V ac
- Current Rating: 15.5 A
- Output Frequency: 0.01 → 599 Hz
- For Use With: AC Motors
- Series: RS510
- IP Rating: IP20



1223413 1.5 kW

RS PRO INVERTER DRIVE, 1-PHASE IN, 2.2 KW, 230 V AC, 21 A

Pack size: **1 x EA**

- Power Rating: 2.2 kW
- Phase: 1
- Supply Voltage: 230 V ac
- Current Rating: 21 A
- Output Frequency: 0.01 → 599 Hz
- For Use With: AC Motors
- Series: RS510
- IP Rating: IP20



1223414 2.2 kW

RS PRO INVERTER DRIVE, 3-PHASE IN, 0.75 KW, 380 → 480 V AC, 4.2 A

Pack size: **1 x EA**

- Power Rating: 0.75 kW
- Phase: 3
- Supply Voltage: 380 → 480 V ac
- Current Rating: 4.2 A
- Output Frequency: 599 Hz
- For Use With: Wide Range of Drive Applications
- IP Rating: IP20
- Field Bus Communication Type: BACnet, Modbus, RS485



1748216 0.75 kW

RS PRO INVERTER DRIVE, 3-PHASE IN, 1.5 KW, 380 → 480 V AC, 5.6 A

Pack size: **1 x EA**

- Power Rating: 1.5 kW
- Phase: 3
- Supply Voltage: 380 → 480 V ac
- Current Rating: 5.6 A
- Output Frequency: 599 Hz
- For Use With: Wide Range of Drive Applications
- IP Rating: IP20
- Field Bus Communication Type: BACnet, Modbus, RS485



1748217 1.5 kW

RS PRO INVERTER DRIVE, 3-PHASE IN, 2.2 KW, 380 → 480 V AC, 7.3 A

Pack size: **1 x EA**

- Power Rating: 2.2 kW
- Phase: 3
- Supply Voltage: 380 → 480 V ac
- Current Rating: 7.3 A
- Output Frequency: 599 Hz
- For Use With: Wide Range of Drive Applications
- IP Rating: IP20
- Field Bus Communication Type: BACnet, Modbus, RS485



1748218 2.2 kW

RS PRO INVERTER DRIVE, 3-PHASE IN, 3.7 KW, 380 → 480 V AC, 10.1 A

Pack size: **1 x EA**

- Power Rating: 3.7 kW
- Phase: 3
- Supply Voltage: 380 → 480 V ac
- Current Rating: 10.1 A
- Output Frequency: 599 Hz
- For Use With: Wide Range of Drive Applications
- IP Rating: IP20
- Field Bus Communication Type: BACnet, Modbus, RS485



1748219 3.7 kW

RS PRO INVERTER DRIVE, 3-PHASE IN, 5.5 KW, 380 → 480 V AC, 14.3 A

Pack size: **1 x EA**

- Power Rating: 5.5 kW
- Phase: 3
- Supply Voltage: 380 → 480 V ac
- Current Rating: 14.3 A
- Output Frequency: 599 Hz
- For Use With: Wide Range of Drive Applications
- IP Rating: IP20
- Field Bus Communication Type: BACnet, Modbus, RS485



1748220 5.5 kW

REGULATOR, VOLTAGE, 15V, 3A, C/W SPEED CONTROL, DC MOTORS

Pack size: **1 x EA**

- Supply Voltage: 6 → 15 V dc
- Current Rating: 3 A
- Voltage Rating: 6 → 15 V dc



2389816 6 → 15 V dc

CONTROL, SERVO MOTOR, PRECISION DC, 4 QUADRANT, 2A

Pack size: **1 x EA**

- Supply Voltage: 10 → 35 V
- Current Rating: 2.2 A
- Voltage Rating: 27.5 V



3132122 10 → 35 V

MOTOR, SPEED, REGULATOR, PANEL MOUNT, PWM, 3A

Pack size: **1 x EA**

- Supply Voltage: 6 → 15 V dc
- Current Rating: 3 A
- Voltage Rating: 6 → 15 V dc



4179728 6 → 15 V dc

BI DIRECTIONAL SPEED REGULATOR

Pack size: **1 x EA**

- Supply Voltage: 6 → 15 V dc
- Current Rating: 3 A
- Voltage Rating: 6 → 15 V dc



7522009 6 → 15 V dc

RS PRO STEPPER MOTOR CONTROLLER, 4.4 A, 48 V

Pack size: **1 x EA**

- Current Rating: 4.4 A
- Voltage Rating: 48 V
- Overall Length: 92 mm
- Overall Width: 85 mm
- Overall Depth: 23 mm



9058780 4.4 A

RS PRO STEPPER MOTOR CONTROLLER 2.2 A, 24 → 48V, 78 X 68

Pack size: **1 x EA**

- Current Rating: 2.2 A
- Voltage Rating: 48 V
- Overall Length: 78 mm
- Overall Width: 68 mm
- Overall Depth: 21 mm



9058786 2.2 A

RS PRO MOUNTING KIT

Pack size: **1 x EA**

- Accessory Type: Mounting Kit
- For Use With: Motor



336214 Mounting Kit

MCLENNAN ADAPTER

Pack size: **1 x EA**

- Accessory Type: Adapter
- For Use With: Motor



718947 Adapter

MCLENNAN SERVO SUPPLIES 24 V 30 W SERVO MOTOR, 1600 RPM, 27 NCM

Pack size: **1 x EA**

- Maximum Output Torque: 27 Ncm
- Supply Voltage: 24 V dc
- Output Speed: 1600 rpm
- Power Rating: 30 W
- Stall Torque: 12 Nm
- Shaft Diameter: 6 mm
- Length: 64 mm
- Width: 66 mm



2635995 27 Ncm

RS PRO 2.2 KW SOFT STARTER, 230 V AC, 1 PHASE

Pack size: **1 x EA**

- Power Rating: 2.2 kW
- Motor Starter Type: Soft Start
- Voltage Rating: 230 V ac
- Phase: 1
- Current Rating: 12 A
- Overall Length: 120 mm
- Overall Width: 45 mm
- Overall Depth: 70 mm



2096340 2.2 kW

MOTOR, SERVO, 24VDC, 9NCM, C/W TACHO ASSEMBLY

Pack size: **1 x EA**

- Maximum Output Torque: 36 Ncm
- Supply Voltage: 24 → 30 V dc
- Output Speed: 1600 rpm
- Power Rating: 30 W
- Stall Torque: 14 Ncm
- Shaft Diameter: 6 mm
- Length: 134 mm
- Width: 66 mm



2636005 36 Ncm

RS PRO 2.2 KW SOFT STARTER, 400 V AC, 3 PHASE, IP20

Pack size: **1 x EA**

- Power Rating: 2.2 kW
- Motor Starter Type: Soft Start
- Voltage Rating: 460 V ac
- Phase: 3
- Current Rating: 5.5 A
- IP Rating: IP20
- Overall Length: 120 mm
- Overall Width: 45 mm



2096356 2.2 kW

RS PRO 2.2 KW SOFT STARTER, 400 V AC, 3 PHASE

Pack size: **1 x EA**

- Power Rating: 2.2 kW
- Motor Starter Type: Soft Start
- Voltage Rating: 460 V ac
- Phase: 3
- Current Rating: 5.5 A
- Overall Length: 120 mm
- Overall Width: 45 mm
- Overall Depth: 75 mm



2128683 2.2 kW

MCLENNAN SERVO SUPPLIES 24 → 30 V 30 W SERVO MOTOR, 1600 RPM, 36

Pack size: **1 x EA**

- Maximum Output Torque: 36 Ncm
- Supply Voltage: 24 → 30 V dc
- Output Speed: 1600 rpm
- Power Rating: 30 W
- Stall Torque: 12 Ncm
- Shaft Diameter: 6 mm
- Length: 88 mm
- Width: 66 mm



2636011 36 Ncm

RS PRO HYBRID STEPPER MOTOR, 12 V, UNIPOLAR, 1.8°, 6.35MM SHAFT

Pack size: **1 x EA**

- Stepper Motor Type: Hybrid
- Step Angle: 1.8°
- Number Of Wires: 6
- Supply Voltage: 12 V
- Frame Size: 56.4 x 56.4 mm
- Shaft Diameter: 6.35 mm
- Current Rating: 400 mA
- Winding Arrangement: Unipolar



1805281 Hybrid

RS PRO HYBRID STEPPER MOTOR, 9,6 V, UNIPOLAR, 1,8°, 5MM SHAFT

Pack size: **1 x EA**

- Stepper Motor Type: Hybrid
- Step Angle: 1.8°
- Number Of Wires: 6
- Supply Voltage: 9.6 V
- Frame Size: 42.3 x 42.3 mm
- Shaft Diameter: 5 mm
- Current Rating: 400 mA
- Winding Arrangement: Unipolar



1805278 Hybrid

RS PRO HYBRID STEPPER MOTOR, 12 V, UNIPOLAR, 1,8°, 5MM SHAFT

Pack size: **1 x EA**

- Stepper Motor Type: Hybrid
- Step Angle: 1.8°
- Number Of Wires: 6
- Supply Voltage: 12 V
- Frame Size: 42.3 x 42.3 mm
- Shaft Diameter: 5 mm
- Current Rating: 310 mA
- Winding Arrangement: Unipolar



1805279 Hybrid

RS PRO HYBRID STEPPER MOTOR, 6 V, UNIPOLAR, 1,8°, 6.35MM SHAFT

Pack size: **1 x EA**

- Stepper Motor Type: Hybrid
- Step Angle: 1.8°
- Number Of Wires: 6
- Supply Voltage: 6 V
- Frame Size: 56.4 x 56.4 mm
- Shaft Diameter: 6.35 mm
- Current Rating: 850 mA
- Winding Arrangement: Unipolar



1805282 Hybrid

RS PRO HYBRID STEPPER MOTOR, 12 V, UNIPOLAR, 1,8°, 6.35MM SHAFT

Pack size: **1 x EA**

- Stepper Motor Type: Hybrid
- Step Angle: 1.8°
- Number Of Wires: 6
- Supply Voltage: 12 V
- Frame Size: 56.4 x 56.4 mm
- Shaft Diameter: 6.35 mm
- Current Rating: 420 mA
- Winding Arrangement: Unipolar



1805283 Hybrid

RS PRO HYBRID STEPPER MOTOR, 1.65 V, 2.39 V, 3.42 V, PARALLEL,

Pack size: **1 x EA**

- Stepper Motor Type: Hybrid
- Step Angle: 1.8°
- Holding Torque: 2.6 [Unipolar] nm, 3.4 [Parallel] nm, 3.4 [Series] nm
- Number Of Wires: 8
- Supply Voltage: 1.65 V, 2.39 V, 3.42 V
- Frame Size: 85.85 x 85.85 mm
- Shaft Diameter: 12 mm
- Current Rating: 3 A, 4.2 A, 5.9 A



1805293 Hybrid

RS PRO HYBRID, PERMANENT MAGNET STEPPER MOTOR, 2.8 V,

Pack size: **1 x EA**

- Stepper Motor Type: Hybrid, Permanent Magnet
- Step Angle: 0.9°
- Holding Torque: 2.2 mNm
- Number Of Wires: 4
- Supply Voltage: 2.8 V
- Frame Size: 42.3 x 42.3 mm
- Shaft Diameter: 5 mm
- Current Rating: 1.33 A



5350372 Hybrid,

RS PRO HYBRID, PERMANENT MAGNET STEPPER MOTOR, 3.96 V,

Pack size: **1 x EA**

- Stepper Motor Type: Hybrid, Permanent Magnet
- Step Angle: 1.8°
- Holding Torque: 17.5 mNm
- Number Of Wires: 4
- Supply Voltage: 3.96 V
- Frame Size: 20.2 x 20.2 mm
- Shaft Diameter: 4 mm
- Current Rating: 600 mA



5350338 Hybrid,

RS PRO HYBRID, PERMANENT MAGNET STEPPER MOTOR, 3.8 V,

Pack size: **1 x EA**

- Stepper Motor Type: Hybrid, Permanent Magnet
- Step Angle: 1.8°
- Holding Torque: 60 mNm
- Number Of Wires: 4
- Supply Voltage: 3.8 V
- Frame Size: 28 x 28 mm
- Shaft Diameter: 5 mm
- Current Rating: 670 mA



5350344 Hybrid,

RS PRO HYBRID STEPPER MOTOR, 2.8 V, 0.44NM TORQUE, 0.9°, 5MM SHAFT

Pack size: **1 x EA**

- Stepper Motor Type: Hybrid
- Step Angle: 0.9°
- Holding Torque: 0.44 Nm
- Number Of Wires: 4
- Supply Voltage: 2.8 V
- Frame Size: 42.3 x 42.3 mm
- Shaft Diameter: 5 mm
- Current Rating: 1.68 A



5350401 Hybrid

RS PRO HYBRID, PERMANENT MAGNET STEPPER MOTOR, 2.8 V,

Pack size: **1 x EA**

- Stepper Motor Type: Hybrid, Permanent Magnet
- Step Angle: 1.8°
- Holding Torque: 0.22 Nm
- Number Of Wires: 4
- Supply Voltage: 2.8 V
- Frame Size: 42.3 x 42.3 mm
- Shaft Diameter: 5 mm
- Current Rating: 1.33 A



5350467 Hybrid,

RS PRO HYBRID, PERMANENT MAGNET STEPPER MOTOR, 2.3 V,

Pack size: **1 x EA**

- Stepper Motor Type: Hybrid, Permanent Magnet
- Step Angle: 1.8°
- Holding Torque: 1.0 Nm
- Number Of Wires: 4
- Supply Voltage: 2.3 V
- Frame Size: 56.4 x 56.4 mm
- Shaft Diameter: 6.35 mm
- Current Rating: 2.8 A



5350423 Hybrid,

RS PRO HYBRID, PERMANENT MAGNET STEPPER MOTOR, 3.2 V,

Pack size: **1 x EA**

- Stepper Motor Type: Hybrid, Permanent Magnet
- Step Angle: 1.8°
- Holding Torque: 1.89 Nm
- Number Of Wires: 4
- Supply Voltage: 3.2 V
- Frame Size: 56.4 x 56.4 mm
- Shaft Diameter: 6.35 mm
- Current Rating: 2.8 A



5350445 Hybrid,

RS PRO HYBRID, PERMANENT MAGNET STEPPER MOTOR, 2.64 V,

Pack size: **1 x EA**

- Stepper Motor Type: Hybrid, Permanent Magnet
- Step Angle: 1.8°
- Holding Torque: 65 mNm
- Number Of Wires: 4
- Supply Voltage: 2.64 V
- Frame Size: 39.2 x 39.2 mm
- Shaft Diameter: 5 mm
- Current Rating: 400 mA



8928729 Hybrid,

RS PRO HYBRID, PERMANENT MAGNET STEPPER MOTOR, 2.8 V,

Pack size: **1 x EA**

- Stepper Motor Type: Hybrid, Permanent Magnet
- Step Angle: 1.8°
- Holding Torque: 0.44 Nm
- Number Of Wires: 4
- Supply Voltage: 2.8 V
- Frame Size: 42.3 x 42.3 mm
- Shaft Diameter: 5 mm
- Current Rating: 1.68 A



5350489 Hybrid,

RS PRO HYBRID, PERMANENT MAGNET STEPPER MOTOR, 2.5 V,

Pack size: **1 x EA**

- Stepper Motor Type: Hybrid, Permanent Magnet
- Step Angle: 0.9°
- Holding Torque: 1.26 Nm
- Number Of Wires: 4
- Supply Voltage: 2.5 V
- Frame Size: 56.4 x 56.4 mm
- Shaft Diameter: 6.35 mm
- Current Rating: 2.8 A



5350502 Hybrid,

RS PRO HYBRID, PERMANENT MAGNET STEPPER MOTOR, 9 V,

Pack size: **1 x EA**

- Stepper Motor Type: Hybrid, Permanent Magnet
- Step Angle: 1.8°
- Holding Torque: 0.21 Nm
- Number Of Wires: 4
- Supply Voltage: 9 V
- Frame Size: 39.2 x 39.2 mm
- Shaft Diameter: 5 mm
- Current Rating: 600 mA



8928723 Hybrid,

**RS PRO SCREENED 1 CORE
MICROPHONE CABLE, 0.22 MM² CSA,**Pack size: **100 x MTR**

- Audio Cable Type: Microphone Cable
- Number of Cores: 1
- Cross Sectional Area: 0.22 mm²
- Screened/Unscreened: Screened
- Insulation Material: PE
- Outer Diameter: 3.1 mm
- Length: 100 m
- Fire Behaviour: Self-extinguishing

**2075312** Microphone**RS PRO SCREENED 4 CORE
MICROPHONE CABLE, 0.16 MM² CSA,**Pack size: **100 x MTR**

- Audio Cable Type: Microphone Cable
- Number of Cores: 4
- Cross Sectional Area: 0.16 mm²
- Screened/Unscreened: Screened
- Insulation Material: PVC
- Outer Diameter: 4.4 mm
- Length: 100 m
- Fire Behaviour: Self-extinguishing

**2075321** Microphone**RS PRO SCREENED 4 CORE
MICROPHONE CABLE, 0.22 MM² CSA,**Pack size: **100 x MTR**

- Audio Cable Type: Microphone Cable
- Number of Cores: 4
- Cross Sectional Area: 0.22 mm²
- Screened/Unscreened: Screened
- Insulation Material: PE
- Outer Diameter: 4.4 mm
- Length: 100 m
- Fire Behaviour: Self-extinguishing

**2075324** Microphone**RS PRO SCREENED 6 CORE
MICROPHONE CABLE, 0.22 MM² CSA,**Pack size: **100 x MTR**

- Audio Cable Type: Microphone Cable
- Number of Cores: 6
- Cross Sectional Area: 0.22 mm²
- Screened/Unscreened: Screened
- Insulation Material: PE
- Outer Diameter: 5.2 mm
- Length: 100 m
- Fire Behaviour: Self-extinguishing

**2075325** Microphone**RS PRO SCREENED 4 CORE
MICROPHONE CABLE, 0.15 MM² CSA,**Pack size: **50 x MTR**

- Audio Cable Type: Microphone Cable
- Number of Cores: 4
- Cross Sectional Area: 0.15 mm²
- Screened/Unscreened: Screened
- Insulation Material: PVC
- Outer Diameter: 4.7 mm
- Length: 50 m
- Fire Behaviour: Self-extinguishing

**2075323** Microphone**RS PRO SCREENED 2 CORE
MICROPHONE CABLE, 0.22 MM² CSA,**Pack size: **100 x MTR**

- Audio Cable Type: Microphone Cable
- Number of Cores: 2
- Cross Sectional Area: 0.22 mm²
- Screened/Unscreened: Screened
- Insulation Material: PE
- Outer Diameter: 3.7 mm
- Length: 100 m
- Minimum Operating Temperature: -20 °C

**2075319** Microphone**RS PRO SCREENED 3 CORE
MICROPHONE CABLE, 0.22 MM² CSA,**Pack size: **100 x MTR**

- Audio Cable Type: Microphone Cable
- Number of Cores: 3
- Cross Sectional Area: 0.22 mm²
- Screened/Unscreened: Screened
- Insulation Material: PE
- Outer Diameter: 4 mm
- Length: 100 m
- Fire Behaviour: Self-extinguishing

**2075320** Microphone**RS PRO SCREENED 1 CORE
MICROPHONE CABLE, 0.22 MM² CSA,**Pack size: **25 x MTR**

- Audio Cable Type: Microphone Cable
- Number of Cores: 1
- Cross Sectional Area: 0.22 mm²
- Screened/Unscreened: Screened
- Insulation Material: PE
- Outer Diameter: 4.5 mm
- Length: 25 m
- Fire Behaviour: Self-extinguishing

**2075329** Microphone**RS PRO MALE FEMALE TV AERIAL
CABLE, RG59/U, 75 Ω, 1.5M**Pack size: **1 x MTR**

- Terminated/Unterminated: Terminated
- Coaxial Type: RG59/U
- Connector 1 Gender: Male
- Connector 2 Gender: Female
- Characteristic Impedance: 75 Ω
- Length: 1.5 m
- Sheath Colour: Grey
- Insulation Material: PVC

**1115462** Terminated**RS PRO MALE FEMALE TV AERIAL
CABLE, 75 Ω, 3.5M**Pack size: **3 x MTR**

- Terminated/Unterminated: Terminated
- Connector 1 Gender: Male
- Connector 2 Gender: Female
- Characteristic Impedance: 75 Ω
- Length: 3.5 m
- Sheath Colour: Grey
- Shielding: Shielded
- Insulation Material: PVC

**1115478** Terminated**RS PRO COAXIAL CABLE, RG59, 75 Ω,
100M**Pack size: **100 x MTR**

- Terminated/Unterminated: Unterminated
- Coaxial Type: RG59
- Outer Diameter: 6.1 mm
- Characteristic Impedance: 75 Ω
- Length: 100 m
- Sheath Colour: Black
- Sheath Material: PVC
- Operating Temperature Range: -10 °C→+70 °C

**2163679** Unterminated**RS PRO COAXIAL CABLE, RG58, 50 Ω,
100M**Pack size: **100 x MTR**

- Terminated/Unterminated: Unterminated
- Coaxial Type: RG58
- Outer Diameter: 4.95 mm
- Characteristic Impedance: 50 Ω
- Length: 100 m
- Sheath Colour: Black
- Sheath Material: PVC
- Operating Temperature Range: -10 °C→+70 °C

**2163678** Unterminated**RS PRO COAXIAL CABLE, RG174A/U,
50 Ω, 20M**Pack size: **20 x MTR**

- Terminated/Unterminated: Unterminated
- Coaxial Type: RG174A/U
- Outer Diameter: 2.79 mm
- Characteristic Impedance: 50 Ω
- Attenuation: 220 dB/100m @ 3GHz, 42 dB/100m @ 200MHz, 60 dB/100m @ 400MHz
- Length: 20 m
- Sheath Colour: Black
- Conductor Strand Type: Stranded

**2228610** Unterminated**RS PRO COAXIAL CABLE, RG58, 50 Ω,
500M**Pack size: **500 x MTR**

- Terminated/Unterminated: Unterminated
- Coaxial Type: RG58
- Outer Diameter: 4.95 mm
- Characteristic Impedance: 50 Ω
- Attenuation: 4.7 dB/100m
- Length: 500 m
- Sheath Colour: White
- Conductor Strand Type: Stranded

**5217916** Unterminated**RS PRO COAXIAL CABLE, RG179, 75 Ω,
50M**Pack size: **50 x MTR**

- Terminated/Unterminated: Unterminated
- Coaxial Type: RG179
- Outer Diameter: 2.8 mm
- Characteristic Impedance: 75 Ω
- Attenuation: 52.5 dB/100m @ 400MHz, 64.6 dB/100m @ 700MHz, 73.2 dB/100m @ 900MHz, 78.7 dB/100m @ 1GHz
- Length: 50 m
- Sheath Colour: Black
- Conductor Strand Type: Stranded

**5217950** Unterminated**RS PRO COAXIAL CABLE, RG62A/U,
93 Ω, 100M**Pack size: **100 x MTR**

- Terminated/Unterminated: Unterminated
- Coaxial Type: RG62A/U
- Outer Diameter: 6.07 mm
- Characteristic Impedance: 93 Ω
- Attenuation: 17.4 dB/100m @ 400MHz, 23.9 dB/100m @ 700MHz, 26.9 dB/100m @ 900MHz, 28.5 dB/100m @ 1GHz
- Length: 100 m
- Sheath Colour: Black
- Conductor Strand Type: Solid

**5218010** Unterminated

RS PRO COAXIAL CABLE, RG62A/U, 93 Ω, 100M

Pack size: **100 x MTR**

- Terminated/Unterminated: Unterminated
- Coaxial Type: RG62A/U
- Outer Diameter: 6.15 mm
- Characteristic Impedance: 93 Ω
- Attenuation: 0.125 dB/m
- Length: 100 m
- Sheath Colour: Black
- Fire Behaviour: Flame Retardant



5218032 Unterminated

RS PRO COAXIAL CABLE, RG178B/U, 50 Ω

Pack size: **100 x MTR**

- Terminated/Unterminated: Unterminated
- Coaxial Type: RG178B/U
- Outer Diameter: 1.85 mm
- Characteristic Impedance: 50 Ω
- Attenuation: 151 dB @ 1GHz
- Sheath Colour: Brown
- Conductor Strand Type: Stranded
- Operating Temperature Range: -70 → +200 °C



9060635 Unterminated

RS PRO DATA CABLE, 0.14 MM², SCREENED, GREY, 26 AWG

Pack size: **50 x MTR**

- Cross Sectional Area: 0.14 mm²
- Screened/Unscreened: Screened
- Sheath Colour: Grey
- American Wire Gauge: 26 AWG
- Outer Diameter: 7.50 mm
- Voltage Rating: 250 V
- Shielded/Unshielded: Shielded



1959503 0.14 mm²

WIRE, ANNEALED COPPER, TINNED, 16 SWG, BS4109, 200G, FUSEWIRE 70A

Pack size: **1 x EA**

- Cross Sectional Area: 1.3 mm²
- American Wire Gauge: 16 AWG
- Core Strands: 1/1.63 mm
- Outer Diameter: 1.63 mm
- Length: 11.4 m
- Finish: Tinned
- Wire Style: BS EN13602
- Shield Type: Unshielded



355041 1.3 mm²

WIRE, ANNEALED COPPER, TINNED, 18 SWG, BS4109, 200G, FUSEWIRE 45A

Pack size: **1 x EA**

- Cross Sectional Area: 1.1 mm²
- American Wire Gauge: 17 AWG
- Core Strands: 1/1.22 mm
- Outer Diameter: 1.22 mm
- Length: 20.2 m
- Finish: Tinned
- Wire Style: BS EN13602
- Shield Type: Unshielded



355057 1.1 mm²

WIRE, ANNEALED COPPER, TINNED, 22 SWG, BS4109, 200G, FUSEWIRE 25A

Pack size: **1 x EA**

- Cross Sectional Area: 0.4 mm²
- American Wire Gauge: 21 AWG
- Core Strands: 1/0.71 mm
- Outer Diameter: 0.71 mm
- Length: 50.9 m
- Finish: Tinned
- Wire Style: BS EN13602
- Shield Type: Unshielded



355079 0.4 mm²

WIRE, ANNEALED COPPER, TINNED, 20 SWG, BS4109, 200G, FUSEWIRE 33A

Pack size: **1 x EA**

- Cross Sectional Area: 0.7 mm²
- American Wire Gauge: 19 AWG
- Core Strands: 1/0.91 mm
- Outer Diameter: 0.91 mm
- Length: 34.6 m
- Finish: Tinned
- Wire Style: BS EN13602
- Shield Type: Unshielded



355063 0.7 mm²

WIRE, ANNEALED COPPER, TINNED, 24 SWG, BS4109, 200G, FUSEWIRE 17A

Pack size: **1 x EA**

- Cross Sectional Area: 0.2 mm²
- American Wire Gauge: 24 AWG
- Core Strands: 1/0.56 mm
- Outer Diameter: 0.56 mm
- Length: 91.3 m
- Finish: Tinned
- Wire Style: BS EN13602
- Shield Type: Unshielded



355085 0.2 mm²

WIRE, COPPER, SOLID, POLYURETHANE INSULATED, BS4520, 500G, 0.25MM

Pack size: **1 x EA**

- Cross Sectional Area: 0.05 mm²
- American Wire Gauge: 30 AWG
- Core Strands: 1/0.25 mm
- Insulation Material: PUR
- Outer Diameter: 0.25 mm
- Length: 1100 m
- Finish: Enamelled
- Wire Style: EN 60317/20



357716 0.05 mm²

WIRE, COPPER, SOLID, POLYURETHANE INSULATED, BS4520, 500G, 0.315MM

Pack size: **1 x EA**

- Cross Sectional Area: 0.08 mm²
- American Wire Gauge: 28 AWG
- Core Strands: 1/0.31 mm
- Insulation Material: PUR
- Outer Diameter: 0.37 mm
- Length: 700 m
- Finish: Enamelled
- Wire Style: EN 60317/20



357722 0.08 mm²

WIRE, COPPER, SOLID, POLYURETHANE INSULATED, BS4520, 500G, 0.4MM

Pack size: **1 x EA**

- Cross Sectional Area: 0.13 mm²
- American Wire Gauge: 26 AWG
- Core Strands: 1/0.4 mm
- Insulation Material: PUR
- Outer Diameter: 0.45 mm
- Length: 400 m
- Finish: Enamelled
- Wire Style: EN 60317/20



357738 0.13 mm²

WIRE, COPPER, SOLID, POLYURETHANE INSULATED, BS4520, 500G, 0.5MM

Pack size: **1 x EA**

- Cross Sectional Area: 0.2 mm²
- American Wire Gauge: 24 AWG
- Core Strands: 1/0.5 mm
- Insulation Material: PUR
- Outer Diameter: 0.5 mm
- Length: 286 m
- Finish: Enamelled
- Wire Style: EN 60317/20



357744 0.2 mm²

WIRE, COPPER, SOLID, POLYURETHANE INSULATED, BS4520, 500G, 0.56MM

Pack size: **1 x EA**

- Cross Sectional Area: 0.26 mm²
- American Wire Gauge: 23 AWG
- Core Strands: 1/0.56 mm
- Insulation Material: PUR
- Outer Diameter: 0.62 mm
- Length: 200 m
- Finish: Enamelled
- Wire Style: EN 60317/20



357750 0.26 mm²

WIRE, COPPER, SOLID, POLYURETHANE INSULATED, BS4520, 500G, 0.71MM

Pack size: **1 x EA**

- Cross Sectional Area: 0.4 mm²
- American Wire Gauge: 21 AWG
- Core Strands: 1/0.71 mm
- Insulation Material: PUR
- Outer Diameter: 0.78 mm
- Length: 120 m
- Finish: Enamelled
- Wire Style: EN 60317/20



357766 0.4 mm²

WIRE, COPPER, SOLID, POLYURETHANE INSULATED, BS4520, 500G, 0.81MM

Pack size: **1 x EA**

- Cross Sectional Area: 0.52 mm²
- American Wire Gauge: 20 AWG
- Core Strands: 1/0.8 mm
- Insulation Material: PUR
- Outer Diameter: 0.87 mm
- Length: 100 m
- Finish: Enamelled
- Wire Style: EN 60317/20



357772 0.52 mm²

WIRE, COPPER, SOLID, POLYURETHANE INSULATED, BS4520, 500G, 1.0MM

Pack size: **1 x EA**

- Cross Sectional Area: 0.82 mm²
- American Wire Gauge: 18 AWG
- Core Strands: 1/1.0 mm
- Insulation Material: PUR
- Outer Diameter: 1.08 mm
- Length: 80 m
- Finish: Enamelled
- Wire Style: EN 60317/20



357788 0.82 mm²

WIRE, COPPER, SOLID, POLYURETHANE INSULATED, BS4520, 500G, 1.25MMPack size: **1 x EA**

- Cross Sectional Area: 1.3 mm²
- American Wire Gauge: 16 AWG
- Core Strands: 1/1.25 mm
- Insulation Material: PUR
- Outer Diameter: 1.33 mm
- Length: 40 m
- Finish: Enamelled
- Wire Style: EN 60317/20

**357794** 1.3 mm²**WIRE, COPPER, SOLID, POLYURETHANE INSULATED, BS4520, 500G, 0.2MM**Pack size: **1 x EA**

- Cross Sectional Area: 0.03 mm²
- American Wire Gauge: 32 AWG
- Core Strands: 1/0.2 mm
- Insulation Material: PUR
- Outer Diameter: 0.23 mm
- Length: 1600 m
- Finish: Enamelled
- Wire Style: EN 60317/20

**357918** 0.03 mm²**WIRE, COPPER, SOLID, POLYURETHANE INSULATED, BS4520, 500G, 0.244MM**Pack size: **1 x EA**

- Cross Sectional Area: 0.04 mm²
- American Wire Gauge: 31 AWG
- Core Strands: 1/0.22 mm
- Insulation Material: PUR
- Outer Diameter: 0.26 mm
- Length: 1300 m
- Finish: Enamelled
- Wire Style: EN 60317/20

**357924** 0.04 mm²**WIRE, COPPER, SOLID, POLYURETHANE INSULATED, BS4520, 500G, 1.5MM**Pack size: **1 x EA**

- Cross Sectional Area: 1.5 mm²
- American Wire Gauge: 15 AWG
- Core Strands: 1/1.5 mm
- Insulation Material: PUR
- Outer Diameter: 1.59 mm
- Length: 30 m
- Finish: Enamelled
- Wire Style: EN 60317/20

**357930** 1.5 mm²**WIRE, ANNEALED COPPER, TINNED, 14SWG, BS4109, 200**Pack size: **1 x EA**

- Cross Sectional Area: 3.3 mm²
- American Wire Gauge: 12 AWG
- Core Strands: 1/2.03 mm
- Outer Diameter: 2.03 mm
- Length: 7.1 m
- Finish: Tinned
- Wire Style: BS EN13602
- Shield Type: Unshielded

**390527** 3.3 mm²**WIRE, ANNEALED COPPER, TINNED, 25SWG, BS4109, 200**Pack size: **1 x EA**

- Cross Sectional Area: 0.2 mm²
- American Wire Gauge: 24 AWG
- Core Strands: 1/0.51 mm
- Outer Diameter: 0.51 mm
- Length: 114 m
- Finish: Tinned
- Wire Style: BS EN13602
- Shield Type: Unshielded

**390549** 0.2 mm²**WIRE, ANNEALED COPPER, TINNED, 29SWG, BS4109, 200**Pack size: **1 x EA**

- Cross Sectional Area: 0.08 mm²
- American Wire Gauge: 28 AWG
- Core Strands: 1/0.35 mm
- Outer Diameter: 0.35 mm
- Length: 256 m
- Finish: Tinned
- Wire Style: BS EN13602
- Shield Type: Unshielded

**390555** 0.08 mm²**WIRE, ANNEALED COPPER, TINNED, 35SWG, BS4109, 200**Pack size: **1 x EA**

- Cross Sectional Area: 0.03 mm²
- American Wire Gauge: 32 AWG
- Core Strands: 1/0.20 mm
- Outer Diameter: 0.21 mm
- Length: 717 m
- Finish: Tinned
- Wire Style: BS EN13602
- Shield Type: Unshielded

**390561** 0.03 mm²**RS PRO CAT5E ETHERNET CABLE, F/UTP SHIELD, GREY PVC SHEATH,**Pack size: **305 x MTR**

- LAN Category: Cat5e
- Terminated/Unterminated: Unterminated
- Length: 305 m
- Outer Sheath Material: PVC
- Shield Type: F/UTP
- Sheath Colour: Grey
- American Wire Gauge: 24 AWG
- Outer Diameter: 5 mm

**556865** Cat5e**RS PRO CAT5E ETHERNET CABLE, F/UTP SHIELD, PURPLE PVC SHEATH,**Pack size: **305 x MTR**

- LAN Category: Cat5e
- Terminated/Unterminated: Unterminated
- Length: 305 m
- Core Strands: 1/24
- Shield Type: F/UTP
- Outer Sheath Material: PVC
- Sheath Colour: Purple
- Fire Behaviour: Low Smoke Zero Halogen (LSZH)

**556869** Cat5e**RS PRO CAT6 ETHERNET CABLE, F/UTP SHIELD, PURPLE LSZH SHEATH,**Pack size: **305 x MTR**

- LAN Category: Cat6
- Terminated/Unterminated: Unterminated
- Length: 305 m
- Core Strands: 1/23
- Shield Type: F/UTP
- Outer Sheath Material: LSZH
- Sheath Colour: Purple
- Fire Behaviour: Low Smoke Zero Halogen (LSZH)

**556875** Cat6**RS PRO CAT5E ETHERNET CABLE, U/UTP SHIELD, PURPLE LSZH SHEATH,**Pack size: **305 x MTR**

- LAN Category: Cat5e
- Terminated/Unterminated: Unterminated
- Length: 305 m
- Core Strands: 1/24
- Shield Type: U/UTP
- Outer Sheath Material: LSZH
- Sheath Colour: Purple
- Fire Behaviour: Low Smoke Zero Halogen (LSZH)

**557193** Cat5e**RS PRO CAT5E ETHERNET CABLE, F/UTP SHIELD, GREY PVC SHEATH,**Pack size: **305 x MTR**

- LAN Category: Cat5e
- Terminated/Unterminated: Unterminated
- Length: 305 m
- Core Strands: 1/24
- Shield Type: F/UTP
- Outer Sheath Material: PVC
- Sheath Colour: Grey
- Conductor Strand Type: Solid

**557212** Cat5e**RS PRO CAT5E ETHERNET CABLE, U/UTP SHIELD, GREY PVC SHEATH,**Pack size: **305 x MTR**

- LAN Category: Cat5e
- Terminated/Unterminated: Unterminated
- Length: 305 m
- Core Strands: 1/24
- Shield Type: U/UTP
- Outer Sheath Material: PVC
- Sheath Colour: Grey
- Attenuation: ≥40 dB

**557470** Cat5e**RS PRO CAT6A ETHERNET CABLE, U/FTP SHIELD, GREY PVC SHEATH,**Pack size: **100 x MTR**

- LAN Category: Cat6a
- Terminated/Unterminated: Unterminated
- Length: 100 m
- Shield Type: U/FTP
- Outer Sheath Material: PVC
- Sheath Colour: Grey
- Attenuation: 45.3 dB/100m
- Standards Met: Euroclass Eca

**1135901** Cat6a**RS PRO CAT6A ETHERNET CABLE, SF/FTP SHIELD, GREY PVC SHEATH,**Pack size: **100 x MTR**

- LAN Category: Cat6a
- Terminated/Unterminated: Unterminated
- Length: 100 m
- Shield Type: SF/FTP
- Outer Sheath Material: PVC
- Sheath Colour: Grey
- Attenuation: 45.3 dB/100m
- Standards Met: Euroclass Eca

**1135902** Cat6a

RS PRO CAT7 ETHERNET CABLE, U/FTP SHIELD, BLACK PVC SHEATH,

Pack size: **100 x MTR**

- LAN Category: Cat7
- Terminated/Unterminated: Unterminated
- Length: 100 m
- Shield Type: U/FTP
- Outer Sheath Material: PVC
- Sheath Colour: Black
- Attenuation: 50.1 dB/100m
- Standards Met: Euroclass Eco



1135903 Cat7

RS PRO CAT7 ETHERNET CABLE, U/FTP SHIELD, BLACK LSZH SHEATH,

Pack size: **100 x MTR**

- LAN Category: Cat7
- Terminated/Unterminated: Unterminated
- Length: 100 m
- Outer Sheath Material: LSZH
- Shield Type: U/FTP
- Sheath Colour: Black
- Fire Behaviour: Low Smoke Zero Halogen (LSZH)
- Attenuation: 61.9 dB/100m



1135904 Cat7

RS PRO CAT7 ETHERNET CABLE, SF/FTP SHIELD, BLACK PVC SHEATH,

Pack size: **100 x MTR**

- LAN Category: Cat7
- Terminated/Unterminated: Unterminated
- Length: 100 m
- Outer Sheath Material: PVC
- Shield Type: SF/FTP
- Sheath Colour: Black
- Attenuation: 50.1 dB/100m
- American Wire Gauge: 23 AWG



1135905 Cat7

RS PRO CAT7 ETHERNET CABLE, U/FTP SHIELD, GREY PVC SHEATH,

Pack size: **100 x MTR**

- LAN Category: Cat7
- Terminated/Unterminated: Unterminated
- Length: 100 m
- Shield Type: U/FTP
- Outer Sheath Material: PVC
- Sheath Colour: Grey
- Attenuation: 50.1 dB/100m
- Standards Met: Euroclass Eco



1135906 Cat7

RS PRO CAT7 ETHERNET CABLE, SF/FTP SHIELD, GREY PVC SHEATH,

Pack size: **100 x MTR**

- LAN Category: Cat7
- Terminated/Unterminated: Unterminated
- Length: 100 m
- Outer Sheath Material: PVC
- Shield Type: SF/FTP
- Sheath Colour: Grey
- Attenuation: 50.1 dB/100m
- American Wire Gauge: 23 AWG



1135908 Cat7

RS PRO CAT7A ETHERNET CABLE, U/FTP SHIELD, BLACK PVC SHEATH,

Pack size: **100 x MTR**

- LAN Category: Cat7a
- Terminated/Unterminated: Unterminated
- Length: 100 m
- Shield Type: U/FTP
- Outer Sheath Material: PVC
- Sheath Colour: Black
- Attenuation: 61.9 dB/100m
- Standards Met: Euroclass Eco



1135909 Cat7a

RS PRO CAT7A ETHERNET CABLE, U/FTP SHIELD, BLACK LSZH SHEATH,

Pack size: **100 x MTR**

- LAN Category: Cat7a
- Terminated/Unterminated: Unterminated
- Length: 100 m
- Shield Type: U/FTP
- Outer Sheath Material: LSZH
- Sheath Colour: Black
- Fire Behaviour: Low Smoke Zero Halogen (LSZH)
- Attenuation: 61.9 dB/100m



1135910 Cat7a

RS PRO CAT6 ETHERNET CABLE, RJ45 TO RJ45, F/UTP SHIELD, GREY PVC

Pack size: **1 x EA**

- Connector 1: RJ45
- LAN Category: Cat6
- Terminated/Unterminated: Terminated
- Connector 2: RJ45
- Connector 1 Gender: Male
- Connector 2 Gender: Male
- Length: 1 m
- Shield Type: F/UTP



2010530 RJ45

RS PRO CAT6 ETHERNET CABLE, RJ45 TO RJ45, F/UTP SHIELD, GREY PVC

Pack size: **1 x EA**

- Connector 1: RJ45
- LAN Category: Cat6
- Terminated/Unterminated: Terminated
- Connector 2: RJ45
- Connector 1 Gender: Male
- Connector 2 Gender: Male
- Length: 2 m
- Shield Type: F/UTP



2010531 RJ45

RS PRO CAT6 ETHERNET CABLE, RJ45 TO RJ45, F/UTP SHIELD, GREY PVC

Pack size: **1 x EA**

- Connector 1: RJ45
- LAN Category: Cat6
- Terminated/Unterminated: Terminated
- Connector 2: RJ45
- Connector 1 Gender: Male
- Connector 2 Gender: Male
- Length: 5 m
- Shield Type: F/UTP



2010533 RJ45

RS PRO CAT6A ETHERNET CABLE, RJ45 TO RJ45, U/FTP SHIELD, GREY

Pack size: **1 x EA**

- Connector 1: RJ45
- LAN Category: Cat6a
- Connector 2: RJ45
- Terminated/Unterminated: Terminated
- Connector 1 Gender: Male
- Connector 2 Gender: Male
- Length: 1 m
- Shield Type: U/FTP



2010534 RJ45

RS PRO CAT6A ETHERNET CABLE, RJ45 TO RJ45, U/FTP SHIELD, GREY

Pack size: **1 x EA**

- Connector 1: RJ45
- LAN Category: Cat6a
- Connector 2: RJ45
- Terminated/Unterminated: Terminated
- Connector 1 Gender: Male
- Connector 2 Gender: Male
- Length: 2 m
- Shield Type: U/FTP



2010535 RJ45

RS PRO CAT6 ETHERNET CABLE, U/UTP SHIELD, WHITE LSZH SHEATH,

Pack size: **100 x MTR**

- LAN Category: Cat6
- Terminated/Unterminated: Unterminated
- Length: 100 m
- Outer Sheath Material: LSZH
- Shield Type: U/UTP
- Sheath Colour: White
- Fire Behaviour: Low Smoke Zero Halogen (LSZH)



2097614 Cat6

RS PRO CAT5 ETHERNET CABLE, U/UTP SHIELD, YELLOW PVC SHEATH,

Pack size: **50 x MTR**

- LAN Category: Cat5
- Terminated/Unterminated: Unterminated
- Length: 50 m
- Core Strands: 7/0.16
- Shield Type: U/UTP
- Outer Sheath Material: PVC
- Sheath Colour: Yellow
- Attenuation: 37.4 dB



8124785 Cat5

RS PRO CAT5 ETHERNET CABLE, U/UTP SHIELD, RED PVC SHEATH, 50M

Pack size: **50 x MTR**

- LAN Category: Cat5
- Terminated/Unterminated: Unterminated
- Length: 50 m
- Core Strands: 7/0.16
- Shield Type: U/UTP
- Outer Sheath Material: PVC
- Sheath Colour: Red
- Attenuation: 37.4 dB



8124788 Cat5

RS PRO CAT5 ETHERNET CABLE, U/UTP SHIELD, BLUE PVC SHEATH,

Pack size: **50 x MTR**

- LAN Category: Cat5
- Terminated/Unterminated: Unterminated
- Length: 50 m
- Core Strands: 7/0.16
- Shield Type: U/UTP
- Outer Sheath Material: PVC
- Sheath Colour: Blue
- Attenuation: 37.4 dB



8124781 Cat5

**RS PRO CAT5E ETHERNET CABLE,
S/UTP SHIELD, GREY PVC SHEATH,**Pack size: **305 x MTR**

- LAN Category: Cat5e
- Terminated/Unterminated: Unterminated
- Length: 305 m
- Core Strands: 7/016
- Outer Sheath Material: PVC
- Shield Type: S/UTP
- Sheath Colour: Grey
- Attenuation: 37.4 dB

**8124791** Cat5e**RS PRO CAT5 ETHERNET CABLE,
U/UTP SHIELD, GREEN PVC SHEATH,**Pack size: **50 x MTR**

- LAN Category: Cat5
- Terminated/Unterminated: Unterminated
- Length: 50 m
- Core Strands: 7/0.16
- Shield Type: U/UTP
- Outer Sheath Material: PVC
- Sheath Colour: Green
- Attenuation: 37.4 dB

**8124794** Cat5**RS PRO CAT5E ETHERNET CABLE,
U/UTP SHIELD, GREY PVC SHEATH,**Pack size: **100 x MTR**

- LAN Category: Cat5e
- Terminated/Unterminated: Unterminated
- Length: 100 m
- Core Strands: 7/016
- Shield Type: U/UTP
- Outer Sheath Material: PVC
- Sheath Colour: Grey
- Attenuation: 37.4 dB

**8124797** Cat5e**RS PRO CAT5E ETHERNET CABLE,
F/UTP SHIELD, GREY PVC SHEATH,**Pack size: **100 x MTR**

- LAN Category: Cat5e
- Terminated/Unterminated: Unterminated
- Length: 100 m
- Core Strands: 7/016
- Shield Type: F/UTP
- Outer Sheath Material: PVC
- Sheath Colour: Grey
- Attenuation: 37.4 dB

**8124801** Cat5e**RS PRO CAT5E ETHERNET CABLE,
U/UTP SHIELD, PURPLE PVC SHEATH,**Pack size: **305 x MTR**

- LAN Category: Cat5e
- Terminated/Unterminated: Unterminated
- Length: 305 m
- Core Strands: 8/0.5
- Shield Type: U/UTP
- Outer Sheath Material: PVC
- Sheath Colour: Purple
- Fire Behaviour: Low Smoke Zero Halogen (LSZH)

**9164080** Cat5e**RS PRO CAT6 ETHERNET CABLE,
U/UTP SHIELD, GREY PVC SHEATH,**Pack size: **305 x MTR**

- LAN Category: Cat6
- Terminated/Unterminated: Unterminated
- Length: 305 m
- Core Strands: 8/0.57
- Shield Type: U/UTP
- Outer Sheath Material: PVC
- Sheath Colour: Grey
- Standards Met: RoHS Compliant

**9164087** Cat6**RS PRO CAT6 ETHERNET CABLE,
U/UTP SHIELD, YELLOW PVC SHEATH,**Pack size: **305 x MTR**

- LAN Category: Cat6
- Terminated/Unterminated: Unterminated
- Length: 305 m
- Core Strands: 8/0.57
- Shield Type: U/UTP
- Outer Sheath Material: PVC
- Sheath Colour: Yellow
- Fire Behaviour: Low Smoke Zero Halogen (LSZH)

**9164093** Cat6**RS PRO CAT6 ETHERNET CABLE,
U/UTP SHIELD, PURPLE PVC SHEATH,**Pack size: **305 x MTR**

- LAN Category: Cat6
- Terminated/Unterminated: Unterminated
- Length: 305 m
- Core Strands: 8/0.57
- Shield Type: U/UTP
- Outer Sheath Material: PVC
- Sheath Colour: Purple
- Fire Behaviour: Low Smoke Zero Halogen (LSZH)

**9164096** Cat6**RS PRO CAT6 ETHERNET CABLE,
U/UTP SHIELD, BLACK PE SHEATH,**Pack size: **100 x MTR**

- LAN Category: Cat6
- Terminated/Unterminated: Unterminated
- Length: 100 m
- Core Strands: 8/0.57
- Shield Type: U/UTP
- Outer Sheath Material: PE
- Sheath Colour: Black
- Standards Met: RoHS Compliant

**9164103** Cat6**RS PRO CAT6 ETHERNET CABLE,
U/UTP SHIELD, BLUE PVC SHEATH,**Pack size: **305 x MTR**

- LAN Category: Cat6
- Terminated/Unterminated: Unterminated
- Length: 305 m
- Core Strands: 8/0.57
- Shield Type: U/UTP
- Outer Sheath Material: PVC
- Sheath Colour: Blue
- Fire Behaviour: Low Smoke Zero Halogen (LSZH)

**9164099** Cat6**RS PRO FEMALE CAT6A RJ45
CONNECTOR**Pack size: **8 x EA**

- Gender: Female
- Ethernet Connector Type: RJ45 Connector
- LAN Category: Cat6a
- Mounting Type: Tool-less Cable Mounting
- Number of Ports: 1
- Number of Ways: 1
- Shield Type: 360° Shielded
- Contact Material: Bronze

**2010529** Female**RS PRO DUPLEX MULTI MODE OM3
FIBRE OPTIC CABLE, 6.5MM, BLACK,**Pack size: **250 x MTR**

- Length: 250 m
- Propagation Mode: Multi Mode
- Terminated/Unterminated: Unterminated
- Core Diameter: 6.5 mm
- Number of Cores: 8
- Sheath Colour: Black
- Cable Construction: Duplex
- Fibre Type: OM3

**1235717** 250 m**RS PRO SIMPLEX FIBRE OPTIC CABLE,
980MM, BLACK, 20M**Pack size: **20 x MTR**

- Length: 20 m
- Terminated/Unterminated: Unterminated
- Core Diameter: 980 µm
- Number of Cores: 2
- Sheath Colour: Black
- Cable Construction: Simplex
- Maximum Operating Temperature: +85 °C
- Minimum Operating Temperature: -45 °C

**1644255** 20 m**RS PRO MULTI MODE FIBRE OPTIC
CABLE, 0.0625MM, BLACK, 500M**Pack size: **500 x MTR**


- Length: 500 m
- Propagation Mode: Multi Mode
- Terminated/Unterminated: Unterminated
- Core Diameter: 0.0625 mm
- Number of Cores: 4
- Sheath Colour: Black
- Fire Behaviour: Low Smoke Zero Halogen (LSZH)
- Sheath Material: Low Smoke Zero Halogen (LSZH)

**2908861** 500 m**RS PRO SIMPLEX FIBRE OPTIC CABLE,
980MM, BLACK, 20M**Pack size: **20 x MTR**

- Length: 20 m
- Terminated/Unterminated: Unterminated
- Core Diameter: 980 µm
- Number of Cores: 1
- Sheath Colour: Black
- Cable Construction: Simplex
- Maximum Operating Temperature: +85 °C
- Minimum Operating Temperature: -45 °C

**1644254** 20 m**RS PRO BLUE 0.13 MM² EQUIPMENT
WIRE, 26 AWG, 1/0.4 MM, 100M, ETFE**Pack size: **100 x MTR**

- Cross Sectional Area: 0.13 mm²
- Sheath Colour: Blue
- American Wire Gauge: 26 AWG
- Core Strands: 1/0.4 mm
- Length: 100 m
- Insulation Material: ETFE
- Outer Diameter: 0.71 mm
- Voltage Rating: 375 V

**354060** 0.13 mm²

RS PRO BLACK 0.13 MM² EQUIPMENT WIRE, 26 AWG, 1/0.4 MM, 100M, ETFE

Pack size: **100 x MTR**

- Cross Sectional Area: 0.13 mm²
- Sheath Colour: Black
- American Wire Gauge: 26 AWG
- Core Strands: 1/0.4 mm
- Length: 100 m
- Insulation Material: ETFE
- Voltage Rating: 375 V
- Outer Diameter: 0.71 mm



354076 0.13 mm²

RS PRO WHITE 0.13 MM² EQUIPMENT WIRE, 26 AWG, 1/0.4 MM, 100M, ETFE

Pack size: **100 x MTR**

- Cross Sectional Area: 0.13 mm²
- Sheath Colour: White
- American Wire Gauge: 26 AWG
- Core Strands: 1/0.4 mm
- Length: 100 m
- Insulation Material: ETFE
- Voltage Rating: 375 V
- Outer Diameter: 0.71 mm



354098 0.13 mm²

RS PRO RED 0.13 MM² EQUIPMENT WIRE, 26 AWG, 1/0.4 MM, 100M, ETFE

Pack size: **100 x MTR**

- Cross Sectional Area: 0.13 mm²
- Sheath Colour: Red
- American Wire Gauge: 26 AWG
- Core Strands: 1/0.4 mm
- Length: 100 m
- Insulation Material: ETFE
- Voltage Rating: 375 V
- Outer Diameter: 0.71 mm



354054 0.13 mm²

RS PRO RED 0.05 MM² EQUIPMENT WIRE, 30 AWG, 1/0.25 MM, 100M,

Pack size: **100 x MTR**

- Cross Sectional Area: 0.05 mm²
- Sheath Colour: Red
- American Wire Gauge: 30 AWG
- Core Strands: 1/0.25 mm
- Length: 100 m
- Insulation Material: ETFE
- Voltage Rating: 375 V
- Outer Diameter: 0.56 mm



359835 0.05 mm²

RS PRO BLUE 0.05 MM² EQUIPMENT WIRE, 30 AWG, 1/0.25 MM, 100M,

Pack size: **100 x MTR**

- Cross Sectional Area: 0.05 mm²
- Sheath Colour: Blue
- American Wire Gauge: 30 AWG
- Core Strands: 1/0.25 mm
- Length: 100 m
- Insulation Material: ETFE
- Outer Diameter: 0.56 mm
- Voltage Rating: 375 V



359841 0.05 mm²

RS PRO BLACK 0.05 MM² EQUIPMENT WIRE, 30 AWG, 1/0.25 MM, 100M,

Pack size: **100 x MTR**

- Cross Sectional Area: 0.05 mm²
- Sheath Colour: Black
- American Wire Gauge: 30 AWG
- Core Strands: 1/0.25 mm
- Length: 100 m
- Insulation Material: ETFE
- Voltage Rating: 375 V
- Outer Diameter: 0.56 mm




359857 0.05 mm²

RS PRO PURPLE 0.05 MM² EQUIPMENT WIRE, 30 AWG, 1/0.25

Pack size: **100 x MTR**

- Cross Sectional Area: 0.05 mm²
- Sheath Colour: Purple
- American Wire Gauge: 30 AWG
- Core Strands: 1/0.25 mm
- Length: 100 m
- Insulation Material: ETFE
- Outer Diameter: 0.56 mm
- Voltage Rating: 375 V



359891 0.05 mm²

RS PRO WHITE 0.05 MM² EQUIPMENT WIRE, 30 AWG, 1/0.25 MM, 100M,

Pack size: **100 x MTR**

- Cross Sectional Area: 0.05 mm²
- Sheath Colour: White
- American Wire Gauge: 30 AWG
- Core Strands: 1/0.25 mm
- Length: 100 m
- Insulation Material: ETFE
- Voltage Rating: 375 V
- Outer Diameter: 0.56 mm



359908 0.05 mm²

RS PRO GREEN 0.05 MM² EQUIPMENT WIRE, 30 AWG, 1/0.25 MM, 100M,

Pack size: **100 x MTR**

- Cross Sectional Area: 0.05 mm²
- Sheath Colour: Green
- American Wire Gauge: 30 AWG
- Core Strands: 1/0.25 mm
- Length: 100 m
- Insulation Material: ETFE
- Voltage Rating: 375 V
- Outer Diameter: 0.56 mm



359885 0.05 mm²

RS PRO WHITE 0.2 MM² HOOKUP & EQUIPMENT WIRE, 24 AWG, 19/0.12

Pack size: **100 x MTR**

- Cross Sectional Area: 0.2 mm²
- Sheath Colour: White
- American Wire Gauge: 24 AWG
- Core Strands: 19/0.12 mm
- Length: 100 m
- Insulation Material: Polyamide
- Voltage Rating: 600 V ac
- Outer Diameter: 0.96 mm



1113142 0.2 mm²

RS PRO GREEN 0.33 MM² EQUIPMENT WIRE, 22 AWG, 19/0.15 MM, 100M,

Pack size: **100 x MTR**

- Cross Sectional Area: 0.33 mm²
- Sheath Colour: Green
- American Wire Gauge: 22 AWG
- Core Strands: 19/0.15 mm
- Length: 100 m
- Insulation Material: Polyamide
- Voltage Rating: 600 V ac
- Outer Diameter: 1.1 mm



1113143 0.33 mm²

RS PRO BLUE 1 MM² AUTOMOTIVE WIRE, 57/0.15 MM, 30M

Pack size: **30 x MTR**

- Cross Sectional Area: 1 mm²
- Sheath Colour: Blue
- Core Strands: 57/0.15 mm
- Length: 30 m
- Outer Diameter: 2.7 mm
- Voltage Rating: 600 V
- Maximum Operating Temperature: +100 °C
- Minimum Operating Temperature: -40 °C



1225857 1 mm²

RS PRO GREEN 1 MM² AUTOMOTIVE WIRE, 57/0.15 MM, 30M

Pack size: **30 x MTR**

- Cross Sectional Area: 1 mm²
- Sheath Colour: Green
- Core Strands: 57/0.15 mm
- Length: 30 m
- Outer Diameter: 2.7 mm
- Voltage Rating: 600 V
- Maximum Operating Temperature: +100 °C
- Minimum Operating Temperature: -40 °C



1225859 1 mm²

RS PRO BROWN 1 MM² AUTOMOTIVE WIRE, 57/0.15 MM, 30M

Pack size: **30 x MTR**

- Cross Sectional Area: 1 mm²
- Sheath Colour: Brown
- Core Strands: 57/0.15 mm
- Length: 30 m
- Outer Diameter: 2.7 mm
- Voltage Rating: 600 V
- Maximum Operating Temperature: +100 °C
- Minimum Operating Temperature: -40 °C



1225858 1 mm²

RS PRO WHITE 1 MM² AUTOMOTIVE WIRE, 57/0.15 MM, 30M

Pack size: **30 x MTR**

- Cross Sectional Area: 1 mm²
- Sheath Colour: White
- Core Strands: 57/0.15 mm
- Length: 30 m
- Outer Diameter: 2.7 mm
- Voltage Rating: 600 V
- Maximum Operating Temperature: +100 °C
- Minimum Operating Temperature: -40 °C



1225860 1 mm²

RS PRO PINK 1 MM² AUTOMOTIVE WIRE, 57/0.15 MM, 30M

Pack size: **30 x MTR**

- Cross Sectional Area: 1 mm²
- Sheath Colour: Pink
- Core Strands: 57/0.15 mm
- Length: 30 m
- Outer Diameter: 2.7 mm
- Voltage Rating: 600 V
- Maximum Operating Temperature: +100 °C
- Minimum Operating Temperature: -40 °C



1225864 1 mm²

**RS PRO BLACK/BLUE 1 MM²
AUTOMOTIVE WIRE, 57/0.15 MM, 30M**Pack size: **30 x MTR**

- Cross Sectional Area: 1 mm²
- Sheath Colour: Black/Blue
- Core Strands: 57/0.15 mm
- Length: 30 m
- Outer Diameter: 2.7 mm
- Voltage Rating: 600 V
- Maximum Operating Temperature: +100 °C
- Minimum Operating Temperature: -40 °C

**1225865** 1 mm²**RS PRO BLACK/YELLOW 1 MM²
AUTOMOTIVE WIRE, 57/0.15 MM, 30M**Pack size: **30 x MTR**

- Cross Sectional Area: 1 mm²
- Sheath Colour: Black/Yellow
- Core Strands: 57/0.15 mm
- Length: 30 m
- Outer Diameter: 2.7 mm
- Voltage Rating: 600 V
- Maximum Operating Temperature: +100 °C
- Minimum Operating Temperature: -40 °C

**1225867** 1 mm²**ISO6722-1 AUTOMOTIVE WIRE 1MM
BL/BK 30M**Pack size: **30 x MTR**

- Cross Sectional Area: 1 mm²
- Sheath Colour: Black/Blue
- Core Strands: 57/0.15 mm
- Length: 30 m
- Outer Diameter: 2.7 mm
- Voltage Rating: 600 V
- Maximum Operating Temperature: +100 °C
- Minimum Operating Temperature: -40 °C

**1225868** 1 mm²**RS PRO BLUE/RED 1 MM²
AUTOMOTIVE WIRE, 57/0.15 MM, 30M**Pack size: **30 x MTR**

- Cross Sectional Area: 1 mm²
- Sheath Colour: Blue/Red
- Core Strands: 57/0.15 mm
- Length: 30 m
- Outer Diameter: 2.7 mm
- Voltage Rating: 600 V
- Maximum Operating Temperature: +100 °C
- Minimum Operating Temperature: -40 °C

**1225869** 1 mm²**RS PRO BLUE/WHITE 1 MM²
AUTOMOTIVE WIRE, 57/0.15 MM, 30M**Pack size: **30 x MTR**

- Cross Sectional Area: 1 mm²
- Sheath Colour: Blue/White
- Core Strands: 57/0.15 mm
- Length: 30 m
- Outer Diameter: 2.7 mm
- Voltage Rating: 600 V
- Maximum Operating Temperature: +100 °C
- Minimum Operating Temperature: -40 °C

**1225870** 1 mm²**RS PRO BROWN/RED 1 MM²
AUTOMOTIVE WIRE, 57/0.15 MM, 30M**Pack size: **30 x MTR**

- Cross Sectional Area: 1 mm²
- Sheath Colour: Brown/Red
- Core Strands: 57/0.15 mm
- Length: 30 m
- Outer Diameter: 2.7 mm
- Voltage Rating: 600 V
- Maximum Operating Temperature: +100 °C
- Minimum Operating Temperature: -40 °C

**1225871** 1 mm²**RS PRO GREEN/RED 1 MM²
AUTOMOTIVE WIRE, 57/0.15 MM, 30M**Pack size: **30 x MTR**

- Cross Sectional Area: 1 mm²
- Sheath Colour: Green/Red
- Core Strands: 57/0.15 mm
- Length: 30 m
- Outer Diameter: 2.7 mm
- Voltage Rating: 600 V
- Maximum Operating Temperature: +100 °C
- Minimum Operating Temperature: -40 °C

**1225873** 1 mm²**RS PRO GREEN/PURPLE 1 MM²
AUTOMOTIVE WIRE, 57/0.15 MM, 30M**Pack size: **30 x MTR**

- Cross Sectional Area: 1 mm²
- Sheath Colour: Green/Purple
- Core Strands: 57/0.15 mm
- Length: 30 m
- Outer Diameter: 2.7 mm
- Voltage Rating: 600 V
- Maximum Operating Temperature: +100 °C
- Minimum Operating Temperature: -40 °C

**1225874** 1 mm²**RS PRO BROWN 2 MM² AUTOMOTIVE
WIRE, 115/0.15 MM, 30M**Pack size: **30 x MTR**

- Cross Sectional Area: 2 mm²
- Sheath Colour: Brown
- Core Strands: 115/0.15 mm
- Length: 30 m
- Outer Diameter: 3.3 mm
- Voltage Rating: 600 V
- Maximum Operating Temperature: +100 °C
- Minimum Operating Temperature: -40 °C

**1225878** 2 mm²**RS PRO GREEN 2 MM² AUTOMOTIVE
WIRE, 115/0.15 MM, 30M**Pack size: **30 x MTR**

- Cross Sectional Area: 2 mm²
- Sheath Colour: Green
- Core Strands: 115/0.15 mm
- Length: 30 m
- Outer Diameter: 3.3 mm
- Voltage Rating: 600 V
- Maximum Operating Temperature: +100 °C
- Minimum Operating Temperature: -40 °C

**1225879** 2 mm²**RS PRO RED 2 MM² AUTOMOTIVE
WIRE, 115/0.15 MM, 30M**Pack size: **30 x MTR**

- Cross Sectional Area: 2 mm²
- Sheath Colour: Red
- Core Strands: 115/0.15 mm
- Length: 30 m
- Outer Diameter: 3.3 mm
- Voltage Rating: 600 V
- Maximum Operating Temperature: +100 °C
- Minimum Operating Temperature: -40 °C

**1225880** 2 mm²**RS PRO WHITE 2 MM² AUTOMOTIVE
WIRE, 115/0.15 MM, 30M**Pack size: **30 x MTR**

- Cross Sectional Area: 2 mm²
- Sheath Colour: White
- Core Strands: 115/0.15 mm
- Length: 30 m
- Outer Diameter: 3.3 mm
- Voltage Rating: 600 V
- Maximum Operating Temperature: +100 °C
- Minimum Operating Temperature: -40 °C

**1225882** 2 mm²**RS PRO RED/WHITE 2 MM²
AUTOMOTIVE WIRE, 115/0.15 MM,**Pack size: **30 x MTR**

- Cross Sectional Area: 2 mm²
- Sheath Colour: Red/White
- Core Strands: 115/0.15 mm
- Length: 30 m
- Outer Diameter: 3.3 mm
- Voltage Rating: 600 V
- Maximum Operating Temperature: +100 °C
- Minimum Operating Temperature: -40 °C

**1225885** 2 mm²**RS PRO BLACK 3 MM² AUTOMOTIVE
WIRE, 175/0.15 MM, 30M**Pack size: **30 x MTR**

- Cross Sectional Area: 3 mm²
- Sheath Colour: Black
- Core Strands: 175/0.15 mm
- Length: 30 m
- Outer Diameter: 4.1 mm
- Voltage Rating: 600 V
- Maximum Operating Temperature: +100 °C
- Minimum Operating Temperature: -40 °C

**1225886** 3 mm²**RS PRO BROWN 3 MM² AUTOMOTIVE
WIRE, 175/0.15 MM, 30M**Pack size: **30 x MTR**

- Cross Sectional Area: 3 mm²
- Sheath Colour: Brown
- Core Strands: 175/0.15 mm
- Length: 30 m
- Outer Diameter: 4.1 mm
- Voltage Rating: 600 V
- Maximum Operating Temperature: +100 °C
- Minimum Operating Temperature: -40 °C

**1225888** 3 mm²**RS PRO RED 3 MM² AUTOMOTIVE
WIRE, 175/0.15 MM, 30M**Pack size: **30 x MTR**

- Cross Sectional Area: 3 mm²
- Sheath Colour: Red
- Core Strands: 175/0.15 mm
- Length: 30 m
- Outer Diameter: 4.1 mm
- Voltage Rating: 600 V
- Maximum Operating Temperature: +100 °C
- Minimum Operating Temperature: -40 °C

**1225889** 3 mm²

RS PRO YELLOW 3 MM² AUTOMOTIVE WIRE, 175/0.15 MM, 30M

Pack size: **30 x MTR**

- Cross Sectional Area: 3 mm²
- Sheath Colour: Yellow
- Core Strands: 175/0.15 mm
- Length: 30 m
- Outer Diameter: 4.1 mm
- Voltage Rating: 600 V
- Maximum Operating Temperature: +100 °C
- Minimum Operating Temperature: -40 °C



1225890 3 mm²

RS PRO GREEN 0.2 MM² EQUIPMENT WIRE, 24 AWG, 1/0.51 MM, 50M, ETFE

Pack size: **50 x MTR**

- Cross Sectional Area: 0.2 mm²
- Sheath Colour: Green
- American Wire Gauge: 24 AWG
- Core Strands: 1/0.51 mm
- Length: 50 m
- Insulation Material: ETFE
- Voltage Rating: 300 V
- Maximum Operating Temperature: +160 °C



2077122 0.2 mm²

RS PRO YELLOW 0.2 MM² EQUIPMENT WIRE, 24 AWG, 1/0.51 MM, 50M, ETFE

Pack size: **50 x MTR**

- Cross Sectional Area: 0.2 mm²
- Sheath Colour: Yellow
- American Wire Gauge: 24 AWG
- Core Strands: 1/0.51 mm
- Length: 50 m
- Insulation Material: ETFE
- Voltage Rating: 300 V
- Maximum Operating Temperature: +160 °C



2077123 0.2 mm²

RS PRO ORANGE 0.2 MM² EQUIPMENT WIRE, 24 AWG, 1/0.51

Pack size: **50 x MTR**

- Cross Sectional Area: 0.2 mm²
- Sheath Colour: Orange
- American Wire Gauge: 24 AWG
- Core Strands: 1/0.51 mm
- Length: 50 m
- Insulation Material: ETFE
- Voltage Rating: 300 V
- Maximum Operating Temperature: -65 °C



2077124 0.2 mm²

RS PRO BLUE 0.2 MM² EQUIPMENT WIRE, 24 AWG, 1/0.51 MM, 50M, ETFE

Pack size: **50 x MTR**

- Cross Sectional Area: 0.2 mm²
- Sheath Colour: Blue
- American Wire Gauge: 24 AWG
- Core Strands: 1/0.51 mm
- Length: 50 m
- Insulation Material: ETFE
- Voltage Rating: 300 V
- Maximum Operating Temperature: +160 °C



2077125 0.2 mm²

RS PRO GREY 0.2 MM² EQUIPMENT WIRE, 24 AWG, 1/0.51 MM, 50M, ETFE

Pack size: **50 x MTR**

- Cross Sectional Area: 0.2 mm²
- Sheath Colour: Grey
- American Wire Gauge: 24 AWG
- Core Strands: 1/0.51 mm
- Length: 50 m
- Insulation Material: ETFE
- Voltage Rating: 300 V
- Maximum Operating Temperature: +160 °C



2077127 0.2 mm²

RS PRO BROWN 0.2 MM² EQUIPMENT WIRE, 24 AWG, 1/0.51 MM, 50M, ETFE

Pack size: **50 x MTR**

- Cross Sectional Area: 0.2 mm²
- Sheath Colour: Brown
- American Wire Gauge: 24 AWG
- Core Strands: 1/0.51 mm
- Length: 50 m
- Insulation Material: ETFE
- Voltage Rating: 300 V
- Maximum Operating Temperature: +160 °C



2077126 0.2 mm²

RS PRO PURPLE 0.2 MM² EQUIPMENT WIRE, 24 AWG, 1/0.51 MM, 50M, ETFE

Pack size: **50 x MTR**

- Cross Sectional Area: 0.2 mm²
- Sheath Colour: Purple
- American Wire Gauge: 24 AWG
- Core Strands: 1/0.51 mm
- Length: 50 m
- Insulation Material: ETFE
- Voltage Rating: 300 V
- Maximum Operating Temperature: +160 °C



2077128 0.2 mm²

RS PRO WHITE 0.12 MM² EQUIPMENT WIRE, 26 AWG, 1/0.40 MM, 50M, ETFE

Pack size: **50 x MTR**

- Cross Sectional Area: 0.12 mm²
- Sheath Colour: White
- American Wire Gauge: 26 AWG
- Core Strands: 1/0.40 mm
- Length: 50 m
- Insulation Material: ETFE
- Voltage Rating: 300 V
- Series: RS PRO



2077129 0.12 mm²

RS PRO RED 0.12 MM² EQUIPMENT WIRE, 26 AWG, 1/0.40 MM, 50M, ETFE

Pack size: **50 x MTR**

- Cross Sectional Area: 0.12 mm²
- Sheath Colour: Red
- American Wire Gauge: 26 AWG
- Core Strands: 1/0.40 mm
- Length: 50 m
- Insulation Material: ETFE
- Voltage Rating: 300 V
- Series: RS PRO



2077130 0.12 mm²

RS PRO GREEN 0.12 MM² EQUIPMENT WIRE, 26 AWG, 1/0.40 MM, 50M, ETFE

Pack size: **50 x MTR**

- Cross Sectional Area: 0.12 mm²
- Sheath Colour: Green
- American Wire Gauge: 26 AWG
- Core Strands: 1/0.40 mm
- Length: 50 m
- Insulation Material: ETFE
- Voltage Rating: 300 V
- Maximum Operating Temperature: 160 °C



2077132 0.12 mm²

RS PRO BLACK 0.12 MM² EQUIPMENT WIRE, 26 AWG, 1/0.40 MM, 50M, ETFE

Pack size: **50 x MTR**

- Cross Sectional Area: 0.12 mm²
- Sheath Colour: Black
- American Wire Gauge: 26 AWG
- Core Strands: 1/0.40 mm
- Length: 50 m
- Insulation Material: ETFE
- Voltage Rating: 300 V
- Series: RS PRO



2077133 0.12 mm²

RS PRO YELLOW 0.12 MM² EQUIPMENT WIRE, 26 AWG, 1/0.40

Pack size: **50 x MTR**

- Cross Sectional Area: 0.12 mm²
- Sheath Colour: Yellow
- American Wire Gauge: 26 AWG
- Core Strands: 1/0.40 mm
- Length: 50 m
- Insulation Material: ETFE
- Voltage Rating: 300 V
- Maximum Operating Temperature: 160 °C



2077134 0.12 mm²

RS PRO BLUE 0.12 MM² EQUIPMENT WIRE, 26 AWG, 1/0.40 MM, 50M, ETFE

Pack size: **50 x MTR**

- Cross Sectional Area: 0.12 mm²
- Sheath Colour: Blue
- American Wire Gauge: 26 AWG
- Core Strands: 1/0.40 mm
- Length: 50 m
- Insulation Material: ETFE
- Voltage Rating: 300 V
- Series: RS PRO



2077135 0.12 mm²

RS PRO WHITE 0.08 MM² EQUIPMENT WIRE, 28 AWG, 1/0.32 MM, 50M, ETFE

Pack size: **50 x MTR**

- Cross Sectional Area: 0.08 mm²
- Sheath Colour: White
- American Wire Gauge: 28 AWG
- Core Strands: 1/0.32 mm
- Length: 50 m
- Insulation Material: ETFE
- Voltage Rating: 300 V
- Series: RS PRO



2077136 0.08 mm²

RS PRO BLACK 0.08 MM² EQUIPMENT WIRE, 28 AWG, 1/0.32 MM, 50M, ETFE

Pack size: **50 x MTR**

- Cross Sectional Area: 0.08 mm²
- Sheath Colour: Black
- American Wire Gauge: 28 AWG
- Core Strands: 1/0.32 mm
- Length: 50 m
- Insulation Material: ETFE
- Voltage Rating: 300 V
- Maximum Operating Temperature: 160 °C



2077137 0.08 mm²

RS PRO BLUE 0.08 MM² EQUIPMENT WIRE, 28 AWG, 1/0.32 MM, 50M, ETFEPack size: **50 x MTR**

- Cross Sectional Area: 0.08 mm²
- Sheath Colour: Blue
- American Wire Gauge: 28 AWG
- Core Strands: 1/0.32 mm
- Length: 50 m
- Insulation Material: ETFE
- Voltage Rating: 300 V
- Series: RS PRO

**2077139** 0.08 mm²**RS PRO RED 0.08 MM² EQUIPMENT WIRE, 28 AWG, 1/0.32 MM, 50M, ETFE**Pack size: **50 x MTR**

- Cross Sectional Area: 0.08 mm²
- Sheath Colour: Red
- American Wire Gauge: 28 AWG
- Core Strands: 1/0.32 mm
- Length: 50 m
- Insulation Material: ETFE
- Voltage Rating: 300 V
- Series: RS PRO

**2077138** 0.08 mm²**RS PRO GREEN 0.08 MM² EQUIPMENT WIRE, 28 AWG, 1/0.32 MM, 50M, ETFE**Pack size: **50 x MTR**

- Cross Sectional Area: 0.08 mm²
- Sheath Colour: Green
- American Wire Gauge: 28 AWG
- Core Strands: 1/0.32 mm
- Length: 50 m
- Insulation Material: ETFE
- Voltage Rating: 300 V
- Maximum Operating Temperature: 160 °C

**2077140** 0.08 mm²**RS PRO WHITE 0.05 MM² EQUIPMENT WIRE, 30 AWG, 1/0.25 MM, 50M,**Pack size: **50 x MTR**

- Cross Sectional Area: 0.05 mm²
- Sheath Colour: White
- American Wire Gauge: 30 AWG
- Core Strands: 1/0.25 mm
- Length: 50 m
- Insulation Material: ETFE
- Voltage Rating: 300 V
- Series: RS PRO

**2077141** 0.05 mm²**RS PRO BLACK 0.05 MM² EQUIPMENT WIRE, 30 AWG, 1/0.25 MM, 50M,**Pack size: **50 x MTR**

- Cross Sectional Area: 0.05 mm²
- Sheath Colour: Black
- American Wire Gauge: 30 AWG
- Core Strands: 1/0.25 mm
- Length: 50 m
- Insulation Material: ETFE
- Voltage Rating: 300 V
- Series: RS PRO

**2077142** 0.05 mm²**RS PRO YELLOW 0.05 MM² EQUIPMENT WIRE, 30 AWG, 1/0.25**Pack size: **50 x MTR**

- Cross Sectional Area: 0.05 mm²
- Sheath Colour: Yellow
- American Wire Gauge: 30 AWG
- Core Strands: 1/0.25 mm
- Length: 50 m
- Insulation Material: ETFE
- Voltage Rating: 300 V
- Series: RS PRO

**2077143** 0.05 mm²**RS PRO RED 0.05 MM² EQUIPMENT WIRE, 30 AWG, 1/0.25 MM, 50M,**Pack size: **50 x MTR**

- Cross Sectional Area: 0.05 mm²
- Sheath Colour: Red
- American Wire Gauge: 30 AWG
- Core Strands: 1/0.25 mm
- Length: 50 m
- Insulation Material: ETFE
- Voltage Rating: 300 V
- Series: RS PRO

**2077144** 0.05 mm²**RS PRO GREEN 0.05 MM² EQUIPMENT WIRE, 30 AWG, 1/0.25 MM, 50M,**Pack size: **50 x MTR**

- Cross Sectional Area: 0.05 mm²
- Sheath Colour: Green
- American Wire Gauge: 30 AWG
- Core Strands: 1/0.25 mm
- Length: 50 m
- Insulation Material: ETFE
- Voltage Rating: 300 V
- Series: RS PRO

**2077145** 0.05 mm²**RS PRO BLUE 0.05 MM² EQUIPMENT WIRE, 30 AWG, 1/0.25 MM, 50M,**Pack size: **50 x MTR**

- Cross Sectional Area: 0.05 mm²
- Sheath Colour: Blue
- American Wire Gauge: 30 AWG
- Core Strands: 1/0.25 mm
- Length: 50 m
- Insulation Material: ETFE
- Voltage Rating: 300 V
- Series: RS PRO

**2077146** 0.05 mm²**RS PRO BROWN 0.05 MM² EQUIPMENT WIRE, 30 AWG, 1/0.25**Pack size: **50 x MTR**

- Cross Sectional Area: 0.05 mm²
- Sheath Colour: Brown
- American Wire Gauge: 30 AWG
- Core Strands: 1/0.25 mm
- Length: 50 m
- Insulation Material: ETFE
- Voltage Rating: 300 V
- Series: RS PRO

**2077148** 0.05 mm²**RS PRO ORANGE 0.05 MM² EQUIPMENT WIRE, 30 AWG, 1/0.25**Pack size: **50 x MTR**

- Cross Sectional Area: 0.05 mm²
- Sheath Colour: Orange
- American Wire Gauge: 30 AWG
- Core Strands: 1/0.25 mm
- Length: 50 m
- Insulation Material: ETFE
- Voltage Rating: 300 V
- Maximum Operating Temperature: 160 °C

**2077149** 0.05 mm²**RS PRO WHITE 0.2 MM² EQUIPMENT WIRE, 24 AWG, 1/0.51 MM, 50M, ETFE**Pack size: **50 x MTR**

- Cross Sectional Area: 0.2 mm²
- Sheath Colour: White
- American Wire Gauge: 24 AWG
- Core Strands: 1/0.51 mm
- Length: 50 m
- Insulation Material: ETFE
- Voltage Rating: 300 V
- Maximum Operating Temperature: +160 °C

**2077150** 0.2 mm²**RS PRO GREY 0.05 MM² EQUIPMENT WIRE, 30 AWG, 1/0.25 MM, 50M,**Pack size: **50 x MTR**

- Cross Sectional Area: 0.05 mm²
- Sheath Colour: Grey
- American Wire Gauge: 30 AWG
- Core Strands: 1/0.25 mm
- Length: 50 m
- Insulation Material: ETFE
- Voltage Rating: 300 V
- Maximum Operating Temperature: 160 °C

**2077151** 0.05 mm²**RS PRO PURPLE 0.05 MM² EQUIPMENT WIRE, 30 AWG, 1/0.25**Pack size: **50 x MTR**

- Cross Sectional Area: 0.05 mm²
- Sheath Colour: Purple
- American Wire Gauge: 30 AWG
- Core Strands: 1/0.25 mm
- Length: 50 m
- Insulation Material: ETFE
- Voltage Rating: 300 V
- Maximum Operating Temperature: 160 °C

**2077152** 0.05 mm²**RS PRO RED 0.2 MM² EQUIPMENT WIRE, 24 AWG, 1/0.51 MM, 50M, ETFE**Pack size: **50 x MTR**

- Cross Sectional Area: 0.2 mm²
- Sheath Colour: Red
- American Wire Gauge: 24 AWG
- Core Strands: 1/0.51 mm
- Length: 50 m
- Insulation Material: ETFE
- Voltage Rating: 300 V
- Minimum Operating Temperature: -65 °C

**2077155** 0.2 mm²**RS PRO BLACK 0.05 MM² EQUIPMENT WIRE, 30 AWG, 1/0.25 MM, 100M,**Pack size: **100 x MTR**

- Cross Sectional Area: 0.05 mm²
- Sheath Colour: Black
- American Wire Gauge: 30 AWG
- Core Strands: 1/0.25 mm
- Length: 100 m
- Insulation Material: ETFE
- Voltage Rating: 300 V
- Series: RS PRO

**2077156** 0.05 mm²

RS PRO GREEN 0.05 MM² EQUIPMENT WIRE, 30 AWG, 1/0.25 MM, 100M,

Pack size: **100 x MTR**

- Cross Sectional Area: 0.05 mm²
- Sheath Colour: Green
- American Wire Gauge: 30 AWG
- Core Strands: 1/0.25 mm
- Length: 100 m
- Insulation Material: ETFE
- Voltage Rating: 300 V
- Series: RS PRO



2077157 0.05 mm²

RS PRO WHITE 0.05 MM² EQUIPMENT WIRE, 30 AWG, 1/0.25 MM, 100M,

Pack size: **100 x MTR**

- Cross Sectional Area: 0.05 mm²
- Sheath Colour: White
- American Wire Gauge: 30 AWG
- Core Strands: 1/0.25 mm
- Length: 100 m
- Insulation Material: ETFE
- Voltage Rating: 300 V
- Series: RS PRO



2077158 0.05 mm²

RS PRO RED 0.05 MM² EQUIPMENT WIRE, 30 AWG, 1/0.25 MM, 100M,

Pack size: **100 x MTR**

- Cross Sectional Area: 0.05 mm²
- Sheath Colour: Red
- American Wire Gauge: 30 AWG
- Core Strands: 1/0.25 mm
- Length: 100 m
- Insulation Material: ETFE
- Voltage Rating: 300 V
- Series: RS PRO



2077159 0.05 mm²

RS PRO YELLOW 0.05 MM² EQUIPMENT WIRE, 30 AWG, 1/0.25

Pack size: **50 x MTR**

- Cross Sectional Area: 0.05 mm²
- Sheath Colour: Yellow
- American Wire Gauge: 30 AWG
- Core Strands: 1/0.25 mm
- Length: 50 m
- Insulation Material: Kynar
- Voltage Rating: 300 V
- Outer Diameter: 0.5 mm



2094798 0.05 mm²

RS PRO RED 0.05 MM² HOOK UP WIRE, 30 AWG, 1/0.25 MM, 50M,

Pack size: **50 x MTR**

- Cross Sectional Area: 0.05 mm²
- Sheath Colour: Red
- American Wire Gauge: 30 AWG
- Core Strands: 1/0.25 mm
- Length: 50 m
- Insulation Material: Kynar
- Voltage Rating: 300 V
- Outer Diameter: 0.5 mm



2094811 0.05 mm²

RS PRO WHITE 0.05 MM² EQUIPMENT WIRE, 30 AWG, 1/0.25 MM, 50M,

Pack size: **50 x MTR**

- Cross Sectional Area: 0.05 mm²
- Sheath Colour: White
- American Wire Gauge: 30 AWG
- Core Strands: 1/0.25 mm
- Length: 50 m
- Insulation Material: Kynar
- Voltage Rating: 300 V
- Outer Diameter: 0.5 mm



2094827 0.05 mm²

RS PRO BLACK 0.05 MM² EQUIPMENT WIRE, 30 AWG, 1/0.25 MM, 50M,

Pack size: **50 x MTR**

- Cross Sectional Area: 0.05 mm²
- Sheath Colour: Black
- American Wire Gauge: 30 AWG
- Core Strands: 1/0.25 mm
- Length: 50 m
- Insulation Material: Kynar
- Outer Diameter: 0.5 mm
- Voltage Rating: 300 V



2094849 0.05 mm²

RS PRO RESISTANCE WIRE, 7M

Pack size: **1 x EA**

- Length: 7 m
- Outer Diameter: 2.03 mm
- Maximum Operating Temperature: +1150 °C
- Conductor Material: Nickel Chrome Alloy



7141717 7 m

RS PRO RESISTANCE WIRE, 36M

Pack size: **1 x EA**

- Length: 36 m
- Outer Diameter: 0.91 mm
- Maximum Operating Temperature: +1150 °C
- Conductor Material: Nickel Chrome Alloy



7141723 36 m

RS PRO RESISTANCE WIRE, 11.5M

Pack size: **1 x EA**

- Length: 11.5 m
- Outer Diameter: 1.63 mm
- Maximum Operating Temperature: +1150 °C
- Conductor Material: Nickel Chrome Alloy



7141726 11.5 m

RS PRO RESISTANCE WIRE, 20.5M

Pack size: **1 x EA**

- Length: 20.5 m
- Outer Diameter: 1.22 mm
- Maximum Operating Temperature: +1150 °C
- Conductor Material: Nickel Chrome Alloy



7141729 20.5 m

RS PRO RESISTANCE WIRE, 60M

Pack size: **1 x EA**

- Length: 60 m
- Outer Diameter: 0.71 mm
- Maximum Operating Temperature: +1150 °C
- Conductor Material: Nickel Chrome Alloy



7141732 60 m

RS PRO RESISTANCE WIRE, 98M

Pack size: **1 x EA**

- Length: 98 m
- Outer Diameter: 0.56 mm
- Maximum Operating Temperature: +1150 °C
- Conductor Material: Nickel Chrome Alloy



7141735 98 m

RS PRO RESISTANCE WIRE, 118M

Pack size: **1 x EA**

- Length: 118 m
- Outer Diameter: 0.51 mm
- Maximum Operating Temperature: +1150 °C
- Conductor Material: Nickel Chrome Alloy



7141739 118 m

RS PRO EQUIPMENT WIRE, 623M

Pack size: **1 x EA**

- Length: 623 m
- Outer Diameter: 0.21 mm
- Maximum Operating Temperature: +1150 °C
- Conductor Material: Nickel Chrome Alloy



7141741 623 m

RS PRO RESISTANCE WIRE, 237M

Pack size: **1 x EA**

- Length: 237 m
- Outer Diameter: 0.35 mm
- Maximum Operating Temperature: +1150 °C
- Conductor Material: Nickel Chrome Alloy



7141748 237 m

RS PRO BLACK 0.08 MM² PTFE EQUIPMENT WIRE, 28 AWG, 7/0.12Pack size: **100 x MTR**

- Cross Sectional Area: 0.08 mm²
- Sheath Colour: Black
- American Wire Gauge: 28 AWG
- Core Strands: 7/0.12 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 300 V
- Outer Diameter: 0.71 mm

**8417131** 0.08 mm²**RS PRO PINK 0.08 MM² PTFE EQUIPMENT WIRE, 28 AWG, 7/0.12**Pack size: **100 x MTR**

- Cross Sectional Area: 0.08 mm²
- Sheath Colour: Pink
- American Wire Gauge: 28 AWG
- Core Strands: 7/0.12 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 300 V
- Outer Diameter: 0.71 mm

**8417134** 0.08 mm²**RS PRO RED 0.08 MM² PTFE EQUIPMENT WIRE, 28 AWG, 7/0.12**Pack size: **100 x MTR**

- Cross Sectional Area: 0.08 mm²
- Sheath Colour: Red
- American Wire Gauge: 28 AWG
- Core Strands: 7/0.12 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 300 V
- Outer Diameter: 0.71 mm

**8417138** 0.08 mm²**RS PRO YELLOW 0.08 MM² PTFE EQUIPMENT WIRE, 28 AWG, 7/0.12**Pack size: **100 x MTR**

- Cross Sectional Area: 0.08 mm²
- Sheath Colour: Yellow
- American Wire Gauge: 28 AWG
- Core Strands: 7/0.12 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 300 V
- Outer Diameter: 0.71 mm

**8417140** 0.08 mm²**RS PRO BLUE 0.08 MM² PTFE EQUIPMENT WIRE, 28 AWG, 7/0.12**Pack size: **100 x MTR**

- Cross Sectional Area: 0.08 mm²
- Sheath Colour: Blue
- American Wire Gauge: 28 AWG
- Core Strands: 7/0.12 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 300 V
- Outer Diameter: 0.71 mm

**8417144** 0.08 mm²**RS PRO WHITE 0.08 MM² PTFE EQUIPMENT WIRE, 28 AWG, 7/0.12**Pack size: **100 x MTR**

- Cross Sectional Area: 0.08 mm²
- Sheath Colour: White
- American Wire Gauge: 28 AWG
- Core Strands: 7/0.12 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 300 V
- Outer Diameter: 0.71 mm

**8417147** 0.08 mm²**RS PRO BROWN 0.08 MM² PTFE EQUIPMENT WIRE, 28 AWG, 7/0.12**Pack size: **100 x MTR**

- Cross Sectional Area: 0.08 mm²
- Sheath Colour: Brown
- American Wire Gauge: 28 AWG
- Core Strands: 7/0.12 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 300 V
- Outer Diameter: 0.71 mm

**8417150** 0.08 mm²**RS PRO ORANGE 0.08 MM² PTFE EQUIPMENT WIRE, 28 AWG, 7/0.12**Pack size: **100 x MTR**

- Cross Sectional Area: 0.08 mm²
- Sheath Colour: Orange
- American Wire Gauge: 28 AWG
- Core Strands: 7/0.12 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 300 V
- Outer Diameter: 0.71 mm

**8417153** 0.08 mm²**RS PRO GREEN 0.08 MM² PTFE EQUIPMENT WIRE, 28 AWG, 7/0.12**Pack size: **100 x MTR**

- Cross Sectional Area: 0.08 mm²
- Sheath Colour: Green
- American Wire Gauge: 28 AWG
- Core Strands: 7/0.12 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 300 V
- Outer Diameter: 0.71 mm

**8417156** 0.08 mm²**RS PRO GREY 0.08 MM² PTFE EQUIPMENT WIRE, 28 AWG, 7/0.12**Pack size: **100 x MTR**

- Cross Sectional Area: 0.08 mm²
- Sheath Colour: Grey
- American Wire Gauge: 28 AWG
- Core Strands: 7/0.12 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 300 V
- Outer Diameter: 0.71 mm

**8417162** 0.08 mm²**RS PRO BLACK 0.12 MM² PTFE EQUIPMENT WIRE, 26 AWG, 7/0.15**Pack size: **25 x MTR**

- Cross Sectional Area: 0.12 mm²
- Sheath Colour: Black
- American Wire Gauge: 26 AWG
- Core Strands: 7/0.15 mm
- Length: 25 m
- Insulation Material: PTFE
- Voltage Rating: 300 V
- Outer Diameter: 0.8 mm

**8417166** 0.12 mm²**RS PRO PURPLE 0.08 MM² PTFE EQUIPMENT WIRE, 28 AWG, 7/0.12**Pack size: **100 x MTR**

- Cross Sectional Area: 0.08 mm²
- Sheath Colour: Purple
- American Wire Gauge: 28 AWG
- Core Strands: 7/0.12 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 300 V
- Outer Diameter: 0.71 mm

**8417169** 0.08 mm²**RS PRO WHITE 0.12 MM² PTFE EQUIPMENT WIRE, 26 AWG, 7/0.15**Pack size: **25 x MTR**

- Cross Sectional Area: 0.12 mm²
- Sheath Colour: White
- American Wire Gauge: 26 AWG
- Core Strands: 7/0.15 mm
- Length: 25 m
- Insulation Material: PTFE
- Voltage Rating: 300 V
- Outer Diameter: 0.8 mm

**8417172** 0.12 mm²**RS PRO RED 0.12 MM² PTFE EQUIPMENT WIRE, 26 AWG, 7/0.15**Pack size: **25 x MTR**

- Cross Sectional Area: 0.12 mm²
- Sheath Colour: Red
- American Wire Gauge: 26 AWG
- Core Strands: 7/0.15 mm
- Length: 25 m
- Insulation Material: PTFE
- Voltage Rating: 300 V
- Outer Diameter: 0.8 mm

**8417178** 0.12 mm²**RS PRO BLACK 0.12 MM² PTFE EQUIPMENT WIRE, 26 AWG, 7/0.15**Pack size: **100 x MTR**

- Cross Sectional Area: 0.12 mm²
- Sheath Colour: Black
- American Wire Gauge: 26 AWG
- Core Strands: 7/0.15 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 300 V
- Outer Diameter: 0.8 mm

**8417181** 0.12 mm²**RS PRO PINK 0.12 MM² PTFE EQUIPMENT WIRE, 26 AWG, 7/0.15**Pack size: **100 x MTR**

- Cross Sectional Area: 0.12 mm²
- Sheath Colour: Pink
- American Wire Gauge: 26 AWG
- Core Strands: 7/0.15 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 300 V
- Outer Diameter: 0.8 mm

**8417184** 0.12 mm²

RS PRO RED 0.12 MM² PTFE EQUIPMENT WIRE, 26 AWG, 7/0.15

Pack size: **100 x MTR**

- Cross Sectional Area: 0.12 mm²
- Sheath Colour: Red
- American Wire Gauge: 26 AWG
- Core Strands: 7/0.15 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 300 V
- Outer Diameter: 0.8 mm



8417188 0.12 mm²

RS PRO BLUE 0.12 MM² PTFE EQUIPMENT WIRE, 26 AWG, 7/0.15

Pack size: **100 x MTR**

- Cross Sectional Area: 0.12 mm²
- Sheath Colour: Blue
- American Wire Gauge: 26 AWG
- Core Strands: 7/0.15 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 300 V
- Outer Diameter: 0.8 mm



8417190 0.12 mm²

RS PRO GREEN 0.12 MM² PTFE EQUIPMENT WIRE, 26 AWG, 7/0.15

Pack size: **100 x MTR**

- Cross Sectional Area: 0.12 mm²
- Sheath Colour: Green
- American Wire Gauge: 26 AWG
- Core Strands: 7/0.15 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 300 V
- Outer Diameter: 0.8 mm



8417194 0.12 mm²

RS PRO WHITE 0.12 MM² PTFE EQUIPMENT WIRE, 26 AWG, 7/0.15

Pack size: **100 x MTR**

- Cross Sectional Area: 0.12 mm²
- Sheath Colour: White
- American Wire Gauge: 26 AWG
- Core Strands: 7/0.15 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 300 V
- Outer Diameter: 0.8 mm



8417197 0.12 mm²

RS PRO PURPLE 0.12 MM² PTFE EQUIPMENT WIRE, 26 AWG, 7/0.15

Pack size: **100 x MTR**

- Cross Sectional Area: 0.12 mm²
- Sheath Colour: Purple
- American Wire Gauge: 26 AWG
- Core Strands: 7/0.15 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 300 V
- Outer Diameter: 0.8 mm



8417201 0.12 mm²

RS PRO YELLOW 0.12 MM² PTFE EQUIPMENT WIRE, 26 AWG, 7/0.15

Pack size: **100 x MTR**

- Cross Sectional Area: 0.12 mm²
- Sheath Colour: Yellow
- American Wire Gauge: 26 AWG
- Core Strands: 7/0.15 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 300 V
- Outer Diameter: 0.8 mm



8417204 0.12 mm²

RS PRO BROWN 0.12 MM² PTFE EQUIPMENT WIRE, 26 AWG, 7/0.15

Pack size: **100 x MTR**

- Cross Sectional Area: 0.12 mm²
- Sheath Colour: Brown
- American Wire Gauge: 26 AWG
- Core Strands: 7/0.15 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 300 V
- Outer Diameter: 0.8 mm



8417207 0.12 mm²

RS PRO ORANGE 0.12 MM² PTFE EQUIPMENT WIRE, 26 AWG, 7/0.15

Pack size: **100 x MTR**

- Cross Sectional Area: 0.12 mm²
- Sheath Colour: Orange
- American Wire Gauge: 26 AWG
- Core Strands: 7/0.15 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 300 V
- Outer Diameter: 0.8 mm



8417210 0.12 mm²

RS PRO BLACK 0.22 MM² PTFE EQUIPMENT WIRE, 24 AWG, 7/0.2

Pack size: **25 x MTR**

- Cross Sectional Area: 0.22 mm²
- Sheath Colour: Black
- American Wire Gauge: 24 AWG
- Core Strands: 7/0.2 mm
- Length: 25 m
- Insulation Material: PTFE
- Voltage Rating: 300 V
- Outer Diameter: 0.95 mm



8417213 0.22 mm²

RS PRO BLACK 0.22 MM² PTFE EQUIPMENT WIRE, 24 AWG, 7/0.2

Pack size: **100 x MTR**

- Cross Sectional Area: 0.22 mm²
- Sheath Colour: Black
- American Wire Gauge: 24 AWG
- Core Strands: 7/0.2 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 300 V
- Outer Diameter: 0.95 mm



8417223 0.22 mm²

RS PRO RED 0.22 MM² PTFE EQUIPMENT WIRE, 24 AWG, 7/0.2

Pack size: **25 x MTR**

- Cross Sectional Area: 0.22 mm²
- Sheath Colour: Red
- American Wire Gauge: 24 AWG
- Core Strands: 7/0.2 mm
- Length: 25 m
- Insulation Material: PTFE
- Voltage Rating: 300 V
- Outer Diameter: 0.95 mm



8417226 0.22 mm²

RS PRO WHITE 0.22 MM² PTFE EQUIPMENT WIRE, 24 AWG, 7/0.2

Pack size: **25 x MTR**

- Cross Sectional Area: 0.22 mm²
- Sheath Colour: White
- American Wire Gauge: 24 AWG
- Core Strands: 7/0.2 mm
- Length: 25 m
- Insulation Material: PTFE
- Voltage Rating: 300 V
- Outer Diameter: 0.95 mm



8417229 0.22 mm²

RS PRO PINK 0.22 MM² PTFE EQUIPMENT WIRE, 24 AWG, 7/0.2

Pack size: **100 x MTR**

- Cross Sectional Area: 0.22 mm²
- Sheath Colour: Pink
- American Wire Gauge: 24 AWG
- Core Strands: 7/0.2 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 300 V
- Outer Diameter: 0.95 mm



8417232 0.22 mm²

RS PRO RED 0.22 MM² PTFE EQUIPMENT WIRE, 24 AWG, 7/0.2

Pack size: **100 x MTR**

- Cross Sectional Area: 0.22 mm²
- Sheath Colour: Red
- American Wire Gauge: 24 AWG
- Core Strands: 7/0.2 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 300 V
- Outer Diameter: 0.95 mm



8417235 0.22 mm²

RS PRO BLUE 0.22 MM² PTFE EQUIPMENT WIRE, 24 AWG, 7/0.2

Pack size: **100 x MTR**

- Cross Sectional Area: 0.22 mm²
- Sheath Colour: Blue
- American Wire Gauge: 24 AWG
- Core Strands: 7/0.2 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 300 V
- Outer Diameter: 0.95 mm



8417241 0.22 mm²

RS PRO ORANGE 0.22 MM² PTFE EQUIPMENT WIRE, 24 AWG, 7/0.2

Pack size: **100 x MTR**

- Cross Sectional Area: 0.22 mm²
- Sheath Colour: Orange
- American Wire Gauge: 24 AWG
- Core Strands: 7/0.2 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 300 V
- Outer Diameter: 0.95 mm



8417245 0.22 mm²

RS PRO YELLOW 0.22 MM² PTFE EQUIPMENT WIRE, 24 AWG, 7/0.2Pack size: **100 x MTR**

- Cross Sectional Area: 0.22 mm²
- Sheath Colour: Yellow
- American Wire Gauge: 24 AWG
- Core Strands: 7/0.2 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 300 V
- Outer Diameter: 0.95 mm

**8417248** 0.22 mm²**RS PRO PURPLE 0.22 MM² PTFE EQUIPMENT WIRE, 24 AWG, 7/0.2**Pack size: **100 x MTR**

- Cross Sectional Area: 0.22 mm²
- Sheath Colour: Purple
- American Wire Gauge: 24 AWG
- Core Strands: 7/0.2 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 300 V
- Outer Diameter: 0.95 mm

**8417251** 0.22 mm²**RS PRO GREEN 0.22 MM² PTFE EQUIPMENT WIRE, 24 AWG, 7/0.2**Pack size: **100 x MTR**

- Cross Sectional Area: 0.22 mm²
- Sheath Colour: Green
- American Wire Gauge: 24 AWG
- Core Strands: 7/0.2 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 300 V
- Outer Diameter: 0.95 mm

**8417254** 0.22 mm²**RS PRO BROWN 0.22 MM² PTFE EQUIPMENT WIRE, 24 AWG, 7/0.2**Pack size: **100 x MTR**

- Cross Sectional Area: 0.22 mm²
- Sheath Colour: Brown
- American Wire Gauge: 24 AWG
- Core Strands: 7/0.2 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 300 V
- Outer Diameter: 0.95 mm

**8417257** 0.22 mm²**RS PRO BLACK 0.34 MM² PTFE EQUIPMENT WIRE, 22 AWG, 19/0.15**Pack size: **100 x MTR**

- Cross Sectional Area: 0.34 mm²
- Sheath Colour: Black
- American Wire Gauge: 22 AWG
- Core Strands: 19/0.15 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 300 V
- Outer Diameter: 1.1 mm

**8417263** 0.34 mm²**RS PRO GREY 0.22 MM² PTFE EQUIPMENT WIRE, 24 AWG, 7/0.2**Pack size: **100 x MTR**

- Cross Sectional Area: 0.22 mm²
- Sheath Colour: Grey
- American Wire Gauge: 24 AWG
- Core Strands: 7/0.2 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 300 V
- Outer Diameter: 0.95 mm

**8417260** 0.22 mm²**RS PRO PINK 0.34 MM² PTFE EQUIPMENT WIRE, 22 AWG, 19/0.15**Pack size: **100 x MTR**

- Cross Sectional Area: 0.34 mm²
- Sheath Colour: Pink
- American Wire Gauge: 22 AWG
- Core Strands: 19/0.15 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 300 V
- Outer Diameter: 1.1 mm

**8417267** 0.34 mm²**RS PRO YELLOW 0.34 MM² PTFE EQUIPMENT WIRE, 22 AWG, 19/0.15**Pack size: **100 x MTR**

- Cross Sectional Area: 0.34 mm²
- Sheath Colour: Yellow
- American Wire Gauge: 22 AWG
- Core Strands: 19/0.15 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 300 V
- Outer Diameter: 1.1 mm

**8417273** 0.34 mm²**RS PRO RED 0.34 MM² PTFE EQUIPMENT WIRE, 22 AWG, 19/0.15**Pack size: **100 x MTR**

- Cross Sectional Area: 0.34 mm²
- Sheath Colour: Red
- American Wire Gauge: 22 AWG
- Core Strands: 19/0.15 mm
- Length: 100 m
- Insulation Material: PTFE
- Outer Diameter: 1.1 mm
- Voltage Rating: 300 V

**8417276** 0.34 mm²**RS PRO WHITE 0.34 MM² PTFE EQUIPMENT WIRE, 22 AWG, 19/0.15**Pack size: **100 x MTR**

- Cross Sectional Area: 0.34 mm²
- Sheath Colour: White
- American Wire Gauge: 22 AWG
- Core Strands: 19/0.15 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 300 V
- Outer Diameter: 1.1 mm

**8417279** 0.34 mm²**RS PRO BLUE 0.34 MM² PTFE EQUIPMENT WIRE, 22 AWG, 19/0.15**Pack size: **100 x MTR**

- Cross Sectional Area: 0.34 mm²
- Sheath Colour: Blue
- American Wire Gauge: 22 AWG
- Core Strands: 19/0.15 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 300 V
- Outer Diameter: 1.1 mm

**8417282** 0.34 mm²**RS PRO ORANGE 0.34 MM² PTFE EQUIPMENT WIRE, 22 AWG, 19/0.15**Pack size: **100 x MTR**

- Cross Sectional Area: 0.34 mm²
- Sheath Colour: Orange
- American Wire Gauge: 22 AWG
- Core Strands: 19/0.15 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 300 V
- Outer Diameter: 1.1 mm

**8417285** 0.34 mm²**RS PRO GREEN 0.34 MM² PTFE EQUIPMENT WIRE, 22 AWG, 19/0.15**Pack size: **100 x MTR**

- Cross Sectional Area: 0.34 mm²
- Sheath Colour: Green
- American Wire Gauge: 22 AWG
- Core Strands: 19/0.15 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 300 V
- Outer Diameter: 1.1 mm

**8417289** 0.34 mm²**RS PRO PURPLE 0.34 MM² PTFE EQUIPMENT WIRE, 22 AWG, 19/0.15**Pack size: **100 x MTR**

- Cross Sectional Area: 0.34 mm²
- Sheath Colour: Purple
- American Wire Gauge: 22 AWG
- Core Strands: 19/0.15 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 300 V
- Outer Diameter: 1.1 mm

**8417291** 0.34 mm²**RS PRO RED 0.6 MM² PTFE EQUIPMENT WIRE, 20 AWG, 19/0.2**Pack size: **100 x MTR**

- Cross Sectional Area: 0.6 mm²
- Sheath Colour: Red
- American Wire Gauge: 20 AWG
- Core Strands: 19/0.2 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 300 V
- Outer Diameter: 1.35 mm

**8417302** 0.6 mm²**RS PRO BROWN 0.34 MM² PTFE EQUIPMENT WIRE, 22 AWG, 19/0.15**Pack size: **100 x MTR**

- Cross Sectional Area: 0.34 mm²
- Sheath Colour: Brown
- American Wire Gauge: 22 AWG
- Core Strands: 19/0.15 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 300 V
- Outer Diameter: 1.1 mm

**8417298** 0.34 mm²

RS PRO BLACK 0.6 MM² PTFE EQUIPMENT WIRE, 20 AWG, 19/0.2

Pack size: **100 x MTR**

- Cross Sectional Area: 0.6 mm²
- Sheath Colour: Black
- American Wire Gauge: 20 AWG
- Core Strands: 19/0.2 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 300 V
- Outer Diameter: 1.35 mm



8417305 0.6 mm²

RS PRO PINK 0.6 MM² PTFE EQUIPMENT WIRE, 20 AWG, 19/0.2

Pack size: **100 x MTR**

- Cross Sectional Area: 0.6 mm²
- Sheath Colour: Pink
- American Wire Gauge: 20 AWG
- Core Strands: 19/0.2 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 300 V
- Outer Diameter: 1.35 mm



8417308 0.6 mm²

RS PRO WHITE 0.6 MM² PTFE EQUIPMENT WIRE, 20 AWG, 19/0.2

Pack size: **100 x MTR**

- Cross Sectional Area: 0.6 mm²
- Sheath Colour: White
- American Wire Gauge: 20 AWG
- Core Strands: 19/0.2 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 300 V
- Outer Diameter: 1.35 mm



8417311 0.6 mm²

RS PRO YELLOW 0.6 MM² PTFE EQUIPMENT WIRE, 20 AWG, 19/0.2

Pack size: **100 x MTR**

- Cross Sectional Area: 0.6 mm²
- Sheath Colour: Yellow
- American Wire Gauge: 20 AWG
- Core Strands: 19/0.2 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 300 V
- Outer Diameter: 1.35 mm



8417314 0.6 mm²

RS PRO BLUE 0.6 MM² PTFE EQUIPMENT WIRE, 20 AWG, 19/0.2

Pack size: **100 x MTR**

- Cross Sectional Area: 0.6 mm²
- Sheath Colour: Blue
- American Wire Gauge: 20 AWG
- Core Strands: 19/0.2 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 300 V
- Outer Diameter: 1.35 mm



8417318 0.6 mm²

RS PRO GREEN 0.6 MM² PTFE EQUIPMENT WIRE, 20 AWG, 19/0.2

Pack size: **100 x MTR**

- Cross Sectional Area: 0.6 mm²
- Sheath Colour: Green
- American Wire Gauge: 20 AWG
- Core Strands: 19/0.2 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 300 V
- Outer Diameter: 1.35 mm



8417320 0.6 mm²

RS PRO ORANGE 0.6 MM² PTFE EQUIPMENT WIRE, 20 AWG, 19/0.2

Pack size: **100 x MTR**

- Cross Sectional Area: 0.6 mm²
- Sheath Colour: Orange
- American Wire Gauge: 20 AWG
- Core Strands: 19/0.2 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 300 V
- Outer Diameter: 1.35 mm



8417327 0.6 mm²

RS PRO BROWN 0.6 MM² PTFE EQUIPMENT WIRE, 20 AWG, 19/0.2

Pack size: **100 x MTR**

- Cross Sectional Area: 0.6 mm²
- Sheath Colour: Brown
- American Wire Gauge: 20 AWG
- Core Strands: 19/0.2 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 300 V
- Outer Diameter: 1.35 mm



8417324 0.6 mm²

RS PRO BLACK 0.22 MM² PTFE EQUIPMENT WIRE, 24 AWG, 7/0.2

Pack size: **25 x MTR**

- Cross Sectional Area: 0.22 mm²
- Sheath Colour: Black
- American Wire Gauge: 24 AWG
- Core Strands: 7/0.2 mm
- Length: 25 m
- Insulation Material: PTFE
- Voltage Rating: 600 V
- Outer Diameter: 1.2 mm



8417330 0.22 mm²

RS PRO PURPLE 0.6 MM² PTFE EQUIPMENT WIRE, 20 AWG, 19/0.2

Pack size: **100 x MTR**

- Cross Sectional Area: 0.6 mm²
- Sheath Colour: Purple
- American Wire Gauge: 20 AWG
- Core Strands: 19/0.2 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 300 V
- Outer Diameter: 1.35 mm



8417333 0.6 mm²

RS PRO GREY 0.6 MM² PTFE EQUIPMENT WIRE, 20 AWG, 19/0.2

Pack size: **100 x MTR**

- Cross Sectional Area: 0.6 mm²
- Sheath Colour: Grey
- American Wire Gauge: 20 AWG
- Core Strands: 19/0.2 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 300 V
- Outer Diameter: 1.35 mm



8417336 0.6 mm²

RS PRO RED 0.22 MM² PTFE EQUIPMENT WIRE, 24 AWG, 7/0.2

Pack size: **25 x MTR**

- Cross Sectional Area: 0.22 mm²
- Sheath Colour: Red
- American Wire Gauge: 24 AWG
- Core Strands: 7/0.2 mm
- Length: 25 m
- Insulation Material: PTFE
- Voltage Rating: 600 V
- Outer Diameter: 1.2 mm



8417342 0.22 mm²

RS PRO YELLOW 0.22 MM² PTFE EQUIPMENT WIRE, 24 AWG, 7/0.2

Pack size: **25 x MTR**

- Cross Sectional Area: 0.22 mm²
- Sheath Colour: Yellow
- American Wire Gauge: 24 AWG
- Core Strands: 7/0.2 mm
- Length: 25 m
- Insulation Material: PTFE
- Voltage Rating: 600 V
- Outer Diameter: 1.2 mm



8417346 0.22 mm²

RS PRO PINK 0.22 MM² PTFE EQUIPMENT WIRE, 24 AWG, 7/0.2

Pack size: **25 x MTR**

- Cross Sectional Area: 0.22 mm²
- Sheath Colour: Pink
- American Wire Gauge: 24 AWG
- Core Strands: 7/0.2 mm
- Length: 25 m
- Insulation Material: PTFE
- Voltage Rating: 600 V
- Outer Diameter: 1.2 mm



8417349 0.22 mm²

RS PRO RED 0.22 MM² PTFE EQUIPMENT WIRE, 24 AWG, 7/0.2

Pack size: **100 x MTR**

- Cross Sectional Area: 0.22 mm²
- Sheath Colour: Red
- American Wire Gauge: 24 AWG
- Core Strands: 7/0.2 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 600 V
- Outer Diameter: 1.2 mm



8417352 0.22 mm²

RS PRO PINK 0.22 MM² PTFE EQUIPMENT WIRE, 24 AWG, 7/0.2

Pack size: **100 x MTR**

- Cross Sectional Area: 0.22 mm²
- Sheath Colour: Pink
- American Wire Gauge: 24 AWG
- Core Strands: 7/0.2 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 600 V
- Outer Diameter: 1.2 mm



8417358 0.22 mm²

RS PRO BLACK 0.22 MM² PTFE EQUIPMENT WIRE, 24 AWG, 7/0.2Pack size: **100 x MTR**

- Cross Sectional Area: 0.22 mm²
- Sheath Colour: Black
- American Wire Gauge: 24 AWG
- Core Strands: 7/0.2 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 600 V
- Outer Diameter: 1.2 mm

**8417355** 0.22 mm²**RS PRO WHITE 0.22 MM² PTFE EQUIPMENT WIRE, 24 AWG, 7/0.2**Pack size: **100 x MTR**

- Cross Sectional Area: 0.22 mm²
- Sheath Colour: White
- American Wire Gauge: 24 AWG
- Core Strands: 7/0.2 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 600 V
- Outer Diameter: 1.2 mm

**8417361** 0.22 mm²**RS PRO YELLOW 0.22 MM² PTFE EQUIPMENT WIRE, 24 AWG, 7/0.2**Pack size: **100 x MTR**

- Cross Sectional Area: 0.22 mm²
- Sheath Colour: Yellow
- American Wire Gauge: 24 AWG
- Core Strands: 7/0.2 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 600 V
- Outer Diameter: 1.2 mm

**8417364** 0.22 mm²**RS PRO BLUE 0.22 MM² PTFE EQUIPMENT WIRE, 24 AWG, 7/0.2**Pack size: **100 x MTR**

- Cross Sectional Area: 0.22 mm²
- Sheath Colour: Blue
- American Wire Gauge: 24 AWG
- Core Strands: 7/0.2 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 600 V
- Outer Diameter: 1.2 mm

**8417370** 0.22 mm²**RS PRO GREEN 0.22 MM² PTFE EQUIPMENT WIRE, 24 AWG, 7/0.2**Pack size: **100 x MTR**

- Cross Sectional Area: 0.22 mm²
- Sheath Colour: Green
- American Wire Gauge: 24 AWG
- Core Strands: 7/0.2 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 600 V
- Outer Diameter: 1.2 mm

**8417374** 0.22 mm²**RS PRO ORANGE 0.22 MM² PTFE EQUIPMENT WIRE, 24 AWG, 7/0.2**Pack size: **100 x MTR**

- Cross Sectional Area: 0.22 mm²
- Sheath Colour: Orange
- American Wire Gauge: 24 AWG
- Core Strands: 7/0.2 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 600 V
- Outer Diameter: 1.2 mm

**8417377** 0.22 mm²**RS PRO GREY 0.22 MM² PTFE EQUIPMENT WIRE, 24 AWG, 7/0.2**Pack size: **100 x MTR**

- Cross Sectional Area: 0.22 mm²
- Sheath Colour: Grey
- American Wire Gauge: 24 AWG
- Core Strands: 7/0.2 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 600 V
- Outer Diameter: 1.2 mm

**8417380** 0.22 mm²**RS PRO BROWN 0.22 MM² PTFE EQUIPMENT WIRE, 24 AWG, 7/0.2**Pack size: **100 x MTR**

- Cross Sectional Area: 0.22 mm²
- Sheath Colour: Brown
- American Wire Gauge: 24 AWG
- Core Strands: 7/0.2 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 600 V
- Outer Diameter: 1.2 mm

**8417383** 0.22 mm²**RS PRO PURPLE 0.22 MM² PTFE EQUIPMENT WIRE, 24 AWG, 7/0.2**Pack size: **100 x MTR**

- Cross Sectional Area: 0.22 mm²
- Sheath Colour: Purple
- American Wire Gauge: 24 AWG
- Core Strands: 7/0.2 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 600 V
- Outer Diameter: 1.2 mm

**8417386** 0.22 mm²**RS PRO PINK 0.34 MM² PTFE EQUIPMENT WIRE, 22 AWG, 19/0.15**Pack size: **25 x MTR**

- Cross Sectional Area: 0.34 mm²
- Sheath Colour: Pink
- American Wire Gauge: 22 AWG
- Core Strands: 19/0.15 mm
- Length: 25 m
- Insulation Material: PTFE
- Voltage Rating: 600 V
- Outer Diameter: 1.35 mm

**8417392** 0.34 mm²**RS PRO RED 0.34 MM² PTFE EQUIPMENT WIRE, 22 AWG, 19/0.15**Pack size: **25 x MTR**

- Cross Sectional Area: 0.34 mm²
- Sheath Colour: Red
- American Wire Gauge: 22 AWG
- Core Strands: 19/0.15 mm
- Length: 25 m
- Insulation Material: PTFE
- Voltage Rating: 600 V
- Outer Diameter: 1.35 mm

**8417396** 0.34 mm²**RS PRO BLACK 0.34 MM² PTFE EQUIPMENT WIRE, 22 AWG, 19/0.15**Pack size: **25 x MTR**

- Cross Sectional Area: 0.34 mm²
- Sheath Colour: Black
- American Wire Gauge: 22 AWG
- Core Strands: 19/0.15 mm
- Length: 25 m
- Insulation Material: PTFE
- Voltage Rating: 600 V
- Outer Diameter: 1.35 mm

**8417399** 0.34 mm²**RS PRO YELLOW 0.34 MM² PTFE EQUIPMENT WIRE, 22 AWG, 19/0.15**Pack size: **25 x MTR**

- Cross Sectional Area: 0.34 mm²
- Sheath Colour: Yellow
- American Wire Gauge: 22 AWG
- Core Strands: 19/0.15 mm
- Length: 25 m
- Insulation Material: PTFE
- Voltage Rating: 600 V
- Outer Diameter: 1.35 mm

**8417406** 0.34 mm²**RS PRO BLACK 0.34 MM² PTFE EQUIPMENT WIRE, 22 AWG, 19/0.15**Pack size: **100 x MTR**

- Cross Sectional Area: 0.34 mm²
- Sheath Colour: Black
- American Wire Gauge: 22 AWG
- Core Strands: 19/0.15 mm
- Length: 100 m
- Insulation Material: PTFE
- Outer Diameter: 1.35 mm
- Voltage Rating: 600 V

**8417409** 0.34 mm²**RS PRO RED 0.34 MM² PTFE EQUIPMENT WIRE, 22 AWG, 19/0.15**Pack size: **100 x MTR**

- Cross Sectional Area: 0.34 mm²
- Sheath Colour: Red
- American Wire Gauge: 22 AWG
- Core Strands: 19/0.15 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 600 V
- Outer Diameter: 1.35 mm

**8417412** 0.34 mm²**RS PRO WHITE 0.34 MM² PTFE EQUIPMENT WIRE, 22 AWG, 19/0.15**Pack size: **100 x MTR**

- Cross Sectional Area: 0.34 mm²
- Sheath Colour: White
- American Wire Gauge: 22 AWG
- Core Strands: 19/0.15 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 600 V
- Outer Diameter: 1.35 mm

**8417415** 0.34 mm²

RS PRO YELLOW 0.34 MM² PTFE EQUIPMENT WIRE, 22 AWG, 19/0.15

Pack size: **100 x MTR**

- Cross Sectional Area: 0.34 mm²
- Sheath Colour: Yellow
- American Wire Gauge: 22 AWG
- Core Strands: 19/0.15 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 600 V
- Outer Diameter: 1.35 mm




8417419 0.34 mm²

RS PRO BLUE 0.34 MM² PTFE EQUIPMENT WIRE, 22 AWG, 19/0.15

Pack size: **100 x MTR**

- Cross Sectional Area: 0.34 mm²
- Sheath Colour: Blue
- American Wire Gauge: 22 AWG
- Core Strands: 19/0.15 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 600 V
- Outer Diameter: 1.35 mm



8417421 0.34 mm²

RS PRO GREEN 0.34 MM² PTFE EQUIPMENT WIRE, 22 AWG, 19/0.15

Pack size: **100 x MTR**

- Cross Sectional Area: 0.34 mm²
- Sheath Colour: Green
- American Wire Gauge: 22 AWG
- Core Strands: 19/0.15 mm
- Length: 100 m
- Insulation Material: PTFE
- Outer Diameter: 1.35 mm
- Voltage Rating: 600 V



8417425 0.34 mm²

RS PRO ORANGE 0.34 MM² PTFE EQUIPMENT WIRE, 22 AWG, 19/0.15

Pack size: **100 x MTR**

- Cross Sectional Area: 0.34 mm²
- Sheath Colour: Orange
- American Wire Gauge: 22 AWG
- Core Strands: 19/0.15 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 600 V
- Outer Diameter: 1.35 mm



8417428 0.34 mm²

RS PRO BLACK 0.6 MM² PTFE EQUIPMENT WIRE, 20 AWG, 19/0.2

Pack size: **100 x MTR**

- Cross Sectional Area: 0.6 mm²
- Sheath Colour: Black
- American Wire Gauge: 20 AWG
- Core Strands: 19/0.2 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 600 V
- Outer Diameter: 1.6 mm



8417431 0.6 mm²

RS PRO BROWN 0.34 MM² PTFE EQUIPMENT WIRE, 22 AWG, 19/0.15

Pack size: **100 x MTR**

- Cross Sectional Area: 0.34 mm²
- Sheath Colour: Brown
- American Wire Gauge: 22 AWG
- Core Strands: 19/0.15 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 600 V
- Outer Diameter: 1.35 mm



8417434 0.34 mm²

RS PRO GREY 0.34 MM² PTFE EQUIPMENT WIRE, 22 AWG, 19/0.15

Pack size: **100 x MTR**

- Cross Sectional Area: 0.34 mm²
- Sheath Colour: Grey
- American Wire Gauge: 22 AWG
- Core Strands: 19/0.15 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 600 V
- Outer Diameter: 1.35 mm



8417437 0.34 mm²

RS PRO RED 0.6 MM² PTFE EQUIPMENT WIRE, 20 AWG, 19/0.2

Pack size: **100 x MTR**

- Cross Sectional Area: 0.6 mm²
- Sheath Colour: Red
- American Wire Gauge: 20 AWG
- Core Strands: 19/0.2 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 600 V
- Outer Diameter: 1.6 mm



8417443 0.6 mm²

RS PRO WHITE 0.6 MM² PTFE EQUIPMENT WIRE, 20 AWG, 19/0.2

Pack size: **100 x MTR**

- Cross Sectional Area: 0.6 mm²
- Sheath Colour: White
- American Wire Gauge: 20 AWG
- Core Strands: 19/0.2 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 600 V
- Outer Diameter: 1.6 mm



8417447 0.6 mm²

RS PRO BLUE 0.6 MM² PTFE EQUIPMENT WIRE, 20 AWG, 19/0.2

Pack size: **100 x MTR**

- Cross Sectional Area: 0.6 mm²
- Sheath Colour: Blue
- American Wire Gauge: 20 AWG
- Core Strands: 19/0.2 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 600 V
- Outer Diameter: 1.6 mm



8417453 0.6 mm²

RS PRO ORANGE 0.6 MM² PTFE EQUIPMENT WIRE, 20 AWG, 19/0.2

Pack size: **100 x MTR**

- Cross Sectional Area: 0.6 mm²
- Sheath Colour: Orange
- American Wire Gauge: 20 AWG
- Core Strands: 19/0.2 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 600 V
- Outer Diameter: 1.6 mm



8417459 0.6 mm²

RS PRO GREEN 0.6 MM² PTFE EQUIPMENT WIRE, 20 AWG, 19/0.2

Pack size: **100 x MTR**

- Cross Sectional Area: 0.6 mm²
- Sheath Colour: Green
- American Wire Gauge: 20 AWG
- Core Strands: 19/0.2 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 600 V
- Outer Diameter: 1.6 mm



8417462 0.6 mm²

RS PRO BROWN 0.6 MM² HARSH ENVIRONMENT WIRE, 20 AWG, 19/0.2

Pack size: **100 x MTR**

- Cross Sectional Area: 0.6 mm²
- Sheath Colour: Brown
- American Wire Gauge: 20 AWG
- Core Strands: 19/0.2 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 600 V
- Outer Diameter: 1.6 mm



8417465 0.6 mm²

RS PRO PURPLE 0.6 MM² HARSH ENVIRONMENT WIRE, 20 AWG, 19/0.2

Pack size: **100 x MTR**

- Cross Sectional Area: 0.6 mm²
- Sheath Colour: Purple
- American Wire Gauge: 20 AWG
- Core Strands: 19/0.2 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 600 V
- Outer Diameter: 1.6 mm



8417469 0.6 mm²

RS PRO PINK 3 MM² HARSH ENVIRONMENT WIRE, 12 AWG,

Pack size: **25 x MTR**

- Cross Sectional Area: 3 mm²
- Sheath Colour: Pink
- American Wire Gauge: 12 AWG
- Core Strands: 19/0.45 mm
- Length: 25 m
- Insulation Material: PTFE
- Voltage Rating: 1 kV
- Outer Diameter: 3.31 mm



8417471 3 mm²

RS PRO GREY 0.6 MM² HARSH ENVIRONMENT WIRE, 20 AWG, 19/0.2

Pack size: **100 x MTR**

- Cross Sectional Area: 0.6 mm²
- Sheath Colour: Grey
- American Wire Gauge: 20 AWG
- Core Strands: 19/0.2 mm
- Length: 100 m
- Insulation Material: PTFE
- Voltage Rating: 600 V
- Outer Diameter: 1.6 mm



8417478 0.6 mm²

RS PRO YELLOW 0.2 MM² HOOK UP WIRE, 24 AWG, 17/0.16 MM, 100M,Pack size: **100 x EA**

- Cross Sectional Area: 0.2 mm²
- Sheath Colour: Yellow
- American Wire Gauge: 24 AWG
- Core Strands: 17/0.16 mm
- Length: 100 m
- Insulation Material: XLPE
- Voltage Rating: 600 V
- Outer Diameter: 2.2 mm

**8724379** 0.2 mm²**RS PRO RED 0.33 MM² HOOK UP WIRE, 22 AWG, 17/0.16 MM, 100M,**Pack size: **100 x EA**

- Cross Sectional Area: 0.33 mm²
- Sheath Colour: Red
- American Wire Gauge: 22 AWG
- Core Strands: 17/0.16 mm
- Length: 100 m
- Insulation Material: XLPE
- Voltage Rating: 600 V
- Outer Diameter: 2.4 mm

**8724391** 0.33 mm²**RS PRO BLACK 0.33 MM² HOOK UP WIRE, 22 AWG, 17/0.16 MM, 100M,**Pack size: **100 x EA**

- Cross Sectional Area: 0.33 mm²
- Sheath Colour: Black
- American Wire Gauge: 22 AWG
- Core Strands: 17/0.16 mm
- Length: 100 m
- Insulation Material: XLPE
- Voltage Rating: 600 V
- Outer Diameter: 2.4 mm

**8724394** 0.33 mm²**RS PRO WHITE 0.33 MM² HOOK UP WIRE, 22 AWG, 17/0.16 MM, 100M,**Pack size: **100 x EA**

- Cross Sectional Area: 0.33 mm²
- Sheath Colour: White
- American Wire Gauge: 22 AWG
- Core Strands: 17/0.16 mm
- Length: 100 m
- Insulation Material: XLPE
- Voltage Rating: 600 V
- Outer Diameter: 2.4 mm

**8724404** 0.33 mm²**RS PRO BROWN 0.08 MM² HOOK UP WIRE, 28 AWG, 7/0.12 MM, 100M,**Pack size: **100 x MTR**

- Cross Sectional Area: 0.08 mm²
- Sheath Colour: Brown
- American Wire Gauge: 28 AWG
- Core Strands: 7/0.12 mm
- Length: 100 m
- Insulation Material: MPPE
- Voltage Rating: 600 V
- Outer Diameter: 0.9 mm

**8724420** 0.08 mm²**RS PRO BLACK 0.08 MM² HOOK UP WIRE, 28 AWG, 7/0.12 MM, 100M,**Pack size: **100 x MTR**

- Cross Sectional Area: 0.08 mm²
- Sheath Colour: Black
- American Wire Gauge: 28 AWG
- Core Strands: 7/0.12 mm
- Length: 100 m
- Insulation Material: MPPE
- Voltage Rating: 600 V
- Outer Diameter: 0.9 mm

**8724426** 0.08 mm²**RS PRO BLUE 0.08 MM² HOOK UP WIRE, 28 AWG, 7/0.12 MM, 100M,**Pack size: **100 x MTR**

- Cross Sectional Area: 0.08 mm²
- Sheath Colour: Blue
- American Wire Gauge: 28 AWG
- Core Strands: 7/0.12 mm
- Length: 100 m
- Insulation Material: MPPE
- Voltage Rating: 600 V
- Outer Diameter: 0.9 mm

**8724432** 0.08 mm²**RS PRO WHITE 0.08 MM² HOOK UP WIRE, 28 AWG, 7/0.12 MM, 100M,**Pack size: **100 x MTR**

- Cross Sectional Area: 0.08 mm²
- Sheath Colour: White
- American Wire Gauge: 28 AWG
- Core Strands: 7/0.12 mm
- Length: 100 m
- Insulation Material: MPPE
- Voltage Rating: 600 V
- Outer Diameter: 0.9 mm

**8724436** 0.08 mm²**RS PRO RED 0.08 MM² HOOK UP WIRE, 28 AWG, 7/0.12 MM, 100M,**Pack size: **100 x MTR**

- Cross Sectional Area: 0.08 mm²
- Sheath Colour: Red
- American Wire Gauge: 28 AWG
- Core Strands: 7/0.12 mm
- Length: 100 m
- Insulation Material: MPPE
- Voltage Rating: 600 V
- Outer Diameter: 0.9 mm

**8724439** 0.08 mm²**RS PRO ORANGE 0.08 MM² HOOK UP WIRE, 28 AWG, 7/0.12 MM, 100M,**Pack size: **100 x MTR**

- Cross Sectional Area: 0.08 mm²
- Sheath Colour: Orange
- American Wire Gauge: 28 AWG
- Core Strands: 7/0.12 mm
- Length: 100 m
- Insulation Material: MPPE
- Voltage Rating: 600 V
- Outer Diameter: 0.9 mm

**8724442** 0.08 mm²**RS PRO GREEN 0.08 MM² HOOK UP WIRE, 28 AWG, 7/0.12 MM, 100M,**Pack size: **100 x MTR**

- Cross Sectional Area: 0.08 mm²
- Sheath Colour: Green
- American Wire Gauge: 28 AWG
- Core Strands: 7/0.12 mm
- Length: 100 m
- Insulation Material: MPPE
- Voltage Rating: 600 V
- Outer Diameter: 0.9 mm

**8724445** 0.08 mm²**RS PRO YELLOW 0.08 MM² HOOK UP WIRE, 28 AWG, 7/0.12 MM, 100M,**Pack size: **100 x MTR**

- Cross Sectional Area: 0.08 mm²
- Sheath Colour: Yellow
- American Wire Gauge: 28 AWG
- Core Strands: 7/0.12 mm
- Length: 100 m
- Insulation Material: MPPE
- Voltage Rating: 600 V
- Outer Diameter: 0.9 mm

**8724448** 0.08 mm²**RS PRO BLACK 0.13 MM² HOOK UP WIRE, 26 AWG, 7/0.16 MM, 100M,**Pack size: **100 x MTR**

- Cross Sectional Area: 0.13 mm²
- Sheath Colour: Black
- American Wire Gauge: 26 AWG
- Core Strands: 7/0.16 mm
- Length: 100 m
- Insulation Material: MPPE
- Voltage Rating: 600 V
- Outer Diameter: 1 mm

**8724458** 0.13 mm²**RS PRO RED 0.13 MM² HOOK UP WIRE, 26 AWG, 7/0.16 MM, 100M,**Pack size: **100 x MTR**

- Cross Sectional Area: 0.13 mm²
- Sheath Colour: Red
- American Wire Gauge: 26 AWG
- Core Strands: 7/0.16 mm
- Length: 100 m
- Insulation Material: MPPE
- Voltage Rating: 600 V
- Outer Diameter: 1 mm

**8724460** 0.13 mm²**RS PRO BLUE 0.13 MM² HOOK UP WIRE, 26 AWG, 7/0.16 MM, 100M,**Pack size: **100 x MTR**

- Cross Sectional Area: 0.13 mm²
- Sheath Colour: Blue
- American Wire Gauge: 26 AWG
- Core Strands: 7/0.16 mm
- Length: 100 m
- Insulation Material: MPPE
- Voltage Rating: 600 V
- Outer Diameter: 1 mm

**8724464** 0.13 mm²**RS PRO BROWN 0.13 MM² HOOK UP WIRE, 26 AWG, 7/0.16 MM, 100M,**Pack size: **100 x MTR**

- Cross Sectional Area: 0.13 mm²
- Sheath Colour: Brown
- American Wire Gauge: 26 AWG
- Core Strands: 7/0.16 mm
- Length: 100 m
- Insulation Material: MPPE
- Voltage Rating: 600 V
- Outer Diameter: 1 mm

**8724467** 0.13 mm²

RS PRO WHITE 0.13 MM² HOOK UP WIRE, 26 AWG, 7/0.16 MM, 100M,

Pack size: **100 x MTR**

- Cross Sectional Area: 0.13 mm²
- Sheath Colour: White
- American Wire Gauge: 26 AWG
- Core Strands: 7/0.16 mm
- Length: 100 m
- Insulation Material: MPPE
- Voltage Rating: 600 V
- Outer Diameter: 1 mm



8724473 0.13 mm²

RS PRO GREEN 0.13 MM² HOOK UP WIRE, 26 AWG, 7/0.16 MM, 100M,

Pack size: **100 x MTR**

- Cross Sectional Area: 0.13 mm²
- Sheath Colour: Green
- American Wire Gauge: 26 AWG
- Core Strands: 7/0.16 mm
- Length: 100 m
- Insulation Material: MPPE
- Voltage Rating: 600 V
- Outer Diameter: 1 mm



8724476 0.13 mm²

RS PRO RED 0.2 MM² HOOK UP WIRE, 24 AWG, 11/0.16 MM, 100M, MPPE

Pack size: **100 x MTR**

- Cross Sectional Area: 0.2 mm²
- Sheath Colour: Red
- American Wire Gauge: 24 AWG
- Core Strands: 11/0.16 mm
- Length: 100 m
- Insulation Material: MPPE
- Voltage Rating: 600 V
- Outer Diameter: 1.12 mm



8724492 0.2 mm²

RS PRO BLACK 0.2 MM² HOOK UP WIRE, 24 AWG, 11/0.16 MM, 100M,

Pack size: **100 x MTR**

- Cross Sectional Area: 0.2 mm²
- Sheath Colour: Black
- American Wire Gauge: 24 AWG
- Core Strands: 11/0.16 mm
- Length: 100 m
- Insulation Material: MPPE
- Voltage Rating: 600 V
- Outer Diameter: 1.12 mm



8724495 0.2 mm²

RS PRO BLUE 0.2 MM² HOOK UP WIRE, 24 AWG, 11/0.16 MM, 100M,

Pack size: **100 x MTR**

- Cross Sectional Area: 0.2 mm²
- Sheath Colour: Blue
- American Wire Gauge: 24 AWG
- Core Strands: 11/0.16 mm
- Length: 100 m
- Insulation Material: MPPE
- Voltage Rating: 600 V
- Outer Diameter: 1.12 mm



8724502 0.2 mm²

RS PRO WHITE 0.2 MM² HOOK UP WIRE, 24 AWG, 11/0.16 MM, 100M,

Pack size: **100 x MTR**

- Cross Sectional Area: 0.2 mm²
- Sheath Colour: White
- American Wire Gauge: 24 AWG
- Core Strands: 11/0.16 mm
- Length: 100 m
- Insulation Material: MPPE
- Voltage Rating: 600 V
- Outer Diameter: 1.12 mm



8724505 0.2 mm²

RS PRO GREEN 0.2 MM² HOOK UP WIRE, 24 AWG, 11/0.16 MM, 100M,

Pack size: **100 x MTR**

- Cross Sectional Area: 0.2 mm²
- Sheath Colour: Green
- American Wire Gauge: 24 AWG
- Core Strands: 11/0.16 mm
- Length: 100 m
- Insulation Material: MPPE
- Voltage Rating: 600 V
- Outer Diameter: 1.12 mm



8724509 0.2 mm²

RS PRO GREY 0.2 MM² HOOK UP WIRE, 24 AWG, 11/0.16 MM, 100M,

Pack size: **100 x MTR**

- Cross Sectional Area: 0.2 mm²
- Sheath Colour: Grey
- American Wire Gauge: 24 AWG
- Core Strands: 11/0.16 mm
- Length: 100 m
- Insulation Material: MPPE
- Voltage Rating: 600 V
- Outer Diameter: 1.12 mm



8724515 0.2 mm²

RS PRO YELLOW 0.2 MM² HOOK UP WIRE, 24 AWG, 11/0.16 MM, 100M,

Pack size: **100 x MTR**

- Cross Sectional Area: 0.2 mm²
- Sheath Colour: Yellow
- American Wire Gauge: 24 AWG
- Core Strands: 11/0.16 mm
- Length: 100 m
- Insulation Material: MPPE
- Voltage Rating: 600 V
- Outer Diameter: 1.12 mm



8724518 0.2 mm²

RS PRO BROWN 0.33 MM² HOOK UP WIRE, 22 AWG, 7/0.12 MM, 100M,

Pack size: **100 x MTR**

- Cross Sectional Area: 0.33 mm²
- Sheath Colour: Brown
- American Wire Gauge: 22 AWG
- Core Strands: 7/0.12 mm
- Length: 100 m
- Insulation Material: MPPE
- Voltage Rating: 600 V
- Outer Diameter: 1.3 mm



8724521 0.33 mm²

RS PRO BLACK 0.33 MM² HOOK UP WIRE, 22 AWG, 7/0.12 MM, 100M,

Pack size: **100 x MTR**

- Cross Sectional Area: 0.33 mm²
- Sheath Colour: Black
- American Wire Gauge: 22 AWG
- Core Strands: 7/0.12 mm
- Length: 100 m
- Insulation Material: MPPE
- Voltage Rating: 600 V
- Outer Diameter: 1.3 mm



8724527 0.33 mm²

RS PRO RED 0.33 MM² HOOK UP WIRE, 22 AWG, 7/0.12 MM, 100M,

Pack size: **100 x MTR**

- Cross Sectional Area: 0.33 mm²
- Sheath Colour: Red
- American Wire Gauge: 22 AWG
- Core Strands: 7/0.12 mm
- Length: 100 m
- Insulation Material: MPPE
- Voltage Rating: 600 V
- Outer Diameter: 1.3 mm



8724530 0.33 mm²

RS PRO BLUE 0.33 MM² HOOK UP WIRE, 22 AWG, 7/0.12 MM, 100M,

Pack size: **100 x MTR**

- Cross Sectional Area: 0.33 mm²
- Sheath Colour: Blue
- American Wire Gauge: 22 AWG
- Core Strands: 7/0.12 mm
- Length: 100 m
- Insulation Material: MPPE
- Voltage Rating: 600 V
- Outer Diameter: 1.3 mm



8724533 0.33 mm²

RS PRO WHITE 0.33 MM² HOOK UP WIRE, 22 AWG, 7/0.12 MM, 100M,

Pack size: **100 x MTR**

- Cross Sectional Area: 0.33 mm²
- Sheath Colour: White
- American Wire Gauge: 22 AWG
- Core Strands: 7/0.12 mm
- Length: 100 m
- Insulation Material: MPPE
- Voltage Rating: 600 V
- Outer Diameter: 1.3 mm



8724537 0.33 mm²

RS PRO ORANGE 0.33 MM² HOOK UP WIRE, 22 AWG, 7/0.12 MM, 100M,

Pack size: **100 x MTR**

- Cross Sectional Area: 0.33 mm²
- Sheath Colour: Orange
- American Wire Gauge: 22 AWG
- Core Strands: 7/0.12 mm
- Length: 100 m
- Insulation Material: MPPE
- Voltage Rating: 600 V
- Outer Diameter: 1.3 mm



8724543 0.33 mm²

RS PRO GREEN 0.33 MM² HOOK UP WIRE, 22 AWG, 7/0.12 MM, 100M,

Pack size: **100 x MTR**

- Cross Sectional Area: 0.33 mm²
- Sheath Colour: Green
- American Wire Gauge: 22 AWG
- Core Strands: 7/0.12 mm
- Length: 100 m
- Insulation Material: MPPE
- Voltage Rating: 600 V
- Outer Diameter: 1.3 mm



8724546 0.33 mm²

RS PRO YELLOW 0.33 MM² HOOK UP WIRE, 22 AWG, 7/0.12 MM, 100M,Pack size: **100 x MTR**

- Cross Sectional Area: 0.33 mm²
- Sheath Colour: Yellow
- American Wire Gauge: 22 AWG
- Core Strands: 7/0.12 mm
- Length: 100 m
- Insulation Material: MPPE
- Voltage Rating: 600 V
- Outer Diameter: 1.3 mm

**8724549** 0.33 mm²**RS PRO RED 0.13 MM² HOOK UP WIRE, 26 AWG, 7/0.16 MM, 100M,**Pack size: **100 x MTR**

- Cross Sectional Area: 0.13 mm²
- Sheath Colour: Red
- American Wire Gauge: 26 AWG
- Core Strands: 7/0.16 mm
- Length: 100 m
- Insulation Material: PVC
- Voltage Rating: 600 V
- Outer Diameter: 2.1 mm

**8724593** 0.13 mm²**RS PRO YELLOW 0.2 MM² HOOK UP WIRE, 24 AWG, 11/0.16 MM, 100M,**Pack size: **100 x MTR**

- Cross Sectional Area: 0.2 mm²
- Sheath Colour: Yellow
- American Wire Gauge: 24 AWG
- Core Strands: 11/0.16 mm
- Length: 100 m
- Insulation Material: PVC
- Voltage Rating: 600 V
- Outer Diameter: 2.2 mm

**8724622** 0.2 mm²**RS PRO YELLOW 0.33 MM² HOOK UP WIRE, 22 AWG, 17/0.16 MM, 100M,**Pack size: **100 x MTR**

- Cross Sectional Area: 0.33 mm²
- Sheath Colour: Yellow
- American Wire Gauge: 22 AWG
- Core Strands: 17/0.16 mm
- Length: 100 m
- Insulation Material: PVC
- Voltage Rating: 600 V
- Outer Diameter: 2.4 mm

**8724640** 0.33 mm²**RS PRO BLACK 0.13 MM² HOOK UP WIRE, 26 AWG, 7/0.16 MM, 100M,**Pack size: **100 x MTR**

- Cross Sectional Area: 0.13 mm²
- Sheath Colour: Black
- American Wire Gauge: 26 AWG
- Core Strands: 7/0.16 mm
- Length: 100 m
- Insulation Material: XLPE
- Voltage Rating: 300 V
- Outer Diameter: 1.3 mm

**8725136** 0.13 mm²**RS PRO RED 0.13 MM² HOOK UP WIRE, 26 AWG, 7/0.16 MM, 100M,**Pack size: **100 x MTR**

- Cross Sectional Area: 0.13 mm²
- Sheath Colour: Red
- American Wire Gauge: 26 AWG
- Core Strands: 7/0.16 mm
- Length: 100 m
- Insulation Material: XLPE
- Voltage Rating: 300 V
- Outer Diameter: 1.3 mm

**8725151** 0.13 mm²**RS PRO BLUE 0.13 MM² HOOK UP WIRE, 26 AWG, 7/0.16 MM, 100M,**Pack size: **100 x MTR**

- Cross Sectional Area: 0.13 mm²
- Sheath Colour: Blue
- American Wire Gauge: 26 AWG
- Core Strands: 7/0.16 mm
- Length: 100 m
- Insulation Material: XLPE
- Voltage Rating: 300 V
- Outer Diameter: 1.3 mm

**8725167** 0.13 mm²**RS PRO BLACK 0.2 MM² HOOK UP WIRE, 24 AWG, 11/0.16 MM, 100M,**Pack size: **100 x MTR**

- Cross Sectional Area: 0.2 mm²
- Sheath Colour: Black
- American Wire Gauge: 24 AWG
- Core Strands: 11/0.16 mm
- Length: 100 m
- Insulation Material: XLPE
- Voltage Rating: 300 V
- Outer Diameter: 1.43 mm

**8725205** 0.2 mm²**RS PRO RED 0.2 MM² HOOK UP WIRE, 24 AWG, 11/0.16 MM, 100M, XLPE**Pack size: **100 x MTR**

- Cross Sectional Area: 0.2 mm²
- Sheath Colour: Red
- American Wire Gauge: 24 AWG
- Core Strands: 11/0.16 mm
- Length: 100 m
- Insulation Material: XLPE
- Voltage Rating: 300 V
- Outer Diameter: 1.43 mm

**8725215** 0.2 mm²**RS PRO BROWN 0.2 MM² HOOK UP WIRE, 24 AWG, 11/0.16 MM, 100M,**Pack size: **100 x MTR**

- Cross Sectional Area: 0.2 mm²
- Sheath Colour: Brown
- American Wire Gauge: 24 AWG
- Core Strands: 11/0.16 mm
- Length: 100 m
- Insulation Material: XLPE
- Voltage Rating: 300 V
- Outer Diameter: 1.43 mm

**8725218** 0.2 mm²**RS PRO BLUE 0.2 MM² HOOK UP WIRE, 24 AWG, 11/0.16 MM, 100M,**Pack size: **100 x MTR**

- Cross Sectional Area: 0.2 mm²
- Sheath Colour: Blue
- American Wire Gauge: 24 AWG
- Core Strands: 11/0.16 mm
- Length: 100 m
- Insulation Material: XLPE
- Voltage Rating: 300 V
- Outer Diameter: 1.43 mm

**8725221** 0.2 mm²**RS PRO WHITE 0.2 MM² HOOK UP WIRE, 24 AWG, 11/0.16 MM, 100M,**Pack size: **100 x MTR**

- Cross Sectional Area: 0.2 mm²
- Sheath Colour: White
- American Wire Gauge: 24 AWG
- Core Strands: 11/0.16 mm
- Length: 100 m
- Insulation Material: XLPE
- Voltage Rating: 300 V
- Outer Diameter: 1.43 mm

**8725233** 0.2 mm²**RS PRO YELLOW 0.2 MM² HOOK UP WIRE, 24 AWG, 11/0.16 MM, 100M,**Pack size: **100 x MTR**

- Cross Sectional Area: 0.2 mm²
- Sheath Colour: Yellow
- American Wire Gauge: 24 AWG
- Core Strands: 11/0.16 mm
- Length: 100 m
- Insulation Material: XLPE
- Voltage Rating: 300 V
- Outer Diameter: 1.43 mm

**8725243** 0.2 mm²**RS PRO GREEN 0.2 MM² HOOK UP WIRE, 24 AWG, 11/0.16 MM, 100M,**Pack size: **100 x MTR**

- Cross Sectional Area: 0.2 mm²
- Sheath Colour: Green
- American Wire Gauge: 24 AWG
- Core Strands: 11/0.16 mm
- Length: 100 m
- Insulation Material: XLPE
- Voltage Rating: 300 V
- Outer Diameter: 1.43 mm

**8725246** 0.2 mm²**RS PRO BLACK 0.33 MM² HOOK UP WIRE, 22 AWG, 17/0.16 MM, 100M,**Pack size: **100 x MTR**

- Cross Sectional Area: 0.33 mm²
- Sheath Colour: Black
- American Wire Gauge: 22 AWG
- Core Strands: 17/0.16 mm
- Length: 100 m
- Insulation Material: XLPE
- Voltage Rating: 300 V
- Outer Diameter: 1.58 mm

**8725274** 0.33 mm²**RS PRO BROWN 0.33 MM² HOOK UP WIRE, 22 AWG, 17/0.16 MM, 100M,**Pack size: **100 x MTR**

- Cross Sectional Area: 0.33 mm²
- Sheath Colour: Brown
- American Wire Gauge: 22 AWG
- Core Strands: 17/0.16 mm
- Length: 100 m
- Insulation Material: XLPE
- Voltage Rating: 300 V
- Outer Diameter: 1.58 mm

**8725277** 0.33 mm²

RS PRO RED 0.33 MM² HOOK UP WIRE, 22 AWG, 17/0.16 MM, 100M,

Pack size: **100 x MTR**

- Cross Sectional Area: 0.33 mm²
- Sheath Colour: Red
- American Wire Gauge: 22 AWG
- Core Strands: 17/0.16 mm
- Length: 100 m
- Insulation Material: XLPE
- Voltage Rating: 300 V
- Outer Diameter: 1.58 mm



8725280 0.33 mm²

RS PRO WHITE 0.33 MM² HOOK UP WIRE, 22 AWG, 17/0.16 MM, 100M,

Pack size: **100 x MTR**

- Cross Sectional Area: 0.33 mm²
- Sheath Colour: White
- American Wire Gauge: 22 AWG
- Core Strands: 17/0.16 mm
- Length: 100 m
- Insulation Material: XLPE
- Voltage Rating: 300 V
- Outer Diameter: 1.58 mm



8725293 0.33 mm²

RS PRO BLUE 0.33 MM² HOOK UP WIRE, 22 AWG, 17/0.16 MM, 100M,

Pack size: **100 x MTR**

- Cross Sectional Area: 0.33 mm²
- Sheath Colour: Blue
- American Wire Gauge: 22 AWG
- Core Strands: 17/0.16 mm
- Length: 100 m
- Insulation Material: XLPE
- Voltage Rating: 300 V
- Outer Diameter: 1.58 mm



8725296 0.33 mm²

RS PRO YELLOW 0.33 MM² HOOK UP WIRE, 22 AWG, 17/0.16 MM, 100M,

Pack size: **100 x MTR**

- Cross Sectional Area: 0.33 mm²
- Sheath Colour: Yellow
- American Wire Gauge: 22 AWG
- Core Strands: 17/0.16 mm
- Length: 100 m
- Insulation Material: XLPE
- Voltage Rating: 300 V
- Outer Diameter: 1.58 mm



8725300 0.33 mm²

RS PRO GREEN 0.33 MM² HOOK UP WIRE, 22 AWG, 17/0.16 MM, 100M,

Pack size: **100 x MTR**

- Cross Sectional Area: 0.33 mm²
- Sheath Colour: Green
- American Wire Gauge: 22 AWG
- Core Strands: 17/0.16 mm
- Length: 100 m
- Insulation Material: XLPE
- Voltage Rating: 300 V
- Outer Diameter: 1.58 mm



8725303 0.33 mm²

RS PRO ORANGE 0.33 MM² HOOK UP WIRE, 22 AWG, 17/0.16 MM, 100M,

Pack size: **100 x MTR**

- Cross Sectional Area: 0.33 mm²
- Sheath Colour: Orange
- American Wire Gauge: 22 AWG
- Core Strands: 17/0.16 mm
- Length: 100 m
- Insulation Material: XLPE
- Voltage Rating: 300 V
- Outer Diameter: 1.58 mm



8725312 0.33 mm²

RS PRO PURPLE 0.33 MM² HOOK UP WIRE, 22 AWG, 17/0.16 MM, 100M,

Pack size: **100 x MTR**

- Cross Sectional Area: 0.33 mm²
- Sheath Colour: Purple
- American Wire Gauge: 22 AWG
- Core Strands: 17/0.16 mm
- Length: 100 m
- Insulation Material: XLPE
- Voltage Rating: 300 V
- Outer Diameter: 1.58 mm



8725322 0.33 mm²

RS PRO GREY 0.33 MM² HOOK UP WIRE, 22 AWG, 17/0.16 MM, 100M,

Pack size: **100 x MTR**

- Cross Sectional Area: 0.33 mm²
- Sheath Colour: Grey
- American Wire Gauge: 22 AWG
- Core Strands: 17/0.16 mm
- Length: 100 m
- Insulation Material: XLPE
- Voltage Rating: 300 V
- Outer Diameter: 1.58 mm



8725325 0.33 mm²

RS PRO BLACK 0.08 MM² HOOK UP WIRE, 28 AWG, 7/0.12 MM, 100M,

Pack size: **100 x MTR**

- Cross Sectional Area: 0.08 mm²
- Sheath Colour: Black
- American Wire Gauge: 28 AWG
- Core Strands: 7/0.12 mm
- Length: 100 m
- Insulation Material: XLPE
- Voltage Rating: 6 kV dc
- Outer Diameter: 1.2 mm



8738876 0.08 mm²

RS PRO RED 0.26 MM² EQUIPMENT WIRE, 23 AWG, 3/0.07 MM, 100M,

Pack size: **100 x MTR**

- Cross Sectional Area: 0.26 mm²
- Sheath Colour: Red
- American Wire Gauge: 23 AWG
- Core Strands: 3/0.07 mm
- Length: 100 m
- Insulation Material: PVC
- Outer Diameter: 1.7 mm
- Voltage Rating: 250 V



8738863 0.26 mm²

RS PRO RED 0.13 MM² HOOK UP WIRE, 26 AWG, 7/0.16 MM, 100M,

Pack size: **100 x MTR**

- Cross Sectional Area: 0.13 mm²
- Sheath Colour: Red
- American Wire Gauge: 26 AWG
- Core Strands: 7/0.16 mm
- Length: 100 m
- Insulation Material: XLPE
- Voltage Rating: 6 kV dc
- Outer Diameter: 1.4 mm



8738911 0.13 mm²

RS PRO BLUE 0.13 MM² HOOK UP WIRE, 26 AWG, 7/0.16 MM, 100M,

Pack size: **100 x MTR**

- Cross Sectional Area: 0.13 mm²
- Sheath Colour: Blue
- American Wire Gauge: 26 AWG
- Core Strands: 7/0.16 mm
- Length: 100 m
- Insulation Material: XLPE
- Voltage Rating: 6 kV dc
- Outer Diameter: 1.4 mm



8738914 0.13 mm²

RS PRO BLACK 0.2 MM² HOOK UP WIRE, 24 AWG, 11/0.16 MM, 100M,

Pack size: **100 x MTR**

- Cross Sectional Area: 0.2 mm²
- Sheath Colour: Black
- American Wire Gauge: 24 AWG
- Core Strands: 11/0.16 mm
- Length: 100 m
- Insulation Material: XLPE
- Voltage Rating: 6 kV dc
- Outer Diameter: 1.5 mm



8738930 0.2 mm²

RS PRO RED 0.2 MM² HOOK UP WIRE, 24 AWG, 11/0.16 MM, 100M, XLPE

Pack size: **100 x MTR**

- Cross Sectional Area: 0.2 mm²
- Sheath Colour: Red
- American Wire Gauge: 24 AWG
- Core Strands: 11/0.16 mm
- Length: 100 m
- Insulation Material: XLPE
- Voltage Rating: 6 kV dc
- Outer Diameter: 1.5 mm



8738942 0.2 mm²

RS PRO BLUE 0.2 MM² HOOK UP WIRE, 24 AWG, 11/0.16 MM, 100M,

Pack size: **100 x MTR**

- Cross Sectional Area: 0.2 mm²
- Sheath Colour: Blue
- American Wire Gauge: 24 AWG
- Core Strands: 11/0.16 mm
- Length: 100 m
- Insulation Material: XLPE
- Voltage Rating: 6 kV dc
- Outer Diameter: 1.5 mm



8738946 0.2 mm²

RS PRO BROWN 0.2 MM² HOOK UP WIRE, 24 AWG, 11/0.16 MM, 100M,

Pack size: **100 x MTR**

- Cross Sectional Area: 0.2 mm²
- Sheath Colour: Brown
- American Wire Gauge: 24 AWG
- Core Strands: 11/0.16 mm
- Length: 100 m
- Insulation Material: XLPE
- Voltage Rating: 6 kV dc
- Outer Diameter: 1.5 mm



8738949 0.2 mm²

RS PRO YELLOW 0.2 MM² HOOK UP WIRE, 24 AWG, 11/0.16 MM, 100M,Pack size: **100 x MTR**

- Cross Sectional Area: 0.2 mm²
- Sheath Colour: Yellow
- American Wire Gauge: 24 AWG
- Core Strands: 11/0.16 mm
- Length: 100 m
- Insulation Material: XLPE
- Voltage Rating: 6 kV dc
- Outer Diameter: 1.5 mm

**8738952** 0.2 mm²**RS PRO WHITE 0.2 MM² HOOK UP WIRE, 24 AWG, 11/0.16 MM, 100M,**Pack size: **100 x MTR**

- Cross Sectional Area: 0.2 mm²
- Sheath Colour: White
- American Wire Gauge: 24 AWG
- Core Strands: 11/0.16 mm
- Length: 100 m
- Insulation Material: XLPE
- Voltage Rating: 6 kV dc
- Outer Diameter: 1.5 mm

**8738955** 0.2 mm²**RS PRO GREEN 0.2 MM² HOOK UP WIRE, 24 AWG, 11/0.16 MM, 100M,**Pack size: **100 x MTR**

- Cross Sectional Area: 0.2 mm²
- Sheath Colour: Green
- American Wire Gauge: 24 AWG
- Core Strands: 11/0.16 mm
- Length: 100 m
- Insulation Material: XLPE
- Voltage Rating: 6 kV dc
- Outer Diameter: 1.5 mm

**8738958** 0.2 mm²**RS PRO ORANGE 0.2 MM² HOOK UP WIRE, 24 AWG, 11/0.16 MM, 100M,**Pack size: **100 x MTR**

- Cross Sectional Area: 0.2 mm²
- Sheath Colour: Orange
- American Wire Gauge: 24 AWG
- Core Strands: 11/0.16 mm
- Length: 100 m
- Insulation Material: XLPE
- Voltage Rating: 6 kV dc
- Outer Diameter: 1.5 mm

**8738961** 0.2 mm²**RS PRO GREY 0.2 MM² HOOK UP WIRE, 24 AWG, 11/0.16 MM, 100M,**Pack size: **100 x MTR**

- Cross Sectional Area: 0.2 mm²
- Sheath Colour: Grey
- American Wire Gauge: 24 AWG
- Core Strands: 11/0.16 mm
- Length: 100 m
- Insulation Material: XLPE
- Voltage Rating: 6 kV dc
- Outer Diameter: 1.5 mm

**8738964** 0.2 mm²**RS PRO PURPLE 0.2 MM² HOOK UP WIRE, 24 AWG, 11/0.16 MM, 100M,**Pack size: **100 x MTR**

- Cross Sectional Area: 0.2 mm²
- Sheath Colour: Purple
- American Wire Gauge: 24 AWG
- Core Strands: 11/0.16 mm
- Length: 100 m
- Insulation Material: XLPE
- Voltage Rating: 6 kV dc
- Outer Diameter: 1.5 mm

**8738968** 0.2 mm²**RS PRO RED 0.33 MM² HOOK UP WIRE, 22 AWG, 17/0.16 MM, 100M,**Pack size: **100 x MTR**

- Cross Sectional Area: 0.33 mm²
- Sheath Colour: Red
- American Wire Gauge: 22 AWG
- Core Strands: 17/0.16 mm
- Length: 100 m
- Insulation Material: XLPE
- Voltage Rating: 6 kV dc
- Outer Diameter: 1.58 mm

**8738974** 0.33 mm²**RS PRO BLACK 0.33 MM² HOOK UP WIRE, 22 AWG, 17/0.16 MM, 100M,**Pack size: **100 x MTR**

- Cross Sectional Area: 0.33 mm²
- Sheath Colour: Black
- American Wire Gauge: 22 AWG
- Core Strands: 17/0.16 mm
- Length: 100 m
- Insulation Material: XLPE
- Voltage Rating: 6 kV dc
- Outer Diameter: 1.58 mm

**8738977** 0.33 mm²**RS PRO BLUE 0.33 MM² HOOK UP WIRE, 22 AWG, 17/0.16 MM, 100M,**Pack size: **100 x MTR**

- Cross Sectional Area: 0.33 mm²
- Sheath Colour: Blue
- American Wire Gauge: 22 AWG
- Core Strands: 17/0.16 mm
- Length: 100 m
- Insulation Material: XLPE
- Voltage Rating: 6 kV dc
- Outer Diameter: 1.58 mm

**8738983** 0.33 mm²**RS PRO WHITE 0.33 MM² HOOK UP WIRE, 22 AWG, 17/0.16 MM, 100M,**Pack size: **100 x MTR**

- Cross Sectional Area: 0.33 mm²
- Sheath Colour: White
- American Wire Gauge: 22 AWG
- Core Strands: 17/0.16 mm
- Length: 100 m
- Insulation Material: XLPE
- Voltage Rating: 6 kV dc
- Outer Diameter: 1.58 mm

**8738986** 0.33 mm²**RS PRO ORANGE 0.33 MM² HOOK UP WIRE, 22 AWG, 17/0.16 MM, 100M,**Pack size: **100 x MTR**

- Cross Sectional Area: 0.33 mm²
- Sheath Colour: Orange
- American Wire Gauge: 22 AWG
- Core Strands: 17/0.16 mm
- Length: 100 m
- Insulation Material: XLPE
- Voltage Rating: 6 kV dc
- Outer Diameter: 1.58 mm

**8738992** 0.33 mm²**RS PRO GREY 0.33 MM² HOOK UP WIRE, 22 AWG, 17/0.16 MM, 100M,**Pack size: **100 x MTR**

- Cross Sectional Area: 0.33 mm²
- Sheath Colour: Grey
- American Wire Gauge: 22 AWG
- Core Strands: 17/0.16 mm
- Length: 100 m
- Insulation Material: XLPE
- Voltage Rating: 6 kV dc
- Outer Diameter: 1.58 mm

**8738996** 0.33 mm²**RS PRO YELLOW 0.33 MM² HOOK UP WIRE, 22 AWG, 17/0.16 MM, 100M,**Pack size: **100 x MTR**

- Cross Sectional Area: 0.33 mm²
- Sheath Colour: Yellow
- American Wire Gauge: 22 AWG
- Core Strands: 17/0.16 mm
- Length: 100 m
- Insulation Material: XLPE
- Voltage Rating: 6 kV dc
- Outer Diameter: 1.58 mm

**8738999** 0.33 mm²**RS PRO RED 0.2 MM² HOOK UP WIRE, 24 AWG, 11/0.16 MM, 100M, PVC**Pack size: **100 x MTR**

- Cross Sectional Area: 0.2 mm²
- Sheath Colour: Red
- American Wire Gauge: 24 AWG
- Core Strands: 11/0.16 mm
- Length: 100 m
- Insulation Material: PVC
- Voltage Rating: 300 V
- Outer Diameter: 1.4 mm

**8739933** 0.2 mm²**RS PRO BLACK 0.2 MM² HOOK UP WIRE, 24 AWG, 11/0.16 MM, 100M,**Pack size: **100 x MTR**

- Cross Sectional Area: 0.2 mm²
- Sheath Colour: Black
- American Wire Gauge: 24 AWG
- Core Strands: 11/0.16 mm
- Length: 100 m
- Insulation Material: PVC
- Voltage Rating: 300 V
- Outer Diameter: 1.4 mm

**8739936** 0.2 mm²**RS PRO WHITE 0.2 MM² HOOK UP WIRE, 24 AWG, 11/0.16 MM, 100M,**Pack size: **100 x MTR**

- Cross Sectional Area: 0.2 mm²
- Sheath Colour: White
- American Wire Gauge: 24 AWG
- Core Strands: 11/0.16 mm
- Length: 100 m
- Insulation Material: PVC
- Voltage Rating: 300 V
- Outer Diameter: 1.4 mm

**8739945** 0.2 mm²

RS PRO RED 0.33 MM² HOOK UP WIRE, 22 AWG, 7/0.25 MM, 100M,

Pack size: **100 x MTR**

- Cross Sectional Area: 0.33 mm²
- Sheath Colour: Red
- American Wire Gauge: 22 AWG
- Core Strands: 7/0.25 mm
- Length: 100 m
- Insulation Material: PVC
- Voltage Rating: 300 V
- Outer Diameter: 1.6 mm



8739970 0.33 mm²

RS PRO BLUE 0.33 MM² HOOK UP WIRE, 22 AWG, 7/0.25 MM, 100M,

Pack size: **100 x MTR**

- Cross Sectional Area: 0.33 mm²
- Sheath Colour: Blue
- American Wire Gauge: 22 AWG
- Core Strands: 7/0.25 mm
- Length: 100 m
- Insulation Material: PVC
- Voltage Rating: 300 V
- Outer Diameter: 1.6 mm



8739973 0.33 mm²

RS PRO WHITE 0.33 MM² HOOK UP WIRE, 22 AWG, 7/0.25 MM, 100M,

Pack size: **100 x MTR**

- Cross Sectional Area: 0.33 mm²
- Sheath Colour: White
- American Wire Gauge: 22 AWG
- Core Strands: 7/0.25 mm
- Length: 100 m
- Insulation Material: PVC
- Voltage Rating: 300 V
- Outer Diameter: 1.6 mm



8739977 0.33 mm²

RS PRO YELLOW 0.33 MM² HOOK UP WIRE, 22 AWG, 17/0.16 MM, 100M,

Pack size: **100 x MTR**

- Cross Sectional Area: 0.33 mm²
- Sheath Colour: Yellow
- American Wire Gauge: 22 AWG
- Core Strands: 17/0.16 mm
- Length: 100 m
- Insulation Material: XLPE
- Outer Diameter: 2.4 mm
- Voltage Rating: 600 V



8740352 0.33 mm²

RS PRO BLACK 0.08 MM² HOOK UP WIRE, 28 AWG, 7/0.12 MM, 100M,

Pack size: **100 x MTR**

- Cross Sectional Area: 0.08 mm²
- Sheath Colour: Black
- American Wire Gauge: 28 AWG
- Core Strands: 7/0.12 mm
- Length: 100 m
- Insulation Material: PVC
- Outer Diameter: 1.2 mm
- Voltage Rating: 300 V



8740361 0.08 mm²

RS PRO PURPLE 0.33 MM² HOOK UP WIRE, 22 AWG, 17/0.16 MM, 100M,

Pack size: **100 x MTR**

- Cross Sectional Area: 0.33 mm²
- Sheath Colour: Purple
- American Wire Gauge: 22 AWG
- Core Strands: 17/0.16 mm
- Length: 100 m
- Insulation Material: XLPE
- Outer Diameter: 2.4 mm
- Voltage Rating: 600 V



8740368 0.33 mm²

RS PRO WHITE 0.08 MM² HOOK UP WIRE, 28 AWG, 7/0.12 MM, 100M,

Pack size: **100 x MTR**

- Cross Sectional Area: 0.08 mm²
- Sheath Colour: White
- American Wire Gauge: 28 AWG
- Core Strands: 7/0.12 mm
- Length: 100 m
- Insulation Material: PVC
- Outer Diameter: 1.2 mm
- Voltage Rating: 300 V



8740371 0.08 mm²

RS PRO RED 0.08 MM² HOOK UP WIRE, 28 AWG, 7/0.12 MM, 100M,

Pack size: **100 x MTR**

- Cross Sectional Area: 0.08 mm²
- Sheath Colour: Red
- American Wire Gauge: 28 AWG
- Core Strands: 7/0.12 mm
- Length: 100 m
- Insulation Material: PVC
- Outer Diameter: 1.2 mm
- Voltage Rating: 300 V



8740374 0.08 mm²

RS PRO BLUE 0.08 MM² HOOK UP WIRE, 28 AWG, 7/0.12 MM, 100M,

Pack size: **100 x MTR**

- Cross Sectional Area: 0.08 mm²
- Sheath Colour: Blue
- American Wire Gauge: 28 AWG
- Core Strands: 7/0.12 mm
- Length: 100 m
- Insulation Material: PVC
- Outer Diameter: 1.2 mm
- Voltage Rating: 300 V



8740377 0.08 mm²

RS PRO GREEN 0.08 MM² HOOK UP WIRE, 28 AWG, 7/0.12 MM, 100M,

Pack size: **100 x MTR**

- Cross Sectional Area: 0.08 mm²
- Sheath Colour: Green
- American Wire Gauge: 28 AWG
- Core Strands: 7/0.12 mm
- Length: 100 m
- Insulation Material: PVC
- Outer Diameter: 1.2 mm
- Voltage Rating: 300 V



8740380 0.08 mm²

RS PRO BLACK 0.13 MM² HOOK UP WIRE, 26 AWG, 7/0.16 MM, 100M,

Pack size: **100 x MTR**

- Cross Sectional Area: 0.13 mm²
- Sheath Colour: Black
- American Wire Gauge: 26 AWG
- Core Strands: 7/0.16 mm
- Length: 100 m
- Insulation Material: PVC
- Outer Diameter: 1.3 mm
- Voltage Rating: 300 V



8740393 0.13 mm²

RS PRO BLUE 0.13 MM² HOOK UP WIRE, 26 AWG, 7/0.16 MM, 100M,

Pack size: **100 x MTR**

- Cross Sectional Area: 0.13 mm²
- Sheath Colour: Blue
- American Wire Gauge: 26 AWG
- Core Strands: 7/0.16 mm
- Length: 100 m
- Insulation Material: PVC
- Outer Diameter: 1.3 mm
- Voltage Rating: 300 V



8740400 0.13 mm²

RS PRO RED 0.13 MM² HOOK UP WIRE, 26 AWG, 7/0.16 MM, 100M,

Pack size: **100 x MTR**

- Cross Sectional Area: 0.13 mm²
- Sheath Colour: Red
- American Wire Gauge: 26 AWG
- Core Strands: 7/0.16 mm
- Length: 100 m
- Insulation Material: PVC
- Outer Diameter: 1.3 mm
- Voltage Rating: 300 V



8740406 0.13 mm²

RS PRO YELLOW 0.13 MM² HOOK UP WIRE, 26 AWG, 7/0.16 MM, 100M,

Pack size: **100 x MTR**

- Cross Sectional Area: 0.13 mm²
- Sheath Colour: Yellow
- American Wire Gauge: 26 AWG
- Core Strands: 7/0.16 mm
- Length: 100 m
- Insulation Material: PVC
- Voltage Rating: 300 V
- Outer Diameter: 1.3 mm



8740416 0.13 mm²

RS PRO WHITE 0.13 MM² HOOK UP WIRE, 26 AWG, 7/0.16 MM, 100M,

Pack size: **100 x MTR**

- Cross Sectional Area: 0.13 mm²
- Sheath Colour: White
- American Wire Gauge: 26 AWG
- Core Strands: 7/0.16 mm
- Length: 100 m
- Insulation Material: PVC
- Outer Diameter: 1.3 mm
- Voltage Rating: 300 V



8740419 0.13 mm²

RS PRO GREY 0.33 MM² HOOK UP WIRE, 22 AWG, 17/0.16 MM, 100M,

Pack size: **100 x MTR**

- Cross Sectional Area: 0.33 mm²
- Sheath Colour: Grey
- American Wire Gauge: 22 AWG
- Core Strands: 17/0.16 mm
- Length: 100 m
- Insulation Material: PVC
- Outer Diameter: 1.58 mm
- Voltage Rating: 300 V



8740450 0.33 mm²

RS PRO YELLOW 0.33 MM² HOOK UP WIRE, 22 AWG, 17/0.16 MM, 100M,Pack size: **100 x MTR**

- Cross Sectional Area: 0.33 mm²
- Sheath Colour: Yellow
- American Wire Gauge: 22 AWG
- Core Strands: 17/0.16 mm
- Length: 100 m
- Insulation Material: PVC
- Outer Diameter: 1.58 mm
- Voltage Rating: 300 V

**8740453** 0.33 mm²**RS PRO BLACK 0.08 MM² HOOK UP WIRE, 28 AWG, 7/0.12 MM, 100M,**Pack size: **100 x MTR**

- Cross Sectional Area: 0.08 mm²
- Sheath Colour: Black
- American Wire Gauge: 28 AWG
- Core Strands: 7/0.12 mm
- Length: 100 m
- Insulation Material: XLPVC
- Outer Diameter: 0.9 mm
- Voltage Rating: 150 V

**8775257** 0.08 mm²**RS PRO BLACK 0.33 MM² HOOK UP WIRE, 22 AWG, 7/0.25 MM, 100M,**Pack size: **100 x MTR**

- Cross Sectional Area: 0.33 mm²
- Sheath Colour: Black
- American Wire Gauge: 22 AWG
- Core Strands: 7/0.25 mm
- Length: 100 m
- Insulation Material: XLPVC
- Outer Diameter: 1.28 mm
- Voltage Rating: 150 V

**8775358** 0.33 mm²**RS PRO BLACK 0.08 MM² HOOK UP WIRE, 28 AWG, 7/0.12 MM, 100M,**Pack size: **100 x MTR**

- Cross Sectional Area: 0.08 mm²
- Sheath Colour: Black
- American Wire Gauge: 28 AWG
- Core Strands: 7/0.12 mm
- Length: 100 m
- Insulation Material: PVC
- Outer Diameter: 1.2 mm
- Voltage Rating: 300 V

**8840837** 0.08 mm²**RS PRO RED 0.08 MM² HOOK UP WIRE, 28 AWG, 7/0.12 MM, 100M,**Pack size: **100 x MTR**

- Cross Sectional Area: 0.08 mm²
- Sheath Colour: Red
- American Wire Gauge: 28 AWG
- Core Strands: 7/0.12 mm
- Length: 100 m
- Insulation Material: PVC
- Outer Diameter: 1.2 mm
- Voltage Rating: 300 V

**8840840** 0.08 mm²**RS PRO RED 0.13 MM² HOOK UP WIRE, 26 AWG, 7/0.16 MM, 100M,**Pack size: **100 x MTR**

- Cross Sectional Area: 0.13 mm²
- Sheath Colour: Red
- American Wire Gauge: 26 AWG
- Core Strands: 7/0.16 mm
- Length: 100 m
- Insulation Material: XLPVC
- Outer Diameter: 1 mm
- Voltage Rating: 150 V

**8775291** 0.13 mm²**RS PRO BLUE 0.08 MM² HOOK UP WIRE, 28 AWG, 7/0.12 MM, 100M,**Pack size: **100 x MTR**

- Cross Sectional Area: 0.08 mm²
- Sheath Colour: Blue
- American Wire Gauge: 28 AWG
- Core Strands: 7/0.12 mm
- Length: 100 m
- Insulation Material: PVC
- Outer Diameter: 1.2 mm
- Voltage Rating: 300 V

**8840843** 0.08 mm²**RS PRO BLACK 0.13 MM² HOOK UP WIRE, 26 AWG, 7/0.16 MM, 100M,**Pack size: **100 x MTR**

- Cross Sectional Area: 0.13 mm²
- Sheath Colour: Black
- American Wire Gauge: 26 AWG
- Core Strands: 7/0.16 mm
- Length: 100 m
- Insulation Material: PVC
- Outer Diameter: 1.3 mm
- Voltage Rating: 300 V

**8840869** 0.13 mm²**RS PRO RED 0.13 MM² HOOK UP WIRE, 26 AWG, 7/0.16 MM, 100M,**Pack size: **100 x MTR**

- Cross Sectional Area: 0.13 mm²
- Sheath Colour: Red
- American Wire Gauge: 26 AWG
- Core Strands: 7/0.16 mm
- Length: 100 m
- Insulation Material: PVC
- Outer Diameter: 1.3 mm
- Voltage Rating: 300 V

**8840871** 0.13 mm²**RS PRO BROWN 0.13 MM² HOOK UP WIRE, 26 AWG, 7/0.16 MM, 100M,**Pack size: **100 x MTR**

- Cross Sectional Area: 0.13 mm²
- Sheath Colour: Brown
- American Wire Gauge: 26 AWG
- Core Strands: 7/0.16 mm
- Length: 100 m
- Insulation Material: PVC
- Outer Diameter: 1.3 mm
- Voltage Rating: 300 V

**8840878** 0.13 mm²**RS PRO ORANGE 0.13 MM² HOOK UP WIRE, 26 AWG, 7/0.16 MM, 100M,**Pack size: **100 x MTR**

- Cross Sectional Area: 0.13 mm²
- Sheath Colour: Orange
- American Wire Gauge: 26 AWG
- Core Strands: 7/0.16 mm
- Length: 100 m
- Insulation Material: PVC
- Outer Diameter: 1.3 mm
- Voltage Rating: 300 V

**8840890** 0.13 mm²**RS PRO GREY 0.33 MM² HOOK UP WIRE, 22 AWG, 17/0.16 MM, 100M,**Pack size: **100 x MTR**

- Cross Sectional Area: 0.33 mm²
- Sheath Colour: Grey
- American Wire Gauge: 22 AWG
- Core Strands: 17/0.16 mm
- Length: 100 m
- Insulation Material: PVC
- Outer Diameter: 1.58 mm
- Voltage Rating: 300 V

**8840926** 0.33 mm²**RS PRO 1.27MM 10 WAY FLAT RIBBON CABLE, GREY SHEATH, 12.7 MM**Pack size: **30 x MTR**


- Ribbon Cable Type: Flat
- Pitch: 1.27 mm
- Terminated/Unterminated: Unterminated
- Number of Ways: 10
- Screened/Unscreened: Unscreened
- American Wire Gauge: 28 AWG
- Length: 30 m
- Width: 12.7 mm

**360093** Flat**RS PRO 1.27MM 20 WAY FLAT RIBBON CABLE, GREY SHEATH, 25.4 MM**Pack size: **30 x MTR**

- Ribbon Cable Type: Flat
- Pitch: 1.27 mm
- Terminated/Unterminated: Unterminated
- Number of Ways: 20
- Screened/Unscreened: Unscreened
- American Wire Gauge: 28 AWG
- Length: 30 m
- Width: 25.4 mm

**360122** Flat**RS PRO 1.27MM 24 WAY FLAT RIBBON CABLE, GREY SHEATH, 30.5 MM**Pack size: **30 x MTR**

- Ribbon Cable Type: Flat
- Pitch: 1.27 mm
- Terminated/Unterminated: Unterminated
- Number of Ways: 24
- Screened/Unscreened: Unscreened
- American Wire Gauge: 28 AWG
- Length: 30 m
- Width: 30.5 mm

**360138** Flat**RS PRO 1.27MM 16 WAY FLAT RIBBON CABLE, GREY SHEATH, 20.3 MM**Pack size: **30 x MTR**

- Ribbon Cable Type: Flat
- Pitch: 1.27 mm
- Terminated/Unterminated: Unterminated
- Number of Ways: 16
- Screened/Unscreened: Unscreened
- American Wire Gauge: 28 AWG
- Length: 30 m
- Width: 20.3 mm

**360116** Flat

RS PRO 1.27MM 25 WAY FLAT RIBBON CABLE, GREY SHEATH, 31.8 MM

Pack size: **30 x MTR**

- Ribbon Cable Type: Flat
- Pitch: 1.27 mm
- Terminated/Unterminated: Unterminated
- Number of Ways: 25
- Screened/Unscreened: Unscreened
- American Wire Gauge: 28 AWG
- Length: 30 m
- Width: 31.8 mm




360144 Flat

RS PRO 1.27MM 26 WAY FLAT RIBBON CABLE, GREY SHEATH, 33 MM WIDTH,

Pack size: **30 x MTR**

- Ribbon Cable Type: Flat
- Pitch: 1.27 mm
- Terminated/Unterminated: Unterminated
- Number of Ways: 26
- Screened/Unscreened: Unscreened
- American Wire Gauge: 28 AWG
- Length: 30 m
- Width: 33 mm



360150 Flat

RS PRO 1.27MM 34 WAY FLAT RIBBON CABLE, GREY SHEATH, 43.2 MM

Pack size: **30 x MTR**

- Ribbon Cable Type: Flat
- Pitch: 1.27 mm
- Terminated/Unterminated: Unterminated
- Number of Ways: 34
- Screened/Unscreened: Unscreened
- American Wire Gauge: 28 AWG
- Length: 30 m
- Width: 43.2 mm



360166 Flat

RS PRO 1.27MM 36 WAY FLAT RIBBON CABLE, GREY SHEATH, 45.7 MM

Pack size: **30 x MTR**

- Ribbon Cable Type: Flat
- Pitch: 1.27 mm
- Terminated/Unterminated: Unterminated
- Number of Ways: 36
- Screened/Unscreened: Unscreened
- American Wire Gauge: 28 AWG
- Length: 30 m
- Width: 45.7 mm



360172 Flat

RS PRO 1.27MM 37 WAY FLAT RIBBON CABLE, GREY SHEATH, 47 MM WIDTH,

Pack size: **30 x MTR**

- Ribbon Cable Type: Flat
- Pitch: 1.27 mm
- Terminated/Unterminated: Unterminated
- Number of Ways: 37
- Screened/Unscreened: Unscreened
- American Wire Gauge: 28 AWG
- Length: 30 m
- Width: 47 mm



360188 Flat

RS PRO 1.27MM 40 WAY FLAT RIBBON CABLE, GREY SHEATH, 50.8 MM

Pack size: **30 x MTR**

- Ribbon Cable Type: Flat
- Pitch: 1.27 mm
- Terminated/Unterminated: Unterminated
- Number of Ways: 40
- Screened/Unscreened: Unscreened
- American Wire Gauge: 28 AWG
- Length: 30 m
- Width: 50.8 mm



360194 Flat

RS PRO 1.27MM 50 WAY FLAT RIBBON CABLE, GREY SHEATH, 63.5 MM

Pack size: **30 x MTR**

- Ribbon Cable Type: Flat
- Pitch: 1.27 mm
- Terminated/Unterminated: Unterminated
- Number of Ways: 50
- Screened/Unscreened: Unscreened
- American Wire Gauge: 28 AWG
- Length: 30 m
- Width: 63.5 mm



360201 Flat

RS PRO 1.27MM 64 WAY FLAT RIBBON CABLE, GREY SHEATH, 81.3 MM

Pack size: **30 x MTR**

- Ribbon Cable Type: Flat
- Pitch: 1.27 mm
- Terminated/Unterminated: Unterminated
- Number of Ways: 64
- Screened/Unscreened: Unscreened
- American Wire Gauge: 28 AWG
- Length: 30 m
- Width: 81.3 mm




360217 Flat

RS PRO 1.27MM 15 WAY FLAT RIBBON CABLE, GREY SHEATH, 19.1 MM

Pack size: **30 x MTR**

- Ribbon Cable Type: Flat
- Pitch: 1.27 mm
- Terminated/Unterminated: Unterminated
- Number of Ways: 15
- Screened/Unscreened: Unscreened
- American Wire Gauge: 28 AWG
- Length: 30 m
- Width: 19.1 mm



360223 Flat

RS PRO 1.27MM 10 WAY FLAT RIBBON CABLE, MULTICOLOURED SHEATH,

Pack size: **25 x MTR**

- Ribbon Cable Type: Flat
- Pitch: 1.27 mm
- Terminated/Unterminated: Unterminated
- Number of Ways: 10
- Screened/Unscreened: Unscreened
- American Wire Gauge: 26 AWG
- Length: 25 m
- Width: 12.7 mm



2140677 Flat

RS PRO 1.27MM 20 WAY FLAT RIBBON CABLE, MULTICOLOURED SHEATH,

Pack size: **10 x MTR**

- Ribbon Cable Type: Flat
- Pitch: 1.27 mm
- Terminated/Unterminated: Unterminated
- Number of Ways: 20
- Screened/Unscreened: Unscreened
- American Wire Gauge: 26 AWG
- Length: 10 m
- Width: 25.4 mm



2140683 Flat

RS PRO 1.27MM 20 WAY FLAT RIBBON CABLE, MULTICOLOURED SHEATH,

Pack size: **25 x MTR**

- Ribbon Cable Type: Flat
- Pitch: 1.27 mm
- Terminated/Unterminated: Unterminated
- Number of Ways: 20
- Screened/Unscreened: Unscreened
- American Wire Gauge: 26 AWG
- Length: 25 m
- Width: 25.4 mm



2140699 Flat

RS PRO 1.27MM 10 WAY FLAT RIBBON CABLE, GREY SHEATH, 12.7 MM

Pack size: **5 x MTR**

- Ribbon Cable Type: Flat
- Pitch: 1.27 mm
- Terminated/Unterminated: Unterminated
- Number of Ways: 10
- Screened/Unscreened: Unscreened
- American Wire Gauge: 28 AWG
- Length: 5 m
- Width: 12.7 mm



2899846 Flat

RS PRO 1.27MM 14 WAY FLAT RIBBON CABLE, GREY SHEATH, 17.8 MM

Pack size: **5 x MTR**

- Ribbon Cable Type: Flat
- Pitch: 1.27 mm
- Terminated/Unterminated: Unterminated
- Number of Ways: 14
- Screened/Unscreened: Unscreened
- American Wire Gauge: 28 AWG
- Length: 5 m
- Width: 17.8 mm



2899852 Flat

RS PRO 1.27MM 16 WAY FLAT RIBBON CABLE, GREY SHEATH, 20.3 MM

Pack size: **5 x MTR**

- Ribbon Cable Type: Flat
- Pitch: 1.27 mm
- Terminated/Unterminated: Unterminated
- Number of Ways: 16
- Screened/Unscreened: Unscreened
- American Wire Gauge: 28 AWG
- Length: 5 m
- Width: 20.3 mm



2899874 Flat

RS PRO 1.27MM 20 WAY FLAT RIBBON CABLE, GREY SHEATH, 25.4 MM

Pack size: **5 x MTR**

- Ribbon Cable Type: Flat
- Pitch: 1.27 mm
- Terminated/Unterminated: Unterminated
- Number of Ways: 20
- Screened/Unscreened: Unscreened
- American Wire Gauge: 28 AWG
- Length: 5 m
- Width: 25.4 mm



2899896 Flat

RS PRO 1.27MM 26 WAY FLAT RIBBON CABLE, GREY SHEATH, 33 MM WIDTH,Pack size: **5 x MTR**

- Ribbon Cable Type: Flat
- Pitch: 1.27 mm
- Terminated/Unterminated: Unterminated
- Number of Ways: 26
- Screened/Unscreened: Unscreened
- American Wire Gauge: 28 AWG
- Length: 5 m
- Width: 33 mm

**2899925** Flat**RS PRO 1.27MM 25 WAY FLAT RIBBON CABLE, GREY SHEATH, 31.8 MM**Pack size: **5 x MTR**

- Ribbon Cable Type: Flat
- Pitch: 1.27 mm
- Terminated/Unterminated: Unterminated
- Number of Ways: 25
- Screened/Unscreened: Unscreened
- American Wire Gauge: 28 AWG
- Length: 5 m
- Width: 31.8 mm

**2899919** Flat**RS PRO 1.27MM 34 WAY FLAT RIBBON CABLE, GREY SHEATH, 43.2 MM**Pack size: **5 x MTR**

- Ribbon Cable Type: Flat
- Pitch: 1.27 mm
- Terminated/Unterminated: Unterminated
- Number of Ways: 34
- Screened/Unscreened: Unscreened
- American Wire Gauge: 28 AWG
- Length: 5 m
- Width: 43.2 mm

**2899931** Flat**RS PRO 1.27MM 37 WAY FLAT RIBBON CABLE, GREY SHEATH, 47 MM WIDTH,**Pack size: **5 x MTR**

- Ribbon Cable Type: Flat
- Pitch: 1.27 mm
- Terminated/Unterminated: Unterminated
- Number of Ways: 37
- Screened/Unscreened: Unscreened
- American Wire Gauge: 28 AWG
- Length: 5 m
- Width: 47 mm

**2899969** Flat**RS PRO 1.27MM 40 WAY FLAT RIBBON CABLE, GREY SHEATH, 50.8 MM**Pack size: **5 x MTR**

- Ribbon Cable Type: Flat
- Pitch: 1.27 mm
- Terminated/Unterminated: Unterminated
- Number of Ways: 40
- Screened/Unscreened: Unscreened
- American Wire Gauge: 28 AWG
- Length: 5 m
- Width: 50.8 mm

**2899975** Flat**RS PRO 1.27MM 50 WAY FLAT RIBBON CABLE, GREY SHEATH, 63.5 MM**Pack size: **5 x MTR**

- Ribbon Cable Type: Flat
- Pitch: 1.27 mm
- Terminated/Unterminated: Unterminated
- Number of Ways: 50
- Screened/Unscreened: Unscreened
- American Wire Gauge: 28 AWG
- Length: 5 m
- Width: 63.5 mm

**2899981** Flat**RS PRO 1.27MM 64 WAY FLAT RIBBON CABLE, GREY SHEATH, 81.3 MM**Pack size: **5 x MTR**

- Ribbon Cable Type: Flat
- Pitch: 1.27 mm
- Terminated/Unterminated: Unterminated
- Number of Ways: 64
- Screened/Unscreened: Unscreened
- American Wire Gauge: 28 AWG
- Length: 5 m
- Width: 81.3 mm

**2899997** Flat**RS PRO 4 CORE 28 AWG TELEPHONE CABLE, 7/0.127 MM, BLACK SHEATH,**Pack size: **100 x MTR**

- Fire Behaviour: Flame Retardant
- Number of Cores: 4
- Shield Type: Unshielded
- Outer Sheath Material: PVC
- Core Strands: 7/0.127 mm
- Cross Sectional Area: 0.09 mm²
- American Wire Gauge: 28 AWG
- Conductor Material: Bare Copper

**5185689** Flame Retardant**RS PRO 6 CORE 30 AWG TELEPHONE CABLE, BLACK SHEATH, 50M**Pack size: **50 x MTR**

- Fire Behaviour: Flame Retardant
- Number of Cores: 6
- Shield Type: Unshielded
- Outer Sheath Material: PVC
- Cross Sectional Area: 0.066 mm²
- American Wire Gauge: 30 AWG
- Conductor Material: Copper
- Terminated/Unterminated: Unterminated

**5185746** Flame Retardant**RS PRO MULTICORE DATA CABLE, 2 PAIRS, 0.22 MM², 4 CORES, 24 AWG,**Pack size: **100 x MTR**

- Number of Pairs: 2
- Cross Sectional Area: 0.22 mm²
- Number of Cores: 4
- American Wire Gauge: 24 AWG
- Screened/Unscreened: Screened
- Length: 100 m
- Shield Type: Unshielded
- Sheath Colour: Grey

**8124680** 2**RS PRO MULTICORE DATA CABLE, 1 PAIRS, 0.76 MM², 2 CORES, 22 AWG,**Pack size: **100 x MTR**

- Number of Pairs: 1
- Cross Sectional Area: 0.76 mm²
- Number of Cores: 2
- American Wire Gauge: 22 AWG
- Screened/Unscreened: Screened
- Length: 100 m
- Shield Type: Aluminium Foil-PET Tape
- Sheath Colour: Grey

**8124684** 1**RS PRO MULTICORE DATA CABLE, 5 PAIRS, 0.2 MM², 10 CORES, 24 AWG,**Pack size: **100 x MTR**

- Number of Pairs: 5
- Cross Sectional Area: 0.2 mm²
- Number of Cores: 10
- American Wire Gauge: 24 AWG
- Screened/Unscreened: Screened
- Length: 100 m
- Shield Type: Tinned Copper
- Sheath Colour: Grey

**8124687** 5**RS PRO TWISTED PAIR DATA CABLE, 2 PAIRS, 0.34 MM², 4 CORES, 22 AWG,**Pack size: **100 x MTR**

- Number of Pairs: 2
- Cross Sectional Area: 0.34 mm²
- Number of Cores: 4
- American Wire Gauge: 22 AWG
- Screened/Unscreened: Screened
- Length: 100 m
- Shield Type: Aluminium Foil-PET Tape
- Sheath Colour: Grey

**8124690** 2**RS PRO TWISTED PAIR DATA CABLE, 3 PAIRS, 0.76 MM², 6 CORES, 22 AWG,**Pack size: **50 x MTR**


- Number of Pairs: 3
- Cross Sectional Area: 0.76 mm²
- Number of Cores: 6
- American Wire Gauge: 22 AWG
- Screened/Unscreened: Screened
- Length: 50 m
- Shield Type: Aluminium Foil-PET Tape
- Sheath Colour: Grey

**8124696** 3**RS PRO MULTICORE DATA CABLE, 9 PAIRS, 0.22 MM², 18 CORES, 24 AWG,**Pack size: **100 x MTR**

- Number of Pairs: 9
- Cross Sectional Area: 0.22 mm²
- Number of Cores: 18
- American Wire Gauge: 24 AWG
- Screened/Unscreened: Screened
- Length: 100 m
- Shield Type: Tinned Copper
- Sheath Colour: Grey

**8124713** 9**RS PRO TWISTED PAIR DATA CABLE, 10 PAIRS, 0.25 MM², 20 CORES, 24**Pack size: **100 x MTR**


- Number of Pairs: 10
- Cross Sectional Area: 0.25 mm²
- Number of Cores: 20
- American Wire Gauge: 24 AWG
- Screened/Unscreened: Screened
- Shield Type: Tinned Copper
- Sheath Colour: Grey
- Outer Diameter: 9.1 mm

**8124716** 10

RS PRO MULTICORE DATA CABLE, 2 PAIRS, 0.64 MM², 4 CORES, 22 AWG,

Pack size: **500 x MTR**

- Number of Pairs: 2
- Cross Sectional Area: 0.64 mm²
- Number of Cores: 4
- American Wire Gauge: 22 AWG
- Screened/Unscreened: Screened
- Length: 500 m
- Shield Type: Aluminium Foil-PET Tape
- Sheath Colour: Grey



8124735 2

RS PRO MULTICORE DATA CABLE, 2 PAIRS, 0.2 MM², 4 CORES, 24 AWG,

Pack size: **100 x MTR**

- Number of Pairs: 2
- Cross Sectional Area: 0.2 mm²
- Number of Cores: 4
- American Wire Gauge: 24 AWG
- Screened/Unscreened: Screened
- Length: 100 m
- Shield Type: Tinned Copper
- Sheath Colour: Grey



8124738 2

RS PRO MULTICORE DATA CABLE, 1 PAIRS, 0.64 MM², 2 CORES, 22 AWG,

Pack size: **100 x MTR**

- Number of Pairs: 1
- Cross Sectional Area: 0.64 mm²
- Number of Cores: 2
- American Wire Gauge: 22 AWG
- Screened/Unscreened: Unscreened
- Length: 100 m
- Shield Type: Unshielded
- Sheath Colour: Grey



8124741 1

RS PRO MULTICORE DATA CABLE, 2 PAIRS, 0.76 MM², 4 CORES, 22 AWG,

Pack size: **100 x MTR**

- Number of Pairs: 2
- Cross Sectional Area: 0.76 mm²
- Number of Cores: 4
- American Wire Gauge: 22 AWG
- Screened/Unscreened: Screened
- Length: 100 m
- Shield Type: Aluminium Foil-PET Tape
- Sheath Colour: Grey




8124747 2

RS PRO TWISTED PAIR DATA CABLE, 4 PAIRS, 0.25 MM², 8 CORES, 24 AWG,

Pack size: **100 x MTR**

- Number of Pairs: 4
- Cross Sectional Area: 0.25 mm²
- Number of Cores: 8
- American Wire Gauge: 24 AWG
- Screened/Unscreened: Screened
- Shield Type: Tinned Copper
- Sheath Colour: Grey
- Outer Diameter: 7.1 mm



8124750 4

RS PRO MULTICORE DATA CABLE, 2 PAIRS, 0.76 MM², 4 CORES, 24 AWG,

Pack size: **100 x MTR**

- Number of Pairs: 2
- Cross Sectional Area: 0.76 mm²
- Number of Cores: 4
- American Wire Gauge: 24 AWG
- Screened/Unscreened: Screened
- Length: 100 m
- Shield Type: Aluminium Foil-PET Tape
- Sheath Colour: Grey



8124753 2

RS PRO MULTICORE DATA CABLE, 2 PAIRS, 0.22 MM², 4 CORES, 24 AWG,

Pack size: **100 x MTR**

- Number of Pairs: 2
- Cross Sectional Area: 0.22 mm²
- Number of Cores: 4
- American Wire Gauge: 24 AWG
- Screened/Unscreened: Screened
- Length: 100 m
- Shield Type: Tinned Copper
- Sheath Colour: Grey




8124757 2

RS PRO MULTICORE DATA CABLE, 3 PAIRS, 0.76 MM², 6 CORES, 22 AWG,

Pack size: **100 x MTR**

- Number of Pairs: 3
- Cross Sectional Area: 0.76 mm²
- Number of Cores: 6
- American Wire Gauge: 22 AWG
- Screened/Unscreened: Screened
- Length: 100 m
- Shield Type: Aluminium Foil-PET Tape
- Sheath Colour: Grey



8124766 3

RS PRO TWISTED PAIR DATA CABLE, 6 PAIRS, 0.25 MM², 12 CORES, 24 AWG,

Pack size: **100 x MTR**

- Number of Pairs: 6
- Cross Sectional Area: 0.25 mm²
- Number of Cores: 12
- American Wire Gauge: 24 AWG
- Screened/Unscreened: Screened
- Shield Type: Tinned Copper
- Sheath Colour: Grey
- Outer Diameter: 7.5 mm



8124769 6

RS PRO MULTICORE DATA CABLE, 1 PAIRS, 0.35 MM², 2 CORES, 22 AWG,

Pack size: **100 x MTR**

- Number of Pairs: 1
- Cross Sectional Area: 0.35 mm²
- Number of Cores: 2
- American Wire Gauge: 22 AWG
- Screened/Unscreened: Screened
- Length: 100 m
- Shield Type: Aluminium Foil-PET Tape
- Sheath Colour: Grey



8606704 1

**CONNECTOR,TEST,TERMINAL
POST,4MM BUNG**Pack size: **10 x EA**

- Colour: Red/Black
- Length: 4 mm
- Type: Banana Plug

**2615064** Red/Black**SPRING TERMINAL M4S SPT2
BLACK/RED**Pack size: **1 x PR**

- Colour: Black, Red
- Current Rating: 15 A
- Voltage Rating: 48 V
- Hole Diameter: 7.2 mm

**1873803** Black, Red**TERMINAL TP6S BLACK/RED GOLD
ASSEM**Pack size: **1 x PR**

- Colour: Black, Red
- Contact Plating: Gold
- Current Rating: 30 A
- Hole Diameter: 7.2 mm

**1873804** Black, Red**NI PLATE BRASS TERMINAL BINDING
POST,30A**Pack size: **5 x EA**

- Colour: Silver
- Contact Material: Brass
- Contact Plating: Nickel
- Current Rating: 30 A
- Height Above Panel: 22 mm
- Maximum Panel Thickness: 12.5 mm
- Hole Diameter: 5 mm

**6684590** Silver**RS PRO ILCM03A CLAMP METER, MAX
CURRENT 60A AC**Pack size: **1 x EA**

- Absolute Maximum AC Current Measurement: 60 A ac
- Absolute Maximum AC Voltage Measurement: 400 V ac
- Absolute Maximum Resistance Measurement: 400 Ω
- Model Number: ILCM03A
- AC Current Measurement Resolution: 10 μA
- Clamp Meter Type: Leakage Clamp Meter
- Best AC Current Accuracy: ±(1% rdg + 3dgt)
- Best AC Voltage Accuracy: ±(1.5% rdg + 2dgt)

**1232204** 60 A ac**RS PRO ICA39T CURRENT CLAMP
ADAPTOR**Pack size: **1 x EA**

- Battery Life: 66 h
- Battery Type: 9V Alkaline
- Maximum Conductor Size: 51 mm
- Safety Category: CAT III 1000 V
- Minimum Operating Temperature: 0 °C
- Safety Category Level: CAT III
- Safety Category Voltage: 1000 V
- Maximum Operating Temperature: +50 °C

**1233224** 66 h**RS PRO RS330 CLAMP METER, MAX
CURRENT 400A AC**Pack size: **1 x EA**

- Absolute Maximum AC Current Measurement: 400 A ac
- Absolute Maximum AC Voltage Measurement: 600 V ac
- Absolute Maximum DC Voltage Measurement: 600 V dc
- Absolute Maximum Resistance Measurement: 20 MΩ
- Model Number: RS330
- AC Current Measurement Resolution: 1 mA
- Clamp Meter Type: AC Auto-Ranging Clamp Meter
- Best AC Current Accuracy: ±(2% rdg + 4dgt)

**1231936** 400 A ac**RS PRO ICM136R CLAMP METER,
600A DC, MAX CURRENT 600A AC**Pack size: **1 x EA**

- Absolute Maximum AC Current Measurement: 600 A ac
- Absolute Maximum DC Current Measurement: 600 A dc
- Absolute Maximum AC Voltage Measurement: 600 V ac
- Absolute Maximum DC Voltage Measurement: 600 V dc
- Absolute Maximum Resistance Measurement: 400 Ω
- Model Number: ICM136R
- AC Current Measurement Resolution: 100 mA
- DC Current Measurement Resolution: 100 mA

**1233222** 600 A ac**RS PRO ICM20 CLAMP METER, MAX
CURRENT 400A AC CAT III 600 V**Pack size: **1 x EA**

- Absolute Maximum AC Current Measurement: 400 A ac
- Model Number: ICM20
- AC Current Measurement Resolution: 100 mA
- Clamp Meter Type: AC Current Clamp Meter
- Best AC Current Accuracy: ±(2% rdg + 0.5A)
- Functions Measured: AC Current, Continuity, Diode Test
- Maximum Conductor Size: 27 (Dia.) mm
- Maximum Operating Temperature: +50 °C

**1233230** 400 A ac**RS PRO ICM139R CLAMP METER, 1KA
DC, MAX CURRENT 1KA AC CAT III**Pack size: **1 x EA**

- Absolute Maximum AC Current Measurement: 1 kA ac
- Absolute Maximum DC Current Measurement: 1 kA dc
- Absolute Maximum AC Voltage Measurement: 750 V ac
- Absolute Maximum DC Voltage Measurement: 1000 V dc
- Absolute Maximum Resistance Measurement: 400 Ω
- Model Number: ICM139R
- AC Current Measurement Resolution: 100 mA
- DC Current Measurement Resolution: 100 mA

**1233227** 1 kA ac**RS PRO ICM30R CLAMP METER, 300A
DC, MAX CURRENT 300A AC CAT III**Pack size: **1 x EA**

- Absolute Maximum AC Current Measurement: 300 A ac
- Absolute Maximum DC Current Measurement: 300 A dc
- Absolute Maximum AC Voltage Measurement: 600 V ac
- Absolute Maximum DC Voltage Measurement: 600 V dc
- Absolute Maximum Resistance Measurement: 40 MΩ
- Model Number: ICM30R
- AC Current Measurement Resolution: 10 mA
- DC Current Measurement Resolution: 10 mA

**1233252** 300 A ac**RS PRO ICMA6 CLAMP METER, MAX
CURRENT 600A AC CAT II 1000 V, CAT**Pack size: **1 x EA**

- Absolute Maximum AC Current Measurement: 600 A ac
- Absolute Maximum AC Voltage Measurement: 750 V ac
- Absolute Maximum DC Voltage Measurement: 1000 V dc
- Absolute Maximum Resistance Measurement: 2 kΩ
- Model Number: ICMA6
- AC Current Measurement Resolution: 100 mA
- Clamp Meter Type: AC Current Clamp Meter
- Best AC Current Accuracy: ±(1.9% rdg + 5dgt)

**1233234** 600 A ac**RS PRO ICMA1 CLAMP METER, 300A
DC, MAX CURRENT 300A AC CAT III**Pack size: **1 x EA**

- Absolute Maximum AC Current Measurement: 300 A ac
- Absolute Maximum DC Current Measurement: 300 A dc
- Model Number: ICMA1
- AC Current Measurement Resolution: 10 mA
- DC Current Measurement Resolution: 10 mA
- Best DC Current Accuracy: ±(1.5% rdg + 5dgt)
- Clamp Meter Type: AC/DC Clamp Meter
- Best AC Current Accuracy: ±(1.5% rdg + 5dgt)

**1233256** 300 A ac**RS PRO CURRENT CLAMP, AC
ADAPTER, 400A AC MAX, TEST LEAD,**Pack size: **1 x EA**

- Adapter Type: AC
- Maximum AC Current: 400 A ac
- Best Accuracy: ±1.9% + 0.5 A
- Resolution: 1 mV/A
- Maximum Conductor Size: 29 mm
- Safety Category: CAT II 600 V
- Output Type: Current, Voltage
- Connector Type: Test Lead

**1233223** AC**RS PRO CURRENT CLAMP, AC
ADAPTER, 300A AC MAX, CURRENT,**Pack size: **1 x EA**

- Adapter Type: AC
- Maximum AC Current: 300 A ac
- Best Accuracy: ±1.9% + 5 Digits
- Resolution: 0.1 A
- Maximum Conductor Size: 29 mm
- Safety Category: CAT III 1000 V, CAT IV 600 V
- Output Type: Current, Voltage
- Maximum Operating Temperature: +50 °C

**1238451** AC**RS PRO CURRENT PROBE, AC,
ROGOWSKI COIL ADAPTER, 3KA AC**Pack size: **1 x EA**

- Adapter Type: AC, Rogowski Coil
- Maximum AC Current: 3 kA ac
- Best Accuracy: ±3 %
- Safety Category: CAT III 1000 V, CAT IV 600 V
- Battery Type: AAA
- Safety Category Level: CAT III, CAT IV
- Safety Category Voltage: 600 V, 1000 V

**1611631** AC, Rogowski

RS PRO CROCODILE CLIP

Pack size: **1 x EA**

- Accessory Type: Crocodile Clip



218100 Crocodile Clip

CONNECTOR,TEST,CLIP,SET,INSULATED,FLUKE 80,MULTIMETER

Pack size: **1 x PR**

- Accessory Type: Crocodile Clip Set



2647881 Crocodile Clip

ET5300 EARTH RESISTANCE TESTER- 4 WIRE

Pack size: **1 x EA**

- Absolute Maximum Resistance Measurement: 2 kΩ
- Best Accuracy: ±2 %
- Display Type: LED
- Battery Type: AA
- Power Source: Battery
- Weight: 700 g
- Height: 50 mm
- Includes: Battery x 6, Carrying Case, Iron Rods x 4, Manual, Sets Test Kits x 4



1445339 2 kΩ

RS PRO BLACK 1 MM² TEST LEAD WIRE, 1200MM, SILICONE

Pack size: **5 x EA**

- Cross Sectional Area: 1 mm²
- Sheath Colour: Black
- Length: 1200 mm
- Insulation Material: Silicone
- Voltage Rating: 1000 V
- Outer Diameter: 3.55 mm
- Current Rating: 20 A
- Conductor Material: Copper



2070881 1 mm²

RS PRO CROCODILE CLIP

Pack size: **1 x SET**

- Accessory Type: Crocodile Clip Set



816170 Crocodile Clip

RS PRO CROCODILE CLIP

Pack size: **1 x PR**

- Accessory Type: Crocodile Clip
- For Use With: Multimeter



3402566 Crocodile Clip

CONNECTOR,TEST,TERMINAL POST,MOUNT, MOUNT PLATE

Pack size: **5 x EA**

- Length: 35 mm
- Enclosure Mounting Type: Mounting Plate
- Colour: Black



404856 35 mm

RS PRO RED 1 MM² TEST LEAD WIRE, 1200MM, SILICONE INSULATION

Pack size: **5 x EA**

- Cross Sectional Area: 1 mm²
- Sheath Colour: Red
- Length: 1200 mm
- Insulation Material: Silicone
- Voltage Rating: 1000 V
- Outer Diameter: 3.55 mm
- Current Rating: 20 A
- Conductor Material: Copper



2070882 1 mm²

RS PRO CROCODILE CLIP

Pack size: **1 x SET**

- Accessory Type: Crocodile Clip



1253738 Crocodile Clip

RS PRO CROCODILE CLIP

Pack size: **1 x SET**

- Accessory Type: Crocodile Clip
- For Use With: Multimeter



4935556 Crocodile Clip

RS PRO FIBRE OPTIC CLEANING PEN FOR FIBRE OPTIC CONNECTORS, 40

Pack size: **1 x EA**

- Cleaner Type: Pen
- Application: Fibre Optic Connectors
- Package Type: Pen
- Package Size: 40 g
- Size: 18 x 18 x 22 mm



2048308 Pen

RS PRO RS5500 INSULATION TESTER, 250V MIN, 1000V MAX, 2GΩ MAX, CAT

Pack size: **1 x EA**

- Tester Type: Insulation Tester
- Minimum Test Voltage: 250 V
- Maximum Test Voltage: 1000 V
- Maximum Insulation Resistance Measurement: 2 GΩ
- Display Type: LCD
- Test Current: ≤200 mA
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: +40 °C



1231931 Insulation Tester

CROCODILE CLIP FOR MULTIMETER TEST LEADS

Pack size: **1 x EA**

- Accessory Type: Crocodile Clip



1253740 Crocodile Clip

RS PRO IET1700 EARTH TESTER 4KΩ

Pack size: **1 x EA**

- Absolute Maximum Resistance Measurement: 4 kΩ
- Best Accuracy: ±2% + 3 Digits
- Display Type: LCD
- Battery Type: AA
- Power Source: Battery
- Weight: 800 g
- Height: 77 mm
- Includes: 1 Set Test Lead, 4 x Auxiliary Earth Spikes, 8 x Battery, Carrying Case, Manual, Neck Strap



1232238 4 kΩ

RS PRO FIBRE OPTIC CLEANING PEN FOR FIBRE OPTIC CONNECTORS, 40

Pack size: **1 x EA**

- Cleaner Type: Pen
- Application: Fibre Optic Connectors
- Package Type: Pen
- Package Size: 40 g
- Size: 18 x 18 x 22 mm



2048309 Pen

GHT114 TEST LEAD CLIP HIGH VOLTAGE PROBE

Pack size: **1 x EA**

- Accessory Type: Test Lead Clip High Voltage Probe



9176314 Test Lead Clip

RS PRO IDM103N HANDHELD DIGITAL MULTIMETER, 10A AC MAX, 10A DCPack size: **1 x EA**

- Multimeter Type: Handheld
- True RMS: No
- Functions Measured: AC Current, AC Voltage, DC Current, DC Voltage, Frequency, Resistance
- Absolute Maximum AC Voltage Measurement: 1000 V ac
- Absolute Maximum DC Voltage Measurement: 1000 V dc
- Absolute Maximum DC Current Measurement: 10 A dc
- Absolute Maximum Resistance Measurement: 40 MΩ

**1233235** Handheld**RS PRO IDM72 HANDHELD DIGITAL MULTIMETER, TRUE RMS, 10A AC MAX,**Pack size: **1 x EA**

- Multimeter Type: Handheld
- True RMS: Yes
- Functions Measured: AC Current, AC Voltage, Capacitance, Continuity, DC Current, DC Voltage, Diode, Frequency, Resistance
- Absolute Maximum Resistance Measurement: 60 MΩ
- Absolute Maximum DC Voltage Measurement: 1000 V dc
- Absolute Maximum AC Voltage Measurement: 750 V ac
- Absolute Maximum DC Current Measurement: 10 A dc
- Absolute Maximum AC Current Measurement: 10 A ac

**1233242** Handheld**RS PRO IDM93N HANDHELD DIGITAL MULTIMETER, 10A AC MAX, 10A DC**Pack size: **1 x EA**

- Multimeter Type: Handheld
- True RMS: No
- Functions Measured: AC Current, AC Voltage, Capacitance, Conductance, DC Current, DC Voltage, Diode, Frequency, Resistance, RMS, Temperature
- Absolute Maximum DC Current Measurement: 10 A dc
- Absolute Maximum DC Voltage Measurement: 600 V dc
- Absolute Maximum Resistance Measurement: 20 MΩ
- Absolute Maximum AC Current Measurement: 10 A ac
- Absolute Maximum AC Voltage Measurement: 600 V ac

**1233245** Handheld**RS PRO IDM5A HANDHELD DIGITAL MULTIMETER, 4mA AC MAX, 4mA DC**Pack size: **1 x EA**

- Multimeter Type: Handheld
- True RMS: No
- Functions Measured: AC Current, AC Voltage, Capacitance, Conductance, DC Current, DC Voltage, Diode, Frequency, Resistance, RMS, Temperature
- Absolute Maximum DC Voltage Measurement: 600 V dc
- Absolute Maximum DC Current Measurement: 4 mA dc
- Absolute Maximum AC Voltage Measurement: 600 V ac
- Absolute Maximum AC Current Measurement: 4 mA ac
- Absolute Maximum Resistance Measurement: 40 MΩ

**1233251** Handheld**RS PRO FUSED, CROCODILE CLIP, 1M, CAT III**Pack size: **1 x EA**

- Lead Type: Test Lead
- Connector Type: Crocodile Clip
- Fused: Yes
- Lead Length: 1 m
- Safety Category Voltage: 600 V
- Safety Category: CAT III 600 V
- Safety Category Level: CAT III

**212988** Test Lead**RS PRO FUSED FUSED PROBE KIT, RIGHT ANGLE PLUG, 1.2M, CAT III**Pack size: **1 x EA**

- Lead Type: Fused Probe Kit
- Connector Type: Right Angle Plug
- Fused: Yes
- Lead Length: 1.2 m
- Safety Category Voltage: 600, 1000 V
- Safety Category: CAT III 1000 V, CAT III 600 V
- Minimum Operating Temperature: -10 °C
- Maximum Operating Temperature: +150 °C

**204583** Fused Probe Kit**RS PRO FUSED FUSED PROBE KIT, STRAIGHT PLUG, 1.2M, CAT III**Pack size: **1 x EA**

- Lead Type: Fused Probe Kit
- Connector Type: Straight Plug
- Fused: Yes
- Lead Length: 1.2 m
- Safety Category Voltage: 600, 1000 V
- Safety Category: CAT III 1000 V, CAT III 600 V
- Minimum Operating Temperature: -10 °C
- Maximum Operating Temperature: +150 °C

**204599** Fused Probe Kit**RS PRO FUSED, CROCODILE CLIP, CAT II, CAT III**Pack size: **1 x EA**

- Lead Type: Test Lead
- Connector Type: Crocodile Clip
- Fused: Yes
- Safety Category Voltage: 600/1000 V
- Safety Category: CAT II 1000 V, CAT III 600 V
- Safety Category Level: CAT II, CAT III

**816029** Test Lead**RS PRO AUTOMOTIVE TEST LEAD KIT, CROCODILE CLIP, 1.2M, 155MM, 10A**Pack size: **1 x KT**

- Lead Type: Automotive Test Lead Kit
- Connector Type: Crocodile Clip
- Lead Length: 1.2m, 155mm, 25mm, 44 mm
- Current Rating: 10 A
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +70 °C

**1247400** Automotive Test**RS PRO TEST LEAD KIT, 10A**Pack size: **1 x PR**

- Lead Type: Test Lead Kit
- Product Type: Automotive Back Probe with Cable Piercer Adapter
- Current Rating: 10 A
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +70 °C

**1247405** Test Lead Kit**RS PRO TEST LEAD KIT, CAT II, 20A**Pack size: **1 x PR**

- Lead Type: Test Lead Kit
- Product Type: Automotive Long Reach Sharp Prod
- Current Rating: 20 A
- Safety Category: CAT II 1000 V
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +70 °C
- Safety Category Level: CAT II

**1247406** Test Lead Kit**RS PRO FUSED, CROCODILE CLIP**Pack size: **1 x EA**

- Lead Type: Test Lead
- Connector Type: Crocodile Clip
- Fused: Yes

**1253730** Test Lead**RS PRO FUSED TEST LEAD KIT, RIGHT ANGLE PLUG, 1.25M, CAT III**Pack size: **1 x EA**

- Lead Type: Test Lead Kit
- Connector Type: Right Angle Plug
- Fused: Yes
- Lead Length: 1.25 m
- Safety Category Voltage: 1000 V
- Safety Category: CAT III 1000 V
- Safety Category Level: CAT III

**1253731** Test Lead Kit**RS PRO TEST LEAD KIT, CROCODILE CLIP, RIGHT ANGLE PLUG, 1.2M, CAT**Pack size: **1 x EA**

- Lead Type: Test Lead Kit
- Connector Type: Crocodile Clip, Right Angle Plug
- Lead Length: 1.2 m
- Current Rating: 15 A
- Safety Category Voltage: 1000 V
- Safety Category: CAT III 1000 V
- Safety Category Level: CAT III

**1253733** Test Lead Kit**RS PRO TEST LEAD KIT, CROCODILE CLIP, RIGHT ANGLE PLUG, SPRING**Pack size: **1 x EA**

- Lead Type: Test Lead Kit
- Connector Type: Crocodile Clip, Right Angle Plug, Spring Hook, Straight Plug
- Lead Length: 1.2 m
- Current Rating: 15 A
- Safety Category Voltage: 1000 V
- Safety Category: CAT III 1000 V
- Safety Category Level: CAT III

**1253735** Test Lead Kit**RS PRO, 1.2M, CAT III, CAT IV, 20A**Pack size: **1 x EA**

- Lead Type: Test Lead
- Lead Length: 1.2 m
- Current Rating: 20 A
- Safety Category Voltage: 600 V, 1000 V
- Safety Category: CAT III, CAT IV, 600 V, 1000 V
- Safety Category Level: CAT III, CAT IV

**1253736** Test Lead

RS PRO FUSED FUSED PROBE KIT, RIGHT ANGLE TO STRAIGHT

Pack size: **1 x EA**

- Lead Type: Fused Probe Kit
- Connector Type: Right Angle to Straight
- Fused: Yes
- Safety Category Voltage: 1000 V
- Safety Category: CAT III 1000 V



1999851 Fused Probe Kit

RS PRO TEST LEAD KIT, CROCODILE CLIP, RIGHT ANGLE PLUG, 1.2M, CAT

Pack size: **1 x EA**

- Lead Type: Test Lead Kit
- Connector Type: Crocodile Clip, Right Angle Plug
- Lead Length: 1.2 m
- Current Rating: 10 A
- Safety Category Voltage: 1000 V
- Safety Category: CAT III 1000 V
- Safety Category Level: CAT III



2432998 Test Lead Kit

RS PRO TEST LEAD KIT, CROCODILE CLIP, SOCKET, 1.2M, 10A

Pack size: **1 x KT**

- Lead Type: Test Lead Kit
- Connector Type: Crocodile Clip, Socket
- Lead Length: 1.2 m
- Current Rating: 10 A



6120835 Test Lead Kit

RS PRO FUSED TEST LEAD KIT, CROCODILE CLIP, RIGHT ANGLE

Pack size: **1 x EA**

- Lead Type: Test Lead Kit
- Connector Type: Crocodile Clip, Right Angle Plug, Spring Hook, Straight Plug
- Fused: Yes
- Lead Length: 1.2 m
- Safety Category Voltage: 600 V
- Safety Category: CAT III 600 V
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +70 °C



7315273 Test Lead Kit

RS PRO TEST LEAD KIT, CROCODILE CLIP, RIGHT ANGLE PLUG, SPRING

Pack size: **1 x EA**

- Lead Type: Test Lead Kit
- Connector Type: Crocodile Clip, Right Angle Plug, Spring Hook, Straight Plug
- Lead Length: 1.2 m
- Safety Category Voltage: 600 V
- Safety Category: CAT III 600 V
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +70 °C
- Safety Category Level: CAT III



7315277 Test Lead Kit

RS PRO MULTI PIN CONNECTOR TEST KIT, CROCODILE CLIP, PIN SOCKET,

Pack size: **1 x KT**

- Lead Type: Multi Pin Connector Test Kit
- Connector Type: Crocodile Clip, Pin Socket, Right Angle Plug
- Lead Length: 1.2 m
- Current Rating: 20 A
- Safety Category Voltage: 1000 V
- Safety Category: CAT III 1000 V
- Safety Category Level: CAT II



7315286 Multi Pin

INDICATOR, NONCONTACT, AC VOLT STICK

Pack size: **1 x EA**

- Indicator Type: Voltage
- Battery Type: AAA
- Power Source: Battery
- Maximum Detection Voltage: 400 V ac
- Maximum Operating Temperature: +50 °C
- Minimum Operating Temperature: -20 °C



214467 Voltage

RS PRO VOLT-STICK PRO NON CONTACT VOLTAGE DETECTOR, 230V

Pack size: **1 x EA**

- Indicator Type: Voltage
- Battery Type: AAA
- Power Source: Battery
- Safety Category: CAT III 1000 V
- Weight: 40 g
- Diameter: 18 mm
- Length: 146 mm
- Maximum Detection Voltage: 1000 V ac



166838 Voltage

PROVING, UNIT, VOLTSTICK AUDIO

Pack size: **1 x EA**

- Indicator Type: Voltage
- Battery Type: AAA
- Audible Tone: Yes
- Power Source: Battery
- Safety Category: CAT III 1000 V
- Weight: 40 g
- Diameter: 17 mm
- Length: 146 mm



167645 Voltage

RS PRO IVP-1 NONCONTACT VOLTAGE INDICATOR

Pack size: **1 x EA**

- Indicator Type: Voltage
- Battery Type: AAA
- Power Source: Battery
- Safety Category: CAT III 1000 V / CAT IV 600 V, CAT IV, CAT III
- Weight: 40 g
- Height: 18 mm
- Length: 152 mm
- Maximum Detection Voltage: 1000 V ac



1233247 Voltage

VOLTAGE TESTER

Pack size: **1 x EA**

- Indicator Type: Voltage
- Battery Type: AAA
- Power Source: Battery
- Safety Category: CAT III 1000 V, CAT IV 600 V
- Weight: 34 g
- Height: 158 mm
- Length: 25 mm
- Maximum Detection Voltage: 1000 V ac



1611627 Voltage

RS PRO NON CONTACT VOLTAGE INDICATOR

Pack size: **1 x EA**

- Indicator Type: Voltage
- Battery Type: AAA
- Power Source: Battery
- Maximum Operating Temperature: +50 °C
- Minimum Operating Temperature: -20 °C



2383571 Voltage

INDICATOR, MAGNETIC FIELD, MAGNET STICK

Pack size: **1 x EA**

- Indicator Type: Magnetic Field
- Magnetic Sensitivity: 0.3 mT
- Battery Type: AAA
- Power Source: Battery
- Safety Category: CAT III 1000 V
- Weight: 40 g
- Diameter: 17 mm
- Length: 152 mm



3755422 Magnetic Field

RS PRO RS9020 PHASE ROTATION TESTER, CAT III 300 V, 400HZ MAX,

Pack size: **1 x EA**

- Connection Type: Crocodile Clip
- Overvoltage Category: CAT III 600V
- Safety Category: CAT III 300 V
- Non-Contact: Non Contact
- Current Consumption: 20 mA
- Battery Life: 1 (Minimum) yr
- Battery Type: 9V Alkaline
- Power Source: Battery



1231932 Crocodile Clip

RS PRO RS9010 PHASE ROTATION TESTER, CAT III 600 V, CAT IV 300 V,

Pack size: **1 x EA**

- Connection Type: Crocodile Clip
- Overvoltage Category: CAT III 600V, CAT IV 300V
- Display Type: LCD
- Safety Category: CAT III 600 V, CAT IV 300 V
- Current Consumption: 1 mA
- Power Source: Mains
- Dimensions: 130 x 69 x 32 mm
- Weight: 130 g



1231933 Crocodile Clip

RS PRO IPM6300 POWER QUALITY ANALYSER

Pack size: **1 x EA**

- Absolute Maximum Current Measurement: 3000 A
- Absolute Maximum Power Measurement: 9999 kW
- Maximum Voltage: 600 V
- Best Voltage Measurement Accuracy: $\pm 0.5\% \pm 5$ Digits
- Best Current Measurement Accuracy: 1 %
- Display Type: LCD
- Measurement Type: AC Current, AC Voltage, AC Wattage, Harmonic, Phase Angle, Power Factor, Total Harmonic Distortion
- Interface Type: RS232C



1232201 3000 A

RS PRO PT100 RTD SENSOR, 30MM LONG, PATCH SENSOR, +150°C MAXPack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 30 mm
- Maximum Temperature Sensed: +150 °C
- Cable Length: 1 m, 1 mm
- Process Connection: Patch Sensor

**7887132** PT100**RS PRO K NEEDLE TEMPERATURE PROBE, 300MM LENGTH, 6MM**Pack size: **1 x EA**

- Sensor Type: K
- Probe Type: Needle
- Probe Length: 300 mm
- Probe Diameter: 6 mm
- Maximum Temperature Measurement: +250 °C
- Cable Length: 2 m
- Best Accuracy: ± 0.5 %
- Connector Type: Miniature Plug

**255516** K**RS PRO K BOW SURFACE TEMPERATURE PROBE, 110MM**Pack size: **1 x EA**


- Sensor Type: K
- Probe Type: Surface
- Probe Tip Type: Bow
- Probe Length: 110 mm
- Probe Diameter: 60 mm
- Maximum Temperature Measurement: +180 °C
- Cable Length: 2 m
- Best Accuracy: ± 0.25 %

**255550** K**RS PRO K FLAT SPATULA TEMPERATURE PROBE, 200MM**Pack size: **1 x EA**

- Sensor Type: K
- Probe Tip Type: Flat Spatula
- Probe Length: 200 mm
- Probe Diameter: 7 mm
- Maximum Temperature Measurement: +450 °C
- Cable Length: 2 m
- Best Accuracy: ± 0.25 %
- Connector Type: Miniature Plug

**255566** K**RS PRO K NEEDLE TEMPERATURE PROBE, 300MM LENGTH, 3.3MM**Pack size: **1 x EA**

- Sensor Type: K
- Probe Type: Needle
- Probe Length: 300 mm
- Probe Diameter: 3.3 mm
- Maximum Temperature Measurement: +250 °C
- Cable Length: 2 m
- Best Accuracy: ± 0.5 %
- Connector Type: Miniature Plug

**255572** K**RS PRO K GENERAL TEMPERATURE PROBE, 1000MM LENGTH, 6MM**Pack size: **1 x EA**

- Sensor Type: K
- Probe Type: General
- Probe Length: 1000 mm
- Probe Diameter: 6 mm
- Maximum Temperature Measurement: +1100 °C
- Cable Length: 2 m
- Best Accuracy: ± 0.25 %
- Connector Type: Miniature Thermocouple Plug

**255588** K**RS PRO K GENERAL TEMPERATURE PROBE, 300MM LENGTH, 1.5MM**Pack size: **1 x EA**

- Sensor Type: K
- Probe Type: General
- Probe Length: 300 mm
- Probe Diameter: 1.5 mm
- Maximum Temperature Measurement: +1100 °C
- Cable Length: 2 m
- Best Accuracy: ± 0.25 %
- Connector Type: Miniature Plug

**255594** K**RS PRO NTC AIR TEMPERATURE PROBE, 41MM LENGTH, 6MM**Pack size: **1 x EA**

- Sensor Type: NTC
- Probe Type: Air
- Probe Length: 41 mm
- Probe Diameter: 6 mm
- Maximum Temperature Measurement: +80 °C
- Cable Length: 1.5 m
- Best Accuracy: ± 0.5 %

**1241079** NTC**RS PRO NTC AIR TEMPERATURE PROBE, 15MM LENGTH, 6MM**Pack size: **1 x EA**

- Sensor Type: NTC
- Probe Type: Air
- Probe Length: 15 mm
- Probe Diameter: 6 mm
- Maximum Temperature Measurement: +105 °C
- Cable Length: 1.5 m
- Best Accuracy: ± 0.5 %

**1241080** NTC**RS PRO NTC AIR TEMPERATURE PROBE, 40MM LENGTH, 6MM**Pack size: **1 x EA**

- Sensor Type: NTC
- Probe Type: Air
- Probe Length: 40 mm
- Probe Diameter: 6 mm
- Maximum Temperature Measurement: +150 °C
- Cable Length: 1.5 m
- Best Accuracy: ± 0.5 %

**1241081** NTC**RS PRO NTC LIQUID TEMPERATURE PROBE, 48MM LENGTH, 6MM**Pack size: **1 x EA**

- Sensor Type: NTC
- Probe Type: Liquid
- Probe Length: 48 mm
- Probe Diameter: 6 mm
- Maximum Temperature Measurement: +150 °C
- Cable Length: 1.5 m
- Best Accuracy: ± 0.5 %

**1241082** NTC**RS PRO TEMPERATURE PROBE**Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 12 mm
- Probe Length: 40 mm
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +900 °C
- Termination Type: Miniature Plug
- Cable Length: 1.5 m

**1741675** K**RS PRO TEMPERATURE PROBE**Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Length: 170 mm
- Probe Material: Stainless Steel
- Termination Type: Miniature Plug
- Cable Length: 1.5 m

**1741679** K**RS PRO TEMPERATURE PROBE**Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 3.3 mm
- Probe Length: 300 mm
- Probe Material: 316 Stainless Steel
- Maximum Temperature Sensed: +400 °C
- Termination Type: Miniature Plug
- Cable Length: 2 m
- Standards Met: IEC

**1741680** K**RS PRO TEMPERATURE PROBE**Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 3.3 mm
- Probe Length: 300 mm
- Probe Material: 316 Stainless Steel
- Maximum Temperature Sensed: +400 °C
- Termination Type: Miniature Plug
- Cable Length: 2 m
- Standards Met: ANSI

**1741681** K**RS PRO TEMPERATURE PROBE**Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 3 mm
- Probe Length: 300 mm
- Maximum Temperature Sensed: +850 °C
- Termination Type: Miniature Plug
- Cable Length: 2 m
- Standards Met: IEC

**1741683** K

RS PRO TEMPERATURE PROBE

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1.5 mm
- Probe Length: 100 mm
- Maximum Temperature Sensed: +850 °C
- Termination Type: Miniature Plug
- Cable Length: 2 m
- Standards Met: ANSI



1741684 K

RS PRO NTC PERFORATED AIR TEMPERATURE PROBE, 110MM

Pack size: **1 x EA**

- Sensor Type: NTC
- Probe Type: Air
- Probe Tip Type: Perforated
- Probe Length: 110 mm
- Probe Diameter: 4 mm
- Maximum Temperature Measurement: 150 °C
- Cable Length: 2 m
- Best Accuracy: ± 0.2 °C ($\pm 0.15\%$)



2048387 NTC

RS PRO NTC NEEDLE INSERTION TEMPERATURE PROBE, 115MM

Pack size: **1 x EA**

- Sensor Type: NTC
- Probe Type: Insertion
- Probe Tip Type: Needle
- Probe Length: 115 mm
- Probe Diameter: 3.3 mm
- Maximum Temperature Measurement: 150 °C
- Cable Length: 2 m
- Best Accuracy: ± 0.2 °C ($\pm 0.15\%$)



2048388 NTC

RS PRO NTC FLAT INSERTION TEMPERATURE PROBE, 100MM

Pack size: **1 x EA**

- Sensor Type: NTC
- Probe Type: Insertion
- Probe Tip Type: Flat Shaft
- Probe Length: 100 mm
- Probe Diameter: 85 x 3 x 5 mm
- Maximum Temperature Measurement: 150 °C
- Cable Length: 2 m
- Best Accuracy: ± 0.2 °C ($\pm 0.15\%$)



2048389 NTC

RS PRO K GENERAL TEMPERATURE PROBE, 210MM LENGTH, 3MM

Pack size: **1 x EA**

- Sensor Type: K
- Probe Type: General
- Probe Length: 210 mm
- Probe Diameter: 3 mm
- Maximum Temperature Measurement: 1100 °C
- Cable Length: 1 m
- Best Accuracy: ± 1.5 °C ($\pm 0.25\%$)
- Connector Type: Miniature Plug



2048390 K

RS PRO K PERFORATED AIR TEMPERATURE PROBE, 110MM

Pack size: **1 x EA**

- Sensor Type: K
- Probe Type: Air
- Probe Tip Type: Perforated
- Probe Length: 110 mm
- Probe Diameter: 4 mm
- Maximum Temperature Measurement: 750 °C
- Cable Length: 1.2 m
- Best Accuracy: ± 1.5 °C ($\pm 0.25\%$)



2048393 K

RS PRO K SURFACE TEMPERATURE PROBE, 200MM LENGTH, 12MM

Pack size: **1 x EA**

- Sensor Type: K
- Probe Type: Surface
- Probe Length: 200 mm
- Probe Diameter: 12 mm
- Maximum Temperature Measurement: 600 °C
- Cable Length: 1 m
- Best Accuracy: ± 1.5 °C ($\pm 0.25\%$)
- Connector Type: Miniature Plug



2048394 K

RS PRO K MAGNETIC SURFACE TEMPERATURE PROBE, 5MM LENGTH,

Pack size: **1 x EA**

- Sensor Type: K
- Probe Type: Surface
- Probe Tip Type: Magnetic
- Probe Length: 5 mm
- Probe Diameter: 10 mm
- Maximum Temperature Measurement: 1372 °C
- Cable Length: 2 m
- Best Accuracy: ± 1.5 °C ($\pm 0.25\%$)



2048396 K

RS PRO K NEEDLE TEMPERATURE PROBE, 115MM LENGTH, 3.3MM

Pack size: **1 x EA**

- Sensor Type: K
- Probe Tip Type: Needle
- Probe Length: 115 mm
- Probe Diameter: 3.3 mm
- Maximum Temperature Measurement: +250 °C
- Cable Length: 2 m
- Best Accuracy: ± 0.5 %
- Connector Type: Miniature Plug



3428833 K

RS PRO K NEEDLE TEMPERATURE PROBE, 100MM LENGTH, 6MM

Pack size: **1 x EA**

- Sensor Type: K
- Probe Type: Needle
- Probe Length: 100 mm
- Probe Diameter: 6 mm
- Maximum Temperature Measurement: +250 °C
- Cable Length: 2 m
- Best Accuracy: ± 0.5 %
- Connector Type: Miniature Plug



3428855 K

RS PRO T NEEDLE TEMPERATURE PROBE, 115MM LENGTH, 3.3MM

Pack size: **1 x EA**

- Sensor Type: T
- Probe Type: Needle
- Probe Length: 115 mm
- Probe Diameter: 3.3 mm
- Maximum Temperature Measurement: +400 °C
- Cable Length: 2 m
- Best Accuracy: ± 0.15 %
- Connector Type: Miniature Thermocouple Plug



3428849 T

RS PRO K GENERAL TEMPERATURE PROBE, 100MM LENGTH, 1.5MM

Pack size: **1 x EA**

- Sensor Type: K
- Probe Type: General
- Probe Length: 100 mm
- Probe Diameter: 1.5 mm
- Maximum Temperature Measurement: +1100 °C
- Cable Length: 2 m
- Best Accuracy: ± 0.25 %
- Connector Type: Miniature Plug



3428883 K

RS PRO K GENERAL TEMPERATURE PROBE, 100MM LENGTH, 3MM

Pack size: **1 x EA**

- Sensor Type: K
- Probe Type: General
- Probe Length: 100 mm
- Probe Diameter: 3 mm
- Maximum Temperature Measurement: +1100 °C
- Cable Length: 2 m
- Best Accuracy: ± 0.25 %
- Connector Type: Miniature Plug



3428899 K

RS PRO T GENERAL PURPOSE TEMPERATURE PROBE, 100MM

Pack size: **1 x EA**

- Sensor Type: T
- Probe Type: General Purpose
- Probe Length: 100 mm
- Probe Diameter: 1.5 mm
- Maximum Temperature Measurement: +400 °C
- Cable Length: 2 m
- Best Accuracy: ± 0.15 %
- Connector Type: Miniature Thermocouple Plug



3428912 T

RS PRO K GENERAL TEMPERATURE PROBE, 300MM LENGTH, 3MM

Pack size: **1 x EA**

- Sensor Type: K
- Probe Type: General
- Probe Length: 300 mm
- Probe Diameter: 3 mm
- Maximum Temperature Measurement: +1100 °C
- Cable Length: 2 m
- Best Accuracy: ± 0.25 %
- Connector Type: Miniature Plug



3428928 K

RS PRO K SURFACE TEMPERATURE PROBE, 110MM LENGTH, 10MM

Pack size: **1 x EA**

- Sensor Type: K
- Probe Type: Surface
- Probe Length: 110 mm
- Probe Diameter: 10 mm
- Maximum Temperature Measurement: +250 °C
- Cable Length: 2 m
- Best Accuracy: ± 0.25 %
- Connector Type: Miniature Plug



3428956 K

RS PRO K SURFACE TEMPERATURE PROBE, 110MM LENGTH, 6MMPack size: **1 x EA**

- Sensor Type: K
- Probe Type: Surface
- Probe Length: 110 mm
- Probe Diameter: 6 mm
- Maximum Temperature Measurement: +600 °C
- Cable Length: 2 m
- Best Accuracy: ± 0.25 %
- Connector Type: Miniature Plug

**3428962** K**RS PRO T SURFACE TEMPERATURE PROBE, 100MM LENGTH, 1MM**Pack size: **1 x EA**

- Sensor Type: T
- Probe Type: Surface
- Probe Length: 100 mm
- Probe Diameter: 1 mm
- Maximum Temperature Measurement: +180 °C
- Cable Length: 2 m
- Best Accuracy: ± 0.25 %
- Connector Type: Miniature Thermocouple Plug

**3428984** T**RS PRO K SURFACE TEMPERATURE PROBE, 210MM LENGTH, 12MM**Pack size: **1 x EA**

- Sensor Type: K
- Probe Type: Surface
- Probe Length: 210 mm
- Probe Diameter: 12 mm
- Maximum Temperature Measurement: +1100 °C
- Cable Length: 2 m
- Best Accuracy: ± 0.25 %
- Connector Type: Miniature Plug

**3428978** K**RS PRO TYPE K THERMOCOUPLE AIR TEMPERATURE PROBE, 110MM**Pack size: **1 x EA**

- Probe Type: Type K Thermocouple
- Probe Length: 110 mm
- Probe Diameter: 4 mm
- Maximum Temperature Measurement: +750 °C
- Cable Length: 2 m
- Best Accuracy: ± 0.25 %
- Connector Type: Miniature Plug

**3428990** Type K**RS PRO TYPE K THERMOCOUPLE HANDLE PROBE, 3MM DIAMETER,**Pack size: **1 x EA**

- Probe Type: Type K Thermocouple
- Probe Diameter: 3 mm
- Maximum Temperature Measurement: +250 °C
- Cable Length: 2 m
- Best Accuracy: ± 0.25 %
- Connector Type: Miniature Plug

**3429038** Type K**RS PRO K AIR TEMPERATURE PROBE, 110MM LENGTH, 4MM DIAMETER,**Pack size: **1 x EA**

- Sensor Type: K
- Probe Type: Air
- Probe Length: 110 mm
- Probe Diameter: 4 mm
- Maximum Temperature Measurement: +750 °C
- Best Accuracy: ± 0.25 %
- Connector Type: Miniature Plug

**3429050** K**RS PRO K GENERAL TEMPERATURE PROBE, 100MM LENGTH, 3MM**Pack size: **1 x EA**

- Sensor Type: K
- Probe Type: General
- Probe Length: 100 mm
- Probe Diameter: 3 mm
- Maximum Temperature Measurement: +750 °C
- Best Accuracy: ± 0.25 %
- Connector Type: Miniature Plug

**3429072** K**RS PRO K INSERTION, NEEDLE TEMPERATURE PROBE, 100MM**Pack size: **1 x EA**

- Sensor Type: K
- Probe Type: Insertion, Needle
- Probe Length: 100 mm
- Probe Diameter: 3.3 mm
- Maximum Temperature Measurement: +250 °C
- Best Accuracy: ± 0.25 %
- Connector Type: Miniature Plug

**3429094** K**RS PRO T GENERAL PURPOSE TEMPERATURE PROBE, 100MM**Pack size: **1 x EA**

- Sensor Type: T
- Probe Type: General Purpose
- Probe Length: 100 mm
- Probe Diameter: 3 mm
- Maximum Temperature Measurement: +250 °C
- Best Accuracy: ± 0.15 %
- Connector Type: Miniature Plug

**3429088** T**RS PRO K SURFACE TEMPERATURE PROBE, 100MM LENGTH, 4MM**Pack size: **1 x EA**

- Sensor Type: K
- Probe Type: Surface
- Probe Length: 100 mm
- Probe Diameter: 4 mm
- Maximum Temperature Measurement: +750 °C
- Best Accuracy: ± 0.25 %
- Connector Type: Miniature Plug

**3429117** K**RS PRO T SURFACE TEMPERATURE PROBE, 110MM LENGTH, 10MM**Pack size: **1 x EA**

- Sensor Type: T
- Probe Type: Surface
- Probe Length: 110 mm
- Probe Diameter: 10 mm
- Maximum Temperature Measurement: +250 °C
- Best Accuracy: ± 0.25 %
- Connector Type: Miniature Plug

**3429139** T**RS PRO TYPE K THERMOCOUPLE TEMPERATURE PROBE KIT, +1100 °C**Pack size: **1 x EA**

- Probe Type: Type K Thermocouple
- Maximum Temperature Measurement: +1100 °C
- Cable Length: 2 m
- Best Accuracy: ± 2.5 °C
- Connector Type: Miniature Plug

**3429151** Type K**RS PRO TYPE K THERMOCOUPLE TEMPERATURE PROBE KIT, +1100 °C**Pack size: **1 x EA**

- Probe Type: Type K Thermocouple
- Maximum Temperature Measurement: +1100 °C
- Cable Length: 2 m
- Best Accuracy: ± 2.5 °C
- Connector Type: Miniature Plug

**3429189** Type K**RS PRO K PIPE CLAMP SURFACE TEMPERATURE PROBE, 110MM**Pack size: **1 x EA**

- Sensor Type: K
- Probe Type: Surface
- Probe Tip Type: Pipe Clamp
- Probe Length: 110 mm
- Probe Diameter: 25 mm
- Maximum Temperature Measurement: +150 °C
- Cable Length: 2 m
- Best Accuracy: ± 0.25 %

**3429202** K**RS PRO PT100 AIR TEMPERATURE PROBE**Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Type: Air
- Probe Length: 110 mm
- Probe Diameter: 4 mm
- Maximum Temperature Measurement: +750 °C
- Cable Length: 2 m
- Best Accuracy: ± 0.2 %

**3482411** PT100**RS PRO PT100 RTD INSERTION, NEEDLE TEMPERATURE PROBE,**Pack size: **1 x EA**

- Sensor Type: PT100 RTD
- Probe Type: Insertion, Needle
- Probe Length: 100 mm
- Probe Diameter: 4 mm
- Maximum Temperature Measurement: +250 °C
- Cable Length: 2 m
- Best Accuracy: ± 0.15 °C

**3482427** PT100 RTD

RS PRO PT100 RTD INSERTION, NEEDLE TEMPERATURE PROBE,

Pack size: **1 x EA**

- Sensor Type: PT100 RTD
- Probe Type: Insertion, Needle
- Probe Length: 100 mm
- Probe Diameter: 3.3 mm
- Maximum Temperature Measurement: +250 °C
- Cable Length: 2 m
- Best Accuracy: ± 0.2 %



3482433 PT100 RTD

RS PRO AIR TEMPERATURE PROBE, TYPE K, MAX. +750 °C

Pack size: **1 x EA**

- Sensor Type: K
- Probe Type: Air
- Probe Length: 110 mm
- Probe Diameter: 30 mm
- Maximum Temperature Measurement: +750 °C
- Cable Length: 2 m
- Best Accuracy: ± 0.25 %
- Connector Type: Miniature Thermocouple Plug



4342421 K

RS PRO SURFACE TEMPERATURE PROBE, TYPE K, MAX. +800 °C

Pack size: **1 x EA**

- Sensor Type: K
- Probe Type: Surface
- Probe Tip Type: Pipe Clip
- Probe Length: 195 mm
- Probe Diameter: 6 mm
- Maximum Temperature Measurement: +800 °C
- Cable Length: 2 m
- Best Accuracy: ± 0.25 %



4342437 K

RS PRO K IMMERSION, SURFACE TEMPERATURE PROBE, 110MM

Pack size: **1 x EA**

- Sensor Type: K
- Probe Type: Immersion, Surface
- Probe Length: 110 mm
- Probe Diameter: 10 mm
- Maximum Temperature Measurement: +250 °C
- Cable Length: 2 m
- Best Accuracy: ± 0.25 %
- Connector Type: Miniature Plug



7128196 K

RS PRO K IMMERSION TEMPERATURE PROBE, 50MM LENGTH, 4MM

Pack size: **1 x EA**

- Sensor Type: K
- Probe Type: Immersion
- Probe Length: 50 mm
- Probe Diameter: 4 mm
- Maximum Temperature Measurement: +250 °C
- Cable Length: 2 m
- Best Accuracy: ± 1.5 °C
- Connector Type: Miniature Plug



7887144 K

RS PRO CABLE MINI PLUG TO MINI PLUG

Pack size: **1 x EA**

- Accessory Type: Cable Mini Plug to Mini Plug



7887122 Cable Mini Plug

RS PRO CABLE MINI PLUG TO MINI PLUG

Pack size: **1 x EA**

- Accessory Type: Cable Mini Plug to Mini Plug



7887126 Cable Mini Plug

RS PRO THERMO ATTACHMENT PAD

Pack size: **1 x EA**

- Accessory Type: Thermo attachment pad



7887148 Thermo

RS PRO RED TERMINAL POST, 3KV, 30A, M6 THREAD

Pack size: **1 x EA**

- Colour: Red
- Current Rating: 30 A
- Thread Size: M6
- Voltage Rating: 3 kV
- Insulated: Yes
- Body Material: Phenolic Resin, Tenite Butyrate
- Maximum Panel Thickness: 25 mm
- Height Above Panel: 28 mm



444775 Red

CONNECTOR,TEST,TERMINAL,INSULATED,LARGE,30A,BLACK

Pack size: **1 x EA**

- Colour: Black
- Current Rating: 30 A
- Thread Size: M6
- Voltage Rating: 3 kV
- Insulated: Yes
- Body Material: Phenolic Resin, Tenite Butyrate
- Maximum Panel Thickness: 25 mm
- Height Above Panel: 28 mm



444781 Black

SMALL PANEL TERMINAL, BLACK,4MM

Pack size: **5 x EA**

- Colour: Black
- Hole Diameter: 4 mm
- Current Rating: 30 A
- Thread Size: 2BA
- Insulated: Yes
- Body Material: Glass Fibre Reinforced Nylon, PP
- Maximum Panel Thickness: 7 mm
- Height Above Panel: 33 mm



6778740 Black

SMALL PANEL TERMINAL, RED,4MM

Pack size: **5 x EA**

- Colour: Red
- Hole Diameter: 4 mm
- Current Rating: 30 A
- Thread Size: 2BA
- Insulated: Yes
- Body Material: Glass Fibre Reinforced Nylon, PP
- Maximum Panel Thickness: 7 mm
- Height Above Panel: 33 mm



6778746 Red

PANEL TERMINAL POST ASSEMBLY,4MM

Pack size: **1 x EA**

- Colour: Black, Red
- Hole Diameter: 4 mm
- Current Rating: 30 A
- Thread Size: 2BA
- Insulated: Yes
- Body Material: Glass Fibre Reinforced Nylon, PP
- Height Above Panel: 30 mm



6778759 Black, Red

RS PRO TEST LEAD & CONNECTOR KIT WITH 1 BLACK LEAD ASSEMBLY, 1 RED

Pack size: **1 x EA**

- Kit Contents: 1 Black Lead Assembly, 1 Red Lead Assembly



2188293 1 Black Lead

RS PRO TEST LEAD & CONNECTOR KIT WITH 1 BLACK LEAD ASSEMBLY, 1 RED

Pack size: **1 x EA**

- Kit Contents: 1 Black Lead Assembly, 1 Red Lead Assembly, 1 x Black Screw-Fit Crocodile Clip, 1 x Red Screw-Fit Crocodile Clip



2188294 1 Black Lead

CONNECTOR,TEST,LEAD,4MM,EXTENSION REEL,12M,BLACK

Pack size: **1 x EA**

- Accessory Type: Extension Reel
- Cable Length: 12 m
- Cable Thickness: 1 mm²
- Cable Colour: Black
- Plug Size: 4 mm
- Socket Size: 4 mm
- Safety Category: CAT III 1000 V, CAT IV 600 V
- Safety Category Level: CAT III, CAT IV



6120829 Extension Reel

TEST LEADS 5000V

Pack size: **1 x EA**

- Lead Length: 1 m
- Current Rating: 10 A
- Colour: Black
- Test Lead Type: 4 mm Connector Test Leads
- Voltage Rating: 5 kV
- Connector A Gender: Male
- Connector A Orientation: Straight



4233175 1 m

TEST LEADS 5000V

Pack size: **1 x EA**

- Lead Length: 1 m
- Current Rating: 10 A
- Colour: Red
- Test Lead Type: 4 mm Connector Test Leads
- Voltage Rating: 5 kV
- Connector A Gender: Male
- Connector A Orientation: Straight



4233197 1 m

0.5M BLACK TEST LEAD, 4MM PLUG

Pack size: **1 x EA**

- Lead Length: 500 mm
- Current Rating: 2.5 A
- Colour: Black
- Test Lead Type: 4 mm Connector Test Leads
- Voltage Rating: 50 V ac
- Connector A Gender: Male
- Connector B Gender: Male
- Connector A Stackable: Yes



6684572 500 mm

0.5M RED TEST LEAD, 4MM PLUG

Pack size: **1 x EA**

- Lead Length: 500 mm
- Current Rating: 2.5 A
- Colour: Red
- Test Lead Type: 4 mm Connector Test Leads
- Voltage Rating: 50 V ac
- Connector A Gender: Male
- Connector B Gender: Male
- Connector A Stackable: Yes



6684581 500 mm

1M BLACK TEST LEAD, 4MM PLUG

Pack size: **1 x EA**

- Lead Length: 1 m
- Current Rating: 2.5 A
- Colour: Black
- Test Lead Type: 4 mm Connector Test Leads
- Voltage Rating: 50 V ac
- Connector A Gender: Male
- Connector B Gender: Male
- Connector A Stackable: Yes



6684584 1 m

UV EPROM, M27C4001-12F1 512KX8BIT FDIP32W

Pack size: **1 x EA**

- Lead Length: 1 m
- Current Rating: 2.5 A
- Colour: Red
- Test Lead Type: 4 mm Connector Test Leads
- Voltage Rating: 50 V ac
- Connector A Gender: Male
- Connector B Gender: Male
- Connector A Stackable: Yes



6684588 1 m

MODULAR TEST LEAD STORAGE RACK

Pack size: **1 x EA**

- Accessory Type: Modular Lead Storage Rack
- Number of Slots: 15
- Maximum Cable Diameter: 16.9 mm
- Colour: Grey
- Body Material: Aluminium
- Dimensions: 350 x 81 x 46 mm
- Height: 46 mm
- Length: 350 mm



6684597 Modular Lead

RS PRO POINT TEST PROBE, 1.6MM SOCKET, 2A

Pack size: **5 x EA**

- Current Rating: 2 A
- Probe Tip Type: Point
- Probe Socket Diameter: 1.6 mm



521611 2 A

SMALL ULTRA THIN BACK PROBE SET

Pack size: **1 x SET**

- Current Rating: 10 A
- Maximum Operating Temperature: +70 °C
- Minimum Operating Temperature: -20 °C



1247401 10 A

SMALL ULTRA THIN BACK PROBE SET

Pack size: **1 x PR**

- Current Rating: 10 A
- Maximum Operating Temperature: +70 °C
- Minimum Operating Temperature: -20 °C



1247402 10 A

EXTENDED BACK PROBE SET

Pack size: **1 x PR**

- Current Rating: 10 A
- Maximum Operating Temperature: +70 °C
- Minimum Operating Temperature: -20 °C



1247403 10 A

RIGHT ANGLED BACK PROBE LEAD SET

Pack size: **1 x PR**

- Current Rating: 10 A
- Maximum Operating Temperature: +70 °C
- Minimum Operating Temperature: -20 °C



1247404 10 A

RS PRO TEST PROBE

Pack size: **1 x EA**

- Maximum Operating Temperature: +150 °C
- Minimum Operating Temperature: -10 °C



1253732 +150 °C

RS PRO TEST PROBE

Pack size: **1 x EA**

- Lead Type: Fused Test Prods
- Connector Type: Banana Jack
- Fused: Yes
- Safety Category Voltage: 1000 V
- Safety Category: CAT III 1000 V
- Safety Category Level: CAT III



1253734 Fused Test Prods

SPRUNG GRABBER FOR MULTIMETER TEST LEADS

Pack size: **1 x EA**

- Accessory Type: Grabber



1253739 Grabber

RS PRO TEST PROBE

Pack size: **1 x EA**

- Lead Type: Extension Lead Set
- Fused: No
- Safety Category Voltage: 1000 V
- Safety Category: CAT III 1000 V



1999852 Extension Lead

RS PRO TEST PROBE

Pack size: **1 x EA**

- Lead Type: Thin Fine Insulated Prod Set
- Fused: No
- Safety Category Voltage: 1000 V
- Safety Category: CAT III 1000 V



1999853 Thin Fine

RS PRO TYPE K TEMPERATURE PROBE 1500MM LENGTH, 7/0.2MM DIAMETER

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 7/0.2 mm
- Probe Length: 1500 mm
- Maximum Temperature Sensed: 280 °C
- Termination Type: Miniature Plug
- Cable Length: 1.5 m



2048391 K

THERMOMETER, PROBE, FINE WIRE, K, FIBRE GLASS

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1.2 mm
- Probe Length: 1 m
- Maximum Temperature Sensed: +450 °C
- Probe Material: Nickel Aluminium, Nickel Chrome
- Termination Type: Miniature Plug
- Cable Length: 1 m
- Standards Met: IEC



4094920 K

RS PRO IVT-20, LCD VOLTAGE TESTER, 750V AC/DC, CONTINUITY CHECK,

Pack size: **1 x EA**

- Maximum Voltage: 750 V ac/dc
- Continuity Check: Yes
- Safety Category: CAT III 750 V, CAT IV 600 V
- Display Type: LCD
- RCD Trip Test: Yes
- IP Rating: IP65
- Battery Type: AAA, LR03
- Power Source: Battery



1241962 750 V ac/dc

RS PRO TEST PROBE

Pack size: **1 x EA**

- Lead Type: Extension Lead Set
- Fused: No
- Safety Category Voltage: 1000 V
- Safety Category: CAT III 1000 V



1999854 Extension Lead

RS PRO TYPE K TEMPERATURE PROBE 800MM LENGTH, 0.2MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 0.2 mm
- Probe Length: 800 mm
- Maximum Temperature Sensed: +450 °C
- Termination Type: Miniature Plug
- Cable Length: 800 mm



2048392 K

K FINE WIRE THERMOCOUPLE 3M -100TO250DEG

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1/0.3 mm
- Probe Length: 3 m
- Maximum Temperature Sensed: +250 °C
- Termination Type: Miniature Plug
- Cable Length: 3 m
- Standards Met: RoHS Compliant
- Response Time: 0.1 s



4791788 K

RS PRO G09-NC1, LED VOLTAGE TESTER, 1000V AC, NO, BATTERY

Pack size: **1 x EA**

- Maximum Voltage: 1000 V ac
- Continuity Check: No
- Safety Category: CAT II 1000 V
- Display Type: LED
- Battery Type: AAA
- Power Source: Battery
- Dimensions: 152 x 4.5 mm
- Weight: 58 g



1923685 1000 V ac

CONNECTOR, TEST, ACCESSORIES, FUSED, LEAD, SPIKE

Pack size: **1 x PR**

- Lead Type: Thin Fine Insulated Prod Set
- Safety Category Voltage: 600 V



2627770 Thin Fine

RS PRO TYPE T THERMOCOUPLE 100MM LENGTH, 1.6MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: T
- Probe Diameter: 1.6 mm
- Probe Length: 100 mm
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +250 °C
- Termination Type: Cable
- Cable Length: 1.5 m
- Standards Met: IEC



2194674 T

RS PRO THERMOMETER ACCESSORY FOR USE WITH IDM 50 SERIES

Pack size: **1 x EA**

- Accessory Type: USB Cable, WinDMM 50 Software
- For Use With: IDM 50 Series



7048135 USB Cable,

RS PRO POLYESTER BACKPACK WITH SHOULDER STRAP 340MM X 220MM X

Pack size: **1 x EA**

- Bag Type: Backpack
- Material: Polyester
- Length: 340 mm
- Width: 220 mm
- Height: 410 mm
- Shoulder Strap: Yes
- Lock Type: Zipper



7887211 Backpack

CONNECTOR, TEST, ACCESSORIES, FUSED, LEAD, LANTERN, PROBE

Pack size: **1 x PR**

- Lead Type: Probe Set
- Connector Type: Lantern



2627786 Probe Set

RS PRO TYPE K THERMOCOUPLE 1M LENGTH, 0.2MM DIAMETER, -50°C →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 0.2 mm
- Probe Length: 1 m
- Maximum Temperature Sensed: +250 °C
- Probe Material: Nickel Aluminium, Nickel Chrome
- Termination Type: Miniature Plug
- Cable Length: 1 m
- Standards Met: RoHS Compliant



4094908 K

RS PRO IVT-10, LED VOLTAGE TESTER, 750V AC/DC, CONTINUITY CHECK,

Pack size: **1 x EA**

- Maximum Voltage: 750 V ac/dc
- Continuity Check: Yes
- Safety Category: CAT III 750 V, CAT IV 600 V
- Display Type: LED
- RCD Trip Test: Yes
- IP Rating: IP65
- Battery Type: AAA, LR03
- Power Source: Battery



1241961 750 V ac/dc

**GROMMET,EDGING STRIP,PANELS 1.6
Ø&A 2MM,5M**Pack size: **5 x MTR**

- Grommet Type: Grommet Strip
- Minimum Panel Thickness: 1 mm
- Minimum Cable Diameter: 1.1 mm
- Maximum Cable Diameter: 2 mm
- Material: PE
- Colour: Natural
- Grommet Strip Length: 5 m
- Maximum Panel Thickness: 5.5 mm

**406928** Grommet Strip**GROMMET,EDGING STRIP,PANELS 2.4
Ø&A 3.2MM,5M**Pack size: **5 x MTR**

- Grommet Type: Grommet Strip
- Minimum Panel Thickness: 4.5 mm
- Minimum Cable Diameter: 1.5 mm
- Maximum Cable Diameter: 3.2 mm
- Material: PE
- Colour: Natural
- Grommet Strip Length: 5 m

**406938** Grommet Strip**RS PRO BLACK NYLON**Pack size: **1 x KT**

- Minimum Cable Diameter: 4.8 mm
- Maximum Cable Diameter: 45 mm
- Material: Nylon
- Colour: Black
- Minimum Operating Temperature: -20 °C

**2326875** 4.8 mm**RS PRO METAL LOCKABLE HANDLE,
KEY UNLOCK**Pack size: **1 x EA**

- Unlock Method: Key
- Material: Metal

**222963** Key**RS PRO CABINET LOCK**Pack size: **1 x EA**

- Type: Key Lock
- For Use With: Enclosure
- Material: Metal

**8428478** Key Lock**RS PRO GREY ABS PUSH BUTTON
ENCLOSURE - 22MM DIAMETER**Pack size: **1 x EA**

- Series: CCS
- Cutout Diameter: 22 mm
- Enclosure Colour: Grey
- Enclosure Material: ABS
- IP Rating: IP65
- Length: 70 mm
- Width: 70 mm
- Depth: 51 mm

**1947454** CCS**RS PRO GREY ABS PUSH BUTTON
ENCLOSURE - 1 HOLE 22MM DIAMETER**Pack size: **1 x EA**

- Series: CCS
- Cutout Diameter: 22 mm
- Number of Cutouts: 1
- Enclosure Colour: Grey
- Enclosure Material: ABS
- IP Rating: IP65
- Length: 70 mm
- Width: 70 mm

**1947455** CCS**RS PRO GREY ABS PUSH BUTTON
ENCLOSURE - 1 HOLE 22MM DIAMETER**Pack size: **1 x EA**


- Series: CCS
- Cutout Diameter: 22 mm
- Number of Cutouts: 1
- Enclosure Colour: Grey
- Enclosure Material: ABS
- IP Rating: IP65
- Length: 70 mm
- Width: 70 mm

**1947458** CCS**RS PRO GREY/YELLOW ABS PUSH
BUTTON ENCLOSURE - 1 HOLE 22MM**Pack size: **1 x EA**

- Series: CCS
- Cutout Diameter: 22 mm
- Number of Cutouts: 1
- Enclosure Colour: Grey/Yellow
- Enclosure Material: ABS
- IP Rating: IP65
- Length: 70 mm
- Width: 70 mm

**1947456** CCS**RS PRO GREY/YELLOW ABS PUSH
BUTTON ENCLOSURE - 1 HOLE 22MM**Pack size: **1 x EA**

- Series: CCS
- Cutout Diameter: 22 mm
- Number of Cutouts: 1
- Enclosure Colour: Grey/Yellow
- Enclosure Material: ABS
- IP Rating: IP65
- Length: 70 mm
- Width: 70 mm

**1947459** CCS**RS PRO GREY ABS PUSH BUTTON
ENCLOSURE - 22MM DIAMETER**Pack size: **1 x EA**

- Series: CCS
- Cutout Diameter: 22 mm
- Enclosure Colour: Grey
- Enclosure Material: ABS
- IP Rating: IP65
- Length: 70 mm
- Width: 70 mm
- Depth: 74 mm

**1947457** CCS**RS PRO GREY ABS PUSH BUTTON
ENCLOSURE - 2 HOLE 22MM**Pack size: **1 x EA**

- Series: CCS
- Cutout Diameter: 22 mm
- Number of Cutouts: 2
- Enclosure Colour: Grey
- Enclosure Material: ABS
- IP Rating: IP65
- Length: 105 mm
- Width: 70 mm

**1947461** CCS**RS PRO GREY ABS PUSH BUTTON
ENCLOSURE - 22MM DIAMETER**Pack size: **1 x EA**

- Series: CCS
- Cutout Diameter: 22 mm
- Enclosure Colour: Grey
- Enclosure Material: ABS
- IP Rating: IP65
- Length: 105 mm
- Width: 70 mm
- Depth: 74 mm

**1947462** CCS**RS PRO GREY ABS PUSH BUTTON
ENCLOSURE - 2 HOLE 22MM**Pack size: **1 x EA**

- Series: CCS
- Cutout Diameter: 22 mm
- Number of Cutouts: 2
- Enclosure Colour: Grey
- Enclosure Material: ABS
- IP Rating: IP65
- Length: 105 mm
- Width: 70 mm

**1947463** CCS**RS PRO GREY ABS PUSH BUTTON
ENCLOSURE - 22MM DIAMETER**Pack size: **1 x EA**

- Series: CCS
- Cutout Diameter: 22 mm
- Enclosure Colour: Grey
- Enclosure Material: ABS
- IP Rating: IP65
- Length: 140 mm
- Width: 70 mm
- Depth: 51 mm

**1947464** CCS**RS PRO GREY ABS PUSH BUTTON
ENCLOSURE - 22MM DIAMETER**Pack size: **1 x EA**

- Series: CCS
- Cutout Diameter: 22 mm
- Enclosure Colour: Grey
- Enclosure Material: ABS
- IP Rating: IP65
- Length: 140 mm
- Width: 70 mm
- Depth: 74 mm

**1947465** CCS

RS PRO GREY ABS PUSH BUTTON ENCLOSURE - 22MM DIAMETER

Pack size: **1 x EA**

- Series: CCS
- Cutout Diameter: 22 mm
- Enclosure Colour: Grey
- Enclosure Material: ABS
- IP Rating: IP65
- Length: 185 mm
- Width: 70 mm
- Depth: 74 mm



1947467 CCS

RS PRO WHITE ABS DESKTOP ENCLOSURE, SLOPED FRONT, 127.37 X

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 127.4 mm
- External Width: 178.1 mm
- External Height: 73.6 mm
- External Dimensions: 127.37 x 178.14 x 73.56 mm
- Sloped Front: Yes
- Colour: White
- Standards Met: UL 94 HB, ULE56070



221011 ABS

RS PRO WHITE ABS DESKTOP ENCLOSURE, SLOPED FRONT, 203.2 X

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 203.2 mm
- External Width: 254 mm
- External Height: 101.6 mm
- External Dimensions: 203.2 x 254.01 x 101.6 mm
- Sloped Front: Yes
- Colour: White
- Standards Met: UL 94 HB, ULE56070



221027 ABS

RS PRO GREY ABS DESKTOP ENCLOSURE, 250 X 275 X 75MM

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 250 mm
- External Width: 275 mm
- External Height: 75 mm
- External Dimensions: 250 x 275 x 75 mm
- Sloped Front: No
- Colour: Grey
- Standards Met: UL 94 HB



504748 ABS

RS PRO GREY ABS DESKTOP ENCLOSURE, 250 X 275 X 100MM

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 250 mm
- External Width: 275 mm
- External Height: 100 mm
- External Dimensions: 250 x 275 x 100 mm
- Sloped Front: No
- Colour: Grey
- Standards Met: UL 94 HB



504754 ABS

ENCLOSURE,CASE,DIN RAIL MOUNT,EN50/022

Pack size: **1 x EA**

- Enclosure Type: DIN Rail
- Body Material: Polycarbonate, Polystyrene
- Length: 110 mm
- Dimensions: 110 x 75 x 50 mm
- Width: 75 mm
- Height: 50 mm
- Maximum Terminals: 12
- Minimum Operating Temperature: -10 °C



507680 DIN Rail

RS PRO MODULAR ENCLOSURE ENCLOSURE TYPE, 53.4 X 89.4 X

Pack size: **1 x EA**

- Enclosure Type: Modular Enclosure
- Body Material: ABS
- Length: 53.4 mm
- Dimensions: 53.4 x 89.4 x 65.2 mm
- Width: 89.4 mm
- Height: 65 mm
- Colour: Light Grey



1862289 Modular

LIGHTGRAY, DIN RAIL, NUMBER OF MODULES:

Pack size: **1 x EA**

- Enclosure Type: Modular Enclosure
- Body Material: ABS
- Length: 34.4 mm
- Dimensions: 34.4 x 88.8 x 62.8 mm
- Width: 88.8 mm
- Height: 63 mm
- Colour: Light Grey



1862290 Modular

LIGHTGRAY, DIN RAIL, NUMBER OF MODULES:

Pack size: **1 x EA**

- Enclosure Type: Modular Enclosure
- Body Material: ABS
- Length: 17.5 mm
- Dimensions: 17.5 x 90.0 x 64.9 mm
- Width: 90 mm
- Height: 65 mm
- Colour: Light Grey



1862292 Modular

RS PRO MODULAR ENCLOSURE ENCLOSURE TYPE, 35.2 X 90.1 X

Pack size: **1 x EA**

- Enclosure Type: Modular Enclosure
- Body Material: ABS
- Length: 35.2 mm
- Dimensions: 35.2 x 90.1 x 65.0 mm
- Width: 90.1 mm
- Height: 65 mm
- Colour: Light Grey



1862293 Modular

RS PRO MODULAR ENCLOSURE ENCLOSURE TYPE, 52.5 X 90.0 X

Pack size: **1 x EA**

- Enclosure Type: Modular Enclosure
- Body Material: ABS
- Length: 52.5 mm
- Dimensions: 52.5 x 90.0 x 65.0 mm
- Width: 90 mm
- Height: 65 mm
- Colour: Light Grey



1862294 Modular

RS PRO DIN RAIL ENCLOSURE ENCLOSURE TYPE, 105.0 X 90.0 X

Pack size: **1 x EA**

- Enclosure Type: DIN Rail Enclosure
- Body Material: ABS
- Length: 105 mm
- Dimensions: 105.0 x 90.0 x 65.3 mm
- Width: 90 mm
- Height: 65 mm
- Colour: Light Grey



1862297 DIN Rail

RS PRO OPEN TOP ENCLOSURE TYPE, 90 X 53 X 114MM, POLYCARBONATE

Pack size: **1 x EA**

- Enclosure Type: Open Top
- Body Material: Polycarbonate
- DIN Rail Type: Enclosure
- Length: 90 mm
- Dimensions: 90 x 53 x 114 mm
- Width: 53 mm
- Height: 114 mm
- Colour: Light Grey



1947471 Open Top

RS PRO OPEN TOP ENCLOSURE TYPE, 90 X 53 X 31.9MM, POLYCARBONATE

Pack size: **1 x EA**

- Enclosure Type: Open Top
- Body Material: Polycarbonate
- DIN Rail Type: Enclosure
- Length: 90 mm
- Dimensions: 90 x 53 x 31.9 mm
- Width: 53 mm
- Height: 32 mm
- Maximum Terminals: 2



1947472 Open Top

RS PRO OPEN TOP ENCLOSURE TYPE, 90 X 53 X 31.9MM, POLYCARBONATE

Pack size: **1 x EA**

- Enclosure Type: Open Top
- Body Material: Polycarbonate
- DIN Rail Type: Enclosure
- Length: 90 mm
- Dimensions: 90 x 53 x 31.9 mm
- Width: 53 mm
- Height: 32 mm
- Colour: Light Grey



1947473 Open Top

RS PRO SOLID TOP ENCLOSURE TYPE, 90 X 53 X 114MM, POLYCARBONATE

Pack size: **1 x EA**

- Enclosure Type: Solid Top
- Body Material: Polycarbonate
- DIN Rail Type: Enclosure
- Length: 90 mm
- Dimensions: 90 x 53 x 114 mm
- Width: 53 mm
- Height: 114 mm
- Maximum Terminals: 2



1947474 Solid Top

RS PRO SOLID TOP ENCLOSURE TYPE, 90 X 53 X 31.9MM, POLYCARBONATEPack size: **1 x EA**

- Enclosure Type: Solid Top
- Body Material: Polycarbonate
- DIN Rail Type: Enclosure
- Length: 90 mm
- Dimensions: 90 x 53 x 31.9 mm
- Width: 53 mm
- Height: 32 mm
- Maximum Terminals: 2

**1947476** Solid Top**RS PRO OPEN TOP ENCLOSURE TYPE, 90 X 106.2 X 31.9MM,**Pack size: **1 x EA**

- Enclosure Type: Open Top
- Body Material: Polycarbonate
- DIN Rail Type: Enclosure
- Length: 90 mm
- Dimensions: 90 x 106.2 x 31.9 mm
- Width: 106.2 mm
- Height: 32 mm
- Maximum Terminals: 4

**1947480** Open Top**RS PRO SOLID TOP ENCLOSURE TYPE, 90 X 106.2 X 114MM,**Pack size: **1 x EA**

- Enclosure Type: Solid Top
- Body Material: Polycarbonate
- DIN Rail Type: Enclosure
- Length: 90 mm
- Dimensions: 90 x 106.2 x 114 mm
- Width: 106.2 mm
- Height: 114 mm
- Colour: Light Grey

**1947483** Solid Top**RS PRO SOLID TOP ENCLOSURE TYPE, 90 X 106.2 X 31.9MM,**Pack size: **1 x EA**

- Enclosure Type: Solid Top
- Body Material: Polycarbonate
- DIN Rail Type: Enclosure
- Length: 90 mm
- Dimensions: 90 x 106.2 x 31.9 mm
- Width: 106.2 mm
- Height: 32 mm
- Colour: Light Grey

**1947485** Solid Top**RS PRO SOLID TOP ENCLOSURE TYPE, 17.5 X 90 X 58MM, POLYCARBONATE**Pack size: **1 x EA**

- Enclosure Type: Solid Top
- Body Material: Polycarbonate
- DIN Rail Type: Enclosure Base
- Length: 17.5 mm
- Dimensions: 17.5 x 90 x 58 mm
- Width: 90 mm
- Height: 58 mm
- Maximum Terminals: 2

**1947575** Solid Top**RS PRO OPEN TOP ENCLOSURE TYPE, 17.5 X 90 X 58MM, POLYCARBONATE**Pack size: **1 x EA**

- Enclosure Type: Open Top
- Body Material: Polycarbonate
- DIN Rail Type: Enclosure Base
- Length: 17.5 mm
- Dimensions: 17.5 x 90 x 58 mm
- Width: 90 mm
- Height: 58 mm
- Maximum Terminals: 2

**1947577** Open Top**RS PRO OPEN TOP ENCLOSURE TYPE, 36 X 90 X 58MM, POLYCARBONATE**Pack size: **1 x EA**

- Enclosure Type: Open Top
- Body Material: Polycarbonate
- DIN Rail Type: Enclosure Base
- Length: 36 mm
- Dimensions: 36 x 90 x 58 mm
- Width: 90 mm
- Height: 58 mm
- Maximum Terminals: 2

**1947578** Open Top**RS PRO SOLID TOP ENCLOSURE TYPE, 36 X 90 X 58MM, POLYCARBONATE**Pack size: **1 x EA**

- Enclosure Type: Solid Top
- Body Material: Polycarbonate
- DIN Rail Type: Enclosure Base
- Length: 36 mm
- Dimensions: 36 x 90 x 58 mm
- Width: 90 mm
- Height: 58 mm
- Maximum Terminals: 2

**1947579** Solid Top**RS PRO OPEN TOP, VENTED SIDES ENCLOSURE TYPE, 36 X 90 X 58MM,**Pack size: **1 x EA**

- Enclosure Type: Open Top, Vented Sides
- Body Material: Polycarbonate
- DIN Rail Type: Enclosure Base
- Length: 36 mm
- Dimensions: 36 x 90 x 58 mm
- Width: 90 mm
- Height: 58 mm
- Maximum Terminals: 2

**1947580** Open Top,**RS PRO EXTENDED WALLS/SIDES ENCLOSURE TYPE, 36 X 90 X 58MM,**Pack size: **1 x EA**

- Enclosure Type: Extended Walls/Sides
- Body Material: Polycarbonate
- DIN Rail Type: Enclosure Base
- Length: 36 mm
- Dimensions: 36 x 90 x 58 mm
- Width: 90 mm
- Height: 58 mm
- Maximum Terminals: 2

**1947581** Extended**RS PRO SOLID TOP ENCLOSURE TYPE, 53.4 X 90 X 58MM, POLYCARBONATE**Pack size: **1 x EA**

- Enclosure Type: Solid Top
- Body Material: Polycarbonate
- DIN Rail Type: Enclosure Base
- Length: 53.4 mm
- Dimensions: 53.4 x 90 x 58 mm
- Width: 90 mm
- Height: 58 mm
- Maximum Terminals: 2

**1947584** Solid Top**RS PRO OPEN TOP, VENTED SIDES ENCLOSURE TYPE, 53.4 X 90 X 58MM,**Pack size: **1 x EA**

- Enclosure Type: Open Top, Vented Sides
- Body Material: Polycarbonate
- DIN Rail Type: Enclosure Base
- Length: 53.4 mm
- Dimensions: 53.4 x 90 x 58 mm
- Width: 90 mm
- Height: 58 mm
- Maximum Terminals: 2

**1947585** Open Top,**RS PRO OPEN TOP ENCLOSURE TYPE, 106.2 X 90 X 58MM, POLYCARBONATE**Pack size: **1 x EA**

- Enclosure Type: Open Top
- Body Material: Polycarbonate
- DIN Rail Type: Enclosure Base
- Length: 106.2 mm
- Dimensions: 106.2 x 90 x 58 mm
- Width: 90 mm
- Height: 58 mm
- Maximum Terminals: 4

**1947592** Open Top**RS PRO SOLID TOP ENCLOSURE TYPE, 106.2 X 90 X 58MM, POLYCARBONATE**Pack size: **1 x EA**

- Enclosure Type: Solid Top
- Body Material: Polycarbonate
- DIN Rail Type: Enclosure Base
- Length: 106.2 mm
- Dimensions: 106.2 x 90 x 58 mm
- Width: 90 mm
- Height: 58 mm
- Maximum Terminals: 4

**1947594** Solid Top**RS PRO EXTENDED WALLS SIDES, OPEN TOP ENCLOSURE TYPE, 106.2 X**Pack size: **1 x EA**

- Enclosure Type: Extended Walls Sides, Open Top
- Body Material: Polycarbonate
- DIN Rail Type: Enclosure Base
- Length: 106.2 mm
- Dimensions: 106.2 x 90 x 58 mm
- Width: 90 mm
- Height: 58 mm
- Maximum Terminals: 4

**1947595** Extended Walls**RS PRO SOLID TOP ENCLOSURE TYPE, 159.2 X 90 X 58MM, POLYCARBONATE**Pack size: **1 x EA**

- Enclosure Type: Solid Top
- Body Material: Polycarbonate
- DIN Rail Type: Enclosure Base
- Length: 159.2 mm
- Dimensions: 159.2 x 90 x 58 mm
- Width: 90 mm
- Height: 58 mm
- Maximum Terminals: 6

**1947596** Solid Top

RS PRO OPEN TOP, VENTED SIDES ENCLOSURE TYPE, 159.2 X 90 X

Pack size: **1 x EA**

- Enclosure Type: Open Top, Vented Sides
- Body Material: Polycarbonate
- DIN Rail Type: Enclosure Base
- Length: 159.2 mm
- Dimensions: 159.2 x 90 x 58 mm
- Width: 90 mm
- Height: 58 mm
- Maximum Terminals: 6



1947597 Open Top,

RS PRO EXTENDED WALLS SIDES, OPEN TOP ENCLOSURE TYPE, 159.2 X

Pack size: **1 x EA**

- Enclosure Type: Extended Walls Sides, Open Top
- Body Material: Polycarbonate
- DIN Rail Type: Enclosure Base
- Length: 159.2 mm
- Dimensions: 159.2 x 90 x 58 mm
- Width: 90 mm
- Height: 58 mm
- Maximum Terminals: 6



1947598 Extended Walls

RS PRO OPEN TOP, VENTED SIDES ENCLOSURE TYPE, 212.1 X 90 X 58MM,

Pack size: **1 x EA**

- Enclosure Type: Open Top, Vented Sides
- Body Material: Polycarbonate
- DIN Rail Type: Enclosure Base
- Length: 212.1 mm
- Dimensions: 212.1 x 90 x 58 mm
- Width: 90 mm
- Height: 58 mm
- Maximum Terminals: 8



1947599 Open Top,

RS PRO DIN RAIL ENCLOSURE ENCLOSURE TYPE, 22.5 X 82 X 90MM,

Pack size: **1 x EA**

- Enclosure Type: DIN Rail Enclosure
- Body Material: Polyamide
- DIN Rail Type: Enclosure
- Length: 22.5 mm
- Dimensions: 22.5 x 82 x 90 mm
- Width: 82 mm
- Height: 90 mm
- Maximum Terminals: 12



1959128 DIN Rail

RS PRO DIN RAIL ENCLOSURE ENCLOSURE TYPE, 75 X 22.5 X

Pack size: **1 x EA**

- Enclosure Type: DIN Rail
- Body Material: Polycarbonate
- DIN Rail Type: Top Hat
- Length: 75 mm
- Dimensions: 75 x 22.5 x 98.5 mm
- Width: 22.5 mm
- Height: 98.5 mm
- Maximum Terminals: 12



2433632 DIN Rail

RS PRO DIN RAIL ENCLOSURE ENCLOSURE TYPE, 75 X 55 X 110MM,

Pack size: **1 x EA**

- Enclosure Type: DIN Rail
- Body Material: Polycarbonate
- DIN Rail Type: Top Hat
- Length: 75 mm
- Dimensions: 75 x 55 x 110 mm
- Width: 55 mm
- Height: 110 mm
- Maximum Terminals: 16



2433654 DIN Rail

RS PRO MODULAR ENCLOSURE ENCLOSURE TYPE, 75 X 99.7 X 110MM,

Pack size: **1 x EA**

- Enclosure Type: DIN Rail
- Body Material: Polycarbonate
- DIN Rail Type: Top Hat
- Length: 75 mm
- Dimensions: 75 x 99.7 x 110 mm
- Width: 99.7 mm
- Height: 110 mm
- Maximum Terminals: 30



2433660 DIN Rail

ENCLOSURE, IP55

Pack size: **1 x EA**

- Length: 95.5 mm
- Dimensions: 95.5 x 80 x 135 mm
- Width: 80 mm
- Height: 135 mm
- Maximum Terminals: 1
- Colour: White
- Series: XL-2000-01
- Enclosure Rating: IP41, IP55



3313731 95.5 mm

RS PRO STEEL SLOTTED DIN RAIL, MINI TOP HAT COMPATIBLE, 1M X 15MM X

Pack size: **5 x EA**

- Compatibility: Mini Top Hat
- Length: 1 m
- Width: 15 mm
- Height: 5.5 mm
- DIN Rail Type: Slotted
- Material: Steel



467349 Mini Top Hat

RS PRO STEEL SLOTTED DIN RAIL, G COMPATIBLE, 500MM X 32MM X

Pack size: **1 x EA**

- Compatibility: G
- Length: 500 mm
- Width: 32 mm
- Height: 15 mm
- DIN Rail Type: Slotted
- Material: Steel



467355 G

RS PRO STEEL UNSLOTTED DIN RAIL, G COMPATIBLE, 500MM X 32MM X

Pack size: **1 x EA**

- Compatibility: G
- Length: 500 mm
- Width: 32 mm
- Height: 15 mm
- DIN Rail Type: Unslotted
- Material: Steel



467359 G

RS PRO, UNSLOTTED DIN RAIL, 1M X 32MM X 15MM

Pack size: **5 x EA**

- Compatibility: G
- Length: 1 m
- Width: 32 mm
- Height: 15 mm
- DIN Rail Type: Unslotted
- Material: Steel

SORRY,
IMAGE NOT
AVAILABLE.

467365 G

RS PRO STEEL SLOTTED DIN RAIL, G COMPATIBLE, 1M X 32MM X 15MM

Pack size: **5 x EA**

- Compatibility: G
- Length: 1 m
- Width: 32 mm
- Height: 15 mm
- DIN Rail Type: Slotted
- Material: Steel



467393 G

RS PRO STEEL UNSLOTTED DIN RAIL, TOP HAT COMPATIBLE, 1M X 35MM X

Pack size: **4 x EA**

- Compatibility: Top Hat
- Length: 1 m
- Width: 35 mm
- Height: 7.5 mm
- DIN Rail Type: Unslotted
- Material: Steel



467399 Top Hat

RS PRO STEEL SLOTTED DIN RAIL, TOP HAT COMPATIBLE, 500MM X 35MM X

Pack size: **1 x EA**

- Compatibility: Top Hat
- Length: 500 mm
- Width: 35 mm
- Height: 7.5 mm
- DIN Rail Type: Slotted
- Material: Steel




467406 Top Hat

RS PRO STEEL UNSLOTTED DIN RAIL, DEEP TOP HAT COMPATIBLE, 1M X

Pack size: **4 x EA**

- Compatibility: Deep Top Hat
- Length: 1 m
- Width: 35 mm
- Height: 15 mm
- DIN Rail Type: Unslotted
- Material: Steel



467412 Deep Top Hat

RS PRO STEEL SLOTTED DIN RAIL, TOP HAT COMPATIBLE, 1M X 35MM XPack size: **4 x EA**

- Compatibility: Top Hat
- Length: 1 m
- Width: 35 mm
- Height: 7.5 mm
- DIN Rail Type: Slotted
- Material: Steel

**467416** Top Hat**RS PRO STEEL SLOTTED DIN RAIL, DEEP TOP HAT COMPATIBLE, 1M X**Pack size: **4 x EA**

- Compatibility: Deep Top Hat
- Length: 1 m
- Width: 35 mm
- Height: 15 mm
- DIN Rail Type: Slotted
- Material: Steel

**467428** Deep Top Hat**RS PRO STEEL SLOTTED DIN RAIL, DEEP TOP HAT COMPATIBLE, 500MM**Pack size: **4 x EA**

- Compatibility: Deep Top Hat
- Length: 500 mm
- Width: 35 mm
- Height: 15 mm
- DIN Rail Type: Slotted
- Material: Steel

**467438** Deep Top Hat**RS PRO DIN RAIL ENCLOSURE KIT**Pack size: **1 x EA**

- Accessory Type: Panel Screw Kit
- For Use With: DIN Rail

**606844** Panel Screw Kit**RS PRO STEEL UNSLOTTED DIN RAIL, TOP HAT COMPATIBLE, 225MM X**Pack size: **1 x EA**

- Compatibility: Top Hat
- Length: 225 mm
- Width: 35 mm
- Height: 7.5 mm
- DIN Rail Type: Unslotted
- Material: Steel

**1882207** Top Hat**RS PRO DIN RAIL, 90MM X 35MM X 7.5MM**Pack size: **1 x EA**

- Length: 90 mm
- Width: 35 mm
- Height: 7.5 mm

**2006726** 90 mm**RS PRO DIN RAIL, 122MM X 35MM X 7.5MM**Pack size: **1 x EA**

- Length: 122 mm
- Width: 35 mm
- Height: 7.5 mm

**2006728** 122 mm**RS PRO DIN RAIL, 135MM X 35MM X 7.5MM**Pack size: **1 x EA**

- Length: 135 mm
- Width: 35 mm
- Height: 7.5 mm

**2006730** 135 mm**RS PRO DIN RAIL, 163MM X 35MM X 7.5MM**Pack size: **1 x EA**

- Length: 163 mm
- Width: 35 mm
- Height: 7.5 mm

**2006731** 163 mm**RS PRO DIN RAIL, 196MM X 35MM X 7.5MM**Pack size: **1 x EA**

- Length: 196 mm
- Width: 35 mm
- Height: 7.5 mm

**2006732** 196 mm**RS PRO DIN RAIL, 218MM X 35MM X 7.5MM**Pack size: **1 x EA**

- Length: 218 mm
- Width: 35 mm
- Height: 7.5 mm

**2006733** 218 mm**RS PRO DIN RAIL, TOP HAT COMPATIBLE, 100MM X 35MM X**Pack size: **1 x EA**

- Compatibility: Top Hat
- Length: 100 mm
- Width: 35 mm
- Height: 7.5 mm

**2258317** Top Hat**RS PRO DIN RAIL, TOP HAT COMPATIBLE, 227MM X 35MM X**Pack size: **1 x EA**

- Compatibility: Top Hat
- Length: 227 mm
- Width: 35 mm
- Height: 7.5 mm

**2258320** Top Hat**RS PRO DIN RAIL, TOP HAT COMPATIBLE, 53MM X 35MM X**Pack size: **1 x EA**

- Compatibility: Top Hat
- Length: 53 mm
- Width: 35 mm
- Height: 7.5 mm

**2258321** Top Hat**RS PRO DIN RAIL, TOP HAT COMPATIBLE, 80MM X 35MM X**Pack size: **1 x EA**

- Compatibility: Top Hat
- Length: 80 mm
- Width: 35 mm
- Height: 7.5 mm

**2258322** Top Hat**RS PRO STEEL SLOTTED DIN RAIL, TOP HAT COMPATIBLE, 134MM X 35MM X**Pack size: **1 x EA**

- Compatibility: Top Hat
- Length: 134 mm
- Width: 35 mm
- Height: 8 mm
- DIN Rail Type: Slotted
- Material: Steel

**2382635** Top Hat

RS PRO STEEL UNSLOTTED DIN RAIL, TOP HAT COMPATIBLE, 156MM X

Pack size: **1 x EA**

- Compatibility: Top Hat
- Length: 156 mm
- Width: 35 mm
- Height: 8 mm
- DIN Rail Type: Unslotted
- Material: Steel



2382641 Top Hat

RS PRO UNPERFORATED DIN RAIL, 60MM X 35MM X 8MM

Pack size: **1 x EA**

- Length: 60 mm
- Width: 35 mm
- Height: 8 mm
- DIN Rail Type: Unperforated



2383966 60 mm

RS PRO STEEL UNSLOTTED DIN RAIL, TOP HAT COMPATIBLE, 500MM X

Pack size: **1 x EA**

- Compatibility: Top Hat
- Length: 500 mm
- Width: 35 mm
- Height: 7.5 mm
- DIN Rail Type: Unslotted
- Material: Steel



7424129 Top Hat

RS PRO SQUARE BRACKET FOR USE WITH TOP HAT DIN RAIL

Pack size: **10 x EA**

- Accessory Type: Square Bracket
- Series: TS
- For Use With: DIN Rail



467343 Square Bracket

RS PRO SQUARE BRACKET FOR USE WITH TOP HAT DIN RAIL

Pack size: **10 x EA**

- Accessory Type: Square Bracket
- Series: TS
- For Use With: DIN Rail



467361 Square Bracket

RS PRO SQUARE BRACKET FOR USE WITH TOP HAT DIN RAIL

Pack size: **10 x EA**

- Accessory Type: Square Bracket
- Series: TS
- For Use With: DIN Rail



467371 Square Bracket

RS PRO ANGLED BRACKET FOR USE WITH TOP HAT DIN RAIL

Pack size: **10 x EA**

- Accessory Type: Angled Bracket
- Series: TS
- For Use With: DIN Rail



467377 Angled Bracket

RS PRO SQUARE BRACKET FOR USE WITH TOP HAT DIN RAIL

Pack size: **10 x EA**

- Accessory Type: Square Bracket
- Series: TS
- For Use With: DIN Rail



467383 Square Bracket

RS PRO ANGLED BRACKET FOR USE WITH TOP HAT DIN RAIL

Pack size: **10 x EA**

- Accessory Type: Angled Bracket
- Series: TS
- For Use With: DIN Rail



467387 Angled Bracket

RS PRO ANGLED BRACKET FOR USE WITH DIN RAIL

Pack size: **10 x EA**

- Accessory Type: Angled Bracket
- For Use With: DIN Rail



606850 Angled Bracket

RS PRO ANGLED BRACKET FOR USE WITH DIN RAIL

Pack size: **10 x EA**

- Accessory Type: Angled Bracket
- For Use With: DIN Rail



606866 Angled Bracket

RS PRO MOUNTING KIT FOR USE WITH 72 MM WIDTH PCB8#146;S

Pack size: **1 x EA**

- Accessory Type: Mounting Kit
- For Use With: 72 mm width PCB8#146;s



1947609 Mounting Kit

DOCUMENT,POCKETS,SELF ADHESIVE,CLEAR PLASTIC,A4

Pack size: **5 x EA**

- Type: Document Pocket
- For Use With: A4 Portrait Paper
- Material: Acrylic
- Dimensions: 303 x 217 mm
- Colour: Transparent
- Quantity: 5



1966018 Document Pocket

RS PRO DOCUMENT WALLET

Pack size: **5 x EA**

- Type: Document Pocket
- For Use With: A5 Landscape Paper
- Material: Acrylic
- Dimensions: 216 x 155 mm
- Colour: Transparent
- Quantity: 5



1966024 Document Pocket

GROMMET,EDGING STRIP,PANELS 1.2 ÔÅ 16MM,5M

Pack size: **5 x MTR**

- Product Type: Edge Protection
- Material: Polyethylene



406922 Edge Protection

GROMMET,STRIP,PANELS 2.5-3.2MM,25M

Pack size: **25 x MTR**

- Product Type: Edge Protection
- Material: Polyethylene



429690 Edge Protection

RS PRO EARTHING STRAP

Pack size: **1 x EA**

- Type: Earthing Strap
- Length: 220 mm
- For Use With: Steel Enclosure

**7467384** Earthing Strap

ENCLOSURE, 19IN, RACK, LABORATORY, KIT, EARTHING

Pack size: **1 x EA**

- Type: Earthing Kit
- For Use With: Frame

**528983** Earthing Kit

RS PRO WALL MOUNT FOR USE WITH INLINE TERMINAL ENCLOSURE

Pack size: **1 x PR**

- Enclosure Mounting Type: Mounting Bracket
- Material: Steel
- For Use With: Inline Terminal Enclosure

**122074** Mounting Bracket

RS PRO GALVANISED STEEL MOUNTING PLATE FOR USE WITH RS

Pack size: **1 x EA**

- Length: 126 mm
- Enclosure Mounting Type: Mounting Plate
- Width: 196 mm
- Dimensions: 126 x 196 x 1.5 mm
- Height: 2 mm
- Material: Galvanised Steel
- For Use With: RS PRO 1920695 Hermetic Enclosure

**1920707** 126 mm

RS PRO GALVANISED STEEL MOUNTING PLATE FOR USE WITH RS

Pack size: **1 x EA**

- Length: 176 mm
- Enclosure Mounting Type: Mounting Plate
- Width: 266.4 mm
- Dimensions: 176 x 266.4 x 1.5 mm
- Height: 2 mm
- Material: Galvanised Steel
- For Use With: RS PRO 1862265 and RS PRO 1862266 Hermetic Enclosures

**1920738** 176 mm

RS PRO ABS MOUNTING KIT FOR USE WITH RS PRO 7710 SERIES

Pack size: **1 x EA**

- Enclosure Mounting Type: Mounting Kit
- Colour: Grey
- Material: ABS
- Series: 7700
- For Use With: RS PRO 7710 Series

**1947496** Mounting Kit

RS PRO MOUNTING KIT

Pack size: **1 x EA**

- Enclosure Mounting Type: Mounting Bracket
- Material: Steel

**7467387** Mounting Bracket

RS PRO STAINLESS STEEL MOUNTING PLATE FOR USE WITH SBOX 3.4-200

Pack size: **1 x EA**

- Length: 198 mm
- Enclosure Mounting Type: Mounting Plate
- Width: 250 mm
- Dimensions: 248 x 198 mm
- Height: 248 mm
- Material: Stainless Steel
- For Use With: SBOX 3.4-200 V2, SBOX 5.5-200 V2, SBOX 6.6-200 V2

**7587163** 198 mm

RS PRO STEEL MOUNTING PLATE FOR USE WITH 200 X 300 ENCLOSURE, 248

Pack size: **1 x EA**

- Length: 148 mm
- Enclosure Mounting Type: Mounting Plate
- Dimensions: 248 x 148 mm
- Height: 248 mm
- Material: Steel
- For Use With: 200 x 300 Enclosure

**7587166** 148 mm

RS PRO STEEL MOUNTING PLATE FOR USE WITH 400 X 300 ENCLOSURE, 248

Pack size: **1 x EA**

- Length: 348 mm
- Enclosure Mounting Type: Mounting Plate
- Dimensions: 248 x 348 mm
- Height: 248 mm
- Material: Steel
- For Use With: 400 x 300 Enclosure

**7587175** 348 mm

RS PRO STEEL MOUNTING PLATE FOR USE WITH 500 X 600 ENCLOSURE,

Pack size: **1 x EA**

- Length: 448 mm
- Enclosure Mounting Type: Mounting Plate
- Dimensions: 548 x 448 mm
- Height: 548 mm
- Material: Steel
- For Use With: 500 x 600 Enclosure

**7587179** 448 mm

RS PRO STEEL MOUNTING PLATE FOR USE WITH 300 X 400 ENCLOSURE, 348

Pack size: **1 x EA**

- Length: 248 mm
- Enclosure Mounting Type: Mounting Plate
- Dimensions: 348 x 248 mm
- Height: 348 mm
- Material: Steel
- For Use With: 300 x 400 Enclosure

**7587181** 248 mm

RS PRO STEEL MOUNTING PLATE FOR USE WITH 400 X 400 ENCLOSURE, 348

Pack size: **1 x EA**

- Length: 348 mm
- Enclosure Mounting Type: Mounting Plate
- Dimensions: 348 x 348 mm
- Height: 348 mm
- Material: Steel
- For Use With: 400 x 400 Enclosure

**7587185** 348 mm

RS PRO STEEL MOUNTING BRACKET FOR USE WITH WALL BOX

Pack size: **1 x EA**

- Enclosure Mounting Type: Mounting Bracket
- Height: 4 mm
- Material: Steel
- For Use With: Wall Box

**8428471** Mounting Bracket

RS PRO STEEL MOUNTING BRACKET FOR USE WITH WALL BOX

Pack size: **1 x EA**

- Enclosure Mounting Type: Mounting Bracket
- Height: 4 mm
- Material: Steel
- For Use With: Wall Box

**8428475** Mounting Bracket

RS PRO ABS HANDLE FOR USE WITH ABS DESK CASE

Pack size: **1 x EA**

- Type: Handle
- For Use With: ABS Desk Case
- Material: ABS

**504798** Handle

RS PRO SLOTTED SCREW FOR USE WITH KM6 PANEL M2.5 X , 100 PACK

Pack size: **100 x EA**

- Type: Slotted Screw
- For Use With: KM6 Panel
- Thread Size: M2.5
- Quantity: 100



543116 Slotted Screw

RS PRO METAL METAL BUSH FOR USE WITH EURO-CARDS FITTED WITH 2-

Pack size: **100 x EA**

- Type: Metal Bush
- For Use With: Euro-cards fitted with 2-part indirect edge connectors to DIN41612
- Material: Metal
- Colour: Grey



543190 Metal Bush

SPACER,HEXAGONAL,ZINC PLATED STEEL,M6X10MM

Pack size: **10 x EA**

- Type: Spacer
- Length: 10 mm
- For Use With: Any Enclosure
- Material: Steel
- Thread Size: M6



603485 Spacer

SPACER,HEXAGONAL,ZINC PLATED STEEL,M6X12MM

Pack size: **10 x EA**

- Type: Spacer
- Length: 12 mm
- For Use With: Any Enclosure
- Material: Steel
- Thread Size: M6



603491 Spacer

SPACER,HEXAGONAL,ZINC PLATED STEEL,M6X14MM

Pack size: **10 x EA**

- Type: Spacer
- Length: 14 mm
- For Use With: Any Enclosure
- Material: Steel
- Thread Size: M6



603508 Spacer

RS PRO STEEL SPACER FOR USE WITH ANY ENCLOSURE

Pack size: **10 x EA**

- Type: Spacer
- Length: 16 mm
- For Use With: Any Enclosure
- Material: Steel
- Thread Size: M6



603514 Spacer

SPACER,HEXAGONAL,ZINC PLATED STEEL,M6X18MM

Pack size: **10 x EA**

- Type: Spacer
- Length: 18 mm
- For Use With: Any Enclosure
- Material: Steel
- Thread Size: M6



603520 Spacer

SPACER,HEXAGONAL,ZINC PLATED STEEL,M6X20MM

Pack size: **10 x EA**

- Type: Spacer
- Length: 20 mm
- For Use With: Any Enclosure
- Material: Steel
- Thread Size: M6



603536 Spacer

SPACER,HEXAGONAL,ZINC PLATED STEEL,FEMALE,M6X20MM

Pack size: **10 x EA**

- Type: Spacer
- Length: 20 mm
- For Use With: Any Enclosure
- Material: Steel
- Thread Size: M6



603542 Spacer

RS PRO POLYCARBONATE DRAINING PLUG FOR USE WITH PANEL

Pack size: **1 x EA**

- Type: Draining Plug
- For Use With: Panel
- Material: Polycarbonate
- Colour: Black



838827 Draining Plug

RS PRO RUBBER FEET FOR USE WITH EXTRUDED ALUMINIUM ENCLOSURES,

Pack size: **1 x EA**

- Type: Feet
- For Use With: Extruded Aluminium Enclosures
- Width: 16 mm
- Material: Rubber
- Dimensions: 16 x 10 mm
- Height: 10 mm
- Colour: Black



1368970 Feet

RS PRO LOCK FOR USE WITH RS PRO GRP WALL BOXES, 17 X 39.6 X

Pack size: **1 x EA**

- Type: Lock
- Length: 17 mm
- For Use With: RS PRO GRP Wall Boxes
- Width: 39.6 mm
- Dimensions: 17 x 39.6 x 40.2 mm
- Height: 40 mm
- Colour: Black



1927131 Lock

KEY ONLY FOR STANDARD ATLAS-CDB-10 LOCK

Pack size: **1 x EA**

- Type: Key
- For Use With: RS PRO Quarter Turn Lock
- Colour: Black



1927135 Key

RS PRO AIR VENT FOR USE WITH RS PRO GRP WALL BOXES, 68 X 50 X

Pack size: **1 x EA**

- Type: Air Vent
- Length: 68 mm
- For Use With: RS PRO GRP Wall Boxes
- Width: 50 mm
- Dimensions: 68 x 50 x 15.8 mm
- Height: 16 mm
- Colour: White
- IP Rating: IP54



1927136 Air Vent

RS PRO AIR VENT FOR USE WITH RS PRO GRP WALL BOXES, 25.75 X 28.45

Pack size: **1 x EA**

- Type: Air Vent
- Length: 26 mm
- For Use With: RS PRO GRP Wall Boxes
- Width: 28.45 mm
- Dimensions: 25.75 x 28.45 x 21.88 mm
- Height: 22 mm
- Colour: White
- IP Rating: IP54



1927137 Air Vent

RS PRO ABS HINGE FOR USE WITH HERMETIC ENCLOSURE, 29 X 20 X

Pack size: **1 x EA**

- Type: Hinge
- Length: 29 mm
- For Use With: Hermetic Enclosure
- Width: 20 mm
- Material: ABS
- Dimensions: 29 x 20 x 19.2 mm
- Height: 19 mm
- Colour: Grey



2006744 Hinge

**RS PRO STEEL TAMPERPROOF SCREW
FOR USE WITH SEALED DIN TYPE**Pack size: **12 x EA**

- Type: Tamperproof Screw
- Length: 15 mm
- For Use With: Sealed DIN Type Enclosure
- Material: Steel
- Dimensions: M5 x 15 mm, M5 x 15 mm

**2826589** Tamperproof**KEY LOCK KIT**Pack size: **1 x EA**

- Type: Compression Latch
- Length: 50 mm
- For Use With: Steel Enclosure
- Width: 49 mm
- Material: Metal, Plastic
- Dimensions: 50 x 49 x 51 mm
- Height: 51 mm
- Colour: Black

**7467380** Compression**RS PRO STEEL POLE MOUNTING KIT
FOR USE WITH WALL BOX, 140 →**Pack size: **1 x EA**

- Type: Pole Mounting Kit
- For Use With: Wall Box
- Material: Steel
- Dimensions: 140 → 260 mm

**8428484** Pole Mounting Kit**BREATHER, IMMERSION PROOF**Pack size: **1 x EA**

- Filter Type: Constant Pressure Equalization
- Mounting Hole Diameter: M16 x 1
- Automatic or Manual: Manual Override

**838805** Constant**RS PRO GREY STEEL ENCLOSURE,
FLANGED, GREY LID, 182 X 257 X**Pack size: **1 x EA**

- Body Material: Steel
- External Length: 182 mm
- External Height: 271 mm
- External Width: 257 mm
- External Dimensions: 182 x 257 x 271 mm
- Colour: Grey
- Lid Colour: Grey
- Flanged: Yes

**232046** Steel**RS PRO GREY STEEL ENCLOSURE,
FLANGED, GREY LID, 182 X 192 X**Pack size: **1 x EA**

- Body Material: Steel
- External Length: 182 mm
- External Height: 246 mm
- External Width: 192 mm
- External Dimensions: 182 x 192 x 246 mm
- Colour: Grey
- Lid Colour: Grey
- Flanged: Yes

**232169** Steel**RS PRO GREY STEEL ENCLOSURE,
FLANGED, GREY LID, 157 X 157 X**Pack size: **1 x EA**

- Body Material: Steel
- External Length: 157 mm
- External Height: 221 mm
- External Width: 157 mm
- External Dimensions: 157 x 157 x 221 mm
- Colour: Grey
- Lid Colour: Grey
- Flanged: Yes

**232175** Steel**RS PRO GREY STEEL ENCLOSURE,
FLANGED, GREY LID, 117 X 132 X**Pack size: **1 x EA**

- Body Material: Steel
- External Length: 117 mm
- External Height: 196 mm
- External Width: 132 mm
- External Dimensions: 117 x 132 x 196 mm
- Colour: Grey
- Lid Colour: Grey
- Flanged: Yes

**232181** Steel**RS PRO GREY FIBREGLASS
ENCLOSURE, IP67, GREY LID, 300 X**Pack size: **1 x EA**

- Body Material: Fibreglass
- External Length: 300 mm
- External Height: 175 mm
- External Width: 370 mm
- External Dimensions: 300 x 370 x 175 mm
- IP Rating: IP67
- Colour: Grey
- Lid Colour: Grey

**501480** Fibreglass**RS PRO GREY FIBREGLASS
ENCLOSURE, IP66, TRANSPARENT LID,**Pack size: **1 x EA**

- Body Material: Fibreglass
- External Length: 372 mm
- External Height: 175 mm
- External Width: 302 mm
- External Dimensions: 372 x 175 x 302 mm
- IP Rating: IP66
- Colour: Grey
- Lid Colour: Transparent

**501496** Fibreglass**RS PRO GREY FIBREGLASS
ENCLOSURE, IP66, TRANSPARENT LID,**Pack size: **1 x EA**

- Body Material: Fibreglass
- External Length: 185 mm
- External Height: 150 mm
- External Width: 130 mm
- External Dimensions: 185 x 130 x 150 mm
- IP Rating: IP66
- Colour: Grey
- Lid Colour: Transparent

**507977** Fibreglass**RS PRO GREY FIBREGLASS
ENCLOSURE, IP67, GREY LID, 300 X**Pack size: **1 x EA**

- Body Material: Fibreglass
- External Length: 300 mm
- External Height: 175 mm
- External Width: 300 mm
- External Dimensions: 300 x 300 x 175 mm
- IP Rating: IP67
- Colour: Grey
- Lid Colour: Grey

**507999** Fibreglass**RS PRO GREY FIBREGLASS
ENCLOSURE, IP67, GREY LID, 185 X**Pack size: **1 x EA**

- Body Material: Fibreglass
- External Length: 185 mm
- External Height: 175 mm
- External Width: 300 mm
- External Dimensions: 185 x 300 x 175 mm
- IP Rating: IP67
- Colour: Grey
- Lid Colour: Grey

**508009** Fibreglass**RS PRO GREY POLYESTER
ENCLOSURE, IP67, GREY LID, 150 X**Pack size: **1 x EA**

- Body Material: Polyester
- External Length: 150 mm
- External Height: 130 mm
- External Width: 185 mm
- External Dimensions: 150 x 185 x 130 mm
- IP Rating: IP67
- Colour: Grey
- Lid Colour: Grey

**508015** Polyester**RS PRO GREY FIBREGLASS
ENCLOSURE, IP66, TRANSPARENT LID,**Pack size: **1 x EA**

- Body Material: Fibreglass
- External Length: 300 mm
- External Height: 300 mm
- External Width: 175 mm
- External Dimensions: 300 x 175 x 300 mm
- IP Rating: IP66
- Colour: Grey
- Lid Colour: Transparent

**508324** Fibreglass**RS PRO GREY FIBREGLASS
ENCLOSURE, IP66, TRANSPARENT LID,**Pack size: **1 x EA**

- Body Material: Fibreglass
- External Length: 300 mm
- External Height: 185 mm
- External Width: 175 mm
- External Dimensions: 300 x 175 x 185 mm
- IP Rating: IP66
- Colour: Grey
- Lid Colour: Transparent

**508330** Fibreglass

RS PRO ALUMINIUM ENCLOSURE, IP66, GREY LID, 81 X 100 X 100MM

Pack size: **1 x EA**

- Body Material: Aluminium
- External Length: 100 mm
- External Height: 81 mm
- External Width: 100 mm
- External Dimensions: 81 x 100 x 100 mm
- IP Rating: IP66
- Lid Colour: Grey
- Flanged: No



1228916 Aluminium

RS PRO ALUMINIUM ENCLOSURE, IP65, IP66, IP67, IP68, GREY LID, 34 X

Pack size: **1 x EA**

- Body Material: Aluminium
- External Length: 58 mm
- External Height: 34 mm
- External Width: 58 mm
- External Dimensions: 34 x 58 x 64 mm
- IP Rating: IP65, IP66, IP67, IP68
- Lid Colour: Grey
- Flanged: No



1228917 Aluminium

RS PRO GREY ALUMINIUM ENCLOSURE, IP65, IP66, IP67, IP68,

Pack size: **1 x EA**

- Body Material: Aluminium
- External Length: 75 mm
- External Height: 57 mm
- External Width: 75 mm
- External Dimensions: 57 x 75 x 80 mm
- IP Rating: IP65, IP66, IP67, IP68
- Colour: Grey
- Lid Colour: Grey



1228919 Aluminium

RS PRO ALUMINIUM ENCLOSURE, IP66, GREY LID, 180 X 330 X 230MM

Pack size: **1 x EA**

- Body Material: Aluminium
- External Length: 330 mm
- External Height: 180 mm
- External Width: 330 mm
- External Dimensions: 180 x 330 x 230 mm
- IP Rating: IP66
- Lid Colour: Grey
- Flanged: No



1228921 Aluminium

RS PRO ALUMINIUM ENCLOSURE, IP66, GREY LID, 57 X 125 X 80MM

Pack size: **1 x EA**

- Body Material: Aluminium
- External Length: 125 mm
- External Height: 57 mm
- External Width: 125 mm
- External Dimensions: 57 x 125 x 80 mm
- IP Rating: IP66
- Lid Colour: Grey
- Flanged: No



1228931 Aluminium

RS PRO ALUMINIUM ENCLOSURE, IP66, GREY LID, 160 X 100 X 81MM

Pack size: **1 x EA**

- Body Material: Aluminium
- External Length: 160 mm
- External Height: 81 mm
- External Width: 100 mm
- External Dimensions: 160 x 100 x 81 mm
- IP Rating: IP66
- Lid Colour: Grey
- Flanged: No



1228934 Aluminium

RS PRO ALUMINIUM ENCLOSURE, IP66, GREY LID, 81 X 122 X 120MM

Pack size: **1 x EA**

- Body Material: Aluminium
- External Length: 122 mm
- External Height: 81 mm
- External Width: 122 mm
- External Dimensions: 81 x 122 x 120 mm
- IP Rating: IP66
- Lid Colour: Grey
- Flanged: No



1228935 Aluminium

RS PRO GREY ALUMINIUM ENCLOSURE, IP65, IP66, IP67, IP68,

Pack size: **1 x EA**

- Body Material: Aluminium
- External Length: 122 mm
- External Height: 91 mm
- External Width: 122 mm
- External Dimensions: 91 x 122 x 120 mm
- IP Rating: IP65, IP66, IP67, IP68
- Colour: Grey
- Lid Colour: Grey



1228920 Aluminium

RS PRO ALUMINIUM ENCLOSURE, IP65, IP66, IP67, IP68, GREY LID, 111 X

Pack size: **1 x EA**

- Body Material: Aluminium
- External Length: 330 mm
- External Height: 111 mm
- External Width: 330 mm
- External Dimensions: 111 x 330 x 230 mm
- IP Rating: IP65, IP66, IP67, IP68
- Lid Colour: Grey
- Flanged: No



1228923 Aluminium

RS PRO ALUMINIUM ENCLOSURE, IP65, IP66, IP67, IP68, GREY LID, 91 X

Pack size: **1 x EA**

- Body Material: Aluminium
- External Length: 160 mm
- External Height: 91 mm
- External Width: 160 mm
- External Dimensions: 91 x 160 x 160 mm
- IP Rating: IP65, IP66, IP67, IP68
- Lid Colour: Grey
- Flanged: No



1228926 Aluminium

RS PRO ALUMINIUM ENCLOSURE, IP65, IP66, IP67, IP68, GREY LID, 113 X

Pack size: **1 x EA**

- Body Material: Aluminium
- External Length: 230 mm
- External Height: 113 mm
- External Width: 230 mm
- External Dimensions: 113 x 230 x 200 mm
- IP Rating: IP65, IP66, IP67, IP68
- Lid Colour: Grey
- Flanged: No



1228927 Aluminium

RS PRO ALUMINIUM ENCLOSURE, IP65, IP66, IP67, IP68, GREY LID, 81 X

Pack size: **1 x EA**

- Body Material: Aluminium
- External Length: 220 mm
- External Height: 81 mm
- External Width: 220 mm
- External Dimensions: 81 x 220 x 120 mm
- IP Rating: IP65, IP66, IP67, IP68
- Lid Colour: Grey
- Flanged: No



1228928 Aluminium

RS PRO ALUMINIUM ENCLOSURE, IP65, IP66, IP67, IP68, GREY LID, 90 X

Pack size: **1 x EA**

- Body Material: Aluminium
- External Length: 360 mm
- External Height: 90 mm
- External Width: 360 mm
- External Dimensions: 90 x 360 x 160 mm
- IP Rating: IP65, IP66, IP67, IP68
- Lid Colour: Grey
- Flanged: No



1228929 Aluminium

RS PRO GREY ALUMINIUM ENCLOSURE, IP65, IP66, IP67, IP68,

Pack size: **1 x EA**

- Body Material: Aluminium
- External Length: 260 mm
- External Height: 90 mm
- External Width: 260 mm
- External Dimensions: 90 x 260 x 160 mm
- IP Rating: IP65, IP66, IP67, IP68
- Colour: Grey
- Lid Colour: Grey



1228930 Aluminium

RS PRO ALUMINIUM ENCLOSURE, IP65, IP66, IP67, IP68, GREY LID, 110 X

Pack size: **1 x EA**

- Body Material: Aluminium
- External Length: 280 mm
- External Height: 110 mm
- External Width: 280 mm
- External Dimensions: 110 x 280 x 230 mm
- IP Rating: IP65, IP66, IP67, IP68
- Lid Colour: Grey
- Flanged: No



1228932 Aluminium

RS PRO ALUMINIUM ENCLOSURE, IP66, GREY LID, 81 X 220 X 120MM

Pack size: **1 x EA**

- Body Material: Aluminium
- External Length: 220 mm
- External Height: 81 mm
- External Width: 220 mm
- External Dimensions: 81 x 220 x 120 mm
- IP Rating: IP66
- Lid Colour: Grey
- Flanged: No



1228933 Aluminium

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, GREY LID, 50.8 X 50.8 XPack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 50.8 mm
- External Height: 31.8 mm
- External Width: 50.8 mm
- External Dimensions: 50.8 x 50.8 x 31.8 mm
- Colour: Grey
- Lid Colour: Grey

**1465294** Die Cast**RS PRO BLACK DIE CAST ALUMINIUM ENCLOSURE, BLACK LID, 110 X 60 X**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 110 mm
- External Height: 54 mm
- External Width: 60 mm
- External Dimensions: 110 x 60 x 54 mm
- Colour: Black
- Lid Colour: Black

**1465333** Die Cast**RS PRO WHITE ABS ENCLOSURE, WHITE LID, 190 X 110 X 60MM**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 190 mm
- External Height: 60 mm
- External Width: 110 mm
- External Dimensions: 190 x 110 x 60 mm
- Colour: White
- Lid Colour: White

**1533202** ABS**RS PRO WHITE ABS ENCLOSURE, WHITE LID, 112 X 62 X 31MM**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 112 mm
- External Height: 31 mm
- External Width: 62 mm
- External Dimensions: 112 x 62 x 31 mm
- Colour: White
- Lid Colour: White

**1533203** ABS**RS PRO BLACK ABS ENCLOSURE, BLACK LID, 130 X 65 X 50.1MM**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 130 mm
- External Height: 50.1 mm
- External Width: 65 mm
- External Dimensions: 130 x 65 x 50.1 mm
- Colour: Black
- Lid Colour: Black

**1533204** ABS**RS PRO WHITE ABS ENCLOSURE, WHITE LID, 55 X 55 X 42MM**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 55 mm
- External Height: 42 mm
- External Width: 55 mm
- External Dimensions: 55 x 55 x 42 mm
- Colour: White
- Lid Colour: White

**1533208** ABS**RS PRO WHITE ABS ENCLOSURE, WHITE LID, 150 X 80 X 50MM**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 150 mm
- External Height: 50 mm
- External Width: 80 mm
- External Dimensions: 150 x 80 x 50 mm
- Colour: White
- Lid Colour: White

**1533211** ABS**RS PRO BLACK ABS ENCLOSURE, BLACK LID, 125 X 125 X 45MM**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 125 mm
- External Height: 45 mm
- External Width: 125 mm
- External Dimensions: 125 x 125 x 45 mm
- Colour: Black
- Lid Colour: Black

**1533671** ABS**RS PRO BLACK ABS ENCLOSURE, IP54, FLANGED, BLACK LID, 99.05 X**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 99.1 mm
- External Height: 28 mm
- External Width: 52.3 mm
- External Dimensions: 99.05 x 52.3 x 28 mm
- IP Rating: IP54
- Colour: Black
- Lid Colour: Black

**1533672** ABS**RS PRO BLACK ABS ENCLOSURE, IP65, FLANGED, BLACK LID, 108.2 X**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 108.2 mm
- External Height: 39.5 mm
- External Width: 58.2 mm
- External Dimensions: 108.2 x 58.2 x 39.5 mm
- IP Rating: IP65
- Colour: Black
- Lid Colour: Black

**1533674** ABS**RS PRO WHITE ABS ENCLOSURE, FLANGED, WHITE LID, 127 X 70.6 X**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 127 mm
- External Height: 50.5 mm
- External Width: 70.6 mm
- External Dimensions: 127 x 70.6 x 50.5 mm
- Colour: White
- Lid Colour: White
- Flanged: Yes

**1533677** ABS**RS PRO GREY ABS ENCLOSURE, IP65, FLANGED, GREY LID, 173.4 X 82.4 X**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 173.4 mm
- External Height: 50.5 mm
- External Width: 82.4 mm
- External Dimensions: 173.4 x 82.4 x 50.5 mm
- IP Rating: IP65
- Colour: Grey
- Lid Colour: Grey

**1533680** ABS**RS PRO BLACK ABS ENCLOSURE, BLACK LID, 100 X 50 X 25MM**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 100 mm
- External Height: 25 mm
- External Width: 50 mm
- External Dimensions: 100 x 50 x 25 mm
- Colour: Black
- Lid Colour: Black

**1533681** ABS**RS PRO GREY ABS ENCLOSURE, FLANGED, GREY LID, 127 X 70.6 X**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 127 mm
- External Height: 35.5 mm
- External Width: 70.6 mm
- External Dimensions: 127 x 70.6 x 35.5 mm
- Colour: Grey
- Lid Colour: Grey
- Flanged: Yes

**1533682** ABS**RS PRO BLACK ABS ENCLOSURE, IP54, FLANGED, BLACK LID, 210 X 112**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 210 mm
- External Height: 61 mm
- External Width: 112 mm
- External Dimensions: 210 x 112 x 61 mm
- IP Rating: IP54
- Colour: Black
- Lid Colour: Black

**1533684** ABS**RS PRO WHITE ABS ENCLOSURE, WHITE LID, 125 X 125 X 45MM**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 125 mm
- External Height: 45 mm
- External Width: 125 mm
- External Dimensions: 125 x 125 x 45 mm
- Colour: White
- Lid Colour: White

**1533685** ABS

RS PRO WHITE ABS ENCLOSURE, WHITE LID, 105 X 70 X 50MM

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 105 mm
- External Height: 50 mm
- External Width: 70 mm
- External Dimensions: 105 x 70 x 50 mm
- Colour: White
- Lid Colour: White



1533686 ABS

RS PRO WHITE ABS ENCLOSURE, WHITE LID, 120 X 65 X 40MM

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 120 mm
- External Height: 40 mm
- External Width: 65 mm
- External Dimensions: 120 x 65 x 40 mm
- Colour: White
- Lid Colour: White



1533687 ABS

RS PRO GREY ABS ENCLOSURE, IP65, FLANGED, GREY LID, 108.2 X 58.2 X

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 108.2 mm
- External Height: 39.5 mm
- External Width: 58.2 mm
- External Dimensions: 108.2 x 58.2 x 39.5 mm
- IP Rating: IP65
- Colour: Grey
- Lid Colour: Grey



1533688 ABS

RS PRO BLACK ABS ENCLOSURE, BLACK LID, 125 X 125 X 25MM

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 125 mm
- External Height: 25 mm
- External Width: 125 mm
- External Dimensions: 125 x 125 x 25 mm
- Colour: Black
- Lid Colour: Black



1533689 ABS

RS PRO BLACK ABS ENCLOSURE, IP65, FLANGED, BLACK LID, 173.4 X

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 173.4 mm
- External Height: 50.5 mm
- External Width: 82.4 mm
- External Dimensions: 173.4 x 82.4 x 50.5 mm
- IP Rating: IP65
- Colour: Black
- Lid Colour: Black



1533692 ABS

RS PRO BLACK ABS ENCLOSURE, BLACK LID, 170 X 85.5 X 35.5MM

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 170 mm
- External Height: 35.5 mm
- External Width: 85.5 mm
- External Dimensions: 170 x 85.5 x 35.5 mm
- Colour: Black
- Lid Colour: Black



1533693 ABS

RS PRO GREY ABS ENCLOSURE, IP65, FLANGED, GREY LID, 135.8 X 64.55 X

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 135.8 mm
- External Height: 31.5 mm
- External Width: 64.6 mm
- External Dimensions: 135.8 x 64.55 x 31.5 mm
- IP Rating: IP65
- Colour: Grey
- Lid Colour: Grey



1533695 ABS

RS PRO BLACK ABS ENCLOSURE, BLACK LID, 105 X 70 X 35MM

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 105 mm
- External Height: 35 mm
- External Width: 70 mm
- External Dimensions: 105 x 70 x 35 mm
- Colour: Black
- Lid Colour: Black



1533696 ABS

RS PRO WHITE ABS ENCLOSURE, WHITE LID, 170 X 85.5 X 35.5MM

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 170 mm
- External Height: 35.5 mm
- External Width: 85.5 mm
- External Dimensions: 170 x 85.5 x 35.5 mm
- Colour: White
- Lid Colour: White



1533702 ABS

RS PRO BLACK DIE CAST ALUMINIUM ENCLOSURE, IP54, BLACK LID, 120 X

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 120 mm
- External Height: 39.8 mm
- External Width: 65.5 mm
- External Dimensions: 120 x 65.5 x 39.75 mm
- IP Rating: IP54
- Colour: Black
- Lid Colour: Black



1585310 Die Cast

RS PRO BLACK DIE CAST ALUMINIUM ENCLOSURE, IP54, BLACK LID, 152 X

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 152 mm
- External Height: 49.8 mm
- External Width: 82 mm
- External Dimensions: 152 x 82 x 49.75 mm
- IP Rating: IP54
- Colour: Black
- Lid Colour: Black



1585312 Die Cast

RS PRO BLACK DIE CAST ALUMINIUM ENCLOSURE, IP54, BLACK LID, 191.6 X

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 191.6 mm
- External Height: 60.5 mm
- External Width: 111.6 mm
- External Dimensions: 191.6 x 111.6 x 60.5 mm
- IP Rating: IP54
- Colour: Black
- Lid Colour: Black



1585314 Die Cast

RS PRO RED DIE CAST ALUMINIUM ENCLOSURE, IP54, RED LID, 120 X

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 120 mm
- External Height: 39.8 mm
- External Width: 65.5 mm
- External Dimensions: 120 x 65.5 x 39.75 mm
- IP Rating: IP54
- Colour: Red
- Lid Colour: Red



1585311 Die Cast

RS PRO RED DIE CAST ALUMINIUM ENCLOSURE, IP54, RED LID, 152 X 82 X

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 152 mm
- External Height: 49.8 mm
- External Width: 82 mm
- External Dimensions: 152 x 82 x 49.75 mm
- IP Rating: IP54
- Colour: Red
- Lid Colour: Red



1585313 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP54, SILVER LID, 187.4 X

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 187.4 mm
- External Height: 56.2 mm
- External Width: 119.2 mm
- External Dimensions: 187.4 x 119.2 x 56.2 mm
- IP Rating: IP54
- Colour: Silver
- Lid Colour: Silver



1610919 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP54, SILVER LID, 120.5 X

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 120.5 mm
- External Height: 59.3 mm
- External Width: 79.6 mm
- External Dimensions: 120.5 x 79.6 x 59.3 mm
- IP Rating: IP54
- Colour: Silver
- Lid Colour: Silver



1610922 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP54, SILVER LID, 152.2 XPack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 152.2 mm
- External Height: 50.8 mm
- External Width: 82.2 mm
- External Dimensions: 152.2 x 82.2 x 50.8 mm
- IP Rating: IP54
- Colour: Silver
- Lid Colour: Silver

**1610926** Die Cast**RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP54, SILVER LID, 187.4 X**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 187.4 mm
- External Height: 38.2 mm
- External Width: 119.2 mm
- External Dimensions: 187.4 x 119.2 x 38.2 mm
- IP Rating: IP54
- Colour: Silver
- Lid Colour: Silver

**1610927** Die Cast**RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP54, SILVER LID, 190.1 X**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 190.1 mm
- External Height: 66.5 mm
- External Width: 190.1 mm
- External Dimensions: 190.1 x 190.1 x 66.5 mm
- IP Rating: IP54
- Colour: Silver
- Lid Colour: Silver

**1610928** Die Cast**RS PRO SILVER ALUMINIUM ALLOY ENCLOSURE, IP65, BLACK LID, 115 X**Pack size: **1 x EA**

- Body Material: Aluminium Alloy
- External Length: 115 mm
- External Height: 30.2 mm
- External Width: 65 mm
- External Dimensions: 115 x 65 x 30.2 mm
- IP Rating: IP65
- Colour: Silver
- Lid Colour: Black

**1610931** Aluminium Alloy**RS PRO SILVER ALUMINIUM ALLOY ENCLOSURE, IP65, SILVER LID, 158.5 X**Pack size: **1 x EA**

- Body Material: Aluminium Alloy
- External Length: 158.5 mm
- External Height: 101.5 mm
- External Width: 158.5 mm
- External Dimensions: 158.5 x 158.5 x 101.5 mm
- IP Rating: IP65
- Colour: Silver
- Lid Colour: Silver

**1610935** Aluminium Alloy**RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP54, SILVER LID, 101 X**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 101 mm
- External Height: 24.5 mm
- External Width: 50 mm
- External Dimensions: 101 x 50 x 24.5 mm
- IP Rating: IP54
- Colour: Silver
- Lid Colour: Silver

**1610937** Die Cast**RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP54, SILVER LID, 120 X**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 120 mm
- External Height: 39.8 mm
- External Width: 65.5 mm
- External Dimensions: 120 x 65.5 x 39.75 mm
- IP Rating: IP54
- Colour: Silver
- Lid Colour: Silver

**1610939** Die Cast**RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP54, IP65, IP66, SILVER**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 152 mm
- External Height: 49.8 mm
- External Width: 82 mm
- External Dimensions: 152 x 82 x 49.75 mm
- IP Rating: IP54, IP65, IP66
- Colour: Silver
- Lid Colour: Silver

**1610940** Die Cast**RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP54, IP65, IP66, SILVER**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 191.6 mm
- External Height: 60.5 mm
- External Width: 111.6 mm
- External Dimensions: 191.6 x 111.6 x 60.5 mm
- IP Rating: IP54, IP65, IP66
- Colour: Silver
- Lid Colour: Silver

**1610941** Die Cast**RS PRO BLACK ABS ENCLOSURE, IP65, IK07, BLACK LID, 197.7 X 144.55**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 197.7 mm
- External Height: 52.6 mm
- External Width: 144.6 mm
- External Dimensions: 197.7 x 144.55 x 52.55 mm
- IP Rating: IP65
- Colour: Black
- Lid Colour: Black

**1862249** ABS**RS PRO BLACK ABS ENCLOSURE, IP65, IK07, BLACK LID, 198.05 X 144.7**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 198.1 mm
- External Height: 72.3 mm
- External Width: 144.7 mm
- External Dimensions: 198.05 x 144.7 x 72.25 mm
- IP Rating: IP65
- Colour: Black
- Lid Colour: Black

**1862250** ABS**RS PRO GREY ABS ENCLOSURE, IP65, IK07, GREY LID, 197.7 X 144.55 X**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 197.7 mm
- External Height: 52.6 mm
- External Width: 144.6 mm
- External Dimensions: 197.7 x 144.55 x 52.55 mm
- IP Rating: IP65
- Colour: Grey
- Lid Colour: Grey

**1862251** ABS**RS PRO GREY ABS ENCLOSURE, IP65, IK09, GREY LID, 89.35 X 74.5 X 41MM**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 89.4 mm
- External Height: 41 mm
- External Width: 74.5 mm
- External Dimensions: 89.35 x 74.5 x 41 mm
- IP Rating: IP65
- Colour: Grey
- Lid Colour: Grey

**1862253** ABS**RS PRO GREY ABS ENCLOSURE, IP67, IK09, GREY LID, 89.35 X 74.5 X 41MM**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 89.4 mm
- External Height: 41 mm
- External Width: 74.5 mm
- External Dimensions: 89.35 x 74.5 x 41 mm
- IP Rating: IP67
- Colour: Grey
- Lid Colour: Grey

**1862254** ABS**RS PRO GREY ABS ENCLOSURE, IP65, IK09, GREY LID, 118.15 X 78.35 X**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 118.2 mm
- External Height: 54.6 mm
- External Width: 78.4 mm
- External Dimensions: 118.15 x 78.35 x 54.6 mm
- IP Rating: IP65
- Colour: Grey
- Lid Colour: Grey

**1862255** ABS**RS PRO GREY ABS ENCLOSURE, IP67, IK09, GREY LID, 118.15 X 78.35 X**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 118.2 mm
- External Height: 54.6 mm
- External Width: 78.4 mm
- External Dimensions: 118.15 x 78.35 x 54.6 mm
- IP Rating: IP67
- Colour: Grey
- Lid Colour: Grey

**1862256** ABS

RS PRO GREY ABS ENCLOSURE, IP65, IK09, GREY LID, 158.15 X 82.2 X

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 158.2 mm
- External Height: 54.9 mm
- External Width: 82.2 mm
- External Dimensions: 158.15 x 82.2 x 54.9 mm
- IP Rating: IP65
- Colour: Grey
- Lid Colour: Grey



1862257 ABS

RS PRO GREY ABS ENCLOSURE, IP67, IK09, GREY LID, 158.15 X 82.2 X

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 158.2 mm
- External Height: 54.9 mm
- External Width: 82.2 mm
- External Dimensions: 158.15 x 82.2 x 54.9 mm
- IP Rating: IP67
- Colour: Grey
- Lid Colour: Grey



1862258 ABS

RS PRO GREY ABS ENCLOSURE, IP65, IK09, GREY LID, 125.3 X 115.4 X

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 125.3 mm
- External Height: 58.1 mm
- External Width: 115.4 mm
- External Dimensions: 125.3 x 115.4 x 58.05 mm
- IP Rating: IP65
- Colour: Grey
- Lid Colour: Grey



1862259 ABS

RS PRO GREY ABS ENCLOSURE, IP67, IK09, GREY LID, 125.3 X 115.4 X

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 125.3 mm
- External Height: 58.1 mm
- External Width: 115.4 mm
- External Dimensions: 125.3 x 115.4 x 58.05 mm
- IP Rating: IP67
- Colour: Grey
- Lid Colour: Grey



1862260 ABS

RS PRO GREY ABS ENCLOSURE, IP65, IK09, GREY LID, 176.8 X 125.95 X

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 176.8 mm
- External Height: 56.7 mm
- External Width: 126 mm
- External Dimensions: 176.8 x 125.95 x 56.65 mm
- IP Rating: IP65
- Colour: Grey
- Lid Colour: Grey



1862261 ABS

RS PRO GREY ABS ENCLOSURE, IP67, IK09, GREY LID, 176.8 X 125.95 X

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 176.8 mm
- External Height: 56.7 mm
- External Width: 126 mm
- External Dimensions: 176.8 x 125.95 x 56.65 mm
- IP Rating: IP67
- Colour: Grey
- Lid Colour: Grey



1862262 ABS

RS PRO GREY ABS ENCLOSURE, IP65, IK09, GREY LID, 225 X 174.8 X

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 225 mm
- External Height: 81.3 mm
- External Width: 174.8 mm
- External Dimensions: 225 x 174.8 x 81.25 mm
- IP Rating: IP65
- Colour: Grey
- Lid Colour: Grey



1862263 ABS

RS PRO GREY ABS ENCLOSURE, IP67, IK09, GREY LID, 225 X 174.8 X

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 225 mm
- External Height: 81.3 mm
- External Width: 174.8 mm
- External Dimensions: 225 x 174.8 x 81.25 mm
- IP Rating: IP67
- Colour: Grey
- Lid Colour: Grey



1862264 ABS

RS PRO GREY ABS ENCLOSURE, IP65, IK09, GREY LID, 283 X 193.2 X 96.7MM

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 283 mm
- External Height: 96.7 mm
- External Width: 193.2 mm
- External Dimensions: 283 x 193.2 x 96.7 mm
- IP Rating: IP65
- Colour: Grey
- Lid Colour: Grey



1862265 ABS

RS PRO GREY ABS ENCLOSURE, IP67, IK09, GREY LID, 283 X 193.2 X 96.7MM

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 283 mm
- External Height: 96.7 mm
- External Width: 193.2 mm
- External Dimensions: 283 x 193.2 x 96.7 mm
- IP Rating: IP67
- Colour: Grey
- Lid Colour: Grey



1862266 ABS

RS PRO GREY ABS ENCLOSURE, IP65, IK09, GREY LID, 70 X 50 X 36.75MM

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 70 mm
- External Height: 36.8 mm
- External Width: 50 mm
- External Dimensions: 70 x 50 x 36.75 mm
- IP Rating: IP65
- Colour: Grey
- Lid Colour: Grey



1862267 ABS

RS PRO GREY ABS ENCLOSURE, IP67, IK09, GREY LID, 70 X 50 X 36.75MM

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 70 mm
- External Height: 36.8 mm
- External Width: 50 mm
- External Dimensions: 70 x 50 x 36.75 mm
- IP Rating: IP67
- Colour: Grey
- Lid Colour: Grey



1862268 ABS

RS PRO GREY ABS ENCLOSURE, IP65, IK09, GREY LID, 81.95 X 79.95 X

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 82 mm
- External Height: 55 mm
- External Width: 80 mm
- External Dimensions: 81.95 x 79.95 x 55 mm
- IP Rating: IP65
- Colour: Grey
- Lid Colour: Grey



1862269 ABS

RS PRO GREY ABS ENCLOSURE, IP67, IK09, GREY LID, 81.95 X 79.95 X

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 82 mm
- External Height: 55 mm
- External Width: 80 mm
- External Dimensions: 81.95 x 79.95 x 55 mm
- IP Rating: IP67
- Colour: Grey
- Lid Colour: Grey



1862270 ABS

RS PRO GREY ABS ENCLOSURE, IP65, IK09, GREY LID, 50.95 X 48.9 X

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 51 mm
- External Height: 36.2 mm
- External Width: 48.9 mm
- External Dimensions: 50.95 x 48.9 x 36.15 mm
- IP Rating: IP65
- Colour: Grey
- Lid Colour: Grey



1862271 ABS

RS PRO GREY ABS ENCLOSURE, IP67, IK09, GREY LID, 50.95 X 48.9 X

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 51 mm
- External Height: 36.2 mm
- External Width: 48.9 mm
- External Dimensions: 50.95 x 48.9 x 36.15 mm
- IP Rating: IP67
- Colour: Grey
- Lid Colour: Grey



1862272 ABS

RS PRO GREY ABS ENCLOSURE, IP65, IK09, GREY LID, 63.15 X 57.1 XPack size: **1 x EA**

- Body Material: ABS
- External Length: 63.2 mm
- External Height: 36.7 mm
- External Width: 57.1 mm
- External Dimensions: 63.15 x 57.1 x 36.65 mm
- IP Rating: IP65
- Colour: Grey
- Lid Colour: Grey

**1862273** ABS**RS PRO GREY ABS ENCLOSURE, IP67, IK09, GREY LID, 63.15 X 57.1 X**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 63.2 mm
- External Height: 36.7 mm
- External Width: 57.1 mm
- External Dimensions: 63.15 x 57.1 x 36.65 mm
- IP Rating: IP67
- Colour: Grey
- Lid Colour: Grey

**1862274** ABS**RS PRO GREY ABS ENCLOSURE, IP65, IK07, GREY LID, 105 X 105 X 60MM**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 105 mm
- External Height: 60 mm
- External Width: 105 mm
- External Dimensions: 105 x 105 x 60 mm
- IP Rating: IP65
- Colour: Grey
- Lid Colour: Grey

**1862275** ABS**RS PRO GREY ABS, POLYCARBONATE ENCLOSURE, IP67, IK07, 105 X 105 X**Pack size: **1 x EA**

- Body Material: ABS, Polycarbonate
- External Length: 105 mm
- External Height: 60.1 mm
- External Width: 105 mm
- External Dimensions: 105 x 105 x 60.1 mm
- IP Rating: IP67
- Colour: Grey
- Shielded: Yes

**1862277** ABS,**RS PRO GREY ABS ENCLOSURE, IP65, IK07, GREY LID, 119.8 X 119.8 X**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 119.8 mm
- External Height: 60.1 mm
- External Width: 119.8 mm
- External Dimensions: 119.8 x 119.8 x 60.1 mm
- IP Rating: IP65
- Colour: Grey
- Lid Colour: Grey

**1862278** ABS**RS PRO GREY ABS ENCLOSURE, IP65, IK07, GREY LID, 149.85 X 149.85 X**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 149.9 mm
- External Height: 60 mm
- External Width: 149.9 mm
- External Dimensions: 149.85 x 149.85 x 60 mm
- IP Rating: IP65
- Colour: Grey
- Lid Colour: Grey

**1862284** ABS**RS PRO GREY POLYCARBONATE ENCLOSURE, IP67, IK07, GREY LID,**Pack size: **1 x EA**

- Body Material: Polycarbonate
- External Length: 149.9 mm
- External Height: 60 mm
- External Width: 149.9 mm
- External Dimensions: 149.85 x 149.85 x 60 mm
- IP Rating: IP67
- Colour: Grey
- Lid Colour: Grey

**1862285** Polycarbonate**RS PRO GREY ABS, POLYCARBONATE ENCLOSURE, IP67, IK07, 149.85 X**Pack size: **1 x EA**

- Body Material: ABS, Polycarbonate
- External Length: 149.9 mm
- External Height: 60 mm
- External Width: 149.9 mm
- External Dimensions: 149.85 x 149.85 x 60 mm
- IP Rating: IP67
- Colour: Grey
- Shielded: Yes

**1862286** ABS,**RS PRO BLACK EXTRUDED ALUMINIUM HEAT SINK CASE, IP40, BLACK LID,**Pack size: **1 x EA**

- Body Material: Extruded Aluminium
- External Length: 300 mm
- External Height: 41 mm
- External Width: 300 mm
- External Dimensions: 300 x 300 x 41 mm
- IP Rating: IP40
- Colour: Black
- Lid Colour: Black

**1881259** Extruded**RS PRO BLACK EXTRUDED ALUMINIUM HEAT SINK CASE, IP40, BLACK LID,**Pack size: **1 x EA**

- Body Material: Extruded Aluminium
- External Length: 300 mm
- External Height: 86 mm
- External Width: 200 mm
- External Dimensions: 300 x 200 x 86 mm
- IP Rating: IP40
- Colour: Black
- Lid Colour: Black

**1881265** Extruded**RS PRO BLACK EXTRUDED ALUMINIUM HEAT SINK CASE, IP40, BLACK LID,**Pack size: **1 x EA**

- Body Material: Extruded Aluminium
- External Length: 400 mm
- External Height: 86 mm
- External Width: 200 mm
- External Dimensions: 400 x 200 x 86 mm
- IP Rating: IP40
- Colour: Black
- Lid Colour: Black

**1881266** Extruded**RS PRO BLACK EXTRUDED ALUMINIUM HEAT SINK CASE, IP40, BLACK LID,**Pack size: **1 x EA**

- Body Material: Extruded Aluminium
- External Length: 200 mm
- External Height: 86 mm
- External Width: 300 mm
- External Dimensions: 200 x 300 x 86 mm
- IP Rating: IP40
- Colour: Black
- Lid Colour: Black

**1881267** Extruded**RS PRO BLACK EXTRUDED ALUMINIUM HEAT SINK CASE, IP40, BLACK LID,**Pack size: **1 x EA**

- Body Material: Extruded Aluminium
- External Length: 300 mm
- External Height: 86 mm
- External Width: 300 mm
- External Dimensions: 300 x 300 x 86 mm
- IP Rating: IP40
- Colour: Black
- Lid Colour: Black

**1881268** Extruded**RS PRO BLACK EXTRUDED ALUMINIUM HEAT SINK CASE, IP40, BLACK LID,**Pack size: **1 x EA**

- Body Material: Extruded Aluminium
- External Length: 400 mm
- External Height: 130 mm
- External Width: 100 mm
- External Dimensions: 400 x 100 x 130 mm
- IP Rating: IP40
- Colour: Black
- Lid Colour: Black

**1881272** Extruded**RS PRO BLACK EXTRUDED ALUMINIUM HEAT SINK CASE, IP40, BLACK LID,**Pack size: **1 x EA**

- Body Material: Extruded Aluminium
- External Length: 200 mm
- External Height: 130 mm
- External Width: 200 mm
- External Dimensions: 200 x 200 x 130 mm
- IP Rating: IP40
- Colour: Black
- Lid Colour: Black

**1881273** Extruded**RS PRO BLACK EXTRUDED ALUMINIUM HEAT SINK CASE, IP40, BLACK LID,**Pack size: **1 x EA**

- Body Material: Extruded Aluminium
- External Length: 300 mm
- External Height: 130 mm
- External Width: 200 mm
- External Dimensions: 300 x 200 x 130 mm
- IP Rating: IP40
- Colour: Black
- Lid Colour: Black

**1881274** Extruded

RS PRO BLACK EXTRUDED ALUMINIUM HEAT SINK CASE, IP40, BLACK LID,

Pack size: **1 x EA**

- Body Material: Extruded Aluminium
- External Length: 300 mm
- External Height: 130 mm
- External Width: 300 mm
- External Dimensions: 300 x 300 x 130 mm
- IP Rating: IP40
- Colour: Black
- Lid Colour: Black



1881277 Extruded

RS PRO BLACK EXTRUDED ALUMINIUM HEAT SINK CASE, IP40, BLACK LID,

Pack size: **1 x EA**

- Body Material: Extruded Aluminium
- External Length: 200 mm
- External Height: 175 mm
- External Width: 200 mm
- External Dimensions: 200 x 200 x 175 mm
- IP Rating: IP40
- Colour: Black
- Lid Colour: Black



1881283 Extruded

RS PRO BLACK EXTRUDED ALUMINIUM HEAT SINK CASE, IP40, BLACK LID,

Pack size: **1 x EA**

- Body Material: Extruded Aluminium
- External Length: 300 mm
- External Height: 175 mm
- External Width: 200 mm
- External Dimensions: 300 x 200 x 175 mm
- IP Rating: IP40
- Colour: Black
- Lid Colour: Black



1881284 Extruded

RS PRO BLACK EXTRUDED ALUMINIUM HEAT SINK CASE, IP40, BLACK LID,

Pack size: **1 x EA**

- Body Material: Extruded Aluminium
- External Length: 400 mm
- External Height: 175 mm
- External Width: 200 mm
- External Dimensions: 400 x 200 x 175 mm
- IP Rating: IP40
- Colour: Black
- Lid Colour: Black



1881285 Extruded

RS PRO BLACK EXTRUDED ALUMINIUM HEAT SINK CASE, IP40, BLACK LID,

Pack size: **1 x EA**

- Body Material: Extruded Aluminium
- External Length: 400 mm
- External Height: 175 mm
- External Width: 300 mm
- External Dimensions: 400 x 300 x 175 mm
- IP Rating: IP40
- Colour: Black
- Lid Colour: Black



1881288 Extruded

RS PRO BLACK EXTRUDED ALUMINIUM HEAT SINK CASE, IP40, BLACK LID,

Pack size: **1 x EA**

- Body Material: Extruded Aluminium
- External Length: 300 mm
- External Height: 219 mm
- External Width: 200 mm
- External Dimensions: 300 x 200 x 219 mm
- IP Rating: IP40
- Colour: Black
- Lid Colour: Black



1881290 Extruded

RS PRO BLACK EXTRUDED ALUMINIUM HEAT SINK CASE, IP40, BLACK LID,

Pack size: **1 x EA**

- Body Material: Extruded Aluminium
- External Length: 400 mm
- External Height: 219 mm
- External Width: 300 mm
- External Dimensions: 400 x 300 x 219 mm
- IP Rating: IP40
- Colour: Black
- Lid Colour: Black



1881294 Extruded

RS PRO BLACK EXTRUDED ALUMINIUM HEAT SINK CASE, IP40, BLACK LID,

Pack size: **1 x EA**

- Body Material: Extruded Aluminium
- External Length: 299 mm
- External Height: 50 mm
- External Width: 175 mm
- External Dimensions: 299 x 175 x 50 mm
- IP Rating: IP40
- Colour: Black
- Lid Colour: Black



1881301 Extruded

RS PRO GREY EXTRUDED ALUMINIUM ENCLOSURE, IP30, GREY LID, 178 X

Pack size: **1 x EA**

- Body Material: Extruded Aluminium
- External Length: 178 mm
- External Height: 65 mm
- External Width: 203 mm
- External Dimensions: 178 x 203 x 65 mm
- IP Rating: IP30
- Colour: Grey
- Lid Colour: Grey



1881328 Extruded

RS PRO GREY EXTRUDED ALUMINIUM ENCLOSURE, IP30, GREY LID, 178 X

Pack size: **1 x EA**

- Body Material: Extruded Aluminium
- External Length: 178 mm
- External Height: 175 mm
- External Width: 305 mm
- External Dimensions: 178 x 305 x 175 mm
- IP Rating: IP30
- Colour: Grey
- Lid Colour: Grey



1881337 Extruded

RS PRO GREY FIBREGLASS REINFORCED POLYESTER

Pack size: **1 x EA**

- Body Material: Fibreglass Reinforced Polyester
- External Length: 600 mm
- External Height: 121 mm
- External Width: 250 mm
- External Dimensions: 600 x 250 x 121 mm
- IP Rating: IP66
- Colour: Grey
- Lid Colour: Grey



1901843 Fibreglass

RS PRO GREY FIBREGLASS REINFORCED POLYESTER GENERAL

Pack size: **1 x EA**

- Body Material: Fibreglass Reinforced Polyester
- External Length: 400 mm
- External Height: 160 mm
- External Width: 250 mm
- External Dimensions: 400 x 250 x 160 mm
- IP Rating: IP66
- Colour: Grey
- Lid Colour: Grey



1901847 Fibreglass

RS PRO BLACK FIBREGLASS REINFORCED POLYESTER GENERAL

Pack size: **1 x EA**

- Body Material: Fibreglass Reinforced Polyester
- External Length: 255 mm
- External Height: 160 mm
- External Width: 250 mm
- External Dimensions: 255 x 250 x 160 mm
- IP Rating: IP66, IP67, IP68
- Colour: Black
- Lid Colour: Black



1901848 Fibreglass

RS PRO BLACK FIBREGLASS REINFORCED POLYESTER GENERAL

Pack size: **1 x EA**

- Body Material: Fibreglass Reinforced Polyester
- External Length: 80 mm
- External Height: 75 mm
- External Width: 75 mm
- External Dimensions: 80 x 75 x 75 mm
- IP Rating: IP66, IP67, IP68
- Colour: Black
- Lid Colour: Black



1901854 Fibreglass

RS PRO GREY FIBREGLASS REINFORCED POLYESTER

Pack size: **1 x EA**

- Body Material: Fibreglass Reinforced Polyester
- External Length: 80 mm
- External Height: 75 mm
- External Width: 75 mm
- External Dimensions: 80 x 75 x 75 mm
- IP Rating: IP66, IP67, IP68
- Colour: Grey
- Lid Colour: Grey



1901856 Fibreglass

RS PRO SILVER ALUMINIUM ENCLOSURE, IP66, IP67, IP68, IK09,

Pack size: **1 x EA**

- Body Material: Aluminium
- External Length: 58 mm
- External Height: 34 mm
- External Width: 64 mm
- External Dimensions: 58 x 64 x 34 mm
- IP Rating: IP66, IP67, IP68
- Colour: Silver
- Lid Colour: Silver



1901860 Aluminium

RS PRO SILVER ALUMINIUM ENCLOSURE, IP66, IP67, IP68, IK09,Pack size: **1 x EA**

- Body Material: Aluminium
- External Length: 140 mm
- External Height: 90 mm
- External Width: 140 mm
- External Dimensions: 140 x 140 x 90 mm
- IP Rating: IP66, IP67, IP68
- Colour: Silver
- Lid Colour: Silver

**1901861** Aluminium**RS PRO GREY ALUMINIUM ENCLOSURE, IP66, IP67, IP68, IK09,**Pack size: **1 x EA**

- Body Material: Aluminium
- External Length: 200 mm
- External Height: 90 mm
- External Width: 140 mm
- External Dimensions: 200 x 140 x 90 mm
- IP Rating: IP66, IP67, IP68
- Colour: Grey
- Lid Colour: Grey

**1901864** Aluminium**RS PRO BLACK FIBREGLASS REINFORCED POLYESTER**Pack size: **1 x EA**

- Body Material: Fibreglass Reinforced Polyester
- External Length: 110 mm
- External Height: 75 mm
- External Width: 75 mm
- External Dimensions: 110 x 75 x 75 mm
- IP Rating: IP66, IP67, IP68
- Colour: Black
- RAL Code: RAL 9011

**1901866** Fibreglass**RS PRO BLACK FIBREGLASS REINFORCED POLYESTER**Pack size: **1 x EA**

- Body Material: Fibreglass Reinforced Polyester
- External Length: 255 mm
- External Height: 160 mm
- External Width: 160 mm
- External Dimensions: 255 x 250 x 160 mm
- IP Rating: IP66, IP67, IP68
- Colour: Black
- RAL Code: RAL 9011

**1901868** Fibreglass**RS PRO BLACK FIBREGLASS REINFORCED POLYESTER**Pack size: **1 x EA**

- Body Material: Fibreglass Reinforced Polyester
- External Length: 400 mm
- External Height: 201 mm
- External Width: 405 mm
- External Dimensions: 400 x 405 x 201 mm
- IP Rating: IP66, IP67, IP68
- Colour: Black
- RAL Code: RAL 9011

**1901870** Fibreglass**RS PRO ALUMINIUM ENCLOSURE, IP66, IP67, IP68, IK09, 180 X 180 X**Pack size: **1 x EA**

- Body Material: Aluminium
- External Length: 180 mm
- External Height: 100 mm
- External Width: 180 mm
- External Dimensions: 180 x 180 x 100 mm
- IP Rating: IP66, IP67, IP68
- IK Rating: IK09
- Gasket Material: Silicone

**1901874** Aluminium**RS PRO ALUMINIUM ENCLOSURE, IP66, IP67, IP68, IK09, 200 X 140 X**Pack size: **1 x EA**

- Body Material: Aluminium
- External Length: 200 mm
- External Height: 90 mm
- External Width: 140 mm
- External Dimensions: 200 x 140 x 90 mm
- IP Rating: IP66, IP67, IP68
- IK Rating: IK09
- Gasket Material: Silicone

**1901875** Aluminium**RS PRO GREY FIBREGLASS REINFORCED POLYESTER**Pack size: **1 x EA**

- Body Material: Fibreglass Reinforced Polyester
- External Length: 255 mm
- External Height: 160 mm
- External Width: 250 mm
- External Dimensions: 255 x 250 x 160 mm
- IP Rating: IP66
- Colour: Grey
- Lid Colour: Grey

**1904274** Fibreglass**RS PRO GREY FIBREGLASS REINFORCED POLYESTER**Pack size: **1 x EA**

- Body Material: Fibreglass Reinforced Polyester
- External Length: 110 mm
- External Height: 75 mm
- External Width: 75 mm
- External Dimensions: 110 x 75 x 75 mm
- IP Rating: IP66
- Colour: Grey
- Lid Colour: Grey

**1904275** Fibreglass**RS PRO GREY FIBREGLASS REINFORCED POLYESTER**Pack size: **1 x EA**

- Body Material: Fibreglass Reinforced Polyester
- External Length: 80 mm
- External Height: 75 mm
- External Width: 75 mm
- External Dimensions: 80 x 75 x 75 mm
- IP Rating: IP66
- Colour: Grey
- Lid Colour: Grey

**1904276** Fibreglass**RS PRO BLACK FIBREGLASS REINFORCED POLYESTER**Pack size: **1 x EA**

- Body Material: Fibreglass Reinforced Polyester
- External Length: 190 mm
- External Height: 75 mm
- External Width: 75 mm
- External Dimensions: 190 x 75 x 75 mm
- IP Rating: IP66
- Colour: Black
- Lid Colour: Black

**1904279** Fibreglass**RS PRO GREY ABS ENCLOSURE, IP65, GREY LID, 139.8 X 209.7 X 60.1MM**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 209.7 mm
- External Height: 60.1 mm
- External Width: 139.8 mm
- External Dimensions: 139.8 x 209.7 x 60.1 mm
- IP Rating: IP65
- Colour: Grey
- Lid Colour: Grey

**1920695** ABS**RS PRO GREY ABS ENCLOSURE, IP65, GREY LID, 100.1 X 150.1 X 60MM**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 150.1 mm
- External Height: 60 mm
- External Width: 100.1 mm
- External Dimensions: 100.1 x 150.1 x 60 mm
- IP Rating: IP65
- Colour: Grey
- Lid Colour: Grey

**1920698** ABS**RS PRO ABS GENERAL PURPOSE ENCLOSURE, 181.55 X 100 X 60MM**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 181.55 mm
- External Height: 60 mm
- External Width: 100 mm
- External Dimensions: 181.55 x 100 x 60 mm

**1920699** ABS**RS PRO GREY ABS ENCLOSURE, IP65, GREY LID, 100 X 150 X 75MM**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 150 mm
- External Height: 75 mm
- External Width: 100 mm
- External Dimensions: 100 x 150 x 75 mm
- IP Rating: IP65
- Colour: Grey
- Lid Colour: Grey

**1920700** ABS**RS PRO GREY ABS ENCLOSURE, IP65, GREY LID, 120.1 X 180.1 X 90.3MM**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 180.1 mm
- External Height: 90.3 mm
- External Width: 120.1 mm
- External Dimensions: 120.1 x 180.1 x 90.3 mm
- IP Rating: IP65
- Colour: Grey
- Lid Colour: Grey

**1920702** ABS

RS PRO BLACK ABS ENCLOSURE, IP20, IK06, BLACK LID, 75.8 X 75.8 X

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 75.8 mm
- External Height: 30.3 mm
- External Width: 75.6 mm
- External Dimensions: 75.8 x 75.8 x 30.2 mm
- IP Rating: IP20
- Colour: Black
- Lid Colour: Black



1920714 ABS

RS PRO WHITE ABS ENCLOSURE, IP20, IK06, WHITE LID, 75.8 X 75.8 X

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 75.8 mm
- External Height: 30.3 mm
- External Width: 75.6 mm
- External Dimensions: 75.8 x 75.8 x 30.2 mm
- IP Rating: IP20
- Colour: White
- Lid Colour: White



1920716 ABS

RS PRO GREY ABS ENCLOSURE, IP65, IK08, GREY LID, 105 X 70 X 40MM

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 105 mm
- External Height: 40 mm
- External Width: 70 mm
- External Dimensions: 105 x 70 x 40 mm
- IP Rating: IP65
- Colour: Grey
- Lid Colour: Grey



1920721 ABS

RS PRO GREY POLYCARBONATE ENCLOSURE, IP68, IK07, GREY LID,

Pack size: **1 x EA**

- Body Material: Polycarbonate
- External Length: 105 mm
- External Height: 40 mm
- External Width: 70 mm
- External Dimensions: 105 x 70 x 40 mm
- IP Rating: IP68
- Colour: Grey
- Lid Colour: Grey



1920722 Polycarbonate

RS PRO GREY ABS, POLYCARBONATE ENCLOSURE, IP68, IK07,

Pack size: **1 x EA**

- Body Material: ABS, Polycarbonate
- External Length: 105 mm
- External Height: 40 mm
- External Width: 70 mm
- External Dimensions: 105 x 70 x 40 mm
- IP Rating: IP68
- Colour: Grey
- Lid Colour: Transparent



1920723 ABS,

RS PRO GREY POLYCARBONATE ENCLOSURE, IP68, IK07, FLANGED,

Pack size: **1 x EA**

- Body Material: Polycarbonate
- External Length: 131.3 mm
- External Height: 40 mm
- External Width: 71.3 mm
- External Dimensions: 105 x 70 x 40 mm
- IP Rating: IP68
- Colour: Grey
- Lid Colour: Grey



1920726 Polycarbonate

RS PRO GREY ABS, POLYCARBONATE ENCLOSURE, IP68, IK07, FLANGED,

Pack size: **1 x EA**

- Body Material: ABS, Polycarbonate
- External Length: 131.3 mm
- External Height: 40 mm
- External Width: 71.3 mm
- External Dimensions: 105 x 70 x 40 mm
- IP Rating: IP68
- Colour: Grey
- Lid Colour: Transparent



1920727 ABS,

RS PRO BLACK ABS ENCLOSURE, BLACK LID, 31.5 X 56.5 X 27.2MM

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 56.5 mm
- External Height: 31.5 mm
- External Width: 27.2 mm
- External Dimensions: 31.5 x 56.5 x 27.2 mm
- Colour: Black
- Lid Colour: Black
- Flanged: No



1920728 ABS

PLASTIC ENCLOSURE Z70 WITH LUGS ABS

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 75.8 mm
- External Height: 27.9 mm
- External Width: 77.9 mm
- External Dimensions: 75.75 x 77.85 x 27.9 mm
- IP Rating: IP54
- Colour: Black
- Flanged: Yes



1920744 ABS

RS PRO BLACK ABS ENCLOSURE, IP54, IK06, BLACK LID, 120 X 90 X

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 119 mm
- External Height: 37.9 mm
- External Width: 89.3 mm
- External Dimensions: 120 x 90 x 38 mm
- IP Rating: IP54
- Colour: Black
- Lid Colour: Black



1920746 ABS

RS PRO BLACK ABS ENCLOSURE, IP52, BLACK LID, 32 X 22 X 17.2MM

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 32 mm
- External Height: 17.2 mm
- External Width: 22 mm
- External Dimensions: 32 x 22 x 17.2 mm
- IP Rating: IP52
- Colour: Black
- Lid Colour: Black



1920750 ABS

RS PRO BLACK ABS ENCLOSURE, IP52, BLACK LID, 41.8 X 41.8 X 21.5MM

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 41.8 mm
- External Height: 21.5 mm
- External Width: 41.8 mm
- External Dimensions: 41.8 x 41.8 x 21.5 mm
- IP Rating: IP52
- Colour: Black
- Lid Colour: Black



1920754 ABS

RS PRO BLACK ABS ENCLOSURE, IP54, BLACK LID, 52 X 46 X 26MM

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 46 mm
- External Height: 26 mm
- External Width: 52 mm
- External Dimensions: 52 x 46 x 26 mm
- IP Rating: IP54
- Colour: Black
- Lid Colour: Black



1920755 ABS

RS PRO BLACK ABS ENCLOSURE, IP53, IK06, BLACK LID, 185.5 X 136 X

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 185.8 mm
- External Height: 65.3 mm
- External Width: 135.9 mm
- External Dimensions: 185.5 x 136 x 60 mm
- IP Rating: IP53
- Colour: Black
- Lid Colour: Black



1920756 ABS

RS PRO BLACK ABS ENCLOSURE, IP53, IK06, BLACK LID, 185.5 X 136 X

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 184.6 mm
- External Height: 45.5 mm
- External Width: 135.9 mm
- External Dimensions: 185.5 x 136 x 40 mm
- IP Rating: IP53
- Colour: Black
- Lid Colour: Black



1920757 ABS

RS PRO BLACK ABS ENCLOSURE, IP53, IK06, BLACK LID, 185.5 X 136 X

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 185.8 mm
- External Height: 84.8 mm
- External Width: 135.7 mm
- External Dimensions: 185.5 x 136 x 80 mm
- IP Rating: IP53
- Colour: Black
- Lid Colour: Black



1920758 ABS

**RS PRO BLACK ABS ENCLOSURE,
IK04, 105 X 30 X 21.5MM**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 105 mm
- External Height: 21.5 mm
- External Width: 30 mm
- External Dimensions: 105 x 30 x 21.5 mm
- Colour: Black
- IK Rating: IK04

**1920759** ABS**RS PRO BLACK ABS ENCLOSURE,
IP54, IK07, BLACK LID, 149 X 51 X**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 149 mm
- External Height: 24.1 mm
- External Width: 50.5 mm
- External Dimensions: 149 x 51 x 24 mm
- IP Rating: IP54
- Colour: Black
- Lid Colour: Black

**1920762** ABS**RS PRO BLACK ABS ENCLOSURE,
IP54, IK07, BLACK LID, 189.9 X 89.8 X**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 189.9 mm
- External Height: 50.5 mm
- External Width: 89.8 mm
- External Dimensions: 189.9 x 89.8 x 50.5 mm
- IP Rating: IP54
- Colour: Black
- Lid Colour: Black

**1920765** ABS**RS PRO BLACK ABS ENCLOSURE,
IP54, 155 X 49 X 27MM**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 177.4 mm
- External Height: 27 mm
- External Width: 49.4 mm
- External Dimensions: 155 x 49 x 27 mm
- IP Rating: IP54
- Colour: Black
- Flanged: No

**1920776** ABS**RS PRO BLACK ABS ENCLOSURE,
IP40, IK05, 74 X 68 X 36MM**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 74.5 mm
- External Height: 36.2 mm
- External Width: 67.9 mm
- External Dimensions: 74 x 68 x 36 mm
- IP Rating: IP40
- Colour: Black
- Flanged: No

**1920778** ABS**RS PRO BLACK ABS ENCLOSURE,
IP54, 26.45 X 17.25 X 14.6MM**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 26.5 mm
- External Height: 14.6 mm
- External Width: 17.3 mm
- External Dimensions: 26.45 x 17.25 x 14.6 mm
- IP Rating: IP54
- Colour: Black

**1920780** ABS**RS PRO BLACK ABS ENCLOSURE,
IP53, BLACK LID, 66 X 49 X 28MM**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 68.8 mm
- External Height: 27.7 mm
- External Width: 64.7 mm
- External Dimensions: 66 x 49 x 28 mm
- IP Rating: IP53
- Colour: Black
- Lid Colour: Black

**1920786** ABS**RS PRO BLACK ABS ENCLOSURE,
IP53, IK07, 75.9 X 58.8 X 27.9MM**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 75.8 mm
- External Height: 27.9 mm
- External Width: 58.9 mm
- External Dimensions: 75.9 x 58.8 x 27.9 mm
- IP Rating: IP53
- Colour: Black
- Flanged: No

**1920789** ABS**PLASTIC ENCLOSURE Z72 ABS**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 178.9 mm
- External Height: 54.3 mm
- External Width: 102.1 mm
- External Dimensions: 178.9 x 102 x 48.8 mm
- IP Rating: IP53
- Colour: Black
- Flanged: No

**1920791** ABS**RS PRO BLACK ABS ENCLOSURE,
IP55, IK06, 109.2 X 79.15 X 31.9MM**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 109.2 mm
- External Height: 31.9 mm
- External Width: 79.2 mm
- External Dimensions: 109.2 x 79.15 x 31.9 mm
- IP Rating: IP55
- Colour: Black
- IK Rating: IK06

**1920793** ABS**PLASTIC ENCLOSURE Z75 ABS**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 95 mm
- External Height: 23.2 mm
- External Width: 45.3 mm
- External Dimensions: 95 x 45 x 23 mm
- IP Rating: IP54
- Colour: Black
- Shielded: No

**1920794** ABS**PLASTIC ENCLOSURE Z76 ABS**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 109.9 mm
- External Height: 28.3 mm
- External Width: 59.9 mm
- External Dimensions: 109 x 59.5 x 28 mm
- IP Rating: IP54
- Colour: Black
- Shielded: No

**1920795** ABS**PLASTIC ENCLOSURE Z77 ABS**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 124.7 mm
- External Height: 37.1 mm
- External Width: 72 mm
- External Dimensions: 124 x 71.5 x 38 mm
- IP Rating: IP54
- Colour: Black
- Shielded: No

**1920796** ABS**RS PRO BLACK ABS ENCLOSURE,
IP20, IK03, 84.8 X 60.8 X 32MM**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 102 mm
- External Height: 34.7 mm
- External Width: 77.5 mm
- External Dimensions: 84.8 x 60.8 x 32 mm
- IP Rating: IP20
- Colour: Black
- Flanged: No

**1920801** ABS**RS PRO SILVER DIE CAST ALUMINIUM
GENERAL PURPOSE ENCLOSURE,**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 111 mm
- External Height: 31 mm
- External Width: 60 mm
- External Dimensions: 111 x 60 x 31 mm
- IP Rating: IP54
- Colour: Silver
- Lid Colour: Black

**1947613** Die Cast**RS PRO SILVER DIE CAST ALUMINIUM
GENERAL PURPOSE ENCLOSURE,**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 119 mm
- External Height: 56 mm
- External Width: 94 mm
- External Dimensions: 119 x 94 x 56 mm
- IP Rating: IP54
- Colour: Silver
- Lid Colour: Black

**1947614** Die Cast

RS PRO BLACK ABS GENERAL PURPOSE ENCLOSURE, IP54, BLACK

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 75 mm
- Range: General Purpose Moulded Enclosure
- External Height: 27 mm
- External Width: 49 mm
- External Dimensions: 75 x 49 x 27 mm
- IP Rating: IP54
- Colour: Black



1959102 ABS

RS PRO GREY ABS GENERAL PURPOSE ENCLOSURE, IP54, GREY

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 75 mm
- Range: General Purpose Moulded Enclosure
- External Height: 27 mm
- External Width: 49 mm
- External Dimensions: 75 x 49 x 27 mm
- IP Rating: IP54
- Colour: Grey



1959103 ABS

RS PRO BLACK ABS GENERAL PURPOSE ENCLOSURE, IP54, BLACK

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 85 mm
- Range: General Purpose Moulded Enclosure
- External Height: 40 mm
- External Width: 56 mm
- External Dimensions: 85 x 56 x 40 mm
- IP Rating: IP54
- Colour: Black



1959104 ABS

RS PRO GREY ABS GENERAL PURPOSE ENCLOSURE, IP54, GREY

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 85 mm
- Range: General Purpose Moulded Enclosure
- External Height: 40 mm
- External Width: 56 mm
- External Dimensions: 85 x 56 x 40 mm
- IP Rating: IP54
- Colour: Grey



1959106 ABS

RS PRO WHITE ABS GENERAL PURPOSE ENCLOSURE, IP54, WHITE

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 85 mm
- Range: General Purpose Moulded Enclosure
- External Height: 40 mm
- External Width: 56 mm
- External Dimensions: 85 x 56 x 40 mm
- IP Rating: IP54
- Colour: White



1959107 ABS

RS PRO GREY ABS GENERAL PURPOSE ENCLOSURE, IP54, GREY

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 100 mm
- Range: General Purpose Moulded Enclosure
- External Height: 40 mm
- External Width: 50 mm
- External Dimensions: 100 x 50 x 40 mm
- IP Rating: IP54
- Colour: Grey



1959109 ABS

RS PRO BLACK ABS GENERAL PURPOSE ENCLOSURE, IP54, BLACK

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 126 mm
- Range: General Purpose Moulded Enclosure
- External Height: 40 mm
- External Width: 65 mm
- External Dimensions: 126 x 65 x 40 mm
- IP Rating: IP54
- Colour: Black



1959112 ABS

RS PRO GREY ABS GENERAL PURPOSE ENCLOSURE, IP54, GREY

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 120 mm
- Range: General Purpose Moulded Enclosure
- External Height: 40 mm
- External Width: 65 mm
- External Dimensions: 120 x 65 x 40 mm
- IP Rating: IP54
- Colour: Grey



1959114 ABS

RS PRO GREY ABS GENERAL PURPOSE ENCLOSURE, IP54, GREY

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 118 mm
- Range: General Purpose Moulded Enclosure
- External Height: 60 mm
- External Width: 64 mm
- External Dimensions: 118 x 64 x 60 mm
- IP Rating: IP54
- Colour: Grey



1959115 ABS

RS PRO GREY ABS GENERAL PURPOSE ENCLOSURE, IP54, GREY

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 120 mm
- Range: General Purpose Moulded Enclosure
- External Height: 40 mm
- External Width: 65 mm
- External Dimensions: 120 x 65 x 40 mm
- IP Rating: IP54
- Colour: Grey



1959116 ABS

RS PRO BLACK ABS GENERAL PURPOSE ENCLOSURE, IP54, BLACK

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 150 mm
- Range: General Purpose Moulded Enclosure
- External Height: 50 mm
- External Width: 80 mm
- External Dimensions: 150 x 80 x 50 mm
- IP Rating: IP54
- Colour: Black



1959117 ABS

RS PRO GREY ABS GENERAL PURPOSE ENCLOSURE, IP54, GREY

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 150 mm
- Range: General Purpose Moulded Enclosure
- External Height: 50 mm
- External Width: 80 mm
- External Dimensions: 150 x 80 x 50 mm
- IP Rating: IP54
- Colour: Grey



1959118 ABS

RS PRO GREY ABS GENERAL PURPOSE ENCLOSURE, IP54, GREY

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 150 mm
- Range: General Purpose Moulded Enclosure
- External Height: 76 mm
- External Width: 80 mm
- External Dimensions: 150 x 80 x 76 mm
- IP Rating: IP54
- Colour: Grey



1959119 ABS

RS PRO GREY ABS GENERAL PURPOSE ENCLOSURE, IP54, GREY

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 150 mm
- Range: General Purpose Moulded Enclosure
- External Height: 50 mm
- External Width: 80 mm
- External Dimensions: 150 x 80 x 50 mm
- IP Rating: IP54
- Colour: Grey



1959120 ABS

RS PRO BLACK ABS GENERAL PURPOSE ENCLOSURE, IP54, BLACK

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 190 mm
- Range: General Purpose Moulded Enclosure
- External Height: 60 mm
- External Width: 110 mm
- External Dimensions: 190 x 110 x 60 mm
- IP Rating: IP54
- Colour: Black



1959121 ABS

RS PRO GREY ABS GENERAL PURPOSE ENCLOSURE, IP54, GREY

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 190 mm
- Range: General Purpose Moulded Enclosure
- External Height: 60 mm
- External Width: 110 mm
- External Dimensions: 190 x 110 x 60 mm
- IP Rating: IP54
- Colour: Grey



1959122 ABS

RS PRO BLACK ABS GENERAL PURPOSE ENCLOSURE, IP54, BLACKPack size: **1 x EA**

- Body Material: ABS
- External Length: 55 mm
- Range: General Purpose Moulded Enclosure
- External Height: 42 mm
- External Width: 55 mm
- External Dimensions: 55 x 55 x 42 mm
- IP Rating: IP54
- Colour: Black

**1959123** ABS**RS PRO GREY ABS GENERAL PURPOSE ENCLOSURE, IP54, GREY**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 55 mm
- Range: General Purpose Moulded Enclosure
- External Height: 42 mm
- External Width: 55 mm
- External Dimensions: 55 x 55 x 42 mm
- IP Rating: IP54
- Colour: Grey

**1959124** ABS**RS PRO GREY ABS GENERAL PURPOSE ENCLOSURE, IP54, GREY**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 200 mm
- Range: General Purpose Moulded Enclosure
- External Height: 65 mm
- External Width: 250 mm
- External Dimensions: 200 x 250 x 65 mm
- IP Rating: IP54
- Colour: Grey

**1959125** ABS**RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,**Pack size: **1 x EA**

- Body Material: Polycarbonate
- External Length: 95 mm
- External Height: 60 mm
- External Width: 65 mm
- External Dimensions: 95 x 65 x 60 mm
- IP Rating: IP65
- Colour: Grey
- Lid Colour: Grey

**1972005** Polycarbonate**RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,**Pack size: **1 x EA**

- Body Material: Polycarbonate
- External Length: 110 mm
- External Height: 65 mm
- External Width: 110 mm
- External Dimensions: 110 x 110 x 65 mm
- IP Rating: IP65
- Colour: Grey
- Lid Colour: Grey

**1972006** Polycarbonate**RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,**Pack size: **1 x EA**

- Body Material: Polycarbonate
- External Length: 130 mm
- External Height: 65 mm
- External Width: 95 mm
- External Dimensions: 130 x 95 x 65 mm
- IP Rating: IP65
- Colour: Grey
- Lid Colour: Grey

**1972008** Polycarbonate**RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,**Pack size: **1 x EA**

- Body Material: Polycarbonate
- External Length: 130 mm
- External Height: 75 mm
- External Width: 130 mm
- External Dimensions: 130 x 130 x 75 mm
- IP Rating: IP65
- Colour: Grey
- Lid Colour: Grey

**1972009** Polycarbonate**RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,**Pack size: **1 x EA**

- Body Material: Polycarbonate
- External Length: 187 mm
- External Height: 90 mm
- External Width: 122 mm
- External Dimensions: 187 x 122 x 90 mm
- IP Rating: IP65
- Colour: Grey
- Lid Colour: Grey

**1972010** Polycarbonate**RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,**Pack size: **1 x EA**

- Body Material: Polycarbonate
- External Length: 187 mm
- External Height: 90 mm
- External Width: 122 mm
- External Dimensions: 187 x 122 x 90 mm
- IP Rating: IP65
- Colour: Grey
- Lid Colour: Transparent

**1972011** Polycarbonate**RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,**Pack size: **1 x EA**

- Body Material: Polycarbonate
- External Length: 240 mm
- External Height: 107 mm
- External Width: 191 mm
- External Dimensions: 240 x 191 x 107 mm
- IP Rating: IP65
- Colour: Grey
- Lid Colour: Grey

**1972015** Polycarbonate**RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,**Pack size: **1 x EA**

- Body Material: Polycarbonate
- External Length: 240 mm
- External Height: 107 mm
- External Width: 191 mm
- External Dimensions: 240 x 191 x 107 mm
- IP Rating: IP65
- Colour: Grey
- Lid Colour: Transparent

**1972016** Polycarbonate**RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,**Pack size: **1 x EA**

- Body Material: Polycarbonate
- External Length: 289 mm
- External Height: 107 mm
- External Width: 239 mm
- External Dimensions: 289 x 239 x 107 mm
- IP Rating: IP65
- Colour: Grey
- Lid Colour: Grey

**1972017** Polycarbonate**RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,**Pack size: **1 x EA**

- Body Material: Polycarbonate
- External Length: 289 mm
- External Height: 107 mm
- External Width: 239 mm
- External Dimensions: 289 x 239 x 107 mm
- IP Rating: IP65
- Colour: Grey
- Lid Colour: Transparent

**1972018** Polycarbonate**RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,**Pack size: **1 x EA**

- Body Material: Polycarbonate
- External Length: 344 mm
- External Height: 117 mm
- External Width: 289 mm
- External Dimensions: 344 x 289 x 117 mm
- IP Rating: IP65
- Colour: Grey
- Lid Colour: Grey

**1972019** Polycarbonate**RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,**Pack size: **1 x EA**

- Body Material: Polycarbonate
- External Length: 344 mm
- External Height: 117 mm
- External Width: 289 mm
- External Dimensions: 344 x 289 x 117 mm
- IP Rating: IP65
- Colour: Grey
- Lid Colour: Transparent

**1972020** Polycarbonate**RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,**Pack size: **1 x EA**

- Body Material: Polycarbonate
- External Length: 95 mm
- External Height: 60 mm
- External Width: 65 mm
- External Dimensions: 95 x 65 x 60 mm
- IP Rating: IP65
- Colour: Grey
- Lid Colour: Grey

**1972021** Polycarbonate

RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,

Pack size: **1 x EA**

- Body Material: Polycarbonate
- External Length: 110 mm
- External Height: 65 mm
- External Width: 110 mm
- External Dimensions: 110 x 110 x 65 mm
- IP Rating: IP65
- Colour: Grey
- Lid Colour: Grey



1972022 Polycarbonate

RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,

Pack size: **1 x EA**

- Body Material: Polycarbonate
- External Length: 130 mm
- External Height: 75 mm
- External Width: 130 mm
- External Dimensions: 130 x 130 x 75 mm
- IP Rating: IP65
- Colour: Grey
- Lid Colour: Grey



1972024 Polycarbonate

RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,

Pack size: **1 x EA**

- Body Material: Polycarbonate
- External Length: 187 mm
- External Height: 90 mm
- External Width: 122 mm
- External Dimensions: 187 x 122 x 90 mm
- IP Rating: IP65
- Colour: Grey
- Lid Colour: Grey



1972025 Polycarbonate

RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,

Pack size: **1 x EA**

- Body Material: Polycarbonate
- External Length: 187 mm
- External Height: 90 mm
- External Width: 122 mm
- External Dimensions: 187 x 122 x 90 mm
- IP Rating: IP65
- Colour: Grey
- Lid Colour: Transparent



1972026 Polycarbonate

RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,

Pack size: **1 x EA**

- Body Material: Polycarbonate
- External Length: 201 mm
- External Height: 98 mm
- External Width: 163 mm
- External Dimensions: 201 x 163 x 98 mm
- IP Rating: IP65
- Colour: Grey
- Lid Colour: Grey



1972027 Polycarbonate

RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,

Pack size: **1 x EA**

- Body Material: Polycarbonate
- External Length: 201 mm
- External Height: 98 mm
- External Width: 163 mm
- External Dimensions: 201 x 163 x 98 mm
- IP Rating: IP65
- Colour: Grey
- Lid Colour: Transparent



1972028 Polycarbonate

RS PRO WHITE POLYCARBONATE GENERAL PURPOSE ENCLOSURE,

Pack size: **1 x EA**

- Body Material: Polycarbonate
- Range: Z8
- External Length: 45.9 mm
- External Height: 22 mm
- External Width: 35.2 mm
- External Dimensions: 45.9 x 35.2 x 22 mm
- IP Rating: IP52
- Colour: White



2006660 Polycarbonate

RS PRO LIGHT GREY POLYCARBONATE ENCLOSURE, IP53,

Pack size: **1 x EA**

- Body Material: Polycarbonate
- Range: Z7
- External Length: 178.9 mm
- External Height: 48.8 mm
- External Width: 102 mm
- External Dimensions: 178.85 x 102 x 48.8 mm
- IP Rating: IP53
- Colour: Light Grey



2006698 Polycarbonate

PLASTIC ENCLOSURE Z73 LIGHTGRAY ABS

Pack size: **1 x EA**

- Body Material: Polycarbonate
- Range: Z7
- External Length: 109.2 mm
- External Height: 31.9 mm
- External Width: 79.2 mm
- External Dimensions: 109.2 x 79.2 x 31.9 mm
- IP Rating: IP65
- Colour: Light Grey



2006700 Polycarbonate

RS PRO LIGHT GREY POLYCARBONATE ENCLOSURE, IP53,

Pack size: **1 x EA**

- Body Material: Polycarbonate
- Range: Z7
- External Length: 154 mm
- External Height: 42.5 mm
- External Width: 84.5 mm
- External Dimensions: 154 x 84.5 x 42.5 mm
- IP Rating: IP63
- Colour: Light Grey



2006704 Polycarbonate

RS PRO LIGHT GREY POLYCARBONATE ENCLOSURE, IP54,

Pack size: **1 x EA**

- Body Material: Polycarbonate
- Range: Z7
- External Length: 90 mm
- External Height: 38 mm
- External Width: 80 mm
- External Dimensions: 90 x 80 x 38 mm
- IP Rating: IP54
- Colour: Light Grey



2006705 Polycarbonate

PLASTIC ENCLOSURE Z112B LIGHTGRAY ABS

Pack size: **1 x EA**

- Body Material: Polycarbonate
- Range: Z11
- External Length: 185.5 mm
- External Height: 80 mm
- External Width: 136 mm
- External Dimensions: 185.5 x 136 x 80 mm
- IP Rating: IP53
- Colour: Light Grey



2006718 Polycarbonate

RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,

Pack size: **1 x EA**

- Body Material: Polycarbonate
- External Length: 52 mm
- Range: 5U2
- External Height: 35 mm
- External Width: 50 mm
- External Dimensions: 50 x 52 x 35 mm
- IP Rating: IP66
- Colour: Grey



2010129 Polycarbonate

RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,

Pack size: **1 x EA**

- Body Material: Polycarbonate
- External Length: 65 mm
- Range: 5U2
- External Height: 35 mm
- External Width: 50 mm
- External Dimensions: 50 x 65 x 35 mm
- IP Rating: IP66
- Colour: Grey



2010130 Polycarbonate

RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,

Pack size: **1 x EA**

- Body Material: Polycarbonate
- External Length: 98 mm
- Range: 5U2
- External Height: 36.4 mm
- External Width: 64 mm
- External Dimensions: 64 x 98 x 36.4 mm
- IP Rating: IP66
- Colour: Grey



2010131 Polycarbonate

RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,

Pack size: **1 x EA**

- Body Material: Polycarbonate
- External Length: 82 mm
- Range: 5U2
- External Height: 55 mm
- External Width: 80 mm
- External Dimensions: 80 x 82 x 55 mm
- IP Rating: IP66
- Colour: Grey



2010132 Polycarbonate

RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,

Pack size: **1 x EA**

- Body Material: Polycarbonate
- External Length: 160 mm
- Range: 5U2
- External Height: 90 mm
- External Width: 120 mm
- External Dimensions: 120 x 160 x 90 mm
- IP Rating: IP66
- Colour: Grey



2010156 Polycarbonate

RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,

Pack size: **1 x EA**

- Body Material: Polycarbonate
- External Length: 160 mm
- Range: 5U2
- External Height: 75 mm
- External Width: 120 mm
- External Dimensions: 120 x 160 x 75 mm
- IP Rating: IP66
- Colour: Grey



2010157 Polycarbonate

RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,

Pack size: **1 x EA**

- Body Material: Polycarbonate
- External Length: 160 mm
- Range: 5U2
- External Height: 90 mm
- External Width: 120 mm
- External Dimensions: 120 x 160 x 90 mm
- IP Rating: IP66
- Colour: Grey



2010158 Polycarbonate

RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,

Pack size: **1 x EA**

- Body Material: Polycarbonate
- External Length: 250 mm
- Range: 5U2
- External Height: 90 mm
- External Width: 160 mm
- External Dimensions: 160 x 250 x 90 mm
- IP Rating: IP66
- Colour: Grey



2010159 Polycarbonate

RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,

Pack size: **1 x EA**

- Body Material: Polycarbonate
- External Length: 240.3 mm
- Range: 5U2
- External Height: 90 mm
- External Width: 160.3 mm
- External Dimensions: 160 x 240.3 x 90 mm
- IP Rating: IP66
- Colour: Grey



2010160 Polycarbonate

RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,

Pack size: **1 x EA**

- Body Material: Polycarbonate
- External Length: 240.3 mm
- Range: 5U2
- External Height: 90 mm
- External Width: 160.3 mm
- External Dimensions: 160.3 x 240.3 x 90 mm
- IP Rating: IP66
- Colour: Grey



2010161 Polycarbonate

RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,

Pack size: **1 x EA**

- Body Material: Polycarbonate
- External Length: 250 mm
- Range: 5U2
- External Height: 119 mm
- External Width: 160 mm
- External Dimensions: 160 x 250 x 119 mm
- IP Rating: IP66
- Colour: Grey



2010162 Polycarbonate

RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,

Pack size: **1 x EA**

- Body Material: Polycarbonate
- External Length: 240.5 mm
- Range: 5U2
- External Height: 100.5 mm
- External Width: 120 mm
- External Dimensions: 120 x 240.5 x 100.5 mm
- IP Rating: IP66
- Colour: Grey



2010163 Polycarbonate

RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,

Pack size: **1 x EA**

- Body Material: Polycarbonate
- External Length: 240.3 mm
- Range: 5U2
- External Height: 120 mm
- External Width: 160.3 mm
- External Dimensions: 160 x 240.3 x 120 mm
- IP Rating: IP66
- Colour: Grey



2010164 Polycarbonate

RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,

Pack size: **1 x EA**

- Body Material: Polycarbonate
- External Length: 160 mm
- Range: 5U2
- External Height: 140 mm
- External Width: 120 mm
- External Dimensions: 120 x 160 x 140 mm
- IP Rating: IP66
- Colour: Grey



2010165 Polycarbonate

RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,

Pack size: **1 x EA**

- Body Material: Polycarbonate
- External Length: 360 mm
- Range: 5U2
- External Height: 100 mm
- External Width: 160 mm
- External Dimensions: 160 x 360 x 100 mm
- IP Rating: IP66
- Colour: Grey



2010167 Polycarbonate

RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,

Pack size: **1 x EA**

- Body Material: Polycarbonate
- External Length: 300 mm
- Range: 5U2
- External Height: 85 mm
- External Width: 230 mm
- External Dimensions: 230 x 300 x 85 mm
- IP Rating: IP66
- Colour: Grey



2010168 Polycarbonate

RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,

Pack size: **1 x EA**

- Body Material: Polycarbonate
- External Length: 300 mm
- Range: 5U2
- External Height: 85 mm
- External Width: 230 mm
- External Dimensions: 230 x 300 x 85 mm
- IP Rating: IP66
- Colour: Grey



2010169 Polycarbonate

RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,

Pack size: **1 x EA**

- Body Material: Polycarbonate
- External Length: 300 mm
- Range: 5U2
- External Height: 110 mm
- External Width: 230 mm
- External Dimensions: 230 x 300 x 110 mm
- IP Rating: IP66
- Colour: Grey



2010170 Polycarbonate

RS PRO GREY POLYCARBONATE GENERAL PURPOSE ENCLOSURE,

Pack size: **1 x EA**

- Body Material: Polycarbonate
- External Length: 360 mm
- Range: 5U2
- External Height: 149.5 mm
- External Width: 200 mm
- External Dimensions: 200 x 360 x 149.5 mm
- IP Rating: IP66
- Colour: Grey



2010171 Polycarbonate

RS PRO GREY ABS GENERAL PURPOSE ENCLOSURE, IP66, IK07,

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 52 mm
- Range: 5U3
- External Height: 35 mm
- External Width: 50 mm
- External Dimensions: 50 x 52 x 35 mm
- IP Rating: IP66
- Colour: Grey



2010172 ABS

**RS PRO GREY ABS GENERAL
PURPOSE ENCLOSURE, IP66, IK07,**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 65 mm
- Range: 5U3
- External Height: 35 mm
- External Width: 50 mm
- External Dimensions: 50 x 65 x 35 mm
- IP Rating: IP66
- Colour: Grey

**2010173** ABS**RS PRO GREY ABS GENERAL
PURPOSE ENCLOSURE, IP66, IK07,**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 98 mm
- Range: 5U3
- External Height: 36.4 mm
- External Width: 64 mm
- External Dimensions: 64 x 98 x 36.4 mm
- IP Rating: IP66
- Colour: Grey

**2010174** ABS**RS PRO GREY ABS GENERAL
PURPOSE ENCLOSURE, IP66, IK07,**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 82 mm
- Range: 5U3
- External Height: 55 mm
- External Width: 80 mm
- External Dimensions: 80 x 82 x 55 mm
- IP Rating: IP66
- Colour: Grey

**2010175** ABS**RS PRO GREY ABS GENERAL
PURPOSE ENCLOSURE, IP66, IK07,**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 120 mm
- Range: 5U3
- External Height: 55 mm
- External Width: 80 mm
- External Dimensions: 80 x 120 x 55 mm
- IP Rating: IP66
- Colour: Grey

**2010176** ABS**RS PRO GREY ABS GENERAL
PURPOSE ENCLOSURE, IP66, IK07,**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 122 mm
- Range: 5U3
- External Height: 55 mm
- External Width: 120 mm
- External Dimensions: 120 x 122 x 55 mm
- IP Rating: IP66
- Colour: Grey

**2010177** ABS**RS PRO GREY ABS GENERAL
PURPOSE ENCLOSURE, IP66, IK07,**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 160 mm
- Range: 5U3
- External Height: 60 mm
- External Width: 80 mm
- External Dimensions: 80 x 160 x 60 mm
- IP Rating: IP66
- Colour: Grey

**2010178** ABS**RS PRO GREY ABS GENERAL
PURPOSE ENCLOSURE, IP66, IK07,**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 160 mm
- Range: 5U3
- External Height: 55 mm
- External Width: 80 mm
- External Dimensions: 160 x 80 x 55 mm
- IP Rating: IP66
- Colour: Grey

**2010179** ABS**RS PRO GREY ABS GENERAL
PURPOSE ENCLOSURE, IP66, IK07,**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 200 mm
- Range: 5U3
- External Height: 75 mm
- External Width: 120 mm
- External Dimensions: 120 x 200 x 75 mm
- IP Rating: IP66
- Colour: Grey

**2010180** ABS**RS PRO GREY ABS GENERAL
PURPOSE ENCLOSURE, IP66, IK07,**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 200 mm
- Range: 5U3
- External Height: 75 mm
- External Width: 120 mm
- External Dimensions: 150 x 200 x 75 mm
- IP Rating: IP66
- Colour: Grey

**2010181** ABS**RS PRO GREY ABS GENERAL
PURPOSE ENCLOSURE, IP66, IK07,**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 82 mm
- Range: 5U3
- External Height: 85 mm
- External Width: 80 mm
- External Dimensions: 80 x 82 x 85 mm
- IP Rating: IP66
- Colour: Grey

**2010182** ABS**RS PRO GREY ABS GENERAL
PURPOSE ENCLOSURE, IP66, IK07,**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 120 mm
- Range: 5U3
- External Height: 85 mm
- External Width: 80 mm
- External Dimensions: 80 x 120 x 85 mm
- IP Rating: IP66
- Colour: Grey

**2010183** ABS**RS PRO GREY ABS GENERAL
PURPOSE ENCLOSURE, IP66, IK07,**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 122 mm
- Range: 5U3
- External Height: 85 mm
- External Width: 120 mm
- External Dimensions: 120 x 122 x 85 mm
- IP Rating: IP66
- Colour: Grey

**2010184** ABS**RS PRO GREY ABS GENERAL
PURPOSE ENCLOSURE, IP66, IK07,**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 120 mm
- Range: 5U3
- External Height: 105 mm
- External Width: 120 mm
- External Dimensions: 120 x 122 x 105 mm
- IP Rating: IP66
- Colour: Grey

**2010185** ABS**RS PRO GREY ABS GENERAL
PURPOSE ENCLOSURE, IP66, IK07,**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 120 mm
- Range: 5U3
- External Height: 90 mm
- External Width: 80 mm
- External Dimensions: 80 x 120 x 90 mm
- IP Rating: IP66
- Colour: Grey

**2010186** ABS**RS PRO GREY ABS GENERAL
PURPOSE ENCLOSURE, IP66, IK07,**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 160 mm
- Range: 5U3
- External Height: 85 mm
- External Width: 80 mm
- External Dimensions: 80 x 160 x 85 mm
- IP Rating: IP66
- Colour: Grey

**2010187** ABS**RS PRO GREY ABS GENERAL
PURPOSE ENCLOSURE, IP66, IK07,**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 160 mm
- Range: 5U3
- External Height: 90 mm
- External Width: 80 mm
- External Dimensions: 80 x 160 x 90 mm
- IP Rating: IP66
- Colour: Grey

**2010189** ABS

RS PRO GREY ABS GENERAL PURPOSE ENCLOSURE, IP66, IK07,

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 200 mm
- Range: 5U3
- External Height: 90 mm
- External Width: 120 mm
- External Dimensions: 120 x 200 x 90 mm
- IP Rating: IP66
- Colour: Grey



2010190 ABS

RS PRO GREY ABS GENERAL PURPOSE ENCLOSURE, IP66, IK07,

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 160 mm
- Range: 5U3
- External Height: 90 mm
- External Width: 120 mm
- External Dimensions: 120 x 160 x 90 mm
- IP Rating: IP66
- Colour: Grey



2010191 ABS

RS PRO GREY ABS GENERAL PURPOSE ENCLOSURE, IP66, IK07,

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 160 mm
- Range: 5U3
- External Height: 75 mm
- External Width: 120 mm
- External Dimensions: 120 x 160 x 75 mm
- IP Rating: IP66
- Colour: Grey



2010192 ABS

RS PRO GREY ABS GENERAL PURPOSE ENCLOSURE, IP66, IK07,

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 250 mm
- Range: 5U3
- External Height: 90 mm
- External Width: 160 mm
- External Dimensions: 160 x 250 x 90 mm
- IP Rating: IP66
- Colour: Grey



2010193 ABS

RS PRO GREY ABS GENERAL PURPOSE ENCLOSURE, IP66, IK07,

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 240.3 mm
- Range: 5U3
- External Height: 90 mm
- External Width: 160.3 mm
- External Dimensions: 160 x 240.3 x 90 mm
- IP Rating: IP66
- Colour: Grey



2010195 ABS

RS PRO GREY ABS GENERAL PURPOSE ENCLOSURE, IP66, IK07,

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 250 mm
- Range: 5U3
- External Height: 119 mm
- External Width: 160 mm
- External Dimensions: 160 x 250 x 119 mm
- IP Rating: IP66
- Colour: Grey



2010196 ABS

RS PRO GREY ABS GENERAL PURPOSE ENCLOSURE, IP66, IK07,

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 240.5 mm
- Range: 5U3
- External Height: 100.5 mm
- External Width: 120 mm
- External Dimensions: 120 x 240.5 x 100.5 mm
- IP Rating: IP66
- Colour: Grey



2010197 ABS

RS PRO GREY ABS GENERAL PURPOSE ENCLOSURE, IP66, IK07,

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 240.3 mm
- Range: 5U3
- External Height: 120 mm
- External Width: 160.3 mm
- External Dimensions: 160.3 x 240.3 x 120 mm
- IP Rating: IP66
- Colour: Grey



2010198 ABS

RS PRO GREY ABS GENERAL PURPOSE ENCLOSURE, IP65, IK07,

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 234 mm
- Range: 5U3
- External Height: 100 mm
- External Width: 150 mm
- External Dimensions: 150 x 234 x 100 mm
- IP Rating: IP65
- Colour: Grey



2010199 ABS

RS PRO GREY ABS GENERAL PURPOSE ENCLOSURE, IP66, IK07,

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 340 mm
- Range: 5U3
- External Height: 120 mm
- External Width: 150 mm
- External Dimensions: 150 x 340 x 120 mm
- IP Rating: IP66
- Colour: Grey



2010200 ABS

RS PRO GREY ABS GENERAL PURPOSE ENCLOSURE, IP66, IK07,

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 160 mm
- Range: 5U3
- External Height: 140 mm
- External Width: 120 mm
- External Dimensions: 120 x 160 x 140 mm
- IP Rating: IP66
- Colour: Grey



2010202 ABS

RS PRO GREY ABS GENERAL PURPOSE ENCLOSURE, IP66, IK07,

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 250 mm
- Range: 5U3
- External Height: 150 mm
- External Width: 160 mm
- External Dimensions: 160 x 250 x 150 mm
- IP Rating: IP66
- Colour: Grey



2010203 ABS

RS PRO GREY ABS GENERAL PURPOSE ENCLOSURE, IP66, IK07,

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 360 mm
- Range: 5U3
- External Height: 100 mm
- External Width: 160 mm
- External Dimensions: 160 x 360 x 100 mm
- IP Rating: IP66
- Colour: Grey



2010204 ABS

RS PRO GREY ABS GENERAL PURPOSE ENCLOSURE, IP65, IK07,

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 300 mm
- Range: 5U3
- External Height: 85 mm
- External Width: 230 mm
- External Dimensions: 230 x 300 x 85 mm
- IP Rating: IP65
- Colour: Grey



2010205 ABS

RS PRO GREY ABS GENERAL PURPOSE ENCLOSURE, IP65, IK07,

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 300 mm
- Range: 5U3
- External Height: 110 mm
- External Width: 230 mm
- External Dimensions: 230 x 300 x 110 mm
- IP Rating: IP65
- Colour: Grey



2010206 ABS

RS PRO GREY ABS GENERAL PURPOSE ENCLOSURE, IP66, IK07,

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 360 mm
- Range: 5U3
- External Height: 149.5 mm
- External Width: 200 mm
- External Dimensions: 200 x 360 x 149.5 mm
- IP Rating: IP66
- Colour: Grey



2010207 ABS

WHITE ABS GENERAL PURPOSE ENCLOSURE, IP20, IK06, WHITE LID,Pack size: **1 x EA**

- Body Material: ABS
- External Length: 100 mm
- External Height: 35.3 mm
- External Width: 100 mm
- External Dimensions: 100 x 100 x 35.3 mm
- IP Rating: IP20
- Colour: White
- Lid Colour: White

**2069055** ABS**RS PRO LIGHT GREY POLYCARBONATE ENCLOSURE, IP65,**Pack size: **1 x EA**

- Body Material: Polycarbonate
- External Length: 121.4 mm
- External Height: 45.2 mm
- External Width: 81.6 mm
- External Dimensions: 121.4 x 81.6 x 45.2 mm
- IP Rating: IP65
- Colour: Light Grey
- Lid Colour: Light Grey

**2069086** Polycarbonate**RS PRO LIGHT GREY ABS, POLYCARBONATE ENCLOSURE, IP65,**Pack size: **1 x EA**

- Body Material: ABS, Polycarbonate
- External Length: 121.4 mm
- External Height: 45.2 mm
- External Width: 81.6 mm
- External Dimensions: 121.4 x 81.6 x 45.2 mm
- IP Rating: IP65
- Colour: Light Grey
- Lid Colour: Transparent

**2069087** ABS,**RS PRO LIGHT GREY ABS ENCLOSURE, IP65, LIGHT GREY LID,**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 120 mm
- External Height: 60.2 mm
- External Width: 80 mm
- External Dimensions: 120 x 80 x 60.2 mm
- IP Rating: IP65
- Colour: Light Grey
- Lid Colour: Light Grey

**2069090** ABS**LIGHT GREY ABS, POLYCARBONATE ENCLOSURE, IP65, TRANSPARENT LID,**Pack size: **1 x EA**

- Body Material: ABS, Polycarbonate
- External Length: 121.4 mm
- External Height: 60.2 mm
- External Width: 81.6 mm
- External Dimensions: 121.4 x 81.6 x 60.2 mm
- IP Rating: IP65
- Colour: Light Grey
- Lid Colour: Transparent

**2069092** ABS,**RS PRO LIGHT GREY ABS ENCLOSURE, IP65, FLANGED, LIGHT**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 121.4 mm
- External Height: 60.2 mm
- External Width: 81.6 mm
- External Dimensions: 121.4 x 81.6 x 60.2 mm
- IP Rating: IP65
- Colour: Light Grey
- Lid Colour: Light Grey

**2069094** ABS**LIGHT GREY POLYCARBONATE ENCLOSURE, IP65, FLANGED, LIGHT**Pack size: **1 x EA**

- Body Material: Polycarbonate
- External Length: 121.4 mm
- External Height: 60.2 mm
- External Width: 81.6 mm
- External Dimensions: 121.4 x 81.6 x 60.2 mm
- IP Rating: IP65
- Colour: Light Grey
- Lid Colour: Light Grey

**2069096** Polycarbonate**RS PRO LIGHT GREY ABS, POLYCARBONATE ENCLOSURE, IP65,**Pack size: **1 x EA**

- Body Material: ABS, Polycarbonate
- External Length: 121.4 mm
- External Height: 60.2 mm
- External Width: 81.6 mm
- External Dimensions: 121.4 x 81.6 x 60.2 mm
- IP Rating: IP65
- Colour: Light Grey
- Lid Colour: Transparent

**2069097** ABS,**RS PRO LIGHT GREY POLYCARBONATE ENCLOSURE, IP65,**Pack size: **1 x EA**

- Body Material: Polycarbonate
- External Length: 121.4 mm
- External Height: 60.2 mm
- External Width: 81.6 mm
- External Dimensions: 121.4 x 81.6 x 60.2 mm
- IP Rating: IP65
- Colour: Light Grey
- Lid Colour: Transparent

**2069098** Polycarbonate**LIGHT GREY ABS ENCLOSURE, IP65, LIGHT GREY LID, 120 X 80 X 75.2MM**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 120 mm
- External Height: 75.2 mm
- External Width: 80 mm
- External Dimensions: 120 x 80 x 75.2 mm
- IP Rating: IP65
- Colour: Light Grey
- Lid Colour: Light Grey

**2069099** ABS**LIGHT GREY ABS, POLYCARBONATE ENCLOSURE, IP65, TRANSPARENT LID,**Pack size: **1 x EA**

- Body Material: ABS, Polycarbonate
- External Length: 120 mm
- External Height: 75.2 mm
- External Width: 80 mm
- External Dimensions: 120 x 80 x 75.2 mm
- IP Rating: IP65
- Colour: Light Grey
- Lid Colour: Transparent

**2069101** ABS,**LIGHT GREY POLYCARBONATE ENCLOSURE, IP65, 191.3 X 240 X**Pack size: **1 x SET**

- Body Material: Polycarbonate
- External Length: 191.3 mm
- External Height: 105.7 mm
- External Width: 240 mm
- External Dimensions: 191.3 x 240 x 105.7 mm
- IP Rating: IP65
- Colour: Light Grey
- Flanged: No

**2069105** Polycarbonate**RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP66, IK09, GREY LID, 91**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 91 mm
- External Height: 120 mm
- External Width: 220 mm
- External Dimensions: 91 x 220 x 120 mm
- IP Rating: IP66
- Colour: Grey
- Lid Colour: Grey

**2131641** Die Cast**RS PRO BLACK FIBREGLASS REINFORCED POLYESTER**Pack size: **1 x EA**

- Body Material: Fibreglass Reinforced Polyester
- External Length: 91 mm
- External Height: 120 mm
- External Width: 122 mm
- External Dimensions: 91 x 122 x 120 mm
- IP Rating: IP66
- Colour: Black
- Lid Colour: Black

**2131649** Fibreglass**RS PRO BLACK FIBREGLASS REINFORCED POLYESTER**Pack size: **1 x EA**

- Body Material: Fibreglass Reinforced Polyester
- External Length: 91 mm
- External Height: 160 mm
- External Width: 160 mm
- External Dimensions: 91 x 160 x 160 mm
- IP Rating: IP66
- Colour: Black
- Lid Colour: Black

**2131651** Fibreglass**ROSE STAINLESS STEEL RMS ENCLOSURES WITH**Pack size: **1 x EA**

- Body Material: 304 Stainless Steel
- External Height: 200 mm
- External Width: 200 mm
- IP Rating: IP66, IP69
- Colour: Steel
- Transparent Door: No

**2134044** 304 Stainless

ROSE STAINLESS STEEL RMS ENCLOSURES WITH

Pack size: **1 x EA**

- Body Material: 304 Stainless Steel
- External Height: 600 mm
- External Width: 300 mm
- IP Rating: IP66, IP69
- Colour: Steel
- Transparent Door: No



2134081 304 Stainless

ROSE STAINLESS STEEL RMS ENCLOSURES WITH

Pack size: **1 x EA**

- Body Material: 304 Stainless Steel
- External Height: 500 mm
- External Width: 400 mm
- IP Rating: IP66, IP69
- Colour: Steel
- Transparent Door: No



2134082 304 Stainless

ROSE STAINLESS STEEL RMS ENCLOSURES WITH

Pack size: **1 x EA**

- Body Material: 304 Stainless Steel
- External Height: 500 mm
- External Width: 500 mm
- IP Rating: IP66, IP69
- Colour: Steel
- Transparent Door: No



2134087 304 Stainless

ROSE STAINLESS STEEL RMS ENCLOSURES WITH

Pack size: **1 x EA**

- Body Material: 304 Stainless Steel
- External Height: 200 mm
- External Width: 200 mm
- IP Rating: IP66, IP69
- Colour: Steel
- Transparent Door: No



2134089 304 Stainless

ROSE STAINLESS STEEL RMS ENCLOSURES WITH

Pack size: **1 x EA**

- Body Material: 304 Stainless Steel
- External Height: 300 mm
- External Width: 600 mm
- IP Rating: IP66, IP69
- Colour: Steel
- Transparent Door: No



2134090 304 Stainless

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP65, SILVER LID, 71 X 110

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 71 mm
- External Height: 135 mm
- External Width: 110 mm
- External Dimensions: 71 x 110 x 135 mm
- IP Rating: IP65
- Colour: Silver
- Lid Colour: Silver



2290334 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP65, SILVER LID, 81 X

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 81 mm
- External Height: 160 mm
- External Width: 135 mm
- External Dimensions: 81 x 135 x 160 mm
- IP Rating: IP65
- Colour: Silver
- Lid Colour: Silver



2290362 Die Cast

RS PRO BLACK ABS ENCLOSURE, BLACK LID, 88.9 X 63.5 X 32.39MM

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 88.9 mm
- External Height: 32.4 mm
- External Width: 63.5 mm
- External Dimensions: 88.9 x 63.5 x 32.39 mm
- Colour: Black
- Lid Colour: Black
- Flanged: No



2374331 ABS

RS PRO BLACK ABS ENCLOSURE, FLANGED, BLACK LID, 88 X 63 X

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 111.8 mm
- External Height: 28.6 mm
- External Width: 63.5 mm
- External Dimensions: 88 x 63 x 29 mm
- Colour: Black
- Lid Colour: Black
- Flanged: Yes



2374347 ABS

RS PRO ABS ENCLOSURE, 60 X 100 X 150MM

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 150 mm
- External Height: 60 mm
- External Width: 100 mm
- External Dimensions: 60 x 100 x 150 mm



2384026 ABS

RS PRO POLYCARBONATE ENCLOSURE, 75 X 100 X 150MM

Pack size: **1 x EA**

- Body Material: Polycarbonate
- External Length: 150 mm
- External Height: 75 mm
- External Width: 100 mm
- External Dimensions: 75 x 100 x 150 mm



2384034 Polycarbonate

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP66, GREY LID, 127 X

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 127 mm
- External Height: 90 mm
- External Width: 125 mm
- External Dimensions: 127 x 125 x 90 mm
- IP Rating: IP66
- Colour: Grey
- Lid Colour: Grey



2433682 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP66, GREY LID, 166 X

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 166 mm
- External Height: 100 mm
- External Width: 166 mm
- External Dimensions: 166 x 166 x 100 mm
- IP Rating: IP66
- Colour: Grey
- Lid Colour: Grey



2433711 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP65, SILVER LID, 73 X

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 73 mm
- External Height: 102 mm
- External Width: 102 mm
- External Dimensions: 73 x 102 x 102 mm
- IP Rating: IP65
- Colour: Silver
- Lid Colour: Silver



2821102 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP65, GREY LID, 87 X 87

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 87 mm
- External Height: 61 mm
- External Width: 87 mm
- External Dimensions: 87 x 87 x 61 mm
- IP Rating: IP65
- Colour: Grey
- Lid Colour: Grey



2821152 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP65, GREY LID, 102 X

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 102 mm
- External Height: 61 mm
- External Width: 102 mm
- External Dimensions: 102 x 102 x 61 mm
- IP Rating: IP65
- Colour: Grey
- Lid Colour: Grey



2821168 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP65, GREY LID, 102 XPack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 102 mm
- External Height: 81 mm
- External Width: 102 mm
- External Dimensions: 102 x 102 x 81 mm
- IP Rating: IP65
- Colour: Grey
- Lid Colour: Grey

**2821180** Die Cast**RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP65, GREY LID, 122 X 75**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 122 mm
- External Height: 61 mm
- External Width: 75 mm
- External Dimensions: 122 x 75 x 61 mm
- IP Rating: IP65
- Colour: Grey
- Lid Colour: Grey

**2821196** Die Cast**RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP65, GREY LID, 122 X 75**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 122 mm
- External Height: 75 mm
- External Width: 75 mm
- External Dimensions: 122 x 75 x 75 mm
- IP Rating: IP65
- Colour: Grey
- Lid Colour: Grey

**2821203** Die Cast**RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP65, GREY LID, 202 X**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 202 mm
- External Height: 61 mm
- External Width: 102 mm
- External Dimensions: 202 x 102 x 61 mm
- IP Rating: IP65
- Colour: Grey
- Lid Colour: Grey

**2821219** Die Cast**RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP65, GREY LID, 202 X**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 202 mm
- External Height: 81 mm
- External Width: 102 mm
- External Dimensions: 202 x 102 x 81 mm
- IP Rating: IP65
- Colour: Grey
- Lid Colour: Grey

**2821225** Die Cast**RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP65, GREY LID, 252 X**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 252 mm
- External Height: 61 mm
- External Width: 87 mm
- External Dimensions: 252 x 87 x 61 mm
- IP Rating: IP65
- Colour: Grey
- Lid Colour: Grey

**2821247** Die Cast**RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP65, GREY LID, 252 X**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 252 mm
- External Height: 75 mm
- External Width: 87 mm
- External Dimensions: 252 x 87 x 75 mm
- IP Rating: IP65
- Colour: Grey
- Lid Colour: Grey

**2821253** Die Cast**RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP65, GREY LID, 262 X**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 262 mm
- External Height: 91 mm
- External Width: 127 mm
- External Dimensions: 262 x 127 x 91 mm
- IP Rating: IP65
- Colour: Grey
- Lid Colour: Grey

**2821269** Die Cast**RS PRO BLACK ABS ENCLOSURE, BLACK LID, 177.8 X 127 X 76.2MM**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 177.8 mm
- External Height: 76.2 mm
- External Width: 127 mm
- External Dimensions: 177.8 x 127 x 76.2 mm
- Colour: Black
- Lid Colour: Black
- Flanged: No

**2876433** ABS**RS PRO BLACK ABS ENCLOSURE, FLANGED, BLACK LID, 200.86 X 127 X**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 200.9 mm
- External Height: 76.2 mm
- External Width: 127 mm
- External Dimensions: 200.86 x 127 x 76.2 mm
- Colour: Black
- Lid Colour: Black
- Flanged: Yes

**2876483** ABS**RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP65, GREY LID, 152 X**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 152 mm
- External Height: 81 mm
- External Width: 102 mm
- External Dimensions: 152 x 102 x 81 mm
- IP Rating: IP65
- Colour: Grey
- Lid Colour: Grey

**4349882** Die Cast**RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP65, GREY LID, 130 X**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 130 mm
- External Height: 91 mm
- External Width: 130 mm
- External Dimensions: 130 x 130 x 91 mm
- IP Rating: IP65
- Colour: Grey
- Lid Colour: Grey

**4349898** Die Cast**RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP66, FLANGED, GREY**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 202 mm
- External Height: 54.9 mm
- External Width: 120.8 mm
- External Dimensions: 202 x 120.8 x 54.9 mm
- IP Rating: IP66
- Colour: Grey
- Lid Colour: Grey

**4799984** Die Cast**RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, SILVER LID, 222.1 X 145.9**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 222.1 mm
- External Height: 55.9 mm
- External Width: 145.9 mm
- External Dimensions: 222.1 x 145.9 x 55.9 mm
- Colour: Silver
- Lid Colour: Silver
- Flanged: No

**5173260** Die Cast**RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, SILVER LID, 114.5 X 63.6**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 114.5 mm
- External Height: 30.3 mm
- External Width: 63.6 mm
- External Dimensions: 114.5 x 63.6 x 30.3 mm
- Colour: Silver
- Lid Colour: Silver
- Flanged: No

**5173276** Die Cast**RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, SILVER LID, 114.4 X 63.7**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 114.4 mm
- External Height: 55.1 mm
- External Width: 63.7 mm
- External Dimensions: 114.4 x 63.7 x 55.1 mm
- Colour: Silver
- Lid Colour: Silver
- Flanged: No

**5173298** Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, SILVER LID, 275 X 175 X

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 275 mm
- External Height: 65.5 mm
- External Width: 175 mm
- External Dimensions: 275 x 175 x 65.5 mm
- Colour: Silver
- Lid Colour: Silver
- Flanged: No



5173305 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, SILVER LID, 250 X 250 X

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 250 mm
- External Height: 100 mm
- External Width: 250 mm
- External Dimensions: 250 x 250 x 100 mm
- Colour: Silver
- Lid Colour: Silver
- Flanged: No



5173311 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, SILVER LID, 119.9 X 100 X

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 119.9 mm
- External Height: 35.7 mm
- External Width: 100 mm
- External Dimensions: 119.9 x 100 x 35.7 mm
- Colour: Silver
- Lid Colour: Silver
- Flanged: No



5173327 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, SILVER LID, 114.7 X 89.7

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 114.7 mm
- External Height: 55.1 mm
- External Width: 89.7 mm
- External Dimensions: 114.7 x 89.7 x 55.1 mm
- Colour: Silver
- Lid Colour: Silver
- Flanged: No



5173333 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, SILVER LID, 171.9 X 120.9

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 171.9 mm
- External Height: 55 mm
- External Width: 120.9 mm
- External Dimensions: 171.9 x 120.9 x 55 mm
- Colour: Silver
- Lid Colour: Silver
- Flanged: No



5173355 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, SILVER LID, 139.1 X 101.5

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 139.1 mm
- External Height: 76.7 mm
- External Width: 101.5 mm
- External Dimensions: 139.1 x 101.5 x 76.7 mm
- Colour: Silver
- Lid Colour: Silver
- Flanged: No



5173361 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, SILVER LID, 79.9 X 54.9 X

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 79.9 mm
- External Height: 25.5 mm
- External Width: 54.9 mm
- External Dimensions: 79.9 x 54.9 x 25.5 mm
- Colour: Silver
- Lid Colour: Silver
- Flanged: No



5173377 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, SILVER LID, 165.8 X 127.3

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 165.8 mm
- External Height: 76.3 mm
- External Width: 127.3 mm
- External Dimensions: 165.8 x 127.3 x 76.3 mm
- Colour: Silver
- Lid Colour: Silver
- Flanged: No



5173383 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, SILVER LID, 60 X 54.9 X

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 60 mm
- External Height: 30 mm
- External Width: 54.9 mm
- External Dimensions: 60 x 54.9 x 30 mm
- Colour: Silver
- Lid Colour: Silver
- Flanged: No



5173399 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, SILVER LID, 171.9 X 120.9

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 171.9 mm
- External Height: 106 mm
- External Width: 120.9 mm
- External Dimensions: 171.9 x 120.9 x 106 mm
- Colour: Silver
- Lid Colour: Silver
- Flanged: No



5173412 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP66, SILVER LID, 250 X

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 250 mm
- External Height: 100 mm
- External Width: 250 mm
- External Dimensions: 250 x 250 x 100 mm
- IP Rating: IP66
- Colour: Silver
- Lid Colour: Silver



5173428 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP66, SILVER LID, 171.9 X

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 171.9 mm
- External Height: 106 mm
- External Width: 120.9 mm
- External Dimensions: 171.9 x 120.9 x 106 mm
- IP Rating: IP66
- Colour: Silver
- Lid Colour: Silver



5173434 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP66, SILVER LID, 275 X

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 275 mm
- External Height: 65.5 mm
- External Width: 175 mm
- External Dimensions: 275 x 175 x 65.5 mm
- IP Rating: IP66
- Colour: Silver
- Lid Colour: Silver



5173440 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP66, SILVER LID, 139.1 X

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 139.1 mm
- External Height: 76.7 mm
- External Width: 101.5 mm
- External Dimensions: 139.1 x 101.5 x 76.7 mm
- IP Rating: IP66
- Colour: Silver
- Lid Colour: Silver



5173456 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP66, SILVER LID, 114.7 X

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 114.7 mm
- External Height: 55.1 mm
- External Width: 89.7 mm
- External Dimensions: 114.7 x 89.7 x 55.1 mm
- IP Rating: IP66
- Colour: Silver
- Lid Colour: Silver



5173462 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP66, SILVER LID, 171.9 X

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 171.9 mm
- External Height: 55 mm
- External Width: 120.9 mm
- External Dimensions: 171.9 x 120.9 x 55 mm
- IP Rating: IP66
- Colour: Silver
- Lid Colour: Silver



5173478 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP66, SILVER LID, 114.4 XPack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 114.4 mm
- External Height: 55.1 mm
- External Width: 63.7 mm
- External Dimensions: 114.4 x 63.7 x 55.1 mm
- IP Rating: IP66
- Colour: Silver
- Lid Colour: Silver

**5173484** Die Cast**RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP66, SILVER LID, 165.8 X**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 165.8 mm
- External Height: 76.3 mm
- External Width: 127.3 mm
- External Dimensions: 165.8 x 127.3 x 76.3 mm
- IP Rating: IP66
- Colour: Silver
- Lid Colour: Silver

**5173490** Die Cast**RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP66, SILVER LID, 60 X**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 60 mm
- External Height: 30 mm
- External Width: 54.9 mm
- External Dimensions: 60 x 54.9 x 30 mm
- IP Rating: IP66
- Colour: Silver
- Lid Colour: Silver

**5173513** Die Cast**RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP66, SILVER LID, 119.9 X**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 119.9 mm
- External Height: 35.7 mm
- External Width: 100 mm
- External Dimensions: 119.9 x 100 x 35.7 mm
- IP Rating: IP66
- Colour: Silver
- Lid Colour: Silver

**5173529** Die Cast**RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, GREY LID, 275 X 175 X**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 275 mm
- External Height: 65.5 mm
- External Width: 175 mm
- External Dimensions: 275 x 175 x 65.5 mm
- Colour: Grey
- Lid Colour: Grey
- Flanged: No

**5173541** Die Cast**RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, GREY LID, 250 X 250 X**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 250 mm
- External Height: 100 mm
- External Width: 250 mm
- External Dimensions: 250 x 250 x 100 mm
- Colour: Grey
- Lid Colour: Grey
- Flanged: No

**5173557** Die Cast**RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, GREY LID, 222.1 X 145.9**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 222.1 mm
- External Height: 55.9 mm
- External Width: 145.9 mm
- External Dimensions: 222.1 x 145.9 x 55.9 mm
- Colour: Grey
- Lid Colour: Grey
- Flanged: No

**5173579** Die Cast**RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, GREY LID, 114.5 X 63.6 X**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 114.5 mm
- External Height: 30.3 mm
- External Width: 63.6 mm
- External Dimensions: 114.5 x 63.6 x 30.3 mm
- Colour: Grey
- Lid Colour: Grey
- Flanged: No

**5173664** Die Cast**RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, GREY LID, 60 X 54.9 X**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 60 mm
- External Height: 30 mm
- External Width: 54.9 mm
- External Dimensions: 60 x 54.9 x 30 mm
- Colour: Grey
- Lid Colour: Grey
- Flanged: No

**5173670** Die Cast**RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, FLANGED, SILVER LID,**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 113.9 mm
- External Height: 30 mm
- External Width: 35.1 mm
- External Dimensions: 113.9 x 35.1 x 30 mm
- Colour: Silver
- Lid Colour: Silver
- Flanged: Yes

**5173709** Die Cast**RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, FLANGED, SILVER LID,**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 139.7 mm
- External Height: 30 mm
- External Width: 63.8 mm
- External Dimensions: 139.7 x 63.8 x 30 mm
- Colour: Silver
- Lid Colour: Silver
- Flanged: Yes

**5173715** Die Cast**RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, FLANGED, SILVER LID,**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 139.8 mm
- External Height: 30 mm
- External Width: 55.2 mm
- External Dimensions: 139.8 x 55.2 x 30 mm
- Colour: Silver
- Lid Colour: Silver
- Flanged: Yes

**5173721** Die Cast**RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, FLANGED, SILVER LID,**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 139.6 mm
- External Height: 55 mm
- External Width: 63.8 mm
- External Dimensions: 139.6 x 63.8 x 55 mm
- Colour: Silver
- Lid Colour: Silver
- Flanged: Yes

**5173737** Die Cast**RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, FLANGED, SILVER LID,**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 149.8 mm
- External Height: 35.6 mm
- External Width: 100.2 mm
- External Dimensions: 149.8 x 100.2 x 35.6 mm
- Colour: Silver
- Lid Colour: Silver
- Flanged: Yes

**5173743** Die Cast**RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, FLANGED, SILVER LID,**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 168.7 mm
- External Height: 76.5 mm
- External Width: 101.6 mm
- External Dimensions: 168.7 x 101.6 x 76.5 mm
- Colour: Silver
- Lid Colour: Silver
- Flanged: Yes

**5173759** Die Cast**RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, FLANGED, SILVER LID,**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 194.8 mm
- External Height: 76.3 mm
- External Width: 127.4 mm
- External Dimensions: 194.8 x 127.4 x 76.3 mm
- Colour: Silver
- Lid Colour: Silver
- Flanged: Yes

**5173765** Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, FLANGED, SILVER LID,

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 201.7 mm
- External Height: 55.3 mm
- External Width: 121.2 mm
- External Dimensions: 201.7 x 121.2 x 55.3 mm
- Colour: Silver
- Lid Colour: Silver
- Flanged: Yes



5173771 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, FLANGED, SILVER LID,

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 201.7 mm
- External Height: 105.4 mm
- External Width: 121.2 mm
- External Dimensions: 201.7 x 121.2 x 105.4 mm
- Colour: Silver
- Lid Colour: Silver
- Flanged: Yes



5173793 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, GREY LID, 114.7 X 89.7 X

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 114.7 mm
- External Height: 55.1 mm
- External Width: 89.7 mm
- External Dimensions: 114.7 x 89.7 x 55.1 mm
- Colour: Grey
- Lid Colour: Grey
- Flanged: No



5173816 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, GREY LID, 114.4 X 63.7 X

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 114.4 mm
- External Height: 55.1 mm
- External Width: 63.7 mm
- External Dimensions: 114.4 x 63.7 x 55.1 mm
- Colour: Grey
- Lid Colour: Grey
- Flanged: No



5173822 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, GREY LID, 222.1 X 145.9

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 222.1 mm
- External Height: 55.9 mm
- External Width: 145.9 mm
- External Dimensions: 222.1 x 145.9 x 55.9 mm
- Colour: Grey
- Lid Colour: Grey
- Flanged: No



5173838 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, GREY LID, 171.9 X 120.9 X

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 171.9 mm
- External Height: 55 mm
- External Width: 120.9 mm
- External Dimensions: 171.9 x 120.9 x 55 mm
- Colour: Grey
- Lid Colour: Grey
- Flanged: No



5173850 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, GREY LID, 114.5 X 63.6 X

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 114.5 mm
- External Height: 30.3 mm
- External Width: 63.6 mm
- External Dimensions: 114.5 x 63.6 x 30.3 mm
- Colour: Grey
- Lid Colour: Grey
- Flanged: No



5173866 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, GREY LID, 89.1 X 35 X

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 89.1 mm
- External Height: 30.3 mm
- External Width: 35 mm
- External Dimensions: 89.1 x 35 x 30.3 mm
- Colour: Grey
- Lid Colour: Grey
- Flanged: No



5173888 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, GREY LID, 222.2 X 146 X

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 222.2 mm
- External Height: 106.5 mm
- External Width: 146 mm
- External Dimensions: 222.2 x 146 x 106.5 mm
- Colour: Grey
- Lid Colour: Grey
- Flanged: No



5173894 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, GREY LID, 250 X 250 X

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 250 mm
- External Height: 100 mm
- External Width: 250 mm
- External Dimensions: 250 x 250 x 100 mm
- Colour: Grey
- Lid Colour: Grey
- Flanged: No



5173917 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, GREY LID, 275 X 175 X

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 275 mm
- External Height: 65.5 mm
- External Width: 175 mm
- External Dimensions: 275 x 175 x 65.5 mm
- Colour: Grey
- Lid Colour: Grey
- Flanged: No



5173923 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, GREY LID, 165.8 X 127.3

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 165.8 mm
- External Height: 76.3 mm
- External Width: 127.3 mm
- External Dimensions: 165.8 x 127.3 x 76.3 mm
- Colour: Grey
- Lid Colour: Grey
- Flanged: No



5173939 Die Cast

RS PRO BLACK DIE CAST ALUMINIUM ENCLOSURE, BLACK LID, 114.5 X 63.6

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 114.5 mm
- External Height: 30.3 mm
- External Width: 63.6 mm
- External Dimensions: 114.5 x 63.6 x 30.3 mm
- Colour: Black
- Lid Colour: Black
- Flanged: No



5173951 Die Cast

RS PRO BLACK DIE CAST ALUMINIUM ENCLOSURE, BLACK LID, 114.4 X 63.7

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 114.4 mm
- External Height: 55.1 mm
- External Width: 63.7 mm
- External Dimensions: 114.4 x 63.7 x 55.1 mm
- Colour: Black
- Lid Colour: Black
- Flanged: No



5173967 Die Cast

RS PRO BLACK DIE CAST ALUMINIUM ENCLOSURE, BLACK LID, 171.9 X 120.9

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 171.9 mm
- External Height: 55 mm
- External Width: 120.9 mm
- External Dimensions: 171.9 x 120.9 x 55 mm
- Colour: Black
- Lid Colour: Black
- Flanged: No



5173973 Die Cast

RS PRO BLACK DIE CAST ALUMINIUM ENCLOSURE, BLACK LID, 275 X 175 X

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 275 mm
- External Height: 65.5 mm
- External Width: 175 mm
- External Dimensions: 275 x 175 x 65.5 mm
- Colour: Black
- Lid Colour: Black
- Flanged: No



5173989 Die Cast

RS PRO BLACK DIE CAST ALUMINIUM ENCLOSURE, BLACK LID, 165.8 X 127.3Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 165.8 mm
- External Height: 76.3 mm
- External Width: 127.3 mm
- External Dimensions: 165.8 x 127.3 x 76.3 mm
- Colour: Black
- Lid Colour: Black
- Flanged: No

**5173995** Die Cast**RS PRO BLACK DIE CAST ALUMINIUM ENCLOSURE, BLACK LID, 250 X 250 X**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 250 mm
- External Height: 100 mm
- External Width: 250 mm
- External Dimensions: 250 x 250 x 100 mm
- Colour: Black
- Lid Colour: Black
- Flanged: No

**5174011** Die Cast**RS PRO BLACK DIE CAST ALUMINIUM ENCLOSURE, BLACK LID, 114.5 X 63.6**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 114.5 mm
- External Height: 30.3 mm
- External Width: 63.6 mm
- External Dimensions: 114.5 x 63.6 x 30.3 mm
- Colour: Black
- Lid Colour: Black
- Flanged: No

**5174033** Die Cast**RS PRO BLACK DIE CAST ALUMINIUM ENCLOSURE, BLACK LID, 114.4 X 63.7**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 114.4 mm
- External Height: 55.1 mm
- External Width: 63.7 mm
- External Dimensions: 114.4 x 63.7 x 55.1 mm
- Colour: Black
- Lid Colour: Black
- Flanged: No

**5174049** Die Cast**RS PRO BLACK DIE CAST ALUMINIUM ENCLOSURE, BLACK LID, 171.9 X 120.9**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 171.9 mm
- External Height: 55 mm
- External Width: 120.9 mm
- External Dimensions: 171.9 x 120.9 x 55 mm
- Colour: Black
- Lid Colour: Black
- Flanged: No

**5174055** Die Cast**RS PRO BLACK DIE CAST ALUMINIUM ENCLOSURE, BLACK LID, 114.7 X 89.7**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 114.7 mm
- External Height: 55.1 mm
- External Width: 89.7 mm
- External Dimensions: 114.7 x 89.7 x 55.1 mm
- Colour: Black
- Lid Colour: Black
- Flanged: No

**5174061** Die Cast**RS PRO BLACK DIE CAST ALUMINIUM ENCLOSURE, BLACK LID, 139.1 X 101.5**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 139.1 mm
- External Height: 76.7 mm
- External Width: 101.5 mm
- External Dimensions: 139.1 x 101.5 x 76.7 mm
- Colour: Black
- Lid Colour: Black
- Flanged: No

**5174083** Die Cast**RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP65, FLANGED, SILVER**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 139.6 mm
- External Height: 55 mm
- External Width: 63.8 mm
- External Dimensions: 139.6 x 63.8 x 55 mm
- IP Rating: IP65
- Colour: Silver
- Lid Colour: Silver

**5174099** Die Cast**RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP65, FLANGED, SILVER**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 113.9 mm
- External Height: 30 mm
- External Width: 35.1 mm
- External Dimensions: 113.9 x 35.1 x 30 mm
- IP Rating: IP65
- Colour: Silver
- Lid Colour: Silver

**5174106** Die Cast**RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP65, FLANGED, SILVER**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 139.8 mm
- External Height: 55.2 mm
- External Width: 89.7 mm
- External Dimensions: 139.8 x 89.7 x 55.2 mm
- IP Rating: IP65
- Colour: Silver
- Lid Colour: Silver

**5174112** Die Cast**RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP65, FLANGED, SILVER**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 139.7 mm
- External Height: 30 mm
- External Width: 63.8 mm
- External Dimensions: 139.7 x 63.8 x 30 mm
- IP Rating: IP65
- Colour: Silver
- Lid Colour: Silver

**5174128** Die Cast**RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP65, FLANGED, SILVER**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 140 mm
- External Height: 77 mm
- External Width: 102 mm
- External Dimensions: 140 x 102 x 77 mm
- IP Rating: IP65
- Colour: Silver
- Lid Colour: Silver

**5174140** Die Cast**RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP65, FLANGED, SILVER**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 201.7 mm
- External Height: 105.4 mm
- External Width: 121.2 mm
- External Dimensions: 201.7 x 121.2 x 105.4 mm
- IP Rating: IP65
- Colour: Silver
- Lid Colour: Silver

**5174156** Die Cast**RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP65, FLANGED, SILVER**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 252 mm
- External Height: 55.5 mm
- External Width: 146.1 mm
- External Dimensions: 252 x 146.1 x 55.5 mm
- IP Rating: IP65
- Colour: Silver
- Lid Colour: Silver

**5174162** Die Cast**RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP65, FLANGED, SILVER**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 184.8 mm
- External Height: 76.3 mm
- External Width: 127.4 mm
- External Dimensions: 184.8 x 127.4 x 76.3 mm
- IP Rating: IP65
- Colour: Silver
- Lid Colour: Silver

**5174178** Die Cast**RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP65, FLANGED, SILVER**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 201.7 mm
- External Height: 55.3 mm
- External Width: 121.2 mm
- External Dimensions: 201.7 x 121.2 x 55.3 mm
- IP Rating: IP65
- Colour: Silver
- Lid Colour: Silver

**5174184** Die Cast

RS PRO BLACK DIE CAST ALUMINIUM ENCLOSURE, IP66, BLACK LID, 89.1 X

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 89.1 mm
- External Height: 30.3 mm
- External Width: 35 mm
- External Dimensions: 89.1 x 35 x 30.3 mm
- IP Rating: IP66
- Colour: Black
- Lid Colour: Black



5174257 Die Cast

RS PRO BLACK DIE CAST ALUMINIUM ENCLOSURE, IP66, BLACK LID, 114.5 X

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 114.5 mm
- External Height: 30.3 mm
- External Width: 63.6 mm
- External Dimensions: 114.5 x 63.6 x 30.3 mm
- IP Rating: IP66
- Colour: Black
- Lid Colour: Black



5174263 Die Cast

RS PRO BLACK DIE CAST ALUMINIUM ENCLOSURE, IP66, BLACK LID, 114.7 X

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 114.7 mm
- External Height: 55.1 mm
- External Width: 89.7 mm
- External Dimensions: 114.7 x 89.7 x 55.1 mm
- IP Rating: IP66
- Colour: Black
- Lid Colour: Black



5174279 Die Cast

RS PRO BLACK DIE CAST ALUMINIUM ENCLOSURE, IP66, BLACK LID, 171.9 X

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 171.9 mm
- External Height: 55 mm
- External Width: 120.9 mm
- External Dimensions: 171.9 x 120.9 x 55 mm
- IP Rating: IP66
- Colour: Black
- Lid Colour: Black



5174285 Die Cast

RS PRO BLACK DIE CAST ALUMINIUM ENCLOSURE, IP66, BLACK LID, 165.8 X

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 165.8 mm
- External Height: 76.3 mm
- External Width: 127.3 mm
- External Dimensions: 165.8 x 127.3 x 76.3 mm
- IP Rating: IP66
- Colour: Black
- Lid Colour: Black



5174308 Die Cast

RS PRO BLACK DIE CAST ALUMINIUM ENCLOSURE, IP66, BLACK LID, 250 X

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 250 mm
- External Height: 100 mm
- External Width: 250 mm
- External Dimensions: 250 x 250 x 100 mm
- IP Rating: IP66
- Colour: Black
- Lid Colour: Black



5174314 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP66, SILVER LID, 114.5 X

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 114.5 mm
- External Height: 30.3 mm
- External Width: 63.6 mm
- External Dimensions: 114.5 x 63.6 x 30.3 mm
- IP Rating: IP66
- Colour: Silver
- Lid Colour: Silver



5174409 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, SILVER LID, 222.2 X 146 X

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 222.2 mm
- External Height: 106.5 mm
- External Width: 146 mm
- External Dimensions: 222.2 x 146 x 106.5 mm
- Colour: Silver
- Lid Colour: Silver
- Flanged: No



5174437 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, SILVER LID, 89.1 X 35 X

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 89.1 mm
- External Height: 30.3 mm
- External Width: 35 mm
- External Dimensions: 89.1 x 35 x 30.3 mm
- Colour: Silver
- Lid Colour: Silver
- Flanged: No



5174443 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP66, SILVER LID, 222.1 X

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 222.1 mm
- External Height: 55.9 mm
- External Width: 145.9 mm
- External Dimensions: 222.1 x 145.9 x 55.9 mm
- IP Rating: IP66
- Colour: Silver
- Lid Colour: Silver



5174459 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP66, SILVER LID, 222.2 X

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 222.2 mm
- External Height: 106.5 mm
- External Width: 146 mm
- External Dimensions: 222.2 x 146 x 106.5 mm
- IP Rating: IP66
- Colour: Silver
- Lid Colour: Silver



5174465 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP66, FLANGED, GREY

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 168.7 mm
- External Height: 76.5 mm
- External Width: 101.6 mm
- External Dimensions: 168.7 x 101.6 x 76.5 mm
- IP Rating: IP66
- Colour: Grey
- Lid Colour: Grey



6214895 Die Cast

RS PRO BLACK DIE CAST ALUMINIUM ENCLOSURE, BLACK LID, 222.1 X 145.9

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 222.1 mm
- External Height: 55.9 mm
- External Width: 145.9 mm
- External Dimensions: 222.1 x 145.9 x 55.9 mm
- Colour: Black
- Lid Colour: Black
- Flanged: No



6214968 Die Cast

RS PRO BLACK DIE CAST ALUMINIUM ENCLOSURE, IP66, FLANGED, BLACK

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 139.6 mm
- External Height: 55 mm
- External Width: 63.8 mm
- External Dimensions: 139.6 x 63.8 x 55 mm
- IP Rating: IP66
- Colour: Black
- Lid Colour: Black



6214980 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP66, FLANGED, GREY

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 113.9 mm
- External Height: 30 mm
- External Width: 35.1 mm
- External Dimensions: 113.9 x 35.1 x 30 mm
- IP Rating: IP66
- Colour: Grey
- Lid Colour: Grey



6215028 Die Cast

RS PRO BLACK DIE CAST ALUMINIUM ENCLOSURE, IP66, FLANGED, BLACK

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 168.7 mm
- External Height: 76.5 mm
- External Width: 101.6 mm
- External Dimensions: 168.7 x 101.6 x 76.5 mm
- IP Rating: IP66
- Colour: Black
- Lid Colour: Black



6215034 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP66, FLANGED, GREYPack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 252 mm
- External Height: 55.5 mm
- External Width: 146.1 mm
- External Dimensions: 252 x 146.1 x 55.5 mm
- IP Rating: IP66
- Colour: Grey
- Lid Colour: Grey

**6215078** Die Cast**RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP67, SILVER LID, 274 X**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 274 mm
- External Height: 100 mm
- External Width: 173 mm
- External Dimensions: 274 x 173 x 100 mm
- IP Rating: IP67
- Colour: Silver
- Lid Colour: Silver

**7004100** Die Cast**RS PRO BLACK DIE CAST ALUMINIUM ENCLOSURE, IP67, BLACK LID, 274 X**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 274 mm
- External Height: 100 mm
- External Width: 173 mm
- External Dimensions: 274 x 173 x 100 mm
- IP Rating: IP67
- Colour: Black
- Lid Colour: Black

**7004131** Die Cast**RS PRO BLACK DIE CAST ALUMINIUM ENCLOSURE, IP67, BLACK LID, 200 X**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 200 mm
- External Height: 75 mm
- External Width: 150 mm
- External Dimensions: 200 x 150 x 75 mm
- IP Rating: IP67
- Colour: Black
- Lid Colour: Black

**7004141** Die Cast**RS PRO BLACK DIE CAST ALUMINIUM ENCLOSURE, IP67, BLACK LID, 200 X**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 200 mm
- External Height: 50 mm
- External Width: 150 mm
- External Dimensions: 200 x 150 x 50 mm
- IP Rating: IP67
- Colour: Black
- Lid Colour: Black

**7004147** Die Cast**RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP66, SILVER LID, 125 X**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 125 mm
- External Height: 57 mm
- External Width: 80 mm
- External Dimensions: 125 x 80 x 57 mm
- IP Rating: IP66
- Colour: Silver
- Lid Colour: Silver

**7608913** Die Cast**RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP66, SILVER LID, 98 X 64**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 98 mm
- External Height: 34 mm
- External Width: 64 mm
- External Dimensions: 98 x 64 x 34 mm
- IP Rating: IP66
- Colour: Silver
- Lid Colour: Silver

**7608926** Die Cast**RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP66, SILVER LID, 75 X 80**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 75 mm
- External Height: 57 mm
- External Width: 80 mm
- External Dimensions: 75 x 80 x 57 mm
- IP Rating: IP66
- Colour: Silver
- Lid Colour: Silver

**7608929** Die Cast**RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP66, SILVER LID, 150 X**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 150 mm
- External Height: 34 mm
- External Width: 64 mm
- External Dimensions: 150 x 64 x 34 mm
- IP Rating: IP66
- Colour: Silver
- Lid Colour: Silver

**7608932** Die Cast**RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP66, SILVER LID, 100 X**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 100 mm
- External Height: 81 mm
- External Width: 100 mm
- External Dimensions: 100 x 100 x 81 mm
- IP Rating: IP66
- Colour: Silver
- Lid Colour: Silver

**7608935** Die Cast**RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP66, SILVER LID, 160 X**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 160 mm
- External Height: 81 mm
- External Width: 100 mm
- External Dimensions: 160 x 100 x 81 mm
- IP Rating: IP66
- Colour: Silver
- Lid Colour: Silver

**7608939** Die Cast**RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP66, SILVER LID, 260 X**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 260 mm
- External Height: 90 mm
- External Width: 160 mm
- External Dimensions: 260 x 160 x 90 mm
- IP Rating: IP66
- Colour: Silver
- Lid Colour: Silver

**7608941** Die Cast**RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP66, SILVER LID, 250 X**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 250 mm
- External Height: 55 mm
- External Width: 80 mm
- External Dimensions: 250 x 80 x 55 mm
- IP Rating: IP66
- Colour: Silver
- Lid Colour: Silver

**7608945** Die Cast**RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP66, SILVER LID, 160 X**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 160 mm
- External Height: 90 mm
- External Width: 160 mm
- External Dimensions: 160 x 160 x 90 mm
- IP Rating: IP66
- Colour: Silver
- Lid Colour: Silver

**7608951** Die Cast**RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP66, SILVER LID, 280 X**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 280 mm
- External Height: 110 mm
- External Width: 230 mm
- External Dimensions: 280 x 230 x 110 mm
- IP Rating: IP66
- Colour: Silver
- Lid Colour: Silver

**7608954** Die Cast**RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP66, SILVER LID, 220 X**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 220 mm
- External Height: 91 mm
- External Width: 120 mm
- External Dimensions: 220 x 120 x 91 mm
- IP Rating: IP66
- Colour: Silver
- Lid Colour: Silver

**7608960** Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP66, GREY LID, 125 X 80

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 125 mm
- External Height: 57 mm
- External Width: 80 mm
- External Dimensions: 125 x 80 x 57 mm
- IP Rating: IP66
- Colour: Grey
- Lid Colour: Grey



7608963 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP66, GREY LID, 122 X

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 122 mm
- External Height: 81 mm
- External Width: 120 mm
- External Dimensions: 122 x 120 x 81 mm
- IP Rating: IP66
- Colour: Grey
- Lid Colour: Grey



7608967 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP66, GREY LID, 50 X 45

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 50 mm
- External Height: 30 mm
- External Width: 45 mm
- External Dimensions: 50 x 45 x 30 mm
- IP Rating: IP66
- Colour: Grey
- Lid Colour: Grey



7608973 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP66, GREY LID, 98 X 64

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 98 mm
- External Height: 81 mm
- External Width: 64 mm
- External Dimensions: 98 x 64 x 81 mm
- IP Rating: IP66
- Colour: Grey
- Lid Colour: Grey



7608976 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP66, GREY LID, 75 X 80

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 75 mm
- External Height: 57 mm
- External Width: 80 mm
- External Dimensions: 75 x 80 x 57 mm
- IP Rating: IP66
- Colour: Grey
- Lid Colour: Grey



7608979 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP66, GREY LID, 150 X 64

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 150 mm
- External Height: 34 mm
- External Width: 64 mm
- External Dimensions: 150 x 64 x 34 mm
- IP Rating: IP66
- Colour: Grey
- Lid Colour: Grey



7608982 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP66, GREY LID, 100 X

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 100 mm
- External Height: 81 mm
- External Width: 100 mm
- External Dimensions: 100 x 100 x 81 mm
- IP Rating: IP66
- Colour: Grey
- Lid Colour: Grey



7608985 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP66, GREY LID, 160 X

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 160 mm
- External Height: 81 mm
- External Width: 100 mm
- External Dimensions: 160 x 100 x 81 mm
- IP Rating: IP66
- Colour: Grey
- Lid Colour: Grey



7608989 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP66, GREY LID, 260 X

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 260 mm
- External Height: 90 mm
- External Width: 160 mm
- External Dimensions: 260 x 160 x 90 mm
- IP Rating: IP66
- Colour: Grey
- Lid Colour: Grey



7608991 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP66, GREY LID, 250 X

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 250 mm
- External Height: 57 mm
- External Width: 80 mm
- External Dimensions: 250 x 80 x 57 mm
- IP Rating: IP66
- Colour: Grey
- Lid Colour: Grey



7608995 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP66, GREY LID, 175 X 80

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 175 mm
- External Height: 57 mm
- External Width: 80 mm
- External Dimensions: 175 x 80 x 57 mm
- IP Rating: IP66
- Colour: Grey
- Lid Colour: Grey



7608998 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP66, GREY LID, 58 X 64

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 58 mm
- External Height: 34 mm
- External Width: 64 mm
- External Dimensions: 58 x 64 x 34 mm
- IP Rating: IP66
- Colour: Grey
- Lid Colour: Grey



7609001 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP66, GREY LID, 160 X

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 160 mm
- External Height: 91 mm
- External Width: 160 mm
- External Dimensions: 160 x 160 x 91 mm
- IP Rating: IP66
- Colour: Grey
- Lid Colour: Grey



7609005 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP66, GREY LID, 280 X

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 280 mm
- External Height: 110 mm
- External Width: 230 mm
- External Dimensions: 280 x 230 x 110 mm
- IP Rating: IP66
- Colour: Grey
- Lid Colour: Grey



7609008 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP66, GREY LID, 220 X

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 200 mm
- External Height: 90 mm
- External Width: 120 mm
- External Dimensions: 220 x 120 x 90 mm
- IP Rating: IP66
- Colour: Grey
- Lid Colour: Grey



7609014 Die Cast

RS PRO SILVER ALUMINIUM ENCLOSURE, IP67, SILVER LID, 262 X

Pack size: **1 x EA**

- Body Material: Aluminium
- External Length: 262 mm
- External Height: 90 mm
- External Width: 182 mm
- External Dimensions: 262 x 182 x 90 mm
- IP Rating: IP67
- Colour: Silver
- Lid Colour: Silver



7683801 Aluminium

RS PRO GREY ABS ENCLOSURE, IP55, GREY LID, 200 X 155 X 80MMPack size: **1 x EA**

- Body Material: ABS
- External Length: 155 mm
- External Height: 200 mm
- External Width: 80 mm
- External Dimensions: 200 x 155 x 80 mm
- IP Rating: IP55
- Colour: Grey
- Lid Colour: Grey

**7696134** ABS**RS PRO GREY ABS ENCLOSURE, IP55, GREY LID, 210 X 160 X 260MM**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 210 mm
- External Height: 260 mm
- External Width: 160 mm
- External Dimensions: 210 x 160 x 260 mm
- IP Rating: IP55
- Colour: Grey
- Lid Colour: Grey

**7696140** ABS**RS PRO GREY ABS ENCLOSURE, IP55, GREY LID, 240 X 135 X 320MM**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 240 mm
- External Height: 320 mm
- External Width: 135 mm
- External Dimensions: 240 x 135 x 320 mm
- IP Rating: IP55
- Colour: Grey
- Lid Colour: Grey

**7696144** ABS**RS PRO GREY ABS ENCLOSURE, IP55, GREY LID, 210 X 95 X 260MM**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 210 mm
- External Height: 260 mm
- External Width: 95 mm
- External Dimensions: 210 x 95 x 260 mm
- IP Rating: IP55
- Colour: Grey
- Lid Colour: Grey

**7696147** ABS**RS PRO GREY ABS ENCLOSURE, IP55, GREY LID, 320 X 240 X 180MM**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 180 mm
- External Height: 320 mm
- External Width: 240 mm
- External Dimensions: 320 x 240 x 180 mm
- IP Rating: IP55
- Colour: Grey
- Lid Colour: Grey

**7696153** ABS**RS PRO BLACK ALUMINIUM ENCLOSURE, IP67, FLANGED, BLACK**Pack size: **1 x EA**

- Body Material: Aluminium
- External Length: 152 mm
- External Height: 55 mm
- External Width: 112 mm
- External Dimensions: 152 x 112 x 55 mm
- IP Rating: IP67
- Colour: Black
- Lid Colour: Black

**7717641** Aluminium**RS PRO BLACK ALUMINIUM ENCLOSURE, IP67, FLANGED, BLACK**Pack size: **1 x EA**

- Body Material: Aluminium
- External Length: 202 mm
- External Height: 80 mm
- External Width: 142 mm
- External Dimensions: 202 x 142 x 80 mm
- IP Rating: IP67
- Colour: Black
- Lid Colour: Black

**7717651** Aluminium**RS PRO BLACK ALUMINIUM ENCLOSURE, IP67, FLANGED, BLACK**Pack size: **1 x EA**

- Body Material: Aluminium
- External Length: 262 mm
- External Height: 90 mm
- External Width: 182 mm
- External Dimensions: 262 x 182 x 90 mm
- IP Rating: IP67
- Colour: Black
- Lid Colour: Black

**7717663** Aluminium**RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP66, SILVER LID, 122 X**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 122 mm
- External Height: 91 mm
- External Width: 120 mm
- External Dimensions: 122 x 120 x 91 mm
- IP Rating: IP66
- Colour: Silver
- Lid Colour: Silver

**8462942** Die Cast**RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP66, SILVER LID, 50 X**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 50 mm
- External Height: 30 mm
- External Width: 45 mm
- External Dimensions: 50 x 45 x 30 mm
- IP Rating: IP66
- Colour: Silver
- Lid Colour: Silver

**8462945** Die Cast**RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP66, SILVER LID, 220 X**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 220 mm
- External Height: 81 mm
- External Width: 120 mm
- External Dimensions: 220 x 120 x 81 mm
- IP Rating: IP66
- Colour: Silver
- Lid Colour: Silver

**8462948** Die Cast**RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP66, SILVER LID, 360 X**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 360 mm
- External Height: 90 mm
- External Width: 160 mm
- External Dimensions: 360 x 160 x 90 mm
- IP Rating: IP66
- Colour: Silver
- Lid Colour: Silver

**8462951** Die Cast**RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP66, SILVER LID, 180 X**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 180 mm
- External Height: 100 mm
- External Width: 180 mm
- External Dimensions: 180 x 180 x 100 mm
- IP Rating: IP66
- Colour: Silver
- Lid Colour: Silver

**8462954** Die Cast**RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP66, SILVER LID, 280 X**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 280 mm
- External Height: 100 mm
- External Width: 180 mm
- External Dimensions: 280 x 180 x 100 mm
- IP Rating: IP66
- Colour: Silver
- Lid Colour: Silver

**8462958** Die Cast**RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP66, SILVER LID, 330 X**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 330 mm
- External Height: 110 mm
- External Width: 230 mm
- External Dimensions: 330 x 230 x 110 mm
- IP Rating: IP66
- Colour: Silver
- Lid Colour: Silver

**8462960** Die Cast**RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP66, SILVER LID, 200 X**Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 200 mm
- External Height: 180 mm
- External Width: 230 mm
- External Dimensions: 200 x 230 x 180 mm
- IP Rating: IP66
- Colour: Silver
- Lid Colour: Silver

**8462964** Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP66, SILVER LID, 230 X

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 230 mm
- External Height: 110 mm
- External Width: 200 mm
- External Dimensions: 230 x 200 x 110 mm
- IP Rating: IP66
- Colour: Silver
- Lid Colour: Silver



8462967 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP66, GREY LID, 220 X

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 220 mm
- External Height: 81 mm
- External Width: 120 mm
- External Dimensions: 220 x 120 x 81 mm
- IP Rating: IP66
- Colour: Grey
- Lid Colour: Grey



8462998 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP66, GREY LID, 280 X

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 280 mm
- External Height: 100 mm
- External Width: 180 mm
- External Dimensions: 280 x 180 x 100 mm
- IP Rating: IP66
- Colour: Grey
- Lid Colour: Grey



8463002 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP66, GREY LID, 360 X

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 360 mm
- External Height: 90 mm
- External Width: 160 mm
- External Dimensions: 360 x 160 x 90 mm
- IP Rating: IP66
- Colour: Grey
- Lid Colour: Grey



8463005 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP66, GREY LID, 180 X

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 180 mm
- External Height: 100 mm
- External Width: 180 mm
- External Dimensions: 180 x 180 x 100 mm
- IP Rating: IP66
- Colour: Grey
- Lid Colour: Grey



8463008 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP66, GREY LID, 230 X

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 230 mm
- External Height: 110 mm
- External Width: 200 mm
- External Dimensions: 230 x 200 x 110 mm
- IP Rating: IP66
- Colour: Grey
- Lid Colour: Grey



8463011 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP66, GREY LID, 200 X

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 200 mm
- External Height: 180 mm
- External Width: 230 mm
- External Dimensions: 200 x 230 x 180 mm
- IP Rating: IP66
- Colour: Grey
- Lid Colour: Grey



8463018 Die Cast

RS PRO SILVER DIE CAST ALUMINIUM ENCLOSURE, IP66, SILVER LID, 400 X

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 400 mm
- External Height: 110 mm
- External Width: 230 mm
- External Dimensions: 400 x 230 x 110 mm
- IP Rating: IP66
- Colour: Silver
- Lid Colour: Silver



8462986 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP66, GREY LID, 330 X

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 330 mm
- External Height: 110 mm
- External Width: 230 mm
- External Dimensions: 330 x 230 x 110 mm
- IP Rating: IP66
- Colour: Grey
- Lid Colour: Grey



8463014 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP66, GREY LID, 400 X

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 400 mm
- External Height: 110 mm
- External Width: 310 mm
- External Dimensions: 400 x 310 x 110 mm
- IP Rating: IP66
- Colour: Grey
- Lid Colour: Grey



8463020 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP66, GREY LID, 330 X

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 330 mm
- External Height: 180 mm
- External Width: 230 mm
- External Dimensions: 330 x 230 x 180 mm
- IP Rating: IP66
- Colour: Grey
- Lid Colour: Grey



8463027 Die Cast

RS PRO GREY DIE CAST ALUMINIUM ENCLOSURE, IP66, GREY LID, 400 X

Pack size: **1 x EA**

- Body Material: Die Cast Aluminium
- External Length: 400 mm
- External Height: 110 mm
- External Width: 230 mm
- External Dimensions: 400 x 230 x 110 mm
- IP Rating: IP66
- Colour: Grey
- Lid Colour: Grey



8463030 Die Cast

RS PRO GREY PET ENCLOSURE, IP66, GREY LID, 110 X 75 X 55MM

Pack size: **1 x EA**

- Body Material: PET
- External Length: 110 mm
- External Height: 55 mm
- External Width: 75 mm
- External Dimensions: 110 x 75 x 55 mm
- IP Rating: IP66
- Colour: Grey
- Lid Colour: Grey



9188727 PET

RS PRO GREY PET ENCLOSURE, IP66, GREY LID, 122 X 120 X 90MM

Pack size: **1 x EA**

- Body Material: PET
- External Length: 122 mm
- External Height: 90 mm
- External Width: 120 mm
- External Dimensions: 122 x 120 x 90 mm
- IP Rating: IP66
- Colour: Grey
- Lid Colour: Grey



9188746 PET

RS PRO BLACK PET ENCLOSURE, IP66, GREY LID, 80 X 75 X 55MM

Pack size: **1 x EA**

- Body Material: PET
- External Length: 80 mm
- External Height: 55 mm
- External Width: 75 mm
- External Dimensions: 80 x 75 x 55 mm
- IP Rating: IP66
- Colour: Black
- Lid Colour: Grey



9188724 PET

RS PRO BLACK PET ENCLOSURE, IP66, BLACK LID, 122 X 120 X 90MM

Pack size: **1 x EA**

- Body Material: PET
- External Length: 122 mm
- External Height: 90 mm
- External Width: 120 mm
- External Dimensions: 122 x 120 x 90 mm
- IP Rating: IP66
- Colour: Black
- Lid Colour: Black



9188758 PET

RS PRO BLACK PET ENCLOSURE, IP66, BLACK LID, 160 X 75 X 75MMPack size: **1 x EA**

- Body Material: PET
- External Length: 160 mm
- External Height: 75 mm
- External Width: 75 mm
- External Dimensions: 160 x 75 x 75 mm
- IP Rating: IP66
- Colour: Black
- Lid Colour: Black

**9188783** PET**RS PRO BLACK PET ENCLOSURE, IP66, BLACK LID, 360 X 160 X 90MM**Pack size: **1 x EA**

- Body Material: PET
- External Length: 360 mm
- External Height: 90 mm
- External Width: 160 mm
- External Dimensions: 360 x 160 x 90 mm
- IP Rating: IP66
- Colour: Black
- Lid Colour: Black

**9188862** PET**RS PRO GREY PET ENCLOSURE, IP66, GREY LID, 160 X 160 X 90MM**Pack size: **1 x EA**

- Body Material: PET
- External Length: 160 mm
- External Height: 90 mm
- External Width: 160 mm
- External Dimensions: 160 x 160 x 90 mm
- IP Rating: IP66
- Colour: Grey
- Lid Colour: Grey

**9188780** PET**RS PRO GREY PET ENCLOSURE, IP66, GREY LID, 190 X 75 X 55MM**Pack size: **1 x EA**

- Body Material: PET
- External Length: 190 mm
- External Height: 55 mm
- External Width: 75 mm
- External Dimensions: 190 x 75 x 55 mm
- IP Rating: IP66
- Colour: Grey
- Lid Colour: Grey

**9188806** PET**RS PRO GREY PET ENCLOSURE, IP66, GREY LID, 220 X 120 X 90MM**Pack size: **1 x EA**

- Body Material: PET
- External Length: 220 mm
- External Height: 90 mm
- External Width: 120 mm
- External Dimensions: 220 x 120 x 90 mm
- IP Rating: IP66
- Colour: Grey
- Lid Colour: Grey

**9188815** PET**RS PRO GREY PET ENCLOSURE, IP66, GREY LID, 255 X 250 X 120MM**Pack size: **1 x EA**

- Body Material: PET
- External Length: 255 mm
- External Height: 120 mm
- External Width: 250 mm
- External Dimensions: 255 x 250 x 120 mm
- IP Rating: IP66
- Colour: Grey
- Lid Colour: Grey

**9188825** PET**RS PRO BLACK POLYESTER ENCLOSURE, IP66, BLACK LID, 220 X**Pack size: **1 x EA**

- Body Material: Polyester
- External Length: 220 mm
- External Height: 90 mm
- External Width: 120 mm
- External Dimensions: 220 x 120 x 90 mm
- IP Rating: IP66
- Colour: Black
- Lid Colour: Black

**9188828** Polyester**RS PRO GREY PET ENCLOSURE, IP66, GREY LID, 260 X 160 X 90MM**Pack size: **1 x EA**

- Body Material: PET
- External Length: 260 mm
- External Height: 90 mm
- External Width: 160 mm
- External Dimensions: 260 x 160 x 90 mm
- IP Rating: IP66
- Colour: Grey
- Lid Colour: Grey

**9188840** PET**RS PRO GREY PET ENCLOSURE, IP66, GREY LID, 400 X 250 X 120MM**Pack size: **1 x EA**

- Body Material: PET
- External Length: 400 mm
- External Height: 120 mm
- External Width: 250 mm
- External Dimensions: 400 x 250 x 120 mm
- IP Rating: IP66
- Colour: Grey
- Lid Colour: Grey

**9188869** PET**RS PRO BLACK ABS ENCLOSURE, FLANGED, BLACK LID, 50 X 50 X**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 50 mm
- External Height: 27 mm
- External Width: 50 mm
- External Dimensions: 50 x 50 x 27 mm
- Colour: Black
- Lid Colour: Black
- Flanged: Yes

**9190323** ABS**RS PRO BLACK ABS ENCLOSURE, FLANGED, BLACK LID, 70 X 50 X 42MM**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 70 mm
- External Height: 42 mm
- External Width: 50 mm
- External Dimensions: 70 x 50 x 42 mm
- Colour: Black
- Lid Colour: Black
- Flanged: Yes

**9190339** ABS**RS PRO BLACK ABS ENCLOSURE, FLANGED, BLACK LID, 90 X 45 X 27MM**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 90 mm
- External Height: 27 mm
- External Width: 45 mm
- External Dimensions: 90 x 45 x 27 mm
- Colour: Black
- Lid Colour: Black
- Flanged: Yes

**9190348** ABS**RS PRO BLACK ABS ENCLOSURE, FLANGED, BLACK LID, 80 X 80 X**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 80 mm
- External Height: 43 mm
- External Width: 80 mm
- External Dimensions: 80 x 80 x 43 mm
- Colour: Black
- Lid Colour: Black
- Flanged: Yes

**9190351** ABS**RS PRO BLACK ABS ENCLOSURE, FLANGED, BLACK LID, 105 X 70 X**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 105 mm
- External Height: 50 mm
- External Width: 70 mm
- External Dimensions: 105 x 70 x 50 mm
- Colour: Black
- Lid Colour: Black
- Flanged: Yes

**9190354** ABS**RS PRO WHITE ABS ENCLOSURE, FLANGED, WHITE LID, 50 X 50 X 27MM**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 50 mm
- External Height: 27 mm
- External Width: 50 mm
- External Dimensions: 50 x 50 x 27 mm
- Colour: White
- Lid Colour: White
- Flanged: Yes

**9190367** ABS**RS PRO WHITE ABS ENCLOSURE, FLANGED, WHITE LID, 70 X 50 X 42MM**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 70 mm
- External Height: 42 mm
- External Width: 50 mm
- External Dimensions: 70 x 50 x 42 mm
- Colour: White
- Lid Colour: White
- Flanged: Yes

**9190373** ABS

RS PRO WHITE ABS ENCLOSURE, FLANGED, WHITE LID, 105 X 70 X

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 105 mm
- External Height: 50 mm
- External Width: 70 mm
- External Dimensions: 105 x 70 x 50 mm
- Colour: White
- Lid Colour: White
- Flanged: Yes



9190398 ABS

RS PRO WHITE ABS HANDHELD ENCLOSURE, INTEGRAL BATTERY

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 96.5 mm
- External Width: 61 mm
- External Height: 25.5 mm
- Integral Battery Compartment: Yes
- Colour: White
- External Dimensions: 96.5 x 61 x 25.5 mm
- Standards Met: RoHS Compliant, UL 94 HB, UL E56070



222777 ABS

RS PRO WHITE ABS HANDHELD ENCLOSURE, INTEGRAL BATTERY

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 116.8 mm
- External Width: 69.9 mm
- External Height: 25.4 mm
- Integral Battery Compartment: Yes
- Colour: White
- External Dimensions: 116.84 x 69.85 x 25.4 mm
- Standards Met: RoHS Compliant, UL 94 HB, UL E56070



222783 ABS

RS PRO WHITE ABS HANDHELD ENCLOSURE, INTEGRAL BATTERY

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 146.1 mm
- External Width: 91.5 mm
- External Height: 52.9 mm
- Integral Battery Compartment: Yes
- Display Window: Yes
- Colour: White
- External Dimensions: 146.1 x 91.5 x 52.9 mm



222828 ABS

RS PRO GREY ABS HANDHELD ENCLOSURE, INTEGRAL BATTERY

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 190.5 mm
- External Width: 101.6 mm
- External Height: 57.2 mm
- Integral Battery Compartment: Yes
- Display Window: Yes
- Colour: Grey
- External Dimensions: 190.5 x 101.6 x 57.2 mm



222834 ABS

ENCLOSURE,ABS,INSTRUMENT CASE,BLACK,58X61X25MM

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 61 mm
- External Width: 57.7 mm
- External Height: 25.4 mm
- Colour: Black
- External Dimensions: 60.96 x 57.66 x 25.4 mm
- Standards Met: RoHS Compliant, UL 94 HB, UL E56070



139669 ABS

RS PRO BLACK ABS HANDHELD ENCLOSURE, INTEGRAL BATTERY

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 96.5 mm
- External Width: 61 mm
- External Height: 22.9 mm
- Integral Battery Compartment: Yes
- Colour: Black
- External Dimensions: 96.5 x 61 x 22.9 mm
- Standards Met: RoHS Compliant, UL 94 HB, UL E56070



1196310 ABS

RS PRO BLACK ABS HAND HELD CASE, IP54, 53 X 33 X 15MM

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 53 mm
- External Width: 33 mm
- External Height: 15 mm
- Weight: 8 g
- IP Rating: IP54
- Colour: Black
- External Dimensions: 53 x 33 x 15 mm



1947486 ABS

RS PRO ABS HAND HELD ENCLOSURE, INTEGRAL BATTERY COMPARTMENT,

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 160 mm
- External Width: 84 mm
- External Height: 30 mm
- Integral Battery Compartment: Yes
- IP Rating: IP54
- External Dimensions: 160 x 84 x 30 mm



1981368 ABS

RS PRO ABS HAND HELD ENCLOSURE, INTEGRAL BATTERY COMPARTMENT,

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 165.1 mm
- External Width: 100.1 mm
- External Height: 32 mm
- Integral Battery Compartment: Yes
- IP Rating: IP65
- External Dimensions: 165.1 x 100 x 32 mm



1981374 ABS

RS PRO BLACK ABS HANDHELD ENCLOSURE, INTEGRAL BATTERY

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 116.8 mm
- External Width: 69 mm
- External Height: 38.1 mm
- Integral Battery Compartment: Yes
- Colour: Black
- External Dimensions: 116.84 x 68.95 x 38.1 mm
- Standards Met: RoHS Compliant, UL 94 HB, UL E56070



2397277 ABS

RS PRO WHITE ABS HANDHELD ENCLOSURE, 61.9 X 41.7 X 20.3MM

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 61.9 mm
- External Width: 41.7 mm
- External Height: 20.3 mm
- Colour: White
- External Dimensions: 61.9 x 41.7 x 20.3 mm
- Standards Met: RoHS Compliant, UL 94 HB, UL E56070



2570523 ABS

ENCLOSURE,INSPECTION WINDOW,POLYCARBONATE,IP44,2

Pack size: **1 x EA**

- Length: 49 mm
- Width: 27 mm
- Height: 78 mm
- Material: Polycarbonate
- Colour: Grey
- For Use With: 46277-3, DIN 43880
- IP Rating: IP44



2971184 49 mm

ENCLOSURE,INSPECTION WINDOW,POLYCARBONATE,IP67,6

Pack size: **1 x EA**

- Length: 127 mm
- Width: 24 mm
- Height: 94 mm
- Material: Polycarbonate
- Colour: Grey
- For Use With: 46277-3, DIN 43880
- IP Rating: IP67



2971207 127 mm

ENCLOSURE,INSPECTION WINDOW,POLYCARBONATE,IP67,8

Pack size: **1 x EA**

- Length: 162 mm
- Width: 24 mm
- Height: 94 mm
- Material: Polycarbonate
- Colour: Grey
- For Use With: 46277-3, DIN 43880
- IP Rating: IP44



2971213 162 mm

ENCLOSURE,INSPECTION WINDOW,POLYCARBONATE,IP67,12

Pack size: **1 x EA**

- Length: 234 mm
- Width: 24 mm
- Height: 94 mm
- Material: Polycarbonate
- Colour: Grey
- For Use With: 46277-3, DIN 43880
- IP Rating: IP44



2971229 234 mm

MENNEKES GREY POLYCARBONATE IP44 INSPECTION WINDOW FOR USEPack size: **1 x EA**

- Length: 127 mm
- Width: 47 mm
- Height: 94 mm
- Material: Polycarbonate
- Colour: Grey
- For Use With: 46277-3, DIN 43880
- IP Rating: IP44

**2971235** 127 mm**MENNEKES GREY POLYCARBONATE IP44 INSPECTION WINDOW FOR USE**Pack size: **1 x EA**

- Length: 162 mm
- Width: 47 mm
- Height: 94 mm
- Material: Polycarbonate
- Colour: Grey
- For Use With: 46277-3, DIN 43880
- IP Rating: IP44

**2971241** 162 mm**MENNEKES GREY POLYCARBONATE IP44 INSPECTION WINDOW FOR USE**Pack size: **1 x EA**

- Length: 234 mm
- Width: 47 mm
- Height: 94 mm
- Material: Polycarbonate
- Colour: Grey
- For Use With: 46277-3, DIN 43880
- IP Rating: IP44

**2971263** 234 mm**RS PRO GREY ABS INSTRUMENT CASE, 120 X 60 X 30MM**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 120 mm
- External Width: 60 mm
- External Height: 30 mm
- External Dimensions: 120 x 60 x 30 mm
- Colour: Grey
- IP Rating: IP54
- Ventilated: No

**218898** ABS**ABS,2-PART,CASE,LIGHT GREY,DARK GREY,120MM,60MM,40MM**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 120 mm
- External Width: 60 mm
- External Height: 40 mm
- External Dimensions: 120 x 60 x 40 mm
- Colour: Grey
- IP Rating: IP54
- Ventilated: No

**219318** ABS**RS PRO GREY ABS INSTRUMENT CASE, 150 X 80 X 45MM**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 150 mm
- External Width: 80 mm
- External Height: 45 mm
- External Dimensions: 150 x 80 x 45 mm
- Colour: Grey
- IP Rating: IP54
- Ventilated: No

**219330** ABS**ABS,2-PART,CASE,LIGHT GREY,DARK GREY,150MM,80MM,60MM**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 150 mm
- External Width: 80 mm
- External Height: 60 mm
- External Dimensions: 150 x 80 x 60 mm
- Colour: Grey
- IP Rating: IP54
- Ventilated: No

**219346** ABS**RS PRO GREY ABS INSTRUMENT CASE, 190 X 100 X 40MM**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 190 mm
- External Width: 100 mm
- External Height: 40 mm
- External Dimensions: 190 x 100 x 40 mm
- Colour: Grey
- IP Rating: IP54
- Ventilated: No

**219380** ABS**RS PRO GREY ABS INSTRUMENT CASE, 190 X 100 X 80MM**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 190 mm
- External Width: 100 mm
- External Height: 80 mm
- External Dimensions: 190 x 100 x 80 mm
- Colour: Grey
- IP Rating: IP54
- Ventilated: No

**219403** ABS**ABS,2-PART,CASE,LIGHT GREY,DARK GREY,90MM,50MM,24MM**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 90 mm
- External Width: 50 mm
- External Height: 24 mm
- External Dimensions: 90 x 50 x 24 mm
- Colour: Grey
- IP Rating: IP54
- Ventilated: No

**219548** ABS**ENCLOSURE,ABS,MOULDED CASE,TWO**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 134 mm
- External Width: 129 mm
- External Height: 38 mm
- External Dimensions: 134 x 129 x 38 mm
- Colour: White
- Ventilated: No
- Carrying Handle: No

**220989** ABS**RS PRO WHITE ABS INSTRUMENT CASE, 159 X 154 X 64MM**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 159 mm
- External Width: 154 mm
- External Height: 64 mm
- External Dimensions: 159 x 154 x 64 mm
- Colour: White
- Ventilated: No
- Carrying Handle: No

**220995** ABS**RS PRO BLACK ANODISED ALUMINIUM INSTRUMENT CASE, 442 X**Pack size: **1 x EA**

- Body Material: Anodised Aluminium
- External Length: 442 mm
- External Width: 254 mm
- External Height: 88 mm
- External Dimensions: 442 x 254 x 88 mm
- Colour: Black
- Ventilated: No
- Carrying Handle: No

**226139** Anodised**RS PRO GREY COLD ROLLED STEEL INSTRUMENT CASE, 350 X 270 X**Pack size: **1 x EA**

- Body Material: Cold Rolled Steel
- External Length: 350 mm
- External Width: 270 mm
- External Height: 95 mm
- External Dimensions: 350 x 270 x 95 mm
- Colour: Grey
- Ventilated: No
- Carrying Handle: No

**231992** Cold Rolled Steel**ENCLOSURE,METAL CASE,GREY,310X230X80MM**Pack size: **1 x EA**

- Body Material: Cold Rolled Steel
- External Length: 310 mm
- External Width: 230 mm
- External Height: 80 mm
- External Dimensions: 310 x 230 x 80 mm
- Colour: Grey
- Ventilated: No
- Carrying Handle: No

**232002** Cold Rolled Steel**RS PRO WHITE COLD ROLLED STEEL INSTRUMENT CASE, 180 X 89 X 80MM**Pack size: **1 x EA**

- Body Material: Cold Rolled Steel
- External Length: 180 mm
- External Width: 89 mm
- External Height: 80 mm
- External Dimensions: 180 x 89 x 80 mm
- Colour: White
- Ventilated: Yes
- Carrying Handle: No

**232030** Cold Rolled Steel

RS PRO WHITE COLD ROLLED STEEL INSTRUMENT CASE, 200 X 123 X 92MM

Pack size: **1 x EA**

- Body Material: Cold Rolled Steel
- External Length: 200 mm
- External Width: 123 mm
- External Height: 92 mm
- External Dimensions: 200 x 123 x 92 mm
- Colour: White
- Ventilated: Yes
- Carrying Handle: No



232074 Cold Rolled Steel

RS PRO GREY COLD ROLLED STEEL INSTRUMENT CASE, 65 X 85 X 42MM

Pack size: **1 x EA**

- Body Material: Cold Rolled Steel
- External Length: 65 mm
- External Width: 85 mm
- External Height: 42 mm
- External Dimensions: 65 x 85 x 42 mm
- Colour: Grey
- Ventilated: No
- Carrying Handle: No



232125 Cold Rolled Steel

RS PRO GREY COLD ROLLED STEEL INSTRUMENT CASE, 200 X 200 X

Pack size: **1 x EA**

- Body Material: Cold Rolled Steel
- External Length: 200 mm
- External Width: 200 mm
- External Height: 100 mm
- External Dimensions: 200 x 200 x 100 mm
- Colour: Grey
- Ventilated: No
- Carrying Handle: No



232197 Cold Rolled Steel

RS PRO GREY COLD ROLLED STEEL INSTRUMENT CASE, 200 X 150 X

Pack size: **1 x EA**

- Body Material: Cold Rolled Steel
- External Length: 200 mm
- External Width: 150 mm
- External Height: 90 mm
- External Dimensions: 200 x 150 x 90 mm
- Colour: Grey
- Ventilated: No
- Carrying Handle: No



232204 Cold Rolled Steel

RS PRO GREY COLD ROLLED STEEL INSTRUMENT CASE, 120 X 150 X 80MM

Pack size: **1 x EA**

- Body Material: Cold Rolled Steel
- External Length: 120 mm
- External Width: 150 mm
- External Height: 80 mm
- External Dimensions: 120 x 150 x 80 mm
- Colour: Grey
- Ventilated: No
- Carrying Handle: No



232210 Cold Rolled Steel

RS PRO GREY COLD ROLLED STEEL INSTRUMENT CASE, 204 X 152 X 76MM

Pack size: **1 x EA**

- Body Material: Cold Rolled Steel
- External Length: 204 mm
- External Width: 152 mm
- External Height: 76 mm
- External Dimensions: 204 x 152 x 76 mm
- Colour: Grey
- Ventilated: No
- Carrying Handle: No



232232 Cold Rolled Steel

ENCLOSURE, METAL CASE, GREY, C/W INTEGRAL HANDLE, ALUMINIUM FRONT

Pack size: **1 x EA**

- Body Material: Cold Rolled Steel
- External Length: 245 mm
- External Width: 105 mm
- External Height: 137 mm
- External Dimensions: 245 x 137 x 105 mm
- Colour: Grey
- Ventilated: No
- Carrying Handle: Yes



232260 Cold Rolled Steel

RS PRO GREY COLD ROLLED STEEL INSTRUMENT CASE, 300 X 200 X

Pack size: **1 x EA**

- Body Material: Cold Rolled Steel
- External Length: 300 mm
- External Width: 200 mm
- External Height: 100 mm
- External Dimensions: 300 x 200 x 100 mm
- Colour: Grey
- Ventilated: No
- Carrying Handle: No



232276 Cold Rolled Steel

RS PRO GREY COLD ROLLED STEEL INSTRUMENT CASE, 406 X 197 X

Pack size: **1 x EA**

- Body Material: Cold Rolled Steel
- External Length: 406 mm
- External Width: 197 mm
- External Height: 159 mm
- External Dimensions: 406 x 197 x 159 mm
- Colour: Grey
- Ventilated: No
- Carrying Handle: No



232282 Cold Rolled Steel

RS PRO GREY, ALUMINIUM & STEEL INSTRUMENT CASE, 432 X 200 X

Pack size: **1 x EA**

- Body Material: Aluminium, Steel
- External Length: 432 mm
- External Width: 200 mm
- External Height: 88 mm
- External Dimensions: 432 x 200 x 88 mm
- Colour: Grey
- Ventilated: No
- Carrying Handle: No



232298 Aluminium, Steel

RS PRO GREY COLD ROLLED STEEL INSTRUMENT CASE, 254 X 197 X

Pack size: **1 x EA**

- Body Material: Cold Rolled Steel
- External Length: 254 mm
- External Width: 197 mm
- External Height: 159 mm
- External Dimensions: 254 x 197 x 159 mm
- Colour: Grey
- Ventilated: No
- Carrying Handle: No



232311 Cold Rolled Steel

ENCLOSURE, POLYSTYRENE, INSTRUMENT CASE, LIGHT

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 190 mm
- External Width: 140 mm
- External Height: 80 mm
- External Dimensions: 190 x 140 x 80 mm
- Colour: Grey
- IP Rating: IP54
- Ventilated: No



315933 ABS

RS PRO GREY ABS INSTRUMENT CASE, 190 X 140 X 60MM

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 190 mm
- External Width: 140 mm
- External Height: 60 mm
- External Dimensions: 190 x 140 x 60 mm
- Colour: Grey
- IP Rating: IP54
- Ventilated: No



315961 ABS

ENCLOSURE, INSTRUMENT CASE, DIN 43700, 96X48X138MM

Pack size: **1 x EA**

- Body Material: Noryl
- External Length: 138 mm
- External Width: 96 mm
- External Height: 48 mm
- External Dimensions: 48 x 96 x 138 mm
- Colour: Black
- Ventilated: No
- Carrying Handle: No



500005 Noryl

ENCLOSURE, INSTRUMENT CASE, DIN 43700, 96X96X138MM

Pack size: **1 x EA**

- Body Material: Noryl
- External Length: 138 mm
- External Width: 96 mm
- External Height: 96 mm
- External Dimensions: 96 x 96 x 138 mm
- Colour: Black
- Ventilated: No
- Carrying Handle: No



500011 Noryl

ENCLOSURE, INSTRUMENT CASE, DIN 43700, 72X72X138MM

Pack size: **1 x EA**

- Body Material: Noryl
- External Length: 116 mm
- External Width: 72 mm
- External Height: 72 mm
- External Dimensions: 72 x 72 x 116 mm
- Colour: Black
- Ventilated: No
- Carrying Handle: No



500027 Noryl

**ENCLOSURE, INSTRUMENT CASE, DIN
43700, 144 X 72 X 138 MM**Pack size: **1 x EA**

- Body Material: Noryl
- External Length: 144 mm
- External Width: 138 mm
- External Height: 72 mm
- External Dimensions: 72 x 138 x 144 mm
- Colour: Black
- Ventilated: No
- Carrying Handle: No

**500033** Noryl**ENCLOSURE, INSTRUMENT CASE, DIN
43700, 144 X 96 X 138 MM**Pack size: **1 x EA**

- Body Material: Noryl
- External Length: 144 mm
- External Width: 138 mm
- External Height: 96 mm
- External Dimensions: 96 x 138 x 144 mm
- Colour: Black
- Ventilated: No
- Carrying Handle: No

**500049** Noryl**RS PRO BLACK ANODISED
ALUMINIUM INSTRUMENT CASE, 165 X**Pack size: **1 x EA**

- Body Material: Anodised Aluminium
- External Length: 165 mm
- External Width: 105 mm
- External Height: 61 mm
- External Dimensions: 165 x 105 x 61 mm
- Colour: Black
- Ventilated: Yes
- Carrying Handle: No

**1853209** Anodised**RS PRO INSTRUMENT CASE**Pack size: **1 x EA**

- Length: 40 mm
- Width: 30 mm
- Material: ABS

**1951523** 40 mm**RS PRO INSTRUMENT CASE**Pack size: **1 x EA**

- Length: 40 mm
- Width: 16 mm
- Material: Aluminium

**1951535** 40 mm**RS PRO BLACK ALUMINIUM
INSTRUMENT CASE, 120 X 63.5 X**Pack size: **1 x EA**

- Body Material: Aluminium
- External Length: 120 mm
- External Width: 63.5 mm
- External Height: 30 mm
- External Dimensions: 120 x 63.5 x 30 mm
- Colour: Black

**1951537** Aluminium**RS PRO SILVER ANODISED
ALUMINIUM INSTRUMENT CASE, 80 X**Pack size: **1 x EA**

- Body Material: Anodised Aluminium
- External Length: 80 mm
- External Width: 63.5 mm
- External Height: 30 mm
- External Dimensions: 80 x 63.5 x 30 mm
- Colour: Silver

**1951540** Anodised**RS PRO SILVER ANODISED
ALUMINIUM INSTRUMENT CASE, 80 X**Pack size: **1 x EA**

- Body Material: Anodised Aluminium
- External Length: 80 mm
- External Width: 108.5 mm
- External Height: 45 mm
- External Dimensions: 80 x 108.5 x 45 mm
- Colour: Silver

**1951545** Anodised**RS PRO SILVER ANODISED
ALUMINIUM INSTRUMENT CASE, 160 X**Pack size: **1 x EA**

- Body Material: Anodised Aluminium
- External Length: 160 mm
- External Width: 108.5 mm
- External Height: 45 mm
- External Dimensions: 160 x 108.5 x 45 mm
- Colour: Silver

**1951546** Anodised**RS PRO SILVER ANODISED
ALUMINIUM INSTRUMENT CASE, 220 X**Pack size: **1 x EA**

- Body Material: Anodised Aluminium
- External Length: 220 mm
- External Width: 108.5 mm
- External Height: 45 mm
- External Dimensions: 220 x 108.5 x 45 mm
- Colour: Silver

**1951547** Anodised**RS PRO SILVER ANODISED
ALUMINIUM INSTRUMENT CASE, 160 X**Pack size: **1 x EA**

- Body Material: Anodised Aluminium
- External Length: 160 mm
- External Width: 169.8 mm
- External Height: 53.8 mm
- External Dimensions: 160 x 169.8 x 53.8 mm
- Colour: Silver

**1951549** Anodised**RS PRO SILVER ANODISED
ALUMINIUM INSTRUMENT CASE, 220 X**Pack size: **1 x EA**

- Body Material: Anodised Aluminium
- External Length: 220 mm
- External Width: 169.8 mm
- External Height: 53.8 mm
- External Dimensions: 220 x 169.8 x 53.8 mm
- Colour: Silver

**1951550** Anodised**RS PRO BEIGE ABS INSTRUMENT
CASE, 105 X 80 X 40 MM**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 105 mm
- External Width: 80 mm
- External Height: 40 mm
- External Dimensions: 105 x 80 x 40 mm
- Colour: Beige

**1981378** ABS**RS PRO BLACK ABS INSTRUMENT
CASE, 105 X 80 X 40 MM**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 105 mm
- External Width: 80 mm
- External Height: 40 mm
- External Dimensions: 105 x 80 x 40 mm
- Colour: Black

**1981379** ABS**RS PRO BEIGE ABS INSTRUMENT
CASE, 50 X 100 X 130 MM**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 50 mm
- External Width: 100 mm
- External Height: 130 mm
- External Dimensions: 50 x 100 x 130 mm
- Colour: Beige

**1981386** ABS**RS PRO BEIGE ABS INSTRUMENT
CASE, 70 X 140 X 190 MM**Pack size: **1 x EA**

- Body Material: ABS
- External Length: 70 mm
- External Width: 140 mm
- External Height: 190 mm
- External Dimensions: 70 x 140 x 190 mm
- Colour: Beige

**1981388** ABS

RS PRO BEIGE ABS INSTRUMENT CASE, 30 X 140 X 190MM

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 30 mm
- External Width: 140 mm
- External Height: 190 mm
- External Dimensions: 30 x 140 x 190 mm
- Colour: Beige



1981390 ABS

RS PRO BEIGE ABS INSTRUMENT CASE, 100 X 180 X 250MM

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 100 mm
- External Width: 180 mm
- External Height: 250 mm
- External Dimensions: 100 x 180 x 250 mm
- Colour: Beige



1981391 ABS

RS PRO BEIGE ABS INSTRUMENT CASE, 75 X 180 X 250MM

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 75 mm
- External Width: 180 mm
- External Height: 250 mm
- External Dimensions: 75 x 180 x 250 mm
- Colour: Beige



1981392 ABS

RS PRO WHITE ABS INSTRUMENT CASE, 159 X 205 X 64MM

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 159 mm
- External Width: 205 mm
- External Height: 64 mm
- External Dimensions: 159 x 205 x 64 mm
- Colour: White
- Ventilated: No
- Carrying Handle: No



2205566 ABS

RS PRO BLACK ABS INSTRUMENT CASE, 231 X 212 X 67MM

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 231 mm
- External Width: 212 mm
- External Height: 67 mm
- External Dimensions: 231 x 212 x 67 mm
- Colour: Black
- Ventilated: No
- Carrying Handle: No



2374426 ABS

ENCLOSURE,CASE,PLASTIC,ABS,CF-275-000

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 231 mm
- External Width: 212 mm
- External Height: 80 mm
- External Dimensions: 231 x 212 x 80 mm
- Colour: Black
- Ventilated: No
- Carrying Handle: No



2374432 ABS

ENCLOSURE,CASE,PLASTIC,ABS,DM2-039

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 291 mm
- External Width: 264 mm
- External Height: 60 mm
- External Dimensions: 291 x 264 x 60 mm
- Colour: White
- Ventilated: No
- Carrying Handle: No



2374454 ABS

ENCLOSURE,CASE,PLASTIC,ABS,DM3-039

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 291 mm
- External Width: 264 mm
- External Height: 86 mm
- External Dimensions: 291 x 264 x 86 mm
- Colour: White
- Ventilated: No
- Carrying Handle: No



2374460 ABS

ENCLOSURE,CASE,PLASTIC,ABS,DM4-039

Pack size: **1 x EA**

- Body Material: ABS
- External Length: 291 mm
- External Width: 264 mm
- External Height: 111 mm
- External Dimensions: 291 x 264 x 111 mm
- Colour: White
- Ventilated: No
- Carrying Handle: No



2374476 ABS

RS PRO BLACK ANODISED ALUMINIUM INSTRUMENT CASE, 285 X

Pack size: **1 x EA**

- Body Material: Anodised Aluminium
- External Length: 285 mm
- External Width: 81.4 mm
- External Height: 40 mm
- External Dimensions: 285 x 81.4 x 40 mm
- Colour: Black
- Ventilated: Yes
- Carrying Handle: No



4687471 Anodised

RS PRO GREY STEEL INSTRUMENT CASE, 178 X 305 X 65MM

Pack size: **1 x EA**

- Body Material: Steel
- External Length: 178 mm
- External Width: 305 mm
- External Height: 65 mm
- External Dimensions: 178 x 305 x 65 mm
- Colour: Grey
- Ventilated: Yes
- Carrying Handle: No



7545951 Steel

1.5UX178DX203W ELECTRONIC ENCLOSURE

Pack size: **1 x EA**

- Body Material: Steel
- External Length: 178 mm
- External Width: 203 mm
- External Height: 65 mm
- External Dimensions: 178 x 203 x 65 mm
- Colour: Black
- Ventilated: Yes
- Carrying Handle: No



7545957 Steel

1.5UX279DX203W ELECTRONIC ENCLOSURE

Pack size: **1 x EA**

- Body Material: Steel
- External Length: 279 mm
- External Width: 203 mm
- External Height: 65 mm
- External Dimensions: 279 x 203 x 65 mm
- Colour: Black
- Ventilated: Yes
- Carrying Handle: No



7545963 Steel

RS PRO BLACK STEEL INSTRUMENT CASE, 178 X 305 X 87MM

Pack size: **1 x EA**

- Body Material: Steel
- External Length: 178 mm
- External Width: 305 mm
- External Height: 87 mm
- External Dimensions: 178 x 305 x 87 mm
- Colour: Black
- Ventilated: Yes
- Carrying Handle: No



7545973 Steel

RS PRO BLACK STEEL INSTRUMENT CASE, 279 X 305 X 87MM

Pack size: **1 x EA**

- Body Material: Steel
- External Length: 279 mm
- External Width: 305 mm
- External Height: 87 mm
- External Dimensions: 279 x 305 x 87 mm
- Colour: Black
- Ventilated: Yes
- Carrying Handle: No



7545985 Steel

RS PRO BLACK STEEL INSTRUMENT CASE, 279 X 432 X 87MM

Pack size: **1 x EA**

- Body Material: Steel
- External Length: 279 mm
- External Width: 432 mm
- External Height: 87 mm
- External Dimensions: 279 x 432 x 87 mm
- Colour: Black
- Ventilated: Yes
- Carrying Handle: No



7545989 Steel

**RS PRO BLACK STEEL PROJECT BOX,
279 X 203 X 131MM**Pack size: **1 x EA**

- Body Material: Steel
- External Length: 279 mm
- External Width: 203 mm
- External Height: 131 mm
- External Dimensions: 279 x 203 x 131 mm
- Colour: Black
- Ventilated: Yes
- Carrying Handle: No

**7545995** Steel**RS PRO GREY STEEL INSTRUMENT
CASE, 279 X 432 X 131MM**Pack size: **1 x EA**

- Body Material: Steel
- External Length: 279 mm
- External Width: 432 mm
- External Height: 131 mm
- External Dimensions: 279 x 432 x 131 mm
- Colour: Grey
- Ventilated: Yes
- Carrying Handle: No

**7546001** Steel**RS PRO BEIGE, GREY STEEL
INSTRUMENT CASE, 178 X 305 X**Pack size: **1 x EA**

- Body Material: Steel
- External Length: 178 mm
- External Width: 305 mm
- External Height: 175 mm
- External Dimensions: 178 x 305 x 175 mm
- Colour: Beige, Grey
- Ventilated: Yes
- Carrying Handle: No

**7546005** Steel**3UX279DX305W ELECTRONIC
ENCLOSURE**Pack size: **1 x EA**

- Body Material: Steel
- External Length: 279 mm
- External Width: 305 mm
- External Height: 131 mm
- External Dimensions: 279 x 305 x 131 mm
- Colour: RAL 7035 Light Grey
- Ventilated: Yes
- Carrying Handle: No

**7546008** Steel**4UX279DX203W ELECTRONIC
ENCLOSURE**Pack size: **1 x EA**

- Body Material: Steel
- External Length: 279 mm
- External Width: 203 mm
- External Height: 175 mm
- External Dimensions: 279 x 203 x 175 mm
- Colour: Black
- Ventilated: Yes
- Carrying Handle: No

**7546017** Steel**5UX279DX203W ELECTRONIC
ENCLOSURE**Pack size: **1 x EA**

- Body Material: Steel
- External Length: 279 mm
- External Width: 203 mm
- External Height: 219 mm
- External Dimensions: 279 x 203 x 219 mm
- Colour: Black
- Ventilated: Yes
- Carrying Handle: No

**7546023** Steel**RS PRO GREY STEEL INSTRUMENT
CASE, 279 X 432 X 219MM**Pack size: **1 x EA**

- Body Material: Steel
- External Length: 279 mm
- External Width: 432 mm
- External Height: 219 mm
- External Dimensions: 279 x 432 x 219 mm
- Colour: Grey
- Ventilated: Yes
- Carrying Handle: No

**7546036** Steel**RS PRO RAL 7032 STEEL JUNCTION
BOX, IP66, 300 X 200 X 120MM**Pack size: **1 x EA**

- Dimensions (L x W x H): 300 x 200 x 120 mm
- Material: Steel
- Length: 300 mm
- Width: 200 mm
- Height: 120 mm
- IP Rating: IP66
- Colour: RAL 7032

**122030** 300 x 200 x 120**RS PRO RAL 7032 STEEL JUNCTION
BOX, IP66, 400 X 200 X 120MM**Pack size: **1 x EA**

- Dimensions (L x W x H): 400 x 200 x 120 mm
- Material: Steel
- Length: 400 mm
- Width: 200 mm
- Height: 120 mm
- IP Rating: IP66
- Colour: RAL 7032

**122046** 400 x 200 x 120**RS PRO RAL 7032 STEEL JUNCTION
BOX, IP66, 300 X 300 X 120MM**Pack size: **1 x EA**

- Dimensions (L x W x H): 300 x 300 x 120 mm
- Material: Steel
- Length: 300 mm
- Width: 300 mm
- Height: 120 mm
- IP Rating: IP66
- Colour: RAL 7032

**122052** 300 x 300 x 120**RS PRO RAL 7032 STEEL JUNCTION
BOX, IP66, 400 X 300 X 120MM**Pack size: **1 x EA**

- Dimensions (L x W x H): 400 x 300 x 120 mm
- Material: Steel
- Length: 400 mm
- Width: 300 mm
- Height: 120 mm
- IP Rating: IP66
- Colour: RAL 7032

**122068** 400 x 300 x 120**RS PRO RAL 7032 STEEL JUNCTION
BOX, IP66, 200 X 200 X 120MM**Pack size: **1 x EA**

- Dimensions (L x W x H): 200 x 200 x 120 mm
- Material: Steel
- Length: 200 mm
- Width: 200 mm
- Height: 120 mm
- IP Rating: IP66
- Colour: RAL 7032

**122096** 200 x 200 x 120**RS PRO RAL 7032 STEEL JUNCTION
BOX, IP66, 150 X 150 X 80MM**Pack size: **1 x EA**

- Dimensions (L x W x H): 150 x 150 x 80 mm
- Material: Steel
- Length: 150 mm
- Width: 150 mm
- Height: 80 mm
- IP Rating: IP66
- Colour: RAL 7032

**122103** 150 x 150 x 80 mm**RS PRO RAL 7032 STEEL JUNCTION
BOX, IP66, 300 X 150 X 80MM**Pack size: **1 x EA**

- Dimensions (L x W x H): 300 x 150 x 80 mm
- Material: Steel
- Length: 300 mm
- Width: 150 mm
- Height: 80 mm
- IP Rating: IP66
- Colour: RAL 7032

**122119** 300 x 150 x 80**ENCLOSURE,ELECTRICAL,INDUSTRIAL,
TERMINAL,INLINE,200X200X80MM**Pack size: **1 x EA**

- Dimensions (L x W x H): 200 x 200 x 80 mm
- Material: Steel
- Length: 200 mm
- Width: 200 mm
- Height: 80 mm
- IP Rating: IP66
- Colour: RAL 7032

**122125** 200 x 200 x 80**RS PRO RAL 7032 STEEL JUNCTION
BOX, IP66, 300 X 200 X 80MM**Pack size: **1 x EA**

- Dimensions (L x W x H): 300 x 200 x 80 mm
- Material: Steel
- Length: 300 mm
- Width: 200 mm
- Height: 80 mm
- IP Rating: IP66
- Colour: RAL 7032

**122131** 300 x 200 x 80

RS PRO RAL 7032 STEEL JUNCTION BOX, IP66, 400 X 200 X 80MM

Pack size: **1 x EA**

- Dimensions (L x W x H): 400 x 200 x 80 mm
- Material: Steel
- Length: 400 mm
- Width: 200 mm
- Height: 80 mm
- IP Rating: IP66
- Colour: RAL 7032



122147 400 x 200 x 80

RS PRO RAL 7032 STEEL JUNCTION BOX, IP66, 300 X 150 X 120MM

Pack size: **1 x EA**

- Dimensions (L x W x H): 300 x 150 x 120 mm
- Material: Steel
- Length: 300 mm
- Width: 150 mm
- Height: 120 mm
- IP Rating: IP66
- Colour: RAL 7032



122153 300 x 150 x 120

RS PRO BLUE JUNCTION BOX, IP66, 150 X 150 X 80MM

Pack size: **1 x EA**

- Dimensions (L x W x H): 150 x 150 x 80 mm
- Length: 150 mm
- Width: 150 mm
- Height: 80 mm
- IP Rating: IP66
- Colour: Blue
- Number of Ways: 0
- Series: TLX



1441348 150 x 150 x 80 mm

RS PRO BLACK JUNCTION BOX, IP66, ATEX, IECEx, 80 X 75 X 55MM

Pack size: **1 x EA**

- Dimensions (L x W x H): 80 x 75 x 55 mm
- Length: 80 mm
- Width: 75 mm
- Height: 55 mm
- IP Rating: IP66
- Colour: Black
- Hazardous Area Certification: ATEX, IECEx



1444450 80 x 75 x 55 mm

RS PRO BLACK JUNCTION BOX, IP66, ATEX, IECEx, 110 X 75 X 55MM

Pack size: **1 x EA**

- Dimensions (L x W x H): 110 x 75 x 55 mm
- Length: 110 mm
- Width: 75 mm
- Height: 55 mm
- IP Rating: IP66
- Colour: Black
- Hazardous Area Certification: ATEX, IECEx



1444451 110 x 75 x 55 mm

RS PRO BLACK JUNCTION BOX, IP66, ATEX, IECEx, 122 X 120 X 90MM

Pack size: **1 x EA**

- Dimensions (L x W x H): 122 x 120 x 90 mm
- Length: 122 mm
- Width: 120 mm
- Height: 90 mm
- IP Rating: IP66
- Colour: Black
- Hazardous Area Certification: ATEX, IECEx



1444452 122 x 120 x 90 mm

RS PRO BLACK JUNCTION BOX, IP66, ATEX, IECEx, 160 X 75 X 55MM

Pack size: **1 x EA**

- Dimensions (L x W x H): 160 x 75 x 55 mm
- Length: 160 mm
- Width: 75 mm
- Height: 55 mm
- IP Rating: IP66
- Colour: Black
- Hazardous Area Certification: ATEX, IECEx



1444453 160 x 75 x 55 mm

RS PRO BLACK JUNCTION BOX, IP66, ATEX, IECEx, 160 X 75 X 75MM

Pack size: **1 x EA**

- Dimensions (L x W x H): 160 x 75 x 75 mm
- Length: 160 mm
- Width: 75 mm
- Height: 75 mm
- IP Rating: IP66
- Colour: Black
- Hazardous Area Certification: ATEX, IECEx



1444454 160 x 75 x 75 mm

RS PRO BLACK JUNCTION BOX, IP66, ATEX, IECEx, 160 X 160 X 90MM

Pack size: **1 x EA**

- Dimensions (L x W x H): 160 x 160 x 90 mm
- Length: 160 mm
- Width: 160 mm
- Height: 90 mm
- IP Rating: IP66
- Colour: Black
- Hazardous Area Certification: ATEX, IECEx



1444455 160 x 160 x 90 mm

RS PRO BLACK JUNCTION BOX, IP66, ATEX, IECEx, 190 X 75 X 55MM

Pack size: **1 x EA**

- Dimensions (L x W x H): 190 x 75 x 55 mm
- Length: 190 mm
- Width: 75 mm
- Height: 55 mm
- IP Rating: IP66
- Colour: Black
- Hazardous Area Certification: ATEX, IECEx



1444456 190 x 75 x 55 mm

RS PRO BLACK JUNCTION BOX, IP66, ATEX, IECEx, 220 X 120 X 90MM

Pack size: **1 x EA**

- Dimensions (L x W x H): 220 x 120 x 90 mm
- Length: 220 mm
- Width: 120 mm
- Height: 90 mm
- IP Rating: IP66
- Colour: Black
- Hazardous Area Certification: ATEX, IECEx



1444457 220 x 120 x 90

RS PRO BLACK JUNCTION BOX, IP66, ATEX, IECEx, 255 X 250 X 120MM

Pack size: **1 x EA**

- Dimensions (L x W x H): 255 x 250 x 120 mm
- Length: 255 mm
- Width: 250 mm
- Height: 120 mm
- IP Rating: IP66
- Colour: Black
- Hazardous Area Certification: ATEX, IECEx



1444458 255 x 250 x 120

RS PRO BLACK JUNCTION BOX, IP66, ATEX, IECEx, 260 X 160 X 90MM

Pack size: **1 x EA**

- Dimensions (L x W x H): 260 x 160 x 90 mm
- Length: 260 mm
- Width: 160 mm
- Height: 90 mm
- IP Rating: IP66
- Colour: Black
- Hazardous Area Certification: ATEX, IECEx



1444459 260 x 160 x 90

RS PRO BLACK JUNCTION BOX, IP66, ATEX, IECEx, 360 X 160 X 90MM

Pack size: **1 x EA**

- Dimensions (L x W x H): 360 x 160 x 90 mm
- Length: 360 mm
- Width: 160 mm
- Height: 90 mm
- IP Rating: IP66
- Colour: Black
- Hazardous Area Certification: ATEX, IECEx



1444460 360 x 160 x 90

RS PRO BLACK JUNCTION BOX, IP66, ATEX, IECEx, 400 X 250 X 120MM

Pack size: **1 x EA**

- Dimensions (L x W x H): 400 x 250 x 120 mm
- Length: 400 mm
- Width: 250 mm
- Height: 120 mm
- IP Rating: IP66
- Colour: Black
- Hazardous Area Certification: ATEX, IECEx



1444461 400 x 250 x 120

RS PRO BLACK JUNCTION BOX, IP66, ATEX, IECEx, 400 X 405 X 120MM

Pack size: **1 x EA**

- Dimensions (L x W x H): 400 x 405 x 120 mm
- Length: 400 mm
- Width: 405 mm
- Height: 120 mm
- IP Rating: IP66
- Colour: Black
- Hazardous Area Certification: ATEX, IECEx



1444462 400 x 405 x 120

**RS PRO UNPAINTED STAINLESS STEEL
TERMINAL BOX, IP66, 400 X 120 X**Pack size: **1 x EA**

- Dimensions (L x W x H): 400 x 120 x 200 mm
- Material: Stainless Steel
- Length: 400 mm
- Width: 120 mm
- Height: 200 mm
- IP Rating: IP66
- Colour: Unpainted

**7491848** 400 x 120 x 200**RS PRO UNPAINTED STAINLESS STEEL
TERMINAL BOX, IP66, 200 X 120 X**Pack size: **1 x EA**

- Dimensions (L x W x H): 200 x 120 x 200 mm
- Material: Stainless Steel
- Length: 200 mm
- Width: 120 mm
- Height: 200 mm
- IP Rating: IP66
- Colour: Unpainted

**7491854** 200 x 120 x 200**S/STEEL 304 TERMINAL BOX
150X150X80MM**Pack size: **1 x EA**

- Dimensions (L x W x H): 150 x 80 x 150 mm
- Material: Stainless Steel
- Length: 150 mm
- Width: 80 mm
- Height: 150 mm
- IP Rating: IP66
- Colour: Unpainted

**7491857** 150 x 80 x 150 mm**RS PRO UNPAINTED STAINLESS STEEL
TERMINAL BOX, IP66, 150 X 80 X**Pack size: **1 x EA**

- Dimensions (L x W x H): 150 x 80 x 150 mm
- Material: Stainless Steel
- Length: 150 mm
- Width: 80 mm
- Height: 150 mm
- IP Rating: IP66
- Colour: Unpainted

**7491860** 150 x 80 x 150 mm**RS PRO UNPAINTED STAINLESS STEEL
TERMINAL BOX, IP66, 300 X 80 X**Pack size: **1 x EA**

- Dimensions (L x W x H): 300 x 80 x 150 mm
- Material: Stainless Steel
- Length: 300 mm
- Width: 80 mm
- Height: 150 mm
- IP Rating: IP66
- Colour: Unpainted

**7491863** 300 x 80 x 150**RS PRO UNPAINTED STAINLESS STEEL
TERMINAL BOX, IP66, 200 X 200 X**Pack size: **1 x EA**

- Dimensions (L x W x H): 200 x 200 x 80 mm
- Material: Stainless Steel
- Length: 200 mm
- Width: 80 mm
- Height: 200 mm
- IP Rating: IP66
- Colour: Unpainted

**7491866** 200 x 200 x 80**RS PRO UNPAINTED STAINLESS STEEL
TERMINAL BOX, IP66, 300 X 80 X**Pack size: **1 x EA**

- Dimensions (L x W x H): 300 x 80 x 200 mm
- Material: Stainless Steel
- Length: 300 mm
- Width: 80 mm
- Height: 200 mm
- IP Rating: IP66
- Colour: Unpainted

**7491876** 300 x 80 x 200**RS PRO RAL 7035 LIGHT GREY MILD
STEEL TERMINAL BOX, IP66, 150 X 80 X**Pack size: **1 x EA**

- Dimensions (L x W x H): 150 x 80 x 150 mm
- Material: Mild Steel
- Length: 150 mm
- Width: 80 mm
- Height: 150 mm
- IP Rating: IP66
- Colour: RAL 7035 Light Grey

**7491888** 150 x 80 x 150 mm**RS PRO RAL 7035 LIGHT GREY MILD
STEEL TERMINAL BOX, IP66, 300 X 120**Pack size: **1 x EA**

- Dimensions (L x W x H): 300 x 120 x 200 mm
- Material: Mild Steel
- Length: 300 mm
- Width: 120 mm
- Height: 200 mm
- IP Rating: IP66
- Colour: RAL 7035 Light Grey

**7491891** 300 x 120 x 200**RS PRO RAL 7035 LIGHT GREY MILD
STEEL TERMINAL BOX, IP66, 300 X 120**Pack size: **1 x EA**

- Dimensions (L x W x H): 300 x 120 x 150 mm
- Material: Mild Steel
- Length: 300 mm
- Width: 120 mm
- Height: 150 mm
- IP Rating: IP66
- Colour: RAL 7035 Light Grey

**7491894** 300 x 120 x 150**RS PRO UNPAINTED STAINLESS STEEL
TERMINAL BOX, IP66, 300 X 150 X**Pack size: **1 x EA**

- Dimensions (L x W x H): 300 x 150 x 80 mm
- Material: Stainless Steel
- Length: 300 mm
- Width: 150 mm
- Height: 80 mm
- IP Rating: IP66
- Colour: Unpainted

**7587046** 300 x 150 x 80**RS PRO UNPAINTED STAINLESS STEEL
TERMINAL BOX, IP66, 200 X 200 X**Pack size: **1 x EA**

- Dimensions (L x W x H): 200 x 200 x 80 mm
- Material: Stainless Steel
- Length: 200 mm
- Width: 200 mm
- Height: 80 mm
- IP Rating: IP66
- Colour: Unpainted

**7587052** 200 x 200 x 80**RS PRO UNPAINTED STAINLESS STEEL
TERMINAL BOX, IP66, 300 X 150 X**Pack size: **1 x EA**

- Dimensions (L x W x H): 300 x 150 x 120 mm
- Material: Stainless Steel
- Length: 300 mm
- Width: 150 mm
- Height: 120 mm
- IP Rating: IP66
- Colour: Unpainted

**7587056** 300 x 150 x 120**RS PRO UNPAINTED STAINLESS STEEL
TERMINAL BOX, IP66, 175 X 175 X**Pack size: **1 x EA**

- Dimensions (L x W x H): 175 x 175 x 120 mm
- Material: Stainless Steel
- Length: 175 mm
- Width: 175 mm
- Height: 120 mm
- IP Rating: IP66
- Colour: Unpainted

**7587059** 175 x 175 x 120**RS PRO UNPAINTED STAINLESS STEEL
TERMINAL BOX, IP66, 300 X 200 X**Pack size: **1 x EA**

- Dimensions (L x W x H): 300 x 200 x 80 mm
- Material: Stainless Steel
- Length: 300 mm
- Width: 200 mm
- Height: 80 mm
- IP Rating: IP66
- Colour: Unpainted
- Number of Ways: 0

**8428302** 300 x 200 x 80**IP66 TERMINAL BOX, M/STEEL,
150X150X120**Pack size: **1 x EA**

- Dimensions (L x W x H): 150 x 150 x 120 mm
- Material: Steel
- Length: 150 mm
- Width: 150 mm
- Height: 120 mm
- IP Rating: IP66
- Colour: RAL 7032
- Number of Ways: 0

**8428308** 150 x 150 x 120

RS PRO UNPAINTED STAINLESS STEEL TERMINAL BOX, IP66, 300 X 150 X

Pack size: **1 x EA**

- Dimensions (L x W x H): 300 x 150 x 80 mm
- Material: Stainless Steel
- Length: 300 mm
- Width: 150 mm
- Height: 80 mm
- IP Rating: IP66
- Colour: Unpainted
- Number of Ways: 0



8428311 300 x 150 x 80

RS PRO UNPAINTED STAINLESS STEEL TERMINAL BOX, IP66, 200 X 200 X

Pack size: **1 x EA**

- Dimensions (L x W x H): 200 x 200 x 80 mm
- Material: Stainless Steel
- Length: 200 mm
- Width: 200 mm
- Height: 80 mm
- IP Rating: IP66
- Colour: Unpainted
- Number of Ways: 0



8428314 200 x 200 x 80

RS PRO UNPAINTED STAINLESS STEEL TERMINAL BOX, IP66, 300 X 150 X

Pack size: **1 x EA**

- Dimensions (L x W x H): 300 x 150 x 120 mm
- Material: Stainless Steel
- Length: 300 mm
- Width: 150 mm
- Height: 120 mm
- IP Rating: IP66
- Colour: Unpainted
- Number of Ways: 0



8428318 300 x 150 x 120

RS PRO UNPAINTED STAINLESS STEEL TERMINAL BOX, IP66, 300 X 200 X

Pack size: **1 x EA**

- Dimensions (L x W x H): 300 x 200 x 120 mm
- Material: Stainless Steel
- Length: 300 mm
- Width: 200 mm
- Height: 120 mm
- IP Rating: IP66
- Colour: Unpainted
- Number of Ways: 0



8428320 300 x 200 x 120

RS PRO UNPAINTED STAINLESS STEEL TERMINAL BOX, IP66, 400 X 200 X

Pack size: **1 x EA**

- Dimensions (L x W x H): 400 x 200 x 120 mm
- Material: Stainless Steel
- Length: 400 mm
- Width: 200 mm
- Height: 120 mm
- IP Rating: IP66
- Colour: Unpainted
- Number of Ways: 0



8428324 400 x 200 x 120

RS PRO UNPAINTED STAINLESS STEEL TERMINAL BOX, IP66, 175 X 175 X

Pack size: **1 x EA**

- Dimensions (L x W x H): 175 x 175 x 120 mm
- Material: Stainless Steel
- Length: 175 mm
- Width: 175 mm
- Height: 120 mm
- IP Rating: IP66
- Colour: Unpainted
- Number of Ways: 0



8428327 175 x 175 x 120

IP66 TERMINAL BOX, S/STEEL, 150X150X80

Pack size: **1 x EA**

- Dimensions (L x W x H): 150 x 150 x 80 mm
- Material: Stainless Steel
- Length: 150 mm
- Width: 150 mm
- Height: 80 mm
- IP Rating: IP66
- Colour: Unpainted
- Number of Ways: 0



8428330 150 x 150 x 80 mm

RS PRO UNPAINTED STAINLESS STEEL TERMINAL BOX, IP66, 300 X 300 X

Pack size: **1 x EA**

- Dimensions (L x W x H): 300 x 300 x 120 mm
- Material: Stainless Steel
- Length: 300 mm
- Width: 300 mm
- Height: 120 mm
- IP Rating: IP66
- Colour: Unpainted
- Number of Ways: 0



8428333 300 x 300 x 120

RS PRO UNPAINTED STAINLESS STEEL TERMINAL BOX, IP66, 200 X 200 X

Pack size: **1 x EA**

- Dimensions (L x W x H): 200 x 200 x 120 mm
- Material: Stainless Steel
- Length: 200 mm
- Width: 200 mm
- Height: 120 mm
- IP Rating: IP66
- Colour: Unpainted
- Number of Ways: 0



8428336 200 x 200 x 120

RS PRO RAL 7032 STEEL JUNCTION BOX, IP65, 150 X 150 X 120MM

Pack size: **1 x EA**

- Dimensions (L x W x H): 150 x 150 x 120 mm
- Material: Steel
- Length: 150 mm
- Width: 150 mm
- Height: 120 mm
- IP Rating: IP65
- Colour: RAL 7032
- Number of Ways: 0



8428481 150 x 150 x 120

RS PRO RAL 7032 STEEL JUNCTION BOX, IP65, 150 X 300 X 80MM

Pack size: **1 x EA**

- Dimensions (L x W x H): 150 x 300 x 80 mm
- Material: Steel
- Length: 150 mm
- Width: 300 mm
- Height: 80 mm
- IP Rating: IP65
- Colour: RAL 7032
- Number of Ways: 0



8428490 150 x 300 x 80

RS PRO RAL 7032 STEEL JUNCTION BOX, IP65, 150 X 300 X 120MM

Pack size: **1 x EA**

- Dimensions (L x W x H): 150 x 300 x 120 mm
- Material: Steel
- Length: 150 mm
- Width: 300 mm
- Height: 120 mm
- IP Rating: IP65
- Colour: RAL 7032
- Number of Ways: 0



8428493 150 x 300 x 120

RS PRO RAL 7032 STEEL JUNCTION BOX, IP65, 200 X 200 X 120MM

Pack size: **1 x EA**

- Dimensions (L x W x H): 200 x 200 x 120 mm
- Material: Steel
- Length: 200 mm
- Width: 200 mm
- Height: 120 mm
- IP Rating: IP65
- Colour: RAL 7032
- Number of Ways: 0



8428497 200 x 200 x 120

RS PRO RAL 7032 STEEL JUNCTION BOX, IP65, 300 X 300 X 120MM

Pack size: **1 x EA**

- Dimensions (L x W x H): 300 x 300 x 120 mm
- Material: Steel
- Length: 300 mm
- Width: 300 mm
- Height: 120 mm
- IP Rating: IP65
- Colour: RAL 7032
- Number of Ways: 0



8428500 300 x 300 x 120

RS PRO RAL 7032 STEEL JUNCTION BOX, IP65, 200 X 300 X 120MM

Pack size: **1 x EA**

- Dimensions (L x W x H): 200 x 300 x 120 mm
- Material: Steel
- Length: 200 mm
- Width: 300 mm
- Height: 120 mm
- IP Rating: IP65
- Colour: RAL 7032
- Number of Ways: 0



8428507 200 x 300 x 120

RS PRO BLACK LOCKING HANDLE, COMPRESSION LATCH

Pack size: **1 x EA**

- Handle Style: Compression Latch
- Handle Length: 48.4 mm
- Colour: Black



1927132 Compression

RS PRO BLACK LOCKING HANDLE, T-HANDLEPack size: **1 x EA**

- Handle Style: T-Handle
- Handle Length: 17 mm
- Colour: Black

**1927133** T-Handle**RS PRO METAL LOCKING HANDLE**Pack size: **1 x EA**

- Material: Metal

**8428469** Metal**1U 19" CABLE ENTRY WITH BRUSH**Pack size: **1 x EA**

- Type: Cable Entry Panel
- Dimensions: 483 mm x 10 mm x 1 U in
- For Use With: 1U Rack Unit
- Material: Steel
- Height (U): 1 U

**8020285** Cable Entry**RS PRO STEEL CABLE ENTRY PANEL FOR USE WITH 2U RACK UNIT, 483**Pack size: **1 x EA**

- Type: Cable Entry Panel
- Dimensions: 483 mm x 10 mm x 2 U in
- For Use With: 2U Rack Unit
- Material: Steel
- Height (U): 2 U

**8020289** Cable Entry**RS PRO STEEL FLOOR MOUNT KIT FOR USE WITH LAB RACK KIT**Pack size: **1 x EA**

- Type: Floor Mount Kit
- For Use With: Lab Rack Kit
- Material: Steel

**528961** Floor Mount Kit**ENCLOSURE, RACK, CABINET, 19IN, IEC 297, ANODISED ALUMINIUM, NATURAL**Pack size: **1 x EA**


- Type: Front Panel
- Rack Units: 1 U
- Colour: Unpainted
- Material: Aluminium
- Dimensions: 482.6 x 43.7 mm
- Length: 482.6 mm
- Width: 43.7 mm

**4393198** Front Panel**ENCLOSURE, 19IN, RACK, FRONT PANEL, 2U, NATURAL**Pack size: **1 x EA**


- Type: Front Panel
- Rack Units: 2 U
- Colour: Unpainted
- Material: Aluminium
- Dimensions: 482.6 x 88.1 mm
- Length: 482.6 mm
- Width: 88.1 mm

**4393205** Front Panel**RS PRO NATURAL ANODIZED ALUMINIUM FRONT PANEL, 8U, 482.6**Pack size: **1 x EA**

- Type: Front Panel
- Rack Units: 8 U
- Colour: Natural Anodized
- Material: Aluminium
- Dimensions: 482.6 x 177 mm
- Length: 482.6 mm
- Width: 177 mm

**4393261** Front Panel**RS PRO GREY ALUMINIUM FRONT PANEL, 10U, 84HP, 482.6 X 443.7MM**Pack size: **1 x EA**

- Type: Front Panel
- Rack Units: 10 U
- Horizontal Pitch: 84 HP
- Colour: Grey
- Material: Aluminium
- Dimensions: 482.6 x 443.7 mm
- Length: 482.6 mm
- Width: 443.7 mm

**4393283** Front Panel**ENCLOSURE, 19IN, RACK, FRONT PANEL, 2U, BLACK**Pack size: **1 x EA**

- Type: Front Panel
- Rack Units: 2 U
- Horizontal Pitch: 21 HP
- Colour: Black
- Material: Aluminium
- Dimensions: 482.6 x 88.1 mm
- Length: 482.6 mm
- Width: 88.1 mm

**4393328** Front Panel**ENCLOSURE, 19IN, RACK, FRONT PANEL, 3U, BLACK**Pack size: **1 x EA**

- Type: Front Panel
- Rack Units: 3 U
- Colour: Black
- Shielded: Yes
- Material: Aluminium
- Dimensions: 12.7 x 74 mm
- Length: 12.7 mm
- Width: 74 mm

**4393334** Front Panel**RS PRO BLACK ALUMINIUM FRONT DOOR, 4U, 42HP, 229.6 X 139.5MM**Pack size: **1 x EA**

- Type: Front Door
- Rack Units: 4 U
- Horizontal Pitch: 42 HP
- Hinges: Yes
- Colour: Black
- Material: Aluminium
- Dimensions: 229.6 x 139.5 mm
- Length: 229.6 mm

**4393340** Front Door**RS PRO GREY STEEL BLANKING PANEL, 2U, 483 X 9MM**Pack size: **1 x EA**

- Type: Blanking Panel
- Rack Units: 2 U
- Colour: Grey
- Material: Steel
- Dimensions: 483 x 9 mm
- Length: 483 mm
- Width: 9 mm

**8020229** Blanking Panel**STEEL 2U BLANKING PANEL 19", RAL9005**Pack size: **1 x EA**

- Type: Blanking Panel
- Rack Units: 2 U
- Colour: Black
- Material: Steel
- Dimensions: 483 x 9 mm
- Length: 483 mm
- Width: 9 mm

**8020254** Blanking Panel**STEEL 3U BLANKING PANEL 19", RAL9005**Pack size: **1 x EA**

- Type: Blanking Panel
- Rack Units: 3 U
- Colour: Black
- Material: Steel
- Dimensions: 483 x 9 mm
- Length: 483 mm
- Width: 9 mm

**8020257** Blanking Panel**RS PRO, 1U 19-INCH RACK MOUNT CASE, 44 X 254MM**Pack size: **1 x EA**

- Rack Units: 1 U
- External Dimensions: 44 x 254 mm
- External Height: 44 mm
- External Depth: 254 mm
- Colour: Grey
- External Case Material: Aluminium
- Front Panel Material: Aluminium
- Standards Met: IEC297

**224206** 1 U

RS PRO, 1U 19-INCH RACK MOUNT CASE, 44 X 89MM

Pack size: **1 x EA**

- Rack Units: 1 U
- External Dimensions: 44 x 89 mm
- External Height: 44 mm
- External Depth: 89 mm
- Colour: Grey
- External Case Material: Aluminium
- Front Panel Material: Aluminium
- Standards Met: IEC297



584205 1 U

ENCLOSURE, 19IN, RACK CASE, IEC297, GREY FRONT

Pack size: **1 x EA**

- Rack Units: 1 U
- External Dimensions: 44 x 153 mm
- External Height: 44 mm
- External Depth: 153 mm
- Colour: Grey
- External Case Material: Aluminium
- Front Panel Material: Aluminium
- Standards Met: IEC297



584211 1 U

RS PRO, 2U 19-INCH RACK MOUNT CASE, 88 X 254MM

Pack size: **1 x EA**

- Rack Units: 2 U
- External Dimensions: 88 x 254 mm
- External Height: 88 mm
- External Depth: 254 mm
- Colour: Grey
- External Case Material: Aluminium
- Front Panel Material: Aluminium
- Standards Met: IEC297




584227 2 U

RS PRO, 3U 10.5-INCH RACK MOUNT CASE

Pack size: **1 x EA**

- Rack Units: 3 U
- External Depth: 322 mm
- Colour: Grey
- External Case Material: Steel
- Standards Met: RoHS




852334 3 U

RS PRO, 6U 19-INCH RACK MOUNT CASE

Pack size: **1 x EA**

- Rack Units: 6 U
- External Depth: 522 mm
- Colour: Grey
- External Case Material: Steel
- Standards Met: RoHS



852356 6 U

RS PRO, 1U 19-INCH RACK MOUNT CASE, 335 X 425 X 39.6MM

Pack size: **1 x EA**

- Rack Units: 1 U
- External Dimensions: 335 x 425 x 39.6 mm
- External Height: 39.6 mm
- External Width: 425 mm
- External Depth: 335 mm
- Colour: Black
- External Case Material: Aluminium, Extruded Aluminium
- Front Panel Material: Aluminium



1881314 1 U

RS PRO, 1U 19-INCH RACK MOUNT CASE, 425 X 425 X 39.6MM

Pack size: **1 x EA**

- Rack Units: 1 U
- External Dimensions: 425 x 425 x 39.6 mm
- External Height: 39.6 mm
- External Width: 425 mm
- External Depth: 425 mm
- Colour: Black
- External Case Material: Aluminium, Extruded Aluminium
- Front Panel Material: Aluminium



1881315 1 U

RS PRO, 2U 19-INCH RACK MOUNT CASE, 245 X 425 X 84MM

Pack size: **1 x EA**

- Rack Units: 2 U
- External Dimensions: 245 x 425 x 84 mm
- External Height: 84 mm
- External Width: 425 mm
- External Depth: 245 mm
- Colour: Black
- External Case Material: Aluminium, Extruded Aluminium
- Front Panel Material: Aluminium



1881316 2 U

RS PRO, 2U 19-INCH RACK MOUNT CASE, 335 X 425 X 84MM

Pack size: **1 x EA**

- Rack Units: 2 U
- External Dimensions: 335 x 425 x 84 mm
- External Height: 84 mm
- External Width: 425 mm
- External Depth: 335 mm
- Colour: Black
- External Case Material: Aluminium, Extruded Aluminium
- Front Panel Material: Aluminium



1881317 2 U

RS PRO, 2U 19-INCH RACK MOUNT CASE, 425 X 425 X 84MM

Pack size: **1 x EA**

- Rack Units: 2 U
- External Dimensions: 425 x 425 x 84 mm
- External Height: 84 mm
- External Width: 425 mm
- External Depth: 425 mm
- Colour: Black
- External Case Material: Aluminium, Extruded Aluminium
- Front Panel Material: Aluminium



1881318 2 U

RS PRO, 3U 19-INCH RACK MOUNT CASE, 335 X 425 X 128.6MM

Pack size: **1 x EA**

- Rack Units: 3 U
- External Dimensions: 335 x 425 x 128.6 mm
- External Height: 128.6 mm
- External Width: 425 mm
- External Depth: 335 mm
- Colour: Black
- External Case Material: Aluminium, Extruded Aluminium
- Front Panel Material: Aluminium



1881319 3 U

RS PRO, 3U 19-INCH RACK MOUNT CASE, 425 X 425 X 128.6MM

Pack size: **1 x EA**

- Rack Units: 3 U
- External Dimensions: 425 x 425 x 128.6 mm
- External Height: 128.6 mm
- External Width: 425 mm
- External Depth: 425 mm
- Colour: Black
- External Case Material: Aluminium, Extruded Aluminium
- Front Panel Material: Aluminium



1881320 3 U

RS PRO, 4U 19-INCH RACK MOUNT CASE, 425 X 425 X 173MM

Pack size: **1 x EA**

- Rack Units: 4 U
- External Dimensions: 425 x 425 x 173 mm
- External Height: 173 mm
- External Width: 425 mm
- External Depth: 425 mm
- Colour: Black
- External Case Material: Aluminium, Extruded Aluminium
- Front Panel Material: Aluminium



1881322 4 U

RS PRO, 5U 19-INCH RACK MOUNT CASE, 425 X 425 X 217.3MM

Pack size: **1 x EA**

- Rack Units: 5 U
- External Dimensions: 425 x 425 x 217.3 mm
- External Height: 217.3 mm
- External Width: 425 mm
- External Depth: 425 mm
- Colour: Black
- External Case Material: Aluminium, Extruded Aluminium
- Front Panel Material: Aluminium



1881324 5 U

RS PRO, 1U RACKMOUNT ENCLOSURE VENTILATED, 44 X 483 X 466MM

Pack size: **1 x EA**

- Rack Units: 1 U
- External Dimensions: 44 x 483 x 466 mm
- External Height: 34 mm
- External Width: 436 mm
- External Depth: 466 mm
- Colour: Grey
- Ventilated: Yes
- External Case Material: Aluminium, Steel



6657630 1 U

RS PRO, 2U RACKMOUNT ENCLOSURE VENTILATED, 88 X 483 X 466MM

Pack size: **1 x EA**

- Rack Units: 2 U
- External Dimensions: 88 x 483 x 466 mm
- External Height: 79 mm
- External Width: 436 mm
- External Depth: 466 mm
- Colour: Grey
- Ventilated: Yes
- External Case Material: Aluminium, Steel



6657633 2 U

RS PRO, 3U RACKMOUNT ENCLOSURE VENTILATED, 133 X 483 X 466MMPack size: **1 x EA**

- Rack Units: 3 U
- External Dimensions: 133 x 483 x 466 mm
- External Height: 123 mm
- External Width: 436 mm
- External Depth: 466 mm
- Colour: Grey
- Ventilated: Yes
- External Case Material: Aluminium, Steel

**6657637** 3 U**RS PRO, 6U RACKMOUNT ENCLOSURE VENTILATED, 266 X 483 X 466MM**Pack size: **1 x EA**

- Rack Units: 6 U
- External Dimensions: 266 x 483 x 466 mm
- External Height: 256 mm
- External Width: 436 mm
- External Depth: 466 mm
- Colour: Grey
- Ventilated: Yes
- External Case Material: Aluminium, Steel

**6657643** 6 U**RS PRO, 4U RACKMOUNT ENCLOSURE VENTILATED, 177 X 483 X 466MM**Pack size: **1 x EA**

- Rack Units: 4 U
- External Dimensions: 177 x 483 x 466 mm
- External Height: 168 mm
- External Width: 436 mm
- External Depth: 466 mm
- Colour: Grey
- Ventilated: Yes
- External Case Material: Aluminium, Steel

**6657646** 4 U**RS PRO, 5U RACKMOUNT ENCLOSURE VENTILATED, 222 X 483 X 466MM**Pack size: **1 x EA**

- Rack Units: 5 U
- External Dimensions: 222 x 483 x 466 mm
- External Height: 212 mm
- External Width: 436 mm
- External Depth: 466 mm
- Colour: Grey
- Ventilated: Yes
- External Case Material: Aluminium, Steel

**6657649** 5 U**RS PRO, 1U 19-INCH RACK MOUNT CASE, 44 X 483 X 250MM**Pack size: **1 x EA**

- Rack Units: 1 U
- External Dimensions: 44 x 483 x 250 mm
- External Height: 44 mm
- External Width: 483 mm
- External Depth: 250 mm
- Colour: Grey
- External Case Material: Aluminium, Steel
- Front Panel Material: Aluminium

**6657659** 1 U**RS PRO, 2U 19-INCH RACK MOUNT CASE, 88 X 483 X 350MM**Pack size: **1 x EA**

- Rack Units: 2 U
- External Dimensions: 88 x 483 x 350 mm
- External Height: 88 mm
- External Width: 483 mm
- External Depth: 350 mm
- Colour: Grey
- External Case Material: Aluminium, Steel
- Front Panel Material: Aluminium

**6657661** 2 U**RS PRO, 3U 19-INCH RACK MOUNT CASE, 133 X 483 X 250MM**Pack size: **1 x EA**

- Rack Units: 3 U
- External Dimensions: 133 x 483 x 250 mm
- External Height: 133 mm
- External Width: 483 mm
- External Depth: 250 mm
- Colour: Grey
- External Case Material: Aluminium, Steel
- Front Panel Material: Aluminium

**6657665** 3 U**RS PRO, 2U 19-INCH RACK MOUNT CASE, 88 X 483 X 250MM**Pack size: **1 x EA**

- Rack Units: 2 U
- External Dimensions: 88 x 483 x 250 mm
- External Height: 88 mm
- External Width: 483 mm
- External Depth: 250 mm
- Colour: Grey
- External Case Material: Aluminium, Steel
- Front Panel Material: Aluminium

**6657668** 2 U**RS PRO, 2U 19-INCH RACK MOUNT CASE, 88 X 483 X 250MM**Pack size: **1 x EA**

- Rack Units: 2 U
- External Dimensions: 88 x 483 x 250 mm
- External Height: 88 mm
- External Width: 483 mm
- External Depth: 250 mm
- Colour: Black, Grey
- External Case Material: Aluminium, Steel
- Front Panel Material: Aluminium

**6657671** 2 U**RS PRO, 3U 19-INCH RACK MOUNT CASE, 133 X 483 X 350MM**Pack size: **1 x EA**

- Rack Units: 3 U
- External Dimensions: 133 x 483 x 350 mm
- External Height: 133 mm
- External Width: 483 mm
- External Depth: 350 mm
- Colour: Natural
- External Case Material: Aluminium, Steel
- Front Panel Material: Aluminium

**6657674** 3 U**RS PRO, 1U 19-INCH RACK MOUNT CASE, 44 X 483 X 250MM**Pack size: **1 x EA**

- Rack Units: 1 U
- External Dimensions: 44 x 483 x 250 mm
- External Height: 44 mm
- External Width: 483 mm
- External Depth: 250 mm
- Colour: Black, Grey
- External Case Material: Aluminium, Steel
- Front Panel Material: Aluminium

**6657677** 1 U**RS PRO, 2U 19-INCH RACK MOUNT CASE, 88 X 483 X 350MM**Pack size: **1 x EA**

- Rack Units: 2 U
- External Dimensions: 88 x 483 x 350 mm
- External Height: 88 mm
- External Width: 483 mm
- External Depth: 350 mm
- Colour: Black, Grey
- External Case Material: Aluminium, EG
- Front Panel Material: Aluminium

**6657680** 2 U**RS PRO, 3U 19-INCH RACK MOUNT CASE, 133 X 483 X 250MM**Pack size: **1 x EA**

- Rack Units: 3 U
- External Dimensions: 133 x 483 x 250 mm
- External Height: 133 mm
- External Width: 483 mm
- External Depth: 250 mm
- Colour: Black, Grey
- External Case Material: Aluminium, Steel
- Front Panel Material: Aluminium

**6657683** 3 U**RS PRO, 3U 19-INCH RACK MOUNT CASE, 133 X 483 X 350MM**Pack size: **1 x EA**

- Rack Units: 3 U
- External Dimensions: 133 x 483 x 350 mm
- External Height: 133 mm
- External Width: 483 mm
- External Depth: 350 mm
- Colour: Black, Grey
- External Case Material: Aluminium, Steel
- Front Panel Material: Aluminium

**6657687** 3 U**RS PRO, 1U 19-INCH RACK MOUNT CASE VENTILATED, 482.6 X 43.7 X**Pack size: **1 x EA**

- Rack Units: 1 U
- External Dimensions: 482.6 x 43.7 x 245 mm
- External Height: 43.7 mm
- External Width: 482.6 mm
- External Depth: 245 mm
- Colour: Black
- Ventilated: Yes
- External Case Material: Steel

**6657700** 1 U**RACK MOUNT ENCLOSURE, 1U 90MM BLACK**Pack size: **1 x EA**

- Rack Units: 1 U
- External Dimensions: 483 x 44 x 90 mm
- External Height: 44 mm
- External Width: 483 mm
- External Depth: 90 mm
- Colour: Black
- Ventilated: Yes
- External Case Material: Steel

**6657706** 1 U

RS PRO, 2U 19-INCH RACK MOUNT CASE VENTILATED, 482.6 X 88.1 X

Pack size: **1 x EA**

- Rack Units: 2 U
- External Dimensions: 482.6 x 88.1 x 335 mm
- External Height: 88.1 mm
- External Width: 482.6 mm
- External Depth: 335 mm
- Colour: Black
- Ventilated: Yes
- External Case Material: Steel



6657712 2 U

RS PRO, 3U 19-INCH RACK MOUNT CASE VENTILATED, 482.6 X 132.6 X

Pack size: **1 x EA**

- Rack Units: 3 U
- External Dimensions: 482.6 x 132.6 x 335 mm
- External Height: 132.6 mm
- External Width: 482.6 mm
- External Depth: 335 mm
- Colour: Black
- Ventilated: Yes
- External Case Material: Steel



6657716 3 U

RS PRO, 2U 19-INCH RACK MOUNT CASE VENTILATED, 482.6 X 88.1 X

Pack size: **1 x EA**

- Rack Units: 2 U
- External Dimensions: 482.6 x 88.1 x 245 mm
- External Height: 88.1 mm
- External Width: 482.6 mm
- External Depth: 245 mm
- Colour: Black
- Ventilated: Yes
- External Case Material: Steel



6657719 2 U

RS PRO, 4U 19-INCH RACK MOUNT CASE VENTILATED, 482.6 X 177 X

Pack size: **1 x EA**

- Rack Units: 4 U
- External Dimensions: 482.6 x 177 x 425 mm
- External Height: 177 mm
- External Width: 482.6 mm
- External Depth: 425 mm
- Colour: Black
- Ventilated: Yes
- External Case Material: Steel



6657722 4 U

RS PRO, 3U 19-INCH RACK MOUNT CASE VENTILATED, 482.6 X 132.6 X

Pack size: **1 x EA**

- Rack Units: 3 U
- External Dimensions: 482.6 x 132.6 x 425 mm
- External Height: 132.6 mm
- External Width: 482.6 mm
- External Depth: 425 mm
- Colour: Black
- Ventilated: Yes
- External Case Material: Steel



6657725 3 U

RS PRO, 4U 19-INCH RACK MOUNT CASE VENTILATED, 482.6 X 177 X

Pack size: **1 x EA**

- Rack Units: 4 U
- External Dimensions: 482.6 x 177 x 335 mm
- External Height: 177 mm
- External Width: 482.6 mm
- External Depth: 335 mm
- Colour: Black
- Ventilated: Yes
- External Case Material: Steel



6657728 4 U

RS PRO, 5U 19-INCH RACK MOUNT CASE VENTILATED, 482.6 X 221.5 X

Pack size: **1 x EA**

- Rack Units: 5 U
- External Dimensions: 482.6 x 221.5 x 425 mm
- External Height: 221.5 mm
- External Width: 482.6 mm
- External Depth: 425 mm
- Colour: Black
- Ventilated: Yes
- External Case Material: Steel



6657731 5 U

RS PRO, 6U 19-INCH RACK MOUNT CASE VENTILATED, 266 X 482 X

Pack size: **1 x EA**

- Rack Units: 6 U
- External Dimensions: 266 x 482 x 465 mm
- External Height: 266 mm
- External Width: 482 mm
- External Depth: 465 mm
- Colour: Black
- Ventilated: Yes
- External Case Material: Aluminium, Steel



6657738 6 U

SCREW KIT, MACHINE, C/W M6 PLASTIC CUPWASHERS, CAGE

Pack size: **10 x EA**

- Number of Pieces: 10
- Screw/Bolt Type: Machine Screw
- Head Shape: Pan
- Drive Type: Cross
- Screw/Bolts Lengths: 16 mm
- Thread Size: M6
- Nut Type: Cage
- Washer Type: Cup



5425410 10

SCREW KIT, MACHINE, C/W M6 PLASTIC CUPWASHERS, CAGE

Pack size: **50 x EA**

- Number of Pieces: 50
- Screw/Bolt Type: Machine Screw
- Head Shape: Pan
- Drive Type: Cross
- Screw/Bolts Lengths: 16 mm
- Thread Size: M6
- Nut Type: Cage
- Washer Type: Cup



5425426 50

RS PRO 6U-RACK SERVER CABINET, 203 X 502 X 300MM

Pack size: **1 x EA**

- Rack Units: 6 U
- Type: Wall Mount
- External Height: 203 mm
- External Width: 502 mm
- External Depth: 300 mm
- External Dimensions: 203 x 502 x 300 mm
- Colour: Black
- External Case Material: Steel



7450742 6 U

RS PRO 2U-RACK SERVER RACK DRAWER

Pack size: **1 x EA**

- Rack Units: 2 U
- Type: Drawer
- External Height: 88 mm
- External Width: 483 mm
- External Depth: 500 mm
- Colour: Grey
- External Case Material: Steel



8020267 2 U

RS PRO 6U-RACK SERVER CABINET, 366 X 600 X 560MM

Pack size: **1 x EA**

- Rack Units: 6 U
- Type: Wall Mount
- External Height: 366 mm
- External Width: 600 mm
- External Depth: 560 mm
- External Dimensions: 366 x 600 x 560 mm
- Colour: Grey
- External Case Material: Steel



8020320 6 U

RS PRO 6U-RACK SERVER CABINET, 366 X 600 X 400MM

Pack size: **1 x EA**

- Rack Units: 6 U
- Type: Wall Mount
- External Height: 366 mm
- External Width: 600 mm
- External Depth: 400 mm
- External Dimensions: 366 x 600 x 400 mm
- Colour: Grey
- External Case Material: Steel



8020327 6 U

RS PRO TIE BAR ASSEMBLY TIE BAR ASSEMBLY FOR USE WITH 19-INCH

Pack size: **1 x EA**

- Type: Tie Bar Assembly
- For Use With: 19-Inch Cabinet, Wall Box
- Material: Steel
- Height (U): 1 U



223770 Tie Bar Assembly

RS PRO DOCUMENT POCKET DOCUMENT POCKET FOR USE WITH

Pack size: **1 x EA**

- Type: Document Pocket
- Dimensions: 278 x 234 x 40 mm
- For Use With: A4 Documents
- Material: Polystyrene



500308 Document Pocket

**RS PRO DOCUMENT POCKET
DOCUMENT POCKET FOR USE WITH**Pack size: **1 x EA**

- Type: Document Pocket
- Dimensions: 188 x 174 x 20 mm
- For Use With: A4 & A5 Plans, DIN A3
- Material: Polystyrene

**500314** Document Pocket**RS PRO SYSTEM CARD GUIDE
SYSTEM CARD GUIDE FOR USE WITH**Pack size: **10 x EA**

- Type: System Card Guide
- For Use With: KM6-II Sub Rack System
- Material: Luranyl

**500550** System Card**RS PRO SYSTEM CARD GUIDE
SYSTEM CARD GUIDE FOR USE WITH**Pack size: **10 x EA**

- Type: System Card Guide
- For Use With: KM6-II Sub Rack System

**500572** System Card**ENCLOSURE,SUBRACK,KM6-II,PLASTIC PCB MOUNT BRACKET**Pack size: **2 x EA**

- Type: Card Mounting Bracket
- For Use With: KM6-II Sub Rack System
- Material: Plastic

**500847** Card Mounting**ENCLOSURE,SUBRACK,KM6-II,METAL
PCB MOUNT BRACKET**Pack size: **10 x EA**

- Type: Card Mounting Bracket
- For Use With: KM6-II Sub Rack System
- Material: Metal

**500853** Card Mounting**RS PRO PLASTIC BUSH PLASTIC BUSH
FOR USE WITH EURO-CARDS FITTED**Pack size: **100 x EA**

- Type: Plastic Bush
- For Use With: Euro-Cards Fitted with 2 Part Indirect Edge Connector
- Material: Plastic
- Thread Size: M2.5

**524571** Plastic Bush**RS PRO BAR HANDLE BAR HANDLE
FOR USE WITH METAL INSTRUMENT**Pack size: **2 x EA**

- Type: Bar Handle
- Dimensions: 136.5 x 9.5 x 33.5 mm
- For Use With: Metal Instrument Case
- Material: Steel

**583820** Bar Handle**RS PRO TIE BAR RECESSED CABLE TIE
BAR FOR USE WITH ELECTRICAL**Pack size: **1 x EA**

- Type: Recessed Cable Tie Bar
- For Use With: Electrical Isolator, Telecom Backmount
- Material: Steel
- Height (U): 1.5 U

**2431888** Recessed Cable**RS PRO TAPPED STRIP TAPPED STRIP
FOR USE WITH KM6-II SUB RACK**Pack size: **1 x EA**

- Type: Tapped Strip
- For Use With: KM6-II Sub Rack System
- Material: Steel
- Width (HP): 42 HP

**4445182** Tapped Strip**RS PRO TAPPED STRIP TAPPED STRIP
FOR USE WITH KM6-II SUB RACK**Pack size: **1 x EA**

- Type: Tapped Strip
- For Use With: KM6-II Sub Rack System
- Material: Steel
- Width (HP): 60 HP

**4445520** Tapped Strip**RS PRO VENTILATED TOP COVER
VENTILATED TOP COVER FOR USE**Pack size: **1 x EA**

- Type: Ventilated Top Cover
- Dimensions: 423 x 466 x 3 mm
- For Use With: 19" Racking System
- Material: Steel

**6657652** Ventilated Top**RS PRO UNVENTILATED TOP COVER
UNVENTILATED TOP COVER FOR USE**Pack size: **1 x EA**

- Type: Unventilated Top Cover
- Dimensions: 423 x 466 x 3 mm
- For Use With: 19" Racking System
- Material: Steel

**6657655** Unventilated Top**RS PRO VENTILATED TOP COVER
VENTILATED TOP COVER FOR USE**Pack size: **1 x EA**

- Type: Ventilated Top Cover
- For Use With: 19-Inch Steel Chassis Tray
- Material: Steel

**6657693** Ventilated Top**RS PRO UNVENTILATED TOP COVER
UNVENTILATED TOP COVER**Pack size: **1 x EA**

- Type: Unventilated Top Cover

**6657696** Unventilated Top**RS PRO UNVENTILATED TOP COVER
UNVENTILATED TOP COVER**Pack size: **1 x EA**

- Type: Unventilated Top Cover

**6657699** Unventilated Top**RS PRO VENTILATED TOP COVER
VENTILATED TOP COVER FOR USE**Pack size: **1 x EA**

- Type: Ventilated Top Cover
- For Use With: 19-Inch Steel Chassis Tray
- Material: Steel

**6657703** Ventilated Top

RS PRO CAGED NUTS KIT CAGED NUTS KIT FOR USE WITH 19 IN RACKPack size: **1 x EA**

- Type: Caged Nuts Kit
- For Use With: 19 in Rack Mounting Equipment
- Thread Size: M6 x 16
- Quantity: 30

**7682621** Caged Nuts Kit**RS PRO BLACK TRAY, 2U, 10KG LOAD X 280MM**Pack size: **1 x EA**

- Type: Tray
- Rack Units: 2 U
- Depth: 280 mm
- Ventilated: Yes
- Colour: Black
- Material: Steel
- Maximum Load: 10 kg
- Maximum Depth: 280 mm

**1959126** Tray**2U 19" CANTILEVER SHELF**Pack size: **1 x EA**

- Type: Cantilever Shelf
- Rack Units: 2 U
- Depth: 250 mm
- Ventilated: Yes
- Colour: Grey
- Material: Steel
- Maximum Load: 25 kg
- Height: 88 mm

**8020273** Cantilever Shelf**1U 19" CANTILEVER SHELF**Pack size: **1 x EA**

- Type: Cantilever Shelf
- Rack Units: 1 U
- Depth: 150 mm
- Ventilated: Yes
- Colour: Grey
- Material: Steel
- Maximum Load: 25 kg
- Height: 44 mm

**8020279** Cantilever Shelf**RS PRO GREY CANTILEVER SHELF, 2U, 25KG LOAD, 483MM X 400MM**Pack size: **1 x EA**

- Type: Cantilever Shelf
- Rack Units: 2 U
- Depth: 400 mm
- Ventilated: Yes
- Colour: Grey
- Material: Steel
- Maximum Load: 25 kg
- Height: 88 mm

**8020282** Cantilever Shelf**RACK MOUNT CHASSIS, 84HP**Pack size: **1 x EA**

- Horizontal Pitch: 84 HP
- Colour: Unpainted
- Width: 426 mm

**500623** 84 HP**RS PRO GLASS REINFORCED PLASTIC WALL BOX, IP66, 100 MM X 120 MM X**Pack size: **1 x EA**

- External Height: 100 mm
- External Width: 120 mm
- External Depth: 140 mm
- Body Material: Glass Reinforced Plastic
- Transparent Door: No
- IP Rating: IP66
- Chassis Plate: No
- Gland Plate: No

**225568** 100 mm**RS PRO STEEL WALL BOX, IP66, 250 MM X 200 MM X 150MM**Pack size: **1 x EA**

- External Height: 250 mm
- External Width: 200 mm
- External Depth: 150 mm
- Body Material: Steel
- IP Rating: IP66
- Chassis Plate: Yes
- Door Lock Type: Single Lock System
- Gland Plate: Yes

**1896587** 250 mm**RS PRO STEEL WALL BOX, IP66, 250 MM X 250 MM X 150MM**Pack size: **1 x EA**

- External Height: 250 mm
- External Width: 250 mm
- External Depth: 150 mm
- Body Material: Steel
- IP Rating: IP66
- Chassis Plate: Yes
- Door Lock Type: Single Lock System
- Gland Plate: Yes

**1896588** 250 mm**RS PRO STEEL WALL BOX, IP66, 300 MM X 250 MM X 200MM**Pack size: **1 x EA**

- External Height: 300 mm
- External Width: 250 mm
- External Depth: 200 mm
- Body Material: Steel
- IP Rating: IP66
- Chassis Plate: Yes
- Door Lock Type: Single Lock System
- Gland Plate: Yes

**1896589** 300 mm**RS PRO STEEL WALL BOX, IP66, 400 MM X 300 MM X 150MM**Pack size: **1 x EA**

- External Height: 400 mm
- External Width: 300 mm
- External Depth: 150 mm
- Body Material: Steel
- IP Rating: IP66
- Chassis Plate: Yes
- Door Lock Type: Single Lock System
- Gland Plate: Yes

**1896590** 400 mm**RS PRO STEEL WALL BOX, IP66, 500 MM X 300 MM X 150MM**Pack size: **1 x EA**

- External Height: 500 mm
- External Width: 300 mm
- External Depth: 150 mm
- Body Material: Steel
- IP Rating: IP66
- Chassis Plate: Yes
- Door Lock Type: Single Lock System
- Gland Plate: Yes

**1896591** 500 mm**RS PRO STEEL WALL BOX, IP66, 600 MM X 500 MM X 150MM**Pack size: **1 x EA**

- External Height: 600 mm
- External Width: 500 mm
- External Depth: 150 mm
- Body Material: Steel
- IP Rating: IP66
- Chassis Plate: Yes
- Door Lock Type: Double Lock System
- Gland Plate: Yes

**1896592** 600 mm**RS PRO STEEL WALL BOX, IP66, 500 MM X 500 MM X 200MM**Pack size: **1 x EA**

- External Height: 500 mm
- External Width: 500 mm
- External Depth: 200 mm
- Body Material: Steel
- IP Rating: IP66
- Chassis Plate: Yes
- Door Lock Type: Single Lock System
- Gland Plate: Yes

**1896594** 500 mm**RS PRO STEEL WALL BOX, IP66, 400 MM X 400 MM X 250MM**Pack size: **1 x EA**

- External Height: 400 mm
- External Width: 400 mm
- External Depth: 250 mm
- Body Material: Steel
- IP Rating: IP66
- Chassis Plate: Yes
- Door Lock Type: Single Lock System
- Gland Plate: Yes

**1896595** 400 mm**RS PRO STEEL WALL BOX, IP66, 500 MM X 400 MM X 250MM**Pack size: **1 x EA**

- External Height: 500 mm
- External Width: 400 mm
- External Depth: 250 mm
- Body Material: Steel
- IP Rating: IP66
- Chassis Plate: Yes
- Door Lock Type: Single Lock System
- Gland Plate: Yes

**1896596** 500 mm

600H X 400W X 250DMM, DOOR & BODY: 1.2MM

Pack size: **1 x EA**

- External Height: 600 mm
- External Width: 400 mm
- External Depth: 250 mm
- Body Material: Steel
- IP Rating: IP66
- Chassis Plate: Yes
- Door Lock Type: Double Lock System
- Gland Plate: Yes



1896597 600 mm

RS PRO STEEL WALL BOX, IP66, 600 MM X 500 MM X 250MM

Pack size: **1 x EA**

- External Height: 600 mm
- External Width: 500 mm
- External Depth: 250 mm
- Body Material: Steel
- IP Rating: IP66
- Chassis Plate: Yes
- Door Lock Type: Double Lock System
- Gland Plate: Yes



1896598 600 mm

RS PRO STEEL WALL BOX, IP66, 600 MM X 500 MM X 300MM

Pack size: **1 x EA**

- External Height: 600 mm
- External Width: 500 mm
- External Depth: 300 mm
- Body Material: Steel
- IP Rating: IP66
- Chassis Plate: Yes
- Door Lock Type: Double Lock System
- Gland Plate: Yes



1896599 600 mm

RS PRO STEEL WALL BOX, IP66, 1000 MM X 600 MM X 300MM

Pack size: **1 x EA**

- External Height: 1000 mm
- External Width: 600 mm
- External Depth: 300 mm
- Body Material: Steel
- IP Rating: IP66
- Chassis Plate: Yes
- Door Lock Type: Triple Lock System
- Gland Plate: Yes



1896601 1000 mm

RS PRO STEEL WALL BOX, IP66, 1200 MM X 800 MM X 250MM

Pack size: **1 x EA**

- External Height: 1200 mm
- External Width: 800 mm
- External Depth: 250 mm
- Body Material: Steel
- IP Rating: IP66
- Chassis Plate: Yes
- Door Lock Type: Triple Lock System
- Gland Plate: Yes



1896602 1200 mm

RS PRO STEEL WALL BOX, IP66, 1000 MM X 800 MM X 400MM

Pack size: **1 x EA**

- External Height: 1000 mm
- External Width: 800 mm
- External Depth: 400 mm
- Body Material: Steel
- IP Rating: IP66
- Chassis Plate: Yes
- Door Lock Type: Triple Lock System
- Gland Plate: Yes



1896603 1000 mm

1200H X 800W X 400DMM, DOOR & BODY: 1.5M

Pack size: **1 x EA**

- External Height: 1200 mm
- External Width: 800 mm
- External Depth: 400 mm
- Body Material: Steel
- IP Rating: IP66
- Chassis Plate: Yes
- Door Lock Type: Triple Lock System
- Gland Plate: Yes



1896604 1200 mm

RS PRO FIBREGLASS REINFORCED POLYESTER WALL BOX, IP66, 300 MM

Pack size: **1 x EA**

- External Height: 300 mm
- External Width: 250 mm
- External Depth: 140 mm
- Body Material: Fibreglass Reinforced Polyester
- Transparent Door: No
- IP Rating: IP66
- Chassis Plate: Yes
- Door Lock Type: Single Lock System



1927114 300 mm

RS PRO FIBREGLASS REINFORCED POLYESTER WALL BOX, IP66, 400 MM

Pack size: **1 x EA**

- External Height: 400 mm
- External Width: 400 mm
- External Depth: 200 mm
- Body Material: Fibreglass Reinforced Polyester
- Transparent Door: No
- IP Rating: IP66
- Chassis Plate: Yes
- Door Lock Type: Double Lock System



1927115 400 mm

RS PRO FIBREGLASS REINFORCED POLYESTER WALL BOX, IP66, 400 MM

Pack size: **1 x EA**

- External Height: 400 mm
- External Width: 300 mm
- External Depth: 200 mm
- Body Material: Fibreglass Reinforced Polyester
- Transparent Door: No
- IP Rating: IP66
- Chassis Plate: Yes
- Door Lock Type: Double Lock System



1927116 400 mm

RS PRO FIBREGLASS REINFORCED POLYESTER WALL BOX, IP66, 500 MM

Pack size: **1 x EA**

- External Height: 500 mm
- External Width: 400 mm
- External Depth: 200 mm
- Body Material: Fibreglass Reinforced Polyester
- Transparent Door: No
- IP Rating: IP66
- Chassis Plate: Yes
- Door Lock Type: Double Lock System



1927117 500 mm

RS PRO FIBREGLASS REINFORCED POLYESTER WALL BOX, IP66, 600 MM

Pack size: **1 x EA**

- External Height: 600 mm
- External Width: 400 mm
- External Depth: 230 mm
- Body Material: Fibreglass Reinforced Polyester
- Transparent Door: No
- IP Rating: IP66
- Chassis Plate: Yes
- Door Lock Type: Double Lock System



1927118 600 mm

RS PRO FIBREGLASS REINFORCED POLYESTER WALL BOX, IP66, 600 MM

Pack size: **1 x EA**

- External Height: 600 mm
- External Width: 500 mm
- External Depth: 230 mm
- Body Material: Fibreglass Reinforced Polyester
- Transparent Door: No
- IP Rating: IP66
- Chassis Plate: Yes
- Door Lock Type: Double Lock System



1927119 600 mm

RS PRO FIBREGLASS REINFORCED POLYESTER WALL BOX, IP66, 800 MM

Pack size: **1 x EA**

- External Height: 800 mm
- External Width: 600 mm
- External Depth: 300 mm
- Body Material: Fibreglass Reinforced Polyester
- Transparent Door: No
- IP Rating: IP66
- Chassis Plate: Yes
- Door Lock Type: Double Lock System



1927121 800 mm

RS PRO FIBREGLASS REINFORCED POLYESTER WALL BOX, IP66,

Pack size: **1 x EA**

- External Height: 300 mm
- External Width: 250 mm
- External Depth: 140 mm
- Body Material: Fibreglass Reinforced Polyester
- Transparent Door: Yes
- IP Rating: IP66
- Chassis Plate: Yes
- Door Lock Type: Single Lock System



1927122 300 mm

RS PRO FIBREGLASS REINFORCED POLYESTER WALL BOX, IP66,

Pack size: **1 x EA**

- External Height: 400 mm
- External Width: 400 mm
- External Depth: 200 mm
- Body Material: Fibreglass Reinforced Polyester
- Transparent Door: Yes
- IP Rating: IP66
- Chassis Plate: Yes
- Door Lock Type: Double Lock System



1927123 400 mm

RS PRO FIBREGLASS REINFORCED POLYESTER WALL BOX, IP66,Pack size: **1 x EA**

- External Height: 400 mm
- External Width: 300 mm
- External Depth: 200 mm
- Body Material: Fibreglass Reinforced Polyester
- Transparent Door: Yes
- IP Rating: IP66
- Chassis Plate: Yes
- Door Lock Type: Double Lock System

**1927124** 400 mm**RS PRO FIBREGLASS REINFORCED POLYESTER WALL BOX, IP66,**Pack size: **1 x EA**

- External Height: 600 mm
- External Width: 500 mm
- External Depth: 230 mm
- Body Material: Fibreglass Reinforced Polyester
- Transparent Door: Yes
- IP Rating: IP66
- Chassis Plate: Yes
- Door Lock Type: Double Lock System

**1927127** 600 mm**RS PRO ABS, POLYCARBONATE WALL BOX, IP65, VIEWING WINDOW, 166**Pack size: **1 x EA**

- External Height: 166 mm
- External Width: 161 mm
- External Depth: 93 mm
- Body Material: ABS, Polycarbonate
- Transparent Door: Yes
- IP Rating: IP65
- Chassis Plate: No
- Door Lock Type: Pad Lock

**1947497** 166 mm**RS PRO ABS, POLYCARBONATE WALL BOX, IP65, VIEWING WINDOW, 296**Pack size: **1 x EA**

- External Height: 296 mm
- External Width: 281 mm
- External Depth: 158 mm
- Body Material: ABS, Polycarbonate
- Transparent Door: Yes
- IP Rating: IP65
- Chassis Plate: No
- Door Lock Type: Pad Lock

**1947501** 296 mm**RS PRO POLYCARBONATE WALL BOX, IP65, 300 MM X 200 MM X 180MM**Pack size: **1 x EA**

- External Height: 300 mm
- External Width: 200 mm
- External Depth: 180 mm
- Body Material: Polycarbonate
- Transparent Door: No
- IP Rating: IP65
- Chassis Plate: Yes
- Gland Plate: No

**2068769** 300 mm**RS PRO POLYCARBONATE WALL BOX, IP65, VIEWING WINDOW, 300 MM X**Pack size: **1 x EA**

- External Height: 300 mm
- External Width: 300 mm
- External Depth: 180 mm
- Body Material: Polycarbonate
- Transparent Door: Yes
- IP Rating: IP65
- Chassis Plate: Yes
- Gland Plate: No

**2068774** 300 mm**RS PRO POLYCARBONATE WALL BOX, IP65, VIEWING WINDOW, 400 MM X**Pack size: **1 x EA**

- External Height: 400 mm
- External Width: 300 mm
- External Depth: 180 mm
- Body Material: Polycarbonate
- Transparent Door: Yes
- IP Rating: IP65
- Chassis Plate: Yes
- Gland Plate: No

**2068776** 400 mm**RS PRO STEEL WALL BOX, IP65, 400 MM X 300 MM X 200MM**Pack size: **1 x EA**

- External Height: 400 mm
- External Width: 300 mm
- External Depth: 200 mm
- Body Material: Steel
- Transparent Door: No
- IP Rating: IP65
- Chassis Plate: Yes
- Door Lock Type: Key

**7467352** 400 mm**RS PRO ABS WALL BOX, IP65, 400 MM X 300 MM X 195MM**Pack size: **1 x EA**

- External Height: 400 mm
- External Width: 300 mm
- External Depth: 195 mm
- Body Material: ABS
- Transparent Door: No
- IP Rating: IP65
- Chassis Plate: Yes
- Door Lock Type: Single Lock System

**7467390** 400 mm**IP65 ABS WALL ENCLOSURE 280X210X130MM**Pack size: **1 x EA**

- External Height: 280 mm
- External Width: 210 mm
- External Depth: 130 mm
- Body Material: ABS
- Transparent Door: No
- IP Rating: IP65
- Chassis Plate: Yes
- Door Lock Type: Double Lock System

**7467393** 280 mm**RS PRO ABS WALL BOX, IP65, 400 MM X 300 MM X 165MM**Pack size: **1 x EA**

- External Height: 400 mm
- External Width: 300 mm
- External Depth: 165 mm
- Body Material: ABS
- Transparent Door: No
- IP Rating: IP65
- Chassis Plate: Yes
- Door Lock Type: Single Lock System

**7467396** 400 mm**RS PRO ABS WALL BOX, IP65, 600 MM X 400 MM X 200MM**Pack size: **1 x EA**

- External Height: 600 mm
- External Width: 400 mm
- External Depth: 200 mm
- Body Material: ABS
- Transparent Door: No
- IP Rating: IP65
- Chassis Plate: Yes
- Door Lock Type: Single Lock System

**7467403** 600 mm**RS PRO ABS WALL BOX, IP65, 500 MM X 400 MM X 175MM**Pack size: **1 x EA**

- External Height: 500 mm
- External Width: 400 mm
- External Depth: 175 mm
- Body Material: ABS
- Transparent Door: No
- IP Rating: IP65
- Chassis Plate: Yes
- Door Lock Type: Single Lock System

**7467400** 500 mm**RS PRO ABS WALL BOX, IP65, 700 MM X 500 MM X 245MM**Pack size: **1 x EA**

- External Height: 700 mm
- External Width: 500 mm
- External Depth: 245 mm
- Body Material: ABS
- Transparent Door: No
- IP Rating: IP65
- Chassis Plate: Yes
- Door Lock Type: Single Lock System

**7467407** 700 mm**RS PRO 304 STAINLESS STEEL WALL BOX, IP66, 300 MM X 250 MM X**Pack size: **1 x EA**

- External Height: 300 mm
- External Width: 250 mm
- External Depth: 150 mm
- Body Material: 304 Stainless Steel
- Transparent Door: No
- IP Rating: IP66
- Chassis Plate: Yes
- Door Lock Type: Quick Release Lock

**7491822** 300 mm**RS PRO 304 STAINLESS STEEL WALL BOX, IP66, 400 MM X 300 MM X**Pack size: **1 x EA**

- External Height: 300 mm
- External Width: 400 mm
- External Depth: 150 mm
- Body Material: 304 Stainless Steel
- Transparent Door: No
- IP Rating: IP66
- Chassis Plate: Yes
- Door Lock Type: Quick Release Lock

**7491826** 300 mm

RS PRO 304 STAINLESS STEEL WALL BOX, IP66, 200 MM X 200 MM X

Pack size: **1 x EA**

- External Height: 200 mm
- External Width: 200 mm
- External Depth: 150 mm
- Body Material: 304 Stainless Steel
- Transparent Door: No
- IP Rating: IP66
- Chassis Plate: Yes
- Door Lock Type: Quick Release Lock



7491829 200 mm

RS PRO 304 STAINLESS STEEL WALL BOX, IP66, 300 MM X 300 MM X

Pack size: **1 x EA**

- External Height: 300 mm
- External Width: 300 mm
- External Depth: 150 mm
- Body Material: 304 Stainless Steel
- Transparent Door: No
- IP Rating: IP66
- Chassis Plate: Yes
- Door Lock Type: Quick Release Lock



7491838 300 mm

RS PRO 304 STAINLESS STEEL WALL BOX, IP66, 400 MM X 400 MM X

Pack size: **1 x EA**

- External Height: 400 mm
- External Width: 400 mm
- External Depth: 200 mm
- Body Material: 304 Stainless Steel
- Transparent Door: No
- IP Rating: IP66
- Chassis Plate: Yes
- Door Lock Type: Quick Release Lock



7491841 400 mm

RS PRO 304 STAINLESS STEEL WALL BOX, IP66, 500 MM X 400 MM X

Pack size: **1 x EA**

- External Height: 400 mm
- External Width: 500 mm
- External Depth: 250 mm
- Body Material: 304 Stainless Steel
- Transparent Door: No
- IP Rating: IP66
- Chassis Plate: Yes
- Door Lock Type: Quick Release Lock



7491844 400 mm

RS PRO 304 STAINLESS STEEL WALL BOX, IP66, 400 MM X 300 MM X

Pack size: **1 x EA**

- External Height: 400 mm
- External Width: 300 mm
- External Depth: 200 mm
- Body Material: 304 Stainless Steel
- Transparent Door: No
- IP Rating: IP66
- Chassis Plate: Yes
- Door Lock Type: Quick Release Lock



7586958 400 mm

RS PRO 304 STAINLESS STEEL WALL BOX, IP66, 500 MM X 400 MM X

Pack size: **1 x EA**

- External Height: 500 mm
- External Width: 400 mm
- External Depth: 200 mm
- Body Material: 304 Stainless Steel
- Transparent Door: No
- IP Rating: IP66
- Chassis Plate: Yes
- Door Lock Type: Quick Release Lock



7586961 500 mm

RS PRO 304 STAINLESS STEEL WALL BOX, IP66, 600 MM X 400 MM X

Pack size: **1 x EA**

- External Height: 600 mm
- External Width: 400 mm
- External Depth: 200 mm
- Body Material: 304 Stainless Steel
- Transparent Door: No
- IP Rating: IP66
- Chassis Plate: Yes
- Door Lock Type: Quick Release Lock



7586964 600 mm

RS PRO 304 STAINLESS STEEL WALL BOX, IP66, 300 MM X 300 MM X

Pack size: **1 x EA**

- External Height: 300 mm
- External Width: 300 mm
- External Depth: 200 mm
- Body Material: 304 Stainless Steel
- Transparent Door: No
- IP Rating: IP66
- Chassis Plate: Yes
- Door Lock Type: Quick Release Lock



7586986 300 mm

RS PRO 304 STAINLESS STEEL WALL BOX, IP69K, 300 MM X 300 MM X

Pack size: **1 x EA**

- External Height: 300 mm
- External Width: 300 mm
- External Depth: 200 mm
- Body Material: 304 Stainless Steel
- Transparent Door: No
- IP Rating: IP69K
- Chassis Plate: No
- Door Lock Type: Key



7586996 300 mm

RS PRO 304 STAINLESS STEEL WALL BOX, IP66, 400 MM X 300 MM X

Pack size: **1 x EA**

- External Height: 300 mm
- External Width: 400 mm
- External Depth: 200 mm
- Body Material: 304 Stainless Steel
- Transparent Door: No
- IP Rating: IP66
- Chassis Plate: Yes
- Door Lock Type: Quick Release Lock



7586999 300 mm

RS PRO 304 STAINLESS STEEL WALL BOX, IP69K, 400 MM X 300 MM X

Pack size: **1 x EA**

- External Height: 400 mm
- External Width: 300 mm
- External Depth: 200 mm
- Body Material: 304 Stainless Steel
- Transparent Door: No
- IP Rating: IP69K
- Chassis Plate: No
- Door Lock Type: Key



7587002 400 mm

RS PRO 316 STAINLESS STEEL WALL BOX, IP69K, 300 MM X 300 MM X

Pack size: **1 x EA**

- External Height: 300 mm
- External Width: 300 mm
- External Depth: 200 mm
- Body Material: 316 Stainless Steel
- Transparent Door: No
- IP Rating: IP69K
- Chassis Plate: No
- Door Lock Type: Key



7587034 300 mm

RS PRO 316 STAINLESS STEEL WALL BOX, IP69K, 400 MM X 300 MM X

Pack size: **1 x EA**

- External Height: 300 mm
- External Width: 400 mm
- External Depth: 200 mm
- Body Material: 316 Stainless Steel
- Transparent Door: No
- IP Rating: IP69K
- Chassis Plate: No
- Door Lock Type: Key



7587037 300 mm

SS T BOX IP66 V2 300X200X80 (304)

Pack size: **1 x EA**

- External Height: 200 mm
- External Width: 300 mm
- External Depth: 80 mm
- Body Material: 304 Stainless Steel
- Transparent Door: No
- IP Rating: IP66
- Chassis Plate: No
- Gland Plate: No



7587040 200 mm

RS PRO 304 STAINLESS STEEL TERMINAL BOX, IP66, 300 MM X 200 MM X

Pack size: **1 x EA**

- External Height: 200 mm
- External Width: 300 mm
- External Depth: 120 mm
- Body Material: 304 Stainless Steel
- Transparent Door: No
- IP Rating: IP66
- Chassis Plate: No
- Gland Plate: No



7587065 200 mm

RS PRO 304 STAINLESS STEEL WALL BOX, IP69K, 600 MM X 500 MM X

Pack size: **1 x EA**

- External Height: 600 mm
- External Width: 500 mm
- External Depth: 300 mm
- Body Material: 304 Stainless Steel
- Transparent Door: No
- IP Rating: IP69K
- Chassis Plate: No
- Door Lock Type: Key



7587214 600 mm

RS PRO 316 STAINLESS STEEL WALL BOX, IP69K, 400 MM X 400 MM XPack size: **1 x EA**

- External Height: 400 mm
- External Width: 400 mm
- External Depth: 200 mm
- Body Material: 316 Stainless Steel
- Transparent Door: No
- IP Rating: IP69K
- Chassis Plate: No
- Door Lock Type: Key

**7587220** 400 mm**RS PRO ABS WALL BOX, IP65, 600 MM X 500 MM X 220MM**Pack size: **1 x EA**

- External Height: 600 mm
- External Width: 500 mm
- External Depth: 220 mm
- Body Material: ABS
- Transparent Door: No
- IP Rating: IP65
- Chassis Plate: Yes
- Door Lock Type: Single Lock System

**7696122** 600 mm**IP65 ABS WALL BOX, 330X250X130MM**Pack size: **1 x EA**

- External Height: 330 mm
- External Width: 250 mm
- External Depth: 130 mm
- Body Material: ABS
- Transparent Door: No
- IP Rating: IP65
- Chassis Plate: Yes
- Door Lock Type: Double Lock System

**7696125** 330 mm**RS PRO ABS WALL BOX, IP65, 500 MM X 350 MM X 195MM**Pack size: **1 x EA**

- External Height: 500 mm
- External Width: 350 mm
- External Depth: 195 mm
- Body Material: ABS
- Transparent Door: No
- IP Rating: IP65
- Chassis Plate: Yes
- Door Lock Type: Single Lock System

**7696128** 500 mm**RS PRO STEEL WALL BOX, IP66, 300 MM X 250 MM X 150MM**Pack size: **1 x EA**

- External Height: 300 mm
- External Width: 250 mm
- External Depth: 150 mm
- Body Material: Steel
- Transparent Door: No
- IP Rating: IP66
- Chassis Plate: Yes
- Door Lock Type: Single Lock System

**7755300** 300 mm**RS PRO STEEL WALL BOX, IP66, 400 MM X 300 MM X 210MM**Pack size: **1 x EA**

- External Height: 300 mm
- External Width: 400 mm
- External Depth: 210 mm
- Body Material: Steel
- Transparent Door: No
- IP Rating: IP66
- Chassis Plate: Yes
- Door Lock Type: Single Lock System

**7755312** 300 mm**RS PRO STEEL WALL BOX, IP66, 400 MM X 600 MM X 210MM**Pack size: **1 x EA**

- External Height: 400 mm
- External Width: 600 mm
- External Depth: 210 mm
- Body Material: Steel
- Transparent Door: No
- IP Rating: IP66
- Chassis Plate: Yes
- Door Lock Type: Single Lock System

**7755328** 400 mm**RS PRO STEEL WALL BOX, IP66, 600 MM X 600 MM X 210MM**Pack size: **1 x EA**

- External Height: 600 mm
- External Width: 600 mm
- External Depth: 210 mm
- Body Material: Steel
- Transparent Door: No
- IP Rating: IP66
- Chassis Plate: Yes
- Door Lock Type: Double Lock System

**7755340** 600 mm**RS PRO STEEL WALL BOX, IP66, 700 MM X 500 MM X 260MM**Pack size: **1 x EA**

- External Height: 700 mm
- External Width: 500 mm
- External Depth: 260 mm
- Body Material: Steel
- Transparent Door: No
- IP Rating: IP66
- Chassis Plate: Yes
- Door Lock Type: Double Lock System

**7755356** 700 mm**RS PRO STEEL WALL BOX, IP66, 300 MM X 400 MM X 200MM**Pack size: **1 x EA**

- External Height: 300 mm
- External Width: 400 mm
- External Depth: 200 mm
- Body Material: Steel
- Transparent Door: No
- IP Rating: IP66
- Chassis Plate: Yes
- Door Lock Type: Single Lock System

**7755794** 300 mm**RS PRO STEEL WALL BOX, IP66, 400 MM X 300 MM X 150MM**Pack size: **1 x EA**

- External Height: 400 mm
- External Width: 300 mm
- External Depth: 150 mm
- Body Material: Steel
- Transparent Door: No
- IP Rating: IP66
- Chassis Plate: Yes
- Door Lock Type: Single Lock System

**7755798** 400 mm**RS PRO STEEL WALL BOX, IP66, 400 MM X 300 MM X 200MM**Pack size: **1 x EA**

- External Height: 400 mm
- External Width: 300 mm
- External Depth: 200 mm
- Body Material: Steel
- Transparent Door: No
- IP Rating: IP66
- Chassis Plate: Yes
- Door Lock Type: Single Lock System

**7755808** 400 mm**RS PRO STEEL WALL BOX, IP66, 700 MM X 500 MM X 200MM**Pack size: **1 x EA**

- External Height: 700 mm
- External Width: 500 mm
- External Depth: 200 mm
- Body Material: Steel
- Transparent Door: No
- IP Rating: IP66
- Chassis Plate: Yes
- Door Lock Type: Double Lock System

**7755823** 700 mm**RS PRO STEEL WALL BOX, IP66, 400 MM X 300 MM X 210MM**Pack size: **1 x EA**

- External Height: 400 mm
- External Width: 300 mm
- External Depth: 210 mm
- Body Material: Steel
- Transparent Door: No
- IP Rating: IP66
- Chassis Plate: Yes
- Door Lock Type: Single Lock System

**7755316** 400 mm**RS PRO STEEL WALL BOX, IP66, 300 MM X 300 MM X 210MM**Pack size: **1 x EA**

- External Height: 300 mm
- External Width: 300 mm
- External Depth: 210 mm
- Body Material: Steel
- Transparent Door: No
- IP Rating: IP66
- Chassis Plate: Yes
- Door Lock Type: Single Lock System

**7755319** 300 mm**RS PRO STEEL WALL BOX, IP66, 500 MM X 400 MM X 210MM**Pack size: **1 x EA**

- External Height: 500 mm
- External Width: 400 mm
- External Depth: 210 mm
- Body Material: Steel
- Transparent Door: No
- IP Rating: IP66
- Chassis Plate: Yes
- Door Lock Type: Single Lock System

**7755322** 500 mm

RS PRO STEEL WALL BOX, IP66, 400 MM X 400 MM X 210MM

Pack size: **1 x EA**

- External Height: 400 mm
- External Width: 400 mm
- External Depth: 210 mm
- Body Material: Steel
- Transparent Door: No
- IP Rating: IP66
- Chassis Plate: Yes
- Door Lock Type: Single Lock System



7755325 400 mm

RS PRO STEEL WALL BOX, IP66, 500 MM X 500 MM X 210MM

Pack size: **1 x EA**

- External Height: 500 mm
- External Width: 500 mm
- External Depth: 210 mm
- Body Material: Steel
- Transparent Door: No
- IP Rating: IP66
- Chassis Plate: Yes
- Door Lock Type: Single Lock System



7755331 500 mm

RS PRO STEEL WALL BOX, IP66, 500 MM X 500 MM X 300MM

Pack size: **1 x EA**

- External Height: 500 mm
- External Width: 500 mm
- External Depth: 300 mm
- Body Material: Steel
- Transparent Door: No
- IP Rating: IP66
- Chassis Plate: Yes
- Door Lock Type: Single Lock System



7755334 500 mm

RS PRO STEEL WALL BOX, IP66, 600 MM X 400 MM X 210MM

Pack size: **1 x EA**

- External Height: 600 mm
- External Width: 400 mm
- External Depth: 210 mm
- Body Material: Steel
- Transparent Door: No
- IP Rating: IP66
- Chassis Plate: Yes
- Door Lock Type: Double Lock System



7755338 600 mm

RS PRO STEEL WALL BOX, IP66, 600 MM X 600 MM X 300MM

Pack size: **1 x EA**

- External Height: 600 mm
- External Width: 600 mm
- External Depth: 300 mm
- Body Material: Steel
- Transparent Door: No
- IP Rating: IP66
- Chassis Plate: Yes
- Door Lock Type: Double Lock System



7755344 600 mm

RS PRO STEEL WALL BOX, IP66, 600 MM X 400 MM X 300MM

Pack size: **1 x EA**

- External Height: 600 mm
- External Width: 400 mm
- External Depth: 300 mm
- Body Material: Steel
- Transparent Door: No
- IP Rating: IP66
- Chassis Plate: Yes
- Door Lock Type: Double Lock System



7755347 600 mm

MS WALL BOX WITH BRACKETS/CHASSIS PLATES

Pack size: **1 x EA**

- External Height: 200 mm
- External Width: 200 mm
- External Depth: 150 mm
- Body Material: Steel
- Transparent Door: No
- IP Rating: IP66
- Chassis Plate: Yes
- Door Lock Type: Single Lock System



7755785 200 mm

RS PRO STEEL WALL BOX, IP66, 300 MM X 200 MM X 150MM

Pack size: **1 x EA**

- External Height: 300 mm
- External Width: 200 mm
- External Depth: 150 mm
- Body Material: Steel
- Transparent Door: No
- IP Rating: IP66
- Chassis Plate: Yes
- Door Lock Type: Single Lock System



7755788 300 mm

RS PRO STEEL WALL BOX, IP66, 300 MM X 300 MM X 150MM

Pack size: **1 x EA**

- External Height: 300 mm
- External Width: 300 mm
- External Depth: 150 mm
- Body Material: Steel
- Transparent Door: No
- IP Rating: IP66
- Chassis Plate: Yes
- Door Lock Type: Single Lock System



7755791 300 mm

RS PRO STEEL WALL BOX, IP66, 400 MM X 400 MM X 200MM

Pack size: **1 x EA**

- External Height: 400 mm
- External Width: 400 mm
- External Depth: 200 mm
- Body Material: Steel
- Transparent Door: No
- IP Rating: IP66
- Chassis Plate: Yes
- Door Lock Type: Single Lock System



7755801 400 mm

RS PRO STEEL WALL BOX, IP66, 500 MM X 400 MM X 150MM

Pack size: **1 x EA**

- External Height: 500 mm
- External Width: 400 mm
- External Depth: 150 mm
- Body Material: Steel
- Transparent Door: No
- IP Rating: IP66
- Chassis Plate: Yes
- Door Lock Type: Single Lock System



7755805 500 mm

RS PRO STEEL WALL BOX, IP66, 600 MM X 500 MM X 200MM

Pack size: **1 x EA**

- External Height: 600 mm
- External Width: 500 mm
- External Depth: 200 mm
- Body Material: Steel
- Transparent Door: No
- IP Rating: IP66
- Chassis Plate: Yes
- Door Lock Type: Double Lock System



7755811 600 mm

RS PRO STEEL WALL BOX, IP66, 500 MM X 400 MM X 200MM

Pack size: **1 x EA**

- External Height: 500 mm
- External Width: 400 mm
- External Depth: 200 mm
- Body Material: Steel
- Transparent Door: No
- IP Rating: IP66
- Chassis Plate: Yes
- Door Lock Type: Single Lock System



7755814 500 mm

RS PRO STEEL WALL BOX, IP66, 600 MM X 400 MM X 200MM

Pack size: **1 x EA**

- External Height: 600 mm
- External Width: 400 mm
- External Depth: 200 mm
- Body Material: Steel
- Transparent Door: No
- IP Rating: IP66
- Chassis Plate: Yes
- Door Lock Type: Double Lock System



7755817 600 mm

RS PRO STEEL WALL BOX, IP66, 300 MM X 200 MM X 200MM

Pack size: **1 x EA**

- External Height: 300 mm
- External Width: 200 mm
- External Depth: 200 mm
- Body Material: Steel
- Transparent Door: No
- IP Rating: IP66
- Chassis Plate: Yes
- Door Lock Type: Single Lock System



8428305 300 mm

RS PRO 304 STAINLESS STEEL WALL BOX, IP66, 400 MM X 300 MM X 150MM

Pack size: **1 x EA**

- External Height: 400 mm
- External Width: 300 mm
- External Depth: 200 mm
- Body Material: 304 Stainless Steel
- Transparent Door: No
- IP Rating: IP66
- Chassis Plate: Yes
- Door Lock Type: Single Lock System



8428342 400 mm

RS PRO 304 STAINLESS STEEL WALL BOX, IP66, 500 MM X 400 MM XPack size: **1 x EA**

- External Height: 500 mm
- External Width: 400 mm
- External Depth: 200 mm
- Body Material: 304 Stainless Steel
- Transparent Door: No
- IP Rating: IP66
- Chassis Plate: No
- Door Lock Type: Single Lock System

**8428346** 500 mm**RS PRO 304 STAINLESS STEEL WALL BOX, IP66, 600 MM X 400 MM X**Pack size: **1 x EA**

- External Height: 600 mm
- External Width: 400 mm
- External Depth: 200 mm
- Body Material: 304 Stainless Steel
- Transparent Door: No
- IP Rating: IP66
- Chassis Plate: No
- Door Lock Type: Single Lock System

**8428349** 600 mm**RS PRO 304 STAINLESS STEEL WALL BOX, IP66, 600 MM X 400 MM X**Pack size: **1 x EA**

- External Height: 600 mm
- External Width: 400 mm
- External Depth: 200 mm
- Body Material: 304 Stainless Steel
- Transparent Door: No
- IP Rating: IP66
- Chassis Plate: Yes
- Door Lock Type: Double Lock System

**8428355** 600 mm**RS PRO 304 STAINLESS STEEL WALL BOX, IP66, 400 MM X 300 MM X**Pack size: **1 x EA**

- External Height: 400 mm
- External Width: 300 mm
- External Depth: 150 mm
- Body Material: 304 Stainless Steel
- Transparent Door: No
- IP Rating: IP66
- Chassis Plate: Yes
- Door Lock Type: Single Lock System

**8428361** 400 mm**RS PRO 304 STAINLESS STEEL WALL BOX, IP66, 700 MM X 500 MM X**Pack size: **1 x EA**

- External Height: 700 mm
- External Width: 500 mm
- External Depth: 250 mm
- Body Material: 304 Stainless Steel
- Transparent Door: No
- IP Rating: IP66
- Chassis Plate: No
- Door Lock Type: Double Lock System

**8428364** 700 mm**RS PRO 304 STAINLESS STEEL WALL BOX, IP66, 300 MM X 300 MM X**Pack size: **1 x EA**

- External Height: 300 mm
- External Width: 300 mm
- External Depth: 200 mm
- Body Material: 304 Stainless Steel
- Transparent Door: No
- IP Rating: IP66
- Chassis Plate: No
- Door Lock Type: Single Lock System

**8428370** 300 mm**RS PRO 304 STAINLESS STEEL WALL BOX, IP66, 500 MM X 500 MM X**Pack size: **1 x EA**

- External Height: 500 mm
- External Width: 500 mm
- External Depth: 200 mm
- Body Material: 304 Stainless Steel
- Transparent Door: No
- IP Rating: IP66
- Chassis Plate: No
- Door Lock Type: Single Lock System

**8428374** 500 mm**RS PRO 304 STAINLESS STEEL WALL BOX, IP66, 400 MM X 300 MM X**Pack size: **1 x EA**

- External Height: 400 mm
- External Width: 300 mm
- External Depth: 150 mm
- Body Material: 304 Stainless Steel
- Transparent Door: No
- IP Rating: IP66
- Chassis Plate: No
- Door Lock Type: Single Lock System

**8428380** 400 mm**RS PRO 304 STAINLESS STEEL WALL BOX, IP66, 400 MM X 300 MM X**Pack size: **1 x EA**

- External Height: 400 mm
- External Width: 300 mm
- External Depth: 200 mm
- Body Material: 304 Stainless Steel
- Transparent Door: No
- IP Rating: IP66
- Chassis Plate: No
- Door Lock Type: Single Lock System

**8428383** 400 mm**RS PRO 304 STAINLESS STEEL WALL BOX, IP66, 300 MM X 250 MM X**Pack size: **1 x EA**

- External Height: 300 mm
- External Width: 250 mm
- External Depth: 150 mm
- Body Material: 304 Stainless Steel
- Transparent Door: No
- IP Rating: IP66
- Chassis Plate: No
- Door Lock Type: Single Lock System

**8428386** 300 mm**IP66 WALL BOX, S/STEEL, 200X200X150MM**Pack size: **1 x EA**

- External Height: 200 mm
- External Width: 200 mm
- External Depth: 150 mm
- Body Material: 304 Stainless Steel
- Transparent Door: No
- IP Rating: IP66
- Chassis Plate: No
- Door Lock Type: Single Lock System

**8428399** 200 mm**RS PRO 304 STAINLESS STEEL WALL BOX, IP66, 500 MM X 400 MM X**Pack size: **1 x EA**

- External Height: 500 mm
- External Width: 400 mm
- External Depth: 250 mm
- Body Material: 304 Stainless Steel
- Transparent Door: No
- IP Rating: IP66
- Chassis Plate: No
- Door Lock Type: Single Lock System

**8428403** 500 mm**RS PRO 304 STAINLESS STEEL WALL BOX, IP66, 300 MM X 300 MM X**Pack size: **1 x EA**

- External Height: 300 mm
- External Width: 300 mm
- External Depth: 150 mm
- Body Material: 304 Stainless Steel
- Transparent Door: No
- IP Rating: IP66
- Chassis Plate: No
- Door Lock Type: Single Lock System

**8428406** 300 mm**RS PRO 304 STAINLESS STEEL WALL BOX, IP66, 400 MM X 400 MM X**Pack size: **1 x EA**

- External Height: 400 mm
- External Width: 400 mm
- External Depth: 200 mm
- Body Material: 304 Stainless Steel
- Transparent Door: No
- IP Rating: IP66
- Chassis Plate: No
- Door Lock Type: Single Lock System

**8428409** 400 mm**IP66 WALL BOX, S/STEEL, 240X180X150MM**Pack size: **1 x EA**

- External Height: 240 mm
- External Width: 180 mm
- External Depth: 150 mm
- Body Material: 304 Stainless Steel
- Transparent Door: No
- IP Rating: IP66
- Chassis Plate: No
- Door Lock Type: Single Lock System

**8428412** 240 mm**RS PRO 304 STAINLESS STEEL WALL BOX, IP66, 240 MM X 240 MM X**Pack size: **1 x EA**

- External Height: 240 mm
- External Width: 240 mm
- External Depth: 150 mm
- Body Material: 304 Stainless Steel
- Transparent Door: No
- IP Rating: IP66
- Chassis Plate: No
- Door Lock Type: Single Lock System

**8428419** 240 mm

RS PRO 304 STAINLESS STEEL WALL BOX, IP66, 360 MM X 180 MM X

Pack size: **1 x EA**

- External Height: 360 mm
- External Width: 180 mm
- External Depth: 150 mm
- Body Material: 304 Stainless Steel
- Transparent Door: No
- IP Rating: IP66
- Chassis Plate: No
- Door Lock Type: Single Lock System



8428421 360 mm

RS PRO 304 STAINLESS STEEL WALL BOX, IP66, 360 MM X 240 MM X

Pack size: **1 x EA**

- External Height: 360 mm
- External Width: 240 mm
- External Depth: 150 mm
- Body Material: 304 Stainless Steel
- Transparent Door: No
- IP Rating: IP66
- Chassis Plate: No
- Door Lock Type: Single Lock System



8428434 360 mm

RS PRO 304 STAINLESS STEEL WALL BOX, IP66, 480 MM X 360 MM X

Pack size: **1 x EA**

- External Height: 480 mm
- External Width: 360 mm
- External Depth: 150 mm
- Body Material: 304 Stainless Steel
- Transparent Door: No
- IP Rating: IP66
- Chassis Plate: No
- Door Lock Type: Single Lock System



8428437 480 mm

RS PRO 304 STAINLESS STEEL WALL BOX, IP66, 360 MM X 360 MM X

Pack size: **1 x EA**

- External Height: 360 mm
- External Width: 360 mm
- External Depth: 240 mm
- Body Material: 304 Stainless Steel
- Transparent Door: No
- IP Rating: IP66
- Chassis Plate: No
- Door Lock Type: Single Lock System



8428440 360 mm

RS PRO STEEL WALL BOX, IP66, 400 MM X 400 MM X 150MM

Pack size: **1 x EA**

- External Height: 400 mm
- External Width: 400 mm
- External Depth: 150 mm
- Body Material: Steel
- Transparent Door: No
- IP Rating: IP66
- Chassis Plate: Yes
- Door Lock Type: Single Lock System



8428443 400 mm

RS PRO STEEL WALL BOX, IP66, 500 MM X 400 MM X 300MM

Pack size: **1 x EA**

- External Height: 500 mm
- External Width: 400 mm
- External Depth: 300 mm
- Body Material: Steel
- Transparent Door: No
- IP Rating: IP66
- Chassis Plate: No
- Door Lock Type: Single Lock System



8428447 500 mm

RS PRO STEEL WALL BOX, IP66, 600 MM X 600 MM X 200MM

Pack size: **1 x KT**

- External Height: 600 mm
- External Width: 600 mm
- External Depth: 200 mm
- Body Material: Steel
- Transparent Door: No
- IP Rating: IP66
- Chassis Plate: Yes
- Door Lock Type: Double Lock System



9155963 600 mm

RS PRO STEEL WALL BOX, IP66, 400 MM X 210 MM X 600MM

Pack size: **1 x KT**

- External Height: 400 mm
- External Width: 210 mm
- External Depth: 600 mm
- Body Material: Steel
- Transparent Door: No
- IP Rating: IP66
- Chassis Plate: Yes
- Door Lock Type: Single Lock System



9155979 400 mm

RS PRO TOP PLUNGER, 2NC/1NO, IP67, PLASTIC HOUSING

Pack size: **1 x EA**

- Normal State Configuration: 2NC/1NO
- IP Rating: IP67
- Housing Material: Plastic
- Connection Type: M20
- Length: 31 mm
- Width: 31 mm
- Depth: 95 mm
- Mechanical Life: 10000000 Operacje



1797561 2NC/1NO

RS PRO TOP PLUNGER, 2NC, IP67, PLASTIC HOUSING

Pack size: **1 x EA**

- Normal State Configuration: 2NC
- IP Rating: IP67
- Housing Material: Plastic
- Connection Type: M20
- Length: 31 mm
- Width: 31 mm
- Depth: 95 mm
- Mechanical Life: 10000000 Operacje



1797562 2NC

RS PRO TOP PLUNGER, NO/NC, IP67, PLASTIC HOUSING

Pack size: **1 x EA**

- Normal State Configuration: NO/NC
- IP Rating: IP67
- Housing Material: Plastic
- Connection Type: M20
- Length: 31 mm
- Width: 31 mm
- Depth: 95 mm
- Mechanical Life: 10000000 Operacje



1797563 NO/NC

RS PRO ROLLER LEVER INTERLOCK SWITCH, NO/NC, IP67, GLASS

Pack size: **1 x EA**

- Actuator Type: Roller Lever
- Normal State Configuration: NO/NC
- IP Rating: IP67
- Housing Material: Glass Reinforced Plastic (GRP)
- Length: 31 mm
- Width: 31 mm
- Depth: 89 mm
- Mechanical Life: 10000000 Operacje



1797566 Roller Lever

RS PRO ROLLER PLUNGER TOP PLUNGER, NO/NC, IP67, GLASS

Pack size: **1 x EA**

- Actuator Type: Roller Plunger
- Normal State Configuration: NO/NC
- IP Rating: IP67
- Housing Material: Glass Reinforced Plastic (GRP)
- Length: 31 mm
- Width: 30.5 mm
- Depth: 84.5 mm
- Mechanical Life: 10000000 Operacje



1797567 Roller Plunger

RS PRO CATS WHISKER TOP PLUNGER, NO/NC, IP67, GLASS

Pack size: **1 x EA**

- Actuator Type: Cats Whisker
- Normal State Configuration: NO/NC
- IP Rating: IP67
- Housing Material: Glass Reinforced Plastic (GRP)
- Length: 31 mm
- Width: 31 mm
- Depth: 172 mm
- Mechanical Life: 10000000 Operacje



1797565 Cats Whisker

RS PRO PLUNGER LIMIT SWITCH, NO/NC, IP67, GLASS REINFORCED

Pack size: **1 x EA**

- Actuator Type: Plunger
- Normal State Configuration: NO/NC
- IP Rating: IP67
- Housing Material: Glass Reinforced Plastic (GRP)
- Length: 31 mm
- Width: 31 mm
- Depth: 74.5 mm
- Mechanical Life: 10000000 Operations



1797568 Plunger

RS PRO ROLLER LEVER LIMIT SWITCH, NO/NC, IP67, GLASS REINFORCED

Pack size: **1 x EA**

- Actuator Type: Roller Lever
- Normal State Configuration: NO/NC
- IP Rating: IP67
- Housing Material: Glass Reinforced Plastic (GRP)
- Length: 31 mm
- Width: 45 mm
- Depth: 62 mm
- Mechanical Life: 10000000 Operacje



1797569 Roller Lever

RS PRO ROLLER LEVER TOP PLUNGER, NO/NC, IP67, GLASS REINFORCED

Pack size: **1 x EA**

- Actuator Type: Roller Lever
- Normal State Configuration: NO/NC
- IP Rating: IP67
- Housing Material: Glass Reinforced Plastic (GRP)
- Length: 31 mm
- Width: 47.5 mm
- Depth: 107 mm
- Mechanical Life: 10000000 Operacje



1797570 Roller Lever

RS PRO SAFETY INTERLOCK SWITCH, 600V AC, 2NC

Pack size: **1 x EA**

- Supply Voltage: 600 V ac
- Actuator Type: Key
- Conduit Entry: PG13.5
- Normal State Configuration: 2NC
- Housing Material: Plastic
- IP Rating: IP67
- Maximum AC Voltage: 600 V
- Width: 31 mm



1797564 600 V ac

RS PRO LIMIT SWITCH OPERATING HEAD FOR USE WITH 1797561,

Pack size: **1 x EA**

- Accessory Type: Actuator
- For Use With: 1797561, 1797563, 1797564



1808172 Actuator

RS PRO IMAGER 2D SCANNING BARCODE SCANNER

Pack size: **1 x EA**

- Product Type: Barcode Scanner
- Model: H261U
- Scanning Technology: Imager
- Maximum Scan Distance: 50 cm
- Wireless: No
- 2D Scanning: Yes
- Interface: USB
- Dimensions: 180 x 65 x 105 mm



2067501 Barcode Scanner

RS PRO CAT6 ETHERNET CABLE, RJ45 TO RJ45, U/UTP SHIELD, BLUE PVC

Pack size: **1 x EA**

- Connector 1: RJ45
- LAN Category: Cat6
- Terminated/Unterminated: Terminated
- Connector 2: RJ45
- Connector 1 Gender: Male
- Connector 2 Gender: Male
- Length: 2 m
- Shield Type: U/UTP



2055985 RJ45

RS PRO PLASTIC FIBRE OPTIC SENSOR 0.01 MM, NPN OUTPUT IO-

Pack size: **1 x EA**

- Detection Range: 0.01 mm
- Output Type: NPN
- Fibre Optic Type: Plastic
- Terminal Type: 2m PVC cable
- Response Time: 60 seconds
- Power Consumption: 1.44 W
- IP Rating: IP54
- Supply Voltage: 24 V dc



2040681 0.01 mm

RS PRO PLASTIC FIBRE OPTIC SENSOR 180 MM, IP54

Pack size: **1 x EA**

- Detection Range: 180 mm
- Fibre Optic Type: Plastic
- Terminal Type: Fiber Amplifier
- IP Rating: IP54
- Housing Material: Plastic
- Maximum Operating Temperature: +70 °C
- Minimum Operating Temperature: -55 °C



2199007 180 mm

RS PRO PLASTIC FIBRE OPTIC SENSOR 500 MM, IP54

Pack size: **1 x EA**

- Detection Range: 500 mm
- Fibre Optic Type: Plastic
- Terminal Type: Fiber Amplifier
- IP Rating: IP54
- Housing Material: Plastic
- Maximum Operating Temperature: +70 °C
- Minimum Operating Temperature: -55 °C



2199009 500 mm

RS PRO PLASTIC FIBRE OPTIC SENSOR 0.01 MM, PNP OUTPUT IO-

Pack size: **1 x EA**

- Detection Range: 0.01 mm
- Output Type: PNP
- Fibre Optic Type: Plastic
- Terminal Type: 2m PVC cable
- Response Time: <0.0002 (Fine mode) seconds, <0.0003 (Turbo mode) seconds, <0.00055 (Super) seconds
- Power Consumption: 1.44 W
- IP Rating: IP54
- Supply Voltage: 24 V dc



2040682 0.01 mm

RS PRO PLASTIC FIBRE OPTIC SENSOR 1000 MM, IP54

Pack size: **1 x EA**

- Detection Range: 1000 mm
- Fibre Optic Type: Plastic
- Terminal Type: Fiber Amplifier
- IP Rating: IP54
- Housing Material: Plastic
- Maximum Operating Temperature: +70 °C
- Minimum Operating Temperature: -55 °C



2199010 1000 mm

RS PRO PLASTIC FIBRE OPTIC SENSOR 140 MM, IP54

Pack size: **1 x EA**

- Detection Range: 140 mm
- Fibre Optic Type: Plastic
- Terminal Type: Fiber Amplifier
- IP Rating: IP54
- Housing Material: Plastic
- Maximum Operating Temperature: +70 °C
- Minimum Operating Temperature: -55 °C



2199008 140 mm

RS PRO PLASTIC FIBRE OPTIC SENSOR 1000 MM, IP54

Pack size: **1 x EA**

- Detection Range: 1000 mm
- Fibre Optic Type: Plastic
- Terminal Type: Fiber Amplifier
- IP Rating: IP54
- Housing Material: Plastic
- Maximum Operating Temperature: +70 °C
- Minimum Operating Temperature: -55 °C



2199011 1000 mm

RS PRO FIBRE OPTIC SENSOR 500 MM, IP65

Pack size: **1 x EA**

- Detection Range: 500 mm
- Terminal Type: M4
- Electrical Connection: Cable
- IP Rating: IP65
- Length: 500 mm
- Standards Met: CE



8967285 500 mm

RS PRO FIBRE OPTIC SENSOR 110 MM, IP65

Pack size: **1 x EA**

- Detection Range: 110 mm
- Terminal Type: M6
- Electrical Connection: Cable
- IP Rating: IP65
- Length: 110 mm
- Standards Met: CE



8967298 110 mm

RS PRO FIBRE OPTIC SENSOR, NPN-NO, PNP-NC OUTPUT, IP65, 12 → 24 V

Pack size: **1 x EA**

- Output Type: NPN-NO, PNP-NC
- Response Time: <1 ms
- Light Source: Red LED
- Electrical Connection: PVC Cable
- Switching Frequency: 50 Hz
- IP Rating: IP65
- Housing Material: ABS, PC
- Supply Voltage: 12 → 24 V dc



8967305 NPN-NO, PNP-NC

RS PRO CIRCULAR CONNECTOR

Pack size: **1 x EA**

- Connector A: M12 A Coded CANopen/DeviceNet Terminating Resistor
- Connector A Gender: Male
- Connector B Gender: Male
- Connector A Number of Contacts: 4
- Current Rating: 4 A
- IP Rating: IP67
- Voltage Rating: 30 V
- Maximum Operating Temperature: +75 °C



2055982 M12 A Coded

SWITCH,SENSOR,PROXIMITY,REED,H D,FORM A,N/O

Pack size: **1 x EA**

- Switch Shape: Rectangular
- Normal State Configuration: NO
- Maximum Current: 5 A
- Maximum AC Voltage: 1500 V
- Maximum DC Voltage: 1500 V
- Contact Resistance: 100 mΩ
- Length: 80 mm
- Maximum Operating Temperature: +85 °C



339746 Rectangular

SWITCH,SENSOR,PROXIMITY,REED,H D,FORM C,CHANGEVER

Pack size: **1 x EA**

- Switch Shape: Rectangular
- Maximum Current: 2 A
- Maximum AC Voltage: 400 V
- Maximum DC Voltage: 400 V
- Contact Resistance: 100 mΩ
- Length: 80 mm
- Width: 10 mm
- Maximum Operating Temperature: +85 °C



339752 Rectangular

RS PRO REED SWITCH RECTANGULAR 140V, NO/NC, 2.75A

Pack size: **1 x EA**

- Switch Shape: Rectangular
- Normal State Configuration: NO/NC
- Terminal Type: Wire Lead
- Maximum Current: 2.75 A
- Maximum AC Voltage: 140 V
- Maximum DC Voltage: 200 V
- Switching Frequency: 100 Hz
- Contact Resistance: 100 mΩ



1365754 Rectangular

REED SWITCH SIDE FACING

Pack size: **1 x EA**

- Switch Shape: Rectangular
- Pole and Throw Configuration: SPST-NO
- Normal State Configuration: NO/NC
- Terminal Type: Wire Lead
- Maximum Current: 250 mA
- Maximum AC Voltage: 140 V
- Maximum DC Voltage: 200 V
- Switching Frequency: 100 Hz



1365753 Rectangular

RS PRO REED SWITCH RECTANGULAR 140V, NO/NC, 2.75A

Pack size: **1 x EA**

- Switch Shape: Rectangular
- Pole and Throw Configuration: SPST-NO
- Normal State Configuration: NO/NC
- Terminal Type: Wire Lead
- Maximum Current: 2.75 A
- Maximum AC Voltage: 140 V
- Maximum DC Voltage: 200 V
- Switching Frequency: 100 Hz



1365755 Rectangular

RS PRO REED SWITCH RECTANGULAR 140V, NO/NC, 2.75A

Pack size: **1 x EA**

- Switch Shape: Rectangular
- Pole and Throw Configuration: SPST-NO
- Normal State Configuration: NO/NC
- Terminal Type: Wire Lead
- Maximum Current: 2.75 A
- Maximum AC Voltage: 140 V
- Maximum DC Voltage: 200 V
- Switching Frequency: 100 Hz



1365756 Rectangular

RS PRO REED SWITCH RECTANGULAR 140V, NO/NC, 2.75A

Pack size: **1 x EA**

- Switch Shape: Rectangular
- Pole and Throw Configuration: SPST-NO
- Normal State Configuration: NO/NC
- Terminal Type: Wire Lead
- Maximum Current: 2.75 A
- Maximum AC Voltage: 140 V
- Maximum DC Voltage: 200 V
- Switching Frequency: 100 Hz



1365757 Rectangular

RS PRO REED SWITCH RECTANGULAR 400V, NC, 1A

Pack size: **1 x EA**

- Switch Shape: Rectangular
- Pole and Throw Configuration: SPST-NO
- Normal State Configuration: NC
- Terminal Type: Wire Lead
- Maximum Current: 1 A
- Maximum AC Voltage: 400 V
- Contact Resistance: 150 mΩ
- Total Length: 1032.5 mm



1365758 Rectangular

RS PRO REED SWITCH RECTANGULAR 200V, NO, 500MA, IP67

Pack size: **1 x EA**

- Switch Shape: Rectangular
- Normal State Configuration: NO
- Maximum Current: 500 mA
- Maximum AC Voltage: 200 V
- Contact Resistance: 300 mΩ
- Total Length: 312 mm
- Length: 32 mm
- Depth: 15 mm



3614911 Rectangular

RS PRO REED SWITCH CYLINDRICAL 200V, NO, 500MA

Pack size: **1 x EA**

- Switch Shape: Cylindrical
- Normal State Configuration: NO
- Terminal Type: Screw
- Maximum Current: 500 mA
- Maximum AC Voltage: 200 V
- Maximum DC Voltage: 200 V
- Contact Resistance: 200 mΩ
- Total Length: 308 mm



3614933 Cylindrical

REED PROXIMITY SWITCHES, CYLINDRICAL REED SENSOR 4MM

Pack size: **1 x EA**

- Switch Shape: Cylindrical
- Pole and Throw Configuration: SPST
- Normal State Configuration: NO
- Terminal Type: Wire Lead
- Maximum Current: 1.5 A
- Maximum AC Voltage: 180 V
- Maximum DC Voltage: 180 V
- Contact Resistance: 150 mΩ



5308911 Cylindrical

REED PROXIMITY SWITCHES, CYLINDRICAL REED SENSOR ONLY

Pack size: **1 x EA**

- Switch Shape: Cylindrical
- Pole and Throw Configuration: SPST
- Normal State Configuration: NO
- Terminal Type: Wire Lead
- Maximum Current: 1 A
- Maximum AC Voltage: 400 V
- Maximum DC Voltage: 400 V
- Contact Resistance: 150 mΩ



5308927 Cylindrical

REED PROXIMITY SWITCHES, MOULDED REED SENSOR, SCREW

Pack size: **1 x EA**

- Switch Shape: Flat
- Pole and Throw Configuration: SPST
- Normal State Configuration: NO
- Terminal Type: Screw
- Maximum Current: 500 mA
- Maximum AC Voltage: 180 V
- Maximum DC Voltage: 500 V
- Contact Resistance: 150 mΩ



5308949 Flat

RS PRO REED SWITCH FLAT 200V, NO, 1A

Pack size: **1 x EA**

- Switch Shape: Flat
- Pole and Throw Configuration: SPST
- Normal State Configuration: NO
- Maximum Current: 1 A
- Maximum AC Voltage: 200 V
- Maximum DC Voltage: 200 V
- Contact Resistance: 150 mΩ
- Total Length: 19.5 mm



5308961 Flat

RS PRO REED SWITCH FLAT 200V, NO, 500MA

Pack size: **1 x EA**

- Switch Shape: Flat
- Pole and Throw Configuration: SPST
- Normal State Configuration: NO
- Maximum Current: 500 mA
- Maximum AC Voltage: 200 V
- Maximum DC Voltage: 200 V
- Contact Resistance: 150 mΩ
- Total Length: 15.6 mm



5308977 Flat

RS PRO REED SWITCH FLAT 170V, NO, 500MA

Pack size: **1 x EA**

- Switch Shape: Flat
- Pole and Throw Configuration: SPST
- Normal State Configuration: NO
- Maximum Current: 500 mA
- Maximum AC Voltage: 170 V
- Maximum DC Voltage: 170 V
- Contact Resistance: 200 mΩ
- Total Length: 12.5 mm



5308999 Flat

RS PRO REED SWITCH FLAT 200V, NO, 1.5A

Pack size: **1 x EA**

- Switch Shape: Flat
- Pole and Throw Configuration: SPNO
- Normal State Configuration: NO
- Maximum Current: 1.5 A
- Maximum AC Voltage: 200 V
- Maximum DC Voltage: 200 V
- Contact Resistance: 150 mΩ
- Total Length: 15.6 mm



5309009 Flat

RS PRO PROXIMITY SWITCH RECTANGULAR 250V, NO, 500MA

Pack size: **1 x EA**

- Switch Shape: Rectangular
- Normal State Configuration: NO
- Terminal Type: Wire Lead
- Maximum Current: 500 mA
- Maximum AC Voltage: 250 V
- Maximum DC Voltage: 150 V
- Switching Frequency: 200 Hz
- Contact Resistance: 150 mΩ



8110736 Rectangular

REED SWITCH, CHANGE OVER, 175VAC

Pack size: **1 x EA**

- Switch Shape: Rectangular
- Normal State Configuration: CO
- Terminal Type: Wire Lead
- Maximum Current: 400 mA
- Maximum AC Voltage: 125 V
- Maximum DC Voltage: 175 V
- Contact Resistance: 120 mΩ
- Total Length: 328.5 mm



8110748 Rectangular

RS PRO CYLINDRICAL MAGNET 3MM

Pack size: **1 x EA**

- Magnet Type: Cylindrical
- Width/Diameter: 3 mm
- Length: 12 mm



5361726 Cylindrical

RS PRO DIFFUSE PHOTOELECTRIC SENSOR, BARREL SENSOR, 200 MM

Pack size: **1 x EA**

- Sensor Style: Barrel
- Detection Type: Diffuse
- Detection Range: 200 mm
- Output Type: PNP
- Electrical Connection: M12 Connector
- Maximum DC Voltage: 30 V
- Light Source: Infrared
- IP Rating: IP67



2564005 Barrel

RS PRO POLARISED RETRO REFLECTION PHOTOELECTRIC

Pack size: **1 x EA**

- Sensor Style: Block
- Detection Type: Polarised Retro Reflection
- Detection Range: 3 m
- Output Type: NPN NO/NC
- Electrical Connection: Cable
- Maximum DC Voltage: 30 V
- Terminal Type: M8 Connector
- Light Source: LED



2018161 Block

RS PRO POLARISED RETRO REFLECTION PHOTOELECTRIC

Pack size: **1 x EA**

- Sensor Style: Block
- Detection Type: Polarised Retro Reflection
- Detection Range: 3 m
- Output Type: PNP NO/NC
- Electrical Connection: Cable
- Maximum DC Voltage: 30 V
- Terminal Type: M8 Connector
- Light Source: LED



2018163 Block

RS PRO DIFFUSE PHOTOELECTRIC SENSOR, BLOCK SENSOR, 1 M

Pack size: **1 x EA**

- Sensor Style: Block
- Detection Type: Diffuse
- Detection Range: 1 m
- Output Type: NPN
- Electrical Connection: Cable 2 m
- Terminal Type: Cable 2 m
- Series: PSE



2024424 Block

RS PRO DIFFUSE PHOTOELECTRIC SENSOR, BLOCK SENSOR, 1 M

Pack size: **1 x EA**

- Sensor Style: Block
- Detection Type: Diffuse
- Detection Range: 1 m
- Output Type: PNP
- Electrical Connection: Cable 2 m
- Terminal Type: Cable 2 m
- Series: PSE



2024426 Block

RS PRO DIFFUSE PHOTOELECTRIC SENSOR, BLOCK SENSOR, 100 MM

Pack size: **1 x EA**

- Sensor Style: Block
- Detection Type: Diffuse
- Detection Range: 100 mm
- Output Type: NPN
- Electrical Connection: Cable 2 m
- Terminal Type: Cable 2 m
- Series: PSE



2024428 Block

RS PRO DIFFUSE PHOTOELECTRIC SENSOR, BLOCK SENSOR, 100 MM

Pack size: **1 x EA**

- Sensor Style: Block
- Detection Type: Diffuse
- Detection Range: 100 mm
- Output Type: NPN
- Electrical Connection: M8 Connector
- Terminal Type: M8 Connector
- Series: PSE



2024429 Block

RS PRO DIFFUSE PHOTOELECTRIC SENSOR, BLOCK SENSOR, 100 MM

Pack size: **1 x EA**

- Sensor Style: Block
- Detection Type: Diffuse
- Detection Range: 100 mm
- Output Type: PNP
- Electrical Connection: M8 Connector
- Terminal Type: M8 Connector
- Series: PSE



2024432 Block

RS PRO DIFFUSE PHOTOELECTRIC SENSOR, BLOCK SENSOR, 300 MM

Pack size: **1 x EA**

- Sensor Style: Block
- Detection Type: Diffuse
- Detection Range: 300 mm
- Output Type: PNP NO/NC
- Electrical Connection: M8 Connector
- Terminal Type: M8 Connector
- Series: PSE



2024436 Block

RS PRO POLARISED RETRO REFLECTION PHOTOELECTRIC

Pack size: **1 x EA**

- Sensor Style: Block
- Detection Type: Polarised Retro Reflection
- Detection Range: 4 m
- Output Type: PNP NO/NC
- Electrical Connection: M8 Connector
- Terminal Type: M8 Connector
- Series: PSE



2024440 Block

RS PRO THROUGH BEAM RECEIVER PHOTOELECTRIC SENSOR, BLOCK

Pack size: **1 x EA**

- Sensor Style: Block
- Detection Type: Through Beam Receiver
- Detection Range: 10 m
- Output Type: PNP NO/NC
- Electrical Connection: Cable 2 m
- Terminal Type: Cable 2 m
- Series: PSE



2024441 Block

RS PRO THROUGH BEAM RECEIVER PHOTOELECTRIC SENSOR, BLOCK

Pack size: **1 x EA**

- Sensor Style: Block
- Detection Type: Through Beam Receiver
- Detection Range: 4 m
- Output Type: PNP NO/NC
- Electrical Connection: Cable 2 m
- Terminal Type: Cable 2 m
- Series: PSE



2024443 Block

RS PRO THROUGH BEAM RECEIVER PHOTOELECTRIC SENSOR, BLOCK

Pack size: **1 x EA**

- Sensor Style: Block
- Detection Type: Through Beam Receiver
- Detection Range: 10 m
- Output Type: NPN NO/NC
- Electrical Connection: M8 Connector
- Terminal Type: M8 Connector
- Series: PSE



2024442 Block

RS PRO THROUGH BEAM RECEIVER PHOTOELECTRIC SENSOR, BLOCK

Pack size: **1 x EA**

- Sensor Style: Block
- Detection Type: Through Beam Receiver
- Detection Range: 10 m
- Output Type: PNP NO/NC
- Electrical Connection: M8 Connector
- Terminal Type: M8 Connector
- Series: PSE



2024444 Block

RS PRO THROUGH BEAM EMITTER PHOTOELECTRIC SENSOR, BLOCK

Pack size: **1 x EA**

- Sensor Style: Block
- Detection Type: Through Beam Emitter
- Detection Range: 10 m
- Electrical Connection: Cable 2 m
- Terminal Type: Cable 2 m
- Series: PSE



2024445 Block

RS PRO BACKGROUND SUPPRESSION PHOTOELECTRIC SENSOR, BLOCK

Pack size: **1 x EA**

- Sensor Style: Block
- Detection Type: Background Suppression
- Detection Range: 350 mm
- Output Type: PNP NO/NC
- Electrical Connection: M8 Connector
- Terminal Type: M8 Connector
- Series: PSE



2024451 Block

RS PRO POLARISED RETRO REFLECTION PHOTOELECTRIC

Pack size: **1 x EA**

- Sensor Style: Block
- Detection Type: Polarised Retro Reflection
- Detection Range: 3 m
- Output Type: NPN NO/NC
- Electrical Connection: Cable 2 m
- Terminal Type: Cable 2 m
- Series: PSR



2024457 Block

RS PRO THROUGH BEAM EMITTER PHOTOELECTRIC SENSOR, BLOCK

Pack size: **1 x EA**

- Sensor Style: Block
- Detection Type: Through Beam Emitter
- Detection Range: 20 m
- Electrical Connection: Cable 2 m
- Terminal Type: Cable 2 m
- Series: PSR



2024461 Block

RS PRO THROUGH BEAM EMITTER PHOTOELECTRIC SENSOR, BLOCK

Pack size: **1 x EA**

- Sensor Style: Block
- Detection Type: Through Beam Emitter
- Detection Range: 20 m
- Electrical Connection: M12 Connector
- Terminal Type: M12 Connector
- Series: PSR



2024462 Block

RS PRO THROUGH BEAM RECEIVER PHOTOELECTRIC SENSOR, BLOCK

Pack size: **1 x EA**

- Sensor Style: Block
- Detection Type: Through Beam Receiver
- Detection Range: 20 m
- Output Type: NPN NO/NC
- Electrical Connection: Cable 2 m
- Terminal Type: Cable 2 m
- Series: PSR



2024463 Block

RS PRO THROUGH BEAM RECEIVER PHOTOELECTRIC SENSOR, BLOCK

Pack size: **1 x EA**

- Sensor Style: Block
- Detection Type: Through Beam Receiver
- Detection Range: 20 m
- Output Type: NPN NO/NC
- Electrical Connection: M12 Connector
- Terminal Type: M12 Connector
- Series: PSR



2024464 Block

RS PRO THROUGH BEAM RECEIVER PHOTOELECTRIC SENSOR, BLOCK

Pack size: **1 x EA**

- Sensor Style: Block
- Detection Type: Through Beam Receiver
- Detection Range: 20 m
- Output Type: PNP NO/NC
- Electrical Connection: Cable 2 m
- Terminal Type: Cable 2 m
- Series: PSR



2024465 Block

RS PRO THROUGH BEAM RECEIVER PHOTOELECTRIC SENSOR, BLOCK

Pack size: **1 x EA**

- Sensor Style: Block
- Detection Type: Through Beam Receiver
- Detection Range: 20 m
- Output Type: PNP NO/NC
- Electrical Connection: M12 Connector
- Terminal Type: M12 Connector
- Series: PSR



2024466 Block

RS PRO DIFFUSE PHOTOELECTRIC SENSOR, BLOCK SENSOR, 2 M

Pack size: **1 x EA**

- Sensor Style: Block
- Detection Type: Diffuse
- Detection Range: 2 m
- Output Type: PNP/NPN
- Electrical Connection: Cable 2 m
- Terminal Type: Cable 2 m
- Series: PTE



2024472 Block

RS PRO DIFFUSE PHOTOELECTRIC SENSOR, BLOCK SENSOR, 2 M

Pack size: **1 x EA**

- Sensor Style: Block
- Detection Type: Diffuse
- Detection Range: 2 m
- Output Type: Relay NO/NC
- Electrical Connection: Cable 2 m
- Terminal Type: Cable 2 m
- Series: PTE



2024475 Block

RS PRO POLARISED RETRO REFLECTION PHOTOELECTRIC

Pack size: **1 x EA**

- Sensor Style: Block
- Detection Type: Polarised Retro Reflection
- Detection Range: 5 m
- Output Type: Relay NO/NC
- Electrical Connection: Cable 2 m
- Terminal Type: Cable 2 m
- Series: PTE



2024479 Block

RS PRO THROUGH BEAM EMITTER PHOTOELECTRIC SENSOR, BLOCK

Pack size: **1 x EA**

- Sensor Style: Block
- Detection Type: Through Beam Emitter
- Detection Range: 60 m
- Output Type: Relay
- Electrical Connection: Cable 2 m
- Terminal Type: Cable 2 m
- Series: PTE



2024482 Block

RS PRO THROUGH BEAM RECEIVER PHOTOELECTRIC SENSOR, BLOCK

Pack size: **1 x EA**

- Sensor Style: Block
- Detection Type: Through Beam Receiver
- Detection Range: 60 m
- Output Type: Relay NO/NC
- Electrical Connection: Cable 2 m
- Terminal Type: Cable 2 m
- Series: PTE



2024483 Block

RS PRO DIFFUSE PHOTOELECTRIC SENSOR, BLOCK SENSOR, 0 → 2 M

Pack size: **1 x EA**

- Sensor Style: Block
- Detection Type: Diffuse
- Detection Range: 0 → 2 m
- Output Type: NPN NO/NC
- Electrical Connection: Terminal Block
- Terminal Type: Terminal
- Light Source: Infrared LED
- Maximum Operating Temperature: +55 °C



2025448 Block

RS PRO DIFFUSE PHOTOELECTRIC SENSOR, BLOCK SENSOR, 0 → 2 M

Pack size: **1 x EA**

- Sensor Style: Block
- Detection Type: Diffuse
- Detection Range: 0 → 2 m
- Output Type: PNP NO/NC
- Electrical Connection: Terminal Block
- Terminal Type: Terminal
- Light Source: Infrared LED
- IP Rating: IP67



2025450 Block

RS PRO DIFFUSE PHOTOELECTRIC SENSOR, BLOCK SENSOR, 0 → 2 M

Pack size: **1 x EA**

- Sensor Style: Block
- Detection Type: Diffuse
- Detection Range: 0 → 2 m
- Output Type: Relay NO/NC
- Electrical Connection: Terminal Block
- Terminal Type: Terminal
- Light Source: Infrared LED
- IP Rating: IP67



2025451 Block

RS PRO DIFFUSE PHOTOELECTRIC SENSOR, BLOCK SENSOR, 0 → 800

Pack size: **1 x EA**

- Sensor Style: Block
- Detection Type: Diffuse
- Detection Range: 0 → 800 mm
- Output Type: Relay NO/NC
- Electrical Connection: Terminal Block
- Terminal Type: Terminal
- IP Rating: IP67
- Maximum Operating Temperature: +55 °C



2025452 Block

RS PRO RETROREFLECTIVE PHOTOELECTRIC SENSOR, BLOCK

Pack size: **1 x EA**

- Sensor Style: Block
- Detection Type: Retroreflective
- Detection Range: 5 m
- Output Type: Relay NO/NC
- Electrical Connection: Terminal Block
- Maximum AC Voltage: 240 V
- Maximum DC Voltage: 240 V
- Terminal Type: Terminal



2025456 Block

RS PRO POLARISED RETRO REFLECTION PHOTOELECTRIC

Pack size: **1 x EA**

- Sensor Style: Block
- Detection Type: Polarised Retro Reflection
- Detection Range: 12 m
- Output Type: NPN NO/NC
- Electrical Connection: Terminal Block
- Maximum DC Voltage: 30 V
- Terminal Type: Terminal
- Light Source: Red LED



2025457 Block

RS PRO THROUGH BEAM PHOTOELECTRIC SENSOR, BLOCK

Pack size: **1 x EA**

- Sensor Style: Block
- Detection Type: Through Beam
- Detection Range: 30 m
- Output Type: Relay
- Electrical Connection: Terminal Block
- Maximum AC Voltage: 240 V
- Maximum DC Voltage: 240 V
- Terminal Type: Terminal



2025460 Block

RS PRO THROUGH BEAM PHOTOELECTRIC SENSOR, BLOCK

Pack size: **1 x EA**

- Sensor Style: Block
- Detection Type: Through Beam
- Detection Range: 30 m
- Output Type: Relay NO/NC
- Electrical Connection: Terminal Block
- Maximum AC Voltage: 240 V
- Maximum DC Voltage: 240 V
- Terminal Type: Terminal



2025462 Block

RS PRO DIFFUSE PHOTOELECTRIC SENSOR, BARREL SENSOR, 150 MM

Pack size: **1 x EA**

- Sensor Style: Barrel
- Detection Type: Diffuse
- Detection Range: 150 mm
- Output Type: NPN NO
- Electrical Connection: Cable 2 m
- Maximum DC Voltage: 30 V
- Terminal Type: Cable 2 m
- Light Source: Yellow LED



2043961 Barrel

RS PRO DIFFUSE PHOTOELECTRIC SENSOR, BARREL SENSOR, 150 MM

Pack size: **1 x EA**

- Sensor Style: Barrel
- Detection Type: Diffuse
- Detection Range: 150 mm
- Output Type: NPN NO
- Electrical Connection: M12 Connector
- Maximum DC Voltage: 30 V
- Terminal Type: M12 Connector
- Light Source: Yellow LED



2043963 Barrel

RS PRO DIFFUSE PHOTOELECTRIC SENSOR, BARREL SENSOR, 150 MM

Pack size: **1 x EA**

- Sensor Style: Barrel
- Detection Type: Diffuse
- Detection Range: 150 mm
- Output Type: PNP NO
- Electrical Connection: Cable 2 m
- Maximum DC Voltage: 30 V
- Terminal Type: Cable 2 m
- Light Source: Yellow LED



2043962 Barrel

RS PRO DIFFUSE PHOTOELECTRIC SENSOR, BARREL SENSOR, 150 MM

Pack size: **1 x EA**

- Sensor Style: Barrel
- Detection Type: Diffuse
- Detection Range: 150 mm
- Output Type: PNP NO
- Electrical Connection: M12 Connector
- Maximum DC Voltage: 30 V
- Terminal Type: M12 Connector
- Light Source: Yellow LED



2043965 Barrel

RS PRO DIFFUSE PHOTOELECTRIC SENSOR, BARREL SENSOR, 150 MM

Pack size: **1 x EA**

- Sensor Style: Barrel
- Detection Type: Diffuse
- Detection Range: 150 mm
- Output Type: PNP NO
- Electrical Connection: Cable 2 m
- Maximum DC Voltage: 30 V
- Terminal Type: Cable 2 m
- Light Source: Yellow LED



2043967 Barrel

RS PRO DIFFUSE PHOTOELECTRIC SENSOR, BARREL SENSOR, 400 MM

Pack size: **1 x EA**

- Sensor Style: Barrel
- Detection Type: Diffuse
- Detection Range: 400 mm
- Output Type: NPN NO/NC
- Electrical Connection: Cable 2 m
- Maximum DC Voltage: 30 V
- Terminal Type: Cable 2 m
- Light Source: Yellow LED



2043968 Barrel

RS PRO DIFFUSE PHOTOELECTRIC SENSOR, BARREL SENSOR, 400 MM

Pack size: **1 x EA**

- Sensor Style: Barrel
- Detection Type: Diffuse
- Detection Range: 400 mm
- Output Type: PNP NO/NC
- Electrical Connection: Cable 2 m
- Maximum DC Voltage: 30 V
- Terminal Type: Cable 2 m
- Light Source: Yellow LED



2043969 Barrel

RS PRO DIFFUSE PHOTOELECTRIC SENSOR, BARREL SENSOR, 400 MM

Pack size: **1 x EA**

- Sensor Style: Barrel
- Detection Type: Diffuse
- Detection Range: 400 mm
- Output Type: NPN NO/NC
- Electrical Connection: M12 Connector
- Maximum DC Voltage: 30 V
- Terminal Type: M12 Connector
- Light Source: Yellow LED



2043970 Barrel

RS PRO DIFFUSE PHOTOELECTRIC SENSOR, BARREL SENSOR, 400 MM

Pack size: **1 x EA**

- Sensor Style: Barrel
- Detection Type: Diffuse
- Detection Range: 400 mm
- Output Type: PNP NO/NC
- Electrical Connection: M12 Connector
- Maximum DC Voltage: 30 V
- Terminal Type: M12 Connector
- Light Source: Yellow LED



2043971 Barrel

RS PRO DIFFUSE PHOTOELECTRIC SENSOR, BARREL SENSOR, 400 MM

Pack size: **1 x EA**

- Sensor Style: Barrel
- Detection Type: Diffuse
- Detection Range: 400 mm
- Output Type: NPN NO/NC
- Electrical Connection: Cable 2 m
- Maximum DC Voltage: 30 V
- Terminal Type: Cable 2 m
- Light Source: Yellow LED



2043972 Barrel

RS PRO DIFFUSE PHOTOELECTRIC SENSOR, BARREL SENSOR, 400 MM

Pack size: **1 x EA**

- Sensor Style: Barrel
- Detection Type: Diffuse
- Detection Range: 400 mm
- Output Type: PNP NO/NC
- Electrical Connection: Cable 2 m
- Maximum DC Voltage: 30 V
- Terminal Type: Cable 2 m
- Light Source: Yellow LED



2043973 Barrel

RS PRO THROUGH BEAM PHOTOELECTRIC SENSOR, BARREL

Pack size: **1 x EA**

- Sensor Style: Barrel
- Detection Type: Through Beam
- Detection Range: 20 m
- Output Type: PNP NO/NC
- Electrical Connection: Cable 2 m
- Maximum DC Voltage: 30 V
- Terminal Type: Cable 2 m
- Light Source: LED



2043999 Barrel

RS PRO THROUGH BEAM PHOTOELECTRIC SENSOR, BARREL

Pack size: **1 x EA**

- Sensor Style: Barrel
- Detection Type: Through Beam
- Detection Range: 5 m
- Output Type: NPN NO
- Electrical Connection: Cable 2 m
- Maximum DC Voltage: 30 V
- Terminal Type: Cable 2 m
- Light Source: LED



2043990 Barrel

RS PRO THROUGH BEAM PHOTOELECTRIC SENSOR, BARREL

Pack size: **1 x EA**

- Sensor Style: Barrel
- Detection Type: Through Beam
- Detection Range: 10 m
- Output Type: NPN NO/NC
- Electrical Connection: Cable 2 m
- Maximum DC Voltage: 30 V
- Terminal Type: Cable 2 m
- Light Source: LED



2044001 Barrel

RS PRO THROUGH BEAM (TRANSMITTER) PHOTOELECTRIC

Pack size: **1 x EA**

- Sensor Style: Barrel
- Detection Type: Through Beam (transmitter)
- Detection Range: 10 m
- Electrical Connection: Cable 2 m
- Maximum DC Voltage: 30 V
- Terminal Type: Cable 2 m
- Light Source: LED
- IP Rating: IP67



2044000 Barrel

RS PRO THROUGH BEAM PHOTOELECTRIC SENSOR, BARREL

Pack size: **1 x EA**

- Sensor Style: Barrel
- Detection Type: Through Beam
- Detection Range: 10 m
- Output Type: PNP NO/NC
- Electrical Connection: Cable 2 m
- Maximum DC Voltage: 30 V
- Terminal Type: Cable 2 m
- Light Source: LED



2044003 Barrel

RS PRO THROUGH BEAM PHOTOELECTRIC SENSOR, BARREL

Pack size: **1 x EA**

- Sensor Style: Barrel
- Detection Type: Through Beam
- Detection Range: 20 m
- Output Type: NPN NO/NC
- Electrical Connection: Cable 2 m
- Maximum DC Voltage: 30 V
- Terminal Type: Cable 2 m
- Light Source: LED



2044004 Barrel

RS PRO THROUGH BEAM PHOTOELECTRIC SENSOR, BARREL

Pack size: **1 x EA**

- Sensor Style: Barrel
- Detection Type: Through Beam
- Detection Range: 20 m
- Output Type: PNP NO/NC
- Electrical Connection: Cable 2 m
- Maximum DC Voltage: 30 V
- Terminal Type: Cable 2 m
- Light Source: LED



2044006 Barrel

RS PRO BACKGROUND SUPPRESSION PHOTOELECTRIC SENSOR, BARREL

Pack size: **1 x EA**

- Sensor Style: Barrel
- Detection Type: Background Suppression
- Detection Range: 100 mm
- Output Type: NPN NO/NC
- Electrical Connection: Cable 2 m
- Maximum DC Voltage: 30 V
- Terminal Type: Cable 2 m
- Light Source: LED



2044014 Barrel

RS PRO POLARISED RETRO REFLECTION PHOTOELECTRIC

Pack size: **1 x EA**

- Sensor Style: Barrel
- Detection Type: Polarised Retro Reflection
- Detection Range: 3 m
- Output Type: NPN NO/NC
- Electrical Connection: Cable 2 m
- Maximum DC Voltage: 30 V
- Terminal Type: Cable 2 m
- Light Source: LED



2044017 Barrel

SENSOR, M12, RETRO SCAN, PNP, N/O

Pack size: **1 x EA**

- Sensor Style: Barrel
- Detection Type: Retroreflective
- Detection Range: 2 m
- Output Type: PNP
- Electrical Connection: M12 Connector
- Maximum DC Voltage: 30 V
- Light Source: LED
- IP Rating: IP67



4405623 Barrel

RS PRO DIFFUSE PHOTOELECTRIC SENSOR, BARREL SENSOR, 100 MM

Pack size: **1 x EA**

- Sensor Style: Barrel
- Detection Type: Diffuse
- Detection Range: 100 mm
- Output Type: PNP
- Electrical Connection: M12 Connector
- Maximum DC Voltage: 30 V
- Light Source: Infrared
- IP Rating: IP67



4405639 Barrel

RS PRO BACKGROUND SUPPRESSION PHOTOELECTRIC SENSOR, BARREL

Pack size: **1 x EA**

- Sensor Style: Barrel
- Detection Type: Background Suppression
- Detection Range: 1 → 140 mm
- Output Type: NPN
- Electrical Connection: 4-Pin M12 Connector
- Maximum DC Voltage: 30 V
- Light Source: LED
- IP Rating: IP67



7295090 Barrel

RS PRO RETROREFLECTIVE PHOTOELECTRIC SENSOR, BARREL

Pack size: **1 x EA**

- Sensor Style: Barrel
- Detection Type: Retro-Reflective
- Detection Range: 0.05 → 7 m
- Output Type: NPN
- Electrical Connection: 4-Pin M12 Connector
- Maximum DC Voltage: 30 V
- Light Source: LED
- IP Rating: IP67



7295101 Barrel

RS PRO BACKGROUND SUPPRESSION PHOTOELECTRIC SENSOR, BARREL

Pack size: **1 x EA**

- Sensor Style: Barrel
- Detection Type: Background Suppression
- Detection Range: 1 → 140 mm
- Output Type: PNP
- Electrical Connection: 4-Pin M12 Connector
- Maximum DC Voltage: 30 V
- Light Source: LED
- IP Rating: IP67



7295104 Barrel

RS PRO BACKGROUND SUPPRESSION PHOTOELECTRIC SENSOR, BARREL

Pack size: **1 x EA**

- Sensor Style: Barrel
- Detection Type: Background Suppression
- Detection Range: 1 → 140 mm
- Output Type: PNP
- Electrical Connection: Cable
- Maximum DC Voltage: 30 V
- Light Source: LED
- IP Rating: IP67



7295107 Barrel

RS PRO RETROREFLECTIVE PHOTOELECTRIC SENSOR, BARREL

Pack size: **1 x EA**

- Sensor Style: Barrel
- Detection Type: Retroreflective
- Detection Range: 0.05 → 7 m
- Output Type: NPN
- Electrical Connection: 4-Wire Cable 2m
- Maximum DC Voltage: 30 V
- Light Source: LED
- IP Rating: IP67



7295110 Barrel

RS PRO RETROREFLECTIVE PHOTOELECTRIC SENSOR, BARREL

Pack size: **1 x EA**

- Sensor Style: Barrel
- Detection Type: Retro-Reflective
- Detection Range: 0.05 → 7 m
- Output Type: PNP
- Electrical Connection: 4-Pin M12 Connector
- Maximum DC Voltage: 30 V
- Light Source: LED
- IP Rating: IP67



7295113 Barrel

RS PRO RETROREFLECTIVE PHOTOELECTRIC SENSOR, BARREL

Pack size: **1 x EA**

- Sensor Style: Barrel
- Detection Type: Retro-Reflective
- Detection Range: 0.05 → 7 m
- Output Type: PNP
- Electrical Connection: Cable
- Maximum DC Voltage: 30 V
- Light Source: LED
- IP Rating: IP67



7295117 Barrel

RS PRO THROUGH BEAM PHOTOELECTRIC SENSOR, BARREL

Pack size: **1 x EA**

- Sensor Style: Barrel
- Detection Type: Through Beam (Emitter)
- Detection Range: 28 m
- Output Type: PNP
- Electrical Connection: 4-Pin M12 Connector
- Maximum DC Voltage: 30 V
- Light Source: LED
- IP Rating: IP67



7295123 Barrel

RS PRO DIFFUSE PHOTOELECTRIC SENSOR, BLOCK SENSOR, 40 MM → 1

Pack size: **1 x EA**

- Sensor Style: Block
- Detection Type: Diffuse
- Detection Range: 40 → 1000 mm
- Output Type: NPN
- Electrical Connection: 4-Pin M12 Connector
- Maximum DC Voltage: 30 V
- Light Source: LED
- IP Rating: IP67



7295135 Block

RS PRO DIFFUSE PHOTOELECTRIC SENSOR, BLOCK SENSOR, 40 MM → 1

Pack size: **1 x EA**

- Sensor Style: Block
- Detection Type: Diffuse
- Detection Range: 40 → 1000 mm
- Output Type: PNP
- Electrical Connection: Cable
- Maximum DC Voltage: 30 V
- Light Source: LED
- IP Rating: IP67



7295139 Block

RS PRO DIFFUSE PHOTOELECTRIC SENSOR, BLOCK SENSOR, 40 MM → 1

Pack size: **1 x EA**

- Sensor Style: Block
- Detection Type: Diffuse
- Detection Range: 40 → 1000 mm
- Output Type: PNP
- Electrical Connection: Cable
- Maximum DC Voltage: 30 V
- Light Source: LED
- IP Rating: IP67



7295141 Block

RS PRO DIFFUSE PHOTOELECTRIC SENSOR, BLOCK SENSOR, 40 MM → 1

Pack size: **1 x EA**

- Sensor Style: Block
- Detection Type: Diffuse
- Detection Range: 40 → 1000 mm
- Output Type: PNP
- Electrical Connection: 4-Pin M12 Connector
- Maximum DC Voltage: 30 V
- Light Source: LED
- IP Rating: IP67



7295148 Block

RS PRO RETROREFLECTIVE PHOTOELECTRIC SENSOR, BLOCK

Pack size: **1 x EA**

- Sensor Style: Block
- Detection Type: Retroreflective
- Detection Range: 0.15 → 10 m
- Output Type: PNP
- Electrical Connection: 4-Wire Cable 2m
- Maximum DC Voltage: 30 V
- Light Source: LED
- IP Rating: IP67



7295151 Block

RS PRO RETROREFLECTIVE PHOTOELECTRIC SENSOR, BLOCK

Pack size: **1 x EA**

- Sensor Style: Block
- Detection Type: Retroreflective
- Detection Range: 0.15 → 10 m
- Output Type: PNP
- Electrical Connection: 4-Pin M12 Connector
- Maximum DC Voltage: 30 V
- Light Source: LED
- IP Rating: IP67



7295157 Block

RS PRO BACKGROUND SUPPRESSION PHOTOELECTRIC SENSOR, BLOCK

Pack size: **1 x EA**

- Sensor Style: Block
- Detection Type: Background Suppression
- Detection Range: 5 → 250 mm
- Output Type: PNP
- Electrical Connection: 4-Pin M8 Connector
- Maximum DC Voltage: 24 V
- Light Source: LED
- IP Rating: IP67



7295185 Block

RS PRO RETROREFLECTIVE PHOTOELECTRIC SENSOR, BLOCK

Pack size: **1 x EA**

- Sensor Style: Block
- Detection Type: Retroreflective
- Detection Range: 7.2 m
- Output Type: NPN
- Electrical Connection: Cable
- Maximum DC Voltage: 24 V
- Light Source: LED
- IP Rating: IP67



7295191 Block

RS PRO RETROREFLECTIVE PHOTOELECTRIC SENSOR, BLOCK

Pack size: **1 x EA**

- Sensor Style: Block
- Detection Type: Retro-Reflective
- Detection Range: 7.2 m
- Output Type: PNP
- Electrical Connection: 4-Pin M8 Connector
- Maximum DC Voltage: 24 V
- Light Source: LED
- IP Rating: IP67



7295195 Block

RS PRO RETROREFLECTIVE PHOTOELECTRIC SENSOR, BLOCK

Pack size: **1 x EA**

- Sensor Style: Block
- Detection Type: Retroreflective
- Detection Range: 7.2 m
- Output Type: NPN
- Electrical Connection: 4-Pin M8 Connector
- Maximum DC Voltage: 24 V
- Light Source: LED
- IP Rating: IP67



7295198 Block

RS PRO RETROREFLECTIVE PHOTOELECTRIC SENSOR, BLOCK

Pack size: **1 x EA**

- Sensor Style: Block
- Detection Type: Retroreflective
- Detection Range: 7.2 m
- Output Type: PNP
- Electrical Connection: 3-Wire Cable 2m
- Maximum DC Voltage: 24 V
- Light Source: LED
- IP Rating: IP67



7295205 Block

RS PRO THROUGH BEAM PHOTOELECTRIC SENSOR, FORK

Pack size: **1 x EA**

- Sensor Style: Fork
- Detection Type: Through Beam
- Detection Range: 30 mm
- Output Type: NPN NO/NC
- Electrical Connection: 4 Wire Cable 2 m
- Maximum DC Voltage: 30 V
- Terminal Type: Pre-Wired
- Light Source: Infrared



9033927 Fork

RS PRO THROUGH BEAM PHOTOELECTRIC SENSOR, FORK

Pack size: **1 x EA**

- Sensor Style: Fork
- Detection Type: Through Beam
- Detection Range: 30 mm
- Output Type: PNP NO
- Electrical Connection: 4 Wire Cable 2 m
- Maximum DC Voltage: 30 V
- Terminal Type: Pre-Wired
- Light Source: Infrared



9033933 Fork

RS PRO THROUGH BEAM PHOTOELECTRIC SENSOR, FORK

Pack size: **1 x EA**

- Sensor Style: Fork
- Detection Type: Through Beam
- Detection Range: 30 mm
- Output Type: PNP NO
- Electrical Connection: 4 Wire Cable 2 m
- Maximum DC Voltage: 30 V
- Terminal Type: Pre-Wired
- Light Source: Infrared



9033936 Fork

RS PRO THROUGH BEAM PHOTOELECTRIC SENSOR, FORK

Pack size: **1 x EA**

- Sensor Style: Fork
- Detection Type: Through Beam
- Detection Range: 30 mm
- Output Type: PNP NO
- Electrical Connection: 4 Wire Cable 2 m
- Maximum DC Voltage: 30 V
- Terminal Type: Pre-Wired
- Light Source: Infrared



9033939 Fork

RS PRO THROUGH BEAM PHOTOELECTRIC SENSOR, FORK

Pack size: **1 x EA**

- Sensor Style: Fork
- Detection Type: Through Beam
- Detection Range: 7 mm
- Output Type: PNP
- Electrical Connection: Cable
- Maximum DC Voltage: 30 V
- Terminal Type: Pre-Wired
- Light Source: Infrared



9033942 Fork

RS PRO INDUCTIVE BLOCK-STYLE PROXIMITY SENSOR, 15 MM

Pack size: **1 x EA**

- Sensor Technology: Inductive
- Body Style: Block
- Output Type: PNP-NO
- Detection Range: 15 mm
- Terminal Type: M12 - 4 Pin
- IP Rating: IP68
- Supply Voltage: 10 → 30 V dc
- Length: 46 mm



208128 Inductive

RS PRO INDUCTIVE BLOCK-STYLE PROXIMITY SENSOR, 75 MM

Pack size: **1 x EA**

- Sensor Technology: Inductive
- Body Style: Block
- Output Type: PNP-NO
- Detection Range: 75 mm
- Terminal Type: M20 Gland
- IP Rating: IP67
- Supply Voltage: 10 → 30 V dc
- Length: 80 mm



208134 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M12 X 1, 8 MM

Pack size: **1 x EA**

- Sensor Technology: Inductive
- Body Style: Barrel
- Thread Size: M12 x 1
- Output Type: PNP-NO
- Detection Range: 8 mm
- Terminal Type: Cable
- Supply Voltage: 10 → 30 V dc
- IP Rating: IP68



208156 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M8 X 1, 4 MM

Pack size: **1 x EA**

- Sensor Technology: Inductive
- Body Style: Barrel
- Thread Size: M8 x 1
- Output Type: PNP-NO
- Detection Range: 4 mm
- Terminal Type: Cable
- IP Rating: IP68
- Supply Voltage: 10 → 30 V dc



208178 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M12 X 1, 3 MM

Pack size: **1 x EA**

- Sensor Technology: Inductive
- Body Style: Barrel
- Thread Size: M12 x 1
- Output Type: PNP-NO
- Detection Range: 3 mm
- Terminal Type: Cable
- IP Rating: IP68
- Supply Voltage: 10 → 30 V dc



208184 Inductive

RS PRO INDUCTIVE BLOCK-STYLE PROXIMITY SENSOR, 35 MM

Pack size: **1 x EA**

- Sensor Technology: Inductive
- Body Style: Block
- Output Type: PNP-NO
- Detection Range: 35 mm
- Terminal Type: M12 - 4 Pin
- IP Rating: IP68
- Supply Voltage: 10 → 30 V dc
- Length: 65 mm



208190 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M18 X 1, 5 MM

Pack size: **1 x EA**

- Sensor Technology: Inductive
- Body Style: Barrel
- Thread Size: M18 x 1
- Output Type: PNP-NO
- Detection Range: 5 mm
- Terminal Type: M12 - 4 Pin
- Supply Voltage: 10 → 30 V dc
- IP Rating: IP68



208213 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M12 X 1, 8 MM

Pack size: **1 x EA**

- Sensor Technology: Inductive
- Body Style: Barrel
- Thread Size: M12 x 1
- Output Type: PNP-NO
- Detection Range: 8 mm
- Terminal Type: M12 - 4 Pin
- IP Rating: IP68
- Supply Voltage: 10 → 30 V dc



208257 Inductive

RS PRO INDUCTIVE BLOCK-STYLE PROXIMITY SENSOR, 25 MM

Pack size: **1 x EA**

- Sensor Technology: Inductive
- Body Style: Block
- Output Type: PNP-NO
- Detection Range: 25 mm
- Terminal Type: M20 Gland
- IP Rating: IP68
- Supply Voltage: 10 → 30 V dc
- Length: 114 mm



208263 Inductive

RS PRO INDUCTIVE BLOCK-STYLE PROXIMITY SENSOR, 40 MM

Pack size: **1 x EA**

- Sensor Technology: Inductive
- Body Style: Block
- Output Type: PNP-NO
- Detection Range: 40 mm
- Terminal Type: M20 Gland
- IP Rating: IP68
- Supply Voltage: 10 → 30 V dc
- Length: 114 mm



208279 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M30 X 1.5, 20

Pack size: **1 x EA**

- Sensor Technology: Inductive
- Body Style: Barrel
- Thread Size: M30 x 1.5
- Output Type: PNP-NO
- Detection Range: 20 mm
- Terminal Type: Cable
- IP Rating: IP68
- Supply Voltage: 10 → 30 V dc



208285 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M30 X 1.5, 10

Pack size: **1 x EA**

- Sensor Technology: Inductive
- Body Style: Barrel
- Thread Size: M30 x 1.5
- Output Type: PNP-NO
- Detection Range: 10 mm
- Terminal Type: Cable
- IP Rating: IP68
- Supply Voltage: 10 → 30 V dc



208314 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M8 X 1, 1.5 MM

Pack size: **1 x EA**

- Sensor Technology: Inductive
- Body Style: Barrel
- Thread Size: M8 x 1
- Output Type: PNP-NO
- Detection Range: 1.5 mm
- Terminal Type: Cable
- IP Rating: IP68
- Supply Voltage: 10 → 30 V dc



208320 Inductive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M12 X 1, 4 MM

Pack size: **1 x EA**

- Sensor Technology: Capacitive
- Body Style: Barrel
- Thread Size: M12 x 1
- Output Type: PNP
- Detection Range: 4 mm
- Terminal Type: Cable
- IP Rating: IP67
- Supply Voltage: 10 → 30 V dc



1466754 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M12 X 1, 2 MM

Pack size: **1 x EA**

- Sensor Technology: Capacitive
- Body Style: Barrel
- Thread Size: M12 x 1
- Output Type: PNP
- Detection Range: 2 mm
- Terminal Type: 4-Pin M12 Connector
- Supply Voltage: 10 → 30 V dc
- IP Rating: IP67



1466755 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M12 X 1, 4 MM

Pack size: **1 x EA**

- Sensor Technology: Capacitive
- Body Style: Barrel
- Thread Size: M12 x 1
- Output Type: PNP
- Detection Range: 4 mm
- Terminal Type: 4-Pin M12 Connector
- IP Rating: IP67
- Supply Voltage: 10 → 30 V dc



1466756 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M18 X 1, 8 MM

Pack size: **1 x EA**

- Sensor Technology: Capacitive
- Body Style: Barrel
- Thread Size: M18 x 1
- Output Type: PNP
- Detection Range: 8 mm
- Terminal Type: Cable
- IP Rating: IP67
- Supply Voltage: 10 → 30 V dc



1466757 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M18 X 1, 5 MM

Pack size: **1 x EA**

- Sensor Technology: Capacitive
- Body Style: Barrel
- Thread Size: M18 x 1
- Output Type: PNP
- Detection Range: 5 mm
- Terminal Type: 4-Pin M12 Connector
- IP Rating: IP67
- Supply Voltage: 10 → 30 V dc



1466758 Capacitive

RS PRO CAPACITIVE BLOCK-STYLE PROXIMITY SENSOR, 10 MM

Pack size: **1 x EA**

- Sensor Technology: Capacitive
- Body Style: Block
- Output Type: PNP
- Detection Range: 10 mm
- Terminal Type: Cable
- Supply Voltage: 10 → 30 V dc
- IP Rating: IP67
- Length: 50 mm



1466759 Capacitive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M8 X 1, 1.5 MM

Pack size: **1 x EA**

- Sensor Technology: Inductive
- Body Style: Barrel
- Thread Size: M8 x 1
- Output Type: PNP
- Detection Range: 1.5 mm
- Terminal Type: Cable
- IP Rating: IP67
- Supply Voltage: 10 → 30 V dc



1646091 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M8 X 1, 1.5 MM

Pack size: **1 x EA**

- Sensor Technology: Inductive
- Body Style: Barrel
- Thread Size: M8 x 1
- Output Type: PNP
- Detection Range: 1.5 mm
- Terminal Type: Cable
- Supply Voltage: 10 → 30 V dc
- IP Rating: IP67



1646092 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M8 X 1, 1.5 MM

Pack size: **1 x EA**

- Sensor Technology: Inductive
- Body Style: Barrel
- Thread Size: M8 x 1
- Output Type: NPN
- Detection Range: 1.5 mm
- Terminal Type: Cable
- Supply Voltage: 10 → 30 V dc
- IP Rating: IP67



1646093 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M8 X 1, 1.5 MM

Pack size: **1 x EA**

- Sensor Technology: Inductive
- Body Style: Barrel
- Thread Size: M8 x 1
- Output Type: NPN
- Detection Range: 1.5 mm
- Terminal Type: Cable
- Supply Voltage: 10 → 30 V dc
- IP Rating: IP67



1646094 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M8 X 1, 2.5 MM

Pack size: **1 x EA**

- Sensor Technology: Inductive
- Body Style: Barrel
- Thread Size: M8 x 1
- Output Type: PNP
- Detection Range: 2.5 mm
- Terminal Type: Cable
- Supply Voltage: 10 → 30 V dc
- IP Rating: IP67



1646095 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M8 X 1, 2.5 MM

Pack size: **1 x EA**

- Sensor Technology: Inductive
- Body Style: Barrel
- Thread Size: M8 x 1
- Output Type: NPN
- Detection Range: 2.5 mm
- Terminal Type: Cable
- Supply Voltage: 10 → 30 V dc
- IP Rating: IP67



1646098 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M8 X 1, 2.5 MM

Pack size: **1 x EA**

- Sensor Technology: Inductive
- Body Style: Barrel
- Thread Size: M8 x 1
- Output Type: PNP
- Detection Range: 2.5 mm
- Terminal Type: Cable
- Supply Voltage: 10 → 30 V dc
- IP Rating: IP67



1646096 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M8 X 1, 2.5 MM

Pack size: **1 x EA**

- Sensor Technology: Inductive
- Body Style: Barrel
- Thread Size: M8 x 1
- Output Type: NPN
- Detection Range: 2.5 mm
- Terminal Type: Cable
- Supply Voltage: 10 → 30 V dc
- IP Rating: IP67



1646097 Inductive

RS PRO CAPACITIVE BLOCK-STYLE PROXIMITY SENSOR, 5 MM

Pack size: **1 x EA**

- Sensor Technology: Capacitive
- Body Style: Block
- Output Type: PNP
- Detection Range: 5 mm
- Terminal Type: Cable
- IP Rating: IP67
- Supply Voltage: 10 → 30 V dc
- Length: 30 mm



1845570 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M12 X 1, 2 MM

Pack size: **1 x EA**

- Sensor Technology: Capacitive
- Body Style: Barrel
- Thread Size: M12 x 1
- Output Type: PNP
- Detection Range: 2 mm
- Terminal Type: 4-Pin M12 Connector
- Supply Voltage: 10 → 30 V dc
- IP Rating: IP67



1845585 Capacitive

RS PRO CAPACITIVE BLOCK-STYLE PROXIMITY SENSOR, PNP NORMALLY

Pack size: **1 x EA**

- Sensor Technology: Capacitive
- Body Style: Block
- Output Type: PNP Normally Open
- Terminal Type: 2 m PVC Cable
- IP Rating: IP67
- Supply Voltage: 10 → 30 V dc
- Length: 43 mm
- Width: 24 mm



1845574 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M18 X 1, 5 MM

Pack size: **1 x EA**

- Sensor Technology: Capacitive
- Body Style: Barrel
- Thread Size: M18 x 1
- Detection Range: 5 mm
- Terminal Type: Cable
- IP Rating: IP67
- Supply Voltage: 20 → 250 V ac
- Length: 70 mm



1845591 Capacitive

RS PRO CAPACITIVE BLOCK-STYLE PROXIMITY SENSOR, 10 MM

Pack size: **1 x EA**

- Sensor Technology: Capacitive
- Body Style: Block
- Output Type: NPN
- Detection Range: 10 mm
- Terminal Type: Cable
- IP Rating: IP67
- Supply Voltage: 10 → 30 V dc
- Length: 50 mm



1845577 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M18 X 1, 5 MM

Pack size: **1 x EA**

- Sensor Technology: Capacitive
- Body Style: Barrel
- Thread Size: M18 x 1
- Output Type: PNP
- Detection Range: 5 mm
- Terminal Type: Cable
- Supply Voltage: 10 → 30 V dc
- IP Rating: IP67



1845596 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M18 X 1, 8 MM

Pack size: **1 x EA**

- Sensor Technology: Capacitive
- Thread Size: M18 x 1
- Body Style: Barrel
- Detection Range: 8 mm
- Terminal Type: 4-Pin M12 Connector
- IP Rating: IP67
- Supply Voltage: 20 → 250 V ac
- Length: 91.5 mm



1845598 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M12 X 1, 4 MM

Pack size: **1 x EA**

- Sensor Technology: Capacitive
- Body Style: Barrel
- Thread Size: M12 x 1
- Output Type: NPN
- Detection Range: 4 mm
- Terminal Type: Cable
- Supply Voltage: 10 → 30 V dc
- IP Rating: IP67



1845586 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M18 X 1, 8 MM

Pack size: **1 x EA**

- Sensor Technology: Capacitive
- Body Style: Barrel
- Thread Size: M18 x 1
- Output Type: NPN
- Detection Range: 8 mm
- Terminal Type: 4-Pin M12 Connector
- Supply Voltage: 10 → 30 V dc
- IP Rating: IP67



1845600 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M18 X 1, 5 MM

Pack size: **1 x EA**

- Sensor Technology: Capacitive
- Body Style: Barrel
- Thread Size: M18 x 1
- Output Type: NPN Normally Open & Normally Closed
- Detection Range: 5 mm
- Terminal Type: Cable
- Supply Voltage: 10 → 30 V dc
- IP Rating: IP67



1845604 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M18 X 1, 5 MM

Pack size: **1 x EA**

- Sensor Technology: Capacitive
- Body Style: Barrel
- Thread Size: M18 x 1
- Output Type: PNP
- Detection Range: 5 mm
- Terminal Type: Cable
- Supply Voltage: 10 → 30 V dc
- IP Rating: IP67



1845606 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M18 X 1, 5 MM

Pack size: **1 x EA**

- Sensor Technology: Capacitive
- Body Style: Barrel
- Thread Size: M18 x 1
- Output Type: PNP
- Detection Range: 5 mm
- Terminal Type: 4-Pin M12 Connector
- Supply Voltage: 10 → 30 V dc
- IP Rating: IP67



1845607 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M18 X 1, 8 MM

Pack size: **1 x EA**

- Sensor Technology: Capacitive
- Body Style: Barrel
- Thread Size: M18 x 1
- Output Type: NPN
- Detection Range: 8 mm
- Terminal Type: Cable
- Supply Voltage: 10 → 30 V dc
- IP Rating: IP67



1845609 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M18 X 1, 8 MM

Pack size: **1 x EA**

- Sensor Technology: Capacitive
- Body Style: Barrel
- Thread Size: M18 x 1
- Output Type: PNP
- Detection Range: 8 mm
- Terminal Type: Cable
- Supply Voltage: 10 → 30 V dc
- IP Rating: IP67



1845611 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M18 X 1, 8 MM

Pack size: **1 x EA**

- Sensor Technology: Capacitive
- Body Style: Barrel
- Thread Size: M18 x 1
- Output Type: PNP
- Detection Range: 8 mm
- Terminal Type: 4-Pin M12 Connector
- Supply Voltage: 10 → 30 V dc
- IP Rating: IP67



1845612 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M30 X 1.5, 10

Pack size: **1 x EA**

- Sensor Technology: Capacitive
- Body Style: Barrel
- Thread Size: M30 x 1.5
- Output Type: PNP
- Detection Range: 10 mm
- Terminal Type: 4-Pin M12 Connector
- Supply Voltage: 10 → 30 V dc
- IP Rating: IP67



1845619 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M18 X 1, 5 MM

Pack size: **1 x EA**

- Sensor Technology: Capacitive
- Body Style: Barrel
- Thread Size: M18 x 1
- Output Type: NPN
- Detection Range: 5 mm
- Terminal Type: Cable
- Supply Voltage: 10 → 30 V dc
- IP Rating: IP67



1845593 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M30 X 1.5, 15

Pack size: **1 x EA**

- Sensor Technology: Capacitive
- Thread Size: M30 x 1.5
- Body Style: Barrel
- Output Type: NPN
- Detection Range: 15 mm
- Terminal Type: Cable
- IP Rating: IP67
- Supply Voltage: 10 → 30 V dc



1845622 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M30 X 1.5, 15

Pack size: **1 x EA**

- Sensor Technology: Capacitive
- Body Style: Barrel
- Thread Size: M30 x 1.5
- Output Type: NPN
- Detection Range: 15 mm
- Terminal Type: 4-Pin M12 Connector
- Supply Voltage: 10 → 30 V dc
- IP Rating: IP67



1845623 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M30 X 1.5, 15

Pack size: **1 x EA**

- Sensor Technology: Capacitive
- Body Style: Barrel
- Thread Size: M30 x 1.5
- Output Type: PNP
- Detection Range: 15 mm
- Terminal Type: 4-Pin M12 Connector
- Supply Voltage: 10 → 30 V dc
- IP Rating: IP67



1845626 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M30 X 1.5, 10

Pack size: **1 x EA**

- Sensor Technology: Capacitive
- Body Style: Barrel
- Thread Size: M30 x 1.5
- Output Type: NPN Normally Open & Normally Closed
- Detection Range: 10 mm
- Terminal Type: Cable
- IP Rating: IP67
- Supply Voltage: 10 → 30 V dc



1845629 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M30 X 1.5, 10

Pack size: **1 x EA**

- Sensor Technology: Capacitive
- Body Style: Barrel
- Thread Size: M30 x 1.5
- Output Type: PNP
- Detection Range: 10 mm
- Terminal Type: Cable
- Supply Voltage: 10 → 30 V dc
- IP Rating: IP67



1845632 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M30 X 1.5, 10

Pack size: **1 x EA**

- Sensor Technology: Capacitive
- Body Style: Barrel
- Thread Size: M30 x 1.5
- Detection Range: 10 mm
- Terminal Type: Cable
- IP Rating: IP67
- Supply Voltage: 20 → 250 V ac/dc
- Length: 62 mm



1845634 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M18 X 1, 8 MM

Pack size: **1 x EA**

- Sensor Technology: Capacitive
- Body Style: Barrel
- Thread Size: M18 x 1
- Output Type: NPN
- Detection Range: 8 mm
- Terminal Type: Cable
- Supply Voltage: 10 → 30 V dc
- IP Rating: IP67



1845599 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M30 X 1.5, 15

Pack size: **1 x EA**

- Sensor Technology: Capacitive
- Body Style: Barrel
- Thread Size: M30 x 1.5
- Output Type: NPN
- Detection Range: 15 mm
- Terminal Type: 4-Pin M12 Connector
- Supply Voltage: 10 → 30 V dc
- IP Rating: IP67



1845639 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M30 X 1.5, 15

Pack size: **1 x EA**

- Sensor Technology: Capacitive
- Body Style: Barrel
- Thread Size: M30 x 1.5
- Detection Range: 15 mm
- Terminal Type: 4-Pin M12 Connector
- IP Rating: IP67
- Supply Voltage: 20 → 250 V ac
- Length: 91 mm



1845621 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M30 X 1.5, 15

Pack size: **1 x EA**

- Sensor Technology: Capacitive
- Body Style: Barrel
- Thread Size: M30 x 1.5
- Output Type: PNP
- Detection Range: 15 mm
- Terminal Type: 4-Pin M12 Connector
- Supply Voltage: 10 → 30 V dc
- IP Rating: IP67



1845641 Capacitive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M5 X 0.5, 1.5

Pack size: **1 x EA**

- Sensor Technology: Inductive
- Body Style: Barrel
- Thread Size: M5 x 0.5
- Output Type: PNP
- Detection Range: 1.5 mm
- Terminal Type: 2 m, 3-wire, Cable
- IP Rating: IP67
- Supply Voltage: 10 → 30 V dc



2066129 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M8 X 1, 2 MM

Pack size: **1 x EA**

- Sensor Technology: Inductive
- Body Style: Barrel
- Thread Size: M8 x 1
- Output Type: PNP
- Detection Range: 2 mm
- Terminal Type: 3-Pin M8 Connector
- IP Rating: IP68
- Supply Voltage: 10 → 30 V dc



2066133 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M4 X 0.5, 0.6

Pack size: **1 x EA**

- Sensor Technology: Inductive
- Body Style: Barrel
- Thread Size: M4 x 0.5
- Output Type: PNP
- Detection Range: 0.6 mm
- Terminal Type: 2 m, 3-wire, Cable
- IP Rating: IP67
- Supply Voltage: 10 → 30 V dc



2066124 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M8 X 1, 2 MM

Pack size: **1 x EA**

- Sensor Technology: Inductive
- Body Style: Barrel
- Thread Size: M8 x 1
- Output Type: PNP
- Detection Range: 2 mm
- Terminal Type: 2 m, 3-wire, Cable
- IP Rating: IP68
- Supply Voltage: 10 → 30 V dc



2066135 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M8 X 1, 4 MM

Pack size: **1 x EA**

- Sensor Technology: Inductive
- Body Style: Barrel
- Thread Size: M8 x 1
- Output Type: PNP
- Detection Range: 4 mm
- Terminal Type: 2 m, 3-wire, Cable
- IP Rating: IP68
- Supply Voltage: 10 → 30 V dc



2066136 Inductive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M30 X 1.5, 15

Pack size: **1 x EA**

- Sensor Technology: Capacitive
- Body Style: Barrel
- Thread Size: M30 x 1.5
- Output Type: NPN
- Detection Range: 15 mm
- Terminal Type: Cable
- Supply Voltage: 10 → 30 V dc
- IP Rating: IP67



1845638 Capacitive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M12 X 1, 4 MM

Pack size: **1 x EA**

- Sensor Technology: Inductive
- Body Style: Barrel
- Thread Size: M12 x 1
- Output Type: PNP
- Detection Range: 4 mm
- Terminal Type: 2 m, 3-wire, Cable
- IP Rating: IP68
- Supply Voltage: 10 → 30 V dc



2066139 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M12 X 1, 4 MM

Pack size: **1 x EA**

- Sensor Technology: Inductive
- Body Style: Barrel
- Thread Size: M12 x 1
- Output Type: PNP
- Detection Range: 4 mm
- Terminal Type: 2 m, 3-wire, Cable
- IP Rating: IP68
- Supply Voltage: 10 → 30 V dc



2066140 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M18 X 1, 8 MM

Pack size: **1 x EA**

- Sensor Technology: Inductive
- Body Style: Barrel
- Thread Size: M18 x 1
- Output Type: PNP
- Detection Range: 8 mm
- Terminal Type: 4-Pin M12 Connector
- IP Rating: IP68
- Supply Voltage: 10 → 30 V dc



2066141 Inductive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M30 X 1.5, 15

Pack size: **1 x EA**

- Sensor Technology: Capacitive
- Body Style: Barrel
- Thread Size: M30 x 1.5
- Output Type: PNP
- Detection Range: 15 mm
- Terminal Type: Cable
- Supply Voltage: 10 → 30 V dc
- IP Rating: IP67



1845640 Capacitive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M12 X 1, 4 MM

Pack size: **1 x EA**

- Sensor Technology: Inductive
- Body Style: Barrel
- Thread Size: M12 x 1
- Output Type: PNP
- Detection Range: 4 mm
- Terminal Type: 4-Pin M12 Connector
- IP Rating: IP68
- Supply Voltage: 10 → 30 V dc



2066138 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M18 X 1, 8 MM

Pack size: **1 x EA**

- Sensor Technology: Inductive
- Body Style: Barrel
- Thread Size: M18 x 1
- Output Type: PNP
- Detection Range: 8 mm
- Terminal Type: 4-Pin M12 Connector
- IP Rating: IP68
- Supply Voltage: 10 → 30 V dc



2066142 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M18 X 1, 8 MM

Pack size: **1 x EA**

- Sensor Technology: Inductive
- Body Style: Barrel
- Thread Size: M18 x 1
- Output Type: PNP
- Detection Range: 8 mm
- Terminal Type: 2 m, 3-wire, Cable
- IP Rating: IP68
- Supply Voltage: 10 → 30 V dc



2066143 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M18 X 1, 8 MM

Pack size: **1 x EA**

- Sensor Technology: Inductive
- Body Style: Barrel
- Thread Size: M18 x 1
- Output Type: PNP
- Detection Range: 8 mm
- Terminal Type: 2 m, 3-wire, Cable
- IP Rating: IP68
- Supply Voltage: 10 → 30 V dc



2066144 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M30 X 1.5, 15

Pack size: **1 x EA**

- Sensor Technology: Inductive
- Body Style: Barrel
- Thread Size: M30 x 1.5
- Output Type: PNP
- Detection Range: 15 mm
- Terminal Type: 4-Pin M12 Connector
- IP Rating: IP68
- Supply Voltage: 10 → 30 V dc



2066146 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M30 X 1.5, 15

Pack size: **1 x EA**

- Sensor Technology: Inductive
- Body Style: Barrel
- Thread Size: M30 x 1.5
- Output Type: PNP
- Detection Range: 15 mm
- Terminal Type: 4-Pin M12 Connector
- IP Rating: IP68
- Supply Voltage: 10 → 30 V dc



2066145 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M8 X 1, 2 MM

Pack size: **1 x EA**

- Sensor Technology: Inductive
- Body Style: Barrel
- Thread Size: M8 x 1
- Output Type: PNP
- Detection Range: 2 mm
- Terminal Type: 4-Pin M12 Connector
- IP Rating: IP68
- Supply Voltage: 10 → 30 V dc



2066150 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M8 X 1, 2 MM

Pack size: **1 x EA**

- Sensor Technology: Inductive
- Body Style: Barrel
- Thread Size: M8 x 1
- Output Type: PNP
- Detection Range: 2 mm
- Terminal Type: 3-Pin M8 Connector
- IP Rating: IP68
- Supply Voltage: 10 → 30 V dc



2066151 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M30 X 1.5, 15

Pack size: **1 x EA**

- Sensor Technology: Inductive
- Body Style: Barrel
- Thread Size: M30 x 1.5
- Output Type: PNP
- Detection Range: 15 mm
- Terminal Type: 2 m, 3-wire, Cable
- IP Rating: IP68
- Supply Voltage: 10 → 30 V dc



2066148 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M30 X 1.5, 15

Pack size: **1 x EA**

- Sensor Technology: Inductive
- Body Style: Barrel
- Thread Size: M30 x 1.5
- Output Type: PNP
- Detection Range: 15 mm
- Terminal Type: 2 m, 3-wire, Cable
- IP Rating: IP68
- Supply Voltage: 10 → 30 V dc



2066149 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M8 X 1, 2 MM

Pack size: **1 x EA**

- Sensor Technology: Inductive
- Body Style: Barrel
- Thread Size: M8 x 1
- Output Type: PNP
- Detection Range: 2 mm
- Terminal Type: 2 m, 3-wire, Cable
- IP Rating: IP68
- Supply Voltage: 10 → 30 V dc



2066152 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M8 X 1, 2 MM

Pack size: **1 x EA**

- Sensor Technology: Inductive
- Body Style: Barrel
- Thread Size: M8 x 1
- Output Type: PNP
- Detection Range: 2 mm
- Terminal Type: 2 m, 3-wire, Cable
- IP Rating: IP68
- Supply Voltage: 10 → 30 V dc



2066154 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M12 X 1, 4 MM

Pack size: **1 x EA**

- Sensor Technology: Inductive
- Body Style: Barrel
- Thread Size: M12 x 1
- Output Type: PNP
- Detection Range: 4 mm
- Terminal Type: 2 m, 3-wire, Cable
- IP Rating: IP68
- Supply Voltage: 10 → 30 V dc



2066157 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M12 X 1, 4 MM

Pack size: **1 x EA**

- Sensor Technology: Inductive
- Body Style: Barrel
- Thread Size: M12 x 1
- Output Type: PNP
- Detection Range: 4 mm
- Terminal Type: 4-Pin M12 Connector
- IP Rating: IP68
- Supply Voltage: 10 → 30 V dc



2066155 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M12 X 1, 4 MM

Pack size: **1 x EA**

- Sensor Technology: Inductive
- Body Style: Barrel
- Thread Size: M12 x 1
- Output Type: PNP
- Detection Range: 4 mm
- Terminal Type: 4-Pin M12 Connector
- IP Rating: IP68
- Supply Voltage: 10 → 30 V dc



2066156 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M12 X 1, 8 MM

Pack size: **1 x EA**

- Sensor Technology: Inductive
- Body Style: Barrel
- Thread Size: M12 x 1
- Output Type: NPN
- Detection Range: 8 mm
- Terminal Type: 2 m, 3-wire, Cable
- IP Rating: IP68
- Supply Voltage: 10 → 30 V dc



2066158 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M12 X 1, 8 MM

Pack size: **1 x EA**

- Sensor Technology: Inductive
- Body Style: Barrel
- Thread Size: M12 x 1
- Output Type: PNP
- Detection Range: 8 mm
- Terminal Type: 4-Pin M12 Connector
- IP Rating: IP68
- Supply Voltage: 10 → 30 V dc



2066159 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M12 X 1, 8 MM

Pack size: **1 x EA**

- Sensor Technology: Inductive
- Body Style: Barrel
- Thread Size: M12 x 1
- Output Type: PNP
- Detection Range: 8 mm
- Terminal Type: 2 m, 3-wire, Cable
- IP Rating: IP68
- Supply Voltage: 10 → 30 V dc



2066160 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M18 X 1, 8 MM

Pack size: **1 x EA**

- Sensor Technology: Inductive
- Body Style: Barrel
- Thread Size: M18 x 1
- Output Type: PNP
- Detection Range: 8 mm
- Terminal Type: 4-Pin M12 Connector
- IP Rating: IP68
- Supply Voltage: 10 → 30 V dc



2066161 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M18 X 1, 8 MM

Pack size: **1 x EA**

- Sensor Technology: Inductive
- Body Style: Barrel
- Thread Size: M18 x 1
- Output Type: PNP
- Detection Range: 8 mm
- Terminal Type: 4-Pin M12 Connector
- IP Rating: IP68
- Supply Voltage: 10 → 30 V dc



2066162 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M30 X 1.5, 10

Pack size: **1 x EA**

- Sensor Technology: Inductive
- Body Style: Barrel
- Thread Size: M30 x 1.5
- Output Type: PNP
- Detection Range: 10 mm
- Terminal Type: 2 m, 3-wire, Cable
- IP Rating: IP68
- Supply Voltage: 10 → 30 V dc



2066165 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M18 X 1, 8 MM

Pack size: **1 x EA**

- Sensor Technology: Inductive
- Body Style: Barrel
- Thread Size: M18 x 1
- Output Type: PNP
- Detection Range: 8 mm
- Terminal Type: 2 m, 3-wire, Cable
- IP Rating: IP68
- Supply Voltage: 10 → 30 V dc



2066163 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M18 X 1, 20 MM

Pack size: **1 x EA**

- Sensor Technology: Inductive
- Body Style: Barrel
- Thread Size: M18 x 1
- Output Type: PNP
- Detection Range: 20 mm
- Terminal Type: 4-Pin M12 Connector
- IP Rating: IP68
- Supply Voltage: 10 → 30 V dc



2066164 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M30 X 1.5, 38

Pack size: **1 x EA**

- Sensor Technology: Inductive
- Body Style: Barrel
- Thread Size: M30 x 1.5
- Output Type: PNP Normally Open
- Detection Range: 38 mm
- Terminal Type: 2 m, 3-wire, Cable
- IP Rating: IP68
- Supply Voltage: 10 → 30 V dc



2066167 Inductive

RS PRO INDUCTIVE RECTANGULAR-STYLE PROXIMITY SENSOR, 3 MM

Pack size: **1 x EA**

- Sensor Technology: Inductive
- Body Style: Rectangular
- Output Type: PNP
- Detection Range: 3 mm
- Terminal Type: 2 m, 3-wire, Cable
- Supply Voltage: 10 → 30 V dc
- IP Rating: IP68
- Length: 16 mm



2066172 Inductive

RS PRO INDUCTIVE RECTANGULAR-STYLE PROXIMITY SENSOR, 20 MM

Pack size: **1 x EA**

- Sensor Technology: Inductive
- Body Style: Rectangular
- Output Type: PNP
- Detection Range: 20 mm
- Terminal Type: 4-Pin M12 Connector
- Supply Voltage: 10 → 30 V dc
- IP Rating: IP67
- Length: 66 mm



2066176 Inductive

RS PRO INDUCTIVE RECTANGULAR-STYLE PROXIMITY SENSOR, 40 MM

Pack size: **1 x EA**

- Sensor Technology: Inductive
- Body Style: Rectangular
- Output Type: PNP
- Detection Range: 40 mm
- Terminal Type: Cable
- Supply Voltage: 10 → 30 V dc
- IP Rating: IP67
- Length: 118 mm



2066181 Inductive

RS PRO INDUCTIVE RECTANGULAR-STYLE PROXIMITY SENSOR, 40 MM

Pack size: **1 x EA**

- Sensor Technology: Inductive
- Body Style: Rectangular
- Output Type: PNP
- Detection Range: 40 mm
- Terminal Type: 4-Pin M12 Connector
- Supply Voltage: 10 → 30 V dc
- IP Rating: IP67
- Length: 66 mm



2066180 Inductive

RS PRO INDUCTIVE RECTANGULAR-STYLE PROXIMITY SENSOR, 40 MM

Pack size: **1 x EA**

- Sensor Technology: Inductive
- Body Style: Rectangular
- Output Type: PNP
- Detection Range: 40 mm
- Terminal Type: Cable
- Supply Voltage: 10 → 30 V dc
- IP Rating: IP67
- Length: 118 mm



2066183 Inductive

RS PRO ULTRASONIC BARREL-STYLE PROXIMITY SENSOR, M30, 2000 MM

Pack size: **1 x EA**

- Sensor Technology: Ultrasonic
- Body Style: Barrel
- Thread Size: M30
- Output Type: Analogue 4-20mA
- Detection Range: 2000 mm
- Terminal Type: 4-Pin M12 Connector
- IP Rating: IP67
- Length: 110 mm



2181168 Ultrasonic

RS PRO ULTRASONIC BARREL-STYLE PROXIMITY SENSOR, M30, 2000 MM

Pack size: **1 x EA**

- Sensor Technology: Ultrasonic
- Body Style: Barrel
- Thread Size: M30
- Output Type: PNP
- Detection Range: 2000 mm
- Terminal Type: 4-Pin M12 Connector
- IP Rating: IP67
- Length: 110 mm



2181169 Ultrasonic

RS PRO ULTRASONIC BARREL-STYLE PROXIMITY SENSOR, M18, 300 MM

Pack size: **1 x EA**

- Sensor Technology: Ultrasonic
- Body Style: Barrel
- Thread Size: M18
- Output Type: Analogue 4-20mA
- Detection Range: 300 mm
- Terminal Type: 4-Pin M12 Connector
- IP Rating: IP67
- Length: 86 mm



2181171 Ultrasonic

RS PRO ULTRASONIC BARREL-STYLE PROXIMITY SENSOR, M18, 300 MM

Pack size: **1 x EA**

- Sensor Technology: Ultrasonic
- Body Style: Barrel
- Thread Size: M18
- Output Type: PNP
- Detection Range: 300 mm
- Terminal Type: 4-Pin M12 Connector
- IP Rating: IP67
- Length: 86 mm



2181172 Ultrasonic

RS PRO ULTRASONIC BARREL-STYLE PROXIMITY SENSOR, M30, 4000 MM

Pack size: **1 x EA**

- Sensor Technology: Ultrasonic
- Body Style: Barrel
- Thread Size: M30
- Output Type: Analogue 4-20mA
- Detection Range: 4000 mm
- Terminal Type: 4-Pin M12 Connector
- IP Rating: IP67
- Length: 110 mm



2181175 Ultrasonic

RS PRO ULTRASONIC BARREL-STYLE PROXIMITY SENSOR, 0 → 300 MM

Pack size: **1 x EA**

- Sensor Technology: Ultrasonic
- Body Style: Barrel
- Detection Range: 0 → 300 mm
- Terminal Type: PCB
- Supply Voltage: 20 V
- Length: 7.1 mm
- Maximum Operating Temperature: +85 °C
- Minimum Operating Temperature: -40 °C



2370799 Ultrasonic

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M18 X 1, 5 MM

Pack size: **1 x EA**

- Sensor Technology: Inductive
- Body Style: Barrel
- Thread Size: M18 x 1
- Output Type: PNP-NO
- Detection Range: 5 mm
- Terminal Type: Cable
- IP Rating: IP67
- Supply Voltage: 10 → 30 V dc



7018213 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M30 X 1.5, 10

Pack size: **1 x EA**

- Sensor Technology: Inductive
- Body Style: Barrel
- Thread Size: M30 x 1.5
- Output Type: PNP-NO
- Detection Range: 10 mm
- Terminal Type: Cable
- IP Rating: IP67
- Supply Voltage: 10 → 30 V dc



7018216 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M30 X 1.5, 10

Pack size: **1 x EA**

- Sensor Technology: Inductive
- Body Style: Barrel
- Thread Size: M30 x 1.5
- Output Type: NPN-NO
- Detection Range: 10 mm
- Terminal Type: Cable
- IP Rating: IP67
- Supply Voltage: 10 → 30 V dc



7018219 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M18 X 1, 5 MM

Pack size: **1 x EA**

- Sensor Technology: Inductive
- Body Style: Barrel
- Thread Size: M18 x 1
- Output Type: NPN-NO
- Detection Range: 5 mm
- Terminal Type: Cable
- IP Rating: IP67
- Supply Voltage: 10 → 30 V dc



7018222 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M12 X 1, 2 MM

Pack size: **1 x EA**

- Sensor Technology: Inductive
- Body Style: Barrel
- Thread Size: M12 x 1
- Output Type: PNP-NO
- Detection Range: 2 mm
- Terminal Type: Cable
- IP Rating: IP67
- Supply Voltage: 10 → 30 V dc



7018225 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M12 X 1, 2 MM

Pack size: **1 x EA**

- Sensor Technology: Inductive
- Body Style: Barrel
- Thread Size: M12 x 1
- Output Type: NPN-NO
- Detection Range: 2 mm
- Terminal Type: Cable
- Supply Voltage: 10 → 30 V dc
- IP Rating: IP67



7018229 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M12 X 1, 2 MM

Pack size: **1 x EA**

- Sensor Technology: Inductive
- Body Style: Barrel
- Thread Size: M12 x 1
- Output Type: PNP-NO
- Detection Range: 2 mm
- Terminal Type: M12 - 4 Pin
- IP Rating: IP67
- Supply Voltage: 10 → 30 V dc



7018231 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M18 X 1, 5 MM

Pack size: **1 x EA**

- Sensor Technology: Inductive
- Body Style: Barrel
- Thread Size: M18 x 1
- Output Type: NPN-NO
- Detection Range: 5 mm
- Terminal Type: M12 - 4 Pin
- IP Rating: IP67
- Supply Voltage: 10 → 30 V dc



7018235 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M12 X 1, 2 MM

Pack size: **1 x EA**

- Sensor Technology: Inductive
- Body Style: Barrel
- Thread Size: M12 x 1
- Output Type: NPN-NO
- Detection Range: 2 mm
- Terminal Type: M12 - 4 Pin
- IP Rating: IP67
- Supply Voltage: 10 → 30 V dc



7018238 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M30 X 1.5, 10

Pack size: **1 x EA**

- Sensor Technology: Inductive
- Body Style: Barrel
- Thread Size: M30 x 1.5
- Output Type: PNP-NO
- Detection Range: 10 mm
- Terminal Type: M12 - 4 Pin
- IP Rating: IP67
- Supply Voltage: 10 → 30 V dc



7018241 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M18 X 1, 5 MM

Pack size: **1 x EA**

- Sensor Technology: Inductive
- Body Style: Barrel
- Thread Size: M18 x 1
- Output Type: PNP-NO
- Detection Range: 5 mm
- Terminal Type: M12 - 4 Pin
- IP Rating: IP67
- Supply Voltage: 10 → 30 V dc



7018244 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M30 X 1.5, 10

Pack size: **1 x EA**

- Sensor Technology: Inductive
- Body Style: Barrel
- Thread Size: M30 x 1.5
- Output Type: NPN-NO
- Detection Range: 10 mm
- Terminal Type: M12 - 4 Pin
- IP Rating: IP67
- Supply Voltage: 10 → 30 V dc



7018247 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M12 X 1, 4 MM

Pack size: **1 x EA**

- Sensor Technology: Inductive
- Body Style: Barrel
- Thread Size: M12 x 1
- Output Type: NPN-NO
- Detection Range: 4 mm
- Terminal Type: Cable
- IP Rating: IP67
- Supply Voltage: 10 → 30 V dc



7018250 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M12 X 1, 4 MM

Pack size: **1 x EA**

- Sensor Technology: Inductive
- Body Style: Barrel
- Thread Size: M12 x 1
- Output Type: PNP-NO
- Detection Range: 4 mm
- Terminal Type: Cable
- IP Rating: IP67
- Supply Voltage: 10 → 30 V dc



7018253 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M18 X 1, 8 MM

Pack size: **1 x EA**

- Sensor Technology: Inductive
- Body Style: Barrel
- Thread Size: M18 x 1
- Output Type: NPN-NO
- Detection Range: 8 mm
- Terminal Type: Cable
- IP Rating: IP67
- Supply Voltage: 10 → 30 V dc



7018257 Inductive

RS PRO INDUCTIVE BARREL-STYLE PROXIMITY SENSOR, M30 X 1.5, 15

Pack size: **1 x EA**

- Sensor Technology: Inductive
- Body Style: Barrel
- Thread Size: M30 x 1.5
- Output Type: PNP-NO
- Detection Range: 15 mm
- Terminal Type: Cable
- IP Rating: IP67
- Supply Voltage: 10 → 30 V dc



7018263 Inductive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M18 X 1, 8 MM

Pack size: **1 x EA**

- Sensor Technology: Capacitive
- Body Style: Barrel
- Thread Size: M18 x 1
- Output Type: NPN
- Detection Range: 8 mm
- Terminal Type: Cable
- IP Rating: IP67
- Supply Voltage: 10 → 30 V dc



8967223 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M18 X 1, 5 MM

Pack size: **1 x EA**

- Sensor Technology: Capacitive
- Body Style: Barrel
- Thread Size: M18 x 1
- Output Type: NPN Normally Open
- Detection Range: 5 mm
- Terminal Type: Cable
- IP Rating: IP67
- Supply Voltage: 10 → 30 V dc



8967229 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M18 X 1, 5 MM

Pack size: **1 x EA**

- Sensor Technology: Capacitive
- Body Style: Barrel
- Thread Size: M18 x 1
- Output Type: PNP
- Detection Range: 5 mm
- Terminal Type: Cable
- IP Rating: IP67
- Supply Voltage: 10 → 30 V dc



8967232 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M18 X 1, 8 MM

Pack size: **1 x EA**

- Sensor Technology: Capacitive
- Body Style: Barrel
- Thread Size: M18 x 1
- Output Type: PNP
- Detection Range: 8 mm
- Terminal Type: Cable
- Supply Voltage: 10 → 30 V dc
- IP Rating: IP67



8967235 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M18 X 1, 5 MM

Pack size: **1 x EA**

- Sensor Technology: Capacitive
- Body Style: Barrel
- Thread Size: M18 x 1
- Detection Range: 5 mm
- Terminal Type: Cable
- Supply Voltage: 20 → 250 V ac
- IP Rating: IP67
- Length: 83.5 mm



8967241 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M18 X 1, 8 MM

Pack size: **1 x EA**

- Sensor Technology: Capacitive
- Body Style: Barrel
- Thread Size: M18 x 1
- Output Type: PNP
- Detection Range: 8 mm
- Terminal Type: 4-Pin M12 Connector
- IP Rating: IP67
- Supply Voltage: 10 → 30 V dc



8967248 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M30 X 1.5, 10

Pack size: **1 x EA**

- Sensor Technology: Capacitive
- Body Style: Barrel
- Thread Size: M30 x 1.5
- Output Type: PNP
- Detection Range: 10 mm
- Terminal Type: Cable
- IP Rating: IP67
- Supply Voltage: 10 → 30 V dc



8967251 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M30 X 1.5, 10

Pack size: **1 x EA**

- Sensor Technology: Capacitive
- Body Style: Barrel
- Thread Size: M30 x 1.5
- Output Type: NPN Normally Open
- Detection Range: 10 mm
- Terminal Type: Cable
- IP Rating: IP67
- Supply Voltage: 10 → 30 V dc



8967254 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M30 X 1.5, 15

Pack size: **1 x EA**

- Sensor Technology: Capacitive
- Body Style: Barrel
- Thread Size: M30 x 1.5
- Output Type: NPN
- Detection Range: 15 mm
- Terminal Type: Cable
- IP Rating: IP67
- Supply Voltage: 10 → 30 V dc



8967257 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M30 X 1.5, 15

Pack size: **1 x EA**

- Sensor Technology: Capacitive
- Body Style: Barrel
- Thread Size: M30 x 1.5
- Output Type: PNP
- Detection Range: 15 mm
- Terminal Type: Cable
- IP Rating: IP67
- Supply Voltage: 10 → 30 V dc



8967260 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M30 X 1.5, 10

Pack size: **1 x EA**

- Sensor Technology: Capacitive
- Body Style: Barrel
- Thread Size: M30 x 1.5
- Output Type: PNP
- Detection Range: 10 mm
- Terminal Type: 4-Pin M12 Connector
- IP Rating: IP67
- Supply Voltage: 10 → 30 V dc



8967263 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M30 X 1.5, 15

Pack size: **1 x EA**

- Sensor Technology: Capacitive
- Body Style: Barrel
- Thread Size: M30 x 1.5
- Output Type: PNP
- Detection Range: 15 mm
- Terminal Type: 4-Pin M12 Connector
- IP Rating: IP67
- Supply Voltage: 10 → 30 V dc



8967267 Capacitive

RS PRO CAPACITIVE BLOCK-STYLE PROXIMITY SENSOR, 10 MM

Pack size: **1 x EA**

- Sensor Technology: Capacitive
- Body Style: Block
- Output Type: PNP
- Detection Range: 10 mm
- Terminal Type: Cable
- IP Rating: IP67
- Supply Voltage: 10 → 30 V dc
- Length: 50 mm



8967273 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M30 X 1.5, 15

Pack size: **1 x EA**

- Sensor Technology: Capacitive
- Body Style: Barrel
- Thread Size: M30 x 1.5
- Detection Range: 15 mm
- Terminal Type: Cable
- Supply Voltage: 20 → 250 V ac/dc
- IP Rating: IP67
- Length: 91 mm



8967276 Capacitive

RS PRO CAPACITIVE BARREL-STYLE PROXIMITY SENSOR, M30 X 1.5, 15

Pack size: **1 x EA**

- Sensor Technology: Capacitive
- Body Style: Barrel
- Thread Size: M30 x 1.5
- Detection Range: 15 mm
- Terminal Type: Cable
- Supply Voltage: 20 → 250 V ac/dc
- IP Rating: IP67
- Length: 91 mm



8967279 Capacitive

RS PRO CAPACITIVE BLOCK-STYLE PROXIMITY SENSOR, 8 MM

Pack size: **1 x EA**

- Sensor Technology: Capacitive
- Body Style: Block
- Output Type: PNP
- Detection Range: 8 mm
- Terminal Type: Cable
- IP Rating: IP67
- Supply Voltage: 10 → 30 V dc
- Length: 50 mm



8967282 Capacitive

RS PRO RIGHT ANGLE FEMALE 4-POLET UNTERMINATED SENSOR

Pack size: **1 x EA**

- Connector 1: M12
- Connector 2: Untermated
- Connector 1 Gender: Female
- Connector 1 Number of Contacts: 4
- Connector 1 Orientation: Right Angle
- Connector 1 Housing Gender: Male
- Length: 15 m
- Sheath Material: PUR



2055980 M12

RS PRO STRAIGHT FEMALE 3-POLET UNTERMINATED SENSOR ACTUATOR

Pack size: **1 x EA**

- Connector 1: M8
- Connector 2: Untermated
- Connector 1 Gender: Female
- Connector 1 Number of Contacts: 3
- Connector 1 Orientation: Straight
- Length: 10 m
- Sheath Material: PVC
- IP Rating: IP67



2055987 M8

RS PRO STRAIGHT FEMALE 4-POLET UNTERMINATED SENSOR ACTUATOR

Pack size: **1 x EA**

- Connector 1: M12
- Connector 2: Untermated
- Connector 1 Gender: Female
- Connector 1 Number of Contacts: 4
- Connector 1 Orientation: Straight
- Connector 1 Housing Gender: Male
- Length: 10 m
- Sheath Material: PUR



2055992 M12

RS PRO RIGHT ANGLE FEMALE 4-POLET UNTERMINATED SENSOR

Pack size: **1 x EA**

- Connector 1: M12
- Connector 2: Untermated
- Connector 1 Gender: Female
- Connector 1 Number of Contacts: 4
- Connector 1 Orientation: Right Angle
- Connector 1 Housing Gender: Male
- Length: 20 m
- Sheath Material: PUR



2055993 M12

RS PRO RIGHT ANGLE FEMALE 4-POLET UNTERMINATED SENSOR

Pack size: **1 x EA**

- Connector 1: M8
- Connector 2: Untermated
- Connector 1 Gender: Female
- Connector 1 Number of Contacts: 4
- Connector 1 Orientation: Right Angle
- Length: 2 m
- Number of Cores: 4
- Connector B: Untermated



2121693 M8

RS PRO RIGHT ANGLE FEMALE 4-POLET UNTERMINATED SENSOR

Pack size: **1 x EA**

- Connector 1: M8
- Connector 2: Untermated
- Connector 1 Gender: Female
- Connector 1 Number of Contacts: 4
- Connector 1 Orientation: Right Angle
- Length: 5 m
- Number of Cores: 4
- Connector B: Untermated



2121694 M8

RS PRO RIGHT ANGLE FEMALE 4-POLET UNTERMINATED SENSOR

Pack size: **1 x EA**

- Connector 1: M8
- Connector 2: Untermated
- Connector 1 Gender: Female
- Connector 1 Number of Contacts: 4
- Connector 1 Orientation: Right Angle
- Length: 5 m
- Number of Cores: 4
- Connector B: Untermated



2121695 M8

RS PRO STRAIGHT FEMALE 4-POLET UNTERMINATED SENSOR ACTUATOR

Pack size: **1 x EA**

- Connector 1: M8
- Connector 2: Untermated
- Connector 1 Gender: Female
- Connector 1 Number of Contacts: 4
- Connector 1 Orientation: Straight
- Length: 2 m
- Number of Cores: 4
- Connector B: Untermated



2121697 M8

RS PRO STRAIGHT FEMALE 4-POLET UNTERMINATED SENSOR ACTUATOR

Pack size: **1 x EA**

- Connector 1: M8
- Connector 2: Untermated
- Connector 1 Gender: Female
- Connector 1 Number of Contacts: 4
- Connector 1 Orientation: Straight
- Length: 5 m
- Number of Cores: 4
- Connector B: Untermated



2121699 M8

RS PRO STRAIGHT FEMALE 4-POLET UNTERMINATED SENSOR ACTUATOR

Pack size: **1 x EA**

- Connector 1: M8
- Connector 2: Untermated
- Connector 1 Gender: Female
- Connector 1 Number of Contacts: 4
- Connector 1 Orientation: Straight
- Length: 5 m
- Number of Cores: 4
- Connector B: Untermated



2121700 M8

RS PRO RIGHT ANGLE FEMALE 4-POLET UNTERMINATED SENSOR

Pack size: **1 x EA**

- Connector 1: M12
- Connector 2: Unterminated
- Connector 1 Gender: Female
- Connector 1 Number of Contacts: 4
- Connector 1 Orientation: Right Angle
- Length: 2 m
- Number of Cores: 4
- Connector B: Unterminated



2121703 M12

RS PRO RIGHT ANGLE FEMALE 4-POLET UNTERMINATED SENSOR

Pack size: **1 x EA**

- Connector 1: M12
- Connector 2: Unterminated
- Connector 1 Gender: Female
- Connector 1 Number of Contacts: 4
- Connector 1 Orientation: Right Angle
- Length: 5 m
- Number of Cores: 4
- Connector B: Unterminated



2121704 M12

RS PRO RIGHT ANGLE FEMALE 4-POLET UNTERMINATED SENSOR

Pack size: **1 x EA**

- Connector 1: M12
- Connector 2: Unterminated
- Connector 1 Gender: Female
- Connector 1 Number of Contacts: 4
- Connector 1 Orientation: Right Angle
- Length: 5 m
- Number of Cores: 4
- Connector B: Unterminated



2121707 M12

RS PRO RIGHT ANGLE FEMALE 4-POLET UNTERMINATED SENSOR

Pack size: **1 x EA**

- Connector 1: M12
- Connector 2: Unterminated
- Connector 1 Gender: Female
- Connector 1 Number of Contacts: 4
- Connector 1 Orientation: Right Angle
- Length: 5 m
- Number of Cores: 4
- Connector B: Unterminated



2121708 M12

RS PRO RIGHT ANGLE FEMALE 4-POLET UNTERMINATED SENSOR

Pack size: **1 x EA**

- Connector 1: M12
- Connector 2: Unterminated
- Connector 1 Gender: Female
- Connector 1 Number of Contacts: 4
- Connector 1 Orientation: Right Angle
- Length: 10 m
- Number of Cores: 4
- Connector B: Unterminated



2121709 M12

RS PRO RIGHT ANGLE FEMALE 4-POLET UNTERMINATED SENSOR

Pack size: **1 x EA**

- Connector 1: M12
- Connector 2: Unterminated
- Connector 1 Gender: Female
- Connector 1 Number of Contacts: 4
- Connector 1 Orientation: Right Angle
- Length: 10 m
- Number of Cores: 4
- Connector B: Unterminated



2121710 M12

RS PRO RIGHT ANGLE FEMALE 4-POLET UNTERMINATED SENSOR

Pack size: **1 x EA**

- Connector 1: M12
- Connector 2: Unterminated
- Connector 1 Gender: Female
- Connector 1 Number of Contacts: 4
- Connector 1 Orientation: Right Angle
- Length: 10 m
- Number of Cores: 4
- Connector B: Unterminated



2121712 M12

RS PRO STRAIGHT FEMALE 4-POLET UNTERMINATED SENSOR ACTUATOR

Pack size: **1 x EA**

- Connector 1: M12
- Connector 2: Unterminated
- Connector 1 Gender: Female
- Connector 1 Number of Contacts: 4
- Connector 1 Orientation: Straight
- Length: 2 m
- Number of Cores: 4
- Connector B: Unterminated



2121715 M12

RS PRO STRAIGHT FEMALE 4-POLET UNTERMINATED SENSOR ACTUATOR

Pack size: **1 x EA**

- Connector 1: M12
- Connector 2: Unterminated
- Connector 1 Gender: Female
- Connector 1 Number of Contacts: 4
- Connector 1 Orientation: Straight
- Length: 2 m
- Number of Cores: 4
- Connector B: Unterminated



2121716 M12

RS PRO FEMALE 4-POLET UNTERMINATED SENSOR ACTUATOR

Pack size: **1 x EA**

- Connector 1: M12
- Connector 2: Unterminated
- Connector 1 Gender: Female
- Connector 1 Number of Contacts: 4
- Length: 5 m
- Number of Cores: 4
- Connector B: Unterminated
- Connector A: M12



2121719 M12

RS PRO STRAIGHT FEMALE 4-POLET UNTERMINATED SENSOR ACTUATOR

Pack size: **1 x EA**

- Connector 1: M12
- Connector 2: Unterminated
- Connector 1 Gender: Female
- Connector 1 Number of Contacts: 4
- Connector 1 Orientation: Straight
- Length: 10 m
- Number of Cores: 4
- Connector B: Unterminated



2121720 M12

RS PRO STRAIGHT FEMALE 4-POLET UNTERMINATED SENSOR ACTUATOR

Pack size: **1 x EA**

- Connector 1: M12
- Connector 2: Unterminated
- Connector 1 Gender: Female
- Connector 1 Number of Contacts: 4
- Connector 1 Orientation: Straight
- Length: 10 m
- Number of Cores: 4
- Connector B: Unterminated



2121721 M12

RS PRO STRAIGHT FEMALE STRAIGHT 4-POLET MALE M12 SENSOR

Pack size: **1 x EA**

- Connector 1: M12
- Connector 2: M12
- Connector 1 Gender: Female
- Connector 2 Gender: Male
- Connector 1 Number of Contacts: 4
- Connector 2 Number of Contacts: 4
- Connector 1 Orientation: Straight
- Connector 2 Orientation: Straight



2121722 M12

RS PRO STRAIGHT FEMALE STRAIGHT 4-POLET MALE M12 SENSOR

Pack size: **1 x EA**

- Connector 1: M12
- Connector 2: M12
- Connector 1 Gender: Female
- Connector 2 Gender: Male
- Connector 1 Number of Contacts: 4
- Connector 2 Number of Contacts: 4
- Connector 1 Orientation: Straight
- Connector 2 Orientation: Straight



2121723 M12

RS PRO CONNECTOR

Pack size: **1 x EA**

- Connector A: M12
- Connector B: Unterminated
- Connector A Gender: Female
- Connector A Orientation: Straight
- Number of Cores: 4
- Mounting Type: Panel Mount
- Length: 2 m
- Sheath Material: PUR



2121724 M12

RS PRO MAGNET FOR USE WITH PROXIMITY SWITCH

Pack size: **1 x EA**

- Accessory Type: Magnet
- For Use With: Proximity Switch
- Application: Proximity Switch



285245 Magnet

RS PRO MAGNET FOR USE WITH MAGNETIC PROXIMITY SWITCH

Pack size: **1 x EA**

- Accessory Type: Magnet
- For Use With: Magnetic Proximity Switch
- Application: Magnetic Proximity Switch



339768 Magnet

RS PRO MOUNTING BRACKET FOR USE WITH M18 SENSOR

Pack size: **1 x EA**

- Accessory Type: Mounting Bracket
- For Use With: M18 Sensor
- Application: Mounting
- Series: M18



2133659 Mounting Bracket

RS PRO MOUNTING BRACKET FOR USE WITH M12 SENSOR

Pack size: **1 x EA**

- Accessory Type: Mounting Bracket
- For Use With: M12 Sensor
- Application: Mounting
- Series: M12



2133660 Mounting Bracket

RS PRO MOUNTING BRACKET FOR USE WITH M30 SENSOR

Pack size: **1 x EA**

- Accessory Type: Mounting Bracket
- For Use With: M30 Sensor
- Application: Mounting
- Series: M30



2133662 Mounting Bracket

RS PRO MAGNET FOR USE WITH PROXIMITY SWITCH

Pack size: **1 x EA**

- Accessory Type: Magnet
- For Use With: Proximity Switch
- Application: Proximity Switch



3614927 Magnet

RS PRO MAGNET FOR USE WITH PROXIMITY SWITCH

Pack size: **1 x EA**

- Accessory Type: Magnet
- For Use With: Proximity Switch
- Application: Proximity Switch



3617011 Magnet

RS PRO MAGNET FOR USE WITH TRANSDUCER

Pack size: **1 x EA**

- Accessory Type: Magnet
- For Use With: Transducer
- Application: Transducer



5361710 Magnet

RS PRO MAGNET FOR USE WITH TRANSDUCER

Pack size: **1 x EA**

- Accessory Type: Magnet
- For Use With: Transducer
- Application: Transducer



5361748 Magnet

RS PRO MOUNTING BRACKET FOR USE WITH M4 → M18 PROXIMITY

Pack size: **1 x EA**

- Accessory Type: Mounting Bracket
- For Use With: M4 → M18 Proximity Sensors



7141697 Mounting Bracket

RS PRO MAGNET FOR USE WITH LINEAR ACTUATOR

Pack size: **1 x EA**

- Accessory Type: Magnet
- For Use With: Linear Actuator
- Application: Linear Actuator



8110745 Magnet

RS PRO SENSOR TESTER FOR USE WITH 18 V DC / 35 MA CHECK OF

Pack size: **1 x EA**

- Accessory Type: Sensor Tester
- For Use With: 18 V dc / 35 mA Check of Proximity Switches
- Application: Proximity Switch
- Series: TM800
- Standards Met: RoHS Compliant




8399875 Sensor Tester

RS PRO SENSOR CONNECTOR TO FREE END WIRE TO BOARD CABLE

Pack size: **1 x EA**

- Sheath Colour: Black
- Connector A Number of Contacts: 4
- Connector B: Free End
- Connector A Gender: Male
- Connector A: Sensor Connector



2055977 Black

RS PRO SENSOR CONNECTOR TO FREE END WIRE TO BOARD CABLE

Pack size: **1 x EA**

- Sheath Colour: Multicoloured
- Connector A Number of Contacts: 3
- Connector B: Free End
- Connector A Gender: Male
- Connector A: Sensor Connector



2055983 Multicoloured

RS PRO TOUCH-SCREEN HMI DISPLAY - 7 IN, TFT LCD DISPLAY, 800 X

Pack size: **1 x EA**

- Display Type: TFT LCD
- Display Size: 7 in
- Display Resolution: 800 x 480 pixels
- Display Colour: Colour
- Number of Ports: 3
- Port Type: COM1, COM2, USB Host, USB Client
- Interface: USB
- Processor Type: ARM Cortex



2156604 TFT LCD

RS PRO TOUCH-SCREEN HMI DISPLAY - 7 IN, TFT LCD DISPLAY, 800 X

Pack size: **1 x EA**

- Display Type: TFT LCD
- Display Size: 7 in
- Display Resolution: 800 x 480 pixels
- Display Colour: Colour
- Number of Ports: 4
- Port Type: COM1, COM2, USB Host, USB Client
- Interface: USB, Ethernet
- Processor Type: ARM Cortex



2156605 TFT LCD

RS PRO TOUCH-SCREEN HMI DISPLAY - 10.2 IN, TFT LCD DISPLAY, 1024 X

Pack size: **1 x EA**

- Display Type: TFT LCD
- Display Size: 10.2 in
- Display Resolution: 1024 x 600 pixels
- Display Colour: Colour
- Number of Ports: 4
- Port Type: COM1, COM2, USB Host, USB Client
- Interface: USB, Ethernet
- Processor Type: ARM Cortex



2156606 TFT LCD

RS PRO DIN RAIL MOUNT ETHERNET SWITCH, 8 RJ45 PORTS,

Pack size: **1 x EA**

- Transmission Speed: 10/100 Mbit/s
- RJ45 Ports: 8
- Mounting: DIN Rail
- Maximum Operating Temperature: +80 °C
- Maximum Supply Voltage: 30 V dc
- Minimum Operating Temperature: -40 °C
- For Use With: Ethernet Network



1448674 10/100 Mbit/s

RS PRO DIN RAIL MOUNT ETHERNET SWITCH, 5 RJ45 PORTS,

Pack size: **1 x EA**

- Transmission Speed: 10/100 Mbit/s
- RJ45 Ports: 5
- Mounting: DIN Rail
- Maximum Operating Temperature: +80 °C
- Maximum Supply Voltage: 30 V dc
- Minimum Operating Temperature: -40 °C
- For Use With: Ethernet Network



1448673 10/100 Mbit/s

RS PRO DIN RAIL MOUNT ETHERNET SWITCH, 5 RJ45 PORTS,

Pack size: **1 x EA**

- Transmission Speed: 10/100 Mbit/s
- RJ45 Ports: 5
- Mounting: DIN Rail
- Height: 99 mm
- Maximum Operating Temperature: +80 °C
- Maximum Supply Voltage: 30 V dc
- Minimum Operating Temperature: -40 °C
- Minimum Supply Voltage: 5 V dc



1448675 10/100 Mbit/s

RS PRO DIN RAIL MOUNT ETHERNET SWITCH, 8 RJ45 PORTS,

Pack size: **1 x EA**

- Transmission Speed: 10/100 Mbit/s
- RJ45 Ports: 8
- Mounting: DIN Rail
- Depth: 115 mm
- Height: 99 mm
- Maximum Operating Temperature: +80 °C
- Maximum Supply Voltage: 30 V dc
- Minimum Operating Temperature: -40 °C



1448676 10/100 Mbit/s

RS PRO WALL MOUNT ETHERNET SWITCH, 8 RJ45 PORTS,

Pack size: **1 x EA**

- Transmission Speed: 10/100 Mbit/s
- RJ45 Ports: 8
- Nominal Supply Voltage: 30 V dc
- Mounting: Wall
- Series: RS-008
- Height: 102 mm
- Maximum Operating Temperature: +60 °C
- Minimum Operating Temperature: -10 °C



2263243 10/100 Mbit/s

RS PRO LOGIC MODULE - 8 INPUTS, 4 OUTPUTS, DIGITAL, RELAY, MODBUS

Pack size: **1 x EA**

- Number of Inputs: 8
- Output Type: Digital, Relay
- Input Type: Digital
- Supply Voltage: 110 → 240 V ac
- Number of Outputs: 4
- Network Type: ModBus
- Display Included: Yes
- Communication Port Type: Serial



9176361 8

RS PRO LOGIC MODULE - 8 INPUTS, 4 OUTPUTS, DIGITAL, RELAY, MODBUS

Pack size: **1 x EA**

- Number of Inputs: 8
- Output Type: Digital, Relay
- Input Type: Analogue, Digital
- Supply Voltage: 12 → 24 V dc
- Number of Outputs: 4
- Network Type: ModBus
- Display Included: Yes
- Communication Port Type: Serial



9176370 8

RS PRO LOGIC MODULE - 8 INPUTS, 4 OUTPUTS, DIGITAL, RELAY, MODBUS

Pack size: **1 x EA**

- Number of Inputs: 8
- Output Type: Digital, Relay
- Input Type: Digital
- Supply Voltage: 110 → 240 V ac
- Number of Outputs: 4
- Network Type: ModBus
- Communication Port Type: Serial
- Program Capacity: 250 lines



9176373 8

LOGIC MODULE W/O DISPLAY 8I/4O 12-24V

Pack size: **1 x EA**

- Number of Inputs: 8
- Output Type: Digital, Relay
- Input Type: Analogue, Digital
- Supply Voltage: 12 → 24 V dc
- Number of Outputs: 4
- Network Type: ModBus
- Communication Port Type: Serial
- Program Capacity: 250 lines



9176377 8

RS PRO COMMUNICATION MODULE - 1 INPUTS, 1 OUTPUTS, RS485

Pack size: **1 x EA**

- For Use With: RS PRO Logic Modules
- Number of Inputs: 1
- Output Type: RS485 Protocol (D-), RS485 Protocol (D+), RS485 Protocol (Two Wires)
- Input Type: TTL Level
- Supply Voltage: 110 → 240 V ac
- Number of Outputs: 1
- Network Type: ModBus
- Communication Port Type: RS485



9176383 RS PRO Logic

RS PRO, I/O EXTENSION MODULE - 8 INPUTS, 4 OUTPUTS, DIGITAL, RELAY,

Pack size: **1 x EA**

- For Use With: RS PRO Logic Modules
- Number of Inputs: 8
- Output Type: Digital, Relay
- Input Type: Digital
- Supply Voltage: 110 → 240 V ac
- Number of Outputs: 4
- Network Type: ModBus
- Communication Port Type: Serial



9176386 RS PRO Logic

RS PRO COMMUNICATION MODULE - 1 INPUTS, 1 OUTPUTS, RS485

Pack size: **1 x EA**

- For Use With: RS PRO Logic Modules
- Number of Inputs: 1
- Output Type: RS485 Protocol (D-), RS485 Protocol (D+), RS485 Protocol (Two Wires)
- Input Type: TTL Level
- Supply Voltage: 12 → 24 V dc
- Number of Outputs: 1
- Network Type: ModBus
- Communication Port Type: RS485



9176392 RS PRO Logic

RS PRO MEMORY MODULE FOR USE WITH RS PRO LOGIC MODULES

Pack size: **1 x EA**

- For Use With: RS PRO Logic Modules
- Maximum Operating Temperature: +55 °C



9176399 RS PRO Logic

LOGIC MODULE USB PROGRAMMING CABLE

- Pack size: **1 x EA**
- Accessory Type: USB Cable
 - For Use With: Logic Module
 - Application: Automation, Commercial, Industrial
 - Termination: Plug-In



9176395 USB Cable

RS PRO 2 PORT PCI RS232 SERIAL CARD

- Pack size: **1 x EA**
- Bus Type: PCI
 - Communication Interface: Serial
 - Number of Ports: 2
 - Connection Port: RS232



6161892 PCI

RS PRO CAR CHARGER, 11 → 16V DC INPUT, 19V DC OUTPUT PLUG IN, 4.7A

Pack size: **1 x EA**

- Input Voltage: 11 → 16 V dc
- Output Voltage: 19 V dc
- Output Power Continuous: 89 W
- Output Connection Type: Plug In
- Output Current: 4.7 A
- Length: 105.9 mm
- Width: 51.5 mm
- Depth: 18.4 mm



417916 11 → 16 V dc

RS PRO DC-DC CONVERTER, 12V DC/, 21.6 → 26.4 V DC INPUT, 1W, PCB

Pack size: **1 x EA**

- Output Voltage: 12 V dc
- Input Voltage Range: 21.6 → 26.4 V dc
- Power Rating: 1 W
- Input Voltage Nominal: 24 V dc
- Mounting Type: PCB Mount
- Isolated: Yes
- Isolation Voltage: 1.5 kV
- Railway Approved: No



2240352 12 V dc

RS PRO CONNECTOR KIT, FOR USE WITH RPS-75

Pack size: **1 x KT**

- Accessory Type: Connector Kit
- For Use With: RPS-75



381835 Connector Kit

RS PRO WALL MOUNT LINEAR POWER SUPPLY, 230V AC INPUT, 24V AC

Pack size: **1 x EA**

- Input Voltage: 230 V ac
- Output Voltage: 24 V ac
- Output Current: 7 A
- Number of Outputs: 1
- Embedded: Yes
- Power Rating: 168 VA
- Length: 122.2 mm
- Width: 89.9 mm



1244715 230 V ac

RS PRO CONNECTOR KIT, FOR USE WITH PS-35, RPS-60

Pack size: **1 x KT**

- Accessory Type: Connector Kit
- For Use With: PS-35, RPS-60



381841 Connector Kit

RS PRO CONNECTOR KIT, FOR USE WITH RPD-60, RPT-60

Pack size: **1 x KT**

- Accessory Type: Connector Kit
- For Use With: RPD-60, RPT-60



381845 Connector Kit

RS PRO CONNECTOR KIT, FOR USE WITH PPT-125

Pack size: **1 x KT**

- Accessory Type: Connector Kit
- For Use With: PPT-125



381851 Connector Kit

POWER SUPPLY, SWITCH MODE, RS RANGE, AC/DC, CONNECTOR

Pack size: **1 x KT**

- Accessory Type: Connector Kit
- For Use With: PPS-125, PPS-200, RPD-75, RPT-75



381857 Connector Kit

RS PRO CONNECTOR KIT, FOR USE WITH ASP-150

Pack size: **1 x KT**

- Accessory Type: Connector Kit
- For Use With: ASP-150



424392 Connector Kit

RS PRO CONNECTOR KIT, FOR USE WITH USP-350

Pack size: **1 x KT**

- Accessory Type: Connector Kit
- For Use With: USP-350



453827 Connector Kit

RS PRO SWITCHING POWER SUPPLY, 24V DC, 2.5A, 60W, 1 OUTPUT

Pack size: **1 x EA**

- Output Voltage: 24 V dc
- Output Current: 2.5 A
- Power Rating: 60 W
- Number of Outputs: 1
- Input Voltage: 100 → 230 V ac
- Mounting Type: Panel Mount
- Package Type: Open Frame
- Length: 101.6 mm



1244711 24 V dc

RS PRO SWITCHING POWER SUPPLY, 12V DC, 5A, 60W, 1 OUTPUT

Pack size: **1 x EA**

- Output Voltage: 12 V dc
- Output Current: 5 A
- Power Rating: 60 W
- Number of Outputs: 1
- Input Voltage: 100 → 230 V ac
- Mounting Type: Panel Mount
- Package Type: Open Frame
- Length: 101.6 mm



1244709 12 V dc

RS PRO SWITCHING POWER SUPPLY, 48V DC, 1.25A, 60W, 1 OUTPUT

Pack size: **1 x EA**

- Output Voltage: 48 V dc
- Output Current: 1.25 A
- Power Rating: 60 W
- Number of Outputs: 1
- Input Voltage: 100 → 230 V ac
- Mounting Type: Panel Mount
- Package Type: Open Frame
- Length: 101.6 mm



1244714 48 V dc

RS PRO SWITCHING POWER SUPPLY, 15V DC, 1.7A, 25.5W, 1 OUTPUT

Pack size: **1 x EA**

- Output Voltage: 15 V dc
- Output Current: 1.7 A
- Power Rating: 25.5 W
- Number of Outputs: 1
- Input Voltage: 88 → 264 V ac
- Mounting Type: Chassis Mount
- Package Type: Enclosed
- Length: 85 mm



1618216 15 V dc

RS PRO SWITCHING POWER SUPPLY, 12V DC, 16.7A, 200W, 1 OUTPUT

Pack size: **1 x EA**

- Output Voltage: 12 V dc
- Output Current: 16.7 A
- Power Rating: 200 W
- Number of Outputs: 1
- Input Voltage: 120 → 370 V dc, 85 → 264 V ac
- Mounting Type: PCB Mount
- Package Type: Enclosed
- Length: 199 mm



1618219 12 V dc

RS PRO SWITCHING POWER SUPPLY, 24V DC, 8.4A, 200W, 1 OUTPUT

Pack size: **1 x EA**

- Output Voltage: 24 V dc
- Output Current: 8.4 A
- Power Rating: 200 W
- Number of Outputs: 1
- Input Voltage: 120 → 370 V dc, 85 → 264 V ac
- Mounting Type: PCB Mount
- Package Type: Enclosed
- Length: 199 mm



1618221 24 V dc

RS PRO SWITCHING POWER SUPPLY, 36V DC, 5.6A, 200W, 1 OUTPUT

Pack size: 1 x EA

- Output Voltage: 36 V dc
- Output Current: 5.6 A
- Power Rating: 200 W
- Number of Outputs: 1
- Input Voltage: 120 → 370 V dc, 85 → 264 V ac
- Mounting Type: PCB Mount
- Package Type: Enclosed
- Length: 199 mm



1618222 36 V dc

RS PRO SWITCHING POWER SUPPLY, 48V DC, 4.2A, 200W, 1 OUTPUT

Pack size: 1 x EA

- Output Voltage: 48 V dc
- Output Current: 4.2 A
- Power Rating: 200 W
- Number of Outputs: 1
- Input Voltage: 120 → 370 V dc, 85 → 264 V ac
- Mounting Type: PCB Mount
- Package Type: Enclosed
- Length: 199 mm



1618223 48 V dc

RS PRO SWITCHING POWER SUPPLY, 48V DC, 5A, 240W, 1 OUTPUT

Pack size: 1 x EA

- Output Voltage: 48 V dc
- Output Current: 5 A
- Power Rating: 240 W
- Number of Outputs: 1
- Input Voltage: 85 → 264 V ac
- Mounting Type: Chassis Mount
- Package Type: Enclosed
- Length: 199 mm



1618227 48 V dc

RS PRO SWITCHING POWER SUPPLY, 24V DC, 10A, 240W, 1 OUTPUT

Pack size: 1 x EA

- Output Voltage: 24 V dc
- Output Current: 10 A
- Power Rating: 240 W
- Number of Outputs: 1
- Input Voltage: 85 → 264 V ac
- Mounting Type: Chassis Mount
- Package Type: Enclosed
- Length: 199 mm



1618226 24 V dc

RS PRO SWITCHING POWER SUPPLY, 12V DC, 25A, 300W, 1 OUTPUT

Pack size: 1 x EA

- Output Voltage: 12 V dc
- Output Current: 25 A
- Power Rating: 300 W
- Number of Outputs: 1
- Input Voltage: 120 → 370 V dc, 90 → 264 V ac
- Mounting Type: PCB Mount
- Package Type: Enclosed
- Length: 199 mm



1618228 12 V dc

RS PRO SWITCHING POWER SUPPLY, 48V DC, 6.7A, 300W, 1 OUTPUT

Pack size: 1 x EA

- Output Voltage: 48 V dc
- Output Current: 6.7 A
- Power Rating: 300 W
- Number of Outputs: 1
- Input Voltage: 120 → 370 V dc, 90 → 264 V ac
- Mounting Type: PCB Mount
- Package Type: Enclosed
- Length: 199 mm



1618230 48 V dc

RS PRO SWITCHING POWER SUPPLY, 24V DC, 13A, 300W, 1 OUTPUT

Pack size: 1 x EA

- Output Voltage: 24 V dc
- Output Current: 13 A
- Power Rating: 300 W
- Number of Outputs: 1
- Input Voltage: 120 → 370 V dc, 90 → 264 V ac
- Mounting Type: PCB Mount
- Package Type: Enclosed
- Length: 199 mm



1618229 24 V dc

RS PRO SWITCHING POWER SUPPLY, 12V DC, 34A, 480W, 1 OUTPUT

Pack size: 1 x EA

- Output Voltage: 12 V dc
- Output Current: 34 A
- Power Rating: 480 W
- Number of Outputs: 1
- Input Voltage: 90 → 264 V ac
- Mounting Type: Chassis Mount
- Package Type: Enclosed
- Length: 218 mm



1618231 12 V dc

RS PRO SWITCHING POWER SUPPLY, 24V DC, 22A, 480W, 1 OUTPUT

Pack size: 1 x EA

- Output Voltage: 24 V dc
- Output Current: 22 A
- Power Rating: 480 W
- Number of Outputs: 1
- Input Voltage: 90 → 264 V ac
- Mounting Type: Chassis Mount
- Package Type: Enclosed
- Length: 218 mm



1618232 24 V dc

RS PRO SWITCHING POWER SUPPLY, 27V DC, 18A, 480W, 1 OUTPUT

Pack size: 1 x EA

- Output Voltage: 27 V dc
- Output Current: 18 A
- Power Rating: 480 W
- Number of Outputs: 1
- Input Voltage: 90 → 264 V ac
- Mounting Type: Chassis Mount
- Package Type: Enclosed
- Length: 218 mm



1618233 27 V dc

RS PRO SWITCHING POWER SUPPLY, 36V DC, 14A, 480W, 1 OUTPUT

Pack size: 1 x EA

- Output Voltage: 36 V dc
- Output Current: 14 A
- Power Rating: 480 W
- Number of Outputs: 1
- Input Voltage: 90 → 264 V ac
- Mounting Type: Chassis Mount
- Package Type: Enclosed
- Length: 218 mm



1618234 36 V dc

RS PRO SWITCHING POWER SUPPLY, 48V DC, 11A, 480W, 1 OUTPUT

Pack size: 1 x EA

- Output Voltage: 48 V dc
- Output Current: 11 A
- Power Rating: 480 W
- Number of Outputs: 1
- Input Voltage: 90 → 264 V ac
- Mounting Type: Chassis Mount
- Package Type: Enclosed
- Length: 218 mm



1618235 48 V dc

RS PRO SWITCHING POWER SUPPLY, 24V DC, 21A, 504W, 1 OUTPUT

Pack size: 1 x EA

- Output Voltage: 24 V dc
- Output Current: 21 A
- Power Rating: 504 W
- Number of Outputs: 1
- Input Voltage: 88 → 264 V ac
- Mounting Type: Chassis Mount
- Package Type: Enclosed
- Length: 183 mm



1618237 24 V dc

RS PRO SWITCHING POWER SUPPLY, 24V DC, 26.5A, 600W, 1 OUTPUT

Pack size: 1 x EA

- Output Voltage: 24 V dc
- Output Current: 26.5 A
- Power Rating: 600 W
- Number of Outputs: 1
- Input Voltage: 90 → 264 V ac
- Mounting Type: Chassis Mount
- Package Type: Enclosed
- Length: 218 mm



1618240 24 V dc

RS PRO SWITCHING POWER SUPPLY, 48V DC, 13.6A, 588W, 1 OUTPUT

Pack size: 1 x EA

- Output Voltage: 48 V dc
- Output Current: 13.6 A
- Power Rating: 588 W
- Number of Outputs: 1
- Input Voltage: 90 → 264 V ac
- Mounting Type: Chassis Mount
- Package Type: Enclosed
- Length: 218 mm



1618242 48 V dc

RS PRO SWITCHING POWER SUPPLY, 24V DC, 27A, 799W, 1 OUTPUT

Pack size: 1 x EA

- Output Voltage: 24 V dc
- Output Current: 27 A
- Power Rating: 799 W
- Number of Outputs: 1
- Input Voltage: 90 → 264 V ac
- Mounting Type: Chassis Mount
- Package Type: Enclosed
- Length: 226 mm



1618243 24 V dc

RS PRO SWITCHING POWER SUPPLY, 27V DC, 23A, 799W, 1 OUTPUT

Pack size: **1 x EA**

- Output Voltage: 27 V dc
- Output Current: 23 A
- Power Rating: 799 W
- Number of Outputs: 1
- Input Voltage: 90 → 264 V ac
- Mounting Type: Chassis Mount
- Package Type: Enclosed
- Length: 226 mm



1618244 27 V dc

RS PRO SWITCHING POWER SUPPLY, 48V DC, 14A, 800W, 1 OUTPUT

Pack size: **1 x EA**

- Output Voltage: 48 V dc
- Output Current: 14 A
- Power Rating: 800 W
- Number of Outputs: 1
- Input Voltage: 90 → 264 V ac
- Mounting Type: Chassis Mount
- Package Type: Enclosed
- Length: 226 mm



1618245 48 V dc

RS PRO SWITCHING POWER SUPPLY, 24V DC, 1KW

Pack size: **1 x EA**

- Output Voltage: 24 V dc
- Power Rating: 1 kW
- Mounting Type: Chassis Mount
- Package Type: Enclosed



1618246 24 V dc

RS PRO SWITCHING POWER SUPPLY, 48V DC, 1KW

Pack size: **1 x EA**

- Output Voltage: 48 V dc
- Power Rating: 1 kW
- Mounting Type: Chassis Mount
- Package Type: Enclosed



1618247 48 V dc

RS PRO SWITCHING POWER SUPPLY, 5V DC, 8A, 40W, 1 OUTPUT

Pack size: **1 x EA**

- Output Voltage: 5 V dc
- Output Current: 8 A
- Power Rating: 40 W
- Number of Outputs: 1
- Input Voltage: 127 → 370 V dc, 90 → 264 V ac
- Mounting Type: Chassis Mount
- Package Type: Open Frame
- Length: 101.6 mm



1618251 5 V dc

RS PRO SWITCHING POWER SUPPLY, 12V DC, 4.5A, 54W, 1 OUTPUT

Pack size: **1 x EA**

- Output Voltage: 12 V dc
- Output Current: 4.5 A
- Power Rating: 54 W
- Number of Outputs: 1
- Input Voltage: 127 → 370 V dc, 90 → 264 V ac
- Mounting Type: Chassis Mount
- Package Type: Open Frame
- Length: 101.6 mm



1618252 12 V dc

RS PRO SWITCHING POWER SUPPLY, 15V DC, 3.6A, 54W, 1 OUTPUT

Pack size: **1 x EA**

- Output Voltage: 15 V dc
- Output Current: 3.6 A
- Power Rating: 54 W
- Number of Outputs: 1
- Input Voltage: 127 → 370 V dc, 90 → 264 V ac
- Mounting Type: Chassis Mount
- Package Type: Open Frame
- Length: 101.6 mm



1618253 15 V dc

RS PRO SWITCHING POWER SUPPLY, 24V DC, 2.5A, 60W, 1 OUTPUT

Pack size: **1 x EA**

- Output Voltage: 24 V dc
- Output Current: 2.5 A
- Power Rating: 60 W
- Number of Outputs: 1
- Input Voltage: 127 → 370 V dc, 90 → 264 V ac
- Mounting Type: Chassis Mount
- Package Type: Open Frame
- Length: 101.6 mm



1618254 24 V dc

RS PRO SWITCHING POWER SUPPLY, 5V DC, 20A, 100W, 1 OUTPUT

Pack size: **1 x EA**

- Output Voltage: 5 V dc
- Output Current: 20 A
- Power Rating: 100 W
- Number of Outputs: 1
- Input Voltage: 90 → 264 V ac
- Mounting Type: Chassis Mount
- Package Type: Open Frame
- Length: 127 mm



1618256 5 V dc

RS PRO SWITCHING POWER SUPPLY, 12V DC, 10.5A, 126W, 1 OUTPUT

Pack size: **1 x EA**

- Output Voltage: 12 V dc
- Output Current: 10.5 A
- Power Rating: 126 W
- Number of Outputs: 1
- Input Voltage: 90 → 264 V ac
- Mounting Type: Chassis Mount
- Package Type: Open Frame
- Length: 127 mm



1618257 12 V dc

RS PRO SWITCHING POWER SUPPLY, 24V DC, 5.2A, 124.8W, 1 OUTPUT

Pack size: **1 x EA**

- Output Voltage: 24 V dc
- Output Current: 5.2 A
- Power Rating: 124.8 W
- Number of Outputs: 1
- Input Voltage: 90 → 264 V ac
- Mounting Type: Chassis Mount
- Package Type: Open Frame
- Length: 127 mm



1618260 24 V dc

RS PRO SWITCHING POWER SUPPLY, 48V DC, 2.6A, 124.8W, 1 OUTPUT

Pack size: **1 x EA**

- Output Voltage: 48 V dc
- Output Current: 2.6 A
- Power Rating: 124.8 W
- Number of Outputs: 1
- Input Voltage: 90 → 264 V ac
- Mounting Type: Chassis Mount
- Package Type: Open Frame
- Length: 127 mm



1618262 48 V dc

RS PRO SWITCHING POWER SUPPLY, 12V DC, 16.6A, 199W, 1 OUTPUT

Pack size: **1 x EA**

- Output Voltage: 12 V dc
- Output Current: 16.6 A
- Power Rating: 199 W
- Number of Outputs: 1
- Input Voltage: 127 → 370 V dc, 90 → 264 V ac
- Mounting Type: Chassis Mount
- Package Type: Open Frame
- Length: 128 mm



1618263 12 V dc

RS PRO SWITCHING POWER SUPPLY, 24V DC, 8.1A, 201.6W, 1 OUTPUT

Pack size: **1 x EA**

- Output Voltage: 24 V dc
- Output Current: 8.1 A
- Power Rating: 201.6 W
- Number of Outputs: 1
- Input Voltage: 127 → 370 V dc, 90 → 264 V ac
- Mounting Type: Chassis Mount
- Package Type: Open Frame
- Length: 128 mm



1618265 24 V dc

RS PRO SWITCHING POWER SUPPLY, 12V DC, 16.7A, 200W, 1 OUTPUT

Pack size: **1 x EA**

- Output Voltage: 12 V dc
- Output Current: 16.7 A
- Power Rating: 200 W
- Number of Outputs: 1
- Input Voltage: 90 → 264 V ac
- Mounting Type: Chassis Mount
- Package Type: Enclosed
- Length: 200 mm



1618269 12 V dc

RS PRO SWITCHING POWER SUPPLY, 24V DC, 8.4A, 200W, 1 OUTPUT

Pack size: **1 x EA**

- Output Voltage: 24 V dc
- Output Current: 8.4 A
- Power Rating: 200 W
- Number of Outputs: 1
- Input Voltage: 90 → 264 V ac
- Mounting Type: Chassis Mount
- Package Type: Enclosed
- Length: 200 mm



1618270 24 V dc

RS PRO SWITCHING POWER SUPPLY, 5V DC, 7A, 35W, 1 OUTPUT

Pack size: **1 x EA**

- Output Voltage: 5 V dc
- Output Current: 7 A
- Power Rating: 35 W
- Number of Outputs: 1
- Mounting Type: Chassis Mount
- Package Type: Enclosed
- Length: 99 mm
- Width: 82 mm



1618272 5 V dc

RS PRO SWITCHING POWER SUPPLY, 15V DC, 2.4A, 36W, 1 OUTPUT

Pack size: **1 x EA**

- Output Voltage: 15 V dc
- Output Current: 2.4 A
- Power Rating: 36 W
- Number of Outputs: 1
- Mounting Type: Chassis Mount
- Package Type: Enclosed
- Length: 99 mm
- Width: 82 mm



1618274 15 V dc

RS PRO SWITCHING POWER SUPPLY, 36V DC, 1A, 36W, 1 OUTPUT

Pack size: **1 x EA**

- Output Voltage: 36 V dc
- Output Current: 1 A
- Power Rating: 36 W
- Number of Outputs: 1
- Mounting Type: Chassis Mount
- Package Type: Enclosed
- Length: 99 mm
- Width: 82 mm



1618276 36 V dc

RS PRO SWITCHING POWER SUPPLY, 48V DC, 800mA, 38W, 1 OUTPUT

Pack size: **1 x EA**

- Output Voltage: 48 V dc
- Output Current: 800 mA
- Power Rating: 38 W
- Number of Outputs: 1
- Mounting Type: Chassis Mount
- Package Type: Enclosed
- Length: 99 mm
- Width: 82 mm



1618277 48 V dc

RS PRO SWITCHING POWER SUPPLY, 15V DC, 51W, 1 OUTPUT

Pack size: **1 x EA**

- Output Voltage: 15 V dc
- Power Rating: 51 W
- Number of Outputs: 1
- Input Voltage: 100 → 240 V ac
- Mounting Type: Chassis Mount
- Package Type: Enclosed
- Length: 99 mm
- Width: 82 mm



1618280 15 V dc

RS PRO SWITCHING POWER SUPPLY, 36V DC, 1.45A, 55W, 1 OUTPUT

Pack size: **1 x EA**

- Output Voltage: 36 V dc
- Output Current: 1.45 A
- Power Rating: 55 W
- Number of Outputs: 1
- Input Voltage: 100 → 240 V ac
- Mounting Type: Chassis Mount
- Package Type: Enclosed
- Length: 99 mm



1618282 36 V dc

RS PRO SWITCHING POWER SUPPLY, 48V DC, 1.1A, 52.8W, 1 OUTPUT

Pack size: **1 x EA**

- Output Voltage: 48 V dc
- Output Current: 1.1 A
- Power Rating: 52.8 W
- Number of Outputs: 1
- Input Voltage: 100 → 240 V ac
- Mounting Type: Chassis Mount
- Package Type: Enclosed
- Length: 99 mm



1618283 48 V dc

RS PRO SWITCHING POWER SUPPLY, 5V DC, 14A, 60W, 1 OUTPUT

Pack size: **1 x EA**

- Output Voltage: 5 V dc
- Output Current: 14 A
- Power Rating: 60 W
- Number of Outputs: 1
- Input Voltage: 100 → 240 V ac
- Mounting Type: Chassis Mount
- Package Type: Enclosed
- Length: 97 mm



1618284 5 V dc

RS PRO SWITCHING POWER SUPPLY, 12V DC, 6A, 72W, 1 OUTPUT

Pack size: **1 x EA**

- Output Voltage: 12 V dc
- Output Current: 6 A
- Power Rating: 72 W
- Number of Outputs: 1
- Input Voltage: 100 → 240 V ac
- Mounting Type: Chassis Mount
- Package Type: Enclosed
- Length: 97 mm



1618285 12 V dc

RS PRO SWITCHING POWER SUPPLY, 24V DC, 3.2A, 76.8W, 1 OUTPUT

Pack size: **1 x EA**

- Output Voltage: 24 V dc
- Output Current: 3.2 A
- Power Rating: 76.8 W
- Number of Outputs: 1
- Input Voltage: 100 → 240 V ac
- Mounting Type: Chassis Mount
- Package Type: Enclosed
- Length: 97 mm



1618288 24 V dc

RS PRO SWITCHING POWER SUPPLY, 36V DC, 2.1A, 75.6W, 1 OUTPUT

Pack size: **1 x EA**

- Output Voltage: 36 V dc
- Output Current: 2.1 A
- Power Rating: 75.6 W
- Number of Outputs: 1
- Input Voltage: 100 → 240 V ac
- Mounting Type: Chassis Mount
- Package Type: Enclosed
- Length: 97 mm



1618289 36 V dc

RS PRO SWITCHING POWER SUPPLY, 48V DC, 1.6A, 76.8W, 1 OUTPUT

Pack size: **1 x EA**

- Output Voltage: 48 V dc
- Output Current: 1.6 A
- Power Rating: 76.8 W
- Number of Outputs: 1
- Input Voltage: 100 → 240 V ac
- Mounting Type: Chassis Mount
- Package Type: Enclosed
- Length: 97 mm



1618290 48 V dc

RS PRO SWITCHING POWER SUPPLY, 15V DC, 105W, 1 OUTPUT

Pack size: **1 x EA**

- Output Voltage: 15 V dc
- Power Rating: 105 W
- Number of Outputs: 1
- Input Voltage: 85 → 264 V ac
- Mounting Type: Chassis Mount
- Package Type: Enclosed
- Length: 129 mm
- Width: 97 mm



1618293 15 V dc

RS PRO SWITCHING POWER SUPPLY, 36V DC, 2.8A, 101W, 1 OUTPUT

Pack size: **1 x EA**

- Output Voltage: 36 V dc
- Output Current: 2.8 A
- Power Rating: 101 W
- Number of Outputs: 1
- Input Voltage: 85 → 264 V ac
- Mounting Type: Chassis Mount
- Package Type: Enclosed
- Length: 129 mm



1618295 36 V dc

RS PRO SWITCHING POWER SUPPLY, 48V DC, 2.3A, 110W, 1 OUTPUT

Pack size: **1 x EA**

- Output Voltage: 48 V dc
- Output Current: 2.3 A
- Power Rating: 110 W
- Number of Outputs: 1
- Input Voltage: 85 → 264 V ac
- Mounting Type: Chassis Mount
- Package Type: Enclosed
- Length: 129 mm



1618296 48 V dc

RS PRO SWITCHING POWER SUPPLY, 12V DC, 12.5A, 150W, 1 OUTPUT

Pack size: **1 x EA**

- Output Voltage: 12 V dc
- Output Current: 12.5 A
- Power Rating: 150 W
- Number of Outputs: 1
- Input Voltage: 170 → 264 V ac, 85 → 132 V ac
- Mounting Type: Chassis Mount
- Package Type: Enclosed
- Length: 159 mm



1618297 12 V dc

RS PRO SWITCHING POWER SUPPLY, 15V DC, 150W, 1 OUTPUT

Pack size: **1 x EA**

- Output Voltage: 15 V dc
- Power Rating: 150 W
- Number of Outputs: 1
- Input Voltage: 170 → 264 V ac, 85 → 132 V ac
- Mounting Type: Chassis Mount
- Package Type: Enclosed
- Length: 99 mm
- Width: 82 mm



1618298 15 V dc

RS PRO SWITCHING POWER SUPPLY, 24V DC, 6.5A, 156W, 1 OUTPUT

Pack size: **1 x EA**

- Output Voltage: 24 V dc
- Output Current: 6.5 A
- Power Rating: 156 W
- Number of Outputs: 1
- Input Voltage: 170 → 264 V ac, 85 → 132 V ac
- Mounting Type: Chassis Mount
- Package Type: Enclosed
- Length: 159 mm



1618299 24 V dc

RS PRO SWITCHING POWER SUPPLY, 36V DC, 4.3A, 155W, 1 OUTPUT

Pack size: **1 x EA**

- Output Voltage: 36 V dc
- Output Current: 4.3 A
- Power Rating: 155 W
- Number of Outputs: 1
- Input Voltage: 170 → 264 V ac, 85 → 132 V ac
- Mounting Type: Chassis Mount
- Package Type: Enclosed
- Length: 99 mm



1618300 36 V dc

RS PRO SWITCHING POWER SUPPLY, 48V DC, 3.3A, 158W, 1 OUTPUT

Pack size: **1 x EA**

- Output Voltage: 48 V dc
- Output Current: 3.3 A
- Power Rating: 158 W
- Number of Outputs: 1
- Input Voltage: 170 → 264 V ac, 85 → 132 V ac
- Mounting Type: Chassis Mount
- Package Type: Enclosed
- Length: 99 mm



1618301 48 V dc

RS PRO SWITCHING POWER SUPPLY, 5V DC, 600MA, 3W, 1 OUTPUT

Pack size: **1 x EA**

- Output Voltage: 5 V dc
- Output Current: 600 mA
- Power Rating: 3 W
- Number of Outputs: 1
- Input Voltage: 110 → 370 V dc, 85 → 264 V ac
- Mounting Type: PCB Mount
- Package Type: Encapsulated
- Length: 37 mm



6675760 5 V dc

RS PRO SWITCHING POWER SUPPLY, 12V DC, 250MA, 3W, 1 OUTPUT

Pack size: **1 x EA**

- Output Voltage: 12 V dc
- Output Current: 250 mA
- Power Rating: 3 W
- Number of Outputs: 1
- Input Voltage: 110 → 370 V dc, 85 → 264 V ac
- Mounting Type: PCB Mount
- Package Type: Encapsulated
- Length: 37 mm



6675773 12 V dc

RS PRO SWITCHING POWER SUPPLY, 9V DC, 330MA, 3W, 1 OUTPUT

Pack size: **1 x EA**

- Output Voltage: 9 V dc
- Output Current: 330 mA
- Power Rating: 3 W
- Number of Outputs: 1
- Input Voltage: 110 → 370 V dc, 85 → 264 V ac
- Mounting Type: PCB Mount
- Package Type: Encapsulated
- Length: 37 mm



6675764 9 V dc

RS PRO SWITCHING POWER SUPPLY, 5V DC, 1A, 5W, 1 OUTPUT

Pack size: **1 x EA**

- Output Voltage: 5 V dc
- Output Current: 1 A
- Power Rating: 5 W
- Number of Outputs: 1
- Input Voltage: 110 → 370 V dc, 85 → 264 V ac
- Mounting Type: PCB Mount
- Package Type: Encapsulated
- Length: 50.8 mm



6675789 5 V dc

RS PRO SWITCHING POWER SUPPLY, 24V DC, 2.5A, 60W, 1 OUTPUT

Pack size: **1 x EA**

- Output Voltage: 24 V dc
- Output Current: 2.5 A
- Power Rating: 60 W
- Number of Outputs: 1
- Input Voltage: 88 → 264 V ac
- Mounting Type: Chassis Mount
- Package Type: Enclosed
- Length: 98 mm



7112636 24 V dc

RS PRO SWITCHING POWER SUPPLY, 24V DC, 1.25A, 30W, 1 OUTPUT

Pack size: **1 x EA**

- Output Voltage: 24 V dc
- Output Current: 1.25 A
- Power Rating: 30 W
- Number of Outputs: 1
- Input Voltage: 85 → 265 V ac
- Mounting Type: PCB Mount
- Package Type: Enclosed
- Length: 89 mm



7511421 24 V dc

RS PRO SWITCHING POWER SUPPLY, 24V DC, 625MA, 15W, 1 OUTPUT

Pack size: **1 x EA**

- Output Voltage: 24 V dc
- Output Current: 625 mA
- Power Rating: 15 W
- Number of Outputs: 1
- Input Voltage: 120 → 375 V dc, 85 → 265 V ac
- Mounting Type: PCB Mount
- Package Type: Enclosed
- Length: 76.2 mm



7719436 24 V dc

RS PRO SWITCHING REGULATOR, SURFACE MOUNT, 3.3V DC OUTPUT

Pack size: **1 x EA**

- Output Voltage: 3.3 V dc
- Input Voltage: 4.75 → 36 V dc
- Output Current: 500 mA
- Mounting Type: Surface Mount
- Number of Outputs: 1
- Package: SMD
- Efficiency: 86/80 %
- Ripple And Noise: 50 mV Pk-Pk



1933954 3.3 V dc

RS PRO SWITCHING REGULATOR, SURFACE MOUNT, 5V DC OUTPUT

Pack size: **1 x EA**

- Output Voltage: 5 V dc
- Input Voltage: 6.5 → 36 V dc
- Output Current: 500 mA
- Mounting Type: Surface Mount
- Number of Outputs: 1
- Package: SMD
- Efficiency: 90/84 %
- Ripple And Noise: 50 mV Pk-Pk



1933956 5 V dc

RS PRO SWITCHING REGULATOR, PCB MOUNT, 3.3V DC OUTPUT

Pack size: **1 x EA**

- Output Voltage: 3.3 V dc
- Input Voltage: 4.75 → 36 V dc
- Output Current: 500 mA
- Mounting Type: PCB Mount
- Number of Outputs: 1
- Efficiency: 86/80 %
- Ripple And Noise: 75 mV Pk-Pk
- Minimum Temperature: -40 °C



1933966 3.3 V dc

RS PRO SWITCHING REGULATOR, PCB MOUNT, 5V DC OUTPUT

Pack size: **1 x EA**

- Output Voltage: 5 V dc
- Input Voltage: 6.5 → 36 V dc
- Output Current: 500 mA
- Mounting Type: PCB Mount
- Number of Outputs: 1
- Efficiency: 90/84 %
- Ripple And Noise: 75 mV Pk-Pk
- Minimum Temperature: -40 °C



1933969 5 V dc

RS PRO SWITCHING REGULATOR, PCB MOUNT, 12V DC OUTPUT

Pack size: **1 x EA**

- Output Voltage: 12 V dc
- Input Voltage: 15 → 36 V dc
- Output Current: 500 mA
- Mounting Type: PCB Mount
- Number of Outputs: 1
- Efficiency: 94/91 %
- Ripple And Noise: 75 mV Pk-Pk
- Minimum Temperature: -40 °C



1933971 12 V dc

RS PRO SWITCHING REGULATOR, PCB MOUNT, 3.3V DC OUTPUT

Pack size: **1 x EA**

- Output Voltage: 3.3 V dc
- Input Voltage: 4.75 → 36 V dc
- Output Current: 500 mA
- Mounting Type: PCB Mount
- Number of Outputs: 1
- Efficiency: 86/80 %
- Ripple And Noise: 75 mV Pk-Pk
- Minimum Temperature: -40 °C



1933974 3.3 V dc

RS PRO SWITCHING REGULATOR, PCB MOUNT, 5V DC OUTPUT

Pack size: **1 x EA**

- Output Voltage: 5 V dc
- Input Voltage: 6.5 → 36 V dc
- Output Current: 500 mA
- Mounting Type: PCB Mount
- Number of Outputs: 1
- Efficiency: 90/84 %
- Ripple And Noise: 75 mV Pk-Pk
- Minimum Temperature: -40 °C



1933976 5 V dc

RS PRO SWITCHING REGULATOR, PCB MOUNT, 9V DC OUTPUT

Pack size: **1 x EA**

- Output Voltage: 9 V dc
- Input Voltage: 12 → 36 V dc
- Output Current: 500 mA
- Mounting Type: PCB Mount
- Number of Outputs: 1
- Efficiency: 93/90 %
- Ripple And Noise: 75 mV Pk-Pk
- Minimum Temperature: -40 °C



1933978 9 V dc

RS PRO SWITCHING REGULATOR, PCB MOUNT, 12V DC OUTPUT

Pack size: **1 x EA**

- Output Voltage: 12 V dc
- Input Voltage: 15 → 36 V dc
- Output Current: 500 mA
- Mounting Type: PCB Mount
- Number of Outputs: 1
- Efficiency: 94/91 %
- Ripple And Noise: 75 mV Pk-Pk
- Minimum Temperature: -40 °C



1933980 12 V dc

RS PRO SWITCHING REGULATOR, 5V DC OUTPUT VOLTAGE, 6.5 → 36V DC

Pack size: **1 x EA**

- Output Voltage: 5 V dc
- Input Voltage: 6.5 → 36 V dc
- Output Current: 500 mA
- Number of Outputs: 1
- Efficiency: 90/84 %
- Ripple And Noise: 75 mV Pk-Pk
- Minimum Temperature: -40 °C
- Maximum Temperature: +85 °C



1933984 5 V dc

RS PRO SWITCHING REGULATOR, PCB MOUNT, 5V DC OUTPUT

Pack size: **1 x EA**

- Output Voltage: 5 V dc
- Input Voltage: 8 → 36 V dc
- Output Current: 1 A
- Mounting Type: PCB Mount
- Number of Outputs: 1
- Efficiency: 93/86 %
- Ripple And Noise: 75 mV Pk-Pk
- Minimum Temperature: -40 °C



1933998 5 V dc

RS PRO SWITCHING REGULATOR, PCB MOUNT, 12V DC OUTPUT

Pack size: **1 x EA**

- Output Voltage: 12 V dc
- Input Voltage: 16 → 36 V dc
- Output Current: 1 A
- Mounting Type: PCB Mount
- Number of Outputs: 1
- Efficiency: 95/92 %
- Ripple And Noise: 75 mV Pk-Pk
- Minimum Temperature: -40 °C



1934000 12 V dc

RS PRO SWITCHING REGULATOR, PCB MOUNT, 3.3V DC OUTPUT

Pack size: **1 x EA**

- Output Voltage: 3.3 V dc
- Input Voltage: 6 → 36 V dc
- Output Current: 1 A
- Mounting Type: PCB Mount
- Number of Outputs: 1
- Efficiency: 90/80 %
- Ripple And Noise: 75 mV Pk-Pk
- Minimum Temperature: -40 °C



1934002 3.3 V dc

RS PRO SWITCHING REGULATOR, PCB MOUNT, 5V DC OUTPUT

Pack size: **1 x EA**

- Output Voltage: 5 V dc
- Input Voltage: 8 → 36 V dc
- Output Current: 1 A
- Mounting Type: PCB Mount
- Number of Outputs: 1
- Efficiency: 93/85 %
- Ripple And Noise: 75 mV Pk-Pk
- Minimum Temperature: -40 °C



1934004 5 V dc

RS PRO SWITCHING REGULATOR, PCB MOUNT, 6.5V DC OUTPUT

Pack size: **1 x EA**

- Output Voltage: 6.5 V dc
- Input Voltage: 10 → 36 V dc
- Output Current: 1 A
- Mounting Type: PCB Mount
- Number of Outputs: 1
- Efficiency: 93/85 %
- Ripple And Noise: 75 mV Pk-Pk
- Maximum Temperature: +85 °C



1934006 6.5 V dc

RS PRO SWITCHING REGULATOR, PCB MOUNT, 9V DC OUTPUT

Pack size: **1 x EA**

- Output Voltage: 9 V dc
- Input Voltage: 13 → 36 V dc
- Output Current: 1 A
- Mounting Type: PCB Mount
- Number of Outputs: 1
- Efficiency: 94/89 %
- Ripple And Noise: 75 mV Pk-Pk
- Minimum Temperature: -40 °C



1934008 9 V dc

RS PRO SWITCHING REGULATOR, PCB MOUNT, 12V DC OUTPUT

Pack size: **1 x EA**

- Output Voltage: 12 V dc
- Input Voltage: 16 → 36 V dc
- Output Current: 1 A
- Mounting Type: PCB Mount
- Number of Outputs: 1
- Efficiency: 95/92 %
- Ripple And Noise: 75 mV Pk-Pk
- Minimum Temperature: -40 °C



1934010 12 V dc

RS PRO SWITCHING REGULATOR, PCB MOUNT, 3.3V DC OUTPUT

Pack size: **1 x EA**

- Output Voltage: 3.3 V dc
- Input Voltage: 6 → 36 V dc
- Output Current: 1 A
- Mounting Type: PCB Mount
- Number of Outputs: 1
- Efficiency: 90/81 %
- Ripple And Noise: 75 mV Pk-Pk
- Minimum Temperature: -40 °C



1934013 3.3 V dc

RS PRO SWITCHING REGULATOR, PCB MOUNT, 5V DC OUTPUT

Pack size: **44 x EA**

- Output Voltage: 5 V dc
- Input Voltage: 8 → 36 V dc
- Output Current: 1 A
- Mounting Type: PCB Mount
- Number of Outputs: 1
- Efficiency: 93/86 %
- Ripple And Noise: 75 mV Pk-Pk
- Maximum Temperature: +85 °C



1934014 5 V dc

RS PRO SWITCHING REGULATOR, PCB MOUNT, 5V DC OUTPUT

Pack size: **1 x EA**

- Output Voltage: 5 V dc
- Input Voltage: 8 → 36 V dc
- Output Current: 1 A
- Mounting Type: PCB Mount
- Number of Outputs: 1
- Efficiency: 93/86 %
- Ripple And Noise: 75 mV Pk-Pk
- Maximum Temperature: +85 °C



1934015 5 V dc

RS PRO SWITCHING REGULATOR, PCB MOUNT, 9V DC OUTPUT

Pack size: **1 x EA**

- Output Voltage: 9 V dc
- Input Voltage: 13 → 36 V dc
- Output Current: 1 A
- Mounting Type: PCB Mount
- Number of Outputs: 1
- Efficiency: 95/90 %
- Ripple And Noise: 75 mV Pk-Pk
- Minimum Temperature: -40 °C



1934017 9 V dc

RS PRO SWITCHING REGULATOR, PCB MOUNT, 12V DC OUTPUT

Pack size: **1 x EA**

- Output Voltage: 12 V dc
- Input Voltage: 16 → 36 V dc
- Output Current: 1 A
- Mounting Type: PCB Mount
- Number of Outputs: 1
- Efficiency: 96/93 %
- Ripple And Noise: 75 mV Pk-Pk
- Minimum Temperature: -40 °C



1934019 12 V dc

RS PRO SWITCHING REGULATOR, PCB MOUNT, 15V DC OUTPUT

Pack size: **1 x EA**

- Output Voltage: 15 V dc
- Input Voltage: 18 → 36 V dc
- Output Current: 1 A
- Mounting Type: PCB Mount
- Number of Outputs: 1
- Efficiency: 96/94 %
- Ripple And Noise: 75 mV Pk-Pk
- Minimum Temperature: -40 °C



1934021 15 V dc

RS PRO SWITCHING REGULATOR, PCB MOUNT, 3.3V DC OUTPUT

Pack size: **1 x EA**

- Output Voltage: 3.3 V dc
- Input Voltage: 6 → 36 V dc
- Output Current: 1 A
- Mounting Type: PCB Mount
- Number of Outputs: 1
- Efficiency: 90/81 %
- Ripple And Noise: 75 mV Pk-Pk
- Minimum Temperature: -40 °C



1934023 3.3 V dc

RS PRO SWITCHING REGULATOR, PCB MOUNT, 5V DC OUTPUT

Pack size: **44 x EA**

- Output Voltage: 5 V dc
- Input Voltage: 8 → 36 V dc
- Output Current: 1 A
- Mounting Type: PCB Mount
- Number of Outputs: 1
- Efficiency: 93/86 %
- Ripple And Noise: 75 mV Pk-Pk
- Minimum Temperature: -40 °C



1934024 5 V dc

RS PRO SWITCHING REGULATOR, PCB MOUNT, 5V DC OUTPUT

Pack size: **1 x EA**

- Output Voltage: 5 V dc
- Input Voltage: 8 → 36 V dc
- Output Current: 1 A
- Mounting Type: PCB Mount
- Number of Outputs: 1
- Efficiency: 93/86 %
- Ripple And Noise: 75 mV Pk-Pk
- Minimum Temperature: -40 °C



1934025 5 V dc

RS PRO SWITCHING REGULATOR, PCB MOUNT, 12V DC OUTPUT

Pack size: **1 x EA**

- Output Voltage: 12 V dc
- Input Voltage: 16 → 36 V dc
- Output Current: 1 A
- Mounting Type: PCB Mount
- Number of Outputs: 1
- Efficiency: 96/93 %
- Ripple And Noise: 75 mV Pk-Pk
- Minimum Temperature: -40 °C



1934028 12 V dc

RS PRO SWITCHING REGULATOR, PCB MOUNT, 3.3V DC OUTPUT

Pack size: **1 x EA**

- Output Voltage: 3.3 V dc
- Input Voltage: 6 → 36 V dc
- Output Current: 2 A
- Mounting Type: PCB Mount
- Number of Outputs: 1
- Efficiency: 89/85 %
- Ripple And Noise: 75 mV Pk-Pk
- Minimum Temperature: -40 °C



1934030 3.3 V dc

RS PRO SWITCHING REGULATOR, PCB MOUNT, 5V DC OUTPUT

Pack size: **44 x EA**

- Output Voltage: 5 V dc
- Input Voltage: 8 → 36 V dc
- Output Current: 2 A
- Mounting Type: PCB Mount
- Number of Outputs: 1
- Efficiency: 92/89 %
- Ripple And Noise: 75 mV Pk-Pk
- Minimum Temperature: -40 °C



1934031 5 V dc

RS PRO SWITCHING REGULATOR, PCB MOUNT, 5V DC OUTPUT

Pack size: **1 x EA**

- Output Voltage: 5 V dc
- Input Voltage: 8 → 36 V dc
- Output Current: 2 A
- Mounting Type: PCB Mount
- Number of Outputs: 1
- Efficiency: 92/89 %
- Ripple And Noise: 75 mV Pk-Pk
- Minimum Temperature: -40 °C



1934032 5 V dc

RS PRO SWITCHING REGULATOR, PCB MOUNT, 9V DC OUTPUT

Pack size: **1 x EA**

- Output Voltage: 9 V dc
- Input Voltage: 13 → 36 V dc
- Output Current: 2 A
- Mounting Type: PCB Mount
- Number of Outputs: 1
- Efficiency: 95/92 %
- Ripple And Noise: 75 mV Pk-Pk
- Minimum Temperature: -40 °C



1934035 9 V dc

RS PRO SWITCHING REGULATOR, PCB MOUNT, 12V DC OUTPUT

Pack size: **1 x EA**

- Output Voltage: 12 V dc
- Input Voltage: 16 → 36 V dc
- Output Current: 2 A
- Mounting Type: PCB Mount
- Number of Outputs: 1
- Efficiency: 96/94 %
- Ripple And Noise: 75 mV Pk-Pk
- Maximum Temperature: +85 °C



1934037 12 V dc

RS PRO SWITCHING REGULATOR, PCB MOUNT, 3.3V DC OUTPUT

Pack size: **1 x EA**

- Output Voltage: 3.3 V dc
- Input Voltage: 8 → 36 V dc
- Output Current: 2 A
- Mounting Type: PCB Mount
- Number of Outputs: 1
- Efficiency: 92/89 %
- Ripple And Noise: 75 mV Pk-Pk
- Maximum Temperature: +85 °C



1934041 3.3 V dc

RS PRO SWITCHING REGULATOR, PCB MOUNT, 5V DC OUTPUT

Pack size: **1 x EA**

- Output Voltage: 5 V dc
- Input Voltage: 8 → 36 V dc
- Output Current: 2 A
- Mounting Type: PCB Mount
- Number of Outputs: 1
- Efficiency: 92/89 %
- Ripple And Noise: 75 mV Pk-Pk
- Minimum Temperature: -40 °C



1934043 5 V dc

RS PRO SWITCHING REGULATOR, PCB MOUNT, 12V DC OUTPUT

Pack size: **1 x EA**

- Output Voltage: 12 V dc
- Input Voltage: 16 → 36 V dc
- Output Current: 2 A
- Mounting Type: PCB Mount
- Number of Outputs: 1
- Efficiency: 96/94 %
- Ripple And Noise: 75 mV Pk-Pk
- Minimum Temperature: -40 °C



1934045 12 V dc

RS PRO VERTICAL PP FLOAT SWITCH, FLOAT, 300MM CABLE, DIRECT LOAD,

Pack size: **1 x EA**

- Device Type: Float
- Mounting Type: Vertical
- Switch Output: Direct Load
- Body Material: PP
- Cable Length: 300 mm
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +80 °C
- Maximum AC Voltage: 250 V



519232 Float

RS PRO VERTICAL PP FLOAT SWITCH, FLOAT, 300MM CABLE, DIRECT LOAD,

Pack size: **1 x EA**

- Device Type: Float
- Mounting Type: Vertical
- Switch Output: Direct Load
- Body Material: PP
- Cable Length: 300 mm
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +80 °C
- Maximum AC Voltage: 140 V



519236 Float

RS PRO VERTICAL PP FLOAT SWITCH, FLOAT, 300MM CABLE, DIRECT LOAD,

Pack size: **1 x EA**

- Device Type: Float
- Mounting Type: Vertical
- Switch Output: Direct Load
- Body Material: PP
- Cable Length: 300 mm
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +80 °C
- Maximum AC Voltage: 130 V



519248 Float

RS PRO VERTICAL PP FLOAT SWITCH, FLOAT, 300MM CABLE, DIRECT LOAD,

Pack size: **1 x EA**

- Device Type: Float
- Mounting Type: Vertical
- Switch Output: Direct Load
- Body Material: PP
- Cable Length: 300 mm
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +80 °C
- Maximum AC Voltage: 140 V



519242 Float

RS PRO VERTICAL PP FLOAT SWITCH, FLOAT, 300MM CABLE, DIRECT LOAD,

Pack size: **1 x EA**

- Device Type: Float
- Mounting Type: Vertical
- Switch Output: Direct Load
- Body Material: PP
- Cable Length: 300 mm
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +80 °C
- Maximum AC Voltage: 250 V



519258 Float

RS PRO VERTICAL STAINLESS STEEL FLOAT SWITCH, FLOAT, 300MM

Pack size: **1 x EA**

- Device Type: Float
- Mounting Type: Vertical
- Switch Output: Direct Load
- Body Material: Stainless Steel
- Cable Length: 300 mm
- Minimum Operating Temperature: -10 °C
- Maximum Operating Temperature: +120 °C
- Maximum AC Voltage: 300 V



3127164 Float

RS PRO FLANGE MOUNT ALUMINIUM (ENCLOSURE), SS 316L (FLOAT) FLOAT

Pack size: **1 x EA**

- Device Type: Float
- Mounting Type: Flange Mount
- Switch Output: SPDT
- Body Material: Aluminium (Enclosure), SS 316L (Float)
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: +130 °C
- Maximum AC Voltage: 250 V
- Maximum DC Voltage: 30 V



1880316 Float

RS PRO HORIZONTAL STAINLESS STEEL FLOAT SWITCH, FLOAT, 300MM

Pack size: **1 x EA**

- Device Type: Float
- Mounting Type: Horizontal
- Switch Output: Direct Load
- Body Material: Stainless Steel
- Cable Length: 300 mm
- Minimum Operating Temperature: -10 °C
- Maximum Operating Temperature: +120 °C
- Maximum AC Voltage: 300 V



2356204 Float

RS PRO HORIZONTAL STAINLESS STEEL FLOAT SWITCH, FLOAT, 300MM

Pack size: **1 x EA**

- Device Type: Float
- Mounting Type: Horizontal
- Switch Output: NO
- Body Material: Stainless Steel
- Cable Length: 300 mm
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +125 °C
- Maximum AC Voltage: 250 V



7621039 Float

RS PRO VERTICAL STAINLESS STEEL FLOAT SWITCH, FLOAT, 300MM

Pack size: **1 x EA**

- Device Type: Float
- Mounting Type: Vertical
- Switch Output: NO/NC
- Body Material: Stainless Steel
- Cable Length: 300 mm
- Minimum Operating Temperature: -40 °C
- Maximum Operating Temperature: +125 °C
- Maximum AC Voltage: 250 V



7621036 Float

RS PRO RADIAL FLOW TURBINE FLOW METER FOR LIQUID, 1.5 L/MIN MIN, 30

Pack size: **1 x EA**

- Media Monitored: Liquid
- Device Type: Radial Flow Turbine
- Minimum Flow Rate: 1.5 L/min
- Maximum Flow Rate: 30 L/min
- Supply Voltage: 4.5 → 16 V dc
- Pipe Diameter Range: 15 mm
- Maximum Pressure: 20 bar
- Material: Acetal Copolymer



257133 Liquid

RS PRO RADIAL FLOW TURBINE FLOW METER FOR LIQUID, 0.25 L/MIN MIN,

Pack size: **1 x EA**

- Media Monitored: Liquid
- Device Type: Radial Flow Turbine
- Minimum Flow Rate: 0.25 L/min
- Maximum Flow Rate: 6.5 L/min
- Supply Voltage: 4.5 → 16 V dc
- Pipe Diameter Range: 15 mm
- Maximum Pressure: 20 bar
- Material: Acetal Copolymer



257149 Liquid

RS PRO OVAL GEAR FLOW METER FOR LIQUID, 0.01 L/MIN MIN, 1 L/MIN

Pack size: **1 x EA**

- Media Monitored: Liquid
- Device Type: Oval Gear
- Minimum Flow Rate: 0.01 L/min
- Maximum Flow Rate: 1 L/min
- Supply Voltage: 5 → 24 V dc
- Pipe Diameter Range: 1/4 in
- Connection Type: 1/4 BSP
- Maximum Pressure: 50 bar



4474427 Liquid

RS PRO OVAL GEAR FLOW METER FOR LIQUID, 0.01 L/MIN MIN, 4 L/MIN

Pack size: **1 x EA**

- Media Monitored: Liquid
- Device Type: Oval Gear
- Minimum Flow Rate: 0.01 L/min
- Maximum Flow Rate: 4 L/min
- Supply Voltage: 5 → 24 V dc
- Pipe Diameter Range: 1/4 in
- Connection Type: 1/4 BSP
- Maximum Pressure: 50 bar



4474449 Liquid

RS PRO FLOW METER, 0.05 → 10 L/MIN MAX

Pack size: **1 x EA**

- Maximum Flow Rate: 0.05 → 10 L/min
- Supply Voltage: 4.5 → 24 V dc
- Pipe Diameter Range: 8 mm
- Minimum Operating Temperature: -25 °C
- Maximum Operating Temperature: +125 °C
- Current Rating: 8 mA



5082704 0.05 → 10 L/min

RS PRO PISTON INLINE FLOW SWITCH FOR LIQUID, 0.04 L/MIN MIN, 0.13

Pack size: **1 x EA**

- Media Monitored: Liquid
- Device Type: Piston Inline
- Minimum Flow Rate: 0.04 L/min
- Maximum Flow Rate: 0.13 L/min
- Supply Voltage: 200 V ac
- Pipe Diameter Range: 1/4 in
- Connection Type: 1/4 BSP
- Maximum Pressure: 300 bar



5100559 Liquid

RS PRO PISTON INLINE FLOW SWITCH FOR LIQUID, 0.1 L/MIN MIN, 0.6 L/MIN

Pack size: **1 x EA**

- Media Monitored: Liquid
- Device Type: Piston Inline
- Minimum Flow Rate: 0.1 L/min
- Maximum Flow Rate: 0.6 L/min
- Supply Voltage: 200 V ac
- Pipe Diameter Range: 1/4 in
- Connection Type: 1/4 BSP
- Maximum Pressure: 300 bar



5100565 Liquid

RS PRO PISTON INLINE FLOW SWITCH FOR LIQUID, 0.5 L/MIN MIN, 3 L/MIN

Pack size: **1 x EA**

- Media Monitored: Liquid
- Device Type: Piston Inline
- Minimum Flow Rate: 0.5 L/min
- Maximum Flow Rate: 3 L/min
- Supply Voltage: 200 V ac
- Pipe Diameter Range: 1/4 in
- Connection Type: 1/4 BSP
- Maximum Pressure: 300 bar



5100571 Liquid

RS PRO FLOW METER, 2.5 → 30.0 L/MIN

Pack size: **1 x EA**

- Maximum Flow Rate: 2.5 → 30.0 L/min
- Supply Voltage: 4.5 → 24 V dc
- Pipe Diameter Range: 1/2 in
- Minimum Operating Temperature: -25 °C
- Maximum Operating Temperature: +125 °C
- Current Rating: 10 mA



5113909 2.5 → 30.0 L/min

RS PRO FLOW METER, 6 → 100 L/MIN MAX

Pack size: **1 x EA**

- Maximum Flow Rate: 6 → 100 L/min
- Supply Voltage: 4.5 → 24 V dc
- Pipe Diameter Range: 3/4 in
- Minimum Operating Temperature: -25 °C
- Maximum Operating Temperature: +125 °C
- Current Rating: 10 mA



5113915 6 → 100 L/min

RS PRO TURBINE FLOW METER FOR LIQUID, 0.25 L/MIN MIN, 6.5 L/MIN

Pack size: **1 x EA**

- Media Monitored: Liquid
- Device Type: Turbine
- Minimum Flow Rate: 0.25 L/min
- Maximum Flow Rate: 6.5 L/min
- Supply Voltage: 4.5 → 24 V dc
- Pipe Diameter Range: 1/4 in
- Connection Type: 1/4 BSP
- Maximum Pressure: 10 bar



5113965 Liquid

RS PRO TURBINE FLOW METER FOR LIQUID, 0.5 L/MIN MIN, 15 L/MIN MAX

Pack size: **1 x EA**

- Media Monitored: Liquid
- Device Type: Turbine
- Minimum Flow Rate: 0.5 L/min
- Maximum Flow Rate: 15 L/min
- Supply Voltage: 4.5 → 24 V dc
- Pipe Diameter Range: 1/2 in
- Connection Type: 1/2 BSP
- Maximum Pressure: 10 bar



5113971 Liquid

RS PRO FLOW METER FOR LIQUID, 0.6 L/MIN MIN, 10 L/MIN MAX

Pack size: **1 x EA**

- Media Monitored: Liquid
- Device Type: Beverage
- Minimum Flow Rate: 0.6 L/min
- Maximum Flow Rate: 10 L/min
- Supply Voltage: 4.5 → 24 V dc
- Pipe Diameter Range: 43315 in
- Connection Type: 3/8 Push On
- Maximum Pressure: 10 bar



5114772 Liquid

RS PRO PADDLE FLOW SWITCH FOR GAS, LIQUID, 4 L/MIN MIN, 5.5 L/MIN

Pack size: **1 x EA**

- Media Monitored: Gas, Liquid
- Device Type: Paddle
- Minimum Flow Rate: 4 L/min
- Maximum Flow Rate: 5.5 L/min
- Supply Voltage: 250 V ac
- Pipe Diameter Range: 10 mm
- Connection Type: 3/8 BSP Female
- Maximum Pressure: 25 bar



6134216 Gas, Liquid

RS PRO PADDLE FLOW SWITCH FOR GAS, LIQUID, 5.5 L/MIN MIN, 7 L/MIN

Pack size: **1 x EA**

- Media Monitored: Gas, Liquid
- Device Type: Paddle
- Minimum Flow Rate: 5.5 L/min
- Maximum Flow Rate: 7 L/min
- Supply Voltage: 250 V ac
- Pipe Diameter Range: 15 mm
- Connection Type: 1/2 BSP Female
- Maximum Pressure: 25 bar



6134238 Gas, Liquid

RS PRO PADDLE FLOW SWITCH FOR GAS, LIQUID, 14 L/MIN MIN, 18 L/MIN

Pack size: **1 x EA**

- Media Monitored: Gas, Liquid
- Device Type: Paddle
- Minimum Flow Rate: 14 L/min
- Maximum Flow Rate: 18 L/min
- Supply Voltage: 250 V ac
- Pipe Diameter Range: 25 mm
- Connection Type: 1 BSP Female
- Maximum Pressure: 25 bar



6134244 Gas, Liquid

RS PRO PRESSURE SENSOR, 0BAR MIN, 1BAR MAX, ANALOGUE OUTPUT,

Pack size: **1 x EA**

- Pressure Reading Type: Relative
- Minimum Pressure Reading: 0 bar
- Maximum Pressure Reading: 1 bar
- Accuracy: ±0.25 %
- Output Type: Analogue
- Process Connection: G1/4
- Electrical Connection: M12 4-pin
- Analogue Output: 4 → 20 mA



1754983 Relative

RS PRO PRESSURE SENSOR, 0BAR MIN, 10BAR MAX, ANALOGUE OUTPUT,

Pack size: **1 x EA**

- Pressure Reading Type: Relative
- Minimum Pressure Reading: 0 bar
- Maximum Pressure Reading: 10 bar
- Accuracy: ±0.25 %
- Output Type: Analogue
- Process Connection: G1/4
- Analogue Output: 4 → 20 mA
- Electrical Connection: M12 4-pin



1754985 Relative

RS PRO PRESSURE SENSOR, 0BAR MIN, 10BAR MAX, ANALOGUE OUTPUT,

Pack size: **1 x EA**

- Pressure Reading Type: Relative
- Minimum Pressure Reading: 0 bar
- Maximum Pressure Reading: 10 bar
- Accuracy: ±0.25 %
- Output Type: Analogue
- Process Connection: G1/4
- Electrical Connection: M12 4-pin
- Analogue Output: 0 → 5 V



1754986 Relative

RS PRO PRESSURE SENSOR, 0BAR MIN, 100BAR MAX, ANALOGUE

Pack size: **1 x EA**

- Pressure Reading Type: Relative
- Minimum Pressure Reading: 0 bar
- Maximum Pressure Reading: 100 bar
- Accuracy: ±0.25 %
- Output Type: Analogue
- Process Connection: G1/4
- Analogue Output: 0 → 5 V
- Electrical Connection: M12 4-pin



1754989 Relative

RS PRO PRESSURE SENSOR, 0BAR MIN, 16BAR MAX, ANALOGUE OUTPUT,

Pack size: **1 x EA**

- Pressure Reading Type: Relative
- Minimum Pressure Reading: 0 bar
- Maximum Pressure Reading: 16 bar
- Accuracy: ±0.25 %
- Output Type: Analogue
- Process Connection: G1/4
- Analogue Output: 4 → 20 mA
- Electrical Connection: M12 4-pin



1754990 Relative

RS PRO PRESSURE SENSOR, 0BAR MIN, 400BAR MAX, ANALOGUE

Pack size: **1 x EA**

- Pressure Reading Type: Relative
- Minimum Pressure Reading: 0 bar
- Maximum Pressure Reading: 400 bar
- Accuracy: ±0.25 %
- Output Type: Analogue
- Process Connection: G1/4
- Analogue Output: 4 → 20 mA
- Electrical Connection: M12 4-pin



1754999 Relative

RS PRO PRESSURE SENSOR, 0BAR MIN, 50MBAR MAX, ANALOGUE

Pack size: **1 x EA**

- Pressure Reading Type: Relative
- Minimum Pressure Reading: 0 bar
- Maximum Pressure Reading: 50 mbar
- Accuracy: $\pm 0.25\%$
- Output Type: Analogue
- Process Connection: G1/4
- Analogue Output: 4 $\rightarrow$ 20 mA
- Electrical Connection: M12 Connector



1755006 Relative

RS PRO PRESSURE SENSOR, 0BAR MIN, 50MBAR MAX, ANALOGUE

Pack size: **1 x EA**

- Pressure Reading Type: Relative
- Minimum Pressure Reading: 0 bar
- Maximum Pressure Reading: 50 mbar
- Accuracy: $\pm 0.25\%$
- Output Type: Analogue
- Process Connection: G1/4
- Analogue Output: 0 $\rightarrow$ 5 V
- Electrical Connection: M12 Connector



1755007 Relative

RS PRO PRESSURE SENSOR, 0BAR MIN, 0.1BAR MAX, ANALOGUE

Pack size: **1 x EA**

- Pressure Reading Type: Relative
- Minimum Pressure Reading: 0 bar
- Maximum Pressure Reading: 0.1 bar
- Accuracy: $\pm 0.25\%$
- Output Type: Analogue
- Process Connection: G1/4
- Analogue Output: 4 $\rightarrow$ 20 mA
- Electrical Connection: M12 Connector



1755008 Relative

RS PRO PRESSURE SENSOR, 0BAR MIN, 0.1BAR MAX, ANALOGUE

Pack size: **1 x EA**

- Pressure Reading Type: Relative
- Minimum Pressure Reading: 0 bar
- Maximum Pressure Reading: 0.1 bar
- Accuracy: $\pm 0.25\%$
- Output Type: Analogue
- Process Connection: G1/4
- Analogue Output: 0 $\rightarrow$ 5 V
- Electrical Connection: M12 Connector



1755009 Relative

RS PRO PRESSURE SENSOR, 0BAR MIN, 0.25BAR MAX, ANALOGUE

Pack size: **1 x EA**

- Pressure Reading Type: Relative
- Minimum Pressure Reading: 0 bar
- Maximum Pressure Reading: 0.25 bar
- Accuracy: $\pm 0.25\%$
- Output Type: Analogue
- Process Connection: G1/4
- Analogue Output: 4 $\rightarrow$ 20 mA
- Electrical Connection: M12 Connector



1755010 Relative

RS PRO PRESSURE SENSOR, OPSI MIN, 2PSI MAX, ANALOGUE OUTPUT,

Pack size: **1 x EA**

- Pressure Reading Type: Relative
- Minimum Pressure Reading: 0 psi
- Maximum Pressure Reading: 2 psi
- Accuracy: $\pm 0.25\%$
- Output Type: Analogue
- Process Connection: NPT 1/4
- Analogue Output: 0 $\rightarrow$ 5 V
- Electrical Connection: M12 Connector



1755021 Relative

RS PRO PRESSURE SENSOR, OPSI MIN, 5PSI MAX, ANALOGUE OUTPUT,

Pack size: **1 x EA**

- Pressure Reading Type: Relative
- Minimum Pressure Reading: 0 psi
- Maximum Pressure Reading: 5 psi
- Accuracy: $\pm 0.25\%$
- Output Type: Analogue
- Process Connection: NPT 1/4
- Electrical Connection: M12 Connector
- Analogue Output: 4 $\rightarrow$ 20 mA



1755022 Relative

RS PRO PRESSURE SENSOR, -14.5PSI MIN, 150PSI MAX, ANALOGUE

Pack size: **1 x EA**

- Pressure Reading Type: Relative
- Minimum Pressure Reading: -14.5 psi
- Maximum Pressure Reading: 150 psi
- Accuracy: $\pm 0.25\%$
- Output Type: Analogue
- Process Connection: NPT 1/4
- Electrical Connection: M12 Connector
- Analogue Output: 4 $\rightarrow$ 20 mA



1755030 Relative

RS PRO PRESSURE SENSOR, -14.5PSI MIN, 150PSI MAX, ANALOGUE

Pack size: **1 x EA**

- Pressure Reading Type: Relative
- Minimum Pressure Reading: -14.5 psi
- Maximum Pressure Reading: 150 psi
- Accuracy: $\pm 0.25\%$
- Output Type: Analogue
- Process Connection: NPT 1/4
- Analogue Output: 0 $\rightarrow$ 5 V
- Electrical Connection: M12 Connector



1755031 Relative

RS PRO PRESSURE SENSOR, OPSI MIN, 30PSI MAX, ANALOGUE OUTPUT,

Pack size: **1 x EA**

- Pressure Reading Type: Relative
- Minimum Pressure Reading: 0 psi
- Maximum Pressure Reading: 30 psi
- Accuracy: $\pm 0.25\%$
- Output Type: Analogue
- Process Connection: NPT 1/4
- Electrical Connection: M12 Connector
- Analogue Output: 4 $\rightarrow$ 20 mA



1755036 Relative

RS PRO PRESSURE SENSOR, OPSI MIN, 100PSI MAX, ANALOGUE

Pack size: **1 x EA**

- Pressure Reading Type: Relative
- Minimum Pressure Reading: 0 psi
- Maximum Pressure Reading: 100 psi
- Accuracy: $\pm 0.25\%$
- Output Type: Analogue
- Process Connection: NPT 1/4
- Electrical Connection: M12 Connector
- Analogue Output: 4 $\rightarrow$ 20 mA



1755040 Relative

RS PRO PRESSURE SENSOR, OPSI MIN, 300PSI MAX, ANALOGUE

Pack size: **1 x EA**

- Pressure Reading Type: Relative
- Minimum Pressure Reading: 0 psi
- Maximum Pressure Reading: 300 psi
- Accuracy: $\pm 0.25\%$
- Output Type: Analogue
- Process Connection: NPT 1/4
- Electrical Connection: M12 Connector



1755047 Relative

RS PRO PRESSURE SWITCH, 0BAR MIN, 10BAR MAX, ANALOGUE OUTPUT,

Pack size: **1 x EA**

- Pressure Reading Type: Gauge
- Minimum Pressure Reading: 0 bar
- Maximum Pressure Reading: 10 bar
- Accuracy: $\pm 0.5\%$
- Output Type: Analogue
- Media Measured: Gas, Liquid
- Process Connection: G1/4
- Electrical Connection: M12 Connector



5184434 Gauge

RS PRO PRESSURE SWITCH, 0BAR MIN, 16BAR MAX, ANALOGUE OUTPUT,

Pack size: **1 x EA**

- Pressure Reading Type: Relative
- Minimum Pressure Reading: 0 bar
- Maximum Pressure Reading: 16 bar
- Accuracy: $\pm 0.5\%$
- Output Type: Analogue
- Media Measured: Gas, Liquid
- Process Connection: G1/4
- Electrical Connection: M12 Connector



5184456 Relative

RS PRO PRESSURE SWITCH, 0BAR MIN, 2.5BAR MAX, ANALOGUE

Pack size: **1 x EA**

- Pressure Reading Type: Gauge
- Minimum Pressure Reading: 0 bar
- Maximum Pressure Reading: 2.5 bar
- Accuracy: $\pm 0.5\%$
- Output Type: Analogue
- Media Measured: Gas, Liquid
- Process Connection: G1/4
- Electrical Connection: M12 Connector



5184490 Gauge

RS PRO PRESSURE SWITCH, 0BAR MIN, 60BAR MAX, ANALOGUE

Pack size: **1 x EA**

- Pressure Reading Type: Gauge
- Minimum Pressure Reading: 0 bar
- Maximum Pressure Reading: 60 bar
- Accuracy: $\pm 0.5\%$
- Output Type: Analogue
- Media Measured: Gas, Liquid
- Process Connection: G1/4
- Electrical Connection: M12 Connector



5215342 Gauge

RS PRO PRESSURE SENSOR, 0BAR MIN, 10BAR MAX, VOLTAGE OUTPUT,

Pack size: **1 x EA**

- Pressure Reading Type: Relative
- Minimum Pressure Reading: 0 bar
- Maximum Pressure Reading: 10 bar
- Accuracy: $\pm 0.25\%$
- Output Type: Voltage
- Media Measured: Air, Gas, Hydraulic Fluid, Liquid, Water
- Process Connection: G1/4
- Analogue Output: 0 $\rightarrow$ 5 V



7975037 Relative

RS PRO PRESSURE SENSOR, 0BAR MIN, 1BAR MAX, VOLTAGE OUTPUT,

Pack size: **1 x EA**

- Pressure Reading Type: Relative
- Minimum Pressure Reading: 0 bar
- Maximum Pressure Reading: 1 bar
- Accuracy: $\pm 0.25\%$
- Output Type: Voltage
- Media Measured: Air, Gas, Hydraulic Fluid, Liquid, Water
- Process Connection: G1/4
- Analogue Output: 0 $\rightarrow$ 5 V



7975043 Relative

RS PRO PRESSURE SENSOR, 0BAR MIN, 6BAR MAX, VOLTAGE OUTPUT,

Pack size: **1 x EA**

- Pressure Reading Type: Relative
- Minimum Pressure Reading: 0 bar
- Maximum Pressure Reading: 6 bar
- Accuracy: $\pm 0.25\%$
- Output Type: Voltage
- Media Measured: Air, Gas, Hydraulic Fluid, Liquid, Water
- Process Connection: G1/4
- Electrical Connection: DIN 43650 Type C



7975046 Relative

RS PRO PRESSURE SENSOR, 0BAR MIN, 250BAR MAX, VOLTAGE OUTPUT,

Pack size: **1 x EA**

- Pressure Reading Type: Relative
- Minimum Pressure Reading: 0 bar
- Maximum Pressure Reading: 250 bar
- Accuracy: $\pm 0.25\%$
- Output Type: Voltage
- Media Measured: Air, Gas, Hydraulic Fluid, Liquid, Water
- Process Connection: G1/4
- Electrical Connection: DIN 43650 Type C



7975049 Relative

RS PRO PRESSURE SENSOR, 0BAR MIN, 25BAR MAX, VOLTAGE OUTPUT,

Pack size: **1 x EA**

- Pressure Reading Type: Relative
- Minimum Pressure Reading: 0 bar
- Maximum Pressure Reading: 25 bar
- Accuracy: $\pm 0.25\%$
- Output Type: Voltage
- Media Measured: Air, Gas, Hydraulic Fluid, Liquid, Water
- Process Connection: G1/4
- Electrical Connection: DIN 43650 Type C



7975052 Relative

RS PRO PRESSURE SENSOR, 0BAR MIN, 50MBAR MAX, CURRENT

Pack size: **1 x EA**

- Pressure Reading Type: Relative
- Minimum Pressure Reading: 0 bar
- Maximum Pressure Reading: 50 mbar
- Accuracy: $\pm 0.25\%$
- Output Type: Current
- Media Measured: Oil, Water
- Process Connection: G1/4
- Analogue Output: 4 $\rightarrow$ 20 mA



8285707 Relative

RS PRO PRESSURE SENSOR, 0BAR MIN, 0.1BAR MAX, CURRENT OUTPUT,

Pack size: **1 x EA**

- Pressure Reading Type: Relative
- Minimum Pressure Reading: 0 bar
- Maximum Pressure Reading: 0.1 bar
- Accuracy: $\pm 0.25\%$
- Output Type: Current
- Media Measured: Oil, Water
- Process Connection: G1/4
- Analogue Output: 4 $\rightarrow$ 20 mA



8285710 Relative

RS PRO PRESSURE SENSOR, 0BAR MIN, 0.1BAR MAX, VOLTAGE OUTPUT,

Pack size: **1 x EA**

- Pressure Reading Type: Relative
- Minimum Pressure Reading: 0 bar
- Maximum Pressure Reading: 0.1 bar
- Accuracy: $\pm 0.25\%$
- Output Type: Voltage
- Media Measured: Oil, Water
- Process Connection: G1/4
- Analogue Output: 0.5 $\rightarrow$ 4.5 V



8285713 Relative

RS PRO PRESSURE SENSOR, 0BAR MIN, 0.25BAR MAX, CURRENT

Pack size: **1 x EA**

- Pressure Reading Type: Relative
- Minimum Pressure Reading: 0 bar
- Maximum Pressure Reading: 0.25 bar
- Accuracy: $\pm 0.25\%$
- Output Type: Current
- Media Measured: Oil, Water
- Process Connection: G1/4
- Analogue Output: 4 $\rightarrow$ 20 mA



8285717 Relative

RS PRO PRESSURE SENSOR, 0BAR MIN, 500MBAR MAX, VOLTAGE

Pack size: **1 x EA**

- Pressure Reading Type: Relative
- Minimum Pressure Reading: 0 bar
- Maximum Pressure Reading: 500 mbar
- Accuracy: $\pm 0.25\%$
- Output Type: Voltage
- Media Measured: Oil, Water
- Process Connection: G1/4
- Analogue Output: 0.5 $\rightarrow$ 4.5 V



8285723 Relative

RS PRO PRESSURE SENSOR, 0BAR MIN, 500MBAR MAX, CURRENT

Pack size: **1 x EA**

- Pressure Reading Type: Relative
- Minimum Pressure Reading: 0 bar
- Maximum Pressure Reading: 500 mbar
- Accuracy: $\pm 0.25\%$
- Output Type: Current
- Media Measured: Oil, Water
- Process Connection: G1/4
- Analogue Output: 4 $\rightarrow$ 20 mA



8285729 Relative

RS PRO PRESSURE SENSOR, 0BAR MIN, 0.25BAR MAX, VOLTAGE

Pack size: **1 x EA**

- Pressure Reading Type: Relative
- Minimum Pressure Reading: 0 bar
- Maximum Pressure Reading: 0.25 bar
- Accuracy: $\pm 0.25\%$
- Output Type: Voltage
- Media Measured: Oil, Water
- Process Connection: G1/4
- Analogue Output: 0.5 $\rightarrow$ 4.5 V



8285726 Relative

RS PRO PRESSURE SENSOR, 0BAR MIN, 1BAR MAX, CURRENT OUTPUT,

Pack size: **1 x EA**

- Pressure Reading Type: Relative
- Minimum Pressure Reading: 0 bar
- Maximum Pressure Reading: 1 bar
- Accuracy: $\pm 0.25\%$
- Output Type: Current
- Media Measured: Air, Gas, Hydraulic Fluid, Liquid, Water
- Process Connection: G1/4
- Electrical Connection: DIN 43650 Type A



8285739 Relative

RS PRO PRESSURE SENSOR, 0BAR MIN, 16BAR MAX, VOLTAGE OUTPUT,

Pack size: **1 x EA**

- Pressure Reading Type: Relative
- Minimum Pressure Reading: 0 bar
- Maximum Pressure Reading: 16 bar
- Accuracy: $\pm 0.25\%$
- Output Type: Voltage
- Media Measured: Air, Gas, Hydraulic Fluid, Liquid, Water
- Process Connection: G1/4
- Electrical Connection: DIN 43650 Type C



8285745 Relative

RS PRO PRESSURE SENSOR, 0BAR MIN, 16BAR MAX, CURRENT OUTPUT,

Pack size: **1 x EA**

- Pressure Reading Type: Relative
- Minimum Pressure Reading: 0 bar
- Maximum Pressure Reading: 16 bar
- Accuracy: $\pm 0.25\%$
- Output Type: Current
- Media Measured: Air, Gas, Hydraulic Fluid, Liquid, Water
- Process Connection: G1/4
- Analogue Output: 4 $\rightarrow$ 20 mA



8285741 Relative

RS PRO PRESSURE SENSOR, 0BAR MIN, 5BAR MAX, CURRENT OUTPUT,

Pack size: **1 x EA**

- Pressure Reading Type: Relative
- Minimum Pressure Reading: 0 bar
- Maximum Pressure Reading: 5 bar
- Accuracy: $\pm 0.25\%$
- Output Type: Current
- Media Measured: Sewage, Viscous Fluid, Water
- Process Connection: G3/4
- Analogue Output: 4 $\rightarrow$ 20 mA



8285763 Relative

RS PRO PRESSURE SENSOR, 0BAR MIN, 10BAR MAX, CURRENT OUTPUT,

Pack size: **1 x EA**

- Pressure Reading Type: Relative
- Minimum Pressure Reading: 0 bar
- Maximum Pressure Reading: 10 bar
- Accuracy: <±0.25 %
- Output Type: Current
- Media Measured: Sewage, Viscous Fluid, Water
- Process Connection: G3/4
- Electrical Connection: M12 Connector



8285767 Relative

RS PRO PRESSURE SENSOR, 0BAR MIN, 20BAR MAX, CURRENT OUTPUT,

Pack size: **1 x EA**

- Pressure Reading Type: Relative
- Minimum Pressure Reading: 0 bar
- Maximum Pressure Reading: 20 bar
- Accuracy: <±0.25 %
- Output Type: Current
- Media Measured: Sewage, Viscous Fluid, Water
- Process Connection: G3/4
- Analogue Output: 4 → 20 mA



8285776 Relative

RS PRO PRESSURE SENSOR, -1BAR MIN, 1BAR MAX, CURRENT OUTPUT,

Pack size: **1 x EA**

- Pressure Reading Type: Relative
- Minimum Pressure Reading: -1 bar
- Maximum Pressure Reading: 1 bar
- Accuracy: <±0.25 %
- Output Type: Current
- Media Measured: Sewage, Viscous Fluid, Water
- Process Connection: G3/4
- Analogue Output: 4 → 20 mA



8285811 Relative

RS PRO PRESSURE SENSOR, 0BAR MIN, 1BAR MAX, VOLTAGE OUTPUT,

Pack size: **1 x EA**

- Pressure Reading Type: Relative
- Minimum Pressure Reading: 0 bar
- Maximum Pressure Reading: 1 bar
- Accuracy: <±0.25 %
- Output Type: Voltage
- Media Measured: Oil, Water
- Process Connection: G1/4
- Electrical Connection: DIN 43650 Type A



8285748 Relative

RS PRO PRESSURE SENSOR, 0BAR MIN, 1BAR MAX, CURRENT OUTPUT,

Pack size: **1 x EA**

- Pressure Reading Type: Absolute
- Minimum Pressure Reading: 0 bar
- Maximum Pressure Reading: 1 bar
- Accuracy: <±0.25 %
- Output Type: Current
- Media Measured: Sewage, Viscous Fluid, Water
- Process Connection: G3/4
- Electrical Connection: M12 Connector



8285820 Absolute

RS PRO PRESSURE SENSOR, -1BAR MIN, 9BAR MAX, CURRENT OUTPUT,

Pack size: **1 x EA**

- Pressure Reading Type: Relative
- Minimum Pressure Reading: -1 bar
- Maximum Pressure Reading: 9 bar
- Accuracy: <±0.25 %
- Output Type: Current
- Media Measured: Sewage, Viscous Fluid, Water
- Process Connection: G3/4
- Analogue Output: 4 → 20 mA



8285818 Relative

RS PRO YELLOW DIE CAST ALUMINIUM PUSH BUTTON

Pack size: **1 x EA**

- Cutout Diameter: 22 mm
- Number of Cutouts: 1
- Enclosure Colour: Yellow
- Enclosure Marking: None
- Enclosure Material: Die Cast Aluminium
- IP Rating: IP65
- Length: 72 mm
- Width: 72 mm



1368581 22 mm

RS PRO YELLOW DIE CAST ALUMINIUM PUSH BUTTON

Pack size: **1 x EA**

- Cutout Diameter: 22 mm
- Number of Cutouts: 1
- Enclosure Colour: Yellow
- Enclosure Marking: TC
- Enclosure Material: Die Cast Aluminium
- IP Rating: IP65
- Length: 105 mm
- Width: 68 mm



1368582 22 mm

RS PRO STAINLESS STEEL PUSH BUTTON ENCLOSURE - 1 HOLE 22MM

Pack size: **1 x EA**

- Cutout Diameter: 22 mm
- Number of Cutouts: 1
- Enclosure Material: Stainless Steel
- IP Rating: IP66, IP69K
- Length: 75 mm
- Width: 50 mm
- Depth: 75 mm
- Dimensions: 75 x 50 x 75 mm



1611521 22 mm

RS PRO STAINLESS STEEL PUSH BUTTON ENCLOSURE - 2 HOLE 22MM

Pack size: **1 x EA**

- Cutout Diameter: 22 mm
- Number of Cutouts: 2
- Enclosure Material: Stainless Steel
- IP Rating: IP66, IP69K
- Length: 100 mm
- Width: 85 mm
- Depth: 160 mm
- Dimensions: 100 x 85 x 160 mm



1611522 22 mm

RS PRO STAINLESS STEEL PUSH BUTTON ENCLOSURE - 3 HOLE 22MM

Pack size: **1 x EA**

- Cutout Diameter: 22 mm
- Number of Cutouts: 3
- Enclosure Material: Stainless Steel
- IP Rating: IP66, IP69K
- Length: 100 mm
- Width: 85 mm
- Depth: 220 mm
- Dimensions: 100 x 85 x 220 mm



1611523 22 mm

RS PRO STAINLESS STEEL PUSH BUTTON ENCLOSURE - 1 HOLE 22MM

Pack size: **1 x EA**

- Cutout Diameter: 22 mm
- Number of Cutouts: 1
- Enclosure Material: Stainless Steel
- IP Rating: IP66, IP69K
- Length: 115 mm
- Width: 85 mm
- Depth: 115 mm
- Dimensions: 115 x 85 x 115 mm



1611524 22 mm

PTEC 22.5MM PULSING SOUNDER 24VAC/DC

Pack size: **1 x EA**

- Accessory Type: 24 V Pulsing Sounder
- For Use With: Alarm Circuit



9092566 24 V Pulsing

PTEC 22.5MM PULSING SOUNDER 12VAC/DC

Pack size: **1 x EA**

- Accessory Type: 12 V Pulsing Sounder
- For Use With: Alarm Circuit



9092562 12 V Pulsing

RS PRO FOOT SWITCH BELLOWS FOR IPX7 PLASTIC FOOT SWITCH

Pack size: **1 x EA**

- Accessory Type: Bellow
- For Use With: IPX7 Plastic Foot Switch



335353 Bellow

SWITCH, FOOT, ACTUATOR, AIR OPERATED, RED

Pack size: **1 x EA**

- Accessory Type: Bellow
- For Use With: Foot Switch



335375 Bellow

SWITCH, FOOT, ACTUATOR, AIR OPERATED, BLACK

Pack size: **1 x EA**

- Accessory Type: Bellow
- For Use With: Air Operated Switch



316945 Bellow

SWITCH, FOOT, ACTUATOR, AIR OPERATED, GREY

Pack size: **1 x EA**

- Accessory Type: Bellow
- For Use With: Foot Switch



335397 Bellow

SWITCH, FOOT, HAND, PVC, BLACK, 3A, 24VDC, N/O, 100000

Pack size: **1 x EA**

- Accessory Type: Bellow
- For Use With: IPX7 Plastic Foot Switch



335404 Bellow

FOOT SWITCH GUARD COVER FOR FOOT SWITCH

Pack size: **1 x EA**

- Accessory Type: Cover
- For Use With: Foot Switch



116653 Cover

FOOT SWITCH GUARD COVER FOR FOOT SWITCH

Pack size: **1 x EA**

- Accessory Type: Guard
- For Use With: Foot Switch



116726 Guard

RS PRO MOMENTARY ON-OFF FOOT SWITCH - DIE CAST ALUMINIUM CASE

Pack size: **1 x EA**

- Foot Switch Type: Heavy Duty Foot Switch
- Switch Operation: Momentary On-Off
- Case Material: Die Cast Aluminium
- Switch Environment: Heavy Duty
- IP Rating: IPX7
- Guard Cover: No
- Colour: Black
- Standards Met: 2014/35/EU, EN 60950, EN 61058, EN 61058-2-1



317718 Heavy Duty Foot

RS PRO FOOT SWITCH MOMENTARY ON-OFF FOOT SWITCH - 16 SWG MILD

Pack size: **1 x EA**

- Switch Operation: Momentary On-Off
- Case Material: 16 SWG Mild Steel
- Switch Environment: Foot Switch
- IP Rating: IPX2
- Guard Cover: No
- Colour: Black, Grey
- Height: 24 mm
- Width: 66 mm



170806 Momentary On-

RS PRO FOOT SWITCH BELLOW MOMENTARY FOOT SWITCH - PVC

Pack size: **1 x EA**

- Foot Switch Type: Momentary Foot Switch
- Contact Configuration: Single Pole Single Throw (SPST)
- Switch Operation: Momentary
- Case Material: PVC
- Contact Voltage Rating (DC): 24 V
- Contact Current Rating: 50 mA
- Switch Environment: Foot Switch Bellow
- IP Rating: IP67



335303 Momentary Foot

SWITCH, FOOT, HAND, BLACK, 1 N/O, 30MA, 24VDC, 100000, IP67

Pack size: **1 x EA**

- Foot Switch Type: Momentary Foot Switch
- Contact Configuration: SPST N/O
- Switch Operation: Momentary
- Case Material: PVC
- Contact Voltage Rating (DC): 24 V
- Contact Current Rating: 50 mA @ 24 V
- Switch Environment: Foot Switch Bellow
- IP Rating: IP67



335319 Momentary Foot

SWITCH, AIR OPERATED, HAND, INDUSTRIAL, GLASS

Pack size: **1 x EA**

- Contact Configuration: SPST-N/O
- Switch Operation: Momentary On-Off
- Case Material: Thermoplastic
- Switch Environment: Light Industrial
- IP Rating: IPX7
- Guard Cover: Yes
- Colour: Black
- Standards Met: 2014/35/EU, EN 60950



335381 SPST-NO

RS PRO LIGHT INDUSTRIAL MOMENTARY USB PROGRAMMABLE

Pack size: **1 x EA**

- Foot Switch Type: Momentary Foot Switch
- Contact Configuration: Single Pole Single Throw (SPST)
- Switch Operation: Momentary
- Case Material: Glass Fibre Reinforced Polymer
- Contact Voltage Rating (AC): 5 V
- Contact Current Rating: 25 mA @ 5 V ac
- Switch Environment: Light Industrial
- IP Rating: IPX2



474537 Momentary Foot

HEAVY DUTY FOOTSWITCH (NO GUARD)

Pack size: **1 x EA**

- Contact Configuration: SP-CO
- Foot Switch Type: Heavy Duty Foot Switch
- Switch Operation: Slow Action
- Contact Voltage Rating (AC): 600 V
- Contact Voltage Rating (DC): 500 V
- Contact Current Rating: 10 A
- Switch Environment: Heavy Duty
- IP Rating: IP65



1222790 SP-CO

RS PRO MOMENTARY HEAVY DUTY FOOT SWITCH - SP-CO, 10 A

Pack size: **1 x EA**

- Contact Configuration: SP-CO
- Foot Switch Type: Heavy Duty Foot Switch
- Switch Operation: Momentary
- Contact Voltage Rating (AC): 600 V
- Contact Voltage Rating (DC): 500 V
- Contact Current Rating: 10 A
- Switch Environment: Heavy Duty
- IP Rating: IP65



1222791 SP-CO

RS PRO MOMENTARY STAGGERED HEAVY DUTY FOOT SWITCH - DIE

Pack size: **1 x EA**

- Foot Switch Type: Heavy Duty Foot Switch
- Contact Configuration: DPST + DPST
- Switch Operation: Momentary Staggered
- Case Material: Die Cast Aluminium
- Contact Voltage Rating (AC): 500 V
- Contact Voltage Rating (DC): 24 V
- Contact Current Rating: 6 A (AC15 230V), 6 A (DC13 24V)
- Switch Environment: Heavy Duty



2083265 Heavy Duty Foot

RS PRO MOMENTARY HEAVY DUTY FOOT SWITCH - DIE CAST ALUMINIUM

Pack size: **1 x EA**

- Foot Switch Type: Heavy Duty Foot Switch
- Contact Configuration: Single Pole Single Throw (SPST)
- Switch Operation: Momentary
- Case Material: Die Cast Aluminium
- Contact Voltage Rating (AC): 500 V
- Contact Voltage Rating (DC): 24 V
- Contact Current Rating: 12 A
- Switch Environment: Heavy Duty



4405566 Heavy Duty Foot

RS PRO MEDICALLY APPROVED FOOT SWITCH BELLOW MOMENTARY

Pack size: **1 x EA**

- Foot Switch Type: Momentary Foot Switch
- Contact Configuration: Single Pole Single Throw (SPST)
- Switch Operation: Momentary
- Case Material: PVC
- Contact Voltage Rating (DC): 30 V
- Contact Current Rating: 50 mA
- Switch Environment: Medically Approved Foot Switch Bellow
- IP Rating: IP67



4561701 Momentary Foot

SWITCH, FOOT, SMALL, IP67, RED

Pack size: **1 x EA**

- Foot Switch Type: Momentary Foot Switch
- Contact Configuration: Single Pole Single Throw (SPST)
- Switch Operation: Momentary
- Case Material: PVC
- Contact Voltage Rating (DC): 30 V
- Contact Current Rating: 50 mA
- Switch Environment: Foot Switch Bellow
- IP Rating: IP67



4561717 Momentary Foot

RS PRO MEDICALLY APPROVED FOOT SWITCH BELLOW MOMENTARY

Pack size: **1 x EA**

- Foot Switch Type: Momentary Foot Switch
- Contact Configuration: Single Pole Single Throw (SPST)
- Switch Operation: Momentary
- Case Material: PVC
- Contact Voltage Rating (DC): 30 V
- Contact Current Rating: 50 mA
- Switch Environment: Medically Approved Foot Switch Bellow
- IP Rating: IP67



4561739 Momentary Foot

FOOT SWITCH, PLASTIC IP67, SPDT, 3A

Pack size: **1 x EA**

- Contact Configuration: Single Pole Double Throw (SPDT)
- Foot Switch Type: Momentary Foot Switch
- Switch Operation: Momentary
- Case Material: Thermoplastic
- Contact Voltage Rating (AC): 24 V
- Contact Voltage Rating (DC): 24 V
- Contact Current Rating: 3 A
- Switch Environment: General Purpose



7748614 Single Pole

6210-VO BLACK FOOT POTENTIOMETER

Pack size: **1 x EA**

- Foot Switch Type: Momentary Foot Switch
- Switch Operation: Momentary
- Case Material: Thermoplastic
- Contact Voltage Rating (AC): 12 V
- Contact Current Rating: 6 A @ 250 V ac
- Switch Environment: Light Industrial
- IP Rating: IPX2
- Colour: Black



8039772 Momentary Foot

RS PRO GENERAL PURPOSE MOMENTARY FOOT SWITCH -

Pack size: **1 x EA**

- Contact Configuration: SP-CO
- Foot Switch Type: Momentary Foot Switch
- Switch Operation: Momentary
- Case Material: Thermoplastic
- Contact Voltage Rating (AC): 24 V
- Contact Voltage Rating (DC): 24 V
- Contact Current Rating: 1.75 A
- Switch Environment: General Purpose



8086982 SP-CO

RS PRO GENERAL PURPOSE MOMENTARY FOOT SWITCH -

Pack size: **1 x EA**

- Contact Configuration: SP-CO
- Foot Switch Type: Momentary Foot Switch
- Switch Operation: Momentary
- Case Material: Thermoplastic
- Contact Voltage Rating (AC): 24 V
- Contact Voltage Rating (DC): 24 V
- Contact Current Rating: 1.75 A
- Switch Environment: General Purpose



8086986 SP-CO

GREY IPX2 COMPACT FOOTSWITCH NO/NC

Pack size: **1 x EA**

- Contact Configuration: SP-CO
- Foot Switch Type: Momentary Foot Switch
- Switch Operation: Momentary
- Case Material: Thermoplastic
- Contact Voltage Rating (AC): 24 V
- Contact Voltage Rating (DC): 24 V
- Contact Current Rating: 1.75 A
- Switch Environment: General Purpose



8086989 SP-CO

IPX7 DOUBLE PEDAL FOOTSWITCH 2 X SPNO

Pack size: **1 x EA**

- Foot Switch Type: Momentary Foot Switch
- Contact Configuration: Double Pole Single Throw [DPST]
- Switch Operation: Momentary
- Case Material: Thermoplastic
- Contact Voltage Rating (AC): 24 V
- Contact Voltage Rating (DC): 24 V
- Contact Current Rating: 3 A
- Switch Environment: General Purpose



8086992 Momentary Foot

RS PRO GENERAL PURPOSE MOMENTARY FOOT SWITCH -

Pack size: **1 x EA**

- Foot Switch Type: Momentary Foot Switch
- Contact Configuration: SP-CO
- Switch Operation: Momentary
- Case Material: Thermoplastic
- Contact Voltage Rating (AC): 24 V
- Contact Voltage Rating (DC): 24 V
- Contact Current Rating: 1.75 A
- Switch Environment: General Purpose



8086995 Momentary Foot

IPX7 DOUBLE PEDAL FOOTSWITCH 2 X NO/NC

Pack size: **1 x EA**

- Foot Switch Type: Momentary Foot Switch
- Contact Configuration: Double Pole Single Throw [DPST]
- Switch Operation: Momentary
- Case Material: Thermoplastic
- Contact Voltage Rating (AC): 24 V
- Contact Voltage Rating (DC): 24 V
- Contact Current Rating: 3 A
- Switch Environment: General Purpose



8087005 Momentary Foot

RS PRO FLEXIBLE TUBE, 3MM ID, PVC, 10M

Pack size: **10 x MTR**

- Inner Diameter: 3 mm
- Outer Diameter: 6 mm
- Material: PVC
- Length: 10 m



317724 3 mm

WEDGE INDICATOR LIGHT, CLEAR, 12 V, 83 MA, 5000H

Pack size: **1 x EA**

- Voltage Rating: 12 V
- Lamp Base: Wedge
- Current Rating: 83 mA
- Diameter: 5 mm
- Lamp Size: T1 1/2
- Length: 20 mm
- Lens Colour: Clear
- Luminosity: 3 lm



6559564 12 V

RS PRO 4P POLE PANEL MOUNT ISOLATOR SWITCH - 32A MAXIMUM

Pack size: **1 x EA**

- Number of Poles: 4P
- Maximum Current: 32 A
- Mounting Type: Panel Mount
- IP Rating: IP65
- Power Rating: 15 kW
- Voltage Rating: 690 V ac
- Electrical Phase: 3
- Handle Colour: Red



7737964 4P

RS PRO 6P POLE ISOLATOR SWITCH - 32A MAXIMUM CURRENT, 15KW

Pack size: **1 x EA**

- Number of Poles: 6P
- Maximum Current: 32 A
- IP Rating: IP65
- Power Rating: 15 kW
- Voltage Rating: 690 V ac
- Electrical Phase: 1, 3
- Handle Colour: Red
- Accepts Padlocks: Yes



7737970 6P

RS PRO 4P POLE PANEL MOUNT ISOLATOR SWITCH - 40A MAXIMUM

Pack size: **1 x EA**

- Number of Poles: 4P
- Maximum Current: 40 A
- Mounting Type: Panel Mount
- IP Rating: IP65
- Power Rating: 18.5 kW
- Voltage Rating: 690 V ac
- Electrical Phase: 3
- Handle Colour: Red



7737973 4P

RS PRO 6P POLE ISOLATOR SWITCH - 25A MAXIMUM CURRENT, 15KW

Pack size: **1 x EA**

- Number of Poles: 6P
- Maximum Current: 25 A
- IP Rating: IP65
- Power Rating: 15 kW
- Voltage Rating: 690 V ac
- Electrical Phase: 1, 3
- Handle Colour: Red
- Accepts Padlocks: Yes



7737976 6P

RS PRO 6P POLE ISOLATOR SWITCH - 125A MAXIMUM CURRENT, 55KW

Pack size: **1 x EA**

- Number of Poles: 6P
- Maximum Current: 125 A
- IP Rating: IP65
- Power Rating: 55 kW
- Voltage Rating: 690 V ac
- Electrical Phase: 1, 3
- Handle Colour: Red
- Accepts Padlocks: Yes



7737986 6P

RS PRO 6P POLE ISOLATOR SWITCH - 63A MAXIMUM CURRENT, 30KW

Pack size: **1 x EA**

- Number of Poles: 6P
- Maximum Current: 63 A
- IP Rating: IP65
- Power Rating: 30 kW
- Voltage Rating: 690 V ac
- Electrical Phase: 1, 3
- Handle Colour: Red
- Accepts Padlocks: Yes



7737989 6P

RS PRO 4P POLE PANEL MOUNT ISOLATOR SWITCH - 32A MAXIMUM

Pack size: **1 x EA**

- Number of Poles: 4P
- Maximum Current: 32 A
- Mounting Type: Panel Mount
- IP Rating: IP65
- Power Rating: 15 kW
- Voltage Rating: 690 V ac
- Electrical Phase: 3
- Accepts Padlocks: Yes



7737992 4P

RS PRO 4P POLE PANEL MOUNT ISOLATOR SWITCH - 40A MAXIMUM

Pack size: **1 x EA**

- Number of Poles: 4P
- Maximum Current: 40 A
- Mounting Type: Panel Mount
- IP Rating: IP65
- Power Rating: 18.5 kW
- Voltage Rating: 690 V ac
- Electrical Phase: 3
- Handle Colour: Red



7738005 4P

RS PRO 4P POLE PANEL MOUNT ISOLATOR SWITCH - 63A MAXIMUM

Pack size: **1 x EA**

- Number of Poles: 4P
- Maximum Current: 63 A
- Mounting Type: Panel Mount
- IP Rating: IP65
- Power Rating: 30 kW
- Voltage Rating: 690 V ac
- Electrical Phase: 3
- Handle Colour: Red



7738008 4P

RS PRO 3P POLE PANEL MOUNT ISOLATOR SWITCH - 32A MAXIMUM

Pack size: **1 x EA**

- Number of Poles: 3P
- Maximum Current: 32 A
- Mounting Type: Panel Mount
- IP Rating: IP65
- Power Rating: 15 kW
- Voltage Rating: 690 V ac
- Electrical Phase: 3
- Handle Colour: Red



7738011 3P

RS PRO 3P POLE PANEL MOUNT ISOLATOR SWITCH - 63A MAXIMUM

Pack size: **1 x EA**

- Number of Poles: 3P
- Maximum Current: 63 A
- Mounting Type: Panel Mount
- IP Rating: IP54
- Power Rating: 18.5 kW
- Voltage Rating: 690 V ac
- Electrical Phase: 3
- Handle Colour: Red



7738018 3P

RS PRO 4P POLE PANEL MOUNT ISOLATOR SWITCH - 32A MAXIMUM

Pack size: **1 x EA**

- Number of Poles: 4P
- Maximum Current: 32 A
- Mounting Type: Panel Mount
- IP Rating: IP54
- Power Rating: 18.5 kW
- Voltage Rating: 690 V ac
- Electrical Phase: 3
- Handle Colour: Red



7738024 4P

RS PRO 4P POLE PANEL MOUNT ISOLATOR SWITCH - 80A MAXIMUM

Pack size: **1 x EA**

- Number of Poles: 4P
- Maximum Current: 80 A
- Mounting Type: Panel Mount
- IP Rating: IP54
- Power Rating: 37 kW
- Voltage Rating: 690 V ac
- Electrical Phase: 3
- Handle Colour: Red



7738030 4P

RS PRO 4P POLE PANEL MOUNT ISOLATOR SWITCH - 40A MAXIMUM

Pack size: **1 x EA**

- Number of Poles: 4P
- Maximum Current: 40 A
- Mounting Type: Panel Mount
- IP Rating: IP54
- Voltage Rating: 690 V ac
- Electrical Phase: 3
- Handle Colour: Red
- Accepts Padlocks: Yes



7738033 4P

RS PRO 4P POLE PANEL MOUNT ISOLATOR SWITCH - 63A MAXIMUM

Pack size: **1 x EA**

- Number of Poles: 4P
- Maximum Current: 63 A
- Mounting Type: Panel Mount
- IP Rating: IP54
- Power Rating: 18.5 kW
- Voltage Rating: 690 V ac
- Electrical Phase: 3
- Handle Colour: Red



7738036 4P

RS PRO 4P POLE PANEL MOUNT ISOLATOR SWITCH - 125A MAXIMUM

Pack size: **1 x EA**

- Number of Poles: 4P
- Maximum Current: 125 A
- Mounting Type: Panel Mount
- IP Rating: IP54
- Power Rating: 75 kW
- Voltage Rating: 690 V ac
- Electrical Phase: 3
- Handle Colour: Red



7738042 4P

RS PRO 4P POLE PANEL MOUNT ISOLATOR SWITCH - 100A MAXIMUM

Pack size: **1 x EA**

- Number of Poles: 4P
- Maximum Current: 100 A
- Mounting Type: Panel Mount
- IP Rating: IP54
- Power Rating: 55 kW
- Voltage Rating: 690 V ac
- Electrical Phase: 3
- Accepts Padlocks: Yes



7738049 4P

RS PRO 2 POSITION SELECTOR SWITCH HEAD, 22MM CUTOUT

Pack size: **1 x EA**

- Number of Positions: 2
- Cutout Diameter: 22 mm
- Switch Actuation: Latching
- IP Rating: IP65
- Angle of Throw: 30 °



1881146 2

RS PRO 2 POSITION SELECTOR SWITCH HEAD, 22MM CUTOUT

Pack size: **1 x EA**

- Number of Positions: 2
- Cutout Diameter: 22 mm
- Switch Actuation: Spring Return
- IP Rating: IP65
- Angle of Throw: 30 °



1881148 2

RS PRO 2-POSITION KEY SWITCH HEAD, LATCHING, 22MM CUTOUT

Pack size: **1 x EA**

- Cutout Diameter: 22 mm
- Number of Positions: 2
- Switch Actuation: Latching
- IP Rating: IP65
- Angle of Throw: 30 °



1881149 22 mm

RS PRO 3 POSITION SELECTOR SWITCH HEAD, 22MM CUTOUT

Pack size: **1 x EA**

- Number of Positions: 3
- Cutout Diameter: 22 mm
- Switch Actuation: Latching
- IP Rating: IP65
- Angle of Throw: 45 °



1881151 3

RS PRO 3 POSITION SELECTOR SWITCH HEAD, 22MM CUTOUT

Pack size: **1 x EA**

- Number of Positions: 3
- Cutout Diameter: 22 mm
- Switch Actuation: Spring Return
- IP Rating: IP65
- Angle of Throw: 45 °



1881152 3

RS PRO 3-POSITION KEY SWITCH HEAD, LATCHING, 22MM CUTOUT

Pack size: **1 x EA**

- Cutout Diameter: 22 mm
- Number of Positions: 3
- Switch Actuation: Latching
- IP Rating: IP65
- Angle of Throw: 40 °



1881154 22 mm

RS PRO 3-POSITION KEY SWITCH HEAD, SPRING RETURN, 22MM

Pack size: **1 x EA**

- Cutout Diameter: 22 mm
- Number of Positions: 3
- Switch Actuation: Spring Return
- IP Rating: IP65
- Angle of Throw: 40 °



1881155 22 mm

RS PRO 2 POSITION SELECTOR SWITCH HEAD, 22MM CUTOUT,

Pack size: **1 x EA**

- Actuator Colour: Green
- Illuminated: Yes
- Number of Positions: 2
- Cutout Diameter: 22 mm
- Switch Actuation: Latching
- IP Rating: IP65
- Angle of Throw: 30 °



1881156 Green

RS PRO 2 POSITION SELECTOR SWITCH HEAD, 22MM CUTOUT,

Pack size: **1 x EA**

- Actuator Colour: Green
- Illuminated: Yes
- Number of Positions: 2
- Cutout Diameter: 22 mm
- Switch Actuation: Spring Return
- IP Rating: IP65
- Angle of Throw: 30 °



1881157 Green

RS PRO 2 POSITION SELECTOR SWITCH HEAD, 22MM CUTOUT, RED

Pack size: **1 x EA**

- Actuator Colour: Red
- Illuminated: Yes
- Number of Positions: 2
- Cutout Diameter: 22 mm
- Switch Actuation: Latching
- IP Rating: IP65
- Angle of Throw: 30 °



1881158 Red

RS PRO 2 POSITION SELECTOR SWITCH HEAD, 22MM CUTOUT, RED

Pack size: **1 x EA**

- Actuator Colour: Red
- Illuminated: Yes
- Number of Positions: 2
- Cutout Diameter: 22 mm
- Switch Actuation: Spring Return
- IP Rating: IP65
- Angle of Throw: 30 °



1881159 Red

RS PRO 2 POSITION SELECTOR SWITCH HEAD, 22MM CUTOUT, AMBER

Pack size: **1 x EA**

- Actuator Colour: Amber
- Illuminated: Yes
- Number of Positions: 2
- Cutout Diameter: 22 mm
- Switch Actuation: Latching
- IP Rating: IP65
- Angle of Throw: 30 °



1881160 Amber

RS PRO 2 POSITION SELECTOR SWITCH HEAD, 22MM CUTOUT, AMBER

Pack size: **1 x EA**

- Actuator Colour: Amber
- Illuminated: Yes
- Number of Positions: 2
- Cutout Diameter: 22 mm
- Switch Actuation: Spring Return
- IP Rating: IP65
- Angle of Throw: 30 °



1881161 Amber

RS PRO 3 POSITION SELECTOR SWITCH HEAD, 22MM CUTOUT, GREEN

Pack size: **1 x EA**

- Actuator Colour: Green
- Illuminated: Yes
- Number of Positions: 3
- Cutout Diameter: 22 mm
- Switch Actuation: Spring Return
- IP Rating: IP65
- Angle of Throw: 30 °



1881163 Green

RS PRO 3 POSITION SELECTOR SWITCH HEAD, 22MM CUTOUT, GREEN

Pack size: **1 x EA**

- Actuator Colour: Green
- Illuminated: Yes
- Number of Positions: 3
- Cutout Diameter: 22 mm
- Switch Actuation: Spring Return
- IP Rating: IP65
- Angle of Throw: 30 °



1881164 Green

RS PRO 686 SERIES MOMENTARY AIR SWITCH, SURFACE MOUNTED

Pack size: **1 x EA**

- Manufacturer Series: 686
- Type: Momentary
- Mounting Type: Surface
- Operation: NO/NC
- For Use With: 3 mm I/D Tubing, Battery Charging Rooms, Garages or Wherever Explosive Gases, Laboratories, Vapours or Powders May Exist



316951 686

RS PRO 6871 SERIES MOMENTARY AIR SWITCH, 250MM FLY LEAD, SURFACE MOUNTED

Pack size: **1 x EA**

- Manufacturer Series: 6871
- Type: Momentary
- Mounting Type: Surface
- Operation: SPCO
- Fly Lead Length: 250 mm
- For Use With: 3 mm I/D Tubing, Battery Charging Rooms, Garages or Wherever Explosive Gases, Laboratories, Vapours or Powders May Exist



319708 6871

RS PRO 6871 SERIES LATCHING AIR SWITCH, 250MM FLY LEAD, SURFACE MOUNTED

Pack size: **1 x EA**

- Manufacturer Series: 6871
- Type: Latching
- Mounting Type: Surface
- Operation: SPCO
- Fly Lead Length: 250 mm
- For Use With: 3 mm I/D Tubing, Battery Charging Rooms, Garages or Wherever Explosive Gases, Laboratories, Vapours or Powders May Exist



319714 6871

RS PRO 6871 SERIES MOMENTARY AIR SWITCH, 250MM FLY LEAD, PANEL MOUNTED

Pack size: **1 x EA**

- Manufacturer Series: 6871
- Type: Momentary
- Mounting Type: Panel
- Operation: SPCO
- Fly Lead Length: 250 mm
- For Use With: 3 mm I/D Tubing, Battery Charging Rooms, Garages or Wherever Explosive Gases, Laboratories, Vapours or Powders May Exist



319720 6871

RS PRO 687 SERIES MOMENTARY AIR SWITCH, 250MM FLY LEAD, PANEL MOUNTED

Pack size: **1 x EA**

- Manufacturer Series: 687
- Type: Momentary
- Mounting Type: Panel
- Operation: NO/NC
- Fly Lead Length: 250 mm
- For Use With: 3 mm I/D Tubing, Battery Charging Rooms, Garages or Wherever Explosive Gases, Laboratories, Vapours or Powders May Exist



319742 687

RS PRO 6871 SERIES LATCHING AIR SWITCH, 250MM FLY LEAD, PANEL MOUNTED

Pack size: **1 x EA**

- Manufacturer Series: 6871
- Type: Latching
- Mounting Type: Panel
- Operation: SPCO
- Fly Lead Length: 250 mm
- For Use With: 3 mm I/D Tubing, Battery Charging Rooms, Garages or Wherever Explosive Gases, Laboratories, Vapours or Powders May Exist



319736 6871

RS PRO 687 SERIES LATCHING AIR SWITCH, PANEL MOUNTED

Pack size: **1 x EA**

- Manufacturer Series: 687
- Type: Latching
- Mounting Type: Panel
- Operation: NO/NC
- For Use With: 3 mm I/D Tubing, Battery Charging Rooms, Garages or Wherever Explosive Gases, Laboratories, Vapours or Powders May Exist



319758 687

RS PRO RED PILOT LIGHT HEAD, 22.5MM CUTOUT

Pack size: **1 x EA**

- Cutout Diameter: 22.5 mm
- Pilot Light Colour: Red
- Pilot Light Shape: Round
- Pilot Light Material: Plastic
- IP Rating: IP65
- Mounting Type: Panel Mount



1881201 22.5 mm

RS PRO WHITE PILOT LIGHT HEAD, 22.5MM CUTOUT

Pack size: **1 x EA**

- Cutout Diameter: 22.5 mm
- Pilot Light Colour: White
- Pilot Light Shape: Round
- Pilot Light Material: Plastic
- IP Rating: IP65
- Mounting Type: Panel Mount



1881203 22.5 mm

RS PRO YELLOW PILOT LIGHT HEAD, 22.5MM CUTOUT

Pack size: **1 x EA**

- Cutout Diameter: 22.5 mm
- Pilot Light Colour: Yellow
- Pilot Light Shape: Round
- Pilot Light Material: Plastic
- IP Rating: IP65
- Mounting Type: Panel Mount



1881205 22.5 mm

RS PRO GREEN PILOT LIGHT HEAD, 22.5MM CUTOUT

Pack size: **1 x EA**

- Cutout Diameter: 22.5 mm
- Pilot Light Colour: Green
- Pilot Light Shape: Round
- Pilot Light Material: Plastic
- IP Rating: IP65
- Mounting Type: Panel Mount



1881206 22.5 mm

RS PRO BLUE PILOT LIGHT HEAD, 22.5MM CUTOUT

Pack size: **1 x EA**

- Cutout Diameter: 22.5 mm
- Pilot Light Colour: Blue
- Pilot Light Shape: Round
- Pilot Light Material: Plastic
- IP Rating: IP65
- Mounting Type: Panel Mount



1881202 22.5 mm

RS PRO AMBER PILOT LIGHT HEAD, 22.5MM CUTOUT

Pack size: **1 x EA**

- Cutout Diameter: 22.5 mm
- Pilot Light Colour: Amber
- Pilot Light Shape: Round
- Pilot Light Material: Plastic
- IP Rating: IP65
- Mounting Type: Panel Mount



1881207 22.5 mm

RS PRO, PANEL MOUNT RED LED PILOT LIGHT, 22MM CUTOUT, IP65,

Pack size: **1 x EA**

- Pilot Light Type: Pilot Light Complete Unit
- Voltage Rating: 24 V ac/dc
- Pilot Light Colour: Red
- Cutout Diameter: 22 mm
- Lamp Type: LED
- Mounting Type: Panel Mount
- IP Rating: IP65
- Terminal Type: Screw



7637909 Pilot Light

RS PRO, PANEL MOUNT BLUE LED PILOT LIGHT, 22MM CUTOUT, IP65,

Pack size: **1 x EA**

- Pilot Light Type: Pilot Light Complete Unit
- Voltage Rating: 24 V ac/dc
- Pilot Light Colour: Blue
- Cutout Diameter: 22 mm
- Lamp Type: LED
- Mounting Type: Panel Mount
- IP Rating: IP65
- Terminal Type: Screw



7637911 Pilot Light

RS PRO, PANEL MOUNT AMBER LED PILOT LIGHT, 22MM CUTOUT, IP65,

Pack size: **1 x EA**

- Pilot Light Type: Pilot Light Complete Unit
- Voltage Rating: 24 V ac/dc
- Pilot Light Colour: Amber
- Cutout Diameter: 22 mm
- Lamp Type: LED
- Mounting Type: Panel Mount
- IP Rating: IP65
- Terminal Type: Screw



7637915 Pilot Light

RS PRO, PANEL MOUNT GREEN LED PILOT LIGHT, 22MM CUTOUT, IP65,

Pack size: **1 x EA**

- Pilot Light Type: Pilot Light Complete Unit
- Voltage Rating: 24 V ac/dc
- Pilot Light Colour: Green
- Cutout Diameter: 22 mm
- Lamp Type: LED
- Mounting Type: Panel Mount
- IP Rating: IP65
- Terminal Type: Screw



7637918 Pilot Light

RS PRO, PANEL MOUNT RED LED PILOT LIGHT, 22MM CUTOUT, IP65,

Pack size: **1 x EA**

- Pilot Light Type: Pilot Light Complete Unit
- Voltage Rating: 12 V ac/dc
- Pilot Light Colour: Red
- Cutout Diameter: 22 mm
- Lamp Type: LED
- Mounting Type: Panel Mount
- IP Rating: IP65
- Terminal Type: Screw



7918573 Pilot Light

RS PRO, PANEL MOUNT WHITE LED PILOT LIGHT, 22MM CUTOUT, IP65,

Pack size: **1 x EA**

- Pilot Light Type: Pilot Light Complete Unit
- Voltage Rating: 12 V ac/dc
- Pilot Light Colour: White
- Cutout Diameter: 22 mm
- Lamp Type: LED
- Mounting Type: Panel Mount
- IP Rating: IP65
- Terminal Type: Screw



7918579 Pilot Light

RS PRO, PANEL MOUNT GREEN LED PILOT LIGHT, 22MM CUTOUT, IP65,

Pack size: **1 x EA**

- Pilot Light Type: Pilot Light Complete Unit
- Voltage Rating: 12 V ac/dc
- Pilot Light Colour: Green
- Cutout Diameter: 22 mm
- Lamp Type: LED
- Mounting Type: Panel Mount
- IP Rating: IP65
- Terminal Type: Screw



7918582 Pilot Light

RS PRO, PANEL MOUNT BLUE LED PILOT LIGHT, 22MM CUTOUT, IP65,

Pack size: **1 x EA**

- Pilot Light Type: Pilot Light Complete Unit
- Voltage Rating: 12 V ac/dc
- Pilot Light Colour: Blue
- Cutout Diameter: 22 mm
- Lamp Type: LED
- Mounting Type: Panel Mount
- IP Rating: IP65
- Terminal Type: Screw



7918585 Pilot Light

RS PRO, PANEL MOUNT WHITE LED PILOT LIGHT, 22MM CUTOUT, IP65,

Pack size: **1 x EA**

- Pilot Light Type: Pilot Light Complete Unit
- Voltage Rating: 24 V ac/dc
- Pilot Light Colour: White
- Cutout Diameter: 22 mm
- Lamp Type: LED
- Mounting Type: Panel Mount
- IP Rating: IP65
- Terminal Type: Screw



7637905 Pilot Light

RS PRO, PANEL MOUNT AMBER LED PILOT LIGHT, 22MM CUTOUT, IP65,

Pack size: **1 x EA**

- Pilot Light Type: Pilot Light Complete Unit
- Voltage Rating: 12 V ac/dc
- Pilot Light Colour: Amber
- Cutout Diameter: 22 mm
- Lamp Type: LED
- Mounting Type: Panel Mount
- IP Rating: IP65
- Terminal Type: Screw



7918589 Pilot Light

RS PRO, PANEL MOUNT BLUE LED PILOT LIGHT COMPLETE, 16MM

Pack size: **1 x EA**

- Pilot Light Type: Pilot Light Complete Unit
- Voltage Rating: 12 V ac/dc
- Pilot Light Colour: Blue
- Cutout Diameter: 16 mm
- Lamp Type: LED
- Mounting Type: Panel Mount
- IP Rating: IP40
- Terminal Type: Screw



9092415 Pilot Light

RS PRO, PANEL MOUNT GREEN LED PILOT LIGHT COMPLETE, 16MM

Pack size: **1 x EA**

- Pilot Light Type: Pilot Light Complete Unit
- Voltage Rating: 12 V ac/dc
- Pilot Light Colour: Green
- Cutout Diameter: 16 mm
- Lamp Type: LED
- Mounting Type: Panel Mount
- IP Rating: IP40
- Terminal Type: Screw



9092430 Pilot Light

RS PRO, PANEL MOUNT BLUE LED PILOT LIGHT COMPLETE, 16MM

Pack size: **1 x EA**

- Pilot Light Type: Pilot Light Complete Unit
- Voltage Rating: 24 V ac/dc
- Pilot Light Colour: Blue
- Cutout Diameter: 16 mm
- Lamp Type: LED
- Mounting Type: Panel Mount
- IP Rating: IP40
- Terminal Type: Screw



9092424 Pilot Light

RS PRO, PANEL MOUNT RED LED PILOT LIGHT COMPLETE, 22MM

Pack size: **1 x EA**

- Pilot Light Type: Pilot Light Complete Unit
- Voltage Rating: 12 V ac/dc
- Pilot Light Colour: Red
- Cutout Diameter: 22 mm
- Lamp Type: LED
- Mounting Type: Panel Mount
- IP Rating: IP30
- Terminal Type: Screw



9092553 Pilot Light

RS PRO, PANEL MOUNT RED LED PILOT LIGHT COMPLETE, 22MM

Pack size: **1 x EA**

- Pilot Light Type: Pilot Light Complete Unit
- Voltage Rating: 24 V ac/dc
- Pilot Light Colour: Red
- Cutout Diameter: 22 mm
- Lamp Type: LED
- Mounting Type: Panel Mount
- IP Rating: IP30
- Terminal Type: Screw



9092556 Pilot Light

RS PRO 6419 SERIES BANJO THREADED-TO-TUBE ADAPTOR, G 1/8

Pack size: **1 x EA**

- Manufacturer Series: 6419
- Pneumatic Fitting Type: Banjo Threaded-to-Tube Adaptor
- Connection Style: Threaded-to-Tube
- Connector A: G 1/8 Male
- Connector B: Push In 3 mm
- Threaded Connection: 1/8 in Male BSP
- Body Material: Nylon
- Minimum Operating Temperature: -10 °C



317752 6419

RS PRO 6401 SERIES TEE TUBE-TO-TUBE ADAPTOR, PUSH IN 3 MM TO

Pack size: **5 x EA**

- Manufacturer Series: 6401
- Pneumatic Fitting Type: Tee Tube-to-Tube Adaptor
- Connection Style: Tube-to-Tube
- Connector A: Push In 3 mm
- Connector B: Push In 3 mm
- Body Material: Nylon
- Minimum Operating Temperature: -10 °C
- Maximum Operating Temperature: +60 °C



317768 6401

RS PRO BLUE ROUND NO PUSH BUTTON HEAD, SPRING RETURN

Pack size: **1 x EA**

- Cutout Diameter: 22 mm
- Push Button Colour: Blue
- Push Button Actuation: Spring Return
- Push Button Style: Round
- Push Button Material: Plastic
- IP Rating: IP65
- Push Button Diameter: 30.2 mm
- Illuminated: No



1881122 22 mm

RS PRO RED ROUND NO PUSH BUTTON HEAD, SPRING RETURN

Pack size: **1 x EA**

- Cutout Diameter: 22 mm
- Push Button Colour: Red
- Push Button Actuation: Spring Return
- Push Button Style: Round
- Push Button Material: Plastic
- IP Rating: IP65
- Push Button Diameter: 30.2 mm
- Illuminated: No



1881123 22 mm

RS PRO GREEN ROUND NO PUSH BUTTON HEAD, SPRING RETURN

Pack size: **1 x EA**

- Cutout Diameter: 22 mm
- Push Button Colour: Green
- Push Button Actuation: Spring Return
- Push Button Style: Round
- Push Button Material: Plastic
- IP Rating: IP65
- Push Button Diameter: 30.2 mm
- Illuminated: No



1881124 22 mm

RS PRO YELLOW ROUND NO PUSH BUTTON HEAD, SPRING RETURN

Pack size: **1 x EA**

- Cutout Diameter: 22 mm
- Push Button Colour: Yellow
- Push Button Actuation: Spring Return
- Push Button Style: Round
- Push Button Material: Plastic
- IP Rating: IP65
- Push Button Diameter: 30.2 mm
- Illuminated: No



1881126 22 mm

RS PRO BLACK ROUND NO PUSH BUTTON HEAD, SPRING RETURN

Pack size: **1 x EA**

- Cutout Diameter: 22 mm
- Push Button Colour: Black
- Push Button Actuation: Spring Return
- Push Button Style: Round
- Push Button Material: Plastic
- IP Rating: IP65
- Push Button Diameter: 30.2 mm
- Illuminated: No



1881127 22 mm

RS PRO WHITE ROUND NO PUSH BUTTON HEAD, SPRING RETURN

Pack size: **1 x EA**

- Cutout Diameter: 22 mm
- Push Button Colour: White
- Push Button Actuation: Spring Return
- Push Button Style: Round
- Push Button Material: Plastic
- IP Rating: IP65
- Push Button Diameter: 30.2 mm
- Illuminated: No



1881128 22 mm

RS PRO RED ROUND NO PUSH BUTTON HEAD, SPRING RETURN

Pack size: **1 x EA**

- Cutout Diameter: 22 mm
- Push Button Colour: Red
- Push Button Actuation: Spring Return
- Push Button Style: Round
- Push Button Material: Plastic
- IP Rating: IP65
- Push Button Diameter: 30.2 mm
- Illuminated: No



1881129 22 mm

RS PRO RED ROUND NO PUSH BUTTON HEAD, SPRING RETURN

Pack size: **1 x EA**

- Cutout Diameter: 22 mm
- Push Button Colour: Red
- Push Button Actuation: Spring Return
- Push Button Style: Round
- Push Button Material: Plastic
- IP Rating: IP65
- Push Button Diameter: 30.2 mm
- Illuminated: No



1881132 22 mm

RS PRO GREEN ROUND NO PUSH BUTTON HEAD, SPRING RETURN

Pack size: **1 x EA**

- Cutout Diameter: 22 mm
- Push Button Colour: Green
- Push Button Actuation: Spring Return
- Push Button Style: Round
- Push Button Material: Plastic
- IP Rating: IP65
- Push Button Diameter: 30.2 mm
- Illuminated: No



1881133 22 mm

RS PRO RED ROUND NO PUSH BUTTON HEAD, SPRING RETURN

Pack size: **1 x EA**

- Cutout Diameter: 22 mm
- Push Button Colour: Red
- Push Button Actuation: Spring Return
- Push Button Style: Round
- Push Button Material: Plastic
- IP Rating: IP65
- Push Button Diameter: 30.2 mm
- Illuminated: No



1881134 22 mm

RS PRO BLUE ROUND NO PUSH BUTTON HEAD, SPRING RETURN

Pack size: **1 x EA**

- Cutout Diameter: 22 mm
- Push Button Colour: Blue
- Push Button Actuation: Spring Return
- Push Button Style: Round
- Push Button Material: Plastic
- IP Rating: IP65
- Push Button Diameter: 30.2 mm
- Illuminated: No



1881137 22 mm

RS PRO BLACK ROUND NO PUSH BUTTON HEAD, SPRING RETURN

Pack size: **1 x EA**

- Cutout Diameter: 22 mm
- Push Button Colour: Black
- Push Button Actuation: Spring Return
- Push Button Style: Round
- Push Button Material: Plastic
- IP Rating: IP65
- Push Button Diameter: 30.2 mm
- Illuminated: No



1881138 22 mm

RS PRO BLACK ROUND NO PUSH BUTTON HEAD, SPRING RETURN

Pack size: **1 x EA**

- Cutout Diameter: 22 mm
- Push Button Colour: Black
- Push Button Actuation: Spring Return
- Push Button Style: Round
- Push Button Material: Plastic
- IP Rating: IP65
- Push Button Diameter: 30.2 mm
- Illuminated: No



1881139 22 mm

RS PRO GREEN ROUND NO PUSH BUTTON HEAD, SPRING RETURN

Pack size: **1 x EA**

- Cutout Diameter: 22 mm
- Push Button Colour: Green
- Push Button Actuation: Spring Return
- Push Button Style: Round
- Push Button Material: Plastic
- IP Rating: IP65
- Push Button Diameter: 30.2 mm
- Illuminated: No



1881140 22 mm

RS PRO BLUE ROUND NO PUSH BUTTON HEAD, SPRING RETURN

Pack size: **1 x EA**

- Cutout Diameter: 22 mm
- Push Button Colour: Blue
- Push Button Actuation: Spring Return
- Push Button Style: Round
- Push Button Material: Plastic
- IP Rating: IP65
- Push Button Diameter: 30.2 mm
- Illuminated: No



1881141 22 mm

RS PRO RED ROUND NO PUSH BUTTON HEAD, SPRING RETURN

Pack size: **1 x EA**

- Cutout Diameter: 22 mm
- Push Button Colour: Red
- Push Button Actuation: Spring Return
- Push Button Style: Round
- Push Button Material: Plastic
- IP Rating: IP65
- Push Button Diameter: 30.2 mm
- Illuminated: No



1881142 22 mm

RS PRO GREEN ROUND NO PUSH BUTTON HEAD, SPRING RETURN

Pack size: **1 x EA**

- Cutout Diameter: 22 mm
- Push Button Colour: Green
- Push Button Actuation: Spring Return
- Push Button Style: Round
- Push Button Material: Plastic
- IP Rating: IP65
- Push Button Diameter: 30.2 mm
- Illuminated: No



1881143 22 mm

RS PRO YELLOW ROUND NO PUSH BUTTON HEAD, SPRING RETURN

Pack size: **1 x EA**

- Cutout Diameter: 22 mm
- Push Button Colour: Yellow
- Push Button Actuation: Spring Return
- Push Button Style: Round
- Push Button Material: Plastic
- IP Rating: IP65
- Push Button Diameter: 30.2 mm
- Illuminated: No



1881144 22 mm

RS PRO WHITE ROUND NO PUSH BUTTON HEAD, SPRING RETURN

Pack size: **1 x EA**

- Cutout Diameter: 22 mm
- Push Button Colour: White
- Push Button Actuation: Spring Return
- Push Button Style: Round
- Push Button Material: Plastic
- IP Rating: IP65
- Push Button Diameter: 30.2 mm
- Illuminated: No



1881145 22 mm

RS PRO GREEN, RED NO PUSH BUTTON HEAD, SPRING RETURN

Pack size: **1 x EA**

- Cutout Diameter: 22 mm
- Push Button Colour: Green, Red
- Push Button Actuation: Spring Return
- Push Button Material: Plastic
- IP Rating: IP65
- Illuminated: No



1881199 22 mm

RS PRO GREEN, RED NO PUSH BUTTON HEAD, SPRING RETURN

Pack size: **1 x EA**

- Cutout Diameter: 22 mm
- Push Button Colour: Green, Red
- Push Button Actuation: Spring Return
- Push Button Material: Plastic
- IP Rating: IP65
- Illuminated: No



1881200 22 mm

RS PRO BLUE ROUND NO PUSH BUTTON HEAD, MOMENTARY

Pack size: **1 x EA**

- Series: RCAS
- Cutout Diameter: 22 mm
- Push Button Colour: Blue
- Push Button Actuation: Momentary
- Push Button Style: Round
- Push Button Material: Metal
- IP Rating: IP65
- Illuminated: No



2052353 RCAS

RS PRO RED ROUND NO PUSH BUTTON HEAD, MOMENTARY

Pack size: **1 x EA**

- Series: RCAS
- Cutout Diameter: 22 mm
- Push Button Colour: Red
- Push Button Actuation: Momentary
- Push Button Style: Round
- Push Button Material: Metal
- IP Rating: IP65
- Illuminated: No




2052354 RCAS

RS PRO GREEN ROUND NO PUSH BUTTON HEAD, MOMENTARY

Pack size: **1 x EA**

- Series: RCAS
- Cutout Diameter: 22 mm
- Push Button Colour: Green
- Push Button Actuation: Momentary
- Push Button Style: Round
- Push Button Material: Metal
- IP Rating: IP65
- Illuminated: No



2052355 RCAS

RS PRO BLACK ROUND NO PUSH BUTTON HEAD, MOMENTARY

Pack size: **1 x EA**

- Series: RCAS
- Cutout Diameter: 22 mm
- Push Button Colour: Black
- Push Button Actuation: Momentary
- Push Button Style: Round
- Push Button Material: Metal
- IP Rating: IP65
- Illuminated: No



2052358 RCAS

RS PRO WHITE ROUND NO PUSH BUTTON HEAD, MOMENTARY

Pack size: **1 x EA**

- Series: RCAS
- Cutout Diameter: 22 mm
- Push Button Colour: White
- Push Button Actuation: Momentary
- Push Button Style: Round
- Push Button Material: Metal
- IP Rating: IP65
- Illuminated: No



2052359 RCAS

RS PRO RED ROUND NO PUSH BUTTON HEAD, MOMENTARY

Pack size: **1 x EA**

- Series: RCAS
- Cutout Diameter: 22 mm
- Push Button Colour: Red
- Push Button Actuation: Momentary
- Push Button Style: Round
- Push Button Material: Metal
- IP Rating: IP65
- Illuminated: No



2052360 RCAS

RS PRO GREEN ROUND NO PUSH BUTTON HEAD, MOMENTARY

Pack size: **1 x EA**

- Series: RCAS
- Cutout Diameter: 22 mm
- Push Button Colour: Green
- Push Button Actuation: Momentary
- Push Button Style: Round
- Push Button Material: Metal
- IP Rating: IP65
- Illuminated: No



2052361 RCAS

RS PRO GREEN ROUND NO PUSH
BUTTON HEAD, MOMENTARY

Pack size: **1 x EA**

- Series: RCAS
- Cutout Diameter: 22 mm
- Push Button Colour: Green
- Push Button Actuation: Momentary
- Push Button Style: Round
- Push Button Material: Metal
- IP Rating: IP65
- Illuminated: No



2052363 RCAS

RS PRO RED ROUND NO PUSH
BUTTON HEAD, MOMENTARY

Pack size: **1 x EA**

- Series: RCAS
- Cutout Diameter: 22 mm
- Push Button Colour: Red
- Push Button Actuation: Momentary
- Push Button Style: Round
- Push Button Material: Metal
- IP Rating: IP65
- Illuminated: No



2052366 RCAS

RS PRO LOCKING RING WRENCH

Pack size: **1 x EA**

- Accessory Type: Lock Ring Hand Tool
- For Use With: 22 mm LEDtec Indicator, 22 mm LEDtec Push Button



1753953 Lock Ring Hand

RS PRO LEGEND PLATE FOR USE WITH
PTEC PUSH BUTTON, O - I

Pack size: **5 x EA**

- Accessory Type: Legend Plate
- Label Text: O - I
- For Use With: Ptec Push Button



1753954 Legend Plate

RS PRO LEGEND PLATE FOR USE WITH
PTEC PUSH BUTTON, CLOSE

Pack size: **5 x EA**

- Accessory Type: Legend Plate
- Label Text: Close
- For Use With: Ptec Push Button



1753955 Legend Plate

RS PRO LEGEND PLATE FOR USE WITH
PTEC PUSH BUTTON, DOWN

Pack size: **5 x EA**

- Accessory Type: Legend Plate
- Label Text: Down
- For Use With: Ptec Push Button



1753956 Legend Plate

RS PRO LEGEND PLATE FOR USE WITH
PTEC PUSH BUTTON, FORWARD

Pack size: **5 x EA**

- Accessory Type: Legend Plate
- Label Text: Forward
- For Use With: Ptec Push Button



1753958 Legend Plate

RS PRO LEGEND PLATE FOR USE WITH
PTEC PUSH BUTTON, I - O - II

Pack size: **5 x EA**

- Accessory Type: Legend Plate
- Label Text: I - O - II
- For Use With: Ptec Push Button



1753959 Legend Plate

RS PRO LEGEND PLATE FOR USE WITH
PTEC PUSH BUTTON, OFF - ON

Pack size: **5 x EA**

- Accessory Type: Legend Plate
- Label Text: Off - On
- For Use With: Ptec Push Button



1753960 Legend Plate

RS PRO LEGEND PLATE FOR USE WITH
PTEC PUSH BUTTON, OPEN

Pack size: **5 x EA**

- Accessory Type: Legend Plate
- Label Text: Open
- For Use With: Ptec Push Button



1753961 Legend Plate

RS PRO LEGEND PLATE FOR USE WITH
PTEC PUSH BUTTON, RESET

Pack size: **5 x EA**

- Accessory Type: Legend Plate
- Label Text: Reset
- For Use With: Ptec Push Button



1753962 Legend Plate

RS PRO LEGEND PLATE FOR USE WITH
PTEC PUSH BUTTON, REVERSE

Pack size: **5 x EA**

- Accessory Type: Legend Plate
- Label Text: Reverse
- For Use With: Ptec Push Button



1753964 Legend Plate

RS PRO LEGEND PLATE FOR USE WITH
PTEC PUSH BUTTON, START

Pack size: **5 x EA**

- Accessory Type: Legend Plate
- Label Text: Start
- For Use With: Ptec Push Button



1753965 Legend Plate

RS PRO LEGEND PLATE FOR USE WITH
PTEC PUSH BUTTON, STOP

Pack size: **5 x EA**

- Accessory Type: Legend Plate
- Label Text: Stop
- For Use With: Ptec Push Button



1753966 Legend Plate

RS PRO LEGEND PLATE FOR USE WITH
PTEC PUSH BUTTON, UP

Pack size: **5 x EA**

- Accessory Type: Legend Plate
- Label Text: Up
- For Use With: Ptec Push Button



1753967 Legend Plate

RS PRO PUSH BUTTON SWITCH

Pack size: **1 x EA**

- Manufacturer Part No.: 6438-0012



1900434 6438-0012

RS PRO PUSH BUTTON SWITCH

Pack size: 1 x EA
• Manufacturer Part No.: 6438-0011



1900440 6438-0011

RS PRO PUSH BUTTON SWITCH

Pack size: 1 x EA
• Manufacturer Part No.: 6438-0009



1900456 6438-0009

RS PRO PUSH BUTTON SWITCH

Pack size: 1 x EA
• Manufacturer Part No.: 6438-0010



1900478 6438-0010

RS PRO PUSH BUTTON SWITCH

Pack size: 1 x EA
• Manufacturer Part No.: 6442-0028



8370975 6442-0028

RS PRO GASKET, FOR USE WITH
PANEL AND DOOR ISOLATOR

Pack size: 1 x EA
• Accessory Type: Gasket
• For Use With: Panel and Door Isolator
• IP Rating: IP65



7737995 Gasket

RS PRO AIR SWITCH ACTUATOR

Pack size: 1 x EA
• Manufacturer Series: 6470



317055 6470

RS PRO AIR SWITCH ACTUATOR

Pack size: 1 x EA
• Manufacturer Series: 6442



317730 6442

WIRE,BRAID,COPPER,FLAT,TINNED,1.9X0.6MM,25M,10A

Pack size: **25 x MTR**

- Size: 1.9 x 0.6 mm
- Conductor Material: Tinned Copper
- Cross Sectional Area: 0.5 mm²
- Current Rating: 10 A
- Length: 25 m
- Conductor Resistance: 35 Ω/km
- Cable Shape: Single Core
- Standards Met: BS4109



358006 1.9 x 0.6 mm

WIRE,BRAID,COPPER,FLAT,TINNED,5X0.7MM,25M,30A

Pack size: **25 x MTR**

- Size: 5 x 0.8 mm
- Conductor Material: Tinned Copper
- Cross Sectional Area: 1.7 mm²
- Current Rating: 30 A
- Length: 25 m
- Conductor Resistance: 10.44 Ω/km
- Cable Shape: Single Core
- Standards Met: BS4109



358012 4 x 0.8 mm

WIRE,BRAID,COPPER,FLAT,TINNED,10X2MM,25M,63A

Pack size: **25 x MTR**

- Size: 10 x 2 mm
- Conductor Material: Tinned Copper
- Cross Sectional Area: 7.5 mm²
- Current Rating: 63 A
- Length: 25 m
- Conductor Resistance: 2.349 Ω/km
- Cable Shape: Single Core
- Standards Met: BS4109



365543 10 x 2 mm

RS PRO BRAIDED WIRE 90 A, 24 X 12 X 0.20 MM, 25M BS4109

Pack size: **25 x MTR**

- Size: 24 x 12 x 0.20 mm
- Conductor Material: Tinned Copper
- Cross Sectional Area: 9.05 mm²
- Current Rating: 90 A
- Length: 25 m
- Conductor Resistance: 1.91 Ω/km
- Cable Shape: Single Core
- Standards Met: BS4109



365559 24 x 12 x 0.20 mm

EARTH,STRAP,ASSEMBLY,25MM,CSA BRAID,M8,500MM

Pack size: **1 x EA**

- Size: 3 x 2 x 16 x 0.2 mm
- Conductor Material: Tinned Copper
- Cross Sectional Area: 36.19 mm²
- Length: 0.5 m
- Conductor Resistance: 0.481 Ω/km
- Stud Size: M8
- Cable Shape: Single Core
- Standards Met: BS EN 13602:2002, BS4109



489153 3 x 2 x 16 x 0.2

EARTH,STRAP,ASSEMBLY,25MM,CSA BRAID,M8,400MM

Pack size: **1 x EA**

- Size: 2 x 24 x 16 x 0.2 mm
- Conductor Material: Tinned Copper
- Cross Sectional Area: 24.13 mm²
- Length: 0.4 m
- Conductor Resistance: 734 Ω/km
- Stud Size: M8
- Cable Shape: Single Core
- Standards Met: BS EN 13602:2002, BS4109



489157 2 x 24 x 16 x 0.2

EARTH,STRAP,ASSEMBLY,15MM,CSA BRAID,M6,250MM

Pack size: **1 x EA**

- Size: 24 x 20 x 0.2 mm
- Conductor Material: Tinned Copper
- Cross Sectional Area: 15.08 mm²
- Length: 0.25 m
- Conductor Resistance: 1174 Ω/km
- Stud Size: M6
- Cable Shape: Single Core
- Standards Met: BS EN 13602:2002, BS4109



489163 24 x 20 x 0.2 mm

EARTH,STRAP,ASSEMBLY,15MM,CSA BRAID,M6,150MM

Pack size: **1 x EA**

- Size: 24 x 20 x 0.2 mm
- Conductor Material: Tinned Copper
- Cross Sectional Area: 15.08 mm²
- Length: 0.4 m
- Conductor Resistance: 1174 Ω/km
- Stud Size: M6
- Cable Shape: Single Core
- Standards Met: BS EN 13602:2002, BS4109



489169 24 x 20 x 0.2 mm

EARTH,STRAP,ASSEMBLY,1.13MM,CSA BRAID,M3.5,100MM

Pack size: **1 x EA**

- Size: 16 x 4 x 0.15 mm
- Conductor Material: Tinned Copper
- Cross Sectional Area: 1.13 mm²
- Length: 0.1 m
- Conductor Resistance: 15.41 Ω/km
- Stud Size: M3.5
- Cable Shape: Single Core
- Standards Met: BS EN 13602:2002, BS4109



489179 16 x 4 x 0.15 mm

EARTH,STRAP,ASSEMBLY,2.26MM,CSA BRAID,M8,200MM

Pack size: **1 x EA**

- Size: 16 x 8 x 0.15 mm
- Conductor Material: Tinned Copper
- Cross Sectional Area: 2.26 mm²
- Length: 0.2 m
- Conductor Resistance: 7830 Ω/km
- Stud Size: M8
- Cable Shape: Single Core
- Standards Met: BS EN 13602:2002, BS4109



489185 16 x 8 x 0.15 mm

RS PRO BRAIDED WIRE, M5 STUD SIZE, DIA 0.2 MM, 0.2M BS EN

Pack size: **1 x EA**

- Size: Dia 0.2 mm
- Conductor Material: Tinned Copper
- Length: 0.2 m
- Conductor Resistance: 2349 Ω/km
- Stud Size: M5
- Cable Shape: Earth Lead
- Standards Met: BS EN 13602:2002, BS4109



489191 Dia 0.2 mm

EARTH,STRAP,ASSEMBLY,10MM,CSA BRAID,M5,100MM

Pack size: **1 x EA**

- Size: 16 x 20 x 0.2 mm
- Conductor Material: Tinned Copper
- Cross Sectional Area: 10.05 mm²
- Length: 0.1 m
- Conductor Resistance: 1762 Ω/km
- Stud Size: M5
- Cable Shape: Single Core
- Standards Met: BS EN 13602:2002, BS4109



489197 16 x 20 x 0.2 mm

EARTH,STRAP,ASSEMBLY,8.29MM,CSA BRAID,M5,150MM

Pack size: **1 x EA**

- Size: 24 x 11 x 0.2 mm
- Conductor Material: Tinned Copper
- Cross Sectional Area: 8.29 mm²
- Length: 0.15 m
- Conductor Resistance: 2.1 Ω/km
- Stud Size: M5
- Cable Shape: Single Core
- Standards Met: BS EN 13602:2002, BS4109



489204 24 x 11 x 0.2 mm

EARTH,STRAP,ASSEMBLY,10MM,CSA BRAID,M5,150MM

Pack size: **1 x EA**

- Size: 16 x 20 x 0.2 mm
- Conductor Material: Tinned Copper
- Cross Sectional Area: 10.05 mm²
- Length: 0.15 m
- Conductor Resistance: 1762 Ω/km
- Stud Size: M5
- Cable Shape: Single Core
- Standards Met: BS EN 13602:2002, BS4109



489208 16 x 20 x 0.2 mm

EARTH,STRAP,ASSEMBLY,15MM,CSA BRAID,M6,150MM

Pack size: **1 x EA**

- Size: 24 x 20 x 0.2 mm
- Conductor Material: Tinned Copper
- Cross Sectional Area: 10.05 mm²
- Length: 0.15 m
- Conductor Resistance: 1762 Ω/km
- Stud Size: M6
- Cable Shape: Single Core
- Standards Met: BS EN 13602:2002, BS4109



489210 24 x 20 x 0.2 mm

EARTH,STRAP,ASSEMBLY,10MM,CSA BRAID,M5,200MM

Pack size: **1 x EA**

- Size: 16 x 20 x 0.2 mm
- Conductor Material: Tinned Copper
- Cross Sectional Area: 10.05 mm²
- Length: 0.2 m
- Conductor Resistance: 1762 Ω/km
- Stud Size: M5
- Cable Shape: Single Core
- Standards Met: BS EN 13602:2002, BS4109



489214 16 x 20 x 0.2 mm

RS PRO DIN RAIL MOUNT INTERFACE RELAY, 24V AC/DC COIL, 6A LOAD

Pack size: **1 x EA**

- Coil Voltage: 24 V ac/dc
- Maximum Input Voltage: 24 V dc
- Contact Configuration: SPDT
- Mounting Type: DIN Rail
- Load Current Rating: 6 A
- Length: 96 mm
- Depth: 6.2 mm
- Height: 78.8 mm



1441579 24 V ac/dc

RS PRO DIN RAIL MOUNT INTERFACE RELAY, 12V AC/DC COIL, 6A LOAD

Pack size: **1 x EA**

- Coil Voltage: 12 V ac/dc
- Contact Configuration: SPDT
- Mounting Type: DIN Rail
- Load Current Rating: 6 A
- Length: 96 mm
- Depth: 6.2 mm
- Height: 78.8 mm
- Input Current: 8 A



1441578 12 V ac/dc

RS PRO DIN RAIL MOUNT INTERFACE RELAY, 48V AC/DC COIL, 6A LOAD

Pack size: **1 x EA**

- Coil Voltage: 48 V ac/dc
- Maximum Input Voltage: 48 V dc
- Contact Configuration: SPDT
- Mounting Type: DIN Rail
- Load Current Rating: 6 A
- Length: 96 mm
- Depth: 6.2 mm
- Height: 78.8 mm



1441580 48 V ac/dc

RS PRO DIN RAIL MOUNT INTERFACE RELAY, 12V AC/DC COIL, SPDT

Pack size: **1 x EA**

- Coil Voltage: 12 V ac/dc
- Contact Configuration: SPDT
- Mounting Type: DIN Rail
- Length: 96 mm
- Depth: 6.2 mm
- Height: 103 mm
- Input Current: 8 A
- Minimum Operating Temperature: -40 °C



1441584 12 V ac/dc

RS PRO DIN RAIL MOUNT INTERFACE RELAY, 24V DC COIL, SPDT

Pack size: **1 x EA**

- Coil Voltage: 24 V dc
- Contact Configuration: SPDT
- Mounting Type: DIN Rail
- Length: 96 mm
- Depth: 6.2 mm
- Height: 103 mm
- Input Current: 8 A
- Minimum Operating Temperature: -40 °C



1441585 24 V dc

RS PRO DIN RAIL MOUNT INTERFACE RELAY, 48V AC/DC COIL, SPDT

Pack size: **1 x EA**

- Coil Voltage: 48 V ac/dc
- Contact Configuration: SPDT
- Mounting Type: DIN Rail
- Length: 96 mm
- Depth: 6.2 mm
- Height: 103 mm
- Input Current: 8 A
- Minimum Operating Temperature: -40 °C



1441586 48 V ac/dc

RS PRO DIN RAIL MOUNT INTERFACE RELAY, 24V DC COIL, SPDT

Pack size: **1 x EA**

- Coil Voltage: 24 V dc
- Contact Configuration: SPDT
- Mounting Type: DIN Rail
- Terminal Type: Screw
- Length: 6.2 mm
- Depth: 73 mm
- Height: 93 mm
- Contact Material: Silver Alloy



8886792 24 V dc

RS PRO DIN RAIL MOUNT INTERFACE RELAY, 24V DC COIL, SPDT

Pack size: **5 x EA**

- Coil Voltage: 24 V dc
- Contact Configuration: SPDT
- Mounting Type: DIN Rail
- Terminal Type: Screw
- Length: 6.2 mm
- Depth: 86 mm
- Height: 78 mm
- Contact Material: Silver Alloy



8886798 24 V dc

RS PRO DIN RAIL MOUNT INTERFACE RELAY, 24V DC COIL, SPDT

Pack size: **5 x EA**

- Minimum Input Voltage: 19.2 V
- Coil Voltage: 24 V dc
- Maximum Input Voltage: 30 V
- Contact Configuration: SPDT
- Mounting Type: DIN Rail
- Switching Voltage: 17 → 250 V
- Terminal Type: Screw
- Length: 6.2 mm



8886802 19.2 V

RS PRO DIN RAIL MOUNT INTERFACE RELAY, 24V DC COIL, SPDT

Pack size: **5 x EA**

- Coil Voltage: 24 V dc
- Minimum Input Voltage: 19.2 V
- Maximum Input Voltage: 30 V
- Contact Configuration: SPDT
- Mounting Type: DIN Rail
- Switching Voltage: 1 → 250 V
- Terminal Type: Screw
- Length: 6.2 mm



8886805 24 V dc

RS PRO DIN RAIL MOUNT INTERFACE RELAY, 24V AC/DC COIL, SPDT

Pack size: **5 x EA**

- Coil Voltage: 24 V ac/dc
- Contact Configuration: SPDT
- Mounting Type: DIN Rail
- Terminal Type: Screw
- Length: 6.2 mm
- Depth: 73 mm
- Height: 93 mm
- Contact Material: Silver Alloy



8886809 24 V ac/dc

RS PRO DIN RAIL MOUNT INTERFACE RELAY, 24V AC/DC COIL, SPDT

Pack size: **5 x EA**

- Coil Voltage: 24 V ac/dc
- Minimum Input Voltage: 19.2 V
- Maximum Input Voltage: 30 V
- Contact Configuration: SPDT
- Mounting Type: DIN Rail
- Switching Voltage: 17 → 250 V
- Terminal Type: Screw
- Length: 6.2 mm



8886811 24 V ac/dc

RS PRO DIN RAIL MOUNT INTERFACE RELAY, 24V AC/DC COIL, SPDT

Pack size: **5 x EA**

- Coil Voltage: 24 V ac/dc
- Contact Configuration: SPDT
- Mounting Type: DIN Rail
- Terminal Type: Screw
- Length: 6.2 mm
- Depth: 73 mm
- Height: 93 mm
- Contact Material: Silver Alloy



8886818 24 V ac/dc

RS PRO DIN RAIL MOUNT INTERFACE RELAY, 24V AC/DC COIL, SPDT

Pack size: **5 x EA**

- Coil Voltage: 24 V ac/dc
- Minimum Input Voltage: 19.2 V
- Maximum Input Voltage: 30 V
- Contact Configuration: SPDT
- Mounting Type: DIN Rail
- Switching Voltage: 1 → 250 V
- Terminal Type: Screw
- Length: 6.2 mm



8886815 24 V ac/dc

RS PRO DIN RAIL MOUNT INTERFACE RELAY, 24V DC COIL, SPDT

Pack size: **5 x EA**

- Coil Voltage: 24 V dc
- Contact Configuration: SPDT
- Mounting Type: DIN Rail
- Switching Voltage: 250 V ac/dc
- Terminal Type: Push In
- Length: 6.2 mm
- Depth: 76 mm
- Series: LCIS



8886871 24 V dc

RS PRO DIN RAIL MOUNT INTERFACE RELAY, 24V DC COIL, SPDT

Pack size: **5 x EA**

- Coil Voltage: 24 V dc
- Contact Configuration: SPDT
- Mounting Type: DIN Rail
- Terminal Type: Push In
- Length: 6.2 mm
- Depth: 73 mm
- Height: 93 mm
- Contact Material: Silver Alloy



8886874 24 V dc

RS PRO DIN RAIL MOUNT INTERFACE RELAY, 24V DC COIL, SPDT

Pack size: **5 x EA**

- Coil Voltage: 24 V dc
- Contact Configuration: SPDT
- Mounting Type: DIN Rail
- Switching Voltage: 250 V ac/dc
- Terminal Type: Push In
- Length: 6.2 mm
- Series: LCIS
- Depth: 76 mm



8886877 24 V dc

PUSH 6.2MM RLY 24VAC/DC 1 C/O 6A 250VAC

Pack size: **5 x EA**

- Coil Voltage: 24 V ac/dc
- Contact Configuration: SPDT
- Mounting Type: DIN Rail
- Terminal Type: Push In
- Length: 6.2 mm
- Depth: 73 mm
- Height: 93 mm
- Contact Material: Silver Alloy



8886880 24 V ac/dc

RS PRO DIN RAIL MOUNT INTERFACE RELAY, 24V AC/DC COIL, SPDT

Pack size: **5 x EA**

- Coil Voltage: 24 V ac/dc
- Contact Configuration: SPDT
- Mounting Type: DIN Rail
- Switching Voltage: 250 V ac/dc
- Terminal Type: Push In
- Length: 6.2 mm
- Depth: 76 mm
- Series: LCIS



8886896 24 V ac/dc

INTERFACE RELAY MODULE BUSBAR FOR USE WITH INTERFACE RELAY

Pack size: **1 x EA**

- Accessory Type: Jumper Bar
- For Use With: Interface Relay



1441590 Jumper Bar

RELAY JUMPER BAR

Pack size: **10 x EA**

- Maximum Load Current: 6 A
- Terminal Type: Plug In
- Number of Poles: 8
- Operating Temperature Range: -40 → +80 °C
- Standards Met: RoHS Compliant
- Length: 70 mm



8886944 6 A

RELAY JUMPER BAR

Pack size: **10 x EA**

- Maximum Load Current: 6 A
- Terminal Type: Plug In
- Number of Poles: 16
- Operating Temperature Range: -40 → +80 °C
- Standards Met: RoHS Compliant
- Length: 79 mm



8886953 6 A

RS PRO JUMPER MALE STRAIGHT BEIGE JUMPER LINK 2 WAY 1 ROW

Pack size: **1 x EA**

- Type: Jumper Link
- Number of Contacts: 2
- Pitch: 6.1 mm
- Gender: Male
- Colour: Beige
- Number of Rows: 1
- Width: 6.1 mm
- Series: RS Pro



2125490 Jumper Link

RS PRO JUMPER MALE STRAIGHT BEIGE JUMPER LINK 10 WAY 1 ROW

Pack size: **1 x EA**

- Type: Jumper Link
- Number of Contacts: 10
- Pitch: 6.1 mm
- Gender: Male
- Colour: Beige
- Number of Rows: 1
- Width: 60.4 mm
- Series: RS Pro



2125491 Jumper Link

RS PRO LINEAR SOLENOID, 24 V DC, 26 X 16 X 20 MM

Pack size: **1 x EA**

- Action: Pull
- Supply Voltage: 24 V dc
- Dimensions: 26 x 16 x 20 mm



1770113 Pull

RS PRO LINEAR SOLENOID, 24 V DC, 29.35 X 15.9 X 19.1 MM

Pack size: **1 x EA**

- Action: Push
- Supply Voltage: 24 V dc
- Dimensions: 29.35 x 15.9 x 19.1 mm



1770114 Push

RS PRO LINEAR SOLENOID, 12 V, 40 X 14 X 19 MM

Pack size: **1 x EA**

- Action: Pull
- Supply Voltage: 12 V
- Dimensions: 40 x 14 x 19 mm



1770115 Pull

RS PRO LINEAR SOLENOID, 12 V, 37 X 20.3 X 26 MM

Pack size: **1 x EA**

- Action: Pull
- Supply Voltage: 12 V
- Dimensions: 37 x 20.3 x 26 mm



1770116 Pull

RS PRO LINEAR SOLENOID, 24 V DC, 40 X 24 X 29 MM

Pack size: **1 x EA**

- Action: Pull
- Supply Voltage: 24 V dc
- Dimensions: 40 x 24 x 29 mm



1770117 Pull

RS PRO LINEAR SOLENOID, 12 V, 40 X 24 X 29 MM

Pack size: **1 x EA**

- Action: Pull
- Supply Voltage: 12 V
- Dimensions: 40 x 24 x 29 mm



1770118 Pull

RS PRO LINEAR SOLENOID, 6 V DC, 40 X 24 X 29 MM

Pack size: **1 x EA**

- Action: Pull
- Supply Voltage: 6 V dc
- Dimensions: 40 x 24 x 29 mm



1770119 Pull

RS PRO LINEAR SOLENOID, 12 V, 53.5 X 27 X 30 MM

Pack size: **1 x EA**

- Action: Pull
- Supply Voltage: 12 V
- Dimensions: 53.5 x 27 x 30 mm



1770120 Pull

RS PRO LINEAR SOLENOID, 24 V DC, 64 X 30 X 38 MM

Pack size: **1 x EA**

- Action: Pull
- Supply Voltage: 24 V dc
- Dimensions: 64 x 30 x 38 mm



1770121 Pull

RS PRO LINEAR SOLENOID, 12 V, 35.5 X 25.4 X 31.8 MM

Pack size: **1 x EA**

- Action: Pull
- Supply Voltage: 12 V
- Dimensions: 35.5 x 25.4 x 31.8 mm



1770122 Pull

RS PRO LINEAR SOLENOID, 24 V DC, 35.5 X 25.4 X 31.8 MM

Pack size: **1 x EA**

- Action: Pull
- Supply Voltage: 24 V dc
- Dimensions: 35.5 x 25.4 x 31.8 mm



1770123 Pull

RS PRO LINEAR SOLENOID, 24 V DC, 58 X 25.4 X 31.8 MM

Pack size: **1 x EA**

- Action: Pull
- Supply Voltage: 24 V dc
- Dimensions: 58 x 25.4 x 31.8 mm



1770125 Pull

RS PRO LINEAR SOLENOID, 12 V, 58 X 25.4 X 31.8 MM

Pack size: **1 x EA**

- Action: Pull
- Supply Voltage: 12 V
- Dimensions: 58 x 25.4 x 31.8 mm



1770127 Pull

RS PRO LINEAR SOLENOID, 12 V, 44 X 32 X 38 MM

Pack size: **1 x EA**

- Action: Pull
- Supply Voltage: 12 V
- Dimensions: 44 x 32 x 38 mm



1770128 Pull

RS PRO LINEAR SOLENOID, 24 V DC, 50 X 37 X 41 MM

Pack size: **1 x EA**

- Action: Pull
- Supply Voltage: 24 V dc
- Dimensions: 50 x 37 x 41 mm



1770130 Pull

RS PRO LINEAR SOLENOID, 12 V, 50 X 37 X 41 MM

Pack size: **1 x EA**

- Action: Pull
- Supply Voltage: 12 V
- Dimensions: 50 x 37 x 41 mm



1770131 Pull

RS PRO LINEAR SOLENOID, 12 V, 84 X 52 X 58 MM

Pack size: **1 x EA**

- Action: Pull
- Supply Voltage: 12 V
- Dimensions: 84 x 52 x 58 mm



1770134 Pull

RS PRO LINEAR SOLENOID, 12 V, 42.5 X 40.9 X 40.9 MM

Pack size: **1 x EA**

- Action: Pull
- Supply Voltage: 12 V
- Dimensions: 42.5 x 40.9 x 40.9 mm



1770135 Pull

RS PRO LINEAR SOLENOID, 6 V DC, 42.5 X 40.9 X 40.9 MM

Pack size: **1 x EA**

- Action: Pull
- Supply Voltage: 6 V dc
- Dimensions: 42.5 x 40.9 x 40.9 mm



1770136 Pull

RS PRO LINEAR SOLENOID, 6 V DC, 16 X 13 X 20 MM

Pack size: **1 x EA**

- Power Consumption: 15 W
- Supply Voltage: 6 V dc
- Plunger Diameter: 5 mm
- Product Height: 16 mm
- Product Width: 13 mm
- Product Depth: 20 mm
- Dimensions: 16 x 13 x 20 mm



1770137 15 W

RS PRO LINEAR SOLENOID, 12 V, 16 X 14 X 30 MM

Pack size: **1 x EA**

- Power Consumption: 30 W
- Supply Voltage: 12 V
- Plunger Diameter: 7 mm
- Product Height: 16 mm
- Product Width: 14 mm
- Product Depth: 30 mm
- Dimensions: 16 x 14 x 30 mm



1770138 30 W

RS PRO LINEAR SOLENOID, 12 V, 26 X 20 X 36.8 MM

Pack size: **1 x EA**

- Power Consumption: 40 W
- Supply Voltage: 12 V
- Plunger Diameter: 10 mm
- Product Height: 26 mm
- Product Width: 20 mm
- Product Depth: 36.8 mm
- Dimensions: 26 x 20 x 36.8 mm



1770139 40 W

RS PRO LINEAR SOLENOID, 24 V DC, 30 X 27 X 53.5 MM

Pack size: **1 x EA**

- Power Consumption: 80 W
- Supply Voltage: 24 V dc
- Plunger Diameter: 12 mm
- Product Height: 30 mm
- Product Width: 27 mm
- Product Depth: 53.5 mm
- Dimensions: 30 x 27 x 53.5 mm



1770140 80 W

RS PRO LINEAR SOLENOID, 24 V DC

Pack size: **1 x EA**

- Supply Voltage: 24 V dc
- Action: Pull



1770141 24 V dc

RS PRO LINEAR SOLENOID, 12 V

- Pack size: **1 x EA**
- Supply Voltage: 12 V
 - Action: Pull



1770142 12 V

RS PRO LINEAR SOLENOID, 24 V DC

- Pack size: **1 x EA**
- Action: Pull
 - Supply Voltage: 24 V dc
 - Maximum Stroke: 10 mm



1770143 Pull

RS PRO LINEAR SOLENOID, 12 V

- Pack size: **1 x EA**
- Action: Pull
 - Supply Voltage: 12 V
 - Maximum Stroke: 10 mm



1770144 Pull

RS PRO LINEAR SOLENOID, 24 V DC

- Pack size: **1 x EA**
- Supply Voltage: 24 V dc
 - Action: Pull



1770145 24 V dc

RS PRO LINEAR SOLENOID, 24 V DC

- Pack size: **1 x EA**
- Supply Voltage: 24 V dc
 - Action: Pull



1770146 24 V dc

BATTERY VOLTAGE ALARM RELAY

- Pack size: **1 x EA**
- Monitoring Application: Voltage
 - Contact Configuration: SPDT
 - Voltage Sensitivity: Undervoltage
 - Electrical Phase: 1
 - Voltage Sensing Range: 12 → 24 V dc
 - Time Delay: 0 → 30 s
 - Mounting Type: DIN Rail
 - Series: L



1026130 Voltage

RS PRO DIN RAIL VOLTAGE MONITORING RELAY, 48 → 63HZ, 1

- Pack size: **1 x EA**
- Monitoring Application: Voltage
 - Contact Configuration: SPDT
 - Voltage Sensitivity: Overvoltage, Undervoltage
 - Electrical Phase: 1
 - Time Delay: 0.2 → 10 s
 - Frequency Sensing Range: 48 → 63 Hz
 - Mounting Type: DIN Rail
 - Series: L



1026131 Voltage

RS PRO DIN RAIL VOLTAGE MONITORING RELAY, MAXIMUM OF

- Pack size: **1 x EA**
- Monitoring Application: Voltage
 - Contact Configuration: SPDT
 - Voltage Sensitivity: Overvoltage, Undervoltage
 - Electrical Phase: 1
 - Voltage Sensing Range: Maximum of 500 V
 - Time Delay: 0.1 → 30 s
 - Frequency Sensing Range: 48 → 63 Hz
 - Mounting Type: DIN Rail



1026133 Voltage

RS PRO DIN RAIL CURRENT MONITORING RELAY, 1 → 10A, 48 →

- Pack size: **1 x EA**
- Monitoring Application: Current
 - Contact Configuration: SPDT
 - Electrical Phase: 1
 - Current Sensitivity: Overcurrent, Undercurrent
 - Minimum Current Sensed: 1 A
 - Maximum Current Sensed: 10 A
 - Time Delay: 0.1 → 30 s
 - Mounting Type: DIN Rail



1026134 Current

RS PRO DIN RAIL PHASE, VOLTAGE MONITORING RELAY, MAXIMUM OF

- Pack size: **1 x EA**
- Monitoring Application: Phase, Voltage
 - Contact Configuration: SPDT
 - Voltage Sensitivity: Undervoltage
 - Electrical Phase: 3
 - Voltage Sensing Range: Maximum of 280 V
 - Phase Sensitivity: Phase Failure, Phase Sequence
 - Time Delay: 100 ms
 - Mounting Type: DIN Rail



1026135 Phase, Voltage

RS PRO DIN RAIL PHASE, VOLTAGE MONITORING RELAY, 48 → 63HZ, 3

- Pack size: **1 x EA**
- Monitoring Application: Phase, Voltage
 - Contact Configuration: SPDT
 - Voltage Sensitivity: Undervoltage
 - Electrical Phase: 3
 - Phase Sensitivity: Phase Failure, Phase Sequence
 - Time Delay: 0.2 → 10 s
 - Frequency Sensing Range: 48 → 63 Hz
 - Mounting Type: DIN Rail



1026136 Phase, Voltage

RS PRO DIN RAIL PHASE, VOLTAGE MONITORING RELAY, 48 → 63HZ, 3

- Pack size: **1 x EA**
- Monitoring Application: Phase, Voltage
 - Contact Configuration: SPDT
 - Voltage Sensitivity: Overvoltage, Undervoltage
 - Electrical Phase: 3
 - Phase Sensitivity: Phase Failure, Phase Sequence
 - Time Delay: 0.2 → 10 s
 - Series: L
 - Frequency Sensing Range: 48 → 63 Hz



1026137 Phase, Voltage

RS PRO PLUGGABLE FUNCTION MODULE, LED MODULE FOR USE WITH

- Pack size: **1 x EA**
- Accessory Type: LED Module
 - For Use With: RFT Relay



1441613 LED Module

RS PRO PLUGGABLE FUNCTION MODULE, RC CIRCUIT FOR USE WITH

- Pack size: **1 x EA**
- Accessory Type: RC Circuit
 - For Use With: RFT Relay



1441616 RC Circuit

RS PRO PLUG IN POWER RELAY, 12V DC COIL, 10A SWITCHING CURRENT,

- Pack size: **1 x EA**
- Coil Voltage: 12 V dc
 - Contact Configuration: DPDT
 - Mounting Type: Plug In
 - Switching Current: 10 A
 - Number of Poles: 2
 - Latching: No
 - Terminal Type: Through Hole
 - Coil Resistance: 120 Ω



348756 12 V dc

RS PRO PLUG IN POWER RELAY, 230V AC COIL, 10A SWITCHING CURRENT,

- Pack size: **1 x EA**
- Coil Voltage: 230 V ac
 - Contact Configuration: DPDT
 - Mounting Type: Plug In
 - Switching Current: 10 A
 - Number of Poles: 2
 - Latching: No
 - Terminal Type: Through Hole
 - Coil Resistance: 8.2 kΩ



348762 230 V ac

RS PRO, 115V AC COIL NON-LATCHING RELAY DPDT, 10A

Pack size: **1 x EA**

- Coil Voltage: 115 V ac
- Coil Power: 2 W
- Coil Resistance: 2 k Ω
- Isolation Coil To Contact: 1.5 kV ac
- Contact Configuration: DPDT
- Mounting Type: Plug In
- Switching Current: 10 A
- Terminal Type: Through Hole



348778 115 V ac

RS PRO PLUG IN POWER RELAY, 24V DC COIL, 10A SWITCHING CURRENT,

Pack size: **1 x EA**

- Coil Voltage: 24 V dc
- Contact Configuration: DPDT
- Mounting Type: Plug In
- Switching Current: 10 A
- Number of Poles: 2
- Latching: No
- Terminal Type: Through Hole
- Coil Resistance: 478 Ω



348784 24 V dc

11PIN 3PDT PLUG-IN RELAY, 10A 230VAC COIL

Pack size: **1 x EA**

- Coil Voltage: 230 V ac
- Contact Configuration: 3PDT
- Mounting Type: Plug In
- Switching Current: 10 A
- Number of Poles: 3
- Latching: No
- Terminal Type: Through Hole
- Coil Resistance: 8.2 k Ω



348813 230 V ac

RELAY, 11 PIN, 24VDC COIL, 475 OHM, 10A, 3PCO

Pack size: **1 x EA**

- Coil Voltage: 24 V dc
- Contact Configuration: 3PDT
- Mounting Type: Plug In
- Switching Current: 10 A
- Number of Poles: 3
- Latching: No
- Terminal Type: Through Hole
- Coil Resistance: 478 Ω



348829 24 V dc

RS PRO PLUG IN POWER RELAY, 115V AC COIL, 10A SWITCHING CURRENT,

Pack size: **1 x EA**

- Coil Voltage: 115 V ac
- Contact Configuration: 3PDT
- Mounting Type: Plug In
- Switching Current: 10 A
- Number of Poles: 3
- Latching: No
- Terminal Type: Through Hole
- Coil Resistance: 2 k Ω



349282 115 V ac

RS PRO PLUG IN POWER RELAY, 24V AC COIL, 10A SWITCHING CURRENT,

Pack size: **1 x EA**

- Coil Voltage: 24 V ac
- Contact Configuration: DPDT
- Mounting Type: Plug In
- Switching Current: 10 A
- Number of Poles: 2
- Latching: No
- Terminal Type: Through Hole
- Coil Resistance: 85 Ω



349327 24 V ac

RS PRO PLUG IN POWER RELAY, 12V DC COIL, 5A SWITCHING CURRENT,

Pack size: **1 x EA**

- Coil Voltage: 12 V dc
- Contact Configuration: 4PDT
- Mounting Type: Plug In
- Switching Current: 5 A
- Number of Poles: 4
- Latching: No
- Terminal Type: Plug In
- Coil Power: 150 W



121795 12 V dc

RS PRO PLUG IN POWER RELAY, 24V DC COIL, 5A SWITCHING CURRENT,

Pack size: **1 x EA**

- Coil Voltage: 24 V dc
- Contact Configuration: 4PDT
- Mounting Type: Plug In
- Switching Current: 5 A
- Number of Poles: 4
- Latching: No
- Terminal Type: Plug In
- Coil Power: 150 W



121796 24 V dc

RS PRO PLUG IN POWER RELAY, 24V DC COIL, 6A SWITCHING CURRENT,

Pack size: **1 x EA**

- Coil Voltage: 24 V dc
- Contact Configuration: 4PDT
- Mounting Type: Plug In
- Switching Current: 6 A
- Number of Poles: 4
- Latching: No
- Terminal Type: Plug In
- Coil Power: 180 W



1217798 24 V dc

RS PRO PLUG IN POWER RELAY, 12V DC COIL, 6A SWITCHING CURRENT,

Pack size: **1 x EA**

- Coil Voltage: 12 V dc
- Contact Configuration: 4PDT
- Mounting Type: Plug In
- Switching Current: 6 A
- Number of Poles: 4
- Latching: No
- Terminal Type: Plug In
- Coil Power: 180 W



1217797 12 V dc

RS PRO PLUG IN POWER RELAY, 24V AC COIL, 6A SWITCHING CURRENT,

Pack size: **1 x EA**

- Coil Voltage: 24 V ac
- Contact Configuration: 4PDT
- Mounting Type: Plug In
- Switching Current: 6 A
- Number of Poles: 4
- Latching: No
- Terminal Type: Plug In
- Coil Power: 180 W



1217799 24 V ac

RS PRO PLUG IN POWER RELAY, 12V DC COIL, 16A SWITCHING CURRENT,

Pack size: **1 x EA**

- Coil Voltage: 12 V dc
- Contact Configuration: SPDO
- Mounting Type: Plug In
- Switching Current: 16 A
- Number of Poles: 1
- Latching: No
- Terminal Type: Plug In
- Coil Power: 480 W



1217804 12 V dc

RS PRO PLUG IN POWER RELAY, 24V DC COIL, 16A SWITCHING CURRENT,

Pack size: **1 x EA**

- Coil Voltage: 24 V dc
- Contact Configuration: SPDT
- Mounting Type: Plug In
- Switching Current: 16 A
- Number of Poles: 1
- Latching: No
- Terminal Type: Plug In
- Coil Power: 480 W



1217806 24 V dc

RS PRO PLUG IN POWER RELAY, 24V DC COIL, 10A SWITCHING CURRENT,

Pack size: **1 x EA**

- Coil Voltage: 24 V dc
- Contact Configuration: DPDT
- Mounting Type: Plug In
- Switching Current: 10 A
- Number of Poles: 2
- Latching: No
- Terminal Type: Plug In
- Coil Power: 300 W



1217811 24 V dc

RS PRO PLUG IN POWER RELAY, 12V DC COIL, 10A SWITCHING CURRENT,

Pack size: **1 x EA**

- Coil Voltage: 12 V dc
- Contact Configuration: DPDT
- Mounting Type: Plug In
- Switching Current: 10 A
- Number of Poles: 2
- Latching: No
- Terminal Type: Plug In
- Coil Power: 300 W



1217810 12 V dc

RS PRO PLUG IN POWER RELAY, 24V AC COIL, 10A SWITCHING CURRENT,

Pack size: **1 x EA**

- Coil Voltage: 24 V ac
- Contact Configuration: DPDT
- Mounting Type: Plug In
- Switching Current: 10 A
- Number of Poles: 2
- Latching: No
- Terminal Type: Plug In
- Coil Power: 300 W



1217812 24 V ac

RS PRO PLUG IN POWER RELAY, 24V AC COIL, 16A SWITCHING CURRENT,

Pack size: **1 x EA**

- Coil Voltage: 24 V ac
- Contact Configuration: SPDT
- Mounting Type: Plug In
- Switching Current: 16 A
- Number of Poles: 1
- Latching: No
- Terminal Type: Plug In
- Coil Power: 480 W



1217807 24 V ac

RS PRO PLUG IN POWER RELAY, 12V DC COIL, 10A SWITCHING CURRENT,

Pack size: **1 x EA**

- Coil Voltage: 12 V dc
- Contact Configuration: 3PDT
- Mounting Type: Plug In
- Switching Current: 10 A
- Number of Poles: 3
- Latching: No
- Terminal Type: Plug In
- Coil Power: 300 W



1217815 12 V dc

RS PRO PLUG IN POWER RELAY, 12V DC COIL, 10A SWITCHING CURRENT,

Pack size: **1 x EA**

- Coil Voltage: 12 V dc
- Contact Configuration: 3PDT
- Mounting Type: Plug In
- Switching Current: 10 A
- Number of Poles: 4
- Latching: No
- Terminal Type: Plug In
- Coil Power: 300 W



1217820 12 V dc

RS PRO PLUG IN POWER RELAY, 24V DC COIL, 10A SWITCHING CURRENT,

Pack size: **1 x EA**

- Coil Voltage: 24 V dc
- Contact Configuration: 3PDT
- Mounting Type: Plug In
- Switching Current: 10 A
- Number of Poles: 3
- Latching: No
- Terminal Type: Plug In
- Coil Power: 300 W



1217816 24 V dc

RS PRO PLUG IN POWER RELAY, 24V DC COIL, 10A SWITCHING CURRENT,

Pack size: **1 x EA**

- Coil Voltage: 24 V dc
- Contact Configuration: 4PDT
- Mounting Type: Plug In
- Switching Current: 10 A
- Number of Poles: 4
- Latching: No
- Terminal Type: Plug In
- Coil Power: 300 W



1217821 24 V dc

RS PRO PLUG IN POWER RELAY, 12V DC COIL, 10A SWITCHING CURRENT,

Pack size: **1 x EA**

- Coil Voltage: 12 V dc
- Contact Configuration: DPDT
- Mounting Type: Plug In
- Switching Current: 10 A
- Number of Poles: 2
- Latching: No
- Terminal Type: Plug In
- Coil Power: 300 W



1217828 12 V dc

RS PRO PLUG IN POWER RELAY, 24V DC COIL, 10A SWITCHING CURRENT,

Pack size: **1 x EA**

- Coil Voltage: 24 V dc
- Contact Configuration: 3PDT
- Mounting Type: Plug In
- Switching Current: 10 A
- Number of Poles: 3
- Latching: No
- Terminal Type: Plug In
- Coil Power: 300 W



1217835 24 V dc

RS PRO PLUG IN POWER RELAY, 24V AC COIL, 10A SWITCHING CURRENT,

Pack size: **1 x EA**

- Coil Voltage: 24 V ac
- Contact Configuration: 3PDT
- Mounting Type: Plug In
- Switching Current: 10 A
- Number of Poles: 3
- Latching: No
- Terminal Type: Plug In
- Coil Power: 300 W



1217836 24 V ac

RS PRO PLUG IN POWER RELAY, 24V DC COIL, 10A SWITCHING CURRENT,

Pack size: **1 x EA**

- Coil Voltage: 24 V dc
- Contact Configuration: DPDT
- Mounting Type: Plug In
- Switching Current: 10 A
- Number of Poles: 2
- Latching: No
- Terminal Type: Plug In
- Coil Power: 300 W



1217829 24 V dc

RELAY, INDUSTRIAL, PLUG IN, 4RT, 5A, 20VAC, 12VDC

Pack size: **1 x EA**

- Coil Voltage: 12 V dc
- Contact Configuration: 4PDT
- Mounting Type: Plug In
- Switching Current: 5 A
- Number of Poles: 4
- Latching: No
- Terminal Type: Through Hole
- Coil Resistance: 160 Ω



3949065 12 V dc

RS PRO PLUG IN POWER RELAY, 24V DC COIL, 5A SWITCHING CURRENT,

Pack size: **1 x EA**

- Coil Voltage: 24 V dc
- Contact Configuration: 4PDT
- Mounting Type: Plug In
- Switching Current: 5 A
- Number of Poles: 4
- Latching: No
- Terminal Type: Through Hole
- Coil Resistance: 636 Ω



3949087 24 V dc

4PDT INDUSTRIAL RELAY, 3A 24VAC COIL

Pack size: **1 x EA**

- Coil Voltage: 24 V ac
- Contact Configuration: 4PDT
- Mounting Type: Plug In
- Switching Current: 5 A
- Number of Poles: 4
- Terminal Type: Through Hole
- Coil Resistance: 180 Ω
- Coil Power: 1.2 W



3949093 24 V ac

RS PRO PLUG IN POWER RELAY, 120V AC COIL, 5A SWITCHING CURRENT,

Pack size: **1 x EA**

- Coil Voltage: 120 V ac
- Contact Configuration: 4PDT
- Mounting Type: Plug In
- Switching Current: 5 A
- Number of Poles: 4
- Latching: No
- Terminal Type: Through Hole
- Coil Resistance: 4.43 k Ω



3949100 120 V ac

RS PRO PCB MOUNT POWER RELAY, 240V AC COIL, 12A SWITCHING

Pack size: **1 x EA**

- Coil Voltage: 240 V ac
- Contact Configuration: DPDT
- Mounting Type: PCB Mount
- Switching Current: 12 A
- Number of Poles: 2
- Latching: No
- Terminal Type: Through Hole
- Coil Resistance: 9.11 k Ω



4500201 240 V ac

RS PRO PLUG IN POWER RELAY, 240V AC COIL, 5A SWITCHING CURRENT,

Pack size: **1 x EA**

- Coil Voltage: 240 V ac
- Contact Configuration: 4PDT
- Mounting Type: Plug In
- Switching Current: 5 A
- Number of Poles: 4
- Latching: No
- Terminal Type: Through Hole
- Coil Resistance: 18.79 k Ω



3949116 240 V ac

RS PRO PCB MOUNT POWER RELAY, 110V AC COIL, 15A SWITCHING

Pack size: **1 x EA**

- Coil Voltage: 110 V ac
- Contact Configuration: SPDT
- Mounting Type: PCB Mount
- Switching Current: 15 A
- Number of Poles: 1
- Latching: No
- Terminal Type: PCB Pin
- Coil Resistance: 3.83 k Ω



4500217 110 V ac

RS PRO PCB MOUNT POWER RELAY, 12V DC COIL, 15A SWITCHING

Pack size: **1 x EA**

- Coil Voltage: 12 V dc
- Contact Configuration: SPDT
- Mounting Type: PCB Mount
- Switching Current: 15 A
- Number of Poles: 1
- Latching: No
- Terminal Type: PCB Pin
- Coil Resistance: 188 Ω



4500223 12 V dc

RS PRO PCB MOUNT POWER RELAY, 24V AC COIL, 15A SWITCHING

Pack size: **1 x EA**

- Coil Voltage: 24 V ac
- Contact Configuration: SPDT
- Mounting Type: PCB Mount
- Switching Current: 15 A
- Number of Poles: 1
- Latching: No
- Terminal Type: PCB Pin
- Coil Resistance: 180 Ω



4500245 24 V ac

RS PRO PCB MOUNT POWER RELAY, 24V DC COIL, 15A SWITCHING

Pack size: **1 x EA**

- Coil Voltage: 24 V dc
- Contact Configuration: SPDT
- Mounting Type: PCB Mount
- Switching Current: 15 A
- Number of Poles: 1
- Latching: No
- Terminal Type: PCB Pin
- Coil Resistance: 750 Ω



4500251 24 V dc

RS PRO PCB MOUNT POWER RELAY, 110V AC COIL, 15A SWITCHING

Pack size: **1 x EA**

- Coil Voltage: 110 V ac
- Contact Configuration: SPDT
- Mounting Type: PCB Mount
- Switching Current: 15 A
- Number of Poles: 1
- Latching: No
- Terminal Type: PCB Pin
- Coil Resistance: 3.83 k Ω



4500267 110 V ac

RS PRO PCB MOUNT POWER RELAY, 12V DC COIL, 15A SWITCHING

Pack size: **1 x EA**

- Coil Voltage: 12 V dc
- Contact Configuration: SPDT
- Mounting Type: PCB Mount
- Switching Current: 15 A
- Number of Poles: 1
- Latching: No
- Terminal Type: PCB Pin
- Coil Resistance: 188 Ω



4500273 12 V dc

RELAY, MINIATURE, PLUG IN, INDICATOR, 24VDC COIL, 750

Pack size: **1 x EA**

- Coil Voltage: 24 V dc
- Contact Configuration: SPDT
- Mounting Type: PCB Mount
- Switching Current: 15 A
- Number of Poles: 1
- Latching: No
- Terminal Type: PCB Pin
- Coil Resistance: 750 Ω



4500295 24 V dc

RS PRO PLUG IN POWER RELAY, 110V AC COIL, 10A SWITCHING CURRENT,

Pack size: **1 x EA**

- Coil Voltage: 110 V ac
- Contact Configuration: DPDT
- Mounting Type: Plug In
- Switching Current: 10 A
- Number of Poles: 2
- Latching: No
- Terminal Type: PCB Pin
- Coil Resistance: 3.83 k Ω



4500302 110 V ac

RS PRO PLUG IN POWER RELAY, 12V DC COIL, 10A SWITCHING CURRENT,

Pack size: **1 x EA**

- Coil Voltage: 12 V dc
- Contact Configuration: DPDT
- Mounting Type: Plug In
- Switching Current: 10 A
- Number of Poles: 2
- Latching: No
- Terminal Type: PCB Pin
- Coil Resistance: 160 Ω



4500318 12 V dc

RELAY, MINIATURE, POWER, 230VAC COIL, 10A, DPCCO

Pack size: **1 x EA**

- Coil Voltage: 230 V ac
- Contact Configuration: DPDT
- Mounting Type: Plug In
- Switching Current: 10 A
- Number of Poles: 2
- Latching: No
- Terminal Type: PCB Pin
- Coil Resistance: 12.5 k Ω



4500324 230 V ac

RELAY, MINIATURE, POWER, 240VAC COIL, 10A, DPCCO

Pack size: **1 x EA**

- Coil Voltage: 240 V ac
- Contact Configuration: DPDT
- Mounting Type: Plug In
- Switching Current: 10 A
- Number of Poles: 2
- Latching: No
- Terminal Type: PCB Pin
- Coil Resistance: 15.7 k Ω



4500330 240 V ac

RS PRO PLUG IN POWER RELAY, 24V AC COIL, 10A SWITCHING CURRENT,

Pack size: **1 x EA**

- Coil Voltage: 24 V ac
- Contact Configuration: DPDT
- Mounting Type: Plug In
- Switching Current: 10 A
- Number of Poles: 2
- Latching: No
- Terminal Type: PCB Pin
- Coil Resistance: 180 Ω



4500346 24 V ac

RS PRO PLUG IN POWER RELAY, 24V DC COIL, 10A SWITCHING CURRENT,

Pack size: **1 x EA**

- Coil Voltage: 24 V dc
- Contact Configuration: DPDT
- Mounting Type: Plug In
- Switching Current: 10 A
- Number of Poles: 2
- Latching: No
- Terminal Type: PCB Pin
- Coil Resistance: 650 Ω



4500352 24 V dc

RS PRO PLUG IN POWER RELAY, 12V DC COIL, 10A SWITCHING CURRENT,

Pack size: **1 x EA**

- Coil Voltage: 12 V dc
- Contact Configuration: DPDT
- Mounting Type: Plug In
- Switching Current: 10 A
- Number of Poles: 2
- Latching: No
- Terminal Type: PCB Pin
- Coil Resistance: 160 Ω



4500374 12 V dc

RS PRO PLUG IN POWER RELAY, 230V AC COIL, 10A SWITCHING CURRENT,

Pack size: **1 x EA**

- Coil Voltage: 230 V ac
- Contact Configuration: DPDT
- Mounting Type: Plug In
- Switching Current: 10 A
- Number of Poles: 2
- Latching: No
- Terminal Type: PCB Pin
- Coil Resistance: 12.5 k Ω



4500380 230 V ac

RELAY, MINIATURE, PLUG IN, INDICATOR, 240VAC

Pack size: **1 x EA**

- Coil Voltage: 240 V ac
- Contact Configuration: DPDT
- Mounting Type: Plug In
- Switching Current: 10 A
- Number of Poles: 2
- Latching: No
- Terminal Type: PCB Pin
- Coil Resistance: 15.7 k Ω



4500403 240 V ac

RS PRO PLUG IN POWER RELAY, 24V AC COIL, 10A SWITCHING CURRENT,

Pack size: **1 x EA**

- Coil Voltage: 24 V ac
- Contact Configuration: DPDT
- Mounting Type: Plug In
- Switching Current: 10 A
- Number of Poles: 2
- Latching: No
- Terminal Type: PCB Pin
- Coil Resistance: 180 Ω



4500419 24 V ac

RELAY, MINIATURE, PLUG IN, INDICATOR, 24VDC COIL, 650

Pack size: **1 x EA**

- Coil Voltage: 24 V dc
- Contact Configuration: DPDT
- Mounting Type: Plug In
- Switching Current: 10 A
- Number of Poles: 2
- Latching: No
- Terminal Type: PCB Pin
- Coil Resistance: 650 Ω



4500425 24 V dc

RS PRO PLUG IN POWER RELAY, 240V AC COIL, 12A SWITCHING CURRENT,

Pack size: **1 x EA**

- Coil Voltage: 240 V ac
- Contact Configuration: 3PDT
- Mounting Type: Plug In
- Switching Current: 12 A
- Number of Poles: 3
- Latching: No
- Terminal Type: PCB Pin
- Coil Resistance: 12.1 k Ω



6133594 240 V ac

RS PRO PLUG IN POWER RELAY, 110V AC COIL, 12A SWITCHING CURRENT,

Pack size: **1 x EA**

- Coil Voltage: 110 V ac
- Contact Configuration: 4PDT
- Mounting Type: Plug In
- Switching Current: 12 A
- Number of Poles: 4
- Latching: No
- Terminal Type: PCB Pin
- Coil Resistance: 1.8 k Ω



6133768 110 V ac

RS PRO PLUG IN POWER RELAY, 12V DC COIL, 12A SWITCHING CURRENT,

Pack size: **1 x EA**

- Coil Voltage: 12 V dc
- Contact Configuration: 4PDT
- Mounting Type: Plug In
- Switching Current: 12 A
- Number of Poles: 4
- Latching: No
- Terminal Type: PCB Pin
- Coil Resistance: 96 Ω



6133780 12 V dc

RS PRO PLUG IN POWER RELAY, 240V AC COIL, 12A SWITCHING CURRENT,

Pack size: **1 x EA**

- Coil Voltage: 240 V ac
- Contact Configuration: 4PDT
- Mounting Type: Plug In
- Switching Current: 12 A
- Number of Poles: 4
- Latching: No
- Terminal Type: PCB Pin
- Coil Resistance: 9.12 k Ω



6133796 240 V ac

DIN RAIL SKT RISING/SCREW 14 PINCLIP&TAG

Pack size: **1 x EA**

- Voltage: 300 V
- For Use With: RS PRO RKE & RKF 14 Pin Relays
- Termination Type: Screw
- Number of Contacts: 14
- Current Rating: 10 A
- Mounting Type: DIN Rail



1217802 300 V

RS PRO PLUG IN POWER RELAY, 24V AC COIL, 12A SWITCHING CURRENT,

Pack size: **1 x EA**

- Coil Voltage: 24 V ac
- Contact Configuration: 4PDT
- Mounting Type: Plug In
- Switching Current: 12 A
- Number of Poles: 4
- Latching: No
- Terminal Type: PCB Pin
- Coil Resistance: 84.5 Ω



6133803 24 V ac

RS PRO PLUG IN POWER RELAY, 24V DC COIL, 12A SWITCHING CURRENT,

Pack size: **1 x EA**

- Coil Voltage: 24 V dc
- Contact Configuration: 4PDT
- Mounting Type: Plug In
- Switching Current: 12 A
- Number of Poles: 4
- Latching: No
- Terminal Type: PCB Pin
- Coil Resistance: 388 Ω



6133819 24 V dc

RS PRO RELAY SOCKET FOR USE WITH RS PRO RKL RELAYS 3PDT 11

Pack size: **1 x EA**

- Voltage: 300 V
- For Use With: RS PRO RKL Relays 3PDT
- Termination Type: Screw
- Number of Contacts: 11
- Current Rating: 16 A
- Mounting Type: DIN Rail



1217826 300 V

RS PRO RELAY SOCKET FOR USE WITH RS PRO RKE & RKF 14 PIN

Pack size: **1 x EA**

- Voltage: 300 V
- For Use With: RS PRO RKE & RKF 14 Pin Relays
- Termination Type: Screw
- Number of Contacts: 14
- Current Rating: 10 A
- Mounting Type: DIN Rail



1217803 300 V

DIN RAIL SKT RISING/SCREW CLIP&TAG

Pack size: **1 x EA**

- Voltage: 300 V
- For Use With: RS PRO RKL Relays DPDT
- Termination Type: Screw
- Number of Contacts: 8
- Current Rating: 16 A
- Mounting Type: DIN Rail



1217825 300 V

DIN RAIL SKT RISING/SCREWCLIP&TAG

Pack size: **1 x EA**

- Voltage: 300 V
- For Use With: RS PRO RKL Relays 4PDT
- Termination Type: Screw
- Number of Contacts: 14
- Current Rating: 16 A
- Mounting Type: DIN Rail



1217827 300 V

RS PRO MARKER FOR USE WITH SOLID STATE RELAYS, 120 PIECES

Pack size: **120 x EA**

- Accessory Type: Marker
- For Use With: Solid State Relays
- Pack Quantity: 120



8886950 Marker

RS PRO RELAY SOCKET FOR USE WITH RS PRO RUB RELAYS 8 PIN, DIN

Pack size: **1 x EA**

- Voltage: 300 V
- For Use With: RS PRO RUB Relays
- Termination Type: Screw
- Number of Contacts: 8
- Current Rating: 12 A
- Mounting Type: DIN Rail



1217839 300 V

RS PRO RELAY SOCKET FOR USE WITH RS PRO RUB RELAYS 11 PIN, DIN

Pack size: **1 x EA**

- Voltage: 300 V
- For Use With: RS PRO RUB Relays
- Termination Type: Screw
- Number of Contacts: 11
- Current Rating: 12 A
- Mounting Type: DIN Rail



1217840 300 V

RS PRO RELAY SOCKET FOR USE WITH RS PRO RUB RELAYS 8 PIN, DIN

Pack size: **1 x EA**

- Voltage: 300 V
- For Use With: RS PRO RUB Relays
- Termination Type: Screw
- Number of Contacts: 8
- Current Rating: 15 A
- Mounting Type: DIN Rail



1217841 300 V

DIN RAIL SKT 11-PIN RISING

Pack size: **1 x EA**

- Voltage: 300 V
- For Use With: RS PRO RUB Relays
- Termination Type: Screw
- Number of Contacts: 11
- Current Rating: 15 A
- Mounting Type: DIN Rail



1217842 300 V

RS PRO RELAY SOCKET FOR USE WITH RFT RELAY, DIN RAIL, 300V AC

Pack size: **1 x EA**

- Voltage: 300 V ac
- For Use With: RFT Relay
- Mounting Type: DIN Rail
- Current Rating: 16 A



1441611 300 V ac

SOCKET RFT2 RISE PLT CLAMP PLASTIC CLIP

Pack size: **1 x EA**

- Voltage: 300 V
- For Use With: RFT Interface Relay
- Termination Type: Screw
- Number of Contacts: 8
- Current Rating: 10 A
- Mounting Type: DIN Rail



1441609 300 V

SOCKET RFT1 RISE PLT CLAMP PLASTIC CLIP

Pack size: **1 x EA**

- Voltage: 300 V
- For Use With: RFT Interface Relay
- Termination Type: Screw
- Number of Contacts: 5
- Current Rating: 16 A
- Mounting Type: DIN Rail



1441610 300 V

RS PRO RELAY SOCKET FOR USE WITH RFT RELAY, DIN RAIL, 300V AC

Pack size: **1 x EA**

- Voltage: 300 V ac
- For Use With: RFT Relay
- Mounting Type: DIN Rail
- Current Rating: 10 A



1441612 300 V ac

RS PRO SIGNAL CONDITIONER, 8 → 30V DC, FREQUENCY INPUT,

Pack size: **1 x EA**

- Module Type: Frequency Converter
- Input Signal Type: Frequency
- Output Signal Type: Current
- Supply Voltage: 8 → 30 V dc
- Input Range: 0 → 1 kHz
- Output Range: 4 → 20 mA
- Mounting Type: DIN Rail Mount
- Operating Temperature Range: 0 → +45 °C



223363 Frequency

RS PRO SIGNAL CONDITIONER, 8 → 30V DC, FREQUENCY INPUT,

Pack size: **1 x EA**

- Module Type: Frequency Converter
- Input Signal Type: Frequency
- Output Signal Type: Current
- Supply Voltage: 8 → 30 V dc
- Input Range: 0 → 100 Hz
- Output Range: 4 → 20 mA
- Mounting Type: DIN Rail Mount
- Operating Temperature Range: 0 → +45 °C



223385 Frequency

RS PRO SIGNAL CONDITIONER, 24 → 230V AC, VOLTAGE INPUT, CURRENT

Pack size: **1 x EA**

- Module Type: Signal Isolator
- Input Signal Type: Voltage
- Output Signal Type: Current
- Supply Voltage: 24 → 230 V ac
- Input Range: 0 → 10 V dc
- Output Range: 4 → 20 mA
- Mounting Type: DIN Rail Mount
- Operating Temperature Range: -20 → +60 °C



629522 Signal Isolator

RS PRO SIGNAL CONDITIONER, 24 → 240V AC/DC, CURRENT, VOLTAGE

Pack size: **1 x EA**

- Module Type: Analogue Signal Converter
- Input Signal Type: Current, Voltage
- Output Signal Type: Current, Voltage
- Supply Voltage: 24 → 240 V ac/dc
- Input Range: 0 → 10 V, 0 → 20 mA, 4 → 20 mA
- Output Range: 0 → 10 V, 0 → 20 mA, 4 → 20 mA
- Mounting Type: DIN Rail Mount
- Operating Temperature Range: -25 → +60 °C



1923389 Analogue Signal

RS PRO SIGNAL CONDITIONER, 24 → 240V AC/DC, CURRENT, VOLTAGE

Pack size: **1 x EA**

- Module Type: Analogue Signal Converter
- Input Signal Type: Current, Voltage
- Output Signal Type: Current, Voltage
- Supply Voltage: 24 → 240 V ac/dc
- Input Range: 0 → 1 V, 0 → 2 V, 0 → 5 mA, 0 → 5 V, 0 → 10 mA, 0 → 10 V, 0 → 20 mA, 0 → 20 V, 0 → 60 mV, 0 → 100 mV, 0 → 300 mV, 0 → 500 mV, 2 → 10 V, 4 → 20 mA, ±5 mA, ±20 mA
- Output Range: 0 → 10 V, 0 → 20 mA, 4 → 20 mA
- Mounting Type: DIN Rail Mount
- Operating Temperature Range: -25 → +60 °C



1923390 Analogue Signal

RS PRO SIGNAL CONDITIONER, CURRENT INPUT, CURRENT OUTPUT

Pack size: **1 x EA**

- Module Type: Analogue Signal Converter
- Input Signal Type: Current
- Output Signal Type: Current
- Input Range: 4 → 20 mA
- Output Range: 4 → 20 mA
- Mounting Type: DIN Rail Mount
- Operating Temperature Range: -25 → +60 °C
- Minimum Operating Temperature: -25 °C



1923391 Analogue Signal

RS PRO SIGNAL CONDITIONER, 24V AC/DC, VOLTAGE INPUT, VOLTAGE

Pack size: **1 x EA**

- Module Type: Analogue Signal Converter
- Input Signal Type: Voltage
- Output Signal Type: Voltage
- Supply Voltage: 24 V ac/dc
- Input Range: 0 → 10 V dc
- Output Range: 0 → 10 V dc
- Mounting Type: DIN Rail Mount
- Operating Temperature Range: -25 → +60 °C



1923392 Analogue Signal

RS PRO SIGNAL CONDITIONER, 24V AC/DC, VOLTAGE INPUT, CURRENT

Pack size: **1 x EA**

- Module Type: Analogue Signal Converter
- Input Signal Type: Voltage
- Output Signal Type: Current
- Supply Voltage: 24 V ac/dc
- Input Range: 0 → 10 V dc
- Output Range: 4 → 20 mA
- Mounting Type: DIN Rail Mount
- Operating Temperature Range: -25 → +60 °C



1923393 Analogue Signal

RS PRO SIGNAL CONDITIONER, 24V AC/DC, CURRENT INPUT, CURRENT,

Pack size: **1 x EA**

- Module Type: Analogue Signal Converter
- Input Signal Type: Current
- Output Signal Type: Current, Voltage
- Supply Voltage: 24 V ac/dc
- Input Range: 4 → 20 mA
- Output Range: 0 → 10 V dc
- Mounting Type: DIN Rail Mount
- Operating Temperature Range: -25 → +60 °C



1923394 Analogue Signal

RS PRO SIGNAL CONDITIONER, 24V AC/DC, CURRENT INPUT, CURRENT,

Pack size: **1 x EA**

- Module Type: Analogue Signal Converter
- Input Signal Type: Current
- Output Signal Type: Current, Voltage
- Supply Voltage: 24 V ac/dc
- Input Range: 4 → 20 mA
- Output Range: 4 → 20 mA
- Mounting Type: DIN Rail Mount
- Operating Temperature Range: -25 → +60 °C



1923395 Analogue Signal

RS PRO SIGNAL CONDITIONER, 24V AC/DC, CURRENT, VOLTAGE INPUT,

Pack size: **1 x EA**

- Module Type: Analogue Signal Converter
- Input Signal Type: Current, Voltage
- Output Signal Type: Current, Voltage
- Supply Voltage: 24 V ac/dc
- Input Range: 0 → 10 V, 0 → 20 mA, 4 → 20 mA
- Output Range: 0 → 10 V, 0 → 20 mA, 4 → 20 mA
- Mounting Type: DIN Rail Mount
- Operating Temperature Range: -25 → +60 °C



1923396 Analogue Signal

RS PRO SIGNAL CONDITIONER, 24 → 240V AC/DC, CURRENT, VOLTAGE

Pack size: **1 x EA**

- Module Type: Analogue Signal Converter
- Input Signal Type: Current, Voltage
- Output Signal Type: Current, Voltage
- Supply Voltage: 24 → 240 V ac/dc
- Input Range: 0 → 10 V, 0 → 20 mA, 4 → 20 mA
- Output Range: 0 → 10 V, 0 → 20 mA, 4 → 20 mA
- Mounting Type: DIN Rail Mount
- Operating Temperature Range: -25 → +60 °C



1923397 Analogue Signal

RS PRO SIGNAL CONDITIONER, 24V AC/DC, VOLTAGE INPUT, CURRENT,

Pack size: **1 x EA**

- Module Type: Analogue Signal Converter
- Input Signal Type: Voltage
- Output Signal Type: Current, Voltage
- Supply Voltage: 24 V ac/dc
- Input Range: 0 → 10 V dc
- Output Range: 0 → 10 V, 0 → 20 mA, 4 → 20 mA
- Mounting Type: DIN Rail Mount
- Operating Temperature Range: -25 → +60 °C



1923398 Analogue Signal

RS PRO SIGNAL CONDITIONER, 24V AC/DC, CURRENT INPUT, CURRENT,

Pack size: **1 x EA**

- Module Type: Analogue Signal Converter
- Input Signal Type: Current
- Output Signal Type: Current, Voltage
- Supply Voltage: 24 V ac/dc
- Input Range: 4 → 20 mA
- Output Range: 0 → 10 V, 0 → 20 mA, 4 → 20 mA
- Mounting Type: DIN Rail Mount
- Operating Temperature Range: -25 → +60 °C



1923399 Analogue Signal

RS PRO SIGNAL CONDITIONER, 10 → 30V DC, CURRENT INPUT, RELAY

Pack size: **1 x EA**

- Module Type: Trip Amplifier
- Input Signal Type: Current
- Output Signal Type: Relay
- Supply Voltage: 20 → 30 V dc
- Input Range: 4 → 20 mA
- Mounting Type: DIN Rail Mount
- Operating Temperature Range: 0 → +50 °C
- Minimum Operating Temperature: 0 °C



2184453 Trip Amplifier

RS PRO SIGNAL CONDITIONER, 10 → 32 V AC, 10 → 48V DC, RTD,

Pack size: **1 x EA**

- Module Type: Temperature Converter
- Input Signal Type: RTD, Thermocouple
- Output Signal Type: Current, Voltage
- Supply Voltage: 10 → 32 V ac, 10 → 48 V dc
- Input Range: 0 → 100 K Ω , -100 → 200 mV, -200 → +2000 °C
- Output Range: 0 → 10 V, 0 → 21.5 mA
- Mounting Type: DIN Rail Mount
- Operating Temperature Range: -30 → +70 °C



7886999 Temperature

RS PRO SIGNAL CONDITIONER, 24V DC, CURRENT INPUT, VOLTAGE

Pack size: **1 x EA**

- Module Type: Signal Isolator
- Input Signal Type: Current
- Output Signal Type: Voltage
- Supply Voltage: 24 V dc
- Input Range: 4 → 20 mA
- Output Range: 0 → 10 V dc
- Mounting Type: DIN Rail Mount
- Operating Temperature Range: 0 → +45 °C



4662258 Signal Isolator

RS PRO SIGNAL CONDITIONER, 9 → 30V DC, CURRENT INPUT, CURRENT

Pack size: **1 x EA**

- Module Type: Signal Isolator
- Input Signal Type: Current
- Output Signal Type: Current
- Supply Voltage: 9 → 30 V dc
- Input Range: 4 → 20 mA
- Output Range: 2 x 4 → 20 mA
- Mounting Type: DIN Rail Mount
- Operating Temperature Range: 0 → +45 °C



4662264 Signal Isolator

RS PRO SIGNAL CONDITIONER, 20 → 240 V AC, 20 → 240V DC, UNIVERSAL

Pack size: **1 x EA**

- Module Type: Universal Signal Converter
- Input Signal Type: Universal
- Output Signal Type: Current, Voltage, Relay
- Supply Voltage: 20 → 240 V ac, 20 → 240 V dc
- Input Range: 1 → 100 K Ω , -10 → 10 V dc, -200 → +2000 °C, -25 → 25 mA
- Output Range: 0 → 12 V, 0 → 20 mA
- Mounting Type: DIN Rail Mount
- Operating Temperature Range: -20 → +70 °C



7886987 Universal Signal

RS PRO SIGNAL CONDITIONER, 10 → 32 V AC, 10 → 48V DC, CURRENT,

Pack size: **1 x EA**

- Module Type: Signal Isolator
- Input Signal Type: Current, Voltage
- Output Signal Type: Current, Voltage
- Supply Voltage: 10 → 32 V ac, 10 → 48 V dc
- Input Range: -50 → +50 mA, -50 → +50 V
- Output Range: 0 → 21.5 mA, -10 → +10 V
- Mounting Type: DIN Rail Mount
- Operating Temperature Range: -30 → +70 °C



7886996 Signal Isolator

RS PRO SIGNAL CONDITIONER, 16.8 → 30 V DC, 19.2 → 28.8V AC,

Pack size: **1 x EA**

- Module Type: Frequency Converter
- Input Signal Type: Frequency
- Output Signal Type: Current, Voltage
- Supply Voltage: 16.8 → 30 V dc, 19.2 → 28.8 V ac
- Input Range: 0 → 1 kHz, 0 → 10 kHz, 0 → 100 Hz, 0 → 12 kHz, 0 → 16 kHz, 0 → 2 kHz, 0 → 2.5 kHz, 0 → 20 kHz, 0 → 200 Hz, 0 → 24 kHz, 0 → 250 Hz, 0 → 28.8 kHz, 0 → 3 kHz, 0 → 4 kHz, 0 → 400 Hz, 0 → 5 kHz, 0 → 500 Hz, 0 → 6 kHz, 0 → 750 Hz, 0 → 8 kHz
- Output Range: 0 → 10 V, 0 → 20 mA, 4 → 20 mA
- Mounting Type: DIN Rail Mount
- Operating Temperature Range: -25 → +60 °C



7948524 Frequency

RS PRO SIGNAL CONDITIONER, 16.8 → 30V, RTD, THERMOCOUPLE INPUT,

Pack size: **1 x EA**

- Module Type: Temperature Converter
- Input Signal Type: RTD, Thermocouple
- Output Signal Type: Current, Voltage
- Supply Voltage: 16.8 → 30 V
- Input Range: -210 → +2310 °C, -220 → +850 °C
- Output Range: 0 → 10 V, 0 → 20 mA, -10 → +10 V, 4 → 20 mA
- Mounting Type: DIN Rail Mount
- Operating Temperature Range: -40 → +70 °C



7948533 Temperature

RS PRO SIGNAL CONDITIONER, 16.8 → 30V, CURRENT, VOLTAGE INPUT,

Pack size: **1 x EA**

- Module Type: Analogue Splitter
- Input Signal Type: Current, Voltage
- Output Signal Type: Current, Voltage
- Supply Voltage: 16.8 → 30 V
- Input Range: 0 → 10 V, 0 → 20 mA, 4 → 20 mA
- Output Range: 0 → 10 V, 0 → 20 mA, 4 → 20 mA
- Mounting Type: DIN Rail Mount
- Operating Temperature Range: -40 → +70 °C



7948574 Analogue Splitter

RS PRO SIGNAL CONDITIONER, 16.8 → 30V, CURRENT INPUT, CURRENT,

Pack size: **1 x EA**

- Module Type: Analogue Signal Converter
- Input Signal Type: Current
- Output Signal Type: Current, Voltage
- Supply Voltage: 16.8 → 30 V
- Input Range: ± 1 A, 0 → 1 A
- Output Range: 0 → 10 V, 0 → 20 mA, 4 → 20 mA
- Mounting Type: DIN Rail Mount
- Operating Temperature Range: -25 → +60 °C



7948549 Analogue Signal

RS PRO SIGNAL CONDITIONER, 16.8 → 30V, CURRENT, VOLTAGE INPUT,

Pack size: **1 x EA**

- Module Type: Analogue Signal Converter
- Input Signal Type: Current, Voltage
- Output Signal Type: Current, Voltage
- Supply Voltage: 16.8 → 30 V
- Input Range: ± 30 V, ± 5 A, ± 50 mA
- Output Range: 0 → 10 V, 0 → 20 mA, -10 → +10 V, 4 → 20 mA
- Mounting Type: DIN Rail Mount
- Operating Temperature Range: -40 → +70 °C



7948570 Analogue Signal

RS PRO DIN RAIL SOLID STATE INTERFACE RELAY, 6 A MAX LOAD, 60

Pack size: **1 x EA**

- Maximum Load Current: 6 A
- Mounting Type: DIN Rail
- Maximum Load Voltage: 60 V dc
- Maximum Control Voltage: 32 V dc
- Minimum Control Voltage: 4 V dc
- Capacitance: 10 pF
- Contact Configuration: SP
- Control Voltage Range: 4 → 32 V dc



1213885 6 A

RS PRO DIN RAIL SOLID STATE RELAY, 20 A MAX. LOAD, 530 VRMS MAX.

Pack size: **1 x EA**

- Maximum Load Current: 20 A
- Mounting Type: DIN Rail
- Minimum Load Voltage: 48 Vrms
- Maximum Load Voltage: 530 Vrms
- Minimum Control Voltage: 90 V ac
- Maximum Control Voltage: 280 V ac
- Switching Type: Random
- Contact Configuration: SP



1213889 20 A

RS PRO DIN RAIL SOLID STATE INTERFACE RELAY, 6 A MAX LOAD,

Pack size: **1 x EA**

- Maximum Load Current: 6 A
- Mounting Type: DIN Rail
- Maximum Load Voltage: 280 V ac
- Maximum Control Voltage: 280 V ac
- Minimum Control Voltage: 200 V ac
- Capacitance: 10 pF
- Contact Configuration: SP
- Control Voltage Range: 200 → 265 V rms



1213887 6 A

RS PRO DIN RAIL SOLID STATE INTERFACE RELAY, 6 A MAX LOAD,

Pack size: **1 x EA**

- Maximum Load Current: 6 A
- Mounting Type: DIN Rail
- Maximum Load Voltage: 280 V ac
- Maximum Control Voltage: 32 V dc
- Minimum Control Voltage: 4 V dc
- Capacitance: 10 pF
- Contact Configuration: SP
- Control Voltage Range: 4 → 32 V dc



1213888 6 A

RS PRO DIN RAIL SOLID STATE RELAY, 20 A MAX. LOAD, 530 VRMS MAX.

Pack size: **1 x EA**

- Maximum Load Current: 20 A
- Mounting Type: DIN Rail
- Minimum Load Voltage: 48 Vrms
- Maximum Load Voltage: 530 Vrms
- Minimum Control Voltage: 4 V dc
- Maximum Control Voltage: 32 V dc
- Switching Type: Zero Crossing
- Contact Configuration: SP



1213892 20 A

RS PRO DIN RAIL SOLID STATE RELAY, 30 A MAX. LOAD, 530 VRMS MAX.

Pack size: **1 x EA**

- Maximum Load Current: 30 A
- Mounting Type: DIN Rail
- Minimum Load Voltage: 48 Vrms
- Maximum Load Voltage: 530 Vrms
- Minimum Control Voltage: 4 V dc
- Maximum Control Voltage: 32 V dc
- Switching Type: Zero Crossing
- Contact Configuration: SP



1213896 30 A

RS PRO DIN RAIL SOLID STATE RELAY, 30 A MAX. LOAD, 530 VRMS MAX.

Pack size: **1 x EA**

- Maximum Load Current: 30 A
- Mounting Type: DIN Rail
- Minimum Load Voltage: 48 Vrms
- Maximum Load Voltage: 530 Vrms
- Minimum Control Voltage: 90 V ac
- Maximum Control Voltage: 280 V ac
- Switching Type: Zero Crossing
- Contact Configuration: SP



1213894 30 A

RS PRO DIN RAIL SOLID STATE RELAY, 20 A MAX. LOAD, 530 VRMS MAX.

Pack size: **1 x EA**

- Maximum Load Current: 20 A
- Mounting Type: DIN Rail
- Minimum Load Voltage: 48 Vrms
- Maximum Load Voltage: 530 Vrms
- Minimum Control Voltage: 90 V ac
- Maximum Control Voltage: 280 V ac
- Switching Type: Zero Crossing
- Contact Configuration: SP



1213890 20 A

RS PRO DIN RAIL SOLID STATE RELAY

Pack size: **1 x EA**

- Series: RS PRO
- Mounting Type: DIN Rail
- Dimensions: 60.8 x 67.5 x 6.1 mm
- Operating Temperature Range: -25 → +60 °C
- Minimum Operating Temperature: -25 °C
- Length: 60.8 mm
- Depth: 6.1 mm
- Maximum Operating Temperature: +60 °C



2125492 RS PRO

RS PRO DIN RAIL SOLID STATE RELAY

Pack size: **1 x EA**

- Series: RS PRO
- Mounting Type: DIN Rail
- Dimensions: 60.8 x 67.5 x 6.1 mm
- Operating Temperature Range: -25 → +60 °C
- Minimum Operating Temperature: -25 °C
- Length: 60.8 mm
- Depth: 6.1 mm
- Maximum Operating Temperature: +60 °C



2125493 RS PRO

RS PRO DIN RAIL SOLID STATE RELAY

Pack size: **1 x EA**

- Series: RS PRO
- Mounting Type: DIN Rail
- Dimensions: 60.8 x 67.5 x 6.1 mm
- Operating Temperature Range: -25 → +60 °C
- Minimum Operating Temperature: -25 °C
- Length: 60.8 mm
- Depth: 6.1 mm
- Maximum Operating Temperature: +60 °C



2125495 RS PRO

RS PRO DIN RAIL SOLID STATE RELAY

Pack size: **1 x EA**

- Series: RS PRO
- Mounting Type: DIN Rail
- Dimensions: 60.8 x 67.5 x 6.1 mm
- Operating Temperature Range: -25 → +60 °C
- Minimum Operating Temperature: -25 °C
- Length: 60.8 mm
- Depth: 6.1 mm
- Maximum Operating Temperature: +60 °C



2125496 RS PRO

RS PRO DIN RAIL SOLID STATE RELAY

Pack size: **1 x EA**

- Series: RS PRO
- Mounting Type: DIN Rail
- Dimensions: 60.8 x 67.5 x 6.1 mm
- Operating Temperature Range: -25 → +60 °C
- Minimum Operating Temperature: -25 °C
- Length: 60.8 mm
- Depth: 6.1 mm
- Maximum Operating Temperature: +60 °C



2125497 RS PRO

RS PRO DIN RAIL SOLID STATE RELAY

Pack size: **1 x EA**

- Series: RS PRO
- Mounting Type: DIN Rail
- Dimensions: 60.8 x 67.5 x 6.1 mm
- Operating Temperature Range: -25 → +60 °C
- Minimum Operating Temperature: -25 °C
- Length: 60.8 mm
- Depth: 6.1 mm
- Maximum Operating Temperature: +60 °C



2125499 RS PRO

RS PRO DIN RAIL SOLID STATE RELAY, 20 A MAX. LOAD, 530 VRMS MAX.

Pack size: **1 x EA**

- Maximum Load Current: 20 A
- Mounting Type: DIN Rail
- Minimum Load Voltage: 48 Vrms
- Maximum Load Voltage: 530 Vrms
- Minimum Control Voltage: 4 V dc
- Maximum Control Voltage: 32 V dc
- Switching Type: Random
- Contact Configuration: SP



1213891 20 A

RS PRO DIN RAIL SOLID STATE RELAY, 2 A MAX. LOAD, 264 V MAX. LOAD, 30

Pack size: **5 x EA**

- Minimum Load Current: 5 mA
- Maximum Load Current: 2 A
- Mounting Type: DIN Rail
- Minimum Load Voltage: 20 V
- Maximum Load Voltage: 264 V
- Minimum Control Voltage: 11 V
- Maximum Control Voltage: 30 V
- Switching Type: AC



8886855 5 mA

RS PRO DIN RAIL SOLID STATE RELAY, 30 A MAX. LOAD, 530 VRMS MAX.

Pack size: **1 x EA**

- Maximum Load Current: 30 A
- Mounting Type: DIN Rail
- Minimum Load Voltage: 48 Vrms
- Maximum Load Voltage: 530 Vrms
- Minimum Control Voltage: 4 V dc
- Maximum Control Voltage: 32 V dc
- Switching Type: Random
- Contact Configuration: SP



1213895 30 A

RS PRO DIN RAIL SOLID STATE RELAY, 5 A MAX. LOAD, 30 V MAX. LOAD, 30 V

Pack size: **5 x EA**

- Minimum Load Current: 1 mA
- Maximum Load Current: 5 A
- Mounting Type: DIN Rail
- Minimum Load Voltage: 10 V
- Maximum Load Voltage: 30 V
- Minimum Control Voltage: 11 V
- Maximum Control Voltage: 30 V
- Switching Type: DC



8886868 1 mA

RS PRO DIN RAIL SOLID STATE RELAY, 2 A MAX. LOAD, 30 V MAX. LOAD, 30 V

Pack size: **5 x EA**

- Minimum Load Current: 1 mA
- Maximum Load Current: 2 A
- Mounting Type: DIN Rail
- Minimum Load Voltage: 10 V
- Maximum Load Voltage: 30 V
- Minimum Control Voltage: 11 V
- Maximum Control Voltage: 30 V
- Switching Type: DC



8886859 1 mA

DC SWITCHING 200 VOLT 20A PANEL MOUNT SS

Pack size: **1 x EA**

- Minimum Load Current: 5 mA
- Maximum Load Current: 20 A
- Series: RMID
- Mounting Type: Panel Mount
- Minimum Load Voltage: 1 V ac/dc
- Maximum Load Voltage: 200 V ac/dc
- Switching Type: DC Switching
- Contact Configuration: SPNO



2303311 5 mA

RS PRO DIN RAIL SOLID STATE RELAY, 3 A MAX. LOAD, 30 V MAX. LOAD, 230

Pack size: **5 x EA**

- Minimum Load Current: 1 mA
- Maximum Load Current: 3 A
- Mounting Type: DIN Rail
- Minimum Load Voltage: 10 V
- Maximum Load Voltage: 30 V
- Minimum Control Voltage: 110 V
- Maximum Control Voltage: 230 V
- Switching Type: DC



8886938 1 mA

RS PRO DIN RAIL SOLID STATE RELAY, 2 A MAX. LOAD, 264 V MAX. LOAD, 30

Pack size: **5 x EA**

- Minimum Load Current: 5 mA
- Maximum Load Current: 2 A
- Mounting Type: DIN Rail
- Minimum Load Voltage: 20 V
- Maximum Load Voltage: 264 V
- Minimum Control Voltage: 11 V
- Maximum Control Voltage: 30 V
- Switching Type: AC



8886922 5 mA

RS PRO DIN RAIL SOLID STATE RELAY

Pack size: **1 x EA**

- Series: RS PRO
- Mounting Type: DIN Rail
- Dimensions: 61.7 x 91 x 6.2 mm
- Operating Temperature Range: -25 → +60 °C
- Minimum Operating Temperature: -25 °C
- Length: 61.7 mm
- Depth: 6.2 mm
- Maximum Operating Temperature: +60 °C



9054302 RS PRO

MULTIFUNCTION TIMER

Pack size: **1 x EA**

- Supply Voltage: 12 → 230 V ac/dc
- Mounting Type: DIN Rail
- Time Range: 0.1 s → 100 h
- Mode of Operation: Multifunction
- Number of Timer Functions: Multi Function
- Contact Configuration: SPDT
- Time Increment: Hours, Seconds
- Maximum Voltage: 230 V



1026122 12 → 230 V ac/dc

RS PRO DIN RAIL SOLID STATE RELAY, 5 A MAX. LOAD, 30 V MAX. LOAD, 30 V

Pack size: **5 x EA**

- Minimum Load Current: 1 mA
- Maximum Load Current: 5 A
- Mounting Type: DIN Rail
- Minimum Load Voltage: 10 V
- Maximum Load Voltage: 30 V
- Minimum Control Voltage: 11 V
- Maximum Control Voltage: 30 V
- Switching Type: DC



8886934 1 mA

OPTOCOUPLER, 100MA DC, DIN, 5-30VDC

Pack size: **1 x EA**

- Series: RS PRO
- Mounting Type: DIN Rail
- Dimensions: 60.8 x 67.5 x 6.1 mm
- Operating Temperature Range: -25 → +60 °C
- Minimum Operating Temperature: -25 °C
- Length: 60.8 mm
- Depth: 6.1 mm
- Maximum Operating Temperature: +60 °C



9054277 RS PRO

RS PRO DIN RAIL MULTI FUNCTION TIMER RELAY, 12 → 230V AC/DC,

Pack size: **1 x EA**

- Supply Voltage: 12 → 230 V ac/dc
- Mounting Type: DIN Rail
- Time Range: 0.1 s → 100 h
- Mode of Operation: ON Delay
- Number of Timer Functions: Multi Function
- Contact Configuration: DPDT
- Time Increment: Hours, Seconds
- Maximum Voltage: 230 V



1026125 12 → 230 V ac/dc

TWO POLE MULTIFUNCTION TIMER

Pack size: **1 x EA**

- Supply Voltage: 12 → 230 V ac/dc
- Mounting Type: DIN Rail
- Time Range: 0.1 s → 100 h
- Mode of Operation: Multifunction
- Number of Timer Functions: Multi Function
- Contact Configuration: DPDT
- Time Increment: Hours, Seconds
- Maximum Voltage: 230 V



1026123 12 → 230 V ac/dc

DELAY OFF TIMER (SWITCH INITIATED)

Pack size: **1 x EA**

- Supply Voltage: 12 → 230 V ac/dc
- Mounting Type: DIN Rail
- Time Range: 0.1 s → 100 h
- Number of Timer Functions: Multi Function
- Contact Configuration: SPDT
- Time Increment: Hours, Seconds
- Maximum Voltage: 230 V
- Maximum Current: 8 A



1026128 12 → 230 V ac/dc

RS PRO DIN RAIL MULTI FUNCTION TIMER RELAY, 12 → 230V AC/DC,

Pack size: **1 x EA**

- Supply Voltage: 12 → 230 V ac/dc
- Mounting Type: DIN Rail
- Time Range: 0.1 s → 100 h
- Number of Timer Functions: Multi Function
- Contact Configuration: SPDT
- Time Increment: Hours, Seconds
- Maximum Voltage: 230 V
- Maximum Current: 8 A



1026129 12 → 230 V ac/dc

RS PRO DIN RAIL MULTI FUNCTION TIMER RELAY, 12 → 230V AC/DC,

Pack size: **1 x EA**

- Supply Voltage: 12 → 230 V ac/dc
- Mounting Type: DIN Rail
- Time Range: 0.1 s → 100 h
- Mode of Operation: ON Delay
- Number of Timer Functions: Multi Function
- Contact Configuration: SPDT
- Time Increment: Hours, Seconds
- Maximum Voltage: 230 V



1026124 12 → 230 V ac/dc

RS PRO DIN RAIL MULTI FUNCTION TIMER RELAY, 12 → 230V AC/DC,

Pack size: **1 x EA**

- Supply Voltage: 12 → 230 V ac/dc
- Mounting Type: DIN Rail
- Time Range: 0.1 s → 100 h
- Number of Timer Functions: Multi Function
- Contact Configuration: SPDT
- Time Increment: Hours, Seconds
- Maximum Voltage: 230 V
- Maximum Current: 8 A



1026127 12 → 230 V ac/dc

RS PRO ROTATING BEACON, 12 V DC, 24 V DC, SURFACE MOUNT,

Pack size: **1 x EA**

- Supply Voltage: 12 V dc, 24 V dc
- Light Effect: Rotating
- Mounting Style: Surface Mount
- Bulb Type: Incandescent
- Current Type: DC
- Base Diameter: 166 mm
- Housing Colour: Black
- Lamp Included: Yes



236284 12 V dc, 24 V dc

XENON SP 10-100VDC/20-72VAC 2W RED

Pack size: **1 x EA**

- Supply Voltage: 10 → 100 V dc, 20 → 72 V ac
- Light Effect: Flashing
- Lens Colour: Red
- Mounting Style: Surface Mount, Wall Mount
- Bulb Type: Xenon
- Current Type: AC, DC
- Current Consumption: 130 mA
- Base Diameter: 72 mm



1879642 10 → 100 V dc, 20

XENON LP 10-100VDC/20-72VAC 2W RED

Pack size: **1 x EA**

- Supply Voltage: 10 → 100 V dc, 20 → 72 V ac
- Light Effect: Flashing
- Lens Colour: Red
- Mounting Style: Stud Mount, Surface Mount
- Bulb Type: Xenon
- Current Consumption: 110 mA
- Current Type: AC, DC
- Base Diameter: 76 mm



1879651 10 → 100 V dc, 20

XENON SP 10-100VDC/20-72VAC 2W AMBER

Pack size: **1 x EA**

- Supply Voltage: 10 → 100 V dc, 20 → 72 V ac
- Light Effect: Flashing
- Lens Colour: Amber
- Mounting Style: Surface Mount, Wall Mount
- Bulb Type: Xenon
- Current Type: AC, DC
- Current Consumption: 130 mA
- Base Diameter: 72 mm



1879643 10 → 100 V dc, 20

XENON LP 18-30VDC 1W RED

Pack size: **1 x EA**

- Supply Voltage: 18 → 30 V dc
- Light Effect: Flashing
- Lens Colour: Red
- Mounting Style: Stud Mount, Surface Mount
- Bulb Type: Xenon
- Current Consumption: 40 mA
- Current Type: DC
- Base Diameter: 76 mm



1879653 18 → 30 V dc

XENON LP 18-30VDC 1W AMBER

Pack size: **1 x EA**

- Supply Voltage: 18 → 30 V dc
- Light Effect: Flashing
- Lens Colour: Amber
- Mounting Style: Stud Mount, Surface Mount
- Bulb Type: Xenon
- Current Consumption: 40 mA
- Current Type: DC
- Base Diameter: 76 mm



1879652 18 → 30 V dc

XENON LP 10-100VDC/20-72VAC 2W AMBER

Pack size: **1 x EA**

- Supply Voltage: 10 → 100 V dc, 20 → 72 V ac
- Light Effect: Flashing
- Lens Colour: Amber
- Mounting Style: Stud Mount, Surface Mount
- Bulb Type: Xenon
- Current Consumption: 110 mA
- Current Type: AC, DC
- Base Diameter: 76 mm



1879654 10 → 100 V dc, 20

RS PRO RED STEADY BEACON, 12 V DC, LED BULB, IP67

Pack size: **1 x EA**

- Supply Voltage: 12 V dc
- Light Effect: Steady
- Lens Colour: Red
- Bulb Type: LED
- Current Type: DC
- Housing Colour: Red
- Lamp Included: Yes
- Height: 16 mm



1902923 12 V dc

RS PRO RED STEADY BEACON, 24 V DC, LED BULB, IP67

Pack size: **1 x EA**

- Supply Voltage: 24 V dc
- Light Effect: Steady
- Lens Colour: Red
- Bulb Type: LED
- Current Type: DC
- Housing Colour: Red
- Lamp Included: Yes
- Height: 16 mm



1902924 24 V dc

RS PRO BLUE STEADY BEACON, 24 VDC, SCREW MOUNT, LED BULB, IP66

Pack size: **1 x EA**

- Supply Voltage: 24 Vdc
- Light Effect: Steady
- Lens Colour: Blue
- Mounting Style: Screw Mount
- Bulb Type: LED
- Current Consumption: 40 mA
- Base Diameter: 70 mm
- Housing Colour: White



1999731 24 Vdc

RS PRO GREEN STEADY BEACON, 24 VDC, SCREW MOUNT, LED BULB, IP66

Pack size: **1 x EA**

- Supply Voltage: 24 Vdc
- Light Effect: Steady
- Lens Colour: Green
- Mounting Style: Screw Mount
- Bulb Type: LED
- Current Consumption: 40 mA
- Base Diameter: 70 mm
- Housing Colour: White



1999729 24 Vdc

RS PRO RED STEADY BEACON, 24 VDC, SCREW MOUNT, LED BULB, IP66

Pack size: **1 x EA**

- Supply Voltage: 24 Vdc
- Light Effect: Steady
- Lens Colour: Red
- Mounting Style: Screw Mount
- Bulb Type: LED
- Current Consumption: 40 mA
- Base Diameter: 70 mm
- Housing Colour: White



1999733 24 Vdc

RS PRO RED MULTIPLE EFFECT BEACON, 12 V AC/DC, 24 V AC/DC,

Pack size: **1 x EA**

- Supply Voltage: 12 V ac/dc, 24 V ac/dc
- Light Effect: Flashing, Rotating, Steady
- Lens Colour: Red
- Mounting Style: Base Mount
- Bulb Type: LED
- Current Type: AC, DC
- Series: M-LINE FLR



1999763 12 V ac/dc, 24 V

RS PRO AMBER MULTIPLE EFFECT BEACON, 12 V AC/DC, 24 V AC/DC,

Pack size: **1 x EA**

- Supply Voltage: 12 V ac/dc, 24 V ac/dc
- Light Effect: Flashing, Rotating, Steady
- Lens Colour: Amber
- Mounting Style: Base Mount
- Bulb Type: LED
- Current Type: AC, DC
- Series: M-LINE FLR



1999764 12 V ac/dc, 24 V

LED BEACON, AMBER, DUAL VOLTAGE, 12/24DV

Pack size: **1 x EA**

- Supply Voltage: 12 V dc, 24 V dc
- Light Effect: Flashing
- Lens Colour: Amber
- Mounting Style: Surface Mount, Wall Mount
- Bulb Type: LED
- Current Consumption: 350 mA
- Current Type: DC
- Housing Colour: Black



9075955 12 V dc, 24 V dc

RS PRO GREEN MULTIPLE EFFECT BEACON, 12 V AC/DC, 24 V AC/DC,

Pack size: **1 x EA**

- Supply Voltage: 12 V ac/dc, 24 V ac/dc
- Light Effect: Flashing, Rotating, Steady
- Lens Colour: Green
- Mounting Style: Base Mount
- Bulb Type: LED
- Current Type: AC, DC
- Series: M-LINE FLR



1999766 12 V ac/dc, 24 V

LED BEACON, RED, DUAL VOLTAGE, 12/24VDC

Pack size: **1 x EA**

- Supply Voltage: 12 V dc, 24 V dc
- Light Effect: Flashing
- Lens Colour: Red
- Mounting Style: Surface Mount, Wall Mount
- Bulb Type: LED
- Current Consumption: 350 mA
- Current Type: DC
- Housing Colour: Black



9075959 12 V dc, 24 V dc

LED BEACON, AMBER, LOW PROF, 10-100VDC

Pack size: **1 x EA**

- Supply Voltage: 10 → 100 V dc
- Light Effect: Flashing
- Lens Colour: Amber
- Mounting Style: Screw Mount
- Bulb Type: LED
- Current Type: DC
- Base Diameter: 77 mm
- Housing Colour: Black



9075961 10 → 100 V dc

LED BEACON, RED, LOW PROF, 10-100VDC

Pack size: **1 x EA**

- Supply Voltage: 10 → 100 V dc
- Light Effect: Flashing
- Lens Colour: Red
- Mounting Style: Screw Mount
- Bulb Type: LED
- Current Type: DC
- Base Diameter: 77 mm
- Housing Colour: Black



9075965 10 → 100 V dc

RS PRO GREEN FLASHING LIGHT MODULE, 12 V DC, 24 V DC, SURFACE

Pack size: **1 x EA**

- Supply Voltage: 12 V dc, 24 V dc
- Light Effect: Flashing
- Lens Colour: Green
- Mounting Style: Surface Mount, Wall Mount
- Bulb Type: LED
- Current Consumption: 350 mA
- Current Type: DC
- Housing Colour: Black



9075968 12 V dc, 24 V dc

RS PRO GREEN FLASHING BEACON, 10 → 100 V DC, SCREW MOUNT, LED

Pack size: **1 x EA**

- Supply Voltage: 10 → 100 V dc
- Light Effect: Flashing
- Lens Colour: Green
- Mounting Style: Screw Mount
- Bulb Type: LED
- Current Type: DC
- Base Diameter: 77 mm
- Housing Colour: Black



9075974 10 → 100 V dc

RS PRO AMBER FLASHING BEACON, 10 → 100 V DC, SCREW MOUNT, LED

Pack size: **1 x EA**

- Supply Voltage: 10 → 100 V dc
- Light Effect: Flashing
- Lens Colour: Amber
- Mounting Style: Screw Mount
- Bulb Type: LED
- Current Type: DC
- Base Diameter: 77 mm
- Housing Colour: Black



9075980 10 → 100 V dc

LED BEACON, RED, TALL PROF, 10-100VDC

Pack size: **1 x EA**

- Supply Voltage: 10 → 100 V dc
- Light Effect: Flashing
- Lens Colour: Red
- Mounting Style: Screw Mount
- Bulb Type: LED
- Current Type: DC
- Base Diameter: 77 mm
- Housing Colour: Black



9075983 10 → 100 V dc

RS PRO AMBER FLASHING BEACON, 10 → 100 V DC, MAGNETIC MOUNT, LED

Pack size: **1 x EA**

- Supply Voltage: 10 → 100 V dc
- Light Effect: Flashing
- Lens Colour: Amber
- Mounting Style: Magnetic Mount
- Bulb Type: LED
- Current Consumption: 300 mA, 600 mA
- Current Type: DC
- Base Diameter: 150 mm



9075993 10 → 100 V dc

RS PRO AMBER FLASHING BEACON, 10 → 100 V DC, FLEXI DIN MOUNT, LED

Pack size: **1 x EA**

- Supply Voltage: 10 → 100 V dc
- Light Effect: Flashing
- Lens Colour: Amber
- Mounting Style: Flexi DIN Mount
- Bulb Type: LED
- Current Consumption: 300 mA, 600 mA
- Current Type: DC
- Base Diameter: 108 mm



9076003 10 → 100 V dc

RS PRO RED FLASHING BEACON, 10 → 100 V DC, MAGNETIC MOUNT, LED

Pack size: **1 x EA**

- Supply Voltage: 10 → 100 V dc
- Light Effect: Flashing
- Lens Colour: Red
- Mounting Style: Magnetic Mount
- Bulb Type: LED
- Current Consumption: 300 mA, 600 mA
- Current Type: DC
- Base Diameter: 150 mm



9076006 10 → 100 V dc

RS PRO GREEN FLASHING BEACON, 10 → 100 V DC, MAGNETIC MOUNT, LED

Pack size: **1 x EA**

- Supply Voltage: 10 → 100 V dc
- Light Effect: Flashing
- Lens Colour: Green
- Mounting Style: Magnetic Mount
- Bulb Type: LED
- Current Consumption: 300 mA, 600 mA
- Current Type: DC
- Base Diameter: 150 mm



9076009 10 → 100 V dc

RS PRO RED FLASHING BEACON, 10 → 100 V DC, FLEXI DIN MOUNT, LED

Pack size: **1 x EA**

- Supply Voltage: 10 → 100 V dc
- Light Effect: Flashing
- Lens Colour: Red
- Mounting Style: Flexi DIN Mount
- Bulb Type: LED
- Current Consumption: 300 mA, 600 mA
- Current Type: DC
- Base Diameter: 108 mm



9076012 10 → 100 V dc

RS PRO AMBER FLASHING BEACON, 10 → 100 V DC, DIN MOUNT, TUBE

Pack size: **1 x EA**

- Supply Voltage: 10 → 100 V dc
- Light Effect: Flashing
- Lens Colour: Amber
- Mounting Style: DIN Mount, Tube Mount
- Bulb Type: LED
- Current Type: DC
- Current Consumption: 300 mA, 600 mA
- Base Diameter: 108 mm



9076019 10 → 100 V dc

RS PRO GREEN FLASHING BEACON, 10 → 100 V DC, DIN MOUNT, TUBE

Pack size: **1 x EA**

- Supply Voltage: 10 → 100 V dc
- Light Effect: Flashing
- Lens Colour: Green
- Mounting Style: DIN Mount, Tube Mount
- Bulb Type: LED
- Current Consumption: 300 mA, 600 mA
- Current Type: DC
- Base Diameter: 108 mm



9076021 10 → 100 V dc

RS PRO AMBER FLASHING BEACON, 10 → 100 V DC, SURFACE MOUNT, LED

Pack size: **1 x EA**

- Supply Voltage: 10 → 100 V dc
- Light Effect: Flashing
- Lens Colour: Amber
- Mounting Style: Surface Mount, Wall Mount
- Bulb Type: LED
- Current Consumption: 300 mA, 600 mA
- Current Type: DC
- Base Diameter: 150 mm



9076025 10 → 100 V dc

RS PRO RED FLASHING BEACON, 10 → 100 V DC, DIN MOUNT, TUBE MOUNT, LED

Pack size: **1 x EA**

- Supply Voltage: 10 → 100 V dc
- Light Effect: Flashing
- Lens Colour: Red
- Mounting Style: DIN Mount, Tube Mount
- Bulb Type: LED
- Current Consumption: 300 mA, 600 mA
- Current Type: DC
- Base Diameter: 108 mm



9076028 10 → 100 V dc

RS PRO AMBER FLASHING BEACON, 10 → 100 V DC, SINGLE POINT MOUNT,

Pack size: **1 x EA**

- Supply Voltage: 10 → 100 V dc
- Light Effect: Flashing
- Lens Colour: Amber
- Mounting Style: Single Point Mount
- Bulb Type: LED
- Current Consumption: 300 mA, 600 mA
- Current Type: DC
- Base Diameter: 108 mm



9076031 10 → 100 V dc

RS PRO RED FLASHING BEACON, 10 → 100 V DC, SURFACE MOUNT, WALL

Pack size: **1 x EA**

- Supply Voltage: 10 → 100 V dc
- Light Effect: Flashing
- Lens Colour: Red
- Mounting Style: Surface Mount, Wall Mount
- Bulb Type: LED
- Current Consumption: 300 mA, 600 mA
- Current Type: DC
- Base Diameter: 150 mm



9076034 10 → 100 V dc

RS PRO GREEN FLASHING BEACON, 10 → 100 V DC, SURFACE MOUNT,

Pack size: **1 x EA**

- Supply Voltage: 10 → 100 V dc
- Light Effect: Flashing
- Lens Colour: Green
- Mounting Style: Surface Mount, Wall Mount
- Bulb Type: LED
- Current Consumption: 300 mA, 600 mA
- Current Type: DC
- Base Diameter: 150 mm



9076037 10 → 100 V dc

RS PRO RED FLASHING BEACON, 10 → 100 V DC, SINGLE POINT MOUNT, LED

Pack size: **1 x EA**

- Supply Voltage: 10 → 100 V dc
- Light Effect: Flashing
- Lens Colour: Red
- Mounting Style: Single Point Mount
- Bulb Type: LED
- Current Type: DC
- Current Consumption: 300 mA, 600 mA
- Base Diameter: 108 mm



9076040 10 → 100 V dc

RS PRO GREEN FLASHING BEACON, 10 → 100 V DC, SINGLE POINT MOUNT,

Pack size: **1 x EA**

- Supply Voltage: 10 → 100 V dc
- Light Effect: Flashing
- Lens Colour: Green
- Mounting Style: Single Point Mount
- Bulb Type: LED
- Current Consumption: 300 mA, 600 mA
- Current Type: DC
- Base Diameter: 108 mm



9076043 10 → 100 V dc

RS PRO AMBER FLASHING BEACON, 10 → 30 V DC, FLEXI DIN MOUNT, LED

Pack size: **1 x EA**

- Supply Voltage: 10 → 30 V dc
- Light Effect: Flashing
- Lens Colour: Amber
- Mounting Style: Flexi DIN Mount
- Bulb Type: LED
- Current Consumption: 1.3 A, 2 A
- Current Type: DC
- Base Diameter: 137 mm



9076047 10 → 30 V dc

RS PRO AMBER FLASHING BEACON, 10 → 30 V DC, SURFACE MOUNT,

Pack size: **1 x EA**

- Supply Voltage: 10 → 30 V dc
- Light Effect: Flashing
- Lens Colour: Amber
- Mounting Style: Surface Mount, Wall Mount
- Bulb Type: LED
- Current Consumption: 1.3 A, 2 A
- Current Type: DC
- Base Diameter: 150 mm



9076056 10 → 30 V dc

RS PRO BLACK SINGLE-TONE ELECTRONIC SOUNDER, 12 → 80 V DC,

Pack size: **1 x EA**

- Supply Voltage: 12 → 80 V dc
- Decibels at 1 Metre: 97 dB
- Current Type: DC
- Number Of Tones: 1
- Housing Colour: Black
- Mounting Style: Universal
- Application Type: Sounder
- Maximum Decibel: 97 dB



235354 12 → 80 V dc

RS PRO BLACK SINGLE-TONE ELECTRONIC SOUNDER, 12 → 80 V DC,

Pack size: **1 x EA**

- Supply Voltage: 12 → 80 V dc
- Decibels at 1 Metre: 107 dB
- Current Type: DC
- Number Of Tones: 1
- Housing Colour: Black
- Mounting Style: Universal
- Application Type: Sounder
- Maximum Decibel: 107 dB



235360 12 → 80 V dc

RS PRO BLACK SINGLE-TONE ELECTRONIC SOUNDER, 12 → 80 V DC,

Pack size: **1 x EA**

- Supply Voltage: 12 → 80 V dc
- Decibels at 1 Metre: 97 dB
- Current Type: DC
- Number Of Tones: 1
- Housing Colour: Black
- Mounting Style: Universal
- Application Type: Sounder
- Maximum Decibel: 97 dB



235405 12 → 80 V dc

RS PRO BLACK SINGLE-TONE ELECTRONIC SOUNDER, 12 → 80 V DC,

Pack size: **1 x EA**

- Supply Voltage: 12 → 80 V dc
- Decibels at 1 Metre: 107 dB
- Current Type: DC
- Number Of Tones: 1
- Housing Colour: Black
- Mounting Style: Universal
- Application Type: Sounder
- Maximum Decibel: 107 dB



235411 12 → 80 V dc

RS PRO RED 8-TONE ELECTRONIC SOUNDER, 10 → 30 V DC, CONDUIT

Pack size: **1 x EA**

- Supply Voltage: 10 → 30 V dc
- IP Rating: IP64, IP65
- Current Type: DC
- Number Of Tones: 8
- Housing Colour: Red
- Mounting Style: Conduit Box, Panel Mount, Surface Mount
- Diameter: 101 mm
- Application Type: Sounder



1445945 10 → 30 V dc

RS PRO RED SINGLE-TONE ELECTRONIC SOUNDER, 24 V, 114DB

Pack size: **1 x EA**

- Supply Voltage: 24 V
- Decibels at 1 Metre: 114 dB
- Current Type: DC
- Number Of Tones: 1
- Housing Colour: Red
- Application Type: Sounder
- Series: superCELERE



1999748 24 V

RS PRO RED SINGLE-TONE SIREN, 24 V, 114DB AT 1 METRE

Pack size: **1 x EA**

- Supply Voltage: 24 V
- Decibels at 1 Metre: 114 dB
- Current Type: AC, DC
- Number Of Tones: 1
- Housing Colour: Red
- Application Type: Sounder
- Series: superCELERE



1999750 24 V

RS PRO GREY SINGLE-TONE SIREN, 24 V, 96DB AT 1 METRE

Pack size: **1 x EA**

- Supply Voltage: 24 V
- Decibels at 1 Metre: 96 dB
- Current Type: DC
- Number Of Tones: 1
- Housing Colour: Grey
- Application Type: Sounder
- Maximum Decibel: 93 dB
- Series: MICRO W10



1999752 24 V

RS PRO RED ELECTRONIC SOUNDER, 24 V, 114DB AT 1 METRE, IP44

Pack size: **1 x EA**

- Supply Voltage: 24 V
- IP Rating: IP44
- Decibels at 1 Metre: 114 dB
- Current Type: DC
- Housing Colour: Red
- Application Type: Sounder



1999770 24 V

RS PRO 95DB PANEL MOUNT BUZZER, 10V DC MIN, 20V DC MAX

Pack size: **1 x EA**

- Mounting Type: Panel Mount
- Minimum Supply Voltage: 10 V dc
- Maximum Supply Voltage: 20 V dc
- Sound Level: 95 dB



2262981 Panel Mount

RS PRO 95DB PANEL MOUNT BUZZER, 130V AC MIN, 240V AC MAX

Pack size: **1 x EA**

- Mounting Type: Panel Mount
- Minimum Supply Voltage: 130 V ac
- Maximum Supply Voltage: 240 V ac
- Sound Level: 95 dB



2262982 Panel Mount

RS PRO 95DB PANEL MOUNT BUZZER, 10V DC MIN, 28V DC MAX

Pack size: **1 x EA**

- Mounting Type: Panel Mount
- Minimum Supply Voltage: 10 V dc
- Maximum Supply Voltage: 28 V dc
- Sound Level: 95 dB



2262983 Panel Mount

RS PRO RED/GREEN LED BEACON, 2 LIGHTS, 24 V DC, SURFACE MOUNT

Pack size: **1 x EA**

- Series: LED-TLM
- Number of Light Elements: 2
- Lens Colour: Red/Green
- Bulb Type: LED
- LED Colour: Red/Green
- Light Effect: Steady
- Multifunction: Yes
- Mounting Style: Surface Mount



1445948 LED-TLM

RS PRO RED/GREEN/AMBER LED BEACON, 3 LIGHTS, 24 V DC,

Pack size: **1 x EA**

- Series: LED-TLM
- Number of Light Elements: 3
- Lens Colour: Red/Green/Amber
- Bulb Type: LED
- LED Colour: Amber, Green, Red
- Light Effect: Steady
- Multifunction: Yes
- Mounting Style: Surface Mount



1445949 LED-TLM

RS PRO RED/GREEN SIGNAL TOWER, 24 V AC/DC

Pack size: **1 x EA**

- Lens Colour: Red/Green
- Bulb Type: LED
- Light Effect: Steady
- Height: 193 mm
- Base Diameter: 100 mm
- Supply Voltage: 24 V ac/dc
- IP Rating: IP66
- Maximum Temperature: +50 °C



1902805 Red/Green

RS PRO RED/GREEN SIGNAL TOWER, 24 V AC/DC

Pack size: **1 x EA**

- Lens Colour: Red/Green
- Bulb Type: LED
- Light Effect: Flashing, Steady
- Multifunction: Yes
- Height: 190 mm
- Base Diameter: 48 mm
- IP Rating: IP66
- Supply Voltage: 24 V ac/dc



1902831 Red/Green

RS PRO RED/GREEN/AMBER SIGNAL TOWER, 24 V AC/DC

Pack size: **1 x EA**

- Lens Colour: Red/Green/Amber
- Bulb Type: LED
- Light Effect: Steady
- Height: 228 mm
- Base Diameter: 100 mm
- Supply Voltage: 24 V ac/dc
- IP Rating: IP66
- Maximum Temperature: +50 °C



1902807 Red/Green/Ambe

RS PRO RED/GREEN/AMBER SIGNAL TOWER, 24 V AC/DC

Pack size: **1 x EA**

- Lens Colour: Red/Green/Amber
- Bulb Type: LED
- Light Effect: Flashing, Steady
- Multifunction: Yes
- Height: 237 mm
- Base Diameter: 48 mm
- IP Rating: IP66
- Supply Voltage: 24 V ac/dc



1902834 Red/Green/Ambe

RS PRO RED/GREEN SIGNAL TOWER, 24 V AC/DC

Pack size: **1 x EA**

- Lens Colour: Red/Green
- Bulb Type: LED
- Light Effect: Steady
- Height: 200 mm
- Base Diameter: 68 mm
- Supply Voltage: 24 V ac/dc
- IP Rating: IP66
- Maximum Temperature: +50 °C



1902859 Red/Green

RS PRO SIGNAL TOWER, 2 LIGHTS, 24 V

Pack size: **1 x EA**

- Series: BABY TWS
- Number of Light Elements: 2
- Bulb Type: LED
- Sounder Component: No Sounder Component
- Supply Voltage: 24 V



1999758 BABY TWS

RS PRO SIGNAL TOWER, 3 LIGHTS, 24 V

Pack size: **1 x EA**

- Series: BABY TWS
- Number of Light Elements: 3
- Bulb Type: LED
- Sounder Component: No Sounder Component
- Supply Voltage: 24 V



1999760 BABY TWS

RS PRO STEADY EFFECT BASE, 24 V AC/DC, AC, DC, IP66

Pack size: **1 x EA**

- Component Type: Steady Light Connection Base
- Multifunction: Yes
- Current Type: AC, DC
- Light Effect: Steady
- Supply Voltage: 24 V ac/dc
- Height: 78 mm
- Base Diameter: 70 mm
- IP Rating: IP66



1902813 Steady Light

RS PRO MULTIPLE EFFECT BASE, 24 V AC/DC, AC, DC, IP66

Pack size: **1 x EA**

- Component Type: Multi-Function Connection Base
- Multifunction: Yes
- Current Type: AC, DC
- Light Effect: Flashing, Steady
- Supply Voltage: 24 V ac/dc
- Height: 78 mm
- Base Diameter: 70 mm
- IP Rating: IP66



1902815 Multi-Function

RS PRO AMBER MULTIPLE EFFECT BEACON UNIT, 24 V AC/DC, LED

Pack size: **1 x EA**

- Component Type: Beacon
- Multifunction: Yes
- Current Type: AC, DC
- Light Effect: Flashing, Steady
- Lens Colour: Amber
- Lamp Included: Yes
- Bulb Type: LED
- Supply Voltage: 24 V ac/dc



1902839 Beacon

RS PRO RED MULTIPLE EFFECT BEACON UNIT, 24 V AC/DC, LED

Pack size: **1 x EA**

- Component Type: Beacon
- Multifunction: Yes
- Current Type: AC, DC
- Light Effect: Flashing, Steady
- Lens Colour: Red
- Lamp Included: Yes
- Bulb Type: LED
- Supply Voltage: 24 V ac/dc



1902840 Beacon

RS PRO GREEN MULTIPLE EFFECT BEACON UNIT, 24 V AC/DC, LED

Pack size: **1 x EA**

- Component Type: Beacon
- Multifunction: Yes
- Current Type: AC, DC
- Light Effect: Flashing, Steady
- Lens Colour: Green
- Lamp Included: Yes
- Bulb Type: LED
- Supply Voltage: 24 V ac/dc



1902841 Beacon

RS PRO YELLOW MULTIPLE EFFECT BEACON UNIT, 24 V AC/DC, LED

Pack size: **1 x EA**

- Component Type: Beacon
- Multifunction: Yes
- Current Type: AC, DC
- Light Effect: Flashing, Steady
- Lens Colour: Yellow
- Lamp Included: Yes
- Bulb Type: LED
- Supply Voltage: 24 V ac/dc



1902842 Beacon

RS PRO CLEAR MULTIPLE EFFECT BEACON UNIT, 24 V AC/DC, LED

Pack size: **1 x EA**

- Component Type: Beacon
- Multifunction: Yes
- Current Type: AC, DC
- Light Effect: Flashing, Steady
- Lens Colour: Clear
- Lamp Included: Yes
- Bulb Type: LED
- Supply Voltage: 24 V ac/dc



1902843 Beacon

RS PRO BLUE STEADY EFFECT STEADY LIGHT ELEMENT, 24 V AC/DC, LED

Pack size: **1 x EA**

- Component Type: Beacon
- Current Type: AC, DC
- Light Effect: Steady
- Lens Colour: Blue
- Lamp Included: Yes
- Bulb Type: LED
- Supply Voltage: 24 V ac/dc
- Height: 59 mm



1902872 Beacon

RS PRO AMBER STEADY EFFECT STEADY LIGHT ELEMENT, 24 V AC/DC,

Pack size: **1 x EA**

- Component Type: Beacon
- Current Type: AC, DC
- Light Effect: Steady
- Lens Colour: Amber
- Lamp Included: Yes
- Bulb Type: LED
- Supply Voltage: 24 V ac/dc
- Height: 59 mm



1902873 Beacon

RS PRO RED STEADY EFFECT STEADY LIGHT ELEMENT, 24 V AC/DC, LED

Pack size: **1 x EA**

- Component Type: Beacon
- Current Type: AC, DC
- Light Effect: Steady
- Lens Colour: Red
- Lamp Included: Yes
- Bulb Type: LED
- Supply Voltage: 24 V ac/dc
- Height: 59 mm



1902874 Beacon

RS PRO GREEN STEADY EFFECT STEADY LIGHT ELEMENT, 24 V AC/DC,

Pack size: **1 x EA**

- Component Type: Beacon
- Current Type: AC, DC
- Light Effect: Steady
- Lens Colour: Green
- Lamp Included: Yes
- Bulb Type: LED
- Supply Voltage: 24 V ac/dc
- Height: 59 mm



1902875 Beacon

RS PRO YELLOW STEADY EFFECT STEADY LIGHT ELEMENT, 24 V AC/DC,

Pack size: **1 x EA**

- Component Type: Beacon
- Current Type: AC, DC
- Light Effect: Steady
- Lens Colour: Yellow
- Lamp Included: Yes
- Bulb Type: LED
- Supply Voltage: 24 V ac/dc
- Height: 59 mm



1902876 Beacon

RS PRO CLEAR STEADY EFFECT STEADY LIGHT ELEMENT, 24 V AC/DC,

Pack size: **1 x EA**

- Component Type: Beacon
- Current Type: AC, DC
- Light Effect: Steady
- Lens Colour: Clear
- Lamp Included: Yes
- Bulb Type: LED
- Supply Voltage: 24 V ac/dc
- Height: 59 mm



1902877 Beacon

RS PRO AMBER BUZZER BEACON, 12 V DC, 24 V DC, BASE MOUNT

Pack size: **1 x EA**

- Supply Voltage: 12 V dc, 24 V dc
- Lens Colour: Amber
- Mounting Style: Base Mount
- Current Type: DC
- Light Effect: Flashing
- Series: CPM
- Bulb Type: LED
- Maximum Decibel: 96 dB



1999746 12 V dc, 24 V dc

RS PRO SOUNDER BEACON, 24 V, IP44, 114dB AT 1 METRE

Pack size: **1 x EA**

- Supply Voltage: 24 V
- Current Type: DC
- Decibels at 1 Metre: 114 dB
- Housing Colour: Red
- Number Of Tones: 32
- IP Rating: IP44



1999772 24 V

RS PRO IP56 RATED DIN MOUNTING STEM FOR USE WITH DIN & FLEXI DIN

Pack size: **1 x EA**

- Accessory Type: DIN Mounting Stem
- For Use With: DIN & Flexi DIN Beacons
- IP Rating: IP56



235613 DIN Mounting

130MM HIGH BULB CAGE FOR USE WITH XENON BULB

Pack size: **1 x EA**

- Accessory Type: Bulb Cage
- For Use With: Xenon Bulb
- Dimensions: 130 (H) mm



235691 Bulb Cage

RS PRO HALOGEN CLEAR BULB, P14.5S 12 V

Pack size: **1 x EA**

- Accessory Type: Bulb
- Colour: Clear
- Bulb Type: Halogen
- Lamp Base: P14.5s
- Voltage Rating: 12 V
- Dimensions: 10 x 68 mm



235736 Bulb

RS PRO HALOGEN CLEAR BULB, P14.5S 24 V

Pack size: **1 x EA**

- Accessory Type: Bulb
- Colour: Clear
- Bulb Type: Halogen
- Lamp Base: P14.5s
- Voltage Rating: 24 V
- Dimensions: 10 x 68 mm



235720 Bulb

RS PRO AMBER LENS FOR USE WITH INCANDESCENT BEACONS

Pack size: **1 x EA**

- Accessory Type: Lens
- Colour: Amber
- For Use With: Incandescent Beacons



235792 Lens

RS PRO CLEAR LENS FOR USE WITH XENON BEACONS

Pack size: **1 x EA**

- Accessory Type: Lens
- Colour: Clear
- For Use With: Xenon Beacons



235809 Lens

RS PRO RED LENS FOR USE WITH XENON BEACONS

Pack size: **1 x EA**

- Accessory Type: Lens
- Colour: Red
- For Use With: Xenon Beacons



235815 Lens

VWD,BEACON,XENON, LENS,AMBER

Pack size: **1 x EA**

- Accessory Type: Lens
- Colour: Amber
- For Use With: Xenon Beacons



236032 Lens

RS PRO BLUE LENS FOR USE WITH XENON BEACONS

Pack size: **1 x EA**

- Accessory Type: Lens
- Colour: Blue
- For Use With: Xenon Beacons



236010 Lens

RS PRO IP65 RATED RED DEEP BASE FOR USE WITH AE40M

Pack size: **1 x EA**

- Accessory Type: Deep Base
- Colour: Red
- For Use With: AE40M
- IP Rating: IP65
- Dimensions: 93 [Dia.] x 40 mm



1445947 Deep Base

LED BEACON LAMP, AMBER, PC, 24 V DC, 14 CHIP

Pack size: **1 x EA**

- Colour: Amber



1999727 Amber

RS PRO, 8MM GROOVE , SLOT 40 X 40, 2M L

Pack size: **1 x EA**

- Product Family: RS Structural System
- Fits Strut Profile: 40 x 40
- Fits Groove Size: 8 mm
- Length: 2 m
- Internal Width: 28 mm
- Internal Height: 35 mm



8508492 RS Structural

RS PRO 4-WAY CONNECTOR CONNECTING COMPONENT, STRUT

Pack size: **4 x EA**

- Connector Type: 4-Way Connector
- Structural Element Type: Connector Bracket & Joint
- Fits Strut Profile: 25 mm
- Fits Square Tube Profile: 25 mm
- Product Family: RS Square Tube System
- Material: Polymer
- Product System: Versatile Construction System



621720 4-Way

RS PRO 4-WAY CONNECTOR CONNECTING COMPONENT, STRUT

Pack size: **4 x EA**

- Connector Type: 4-Way Connector
- Structural Element Type: Connector Bracket & Joint
- Fits Strut Profile: 25 mm
- Fits Square Tube Profile: 25 mm
- Product Family: RS Square Tube System
- Material: Polymer
- Product System: Versatile Construction System



621736 4-Way

RS PRO 3-WAY CONNECTOR CONNECTING COMPONENT, STRUT

Pack size: **4 x EA**

- Connector Type: 3-Way Connector
- Structural Element Type: Connector Bracket & Joint
- Fits Strut Profile: 25 mm
- Fits Square Tube Profile: 25 mm
- Product Family: RS Square Tube System
- Material: Polymer
- Product System: Versatile Construction System



621708 3-Way

RS PRO 2-WAY CONNECTOR CONNECTING COMPONENT, STRUT

Pack size: **4 x EA**

- Connector Type: 2-Way Connector
- Structural Element Type: Connector Bracket & Joint
- Fits Strut Profile: 25 mm
- Fits Square Tube Profile: 25 mm
- Product Family: RS Square Tube System
- Material: Polymer
- Product System: Versatile Construction System



621691 2-Way Connector

RS PRO 3-WAY CONNECTOR CONNECTING COMPONENT, STRUT

Pack size: **4 x EA**

- Connector Type: 3-Way Connector
- Structural Element Type: Connector Bracket & Joint
- Fits Strut Profile: 25 mm
- Fits Square Tube Profile: 25 mm
- Product Family: RS Square Tube System
- Material: Polymer
- Product System: Versatile Construction System



621714 3-Way

RS PRO 5-WAY CONNECTOR CONNECTING COMPONENT, STRUT

Pack size: **4 x EA**

- Connector Type: 5-Way Connector
- Structural Element Type: Connector Bracket & Joint
- Fits Strut Profile: 25 mm
- Fits Square Tube Profile: 25 mm
- Product Family: RS Square Tube System
- Material: Polymer
- Product System: Versatile Construction System



621742 5-Way

RS PRO SHELF CLIP CONNECTING COMPONENT, STRUT PROFILE 25 MM

Pack size: **12 x EA**

- Connector Type: Shelf Clip
- Structural Element Type: Connector Bracket & Joint
- Fits Strut Profile: 25 mm
- Fits Square Tube Profile: 25 mm
- Product Family: RS Square Tube System
- Material: Steel
- Product System: Versatile Construction System



621792 Shelf Clip

RS PRO T-SLOT NUT CONNECTING COMPONENT, STRUT PROFILE 20 MM,

Pack size: **10 x EA**

- Connector Type: T-Slot Nut
- Structural Element Type: Fixing & Connection Element
- Fits Groove Size: 5 mm
- Thread Size: M3
- Length: 12 mm
- Fits Strut Profile: 20 mm
- Product Family: RS Structural System
- Material: Steel



1809105 T-Slot Nut

RS PRO T-SLOT NUT CONNECTING COMPONENT, STRUT PROFILE 20 MM,

Pack size: **10 x EA**

- Connector Type: T-Slot Nut
- Structural Element Type: Fixing & Connection Element
- Fits Groove Size: 5 mm
- Thread Size: M5
- Length: 12 mm
- Fits Strut Profile: 20 mm
- Product Family: RS Structural System
- Material: Steel



1809104 T-Slot Nut

RS PRO T-SLOT NUT CONNECTING COMPONENT, STRUT PROFILE 20 MM,

Pack size: **10 x EA**

- Connector Type: T-Slot Nut
- Structural Element Type: Fixing & Connection Element
- Fits Groove Size: 5 mm
- Thread Size: M3
- Length: 12 mm
- Fits Strut Profile: 20 mm
- Product Family: RS Structural System
- Material: Steel



1809102 T-Slot Nut

RS PRO T-SLOT NUT CONNECTING COMPONENT, STRUT PROFILE 20 MM,

Pack size: **10 x EA**

- Connector Type: T-Slot Nut
- Structural Element Type: Fixing & Connection Element
- Fits Groove Size: 5 mm
- Thread Size: M4
- Length: 12 mm
- Fits Strut Profile: 20 mm
- Product Family: RS Structural System
- Material: Steel



1809106 T-Slot Nut

RS PRO T-SLOT NUT CONNECTING COMPONENT, STRUT PROFILE 20 MM,

Pack size: **10 x EA**

- Connector Type: T-Slot Nut
- Structural Element Type: Fixing & Connection Element
- Fits Groove Size: 5 mm
- Thread Size: M4
- Length: 12 mm
- Fits Strut Profile: 20 mm
- Product Family: RS Structural System
- Material: Steel



1809103 T-Slot Nut

RS PRO T-SLOT NUT CONNECTING COMPONENT, STRUT PROFILE 20 MM,

Pack size: **10 x EA**

- Connector Type: T-Slot Nut
- Structural Element Type: Fixing & Connection Element
- Fits Groove Size: 5 mm
- Thread Size: M5
- Length: 12 mm
- Fits Strut Profile: 20 mm
- Product Family: RS Structural System
- Material: Steel



1809107 T-Slot Nut

RS PRO T-SLOT NUT CONNECTING COMPONENT, STRUT PROFILE 20 MM,

Pack size: **10 x EA**

- Connector Type: T-Slot Nut
- Structural Element Type: Fixing & Connection Element
- Fits Groove Size: 5 mm
- Thread Size: M4
- Length: 12 mm
- Fits Strut Profile: 20 mm
- Product Family: RS Structural System
- Material: Stainless Steel



1809108 T-Slot Nut

RS PRO T-SLOT NUT CONNECTING COMPONENT, STRUT PROFILE 20 MM,

Pack size: **10 x EA**

- Connector Type: T-Slot Nut
- Structural Element Type: Fixing & Connection Element
- Fits Groove Size: 5 mm
- Thread Size: M5
- Length: 12 mm
- Fits Strut Profile: 20 mm
- Product Family: RS Structural System
- Material: Stainless Steel



1809109 T-Slot Nut

RS PRO T-SLOT NUT CONNECTING COMPONENT, STRUT PROFILE 20 MM,

Pack size: **10 x EA**

- Connector Type: T-Slot Nut
- Structural Element Type: Fixing & Connection Element
- Fits Groove Size: 5 mm
- Thread Size: M5
- Length: 18 mm
- Fits Strut Profile: 20 mm
- Product Family: RS Structural System
- Material: Steel



1809111 T-Slot Nut

RS PRO T-SLOT NUT CONNECTING COMPONENT, STRUT PROFILE 20 MM,

Pack size: **10 x EA**

- Connector Type: T-Slot Nut
- Structural Element Type: Fixing & Connection Element
- Fits Groove Size: 5 mm
- Thread Size: M4
- Length: 18 mm
- Fits Strut Profile: 20 mm
- Product Family: RS Structural System
- Material: Steel



1809110 T-Slot Nut

RS PRO T-SLOT NUT CONNECTING COMPONENT, STRUT PROFILE 30 MM,

Pack size: **10 x EA**

- Connector Type: T-Slot Nut
- Structural Element Type: Fixing & Connection Element
- Fits Groove Size: 6 mm
- Thread Size: M4
- Length: 17 mm
- Fits Strut Profile: 30 mm
- Product Family: RS Structural System
- Material: Steel



1809114 T-Slot Nut

RS PRO T-SLOT NUT CONNECTING COMPONENT, STRUT PROFILE 30 MM,

Pack size: **10 x EA**

- Connector Type: T-Slot Nut
- Structural Element Type: Fixing & Connection Element
- Fits Groove Size: 6 mm
- Thread Size: M6
- Length: 16 mm
- Fits Strut Profile: 30 mm
- Product Family: RS Structural System
- Material: Steel



1809124 T-Slot Nut

RS PRO T-SLOT NUT CONNECTING COMPONENT, STRUT PROFILE 30 MM,

Pack size: **10 x EA**

- Connector Type: T-Slot Nut
- Structural Element Type: Fixing & Connection Element
- Fits Groove Size: 6 mm
- Thread Size: M6
- Length: 16 mm
- Fits Strut Profile: 30 mm
- Product Family: RS Structural System
- Material: Steel



1809127 T-Slot Nut

RS PRO T-SLOT NUT CONNECTING COMPONENT, STRUT PROFILE 30 MM,

Pack size: **10 x EA**

- Connector Type: T-Slot Nut
- Structural Element Type: Fixing & Connection Element
- Fits Groove Size: 6 mm
- Thread Size: M6
- Length: 17 mm
- Fits Strut Profile: 30 mm
- Product Family: RS Structural System
- Material: Steel



1809116 T-Slot Nut

RS PRO PIVOT JOINT CONNECTING COMPONENT, STRUT PROFILE 20 MM,

Pack size: **1 x EA**

- Connector Type: Pivot Joint
- Structural Element Type: Connector Bracket & Joint
- Fits Groove Size: 5mm, 6 mm
- Fits Strut Profile: 20 mm
- Product Family: RS Structural System
- Material: Die Cast Aluminium
- Product System: 20



1809135 Pivot Joint

RS PRO PIVOT JOINT CONNECTING COMPONENT, STRUT PROFILE 20 MM,

Pack size: **1 x EA**

- Connector Type: Pivot Joint
- Structural Element Type: Connector Bracket & Joint
- Fits Groove Size: 5mm, 6 mm
- Fits Strut Profile: 20 mm
- Product Family: RS Structural System
- Material: Die Cast Aluminium
- Product System: 20



1809134 Pivot Joint

RS PRO ANGLE BRACKET CONNECTING COMPONENT, STRUT

Pack size: **10 x EA**

- Connector Type: Angle Bracket
- Structural Element Type: Connector Bracket & Joint
- Fits Groove Size: 5 mm
- Length: 18 mm
- Fits Strut Profile: 20 mm
- Product Family: RS Structural System
- Material: Die Cast Aluminium
- Product System: 20



1809136 Angle Bracket

RS PRO ANGLE BRACKET CONNECTING COMPONENT, STRUT

Pack size: **10 x EA**

- Connector Type: Angle Bracket
- Structural Element Type: Connector Bracket & Joint
- Fits Groove Size: 6 mm
- Fits Strut Profile: 20 mm
- Product Family: RS Structural System
- Material: Die Cast Aluminium
- Product System: 20



1809137 Angle Bracket

RS PRO ANGLE BRACKET CONNECTING COMPONENT, STRUT

Pack size: **10 x EA**

- Connector Type: Angle Bracket
- Structural Element Type: Connector Bracket & Joint
- Fits Groove Size: 5 mm
- Thread Size: M5
- Length: 18 mm
- Fits Strut Profile: 20 mm
- Product Family: RS Structural System
- Material: Die Cast Zinc



1809138 Angle Bracket

RS PRO 3-WAY CONNECTOR CONNECTING COMPONENT, STRUT

Pack size: **10 x EA**

- Connector Type: 3-Way Connector
- Structural Element Type: Connector Bracket & Joint
- Fits Groove Size: 5 mm
- Fits Strut Profile: 20 mm
- Product Family: RS Structural System
- Material: Nylon
- Product System: 20



1809140 3-Way

RS PRO CUBE CONNECTOR CONNECTING COMPONENT, STRUT

Pack size: **1 x EA**

- Connector Type: Cube Connector
- Structural Element Type: Connector Bracket & Joint
- Fits Groove Size: 5 mm
- Fits Strut Profile: 20 mm
- Product Family: RS Structural System
- Material: Die Cast Aluminium
- Product System: 20



1809141 Cube Connector

RS PRO T-SLOT NUT CONNECTING COMPONENT, STRUT PROFILE 40 MM,

Pack size: **10 x EA**

- Connector Type: T-Slot Nut
- Structural Element Type: Fixing & Connection Element
- Fits Groove Size: 8 mm
- Thread Size: M8
- Length: 22 mm
- Fits Strut Profile: 40 mm
- Product Family: RS Structural System
- Material: Steel



2247637 T-Slot Nut

STORAGE,STEEL TUBE FITTING,SHORT TEE,1IN

Pack size: **1 x EA**

- Structural Element Type: Round Tube
- Connector Type: T-Connector
- Fits Strut Profile: Type 1
- Fits Tube Diameter: 33.7 mm
- Product Family: RS Handrail System
- Material: Cast Iron
- Product System: 101



2863308 Round Tube

RS PRO T-CONNECTOR CONNECTING COMPONENT, STRUT PROFILE TYPE 2,

Pack size: **1 x EA**

- Connector Type: T-Connector
- Structural Element Type: Connector Bracket & Joint
- Fits Strut Profile: Type 2
- Fits Tube Diameter: 42.4 mm
- Fits Round Tube Size: Type 2
- Product Family: RS Handrail System
- Material: Cast Iron
- Product System: 101



2863314 T-Connector

RS PRO T-CONNECTOR CONNECTING COMPONENT, STRUT PROFILE TYPE 3,

Pack size: **1 x EA**

- Connector Type: T-Connector
- Structural Element Type: Connector Bracket & Joint
- Fits Strut Profile: Type 3
- Fits Tube Diameter: 48.3 mm
- Fits Round Tube Size: Type 3
- Product Family: RS Handrail System
- Material: Cast Iron
- Product System: 101



2863320 T-Connector

RS PRO JOINT CLAMP CONNECTING COMPONENT, STRUT PROFILE TYPE 2,

Pack size: **1 x EA**

- Connector Type: Joint Clamp
- Structural Element Type: Connector Bracket & Joint
- Length: 102 mm
- Fits Strut Profile: Type 2
- Fits Tube Diameter: 42.4 mm
- Fits Round Tube Size: Type 2
- Product Family: RS Handrail System
- Material: Cast Iron



2863358 Joint Clamp

RS PRO JOINT CLAMP CONNECTING COMPONENT, STRUT PROFILE TYPE 3,

Pack size: **1 x EA**

- Connector Type: Joint Clamp
- Structural Element Type: Connector Bracket & Joint
- Length: 100 mm
- Fits Strut Profile: Type 3
- Fits Tube Diameter: 48.3 mm
- Fits Round Tube Size: Type 3
- Product Family: RS Handrail System
- Material: Cast Iron



2863364 Joint Clamp

STORAGE,STEEL TUBE FITTING,ELBOW,90DEG,1IN

Pack size: **1 x EA**

- Structural Element Type: Round Tube
- Connector Type: 2-Way Connector
- Fits Strut Profile: Type 1
- Fits Tube Diameter: 33.7 mm
- Product Family: RS Handrail System
- Material: Cast Iron
- Product System: 125



2863370 Round Tube

RS PRO 2-WAY CONNECTOR CONNECTING COMPONENT, STRUT

Pack size: **1 x EA**

- Connector Type: 2-Way Connector
- Structural Element Type: Connector Bracket & Joint
- Fits Strut Profile: Type 2
- Fits Tube Diameter: 42.4 mm
- Fits Round Tube Size: Type 2
- Product Family: RS Handrail System
- Material: Cast Iron
- Product System: 125



2863386 2-Way Connector

RS PRO 3-WAY CONNECTOR CONNECTING COMPONENT, STRUT

Pack size: **1 x EA**

- Connector Type: 3-Way Connector
- Structural Element Type: Connector Bracket & Joint
- Fits Strut Profile: Type 1
- Fits Tube Diameter: 33.7 mm
- Fits Round Tube Size: Type 1
- Product Family: RS Handrail System
- Material: Cast Iron
- Product System: 128



2863392 3-Way

RS PRO 3-WAY CONNECTOR CONNECTING COMPONENT, STRUT

Pack size: **1 x EA**

- Connector Type: 3-Way Connector
- Structural Element Type: Connector Bracket & Joint
- Fits Strut Profile: Type 2
- Fits Tube Diameter: 42.4 mm
- Fits Round Tube Size: Type 2
- Product Family: RS Handrail System
- Material: Cast Iron
- Product System: 128



2863409 3-Way

RS PRO 3-WAY CONNECTOR CONNECTING COMPONENT, STRUT

Pack size: **1 x EA**

- Connector Type: 3-Way Connector
- Structural Element Type: Connector Bracket & Joint
- Fits Strut Profile: Type 1
- Fits Tube Diameter: 33.7 mm
- Fits Round Tube Size: Type 1
- Product Family: RS Handrail System
- Material: Cast Iron
- Product System: 116



2863421 3-Way

RS PRO 3-WAY CONNECTOR CONNECTING COMPONENT, STRUT

Pack size: **1 x EA**

- Connector Type: 3-Way Connector
- Structural Element Type: Connector Bracket & Joint
- Fits Strut Profile: Type 2
- Fits Tube Diameter: 42.4 mm
- Fits Round Tube Size: Type 2
- Product Family: RS Handrail System
- Material: Cast Iron
- Product System: 116



2863437 3-Way

STORAGE,STEEL TUBE FITTING, LONG TEE, 1IN

Pack size: **1 x EA**

- Structural Element Type: Round Tube
- Connector Type: T-Connector
- Length: 96 mm
- Fits Strut Profile: Type 1
- Fits Tube Diameter: 33.7 mm
- Product Family: RS Handrail System
- Material: Cast Iron
- Product System: 104



2863459 Round Tube

RS PRO T-CONNECTOR CONNECTING COMPONENT, STRUT PROFILE TYPE 2,

Pack size: **1 x EA**

- Connector Type: T-Connector
- Structural Element Type: Connector Bracket & Joint
- Length: 122 mm
- Fits Strut Profile: Type 2
- Fits Tube Diameter: 42.4 mm
- Fits Round Tube Size: Type 2
- Product Family: RS Handrail System
- Material: Cast Iron



2863465 T-Connector

RS PRO 2-WAY CONNECTOR CONNECTING COMPONENT, STRUT

Pack size: **1 x EA**

- Connector Type: 2-Way Connector
- Structural Element Type: Connector Bracket & Joint
- Length: 48 mm
- Fits Strut Profile: Type 1
- Fits Tube Diameter: 33.7 mm
- Fits Round Tube Size: Type 1
- Product Family: RS Handrail System
- Material: Cast Iron



2863487 2-Way Connector

RS PRO 2-WAY CONNECTOR CONNECTING COMPONENT, STRUT

Pack size: **1 x EA**

- Connector Type: 2-Way Connector
- Structural Element Type: Connector Bracket & Joint
- Length: 60 mm
- Fits Strut Profile: Type 2
- Fits Tube Diameter: 42.4 mm
- Fits Round Tube Size: Type 2
- Product Family: RS Handrail System
- Material: Cast Iron



2863500 2-Way Connector

RS PRO SINGLE SWIVEL COMBINATION CONNECTING

Pack size: **1 x EA**

- Connector Type: Single Swivel Combination
- Structural Element Type: Connector Bracket & Joint
- Fits Strut Profile: Type 3
- Fits Tube Diameter: 48.3 mm
- Fits Round Tube Size: Type 3
- Product Family: RS Handrail System
- Material: Cast Iron
- Product System: 173



2863538 Single Swivel

RS PRO ROUND TUBE HANDRAIL BRACKET, STRUT PROFILE TYPE 1,

Pack size: **1 x EA**

- Structural Element Type: Round Tube
- Connector Type: Handrail Bracket
- Fits Strut Profile: Type 1
- Fits Tube Diameter: 33.7 mm
- Product Family: RS Handrail System
- Material: Cast Iron
- Product System: 143



2863689 Round Tube

RS PRO HANDRAIL BRACKET CONNECTING COMPONENT, STRUT

Pack size: **1 x EA**

- Connector Type: Handrail Bracket
- Structural Element Type: Connector Bracket & Joint
- Fits Strut Profile: Type 2
- Fits Tube Diameter: 42.4 mm
- Fits Round Tube Size: Type 2
- Product Family: RS Handrail System
- Material: Cast Iron
- Product System: 143



2863695 Handrail Bracket

RS PRO HANDRAIL BRACKET CONNECTING COMPONENT, STRUT

Pack size: **1 x EA**

- Connector Type: Handrail Bracket
- Structural Element Type: Connector Bracket & Joint
- Fits Strut Profile: Type 3
- Fits Tube Diameter: 48.3 mm
- Fits Round Tube Size: Type 3
- Product Family: RS Handrail System
- Material: Cast Iron
- Product System: 143



2863702 Handrail Bracket

RS PRO SINGLE SWIVEL COMBINATION CONNECTING

Pack size: **1 x EA**

- Connector Type: Single Swivel Combination
- Structural Element Type: Connector Bracket & Joint
- Fits Strut Profile: Type 2
- Fits Tube Diameter: 42.4 mm
- Fits Round Tube Size: Type 2
- Product Family: RS Handrail System
- Material: Cast Iron
- Product System: 173



2863752 Single Swivel

RS PRO 2-WAY CONNECTOR CONNECTING COMPONENT, STRUT

Pack size: **1 x EA**

- Connector Type: 2-Way Connector
- Structural Element Type: Connector Bracket & Joint
- Thread Size: M6
- Fits Strut Profile: Type 3
- Fits Tube Diameter: 48.3 mm
- Fits Round Tube Size: Type 3
- Product Family: RS Handrail System
- Material: Cast Iron



2863954 2-Way Connector

RS PRO 15 TO 60 DEGREE ELBOW CONNECTING COMPONENT, STRUT

Pack size: **1 x EA**

- Connector Type: 15 to 60 Degree Elbow
- Structural Element Type: Connector Bracket & Joint
- Fits Strut Profile: Type 2
- Fits Tube Diameter: 42.4 mm
- Fits Round Tube Size: Type 2
- Product Family: RS Handrail System
- Material: Cast Iron
- Product System: 124



4155980 15 to 60 Degree

RS PRO T-CONNECTOR CONNECTING COMPONENT, STRUT PROFILE TYPE 1,

Pack size: **1 x EA**

- Connector Type: T-Connector
- Structural Element Type: Connector Bracket & Joint
- Fits Strut Profile: Type 1
- Fits Tube Diameter: 33.7 mm
- Fits Round Tube Size: Type 1
- Product Family: RS Handrail System
- Material: Cast Iron
- Product System: 129



4156006 T-Connector

RS PRO ROUND TUBE T-CLAMP, STRUT PROFILE TYPE 2,

Pack size: **1 x EA**

- Structural Element Type: Round Tube
- Connector Type: T-Clamp
- Fits Strut Profile: Type 2
- Fits Tube Diameter: 42.4 mm
- Product Family: RS Handrail System
- Material: Cast Iron
- Product System: 135



4156078 Round Tube

RS PRO T-CLAMP CONNECTING COMPONENT, STRUT PROFILE TYPE 3,

Pack size: **1 x EA**

- Connector Type: T-Clamp
- Structural Element Type: Connector Bracket & Joint
- Fits Strut Profile: Type 3
- Fits Tube Diameter: 48.3 mm
- Fits Round Tube Size: Type 3
- Product Family: RS Handrail System
- Material: Cast Iron
- Product System: 135



4156084 T-Clamp

RS PRO T-CONNECTOR CONNECTING COMPONENT, STRUT PROFILE TYPE 3,

Pack size: **1 x EA**

- Connector Type: T-Connector
- Structural Element Type: Connector Bracket & Joint
- Fits Strut Profile: Type 3
- Fits Tube Diameter: 48.3 mm
- Fits Round Tube Size: Type 3
- Product Family: RS Handrail System
- Material: Cast Iron
- Product System: 148



4156214 T-Connector

RS PRO 90° CONNECTOR CONNECTING COMPONENT, STRUT

Pack size: **1 x EA**

- Connector Type: 90° Connector
- Structural Element Type: Connector Bracket & Joint
- Thread Size: M6, M8
- Fits Strut Profile: Type 1
- Fits Tube Diameter: 33.7 mm
- Fits Round Tube Size: Type 1
- Product Family: RS Handrail System
- Material: Cast Iron



4156309 90° Connector

RS PRO 90° CONNECTOR CONNECTING COMPONENT, STRUT

Pack size: **1 x EA**

- Connector Type: 90° Connector
- Structural Element Type: Connector Bracket & Joint
- Fits Strut Profile: Type 3
- Fits Tube Diameter: 48.3 mm
- Fits Round Tube Size: Type 3
- Product Family: RS Handrail System
- Material: Cast Iron
- Product System: 161



4156337 90° Connector

RS PRO T-CLAMP CONNECTING COMPONENT, STRUT PROFILE TYPE 1,

Pack size: **1 x EA**

- Connector Type: T-Clamp
- Structural Element Type: Connector Bracket & Joint
- Thread Size: M6
- Fits Strut Profile: Type 1
- Fits Tube Diameter: 33.7 mm
- Fits Round Tube Size: Type 1
- Product Family: RS Handrail System
- Material: Cast Iron



4157021 T-Clamp

RS PRO 4-WAY CONNECTOR CONNECTING COMPONENT, STRUT

Pack size: **1 x EA**

- Connector Type: 4-Way Connector
- Structural Element Type: Connector Bracket & Joint
- Fits Strut Profile: Type 1
- Fits Tube Diameter: 33.7 mm
- Fits Round Tube Size: Type 1
- Product Family: RS Handrail System
- Material: Cast Iron
- Product System: 158



4244614 4-Way

RS PRO T-CONNECTOR CONNECTING COMPONENT, STRUT PROFILE TYPE 1,

Pack size: **1 x EA**

- Connector Type: T-Connector
- Structural Element Type: Connector Bracket & Joint
- Fits Strut Profile: Type 1
- Fits Tube Diameter: 33.7 mm
- Fits Round Tube Size: Type 1
- Product Family: RS Handrail System
- Material: Cast Iron
- Product System: 176



4244658 T-Connector

RS PRO CONNECTING CLAMP CONNECTING COMPONENT

Pack size: **1 x EA**

- Connector Type: Connecting Clamp
- Structural Element Type: Fixing & Connection Element
- Thread Size: M5
- Fits Tube Diameter: 8 mm
- Product Family: Elessa Connecting Clamps
- Material: Aluminium
- Product System: MSM



7865980 Connecting

RS PRO CONNECTING CLAMP CONNECTING COMPONENT

Pack size: **1 x EA**

- Connector Type: Connecting Clamp
- Structural Element Type: Connector Bracket & Joint
- Thread Size: M4
- Fits Tube Diameter: 8 mm
- Product Family: Elessa Connecting Clamps
- Material: Aluminium
- Product System: MSM



7865986 Connecting

RS PRO CONNECTING CLAMP CONNECTING COMPONENT

Pack size: **1 x EA**

- Connector Type: Connecting Clamp
- Structural Element Type: Fixing & Connection Element
- Thread Size: M4
- Fits Tube Diameter: 8 mm
- Product Family: Elessa Connecting Clamps
- Material: Aluminium
- Product System: MSM



7865992 Connecting

RS PRO BASE CLAMP CONNECTING COMPONENT

Pack size: **1 x EA**

- Connector Type: Base Clamp
- Structural Element Type: Connector Bracket & Joint
- Thread Size: M6
- Fits Tube Diameter: 20 mm
- Fits Square Tube Profile: 16 mm
- Product Family: Elessa Connecting Clamps
- Material: Aluminium
- Product System: MSM



7866166 Base Clamp

RS PRO CONNECTING CLAMP CONNECTING COMPONENT

Pack size: **1 x EA**

- Connector Type: Connecting Clamp
- Structural Element Type: Connector Bracket & Joint
- Thread Size: M6
- Fits Tube Diameter: 20 mm
- Fits Square Tube Profile: 16 mm
- Product Family: Elessa Connecting Clamps
- Material: Aluminium
- Product System: MSM



7866169 Connecting

RS PRO CONNECTING CLAMP CONNECTING COMPONENT

Pack size: **1 x EA**

- Connector Type: Connecting Clamp
- Structural Element Type: Fixing & Connection Element
- Thread Size: M6
- Fits Tube Diameter: 20 mm
- Fits Square Tube Profile: 16 mm
- Product Family: Elessa Connecting Clamps
- Material: Aluminium
- Product System: MSM



7866175 Connecting

RS PRO CONNECTING COMPONENT

Pack size: **1 x EA**

- Structural Element Type: Connecting Clamp
- Thread Size: M5
- Product Family: Elessa Connecting Clamps
- Material: Stainless Steel
- Product System: MSM



7866210 Connecting

RS PRO, BLACK PP T-SLOT COVERS, 5MM GROOVE SIZE, 2M LENGTH

Pack size: **10 x EA**

- Product Family: RS Structural System
- Fits Groove Size: 5 mm
- Fits Strut Profile: 20 mm
- Length: 2 m
- Material: PP
- Colour: Black



1809131 RS Structural

RS PRO, DOOR HINGE

Pack size: **2 x EA**

- Component Type: Plastic Hinge
- Product Family: RS Structural System
- Fits Strut Profile: 20 mm



1809098 Plastic Hinge

RS PRO ALUMINIUM ALLOY COVER STRIP, 8MM GROOVE SIZE, 2M

Pack size: **10 x EA**

- Product Family: RS Structural System
- Fits Groove Size: 8 mm
- Fits Strut Profile: 40 mm
- Length: 2 m
- Material: Aluminium Alloy
- Series: Profile 8



8508511 RS Structural

RS PRO, DOOR HINGE, 20 5MM SLOT

Pack size: **2 x EA**

- Component Type: Plastic Hinge
- Product Family: RS Structural System
- Product System: 20
- Fits Strut Profile: 20 mm
- Fits Groove Size: 5 mm



1809099 Plastic Hinge

RS PRO, DOOR HINGE, 20 6MM SLOT

Pack size: **2 x EA**

- Component Type: Plastic Hinge
- Product Family: RS Structural System
- Product System: 20
- Fits Strut Profile: 20 mm
- Fits Groove Size: 6 mm



1809100 Plastic Hinge

RS PRO 5MM SLOT

Pack size: **1 x KT**

- Fits Strut Profile: 20 mm
- Fits Groove Size: 5 mm



1809101 20 mm

BPS.30 BALL SHAPED DOOR LOCK

Pack size: **1 x EA**

- Component Type: Ball Latch Kit
- Product Family: Elessa
- Product System: BPS
- Fits Strut Profile: Minimum of 15 mm



7865974 Ball Latch Kit

RS PRO CAST IRON 131 WALL FLANGE, 42MM ROUND TUBE, TYPE 2

Pack size: **1 x EA**

- Component Type: Wall Flange
- Structural Element Type: Round Tube
- Product Family: RS Handrail System
- Product System: 131
- Fits Round Tube Size: Type 2
- Fits Tube Diameter: 42 mm
- Fits Strut Profile: Type 2
- Material: Cast Iron



2863594 Wall Flange

RS PRO CAST IRON 131 WALL FLANGE, 48MM ROUND TUBE, TYPE 3

Pack size: **1 x EA**

- Component Type: Wall Flange
- Structural Element Type: Round Tube
- Product Family: RS Handrail System
- Product System: 131
- Fits Round Tube Size: Type 3
- Fits Tube Diameter: 48 mm
- Fits Strut Profile: Type 3
- Material: Cast Iron



2863601 Wall Flange

RS PRO CAST IRON 132 BASE FLANGE, 42MM ROUND TUBE, TYPE 2

Pack size: **1 x EA**

- Component Type: Base Flange
- Structural Element Type: Round Tube
- Product Family: RS Handrail System
- Product System: 132
- Fits Round Tube Size: Type 2
- Fits Tube Diameter: 42 mm
- Fits Strut Profile: Type 2
- Material: Cast Iron



2863639 Base Flange

STORAGE,STEEL TUBE FITTING,RAIL BASE FLANGE,1IN

Pack size: **1 x EA**

- Component Type: Base Flange
- Structural Element Type: Round Tube
- Product Family: RS Handrail System
- Product System: 132
- Fits Round Tube Size: Type 1
- Fits Tube Diameter: 33.7 mm
- Fits Strut Profile: Type 1
- Material: Cast Iron



2863623 Base Flange

RS PRO CAST IRON 132 BASE FLANGE, 48MM ROUND TUBE, TYPE 3

Pack size: **1 x EA**

- Component Type: Base Flange
- Structural Element Type: Round Tube
- Product Family: RS Handrail System
- Product System: 132
- Fits Round Tube Size: Type 3
- Fits Tube Diameter: 48 mm
- Fits Strut Profile: Type 3
- Material: Cast Iron



2863645 Base Flange

CAPS,END,SQUARE TUBE SYSTEM,BLACK PLASTIC

Pack size: **12 x EA**

- Structural Element Type: Square End Cap
- Fits Square Tube Profile: 25 mm
- Fits Strut Profile: 25 mm
- Material: Plastic
- Colour: Black
- Product Family: RS Square Tube System



621764 Square End Cap

RS PRO BLACK END CAP, GROOVE 5MM

Pack size: **10 x EA**

- Structural Element Type: End Cap
- Fits Tube Diameter: 4.5 mm
- Fits Groove Size: 5 mm
- Colour: Black
- Product Family: RS Structural System
- Product System: 20



1880351 End Cap

STORAGE,STEEL TUBE FITTING,BASE FLANGE,1IN

Pack size: **1 x EA**

- Component Type: Wall Flange
- Structural Element Type: Round Tube
- Product Family: RS Handrail System
- Product System: 131
- Fits Round Tube Size: Type 1
- Fits Tube Diameter: 33.7 mm
- Fits Strut Profile: Type 1
- Material: Cast Iron



2863588 Wall Flange

BLACK PROFILE END CAP 20 X 40

Pack size: **10 x EA**

- Structural Element Type: End Cap
- Fits Tube Diameter: 4.5 mm
- Fits Strut Profile: 20 x 40 mm
- Fits Groove Size: 5 mm
- Colour: Black
- Product Family: RS Structural System
- Product System: 20



1880353 End Cap

INSERT,ROUND TUBE,IMPERIAL,1 1/2IN

Pack size: **100 x EA**

- Structural Element Type: Round Tube Plug
- Fits Tube Diameter: 38.1 mm
- Colour: Black
- Product Family: RS



2372199 Round Tube Plug

STORAGE,STEEL TUBE FITTING,STOP END,PLASTIC,1IN

Pack size: **10 x EA**

- Structural Element Type: Round End Cap
- Fits Tube Diameter: 33.7 mm
- Fits Strut Profile: Type 1
- Material: Plastic
- Product Family: RS Handrail System
- Product System: 133



2863718 Round End Cap

STORAGE,STEEL TUBE FITTING,STOP END PLASTIC,1 1/4IN

Pack size: **10 x EA**

- Structural Element Type: Round End Cap
- Fits Tube Diameter: 42.4 mm
- Fits Strut Profile: Type 2
- Material: Plastic
- Product Family: RS Handrail System
- Product System: 133



2863724 Round End Cap

RS PRO PLASTIC ROUND END CAP TYPE 3 STRUT PROFILE

Pack size: **10 x EA**

- Structural Element Type: Round End Cap
- Fits Tube Diameter: 48.3 mm
- Fits Strut Profile: Type 3
- Material: Plastic
- Product Family: RS Handrail System
- Product System: 133



2863730 Round End Cap

RS PRO CAST IRON ROUND TUBE GATE EYE, 48.3MM OD

Pack size: **1 x EA**

- Component Type: Gate Eye
- Structural Element Type: Round Tube
- Product Family: RS Handrail System
- Product System: 138
- Fits Strut Profile: Type 3
- Fits Round Tube Size: Type 3
- Fits Tube Diameter: 48.3 mm
- Material: Cast Iron



4156129 Gate Eye

GROMMET FOR MINI IN-LINE CONNECTOR PK 25

Pack size: **25 x EA**

- Grommet Type: Cable Grommet
- Minimum Cable Diameter: 1 mm
- Maximum Cable Diameter: 3 mm
- Material: Rubber
- Colour: Black



6667365 Cable Grommet

PROCESS HEATER,MAT,1.25W,50X25MM,12VDC

Pack size: **1 x EA**

- Mat Shape: Rectangle
- Power Rating: 1.25 W
- Rectangular Mat Size: 25 x 50 mm
- Peak Temperature: +300 °C
- Supply Voltage: 12 V dc
- Dimensions: 25 x 50 mm



245499 Rectangle

RS PRO SILICONE HEATER MAT, 5 W, 50 X 100MM, 12 V

Pack size: **1 x EA**

- Mat Shape: Rectangle
- Power Rating: 5 W
- Rectangular Mat Size: 50 x 100 mm
- Peak Temperature: +300 °C
- Supply Voltage: 12 V
- Dimensions: 50 x 100 mm



245528 Rectangle

PROCESS HEATER,MAT,7.5W,100X75MM,12VDC

Pack size: **1 x EA**

- Mat Shape: Rectangle
- Power Rating: 7.5 W
- Rectangular Mat Size: 75 x 100 mm
- Peak Temperature: +300 °C
- Supply Voltage: 12 V dc
- Dimensions: 75 x 100 mm



245534 Rectangle

RS PRO SILICONE HEATER MAT, 2.5 W, 50 X 50MM, 12 V DC

Pack size: **1 x EA**

- Mat Shape: Rectangle
- Power Rating: 2.5 W
- Rectangular Mat Size: 50 x 50 mm
- Peak Temperature: +180 °C
- Supply Voltage: 12 V dc
- Dimensions: 50 x 50 mm



245506 Rectangle

RS PRO SILICONE HEATER MAT, 3.75 W, 50 X 75MM, 12 V

Pack size: **1 x EA**

- Mat Shape: Rectangle
- Power Rating: 3.75 W
- Rectangular Mat Size: 50 x 75 mm
- Peak Temperature: +300 °C
- Supply Voltage: 12 V
- Dimensions: 50 x 75 mm



245512 Rectangle

RS PRO SILICONE HEATER MAT, 10 W, 100 X 100MM, 12 V DC

Pack size: **1 x EA**

- Mat Shape: Square
- Power Rating: 10 W
- Rectangular Mat Size: 100 x 100 mm
- Peak Temperature: +300 °C
- Supply Voltage: 12 V dc
- Dimensions: 100 x 100 mm



245540 Square

PROCESS HEATER,MAT,750W,50X150MM,12VDC

Pack size: **1 x EA**

- Mat Shape: Rectangle
- Power Rating: 7.5 W
- Rectangular Mat Size: 50 x 150 mm
- Peak Temperature: +300 °C
- Supply Voltage: 12 V dc
- Dimensions: 50 x 150 mm



245556 Rectangle

PROCESS HEATER,MAT,15W,200X75MM,12VDC

Pack size: **1 x EA**

- Mat Shape: Rectangle
- Power Rating: 15 W
- Rectangular Mat Size: 75 x 200 mm
- Peak Temperature: +300 °C
- Supply Voltage: 12 V dc
- Dimensions: 75 x 200 mm



245562 Rectangle

RS PRO SILICONE HEATER MAT, 80 W, 200 X 400MM, 12 V DC

Pack size: **1 x EA**

- Mat Shape: Rectangle
- Power Rating: 80 W
- Rectangular Mat Size: 200 x 400 mm
- Peak Temperature: +300 °C
- Supply Voltage: 12 V dc
- Dimensions: 200 x 400 mm



245578 Rectangle

PROCESS HEATER,MAT,2W,50MM DIA,12VDC

Pack size: **1 x EA**

- Mat Shape: Circle
- Power Rating: 2 W
- Circular Mat Diameter: 50 mm
- Peak Temperature: +300 °C
- Supply Voltage: 12 V dc
- Dimensions: 50 mm



245584 Circle

RS PRO SILICONE HEATER MAT, 4 W, 12 V DC

Pack size: **1 x EA**

- Mat Shape: Circle
- Power Rating: 4 W
- Circular Mat Diameter: 75 mm
- Peak Temperature: +300 °C
- Supply Voltage: 12 V dc
- Dimensions: 75 mm



245590 Circle

PROCESS HEATER,MAT,8W,100MM DIA,12VDC

Pack size: **1 x EA**

- Mat Shape: Circle
- Power Rating: 8 W
- Circular Mat Diameter: 100 mm
- Peak Temperature: +300 °C
- Supply Voltage: 12 V dc
- Dimensions: 100 mm



245607 Circle

PROCESS HEATER,MAT,15W,100X150MM,12V

Pack size: **1 x EA**

- Mat Shape: Rectangle
- Power Rating: 15 W
- Rectangular Mat Size: 100 x 150 mm
- Peak Temperature: +300 °C
- Supply Voltage: 12 V dc
- Dimensions: 100 x 150 mm



731350 Rectangle

PROCESS HEATER,MAT,30W,150X200MM,12V

Pack size: **1 x EA**

- Mat Shape: Rectangle
- Power Rating: 30 W
- Rectangular Mat Size: 150 x 200 mm
- Peak Temperature: +300 °C
- Supply Voltage: 12 V dc
- Dimensions: 150 x 200 mm



731366 Rectangle

PROCESS HEATER,MAT,60W,200X300MM,12V

Pack size: **1 x EA**

- Mat Shape: Rectangle
- Power Rating: 60 W
- Rectangular Mat Size: 200 x 300 mm
- Peak Temperature: +300 °C
- Supply Voltage: 12 V dc
- Dimensions: 200 x 300 mm



731372 Rectangle

PROCESS HEATER, MAT, MULTI ELEMENT, 150W, 50W, 38W, 25W, 18.5

Pack size: **1 x EA**

- Mat Shape: Rectangle
- Power Rating: 150 W
- Rectangular Mat Size: 150 x 300 mm
- Peak Temperature: +300 °C
- Supply Voltage: 30 V dc
- Dimensions: 150 x 300 mm




731388 Rectangle

RS PRO SILICONE HEATER MAT, 100 W, 100 X 150MM, 240 V AC

Pack size: **1 x EA**

- Mat Shape: Rectangle
- Power Rating: 100 W
- Rectangular Mat Size: 100 x 150 mm
- Peak Temperature: +180 °C
- Supply Voltage: 240 V ac
- Dimensions: 100 x 150 mm



1065407 Rectangle

RS PRO SILICONE HEATER MAT, 400 W, 200 X 300MM, 240 V AC

Pack size: **1 x EA**

- Mat Shape: Rectangle
- Power Rating: 400 W
- Rectangular Mat Size: 200 x 300 mm
- Peak Temperature: +180 °C
- Supply Voltage: 240 V ac
- Dimensions: 200 x 300 mm



1065409 Rectangle

RS PRO SILICONE HEATER MAT, 35 W, 110 V AC

Pack size: **1 x EA**

- Mat Shape: Cylindrical
- Power Rating: 35 W
- Circular Mat Diameter: 28 mm
- Peak Temperature: +200 °C
- Supply Voltage: 110 V ac
- Dimensions: 28 mm



1065412 Cylindrical

RS PRO SILICONE HEATER MAT, 69 W, 110 V AC

Pack size: **1 x EA**

- Mat Shape: Cylindrical
- Power Rating: 69 W
- Circular Mat Diameter: 28 mm
- Peak Temperature: +200 °C
- Supply Voltage: 110 V ac
- Dimensions: 28 mm



1065413 Cylindrical

RS PRO SILICONE HEATER MAT, 52 W, 240 V AC

Pack size: **1 x EA**

- Mat Shape: Cylindrical
- Power Rating: 52 W
- Circular Mat Diameter: 42 mm
- Peak Temperature: +200 °C
- Supply Voltage: 240 V ac
- Dimensions: 42 mm



1065414 Cylindrical

RS PRO SILICONE HEATER MAT, 105 W, 240 V AC

Pack size: **1 x EA**

- Mat Shape: Cylindrical
- Power Rating: 105 W
- Circular Mat Diameter: 42 mm
- Peak Temperature: +200 °C
- Supply Voltage: 240 V ac
- Dimensions: 42 mm



1065415 Cylindrical

RS PRO SILICONE HEATER MAT, 69 W, 240 V AC

Pack size: **1 x EA**

- Mat Shape: Cylindrical
- Power Rating: 69 W
- Circular Mat Diameter: 55 mm
- Peak Temperature: +200 °C
- Supply Voltage: 240 V ac
- Dimensions: 55 mm



1065417 Cylindrical

RS PRO SILICONE HEATER MAT, 105 W, 240 V AC

Pack size: **1 x EA**

- Mat Shape: Cylindrical
- Power Rating: 105 W
- Circular Mat Diameter: 83 mm
- Peak Temperature: +200 °C
- Supply Voltage: 240 V ac
- Dimensions: 83 mm



1065420 Cylindrical

RS PRO SILICONE HEATER MAT, 414 W, 240 V AC

Pack size: **1 x EA**

- Mat Shape: Cylindrical
- Power Rating: 414 W
- Circular Mat Diameter: 115 mm
- Peak Temperature: +200 °C
- Supply Voltage: 240 V ac
- Dimensions: 115 mm



1065425 Cylindrical

RS PRO SILICONE HEATER MAT, 176 W, 200 X 200MM, 240 V AC

Pack size: **1 x EA**

- Mat Shape: Square
- Power Rating: 176 W
- Rectangular Mat Size: 200 x 200 mm
- Peak Temperature: +180 °C
- Supply Voltage: 240 V ac
- Dimensions: 200 x 200 mm



1065427 Square

RS PRO SILICONE HEATER MAT, 275 W, 250 X 250MM, 240 V AC

Pack size: **1 x EA**

- Mat Shape: Square
- Power Rating: 275 W
- Rectangular Mat Size: 250 x 250 mm
- Peak Temperature: +180 °C
- Supply Voltage: 240 V ac
- Dimensions: 250 x 250 mm



1065428 Square

RS PRO SILICONE HEATER MAT, 100 W, 50 X 254MM, 120 V AC

Pack size: **1 x EA**

- Mat Shape: Rectangle
- Power Rating: 100 W
- Rectangular Mat Size: 50 x 254 mm
- Peak Temperature: +180 °C
- Supply Voltage: 120 V ac
- Dimensions: 2 x 10 in



1812055 Rectangle

RS PRO SILICONE HEATER MAT, 180 W, 152 X 305MM, 120 V AC

Pack size: **1 x EA**

- Mat Shape: Rectangle
- Power Rating: 180 W
- Rectangular Mat Size: 152 x 305 mm
- Peak Temperature: +180 °C
- Supply Voltage: 120 V ac
- Dimensions: 6 x 12 in



1812057 Rectangle

RS PRO SILICONE HEATER MAT, 60 W, 50 X 152MM, 12 V DC

Pack size: **1 x EA**

- Mat Shape: Rectangle
- Power Rating: 60 W
- Rectangular Mat Size: 50 x 152 mm
- Peak Temperature: +180 °C
- Supply Voltage: 12 V dc
- Dimensions: 2 x 6 in



1812061 Rectangle

SILICONE HEATER MAT 2" X 8" 12V 80W 20"

Pack size: **1 x EA**

- Mat Shape: Rectangle
- Power Rating: 80 W
- Rectangular Mat Size: 50 x 203 mm
- Peak Temperature: +180 °C
- Supply Voltage: 12 V dc
- Dimensions: 2 x 8 in



1812063 Rectangle

RS PRO SILICONE HEATER MAT, 250 W, 127 X 254MM, 230 V AC

Pack size: **1 x EA**

- Mat Shape: Rectangle
- Power Rating: 250 W
- Rectangular Mat Size: 127 x 254 mm
- Peak Temperature: +180 °C
- Supply Voltage: 230 V ac
- Dimensions: 5 x 10 in



1812064 Rectangle

SILICONE HEATER MAT 4" X 8" 230V 160W 20

Pack size: **1 x EA**

- Mat Shape: Rectangle
- Power Rating: 160 W
- Rectangular Mat Size: 102 x 203 mm
- Peak Temperature: +180 °C
- Supply Voltage: 230 V ac
- Dimensions: 4 x 8 in



1812065 Rectangle

RS PRO SILICONE HEATER MAT, 500 W, 254 X 254MM, 230 V AC

Pack size: **1 x EA**

- Mat Shape: Rectangle
- Power Rating: 500 W
- Rectangular Mat Size: 254 x 254 mm
- Peak Temperature: +180 °C
- Supply Voltage: 230 V ac
- Dimensions: 10 x 10 in



1812066 Rectangle

RS PRO SILICONE HEATER MAT, 320 W, 203 X 203MM, 230 V AC

Pack size: **1 x EA**

- Mat Shape: Rectangle
- Power Rating: 320 W
- Rectangular Mat Size: 203 x 203 mm
- Peak Temperature: +180 °C
- Supply Voltage: 230 V ac
- Dimensions: 8 x 8 in



1812067 Rectangle

RS PRO SILICONE HEATER MAT, 500 W, 127 X 508MM, 230 V AC

Pack size: **1 x EA**

- Mat Shape: Rectangle
- Power Rating: 500 W
- Rectangular Mat Size: 127 x 508 mm
- Peak Temperature: +180 °C
- Supply Voltage: 230 V ac
- Dimensions: 5 x 20 in



1812068 Rectangle

RS PRO MICA HEATING PAD, 100 W, 230 V

Pack size: **1 x EA**

- Power Rating: 100 W
- Peak Temperature: +260 °C
- Supply Voltage: 230 V
- Dimensions: 60 x 60 mm



7904827 100 W

RS PRO MICA HEATING PAD, 300 W, 230 V

Pack size: **1 x EA**

- Power Rating: 300 W
- Peak Temperature: +260 °C
- Supply Voltage: 230 V
- Dimensions: 200 x 100 mm




7904833 300 W

RS PRO MICA HEATING PAD, 220 W, 230 V

Pack size: **1 x EA**

- Power Rating: 220 W
- Peak Temperature: +260 °C
- Supply Voltage: 230 V
- Dimensions: 70 x 75 mm



7904836 220 W

RS PRO MICA HEATING PAD, 300 W, 230 V

Pack size: **1 x EA**

- Power Rating: 300 W
- Peak Temperature: +260 °C
- Supply Voltage: 230 V
- Dimensions: 190 x 320 mm



7904839 300 W

RS PRO MICA HEATING PAD, 80 W, 230 V

Pack size: **1 x EA**

- Power Rating: 80 W
- Peak Temperature: +260 °C
- Supply Voltage: 230 V
- Dimensions: 50 x 50 mm



7904842 80 W

RS PRO HEATER MAT, 1.25 W, 25 X 50MM, 12 V

Pack size: **1 x EA**

- Mat Shape: Rectangle
- Power Rating: 1.25 W
- Rectangular Mat Size: 25 x 50 mm
- Supply Voltage: 12 V
- Dimensions: 25 x 50 x 0.2 mm
- Maximum Operating Temperature: +200 °C
- Thickness: 0.2 mm




7983741 Rectangle

RS PRO HEATER MAT, 2 W, 25 X 75MM, 12 V

Pack size: **1 x EA**

- Mat Shape: Rectangle
- Power Rating: 2 W
- Rectangular Mat Size: 25 x 75 mm
- Supply Voltage: 12 V
- Dimensions: 25 x 75 x 0.2 mm
- Maximum Operating Temperature: +200 °C
- Thickness: 0.2 mm



7983750 Rectangle

RS PRO HEATER MAT, 4 W, 25 X 100MM, 12 V

Pack size: **1 x EA**

- Power Rating: 4 W
- Rectangular Mat Size: 25 x 100 mm
- Supply Voltage: 12 V
- Dimensions: 25 x 100 x 0.2 mm
- Maximum Operating Temperature: +200 °C
- Thickness: 0.2 mm




7983753 4 W

RS PRO HEATER MAT, 2.5 W, 50 X 50MM, 12 V

Pack size: **1 x EA**

- Power Rating: 2.5 W
- Rectangular Mat Size: 50 x 50 mm
- Supply Voltage: 12 V
- Dimensions: 50 x 50 x 0.2 mm
- Maximum Operating Temperature: +200 °C
- Thickness: 0.2 mm




7983757 2.5 W

RS PRO HEATER MAT, 7.5 W, 75 X 100MM, 12 V

Pack size: **1 x EA**

- Power Rating: 7.5 W
- Rectangular Mat Size: 75 x 100 mm
- Supply Voltage: 12 V
- Dimensions: 75 x 100 x 0.2 mm
- Maximum Operating Temperature: +200 °C
- Thickness: 0.2 mm



7983763 7.5 W

RS PRO HEATER MAT, 2 W, 12 V

Pack size: **1 x EA**

- Power Rating: 2 W
- Circular Mat Diameter: 50 x 0.2 mm
- Supply Voltage: 12 V
- Dimensions: 50 x 0.2 mm
- Thickness: 0.2 mm
- Maximum Operating Temperature: 200 °C



7983772 2 W

HEATING ELEMENT, 1 KW, 230 V AC

Pack size: **1 x EA**

- Element Type: Drum Heater - Silicone
- Power Rating: 1 kW
- Supply Voltage: 230 V ac



1799541 Drum Heater -

HEATING ELEMENT, 1 KW

Pack size: **1 x EA**

- Element Type: Drum Heater - Silicone
- Power Rating: 1 kW



1799543 Drum Heater -

HEATING ELEMENT, 1.5 KW, 230 V AC

Pack size: **1 x EA**

- Element Type: Drum Heater - Silicone
- Power Rating: 1.5 kW
- Supply Voltage: 230 V ac



1799545 Drum Heater -

HEATING ELEMENT, 1.8 KW, 230 V AC

Pack size: **1 x EA**

- Element Type: Drum Heater - Silicone
- Power Rating: 1.8 kW
- Supply Voltage: 230 V ac



1799549 Drum Heater -

HEATING ELEMENT, 450 W, 230 V AC

Pack size: **1 x EA**

- Element Type: Drum Heater - Silicone
- Power Rating: 450 W
- Supply Voltage: 230 V ac



1799550 Drum Heater -

HEATING ELEMENT, 1.2 KW, 230 V AC

Pack size: **1 x EA**

- Element Type: Drum Heater - Silicone
- Power Rating: 1.2 kW
- Supply Voltage: 230 V ac



1799551 Drum Heater -

REFLECTOR,CERAMIC HEATER,60X245MM

Pack size: **1 x EA**

- Length: 255 mm
- Width: 92 mm
- Thickness: 60 mm
- Heating Element Form: Reflector Bracket
- Dimensions: 255 x 92 x 60 mm



2462501 255 mm

REFLECTOR,CERAMIC,HEATER,60X122MM

Pack size: **1 x EA**

- Length: 160 mm
- Width: 92 mm
- Thickness: 32 mm
- Heating Element Form: Reflector Bracket
- Dimensions: 160 x 92 x 32 mm



2462517 160 mm

MICA SEALED NOZZLE HEATER 150W 240V

Pack size: **1 x EA**

- Element Type: Band Heater
- Power Rating: 150 W
- Supply Voltage: 240 V
- Width: 30 mm
- Diameter: 35 mm
- Dimensions: 35 (Dia.) x 30 mm



7904855 Band Heater

MICA SEALED NOZZLE HEATER 225W 230V

Pack size: **1 x EA**

- Element Type: Band Heater
- Power Rating: 225 W
- Supply Voltage: 240 V
- Width: 25 mm
- Diameter: 60 mm
- Dimensions: 60 (Dia.) x 25 mm



7904858 Band Heater

MICA SEALED NOZZLE HEATER 200W 230V

Pack size: **1 x EA**

- Element Type: Band Heater
- Power Rating: 200 W
- Supply Voltage: 240 V
- Width: 32 mm
- Diameter: 42 mm
- Dimensions: 42 (Dia.) x 32 mm



7904864 Band Heater

MICA SEALED NOZZLE HEATER 150W 240V

Pack size: **1 x EA**

- Element Type: Band Heater
- Power Rating: 150 W
- Supply Voltage: 230 V
- Width: 1.5 in
- Diameter: 25 mm
- Dimensions: 1 (Dia.) x 1.5 mm




7904867 Band Heater

HEATING ELEMENT, 3.75 W, 12 V

Pack size: **1 x EA**

- Element Type: Heater Mat
- Power Rating: 3.75 W
- Supply Voltage: 12 V



7983766 Heater Mat

KAPTON HEATER MAT, 50X100MM, 12V, 5W

Pack size: **1 x EA**

- Element Type: Heater Mat
- Power Rating: 5 W
- Supply Voltage: 12 V



7983769 Heater Mat

HEATING ELEMENT, 75MM, 175 W, 220 V AC

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 175 W
- Supply Voltage: 220 V ac
- Length: 75 mm
- Diameter: 12.5 mm



8606732 Cartridge Heater

CARTRIDGE HEATER, 10MM X 70MM, 250W

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 250 W
- Supply Voltage: 220 V ac
- Length: 70 mm
- Diameter: 10 mm



8606741 Cartridge Heater

CARTRIDGE HEATER, 10MM X 75MM, 125W

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 125 W
- Supply Voltage: 220 V ac
- Length: 75 mm
- Diameter: 10 mm



8606744 Cartridge Heater

HEATING ELEMENT, 90MM, 150 W, 220 V AC

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 150 W
- Supply Voltage: 220 V ac
- Length: 90 mm
- Diameter: 10 mm



8606748 Cartridge Heater

HEATING ELEMENT, 2IN, 120 W, 120 V AC

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 120 W
- Supply Voltage: 120 V ac
- Length: 2 in
- Diameter: 1/2 in



8606750 Cartridge Heater

HEATING ELEMENT, 90MM, 300 W, 220 V AC

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 300 W
- Supply Voltage: 220 V ac
- Length: 90 mm
- Diameter: 10 mm



8606757 Cartridge Heater

HEATING ELEMENT, 3IN, 200 W, 220 V AC

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 200 W
- Supply Voltage: 220 V ac
- Length: 3 in
- Diameter: 1/2 in



8606760 Cartridge Heater

HEATING ELEMENT, 2IN, 270 W, 220 V AC

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 270 W
- Supply Voltage: 220 V ac
- Length: 2 in
- Diameter: 1/2 in



8606763 Cartridge Heater

HEATING ELEMENT, 3IN, 535 W, 220 V AC

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 535 W
- Supply Voltage: 220 V ac
- Length: 3 in
- Diameter: 1/2 in



8606766 Cartridge Heater

HEATING ELEMENT, 4IN, 275 W, 220 V AC

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 275 W
- Supply Voltage: 220 V ac
- Length: 4 in
- Diameter: 1/2 in



8606776 Cartridge Heater

HEATING ELEMENT, 3IN, 335 W, 220 V AC

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 335 W
- Supply Voltage: 220 V ac
- Length: 3 in
- Diameter: 1/2 in



8606772 Cartridge Heater

HEATING ELEMENT, 3IN, 200 W, 120 V AC

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 200 W
- Supply Voltage: 120 V ac
- Length: 3 in
- Diameter: 1/2 in



8606779 Cartridge Heater

HEATING ELEMENT, 4IN, 275 W, 220 V AC

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 275 W
- Supply Voltage: 220 V ac
- Length: 4 in
- Diameter: 1/2 in



8606785 Cartridge Heater

HEATING ELEMENT, 50MM, 200 W, 220 V AC

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 200 W
- Supply Voltage: 220 V ac
- Length: 50 mm
- Diameter: 13 mm



8606794 Cartridge Heater

HEATING ELEMENT, 8IN, 650 W, 220 V AC

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 650 W
- Supply Voltage: 220 V ac
- Length: 8 in
- Diameter: 1/2 in



8606801 Cartridge Heater

HEATING ELEMENT, 1.5IN, 20 W, 120 V AC

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 20 W
- Supply Voltage: 120 V ac
- Length: 1.5 in
- Diameter: 1/4 in



8606805 Cartridge Heater

HEATING ELEMENT, 6IN, 425 W, 220 V AC

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 425 W
- Supply Voltage: 220 V ac
- Length: 6 in
- Diameter: 1/2 in



8606808 Cartridge Heater

HEATING ELEMENT, 3IN, 100 W, 220 V AC

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 100 W
- Supply Voltage: 220 V ac
- Length: 3 in
- Diameter: 1/4 in



8606811 Cartridge Heater

CARTRIDGE HEATER, 1/4" X 1-1/2", 50W

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 50 W
- Supply Voltage: 220 V ac
- Length: 1.5 in
- Diameter: 1/4 in



8606814 Cartridge Heater

HEATING ELEMENT, 3.5IN, 90 W, 220 V AC

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 90 W
- Supply Voltage: 220 V ac
- Length: 3.5 in
- Diameter: 1/4 in



8606820 Cartridge Heater

HEATING ELEMENT, 4IN, 110 W, 220 V AC

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 110 W
- Supply Voltage: 220 V ac
- Length: 4 in
- Diameter: 1/4 in



8606823 Cartridge Heater

HEATING ELEMENT, 4IN, 235 W, 220 V AC

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 235 W
- Supply Voltage: 220 V ac
- Length: 4 in
- Diameter: 1/4 in



8606827 Cartridge Heater

CARTRIDGE HEATER, 1/4" X 4", 300W

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 300 W
- Supply Voltage: 220 V ac
- Length: 4 in
- Diameter: 1/4 in



8606836 Cartridge Heater

HEATING ELEMENT, 4IN, 300 W, 120 V AC

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 300 W
- Supply Voltage: 120 V ac
- Length: 4 in
- Diameter: 1/4 in



8606839 Cartridge Heater

HEATING ELEMENT, 5IN, 400 W, 220 V AC

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 400 W
- Supply Voltage: 220 V ac
- Length: 5 in
- Diameter: 1/4 in



8606842 Cartridge Heater

HEATING ELEMENT, 75MM, 150 W, 120 V AC

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 150 W
- Supply Voltage: 120 V ac
- Length: 75 mm
- Diameter: 6.5 mm



8606845 Cartridge Heater

CARTRIDGE HEATER, 1/4" X 1-1/2", 30W

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 30 W
- Supply Voltage: 220 V ac
- Length: 1.5 in
- Diameter: 1/4 in



8606849 Cartridge Heater

CARTRIDGE HEATER, 1/4" X 2-1/2", 75W

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 75 W
- Supply Voltage: 220 V ac
- Length: 2.5 in
- Diameter: 1/4 in



8606851 Cartridge Heater

HEATING ELEMENT, 3IN, 100 W, 120 V AC

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 100 W
- Supply Voltage: 120 V ac
- Length: 3 in
- Diameter: 1/4 in



8606855 Cartridge Heater

HEATING ELEMENT, 2IN, 50 W, 220 V AC

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 50 W
- Supply Voltage: 220 V ac
- Length: 2 in
- Diameter: 1/4 in



8606858 Cartridge Heater

HEATING ELEMENT, 3.5IN, 200 W, 220 V AC

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 200 W
- Supply Voltage: 220 V ac
- Length: 3.5 in
- Diameter: 1/4 in



8606867 Cartridge Heater

CARTRIDGE HEATER, 10MM X 100MM, 350W

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 350 W
- Supply Voltage: 220 V ac
- Length: 100 mm
- Diameter: 10 mm



8606870 Cartridge Heater

HEATING ELEMENT, 100MM, 500 W, 120 V AC

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 500 W
- Supply Voltage: 120 V ac
- Length: 100 mm
- Diameter: 10 mm



8606877 Cartridge Heater

HEATING ELEMENT, 100MM, 500 W, 120 V AC

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 500 W
- Supply Voltage: 120 V ac
- Length: 100 mm
- Diameter: 10 mm



8606883 Cartridge Heater

CARTRIDGE HEATER, 10MM X 100MM, 150W

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 150 W
- Supply Voltage: 220 V ac
- Length: 100 mm
- Diameter: 10 mm



8606886 Cartridge Heater

CARTRIDGE HEATER, 10MM X 100MM, 200W

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 200 W
- Supply Voltage: 220 V ac
- Length: 100 mm
- Diameter: 10 mm



8606889 Cartridge Heater

CARTRIDGE HEATER, 10MM X 125MM, 500W

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 500 W
- Supply Voltage: 220 V ac
- Length: 125 mm
- Diameter: 10 mm



8606895 Cartridge Heater

CARTRIDGE HEATER, 10MM X 150MM, 300W

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 300 W
- Supply Voltage: 220 V ac
- Length: 150 mm
- Diameter: 10 mm



8606899 Cartridge Heater

CARTRIDGE HEATER, 10MM X 40MM, 50W

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 50 W
- Supply Voltage: 220 V ac
- Length: 40 mm
- Diameter: 10 mm



8606902 Cartridge Heater

HEATING ELEMENT, 50MM, 75 W, 120 V AC

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 75 W
- Supply Voltage: 120 V ac
- Length: 50 mm
- Diameter: 10 mm



8606906 Cartridge Heater

CARTRIDGE HEATER, 10MM X 40MM, 200W

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 200 W
- Supply Voltage: 220 V ac
- Length: 40 mm
- Diameter: 10 mm



8606909 Cartridge Heater

CARTRIDGE HEATER, 10MM X 50MM, 200W

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 200 W
- Supply Voltage: 220 V ac
- Length: 50 mm
- Diameter: 10 mm



8606912 Cartridge Heater

HEATING ELEMENT, 50MM, 75 W, 220 V AC

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 75 W
- Supply Voltage: 220 V ac
- Length: 50 mm
- Diameter: 10 mm



8606915 Cartridge Heater

CARTRIDGE HEATER, 10MM X 50MM, 150W

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 150 W
- Supply Voltage: 220 V ac
- Length: 50 mm
- Diameter: 10 mm



8606918 Cartridge Heater

CARTRIDGE HEATER, 10MM X 65MM, 300W

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 300 W
- Supply Voltage: 220 V ac
- Length: 65 mm
- Diameter: 10 mm



8606921 Cartridge Heater

HEATING ELEMENT, 100MM, 250 W, 120 V AC

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 250 W
- Supply Voltage: 120 V ac
- Length: 100 mm
- Diameter: 13 mm



8606930 Cartridge Heater

HEATING ELEMENT, 100MM, 450 W, 220 V AC

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 450 W
- Supply Voltage: 220 V ac
- Length: 100 mm
- Diameter: 13 mm



8606934 Cartridge Heater

HEATING ELEMENT, 100MM, 250 W, 220 V AC

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 250 W
- Supply Voltage: 220 V ac
- Length: 100 mm
- Diameter: 12.5 mm



8606937 Cartridge Heater

HEATING ELEMENT, 125MM, 325 W, 220 V AC

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 325 W
- Supply Voltage: 220 V ac
- Length: 125 mm
- Diameter: 12.5 mm



8606943 Cartridge Heater

HEATING ELEMENT, 200MM, 600 W, 220 V AC

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 600 W
- Supply Voltage: 220 V ac
- Length: 200 mm
- Diameter: 12.5 mm



8606956 Cartridge Heater

HEATING ELEMENT, 175MM, 500 W, 220 V AC

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 500 W
- Supply Voltage: 220 V ac
- Length: 175 mm
- Diameter: 12.5 mm



8606959 Cartridge Heater

HEATING ELEMENT, 50MM, 200 W, 120 V AC

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 200 W
- Supply Voltage: 120 V ac
- Length: 50 mm
- Diameter: 13 mm



8606965 Cartridge Heater

HEATING ELEMENT, 65MM, 150 W, 220 V AC

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 150 W
- Supply Voltage: 220 V ac
- Length: 65 mm
- Diameter: 13 mm



8606968 Cartridge Heater

HEATING ELEMENT, 100MM, 350 W, 220 V AC

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 350 W
- Supply Voltage: 220 V ac
- Length: 100 mm
- Diameter: 16 mm



8606980 Cartridge Heater

CARTRIDGE HEATER, 16MM X 200MM, 700W

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 700 W
- Supply Voltage: 220 V ac
- Length: 200 mm
- Diameter: 16 mm



8606990 Cartridge Heater

HEATING ELEMENT, 150MM, 500 W, 220 V AC

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 500 W
- Supply Voltage: 220 V ac
- Length: 150 mm
- Diameter: 16 mm



8606993 Cartridge Heater

HEATING ELEMENT, 175MM, 600 W, 220 V AC

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 600 W
- Supply Voltage: 220 V ac
- Length: 175 mm
- Diameter: 16 mm



8606996 Cartridge Heater

HEATING ELEMENT, 75MM, 225 W, 220 V AC

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 225 W
- Supply Voltage: 220 V ac
- Length: 75 mm
- Diameter: 16 mm



8607000 Cartridge Heater

CARTRIDGE HEATER, 16MM X 200MM, 1000W

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 1 kW
- Supply Voltage: 220 V ac
- Length: 200 mm
- Diameter: 16 mm



8607003 Cartridge Heater

HEATING ELEMENT, 50MM, 250 W, 220 V AC

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 250 W
- Supply Voltage: 220 V ac
- Length: 50 mm
- Diameter: 16 mm



8607006 Cartridge Heater

HEATING ELEMENT, 6IN, 500 W, 220 V AC

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 500 W
- Supply Voltage: 220 V ac
- Length: 6 in
- Diameter: 19 mm



8607012 Cartridge Heater

HEATING ELEMENT, 2IN, 100 W, 120 V AC

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 100 W
- Supply Voltage: 120 V ac
- Length: 2 in
- Diameter: 3/8 in



8607025 Cartridge Heater

HEATING ELEMENT, 2IN, 150 W, 220 V AC

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 150 W
- Supply Voltage: 220 V ac
- Length: 2 in
- Diameter: 3/8 in



8607028 Cartridge Heater

HEATING ELEMENT, 2.5IN, 300 W, 220 V AC

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 300 W
- Supply Voltage: 220 V ac
- Length: 2.5 in
- Diameter: 3/8 in



8607031 Cartridge Heater

HEATING ELEMENT, 3IN, 250 W, 120 V AC

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 250 W
- Supply Voltage: 120 V ac
- Length: 3 in
- Diameter: 3/8 in



8607038 Cartridge Heater

HEATING ELEMENT, 3.5IN, 150 W, 220 V AC

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 150 W
- Supply Voltage: 220 V ac
- Length: 3.5 in
- Diameter: 3/8 in



8607040 Cartridge Heater

HEATING ELEMENT, 3IN, 400 W, 220 V AC

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 400 W
- Supply Voltage: 220 V ac
- Length: 3 in
- Diameter: 3/8 in



8607047 Cartridge Heater

HEATING ELEMENT, 4IN, 500 W, 240 V AC

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 500 W
- Supply Voltage: 240 V ac
- Length: 4 in
- Diameter: 3/8 in



8607050 Cartridge Heater

HEATING ELEMENT, 4IN, 350 W, 220 V AC

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 350 W
- Supply Voltage: 220 V ac
- Length: 4 in
- Diameter: 3/8 in



8607053 Cartridge Heater

HEATING ELEMENT, 4IN, 350 W, 120 V AC

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 350 W
- Supply Voltage: 120 V ac
- Length: 4 in
- Diameter: 3/8 in



8607056 Cartridge Heater

HEATING ELEMENT, 5IN, 500 W, 220 V AC

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 500 W
- Supply Voltage: 220 V ac
- Length: 5 in
- Diameter: 3/8 in



8607062 Cartridge Heater

CARTRIDGE HEATER, 3/8 " X 1-1/2", 100W

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 100 W
- Supply Voltage: 220 V ac
- Length: 1.5 in
- Diameter: 3/8 in



8607066 Cartridge Heater

HEATING ELEMENT, 5IN, 280 W, 220 V AC

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 280 W
- Supply Voltage: 220 V ac
- Length: 5 in
- Diameter: 3/8 in



8607069 Cartridge Heater

CARTRIDGE HEATER, 3/8" X 1-1/2", 200W

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 200 W
- Supply Voltage: 220 V ac
- Length: 1.5 in
- Diameter: 3/8 in



8607075 Cartridge Heater

HEATING ELEMENT, 2IN, 200 W, 220 V AC

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 200 W
- Supply Voltage: 220 V ac
- Length: 2 in
- Diameter: 3/8 in



8607072 Cartridge Heater

HEATING ELEMENT, 1.5IN, 50 W, 220 V AC

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 50 W
- Supply Voltage: 220 V ac
- Length: 1.5 in
- Diameter: 3/8 in



8607078 Cartridge Heater

CARTRIDGE HEATER, 6.5MM X 100MM, 100W

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 100 W
- Supply Voltage: 220 V ac
- Length: 100 mm
- Diameter: 6.5 mm



8607101 Cartridge Heater

HEATING ELEMENT, 6IN, 540 W, 220 V AC

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 540 W
- Supply Voltage: 220 V ac
- Length: 6 in
- Diameter: 5/8 in



8607090 Cartridge Heater

HEATING ELEMENT, 6IN, 350 W, 220 V AC

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 350 W
- Supply Voltage: 220 V ac
- Length: 6 in
- Diameter: 3/8 in



8607081 Cartridge Heater

HEATING ELEMENT, 8IN, 750 W, 220 V AC

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 750 W
- Supply Voltage: 220 V ac
- Length: 8 in
- Diameter: 5/8 in



8607104 Cartridge Heater

CARTRIDGE HEATER, 6.5MM X 100MM, 400W

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 400 W
- Supply Voltage: 220 V ac
- Length: 100 mm
- Diameter: 6.5 mm



8607113 Cartridge Heater

HEATING ELEMENT, 100MM, 300 W, 220 V AC

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 300 W
- Supply Voltage: 220 V ac
- Length: 100 mm
- Diameter: 6.5 mm



8607117 Cartridge Heater

CARTRIDGE HEATER, 6.5MM X 100MM, 250W

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 250 W
- Supply Voltage: 220 V ac
- Length: 100 mm
- Diameter: 6.5 mm



8607126 Cartridge Heater

CARTRIDGE HEATER, 6.5MM X 40MM, 50W

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 50 W
- Supply Voltage: 220 V ac
- Length: 40 mm
- Diameter: 6.5 mm



8607139 Cartridge Heater

HEATING ELEMENT, 60MM, 100 W, 120 V AC

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 100 W
- Supply Voltage: 120 V ac
- Length: 60 mm
- Diameter: 6.5 mm



8607141 Cartridge Heater

CARTRIDGE HEATER, 6.5MM X 90MM, 200W

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 200 W
- Supply Voltage: 220 V ac
- Length: 90 mm
- Diameter: 6.5 mm



8607151 Cartridge Heater

CARTRIDGE HEATER, 6.5MM X 75MM, 100W

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 100 W
- Supply Voltage: 220 V ac
- Length: 75 mm
- Diameter: 6.5 mm



8607154 Cartridge Heater

HEATING ELEMENT, 4IN, 500 W, 220 V AC

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 500 W
- Supply Voltage: 220 V ac
- Length: 4 in
- Diameter: 1/2 in



8607160 Cartridge Heater

CARTRIDGE HEATER, 10MM X 40MM, 100W

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 100 W
- Supply Voltage: 220 V ac
- Length: 40 mm
- Diameter: 10 mm
- Heating Element Form: Tubular



8607163 Cartridge Heater

HEATING ELEMENT, 150MM, 600 W, 220 V AC

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 600 W
- Supply Voltage: 220 V ac
- Length: 150 mm
- Diameter: 10 mm



8607167 Cartridge Heater

HEATING ELEMENT, 150MM, 400 W, 220 V AC

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 400 W
- Supply Voltage: 220 V ac
- Length: 150 mm
- Diameter: 16 mm



8607173 Cartridge Heater

HEATING ELEMENT, 4IN, 400 W, 220 V AC

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 400 W
- Supply Voltage: 220 V ac
- Length: 4 in
- Diameter: 1/4 in



8607179 Cartridge Heater

HEATING ELEMENT, 400 W, 120 V AC

Pack size: **1 x EA**

- Element Type: Cartridge Heater
- Power Rating: 400 W
- Supply Voltage: 120 V ac



8607182 Air Heater

HEATING ELEMENT, 400 W, 240 V AC

Pack size: **1 x EA**

- Element Type: Air Heater
- Power Rating: 400 W
- Supply Voltage: 240 V ac



8607185 Air Heater

HEATING ELEMENT, 600 W, 120 V AC

Pack size: **1 x EA**

- Element Type: Air Heater
- Power Rating: 600 W
- Supply Voltage: 120 V ac



8607189 Air Heater

AIR HEATER, 600W, 240V AC, INC LEAD

Pack size: **1 x EA**

- Element Type: Air Heater
- Power Rating: 600 W
- Supply Voltage: 240 V ac



8607198 Air Heater

HEATING ELEMENT, 600 W, 240 V AC

Pack size: **1 x EA**

- Element Type: Air Heater
- Power Rating: 600 W
- Supply Voltage: 240 V ac



8607208 Air Heater

HEATING ELEMENT, 235 W, 230 V AC

Pack size: **1 x EA**

- Element Type: Band Heater
- Power Rating: 235 W
- Supply Voltage: 230 V ac
- Diameter: 38 mm



9209956 Band Heater

HEATING ELEMENT, 345 W, 230 V AC

Pack size: **1 x EA**

- Element Type: Band Heater
- Power Rating: 345 W
- Supply Voltage: 230 V ac
- Diameter: 40 mm



9209962 Band Heater

HEATING ELEMENT, 415 W, 230 V AC

Pack size: **1 x EA**

- Element Type: Band Heater
- Power Rating: 415 W
- Supply Voltage: 230 V ac
- Diameter: 60 mm



9209966 Band Heater

HEATING ELEMENT, 270 W, 230 V AC

Pack size: **1 x EA**

- Element Type: Band Heater
- Power Rating: 270 W
- Supply Voltage: 230 V ac
- Diameter: 40 mm



9209969 Band Heater

NOZZLE HEATER, 40X38MM, 300W, 230V

Pack size: **1 x EA**

- Element Type: Band Heater
- Power Rating: 300 W
- Supply Voltage: 230 V ac
- Diameter: 40 mm



9209975 Band Heater

HEATING ELEMENT, 375 W, 230 V AC

Pack size: **1 x EA**

- Element Type: Band Heater
- Power Rating: 375 W
- Supply Voltage: 230 V ac
- Diameter: 60 mm



9209984 Band Heater

HEATING ELEMENT, 390 W, 230 V AC

Pack size: **1 x EA**

- Element Type: Band Heater
- Power Rating: 390 W
- Supply Voltage: 230 V ac
- Diameter: 60 mm



9209981 Band Heater

HEATING ELEMENT, 440 W, 230 V AC

Pack size: **1 x EA**

- Element Type: Band Heater
- Power Rating: 440 W
- Supply Voltage: 230 V ac
- Diameter: 70 mm



9209988 Band Heater

HEATING ELEMENT, 560 W, 230 V AC

Pack size: **1 x EA**

- Element Type: Band Heater
- Power Rating: 560 W
- Supply Voltage: 230 V ac
- Diameter: 70 mm



9209997 Band Heater

HEATING ELEMENT, 750 W, 230 V AC

Pack size: **1 x EA**

- Element Type: Mica Strip
- Power Rating: 750 W
- Supply Voltage: 230 V ac



9210023 Mica Strip

HEATING ELEMENT, 600 W, 230 V AC

Pack size: **1 x EA**

- Element Type: Mica Strip
- Power Rating: 600 W
- Supply Voltage: 230 V ac



9210032 Mica Strip

HEATING ELEMENT, 400 W, 230 V AC

Pack size: **1 x EA**

- Element Type: Mica Strip
- Power Rating: 400 W
- Supply Voltage: 230 V ac



9210035 Mica Strip

HEATING ELEMENT, 950 W, 230 V AC

Pack size: **1 x EA**

- Element Type: Mica Strip
- Power Rating: 950 W
- Supply Voltage: 230 V ac



9210039 Mica Strip

HEATING ELEMENT, 450 W, 230 V AC

Pack size: **1 x EA**

- Element Type: Mica Strip
- Power Rating: 450 W
- Supply Voltage: 230 V ac



9210041 Mica Strip

HEATING ELEMENT, 850 W, 230 V AC

Pack size: **1 x EA**

- Element Type: Mica Strip
- Power Rating: 850 W
- Supply Voltage: 230 V ac



9210054 Mica Strip

HEATING ELEMENT, 550 W, 230 V AC

Pack size: **1 x EA**

- Element Type: Mica Strip
- Power Rating: 550 W
- Supply Voltage: 230 V ac



9210057 Mica Strip

HEATING ELEMENT, 1.45 KW, 230 V AC

Pack size: **1 x EA**

- Element Type: Mica Strip
- Power Rating: 1.45 kW
- Supply Voltage: 230 V ac




9210067 Mica Strip

HEATING ELEMENT, 2 KW, 230 V AC

Pack size: **1 x EA**

- Element Type: Mica Strip
- Power Rating: 2 kW
- Supply Voltage: 230 V ac



9210073 Mica Strip

HEATING ELEMENT, 700 W, 230 V AC

Pack size: **1 x EA**

- Element Type: Mica Strip
- Power Rating: 700 W
- Supply Voltage: 230 V ac



9210079 Mica Strip

HEATING ELEMENT, 1.6 KW, 230 V AC

Pack size: **1 x EA**

- Element Type: Mica Strip
- Power Rating: 1.6 kW
- Supply Voltage: 230 V ac



9210082 Mica Strip

HEATING ELEMENT, 800 W, 230 V AC

Pack size: **1 x EA**

- Element Type: Mica Strip
- Power Rating: 800 W
- Supply Voltage: 230 V ac



9210089 Mica Strip

INFRARED TEMPERATURE SENSOR

Pack size: **1 x EA**

- Sensor Type: V Output Signal
- Response Time: 250 ms
- Accuracy: $\pm 1.5^{\circ}\text{C}$ or $\pm 1.5\%$ of reading
- Cable Length: 1 m
- Supply Voltage: 24 V dc
- Minimum Temperature Sensed: 0°C
- Output Type: Alarm, Analogue
- Light Source: Infrared



1618103 V Output Signal

RS PRO V OUTPUT SIGNAL UART, USB INFRARED TEMPERATURE SENSOR, 1M

Pack size: **1 x EA**

- Sensor Type: V Output Signal
- Response Time: 250 ms
- Accuracy: $\pm 1.5^{\circ}\text{C}$ or $\pm 1.5\%$ of reading
- Cable Length: 1 m
- Supply Voltage: 24 V dc
- Minimum Temperature Sensed: 0°C
- Output Type: Alarm, Analogue
- Light Source: Infrared



2387241 V Output Signal

DIGITAL PROCESS INDICATOR, 77X35MM DIMEN

Pack size: **1 x EA**

- Properties Measured: Current, Voltage
- Display Type: Digital
- Cutout Height: 71 mm
- Cutout Width: 29 mm
- Depth: 62.5 mm
- Number of Digits: 4
- Meter Type: Process Indicator



1981166 Current, Voltage

THERMOMETER, PLATINUM RESISTANCE, PT100, STAINLESS

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 100 mm
- Probe Diameter: 3 mm
- Minimum Temperature Sensed: -50°C
- Maximum Temperature Sensed: $+200^{\circ}\text{C}$
- Termination Type: Lead Wire
- Cable Length: 1 m
- Probe Material: Stainless Steel



158985 PT100

RS PRO PT100 RTD SENSOR, 6MM DIA, 200MM LONG, 4 WIRE, PROBE,

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 200 mm
- Probe Diameter: 6 mm
- Minimum Temperature Sensed: -50°C
- Maximum Temperature Sensed: $+450^{\circ}\text{C}$
- Termination Type: Connection Head
- Probe Material: Stainless Steel
- Process Connection: Probe



285633 PT100

RS PRO PT100 RTD SENSOR, 6MM DIA, 400MM LONG, 4 WIRE, PROBE,

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 400 mm
- Probe Diameter: 6 mm
- Minimum Temperature Sensed: -50°C
- Maximum Temperature Sensed: $+450^{\circ}\text{C}$
- Termination Type: Connection Head
- Probe Material: Stainless Steel
- Process Connection: Probe



285649 PT100

RS PRO PT100 RTD SENSOR, 6MM DIA, 600MM LONG, 4 WIRE, PROBE,

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 600 mm
- Probe Diameter: 6 mm
- Minimum Temperature Sensed: -50°C
- Maximum Temperature Sensed: $+450^{\circ}\text{C}$
- Termination Type: Connection Head
- Probe Material: Stainless Steel
- Process Connection: Probe



285655 PT100

THERMOMETER, PLATINUM RESISTANCE, PT100, PATCH, SELF

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 40 mm
- Probe Diameter: 13 mm
- Minimum Temperature Sensed: -50°C
- Maximum Temperature Sensed: $+150^{\circ}\text{C}$
- Termination Type: Lead Wire
- Cable Length: 2 m
- Probe Material: Aluminium Foil Backing, Silicone Rubber



285661 PT100

RS PRO PT100 RTD SENSOR, $+70^{\circ}\text{C}$ MAX

Pack size: **1 x EA**

- Sensor Type: PT100
- Minimum Temperature Sensed: -30°C
- Maximum Temperature Sensed: $+70^{\circ}\text{C}$



813862 PT100

RS PRO PT100 RTD SENSOR, $+70^{\circ}\text{C}$ MAX

Pack size: **1 x EA**

- Sensor Type: PT100
- Minimum Temperature Sensed: -30°C
- Maximum Temperature Sensed: $+70^{\circ}\text{C}$



813878 PT100

RS PRO PT100 RTD SENSOR, $+110^{\circ}\text{C}$ MAX

Pack size: **1 x EA**

- Sensor Type: PT100
- Minimum Temperature Sensed: -30°C
- Maximum Temperature Sensed: $+110^{\circ}\text{C}$, $+40^{\circ}\text{C}$



813890 PT100

RS PRO PT100 RTD SENSOR, 2.8MM DIA, 15MM LONG, 2 WIRE, PROBE,

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 15 mm
- Probe Diameter: 2.8 mm
- Minimum Temperature Sensed: -50°C
- Maximum Temperature Sensed: $+350^{\circ}\text{C}$
- Termination Type: Lead Wire
- Cable Length: 300 mm
- Probe Material: Glass Fibre



1104460 PT100

RS PRO PT100 RTD SENSOR, 2.8MM DIA, 15MM LONG, 2 WIRE, PROBE,

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 15 mm
- Probe Diameter: 2.8 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +350 °C
- Termination Type: Lead Wire
- Cable Length: 1 m
- Probe Material: Glass Fibre



1104462 PT100

PRTD PT100, 3MM X 25MM 2 MTR CABLE

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 25 mm
- Probe Diameter: 3 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +250 °C
- Termination Type: Cable
- Cable Length: 2 m
- Probe Material: Stainless Steel



1235583 PT100

RS PRO PT100 RTD SENSOR, 3MM DIA, 50MM LONG, 4 WIRE, PROBE,

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 50 mm
- Probe Diameter: 3 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +250 °C
- Termination Type: Cable
- Cable Length: 2 m
- Probe Material: Stainless Steel



1235584 PT100

PRTD PT100, 3MM X 100MM 2 MTR CABLE

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 100 mm
- Probe Diameter: 3 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +250 °C
- Termination Type: Cable
- Cable Length: 2 m
- Probe Material: Stainless Steel



1235585 PT100

RS PRO PT100 RTD SENSOR, 3MM DIA, 125MM LONG, 4 WIRE, PROBE,

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 125 mm
- Probe Diameter: 3 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +250 °C
- Termination Type: Cable
- Cable Length: 2 m
- Probe Material: Stainless Steel



1235586 PT100

RS PRO PT100 RTD SENSOR, 3MM DIA, 150MM LONG, 4 WIRE, CLASS B

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 150 mm
- Probe Diameter: 3 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +250 °C
- Termination Type: Cable
- Cable Length: 2 m
- Probe Material: Stainless Steel



1235587 PT100

PRTD PT100, 4MM X 25MM 2 MTR CABLE

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 25 mm
- Probe Diameter: 4 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +250 °C
- Termination Type: Cable
- Cable Length: 2 m
- Probe Material: Stainless Steel



1235588 PT100

PRTD PT100, 4MM X 50MM 2 MTR CABLE

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 50 mm
- Probe Diameter: 4 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +250 °C
- Termination Type: Cable
- Cable Length: 2 m
- Probe Material: Stainless Steel



1235589 PT100

PRTD PT100, 4MM X 100MM 2 MTR CABLE

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 100 mm
- Probe Diameter: 4 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +250 °C
- Termination Type: Cable
- Cable Length: 2 m
- Probe Material: Stainless Steel



1235590 PT100

PRTD PT100, 4MM X 150MM 2 MTR CABLE

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 150 mm
- Probe Diameter: 4 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +250 °C
- Termination Type: Cable
- Cable Length: 2 m
- Probe Material: Stainless Steel



1235591 PT100

RS PRO PT100 RTD SENSOR, 4.5MM DIA, 25MM LONG, 4 WIRE, PROBE,

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 25 mm
- Probe Diameter: 4.5 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +250 °C
- Termination Type: Cable
- Cable Length: 2 m
- Probe Material: Stainless Steel



1235593 PT100

RS PRO PT100 RTD SENSOR, 4.5MM DIA, 100MM LONG, 4 WIRE, PROBE,

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 100 mm
- Probe Diameter: 4.5 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +250 °C
- Termination Type: Cable
- Cable Length: 2 m
- Probe Material: Stainless Steel



1235596 PT100

PRTD PT100, 4MM X 50MM 2 MTR CABLE

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 50 mm
- Probe Diameter: 4.5 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +250 °C
- Termination Type: Cable
- Cable Length: 2 m
- Probe Material: Stainless Steel



1235594 PT100

RS PRO PT100 RTD SENSOR, 4.5MM DIA, 75MM LONG, 4 WIRE, PROBE,

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 75 mm
- Probe Diameter: 4.5 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +250 °C
- Termination Type: Cable
- Cable Length: 2 m
- Probe Material: Stainless Steel



1235595 PT100

RS PRO PT100 RTD SENSOR, 4.5MM DIA, 125MM LONG, 4 WIRE, PROBE,

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 125 mm
- Probe Diameter: 4.5 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +250 °C
- Termination Type: Cable
- Cable Length: 2 m
- Probe Material: Stainless Steel



1235597 PT100

RS PRO PT100 RTD SENSOR, 4.5MM DIA, 150MM LONG, 4 WIRE, PROBE,

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 150 mm
- Probe Diameter: 4.5 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +250 °C
- Termination Type: Cable
- Cable Length: 2 m
- Probe Material: Stainless Steel



1235598 PT100

RS PRO PT100 RTD SENSOR, 4.5MM DIA, 200MM LONG, 4 WIRE, PROBE,

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 200 mm
- Probe Diameter: 4.5 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +250 °C
- Termination Type: Cable
- Cable Length: 2 m
- Probe Material: Stainless Steel



1235599 PT100

PRTD PT100, 6MM X 50MM 2 MTR CABLE

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 50 mm
- Probe Diameter: 6 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +250 °C
- Termination Type: Cable
- Cable Length: 2 m
- Probe Material: Stainless Steel



1235600 PT100

PRTD PT100, 6MM X 100MM 2 MTR CABLE

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 100 mm
- Probe Diameter: 6 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +250 °C
- Termination Type: Cable
- Cable Length: 2 m
- Probe Material: Stainless Steel



1235602 PT100

RS PRO PT100 RTD SENSOR, 6MM DIA, 125MM LONG, 4 WIRE, PROBE,

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 125 mm
- Probe Diameter: 6 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +250 °C
- Termination Type: Cable
- Cable Length: 2 m
- Probe Material: Stainless Steel



1235603 PT100

PRTD PT100, 6MM X 150MM 2 MTR CABLE

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 150 mm
- Probe Diameter: 6 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +250 °C
- Termination Type: Cable
- Cable Length: 2 m
- Probe Material: Stainless Steel



1235604 PT100

PRTD PT100, 6MM X 300MM 2 MTR CABLE

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 300 mm
- Probe Diameter: 6 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +250 °C
- Termination Type: Cable
- Cable Length: 2 m
- Probe Material: Stainless Steel



1235606 PT100

PRTD PT100, 4MM X 25MM 1 MTR CABLE

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 25 mm
- Probe Diameter: 4 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +200 °C
- Termination Type: Cable
- Cable Length: 1 m
- Probe Material: Stainless Steel



1235607 PT100

PRTD PT100, 4MM X 40MM 1 MTR CABLE

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 40 mm
- Probe Diameter: 4 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +200 °C
- Termination Type: Cable
- Cable Length: 1 m
- Probe Material: Stainless Steel



1235608 PT100

RS PRO PT100 RTD SENSOR, 4MM DIA, 65MM LONG, 4 WIRE, PROBE,

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 65 mm
- Probe Diameter: 4 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +200 °C
- Termination Type: Cable
- Cable Length: 1 m
- Probe Material: Stainless Steel



1235609 PT100

PRTD PT1000, 4MM X 40MM 1 MTR CABLE

Pack size: **1 x EA**

- Sensor Type: PT1000
- Probe Length: 40 mm
- Probe Diameter: 4 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +200 °C
- Termination Type: Cable
- Cable Length: 1 m
- Probe Material: Stainless Steel



1235612 PT1000

RS PRO PT100 RTD SENSOR, 0.9MM DIA, 15MM LONG, PROBE, +650°C

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 15 mm
- Probe Diameter: 0.9 mm
- Minimum Temperature Sensed: -200 °C
- Maximum Temperature Sensed: +650 °C
- Termination Type: Solder
- Probe Material: Alumina Ceramic (Body)
- Process Connection: Probe



1741656 PT100

RS PRO PT1000 RTD SENSOR, 4MM DIA, 75MM LONG, 2 WIRE, PROBE,

Pack size: **1 x EA**

- Sensor Type: PT1000
- Probe Length: 75 mm
- Probe Diameter: 4 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +200 °C
- Termination Type: Cable
- Cable Length: 1 m
- Probe Material: 316 Stainless Steel



1365901 PT1000

PT1000 PLATINUM RESISTANCE THERMOMETER

Pack size: **1 x EA**

- Sensor Type: PT1000
- Probe Length: 125 mm
- Probe Diameter: 4 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +200 °C
- Termination Type: Cable
- Cable Length: 1 m
- Probe Material: 316 Stainless Steel



1365902 PT1000

RS PRO PT100 RTD SENSOR, 2.8MM DIA, 25MM LONG, PROBE, +650°C

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 25 mm
- Probe Diameter: 2.8 mm
- Minimum Temperature Sensed: -200 °C
- Maximum Temperature Sensed: +650 °C
- Termination Type: Solder
- Probe Material: Alumina Ceramic (Body)
- Process Connection: Probe



1741659 PT100

PLATINUM RESISTANCE PT1000 CLASS B SENSO

Pack size: **1 x EA**

- Sensor Type: PT1000
- Probe Length: 25 mm
- Probe Diameter: 4 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +200 °C
- Termination Type: Cable
- Cable Length: 1 m
- Probe Material: 316 Stainless Steel



1780974 PT1000

RS PRO PT1000 RTD SENSOR, 4MM DIA, 150MM LONG, 2 WIRE, PROBE,

Pack size: **1 x EA**

- Sensor Type: PT1000
- Probe Length: 150 mm
- Probe Diameter: 4 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +200 °C
- Termination Type: Cable
- Cable Length: 1 m
- Probe Material: 316 Stainless Steel



1780975 PT1000

SENSOR PT-100

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 2 mm
- Probe Diameter: 2 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +600 °C
- Termination Type: Solder
- Process Connection: Chip
- Accuracy: Class A



1812028 PT100

RS PRO PT100 RTD SENSOR, 6MM DIA, 250MM LONG, 2 X 3 WIRE,

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 250 mm
- Probe Diameter: 6 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +250 °C
- Termination Type: KNE Terminal Head
- Probe Material: 316 Stainless Steel
- Process Connection: Probe



2000592 PT100

RS PRO PT100 RTD SENSOR, 2MM DIA, 10MM LONG, CHIP, CLASS B

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 10 mm
- Probe Diameter: 2 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +600 °C
- Termination Type: Solder
- Process Connection: Chip
- Accuracy: Class B



1811980 PT100

RS PRO PT100 RTD SENSOR, 6MM DIA, 75MM LONG, 3 WIRE, G1/2,

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 75 mm
- Probe Diameter: 6 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +250 °C
- Probe Material: 316 Stainless Steel
- Process Connection: G1/2
- Number Of Wires: 3



2000594 PT100

RS PRO PT100 RTD SENSOR, 6MM DIA, 300MM LONG, 3 WIRE, PROBE,

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 300 mm
- Probe Diameter: 6 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +250 °C
- Probe Material: 316 Stainless Steel
- Process Connection: Probe
- Number Of Wires: 3



2000598 PT100

RS PRO PT100 RTD SENSOR, 6MM DIA, 150MM LONG, 4 WIRE, PROBE,

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 150 mm
- Probe Diameter: 6 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +250 °C
- Termination Type: Cable
- Cable Length: 1 m
- Probe Material: Stainless Steel



2364261 PT100

RS PRO PT100 RTD SENSOR, 6MM DIA, 100MM LONG, 2 X 3 WIRE, G1/2,

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 100 mm
- Probe Diameter: 6 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +250 °C
- Termination Type: KNE Terminal Head
- Probe Material: 316 Stainless Steel
- Process Connection: G1/2



2000588 PT100

SENSOR,TEMPERATURE,EXTERNAL/C OLD STORE,PT100

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 75 mm
- Probe Diameter: 12.7 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +150 °C
- Termination Type: Cable Gland
- Probe Material: Stainless Steel
- Process Connection: Wall



2364283 PT100

SENSOR,TEMPERATURE,PRECISION,PT100

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 250 mm
- Probe Diameter: 6 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +250 °C
- Termination Type: Cable
- Cable Length: 2 m
- Probe Material: Stainless Steel



2364299 PT100

ELEMENT,PLATINUM FILM,PT100,THIN FILM TECHNOLOGY

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 10 mm
- Probe Diameter: 2 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +500 °C
- Termination Type: Solder
- Probe Material: Platinum
- Process Connection: Chip



2371607 PT100

RS PRO PT100 RTD SENSOR, 6MM DIA, 150MM LONG, 3 WIRE, G1/2,

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 150 mm
- Probe Diameter: 6 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +250 °C
- Probe Material: 316 Stainless Steel
- Process Connection: G1/2
- Number Of Wires: 3



2000596 PT100

PROBE,INDUSTRIAL PT100,6MM DIA X 250MM

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 250 mm
- Probe Diameter: 6 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +250 °C
- Termination Type: Cable
- Cable Length: 1 m
- Probe Material: Stainless Steel



2364277 PT100

ELEMENT,PLATINUM FILM,PT100,THIN FILM TECHNOLOGY,STAINLESS STEEL

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 35 mm
- Probe Diameter: 6 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +250 °C
- Termination Type: Lead Wire
- Cable Length: 1 m
- Probe Material: Stainless Steel



2371613 PT100

SENSOR,TUBULAR CERAMIC ENCASED,PT100,2 WIRE,MULTI

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 35 mm
- Probe Diameter: 5 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +250 °C
- Termination Type: Lead Wire
- Cable Length: 450 mm
- Probe Material: Platinum



2371657 PT100

CONNECTOR,PT 100 PROBE,4 WIRE OUTPUT,1M

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 150 mm
- Probe Diameter: 4 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +250 °C
- Termination Type: Lead Wire
- Cable Length: 1 m
- Probe Material: Stainless Steel



2371663 PT100

RS PRO PT100 RTD SENSOR, 2MM DIA, 5MM LONG, 2 WIRE, CHIP,

Pack size: **5 x EA**

- Sensor Type: PT100
- Probe Length: 5 mm
- Probe Diameter: 2 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +500 °C
- Termination Type: Solder
- Probe Material: Platinum
- Process Connection: Chip



2905070 PT100

PROBE PT100

Pack size: **1 x EA**

- Sensor Type: PT1000
- Probe Length: 10 mm
- Probe Diameter: 2 mm
- Minimum Temperature Sensed: -70 °C
- Maximum Temperature Sensed: +550 °C
- Termination Type: Solder
- Process Connection: Chip
- Accuracy: Class 1/3 B



2938446 PT1000

RS PRO PT100 RTD SENSOR, 5MM DIA, 35MM LONG, 4 WIRE, PROBE,

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 35 mm
- Probe Diameter: 5 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +450 °C
- Termination Type: Lead Wire
- Cable Length: 450 mm
- Probe Material: Platinum



2371635 PT100

RS PRO PT100 RTD SENSOR, 2.8MM DIA, 25MM LONG, PROBE, CLASS A

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 25 mm
- Probe Diameter: 2.8 mm
- Minimum Temperature Sensed: -200 °C
- Maximum Temperature Sensed: +600 °C
- Termination Type: Solder
- Probe Material: Platinum
- Process Connection: Probe



2938496 PT100

RS PRO RTD SENSOR, +40°C MAX

Pack size: **1 x EA**

- Minimum Temperature Sensed: 0 °C
- Maximum Temperature Sensed: +40 °C



3122939 0 °C

SENSOR,TUBULAR CERAMIC ENCASED,PT100,2 WIRE,MULTI

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 35 mm
- Probe Diameter: 2 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +250 °C
- Termination Type: Lead Wire
- Cable Length: 50 mm
- Probe Material: Platinum



2371641 PT100

RS PRO RTD SENSOR, +50°C MAX

Pack size: **1 x EA**

- Minimum Temperature Sensed: -20 °C
- Maximum Temperature Sensed: +50 °C



3122951 -20 °C

TEMP SENSOR, PT1000, 6MM

Pack size: **1 x EA**

- Sensor Type: PT1000
- Probe Length: 100 mm
- Probe Diameter: 6 mm
- Minimum Temperature Sensed: -20 °C
- Maximum Temperature Sensed: +100 °C
- Termination Type: Cable
- Cable Length: 2 m
- Probe Material: Stainless Steel



3342616 PT1000

SENSOR,AIR/TEMPERATURE,CLEAN ROOM,PT00

Pack size: **1 x EA**

- Sensor Type: PT100
- Minimum Temperature Sensed: 0 °C
- Maximum Temperature Sensed: +70 °C
- Termination Type: Cable Gland
- Process Connection: Wall
- Accuracy: Class B



3389491 PT100

SENSOR,TEMPERATURE,THERMOCOUPLE,PLATINUM,THIN

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 10 mm
- Probe Diameter: 2 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +500 °C
- Termination Type: Solder
- Probe Material: Platinum
- Process Connection: Chip



3629799 PT100

RS PRO PT100 RTD SENSOR, 1.6MM DIA, 8MM LONG, PROBE, CLASS 1/10

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 8 mm
- Probe Diameter: 1.6 mm
- Minimum Temperature Sensed: -200 °C
- Maximum Temperature Sensed: +600 °C
- Termination Type: Solder
- Probe Material: Platinum
- Process Connection: Probe



2938480 PT100

SENSOR,TEMPERATURE,THERMOCOUPLE,PLATINUM,THIN

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 2.3 mm
- Probe Diameter: 2 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +500 °C
- Termination Type: Solder
- Probe Material: Platinum
- Process Connection: Chip



3629834 PT100

RS PRO RTD SENSOR, +50°C MAX

Pack size: **1 x EA**

- Minimum Temperature Sensed: -20 °C
- Maximum Temperature Sensed: +50 °C



3122945 -20 °C

SENSOR,TEMPERATURE,THERMOCOUPLE,PLATINUM,THIN

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 2.3 mm
- Probe Diameter: 2 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +500 °C
- Termination Type: Solder
- Probe Material: Platinum
- Process Connection: Chip



3629856 PT100

SENSOR,TEMPERATURE,THERMOCOUPLE,PLATINUM,THIN

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 10 mm
- Probe Diameter: 2 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +500 °C
- Termination Type: Solder
- Probe Material: Platinum
- Process Connection: Chip



3629812 PT100

SENSOR,TEMPERATURE,THERMOCOUPLE,PLATINUM,THIN

Pack size: **1 x EA**

- Sensor Type: PT1000
- Probe Length: 10 mm
- Probe Diameter: 2 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +500 °C
- Termination Type: Solder
- Probe Material: Platinum
- Process Connection: Chip



3629913 PT1000

SENSOR,TEMPERATURE,THERMOCOUPLE,PLATINUM,THIN

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 2.3 mm
- Probe Diameter: 2 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +500 °C
- Termination Type: Solder
- Probe Material: Platinum
- Process Connection: Chip



3629840 PT100

PROBE, INDUSTRIAL, PT100, 3MM DIA X 250MM

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 250 mm
- Probe Diameter: 3 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +250 °C
- Termination Type: Cable
- Cable Length: 1 m
- Probe Material: Stainless Steel



3629941 PT100

TEMPERATURE PROBE

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 100 mm
- Probe Diameter: 6 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +200 °C
- Termination Type: Cable
- Cable Length: 2 m
- Probe Material: Stainless Steel



3730372 PT100

SENSOR, TEMPERATURE, THERMOCOUPLE, PLATINUM, THIN

Pack size: **1 x EA**

- Sensor Type: PT1000
- Probe Length: 10 mm
- Probe Diameter: 2 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +500 °C
- Termination Type: Solder
- Probe Material: Platinum
- Process Connection: Chip



3629907 PT1000

RS PRO PT100 RTD SENSOR, 3MM DIA, 150MM LONG, 4 WIRE, PROBE,

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 150 mm
- Probe Diameter: 3 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +250 °C
- Termination Type: Cable
- Cable Length: 1 m
- Probe Material: Stainless Steel



3629935 PT100

RS PRO PT100 RTD SENSOR, +60°C MAX

Pack size: **1 x EA**

- Sensor Type: PT100
- Minimum Temperature Sensed: -10 °C
- Maximum Temperature Sensed: +60 °C



3761477 PT100

RS PRO PT100 RTD SENSOR, 3MM DIA, 150MM LONG, 4 WIRE, PROBE,

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 150 mm
- Probe Diameter: 3 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +500 °C
- Termination Type: Cable
- Cable Length: 1 m
- Probe Material: Stainless Steel



3971315 PT100

RS PRO PT100 RTD SENSOR, 3MM DIA, 250MM LONG, 4 WIRE, PROBE,

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 250 mm
- Probe Diameter: 3 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +500 °C
- Termination Type: Cable
- Cable Length: 1 m
- Probe Material: Stainless Steel



3971321 PT100

RS PRO PT100 RTD SENSOR, 6MM DIA, 150MM LONG, 4 WIRE, PROBE,

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 150 mm
- Probe Diameter: 6 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +250 °C
- Termination Type: Cable
- Cable Length: 1 m
- Probe Material: Stainless Steel



3971337 PT100

RS PRO PT100 RTD SENSOR, 1.5MM DIA, 15MM LONG, 2 WIRE, PROBE,

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 15 mm
- Probe Diameter: 1.5 mm
- Minimum Temperature Sensed: -200 °C
- Maximum Temperature Sensed: +650 °C
- Termination Type: Solder
- Probe Material: Ceramic
- Process Connection: Probe



3971595 PT100

RS PRO PT100 RTD SENSOR, 6MM DIA, 150MM LONG, 2 X 3 WIRE,

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 150 mm
- Probe Diameter: 6 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +250 °C
- Termination Type: Cable
- Cable Length: 1 m
- Probe Material: Stainless Steel



3971393 PT100

PT100 PROBE

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 60 mm
- Probe Diameter: 6 mm
- Minimum Temperature Sensed: -20 °C
- Maximum Temperature Sensed: +200 °C
- Termination Type: Cable
- Cable Length: 2.5 m
- Probe Material: Stainless Steel



4071387 PT100

RS PRO PT100 RTD SENSOR, 6MM DIA, 100MM LONG, 3 WIRE, G1/2,

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 100 mm
- Probe Diameter: 6 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +250 °C
- Termination Type: Connection Head
- Probe Material: Stainless Steel
- Process Connection: G1/2



4071624 PT100

RS PRO PT100 RTD SENSOR, 6MM DIA, 250MM LONG, 3 WIRE, G1/2,

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 250 mm
- Probe Diameter: 6 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +250 °C
- Termination Type: Connection Head
- Probe Material: Stainless Steel
- Process Connection: G1/2



4071630 PT100

RS PRO PT100 RTD SENSOR, 6MM DIA, 150MM LONG, 2 X 3 WIRE,

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 150 mm
- Probe Diameter: 6 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +500 °C
- Termination Type: Cable
- Cable Length: 1 m
- Probe Material: Stainless Steel



3971416 PT100

RS PRO PT100 RTD SENSOR, 6MM DIA, 150MM LONG, 4 WIRE, CLASS B

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 150 mm
- Probe Diameter: 6 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +200 °C
- Termination Type: Cable
- Cable Length: 1 m
- Probe Material: Stainless Steel



3971832 PT100

SENSOR, PRT, GENERAL PURPOSE, 6X50MM

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 50 mm
- Probe Diameter: 6 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +200 °C
- Termination Type: Cable
- Cable Length: 2 m
- Probe Material: Stainless Steel



4553968 PT100

RS PRO PT100 RTD SENSOR, 8MM DIA, 250MM LONG, 4 WIRE, G1/2,

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 250 mm
- Probe Diameter: 8 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +450 °C
- Termination Type: Connection Head
- Probe Material: Stainless Steel
- Process Connection: G1/2



4553980 PT100

RS PRO PT100 RTD SENSOR, 6MM DIA, 150MM LONG, 4 WIRE, G1/2,

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 150 mm
- Probe Diameter: 6 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +450 °C
- Termination Type: Connection Head
- Probe Material: Stainless Steel
- Process Connection: G1/2



4554040 PT100

RS PRO PT100 RTD SENSOR, 6MM DIA, 250MM LONG, 4 WIRE, G1/2,

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 250 mm
- Probe Diameter: 6 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +450 °C
- Termination Type: Connection Head
- Probe Material: Stainless Steel
- Process Connection: G1/2




4554056 PT100

RS PRO PT1000 RTD SENSOR, 2MM DIA, 5MM LONG, CHIP, CLASS B

Pack size: **1 x EA**

- Sensor Type: PT1000
- Probe Length: 5 mm
- Probe Diameter: 2 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +600 °C
- Termination Type: Solder
- Process Connection: Chip
- Accuracy: Class B



4573596 PT1000

CAPTEUR PT-1000

Pack size: **1 x EA**

- Sensor Type: PT1000
- Probe Length: 5 mm
- Probe Diameter: 2 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +600 °C
- Termination Type: Solder
- Process Connection: Chip
- Accuracy: Class A



4573603 PT1000

RS PRO PT100 RTD SENSOR, 12.7MM DIA, 75MM LONG, 2 X 4 WIRE, WALL,

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 75 mm
- Probe Diameter: 12.7 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +150 °C
- Termination Type: Cable Gland
- Probe Material: Stainless Steel
- Process Connection: Wall



4554208 PT100

BOX, OUTSIDE, AIR, 4-20MA

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 75 mm
- Probe Diameter: 12.7 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +150 °C
- Termination Type: Cable Gland
- Probe Material: Stainless Steel
- Process Connection: Wall



4554214 PT100

SONDE TYPE 109-06

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 10 mm
- Probe Diameter: 2 mm
- Minimum Temperature Sensed: 0 °C
- Maximum Temperature Sensed: +250 °C
- Termination Type: Cable
- Cable Length: 2 m
- Process Connection: Probe



4573625 PT100

SONDE DE TEMP. PT1000

Pack size: **1 x EA**

- Sensor Type: PT1000
- Probe Length: 35 mm
- Probe Diameter: 6 mm
- Minimum Temperature Sensed: -20 °C
- Maximum Temperature Sensed: +100 °C
- Termination Type: Cable
- Cable Length: 1 m
- Probe Material: Stainless Steel



4573653 PT1000

SONDE PT-100

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 60 mm
- Probe Diameter: 6 mm
- Minimum Temperature Sensed: -20 °C
- Maximum Temperature Sensed: +200 °C
- Termination Type: Cable
- Cable Length: 2.5 m
- Probe Material: Stainless Steel



4573704 PT100

RS PRO PT100 RTD SENSOR, 8MM DIA, 350MM LONG, 3 WIRE, G1/2,

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 350 mm
- Probe Diameter: 8 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +250 °C
- Termination Type: Connection Head
- Probe Material: Stainless Steel
- Process Connection: G1/2



5477590 PT100

SONDE PT-100

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 30 mm
- Probe Diameter: 3 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +250 °C
- Termination Type: Cable
- Cable Length: 2 m
- Probe Material: Stainless Steel



4573710 PT100

RS PRO PT100 RTD SENSOR, 6MM DIA, 300MM LONG, 3 WIRE, PROBE,

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 300 mm
- Probe Diameter: 6 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +250 °C
- Termination Type: Connection Head
- Probe Material: 316 Stainless Steel
- Process Connection: Probe



5477562 PT100

RS PRO PT100 RTD SENSOR, 8MM DIA, 250MM LONG, 3 WIRE, G1/2,

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 250 mm
- Probe Diameter: 8 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +250 °C
- Termination Type: Connection Head
- Probe Material: Stainless Steel
- Process Connection: G1/2



5477635 PT100

RS PRO PT100 RTD SENSOR, 8MM DIA, 50MM LONG, 3 WIRE, G1/2,

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 50 mm
- Probe Diameter: 8 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +250 °C
- Termination Type: Connection Head
- Probe Material: Stainless Steel
- Process Connection: G1/2



5477663 PT100

RS PRO PT100 RTD SENSOR, 8MM DIA, 100MM LONG, 3 WIRE, G1/2,

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 100 mm
- Probe Diameter: 8 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +250 °C
- Termination Type: Connection Head
- Probe Material: Stainless Steel
- Process Connection: G1/2



5477714 PT100

SENSOR,TEMPERATURE,THERMOCOUPLE,PLATINUM,THIN

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 5 mm
- Probe Diameter: 2 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +500 °C
- Termination Type: Solder
- Probe Material: Platinum
- Process Connection: Chip



6117801 PT100

RS PRO PT100 RTD SENSOR, 2.8MM DIA, 25MM LONG, PROBE, CLASS A

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 25 mm
- Probe Diameter: 2.8 mm
- Minimum Temperature Sensed: -200 °C
- Maximum Temperature Sensed: +650 °C
- Termination Type: Solder
- Probe Material: Platinum
- Process Connection: Probe



6117817 PT100

SENSOR,TEMPERATURE,THERMOCOUPLE,PLATINUM,THIN

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 5 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +500 °C
- Termination Type: Solder
- Probe Material: Platinum
- Process Connection: Chip
- Number Of Wires: 2



6117788 PT100

SENSOR,TEMPERATURE,SIMPLEX,PLATINUM,PT100,WIREWOUND,2

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 25 mm
- Probe Diameter: 2.8 mm
- Minimum Temperature Sensed: -200 °C
- Maximum Temperature Sensed: +650 °C
- Termination Type: Solder
- Probe Material: Platinum
- Process Connection: Probe



6117794 PT100

RS PRO PT100 RTD SENSOR, 2.8MM DIA, 15MM LONG, PROBE, CLASS B

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 15 mm
- Probe Diameter: 2.8 mm
- Minimum Temperature Sensed: -200 °C
- Maximum Temperature Sensed: +650 °C
- Termination Type: Solder
- Probe Material: Platinum
- Process Connection: Probe



6117823 PT100

SENSOR,TEMPERATURE,SIMPLEX,PLATINUM,PT100,WIREWOUND,2

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 15 mm
- Probe Diameter: 1.5 mm
- Minimum Temperature Sensed: -200 °C
- Maximum Temperature Sensed: +650 °C
- Termination Type: Solder
- Probe Material: Platinum
- Process Connection: Probe



6117839 PT100

RS PRO PT100 RTD SENSOR, 2.8MM DIA, 15MM LONG, PROBE, CLASS A

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 15 mm
- Probe Diameter: 2.8 mm
- Minimum Temperature Sensed: -200 °C
- Maximum Temperature Sensed: +650 °C
- Termination Type: Solder
- Probe Material: Platinum
- Process Connection: Probe



6117845 PT100

SENSOR,TEMPERATURE,SIMPLEX,PLATINUM,PT100,WIREWOUND,2

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 8 mm
- Probe Diameter: 1.5 mm
- Minimum Temperature Sensed: -200 °C
- Maximum Temperature Sensed: +650 °C
- Termination Type: Solder
- Probe Material: Platinum
- Process Connection: Probe



6117873 PT100

SENSOR,TEMPERATURE,SIMPLEX,PLATINUM,PT100,WIREWOUND,2

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 8 mm
- Probe Diameter: 1.5 mm
- Minimum Temperature Sensed: -200 °C
- Maximum Temperature Sensed: +650 °C
- Termination Type: Solder
- Probe Material: Platinum
- Process Connection: Probe



6117851 PT100

SENSOR,TEMPERATURE,SIMPLEX,PLATINUM,PT100,WIREWOUND,2

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 15 mm
- Probe Diameter: 1.5 mm
- Minimum Temperature Sensed: -200 °C
- Maximum Temperature Sensed: +650 °C
- Termination Type: Solder
- Probe Material: Platinum
- Process Connection: Probe



6117867 PT100

SENSOR,PRT,GENERAL PURPOSE,6X100MM

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 100 mm
- Probe Diameter: 6 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +200 °C
- Termination Type: Cable
- Cable Length: 2 m
- Probe Material: Stainless Steel



6118264 PT100

THIN FILM PT100 DETECT 1.6X1.2MM CLASS B

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 1.6 mm
- Probe Diameter: 1.2 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +500 °C
- Termination Type: Solder
- Probe Material: Platinum
- Process Connection: Chip



6667353 PT100

THIN FILM PT100 DETECTOR, 3X1MM, CLASS A

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 3 mm
- Probe Diameter: 1 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +500 °C
- Termination Type: Solder
- Probe Material: Platinum
- Process Connection: Chip



6667359 PT100

RS PRO PT1000 RTD SENSOR, 15MM DIA, 30MM LONG, 2 WIRE, PATCH

Pack size: **1 x EA**

- Sensor Type: PT1000
- Probe Length: 30 mm
- Probe Diameter: 15 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +150 °C
- Termination Type: Cable
- Cable Length: 1 m
- Probe Material: Aluminium Foil Backing, Silicone Rubber



7621130 PT1000

RS PRO PT100 RTD SENSOR, 1MM DIA, 3MM LONG, CHIP, CLASS B +500°C

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 3 mm
- Probe Diameter: 1 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +500 °C
- Termination Type: Solder
- Probe Material: Platinum
- Process Connection: Chip



6667356 PT100

THIN FILM PT100 DETECT 1.6X1.2MM CLASS A

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 1.6 mm
- Probe Diameter: 1.2 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +500 °C
- Termination Type: Solder
- Probe Material: Platinum
- Process Connection: Chip



6667362 PT100

PT100 PROBE 1MTR TEFLON LEAD

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 25 mm
- Probe Diameter: 3 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +200 °C
- Termination Type: Lead Wire
- Cable Length: 1 m
- Probe Material: Stainless Steel



7621134 PT100

RS PRO PT100 RTD SENSOR, 1.2MM DIA, CHIP, +500°C MAX

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Diameter: 1.2 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +500 °C
- Termination Type: Solder
- Process Connection: Chip



8140162 PT100

PT100 4 WIRE 5MTS TEFLON LEAD

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 40 mm
- Probe Diameter: 13 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +150 °C
- Termination Type: Lead Wire
- Cable Length: 5 m
- Probe Material: Aluminium Foil Backing, Silicone Rubber



7621137 PT100

PT100 PROBE 3.0X50MM B 1MTR TEFLON LEAD

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 50 mm
- Probe Diameter: 3 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +200 °C
- Termination Type: Lead Wire
- Cable Length: 1 m
- Probe Material: Stainless Steel



7621143 PT100

RS PRO PT100 RTD SENSOR, 1.2MM DIA, CHIP, +500°C MAX

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Diameter: 1.2 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +500 °C
- Termination Type: Solder
- Process Connection: Chip



8140165 PT100

RS PRO PT100 RTD SENSOR, 1.2MM DIA, CHIP, +500°C MAX

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Diameter: 1.2 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +500 °C
- Termination Type: Solder
- Process Connection: Chip




8140169 PT100

RS PRO PT1000 RTD SENSOR, 1.25MM DIA, CHIP, +500°C MAX

Pack size: **1 x EA**

- Sensor Type: PT1000
- Probe Diameter: 1.25 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +500 °C
- Termination Type: Solder
- Process Connection: Chip



8140175 PT1000

RS PRO PT1000 RTD SENSOR, 2MM DIA, CHIP, +500°C MAX

Pack size: **1 x EA**

- Sensor Type: PT1000
- Probe Diameter: 2 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +500 °C
- Termination Type: Solder
- Process Connection: Chip



8140178 PT1000

RS PRO PT100 RTD SENSOR, 6MM DIA, 150MM LONG, 3 WIRE, G1/2,

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 150 mm
- Probe Diameter: 6 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +450 °C
- Termination Type: Connection Head
- Probe Material: Stainless Steel
- Process Connection: G1/2



8722701 PT100

RS PRO PT100 RTD SENSOR, 6MM DIA, 150MM LONG, 3 WIRE, G1/2,

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 150 mm
- Probe Diameter: 6 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +450 °C
- Termination Type: Connection Head
- Probe Material: Stainless Steel
- Process Connection: G1/2



8722705 PT100

RS PRO PT100 RTD SENSOR, 6MM DIA, 100MM LONG, 4 WIRE, PROBE,

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 100 mm
- Probe Diameter: 6 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +450 °C
- Termination Type: Connection Head
- Probe Material: Stainless Steel
- Process Connection: Probe



8722717 PT100

RS PRO PT100 RTD SENSOR, 6MM DIA, 200MM LONG, 4 WIRE, PROBE,

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 200 mm
- Probe Diameter: 6 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +450 °C
- Termination Type: Connection Head
- Probe Material: Stainless Steel
- Process Connection: Probe



8722720 PT100

RS PRO PT100 RTD SENSOR, 6MM DIA, 250MM LONG, 4 WIRE, PROBE,

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 250 mm
- Probe Diameter: 6 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +450 °C
- Termination Type: Connection Head
- Probe Material: Stainless Steel
- Process Connection: Probe



8722723 PT100

RS PRO PT100 RTD SENSOR, 6MM DIA, 300MM LONG, 4 WIRE, PROBE,

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 300 mm
- Probe Diameter: 6 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +450 °C
- Termination Type: Connection Head
- Probe Material: Stainless Steel
- Process Connection: Probe



8722727 PT100

RS PRO PT100 RTD SENSOR, 6MM DIA, 150MM LONG, 4 WIRE, PROBE,

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 150 mm
- Probe Diameter: 6 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +450 °C
- Termination Type: Connection Head
- Probe Material: Stainless Steel
- Process Connection: Probe



8722739 PT100

RS PRO PT100 RTD SENSOR, 6MM DIA, 300MM LONG, 4 WIRE, CLASS B

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 300 mm
- Probe Diameter: 6 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +450 °C
- Termination Type: Connection Head
- Probe Material: Stainless Steel
- Number Of Wires: 4



8722745 PT100

RS PRO PT100 RTD SENSOR, 6MM DIA, 500MM LONG, ¼ WIRE, PROBE,

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 500 mm
- Probe Diameter: 6 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +450 °C
- Termination Type: Connection Head
- Probe Material: Stainless Steel
- Process Connection: Probe



8722749 PT100

PT100 2X10 CLASS B 300 MM LEADS, 7/0.2

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 10 mm
- Probe Diameter: 2 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +250 °C
- Termination Type: Lead Wire
- Cable Length: 300 mm
- Probe Material: Platinum



8919132 PT100

PT100 2X10 CLASS B 500 MM LEADS, 7/0.2

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 10 mm
- Probe Diameter: 2 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +250 °C
- Termination Type: Lead Wire
- Cable Length: 500 mm
- Probe Material: Platinum



8919135 PT100

PT100 2X10 CLASS B 1000 MM LEADS, 7/0.2

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 10 mm
- Probe Diameter: 2 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +250 °C
- Termination Type: Lead Wire
- Cable Length: 1 m
- Probe Material: Platinum



8919139 PT100

PT100 2X10 CLASS A 500 MM LEADS, 7/0.15

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 10 mm
- Probe Diameter: 2 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +250 °C
- Termination Type: Lead Wire
- Cable Length: 500 mm
- Probe Material: Platinum



8919141 PT100

PT100 2X10 CLASS A 1000 MM LEADS, 7/0.15

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 10 mm
- Probe Diameter: 2 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +250 °C
- Termination Type: Lead Wire
- Cable Length: 1 m
- Probe Material: Platinum



8919145 PT100

PT100 2X10 CLASS A 300 MM LEADS, 7/0.15

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 10 mm
- Probe Diameter: 2 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +250 °C
- Termination Type: Lead Wire
- Cable Length: 300 mm
- Probe Material: Platinum



8919148 PT100

PT1000 2X10 CLASS B 1000 MM LEADS, 7/0.2

Pack size: **1 x EA**

- Sensor Type: PT1000
- Probe Length: 10 mm
- Probe Diameter: 2 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +250 °C
- Termination Type: Lead Wire
- Cable Length: 1 m
- Probe Material: Platinum



8919151 PT1000

PT1000 2X10 CLASS B 300 MM LEADS, 7/0.2

Pack size: **1 x EA**

- Sensor Type: PT1000
- Probe Length: 10 mm
- Probe Diameter: 2 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +250 °C
- Termination Type: Lead Wire
- Cable Length: 300 mm
- Probe Material: Platinum



8919154 PT1000

PT1000 2X10 CLASS B 500 MM LEADS, 7/0.2

Pack size: **1 x EA**

- Sensor Type: PT1000
- Probe Length: 10 mm
- Probe Diameter: 2 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +250 °C
- Termination Type: Lead Wire
- Cable Length: 500 mm
- Probe Material: Platinum



8919157 PT1000

PT100/1528 CLASS B 1000 MM LEADS, 1/0.4

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 15 mm
- Probe Diameter: 2.8 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +350 °C
- Termination Type: Lead Wire
- Cable Length: 1 m
- Probe Material: Platinum



8919163 PT100

RS PRO PT100 RTD SENSOR, 5MM DIA, 50MM LONG, +100°C MAX

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 50 mm
- Probe Diameter: 5 mm
- Minimum Temperature Sensed: -20 °C
- Maximum Temperature Sensed: +100 °C
- Termination Type: Cable
- Cable Length: 1.5 m
- Probe Material: Stainless Steel



8968395 PT100

RTD 5X50 PT1000 2 WIRES CABLE LG 1,5M

Pack size: **1 x EA**

- Sensor Type: PT1000
- Probe Length: 50 mm
- Probe Diameter: 5 mm
- Minimum Temperature Sensed: -20 °C
- Maximum Temperature Sensed: +100 °C
- Termination Type: Cable
- Cable Length: 1.5 m
- Probe Material: Stainless Steel



8968399 PT1000

RTD 1XPT100 6X200 HEAD/SLIDING FITTING

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 200 mm
- Probe Diameter: 6 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +250 °C
- Termination Type: Connection Head
- Probe Material: Stainless Steel
- Process Connection: G1/4



8968406 PT100

RTD 1XPT100 5X120 HEAD/ THERMOWELL

Pack size: **1 x EA**

- Sensor Type: PT100
- Probe Length: 120 mm
- Probe Diameter: 5.7 mm
- Minimum Temperature Sensed: -50 °C
- Maximum Temperature Sensed: +250 °C
- Termination Type: Connection Head
- Probe Material: Stainless Steel
- Process Connection: G1/2



8968415 PT100

GLAND, COMPRESSION, STAINLESS STEEL, 1/8 BSP, 3.0MM DIA BORE

Pack size: **1 x EA**

- Accessory Type: Thermocouple Compression Fitting
- For Use With: Thermocouple
- Application: 1/8 BSPT Connector
- Connector Size: 1/8 BSPT
- Probe Diameter: 3 mm
- Standards Met: RoHS Compliant



158610 Thermocouple

RS PRO THERMOCOUPLE COMPRESSION FITTING FOR USE

Pack size: **1 x EA**

- Accessory Type: Thermocouple Compression Fitting
- For Use With: Thermocouple
- Application: 1/8 BSPT Connector
- Connector Size: 1/8 BSPT
- Probe Diameter: 1.5 mm
- Standards Met: RoHS Compliant



286715 Thermocouple

RS PRO THERMOCOUPLE COMPRESSION FITTING FOR USE

Pack size: **1 x EA**

- Accessory Type: Thermocouple Compression Fitting
- For Use With: Thermocouple
- Application: 1/8 BSPT Connector
- Connector Size: 1/8 BSPT
- Probe Diameter: 3 mm
- Standards Met: RoHS Compliant



286721 Thermocouple

RS PRO THERMOCOUPLE COMPRESSION FITTING FOR USE

Pack size: **1 x EA**

- Accessory Type: Thermocouple Compression Fitting
- For Use With: Thermocouple
- Application: 1/8 BSPT Connector
- Connector Size: 1/8 BSPT
- Probe Diameter: 4.5 mm
- Standards Met: RoHS Compliant



286737 Thermocouple

RS PRO THERMOCOUPLE COMPRESSION FITTING FOR USE

Pack size: **1 x EA**

- Accessory Type: Thermocouple Compression Fitting
- For Use With: Thermocouple
- Application: 1/2 BSPT Connector
- Connector Size: 1/2 BSPT
- Probe Diameter: 6 mm
- Standards Met: RoHS Compliant



286771 Thermocouple

RS PRO THERMOCOUPLE COMPRESSION FITTING FOR USE

Pack size: **1 x EA**

- Accessory Type: Thermocouple Compression Fitting
- For Use With: Thermocouple
- Application: 1/2 BSPT Connector
- Connector Size: 1/2 BSPT
- Probe Diameter: 4.5 mm
- Standards Met: RoHS Compliant



286787 Thermocouple

RS PRO THERMOCOUPLE FLANGE FOR USE WITH TEMPERATURE

Pack size: **1 x EA**

- Accessory Type: Thermocouple Flange
- For Use With: Temperature Sensor
- Application: 1/8 BSP Flange
- Connector Size: 1/8 BSP
- Mounting Type: Chassis Mount
- Standards Met: RoHS Compliant



286816 Thermocouple

RS PRO BAYONET ADAPTER FOR USE WITH TEMPERATURE SENSOR, 1/8

Pack size: **1 x EA**

- Accessory Type: Bayonet Adapter
- For Use With: Temperature Sensor
- Application: 1/8 BSP Connector
- Connector Size: 1/8 BSP
- Probe Diameter: 6 mm
- Standards Met: RoHS Compliant



286866 Bayonet Adapter

RS PRO THERMOCOUPLE COMPRESSION FITTING FOR USE

Pack size: **1 x EA**

- Accessory Type: Thermocouple Compression Fitting
- For Use With: Thermocouple
- Application: 1/2 BSPT Connector
- Connector Size: 1/2 BSPT
- Probe Diameter: 6 mm
- Standards Met: RoHS Compliant



286793 Thermocouple

RS PRO BAYONET ADAPTER FOR USE WITH TEMPERATURE SENSOR, 1/8

Pack size: **1 x EA**

- Accessory Type: Bayonet Adapter
- For Use With: Temperature Sensor
- Application: 1/8 BSP Connector
- Connector Size: 1/8 BSP
- Standards Met: RoHS Compliant



286872 Bayonet Adapter

RS PRO BAYONET ADAPTER FOR USE WITH TEMPERATURE SENSOR, 1/8

Pack size: **1 x EA**

- Accessory Type: Bayonet Adapter
- For Use With: Temperature Sensor
- Application: 1/8 BSP Connector
- Connector Size: 1/8 BSP
- Standards Met: RoHS Compliant



286888 Bayonet Adapter

RS PRO BAYONET ADAPTER FOR USE WITH TEMPERATURE SENSOR, 1/8

Pack size: **1 x EA**

- Accessory Type: Bayonet Adapter
- For Use With: Temperature Sensor
- Application: 1/8 BSP Connector
- Connector Size: 1/8 BSP
- Standards Met: RoHS Compliant



286894 Bayonet Adapter

RS PRO BAYONET ADAPTER FOR USE WITH TEMPERATURE SENSOR, 1/8

Pack size: **1 x EA**

- Accessory Type: Bayonet Adapter
- For Use With: Temperature Sensor
- Application: 1/8 BSP Connector
- Connector Size: 1/8 BSP
- Probe Diameter: 6 mm
- Standards Met: RoHS Compliant



286901 Bayonet Adapter

RS PRO BAYONET ADAPTER FOR USE WITH TEMPERATURE SENSOR, M10,

Pack size: **1 x EA**

- Accessory Type: Bayonet Adapter
- For Use With: Temperature Sensor
- Application: M10 Connector
- Connector Size: M10
- Standards Met: RoHS Compliant



286917 Bayonet Adapter

RS PRO PANEL MOUNT THERMOCOUPLE CONNECTOR FOR

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type J Thermocouple
- Application: Standard Panel Mount Connector
- Connector Type: Panel Mount
- Plug/Socket: Socket
- Connector Size: Standard
- Mounting Type: Nylon Clip
- Standards Met: BS



475583 Thermocouple

RS PRO THERMOCOUPLE COMPRESSION FITTING FOR USE

Pack size: **1 x EA**

- Accessory Type: Thermocouple Compression Fitting
- For Use With: Thermocouple
- Application: 1/8 BSPT Connector
- Connector Size: 1/8 BSPT
- Probe Diameter: 1/4 in
- Standards Met: RoHS Compliant



1104475 Thermocouple

RS PRO THERMOCOUPLE COMPRESSION FITTING FOR USE

Pack size: **1 x EA**

- Accessory Type: Thermocouple Compression Fitting
- For Use With: Thermocouple
- Application: 1/8 BSP Connector
- Connector Size: 1/8 BSP
- Probe Diameter: 1/4 in
- Standards Met: RoHS Compliant



1104476 Thermocouple

**RS PRO IN-LINE THERMOCOUPLE
COMPRESSION FITTING FOR USE**

- Pack size: **1 x EA**
- Accessory Type: Thermocouple Compression Fitting
 - For Use With: Thermocouple
 - Application: 1/2 NPT In-Line Connector
 - Connector Type: In-Line
 - Connector Size: 1/2 NPT
 - Probe Diameter: 4.5 mm
 - Standards Met: RoHS Compliant



1235577 Thermocouple

**RS PRO IN-LINE THERMOCOUPLE
COMPRESSION FITTING FOR USE**

- Pack size: **1 x EA**
- Accessory Type: Thermocouple Compression Fitting
 - For Use With: Thermocouple
 - Application: 1/2 NPT In-Line Connector
 - Connector Type: In-Line
 - Connector Size: 1/2 NPT
 - Probe Diameter: 6 mm
 - Standards Met: RoHS Compliant



1235578 Thermocouple

**RS PRO IN-LINE THERMOCOUPLE
COMPRESSION FITTING FOR USE**

- Pack size: **1 x EA**
- Accessory Type: Thermocouple Compression Fitting
 - For Use With: Thermocouple
 - Application: 1/2 NPT In-Line Connector
 - Connector Type: In-Line
 - Connector Size: 1/2 NPT
 - Standards Met: RoHS Compliant



1235579 Thermocouple

**RS PRO IN-LINE THERMOCOUPLE
COMPRESSION FITTING FOR USE**

- Pack size: **1 x EA**
- Accessory Type: Thermocouple Compression Fitting
 - For Use With: Thermocouple
 - Application: 1/2 NPT In-Line Connector
 - Connector Type: In-Line
 - Connector Size: 1/2 NPT
 - Probe Diameter: 1/4 in
 - Standards Met: RoHS Compliant



1235582 Thermocouple

**RS PRO STAINLESS STEEL
COMPRESSION FITTING FOR USE**

- Pack size: **1 x EA**
- Accessory Type: Stainless Steel Compression Fitting
 - For Use With: 2 mm Diameter Thermocouple Probe
 - Application: 1/8 in BSP Connector
 - Connection Gender: Male



1314765 Stainless Steel

**RS PRO STAINLESS STEEL
COMPRESSION FITTING FOR USE**

- Pack size: **1 x EA**
- Accessory Type: Stainless Steel Compression Fitting
 - For Use With: 2 mm Diameter Thermocouple Probe
 - Application: 1/8 in BSP Connector
 - Connection Gender: Male



1314766 Stainless Steel

**RS PRO IN-LINE THERMOCOUPLE
COMPRESSION FITTING FOR USE**

- Pack size: **1 x EA**
- Accessory Type: Thermocouple Compression Fitting
 - For Use With: 3 mm Probe Thermocouple
 - Application: 1/8 NPT In-Line Connector
 - Connector Type: In-Line
 - Plug/Socket: Plug
 - Connector Size: 1/8 NPT
 - Standards Met: RoHS Compliant



1365852 Thermocouple

**RS PRO IN-LINE THERMOCOUPLE
COMPRESSION FITTING FOR USE**

- Pack size: **1 x EA**
- Accessory Type: Thermocouple Compression Fitting
 - For Use With: 3 mm Probe Thermocouple
 - Application: 1/4 NPT In-Line Connector
 - Connector Type: In-Line
 - Plug/Socket: Plug
 - Connector Size: 1/4 NPT
 - Standards Met: RoHS Compliant



1365854 Thermocouple

**RS PRO IN-LINE THERMOCOUPLE
COMPRESSION FITTING FOR USE**

- Pack size: **1 x EA**
- Accessory Type: Thermocouple Compression Fitting
 - For Use With: 6 mm Probe Thermocouple
 - Application: 1/4 NPT In-Line Connector
 - Connector Type: In-Line
 - Plug/Socket: Plug
 - Connector Size: 1/4 NPT
 - Standards Met: RoHS Compliant



1365855 Thermocouple

**RS PRO IN-LINE THERMOCOUPLE
COMPRESSION FITTING FOR USE**

- Pack size: **1 x EA**
- Accessory Type: Thermocouple Compression Fitting
 - For Use With: 1.5 mm Probe Thermocouple
 - Application: M8 In-Line Connector
 - Connector Type: In-Line
 - Connector Size: M8
 - Standards Met: RoHS Compliant



1365857 Thermocouple

**RS PRO IN-LINE THERMOCOUPLE
COMPRESSION FITTING FOR USE**

- Pack size: **1 x EA**
- Accessory Type: Thermocouple Compression Fitting
 - For Use With: 3 mm Probe Thermocouple
 - Application: M8 In-Line Connector
 - Connector Type: In-Line
 - Connector Size: M8
 - Standards Met: RoHS Compliant



1365859 Thermocouple

**RS PRO THERMOWELL FOR USE WITH
TEMPERATURE PROBE, 1/2 BSP, 3 MM,**

- Pack size: **1 x EA**
- Accessory Type: Thermowell
 - For Use With: Temperature Probe
 - Application: 1/2 BSP Connector
 - Plug/Socket: Plug
 - Connector Size: M8
 - Probe Diameter: 3 mm, 8 (Pocket) mm



1780953 Thermowell

**RS PRO THERMOWELL FOR USE WITH
TEMPERATURE PROBE, 1/2 BSP, 3 MM,**

- Pack size: **1 x EA**
- Accessory Type: Thermowell
 - For Use With: Temperature Probe
 - Application: 1/2 BSP Connector
 - Plug/Socket: Plug
 - Connector Size: 1/2 BSP
 - Probe Diameter: 3 mm, 8 (Pocket) mm



1780954 Thermowell

**RS PRO THERMOWELL FOR USE WITH
TEMPERATURE PROBE, 1/2 BSP, 6MM**

- Pack size: **1 x EA**
- Accessory Type: Thermowell
 - For Use With: Temperature Probe
 - Application: 1/2 BSP Connector
 - Plug/Socket: Plug
 - Connector Size: 1/2 BSP
 - Probe Diameter: 6 mm



1780956 Thermowell

**RS PRO THERMOWELL FOR USE WITH
TEMPERATURE PROBE, 1/2 BSP, 6 MM,**

- Pack size: **1 x EA**
- Accessory Type: Thermowell
 - For Use With: Temperature Probe
 - Application: 1/2 BSP Connector
 - Plug/Socket: Plug
 - Connector Size: 1/2 BSP
 - Probe Diameter: 6 mm, 11.1 (Pocket) mm



1780957 Thermowell

**RS PRO THERMOWELL FOR USE WITH
TEMPERATURE PROBE, 1/2 BSP, 6 MM,**

- Pack size: **1 x EA**
- Accessory Type: Thermowell
 - For Use With: Temperature Probe
 - Application: 1/2 BSP Connector
 - Plug/Socket: Plug
 - Connector Size: 1/2 BSP
 - Probe Diameter: 6 mm, 11.1 (Pocket) mm



1780958 Thermowell

RS PRO IN-LINE THERMOCOUPLE COMPRESSION FITTING FOR USE

Pack size: **1 x EA**

- Accessory Type: Thermocouple Compression Fitting
- For Use With: Thermocouple
- Application: 1/4 BSP In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Plug
- Connector Size: 1/4 BSP
- Probe Diameter: 1.5 mm



1780960 Thermocouple

RS PRO IN-LINE THERMOCOUPLE COMPRESSION FITTING FOR USE

Pack size: **1 x EA**

- Accessory Type: Thermocouple Compression Fitting
- For Use With: Thermocouple
- Application: 1/4 BSP In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Plug
- Connector Size: 1/4 BSP
- Probe Diameter: 3 mm



1780961 Thermocouple

RS PRO IN-LINE THERMOCOUPLE COMPRESSION FITTING FOR USE

Pack size: **1 x EA**

- Accessory Type: Thermocouple Compression Fitting
- For Use With: Thermocouple
- Application: 1/8 BSPT In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Plug
- Connector Size: 1/8 BSPT
- Probe Diameter: 3 mm



1780963 Thermocouple

RS PRO IN-LINE THERMOCOUPLE COMPRESSION FITTING FOR USE

Pack size: **1 x EA**

- Accessory Type: Thermocouple Compression Fitting
- For Use With: Thermocouple
- Application: 1/4 BSPT In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Plug
- Connector Size: 1/4 BSPT
- Probe Diameter: 4 mm



1780965 Thermocouple

RS PRO IN-LINE THERMOCOUPLE COMPRESSION FITTING FOR USE

Pack size: **1 x EA**

- Accessory Type: Thermocouple Compression Fitting
- For Use With: Thermocouple
- Application: M8 In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Plug
- Connector Size: M8
- Probe Diameter: 4 mm



1780966 Thermocouple

RS PRO IN-LINE THERMOCOUPLE COMPRESSION FITTING FOR USE

Pack size: **1 x EA**

- Accessory Type: Thermocouple Compression Fitting
- For Use With: Thermocouple
- Application: M8 In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Plug
- Connector Size: M8
- Probe Diameter: 4.5 mm



1780967 Thermocouple

RS PRO IN-LINE THERMOCOUPLE COMPRESSION FITTING FOR USE

Pack size: **1 x EA**

- Accessory Type: Thermocouple Compression Fitting
- For Use With: Thermocouple
- Application: M8 In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Plug
- Connector Size: M8
- Probe Diameter: 4.7625 mm



1780969 Thermocouple

RS PRO IN-LINE THERMOCOUPLE COMPRESSION FITTING FOR USE

Pack size: **1 x EA**

- Accessory Type: Thermocouple Compression Fitting
- For Use With: Thermocouple
- Application: 1/8 NPT In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Plug
- Connector Size: 1/8 NPT
- Probe Diameter: 2 mm



1780973 Thermocouple

RS PRO BAYONET ADAPTER FOR USE WITH BAYONET CAP STYLE

Pack size: **1 x EA**

- Accessory Type: Bayonet Adapter
- For Use With: Bayonet Cap Style Thermocouples
- Application: Single Pair Connector
- Connector Size: Single Pair



2000617 Bayonet Adapter

RS PRO FASCIA THERMOCOUPLE CONNECTOR FOR USE WITH TYPE K

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type K Thermocouple
- Application: Standard Panel Mount Connector
- Connector Type: Fascia
- Plug/Socket: Socket
- Connector Size: Standard
- Mounting Type: Nylon Clip
- Standards Met: IEC



2194949 Thermocouple

RS PRO FASCIA THERMOCOUPLE CONNECTOR FOR USE WITH TYPE T

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type T Thermocouple
- Application: Standard Panel Mount Connector
- Connector Type: Fascia
- Plug/Socket: Socket
- Connector Size: Standard
- Mounting Type: Nylon Clip
- Standards Met: IEC



2194977 Thermocouple

RS PRO FASCIA THERMOCOUPLE CONNECTOR FOR USE WITH TYPE J

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type J Thermocouple
- Application: Standard Panel Mount Connector
- Connector Type: Fascia
- Plug/Socket: Socket
- Connector Size: Standard
- Mounting Type: Nylon Clip
- Standards Met: IEC



2195009 Thermocouple

RS PRO FASCIA THERMOCOUPLE CONNECTOR FOR USE WITH TYPE R/S

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type R/S Thermocouple
- Application: Standard Panel Mount Connector
- Connector Type: Fascia
- Plug/Socket: Socket
- Connector Size: Standard
- Mounting Type: Nylon Clip
- Standards Met: IEC



2195037 Thermocouple

RS PRO THERMOCOUPLE CONNECTOR FOR USE WITH

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Thermocouple
- Application: Miniature In-Line Connector
- Connection Gender: Male-Female
- Plug/Socket: Plug & Socket
- Connector Size: Miniature
- Standards Met: ANSI



2209519 Thermocouple

RS PRO THERMOCOUPLE CONNECTOR FOR USE WITH

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Thermocouple
- Application: Standard In-Line Connector
- Connection Gender: Male-Female
- Plug/Socket: Plug & Socket
- Connector Size: Standard
- Standards Met: ANSI



2209520 Thermocouple

RS PRO DUPLEX THERMOCOUPLE CONNECTOR FOR USE WITH TYPE J

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type J Thermocouple
- Application: Standard Duplex Connector
- Connector Type: Duplex
- Plug/Socket: Plug
- Connector Size: Standard
- Standards Met: IEC



2364081 Thermocouple

RS PRO THERMOCOUPLE CLAMP FOR USE WITH MINIATURE

Pack size: **1 x EA**

- Accessory Type: Thermocouple Clamp
- For Use With: Miniature Thermocouple Connector
- Mounting Type: Chassis Mount
- Standards Met: RoHS Compliant



2364104 Thermocouple

RS PRO THERMOCOUPLE CLAMP FOR USE WITH STANDARD

Pack size: **1 x EA**

- Accessory Type: Thermocouple Clamp
- For Use With: Thermocouple Connector
- Mounting Type: Chassis Mount
- Standards Met: RoHS Compliant



2364110 Thermocouple

RS PRO THERMOCOUPLE PANEL FOR USE WITH MINIATURE SOCKET,

Pack size: **1 x EA**

- Accessory Type: Thermocouple Panel
- For Use With: Miniature Socket
- Application: Miniature Faceplate
- Connector Size: Miniature
- Mounting Type: Flange Mount
- Standards Met: RoHS Compliant



2364132 Thermocouple

RS PRO THERMOCOUPLE PANEL FOR USE WITH STANDARD SOCKET,

Pack size: **1 x EA**

- Accessory Type: Thermocouple Panel
- For Use With: Standard Socket
- Application: Standard Faceplate
- Connector Size: Standard
- Mounting Type: Flange Mount
- Standards Met: RoHS Compliant



2364148 Thermocouple

RS PRO THERMOCOUPLE PANEL FOR USE WITH STANDARD SOCKET,

Pack size: **1 x EA**

- Accessory Type: Thermocouple Panel
- For Use With: Standard Socket
- Application: Standard Faceplate
- Connector Size: Standard
- Mounting Type: Flange Mount
- Standards Met: RoHS Compliant



2364154 Thermocouple

RS PRO THERMOCOUPLE SPADE LUG FOR USE WITH TYPE K

Pack size: **1 x EA**

- Accessory Type: Thermocouple Spade Lug
- For Use With: Type K Thermocouple
- Application: Connector
- Standards Met: RoHS Compliant



2364160 Thermocouple

RS PRO BARRIER TERMINAL THERMOCOUPLE TERMINAL BLOCK

Pack size: **1 x EA**

- Accessory Type: Thermocouple Terminal Block
- For Use With: Type J Thermocouple
- Application: Single Pair Barrier Terminal
- Connector Type: Barrier Terminal
- Plug/Socket: Socket
- Connector Size: Single Pair
- Standards Met: IEC



2364198 Thermocouple

RS PRO BARRIER TERMINAL THERMOCOUPLE TERMINAL BLOCK

Pack size: **1 x EA**

- Accessory Type: Thermocouple Terminal Block
- For Use With: Type K Thermocouple
- Application: Single Pair Barrier Terminal
- Connector Type: Barrier Terminal
- Plug/Socket: Socket
- Connector Size: Single Pair
- Standards Met: IEC



2364205 Thermocouple

THERMO,PADS,SHEET X20

Pack size: **1 x EA**

- Accessory Type: Self-adhesive Thermocouple Thermopads
- For Use With: Welded Tip Thermocouple
- Standards Met: IEC



2905058 Self-adhesive

RS PRO THERMOCOUPLE CLAMP FOR USE WITH THERMOCOUPLE

Pack size: **1 x EA**

- Accessory Type: Thermocouple Clamp
- For Use With: Thermocouple Connectors
- Mounting Type: Chassis Mount
- Standards Met: RoHS Compliant



3139987 Thermocouple

RS PRO BAYONET ADAPTER FOR USE WITH TEMPERATURE SENSOR, M12,

Pack size: **1 x EA**

- Accessory Type: Bayonet Adapter
- For Use With: Temperature Sensor
- Application: M12 Connector
- Connector Size: M12
- Standards Met: RoHS Compliant



3242128 Bayonet Adapter

RS PRO BAYONET ADAPTER FOR USE WITH TEMPERATURE SENSOR, 1/4

Pack size: **1 x EA**

- Accessory Type: Bayonet Adapter
- For Use With: Temperature Sensor
- Application: 1/4 GCY Connector
- Connector Size: 1/4 GCY
- Standards Met: RoHS Compliant



3242162 Bayonet Adapter

RS PRO BAYONET ADAPTER FOR USE WITH TEMPERATURE SENSOR, M10,

Pack size: **1 x EA**

- Accessory Type: Bayonet Adapter
- For Use With: Temperature Sensor
- Application: M10 Connector
- Connector Size: M10
- Standards Met: RoHS Compliant



3242184 Bayonet Adapter

RS PRO BAYONET ADAPTER FOR USE WITH TEMPERATURE SENSOR, M12,

Pack size: **1 x EA**

- Accessory Type: Bayonet Adapter
- For Use With: Temperature Sensor
- Application: M12 Connector
- Connector Size: M12
- Standards Met: RoHS Compliant



3242314 Bayonet Adapter

RS PRO THERMOCOUPLE COMPRESSION FITTING FOR USE

Pack size: **1 x EA**

- Accessory Type: Thermocouple Compression Fitting
- For Use With: Thermocouple
- Application: M6 Connector
- Connector Size: M6
- Probe Diameter: 1 mm
- Standards Met: RoHS Compliant



3342795 Thermocouple

RS PRO THERMOWELL FOR USE WITH TEMPERATURE SENSOR, 1/2 BSP,

Pack size: **1 x EA**

- Accessory Type: Thermowell
- For Use With: Temperature Sensor
- Application: 1/2 BSP Connector
- Connector Size: 1/2 BSP
- Mounting Type: Threaded
- Probe Diameter: 6 mm
- Standards Met: RoHS Compliant



3389508 Thermowell

RS PRO FASCIA THERMOCOUPLE CONNECTOR FOR USE WITH

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Temperature Sensor
- Application: Standard Panel Mount Connector
- Connector Type: Fascia
- Plug/Socket: Socket
- Connector Size: Standard
- Mounting Type: Nylon Clip
- Standards Met: IEC



3629783 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE J

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type J Thermocouple
- Application: Standard Quickwire Connector
- Connector Type: Quickwire
- Plug/Socket: Plug
- Connector Size: Standard
- Standards Met: IEC



3629963 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE J

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type J Thermocouple
- Application: Standard Quickwire Connector
- Connector Type: Quickwire
- Plug/Socket: Socket
- Connector Size: Standard
- Standards Met: IEC



3629979 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE K

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type K Thermocouple
- Application: Standard Quickwire Connector
- Connector Type: Quickwire
- Plug/Socket: Plug
- Connector Size: Standard
- Standards Met: IEC



3629991 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE K

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type K Thermocouple
- Application: Standard Quickwire Connector
- Connector Type: Quickwire
- Plug/Socket: Socket
- Connector Size: Standard
- Standards Met: IEC



3630008 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE T

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type T Thermocouple
- Application: Standard Quickwire Connector
- Connector Type: Quickwire
- Plug/Socket: Socket
- Connector Size: Standard
- Standards Met: IEC



3630020 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE N

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type N Thermocouple
- Application: Standard Quickwire Connector
- Connector Type: Quickwire
- Plug/Socket: Socket
- Connector Size: Standard
- Standards Met: IEC



3630042 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE R/S

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type R/S Thermocouple
- Application: Standard Quickwire Connector
- Connector Type: Quickwire
- Plug/Socket: Plug
- Connector Size: Standard
- Standards Met: IEC



3630058 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE R/S

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type R/S Thermocouple
- Application: Standard Quickwire Connector
- Connector Type: Quickwire
- Plug/Socket: Socket
- Connector Size: Standard
- Standards Met: IEC



3630064 Thermocouple

RS PRO HIGH TEMPERATURE THERMOCOUPLE CONNECTOR FOR

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type K Thermocouple
- Application: Standard In-Line Connector
- Connector Type: High Temperature Plastic
- Plug/Socket: Plug
- Connector Size: Standard
- Standards Met: IEC



3630137 Thermocouple

RS PRO HIGH TEMPERATURE THERMOCOUPLE CONNECTOR FOR

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type K Thermocouple
- Application: Standard In-Line Connector
- Connector Type: High Temperature Plastic
- Plug/Socket: Socket
- Connector Size: Standard
- Standards Met: IEC



3630159 Thermocouple

RS PRO STRAIGHT FEMALE/MALE THERMOCOUPLE EXTENSION CABLE

Pack size: **1 x EA**

- Accessory Type: Thermocouple Extension Cable
- For Use With: Type K Thermocouple
- Application: Straight Female/Male Connector
- Connector Type: Straight Female/Male
- Plug/Socket: Plug & Socket
- Standards Met: RoHS Compliant



3706149 Thermocouple

RS PRO THERMOCOUPLE COMPRESSION FITTING FOR USE

Pack size: **1 x EA**

- Accessory Type: Thermocouple Compression Fitting
- For Use With: Thermocouple
- Application: 1/8 BSPP Connector
- Connector Size: 1/8 BSPP
- Probe Diameter: 3 mm
- Standards Met: RoHS Compliant



3817277 Thermocouple

RS PRO THERMOCOUPLE COMPRESSION FITTING FOR USE

Pack size: **1 x EA**

- Accessory Type: Thermocouple Compression Fitting
- For Use With: Thermocouple
- Application: 1/4 BSPT Connector
- Connector Size: 1/4 BSPT
- Probe Diameter: 3 mm
- Standards Met: RoHS Compliant



3817283 Thermocouple

RS PRO THERMOCOUPLE COMPRESSION FITTING FOR USE

Pack size: **1 x EA**

- Accessory Type: Thermocouple Compression Fitting
- For Use With: Thermocouple
- Application: 1/4 BSPP Connector
- Connector Size: 1/4 BSPP
- Probe Diameter: 3 mm
- Standards Met: RoHS Compliant



3817306 Thermocouple

RS PRO THERMOCOUPLE COMPRESSION FITTING FOR USE

Pack size: **1 x EA**

- Accessory Type: Thermocouple Compression Fitting
- For Use With: Thermocouple
- Application: 1/8 BSPP Connector
- Connector Size: 1/8 BSPP
- Probe Diameter: 1.5 mm
- Standards Met: RoHS Compliant



3817334 Thermocouple

RS PRO THERMOCOUPLE COMPRESSION FITTING FOR USE

Pack size: **1 x EA**

- Accessory Type: Thermocouple Compression Fitting
- For Use With: Thermocouple
- Application: 1/8 BSPP Connector
- Connector Size: 1/8 BSPP
- Probe Diameter: 3 mm
- Standards Met: RoHS Compliant



3817340 Thermocouple

RS PRO THERMOCOUPLE COMPRESSION FITTING FOR USE

Pack size: **1 x EA**

- Accessory Type: Thermocouple Compression Fitting
- For Use With: Thermocouple
- Application: 1/8 BSPP Connector
- Connector Size: 1/8 BSPP
- Probe Diameter: 6 mm
- Standards Met: RoHS Compliant



3817356 Thermocouple

RS PRO THERMOCOUPLE COMPRESSION FITTING FOR USE

Pack size: **1 x EA**

- Accessory Type: Thermocouple Compression Fitting
- For Use With: Thermocouple
- Application: 1/4 BSPP Connector
- Connector Size: 1/4 BSPP
- Probe Diameter: 3 mm
- Standards Met: RoHS Compliant



3817362 Thermocouple

RS PRO THERMOCOUPLE COMPRESSION FITTING FOR USE

Pack size: **1 x EA**

- Accessory Type: Thermocouple Compression Fitting
- For Use With: Thermocouple
- Application: 1/4 BSPP Connector
- Connector Size: 1/4 BSPP
- Probe Diameter: 6 mm
- Standards Met: RoHS Compliant



3817378 Thermocouple

RS PRO THERMOCOUPLE COMPRESSION FITTING FOR USE

Pack size: **1 x EA**

- Accessory Type: Thermocouple Compression Fitting
- For Use With: Thermocouple
- Application: 1/4 BSPT Connector
- Connector Size: 1/4 BSPT
- Probe Diameter: 3 mm
- Standards Met: RoHS Compliant



3817384 Thermocouple

RS PRO THERMOCOUPLE COMPRESSION FITTING FOR USE

Pack size: **1 x EA**

- Accessory Type: Thermocouple Compression Fitting
- For Use With: Thermocouple
- Application: 1/4 BSPT Connector
- Connector Size: 1/4 BSPT
- Probe Diameter: 6 mm
- Standards Met: RoHS Compliant



3817390 Thermocouple

RS PRO THERMOCOUPLE COMPRESSION FITTING FOR USE

Pack size: **1 x EA**

- Accessory Type: Thermocouple Compression Fitting
- For Use With: Thermocouple
- Application: 1/2 BSPP Connector
- Connector Size: 1/2 BSPP
- Probe Diameter: 6 mm
- Standards Met: RoHS Compliant



3817407 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE J

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type J Thermocouple
- Application: Miniature Quickwire Connector
- Connector Type: Quickwire
- Plug/Socket: Plug
- Connector Size: Miniature
- Standards Met: IEC



3817413 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE J

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type J Thermocouple
- Application: Miniature Quickwire Connector
- Connector Type: Quickwire
- Plug/Socket: Socket
- Connector Size: Miniature
- Standards Met: IEC



3817429 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE K

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type K Thermocouple
- Application: Miniature Quickwire Connector
- Connector Type: Quickwire
- Plug/Socket: Plug
- Connector Size: Miniature
- Standards Met: IEC



3817435 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE K

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type K Thermocouple
- Application: Miniature Quickwire Connector
- Connector Type: Quickwire
- Plug/Socket: Socket
- Connector Size: Miniature
- Standards Met: IEC



3817441 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE T

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type T Thermocouple
- Application: Standard Quickwire Connector
- Connector Type: Quickwire
- Plug/Socket: Plug
- Connector Size: Miniature
- Standards Met: IEC



3817457 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE T

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type T Thermocouple
- Application: Standard Quickwire Connector
- Connector Type: Quickwire
- Plug/Socket: Socket
- Connector Size: Miniature
- Standards Met: IEC



3817463 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE N

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type N Thermocouple
- Application: Standard Quickwire Connector
- Connector Type: Quickwire
- Plug/Socket: Plug
- Connector Size: Miniature
- Standards Met: IEC



3817485 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE N

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type N Thermocouple
- Application: Standard Quickwire Connector
- Connector Type: Quickwire
- Plug/Socket: Socket
- Connector Size: Miniature
- Standards Met: IEC



3817491 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE R/S

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type R/S Thermocouple
- Application: Miniature Quickwire Connector
- Connector Type: Quickwire
- Plug/Socket: Plug
- Connector Size: Miniature
- Standards Met: IEC



3817508 Thermocouple

RS PRO PCB MOUNTING THERMOCOUPLE CONNECTOR FOR

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type K Thermocouple
- Application: Miniature PCB Mounting Connector
- Connector Type: PCB Mounting
- Plug/Socket: Socket
- Connector Size: Miniature
- Mounting Type: PCB Mount
- Standards Met: IEC



3817564 Thermocouple

RS PRO PCB MOUNTING THERMOCOUPLE CONNECTOR FOR

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type T Thermocouple
- Application: Miniature PCB Mounting Connector
- Connector Type: PCB Mounting
- Plug/Socket: Socket
- Connector Size: Miniature
- Mounting Type: PCB Mount
- Standards Met: IEC



3817570 Thermocouple

RS PRO THERMOCOUPLE PANEL FOR USE WITH MINIATURE SOCKET,

Pack size: **1 x EA**

- Accessory Type: Thermocouple Panel
- For Use With: Miniature Socket
- Application: Miniature Faceplate
- Connector Size: Miniature
- Mounting Type: Flange Mount
- Standards Met: RoHS Compliant



3971674 Thermocouple

RS PRO THERMOCOUPLE PANEL FOR USE WITH MINIATURE SOCKET,

Pack size: **1 x EA**

- Accessory Type: Thermocouple Panel
- For Use With: Miniature Socket
- Application: Miniature Faceplate
- Connector Size: Miniature
- Mounting Type: Flange Mount
- Standards Met: RoHS Compliant



3971703 Thermocouple

RS PRO THERMOCOUPLE PANEL FOR USE WITH MINIATURE SOCKET,

Pack size: **1 x EA**

- Accessory Type: Thermocouple Panel
- For Use With: Miniature Socket
- Application: Standard Faceplate
- Connector Size: Miniature
- Mounting Type: Flange Mount
- Standards Met: RoHS Compliant




3971719 Thermocouple

RS PRO THERMOCOUPLE PANEL FOR USE WITH STANDARD SOCKET,

Pack size: **1 x EA**

- Accessory Type: Thermocouple Panel
- For Use With: Standard Socket
- Application: Standard Faceplate
- Connector Size: Standard
- Mounting Type: Flange Mount
- Standards Met: RoHS Compliant



3971731 Thermocouple

RS PRO THERMOCOUPLE PANEL FOR USE WITH STANDARD SOCKET,

Pack size: **1 x EA**

- Accessory Type: Thermocouple Panel
- For Use With: Standard Socket
- Application: Standard Faceplate
- Connector Size: Standard
- Mounting Type: Flange Mount
- Standards Met: RoHS Compliant



3971769 Thermocouple

RS PRO MINIATURE BLANKING PLUG FOR USE WITH CONNECTOR

Pack size: **1 x EA**

- Accessory Type: Miniature Blanking Plug
- For Use With: Connector Faceplates
- Mounting Type: Nylon Clip
- Standards Met: RoHS Compliant



3971797 Miniature

RS PRO THERMOWELL FOR USE WITH TEMPERATURE SENSOR, 1/2 BSP,

Pack size: **1 x EA**

- Accessory Type: Thermowell
- For Use With: Temperature Sensor
- Application: 1/2 BSP Connector
- Connector Size: 1/2 BSP
- Mounting Type: Threaded
- Probe Diameter: 6 mm
- Standards Met: RoHS Compliant



4360665 Thermowell

RS PRO THERMOCOUPLE CONNECTION HEAD FOR USE WITH

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connection Head
- For Use With: Temperature Sensor
- Application: 1/2 BSPP Connector
- Connector Size: 1/2 BSPP
- Standards Met: RoHS Compliant



4553801 Thermocouple

RS PRO THERMOCOUPLE CONNECTION HEAD FOR USE WITH

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connection Head
- For Use With: Temperature Sensor
- Application: 1/2 BSPP Connector
- Connector Size: 1/2 BSPP
- Standards Met: RoHS Compliant



4553817 Thermocouple

RS PRO THERMOCOUPLE CONNECTION HEAD FOR USE WITH

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connection Head
- For Use With: Temperature Sensor
- Application: 1/8 BSPP Connector
- Connector Size: 1/8 BSPP
- Standards Met: RoHS Compliant



4553823 Thermocouple

RS PRO SCREW THERMOCOUPLE TERMINAL BLOCK FOR USE WITH KNS

Pack size: **1 x EA**

- Accessory Type: Thermocouple Terminal Block
- For Use With: KNS Head
- Connector Type: Screw
- Standards Met: RoHS Compliant



4553839 Thermocouple

RS PRO SCREW THERMOCOUPLE TERMINAL BLOCK FOR USE WITH TYPE

Pack size: **1 x EA**

- Accessory Type: Thermocouple Terminal Block
- For Use With: Type K Thermocouple
- Connector Type: Screw
- Standards Met: RoHS Compliant



4553867 Thermocouple

RS PRO SCREW THERMOCOUPLE TERMINAL BLOCK FOR USE WITH TYPE

Pack size: **1 x EA**

- Accessory Type: Thermocouple Terminal Block
- For Use With: Type K Thermocouple
- Connector Type: Screw
- Standards Met: RoHS Compliant



4553902 Thermocouple

RS PRO SCREW THERMOCOUPLE TERMINAL BLOCK FOR USE WITH

Pack size: **1 x EA**

- Accessory Type: Thermocouple Terminal Block
- For Use With: Terminal Block Head
- Connector Type: Screw
- Standards Met: RoHS Compliant



4553924 Thermocouple

RS PRO SCREW THERMOCOUPLE TERMINAL BLOCK FOR USE WITH

Pack size: **1 x EA**

- Accessory Type: Thermocouple Terminal Block
- For Use With: Terminal Block Head
- Connector Type: Screw
- Standards Met: RoHS Compliant



4553918 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE J

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type J Thermocouple
- Application: Miniature In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Socket
- Connector Size: Miniature
- Standards Met: BS



4559506 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE K

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type K Thermocouple
- Application: Miniature In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Socket
- Connector Size: Miniature
- Standards Met: BS



4559512 Thermocouple

RS PRO PANEL MOUNT THERMOCOUPLE CONNECTOR FOR

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type K Thermocouple
- Application: Miniature Panel Mount Connector
- Connector Type: Panel Mount
- Plug/Socket: Socket
- Connector Size: Miniature
- Mounting Type: Nylon Clip
- Standards Met: BS



4559528 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE K

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type K Thermocouple
- Application: Miniature In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Plug
- Connector Size: Miniature
- Standards Met: BS



4559534 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE K

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type K Thermocouple
- Application: Miniature In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Plug & Socket
- Connector Size: Miniature
- Standards Met: BS



4559540 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE T

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type T Thermocouple
- Application: Miniature In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Socket
- Connector Size: Miniature
- Standards Met: BS



4559562 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE T

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type T Thermocouple
- Application: Miniature In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Plug
- Connector Size: Miniature
- Standards Met: BS



4559578 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE T

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type T Thermocouple
- Application: Miniature In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Plug & Socket
- Connector Size: Miniature
- Standards Met: IEC



4559584 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE J

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type J Thermocouple
- Application: Standard In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Plug
- Connector Size: Standard
- Standards Met: BS



4559590 Thermocouple

RS PRO PANEL MOUNT THERMOCOUPLE CONNECTOR FOR

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type K Thermocouple
- Application: Standard Panel Mount Connector
- Connector Type: Panel Mount
- Plug/Socket: Socket
- Connector Size: Standard
- Mounting Type: Nylon Clip
- Standards Met: BS



4559607 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE K

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type K Thermocouple
- Application: Standard In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Plug
- Connector Size: Standard
- Standards Met: BS



4559629 Thermocouple

RS PRO FASCIA THERMOCOUPLE CONNECTOR FOR USE WITH COPPER

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Copper Thermocouple
- Application: Miniature Panel Mount Connector
- Connector Type: Fascia
- Plug/Socket: Socket
- Connector Size: Miniature
- Mounting Type: Nylon Clip
- Standards Met: IEC



4559657 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE CU

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type CU Thermocouple
- Application: Miniature In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Socket
- Connector Size: Miniature
- Standards Met: IEC



4559663 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE CU

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type CU Thermocouple
- Application: Miniature In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Plug
- Connector Size: Miniature
- Standards Met: IEC



4559679 Thermocouple

RS PRO FASCIA THERMOCOUPLE CONNECTOR FOR USE WITH TYPE J

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type J Thermocouple
- Application: Miniature Panel Mount Connector
- Connector Type: Fascia
- Plug/Socket: Socket
- Connector Size: Miniature
- Mounting Type: Nylon Clip
- Standards Met: IEC



4559691 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE J

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type J Thermocouple
- Application: Miniature In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Socket
- Connector Size: Miniature
- Standards Met: IEC



4559708 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE J

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type J Thermocouple
- Application: Miniature In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Plug
- Connector Size: Miniature
- Standards Met: IEC



4559714 Thermocouple

RS PRO PANEL MOUNT THERMOCOUPLE CONNECTOR FOR

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type J Thermocouple
- Application: Miniature Panel Mount Connector
- Connector Type: Panel Mount
- Plug/Socket: Socket
- Connector Size: Miniature
- Mounting Type: Stainless Steel Bracket
- Standards Met: IEC



4559720 Thermocouple

RS PRO FASCIA THERMOCOUPLE CONNECTOR FOR USE WITH TYPE K

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type K Thermocouple
- Application: Miniature Panel Mount Connector
- Connector Type: Fascia
- Plug/Socket: Socket
- Connector Size: Miniature
- Mounting Type: Nylon Clip
- Standards Met: IEC



4559742 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE K

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type K Thermocouple
- Application: Miniature In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Socket
- Connector Size: Miniature
- Standards Met: IEC



4559758 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE K

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type K Thermocouple
- Application: Miniature In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Plug
- Connector Size: Miniature
- Standards Met: IEC



4559764 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE K

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type K Thermocouple
- Application: Miniature In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Plug & Socket
- Connector Size: Miniature
- Standards Met: IEC



4559786 Thermocouple

RS PRO PANEL MOUNT THERMOCOUPLE CONNECTOR FOR

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type K Thermocouple
- Application: Miniature Panel Mount Connector
- Connector Type: Panel Mount
- Plug/Socket: Socket
- Connector Size: Miniature
- Mounting Type: Stainless Steel Bracket
- Standards Met: IEC



4559792 Thermocouple

RS PRO FASCIA THERMOCOUPLE CONNECTOR FOR USE WITH TYPE N

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type N Thermocouple
- Application: Miniature Panel Mount Connector
- Connector Type: Fascia
- Plug/Socket: Socket
- Connector Size: Miniature
- Mounting Type: Nylon Clip
- Standards Met: IEC



4559815 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE N

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type N Thermocouple
- Application: Miniature In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Socket
- Connector Size: Miniature
- Standards Met: IEC



4559821 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE N

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type N Thermocouple
- Application: Miniature In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Plug
- Connector Size: Miniature
- Standards Met: IEC



4559843 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE R/S

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type R/S Thermocouple
- Application: Miniature In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Socket
- Connector Size: Miniature
- Standards Met: IEC



4559859 Thermocouple

RS PRO FASCIA THERMOCOUPLE CONNECTOR FOR USE WITH TYPE R/S

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type R/S Thermocouple
- Application: Miniature Panel Mount Connector
- Connector Type: Fascia
- Plug/Socket: Socket
- Connector Size: Miniature
- Mounting Type: Nylon Clip
- Standards Met: IEC



4559871 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE R/S

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type R/S Thermocouple
- Application: Miniature In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Plug
- Connector Size: Miniature
- Standards Met: IEC



4559887 Thermocouple

RS PRO FASCIA THERMOCOUPLE CONNECTOR FOR USE WITH TYPE T

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type T Thermocouple
- Application: Miniature Panel Mount Connector
- Connector Type: Fascia
- Plug/Socket: Socket
- Connector Size: Miniature
- Mounting Type: Nylon Clip
- Standards Met: IEC



4559900 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE T

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type T Thermocouple
- Application: Miniature In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Socket
- Connector Size: Miniature
- Standards Met: IEC



4559916 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE T

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type T Thermocouple
- Application: Miniature In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Plug
- Connector Size: Miniature
- Standards Met: IEC



4559922 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE T

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type T Thermocouple
- Application: Miniature In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Plug & Socket
- Connector Size: Miniature
- Standards Met: IEC



4559938 Thermocouple

RS PRO PANEL MOUNT THERMOCOUPLE CONNECTOR FOR

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type T Thermocouple
- Application: Miniature Panel Mount Connector
- Connector Type: Panel Mount
- Plug/Socket: Socket
- Connector Size: Miniature
- Mounting Type: Stainless Steel Bracket
- Standards Met: IEC



4559944 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE J

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type J Thermocouple
- Application: Standard In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Socket
- Connector Size: Standard
- Standards Met: IEC



4559950 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE J

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type J Thermocouple
- Application: Standard In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Plug
- Connector Size: Standard
- Mounting Type: Stainless Steel Bracket
- Standards Met: IEC



4559966 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE K

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type K Thermocouple
- Application: Standard In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Socket
- Connector Size: Standard
- Standards Met: IEC



4559972 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE K

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type K Thermocouple
- Application: Standard In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Plug
- Connector Size: Standard
- Standards Met: IEC



4559988 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE N

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type N Thermocouple
- Application: Standard In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Socket
- Connector Size: Standard
- Standards Met: IEC



4560001 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE N

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type N Thermocouple
- Application: Standard In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Plug
- Connector Size: Standard
- Standards Met: IEC



4560017 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE R/S

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type R/S Thermocouple
- Application: Standard In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Socket
- Connector Size: Standard
- Standards Met: IEC



4560023 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE R/S

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type R/S Thermocouple
- Application: Standard In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Plug
- Connector Size: Standard
- Standards Met: IEC



4560039 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE T

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type T Thermocouple
- Application: Standard In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Socket
- Connector Size: Standard
- Standards Met: IEC



4560045 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE T

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type T Thermocouple
- Application: Standard In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Plug
- Connector Size: Standard
- Standards Met: IEC



4560051 Thermocouple

RS PRO PANEL MOUNT THERMOCOUPLE CONNECTOR FOR

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type J Thermocouple
- Application: Standard Panel Mount Connector
- Connector Type: Panel Mount
- Plug/Socket: Socket
- Connector Size: Standard
- Mounting Type: Stainless Steel Bracket
- Standards Met: IEC



4560089 Thermocouple

RS PRO PANEL MOUNT THERMOCOUPLE CONNECTOR FOR

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type J Thermocouple
- Application: Standard Panel Mount Connector
- Connector Type: Panel Mount
- Plug/Socket: Socket
- Connector Size: Standard
- Mounting Type: Stainless Steel Bracket
- Standards Met: IEC



4560102 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE K

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type K Thermocouple
- Application: Standard In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Socket
- Connector Size: Standard
- Standards Met: BS



4560540 Thermocouple

RS PRO THERMOWELL FOR USE WITH PT 100 + 10K3A1 THERMOCOUPLE,

Pack size: **1 x EA**

- Accessory Type: Thermowell
- For Use With: PT 100 Thermocouple
- Standards Met: RoHS Compliant



4941040 Thermowell

RS PRO BAYONET ADAPTER FOR USE WITH TYPE J THERMOCOUPLE, ROHS

Pack size: **1 x EA**

- Accessory Type: Bayonet Adapter
- For Use With: Type J Thermocouple
- Standards Met: RoHS Compliant



5477815 Bayonet Adapter

RS PRO THERMOCOUPLE COMPRESSION FITTING FOR USE

Pack size: **1 x EA**

- Accessory Type: Thermocouple Compression Fitting
- For Use With: Thermocouple
- Application: 1/8 BSP Connector
- Connector Size: 1/8 BSP
- Probe Diameter: 3 mm
- Standards Met: RoHS Compliant



5477837 Thermocouple

RS PRO HIGH TEMPERATURE THERMOCOUPLE CONNECTOR FOR

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type K Thermocouple
- Application: Miniature In-Line Connector
- Connector Type: High Temperature Plastic
- Plug/Socket: Plug
- Connector Size: Miniature
- Standards Met: IEC



6118113 Thermocouple

RS PRO HIGH TEMPERATURE THERMOCOUPLE CONNECTOR FOR

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type K Thermocouple
- Application: Miniature In-Line Connector
- Connector Type: High Temperature Plastic
- Plug/Socket: Socket
- Connector Size: Miniature
- Standards Met: IEC



6118135 Thermocouple

RS PRO HIGH TEMPERATURE THERMOCOUPLE CONNECTOR FOR

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type J Thermocouple
- Application: Miniature In-Line Connector
- Connector Type: High Temperature Plastic
- Plug/Socket: Plug
- Connector Size: Miniature
- Standards Met: IEC



6118141 Thermocouple

RS PRO PCB MOUNTING THERMOCOUPLE CONNECTOR FOR

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Temperature Sensor
- Application: Miniature PCB Mounting Connector
- Connector Type: PCB Mounting
- Plug/Socket: Socket
- Connector Size: Miniature
- Mounting Type: PCB Mount
- Standards Met: IEC



6118157 Thermocouple

RS PRO HIGH TEMPERATURE THERMOCOUPLE CONNECTOR FOR

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type J Thermocouple
- Application: Miniature In-Line Connector
- Connector Type: High Temperature Plastic
- Plug/Socket: Socket
- Connector Size: Miniature
- Standards Met: IEC



6118163 Thermocouple

RS PRO HIGH TEMPERATURE THERMOCOUPLE CONNECTOR FOR

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type J Thermocouple
- Application: Standard In-Line Connector
- Connector Type: High Temperature Plastic
- Plug/Socket: Plug
- Connector Size: Standard
- Standards Met: IEC



6118179 Thermocouple

RS PRO HIGH TEMPERATURE THERMOCOUPLE CONNECTOR FOR

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type J Thermocouple
- Application: Standard In-Line Connector
- Connector Type: High Temperature Plastic
- Plug/Socket: Socket
- Connector Size: Standard
- Standards Met: IEC



6118185 Thermocouple

RS PRO THERMOCOUPLE PANEL FOR USE WITH MINIATURE SOCKET,

Pack size: **1 x EA**

- Accessory Type: Thermocouple Panel
- For Use With: Miniature Socket
- Application: Miniature Faceplate
- Connector Size: Miniature
- Mounting Type: Flange Mount
- Standards Met: RoHS Compliant



6118191 Thermocouple

RS PRO THERMOCOUPLE PANEL FOR USE WITH MINIATURE SOCKET,

Pack size: 1 x EA

- Accessory Type: Thermocouple Panel
- For Use With: Miniature Socket
- Application: Miniature Faceplate
- Connector Size: Miniature
- Mounting Type: Flange Mount
- Standards Met: RoHS Compliant



6118214 Thermocouple

RS PRO THERMOCOUPLE PANEL FOR USE WITH MINIATURE SOCKET,

Pack size: 1 x EA

- Accessory Type: Thermocouple Panel
- For Use With: Miniature Socket
- Application: Miniature Faceplate
- Connector Size: Miniature
- Mounting Type: Flange Mount
- Standards Met: RoHS Compliant



6118220 Thermocouple

RS PRO THERMOCOUPLE PANEL FOR USE WITH STANDARD SOCKET,

Pack size: 1 x EA

- Accessory Type: Thermocouple Panel
- For Use With: Standard Socket
- Application: Standard Faceplate
- Connector Size: Standard
- Mounting Type: Flange Mount
- Standards Met: RoHS Compliant



6118258 Thermocouple

RS PRO THERMOCOUPLE PANEL FOR USE WITH STANDARD SOCKET,

Pack size: 1 x EA

- Accessory Type: Thermocouple Panel
- For Use With: Standard Socket
- Application: Standard Faceplate
- Connector Size: Standard
- Mounting Type: Flange Mount
- Standards Met: RoHS Compliant



6118270 Thermocouple

RS PRO BAYONET ADAPTER FOR USE WITH J & K TYPE ADJUSTABLE

Pack size: 1 x EA

- Accessory Type: Bayonet Adapter
- For Use With: J & K Type Adjustable Bayonet
- Application: 1/8 BSP Connector
- Connector Size: 1/8 BSP
- Standards Met: RoHS Compliant



6212243 Bayonet Adapter

RS PRO THERMOCOUPLE PANEL FOR USE WITH MINIATURE SOCKET,

Pack size: 1 x EA

- Accessory Type: Thermocouple Panel
- For Use With: Miniature Socket
- Application: Miniature Faceplate
- Connector Size: Miniature
- Mounting Type: Flange Mount
- Standards Met: RoHS Compliant



7621156 Thermocouple

RS PRO BRASS LOCKNUT FOR USE WITH TEMPERATURE SENSOR, M8,

Pack size: 1 x EA

- Accessory Type: Brass Locknut
- For Use With: Temperature Sensor
- Application: M8 Locknut
- Connector Size: M8
- Mounting Type: M8
- Standards Met: RoHS Compliant



7621162 Brass Locknut

RS PRO THERMOCOUPLE PANEL FOR USE WITH MINIATURE SOCKET,

Pack size: 1 x EA

- Accessory Type: Thermocouple Panel
- For Use With: Miniature Socket
- Application: Miniature Faceplate
- Connector Size: Miniature
- Mounting Type: Flange Mount
- Standards Met: RoHS Compliant



7621165 Thermocouple

RS PRO THERMOCOUPLE PANEL FOR USE WITH MINIATURE SOCKET,

Pack size: 1 x EA

- Accessory Type: Thermocouple Panel
- For Use With: Miniature Socket
- Application: Miniature Faceplate
- Connector Size: Miniature
- Mounting Type: Flange Mount
- Standards Met: RoHS Compliant



7621168 Thermocouple

RS PRO BRASS LOCKNUT FOR USE WITH TEMPERATURE SENSOR, 1/8

Pack size: 1 x EA

- Accessory Type: Brass Locknut
- For Use With: Temperature Sensor
- Application: 1/8 BSPP Locknut
- Connector Size: 1/8 BSPP
- Mounting Type: 1/8 BSPP
- Standards Met: RoHS Compliant



7621171 Brass Locknut

RS PRO BRASS LOCKNUT FOR USE WITH TEMPERATURE SENSOR, 1/4

Pack size: 1 x EA

- Accessory Type: Brass Locknut
- For Use With: Temperature Sensor
- Application: 1/4 BSPP Locknut
- Connector Size: 1/4 BSPP
- Mounting Type: 1/4 BSPP
- Standards Met: RoHS Compliant



7621174 Brass Locknut

RS PRO BRASS LOCKNUT FOR USE WITH TEMPERATURE SENSOR, 1/2

Pack size: 1 x EA

- Accessory Type: Brass Locknut
- For Use With: Temperature Sensor
- Application: 1/2 BSPP Locknut
- Connector Size: 1/2 BSPP
- Mounting Type: 1/2 BSPP
- Standards Met: RoHS Compliant



7621178 Brass Locknut

RS PRO STAINLESS STEEL LOCKNUT FOR USE WITH TEMPERATURE

Pack size: 1 x EA

- Accessory Type: Stainless Steel Locknut
- For Use With: Temperature Sensor
- Application: 1/8 BSPP Locknut
- Connector Size: 1/8 BSPP
- Mounting Type: 1/8 BSPP
- Standards Met: RoHS Compliant



7621180 Stainless Steel

RS PRO STAINLESS STEEL LOCKNUT FOR USE WITH TEMPERATURE

Pack size: 1 x EA

- Accessory Type: Stainless Steel Locknut
- For Use With: Temperature Sensor
- Application: 1/4 BSPP Locknut
- Connector Size: 1/4 BSPP
- Mounting Type: 1/4 BSPP
- Standards Met: RoHS Compliant



7621184 Stainless Steel

RS PRO STAINLESS STEEL LOCKNUT FOR USE WITH TEMPERATURE

Pack size: 1 x EA

- Accessory Type: Stainless Steel Locknut
- For Use With: Temperature Sensor
- Application: M8 Locknut
- Connector Size: M8
- Mounting Type: M8x1
- Standards Met: RoHS Compliant



7621187 Stainless Steel

RS PRO STAINLESS STEEL LOCKNUT FOR USE WITH TEMPERATURE

Pack size: 1 x EA

- Accessory Type: Stainless Steel Locknut
- For Use With: Temperature Sensor
- Application: 1/2 BSPP Locknut
- Connector Size: 1/2 BSPP
- Mounting Type: 1/2 BSPP
- Standards Met: RoHS Compliant



7621193 Stainless Steel

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE R/S

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type R/S Thermocouple
- Application: Miniature Quickwire Connector
- Connector Type: Quickwire
- Plug/Socket: Plug
- Connector Size: Miniature
- Standards Met: ANSI



7691155 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE K

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type K Thermocouple
- Application: Miniature Quickwire Connector
- Connector Type: Quickwire
- Plug/Socket: Plug
- Connector Size: Miniature
- Standards Met: ANSI



7691158 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE E

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type E Thermocouple
- Application: Miniature Quickwire Connector
- Connector Type: Quickwire
- Plug/Socket: Socket
- Connector Size: Miniature
- Standards Met: ANSI



7691161 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE T

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type T Thermocouple
- Application: Miniature Quickwire Connector
- Connector Type: Quickwire
- Plug/Socket: Plug
- Connector Size: Miniature
- Standards Met: ANSI



7691164 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE B

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type B Thermocouple
- Application: Miniature Quickwire Connector
- Connector Type: Quickwire
- Plug/Socket: Socket
- Connector Size: Miniature
- Standards Met: ANSI



7691167 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE K

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type K Thermocouple
- Application: Miniature Quickwire Connector
- Connector Type: Quickwire
- Plug/Socket: Socket
- Connector Size: Miniature
- Standards Met: ANSI



7691173 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE R/S

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type R/S Thermocouple
- Application: Miniature Quickwire Connector
- Connector Type: Quickwire
- Plug/Socket: Socket
- Connector Size: Miniature
- Standards Met: ANSI



7691186 Thermocouple

RS PRO FASCIA THERMOCOUPLE CONNECTOR FOR USE WITH TYPE K

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type K Thermocouple
- Application: Miniature Panel Mount Connector
- Connector Type: Fascia
- Plug/Socket: Socket
- Connector Size: Miniature
- Mounting Type: Nylon Clip
- Standards Met: ANSI



7691199 Thermocouple

RS PRO FASCIA THERMOCOUPLE CONNECTOR FOR USE WITH TYPE R/S

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type R/S Thermocouple
- Application: Miniature Panel Mount Connector
- Connector Type: Fascia
- Plug/Socket: Socket
- Connector Size: Miniature
- Mounting Type: Nylon Clip
- Standards Met: ANSI



7691202 Thermocouple

RS PRO FASCIA THERMOCOUPLE CONNECTOR FOR USE WITH TYPE T

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type T Thermocouple
- Application: Miniature Panel Mount Connector
- Connector Type: Fascia
- Plug/Socket: Socket
- Connector Size: Miniature
- Mounting Type: Nylon Clip
- Standards Met: ANSI



7691206 Thermocouple

RS PRO FASCIA THERMOCOUPLE CONNECTOR FOR USE WITH TYPE N

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type N Thermocouple
- Application: Miniature Panel Mount Connector
- Connector Type: Fascia
- Plug/Socket: Socket
- Connector Size: Miniature
- Mounting Type: Nylon Clip
- Standards Met: ANSI



7691209 Thermocouple

RS PRO PANEL MOUNT THERMOCOUPLE CONNECTOR FOR

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type K Thermocouple
- Application: Miniature Panel Mount Connector
- Connector Type: Panel Mount
- Plug/Socket: Socket
- Connector Size: Miniature
- Mounting Type: Stainless Steel Bracket
- Standards Met: ANSI



7691221 Thermocouple

RS PRO PANEL MOUNT THERMOCOUPLE CONNECTOR FOR

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type T Thermocouple
- Application: Miniature Panel Mount Connector
- Connector Type: Panel Mount
- Plug/Socket: Socket
- Connector Size: Miniature
- Mounting Type: Stainless Steel Bracket
- Standards Met: ANSI



7691237 Thermocouple

RS PRO QUICKWIRE PANEL MOUNT THERMOCOUPLE CONNECTOR FOR

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type K Thermocouple
- Application: Miniature Quickwire Panel Mount Connector
- Connector Type: Quickwire Panel Mount
- Plug/Socket: Socket
- Connector Size: Miniature
- Mounting Type: Stainless Steel Bracket
- Standards Met: ANSI



7691246 Thermocouple

RS PRO PCB MOUNTING THERMOCOUPLE CONNECTOR FOR

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type K Thermocouple
- Application: Miniature PCB Mounting Connector
- Connector Type: PCB Mounting
- Plug/Socket: Socket
- Connector Size: Miniature
- Mounting Type: PCB Mount
- Standards Met: ANSI



7691262 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE J

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type J Thermocouple
- Application: Standard In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Plug
- Connector Size: Standard
- Standards Met: ANSI



7691284 Thermocouple

RS PRO FASCIA THERMOCOUPLE CONNECTOR FOR USE WITH TYPE R/S

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type R/S Thermocouple
- Application: Standard Panel Mount Connector
- Connector Type: Fascia
- Plug/Socket: Socket
- Connector Size: Standard
- Mounting Type: Nylon Clip
- Standards Met: ANSI



7691394 Thermocouple

RS PRO FASCIA THERMOCOUPLE CONNECTOR FOR USE WITH TYPE T

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type T Thermocouple
- Application: Standard Panel Mount Connector
- Connector Type: Fascia
- Plug/Socket: Socket
- Connector Size: Standard
- Mounting Type: Nylon Clip
- Standards Met: ANSI



7691397 Thermocouple

RS PRO PANEL MOUNT THERMOCOUPLE CONNECTOR FOR

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type J Thermocouple
- Application: Standard Quickwire Panel Mount Connector
- Connector Type: Panel Mount
- Plug/Socket: Socket
- Connector Size: Standard
- Mounting Type: Stainless Steel Bracket
- Standards Met: ANSI



7691404 Thermocouple

RS PRO PANEL MOUNT THERMOCOUPLE CONNECTOR FOR

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type K Thermocouple
- Application: Standard Quickwire Panel Mount Connector
- Connector Type: Panel Mount
- Plug/Socket: Socket
- Connector Size: Standard
- Mounting Type: Stainless Steel Bracket
- Standards Met: ANSI



7691408 Thermocouple

RS PRO QUICKWIRE PANEL MOUNT THERMOCOUPLE CONNECTOR FOR

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type J Thermocouple
- Application: Standard Quickwire Panel Mount Connector
- Connector Type: Quickwire Panel Mount
- Plug/Socket: Socket
- Connector Size: Standard
- Mounting Type: Stainless Steel Bracket
- Standards Met: ANSI



7691420 Thermocouple

RS PRO DUPLEX THERMOCOUPLE CONNECTOR FOR USE WITH TYPE K

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type K Thermocouple
- Application: Standard Duplex Connector
- Connector Type: Duplex
- Plug/Socket: Plug
- Connector Size: Standard
- Standards Met: ANSI



7691454 Thermocouple

RS PRO DUPLEX THERMOCOUPLE CONNECTOR FOR USE WITH TYPE K

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type K Thermocouple
- Application: Standard Duplex Connector
- Connector Type: Duplex
- Plug/Socket: Socket
- Connector Size: Standard
- Standards Met: ANSI



7691470 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE J

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type J Thermocouple
- Application: Miniature In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Plug
- Connector Size: Miniature
- Standards Met: JIS



7718761 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE E

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type E Thermocouple
- Application: Miniature In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Plug
- Connector Size: Miniature
- Standards Met: JIS



7718767 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE K

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type K Thermocouple
- Application: Miniature In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Plug
- Connector Size: Miniature
- Standards Met: JIS



7718770 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE R/S

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type R/S Thermocouple
- Application: Miniature In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Plug
- Connector Size: Miniature
- Standards Met: JIS



7718773 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE T

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type T Thermocouple
- Application: Miniature In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Plug
- Connector Size: Miniature
- Standards Met: JIS



7718777 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE J

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type J Thermocouple
- Application: Miniature In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Socket
- Connector Size: Miniature
- Standards Met: JIS



7718783 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE E

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type E Thermocouple
- Application: Miniature In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Socket
- Connector Size: Miniature
- Standards Met: JIS



7718789 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE K

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type K Thermocouple
- Application: Miniature In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Socket
- Connector Size: Miniature
- Standards Met: JIS



7718792 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE R/S

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type R/S Thermocouple
- Application: Miniature In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Socket
- Connector Size: Miniature
- Standards Met: JIS



7718795 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE T

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type T Thermocouple
- Application: Miniature In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Socket
- Connector Size: Miniature
- Standards Met: JIS



7718799 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE J

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type J Thermocouple
- Application: Miniature Quickwire Connector
- Connector Type: Quickwire
- Plug/Socket: Plug
- Connector Size: Miniature
- Standards Met: JIS



7718806 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE B

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type B Thermocouple
- Application: Miniature Quickwire Connector
- Connector Type: Quickwire
- Plug/Socket: Plug
- Connector Size: Miniature
- Standards Met: JIS



7718809 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE T

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type T Thermocouple
- Application: Miniature Quickwire Connector
- Connector Type: Quickwire
- Plug/Socket: Plug
- Connector Size: Miniature
- Standards Met: JIS



7718812 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE K

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type K Thermocouple
- Application: Miniature Quickwire Connector
- Connector Type: Quickwire
- Plug/Socket: Plug
- Connector Size: Miniature
- Standards Met: JIS



7718815 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE R/S

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type R/S Thermocouple
- Application: Miniature Quickwire Connector
- Connector Type: Quickwire
- Plug/Socket: Plug
- Connector Size: Miniature
- Standards Met: JIS



7718818 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE J

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type J Thermocouple
- Application: Miniature Quickwire Connector
- Connector Type: Quickwire
- Plug/Socket: Socket
- Connector Size: Miniature
- Standards Met: JIS



7718828 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE T

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type T Thermocouple
- Application: Miniature Quickwire Connector
- Connector Type: Quickwire
- Plug/Socket: Socket
- Connector Size: Miniature
- Standards Met: JIS



7718834 Thermocouple

RS PRO FASCIA THERMOCOUPLE CONNECTOR FOR USE WITH TYPE T

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type T Thermocouple
- Application: Miniature Panel Mount Connector
- Connector Type: Fascia
- Plug/Socket: Socket
- Connector Size: Miniature
- Mounting Type: Nylon Clip
- Standards Met: JIS



7718856 Thermocouple

RS PRO FASCIA THERMOCOUPLE CONNECTOR FOR USE WITH TYPE K

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type K Thermocouple
- Application: Miniature Panel Mount Connector
- Connector Type: Fascia
- Plug/Socket: Socket
- Connector Size: Miniature
- Mounting Type: Nylon Clip
- Standards Met: JIS



7718859 Thermocouple

RS PRO PANEL MOUNT THERMOCOUPLE CONNECTOR FOR

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type K Thermocouple
- Application: Miniature Panel Mount Connector
- Connector Type: Panel Mount
- Plug/Socket: Socket
- Connector Size: Miniature
- Mounting Type: Stainless Steel Bracket
- Standards Met: JIS



7718871 Thermocouple

RS PRO PANEL MOUNT THERMOCOUPLE CONNECTOR FOR

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type T Thermocouple
- Application: Miniature Panel Mount Connector
- Connector Type: Panel Mount
- Plug/Socket: Socket
- Connector Size: Miniature
- Mounting Type: Stainless Steel Bracket
- Standards Met: JIS



7718878 Thermocouple

RS PRO PCB MOUNTING THERMOCOUPLE CONNECTOR FOR

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type K Thermocouple
- Application: Miniature PCB Mounting Connector
- Connector Type: PCB Mounting
- Plug/Socket: Socket
- Connector Size: Miniature
- Mounting Type: PCB Mount
- Standards Met: JIS



7718916 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE E

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type E Thermocouple
- Application: Standard In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Plug
- Connector Size: Standard
- Standards Met: JIS



7718925 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE J

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type J Thermocouple
- Application: Standard In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Plug
- Connector Size: Standard
- Standards Met: JIS



7718929 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE R/S

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type R/S Thermocouple
- Application: Standard In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Plug
- Connector Size: Standard
- Standards Met: JIS



7718931 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE T

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type T Thermocouple
- Application: Standard In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Plug
- Connector Size: Standard
- Standards Met: JIS



7718935 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE K

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type K Thermocouple
- Application: Standard In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Plug
- Connector Size: Standard
- Standards Met: JIS



7718938 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE J

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type J Thermocouple
- Application: Standard In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Socket
- Connector Size: Standard
- Standards Met: JIS



7718941 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE K

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type K Thermocouple
- Application: Standard In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Socket
- Connector Size: Standard
- Standards Met: JIS



7718950 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE R/S

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type R/S Thermocouple
- Application: Standard In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Socket
- Connector Size: Standard
- Standards Met: JIS



7718953 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE T

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type T Thermocouple
- Application: Standard In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Socket
- Connector Size: Standard
- Standards Met: JIS



7718957 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE J

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type J Thermocouple
- Application: Standard Quickwire Connector
- Connector Type: Quickwire
- Plug/Socket: Plug
- Connector Size: Standard
- Standards Met: JIS



7718963 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE B

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type B Thermocouple
- Application: Standard Quickwire Connector
- Connector Type: Quickwire
- Plug/Socket: Plug
- Connector Size: Standard
- Standards Met: JIS



7718966 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE K

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type K Thermocouple
- Application: Standard Quickwire Connector
- Connector Type: Quickwire
- Plug/Socket: Plug
- Connector Size: Standard
- Standards Met: JIS



7718972 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE J

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type J Thermocouple
- Application: Standard Quickwire Connector
- Connector Type: Quickwire
- Plug/Socket: Socket
- Connector Size: Standard
- Standards Met: JIS



7718985 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE K

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type K Thermocouple
- Application: Standard Quickwire Connector
- Connector Type: Quickwire
- Plug/Socket: Socket
- Connector Size: Standard
- Standards Met: JIS



7718994 Thermocouple

RS PRO FASCIA THERMOCOUPLE CONNECTOR FOR USE WITH TYPE J

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type J Thermocouple
- Application: Standard Panel Mount Connector
- Connector Type: Fascia
- Plug/Socket: Socket
- Connector Size: Standard
- Mounting Type: Nylon Clip
- Standards Met: JIS



7719001 Thermocouple

RS PRO FASCIA THERMOCOUPLE CONNECTOR FOR USE WITH TYPE B

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type B Thermocouple
- Application: Standard Panel Mount Connector
- Connector Type: Fascia
- Plug/Socket: Socket
- Connector Size: Standard
- Mounting Type: Nylon Clip
- Standards Met: JIS



7719004 Thermocouple

RS PRO FASCIA THERMOCOUPLE CONNECTOR FOR USE WITH TYPE R/S

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type R/S Thermocouple
- Application: Standard Panel Mount Connector
- Connector Type: Fascia
- Plug/Socket: Socket
- Connector Size: Standard
- Mounting Type: Nylon Clip
- Standards Met: JIS



7719013 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE CU

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type CU Thermocouple
- Application: Standard In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Plug
- Connector Size: Standard
- Standards Met: IEC



7743776 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE B

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type B Thermocouple
- Application: Miniature In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Plug
- Connector Size: Miniature
- Standards Met: IEC



7747181 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE E

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type E Thermocouple
- Application: Miniature In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Plug
- Connector Size: Miniature
- Standards Met: IEC



7747185 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE B

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type B Thermocouple
- Application: Miniature Quickwire Connector
- Connector Type: Quickwire
- Plug/Socket: Plug
- Connector Size: Miniature
- Standards Met: IEC



7747191 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE E

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type E Thermocouple
- Application: Miniature Quickwire Connector
- Connector Type: Quickwire
- Plug/Socket: Plug
- Connector Size: Miniature
- Standards Met: IEC



7747201 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE K

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type K Thermocouple
- Application: Miniature Quickwire Panel Mount Connector
- Connector Type: Quickwire
- Plug/Socket: Socket
- Connector Size: Miniature
- Mounting Type: Stainless Steel Bracket
- Standards Met: IEC



7747236 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE T

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type T Thermocouple
- Application: Miniature Quickwire Panel Mount Connector
- Connector Type: Quickwire
- Plug/Socket: Socket
- Connector Size: Miniature
- Mounting Type: Stainless Steel Bracket
- Standards Met: IEC



7747242 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE E

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type E Thermocouple
- Application: Standard In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Socket
- Connector Size: Standard
- Standards Met: IEC



7747264 Thermocouple

RS PRO PANEL MOUNT THERMOCOUPLE CONNECTOR FOR

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type R/S Thermocouple
- Application: Standard Panel Mount Connector
- Connector Type: Panel Mount
- Plug/Socket: Socket
- Connector Size: Standard
- Mounting Type: Stainless Steel Bracket
- Standards Met: IEC



7747302 Thermocouple

RS PRO QUICKWIRE PANEL MOUNT THERMOCOUPLE CONNECTOR FOR

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type K Thermocouple
- Application: Standard Quickwire Panel Mount Connector
- Connector Type: Quickwire Panel Mount
- Plug/Socket: Socket
- Connector Size: Standard
- Mounting Type: Stainless Steel Bracket
- Standards Met: IEC



7747315 Thermocouple

RS PRO THERMOCOUPLE COMPRESSION FITTING FOR USE

Pack size: **1 x EA**

- Accessory Type: Thermocouple Compression Fitting
- For Use With: Thermocouple
- Application: 1/8 BSP Connector
- Connector Size: 1/8 BSP
- Probe Diameter: 1 mm
- Standards Met: RoHS Compliant



8047975 Thermocouple

RS PRO THERMOCOUPLE COMPRESSION FITTING FOR USE

Pack size: **1 x EA**

- Accessory Type: Thermocouple Compression Fitting
- For Use With: Thermocouple
- Application: 1/8 BSPT Connector
- Connector Size: 1/8 BSPT
- Probe Diameter: 1 mm
- Standards Met: RoHS Compliant



8047984 Thermocouple

RS PRO ELECTRODE FOR USE WITH THERMOCOUPLE & FINE WIRE

Pack size: **1 x EA**

- Accessory Type: Electrode
- For Use With: Thermocouple & Fine Wire Welder
- Standards Met: RoHS Compliant



8140184 Electrode

RS PRO IN-LINE THERMOCOUPLE COMPRESSION FITTING FOR USE

Pack size: **1 x EA**

- Accessory Type: Thermocouple Compression Fitting
- For Use With: Thermocouple
- Application: 1/8 BSPP In-Line Connector
- Connector Type: In-Line
- Connector Size: 1/8 BSPP
- Probe Diameter: 1.5 mm
- Standards Met: RoHS Compliant



8399496 Thermocouple

RS PRO IN-LINE THERMOCOUPLE COMPRESSION FITTING FOR USE

Pack size: **1 x EA**

- Accessory Type: Thermocouple Compression Fitting
- For Use With: Thermocouple
- Application: 1/8 BSPP In-Line Connector
- Connector Type: In-Line
- Connector Size: 1/8 BSPP
- Probe Diameter: 6 mm
- Standards Met: RoHS Compliant



8399507 Thermocouple

RS PRO IN-LINE THERMOCOUPLE COMPRESSION FITTING FOR USE

Pack size: **1 x EA**

- Accessory Type: Thermocouple Compression Fitting
- For Use With: Thermocouple
- Application: 1/8 BSPT In-Line Connector
- Connector Type: In-Line
- Connector Size: 1/8 BSPT
- Probe Diameter: 1/8 in
- Standards Met: RoHS Compliant



8399522 Thermocouple

RS PRO IN-LINE THERMOCOUPLE COMPRESSION FITTING FOR USE

Pack size: **1 x EA**

- Accessory Type: Thermocouple Compression Fitting
- For Use With: Thermocouple
- Application: 1/8 BSPT In-Line Connector
- Connector Type: In-Line
- Connector Size: 1/8 BSPT
- Probe Diameter: 6 mm
- Standards Met: RoHS Compliant



8399529 Thermocouple

RS PRO IN-LINE THERMOCOUPLE COMPRESSION FITTING FOR USE

Pack size: **1 x EA**

- Accessory Type: Thermocouple Compression Fitting
- For Use With: Thermocouple
- Application: 1/4 BSPP In-Line Connector
- Connector Type: In-Line
- Connector Size: 1/4 BSPP
- Probe Diameter: 3 mm
- Standards Met: RoHS Compliant



8399531 Thermocouple

RS PRO IN-LINE THERMOCOUPLE COMPRESSION FITTING FOR USE

Pack size: **1 x EA**

- Accessory Type: Thermocouple Compression Fitting
- For Use With: Thermocouple
- Application: 1/8 BSPT In-Line Connector
- Connector Type: In-Line
- Connector Size: 1/8 BSPT
- Probe Diameter: 1/4 in
- Standards Met: RoHS Compliant



8399538 Thermocouple

RS PRO IN-LINE THERMOCOUPLE COMPRESSION FITTING FOR USE

Pack size: **1 x EA**

- Accessory Type: Thermocouple Compression Fitting
- For Use With: Thermocouple
- Application: 1/2 BSPT In-Line Connector
- Connector Type: In-Line
- Connector Size: 1/2 BSPT
- Probe Diameter: 3 mm
- Standards Met: RoHS Compliant



8399541 Thermocouple

RS PRO IN-LINE THERMOCOUPLE COMPRESSION FITTING FOR USE

Pack size: **1 x EA**

- Accessory Type: Thermocouple Compression Fitting
- For Use With: Thermocouple
- Application: 1/4 BSP In-Line Connector
- Connector Type: In-Line
- Connector Size: 1/4 BSP
- Probe Diameter: 6 mm
- Standards Met: RoHS Compliant



8399544 Thermocouple

RS PRO IN-LINE THERMOCOUPLE COMPRESSION FITTING FOR USE

Pack size: **1 x EA**

- Accessory Type: Thermocouple Compression Fitting
- For Use With: Thermocouple
- Application: 1/4 BSP In-Line Connector
- Connector Type: In-Line
- Connector Size: 1/4 BSP
- Probe Diameter: 3/16 in
- Standards Met: RoHS Compliant



8399547 Thermocouple

RS PRO IN-LINE THERMOCOUPLE COMPRESSION FITTING FOR USE

Pack size: **1 x EA**

- Accessory Type: Thermocouple Compression Fitting
- For Use With: Thermocouple
- Application: 1/2 BSPT In-Line Connector
- Connector Type: In-Line
- Connector Size: 1/2 BSPT
- Probe Diameter: 8 mm
- Standards Met: RoHS Compliant



8399550 Thermocouple

RS PRO IN-LINE THERMOCOUPLE COMPRESSION FITTING FOR USE

Pack size: **1 x EA**

- Accessory Type: Thermocouple Compression Fitting
- For Use With: Thermocouple
- Application: 1/8 NPT In-Line Connector
- Connector Type: In-Line
- Connector Size: 1/8 NPT
- Probe Diameter: 1.5 mm
- Standards Met: RoHS Compliant



8399553 Thermocouple

RS PRO IN-LINE THERMOCOUPLE COMPRESSION FITTING FOR USE

Pack size: **1 x EA**

- Accessory Type: Thermocouple Compression Fitting
- For Use With: Thermocouple
- Application: 1/8 BSP In-Line Connector
- Connector Type: In-Line
- Connector Size: 1/8 BSP
- Probe Diameter: 3/16 in
- Standards Met: RoHS Compliant



8399563 Thermocouple

RS PRO IN-LINE THERMOCOUPLE COMPRESSION FITTING FOR USE

Pack size: **1 x EA**

- Accessory Type: Thermocouple Compression Fitting
- For Use With: Thermocouple
- Application: 1/4 BSP In-Line Connector
- Connector Type: In-Line
- Connector Size: 1/4 BSP
- Probe Diameter: 4 mm
- Standards Met: RoHS Compliant



8399566 Thermocouple

RS PRO IN-LINE THERMOCOUPLE COMPRESSION FITTING FOR USE

Pack size: **1 x EA**

- Accessory Type: Thermocouple Compression Fitting
- For Use With: Thermocouple
- Application: 1/8 BSP In-Line Connector
- Connector Type: In-Line
- Connector Size: 1/8 BSP
- Probe Diameter: 4.5 mm
- Standards Met: RoHS Compliant



8399569 Thermocouple

RS PRO IN-LINE THERMOCOUPLE COMPRESSION FITTING FOR USE

Pack size: **1 x EA**

- Accessory Type: Thermocouple Compression Fitting
- For Use With: Thermocouple
- Application: 1/4 BSP In-Line Connector
- Connector Type: In-Line
- Connector Size: 1/4 BSP
- Probe Diameter: 1/4 in
- Standards Met: RoHS Compliant



8399575 Thermocouple

RS PRO IN-LINE THERMOCOUPLE COMPRESSION FITTING FOR USE

Pack size: **1 x EA**

- Accessory Type: Thermocouple Compression Fitting
- For Use With: Thermocouple
- Application: 1/2 BSP In-Line Connector
- Connector Type: In-Line
- Connector Size: 1/2 BSP
- Probe Diameter: 3 mm
- Standards Met: RoHS Compliant



8399579 Thermocouple

RS PRO IN-LINE THERMOCOUPLE COMPRESSION FITTING FOR USE

Pack size: **1 x EA**

- Accessory Type: Thermocouple Compression Fitting
- For Use With: Thermocouple
- Application: 1/4 BSPT In-Line Connector
- Connector Type: In-Line
- Connector Size: 1/4 BSPT
- Probe Diameter: 3/16 in
- Standards Met: RoHS Compliant



8399585 Thermocouple

RS PRO IN-LINE THERMOCOUPLE COMPRESSION FITTING FOR USE

Pack size: **1 x EA**

- Accessory Type: Thermocouple Compression Fitting
- For Use With: Thermocouple
- Application: 1/8 BSPT In-Line Connector
- Connector Type: In-Line
- Connector Size: 1/8 BSPT
- Probe Diameter: 6 mm
- Standards Met: RoHS Compliant



8399591 Thermocouple

RS PRO IN-LINE THERMOCOUPLE COMPRESSION FITTING FOR USE

Pack size: **1 x EA**

- Accessory Type: Thermocouple Compression Fitting
- For Use With: Thermocouple
- Application: 1/8 BSPT In-Line Connector
- Connector Type: In-Line
- Connector Size: 1/8 BSPT
- Probe Diameter: 3/16 in
- Standards Met: RoHS Compliant



8399597 Thermocouple

RS PRO IN-LINE THERMOCOUPLE COMPRESSION FITTING FOR USE

Pack size: **1 x EA**

- Accessory Type: Thermocouple Compression Fitting
- For Use With: Thermocouple
- Application: 1/4 BSPT In-Line Connector
- Connector Type: In-Line
- Connector Size: 1/4 BSPT
- Probe Diameter: 4.5 mm
- Standards Met: RoHS Compliant



8399604 Thermocouple

RS PRO PROBE SUPPORT FOR USE WITH THERMOCOUPLE CONNECTOR,

Pack size: **10 x EA**

- Accessory Type: Probe Support
- For Use With: Thermocouple Connector
- Application: Miniature Connector
- Connector Size: Miniature
- Mounting Type: Crimp
- Probe Diameter: 3 mm
- Standards Met: RoHS Compliant



8399755 Probe Support

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE J

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type J Thermocouple
- Application: Miniature In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Plug & Socket
- Connector Size: Miniature
- Standards Met: IEC



8919012 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE K

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type K Thermocouple
- Application: Miniature In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Plug & Socket
- Connector Size: Miniature
- Standards Met: ANSI



8919016 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE K

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type K Thermocouple
- Application: Standard In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Plug & Socket
- Connector Size: Standard
- Standards Met: IEC



8919022 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE K

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type K Thermocouple
- Application: Standard In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Plug & Socket
- Connector Size: Standard
- Standards Met: ANSI



8919025 Thermocouple

RS PRO IN-LINE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE J

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type J Thermocouple
- Application: Standard In-Line Connector
- Connector Type: In-Line
- Plug/Socket: Plug & Socket
- Connector Size: Standard
- Standards Met: IEC



8919028 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE K

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type K Thermocouple
- Application: Miniature Quickwire Connector
- Connector Type: Quickwire
- Plug/Socket: Plug & Socket
- Connector Size: Miniature
- Standards Met: IEC



8919031 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE K

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type K Thermocouple
- Application: Miniature Quickwire Connector
- Connector Type: Quickwire
- Plug/Socket: Plug & Socket
- Connector Size: Miniature
- Standards Met: ANSI



8919034 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE K

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type K Thermocouple
- Application: Standard Quickwire Connector
- Connector Type: Quickwire
- Plug/Socket: Plug & Socket
- Connector Size: Standard
- Standards Met: IEC



8919038 Thermocouple

RS PRO QUICKWIRE THERMOCOUPLE CONNECTOR FOR USE WITH TYPE K

Pack size: **1 x EA**

- Accessory Type: Thermocouple Connector
- For Use With: Type K Thermocouple
- Application: Standard Quickwire Connector
- Connector Type: Quickwire
- Plug/Socket: Plug & Socket
- Connector Size: Standard
- Standards Met: ANSI



8919047 Thermocouple

RS PRO THERMOCOUPLE SELECTOR SWITCH FOR USE WITH TYPE K

Pack size: **1 x EA**

- Accessory Type: Thermocouple Selector Switch
- For Use With: Type K Thermocouple
- Mounting Type: Bench
- Standards Met: ANSI, RoHS Compliant



8919053 Thermocouple

RS PRO THERMOCOUPLE SELECTOR SWITCH FOR USE WITH TYPE K

Pack size: **1 x EA**

- Accessory Type: Thermocouple Selector Switch
- For Use With: Type K Thermocouple
- Mounting Type: Bench
- Standards Met: IEC, RoHS Compliant



8919056 Thermocouple

RS PRO THERMOCOUPLE SELECTOR SWITCH FOR USE WITH TYPE K

Pack size: **1 x EA**

- Accessory Type: Thermocouple Selector Switch
- For Use With: Type K Thermocouple
- Mounting Type: Bench
- Standards Met: ANSI, RoHS Compliant



8919062 Thermocouple

RS PRO AIR PURGE COLLAR FOR USE WITH INFRARED TEMPERATURE

Pack size: **1 x EA**

- Accessory Type: Air Purge Collar
- For Use With: Infrared Temperature Sensor



9058770 Air Purge Collar

RS PRO ADJUSTABLE MOUNTING BRACKET FOR USE WITH INFRARED

Pack size: **1 x EA**

- Accessory Type: Adjustable Mounting Bracket
- For Use With: Infrared Temperature Sensor



9058777 Adjustable

ANALOGUE THERMOSTAT, 96X96, 8A RELAY

Pack size: **1 x EA**

- Output Type: Relay
- Supply Voltage: 230 V ac
- Size: 96 x 96 mm
- Number of Outputs: 1
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: +400 °C
- IP Rating: IP65
- Mounting Type: Panel Mount



1241044 Relay

RS PRO PANEL MOUNT ON/OFF TEMPERATURE CONTROLLER, 77 X

Pack size: **1 x EA**

- Output Type: Relay
- Supply Voltage: 230 V ac
- Size: 77 x 35 mm
- Number of Inputs: 1
- Number of Outputs: 1
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: +50 °C
- IP Rating: IP20, IP65



1241051 Relay

RS PRO DIN RAIL PID TEMPERATURE CONTROLLER, 22.5 X 110MM 3 INPUT,

Pack size: **1 x EA**

- Output Type: Changeover Relay, Relay
- Supply Voltage: 24 V ac/dc
- Size: 22.5 x 110 mm
- Number of Inputs: 3
- Number of Outputs: 2
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: +55 °C
- Control Type: Controller



1448683 Changeover

RS PRO DIN RAIL PID TEMPERATURE CONTROLLER, 22.5 X 110MM 3 INPUT,

Pack size: **1 x EA**

- Output Type: Changeover Relay, Relay
- Supply Voltage: 100 → 240 V ac
- Size: 22.5 x 110 mm
- Number of Inputs: 3
- Number of Outputs: 2
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: +55 °C
- Control Type: Controller



1448684 Changeover

RS PRO PID TEMPERATURE CONTROLLER, 72 X 72MM 1 INPUT, 2

Pack size: **1 x EA**

- Output Type: Relay, SSR
- Supply Voltage: 230 V ac
- Size: 72 x 72 mm
- Number of Inputs: 1
- Number of Outputs: 2
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: +50 °C
- Temperature Range: 0 → 400 °C, 0 → 50 °C



1885159 Relay, SSR

RS PRO PID TEMPERATURE CONTROLLER, 72 X 72MM 1 INPUT, 2

Pack size: **1 x EA**

- Output Type: Relay, SSR
- Supply Voltage: 230 V ac
- Size: 72 x 72 mm
- Number of Inputs: 1
- Number of Outputs: 2
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: +50 °C
- Temperature Range: 0 → 50 °C, 0 → 800 °C



1885160 Relay, SSR

RS PRO PID TEMPERATURE CONTROLLER, 96 X 96MM 1 INPUT, 2

Pack size: **1 x EA**

- Output Type: Relay, SSR
- Supply Voltage: 230 V ac
- Size: 96 x 96 mm
- Number of Inputs: 1
- Number of Outputs: 2
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: +50 °C
- Temperature Range: 0 → 400 °C, 0 → 50 °C



1885162 Relay, SSR

TEMPERATURE CONTROLLER, POWER SUPPLY: 24

Pack size: **1 x EA**

- Output Type: Relay, SSR
- Supply Voltage: 24 V ac
- Size: 96 x 96 mm
- Number of Inputs: 1
- Number of Outputs: 2
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: +50 °C
- Temperature Range: 0 → 50 °C, -200 → +1700 °C



1885164 Relay, SSR

TEMPERATURE CONTROLLER, POWER SUPPLY: 23

Pack size: **1 x EA**

- Output Type: Relay, SSR
- Supply Voltage: 230 V ac
- Size: 96 x 96 mm
- Number of Inputs: 1
- Number of Outputs: 2
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: +50 °C
- Temperature Range: 0 → 50 °C, -200 → +1700 °C



1885167 Relay, SSR

DIGITAL ON/OFF TEMPERATURE CONTROLLER, 4

Pack size: **1 x EA**

- Output Type: Relay
- Supply Voltage: 100 → 240 V ac
- Size: 48 x 48 mm
- Number of Outputs: 2
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: +50 °C
- IP Rating: IP20, IP65
- Input Type: K Type Thermocouple



1981172 Relay

DIGITAL ON/OFF TEMPERATURE CONTROLLER, 4

Pack size: **1 x EA**

- Output Type: Relay
- Supply Voltage: 10 → 30 V dc
- Size: 48 x 48 mm
- Number of Outputs: 2
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: +50 °C
- IP Rating: IP20, IP65
- Input Type: K Type Thermocouple



1981173 Relay

RS PRO ON/OFF TEMPERATURE CONTROLLER, 96MM 1 INPUT, 2

Pack size: **1 x EA**

- Output Type: Analogue Relay
- Supply Voltage: 230 V ac
- Size: 96mm x 96 mm
- Number of Inputs: 1
- Number of Outputs: 2
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: +50 °C
- Input Type: J Type Thermocouple



1981175 Analogue Relay

RS PRO ON/OFF TEMPERATURE CONTROLLER, 96MM 1 INPUT, 2

Pack size: **1 x EA**

- Output Type: Analogue Relay
- Supply Voltage: 230 V ac
- Size: 96mm x 96 mm
- Number of Inputs: 1
- Number of Outputs: 2
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: +50 °C
- IP Rating: IP20, IP65



1981176 Analogue Relay

PID CONTROL UNIT, POWER SUPPLY: 100-240

Pack size: **1 x EA**

- Output Type: Relay, SSR
- Supply Voltage: 100 → 240 V
- Size: 48 x 48 mm
- Number of Inputs: 2
- Number of Outputs: 3
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: +50 °C
- Temperature Range: 0 → +50 °C



2228113 Relay, SSR

PID CONTROL UNIT, POWER SUPPLY: 100-240

Pack size: **1 x EA**

- Output Type: Relay, SSR
- Supply Voltage: 100 → 240 V
- Size: 48 x 48 mm
- Number of Inputs: 2
- Number of Outputs: 3
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: +50 °C
- Temperature Range: 0 → +50 °C



2228114 Relay, SSR

ON/OFF CONTROL UNIT, POWER SUPPLY: 230 V

Pack size: **1 x EA**

- Output Type: Relay
- Supply Voltage: 230 V
- Size: 77 x 35 mm
- Number of Inputs: 1
- Number of Outputs: 1
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +70 °C
- Temperature Range: -20 → +70 °C



2228123 Relay

PID CONTROL UNIT, POWER SUPPLY: 100-240

Pack size: **1 x EA**

- Output Type: Relay
- Supply Voltage: 100 → 240 V
- Size: 77 x 35 mm
- Number of Inputs: 1
- Number of Outputs: 2
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +70 °C
- Temperature Range: -20 → +70 °C



2228134 Relay

PID CONTROL UNIT, POWER SUPPLY: 24 VAC/D

Pack size: **1 x EA**

- Output Type: Relay
- Supply Voltage: 24 V
- Size: 77 x 35 mm
- Number of Inputs: 1
- Number of Outputs: 2
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +70 °C
- Temperature Range: -20 → +70 °C



2228136 Relay

PID CONTROL UNIT, POWER SUPPLY: 10-30 VD

Pack size: **1 x EA**

- Output Type: Relay, SSR
- Supply Voltage: 10 → 30 V
- Size: 77 x 35 mm
- Number of Inputs: 1
- Number of Outputs: 2
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +70 °C
- Temperature Range: -20 → +70 °C



2228139 Relay, SSR

ON/OFF CONTROL UNIT, POWER SUPPLY: 100-2

Pack size: **1 x EA**

- Output Type: Relay
- Supply Voltage: 100 → 240 V
- Size: 48 x 48 mm
- Number of Inputs: 1
- Number of Outputs: 1
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: +50 °C
- Temperature Range: 0 → +50 °C



2228140 Relay

RS PRO DIN RAIL PID TEMPERATURE CONTROLLER, 72 X 72MM, 3 OUTPUT

Pack size: **1 x EA**

- Output Type: SSR
- Supply Voltage: 24 V ac/dc
- Size: 72 x 72 mm
- Number of Outputs: 3
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: +50 °C
- Temperature Range: 0 → +1700 (Type R Thermocouple) °C, 0 → +1700 (Type S Thermocouple) °C, -199.9 → +650 (RTD - PT 100) °C, -200 → +1300 (Type K Thermocouple) °C, -200 → +400 (Type T Thermocouple) °C, -200 → +650 (RTD - PT 100) °C, -200 → +900 (Type J Thermocouple) °C
- Control Type: ON/OFF, PID Controller



7864772 SSR

RS PRO DIN RAIL PID TEMPERATURE CONTROLLER, 72 X 72MM, 3 OUTPUT

Pack size: **1 x EA**

- Output Type: SSR
- Supply Voltage: 230 V ac
- Size: 72 x 72 mm
- Number of Outputs: 3
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: +50 °C
- Temperature Range: 0 → +1700 (Type R Thermocouple) °C, 0 → +1700 (Type S Thermocouple) °C, -199.9 → +650 (RTD - PT 100) °C, -200 → +1300 (Type K Thermocouple) °C, -200 → +400 (Type T Thermocouple) °C, -200 → +650 (RTD - PT 100) °C, -200 → +900 (Type J Thermocouple) °C
- Control Type: ON/OFF, PID Controller



7864775 SSR

ON/OFF TEMP CONTROLLER, 76X35, 24VDC

Pack size: **1 x EA**

- Output Type: Relay
- Supply Voltage: 10 → 30 V dc
- Size: 76 x 34.5 mm
- Number of Inputs: 1
- Number of Outputs: 3
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: +70 °C
- IP Rating: NEMA 4X



7983435 Relay

RS PRO PANEL MOUNT PID TEMPERATURE CONTROLLER, 72 X

Pack size: **1 x EA**

- Output Type: Relay, SSR
- Supply Voltage: 100 → 240 V ac
- Size: 72 x 72 mm
- Number of Outputs: 3
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: +50 °C
- Temperature Range: 0 → +50 °C
- Control Type: ON/OFF, PID Controller



7983466 Relay, SSR

RS PRO PANEL MOUNT PID TEMPERATURE CONTROLLER, 96 X

Pack size: **1 x EA**

- Output Type: SSR
- Supply Voltage: 230 V ac
- Size: 96 x 96 mm
- Number of Outputs: 3
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: +50 °C
- Temperature Range: 0 → +50 °C
- Control Type: ON/OFF, PID Controller



7983472 SSR

RS PRO PANEL MOUNT PID TEMPERATURE CONTROLLER, 96 X

Pack size: **1 x EA**

- Output Type: Relay, SSR
- Supply Voltage: 100 → 240 V ac
- Size: 96 x 96 mm
- Number of Outputs: 3
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: +50 °C
- Temperature Range: 0 → +50 °C
- Control Type: ON/OFF, PID Controller



7983479 Relay, SSR

RS PRO 1/8 DIN (H) ON/OFF TEMPERATURE CONTROLLER, 48 X

Pack size: **1 x EA**

- Output Type: Relay
- Supply Voltage: 100 → 240 V ac
- Size: 48 x 96 mm
- Number of Inputs: 1
- Number of Outputs: 2
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: +50 °C
- IP Rating: IP65, NEMA 4X



8751214 Relay

ON/OFF TEMP CONTROLLER, 96X96, 230VAC

Pack size: **1 x EA**

- Output Type: Relay
- Supply Voltage: 230 V ac
- Size: 96 x 96 mm
- Number of Inputs: 1
- Number of Outputs: 1
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: +50 °C
- IP Rating: IP65, NEMA 4X



8751232 Relay

ON/OFF TEMP CONTROLLER, 72X72, 230VAC

Pack size: **1 x EA**

- Output Type: Relay
- Supply Voltage: 230 V ac
- Size: 72 x 72 mm
- Number of Inputs: 1
- Number of Outputs: 1
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: +50 °C
- IP Rating: IP65, NEMA 4X



8751239 Relay

RS PRO PANEL MOUNT PID TEMPERATURE CONTROLLER, 76 X

Pack size: **1 x EA**

- Output Type: Relay
- Supply Voltage: 230 V ac
- Size: 76 x 34.5 mm
- Number of Inputs: 4
- Number of Outputs: 4
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: +50 °C
- Temperature Range: 0 → +100 °C



8751242 Relay

RS PRO PANEL MOUNT PID TEMPERATURE CONTROLLER, 76 X

Pack size: **1 x EA**

- Output Type: Relay
- Supply Voltage: 230 V ac
- Size: 76 x 34.5 mm
- Number of Inputs: 1
- Number of Outputs: 3
- Minimum Operating Temperature: -30 °C
- Maximum Operating Temperature: +80 °C
- Temperature Range: 0 → +100 °C



8751245 Relay

RS PRO 1/16 DIN ON/OFF TEMPERATURE CONTROLLER, 35 X

Pack size: **1 x EA**

- Output Type: SSR
- Supply Voltage: 230 V ac
- Size: 35 x 77 mm
- Number of Inputs: 1
- Number of Outputs: 1
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: +50 °C
- IP Rating: IP65, NEMA 4X



8751264 SSR

RS PRO 1/16 DIN ON/OFF TEMPERATURE CONTROLLER, 35 X

Pack size: **1 x EA**

- Output Type: Relay
- Supply Voltage: 230 V ac
- Size: 35 x 77 mm
- Number of Inputs: 1
- Number of Outputs: 1
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: +50 °C
- IP Rating: IP65, NEMA 4X



8751267 Relay

TEMPERATURE, SENSITIVE LABEL, CLOCK TYPE, SCALE 1,4-0-

Pack size: **10 x EA**

- Minimum Temperature Sensitivity: 40 °C
- Maximum Temperature Sensitivity: 54 °C
- Number of Temperature Levels: 5
- Orientation: Circle
- Reversibility: No
- Label Diameter: 14 mm



285964 40 °C

TERMINAL COVER

Pack size: **1 x EA**

- Accessory Type: Adapter



1241083 Adapter

TEMPERATURE,SENSITIVE LABEL,CLOCK TYPE,SCALE 2,60-

Pack size: **10 x EA**

- Minimum Temperature Sensitivity: 60 °C
- Maximum Temperature Sensitivity: 82 °C
- Number of Temperature Levels: 5
- Orientation: Circle
- Reversibility: No
- Label Diameter: 14 mm



285970 60 °C

TEMPERATURE,SENSITIVE LABEL,CLOCK TYPE,SCALE 3,88-

Pack size: **10 x EA**

- Minimum Temperature Sensitivity: 88 °C
- Maximum Temperature Sensitivity: 110 °C
- Number of Temperature Levels: 5
- Orientation: Circle
- Reversibility: No
- Label Diameter: 14 mm



285986 88 °C

TEMPERATURE,SENSITIVE LABEL,CLOCK TYPE,SCALE 4,116-

Pack size: **10 x EA**

- Minimum Temperature Sensitivity: 116 °C
- Maximum Temperature Sensitivity: 138 °C
- Number of Temperature Levels: 5
- Orientation: Circle
- Reversibility: No
- Label Diameter: 14 mm



285992 116 °C

TEMPERATURE,SENSITIVE LABEL,CLOCK TYPE,SCALE 5,143-

Pack size: **10 x EA**

- Minimum Temperature Sensitivity: 143 °C
- Maximum Temperature Sensitivity: 166 °C
- Number of Temperature Levels: 5
- Orientation: Circle
- Reversibility: No
- Label Diameter: 14 mm



286002 143 °C

RS PRO NON-REVERSIBLE TEMPERATURE SENSITIVE LABEL, 171°C

Pack size: **10 x EA**

- Minimum Temperature Sensitivity: 171 °C
- Maximum Temperature Sensitivity: 193 °C
- Number of Temperature Levels: 5
- Orientation: Circle
- Reversibility: No
- Label Diameter: 14 mm



286018 171 °C

RS PRO NON-REVERSIBLE TEMPERATURE SENSITIVE LABEL, 40°C

Pack size: **10 x EA**

- Minimum Temperature Sensitivity: 40 °C
- Maximum Temperature Sensitivity: 46 °C
- Number of Temperature Levels: 4
- Orientation: Circle
- Reversibility: No
- Label Length: 11 mm
- Label Width: 4 mm



286080 40 °C

TEMPERATURE,SENSITIVE LABEL,MICRO,SCALE 2,49-65DEGC

Pack size: **10 x EA**

- Minimum Temperature Sensitivity: 49 °C
- Maximum Temperature Sensitivity: 65 °C
- Number of Temperature Levels: 4
- Orientation: Circle
- Reversibility: No
- Label Length: 11 mm
- Label Width: 4 mm



286096 49 °C

RS PRO NON-REVERSIBLE TEMPERATURE SENSITIVE LABEL, 71°C

Pack size: **10 x EA**

- Minimum Temperature Sensitivity: 71 °C
- Maximum Temperature Sensitivity: 88 °C
- Number of Temperature Levels: 4
- Orientation: Circle
- Reversibility: No
- Label Length: 11 mm
- Label Width: 4 mm



286103 71 °C

RS PRO NON-REVERSIBLE TEMPERATURE SENSITIVE LABEL, 93°C

Pack size: **10 x EA**

- Minimum Temperature Sensitivity: 93 °C
- Maximum Temperature Sensitivity: 110 °C
- Number of Temperature Levels: 4
- Orientation: Circle
- Reversibility: No
- Label Length: 11 mm
- Label Width: 4 mm



286119 93 °C

TEMPERATURE,SENSITIVE LABEL,MICRO,SCALE 5,116-132DEGC

Pack size: **10 x EA**

- Minimum Temperature Sensitivity: 116 °C
- Maximum Temperature Sensitivity: 132 °C
- Number of Temperature Levels: 4
- Orientation: Circle
- Reversibility: No
- Label Length: 11 mm
- Label Width: 4 mm



286125 116 °C

RS PRO NON-REVERSIBLE TEMPERATURE SENSITIVE LABEL,

Pack size: **10 x EA**

- Minimum Temperature Sensitivity: 138 °C
- Maximum Temperature Sensitivity: 154 °C
- Number of Temperature Levels: 4
- Orientation: Circle
- Reversibility: No
- Label Length: 11 mm
- Label Width: 4 mm



286131 138 °C

LABEL,TEMPERATURE SENSITIVE,MICRO KIT 1,10X40-

Pack size: **1 x KT**

- Minimum Temperature Sensitivity: 40 °C
- Maximum Temperature Sensitivity: 88 °C
- Number of Temperature Levels: 4
- Labels Per Product: 30
- Orientation: Horizontal
- Reversibility: No
- Label Length: 4 mm
- Label Width: 11 mm



552618 40 °C

LABEL,TEMPERATURE SENSITIVE,MICRO KIT 2,10X93-

Pack size: **1 x KT**

- Minimum Temperature Sensitivity: 93 °C
- Maximum Temperature Sensitivity: 154 °C
- Number of Temperature Levels: 4
- Labels Per Product: 30
- Orientation: Horizontal
- Reversibility: No
- Label Length: 4 mm
- Label Width: 11 mm



552624 93 °C

RS PRO NON-REVERSIBLE TEMPERATURE SENSITIVE LABEL,

Pack size: **1 x KT**

- Minimum Temperature Sensitivity: 160 °C
- Maximum Temperature Sensitivity: 224 °C
- Number of Temperature Levels: 4
- Labels Per Product: 30
- Orientation: Horizontal
- Reversibility: No
- Label Length: 4 mm
- Label Width: 11 mm




552630 160 °C

LABEL,TEMPERATURE SENSITIVE,SCALE B,71-110DEGC

Pack size: **10 x EA**

- Minimum Temperature Sensitivity: 71 °C
- Maximum Temperature Sensitivity: 110 °C
- Number of Temperature Levels: 8
- Orientation: Vertical
- Reversibility: No
- Label Length: 18 mm
- Label Width: 51 mm




555409 71 °C

LABEL,TEMPERATURE SENSITIVE,SCALE C,116-154DEGC

Pack size: **10 x EA**

- Minimum Temperature Sensitivity: 116 °C
- Maximum Temperature Sensitivity: 154 °C
- Number of Temperature Levels: 8
- Orientation: Vertical
- Reversibility: No
- Label Length: 18 mm
- Label Width: 51 mm



555415 116 °C

LABEL,TEMPERATURE SENSITIVE,SCALE D,160-199DEGC

Pack size: **10 x EA**

- Minimum Temperature Sensitivity: 160 °C
- Maximum Temperature Sensitivity: 199 °C
- Number of Temperature Levels: 8
- Orientation: Vertical
- Reversibility: No
- Label Length: 18 mm
- Label Width: 51 mm



555421 160 °C

LABEL,TEMPERATURE SENSITIVE,SCALE E,204-260DEGC

Pack size: **10 x EA**

- Minimum Temperature Sensitivity: 204 °C
- Maximum Temperature Sensitivity: 260 °C
- Number of Temperature Levels: 8
- Orientation: Vertical
- Reversibility: No
- Label Length: 18 mm
- Label Width: 51 mm



555437 204 °C

11 LEVEL REVERSIBLE SCA STRIPS VERTICAL

Pack size: **10 x EA**

- Minimum Temperature Sensitivity: 0 °C
- Maximum Temperature Sensitivity: 50 °C
- Number of Temperature Levels: 11
- Labels Per Product: 10
- Orientation: Vertical
- Reversibility: Yes
- Label Length: 51 mm
- Label Width: 18 mm



9064599 0 °C

TRAFFIC LIGHT INDICATOR REVERSIBLE STRIP

Pack size: **10 x EA**

- Minimum Temperature Sensitivity: 50 °C
- Maximum Temperature Sensitivity: 70 °C
- Number of Temperature Levels: 3
- Labels Per Product: 10
- Reversibility: Yes
- Label Length: 52 mm
- Label Width: 48 mm



9064602 50 °C

RS PRO TEMPERATURE LABEL INDICATOR, 2°C TO 8°C, 2 LEVELS

Pack size: **10 x EA**

- Minimum Temperature Sensitivity: 2 °C
- Maximum Temperature Sensitivity: 8 °C
- Number of Temperature Levels: 2
- Labels Per Product: 10
- Orientation: Horizontal
- Reversibility: Yes
- Label Length: 40 mm
- Label Width: 96 mm



9064606 2 °C

11 LEVEL REVERSIBLE SCA STRIPS VERTICAL

Pack size: **10 x EA**

- Minimum Temperature Sensitivity: 50 °C
- Maximum Temperature Sensitivity: 100 °C
- Number of Temperature Levels: 11
- Labels Per Product: 10
- Orientation: Vertical
- Reversibility: Yes
- Label Length: 51 mm
- Label Width: 18 mm



9064609 50 °C

RS PRO TEMPERATURE LABEL INDICATOR, 1°C TO 12°C, 12 LEVELS

Pack size: **10 x EA**

- Minimum Temperature Sensitivity: 1 °C
- Maximum Temperature Sensitivity: 12 °C
- Number of Temperature Levels: 12
- Labels Per Product: 10
- Orientation: Horizontal
- Reversibility: Yes
- Label Length: 10 mm
- Label Width: 90 mm



9064612 1 °C

RS PRO TEMPERATURE LABEL INDICATOR, 50°C

Pack size: **10 x EA**

- Maximum Temperature Sensitivity: 50 °C
- Labels Per Product: 10
- Orientation: Vertical
- Label Diameter: 37 mm



9064615 50 °C

ROOM THERMOMETER REVERSIBLE 10C - 32C

Pack size: **10 x EA**

- Minimum Temperature Sensitivity: 10 °C
- Maximum Temperature Sensitivity: 32 °C
- Number of Temperature Levels: 12
- Labels Per Product: 10
- Orientation: Horizontal
- Reversibility: Yes
- Label Length: 10 mm
- Label Width: 96 mm



9064618 10 °C

RS PRO TEMPERATURE TRANSMITTER PT100 INPUT, 12 → 36 V DC, 0 → +100

Pack size: **1 x EA**

- Input Type: PT100
- Supply Voltage: 12 → 36 V dc
- Diameter: 42 mm
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: +100 °C
- Series: RS PRO
- Depth: 32 mm



1852284 PT100

RS PRO TEMPERATURE TRANSMITTER PT100 INPUT, 12 → 36 V DC, 0 → +200

Pack size: **1 x EA**

- Input Type: PT100
- Supply Voltage: 12 → 36 V dc
- Diameter: 42 mm
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: +200 °C
- Series: RS PRO
- Depth: 32 mm



1852290 PT100

RS PRO TEMPERATURE TRANSMITTER THERMOCOUPLE TYPE J INPUT, 12 →

Pack size: **1 x EA**

- Input Type: Thermocouple Type J
- Supply Voltage: 12 → 36 V dc
- Diameter: 42 mm
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: +300 °C
- Series: RS PRO
- Depth: 32 mm



1852341 Thermocouple

RS PRO TEMPERATURE TRANSMITTER THERMOCOUPLE TYPE K INPUT, 12 →

Pack size: **1 x EA**

- Input Type: Thermocouple Type K
- Supply Voltage: 12 → 36 V dc
- Diameter: 42 mm
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: +200 °C
- Series: RS PRO
- Depth: 32 mm



1852357 Thermocouple

RS PRO TEMPERATURE TRANSMITTER THERMOCOUPLE TYPE K INPUT, 12 →

Pack size: **1 x EA**

- Input Type: Thermocouple Type K
- Supply Voltage: 12 → 36 V dc
- Diameter: 42 mm
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: +1100 °C
- Series: RS PRO
- Depth: 32 mm



1852363 Thermocouple

RS PRO TEMPERATURE TRANSMITTER PT100 INPUT, 10 → 30 V DC, 0 → +70 °C

Pack size: **1 x EA**

- Input Type: PT100
- Supply Voltage: 10 → 30 V dc
- Diameter: 42 mm
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: +70 °C
- Series: RS PRO
- Depth: 33 mm



3630216 PT100

RS PRO TEMPERATURE TRANSMITTER VARIOUS INPUT, 10 → 30 V DC

Pack size: **1 x EA**

- Input Type: Thermocouple Type J, Thermocouple Type K, Thermocouple Type T
- Supply Voltage: 10 → 30 V dc
- Diameter: 42 mm
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: +70 °C
- Series: RS PRO
- Depth: 23 mm



3630222 Thermocouple

RS PRO TEMPERATURE TRANSMITTER PT100 INPUT, 10 → 30 V DC, 0 → +70 °C

Pack size: **1 x EA**

- Input Type: PT100
- Supply Voltage: 10 → 30 V dc
- Diameter: 43 mm
- Minimum Operating Temperature: 0 °C
- Maximum Operating Temperature: +70 °C
- Series: RS PRO
- Depth: 21 mm



3630238 PT100

RS PRO TEMPERATURE TRANSMITTER VARIOUS INPUT, 8 → 30 V DC

Pack size: **1 x EA**

- Input Type: mV, Thermocouple Type E, Thermocouple Type J, Thermocouple Type K, Thermocouple Type N, Thermocouple Type R, Thermocouple Type S, Thermocouple Type T
- Supply Voltage: 8 → 30 V dc
- Diameter: 43 mm
- Minimum Operating Temperature: -20 °C
- Maximum Operating Temperature: +70 °C
- Series: RS PRO
- Depth: 21 mm



3817132 mV,

RS PRO TYPE J THERMOCOUPLE WIRE, 10M, UNSCREENED, PVC

Pack size: **10 x MTR**

- Length: 10 m
- Insulation Material: PVC
- Thermocouple Type: J
- Screened/Unscreened: Unscreened
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: BS



150010 10 m

RS PRO TYPE K THERMOCOUPLE WIRE, 10M, UNSCREENED, GLASS

Pack size: **10 x MTR**

- Length: 10 m
- Insulation Material: Glass Fibre
- Maximum Operating Temperature: +350 °C
- Thermocouple Type: K
- Screened/Unscreened: Unscreened
- Core Strands: 1/0.315 mm
- Cable Shape: Flat Pair
- Number of Strands: 2



151209 10 m

RS PRO TYPE K THERMOCOUPLE WIRE, 25M, UNSCREENED, PVC

Pack size: **25 x MTR**

- Length: 25 m
- Insulation Material: PVC
- Maximum Operating Temperature: +80 °C
- Thermocouple Type: K
- Screened/Unscreened: Unscreened
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2



151316 25 m

RS PRO TYPE K THERMOCOUPLE WIRE, 100M, PVC INSULATION,

Pack size: **100 x MTR**

- Length: 100 m
- Insulation Material: PVC
- Thermocouple Type: K
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: BS



158963 100 m

RS PRO TYPE E THERMOCOUPLE WIRE, 10M, PVC INSULATION,

Pack size: **1 x EA**

- Length: 10 m
- Insulation Material: PVC
- Thermocouple Type: E
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: IEC



1365863 10 m

RS PRO TYPE E THERMOCOUPLE WIRE, 25M, PVC INSULATION,

Pack size: **1 x EA**

- Length: 25 m
- Insulation Material: PVC
- Thermocouple Type: E
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: IEC



1365864 25 m

RS PRO TYPE E THERMOCOUPLE WIRE, 10M, PFA INSULATION,

Pack size: **1 x EA**

- Length: 10 m
- Insulation Material: PFA
- Thermocouple Type: E
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: IEC



1365865 10 m

RS PRO TYPE J THERMOCOUPLE WIRE, 25M, PFA INSULATION,

Pack size: **1 x EA**

- Length: 25 m
- Insulation Material: PFA
- Thermocouple Type: J
- Core Strands: 1/0.3 mm
- Number of Strands: 2
- Standards Met: IEC



1365866 25 m

RS PRO TYPE J THERMOCOUPLE WIRE, 10M, SCREENED, PFA

Pack size: **1 x EA**

- Length: 10 m
- Insulation Material: PFA
- Maximum Operating Temperature: +260 °C
- Thermocouple Type: J
- Screened/Unscreened: Screened
- Core Strands: 1/0.3 mm
- Cable Shape: Twin Twisted
- Number of Strands: 2



1780950 10 m

RS PRO TYPE K THERMOCOUPLE WIRE, 25M, PVC INSULATION, +105 °C

Pack size: **1 x EA**

- Length: 25 m
- Insulation Material: PVC
- Thermocouple Type: K
- Maximum Operating Temperature: +105 °C
- Core Strands: 23/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: IEC



1853004 25 m

RS PRO RESISTANCE THERMOMETER DETECTOR (RTD) WIRE, 5M,

Pack size: **1 x EA**

- Length: 5 m
- Insulation Material: PVC
- Screened/Unscreened: Screened
- Core Strands: 7/0.2 mm
- Number of Strands: 4



1853010 5 m

RS PRO TYPE K THERMOCOUPLE WIRE, 5M, GLASS FIBRE INSULATION,

Pack size: **1 x EA**

- Length: 5 m
- Insulation Material: Glass Fibre
- Thermocouple Type: K
- Maximum Operating Temperature: +350 °C
- Core Strands: 1/0.315 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: BS



1853011 5 m

RS PRO TYPE RTD RESISTANCE THERMOMETER DETECTOR (RTD)

Pack size: **1 x EA**

- Length: 5 m
- Insulation Material: Silicone Rubber
- Thermocouple Type: RTD
- Maximum Operating Temperature: +200 °C
- Core Strands: 7/0.2 mm
- Number of Strands: 4



1853014 5 m

RS PRO TYPE RTD RESISTANCE THERMOMETER DETECTOR (RTD)

Pack size: **1 x EA**

- Length: 5 m
- Insulation Material: PTFE
- Thermocouple Type: RTD
- Maximum Operating Temperature: +260 °C
- Core Strands: 7/0.2 mm
- Number of Strands: 4



1853015 5 m

RS PRO TYPE K THERMOCOUPLE WIRE, 5M, GLASS FIBRE INSULATION,

Pack size: **1 x EA**

- Length: 5 m
- Insulation Material: Glass Fibre
- Maximum Operating Temperature: +350 °C
- Thermocouple Type: K
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Voltage Rating: 220 → 250 V ac



1853016 5 m

RS PRO TYPE K THERMOCOUPLE WIRE, 5M, PFA INSULATION, +260°C

Pack size: **1 x EA**

- Length: 5 m
- Insulation Material: PFA
- Thermocouple Type: K
- Maximum Operating Temperature: +260 °C
- Core Strands: 1/0.315 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: IEC



1853019 5 m

RS PRO TYPE K THERMOCOUPLE WIRE, 5M, PFA INSULATION, +260°C

Pack size: **1 x EA**

- Length: 5 m
- Insulation Material: PFA
- Maximum Operating Temperature: +260 °C
- Thermocouple Type: K
- Core Strands: 1/0.2 mm
- Number of Strands: 2
- Standards Met: IEC



1853020 5 m

RS PRO TYPE K THERMOCOUPLE WIRE, 25M, PFA INSULATION, +250°C

Pack size: **1 x EA**

- Length: 25 m
- Insulation Material: PFA
- Thermocouple Type: K
- Maximum Operating Temperature: +250 °C
- Core Strands: 1/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: IEC



2000618 25 m

RS PRO TYPE K THERMOCOUPLE WIRE, 100M, HIGH TEMPERATURE

Pack size: **1 x EA**

- Length: 100 m
- Insulation Material: High Temperature Glass Fibre
- Maximum Operating Temperature: +700 °C
- Thermocouple Type: K
- Core Strands: 1/0.711 mm
- Number of Strands: 2
- Standards Met: ANSI



2000622 100 m

RS PRO TYPE K THERMOCOUPLE WIRE, 25M, PFA INSULATION, +250°C

Pack size: **1 x EA**

- Length: 25 m
- Insulation Material: PFA
- Thermocouple Type: K
- Maximum Operating Temperature: +250 °C
- Core Strands: 1/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: ANSI



2000623 25 m

RS PRO TYPE K THERMOCOUPLE WIRE, 25M, PFA INSULATION, +250°C

Pack size: **1 x EA**

- Length: 25 m
- Insulation Material: PFA
- Thermocouple Type: K
- Maximum Operating Temperature: +250 °C
- Core Strands: 1/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: ANSI



2000625 25 m

RS PRO TYPE K THERMOCOUPLE WIRE, 100M, PFA INSULATION,

Pack size: **1 x EA**

- Length: 100 m
- Insulation Material: PFA
- Thermocouple Type: K
- Maximum Operating Temperature: +250 °C
- Core Strands: 1/0.5 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: ANSI



2000628 100 m

RS PRO TYPE J THERMOCOUPLE WIRE, 50M, UNSCREENED, PVC

Pack size: **1 x EA**

- Length: 50 m
- Insulation Material: PVC
- Maximum Operating Temperature: +105 °C
- Thermocouple Type: J
- Screened/Unscreened: Unscreened
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2



2154870 50 m

RS PRO TYPE J THERMOCOUPLE WIRE, 10M, SCREENED, PVC MYLAR

Pack size: **1 x EA**

- Length: 10 m
- Insulation Material: PVC Mylar
- Maximum Operating Temperature: +105 °C
- Thermocouple Type: J
- Screened/Unscreened: Screened
- Core Strands: 7/0.2 mm
- Cable Shape: Twisted
- Number of Strands: 2



2154871 10 m

RS PRO TYPE J THERMOCOUPLE WIRE, 10M, UNSCREENED, PTFE

Pack size: **1 x EA**

- Length: 10 m
- Insulation Material: PTFE
- Maximum Operating Temperature: +260 °C
- Thermocouple Type: J
- Screened/Unscreened: Unscreened
- Core Strands: 13/0.508 mm
- Cable Shape: Twin Twisted
- Number of Strands: 2



2154882 10 m

RS PRO TYPE J THERMOCOUPLE WIRE, 10M, UNSCREENED, PFA

Pack size: **1 x EA**

- Length: 10 m
- Insulation Material: PFA
- Maximum Operating Temperature: +260 °C
- Thermocouple Type: J
- Screened/Unscreened: Unscreened
- Core Strands: 1/0.508 mm
- Cable Shape: Twin Twisted
- Number of Strands: 2



2154886 10 m

RS PRO TYPE J THERMOCOUPLE WIRE, 100M, UNSCREENED, PTFE

Pack size: **1 x EA**

- Length: 100 m
- Insulation Material: PTFE
- Maximum Operating Temperature: +260 °C
- Thermocouple Type: J
- Screened/Unscreened: Unscreened
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2



2154888 100 m

RS PRO TYPE J THERMOCOUPLE WIRE, 10M, UNSCREENED, SILICONE

Pack size: **1 x EA**

- Length: 10 m
- Insulation Material: Silicone Rubber
- Maximum Operating Temperature: +200 °C
- Thermocouple Type: J
- Screened/Unscreened: Unscreened
- Core Strands: 7/0.2 mm
- Cable Shape: Twisted
- Number of Strands: 2



2154889 10 m

RS PRO TYPE K THERMOCOUPLE WIRE, 10M, UNSCREENED, PVC

Pack size: **1 x EA**

- Length: 10 m
- Insulation Material: PVC
- Maximum Operating Temperature: +105 °C
- Thermocouple Type: K
- Screened/Unscreened: Unscreened
- Core Strands: 13/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2



2154893 10 m

RS PRO TYPE K THERMOCOUPLE WIRE, 50M, UNSCREENED, PVC

Pack size: **1 x EA**

- Length: 50 m
- Insulation Material: PVC
- Maximum Operating Temperature: +105 °C
- Thermocouple Type: K
- Screened/Unscreened: Unscreened
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2



2154895 50 m

RS PRO TYPE K THERMOCOUPLE WIRE, 10M, UNSCREENED, PVC

Pack size: **1 x EA**

- Length: 10 m
- Insulation Material: PVC
- Maximum Operating Temperature: +105 °C
- Thermocouple Type: K
- Screened/Unscreened: Unscreened
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2



2154896 10 m

RS PRO TYPE K THERMOCOUPLE WIRE, 10M, UNSCREENED, PTFE

Pack size: **1 x EA**

- Length: 10 m
- Insulation Material: PTFE
- Maximum Operating Temperature: +260 °C
- Thermocouple Type: K
- Screened/Unscreened: Unscreened
- Core Strands: 1/0.508 mm
- Cable Shape: Twin Twisted
- Number of Strands: 2



2154899 10 m

RS PRO TYPE K THERMOCOUPLE WIRE, 10M, UNSCREENED, PFA

Pack size: **1 x EA**

- Length: 10 m
- Insulation Material: PFA
- Maximum Operating Temperature: +260 °C
- Thermocouple Type: K
- Screened/Unscreened: Unscreened
- Core Strands: 1/0.3 mm
- Cable Shape: Twin Twisted
- Number of Strands: 2



2154901 10 m

RS PRO TYPE K THERMOCOUPLE WIRE, 10M, UNSCREENED, PFA

Pack size: **1 x EA**

- Length: 10 m
- Insulation Material: PFA
- Maximum Operating Temperature: +260 °C
- Thermocouple Type: K
- Screened/Unscreened: Unscreened
- Core Strands: 1/0.3 mm
- Cable Shape: Twin Twisted
- Number of Strands: 2



2154902 10 m

RS PRO TYPE K THERMOCOUPLE WIRE, 10M, UNSCREENED, PTFE

Pack size: **1 x EA**

- Length: 10 m
- Insulation Material: PTFE
- Maximum Operating Temperature: +260 °C
- Thermocouple Type: K
- Screened/Unscreened: Unscreened
- Core Strands: 1/0.315 mm
- Cable Shape: Flat Pair
- Number of Strands: 2



2154905 10 m

RS PRO TYPE K THERMOCOUPLE WIRE, 50M, UNSCREENED, GLASS

Pack size: **1 x EA**

- Length: 50 m
- Insulation Material: Glass Fibre
- Maximum Operating Temperature: +350 °C
- Thermocouple Type: K
- Screened/Unscreened: Unscreened
- Core Strands: 1/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2



2154927 50 m

RS PRO TYPE K THERMOCOUPLE WIRE, 10M, UNSCREENED, PVC

Pack size: **1 x EA**

- Length: 10 m
- Insulation Material: PVC
- Maximum Operating Temperature: +105 °C
- Thermocouple Type: K
- Screened/Unscreened: Unscreened
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2



2154936 10 m

RS PRO TYPE K THERMOCOUPLE WIRE, 50M, UNSCREENED, PVC

Pack size: **1 x EA**

- Length: 50 m
- Insulation Material: PVC
- Maximum Operating Temperature: +105 °C
- Thermocouple Type: K
- Screened/Unscreened: Unscreened
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2



2154937 50 m

RS PRO TYPE K THERMOCOUPLE WIRE, 10M, UNSCREENED, PVC

Pack size: **1 x EA**

- Length: 10 m
- Insulation Material: PVC
- Maximum Operating Temperature: +260 °C
- Thermocouple Type: K
- Screened/Unscreened: Unscreened
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2



2154938 10 m

RS PRO TYPE K THERMOCOUPLE WIRE, 25M, UNSCREENED, PVC

Pack size: **25 x MTR**

- Length: 25 m
- Insulation Material: PVC
- Maximum Operating Temperature: +105 °C
- Thermocouple Type: K
- Screened/Unscreened: Unscreened
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2



2194551 25 m

RS PRO TYPE K THERMOCOUPLE WIRE, 100M, UNSCREENED, PVC

Pack size: **100 x MTR**

- Length: 100 m
- Insulation Material: PVC
- Maximum Operating Temperature: +105 °C
- Thermocouple Type: K
- Screened/Unscreened: Unscreened
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2



2194573 100 m

RS PRO TYPE K THERMOCOUPLE WIRE, 10M, UNSCREENED, GLASS

Pack size: **10 x MTR**

- Length: 10 m
- Insulation Material: Glass Fibre
- Maximum Operating Temperature: +400 °C
- Thermocouple Type: K
- Screened/Unscreened: Unscreened
- Core Strands: 1/0.315 mm
- Cable Shape: Flat Pair
- Number of Strands: 2



2194589 10 m

RS PRO TYPE K THERMOCOUPLE WIRE, 10M, UNSCREENED, GLASS

Pack size: **10 x MTR**

- Length: 10 m
- Insulation Material: Glass Fibre
- Maximum Operating Temperature: +400 °C
- Thermocouple Type: K
- Screened/Unscreened: Unscreened
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2



2194595 10 m

RS PRO TYPE N THERMOCOUPLE WIRE, 10M, UNSCREENED, PVC

Pack size: **10 x MTR**

- Length: 10 m
- Insulation Material: PVC
- Maximum Operating Temperature: +105 °C
- Thermocouple Type: N
- Screened/Unscreened: Unscreened
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2



2194668 10 m

RS PRO TYPE T THERMOCOUPLE WIRE, 10M, UNSCREENED, PVC

Pack size: **10 x MTR**

- Length: 10 m
- Insulation Material: PVC
- Maximum Operating Temperature: +105 °C
- Thermocouple Type: T
- Screened/Unscreened: Unscreened
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2



2194703 10 m

RS PRO TYPE J THERMOCOUPLE WIRE, 10M, UNSCREENED, PVC

Pack size: **10 x MTR**

- Length: 10 m
- Insulation Material: PVC
- Maximum Operating Temperature: +105 °C
- Thermocouple Type: J
- Screened/Unscreened: Unscreened
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2



2194753 10 m

RS PRO TYPE R/S THERMOCOUPLE WIRE, 10M, UNSCREENED, PVC

Pack size: **10 x MTR**

- Length: 10 m
- Insulation Material: PVC
- Maximum Operating Temperature: +105 °C
- Thermocouple Type: R/S
- Screened/Unscreened: Unscreened
- Core Strands: 13/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2



2194769 10 m

RS PRO TYPE E THERMOCOUPLE WIRE, 25M, UNSCREENED, PFA

Pack size: **1 x EA**

- Insulation Material: PFA
- Length: 25 m
- Maximum Operating Temperature: +260 °C
- Thermocouple Type: E
- Screened/Unscreened: Unscreened
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2



2209471 PFA

RS PRO TYPE E THERMOCOUPLE WIRE, 50M, UNSCREENED, PFA

Pack size: **1 x EA**

- Length: 50 m
- Insulation Material: PFA
- Maximum Operating Temperature: +260 °C
- Thermocouple Type: E
- Screened/Unscreened: Unscreened
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2



2209472 50 m

RS PRO TYPE E THERMOCOUPLE WIRE, 100M, UNSCREENED, PFA

Pack size: **1 x EA**

- Length: 100 m
- Insulation Material: PFA
- Maximum Operating Temperature: +260 °C
- Thermocouple Type: E
- Screened/Unscreened: Unscreened
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2



2209474 100 m

RS PRO TYPE T THERMOCOUPLE WIRE, 100M, UNSCREENED, GLASS

Pack size: **1 x EA**

- Length: 100 m
- Insulation Material: Glass Fibre
- Maximum Operating Temperature: +350 °C
- Thermocouple Type: T
- Screened/Unscreened: Unscreened
- Core Strands: 1/0.315 mm
- Cable Shape: Flat Pair
- Number of Strands: 2



2209481 100 m

RS PRO TYPE K THERMOCOUPLE & EXTENSION WIRE, 10M, SCREENED

Pack size: **1 x EA**

- Length: 10 m
- Insulation Material: PFA
- Maximum Operating Temperature: +260 °C
- Thermocouple Type: K
- Screened/Unscreened: Screened
- Cable Shape: Twisted
- Number of Strands: 2
- Standards Met: IEC



2209492 10 m

RS PRO TYPE K THERMOCOUPLE & EXTENSION WIRE, 10M, SCREENED

Pack size: **1 x EA**

- Length: 10 m
- Insulation Material: PFA
- Maximum Operating Temperature: +260 °C
- Thermocouple Type: K
- Screened/Unscreened: Screened
- Cable Shape: Twisted
- Number of Strands: 2
- Standards Met: IEC



2209493 10 m

RS PRO TYPE K THERMOCOUPLE & EXTENSION WIRE, 1M, SCREENED

Pack size: **1 x EA**

- Length: 1 m
- Insulation Material: PFA
- Maximum Operating Temperature: +260 °C
- Thermocouple Type: K
- Screened/Unscreened: Screened
- Cable Shape: Twisted
- Number of Strands: 2
- Standards Met: IEC



2209494 1 m

RS PRO TYPE K THERMOCOUPLE & EXTENSION WIRE, 3M, SCREENED

Pack size: **1 x EA**

- Length: 3 m
- Insulation Material: PFA
- Maximum Operating Temperature: +260 °C
- Thermocouple Type: K
- Screened/Unscreened: Screened
- Cable Shape: Twisted
- Number of Strands: 2
- Standards Met: IEC



2209495 3 m

RS PRO TYPE K THERMOCOUPLE & EXTENSION WIRE, 3M, SCREENED

Pack size: **1 x EA**

- Length: 3 m
- Insulation Material: PFA
- Maximum Operating Temperature: +260 °C
- Thermocouple Type: K
- Screened/Unscreened: Screened
- Cable Shape: Twisted
- Number of Strands: 2
- Standards Met: IEC



2209497 3 m

RS PRO TYPE T THERMOCOUPLE WIRE, 10M, UNSCREENED, PTFE

Pack size: **1 x EA**

- Length: 10 m
- Insulation Material: PTFE
- Maximum Operating Temperature: +260 °C
- Thermocouple Type: T
- Screened/Unscreened: Unscreened
- Core Strands: 1/0.315 mm
- Cable Shape: Twin Twisted
- Number of Strands: 2



2209501 10 m

RS PRO TYPE T THERMOCOUPLE WIRE, 100M, UNSCREENED, PTFE

Pack size: **1 x EA**

- Length: 100 m
- Insulation Material: PTFE
- Maximum Operating Temperature: +260 °C
- Thermocouple Type: T
- Screened/Unscreened: Unscreened
- Core Strands: 1/0.315 mm
- Cable Shape: Twin Twisted
- Number of Strands: 2



2209503 100 m

RS PRO TYPE U THERMOCOUPLE WIRE, 25M, SCREENED, GLASS FIBRE

Pack size: **1 x EA**

- Length: 25 m
- Insulation Material: Glass Fibre
- Maximum Operating Temperature: +350 °C
- Thermocouple Type: U
- Screened/Unscreened: Screened
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2



2209506 25 m

RS PRO TYPE U THERMOCOUPLE WIRE, 100M, SCREENED, GLASS FIBRE

Pack size: **1 x EA**

- Length: 100 m
- Insulation Material: Glass Fibre
- Maximum Operating Temperature: +350 °C
- Thermocouple Type: U
- Screened/Unscreened: Screened
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2



2209508 100 m

RS PRO TYPE T THERMOCOUPLE WIRE, 10M, UNSCREENED, PTFE

Pack size: **1 x EA**

- Length: 10 m
- Insulation Material: PTFE
- Maximum Operating Temperature: +260 °C
- Thermocouple Type: T
- Screened/Unscreened: Unscreened
- Core Strands: 1/0.376 mm
- Cable Shape: Single Shot
- Number of Strands: 2



2209523 10 m

RS PRO TYPE K THERMOCOUPLE & EXTENSION WIRE, 10M, UNSCREENED,

Pack size: **1 x EA**

- Length: 10 m
- Insulation Material: PVC
- Maximum Operating Temperature: +105 °C
- Thermocouple Type: K
- Screened/Unscreened: Unscreened
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2



2318468 10 m

RS PRO TYPE K THERMOCOUPLE & EXTENSION WIRE, 1M, UNSCREENED,

Pack size: **1 x EA**

- Length: 1 m
- Insulation Material: PVC
- Maximum Operating Temperature: +105 °C
- Thermocouple Type: K
- Screened/Unscreened: Unscreened
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2



2318472 1 m

RS PRO TYPE K THERMOCOUPLE WIRE, 25M, UNSCREENED, PVC

Pack size: **25 x MTR**

- Length: 25 m
- Insulation Material: PVC
- Maximum Operating Temperature: +105 °C
- Thermocouple Type: K
- Screened/Unscreened: Unscreened
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2



2363820 25 m

RS PRO TYPE K THERMOCOUPLE WIRE, 25M, UNSCREENED, GLASS

Pack size: **25 x MTR**

- Length: 25 m
- Insulation Material: Glass Fibre
- Maximum Operating Temperature: +400 °C
- Thermocouple Type: K
- Screened/Unscreened: Unscreened
- Core Strands: 1/0.315 mm
- Cable Shape: Flat Pair
- Number of Strands: 2



2363836 25 m

RS PRO TYPE K THERMOCOUPLE WIRE, 25M, SCREENED, GLASS FIBRE

Pack size: **25 x MTR**

- Length: 25 m
- Insulation Material: Glass Fibre
- Maximum Operating Temperature: +400 °C
- Thermocouple Type: K
- Screened/Unscreened: Screened
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2



2363842 25 m

RS PRO TYPE K THERMOCOUPLE WIRE, 25M, UNSCREENED, PTFE

Pack size: **25 x MTR**

- Length: 25 m
- Insulation Material: PTFE
- Maximum Operating Temperature: +250 °C
- Thermocouple Type: K
- Screened/Unscreened: Unscreened
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2



2363858 25 m

RS PRO TYPE K THERMOCOUPLE WIRE, 25M, SCREENED, PVC

Pack size: **25 x MTR**

- Length: 25 m
- Insulation Material: PVC
- Maximum Operating Temperature: +105 °C
- Thermocouple Type: K
- Screened/Unscreened: Screened
- Core Strands: 7/0.2 mm
- Cable Shape: Multicore
- Number of Strands: 2



2363864 25 m

RS PRO TYPE T THERMOCOUPLE WIRE, 25M, UNSCREENED, PVC

Pack size: **25 x MTR**

- Length: 25 m
- Insulation Material: PVC
- Maximum Operating Temperature: +105 °C
- Thermocouple Type: T
- Screened/Unscreened: Unscreened
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2



2363870 25 m

RS PRO TYPE T THERMOCOUPLE WIRE, 10M, UNSCREENED, GLASS

Pack size: **10 x MTR**

- Length: 10 m
- Insulation Material: Glass Fibre
- Maximum Operating Temperature: +400 °C
- Thermocouple Type: T
- Screened/Unscreened: Unscreened
- Core Strands: 1/0.315 mm
- Cable Shape: Flat Pair
- Number of Strands: 2



2363909 10 m

RS PRO TYPE J THERMOCOUPLE WIRE, 100M, UNSCREENED, PVC

Pack size: **100 x MTR**

- Length: 100 m
- Insulation Material: PVC
- Maximum Operating Temperature: +105 °C
- Thermocouple Type: J
- Screened/Unscreened: Unscreened
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2



2363915 100 m

RS PRO TYPE J THERMOCOUPLE WIRE, 25M, SCREENED, PVC

Pack size: **25 x MTR**

- Length: 25 m
- Insulation Material: PVC
- Maximum Operating Temperature: +105 °C
- Thermocouple Type: J
- Screened/Unscreened: Screened
- Core Strands: 7/0.2 mm
- Cable Shape: Multicore
- Number of Strands: 2



2363921 25 m

RS PRO TYPE J THERMOCOUPLE WIRE, 25M, SCREENED, GLASS FIBRE

Pack size: **25 x MTR**

- Length: 25 m
- Insulation Material: Glass Fibre
- Maximum Operating Temperature: +400 °C
- Thermocouple Type: J
- Screened/Unscreened: Screened
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2



2363937 25 m

RS PRO TYPE K THERMOCOUPLE WIRE, 25M, SCREENED, PVC

Pack size: **25 x MTR**

- Length: 25 m
- Insulation Material: PVC
- Maximum Operating Temperature: +105 °C
- Thermocouple Type: K
- Screened/Unscreened: Screened
- Core Strands: 7/0.2 mm
- Cable Shape: Multicore
- Number of Strands: 2



2363959 25 m

RS PRO TYPE RTD RESISTANCE THERMOMETER DETECTOR (RTD)

Pack size: **1 x EA**

- Length: 25 m
- Insulation Material: PVC
- Maximum Operating Temperature: +105 °C
- Thermocouple Type: RTD
- Screened/Unscreened: Screened
- Core Strands: 7/0.2 mm
- Cable Shape: Multicore
- Number of Strands: 4



2904954 25 m

RS PRO TYPE K THERMOCOUPLE WIRE, 25M, UNSCREENED, PTFE

Pack size: **1 x EA**

- Length: 25 m
- Insulation Material: PTFE
- Maximum Operating Temperature: +250 °C
- Thermocouple Type: K
- Screened/Unscreened: Unscreened
- Core Strands: 1/0.2 mm
- Cable Shape: Twin Twisted
- Number of Strands: 2



3630389 25 m

RS PRO TYPE T THERMOCOUPLE WIRE, 25M, UNSCREENED, PTFE

Pack size: **1 x EA**

- Length: 25 m
- Insulation Material: PTFE
- Maximum Operating Temperature: +250 °C
- Thermocouple Type: T
- Screened/Unscreened: Unscreened
- Core Strands: 1/0.2 mm
- Cable Shape: Single Core
- Number of Strands: 2



3630402 25 m

RS PRO TYPE T THERMOCOUPLE WIRE, 25M, UNSCREENED, PTFE

Pack size: **1 x EA**

- Length: 25 m
- Insulation Material: PTFE
- Maximum Operating Temperature: +250 °C
- Thermocouple Type: T
- Screened/Unscreened: Unscreened
- Core Strands: 1/0.315 mm
- Cable Shape: Flat Pair
- Number of Strands: 2



3630418 25 m

RS PRO TYPE RTD THERMOCOUPLE & EXTENSION WIRE, 25M, SCREENED,

Pack size: **25 x MTR**

- Length: 25 m
- Insulation Material: PVC
- Thermocouple Type: RTD
- Maximum Operating Temperature: +80 °C
- Screened/Unscreened: Screened
- Core Strands: 7/0.2 mm
- Cable Shape: Multicore
- Number of Strands: 7



4071466 25 m

RS PRO TYPE K THERMOCOUPLE & EXTENSION WIRE, 20M,

Pack size: **20 x MTR**

- Length: 20 m
- Insulation Material: Fibreglass
- Maximum Operating Temperature: +600 °C
- Thermocouple Type: K
- Screened/Unscreened: Unscreened
- Cable Shape: Single Core
- Number of Strands: 2



4071545 20 m

RS PRO TYPE J THERMOCOUPLE & EXTENSION WIRE, 20M,

Pack size: **20 x MTR**

- Length: 20 m
- Insulation Material: Glass Fibre
- Maximum Operating Temperature: +600 °C
- Thermocouple Type: J
- Screened/Unscreened: Unscreened
- Cable Shape: Single Core
- Number of Strands: 2



4071551 20 m

RS PRO TYPE K THERMOCOUPLE & EXTENSION WIRE, 20M,

Pack size: **20 x MTR**

- Length: 20 m
- Insulation Material: Fibreglass
- Maximum Operating Temperature: +800 °C
- Thermocouple Type: K
- Screened/Unscreened: Unscreened
- Cable Shape: Single Core
- Number of Strands: 2



4071567 20 m

RS PRO TYPE K THERMOCOUPLE & EXTENSION WIRE, 20M,

Pack size: **20 x MTR**

- Length: 20 m
- Insulation Material: Ceramic Fibre
- Maximum Operating Temperature: +1200 °C
- Thermocouple Type: K
- Screened/Unscreened: Unscreened
- Cable Shape: Single Core
- Number of Strands: 2



4071573 20 m

RS PRO TYPE T THERMOCOUPLE WIRE, 25M, UNSCREENED, SILICONE

Pack size: **1 x EA**

- Length: 25 m
- Insulation Material: Silicone Rubber
- Maximum Operating Temperature: +200 °C
- Thermocouple Type: T
- Screened/Unscreened: Unscreened
- Core Strands: 7/0.2 mm
- Cable Shape: Multicore
- Number of Strands: 2



4554236 25 m

RS PRO TYPE RTD RESISTANCE THERMOMETER DETECTOR (RTD)

Pack size: **1 x EA**

- Length: 25 m
- Insulation Material: PTFE
- Thermocouple Type: RTD
- Maximum Operating Temperature: +200 °C
- Screened/Unscreened: Unscreened
- Core Strands: 7/0.2 mm
- Cable Shape: Single Core
- Number of Strands: 4



4554242 25 m

RS PRO TYPE J THERMOCOUPLE WIRE, 25M, UNSCREENED, PTFE

Pack size: **25 x MTR**

- Length: 25 m
- Insulation Material: PTFE
- Maximum Operating Temperature: +250 °C
- Thermocouple Type: J
- Screened/Unscreened: Unscreened
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2



4554258 25 m

RS PRO TYPE RTD RESISTANCE THERMOMETER DETECTOR (RTD)

Pack size: **1 x EA**

- Length: 10 m
- Insulation Material: PVC
- Thermocouple Type: RTD
- Maximum Operating Temperature: +105 °C
- Screened/Unscreened: Screened
- Core Strands: 7/0.2 mm
- Cable Shape: Multicore
- Number of Strands: 4



4929753 10 m

RS PRO RESISTANCE THERMOMETER DETECTOR (RTD) WIRE, 10M,

Pack size: **1 x EA**

- Length: 10 m
- Insulation Material: PTFE
- Maximum Operating Temperature: +260 °C
- Screened/Unscreened: Screened
- Core Strands: 7/0.2 mm
- Cable Shape: Multicore
- Number of Strands: 4



4929775 10 m

RS PRO TYPE K THERMOCOUPLE WIRE, 100M, UNSCREENED, PVC

Pack size: **100 x MTR**

- Length: 100 m
- Insulation Material: PVC
- Maximum Operating Temperature: +105 °C
- Thermocouple Type: K
- Screened/Unscreened: Unscreened
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2



6117889 100 m

RS PRO TYPE K THERMOCOUPLE WIRE, 100M, SCREENED, PVC

Pack size: **100 x MTR**

- Length: 100 m
- Insulation Material: PVC
- Thermocouple Type: K
- Maximum Operating Temperature: +105 °C
- Screened/Unscreened: Screened
- Core Strands: 7/0.2 mm
- Cable Shape: Multicore
- Number of Strands: 2



6117895 100 m

RS PRO TYPE R/S THERMOCOUPLE WIRE, 25M, UNSCREENED, PVC

Pack size: **25 x MTR**

- Length: 25 m
- Insulation Material: PVC
- Maximum Operating Temperature: +105 °C
- Thermocouple Type: R/S
- Screened/Unscreened: Unscreened
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2



6117902 25 m

RS PRO TYPE J THERMOCOUPLE WIRE, 100M, SCREENED, PVC

Pack size: **100 x MTR**

- Length: 100 m
- Insulation Material: PVC
- Maximum Operating Temperature: +105 °C
- Thermocouple Type: J
- Screened/Unscreened: Screened
- Core Strands: 7/0.2 mm
- Cable Shape: Multicore
- Number of Strands: 2




6117918 100 m

RS PRO TYPE K THERMOCOUPLE WIRE, 100M, SCREENED, PVC

Pack size: **100 x MTR**

- Length: 100 m
- Insulation Material: PVC
- Maximum Operating Temperature: +105 °C
- Thermocouple Type: K
- Screened/Unscreened: Screened
- Core Strands: 7/0.2 mm
- Cable Shape: Multicore
- Number of Strands: 2



6117924 100 m

RS PRO TYPE K THERMOCOUPLE WIRE, 100M, UNSCREENED, PFA

Pack size: 100 x MTR

- Length: 100 m
- Insulation Material: PFA
- Maximum Operating Temperature: +260 °C
- Thermocouple Type: K
- Screened/Unscreened: Unscreened
- Core Strands: 1/0.2 mm
- Cable Shape: Multicore
- Number of Strands: 2



6117946 100 m

RS PRO TYPE T THERMOCOUPLE WIRE, 100M, UNSCREENED, PFA

Pack size: 100 x MTR

- Length: 100 m
- Insulation Material: PFA
- Maximum Operating Temperature: +260 °C
- Thermocouple Type: T
- Screened/Unscreened: Unscreened
- Core Strands: 1/0.2 mm
- Cable Shape: Multicore
- Number of Strands: 2



6117952 100 m

RS PRO TYPE K THERMOCOUPLE WIRE, 50M, UNSCREENED, PFA

Pack size: 50 x MTR

- Length: 50 m
- Insulation Material: PFA
- Maximum Operating Temperature: +260 °C
- Thermocouple Type: K
- Screened/Unscreened: Unscreened
- Core Strands: 1/0.2 mm
- Cable Shape: Multicore
- Number of Strands: 2



6117968 50 m

RS PRO TYPE T THERMOCOUPLE WIRE, 50M, UNSCREENED, PFA

Pack size: 50 x MTR

- Length: 50 m
- Insulation Material: PFA
- Maximum Operating Temperature: +260 °C
- Thermocouple Type: T
- Screened/Unscreened: Unscreened
- Core Strands: 1/0.2 mm
- Cable Shape: Twisted
- Number of Strands: 2



6117974 50 m

RS PRO TYPE K THERMOCOUPLE WIRE, 25M, UNSCREENED, PFA

Pack size: 25 x MTR

- Length: 25 m
- Insulation Material: PFA
- Maximum Operating Temperature: +260 °C
- Thermocouple Type: K
- Screened/Unscreened: Unscreened
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2



6117980 25 m

RS PRO TYPE N THERMOCOUPLE WIRE, 25M, UNSCREENED, PFA

Pack size: 25 x MTR

- Length: 25 m
- Insulation Material: PFA
- Maximum Operating Temperature: +250 °C
- Thermocouple Type: N
- Screened/Unscreened: Unscreened
- Core Strands: 1/0.2 mm
- Cable Shape: Twisted
- Number of Strands: 2



6117996 25 m

RS PRO TYPE K THERMOCOUPLE WIRE, 50M, UNSCREENED, PFA

Pack size: 50 x MTR

- Length: 50 m
- Insulation Material: PFA
- Maximum Operating Temperature: +260 °C
- Thermocouple Type: K
- Screened/Unscreened: Unscreened
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2



6118006 50 m

RS PRO TYPE K THERMOCOUPLE WIRE, 25M, UNSCREENED, PFA

Pack size: 25 x MTR

- Length: 25 m
- Insulation Material: PFA
- Maximum Operating Temperature: +250 °C
- Thermocouple Type: K
- Screened/Unscreened: Unscreened
- Core Strands: 1/0.315 mm
- Cable Shape: Flat Pair
- Number of Strands: 2



6118012 25 m

RS PRO TYPE T THERMOCOUPLE WIRE, 50M, UNSCREENED, PFA

Pack size: 50 x MTR

- Length: 50 m
- Insulation Material: PFA
- Maximum Operating Temperature: +260 °C
- Thermocouple Type: T
- Screened/Unscreened: Unscreened
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2



6118040 50 m

RS PRO TYPE J THERMOCOUPLE WIRE, 50M, UNSCREENED, PFA

Pack size: 50 x MTR

- Length: 50 m
- Insulation Material: PFA
- Maximum Operating Temperature: +260 °C
- Thermocouple Type: J
- Screened/Unscreened: Unscreened
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2



6118056 50 m

RS PRO TYPE N THERMOCOUPLE WIRE, 25M, UNSCREENED, PFA

Pack size: 25 x MTR

- Length: 25 m
- Insulation Material: PFA
- Maximum Operating Temperature: +260 °C
- Thermocouple Type: N
- Screened/Unscreened: Unscreened
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2



6118062 25 m

RS PRO RESISTANCE THERMOMETER DETECTOR (RTD) WIRE, 10M,

Pack size: 10 x MTR

- Length: 10 m
- Insulation Material: PFA
- Maximum Operating Temperature: +260 °C
- Screened/Unscreened: Screened
- Core Strands: 7/0.2 mm
- Cable Shape: Multicore
- Number of Strands: 4



6118078 10 m

RS PRO RESISTANCE THERMOMETER DETECTOR (RTD) WIRE, 25M,

Pack size: 25 x MTR

- Length: 25 m
- Insulation Material: PFA
- Maximum Operating Temperature: +260 °C
- Screened/Unscreened: Screened
- Core Strands: 7/0.2 mm
- Cable Shape: Multicore
- Number of Strands: 4



6118090 25 m

RS PRO RESISTANCE THERMOMETER DETECTOR (RTD) WIRE, 25M,

Pack size: **25 x MTR**

- Length: 25 m
- Insulation Material: PFA
- Maximum Operating Temperature: +260 °C
- Screened/Unscreened: Screened
- Core Strands: 7/0.2 mm
- Cable Shape: Multicore
- Number of Strands: 6



6118107 25 m

RS PRO RESISTANCE THERMOMETER DETECTOR (RTD) WIRE, 50M,

Pack size: **50 x MTR**

- Length: 50 m
- Insulation Material: PVC
- Maximum Operating Temperature: +105 °C
- Screened/Unscreened: Screened
- Core Strands: 7/0.2 mm
- Cable Shape: Multicore
- Number of Strands: 4



6118129 50 m

RS PRO TYPE T THERMOCOUPLE WIRE, 100M, UNSCREENED, PVC

Pack size: **100 x MTR**

- Length: 100 m
- Insulation Material: PVC
- Maximum Operating Temperature: +105 °C
- Thermocouple Type: T
- Screened/Unscreened: Unscreened
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2



7621146 100 m

RS PRO TYPE K EXTENSION CABLE, 2M, PVC INSULATION, +220°C MAX,

Pack size: **1 x EA**

- Length: 2 m
- Insulation Material: PVC
- Thermocouple Type: K
- Maximum Operating Temperature: +220 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Multicore
- Number of Strands: 2
- Standards Met: IEC, RoHS Compliant



7686581 2 m

RS PRO TYPE T THERMOCOUPLE WIRE, 25M, SCREENED, PVC

Pack size: **25 x MTR**

- Length: 25 m
- Insulation Material: PVC
- Maximum Operating Temperature: +105 °C
- Thermocouple Type: T
- Screened/Unscreened: Screened
- Core Strands: 7/0.2 mm
- Cable Shape: Twisted
- Number of Strands: 2



7621140 25 m

RS PRO TYPE K THERMOCOUPLE WIRE, 100M, UNSCREENED, PVC

Pack size: **100 x MTR**

- Length: 100 m
- Insulation Material: PVC
- Maximum Operating Temperature: +105 °C
- Thermocouple Type: K
- Screened/Unscreened: Unscreened
- Core Strands: 13/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2



7621152 100 m

RS PRO TYPE J EXTENSION CABLE, 5M, PVC INSULATION, +220°C MAX,

Pack size: **1 x EA**

- Length: 5 m
- Insulation Material: PVC
- Thermocouple Type: J
- Maximum Operating Temperature: +220 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Multicore
- Number of Strands: 2
- Standards Met: IEC, RoHS Compliant



7686591 5 m

RS PRO TYPE K EXTENSION CABLE, 5M, PVC INSULATION, +220°C MAX,

Pack size: **1 x EA**

- Length: 5 m
- Insulation Material: PVC
- Thermocouple Type: K
- Maximum Operating Temperature: +220 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Multicore
- Number of Strands: 2
- Standards Met: IEC, RoHS Compliant



7686585 5 m

RS PRO TYPE K EXTENSION CABLE, 10M, PVC INSULATION, +220°C MAX,

Pack size: **1 x EA**

- Length: 10 m
- Insulation Material: PVC
- Thermocouple Type: K
- Maximum Operating Temperature: +220 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Multicore
- Number of Strands: 2
- Standards Met: IEC, RoHS Compliant



7686594 10 m

RS PRO TYPE J EXTENSION CABLE, 2M, PVC INSULATION, +220°C MAX,

Pack size: **1 x EA**

- Length: 2 m
- Insulation Material: PVC
- Thermocouple Type: J
- Maximum Operating Temperature: +220 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Multicore
- Number of Strands: 2
- Standards Met: IEC, RoHS Compliant



7686597 2 m

RS PRO TYPE J EXTENSION CABLE, 10M, PVC INSULATION, +220°C MAX,

Pack size: **1 x EA**

- Length: 10 m
- Insulation Material: PVC
- Thermocouple Type: J
- Maximum Operating Temperature: +220 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Multicore
- Number of Strands: 2
- Standards Met: IEC, RoHS Compliant



7686601 10 m

RS PRO TYPE T EXTENSION CABLE, 2M, PVC INSULATION, +220°C MAX,

Pack size: **1 x EA**

- Length: 2 m
- Insulation Material: PVC
- Thermocouple Type: T
- Maximum Operating Temperature: +220 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Multicore
- Number of Strands: 2
- Standards Met: IEC, RoHS Compliant



7686604 2 m

RS PRO TYPE T EXTENSION CABLE, 5M, PVC INSULATION, +220°C MAX,

Pack size: **1 x EA**

- Length: 5 m
- Insulation Material: PVC
- Thermocouple Type: T
- Maximum Operating Temperature: +220 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Multicore
- Number of Strands: 2
- Standards Met: IEC, RoHS Compliant



7686608 5 m

RS PRO TYPE N EXTENSION CABLE, 2M, PVC INSULATION, +220°C MAX,

Pack size: **1 x EA**

- Length: 2 m
- Insulation Material: PVC
- Thermocouple Type: N
- Maximum Operating Temperature: +220 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Multicore
- Number of Strands: 2
- Standards Met: IEC, RoHS Compliant



7686610 2 m

RS PRO TYPE N EXTENSION CABLE, 5M, PVC INSULATION, +220°C MAX,

Pack size: **1 x EA**

- Length: 5 m
- Insulation Material: PVC
- Thermocouple Type: N
- Maximum Operating Temperature: +220 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Multicore
- Number of Strands: 2
- Standards Met: IEC, RoHS Compliant



7686614 5 m

RS PRO TYPE T EXTENSION CABLE, 10M, PVC INSULATION, +220°C MAX,

Pack size: **1 x EA**

- Length: 10 m
- Insulation Material: PVC
- Thermocouple Type: T
- Maximum Operating Temperature: +220 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Multicore
- Number of Strands: 2
- Standards Met: IEC, RoHS Compliant



7686617 10 m

RS PRO TYPE K EXTENSION CABLE, 2M, PVC INSULATION, +220°C MAX,

Pack size: **1 x EA**

- Length: 2 m
- Insulation Material: PVC
- Thermocouple Type: K
- Maximum Operating Temperature: +220 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Multicore
- Number of Strands: 2
- Standards Met: IEC, RoHS Compliant



7686626 2 m

RS PRO TYPE J EXTENSION CABLE, 5M, PVC INSULATION, +220°C MAX,

Pack size: **1 x EA**

- Length: 5 m
- Insulation Material: PVC
- Thermocouple Type: J
- Maximum Operating Temperature: +220 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Multicore
- Number of Strands: 2
- Standards Met: IEC, RoHS Compliant



7686636 5 m

RS PRO TYPE T EXTENSION CABLE, 2M, PVC INSULATION, +220°C MAX,

Pack size: **1 x EA**

- Length: 2 m
- Insulation Material: PVC
- Thermocouple Type: T
- Maximum Operating Temperature: +220 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Multicore
- Number of Strands: 2
- Standards Met: IEC, RoHS Compliant



7686648 2 m

RS PRO TYPE K EXTENSION CABLE, 5M, GLASS FIBRE INSULATION,

Pack size: **1 x EA**

- Length: 5 m
- Insulation Material: Glass Fibre
- Thermocouple Type: K
- Core Strands: 7/0.2 mm
- Number of Strands: 2



7799671 5 m

RS PRO TYPE K EXTENSION CABLE, 2M, GLASS FIBRE INSULATION,

Pack size: **1 x EA**

- Length: 2 m
- Insulation Material: Glass Fibre
- Thermocouple Type: K
- Core Strands: 7/0.2 mm
- Number of Strands: 2



7799678 2 m

RS PRO TYPE K EXTENSION CABLE, 2M, PFA INSULATION, 7/0.2MM

Pack size: **1 x EA**

- Length: 2 m
- Insulation Material: PFA
- Thermocouple Type: K
- Core Strands: 7/0.2 mm
- Number of Strands: 2



7799697 2 m

RS PRO TYPE K EXTENSION CABLE, 5M, PFA INSULATION, 7/0.2MM

Pack size: **1 x EA**

- Length: 5 m
- Insulation Material: PFA
- Thermocouple Type: K
- Core Strands: 7/0.2 mm
- Number of Strands: 2



7799707 5 m

RS PRO TYPE K EXTENSION CABLE, 2M, PVC INSULATION, 7/0.2MM

Pack size: **1 x EA**

- Length: 2 m
- Insulation Material: PVC
- Thermocouple Type: K
- Core Strands: 7/0.2 mm
- Number of Strands: 2



7799713 2 m

RS PRO TYPE K EXTENSION CABLE, 5M, PVC INSULATION, 7/0.2MM

Pack size: **1 x EA**

- Length: 5 m
- Insulation Material: PVC
- Thermocouple Type: K
- Core Strands: 7/0.2 mm
- Number of Strands: 2




7799716 5 m

RS PRO TYPE J THERMOCOUPLE WIRE, 25M, UNSCREENED, PVC

Pack size: **1 x EA**

- Length: 25 m
- Insulation Material: PVC
- Maximum Operating Temperature: +105 °C
- Thermocouple Type: J
- Screened/Unscreened: Unscreened
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2




8139995 25 m

RS PRO TYPE J THERMOCOUPLE WIRE, 100M, UNSCREENED, PVC

Pack size: **1 x EA**

- Length: 100 m
- Insulation Material: PVC
- Maximum Operating Temperature: +105 °C
- Thermocouple Type: J
- Screened/Unscreened: Unscreened
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2



8140005 100 m

RS PRO TYPE J THERMOCOUPLE WIRE, 100M, SCREENED, PVC MYLAR

Pack size: **1 x EA**

- Length: 100 m
- Insulation Material: PVC Mylar
- Maximum Operating Temperature: +105 °C
- Thermocouple Type: J
- Screened/Unscreened: Screened
- Core Strands: 7/0.2 mm
- Cable Shape: Twisted
- Number of Strands: 2



8140011 100 m

RS PRO TYPE K THERMOCOUPLE WIRE, 25M, PVC INSULATION, +105°C

Pack size: **1 x EA**

- Length: 25 m
- Insulation Material: PVC
- Thermocouple Type: K
- Maximum Operating Temperature: +105 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: ANSI




8140018 25 m

RS PRO TYPE K THERMOCOUPLE WIRE, 200M, PVC INSULATION,

Pack size: **1 x EA**

- Length: 200 m
- Insulation Material: PVC
- Thermocouple Type: K
- Maximum Operating Temperature: +105 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: ANSI



8140020 200 m

RS PRO TYPE K THERMOCOUPLE WIRE, 25M, PFA INSULATION, +260°C

Pack size: **1 x EA**

- Length: 25 m
- Insulation Material: PFA
- Thermocouple Type: K
- Maximum Operating Temperature: +260 °C
- Core Strands: 1/0.3 mm
- Cable Shape: Twisted
- Number of Strands: 2
- Standards Met: ANSI




8140024 25 m

RS PRO TYPE K THERMOCOUPLE WIRE, 100M, PVC INSULATION,

Pack size: **1 x EA**

- Length: 100 m
- Insulation Material: PVC
- Thermocouple Type: K
- Maximum Operating Temperature: +105 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: ANSI



8140027 100 m

RS PRO TYPE K THERMOCOUPLE WIRE, 25M, PFA INSULATION, +260°C

Pack size: **1 x EA**

- Length: 25 m
- Insulation Material: PFA
- Thermocouple Type: K
- Maximum Operating Temperature: +260 °C
- Core Strands: 1/0.2 mm
- Cable Shape: Twisted
- Number of Strands: 2
- Standards Met: ANSI



8140030 25 m

RS PRO TYPE K THERMOCOUPLE WIRE, 50M, PFA INSULATION, +260°C

Pack size: **1 x EA**

- Length: 50 m
- Insulation Material: PFA
- Thermocouple Type: K
- Maximum Operating Temperature: +260 °C
- Core Strands: 1/0.3 mm
- Cable Shape: Twisted
- Number of Strands: 2
- Standards Met: ANSI



8140033 50 m

RS PRO TYPE K THERMOCOUPLE WIRE, 100M, PFA INSULATION,

Pack size: **1 x EA**

- Length: 100 m
- Insulation Material: PFA
- Thermocouple Type: K
- Maximum Operating Temperature: +260 °C
- Core Strands: 1/0.3 mm
- Cable Shape: Twisted
- Number of Strands: 2
- Standards Met: ANSI



8140036 100 m

RS PRO TYPE K THERMOCOUPLE WIRE, 100M, PFA INSULATION,

Pack size: **1 x EA**

- Length: 100 m
- Insulation Material: PFA
- Thermocouple Type: K
- Maximum Operating Temperature: +260 °C
- Core Strands: 1/0.2 mm
- Cable Shape: Twisted
- Number of Strands: 2
- Standards Met: ANSI



8140042 100 m

RS PRO TYPE K THERMOCOUPLE WIRE, 25M, PFA INSULATION, +260°C

Pack size: **1 x EA**

- Length: 25 m
- Insulation Material: PFA
- Thermocouple Type: K
- Maximum Operating Temperature: +260 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Twisted
- Number of Strands: 2
- Standards Met: ANSI



8140046 25 m

RS PRO TYPE K THERMOCOUPLE WIRE, 50M, PFA INSULATION, +260°C

Pack size: **1 x EA**

- Length: 50 m
- Insulation Material: PFA
- Thermocouple Type: K
- Maximum Operating Temperature: +260 °C
- Core Strands: 1/0.315 mm
- Cable Shape: Twisted
- Number of Strands: 2
- Standards Met: ANSI



8140049 50 m

RS PRO TYPE K THERMOCOUPLE WIRE, 25M, GLASS FIBRE

Pack size: **1 x EA**

- Length: 25 m
- Insulation Material: Glass Fibre
- Thermocouple Type: K
- Maximum Operating Temperature: +350 °C
- Core Strands: 1/0.315 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: ANSI



8140052 25 m

RS PRO TYPE K THERMOCOUPLE WIRE, 50M, PFA INSULATION, +260°C

Pack size: **1 x EA**

- Length: 50 m
- Insulation Material: PFA
- Thermocouple Type: K
- Maximum Operating Temperature: +260 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Twisted
- Number of Strands: 2
- Standards Met: ANSI



8140055 50 m

RS PRO TYPE K THERMOCOUPLE WIRE, 50M, GLASS FIBRE

Pack size: **1 x EA**

- Length: 50 m
- Insulation Material: Glass Fibre
- Thermocouple Type: K
- Maximum Operating Temperature: +350 °C
- Core Strands: 1/0.315 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: ANSI



8140061 50 m

RS PRO TYPE K THERMOCOUPLE WIRE, 100M, GLASS FIBRE

Pack size: **1 x EA**

- Length: 100 m
- Insulation Material: Glass Fibre
- Thermocouple Type: K
- Maximum Operating Temperature: +350 °C
- Core Strands: 1/0.315 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: ANSI




8140064 100 m

RS PRO TYPE K THERMOCOUPLE WIRE, 25M, SCREENED, PVC MYLAR

Pack size: **1 x EA**

- Length: 25 m
- Insulation Material: PVC Mylar
- Maximum Operating Temperature: +105 °C
- Thermocouple Type: K
- Screened/Unscreened: Screened
- Core Strands: 7/0.2 mm
- Cable Shape: Twisted
- Number of Strands: 2




8140068 25 m

RS PRO TYPE K THERMOCOUPLE WIRE, 200M, SCREENED, PVC MYLAR

Pack size: **1 x EA**

- Length: 200 m
- Insulation Material: PVC Mylar
- Maximum Operating Temperature: +105 °C
- Thermocouple Type: K
- Screened/Unscreened: Screened
- Core Strands: 7/0.2 mm
- Cable Shape: Twisted
- Number of Strands: 2




8140070 200 m

RS PRO TYPE T THERMOCOUPLE WIRE, 25M, PVC INSULATION, +105°C

Pack size: **1 x EA**

- Length: 25 m
- Insulation Material: PVC
- Thermocouple Type: T
- Maximum Operating Temperature: +105 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: ANSI




8140074 25 m

RS PRO TYPE T THERMOCOUPLE WIRE, 25M, PFA INSULATION, +260°C

Pack size: **1 x EA**

- Length: 25 m
- Insulation Material: PFA
- Thermocouple Type: T
- Maximum Operating Temperature: +260 °C
- Core Strands: 1/0.3 mm
- Cable Shape: Twisted
- Number of Strands: 2
- Standards Met: ANSI



8140080 25 m

RS PRO TYPE T THERMOCOUPLE WIRE, 100M, PVC INSULATION,

Pack size: **1 x EA**

- Length: 100 m
- Insulation Material: PVC
- Thermocouple Type: T
- Maximum Operating Temperature: +105 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: ANSI




8140083 100 m

RS PRO TYPE T THERMOCOUPLE WIRE, 200M, PVC INSULATION,

Pack size: **1 x EA**

- Length: 200 m
- Insulation Material: PVC
- Maximum Operating Temperature: +105 °C
- Thermocouple Type: T
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: ANSI



8140086 200 m

RS PRO TYPE T THERMOCOUPLE WIRE, 100M, PFA INSULATION,

Pack size: **1 x EA**

- Length: 100 m
- Insulation Material: PFA
- Thermocouple Type: T
- Maximum Operating Temperature: +260 °C
- Core Strands: 1/0.3 mm
- Cable Shape: Twisted
- Number of Strands: 2
- Standards Met: ANSI



8140092 100 m

RS PRO TYPE T THERMOCOUPLE WIRE, 25M, PFA INSULATION, +260°C

Pack size: **1 x EA**

- Length: 25 m
- Insulation Material: PFA
- Thermocouple Type: T
- Maximum Operating Temperature: +260 °C
- Core Strands: 1/0.2 mm
- Cable Shape: Twisted
- Number of Strands: 2
- Standards Met: ANSI




8140096 25 m

RS PRO TYPE T THERMOCOUPLE WIRE, 50M, PFA INSULATION, +260°C

Pack size: **1 x EA**

- Length: 50 m
- Insulation Material: PFA
- Thermocouple Type: T
- Maximum Operating Temperature: +260 °C
- Core Strands: 1/0.3 mm
- Cable Shape: Twisted
- Number of Strands: 2
- Standards Met: ANSI



8140099 50 m

RS PRO TYPE K THERMOCOUPLE WIRE, 25M, PVC INSULATION, +105°C

Pack size: **1 x EA**

- Length: 25 m
- Insulation Material: PVC
- Thermocouple Type: K
- Maximum Operating Temperature: +105 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: ANSI



8140103 25 m

RS PRO TYPE T THERMOCOUPLE WIRE, 50M, PFA INSULATION, +260°C

Pack size: **1 x EA**

- Length: 50 m
- Insulation Material: PFA
- Thermocouple Type: T
- Maximum Operating Temperature: +260 °C
- Core Strands: 1/0.2 mm
- Cable Shape: Twisted
- Number of Strands: 2
- Standards Met: ANSI



8140106 50 m

RS PRO TYPE T THERMOCOUPLE WIRE, 100M, PFA INSULATION,

Pack size: **1 x EA**

- Length: 100 m
- Insulation Material: PFA
- Thermocouple Type: T
- Maximum Operating Temperature: +260 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Twisted
- Number of Strands: 2
- Standards Met: ANSI



8140109 100 m

RS PRO TYPE K THERMOCOUPLE WIRE, 200M, PVC INSULATION,

Pack size: **1 x EA**

- Length: 200 m
- Insulation Material: PVC
- Thermocouple Type: K
- Maximum Operating Temperature: +105 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: ANSI



8140115 200 m

RS PRO TYPE K THERMOCOUPLE WIRE, 25M, PVC INSULATION, +260°C

Pack size: **1 x EA**

- Length: 25 m
- Insulation Material: PVC
- Thermocouple Type: K
- Maximum Operating Temperature: +260 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: ANSI



8140119 25 m

RS PRO TYPE K THERMOCOUPLE WIRE, 100M, PVC INSULATION,

Pack size: **1 x EA**

- Length: 100 m
- Insulation Material: PVC
- Thermocouple Type: K
- Maximum Operating Temperature: +260 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: ANSI



8140121 100 m

RS PRO TYPE K THERMOCOUPLE WIRE, 50M, PVC INSULATION, +260°C

Pack size: **1 x EA**

- Length: 50 m
- Insulation Material: PVC
- Thermocouple Type: K
- Maximum Operating Temperature: +260 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: ANSI



8140128 50 m

RS PRO TYPE J THERMOCOUPLE WIRE, 25M, PVC INSULATION, +105°C

Pack size: **1 x EA**

- Length: 25 m
- Insulation Material: PVC
- Thermocouple Type: J
- Maximum Operating Temperature: +105 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: IEC



8275592 25 m

RS PRO TYPE J THERMOCOUPLE WIRE, 50M, PVC INSULATION, +105°C

Pack size: **1 x EA**

- Length: 50 m
- Insulation Material: PVC
- Thermocouple Type: J
- Maximum Operating Temperature: +105 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: IEC



8275596 50 m

RS PRO TYPE K THERMOCOUPLE WIRE, 50M, PVC INSULATION, +105°C

Pack size: **1 x EA**

- Length: 50 m
- Insulation Material: PVC
- Thermocouple Type: K
- Maximum Operating Temperature: +105 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: IEC



8275603 50 m

RS PRO TYPE J THERMOCOUPLE WIRE, 200M, PVC INSULATION,

Pack size: **1 x EA**

- Length: 200 m
- Insulation Material: PVC
- Thermocouple Type: J
- Maximum Operating Temperature: +105 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: IEC



8275606 200 m

RS PRO TYPE K THERMOCOUPLE WIRE, 10M, PVC INSULATION, +105°C

Pack size: **1 x EA**

- Length: 10 m
- Insulation Material: PVC
- Thermocouple Type: K
- Maximum Operating Temperature: +105 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: IEC



8275609 10 m

RS PRO TYPE K THERMOCOUPLE WIRE, 200M, PVC INSULATION,

Pack size: **1 x EA**

- Length: 200 m
- Insulation Material: PVC
- Thermocouple Type: K
- Maximum Operating Temperature: +105 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: IEC



8275612 200 m

RS PRO TYPE K THERMOCOUPLE WIRE, 10M, PVC INSULATION, +105°C

Pack size: **1 x EA**

- Length: 10 m
- Insulation Material: PVC
- Thermocouple Type: K
- Maximum Operating Temperature: +105 °C
- Core Strands: 13/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: IEC



8275621 10 m

RS PRO TYPE K THERMOCOUPLE WIRE, 10M, PVC INSULATION, +105°C

Pack size: **1 x EA**

- Length: 10 m
- Insulation Material: PVC
- Thermocouple Type: K
- Maximum Operating Temperature: +105 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: IEC



8275615 10 m

RS PRO TYPE K THERMOCOUPLE WIRE, 25M, PVC INSULATION, +105°C

Pack size: **1 x EA**

- Length: 25 m
- Insulation Material: PVC
- Thermocouple Type: K
- Maximum Operating Temperature: +105 °C
- Core Strands: 13/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: IEC



8275625 25 m

RS PRO TYPE K THERMOCOUPLE WIRE, 200M, PVC INSULATION, +105°C

Pack size: **1 x EA**

- Length: 200 m
- Insulation Material: PVC
- Thermocouple Type: K
- Maximum Operating Temperature: +105 °C
- Core Strands: 13/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: IEC



8275628 200 m

RS PRO TYPE N THERMOCOUPLE WIRE, 50M, PVC INSULATION, +105°C

Pack size: **1 x EA**

- Length: 50 m
- Insulation Material: PVC
- Thermocouple Type: N
- Maximum Operating Temperature: +105 °C
- Core Strands: 13/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: IEC



8275631 50 m

RS PRO TYPE N THERMOCOUPLE WIRE, 25M, PVC INSULATION, +105°C

Pack size: **1 x EA**

- Length: 25 m
- Insulation Material: PVC
- Thermocouple Type: N
- Maximum Operating Temperature: +105 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: IEC



8275637 25 m

RS PRO TYPE N THERMOCOUPLE WIRE, 100M, PVC INSULATION, +105°C

Pack size: **1 x EA**

- Length: 100 m
- Insulation Material: PVC
- Thermocouple Type: N
- Maximum Operating Temperature: +105 °C
- Core Strands: 13/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: IEC



8275640 100 m

RS PRO TYPE R/S THERMOCOUPLE WIRE, 25M, PVC INSULATION, +105°C

Pack size: **1 x EA**

- Length: 25 m
- Insulation Material: PVC
- Thermocouple Type: R/S
- Maximum Operating Temperature: +105 °C
- Core Strands: 13/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: IEC



8275643 25 m

RS PRO TYPE R/S THERMOCOUPLE WIRE, 50M, PVC INSULATION, +105°C

Pack size: **1 x EA**

- Length: 50 m
- Insulation Material: PVC
- Thermocouple Type: R/S
- Maximum Operating Temperature: +105 °C
- Core Strands: 13/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: IEC



8275647 50 m

RS PRO TYPE T THERMOCOUPLE WIRE, 50M, PVC INSULATION, +105°C

Pack size: **1 x EA**

- Length: 50 m
- Insulation Material: PVC
- Thermocouple Type: T
- Maximum Operating Temperature: +105 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: IEC



8275653 50 m

RS PRO TYPE R/S THERMOCOUPLE WIRE, 10M, PVC INSULATION, +105°C

Pack size: **1 x EA**

- Length: 10 m
- Insulation Material: PVC
- Thermocouple Type: R/S
- Maximum Operating Temperature: +105 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: IEC



8275656 10 m

RS PRO TYPE R/S THERMOCOUPLE WIRE, 50M, PVC INSULATION, +105°C

Pack size: **1 x EA**

- Length: 50 m
- Insulation Material: PVC
- Thermocouple Type: R/S
- Maximum Operating Temperature: +105 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: IEC



8275659 50 m

RS PRO TYPE J THERMOCOUPLE WIRE, 10M, SCREENED, PVC

Pack size: **1 x EA**

- Length: 10 m
- Insulation Material: PVC
- Maximum Operating Temperature: +105 °C
- Thermocouple Type: J
- Screened/Unscreened: Screened
- Core Strands: 7/0.2 mm
- Cable Shape: Twisted
- Number of Strands: 2




8275665 10 m

RS PRO TYPE K THERMOCOUPLE WIRE, 50M, SCREENED, PVC

Pack size: **1 x EA**

- Length: 50 m
- Insulation Material: PVC
- Maximum Operating Temperature: +105 °C
- Thermocouple Type: K
- Screened/Unscreened: Screened
- Core Strands: 7/0.2 mm
- Cable Shape: Twisted
- Number of Strands: 2




8275671 50 m

RS PRO TYPE K THERMOCOUPLE WIRE, 200M, SCREENED, PVC

Pack size: **1 x EA**

- Length: 200 m
- Insulation Material: PVC
- Maximum Operating Temperature: +105 °C
- Thermocouple Type: K
- Screened/Unscreened: Screened
- Core Strands: 7/0.2 mm
- Cable Shape: Twisted
- Number of Strands: 2




8275675 200 m

RS PRO TYPE K THERMOCOUPLE WIRE, 10M, PVC INSULATION, +105°C

Pack size: **1 x EA**

- Length: 10 m
- Insulation Material: PVC
- Thermocouple Type: K
- Maximum Operating Temperature: +105 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Twisted
- Number of Strands: 2
- Standards Met: IEC



8275690 10 m

RS PRO TYPE K THERMOCOUPLE WIRE, 10M, PVC INSULATION, +105°C

Pack size: **1 x EA**

- Length: 10 m
- Insulation Material: PVC
- Thermocouple Type: K
- Maximum Operating Temperature: +105 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Twisted
- Number of Strands: 2
- Standards Met: IEC




8275678 10 m

RS PRO TYPE K THERMOCOUPLE WIRE, 50M, PVC INSULATION, +105°C

Pack size: **1 x EA**

- Length: 50 m
- Insulation Material: PVC
- Thermocouple Type: K
- Maximum Operating Temperature: +105 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Twisted
- Number of Strands: 2
- Standards Met: IEC



8275693 50 m

RS PRO TYPE K THERMOCOUPLE WIRE, 25M, GLASS FIBRE

Pack size: **1 x EA**

- Length: 25 m
- Insulation Material: Glass Fibre
- Thermocouple Type: K
- Maximum Operating Temperature: +350 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: BS



8275704 25 m

RS PRO TYPE K THERMOCOUPLE WIRE, 25M, GLASS FIBRE

Pack size: **1 x EA**

- Length: 25 m
- Insulation Material: Glass Fibre
- Thermocouple Type: K
- Maximum Operating Temperature: +350 °C
- Core Strands: 1/0.315 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: BS



8275707 25 m

RS PRO TYPE K THERMOCOUPLE WIRE, 100M, PFA INSULATION, +260°C

Pack size: **1 x EA**

- Length: 100 m
- Insulation Material: PFA
- Thermocouple Type: K
- Maximum Operating Temperature: +260 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: IEC



8275710 100 m

RS PRO TYPE K THERMOCOUPLE WIRE, 50M, GLASS FIBRE

Pack size: **1 x EA**

- Length: 50 m
- Insulation Material: Glass Fibre
- Thermocouple Type: K
- Maximum Operating Temperature: +350 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: BS



8275713 50 m

RS PRO TYPE K THERMOCOUPLE WIRE, 10M, PFA INSULATION, +260°C

Pack size: **1 x EA**

- Length: 10 m
- Insulation Material: PFA
- Thermocouple Type: K
- Maximum Operating Temperature: +260 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: IEC




8275716 10 m

RS PRO TYPE K THERMOCOUPLE WIRE, 50M, PFA INSULATION, +260°C

Pack size: **1 x EA**

- Length: 50 m
- Insulation Material: PFA
- Thermocouple Type: K
- Maximum Operating Temperature: +260 °C
- Core Strands: 1/0.315 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: IEC



8275722 50 m

RS PRO TYPE K THERMOCOUPLE WIRE, 50M, GLASS FIBRE

Pack size: **1 x EA**

- Length: 50 m
- Insulation Material: Glass Fibre
- Thermocouple Type: K
- Maximum Operating Temperature: +350 °C
- Core Strands: 1/0.315 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: BS



8275700 50 m

RS PRO TYPE K THERMOCOUPLE WIRE, 10M, PFA INSULATION, +260°C

Pack size: **1 x EA**

- Length: 10 m
- Insulation Material: PFA
- Thermocouple Type: K
- Maximum Operating Temperature: +260 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: IEC



8275729 10 m

RS PRO TYPE J THERMOCOUPLE WIRE, 10M, PFA INSULATION, +260°C

Pack size: **1 x EA**

- Length: 10 m
- Insulation Material: PFA
- Thermocouple Type: J
- Maximum Operating Temperature: +260 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: IEC



8275732 10 m

RS PRO TYPE K THERMOCOUPLE WIRE, 100M, PFA INSULATION, +260°C

Pack size: **1 x EA**

- Length: 100 m
- Insulation Material: PFA
- Thermocouple Type: K
- Maximum Operating Temperature: +260 °C
- Core Strands: 1/0.315 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: IEC



8275726 100 m

RS PRO TYPE J THERMOCOUPLE WIRE, 100M, PFA INSULATION, +260°C

Pack size: **1 x EA**

- Length: 100 m
- Insulation Material: PFA
- Thermocouple Type: J
- Maximum Operating Temperature: +260 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: IEC



8275741 100 m

RS PRO TYPE T THERMOCOUPLE WIRE, 100M, PFA INSULATION, +260°C

Pack size: **1 x EA**

- Length: 100 m
- Insulation Material: PFA
- Thermocouple Type: T
- Maximum Operating Temperature: +260 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: IEC



8275738 100 m

RS PRO TYPE T THERMOCOUPLE WIRE, 10M, PFA INSULATION, +260°C

Pack size: **1 x EA**

- Length: 10 m
- Insulation Material: PFA
- Thermocouple Type: T
- Maximum Operating Temperature: +260 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: IEC



8275735 10 m

RS PRO TYPE N THERMOCOUPLE WIRE, 10M, PFA INSULATION, +260°C

Pack size: **1 x EA**

- Length: 10 m
- Insulation Material: PFA
- Thermocouple Type: N
- Maximum Operating Temperature: +260 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: IEC



8275744 10 m

RS PRO TYPE K THERMOCOUPLE WIRE, 25M, PFA INSULATION, +260°C

Pack size: **1 x EA**

- Length: 25 m
- Insulation Material: PFA
- Thermocouple Type: K
- Maximum Operating Temperature: +260 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Twin Twisted
- Number of Strands: 2
- Standards Met: IEC



8275750 25 m

RS PRO TYPE K THERMOCOUPLE WIRE, 10M, PFA INSULATION, +260°C

Pack size: **1 x EA**

- Length: 10 m
- Insulation Material: PFA
- Thermocouple Type: K
- Maximum Operating Temperature: +260 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Twin Twisted
- Number of Strands: 2
- Standards Met: IEC



8275757 10 m

RS PRO TYPE K THERMOCOUPLE WIRE, 10M, PFA INSULATION, +260°C

Pack size: **1 x EA**

- Length: 10 m
- Insulation Material: PFA
- Thermocouple Type: K
- Maximum Operating Temperature: +260 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Twin Twisted
- Number of Strands: 2
- Standards Met: IEC



8275763 10 m

RS PRO TYPE N THERMOCOUPLE WIRE, 10M, PFA INSULATION, +260°C

Pack size: **1 x EA**

- Length: 10 m
- Insulation Material: PFA
- Thermocouple Type: N
- Maximum Operating Temperature: +260 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Twin Twisted
- Number of Strands: 2
- Standards Met: IEC



8275760 10 m

RS PRO TYPE K THERMOCOUPLE WIRE, 10M, PTFE INSULATION, +260°C

Pack size: **1 x EA**

- Length: 10 m
- Insulation Material: PTFE
- Thermocouple Type: K
- Maximum Operating Temperature: +260 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: IEC



8275776 10 m

RS PRO TYPE K THERMOCOUPLE WIRE, 25M, PFA INSULATION, +260°C

Pack size: **1 x EA**

- Length: 25 m
- Insulation Material: PFA
- Thermocouple Type: K
- Maximum Operating Temperature: +260 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Twin Twisted
- Number of Strands: 2
- Standards Met: IEC



8275766 25 m

RS PRO TYPE T THERMOCOUPLE WIRE, 50M, PTFE INSULATION, +260°C

Pack size: **1 x EA**

- Length: 50 m
- Insulation Material: PTFE
- Thermocouple Type: T
- Maximum Operating Temperature: +260 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: IEC



8275782 50 m

RS PRO TYPE T THERMOCOUPLE WIRE, 10M, PFA INSULATION, +260°C

Pack size: **1 x EA**

- Length: 10 m
- Insulation Material: PFA
- Thermocouple Type: T
- Maximum Operating Temperature: +260 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Twin Twisted
- Number of Strands: 2
- Standards Met: IEC



8275779 10 m

RS PRO TYPE T THERMOCOUPLE WIRE, 10M, PTFE INSULATION, +260°C

Pack size: **1 x EA**

- Length: 10 m
- Insulation Material: PTFE
- Thermocouple Type: T
- Maximum Operating Temperature: +260 °C
- Core Strands: 1/0.315 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: IEC



8275791 10 m

RS PRO TYPE K THERMOCOUPLE WIRE, 50M, PTFE INSULATION, +260°C

Pack size: **1 x EA**

- Length: 50 m
- Insulation Material: PTFE
- Thermocouple Type: K
- Maximum Operating Temperature: +260 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: IEC



8275785 50 m

RS PRO TYPE T THERMOCOUPLE WIRE, 50M, PTFE INSULATION, +260°C

Pack size: **1 x EA**

- Length: 50 m
- Insulation Material: PTFE
- Thermocouple Type: T
- Maximum Operating Temperature: +260 °C
- Core Strands: 1/0.315 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: IEC



8275794 50 m

RS PRO TYPE J THERMOCOUPLE WIRE, 10M, PTFE INSULATION, +260°C

Pack size: **1 x EA**

- Length: 10 m
- Insulation Material: PTFE
- Thermocouple Type: J
- Maximum Operating Temperature: +260 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: IEC



8275798 10 m

RS PRO TYPE K THERMOCOUPLE WIRE, 50M, PTFE INSULATION, +260°C

Pack size: **1 x EA**

- Length: 50 m
- Insulation Material: PTFE
- Thermocouple Type: K
- Maximum Operating Temperature: +260 °C
- Core Strands: 1/0.2 mm
- Cable Shape: Twin Twisted
- Number of Strands: 2
- Standards Met: IEC



8275805 50 m

RS PRO TYPE K THERMOCOUPLE WIRE, 10M, PTFE INSULATION, +260°C

Pack size: **1 x EA**

- Length: 10 m
- Insulation Material: PTFE
- Thermocouple Type: K
- Maximum Operating Temperature: +260 °C
- Core Strands: 1/0.2 mm
- Cable Shape: Twin Twisted
- Number of Strands: 2
- Standards Met: IEC



8275801 10 m

RS PRO TYPE J THERMOCOUPLE WIRE, 50M, PTFE INSULATION, +260°C

Pack size: **1 x EA**

- Length: 50 m
- Insulation Material: PTFE
- Thermocouple Type: J
- Maximum Operating Temperature: +260 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: IEC



8275808 50 m

RS PRO TYPE K THERMOCOUPLE WIRE, 100M, PTFE INSULATION, +260°C

Pack size: **1 x EA**

- Length: 100 m
- Insulation Material: PTFE
- Thermocouple Type: K
- Maximum Operating Temperature: +260 °C
- Core Strands: 1/0.2 mm
- Cable Shape: Twin Twisted
- Number of Strands: 2
- Standards Met: IEC



8275814 100 m

RS PRO TYPE T THERMOCOUPLE WIRE, 10M, PTFE INSULATION, +260°C

Pack size: **1 x EA**

- Length: 10 m
- Insulation Material: PTFE
- Thermocouple Type: T
- Maximum Operating Temperature: +260 °C
- Core Strands: 1/0.2 mm
- Cable Shape: Twin Twisted
- Number of Strands: 2
- Standards Met: IEC



8275817 10 m

RS PRO TYPE T THERMOCOUPLE WIRE, 100M, PTFE INSULATION,

Pack size: **1 x EA**

- Length: 100 m
- Insulation Material: PTFE
- Thermocouple Type: T
- Maximum Operating Temperature: +260 °C
- Core Strands: 1/0.2 mm
- Cable Shape: Twin Twisted
- Number of Strands: 2
- Standards Met: IEC



8275820 100 m

RS PRO TYPE RTD RESISTANCE THERMOMETER DETECTOR (RTD)

Pack size: **1 x EA**

- Length: 10 m
- Insulation Material: PFA
- Thermocouple Type: RTD
- Maximum Operating Temperature: +200 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Twisted
- Number of Strands: 4



8275823 10 m

RS PRO TYPE RTD RESISTANCE THERMOMETER DETECTOR (RTD)

Pack size: **1 x EA**

- Length: 50 m
- Insulation Material: PFA
- Thermocouple Type: RTD
- Maximum Operating Temperature: +260 °C
- Screened/Unscreened: Screened
- Core Strands: 7/0.2 mm
- Cable Shape: Twisted
- Number of Strands: 4



8275827 50 m

RS PRO TYPE K THERMOCOUPLE WIRE, 50M, GLASS FIBRE

Pack size: **1 x EA**

- Length: 50 m
- Insulation Material: Glass Fibre
- Thermocouple Type: K
- Maximum Operating Temperature: +350 °C
- Core Strands: 1/0.315 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: IEC



8275833 50 m

RS PRO TYPE RTD RESISTANCE THERMOMETER DETECTOR (RTD)

Pack size: **1 x EA**

- Length: 100 m
- Insulation Material: PFA
- Thermocouple Type: RTD
- Maximum Operating Temperature: +260 °C
- Screened/Unscreened: Screened
- Core Strands: 7/0.2 mm
- Cable Shape: Twisted
- Number of Strands: 4



8275836 100 m

RS PRO TYPE K THERMOCOUPLE WIRE, 100M, GLASS FIBRE

Pack size: **1 x EA**

- Length: 100 m
- Insulation Material: Glass Fibre
- Thermocouple Type: K
- Maximum Operating Temperature: +350 °C
- Core Strands: 1/0.315 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: IEC



8275842 100 m

RS PRO TYPE K THERMOCOUPLE WIRE, 200M, GLASS FIBRE

Pack size: **1 x EA**

- Length: 200 m
- Insulation Material: Glass Fibre
- Thermocouple Type: K
- Maximum Operating Temperature: +350 °C
- Core Strands: 1/0.315 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: IEC



8275845 200 m

RS PRO TYPE T THERMOCOUPLE WIRE, 25M, GLASS FIBRE

Pack size: **1 x EA**

- Length: 25 m
- Insulation Material: Glass Fibre
- Thermocouple Type: T
- Maximum Operating Temperature: +350 °C
- Core Strands: 1/0.315 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: IEC



8275849 25 m

RS PRO TYPE J THERMOCOUPLE WIRE, 10M, GLASS FIBRE INSULATION,

Pack size: **1 x EA**

- Length: 10 m
- Insulation Material: Glass Fibre
- Thermocouple Type: J
- Maximum Operating Temperature: +350 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: IEC



8275851 10 m

RS PRO TYPE K THERMOCOUPLE WIRE, 100M, GLASS FIBRE

Pack size: **1 x EA**

- Length: 100 m
- Insulation Material: Glass Fibre
- Thermocouple Type: K
- Maximum Operating Temperature: +350 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: IEC



8275861 100 m

RS PRO TYPE K THERMOCOUPLE WIRE, 50M, GLASS FIBRE

Pack size: **1 x EA**

- Insulation Material: Glass Fibre
- Length: 50 m
- Maximum Operating Temperature: +350 °C
- Thermocouple Type: K
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: IEC



8275867 Glass Fibre

RS PRO TYPE J THERMOCOUPLE WIRE, 10M, GLASS FIBRE INSULATION,

Pack size: **1 x EA**

- Length: 10 m
- Insulation Material: Glass Fibre
- Thermocouple Type: J
- Maximum Operating Temperature: +350 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: IEC



8275870 10 m

RS PRO TYPE K THERMOCOUPLE WIRE, 25M, PVC INSULATION, +105°C

Pack size: **1 x EA**

- Length: 25 m
- Insulation Material: PVC
- Thermocouple Type: K
- Maximum Operating Temperature: +105 °C
- Core Strands: 13/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: IEC



8275883 25 m

RS PRO TYPE K THERMOCOUPLE WIRE, 25M, SILICONE RUBBER

Pack size: **1 x EA**

- Length: 25 m
- Insulation Material: Silicone Rubber
- Thermocouple Type: K
- Maximum Operating Temperature: +200 °C
- Core Strands: 7/0.2 mm
- Cable Shape: Twisted
- Number of Strands: 2
- Standards Met: IEC



8275906 25 m

RS PRO TYPE J THERMOCOUPLE WIRE, 25M, PFA INSULATION, +260°C

Pack size: **1 x EA**

- Length: 25 m
- Insulation Material: PFA
- Thermocouple Type: J
- Maximum Operating Temperature: +260 °C
- Core Strands: 1/0.2 mm
- Cable Shape: Twisted
- Number of Strands: 2
- Standards Met: IEC



8275918 25 m

RS PRO TYPE K THERMOCOUPLE WIRE, 25M, PFA INSULATION, +260°C

- Pack size: 1 x EA
- Length: 25 m
 - Insulation Material: PFA
 - Thermocouple Type: K
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 1/0.3 mm
 - Cable Shape: Twisted
 - Number of Strands: 2
 - Standards Met: IEC



8275924 25 m

RS PRO TYPE K THERMOCOUPLE WIRE, 50M, PFA INSULATION, +260°C

- Pack size: 1 x EA
- Length: 50 m
 - Insulation Material: PFA
 - Thermocouple Type: K
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 1/0.3 mm
 - Cable Shape: Twisted
 - Number of Strands: 2
 - Standards Met: IEC



8275928 50 m

RS PRO TYPE K THERMOCOUPLE WIRE, 100M, PFA INSULATION, +260°C

- Pack size: 1 x EA
- Length: 100 m
 - Insulation Material: PFA
 - Thermocouple Type: K
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 1/0.3 mm
 - Cable Shape: Twisted
 - Number of Strands: 2
 - Standards Met: IEC



8275937 100 m

RS PRO TYPE T THERMOCOUPLE WIRE, 25M, PFA INSULATION, +260°C

- Pack size: 1 x EA
- Length: 25 m
 - Insulation Material: PFA
 - Thermocouple Type: T
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 1/0.3 mm
 - Cable Shape: Twisted
 - Number of Strands: 2
 - Standards Met: IEC



8275943 25 m

RS PRO TYPE T THERMOCOUPLE WIRE, 50M, PFA INSULATION, +260°C

- Pack size: 1 x EA
- Length: 50 m
 - Insulation Material: PFA
 - Thermocouple Type: T
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 1/0.508 mm
 - Cable Shape: Twisted
 - Number of Strands: 2
 - Standards Met: IEC



8275959 50 m

RS PRO TYPE K THERMOCOUPLE WIRE, 50M, PFA INSULATION, +260°C

- Pack size: 1 x EA
- Length: 50 m
 - Insulation Material: PFA
 - Thermocouple Type: K
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 1/0.508 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: IEC



8275962 50 m

RS PRO TYPE T THERMOCOUPLE WIRE, 25M, PFA INSULATION, +260°C

- Pack size: 1 x EA
- Length: 25 m
 - Insulation Material: PFA
 - Thermocouple Type: T
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 1/0.315 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: IEC



8275971 25 m

RS PRO TYPE T THERMOCOUPLE WIRE, 50M, PFA INSULATION, +260°C

- Pack size: 1 x EA
- Length: 50 m
 - Insulation Material: PFA
 - Thermocouple Type: T
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 1/0.315 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: IEC



8275974 50 m

RS PRO TYPE J THERMOCOUPLE WIRE, 50M, PTFE INSULATION, +260°C

- Pack size: 1 x EA
- Length: 50 m
 - Insulation Material: PTFE
 - Thermocouple Type: J
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 1/0.2 mm
 - Cable Shape: Twisted
 - Number of Strands: 2
 - Standards Met: IEC



8275984 50 m

RS PRO TYPE T THERMOCOUPLE WIRE, 50M, PFA INSULATION, +260°C

- Pack size: 1 x EA
- Length: 50 m
 - Insulation Material: PFA
 - Thermocouple Type: T
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 1/0.5 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: IEC



8275987 50 m

RS PRO TYPE K THERMOCOUPLE WIRE, 25M, PTFE INSULATION, +260°C

- Pack size: 1 x EA
- Length: 25 m
 - Insulation Material: PTFE
 - Thermocouple Type: K
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 1/0.315 mm
 - Cable Shape: Twisted
 - Number of Strands: 2
 - Standards Met: IEC



8276000 25 m

RS PRO TYPE J THERMOCOUPLE WIRE, 25M, PTFE INSULATION, +260°C

- Pack size: 1 x EA
- Length: 25 m
 - Insulation Material: PTFE
 - Thermocouple Type: J
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 7/0.2 mm
 - Cable Shape: Twisted
 - Number of Strands: 2
 - Standards Met: IEC



8276006 25 m

RS PRO TYPE K THERMOCOUPLE WIRE, 50M, PTFE INSULATION, +260°C

- Pack size: 1 x EA
- Length: 50 m
 - Insulation Material: PTFE
 - Thermocouple Type: K
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 1/0.315 mm
 - Cable Shape: Twisted
 - Number of Strands: 2
 - Standards Met: IEC



8276019 50 m

RS PRO TYPE K THERMOCOUPLE WIRE, 50M, PTFE INSULATION, +260°C

- Pack size: 1 x EA
- Length: 50 m
 - Insulation Material: PTFE
 - Thermocouple Type: K
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 1/0.315 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: IEC



8276047 50 m

RS PRO TYPE K THERMOCOUPLE WIRE, 25M, PTFE INSULATION, +260°C

- Pack size: 1 x EA
- Length: 25 m
 - Insulation Material: PTFE
 - Thermocouple Type: K
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 1/0.315 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: IEC



8276038 25 m

RS PRO TYPE T THERMOCOUPLE WIRE, 25M, PTFE INSULATION, +260°C

- Pack size: 1 x EA
- Length: 25 m
 - Insulation Material: PTFE
 - Thermocouple Type: T
 - Maximum Operating Temperature: +260 °C
 - Core Strands: 1/0.508 mm
 - Cable Shape: Flat Pair
 - Number of Strands: 2
 - Standards Met: IEC



8276040 25 m

RS PRO TYPE K THERMOCOUPLE WIRE, 2M, POLYURETHANE

Pack size: **1 x EA**

- Length: 2 m
- Insulation Material: Polyurethane
- Thermocouple Type: K
- Maximum Operating Temperature: +125 °C
- Core Strands: 10/0.12
- Cable Shape: Curly
- Number of Strands: 2
- Standards Met: IEC



8276056 2 m

RS PRO TYPE J THERMOCOUPLE WIRE, 25M, GLASS FIBRE

Pack size: **1 x EA**

- Length: 25 m
- Insulation Material: Glass Fibre
- Thermocouple Type: J
- Maximum Operating Temperature: +350 °C
- Core Strands: 1/0.315 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: IEC



8276062 25 m

RS PRO TYPE K THERMOCOUPLE WIRE, 25M, GLASS FIBRE

Pack size: **1 x EA**

- Length: 25 m
- Insulation Material: Glass Fibre
- Thermocouple Type: K
- Maximum Operating Temperature: +350 °C
- Core Strands: 1/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: IEC



8276066 25 m

RS PRO TYPE J THERMOCOUPLE WIRE, 25M, GLASS FIBRE

Pack size: **1 x EA**

- Length: 25 m
- Insulation Material: Glass Fibre
- Thermocouple Type: J
- Maximum Operating Temperature: +350 °C
- Core Strands: 1/0.2 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: IEC



8276069 25 m

RS PRO TYPE K THERMOCOUPLE WIRE, 25M, GLASS FIBRE

Pack size: **1 x EA**

- Length: 25 m
- Insulation Material: Glass Fibre
- Thermocouple Type: K
- Maximum Operating Temperature: +350 °C
- Core Strands: 1/0.508 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: IEC



8276075 25 m

RS PRO TYPE N THERMOCOUPLE WIRE, 25M, GLASS FIBRE

Pack size: **1 x EA**

- Length: 25 m
- Insulation Material: Glass Fibre
- Thermocouple Type: N
- Maximum Operating Temperature: +350 °C
- Core Strands: 1/0.315 mm
- Cable Shape: Flat Pair
- Number of Strands: 2
- Standards Met: IEC



8276081 25 m

THERMOCOUPLE, WELDED TIP, J, GLASS FIBRE INSULATED, -

Pack size: **1 x EA**

- Thermocouple Type: J
- Probe Diameter: 1/0.3 mm
- Probe Length: 2 m
- Maximum Temperature Sensed: +400 °C
- Termination Type: Cable
- Cable Length: 2 m
- Standards Met: BS



150004 J

RS PRO TYPE J THERMOCOUPLE 200MM LENGTH, 6MM DIAMETER,

Pack size: **1 x EA**

- Thermocouple Type: J
- Probe Diameter: 6 mm
- Probe Length: 200 mm
- Maximum Temperature Sensed: +350 °C
- Termination Type: Cable
- Standards Met: BS
- Minimum Temperature Sensed: -60 °C



150026 J

THERMOCOUPLE, WELDED TIP, K, GLASS FIBRE INSULATED

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1/0.3 mm
- Probe Length: 2 m
- Maximum Temperature Sensed: +400 °C
- Termination Type: Cable
- Cable Length: 2 m
- Standards Met: BS



151192 K

RS PRO TYPE T THERMOCOUPLE 100MM LENGTH, 1.6MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: T
- Probe Diameter: 1.6 mm
- Probe Length: 100 mm
- Probe Material: Constantan, Copper
- Maximum Temperature Sensed: +250 °C
- Termination Type: Cable
- Cable Length: 1.5 m
- Standards Met: BS



151271 T

RS PRO TYPE K THERMOCOUPLE 300MM LENGTH, 3MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 3 mm
- Probe Length: 300 mm
- Probe Material: 316 Stainless Steel
- Maximum Temperature Sensed: +1000 °C
- Termination Type: Cable
- Cable Length: 1 m
- Standards Met: IEC



158604 K

THERMOCOUPLE, SELF ADHESIVE, K

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 7 mm
- Probe Length: 1 m
- Probe Material: Copper
- Maximum Temperature Sensed: +200 °C
- Termination Type: Cable
- Cable Length: 1 m
- Standards Met: BS



158626 K

RS PRO TYPE T THERMOCOUPLE 1M LENGTH, 1/0.2MM DIAMETER →

Pack size: **5 x EA**

- Thermocouple Type: T
- Probe Diameter: 1/0.2 mm
- Probe Length: 1 m
- Maximum Temperature Sensed: +200 °C
- Termination Type: Cable
- Cable Length: 1 m
- Standards Met: BS



158907 T

RS PRO TYPE K THERMOCOUPLE 1M LENGTH, 1.5MM DIAMETER → +800°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1.5 mm
- Probe Length: 1 m
- Probe Material: 316 Stainless Steel
- Maximum Temperature Sensed: +800 °C
- Termination Type: Cable
- Cable Length: 100 mm
- Standards Met: BS



159039 K

THERMOCOUPLE, WELDED TIP, K, PTFE INSULATED

Pack size: **5 x EA**

- Thermocouple Type: K
- Probe Diameter: 1/0.2 mm
- Probe Length: 1 m
- Maximum Temperature Sensed: +250 °C
- Termination Type: Cable
- Cable Length: 1 m
- Standards Met: BS



158913 K

RS PRO TYPE K THERMOCOUPLE 500MM LENGTH, 1.5MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1.5 mm
- Probe Length: 500 mm
- Probe Material: 316 Stainless Steel
- Maximum Temperature Sensed: +800 °C
- Termination Type: Cable
- Cable Length: 100 mm
- Standards Met: BS



159023 K

RS PRO TYPE K THERMOCOUPLE 500MM LENGTH, 1.5MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1.5 mm
- Probe Length: 500 mm
- Probe Material: Inconel 600
- Maximum Temperature Sensed: +1100 °C
- Termination Type: Cable
- Cable Length: 100 mm
- Standards Met: BS



159095 K

RS PRO TYPE K THERMOCOUPLE 1M LENGTH, 1.5MM DIAMETER → +1100°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1.5 mm
- Probe Length: 1 m
- Probe Material: Inconel 600
- Maximum Temperature Sensed: +1100 °C
- Termination Type: Cable
- Cable Length: 100 mm
- Standards Met: BS



159102 K

RS PRO TYPE K THERMOCOUPLE 500MM LENGTH, 3MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 3 mm
- Probe Length: 500 mm
- Probe Material: Inconel 600
- Maximum Temperature Sensed: +1100 °C
- Termination Type: Cable
- Cable Length: 100 mm
- Standards Met: BS



159118 K

RS PRO TYPE K THERMOCOUPLE 1M LENGTH, 3MM DIAMETER → +1100°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 3 mm
- Probe Length: 1 m
- Probe Material: Inconel 600
- Maximum Temperature Sensed: +1100 °C
- Termination Type: Cable
- Cable Length: 100 mm
- Standards Met: BS



159124 K

RS PRO TYPE K THERMOCOUPLE 2M LENGTH, 3MM DIAMETER → +1100°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 3 mm
- Probe Length: 2 m
- Probe Material: Inconel 600
- Maximum Temperature Sensed: +1100 °C
- Termination Type: Cable
- Cable Length: 100 mm
- Standards Met: BS



159130 K

THERMOCOUPLE, BAYONET, J

Pack size: **1 x EA**

- Thermocouple Type: J
- Probe Diameter: 6 mm
- Probe Length: 170 mm
- Maximum Temperature Sensed: +350 °C
- Probe Material: Stainless Steel
- Termination Type: Cable
- Cable Length: 2 m
- Standards Met: RoHS Compliant



259328 J

THERMOCOUPLE, ADJ BAYONET, K

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 6 mm
- Probe Length: 170 mm
- Maximum Temperature Sensed: +400 °C
- Probe Material: Stainless Steel
- Termination Type: Cable
- Cable Length: 2 m
- Standards Met: RoHS Compliant



259334 K

RS PRO THERMISTOR, -10°C MIN, +60°C MAX

Pack size: **1 x EA**

- Minimum Temperature Sensed: -10 °C
- Maximum Temperature Sensed: +60 °C



813806 -10 °C

RS PRO THERMISTOR, -30°C MIN, +70°C MAX

Pack size: **1 x EA**

- Minimum Temperature Sensed: -30 °C
- Maximum Temperature Sensed: +70 °C



813840 -30 °C

RS PRO TYPE K THERMOCOUPLE 1M LENGTH, → +220°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Length: 1 m
- Maximum Temperature Sensed: +220 °C
- Termination Type: Miniature Plug
- Cable Length: 1 m
- Standards Met: IEC, RoHS Compliant



1104463 K

RS PRO THERMISTOR, -10°C MIN, +110°C MAX

Pack size: **1 x EA**

- Minimum Temperature Sensed: -10 °C
- Maximum Temperature Sensed: +110 °C, +40 °C



813828 -10 °C

RS PRO THERMISTOR, -30°C MIN, +70°C MAX

Pack size: **1 x EA**

- Minimum Temperature Sensed: -30 °C
- Maximum Temperature Sensed: +70 °C



813834 -30 °C

RS PRO TYPE K THERMOCOUPLE 2M LENGTH, → +220°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Length: 2 m
- Maximum Temperature Sensed: +220 °C
- Termination Type: Miniature Plug
- Cable Length: 2 m
- Standards Met: IEC, RoHS Compliant



1104468 K

TYPE T THERMOCOUPLE WITH 2M CABLE TIDY

Pack size: **1 x EA**

- Thermocouple Type: T
- Probe Length: 2 m
- Maximum Temperature Sensed: +220 °C
- Termination Type: Miniature Plug
- Cable Length: 2 m
- Standards Met: IEC, RoHS Compliant



1104470 T

RS PRO TYPE K THERMOCOUPLE → +220°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Maximum Temperature Sensed: +220 °C
- Termination Type: Standard Plug
- Cable Length: 2 m
- Standards Met: ANSI, RoHS Compliant



1104472 K

RS PRO TYPE T THERMOCOUPLE → +220°C

Pack size: **1 x EA**

- Thermocouple Type: T
- Maximum Temperature Sensed: +220 °C
- Termination Type: Miniature Plug
- Cable Length: 2 m
- Standards Met: ANSI, RoHS Compliant



1104474 T

TYPE K THERMOCOUPLE 2M WITH MINI PLUG

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1/0.2 mm
- Probe Length: 2 m
- Maximum Temperature Sensed: +250 °C
- Termination Type: Miniature Plug
- Cable Length: 2 m
- Standards Met: IEC



1104482 K

RS PRO TYPE J THERMOCOUPLE 2M LENGTH, 1/0.2MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: J
- Probe Diameter: 1/0.2 mm
- Probe Length: 2 m
- Maximum Temperature Sensed: +260 °C
- Termination Type: Miniature Plug
- Cable Length: 2 m
- Standards Met: IEC



1236308 J

RS PRO TYPE J THERMOCOUPLE 10M LENGTH, 1/0.2MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: J
- Probe Diameter: 1/0.2 mm
- Probe Length: 10 m
- Maximum Temperature Sensed: +260 °C
- Termination Type: Miniature Plug
- Cable Length: 10 m
- Standards Met: IEC



1236310 J

RS PRO TYPE T THERMOCOUPLE 2M LENGTH, 1/0.2MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: T
- Probe Diameter: 1/0.2 mm
- Probe Length: 2 m
- Maximum Temperature Sensed: +260 °C
- Termination Type: Miniature Plug
- Cable Length: 2 m
- Standards Met: IEC



1236311 T

TYPE K IEC 1/0.2MM THERMOCOUPLE+PLUG 5M

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1/0.2 mm
- Probe Length: 5 m
- Maximum Temperature Sensed: +260 °C
- Termination Type: Miniature Plug
- Cable Length: 5 m
- Standards Met: IEC



1236306 K

TYPE T IEC 1/0.2MM THERMOCOUPLE+PLUG 5M

Pack size: **1 x EA**

- Thermocouple Type: T
- Probe Diameter: 1/0.2 mm
- Probe Length: 5 m
- Maximum Temperature Sensed: +260 °C
- Termination Type: Miniature Plug
- Cable Length: 5 m
- Standards Met: IEC



1236312 T

RS PRO TYPE K THERMOCOUPLE 10M LENGTH, 1/0.2MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1/0.2 mm
- Probe Length: 10 m
- Maximum Temperature Sensed: +260 °C
- Termination Type: Miniature Plug
- Cable Length: 10 m
- Standards Met: IEC



1236307 K

RS PRO TYPE J THERMOCOUPLE → +260°C

Pack size: **1 x EA**

- Thermocouple Type: J
- Maximum Temperature Sensed: +260 °C
- Termination Type: Miniature Plug
- Cable Length: 5 m
- Standards Met: IEC



1236309 J

RS PRO TYPE K THERMOCOUPLE 1M LENGTH, 1/0.508MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1/0.508 mm
- Probe Length: 1 m
- Maximum Temperature Sensed: +350 °C
- Termination Type: Cable
- Cable Length: 1 m
- Standards Met: IEC



1236314 K

RS PRO TYPE K THERMOCOUPLE 10M LENGTH, → +350°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Length: 10 m
- Maximum Temperature Sensed: +350 °C
- Termination Type: Miniature Plug
- Cable Length: 10 m
- Standards Met: IEC



1236317 K

RS PRO TYPE K THERMOCOUPLE 1/0.508MM DIAMETER → +350°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1/0.508 mm
- Maximum Temperature Sensed: +350 °C
- Termination Type: Miniature Plug
- Cable Length: 1 m
- Standards Met: IEC



1236316 K

RS PRO TYPE T THERMOCOUPLE 10M LENGTH, 1/0.2MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: T
- Probe Diameter: 1/0.2 mm
- Probe Length: 10 m
- Maximum Temperature Sensed: +260 °C
- Termination Type: Miniature Plug
- Cable Length: 10 m
- Standards Met: IEC



1236313 T

TYPE K IEC 0.315MM THERMOCOUPLE+PLUG 2M

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1/0.315 mm
- Probe Length: 2 m
- Maximum Temperature Sensed: +250 °C
- Termination Type: Miniature Plug
- Cable Length: 2 m
- Standards Met: IEC



1236319 K

TYPE K IEC 7/0.2MM THERMOCOUPLE+PLUG 1M

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 7/0.2 mm
- Maximum Temperature Sensed: +250 °C
- Termination Type: Miniature Plug
- Cable Length: 1 m
- Standards Met: IEC



1236320 K

RS PRO TYPE K THERMOCOUPLE 2M LENGTH, 7/0.2MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 7/0.2 mm
- Probe Length: 2 m
- Maximum Temperature Sensed: +250 °C
- Termination Type: Miniature Plug
- Cable Length: 2 m
- Standards Met: IEC



1236321 K

RS PRO TYPE K THERMOCOUPLE 1M LENGTH, 1/0.2MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1/0.2 mm
- Probe Length: 1 m
- Maximum Temperature Sensed: +250 °C
- Termination Type: Miniature Plug
- Cable Length: 1 m
- Standards Met: IEC



1236322 K

TYPE K IEC 1/0.2MM THERMOCOUPLE+PLUG 2M

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1/0.2 mm
- Probe Length: 2 m
- Maximum Temperature Sensed: +250 °C
- Termination Type: Miniature Plug
- Cable Length: 2 m
- Standards Met: IEC



1236323 K

RS PRO TYPE K THERMOCOUPLE 10M LENGTH, → +250°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Length: 10 m
- Maximum Temperature Sensed: +250 °C
- Termination Type: Miniature Plug
- Cable Length: 10 m
- Standards Met: IEC



1236324 K

TYPE J IEC 1/0.2MM THERMOCOUPLE+PLUG 1M

Pack size: **1 x EA**

- Thermocouple Type: J
- Probe Length: 1 m
- Maximum Temperature Sensed: +250 °C
- Termination Type: Miniature Plug
- Cable Length: 1 m
- Standards Met: IEC



1236325 J

RS PRO TYPE J THERMOCOUPLE → +250°C

Pack size: **1 x EA**

- Thermocouple Type: J
- Maximum Temperature Sensed: +250 °C
- Termination Type: Miniature Plug
- Cable Length: 10 m
- Standards Met: IEC



1236327 J

TYPE T IEC 0.315MM THERMOCOUPLE+PLUG 1M

Pack size: **1 x EA**

- Thermocouple Type: T
- Probe Diameter: 1/0.315 mm
- Probe Length: 1 m
- Maximum Temperature Sensed: +250 °C
- Termination Type: Miniature Plug
- Cable Length: 1 m
- Standards Met: IEC



1236328 T

RS PRO TYPE K THERMOCOUPLE 1/0.508MM DIAMETER → +350°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1/0.508 mm
- Maximum Temperature Sensed: +350 °C
- Termination Type: Cable
- Cable Length: 10 m
- Standards Met: IEC



1236315 K

RS PRO TYPE K THERMOCOUPLE 1/0.315MM DIAMETER → +250°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1/0.315 mm
- Maximum Temperature Sensed: +250 °C
- Termination Type: Miniature Plug
- Cable Length: 1 m
- Standards Met: IEC



1236318 K

TYPE T IEC 0.315MM THERMOCOUPLE+PLUG 2M

Pack size: **1 x EA**

- Thermocouple Type: T
- Probe Diameter: 1/0.315 mm
- Probe Length: 2 m
- Maximum Temperature Sensed: +250 °C
- Termination Type: Miniature Plug
- Cable Length: 2 m
- Standards Met: IEC



1236329 T

RS PRO TYPE T THERMOCOUPLE 1M LENGTH, → +250°C

Pack size: **1 x EA**

- Thermocouple Type: T
- Probe Length: 1 m
- Maximum Temperature Sensed: +250 °C
- Termination Type: Miniature Plug
- Cable Length: 1 m
- Standards Met: IEC



1236332 T

RS PRO TYPE T THERMOCOUPLE 7/0.2MM DIAMETER → +250°C

Pack size: **1 x EA**

- Thermocouple Type: T
- Probe Diameter: 7/0.2 mm
- Maximum Temperature Sensed: +250 °C
- Termination Type: Miniature Plug
- Cable Length: 1 m
- Standards Met: IEC



1236330 T

RS PRO TYPE T THERMOCOUPLE 10M LENGTH, → +250°C

Pack size: **1 x EA**

- Thermocouple Type: T
- Probe Length: 10 m
- Maximum Temperature Sensed: +250 °C
- Termination Type: Miniature Plug
- Cable Length: 10 m
- Standards Met: IEC



1236334 T

RS PRO TYPE K THERMOCOUPLE 11N DIAMETER → +250°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 11n
- Maximum Temperature Sensed: +250 °C
- Termination Type: Miniature Plug
- Cable Length: 1 m
- Standards Met: IEC



1314735 K

RS PRO TYPE T THERMOCOUPLE 7/0.2MM DIAMETER → +250°C

Pack size: **1 x EA**

- Thermocouple Type: T
- Probe Diameter: 7/0.2 mm
- Maximum Temperature Sensed: +250 °C
- Termination Type: Miniature Plug
- Cable Length: 2 m
- Standards Met: IEC



1236331 T

RS PRO TYPE K THERMOCOUPLE 50MM LENGTH, → +100°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Length: 50 mm
- Maximum Temperature Sensed: +100 °C
- Termination Type: Miniature Plug
- Cable Length: 1 m
- Standards Met: IEC



1314737 K

RS PRO TYPE T THERMOCOUPLE 2M LENGTH, 1/0.2MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: T
- Probe Diameter: 1/0.2 mm
- Probe Length: 2 m
- Maximum Temperature Sensed: +250 °C
- Termination Type: Miniature Plug
- Cable Length: 2 m
- Standards Met: IEC



1236333 T

RS PRO TYPE K THERMOCOUPLE 1M LENGTH, 6.35MM DIAMETER → +200°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 6.35 mm
- Probe Length: 1 m
- Probe Material: Copper
- Maximum Temperature Sensed: +200 °C
- Termination Type: Miniature Plug
- Cable Length: 1 m
- Standards Met: IEC



1314739 K

RS PRO TYPE K THERMOCOUPLE 2M LENGTH, 1/2IN DIAMETER → +250°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1/2 in
- Probe Length: 2 m
- Maximum Temperature Sensed: +250 °C
- Termination Type: Miniature Plug
- Cable Length: 2 m
- Standards Met: IEC



1314736 K

RS PRO TYPE J THERMOCOUPLE 2M LENGTH, 6.35MM DIAMETER → +200°C

Pack size: **1 x EA**

- Thermocouple Type: J
- Probe Diameter: 6.35 mm
- Probe Length: 2 m
- Probe Material: Copper
- Maximum Temperature Sensed: +200 °C
- Termination Type: Miniature Plug
- Cable Length: 2 m
- Standards Met: IEC



1314742 J

RS PRO TYPE K THERMOCOUPLE 40MM LENGTH, → +150°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Length: 40 mm
- Maximum Temperature Sensed: +150 °C
- Termination Type: Cable
- Cable Length: 2 m
- Standards Met: IEC



1314738 K

RS PRO TYPE J THERMOCOUPLE 6MM DIAMETER → +350°C

Pack size: **1 x EA**

- Thermocouple Type: J
- Probe Diameter: 6 mm
- Maximum Temperature Sensed: +350 °C
- Termination Type: Standard Plug
- Cable Length: 2 m
- Standards Met: IEC



1314744 J

RS PRO TYPE K THERMOCOUPLE → +350°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Maximum Temperature Sensed: +350 °C
- Termination Type: Standard Plug
- Cable Length: 2 m
- Standards Met: IEC



1314745 K

LEAF THERMOCOUPLE TYPE K 2M

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Length: 25 mm
- Maximum Temperature Sensed: +350 °C
- Termination Type: Standard Plug
- Cable Length: 2 m
- Standards Met: IEC



1314746 K

RS PRO TYPE K THERMOCOUPLE 150MM LENGTH, 4.5MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 4.5 mm
- Probe Length: 150 mm
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +350 °C
- Termination Type: Standard Plug
- Cable Length: 2 m
- Standards Met: IEC



1314748 K

IEC TYPE K FINE WIRE THERMOCOUPLE 2M

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 6.35 mm
- Probe Length: 2 m
- Probe Material: Copper
- Maximum Temperature Sensed: +200 °C
- Termination Type: Miniature Plug
- Cable Length: 2 m
- Standards Met: IEC



1314740 K

RS PRO TYPE K THERMOCOUPLE 2M LENGTH, 6MM DIAMETER → +350°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 6 mm
- Probe Length: 2 m
- Maximum Temperature Sensed: +350 °C
- Termination Type: Standard Plug
- Cable Length: 2 m
- Standards Met: IEC



1314743 K

RS PRO TYPE K THERMOCOUPLE 20M LENGTH, → +700°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Length: 20 m
- Maximum Temperature Sensed: +700 °C
- Termination Type: Standard Plug
- Cable Length: 20 m
- Standards Met: ANSI



1314751 K

THERMOCOUPLE HIGH TEMP EXPOSED JUNCTION

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Length: 5 m
- Maximum Temperature Sensed: +700 °C
- Termination Type: Standard Plug
- Cable Length: 5 m
- Standards Met: ANSI



1314749 K

THERMOCOUPLE MINI TYPE K IEC PLUG 3M

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1/0.3 mm
- Probe Length: 3 m
- Maximum Temperature Sensed: +260 °C
- Termination Type: Miniature Plug
- Cable Length: 3 m
- Standards Met: IEC



1314754 K

RS PRO TYPE K THERMOCOUPLE 3M LENGTH, → +260°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Length: 3 m
- Maximum Temperature Sensed: +260 °C
- Termination Type: Miniature Plug
- Cable Length: 3 m
- Standards Met: IEC



1314757 K

RS PRO TYPE K THERMOCOUPLE 10M LENGTH, → +700°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Length: 10 m
- Maximum Temperature Sensed: +700 °C
- Termination Type: Standard Plug
- Cable Length: 10 m
- Standards Met: ANSI




1314750 K

RS PRO TYPE K THERMOCOUPLE 2M LENGTH, → +260°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Length: 2 m
- Maximum Temperature Sensed: +260 °C
- Termination Type: Miniature Plug
- Cable Length: 2 m
- Standards Met: IEC




1314753 K

RS PRO TYPE K THERMOCOUPLE 1M LENGTH, → +260°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Length: 1 m
- Maximum Temperature Sensed: +260 °C
- Termination Type: Miniature Plug
- Cable Length: 1 m
- Standards Met: ANSI



1314758 K

RS PRO TYPE K THERMOCOUPLE 2M LENGTH, → +260°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Length: 2 m
- Maximum Temperature Sensed: +260 °C
- Termination Type: Miniature Plug
- Cable Length: 2 m
- Standards Met: ANSI



1314759 K

RS PRO TYPE K THERMOCOUPLE 3M LENGTH, → +260°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Length: 3 m
- Maximum Temperature Sensed: +260 °C
- Termination Type: Miniature Plug
- Cable Length: 3 m
- Standards Met: ANSI



1314760 K

RS PRO TYPE K THERMOCOUPLE 6MM DIAMETER → +350°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 6 mm
- Maximum Temperature Sensed: +350 °C
- Termination Type: Standard Plug
- Cable Length: 2 m
- Standards Met: IEC



1314761 K

RS PRO TYPE J THERMOCOUPLE 3M LENGTH, 6MM DIAMETER → +350°C

Pack size: **1 x EA**

- Thermocouple Type: J
- Probe Diameter: 6 mm
- Probe Length: 3 m
- Maximum Temperature Sensed: +350 °C
- Termination Type: Standard Plug
- Cable Length: 3 m
- Standards Met: IEC



1314764 J

RS PRO TYPE K THERMOCOUPLE 250MM LENGTH, 6MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 6 mm
- Probe Length: 250 mm
- Maximum Temperature Sensed: +1100 °C
- Probe Material: 310 Stainless Steel
- Termination Type: Miniature Plug
- Standards Met: IEC 584



1365850 K

RS PRO TYPE K THERMOCOUPLE 3M LENGTH, 6MM DIAMETER → +350°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 6 mm
- Probe Length: 3 m
- Maximum Temperature Sensed: +350 °C
- Termination Type: Standard Plug
- Cable Length: 3 m
- Standards Met: IEC



1314762 K

RS PRO TYPE J THERMOCOUPLE 2M LENGTH, 6MM DIAMETER → +350°C

Pack size: **1 x EA**

- Thermocouple Type: J
- Probe Diameter: 6 mm
- Probe Length: 2 m
- Maximum Temperature Sensed: +350 °C
- Termination Type: Standard Plug
- Cable Length: 2 m
- Standards Met: IEC



1314763 J

RS PRO TYPE J THERMOCOUPLE 0.3MM DIAMETER → +250°C

Pack size: **1 x EA**

- Thermocouple Type: J
- Probe Diameter: 0.3 mm
- Maximum Temperature Sensed: +250 °C
- Termination Type: Miniature Plug
- Cable Length: 1 m
- Standards Met: RoHS Compliant



1365868 J

RS PRO TYPE J THERMOCOUPLE 2M LENGTH, 0.3MM DIAMETER → +250°C

Pack size: **1 x EA**

- Thermocouple Type: J
- Probe Diameter: 0.3 mm
- Probe Length: 2 m
- Maximum Temperature Sensed: +250 °C
- Termination Type: Miniature Plug
- Cable Length: 2 m
- Standards Met: RoHS Compliant



1365870 J

RS PRO TYPE J THERMOCOUPLE 2M LENGTH, → +250°C

Pack size: **1 x EA**

- Thermocouple Type: J
- Probe Length: 2 m
- Maximum Temperature Sensed: +250 °C
- Probe Material: Teflon PFA
- Termination Type: Miniature Plug
- Cable Length: 2 m
- Standards Met: EN 60584-3:2008, IEC 584-3



1365874 J

RS PRO TYPE J THERMOCOUPLE → +250°C

Pack size: **1 x EA**

- Thermocouple Type: J
- Maximum Temperature Sensed: +250 °C
- Probe Material: Teflon PFA
- Termination Type: Miniature Plug
- Cable Length: 5 m
- Standards Met: EN 60584-3:2008, IEC 584-3



1365877 J

RS PRO TYPE K THERMOCOUPLE 1M LENGTH, → +250°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Length: 1 m
- Maximum Temperature Sensed: +250 °C
- Probe Material: Teflon PFA
- Termination Type: Miniature Plug
- Cable Length: 1 m
- Standards Met: EN 60584-3:2008, IEC 584-3



1365879 K

RS PRO TYPE K THERMOCOUPLE → +250°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Maximum Temperature Sensed: +250 °C
- Probe Material: Teflon PFA
- Termination Type: Miniature Plug
- Cable Length: 5 m
- Standards Met: EN 60584-3:2008, IEC 584-3



1365883 K

RS PRO TYPE K THERMOCOUPLE 10M LENGTH, → +250°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Length: 10 m
- Maximum Temperature Sensed: +250 °C
- Probe Material: Teflon PFA
- Termination Type: Miniature Plug
- Cable Length: 10 m
- Standards Met: EN 60584-3:2008, IEC 584-3



1365884 K

RS PRO TYPE K THERMOCOUPLE 2M LENGTH, → +250°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Length: 2 m
- Maximum Temperature Sensed: +250 °C
- Probe Material: Teflon PFA
- Termination Type: Miniature Plug
- Cable Length: 2 m
- Standards Met: EN 60584-3:2008, IEC 584-3



1365880 K

RS PRO TYPE K THERMOCOUPLE 2M LENGTH, → +250°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Length: 2 m
- Maximum Temperature Sensed: +250 °C
- Probe Material: Teflon PFA
- Termination Type: Miniature Plug
- Cable Length: 2 m
- Standards Met: EN 60584-3:2008, IEC 584-3



1365886 K

TYPE K EXP.JUNCTION THERMOCOUPLE PFA 3M

Pack size: **1 x EA**

- Thermocouple Type: K
- Maximum Temperature Sensed: +250 °C
- Probe Material: Teflon PFA
- Termination Type: Miniature Plug
- Cable Length: 3 m
- Standards Met: EN 60584-3:2008, IEC 584-3



1365882 K

TYPE K EXP.JUNCTION THERMOCOUPLE PFA 1M

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Length: 1 m
- Maximum Temperature Sensed: +250 °C
- Probe Material: Teflon PFA
- Termination Type: Miniature Plug
- Cable Length: 1 m
- Standards Met: EN 60584-3:2008, IEC 584-3



1365885 K

RS PRO TYPE K THERMOCOUPLE 1M LENGTH, → +250°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Length: 1 m
- Maximum Temperature Sensed: +250 °C
- Probe Material: Teflon PFA
- Termination Type: Miniature Plug
- Cable Length: 1 m
- Standards Met: EN 60584-3:2008, IEC 584-3



1365889 K

TYPE K EXP.JUNCTION THERMOCOUPLE PFA 3M

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Length: 3 m
- Maximum Temperature Sensed: +250 °C
- Probe Material: Teflon PFA
- Termination Type: Miniature Plug
- Cable Length: 3 m
- Standards Met: EN 60584-3:2008, IEC 584-3



1365887 K

TYPE K EXP.JUNCTION THERMOCOUPLE PFA 5M

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Length: 5 m
- Maximum Temperature Sensed: +250 °C
- Probe Material: Teflon PFA
- Termination Type: Miniature Plug
- Cable Length: 5 m
- Standards Met: EN 60584-3:2008, IEC 584-3



1365888 K

RS PRO TYPE K THERMOCOUPLE 2M LENGTH, → +250°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Length: 2 m
- Maximum Temperature Sensed: +250 °C
- Probe Material: Teflon PFA
- Termination Type: Miniature Plug
- Cable Length: 2 m
- Standards Met: EN 60584-3:2008, IEC 584-3



1365890 K

RS PRO TYPE K THERMOCOUPLE 3M LENGTH, → +250°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Length: 3 m
- Maximum Temperature Sensed: +250 °C
- Probe Material: Teflon PFA
- Termination Type: Miniature Plug
- Cable Length: 3 m
- Standards Met: EN 60584-3:2008, IEC 584-3



1365891 K

RS PRO TYPE K THERMOCOUPLE → +250°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Maximum Temperature Sensed: +250 °C
- Probe Material: Teflon PFA
- Termination Type: Miniature Plug
- Cable Length: 5 m
- Standards Met: EN 60584-3:2008, IEC 584-3



1365892 K

RS PRO TYPE K THERMOCOUPLE 250MM LENGTH, 2MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 2 mm
- Probe Length: 250 mm
- Maximum Temperature Sensed: +1100 °C
- Probe Material: 310 Stainless Steel
- Termination Type: Miniature Plug
- Standards Met: IEC 584



1365895 K

RS PRO TYPE K THERMOCOUPLE 150MM LENGTH, 2MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 2 mm
- Probe Length: 150 mm
- Maximum Temperature Sensed: +1100 °C
- Probe Material: 310 Stainless Steel
- Termination Type: Miniature Plug
- Standards Met: IEC 584



1365896 K

RS PRO TYPE K THERMOCOUPLE → +250°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Maximum Temperature Sensed: +250 °C
- Probe Material: Teflon PFA
- Termination Type: Miniature Plug
- Cable Length: 10 m
- Standards Met: EN 60584-3:2008, IEC 584-3



1365893 K

RS PRO TYPE K THERMOCOUPLE 150MM LENGTH, 2MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 2 mm
- Probe Length: 150 mm
- Maximum Temperature Sensed: +1100 °C
- Probe Material: 310 Stainless Steel
- Termination Type: Miniature Plug
- Standards Met: IEC 584



1365894 K

RS PRO TYPE J THERMOCOUPLE 150MM LENGTH, 3MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: J
- Probe Diameter: 3 mm
- Probe Length: 150 mm
- Maximum Temperature Sensed: +760 °C
- Termination Type: Miniature Plug
- Standards Met: IEC 584



1741665 J

RS PRO TYPE K THERMOCOUPLE 150MM LENGTH, 2MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 2 mm
- Probe Length: 150 mm
- Maximum Temperature Sensed: +1100 °C
- Probe Material: 310 Stainless Steel
- Termination Type: Miniature Plug
- Standards Met: IEC 584



1365899 K

RS PRO TYPE K THERMOCOUPLE 250MM LENGTH, 2MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 2 mm
- Probe Length: 250 mm
- Maximum Temperature Sensed: +1100 °C
- Probe Material: 310 Stainless Steel
- Termination Type: Miniature Plug
- Standards Met: IEC 584



1365900 K

RS PRO TYPE J THERMOCOUPLE 500MM LENGTH, 3MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: J
- Probe Diameter: 3 mm
- Probe Length: 500 mm
- Maximum Temperature Sensed: +760 °C
- Termination Type: Miniature Plug
- Standards Met: IEC 584



1741667 J

RS PRO TYPE K THERMOCOUPLE → +250°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Maximum Temperature Sensed: +250 °C
- Probe Material: Stainless Steel
- Termination Type: Miniature Plug
- Cable Length: 1 m
- Standards Met: IEC 584



1741669 K

RS PRO TYPE K THERMOCOUPLE → +250°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Maximum Temperature Sensed: +250 °C
- Probe Material: Stainless Steel
- Termination Type: Miniature Plug
- Cable Length: 3 m
- Standards Met: IEC 584



1741670 K

RS PRO TYPE J THERMOCOUPLE 3M LENGTH, → +250°C

Pack size: **1 x EA**

- Thermocouple Type: J
- Probe Length: 3 m
- Maximum Temperature Sensed: +250 °C
- Probe Material: Stainless Steel
- Termination Type: Miniature Plug
- Cable Length: 3 m
- Standards Met: IEC 584



1741672 J

RS PRO TYPE K THERMOCOUPLE 150MM LENGTH, 6MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 6 mm
- Probe Length: 150 mm
- Maximum Temperature Sensed: +1100 °C
- Termination Type: Connection Head
- Cable Length: 150 mm



1780979 K

RS PRO TYPE K THERMOCOUPLE 500MM LENGTH, 6MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 6 mm
- Probe Length: 500 mm
- Maximum Temperature Sensed: +1100 °C
- Termination Type: Connection Head
- Cable Length: 500 mm



1780981 K

RS PRO TYPE K THERMOCOUPLE 4MM LENGTH, 3.2MM DIAMETER → +400°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 3.2 mm
- Probe Length: 4 mm
- Probe Material: Nickel Aluminium, Nickel Chrome
- Maximum Temperature Sensed: +400 °C
- Termination Type: Bare Wire Tail
- Cable Length: 1 m



2000601 K

RS PRO TYPE K THERMOCOUPLE 250MM LENGTH, 6MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 6 mm
- Probe Length: 250 mm
- Maximum Temperature Sensed: +1100 °C
- Termination Type: Connection Head
- Cable Length: 250 mm



1780980 K

RS PRO TYPE K THERMOCOUPLE 4MM LENGTH, 4MM DIAMETER → +400°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 4 mm
- Probe Length: 4 mm
- Probe Material: Nickel Aluminium, Nickel Chrome
- Maximum Temperature Sensed: +400 °C
- Termination Type: Bare Wire Tail
- Cable Length: 1 m



2000600 K

RS PRO TYPE J THERMOCOUPLE 4MM LENGTH, 4MM DIAMETER → +400°C

Pack size: **1 x EA**

- Thermocouple Type: J
- Probe Diameter: 4 mm
- Probe Length: 4 mm
- Maximum Temperature Sensed: +400 °C
- Termination Type: Bare Wire Tail
- Cable Length: 1 m



2000603 J

RS PRO TYPE J THERMOCOUPLE 4MM LENGTH, 3.2MM DIAMETER → +400°C

Pack size: **1 x EA**

- Thermocouple Type: J
- Probe Diameter: 3.2 mm
- Probe Length: 4 mm
- Maximum Temperature Sensed: +400 °C
- Termination Type: Bare Wire Tail
- Cable Length: 1 m



2000604 J

RS PRO TYPE J THERMOCOUPLE 4MM DIAMETER → +350°C

Pack size: **1 x EA**

- Thermocouple Type: J
- Probe Diameter: 4 mm
- Probe Material: Copper
- Maximum Temperature Sensed: +350 °C
- Termination Type: Bare Wire Tail
- Cable Length: 2 m



2000607 J

RS PRO TYPE J THERMOCOUPLE 3.5MM DIAMETER → +350°C

Pack size: **1 x EA**

- Thermocouple Type: J
- Probe Diameter: 3.5 mm
- Probe Material: Copper
- Maximum Temperature Sensed: +350 °C
- Termination Type: Bare Wire Tail
- Cable Length: 2 m



2000605 J

RS PRO TYPE K THERMOCOUPLE 3.5MM DIAMETER → +350°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 3.5 mm
- Probe Material: Copper
- Maximum Temperature Sensed: +350 °C
- Termination Type: Bare Wire Tail
- Cable Length: 2 m



2000606 K

RS PRO TYPE K THERMOCOUPLE 4MM DIAMETER → +350°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 4 mm
- Probe Material: Copper
- Maximum Temperature Sensed: +350 °C
- Termination Type: Bare Wire Tail
- Cable Length: 2 m



2000609 K

RS PRO TYPE J THERMOCOUPLE 5MM DIAMETER → +350°C

Pack size: **1 x EA**

- Thermocouple Type: J
- Probe Diameter: 5 mm
- Probe Material: Copper
- Maximum Temperature Sensed: +350 °C
- Termination Type: Bare Wire Tail
- Cable Length: 2 m



2000610 J

RS PRO TYPE K THERMOCOUPLE 5MM DIAMETER → +350°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 5 mm
- Probe Material: Copper
- Maximum Temperature Sensed: +350 °C
- Termination Type: Bare Wire Tail
- Cable Length: 2 m



2000611 K

RS PRO TYPE J THERMOCOUPLE 8MM DIAMETER → +350°C

Pack size: **1 x EA**

- Thermocouple Type: J
- Probe Diameter: 8 mm
- Probe Material: Copper
- Maximum Temperature Sensed: +350 °C
- Termination Type: Bare Wire Tail
- Cable Length: 2 m



2000612 J

RS PRO TYPE K THERMOCOUPLE 8MM DIAMETER → +350°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 8 mm
- Probe Material: Copper
- Maximum Temperature Sensed: +350 °C
- Termination Type: Bare Wire Tail
- Cable Length: 2 m



2000613 K

RS PRO TYPE J THERMOCOUPLE 10MM DIAMETER → +350°C

Pack size: **1 x EA**

- Thermocouple Type: J
- Probe Diameter: 10 mm
- Probe Material: Copper
- Maximum Temperature Sensed: +350 °C
- Termination Type: Bare Wire Tail
- Cable Length: 2 m



2000615 J

RS PRO TYPE K THERMOCOUPLE 10MM DIAMETER → +350°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 10 mm
- Probe Material: Copper
- Maximum Temperature Sensed: +350 °C
- Termination Type: Bare Wire Tail
- Cable Length: 2 m



2000616 K

RS PRO TYPE K THERMOCOUPLE 1M LENGTH, 1MM DIAMETER → +750°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1 mm
- Probe Length: 1 m
- Probe Material: 316 Stainless Steel
- Maximum Temperature Sensed: +750 °C
- Termination Type: Cable
- Cable Length: 100 mm
- Standards Met: IEC



2194359 K

THERMOCOUPLE, MI, K, 1.5MMX0.5M

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1.5 mm
- Probe Length: 500 mm
- Probe Material: 316 Stainless Steel
- Maximum Temperature Sensed: +1100 °C
- Termination Type: Cable
- Cable Length: 100 mm
- Standards Met: IEC



2194365 K

RS PRO TYPE K THERMOCOUPLE 1M LENGTH, 1.5MM DIAMETER → +1100°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1.5 mm
- Probe Length: 1 m
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +1100 °C
- Termination Type: Cable
- Cable Length: 100 mm
- Standards Met: IEC



2194371 K

RS PRO TYPE K THERMOCOUPLE 500MM LENGTH, 3MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 3 mm
- Probe Length: 500 mm
- Probe Material: 316 Stainless Steel
- Maximum Temperature Sensed: +1100 °C
- Termination Type: Cable
- Cable Length: 100 mm
- Standards Met: IEC



2194387 K

THERMOCOUPLE, MI, K, 3.0MMX1.0M

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 3 mm
- Probe Length: 1 m
- Probe Material: 316 Stainless Steel
- Maximum Temperature Sensed: +1100 °C
- Termination Type: Cable
- Cable Length: 100 mm
- Standards Met: IEC



2194393 K

RS PRO TYPE K THERMOCOUPLE 1M LENGTH, 1MM DIAMETER → +750°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1 mm
- Probe Length: 1 m
- Probe Material: Inconel 600
- Maximum Temperature Sensed: +750 °C
- Termination Type: Cable
- Cable Length: 100 mm
- Standards Met: IEC



2194450 K

RS PRO TYPE K THERMOCOUPLE 500MM LENGTH, 1.5MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1.5 mm
- Probe Length: 500 mm
- Probe Material: Inconel 600
- Maximum Temperature Sensed: +1100 °C
- Termination Type: Cable
- Cable Length: 100 mm
- Standards Met: IEC



2194466 K

RS PRO TYPE K THERMOCOUPLE 1M LENGTH, 1.5MM DIAMETER → +1100°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1.5 mm
- Probe Length: 1 m
- Probe Material: Inconel 600
- Maximum Temperature Sensed: +1100 °C
- Termination Type: Cable
- Cable Length: 100 mm
- Standards Met: IEC



2194472 K

RS PRO TYPE K THERMOCOUPLE 500MM LENGTH, 3MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 3 mm
- Probe Length: 500 mm
- Probe Material: Inconel 600
- Maximum Temperature Sensed: +1100 °C
- Termination Type: Cable
- Cable Length: 100 mm
- Standards Met: IEC



2194488 K

THERMOCOUPLE, MI, 3MMX3.0M

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 3 mm
- Probe Length: 300 mm
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +1100 °C
- Termination Type: Cable
- Cable Length: 1 m
- Standards Met: IEC



2194539 K

THERMOCOUPLE, K, MAGNETIC BASE

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Length: 50 mm
- Maximum Temperature Sensed: +100 °C
- Termination Type: Miniature Plug
- Cable Length: 2 m
- Standards Met: IEC



2194545 K

THERMOCOUPLE, N, 3X300MM

Pack size: **1 x EA**

- Thermocouple Type: N
- Probe Diameter: 3 mm
- Probe Length: 300 mm
- Probe Material: Nicrosil Alloy
- Maximum Temperature Sensed: +1300 °C
- Termination Type: Cable
- Cable Length: 1 m
- Standards Met: IEC



2194652 N

RS PRO TYPE J THERMOCOUPLE 76MM LENGTH, 3MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: J
- Probe Diameter: 3 mm
- Probe Length: 76 mm
- Maximum Temperature Sensed: +500 °C
- Probe Material: Constantan, Iron
- Termination Type: Standard Plug
- Standards Met: IEC



2194731 J

RS PRO TYPE K THERMOCOUPLE 3M LENGTH, 1/0.2MM DIAMETER, -75°C →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1/0.2 mm
- Probe Length: 3 m
- Probe Material: Teflon PTFE
- Maximum Temperature Sensed: +260 °C
- Termination Type: Twin Twisted Tail
- Cable Length: 3 m
- Minimum Temperature Sensed: -75 °C



2209487 K

THERMOCOUPLE, PROBE HD, J

Pack size: **1 x EA**

- Thermocouple Type: J
- Probe Diameter: 4.5 mm
- Probe Length: 150 mm
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +350 °C
- Termination Type: Cable
- Cable Length: 2 m
- Standards Met: IEC



2194725 J

RS PRO TYPE J THERMOCOUPLE 3M LENGTH, 1/0.2MM DIAMETER, -75°C →

Pack size: **1 x EA**

- Thermocouple Type: J
- Probe Diameter: 1/0.2 mm
- Probe Length: 3 m
- Maximum Temperature Sensed: +260 °C
- Probe Material: Teflon PTFE
- Termination Type: Twin Twisted Tail
- Cable Length: 3 m
- Standards Met: IEC 584-3



2209486 J

RS PRO TYPE T THERMOCOUPLE 3M LENGTH, 1/0.2MM DIAMETER, -75°C →

Pack size: **1 x EA**

- Thermocouple Type: T
- Probe Diameter: 1/0.2 mm
- Probe Length: 3 m
- Probe Material: Teflon PTFE
- Maximum Temperature Sensed: +260 °C
- Termination Type: Twin Twisted Tail
- Cable Length: 3 m
- Minimum Temperature Sensed: -75 °C



2209488 T

RS PRO TYPE K THERMOCOUPLE 2M LENGTH, 1/0.076MM DIAMETER, -75°C →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1/0.076 mm
- Probe Length: 2 m
- Maximum Temperature Sensed: +260 °C
- Probe Material: Teflon PTFE
- Termination Type: 2-Wire Tail
- Cable Length: 2 m
- Standards Met: ANSI MC96.1



2209490 K

THERMOCOUPLE, MINERAL INSULATED, K, STAINLESS STEEL

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1.5 mm
- Probe Length: 150 mm
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +1100 °C
- Termination Type: Cable
- Cable Length: 100 mm
- Standards Met: IEC



2287445 K

RS PRO TYPE K THERMOCOUPLE 250MM LENGTH, 1.5MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1.5 mm
- Probe Length: 250 mm
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +1100 °C
- Termination Type: Cable
- Cable Length: 100 mm
- Standards Met: IEC



2287451 K

RS PRO TYPE K THERMOCOUPLE 500MM LENGTH, 1/0.076MM

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1/0.076 mm
- Probe Length: 500 mm
- Probe Material: Teflon PTFE
- Maximum Temperature Sensed: +260 °C
- Termination Type: 2-Wire Tail
- Cable Length: 500 m
- Minimum Temperature Sensed: -75 °C



2209491 K

RS PRO TYPE K THERMOCOUPLE 250MM LENGTH, 3MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 3 mm
- Probe Length: 250 mm
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +1100 °C
- Termination Type: Cable
- Cable Length: 100 mm
- Standards Met: IEC



2287489 K

RS PRO TYPE K THERMOCOUPLE 150MM LENGTH, 3MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 3 mm
- Probe Length: 150 mm
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +1100 °C
- Termination Type: Cable
- Cable Length: 100 mm
- Standards Met: IEC



2287467 K

RS PRO TYPE K THERMOCOUPLE 2M LENGTH, 12.5MM DIAMETER, -50°C →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 12.5 mm
- Probe Length: 2 m
- Maximum Temperature Sensed: +250 °C
- Probe Material: PFA
- Series: ANSI
- Termination Type: Miniature Plug
- Cable Length: 2 m



2318457 K

RS PRO TYPE K THERMOCOUPLE 3M LENGTH, 1/0.376MM DIAMETER, -75°C →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1/0.376 mm
- Probe Length: 3 m
- Probe Material: Teflon PTFE
- Maximum Temperature Sensed: +250 °C
- Termination Type: Miniature Plug
- Cable Length: 3 m
- Minimum Temperature Sensed: -75 °C



2209509 K

RS PRO TYPE K THERMOCOUPLE 250MM LENGTH, 6MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 6 mm
- Probe Length: 250 mm
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +1100 °C
- Termination Type: Cable
- Cable Length: 100 mm
- Standards Met: IEC



2287495 K

RS PRO TYPE K THERMOCOUPLE 50MM LENGTH, 25 X 50MM

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 25 x 50 mm
- Probe Length: 50 mm
- Maximum Temperature Sensed: +100 °C
- Probe Material: PFA
- Series: ANSI
- Termination Type: Miniature Plug
- Cable Length: 2 m



2318459 K

RS PRO TYPE K THERMOCOUPLE 40MM LENGTH, 40 X 13 X 5MM

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 40 x 13 x 5 mm
- Probe Length: 40 mm
- Maximum Temperature Sensed: +100 °C
- Probe Material: Silicone Rubber
- Series: ANSI
- Termination Type: Miniature Plug
- Cable Length: 2 m



2318463 K

RS PRO TYPE K THERMOCOUPLE 50MM LENGTH, 25 X 50MM

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 25 x 50 mm
- Probe Length: 50 mm
- Maximum Temperature Sensed: +100 °C
- Probe Material: PFA
- Series: ANSI
- Termination Type: Miniature Plug
- Cable Length: 1 m



2318461 K

RS PRO TYPE T THERMOCOUPLE 3M LENGTH, , -75°C → +250°C

Pack size: **1 x EA**

- Thermocouple Type: T
- Probe Length: 3 m
- Maximum Temperature Sensed: +250 °C
- Probe Material: PVC
- Series: ANSI
- Termination Type: Miniature Plug
- Cable Length: 3 m
- Standards Met: RoHS



2318478 T

RS PRO TYPE T THERMOCOUPLE 3M LENGTH, , -75°C → +250°C

Pack size: **1 x EA**

- Thermocouple Type: T
- Probe Length: 3 m
- Maximum Temperature Sensed: +250 °C
- Probe Material: PFA
- Series: ANSI
- Termination Type: Bare Wire Tail
- Cable Length: 3 m
- Standards Met: RoHS



2318480 T

RS PRO TYPE K THERMOCOUPLE 3M LENGTH, , -75°C → +250°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Length: 3 m
- Maximum Temperature Sensed: +250 °C
- Probe Material: PVC
- Series: ANSI
- Termination Type: Miniature Plug
- Cable Length: 3 m
- Standards Met: RoHS



2318474 K

PROBE,BUTTON MAGNET,THERMOCOUPLE,K

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 6 mm
- Maximum Temperature Sensed: +250 °C
- Probe Material: Stainless Steel
- Termination Type: Miniature Plug
- Cable Length: 1 m
- Standards Met: IEC



2364255 K

RS PRO JIS TYPE K EXPOSED WELDED TIP THE

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1/0.3 mm
- Probe Length: 5 m
- Maximum Temperature Sensed: +250 °C
- Probe Material: PFA
- Termination Type: Bare Wire Tail
- Series: XQ



2394542 K

RS PRO JIS TYPE K EXPOSED WELDED TIP THE

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1/0.3 mm
- Probe Length: 10 m
- Maximum Temperature Sensed: +250 °C
- Probe Material: PFA
- Termination Type: Bare Wire Tail
- Series: XQ



2394544 K

RS PRO JIS TYPE K EXPOSED WELDED TIP THE

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1/0.2 mm
- Probe Length: 10 m
- Maximum Temperature Sensed: +250 °C
- Probe Material: PFA
- Termination Type: Miniature Plug
- Series: XQ



2394532 K

RS PRO JIS TYPE K EXPOSED WELDED TIP THE

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 7/0.2 mm
- Probe Length: 5 m
- Maximum Temperature Sensed: +250 °C
- Probe Material: PFA
- Termination Type: Bare Wire Tail
- Series: XQ



2394552 K

THERMOCOUPLE,PATCH,K

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1/0.3 mm
- Probe Length: 40 mm
- Probe Material: Aluminium Foil Backing, Silicone Rubber
- Maximum Temperature Sensed: +150 °C
- Termination Type: Cable
- Cable Length: 1 m
- Standards Met: IEC



2905036 K

RS PRO TYPE J THERMOCOUPLE 20MM LENGTH, 5MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: J
- Probe Diameter: 5 mm
- Probe Length: 20 mm
- Maximum Temperature Sensed: +400 °C
- Probe Material: 316 Stainless Steel
- Termination Type: Cable
- Cable Length: 2.5 m
- Standards Met: RoHS Compliant



3241737 J

RS PRO TYPE J THERMOCOUPLE 20MM LENGTH, 5MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: J
- Probe Diameter: 5 mm
- Probe Length: 20 mm
- Maximum Temperature Sensed: +400 °C
- Probe Material: 316 Stainless Steel
- Termination Type: Cable
- Cable Length: 2.5 m
- Standards Met: RoHS Compliant



3241721 J

RS PRO TYPE J THERMOCOUPLE 20MM LENGTH, 5MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: J
- Probe Diameter: 5 mm
- Probe Length: 20 mm
- Maximum Temperature Sensed: +400 °C
- Probe Material: 316 Stainless Steel
- Termination Type: Cable
- Cable Length: 2.5 m
- Standards Met: RoHS Compliant



3241844 J

RS PRO TYPE J THERMOCOUPLE 20MM LENGTH, 6MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: J
- Probe Diameter: 6 mm
- Probe Length: 20 mm
- Maximum Temperature Sensed: +600 °C
- Probe Material: 316 Stainless Steel
- Termination Type: Cable
- Cable Length: 2.5 m
- Standards Met: RoHS Compliant



3241894 J

RS PRO TYPE J THERMOCOUPLE 150MM LENGTH, 1MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: J
- Probe Diameter: 1 mm
- Probe Length: 150 mm
- Maximum Temperature Sensed: +400 °C
- Probe Material: 316 Stainless Steel
- Termination Type: Cable
- Cable Length: 2 m
- Standards Met: RoHS Compliant



3242443 J

RS PRO TYPE J THERMOCOUPLE 20MM LENGTH, 8MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: J
- Probe Diameter: 8 mm
- Probe Length: 20 mm
- Maximum Temperature Sensed: +400 °C
- Probe Material: 316 Stainless Steel
- Termination Type: Cable
- Cable Length: 2.5 m
- Standards Met: RoHS Compliant



3241967 J

RS PRO TYPE J THERMOCOUPLE 300MM LENGTH, 1MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: J
- Probe Diameter: 1 mm
- Probe Length: 300 mm
- Maximum Temperature Sensed: +400 °C
- Probe Material: 316 Stainless Steel
- Termination Type: Cable
- Cable Length: 2 m
- Standards Met: RoHS Compliant



3242459 J

RS PRO TYPE J THERMOCOUPLE 150MM LENGTH, 1.5MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: J
- Probe Diameter: 1.5 mm
- Probe Length: 150 mm
- Maximum Temperature Sensed: +400 °C
- Probe Material: 316 Stainless Steel
- Termination Type: Cable
- Cable Length: 2 m
- Standards Met: RoHS Compliant



3242465 J

THERMOCOUPLE K PROBE

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 5 mm
- Probe Length: 20 mm
- Maximum Temperature Sensed: +750 °C
- Probe Material: 316L Stainless Steel
- Termination Type: Cable
- Cable Length: 2.5 m
- Standards Met: RoHS Compliant



3342622 K

THERMOCOUPLE J PROBE

Pack size: **1 x EA**

- Thermocouple Type: J
- Probe Diameter: 5 mm
- Probe Length: 20 mm
- Maximum Temperature Sensed: +600 °C
- Probe Material: 316L Stainless Steel
- Termination Type: Cable
- Cable Length: 2.5 m
- Standards Met: RoHS Compliant



3342638 J

RS PRO TYPE J THERMOCOUPLE 5MM LENGTH, 3MM DIAMETER → +500°C

Pack size: **1 x EA**

- Thermocouple Type: J
- Probe Diameter: 3 mm
- Probe Length: 5 mm
- Maximum Temperature Sensed: +500 °C
- Probe Material: Constantan, Iron
- Termination Type: Standard Plug
- Standards Met: IEC



3534578 J

THERMOCOUPLE, EXPOSED JUNCTION, MIN

Pack size: **1 x EA**

- Thermocouple Type: J
- Probe Diameter: 1/0.2 mm
- Probe Length: 1 m
- Maximum Temperature Sensed: +250 °C
- Termination Type: Miniature Plug
- Cable Length: 1 m
- Standards Met: IEC



3630244 J

THERMOCOUPLE, EXPOSED JUNCTION, MIN

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1/0.2 mm
- Probe Length: 1 m
- Maximum Temperature Sensed: +250 °C
- Termination Type: Miniature Plug
- Cable Length: 1 m
- Standards Met: IEC



3630250 K

THERMOCOUPLE, EXPOSED JUNCTION, MIN

Pack size: **1 x EA**

- Thermocouple Type: T
- Probe Diameter: 1/0.2 mm
- Probe Length: 1 m
- Maximum Temperature Sensed: +250 °C
- Termination Type: Miniature Plug
- Cable Length: 1 m
- Standards Met: IEC



3630266 T

THERMOCOUPLE, EXPOSED JUNCTION, MIN

Pack size: **1 x EA**

- Thermocouple Type: J
- Probe Diameter: 1/0.3 mm
- Probe Length: 2 m
- Maximum Temperature Sensed: +350 °C
- Termination Type: Miniature Plug
- Cable Length: 2 m
- Standards Met: IEC



3630288 J

RS PRO TYPE K THERMOCOUPLE 2M LENGTH, 1/0.315MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1/0.315 mm
- Probe Length: 2 m
- Maximum Temperature Sensed: +350 °C
- Termination Type: Miniature Plug
- Cable Length: 2 m
- Standards Met: IEC
- Response Time: Fast



3630294 K

RS PRO TYPE N THERMOCOUPLE 1/0.3MM DIAMETER → +350°C

Pack size: **1 x EA**

- Thermocouple Type: N
- Probe Diameter: 1/0.3 mm
- Maximum Temperature Sensed: +350 °C
- Termination Type: Miniature Plug
- Cable Length: 2 m
- Standards Met: IEC



3630301 N

RS PRO TYPE J THERMOCOUPLE 1M LENGTH, 1/0.2MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: J
- Probe Diameter: 1/0.2 mm
- Probe Length: 1 m
- Maximum Temperature Sensed: +250 °C
- Termination Type: Miniature Plug
- Cable Length: 1 m
- Standards Met: IEC



3630317 J

THERMOCOUPLE, EXPOSED JUNCTION, MIN

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1/0.2 mm
- Probe Length: 1 m
- Maximum Temperature Sensed: +250 °C
- Termination Type: Miniature Plug
- Cable Length: 1 m
- Standards Met: IEC



3630323 K

THERMOCOUPLE, EXPOSED JUNCTION, MIN

Pack size: **1 x EA**

- Thermocouple Type: T
- Probe Diameter: 1/0.2 mm
- Probe Length: 1 m
- Maximum Temperature Sensed: +250 °C
- Termination Type: Miniature Plug
- Cable Length: 1 m
- Standards Met: IEC



3630339 T

SENSOR, THERMOCOUPLE, K, MINERAL INSULATED, 1.5MM

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1.5 mm
- Probe Length: 150 mm
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +1100 °C
- Termination Type: Cable
- Cable Length: 1 m
- Standards Met: IEC



3971236 K

SENSOR, THERMOCOUPLE, K, MINERAL INSULATED, 1.5MM

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1.5 mm
- Probe Length: 250 mm
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +1100 °C
- Termination Type: Cable
- Cable Length: 1 m
- Standards Met: IEC



3971258 K

SENSOR,THERMOCOUPLE,K,MINERAL INSULATED,3.0MM

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 3 mm
- Probe Length: 150 mm
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +1100 °C
- Termination Type: Cable
- Cable Length: 1 m
- Standards Met: IEC



3971264 K

SENSOR,THERMOCOUPLE,K,MINERAL INSULATED,3.0MM

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 3 mm
- Probe Length: 250 mm
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +1100 °C
- Termination Type: Cable
- Cable Length: 1 m
- Standards Met: IEC



3971270 K

SENSOR,THERMOCOUPLE,K,MINERAL INSULATED,6.0MM

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 6 mm
- Probe Length: 150 mm
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +1100 °C
- Termination Type: Cable
- Cable Length: 1 m
- Standards Met: IEC



3971286 K

RS PRO TYPE K THERMOCOUPLE 250MM LENGTH, 6MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 6 mm
- Probe Length: 250 mm
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +1100 °C
- Termination Type: Cable
- Cable Length: 1 m
- Standards Met: IEC



3971292 K

SENSOR,THERMOCOUPLE,K,MINERAL INSULATED,DUPLEX,1000MM

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 3 mm
- Probe Length: 150 mm
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +1100 °C
- Termination Type: Cable
- Cable Length: 1 m
- Standards Met: IEC



3971359 K

RS PRO TYPE K THERMOCOUPLE 250MM LENGTH, 3MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 3 mm
- Probe Length: 250 mm
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +1100 °C
- Termination Type: Cable
- Cable Length: 1 m
- Standards Met: IEC



3971365 K

SENSOR,THERMOCOUPLE,K,MINERAL INSULATED,DUPLEX,1000MM

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 6 mm
- Probe Length: 150 mm
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +1100 °C
- Termination Type: Cable
- Cable Length: 1 m
- Standards Met: IEC



3971371 K

RS PRO TYPE K THERMOCOUPLE 250MM LENGTH, 6MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 6 mm
- Probe Length: 250 mm
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +1100 °C
- Termination Type: Cable
- Cable Length: 1 m
- Standards Met: IEC



3971387 K

SENSOR,THERMOCOUPLE,K,MINERAL INSULATED,MIN PLUG,1.5MM

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1.5 mm
- Probe Length: 150 mm
- Maximum Temperature Sensed: +1100 °C
- Probe Material: Stainless Steel
- Termination Type: Miniature Plug
- Standards Met: IEC



3971450 K

SENSOR,THERMOCOUPLE,K,MINERAL INSULATED,MIN PLUG,1.5MM

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1.5 mm
- Probe Length: 250 mm
- Maximum Temperature Sensed: +1100 °C
- Probe Material: Stainless Steel
- Termination Type: Miniature Plug
- Standards Met: IEC



3971472 K

SENSOR,THERMOCOUPLE,K,MINERAL INSULATED,MIN PLUG,3.0MM

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 3 mm
- Probe Length: 150 mm
- Maximum Temperature Sensed: +1100 °C
- Probe Material: Stainless Steel
- Termination Type: Miniature Plug
- Standards Met: IEC



3971488 K

SENSOR,THERMOCOUPLE,K,MINERAL INSULATED,MIN PLUG,3.0MM

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 3 mm
- Probe Length: 250 mm
- Maximum Temperature Sensed: +1100 °C
- Probe Material: Stainless Steel
- Termination Type: Miniature Plug
- Standards Met: IEC



3971494 K

SENSOR,THERMOCOUPLE,K,MINERAL INSULATED,STD PLUG,1.5MM

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1.5 mm
- Probe Length: 150 mm
- Maximum Temperature Sensed: +1100 °C
- Probe Material: Nickel Aluminium, Nickel Chrome
- Termination Type: Standard Plug
- Standards Met: IEC



3971501 K

SENSOR,THERMOCOUPLE,K,MINERAL INSULATED,STD PLUG,1.5MM

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1.5 mm
- Probe Length: 250 mm
- Maximum Temperature Sensed: +1100 °C
- Probe Material: Stainless Steel
- Termination Type: Standard Plug
- Standards Met: IEC



3971517 K

SENSOR,THERMOCOUPLE,K,MINERAL INSULATED,STD PLUG,3.0MM

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 3 mm
- Probe Length: 150 mm
- Maximum Temperature Sensed: +1100 °C
- Probe Material: Stainless Steel
- Termination Type: Standard Plug
- Standards Met: IEC



3971539 K

SENSOR,THERMOCOUPLE,K,MINERAL INSULATED,STD PLUG,3.0MM

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 3 mm
- Probe Length: 250 mm
- Maximum Temperature Sensed: +1100 °C
- Probe Material: Stainless Steel
- Termination Type: Standard Plug
- Standards Met: IEC



3971545 K

SENSOR, THERMOCOUPLE, K, MINERAL INSULATED, STD PLUG, 6.0MM

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 6 mm
- Probe Length: 150 mm
- Maximum Temperature Sensed: +1100 °C
- Probe Material: Stainless Steel
- Termination Type: Standard Plug
- Standards Met: IEC



3971551 K

SENSOR, THERMOCOUPLE, K, MINERAL INSULATED, STD PLUG, 6.0MM

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 6 mm
- Probe Length: 250 mm
- Maximum Temperature Sensed: +1100 °C
- Probe Material: Stainless Steel
- Termination Type: Standard Plug
- Standards Met: IEC



3971567 K

SENSOR, THERMOCOUPLE, K, FINE GAUGE, BARE WIRE

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 0.025 mm
- Probe Length: 200 mm
- Termination Type: Cable
- Cable Length: 200 mm
- Standards Met: IEC



3971573 K

RS PRO TYPE K TEMPERATURE PROBE 3M LENGTH, 2.8 X 3.9MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 2.8 x 3.9 mm
- Probe Length: 3 m
- Maximum Temperature Sensed: +1200 °C
- Probe Material: Ceramic Fiber
- Termination Type: Cable
- Cable Length: 3 m
- Standards Met: RoHS Compliant



4071393 K

RS PRO TYPE K THERMOCOUPLE 70MM LENGTH, 3MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 3 mm
- Probe Length: 70 mm
- Maximum Temperature Sensed: +700 °C
- Probe Material: Stainless Steel
- Termination Type: Miniature Plug
- Cable Length: 300 mm
- Standards Met: RoHS Compliant



4334379 K

RS PRO TYPE K THERMOCOUPLE 300MM LENGTH, 3MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 3 mm
- Probe Length: 300 mm
- Maximum Temperature Sensed: +1200 °C
- Probe Material: Stainless Steel
- Termination Type: Miniature Plug
- Cable Length: 2 m
- Standards Met: RoHS Compliant



4334420 K

RS PRO TYPE K THERMOCOUPLE 300MM LENGTH, 4.5MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 4.5 mm
- Probe Length: 300 mm
- Maximum Temperature Sensed: +1200 °C
- Probe Material: Stainless Steel
- Termination Type: Miniature Plug
- Cable Length: 3 m
- Standards Met: RoHS Compliant



4334436 K

THERMOCOUPLE, GROUNDED, K, MI, 0.5X150MM

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 0.5 mm
- Probe Length: 150 mm
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +750 °C
- Termination Type: Cable
- Cable Length: 100 mm
- Standards Met: IEC



4437917 K

THERMOCOUPLE, GROUNDED, K, MI, 0.5X500MM

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 0.5 mm
- Probe Length: 500 mm
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +750 °C
- Termination Type: Cable
- Cable Length: 100 mm
- Standards Met: IEC



4437939 K

RS PRO TYPE K THERMOCOUPLE 500MM LENGTH, 0.5MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 0.5 mm
- Probe Length: 500 mm
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +750 °C
- Termination Type: Cable
- Cable Length: 100 mm
- Standards Met: IEC



4437951 K

THERMOCOUPLE, GROUNDED, K, MI, 0.5X150MM, +MP

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 0.5 mm
- Probe Length: 150 mm
- Maximum Temperature Sensed: +750 °C
- Probe Material: Stainless Steel
- Termination Type: Miniature Plug
- Standards Met: IEC



4437967 K

THERMOCOUPLE, GROUNDED, K, MI, 0.5X250MM, +MP

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 0.5 mm
- Probe Length: 250 mm
- Maximum Temperature Sensed: +750 °C
- Probe Material: Stainless Steel
- Termination Type: Miniature Plug
- Standards Met: IEC



4437973 K

RS PRO TYPE K THERMOCOUPLE 150MM LENGTH, 0.5MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 0.5 mm
- Probe Length: 150 mm
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +750 °C
- Termination Type: Cable
- Cable Length: 100 mm
- Standards Met: IEC



4441231 K

THERMOCOUPLE, INSULATED, K, MI, 0.5X150MM, +MP

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 0.5 mm
- Probe Length: 150 mm
- Maximum Temperature Sensed: +750 °C
- Probe Material: Stainless Steel
- Termination Type: Miniature Plug
- Standards Met: IEC



4441275 K

THERMOCOUPLE, INSULATED, K, MI, 0.5X250MM, +MP

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 0.5 mm
- Probe Length: 250 mm
- Maximum Temperature Sensed: +1100 °C
- Probe Material: Stainless Steel
- Termination Type: Miniature Plug
- Standards Met: IEC



4441281 K

RS PRO TYPE K THERMOCOUPLE 3M LENGTH, 3MM DIAMETER → +1100°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 3 mm
- Probe Length: 3 m
- Probe Material: Inconel 600
- Maximum Temperature Sensed: +1100 °C
- Termination Type: Cable
- Cable Length: 100 mm
- Standards Met: IEC



4553750 K

THERMOCOUPLE,SENSOR,MINERAL,INSULATED,J,1.5X150MM,1M

Pack size: **1 x EA**

- Thermocouple Type: J
- Probe Diameter: 1.5 mm
- Probe Length: 150 mm
- Maximum Temperature Sensed: +760 °C
- Termination Type: Cable
- Cable Length: 1 m
- Standards Met: IEC



4554270 J

RS PRO TYPE J THERMOCOUPLE 250MM LENGTH, 1.5MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: J
- Probe Diameter: 1.5 mm
- Probe Length: 250 mm
- Probe Material: Nickel Aluminium, Nickel Chrome
- Maximum Temperature Sensed: +760 °C
- Termination Type: Cable
- Cable Length: 1 m
- Standards Met: IEC



4554286 J

THERMOCOUPLE,SENSOR,MINERAL,INSULATED,J,3.0X150MM,1M

Pack size: **1 x EA**

- Thermocouple Type: J
- Probe Diameter: 3 mm
- Probe Length: 150 mm
- Maximum Temperature Sensed: +760 °C
- Termination Type: Cable
- Cable Length: 1 m
- Standards Met: IEC



4554292 J

RS PRO TYPE J THERMOCOUPLE 250MM LENGTH, 3MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: J
- Probe Diameter: 3 mm
- Probe Length: 250 mm
- Maximum Temperature Sensed: +760 °C
- Termination Type: Cable
- Cable Length: 1 m
- Standards Met: IEC



4554309 J

RS PRO TYPE J THERMOCOUPLE 150MM LENGTH, 6MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: J
- Probe Diameter: 6 mm
- Probe Length: 150 mm
- Maximum Temperature Sensed: +760 °C
- Termination Type: Cable
- Cable Length: 1 m
- Standards Met: IEC



4554315 J

RS PRO TYPE J THERMOCOUPLE 30MM LENGTH, 5MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: J
- Probe Diameter: 5 mm
- Probe Length: 30 mm
- Maximum Temperature Sensed: +400 °C
- Probe Material: Stainless Steel
- Termination Type: Cable
- Cable Length: 2 m
- Standards Met: RoHS Compliant




5477865 J

SENSOR,THERMOCOUPLE,N,MINERAL INSULATED,INCONEL SHEATH,1.5MM

Pack size: **1 x EA**

- Thermocouple Type: N
- Probe Diameter: 1.5 mm
- Probe Length: 500 mm
- Probe Material: Inconel 600
- Maximum Temperature Sensed: +1250 °C
- Termination Type: Cable
- Cable Length: 2 m
- Standards Met: IEC



6118286 N

RS PRO TYPE N THERMOCOUPLE 500MM LENGTH, 3MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: N
- Probe Diameter: 3 mm
- Probe Length: 500 mm
- Probe Material: Inconel 600
- Maximum Temperature Sensed: +1250 °C
- Termination Type: Cable
- Cable Length: 2 m
- Standards Met: IEC



6118292 N

RS PRO TYPE N THERMOCOUPLE 500MM LENGTH, 1.5MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: N
- Probe Diameter: 1.5 mm
- Probe Length: 500 mm
- Probe Material: Nicrosil Alloy
- Maximum Temperature Sensed: +1250 °C
- Termination Type: Cable
- Cable Length: 2 m
- Standards Met: IEC



6118309 N

RS PRO TYPE N THERMOCOUPLE 500MM LENGTH, 3MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: N
- Probe Diameter: 3 mm
- Probe Length: 500 mm
- Probe Material: Nicrosil Alloy
- Maximum Temperature Sensed: +1250 °C
- Termination Type: Cable
- Cable Length: 2 m
- Standards Met: IEC



6118315 N

THERMOCOUPLE TYPE J VISIBLE WELDING TIP,CABLE PTFE INSULATED

Pack size: **1 x EA**

- Thermocouple Type: J
- Probe Diameter: 2 mm
- Probe Length: 1 m
- Maximum Temperature Sensed: +250 °C
- Probe Material: Teflon PTFE
- Termination Type: Cable
- Cable Length: 1 m
- Standards Met: RoHS Compliant



6212142 J

THERMOCOUPLE TYPE K VISIBLE WELDING TIP,CABLE PTFE INSULATED

Pack size: **5 x EA**

- Thermocouple Type: K
- Probe Diameter: 2 mm
- Probe Length: 1 m
- Maximum Temperature Sensed: +250 °C
- Probe Material: Teflon PTFE
- Termination Type: Cable
- Cable Length: 1 m
- Standards Met: RoHS Compliant



6212158 K

RS PRO TYPE T THERMOCOUPLE 1M LENGTH, 2MM DIAMETER → +350°C

Pack size: **5 x EA**

- Thermocouple Type: T
- Probe Diameter: 2 mm
- Probe Length: 1 m
- Maximum Temperature Sensed: +350 °C
- Probe Material: Teflon PTFE
- Termination Type: Cable
- Cable Length: 1 m
- Standards Met: RoHS Compliant



6212164 T

RS PRO TYPE K THERMOCOUPLE 2M LENGTH, 0.3MM DIAMETER → +600°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 0.3 mm
- Probe Length: 2 m
- Maximum Temperature Sensed: +600 °C
- Probe Material: Glass Fibre
- Termination Type: Cable
- Cable Length: 2 m
- Standards Met: RoHS Compliant



6212170 K

THERMOCOUPLE,INDUSTRIAL,WELDED TIP GLASS FIBRE,J,2M,RS,E06065

Pack size: **1 x EA**

- Thermocouple Type: J
- Probe Diameter: 0.3 mm
- Probe Length: 2 m
- Maximum Temperature Sensed: +750 °C
- Termination Type: Cable
- Cable Length: 2 m
- Standards Met: RoHS Compliant
- Response Time: 0.7 s



6212186 J

THERMOCOUPLE,N,GLASS FIBRE

Pack size: **1 x EA**

- Thermocouple Type: N
- Probe Diameter: 0.3 mm
- Probe Length: 2 m
- Maximum Temperature Sensed: +1200 °C
- Termination Type: Cable
- Cable Length: 2 m
- Standards Met: RoHS Compliant
- Response Time: 0.7 s



6212192 N

THERMOCOUPLE, INDUSTRIAL, WELDED TIP GLASS FIBRE, T, 2M, RS, E06068

Pack size: 1 x EA

- Thermocouple Type: T
- Probe Diameter: 0.3 mm
- Probe Length: 2 m
- Maximum Temperature Sensed: +350 °C
- Termination Type: Cable
- Cable Length: 2 m
- Standards Met: RoHS Compliant
- Response Time: 0.7 s



6212209 T

THERMOCOUPLE, ADJUSTABLE BAYONET, TYPE J, 6X170MM SPRING,

Pack size: 1 x EA

- Thermocouple Type: J
- Probe Diameter: 6 mm
- Probe Length: 175 mm
- Maximum Temperature Sensed: +350 °C
- Probe Material: Stainless Steel
- Termination Type: Cable
- Cable Length: 2 m
- Standards Met: RoHS Compliant



6212215 J

RS PRO TYPE K THERMOCOUPLE 175MM LENGTH, 6MM DIAMETER →

Pack size: 1 x EA

- Thermocouple Type: K
- Probe Diameter: 6 mm
- Probe Length: 175 mm
- Maximum Temperature Sensed: +1100 °C
- Probe Material: Stainless Steel
- Termination Type: Cable
- Cable Length: 2 m
- Standards Met: RoHS Compliant



6212221 K

RS PRO TYPE J THERMOCOUPLE 2M LENGTH, 0.2MM DIAMETER → +400°C

Pack size: 1 x EA

- Thermocouple Type: J
- Probe Diameter: 0.2 mm
- Probe Length: 2 m
- Maximum Temperature Sensed: +400 °C
- Probe Material: Stainless Steel
- Termination Type: Cable
- Cable Length: 2 m
- Standards Met: RoHS Compliant



6212259 J

TYPE J WASHER, 6MM DIAMETER, 2M STAINLESS STEEL BRAIDED

Pack size: 1 x EA

- Thermocouple Type: J
- Probe Diameter: 6 mm
- Probe Length: 2 m
- Maximum Temperature Sensed: +350 °C
- Probe Material: Stainless Steel
- Termination Type: Cable
- Cable Length: 2 m
- Standards Met: RoHS Compliant



6212265 J

TYPE K WASHER, 6MM DIAMETER, 2M STAINLESS STEEL BRAIDED

Pack size: 1 x EA

- Thermocouple Type: K
- Probe Diameter: 6 mm
- Probe Length: 2 m
- Maximum Temperature Sensed: +350 °C
- Probe Material: Stainless Steel
- Termination Type: Cable
- Cable Length: 2 m
- Standards Met: RoHS Compliant



6212271 K

THERMOCOUPLE, SELF ADHESIVE, K, 1M

Pack size: 1 x EA

- Thermocouple Type: K
- Probe Diameter: 6.35 mm
- Probe Length: 1 m
- Maximum Temperature Sensed: +200 °C
- Probe Material: Copper
- Termination Type: Cable
- Cable Length: 1 m
- Standards Met: RoHS Compliant



6212287 K

THERMOCOUPLE, TYPE K, PIPE SURFACE, DIA 13-20MM, 0 TO

Pack size: 1 x EA

- Thermocouple Type: K
- Probe Diameter: 13 → 20 mm
- Probe Length: 2 m
- Maximum Temperature Sensed: +1100 °C
- Termination Type: Cable
- Cable Length: 2 m
- Standards Met: RoHS Compliant
- Response Time: 0.7 s



6212293 K

RS PRO TYPE K THERMOCOUPLE 2M LENGTH, 22 → 30MM DIAMETER →

Pack size: 1 x EA

- Thermocouple Type: K
- Probe Diameter: 22 → 30 mm
- Probe Length: 2 m
- Maximum Temperature Sensed: +1100 °C
- Probe Material: 316 Stainless Steel
- Termination Type: Cable
- Cable Length: 2 m
- Standards Met: RoHS Compliant



6212300 K

RS PRO TYPE K THERMOCOUPLE 2M LENGTH, 30 → 40MM DIAMETER →

Pack size: 1 x EA

- Thermocouple Type: K
- Probe Diameter: 30 → 40 mm
- Probe Length: 2 m
- Maximum Temperature Sensed: +1100 °C
- Probe Material: 316 Stainless Steel
- Termination Type: Cable
- Cable Length: 2 m
- Standards Met: RoHS Compliant



6212316 K

RS PRO TYPE K THERMOCOUPLE 2M LENGTH, 40 → 50MM DIAMETER →

Pack size: 1 x EA

- Thermocouple Type: K
- Probe Diameter: 40 → 50 mm
- Probe Length: 2 m
- Maximum Temperature Sensed: +1100 °C
- Probe Material: 316 Stainless Steel
- Termination Type: Cable
- Cable Length: 2 m
- Standards Met: RoHS Compliant



6212322 K

RS PRO TYPE K THERMOCOUPLE 150MM LENGTH, 6MM DIAMETER →

Pack size: 1 x EA

- Thermocouple Type: K
- Probe Diameter: 6 mm
- Probe Length: 150 mm
- Maximum Temperature Sensed: +1100 °C
- Probe Material: Stainless Steel
- Termination Type: Connection Head
- Standards Met: RoHS Compliant



6212338 K

RS PRO TYPE K THERMOCOUPLE 250MM LENGTH, 6MM DIAMETER →

Pack size: 1 x EA

- Thermocouple Type: K
- Probe Diameter: 6 mm
- Probe Length: 250 mm
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +1100 °C
- Termination Type: Connection Head
- Cable Length: 1 m
- Standards Met: RoHS Compliant



6212350 K

RS PRO TYPE K THERMOCOUPLE 500MM LENGTH, 6MM DIAMETER →

Pack size: 1 x EA

- Thermocouple Type: K
- Probe Diameter: 6 mm
- Probe Length: 500 mm
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +1100 °C
- Termination Type: Connection Head
- Cable Length: 1 m
- Standards Met: RoHS Compliant



6212366 K

RS PRO TYPE J THERMOCOUPLE 200MM LENGTH, 6MM DIAMETER →

Pack size: 1 x EA

- Thermocouple Type: J
- Probe Diameter: 6 mm
- Probe Length: 200 mm
- Maximum Temperature Sensed: +700 °C
- Probe Material: 316L Stainless Steel
- Termination Type: Connection Head
- Standards Met: RoHS Compliant
- Response Time: 5 s



6212388 J

RS PRO TYPE K THERMOCOUPLE 200MM LENGTH, 6MM DIAMETER →

Pack size: 1 x EA

- Thermocouple Type: K
- Probe Diameter: 6 mm
- Probe Length: 200 mm
- Maximum Temperature Sensed: +700 °C
- Probe Material: 310 Stainless Steel
- Termination Type: Connection Head
- Standards Met: RoHS Compliant
- Response Time: 5 s



6212401 K

RS PRO TYPE K THERMOCOUPLE 165MM LENGTH, 8MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 8 mm
- Probe Length: 165 mm
- Maximum Temperature Sensed: +800 °C
- Probe Material: 316L Stainless Steel
- Termination Type: Connection Head
- Standards Met: RoHS Compliant
- Response Time: 20 s



6212417 K

RS PRO TYPE K THERMOCOUPLE 400MM LENGTH, 6MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 6 mm
- Probe Length: 400 mm
- Maximum Temperature Sensed: +800 °C
- Probe Material: 310 Stainless Steel
- Termination Type: Connection Head
- Standards Met: RoHS Compliant
- Response Time: 2.2 s



6212423 K

RS PRO TYPE K THERMOCOUPLE 265MM LENGTH, 8MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 8 mm
- Probe Length: 265 mm
- Maximum Temperature Sensed: +800 °C
- Probe Material: 316L Stainless Steel
- Termination Type: Connection Head
- Standards Met: RoHS Compliant
- Response Time: 20 s



6212439 K

RS PRO TYPE K THERMOCOUPLE 600MM LENGTH, 6MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 6 mm
- Probe Length: 600 mm
- Maximum Temperature Sensed: +800 °C
- Probe Material: 310 Stainless Steel
- Termination Type: Connection Head
- Standards Met: RoHS Compliant
- Response Time: 5 s



6212445 K

RS PRO TYPE K THERMOCOUPLE 150MM LENGTH, 7/0.2MM DIAMETER

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 7/0.2 mm
- Probe Length: 150 mm
- Maximum Temperature Sensed: +250 °C
- Termination Type: Miniature Plug
- Cable Length: 5 m
- Standards Met: IEC



7621112 K

THERMOCOUPLE TYPE K HD MAGNET 2MTS

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 4.5 mm
- Probe Length: 2 m
- Maximum Temperature Sensed: +250 °C
- Termination Type: Miniature Plug
- Cable Length: 2 m
- Standards Met: IEC



7621115 K

THERMOCOUPLE TYPE K WELDED TIP 5M

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1/0.3 mm
- Probe Length: 5 m
- Maximum Temperature Sensed: +250 °C
- Termination Type: Miniature Plug
- Cable Length: 5 m
- Standards Met: IEC



7621118 K

THERMOCOUPLE TYPE T WELDED TIP 5M

Pack size: **1 x EA**

- Thermocouple Type: T
- Probe Diameter: 1/0.315 mm
- Probe Length: 5 m
- Maximum Temperature Sensed: +250 °C
- Termination Type: Miniature Plug
- Cable Length: 5 m
- Standards Met: IEC



7621121 T

RS PRO TYPE T THERMOCOUPLE 5M LENGTH, 7/0.2MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: T
- Probe Diameter: 7/0.2 mm
- Probe Length: 5 m
- Maximum Temperature Sensed: +250 °C
- Termination Type: Miniature Plug
- Cable Length: 5 m
- Standards Met: IEC



7621124 T

THERMOCOUPLE TYPE K 2MTS CABLE

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 4.5 mm
- Probe Length: 150 mm
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +350 °C
- Termination Type: Cable
- Cable Length: 2 m
- Standards Met: IEC



7621128 K

RS PRO TYPE K THERMOCOUPLE 150MM LENGTH, 1MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1 mm
- Probe Length: 150 mm
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +1100 °C
- Termination Type: Cable
- Cable Length: 1 m
- Standards Met: IEC



7877696 K

RS PRO TYPE K THERMOCOUPLE 1M LENGTH, 1MM DIAMETER → +1100°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1 mm
- Probe Length: 1 m
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +1100 °C
- Termination Type: Cable
- Cable Length: 1 m
- Standards Met: IEC




7877703 K

TYPE K INSULATED THERMOCOUPLE, 1.0X250MM

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1 mm
- Probe Length: 250 mm
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +1100 °C
- Termination Type: Cable
- Cable Length: 1 m
- Standards Met: IEC



7877706 K

TYPE K INSULATED THERMOCOUPLE, 1.0X500MM

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1 mm
- Probe Length: 500 mm
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +1100 °C
- Termination Type: Cable
- Cable Length: 1 m
- Standards Met: IEC



7877709 K

RS PRO TYPE K THERMOCOUPLE 1.5M LENGTH, 1MM DIAMETER → +1100°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1 mm
- Probe Length: 1.5 m
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +1100 °C
- Termination Type: Cable
- Cable Length: 1 m
- Standards Met: IEC



7877712 K

TYPE K INSULATED THERMOCOUPLE, 1.0X2000MM

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1 mm
- Probe Length: 2 m
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +1100 °C
- Termination Type: Cable
- Cable Length: 1 m
- Standards Met: IEC



7877715 K

TYPE K INSULATED THERMOCOUPLE,1.5X500MM

- Pack size: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1.5 mm
 - Probe Length: 500 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: IEC



7877719 K

RS PRO TYPE K THERMOCOUPLE 1.5M LENGTH, 1.5MM DIAMETER → +1100°C

- Pack size: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1.5 mm
 - Probe Length: 1.5 m
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: IEC



7877721 K

RS PRO TYPE K THERMOCOUPLE 2M LENGTH, 1.5MM DIAMETER → +1100°C

- Pack size: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1.5 mm
 - Probe Length: 2 m
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: IEC



7877725 K

RS PRO TYPE K THERMOCOUPLE 1M LENGTH, 1.5MM DIAMETER → +1100°C

- Pack size: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1.5 mm
 - Probe Length: 1 m
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: IEC



7877728 K

RS PRO TYPE K THERMOCOUPLE 1.5M LENGTH, 3MM DIAMETER → +1100°C

- Pack size: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 3 mm
 - Probe Length: 1.5 m
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: IEC



7877731 K

TYPE K INSULATED THERMOCOUPLE,3X500MM

- Pack size: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 3 mm
 - Probe Length: 500 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: IEC



7877734 K

TYPE K INSULATED THERMOCOUPLE,3X1000MM

- Pack size: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 3 mm
 - Probe Length: 1 m
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: IEC



7877737 K

RS PRO TYPE K THERMOCOUPLE 500MM LENGTH, 6MM DIAMETER →

- Pack size: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 6 mm
 - Probe Length: 500 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: IEC



7877759 K

K INSULATED THERMOCOUPLEW/PLUG,1X150MM

- Pack size: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1 mm
 - Probe Length: 150 mm
 - Maximum Temperature Sensed: +750 °C
 - Probe Material: Stainless Steel
 - Termination Type: Miniature Plug
 - Standards Met: IEC



7877762 K

K INSULATED THERMOCOUPLEW/PLUG,1X250MM

- Pack size: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1 mm
 - Probe Length: 250 mm
 - Maximum Temperature Sensed: +750 °C
 - Probe Material: Stainless Steel
 - Termination Type: Miniature Plug
 - Standards Met: IEC



7877765 K

RS PRO TYPE K THERMOCOUPLE 500MM LENGTH, 1MM DIAMETER →

- Pack size: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1 mm
 - Probe Length: 500 mm
 - Maximum Temperature Sensed: +750 °C
 - Probe Material: Stainless Steel
 - Termination Type: Miniature Plug
 - Standards Met: IEC



7877769 K

K INSULATED THERMOCOUPLEW/PLUG,1.5X500MM

- Pack size: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1.5 mm
 - Probe Length: 500 mm
 - Maximum Temperature Sensed: +1100 °C
 - Probe Material: Stainless Steel
 - Termination Type: Miniature Plug
 - Standards Met: IEC



7877771 K

K INSULATED THERMOCOUPLE W/PLUG, 1.5X1000MM

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1.5 mm
- Probe Length: 1 m
- Maximum Temperature Sensed: +1100 °C
- Probe Material: Stainless Steel
- Termination Type: Miniature Plug
- Standards Met: IEC



7877775 K

K INSULATED THERMOCOUPLE W/PLUG, 1X1000MM

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1 mm
- Probe Length: 1 m
- Maximum Temperature Sensed: +750 °C
- Probe Material: Stainless Steel
- Termination Type: Miniature Plug
- Standards Met: IEC



7877778 K

K INSULATED THERMOCOUPLE W/PLUG, 3X500MM

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 3 mm
- Probe Length: 500 mm
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +1100 °C
- Termination Type: Miniature Plug
- Cable Length: 100 mm
- Standards Met: IEC



7877784 K

RS PRO TYPE K THERMOCOUPLE 1M LENGTH, 3MM DIAMETER → +1100°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 3 mm
- Probe Length: 1 m
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +1100 °C
- Termination Type: Miniature Plug
- Cable Length: 100 mm
- Standards Met: IEC



7877787 K

RS PRO TYPE K THERMOCOUPLE 1M LENGTH, 3MM DIAMETER → +1100°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 3 mm
- Probe Length: 1 m
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +1100 °C
- Termination Type: Standard Plug
- Cable Length: 100 mm
- Standards Met: IEC



7877797 K

RS PRO TYPE K THERMOCOUPLE 500MM LENGTH, 1.5MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1.5 mm
- Probe Length: 500 mm
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +1100 °C
- Termination Type: Standard Plug
- Cable Length: 100 mm
- Standards Met: IEC



7877781 K

RS PRO TYPE K THERMOCOUPLE 1M LENGTH, 6MM DIAMETER → +1100°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 6 mm
- Probe Length: 1 m
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +1100 °C
- Termination Type: Standard Plug
- Cable Length: 100 mm
- Standards Met: IEC



7877800 K

RS PRO TYPE K THERMOCOUPLE 100MM LENGTH, 6MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 6 mm
- Probe Length: 100 mm
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +1100 °C
- Termination Type: Cable
- Cable Length: 100 mm
- Standards Met: IEC



7877804 K

RS PRO TYPE K THERMOCOUPLE 250MM LENGTH, 6MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 6 mm
- Probe Length: 250 mm
- Maximum Temperature Sensed: +1100 °C
- Probe Material: Stainless Steel
- Termination Type: Cable
- Standards Met: IEC



7877810 K

RS PRO TYPE K THERMOCOUPLE 150MM LENGTH, 6MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 6 mm
- Probe Length: 150 mm
- Maximum Temperature Sensed: +1100 °C
- Probe Material: Stainless Steel
- Termination Type: Cable
- Standards Met: IEC



7877813 K

RS PRO TYPE K THERMOCOUPLE 200MM LENGTH, 6MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 6 mm
- Probe Length: 200 mm
- Maximum Temperature Sensed: +1100 °C
- Probe Material: Stainless Steel
- Termination Type: Cable
- Standards Met: IEC



7877816 K

RS PRO TYPE K THERMOCOUPLE 150MM LENGTH, 1MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1 mm
- Probe Length: 150 mm
- Probe Material: Inconel 600, Stainless Steel
- Maximum Temperature Sensed: +750 °C
- Termination Type: Cable
- Cable Length: 100 mm
- Standards Met: IEC



7877822 K

RS PRO TYPE K THERMOCOUPLE 250MM LENGTH, 1MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1 mm
- Probe Length: 250 mm
- Probe Material: Inconel 600, Stainless Steel
- Maximum Temperature Sensed: +750 °C
- Termination Type: Cable
- Cable Length: 100 mm
- Standards Met: IEC



7877826 K

RS PRO TYPE K THERMOCOUPLE 300MM LENGTH, 6MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 6 mm
- Probe Length: 300 mm
- Maximum Temperature Sensed: +1100 °C
- Probe Material: Stainless Steel
- Termination Type: Cable
- Standards Met: IEC



7877829 K

RS PRO TYPE K THERMOCOUPLE 500MM LENGTH, 1MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1 mm
- Probe Length: 500 mm
- Probe Material: Inconel 600, Stainless Steel
- Maximum Temperature Sensed: +750 °C
- Termination Type: Cable
- Cable Length: 100 mm
- Standards Met: IEC



7877835 K

RS PRO TYPE K THERMOCOUPLE 1.5M LENGTH, 1.5MM DIAMETER → +1100°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1.5 mm
- Probe Length: 1.5 m
- Probe Material: Inconel 600, Stainless Steel
- Maximum Temperature Sensed: +1100 °C
- Termination Type: Cable
- Cable Length: 100 mm
- Standards Met: IEC



7877841 K

RS PRO TYPE K THERMOCOUPLE 2M LENGTH, 1.5MM DIAMETER → +1100°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1.5 mm
- Probe Length: 2 m
- Probe Material: Inconel 600, Stainless Steel
- Maximum Temperature Sensed: +1100 °C
- Termination Type: Cable
- Cable Length: 100 mm
- Standards Met: IEC



7877844 K

RS PRO TYPE K THERMOCOUPLE 1.5M LENGTH, 3MM DIAMETER → +1100°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 3 mm
- Probe Length: 1.5 m
- Probe Material: Inconel 600, Stainless Steel
- Maximum Temperature Sensed: +1100 °C
- Termination Type: Cable
- Cable Length: 100 mm
- Standards Met: IEC



7877848 K

RS PRO TYPE K THERMOCOUPLE 250MM LENGTH, 4.5MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 4.5 mm
- Probe Length: 250 mm
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +1100 °C
- Termination Type: Cable
- Cable Length: 100 mm
- Standards Met: IEC



7877850 K

RS PRO TYPE K THERMOCOUPLE 150MM LENGTH, 4.5MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 4.5 mm
- Probe Length: 150 mm
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +1100 °C
- Termination Type: Cable
- Cable Length: 100 mm
- Standards Met: IEC



7877857 K

RS PRO TYPE K THERMOCOUPLE 1M LENGTH, 0.5MM DIAMETER → +750°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 0.5 mm
- Probe Length: 1 m
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +750 °C
- Termination Type: Cable
- Cable Length: 100 mm
- Standards Met: IEC



7877860 K

RS PRO TYPE K THERMOCOUPLE 1M LENGTH, 0.5MM DIAMETER → +750°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 0.5 mm
- Probe Length: 1 m
- Probe Material: Inconel 600, Stainless Steel
- Maximum Temperature Sensed: +750 °C
- Termination Type: Cable
- Cable Length: 100 mm
- Standards Met: IEC



7877866 K

IEC G/F THERMOCOUPLE, MINI PLUG, K, 5M

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1/0.3 mm
- Probe Length: 5 m
- Maximum Temperature Sensed: +350 °C
- Termination Type: Miniature Plug
- Cable Length: 5 m
- Standards Met: IEC



8047874 K

RS PRO TYPE K THERMOCOUPLE CONNECTOR 10M LENGTH, , -75°C →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Length: 10 m
- Maximum Temperature Sensed: +250 °C
- Termination Type: Miniature Plug
- Standards Met: IEC
- Minimum Temperature Sensed: -75 °C



8047886 K

RS PRO TYPE T THERMOCOUPLE CONNECTOR 10M LENGTH, , -75°C →

Pack size: **1 x EA**

- Thermocouple Type: T
- Probe Length: 10 m
- Maximum Temperature Sensed: +250 °C
- Termination Type: Miniature Plug
- Standards Met: IEC
- Minimum Temperature Sensed: -75 °C



8047892 T

RS PRO TYPE K THERMOCOUPLE CONNECTOR 5M LENGTH, , -75°C →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Length: 5 m
- Maximum Temperature Sensed: +250 °C
- Termination Type: Miniature Plug
- Standards Met: IEC
- Minimum Temperature Sensed: -75 °C



8047899 K

RS PRO TYPE T THERMOCOUPLE CONNECTOR 5M LENGTH, , -75°C →

Pack size: **1 x EA**

- Thermocouple Type: T
- Probe Length: 5 m
- Maximum Temperature Sensed: +250 °C
- Termination Type: Miniature Plug
- Standards Met: IEC
- Minimum Temperature Sensed: -75 °C



8047906 T

RS PRO TYPE K THERMOCOUPLE CONNECTOR 150MM LENGTH, 1.5MM

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1.5 mm
- Probe Length: 150 mm
- Maximum Temperature Sensed: +1100 °C
- Termination Type: Miniature Plug
- Standards Met: ANSI
- Minimum Temperature Sensed: -40 °C



8047909 K

RS PRO TYPE K THERMOCOUPLE CONNECTOR 250MM LENGTH, 3MM

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 3 mm
- Probe Length: 250 mm
- Maximum Temperature Sensed: +1100 °C
- Termination Type: Miniature Plug
- Standards Met: ANSI
- Minimum Temperature Sensed: -40 °C



8047915 K

RS PRO TYPE K THERMOCOUPLE CONNECTOR 150MM LENGTH, 1MM

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1 mm
- Probe Length: 150 mm
- Maximum Temperature Sensed: +1100 °C
- Termination Type: Miniature Plug
- Standards Met: ANSI
- Minimum Temperature Sensed: -40 °C



8047931 K

RS PRO TYPE K THERMOCOUPLE CONNECTOR 1M LENGTH, 1.5MM

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1.5 mm
- Probe Length: 1 m
- Maximum Temperature Sensed: +1100 °C
- Termination Type: Miniature Plug
- Standards Met: ANSI
- Minimum Temperature Sensed: -40 °C



8047956 K

RS PRO TYPE K THERMOCOUPLE CONNECTOR 3MM DIAMETER, -40°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 3 mm
- Maximum Temperature Sensed: +1100 °C
- Termination Type: Miniature Plug
- Standards Met: ANSI
- Minimum Temperature Sensed: -40 °C



8047965 K

RS PRO TYPE K THERMOCOUPLE 1M LENGTH, , -75°C → +260°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Length: 1 m
- Maximum Temperature Sensed: +260 °C
- Termination Type: Cable
- Standards Met: IEC
- Minimum Temperature Sensed: -75 °C



8047981 K

RS PRO TYPE K THERMOCOUPLE 500MM LENGTH, , -75°C → +260°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Length: 500 mm
- Maximum Temperature Sensed: +260 °C
- Termination Type: Cable
- Standards Met: IEC
- Minimum Temperature Sensed: -75 °C



8047987 K

RS PRO TYPE K THERMOCOUPLE 2M LENGTH, , -75°C → +260°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Length: 2 m
- Maximum Temperature Sensed: +260 °C
- Termination Type: Cable
- Standards Met: IEC
- Minimum Temperature Sensed: -75 °C



8047990 K

RS PRO TYPE K THERMOCOUPLE → +250°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Maximum Temperature Sensed: +250 °C
- Probe Material: Nickel Aluminium, Nickel Chrome
- Termination Type: Miniature Plug
- Cable Length: 1 m
- Standards Met: ANSI



8140125 K

ANSI K PFA EXPOSED JUNCTION + MP, 2M

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1/0.2 mm
- Probe Length: 2 m
- Maximum Temperature Sensed: +250 °C
- Termination Type: Miniature Plug
- Cable Length: 2 m
- Standards Met: ANSI



8140131 K

ANSI K PFA EXPOSED JUNCTION + MP, 2M

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1/0.3 mm
- Probe Length: 2 m
- Maximum Temperature Sensed: +250 °C
- Termination Type: Miniature Plug
- Cable Length: 2 m
- Standards Met: ANSI



8140134 K

ANSI K PFA EXPOSED JUNCTION + MP, 1M

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1/0.2 mm
- Probe Length: 1 m
- Maximum Temperature Sensed: +250 °C
- Termination Type: Miniature Plug
- Cable Length: 1 m
- Standards Met: ANSI



8140137 K

RS PRO TYPE K THERMOCOUPLE 7/0.2MM DIAMETER → +250°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 7/0.2 mm
- Maximum Temperature Sensed: +250 °C
- Probe Material: Nickel Aluminium, Nickel Chrome
- Termination Type: Miniature Plug
- Cable Length: 1 m
- Standards Met: ANSI



8140140 K

RS PRO TYPE K THERMOCOUPLE 2M LENGTH, 7/0.2MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 7/0.2 mm
- Probe Length: 2 m
- Probe Material: Nickel Aluminium, Nickel Chrome
- Maximum Temperature Sensed: +250 °C
- Termination Type: Miniature Plug
- Cable Length: 2 m
- Standards Met: ANSI



8140143 K

ANSI K F/G EXPOSED JUNCTION + MP, 1M

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1/0.3 mm
- Probe Length: 1 m
- Maximum Temperature Sensed: +350 °C
- Termination Type: Miniature Plug
- Cable Length: 1 m
- Standards Met: ANSI



8140147 K

ANSI T PFA EXPOSED JUNCTION + MP, 2M

Pack size: **1 x EA**

- Thermocouple Type: T
- Probe Diameter: 0.2mm, 0.3 mm
- Probe Length: 2 m
- Maximum Temperature Sensed: +250 °C
- Termination Type: Miniature Plug
- Cable Length: 2 m
- Standards Met: ANSI



8140153 T

ANSI K F/G EXPOSED JUNCTION + MP, 2M

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1/0.3 mm
- Probe Length: 2 m
- Maximum Temperature Sensed: +350 °C
- Termination Type: Miniature Plug
- Cable Length: 2 m
- Standards Met: ANSI



8140156 K

RS PRO TYPE T THERMOCOUPLE 1M LENGTH, 1/0.3MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: T
- Probe Diameter: 1/0.3 mm
- Probe Length: 1 m
- Probe Material: Copper
- Maximum Temperature Sensed: +250 °C
- Termination Type: Miniature Plug
- Cable Length: 1 m
- Standards Met: ANSI



8140159 T

RS PRO TYPE K THERMOCOUPLE 250MM LENGTH, 1.5MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1.5 mm
- Probe Length: 250 mm
- Maximum Temperature Sensed: +900 °C
- Probe Material: Inconel 600
- Termination Type: Standard Plug
- Standards Met: RoHS Compliant
- Response Time: 0.9 s



8240509 K

RS PRO TYPE K THERMOCOUPLE 150MM LENGTH, 3MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 3 mm
- Probe Length: 150 mm
- Maximum Temperature Sensed: +1200 °C
- Probe Material: Inconel 600, Stainless Steel
- Termination Type: Standard Plug
- Standards Met: RoHS Compliant
- Response Time: 2.1 s



8240512 K

RS PRO TYPE K THERMOCOUPLE 250MM LENGTH, 6MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 6 mm
- Probe Length: 250 mm
- Maximum Temperature Sensed: +1200 °C
- Probe Material: 310 Stainless Steel
- Termination Type: Standard Plug
- Standards Met: RoHS Compliant
- Response Time: 5 s



8240584 K

RS PRO TYPE K THERMOCOUPLE 500MM LENGTH, 6MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 6 mm
- Probe Length: 500 mm
- Maximum Temperature Sensed: +1200 °C
- Probe Material: 310 Stainless Steel
- Termination Type: Standard Plug
- Standards Met: RoHS Compliant
- Response Time: 5 s



8240596 K

K TYPE INSULATED THERMOCOUPLE 100MM

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1 mm
- Probe Length: 100 mm
- Maximum Temperature Sensed: +800 °C
- Probe Material: Inconel 600
- Termination Type: Miniature Plug
- Standards Met: RoHS Compliant
- Response Time: 0.7 s



8240603 K

K TYPE INSULATED THERMOCOUPLE 1000MM

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1 mm
- Probe Length: 1 m
- Maximum Temperature Sensed: +800 °C
- Probe Material: Inconel 600
- Termination Type: Miniature Plug
- Standards Met: RoHS Compliant
- Response Time: 0.7 s



8240613 K

RS PRO TYPE K THERMOCOUPLE 500MM LENGTH, 1MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1 mm
- Probe Length: 500 mm
- Maximum Temperature Sensed: +800 °C
- Probe Material: Inconel 600
- Termination Type: Miniature Plug
- Standards Met: RoHS Compliant
- Response Time: 0.7 s



8240619 K

K TYPE INSULATED THERMOCOUPLE 100MM

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1.5 mm
- Probe Length: 100 mm
- Maximum Temperature Sensed: +800 °C
- Probe Material: Inconel 600
- Termination Type: Miniature Plug
- Standards Met: RoHS Compliant
- Response Time: 0.9 s



8240622 K

RS PRO TYPE K THERMOCOUPLE 150MM LENGTH, 1.5MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1.5 mm
- Probe Length: 150 mm
- Maximum Temperature Sensed: +800 °C
- Probe Material: Inconel 600
- Termination Type: Miniature Plug
- Standards Met: RoHS Compliant
- Response Time: 0.9 s



8240625 K

RS PRO TYPE K THERMOCOUPLE 250MM LENGTH, 1.5MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1.5 mm
- Probe Length: 250 mm
- Maximum Temperature Sensed: +800 °C
- Probe Material: Inconel 600
- Termination Type: Miniature Plug
- Standards Met: RoHS Compliant
- Response Time: 0.9 s



8240629 K

K TYPE INSULATED THERMOCOUPLE 1000MM

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1.5 mm
- Probe Length: 1 m
- Maximum Temperature Sensed: +800 °C
- Probe Material: Inconel 600
- Termination Type: Miniature Plug
- Standards Met: RoHS Compliant
- Response Time: 0.9 s



8240631 K

K TYPE INSULATED THERMOCOUPLE 100MM

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1 mm
- Probe Length: 100 mm
- Maximum Temperature Sensed: +800 °C
- Probe Material: Inconel 600
- Termination Type: Cable
- Cable Length: 1 m
- Standards Met: RoHS Compliant



8240635 K

RS PRO TYPE K THERMOCOUPLE 500MM LENGTH, 1.5MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1.5 mm
- Probe Length: 500 mm
- Maximum Temperature Sensed: +800 °C
- Probe Material: Inconel 600
- Termination Type: Miniature Plug
- Standards Met: RoHS Compliant
- Response Time: 0.9 s




8240638 K

K TYPE INSULATED THERMOCOUPLE 150MM

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1 mm
- Probe Length: 150 mm
- Maximum Temperature Sensed: +800 °C
- Probe Material: Inconel 600
- Termination Type: Cable
- Cable Length: 1 m
- Standards Met: RoHS Compliant



8240644 K

RS PRO TYPE K THERMOCOUPLE 500MM LENGTH, 1MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1 mm
- Probe Length: 500 mm
- Maximum Temperature Sensed: +800 °C
- Probe Material: Inconel 600
- Termination Type: Cable
- Cable Length: 1 m
- Standards Met: RoHS Compliant



8240641 K

RS PRO TYPE K THERMOCOUPLE 250MM LENGTH, 1MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1 mm
- Probe Length: 250 mm
- Maximum Temperature Sensed: +800 °C
- Probe Material: Inconel 600
- Termination Type: Cable
- Cable Length: 1 m
- Standards Met: RoHS Compliant



8240647 K

RS PRO TYPE K THERMOCOUPLE 150MM LENGTH, 1.5MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1.5 mm
- Probe Length: 150 mm
- Maximum Temperature Sensed: +800 °C
- Probe Material: Inconel 600
- Termination Type: Cable
- Cable Length: 1 m
- Standards Met: RoHS Compliant



8240653 K

RS PRO TYPE K THERMOCOUPLE 2M LENGTH, 1.5MM DIAMETER → +800°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1.5 mm
- Probe Length: 2 m
- Maximum Temperature Sensed: +800 °C
- Probe Material: Inconel 600
- Termination Type: Cable
- Cable Length: 1 m
- Standards Met: RoHS Compliant



8240672 K

K TYPE INSULATED THERMOCOUPLE 150MM

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 3 mm
- Probe Length: 150 mm
- Maximum Temperature Sensed: +1200 °C
- Probe Material: Inconel 600, Stainless Steel
- Termination Type: Cable
- Cable Length: 1 m
- Standards Met: RoHS Compliant



8240675 K

K TYPE INSULATED THERMOCOUPLE
250MM

- Pack size: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 3 mm
 - Probe Length: 250 mm
 - Maximum Temperature Sensed: +1200 °C
 - Probe Material: Inconel 600, Stainless Steel
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: RoHS Compliant



8240679 K

K TYPE INSULATED THERMOCOUPLE
500MM

- Pack size: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 3 mm
 - Probe Length: 500 mm
 - Maximum Temperature Sensed: +1200 °C
 - Probe Material: Inconel 600, Stainless Steel
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: RoHS Compliant



8240688 K

RS PRO TYPE K THERMOCOUPLE
500MM LENGTH, 1MM DIAMETER →

- Pack size: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1 mm
 - Probe Length: 500 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: ANSI



8471021 K

RS PRO TYPE K THERMOCOUPLE
150MM LENGTH, 1.5MM DIAMETER →

- Pack size: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1.5 mm
 - Probe Length: 150 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: ANSI



8471025 K

TYPE K THERMOCOUPLE, S/S,
1X150MM + ANSI

- Pack size: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1 mm
 - Probe Length: 150 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +750 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: ANSI



8471019 K

RS PRO TYPE K THERMOCOUPLE
250MM LENGTH, 1MM DIAMETER →

- Pack size: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1 mm
 - Probe Length: 250 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: ANSI



8471028 K

RS PRO TYPE K THERMOCOUPLE
150MM LENGTH, 3MM DIAMETER →

- Pack size: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 3 mm
 - Probe Length: 150 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: ANSI



8471031 K

RS PRO TYPE K THERMOCOUPLE
500MM LENGTH, 1.5MM DIAMETER →

- Pack size: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1.5 mm
 - Probe Length: 500 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: ANSI



8471037 K

RS PRO TYPE K THERMOCOUPLE
250MM LENGTH, 3MM DIAMETER →

- Pack size: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 3 mm
 - Probe Length: 250 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: ANSI



8471040 K

RS PRO TYPE K THERMOCOUPLE
150MM LENGTH, 4.5MM DIAMETER →

- Pack size: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 4.5 mm
 - Probe Length: 150 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: ANSI



8471047 K

RS PRO TYPE K THERMOCOUPLE
150MM LENGTH, 6MM DIAMETER →

- Pack size: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 6 mm
 - Probe Length: 150 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: ANSI



8471053 K

RS PRO TYPE K THERMOCOUPLE
250MM LENGTH, 6MM DIAMETER →

- Pack size: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 6 mm
 - Probe Length: 250 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: ANSI



8471062 K

RS PRO TYPE K THERMOCOUPLE
500MM LENGTH, 6MM DIAMETER →

- Pack size: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 6 mm
 - Probe Length: 500 mm
 - Probe Material: Stainless Steel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 1 m
 - Standards Met: ANSI



8471065 K

RS PRO TYPE K THERMOCOUPLE
500MM LENGTH, 0.5MM DIAMETER →

- Pack size: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 0.5 mm
 - Probe Length: 500 mm
 - Probe Material: Inconel 600, Stainless Steel
 - Maximum Temperature Sensed: +750 °C
 - Termination Type: Cable
 - Cable Length: 100 mm
 - Standards Met: ANSI



8471075 K

RS PRO TYPE K THERMOCOUPLE 1M
LENGTH, 1.5MM DIAMETER → +1100°C

- Pack size: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 1.5 mm
 - Probe Length: 1 m
 - Probe Material: Inconel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 100 mm
 - Standards Met: ANSI



8471081 K

RS PRO TYPE K THERMOCOUPLE 1M
LENGTH, 3MM DIAMETER → +1100°C

- Pack size: 1 x EA
- Thermocouple Type: K
 - Probe Diameter: 3 mm
 - Probe Length: 1 m
 - Probe Material: Inconel
 - Maximum Temperature Sensed: +1100 °C
 - Termination Type: Cable
 - Cable Length: 100 mm
 - Standards Met: ANSI



8471093 K

**RS PRO TYPE K THERMOCOUPLE
500MM LENGTH, 0.5MM DIAMETER,**

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 0.5 mm
- Probe Length: 500 mm
- Maximum Temperature Sensed: +750 °C
- Probe Material: Inconel
- Termination Type: Cable
- Cable Length: 100 mm
- Standards Met: ANSI



8471084 K

**RS PRO TYPE K THERMOCOUPLE
500MM LENGTH, 3MM DIAMETER →**

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 3 mm
- Probe Length: 500 mm
- Probe Material: Inconel
- Maximum Temperature Sensed: +1100 °C
- Termination Type: Cable
- Cable Length: 100 mm
- Standards Met: ANSI



8471100 K

**RS PRO TYPE K THERMOCOUPLE 2M
LENGTH, 3MM DIAMETER → +1100°C**

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 3 mm
- Probe Length: 2 m
- Probe Material: Inconel
- Maximum Temperature Sensed: +1100 °C
- Termination Type: Cable
- Cable Length: 100 mm
- Standards Met: ANSI



8471097 K

**RS PRO TYPE K THERMOCOUPLE 3M
LENGTH, 3MM DIAMETER → +1100°C**

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 3 mm
- Probe Length: 3 m
- Probe Material: Inconel
- Maximum Temperature Sensed: +1100 °C
- Termination Type: Cable
- Cable Length: 100 mm
- Standards Met: ANSI



8471107 K

**TYPE K
THERMOCOUPLE, S/S, 1X150MM +**

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1 mm
- Probe Length: 150 mm
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +750 °C
- Termination Type: Cable
- Cable Length: 100 mm
- Standards Met: ANSI



8471122 K

**RS PRO TYPE K THERMOCOUPLE
250MM LENGTH, 1MM DIAMETER →**

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1 mm
- Probe Length: 250 mm
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +1100 °C
- Termination Type: Cable
- Cable Length: 100 mm
- Standards Met: ANSI



8471126 K

**RS PRO TYPE K THERMOCOUPLE
250MM LENGTH, 0.5MM DIAMETER →**

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 0.5 mm
- Probe Length: 250 mm
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +1100 °C
- Termination Type: Cable
- Cable Length: 100 mm
- Standards Met: ANSI



8471116 K

**RS PRO TYPE K THERMOCOUPLE
500MM LENGTH, 1MM DIAMETER →**

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1 mm
- Probe Length: 500 mm
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +1100 °C
- Termination Type: Cable
- Cable Length: 100 mm
- Standards Met: ANSI



8471135 K

**RS PRO TYPE K THERMOCOUPLE 1M
LENGTH, 1MM DIAMETER → +1100°C**

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1 mm
- Probe Length: 1 m
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +1100 °C
- Termination Type: Cable
- Cable Length: 100 mm
- Standards Met: ANSI



8471129 K

**RS PRO TYPE K THERMOCOUPLE
250MM LENGTH, 1.5MM DIAMETER →**

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1.5 mm
- Probe Length: 250 mm
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +1100 °C
- Termination Type: Cable
- Cable Length: 100 mm
- Standards Met: ANSI



8471141 K

**RS PRO TYPE K THERMOCOUPLE 1M
LENGTH, 1.5MM DIAMETER → +1100°C**

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1.5 mm
- Probe Length: 1 m
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +1100 °C
- Termination Type: Cable
- Cable Length: 100 mm
- Standards Met: ANSI



8471138 K

**RS PRO TYPE K THERMOCOUPLE 2M
LENGTH, 3MM DIAMETER → +1100°C**

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 3 mm
- Probe Length: 2 m
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +1100 °C
- Termination Type: Cable
- Cable Length: 100 mm
- Standards Met: ANSI



8471150 K

**RS PRO TYPE K THERMOCOUPLE
250MM LENGTH, 3MM DIAMETER →**

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 3 mm
- Probe Length: 250 mm
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +1100 °C
- Termination Type: Cable
- Cable Length: 100 mm
- Standards Met: ANSI



8471154 K

**RS PRO TYPE K THERMOCOUPLE
500MM LENGTH, 1.5MM DIAMETER →**

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1.5 mm
- Probe Length: 500 mm
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +1100 °C
- Termination Type: Cable
- Cable Length: 100 mm
- Standards Met: ANSI



8471144 K

**ANSI K THERMOCOUPLE EXPOSED
JUNCTION 2M**

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1/0.2 mm
- Probe Length: 2 m
- Maximum Temperature Sensed: +250 °C
- Termination Type: Cable
- Cable Length: 2 m
- Standards Met: ANSI



8479665 K

**ANSI K THERMOCOUPLE EXPOSED
JUNCTION 1M**

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1/0.2 mm
- Probe Length: 1 m
- Maximum Temperature Sensed: +250 °C
- Termination Type: Cable
- Cable Length: 1 m
- Standards Met: ANSI



8479669 K

RS PRO TYPE K THERMOCOUPLE 2M LENGTH, 1/0.3MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1/0.3 mm
- Probe Length: 2 m
- Maximum Temperature Sensed: +250 °C
- Termination Type: Cable
- Cable Length: 2 m
- Standards Met: ANSI



8479671 K

RS PRO TYPE K THERMOCOUPLE 150MM LENGTH, 3MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 3 mm
- Probe Length: 150 mm
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +1100 °C
- Termination Type: Cable
- Cable Length: 100 mm
- Standards Met: ANSI



8471157 K

RS PRO TYPE K THERMOCOUPLE 1M LENGTH, 1/0.3MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1/0.3 mm
- Probe Length: 1 m
- Maximum Temperature Sensed: +250 °C
- Termination Type: Cable
- Cable Length: 1 m
- Standards Met: ANSI



8479675 K

RS PRO TYPE K THERMOCOUPLE 1M LENGTH, → +250°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Length: 1 m
- Maximum Temperature Sensed: +250 °C
- Termination Type: Cable
- Cable Length: 1 m
- Standards Met: ANSI



8479678 K

RS PRO TYPE T THERMOCOUPLE 1M LENGTH, 1/0.3MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: T
- Probe Diameter: 1/0.3 mm
- Probe Length: 1 m
- Maximum Temperature Sensed: +250 °C
- Termination Type: Cable
- Cable Length: 1 m
- Standards Met: ANSI



8479681 T

RS PRO TYPE K THERMOCOUPLE 2M LENGTH, 1/0.3MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1/0.3 mm
- Probe Length: 2 m
- Maximum Temperature Sensed: +250 °C
- Termination Type: Cable
- Cable Length: 2 m
- Standards Met: ANSI



8479684 K

ANSI T THERMOCOUPLE EXPOSED JUNCTION 2M

Pack size: **1 x EA**

- Thermocouple Type: T
- Probe Diameter: 1/0.3 mm
- Probe Length: 2 m
- Maximum Temperature Sensed: +250 °C
- Termination Type: Cable
- Cable Length: 2 m
- Standards Met: ANSI



8479687 T

RS PRO TYPE K THERMOCOUPLE 1M LENGTH, → +250°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Length: 1 m
- Maximum Temperature Sensed: +250 °C
- Termination Type: Cable
- Cable Length: 1 m
- Standards Met: ANSI



8479690 K

RS PRO TYPE K THERMOCOUPLE 2M LENGTH, 7/0.2MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 7/0.2 mm
- Probe Length: 2 m
- Maximum Temperature Sensed: +250 °C
- Termination Type: Cable
- Cable Length: 2 m
- Standards Met: ANSI



8479693 K

RS PRO TYPE K THERMOCOUPLE 1/0.2MM DIAMETER → +250°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1/0.2 mm
- Maximum Temperature Sensed: +250 °C
- Termination Type: Cable
- Cable Length: 5 m
- Standards Met: ANSI



8479697 K

RS PRO TYPE K THERMOCOUPLE 5M LENGTH, 1/0.3MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1/0.3 mm
- Probe Length: 5 m
- Maximum Temperature Sensed: +250 °C
- Termination Type: Cable
- Cable Length: 5 m
- Standards Met: ANSI



8479700 K

RS PRO TYPE T THERMOCOUPLE 1/0.3MM DIAMETER → +250°C

Pack size: **1 x EA**

- Thermocouple Type: T
- Probe Diameter: 1/0.3 mm
- Maximum Temperature Sensed: +250 °C
- Termination Type: Cable
- Cable Length: 5 m
- Standards Met: ANSI



8479704 T

RS PRO TYPE K THERMOCOUPLE 5M LENGTH, 1/0.3MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1/0.3 mm
- Probe Length: 5 m
- Maximum Temperature Sensed: +250 °C
- Termination Type: Cable
- Cable Length: 5 m
- Standards Met: ANSI



8479707 K

RS PRO TYPE K THERMOCOUPLE 5M LENGTH, 1/0.3MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1/0.3 mm
- Probe Length: 5 m
- Maximum Temperature Sensed: +250 °C
- Termination Type: Miniature Plug
- Cable Length: 5 m
- Standards Met: ANSI



8479710 K

RS PRO TYPE K THERMOCOUPLE 5M LENGTH, → +250°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Length: 5 m
- Maximum Temperature Sensed: +250 °C
- Termination Type: Cable
- Cable Length: 5 m
- Standards Met: ANSI



8479713 K

RS PRO TYPE K THERMOCOUPLE 5M LENGTH, 1/0.2MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1/0.2 mm
- Probe Length: 5 m
- Maximum Temperature Sensed: +250 °C
- Termination Type: Miniature Plug
- Cable Length: 5 m
- Standards Met: ANSI



8479716 K

RS PRO TYPE T THERMOCOUPLE 5M LENGTH, → +250°C

Pack size: **1 x EA**

- Thermocouple Type: T
- Probe Length: 5 m
- Maximum Temperature Sensed: +250 °C
- Termination Type: Miniature Plug
- Cable Length: 5 m
- Standards Met: ANSI



8479722 T

RS PRO TYPE K THERMOCOUPLE 5M LENGTH, 7/0.2MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 7/0.2 mm
- Probe Length: 5 m
- Maximum Temperature Sensed: +250 °C
- Termination Type: Miniature Plug
- Cable Length: 5 m
- Standards Met: ANSI



8479726 K

RS PRO TYPE K THERMOCOUPLE 5M LENGTH, 1/0.3MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1/0.3 mm
- Probe Length: 5 m
- Maximum Temperature Sensed: +250 °C
- Termination Type: Miniature Plug
- Cable Length: 5 m
- Standards Met: ANSI



8479729 K

RS PRO TYPE K THERMOCOUPLE 10M LENGTH, 1/0.3MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1/0.3 mm
- Probe Length: 10 m
- Maximum Temperature Sensed: +250 °C
- Termination Type: Cable
- Cable Length: 10 m
- Standards Met: ANSI



8479732 K

RS PRO TYPE K THERMOCOUPLE 10M LENGTH, 1/0.2MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1/0.2 mm
- Probe Length: 10 m
- Maximum Temperature Sensed: +250 °C
- Termination Type: Cable
- Cable Length: 10 m
- Standards Met: ANSI



8479735 K

RS PRO TYPE K THERMOCOUPLE 10M LENGTH, → +250°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Length: 10 m
- Maximum Temperature Sensed: +250 °C
- Termination Type: Cable
- Cable Length: 10 m
- Standards Met: ANSI



8479738 K

RS PRO TYPE T THERMOCOUPLE 10M LENGTH, → +250°C

Pack size: **1 x EA**

- Thermocouple Type: T
- Probe Length: 10 m
- Maximum Temperature Sensed: +250 °C
- Termination Type: Cable
- Cable Length: 10 m
- Standards Met: ANSI



8479741 T

RS PRO TYPE K THERMOCOUPLE 10M LENGTH, 7/0.2MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 7/0.2 mm
- Probe Length: 10 m
- Maximum Temperature Sensed: +250 °C
- Termination Type: Cable
- Cable Length: 10 m
- Standards Met: ANSI



8479744 K

RS PRO TYPE K THERMOCOUPLE 10M LENGTH, → +250°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Length: 10 m
- Maximum Temperature Sensed: +250 °C
- Termination Type: Miniature Plug
- Cable Length: 10 m
- Standards Met: ANSI



8479748 K

RS PRO TYPE K THERMOCOUPLE 10M LENGTH, 1/0.3MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1/0.3 mm
- Probe Length: 10 m
- Maximum Temperature Sensed: +350 °C
- Termination Type: Miniature Plug
- Cable Length: 10 m
- Standards Met: ANSI



8479750 K

RS PRO TYPE T THERMOCOUPLE 10M LENGTH, → +250°C

Pack size: **1 x EA**

- Thermocouple Type: T
- Probe Length: 10 m
- Maximum Temperature Sensed: +250 °C
- Termination Type: Miniature Plug
- Cable Length: 10 m
- Standards Met: ANSI



8479754 T

RS PRO TYPE K THERMOCOUPLE 10M LENGTH, → +250°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Length: 10 m
- Maximum Temperature Sensed: +250 °C
- Termination Type: Miniature Plug
- Cable Length: 10 m
- Standards Met: ANSI



8479757 K

TYPE K THERMOCOUPLE 2M BRAIDED CABLE

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 3.18 mm
- Probe Length: 25 mm
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +350 °C
- Termination Type: Cable
- Cable Length: 2 m
- Standards Met: IEC



8722503 K

RS PRO TYPE K THERMOCOUPLE 10M LENGTH, → +250°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Length: 10 m
- Maximum Temperature Sensed: +250 °C
- Termination Type: Miniature Plug
- Cable Length: 10 m
- Standards Met: ANSI



8479763 K

TYPE K THERMOCOUPLE 2M BRAIDED CABLE

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 3.18 mm
- Probe Length: 13 mm
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +350 °C
- Termination Type: Cable
- Cable Length: 2 m
- Standards Met: IEC



8722509 K

RS PRO TYPE K THERMOCOUPLE 40MM LENGTH, 3.18MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 3.18 mm
- Probe Length: 40 mm
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +350 °C
- Termination Type: Cable
- Cable Length: 2 m
- Standards Met: IEC



8722512 K

RS PRO TYPE J THERMOCOUPLE 25MM LENGTH, 4MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: J
- Probe Diameter: 4 mm
- Probe Length: 25 mm
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +350 °C
- Termination Type: Cable
- Cable Length: 2 m
- Standards Met: IEC



8722519 J

RS PRO TYPE K THERMOCOUPLE 13MM LENGTH, 4MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 4 mm
- Probe Length: 13 mm
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +350 °C
- Termination Type: Cable
- Cable Length: 2 m
- Standards Met: IEC



8722521 K

TYPE K THERMOCOUPLE 2M BRAIDED CABLE

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 4 mm
- Probe Length: 25 mm
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +350 °C
- Termination Type: Cable
- Cable Length: 2 m
- Standards Met: IEC



8722525 K

TYPE J THERMOCOUPLE 2M BRAIDED CABLE

Pack size: **1 x EA**

- Thermocouple Type: J
- Probe Diameter: 4 mm
- Probe Length: 40 mm
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +350 °C
- Termination Type: Cable
- Cable Length: 2 m
- Standards Met: IEC



8722528 J

TYPE K THERMOCOUPLE 2M BRAIDED CABLE

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 4 mm
- Probe Length: 40 mm
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +350 °C
- Termination Type: Cable
- Cable Length: 2 m
- Standards Met: IEC



8722534 K

RS PRO TYPE J THERMOCOUPLE 40MM LENGTH, 4.76MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: J
- Probe Diameter: 4.76 mm
- Probe Length: 40 mm
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +350 °C
- Termination Type: Cable
- Cable Length: 2 m
- Standards Met: IEC



8722540 J

RS PRO TYPE J THERMOCOUPLE 75MM LENGTH, 4.76MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: J
- Probe Diameter: 4.76 mm
- Probe Length: 75 mm
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +350 °C
- Termination Type: Cable
- Cable Length: 2 m
- Standards Met: IEC



8722543 J

RS PRO TYPE J THERMOCOUPLE 100MM LENGTH, 4.76MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: J
- Probe Diameter: 4.76 mm
- Probe Length: 100 mm
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +350 °C
- Termination Type: Cable
- Cable Length: 2 m
- Standards Met: IEC



8722547 J

RS PRO TYPE K THERMOCOUPLE 40MM LENGTH, 4.76MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 4.76 mm
- Probe Length: 40 mm
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +350 °C
- Termination Type: Cable
- Cable Length: 2 m
- Standards Met: IEC



8722553 K

RS PRO TYPE K THERMOCOUPLE 13MM LENGTH, 4.76MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 4.76 mm
- Probe Length: 13 mm
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +350 °C
- Termination Type: Cable
- Cable Length: 2 m
- Standards Met: IEC



8722556 K

RS PRO TYPE K THERMOCOUPLE 25MM LENGTH, 4.76MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 4.76 mm
- Probe Length: 25 mm
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +350 °C
- Termination Type: Cable
- Cable Length: 2 m
- Standards Met: IEC



8722559 K

RS PRO TYPE K THERMOCOUPLE 75MM LENGTH, 4.76MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 4.76 mm
- Probe Length: 75 mm
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +350 °C
- Termination Type: Cable
- Cable Length: 2 m
- Standards Met: IEC



8722562 K

RS PRO TYPE K THERMOCOUPLE 100MM LENGTH, 4.76MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 4.76 mm
- Probe Length: 100 mm
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +350 °C
- Termination Type: Cable
- Cable Length: 2 m
- Standards Met: IEC



8722565 K

RS PRO TYPE J THERMOCOUPLE 13MM LENGTH, M8 BOLT DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: J
- Probe Diameter: M8 Bolt
- Probe Length: 13 mm
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +250 °C
- Termination Type: Cable
- Cable Length: 2 m
- Standards Met: IEC



8722569 J

RS PRO TYPE J THERMOCOUPLE 25MM LENGTH, M8 BOLT DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: J
- Probe Diameter: M8 Bolt
- Probe Length: 25 mm
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +250 °C
- Termination Type: Cable
- Cable Length: 2 m
- Standards Met: IEC



8722578 J

RS PRO TYPE K THERMOCOUPLE 13MM LENGTH, M8 BOLT DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: M8 Bolt
- Probe Length: 13 mm
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +250 °C
- Termination Type: Cable
- Cable Length: 2 m
- Standards Met: IEC



8722581 K

RS PRO TYPE J THERMOCOUPLE 25MM LENGTH, M12 BOLT DIAMETER

Pack size: **1 x EA**

- Thermocouple Type: J
- Probe Diameter: M12 Bolt
- Probe Length: 25 mm
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +250 °C
- Termination Type: Cable
- Cable Length: 2 m
- Standards Met: IEC



8722587 J

RS PRO TYPE K THERMOCOUPLE 25MM LENGTH, M8 DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: M8
- Probe Length: 25 mm
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +250 °C
- Termination Type: Cable
- Cable Length: 2 m
- Standards Met: IEC



8722590 K

RS PRO TYPE K THERMOCOUPLE 13MM LENGTH, M10 DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: M10
- Probe Length: 13 mm
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +250 °C
- Termination Type: Cable
- Cable Length: 2 m
- Standards Met: IEC



8722593 K

RS PRO TYPE K THERMOCOUPLE 25MM LENGTH, M10 DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: M10
- Probe Length: 25 mm
- Probe Material: Stainless Steel
- Maximum Temperature Sensed: +250 °C
- Termination Type: Cable
- Cable Length: 2 m
- Standards Met: IEC



8722597 K

RS PRO TYPE K THERMOCOUPLE 13MM LENGTH, M12 BOLT DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: M12 Bolt
- Probe Length: 13 mm
- Maximum Temperature Sensed: +250 °C
- Probe Material: Stainless Steel
- Termination Type: Cable
- Cable Length: 2 m
- Standards Met: IEC



8722607 K

RS PRO TYPE K THERMOCOUPLE 2M LENGTH, 1/0.508MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1/0.508 mm
- Probe Length: 2 m
- Probe Material: Glass Fibre
- Maximum Temperature Sensed: +350 °C
- Termination Type: Miniature Plug
- Cable Length: 2 m
- Standards Met: IEC



8722604 K

IEC G/F THERMOCOUPLE, MINI PLUG, K, 10M

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1/0.3 mm
- Probe Length: 10 m
- Probe Material: Glass Fibre
- Maximum Temperature Sensed: +350 °C
- Termination Type: Miniature Plug
- Cable Length: 10 m
- Standards Met: IEC



8722610 K

RS PRO TYPE K THERMOCOUPLE 1/0.508MM DIAMETER → +350°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1/0.508 mm
- Maximum Temperature Sensed: +350 °C
- Probe Material: Glass Fibre
- Termination Type: Miniature Plug
- Cable Length: 5 m
- Standards Met: IEC



8722613 K

RS PRO TYPE J THERMOCOUPLE 10M LENGTH, 1/0.3MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: J
- Probe Diameter: 1/0.3 mm
- Probe Length: 10 m
- Probe Material: Glass Fibre
- Maximum Temperature Sensed: +350 °C
- Termination Type: Miniature Plug
- Cable Length: 10 m
- Standards Met: IEC



8722626 J

IEC G/F THERMOCOUPLE, MINI PLUG, K, 1M

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1/0.3 mm
- Maximum Temperature Sensed: +350 °C
- Probe Material: Glass Fibre
- Termination Type: Miniature Plug
- Cable Length: 1 m
- Standards Met: IEC



8722616 K

RS PRO TYPE J THERMOCOUPLE 5M LENGTH, → +350°C

Pack size: **1 x EA**

- Thermocouple Type: J
- Probe Length: 5 m
- Maximum Temperature Sensed: +350 °C
- Probe Material: Glass Fibre
- Termination Type: Miniature Plug
- Cable Length: 5 m
- Standards Met: IEC



8722622 J

RS PRO TYPE J THERMOCOUPLE 1M LENGTH, → +350°C

Pack size: **1 x EA**

- Thermocouple Type: J
- Probe Length: 1 m
- Maximum Temperature Sensed: +350 °C
- Probe Material: Glass Fibre
- Termination Type: Miniature Plug
- Cable Length: 1 m
- Standards Met: IEC



8722629 J

RS PRO TYPE K THERMOCOUPLE 1/0.376MM DIAMETER → +250°C

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1/0.376 mm
- Maximum Temperature Sensed: +250 °C
- Termination Type: Miniature Plug
- Cable Length: 2 m
- Standards Met: IEC



8722638 K

TYPE T THERMOCOUPLE + PLUG, 1M

Pack size: **1 x EA**

- Thermocouple Type: T
- Probe Length: 1 m
- Maximum Temperature Sensed: +250 °C
- Termination Type: Miniature Plug
- Cable Length: 1 m
- Standards Met: IEC



8722644 T

RS PRO TYPE T THERMOCOUPLE 2M LENGTH, → +250°C

Pack size: **1 x EA**

- Thermocouple Type: T
- Probe Length: 2 m
- Maximum Temperature Sensed: +250 °C
- Termination Type: Miniature Plug
- Cable Length: 2 m
- Standards Met: IEC



8722648 T

RS PRO TYPE T THERMOCOUPLE 10M LENGTH, → +250°C

Pack size: **1 x EA**

- Thermocouple Type: T
- Probe Length: 10 m
- Maximum Temperature Sensed: +250 °C
- Termination Type: Miniature Plug
- Cable Length: 10 m
- Standards Met: IEC



8722650 T

RS PRO TYPE T THERMOCOUPLE 5M LENGTH, → +250°C

Pack size: **1 x EA**

- Thermocouple Type: T
- Probe Length: 5 m
- Maximum Temperature Sensed: +250 °C
- Termination Type: Miniature Plug
- Cable Length: 5 m
- Standards Met: IEC



8722657 T

TYPE K THERMOCOUPLE + PLUG & SOCKET

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1.5 mm
- Probe Length: 300 mm
- Maximum Temperature Sensed: +1100 °C
- Probe Material: Stainless Steel
- Termination Type: Miniature Plug
- Standards Met: IEC



8722660 K

TYPE K THERMOCOUPLE + PLUG & SOCKET

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1 mm
- Probe Length: 300 mm
- Maximum Temperature Sensed: +750 °C
- Probe Material: Stainless Steel
- Termination Type: Miniature Plug
- Standards Met: IEC



8722663 K

TYPE K THERMOCOUPLE + PLUG & SOCKET

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 3 mm
- Probe Length: 150 mm
- Maximum Temperature Sensed: +1100 °C
- Probe Material: Stainless Steel
- Termination Type: Miniature Plug
- Standards Met: IEC



8722679 K

TYPE K THERMOCOUPLE + PLUG

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 4.5 mm
- Probe Length: 750 mm
- Maximum Temperature Sensed: +1100 °C
- Probe Material: Stainless Steel
- Termination Type: Standard Plug
- Standards Met: IEC



8722682 K

TYPE K THERMOCOUPLE + PLUG

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 4.5 mm
- Probe Length: 300 mm
- Maximum Temperature Sensed: +1100 °C
- Probe Material: Stainless Steel
- Termination Type: Standard Plug
- Standards Met: IEC



8722685 K

RS PRO TYPE K THERMOCOUPLE 2M LENGTH, 1/0.508MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1/0.508 mm
- Probe Length: 2 m
- Probe Material: Glass Fibre
- Maximum Temperature Sensed: +350 °C
- Termination Type: Cable
- Cable Length: 2 m
- Standards Met: IEC



8722795 K

RS PRO TYPE K THERMOCOUPLE 5M LENGTH, 1/0.508MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 1/0.508 mm
- Probe Length: 5 m
- Probe Material: Glass Fibre
- Maximum Temperature Sensed: +350 °C
- Termination Type: Cable
- Cable Length: 5 m
- Standards Met: IEC



8722799 K

RS PRO TYPE J THERMOCOUPLE 13MM LENGTH, 3.18MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: J
- Probe Diameter: 3.18 mm
- Probe Length: 13 mm
- Probe Material: Glass Fibre
- Maximum Temperature Sensed: +350 °C
- Termination Type: Cable
- Cable Length: 2 m
- Standards Met: IEC



8722809 J

RS PRO TYPE J THERMOCOUPLE 25MM LENGTH, 3.18MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: J
- Probe Diameter: 3.18 mm
- Probe Length: 25 mm
- Probe Material: Glass Fibre
- Maximum Temperature Sensed: +350 °C
- Termination Type: Cable
- Cable Length: 2 m
- Standards Met: IEC



8722802 J

RS PRO TYPE J THERMOCOUPLE 40MM LENGTH, 3.18MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: J
- Probe Diameter: 3.18 mm
- Probe Length: 40 mm
- Probe Material: Glass Fibre
- Maximum Temperature Sensed: +350 °C
- Termination Type: Cable
- Cable Length: 2 m
- Standards Met: IEC



8722806 J

RS PRO TYPE T THERMOCOUPLE 500MM LENGTH, 1MM DIAMETER,

Pack size: **1 x EA**

- Thermocouple Type: T
- Probe Diameter: 1 mm
- Probe Length: 500 mm
- Maximum Temperature Sensed: +400 °C
- Termination Type: Miniature Plug
- Standards Met: IEC
- Minimum Temperature Sensed: -100 °C



8919078 T

IEC TYPE T THERMOCOUPLE 1.0X150MM

Pack size: **1 x EA**

- Thermocouple Type: T
- Probe Diameter: 1 mm
- Probe Length: 150 mm
- Probe Material: 316 Stainless Steel
- Maximum Temperature Sensed: +400 °C
- Termination Type: Cable
- Cable Length: 100 mm
- Standards Met: IEC



8919090 T

RS PRO TYPE T THERMOCOUPLE 1M LENGTH, 1.5MM DIAMETER, -100°C →

Pack size: **1 x EA**

- Thermocouple Type: T
- Probe Diameter: 1.5 mm
- Probe Length: 1 m
- Maximum Temperature Sensed: +400 °C
- Termination Type: Miniature Plug
- Standards Met: IEC
- Minimum Temperature Sensed: -100 °C



8919097 T

RS PRO TYPE T THERMOCOUPLE 150MM LENGTH, 3MM DIAMETER →

Pack size: **1 x EA**

- Thermocouple Type: T
- Probe Diameter: 3 mm
- Probe Length: 150 mm
- Probe Material: 316 Stainless Steel
- Maximum Temperature Sensed: +400 °C
- Termination Type: Cable
- Cable Length: 100 mm
- Standards Met: IEC



8919126 T

THERMOCOUPLE 6X250 SLIDING FITTING

Pack size: **1 x EA**

- Thermocouple Type: K
- Probe Diameter: 6 mm
- Probe Length: 250 mm
- Maximum Temperature Sensed: +1000 °C
- Probe Material: Stainless Steel
- Termination Type: Connection Head
- Standards Met: RoHS Compliant
- Response Time: <2 s



8968409 K

RS PRO TYPE T THERMOCOUPLE
250MM LENGTH, 1.5MM DIAMETER →

- Pack size: **1 x EA**
- Thermocouple Type: T
 - Probe Diameter: 1.5 mm
 - Probe Length: 250 mm
 - Probe Material: 316 Stainless Steel
 - Maximum Temperature Sensed: +400 °C
 - Termination Type: Cable
 - Cable Length: 100 mm
 - Standards Met: IEC



8919110 T

RS PRO TYPE T THERMOCOUPLE
500MM LENGTH, 1.5MM DIAMETER →

- Pack size: **1 x EA**
- Thermocouple Type: T
 - Probe Diameter: 1.5 mm
 - Probe Length: 500 mm
 - Probe Material: 316 Stainless Steel
 - Maximum Temperature Sensed: +400 °C
 - Termination Type: Cable
 - Cable Length: 100 mm
 - Standards Met: IEC



8919113 T

SENSOR,PIEZO,CERAMIC,BI-MORPH,VIBRATION

- Pack size: **5 x EA**
- Switching Frequency: 100 Hz
 - Length: 15 mm
 - Width: 1.5 mm
 - Depth: 0.6 mm
 - Minimum Operating Temperature: -15 °C
 - Maximum Operating Temperature: +55 °C
 - Dimensions: 15 x 1.5 x 0.6 mm



285784 100 Hz

METER, PANEL, ANALOGUE, EDGE INDICATING, 100-0-100UA, NULL

Pack size: **1 x EA**

- Maximum Value: 100 μ A
- Cutout Width: 50 mm
- Depth: 14 mm
- Meter Accuracy: ± 20 %
- Minimum Temperature: -10 °C
- Maximum Temperature: +55 °C
- Approvals: RoHS Compliant
- Series: RS PRO



259549 100 μ A

METER, PANEL, ANALOGUE, EDGE INDICATING, 0-100UA, SCALE 0-10

Pack size: **1 x EA**

- Maximum Value: 100 μ A
- Cutout Width: 50 mm
- Depth: 14 mm
- Meter Accuracy: ± 20 %
- Minimum Temperature: -10 °C
- Maximum Temperature: +55 °C
- Approvals: RoHS Compliant
- Series: RS PRO



259561 100 μ A

RS PRO DIGITAL PANEL AMMETER, 90MM X 90MM

Pack size: **1 x EA**

- Cutout Height: 90 mm
- Cutout Width: 90 mm
- Depth: 55 mm
- Meter Accuracy: Class 1.0



1797573 90 mm

RS PRO DIGITAL AMMETER AC, 43.5MM X 92MM, $\pm 0.5\%$ + 1 DIGIT

Pack size: **1 x EA**

- Current Type: AC
- Cutout Height: 43.5 mm
- Cutout Width: 92 mm
- Depth: 68 mm
- Meter Accuracy: $\pm 0.5\%$ + 1 Digit
- Minimum Temperature: 0 °C
- Maximum Temperature: +50 °C
- Measurement Range: 1 $\rightarrow$ 5 (Input) A



1365390 AC

RS PRO DIGITAL AMMETER AC, 43.5MM X 92MM, $\pm 0.5\%$ + 1 DIGIT

Pack size: **1 x EA**

- Current Type: AC
- Cutout Height: 43.5 mm
- Cutout Width: 92 mm
- Depth: 68 mm
- Meter Accuracy: $\pm 0.5\%$ + 1 Digit
- Minimum Temperature: 0 °C
- Maximum Temperature: +50 °C
- Measurement Range: 1 $\rightarrow$ 5 (Input) A



1365385 AC

RS PRO DIGITAL AMMETER AC, 92MM X 92MM, $\pm 0.5\%$ + 1 DIGIT

Pack size: **1 x EA**

- Current Type: AC
- Cutout Height: 92 mm
- Cutout Width: 92 mm
- Depth: 55 mm
- Meter Accuracy: $\pm 0.5\%$ + 1 Digit
- Minimum Temperature: 0 °C
- Maximum Temperature: +50 °C
- Measurement Range: 1 $\rightarrow$ 5 (Input) A



1365387 AC

RS PRO ANALOGUE PANEL AMMETER 5 (INPUT, SCALE)A AC, 45MM X

Pack size: **1 x EA**

- Maximum Value: 5 (Input, Scale) A
- Current Type: AC
- Moving Element: Moving Iron
- Cutout Height: 45 mm
- Cutout Width: 45 mm
- Depth: 54 (≤ 30 A) mm
- Meter Accuracy: 1 %
- Minimum Temperature: -10 °C



1862412 5 (Input, Scale) A

RS PRO DIGITAL AMMETER, 90MM X 90MM

Pack size: **1 x EA**

- Cutout Height: 90 mm
- Cutout Width: 90 mm
- Depth: 55 mm
- Meter Accuracy: Class 1.0



1797575 90 mm

RS PRO ANALOGUE PANEL AMMETER 25 (INPUT, SCALE)A AC, 45MM X

Pack size: **1 x EA**

- Maximum Value: 25 (Input, Scale) A
- Current Type: AC
- Moving Element: Moving Iron
- Cutout Height: 45 mm
- Cutout Width: 45 mm
- Depth: 54 (≤ 30 A) mm
- Meter Accuracy: 1 %
- Minimum Temperature: -10 °C



1862414 25 (Input, Scale)

RS PRO ANALOGUE PANEL AMMETER 40 (INPUT, SCALE)A AC, 45MM X

Pack size: **1 x EA**

- Maximum Value: 40 (Input, Scale) A
- Current Type: AC
- Moving Element: Moving Iron
- Cutout Height: 45 mm
- Cutout Width: 45 mm
- Depth: 54 (≤ 30 A) mm, 72 (30 $\rightarrow$ 60 A) mm
- Meter Accuracy: 1 %
- Minimum Temperature: -10 °C



1862416 40 (Input, Scale)

RS PRO ANALOGUE PANEL AMMETER 30 (INPUT, SCALE)A AC, 45MM X

Pack size: **1 x EA**

- Maximum Value: 30 (Input, Scale) A
- Current Type: AC
- Moving Element: Moving Iron
- Cutout Height: 45 mm
- Cutout Width: 45 mm
- Depth: 54 (≤ 30 A) mm, 72 (30 $\rightarrow$ 60 A) mm
- Meter Accuracy: 1 %
- Minimum Temperature: -10 °C



1862415 30 (Input, Scale)

RS PRO ANALOGUE PANEL AMMETER 10 (INPUT, SCALE)A AC, 45MM X

Pack size: **1 x EA**

- Maximum Value: 10 (Input, Scale) A
- Current Type: AC
- Moving Element: Moving Iron
- Cutout Height: 45 mm
- Cutout Width: 45 mm
- Depth: 54 (≤ 30 A) mm
- Meter Accuracy: 1 %
- Minimum Temperature: -10 °C



1862413 10 (Input, Scale)

RS PRO ANALOGUE PANEL AMMETER 10 (INPUT, SCALE)A AC, 45MM X

Pack size: **1 x EA**

- Maximum Value: 10 (Input, Scale) A
- Current Type: AC
- Moving Element: Moving Iron
- Cutout Height: 45 mm
- Cutout Width: 45 mm
- Depth: 54 (≤ 30 A) mm
- Meter Accuracy: 1 %
- Minimum Temperature: -10 °C



1862418 10 (Input, Scale)

RS PRO ANALOGUE PANEL AMMETER 3 (INPUT, SCALE)A AC, 45MM X

Pack size: **1 x EA**

- Maximum Value: 3 (Input, Scale) A
- Current Type: AC
- Moving Element: Moving Iron
- Cutout Height: 45 mm
- Cutout Width: 45 mm
- Depth: 54 (≤ 30 A) mm
- Meter Accuracy: 1 %
- Minimum Temperature: -10 °C



1862417 3 (Input, Scale) A

RS PRO ANALOGUE PANEL AMMETER 10 (INPUT) A, 100 (SCALE) A, 50/5 (CT)

Pack size: **1 x EA**

- Maximum Value: 10 (Input) A, 100 (Scale) A, 50/5 (CT) A
- Current Type: AC
- Moving Element: Moving Iron
- Cutout Height: 45 mm
- Cutout Width: 45 mm
- Depth: 54 (≤ 30 A) mm, 72 (30 $\rightarrow$ 60 A) mm
- Meter Accuracy: 1 %
- Minimum Temperature: -10 °C



1862419 10 (Input) A, 100

RS PRO ANALOGUE PANEL AMMETER 10 (INPUT) A, 100/5 (CT) A, 200

Pack size: **1 x EA**

- Maximum Value: 10 (Input) A, 100/5 (CT) A, 200 (Scale) A
- Current Type: AC
- Moving Element: Moving Iron
- Cutout Height: 45 mm
- Cutout Width: 45 mm
- Depth: 54 (≤ 30 A) mm, 72 (30 $\rightarrow$ 60 A) mm
- Meter Accuracy: 1 %
- Minimum Temperature: -10 °C



1862420 10 (Input) A,

RS PRO ANALOGUE PANEL AMMETER 10 (INPUT) A, 250/5 (CT) A, 500

Pack size: **1 x EA**

- Maximum Value: 10 (Input) A, 250/5 (CT) A, 500 (Scale) A
- Current Type: AC
- Moving Element: Moving Iron
- Cutout Height: 45 mm
- Cutout Width: 45 mm
- Depth: 54 (<30 A) mm, 72 (30 → 60 A) mm
- Meter Accuracy: 1 %
- Minimum Temperature: -10 °C



1862421 10 (Input) A,

RS PRO ANALOGUE PANEL AMMETER 30 (INPUT) A AC, 45MM X 45MM, 1 %

Pack size: **1 x EA**

- Maximum Value: 30 (Input) A
- Current Type: AC
- Moving Element: Moving Iron
- Cutout Height: 45 mm
- Cutout Width: 45 mm
- Depth: 54 (<30 A) mm, 72 (30 → 60 A) mm
- Meter Accuracy: 1 %
- Minimum Temperature: -10 °C



1862423 30 (Input) A

RS PRO ANALOGUE PANEL AMMETER 20 (INPUT) A AC, 45MM X 45MM, 1 %

Pack size: **1 x EA**

- Maximum Value: 20 (Input) A
- Current Type: AC
- Moving Element: Moving Iron
- Cutout Height: 45 mm
- Cutout Width: 45 mm
- Depth: 54 (<30 A) mm, 72 (30 → 60 A) mm
- Meter Accuracy: 1 %
- Minimum Temperature: -10 °C



1862422 20 (Input) A

RS PRO ANALOGUE PANEL AMMETER 50 (INPUT) A AC, 45MM X 45MM, 1 %

Pack size: **1 x EA**

- Maximum Value: 50 (Input) A
- Current Type: AC
- Moving Element: Moving Iron
- Cutout Height: 45 mm
- Cutout Width: 45 mm
- Depth: 54 (<30 A) mm, 72 (30 → 60 A) mm
- Meter Accuracy: 1 %
- Minimum Temperature: -10 °C



1862425 50 (Input) A

RS PRO ANALOGUE PANEL AMMETER 150 (SCALE) A, 150/5 (CT) A, 5 (INPUT)

Pack size: **1 x EA**

- Maximum Value: 150 (Scale) A, 150/5 (CT) A, 5 (Input) A
- Current Type: AC
- Moving Element: Moving Iron
- Cutout Height: 68 mm
- Cutout Width: 68 mm
- Depth: 54 (<30 A) mm, 62 (30 → 60 A) mm, 66 (100 A) mm
- Meter Accuracy: 1 %
- Minimum Temperature: -10 °C



1862436 150 (Scale) A,

RS PRO ANALOGUE PANEL AMMETER 200 (SCALE) A, 200/5 (CT) A, 5 (INPUT)

Pack size: **1 x EA**

- Maximum Value: 200 (Scale) A, 200/5 (CT) A, 5 (Input) A
- Current Type: AC
- Moving Element: Moving Iron
- Cutout Height: 68 mm
- Cutout Width: 68 mm
- Depth: 54 (<30 A) mm, 62 (30 → 60 A) mm, 66 (100 A) mm
- Meter Accuracy: 1 %
- Minimum Temperature: -10 °C



1862437 200 (Scale) A,

RS PRO ANALOGUE PANEL AMMETER 100 (SCALE) A, 100/5 (CT) A, 5 (INPUT)

Pack size: **1 x EA**

- Maximum Value: 100 (Scale) A, 100/5 (CT) A, 5 (Input) A
- Current Type: AC
- Moving Element: Moving Iron
- Cutout Height: 68 mm
- Cutout Width: 68 mm
- Depth: 54 (<30 A) mm, 62 (30 → 60 A) mm, 66 (100 A) mm
- Meter Accuracy: 1 %
- Minimum Temperature: -10 °C



1862435 100 (Scale) A,

RS PRO ANALOGUE PANEL AMMETER 10 (INPUT) A AC, 68MM X 68MM, 1 %

Pack size: **1 x EA**

- Maximum Value: 10 (Input) A
- Current Type: AC
- Moving Element: Moving Iron
- Cutout Height: 68 mm
- Cutout Width: 68 mm
- Depth: 54 (<30 A) mm, 62 (30 → 60 A) mm, 66 (100 A) mm
- Meter Accuracy: 1 %
- Minimum Temperature: -10 °C



1862438 10 (Input) A

RS PRO ANALOGUE PANEL AMMETER 25 (INPUT) A AC, 68MM X 68MM, 1 %

Pack size: **1 x EA**

- Maximum Value: 25 (Input) A
- Current Type: AC
- Moving Element: Moving Iron
- Cutout Height: 68 mm
- Cutout Width: 68 mm
- Depth: 54 (<30 A) mm
- Meter Accuracy: 1 %
- Minimum Temperature: -10 °C



1862439 25 (Input) A

RS PRO ANALOGUE PANEL AMMETER 60 (INPUT) A AC, 68MM X 68MM, 1 %

Pack size: **1 x EA**

- Maximum Value: 60 (Input) A
- Current Type: AC
- Moving Element: Moving Iron
- Cutout Height: 68 mm
- Cutout Width: 68 mm
- Depth: 54 (<30 A) mm, 62 (30 → 60 A) mm
- Meter Accuracy: 1 %
- Minimum Temperature: -10 °C



1862440 60 (Input) A

RS PRO ANALOGUE PANEL AMMETER 3 (INPUT) A AC, 68MM X 68MM, 1 %

Pack size: **1 x EA**

- Maximum Value: 3 (Input) A
- Current Type: AC
- Moving Element: Moving Iron
- Cutout Height: 68 mm
- Cutout Width: 68 mm
- Depth: 54 (<30 A) mm
- Meter Accuracy: 1 %
- Minimum Temperature: -10 °C



1862441 3 (Input) A

RS PRO ANALOGUE PANEL AMMETER 10 (INPUT) A, 100 (SCALE) A, 50/5 (CT)

Pack size: **1 x EA**

- Maximum Value: 10 (Input) A, 100 (Scale) A, 50/5 (CT) A
- Current Type: AC
- Moving Element: Moving Iron
- Cutout Height: 68 mm
- Cutout Width: 68 mm
- Depth: 54 (<30 A) mm, 62 (30 → 60 A) mm, 66 (100 A) mm
- Meter Accuracy: 1 %
- Minimum Temperature: -10 °C



1862443 10 (Input) A, 100

RS PRO ANALOGUE PANEL AMMETER 10 (INPUT) A, 100/5 (CT) A, 200

Pack size: **1 x EA**

- Maximum Value: 10 (Input) A, 100/5 (CT) A, 200 (Scale) A
- Current Type: AC
- Moving Element: Moving Iron
- Cutout Height: 68 mm
- Cutout Width: 68 mm
- Depth: 54 (<30 A) mm, 62 (30 → 60 A) mm, 66 (100 A) mm
- Meter Accuracy: 1 %
- Minimum Temperature: -10 °C



1862444 10 (Input) A,

RS PRO ANALOGUE PANEL AMMETER 10 (INPUT) A, 200/5 (CT) A, 400

Pack size: **1 x EA**

- Maximum Value: 10 (Input) A, 200/5 (CT) A, 400 (Scale) A
- Current Type: AC
- Moving Element: Moving Iron
- Cutout Height: 68 mm
- Cutout Width: 68 mm
- Depth: 54 (<30 A) mm, 62 (30 → 60 A) mm, 66 (100 A) mm
- Meter Accuracy: 1 %
- Minimum Temperature: -10 °C



1862445 10 (Input) A,

RS PRO ANALOGUE PANEL AMMETER 10 (INPUT) A, 250/5 (CT) A, 500

Pack size: **1 x EA**

- Maximum Value: 10 (Input) A, 250/5 (CT) A, 500 (Scale) A
- Current Type: AC
- Moving Element: Moving Iron
- Cutout Height: 68 mm
- Cutout Width: 68 mm
- Depth: 54 (<30 A) mm, 62 (30 → 60 A) mm, 66 (100 A) mm
- Meter Accuracy: 1 %
- Minimum Temperature: -10 °C



1862446 10 (Input) A,

RS PRO ANALOGUE PANEL AMMETER 20 (INPUT) A AC, 68MM X 68MM, 1 %

Pack size: **1 x EA**

- Maximum Value: 20 (Input) A
- Current Type: AC
- Moving Element: Moving Iron
- Cutout Height: 68 mm
- Cutout Width: 68 mm
- Depth: 54 (<30 A) mm
- Meter Accuracy: 1 %
- Minimum Temperature: -10 °C



1862447 20 (Input) A

**RS PRO ANALOGUE PANEL AMMETER
50 (INPUT)A AC, 68MM X 68MM, 1 %**Pack size: **1 x EA**

- Maximum Value: 50 (Input) A
- Current Type: AC
- Moving Element: Moving Iron
- Cutout Height: 68 mm
- Cutout Width: 68 mm
- Depth: 54 (<30 A) mm, 62 (30 → 60 A) mm
- Meter Accuracy: 1 %
- Minimum Temperature: -10 °C

**1862451** 50 (Input) A**RS PRO ANALOGUE PANEL AMMETER
80 (INPUT)A AC, 68MM X 68MM, 1 %**Pack size: **1 x EA**

- Maximum Value: 80 (Input) A
- Current Type: AC
- Moving Element: Moving Iron
- Cutout Height: 68 mm
- Cutout Width: 68 mm
- Depth: 54 (<30 A) mm, 62 (30 → 60 A) mm, 66 (100 A) mm
- Meter Accuracy: 1 %
- Minimum Temperature: -10 °C

**1862453** 80 (Input) A**RS PRO ANALOGUE PANEL AMMETER
5 (INPUT, SCALE)A AC, 92MM X 92MM X**Pack size: **1 x EA**

- Maximum Value: 5 (Input, Scale) A
- Current Type: AC
- Moving Element: Moving Iron
- Cutout Height: 92 mm
- Cutout Width: 92 mm
- Depth: 54 (<30 A) mm
- Meter Accuracy: 1 %
- Minimum Temperature: -10 °C

**1862458** 5 (Input, Scale) A**RS PRO ANALOGUE PANEL AMMETER
10 (INPUT)A AC, 92MM X 92MM, 1 %**Pack size: **1 x EA**

- Maximum Value: 10 (Input) A
- Current Type: AC
- Moving Element: Moving Iron
- Cutout Height: 92 mm
- Cutout Width: 92 mm
- Depth: 54 (<30 A) mm
- Meter Accuracy: 1 %
- Minimum Temperature: -10 °C

**1862459** 10 (Input) A**RS PRO ANALOGUE PANEL AMMETER
25 (INPUT)A AC, 92MM X 92MM, 1 %**Pack size: **1 x EA**

- Maximum Value: 25 (Input) A
- Current Type: AC
- Moving Element: Moving Iron
- Cutout Height: 92 mm
- Cutout Width: 92 mm
- Depth: 54 (<30 A) mm
- Meter Accuracy: 1 %
- Minimum Temperature: -10 °C

**1862460** 25 (Input) A**RS PRO ANALOGUE PANEL AMMETER
10 (INPUT, SCALE)A AC, 92MM X 92MM X**Pack size: **1 x EA**

- Maximum Value: 10 (Input, Scale) A
- Current Type: AC
- Moving Element: Moving Iron
- Cutout Height: 92 mm
- Cutout Width: 92 mm
- Depth: 54 (<30 A) mm
- Meter Accuracy: 1 %
- Minimum Temperature: -10 °C

**1862462** 10 (Input, Scale)**RS PRO ANALOGUE PANEL AMMETER
10 (INPUT)A, 100 (SCALE) A, 50/5 (CT)**Pack size: **1 x EA**

- Maximum Value: 10 (Input) A, 100 (Scale) A, 50/5 (CT) A
- Current Type: AC
- Moving Element: Moving Iron
- Cutout Height: 92 mm
- Cutout Width: 92 mm
- Depth: 54 (<30 A) mm, 62 (30 → 60 A) mm, 66 (100 A) mm
- Meter Accuracy: 1 %
- Minimum Temperature: -10 °C

**1862463** 10 (Input) A, 100**RS PRO ANALOGUE PANEL AMMETER
20 (INPUT)A AC, 92MM X 92MM, 1 %**Pack size: **1 x EA**

- Maximum Value: 20 (Input) A
- Current Type: AC
- Moving Element: Moving Iron
- Cutout Height: 92 mm
- Cutout Width: 92 mm
- Depth: 54 (<30 A) mm
- Meter Accuracy: 1 %
- Minimum Temperature: -10 °C

**1862464** 20 (Input) A**RS PRO ANALOGUE PANEL AMMETER
30 (INPUT)A AC, 92MM X 92MM, 1 %**Pack size: **1 x EA**

- Maximum Value: 30 (Input) A
- Current Type: AC
- Moving Element: Moving Iron
- Cutout Height: 92 mm
- Cutout Width: 92 mm
- Depth: 54 (<30 A) mm, 62 (30 → 60 A) mm
- Meter Accuracy: 1 %
- Minimum Temperature: -10 °C

**1862465** 30 (Input) A**RS PRO ANALOGUE PANEL AMMETER
40 (INPUT)A AC, 92MM X 92MM, 1 %**Pack size: **1 x EA**

- Maximum Value: 40 (Input) A
- Current Type: AC
- Moving Element: Moving Iron
- Cutout Height: 92 mm
- Cutout Width: 92 mm
- Depth: 54 (<30 A) mm, 62 (30 → 60 A) mm
- Meter Accuracy: 1 %
- Minimum Temperature: -10 °C

**1862466** 40 (Input) A**RS PRO ANALOGUE PANEL AMMETER
50 (INPUT)A AC, 92MM X 92MM, 1 %**Pack size: **1 x EA**

- Maximum Value: 50 (Input) A
- Current Type: AC
- Moving Element: Moving Iron
- Cutout Height: 92 mm
- Cutout Width: 92 mm
- Depth: 54 (<30 A) mm, 62 (30 → 60 A) mm
- Meter Accuracy: 1 %
- Minimum Temperature: -10 °C

**1862467** 50 (Input) A**RS PRO ANALOGUE PANEL AMMETER
20 (INPUT)MA DC, 45MM X 45MM, 1**Pack size: **1 x EA**

- Maximum Value: 20 (Input) mA
- Current Type: DC
- Moving Element: Moving Coil
- Cutout Height: 45 mm
- Cutout Width: 45 mm
- Depth: 54 (<30 A) mm
- Meter Accuracy: 1 %
- Minimum Temperature: -10 °C

**1862475** 20 (Input) mA**RS PRO ANALOGUE PANEL AMMETER
DC, 45MM X 45MM, 1 % MOVING**Pack size: **1 x EA**

- Current Type: DC
- Moving Element: Moving Coil
- Cutout Height: 45 mm
- Cutout Width: 45 mm
- Depth: 54 (<30 A) mm, 72 (30 → 60 A) mm
- Meter Accuracy: 1 %
- Minimum Temperature: -10 °C
- Maximum Temperature: +65 °C

**1862477** DC**RS PRO ANALOGUE PANEL AMMETER
DC, 45MM X 45MM, 1 % MOVING**Pack size: **1 x EA**

- Current Type: DC
- Moving Element: Moving Coil
- Cutout Height: 45 mm
- Cutout Width: 45 mm
- Depth: 54 (<30 A) mm, 72 (30 → 60 A) mm
- Meter Accuracy: 1 %
- Minimum Temperature: -10 °C
- Maximum Temperature: +65 °C

**1862478** DC**RS PRO ANALOGUE PANEL AMMETER
DC, 45MM X 45MM, 1 % MOVING**Pack size: **1 x EA**

- Current Type: DC
- Moving Element: Moving Coil
- Cutout Height: 45 mm
- Cutout Width: 45 mm
- Depth: 54 (<30 A) mm, 72 (30 → 60 A) mm
- Meter Accuracy: 1 %
- Minimum Temperature: -10 °C
- Maximum Temperature: +65 °C

**1862479** DC**RS PRO ANALOGUE PANEL AMMETER
DC, 45MM X 45MM, 1 % MOVING**Pack size: **1 x EA**

- Current Type: DC
- Moving Element: Moving Coil
- Cutout Height: 45 mm
- Cutout Width: 45 mm
- Depth: 54 (<30 A) mm, 72 (30 → 60 A) mm
- Meter Accuracy: 1 %
- Minimum Temperature: -10 °C
- Maximum Temperature: +65 °C

**1862483** DC

RS PRO ANALOGUE PANEL AMMETER DC, 45MM X 45MM, 1 % MOVING

Pack size: **1 x EA**

- Current Type: DC
- Moving Element: Moving Coil
- Cutout Height: 45 mm
- Cutout Width: 45 mm
- Depth: 54 (<30 A) mm, 72 (30 → 60 A) mm
- Meter Accuracy: 1 %
- Minimum Temperature: -10 °C
- Maximum Temperature: +65 °C



1862485 DC

RS PRO ANALOGUE PANEL AMMETER 1 (INPUT)MA DC, 68MM X 68MM, 1 %

Pack size: **1 x EA**

- Maximum Value: 1 (Input) mA
- Current Type: DC
- Moving Element: Moving Coil
- Cutout Height: 68 mm
- Cutout Width: 68 mm
- Depth: 54 (<4 A) mm
- Meter Accuracy: 1 %
- Minimum Temperature: -10 °C



1862487 1 (Input) mA

RS PRO ANALOGUE PANEL AMMETER 20 (INPUT)MA DC, 68MM X 68MM, 1

Pack size: **1 x EA**

- Maximum Value: 20 (Input) mA
- Current Type: DC
- Moving Element: Moving Coil
- Cutout Height: 68 mm
- Cutout Width: 68 mm
- Depth: 54 (<4 A) mm
- Meter Accuracy: 1 %
- Minimum Temperature: -10 °C



1862488 20 (Input) mA

RS PRO ANALOGUE PANEL AMMETER 20 (INPUT)MA DC, 68MM X 68MM, 1

Pack size: **1 x EA**

- Maximum Value: 20 (Input) mA
- Current Type: DC
- Moving Element: Moving Coil
- Cutout Height: 68 mm
- Cutout Width: 68 mm
- Depth: 54 (<4 A) mm
- Meter Accuracy: 1 %
- Minimum Temperature: -10 °C



1862489 20 (Input) mA

RS PRO ANALOGUE PANEL AMMETER 0/10A FOR SHUNT 75MV DC, 68MM X

Pack size: **1 x EA**

- Maximum Value: 0/10A For Shunt 75 mV
- Current Type: DC
- Moving Element: Moving Coil
- Cutout Height: 68 mm
- Cutout Width: 68 mm
- Depth: 54 (<4 A) mm, 67 (5 → 60 A) mm, 67 (60 → 100 A) mm
- Meter Accuracy: 1 %
- Minimum Temperature: -10 °C



1862490 0/10A For Shunt

RS PRO ANALOGUE PANEL AMMETER 0/30A FOR SHUNT 75MV DC, 68MM X

Pack size: **1 x EA**

- Maximum Value: 0/30A For Shunt 75 mV
- Current Type: DC
- Moving Element: Moving Coil
- Cutout Height: 68 mm
- Cutout Width: 68 mm
- Depth: 54 (<4 A) mm, 67 (5 → 60 A) mm, 67 (60 → 100 A) mm
- Meter Accuracy: 1 %
- Minimum Temperature: -10 °C



1862491 0/30A For Shunt

RS PRO ANALOGUE PANEL AMMETER 0/100A FOR SHUNT 75MV DC, 68MM

Pack size: **1 x EA**

- Maximum Value: 0/100A For Shunt 75 mV
- Current Type: DC
- Moving Element: Moving Coil
- Cutout Height: 68 mm
- Cutout Width: 68 mm
- Depth: 54 (<4 A) mm, 67 (5 → 60 A) mm, 67 (60 → 100 A) mm
- Meter Accuracy: 1 %
- Minimum Temperature: -10 °C



1862492 0/100A For Shunt

RS PRO ANALOGUE PANEL AMMETER 0/300A FOR SHUNT 75MV DC, 68MM

Pack size: **1 x EA**

- Maximum Value: 0/300A For Shunt 75 mV
- Current Type: DC
- Moving Element: Moving Coil
- Cutout Height: 68 mm
- Cutout Width: 68 mm
- Depth: 54 (<4 A) mm, 67 (5 → 60 A) mm, 67 (60 → 100 A) mm
- Meter Accuracy: 1 %
- Minimum Temperature: -10 °C



1862493 0/300A For Shunt

RS PRO ANALOGUE PANEL AMMETER DC, 68MM X 68MM, 1 % MOVING

Pack size: **1 x EA**

- Current Type: DC
- Moving Element: Moving Coil
- Cutout Height: 68 mm
- Cutout Width: 68 mm
- Depth: 54 (<4 A) mm, 67 (5 → 60 A) mm, 67 (60 → 100 A) mm
- Meter Accuracy: 1 %
- Minimum Temperature: -10 °C
- Maximum Temperature: +65 °C



1862496 DC

RS PRO ANALOGUE PANEL AMMETER 20 (INPUT)MA DC, 92MM X 92MM, 1 %

Pack size: **1 x EA**

- Maximum Value: 20 (Input) mA
- Current Type: DC
- Moving Element: Moving Coil
- Cutout Height: 92 mm
- Cutout Width: 92 mm
- Depth: 54 (<4 A) mm
- Meter Accuracy: 1 %
- Minimum Temperature: -10 °C



1862502 20 (Input) mA

RS PRO ANALOGUE PANEL AMMETER 0/10A FOR SHUNT 75MV DC, 92MM X

Pack size: **1 x EA**

- Maximum Value: 0/10A For Shunt 75 mV
- Current Type: DC
- Moving Element: Moving Coil
- Cutout Height: 92 mm
- Cutout Width: 92 mm
- Depth: 54 (<4 A) mm, 67 (5 → 60 A) mm, 67 (60 → 100 A) mm
- Meter Accuracy: 1 %
- Minimum Temperature: -10 °C



1862503 0/10A For Shunt

RS PRO ANALOGUE PANEL AMMETER 0/30A FOR SHUNT 75MV DC, 92MM X

Pack size: **1 x EA**

- Maximum Value: 0/30A For Shunt 75 mV
- Current Type: DC
- Moving Element: Moving Coil
- Cutout Height: 92 mm
- Cutout Width: 92 mm
- Depth: 54 (<4 A) mm, 67 (5 → 60 A) mm, 67 (60 → 100 A) mm
- Meter Accuracy: 1 %
- Minimum Temperature: -10 °C



1862504 0/30A For Shunt

RS PRO ANALOGUE PANEL AMMETER 0/300A FOR SHUNT 75MV DC, 92MM

Pack size: **1 x EA**

- Maximum Value: 0/300A For Shunt 75 mV
- Current Type: DC
- Moving Element: Moving Coil
- Cutout Height: 92 mm
- Cutout Width: 92 mm
- Depth: 54 (<4 A) mm, 67 (5 → 60 A) mm, 67 (60 → 100 A) mm
- Meter Accuracy: 1 %
- Minimum Temperature: -10 °C



1862506 0/300A For Shunt

RS PRO ANALOGUE PANEL AMMETER 0/100A FOR SHUNT 75MV DC, 92MM

Pack size: **1 x EA**

- Maximum Value: 0/100A For Shunt 75 mV
- Current Type: DC
- Moving Element: Moving Coil
- Cutout Height: 92 mm
- Cutout Width: 92 mm
- Depth: 54 (<4 A) mm, 67 (5 → 60 A) mm, 67 (60 → 100 A) mm
- Meter Accuracy: 1 %
- Minimum Temperature: -10 °C



1862505 0/100A For Shunt

RS PRO ANALOGUE PANEL AMMETER DC, 92MM X 92MM, 1 % MOVING

Pack size: **1 x EA**

- Current Type: DC
- Moving Element: Moving Coil
- Cutout Height: 92 mm
- Cutout Width: 92 mm
- Depth: 54 (<4 A) mm, 67 (5 → 60 A) mm, 67 (60 → 100 A) mm
- Meter Accuracy: 1 %
- Minimum Temperature: -10 °C
- Maximum Temperature: +65 °C



1862509 DC

RS PRO ANALOGUE PANEL AMMETER DC, 92MM X 92MM, 1 % MOVING

Pack size: **1 x EA**

- Current Type: DC
- Moving Element: Moving Coil
- Cutout Height: 92 mm
- Cutout Width: 92 mm
- Depth: 54 (<4 A) mm, 67 (5 → 60 A) mm, 67 (60 → 100 A) mm
- Meter Accuracy: 1 %
- Minimum Temperature: -10 °C
- Maximum Temperature: +65 °C



1862510 DC

**RS PRO ANALOGUE PANEL AMMETER
DC, 92MM X 92MM, 1 % MOVING**Pack size: **1 x EA**

- Current Type: DC
- Moving Element: Moving Coil
- Cutout Height: 92 mm
- Cutout Width: 92 mm
- Depth: 54 (<4 A) mm, 67 (5 → 60 A) mm, 67 (60 → 100 A) mm
- Meter Accuracy: 1 %
- Minimum Temperature: -10 °C
- Maximum Temperature: +65 °C

**1862511** DC**RS PRO ANALOGUE PANEL AMMETER
DC, 92MM X 92MM, 1 % MOVING**Pack size: **1 x EA**

- Current Type: DC
- Moving Element: Moving Coil
- Cutout Height: 92 mm
- Cutout Width: 92 mm
- Depth: 54 (<4 A) mm, 67 (5 → 60 A) mm, 67 (60 → 100 A) mm
- Meter Accuracy: 1 %
- Minimum Temperature: -10 °C
- Maximum Temperature: +65 °C

**1862513** DC**RS PRO ANALOGUE PANEL AMMETER
80 (INPUT)A AC, 76MM X 74MM, ±1.5**Pack size: **1 x EA**

- Maximum Value: 80 (Input) A
- Current Type: AC
- Cutout Height: 76 mm
- Cutout Width: 74 mm
- Depth: 45.7 mm
- Meter Accuracy: ±1.5 %
- Minimum Temperature: 0 °C
- Maximum Temperature: +60 °C

**1862517** 80 (Input) A**RS PRO ANALOGUE PANEL AMMETER 1
(INPUT)A DC, 76MM X 74MM, ±1.5 %**Pack size: **1 x EA**

- Maximum Value: 1 (Input) A
- Current Type: DC
- Moving Element: Moving Coil
- Cutout Height: 76 mm
- Cutout Width: 74 mm
- Depth: 45.7 mm
- Meter Accuracy: ±1.5 %
- Minimum Temperature: 0 °C

**1862527** 1 (Input) A**RS PRO ANALOGUE PANEL AMMETER
5 (INPUT)A DC, 76MM X 74MM, ±1.5 %**Pack size: **1 x EA**

- Maximum Value: 5 (Input) A
- Current Type: DC
- Moving Element: Moving Coil
- Cutout Height: 76 mm
- Cutout Width: 74 mm
- Depth: 45.7 mm
- Meter Accuracy: ±1.5 %
- Minimum Temperature: 0 °C

**1862528** 5 (Input) A**RS PRO ANALOGUE PANEL AMMETER
10 (INPUT)A DC, 76MM X 74MM, ±1.5**Pack size: **1 x EA**

- Maximum Value: 10 (Input) A
- Current Type: DC
- Moving Element: Moving Coil
- Cutout Height: 76 mm
- Cutout Width: 74 mm
- Depth: 45.7 mm
- Meter Accuracy: ±1.5 %
- Minimum Temperature: 0 °C

**1862529** 10 (Input) A**RS PRO ANALOGUE PANEL AMMETER
50 (INPUT)A DC, 76MM X 74MM, ±1.5**Pack size: **1 x EA**

- Maximum Value: 50 (Input) A
- Current Type: DC
- Moving Element: Moving Coil
- Cutout Height: 76 mm
- Cutout Width: 74 mm
- Depth: 45.7 mm
- Meter Accuracy: ±1.5 %
- Minimum Temperature: 0 °C

**1862530** 50 (Input) A**RS PRO ANALOGUE PANEL AMMETER
DC, 76MM X 74MM, ±1.5 % MOVING**Pack size: **1 x EA**

- Current Type: DC
- Moving Element: Moving Coil
- Cutout Height: 76 mm
- Cutout Width: 74 mm
- Depth: 45.7 mm
- Meter Accuracy: ±1.5 %
- Minimum Temperature: 0 °C
- Maximum Temperature: +60 °C

**1862531** DC**RS PRO ANALOGUE PANEL AMMETER
DC, 57MM X 44MM, ±1.5 % MOVING**Pack size: **1 x EA**

- Current Type: DC
- Moving Element: Moving Coil
- Cutout Height: 57 mm
- Cutout Width: 44 mm
- Depth: 45.7 mm
- Meter Accuracy: ±1.5 %
- Minimum Temperature: 0 °C
- Maximum Temperature: +60 °C

**1862533** DC**RS PRO ANALOGUE PANEL AMMETER
50 (INPUT)MA DC, 57MM X 44MM,**Pack size: **1 x EA**

- Maximum Value: 50 (Input) mA
- Current Type: DC
- Moving Element: Moving Coil
- Cutout Height: 57 mm
- Cutout Width: 44 mm
- Depth: 45.7 mm
- Meter Accuracy: ±1.5 %
- Minimum Temperature: 0 °C

**1862535** 50 (Input) mA**RS PRO ANALOGUE PANEL AMMETER
DC, 57MM X 44MM, ±1.5 % MOVING**Pack size: **1 x EA**

- Current Type: DC
- Moving Element: Moving Coil
- Cutout Height: 57 mm
- Cutout Width: 44 mm
- Depth: 45.7 mm
- Meter Accuracy: ±1.5 %
- Minimum Temperature: 0 °C
- Maximum Temperature: +60 °C

**1862534** DC**RS PRO ANALOGUE PANEL AMMETER
100 (INPUT)MA DC, 57MM X 44MM,**Pack size: **1 x EA**

- Maximum Value: 100 (Input) mA
- Current Type: DC
- Moving Element: Moving Coil
- Cutout Height: 57 mm
- Cutout Width: 44 mm
- Depth: 45.7 mm
- Meter Accuracy: ±1.5 %
- Minimum Temperature: 0 °C

**1862536** 100 (Input) mA**RS PRO DIGITAL AMMETER**Pack size: **1 x EA**

- Depth: 66 mm
- Minimum Temperature: -20 °C
- Maximum Temperature: +60 °C
- Measurement Range: 4 → 20 mA

**1883473** 66 mm**AC AMMETER 48X48 90 DEG 0-10/20A**Pack size: **1 x EA**

- Maximum Value: 10 A
- Current Type: AC
- Moving Element: Moving Iron
- Cutout Height: 46 mm
- Cutout Width: 46 mm
- Depth: 39 mm
- Meter Accuracy: ±1.5 %
- Minimum Temperature: -25 °C

**9010337** 10 A**AC AMMETER 48X48 90 DEG 0-
20/40A**Pack size: **1 x EA**

- Maximum Value: 20 A
- Current Type: AC
- Moving Element: Moving Iron
- Cutout Height: 46 mm
- Cutout Width: 46 mm
- Depth: 39 mm
- Meter Accuracy: ±1.5 %
- Minimum Temperature: -25 °C

**9010330** 20 A**RS PRO ANALOGUE PANEL AMMETER
5A AC, 68MM X 68MM, ±1.5 %**Pack size: **1 x EA**

- Maximum Value: 5 A
- Current Type: AC
- Moving Element: Moving Iron
- Cutout Height: 68 mm
- Cutout Width: 68 mm
- Depth: 36.5 mm
- Meter Accuracy: ±1.5 %
- Minimum Temperature: -25 °C

**9010343** 5 A

AC AMMETER 72X72 90 DEG 0-20/40A

Pack size: **1 x EA**

- Maximum Value: 40 A
- Current Type: AC
- Moving Element: Moving Iron
- Cutout Height: 68 mm
- Cutout Width: 68 mm
- Depth: 59 mm
- Meter Accuracy: $\pm 1.5\%$
- Minimum Temperature: $-25\text{ }^{\circ}\text{C}$



9010340 40 A

AC AMMETER 72X72 90 DEG 0-10/20A

Pack size: **1 x EA**

- Maximum Value: 10 A
- Current Type: AC
- Moving Element: Moving Iron
- Cutout Height: 68 mm
- Cutout Width: 68 mm
- Depth: 36.5 mm
- Meter Accuracy: $\pm 1.5\%$
- Minimum Temperature: $-25\text{ }^{\circ}\text{C}$



9010346 10 A

AC AMMETER 96X96 90 DEG 0-10/20A

Pack size: **1 x EA**

- Maximum Value: 10 A
- Current Type: AC
- Moving Element: Moving Iron
- Cutout Height: 92 mm
- Cutout Width: 92 mm
- Depth: 45 mm
- Meter Accuracy: $\pm 1.5\%$
- Minimum Temperature: $-25\text{ }^{\circ}\text{C}$



9010356 10 A

RS PRO ANALOGUE PANEL AMMETER 40A AC, 92MM X 92MM, $\pm 1.5\%$

Pack size: **1 x EA**

- Maximum Value: 40 A
- Current Type: AC
- Moving Element: Moving Iron
- Cutout Height: 92 mm
- Cutout Width: 92 mm
- Depth: 45 mm
- Meter Accuracy: $\pm 1.5\%$
- Minimum Temperature: $-25\text{ }^{\circ}\text{C}$



9010365 40 A

RS PRO ANALOGUE PANEL AMMETER 30A AC, 92MM X 92MM, $\pm 1.5\%$

Pack size: **1 x EA**

- Maximum Value: 30 A
- Current Type: AC
- Moving Element: Moving Iron
- Cutout Height: 92 mm
- Cutout Width: 92 mm
- Depth: 45 mm
- Meter Accuracy: $\pm 1.5\%$
- Minimum Temperature: $-25\text{ }^{\circ}\text{C}$



9010368 30 A

4 DIGIT HAND HELD TALLY COUNTER

Pack size: **1 x EA**

- Count Mode: Pulse
- Display Type: Mechanical
- Input Type: Manual
- Reset Method: Manual
- Number of Digits: 4
- Mounting Type: Surface Mount
- Count Direction: Up
- Digit Height: 4 mm



7105212 Pulse

4 DIGIT DESK MOUNTED TALLY COUNTER

Pack size: **1 x EA**

- Count Mode: Pulse
- Display Type: Mechanical
- Input Type: Manual
- Reset Method: Manual
- Number of Digits: 4
- Mounting Type: Surface Mount
- Count Direction: Up
- Digit Height: 4 mm



7105216 Pulse

AC AMMETER 72X72 90 DEG 0-30/60A

Pack size: **1 x EA**

- Maximum Value: 30 A
- Current Type: AC
- Moving Element: Moving Iron
- Cutout Height: 68 mm
- Cutout Width: 68 mm
- Depth: 36.5 mm
- Meter Accuracy: $\pm 1.5\%$
- Minimum Temperature: $-25\text{ }^{\circ}\text{C}$



9010359 30 A

5 DIGIT LHS SHAFT MECH STROKE COUNTER

Pack size: **1 x EA**

- Count Mode: Impulses
- Display Type: Mechanical
- Input Type: Manual
- Reset Method: Manual
- Number of Digits: 5
- Mounting Type: Screw Clamp
- Count Direction: Up
- Digit Height: 4.8 mm



7105219 Impulses

4 DIGIT BANK OF 4 TALLY COUNTER

Pack size: **1 x EA**

- Display Type: Mechanical
- Input Type: Manual
- Reset Method: Manual
- Number of Digits: 4
- Mounting Type: Surface Mount
- Count Direction: Up
- Digit Height: 4 mm
- Cutout Width: 1350 mm



7105225 Mechanical

5 DIGIT RHS SHAFT MECH STROKE COUNTER

Pack size: **1 x EA**

- Count Mode: Impulses
- Display Type: Mechanical
- Input Type: Manual
- Reset Method: Manual
- Number of Digits: 5
- Mounting Type: Screw Clamp
- Count Direction: Up
- Digit Height: 4.8 mm



7105228 Impulses

RS PRO COUNTER COUNTER, 6 DIGIT, 20KHZ, 24 V

Pack size: **1 x EA**

- Supply Voltage: 24 V
- Count Mode: Pulse
- Display Type: LED
- Input Type: Transistor
- Connection Type: Flying Lead
- Reset Method: Automatic, Manual
- Number of Digits: 6
- Mounting Type: Panel Mount



8086614 24 V

RS PRO COUNTER COUNTER, 6 DIGIT, 20KHZ, 230 V AC

Pack size: **1 x EA**

- Supply Voltage: 230 V ac
- Count Mode: Seconds
- Display Type: LED
- Input Type: Transistor
- Connection Type: Flying Lead
- Reset Method: Automatic, Manual
- Number of Digits: 6
- Mounting Type: Panel Mount



8086605 230 V ac

RS PRO COUNTER COUNTER, 6 DIGIT, 20KHZ, 230 V AC

Pack size: **1 x EA**

- Supply Voltage: 230 V ac
- Count Mode: Seconds
- Display Type: LED
- Input Type: Transistor
- Connection Type: Flying Lead
- Reset Method: Automatic, Manual
- Number of Digits: 6
- Mounting Type: Panel Mount



8086617 230 V ac

RS PRO COUNTER COUNTER, 6 DIGIT, 20KHZ, 24 V

Pack size: **1 x EA**

- Supply Voltage: 24 V
- Count Mode: Seconds
- Display Type: LED
- Input Type: Transistor
- Connection Type: Flying Lead
- Reset Method: Automatic, Manual
- Number of Digits: 6
- Mounting Type: Panel Mount



8086633 24 V

RS PRO COUNTER COUNTER, 6 DIGIT, 20KHZ, 230 V AC

Pack size: **1 x EA**

- Supply Voltage: 230 V ac
- Count Mode: Impulses
- Display Type: LED
- Input Type: Transistor
- Connection Type: Screw Clamp
- Reset Method: Automatic, Manual
- Number of Digits: 6
- Mounting Type: Panel Mount



8086627 230 V ac

RS PRO COUNTER COUNTER, 6 DIGIT, 20KHZ, 24 V

Pack size: **1 x EA**

- Supply Voltage: 24 V
- Count Mode: Impulses
- Display Type: LED
- Input Type: Transistor
- Connection Type: Flying Lead
- Reset Method: Automatic, Manual
- Number of Digits: 6
- Mounting Type: Panel Mount



8086636 24 V

RS PRO COUNTER COUNTER, 6 DIGIT, 20KHZ, 230 V AC

Pack size: **1 x EA**

- Supply Voltage: 230 V ac
- Count Mode: Seconds
- Display Type: LED
- Input Type: Transistor
- Connection Type: Flying Lead
- Reset Method: Automatic, Manual
- Number of Digits: 6
- Mounting Type: Panel Mount



8086639 230 V ac

RS PRO COUNTER, PROGRAMMABLE TIMER COUNTER, 6 DIGIT, 6KHZ, 100

Pack size: **1 x EA**

- Supply Voltage: 100 → 240 V ac
- Count Mode: Seconds
- Display Type: LED
- Input Type: NPN, PNP
- Connection Type: Terminal
- Reset Method: Automatic, Manual
- Number of Digits: 6
- Mounting Type: Panel Mount



8751309 100 → 240 V ac

RS PRO COUNTER, PROGRAMMABLE TIMER COUNTER, 6 DIGIT, 6KHZ, 24 V

Pack size: **1 x EA**

- Supply Voltage: 24 V ac/dc
- Count Mode: Seconds
- Display Type: LED
- Input Type: NPN, PNP
- Connection Type: Terminal
- Reset Method: Automatic, Manual
- Number of Digits: 6
- Mounting Type: Panel Mount



8751318 24 V ac/dc

RS PRO HOUR METER COUNTER, 6 DIGIT, 50HZ, 90 → 264 V AC

Pack size: **1 x EA**

- Supply Voltage: 90 → 264 V ac
- Count Mode: Hours
- Display Type: Analogue
- Input Type: Voltage
- Connection Type: Spade Terminal
- Reset Method: No Reset
- Number of Digits: 6
- Mounting Type: Panel Mount



8966894 90 → 264 V ac

RS PRO HOUR METER COUNTER, 6 DIGIT, 50HZ, 10 → 80 V DC

Pack size: **1 x EA**

- Supply Voltage: 10 → 80 V dc
- Count Mode: Hours
- Display Type: Analogue
- Input Type: Voltage
- Connection Type: Spade Terminal
- Reset Method: No Reset
- Number of Digits: 6
- Mounting Type: Panel Mount



8966898 10 → 80 V dc

RS PRO HOUR METER COUNTER, 6 DIGIT, 50HZ, 90 → 264 V AC

Pack size: **1 x EA**

- Supply Voltage: 90 → 264 V ac
- Count Mode: Hours
- Display Type: Analogue
- Input Type: Voltage
- Connection Type: Spade Terminal
- Reset Method: No Reset
- Number of Digits: 6
- Mounting Type: Panel Mount



8966905 90 → 264 V ac

RS PRO HOUR METER COUNTER, 6 DIGIT, 50HZ, 10 → 80 V DC

Pack size: **1 x EA**

- Supply Voltage: 10 → 80 V dc
- Count Mode: Hours
- Display Type: Analogue
- Input Type: Voltage
- Connection Type: Spade Terminal
- Reset Method: No Reset
- Number of Digits: 6
- Mounting Type: Panel Mount



8966911 10 → 80 V dc

RS PRO HOUR METER COUNTER, 6 DIGIT, 50HZ, 10 → 80 V DC

Pack size: **1 x EA**

- Supply Voltage: 10 → 80 V dc
- Count Mode: Hours
- Display Type: Analogue
- Input Type: Voltage
- Connection Type: Spade Terminal
- Reset Method: No Reset
- Number of Digits: 6
- Mounting Type: Panel Mount



8966914 10 → 80 V dc

RS PRO HOUR METER COUNTER, 6 DIGIT, 50HZ, 90 → 264 V AC

Pack size: **1 x EA**

- Supply Voltage: 90 → 264 V ac
- Count Mode: Hours
- Display Type: Analogue
- Input Type: Voltage
- Connection Type: Spade Terminal
- Reset Method: No Reset
- Number of Digits: 6
- Mounting Type: Panel Mount



8966917 90 → 264 V ac

RS PRO HOUR METER COUNTER, 6 DIGIT, 50HZ, 4 → 30 V AC/DC

Pack size: **1 x EA**

- Supply Voltage: 4 → 30 V ac/dc
- Count Mode: Hours
- Display Type: Analogue
- Input Type: Voltage
- Connection Type: Spade Terminal
- Reset Method: No Reset
- Number of Digits: 6
- Mounting Type: Panel Mount



8966920 4 → 30 V ac/dc

RS PRO HOUR METER COUNTER, 6 DIGIT, 50HZ, 4 → 30 V AC/DC

Pack size: **1 x EA**

- Supply Voltage: 4 → 30 V ac/dc
- Count Mode: Hours
- Display Type: Analogue
- Input Type: Voltage
- Connection Type: Spade Terminal
- Reset Method: No Reset
- Number of Digits: 6
- Mounting Type: Panel Mount



8966923 4 → 30 V ac/dc

RS PRO HOUR METER COUNTER, 6 DIGIT, 50HZ, 90 → 264 V AC

Pack size: **1 x EA**

- Supply Voltage: 90 → 264 V ac
- Count Mode: Hours
- Display Type: Analogue
- Input Type: Voltage
- Connection Type: Spade Terminal
- Reset Method: No Reset
- Number of Digits: 6
- Mounting Type: Panel Mount



8966927 90 → 264 V ac

RS PRO HOUR METER COUNTER, 6 DIGIT, 50HZ, 90 → 264 V AC

Pack size: **1 x EA**

- Supply Voltage: 90 → 264 V ac
- Count Mode: Hours
- Display Type: Analogue
- Input Type: Voltage
- Connection Type: Spade Terminal
- Reset Method: No Reset
- Number of Digits: 6
- Mounting Type: Panel Mount



8966933 90 → 264 V ac

RS PRO HOUR METER COUNTER, 6 DIGIT, 50HZ, 10 → 80 V DC

Pack size: **1 x EA**

- Supply Voltage: 10 → 80 V dc
- Count Mode: Hours
- Display Type: Analogue
- Input Type: Voltage
- Connection Type: Spade Terminal
- Reset Method: No Reset
- Number of Digits: 6
- Mounting Type: Panel Mount



8966936 10 → 80 V dc

RS PRO HOUR METER COUNTER, 6 DIGIT, 50HZ, 10 → 80 V DC

Pack size: **1 x EA**

- Supply Voltage: 10 → 80 V dc
- Count Mode: Hours
- Display Type: Analogue
- Input Type: Voltage
- Connection Type: Spade Terminal
- Reset Method: No Reset
- Number of Digits: 6
- Mounting Type: Panel Mount



8966939 10 → 80 V dc

RS PRO HOUR METER COUNTER, 6 DIGIT, 50HZ, 4 → 30 V AC/DC

Pack size: **1 x EA**

- Supply Voltage: 4 → 30 V ac/dc
- Count Mode: Hours
- Display Type: Analogue
- Input Type: Voltage
- Connection Type: Spade Terminal
- Reset Method: No Reset
- Number of Digits: 6
- Mounting Type: Panel Mount



8966942 4 → 30 V ac/dc

RS PRO HOUR METER COUNTER, 6 DIGIT, 50HZ, 270 → 460 V AC, 90 →

Pack size: **1 x EA**

- Supply Voltage: 270 → 460 V ac, 90 → 264 V ac
- Count Mode: Hours
- Display Type: Analogue
- Input Type: Voltage
- Connection Type: Spade Terminal
- Reset Method: No Reset
- Number of Digits: 6
- Mounting Type: DIN Rail



8966945 270 → 460 V ac,

RS PRO HOUR METER COUNTER, 6 DIGIT, 10 → 80 V DC

Pack size: **1 x EA**

- Supply Voltage: 10 → 80 V dc
- Count Mode: Hours
- Display Type: Analogue
- Input Type: Voltage
- Connection Type: Spade Terminal
- Reset Method: No Reset
- Number of Digits: 6
- Mounting Type: DIN Rail



8966949 10 → 80 V dc

RS PRO HOUR METER COUNTER, 6 DIGIT, 50HZ, 85 → 265 V AC

Pack size: **1 x EA**

- Supply Voltage: 85 → 265 V ac
- Count Mode: Hours
- Display Type: LCD
- Input Type: Voltage
- Connection Type: Screw
- Reset Method: Remote
- Number of Digits: 6
- Mounting Type: Flush Mount, Panel Mount



8966951 85 → 265 V ac

RS PRO HOUR METER COUNTER, 6 DIGIT, 50HZ, 12 → 48 V AC/DC

Pack size: **1 x EA**

- Supply Voltage: 12 → 48 V ac/dc
- Count Mode: Hours
- Display Type: LCD
- Input Type: Voltage
- Connection Type: Screw
- Reset Method: Remote
- Number of Digits: 6
- Mounting Type: Flush Mount, Panel Mount



8966955 12 → 48 V ac/dc

RS PRO HOUR METER COUNTER, 6 DIGIT, 110 V DC

Pack size: **1 x EA**

- Supply Voltage: 110 V dc
- Count Mode: Hours
- Display Type: Analogue
- Input Type: Voltage
- Connection Type: Spade Terminal
- Reset Method: No Reset
- Number of Digits: 6
- Mounting Type: DIN Rail



8966958 110 V dc

RS PRO HOUR METER COUNTER, 6 DIGIT, 50HZ, 12 → 48 V AC/DC

Pack size: **1 x EA**

- Supply Voltage: 12 → 48 V ac/dc
- Count Mode: Hours
- Display Type: LCD
- Input Type: Voltage
- Connection Type: Screw
- Reset Method: Remote
- Number of Digits: 6
- Mounting Type: Flush Mount, Panel Mount



8966961 12 → 48 V ac/dc

RS PRO HOUR METER COUNTER, 6 DIGIT, 10 → 80 V DC

Pack size: **1 x EA**

- Supply Voltage: 10 → 80 V dc
- Count Mode: Hours
- Display Type: LCD
- Input Type: Voltage
- Connection Type: Screw
- Reset Method: Remote
- Number of Digits: 6
- Mounting Type: Flush Mount, Panel Mount



8966964 10 → 80 V dc

RS PRO HOUR METER COUNTER, 6 DIGIT, 50HZ, 85 → 265 V AC

Pack size: **1 x EA**

- Supply Voltage: 85 → 265 V ac
- Count Mode: Hours
- Display Type: LCD
- Input Type: Voltage
- Connection Type: Screw
- Reset Method: Remote
- Number of Digits: 6
- Mounting Type: Flush Mount, Panel Mount



8966967 85 → 265 V ac

RS PRO HOUR METER COUNTER, 6 DIGIT, 10 → 80 V DC

Pack size: **1 x EA**

- Supply Voltage: 10 → 80 V dc
- Count Mode: Hours
- Display Type: LCD
- Input Type: Voltage
- Connection Type: Crimp Terminal
- Reset Method: Remote
- Number of Digits: 6
- Mounting Type: Flush Mount, Panel Mount



8966970 10 → 80 V dc

RS PRO HOUR METER COUNTER, 6 DIGIT, 50HZ, 85 → 265 V AC

Pack size: **1 x EA**

- Supply Voltage: 85 → 265 V ac
- Count Mode: Hours
- Display Type: LCD
- Input Type: Voltage
- Connection Type: Screw
- Reset Method: Remote
- Number of Digits: 6
- Mounting Type: Flush Mount, Panel Mount



8966973 85 → 265 V ac

RS PRO HOUR METER COUNTER, 6 DIGIT, 50HZ, 12 → 48 V AC/DC

Pack size: **1 x EA**

- Supply Voltage: 12 → 48 V ac/dc
- Count Mode: Hours
- Display Type: LCD
- Input Type: Voltage
- Connection Type: Screw
- Reset Method: Remote
- Number of Digits: 6
- Mounting Type: Flush Mount, Panel Mount



8966977 12 → 48 V ac/dc

RS PRO COUNTER, DIGITAL HOUR METER COUNTER, 7 DIGIT, 40HZ, 9 →

Pack size: **1 x EA**

- Supply Voltage: 9 → 30 V dc
- Count Mode: Hours, Minutes, Seconds
- Display Type: LCD
- Input Type: Voltage
- Connection Type: Terminal
- Reset Method: Automatic, Manual, No Reset
- Number of Digits: 7
- Mounting Type: Flush Mount, Panel Mount



8966992 9 → 30 V dc

RS PRO COUNTER, DIGITAL HOUR METER COUNTER, 7 DIGIT, 40HZ, 85 →

Pack size: **1 x EA**

- Supply Voltage: 85 → 265 V ac/dc
- Count Mode: Hours, Minutes, Seconds
- Display Type: LCD
- Input Type: Voltage
- Connection Type: Terminal
- Reset Method: Automatic, Manual, No Reset
- Number of Digits: 7
- Mounting Type: Flush Mount, Panel Mount



8966983 85 → 265 V ac/dc

RS PRO HOUR METER COUNTER, 6 DIGIT, 10 → 80 V DC

Pack size: **1 x EA**

- Supply Voltage: 10 → 80 V dc
- Count Mode: Hours
- Display Type: LCD
- Input Type: Voltage
- Connection Type: Screw
- Reset Method: Remote
- Number of Digits: 6
- Mounting Type: Flush Mount, Panel Mount



8966986 10 → 80 V dc

RS PRO COUNTER, 7 DIGIT

Pack size: **1 x EA**

- Display Type: LCD
- Number of Digits: 7
- Digit Height: 6.5 mm
- Depth: 62 mm
- Series: RS PRO
- Approvals: RoHS Compliant
- Measurement Range: 0 → 9999999
- Meter Type: Digital



8966995 LCD

RS PRO IMPULSE COUNTER COUNTER, 6 DIGIT, 10HZ, 12 → 48 V

Pack size: **1 x EA**

- Supply Voltage: 12 → 48 V ac/dc
- Count Mode: Pulse
- Display Type: LCD
- Input Type: Voltage
- Connection Type: Terminal
- Reset Method: Electrical
- Number of Digits: 6
- Mounting Type: Flush Mount, Panel Mount



8966999 12 → 48 V ac/dc

RS PRO IMPULSE COUNTER COUNTER, 6 DIGIT, 10HZ, 85 → 265 V

Pack size: **1 x EA**

- Supply Voltage: 85 → 265 V ac
- Count Mode: Pulse
- Display Type: LCD
- Input Type: Voltage
- Connection Type: Terminal
- Reset Method: Electrical
- Number of Digits: 6
- Mounting Type: Flush Mount, Panel Mount



8967002 85 → 265 V ac

RS PRO IMPULSE COUNTER COUNTER, 6 DIGIT, 30HZ, 10 → 80 V

Pack size: **1 x EA**

- Supply Voltage: 10 → 80 V dc
- Count Mode: Pulse
- Display Type: LCD
- Input Type: Voltage
- Connection Type: Terminal
- Reset Method: Electrical
- Number of Digits: 6
- Mounting Type: Flush Mount, Panel Mount



8967005 10 → 80 V dc

RS PRO IMPULSE COUNTER COUNTER, 6 DIGIT, 10HZ, 110 V DC

Pack size: **1 x EA**

- Supply Voltage: 110 V dc
- Count Mode: Pulse
- Display Type: Digital
- Input Type: Voltage
- Connection Type: Terminal Strip
- Reset Method: No Reset
- Number of Digits: 6
- Mounting Type: Panel Mount



8967009 110 V dc

RS PRO IMPULSE COUNTER COUNTER, 6 DIGIT, 10HZ, 230 V AC

Pack size: **1 x EA**

- Supply Voltage: 230 V ac
- Count Mode: Pulse
- Display Type: Digital
- Input Type: Voltage
- Connection Type: Terminal Strip
- Reset Method: Manual
- Number of Digits: 6
- Mounting Type: Panel Mount



8967011 230 V ac

RS PRO IMPULSE COUNTER COUNTER, 6 DIGIT, 10HZ, 24 V DC

Pack size: **1 x EA**

- Supply Voltage: 24 V dc
- Count Mode: Pulse
- Display Type: Impulse
- Input Type: Voltage
- Connection Type: Terminal Strip
- Reset Method: Manual
- Number of Digits: 6
- Mounting Type: Panel Mount



8967015 24 V dc

RS PRO IMPULSE COUNTER COUNTER, 6 DIGIT, 10HZ, 220 V DC

Pack size: **1 x EA**

- Supply Voltage: 220 V dc
- Count Mode: Pulse
- Display Type: Digital
- Input Type: Voltage
- Connection Type: Terminal Strip
- Reset Method: Manual
- Number of Digits: 6
- Mounting Type: Panel Mount



8967018 220 V dc

RS PRO IMPULSE COUNTER COUNTER, 6 DIGIT, 10HZ, 115 V AC

Pack size: **1 x EA**

- Supply Voltage: 115 V ac
- Count Mode: Pulse
- Display Type: Digital
- Input Type: Voltage
- Connection Type: Terminal Strip
- Reset Method: Manual
- Number of Digits: 6
- Mounting Type: Panel Mount



8967027 115 V ac

RS PRO IMPULSE COUNTER COUNTER, 6 DIGIT, 10HZ, 12 V DC

Pack size: **1 x EA**

- Supply Voltage: 12 V dc
- Count Mode: Pulse
- Display Type: Digital
- Input Type: Voltage
- Connection Type: Terminal Strip
- Reset Method: Manual
- Number of Digits: 6
- Mounting Type: Panel Mount



8967021 12 V dc

RS PRO IMPULSE COUNTER COUNTER, 6 DIGIT, 10HZ, 24 V DC

Pack size: **1 x EA**

- Supply Voltage: 24 V dc
- Count Mode: Pulse
- Display Type: Digital
- Input Type: Voltage
- Connection Type: Terminal Strip
- Reset Method: No Reset
- Number of Digits: 6
- Mounting Type: Panel Mount



8967033 24 V dc

RS PRO IMPULSE COUNTER COUNTER, 7 DIGIT, 10HZ, 24 V DC

Pack size: **1 x EA**

- Supply Voltage: 24 V dc
- Count Mode: Pulse
- Display Type: Digital
- Input Type: Voltage
- Connection Type: Screw
- Reset Method: No Reset
- Number of Digits: 7
- Mounting Type: Panel Mount



8967043 24 V dc

RS PRO IMPULSE COUNTER COUNTER, 6 DIGIT, 10HZ, 230 V AC

Pack size: **1 x EA**

- Supply Voltage: 230 V ac
- Count Mode: Pulse
- Display Type: Digital
- Input Type: Voltage
- Connection Type: Terminal Strip
- Reset Method: Manual
- Number of Digits: 6
- Mounting Type: Panel Mount



8967024 230 V ac

RS PRO IMPULSE COUNTER COUNTER, 6 DIGIT, 10HZ, 24 V DC

Pack size: **1 x EA**

- Supply Voltage: 24 V dc
- Count Mode: Pulse
- Display Type: Mechanical
- Input Type: Voltage
- Connection Type: Flying Lead
- Reset Method: Manual
- Number of Digits: 6
- Mounting Type: Panel Mount



8967030 24 V dc

RS PRO IMPULSE COUNTER COUNTER, 7 DIGIT, 10HZ, 12 V DC

Pack size: **1 x EA**

- Supply Voltage: 12 V dc
- Count Mode: Pulse
- Display Type: Digital
- Input Type: Voltage
- Connection Type: Screw
- Reset Method: No Reset
- Number of Digits: 7
- Mounting Type: Panel Mount



8967049 12 V dc

RS PRO IMPULSE COUNTER COUNTER, 7 DIGIT, 10HZ, 12 V DC

Pack size: **1 x EA**

- Supply Voltage: 12 V dc
- Count Mode: Pulse
- Display Type: Digital
- Input Type: Voltage
- Connection Type: Screw
- Reset Method: No Reset
- Number of Digits: 7
- Mounting Type: Panel Mount



8967037 12 V dc

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 50A INPUT, 50:5, 5 A

Pack size: **1 x EA**

- Current Ratio: 50:5
- Bore Size: 21 x 10 mm
- Transformer Type: Base Mounted
- Input Current: 50 A
- Output Current: 5 A
- Overall Height: 65 mm
- Overall Width: 7.2 mm
- Overall Depth: 40 mm



1718750 50:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 60A INPUT, 60:5, 5 A

Pack size: **1 x EA**

- Current Ratio: 60:5
- Bore Size: 21 x 10 mm
- Transformer Type: Base Mounted
- Input Current: 60 A
- Output Current: 5 A
- Overall Height: 65 mm
- Overall Width: 7.2 mm
- Overall Depth: 40 mm



1718751 60:5

RS PRO IMPULSE COUNTER COUNTER, 7 DIGIT, 10HZ, 24 V DC

Pack size: **1 x EA**

- Supply Voltage: 24 V dc
- Count Mode: Pulse
- Display Type: Digital
- Input Type: Voltage
- Connection Type: Screw
- Reset Method: No Reset
- Number of Digits: 7
- Mounting Type: Panel Mount



8967046 24 V dc

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 100A INPUT, 100:5, 5

Pack size: **1 x EA**

- Current Ratio: 100:5
- Bore Size: 21 x 10 mm
- Transformer Type: Base Mounted
- Input Current: 100 A
- Output Current: 5 A
- Overall Height: 65 mm
- Overall Width: 45 mm
- Overall Depth: 40 mm



1718755 100:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 125A INPUT, 125:5, 5

Pack size: **1 x EA**

- Current Ratio: 125:5
- Bore Size: 21 x 10 mm
- Transformer Type: Base Mounted
- Input Current: 125 A
- Output Current: 5 A
- Overall Height: 65 mm
- Overall Width: 45 mm
- Overall Depth: 40 mm



1718756 125:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 150A INPUT, 150:5, 5

Pack size: **1 x EA**

- Current Ratio: 150:5
- Bore Size: 21 x 10 mm
- Transformer Type: Base Mounted
- Input Current: 150 A
- Output Current: 5 A
- Overall Height: 65 mm
- Overall Width: 45 mm
- Overall Depth: 40 mm



1718758 150:5

RS PRO CURRENT TRANSFORMER, 50:1, 21 X 10MM BORE

Pack size: **1 x EA**

- Current Ratio: 50:1
- Bore Size: 21 x 10 mm
- Overall Height: 65 mm
- Overall Width: 7.2 mm
- Overall Depth: 40 mm
- Dimensions: 45 x 40 x 65 mm



1718749 50:1

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 80A INPUT, 80:5, 5 A

Pack size: **1 x EA**

- Current Ratio: 80:5
- Bore Size: 21 x 10 mm
- Transformer Type: Base Mounted
- Input Current: 80 A
- Output Current: 5 A
- Overall Height: 65 mm
- Overall Width: 7.2 mm
- Overall Depth: 40 mm



1718753 80:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 200A INPUT, 200:5, 5

Pack size: **1 x EA**

- Current Ratio: 200:5
- Bore Size: 21 x 10 mm
- Transformer Type: Base Mounted
- Input Current: 200 A
- Output Current: 5 A
- Overall Height: 65 mm
- Overall Width: 45 mm
- Overall Depth: 40 mm



1718760 200:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 100A INPUT, 100:5, 5

Pack size: **1 x EA**

- Current Ratio: 100:5
- Bore Size: 30 x 10 mm
- Transformer Type: Base Mounted
- Input Current: 100 A
- Output Current: 5 A
- Overall Height: 70 mm
- Overall Width: 50 mm
- Overall Depth: 31 mm



1718765 100:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 80A INPUT, 80:5, 5 A

Pack size: **1 x EA**

- Current Ratio: 80:5
- Bore Size: 30 x 10 mm
- Transformer Type: Base Mounted
- Input Current: 80 A
- Output Current: 5 A
- Overall Height: 70 mm
- Overall Width: 50 mm
- Overall Depth: 31 mm



1718763 80:5

RS PRO CURRENT TRANSFORMER, 100:1, 30 X 10MM BORE

Pack size: **1 x EA**

- Current Ratio: 100:1
- Bore Size: 30 x 10 mm
- Overall Height: 70 mm
- Overall Width: 50 mm
- Overall Depth: 30 mm
- Dimensions: 50 x 30 x 70 mm



1718764 100:1

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 150A INPUT, 150:5, 5

Pack size: **1 x EA**

- Current Ratio: 150:5
- Bore Size: 30 x 10 mm
- Transformer Type: Base Mounted
- Input Current: 150 A
- Output Current: 5 A
- Overall Height: 70 mm
- Overall Width: 50 mm
- Overall Depth: 31 mm



1718769 150:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 200A INPUT, 200:5, 5

Pack size: **1 x EA**

- Current Ratio: 200:5
- Bore Size: 30 x 10 mm
- Transformer Type: Base Mounted
- Input Current: 200 A
- Output Current: 5 A
- Overall Height: 70 mm
- Overall Width: 50 mm
- Overall Depth: 31 mm



1718771 200:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 250A INPUT, 250:5, 5

Pack size: **1 x EA**

- Current Ratio: 250:5
- Bore Size: 30 x 10 mm
- Transformer Type: Base Mounted
- Input Current: 250 A
- Output Current: 5 A
- Overall Height: 70 mm
- Overall Width: 50 mm
- Overall Depth: 31 mm



1718773 250:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 125A INPUT, 125:5, 5

Pack size: **1 x EA**

- Current Ratio: 125:5
- Bore Size: 30 x 10 mm
- Transformer Type: Base Mounted
- Input Current: 125 A
- Output Current: 5 A
- Overall Height: 70 mm
- Overall Width: 50 mm
- Overall Depth: 31 mm



1718766 125:5

RS PRO CURRENT TRANSFORMER, 200:1, 30 X 10MM BORE

Pack size: **1 x EA**

- Current Ratio: 200:1
- Bore Size: 30 x 10 mm
- Overall Height: 70 mm
- Overall Width: 50 mm
- Overall Depth: 30 mm
- Dimensions: 50 x 30 x 70 mm



1718770 200:1

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 400A INPUT, 400:5, 5

Pack size: **1 x EA**

- Current Ratio: 400:5
- Bore Size: 30 x 10 mm
- Transformer Type: Base Mounted
- Input Current: 400 A
- Output Current: 5 A
- Overall Height: 70 mm
- Overall Width: 50 mm
- Overall Depth: 31 mm



1718777 400:5

RS PRO CURRENT TRANSFORMER, 400:1, 30 X 10MM BORE

Pack size: **1 x EA**

- Current Ratio: 400:1
- Bore Size: 30 x 10 mm
- Overall Height: 70 mm
- Overall Width: 50 mm
- Overall Depth: 30 mm
- Dimensions: 50 x 30 x 70 mm



1718776 400:1

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 500A INPUT, 500:5, 5

Pack size: **1 x EA**

- Current Ratio: 500:5
- Bore Size: 30 x 10 mm
- Transformer Type: Base Mounted
- Input Current: 500 A
- Output Current: 5 A
- Overall Height: 70 mm
- Overall Width: 50 mm
- Overall Depth: 31 mm



1718778 500:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 600A INPUT, 600:5, 5

Pack size: **1 x EA**

- Current Ratio: 600:5
- Bore Size: 30 x 10 mm
- Transformer Type: Base Mounted
- Input Current: 600 A
- Output Current: 5 A
- Overall Height: 70 mm
- Overall Width: 50 mm
- Overall Depth: 31 mm



1718779 600:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 100A INPUT, 100:5, 5

Pack size: **1 x EA**

- Current Ratio: 100:5
- Bore Size: 30 x 11 mm
- Transformer Type: Base Mounted
- Input Current: 100 A
- Output Current: 5 A
- Overall Height: 78 mm
- Overall Width: 62 mm
- Overall Depth: 40 mm



1718781 100:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 125A INPUT, 125:5, 5

Pack size: **1 x EA**

- Current Ratio: 125:5
- Bore Size: 30 x 11 mm
- Transformer Type: Base Mounted
- Input Current: 125 A
- Output Current: 5 A
- Overall Height: 78 mm
- Overall Width: 62 mm
- Overall Depth: 40 mm



1718782 125:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 150A INPUT, 150:5, 5

Pack size: **1 x EA**

- Current Ratio: 150:5
- Bore Size: 30 x 11 mm
- Transformer Type: Base Mounted
- Input Current: 150 A
- Output Current: 5 A
- Overall Height: 78 mm
- Overall Width: 62 mm
- Overall Depth: 40 mm



1718783 150:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 100A INPUT, 100:5, 5

Pack size: **1 x EA**

- Current Ratio: 100:5
- Bore Size: 40 x 11 mm
- Transformer Type: Base Mounted
- Input Current: 100 A
- Output Current: 5 A
- Overall Height: 78 mm
- Overall Width: 62 mm
- Overall Depth: 40 mm



1718785 100:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 200A INPUT, 200:5, 5

Pack size: **1 x EA**

- Current Ratio: 200:5
- Bore Size: 40 x 11 mm
- Transformer Type: Base Mounted
- Input Current: 200 A
- Output Current: 5 A
- Overall Height: 78 mm
- Overall Width: 62 mm
- Overall Depth: 40 mm



1718787 200:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 250A INPUT, 250:5, 5

Pack size: **1 x EA**

- Current Ratio: 250:5
- Bore Size: 40 x 11 mm
- Transformer Type: Base Mounted
- Input Current: 250 A
- Output Current: 5 A
- Overall Height: 78 mm
- Overall Width: 62 mm
- Overall Depth: 40 mm



1718788 250:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 300A INPUT, 300:5, 5

Pack size: **1 x EA**

- Current Ratio: 300:5
- Bore Size: 40 x 11 mm
- Transformer Type: Base Mounted
- Input Current: 300 A
- Output Current: 5 A
- Overall Height: 78 mm
- Overall Width: 62 mm
- Overall Depth: 40 mm



1718789 300:5

RS PRO CURRENT TRANSFORMER, 400:1, 40 X 11MM BORE

Pack size: **1 x EA**

- Current Ratio: 400:1
- Bore Size: 40 x 11 mm
- Overall Height: 78 mm
- Overall Width: 62 mm
- Overall Depth: 40 mm
- Dimensions: 62 x 40 x 78 mm



1718790 400:1

RS PRO CURRENT TRANSFORMER, 250:1, 30 X 10MM BORE

Pack size: **1 x EA**

- Current Ratio: 250:1
- Bore Size: 30 x 10 mm
- Overall Height: 70 mm
- Overall Width: 50 mm
- Overall Depth: 30 mm
- Dimensions: 50 x 30 x 70 mm



1718772 250:1

RS PRO CURRENT TRANSFORMER, 600:1, 40 X 11MM BORE

Pack size: **1 x EA**

- Current Ratio: 600:1
- Bore Size: 40 x 11 mm
- Overall Height: 78 mm
- Overall Width: 62 mm
- Overall Depth: 40 mm
- Dimensions: 62 x 40 x 78 mm



1718793 600:1

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 300A INPUT, 300:5, 5

Pack size: **1 x EA**

- Current Ratio: 300:5
- Bore Size: 30 x 10 mm
- Transformer Type: Base Mounted
- Input Current: 300 A
- Output Current: 5 A
- Overall Height: 70 mm
- Overall Width: 50 mm
- Overall Depth: 31 mm



1718775 300:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 600A INPUT, 600:5, 5

Pack size: **1 x EA**

- Current Ratio: 600:5
- Bore Size: 40 x 11 mm
- Transformer Type: Base Mounted
- Input Current: 600 A
- Output Current: 5 A
- Overall Height: 78 mm
- Overall Width: 62 mm
- Overall Depth: 40 mm



1718794 600:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 400A INPUT, 400:5, 5

Pack size: **1 x EA**

- Current Ratio: 400:5
- Bore Size: 41 x 41 mm
- Transformer Type: Base Mounted
- Input Current: 400 A
- Output Current: 5 A
- Overall Height: 98 mm
- Overall Width: 74 mm
- Overall Depth: 45 mm



1718799 400:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 800A INPUT, 800:5, 5

Pack size: **1 x EA**

- Current Ratio: 800:5
- Bore Size: 40 x 11 mm
- Transformer Type: Base Mounted
- Input Current: 800 A
- Output Current: 5 A
- Overall Height: 78 mm
- Overall Width: 62 mm
- Overall Depth: 40 mm



1718798 800:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 400A INPUT, 400:5, 5

Pack size: **1 x EA**

- Current Ratio: 400:5
- Bore Size: 40 x 11 mm
- Transformer Type: Base Mounted
- Input Current: 400 A
- Output Current: 5 A
- Overall Height: 78 mm
- Overall Width: 62 mm
- Overall Depth: 40 mm



1718791 400:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 600A INPUT, 600:5, 5

Pack size: **1 x EA**

- Current Ratio: 600:5
- Bore Size: 41 x 41 mm
- Transformer Type: Base Mounted
- Input Current: 600 A
- Output Current: 5 A
- Overall Height: 98 mm
- Overall Width: 74 mm
- Overall Depth: 45 mm



1718801 600:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 500A INPUT, 500:5, 5

Pack size: **1 x EA**

- Current Ratio: 500:5
- Bore Size: 40 x 11 mm
- Transformer Type: Base Mounted
- Input Current: 500 A
- Output Current: 5 A
- Overall Height: 78 mm
- Overall Width: 62 mm
- Overall Depth: 40 mm



1718792 500:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 500A INPUT, 500:5, 5

Pack size: **1 x EA**

- Current Ratio: 500:5
- Bore Size: 41 x 41 mm
- Transformer Type: Base Mounted
- Input Current: 500 A
- Output Current: 5 A
- Overall Height: 98 mm
- Overall Width: 74 mm
- Overall Depth: 45 mm



1718800 500:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 1000A INPUT, 1000:5, 5

Pack size: **1 x EA**

- Current Ratio: 1000:5
- Bore Size: 61 x 51 mm
- Transformer Type: Base Mounted
- Input Current: 1000 A
- Output Current: 5 A
- Overall Height: 110 mm
- Overall Width: 86 mm
- Overall Depth: 45 mm



1718805 1000:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 1250A INPUT, 1250:5, 5

Pack size: **1 x EA**

- Current Ratio: 1250:5
- Bore Size: 61 x 51 mm
- Transformer Type: Base Mounted
- Input Current: 1250 A
- Output Current: 5 A
- Overall Height: 110 mm
- Overall Width: 86 mm
- Overall Depth: 45 mm



1718807 1250:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 800A INPUT, 800:5, 5

Pack size: **1 x EA**

- Current Ratio: 800:5
- Bore Size: 41 x 41 mm
- Transformer Type: Base Mounted
- Input Current: 800 A
- Output Current: 5 A
- Overall Height: 98 mm
- Overall Width: 74 mm
- Overall Depth: 45 mm



1718802 800:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 1000A INPUT, 1000:5, 5

Pack size: **1 x EA**

- Current Ratio: 1000:5
- Bore Size: 41 x 41 mm
- Transformer Type: Base Mounted
- Input Current: 1000 A
- Output Current: 5 A
- Overall Height: 98 mm
- Overall Width: 74 mm
- Overall Depth: 45 mm



1718804 1000:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 1000A INPUT, 1000:5, 5

Pack size: **1 x EA**

- Current Ratio: 1000:5
- Bore Size: 80 x 12 mm
- Transformer Type: Base Mounted
- Input Current: 1000 A
- Output Current: 5 A
- Overall Height: 126 mm
- Overall Width: 104 mm
- Overall Depth: 45 mm



1718812 1000:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 1500A INPUT, 1500:5, 5

Pack size: **1 x EA**

- Current Ratio: 1500:5
- Bore Size: 61 x 51 mm
- Transformer Type: Base Mounted
- Input Current: 1500 A
- Output Current: 5 A
- Overall Height: 110 mm
- Overall Width: 86 mm
- Overall Depth: 45 mm



1718809 1500:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 800A INPUT, 800:5, 5

Pack size: **1 x EA**

- Current Ratio: 800:5
- Bore Size: 80 x 12 mm
- Transformer Type: Base Mounted
- Input Current: 800 A
- Output Current: 5 A
- Overall Height: 126 mm
- Overall Width: 104 mm
- Overall Depth: 45 mm



1718811 800:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 1250A INPUT, 1250:5, 5

Pack size: **1 x EA**

- Current Ratio: 1250:5
- Bore Size: 80 x 12 mm
- Transformer Type: Base Mounted
- Input Current: 1250 A
- Output Current: 5 A
- Overall Height: 126 mm
- Overall Width: 104 mm
- Overall Depth: 45 mm



1718814 1250:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 2000A INPUT, 2000:5, 5

Pack size: **1 x EA**

- Current Ratio: 2000:5
- Bore Size: 80 x 12 mm
- Transformer Type: Base Mounted
- Input Current: 2000 A
- Output Current: 5 A
- Overall Height: 126 mm
- Overall Width: 104 mm
- Overall Depth: 45 mm



1718817 2000:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 2000A INPUT, 2000:5, 5

Pack size: **1 x EA**

- Current Ratio: 2000:5
- Bore Size: 100 x 30 mm
- Transformer Type: Base Mounted
- Input Current: 2000 A
- Output Current: 5 A
- Overall Height: 155 mm
- Overall Width: 140 mm
- Overall Depth: 45 mm



1718821 2000:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 2500A INPUT,

Pack size: **1 x EA**

- Current Ratio: 2500:5
- Bore Size: 100 x 30 mm
- Transformer Type: Base Mounted
- Input Current: 2500 A
- Output Current: 5 A
- Overall Height: 155 mm
- Overall Width: 140 mm
- Overall Depth: 45 mm



1718822 2500:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 1500A INPUT, 1500:5,

Pack size: **1 x EA**

- Current Ratio: 1500:5
- Bore Size: 80 x 12 mm
- Transformer Type: Base Mounted
- Input Current: 1500 A
- Output Current: 5 A
- Overall Height: 126 mm
- Overall Width: 104 mm
- Overall Depth: 45 mm



1718815 1500:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 1600A INPUT, 1600:5,

Pack size: **1 x EA**

- Current Ratio: 1600:5
- Bore Size: 80 x 12 mm
- Transformer Type: Base Mounted
- Input Current: 1600 A
- Output Current: 5 A
- Overall Height: 126 mm
- Overall Width: 104 mm
- Overall Depth: 45 mm



1718816 1600:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 3000A INPUT,

Pack size: **1 x EA**

- Current Ratio: 3000:5
- Bore Size: 100 x 30 mm
- Transformer Type: Base Mounted
- Input Current: 3000 A
- Output Current: 5 A
- Overall Height: 155 mm
- Overall Width: 140 mm
- Overall Depth: 45 mm



1718823 3000:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 150A INPUT, 150:5, 5

Pack size: **1 x EA**

- Current Ratio: 150:5
- Bore Size: 35 mm
- Transformer Type: Base Mounted
- Input Current: 150 A
- Output Current: 5 A
- Overall Height: 87.5 mm
- Overall Width: 105 mm
- Overall Depth: 38 mm



1718826 150:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 100A INPUT, 100:5, 5

Pack size: **1 x EA**

- Current Ratio: 100:5
- Bore Size: 35 mm
- Transformer Type: Base Mounted
- Input Current: 100 A
- Output Current: 5 A
- Overall Height: 87.5 mm
- Overall Width: 105 mm
- Overall Depth: 38 mm



1718824 100:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 125A INPUT, 125:5, 5

Pack size: **1 x EA**

- Current Ratio: 125:5
- Bore Size: 35 mm
- Transformer Type: Base Mounted
- Input Current: 125 A
- Output Current: 5 A
- Overall Height: 87.5 mm
- Overall Width: 105 mm
- Overall Depth: 38 mm



1718825 125:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 160A INPUT, 160:5, 5

Pack size: **1 x EA**

- Current Ratio: 160:5
- Bore Size: 35 mm
- Transformer Type: Base Mounted
- Input Current: 160 A
- Output Current: 5 A
- Overall Height: 87.5 mm
- Overall Width: 105 mm
- Overall Depth: 38 mm



1718827 160:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 200A INPUT, 200:5, 5

Pack size: **1 x EA**

- Current Ratio: 200:5
- Bore Size: 35 mm
- Transformer Type: Base Mounted
- Input Current: 200 A
- Output Current: 5 A
- Overall Height: 87.5 mm
- Overall Width: 105 mm
- Overall Depth: 38 mm



1718828 200:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 250A INPUT, 250:5, 5

Pack size: **1 x EA**

- Current Ratio: 250:5
- Bore Size: 35 mm
- Transformer Type: Base Mounted
- Input Current: 250 A
- Output Current: 5 A
- Overall Height: 87.5 mm
- Overall Width: 105 mm
- Overall Depth: 38 mm



1718829 250:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 250A INPUT, 250:5, 5

Pack size: **1 x EA**

- Current Ratio: 250:5
- Bore Size: 45 mm
- Transformer Type: Base Mounted
- Input Current: 250 A
- Output Current: 5 A
- Overall Height: 102.5 mm
- Overall Width: 141 mm
- Overall Depth: 38 mm



1718830 250:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 300A INPUT, 300:5, 5

Pack size: **1 x EA**

- Current Ratio: 300:5
- Bore Size: 45 mm
- Transformer Type: Base Mounted
- Input Current: 300 A
- Output Current: 5 A
- Overall Height: 102.5 mm
- Overall Width: 141 mm
- Overall Depth: 38 mm



1718831 300:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 400A INPUT, 400:5, 5

Pack size: **1 x EA**

- Current Ratio: 400:5
- Bore Size: 45 mm
- Transformer Type: Base Mounted
- Input Current: 400 A
- Output Current: 5 A
- Overall Height: 102.5 mm
- Overall Width: 141 mm
- Overall Depth: 38 mm



1718832 400:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 2000A INPUT,

Pack size: **1 x EA**

- Current Ratio: 2000:5
- Bore Size: 38 x 128 mm
- Transformer Type: Base Mounted
- Input Current: 2000 A
- Output Current: 5 A
- Overall Height: 170 mm
- Overall Width: 99 mm
- Overall Depth: 45 mm



1718838 2000:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 600A INPUT, 600:5, 5

Pack size: **1 x EA**

- Current Ratio: 600:5
- Bore Size: 45 mm
- Transformer Type: Base Mounted
- Input Current: 600 A
- Output Current: 5 A
- Overall Height: 102.5 mm
- Overall Width: 141 mm
- Overall Depth: 38 mm



1718833 600:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 1000A INPUT, 1000:5,

Pack size: **1 x EA**

- Current Ratio: 1000:5
- Bore Size: 38 x 128 mm
- Transformer Type: Base Mounted
- Input Current: 1000 A
- Output Current: 5 A
- Overall Height: 170 mm
- Overall Width: 99 mm
- Overall Depth: 45 mm



1718834 1000:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 2500A INPUT,

Pack size: **1 x EA**

- Current Ratio: 2500:5
- Bore Size: 38 x 128 mm
- Transformer Type: Base Mounted
- Input Current: 2500 A
- Output Current: 5 A
- Overall Height: 170 mm
- Overall Width: 99 mm
- Overall Depth: 45 mm



1718839 2500:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 1000A INPUT, 1000:5,

Pack size: **1 x EA**

- Current Ratio: 1000:5
- Bore Size: 101 x 56 mm
- Transformer Type: Base Mounted
- Input Current: 1000 A
- Output Current: 5 A
- Overall Height: 170 mm
- Overall Width: 130 mm
- Overall Depth: 60 mm



1718840 1000:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 2500A INPUT,

Pack size: **1 x EA**

- Current Ratio: 2500:5
- Bore Size: 101 x 56 mm
- Transformer Type: Base Mounted
- Input Current: 2500 A
- Output Current: 5 A
- Overall Height: 170 mm
- Overall Width: 130 mm
- Overall Depth: 60 mm



1718845 2500:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 100A INPUT, 100:5, 5

Pack size: **1 x EA**

- Current Ratio: 100:5
- Bore Size: 33 x 23 mm
- Transformer Type: Base Mounted
- Input Current: 100 A
- Output Current: 5 A
- Overall Height: 106 mm
- Overall Width: 93 mm
- Overall Depth: 40 mm



1718846 100:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 200A INPUT, 200:5, 5

Pack size: **1 x EA**

- Current Ratio: 200:5
- Bore Size: 33 x 23 mm
- Transformer Type: Base Mounted
- Input Current: 200 A
- Output Current: 5 A
- Overall Height: 106 mm
- Overall Width: 93 mm
- Overall Depth: 40 mm



1718848 200:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 500A INPUT, 500:5, 5

Pack size: **1 x EA**

- Current Ratio: 500:5
- Bore Size: 55 x 43 mm
- Transformer Type: Base Mounted
- Input Current: 500 A
- Output Current: 5 A
- Overall Height: 125 mm
- Overall Width: 108 mm
- Overall Depth: 51 mm



1718852 500:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 250A INPUT, 250:5, 5

Pack size: **1 x EA**

- Current Ratio: 250:5
- Bore Size: 33 x 23 mm
- Transformer Type: Base Mounted
- Input Current: 250 A
- Output Current: 5 A
- Overall Height: 106 mm
- Overall Width: 93 mm
- Overall Depth: 40 mm



1718849 250:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 300A INPUT, 300:5, 5

Pack size: **1 x EA**

- Current Ratio: 300:5
- Bore Size: 33 x 23 mm
- Transformer Type: Base Mounted
- Input Current: 300 A
- Output Current: 5 A
- Overall Height: 106 mm
- Overall Width: 93 mm
- Overall Depth: 40 mm



1718850 300:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 400A INPUT, 400:5, 5

Pack size: **1 x EA**

- Current Ratio: 400:5
- Bore Size: 33 x 23 mm
- Transformer Type: Base Mounted
- Input Current: 400 A
- Output Current: 5 A
- Overall Height: 106 mm
- Overall Width: 93 mm
- Overall Depth: 40 mm



1718851 400:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 600A INPUT, 600:5, 5

Pack size: **1 x EA**

- Current Ratio: 600:5
- Bore Size: 55 x 43 mm
- Transformer Type: Base Mounted
- Input Current: 600 A
- Output Current: 5 A
- Overall Height: 125 mm
- Overall Width: 108 mm
- Overall Depth: 51 mm



1718854 600:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 10A INPUT, 10:5, 5 A

Pack size: **1 x EA**

- Current Ratio: 10:5
- Bore Size: 62 x 40 mm
- Transformer Type: Base Mounted
- Input Current: 10 A
- Output Current: 5 A
- Overall Height: 78 mm
- Overall Width: 62 mm
- Overall Depth: 40 mm



1718856 10:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 20A INPUT, 20:5, 5 A

Pack size: **1 x EA**

- Current Ratio: 20:5
- Bore Size: 62 x 40 mm
- Transformer Type: Base Mounted
- Input Current: 20 A
- Output Current: 5 A
- Overall Height: 78 mm
- Overall Width: 62 mm
- Overall Depth: 40 mm



1718858 20:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 30A INPUT, 30:5, 5 A

Pack size: **1 x EA**

- Current Ratio: 30:5
- Bore Size: 62 x 40 mm
- Transformer Type: Base Mounted
- Input Current: 30 A
- Output Current: 5 A
- Overall Height: 78 mm
- Overall Width: 62 mm
- Overall Depth: 40 mm



1718859 30:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 15A INPUT, 15:5, 5 A

Pack size: **1 x EA**

- Current Ratio: 15:5
- Bore Size: 62 x 40 mm
- Transformer Type: Base Mounted
- Input Current: 15 A
- Output Current: 5 A
- Overall Height: 78 mm
- Overall Width: 62 mm
- Overall Depth: 40 mm



1718857 15:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 5A INPUT, 5:5, 5 A

Pack size: **1 x EA**

- Current Ratio: 5:5
- Bore Size: 62 x 40 mm
- Transformer Type: Base Mounted
- Input Current: 5 A
- Output Current: 5 A
- Overall Height: 78 mm
- Overall Width: 62 mm
- Overall Depth: 40 mm



1718855 5:5

RS PRO BASE MOUNTED CURRENT TRANSFORMER, 40A INPUT, 40:5, 5 A

Pack size: **1 x EA**

- Current Ratio: 40:5
- Bore Size: 74 x 45 mm
- Transformer Type: Base Mounted
- Input Current: 40 A
- Output Current: 5 A
- Overall Height: 98 mm
- Overall Width: 74 mm
- Overall Depth: 45 mm



1718860 40:5

RS PRO 3 PHASE ENERGY METER, TYPE

Pack size: **1 x EA**

- Cutout Height: 90 mm
- Cutout Width: 90 mm
- Display Type: Digital
- Number of Digits: 4
- Number of Phases: 3
- Depth: 55 mm
- Digit Height: 10 mm
- Meter Accuracy: Class 1



1797572 90 mm

RS PRO LED DIGITAL PANEL MULTI-FUNCTION METER FOR CURRENT,

Pack size: **1 x EA**

- Properties Measured: Current, Frequency, On Hour, RPM, Run Hour, Voltage
- Display Type: LED
- Cutout Height: 92 mm
- Cutout Width: 92 mm
- Depth: 55 mm
- Number of Digits: 3
- Minimum Temperature: -10 °C
- Maximum Temperature: +55 °C



1365377 Current,

RS PRO 3 PHASE LED ENERGY METER, TYPE

Pack size: **1 x EA**

- Cutout Height: 90 mm
- Cutout Width: 90 mm
- Display Type: LED
- Number of Digits: 4 (Instantaneous), 6 (Integrated)
- Number of Phases: 3
- Depth: 55 mm
- Digit Height: 10 mm
- Meter Accuracy: Class 1



1797577 90 mm

RS PRO FREQUENCY CONTROL FREQUENCY METER

Pack size: **1 x EA**

- Display Type: Analogue
- Cutout Size: 72 x 72 mm
- Function: Frequency Control
- Cutout Height: 72 mm
- Cutout Width: 72 mm
- Meter Type: Moving Iron
- Maximum Temperature: +50 °C
- Measurement Range: 45 → 65 Hz



9010573 Analogue

RS PRO FREQUENCY CONTROL FREQUENCY METER

Pack size: **1 x EA**

- Display Type: Analogue
- Cutout Size: 96 x 96 mm
- Function: Frequency Control
- Cutout Height: 96 mm
- Cutout Width: 96 mm
- Meter Type: Moving Iron
- Maximum Temperature: +50 °C
- Measurement Range: 45 → 65 Hz



9010576 Analogue

RS PRO LED DIGITAL PANEL MULTI-FUNCTION METER FOR CURRENT,

Pack size: **1 x EA**

- Properties Measured: Current, Frequency, On Hour, RPM, Run Hour, Voltage
- Display Type: LED
- Cutout Height: 92 mm
- Cutout Width: 92 mm
- Depth: 55 mm
- Number of Digits: 3
- Minimum Temperature: -10 °C
- Maximum Temperature: +55 °C



1365378 Current,

RS PRO LED DIGITAL PANEL MULTI-FUNCTION METER FOR AC CURRENT,

Pack size: **1 x EA**

- Properties Measured: AC Current, AC Voltage, Frequency, Hour, RPM
- Display Type: LED
- Cutout Height: 92 mm
- Cutout Width: 92 mm
- Depth: 62 mm
- Number of Digits: 4
- Digit Height: 20 mm
- Minimum Temperature: -20 °C



1365379 AC Current, AC

RS PRO LED DIGITAL PANEL MULTI-FUNCTION METER FOR AC CURRENT,

Pack size: **1 x EA**

- Properties Measured: AC Current, AC Voltage, Frequency, Hour, RPM
- Display Type: LED
- Cutout Height: 92 mm
- Cutout Width: 92 mm
- Depth: 62 mm
- Number of Digits: 4
- Digit Height: 20 mm
- Minimum Temperature: -20 °C



1365380 AC Current, AC

RS PRO LED DIGITAL PANEL MULTI-FUNCTION METER FOR CURRENT,

Pack size: **1 x EA**

- Properties Measured: Current, Frequency, System Active Power, System Re-Active Power, Voltage
- Display Type: LED
- Cutout Height: 92 mm
- Cutout Width: 92 mm
- Depth: 55 mm
- Number of Digits: 4
- Minimum Temperature: 0 °C
- Maximum Temperature: +50 °C



1365381 Current,

RS PRO LED DIGITAL PANEL MULTI-FUNCTION METER FOR CURRENT,

Pack size: **1 x EA**

- Properties Measured: Current, Frequency, System Active Power, System Re-Active Power, Voltage
- Display Type: LED
- Cutout Height: 92 mm
- Cutout Width: 92 mm
- Depth: 55 mm
- Number of Digits: 4
- Minimum Temperature: 0 °C
- Maximum Temperature: +50 °C



1365382 Current,

MAGNET, CENTRE POLE, SURFACE MOUNT

Pack size: **5 x EA**

- Accessory Type: Centre Pole Magnet
- For Use With: Hall Effect Switch, Reed Proximity Switch, Reed Relay



260369 Centre Pole

RS PRO LED DIGITAL PANEL MULTI-FUNCTION METER FOR AC CURRENT,

Pack size: **1 x EA**

- Properties Measured: AC Current, AC Voltage, Active, Apparent Power, Frequency, Import Export Energy, Reactive
- Display Type: LED
- Cutout Height: 92 mm
- Cutout Width: 92 mm
- Depth: 55 mm
- Number of Digits: 4
- Minimum Temperature: -20 °C
- Maximum Temperature: +70 °C



1365383 AC Current, AC

RS PRO 7 SEGMENT LED DIGITAL PANEL MULTI-FUNCTION METER FOR

Pack size: **1 x EA**

- Properties Measured: Current, Voltage
- Display Type: 7 Segment LED
- Depth: 66 mm
- Number of Digits: 4
- Digit Height: 14 mm
- Minimum Temperature: -20 °C
- Maximum Temperature: +60 °C
- Measurement Range: ±2 → ±10 (Voltage) V, -20 → 20 (Current) mA



1883474 Current, Voltage

RS PRO BEZEL FOR USE WITH 55 X 55 HOUR METER

Pack size: **1 x EA**

- Accessory Type: Bezel
- For Use With: 55 x 55 Hour Meter




8966908 Bezel

RS PRO 60A METER SCALE FOR USE WITH 72 X 72 ANALOGUE PANEL

Pack size: **1 x EA**

- Accessory Type: 60A Meter Scale
- For Use With: 72 x 72 Analogue Panel Ammeter



9010422 60A Meter Scale

RS PRO 250A METER SCALE FOR USE WITH 72 X 72 ANALOGUE PANEL

Pack size: **1 x EA**

- Accessory Type: 250A Meter Scale
- For Use With: 72 x 72 Analogue Panel Ammeter



9010444 250A Meter Scale

RS PRO PANEL MOUNT MULTI FUNCTION TIMER RELAY, 24V AC/DC

Pack size: **1 x EA**

- Supply Voltage: 24 V ac/dc
- Mounting Type: Panel Mount
- Mode of Operation: Multifunction
- Number of Timer Functions: Multi Function
- Time Increment: Seconds
- Maximum Voltage: 230 V
- Terminal Type: Screw
- Minimum Voltage: 24 V



1241078 24 V ac/dc

RS PRO 60A METER SCALE FOR USE WITH 96 X 96 ANALOGUE PANEL

Pack size: **1 x EA**

- Accessory Type: 60A Meter Scale
- For Use With: 96 x 96 Analogue Panel Ammeter



9010472 60A Meter Scale

DIGITAL TIMER, 35X77, 230V AC

Pack size: **1 x EA**

- Supply Voltage: 230 V ac
- Mounting Type: Panel Mount
- Mode of Operation: Multifunction
- Number of Timer Functions: Multi Function
- Time Increment: Seconds
- Maximum Voltage: 230 V
- Terminal Type: Screw
- Minimum Voltage: 100 V



1241077 230 V ac

RS PRO PANEL MOUNT MULTI FUNCTION TIMER RELAY, 12 → 48 V

Pack size: **1 x EA**

- Supply Voltage: 12 → 48 V dc, 24 → 48 V ac
- Mounting Type: Panel Mount
- Number of Contacts: 2
- Time Range: 0.1 s → 300 h
- Mode of Operation: Flicker OFF Start, Flicker ON Start, Interval, ON Delay, Signal OFF Delay, Signal ON/OFF Delay
- Number of Timer Functions: Multi Function
- Contact Configuration: DPDT
- Time Increment: Hours, Seconds



1792916 12 → 48 V dc, 24 →

RS PRO PANEL MOUNT MULTI FUNCTION TIMER RELAY, 12 → 48 V

Pack size: **1 x EA**

- Supply Voltage: 12 → 48 V dc, 24 → 48 V ac
- Mounting Type: Panel Mount
- Number of Contacts: 2
- Time Range: 0.1 s → 300 h
- Mode of Operation: Flicker ON Start, Interval, ON Delay, One Shot
- Number of Timer Functions: Multi Function
- Contact Configuration: DPDT
- Time Increment: Hours, Seconds



1792918 12 → 48 V dc, 24 →

RS PRO PANEL MOUNT MULTI FUNCTION TIMER RELAY, 24V DC,

Pack size: **1 x EA**

- Supply Voltage: 24 V dc
- Mounting Type: Panel Mount
- Number of Contacts: 2
- Time Range: 0.1 s → 300 h
- Mode of Operation: Flicker OFF Start, Flicker ON Start, Interval, ON Delay, Signal OFF Delay, Signal ON/OFF Delay
- Number of Timer Functions: Multi Function
- Contact Configuration: DPDT
- Time Increment: Hours, Seconds



1792922 24 V dc

RS PRO PLUG IN SINGLE FUNCTION TIMER RELAY, 24V DC, DPDT, 0.2 → 5S

Pack size: **1 x EA**

- Supply Voltage: 24 V dc
- Mounting Type: Plug In
- Number of Contacts: 2
- Time Range: 0.2 → 5 s
- Mode of Operation: ON Delay
- Number of Timer Functions: Single
- Contact Configuration: DPDT
- Time Increment: Seconds



1792948 24 V dc

RS PRO PANEL MOUNT SINGLE FUNCTION TIMER RELAY, 24V DC, 2 X

Pack size: **1 x EA**

- Supply Voltage: 24 V dc
- Mounting Type: Panel Mount
- Number of Contacts: 2
- Time Range: 0.1 s → 300 h
- Mode of Operation: ON Delay
- Number of Timer Functions: Single
- Contact Configuration: 2 x SPDT
- Time Increment: Hours, Seconds



1792926 24 V dc

RS PRO PLUG IN SINGLE FUNCTION TIMER RELAY, 24V DC, DPDT, 0.1 →

Pack size: **1 x EA**

- Supply Voltage: 24 V dc
- Mounting Type: Plug In
- Number of Contacts: 2
- Time Range: 0.1 → 3 min
- Mode of Operation: ON Delay
- Number of Timer Functions: Single
- Contact Configuration: DPDT
- Time Increment: Minutes



1792953 24 V dc

RS PRO PLUG IN SINGLE FUNCTION TIMER RELAY, 24V DC, DPDT, 0.1 → 1S

Pack size: **1 x EA**

- Supply Voltage: 24 V dc
- Mounting Type: Plug In
- Number of Contacts: 2
- Time Range: 0.1 → 1 s
- Mode of Operation: ON Delay
- Number of Timer Functions: Single
- Contact Configuration: DPDT
- Time Increment: Seconds



1792947 24 V dc

RS PRO PLUG IN SINGLE FUNCTION TIMER RELAY, 24V DC, DPDT, 0.5 →

Pack size: **1 x EA**

- Supply Voltage: 24 V dc
- Mounting Type: Plug In
- Number of Contacts: 2
- Time Range: 0.5 → 10 s
- Mode of Operation: ON Delay
- Number of Timer Functions: Single
- Contact Configuration: DPDT
- Time Increment: Seconds



1792949 24 V dc

RS PRO PLUG IN SINGLE FUNCTION TIMER RELAY, 24V DC, DPDT, 1 → 30S

Pack size: **1 x EA**

- Supply Voltage: 24 V dc
- Mounting Type: Plug In
- Number of Contacts: 2
- Time Range: 1 → 30 s
- Mode of Operation: ON Delay
- Number of Timer Functions: Single
- Contact Configuration: DPDT
- Time Increment: Seconds



1792950 24 V dc

RS PRO PLUG IN SINGLE FUNCTION TIMER RELAY, 24V DC, DPDT, 0.5 →

Pack size: **1 x EA**

- Supply Voltage: 24 V dc
- Mounting Type: Plug In
- Number of Contacts: 2
- Time Range: 0.5 → 10 min
- Mode of Operation: ON Delay
- Number of Timer Functions: Single
- Contact Configuration: DPDT
- Time Increment: Minutes



1792955 24 V dc

RS PRO PLUG IN SINGLE FUNCTION TIMER RELAY, 24V DC, DPDT, 1 →

Pack size: **1 x EA**

- Supply Voltage: 24 V dc
- Mounting Type: Plug In
- Number of Contacts: 2
- Time Range: 1 → 30 min
- Mode of Operation: ON Delay
- Number of Timer Functions: Single
- Contact Configuration: DPDT
- Time Increment: Minutes



1792956 24 V dc

RS PRO PLUG IN SINGLE FUNCTION TIMER RELAY, 24V DC, 4PDT, 0.5 →

Pack size: **1 x EA**

- Supply Voltage: 24 V dc
- Mounting Type: Plug In
- Number of Contacts: 4
- Time Range: 0.5 → 10 s
- Mode of Operation: ON Delay
- Number of Timer Functions: Single
- Contact Configuration: 4PDT
- Time Increment: Seconds



1792979 24 V dc

RS PRO PLUG IN SINGLE FUNCTION TIMER RELAY, 24V DC, 4PDT, 1 →

Pack size: **1 x EA**

- Supply Voltage: 24 V dc
- Mounting Type: Plug In
- Number of Contacts: 4
- Time Range: 1 → 30 min
- Mode of Operation: ON Delay
- Number of Timer Functions: Single
- Contact Configuration: 4PDT
- Time Increment: Minutes



1792986 24 V dc

RS PRO PLUG IN SINGLE FUNCTION TIMER RELAY, 24V DC, 4PDT, 1 → 30S

Pack size: **1 x EA**

- Supply Voltage: 24 V dc
- Mounting Type: Plug In
- Number of Contacts: 4
- Time Range: 1 → 30 s
- Mode of Operation: ON Delay
- Number of Timer Functions: Single
- Contact Configuration: 4PDT
- Time Increment: Seconds



1792981 24 V dc

RS PRO PLUG IN SINGLE FUNCTION TIMER RELAY, 24V DC, 4PDT, 0.5 →

Pack size: **1 x EA**

- Supply Voltage: 24 V dc
- Mounting Type: Plug In
- Number of Contacts: 4
- Time Range: 0.5 → 10 min
- Mode of Operation: ON Delay
- Number of Timer Functions: Single
- Contact Configuration: 4PDT
- Time Increment: Minutes



1792985 24 V dc

RS PRO CLAMP SINGLE FUNCTION TIMER RELAY, 230V AC, NC, SPNO

Pack size: **1 x EA**

- Supply Voltage: 230 V ac
- Mounting Type: Clamp
- Number of Contacts: 1
- Mode of Operation: Interval
- Number of Timer Functions: Single
- Contact Configuration: NC, SPNO
- Time Increment: Hours, Minutes, Seconds
- Maximum Voltage: 230 V ac



7983444 230 V ac

RS PRO CLAMP SINGLE FUNCTION TIMER RELAY, 10 → 30V DC, NC, SPNO

Pack size: **1 x EA**

- Supply Voltage: 10 → 30 V dc
- Mounting Type: Clamp
- Number of Contacts: 1
- Mode of Operation: Interval
- Number of Timer Functions: Single
- Contact Configuration: NC, SPNO
- Time Increment: Hours, Minutes, Seconds
- Maximum Voltage: 30 V dc



7983448 10 → 30 V dc

RS PRO PANEL MOUNT SINGLE FUNCTION TIMER RELAY, 24V AC/DC,

Pack size: **1 x EA**

- Supply Voltage: 24 V ac/dc
- Mounting Type: Panel Mount
- Number of Contacts: 1
- Mode of Operation: One Shot
- Number of Timer Functions: Single
- Contact Configuration: SPDT
- Time Increment: Hours, Minutes, Seconds
- Maximum Voltage: 24 V ac/dc



8086623 24 V ac/dc

RS PRO PANEL MOUNT SINGLE FUNCTION TIMER RELAY, 230V AC,

Pack size: **1 x EA**

- Supply Voltage: 230 V ac
- Mounting Type: Panel Mount
- Number of Contacts: 1
- Mode of Operation: One Shot
- Number of Timer Functions: Single
- Contact Configuration: SPDT
- Time Increment: Minutes, Seconds
- Maximum Voltage: 230 V ac



8086620 230 V ac

RS PRO DIN RAIL SINGLE FUNCTION TIMER RELAY, 24V AC, SPDT, 0.3 S →

Pack size: **1 x EA**

- Supply Voltage: 24 V ac/dc, 240 V
- Mounting Type: DIN Rail
- Number of Contacts: 1
- Time Range: 0.3 s → 30 h
- Mode of Operation: ON Delay
- Number of Timer Functions: Single
- Contact Configuration: SPDT
- Time Increment: Seconds



8966810 24 V ac/dc, 240 V

TIME RELAY MULTI-FUNCTION 12- 240VAC/DC

Pack size: **1 x EA**

- Supply Voltage: 12 → 240 V ac/dc
- Mounting Type: DIN Rail
- Number of Contacts: 1
- Time Range: 0.1 s → 100 h
- Mode of Operation: Multifunction
- Number of Timer Functions: Multi Function
- Contact Configuration: SPDT
- Time Increment: Hours, Minutes, Seconds



8966813 12 → 240 V ac/dc

RS PRO DIN RAIL SINGLE FUNCTION TIMER RELAY, 24V AC, SPDT, 0.3 S →

Pack size: **1 x EA**

- Supply Voltage: 24 V ac/dc, 110 V ac
- Mounting Type: DIN Rail
- Number of Contacts: 1
- Time Range: 0.3 s → 30 h
- Mode of Operation: ON Delay
- Number of Timer Functions: Single
- Contact Configuration: SPDT
- Time Increment: Seconds



8966816 24 V ac/dc, 110 V

RS PRO DIN RAIL SINGLE FUNCTION TIMER RELAY, 24V AC, SPDT, 0.3 S →

Pack size: **1 x EA**

- Supply Voltage: 24 V ac/dc, 240 V ac
- Mounting Type: DIN Rail
- Number of Contacts: 1
- Time Range: 0.3 s → 30 h
- Mode of Operation: OFF Delay
- Number of Timer Functions: Single
- Contact Configuration: SPDT
- Time Increment: Seconds



8966822 24 V ac/dc, 240 V

ASYMMETRIC RECYCLING TIME RELAY

Pack size: **1 x EA**

- Supply Voltage: 12 → 240 V ac/dc
- Mounting Type: DIN Rail
- Number of Contacts: 1
- Time Range: 0.1 s → 100 h
- Mode of Operation: Asymmetric OFF/ON, Asymmetric ON/OFF
- Number of Timer Functions: Multi Function
- Contact Configuration: SPDT
- Time Increment: Hours, Minutes, Seconds



8966826 12 → 240 V ac/dc

RS PRO DIN RAIL SINGLE FUNCTION TIMER RELAY, 24V AC, SPDT, 0.3 S →

Pack size: **1 x EA**

- Supply Voltage: 24 V ac/dc, 110 V ac
- Mounting Type: DIN Rail
- Number of Contacts: 1
- Time Range: 0.3 s → 30 h
- Mode of Operation: OFF Delay
- Number of Timer Functions: Single
- Contact Configuration: SPDT
- Time Increment: Seconds



8966829 24 V ac/dc, 110 V

RS PRO DIN RAIL SINGLE FUNCTION TIMER RELAY, 240 → 415V AC, 2 X

Pack size: **1 x EA**

- Supply Voltage: 240 → 415 V ac
- Mounting Type: DIN Rail
- Number of Contacts: 2
- Time Range: 3 → 120 s
- Mode of Operation: Star Delta
- Number of Timer Functions: Single
- Contact Configuration: 2 x SPNO
- Time Increment: Seconds



8966832 240 → 415 V ac

RS PRO DIN RAIL SINGLE FUNCTION TIMER RELAY, 115V AC, SPNO, 3 →

Pack size: **1 x EA**

- Supply Voltage: 115 V ac
- Mounting Type: DIN Rail
- Number of Contacts: 2
- Time Range: 3 → 120 s
- Mode of Operation: Star Delta
- Number of Timer Functions: Single
- Contact Configuration: SPNO
- Time Increment: Seconds



8966835 115 V ac

RS PRO DIN RAIL SINGLE FUNCTION TIMER RELAY, 240V AC, SPNO, 3 →

Pack size: **1 x EA**

- Supply Voltage: 240 V ac
- Mounting Type: DIN Rail
- Number of Contacts: 2
- Time Range: 3 → 120 s
- Mode of Operation: Star Delta
- Number of Timer Functions: Single
- Contact Configuration: SPNO
- Time Increment: Seconds



8966838 240 V ac

DPDO TIME RELAY MULTI-RANGE 24- 240VAC/DC

Pack size: **1 x EA**

- Supply Voltage: 24 → 240 V ac/dc
- Mounting Type: DIN Rail
- Number of Contacts: 1
- Time Range: 0.1 s → 120 days
- Mode of Operation: Multifunction
- Number of Timer Functions: Multi Function
- Contact Configuration: SPDT
- Time Increment: Seconds



8966841 24 → 240 V ac/dc

RS PRO DIN RAIL SINGLE FUNCTION TIMER RELAY, 24 → 240V AC/DC,

Pack size: **1 x EA**

- Supply Voltage: 24 → 240 V ac/dc
- Mounting Type: DIN Rail
- Number of Contacts: 2
- Time Range: 0.6 → 600 s
- Mode of Operation: True OFF Delay
- Number of Timer Functions: Single
- Contact Configuration: DPDT
- Time Increment: Seconds



8966844 24 → 240 V ac/dc

DPCO TIME RELAY MULTI-RANGE 24- 240VAC/DC

Pack size: **1 x EA**

- Supply Voltage: 24 → 240 V ac/dc
- Mounting Type: DIN Rail
- Number of Contacts: 2
- Time Range: 0.1 s → 10 h
- Mode of Operation: ON Delay
- Number of Timer Functions: Multi Function
- Contact Configuration: DPDT
- Time Increment: Seconds



8966848 24 → 240 V ac/dc

8 FUNCTION TIME RELAY 24- 240VAC/DC

Pack size: **1 x EA**

- Supply Voltage: 24 → 240 V ac/dc
- Mounting Type: DIN Rail
- Number of Contacts: 1
- Time Range: 0.1 s → 999 h
- Mode of Operation: Multifunction
- Number of Timer Functions: Multi Function
- Contact Configuration: SPDT
- Time Increment: Hours, Minutes, Seconds



8966854 24 → 240 V ac/dc

RS PRO DIN RAIL SINGLE FUNCTION TIMER RELAY, 24 → 240V AC/DC,

Pack size: **1 x EA**

- Supply Voltage: 24 → 240 V ac/dc
- Mounting Type: DIN Rail
- Number of Contacts: 2
- Time Range: 3 → 120 s
- Mode of Operation: Star Delta
- Number of Timer Functions: Single
- Contact Configuration: SPNO
- Time Increment: Seconds



8966857 24 → 240 V ac/dc

RS PRO DIN RAIL MULTI FUNCTION TIMER RELAY, 24 → 240V AC/DC,

Pack size: **1 x EA**

- Supply Voltage: 24 → 240 V ac/dc
- Mounting Type: DIN Rail
- Number of Contacts: 2
- Time Range: 0.1 s → 999 h
- Mode of Operation: Multifunction
- Number of Timer Functions: Multi Function
- Contact Configuration: DPNO
- Time Increment: Hours, Minutes, Seconds



8966860 24 → 240 V ac/dc

18 FUNCTION TIME RELAY 24- 240VAC/DC

Pack size: **1 x EA**

- Supply Voltage: 24 → 240 V ac/dc
- Mounting Type: DIN Rail
- Number of Contacts: 1
- Time Range: 0.1 s → 999 h
- Mode of Operation: Multifunction
- Number of Timer Functions: Multi Function
- Contact Configuration: SPDT
- Time Increment: Hours, Minutes, Seconds



8966863 24 → 240 V ac/dc

RS PRO DIN RAIL MULTI FUNCTION TIMER RELAY, 24 → 240V AC/DC,

Pack size: **1 x EA**

- Supply Voltage: 24 → 240 V ac/dc
- Mounting Type: DIN Rail
- Number of Contacts: 2
- Time Range: 0.1 s → 999 h
- Mode of Operation: Multifunction
- Number of Timer Functions: Multi Function
- Contact Configuration: ZNO
- Time Increment: Hours, Minutes, Seconds



8966866 24 → 240 V ac/dc

RS PRO PANEL MOUNT MULTI FUNCTION TIMER RELAY, 110 → 240V

Pack size: **1 x EA**

- Supply Voltage: 110 → 240 V ac
- Mounting Type: Panel Mount
- Number of Contacts: 2
- Time Range: 0.1 s → 999 days
- Mode of Operation: Multifunction
- Number of Timer Functions: Multi Function
- Contact Configuration: DPDT
- Time Increment: Days, Hours, Minutes, Seconds



8966872 110 → 240 V ac

RS PRO PANEL MOUNT MULTI FUNCTION TIMER RELAY, 110 → 240V

Pack size: **1 x EA**

- Supply Voltage: 110 → 240 V ac
- Mounting Type: Panel Mount
- Number of Contacts: 2
- Time Range: 0.1 s → 999 days
- Mode of Operation: Multifunction
- Number of Timer Functions: Multi Function
- Contact Configuration: DPDT
- Time Increment: Days, Hours, Minutes, Seconds



8966879 110 → 240 V ac

DIG VOLT METER, 48X96, 1PH, 40- 300V AC/DC

Pack size: **1 x EA**

- Current Type: AC
- Number of Digits: 4
- Display Type: LED
- Cutout Height: 43.5 mm
- Cutout Width: 92 mm
- Depth: 68 mm
- Digit Height: 14 mm
- Meter Accuracy: $\pm 0.5 + 1 \text{ Digit } \%$



1365388 AC

RS PRO DIGITAL VOLT METER AC, LED DISPLAY 4-DIGITS $\pm 0.5 + 1 \text{ DIGIT } \%$

Pack size: **1 x EA**

- Current Type: AC
- Number of Digits: 4
- Display Type: LED
- Cutout Height: 92 mm
- Cutout Width: 92 mm
- Depth: 55 mm
- Digit Height: 14 mm
- Meter Accuracy: $\pm 0.5 + 1 \text{ Digit } \%$



1365389 AC

RS PRO DIGITAL VOLT METER AC, LED DISPLAY 4-DIGITS $\pm 0.5 + 1 \text{ DIGIT } \%$

Pack size: **1 x EA**

- Current Type: AC
- Number of Digits: 4
- Display Type: LED
- Cutout Height: 43.5 mm
- Cutout Width: 92 mm
- Depth: 68 mm
- Digit Height: 14 mm
- Meter Accuracy: $\pm 0.5 + 1 \text{ Digit } \%$



1365393 AC

RS PRO DIGITAL VOLT METER AC, LED DISPLAY 4-DIGITS $\pm 0.5 + 1 \text{ DIGIT } \%$

Pack size: **1 x EA**

- Current Type: AC
- Number of Digits: 4
- Display Type: LED
- Cutout Height: 92 mm
- Cutout Width: 92 mm
- Depth: 55 mm
- Digit Height: 14 mm
- Meter Accuracy: $\pm 0.5 + 1 \text{ Digit } \%$



1365394 AC

RS PRO DIGITAL VOLT METER, DIGITAL DISPLAY 4-DIGITS CLASS 1.0, 90 X 90

Pack size: **1 x EA**

- Number of Digits: 4
- Display Type: Digital
- Cutout Height: 90 mm
- Cutout Width: 90 mm
- Depth: 55 mm
- Digit Height: 10 mm
- Meter Accuracy: Class 1.0
- Meter Type: Voltmeter



1797574 4

RS PRO DIGITAL VOLT METER, DIGITAL DISPLAY 4-DIGITS CLASS 1.0, 90 X 90

Pack size: **1 x EA**

- Number of Digits: 4
- Display Type: Digital
- Cutout Height: 90 mm
- Cutout Width: 90 mm
- Depth: 55 mm
- Digit Height: 10 mm
- Meter Accuracy: Class 1.0
- Meter Type: Voltmeter



1797576 4

RS PRO ANALOGUE VOLT METER AC, ANALOGUE DISPLAY 0.01

Pack size: **1 x EA**

- Current Type: AC
- Display Type: Analogue
- Cutout Height: 45 mm
- Cutout Width: 45 mm
- Depth: 54 (≤30 A) mm, 72 (30 → 60 A) mm
- Meter Accuracy: 0.01
- Minimum Temperature: -10 °C
- Maximum Temperature: +65 °C



1862430 AC

RS PRO ANALOGUE VOLTMETER AC, ANALOGUE DISPLAY 0.01

Pack size: **1 x EA**

- Current Type: AC
- Display Type: Analogue
- Cutout Height: 45 mm
- Cutout Width: 45 mm
- Depth: 54 (-30 A) mm, 72 (30 → 60 A) mm
- Meter Accuracy: 0.01
- Minimum Temperature: -10 °C
- Maximum Temperature: +65 °C



1862431 AC

RS PRO ANALOGUE VOLTMETER AC, ANALOGUE DISPLAY 0.01

Pack size: **1 x EA**

- Current Type: AC
- Display Type: Analogue
- Cutout Height: 68 mm
- Cutout Width: 68 mm
- Depth: 66 (100 A) mm
- Meter Accuracy: 0.01
- Minimum Temperature: -10 °C
- Maximum Temperature: +65 °C



1862456 AC

RS PRO ANALOGUE VOLTMETER AC, ANALOGUE DISPLAY 0.01

Pack size: **1 x EA**

- Current Type: AC
- Display Type: Analogue
- Cutout Height: 68 mm
- Cutout Width: 68 mm
- Depth: 66 (100 A) mm
- Meter Accuracy: 0.01
- Minimum Temperature: -10 °C
- Maximum Temperature: +65 °C



1862457 AC

RS PRO ANALOGUE VOLTMETER AC, ANALOGUE DISPLAY 0.01

Pack size: **1 x EA**

- Current Type: AC
- Display Type: Analogue
- Cutout Height: 92 mm
- Cutout Width: 92 mm
- Depth: 66 (100 A) mm
- Meter Accuracy: 0.01
- Minimum Temperature: -10 °C
- Maximum Temperature: +65 °C



1862472 AC

RS PRO ANALOGUE VOLTMETER AC, ANALOGUE DISPLAY 0.01

Pack size: **1 x EA**

- Current Type: AC
- Display Type: Analogue
- Cutout Height: 92 mm
- Cutout Width: 92 mm
- Depth: 66 (100 A) mm
- Meter Accuracy: 0.01
- Minimum Temperature: -10 °C
- Maximum Temperature: +65 °C



1862473 AC

RS PRO DIGITAL VOLTMETER DC, LED DISPLAY 1%

Pack size: **1 x EA**

- Current Type: DC
- Display Type: LED
- Cutout Height: 37 mm
- Cutout Width: 25 mm
- Meter Accuracy: 1%
- Meter Type: Battery Meter



2337810 DC

LEAD-ACID BATTERY INDICATOR, 12/24VDC. D

Pack size: **1 x EA**

- Current Type: DC
- Display Type: LED
- Cutout Height: 27.1 mm
- Cutout Width: 32 mm
- Meter Accuracy: 1%
- Meter Type: Battery Meter



2337811 DC

AC VOLTMETER 48X48MM 90 DEG SCALE 300V

Pack size: **1 x EA**

- Current Type: AC
- Cutout Height: 46 mm
- Cutout Width: 46 mm
- Depth: 39 mm
- Meter Accuracy: 1.5 %
- Minimum Temperature: -25 °C
- Meter Type: Voltmeter
- Maximum Temperature: +50 °C



9010514 AC

AC VOLTMETER 72X72MM 90 DEG SCALE 500V

Pack size: **1 x EA**

- Current Type: AC
- Cutout Height: 68 mm
- Cutout Width: 68 mm
- Depth: 36.5 mm
- Meter Accuracy: ±1.5 %
- Minimum Temperature: -25 °C
- Meter Type: Voltmeter
- Maximum Temperature: +50 °C



9010520 AC

AC VOLTMETER 48X48MM 90 DEG SCALE 500V

Pack size: **1 x EA**

- Current Type: AC
- Cutout Height: 46 mm
- Cutout Width: 46 mm
- Depth: 39 mm
- Meter Accuracy: 1.5 %
- Minimum Temperature: -25 °C
- Meter Type: Voltmeter
- Maximum Temperature: +50 °C



9010523 AC

RS PRO ANALOGUE VOLTMETER AC ±1.5 %, 68 X 68 MM

Pack size: **1 x EA**

- Current Type: AC
- Cutout Height: 68 mm
- Cutout Width: 68 mm
- Depth: 36.5 mm
- Meter Accuracy: ±1.5 %
- Minimum Temperature: -25 °C
- Meter Type: Voltmeter
- Maximum Temperature: +50 °C



9010526 AC

AC VOLTMETER 96X96MM 90 DEG SCALE 500V

Pack size: **1 x EA**

- Current Type: AC
- Cutout Height: 92 mm
- Cutout Width: 92 mm
- Depth: 45 mm
- Meter Accuracy: ±1.5 %
- Minimum Temperature: -25 °C
- Meter Type: Voltmeter
- Maximum Temperature: +50 °C



9010532 AC

AC VOLTMETER 96X96MM 90 DEG SCALE 300V

Pack size: **1 x EA**

- Current Type: AC
- Cutout Height: 92 mm
- Cutout Width: 92 mm
- Depth: 45 mm
- Meter Accuracy: ±1.5 %
- Minimum Temperature: -25 °C
- Meter Type: Voltmeter
- Maximum Temperature: +50 °C



9010539 AC

RS PRO ANALOGUE VOLTMETER DC ±1.5 %, 68 X 68 MM

Pack size: **1 x EA**

- Current Type: DC
- Cutout Height: 68 mm
- Cutout Width: 68 mm
- Depth: 36.5 mm
- Meter Accuracy: ±1.5 %
- Minimum Temperature: -25 °C
- Meter Type: Voltmeter
- Maximum Temperature: +50 °C



9010542 DC

DC VOLTMETER 48X48MM 90 DEG SCALE 150V

Pack size: **1 x EA**

- Current Type: DC
- Cutout Height: 46 mm
- Cutout Width: 46 mm
- Depth: 39 mm
- Meter Accuracy: 1.5 %
- Minimum Temperature: -25 °C
- Meter Type: Voltmeter
- Maximum Temperature: +50 °C



9010548 DC

DC VOLTMETER 72X72MM 90 DEG SCALE 40V

Pack size: **1 x EA**

- Current Type: DC
- Cutout Height: 68 mm
- Cutout Width: 68 mm
- Depth: 36.5 mm
- Meter Accuracy: ±1.5 %
- Minimum Temperature: -25 °C
- Meter Type: Voltmeter
- Maximum Temperature: +50 °C



9010551 DC

RS PRO ANALOGUE VOLTMETER DC
±1.5 %, 68 X 68 MM

Pack size: 1 x EA

- Current Type: DC
- Cutout Height: 68 mm
- Cutout Width: 68 mm
- Depth: 36.5 mm
- Meter Accuracy: ±1.5 %
- Minimum Temperature: -25 °C
- Meter Type: Voltmeter
- Maximum Temperature: +50 °C



9010554 DC

RS PRO ANALOGUE VOLTMETER DC
±1.5 %, 92 X 92 MM

Pack size: 1 x EA

- Current Type: DC
- Cutout Height: 92 mm
- Cutout Width: 92 mm
- Depth: 45 mm
- Meter Accuracy: ±1.5 %
- Minimum Temperature: -25 °C
- Meter Type: Voltmeter
- Maximum Temperature: +50 °C



9010558 DC

RS PRO ANALOGUE VOLTMETER DC
±1.5 %, 90.5 X 90.5 MM

Pack size: 1 x EA

- Current Type: DC
- Cutout Height: 90.5 mm
- Cutout Width: 90.5 mm
- Depth: 45 mm
- Meter Accuracy: ±1.5 %
- Minimum Temperature: -25 °C
- Meter Type: Voltmeter
- Maximum Temperature: +50 °C



9010560 DC

RS PRO ANALOGUE VOLTMETER DC
±1.5 %, 92 X 92 MM

Pack size: 1 x EA

- Current Type: DC
- Cutout Height: 92 mm
- Cutout Width: 92 mm
- Depth: 45 mm
- Meter Accuracy: ±1.5 %
- Minimum Temperature: -25 °C
- Meter Type: Voltmeter
- Maximum Temperature: +50 °C



9010567 DC



Contact us to learn more:

Orders:

orders.ph@rs-components.com

Enquiries:

customerserviceph@rs-components.com

Technical Support:

tech.PH@rs-components.com

Office Location:

RS Components Corporation
21/F Multinational Bancorporation Centre
6805 Ayala Avenue, Makati City

Order line:

+632 8888 4030

