

# DH-PFS3008-8GT-L

8-Port Unmanaged Gigabit Switch



- Supports eight 10/100/1000 Mbps adaptive ports.
- Small and light, it is easy to carry and has multiple chips embedded in it.
- · Easy to operate.









# **System Overview**

The Device is a layer-2 commercial switch. It has a high-performance switching engine and a large buffer memory to ensure smooth video stream transmission. With a full-metal and fanless design, the Device features great heat dissipation capability on the shell surface. The Device is an unmanaged switch, so it does not need to be configured through web interface, which simplifies installation.

#### **Functions**

### **Robust Design**

Built to last, the architecture of the switch makes it highly reliable, operating with high-efficiency non-stop.

#### **Plug and Play**

Hassle-free, it does not require any configuration. Simply use after it is powered on.

#### **Optimized Performance**

All ports can transmit streams at high speeds without delay.

#### **Easy Installation**

Both desktop and wall mount installation are supported, making it suitable for a wide variety of scenarios.

## Scene



Home



Shop








Meeting Room

#### **Specification** Hardware Included Power Adapter Yes **Ethernet Port** 8 10/100/1000 Mbps **Ethernet Port Speed** Description of Function Port 1–8: 8 × 10/100/1000 Base-T Slots 5 VDC; 1 A **Power Supply** Operating Temperature 0 °C to +45 °C (+32 °F to +113 °F) Operating Humidity 5%-95% (RH) Storage Temperature -40 °C to +70 °C (-40 °F to +158 °F) Storage Humidity 5%-95% (RH) Idling: 0.5 W; **Power Consumption** Full load: 3.0 W Performance MTBF 576.29 years **Switching Capacity** 16 Gbit Packet Forwarding Rate 11.904 Mpps 768 kbit Packet Buffer Size MAC Table Size 2K General Air discharge: 8 kV **Statics Protection** Contact discharge: 4 kV **Lighting Protection** Common mode: 2 kV Net Weight 0.16 kg (0.35 lb) Gross Weight 0.29 kg (0.64 lb) 132.9 mm × 62.4 mm × 24.0 mm **Product Dimensions** (5.23" × 2.46" × 0.94") 136.0 mm × 55.0 mm × 153.0 mm **Packaging Dimensions** (5.35" × 2.17" × 6.02") Casing Material Plastic Installation Desktop mount

CE; FCC

# Dimensions (mm[inch])









Certifications