

DHI-SSD-C800A 2.5 inch SATA Solid State Drive



Adopts high-quality wafer level chip

- Supports SATA III protocol with transmission speed up to 550 MB/s
- View information through S.M.A.R.T
- $\boldsymbol{\cdot}$ Provides better read and write performance with TRIM and NCQ
- Low power consumption management

System Overview

As a new generation of 2.5 inch SSD product launched by Dahua, C800A series adopts high-quality 3D wafer level chip and high-performance controller. It is consumer-grade solid state drive designed for personal desktops and notebooks. The product can process data efficiently and ensure quick start-ups. In multi-tasking, it can ensure high speed and stability.

Scene

C800A series is standard 2.5 inch consumer-grade solid state drive which is applicable to personal desktops, notebooks, all-in-one computers, and more.

Technical Specification				
Product Model	DHI-SSD- C800AS120G	DHI-SSD- C800AS240G	DHI-SSD- C800AS480G	DHI-SSD- C800AS500G
Capacity ¹	120 GB	240 GB	480 GB	500 GB
Form Factor	2.5 inch			
Port	SATA III 6Gb/s			
Net Weight	Max 40 g (0.09 lb)			
Product Dimensions	100.20 mm × 69.90 mm × 7.00 mm (3.94" × 2.75" × 0.28")			
Packaging Dimensions	140.50 mm × 105.50 mm × 15.50 mm (5.53" × 4.15" × 0.61")			
Memory Component	3D NAND			
Power Consumption	1195 mW (max) 415 mW (idle)	1200 mW (max) 370 mW (idle)	1600 mW (max) 510 mW (idle)	1910 mW (max) 790 mW (idle)
S.M.A.R.T	Support			
TRIM	Support			
Garbage Collection	Support			

Sequential Read ²	Up to 500 MB/s	Up to 500 MB/s	Up to 530 MB/s	Up to 530 MB/s
Sequential Write ²	Up to 400 MB/s	Up to 450 MB/s	Up to 470 MB/s	Up to 500 MB/s
MTBF	1,500,000 hours			
Operating Temperature	0°C to +70°C (+32°F to +158°F)			
Storage Temperature	-40°C to +85°C (-40°F to +185°F)			
Operating Humidity	5%–95% (non-condensing)			
Vibration Resistance	10-200Hz, 0.5G			
TBW	Up to 50 TB	Up to 100 TB	Up to 150 TB	Up to 200 TB
Warranty ³	3-year limited warranty	3-year limited warranty	3-year limited warranty	5-year limited warranty
Reference Information	 Capacity calculation: 1GB = 1 billion bytes (IDEMA). Actual available capacity might be reduced (due to formatting, partition, operating system applications, or other necessary usage). System configuration of performance test: Intel Z390 Chipset, Intel Core i9-9900KF@3.6GHz, 16GB DDR4; operating system-Windows 10 x64; testing tool-CrystalDiskMark 6.0.0. Warranty period or maximum write amount (TBW), whichever comes first. High performance SLC cache has been enabled. (*Above data based on internal testing of Dahua Memory Laboratory) 			

C800 Series | DHI-SSD-C800A

Technical Specification Product DHI-SSD-DHI-SSD-DHI-SSD-Model C800AS960G C800AS1000G C800AS2000G Capacity¹ 960 GB 1000 GB 2000 GB Form Factor 2.5 inch SATA III 6Gh/c Port Net Pro Din Pad

Ordering Information				
Туре	Model	Description		
	DHI-SSD-C800AS120G	Dahua 2.5 inch SATA Solid State Drive 120G Dramless 0~70°C		
	DHI-SSD-C800AS240G	Dahua 2.5 inch SATA Solid State Drive 240G Dramless 0~70°C		
	DHI-SSD-C800AS480G	Dahua 2.5 inch SATA Solid State Drive 480G Dramless 0~70°C		
C800 Series	DHI-SSD-C800AS500G	Dahua 2.5 inch SATA Solid State Drive 500G Dramless 0~70°C		
	DHI-SSD-C800AS960G	Dahua 2.5 inch SATA Solid State Drive 960G Dramless 0~70°C		
	DHI-SSD-C800AS1000G	Dahua 2.5 inch SATA Solid State Drive 1000G Dramless 0~70°C		
	DHI-SSD-C800AS2000G	Dahua 2.5 inch SATA Solid State Drive 2000G Dramless 0~70°C		

Installation





Dimensions (mm[inch])







(**jeninim**, **pini**k)

Port	SATA III 6Gb/s			
Net Weight	Max 40 g (0.09 lb)			
Product Dimensions	100.20 mm × 69.90 mm × 7.00 mm (3.94" × 2.75" × 0.28")			
Packaging Dimensions	140.50 mm × 105.50 mm × 15.50 mm (5.53" × 4.15" × 0.61")			
Memory Component	3D NAND			
Power Consumption	2200 mW (max) 550 mW (idle)	1960 mW (max) 840 mW (idle)	2500 mW (max) 960 mW (idle)	
S.M.A.R.T	Support			
TRIM	Support			
Garbage Collection	Support			
Sequential Read ²	Up to 550 MB/s	Up to 550 MB/s	Up to 550 MB/s	
Sequential Write ²	Up to 490 MB/s	Up to 500 MB/s	Up to 460 MB/s	
MTBF	1,500,000 hours			
Operating Temperature	0°C to +70°C (+32°F to +158°F)			
Storage Temperature	-40°C to +85°C (-40°F to +185°F)			
Operating Humidity	5%–95% (non-condensing)			
Vibration Resistance	10-200 Hz, 0.5G			
TBW	Up to 310 TB	Up to 400 TB	Up to 800 TB	
Warranty ³	5-year limited warranty			
Reference Information	 Capacity calculation: 1GB = 1 billion bytes (IDEMA). Actual available capacity might be reduced (due to formatting, partition, operating system applications, or other necessary usage). System configuration of performance test: Intel Z390 Chipset, Intel Core i9-9900KF@3.6GHz, 16GB DDR4; operating system-Windows 10 x64; testing tool-CrystalDiskMark 6.0.0. Warranty period or maximum write amount (TBW), whichever 			

Rev 002.000 © 2022 Dahua. All rights reserved. Design and specifications are subject to change without notice. The images, specifications and information mentioned in the document are only for reference, and might differ from the actual product.

3. Warranty period or maximum write amount (TBW), whichever

(*Above data based on internal testing of Dahua Memory Laboratory)

4. High performance SLC cache has been enabled.

comes first.