

DH-PFM350-480-110-A

600VA/480W Line-interactive UPS



Features

- Amplio rango de tensión de entrada: AC81~145V o AC140~290V, cumplen los requisitos en diferentes partes para la fluctuación de la red eléctrica.
- AVR Boost y Buck para estabilizar la tensión.
- Carga en modo desactivado, función de arranque en frío y protección total.
- Alimentación continua para evitar la pérdida de datos.
- Tamaño compacto.

Technical Specifications

Model	DH-PFM350-480				
Plug type	European	British	Australian	Indian	North American
Capacity	600VA/480W				
Input					
Rated voltage	220Vac~240Vac			110Vac~120Vac	
Voltage range	140Vac~290Vac			81Vac~145Vac	
Rated frequency range	50Hz or 60Hz				
Power factor	0.6				
Output					
Voltage	220/230/240 VAC			110/120 VAC	
AC Voltage Regulation (Batt. Mode)	±10%				
Frequency Range (Batt. Mode)	50Hz or 60Hz ±1Hz				
Transfer Time	2-6ms				
Waveform (Batt. Mode)	Simulated sinewave				
Battery					
Battery type & number	12 V/7 Ah x 1				
Typical recharge time	4 hours recover to 90% capacity				
Charging voltage	13.7V±1%				
Indicators					
Battery mode	Green lighting				
AC mode	Green lighting				
Alarm					
Battery mode	Sounding every 10 seconds				
Low battery	Sounding every second				
Overload	Sounding every 0.5 second				
Fault	Continuously sounding				
Protection					
Full protection	Overload, discharge and overcharge protection				
Environmental					
Operating temperature	0°C ~ +40°C (+32°F ~ +104°F)				
Operating humidity	0~90% RH(non-condensing)				
Altitude range	<1000m(3280.84ft)				
Construction					
Color	Black				
Noise level	<40dB				
Dimensions	279mmx101mmx142mm(10.98"x3.98"x5.59")				
Weight	4.25kg(9.37lb)				

Order Information

Type	Part Number	Description
Power Series	DH-PFM350-480	Uninterruptible Power Supply(UPS) _Dahua brand, Line-interactive
	DH-PFM350-900	Uninterruptible Power Supply(UPS) _Dahua brand, Line-interactive
	DH-PFM351-900	Uninterruptible Power Supply(UPS) _Dahua brand, Smart online

Package Information

- Uninterruptible Power Supply(UPS) DH-PFM350-360 *1
- Installation Instruction *1