### Ruijie | Reyce

# RG-EW1300G 1300M Wi-Fi 5 Dual-band Gigabit Mesh Router

DATASHEET



#### Highlights

- 802.11ac wave2
- Five omnidirectional & foldable antennas providing strong Wi-Fi signals
- Full coverage, easy setup, and seamless roaming
- 96 concurrent connections
- Easy network management at your fingertips with Reyee Router App

### Highlight Features



#### AC1300 Dual Band WiFi Meets your Smooth Networks Needs

You can effortlessly connect multiple devices and enjoy seamless streaming using the dual 2.4GHz and 5GHz bands.



#### **Concurrently Support Multiple Devices Connection**

Dual-Band integration together with the MU-MIMO technology offer low interference and fast speed internet to up to 96 terminals simultaneously.









### Highlight Features





#### Take Control of Your Home Network at Fingertips

Set up your home network in **Reyee Router App** in two minutes. More **Life-time Free** functions are waiting for you to Explore.Experience,Expect.

Parental

Control

Remote Management Parental Control



Getificon Google Play

## Specifications

Model	RG-EW1300G
	Basic
Dimensions (W×D×H)	230 mm × 130 mm × 30 mm (9.06 in. × 5.12 in. × 1.18 in. antennas not included)
Weight	0.29 kg (packages not included)
Wi-Fi Standards	Wi-Fi 5 (802.11ac)
МІМО	2.4 GHz, 2×2, MU-MIMO 5 GHz, 2×2, MU-MIMO
Max. Wi-Fi Speed	2.4 GHz: 400 Mbps 5 GHz: 867 Mbps
Channel Width	2.4 GHz: Auto/20/40 MHz 5 GHz: Auto/20/40/80MHz
Antennas	5
Antennas Type	External Omnidirectional
Antennas Gain	2.4 GHz: 4.5 dBi 5 GHz: 5.5 dBi
WAN Port	1×10/100/1000 Base-T
LAN Ports	3×10/100/1000 Base-T
Recommended Users	32
Max. Users	96
Power Supply	DC 12V/1.0A
Power Consumption	< 12 W
<b>Operation Frequency Bands</b>	802.11b/g/n: 2.400 GHz to 2.483 GHz 802.11a/n/ac: 5.150 GHz to 5.350 GHz 802.11a/n/ac: 5.470 GHz to 5.725 GHz , 5.725 GHz to 5.850 GHz country-specific restrictions apply
Transmit Power	General: CE EIRP: ≤20dBm (2.4GHz) ≤27dBm (5GHz)

Model	RG-EW1300G
	Myanmar: $2400~2483.5MHz \leq 20dBm(EIRP);$ $5150~5350MHz \leq 23dBm(EIRP);$ $5470~5725MHz \leq 30dBm(EIRP);$ $5725~5850MHz \leq 30dBm(EIRP);$
Receive Sensitivity	2.4 GHz:20MHz 802.11b: -91.5 dBm(1 Mbps) 802.11g: -88.5 dBm(6 Mbps), -71 dBm(54 Mbps) 802.11n: -88dBm(MCS0), -69 dBm(MCS7) 5 GHz:20MHz 802.11n: -92 dBm(MCS0), -71 dBm(MCS7) 802.11a: -89 dBm(6 Mbps), -74 dBm(54 Mbps) 802.11ac: -89dBm(MCS0), -65dBm(MCS8)
Operating Temperature	-10 °C to +40 °C (14 °F to 104 °F)
Operating Humidity	5% to 95% Noncondensing
Certifications	CE
Wireless	
OFDMA	-
MU-MIMO	Support
BSS Coloring	-
Maximum Number of SSIDs	6
SSID Hiding	Support
Band Steering	Support
Guest Wi-Fi	Support
WPA/WPA2	Support
WPA3	Support
Roaming	Layer 2 Roaming
Blacklist	Support

Model	RG-EW1300G	
Mesh Pairing by Hardware	Support	
Mesh Pairing by Mesh Button	Support	
Mesh Pairing by Eweb	Support	
Recommended Hop Count	≪5	
Wi-Fi Optimization	Support	
QoS (WMM)	Support	
WPS	-	
Transmission Power Adjustment	Support	
Hardware		
СРИ	MT7621DA	
Flash	16 MB	
RAM/SDRAM	128 M Byte	
Color	Black	
System LED Indicator	Support	
Reyee Mesh LED Indicator	Support	
Reyee Mesh Button	Support	
Power Button	-	
Reset Button	Support	
DC Connector Dimensions	Outer Diameter: 5.5 mm Inner Diameter: 2.1 mm Length: 9.0 mm (Outer Diameter: 0.22 in. Inner Diameter: 0.08 in. Length: 0.354 in. )	
WAN		
Static IP	Support	
DHCP	Support	

Model	RG-EW1300G	
РРРоЕ	Support	
Learning PPPoE Account & Password	Support	
VLAN Tagging	Support	
LAN		
DHCP Server	Support	
Client List	Support	
Static IP Assignment	Support	
Port-Based Flow Control	Support	
Features		
TR069	Support	
IPv6	Support	
DDNS	Support	
IPTV	Support	
Alarm	Support	
Diagnosis	Support	
UPnP	Support	
ARP Binding	Support	
Port Mapping	Support	
DMZ Host	Support	
Rate Limitation of Terminals	Support	
Hardware Acceleration	Support	
MAC Address Cloning	Support	
Cloud Management	Support	
Repeater Mode	Support	
WISP Mode	Support	

Model	RG-EW1300G	
	Security	
PPTP VPN Server	-	
PPTP VPN Client	Support	
L2TP VPN Client	-	
Parental Control	Time Schedule	
Protect TCP Flood Attacks	Support	
Protect ICMP Attacks	-	
Protect UDP Flood Attacks	-	
System		
Default Access/Password	192.168.110.1 No Password Required by Default	
URL Access	Support	
Local Upgrade	Support	
Online Upgrade	Support	
APP Upgrade	Support	
Syslog	Support	
Backup	Support	
Factory Reset	Support	
Language	Chinese English Vietanmese Turkish Indonesian Thai traditioanl Chinese Spanish Russian Arabic	

Model	RG-EW1300G
	Czech Italian
	Package Contents
Package Information	RG-EW1300G
Wireless Router	1
Power Adapter	1
Quick Start Guide	1
Warranty Card	1
Cat5E UTP Cable	1

### Rujje Rcycc

Redefine your easy network

**Copyright** ©2000-2024 Ruijie Networks Co., Ltd. All rights reserved. No part of this document may be reproduced or transmitted in any form or any means without prior written consent of Ruijie Networks Co., Ltd.

#### Notice

This content is applicable only to regions outside the China mainland. Ruijie Networks Co., Ltd. reserves the right to interpret this content.

The information contained herein is subject to change without notice. Nothing herein should be construed as constituting an additional warranty. Ruijie Networks Co., Ltd. shall not be liable for technical or editorial errors or omissions contained herein.



Ruijie Networks Co., Ltd. Website: https://reyee.ruijie.com/en-global