Ruijie | Reyce

RG-EW3000GX PRO 3000M Wi-Fi 6 Dual-Band Gigabit Mesh Router

DATASHEET



Highlights

- Next-generation gigabit Wi-Fi 6 standard
- WAN aggregation
- Gaming engine providing unrivalled gaming experience
- Strong signals received
- Exclusive Reyee mesh providing whole-home Wi-Fi coverage
- Control of your home network at your fingertips



2X Capacity, 3X Faster

Ultra-fast Wi-Fi 6 design with **160MHz** channel and a concurrent data rate of up to 3000 Mbps. **Two** 1 Gbps broadband connections with a combined rate of up to **1.6 Gbps**. With MU-MIMO and BSS coloring technology, all your devices get their fair share of the WiFi bandwidth.





RG-EW3000GX PRO features WAN aggregation, delivering ultra-fast gigabit wired speed. You canenjoy a 2 Gbps wired speed from your modems all the way to your PC and gaming console.

Accelerated Wired Connection



Lag-free Gaming Experience While

wnloading Thre

Multiplayers

Wi-Fi QoS, Reyee self-developed technology, automatically classify the game frames into the highest-priority transmission queue, ensuring high stability in up to 10 multi-players.











Take Control of Your Home Network at Fingertips

Set up your home network in **Reyee Router App** in two minutes. More **Life-time Free** functions are waiting for you to Explore, Experience, and Expect.

2

Parental

Control









Google Play



Specifications

Model	RG-EW3000GX PRO	
Basic		
Dimensions (W×D×H)	260 mm × 140 mm × 30 mm (10.24 in. × 5.51 in. × 1.18 in. antennas not included)	
Weight	0.48 kg (packages not included)	
Wi-Fi Standards	Wi-Fi 6 (802.11ax)	
МІМО	2.4 GHz, 2×2, MU-MIMO 5 GHz, 2×2, MU-MIMO	
Max. Wi-Fi Speed	2.4 GHz: 574 Mbps 5 GHz: 2402 Mbps	
Channel Width	2.4 GHz: Auto/20/40 MHz 5 GHz: Auto/20/40/80/160/MHz	
Antennas	5	
Antennas Type	External Omnidirectional	
Antenna Gain	2.4 GHz: 5 dBi 5 GHz: 5 dBi	
Ports	1×10/100/1000 Base-T WAN/LAN	
	1×10/100/1000 Base-T WAN	
	2×10/100/1000 Base-T LAN	
Recommended Users	60	
Max. Users	192	
Power Supply	DC 12V/1.5A	
Power Consumption	< 18 W	
Operation Frequency Bands	802.11b/g/n/ax: 2.400 GHz to 2.483 GHz 802.11a/n/ac/ax: 5.150 GHz to 5.350 GHz 802.11a/n/ac/ax: 5.470 GHz to 5.725 GHz , 5.725 GHz to 5.850 GHz country-specific restrictions apply	
DFS	Support	

Transmit Power	General:CE EIRP: \leq 20dBm (2.4GHz) \leq 27dBm (5GHz) \leq 20dBm 2400~2483.5MHzMyanmar:2400~2483.5MHz \leq 20dBm(EIRP);5150~5350MHz \leq 23dBm(EIRP);5470~5725MHz \leq 30dBm(EIRP);5725~5850MHz \leq 30dBm(EIRP);
Receive Sensitivity	2.4 GHz:20MHz 802.11b: -91 dBm(1 Mbps) 802.11g: -91 dBm(6 Mbps), -72 dBm(54 Mbps) 802.11n: -90dBm(MCS0), -70 dBm(MCS7) 5 GHz:20MHz 802.11n: -85 dBm(MCS0), -67 dBm(MCS7) 802.11a: -89 dBm(6 Mbps), -72 dBm(54 Mbps) 802.11ac: -90dBm(MCS0), -63dBm(MCS8) 802.11ax: -88dBm(MCS0), -62dBm(MCS8), -58dBm(MCS11)
Operating Temperature	-10 °C to +40 °C (14 °F to 104 °F)
Operating Humidity	5% to 95% Noncondensing
Wireless	
OFDMA	-
MU-MIMO	Support
MU-MIMO BSS Coloring	Support Support
BSS Coloring	Support
BSS Coloring Maximum Number of SSIDs	Support 6
BSS Coloring Maximum Number of SSIDs SSID Hiding	Support 6 Support
BSS Coloring Maximum Number of SSIDs SSID Hiding Band Steering	Support 6 Support Support
BSS Coloring Maximum Number of SSIDs SSID Hiding Band Steering Guest Wi-Fi	Support 6 Support Support Support
BSS ColoringMaximum Number of SSIDsSSID HidingBand SteeringGuest Wi-FiWPA/WPA2	Support 6 Support Support Support Support
BSS ColoringMaximum Number of SSIDsSSID HidingBand SteeringGuest Wi-FiWPA/WPA2WPA3	Support G Support Support Support Support

Reyee Mesh	Support
Mesh Pairing by Hardware	Support
Mesh Pairing by Mesh Button	Support
Mesh Pairing by Eweb	Support
Recommended Hop Count	≤5
Wi-Fi Optimization	Support
QoS (WMM)	Support
WPS	-
Transmission Power Adjustment	Support
Hardware	
CPU	MT7981
Flash	128 MB
RAM/SDRAM	256 MB
Color	Black
System LED Indicator	Support
Reyee Mesh LED Indicator	Support
Reyee Mesh Button	Support
Power Button	-
Reset Button	Support
DC Connector Dimensions	Outer Diameter: 5.5 mm Inner Diameter: 2.1 mm Length: 9.5 mm (Outer Diameter: 0.22 in. Inner Diameter: 0.08 in. Length: 0.37 in.)
WAN	
Static IP	Support
DHCP	Support

РРРоЕ	Support	
Learning PPPoE Account & Password	Support	
VLAN Tagging	Support	
LAN		
DHCP Server	Support	
Client List	Support	
Static IP Assignment	Support	
Port-Based Flow Control	Support	
Features		
TR069	Support	
IPv6	Support	
DDNS	Support	
ΙΡΤΥ	Support	
Alarm	Support	
Diagnosis	Support	
UPnP	Support	
ARP Binding	Support	
Port Mapping	Support	
DMZ Host	Support	
Rate Limitation of Terminals	Support	
Hardware Acceleration	Support	
MAC Address Cloning	Support	
Cloud Management	Support	
Repeater Mode	Support	
WISP Mode	Support	
Security		

PPTP VPN Server	Support
PPTP VPN Client	Support
L2TP VPN Client	-
Parental Control	Time Schedule
Protect TCP Flood Attacks	Support
Protect ICMP Attacks	-
Protect UDP Flood Attacks	-

System

System	
Default Access/Password	192.168.110.1 No Password Required by Default
URL Access	Support
Local Upgrade	Support
Online Upgrade	Support
APP Upgrade	Support
Syslog	Support
Backup	Support
Factory Reset	Support
Language	Chinese English Vietanmese Turkish Indonesian Thai traditioanl Chinese Spanish Russian Arabic Ukrainian Czech

Package Contents

Package Information	RG-EW3000GX PRO
Wireless Router	1
Power Adapter	1
Quick Installation Guide	1
Warranty Card	1
Cat5E UTP Cable	1

Rujje Rcycc

Redefine your easy network

Copyright ©2000-2024 Ruijie Networks Co., Ltd. All rights reserved. No part of this document may be reproduced or transmitted in any form or any means without prior written consent of Ruijie Networks Co., Ltd.

Notice

This content is applicable only to regions outside the China mainland. Ruijie Networks Co., Ltd. reserves the right to interpret this content.

The information contained herein is subject to change without notice. Nothing herein should be construed as constituting an additional warranty. Ruijie Networks Co., Ltd. shall not be liable for technical or editorial errors or omissions contained herein.



Ruijie Networks Co., Ltd. Website: https://reyee.ruijie.com/en-global