Ruíjie | Reyce

RG-EW1200G PRO 1267Mbps Dual-band Gigabit Wireless Router

DATASHEET



Highlights

- Support 802.11ac wave2
- 6 Omnidirectional antennas with signal amplifiers extend and concentrate the Wi-Fi signals
- MU-MIMO technology, concurrently support 96 devices connection
- Reyee Mesh is your full space coverage Wi-Fi solution
- Easy network management at your fingertips with Reyee Router App



RG-EW1200G PRO

Enjoy Family Moment with a Superior Internet

It's our mission to provide you high-quality online moment.





Strong WiFi Signal Throughout Your Home





Highlight Features

Good Helper for Your Family Management

Parental Control Health Mode

Ruijie Cloud App allows you to manage the internet access authority of the specified terminal, including the time limit, URL blocking and black/white list setup.

Parental Control Health Mode

The health mode limits the radiation exposure and blacks out the indicator lights for you to have a good sleep.



Concurrently Support Multiple Devices Connection

Dual-Band integration together with the MU-MIMO technology offer low interference and fast speed internet to up to 96 terminals simultaneously.





Specifications

Basic	
Dimensions (W×D×H)	220 mm x 140 mm x 36 mm (8.67 in. × 5.51 in. × 1.42 in. antennas not included)
Weight	0.55 kg (packages not included)
Wi-Fi Standards	Wi-Fi 5 (802.11ac)
MIMO	2.4 GHz, 2×2, MU-MIMO 5 GHz, 2×2, MU-MIMO
Max. Wi-Fi Speed	2.4 GHz: 400 Mbps 5 GHz: 867 Mbps
Channel Width	2.4 GHz: Auto/20/40 MHz 5 GHz: Auto/20/40/80 MHz
Antennas	6
Antennas Type	External Omnidirectional
Antenna Gain	2.4 GHz: 6 dBi 5 GHz: 6 dBi
WAN Port	1×10/100/1000 Base-T Port
LAN Ports	3×10/100/1000 Base-T Ports
Recommended Users	32
Max. Users	96
Power Supply	DC 12V/1.5A
Power Consumption	≤15W
Operation Frequency Bands	802.11b/g/n: 2.400 GHz to 2.483 GHz 802.11a/n/ac: 5.150 GHz to 5.350 GHz 802.11a/n/ac: 5.470 GHz to 5.725 GHz , 5.725 GHz to 5.850 GHz country-specific restrictions apply
DFS	\checkmark
Transmit Power	Regular: CE EIRP: ≤20 dBm (2.4 GHz) ≤27 dBm (5 GHz)
Operating Temperature	0 °C to +45 °C (32 °F to 113 °F)
Operating Humidity	5% to 95% Noncondensing
Certifications	CE,RoHS

Specifications

	Wireless
OFDMA	-
MU-MIMO	\checkmark
BSS Coloring	-
Maximum Number of SSIDs	6
SSID Hiding	\checkmark
Band Steering	\checkmark
Guest Wi-Fi	\checkmark
WPA/WPA2	\checkmark
WPA3	-
Roaming	Layer 2 Roaming Roaming with 802.11k and 802.11v
Blacklist	\checkmark
Reyee Mesh	\checkmark
Mesh Pairing by Hardware	\checkmark
Mesh Pairing by Mesh Button	\checkmark
Mesh Pairing by Eweb	\checkmark
Recommended Hop Count	<2
Wi-Fi Optimization	\checkmark
QoS (WMM)	\checkmark
WPS	-
Transmission Power Adjustment	\checkmark
DFS	\checkmark
Hardware	
CPU	MT7621
Flash	16 MB



	Hardware
RAM/SDRAM	128 MB
Color	Black
System LED Indicator	\checkmark
Reyee Mesh LED Indicator	-
Reyee Mesh Button	\checkmark
Power Button	-
Reset Button	\checkmark
DC Connector Dimensions	5.5 mm x 2.1 mm x 9 mm (0.22 in. × 0.08 in. × 0.35 in. antennas not included)
WAN	
Static IP	\checkmark
DHCP	\checkmark
PPPoE	\checkmark
Learning PPPoE Account & Password	\checkmark
VLAN Tagging	\checkmark
LAN	

DHCP Server	\checkmark
Client List	\checkmark
Static IP Assignment	\checkmark
Port-Based Flow Control	\checkmark

Features	
TR069	\checkmark
Preset	\checkmark
IPv6	\checkmark
DDNS	\checkmark

Specifications

	Features
IPTV	\checkmark
Alarm	\checkmark
Diagnosis	\checkmark
UPnP	\checkmark
ARP Binding	\checkmark
Port Mapping	\checkmark
DMZ Host	\checkmark
Rate Limitation of Terminals	\checkmark
Hardware Acceleration	\checkmark
MAC Address Cloning	\checkmark
Cloud Management	\checkmark
Repeater Mode	\checkmark
WISP Mode	\checkmark
	Security
PPTP VPN Server	-
PPTP VPN Client	\checkmark
Open VPN Server	\checkmark
Open VPN Client	\checkmark
L2TP VPN Client	-
Parental Control	\checkmark
Protect TCP Flood Attacks	\checkmark
Protect ICMP Attacks	-
Protect UDP Flood Attacks	-



System	
Default Access/Password	192.168.110.1 No Password Required by Default
URL Access	\checkmark
Local Upgrade	\checkmark
Online Upgrade	\checkmark
APP Upgrade	\checkmark
Syslog	-
Backup	\checkmark
Factory Reset	\checkmark
Language	Chinese English Vietnamese Indonesian Thai Arabic Traditional Chinese Spanish Russian

Package Contents

Model	RG-EW1200G PRO
Wireless Router	1
Power Adapter	1
Quick Start Guide	1
Cat5E UTP Cable	1

Rujje Rcycc

Redefine your easy network

Copyright ©2000-2024 Ruijie Networks Co., Ltd. All rights reserved.

No part of this document may be reproduced or transmitted in any form or any means without prior written consent of Ruijie Networks Co., Ltd.

Notice

This content is applicable only to regions outside the China mainland. Ruijie Networks Co., Ltd. reserves the right to interpret this content.

The information contained herein is subject to change without notice. Nothing herein should be construed as constituting an additional warranty. Ruijie Networks Co., Ltd. shall not be liable for technical or editorial errors or omissions contained herein.



Ruijie Networks Co., Ltd. Website: https://reyee.ruijie.com/en-global