SATCO NUVO

Project Name

Location

Prepared By



SATCO S39392

36W/LED/HID/5000K/100-277V E26

Notes

www] 08-09-2021 01:41:2

Compliance

General	
Status	Active
Watts	36W
Incandescent Equivalent	200W
Fluorescent Equivalent	55W
HID Equivalent	150W
Volts	100V-277V
Shape	Corncob
Base	Medium
ANSI Base	E26
Finish	Clear
CCT (Kelvin)	5000
Temperature	Natural Light
CRI	80
Lumens	5148L
Beam Spread	300
Dimmable	Non-Dimmable
Hours Rated	50000
Lamp Type	Corncob
Technology	LED
Min Compartment Size	Length: 8.5 in. Width: 6 in. Depth: 6 in.
Ballasting Requirements	Ballast Bypass-Direct wire only 100-277V
Electrical	
Working Voltage	AC 90-305V
Working Voltage	AC 90-305V
Operating Frequency	50/60 Hz
Operating Frequency Power Factor	50/60 Hz >0.9
Operating Frequency Power Factor Burning Position	50/60 Hz >0.9 Universal
Operating Frequency Power Factor Burning Position Surge Protection	50/60 Hz >0.9 Universal Built-in surge protection - 4KV
Operating Frequency Power Factor Burning Position	50/60 Hz >0.9 Universal
Operating Frequency Power Factor Burning Position Surge Protection	50/60 Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to a maximum of +45C
Operating Frequency Power Factor Burning Position Surge Protection Operating Temperature	50/60 Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to a maximum of +45C
Operating Frequency Power Factor Burning Position Surge Protection Operating Temperature Physical	50/60 Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to a maximum of +45C (+113F)
Operating Frequency Power Factor Burning Position Surge Protection Operating Temperature Physical MOL	50/60 Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to a maximum of +45C (+113F) 7.34
Operating Frequency Power Factor Burning Position Surge Protection Operating Temperature Physical MOL MOD	50/60 Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to a maximum of +45C (+113F) 7.34 3.34
Operating Frequency Power Factor Burning Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish	50/60 Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to a maximum of +45C (+113F) 7.34 3.34 Clear
Operating Frequency Power Factor Burning Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material	50/60 Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to a maximum of +45C (+113F) 7.34 3.34 Clear Plastic
Operating Frequency Power Factor Burning Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color	50/60 Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to a maximum of +45C (+113F) 7.34 3.34 Clear Plastic White
Operating Frequency Power Factor Burning Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.)	50/60 Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to a maximum of +45C (+113F) 7.34 3.34 Clear Plastic White 1.52
Operating Frequency Power Factor Burning Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.)	50/60 Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to a maximum of +45C (+113F) 7.34 3.34 Clear Plastic White
Operating Frequency Power Factor Burning Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information	50/60 Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to a maximum of +45C (+113F) 7.34 3.34 Clear Plastic White 1.52 UL approved for totally enclosed fixtures; For outdoor & indoor use; Emits no UV light / Contains no
Operating Frequency Power Factor Burning Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information	50/60 Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to a maximum of +45C (+113F) 7.34 3.34 Clear Plastic White 1.52 UL approved for totally enclosed fixtures; For outdoor & indoor use; Emits no UV light / Contains no Mercury (Hg)
Operating Frequency Power Factor Burning Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Info	50/60 Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to a maximum of +45C (+113F) 7.34 3.34 Clear Plastic White 1.52 UL approved for totally enclosed fixtures; For outdoor & indoor use; Emits no UV light / Contains no Mercury (Hg) Yes

Safety Listing	cULus
Location Rating	Damp
Energy Star	No
California Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Lamp

Copyright 2020 Satco Products, Inc. All Rights Reserved

For More Information Visit: http://www.satco.com/







