

Part number

MFON 24.32



Hood, LS-TYPE series, with 4 pegs, M32 side cable entry without adapter, size "104.27", high construction

Product description

Product type	Hood
Series	LS-TYPE
Closing type	With 4 pegs
Size	Size 104.27
Cable entry	Side cable entry M32
Specification	High construction

Technical data

IP degree of protection IP65

Further technical details

Weight	236,00 g
Operating temperature range (min, max)	-40°C...+125°C

Material properties

Colour	RAL 9005 black
RoHs conformity	Compliant
China RoHs - EFUP	E
REACH SVHC substances	No

Approvals / Standards

Certifications	DNV, BV
UL	ECBT2
cUL	ECBT8

General ordering information

EAN13 code	8015747019330
eCl@ss 8.1	27440202
ETIM 7.0	EC000437

Packaging Information

Sub-packaging weight	1,18 kg
Sub-packaging description	Plastic packaging
Sub-packaging quantity	5 Pcs
Sub-packaging EAN barcode	8015747187756

Part number MFON 24.32



Catalogue drawings



Catalogue drawings

CH..N - MA, MF..N enclosures size "104.27" **LS-TYPE version**

inserts:	page	housings with double lever	hoods with 4 pegs
CD	64 poles + @ 51+53 *		
CT, CTS **)	64 poles + @ 57 *		
CDD	108 poles + @ 64+66 *		
CDE	46 poles + @ 83+85 *		
CSH	24 poles + @ 91+93 *		
CCE	24 poles + @ 100+104 *		
CNE, CSE, JCNE, JCSE	24 poles + @ 101 and 109 *		
CSS	24 poles + @ 122+123 *		
CTE, CTSE **)	24 poles + @ 129 *		
CMSE	10+2 (aux) poles + @ 139 *		
CMCE	10+2 (aux) poles + @ 138 *		
CX	4/8 poles + @ 155 *		
MIXO	6 modules 160+195 *		

insert centre distance: 104 x 27 mm
* refer to catalogue page CN.12

description	part no.	entry	part no.	entry
bulkhead mounting housing, with 2 levers	CHIN 24	M		
surface mounting housing, high construction, with 2 levers	MAPN 24.32	32		
with pegs, side entry			MHON 24.32	32
with pegs, side entry, high construction			MFON 24.32	32
with pegs, side entry			MHVN 24.32	32
with pegs, side entry, high construction			MFVN 24.32	32

**) only in the CHIN 24 enclosure

panel cut-out for bulkhead mounting housing in mm

- kiln powder coating with RAL 9005 black epoxy polyester powder
- RAL 9005 black self-extinguishing thermoplastic locking lever (spare lever page 12)

dimensions shown are not binding and may be changed without notice

dimensions in mm

CHIN 24

MAPN 24.32

dimensions in mm

MFON 24.32

MFVN 24.32

MHON 24.32

MHVN 24.32

Notes

Dimensions shown in mm are not binding and may be changed without notice.