

Features

Use: Indoor
 Type of installation: WALL, RECESSED INTO PLASTERBOARD, SUSPENDED, CEILING MOUNTED, TRACK
 Emission: DIRECT
 Optics: MICROPRISMATIZED
 Colour: CAFFE
 Dimming: ON/OFF
 Emergency: NO
 L: 589x589mm
 A: 53mm
 H: 69mm
 Made in: ITALY
 Warranty: 5 years
 Weight: 2.1kg

Tech data

Luminaire input power: 28.5W
 Luminaire luminous flux: 2355lm
 IP: 40
 Insulation class: I
 Supply voltage: 220-240V 50/60Hz
 UGR: <19
 SELV: Si

Source

Light source: LED
 Source power: 24W
 Colour temperature: 4000K
 CRI: >90
 Colour tolerance: 3 Step MacAdam
 LED lifespan: 50000h L80 B20

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012

Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.
 CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

Average luminance

Average luminance limits for DSE workstation 65°(in accordance to EN 12464-1:2012).

[View more product info](#)



COMPLETION ACCESSORIES

	HERO: MOD.CIECO 250 CAF	108676.20
	HERO: MOD.CIECO 1400 CAF	108680.20
	HERO: MOD.CIECO ANG.SX 150 CAF	108677.20
	HERO: MOD.CIECO 1680 CAF	108681.20
	HERO: MOD.CIECO ANG.DX 150 CAF	108678.20
	HERO: MOD.CIECO 1120 CAF	108679.20

MOUNTING ACCESSORIES

	HERO: SOSPL3000 1PZ. TESTA/CODA	108685.99
	KIT ALIMENTAZIONE L1200 3P CAF	108919.20
	KIT ALIMENTAZIONE L1200 3P BIA	108919.01
	HERO: SPESS. CARTONG. 10MM 2PZ.	108689.99
	HERO: SOSPL3000 1PZ. UNIONE	108686.99



HERO: STAFFA PARETE "L" CAF

108687.20



HERO: SOSP.L3000 1PZ TESTA W.G.ALTO

1086A1.99




KIT ALIMENTAZIONE L3000 3P BIA

108920.01



HERO: KIT INCASSO LED (1X)

108688.99



HERO: SOSP.L3000 1PZ UNIONE W.G.ALTO

1086A2.99



KIT ALIMENTAZIONE L3000 3P CAF

108920.20