

Fiche produit

Caractéristiques

7314129000

Vanne 3 voies bronze fileté PN16 DN15 Kv4



Principales

Valve product range	Venta
Type de produit ou équipement	Valve
Valve type	Globe
Valve product series	V341
Valve model	V341/15/4.0
Medium compatibility	Glycol 25 % Glycol 30 % Glycol 50 % Water
Valve configuration	3-Way
Valve connection type	G External
Valve connection size	G 1B
Pipe size	15 mm
Body size	15 mm (1/2 in)
Flow characteristic	Equal percentage
Flow coefficient	4.62 cv 4 kvs
Pressure class	PN16
Operating fluid temperature	-20... 150 °C
Control valve rangeability	Greater than 50:1
Stroke length	20 mm
Seat leakage	Port A: Less than 0.02 % of kvs (Ports A-AB) Port B: Less than 0.05 % of kvs (Ports B-AB)
Stem flow action	Stem up closes A and opens B to AB
Stem movement	Linear
Trim material	Stainless steel
Matière du corps	Bronze Rg5
Seat material	Port A: stainless steel AISI 303 Port B: stainless steel AISI 303
Stem material	Stainless steel AISI 303
Plug material	Stainless steel AISI 303
Stem seal material	EPDM (ethylene propylene diene monomer)
Seating seal material	Port A: metal to metal
Packing material	EPDM (ethylene propylene diene monomer)
Région cible	Europe Asie Pacifique Australia.

Packing Units

Type d'emballage 1	PCE
Nombre d'unité par paquet	1
Poids de l'emballage (Kg)	1,055 kg
Hauteur de l'emballage 1	5 cm
Largeur de l'emballage 1	10,5 cm
Longueur de l'emballage 1	18 cm

Offer Sustainability

Directive RoHS UE	Non applicable, en dehors du scope légal RoHS UE
Régulation RoHS Chine	Déclaration RoHS Pour La Chine
Profil environnemental	Profil Environnemental Du Produit

Garantie contractuelle

Garantie	18 mois
----------	---------